DOE/PC/90310--T10

DOE/PC/90310--T10

DE93 013072

QUARTERLY PROGRESS REPORT #9

TITLE: COMBUSTION OF DENSE STREAMS OF COAL PARTICLES

GRANT NO: De-FG-22-90PC90310

REPORT PERIOD: Aug. 29, 1992 to Nov. 28, 1992

PRINCIPAL INVESTIGATOR: Kalyan Annamalai
Mechanical Engineering
Texas A&M University
College Station, TX 77843-3123
409-845-2562

GRADUATE STUDENTS: C. Gopalakrishnan
E. Kharbat
X. Du

SUBMITTED TO: Pittsburgh Energy Tech. Center
US Department of Energy
P.O. Box 10940
Pittsburgh, PA 15236

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

Tasks for Aug. 29, 1992 to Nov. 28, 1992

1. Submit the part II of the invited review article to Prog. Energy and Comb. Sc.
2. Submit a topical report on " Digital Image Processing Applications in the Ignition and Combustion of Char/Coal Particles" .
3. Continue the experiments on combustion of dense streams.

Activities During Aug. 29, 1992 to Nov. 28, 1992

1. The part II of invited review on " Interactive Processes in Gasification and Combustion, Part II: Isolated Coal/Char particle, Arrays and Clouds," has been submitted to Prog. Energy and Combustion Science on Sep 25 and it is under review.
2. The topical report on "Digital Image Processing Applications in the Ignition and Combustion of Char/Coal Particles," has been mailed separately under book-post. The report is based on MS thesis of Mr. E. Kharbat. Enclosed please find a summary of significant findings in Section A enclosed with this progress report. A paper will be presented at Combustion Institute meeting in New Orleans [Mar 15-17, 1992] and a full length will be presented to journal after the meeting.
3. Experiments were also conducted on dense stream of coal particles. The digital image contours (or pixel contour; pixel value is proportional to luminosity) reveal a group flame; but it is also accompanied by flame islets due to a few of the particles detaching from the stream. In order to maintain same ambient temperature, the water cooled collection probe was positioned at about 3 cm above the flat flame. Ash tracer technique was used in obtaining the combustion (or gasification efficiency). Please find a brief summary of results in Section B.

Tasks for Nov. 29, 1992 to Feb. 28, 1992

1. Continue the parametric experiments on stream combustion: i) cloud denseness, ii) particle size, iii) gas temperature, iv) residence time, v) oxygen concentration.
2. Mr. Gopalakrishnan is expected to defend his MS thesis by May 1993. The MS thesis of Mr. Gopalakrishnan and a part of PhD theses of Mr. Du and Dr. William Ryan will constitute the final report on the project.

A. Summary of significant Findings obtained from Preliminary Array Studies.

Recently, investigators have employed new techniques and advanced computer technology to investigate the behavior of char/coal under combustion. Such techniques provided new concepts and insights in combustion science. A recent technique, digital image processing, is employed in this research study in order to visually investigate the ignition and combustion characteristics of isolated char/coal particles as well as the effect of interactive combustion in binary char/coal arrays. Experiments were also conducted on miniature isolated candles as well as two-candle arrays.

Results indicate that as the candle starts to burn, a flame is formed around its wick including a black inner zone possibly due to the formation of fuel rich zone. **Group flame is formed for the binary arrays at closer inter-candle spacing.** [Fig.A.1]. With increased inter-candle spacing for the two-candle arrays, the burn time first decreases and later increases [Fig.A.2].

Ignition of the high volatile isolated coal particles in vitiated environment seems to occur heterogeneously at the leading edge of the particle. **Volatiles are observed to be ejected upward as jets in the direction of the convective flow but only after heterogeneous ignition.** The volatiles burn in the gas phase homogeneously and form a wake flame; a black inner zone (unburned volatile) is formed (see Fig.A.3 for many common characteristics of isolated flames).

Intermittent volatile ignition and combustion are observed to occur during the combustion process for a few of the isolated particle combustion experiments on high volatile non-swelling coal. The medium volatile coal particles ignite faster than the high volatile coal; but the intermittent ignition is not observed. The low volatile isolated coal particles combust in shorter time. The isolated char particles ignite at the surface of the particle heterogeneously with little volatile ejected, yet are not sufficient to form a volatile flame, resulting in a subsequent heterogeneous combustion.

A group flame is formed for the two-particle arrays at closer interparticle spacing (Fig.A.4). Also, intermittent ignition does not occur for the high volatile particles when the two particles are at farther distances which suggests that radiation interaction between the particles might be occurring. However this conclusion is purely speculative. The char arrays experience heterogeneous ignition at the leading edge; combustion proceeds heterogeneously.

Figure A.1. The Burning Sequence for Two-Candle Array at $l/a = 6$ mm

**Figure A.2 Variation of 40% Burn Time with Inter-Candle Spacing
for Candle Arrays**

Figure A-3 A Typical Sketch of Combustion of Isolated Coal Particle in
Vitiated Environment

Figure A-4. Ignition and Combustion Sequence for Large High Volatile
Coal Two-Particle Array ($l = 4.86$ mm)

B. COAL STREAM COMBUSTION

Introduction:

The objective is to study the group combustion of a stream of particles in a hot environment. In the past, conventional laminar flow reactor with gravity assisted injection system was used to study the ignition of coal particles. However, difficulties were experienced in viewing the flame since quartz window was deposited with coal dust. Hence, a flat flame burner with fluidized feeder and image processing equipment was used for the current experiments. A water cooled sampling probe was used for collecting the burnt samples.. This report explains the initial experimental details and the preliminary results obtained for the first two trial exercises.

Experimental Setup:

The construction of flat flame burner and its experimental set up were explained in the reports#5&6. The coal feeding arrangement is briefly discussed here(Fig 1). A locally fluidized feeder is loaded with moisture free coal particles. The feeder has provisions for pressurization and exhaust air flows at the top. A off take system is fitted at the bottom. This offtake system has a 1.5mm transfer tube to carry coal particles. It also has dilution and fluidization air lines. Dilution air is used to flush out the coal particles in the transfer tube. A curled up wire is inserted in the feeder to prevent the coal lump moving up when sleeve/dilution air is supplied. This coal off take system and the flat flame burner coal feeding tube are connected by a stainless steel tube with pvc joints at the ends. As shown in Fig#1, the coal particles have to travel upwards against gravity into the hot ambience provided by the flat flame(methane+ air mix). Coal particle agglomeration in the passage is prevented by drying the particles in the furnace. Further a DC power operated buzzer vibrator strapped near the off take system on the feeder is also used. This ensures a smooth flow of coal particles for a short period of time. The flowing burnt particles are then collected at the collection probe. The burnt samples are collected from the probe and as well from the beaker and sent for further analysis.

Experimental procedure:

First, the cooling water circuit of the burner is activated. Air and methane flows are then started in proportion to have a steady flat flame at the burner with 10% oxygen concentration in the vitiated products. This 10% oxygen concentration is verified with ZrO_2 analyzer. The shroud N_2 flow is then started. The particle collection system is made active by switching on the vacuum pump. The vacuum at the collection beaker is adjusted with the use of U tube manometer. The sampling probe and the beaker are thoroughly cleaned to ensure collection of pure sample. The temperature is measured to be around 1200 K.(report# 7)

FIG 1.COAL FEEDER SET UP

The coal feeding procedure is initiated by sending the dilution air @8scfh to flush the coal passage tube. Then pressurization and sleeve air flows are adjusted to get a bed pressure around 1.5"Hg. With this arrangement, when the buzzer vibrator is powered, coal particles started flowing. Simultaneously, the digital balance readings are recorded through a computer for the later use of mass flow rate calculations. Since the gap between the particle collection system and particle injector at the burner is fixed at 3cm, the residence time available for the coal particles depends on particle velocity. The particles release volatiles and establish flame. The burnt particles get deposited on the collection tube wall and in the beaker. When the particles flow steadily, a Digital camera CID2250 is used to capture images of the flames at different time intervals. These flame images can later be processed for finding flame boundary, flame location and the velocity of particles. The burnt particle samples are then sent for proximate analysis to determine ash percentage. In all the cases, furnace dried coal is only used to reduce the moisture.

Result Description:

The coal used for the experiments is PSOC-1336(64 micron size). It has 14.23%ash, 33.09%volatile and 52.68%C on dry basis. Two trial experiments were conducted, the details of which are tabulated below.

	trial 1	trial 2
coal type	PSOC 1336	PSOC 1336
dilution air	7 scfh	7 scfh
fluidization air	7.5 scfh	6 scfh
pressurization	8 scfh	8 scfh
exhaust	0 scfh	0 scfh
mass flow rate	0.07g/sec	0.0157g/sec
A:F ratio	2.9(dense)	12.3(dilute)
cold flow vel (by flowrate)	56.4 m/s	52.6 m/s
l/a ratio	23.9	38.4
Ash % bef exp	13.865	13.865
Ash % aft exp	15.66	16.405
gasi. eff (η_p)	0.1331	0.1798

The gasification efficiencies are calculated using ash Ash tracer technique. There are two effects: Reduction in gasification % with dense flow is due to (i) dense cloud effects (ii) velocity effects. Clearly , estimated coal flow velocity is approximately same in both the cases. Since air flows are similar, residence time is expected to be similar. Dense stream has lower gasification efficiency. Assuming that stream 2 is very dilute, the gasification corresponds to isolated particle burn rate. Therefore stream 1

$t = 0\text{ms}$

$t = 33\text{ms}$

$t = 66\text{ms}$

$t = 99\text{ms}$

fig2. Four consequent frame images.

which is dense burns at 70% of isolated burn rate. Measuring particle velocity directly using digital images is in progress. The above results can be discussed only with the knowledge of particle flow velocity. In both the cases, the reaction zone height is maintained at 3 cm. Though the air flow rate is approximately same, the mass flow rate is quite different resulting in extreme air fuel ratios. The four consecutive flame images are presented in the figure2. The brightening of the images were quantified in terms of pixel values. Higher the brightness, higher is the pixel value. Since there is no flame far away from the center, the pixel values are low. However as one approaches the stream radially, the pixel value suddenly increases at the outer boundary of the flame. The boundary morphological operation of the image software detects the increase in pixel value and gives the flame boundary contours as shown in Fig 2. The boundaries look similar for all the 4 images. There are also "flame isolets" due to isolated particles detached from the stream either due to jet action of volatiles or the disturbance in the coal flow. It is also seen clearly from fig 3 that there is intense outer flame indicative of group flame with a central dark zone as represented by two peaks for flame left and right peripheries and a central depression for dark coal stream. This plot shows variation in pixel values as one moves from left to right and at different distances from the burner. The pixel values near the center did not indicate any other flame at the center while the model predicts double flame for a short duration. Further experiments are in progress.

fig 3

END

DATE
FILMED

6 / 4 / 93