QTR #10

DOE/PC/90756--T11

DOE/PC/90756--T11

DE93 003898

**Research on Thermophoretic and Inertial Aspects of Ash
Particle Deposition on Heat Exchanger Surfaces in
Coal-Fired Equipment**

Daniel E. Rosner
Principal Investigator

High Temperature Chemical Reaction Engineering Laboratory
Yale University, Department of Chemical Engineering
New Haven, CT 06520 U.S.A.

Quarterly Technical Report on: DE-FG22-86 PC 90756

Total Contract Period: 9/1/86 - 8/31/89

Quarterly Period Covered: 12/1/88 - 2/28/89

Attention: **James D. Hickerson (COTR)**

U.S. Department of Energy
Pittsburgh Energy Technology Center
Cochran Mill Road
P.O. Box 10940
Pittsburgh, PA 15236

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

MASTER

1. Introduction

DOE-PETC initiated at the Yale HTCRE Laboratory a systematic three-year experimental and theoretical research program directed toward providing engineers with the data, methods, and rational correlations needed to improve the generality and accuracy of prediction of inorganic particle *deposition rates* under typical coal combustion conditions (*i.e.*, those leading to the importance of thermophoretically-enhanced diffusion (submicron mode) and the inertially-enhanced "impaction" (supermicron mode), often in the presence of simultaneous alkali salt vapor condensation. After a brief statement of objectives (Section 2) we outline our experimental and theoretical progress during this quarterly reporting period (Section 3), with our results summarized in the references documented in Section 5 and Appendix A. Section 4 gives relevant administrative information (personnel, research plans).

2. Background Statement: Objectives

The goal of our research in the area of ash *transport* is to advance the capability of making reliable engineering predictions of the dynamics of net deposit growth for surfaces exposed to the products of coal combustion. To accomplish this for a wide variety of combustor types, coal types, and operating conditions, this capability must be based on a quantitative understanding of each of the important mechanisms of mineral matter transport, as well as the nature of the interactions between these substances and the prevailing "fireside" surface of the deposit. This level of understanding and predictive capability could ultimately be translated into very significant cost reductions for coal-fired equipment design, development and operation.

Our emphasis in the present program: "Research on Thermophoretic and Inertial Aspects of Ash Particle Deposition on Heat Exchanger Surfaces in Coal-Fired Equipment" is on developing and experimentally validating* rational, theoretical methods of predicting the role of *inertia* and ash particle *thermophoresis* in determining net deposition rates (see, *e.g.*, Rosner, 1985; 1986). We also wish to quantify how simultaneous *vapor* deposition (*e.g.*, alkali sulfate) can influence the sticking and erosion associated with impacting particles. Specifically, as a result of this DOE-PETC supported program, we believe that it will be possible for us to develop:

- a. An understanding of the factors governing impacting particle capture and deposit erosion probabilities, leading to rational correlations (see, *e.g.*, Rosner and Nagarajan, 1987).
- b. Ways of applying recent *mass* transfer theories (developed for idealized geometries) and available *heat* and *momentum* transfer data to develop prediction methods for important practical situations — *eg.* deep tube bundles ('banks') (see, *eg.*, Rosner, 1986).

* Our previous DOE-METC supported experiments have been confined to vapor and submicron particle systems in the absence of inertial phenomena. For an overview of convective mass transfer, see the PI's recent textbook (Rosner, 1986, 1988), especially Chapters 6, 8.

- c. Necessary extensions of available particle deposition rate theory (see, e.g., Park and Rosner, 1988).
- d. Useful, yet rational, correlations to generalize the results of actual or numerical experiments and make them suitable for engineering design calculations (Israel and Rosner, 1983; Wessel and Righi, 1988).

To develop tractable but realistic/rational 'subroutines' for predicting the evolution of wall deposits, we also have intensified communication with more empirically oriented engineers/chemists who have the necessary boiler fouling/slugging experience. Thus, we should ultimately be able to recommend economical 'subroutines' (compatible with practical requirements of global computer codes, recent deposition research results and cumulative empirical observations) to predict the evolution of wall deposits for, say, design studies of coal-fired furnaces and boilers (see, e.g., Gokoglu and Rosner, 1984; and, also, Appendix A3).

3. Research Progress

Our most recent results can be conveniently divided into the following five sub-areas:

3.1 *Experimental Studies of Particle Deposition in the Simultaneous Presence of Inertia and Thermophoretic Effects*

We have developed a Single Particle Counter (SPC) with Transit Time Velocimeter (TTV), (Holve *et al.*, 1981; Holve, 1982) capabilities, which is presently being tested with our seeded (C_3H_8 /air) microcombustor to obtain more precise measurements of particle concentrations and velocities (Figure 1). To interpret the particle deposition rate trends reported in our previous QTR's (effect of particle inertia on thermophoretic deposition rates) a theoretical model is under development, based on the approach of Fernandez de la Mora and Rosner (1981) (see, also, Appendix A3). In addition, we are examining rational theories of particle sticking upon impaction and the effects of liquid layers on particle capture (see, eg. Rosner and Nagarajan, 1987, for relevant background information). We intend to resume our experimental study of this phenomenon as soon as a new multiple-target holder with its ancillary instrumentation (cooling probes, temperature sensors, etc.) is constructed, to allow for a sufficient number of samples to be collected for SEM and/or Atomic Absorption (AA) analysis.

Figure 1: SPC and TTV set-up

3.2 Relation between Deposit Microstructure and Particle Deposition Mechanism

Our AIChE J. paper (Tassopoulos *et al.*, 1989) on deposit *microstructures* resulting from various particle deposition *mechanisms* has been extended (see QTR#9) and accepted for publication in mid-1989. In the immediate future our attention will be focused on predicting the relevant *thermophysical properties* of such deposits: eg. effective thermal conductivity and effective vapor diffusivity. Further work is also being done on the nature of deposits grown from mainstream particles which are non-uniform in size — work which is being closely coordinated with that described in Section 3.3. below. Our longer range goals are to examine details of the incident particle sticking 'sub-model' (which will require iterative comparisons with laboratory deposit microstructures) and, ultimately, also develop rational methods for predicting deposit evolution in response to sintering.

3.3 Theory of Particle Deposition from 'Polydispersed' Aerosols

We have extended the theory of total mass deposition rates from "coagulation-aged" particle size distributions (Rosner, 1989) to allow for log-normal particle populations of arbitrary spread and multiple deposition mechanisms (Rosner and Tassopoulos, 1989, Appendix A1). Our methods provide immediate relations between actual mass deposition rates and deposition rates if all particles had the mean particle volume ϕ_p/N_p , where ϕ_p is the particle total volume fraction. As a by-product they provide computationally efficient 'finite-analytic' algorithms for predicting deposition rates from arbitrary population distributions with arbitrary capture efficiency characteristics. Illustrative examples (eg. convective diffusion + inertial impaction on a circular cylinder in crossflow) are included in Section 4.2 of Rosner and Tassopoulos (1989).

3.4 Application of Counterflow Diffusion Flames to the Determination of Particle Thermophoretic Diffusivities

Preliminary results have been obtained on the thickness of the (thermophoretically-induced) particle-free zone in counterflow diffusion flames using either N_2 or He as 'diluent'. These data are now being analyzed to compare the dependence of the inferred thermophoretic diffusivity $(\alpha_T D)_p$ of TiO_2 -particles on the momentum diffusivity of the host gas with that expected from the Waldmann kinetic theory (see, eg. Garcia-Ybarra and Rosner, 1989). Our goal is to assess the accuracy of this theoretical approach for predicting the thermophoretic diffusivities of important inorganic particulate matter in combustion systems.

3.5 Role of Photophoresis in Combustors with High Radiative Heat Fluxes

Our extended manuscript on photophoretic particle transport across laminar boundary layers (Castillo, Mackowski and Rosner, 1989) has led us to the following interesting conclusions:

- C1. For intermediate size absorbing particles the recent *photophoretic* predictions of Mackowski (1989) lead us to expect a noticeable (*ca* 10 percent) increase in particle deposition rates to heat exchanger surfaces exposed to incident radiative fluxes comparable to 'convective' - (local conductive-) fluxes.
- C2. Generalized (dimensionless-) deposition rate predictions have been made of the photophoretically modified (augmented or reduced) deposition rate of particles from forced convection laminar non-isothermal boundary layers. Explicitly treated are ('intermediate'-size) particles for which $v/D_p \gg 1$ and yet *inertia* is negligible

(sufficiently subcritical Stokes numbers; see, e.g. Fernandez de la Mora and Rosner, 1982; see, also C5.).

- C3. Radiative energy fluxes can cause appreciable deposition rate reductions for strongly absorbing (char-like) particles if the radiation flux is directed away from the deposition surface, or, modest reductions for sufficiently small weakly absorbing (ash-like) particles if the radiation flux is directed toward the deposition surface. (The latter effect is due to the 'rearward' radiative heating of such partially 'transparent' particles).
- C4. Even at the radiative/conductive flux ratios achieved in ordinary engineering practice (in, say, pulverized coal power stations and furnaces) photophoretic deposition effects are expected to be negligible for very small particles (say, $d_p < 1 \mu\text{m}$) and for particles large enough to be strongly influenced by their inertia (say, $d_p > 10 \mu\text{m}$). The effects for intermediate size particles are also diminished if the particles are highly thermally conductive.
- C5. An 'additive suction velocity' scheme for conveniently calculating/correlating particle deposition rates in flow systems under the simultaneous influence of several mechanisms, currently under development at this laboratory (Gokoglu and Rosner, 1984; Rosner *et al.*, 1981) successfully describes the present high Sc laminar boundary layer-results for all q_R/q_F -ratios of current practical interest.
- C6. Size- and wavelength-dependent photophoretic control of the local deposition rate of (partially) absorbing particles from hot 'dusty' gases could be exploited using intense laser sources, perhaps for research purposes.

We are now examining the consequences of particle asymmetry (eg. in gas/solid momentum accommodation coefficient) for particle transport (effective Brownian diffusion coefficient) and Brownian-induced coagulation rates. An abstract describing our preliminary ideas (Mackowski and Rosner, 1989) has been prepared for the forthcoming Fine Particle Society Meeting (8/89, Boston, MA; see Appendix A2)

4. Administrative Information

Based, in part, on this DOE-PETC-supported program at Yale during this reporting period:

- 4.1 the following relevant papers have appeared in print: Park and Rosner (1989a), Rosner (1989), Garcia-Ybarra and Rosner (1989), and Castillo and Rosner (1989).

We also became aware of the paper by H.C. Wang (1986) which, together with Wessel and Righi (1988), further demonstrates the utility of our 'effective Stokes number' correlation ideas (Israel and Rosner, 1983) in the context of inertial particle (impaction) on a circular cylinder in subsonic dusty gas crossflow.

- 4.2 The following papers have been revised and re-submitted for final archival publication: Park and Rosner (1989b), Park and Rosner (1989c), Park and Rosner (1989d), Tassopoulos, O'Brien and Rosner (1989), Castillo, Mackowski and Rosner (1989).

During the next reporting period, we anticipate completing and submitting Liang *et al.* (1989), Labowsky and Rosner (1989), Rosner and Günes (1989). Work has also been initiated on the thermophoretic 'scavenging' of small particles by large particles/droplets (Mackowski and Rosner, 1989) and our follow-on proposal to DOE-PETC. D.

Mackowski will also present our recent photophoretic transport studies at the ACS Symposium (Session on Ash Deposition, April 9-14, 1989, Dallas, TX).

Participants in this comprehensive research program on particle deposition from combustion gases include the writer-P.I. (D. E. Rosner), Graduate Students A. Konstandopoulos, M. Tassopoulos and P. Yaras, and Drs. J.L. Castillo, P. Garcia-Ybarra, A. Gomez, D. Mackowski, and Y. Sun.

5. References

Castillo, J.L. and Rosner, D.E., "Theory of Surface Deposition from a Binary Dilute Vapor-Containing Stream, Allowing for Equilibrium Condensation within the Laminar Boundary Layer", *Int. J. Multiphase Flow*, **15**, [1], 97-118(1989)

Castillo, J.L., Mackowski, D., and Rosner, D.E., "Photophoretic Contribution to the Transport of Absorbing Particles across Combustion Gas Boundary Layers", to be presented at Symposium on Ash Deposition, ACS Mtg., Div. Fuel Chem., April 9-14, 1988, Dallas TX.

Fernandez de la Mora, J., and Rosner, D.E., "Effects of Inertia on the Diffusional Deposition of Small Particles to Spheres and Cylinders at Low Reynolds Numbers", *J. Fluid Mech.*, **125**, 379-395 (1982).

Garcia-Ybarra, P., and Rosner, D.E., "Thermophoretic Properties of Nonspherical Particles and Large Molecules", *AIChE J.*, **35**, [1], 139-147 (1989)

Gökoğlu, S.A., and Rosner, D.E., "Correlation of Thermophoretically-Modified Small Particle Diffusional Deposition Rates in Forced Convection Systems with Variable Properties, Transpiration Cooling and/or Viscous Dissipation", *Int. J. Heat and Mass Transfer* **27**, 639-645 (1984)

Gomez, A., Smooke, M.D. and Rosner, D.E., "Application of Counterflow Diffusion Flames to the Determination of Particle Thermophoretic Diffusivities", presented at the 22nd Int. Combustion Symp. August 1988, Seattle, WA.

Holve, D.J., Tichenor, D., Wang, J. C.F., and Hardesty, D.R., "Design Criteria and Recent Developments of Optical Single Particle Counters for Fossil Fuel Systems", *Opt. Engrg.*, **20** (4), 529-539 (1981).

Holve, D.J., "Transit Timing Velocimetry (TTV) for Two-Phase Reacting Flows", *Comb. and Flame*, **48**, 105-108, (1982).

Israel, R. and Rosner, D.E., "Use of a Generalized Stokes Number to Determine the Aerodynamic Capture Efficiency of Non-Stokesian Particles from a Compressible Gas Flow", *Aerosol Sci. & Tech.* (J. of Amer. Assoc. Aerosol Res.) **2**, 45-51 (1983)

Konstandopoulos, A.G., Goldman, Y. and Rosner, D.E., "Experimental Studies of Inorganic Particle-Laden High Temperature/Velocity Jet Impingement at Collecting Surfaces; Sticking and Deposit Erosion in the Simultaneous Presence of Condensing Alkali Sulfate Vapors", presented at the 18th Annual Meeting of the Fine Particle Society, Symposium on Multiphase Flow, Boston, MA 8/3-7/1987 (in preparation, 1989)

Konstandopoulos, A.G., Goldman, Y. and Rosner, D.E., "Experimental and Theoretical Studies of the Combined Effects of Particle Inertia and Thermophoresis on Deposition Rates across Laminar Combustion Gas Boundary Layers" (in preparation, 1989)

Labowsky M. and Rosner D.E., "The Method of Line Source Images for Solving Interacting Cylinder Diffusion Problems", *I.J.H.M.T.* (in press, 1989)

Liang B., Gomez A., Castillo J. and Rosner D.E., "Experimental Studies of Nucleation Phenomena within Thermal Boundary Layers — Influence of Chemical Vapor Deposition Rate Processes", Paper A5A, 1987 Annual Mtg. of the Amer. Assoc. of Aerosol Research; *Chem. Engrg Communications* (in press, 1989)

Mackowski, D., "Photophoresis of Aerosol Particles in the Free Molecular and Slip-Flow Regimes", *Int. J. Heat Mass Transfer* (in press, 1989)

Mackowski, D. and Rosner, D.E., "Photophoretic Motion of Non-Uniform Particles", Prepared for presentation at the 20th Annual meeting of the Fine Particle Society, Boston, MA, 22-26 August 1989

Park, H.M. and Rosner, D.E., "Multiphase Continuum Theory of Dopant Redistribution Across Aerosol-Laden Laminar NonIsothermal Boundary Layers" *Chemical Engrg. Science*, 44 [3] 603-617 (1989a)

Park, H.M. and Rosner, D.E., "Combined Inertial and Thermophoretic Effects on Particle Deposition Rates in Highly Loaded Dusty Gas Systems", *Chemical Engrg. Science*, (in press, 1989b)

Park, H.M. and Rosner, D.E., "Effect of Coagulation in the Boundary Layer on the Size Distribution of Thermophoretically Deposited Particles", *Chem. Engrg. Science* (in press, 1989c)

Park, H.M. and Rosner, D.E., "Thermophoretically Induced Phase-Separation in Highly Masss-Loaded 'Dusty' Gas Mixtures", HTCRe Laboratory, May 1987 , *AIChE J.* (submitted, 1989d)

Rosner, D.E., "Mass Transfer across Combustion Gas Thermal Boundary Layers — Power Production and Materials Processing Implications", in *Heat Transfer in Fire and Combustion Systems*, HTD 45, ASME, NY-NY, 3-8 (1985)

Rosner, D.E., *Transport Processes in Chemically Reacting Flow Systems*, Butterworths, Stoneham, MA (1986); Second Printing, 1988

Rosner, D.E., "Total Mass Deposition Rates from 'Polydispersed' Aerosols"; *AIChE J.* 35, [1], 164-167 (1989)

Rosner D.E. and Günes D., "Theory of Deposit Shape Evolution for Heat Exchanger Surfaces Exposed to the Flow of Fly-Ash Containing Combustion Products", in preparation, (1989)

Rosner D.E., Israel R. and Zydney A., "Effect of Thermophoresis of the Minimum Aerosol Diffusional Deposition Rate before the Onset of Inertial Impaction", presented at the *ACS/ EC-81 Winter Symposium on Aerosol Systems*, Tucson, AZ, 26-28 (1981)

Rosner, D.E., and Kim, S.S., "Optical Experiments on Thermophoretically Augmented Submicron Particle Deposition from 'Dusty' High Temperature Gas Flows", *The Chemical Engrg. J.* (Elsevier) **29**, No.3, 147-157 (1984)

Rosner, D.E., and Nagarajan, R., "Toward a Mechanistic Theory of Deposit Growth from Ash-Laden Flowing Combustion Gases: Self-Regulated Sticking of Impacting Particles and Deposit Erosion in the Presence of Vapor 'Glue'", in *AIChE Symposium Series 83*, No.257, **Heat Transfer-Pittsburgh 1987** (R.W. Lyckowski, ed.) 289-296 (1987)

Rosner D.E. and Park H.M., "Thermophoretically Augmented Mass, Momentum and Energy Transfer Rates in High Particle Mass-Loaded Laminar Forced Convection Systems", *Chem. Engrg. Science* **43**, [10], 2689-2704 (1988)

Rosner D.E. and Tassopoulos M., "Mass Deposition Rates from Streams Containing 'Polydispersed' Particle Populations of Arbitrary Spread", to be presented at the AIChE Annual Meeting, Session on *Fundamentals of Mass Transport*, San Fransisco, November 6-10, 1989; *AIChE J.* (submitted, 1989)

Tassopoulos, M., O'Brien, J.A., and Rosner, D.E., "Theoretical Approach to Establish Particle Deposition Mechanism/Deposit Microstructure Relationships", Paper 28f, 1988 Annual AIChE Mtg., Session 28 on *Fundamental Research in Heat and Mass Transfer in Two and Three Phase Systems* (Washington D.C., Nov.27-Dec.2, 1988); *AIChE J.* (in press, 1989)

Wang H.C., "Theoretical Adhesive Efficiency for Particles Impacting a Cylinder at High Reynolds Number", *J. Aerosol Sci.* **17** [5] 827-837 (1986)

Wessel, R.A and Righi, J., " Generalized Correlations for Inertial Impaction of Particles on a Circular Cylinder", *Aerosol Sci.and Tech.* (J. of Amer. Assoc. Aerosol Res.) **9**, No. 1, 29-60 (1988)

Appendices:

A1: Rosner and Tassopoulos (1989)

A2: Mackowski and Rosner - Fine Particle Society Mtg (1989)

A3: Park and Rosner (1989)

Mass Deposition Rates from Streams Containing "Polydispersed" Particle Populations of Arbitrary Spread*

Daniel E. Rosner† and Menelaos Tassopoulos‡

Yale University, Department of Chemical Engineering
High Temperature Chemical Reaction Engineering Laboratory
New Haven, CT 06520, U.S.A.

Abstract

It is shown that for particle deposition from log-normal polydispersed aerosol streams by one or more of several mechanisms (convective-diffusion, eddy impaction, ...) there are useful relations between actual total mass deposition rates and the reference deposition rate one would calculate by imagining that all particles in the mainstream population had the average particle volume $\bar{v}$ ($= \phi_p/N_p$). To facilitate engineering calculations of total mass deposition rates from (ubiquitous) polydispersed aerosols these relations are established and illustrated for diffusion- or inertial-mechanisms for laminar- or turbulent-boundary layers, free molecular (Knudsen-) diffusion or continuum (Stokes-Einstein-) diffusion at high Peclet numbers of dense spherical particles or fractal agglomerates. In each of these cases the mainstream particle size (volume) distribution is considered to be log-normal with an arbitrary "spread"-parameter, thereby generalizing earlier results for "coagulation-aged" (self-preserving) distributions. Further generalizations to include transitions between important particle transport mechanisms, and aerosol particle size distributions which can be represented as *sums* of log-normal distributions are outlined, opening the way to efficient, finite-analytic methods for predicting mass deposition rates for arbitrary size-dependent particle capture efficiencies (or mass transfer Stanton numbers, $St_m(v)$) and for particle size distributions of arbitrary shape.

*Research supported, in part, by the US Department of Energy-Pittsburgh Energy Technology Laboratories, under Grant No. DE-FG22-86PC90756 and the US Air Force Office of Scientific Research, under Grant No. AFOSR-84-0034. Prepared for the 1989 AIChE National Annual Meeting and AIChE J., DER#172

†Professor of Chemical Engineering; Director, Yale HTCRE Laboratory; to whom inquiries concerning this paper should be directed.

‡Graduate Research Assistant, HTCRE Laboratory, Yale University, Chemical Engineering Department.

Combined Inertial and Thermophoretic Effects on Particle Deposition Rates in Highly Loaded Dusty Gas Systems ^a

H.M. PARK^b and D. E. ROSNER^c

Yale University, Department of Chemical Engineering
High Temperature Chemical Reaction Engineering Laboratory
New Haven, CT 06520, U.S.A.

ABSTRACT

Little is yet known (theoretically or experimentally) about the simultaneous effects of particle inertia, particle thermophoresis and high mass loading on the important engineering problem of predicting deposition rates from flowing 'dusty' gases. For this reason, we investigate the motion of particles present at nonnegligible mass loading in a flowing non-isothermal gaseous medium and their deposition on strongly cooled or heated solid objects by examining the instructive case of steady axisymmetric 'dusty gas' flow between two infinite disks: an inlet (porous) disk and the impermeable 'target' disk — a flow not unlike that encountered in recent seeded-flame experiments. Since this stagnation flow/geometry admits interesting self-similar solutions at all Reynolds numbers, we are able to predict laminar flow mass-, momentum- and energy-transfer rate coefficients over a wide range of particle mass loadings, dimensionless particle relaxation times (Stokes numbers), dimensionless thermophoretic diffusivities, and gas Reynolds numbers. As a by-product, we illustrate the accuracy and possible improvement of our previous 'diffusion model' for tightly coupled dusty gas systems (Rosner and Park, 1988, Park and Rosner, 1988). Moreover, we report new results illustrating the dependence of the important 'critical' Stokes number (for incipient particle impaction) on particle mass loading and wall/gas temperature ratio for dust-laden gas motion towards 'overheated' solid surfaces. The present formulation and resulting transport coefficients should not only be useful in explaining/predicting recent deposition rate trends in 'seeded' flame experiments, but also highly mass-loaded systems of technological interest, such as the deposition of opto-electronic materials by jet impingement, and fouling layers from ash-laden fossil fuel combustion products.

^a Originally submitted March 1987 to Chemical Engineering Science (Pergamon); Research supported, in part, by the U.S. Air Force Office of Scientific Research (Grant 84-0034) and DOE-PETC (Grant DE-FG22-86PC90756), based, in part, on H.M. Park Ph.D. Dissertation (Yale University, Department of Chemical Engineering, 1987), DER#161

^b Graduate Research Assistant, Yale University, HTCRES Laboratory; present address: Brown University, Center for Fluid Mechanics, Providence, RI 02912.

^c Director, HTCRES Laboratory; Professor, Chemical Engineering Department, Yale University; Author to whom all correspondence concerning this paper should be directed.

PHOTOPHORETIC MOTION OF NON-UNIFORM PARTICLES^aDaniel W. Mackowski^b and Daniel E. Rosner^c

High Temperature Chemical Reaction Engineering Laboratory

Chemical Engineering Department, Yale University, New Haven, CT 06520 (USA)

ABSTRACT

Radiation is often the dominant form of energy transfer in large-scale fossil-fuel-fired power stations and industrial furnaces. Consequently, an understanding of the photophoretic motion of absorbing aerosol particles in high-intensity thermal radiation fields is essential in order to predict accurately the behavior of combustion-generated particles, including coagulation rates and deposition rates. A recent analysis for spherical, homogeneous particles of intermediate size (too small to inertially impact; too large to have an appreciable Brownian diffusivity) has indicated that photophoresis can be an important contributor to the transport of such particles across combustion-gas boundary layers¹. Combustion-generated particles, however, are frequently asymmetric in shape and non-homogeneous in physical structure and chemical composition — characteristics which are expected to influence their dynamics, especially when such particles are hotter or colder than the surrounding gas. Accordingly, we have initiated investigations of the transport effects of non-uniformities upon the photophoretic behavior of particles in the slip-flow regime. To incorporate the asymmetrical nature of the problem, and yet retain mathematical tractability, the particle is first modelled as an 'equivalent' sphere with surface properties (thermal and momentum accommodation coefficients) that vary across the particle surface. Our preliminary results indicate that, in a host gas, nonuniform surface properties can lead to a body-fixed force considerably greater than the force arising from nonuniform absorption of radiation within an aerosol particle (i.e., 'conventional' photophoresis). When external, space-fixed forces do not act to align the particle in a particular direction, the stochastic motion resulting from the body-fixed force can lead to an appreciable increase in the effective Brownian diffusivity of such particles, with important implications for coagulation and deposition (capture) rates.

^a Prepared for presentation at the 20th Annual meeting of the Fine Particle Society, Boston, MA, 22-26 August 1989; Supported, in part, by Grants DE-FG22-86PC 90756 (DOE-PETC) and 89-0223 (AFOSR), and the Yale-HTCRE Laboratory Industrial Affiliates.

^b Postdoctoral Research Associate, HTCRES Laboratory, Chemical Engineering, Yale University

^c Professor, Chemical Engineering, Yale University; Director, Yale HTCRES Laboratory

¹ Castillo, J.L., Mackowski D.W., and Rosner D.E., "Photophoretic Modification of the Transport of Absorbing Particles Across Combustion Gas Boundary Layers", 197th Annual ACS Mtg., Symposium on Ash Deposition, Dallas, TX 9-14 April 1989.

END

**DATE
FILMED**

12 / 30 / 92