JAN 13

DOE/PC/91041--T5

PRECONVERSION PROCESSING OF BITUMINOUS COALS
- NEW DIRECTIONS TO IMPROVED DIRECT CATALYTIC COAL LIQUEFACTION-
DOE Contract No. DE-AC22-91PC91041

Quarterly Report
(10/01/92-12/31/92)

DOE/PC/91041--T5
DE93 008093

Prepared for

U.S. Department of Energy
Pittsburgh Energy Technology Center
P.O. Box 10940
Pittsburgh, PA 15236

January, 1993

Viking Systems International
2070 William Pitt Way
Pittsburgh, PA 15238

MASTER

"US/DOE Patent Clearance is not required prior to the publication of this document"

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

JP

TABLE OF CONTENTS

	Page
Introduction	1
Experimental	4
Results and Discussion	7
Coal dissolution and liquefaction	7
Coal fractions and liquefaction	11
The associated molecular nature and liquefaction	12
Conciusion	16
References	16

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

RECEIVED
JUL 01 1983
OSTI

LIST OF FIGURES

FIGURE	Page
1 Effect of soaking before liquefaction on coal conversion	8
2 Effect of soaking temperature on extractability	9
3 Effect of step-wise soaking on extractability	10
4 Coal fractions and their conversion	13
5 Block diagram of the proposed coal liquefaction procedure	14
6 Coal conversion by the proposed procedure for a high-volatile ... bituminous coal and a subbituminous coal	17

SCHEME

1 Mass balance for Runs 20 and 22	18
---	----

LIST OF TABLES

TABLE	Page
1 Elemental analyses of coals and a coal liquid used	4
2 Run numbers and experimental conditions	5
3 Gas composition obtained from liquefaction	15

INTRODUCTION

Coal structure should be well understood for the effective development of coal liquefaction. A cross-linked three-dimensional macromolecular model has been widely accepted for the structure of coal. Current coal liquefaction technology are being developed based on this model. Recent studies, however, showed that significant portions (far more than generally believed) of coal molecules are physically associated¹. Therefore, care should be used in the development of a coal liquefaction process. If physical association is dominant, all properties and reactivities in coal liquefaction must be a strong function of intra- and intermolecular (secondary) interactions and molecular weight.

Our recent work^{2,7} demonstrated the significance and importance of relatively strong secondary interactions in all ranks of coal. Relatively strong secondary interactions include ionic forces, the charge-transfer interaction and the so-called π - π interaction⁸. It is thought that dissolution of these relatively strong secondary interactions is the essential step for effective coal liquefaction. The dissolution of physical associations with relatively strong secondary interactions should be considered before breaking covalent bonds in liquefaction. However, some portions of these interactions are not solvated even with good solvents such as pyridine^{2,3}, and the dissolution is expected to be a very difficult task.

It is known, as reviewed in the paper¹, that a most portion of bituminous coals can be disintegrated in coal-derived liquids and polycyclic aromatic hydrocarbons at 300-400°C (high-temperature soaking). These temperatures are well below regular coal liquefaction or decomposition points. It was proposed that electron donors and acceptors of low molecular weight contained in these materials substitute coal-coal complexes with charge-transfer interactions (physical dissolution), although chemical bond breakages may concurrently occur to some extent at these temperatures.

Whereas, association are formed for high volatile bituminous coals by soaking at temperatures below 300°C^{2,3}. It was interpreted that relatively weak secondary interactions were broken and relatively strong secondary interaction were formed (solvent-induced association). Therefore, optimum temperatures for dissolution of coal should be noticed. Unfortunately, the reduction in dissolution after soaking coal in a coal liquid at 200-300°C has been regarded as a retrograde reaction^{9,10}. These temperatures are being used for

mixing and preconversion of coal in recycle oils in many processes¹¹. Care should be exercised about temperatures for the pretreatment of coal¹.

The disintegration mechanism during the high-temperature soaking was studied in the previous tasks^{12,13}. Pyridine insolubles were obtained from extracts of a high volatile bituminous coal by soaking in toluene at 200 and 350°. These products were analyzed by coal swelling. Swelling ratios of residues from the raw coal and samples treated at both temperatures were significantly larger than those of their extracts. The dependence of sample concentration on coal swelling was also examined. From these results, it was concluded that the change in extractability under the condition is primarily controlled by associative equilibria (physical phenomena). Then, a systematic study using actual coal liquids was carried out to follow up the proposition in the high-temperature soaking. Changes in extractability under various conditions could be rationalized by the associative equilibria. Significant physical dissolution by the high-temperature soaking of coal was consistent with the associated molecular nature of coal.

One of the main goals in coal liquefaction is to decrease a gas yield. Running cost of hydrogen is estimated to be very high (generally 30-40 %) in the total cost¹¹. Hydrogen is primarily lost with produced gas such as methane and ethane. It is expected that reactivity of dissolved coal is higher than that of undissolved coal. Higher reactivity will lead to lower severity in liquefaction, and this will result in decrease in a gas yield. The high-temperature soaking in a coal liquid (recycle oil) produced from coal will be one method for physical dissolution in which any chemicals and hydrogen are not necessary.

Another important factor to decrease a gas yield is suggested on the basis of the associated molecular nature of coal. Hydrocarbons with lower molecular weight generally produce more gas by thermal pyrolysis. Hydrocarbons with higher molecular mass will be decomposed with more severe conditions under which more gas will be produced from hydrocarbons with lower molecular weight. The associated structural model of coal can be regarded as material with a broad molecular weight distribution. Therefore, coal with different molecular weight should be treated separately, if possible.

Treatments of coal under mild conditions for dissolution has been studied for years.

A recent brief review appears in the Shams *et al.*'s paper¹⁴. The attention is recently being redrawn as a pretreatment before liquefaction¹⁵. The procedures of chemical reactions such as alkylation, oxidation and hydrolysis have mostly been attempted¹⁴. Other methods have been employed at higher temperatures of 300-350°C in the presence of CO/H₂O¹⁶⁻¹⁹, CH₃OH¹⁴, nitrogen-containing compounds²⁰⁻²¹ etc. A negative change in dissolution during a treatment is regarded as result of retrograde reactions as shown above, and hydroaromatics and hydrogenated solvents have been considered for prevention of retrograde reactions²². It seems that these treatments are based on the network model of coal. If the network model of coal is considered for liquefaction, bond cleavages and stabilization of labile intermediates during decomposition will be major concerns. From an economical point of view, environment under high pressure of H₂, H₂O and CO and the addition of chemicals are not recommended. A more practical procedure is required, and appropriate coal structural model should be well considered.

In this report, an improved concept for coal liquefaction is investigated on the basis of the associated molecular model of coal. Two issues pointed above are focused on: (1) maximizing dissolution of associated coal and (2) step-wise conversion of associated coal with broad molecular weight distribution. From the results under various conditions, an improved liquefaction concept to increase liquid and decrease gas is proposed and tested.

EXPERIMENTAL

Coal samples were obtained from the DOE Coal Bank at Pennsylvania State University. Their elemental analyses are shown in *Table 1*. Illinois no. 6 coal (DECS-2) was used as received, and Smith Roland coal (DECS-8) was washed with 2N HCl⁵ and dried before use. A coal liquid derived from Illinois no. 6 coal obtained from the Wilsonville pilot plant²³ was used. The elemental analysis of this coal liquid is also shown in *Table 1*. All the reagents and solvents were obtained from Aldrich Chemical Co. (Milwaukee, WI) and Fisher Scientific (Pittsburgh, PA), and HPLC-grade solvents were used without further purification.

Two reactors, a 250 ml autoclave (Model 4576; Parr Instrument CO., Moline, IL) and 27 ml microreactors fabricated¹³, were used. These reactors were evacuated and

Table 1 Elemental analyses of coals and a coal liquid used (wt%)

Symbol	Sample	H ₂ O	Ash	Element (daf)			
				C	H	N	S
DECS-2	Illinois no. 6 (hvb)	10.4	14.5	78.1	5.4	1.3	5.4
DECS-8	Smith-Roland (subb)	28.4	9.9	74.4	5.2	1.0	0.9
--	coal liquid	--	--	88.4	11.4	0.2	1.1

purged with nitrogen five times after charging a coal sample and a solvent. The autoclave was heated approximately at $8^{\circ}\text{C min}^{-1}$ to required temperature, and controlled to $\pm 3^{\circ}\text{C}$, while agitating with the autoclave stirrer (500 rev min^{-1}). Microreactors were heated in a fluidized sand bath (Model SBL-2; Techne Corp., Princeton, NJ) which was controlled within $\pm 1.0^{\circ}\text{C}$ of the set point. The shaker (Model 75; the Burrell Corp., Pittsburgh, PA) was modified to shake the microreactor horizontally at 320 rev min^{-1} . Mixtures in the reactor attained the set point within 5 min, when the reactor was being immersed into the sand bath. Conditions for all runs are summarized in *Table 2*.

After reactions, the mixtures were filtered and Soxhlet-extracted with cyclohexane, toluene and tetrahydrofuran (THF) for 24 h, respectively, and then these samples were dried under vacuum at 95°C overnight. The amounts of THF solubles (TS), toluene solubles (ToS) and cyclohexane solubles (CyS) were determined from weights of the respective insolubles. Produced gas was generally included in the CyS yield.

Gas was collected with a sample bag after cooling the autoclave, and analyzed with gas chromatography by the University of Pittsburgh Applied Research Center (Pittsburgh, PA). Approximate gas yields were calculated on the assumption that the amount of nitrogen did not change before and after reactions.

Table 2 Run numbers and experimental conditions

Run no.	Condition						
	Coal (g)	Temp. °C	Time h	Solvent (ml)	Atmosphere (MPa)	Cat. (mg)	Additive (ml)
1	DECS-2 (5)	200/430	1.0/1.0	Liquid A (50)	N ₂ (1.4)		
2	"	350/430	"	"	"		
3	"	430	1.0	"	N ₂ /H ₂ (2.8/0.7)	MoS ₂ (50)	
4 ^a	"	"	"	"	"	"	
5 ^{b,c}	"	275	1.5	Liquid B (15)	N ₂ (0.35)		
6 ^{b,c}	"	300	"	"	"		
7 ^{b,c}	"	325	"	"	"		
8 ^{b,c}	"	350	"	"	"		
9 ^{b,c}	"	375	"	"	"		
10 ^d	"	350/400	1.0/1.0	Liquid A (50)	N ₂ (1.4)		
11 ^d	"	200/400	"	"	"		
12 ^d	"	350/400	"	"	H ₂ (1.4)		H ₂ O ₂ (5)
13 ^b	" (3.5)	430	2.5	" (14)	N ₂ (0.35)		

Table 2 (continued)

Run no.	Condition						
	Coal (g)	Temp. °C	Time h	Solvent (ml)	Atmosphere (MPa)	Cat. (mg)	Additive (ml)
14 ^b	DECS-2 (3.5)	350/400/430	0.5/0.5/1.0	Liquid A (14)	N ₂ (0.35)		
15 ^b	"	e	e	"	"		
16	DECS-2/PS ^f (5)	430	1.0	" (50)	N ₂ /H ₂ (0.7/2.8)	MoS ₂ (50)	
17	DECS-2/PI ^f (5)	"	"	"	"	"	
18	DECS-2/CyI ^g (5)	"	"	"	"	"	
19	DECS-2 (5)	200/430	1.0/2.0	"	"	"	
20	Run 10 + Run 18						
21	DECS-8 ^h (5)	200/430	1.0/2.0	Liquid A	N ₂ /H ₂ (0.7/2.8)	MoS ₂ (50)	
22	"	350/400 ⁱ ---> 430	1.0/1.0 ⁱ ---> 1.0	"	"	"	

^aPyridine refluxed coal, followed by the removal of solvent

^bMicroreactor (27 ml) was used ^cRef. 12 ^dRef. 27

^eProgramed heating: 130°C ----- 240°C ----- 350°C ----- 400°C ----- 430°C
(28 min) (30 min) (21 min) (11 min) (1 h)

^fPS: pyridine solubles, PI: pyridine insolubles

^gCyclohexane insolubles from Run 10

^h2N HCl-washed and dried coal

ⁱCyclohexane insolubles was liquefied after soaking at 350/400°C

RESULTS AND DISCUSSION

Coal dissolution and liquefaction

Higher temperatures are required for dissolution by soaking in poorer solvents, and lower temperatures are enough when better solvents were used. For the former example, an increase in conversion at 427°C was observed when a coal/coal liquid mixture was soaked at 277-322°C for 10 min²⁴. For the latter, preswelling with THF and tetraammoniumhydroxide at room temperature, followed by removal of solvents, enhanced hydroliquefaction yields at 400°C^{25,26}. In this study, the effect of soaking temperature on liquefaction was compared between at 200°C (Run 1, see *Figure 1*) and at 350°C (Run 2). Illinois no. 6 coal was liquefied at 430°C for 1 h after soaking at these temperatures. The yields of TS were the same for these runs, but the yields of ToS and CyS were 5% higher for soaking at 350°C than for that at 200°C. The coal was mildly refluxed in pyridine for 24 h, followed by the removal of the solvent, and then liquefied at 430°C (Run 4). The conversion was compared to that liquefied under the same condition but using the raw coal (Run 3). The yield of CyS increased about 10% by soaking in pyridine.

The above result showed that the high-temperature soaking in the coal liquid enhanced the conversion of the following coal liquefaction. The optimum temperature of the high temperature soaking was around 350°C as reported in the previous task¹³ (Runs 5-9 in *Figure 2*)¹³. However, the CyS (or oil) yield was still low (35%) at 350°C. The two-step soaking was further tested to increase an oil yield. Soaking at 350°C, followed by another soaking at 400°C, gave the 50% oil yield (Run 10 in *Figure 3*)²⁷, but soaking at 200°C, followed by another soaking at 400°C, was not effective and led to the yield of more than 100% because of strong incorporation of the coal liquid (Run 11).

The effect of radical initiators on the high-temperature soaking and liquefaction were investigated in the previous tasks^{27,28}. Although it has been widely accepted that radicals cause retrograde reactions, the effect of hydrogen peroxide on coal conversion was dependent upon temperature. The effect was positive in the high-temperature soaking (350-400°C), but negative at higher temperatures (430-440°C). These positive and negative effects were enhanced under hydrogen. The addition of H₂O₂ at the high-temperature soaking increased the 5% oil yield under low pressure hydrogen gas (Run 12)²⁸. The

Figure 1 Effect of soaking before liquefaction on coal conversion (Conditions are listed in *Table 2*)

Figure 2 Effect of soaking temperature on extractability¹³ (Conditions are in *Table 2*)

Figure 3 Effect of step-wise soaking on extractability (Conditions are in *Table 2*)

addition of a small amount of water alone gave the similar change in conversion in the high-temperature soaking. Therefore, a small amount of water or hydrogen peroxide water solution may be added to improve the effect of the high-temperature soaking.

The two-step high-temperature soaking at 350°C and 400°C gave the 50% of cyclohexane solubles as shown above. This implies that slow or programmed heating is better than rapid heating on coal conversion. The autoclave was heated up relatively slowly (at 8°C min⁻¹). The effect of heating rate, therefore, was investigated using the microreactor which was rapidly heated up in the sand bath. The reactor was heated from room temperature to 430°C in 0.5 h and held at 430°C for 2 h (Run 13). For Run 14, the mixture was reacted under the same condition, but heated up with a step-wise before reaction (at 350°C for 0.5 h and at 400°C for 0.5 h), and then held at 430°C for 1 h. The heating-up time from room temperature to 350°C, from 350°C to 400°C and from 400°C to 430°C was 0.5 h. So, the total residence time including heating-up was 2.5 h. For Run 15, the mixture was slowly heated from 130°C to 430°C as shown in *Table 2* and held at 430°C for 1 h. The total duration of heating-up and reaction time was also controlled to 2.5 h. Although the coal was reacted at 430°C for the longest duration for Run 13, coal conversion was the lowest among these Runs. The oil yield was enhanced about 10% by two programmed heatings. These results shows that the programmed heating or step-wise high-temperature soaking was important for coal conversion. Song *et al.*²⁹ recently reported the same effect of the temperature-programmed liquefaction of low rank coals. Montana subbituminous coal was converted to 5-10% more (THF solubles) by slow heating compared to rapid heating.

Coal fractions and liquefaction

It was suggested above that a large portion of coal is associated, and can be regarded as material with a broad molecular weight distribution¹. A low molecular weight fraction may lead to a higher gas yield compared to a high molecular weight fraction by pyrolysis under the same condition. A low molecular weight fraction may be separated after dissolution of coal, and a remaining high molecular weight fraction may be selectively liquefied. Here, pyridine solubles and insolubles were separately liquefied to compare their

conversions under the same condition (Runs 16 and 17). Approximately the same oil yield was obtained from pyridine solubles and insolubles (*Figure 4*). Furthermore, cyclohexane insolubles from Run 10 was examined. The 50% oil yield was obtained even from this fraction (Run 18).

The liquefaction characteristics of the soluble and insoluble components has been recently reviewed and studied³⁰. Dissolution and hydrogen consumption rates of a pyridine extracted coal and a whole coal were similar for West Kentucky coal (80% carbon, daf)³¹. Whereas, a significant decrease in liquefaction conversions was observed when a coal was extracted with pyridine for Illinois no. 6 coal³². Warzinski and Holder³⁰ found the retrogressive behavior in conversion for the pyridine extract part of Illinois no. 6 coal. Although it is difficult to conclude the effect of the soluble and insoluble components from these results, it seems that the reactivity of residues or high molecular weight components is not so poor as that of low molecular weight components.

The associated molecular nature and liquefaction

It was shown that a large portion of coal can be dissolved by the high-temperature soaking in the coal liquid, and a programmed or step-wise heating is preferred to enhance an oil yield. The highly dissolved coal was liquefied to a larger extent. Further, it was suggested that coal with a broad molecular weight distribution should be separated into a oil and bottom fractions after dissolution, and that bottoms should be liquefied at a next step. From these results, the improved concept is proposed to increase an oil yield and decrease a gas yield as shown in the block diagram (*Figure 5*). Coal is soaked in a recycle oil at 350°C and at 400°C. Gas and oil are recovered with vacuum distillation, and the bottom fraction is sent to a liquefaction section and liquefied under a low pressure of hydrogen at relatively low temperature.

The proposed procedure was tested using an autoclave. The DECS-2 coal was soaked in the coal liquid under nitrogen at 350°C and at 400°C for 1 h, respectively. The oil fraction was extracted with cyclohexane, and the cyclohexane insoluble portion was liquefied under a low pressure of hydrogen (2.8 MPa) at 430°C for 1 h (Run 20). For comparison, the coal was soaked in the coal liquid at 200°C for 1 h, and then the mixture

Figure 4 Coal fractions and their conversion (Conditions are in *Table 2*)

Figure 5 Block diagram of the proposed coal liquefaction procedure

Table 3 Gas composition obtained from liquefaction^a

(Vol %)				
Gas	Run 19	Run 20 ^b (CyI)	Run 21	Run 22 ^b (CyI)
Hydrogen	61.53	68.05	62.61	70.76
CO	0.15	0.09	0.45	0.14
CO ₂	0.21	0.07	1.41	0.14
Methane	9.32	5.03	9.23	4.84
Ethane	4.19	2.55	4.15	2.44
Ethylene	0.04	0.05	0.04	0.05
Propane	2.21	1.44	2.15	1.38
Propylene	0.09	0.11	neg	0.10
n-Butane	0.51	0.40	0.48	0.36
i-Butane	0.16	0.12	0.16	0.11
Butene	0.02	0.04	neg	0.02

^aGas samples include gas produced from coal liquid,
Coal/coal liquid = 5 g/50 ml

^bGas obtained from the second step at 430°C

was liquefied under the same condition for 2 h (Run 19). In these Runs, gas yields were analyzed. *Figure 6* shows these results. *Scheme 1* shows the mass balance for Run 20. It is notable that the CyS (or oil) yield increased 30% and the gas yield decreased 15% by this test.

DECS-8 (subbituminous) coal was also examined with the same procedure. As the ionic forces are relatively strong and abundant in low rank coals⁵, it is an important step to weaken the ionic forces before the high-temperature soaking. Although it has been known that acid washing enhances the conversion of low rank coal³³⁻³⁶, the details on acid washing have not clearly been explained. Here, 2N HCl washing⁵ was used to weaken the ionic forces in the coal before the high-temperature soaking. The sample was soaked in the coal liquid at 350°C and at 400°C for 1 h, respectively. Cyclohexane insolubles from

the soaked coal was similarly liquefied at 430°C for 1 h (Run 22). As the acid washed coal was dried, the dried DECS-8 coal was soaked at 200°C for 1 h and then liquefied at 430°C for 2 h for comparison (Run 21). Again, more than 30% increase in an oil yield and 20% decrease in a gas yield was observed by the procedure (*Figure 6* and *Scheme 1*).

About 2% of gas was produced from the coal liquid under the condition at 430°C by the control experiment without coal. This produced gas was subtracted from the results for the above Runs. As change in hydrogen and gas produced from the coal liquid was greater than the amount of produced gas at the second step (430°C, CyI) for Runs 20 and 22, precise gas yields were not analyzed. *Table 3* shows gas compositions produced at 430°C. Generally, the residue from the high-temperature soaking (CyI) produced a small amount of CO, CO₂, and methane and a large amount of olefine gases.

CONCLUSIONS

Improved coal liquefaction was reinvestigated for the current two-stage process on the basis of the associated molecular nature of coal. Since a significant portion of coal molecules are physically associated as pointed in our recent paper, physical dissolution should be considered. The step-wise high-temperature soaking was a simple and effective method for coal dissolution. Larger dissolution made liquefaction severity lower. Broad molecular mass distribution in the associated coal was another important factor. The selective reaction of fractions with high molecular weight isolated after the high-temperature soaking made gas yield lower. Tests with using an autoclave by the concept shown in *Figure 5* enabled to produce 30% more oil and 15-20% less gas yields. It is expected that the procedure will result in great cost down in coal liquefaction.

REFERENCES

- 1 Nishioka, M. *Fuel* 1992, 71, 941
- 2 Nishioka, M. and Larsen, J. W. *Energy & Fuels* 1990, 4, 100
- 3 Nishioka, M. and Larsen, J. W. *Am. Chem. Soc. Div. Fuel Chem. Prepr.* 1990, 35(2), 319

Figure 6 Coal conversion by the proposed procedure for a high-volatile bituminous coal and a subbituminous coal (Conditions are in *Table 2*)

Run 20 (CECS-2 Coal)

Total yield (wt%, daf)	
Gas	4
CyS	73
ToS-CyS	7
TS-ToS	7
TI	9

Run 22 (CECS-8 Coal)

Total yield (wt%, daf)	
Gas	3
CyS	76
ToS-CyS	8
TS-ToS	5
TI	8

Scheme 1 Mass balance for Runs 20 and 22

- 4 Nishioka, M. *Energy & Fuels* 1991, 5, 487
- 5 Nishioka, M., Gebhard, L. and Silbernagel, B. G. *Fuel* 1991, 70, 341
- 6 Nishioka, M. *Energy & Fuels* 1991, 5, 523
- 7 Nishioka, M. *Fuel* 1991, 70, 1413
- 8 Haenel, M. W. and Schweitzer, D. in 'Advances in Chemistry no. 217', American Chemical Society, Washington DC, 1988, Ch. 19
- 9 Solomon, P. R., Serio, M. A., Deshpande, G. V. *et al. Am. Chem. Soc. Div. Fuel Chem. Prepr.* 1989, 34(3), 803
- 10 Derbyshire, F. J., Davis, A., Epstein, M. *et al. Fuel* 1986, 65, 1233
- 11 The U.S. Department of Energy Report, in 'Coal Liquefaction - A Research & Development Needs Assessment', 1989
- 12 Nishioka, M., Laird, W. and Bendale, P. *Fuel* submitted
- 13 Bendale, P., Zeli, R. A. and Nishioka, M. *Fuel* submitted
- 14 Shams, K. G., Miller, R. L. and Baldwin, R. M. *Fuel* 1992, 71, 1015
- 15 Warzinski, R. P. and Khan, R. R. *Fuel* 1992, 71, 979
- 16 Fu, Y. C. and Illig, E. G. *Ind. Eng. Chem. Proc. Des. Dev.* 1976, 15, 392
- 17 Ross, D. S., Blessing, J. E., Nguyen, Q. C. and Hum, G. P. *Fuel* 1984, 63, 1206
- 18 Ross, D. S. in 'Coal Science Vol. 3' (Eds M. L. Gorbaty, J. W. Larsen and I. Wender), Academic Press, New York, 1984 p. 301
- 19 Blaustein, B. D., Bochrath, B. C., Davis, H. M., Friedman, S., Illig, E. G. and Mikita, M. A. *Am. Chem. Soc. Div. Fuel Chem. Prepr.* 1985, 30(2), 359
- 20 Tagaya, H., Sugai, J., Onuki, M. and Chiba, K. *Energy & Fuels* 1987, 1, 397
- 21 Miller, R. L., Giacomelli, G. F., McHugh, K. J. and Baldwin, R. M. *Energy & Fuels* 1989, 3, 127
- 22 Neavel, R. C. in 'Coal Science Vol. 1' (Eds M. L. Gorbaty, J. W. Larsen and I. Wender), Academic Press, New York, 1982 p. 1
- 23 Gollakota, S. V., Lee, J. M. and Davies, O. *Fuel Proc. Tech.* 1989, 22, 205
- 24 Wham, R. M. *Fuel* 1987, 66, 283
- 25 Joseph, J. T. *Fuel* 1991, 70, 139

- 26 Joseph, J. T. *Fuel* 1991, **70**, 459
- 27 Nishioka, M., Laird, W. and Bendale, P. *Fuel* submitted
- 28 Nishioka, M. and Laird, W. *Fuel* submitted
- 29 Song, C., Schobert, H. H. and Hatcher, P. G. *Energy & Fuels* 1992, **6**, 328
- 30 Warzinski, R. P. and Holder, G. D. *Fuel* 1992, **71**, 993
- 31 Whitehurst, D. D., Farcasiu, M., Mitchell, T. O. and Dickert, J. J. Jr. Electric Power Research Institute Report EPRI AF-480, Palo Alto, CA, 1077, pp. 7-2-7-10
- 32 Seth, M. PhD Thesis University of California Berkeley, Berkeley, CA, 1980
- 33 Schafer, H. N. S. *Fuel* 1970, **49**, 197
- 34 Mochida, I., Shimohara, T., Korai, Y., Fujitsu, H. and Takeshita, K. *Fuel* 1983, **62**, 659
- 35 Serio, M. A., Solomon, P. R., Kroo, E., Bassilakis, R., Malhotra, R. and McMillen, D. *Am. Chem. Soc. Div. Fuel Chem. Prepr.* 1990, **35**(1), 61
- 36 Joseph, J. T. and Rorrai, T. R. *Fuel* 1992, **71**, 75

END

DATE
FILMED

3 / 24 / 93