PROGRESS REPORT**ANALYSIS OF NUCLEAR REACTOR INSTABILITY PHENOMENA**
(DE-FG02-92ER75701)

R.T. Lahey, Jr. - Principal Investigator
Rensselaer Polytechnic Institute
Troy, NY 12180-3590

RECEIVED**MAR 22 1993****OCTI****INTRODUCTION**

The phenomena known as density-wave instability often occurs in phase change systems, such as boiling water nuclear reactors (BWRs). Our current understanding of density-wave oscillations is in fairly good shape for linear phenomena (eg, the onset of instabilities) but is not very advanced for non-linear phenomena [Lahey and Podowski, 1989]. In particular, limit cycle and chaotic instability modes are not well understood in boiling systems such as current and advanced generation BWRs (eg, SBWR). In particular, the SBWR relies on natural circulation and is thus inherently prone to problems with density-wave instabilities.

The purpose of this research is to develop a quantitative understanding of nonlinear nuclear-coupled density-wave instability phenomena in BWRs. This research builds on the work of Achard et al [1985] and Clausse et al [1991] who showed, respectively, that Hopf bifurcations and chaotic oscillations may occur in boiling systems.

During the first year of the subject research project a nodal drift-flux model was derived for a boiling channel. A linear stability analysis was also performed to study the sensitivity of the nodal model to the number of axial nodes used.

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

MASTER**DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED**

DISCUSSION - BOILING CHANNEL MODEL

In deriving the systems of differential equations which represent the lumped parameter model of a boiling channel, the following reasonable assumptions have been made:

- The system pressure is constant
- The heat flux is uniform
- Both phases are incompressible
- The two phases are in thermodynamic equilibrium
- The phasic slip between the phases is quantified by drift-flux parameters.
- Viscous dissipation, kinetic energy, potential energy and flow work are neglected in the energy equation.
- The channel's inlet temperature is constant.
- The channel is vertical.

The one-dimensional continuity, momentum and energy equations for the two-phase mixture are [Lahey and Moody, 1979]:

Mass

$$\frac{\partial \langle \bar{\rho} \rangle}{\partial t} + \frac{\partial G}{\partial z} = 0 \quad (1.a)$$

Momentum

$$-\frac{\partial p}{\partial z} - g \langle \bar{\rho} \rangle - \frac{\tau_w P_f}{A_{x-s}} - \frac{\partial}{\partial z} \left[\frac{(\rho_f - \langle \bar{\rho} \rangle) \rho_f \rho_g (V'_{gj})^2}{(\langle \bar{\rho} \rangle - \rho_g) \langle \bar{\rho} \rangle} \right] = \frac{\partial G}{\partial t} + \frac{\partial}{\partial z} \left(\frac{G^2}{\langle \bar{\rho} \rangle} \right) \quad (1.b)$$

Energy

$$\frac{q'' P_H}{A_{x-s}} \cdot \frac{\partial}{\partial z} \left[\frac{\langle \alpha \rangle \rho_f \rho_g}{\langle \bar{\rho} \rangle} V'_{gj} h_{fg} \right] = \frac{\partial}{\partial t} (\langle \bar{\rho} \rangle \bar{h}) + \frac{\partial}{\partial z} (\langle \bar{\rho} \rangle u_m \bar{h}) \quad (1.c)$$

where, $V'_{gj} = (C_0 - 1) \langle j \rangle + V_{gj}$

and using the Zuber-Findlay void-quality model [Zuber and Findlay, 1965],

$$\langle \alpha \rangle = \frac{\langle x \rangle}{C_0 \left[\langle x \rangle + \frac{\rho_g}{\rho_f} (1 - \langle x \rangle) \right] + \frac{\rho_g V_{gi}}{G}}$$

The state equation for the two-phase density can be written as:

$$\langle \bar{\rho} \rangle = \rho_f - (\rho_f - \rho_g) \left\{ \frac{\frac{(\langle h \rangle - h_f)}{h_{fg}}}{C_0 \left[\frac{(\langle h \rangle - h_f)}{h_{fg}} + \frac{\rho_g}{\rho_f} \left(1 - \frac{(\langle h \rangle - h_f)}{h_{fg}} \right) \right] + \frac{\rho_g V_{gi}}{G}} \right\} \quad (1.d)$$

It is convenient to rewrite these equations in non-dimensional form as:

$$\frac{\partial \langle \bar{\rho} \rangle^+}{\partial t^+} + \frac{\partial [\langle \bar{\rho} \rangle^+ u_m^+]}{\partial t^+} = 0 \quad (2.a)$$

$$\begin{aligned} & - Eu \frac{\partial p^+}{\partial z^+} - \frac{1}{Fr} g \langle \bar{\rho} \rangle^+ - \Lambda \langle \bar{\rho} \rangle^+ u_m^{+2} - \left[\sum_i^N K_i \delta(z - z_i) \right] \frac{\langle \bar{\rho} \rangle^+ u_m^{+2}}{2} \\ & - \frac{v_f}{v_g} \frac{\partial}{\partial z^+} \left[\left(\frac{1 - \langle \bar{\rho} \rangle^+}{\langle \bar{\rho} \rangle^+ - \frac{\rho_g}{\rho_f}} \right) \frac{1}{\langle \bar{\rho} \rangle^+} (V'_{gj})^2 \right] = \frac{\partial [\langle \bar{\rho} \rangle^+ u_m^+]}{\partial t^+} + \frac{\partial [\langle \bar{\rho} \rangle^+ u_m^{+2}]}{\partial z^+} \quad (2.b) \end{aligned}$$

$$\frac{N_{sub}}{N_{pch}} Q^+ - \frac{1}{\frac{v_g}{v_{fg}} N_{pch}} \frac{\partial}{\partial z^+} \left[\frac{\langle \alpha \rangle}{\langle \bar{\rho} \rangle^+} V'_{gj} \right] = \frac{\partial}{\partial t^+} [\langle \bar{\rho} \rangle^+ \bar{h}^+] + \frac{\partial}{\partial z^+} [\langle \bar{\rho} \rangle^+ \bar{h}^+ u_m^+] \quad (2.c)$$

$$\langle \bar{\rho} \rangle^+ = 1 - \frac{N_{pch} \langle h \rangle^+}{C_o + \frac{V'^+}{\bar{G}^+} + C_o N_{pch} \langle h \rangle^+} \quad (2.d)$$

A definition of these non-dimensional quantities is given in the Nomenclature.

The lumped parameter model is based on a Galerkin nodal approximation of the conservation equations for a boiling channel [Clausse et al, 1991] in which a linear shape function is used for enthalpy.

Single-Phase Region

The single-phase region extends from the inlet of the channel to the boiling boundary, λ . As noted in Figure-1, this region has been divided into $N_{1\phi}$ nodes. In each of these nodes the enthalpy increase is assumed to be linear and equal to $\frac{(h_f - h_i)}{N_{1\phi}}$. The boundary between consecutive nodes is defined as the point where the enthalpy of the liquid is,

$$h_n = h_i + \frac{n}{N_{1\phi}} (h_f - h_i) \quad (3)$$

It is important to note that the position of the boundaries, L_n , are a function of time.

The single-phase energy equation was integrated in space over each node, using Leibnitz's rule for the time derivatives. The resulting nodal equations are:

$$\frac{dL_n}{dt} = 2 u_{in} + \frac{2q''P_H}{A_{x-s}} \frac{N_{1\phi}}{(h_f - h_i)\rho_\ell} (L_n - L_{n-1}) - \frac{dL_{n-1}}{dt} \quad (4.a)$$

In non-dimensional form Eq. (4a) becomes:

$$\frac{dL_n^+}{dt^+} = 2u_{in}^+ + 2N_{1\phi} \frac{N_{sub}}{N_{pch}} \frac{Q^+}{h_{in}^+} (L_n^+ - L_{n-1}^+) - \frac{dL_{n-1}^+}{dt^+} \quad (4.b)$$

The time derivatives of the (n-1) previous node boundaries can be eliminated using backward substitution to achieve an ordinary differential equation (ODE) for the new state variable, $L_n(t)$. The position of the last boundary $L_{N_{1\phi}}^+$ defines the so-called boiling boundary, λ^+ . This is the position at which the liquid first becomes saturated.

Two-Phase Region

The two-phase region extends from the boiling boundary, λ^+ , to the exit of the heated channel. This region is divided into $N_{2\phi}$ nodes. At the boundaries of these nodes the enthalpy is given by, $h_n = h_f + \frac{(h_e - h_f)}{N} n$, or in non-dimensional form, $h_n^+ = \frac{n}{N} h_e^+$, where h_e^+ is the non-dimensional two-phase enthalpy at the exit of the heated channel.

As before, a linear enthalpy profile was assumed within each two-phase node and the continuity equation was integrated over each node. The resulting non-dimensional nodal mass conservation equation is:

$$\frac{dM_n^+}{dt^+} - \langle \bar{\rho} \rangle_n^+ \frac{dL_n^+}{dt^+} + \langle \bar{\rho} \rangle_{n-1}^+ \frac{dL_{n-1}^+}{dt^+} + \langle \bar{\rho} \rangle_n^+ u_{m_n}^+ - \langle \bar{\rho} \rangle_n^+ u_{m_{n-1}}^+ = 0 \quad (5)$$

where the non-dimensional mass in node-n is given by:

$$M_n^+ = \int_{L_{n-1}^+}^{L_n^+} \langle \bar{\rho} \rangle^+ dz^+ \quad (6)$$

and $\langle \bar{\rho} \rangle^+$ is given by Eq. (2.d).

It should be noted that in the state equation, Eq. (1.d), G is a function of $\langle \bar{\rho} \rangle$, since $G = \langle \bar{\rho} \rangle u_m$. The mass flux, G , could be eliminated in terms of $\langle \bar{\rho} \rangle$ and the resulting equation solved for $\langle \bar{\rho} \rangle$, however, this would yield a very complex expression. Instead, G was assumed to be constant and equal to its average value within the node. That is,

$$G_n = \bar{G}_n = \frac{(G_n + G_{n+1})}{2} = \frac{[\langle \bar{\rho} \rangle_n u_n + \langle \bar{\rho} \rangle_{n+1} u_{n-1}]}{2}$$

With this simplification, the non-dimensional mass in node- n is given by:

$$M_n^+ = \frac{(C_o - 1)}{C_o} (L_n^+ - L_{n-1}^+) + \frac{\left[C_o + \frac{V_{gj}^+}{G_n^+} \right] (L_n^+ - L_{n-1}^+)}{C_o^2 N_{pch} h_e^+} N_{2\phi} \ell_n \left[1 + \frac{C_o N_{pch} \frac{h_e^+}{N_{2\phi}}}{C_o + \frac{V_{gj}^+}{G_n^+} + C_o N_{pch} \frac{(n-1)}{N_{2\phi}}} \right] \quad (7)$$

Differentiating Eq. (7) with respect to time and substituting the result into Eq. (5) the ODE which characterizes a node in the two-phase region was obtained.

When $C_o = 1.0$ and $V_{gj} = 0.0$, these equations reduce to the equations for a heated channel obtained with a homogeneous equilibrium model (HEM) [Clausse et al, 1991].

Closure of the Model

The system of equations has $N_{1\phi} + N_{2\phi}$ equations and $N_{1\phi} + N_{2\phi-1}$ unknowns. An additional independent equation is therefore necessary to achieve closure. This equation comes from the boundary condition which specifies the

pressure drop across the heat channel. In order to introduce this boundary conditions, the non-dimensional momentum equation, Eq. (2.b), was integrated along the channel. The following ODE was obtained.

$$\frac{dW^+}{dt} = -\Delta p_a^+ - \Delta p_f^+ - \Delta p_L^+ - \Delta p_g^+ \quad (8)$$

where,

$$W^+ = \int_0^{\lambda^+} \frac{\partial u_{in}^+}{\partial t^+} dz^+ + \int_{\lambda^+}^1 \frac{\partial G^+}{\partial t^+} dz^+ \quad (9a)$$

$$\Delta p_a^+ = \langle \bar{\rho} \rangle^+ u_n^{+2} - u_i^{+2} + \frac{\rho_g}{\rho_f} \left(\frac{1 - \langle \bar{\rho} \rangle_e^+}{\langle \bar{\rho} \rangle_e^+ - \frac{\rho_g}{\rho_f}} \right) \frac{1}{\langle \bar{\rho} \rangle_e^+} (V_{gj}^+)^2 \quad (9b)$$

$$\Delta p_f^+ = \Lambda \left[\int_0^{\lambda^+} u_{in}^{+2} dz^+ + \int_{\lambda^+}^1 \frac{G^{+2}}{\langle \bar{\rho} \rangle^+} dz^+ \right] \quad (9c)$$

$$\Delta p_L = K_i u_{in}^{+2} + K_e \frac{G_e^{+2}}{\langle \bar{\rho} \rangle_e^+} \quad (9d)$$

$$\Delta p_g = \frac{1}{Fr} \left\{ (1 - \lambda^+) + \sum_{i=1}^{N_{2\phi}} M_{i_{2\phi}}^+ + \frac{bN_{sub}}{2N_{1\phi}} \left[\sum_{i=1}^{N_{1\phi}} \left\{ (2n-1)(L_n^+ - L_{n-1}^+) \right\} - \lambda^+ \right] \right\} \quad (9e)$$

Again, for $C_o = 1.0$ and $V_{gj} = 0.0$, this equation reduces to the ODE for a homogeneous equilibrium model [Clausse et al, 1991].

This model can be extended to include an unheated two-phase riser, the dynamics of the heated wall, and nuclear feedback effects. To simplify the algebra

involved, the details of the derivations are given in Appendix-I for a homogeneous equilibrium, model ($C_o = 1.0$, $V_{gj} = 0.0$).

Linear Stability Analysis

A linear stability analysis for the system of ODEs for a heated channel was performed. The sensitivity of the linear stability map to the number of nodes was studied.

Since the equations for the drift-flux model are complex and the nodal characteristics of the model are essentially independent of the slip, the equations can be reduced to the homogeneous equilibrium model ($C_o = 1.0$, $V_{gj} = 0.0$). Indeed, previous studies [Rizwan Uddin, 1987] have shown that the value of C_o and V_{gj} does not strongly affect the marginal stability boundary.

The resulting system of nonlinear ODEs can be written in matrix form as,

$$\dot{\mathbf{x}} = \mathbf{f}(\mathbf{x}) \quad (10)$$

where,

$$\mathbf{x}^{\Delta} = (L_1^+, \dots, L_{N_{1\phi-1}}^+, \lambda^+, L_{N_{1\phi+1}}, \dots, L_{N_{2\phi-1}}^+, \rho_e^+, W^+) \quad (11)$$

The system of nonlinear ODE was linearized around their fixed points, $\mathbf{x}_0$, where, $\mathbf{x}_0 = \mathbf{x} - \delta\mathbf{x}$.

The resulting linear system is:

$$\delta \dot{\mathbf{x}} = \underline{\underline{J}}_0 \delta\mathbf{x} \quad (12)$$

where,

$J_0 = \left. \frac{\partial f}{\partial \underline{x}} \right|_{\underline{x}=\underline{x}_0}$ is the Jacobian matrix evaluated by the steady-states ($\underline{x}_0$).

The linear stability characteristics of the system is given by the eigenvalues, λ_i , of the Jacobian matrix:

$$\det \left[\left. \frac{\partial f}{\partial \underline{x}} \right|_{\underline{x}=\underline{x}_0} - \lambda \underline{I} \right] = 0 \quad (13)$$

If all the eigenvalues (λ) have negative real parts, the system is linearly stable. If an eigenvalue is real and positive, the system has an excursive instability. If any pair of complex conjugate eigenvalues have positive real parts, the system is linearly unstable and oscillatory (ie, an unstable phase plane spiral).

The eigenvalues of the system have been calculated numerically for different numbers of axial nodes, and the stable and unstable points plotted in the $N_{pch} - N_{sub}$ phase plane, such that the linear stability map was obtained. The linear stability boundary is the line that separates the region of unstable and stable points.

Figures 2, 3 and 4 show the linear stability maps for 2, 4 and 6 nodes, respectively, in the single-phase region and one node in the two-phase region. The operating conditions were chosen to compare the maps with those obtained in previous studies [Rizwan-Uddin, 1987]. It is apparent that the linear stability map changes only slightly when increasing from two to four single-phase nodes and that it doesn't change at all from four to six nodes. This is significant since the more nodes we have, the larger the computer time requirements in the nonlinear evaluations of the model.

Compared with previous calculations which used a distributed parameter model [Rizwan-Uddin, 1987], good agreement is found in the regions of low subcooling. In contrast, the high subcooling boundary is shifted to the right in the nodal model. The reason for this discrepancy is not yet clear and is currently under investigation. Moreover, a similar analysis is currently being performed for various number of nodes in the two-phase region.

DISCUSSION - MODEL EVALUATION

The nodal HEM model has been numerically evaluated for two nodes in the single-phase region, one in the two-phase region of the heater and three in an unheated riser ($N_R = 3$). The model thus had a total of seven state variables when constant heat flux conditions were assumed (ie, when heater wall dynamics and neutron feedback effects were neglected). The parameters used in these calculations are given in Table-I.

TABLE-I	
$N_{\text{sub}} = 100$	$K_e = 0$
$Fr = 0.0016$	$K_{re} = 15$
$b = 0.0002$	$L_R/L_H = 3$
$K_i = 42$	$A_R/A_H = 4$

For a phase change number (N_{pch}) of 109.0 the limit cycle shown in Figure-5 was found. Since the system is of order higher than three, a method for determining a Poincaré section in hyperspace had to be derived. This derivation is given in Appendix-II. It can be seen in Figure-5, that, as expected, a limit cycle gives a point in the Poincaré section.

As the phase change number is reduced, period doubling occurs, as shown in Figure-6. This period doubling can be clearly seen in the $u_1^+ - \lambda^+$ phase plane projection, and the first return map for u_1^+ also shown in Figure-6.

At $N_{pch} = 106.7$ a quasi-periodic T^2 torus was observed, as seen in Figure-7. The fractal signature of the T^2 torus is seen in the Poincaré sections shown in Figure-8.

Finally, as N_{pch} is further reduced (to 106.545) aperiodic chaotic oscillations occur. These oscillations, and the strange attractor, can be seen in 2D in Figure-9 and in 3D in Figure-10. In addition, the fractal signature of the strange attractor is given in Figure-11. Note that the $u_1^+ - \lambda^+$ phase plane projection of the Poincaré section implies the stretching and folding which is essential to having a strange attractor.

The most definitive measure of a strange attractor is the evaluation of the Lyapunov exponents. The largest Lyapunov exponent (Λ_{max}) can be approximated by [Wolf et al, 1985],

$$\Lambda_{max} = \frac{1}{(t_m - t_0)} \sum_{i=1}^m \log_2 \left[\frac{L(t_i)}{L(t_{i-1})} \right] \quad (14)$$

Note that, if in each interval,

$$L(t_i) = L(t_{i-1}) 2^{\Lambda_i(t_i - t_{i-1})} \quad (15)$$

then,

$$\log_2 \left(\frac{L(t_i)}{L(t_{i-1})} \right) = \Lambda_i(t_i - t_{i-1}) \stackrel{\Delta}{=} \Lambda_i \Delta t_i \quad (16)$$

Hence, renormalizing the process after each time step, we have:

$$\Lambda_{\max} = \bar{\Lambda} = \frac{1}{(t_m - t_0)} \sum_{i=1}^m \Lambda_i \Delta t_i \quad (17)$$

Thus, we see that $\Lambda_{\max}$ is just the average of the Lyapunov exponents, $\bar{\Lambda}$, along the solution flow in hyperspace.

Figure-12 gives the maximum Lyapunov exponent ($\Lambda_{\max}$) for various phase change numbers. We note that $\Lambda_{\max} = 0$ implies a periodic limit cycle while $\Lambda_{\max} > 0$ denotes an aperiodic strange attractor.

SUMMARY - RESEARCH PERFORMED TO DATE

A lumped parameter drift-flux model has been derived for the analysis of linear and nonlinear density-wave oscillations in a boiling channel.

A linear stability analysis has been performed to investigate the effect for various numbers of nodes in the single-phase region. The sensitivity of the linear stability map to the number of nodes was studied and it was found to be relatively insensitive to the number of nodes used. Moreover, good agreement was found in the low subcooling region between the linear stability boundaries of the lumped parameter model and a distributed parameter model. In contrast, in the high subcooling region the agreement is not as good. The reasons for this discrepancy are currently under investigation.

A numerical analysis of nonlinear density-wave instability phenomena was also investigated. Significantly, limit cycles, period doubling, a T^2 torus and a chaotic strange attractor were found for the case of constant heat flux. Similar channel response is expected when heated wall dynamics and nuclear feedback effects are included in the model. Indeed, these important effects will be one of the subjects of investigation next year.

p. 13 removed

It can be anticipated that this research will result in a significant advance in our understanding of nonlinear density-wave instability phenomena in boiling systems; in particular, boiling water nuclear reactors.

RESEARCH SUPERVISION

This research will be conducted by Ms. Veronica Garea (a Hispanic female) in partial fulfillment of her PhD requirements at Rensselaer. This research will be conducted under the supervision of Professor R.T. Lahey, Jr. (PI), *The Edward E. Hood, Jr. Professor of Engineering* at Rensselaer (see attached vita). The cost estimate for this (one-year) research continuation is also attached.

NOMENCLATURE

A_{x-s}	Cross-sectional area	q''	heat flux
c_{pf}	liquid heat capacity	t	time
D	diameter	u	axial velocity
Eu	Euler number	u_m	center-of-mass velocity, $G/\langle \bar{\rho} \rangle$
f	friction factor	v	specific volume
Fr	Froude number	z	axial coordinate
G	mass flux	$\langle \alpha \rangle$	void fraction
g	gravity	β	Boussinesq approximation coefficient
h	enthalpy	Λ	nondimensional friction factor
L	length	ρ	density
M	mass	$\langle \bar{\rho} \rangle$	two-phase mixture density, $\langle \bar{\rho} \rangle = \rho_g \langle \alpha \rangle + \rho_l (1 - \langle \alpha \rangle)$
N_{sub}	subcooling number		
N_{pch}	phase change number		
p	pressure		
P	perimeter		

It can be anticipated that this research will result in a significant advance in our understanding of nonlinear density-wave instability phenomena in boiling systems; in particular, boiling water nuclear reactors.

RESEARCH SUPERVISION

This research will be conducted by Ms. Veronica Garea (a Hispanic female) in partial fulfillment of her PhD requirements at Rensselaer. This research will be conducted under the supervision of Professor R.T. Lahey, Jr. (PI), *The Edward E. Hood, Jr. Professor of Engineering* at Rensselaer (see attached vita). The cost estimate for this (one-year) research continuation is also attached.

NOMENCLATURE

A_{x-s}	Cross-sectional area	q''	heat flux
c_{pf}	liquid heat capacity	t	time
D	diameter	u	axial velocity
Eu	Euler number	u_m	center-of-mass velocity, $G/\langle \bar{\rho} \rangle$
f	friction factor	v	specific volume
Fr	Froude number	z	axial coordinate
G	mass flux	$\langle \alpha \rangle$	void fraction
g	gravity	β	Boussinesq approximation coefficient
h	enthalpy	Λ	nondimensional friction factor
L	length	ρ	density
M	mass	$\langle \bar{\rho} \rangle$	two-phase mixture density, $\langle \bar{\rho} \rangle = \rho_g \langle \alpha \rangle + \rho_l (1 - \langle \alpha \rangle)$
N_{sub}	subcooling number		
N_{pch}	phase change number		
p	pressure		
P	perimeter		

Subscripts

i inlet
o steady state

l liquid
g gas
ref reference value

Non-Dimensional Quantities

The non-dimensional quantities in the equations for the heated boiling channel are defined as:

$$z^+ = \frac{z}{L_H}$$

$$t^+ = \frac{t}{t_{\text{ref}}}$$

$$u^+ = \frac{u}{u_{\text{ref}}}$$

$$\rho^+ = \frac{\rho}{\rho_f}$$

$$p^+ = \frac{(p - p_i)}{\Delta p_{\text{tot}}}$$

$$h^+ = \frac{(h - h_f)}{h_{\text{ref}}}$$

$$Q^+ = \frac{\left(\frac{q'' P_H}{A_{x-s}} \right)}{\left(\frac{q''_o P_H}{A_{x-s}} \right)}$$

$$t_{\text{ref}} = \frac{\rho_f (h_f - h_{io})}{\left(\frac{q''_o P_H}{A_{x-s}} \right)}$$

$$u_{\text{ref}} = \frac{L_H}{t_{\text{ref}}}$$

$$h_{\text{ref}} = \frac{q''_o P_H}{A_{x-s}} \frac{L_H}{\rho_f u_{io}}$$

$$N_{\text{sub}} = \frac{(h_f - h_{io})}{h_{fg}} \frac{v_{fg}}{v_f}$$

$$N_{\text{pch}} = \frac{q''_o P_H}{A_{x-s}} \frac{h_{\text{ref}} v_{fg}}{h_{fg} v_f}$$

$$\Lambda = \frac{f L_H}{2 D_H}$$

$$\text{Fr} = \frac{u_{\text{ref}}^2}{g L_H}$$

$$\text{Eu} = \frac{\Delta p_{\text{tot}}}{2 \rho_f u_{\text{ref}}^2}$$

$$b = \frac{\beta h_{fg} v_f}{C_{pf} v_{fg}}$$

REFERENCES

- Achard, J.L., Drew, D.A. and Lahey, R.T., Jr., "The Analysis of Nonlinear Density-Wave Oscillations in Boiling Channels," J. of Fluid Mechanics, Vol-155, pp. 213, 1985.
- Clausse, A. and Lahey, R.T., Jr., "The Analysis of Periodic and Strange Attractors During Density-Wave Oscillations in Boiling Flows," J. of Chaos, Solitons and Fractals, Vol-1, No. 2, pp. 17, 1991.
- Lahey, R.T., Jr. and Moody, F.J., "The Thermal-Hydraulics of a Boiling Water Nuclear Reactor," ANS Monograph, 1977.
- Lahey, R.T., Jr. and Podowski, M.Z., "On the Analysis of Instabilities in Two-Phase Flows," Multiphase Science & Technology, Vol-3, Hemisphere Press, 1987.
- Rizwan Uddin, "Linear and Nonlinear Stability Analysis of Density-Wave Oscillations in Heated Channels," PhD Thesis, Department of Nuclear Engineering, University of Illinois, Urbana-Champaign, 1987.
- Weaver, L.E., "System Analysis of Nuclear Reactor Dynamics," ANS Monograph, 1963.
- Wolf, A., Swift, J.B., Swinney, H.L. and Vastano, J.A., "Determining Lyapunov Exponents in a Time Series," Physica 16D, pp. 285, 1985.

APPENDIX-I

The non-dimensional conservation equations of homogeneous, equilibrium two-phase flow ($C_o = 1.0$, $V_{gj} = 0.0$) are:

Mass Conservation

$$\frac{\partial \rho^*}{\partial t^*} + \frac{\partial}{\partial z^*} (\rho^* u^*) = 0 \quad (\text{A.I.1})$$

Momentum Conservation

$$\frac{\partial}{\partial t^*} (\rho^* u^*) + \frac{\partial}{\partial z^*} (\rho^* u^{*2}) = - \left[\Lambda + \sum_{i=1}^N K_i \delta(z^* - z_i^*) \right] \rho^* u^{*2} - \frac{\rho^*}{Fr} - Eu \frac{\partial p^*}{\partial z^*} \quad (\text{A.I.2})$$

Energy Conservation

$$\frac{\partial}{\partial t^*} (\rho^* h^*) + \frac{\partial}{\partial z^*} (\rho^* h^* u^*) = \frac{N_{sub}}{N_{pch}} q'''^* + \frac{\partial p^*}{\partial t^*} \quad (\text{A.I.3})$$

State Equations

$$\rho^* = 1 \quad , \text{ for } h^* \leq 0 \quad (\text{A.I.4a})$$

$$\rho^* = [1 - N_{pch} h^*]^{-1} \quad , \text{ for } h^* > 0 \quad (\text{A.I.4b})$$

Single-Phase Region

For $\rho^* = 1$, the continuity equation can be written as,

$$\frac{\partial u^*}{\partial z^*} = 0 \quad (\text{A.I.5})$$

Thus,

$$u^* = u_i^* \quad (\text{A.I.6})$$

We may subdivide this region into N_ℓ nodes having the same enthalpy change.

The enthalpy at node-n can be thus written as,

$$h_n = h_i + \frac{n}{N_\ell} (h_f - h_i) \quad (\text{A.I.7})$$

or, in nondimensional form,

$$h_n^* = \frac{N_{\text{sub}}}{N_{\text{pch}}} \frac{(n-N_\ell)}{N_\ell} \quad (\text{A.I.8})$$

Assuming that the system pressure is time invariant, we may integrate the energy equation, Eq. (A.I.3), over a node and apply the equation of state for liquid, Eq. (A.I.4a),

$$\int_{L_{\ell n-1}^*}^{L_{\ell n}^*} \frac{\partial h^*}{\partial t^*} dz^* + \int_{L_{\ell n-1}^*}^{L_{\ell n}^*} \frac{\partial (h^* u^*)}{\partial z^*} dz^* = \int_{L_{\ell n-1}^*}^{L_{\ell n}^*} \frac{N_{\text{sub}}}{N_{\text{pch}}} q'''^* dz^* \quad (\text{A.I.9})$$

Assuming a linear enthalpy profile within the node and applying Leibnitz rule,

$$\begin{aligned} \frac{d}{dt^*} \left[\frac{(L_{\ell n}^* - L_{\ell n-1}^*)(h_n^* + h_{n-1}^*)}{2} \right] - h_n^* \frac{dL_{\ell n}^*}{dt^*} + h_{n-1}^* \frac{dL_{\ell n}^*}{dt^*} \\ + (h_n^* - h_{n-1}^*) u_i^* = \frac{N_{\text{sub}}}{N_{\text{pch}}} q'''^* (L_{\ell n}^* - L_{\ell n-1}^*) \end{aligned} \quad (\text{A.I.10})$$

Substituting Eq. (A.I.8) into Eq. (A.I.10) and rearranging we obtain,

$$\frac{dL_{\ell n}^*}{dt^*} = 2u_i^* - 2N_\ell (L_{\ell n}^* - L_{\ell n-1}^*) q'''^* - \frac{dL_{\ell n-1}^*}{dt^*} \quad (\text{A.I.11})$$

Two-Phase Region

From Eq. (A.I.4b),

$$\rho^* h^* = \frac{h^*}{1 + N_{pch} h^*} = \frac{(1 - \rho^*)}{N_{pch}} \quad (\text{A.I.12})$$

Substituting Eq. (A.I.12) into the momentum equation of the homogeneous two-phase mixture, Eq. (A.I.2),

$$-\frac{\partial \rho^*}{\partial t^*} + \frac{\partial}{\partial z^*} [(1 - \rho^*) u^*] = N_{sub} q_{2\phi}'''^* \quad (\text{A.I.13})$$

Equation (A.I.13) can be simplified using the continuity equation, Eq. (A.I.1),

$$\frac{\partial u^*}{\partial z^*} = N_{sub} q_{2\phi}'''^* \quad (\text{A.I.14})$$

Equation (A.I.14) can be integrated assuming a uniform axial power distribution, $q_{2\phi}'''^*$, in the two-phase region. This results in,

$$u^* = u_i^* + N_{sub} q_{2\phi}'''^* (z^* - \lambda^*) \quad (\text{A.I.15})$$

The two-phase region is also divided into N nodes where,

$$h_n = h_f + \frac{(h_e - h_f)}{N} n \quad (\text{A.I.16})$$

Nondimensionalizing Eq. (A.I.16),

$$h_n^* = \frac{n}{N} h_e^* \quad (\text{A.I.17})$$

Substituting Eq. (A.I.17) into Eq. (A.I.4b), the density at the boundary between node- n and node- $(n+1)$ is,

$$\rho_n^* = \left[1 + N_{pch} \frac{n}{N} h_e^* \right]^{-1} \quad (\text{A.I.18})$$

Since

$$h_e^* = \left[\frac{1}{\rho_e^*} - 1 \right] \frac{1}{N_{pch}} \quad (\text{A.I.19})$$

Equations (A.I.18) and (A.I.19) yield,

$$\rho_n^* = \left[1 + \frac{n}{N} \left(\frac{1}{\rho_e^*} - 1 \right) \right]^{-1} \quad (\text{A.I.20})$$

Integrating the continuity equation, Eq. (A.I.1), and using Leibnitz rule,

$$\int_{L_{n-1}^*}^{L_n^*} \frac{\partial \rho^*}{\partial t^*} dz^* + \int_{L_{n-1}^*}^{L_n^*} \frac{\partial (\rho^* u^*)}{\partial z^*} dz^* = 0 \quad (\text{A.I.21})$$

Thus,

$$\frac{dM_n^*}{dt^*} - \rho_n^* \frac{dL_n^*}{dt^*} + \rho_{n-1}^* \frac{dL_{n-1}^*}{dt^*} + \rho_n^* u_n^* - \rho_{n-1}^* u_{n-1}^* = 0 \quad (\text{A.I.22})$$

where M_n^* is the two-phase mass in node-n. Assuming a linear enthalpy profile,

$$\begin{aligned} M_n^* &= \int_{L_{n-1}^*}^{L_n^*} \rho^* dz^* = (L_n^* - L_{n-1}^*) \frac{\ln(\rho_{n-1}^* / \rho_n^*)}{[1/\rho_n^* - 1/\rho_{n-1}^*]} \\ &= (L_n^* - L_{n-1}^*) \rho_{an}^* \end{aligned} \quad (\text{A.I.23})$$

where, the average density in node-n is given by,

$$\rho_{an}^* = \frac{\ell n(\rho_{n-1}^*/\rho_n^*)}{[1/\rho_n^* - 1/\rho_{n-1}^*]} \quad (\text{A.I.24})$$

Differentiating M_n^* with respect to time,

$$\frac{dM_n^*}{dt} = \left(\frac{dL_n^*}{dt} - \frac{dL_{n-1}^*}{dt} \right) \rho_{an}^* + (L_n^* - L_{n-1}^*) \frac{d\rho_{an}^*}{dt} \quad (\text{A.I.25})$$

Differentiating Eq. (I.A.24) and combining the result with Eq. (I.A.20),

$$\frac{d\rho_n^*}{dt} = \frac{N}{(1-\rho_e^*)^2} \left[\ell n(\rho_{n-1}^*/\rho_n^*) + \rho_n^* - \rho_{n-1}^* \right] \frac{d\rho_e^*}{dt} \quad (\text{A.I.26})$$

Substituting Eqs. (A.I.25) & (A.I.26) into Eq. (A.I.22), and rearranging,

$$\begin{aligned} \frac{dL_n^*}{dt} = & - \frac{(L_n^* - L_{n-1}^*)}{(\rho_{an}^* - \rho_n^*)} \frac{N}{(1-\rho_e^*)^2} \left[\ell n\left(\frac{\rho_{n-1}^*}{\rho_n^*}\right) + \rho_n^* - \rho_{n-1}^* \right] \frac{d\rho_e^*}{dt} \\ & - \frac{(\rho_n^* u_n^* - \rho_{n-1}^* u_{n-1}^*)}{(\rho_{an}^* - \rho_n^*)} + \frac{(\rho_{an}^* - \rho_{n-1}^*)}{(\rho_{an}^* - \rho_n^*)} \frac{dL_{n-1}^*}{dt} \end{aligned} \quad (\text{A.I.27})$$

We note that $L_n^* = 1$ when $n = N$ and $\frac{dL_n^*}{dt} = 0$. Equation (A.I.27) can be rewritten in terms of ρ_e^* as,

$$\frac{d\rho_e^*}{dt} = \frac{(1-\rho_e^*)^2}{N} \frac{(\rho_{ae}^* - \rho_e^*)/(1-L_{n-1}^*)}{\ell n\left(\frac{\rho_{n-1}^*}{\rho_e^*}\right) + \rho_e^* - \rho_{n-1}^*}$$

$$\times \left[-\frac{(\rho_e^* u_e^* - \rho_{n-1}^* u_{n-1}^*)}{(1-L_{n-1}^*)} + \frac{(\rho_{ae}^* - \rho_{n-1}^*)}{(1-L_{n-1}^*)} \frac{dL_{n-1}^*}{dt^*} \right] \quad (\text{A.I.28})$$

Equations (A.I.27) and (A.I.28) can be solved using a recurrence formula.

The Adiabatic Riser

The adiabatic riser can be divided into N_R nodes. By continuity we note that,

$$u_{Rn} A_{Rn} = u_e A_{xs} \quad (\text{A.I.29})$$

The non-dimensional riser velocity is thus,

$$u_{Rn}^* = u_e^* / A_{Rn}^* \quad (\text{A.I.30})$$

Integrating the continuity equation in the riser,

$$\frac{dM_{Rn}^*}{dt^*} = (\rho_{Rn-1}^* - \rho_{Rn}^*) u_{Rn}^* \quad (\text{A.I.31})$$

where,

$$M_{Rn}^* = \int_{L_{Rn-1}^*}^{L_{Rn}^*} \rho^* dz^* = \frac{L_R^*}{N_R} \frac{\ln(\rho_{Rn-1}^* / \rho_{Rn}^*)}{[1/\rho_{Rn}^* - 1/\rho_{Rn-1}^*]} \quad (\text{A.I.32})$$

If the number of riser nodes, N_R , is large enough, then ρ_{Rn}^* is close to ρ_{Rn-1}^* , and Eq. (A.I.32) can be expressed as,

$$M_{Rn}^* = \frac{L_R^*}{N_R} \sqrt{\rho_{Rn}^* \rho_{Rn-1}^*} \quad (\text{A.I.33})$$

This eliminates the problem of M_{Rn}^* being undefined when $\rho_{Rn-1}^* = \rho_{Rn}^*$, as occurs for steady state.

Substituting Eq. (A.I.30) into (A.I.31) we obtain,

$$\frac{dM_{Rn}^*}{dt^*} = \frac{u_e^*}{A_R^*} [\rho_{Rn-1}^* - \rho_{Rn}^*] \quad (\text{A.I.34})$$

The Momentum Equation

In order to achieve closure we must consider the externally imposed pressure drop, Δp_{ext}^* . This pressure drop can be partitioned into the temporal acceleration (I), spatial acceleration (a), frictional (f) and gravitational (g) pressure drops, $\Delta p_{\text{ext}}^* = \Delta p_I^* + \Delta p_a^* + \Delta p_f^* + \Delta p_g^*$. These pressure drops come from integrating the two-phase momentum equation. Let us next perform these integrations term-by-term.

The Inertia Term

$$\begin{aligned} \Delta p_I^* &= \frac{d}{dt^*} \left[\int_0^{\lambda^*} \rho^* u^* dz^* + \int_{\lambda^*}^1 \rho^* u^* dz^* + \int_1^{L_R^*} \rho^* u^* dz^* \right] \\ &= \frac{d}{dt^*} \left\{ u_i M_{CH}^* + \sum_{n=1}^{N_R} \frac{u_e^*}{A_R^*} M_{Rn}^* + N_{\text{sub}} q_{2\phi}^{'''} \right. \\ &\quad \left. + \sum_{n=1}^N \left[\frac{(L_n^* - L_{n-1}^*)}{(v_n^* - v_{n-1}^*)} (L_n^* - L_{n-1}^* - v_{n-1}^* M_n^*) + (L_{n-1}^* - \lambda^*) M_n^* \right] \right\} \quad (\text{A.I.35}) \end{aligned}$$

where,

$$M_{CH}^* = \lambda^* + \sum_{i=1}^N M_n^* \quad (A.I.36)$$

Spatial Acceleration Term

$$\Delta p_a^* = \int_0^{1+L_R^*} \frac{\partial}{\partial z^*} (\rho^* u^{*2}) dz^* = \rho_{Re}^* \frac{u_e^{*2}}{A_{Re}^{*2}} - u_i^{*2} \quad (A.I.37)$$

The Frictional Term

$$\begin{aligned} \Delta p_f^* &= \Lambda \left[\int_0^{\lambda^*} \rho^* u^{*2} dz^* + \int_{\lambda^*}^1 \rho^* u^{*2} dz^* + \int_1^{L_R^*} \rho^* u^{*2} dz^* \right] \\ &\quad + K_i u_i^{*2} + K_e \rho_e u_e^{*2} + K_{Re} \rho_{Re}^* u_R^{*2} \\ &= \Lambda \left\{ \lambda^* u_i^{*2} + \sum_{i=1}^N u_{n-1}^{*2} M_n^* + 2N_{sub} u_i^* q_{2\phi}'''^* \right. \\ &\quad \times \sum_{n=1}^N \left[\frac{(L_n^* - L_{n-1}^*)}{(v_n^* - v_{n-1}^*)} (L_n^* - L_{n-1}^* - v_{n-1}^* M_n^*) u_{n-1}^* \right] \\ &\quad + N_{sub}^2 q_{2\phi}'''^{*2} \left(\frac{L_n^* - L_{n-1}^*}{v_n^* - v_{n-1}^*} \right)^2 \left[\frac{1}{2} (L_n^* - L_{n-1}^*) (v_n^* - 3v_{n-1}^*) + v_{n-1}^{*2} M_n^* \right] \\ &\quad \left. + \sum_{n=1}^{N_R} M_{Rn}^* \frac{u_e^{*2}}{A_R^{*2}} + K_i u_i^{*2} + K_e \rho_e^* u_e^{*2} + K_{Re} \rho_{Re} \frac{u_e^{*2}}{A_R^{*2}} \right\} \quad (A.I.38) \end{aligned}$$

The Gravity Head Term

$$\Delta p_g^* = \frac{1}{Fr} \left\{ -bN_{pch} h_i^* \left[\lambda^* - \frac{1}{2N_{\ell}} \sum_{n=1}^{N_{\ell}} (2n-1) (L_{\ell n}^* - L_{\ell n-1}^*) \right] + M_{CH}^* + M_R^* \right\} \quad (A.I.39)$$

It is convenient to define a momentum parameter W^* as,

$$W^* \triangleq \int_0^{L_R^*} \rho^* u^* dz = M_{CH}^* u_i^* + \frac{M_R^*}{A_R^*} \left[u_i^* + N_{sub} q_{2\phi}'''^* (1 - \lambda^*) \right] \\ + N_{sub} q_{2\phi}'''^* \sum_{n=1}^N \left[\frac{(L_n^* - L_{n-1}^*)}{(v_n^* - v_{n-1}^*)} (L_n^* - L_{n-1}^* - v_{n-1}^* M_n^*) + (L_{n-1}^* - \lambda^*) M_n^* \right] \quad (A.I.40)$$

Using this function and the pressure drop components previously evaluated, the momentum equation can be written as,

$$\frac{dW^*}{dt^*} = Eu - \Delta p_a^* - \Delta p_f^* - \Delta p_g^* \quad (A.I.41)$$

Using Eqs. (A.I.35) - (A.I.41) we find that the inlet velocity u_i^* can be expressed as,

$$u_i^* = \left(M_{CH}^* + \frac{M_R^*}{A_R^*} \right)^{-1} \left\{ W^* - \frac{M_R^*}{A_R^*} N_{sub} q_{2\phi}'''^* (1 - \lambda^*) \right. \\ \left. - N_{sub} q_{2\phi}'''^* \sum_{n=1}^N \left[\frac{(L_n^* - L_{n-1}^*)}{(v_n^* - v_{n-1}^*)} (L_n^* - L_{n-1}^* - v_{n-1}^* M_n^*) + (L_{n-1}^* - \lambda^*) M_n^* \right] \right\} \quad (A.I.42)$$

Heated Wall Dynamics

Let us assume the validity of a lumped parameter heater model. Thus,

$$M_{Hc} \frac{dT_H}{dt} = Vq''' - A_{HT} H (T_H - T_b) \quad (A.I.43)$$

where, T_H is the heater temperature and T_b is the local bulk temperature.

Dividing Eq. (A.I.43) by the heated length, L_H ,

$$\rho_H A_H c_{pH} \frac{dT_H}{dt} = A_H q''' - P_H H (T_H - T_b) \quad (\text{A.I.44})$$

Divide Eq. (A.I.44) by $\rho_H A_H c_{pH}$, yields,

$$\frac{dT_H}{dt} = \frac{q'''}{c_{pH} \rho_H} - \frac{P_H H}{c_{pH} \rho_H A_H} (T_H - T_b) \quad (\text{A.I.45})$$

Non-dimensionalizing Eq. (A.I.45) we obtain,

$$\frac{dT_H^*}{dt} = \frac{1}{N_{MH}} \left[q'''^* - K_H (T_H^* - T_b^*) \right] \quad (\text{A.I.46})$$

where,

$$N_{MH} \triangleq \frac{N_{pch}}{N_{sub}} \frac{c_{pH} \rho_H}{c_{pf} \rho_f} A_H^* \quad (\text{A.I.47})$$

$$K_H \triangleq \frac{\rho_H L_H}{c_{pf} \rho_f u_{io} A_{xs}} \quad (\text{A.I.48})$$

The Single-Phase Region

Integrating Eq. (A.I.46) between $L_{\ell n-1}^*$ and $L_{\ell n}^*$, we obtain:

$$\begin{aligned} \int_{L_{\ell n-1}^*}^{L_{\ell n}^*} \frac{dT_H^*}{dt^*} dz^* &= \frac{q'''^* (L_{\ell n}^* - L_{\ell n-1}^*)}{N_{MH}} + \frac{K_{H\ell}}{N_{MH}} T_{H_{\ell n}}^* (L_{\ell n-1}^* - L_{\ell n}^*) \\ &+ \frac{K_{H\ell}}{N_{MH}} \int_{L_{\ell n-1}^*}^{L_{\ell n}^*} T_b^* dz^* \end{aligned} \quad (\text{A.I.49})$$

Using Leibnitz rule,

$$\int_{L_{\ell n-1}^*}^{L_{\ell n}^*} \frac{dT_{H\ell n}^*}{dt^*} dz^* = (L_{\ell n}^* - L_{\ell n-1}^*) \frac{dT_{H\ell n}^*}{dt^*} - \frac{(T_{H\ell n+1}^* - T_{H\ell n}^*)}{2} \frac{dL_{\ell n}^*}{dt^*} - \frac{(T_{H\ell n}^* - T_{H\ell n-1}^*)}{2} \frac{dL_{\ell n-1}^*}{dt^*} \quad (\text{A.I.50})$$

The bulk fluid temperature, T_{bn}^* , in Eq. (A.I.49) is derived using Eq. (A.I.7)

as,

$$T_{bn}^* = \frac{(N_{\ell} - n)}{N_{\ell}} h_i^* \quad (\text{A.I.51})$$

and

$$\begin{aligned} \int_{L_{\ell n-1}^*}^{L_{\ell n}^*} T_b^* dz^* &= \frac{(T_{bn}^* + T_{bn-1}^*)}{2} (L_{\ell n}^* - L_{\ell n-1}^*) \\ &= \frac{(2N_{\ell} - 2n + 1)}{2N_{\ell}} (L_{\ell n}^* - L_{\ell n-1}^*) h_i^* \end{aligned} \quad (\text{A.I.52})$$

Substituting Eqs. (A.I.50) and (A.I.52) into Eq. (A.I.49), we obtain:

$$\begin{aligned} \frac{dT_{H\ell n}^*}{dt^*} &= \frac{(T_{H\ell n+1}^* - T_{H\ell n}^*)}{2(L_{\ell n}^* - L_{\ell n-1}^*)} \frac{dL_{\ell n}^*}{dt^*} + \frac{(T_{H\ell n+1}^* - T_{H\ell n}^*)}{2(L_{\ell n}^* - L_{\ell n-1}^*)} \frac{dL_{\ell n-1}^*}{dt^*} \\ &\quad + \frac{1}{N_{MH}} \left[q'''^* - K_{H\ell} \left(T_{H\ell n}^* - \frac{(2N_{\ell} - 2n + 1)}{2N_{\ell}} h_i^* \right) \right] \end{aligned} \quad (\text{A.I.53})$$

where,

$$K_{H\ell} = \frac{P_H L_H H_{1\phi}}{c_{pf} \rho_f u_{io} A_{xs}} \quad (\text{A.I.54})$$

The single-phase heat transfer coefficient, $H_{1\phi}$, is given by the Dittus-Boelter equation,

$$H_{1\phi} = 0.023 \text{Re}^{0.8} \text{Pr}^{0.4} \frac{k_f}{D_H} \quad (\text{A.I.55})$$

Therefore,

$$K_{H\ell} = 0.023 \frac{k_f}{D_H} \left(\frac{u_i D_H}{v_f} \right)^{0.8} \text{Pr}^{0.4} \frac{P_H L_H}{c_{pf} \rho_f u_{io} A_{xs}} = K_{DB} u_i^{*0.8} \quad (\text{A.I.56})$$

where,

$$K_{DB} = 0.023 \frac{k_f}{D_H^{0.2}} \frac{\text{Pr}^{0.4}}{v_f^{0.8}} \frac{P_H L_H u_{ref}^{0.8}}{c_{pf} \rho_f u_{io} A_{xs}} \quad (\text{A.I.57})$$

Substituting Eq. (A.I.57) into Eq. (A.I.53),

$$\begin{aligned} \frac{dT_{H\ell n}^*}{dt^*} &= \frac{(T_{H\ell n+1}^* - T_{H\ell n}^*)}{2(L_{\ell n}^* - L_{\ell n-1}^*)} \frac{dL_{\ell n}^*}{dt^*} + \frac{(T_{H\ell n}^* - T_{H\ell n-1}^*)}{2(L_{\ell n}^* - L_{\ell n-1}^*)} \frac{dL_{\ell n-1}^*}{dt^*} \\ &+ \frac{1}{N_{MH}} \left[q'''^* - K_{DB} u_i^{*0.8} \left(T_{H\ell n}^* - \frac{(2N_\ell - 2n + 1)}{2N_\ell} h_i^* \right) \right] \end{aligned} \quad (\text{A.I.58})$$

To make this expression more compact the volumetric convective heat in the single-phase node, q'''^* , can be defined as,

$$q_{ln}''' = K_{DB} u_i^{*0.8} \left(T_{Hln}^* - \left[\frac{2N_l - 2n + 1}{2N_l} \right] h_i^* \right) \quad (A.I.59)$$

Two-Phase Region

In the boiling region, the bulk temperature is the saturation temperature, thus $T_b^* = 0$. Integrating Eq. (A.I.46) over the two-phase region, from $z = \lambda^*$ to 1, we obtain:

$$\int_{\lambda^*}^1 \frac{dT_H^*}{dz^*} dz^* = \frac{1}{N_{MH}} \left(q''' - K_{H2\phi} T_{H2\phi}^* \right) (1 - \lambda^*) \quad (A.I.60)$$

where,

$$K_{H2\phi} = \frac{P_H L_H H_{2\phi}}{c_{pf} \rho_f u_{io} A_{xs}}$$

The boiling heat transfer coefficient, $H_{2\phi}$, is given by the Jens-Lottes equation.

Thus,

$$K_{H2\phi} = \frac{\exp(4p/900)}{1296 \times 10^4} \frac{10^6}{3600} \frac{P_H L_H T_{ref}^3 T_{H2\phi}^{*3}}{c_{pf} \rho_f u_{io} A_{xs}} = K_{JL} T_{H2\phi}^{*3} \quad (A.I.61)$$

where,

$$K_{JL} = \frac{\exp(4p/900)}{1296 \times 10^4} \frac{10^6}{3600} \frac{P_H L_H T_{ref}^3}{c_{pf} \rho_f u_{io} A_{xs}}$$

Using Leibnitz rule, as before,

$$\frac{dT_{H2\phi}^*}{dt^*} = \frac{(T_{H2\phi}^* - T_{HN\ell}^*)}{2(1-\lambda^*)} \frac{d\lambda^*}{dt^*} + \frac{(q_{2\phi}''' - K_{JL} T_{H2\phi}^{*4})}{N_{MH}} \quad (\text{A.I.62})$$

Again for convenience, the volumetric convective heat in the two-phase region, $q_{2\phi}'''$, can be defined as,

$$q_{2\phi}''' = K_{JL} T_{H2\phi}^{*4} \quad (\text{A.I.63})$$

Neutron Kinetics

The appropriate equations for point neutron kinetics are given as [Weaver, 1963]:

Neutron Density Balance

$$\frac{dn}{dt} = \frac{\Delta k - \beta}{\ell} n + \lambda_d C \quad (\text{A.I.64})$$

Precursor Density Balance

$$\frac{dC}{dt} = \frac{\beta}{\ell} n - \lambda_d C \quad (\text{A.I.65})$$

Excess Reactivity

$$\Delta k = C_\rho (\bar{\rho}_{CH} - \bar{\rho}_{CHO}) / \bar{\rho}_{CHO} + C_T (T_{HCH} - T_{HCHO}) \quad (\text{A.I.66})$$

or,

$$\Delta k = C_\alpha (\alpha_{CH} - \alpha_{CHO}) + C_T (T_{HCH} - T_{HCHO}) \quad (\text{A.I.67})$$

where C_ρ , C_α , and C_T are the density, void fraction, and doppler coefficient of reactivity, respectively, and $\bar{\rho}_{CH}$, α_{CH} and T_{HCH} are the average density, void fraction and heater temperature over the heated channel. That is,

$$\rho_{CH} = \frac{1}{L_H} \int_0^{L_H} \rho dz \quad (A.I.68)$$

$$\alpha_{CH} = \frac{(\rho_\ell - \bar{\rho}_{CH})}{(\rho_\ell - \rho_\varepsilon)} \quad (A.I.69)$$

$$T_{HCH} = \frac{1}{L_H} \int_0^{L_H} T_H dz \quad (A.I.70)$$

Non-dimensionalizing,

$$\frac{dn^*}{dt^*} = N_\ell \left[\left(\frac{\Delta k}{\beta} - 1 \right) n^* + C^* \right] \quad (A.I.71)$$

$$\frac{dC^*}{dt^*} = N_\lambda [n^* - C^*] \quad (A.I.72)$$

Similarly,

$$\Delta k = C_\rho (\rho_{CH}^* - \rho_{CHO}^*) / \rho_{CHO}^* + C_T T_{Href} (T_{HCH}^* - T_{HCHO}^*) \quad (A.I.73)$$

or,

$$\Delta k = C_\alpha (\alpha_{CH}^* - \alpha_{CHO}^*) + C_T T_{Href} (T_{HCH}^* - T_{HCHO}^*) \quad (A.I.74)$$

where,

$$\rho_{CH}^* = \int_0^1 \rho^* dz = M_{CH}^* \quad (A.I.75)$$

and,

FIGURE 1 Schematic of the boiling channel

FIGURE 2 Linear stability map
(Two nodes in single-phase region)

FIGURE 3 Linear stability map
(Four nodes in single-phase region)

FIGURE 5

LIMIT CYCLE

FIGURE 6

PERIOD DOUBLING

FIGURE 7
 T^2 TORUS

T^2 TORUS

FIGURE 8 Poincaré Sections of T^2 Torus

FIGURE 9
STRANGE ATTRACTOR

STRANGE ATTRACTOR
($N_{PCH} = 106.545$)

FIGURE 10 THREE DIMENSIONAL DISPLAY OF STRANGE ATTRACTOR

STRANGE ATTRACTOR
($N_{PCH} = 106.545$)

FIGURE 11 POINCARÉ SECTIONS OF STRANGE ATTRACTOR

FIGURE 12 LARGEST LYAPUNOV EXPONENT

END

DATE
FILMED

5 / 19 / 93