EGG-NE-10289
July 1992

**Idaho
National
Engineering
Laboratory**

*Managed
by the U.S.
Department
of Energy*

INFORMAL REPORT

**Countercurrent Flow-limiting
Characteristics of a Savannah
River Plant Control Rod Septifoil**

James L. Anderson

*Work performed under
DOE Contract
No. DE-AC07-76ID01570*

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

EGG-NE--10289

DE92 019686

Countercurrent Flow-limiting Characteristics of a Savannah River Plant Control Rod Septifoil

James L. Anderson

July 1992

**Idaho National Engineering Laboratory
EG&G Idaho, Inc.
P. O. Box 1625
Idaho Falls, Idaho 83415-2404**

**Prepared for the
U. S. Department of Energy
Assistant Secretary for Defense Programs
Under DOE Field Office, Idaho
Contract DE-AC07-76ID01570**

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

Countercurrent Flow-limiting Characteristics of a Savannah River Plant Control Rod Septifoil

Prepared by:

J. L. Anderson 7/22/92
J. L. Anderson Date

Reviewed by:

T. K. Larson 7/22/92
T. K. Larson Date

Approved by:

W. G. Lussie 7/22/92
W. G. Lussie Date

D. C. Mecham 7/22/92
D. C. Mecham, Manager Experimental Programs Date

ABSTRACT

Experiments were performed at the Idaho National Engineering Laboratory to investigate the counter-current flow limiting characteristics of a Savannah River Plant control rod septifoil assembly. These experiments were unheated, using air and water as the working fluids. Results are presented in terms of the Wallis flooding correlation for several different control rod configurations. Flooding was observed to occur in the vicinity of the inlet slots/holes of the septifoil, rather than within the rod bundle at the location of the minimum flow area. Nearly identical flooding characteristics of the septifoil were observed for configurations with zero, three, and four rods inserted, but significantly different results occurred with 5 rods inserted.

EXECUTIVE SUMMARY

Experiments were performed at the Idaho National Engineering Laboratory (INEL) to investigate the countercurrent flow-limiting (CCFL) characteristics of a type-Q control rod septifoil assembly at the Savannah River Plant (SRP). It has been postulated that a potential accident scenario is for a septifoil coolant line to become partially or totally blocked during normal reactor operation. In this scenario, the only cooling available for the control rods (being heated from the gamma and neutron flux in the reactor) would be by conductive heat transfer through the septifoil housing and water entering the septifoil from the moderator tank through the slots and holes at the top of the septifoil. The latter mechanism would be influenced by the CCFL characteristics of the septifoil. In order to predict the temperatures of the control rods resulting from this accident scenario, the amount of coolant entering the septifoil must be calculated. Because the coefficients used in the correlations for predicting the CCFL flowrates are geometry dependent, and could have a wide range of values, a set of experiments was performed to obtain the values of the correlation coefficients for several different control rod configurations. These experiments were performed using air and water as the working fluids.

The septifoil contains seven rods: two cadmium control rods that are completely withdrawn on reactor startup, and three full-length and two partial-length lithium-aluminum control rods that are at axial positions depending on reactor control requirements. The bottom of the fully withdrawn rods is at the elevation of the top of the slots in the septifoil housing. Flooding (or CCFL) was observed in the experiments to occur at the general elevation of the septifoil slots/holes. This observation was true for all configurations tested.

This is contrary to the generally accepted theory that flooding will occur at the location of the minimum flow area. It was expected that flooding would occur at the inlet to the septifoil (bottom), the location of the minimum flow area, and a two-phase pool would form above this location. Neither of these expectations occurred. At no time was a pool observed to occur within the septifoil housing. Flow through the 0.25-inch holes was always observed to be liquid flow from the tank into the septifoil housing. Within the septifoil housing, air flow was predominately up the empty channels (those in which the control rod would be fully withdrawn), with liquid flow down the channels with rods and film flow on the inner wall of the septifoil housing.

Results (in terms of the Wallis correlation) from the test series with zero, three, and four rods inserted were virtually identical when using a common flow area and hydraulic diameter (the Wallis nondimensional superficial velocities use a flow area and hydraulic diameter to nondimensionalize the individual flowrates), and resulted in Wallis correlation coefficients within the generally expected values ($m = 0.88$ and $C = 0.88$). However, the results from the series with five rods inserted are significantly different from the other configuration results, with much smaller values for the coefficients ($m=0.46$ and $C=0.64$). Because flooding occurs in the general vicinity of the slots/holes, the liquid flow available for cooling of the control rods further down the septifoil is limited by conditions at this elevation. Analysis will require using the five-rod flooding results anytime that five rods are even partially inserted, leading to the most limiting liquid flow and cooling case.

ACKNOWLEDGEMENTS

The work documented herein was supported by the U. S. Department of Energy, Assistant Secretary for Defense Programs, under the DOE Idaho Field Office, to whom we are grateful. We appreciate the guidance and interest of Dr. Fred E. Witmer and Sharon L. Zeigler, DOE, who helped as technical program monitors. Thomas K. Larson provided extensive help during the experimental proposal, also providing general advice and technical review. William H. Landman provided design and facility construction support. Blaine Merkley and Jody Boyce assisted in the installation and checkout of the instrumentation, and provided support during testing and configuration changes. Dr. M. G. McKellar helped checking the calculations. We are also grateful to Dr. Greg Flach and George Richardson of Savannah River Laboratory for technical information and providing the septifoil spider.

CONTENTS

ABSTRACT.....	iv
EXECUTIVE SUMMARY.....	v
ACKNOWLEDGEMENTS	vi
1. INTRODUCTION	1
2. THE FACILITY	2
2.1 Experimental Apparatus.....	2
3. CONDUCT OF THE EXPERIMENT	7
3.1 Test Matrix	7
4. CCFL CORRELATION.....	10
5. RESULTS OF THE EXPERIMENT	11
5.1 General Observations.....	11
5.2 Typical Test Point.....	11
5.3 Wallis Correlation Results	15
5.4 Consolidated Experimental Results	18
5.5 Wallis Correlation Coefficients.....	18
6. SUMMARY AND CONCLUSIONS	21
7. REFERENCES	22
APPENDIX A - Facility Drawings.....	A-1
APPENDIX B - Uncertainty Analysis.....	B-1
APPENDIX C - Data Tabulations.....	C-1

Countercurrent Flow-limiting Characteristics of a Savannah River Plant Control Rod Septifoil

1. INTRODUCTION

One postulated accident scenario for a Savannah River Plant (SRP) reactor is plugging of a septifoil coolant flow supply line, resulting in either partial or complete termination of coolant to the control rods. It is further postulated that this occurs under normal power operations and remains undetected such that reactor scram does not occur. In this scenario, liquid in the septifoil would reach saturation temperature and would begin to boil. The only water available for cooling of a type-Q septifoil would need to flow into the septifoil through the slots and holes near the top of the septifoil. It has been postulated that liquid flow from the tank through the septifoil slots into the septifoil may be limited owing to the countercurrent flow of steam from the holes or within the rod bundle of the septifoil (CCFL). In fact, if the rate of steam generation within the septifoil is sufficient, no liquid would be able to flow into and down the septifoil, possibly leading to melting of the control rods. Because the coefficients used in the most common CCFL correlation, [the Wallis correlation (1969)]^a are geometry dependent, and because the range of values these coefficients take is broad, an accurate prediction of

a. Referencing is by author-date. See the Reference section for full citations.

the liquid flowrate into the septifoil is not possible without experimental confirmation of the values of the correlation constants. This report documents the results from experiments performed at the Idaho National Engineering Laboratory (INEL) to determine the CCFL characteristics of the septifoil assembly under various configurations using air and water as the working fluids.

The purpose of these experiments was to determine the slope and intercept coefficients of the Wallis CCFL correlation as applied to the SRP Type-Q septifoil. Of particular interest, are the CCFL characteristics within the rod bundle for various rod configurations, and at the slots and holes in the vicinity of the deflector plate. The results will be used for analysis of the septifoil response (particularly the control rods thermal response) during the postulated accident of interrupted coolant flow to the septifoil.

This document describes the experiment facility, conduct of the experiment, and the test results. Appendix A presents drawings of the facility and various components. Appendix B presents an uncertainty analysis of calculated parameters. Appendix C tabulates selected data.

2. THE FACILITY

2.1 Experimental Apparatus

Figure 1 shows the test section used for the experiments. The test section consisted of an upper section fabricated with a segment of 36-cm (14-inch) OD acrylic pipe for the moderator tank simulator. A 2-m (6-foot-) long septifoil simulator with the holes/slots near the top was also fabricated from acrylic pipe, which permitted visual observation of the flooding characteristics. The septifoil included a 2-m (6-foot) segment of an actual septifoil spider. Figure 2 is a cross-sectional view of the septifoil and rod configuration.

The septifoil was terminated approximately 6 inches above the holes/slots. For flooding to occur at the holes/slots or within the control rod bundle, all liquid within the septifoil above the holes/slots would have drained down to the level at which CCFL occurs, so it was not necessary to simulate the upper standpipe section of the guide tube structure. The septifoil simulator ended in a 20-cm (8-inch) diameter tank for air injection and separation of the water and entrained air. Air was injected into the separator tank above the level of the septifoil bottom, flowed down the tank and up into and through the septifoil, exited into the moderator tank simulator, and finally vented to the atmosphere from the top of the tank. Injected liquid was measured and controlled using the steam-air-water (SAW) loop. The liquid was injected into the top of the moderator tank simulator. The level was maintained at 114 cm (45 inches) above the top of the septifoil slots by controlling the liquid injection rate. Liquid from the tank flowed into the septifoil slots and holes, down through the septifoil, and into the separator tank where a level was established based on the naturally occurring

pressure drops that resulted from the test conditions. Liquid exited the separator tank, flowed through the appropriate flow measurement devices, and flowed back into the SAW loop water supply tank for recirculation. Table 1 tabulates pertinent dimensions.

Figure 3 is a piping and instrumentation diagram (P&ID) for the facility. The experiments were performed using the SAW loop in Building TAN-645 at the INEL. The SAW loop comprised pump, piping, and measurement systems for delivering air and water to the experimental apparatus, measuring the individual flows, separating the air and water, venting the air to the atmosphere, and recirculating the water. Individual component flowrates were measured over multiple ranges, permitting a wide range of flows to be controlled and measured. Liquid flowrate was measured using turbine flow meters. Air flowrate was measured using venturi and thermal flow meters. The P&ID in Figure 3 differentiates between the existing SAW loop components and those components of the experimental rig. The primary experimental measurements were the flowrates of the air injected into the apparatus and the flowrate of the liquid draining into and down through the septifoil, upon which the nondimensional superficial velocities are based. Secondary measurements include temperatures, pressures, and differential pressure measurements for determining level and pressure drops in the septifoil. Table 2 lists all measurements and individual uncertainties. Uncertainties are based on manufacturers specifications and calibration results from the INEL Standards and Calibration Laboratory. Appendix A presents drawings of the facility and various components. Appendix B presents an uncertainty analysis of calculated parameters.

Figure 1. Septifoil CCFL test apparatus.

Full-length rods: B, C, E, G, and F
 Partial-length rods: A and D

Note: E and G are stainless steel clad cadmium control rods.
 A, B, C, D, and F are aluminum clad lithium-aluminum control rods.

Figure 2. Cross-section of septifoil, showing rod positions.

Table 1. Pertinent dimensions of the CCFL apparatus.

Component	Wetted Perimeter ^a (m)	Flow Area (m ²)	Hydraulic Diameter (m)
Slot (0.436 in. x 1.155 in.)	0.0713	2.985x10 ⁻⁴	0.016
Hole (0.25 in.)	0.020	3.167x10 ⁻⁵	0.0064
Slots/Holes (12)	1.095	3.963x10 ⁻³	0.0145
Spider ^b	0.458	3.490x10 ⁻⁴	0.0030
Rod	0.075	4.535x10 ⁻⁴	0.0240
Housing, Lucite	0.261	5.418x10 ⁻³	0.0831
Septifoil with			
0 Rods Inserted ^c	1.095	3.963x10 ⁻³	0.0145
3 Rods Inserted	0.946	3.709x10 ⁻³	0.0157
4 Rods Inserted	1.021	3.255x10 ⁻³	0.0128
5 Rods Inserted	1.096	2.802x10 ⁻³	0.010

a. Wetted perimeter, flow area, and hydraulic diameter are based on location of minimum flow area.

b. Spider dimensions are from Vreeland 1991.

c. Minimum flow area is located at the slots/holes.

Table 2. Measurements list.

Measurement ID	Description	Type	Range	Uncertainty
QW_IN_HI	Liquid injection rate - high range	Turbine	100-1000 Lpm	± 3 Lpm
QW_IN_LO	Liquid injection rate - low range	Turbine	10-35 Lpm	± 1 Lpm
QW_OU_HI	Liquid draining rate - high range	Turbine	100-1000 Lpm	± 3 Lpm
QW_OU_LO	Liquid draining rate - low range	Turbine	10-100 Lpm	± 0.2 Lpm
QW_OU_VL	Liquid draining rate - very low range	Turbine	1-15 Lpm	± 0.03 Lpm
QA_IN_VL	Air injection rate - very low range	Thermal flow meter	6-300 sLpm	± 6 sLpm
DP_A_LH	Low-range venturi - high-Range DP	Differential pressure	0-125kPa	± 1.6 kPa
DP_A_LL	Low-range venturi - low-Range DP	Differential pressure	0-12.5kPa	± 0.12 kPa
L_TANK	Liquid level in moderator tank	Differential pressure	0-1.72m	± 0.013 m
L_OUT	Liquid level in outlet tank	Differential pressure	0-2.975m	± 0.038 m
DP_1_2	DP from bottom of rods to holes	Differential pressure	0-25kPa	± 0.25 kPa
DP_2_TNK	DP from holes to moderator tank	Differential pressure	0-25kPa	± 0.25 kPa
P_TANK	Pressure in tank at level of slots	Absolute pressure	0-170kPa	± 0.35 kPa
P_IN	Pressure at inlet to septifoil	Absolute pressure	0-170kPa	± 0.35 kPa
P_A_IN	Pressure at inlet to venturi air measurement	Absolute pressure	0-800kPa	± 1.6 kPa
TF_W_IN	Fluid temperature at inlet measurement	Fluid temperature	273-821 K	± 2 K
TF_W_OU	Fluid temperature at outlet measurement	Fluid temperature	273-821 K	± 2 K
TF_A_IN	Fluid temperature at air inlet	Fluid temperature	273-821 K	± 2 K
TF_TANK	Fluid temperature in tank	Fluid temperature	273-821 K	± 2 K

3. CONDUCT OF THE EXPERIMENT

The experiments were steady-state and performed to the following procedural steps.

1. Insert the control rod simulators into the septifoil for the desired configuration. Perform the daily measurement systems checks, including backfill of the differential pressure sense lines. Record averaged data for an initial drained no-flow condition.
2. Adjust the water injection rate into the moderator tank simulator to a 114-cm (45-inch) liquid level. Set the level control system to automatic.
3. Establish the air injection rate according to the test matrix.
4. Allow the system to stabilize and reach steady-state.
5. Start the data acquisition system, and record data for 5 minutes.
6. Repeat Steps 3 through 5 until complete flooding occurs, or maximum air flowrate is reached.
7. Terminate air and water injection.
8. Record averaged data for a post-test drained no-flow condition.

For analysis, all data were acquired at the rate of 2 samples per second and averaged over the 5-minute recording period. The original time series data were converted into the HDF format^b and archived.

b. HDF (hierarchical data format) is a machine-independent file format developed and supported by the National Center for Supercomputer Applications (NCSA) in Urbana, Illinois.

3.1 Test Matrix

Table 3 tabulates the test configurations and designates the test points. Six different rod configurations, with 15 different air injection rates for each configuration, were tested. The first two configurations, each with five rods, represent maximum power generation. The intent was to obtain the flooding characteristics within the rod bundle in a segment with five control rods inserted (presumably near the top of the septifoil, just below the slots/holes).^c The next three configurations represent four and three rods inserted (two different three-rod configurations to determine sensitivity to rod location) to obtain the flooding characteristics in regions in which three and four rods exist (presumably, these configurations would occur in the middle and lower reaches of the septifoil). The final two configurations were with all rods totally withdrawn to obtain the flooding characteristics of the slots/holes in the septifoil housing (the last configuration was with the upper tube sheet and deflector plate simulators installed to determine the sensitivity of the results to the plates). It is recognized that these final two configurations are not realistic for actual reactor conditions; however, it was desired to obtain the flooding characteristics of the slots/holes for completeness in modeling, which can only be obtained with all rods withdrawn, thus resulting in the flow area equivalent to the flow area through the slots/holes.

c. S5Ab was a repeat of S5A, with the same rod configuration. However, the poison/deflector plate simulators were installed. This test was repeated to verify the non-typical response observed in the original series.

Table 3. Matrix of tests performed.

Test Point Designation	Control Rod Configuration	Air Injection Rate (m/s)
S5A_ (0-15)	5 rods (A,B,C,D,E)	0-7
S5Ab_ (0-15)	5 rods (A,B,C,D,E)	0-7
S4A_ (0-15)	4 rods (A,B,C,D)	0-7
S3aA_ (0-15)	3 rods (A,C,D)	0-7
S3bA_ (0-15)	3 rods (C,D,E)	0-7
S0aA_ (0-15)	0 rods	0-7
S0bA_ (0-15)	0 rods	0-7

4. COUNTERCURRENT FLOW-LIMITING CORRELATION

There are two major correlations used for predicting CCFL, the Wallis and Kutateladze correlations. For comparing air/water and steam/water systems, there is no significant technical reason for choosing one above the other. Because the Wallis correlation is more frequently used, this is the correlation that will be discussed. The Wallis correlation (Wallis 1969) is given by

$$\sqrt{j_g^*} + m \sqrt{j_f^*} = C \quad (1)$$

where

$$j_g = j_g \sqrt{(\rho_g / (g d_h (\rho_f - \rho_g)))}$$

m = slope constant in the Wallis correlation

$$j_f = j_f^* = j_f \sqrt{(\rho_f / (g d_h (\rho_f - \rho_g)))}$$

C = intercept constant in the Wallis correlation

j_g = vapor upflow superficial velocity (m/s)

ρ_g = vapor density (kg/m³)

j_f = liquid downflow superficial velocity (m/s)

d_h = hydraulic diameter ($= 1.447 \times 10^{-2}$ m)

g = gravitational acceleration ($= 9.8$ m/s²)

ρ_f = liquid density (kg/m³)

The superficial velocities in Equation (1) are defined using the minimum flow area through the septifoil. Depending on the number of rods inserted into the septifoil, the minimum flow area, and the location that flooding would be expected to occur is below the slots and inside the septifoil. The SRP reactors use steam rather than air as the working fluid. This raises a question regarding the outcome of the results. This can be answered by considering the fluid material properties in Equation (1). Define parameters β_g and β_f as

$$\beta_g = [\rho_g / (g d_h (\rho_f - \rho_g))]^{1/4}$$

$$\beta_f = [\rho_f / (g d_h (\rho_f - \rho_g))]^{1/4}$$

These parameters are functions only of fluid properties and the hydraulic diameter. Equation (1) can be rewritten as

$$\beta_g \sqrt{j_g} + m \beta_f \sqrt{j_f} = C \quad (2)$$

The parameters β_g and β_f can be used for comparing the expected results when using air/water with the expected behavior of heavy steam/water in the reactor. Assuming local atmospheric conditions with a 1.14-m liquid head (98 kPa and 290 K), the values for these functions using air/water are^d

$$\begin{aligned} \beta_g &= 0.3022 \\ \beta_f &= 1.6301 \end{aligned}$$

These compare to the values calculated for heavy water under full-power reactor conditions (158 kPa and 340°K), assuming saturation temperature at a local pressure (387°K) of

$$\begin{aligned} \beta_g &= 0.2864 \\ \beta_f &= 1.6300 \end{aligned}$$

Use of air/water at local conditions results in a β_g value 5.5% larger than for D₂O and β_f equal to that for D₂O.

Because the slope and intercept constants in the Wallis correlation are predominantly functions of geometry, and the property constants β_g and β_f for air/water are within 5.5% of those for the actual D₂O system, performing these experiments with air/water rather than steam/water appears technically justified. Additionally, performing the experiments with air is much more economic (no

d. Using a hydraulic diameter of 1.447 cm, calculated for both the 12 slots and the 12 0.25-inch holes.

heated system for safety considerations and no need for obtaining a steam supply system) and easier in terms of operation and measurement (no need to account for condensation and moisture content of the steam). However, condensation

effects at the slots/holes resulting from steam mixing with the subcooled water will not be accounted for in these experiments. The magnitude of this effect on the septifoil flooding characteristics is unknown.

5. RESULTS OF THE EXPERIMENT

5.1 General Observations

Flooding (or CCFL) was observed to occur at the general elevation of the slots/holes, or slightly below, an observation true for all configurations tested. This is contrary to the generally accepted theory that flooding will occur at the location of minimum flow area. Figure 4 is an example of the flooding location, being a photograph of a low air flow injection point with four rods inserted (S4A_3b). For these tests, it was expected that flooding would occur at the inlet to the septifoil (bottom of the control rods), and a two-phase pool would form above this location. Neither of these expectations occurred. At no time was a pool observed to occur within the septifoil housing. Flow through the 1/4-inch holes was always observed to be liquid flow from the tank into the septifoil housing. Within the septifoil housing, air flow was predominately up the empty channels, liquid flow was down the channels with rods, and film flow occurred on the inner wall of the septifoil housing. Surging in the test section was observed at low air flowrates, resulting from an insufficient gravity head in the separator tank for the liquid flowrate (the level in the separator tank was oscillating at the bottom entrance to the septifoil housing). These test points were not used in determining the correlation coefficients.

5.2 Typical Test Point

CCFL phenomena are typically time varying, but stationary over a sufficiently long period. The

5-minute data acquisition period used during these experiments is sufficiently long that the averages approach the stationary (or steady-state) value. The time series data for selected measurements and parameters are presented in this section, to support this assertion.

The first parameter that determines the liquid flowrate through the septifoil is the level of the liquid pool in the moderator tank simulator. This level was controlled in the experiments using a proportional-integral-differential (PID) controller, controlling the liquid injection rate into the moderator tank simulator. This level, calculated using a differential pressure transducer to measure the hydrostatic head, is shown in Figure 5 for an all liquid test point (S3bA_0). The liquid level varied 13 cm over the two cycles exhibited during the 5-minute period (a standard deviation of 3.5 %), with an average value of 114.8-cm. Because the parameter of most interest is the nondimensional liquid flowrate (j^*_f) through the septifoil, the square root of this parameter is shown in Figure 6. In this case, the standard deviation is 0.6 %, significantly less than the level variation.^e Thus, the variation in the moderator tank simulator liquid level is a secondary effect on the nondimensional superficial liquid velocity used in the Wallis correlation.

e. This is to be expected since the draining rate depends on the square root of the liquid level; thus, the square root of the nondimensional liquid superficial velocity depends only on the 4th root of the liquid level in the moderator tank simulator.

Figure 4. Photograph of the upper septifoil housing, showing flow patterns for test point S4A_3b.

Figure 5. Moderator tank simulator liquid level for all liquid flow point S3bA_0.

Figure 6. Square root of nondimensional superficial liquid velocity j^*_f for all liquid flow point S3bA_0.

The same variation was observed for a typical two-phase test point. Figure 7 shows the level variation for test point S3bA_5 (a 3-rod

configuration with an inlet air superficial velocity of 0.86 m/s); Figure 8 shows the nondimensional liquid superficial velocity. The variation

Figure 7. Moderator tank simulator liquid level for two-phase flow point S3bA_5 ($j_g = 0.86$ m/s).

Figure 8. Square root of nondimensional superficial liquid velocity j^*_f for two-phase flow point S3bA_5 ($j_g = 0.86$ m/s).

in the liquid level was only 2.0% with a variation in $\sqrt{j_f^*}$ of 0.3%. This reduced variation in the liquid level oscillation was frequently observed (but not always) for the two-phase test points. However, the control point (the average liquid level about which the automatic controller controlled) frequently increased with an increasing air injection rate, the reason for which was never determined.

5.3 Wallis Correlation Results

Two different test series were performed with no rods inserted, S0aA and S0bA, to investigate the effect of adding the mockups of the deflector and poison plates to the assembly. Series S0aA was conducted without the plates, and series S0bA was conducted with the plates. Installation of the plates had no effect on the septifoil flow area. Figure 9 presents the results from the two series in terms of the liquid and air nondimensional superficial velocities. With the exception of some scatter in the S0aA data at low air injection rates, the data from these two series is statistically indistinguishable. The Wallis correlation coefficient

for these two series are S0aA: $m=0.80$, $C=0.85$, and S0bA: $m=0.76$, $C=0.80$.

The conclusion drawn is that the deflector and poison plate mockups had no effect on the flooding characteristics of the septifoil with no rods inserted. Because this configuration is expected to have the most sensitivity to these plates, it can be concluded that the flooding characteristics of the septifoil in general do not depend on the plates, but rather that the flooding characteristics of the septifoil probably depend only on the internal geometry of the septifoil (including the internal characteristics of the slots/holes).

Another sensitivity to geometry investigated was the effect of rod location within the septifoil for two cases with the same number of rods inserted (i.e., three rods). This was investigated in test series S3aA (rods in positions A, C, and D) and S3bA (rods in adjacent positions C, D, and E). Figure 10 presents the results from these two series. The data from the two series are virtually identical. It can, therefore, be concluded that the rod positions (at least for the three-rod case) have no effect on the flooding characteristics of the septifoil. The Wallis

Figure 9. Square root of liquid and air nondimensional superficial velocities for series S0aA and S0bA. No control rods.

Figure 10. Square root of liquid and air nondimensional superficial velocities for series S3aA and S3bA. Three control rods inserted.

correlation coefficients are S3aA: $m=0.98$, $C=0.96$; and S3bA: $m=0.93$, $C=0.94$.

Figure 11 presents the results from the configuration with four rods inserted. The results are different from the three-rod configuration results, with Wallis correlation coefficients of $m=1.08$ and $C=1.16$.

Figure 12 presents results from the configuration with five rods inserted. The S5Ab series was a repeat of the S5A series (same rod configuration, that is, with the poison/deflector plates installed following the S0bA series). This series was performed to verify the results obtained from the original series, because the five-rod configuration results were somewhat different from the other configuration results. As shown in Figure 12, the S5A results were duplicated in the repeat series.

Basically, there is a very large slope change in the results at approximately $\sqrt{j_f^*} = 0.9$. Although this phenomena had been observed in the other configuration results, the S5A slope change is larger and extends over a larger range. Several mechanisms for this slope change were investigated. The tests were performed using two different low-air-flow measurements (both thermal flow meters) to see if perhaps the original measurement was in error. This change had no effect. The tests were repeated using the 3-inch discharge line, rather than the 1.5-inch discharge line normally used, with no appreciable effect on the results. It is concluded that in the region of $\sqrt{j_f^*} > 0.9$ there is an interaction between the CCFL phenomena occurring near the slots/holes and pressure drops occurring within the much smaller flow area of the septifoil region with five-rods inserted. The Wallis correlation coefficients for these two series are S5A: $m=0.45$, $C=0.82$; and S5Ab: $m=0.43$, $C=0.83$.

Figure 11. Square root of liquid and air nondimensional superficial velocities for series S4A. Four control rods inserted.

Figure 12. Square root of liquid and air nondimensional superficial velocities for series S5A and S5Ab. Five control rods inserted.

5.4 Consolidated Experimental Results

Figure 13 presents the results from all of the test series in terms of $\sqrt{j_f^*}$ versus $\sqrt{j_g^*}$. Every configuration has its own unique characteristics, including the slope and intercept values. In an attempt to consolidate the results, all of the nondimensional superficial velocities were converted by using a common flow area and hydraulic diameter in equation (1). The values used were those for the slots/holes used in series S0aA and S0bA, with no rods inserted (Wallis 1969) ($A_f = 3.963 \times 10^{-3} \text{ m}^2$, $dh = 1.447 \text{ cm}$).⁴

Figure 14 presents the results from these calculations. With the exception of the five-rod configuration results, series S5A and S5Ab, this modification collapsed all of the results into a single curve. Excepting the five-rod configuration results, the data can be fit with a single equation, as shown in Figure 15. The resulting slope and

intercept values ($m=0.877$ and $C=0.885$) are well within the typical values for these coefficients (usually on the order of 0.8-1.2 for both coefficients). What is different is the large change in the flow area between the zero-, three-, and four-rod configurations, with no discernible effect on the flooding characteristics of the septifoil.

Figure 16 presents the results from the five-rod configuration, series S5A and S5Ab, along with the curve fit to the data. The resulting values of the coefficients are significantly smaller ($m=0.462$ and $C=0.642$) than the generally accepted values and the coefficient values from the other series in the septifoil CCFL experiments.

5.5 Wallis Correlation Coefficients

Table 4 tabulates the slope and intercept coefficients, m and C in equation (1), for all test series.

Figure 13. Square root of liquid and air nondimensional superficial velocities for all septifoil CCFL test series.

Figure 14. Square root of liquid and air nondimensional superficial velocities for all septifoil CCFL test series, based on slots/holes flow area and hydraulic diameter.

Figure 15. Square root of liquid and air nondimensional superficial velocities for series S0aA, S0bA, S3aA, S3bA, and S4A, based on slots/holes flow area and hydraulic diameter. Five-rod data are excluded.

Figure 16. Square root of liquid and air nondimensional superficial velocities for series S5A and S5Ab, based on slots/holes flow area and hydraulic diameter. Data only for five-rod config-

Table 4. Correlation coefficients of the septifoil CCFL experiments.

Configuration	Slope, m	Intercept, C	r^2 ^a
<u>Based on slots/holes flow area and hydraulic diameter</u>			
0, 3, & 4 rods	0.8773	0.8846	0.972
5 rods	0.4623	0.6420	0.972
<u>Based on each configurations minimum flow area and hydraulic diameter</u>			
S0aA	0.8003	0.8514	0.964
S0bA	0.7622	0.7978	0.991
S3aA	0.9790	0.9559	0.998
S3bA	0.9316	0.9351	0.991
S4A	1.0837	1.1649	0.990
S5A	0.4489	0.8150	0.974
S5Ab	0.4299	0.8321	0.981

a. Goodness of fit parameter. Perfect fit, $r^2 = 1$.

6. SUMMARY AND CONCLUSIONS

Flooding (or CCFL) was observed to occur at the general elevation of the septifoil slots/holes, an observation true for all configurations tested. This is contrary to the generally accepted theory that flooding would occur at the location of minimum flow area. It was expected that flooding would occur at the inlet to the septifoil (bottom of the control rods), and that a two-phase pool would form above this location. Neither of these expectations occurred. At no time was a pool observed to occur within the septifoil housing. Flow through the 0.25-inch holes was always observed to be liquid flow from the tank into the septifoil housing. Within the septifoil housing, air flow was predominately up the empty channels, liquid flow was down the channels, with rods and film flow occurring on the inner wall of the septifoil housing.

Results (in terms of the square root of the Wallis non-dimensional superficial velocities) from the test series with zero, three, and four rods inserted were virtually identical when using a common flow area and hydraulic diameter in Equation (1) and resulted in correlation coefficients within the generally expected values ($m = 0.88$ and $C = 0.88$). However, the results from the series with five rods inserted are significantly different from the other configuration results, with much smaller values for the coefficients ($m=0.46$ and $C=0.64$). Because flooding occurs in the general vicinity of the slots/holes, the liquid flow available for cooling of the control rods further down the septifoil is limited at this elevation. Analysis will require using the five-rod flooding results anytime that five rods are even partially inserted, leading to the most limited liquid flow and cooling.

7. REFERENCES

1. G. B. Wallis, *One Dimensional Two-Phase Flow*, McGraw Hill, Inc., 1969.
2. Vreeland, D. G. 1991. *Control rod power and flow levels based on flow instability limits*, SRL-SAG-91-9057, Appendix A, pp. 23-27.

APPENDIX A
Facility Drawings

APPENDIX A

Facility Drawings

This Appendix presents the facility drawings for the components of the Septifoil CCFL experiments. The following special purpose drawings are included in this Appendix:

CCf11	CCFL Test Facility - Piping and Instrumentation Diagram
CCFL2	CCFL Test Facility - Septifoil Housing Details
CCFL3	CCFL Test Facility - Septifoil Housing Details
CCFL4	CCFL Test Facility - Septifoil Housing Assembly
CCFL5	CCFL Test Facility - Simulated Control Rod Assembly and Details
CCFL9	CCFL Test Facility - Test Rig Installation
CCFL10	CCFL Test Facility - Test Rig Lower Flange Assembly
CCFL11	CCFL Test Facility - Tubesheet & Deflector Simulator

IST'G SAW LOOP

CCFL TEST FACILITY
PIPING AND INSTRUMENTATION
DIAGRAM

SKETCH NO.

CCFL1

SECTION A - A

SECTION B - B

SEPTIFOIL HOUSING SL.
3.75 OD x .25 WALL A

N B - B

SECTION C - C
2 PLACES

EEVE
CRYLIC

CCFL TEST FACILITY
SEPTIFOIL HOUSING
DETAILS

SKETCH NO.

CCFL2

1. ALL MATERIAL 6061-T6 ALUMINUM

HOUSING PLUG DETAIL

PLUG
1/16" S

UPPER HOUSING CAP
DETAIL

GASKET DETAIL
SILICONE RUBBER

PRESSURE TAP PLUG
DETAIL

LOWER HOUSING CAP
DETAIL

CCFL TEST FACILITY
SEPTIFOIL HOUSING
DETAILS

SKETCH NO.

CCFL3

1 GLUE ITEMS USING WELD-ON 40

2. ASSEMBLE SPIDER IN HOUSING TUBE WITH SOLID END TOWARDS UPPER HOUSING PLUG.

B - B

CCFL TEST FACILITY SEPTIFOIL HOUSING ASSEMBLY	
SKETCH NO.	CCFL4

1. ALL MATERIALS 300 SERIES SS

WELD PER S 2.0. WELD HEIGHT NOT TO EXCEED .03"
WELD BUILD-UP ON O.D. NOT TO EXCEED .004".

LONG ROD ASSEMBLY
4 REQ'D

SHORT ROD
DETAIL
7 REQ'D

LONG ROD END
DETAIL

LONG ROD PLUG
DETAIL

CCFL TEST FACILITY
SIMULATED CONTROL ROD
ASSEMBLY AND DETAILS

SKETCH NO.

CCFL5

VIEW LOOKING NORTH

CCFL TEST FACILITY
TEST RIG
INSTALLATION

SKETCH NO.

CCFL9

TEST RIG HOUSING

0.25 THICK O-RING MATL

SEAL FLANGE

3/8 - 16 X 2" LONG

SEPTIFOIL HOUSING

CCFL TEST FACILITY
TEST RIG LOWER FLANGE
ASSEMBLY

SKETCH NO.

CCFL10

TUBESHEET SIMULATOR
DEFLECTOR SIMULATOR

438

CCFL TEST FACILITY
TUBESHEET & DEFLECTOR
SIMULATOR

SKETCH NO.

CCFL11

APPENDIX B

Uncertainty Analysis For CCFL Calculated Parameters

APPENDIX B

Uncertainty Analysis For CCFL Calculated Parameters

The following analysis of the uncertainties in the calculated parameters is based upon the method presented by S. J. Kline and F. A. McClintock^{B-1} for uncertainties in the single sample experiments and accepted by the ASME^{B-2}. The analysis is primarily to provide the uncertainty for the root of the Wallis nondimensional mass fluxes j_g^* and j_f^* . However, the uncertainty in the individual phase densities and mass flow rates are also derived, since the uncertainties in the nondimensional mass fluxes require these.

In this appendix the derivation of the basic uncertainty equations will be presented first. Next the results of the uncertainty analysis for five test cases will be presented.

Method for Uncertainty Analysis

The method for uncertainty analysis of a computed result presented by Kline and McClintock^{B-1} may be summarized by

$$\Delta R = \left[\sum_{i=1}^N \left(\frac{\partial R}{\partial V_i} \Delta V_i \right)^2 \right]^{1/2} \quad (\text{B-1})$$

where

R = result

V_i = i^{th} independent variable

$\Delta R_i, \Delta V_i$ = absolute uncertainty in the result and the independent i^{th} variable, respectively.

Uncertainty in Mass Flow Measurements

The mass flow rate of the gas and liquid were measured by two different methods. The injection gas was measured by a venturi using two differential pressure transducers of 10:1 ranges, to provide a total 10:1 range of the flow rate measurement, and a thermal mass flow meter with a 20:1 range. This provided a total air mass flow rate range of 7-3400 g/min. The liquid draining measurement (upon which the j_f^* number is based) was made using turbines (10:1 range) of sizes 0.5-inch, 1-inch, and 3-inch, providing a total measurement range of 1-1000 LPM. The uncertainty analysis of each measurement type will be presented separately.

Liquid Mass Flow Rate Uncertainty. The liquid mass flow rate, using a turbine, is calculated using

$$\dot{m}_F = Q_F \rho_F \quad (B-2)$$

where

$$\begin{aligned} \dot{m}_F &= \text{liquid mass flow rate (kg/s)} \\ Q_F &= \text{volumetric flow rate measured by the turbine (m}^3\text{/s)} \\ \rho_F &= \text{liquid density (kg/m}^3\text{)} \end{aligned}$$

Applying Equation (B-1) upon Equation (B-2) the measurement uncertainty in the liquid mass flow rate can be given by

$$\frac{\delta \dot{m}_F}{\dot{m}_F} = \frac{\Delta \dot{m}_F}{\dot{m}_F} = \sqrt{\left(\frac{\Delta Q_F}{Q_F}\right)^2 + \left(\frac{\Delta \rho_F}{\rho_F}\right)^2} \quad (B-3)$$

where the absolute uncertainties in the independent variables are represented by Δ 's. The uncertainty in the volumetric flow rate measured by the turbine, ΔQ_F , is given in Table 2 of the main report as $\pm 0.5\%$ of the full scale. The liquid density, ρ_F , is obtained from a curve fit to the steam tables using the measured temperature. Using the uncertainty in the temperature measurement as input to the curve fit results in an uncertainty for the liquid density of $\pm 0.4 \text{ kg/m}^3$. This includes the uncertainty due to the curve fit and the difference between subcooled and saturated liquid densities for the temperature range of interest. Therefore, the uncertainty in the liquid mass flow rate is a constant for a particular flow rate measurement.

Venturi Gas Mass Flow Rate Uncertainty. The mass flow rate of the gas measured using a venturi can be given by

$$\dot{m}_G = \frac{\beta^2}{\sqrt{1-\beta^4}} Y A C \sqrt{\rho_G DP} \quad (B-4)$$

where

$$\begin{aligned} \dot{m}_G &= \text{mass flow rate of the gas (kg/s)} \\ \beta &= \text{diameter ratio (= throat diameter/pipe diameter) (nondimensional)} \\ A &= \text{pipe flow area (m}^2\text{)} \\ C &= \text{venturi discharge coefficient (nondimensional)} \\ \rho_G &= \text{gas density based upon the temperature and pressure upstream of the venturi (kg/m}^3\text{)} \\ DP &= \text{differential pressure between the venturi throat and the upstream pressure tap (N/m}^2\text{ = kg/m}\cdot\text{s}^2\text{ = Pa)} \\ Y &= \text{compressibility correction factor (nondimensional)} \end{aligned}$$

For this analysis Equation (B-4) can be rewritten as

$$\dot{m}_G = K A \sqrt{\rho_G DP} \quad (B-5)$$

where K = a constant obtained from combining all of the constants in Equation (B-4).

Combining Equation (B-5) and Equation (B-1) the uncertainty in the gas mass flow rate is given by

$$\delta \dot{m}_G = \frac{\Delta \dot{m}_G}{\dot{m}_G} = \sqrt{\left(\frac{\Delta K}{K}\right)^2 + \left(\frac{\Delta A}{A}\right)^2 + \frac{1}{4} \left(\frac{\Delta \rho_G}{\rho_G}\right)^2 + \frac{1}{4} \left(\frac{\Delta DP}{DP}\right)^2} \quad (B-6)$$

The gas density, ρ_G , is obtained using the ideal gas law

$$\rho_G = \mathfrak{R}_G \frac{P}{T} \quad (B-7)$$

where

$$\begin{aligned} \mathfrak{R}_G &= \text{constant for the gas in question, air, and the units for the pressure} \\ &\quad \text{and temperature } (=3.483 \text{ kg/m}^3 \cdot \text{K/kPa}) \\ P &= \text{gas pressure (kPa)} \\ T &= \text{gas temperature (K)}. \end{aligned}$$

The uncertainty in the gas density is obtained by substituting Equation (B-7) in Equation (B-1) resulting in

$$\delta \rho_G = \frac{\Delta \rho_G}{\rho_G} = \sqrt{\left(\frac{\Delta \mathfrak{R}_G}{\mathfrak{R}_G}\right)^2 + \left(\frac{\Delta P}{P}\right)^2 + \left(\frac{\Delta T}{T}\right)^2} \quad (B-8)$$

Uncertainty in Nondimensional Mass Fluxes

The root of the liquid nondimensional mass flux, $\sqrt{j_F^*}$, is given by

$$\sqrt{j_F^*} = \frac{(\dot{m}_F / A)^{1/2}}{[g w \rho_F (\rho_F - \rho_G)]^{1/4}} \quad (B-9)$$

where

$$\begin{aligned} A &= \text{minimum flow area in the test vessel (m}^2\text{)} \\ g &= \text{gravitational acceleration (9.78 m/s}^2\text{)} \\ w &= \text{characteristic dimension, hydraulic diameter (m)} \end{aligned}$$

Combining Equations (B-1) and (B-9), the expression for uncertainty results in,

$$\frac{\Delta \sqrt{j_F^*}}{\sqrt{j_F^*}} = \frac{1}{2} \sqrt{\left(\frac{\Delta \dot{m}_F}{\dot{m}_F}\right)^2 + \left(\frac{\Delta A}{A}\right)^2 + \left(\frac{1}{2} \frac{\Delta g}{g}\right)^2 + \left(\frac{1}{2} \frac{\Delta w}{w}\right)^2 + \left(\frac{1}{2} \frac{(2\rho_F - \rho_G) \Delta \rho_F}{(\rho_F - \rho_G) \rho_F}\right)^2 + \left(\frac{1}{2} \frac{\rho_G \Delta \rho_G}{\rho_F - \rho_G \rho_G}\right)^2} \quad (\text{B-10})$$

The root of the gas nondimensional mass flux, $\sqrt{j_G^*}$, is given by

$$\sqrt{j_G^*} = \frac{(\dot{m}_G / A)^{1/2}}{[g w \rho_G (\rho_F - \rho_G)]^{1/4}} \quad (\text{B-11})$$

When Equation (B-11) is substituted into Equation (B-1), the expression for the uncertainty is

$$\frac{\Delta \sqrt{j_G^*}}{\sqrt{j_G^*}} = \frac{1}{2} \sqrt{\left(\frac{\Delta \dot{m}_G}{\dot{m}_G}\right)^2 + \left(\frac{\Delta A}{A}\right)^2 + \left(\frac{1}{2} \frac{\Delta g}{g}\right)^2 + \left(\frac{1}{2} \frac{\Delta w}{w}\right)^2 + \left(\frac{1}{2} \frac{\rho_F \Delta \rho_F}{(\rho_F - \rho_G) \rho_F}\right)^2 + \left(\frac{1}{2} \frac{(\rho_F - 2\rho_G) \Delta \rho_G}{\rho_F - \rho_G \rho_G}\right)^2} \quad (\text{B-12})$$

Uncertainties for Representative Test Cases

A set of 5 tests were selected as being representative of the range of conditions experienced during the Septifoil CCFL experiments. These tests cover the range of air injection rates, and thus liquid draining rates, for which flooding occurred ($j_G > 0.5$ m/s). The results for these tests are presented in Table B-1. The parameters preceded by Δ 's are the absolute uncertainties in the calculated parameters at the 95% confidence level. The parameters preceded by δ 's are the relative uncertainties (ratio of absolute uncertainty to the measurement) in the calculated parameters. The uncertainties in the square root of the nondimensional liquid superficial velocity range from 0.4% of reading, at the high draining rates (52 LPM), to 1.4% at the low draining rates (1 LPM). The uncertainties in the square root of the nondimensional gas superficial velocity range from 2.7% of reading, at a relatively low injection rate (128 SLPM), to 1.0% at the highest air injection rate measured using the thermal flow meter (360 SLPM).

REFERENCES

- B-1 S. J. Kline and F. A. McClintock, "Describing Uncertainty in Single-Sample Experiments," *Mechanical Engineering*, **75**, No. 1, pp. 3-8, January 1953.
- B-2 ASME-Journal of Fluids Engineering, *Guide on Uncertainty Prediction and Presentation Techniques for Authors*, August 1975.

TABLE B-1. Uncertainty calculations for Septifoil CCFL Experiments

Test Section Parameters ¹									
Test ID	j_G (m/s)	T (K)	ΔT (K)	P (kPa)	ΔP (kPa)	ρ_G (kg/m ³)	$\delta \rho_G$ (%)	$\sqrt{j_F^*}$	$\delta \sqrt{j_F^*}$
S0bA_4	0.55	289.3	2	98.33	0.35	1.19	0.9%	0.7617	0.40%
S0bA_7	1.55	289.2	2	97.78	0.35	1.18	0.9%	0.5568	0.50%
S0bA_7b	1.64	289.7	2	97.02	0.35	1.17	0.9%	0.5153	0.54%
S0bA_11	3.81	289.4	2	98.83	0.35	1.19	0.9%	0.2859	0.40%
S0bA_15	7.05	289.5	2	98.72	0.35	1.19	0.9%	0.1097	1.44%

Air Mass Flowrate Parameters									
Thermal Flow meter Calculations									
Test ID	j_G (m/s)	T (K)	ΔT (K)	P (kPa)	ΔP (kPa)	ρ_G (kg/m ³)	$\Delta \rho_G$ (kg/m ³)	Q _{air} (SLPM)	$\delta \dot{m}_G$ (%)
S0bA_4	0.55	292.7	2	804.97	1.6	9.60	0.08	128.4	7
S0bA_7	1.55	291.6	2	802.40	1.6	9.60	0.08	362.9	7
Venturi Flow meter Calculations									
Test ID	j_G (m/s)	T (K)	ΔT (K)	P (kPa)	ΔP (kPa)	ρ_G (kg/m ³)	$\Delta \rho_G$ (kg/m ³)	DP (kPa)	$\delta \dot{m}_G$ (%)
S0bA_7b	1.64	293.2	2	801.81	1.6	9.54	0.08	1.8156	0.12
S0bA_11	3.81	292.2	2	793.62	1.6	9.48	0.08	10.3416	0.12
S0bA_15	7.05	292.3	2	769.99	1.6	9.19	0.08	38.5024	1.6

Draining Turbine Measurement Parameters									
Test ID	j_F (m/s)	T (K)	ΔT (K)	Q (LPM)	ΔQ (LPM)	ρ_F (kg/m ³)	$\Delta \rho_F$ (kg/m ³)	$\dot{m}_F$ (kg/s)	$\delta \dot{m}_F$ (%)
S0bA_4	0.218	289.3	2	51.93	0.20	998.75	0.4	0.864	0.39%
S0bA_7	0.117	289.2	2	27.74	0.20	998.76	0.4	0.462	0.72%
S0bA_7b	0.100	289.7	2	23.76	0.20	998.67	0.4	0.396	0.84%
S0bA_11	0.031	289.4	2	7.32	0.03	998.72	0.4	0.122	0.41%
S0bA_15	0.005	289.5	2	1.08	0.03	998.70	0.4	0.018	2.79%

¹ Assumed uncertainties in constants: $\delta g = 0.2\%$, $\delta K = 2\%$, $\delta A = 0.5\%$, $\delta w = 0.01\%$, $\delta \rho_G = 0.5\%$

APPENDIX C
Data Tabulations for Septifoil CCFL Experiments

APPENDIX C

DATA TABULATIONS FOR SEPTIFOIL CCFL EXPERIMENTS

The following tabulations are data averages of the various data channels over the data acquisition time period. Only selected channels considered to be of interest are presented.

List of Tables

Table C-1	Test Section Measurements and Parameters for Series S0aA	C- 2
Table C-2	Miscellaneous Measurements for Series S0aA	C- 3
Table C-3	Test Section Measurements and Parameters for Series S0bA	C- 4
Table C-4	Miscellaneous Measurements for Series S0bA	C- 5
Table C-5	Test Section Measurements and Parameters for Series S3aA	C- 6
Table C-6	Miscellaneous Measurements for Series S3aA	C- 7
Table C-7	Test Section Measurements and Parameters for Series S3bA	C- 8
Table C-8	Miscellaneous Measurements for Series S3bA	C- 9
Table C-9	Test Section Measurements and Parameters for Series S4A	C-10
Table C-10	Miscellaneous Measurements for Series S4A	C-11
Table C-11	Test Section Measurements and Parameters for Series S5A	C-12
Table C-12	Miscellaneous Measurements for Series S5A	C-14
Table C-13	Test Section Measurements and Parameters for Series S5Ab	C-16
Table C-14	Miscellaneous Measurements for Series S5Ab	C-17

Table C-1. Test Section Measurements and Parameters for Series S0aA

TEST IDS	TF_TANK	P_TANK	L_TANK	DP_1_2	DP_2_TNK	JF	JG	JF_ROOT	JG_ROOT
S0aA_E1	289.7	86.30	0.013	6.20	1.52	0.0000	0.0000	0.0000	0.0000
S0aA_E2	295.8	86.03	-0.020	5.68	1.84	0.0000	0.0000	0.0000	0.0000
S0aA_E3	297.0	85.28	-0.046	5.89	1.22	0.0000	0.0000	0.0000	0.0000
S0aA_0	288.5	97.6	1.154	-0.89	1.12	0.2894	0.0000	0.8769	0.0000
S0aA_0b	293.7	97.5	1.149	-0.85	1.06	0.3230	0.0000	0.9263	0.0000
S0aA_0c	289.9	97.2	1.186	0.05	10.63	2.5400	0.0000	2.5979	0.0000
S0aA_1	294.8	97.5	1.157	-0.04	1.35	0.3130	0.0922	0.9118	0.0904
S0aA_2	295.2	97.5	1.157	0.43	1.45	0.3068	0.1443	0.9027	0.1142
S0aA_4	288.3	97.6	1.157	2.37	1.58	0.2560	0.4916	0.8246	0.2119
S0aA_4b	295.5	97.5	1.156	1.48	1.57	0.2948	0.5448	0.8850	0.2217
S0aA_5	288.1	97.5	1.150	2.60	1.41	0.2538	0.6983	0.8212	0.2526
S0aA_5b	293.2	97.5	1.154	2.19	1.45	0.2895	0.7976	0.8769	0.2688
S0aA_6	288.0	97.5	1.147	3.29	1.46	0.2471	1.0620	0.8102	0.3115
S0aA_7	292.4	97.75	1.190	6.35	0.88	0.131	1.550	0.590	0.3750
S0aA_8	290.7	98.25	1.267	5.98	0.92	0.110	2.090	0.540	0.4370
S0aA_8b	289.9	98.25	1.272	6.02	1.21	0.105	2.020	0.527	0.4300
S0aA_9	290.1	98.22	1.291	6.12	1.08	0.083	2.610	0.469	0.4880
S0aA_10	290.3	98.17	1.273	6.19	1.03	0.049	3.190	0.360	0.5390
S0aA_11	290.4	97.20	1.163	6.17	0.99	0.032	3.790	0.291	0.5870
S0aA_12	290.4	97.96	1.240	6.20	1.02	0.030	4.490	0.281	0.6400
S0aA_13	290.4	99.42	1.277	6.22	1.01	0.020	5.280	0.230	0.6960
S0aA_14	290.2	97.13	1.163	6.14	1.05	0.004	6.150	0.064	0.7480

Table C-2. Miscellaneous Measurements for Series S0aA

Test ID	QW_IN	QW_OUT	MDOT_AIR	P_A_IN	DP_A_L	TF_A_IN	L_OUT	P_IN	P_TANK
S0aA_E1				810.9	0.05	291.8	2.707	87.6	86.3
S0aA_E2				800.1	0.00	289.0	2.706	86.0	86.0
S0aA_E3				796.1	-0.56	291.0	2.712	85.6	85.3
S0aA_0	71.2	68.8	0.000000	123.0	0.07	290.9	2.989	112.1	97.6
S0aA_0b	75.1	76.8	0.000000	799.0	0.11	288.9	2.970	110.5	97.5
S0aA_0c	613.5	604.0	0.000000	801.0	-0.21	292.3	2.939	98.0	97.2
S0aA_1	72.6	74.4	0.00042	798.6	-0.13	289.1	2.968	109.0	97.5
S0aA_2	70.8	73.0	0.00066	798.9	-0.15	289.3	2.967	108.1	97.5
S0aA_4	63.2	60.9	0.00230	809.7	0.05	291.2	2.985	106.9	97.6
S0aA_4b	68.2	70.1	0.00249	798.6	-0.15	289.4	2.964	106.4	97.5
S0aA_5	62.8	60.4	0.00327	807.0	0.07	291.3	2.981	106.6	97.5
S0aA_5b	67.9	68.9	0.00367	798.3	-0.10	289.6	2.965	105.6	97.5
S0aA_6	61.4	58.8	0.00497	810.7	0.10	290.9	2.979	105.6	97.5
S0aA_7	35.1	31.1	0.00720	808.3	1.58	291.1	2.181	99.5	97.8
S0aA_8	19.3	26.1	0.00980	804.5	2.96	291.0	1.806	98.7	98.3
S0aA_8b	10.1	24.9	0.00950	802.3	2.79	291.8	1.788	98.5	98.3
S0aA_9	11.4	19.7	0.01230	795.6	4.75	291.9	1.654	98.5	98.2
S0aA_10	0.0	11.6	0.01490	795.4	7.04	291.9	1.502	98.4	98.2
S0aA_11	0.0	7.6	0.01760	793.8	9.85	291.7	2.769	97.6	97.2
S0aA_12	0.0	7.1	0.02090	790.6	14.14	291.6	2.541	98.4	98.0
S0aA_13	0.0	4.7	0.02500	783.0	20.57	291.5	1.758	99.9	99.4
S0aA_14	0.0	0.9	0.02850	782.2	27.06	291.3	1.569	97.7	97.1

Table C-3. Test Section Measurements and Parameters for Series S0bA

Test ID	TF_TANK	P_TANK	L_TANK	DP_1_2	DP_2_TNK	JF	JG	JF_ROOT	JG_ROOT
S0bA_E1		85.9	-0.002	5.91	1.83				
S0bA_E2		85.9	0.003	5.82	1.78				
S0bA_E3		85.9	0.004	6.08	1.57				
S0bA_E4		85.7	0.011	6.07	1.64				
S0bA_DRN	289.4	105.8	1.710	-0.42	0.47	0.000	0.000	0.0000	0.0000
S0bA_0	289.4	97.2	1.149	-0.67	0.84	0.292	0.000	0.8800	0.0000
S0bA_0E	289.2	97.8	1.240	-0.27	9.74	2.654	0.000	2.6560	0.0000
S0bA_1	289.5	97.2	1.152	1.47	1.19	0.268	0.052	0.8442	0.0688
S0bA_2	289.4	97.0	1.132	2.79	1.34	0.254	0.161	0.8219	0.1211
S0bA_3	289.4	97.4	1.168	4.09	1.35	0.245	0.329	0.8063	0.1732
S0bA_4	289.3	98.3	1.262	6.08	1.26	0.218	0.547	0.7615	0.2237
S0bA_4b	289.2	96.6	1.130	6.28	1.12	0.218	0.558	0.7607	0.2250
S0bA_5	289.2	97.5	1.181	6.12	1.21	0.186	0.844	0.7030	0.2774
S0bA_6	289.2	97.0	1.127	6.08	1.19	0.153	1.167	0.6379	0.3258
S0bA_7	289.2	97.8	1.214	6.13	1.09	0.117	1.552	0.5569	0.3764
S0bA_7b	289.7	97.0	1.167	6.34	0.93	0.100	1.640	0.5148	0.3861
S0bA_8	289.2	97.8	1.228	6.28	0.96	0.078	2.115	0.4554	0.4396
S0bA_9	289.2	97.9	1.230	6.29	0.93	0.057	2.541	0.3886	0.4818
S0bA_10	289.2	97.9	1.236	6.29	0.90	0.036	3.170	0.3098	0.5383
S0bA_10b	290.1	98.5	1.308	5.56	0.86	0.038	3.216	0.3193	0.5425
S0bA_11	289.4	98.8	1.308	6.34	0.80	0.031	3.805	0.2859	0.5910
S0bA_12	289.5	98.4	1.263	6.26	0.91	0.018	4.561	0.2169	0.6462
S0bA_13	289.7	98.9	1.266	6.28	0.91	0.011	5.243	0.1700	0.6937
S0bA_14	289.7	98.6	1.226	6.30	0.90	0.006	6.199	0.1219	0.7537
S0bA_15	289.5	98.7	1.205	6.33	0.87	0.004	7.048	0.1082	0.8040

Table C-4. Miscellaneous Measurements for Series S0bA

Test ID	OW_IN	QW_OUT	MDOT_AIR	P_A_IN	DP_A_L	TF_A_IN	L_OUT	P_IN	P_TANK
S0bA_E1								86.0	85.9
S0bA_E2								85.9	85.9
S0bA_E3								85.8	85.9
S0bA_E4								85.5	85.7
S0bA_DRN	0.0	0.0	0.00000	804.4	0.00	294.2	2.983	119.3	105.8
S0bA_0	71.7	69.3	0.00000	806.7	-0.01	292.6	2.986	110.5	97.2
S0bA_0E	644.0	631.1	0.00000	799.5	0.00	294.4	2.949	99.8	97.8
S0bA_1	65.7	63.8	0.00024	806.6	-0.01	292.7	2.985	106.8	97.2
S0bA_2	62.5	60.5	0.00075	806.5	0.01	292.8	2.984	104.8	97.0
S0bA_3	61.4	58.2	0.00153	805.5	0.07	292.9	2.983	103.4	97.4
S0bA_4	53.8	51.9	0.00257	805.0	0.20	292.7	2.975	99.7	98.3
S0bA_4b	54.3	51.8	0.00258	801.7	0.22	293.5	2.973	99.8	96.6
S0bA_5	45.7	44.2	0.00393	804.3	0.45	292.2	2.757	98.0	97.5
S0bA_6	38.2	36.4	0.00541	803.5	0.83	291.9	2.457	97.5	97.0
S0bA_7	29.8	27.8	0.00726	802.4	1.44	291.8	2.042	98.3	97.8
S0bA_7b	25.8	23.7	0.00760	801.8	1.81	293.2	1.969	97.5	97.0
S0bA_8	19.8	18.6	0.00990	801.1	3.07	292.2	1.753	98.4	97.8
S0bA_9	0.5	13.5	0.01189	799.5	4.44	292.1	1.635	98.3	97.9
S0bA_10	0.0	6.6	0.01484	796.8	6.98	292.1	1.534	98.4	97.9
S0bA_10b	0.0	9.1	0.01509	796.2	7.24	292.8	2.979	102.1	98.5
S0bA_11	2.4	7.3	0.01797	793.6	10.33	292.2	2.611	99.4	98.8
S0bA_12	0.0	4.2	0.02143	788.1	14.92	292.0	1.817	99.0	98.4
S0bA_13	0.0	2.6	0.02476	784.0	20.22	292.2	1.484	99.6	98.9
S0bA_14	0.0	1.3	0.02918	777.5	26.79	292.2	1.374	99.4	98.6
S0bA_15	0.0	1.1	0.03324	770.0	38.46	292.3	1.337	99.6	98.7

Table C-5. Test Section Measurements and Parameters for Series S3aA

TEST IDS	IF_TANK	P_TANK	L_TANK	DP_1_2	DP_2_TNK	JF	JF_ROOT	JG	JG_ROOT
S3aA_E1		86.5	-0.023	6.01	1.28				
S3aA_E2		86.3	-0.034	6.80	0.41				
S3aA_E3		86.2	-0.034	6.91	0.31				
S3aA_E4		85.7	-0.005	6.13	1.62				
S3aA_E5		85.9	0.002	6.21	1.60				
S3aA_E6		85.8	-0.001	6.65	1.22				
S3aA_DRN	288.0	106.0	1.695	-0.05	0.19	0.000	0.0000	0.000	0.0001
S3aA_0	289.6	97.5	1.186	0.13	0.32	0.318	0.9017	0.000	0.0003
S3aA_0B	287.2	97.2	1.156	-0.24	1.10	0.313	0.8931	0.001	0.0109
S3aA_0C	288.0	97.3	1.173	-0.43	0.88	0.318	0.9004	0.000	0.0020
S3aA_0D	288.0	89.9	0.418	0.39	3.65	1.252	1.7880	0.000	0.0008
S3aA_0E		98.5	1.295	1.27	13.21	2.484	2.5186	0.000	0.0000
S3aA_1	289.5	97.7	1.266	3.21	0.62	0.293	0.8542	0.061	0.0728
S3aA_2	289.5	97.6	1.306	4.46	0.65	0.282	0.8490	0.169	0.1218
S3aA_3	289.6	97.1	1.266	6.71	0.63	0.256	0.8080	0.338	0.1718
S3aA_3B	288.1	97.5	1.195	5.95	1.30	0.252	0.8026	0.337	0.1720
S3aA_4	289.5	97.2	1.307	6.77	0.57	0.220	0.7495	0.580	0.2252
S3aA_5	289.3	98.4	1.202	6.78	0.52	0.191	0.6975	0.807	0.2666
S3aA_5B	287.9	97.5	1.193	6.24	1.19	0.184	0.6850	0.839	0.2715
S3aA_6	289.3	98.4	1.200	6.78	0.47	0.159	0.6376	1.182	0.3226
S3aA_7	289.2	98.5	1.216	6.80	0.46	0.135	0.5861	1.595	0.3748
S3aA_7B	287.9	98.0	1.236	6.25	1.13	0.138	0.5943	1.601	0.3754
S3aA_8	289.3	98.6	1.231	6.76	0.42	0.113	0.5364	2.137	0.4339
S3aA_9	289.3	98.8	1.251	6.76	0.38	0.094	0.4889	2.604	0.4793
S3aA_10	289.4	98.8	1.255	6.77	0.34	0.076	0.4402	3.165	0.5284
S3aA_10B	287.6	98.0	1.243	6.20	1.11	0.078	0.4455	3.198	0.5308
S3aA_11	287.1	98.1	1.251	6.20	1.07	0.061	0.3941	3.935	0.5891
S3aA_12	287.1	98.2	1.255	6.20	1.04	0.043	0.3297	4.547	0.6335
S3aA_13	287.1	98.2	1.255	6.20	1.04	0.043	0.3297	4.547	0.6335
S3aA_13B	287.1	98.2	1.236	6.28	0.97	0.030	0.2755	5.339	0.6864
S3aA_14	287.2	98.3	1.230	6.26	0.98	0.019	0.2204	6.101	0.7340
S3aA_15	286.9	98.2	1.207	6.20	0.96	0.010	0.1606	7.046	0.7888

Table C-6. Miscellaneous Measurements for Series S3aA

TEST IDS	QW_IN	QW_OUT	MDCT_AIR	P_A_IN	DP_A_LL	TF_A_IN	L_OUT	P_IN	P_TANK
S3aA_E1								86.5	86.5
S3aA_E2								86.4	86.3
S3aA_E3								86.3	86.2
S3aA_E4								85.7	85.7
S3aA_E5								85.7	85.9
S3aA_E6								85.6	85.8
S3aA_DRN	0.1	0.0	0.00000	796.5	0.00	290.0	2.991	119.3	106.0
S3aA_L0	72.5	70.9	0.00000	803.9	-0.02	290.2	2.990	110.7	97.5
S3aA_L0B	71.5	69.6	0.00001	800.7	-0.01	286.9	2.992	109.5	97.2
S3aA_L0C	72.4	70.7	0.00000	799.2	0.01	289.1	2.982	110.2	97.3
S3aA_L0D	278.0	278.6	0.00000	799.8	0.00	289.4	2.295	98.8	89.9
S3aA_L0E								96.1	98.5
S3aA_L1	67.4	65.1	0.00026	804.3	-0.02	290.4	2.987	106.8	97.7
S3aA_L2	64.4	62.8	0.00074	804.8	0.00	290.6	2.981	105.4	97.6
S3aA_L3	58.1	56.9	0.00147	805.0	0.05	290.7	2.980	101.9	97.1
S3aA_L3B	58.1	56.2	0.00148	799.0	0.08	288.8	2.984	101.2	97.5
S3aA_L4	50.9	49.0	0.00252	807.2	0.17	290.8	2.818	99.4	97.2
S3aA_L5	43.9	42.4	0.00356	806.6	0.36	291.1	2.620	98.3	98.4
S3aA_L5B	43.2	40.9	0.00368	799.3	0.43	288.0	2.564	97.6	97.5
S3aA_L6	37.3	35.4	0.00520	805.9	0.76	290.9	2.328	98.4	98.4
S3aA_L7	32.2	29.9	0.00703	804.9	1.34	290.9	2.109	98.5	98.5
S3aA_L7B	32.1	30.6	0.00705	798.6	1.53	287.5	2.115	98.3	98.0
S3aA_L8	26.3	25.1	0.00943	803.1	2.76	290.9	1.923	98.7	98.6
S3aA_L9	21.9	20.8	0.01151	801.5	4.13	290.8	1.771	99.0	98.8
S3aA_L10	18.2	16.9	0.01399	799.2	6.14	290.7	1.669	99.1	98.8
S3aA_L10B	16.7	17.3	0.01410	794.5	6.19	286.8	1.683	98.5	98.0
S3aA_L11	7.5	13.5	0.01740	832.9	9.01	286.3	1.587	98.6	98.1
S3aA_L12	0.0	9.5	0.02013	830.4	12.14	285.6	1.495	99.0	98.2
S3aA_L13	0.0	9.5	0.02013	830.4	12.14	285.6	1.495	99.0	98.2
S3aA_L13B	0.0	6.6	0.02363	784.9	17.81	284.2	2.430	99.0	98.2
S3aA_L14	0.0	4.2	0.02703	779.5	23.75	284.3	1.614	99.2	98.3
S3aA_L15	0.0	2.2	0.03122	773.4	32.44	284.0	1.495	99.2	98.2

Table C-7. Test Section Measurements and Parameters for Series S3bA

TEST IDs	TF_TANK	P_TANK	L_TANK	DP_1_2	DP_2_TNK	JF	JG	JF_ROOT	JG_ROOT
S3bA_E1		86.4	-0.002	5.81	1.95				
S3bA_E2		86.5	0.000	6.24	1.46				
S3bA_E3		86.6	0.000	6.31	1.44				
S3bA_E4		86.4	-0.002	6.27	1.44				
S3bA_E5		86.6	0.001	5.93	1.85				
S3bA_E6		86.6	-0.004	6.01	1.67				
S3bA_DRN	289.5	107.9	1.696	-0.32	0.34	0.000	0	0.0000	0
S3bA_0	289.4	97.7	1.148	0.31	0.50	0.311	0	0.8909	0
S3bA_0B	290.0	97.9	1.171	-0.19	0.84	0.309	0	0.8885	0
S3bA_0C	289.7	97.9	1.148	-0.33	1.00	0.308	0	0.8871	0
S3bA_0D	289.7	102.3	1.606	-0.21	2.84	1.027	0	1.6190	0
S3bA_0E	289.6	100.5	1.412	0.63	14.56	2.556	0	2.5550	0
S3bA_1	289.6	98.1	1.181	2.95	0.72	0.284	0.057	0.8521	0.0710
S3bA_2	289.6	98.0	1.172	4.20	0.73	0.271	0.164	0.8317	0.1200
S3bA_3	289.7	96.2	1.190	5.12	0.77	0.262	0.325	0.8185	0.1691
S3bA_4	289.7	98.3	1.202	6.60	0.66	0.232	0.557	0.7703	0.2214
S3bA_5	289.8	98.2	1.188	6.62	0.60	0.201	0.820	0.7162	0.2684
S3bA_5B	290.0	98.2	1.205	6.43	0.80	0.192	0.849	0.7000	0.2731
S3bA_6	289.7	98.4	1.215	6.66	0.53	0.160	1.198	0.6395	0.3247
S3bA_7	289.9	98.4	1.209	6.68	0.51	0.134	1.600	0.5841	0.3750
S3bA_7B	290.0	98.4	1.229	6.49	0.69	0.125	1.661	0.5653	0.3822
S3bA_8	289.5	98.5	1.226	6.71	0.56	0.122	2.056	0.5573	0.4255
S3bA_9	289.6	98.8	1.253	6.70	0.54	0.102	2.595	0.5111	0.4783
S3bA_10	289.7	98.8	1.254	6.69	0.52	0.079	3.264	0.4495	0.5364
S3bA_10B	290.2	98.7	1.253	6.58	0.67	0.083	3.220	0.4598	0.5324
S3bA_11	289.9	99.0	1.275	6.72	0.53	0.069	3.822	0.4198	0.5806
S3bA_12	289.8	99.0	1.270	6.70	0.52	0.036	4.549	0.3029	0.6336
S3bA_12B	290.3	99.2	1.287	6.08	0.58	0.039	4.495	0.3138	0.6298
S3bA_13	290.0	99.3	1.271	6.72	0.49	0.029	5.359	0.2727	0.6881
S3bA_14	289.9	99.4	1.255	6.64	0.49	0.015	6.185	0.1982	0.7393
S3bA_15	289.8	99.3	1.231	6.58	0.49	0.009	7.033	0.1477	0.7883

Table C-8. Miscellaneous Measurements for Series S3bA

TEST IDS	QW_IN	QW_OUT	MDOT_AIR	P_A_IN	DP_A_L	TF_A_IN	L_OUT	P_IN	P_TANK
S3bA_E1								86.3	86.4
S3bA_E2								86.4	86.5
S3bA_E3								86.4	86.6
S3bA_E4								86.3	86.4
S3bA_E5								86.6	86.6
S3bA_E6								86.5	86.6
S3bA_DRN								121.3	107.9
S3bA_0	0.2	0.0	0.00000	806.3	0.01	293.0	2.987	110.0	97.7
S3bA_0B	71.5	69.2	0.00000	801.3	-0.02	292.5	2.991	110.4	97.9
S3bA_0C	72.3	68.8	0.00000	803.4	-0.02	292.9	2.985	110.5	97.9
S3bA_0D	70.8	68.6	0.00000	802.9	0.02	293.4	2.984	112.9	102.3
S3bA_0E	228.4	228.4	0.00000	804.3	0.01	293.3	2.979	97.5	100.5
S3bA_1	582.1	568.8	0.00000	802.8	0.01	293.2	2.950	106.3	98.1
S3bA_2	64.9	63.3	0.00025	803.7	-0.02	292.0	2.988	104.5	98.0
S3bA_3	62.0	60.3	0.00072	802.0	0.00	292.0	2.986	103.3	98.2
S3bA_4	60.3	58.4	0.00143	803.7	0.05	292.0	2.983	99.6	98.3
S3bA_5	53.4	51.7	0.00245	803.6	0.17	292.0	2.979	98.5	98.2
S3bA_5B	46.6	44.7	0.00359	804.6	0.37	291.9	2.738	98.5	98.2
S3bA_6	44.1	42.7	0.00372	803.9	0.42	292.3	2.647	98.8	98.4
S3bA_7	37.3	35.6	0.00527	802.2	0.79	291.7	2.310	98.8	98.4
S3bA_7B	31.5	29.7	0.00703	804.3	1.36	291.7	2.101	96.8	96.4
S3bA_8	28.8	27.9	0.00730	802.0	1.66	291.8	2.026	96.8	96.4
S3bA_9	28.9	27.1	0.00906	800.8	2.56	291.6	1.995	99.3	98.5
S3bA_10	24.5	22.8	0.01146	797.6	4.12	291.4	1.825	99.3	98.8
S3bA_10B	17.7	17.6	0.01441	798.1	6.53	291.2	1.686	99.2	98.7
S3bA_11	20.0	18.4	0.01417	797.2	6.33	291.3	1.700	99.7	99.0
S3bA_12	13.0	15.4	0.01689	795.7	9.05	291.1	1.600	99.9	99.0
S3bA_12B	0.0	8.0	0.02012	790.7	14.12	290.7	1.443	101.4	99.2
S3bA_13	0.1	8.6	0.01989	790.3	13.88	291.0	2.930	100.2	99.3
S3bA_14	0.0	6.5	0.02377	785.7	18.42	290.5	2.330	100.2	99.4
S3bA_15	0.0	3.4	0.02744	780.9	25.01	290.5	1.616	100.3	99.3
	0.0	1.9	0.03116	774.8	33.07	290.5	1.407		

Table C-9. Test Section Measurements and Parameters for Series S4A

TEST IDS	TF_TANK	P_TANK	L_TANK	DP_1_2	DP_2_TNK	JF	JG	JF_ROOT	JG_ROOT
S4A_E1		84.5		5.71	1.49				
S4A_E2		84.7		5.83	1.38				
S4A_E3		85.3		5.73	1.95				
S4A_E4		85.6		5.71	1.98				
S4A_E5		85.6		6.27	1.44				
S4A_0	290.1	96.1	1.152	-0.86	1.30	0.364	0.000	1.0150	0.0000
S4A_0B	290.2	96.6	1.170	-0.63	1.06	0.358	0.000	1.0060	0.0000
S4A_1	291.0	96.5	1.190	2.60	1.51	0.328	0.063	0.9634	0.0782
S4A_2	291.2	96.6	1.196	3.39	1.55	0.317	0.165	0.9464	0.1262
S4A_3	291.5	96.5	1.191	4.95	1.52	0.299	0.322	0.9201	0.1759
S4A_3B	292.1	96.8	1.140	4.53	1.36	0.296	0.326	0.9146	0.1773
S4A_4	291.7	96.8	1.210	5.88	1.41	0.268	0.532	0.8705	0.2263
S4A_5	291.7	96.8	1.211	5.89	1.33	0.239	0.768	0.8213	0.2719
S4A_5B	293.0	97.0	1.156	5.94	1.23	0.230	0.779	0.8066	0.2738
S4A_6	292.0	96.7	1.203	5.89	1.29	0.208	1.071	0.7668	0.3211
S4A_7	292.0	96.9	1.222	5.93	1.24	0.187	1.429	0.7272	0.3711
S4A_8	292.0	96.8	1.215	5.92	1.23	0.170	1.821	0.6935	0.4188
S4A_8B	292.6	97.6	1.225	5.90	1.24	0.169	1.833	0.6921	0.4207
S4A_9	290.5	97.3	1.245	5.92	1.20	0.152	2.271	0.6556	0.4688
S4A_10	291.0	97.5	1.255	5.89	1.21	0.128	2.743	0.6010	0.5152
S4A_10B	292.4	97.8	1.248	5.90	1.19	0.132	2.678	0.6114	0.5089
S4A_11	289.9	97.9	1.277	6.02	1.09	0.112	3.390	0.5623	0.5739
S4A_12		98.0	1.270	5.99	0.96	0.099	3.879	0.5297	0.6138
S4A_12B	292.6	97.7	1.238	5.92	1.14	0.086	3.935	0.4926	0.6167
S4A_13		96.7	1.141	5.87	1.13	0.066	4.655	0.4315	0.6701
S4A_14		97.5	1.219	5.81	1.18	0.040	5.213	0.3344	0.7102
S4A_15	291.0	96.7	1.133	5.80	1.11	0.021	6.068	0.2457	0.7648

Table C-10. Miscellaneous Measurements for Series S4A

TEST IDS	QW_IN	QW_OUT	MDOT_AIR	P_A_IN	DP_A_L	TF_A_IN	L_OUT	P_IN	P_TANK
S4A_E1								85.2	84.5
S4A_E2								85.3	84.7
S4A_E3								85.7	85.3
S4A_E4								85.8	85.6
S4A_E5								85.9	85.6
S4A_0	71.81	71.09	0.00000	800.7	-0.02	290.2	2.978	109.3	96.1
S4A_0B	72.26	69.89	0.00000	803.5	0.00	285.8	2.982	110.0	96.6
S4A_1	64.88	64.12	0.00024	800.4	-0.02	290.3	2.974	104.7	96.5
S4A_2	62.39	61.86	0.00062	799.6	-0.01	290.3	2.974	103.3	96.6
S4A_3	59.09	58.47	0.00121	799.4	0.03	290.5	2.973	101.4	96.5
S4A_3B	58.62	57.77	0.00123	802.0	0.04	288.5	2.970	102.2	96.8
S4A_4	53.02	52.34	0.00200	799.2	0.11	290.6	2.970	98.1	96.8
S4A_5	47.39	46.58	0.00289	799.0	0.24	290.5	2.747	97.4	96.8
S4A_5B	46.14	44.94	0.00293	806.6	0.26	288.3	2.755	97.7	97.0
S4A_6	41.54	40.61	0.00403	799.3	0.47	290.6	2.482	97.4	96.7
S4A_7	37.31	36.52	0.00539	799.2	0.82	290.3	2.296	97.6	96.9
S4A_8	34.26	33.21	0.00686	799.1	1.30	290.0	2.175	97.6	96.8
S4A_8B	35.19	33.08	0.00694	802.5	1.48	288.0	2.186	98.4	97.6
S4A_9	31.50	29.68	0.00865	803.3	2.28	286.0	2.069	98.3	97.3
S4A_10	27.22	24.95	0.01044	802.0	3.33	286.0	1.894	98.5	97.5
S4A_10B	28.12	25.81	0.01018	802.3	3.19	287.7	1.907	98.7	97.8
S4A_11	19.64	21.85	0.01300	799.9	5.23	287.6	1.773	98.9	97.9
S4A_12								99.2	98.0
S4A_12B	17.76	16.77	0.01493	798.3	6.93	287.5	1.644	98.8	97.7
S4A_13								97.9	96.7
S4A_14								98.6	97.5
S4A_15	0.01	4.17	0.02291	787.6	16.86	287.7	1.923	97.9	96.7

Table C-11. Test Section Measurements and Parameters for Series S5A

TEST IDS	TF_TANK	P_TANK	L_TANK	DP_1_2	DP_2_TNK	JF	JG	JF_ROOT	JG_ROOT
S5A_E1		85.7	0.001	6.21	1.10				
S5A_E2		86.0	0.029	6.20	1.59				
S5A_E3		85.9	0.047	6.19	1.60				
S5A_E4		85.6	-0.070	5.52	1.74				
S5A_0	289.2	97.3	1.130	0.32	1.00	0.454	0.000	1.1990	0.0000
S5A_0B	290.3	98.1	1.248	-0.31	0.90	0.462	0.000	1.2100	0.0000
S5A_0D		96.8	1.158	0.31	3.89	1.224	0.000	1.9693	0.0000
S5A_0E	289.2	97.9	1.193	-0.93	1.72	0.463	0.009	1.2110	0.0308
S5A_DRN	289.3	106.2	1.651	-0.75	0.61	0.000	0.005	0.0017	0.0239
S5A_1	290.4	98.1	1.248	5.03	1.08	0.388	0.083	1.1080	0.0948
S5A_1B		98.3	1.310	6.43	0.91	0.431	0.074	1.1683	0.0897
S5A_2	290.3	98.1	1.250	6.06	1.03	0.373	0.178	1.0870	0.1393
S5A_2B		98.3	1.314	6.42	0.88	0.400	0.185	1.1255	0.1418
S5A_2D	289.3	98.1	1.214	4.87	1.59	0.389	0.177	1.1100	0.1390
S5A_3		98.1	1.246	6.35	0.81	0.339	0.331	1.0364	0.1897
S5A_3B		98.3	1.311	6.45	0.80	0.359	0.333	1.0650	0.1903
S5A_4	290.3	98.0	1.234	6.35	0.77	0.312	0.543	0.9942	0.2431
S5A_4B		0.8	1.328	6.45	0.76	0.338	0.535	1.0335	0.2416
S5A_4D	289.2	98.1	1.207	5.84	1.44	0.326	0.515	1.0170	0.2370
S5A_5	290.2	97.8	1.195	6.35	0.70	0.297	0.820	0.9703	0.2985
S5A_5B		98.4	1.322	6.47	0.72	0.324	0.810	1.0119	0.2972
S5A_6	289.9	97.8	1.199	6.35	0.70	0.287	1.104	0.9528	0.3466
S5A_6B		98.4	1.319	6.47	0.70	0.303	1.115	0.9784	0.3487

Table C-11 (Cont). Test Section Measurements and Parameters for Series S5A

TEST IDs	TF_TANK	P_TANK	L_TANK	DP_1_2	DP_2_TNK	JF	JG	JF_ROOT	JG_ROOT
S5A_7	289.2	97.8	1.224	6.35	0.71	0.271	1.429	0.9266	0.3944
S5A_7B	290.5	98.8	1.339	6.34	0.85	0.265	1.442	0.9168	0.3969
S5A_7C		98.8	1.356	6.49	0.66	0.286	1.462	0.9501	0.3998
S5A_7D	289.1	98.3	1.229	5.88	1.35	0.266	1.374	0.9170	0.3874
S5A_8		98.0	1.228	6.15	0.99	0.181	1.926	0.7565	0.4585
S5A_8B	289.1	98.2	1.214	5.86	1.35	0.263	1.534	0.9126	0.4091
S5A_8C	288.9	98.7	1.259	5.92	1.29	0.244	1.676	0.8797	0.4282
S5A_8D	288.7	98.4	1.229	5.92	1.26	0.239	1.808	0.8701	0.4446
S5A_9		98.5	1.290	6.24	0.90	0.149	2.272	0.6873	0.4985
S5A_9D	288.6	98.5	1.237	5.92	1.19	0.192	2.168	0.7795	0.4870
S5A_10		98.7	1.301	6.21	0.87	0.096	2.755	0.5511	0.5492
S5A_10B		99.0	1.306	5.47	1.36	0.105	2.770	0.5776	0.5508
S5A_11		97.4	1.171	5.11	0.99	0.055	3.309	0.4159	0.5999
S5A_12		98.0	1.239	6.03	1.03	0.045	3.951	0.3791	0.6565
S5A_12B		98.6	1.314	6.27	0.74	0.047	3.910	0.6537	0.6537
S5A_13		97.7	1.231	6.33	0.72	0.027	4.641	0.2937	0.7105

Table C-12. Miscellaneous Measurements for Series S5A

TEST IDS	QW_IN	QW_OUT	MDOT_AIR	P_A_IN	DP_A_L	TF_A_IN	L_OUT	P_IN	P_TANK
S5A_E1								85.6	85.7
S5A_E2								85.6	86.0
S5A_E3								85.5	85.9
S5A_E4								85.4	85.6
S5A_0	79.8	76.3	0.00000	806.6	0.00	290.2	2.978	108.6	97.3
S5A_0B	80.9	77.7	0.00000	802.4	0.01	287.9	2.981	110.4	98.1
S5A_0D								105.3	96.8
S5A_0E	78.9	77.8	0.00003	798.3	-0.04	288.9	2.971	110.0	97.9
S5A_DRN	0.0	0.0	0.00002	800.7	-0.06	288.9	2.971	119.3	106.2
S5A_1	66.3	65.2	0.00027	802.9	0.02	287.8	2.976	102.9	98.1
S5A_1B								98.3	98.3
S5A_2	64.2	62.8	0.00059	802.5	0.03	287.5	2.978	101.6	98.1
S5A_2B								98.4	98.3
S5A_2D	66.8	65.4	0.00059	798.2	-0.01	288.8	2.969	102.5	98.1
S5A_3								98.8	98.1
S5A_3B								98.5	98.3
S5A_4	53.1	52.5	0.00179	805.0	0.14	287.1	2.803	98.2	98.0
S5A_4B								6.5	0.8
S5A_4D	55.9	54.9	0.00171	797.5	0.07	288.6	2.840	98.1	98.1
S5A_5	51.1	50.0	0.00270	805.3	0.26	286.7	2.714	98.0	97.8
S5A_5B								98.6	98.4
S5A_6	52.7	48.2	0.00364	808.5	0.43	286.6	2.627	98.0	97.8
S5A_6B								98.7	98.4

Table C-12 (Cont). Miscellaneous Measurements for Series S5A

TEST IDS	OW_IN	OW_OUT	MDOT_AIR	P_A_IN	DP_A_L	TF_A_IN	L_OUT	P_IN	P_TANK
S5A_7	47.7	45.6	0.00472	808.9	0.67	286.2	2.515	98.0	97.8
S5A_7B	45.7	44.6	0.00460	802.2	0.67	289.3	2.334	99.0	98.8
S5A_7C								99.1	98.8
S5A_7D	45.6	44.6	0.00457	798.2	0.62	286.3	2.373	98.5	98.3
S5A_8								98.2	98.0
S5A_8B	45.1	44.2	0.00509	795.3	0.77	288.1	2.371	98.4	98.2
S5A_8C	42.9	41.1	0.00560	800.0	0.91	287.8	2.217	98.8	98.7
S5A_8D	40.4	40.2	0.00603	799.3	1.05	287.4	2.211	98.5	98.4
S5A_9								98.7	98.5
S5A_9D	35.0	32.3	0.00724	799.9	1.52	287.5	1.944	98.7	98.5
S5A_10								98.9	98.7
S5A_10B								99.2	99.0
S5A_11								101.4	97.4
S5A_12								98.3	98.0
S5A_12B								99.0	98.6
S5A_13								98.1	97.7

Table C-13. Test Section Measurements and Parameters for Series S5Ab

TEST IDS	TF_TANK	P_TANK	L_TANK	DP_1_2	DP_2_TNK	JF	JG	JF_ROOT	JG_ROOT
S5Ab_E1		86.24	-0.002	6.85	0.87				
S5Ab_E2		86.25	-0.002	6.85	0.88				
S5Ab_E3		85.47	-0.012	5.89	1.74				
S5Ab_E4		85.57	0.000	6.32	1.41				
S5Ab_E5	290.5	85.42	0.003	6.20	1.55	0.000	0.000	0.0000	0.0052
S5Ab_L1q	290.6	110.30	1.703	-0.16	0.16	0.000	0.000	0.0000	0.0052
S5Ab_0	289.2	97.24	1.127	0.20	0.39	0.429	0.000	1.1660	0.0000
S5Ab_0b	289.9	97.19	1.176	-0.53	1.17	0.433	0.002	1.1710	0.0139
S5Ab_0c	290.5	100.40	1.530	2.45	17.14	3.164	0.015	3.1610	0.0306
S5Ab_1	288.3	97.64	1.173	3.18	0.67	0.388	0.077	1.1080	0.0915
S5Ab_2	288.1	97.79	1.189	4.88	0.64	0.368	0.211	1.0800	0.1518
S5Ab_3	288.2	98.12	1.224	5.51	0.59	0.362	0.412	1.0700	0.2121
S5Ab_4	288.5	98.19	1.232	6.66	0.56	0.333	0.642	1.0280	0.2647
S5Ab_5	288.4	97.92	1.207	6.68	0.51	0.313	0.955	0.9963	0.3229
S5Ab_5b	290.5	97.58	1.239	6.42	0.79	0.301	1.013	0.9757	0.3316
S5Ab_6	288.6	97.87	1.202	6.67	0.49	0.286	1.385	0.9524	0.3886
S5Ab_7	288.5	97.80	1.196	6.69	0.44	0.263	1.842	0.9120	0.4481
S5Ab_7b	290.4	97.83	1.263	6.43	0.73	0.274	1.858	0.9310	0.4494
S5Ab_8	289.9	98.61	1.324	6.06	0.98	0.151	2.436	0.6916	0.5158
S5Ab_9	289.7	98.82	1.342	6.04	0.93	0.100	3.039	0.5617	0.5765
S5Ab_10	289.5	99.24	1.369	6.05	0.89	0.058	3.697	0.4301	0.6367
S5Ab_10b	290.4	99.26	1.383	6.43	0.59	0.060	3.614	0.4364	0.6291
S5Ab_11	290.4	99.69	1.368	6.42	0.49	0.036	4.290	0.3359	0.6861
S5Ab_12	290.2	99.80	1.350	6.37	0.54	0.022	4.982	0.2654	0.7397
S5Ab_12b	289.8	99.94	1.359	6.38	0.54	0.021	4.905	0.2586	0.7344
S5Ab_13	289.9	99.91	1.320	6.36	0.52	0.011	6.022	0.1824	0.8137
S5Ab_14	289.9	99.81	1.276	6.33	0.52	0.005	6.999	0.1206	0.8770

Table C-14. Miscellaneous Measurements for Series S5Ab

TEST IDS	OW_IN	OW_OUT	MDOT_AIR	P_A_IN	DP_A_L	TF_A_IN	L_OUT	P_IN	P_TANK
S5Ab_E1				86.76				86.09	86.24
S5Ab_E2				805.45				86.09	86.25
S5Ab_E3				802.37				86.67	85.47
S5Ab_E4				804.46				86.52	85.57
S5Ab_E5	0.0	0.0	0.00000	144.30	0.03	294.2	2.682	86.34	85.42
S5Ab_L1q	0.0	0.0	0.00000	169.10	0.03	294.1	2.968	124.80	110.30
S5Ab_0	70.6	72.2	0.00000	801.90	-0.01	296.5	2.968	109.90	97.24
S5Ab_0b	71.0	72.8	0.00001	806.50	0.03	291.7	2.970	111.00	97.19
S5Ab_0c	431.8	531.9	0.00005	767.30	0.04	294.6	2.860	93.71	100.40
S5Ab_1	64.3	65.3	0.00025	803.50	0.00	296.5	2.964	106.00	97.64
S5Ab_2	60.8	61.9	0.00070	804.10	0.01	296.6	2.962	103.80	97.79
S5Ab_3	59.5	60.8	0.00137	802.80	0.06	296.6	2.963	103.20	98.12
S5Ab_4	54.9	56.0	0.00214	802.40	0.14	296.8	2.961	100.50	98.19
S5Ab_5	54.3	52.7	0.00317	804.10	0.31	297.0	2.944	98.91	97.92
S5Ab_5b	49.8	50.5	0.00333	802.80	0.39	295.3	2.843	99.12	97.58
S5Ab_6	50.9	48.2	0.00459	802.20	0.64	297.4	2.749	98.52	97.87
S5Ab_7	45.7	44.1	0.00611	806.20	1.08	297.5	2.560	98.49	97.80
S5Ab_7b	45.4	46.0	0.00612	803.30	1.15	295.3	2.576	99.51	97.83
S5Ab_8	24.8	25.4	0.00810	806.20	2.04	292.1	1.741	100.40	98.61
S5Ab_9	11.7	16.7	0.01014	804.70	3.20	292.2	1.500	100.60	98.82
S5Ab_10	0.0	9.8	0.01239	802.80	4.81	292.3	1.329	101.00	99.24
S5Ab_10b	0.0	10.1	0.01208	802.30	4.62	295.4	1.308	101.00	99.26
S5Ab_11	0.1	6.0	0.01440	798.30	6.58	293.6	2.039	101.50	99.69
S5Ab_12	0.1	3.7	0.01675	798.20	5.96	294.0	1.522	101.70	99.80
S5Ab_12b	0.1	3.6	0.01654	798.50	5.76	295.1	1.485	101.70	99.94
S5Ab_13	0.1	1.8	0.02030	794.20	13.34	294.4	1.233	101.80	99.91
S5Ab_14	0.1	0.8	0.02356	785.30	15.31	294.9	1.160	101.80	99.81

END

**DATE
FILMED**

10/2/92