Supercritical Water Oxidation Pump Investigation

**Glenn Thurston
Karen Garcia**

Published February 1993

**Idaho National Engineering Laboratory
EG&G Idaho, Inc.
Idaho Falls, Idaho 83415**

**Prepared for the
U.S. Department of Energy
Office of Environmental Restoration and Waste Management
Under DOE Idaho Field Office
Contract DE-AC07-76ID01570**

MASTER

Supercritical Water Oxidation Pump Investigation

EGG-WTD-10674

Prepared by:

G. Thurston
Senior Engineering Specialist

Date

Reviewed by:

R. Marshall
Senior Engineering Specialist

Date

Approved by:

J. M. Beller
Senior Project Engineer

Date

ABSTRACT

This report investigates the pumping techniques and pumping equipment that would be appropriate for a 5,000 gallon per day supercritical water oxidation waste disposal facility. The pumps must boost water, waste, and additives from atmospheric pressure to approximately 27.6 MPa (4,000 psia). The required flow ranges from 10 gpm to less than 0.1 gpm. For the higher flows, many commercial piston pumps are available. These pumps have packing and check-valves that will require periodic maintenance; probably at 2 to 6 month intervals. Several commercial diaphragm pumps were also discovered that could pump the higher flow rates. Diaphragm pumps have the advantage of not requiring dynamic seals. For the lower flows associated with the waste and additive materials, commercial diaphragm pumps are available. Difficult to pump materials that are sticky, radioactive, or contain solids, could be injected with an accumulator using an inert gas as the driving mechanism. The information presented in this report serves as a spring board for trade studies and the development of equipment specifications.

EXECUTIVE SUMMARY

This report reviews the pumping requirements and the availability of commercial pumps for a supercritical water oxidation facility with a through-put of 500 to 5,000 gallons per day. This report does not address the pumping of oxygen. Clean water is the major fluid to be pumped (80 to 95%). In addition, it will be necessary to pump the waste material that is to be oxidized and in some cases, additives such as methyl ethyl ketone or butyl alcohol. The temperature of the fluids to be pumped is near ambient (60°–100°F); heat is added at a later point in the process. The pumping system must boost the pressure from near atmospheric to approximately 27.6 MPa (4,000 psia). The liquid flow required for this size of a facility is in the range of 1–10 gpm and the power required is approximately 4 horsepower for each gpm of flow.

For flows in the 1–10 gpm range, there are a number of commercial plunger (piston) pumps that are proven in other process applications and are readily available. In addition, two commercial diaphragm pumps in this flow range were also located. Vendor addresses and phone numbers have been listed for further investigation. All these positive displacement pumps have check-valves that will require maintenance at 2 to 6 month intervals. In addition, the plunger pumps have piston packing that will need refurbishing.

For the lower flows (1 gpm) associated with the waste and additive materials, commercial diaphragm pumps are available. Diaphragm pumps have the advantage of not requiring dynamic seals.

Difficult to pump materials (i.e., sticky, radioactive, or material containing solids) will be macerated and diluted with water to make the easier to handle. These fluids could also be injected with an accumulator using an inert gas as the driving mechanism.

The findings of our investigation also conclude that the combination of head and flow precludes the use of dynamic pumps.

CONTENTS

ABSTRACT	iii
EXECUTIVE SUMMARY	v
1. INTRODUCTION	1
2. FLUID DESCRIPTION	1
3. FLOW RATE	2
4. POWER REQUIREMENTS	2
5. PUMPING SYSTEM ARRANGEMENTS	2
6. PUMP TYPES	3
7. GAS DISPLACEMENT PUMPING	5
8. SPECIAL CONCERNS	5
9. COMMERCIALLY AVAILABLE EQUIPMENT	7
9.1 Plunger Pumps	7
9.2 Diaphragm Pumps	7
9.3 Rotary Positive Displacement Pumps	8
9.4 Dynamic Pumps	8
10. RECOMMENDATIONS	9
11. REFERENCES	10
APPENDIX A—SELECTED PUMP MANUFACTURERS	A-1
APPENDIX B—SELECTED VENDOR CATALOG INFORMATION	B-1

FIGURES

1. Dimensionless specific speed diagram for single stage pumps	4
2. Gas displacement injection system	6

Supercritical Water Oxidation Pump Investigation

1. INTRODUCTION

This report provides an overview of the pumping techniques and equipment that might be used in a full-scale supercritical water oxidation waste disposal facility.

Supercritical Water Oxidation (SCWO) brings together water, organics, and oxygen at a pressure and temperature above the critical pressure and temperature of water. Water at these conditions acts as a solvent for the organic material and allows oxidation to rapidly and completely take place. The critical pressure for water is 22.11 MPa (3,206 psia) and the critical temperature is 374 °C (705 °F).

In a typical SCWO process the reactor pressure is 25 MPa (3,625 psia); for this investigation we will assume that the required pump output pressure is 27.6 MPa (4,000 psia). The fluid inlet temperature to the pump is about ambient temperature because heating takes place after the fluids leave the pump.

There are four general input process streams that require pumping in SCWO.

- **Bulk Water**—This is the major flow (80–95%).
- **Organic Waste**—This is the product being processed. It may contain material unaffected by processing.
- **Additives**—This is material added to the process for control. It could be a fuel that adds to the exothermic reaction and/or it might also be a material that aides in the control of the end products.
- **Oxygen**—Oxygen pumping is not addressed in this report.

2. FLUID DESCRIPTION

The fluids pumped through this facility are water, waste, and additive fluids.

- **Bulk Water**—A neutral pH and high purity is assumed for the water. Once it is mixed with waste and additives, the pH will be slightly alkaline (pH 8–9).
- **Waste**—The DOE candidate wastes for SCWO fall into several categories
 - Oils and solvents
 - Organics including sewer sledge
 - Scintillation fluids
 - Activated carbon
 - Rags.

It is assumed that solids in the waste stream will have a low impact on the process because they will be ground, macerated, and diluted.

- **Additive Fluids**—Typically methyl ethyl ketone or butyl alcohol.

3. FLOW RATE

This report specifically address the pumping requirements for SCWO plants in the pilot-scale to full-scale range (500 to 5,000 gallons per day). It is not known at this time if the operation would be continuous (1,440 minutes per day) or run in one 8-hour shift (480 minutes). The full-scale mixed waste treatment plant would presumably run continuously but the possibility exists that it would run one 8-hour shift per day. The maximum capacity is 10 gpm based on a single 8-hour shift. Using continuous operation (1,440 minutes), the maximum capacity is 3.5 gpm. For this investigation, a flow range of 1 to 10 gpm is used for the bulk water pumps. The maximum waste-plus-additive flow is assumed to be 10% of the bulk flow or 0.1 to 1 gpm.

4. POWER REQUIREMENTS

The power required for pumping is a function of the head, flow, and pump efficiency. For a 4000 psi head, 10 gpm flow, and 60% efficiency the following equation illustrates the estimated power requirements.

$$\begin{aligned}\text{power} &= \frac{\text{head} \times \text{flow}}{\text{eff}} \\ &= \frac{4,000}{0.434} \times \frac{10 \times 62.4}{7.48} \times \frac{1}{0.6} \\ &= 1.283 \times 10^6 \text{ ft-lb/min} \\ &= 38.9 \text{ hp}\end{aligned}$$

where

power = foot-pounds per minute

head = ft of fluid

flow = pounds per minute.

Based on this equation, the power required is approximately 4 hp per 1 gpm.

5. PUMPING SYSTEM ARRANGEMENTS

The following system schemes could be considered to accomplish the required pumping.

- Separate pumps for each process stream with mixing occurring after the boost to high pressure.
- Proportional mixing of the process streams at low pressure followed by a boost to high pressure.

The possible combination of pumps in series or parallel is an additional systems consideration. Providing pumps in a parallel arrangement is a common method of adding on-line spare capacity to allow for maintenance and repairs. A typical arrangement is two full-capacity pumps or three 50% capacity pumps. Pumps arranged in series can be used to provide multistage capability and spread the head requirement over several pumps.

6. PUMP TYPES

Pump types are broadly categorized into two groups (1) positive displacement devices, and (2) dynamic devices. A positive displacement pump generates pressure by confining a fluid volume at pump inlet conditions and then displacing the trapped volume to the pump exit. The volume flow is fairly constant and independent of the discharge pressure. Following are some typical positive displacement pumps types: reciprocating piston (plunger), reciprocating diaphragm, rotary gear, rotary progressive cavity, and rotary sliding vane.

In a dynamic pump, energy is added to the fluid with a rotating impeller that increases the velocity and momentum of the fluid. The velocity is then converted to pressure by decelerating the flow in a controlled manner with a diffuser (Bernoulli's Theorem). Some typical dynamic devices are axial and centrifugal flow pumps, regenerative turbine (drag) pumps, and pitot pumps. The advantage of a dynamic pump is the absence of valves, reciprocating seals, minimal wearing parts, and a nonpulsating discharge pressure. This type of pump could handle some suspended particles. The disadvantages are lower pump efficiency, high rotational speed, and probably high cost.

Specific speed is a characterizing parameter typically used to determine appropriate pump types. It relates the head, flow, and rotating speed of dynamic pumping machinery. Geometrically similar pumps with the same specific speed will have the same velocity triangles and approximately the same efficiency. Figure 1 shows a plot of dimensionless specific speed and efficiency for various pump types (Balje 1981).

The specific speed N_s for our reference pump with a standard drive motor (10 gpm, 3,600 rpm, and 9,216 feet of head) is as follows:

$$\begin{aligned} N_s &= \frac{N \times \sqrt{\text{flow}}}{H^{3/4}} \\ &= \frac{3600 \times \sqrt{10}}{9216^{0.75}} \\ &= 12.1 \end{aligned}$$

where

N = revolutions per minute

flow = gallons per minute

H = head in feet.

Figure 1. Dimensionless specific speed diagram for single stage pumps.

This specific speed is then converted to a dimensionless specific speed of 4.4×10^{-3} . Referring to Figure 1, it can be seen that the minimum practical dimensionless specific speed for a single stage centrifugal pump is 1.8×10^{-1} . To obtain an appropriate specific speed would require multistaging and a high-speed rotor. Other possible solutions include a high-speed partial emission design or a high-speed pitot tube pump.

7. GAS DISPLACEMENT PUMPING

Gas displacement pumping is an alternate strategy that could be practical for difficult-to-pump waste fluids. The waste fluid is pumped into a pressure vessel using a low-pressure centrifugal pump. The vessel is filled with liquid to approximately 90% capacity, and the fill-pump is valved-out. The vessel is then pressurized with a high-pressure gas (4,000 psi) and the outlet valve to the process is opened and adjusted to provide the desired flow. Gas is added as necessary to replace the displaced liquid and keep the tank at a constant pressure. This process continues until the tank is nearly empty.

If two tanks are provided the process could be continuous. Using this process, gritty or sticky fluids could be processed. It would also be practical for processing radioactive fluids, since there are not any high-pressure pump seals and the gas pumping equipment is not exposed to the radioactive fluid.

The displacement gas could be nitrogen or helium and it would be vented to a large-volume low-pressure storage tank and recycled at the end of the cycle. The high-pressure storage vessel does not have to be very large as the waste flow-rate is low (less than 1 gpm). The high-pressure storage vessel could be an accumulator type device with a piston or bladder that separates the liquid from the gas. The gas could be recycled with an air driven intensifier or a small multistage piston type compressor, similar to that used for filling scuba tanks. A possible system configuration is shown in Figure 2.

8. SPECIAL CONCERNS

Seal Leakage—When handling mixed waste it is imperative that there be a minimum of leakage and direct maintenance. The pump seal would ideally have zero leakage and require maintenance at very infrequent periods. This could be accomplished with a gas displacement system in which the waste material is pumped into a high-pressure holding tank with a low-head centrifugal pump and then pressurized with an inert gas to feed it to the reactor. The centrifugal pump could be a sealless magnetic drive unit. Zero leakage can also be achieved with a diaphragm pump.

Pulsating Flow—Plunger and diaphragm pumps both exhibit an undesirable pulsing flow characteristic. The pulsing flow needs to be dampened-out as it tends to make the flow control system unstable. In addition, a pulsing flow can cause resonate piping vibrations and may require tuning of the pipe supports or system configuration.

Capacity Control—A system for variable flow needs to be determined because of the many possible types of wastes to be processed and the probable requirements for a range of flow rates. For a positive displacement pump, such as a plunger pump or diaphragm pump, it can be accomplished with a variable speed driver, or in some instances, by mechanically varying the stroke. The variable speed is customarily carried out with a variable frequency power supply and an induction motor. Dynamic pumps can be throttled to provide a limited range of flows. However, variable speed can also be useful and even more efficient. Because of the high-pressure drop, bypass control (i.e., returning the discharge flow back to the suction), does not appear to be very desirable.

L93 0149

Figure 2. Gas displacement injection system.

Inlet Filters—All the pumps will require good high-quality filters at the pump inlet as there is a high probability of particles that could damage the pump seals or valves. The filter should be of the duplex type so that pump operation can continue during filter cleaning or change out. The filter probably needs a 60 micron absolute rating. However, the pump manufacturer's recommendation should be used. A coarse pre-filter would extend the life of the final filter.

9. COMMERCIALLY AVAILABLE EQUIPMENT

9.1 Plunger Pumps

A large number of manufacturers produce plunger pumps that meet the required flow and head. A typical plunger pump is a mechanically driven triplex design. Three-in-a-line piston plungers are driven by a crank shaft that provides one plunger stroke for each 120 degree of crank rotation. The multiple pistons tend to smooth out the pulsating flow. Each plunger has an inlet and outlet check-valve connected to a common inlet and outlet flow manifold. The plunger reciprocates back and forth in a cylinder that has a stuffing box preventing fluid leakage to ambient.

Pump speeds can vary from 250 to 3,400 rpm depending on the pump design and the manufacturer. High-speed pumps tend to be smaller and less costly, where as low-speed designs are more expensive but can provide a much longer life.

Flow control is generally provided by varying the driver speed. The plunger packing is the most troublesome part of the design. It must seal a pulsating full discharge pressure on a sliding surface. The fluid wipes back and forth over the packing. Any particles in the fluid tend to be drawn into the packing and damage the seal. Water has a low viscosity and is a poor lubricant, which adds to the difficulty. Some packing leakage is acceptable. However, if the packing can be lubricated by injecting a small amount of oil (3 to 5 drops per minute) into the packing gland, the life can be greatly extended. It would appear that this would be an acceptable procedure in our application.

Another technique is to use a labyrinth seal (clearance seal) and a packed seal in series. The high-pressure drop is absorbed by the labyrinth and the packed seal is used to prevent leakage to ambient. The leakage through the seal is collected and recycled. The packing life and leakage must be carefully considered when making the pump selection. Standard packing will probably require service and replacement at least every two to three months. The inlet and outlet check-valves are also subject to wear and require periodic maintenance at least every four to six months.

9.2 Diaphragm Pumps

Diaphragm pumps are built in a number of styles but they all rely on flexing a membrane to change the volume of a cavity, which moves the fluid from the pump inlet to the outlet. The membrane is typically flexed by air or hydraulic pressure and in some cases, with a direct mechanical linkage. A major design feature and advantage that diaphragm pumps have is that the pumped fluid can be completely isolated from the ambient without use of dynamic seals. The pump can therefore be made 100% leak-tight using only static seals.

Unfortunately, leak-tight doesn't mean maintenance free. A diaphragm pump still requires inlet and outlet check-valves. In addition, the diaphragm quickly acquires a large number of flexure cycles that may ultimately lead to fatigue failure, particularly if the diaphragm is metal.

The inlet and outlet check-valves are subject to full pump differential and must open and close on every stroke. Check valve leakage reduces the pump through-put and causes heating by repeatedly pumping the same fluid over and over. Due to heat and erosion, a leaking check valve can quickly destroy itself. A number of pump check valve designs have evolved for specific fluids. Sometimes two valves in series are provided to enhance sealing. This is particularly true in slurry flows or fluids with fibers. Check-valve types and their merits are discussed in detail in (Karassik et al. 1987; Li and Gloyna 1992). This same material on valves is applicable to plunger pumps, which also rely on inlet and outlet check-valves for their operation.

In a fluid pulsed diaphragm pump the pressure on both sides of the diaphragm is equal. The diaphragm is subjected to the fluid compressive stress and the additional stress from flexure and displacement. Some manufacturers provide diaphragms made of an elastomer or plastic material that can provide an almost infinite life. Metal diaphragms are subject to fairly high flexure stress and are prone to fatigue failure. Diaphragm fatigue failure can lead to sudden external leaks and mixing of the pulsing fluid with the process fluid. This can occur without any warning. In critical applications, multiple diaphragms in series with some sort of leak detection are used to provide an alarm.

Most commercial diaphragm pumps are limited to about 5 hp and are unable to deal with the bulk water flow. However, many of these low horsepower pumps could handle the waste and or additive flow.

Two diaphragm pump manufacturers were located that could provide the higher flows associated with the bulk water flow (4,000 psi and 10 gpm). One is Bran+Luebbe^a of Buffalo Grove, Illinois; they make a precision micro-metering chemical injection pump with a variable stroke. This is a very expensive device with a price in the \$100-150k range. The other pump is a multi-cylinder radial piston diaphragm pump similar to a radial cylinder aircraft engine. This pump is manufactured by Harbin, Inc., of Cumming, Georgia. It is very reasonably priced and is used primarily in high-pressure water-jet cutting and cleaning services.

9.3 Rotary Positive Displacement Pumps

Rotary positive displacement pumps of the gear and vane type are limited to about 200 psi discharge pressure when pumping water. This is because of internal leakage and the low viscosity and poor lubricating qualities of water. Progress cavity pumps, such as the "Moyno" pump manufactured by Robbins and Meyer, are limited to a 2,000 psi discharge because of internal leakage and the low viscosity of water. Staging rotary positive displacement pumps, by using separate pumps in series, can be a problem because of the shaft seal on the higher stages. This seal is subject to pump inlet pressure because of its location.

9.4 Dynamic Pumps

Manufacturers of dynamic pumps with the required head and flow (4,000 psi and 10 gpm) were not found in our investigation. This field is dominated by plunger pumps. A dynamic pump will

a. Mention of specific products and/or manufacturers in this document implies neither endorsement or preference, nor disapproval by the U.S. Government, any of its agencies, or EG&G Idaho, Inc. of the use of a specific product for any purpose.

require a high-speed driver and or multi-staging. This type of pump is more expensive and less efficient. A custom pump could be designed for this application, but the expense would be difficult to justify.

High-speed geared centrifugal pumps, manufactured by Sundstrand Fluid Handling Company, are capable of producing the required head but their minimum flow is about 150 gpm. In a larger plant with higher flow requirements, this could be a useful pump. No other commercial centrifugal pumps met our requirements.

A patented pitot tube pump is manufactured by Roto-Jet Pump of Sacramento, California. Their standard Model RO is capable of producing 5,200 ft of head in a single stage with the required 10 gpm flow. This pump runs at 6,321 rpm and is capable of higher speeds and heads. Roto-Jet is presently developing custom pumps for higher pressures. It is possible that they might have a pump in the near future that could meet our requirements. A pump of this type could provide a low maintenance, smooth, pulse-free flow, and a simple mechanical design. The only dynamic seal in the pump is a rotating shaft seal, which seals against the pump inlet pressure.

10. RECOMMENDATIONS

Bulk Water Pump—The higher flow rate (10 gpm) required for the bulk water flow can be supplied by a number of plunger pumps and a few diaphragm pumps. The following units are recommended. However, this recommendation is not meant to be all-inclusive and additional trade studies are suggested.

- **Plunger Pump**—Hammelman Corporation produces a unique and patented plunger pump with a labyrinth seal that greatly extends the seal life and reduces friction. This pump has a long record of successful operation and would be a good choice for a plunger type pump.
- **Diaphragm Pump**—The radial piston diaphragm built by Harben, Inc., is a relatively inexpensive pump and the high-speed operation combined with multiple plungers should reduce the flow pulsations considerably. (Need to check and see if a diaphragm leak detector is available.)

Waste and Additive Flow Pumps—These streams are best pumped with one of the many commercial diaphragm pumps available in this size range. For fluids that are very difficult to pump because of solids, viscosity, or activity level, a gas displacement system would be practical.

Cost of a typical Pump (10 gpm, 4,000 psi). The following cost data is not based on firm pricing or rigid specifications but is meant to be and to show the general cost trends.

- **Plunger Pump**—Heavy Duty Industrial Quality, Includes drive motor, H&R Industries, \$10,000 to \$17,000
- **Labyrinth Sealed design, internal gear reduction, Hammelmann Corp, \$20,000 to \$22,000**
- **Diaphragm Pump**—Radial piston multi-plunger, complete with drive motor, Harben Incorporated, \$7000 to \$12,000

Heavy duty, variable stroke, metering pump, with motor, Bran+Lubbe, \$150,000.

11. REFERENCES

- Balje, O. E., *Turbomachines*, New York, John Wiley & Sons, 1981.
- Karassik, I. J., et al., *Pump Handbook*, 2nd edition, New York: McGraw-Hill Book Company, 1987.
- Li, Lixiong and Gloyna, E. F., "A Reciprocating Pump Check Valve Designed for Supercritical Water Oxidation of Sludges", *Journal of Hazardous Materials*, 24, 1992, pp.77-82.

Appendix A

Selected Pump Manufacturers

Appendix A

Selected Pump Manufacturers

Plunger Pumps

H&R Industries, Inc.
3020 Stafford S. W.
Grand Rapids, MI 49548
616-247-1165
David Herr

Hammelmann Corp.
3949 Dayton Park Drive
Dayton, OH 45414
513-233-4935
Michael G. Goecke

Diaphragm Pumps

Bran+Luebbe
1025 Busch Parkway
Buffalo Grove, IL 60015
708-520-0700
Henery Schorsch

Harben, Inc.
P. O. Box 830107
Cumming, GA 30130
800-327-5387
Troy Richards

Crane Co./Chempump Division
175 Titus Ave
Warrington, PA 18976
215-343-6000

Milton Roy
201 Ivyland Road
Ivyland, PA 18974
215-441-0800

American Lewa Inc.
132 Hopping Brook Road
Holliston, MA 01746
508-429-7403

Pitot Tube Pump

Roto-Jet-Pump
721 North B Street
Sacramento, CA 95852
916-444-7195
Dennis Schendel

Geared Centrifugal

Sunstrand/Fluid Handling
14845 West 64th Avenue
Arvada, CO 80004
303-425-0800

Appendix B

Selected Vendor Catalog Information

HARBEN INCORPORATED
POST OFFICE BOX 2250
CUMMING, GA 30130 USA

TEL: (404) 889-9535
FAX: (404) 887-9411
TOLL FREE: 1-800-327-JETS

January 5, 1993

Glen Thurston
E G & G Idaho
P.O. Box 1625
Idaho Falls, ID 83415
208-526-8271

Dear Mr. Thurston:

Thank you for your interest in the range of high pressure water jetting equipment we manufacture.

The Harben machines offer a versatile system in a compact design. They can either be diesel or electric powered. The former can be trailer, truck or skid mounted with various water carrying capacities. The electric units can be skid mounted or mounted on a three wheel cart.

As you will see from the enclosed materials, we offer various sizes and performance ratings from 2,000 psi up to 10,000 psi with flows from 6 gpm to 20 gpm. The Harben machines are capable of many varied uses including sewer and drain cleaning, graffiti removal, surface and floor cleaning plus many other applications.

The Harben Pump itself is of a unique design. It is a radial piston diaphragm pump and is designed for continuous operation. As all the moving parts run in oil and the pumped fluid is isolated by the tubular rubber diaphragms, the Harben Pump can run dry without damage. There are no piston seals and no packings and being direct driven, there are no belts to adjust. All this means less downtime.

We have distributors located across the country supported by Regional Sales Managers for your convenience. If you have any technical questions or require a demonstration of this unit, please call your Regional Sales Manager, Kyle Krebs at 707-894-2888.

Sincerely,

A handwritten signature in cursive script, appearing to read "Trae".

Trae Rogers
Internal Support Engineer

TR/lc

Enclosures

cc: Kyle Krebs
Regional Sales Manager

THE POWER BEHIND THE PRESSURE

Quality through good design is a concept closely followed at Harben.

This approach has made Harben's Unique Radial Piston Diaphragm Pumps the best performing and most reliable high pressure pumps on the market today, with none of the drawbacks normally associated with conventional high pressure piston pumps.

Benefits include:

- Unrivalled reliability and long service intervals
- Variable pressure and flow options without piston changes
- Pump can run dry without damage as there are no piston seals
- Filtration to 150 microns
- No modification is required to pump sea water
- Pump has multi-cylinders therefore no pulsation
- Positive displacement (high efficiency)
- Unequalled continuous running capabilities
- Compact and lightweight
- High speed (high power to weight ratio)

The pumps work on the radial piston design principle using one way valves in conjunction with tubular diaphragms fitted with an internal support or mandrel. The pumped fluid which passes through this diaphragm is surrounded by a cylindrical pressure chamber or barrel, in the ends of which inlet and delivery valves are fitted.

The pumps' crankcase, which contains the only moving parts, is filled with a mineral hydraulic HLP oil which performs two tasks:

- The lubrication of all moving parts within the crankcase
- As a means of pressure to compress the diaphragm

As the shaft rotates, the piston advances and its ports pass the end of the cylinder, sealing the chamber. Further advance causes the trapped oil to compress the diaphragm around the mandrel expelling the water in the diaphragm through the delivery valve into the delivery manifold.

As the piston retreats, the diaphragm reverts to its tubular form drawing water through the inlet valve. Any oil slippage past the piston during the delivery stroke is made up through the piston ports as they open to the crankcase oil.

All mechanical parts, with the exception of the inlet and delivery valves, run in the oil flooded crankcase and so are unaffected by contamination from the pumped fluid or by running dry.

Standard filtration for these pumps is normally 150 microns and this filter is usually fitted to the inlet of the supply tank or reservoir. A coarse strainer is fitted to the tank exit; this arrangement ensures that if the filter is neglected to the point of blockage, the tank will empty and the pump will run dry, enabling the dry-running qualities of the pump to be

used as a filter maintenance indicator. Inlet conditions required are flooded suction; pressure feeding is not necessary.

Arrangements are made on both 'P' type and Century Series pumps for the incoming fluid to cool the crankcase oil. The use of standard diaphragm/barrel assemblies provides a choice of flows, depending upon the number of barrels fitted to a crankcase. The cylindrical form of these barrels is well suited to containing high pressures. Three piston diameters are available to suit a range of pressures.

The product range includes the smaller 'P' type Pump with pressures up to 420 bar (6,000 PSI) and the larger Century Series Pump with pressures up to 828 bar (12,000 PSI).

Both pumps are designed to be directly coupled and flange mounted and can be supplied in bare-shaft form, skid mounted, trolley mounted, trailer mounted or truck mounted. Pumps can even be mounted on underwater ROV's. Diesel drive, electrical drive and hydraulic drive options are available.

A complete range of performance options for both 'P' type and Century Series pump heads are shown on the adjoining pages.

Applications

It is almost impossible to list all of the industrial applications of our pumps. Some of these include:

- High pressure cutting of board, plastic and materials
- Water hydraulic systems
- Abrasive blasting and descaling
- Drain/sewer cleaning
- Tube descaling
- Desalination by reverse osmosis
- Pumping demineralised water
- Floor and surface cleaning
- Underwater cleaning

Harben high pressure Radial Piston Diaphragm Pumps are backed by the world's most comprehensive network of distributors. So wherever you are, whatever the job, the back-up is there.

Naturally, all the company's pumps and products are thoroughly tested and checked before they leave the plant and come with a full 12 months warranty. The company also operates a servicing and maintenance division which can either advise customers' own engineering staff or undertake work in the field or at the plant, depending on the nature of the task. Operator and Safety Training can also be provided. Full instructions are supplied with every item of equipment and comprehensive spares are stocked by Harben and all distributors. In addition, specialist systems for individual applications can be catered for upon request.

Unique radial piston diaphragm pump.

1. Crankcase
2. Inlet manifold
3. Cylinder chamber
4. Piston
5. Piston port
6. Tubular diaphragm
7. Support mandrel
8. Diaphragm protection valve
9. Inlet valve plug
10. Inlet seat
11. Inlet nut
12. Delivery valve
13. Delivery seat
14. Delivery nut
15. Bleed screw
16. Delivery manifold
17. Main bearing
18. Eccentric
19. Shaft
20. Slipper assembly
21. Outlet to expansion chamber
22. Drain plug

Colour Key

	Oil at atmospheric pressure
	Oil at delivery pressure
	Water at inlet pressure
	Water at delivery pressure

As the shaft rotates, the piston advances and passes the end of the cylinder, sealing the chamber. Further advance causes the trapped oil to compress the diaphragm tube round the mandrel expelling the water in the tube through the delivery valve.

As the piston retreats, the diaphragm reverts to its tubular form drawing water through the inlet valve. Any oil slip past the piston during the delivery stroke is made up through the piston ports as they open to the crankcase oil.

The diagram shows a 4 cylinder Century Series pump but as many as 8 cylinders can be fitted to a crankcase running on a common eccentric, depending on the flow required.

Section through cylinder 'C' (Delivery Stroke)

Diaphragm Protection Valve (Century Pump Only)

To protect the diaphragms against failure due to damaged delivery valves a special diaphragm protection valve is fitted in each cylinder and functions as described in A and B.

A. Normal Operation

The protection valve is held closed by a spring allowing high pressure oil to circulate around the diaphragm during compression stroke of piston.

B. Damaged Delivery Valve Condition

High pressure water inflates diaphragm during return stroke of piston and wall of diaphragm contacts the valve. Pressure within diaphragm overcomes spring pressure opening valve ports to crankcase allowing oil to circulate at zero pressure.

Performance graphs shown above are for 1000 R.P.M. pump performance.

Diaphragm Metering Pumps

For greater Economy - Safety - Versatility.

Bran+Luebbe offers a comprehensive standardized range of hydraulically actuated diaphragm pumps. Conforming to API 675 for virtually all metering applications, all pump gears are of positive displacement designs (no lost motion). Double diaphragm design exceeds API 675 in providing a complete, reliable rupture detection system for added safety.

Components in direct contact with the process fluid are as a standard SS 316 and special alloys such as hastelloy B and C, as well as a variety of plastics, are also available.

Metering capacities range from a few ml/h to 2640 gph (10,000 lt/hr) for a single pumphead. Higher capacities can be obtained using multiple pumphead arrangements.

In comparison with conventional plunger pumps, the plunger in a diaphragm pump is isolated from the process liquid and operates in a hydraulic fluid which is safe and an excellent lubricant. The rugged diaphragm, normally made of PTFE, separates the process fluid from the hydraulic fluid. The range of application extends to 5000 psig (350 bar) using PTFE diaphragms and 7100 psig (500 bar) using stainless steel diaphragms.

The diaphragm is operated by the displacement of hydraulic fluid activated by the stroking action of the plunger.

Three important valves control the volume of hydraulic oil displaced.

Relief valve – A pressure relief valve on the hydraulic fluid side protects the gears and diaphragm pumphead from excessive loading. After installation of the relevant monitoring sensors, this valve can also replace a relief valve in the process piping. This feature is ideal in applications such as the metering of slurries.

Air bleed valve – An automatic air bleed valve is provided to allow the escape of entrained air which may otherwise accumulate in the hydraulic system resulting in erratic metering.

The Bran + L

Mechanics

Fig. 1. shows the plunger (7) at the end of the discharge stroke and the diaphragm (1) is shown in the forward

position. The refill valve (5) is closed via the spring (6) – control pin (3) and the stem (4).

Luebbe Principle

Refill Actuation

Fig. 1a. shows the plunger (7) at the end of the suction stroke. The diaphragm pushes the control plate (2) against the control pin (3) and spring (6). The stem (4) moves down allowing the refill valve (5) to open and replenish the oil.

Refill valve – The mechanically operated refill valve is regulated by a trend setting control system. This valve automatically replaces the oil vented by the air bleed valve and provides stable positioning of the diaphragm.

Unique Bran + Luebbe Advantages

Greater Economy

- Long service life from rugged, abrasion-resistant PTFE diaphragm and a smooth-flow process chamber design.
- Low service costs – plunger and seals operate under ideal lubricating conditions.
- Limited number of moving parts.
- Easy to install.
- Low costs due to standardized components.

Greater Safety

- Corrosive and toxic process fluids are safely metered as diaphragm pumps are hermetically sealed.
- The mechanically actuated refill valve provides reliable diaphragm protection against excessive loading.
- Will operate without damage during starved suction conditions.
- The double diaphragm design offers even more safety by immediately indicating diaphragm rupture.

Greater Versatility

- Diaphragm pumps with mechanically actuated refill valve have a smooth unobstructed process fluid chamber allowing the metering of most fluids including viscous liquids and slurries.
- The reduced internal pressure drop allows larger volumes to be metered.
- Reduces required Net Positive Suction Head.
- The internal hydraulic relief valve can be used to replace the process relief valve which is particularly useful when handling slurries and difficult to handle fluids.
- The hydraulic stuffing box condition can easily be monitored and adjusted in a clean oil free zone while the pump is in operation.

Heavy Duty Large Capacity Metering Pump Type-BS

Gear Type : BS
Stroke Length Range : 0-120 mm
Max. Plunger Force : 100,000 N
Weight : 4,400 lbs. (approx.)
Maximum power capacity at drive speed
n = 1,000 rpm : 535 kw (715 hp)
n = 1,500 rpm : 800 kw (1070 hp)

The gear can be combined horizontally with Bran+Luebbe gears B, KA, DA and with an angled drive, gears J, C, and DS.

Dimensional Data

A - 25 inches
B - 63 inches
C - 69 inches

B and C dimension will vary depending on the type of stroke adjustment and liquid end used. An additional 25 inches (approx.) will be added to the C dimension when the liquid pumphead end is in place.

Type of Adjustments Available	Height
0: With stroke length adjustment	H = 31.5 inches
4: Electric motor*	H = 63 inches
5: Pneumatic	H = 84 inches

*As shown in the illustration

BS Gear Capacity Chart

Capacity (gph)	8	15,646
Maximum Pressure (psig)	42,600	454
Stroke Length (mm)	0	120
Plunger Diameter (mm)	20	200
Stroking Speeds (spm)	128,160,193,231	

Capacity at 128 strokes/min. gph	Maximum Pressure psig	Plunger Diameter mm	Connection Size
0... 74	42,600	20	½" ASA
0... 116	28,970	25	1" ASA
0... 168	20,020	30	1" ASA
0... 242	13,915	36	1" ASA
0... 329	10,225	42	1½" ASA
0... 467	7,240	50	1½" ASA
0... 584	5,820	56	1½" ASA
0... 718	4,685	62	1½" ASA
0... 863	3,905	68	1½" ASA
0...1051	3,265	75	1½" ASA
0...1260	2,700	82	2" ASA
0...1516	2,230	90	2" ASA
0...1867	1,805	100	2" ASA
0...2263	1,490	110	2½" ASA
0...2922	1,160	125	2½" ASA
0...4215	766	150	3" ASA
0...5738	590	175	4" ASA
0...7494	454	200	4" ASA

Motor- Speed n =	Pump Stroke Number/ Min. with Gear Ratio I =				
	6.0	7.5	9.0	10.8	13.5
at 60 Hz					
870	145	116	97	81	64
1160	193	155	129	107	86
1740	290	232	193	161	129
at 50 Hz					
725	121	97	81	67	54
965	161	129	107	89	72
1450	242	193	161	134	107

The connection dimensions of the gear are adapted to the particular motor flange dimension. Gear BS can be fitted with a second pumphead doubling the flowrate. Both pumpheads have a joint stroke length adjustment.

Pump capacity tables

B Gear

in GPH for 120 mm max. stroke length at 98% volumetric efficiency

Strokes/min.*							Plunger Dia. mm	P _{max.} ** psig	Con- nec- tion	Stroke volume ml
64	84	113	127	134	170	202				
24	31	42	48	50	64	76	16	36,250	1/2"	23.6
37	49	63	74	78	99	118	20	23,200	1/2"	36.9
58	77	103	116	123	155	185	25	14,800	1"	57.7
84	110	149	167	176	224	267	30	10,200	1"	83.1
121	159	214	241	254	322	383	36	7,100	1"	119
165	217	291	328	346	439	520	42	5,220	1 1/2"	162
207	272	365	410	433	550	653	47	4,260	1 1/2"	204
234	306	415	465	491	624	740	50	3,700	1 1/2"	230
293	386	518	584	616	779	927	56	3,000	1 1/2"	289
359	473	637	716	753	956	1136	62	2,400	1 1/2"	355
433	568	763	859	906	1152	1369	68	2,030	1 1/2"	427
528	692	930	1046	1104	1400	1664	75	1,670	1 1/2"	519
629	827	1112	1250	1318	1672	1989	82	1,330	2"	621
758	996	1339	1506	1590	2016	2396	90	1,130	2"	748
938	1231	1654	1860	1963	2489	2959	100	910	2"	923
1133	1487	2003	2251	2375	3012	3593	110	770	2 1/2"	1120
1464	1921	2584	2906	3065	3884	4624	125	580	2 1/2"	1440
2108	2774	3725	4174	4412	5601	6658	150	398	3"	2080
2880	3778	5073	5707	5997	7635		175	285	4"	2830
3752	4914	6631	7450	7847	9960		200	227	4"	3690
Reduction ratios							Motor RPM			
13.7	—	—	—	—	—	—				
—	13.7	10.2	—	8.6	—	—				
—	—	—	13.7	—	10.2	8.6	870			
							1150			
							1740			

* The max. possible stroking speed depends upon viscosity and installation parameters.

** Max. permissible pump pressure, based on a maximum crosshead loading of 11,240 lbs.
The design pressure of the pumphead must also be taken into account.

BS Gear

in GPH for 120 mm max. stroke length at 98% volumetric efficiency

Strokes/min.*							Plunger Dia. mm	P _{max.} ** psig	Connec- tion	Stroke volume ml
64	85	107	129	161	194	232				
37	50	63	75	94	114	136	20	45,150	½"	36.9
58	78	98	118	147	177	212	25	28,885	1"	57.7
84	112	141	170	212	255	306	30	20,060	1"	83.1
121	161	203	245	306	367	441	36	13,915	1"	119
165	219	277	333	415	502	600	42	10,225	1½"	162
234	312	391	473	589	711	848	50	7,240	1½"	230
293	391	491	592	740	890	1065	56	5,820	1½"	289
359	478	602	727	906	1091	1305	62	4,685	1½"	355
433	576	724	875	1091	1313	1572	68	3,905	1½"	427
528	700	882	1062	1326	1598	1910	75	3,265	1½"	519
629	838	1054	1271	1585	1910	2283	82	2,700	2"	621
758	1009	1268	1530	1910	2301	2748	90	2,230	2"	748
938	1244	1567	1889	2357	2853	3408	100	1,805	2"	923
1133	1506	1894	2285	2853	3435	4122	110	1,490	2"	1120
1464	1945	2449	2959	3672	4439	5310	125	1,160	2½"	1440
2880	3804	4808	5786	7213			175	590	4"	2830
3752	4967	6262	7556	9432			200	454	4"	3690
Reduction ratios							Motor RPM			
13.5	—	—	—	—	—	—	870			
—	13.5	10.8	—	—	—	—	1150			
—	—	—	13.5	10.8	9	7.5	1740			

* The max. possible stroking speed depends upon viscosity and installation parameters.

** Max. permissible pump pressure, based on a maximum crosshead loading of 22,480 lbs.
The design pressure of the pumphead must also be taken into account.

Applications

1
Diaphragm metering pumps for metering monomer and catalysts. 260 gph and 80 gph against 1415 psig operating pressure.

2
Bromine metering application using a diaphragm pump with wetted parts of filled PTFE. 50 gph against 85 psig operating pressure.

3
Diaphragm metering pumps with quick-change valves for metering of nitric acid

in a nuclear reactor fuel reprocessing facility. 70 gph against 152 psig working pressure.

4
High-pressure diaphragm metering pump for metering ammonia. 160 gph against 4600 psig operating pressure.

5
High-pressure diaphragm metering pump used in the chemical industry for metering vinyl acetate. 660 gph against 4600 psig operating pressure.

B-13

Hammelmann Corp.

3949 Dayton Park Drive
Dayton, Ohio 45414
TELEPHONE: 513-233-4935
FAX: 513-233-3951

December 8, 1992

Mr. Glen Thurston
EG&G Idaho, Inc.
P.O. Box 1625
Idaho Falls, ID 83415

Dear Mr. Thurston:

Thank you for your inquiry.

Since 1947 Hammelmann has manufactured thousands of pumps and waterjetting units for service in a broad range of industries all over the world.

Hammelmann pumps feature a high pressure, friction free (labyrinth seal), piston seal assembly. This patented high pressure design eliminates high pressure packing.

The Hammelmann pump also features:

- * Stainless steel, stress free pumphead
- * High volumetric efficient fluid end (stainless steel).
- * Internal geared pump (no belts or pulleys)
- * 40 thru 1500 horsepower bare shaft pump (vertical design above 75 hp)
- * Operating pressure to 35,000 PSI

Accessories such as guns, nozzles, grate/floor cleaners, pipe and tube lances and specialty cleaning devices are available for almost any application. We feature rotorjets for hand or robotic operations as well as stackcleaners.

Hammelmann supplies high pressure equipment to the following industries: automotive, concrete plants, cleaning contractors, airports, chemical, foundries, construction, shipbuilding, metal working, petrochemical, pulp & paper, refineries and numerous other applications. Our experienced staff would appreciate the opportunity to discuss your particular application.

As we can be of assistance with either a quotation, demonstration or special engineering please call, fax or send in your special application.

We look forward to the opportunity to work with you.

Yours Truly,

Michael G. Goetze
General Manager

MGG/kal

Enclosure: Literature

High pressure pumps
Ultrahigh pressure pumps
Process pumps
Application engineering

B-15

High pressure systems, tailor made

HAMMELMANN

High pressure systems, tailor made

Hammelmann High pressure technology is based upon our High pressure, Ultrahigh pressure and Process pumps. Operating pressure and flow rate determine performance and results. We offer a range of over 1000 combinations to meet individual requirements.

Op. pressures: 500 - 35.000 psi
Flow rates: 1 - 1000 gpm
Power ratings:
3 plunger pumps 40, 80, 100, 150, 220, 450 HP
5 plunger pumps 250, 750, 1500 HP

The well known reliability and high performance of Hammelmann pumps stems from the most modern high pressure technology.

The vertical, coaxially aligned construction reduces wear on moving components. Crossheads, plungers and sleeves operate with evenly distributed weight forces. Another advantage of our vertical design is that the water end is self-venting.

The friction free plunger seal assembly (patented in F.R.G. and abroad) has no seals or packings in the high pressure end. The labyrinth system metallic seal gives a long working life so it is possible to accurately plan servicing intervals.

□ Minimum of stressed area

The valve housing is not subjected to alternating stress. The special design eliminates the risk of fatigue cracking and pressure bearing surfaces are kept to an absolute minimum resulting in a correspondingly reduced load.

The crankshaft main bearings are fitted between the connecting rods. This extremely robust and precise construction results in long working life expectancy for the crank section.

The pressurised oil lubrication system feeds filtered, cooled oil to all sliding and rotating crank parts even under extreme operating conditions such as inclined working or continual changes in demand.

The many and varied application requirements are met by building the pump into a suitable self contained unit. Our standard range includes stationary units with electric or diesel drives, mobile units for on site or public road use and sound dampened units complying with the most stringent noise emission regulations.

END

DATE
FILMED

7 / 8 / 93