2.
.
.
WSRC-TR-92-302

RELEASE OF AMMONIA FROM HAN-TYPE PHA (U)

WSRC-TR--92-302

by J. R. Zamecnik

DE93 004878

Westinghouse Savannah River Company
Savannah River Site
Aiken, South Carolina 29808

Other Authors: *N/A*

MASTER
NOV 17 1992

This paper was prepared in connection with work done under Contract No. DE-AC09-89SR18035 with the U. S. Department of Energy. By acceptance of this paper, the publisher and/or recipient acknowledges the U. S. Government's right to retain a nonexclusive, royalty-free license in and to any copyright covering this paper, along with the right to reproduce and to authorize others to reproduce all or part of the copyrighted paper.

MASTER

So
DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

This report has been reproduced directly from the best available copy.

Available to DOE and DOE contractors from the Office of Scientific and Technical Information, P.O. Box 62, Oak Ridge, TN 37831; prices available from (615) 576-8401, FTS 626-8401.

Available to the public from the National Technical Information Service, U.S. Department of Commerce, 5285 Port Royal Rd., Springfield, VA 22161.

Keywords: DWPF, Ammonia,
Ammonium Nitrate

cc: R. T. Begley, 773-A
L. M. Papouchado, 773-A
H. H. Elder, 704-S
W. J. Vetsch, 704-S
J. A. Gentilucci, 704-S
D. H. McGulre, 704-27S
E. C. Guldotti, 704-27S
J. T. Carter, 704-1T
L. F. Landon, 704-T
SRTC Records (4)

June 10, 1992

D. B. Amerine, Manager DWPF
Westinghouse Savannah River Company

Attention: J. F. Ortaldo, 704-S (5)

RELEASE OF AMMONIA FROM HAN-TYPE PHA

Attached is WSRC-TR-92-302 "Release of Ammonia from HAN-Type PHA in the DWPF Chemical Process Cell - Results of the IDMS HM4 Run". During Run HM4, Precipitate Hydrolysis Aqueous (PHA) which was made using the Hydroxylamine Nitrate (HAN) Process was used in melter feed preparation and the process vessel vent system was monitored for ammonia evolution.

The data is currently being compared to the Theoretical Model of Ammonia Evolution (WSRC-RP-92-346) and will be used to update the Preliminary Design Criteria for the DWPF Ammonia Scrubbers (WSRC-TR-92-160). This basis will be updated by 6/20/92 per the DWPF scrubber schedule.

WSRC-TR-92-302 also serves as the basis for attainment calculations for the HAN Process. Approximately 60 pounds of ammonium nitrate can accumulate during SRAT and SME Processing (in the absence of scrubbers) excluding any deposition from the RCT. The experimentation was repeated during IDMS Run PX3 and additional data was obtained to include the RCT. This will be reported as soon as all analytical results are available.

Questions can be directed to J. T. Carter (5-6454) or J. R. Zamecnik (5-6300) of my staff.

Sincerely,

E. W. HOLTZSCHEITER, MANAGER
DEFENSE WASTE PROCESSING TECHNOLOGY

WESTINGHOUSE SAVANNAH RIVER COMPANY
SAVANNAH RIVER TECHNOLOGY CENTER

WSRC-TR-92-302

Keywords: DWPF, IDMS,
Ammonia, Ammonium
Nitrate, SRAT, SME

Retention: Permanent

June 10, 1992

cc: L. M. Papouchado, 773-A E. W. Holtzscheiter, 773-A
M. J. Plodinec, 773-A C. T. Randall, 704-T
L. F. Landon, 704-T J. E. Lunn, 704-T
Process Modeling and Control Group (10)
Process Technology and Development Group (9)
Glass Technology Group (8)
Large Scale Experimentation Group (11)
TNX Operations Section (4)
SRTC Records (4)

To: J. T. Carter, 704-1T

From: J. R. Zamecnik

RELEASE OF AMMONIA FROM HAN-TYPE PHA IN THE DWPF CHEMICAL
PROCESS CELL - RESULTS OF THE IDMS HM4 RUN

INTRODUCTION

A preliminary design basis for ammonia scrubbers in the DWPF has been issued.¹ This design basis is based on a theoretical model of ammonia evolution from the SRAT, SME and RCT.² It is desirable to acquire actual process data on ammonia evolution prior to performing detailed design of scrubbers for DWPF.

The evolution of ammonia from the SRAT and SME in the Integrated DWPF Melter System (IDMS) was investigated during the HM4 run. In this run, Precipitate Hydrolysis Aqueous (PHA), which was made in the Precipitate Hydrolysis Experimental Facility (PHEF) using the HAN (hydroxylamine nitrate) process was used, thus resulting in PHA with a high concentration of ammonium ion.

J. T. Carter, 704-1T
Authorized Derivative Classifier

The ammonia in the Chemical Process Cell (CPC) comes from three sources:

- 1) the PHA via decomposition of HAN.
- 2) the PHA via radiolysis of the precipitate during storage in Tank 49 (does not occur with PHA from PHEF).
- 3) ammonia formed in the SRAT from the reaction of nitrite or nitrate with formic acid and formate.

Since HAN-type PHA was used in HM4, it was not possible to determine the amount of ammonia produced by (3), since the amount produced by these reactions is much smaller than the amount added with the PHA. Moreover, since nitric acid was used rather than formic acid for pH adjustment, the amount of ammonia produced from nitrite and nitrate is even smaller than it may have been if formic acid had been used.

CHRONOLOGY

In the HM4 run, approximately 1100 gal of simulated HM-type sludge was used. This sludge contained flowsheet levels of all chemicals including noble metals and mercury. The sludge contained no ammonium initially. The nitrite level in this sludge was approximately 0.3M. Nitric acid ($\approx 7.5M$, 75 gal) was added at 95°C and was then refluxed for several hours.

PHA was then added over five days in 17 small (100-150 gal) batches which were each concentrated before the next addition. The amount of PHA added was 2000 gal; this PHA contained only about 50-60% of the amount of formic acid/formate normally in HAN-type PHA due to excess boiling of the PHA in PHEF. The ammonium concentration in the PHA was 1065 mg/l.

Frit slurry was then added and the SME concentrated on five separate days. Figure 1 shows the addition rates, SRAT/SME temperature and pH for the nitric acid and PHA additions and the first three SME concentrations.

SAMPLING

Samples of the SRAT, SME, the SRAT/SME Condenser (SRATC/SMEC) condensate were taken and analyzed for ammonium throughout the run. Offgas samples were taken at the SRAT/SME condenser exit and the FAVC inlet by drawing small amounts of offgas through two scrubbers containing 2M sulfuric acid. This method is based on a published method.⁴ The resulting scrub solutions were then analyzed for ammonium ion by ion chromatography.

RESULTS

Analysis of the SRAT and SRATC condensate samples during the nitric acid addition and reflux showed no detectable ammonium. The offgas samples also showed no ammonia.

As shown in Figures 1 and 2, the pH of the SRAT began increasing from ≈ 6.2 to ≈ 7.7 upon addition and concentration of the PHA. The pH reported is that measured by either the on-line pH probe or that of samples analyzed in the laboratory. During the time in which the lab pH is reported, the on-line measurements were unreliable. Note that the addition of PHA decreased the pH and that the pH then quickly increased back to the same or higher value upon concentrating. Also note that the lab pH values reported were adjusted to estimate the average pH since the samples analyzed were taken immediately after addition of PHA (the pH was near the bottom of the spikes).

The condensate pH quickly increased from about pH 2 to pH 9 when ammonia began to be detected in condensate. At about 55 hours, ammonia was first detected in the offgas samples. As more ammonia was added to the SRAT with the PHA, the amount of ammonia found at all locations increased.

During the SME cycle, the SME pH increased only slightly, the SRAT ammonium concentration decreased steadily, and the concentration of ammonium in the condensate increased slightly. The concentration of ammonia in the offgas continued to increase.

Figure 3 shows the total amount of ammonia (gmol) in the SRAT/SME, SRAT/SME Condenser condensate and the offgas at the SRAT/SME Condenser exit and FAVC exit as functions of time. The amount of ammonia in the offgas is seen to be a small portion of the total ammonia emitted from the SRAT/SME. Figure 4 shows the configuration of the offgas system in IDMS. The condensate from the condenser goes to the Waste Water Pump Tank (WWPT), which is operated in a manner similar to the Recycle Collection Tank (RCT) in DWPF. The pH of the WWPT is maintained at 9-12. At this pH, the theoretical model predicts that a significant amount of ammonia should be released from the WWPT.

Between the SRAT/SME condenser and the FAVC, 16-27% of the ammonia leaving the SRAT/SME condenser was deposited, assuming that no ammonia comes from the WWPT. Not knowing the rate of generation of ammonia from the WWPT makes it impossible to determine how much ammonium nitrate is deposited between the condensers.

Referring to Figure 4, the following material balance can be written:

$$N_{\text{deposited}} = N_2 + N_4 - N_5$$

where N is the mass of ammonium nitrate equivalent to the amount of ammonia measured. Since N_4 is unknown, it can only be concluded that the deposits are greater than or equal to $N_2 - N_5$. Table 1 shows the amounts of ammonia in the SRAT/SME, condensate and offgas during the run. The closure of the material balance ranged from 103 to 112%, which, based on the inaccuracies in the data (see Appendix), is very good.

Figure 1. Nitric Acid and PHA Additions, SRAT/SME Temperature, and SRAT/SME pH During the HM4 Run.

Figure 2. Ammonia and Ammonium Concentrations, Offgas Flowrate and Condensate Flowrate During the HM4 Run.

Figure 3. Total Ammonia and Ammonium During HM4.

Figure 4. IDMS Feed Preparation System.

The amount of ammonia fed that was scrubbed to the condensate ranged from 42-62%, with the percentage increasing with time. The amount of ammonia in the offgas also increased with time, from 6% to 12.5%. Of all of the ammonia added with the PHA, 3.4% was deposited in the offgas system (assuming no ammonia from the WWPT). Table 1 summarizes these results.

Table 2 shows the total amounts of ammonium nitrate that could have potentially accumulated after the SRAT/SME Condenser for the HM4 run. The first column contains the amount of ammonium nitrate that could potentially have accumulated during HM4 if none had been scrubbed in the SRAT/SME Condenser. The actual amount that was deposited is given in column 2.

Table 3 shows the peak evolution rates of ammonia from the SRAT and SME. Also included are the flowrates of ammonia in the SRATC and SMEC condensate, and in the vapor from the SRATC and SMEC.

RECOMMENDATIONS FOR FUTURE IDMS RUNS

Since the amount of ammonium nitrate from the RCT (WWPT) was not measured during the HM4 run, it is recommended that this quantity be measured or estimated during future runs. These necessary measurements are presently being performed in the IDMS PX3 run.

Table 1
Ammonia Mass Balances for HM4

(gmol)

	In SRAT Initially	Added In PHA	After PHA Addition	After Partial SME*	After Complete SME	Total
SRAT or SME	0	480.2	262.8	182.5	103.6	103.6
Condensate			202.2	91.1	159.6	361.8
Condenser Exit Vapor			29.7	30.4	43.7	73.4
FAVC Inlet Vapor			24.9	18.9	30.2	55.1
Estimated deposit between Condenser & FAVC			4.8	11.5	2.0	18.3

* approximately 2/3 of SME cycle completed

Table 2
Total Ammonia Evolution During
the HM4 Run (on a DWPF Basis)

		Total Ammonia	
Evolution From:		HM4 ¹	HM4 ²
	SRAT	33.0	4.9
	SME	26.2	7.2
	RCT	N/A	N/A
Total Accumulation		59.2	12.1
¹ total ammonia evolved			
² total ammonia exiting in SRATC/SMEC vapor			

Table 3
Ammonia Concentrations from the SRAT and SME
(condensate concentrations converted to vapor basis)

	ppm by volume
SRAT	2465
SME	4857
SRATC Condensate	2046
SMEC Condensate	3972
SRATC Vapor	419
SMEC Vapor	885

REFERENCES

1. L. F. Landon, "Preliminary Design Bases for DWPF Ammonia Scrubbers (U)", **WSRC-TR-92-160**, April 10, 1992.
2. L. Lee, "Formation Rate of Ammonium Nitrate in the Off-Gas Line of SRAT and SME in DWPF", **WSRC-RP-92-346**, February 25, 1992.
3. L. Lee, "Total Ammonium Ion Concentration in SMEC(T) Condensate," May 29, 1992.
4. B. Dellinger, G. Grotecloss, C. R. Fortune, J. L. Cheney, J. B. Homolya, "Sulfur Dioxide Oxidation and Plume Formation at Cement Kilns." **Environmental Science & Technology**, 14(10), p. 1244, (1980).

APPENDIX**SOURCES OF ERROR**

The analytical results (IC) were $\pm 5\%$. The tank volumes used in determining the total amounts of ammonium were ± 150 gal due to problems with the Hollidge gauge level probe. The condensate flowrate had to be estimated since its flow was not measured. It was estimated as 90% of the actual steam flowrate when the SRAT/SME was at boiling and as 0.2 gpm when above 90°C.

END

**DATE
FILMED**

4 / 20 / 93