INDEPENDENT VALIDATION TESTING
OF THE FLAME COMPUTER CODE, VERSION 1.0

EGG-GEO--10368

DE92 019691

Pete Martian
Jacob N. Chung

July 1992

Department of Mechanical and Materials Engineering
Washington State University
Pullman, Washington 99164

Prepared for EG&G Idaho, Inc.
Under Subcontract No. C85-110796-010
and for the
U.S. Department of Energy
Office of Environmental Restoration and Waste Management
Under DOE Idaho Field Office Contract No. DE-AC07-76ID01570

MASTER

ABSTRACT

Independent testing of the FLAME computer code, Version 1.0, was conducted to determine if the code is ready for use in hydrological and environmental studies at Department of Energy sites. This report describes the technical basis, approach, and results of this testing.

Validation tests, (i.e., tests which compare field data to the computer generated solutions) were used to determine the operational status of the FLAME computer code and were done on a qualitative basis through graphical comparisons of the experimental and numerical data.

These tests were specifically designed to check: (1) correctness of the FORTRAN coding, (2) computational accuracy, and (3) suitability to simulating actual hydrologic conditions.

This testing was performed using a structured evaluation protocol which consisted of: (1) independent applications, and (2) graduated difficulty of test cases.

Three tests ranging in complexity from simple one-dimensional steady-state flow field problems under near-saturated conditions to two-dimensional transient flow problems with very dry initial conditions. These validation tests showed good agreement with the experimental data considering the complex nature of the field hydraulic properties and the uniform soil models used in the simulations. However, two options were found to be not operational and several "bugs" were encountered during the testing.

Based on the results of this testing, it was concluded that the FLAME code represents a high level of code development, but was found to be only partially operational and in need of further refinement. Nevertheless, the code is a versatile and powerful two-dimensional analysis tool for groundwater solute transport and the code may be used in hydrological and environmental studies at the INEL but caution should be exercised not to use the inoperational options until they are corrected.

Table of Contents

List of Figures	iii
List of Tables	iii
1.0 INTRODUCTION	1
1.1 Background	1
1.2 Computational Testing	2
1.3 Description of Test Cases	2
2.0 TEST APPROACH AND REQUIREMENTS	4
2.1 Test Objectives	4
2.2 Test Protocol	4
2.3 Performance Evaluation	5
3.0 VALIDATION TESTS	6
3.1 Los Alamos Caisson Experiment	6
3.2 Las Cruces Trench Experiment 1	13
3.3 Las Cruces Trench Experiment 2	19
4.0 FINDINGS AND RECOMMENDATIONS	25
4.1 General Findings	26
4.2 Recommended Refinements	27
4.3 Recommendations for additional Testing ..	28
ACKNOWLEDGMENTS	29
REFERENCES	30

List of Figures

1	Los Alamos caisson experiment cluster	6
2	Test VAL-1 break-through curve at 36 cm	9
3	Test VAL-1 break-through curve at 113 cm	10
4	Test VAL-1 break-through curve at 264 cm	11
5	Test VAL-1 break-through curve at 339 cm	12
6	Test VAL-1 break-through curve at 415 cm	13
7	Plan view of test trench and experiment 1 area	15
8	Test VAL-2 break-through curve at 0.5 m	18
9	Test VAL-2 break-through curve at 1.5 m	19
10	Plan view of test trench and experiment 2 area	20
11	Geometry for test VAL-3	22
12	Observed relative concentrations on day 71	24
13	Relative concentrations predicted by FLAME on day 71	24
14	Observed relative concentrations on day 277	25
15	Relative concentrations predicted by FLAME on day 277	25

List of Tables

1	Initial tensions for test VAL-2	16
2	Initial tensions for test VAL-3	21

1.0 INTRODUCTION

The Department of Mechanical and Materials Engineering of Washington State University has conducted independent testing of the FLAME Version 1.0 computer code. The main objective of the study focused on determining whether the code is ready for use in hydrological and environmental studies at the Idaho National Engineering Laboratory (INEL) and other Department of Energy (DOE) sites. This primary objective was accomplished through validation tests (i.e., comparisons with field or laboratory data). This report describes the basis, approach and results of the FLAME testing.

1.1 BACKGROUND

The FLAME computer code was primarily developed for use in performance assessment studies that focus on evaluation of clean-up and disposal options at the INEL site. The code was specifically designed to solve groundwater contaminant transport problems occurring at arid sites. Some of the primary code capabilities are:

- o models mass transport in either time-dependent or steady-state flow fields,
- o accommodates advection-dominated mass transport,
- o describes mass transfer between the porous media and discrete fractures, and
- o accommodates heterogeneous media with complex stratigraphy.

The FLAME code uses pressure head and volumetric moisture content distributions generated by the companion code, FLASH (Baca and Magnuson, [1992]), to calculate velocity fields. The code solves the advective-dispersion equation using the Galerkin finite-element method. Some of the major assumptions are:

- o fluid flow is independent of solute concentrations,
- o dispersion induced by fluid flow is described by a Fickian type flux law,
- o sorption of the contaminant onto the porous media is an equilibrium process described by a linear isotherm,
- o fluid properties are independent of temperature, and
- o transport properties of the porous continuum are volume averages.

1.2 COMPUTATIONAL TESTING

Computational testing in general can be divided into 3 categories: (1) verification, (2) validation, and (3) benchmarking. Verification testing is performed by comparing known analytical solutions to groundwater problems with the equivalent numerical solutions provided by the tested code. Code validation is aimed at determining how well mathematical theory used in the computer code agrees with real phenomena (i.e., comparing numerical results from the tested code with field data). Benchmark testing involves code-to-code comparisons using test problems that are realistic and of practical interest.

The most critical of the three testing categories is code validation and the scope of the FLAME testing was limited to this category. The validation testing was performed with the main objective of determining a "degree of correlation" between predicted results and the observed data. As used here a computer code is said to be adequately *validated* when the numerical results show reasonable correlation with the field data. The results of the validation testing contained in this report provide the technical documentation certifying the operational status of the FLAME computer code, version 1.0.

1.3 DESCRIPTION OF TEST CASES

Three test problems were selected from various studies sponsored by the U.S. Nuclear Regulatory Commission. The three validation tests were simulations of actual field experiments of increasing complexity. Two of the three validation tests were also modeled by different researchers and could serve to provide an informal benchmarking of the FLAME code. The following are brief descriptions of the three validation problems.

VAL-1 Los Alamos Caisson Experiment. Nearly saturated, steady-state flow with a bromide pulse is considered with experimental data taken from caisson B of the Los Alamos caisson experiment by Polzer et al. [1986]. This validation test demonstrated the ability of the FLAME code to solve the one-dimensional advective-dispersion equation under a steady-state flow field.

VAL-2 Las Cruces Test Trench Experiment 1. Experiment One at the Las Cruces Test Trench is simulated in which water containing a tritium tracer is applied over a wide area as described by Wierenga et al. [1991]. This test problem provides a comparison of FLAME code simulation with a one-dimensional transient flow field problem which is much more difficult to solve numerically than test VAL-1 because of very dry initial conditions occurring in the Las Cruces Test Trench soils.

VAL-3 Las Cruces Test Trench Experiment 2. This test considers Experiment Two at the Las Cruces Test Trench where a narrow plot is irrigated over a 75.5 day period described by Wierenga et al. [1991]. A bromide tracer is added to the applied water during a short period at the start of the experiment. The simulation uses the in-situ soil properties of the native soil and tests the ability of the FLAME code to solve a difficult two-dimensional transport problem under very dry initial conditions and provides a step up in complexity over test VAL-2.

2.0 TEST APPROACH AND REQUIREMENTS

2.1 TEST OBJECTIVES

The main objective of this study was to determine the operational status of the FLAME computer code for use in hydrological and environmental studies at the INEL. This was accomplished by testing the major options, features and computational algorithms of the code. Three fundamental conclusions were possible: (1) the code is fully operational, (2) the code is only partially operational and some corrections and/or improvements are needed, and (3) the code is not operational and requires further development. The work presented in this report provides both quantitative and qualitative evidence to support the conclusion.

2.2 TEST PROTOCOL

The testing process was designed to be an independent and unbiased evaluation of FLAME, Version 1.0. To perform the testing process, a convention using the following requirements was employed:

- (1) independent applications, and
- (2) graduated difficulty of tests.

The first requirement excluded the code developer from participating in the testing process. The code tester was permitted to consult the code developer only if: (1) unexplained difficulties arose, (2) code modifications were necessary to accommodate special characteristics of a specific test problem, or (3) clarification of input instructions was needed.

The second requirement allowed testing of the code over a wide range of problems to determine the application limits of the code.

2.3 PERFORMANCE EVALUATION

Judging the quality of correlation between code and field results was somewhat problematic because the validation tests are actual attempts to simulate field conditions. Field conditions represent complex physical settings which are usually simplified for incorporation into a numerical simulation. Because significant differences were expected in the results from FLAME and the experimental data gathered in the field experiments, a qualitative graphical comparison was made for the variable of interest which was solute concentration.

3.0 VALIDATION TESTS

3.1 LOS ALAMOS CAISSON EXPERIMENT

3.1.1 VT-1 Problem Statement

This validation test considers one-dimensional steady-state unsaturated flow with a bromide tracer. The test was taken from Polzer et al. [1986] and was based on results from caisson B of the Los Alamos caisson experiment. The simulation tests the capability of FLAME to predict solute break-through curves under steady flow conditions.

3.1.2 Experimental Background

The experiment was conducted in the one of the six caissons in the experiment cluster at the Engineered Test Facility located at Los Alamos National Laboratory. The caisson is 3 meters in diameter by 6 meters deep as illustrated in Figure 1.

Figure 1. Los Alamos caisson experiment cluster

Caisson B was used for the steady state experiment and was filled with native Los Alamos tuff. The tuff was excavated using front end loaders and then crushed by running the front end loaders over the tuff before being screened through a 12.7 millimeter screen. The tuff was then mixed in a cement truck with enough water to obtain a moisture content of 10 to 13 % ensuring maximum mixture density. Finally, the tuff was compacted into the caisson in 15 to 20 cm layers using "jumping jacks". The caisson was then instrumented with horizontal and vertical neutron probe access tubes along with solute samplers and thermocouple psychrometers.

Water was then applied at a rate of 200 ml/min until a steady-state condition was achieved, i.e. flow into the top equaled flow out the bottom. At this time a bromide tracer was added to the water source corresponding to a concentration of 89 mg/l over a six day period. Finally, solution samples were taken over time at approximately 75 cm intervals throughout the caisson beginning at the 36 cm depth.

3.1.3 Input Specifications

The tuff hydraulic properties describing the flow field were taken from Abeele [1984] and the soil moisture curve can be represented as

$$\Theta_v = 1.1455 - \frac{\ln \Psi}{4.8678}.$$

Where Θ_v is moisture content and Ψ is matric potential in KPa. The moisture curve is valid for moisture content ranging from 0.35 to 0.90 of saturation. This soil moisture curve was then input into a curve fitting program to calculate the van Genuchten parameters and the relative hydraulic conductivity curve needed in FLASH. The parameters obtained were

$$\alpha = 0.00125 \text{ 1/cm}$$

$$N = 4.81312$$

$$K_s = 0.000146 \text{ cm/sec}$$

$$\Theta_s = 0.346$$

$$\Theta_r = 0.12$$

Transport properties were unknown and various values of dispersivity were arbitrarily tried. Diffusion was set to zero and a dispersivity of .5 cm provided the best match between the experimental data and the numerical data from the simulation.

A uniform grid of 50 line elements and 101 nodes was used to discretize the 550 cm deep soil profile. The bromide concentration of $8.9 \times 10^{-5} \text{ g/cm}^3$ was specified as the surface boundary condition over a six day period. This initial period was followed by a 44 day redistribution period in which both the upper and lower boundaries were specified as zero flux.

3.1.4 Output Requirements

The output from this validation test was the solute break-through curves at the 36, 113, 264, 339 and 415 cm depths.

3.1.5 Validation Test Results

Test VAL-1 was involved simulating one-dimensional transport in a steady state velocity field on a large scale and was the simplest of the three validation tests. The experimental data reflected some expected soil layering was present in the caisson.

Figures 2 through 6 show the experimental values superimposed over the FLAME results. These results illustrate good agreement in shape and magnitude however, the position of the break through curves show only fair agreement. At the 36 and 113 cm depths, there is good correspondence between FLAME and the experimental data in peak concentration position but at 264 cm depths, the FLASH results lead the experimental results while at 339 and 415 cm depths the FLASH results lag behind the experimental results.

These discrepancies indicate that distinct differences in pore water velocities occurred at different depths in the caisson because of non-uniformities in the soil hydraulic properties. By defining different hydraulic properties and dispersivities at different caisson depths a much better agreement between experimental data and numerical results could have been obtained. Specifically, a lower saturated conductivity could have been assigned near the caisson center, while a higher

saturated conductivity could have been specified in the lower third of the caisson. Nevertheless, the results do show the FLAME code does a good job of predicting solute break-through curves under steady flow conditions considering the uniform soil model used in the simulation.

Figure 2. Test VAL-1 break-through curve at 36 cm.

Figure 3. Test VAL-1 break-through curve at 113 cm.

Figure 4. Test VAL-1 break-through curve at 264 cm.

Figure 5. Test VAL-1 break-through curve at 339 cm.

Figure 6. Test VAL-1 break-through curve at 415 cm.

3.2 LAS CRUCES TRENCH EXPERIMENT 1

3.2.1 Problem Statement for VAL-2

Test VAL-2 was taken from Experiment One of the Las Cruces field trench study presented in Wierenga et al. [1991]. A 4 m by 9 m area was irrigated with water containing a tritium tracer. The test is a transient one-dimensional simulation in which the tritium tracer was added during the early part of the simulation.

3.2.2 Experimental Background

A deep trench was constructed at the Las Cruces Trench Site providing horizontal access to adjacent irrigated plots for tensiometers and solution samplers. Two experiment areas were placed on the north and south sides of the trench to provide a base case to test one and two-dimensional ground water models. A narrow strip was irrigated on the north side plot providing two-dimensional experimental data, while a wide area was irrigated on the south side plot providing one dimensional experimental data.

This validation test considers the latter experiment as illustrated in Figure 7. A 4 m by 9 m area was irrigated using closely spaced drip emitters at a rate of 1.82 cm/day. The tritium tracer was added to the applied water at a rate of 0.01 mCi/l over the initial 10 days of the irrigation period. Solute samplers, tensiometers and neutron probes were then used to monitor solute and water transport over the experimental period.

Not to Scale

Figure 7. Plan view of test trench and experiment 1 area.

3.2.3 Input Specifications

A uniform soil model i.e., homogeneous without layering was used in the simulation and the hydraulic parameters were taken from Wierenga et al. [1991]. The van Genuchten parameters were:

$$\alpha = 0.05501 \text{ 1/cm}$$

$$N = 1.5093$$

$$K_s = 270.1 \text{ cm/day}$$

$$\Theta_R = 0.0828$$

$$\Theta_s = 0.3209$$

Because dispersivity was not determined in the trench experiment, various values were tried and the best match between the experimental data and FLAME results was obtained with a dispersivity of 1.0 cm.

Initial conditions were taken from initial tension readings before the start of the experiment and are shown in Table 1. A cubic spline was then fit to the initial conditions to estimate tensions at intermediate depths while the tensions above 60 cm were assumed to be the same as those at 60 cm.

Table 1. Initial tensions for test VAL-2

<u>Depth (cm)</u>	<u>Head (cm H₂O)</u>
60	6910
135	21530
210	28860
285	36980
360	47090
435	48020
510	53300
585	56350
660	64940

The test trench was modeled to a depth of 660 cm using 101 nodes. The upper node was specified at a relative concentration of 1.0 while a zero flux was designated at the bottom node. To prevent any boundary effects from the zero flux bottom boundary, the simulation was restricted to 40 days which corresponded to time well before the wetting front reached the 600 cm depth as determined by neutron probe measurements.

3.2.4 Output Requirements

The output from this validation test was the solute break-through curves at 0.5 m and 1.5 m.

3.2.5 Validation Test Results

Test VAL-2 provided an increase in complexity over test VAL-1. The strong wetting moving through very dry initial conditions pose a challenging computational problem to test the computational stability of the FLAME code. The numerical solution proved to be very stable with only a slight oscillation occurring near the solute front.

Plots of observed break-through curves and the break-through curves as predicted by FLAME are illustrated in Figures 8 and 9. There is excellent agreement in shape and magnitude between the experimental data and the FLAME results, however the FLAME results slightly lead the experimental results at both depths.

The slight lead of the FLAME results can be explained by an overestimation of hydraulic conductivity by the uniform soil model in the 15 to 140 cm depth. Nine distinct soil layers have been identified at the Las Cruces Test Site with saturated conductivities varying between 171.5 to 539.2 cm/day. The use of a layered soil model would provide better agreement in position of the break-through curves by adjusting the flow field to agree with actual field conditions. Overall, the FLAME code did good job of estimating break-through curves in a transient one-dimensional simulation considering the uniform soil assumption.

Figure 8. Test VAL-2 break-through curve at 0.5 m.

Figure 9. Test Val-2 break-through curve at 1.5 m.

3.3 LAS CRUCES TRENCH EXPERIMENT 2

3.3.1 Problem Statement for VAL-3

This validation test, taken from Wierenga et al. [1990], considers Experiment 2 conducted at the Las Cruces Trench Site. A narrow plot is initially irrigated with a bromide solution which is followed first by a period of solute-free water application and then by a period of redistribution. A cross-section perpendicular to the irrigated strip is modeled with the FLAME code in order to test a two-dimensional transient simulation problem.

3.3.2 Experimental Background

Experiment 2 was conducted on the north side of the test trench described in section 3.2.2 and is illustrated in Figure 10. Water was applied to a 1.2 m by 12 m area adjacent to the test trench through a series of closely spaced drip emitters. The water was applied at a rate of 0.43 cm/day and neutron probe readings and solution samples were taken every 4 to 5 days. The applied water contained a bromide tracer at 939 mg/l concentration during the first 11.5 days of the irrigation period and thereafter was applied without tracers for an additional 64 days.

Figure 10. Plan view of test trench and experiment 2 area.

3.3.3 Input Specifications

A modeling approach similar to Wierenga et al. [1990] was used in this validation test. The same uniform soil model used in test VAL-2 was used in this validation test, however the dispersivity was changed to 5 cm and molecular diffusion was specified as 1.0×10^{-5} cm/sec corresponding to the transport properties used by Wierenga et al. [1990].

Initial conditions were taken from initial tension readings before the start of the experiment and are shown in Table 3. The top 1.5 m have an unusually high water content due to heavy rainfalls just prior to beginning the experiment. Linear interpolation was then used to estimate initial tensions at intermediate depths.

Table 3. Initial tensions for test VAL-3.

<u>Depth (cm)</u>	<u>Head (cm H₂O)</u>
25	143.9
75	170.2
100	249.3
150	215.5
210	28860
285	36980
360	47090
435	48020
510	53300
585	56330
660	64940

Symmetry was utilized and only one half of the experimental domain was modeled. A region 600 cm deep by 508.33 cm wide was discretized using 1005 isoparametric rectangular and isoparametric triangle transition elements. Some refinement in the finite-element grid near the 150 cm depth was necessary because of the strong wetting front presented by the initial conditions. All boundary conditions were specified as no flux except for the upper left hand corner where a specified concentration was used during the initial 11.5 days of the simulation. The computational domain is illustrated in Figure 11.

Figure 11. Geometry for test VAL-3

3.3.4 Output Requirements

Relative concentrations (C/C_0) throughout the modeled cross-section at 71 and 277 days were compared graphically with the experimental data taken from solution samplers located 0.5 m behind the trench wall.

3.3.5 Validation Test Results

Test case VAL-3 was the most rigorous test of the transport algorithms implemented in the FLAME code. This two-dimensional problem tested the FLAME code's capability to simulate transient flow, unsaturated transport problems under complex hydrologic conditions. Heavy rains prior to the experiment further complicated the test case by placing a strong wetting front in the initial conditions.

The experimental data and the FLAME simulation are shown with the numerical results in Figures 12 through 15. Because of the sparse experimental data, a graphical presentation program, Graphtool (3-D Visions Corporation, Redondo Beach, California), was used generate additional data points using an inverse distance weighting algorithm. Plots of the modified experimental data show that a large amount of spatial variability is present in the observed tracer concentrations indicating significant soil layering probably exists in the test trench soil. Although the effects of heterogeneity in the soil have distorted the solute concentration profiles in the experimental data, there appears to be relatively good qualitative agreement between the FLASH results and the experimental data. General regions of the experimental data tend to have the same overall relative concentrations as predicted by the FLAME code.

The FLAME code did a good job of predicting relative concentrations in a two-dimensional problem considering the complexity of the soil located at the Las Cruces Test Trench. Additionally, the FLASH code results agreed very closely with the modeling results obtained by Wierenga et al. [1990].

Figure 12. Observed relative concentrations on day 71.

Figure 13. Relative concentrations predicted by FLAME on day 71.

Figure 14. Observed relative concentrations on day 277.

Figure 15. Relative concentrations predicted by FLAME on day 277

4.0 FINDINGS AND RECOMMENDATIONS

Detailed computational testing of the FLAME computer code was performed with two main objectives in mind: (1) to determine the operational status of version 1.0 of the code and (2) to examine the general capabilities and limitations of the code. These objectives were accomplished through code validation tests, i.e. comparison of the numerical results with the corresponding experimental data. These validation tests were specifically designed to:

- o check the correctness of the FORTRAN coding,
- o assess computational accuracy, and
- o test the code's capability to simulate diverse hydrologic conditions.

4.1 GENERAL FINDINGS

Results of the three validation tests showed good qualitative agreement between the FLAME results and experimental data. Comparison of break-through curves for the steady-state and transient problems illustrated very good agreement in shape and magnitude but some discrepancies were present in the position of the curves. Spatial heterogeneities in soil hydraulic properties were probably responsible for the discrepancies.

The two-dimensional validation test showed good agreement in magnitude but poor agreement in shape of the solute concentration profile. This poor agreement was once again, probably due to differences between the uniform soil assumption in the FLAME model and the heterogeneity occurring in the test trench soil itself. Overall, the validation tests showed the FLAME code does a good job of simulating complex, hydrologic conditions.

Two options were found to be not operational in the FLAME code. Specifically, these were: (1) the FLUX boundary which allows the use to specify point sources of a contaminant as a mass injection rate and (2) the retardation factor in the transport command which allows users to account for adsorption or precipitation of contaminant species from the ground water matrix. Additionally, several bugs were found and corrected in the code during the testing. Because of these discrepancies,

the code was found to be only *partially operational* and in need of some refinement.

The FLAME code is a powerful two-dimensional analysis tool for contaminant transport in groundwater and may be used hydrological and environmental studies at the INEL and other DOE sites as the code now stands but caution should be exercised not to use the inoperational options until they are fixed.

4.2 RECOMMENDED REFINEMENTS

The FLAME computer code represents a high level of code development. However, the independent code testing reported here has identified two specific areas where the code would benefit from further refinement. These are, (1) computational changes and (2) output options. Specific recommendations for improvements in these areas are discussed below.

4.2.1 Computational Changes

Results of the validation tests demonstrated that the computational algorithms are highly efficient and well programmed. However, the bugs encountered during testing indicate some overall refinement should be done. Additionally, the inoperational options mentioned in section 4.1 should be corrected and the operational status of all other available options should be thoroughly tested.

4.2.2 Output Options

The output file provided a good history of the simulation run, however the output did not allow easy plotting of solution parameters such as concentration and fluid velocity vs. position. An option should be incorporated to output solution parameters in a two column format (depth vs. concentration etc.) for one-dimensional simulations and a three column format (x position and y position, vs. concentration etc.) for two-dimensional simulations.

4.3 RECOMMENDATIONS FOR ADDITIONAL TESTING

The validation test cases were aimed at testing the major feature of the FLAME code, namely solute transport. However, other features of the code would benefit from further testing. These are:

- o transport in heterogeneous media with complex stratigraphy, and
- o transport in discrete fractures (dual permeability model).

Additionally, formal benchmark testing should be performed to provide a performance comparison with similar codes and verification testing should be performed to compare known analytical solutions with equivalent numerical solutions provided by the FLAME code.

ACKNOWLEDGMENTS

The authors wish to thank a number of individuals who provided assistance with this project. First and foremost, the authors thank Swen O. Magnuson, of EG&G Idaho, Inc., for his assistance in debugging the FLAME code and for his thorough review of the draft report. The authors also wish to thank Robert G. Baca, from Southwest Research Inc., for providing assistance with the FLAME code and answering the author's numerous questions. Finally, the authors wish to thank A. Jeff Sondrup, EG&G Idaho, Inc., for his careful review of the draft report and Tony R. Moser, EG&G Idaho, Inc., for his assistance with the report graphics. The quality of the report was greatly improved by their contributions.

REFERENCES

1. Abeele, W.V., Hydraulic Testing of Bandelier Tuff, LA-10037-MS, Los Alamos National Laboratory, Los Alamos, NM (1984).
2. Hills, R.G. and P.J. Wierenga, Model Validation at the Las Cruces Trench Site, NUREG/CR-5716, Department of Soil and Water Science, University of Arizona, Tucson, AZ (1991).
3. Hills, R.G., P.J. Wierenga and D.B. Hudson, "The Second Las Cruces Trench Experiment: Results and Two-Dimensional Flow Predictions", *Water Resources Research*, 47, 2707-2718 (1991).
4. Haverkamp, R., M. Vanclim, J. Touma, P.J. Wierenga, and G. Vachaud, "A Comparison of Numerical Simulation Models for One-Dimensional Infiltration", *Soil Sci. Soc. Am. J.*, 41, 285-294 (1977).
5. INTERA Technologies, Inc., Comparison of Unsaturated Flow and Transport Models with Volume and Nitrate Measurements from a Pilot-Scale, In-Situ Lysimeter With Different Geometry Low Level Radioactive Waste Designs, Austin, TX (1989).
6. Polzer, W.L., H.R. Fuentes, E.P. Springer and J.W. Nyhan, Modeling Study of Solute Transport in the Unsaturated Zone, LA-10730-MS, Los Alamos National Laboratory, Los Alamos, NM (1986).
7. Wierenga, P.J., A.F. Toorman, D.B. Hudson, J. Vinson, M. Nash and R.G. Hills, Soil Physical Properties at the Las Cruces Trench Site, NUREG/CR-5441, Department of Soil and Water Science, University of Arizona, Tucson, AZ (1989),
8. Wierenga, P.J., D.B. Hudson, R.G. Hills, I. Porro, M.R. Kirkland and J. Vinson, Flow and Transport at the Las Cruces Trench Site, Experiments 1 and 2, NUREG/CR-5607, Department of Soil and Water Science, University of Arizona, Tucson, AZ (1990).

END

DATE
FILMED

10/28/92