ANL-AMD-TM--235
RECEIVED
MAIL DE93 006407

FLEXIBLE CUBIC SPLINE INTERPOLATION

by

I. K. Abu-Shumays

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

ARGONNE NATIONAL LABORATORY
9700 S. Cass Avenue
Argonne, Illinois 60439

Operated by
The University of Chicago under
Contract W-31-109-Eng-38
for the U. S. Atomic Energy Commission

MAST

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

ARGONNE NATIONAL LABORATORY
Argonne, Illinois 60439
Applied Mathematics Division

FLEXIBLE CUBIC SPLINE INTERPOLATION

I. K. Abu-Shumays

March 1972

Technical Memorandum No. 235

Work performed under the auspices of the U.S. Atomic Energy Commission.

TABLE OF CONTENTS

	<u>Page</u>
ABSTRACT.	5
I. INTRODUCTION.	5
II. METHOD OF INTERPOLATION	7
III. APPLICATION OF PROGRAM.	15
IV. CUBIC SPLINE INTERPOLATION OF $X \log(1/X)$	19
ACKNOWLEDGEMENTS.	24
REFERENCES.	25
APPENDIX A.	27

LIST OF TABLES

<u>No.</u>	<u>Title</u>	<u>Page</u>
I.	Accuracy of Cubic Spline Interpolation of $x \log(1/x)$. First Derivatives at $X(2)$ and $X(N+1)$ Given.	20
II.	Approximation of the Integral (34) by the Area under the Curve of the Cubic Spline Interpolant. Boundary Conditions Eqs. (27) and (29) used. Exact Value = 0.000882404601. . . .	22
III.	Approximation of the Integrals (35a,b).	23

FLEXIBLE CUBIC SPLINE INTERPOLATION

by

I. K. Abu-Shumays

ABSTRACT

This report describes a simple, efficient, and flexible program for cubic spline interpolation in one dimension, suitable for inclusion in the ANL Subroutine Library and in an interactive timesharing system. Most of the cubic spline programs already available either restrict the boundary conditions to knowledge of the first derivative at both end points, or require the second derivatives to vanish at these points. The program described here removes these restrictions and enables the user to adopt boundary conditions appropriate for his own problem. The advantage is demonstrated for the extreme case of interpolating the function $x \log (1/x)$, which has singularities in all its derivatives at $x = 0$.

I. INTRODUCTION

Spline functions have found widespread applications for interpolations, curve plotting, smoothing of experimental data, approximations of functions, numerical approximations of solutions of differential equations, and numerical estimation of definite integrals [1-6,8,9]. The reader is referred to Sard and Weintraub [9] for an extensive bibliography on the theory and applications of spline functions. The author had occasion to use splines in connection with reactor mathematics problems (work in progress). Several cubic spline programs have been used as an aid in evaluating neutron cross-section data over a wide energy range [6, Chap. 9]; the complexity of the underlying physical laws attest to the power of cubic spline methods [1].

Piecewise polynomials prove very useful for interpolation. A spline of degree m is the special case of a piecewise polynomial of degree m where, to guarantee more smoothness, the polynomial pieces are joined at each "knot" such that the first $(m-1)$ derivatives are continuous over the whole interval under consideration. A spline $s(x)$ of degree $m = 2k-1$ is the only interpolating function that has the property that if its derivatives satisfy the conditions

$$s^{(k)}(x) = s^{(k+1)}(x) = \dots = s^{(2k-2)}(x) = 0 \quad (1)$$

at the end points, say $x = x_1, x_{n+1}$, then it minimizes the integral

$$\int_{x_1}^{x_{n+1}} [s^{(k)}(x)]^2 dx. \quad (2)$$

Conditions (1) are too restrictive and may prove inappropriate for many interpolation problems. The remainder of this treatment is confined to cubic splines, i.e., to piecewise cubic polynomials which are continuous and have continuous first and second derivatives at the knots. The program SMOOTH [4,8], which is part of the ANL Subroutine Library, is devoted to the case (1) and (2) with $m = k = 2$; i.e., the second derivative of the cubic spline is required to vanish at the end points

$$s''(x_1) = s''(x_{n+1}) = 0. \quad (3)$$

Under these conditions (3), the cubic spline minimizes

$$\int_{x_1}^{x_{n+1}} [s''(x)]^2 dx. \quad (4)$$

In general, the second derivative of a function need not vanish at the boundary and conditions (3) need not be satisfied (see Section IV below). In fact, A. R. Curtis [6, Chap. 4] suggests rejecting the conditions (3) since, for uniform mesh spacing h , they lead to errors $O(h^2)$ instead of $O(h^4)$, which is theoretically possible near the ends of the range. The algorithm given here enables the user to select, from a variety of possible choices, the boundary conditions most appropriate to his problem.

The computations given in this paper were also reproduced using cubic Hermite interpolation in place of cubic spline. Equally good results were obtained for uniform mesh spacings. The advantage of the cubic spline interpolation became apparent whenever a more appropriate choice of mesh spacing for each application was made (for example, when a fine mesh close to a singularity and a course mesh elsewhere were chosen).

The following section is devoted to a derivation of the algorithm and of suitable boundary conditions. The reader whose main interest is in the use of the program may proceed to Section III below.

II. METHOD OF INTERPOLATION

Let $x_i, y_i, i = 1, \dots, n+1$, be a given set of corresponding coordinates (knots and function values or data) arranged such that

$$x_1 < x_2 < \dots < x_n < x_{n+1}. \quad (5)$$

Then, a suitable representation of a cubic spline for the data on the interval $[x_1, x_{n+1}]$ (see [2,3,5,6,9] for other formulations) is

$$f(x) = a_i + b_i(x-x_i) + c_i(x-x_i)^2 + d_i(x-x_i)^3, \quad (6)$$

$$x_i \leq x \leq x_{i+1}, \quad i = 1, \dots, n,$$

where the requirements of interpolation $f(x_i) = y_i$ imply

$$a_i = f(x_i) \equiv f_i = y_i, \quad i = 1, \dots, n, \quad (7)^*$$

$$a_i + b_i h_i + c_i h_i^2 + d_i h_i^3 = f_{i+1} = y_{i+1}, \quad h_i = x_{i+1} - x_i, \quad (8)$$

$$i = 1, \dots, n,$$

and where continuity of the first and second derivatives of (6) at interior knots x_i require

$$b_i + 2c_i h_i + 3d_i h_i^2 = b_{i+1}, \quad i = 1, \dots, n-1, \quad (9)$$

$$2c_i + 6d_i h_i = 2c_{i+1}, \quad i = 1, \dots, n-1. \quad (10)$$

The spline representation (6) has $4n$ coefficients a_i, b_i, c_i, d_i , $i = 1, \dots, n$, while Eqs. (7)-(10) supply only $4n-2$ relations between these coefficients. Therefore, two additional independent relations, or so called boundary conditions, are needed in order to determine the coefficients of (6) and to get a unique cubic spline interpolation function. Flexibility is achieved in the program developed here (see Appendix A for a listing) by enabling the user to select two relations

*Henceforth f_i and y_i will be used interchangeably.

or boundary conditions, or to experiment with the various choices and determine those conditions suitable for his own application.

We shall give only a sample of boundary conditions which are very likely to occur; the user may wish to derive others. If, for example, the first derivative f'_1 , the second derivative f''_1 , or the area under the curve in the first interval

$$AL = \int_{x_1}^{x_2} f(x) dx$$

is given, then the corresponding left-boundary conditions would be

$$b_1 = f'_1, \quad (11L)$$

$$c_1 = f''_1/2, \quad (12L)$$

or

$$a_1 h_1 + b_1 h_1^2/2 + c_1 h_1^3/3 + d_1 h_1^4/4 = AL, \quad h_1 = x_2 - x_1, \quad (13L)$$

respectively. These relations (11L)-(13L) follow directly from Eq. (6). Similarly, the corresponding relations for the right boundary are

$$b_n + 2c_n h_n + 3d_n h_n^2 = f'_{n+1}, \quad h_n = x_{n+1} - x_n, \quad (11R)$$

$$2c_n h_n + 6d_n h_n^2 = f''_{n+1}, \quad (12R)$$

or

$$a_n h_n + b_n h_n^2/2 + c_n h_n^3/3 + d_n h_n^4/4 = AR, \quad (13R)$$

where

$$AR = \int_{x_n}^{x_{n+1}} f(x) dx$$

stands for the area under the curve in the last interval. Only two of the above conditions (11L)-(13R) are needed to define a spline.

The program below computes and returns the coefficients a_i , b_i , c_i , and d_i for the spline representation (6). The coefficients a_i are given by Eq. (7). It is convenient to solve Eqs. (7)-(10) for either d_i and b_i or d_i and c_i in terms of the function values f_i and the remaining coefficients; we shall choose to solve for d_i and b_i . Equations (10) yield

$$d_i = (c_{i+1} - c_i)/3h_i, \quad i = 1, \dots, n-1. \quad (14a)$$

Equations (7), (8), and (14a) yield

$$b_i = (f_{i+1} - f_i)/h_i - c_i h_i - d_i h_i^2, \quad i = 1, \dots, n, \quad (15a)$$

$$b_i = (f_{i+1} - f_i)/h_i - h_i c_{i+1}/3 - 2h_i c_i/3, \quad i = 1, \dots, n-1. \quad (15b)$$

Equations (9), (14a), and (15b) yield

$$b_n = h_{n-1} c_{n-1}/3 + 2h_{n-1} c_n/3 + (f_n - f_{n-1})/h_{n-1}, \quad (15c)$$

and Eqs. (7), (8), and (15c) yield

$$h_{nn}^2 d_{nn} = (f_{n+1} - f_n)/h_n - (f_n - f_{n-1})/h_{n-1} - h_{n-1}c_{n-1}/3 - 2h_{n-1}c_n/3 - h_n c_n. \quad (14b)$$

Now, substituting (14a) and (15b) in the first $n-2$ equations of (9) and rearranging terms, we obtain the system

$$\frac{1}{3}h_1 c_1 + \frac{2}{3}(h_1 + h_{1+1})c_{1+1} + \frac{1}{3}h_{1+1}c_{1+2} = (f_{1+2} - f_{1+1})/h_{1+1} - (f_{1+1} - f_1)/h_1, \\ i = 1, \dots, n-2. \quad (16)$$

The system (16) has $n-2$ equations in n unknowns; the remaining two equations needed in order to determine the coefficients c_i can be deduced from the boundary conditions (11L)-(13R). For the left boundary, if Eq. (11L) corresponding to the first derivative is used, then (15b) for $i = 1$ yields, upon rearranging terms,

$$\frac{2}{3}h_1 c_1 + \frac{1}{3}h_1 c_2 = (f_2 - f_1)/h_1 - f'_1. \quad (17a)$$

Equation (12L) corresponding to the second derivative is already in the desirable form

$$c_1 = f''_1/2. \quad (17b)$$

If Eq. (13L) corresponding to the area under the curve in the first interval AL is used, then substituting for a_1 , b_1 , and d_1 in (13L) their expression given by (7), (15b), and (10) yields, upon rearranging terms and dividing by $h_1^2/4$,

$$\boxed{\frac{1}{3}h_1c_1 + \frac{1}{3}h_1c_2 = 2(f_1+f_2)/h_1 - 4AL/h_1^2} \quad (17c)$$

Similarly, for the right boundary, if the first derivative (11R) is used, then substituting (14b) and (15c) in (11R) yields

$$\boxed{\frac{1}{3}h_{n-1}c_{n-1} + (\frac{2}{3}h_{n-1} + \frac{1}{2}h_n)c_n = \frac{3}{2}(f_{n+1}-f_n)/h_n - (f_n-f_{n-1})/h_{n-1} - \frac{1}{2}f'_{n+1}} \quad (18a)$$

If (12R) corresponding to the second derivative is used, then utilizing (14b) leads to

$$\boxed{\frac{1}{3}h_{n-1}c_{n-1} + \frac{2}{3}(h_{n-1}+h_n)c_n = -(f_n-f_{n-1})/h_{n-1} + (f_{n+1}-f_n)/h_n - f''_{n+1}/6} \quad (18b)$$

and if (13R) corresponding to the area under the curve is used, then

$$\boxed{\begin{aligned} &\frac{1}{3}h_{n-1}c_{n-1} + (\frac{2}{3}h_{n-1} + \frac{1}{3}h_n)c_n \\ &= 4AR/h_n^2 - (f_n-f_{n-1})/h_{n-1} - (f_{n+1}+3f_n)/h_n \end{aligned}} \quad (18c)$$

Observe now that when any two of the equations (17a,b,c) and (18a,b,c) are adjoined to the system (16), the new system can then be solved and leads to a unique spline representation (6) satisfying the boundary conditions chosen.

The reader should note that the program given below does not treat the case in which two conditions are chosen at one of the boundaries and none at the other. In this case, the spline may be constructed by writing program statements based on Eq. (16). Specifically,

(a) If any two of Eqs. (17a,b,c) are chosen, then these equations can be solved for c_1 and c_2 and the system (16), viewed as a recurrence relation, yields the rest of the c_i 's. The remaining coefficients for the spline representation (6) follow from (7), (14a,b), and (15b,c).

(b) Similarly, if two of Eqs. (18a,b,c) are selected, then these equations can be solved for c_n and c_{n-1} and again (16) can be used to solve for $c_{n-2}, c_{n-3}, \dots, c_1$. The remaining coefficients in the representation (6) can then be computed using (7), (14a,b), and (15b,c).

We stress here that (16), viewed as a system of difference equations, can be shown to be numerically unstable [6, pp. 410ff]. The reader is advised to program in double precision in order to avoid the anticipated accumulation of roundoff errors, and in multiple precision if the number of points turns out to be large. Detailed analysis of this situation and alternate approaches will be treated elsewhere.

Let only one of the left boundary conditions (17a,b,c) and only one of the right boundary conditions (18a,b,c) be chosen. Then adjoining such a choice to Eq. (16) leads to a system of n -equations in n unknowns which has the matrix representation

$$Q\mathbf{c} = \mathbf{e}. \quad (19)$$

Here Q is a real tridiagonal matrix, $\mathbf{c} = (c_1, c_2, \dots, c_n)^T$, and $\mathbf{e}$ is a vector whose elements are the right-hand sides of (16) and of the two equations chosen among (17a,b,c) and (18a,b,c). Note from Eqs. (16)-(18) that the real matrix Q of Eq. (19) is either symmetric, strictly diagonally dominant with positive diagonal entries and therefore positive definite [10], or can be made so by a simple manipulation. If the first derivative (17a) is chosen for the left boundary and any of the conditions (18a,b,c) is chosen for the right boundary, then Q is already in the desired form. If the second derivative (17b) is chosen, then $c_1 = f''/2$ is no longer an unknown; the matrix equation (19) can then be reduced (by discarding the first row and first column of Q , the first element of $\mathbf{c}$, and the first element of $\mathbf{e}$ and by modifying the second element of $\mathbf{e}$) to represent a system of $(n-1)$ equations in the $(n-1)$ remaining unknowns $c_2, \dots, c_n$. The coefficient matrix of the reduced system of equations is indeed tridiagonal, symmetric, and positive definite. These properties of the coefficient matrix will also be satisfied if the area under the curve in the first interval is chosen, provided that the unknown c_1 in Eqs. (17c) and (16) is transformed to $\bar{c}_1 = c_1/2$ and the resulting expression for (17c) is multiplied by a factor of two. We conclude from the above and from Ref. [10] that Eq. (19) can be solved extremely rapidly for the c_i 's by Gaussian elimination and that this method is numerically stable. The program given below does this and solves for the remaining coefficients a_i, b_i, d_i according to (7), (15b,c), and (14a,b).

The user may wish to derive other boundary conditions. For example, he may wish to match the whole area under the curve, the first or second derivative at any interior point, etc. The procedure is to derive a relation among either the coefficients c_1 and c_2 or c_{n-1}, c_n , to correspond to the desired boundary condition. Equations (17a,b,c), (18a,b,c) provide special examples. As an additional example, if the first derivative is given at x_2 , then from (6)

$$b_1 + 2c_1h_1 + 3d_1h_1^2 = f'_2. \quad (20)$$

Now, eliminating b_1 and d_1 from Eqs. (15b), (14a) for $i = 1$, and Eq. (20), rearranging terms and using $a_1 = f_1$, we obtain the result

$$c_1 + 2c_2 = 3f'_2/h_1 - 3(f_2 - f_1)/h_1^2. \quad (21)$$

Equations similar to (21) can also be derived to satisfy any other suitable boundary condition--their enumeration is eliminated for brevity.

III. APPLICATION OF PROGRAM

The program described is subroutine SPLINE of Appendix A. It is in double precision and can be called by the FORTRAN statement

$$\text{CALL SPLINE (X,Y,BC,N,A,B,C,D)} \quad (22)$$

where

X, Y = user-supplied arrays of abscissas $\{x_i\}$ and corresponding function values $\{y_i\}$. The components of the array X must be strictly increasing;
 BC = user-supplied array of boundary conditions (see details below);
 N = number of subdivision ($N+1$ = number of data points);
 A, B, C, D = arrays of coefficients $\{a_i, b_i, c_i, d_i\}$ of the spline representation Eq. (6), computed by subroutine SPLINE.

The array BC of boundary conditions should have a dimension of 6 or more. The user may choose any set of dimensions for the remaining arrays in (22), consistent with his choice of $N+1$ data points.

As mentioned in the paragraph following Eq. (18c) above, the program SPLINE does not apply if two boundary conditions are available for one boundary and none for the other. The boundary conditions accepted by subroutine SPLINE are to be viewed as the two relations

$$BC(1)C(1) + BC(2)C(2) = BC(3), \quad (23)$$

and

$$BC(4)C(N-1) + BC(5)C(N) = BC(6). \quad (24)$$

These relations correspond to any one of Eqs. (17a,b,c), (21) and any one of Eqs. (18a,b,c), or any of their equivalents derived by

the user. In order to make this section self-sufficient we note the following choices for the left boundary conditions.

a) If the first derivative f'_1 is given at x_1 , then from (17a) and (23)

$$BC(1) = 2h_1/3, \quad BC(2) = h_1/3, \quad (25a,b)$$

$$BC(3) = (f_2 - f_1)/h_1 - f'_1, \quad h_1 = x_2 - x_1. \quad (25c)$$

b) If the second derivative f''_1 is given at x_1 , then from (17b) and (23)

$$BC(1) = 1, \quad BC(2) = 0, \quad BC(3) = f''_1/2. \quad (26a,b,c)$$

c) If the area AL under the curve in the first interval is given, then from (17c) and (23)

$$BC(1) = BC(2) = h_1/3, \quad (27a,b)$$

$$BC(3) = 2(f_1 + f_2)/h_1 - 4AL/h_1^2. \quad (27c)$$

d) If the first derivative f'_2 is given at the second point x_2 , then from (21) and (23)

$$BC(1) = 1, \quad BC(2) = 2, \quad (28a,b)$$

$$BC(3) = 3f'_2/h_1 - 3(f_2 - f_1)/h_1^2. \quad (28c)$$

Similarly, we note the following choices for the right boundary conditions.

a) If the first derivative f'_{n+1} is given at x_{n+1} , then from (18a) and (24)

$$BC(4) = h_{n-1}/3, \quad h_{n-1} = x_n - x_{n-1}, \quad (29a)$$

$$BC(5) = 2h_{n-1}/3 + h_n/2, \quad h_n = x_{n+1} - x_n, \quad (29b)$$

$$BC(6) = 3(f_{n+1} - f_n)/2h_n - (f_n - f_{n-1})/h_{n-1} - f'_{n+1}/2. \quad (29c)$$

b) If the second derivative f''_{n+1} is given at x_{n+1} , then from (18b) and (24)

$$BC(4) = h_{n-1}/3, \quad BC(5) = \frac{2}{3}(h_{n-1} + h_n), \quad (30a,b)$$

$$BC(6) = -(f_n - f_{n-1})/h_{n-1} + (f_{n+1} - f_n)/h_n - f''_{n+1}/6. \quad (30c)$$

c) If the area AR under the curve in the last interval is given, then from (18c) and (24)

$$BC(4) = h_{n-1}/3, \quad BC(5) = \frac{2}{3}h_{n-1} + \frac{1}{3}h_n, \quad (31a,b)$$

$$BC(6) = 4AR/h_n^2 - (f_n - f_{n-1})/h_{n-1} - (f_{n+1} + 3f_n)/h_n. \quad (31c)$$

To summarize the application of subroutine SPLINE, the user has to construct the arrays of coordinates X,Y, the array BC according to one choice among (25)-(28) and one choice among (29)-(31), and then call the subroutine in his main program as is indicated in the statement (22).

IV. CUBIC SPLINE INTERPOLATION OF $X \log(1/X)$

Although cubic spline interpolation of logarithmic functions may not be appropriate, especially in the neighborhood of the singularity, the present example is selected to illustrate the need for flexibility in adapting boundary conditions such as is provided by subroutine SPLINE. Flexibility in the choice of mesh spacing is also vital and enables the user to gain more accuracy by adopting a fine mesh near the points which are likely to cause trouble (such as $x = 0$ in the present example) and a coarse mesh in the regions where the function is expected to be very smooth.

For illustration, results for the special interval $x \in [0, 0.02]$ will be summarized. Initially this interval was divided into $N = 10, 20, 40$, and 80 equal parts $DX = 0.02/N$ and the ANL Library subroutine SMOOTH was used to construct corresponding spline interpolations for

$$f(x) = x \log(1/x). \quad (32)$$

The arrays X and Y in this case are

$$X(1) = 0, \quad Y(1) = 0, \quad (33a)$$

and, for $I = 2, \dots, N+1$,

$$X(I) = (I-1)*DX, Y(I) = X(I)*DLOG(1/X(I)). \quad (33b)$$

As expected, the results were unchanged when the subroutine SMOOTH was replaced by the subroutine SPLINE with the requirement that the second derivative of the interpolating spline should vanish at the end points $x = 0$ and $x = 0.02$. This requirement is obviously unrealistic since the second derivative $f''(x)$ of (32) vanishes at $x = 0$ and is -50.0 at $x = 0.02$; indeed, the results were poor in the neighborhood of these end points. General improvement of between 1 to 5 additional significant figures was achieved when more realistic boundary conditions derived from Eqs. (25), (27)-(32) were implemented. Table I indicates

Table I. Accuracy of Cubic Spline Interpolation of $x \log(1/x)$.
First Derivatives at $X(2)$ and $X(N+1)$ Given.

Subinterval N	0-.004	.004-.008	.008-.012	.012-.016	.016-.02
10	2-5 S.F. ^a	6-7 S.F.	6-7 S.F.	7 S.F.	7-8 S.F.
20	2-6 S.F.	7-8 S.F.	7-8 S.F.	8 S.F.	8-9 S.F.
40	2-8 S.F.	8-9 S.F.	9 S.F.	9 S.F.	10 S.F.
80	2-9 S.F.	9-10 S.F.	10 S.F.	10-11 S.F.	11 S.F.

^aThese figures 2-5 S.F. indicate that the accuracy was to 2 significant figures or better near the beginning, $x=0$, and improved to 5 significant figures or better near the end, $x=.004$, of the subinterval $[0,.004]$ --and so on. Note that machine accuracy was achieved at the points of interpolation $X(I)$.

the accuracy of the interpolating spline in each of five subregions when Eqs. (28a,b,c) and (29a,b,c) for the exact value of the first derivative $f'(x) = \log(1/x) - 1$ at the second point $X(2) = DX$ and at the last point $X(N+1) = 0.02$ were used as boundary conditions.

Results comparable, though slightly inferior, to those in Table I were achieved when the left boundary condition (28a,b,c) was replaced by (27a,b,c), corresponding to knowledge of the area under the curve in the first interval. As one might expect this latter choice of boundary conditions (27a,b,c) gave slightly better results than (28a,b,c) for estimating the integral*

$$\int_0^{0.02} x \log(1/x) dx = 0.000882404601 \quad (34)$$

by the area under the cubic spline interpolant of $x \log(1/x)$. Table II lists a few results for approximating (34) and, *more importantly*, indicates the improvement that can be achieved by varying the mesh spacing. Three mesh spacings were considered: (a) uniform mesh spacing, (b) slightly increasing mesh spacing $\Delta x_{i+1} = (1.1)\Delta x_i$, and (c) more rapidly increasing mesh spacing $x_{i+1} = i^2 h_1$, $h_1 = x_2 - x_1$. Table II indicates clearly that the best results are achieved when a relatively fine mesh is selected near $x=0$ where the interpolation is expected to be least accurate (see also Table I).

* In practice, when exact boundary conditions are not known, the user may wish to estimate the first derivative, or the area under the curve in the first or last interval, etc. The best choice would vary depending on the actual data and the application sought.

Table II. Approximation of the Integral (34) by the Area under the Curve of the Cubic Spline Interpolant. Boundary Conditions Eqs. (27) and (29) used. Exact Value = 0.000882404601.

Mesh N	Uniform	$\Delta x_{i+1} = (1.1)\Delta x_i$	$x_{i+1} = i^2 h_1$
10	.00088238	.00088239	.000882409
20	.000882398	.0008824038	.0009924050
40	.000882403	.00088240464	.00088240464
80	.000882402	.00088240465	.000882404604

Another possible application of the cubic spline interpolations is to approximate integrals of the form $\int f(x)g(x)dx$. Such approximations are meaningful whenever the integrations $\int g(x)x^l dx$, $l = 0,1,2,3$, can be carried out analytically and $f(x)$ can be well approximated by a spline. As an illustration, the cubic spline interpolation of $x \log(1/x)$ was used in order to approximate the integrals

$$E_1 \equiv \int_0^{0.02} x \log(1/x) E_1(x) dx, \quad (35a,b)$$

$$E_2 \equiv \int_0^{0.02} x \log(1/x) E_2(x) dx,$$

where E_1, E_2 are the exponential integrals

$$E_n(x) = \int_0^1 e^{-x/u} u^{n-2} du, \quad n = 1, 2. \quad (36)$$

Table III lists the results when $x \log(1/x)$ is approximated by the cubic spline interpolation corresponding to a uniform mesh spacing and boundary conditions Eqs. (27) and (29), and the remaining integrals of $x^l E_n(x)$ in (35) are carried out analytically. Note from this table that for E2 there is an improvement as N increases from 10 to 40 and an indication of a deterioration for the larger $N = 80$.

TABLE III. Approximation of the integrals (35a,b)^a

N	E1	E2
10	.0034449	.00082915
20	.00344506	.000829171
40	.00344511	.000829176
80	.003445129	.000829182
Exact	.003445131	.000829177

^aSee text.

Two remarks are appropriate here. First, in general, for spline approximations and for their applications one expects the results to improve as the number of subdivisions N increases up to a certain value; beyond such a value the results either start to fluctuate around some value or to deteriorate (due to errors introduced in solving the larger systems of linear equations by the subroutine SPLINE and/or due to other round-off errors). Second, one should not expect that a choice of mesh spacing which yields excellent results for a particular application of the subroutine should necessarily be appropriate for other applications. For example, when Table III was

reproduced for the mesh spacings corresponding to columns three and four of Table II, the results were much inferior to those given in Table III.

The subroutine SPLINE is currently being incorporated into the Argonne National Laboratory ANL Subroutine Library. The author intends to issue an interactive DISCOM version of the subroutine for RESCUE users. He also intends to evaluate the need to expand this subroutine to include smoothing of experimental data. Therefore any feedback as to experience in application of the program to real physical problems would be most helpful.

ACKNOWLEDGEMENTS

The author is grateful for valuable discussions with E. H. Bareiss, G. Birkhoff, W. J. Cody, and T. Ginsberg. This report resulted from the continued help and encouragement of W. J. Cody. Dr. Ginsberg has applied SPLINE, with success, to actual data for an environmental problem. Thanks are also due to Diane E. Neal for her careful editing of the report and to Doris I. Haight and Judy Beumer for their careful preparation of the manuscript.

REFERENCES

1. G. Birkhoff and C. R. De Boor, "Piecewise Polynomial Interpolation," in *Approximation of Functions*, H. L. Garabedian, Editor, Elsevier, Amsterdam 1965.
2. C. De Boor, "Spline Package for Calculating with B-Splines," Los Alamos Scientific Laboratory Report LA-4728-MS, 1971.
3. C. De Boor and J. R. Rice, "Least Squares Cubic Spline Approximation," Parts I and II, Purdue University Computer Science Departments Reports CSD TR 20 and CSD TR 21, 1968.
4. B. S. Barbow, "SMOOTH, Smoothing by Cubic Splines," Argonne National Laboratory System/360 Library Subroutine ANL E350S, 1968.
5. T. N. E. Greville, *Theory and Applications of Spline Functions*, Academic Press, New York, 1969.
6. J. G. Hayes, Editor, *Numerical Approximation of Functions and Data*, The Athlone Press (1970).
7. E. Isaacson and H. B. Keller, *Analysis of Numerical Methods*, J. Wiley and Sons, Inc., New York, 1966.
8. C. H. Reinsch, "Smoothing by Spline Functions," *Numer. Math.* 10, 177-183 (1967).
9. A. Sard and S. Weintraub, *A Book of Splines*, J. Wiley and Sons, Inc., New York, 1971.
10. J. H. Wilkinson, *The Algebraic Eigenvalue Problem*, Clarendon Press, Oxford, 1965.

APPENDIX A

FORTRAN IV DOUBLE PRECISION CUBIC SPLINE INTERPOLATION
SUBROUTINE

```

      SUBROUTINE SPLINE(X,Y,BC,N,A,B,C,D)
C
C      CUBIC SPLINE INTERPOLATION
C      X(I) ARE STRICTLY INCREASING
C
C      BOUNDARY CONDITIONS SHOULD BE SUPPLIED BY THE USER
C
      IMPLICIT REAL*8 (A-H,O-Z)
      DIMENSION X(1),Y(1),BC(1),A(1),B(1),C(1),D(1)
C
      NM1=N-1
      H=X(2)-X(1)
      F=(Y(2)-Y(1))/H
      B(1) =BC(1)
      A(1) =BC(2)/B(1)
      D(1) =BC(3)/B(1)
      C(1) =H/3.0D0
      DO 10 I=2,NM1
      G=H
      H=X(I+1)-X(I)
      E=F
      F=(Y(I+1)-Y(I))/H
      B(I)= 2.0D0*(G+H)/3.0D0-C(I-1)*A(I-1)
      C(I) =H/3.0D0
      D(I)=(F-E -C(I-1)*D(I-1))/B(I)
10  A(I) =C(I)/B(I)
      C(N) =(BC(6)-BC(4)*D(NM1))/(BC(5)-BC(4)*A(NM1))
      DO 20 I=1,NM1
      J =N-I
20  C(J)=D(J)-A(J)*C(J+1)
      DO 30 I=1,NM1
      A(I)=Y(I)
      H=X(I+1)-X(I)
      D(I)=(C(I+1)-C(I))/(3.0*H)
30  B(I)=(Y(I+1)-Y(I))/H-(H*D(I)+C(I))*H
      A(N)=Y(N)
      B(N)=B(NM1)+2.0D0*H*C(NM1)+3.0D0*H*H*D(NM1)
      H=X(N+1)-X(N)
      D(N)=(((Y(N+1)-Y(N))/H-B(N))/H-C(N))/H
      RETURN
      END

```

END

**DATE
FILMED**

3 / 17 / 93