DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

This report has been reproduced directly from the best available copy.

Available to DOE and DOE contractors from the Office of Scientific and Technical Information, P.O. Box 62, Oak Ridge, TN 37831; prices available from (615)576-8401.

Available to the public from the National Technical Information Service, U. S. Department of Commerce, 5285 Port Royal Rd., Springfield, VA 22161.

FINAL REPORT

Contract DE-FG22-89PC89782

on

**SELENIUM TRANSFORMATION IN COAL MINE SPOILS:
ITS ENVIRONMENTAL IMPACT ASSESSMENT**

to

**Mr. Jerry Harness
U.S. Department of Energy
Morgantown Energy Technology Center
Morgantown, W.V. 26507-0880**

December 31, 1991

by

Asmare Atalay, K.J. Koll, H. Zhang, and D. Maggon

**University of Oklahoma
Civil Engineering and Environmental Science
202 W. Boyd St., Room 334
Norman, O.K. 73019**

TABLE OF CONTENTS

Section	Title	Page
	EXECUTIVE SUMMARY.....	1
I	Introduction.....	3
	A. Objective	
	B. Background	
	C. Scope	
II	TECHNICAL LITERATURE REVIEW.....	7
	A. INTRODUCTION.....	7
	B. SOURCES OF SELENIUM IN NATURE.....	8
	1. Soils and Rocks	
	2. Plants	
	3. Other Natural Sources in the Environment	
	4. Anthropogenic Sources	
	5. Cycle of Selenium in Nature	
	C. SELENIUM TRANSFORMATION IN NATURE.....	16
	1. Biological	
	2. Chemical	
	D. USES OF SELENIUM COMPOUNDS.....	19
	E. SELENIUM FROM COAL MINES AND SPOILS.....	21
	1. Selenium Solubility	
	2. Speciation of Selenium	
	3. Selenium and Sulfur	
	F. HEALTH IMPACTS OF SELENIUM.....	38
	1. In Humans	
	2. In Aquatic Animals	
	3. In Plant and Farm Animals	
	G. REGULATIONS ON SELENIUM POLLUTION.....	53
	1. Drinking Water Standards	
	2. Surface Water Standards	
	3. Ambient Water Criteria	
	4. Effluent Standards	
	5. Industrial Effluent Limitation and Guidelines	
	6. Hazard Threshold Level	

	7. Recommended Dietary Allowance	
III.	SITE SELECTION AND EQUIPMENT SETUP.....	62
	A. LYSIMETER SETUP.....	67
	1. Construction of the Eh Electrode	
	2. Eh, pH, Temperature, Water, and Air Measurement	
	3. Sampling Spoils	
	B. DATA COLLECTION.....	74
IV.	GROUNDWATER AND SOIL SAMPLING.....	76
	1. Groundwater	
	2. Soil	
	3. Problems Encountered	
V.	SAMPLE PREPARATION AND ANALYSIS.....	78
	1. Digestion of of Water, Spoil, and Soil Samples	
	2. Atomic Absorption Procedure for Total Selenium Analysis	
	3. Ion Chromatography for Selenite and Selenate Analysis	
VI.	SELENIUM TRANSFORMATION STUDY.....	85
VII.	RESULTS AND DISCUSSION.....	94
	A. SELENIUM IMPACT ASSESSMENT STUDY.....	94
	1. Outline of Selenium Impact Procedure	
	2. Defining Impact Boundaries	
	3. Soil Impact Calculation	
	4. Surface Water Impact Calculations	
	a. Streams	
	b. Rivers	
	5. Lakes and Impoundments	
	B. GROUNDWATER IMPACT CALCULATION.....	110
	C. SELENIUM IN OKLAHOMA GROUNDWATER AND SOIL.....	111
	1. Selenium Entry to Aquatic Systems	
	2. Speciation of Selenium in Oklahoma's Rural Groundwater	

3.	Distribution of Total Selenium in Groundwater	
4.	Relating Selenium level to Principal Aquifers and Geology in Oklahoma	
5.	pH and Selenium Content in Groundwater	
6.	Relationships Between Selenium and Depth to Groundwater	
D.	SELENIUM IN COAL MINE SPOILS.....	136
1.	Factors that Affect Selenium Accumulation	
2.	Selenium in Active vs. Abandoned Mine Spoils	
3.	Copper Deposits and Selenium Content	
VIII.	SUMMARY, CONCLUSIONS AND RECOMMENDATIONS.....	156
A.	Summary and Conclusion	
B.	Recommendations	
	REFERENCES.....	160

APPENDIX

A.	DATA FROM FIELD LEASUREMENT.....
B.	QUALITY ASSURANCE/QUALITY CONTROL.....
1..	Introduction
2.	Field Data Collection
a.	Sampling Frequency
b.	Sample Collection
c.	Documentation
3.	Analytical Methods
a.	Instrument Calibration
b.	Sample Identification
c.	Data collection and Storage
4.	Corrective Actions
a.	Data Accuracy
b.	Data Precision

LIST OF FIGURES

Figure	Title	Page
1	Possible Cycle of Selenium under field Conditions.....	17
2.	Some Selenate Minerals Solubilities.....	26
3.	Some Selenite Minerals Solubilities.....	27
4.	Solubilities of Selenide Minerals and Elemental Selenium.....	28
5.	The Relationship Among Selenium Species, pH, and Eh.....	30
6.	The Effect of Redox and pH on Selenium Species in Soil Solution.....	31
7.	The Effect of Redox on Solubilities of Selenate and Selenite in Natural Soils.....	33
8.	The Effect of Redox on Solubilities of Elemental Se and Selenide in Soils at pH = 7.....	34
9.	Loss of Nails in Selenium Poisoned Patients.....	40
10.	Black-necked Stilt Embryos from Eggs Collected at Kesterson Reservoir.....	47
11.	Distribution of Seleniferous Vegetation in the Western U.S.A. and Canada.....	49
12.	Location and Classification of Counties in the U.S.A. Where Plants Were Collected for Selenium Analysis.....	50
13.	Selenium Level in Forage Crops of the U.S.A...	52
14.	Congenital Alkali Disease in 14-day Old Colt...	54
15.	The Coal Producing Areas of Northeastern Oklahoma.....	63
16.	A Road Map of Okmulgee County, Oklahoma.....	64
17.	A Map Showing the Location of the Experimental Site.....	65

(List of Figures Continued)

18.	Legal Description for the location of the Sampling Site.....	66
19.	An Illustration for the Construvtion of a Platinum Electrode.....	69
20.	An Aerial Photograph of the Study Site.....	70
21.	Diagram Showing Tensiometer Layout at the Study Site.....	72
22.	Diagram of the Jet Fill Tensiometer.....	73
23.	Ion Chromatogram Showing the Effect of 100 ppm Nitrate and 100 ppm Sulfate on the Resolution of Selenite and Selenate.....	80
24.	Ion Chromatogram Showing the Effect of 1000 ppm Sulfate on teh Resolution of 5 ppm Selenate..	81
25.	A Mini-column Assembly Used for Selenium Adsorption Study.....	85
26.	Adsorption Isotherm for Selenium Species on Coal Mine Spoil Material.....	93
27.	Postulated Pathway of Selenium from the Coal Mine Spoil to the Environment.....	95
28.	Possible Pathway of Selenium Through the Food Chain.....	96
29.	A Hypothetical Coal Mine Spoil Site Near three Towns Symbolized by A, B, C; and a River Designated by XYZ.....	98
30.	Sub-area Divisions of the Hypothetical Site.....	99
31.	Map of Oklahoma Showing the Location of Soil and Groundwater Sampling Sites.....	117
32.	An Eh-pH Diagram for the Se-H ₂ O System.....	119
33.	Relation of Oxidation-Reduction Potentials of Some Se Compounds to pH.....	120

(List of Figures Continued)

34.	Predominance Area Diagram for Se in Aqueous Systems Under Standard Conditions.....	123
35.	Distribution of Selenium in Oklahoma Soils.....	126
36.	Major Sources of Groundwater in Oklahoma.....	128
37.	Distribution of Selenium in Oklahoma Groundwater..	131
38.	An Eh-pH Diagram for the Se-H ₂ O System Enscribing Selenium Values from the Spoil Site.....	138
39.	Northeastern Oklahoma and Adjoining States Where Copper Was Mined Over 80 Years Ago.....	152

LIST OF TABLES

Table	Title	Page
1.	Selected Se Sources in Nature.....	13
2.	Uses of Some Inorganic Se Compounds.....	20
3.	Selenium Content of U.S.A. Coals.....	22
4.	Selenium in Coal Mine Spoils and Associated Materials in the Western Energy Regions of the United States.....	24
5.	Effects of Supplemental Selenium in the Diets of Keshan Disease Patients.....	44
6.	Surface Water Quality Standards for Selenium by State.....	57
7.	U.S.-EPA Industrial Effluent Guidelines for Se.	60
8.	The Effect of Adding 5 mM Barium on Selenate+Sulfate Standards.....	83
9.	Soil Media Description for the Adsorption/ Desorption Mini-Column Study.....	87
10.	Total Se levels in Selected Soil Samples taken from the Heneryetta Site.....	91
11.	Adsorption Isotherm Studies for Selenium on Soil, Sand, and Overburden.....	92
12.	Some Selected Groundwater Models.....	112
13.	Selenite Measurement in Oklahoma Groundwater.	115
14.	Standdard Energies of Formation for Some Selenium Species.....	124
15.	Selenium Concentration in Magnatic and Sedimentary Rocks.....	132
16.	pH and Depth to Groundwater for WEater from Oklahoma Counties.....	133
17.	Relation Between Se in Coal Mine Spoils and Associated Materials.....	137

EXECUTIVE SUMMARY

The objective of this program was to conduct an environmental impact assessment study for selenium from coal mine spoils. The use of in-situ lysimetry to predict selenium speciation, transformation, and mobility under natural conditions was evaluated.

The scope of the study was to construct and test field-scale lysimeter and laboratory mini-column to assess mobility and speciation of selenium in coal mine overburden and soil systems; to conduct soil and groundwater sampling throughout the state of Oklahoma for an overall environmental impact assessment of selenium; and to conduct an indepth literature review on the solubility, speciation, mobility, and toxicity of selenium from various sources.

The in-situ lysimeter was constructed and installed by graduate students who worked on the project. Components of the lysimeter were: tensiometers, Eh electrodes, and temperature and air access tubes. The site for the project was located at Henryetta, Oklahoma, where there used to be an extensive coal mining activity from late 1800 to early 1900. Between 1987 and 1989 the Oklahoma Conservation Commission has done some reclamation near the vicinity of the research site. The study site was divided into three sections: spoil, reclaimed, and control. At each section lysimeters for measuring Eh, pH, moisture, and temperature were installed in triplicates at depths of 1 ft, 3 ft, and 5 ft. Soil samples from each section were collected using a motorized auger from these three depths. Moisture readings were taken from the burried tensiometers, Eh was also measured from burried platinum electrodes, and soil pH and temperature were measured using a portable pH/temperature meter. Data were collected bi-weekly during the first three months and monthly thereafter, for a total sampling period of one year.

Groundwater and surface soil samples were also collected from each county in Oklahoma. Soils were sampleed from the top six inches of the ground after removing the grass cover. Water samples were collected from designated wells by using a submersible pump. Soil samples were kept in ziploc plastic bags whereas water samples were collected in acid-cleaned brown bottles with screw caps. Both soil and water samples were processed for total selenium, selenate, and selenite analyses.

A comprehensive environmental impact assessment model was also developed. This mathematical model could be used to predict surface and groundwater contamination with selenium from any source. The only limitation to this model was availability of input parameters.

Data collected from the lysimeter study indicated that selenium in the overburden of the abandoned mine site was mainly found in the selenite form. The amount of selenite found was too low and immobile to be of concern to the environment. The spoil had equilibrated long enough (over 50 years) that most of the soluble forms of selenium have already been lost. Examination of the overburden indicated the presence of pyrite crystals that precipitated over time. The laboratory mini-column study indicated that selenite is quite immobile and remained on the overburden material even after leaching with dilute acid. Data from groundwater samples indicated that based on the current permissible level for selenium in groundwater (0.01 mg Se/L), Oklahoma groundwater is widely contaminated with the element. However, according to the new regulation (0.05 mg Se/L), which is to be promulgated in 1992, only 9 of the 77 counties in the state exceed the limit.

Recommendations for future work include selenium impact assessment from recent or active coal mine spoils. Studies involving the microbial transformation of selenium at active mine sites will be an added advantage to understanding the behaviour of selenium in the natural environment. Moreover, literature survey has indicated that selenium from fly ash and other anthropogenic sources are potential causes for environmental pollution. It is also the consensus of the research team that the recent change in the regulation of selenium level in drinking water seems to suggest that this trace mineral may not be as toxic as previously predicted. It is also suggested that extensive biological testing is required in order to define the fine lines among deficiency, sufficiency and toxicity levels of selenium in drinking and surface waters, in various food groups, plants, soils, and minerals.

SECTION I

INTRODUCTION

Since the discovery of Se in 1817 by Berzelius and Gahn in connection with their studies of sulfuric acid, this element has achieved a unique duality in nature wherein the range between dietary requirements and toxic levels is relatively narrow. Selenium toxicity diseases (sometimes called alkali disease) in animals are known to occur when the intake exceeds 4 mg/kg and selenium deficiency symptoms may occur when dietary intake is less than 0.04 mg/kg. The narrow gap between necessary and toxic concentrations makes it imperative to understand processes controlling speciation, mobility and availability of this element in the environment. Selenium is absorbed by forage and other plants in sufficient amounts to cause toxicity in animals. The SeO_4^{2-} species is the most soluble Se form and is responsible for most Se content in Se-accumulator plants. Selenium deficiency is recognized in animals as "white muscle disease" (muscular dystrophy) when Se content in feed is less than 0.03-0.10 ppm. Previous reports indicated Se toxicity in animals occur if Se concentration exceeded 5 ppm. The U.S.-EPA and the World Health Organization (WHO) both have drinking water standards for Se which is set at a 0.01 ppm (10 ppb). The recommended dietary intake for a 70 kg man is 0.0007-0.0028 mg/kg per day. In humans, for example, longterm exposure may cause amyotrophic lateral sclerosis. On the other hand, studies have indicated that trace amounts of Se in the diet may protect people from cancer and heart disease. The first study involved 27 countries showing an inverse relationship between Se content in soil and incidence of cancer. The second study reported a positive correlation between low Se content in blood and the incidence of breast cancer in women. The National Academy of Sciences stipulates the water quality guideline for Se in irrigation water not to exceed 0.02 ppm, however the promulgated level for Se in drinking water in 1992 is 0.05 ppm. High Se in the Kesterson Reservoir System in California was traced to the unusual death and deformation of waterfowl. The Se was leached from agricultural soils and entered the Reservoir by irrigation drainage water.

These values and examples should exemplify the types of concerns involved. Much of the Se found in water systems and in plants and forages is from soils.

However, analysis of geologic samples indicate the geographical distribution of Se is not uniform.

A. Objectives

The objective of the research program is to assess the environmental impact of selenium from coal mine spoils. The goal was to gather sufficient technical information to allow assessment of this unique environmental problem. The assessment included gathering extensive literature on the work done concerning the origin, solubility, transformation, and health impacts of selenium. Additionally, it was the aim of the project to conduct an elaborate lysimeter study at a selected orphan coal mine site and gather necessary data on the chemical transformation of selenium under natural conditions. Moreover, laboratory mini-column study was conducted to compare data on the chemical transformation of selenium under controlled conditions. A mathematical model was also developed that could provide an early warning on the potential contamination of groundwater resources with selenium. It was also the objective of the project to gather water and soil samples from every county in Oklahoma and to use the data to identify counties that may exceed the permissible level of selenium in drinking water.

B. Background

With an increased awareness in alternate energy sources such as enhanced oil recovery and expanded use of existing coal reserves, it is imperative to further understand the role of man's activity upon potential environmental problems. Regulations and programs exist to productively reclaim mining sites. One criteria addressed by some mining regulations is a chemical parameter analysis, including selenium as a potential hazard.

Selenium is a biologically essential element recognized as a metabolic requirement in trace amounts for animals. It is toxic to them when ingested in amounts ranging from about 0.1 to 10 mg/kg of food. Accounts are recorded indicating a relationship between selenium and birth deformities in humans and also, for example, in birds. Determinations of Se concentrations in several materials indicate Se is widely distributed. The common range for Se in soils

is 0.1-2 ppm with the selected average 0.3 ppm.

Surface mining and reclamation are activities which are regulated by the Surface Mining Control and Reclamation Act. One parameter addressed in some state regulatory criteria is the analysis of Se (usually expressed only as total Se) in the topsoil and overburden. Available Se is known to be responsible for deficiency diseases and poisonings. The Se species most readily available for plant uptake is selenate, depending on the redox conditions of the soil environment. High oxidation potential, low pH, and oxic soils would establish selenate as the predominate species.

This study investigated available Se in a selected mine site and the potential for environmental concern.

C. Scope

The scope of the project covered the following tasks:

Task 1 - Literature review

Task 2 - Lysimeter setup

Task 3 - Environmental impact assessment

Task 4 - Groundwater and soil sampling and analysis

Task 5 - Laboratory mini-column study

Several changes in emphasis and tasking were made during the course of the project. These are described below. The literature review (task 1) included the published literature available, information obtained by direct contact with current investigators in the field, and new data that became available during the course of the project. Close communication with the DOE project officer, Mr. Jerry Harness, was kept to make sure that the project was fulfilling its prime objectives.

In task 2, lysimeter design, construction, and setup was based on the previously proven work by Feagley and Blanchard at the University of Missouri. Close communication with these researchers was encouraged at the initial stage of the project for exchange of ideas on modification of the lysimeter system.

Task 3, environmental impact assessment, was conducted by a graduate

student, Mr. Hualiang Zhang, who developed a mathematical model that could be used to predict the environmental impact of selenium from various sources. Although this model has not been tested for this project, primarily due to shortage of time and the lack of input parameters, it is aim of the principal investigator to apply the model in anticipated projects.

Task 4, groundwater and soil sampling, was initiated in order to gather sufficient data from Oklahoma soils and groundwaters such that an overall impact assessment of selenium can be made. The task included collecting soil and groundwater samples from each county in Oklahoma and assaying for total selenium, selenite and selenate. Some problems were encountered in locating functioning water wells in some counties, although most of the owners were cooperative.

Task 5, laboratory mini-column study, was one that was added to the original objectives to serve as a compliment for the data obtained from the field lysimeter study. The same spoil and soil samples, from the field where the lysimeter was installed, were used in this study. The mini-columns were constructed from disposable syringe barrels packed with the spoil or soil material. This study showed that selenite was indeed the only stable species that was found in the overburden, and that it was so tenaciously held by the fine particles that even a dilute acid solution could not remove it.

SECTION II

TECHNICAL LITERATURE REVIEW

A. INTRODUCTION

Selenium was discovered in 1817 by the Swedish chemist, Berzelius, in residue from Sulphuric acid production. It was named from the Greek word, Selene, meaning the moon, because of its resemblance to Tellurium, an element which had been discovered earlier and was named from the Latin word *tellus*, meaning the earth (1). Selenium is located between Sulfur and Tellurium in the periodic table. It is both beneficial and toxic to animals, plants and humans. The narrow gap between necessary and toxic concentration of Se makes it imperative to understand the processes controlling the distribution of this element in the environment. The processes responsible for its distribution include volcanic activity, the burning of fossil fuels, the weathering of rocks and soils, ground water transport, precipitation of minerals, adsorption, chemical or bacterial reduction and oxidation, and metabolic uptake and subsequent release of the element by plants and animals (2).

Although Se in high concentrations is toxic to animals, the element is an essential nutrient in low concentrations. Selenium deficiency became an agricultural problem because of changes in animal nutrition, which resulted in losses of livestock in the United States. This prompted the Food and Drug Administration to approve the use of Se as Selenate or Selenite in concentrations up to 0.2 ppm as an additive in animal feeds. Most Se intake is normally associated with consumption of cereals and sea foods. The average human diet in the U.S. contains 1.8 mg of Se per month (3).

Selenium is widely distributed in nature but does not occur evenly in the lithosphere. Its compounds are toxic to animals feeding on highly seleniferous plants, causing them to develop "alkali disease". Symptoms of chronic toxicity in animals include lameness, hoof malformation, loss of hair and emaciation (4). Most evidences indicate that there is a great overall potential for Se deficiency than for toxicity at current levels of Se intake. The maximum contaminant level in drinking water is 10 micrograms per liter, a level that barely provides the

minimum nutrient amount of Selenium with a consumption of 2 liters per day (5).

Selenium is one of the most widely distributed elements on the earth's crust and is rarely present in any materials in concentrations exceeding 500 ug/g. The presence or absence of Se in any soil is dependent on a series of geochemical and environmental factors. Selenium originating from igneous rocks may be released to sediments and finally reaching the soils. Plants may take up Se from the soil. Studies conducted on the occurrence of Se indicate that Se in soils comes mainly from geochemical processes and anthropogenic sources (6).

Selenium is involved in a variety of physical, chemical and biological processes. These processes include volcanic activity, combustion of fossil fuels, weathering of rocks and soils, soil leaching, groundwater transport, plant and animal uptake and releases, adsorption and desorption, chemical and biological redox reactions and mineral formation. The importance of a given process is largely determined by the particular speciation of Se. Therefore, the biogeochemistry of Se and environmental parameters, such as pH and redox conditions, strongly influence the concentration, mobility and distribution of Se in the environment.

B. SOURCES OF SELENIUM IN NATURE

1. Soils and Rocks

Much of the Se in the earth's crust is associated with sulfide minerals and it is here that Se is recovered during the electrolytic refining of sulfide minerals. Selenium is associated with sulfides of silver, copper, lead, mercury, nickel and other metals (6). During the early magmatic stage, sulfides of iron, cobalt, and nickel tend to separate from magma and, at the same time, Se separates and gets associated with some of the sulfide minerals (6). Kolgonen (7?) observed that Se, being a chalcophile element, does not become incorporated into silicates during the endogenic conditions and, therefore, most of it is found in sulfides. During exogenic processes, Se partly separates from sulfur (6).

During magma crystallization, volatile components including sulfur and Se are concentrated in the residual fluid phase, thus becoming separated from magma and often from sulfide ore bodies. However, the average sulfur and Se content

in igneous rocks is considered to be an acceptable value. Goldschmidt (6) reported an average of 520 ppm sulfur and 0.09 ppm Se in igneous rocks, thereby giving a S : Se ratio of 1 : 6000. Coleman and Delevaux (7) reported the following maximum values for Se: Pyrite 5 %, marcasite 0.65 %, and chalcocite 5 %. It must be noted, however, that there is a wide variation in the Se content of sulfide minerals with such factors as mineralogical composition, type of deposits and geological setting of ore body that play an important role in dictating Se levels. The highest content of Se is found in Chalcopyrite - pentlandite - pyrrhotite deposits and quartz - pyrite - chalcopyrite formations. Goldschmidt suggested that the Se content is higher in high temperature sulfides than in low temperature ones.

Selenium is very mobile in conditions under which Granite rocks are crystallized and is depleted in silicic plutonic rocks and in pegmatites (6). The behavior of Se during weathering of minerals is fairly simple compared with most other elements. When sulfides weather in acid soils, Se is oxidised to the elemental form or to selenite. It is adsorbed to colloids and migrates with difficulty. Under neutral to alkaline environments, such as, in calcareous soils, Se is oxidised to Selenate, in which form it easily dissolves (6).

Selenium is not evenly distributed in geologic materials. Igneous rocks have been estimated to contain Se in the range of 0.03 to 0.8 ppm, with an average of 0.09 ppm (8). This value was accepted as the average crustal abundance of the element, but revision of the recent data showed an estimated abundance of 0.05 ppm (9). Selenium was found in volcanic gases, which suggested that volcanic activity played an important role in the development of Seleniferous geologic beds. In addition to volcanism, weathering of igneous rocks and leaching by rain water were considered to be important sources of the element (10). In practice, Se tends to concentrate in sedimentary rather than in igneous rocks. Silicate rocks are formed from the magma, and volcanic eruptions result in losses of volatile selenium. Volatile Se is distributed over the earth's surface, eventually that adds to the Se content of the present day soils (11). Igneous rocks are generally deficient in Se because of volatilization of the sediment by volcanic activity (12). Rock weathering is the major natural source of Se in the environment. Weathering of the earth's crustal material results in an estimated 7.2×10^6 kg Se being mobilized annually and transported by rivers draining the land mass (13).

The concentration of selenium in most soils lies within the range of 0.01 to 2.0 mg Se/kg. However, high concentrations of 1200 mg Se/kg as total and 38 mg Se/kg as water soluble selenate have been reported in seleniferous areas of the world (14). The concentrations of Se in soils varies with the origin, pH and composition of soils (15). Shales are the parent materials for about 40% of the earth's soil. Sandstones, limestones and igneous rocks are about equally abundant at weathering surfaces. Soils derived from shales are most likely to be supplied with Selenium. The majority of seleniferous soils are weathered from shales. Soils derived from sandstones and limestones may have variable Se concentrations. Soils of igneous origin are most likely to be very low in Se. Selenium concentrations in soils range from less than 0.1 ppm in a Se deficient area of New Zealand to as high as 1200 ppm in an organic soil in Ireland (16). Availability of Se to plants is governed by the chemical form of the element in the soil and by the pH and Eh in the root-soil environment (15).

Surveys in most countries like Denmark, Iceland, Sweden, Finland etc. indicate that high levels of Se in crops could be attributed to the geology of the area. Various reports from most countries have indicated areas with low, medium and high Se concentrations (14). Allaway (15) has summarized the relationship among the concentrations of Se in rocks, soils and plants as follows:

- a) Where rocks with a high content of Se decompose to form well-drained soils in subhumid areas (<20 in of annual rainfall), selenides and other insoluble forms of Se will be converted to selenates and organic Se compounds. These compounds will be available to plants, and vegetation containing potentially toxic levels of Se will probably be produced in these soils.
- b) Where rocks with a high content of Se weather to form soils in humid areas, slightly soluble complexes of ferric oxide or hydroxides and selenate ions will be formed. These soils will also be slightly-to-strongly acid, and plants produced on them will not contain toxic concentrations of Se, but they may contain sufficient Se to protect livestock consuming them from Se deficiency.
- c) Where rocks with a high content of Se weather to form poorly drained soils, or where Se from higher lying areas is deposited in poorly drained areas by alluvial action, and where the soils are alkaline, plants containing toxic levels of selenium are likely to be produced.
- d) Where rocks with a low content of Se decompose to form soils under either humid or dry conditions, the plants produced are likely to

contain insufficient Se to protect animals from Se deficiency (15).

2. Plants

Plants are capable of taking up some Se if growing in soils where Se is available. The greatest interest in plant Se is due to the importance of this element in nutrition, particularly for domestic animals, since Se can act both as micro nutrient and a toxin (16). Plants capable of assimilating large quantities of Se have been divided into primary and secondary Se absorbers. Primary absorbers grow only on Se toxic soils and include about 24 species. Secondary absorbers are capable of accumulating moderately large quantities of Se when growing on soils containing high quantities of available Se (17).

In general, Se uptake by plants depends on climatic conditions, water regime of soil, oxidation-reduction potential, and pH. About 8 Se-containing organic compounds have been identified in plants. Amino acids, especially cysteine, are likely to bind Se, which may have several metabolic implications. During growth and accumulation, Se is mined from the soil and rocks and is concentrated near the soil surface. Plants decompose at the soil surface and release organic and inorganic Se to the environment. Some of the Se upon decomposition in-situ or by animal digestive processes is present as organic compounds but most of it is in inorganic form as Selenate or Selenite.

3. Other Natural Sources in the Environment

Selenium occurs commonly in fossil fuels. Coal usually contains up to 10 mg Se/kg, and fuel oil up to 7.5 mg Se/kg. The large amounts of coal residues produced by coal-fired power plants are a potential source of Se in the environment (18). Selenium concentrations in surface waters average 2 ug/L or less (19). Drainage from irrigation and soil leaching are principal sources of Se in waters. Apparently, water can rarely be considered a significant source of the element either from a nutritional or a toxicity viewpoint. However, even at the very low levels found in rivers, the large volume of water involved contribute to the transport of rather large amount of the element. It is estimated that river flow deposits about 8,000 tons of Se per year into oceans (20). Water, therefore, is important in actively and continuously leaching,

transporting, and redepositing the element. A potential Se pollution source, especially in the food chain, may be the use of sewage fertilizers on agricultural lands. Andersen and Nelson (21) measured changes in content of trace elements in soils and plants as the result of applications of sewage sludge. Total and acid extractable soil contents of all elements applied (Mn, Zn, Cu, Ni, Co, Cr, Pb, Cd, Hg, and Se) increased as would be expected. However, the observed fact that the decreased plant availability of Se from the treated soils was difficult to explain. Two possible postulations based on soil chemistry were suggested. First, if sludge additions result in lowered soil pH, then Se may be less available by virtue of formation of the very insoluble $\text{Fe}_2(\text{OH})_4\text{SeO}_3$. Second, other cations in the sludge, Cd, Co, Cu, Pb, etc., may also form insoluble Se compounds (22). Table 1 lists selected Se sources in nature.

a. Minerals

Sulfides or native sulfur deposits often contain Se in significant amounts because of the chemical similarity between Sulfur and Se. Thus sulfides of iron, mercury, silver, copper, lead and zinc have been found to contain Se, sometimes at levels over 20 % (23).

Selenium also occurs in coal deposits, probably due to the presence of Se enriched biomaterials, which decompose during coal formation. The Se content of 138 samples of coal from U.S. deposits, in 22 states, ranged from 0.46 to 10.65 ppm and averaged 2.8 ppm which was over 50 times the crustal abundance of the element (24). Coal often contains 1 to 20 mg Se/kg. Upon combustion, coal releases large amount of Se into the ecosystem. An estimated 6×10^{11} and 28×10^{11} tons of coal (having about 11% of ash) are combusted annually in the USA and the world, respectively (25). Upon combustion, about 40% of the ash occurs as bottom ash or slag, 60% as fly ash, and less than 1% as aerosols, that escapes to the atmosphere (26). These proportions may differ for other coal boiler plants because of design and operating conditions. Most coal consumed is burned at power plants where Se and other elements entering the boiler are partitioned between the bottom ash stream (slag) and flue gas stream containing suspended fly ash and the vapors of volatile elements or compounds (27).

Table 1. Selected Se concentrations in some natural sources.

Materials	Se, mg/kg	Reference
Earth's crust	0.05 0.03-0.8	Taylor, 1964 NAS, 1976
Granite	0.01-0.05	Kabata-Pendias, 1984
Limestone	0.08 0.03-0.1	Ebens & Shacklette, 1982 Kabata-Pendias, 1984
(Oklahoma)	0.19-0.31	Connor & Shacklette, 1975
Sandstone	< 0.05 0.05-1.12	Ebens & Shacklette, 1982 Lakin & Davison, 1967
(Oklahoma)	0.11	Connor & Shacklette, 1975
Shales	0.06 0.24-277	Ebens & Shacklette, 1982 Lakin & Davison, 1967
(oklahoma)	0.46-0.64	Connor & Shacklette, 1975
Phosphate rocks	1- 300 1-178	NAS-NRC, 1976 Rader & Hill, 1935
Soils		
Seleniferous	1-80 <1200	Trelease, 1945 Fleming, 1962
Other soils		
USA	<0.1-4.3	Shacklette & Boerngen, 1984
England	<0.01-4.7	Thornton et al., 1983
Coal	0.46-10.65 0.2-44 1-20	Pillay et al., 1969 Boon & Smith, 1985 Mayland et al, 1989
Crude oil	0.06-0.39	Pillay et al, 1969
Atmospheric dust	0.05-10	Lakin & Byers, 1941
Vegetation		
Se accumulators	51-4474	Rosenfeld & Beath, 1964
Crop plants(low-Se)	< 0.05	Rosenfeld & Beach, 1964
Fruits and vegetables	< 0.01	Allaway, 1973
USA plants		
Grasses	0.01-0.04	Kabata-Pendias, 1984
Clover & alfalfa	0.03-0.88	Kabata-Pendias, 1984
Barley	0.2-1.8	Ebens & Shacklette, 1982
Algae		
Marine	0.04 - 0.24	Chau & Riley, 1965
Freshwater	<2.0	Jenkins, 1980
Ocean waters	0.0001-0.004	Schutz and Turekian, 1965
River waters	0.0001-0.0004	Kharkar et al, 1968
Aquatic plants	0.02-0.14	Sandholm et al, 1973
Fish	0.5 - 6.2	Lakin, 1972
Anthropogenic		
Petroleum products	0.15-1.65	Lakin, 1972
Fly ash	1.2-16.5	Grtenmann et al, 1976
Sewage sludge	1.8-4.8	Furr et al, 1980

b. The Atmosphere

Selenium is introduced to the atmosphere by several natural sources. It has been suggested that volcanoes may be major contributors of Se in the air (28). Volatile Se compounds are released by accumulator plants mainly as dimethyl selenide. There are no accurate estimates, however, of the quantities contributed to the air by each of the above sources. The estimated industrial emissions of Se seems to be a small quantity to cause a serious pollution problem in comparison with the amounts of other industrial pollutants emitted (29).

c. Natural Waters

The occurrence of soluble Se compounds in some selenium-rich soils and other geological materials suggests that natural waters would be effective in leaching and transporting the element from drainage areas to flood plains and other large water bodies. While considering the recent available information, the overall speciation data shows SeO_3^{2-} to be the dominant form of Se, with Se (-2) and Se(0) having the lowest concentrations (30). Nevertheless, the data also indicated that every river is unique with respect to its speciation and concentration of Se, and broad generalizations are therefore, inappropriate. Cutter (31) has obtained speciation data for the largest river system of California, the San Joaquin and Sacramento rivers. The San Joaquin, which drains the southern portion of the agriculturally important central valley of California, has total Se concentration of an order of magnitude higher than those of the Sacramento draining the northern valley. In San Joaquin, selenate is the dominant form, while selenite and selenide or elemental Se are primary species in Sacramento river (31).

The content and speciation of Se in ground water and drinking water is of the most direct concern to humans. Selenium is a minor constituent in drinking water where it is found in a concentration range of less than 0.1-100 ug/L. The Safe Drinking Water Act of the U.S.-EPA has established an upper limit of 0.01 mg/liter which is rarely exceeded. However, water derived from some of the cretaceous zones may have high concentrations of both Se and total soluble salts (32). In a study in central Montana, it was reported that water from wells drilled into any of the geologic formations, cretaceous Colorado

group, contained as much as 1000 mg/liter Se (32). An important source of drinking water, ground water, has total Se concentration ranging from less than 0.6-342 nmoles/kg. From these a worldwide average of 30nmoles/kg can be extrapolated. All the available data shows that selenate is the major Se species in ground water. Humic substances in ground water interfere with ground water Se speciation (31).

Selenium concentrations in surface water averages 2 ug/L or less. Drainage from irrigation and soil leachate are the principal sources of Se in surface water. High concentrations of Se also occur in subsurface drainage waters from irrigated soils such as in much of the San Joaquin valley. However, the occurrence of elevated Se level in ground water within this region is not uniform. Some areas have relatively low concentrations of Se while the surrounding areas have much higher levels (32).

4. Anthropogenic Sources

Human activities are significantly impacting the global Se cycle. Andren et al. (33) concluded that 1.5 - 2.5 times as much Se is mobilized through coal burning as by natural weathering process. Most of the bottom ash from the precipitators are transported to landfills and the solid residuals are flushed with water to ash ponds, where Se may be leached from the ash and enter the aquatic environment. Vapors are discharged as aerosols to the atmosphere, only to enter the terrestrial and aquatic environment by wet or dry deposition (34). According to Se mass balance study conducted at the Allen Steel Plant in Memphis (35), of the 2.2 mg Se/kg coal entering the boiler, 0.3 % exited with the slag, 68% was with the precipitated fly ash particles and the remaining 32% was associated with the vapor phase (34). A survey of 86 samples of coal from USA indicate that these samples contain an average of 3.36 ppm Se, which is over 34 times the crustal abundance of the element (36).

Almost all primary Se is produced from copper refinery slimes. The present production technology consists of processes designed primarily for effective recovery of precious metals. Selenium recoveries have therefore received secondary importance, which is reflected in low recovery efficiencies (37). Selenium is recovered from slimes by volatilization during roasting or furnacing as the oxide which is scrubbed from exhaust gas or by leaching of roasted calcine

or furnace slag. All processes use sulfur dioxide to precipitate Se metal from solutions of sodium selenite and selenious acid (37). The annual consumption of Se in the United States increased 50% from 1964 to 1973. The most significant use of Se has been in the electronic industry, including use in rectifiers, xerographics copying machines, and photoelectric cells. The chemical industry accounted for an estimated 1/8 of the Se consumed. The chief use of the element in agriculture is in prevention of Se deficiency in livestock and poultry (37).

5. Cycle of Selenium in Nature

The schematic diagram summarizing the environmental cycle of Se is shown in Figure 1. This element is 40th in abundance in the earth (38). Volcanic eruptions often result in losses of volatile Se from silicate rocks formed from magma. Volatile Se is distributed over the earth's surface which eventually adds to the Se content of the present day soils. Soils derived from shales are most likely to be supplied with Se. Plants absorb and accumulate Se from soils. Plants decompose at the soil surface and release organic and inorganic Se to the environment. Some of the plants and plant products are consumed by animals and human beings. Conversely, these plants products may be transported elsewhere before they are consumed and waste fractions are returned to the soil, streams, lakes and oceans (38).

C. SELENIUM TRANSFORMATION IN NATURE

1. Biological

Biological activity is considered a major contributor to selenium release into the atmosphere from aquatic and terrestrial environments (39). Rosenfeld and Beath (40) reported that elemental Se may be present in some soils due to the action of some bacteria and fungi that can reduce selenite and selenate to elemental selenium. Also under suitable conditions elemental Se could be converted to selenite and selenate by microorganisms. Volatile compounds of selenium include dimethyl selenide (DMSe), dimethyl diselenide, dimethylselenone, methane selenol, and hydrogen selenide (41). Dimethyl selenide is the principle compound released by microbial and plant respiration (42). Volatile selenium was

Figure 1. Possible Cycle of Selenium under field Conditions.

initially collected from accumulator (*Astragalus racemosus*) and nonaccumulator plants and the volatile form respired by selenium-accumulator plants was identified as DMSe (43). The same authors also found DMSe to be the major Se compound produced by fresh cabbage leaves.

Under certain conditions significant quantities of Se as DMSe are respired by animals as a volatile compound having a garlic-like odor (44). This compound is probably formed by methylating selenite. This author also found that the amount exhaled by animals increases with increasing Se intake and is greater for orally administered selenite than selenate, selenomethionine, or seleniferous wheat. Several investigators have indicated that the formation of DMSe is inhibited by the presence of As, Cd, and other heavy metals.

Zieve and Peterson (45) observed that $^{75}\text{SeDMSe}$ was also sorbed to soils. The amount sorbed was greater for wet soils than dry and was greater when the atmospheric concentration of DMSe was higher than when it was lower. These authors found that sorption of DMSe by individual soil constituents was greatest for organic matter and clays, less for Mn and Fe oxides, and least for acid-washed sands. Experiments with sterilized soils indicated that microorganisms were not significantly involved in the sorption process but may have been responsible for the conversion of DMSe to other Se forms after sorption occurred. They concluded that the soil was an important natural sink for atmospheric DMSe.

2. Chemical

Solubility diagrams are useful tools for investigating how Eh and pH can control the chemical forms of an element in soils. Also, they indicate when a chemical reaction can take place and the direction of that reaction. Kinetic studies are necessary, however, to determine the rate at which these reactions occur as a result of changes in both redox and pH.

The rate of transformation from selenite to selenate and vice versa is slow, and of selenite to elemental Se is even slower (46). These authors also indicated that when elemental Se is added to soils, parts of it rapidly oxidizes to selenite. After the fast initial oxidation, the remaining Se is quite inert and its oxidation can be predicted to proceed very slowly. The oxidation of elemental Se is therefore non pH-dependent, although the rate of oxidation may vary with the type of soil under investigation.

Lakin (47) found that under an acid environment, oxidation of selenite to selenate is very difficult. But at neutral and alkaline pH, the oxidation of selenite to selenate is much faster. If selenite were distributed in porous alkaline moist soil, its oxidation by air might proceed at measurable rate. In alkaline and oxidizing environments, selenate is expected to be very stable. Rosenfeld and Beath (40) stated that selenium dioxide is the most stable oxide form of the element. Mild reducing agents can easily react with selenium dioxide to form elemental Se. Selenium dioxide dissolves in water readily and forms selenious acid, which is a weak acid. Under very strong acidic conditions, powerful oxidizing agents are required to oxidize Se or selenious acid to selenic acid. Selenic acid is a less stable but stronger oxidizing agent than sulfuric acid. Larkin (47) reported that H_2Se is unstable in the presence of moist air, where it decomposes to elemental Se and water. The presence of Se as a pink halo around oxidizing sulfide minerals is indicative of this instability. Selenite is rapidly reduced to elemental Se by mild reducing agents such as sulfur dioxide under acidic conditions (NAS-NRC, 1983).

D. USES OF SELENIUM COMPOUNDS

The unique optical properties of selenium are useful in the laboratory and industrial applications. The familiar photographic exposure meters incorporate a Se photocell and a galvanometer which measures the current generated upon exposure of the cell to the light. It is extensively used to decolorize the green tint in glass resulting from ferrous sillicate (48). Selenate and also a 30% solution of potassium ammonium selenosulfide (selocide) have been used in control of mites and red spider. With the recognition of the role of Se in animal health and the development of safe and effective means of prevention of treatment of Se-responsive diseases, the use of Se as a food additive for animals may soon become one of the most important uses of the element and its compounds (48). However, commercial uses of Se are listed in Table 2.

Most Selenite salts are less soluble than the corresponding selenates. The extremely low solubility of ferric selenite and basic ferric selenite, which is found in dilute solutions of ferric chloride and sodium selenite, are important to environmental cycling of Se. Selenites also form stable adsorption complexes with ferric oxides of even lower solubility than the ferric selenites. Under

Table 2. Uses of some inorganic Se compounds (National Academy of Science, 1976).

Selenium Compound	Industrial Use
Aluminium selenide research.	in preparation of hydrogen selenide; semiconductor
Ammonium selenite	in manufacture of red glass; as reagent for alkaloids
Arsenic Hemiselenide	in manufacture of glass
Cadmium selenide	in photoconductors, semiconductor photoelectric cells; in phosphors
Calcium selenide	in electron emitters
Cupric selenate	in coloring copper alloys black.
Indium selenide	in semiconductor research
Potassium selenate	as reagent
Selenium hexafluoride	as gaseous electric insulator
Selenium dioxide	in the manufacture of selenium compounds; as reagent for alkaloids
Sodium selenate	as veterinary therapeutic agent

certain conditions, selenite seems to be completely adsorbed in high amounts by ferric hydroxide and to a lesser extent, by aluminium hydroxide, while selenate is not.

The adsorption of selenite was shown to follow a Langmuirian isotherm, with the specific adsorption being higher in acidic solutions and decreasing with an increase of pH value (49). The low levels of Se in ocean waters have been attributed to adsorption of Selenite by the oxides of the metals, such as iron and manganese (49).

D. SELENIUM FROM COAL MINES AND SPOILS

In order to determine the quantity of Se that originate from coal mine spoils, and the release of the element into the surrounding environment, we must first characterize the Se content of the coal. Since Se can replace S in organic complexes and in sulfides, the Se content of coal may be many times its crustal abundance. In fact, Se is the most enriched element found in coal. Coal often contains from 1 to 20 mg Se/kg, although some coal from the People's Republic of China is known to contain over 1000 mg Se/kg (50). A survey of 86 U.S.A. coals (see Table 2) indicates that these samples contain an average of 3.36 ppm of Selenium, which is over 34 times the crustal abundance of the element (51). It is evident that selenium concentration in coal can vary over a wide range. This variation occurs not only between coal type and location, but also within seams at a given location. The Se content of Oklahoma coal is expected to be in the same range as those in the neighboring states.

Upon combustion, coal releases large amounts of Se into the ecosystem. About 40 % of the ash occurs as bottom ash or slag, 60 % as fly ash, and < 1 % as aerosols that escape to the atmosphere (52) (17). Most of the bottom ash and the ash from precipitators are transported to landfills as solid residues or flushed with water to ash ponds, in this case Se may be leached from the ash and enter the aquatic environment. Also, during coal combustion small particles and vapors are discharged as aerosols to the atmosphere which eventually finds its way into terrestrial and aquatic environments either by wet or dry deposition. It is estimated that 1.5 to 2.5 times as much Se is mobilized through coal burning as by natural weathering process ((53) (18)).

Table 3. Selenium content of U.S.A. coals (Pillay, K.K.S. et al.)

State	# of Samples	Selenium content		
		Low	High	Average
		(ppm)	(ppm)	(ppm)
Alabama	4	2.20	8.15	5.14
Colorado	3	1.25	2.05	1.65
Illinois	2	1.05	1.97	1.51
Indiana	4	1.41	8.36	3.96
Iowa	1	1.54	1.54	1.54
Kansas	1	2.27	2.27	2.27
Kentucky	5	1.71	4.82	3.13
Maryland	1	1.70	1.70	1.70
Missouri	2	3.41	4.98	4.19
Montana	3	2.20	4.11	3.04
New Mexico	2	4.43	4.82	4.62
North Dakota	1	0.98	0.98	0.98
Ohio	4	2.64	7.30	4.62
Pennsylvania	11	1.35	10.65	3.74
Tennessee	1	4.89	4.89	4.89
Utah	4	1.30	2.37	1.83
Virginia	4	2.24	6.13	4.37
Washington	2	0.46	0.66	0.56
West Virginia	30	0.92	6.80	3.36
Wyoming	1	3.43	3.43	3.43

The development of large-scale coal mining operation in the western USA has raised concerns regarding the potential contamination of soils, surface water, and groundwaters with Se in and adjacent to these mining operations. Coal mining operations in the resaturated backfill can increase Se solubility and mobility following oxidation of carbonaceous materials. The greatest Se contribution in backfill aquifers of coal mines apparently comes from carbonaceous roof shales, and rider seams (54).

The introduction of selenium into the environment will follow some general paths. These potential routes include erosion of coal mine spoils onto land and into aquifer, and oxidation and movement of selenates in percolating and runoff mine waters. Literature search has revealed that only a few studies have investigated Se concentration in coal mine spoils and associated materials. Selenium concentration in coal mine spoils and associated materials from eight mines in the western energy region of the United States was determined by X-ray fluorescence and fluorimetric methods, respectively. Coal mine spoil materials at all mines consisted of claystone and siltstone with lesser amounts of sandstone, shale, and coal. Glacial deposits consisting of gravel, silt, sand, and clay are important spoil materials. Samples of spoil material or a spoil-soil mixture were collected to a depth of about 20 cm. The ground cover consisted of sweetclover and alfalfa that grew within 1 m of the coal spoil site. Table 4 lists the resulting data (55).

Crested wheatgrass was analyzed at the Dave Johnston Mine, Wyoming, to assess the possible effects of coal mine spoils on the chemical composition of this widely used reclamation species. Eight elements (Cd, Co, F, Mn, P, U, V, and Zn) showed significant differences between the samples growing in 10-15 cm of topsoil covering the spoils and the samples from soils nearby. Selenium concentration, however, showed no significant difference. The mean Se concentrations in the topsoil borrow areas and reclaimed spoil areas are 0.23 ppm and 0.27 ppm, respectively (56). Further investigations are needed to determine Se content in spoils and plants that grow on mine spoil and reclaimed soils of abandoned coal mine area. The possibility that elemental composition of forage grown on reclaimed spoil may be injurious to domestic as well as native animals should receive careful consideration in planning the revegetation of mined areas and proper utilization of these areas.

Table 4. Selenium in coal mine spoils and associated materials in the western energy region in the United State (20).

Sample, collection	Mean (ppm)	Observed range (ppm)
Coal mine spoil		
Beulah North mine, North Dakota	0.19	0.1-0.41
Dave Johnston mine, Wyoming	0.28	<0.1-0.69
Hidden Valley mine, Wyoming	0.31	0.18-0.49
Kincaid mine, North Dakota	0.22	<0.1-0.45
Savage mine, Montana	0.20	<0.1-0.66
Velva mine, North Dakota	0.21	<0.1-0.54
Big Sky mine, Montana	0.17	<0.1-0.40
San Juan mine, New Mexico	0.19	<0.2-0.70
Topsoil used in spoil reclamation		
San Juan mine, New Mexico	0.18	<0.2-0.50
Plants (dry-weight basis)		
Yellow sweetclover		
Beulah North mine, North Dakota	0.15	0.08-0.60
Dave Johnston mine, Wyoming	0.37	0.10-3.00
Hidden Valley mine, Wyoming	0.53	0.15-1.20
Kincaid mine, North Dakota	0.17	0.06-0.55
Savage mine, Montana	1.30	0.60-6.00
Velva mine, North Dakota	0.49	0.15-2.00
White sweetclover		
Big Sky mine, Montana	0.42	0.08-1.00
Utility mine, Saskatchewan	0.23	0.06-0.50
Alfalfa		
Beulah North mine, North Dakota	0.18	0.06-0.35
Dave Johnston mine, Wyoming	0.34	0.20-0.80
Savage mine, Montana	1.10	0.75-2.70
Velva mine, North Dakota	0.33	0.30-0.40
Big Sky mine, Montana	0.22	0.10-0.45
San Juan mine, New Mexico		
Fourwing saltbush	0.22	0.10-0.45
Alkali Sacaton	0.096	0.080-0.10

1. Selenium Solubility

Selenium, like sulfur, can exist in four oxidation states: II^- , 0, IV^+ , and VI^+ . The concentration, speciation, and solubility of these species in soils are different, and depend on the soil environment, such as pH, redox potential, reaction kinetics, and biological interactions. The common forms of Se present in most soils are selenates, selenites, elemental Se, selenides, and organic Se compounds. It is known that Se speciation and solubility in soils are mainly governed by the redox potential and pH. Therefore, discussion of Se speciation, solubility in soils, and the influences of redox potential and pH on Se speciation and solubility will be helpful in understanding the pollution potential of Se emanating from coal mine spoils.

The solubilities of some common selenate minerals are shown in Figure 2 (57). It indicates that most selenate minerals are very soluble and unstable in soils. The most stable form of selenate in soils is BaSeO_4 , however, this specie is still very soluble. Most selenate minerals can not exist in cultivated soils, thus selenate is the form of Se most readily taken up by plants.

Figure 3 is a solubility diagram for most selenite minerals (58). It suggests that MnSeO_3 is the only selenite mineral that might persist in acid soils. Other selenite minerals are too soluble to form in soils especially in the alkaline pH range. However, it is apparent that most selenite minerals are less soluble than the corresponding selenate minerals. This is due to the fact that selenites have a stronger affinity for adsorption than that of selenates (59). Solubilities of some selenide minerals and elemental Se are shown in Figure 4 (60). It is observed that the solubilities of selenides and elemental Se are very low in soils under highly reducing conditions. It has been suggested

Figure 2. Some Selenate Minerals Solubilities.

Figure 3. Some Selenite Minerals Solubilities.

Figure 4. Solubilities of Selenide Minerals and Elemental Selenium.

that at reduced conditions, elemental Se and/or metal selenides may control Se solubility in soils (61). Figure 3 indicates that the solubilities of some selenides increase with pH while others show decreased solubilities up to a certain pH. This could be due to the solubility characteristics of the companion ion and the dissolution of the minerals.

2. Speciation of Selenium

Selenium in soil solution is predominantly present in the following forms:

Selenate (VI) SeO_4^{2-} , HSeO_4^- , and H_2SeO_4

Selenite (IV) SeO_3^{2-} , HSeO_3^- , and H_2SeO_3

Selenide (-II) Se^{2-} , HSe^- , and H_2Se

The relationship of Se species, pH, and Eh conditions is demonstrated in Figure 5. It can be used to predict the forms of Se present in the soil solution at a measured pH and pe. The redox couples $\text{O}_2(\text{g})/\text{H}_2\text{O}(\text{l})$ and $\text{H}^+/\text{H}_2(\text{g})$ represent the redox boundaries of the natural aqueous environment. For example, in the region between the lines of $\text{O}_2(\text{g})/\text{H}_2\text{O}$ couple and the selenate/selenite couples, it can be expected that selenium in solution would be in the selenate form.

The solubility and speciation of selenium in soil solution are controlled by many physical and chemical factors, such as pH, dissociation constants, solubility products, and oxidation-reduction potentials. It is known that pH and redox potential are the two most important factors. Figure 6 shows evidence for the effect of redox and pH on Se species in soil solution. It is evident that at high redox conditions ($\text{pe} + \text{pH} > 15.0$), SeO_4^{2-} is the predominant species in solution in both acid and alkaline soils. In the moderate redox range ($\text{pe} + \text{pH}$ is between 7.5 and 15.0), either HSeO_3^- or SeO_3^{2-} is the most important species,

Figure 5. The Relationship Among Selenium Species, pH, and Eh.

Figure 6. The Effect of Redox and pH on Selenium Species in Soil Solution.

depending on soil pH condition. In acid soils HSeO_3^- is predominant, while in alkaline soils SeO_3^{2-} is the major species. At low redox ($\text{pe} + \text{pH} < 7.5$), the major form of Se in soil solution is HSe^- , particularly in alkaline soils. Only in strongly acidic conditions, H_2Se^0 species will contribute selenium to the solution. The concentration of Se^{2-} species is very low in such a solution, and may not be important for most soils.

The effect of redox on solubilities of selenate and selenite minerals in neutral soils ($\text{pH} \approx 7$) is shown in Figure 7 (62). As redox potential increases, selenate solubility decreases slightly, while selenite solubility increases. All of these minerals, however, are very soluble and may not exist under normal soil conditions. Manganese selenite (MnSeO_3) is the only one that might precipitate in strongly acidic soils. The effect of redox on solubilities of elemental Se and selenide minerals in soils at $\text{pH} = 7$ is shown in Figure 8 (63). For most selenides increasing redox will result in increased solubility. Elemental Se is most stable or insoluble at neutral conditions. It is likely that at low redox condition, either elemental selenium or selenide minerals may control selenium solubility in soils.

3. Selenium and Sulfur

Since selenium is located in the oxygen group of the Periodic Table next to sulfur, it is not surprising to find that the chemistry of Se resembles that of S. In fact, selenium metabolism research and studies are based on the assumption that selenium is subjected to the same or similar metabolism processes as sulfur. Therefore, sulfur metabolic pathways provide a useful guideline to discuss selenium metabolism. Comparison of the metabolic pathways of these two

Figure 7. The Effect of Redox on Solubilities of Selenate and Selenite in Natural Soils.

Figure 8. The Effect of Redox on Solubilities of Elemental Se and Selenide in Soils at pH = 7.

elements can help understand the toxic effects of selenium on plants and animals since some selenium toxicity actually is the result of its interference with sulfur metabolism.

a. Similarity

It was found that some organic Se compounds undergo similar metabolic routes as its analog of S since many isolated enzyme systems can utilize S and Se interchangeably (64). The common organic Se compounds usually found in plants are trimethylselenonium ($(\text{CH}_3)_3\text{Se}^+$), selenomethionine $\text{CH}_3\text{Se}(\text{CH}_2)_2\text{CHNH}_2\text{CO}_2\text{H}$, and selenocystine $(\text{HO}_2\text{CCH}(\text{NH}_2)\text{CH}_2\text{Se})_2$. Similarity between the metabolisms of selenonium and sulfonium compounds was found. Trimethylsulfonium is one of the sulfonium compounds, and its metabolism results in the formation of dimethyl sulfide (65). Trimethylselenonium is found to be metabolized by a similar mechanism. Pseudomonas can utilize trimethylselenonium as its carbon source, and one of its metabolism products is identified as dimethyl selenide (66). The microbial decomposition of other sulfonium compounds such as methylmethionine also results in the formation of dimethyl sulfide (67). There is no report in the literature on the microbial metabolism of Se-methylseleno-methionine to dimethyl selenide, but such a cleavage has been found in plant leaves (68).

It is found that methyl mercaptan (CH_3SH) and dimethyl disulfide are two major S products which result from the metabolism of methionine by microorganisms (69). The microbial metabolism of selenomethionine seems to proceed in parallel with that of its S analog. Coch and Greene (70) reported that selenomethionine can support growth of methionine-requiring mutants of Escherichia coli. Doran and Alexander (71) found that when cultures grown on methionine were incubated with

selenomethionine, dimethyl diselenide was evolved from the culture. Transformation of selenomethionine to dimethyl diselenide was also evidenced by resting cell studies with some methionine-utilizing bacteria (72). Therefore, even selenomethionine is toxic to some microorganisms when it is present at substrate concentration, it may be undergoing the same sequence of metabolism as its S analog.

The microbial degradation of selenocystine also proceeds in the same pathway as its S analog, cystine. There are two pathways for the microbial metabolism of cystine (73). One is an oxidative route in which cystine is oxidized through a series of organic S compounds to sulfate. In another route, cystine is reduced to cysteine from which H_2S is released. It is known that selenocystine can be used by some cystine-utilizing microorganisms for growth (71). Hydrogen selenide (H_2Se) and elemental Se are the products of selenocystine metabolism. Because no volatile and soluble organic Se compounds are evolved in the selenocystine metabolism process, it can be concluded that selenocystine is metabolized in a reductive pathway. It is similar to that of cystine and results in the formation of H_2Se , which is oxidized to elemental Se.

The investigation of selenate metabolism indicates that selenate metabolism processes are performed by the same enzyme system that metabolize sulfate (74). It is known that adenosine triphosphate sulfurylase can catalyze the formation of adenosine phosphosulfate (APS) from adenosine triphosphate (ATP) and sulfate as follows:

When selenate was used as a substrate, the ATP sulfurylase showed equal or greater activity. The amount of resultant APSe was less than predicted on the basis of its chemical instability alone (74). This suggested that APSe is less

stable than its analog APS in the presence of sulfurylase. Reuveny (75) proposed that selenate enters the metabolism pathway as an alternative substrate to sulfate via the reaction catalyzed by ATP sulfurylase.

Sulfur is an essential element for life. The similarity between the metabolism of Se and S led researchers to believe that the toxic effects of Se could be in part due to its interference with sulfur metabolism. In fact, the components of the cell which are most sensitive to Se toxicity are those components in which sulfur is required for specific functions (76). In such cases, toxic effect will occur if sulfur is replaced by selenium.

b. Difference

Although similar metabolic pathways of the two elements exist, there are observations which indicate differences in their metabolism. For example, Nissen and Benson (77) found that the excised roots of several crop plants fed with selenate did not form detectable amounts of choline selenate after being treated for 24 hours, while those fed with sulfate formed appreciable amounts of choline sulfate. Also, the requirement of selenium as a trace nutritional element for animals and its incorporation into specific proteins can be indicated that some metabolic processes of some organisms are selenium specific. Such processes may not follow the same metabolic pathway as its sulfur analog. Therefore, the metabolism of selenium can not be derived directly from studies conducted on the metabolism of its analog, sulfur.

E. HEALTH IMPACTS OF SELENIUM

1. In Humans

Humans are also susceptible to Se poisoning. Selenium released from coal mine spoils may ultimately reach humans through the food chain. The main source of Se in the food chain are plant materials, such as vegetables and grains. Water usually does not contribute significantly as a major source of Se except in excessively polluted regions. It is expected that most coal mine spoil sites would be located in rural areas, and people living in such areas usually consume locally grown food and drink ground water for a major part of their diet. In these cases food would become a potential source of Se poisoning in humans. For obvious reason, human health is of priority concern when the issue of Se poisoning is discussed. Identification of Se poisoning in humans, therefore, is an integrated part of the environmental impact assessment of Se from coal mine spoils.

There are some reports in the early literature concerning the Se poisoning in humans. The work of Smith et al perhaps was the first systematic studies of Se poisoning in humans. In his report, Se poisoning in humans was investigated in South Dakota, Wyoming, and Nebraska where animals were found to suffer from alkali disease (78). Farmers living on these seleniferous areas developed some clinical signs due to selenium toxicosis, which included bad teeth, jaundice, vertigo, dermatitis, nail changes, chronic gastrointestinal disease, arthritis, edema, lassitude, and fatigue. Analysis of the Se content of the food of these farmers showed that daily intakes of Se were 0.1 to 0.2 mg of Se per kilogram body weight. It was equivalent to 7.5 to 15 mg/day and far beyond the adequate

range of 0.05 to 0.2 mg/day set by the U.S. Food and Drug Board of the National Research Council.

The most important evidence of Se poisoning in humans in terms of the people affected and the exposure time is an outbreak of endemic Se intoxication in China (79). An endemic disease occurred in 1961 in Enshi County, Hubei Province of the People's Republic of China. The highest occurrence of the disease was from 1961 to 1964. The morbidity was about 50 % in the 248 residents of the five most severely poisoned villages. Selenium poisoning was identified as the cause of the disease. The most common symptoms of the poisoning were loss of hair and nails. The hair became dry and brittle and was easily broken off at the scalp. The nails of patients also became brittle, followed by a break on the wall of the nail. Figure 9 shows the loss of nails of Se poisoned patients. Lesions of the skin, deteriorated teeth, and abnormal nervous system were also observed. Affected skin was red and swollen, and then blistered and eruptive. Mottled and erosive teeth were found among Se poisoned patients. Abnormalities of the nervous system were also reported. Peripheral anesthesia was the first symptom, then numbness, convulsions, paralysis, motor disturbance, and even hemiplegia. Selenium levels in the hair and blood of the selenosis patients were analyzed. The results showed an average hair Se content of about 100 times greater than that in Se-normal areas, and 400 times greater than that in the Keshan Disease area (Se-deficiency disease). Further analysis of Se contents in the foods showed that vegetables in that selenium poisoned area contained high levels of Se. The Se contents in cereals (which is the main traditional food stuff for local residents) were very high. Corn, rice, and soybeans grown on that area contained about 200, 100, and 150 times more Se than those in the Se-normal area; and 1500, 500, and 1000 times more than those in the Se-deficiency

Figure 9. Loss of nails of selenium poisoned patients in China.

Kashan Disease area, respectively. The average daily Se intake was 4.99 mg compared with that of 0.114 mg in the Se-normal area. The average Se concentration in local drinking water was 54 ug/L, which also contributed to the high level of Se intake for local residents. The ultimate environmental Se source in that Se-poisoned area was identified as coal with very high Se content, averaging more than 300 mg/kg. These high Se-containing coals released Se to the surrounding soils through weathering, leaching, and biological actions, and made it available to the plants and cereals, thus entering the food chain. The traditional use of lime as fertilizer in that area resulted in increase of soil pH favoring the oxidation of Se to selenate, which is subsequently taken up by plants.

Although food is the main route of Se exposure to humans, it also has to consider Se poisoning in humans from water source. Water consumption, for a long period of time, even in seleniferous areas of the western United States was not accepted as a potential Se poisoning source. However, one instance of Se poisoning in humans from an underground water source was reported by Beath. In that case, a family in Colorado developed Se poisoning symptoms after using, for 3 months, well water which contained 9 mg/L of Se. Since no Se was found in the food, the well water was suspected as the source for abnormally high level of Se which led to Se poisoning in man. The signs of the poisoning were identified as lassitude, loss of hair and nails, and discoloration, which were similar to symptoms identified in Hubei Province, China. Experiments were conducted to prove the source of Se toxicity by discontinuing the use of the well water. This resulted in regrowth of the hair and nails, and in time increased the mental alertness of the patients.

There are conflicting reports in the literature regarding Se toxicity

effect in human dental caries. Hadjimarkos (80) indicated that one of the toxic signs of excessive Se intake is an increase in dental caries. However, other studies proved either no relation or just weak correlation between Se intake and the incidence of dental caries (81). Moreover, the National Academy of Science (NAS) stated that low level of dietary Se causes dental caries (82). It seems that this subject needs further research before any conclusion can be made.

Perhaps the most controversial issue of selenium toxicity is its carcinogenicity. Earlier reports claimed that selenium is a carcinogen (83). Schroeder and Mitchener (84) suggested Se carcinogenicity only when Se is ingested at high levels. Some studies, however, found inverse correlation between the incidence of cancer and Se content in patients' blood (85). Some investigators believe that Se has anticancer effect (86). Demographic studies showed the existence of an inverse correlation between cancer mortality and Se contents using data collected from cancer patients' serum (85). The conclusion made by the United States Food and Drug Administration in 1974 (86) was that the use of Se in the nutritionally required levels represents no carcinogenic risk.

Since Se is recognized as one of the nutritional trace elements for humans, similar to the situation of excessive Se poisoning, extremely low level intakes of Se from food also have deleterious health effects on humans. This may also be considered as Se poisoning in the sense of environmental impact assessment.

The beneficial nutritional effect of Se was first identified in animals. After that, the role of Se in human nutrition was also established. The first humans Se-deficiency case found in the literature was in a patient in New Zealand, a low Se country (87). The symptom was bilateral muscular discomfort. After daily addition of 100 ug of Se as selenomethionine for a week, all muscle symptoms disappeared and full activity was restored. The concept that Selenium

deficiency would cause adverse health effects on humans is supported by evidence from the people's Republic of China where an endemic cardiomyopathy known as Keshan Disease has been connected with a low selenium status (88). The symptoms is characterized by heart enlargement, gallop rhythm, heart failure, arrhythmia, and cardiogenic shock. Children from one to nine years of age and women of child-bearing age were found to be susceptible to these symptoms. The patients had low contents of Se in their hair and blood. The daily average Se intake of Keshan Disease patients was just 11 ug compared with 116 ug in patients from Se-normal area. Selenium supplementation in children's diet have further proved the role of Se in the etiology of Keshan Disease and demonstrated that the Keshan disease is indeed a human Se-deficiency disease. Table 5 shows the effect of supplemental Se in the diet of patients suffering from Keshan Disease. The mortalities of Keshan Disease patients with placebo treatment in 1974 and 1975 were both 50 %, while the mortalities of the patients with selenium supplement treatment were 0 % and 14 %, respectively. It convinced the researchers that Se plays a critical role in the treatment of Keshan Disease. The significance and importance of Se-deficiency disease in humans have received official attention. The Food and Drug Board of the National Research Council in 1980 established selenium intakes in adults of 50 to 200 ug/day as a safe and adequate range.

2. In Aquatic Animals

Selenium released from coal mine spoils can also be transported to nearby rivers and lakes through runoff or erosion. Increased Se content in water may cause Se poisoning in fish and other waterfowl living and nesting in these aquatic systems. From this point of view, a brief review of Se poisoning in fish and waterfowl is a necessary step in understanding the environmental impact

Table 5. Effect of supplemental Se in the diet of Keshan Disease patients.

Treatment	Year	Subjects	Number of KD	Death
Placebo	1974	3,985	54	27
	1975	5,445	52	26
	1976	212	1	0
0.5-1.0 mg/wk (as sodium selenite)	1974	4,510	10	0
	1975	6,767	7	1
	1976	12,579	4	2
	1977	12,749	0	0

assessment of Se from coal mine spoils.

Many studies show that elevated Se concentration in water has a definite adverse effects on the life of fish. The severity of poisoning will intensify when Se content in water increases. The U.S. EPA (89) in 1980 established a selenium toxicology data base for freshwater aquatic organisms, which include invertebrate and fish. It consisted of acute Se poisoning measurements for eight fish species and five invertebrate species, and chronic Se poisoning measurements for two fish species and two invertebrate species. The selenium concentration in water that cause acute poisoning in fish ranges from 1,460 ppb for the Fathead minnow (Pimephales promelas) to 28,500 ppb for the Bluegill (Lepomis macrochirus). Such levels of Se usually can cause fish mortality. For some sensitive species, death would occur at Se concentration between 60 and 600 ppb (90). Most of these dead fish are in the early life history stages which are subjected to comparatively long exposure period.

After exposure to relatively high Se concentration, fish would have potentially latent acute mortality. For instance, Niimi and LaHam (91) reported that all embryos of the zebrafish (Brachydanio rerio) survived exposure to 3,000 ppb of Se during development, but more than 90 % of the resultant larvae died soon after hatching. The U.S. EPA (92) suggested that selenite is more toxic to fish than selenate. Stephen B.M. (91) consider organic forms of Se in the diet to be more toxic to fish. In fact, Se poisoning effects are determined by some factors, such as different chemical forms of Se, fish species, duration of exposure, water quality, method of uptake, and other factors. Acute Se poisoning in fish has the following signs: lethargy, muscle spasms, protruding eyes, swollen abdomen, liver degeneration, reduction in blood hemoglobin and erythrocyte number, increase in white blood cells, histopathology of kidney and heart, swollen gill lamellae with extensive cellular vacuolization, and necrotic and degenerating ovarian follicles (92).

According to the EPA (90) data base, chronic Se poisoning concentration in fish is 88 ppb for rainbow trout (Salmo gairdneri) and 113 ppb for Fathead minnow (Pimephales promelas). Laboratory studies and field investigations with fish show that elevated concentrations of Se in diet or water will cause impaired reproduction, reduced rate of growth and survival of young, and teratogenicity. For example, in a lake in North Carolina which receives Se as fly ash from a

coal-fired power station, it was found that the reproduction ability of green sunfish failed, resulting in marked population decline. In these fish, Se levels were higher in the liver, kidney, and the heart; their liver, and gills showed histopathology. Ovaries of affected fish had many necrotic and ruptured egg follicles and contributed to the overall decline of fish population (93). It is likely that Se was first taken up by plankton, then was introduced into the food chain where it finally reached elevated levels in fish through biomagnification. In frogs, cranial and vertebral deformities were found and the survival rates were low when development occurred in water containing 2,000 ppb of Se (94). At water concentration of 47 to 53 ppb Se, toxicity was associated with anemia and reduced hatch in rainbow trout (Salmo gairdneri). At 250 ppb of Se, growth of rainbow trout fry was reduced after exposure for 21 days, and goldfish showed an avoidance response after 48 hours exposure (95). It was evidenced that Se is the causative agent for reduced fish population in cooling reservoirs of coal-fired power plants (96).

Selenium has also adverse effects on waterfowl. High level of Se was associated with decreased egg weight and production, decreased hatchability, anemia; elevated Se residues in the kidney and liver; and high incidence of embryo deformation with missing or distorted eyes, beaks, wings, legs, and feet (97). Figure 10 shows the abnormal black-necked stilt embryos from eggs collected at Kesterson Reservoir. Studies in the San Joaquin Valley, California, have confirmed that Se toxicity affects aquatic birds (98). Severe reproductive effects on ducks (Anas), American coot (Fulica americana), and other species of aquatic birds nesting at irrigation drainwater ponds are reported. Water in these ponds had unusually high Se concentration of about 300 ppb. In addition, anomalies in brain, heart, liver, and skeleton were also found. Studies at Patuxent Wildlife Research Center (99) show that ducks given diets containing 100 ppm of inorganic selenite usually died within a month; before death, ducks showed reduced food intakes and weight loss. In birds receiving 25 ppm Se, growth and reproduction were dramatically retardated. There were evidences of teratogenic effects at 3 months in ducklings of mallards receiving 10 ppm Se.

Figure 10. Black-necked Stilt Embryos from Eggs Collected at Kesterson Reservoir.

3. In Plants and Farm Animals

Toxicity of Se to plants growing under natural conditions has not been reported, but symptoms of Se toxicity to crop plants have been described. Also, a decrease in yield of several crops was affected by the application of about 2 ppm Se into the soil (99). Increased Se levels in plants suppresses concentrations of N, P & S as well as several amino acids. So far, there is no evidence that Se is an essential element for the plants. Selenium deficient crops seem to occur intensely farmed humid areas on strongly leached soils.

Food constitutes the major route of human exposure to environmental Se in the general population. Estimates of adult exposure to environmental Se, generally, fall in the range of 20 - 300 ug/day. There is a very wide range of natural intake of dietary Se in different parts of the world. The Se compounds that may be encountered are Se dust and Selenium dioxide. The Grasslands of western Meced County, California, contain more than 30,000 hectares of seasonal and permanent wetlands in an area of largely native Grassland vegetation. This area comprises the largest tract of waterfowl habitat in the San Joaquin Valley and is also an important wintering area for waterfowl of pacific flyway. About two thirds of grasslands are located west of the San Joaquin River. Of this area, 20600 hectares are in the Grassland water District, 90% of which consists of Wetlands operated as private hunting clubs (100).

Subsurface agricultural drainage has been the sole source of water for Kesterson National Wildlife refuge. During 1983 to 85, aquatic birds nesting at Kesterson experienced poor reproductive success. The cause of this problem is considered to be exceptionally high concentrations of Se present in water and food chain organisms (101). Figures 11 & 12 show areas of USA where Se concentration in plants is less than 0.1 mg/kg and where Se deficiency disorders are likely to occur in livestock and poultry. Distribution of seleniferous vegetation in western USA and Canada is illustrated in figure 7. Each open dot represents the place of collection of a plant specimen containing 50-500 mg Se/Kg. Vertical lines, x's and solid dots indicate counties where more than one half of the crops sampled contained <0.1 , >0.1 , or where Se accumulator plants contained >50 mg Se/kg, respectively.

It has been found that Se concentrations are higher in sedimentary rocks

Figure 11. Distribution of Seleniferous Vegetation in the Western U.S.A. and Canada.

Figure 12. Location and Classification of Counties in the U.S.A. Where Plants Were Collected for Selenium Analysis.

where it is associated with the clay fraction, and thus, larger concentrations are found in shales and in limestones or sandstones. Even in shales, the concentrations are seldom >500 mg Se/kg. Values range from <1 to nearly 300 mg Se/kg in cretaceous black shales in Wyoming (102). Soils developed from the cretaceous shales of South Dakota, Montana, Wyoming, Nebraska, Kansas, Utah, Colorado and New Mexico tend to have high Se values. It is in these areas that natural Se toxicosis has occurred (103). Figure 13 shows parts of North America which contain insufficient Se to meet the minimal animal nutritional needs.

Selenium released from coal mine spoils could enter the environment through erosion or runoff, and may be taken up by plants growing on the surrounding soils. Selenium poisoning is likely to occur in animals grazing on seleniferous forages, such as grasses and shrubs. Thus, identification of Se poisoning in grazing animals, particularly in cattle, is of practical importance in the environmental impact assessment of Se from coal mine spoils.

Two types of selenium poisoning have been identified, acute and chronic. Acute Se poisoning is the result of ingestion of excessive amounts of plants containing high levels of Se in a short period of time. The plants involved in acute Se poisoning usually contain 400 to 800 ppm Se (104). Acute Se poisoning in domestic livestock is characterized by abnormal movements, lowered head, drooped ears, diarrhea, elevated temperature, rapid pulse, labored breathing, bloating with abdominal pain, increased urination, prostration, and death (105). Duration of poisoning can be from a few hours to several days, depending on the toxicity of the ingested plant. Cattle is the most common victim of acute Se poisoning, sheep and horses can also be poisoned (105). In fact, acute Se poisoning is rare to happen and seems less important than chronic poisoning because plants containing high amounts of Se are usually unpalatable, animals tend to avoid these types of plants.

Chronic Se poisoning can be divided into two syndromes: alkali disease and blind staggers. Alkali disease is caused by the ingestion of seleniferous forages and feed crops over a period of time. In alkali disease, selenium is bound to proteins and it is relatively insoluble in water. The symptoms include anemia, lameness, emaciation, lack of vitality, dullness, loss of hair, deformation and sloughing of hoof, and reduced reproductive ability (106).

■ $< 0.03 \text{ mg Se kg}^{-1}$

▨ $0.08 \text{ mg Se kg}^{-1}$

▤ $0.05 \text{ mg Se kg}^{-1}$

□ $0.26 \text{ mg Se kg}^{-1}$

Figure 13. Selenium Level in Forage Crops of the U.S.A.

Cattle, horses, and swine are the most common victims of alkali disease. Figure 14 shows a picture of congenital alkali disease in a 14-day-old colt born of a mare that became alkaliied during gestation. It has been postulated that Se displaces sulfur in keratin, resulting in structural changes in hair, nails, and hooves (107).

Blind staggers is another type of chronic Se poisoning. It is the result of consumption of limited amounts of indicator plants over a period of weeks or months. The species of Se involved in this type of chronic poisoning are water-soluble selenium compounds (106). Cattle and sheep are common victims of blind staggers. There usually are three stages in the development of blind stagger symptoms. In Stage 1, the animal wanders, stumbles over objects in its path, shows no or little desire for food or water, has vision impairment. In Stage 2, the symptoms developed in Stage 1 are intensified, usually with increasing weakness in the front legs. Stage 3 is a paralytic stage; the mechanism of tongue and swallowing become paralyzed partially or totally. There is a varying degree of blindness associated with this stage, signs of respiratory failure, abdominal pain, grinding of the teeth, excessive salivation, sudden collapse, and finally death (106).

Although toxic effects of Se have been recognized by people much earlier than its nutritional effects, selenium deficiency may also occur in livestock with equal health results. White muscle disease is the most common Se-deficiency disease (107). Cattle is also subject to this type of disease. The signs of white muscle disease are skeletal weakness, calcification, degeneration of skeletal muscle and myocardium, slow growth, and lowered reproductive ability (106). New born or rapidly growing lambs, calves, and pigs are subject to sudden death due to weakness of the heart muscle. In this situation, Se released from coal mine spoils may become a nutritional supplement to the grazing animals in the surrounding Se-deficient areas. This possibility should be taken into account when discussing the issue of Se poisoning in cattle and other animals.

F. REGULATIONS ON SELENIUM POLLUTION

Selenium is a micronutrient which is essential for animals and humans. However, at high concentrations, it is toxic. Its adverse and beneficial effects

Figure 14. A picture of congenital alkali disease in 14-day-old colt.

depend on the amount ingested. In order to control the element properly, some rules and regulations regarding Se poisoning have been promulgated by regulatory agencies. Knowledge and understanding of these rules and regulations are desirable since one of the major concerns in assessment of selenium impacts is the question of whether any related standards will be exceeded. These regulations will provide a useful guideline in the process of environmental impact assessment of Se from coal mine spoils.

1. Drinking Water Standards

The United States Public Health Service (USPHS) in 1942 established the maximum level of Se in drinking water to be 0.05 mg/L. However, due to the growing concern on the possible carcinogenic properties of Se, the standard was re-evaluated and the USPHS lowered the limit to 0.01 mg/L in the 1962 revised PHS standard. The Safe Drinking Water Act of 1974 (Public Law 93-523) mandated the U.S. Environmental Protection Agency to establish drinking water standards for all public water systems serving more than 25 people. In 1976, the U.S. EPA (40 FR 248 59566) established 0.01 mg/L as maximum contamination level (MCL) for Se in drinking water in its National Interim Primary Drinking Water Regulations (NIPDWR) which went into effect in June of 1977. Prior to that, the World Health Organization (WHO) has set minimum standards for drinking water that all nations were urged to meet. In 1958, WHO International set 0.05 mg/L as the maximum limit for Se in drinking water. Also, in 1960, WHO European set 0.05 mg/L as a tolerance limit of Se in drinking water. It is apparent that the 1976 U.S. EPA standard of 0.01 mg/L set for Se was much more stringent than that of WHO's standards. The National Academy of Science (NAS) made a report on the adequacy of the Se MCL on NIPDWR. It stated that "most evidence indicates that there is a greater overall potential for selenium deficiency than for selenium toxicity at current levels of selenium intake." It also states that "The no-observed-adverse-health effect for selenium in water is at least 100 ug/L and appears to be as great as 500 ug/L."

2. Surface Water Standards

The U.S. EPA in 1975 established the maximum permissible concentrations of inorganic chemicals in irrigation waters based on two standards. One standard refers to a maximum concentration for continuous use in all soils and the other standard calls for a maximum concentration for 20 years in fine textures soils (pH 6.0-8.5). In both standards, Se concentrations were set as 0.02 mg/L.

Standards for selenium in surface water have been promulgated in several forms. A common form is the narrative standard which states that no toxic substance may exist in surface water in concentrations that will have adverse impact on the environment. Selenium is never specified by name in such statements, but is just implicitly considered as a toxicant. As can be seen from Table 6, most states use this type of narrative standards. Only a few states use specific numeric standards for Se. The common numeric value, 0.01 mg/L, is the same maximum concentration allowed by Federal Law in finished drinking water. Oklahoma, like most other states, uses a narrative standard for Se in surface water. California State specifies separate numeric standards for irrigation water (0.02 mg/L) and water used for livestock (0.05 mg/L).

3. Ambient Water Quality Criteria

In 1986, Ambient Water Quality Criteria for Selenium was established by U.S. EPA. To protect freshwater aquatic organisms and their uses, the four-day average concentration of selenium should not exceed 5.0 ug/L more than once every three years on the average and the one-hour average concentration of selenium should not exceed 20 ug/L more than once every three years on the average. To protect saltwater aquatic organisms and their uses, the four-day average concentration of selenium should not exceed 71ug/L more than once every three years on the average and the one-hour average concentration should not exceed 300 ug/L more than once every three years on the average (108). It should be noted that a water quality criterion has regulatory impact only after it has been adopted in a state water quality standard. The water quality standards of the State of Oklahoma recognized a selenium synergistic effect with other materials. It stated that " The following materials may have synergistic effects: ammonia,

Table 6. Surface Water Quality Standards for Selenium, by State. (compiled from Ronald C. Flemal et al., 1977)

State	Standard	Water Use *
Alabama	Narrative	GU/PWS
Alaska	Narrative	GU/PWS
Arizona	0.01 mg/L PWS; Narrative, GU	GU/PWS
Arkansas	0.01 of 96 hr median toxic limit	GU/PWS
California	0.01 mg/; (.05 livestock;.02 irrig.)	PWS
Colorado	Narrative	GU
Connecticut	Narrative	GU/PWS
Delaware	Narrative	GU
Florida	Narrative	GU/PWS
Georgia	Narrative	GU/PWS
Hawaii	Narrative	GU/PWS
Idaho	Narrative	GU
Illinois	1.0 mg/L, GU; .01 mg/L, PWS.	GU/PWS
Indiana	Narrative	PWS
Iowa	1.0 mg/L, GU; 0.01 mg/L, PWS.	GU/PWS
Kansas	Narrative	GU/PWS
Kentucky	0.01 mg/L	PWS
Louisiana	Narrative	GU
Maine	Narrative	GU/PWS
Maryland	None	
Massachusetts	Narrative	GU/PWS
Michigan	Narrative	GU
Minnesota	0.01 mg/L	PWS/I
Mississippi	0.01 mg/L	PWS/GU
Missouri	Narrative	GU/PWS
Montana	Narrative	GU/PWS/I
Nebraska	Narrative	GU/PWS
Nevada	Narrative	GU/PWS
New Hampshire	Narrative	GU/PWS
New Jersey	0.01 mg/L and Narrative	GU/PWS/I
New Mexico	Narrative	VAR
New York	Narrative	GU
North Carolina	Narrative	GU/PWS
North Dakota	0.01 mg/L	GU/PWS
Ohio	0.005 mg/L	GU/PWS/I
Oklahoma	Narrative	

(Table 6 Continued)

Oregon	Narrative	VAR
Pennsylvania	Narrative	VAR
Rhode Island	Narrative	GU/PWS/I
South Carolina	Narrative	GU/PWS/I
South Dakota	None	
Tennessee	Narrative	GU/PWS/I
Texas	Narrative	GU/PWS
Utah	Narrative	GU/PWS/I
Vermont	Narrative	GU/PWS
Virginia	0.01 mg/L	GU/PWS
Washington	Narrative	GU/PWS/I
West Virginia	0.01 mg/L and Narrative	GU/PWS
Wisconsin	Narrative	GU/PWS
Wyoming	Narrative	GU/PWS

* GU: General Use
PWS: Public Water Supply
VAR: Standards vary with water body
I: Industrial uses.

cadmium, hexavalent chromium, trivalent chromium, copper, cyanide, lead, mercury, nickel, selenium, silver, and zinc. These substances shall not be present in sufficient concentration to allow the cumulative relationship value to exceed the numerical value of one." (109).

4. Effluent Standards

The Water Pollution Control Act of 1972 (Public Law 92-500) mandated the Environmental Protection Agency to establish standards for wastewater discharges. Current standards require that, as a minimum, all municipal wastewater be treated to secondary standards in which no specific data was set for Se concentration. Only two states, Illinois (1.0 mg/L) and Delaware (0.020 mg/L), have specified numeric standards for selenium in waste water effluent (110). Connecticut State uses best available technology (BAT) as a standard. The British Government had effluent standards for discharge of wastewater in which Se maximum concentration is set at 0.05 mg/L. The monthly average over any 4 weeks is 0.02 mg/L (70). These limit concentrations could be used as a reference in the U.S.A.

5. Industry Effluent Limitation Guidelines

Also, under the authority of public law 92-500, the U.S. EPA has promulgated industry effluent limitation guidelines. The guidelines were developed on the basis of both Best Practicable Control Technology Currently Available (BPCTCA) and Best Available Technology Economically Achievable (BATEA). Selenium is considered as a major pollutant in four out of more than 400 industrial subcategories. Table 7 lists the guidelines for selenium in four industrial subcategories.

6. Hazardous Threshold Level

Selenium has been included in 1976 EPA's list of priority pollutants (111). Also, Se is identified under the Resource Conservation and Recovery Act (RCRA) as a hazardous waste with EPA hazardous waste No.D010. The U.S. EPA has set regulatory toxicity threshold levels for some contaminants. Any waste that

Table 7. U.S. EPA Industrial Effluent Guidelines for Se, mg/L.

Subcategory		BPCTCA Category		BATEA Category	
		Avg*	Max**	Avg*	Max**
Inorganic Chemical	Copper Sulfate 40 CFR 415.360	0.5	1.6	nd	nd
Nonferrous Metals	Primary Copper Smelting 40 CFR 421.40	5.0	10.0	5.0	10.0
Nonferrous Metals	Primary Copper Refining 40 CFR 421.50	5.0	10.0	5.0	10.0
Nonferrous Metals	Primary Zinc 40 CFR 421.80	5.0	10.0	5.0	10.0

* Thirty-day average, in mg/L

** Twenty-four maximum, in mg/L

nd: no data

exceeded the set toxicity threshold levels is considered hazardous. The threshold level set for Se is 1.0 mg/L.

7. Recommended Dietary Allowance

The Food and Drug Administration (38 FR 81 8229) has stated that sodium selenite or sodium selenate can be used as food additive for selenium deficiency. To the complete feed for swine and chickens up to 16 weeks of age, the Se level should not exceed 0.1 ppm, and for turkeys the Se level should not exceed 0.2 ppm.

Recommended Dietary Allowances (RDA) has been prepared by the Food and Nutrition Board of the National Academy of Science since 1941. The RDA are the levels of intake of essential nutrients that, on the basis of scientific knowledge, are judged by the Food and Nutrition Board to be adequate to meet the known nutrient needs of all healthy persons. In the eighth edition of RDA (1974), it stated that "very little is known about a human requirement for selenium,..... a recommended daily allowance cannot be established yet." This statement reflects a fact that only limited data on Se health effects on humans was available at that time. Standards have evolved over the following years as people's knowledge about the nature and health effects of Se on humans has grown. In the ninth edition of RDA (1980), it stated that "selenium must be essential for man as well....., a range of 50 to 200 ug/day is suggested as adequate and safe for adults." As more is learned about the Se health effect on humans in the following 9 years, the RDA of selenium, established for the first time in its 10th edition of 1989, are based on recent studies of Chinese men. In the 10th edition, the RDA of selenium in adults is set at 70 ug/day for men and 55 ug/day for women. The RDA of infants, children, and adolescents are extrapolated from adult values on the basis of body weight, and an arbitrary factor is added for growth.

SECTION III

SITE SELECTION AND EQUIPMENT SETUP

The investigation site chosen for this study is an abandoned strip mine consisting of several pits from which coal was once mined. Steep, narrow ridges line the pits where raw clay and shale were piled during mining operations. The pits have been filled with rain and run-off water. The surrounding area is not suitable for cultivation and is generally heavily wooded. The soils are recognized as unsuitable due to unfavorable texture; poor to somewhat excessive drainage; shallowness; medium to high waterholding capacity; and restricted root zone. Mining pits on both sides of Trudgeon Road have been partially reclaimed by the Oklahoma Department of Conservation. It is our understanding that reclamation was done by filling in the mining pit with spoil, compacted and subsequently covered with six inches of topsoil. The reclamation was initiated since Trudgeon Road in that vicinity was considered a driving hazard. The reclamation project was completed about three years ago. The reclaimed land had been seeded with grasses, but the stand of grasses seems poor. Casual observation indicates the topsoil has been eroded to less than two inches in some locations. Evidence of adverse erosion is also evident near the investigation site.

The site is located near Henryetta, Oklahoma, eighty-six miles east of Oklahoma City along Interstate 40. Once in Henryetta, one can arrive at the study site by traveling east of the intersection of Highway 75/62 and Trudgeon Road. It is 0.88 km from the intersection of Trudgeon Road to a graveled entrance to 141 acres of privately-owned property. Figure 15 outlines the coal-producing areas of Oklahoma and identifies the Henryetta area. Figure 16 is a road map of Okmulgee County and Henryetta. Figure 17 is a drawing that gives the legal description of the property with respect to Henryetta. Eighty-three acres of this property was accessible for mining operations. Figure 18 identifies the legal description of the property by special code which also will identify samples and measurements by code number.

The study area is 0.64 km north of Trudgeon Road and is described as mine

Figure 15. The Coal Producing Areas of Northeastern Oklahoma.

Figure 16. A Road Map of Oklahoma County, Oklahoma.

Figure 17. A Map Showing the Location of the Experimental Site.

Figure 18. Legal Description for the location of the Sampling Site.

spoils (Sm) by the Okmulgee County Soil Survey book. The property is in T.11N., R.13E., Section 8 (Figure 18). For the investigator's, it is worth noting Lake Henryetta to the southeast and Lake Eufala to the east of Henryetta. It is not that the selected field site poses any potential environmental hazard, but that proposed mining sites could potentially affect large surface impoundments. The coal mining operation on the field site was abandoned in the early 1950's (Mrs. Marler, Study Site Owner, personal communication, 1990). The study site was selected because it fulfilled the following criteria: (i) it consists of reclaimed mining land, spoils, and unmined areas (control); (ii) at least 45 years has elapsed since cessation of mining operations allowing time for mineral migration to equilibrate; and (iii) three years have elapsed since reclamation was completed also allowing time for equilibration of the soil environment from reclamation activity.

The method for describing the location of a data-collection site is a partial legal description with an identification number added to provide a local number for each site. By this method, the location of the site is given as SW1/4 NE1/4, Sec 8, T.11N., R.13E. followed with an identification number. SW1/4 NE1/4, Sec 8 is replaced with alphabetic characters. The three selected data collection sites will be identified as

11N-13E-8 BC CON (1-9)

11N-13E-8 BC SPO (1-9)

11N-13E-8 BC REC (1-9)

where CON (1-9), SPO (1-9), and REC (1-9) describe one of nine data stations at each site. The three sites will be identified as CON (control), SPO (mine spoils) and REC (reclaimed land).

A. LYSIMETER SETUP

1. Construction of the Eh Electrode

The platinum electrode was constructed as follows: a 2.2 cm, 18 gauge platinum wire was soldered to a Type RG-58U copper wire and cable from Radio

Shack. Nine electrodes measuring 46 cm in length, nine 107 cm in length and nine 168 cm in length were attached to solderless BNC connectors containing the RG-58 coax cable. The connectors were adapted for use on the Fisher pH/MV/temperature meter. The reference electrode is a calomel electrode (catalog number 13-620-259) manufactured by Fisher Scientific. The calomel reference electrode attaches to the pH/MV meter by a pin jack. The complete assembly (Figure 19) for each platinum electrode, not only consists of solder 0.2 cm of platinum to the copper wire, but uses 3/32 inch shrink tubing ordered from Alpha Wire Corporation (Elizabeth, New Jersey) sealed around the solder joint to protect the connection from moisture and any subsequent corrosion. The coax cable end with the solder connection is inserted through a 1/4 inch hole drilled through a 5/8 inch dowel rod 7/8 inch in length. The platinum wire extends 2.0 cm beyond the dowel rod. The entire length of cable is pushed through 1/2 inch PVC Schedule 40 tubing. The dowel rod "plug" is glued with Elmer's^R wood glue into the end of the PVC tubing. Each PVC tube used in the construction of the platinum electrodes is filled with paraffin wax to keep air and moisture from the electrode wire and connection. A second dowel rod "plug" is inserted at the top end of the PVC tube to seal the tube and support the coax cable. Appropriately sized PVC connections with 50 cm lengths of 3/4 PVC were employed to design a protective cap for the platinum electrode. When Eh measurements are taken the protective cap can easily be removed from the 1/2 PVC to expose a 16 cm length of coax cable with BNC connectors. The reference electrodes are inserted through 3/4 inch PVC at the same depth (30, 90 or 150 $\pm$ 2 cm as the platinum electrodes).

2. Soil Moisture, pH, Temperature, Eh, and Air Measurement

The field parameters measured in the site investigation include (i) Eh, (ii) soil pH, (iii) soil moisture and (iv) soil temperature with the ambient air temperature. The three study areas (spoil, reclaimed and control) are identified at the site on a dated aerial photograph (Figure 20). The aerial photograph is prior to any reclamation. Trudgeon Road is east/west or left to right across the center. The larger mining sites along Trudgeon Road have since been reclaimed. On the photograph, the field sites are marked C, control; S, spoils; and R, reclaimed. Each field site will have nine platinum electrodes installed, each

Figure 19. An illustration for the design and construction of the platinum electrode which is used with a calomel reference electrode to measure Eh in a subsurface environment.

Figure 20. An Aerial Photograph of the Study Site.

accompanied with a calomel reference electrode access tube; nine soil gas access tubes; and nine tensiometers (Figure 21). At each study area (spoils, reclaimed or control), three electrode combinations (platinum and reference), gas access tubes and tensiometers were installed at depths of 30 cm, 91 cm and 152 cm, respectively. During sampling, Eh measurement (in millivolts) were taken using a platinum electrode connected to a Fisher Accemet Model 955 Portable pH/MV Temperature Meter.

Soil moisture is measured using tensiometers from Soil Moisture Equipment Corporation (Santa Barbara, California). The 2725 series Jet Fill Tensiometer (Figure 22) is used to measure soil moisture potential at designated depths in the subsurface. Soil moisture is measured in centibars. Flooded or ponded conditions contribute to reducing conditions which support the transformation of selenate to selenite, the less soluble or less mobile form (Long, et al., 1990).

Soil pH was measured in the field by removing a soil sample from the same depths as are the air access tubes and electrodes. Samples were saturated with deionized water at an approximate volume ratio of 1:1. The pH was measured with a Fisher Accemet Model 955 Portable pH/MV Temperature Meter immediately upon return to the laboratory. After 72 hours the pH was again recorded. Also, pH was measured using air-dried, <2mm soil fractions. 10g of air-dry soil is placed into a 25-ml plastic beaker. 10 ml of deionized water is added to the soil fraction. The soil solution is stirred and left to settle for 30 minutes. pH readings are taken from the clear supernatant.

Soil temperature was taken by placing a Celsius thermometer in selected reference electrode access tubes representative of each depth. Ambient temperature taken 3 ft above the ground surface was also recorded at each study site.

Soil gas samples (oxygen and carbon dioxide) are taken using medical vacutainers with needles and 10 ml blood collection tubes. The needles inserted through a septum screw cap on top of the 1/2 in PVC tube which is used as an air access tube. The vacutainer withdraws approximately 10 ml of soil air. After a preselected equilibrium time, the vacutainer is removed and placed in a cooler containing dry ice. The concentration of oxygen and carbon dioxide in the soil air is determined with a gas chromatograph equipped with thermal conductivity

(a)

(b)

Figure 2L Graphical description of the coal mining area with locations of the soil air tubes, Pt electrodes, tensiometers and calomel reference electrode access tubes used for the field study. (a) A distribution of the electrodes and access tubes for each site. (b) A graphical description of the electrodes and access tubes installed at varying depths.

Figure 22. Diagram of the Jet Fill Tensiometer.

detector. Unfortunately all samples (sampled periodically) showed similar levels of the two gases as found in the ambient atmosphere. Therefore, no data is tabulated with this report.

3. Sampling and Analysis of Spoils and Soils

The objectives of the field and laboratory investigations are to evaluate (i) the migration characteristics of SeO_3^{2-} and SeO_4^{2-} through a soil mini-column affected by pH and Se concentration, (ii) the Se transformation in coal mine spoils as affected by controlled pH and oxidation-reduction potential and (iii) some environmental limitations for Se speciation at a mining site.

Soil samples from the site were collected periodically at depths of 1 foot (30 cm), 3 feet (91 cm) and 5 feet (152 cm) from control, reclaimed and mine spoil sites. A power auger with a six-inch auger was used to sample from the appropriate depths at each site. A Hoffer tube was used to remove soil samples from the appropriate depth. Approximately 300 grams of wet soil was removed from each bore hole. Samples were placed in Ziploc[®] plastic bags and transported to the laboratory. Upon arrival, the samples were placed in plastic pans and air-dried. Soils were then mechanically ground and sieved, passing through a No. 10 sieve. The air-dried and <2 mm soil fraction from each is kept in Ziploc[®] plastic bags until needed for subsequent experiments. Replacement samples will be obtained from the field site as needed.

Selected soil samples were analyzed for both SeO_3^{2-} and SeO_4^{2-} concentration and total Se. Digested samples were used to determine total selenium on a Model 951 Instrumentation Laboratory aa/ae Spectrophotometer equipped with a graphite furnace. Undigested water samples were analyzed for SeO_3^{2-} and SeO_4^{2-} using DIONEX AI-450 Ion Chromatograph with the DIONEX conductivity and variable wavelength detectors.

B. DATA COLLECTION

Data collection from the field included soil, spoil, air, temperature, moisture, Eh, and pH. The sampling stations included a spoil, a reclaimed, and a control site. The aforementioned parameters were measured from each site.

Soil samples from the site were collected periodically at depths of 1 ft (30 cm), 3 ft (91 cm), and 5 ft (152 cm). A power auger with dimensions of six-inch in diameter and six-feet in length was used to drill the ground at appropriate depths in each site. A Hoffer tube was used to remove spoil and/or soil samples from each depth. Approximately 300 g of wet soil or spoil sample was removed from each bore hole. Samples were placed in ziploc plastic bags and transported to the laboratory where they were prepared for various experiments. Details of sampling of other parameters are given under III A.2.

For the first three months after the installation of the lysimeter, samples from the study site were collected every two weeks. However, when analyzed data showed no variation within the two weeks sampling period, samples were collected every month. Field data were recorded in hard cover logbooks at the site. At the end of each collection period, the data is manually transferred into a computer database which tabulates it into a format presented in Appendix A.

SECTION IV

GROUNDWATER AND SOIL SAMPLING

The objective of sampling is to collect a portion of material small enough in volume to be transported conveniently and handled in the laboratory while still accurately representing the material being sampled. This implies that the relative concentrations of all pertinent components will be the same in the samples as it is in the material from which the sample was taken. Every effort was taken to get samples that are representative of the actual field conditions. One basic strategy included attempting to reaching the middle portion of each county in Oklahoma. Such a strategy was sought to enable uniform distribution of the sampling sites on the map. Samples were taken from agricultural fields as well as nearby homes. Distance from well, fertilizer application, and other soil amendments were given due consideration.

1. Groundwater

Borosilicate brown glass containers were used to accomplish this task. Sampling was achieved only after the wells were pumped sufficiently to insure that the sample represents the groundwater source. In order to avoid any kind of contamination, the containers were cleaned with a metal free non-ionic detergent solution, rinsed with tap water, soaked in (1:1) Nitric acid and then rinsed with metal free water. Chromic acid was used to remove organic deposits from the containers. All containers were then rinsed several times with deionised water to remove any residual chromium. Water to be sampled was allowed to run for a while before samples were taken. Every effort was done to reach as close to the source of the water as possible in order to avoid any contamination during transport through hose pipes etc. Immediately after sampling, water samples were kept in ice chest and then transferred to the refrigerator. Bottles were completely filled with water in order to avoid oxidation.

2. Soil

Selection of the sampling sites was based on the proximity to the well which was also sampled for water. Prior to taking soil samples, the grass cover was removed with a shovel. Then, the ground was dug to a depth of about six inches with either a shovel or a pick ax. Grass roots were shaken off and discarded. About one kilogram of the moist soil is scooped and placed in a zip-lock plastic bag. The sample was labeled with proper identification and taken to the laboratory.

3. Problems Encountered

Access to some of the wells were denied by the property owners while some were declared contaminated by nearby producing oil wells. At times, chosen water wells were found unoperable due to mechanical failures. On few occasions, upon arrival at the site, it was realized that the wells had caved in and inaccessible for sampling.

SECTION V

SAMPLE PREPARATION AND ANALYSIS

1. Digestion of Water, Spoil and Soil Samples

Water samples were mixed by inverting the brown bottles several times. Fifty milliliter samples were pipeted and placed in 100 ml digestion tubes. Samples were acidified by adding 5 ml concentrated nitric acid. Two glass rods were put in each tube containing the sample and placed in a Tecator Digestion Block. The sample was heated gradually to a gentle boil. When approximately 10 ml of the sample remained, another 5 ml nitric acid and 5 ml sulfuric acid were added. The temperature of the digester was increased to 150 °C and maintained for about two hours. Then, the sample was removed from the digester and cooled. More nitric acid (10 ml) was added and heated for additional one hour at 350 °C. The appearance of a white fume indicated a completion of the digestion process. At this time, the sample was removed from the digestion block, cooled, and diluted to the 100 ml mark with 18 megahom deionized water. It was then filtered and kept in properly labeled polyethylene bottles until analysis.

Soil and spoil samples were digested in a similar manner. A 1.0 g soil or spoil sample was placed in the digestion tube to which was added 5 ml nitric acid and 5 ml sulfuric acid. In each tube two glass rods were placed to facilitate uniform boiling. The tube was then placed in a Tecator Digester and digested as described above.

2. Atomic Absorption Procedure for Total Selenium Analysis

The Model 951 Instrumentation Laboratory aa/ae Spectrophotometer equipped with a graphite furnace was used for analysis of digested water and soil samples. The following operational parameters were employed: bandwidth - 2.0; wavelength - 196.0 nm; voltage setting - 700 v; current - 7 ma; injection delay - 7 sec; deposit time - 10 sec, and; temperature settings - 149°, 508°, 620° and 2550°. The integration was with peak height at 4.0 sec. One ml of each digested sample

was diluted to 10-ml using a volumetric flask with 1 ml of 100 ppm Ni, 0.1 ml of 1:1 HNO_3 and DI water. Nickel was used as an interference matrix and the solutions were prepared from Ni reference solution, Fisher certified (cat. no. SN70-500) with the Ni as $\text{Ni}(\text{NO}_3)_2$. Standards were made from Se reference solution, Fisher certified (cat. no. SS460-500) with the Se as SeO_2 . The nitric acid used was reagent ACS grade from Fisher Scientific. The standards prepared for total Se analysis were 0 ppb (blank), 10 ppb, 20 ppb, 40 ppb and 50 ppb. Each standard Se solution was prepared using 100-ml volumetric flasks to which had been added 10-ml of 100 ppm Ni and 1-ml of 1:1 HNO_3 .

3. Ion Chromatography for Selenite and Selenate Analysis

There are vast range of technologies for determining $\text{Se}(+\text{IV})$, such as fluorometry, electron capture and gas chromatography, hydride generation atomic absorption, and x-ray fluorescence. However, none of these procedures are straight forward. Most of them require organic solvent extractions and preconcentration to lower the detection limit. An alternative technique is the use of ion chromatography with conductivity and variable wavelength detectors which can separate soluble Se species (selenate and selenite) and enable their quantitation. Refinement of the method is, however, required to achieve adequate sensitivity to detect Se species at the $\mu\text{g/L}$ level and to eliminate interferences from other anions.

Ion chromatography is an accurate, rapid method for the analysis of Se species when the concentrations of nitrate and sulfate are low enough not to interfere. Figures 23 and 24 show the extent of interferences by 100 ppm nitrate, on 10 ppm selenite and 100 ppm sulfate on 5 ppm selenate, respectively. Groundwater supplies, specially those near agricultural areas, normally contain high levels of sulfate and nitrate. Both of these anions come from applied fertilizers and are highly mobile in the soil environment. In typical groundwater, the level of these interfering anions are too high to allow detection of selenite or selenate without chemical pretreatment.

Addition of barium hydroxide on equivalent basis successfully reduced sulfate interference on selenate by precipitating out the sulfate. At this equivalent level, sulfate did not co-precipitate with selenate. Although the pH

Figure 23. Ion Chromatogram Showing the Effects of 100 ppm nitrate and 100 ppm sulfate on the resolution of selenite and selenate.

Figure 24. Ion Chromatogram Showing the Effect of 1000 ppm sulfate on the Resolution of 5 ppm selenate.

of the resulting solution had to be adjusted before analysis with ion chromatography, it did not seem to affect the speciation of selenium. An equilibration time of one hour before centrifugation was enough to precipitate out most of the sulfate. The use of barium carbonate did not precipitate sulfate effectively. Another technique that was used to solve sulfate interference was by applying variable wavelength detection. Since sulfate is not chromophoric, it does not absorb UV light, therefore, it cannot be detected. Unfortunately there is no similar pretreatment technique that can be used to remove nitrate interference on selenite. Selenite like nitrate is highly chromophoric and can be analyzed by UV detection with greater sensitivity than by conductivity detection.

Since adequate resolution between the selenate and sulfate peaks was not achieved by varying instrumental parameters, the next step was to investigate chemical pretreatment to eliminate sulfate interference. Addition of a barium salt to selenate + sulfate standards was investigated as a means of eliminating sulfate interference through its precipitation as barium salt. This form of pretreatment should remove the sulfate without precipitating any selenate because the solubility product of barium sulfate is approximately three orders of magnitude lower than that of barium selenate and the selenate concentration in groundwater is typically three orders of magnitude lower than the concentration of sulfate. The solubility products and saturation solubilities of barium sulfate and barium selenate are 1.1×10^{-10} , 0.00233 mg/L and 1.7×10^{-7} , 0.118 mg/L, respectively. Based on calculations using these solubility products, a 500 ug/L selenate concentration would not begin to precipitate upon addition of barium until the added barium was 7 g in excess of the quantity needed to stoichiometrically match the sulfate concentration in the sample. Although solubility calculations indicate that barium addition should not cause precipitation of selenate, there is still the possibility of selenate loss occurring with the precipitating barium sulfate in a sweep floc effect.

To test the efficiency of barium addition on the removing the interference of sulfate on selenate, a series of known concentrations of standard sulfate solutions in centrifuge tubes were dosed with various concentrations of barium hydroxide solutions. The results of this study are shown in Table 8. Initially a 25 ug/L selenate, 100 mg/L sulfate standard was made up with approximately

Table 8. The effect of adding 5 mM barium on selenate + sulfate standards.

Standard	SeO ₄ ²⁻	SO ₄ ²⁻	Resolution	SeO ₄ ²⁻	SO ₄ ²⁻	Resolution
	ppm		%	ppm		%
1	25	0	--	25	0	--
2	25	50	100	25	5	100
3	25	100	85	24	15	100
4	25	500	<5	19	90	44

1 mM barium present as barium hydroxide. The standard sample was first centrifuged using a bench top centrifuge at 1000 x g, then it was filtered via a 0.045 micron Gelman syringe filter. The pH of the solution was adjusted near neutral prior to analysis by ion chromatography. Addition of the barium salt to this standard increased the percentage resolution from 0 to 45% and did not result in any selenate loss. This preliminary result indicated that barium addition can effectively eliminate sulfate interference and maintain the integrity of the selenate concentration when the quantity of added barium stoichiometrically matched the sulfate concentration.

Non-stoichiometric addition of barium to sulfate was also conducted to discern the effectiveness of barium addition to a sample of unknown concentration of sulfate and selenate. Results indicated that a 5 mM barium dose could precipitate up to 500 mg/L sulfate, which in most cases is the maximum sulfate level in most groundwaters.

Barium hydroxide was chosen for the barium dosing because it is the only barium compound which is sufficiently soluble in water and does not introduce interfering anions to the sample as in the case of barium nitrate or barium chloride. The use of barium carbonate was not investigated since the compound is not soluble in water. Pretreatment of a sample with barium hydroxide will, however, substantially increase the pH of the sample and possibly alter the speciation of selenium. Addition of 5 mM barium as barium hydroxide raised the pH of the mixed selenite + sulfate standard from 6 to 12. To investigate the effect of this pH change on speciation, 5 mM barium as barium hydroxide was added to a standard containing 100 ppm selenite, and 100 ppm selenate. An ion chromatographic scan of this standard before and after the addition of barium indicated that no shift had occurred due to the increased pH.

Although the pH increase due to addition of barium hydroxide does not appear to alter the speciation of selenium in a mixed standard, it may influence speciation in the complex matrix of a real sample. To eliminate the change in sample pH upon addition of barium, the use of ion exchange resin (preferably in the barium form) is currently being considered.

SECTION VI

SELENIUM TRANSFORMATION STUDY

A. Laboratory Adsorption/Desorption Mini-Column Study

The objectives of the laboratory experiments and field investigations are to evaluate: (i) the migration characteristics of selenate and selenite through a soil or a spoil material as affected by changes in pH and Se concentration; (ii) selenium transformation in coal mine spoils as affected by controlled pH and oxidation-reduction potentials; and (iii) the environmental limitations for selenium speciation at a mining site. To accomplish these objectives the following experiments were conducted.

One hundred grams of small particle sand and 100 grams of air-dried, <2 mm soil taken from the reclaimed site were each mixed with 100 ml of deionized water. To each sample was added 10 ml of 100 ppm selenite. The solutions were mechanically shaken for 24 hours. Analysis of a supernatant extract using ion chromatography indicated nearly 100 percent adsorption of selenite on the soil sample and essentially no adsorption on the sand. Thus, it became necessary to perform preliminary experiments using mini-columns (Figure 25) to study both adsorption and potential desorption of selenite on various soil media.

The preliminary experiments using the mini-column design included three types of soil media. Characteristics of the soil media used are described in Table 9. Two grams of the soil medium were placed on top of glass wool which was used to plug the bottom of the mini-column. The soil medium was first wetted with deionized water, then it was loaded with 1 ml of 267 ppm SeO_3^{2-} solution. Immediately, the soil was covered with distilled water (purified to 15.4 megaohm). A constant head of water was maintained using a peristaltic pump. Leachate was collected from each mini-column in 25-ml, acid-washed vial. The leachate collected was refrigerated at 4°C until analyzed on the ion chromatograph.

Figure 25. A Mini-column Assembly Used for Selenium Adsorption Study.

Table 9. Soil media description for the adsorption/desorption mini-column study.

NO.	SAMPLE	PARTICLE SIZE	SOIL DESCRIPTION
1.	sand	100 mesh	graded commercial sand, acid-washed and rinsed with DI water
2.	top soil	not measured	black soil sampled from the first six inches of topsoil (Cleveland County, Oklahoma)
3.	overburden	< 2mm	soil from the reclaimed site obtained from a depth of 90 cm (Okfuskee County, Oklahoma)

1. Sample Preparation

Calcareous and noncalcareous samples of soil/overburden material could be segregated prior to laboratory analysis. A few drops of 10% HCl were placed on selected soil samples to determine the presence of free carbonates in calcareous samples. Slight to violent effervescence indicates the presence of a calcareous soil. No effervescence was noted for any soil sample.

For a noncalcareous sample, the bulk of the soil sample was airdried for 72 hours and ground using a Wiley Mill. The samples were passed through a 2-mm steel sieve, and the <2-mm fraction was collected and saved in zip lock bags until analysis.

2. Moisture Determination

Moisture determination of the air-dry soil was expressed as a percent. Five grams of the soil fraction was weighed into a tared 100-ml Pyrex^R beaker. The beaker and its contents were placed in an oven set at 105°C for 24 hours. The sample was removed and cooled in a desiccator for 60 minutes. After weighing on an analytical balance, the loss in weight was expressed as a percent of the oven-dry soil.

Undisturbed field samples were also analyzed for percent moisture content. Five grams of the sample was weighed into a tared 100-ml Pyrex^R beaker. The beaker and its contents were placed in an oven set at 105°C for 24 hours. The sample was removed and cooled in a desiccator for 60 minutes. After weighing on an analytical balance, the loss in weight was expressed as a percent of the oven-dry soil.

3. Soil pH

Ten grams of air-dry, <2-mm fraction, disaggregated sample was weighed into a 50-ml plastic beaker. 10 ml of deionized (DI) water was added to the sample and the sample stirred. The suspension was allowed to equilibrate for 30 minutes with occasional stirring. After the clay fraction settled, pH readings were taken from the clear supernatant. Soil pH was measured in undisturbed field samples immediately upon arrival at the laboratory. Measurement of pH was also

taken on samples that were allowed to air dry for 72 hours. The pH was taken using the Fisher pH/mv/temperature meter.

4. Soil Digestion

Selected soil samples which are air-dry, disaggregated fractions were digested using the Tecator 1009 Digester. A 0.50 to 0.75 gram soil samples were placed in 100-ml digestion tubes. The 12 100-ml tubes, each with a digestion rod for uniform boiling, were placed in an aluminum block for even heating. A 5 ml volume of concentrated HNO_3 was added in each tube containing the soil sample and allowed to boil for 1 hour at 100°C . After cooling for 10 minutes, 10 ml of a 3:1 HNO_3 , H_2SO_4 mixture was added. The temperature was gradually increased to 220°C and remained there until a white residue appeared. The sample was diluted to 100-ml with DI water (15.4 megachm). The digested soil samples were stored in acid-washed, rinsed bottles at room temperature until analysis using atomic absorption.

5. Soil Extraction

Air-dried and pulverized soil samples were used for a water-soluble extraction of selenium species. One hundred grams of soil sample were weighed into a tared 1 pint glass jar. 100 ml of deionized water was added to the sample. The jar and contents were placed on a mechanical shaker for 24 hours at low speed. After 24 hours, the samples were allowed to settle and filtered using a vacuum filtration system. The filtrate collected was placed in acid-washed, rinsed bottles and stored in a refrigerator at 4°C until analysis on the ion chromatograph.

6. Sample Analysis Using Ion Chromatography

Extracted samples were diluted with DI water (>15.4 megachm) as needed to use with the Dionex AI-450 Ion Chromatograph. Each sample was filtered with a micropore filter before injection. Anion species determined in each sample analyzed included Cl^- , SO_4^{2-} , SeO_3^{2-} and SeO_4^{2-} .

7. Data Presentation

The complete field data is tabulated and presented in Table 1 of Appendix A. This table summarizes temperature, moisture, Eh, and pH variation with depth for each station in the study site.

Table 10 is total Se concentration in overburden (mine spoils) taken from the Henryetta site. An analysis of all soil samples obtained from coal-mining area showed evidence of no Se in the samples except those taken from the mine spoils.

Tabulated data for the adsorption studies conducted thus far are presented in Table 11. The concentrations in ppm SeO_3^{2-} are listed for topsoil, sand, and overburden material. Figure 26 graphical displays an adsorption isotherm for the adsorption and apparent desorption of SeO_3^{2-} from sand, topsoil and overburden. It demonstrates that no adsorption of SeO_3^{2-} has occurred with sand. However, with both the overburden and topsoil, adsorption of SeO_3^{2-} has occurred, and was followed by an apparent desorption.

Table 10. Total selenium concentration in selected soil samples taken from the Heneryetta site. These measurements are from selected overburden. The concentrations are expressed in mg/kg (ppm).

Sampling Date	Depth, cm		
	30	90	150
9/12/90	0.12	0.09	<0
9/24/90	0.14	<0	0.45
10/05/90	0.29	0.33	0.12
10/19/90	0.28	0.62	<0
10/31/90	<0	0.16	<0

Table 11. Adsorption isotherm studies for selenium on soil, sand, overburden.

Topsoil		Sand		Overburden	
ppm, Se	Time (min)	ppm, Se	Time (min)	ppm, Se	Time (min)
8.536	7	137.2	0	31.815	7
2.052	14	64.24	0.5	0.317	14
0.924	21	4.96	6.0	0.165	21
0.621	28	4.72	11.5	0.175	28
0.472	35	-	17.0	0.127	35
0.350	42	4.03	24.0	ND	42
0.292	49	-	33.4	ND	49
0.237	56	0.06	45.0	135.802	56
68.818	63	-	-	ND	61
0.139	70	-	-	0.090	68
67.640	77	-	-	41.43	75
58.677	84	-	-	ND	82

Figure 26. Adsorption Isotherm for Selenium Species on Coal Mine Spoil Material.

SECTION VII

RESULTS AND DISCUSSION

A. SELENIUM IMPACT ASSESSMENT STUDY

Selenium released from coal mine spoils can be dispersed and transported into the environment through some pathways. The main routes of Se from coal mine spoils into the surrounding area are erosion and runoff of coal mine spoil onto land and surface waters; and leaching both from mined coal and coal mine spoils into ground waters. In order to predict and identify the environmental impact associated with such migration, the methods applied must be able to follow Se through the environment and to calculate selenium concentrations in all media of the area surrounding the coal mine spoils source.

1. Outline of Selenium Impact Assessment Procedure

An outline of the environmental impact assessment process of Se from coal mine spoils is presented in Figures 27 and 28. Figure 27 traces Se from coal mine spoil through an environmental transport mechanism. This mechanism shows that selenium from coal mine spoil can enter the surrounding soils, surface waters, and ground waters. Selenium, after entering these different media, is subjected to dispersion and transfer among these media. Figure 27 demonstrates these general processes and the interactions between media that must be considered in determining the distribution of Se concentrations in the area surrounding the source. Figure 28 shows that Se concentrations in the environment are passed through a food chain to generate health effects on plants, animals, and humans.

Similar to other environmental impact calculation methods, some simplified environmental transport models can be applied to calculate Se concentrations in soils, surface waters, and ground waters. It is beyond the scope of this study to derive various mathematical models used for selenium impacts calculations. This section is oriented to presentation of several existing mathematical models that can be used in selenium impacts calculations. The results of these

Figure 27. Postulated Pathway of Selenium from the Coal Mine Spoil to the Environment.

Figure 28. Possible Pathway of Selenium Through the Food Chain.

calculations could be incorporated into environmental impact reports or similar documents and used to respond to public concern about selenium potential pollution. The following impact assessment procedure was formulated by modifying the method developed by EPRI's " Risk Assessment of Toxic Emissions: Alternative Models and Practices".

2. Defining The Impact Calculation Boundaries

In the beginning of the impact calculations, large scale maps or aerial photographs of the surrounding coal mine spoils should be obtained. These maps or photographs should contain the entire area expected to be included in the impact calculations. They can be used to determine the surface water network, locate area populations, estimate runoff patterns, and define land use patterns in the area.

Based on the area maps and preliminary information, the spatial and temporal boundaries of the impact calculations can be defined. This definition should include (1) study area; (2) overall time period; (3) environmental media; (4) pollution species, in this case, selenium; (5) surface water network; and (6) Selenium migration routes. This definition, however, can be changed later if it is necessary.

For the convenience of Se impact calculations, the study area can be divided into sub-areas. The sub-areas definition is flexible and can probably be based on regional population distribution, water consumption patterns, and the surface water network. For example, Figure 29 shows a hypothetical coal mine spoil site near three towns of A, B, C, and a river XYZ. To simplify the impact calculations, but still have sufficient detail to demonstrate the methodology, the study area can be partitioned into 32 sub-areas using a combination of angular sectors and radial segments. This type of partitioning is also used in the environmental impact assessment of coal mines and nuclear power plants. The sub-areas divisions are shown in Figure 30.

3. Soil Impact Calculation

Selenium concentration in surface soil layers and runoff into surface waters can be calculated by soil transport models. Runoff results become source

Figure 29. A Hypothetical Coal Mine Spoil Site Near three Towns Symbolized by A, B, C; and a River Designated by XYZ.

Legend
 I - V - River reaches
 10 - 50 - Subregion radius
 N - S - Subregion sectors

Figure 30. Sub-area Divisions of the Hypothetical Site.

terms in the subsequent surface water impact calculations. Soil impact calculation is performed to determine Se concentration in surface soil layers, Se infiltration rates through the soil into the ground water, and runoff flows and Se concentration in the runoff.

A simplified method can be used in many situations for Se soil impact calculations. In this method (112), some possible processes are considered. They include:

- (i) Deposition from irrigation water.
- (ii) Accumulation in surface soil.
- (iii) Uptake by plants.
- (iv) Deep infiltration into subsurface soil or groundwater.
- (v) Runoff into surface water.

Each of these processes is considered in calculating Se concentration in the surface soil layers. It is designed to investigate how each of these processes may affect the distribution of Se in soils.

The quantity of Se in a volume of surface soil at the end of a particular time period can be determined by the background Se concentration in the soil at the beginning of the period, the deposition rate, and the rate at which Se leaves the soil volume. Selenium can leave surface soil either through runoff, plant uptake, or infiltration into deeper soil layers and ground water. First, the deposition rate is calculated as follows:

$$D_t = D_{is} + D_{ig}$$

$$D_{is} = I_s C_s$$

$$D_{ig} = I_g C_g$$

Where D_t = total Se deposition rate ($\text{mg}/\text{m}^2/\text{s}$),
 D_{is} = Se deposition rate from surface water
irrigation ($\text{mg}/\text{m}^2/\text{s}$),
 D_{ig} = Se deposition rate from groundwater irrigation
($\text{mg}/\text{m}^2/\text{s}$),
 I_s = irrigation rate of surface water ($\text{L}/\text{m}^2/\text{s}$),

- I_g - irrigation rate of groundwater ($L/m^2/s$),
 C_s - incremental Se concentration in surface water used for irrigation (mg/L),
 C_g - incremental Se concentration in ground water used for irrigation (mg/L).

Note that Se concentration in irrigation water should be more, since the model deals only with the amount of Se in the above background levels, that is, only Se added to the water from the coal mine spoils.

Selenium entering a volume of soil may be lost to (1) plant uptake, (2) infiltration into deeper soil layers or ground waters, (3) runoff into surface waters. The remainder of the Se will accumulate in the surface soil layer. If the total deposition rate is known, then Se removal rates for infiltration and plant uptake can be calculated from the following relationships:

$$\begin{aligned}
 R_p &= D_t f_p T \\
 R_{di} &= D_t f_{di} T
 \end{aligned}$$

Where R_p - Se removal rate by plant uptake (mg/m^2),
 R_{di} - Se removal rate by deep infiltration (mg/m^2),
 f_p - fraction of total deposition removed by plant uptake (dimensionless),
 f_{di} - fraction of total deposition removed by deep infiltration (dimensionless),
 T - length of time period (s).

Selenium may also be removed from the soil through runoff to surface waters. For a given subarea, Se in runoff can be calculated as follows:

$$O_t = D_t A f_r [f_{ar} + (1.0 - f_{ar}) f_{au}]$$

Where O_t - Se contained in runoff to surface water (mg/s),
 A - subregion area (m^2),
 f_{ar} - fraction of subregion area that is rural (dimensionless),
 f_{au} - attenuation factor for urban area (dimensionless),

f_r - fraction of total deposition in rural areas that enters runoff to surface waters (dimensionless).

This calculation divides Se deposition between urban and rural areas and assigns an effective attenuation factor to urban area.

Then, the amount of Se remaining in the soil can be estimated by the following equation:

$$R_s = D_t f_s T$$

Where R_s - Se accumulation rate in surface soil (mg/m²),

f_s - fraction of total deposition remaining in surface soil (dimensionless).

This accumulated Se will change the existing background Se concentration in the surface soil. The new Se concentration can be determined by the following equation:

$$C_s = C_{sb} + \frac{R_s}{p_s}$$

Where C_s - Se concentration in surface soil (mg/kg),

C_{sb} - background Se concentration in surface soil (mg/kg),

p_s - effective surface soil density (kg/m²).

The effective surface soil density is calculated from

$$p_s = 10.0 p d_s$$

Where p - soil density (gm/cm³),

d_s - depth of surface soil (cm).

In effect, the simplified soil transport model partitions Se between plant uptake, deep infiltration, surface soil accumulation, and runoff. Deposition and runoff rates depend on the extent and type of irrigation, soil conditions, precipitation characteristics, and agricultural practices. To simplify the analysis, uniform soil conditions and irrigation practices across the area can be assumed. A difficult assumption to make in the application of the above equations is the deposition period. Since Se may or may not accumulate in the

soil over time, depending on whether or not Se is taken up by harvested plants. If Se is not taken up by plants, it will accumulate in the soil and higher concentrations will develop over time. However, if it remains in the soil, it will not have any health effects on animals and humans. On the other hand, if plant uptake is significant, the potential health effects will increase, but surface soil concentration will be lower. As a result, usually a one-year period can be selected based on the assumption that plants were harvested once a year. In fact, Se concentration in soils is influenced by some factors, such as plant types, soil conditions, agricultural and irrigation practices, and meteorological conditions.

4. Surface Water Impact Calculation

Two types of surface water bodies are considered in the Se impact calculations. One type is streams and rivers, another type is lakes and impoundments. The important route for Se from coal mine spoils to enter surface water bodies is via runoff and erosion (nonpoint source). At the same time, there may be other sources for Se to enter surface waters. They may include runoff from agriculture, forest, and urban areas (nonpoint source), and direct discharges from municipalities and other industries (point source), such as coal fired-power plants discharges and irrigation return flows. Finally, there is background Se levels in surface water bodies (natural source). A useful water quality model should be able to deal with all three types of sources. The two types of surface water bodies will be discussed separately in the following sections.

(a) Streams And Rivers

Before the simplified stream model is applied to a real problem, some assumptions have to be made. These general assumptions are:

- (i) Steady-state conditions.
- (ii) Plug flow without dispersion.
- (iii) Complete vertical and lateral mixing.
- (iv) First order decay processes.

The steady-state assumption implies that the conditions are independent of time but change over distance along the waterway. The second and third assumptions mean that dispersion effects can be ignored along the waterway and that Se concentration is constant across the entire waterway at all depths at any given location. The assumption of plug flow may give higher Se concentration than it would be with normal dispersion processes. There is limitation on the first-order relationship for all decay processes, so care should be taken when in any particular situation to determine the validity of this assumption.

To use the model, waterways under calculation can be divided into several reaches, each of which is assumed to be uniform in character (such as velocity, depth, area, nonpoint loading rate). Reach determination can be based on consideration of the locations of major point sources and the distribution of nonpoint sources along the stream. The model equation is based on locating primary point sources at the beginning of each reach and distributing nonpoint sources uniformly along the entire reach. For each reach, some data are needed. These data include stream velocities and flow rates, Se loading rates (point and nonpoint sources), decay rates, and background Se concentrations. Besides, Since background Se concentration and other loading rates may vary with season, it may be appropriate to consider mean and extreme conditions throughout the year.

The model calculates Se concentrations within each reach as a function of distance downstream from the beginning of the reach. For a selected stream, the model begins calculations at the extreme upstream reach. Although the decay mechanism is supposed to be a first-order process, the total decay coefficient, k_t , can vary in different reaches, depending on the physical and chemical conditions of the reach. The following is the basic equation of the model (112),

$$\frac{\partial C}{\partial t} + \frac{1}{A} \frac{\partial}{\partial x} (QC) - k_t C + \frac{C_d}{A} \left(\frac{\partial Q}{\partial x} \right) + C_p$$

Where C = Se concentration (mg/L),

Q = flow rate (m^3/s),

A = stream cross-sectional area (m^2),

k_t = total decay coefficient (1/s),

C_d = Se concentration in nonpoint sources with flow (mg/L),

C_p = Se concentration in point sources (mg/L),
 x = downstream distance (m).

There are four different solutions of the above model equation according to the four different types of Se sources in each reach. These four solutions and their application conditions are presented below (112).

Type 1: In this case, there is just only one point Se source in the beginning of the reach. Under this condition, the Se concentrations at any point downstream can be determined by following equation:

$$C_0 = \frac{C_u Q_u + 0.001(W - W_i)}{Q_u + Q_w - Q_i}$$

$$C = C_0 \exp \left(\frac{-1000.0 k_t x}{U_0} \right)$$

$$Q_x = Q_u + Q_w - Q_i$$

Where C = Se concentration at location x (mg/L),
 C_0 = Se concentration at upstream end of reach (mg/L),
 C_u = Se concentration at upstream reach (mg/L),
 Q_x = stream flow rate at location x (m³/s),
 Q_u = stream flow rate in upstream reach (m³/s),
 Q_w = water flow rate from point source (m³/s),
 Q_i = water removal rate for irrigation (m³/s),
 U_0 = stream velocity at upstream end of reach (m/s),
 W = Se load from point source (mg/s),
 W_i = Se removal rate for irrigation (mg/s),
 x = distance downstream from beginning of reach (m).

The upstream end Se concentrations and flow rates are the equivalent quantities

at the downstream end of the previous reach.

Type 2: In this type condition, there are a point source at the beginning of the reach and a nonpoint source without additional flow along the reach. Under these conditions, the solution is:

$$C_p = \frac{0.001(W_p + W_r)}{X_r A}$$

$$C_0 = \frac{C_u Q_u + 0.001(W - W_i)}{Q_u + Q_w - Q_i}$$

$$C = \frac{C_p}{k_t} + \left(C_0 - \frac{C_p}{k_t} \right) \exp - 1000.0 k_t \left(\frac{x}{U_0} \right)$$

$$Q_x = Q_u + Q_w - Q_i$$

Where C_p = Se flux from nonpoint source (mg/L/s),
 W_p = Se load from nonpoint sources without flow
 (mg/s),
 W_r = Se load from soil runoff without flow (mg/s),
 X_r = Length of reach (m).

Type 3: In this type condition, the reach has a point source at the beginning and nonpoint source with flow along its length. The flow at any point downstream from the beginning of the reach can be determined by following:

$$Q_x = Q_u + Q_w + (Q_r - Q_u - Q_w) \frac{x}{x_r}$$

$$\Delta_q = \frac{Q_r - Q_u - Q_w}{x_r}$$

Where Q_r = stream flow rate at end of reach (m^3/s),
 Δ_q = incremental stream flow rate ($m^3/s/m$).

The Se concentration at any point x can be determined by following:

$$C_d = 0.001 \frac{W_d + W_g}{\Delta_q}$$

$$C_0 = \frac{C_u Q_u + 0.001(W - W_i)}{Q_u + Q_w - Q_i}$$

$$C = \frac{C_d}{E} + \left(\frac{C_d}{E} - \frac{C_0}{E} \right) \left(\frac{Q_u + Q_w + Q_i}{Q_x} \right) E$$

$$E = \frac{k_t A + \Delta_q}{\Delta_q}$$

Where C_d = Se concentration in the nonpoint source with flow
 (mg/L),

W_d = Se load from nonpoint source with flow (mg/s/m)

W_g = Se load from groundwater interaction (mg/s/m).

Type 4. In this condition, there is a point source at the beginning of the reach and nonpoint sources with and without additional flow along the reach. In this condition, the flow rate equations are the same as the third type above, and the Se concentrations can be determined by:

$$C_0 = \frac{C_u Q_u + 0.001(W - W_i)}{Q_u + Q_w - Q_i}$$

$$C_p = \frac{0.001 W_p}{x_r A}$$

$$C_d = \frac{0.001 \left[(W_d + W_g) + \frac{0.001 W_r}{x_r} \right]}{\Delta_q}$$

$$C = C_0 \frac{Q_u + Q_w - Q_i}{k_t A + \Delta_q} + \frac{E}{Q_x} \frac{C_d \Delta_q + C_p A}{Q_x}$$

$$* \left[1.0 - \left(\frac{Q_u + Q_w - Q_i}{Q_x} \right) \right]$$

When using the above solutions, the runoff flows and Se loading in runoff can be obtained from previous soil transport model, and the Se loading from groundwater interaction can be obtained from the result of groundwater transport calculation.

(b) Lakes And Impoundments

The difference of water quality in lakes or impoundments from that in stream or rivers is the occurrence and strength of thermal stratification. When there is no stratification, lakes will mix well and Se concentrations are uniform throughout the lakes. If there is stratification, it may trap Se in the various water layers, causing great concentration gradients. Sedimentation can also affect Se concentrations in lakes since settling process can reduce Se concentration. Settled Se will accumulate on the bottom of a lake and act as a source of pollution in later time. Same as the stream condition, some basic

assumptions are made for the lake model. These include:

- (i) Steady-state conditions.
- (ii) Complete vertical and horizontal mixing within each unstratified volume.
- (iii) First order decay process.

The physical meaning and implication of these assumptions are the same as discussed in the stream analysis. However, in a lake, it has to assume complete mixing of the inflowing water with the available volume of the lake water body. This available volume can be the entire volume of an unstratified body or the upper mixed layer in the stratification. The concept of "active volume" means the water body which mixes well within a period of time and is used in the lake impact calculations. Besides, the settling process is included in the lake calculations because settling is more significant in lakes than in streams.

The model equation for Se in a lake can be expressed as follows: (113)

$$\frac{dC}{dt} = W_d/V - k_s C - k_t C - \frac{QC}{V}$$

Where C = Se concentration in the lake water (mg/L),
 W_d = mean total Se loading rate from all sources (mg/L/s),
 k_t = mean total decay coefficient (1/s),
 k_s = mean settling rate (1/s),
 Q = mean outflow rate (L/s),
 V = lake active volume (L).

This equation can be solved at steady-state condition by setting the concentration change to zero:

$$C = \frac{W_d}{V(k_t + k_s + Q/V)}$$

The mean total Se loading rate can be obtained from the following equation:

$$W_d = W_{db} + W_0 - W_i$$

$$W_{db} = C_b V \left(k_t + k_s + \frac{Q}{V} \right)$$

Where W_0 = Se loading from soil runoff (mg/s),
 W_i = Se removal for irrigation (mg/s),
 W_{db} = mean background Se loading rate (mg/s),
 C_b = background Se concentration (mg/L).

B. GROUNDWATER IMPACT CALCULATION

The primary release of Se from coal mine spoils into groundwater is leachate. The amount and chemical characteristics of such leachate will depend on coal and coal mine spoils composition, and soil characteristics.

There are hundreds of different groundwater models described in the literature. Each of these different models has its own assumptions and limitations, but many of them can be used equally well in any particular situation. Thus, it is not necessary to illustrate the application of these models here because different types of models may be required for different situation. According to Whelan and Brown (114), when selecting a suitable model to calculate Se transport, it should select a particular computer code that:

- (i) Interfaces well with the soil and surface water transport models.
- (ii) Provides pollutant concentrations at appropriate locations averaged over the time period of the analysis.
- (iii) Incorporates the mechanisms of advection, dispersion, and retention.
- (iv) Considers groundwater and contaminant sinks with geometries consistent with drinking water and

irrigation wells.

- (v) Can be applied to a sufficiently large area to incorporate the population of concern.

Oster (115), Thomas et al (116), and Wang et al (117) have done some literature reviews about groundwater transport models. These reviews provide useful information for model selection. Whelan and Brown (113) also describe a set of groundwater transport models. Table 12 presents these models for reference. The result of most groundwater transport models is pollutant concentrations in groundwater. They can also give us information about flow rates for interactions between groundwater and surface water bodies. This kind of information can be put into surface water transport models discussed above.

C. SELENIUM IN OKLAHOMA GROUNDWATER AND SOIL

1. Selenium Entry to Aquatic Systems

Selenium is continuously cycled by natural processes. A general model explaining the cyclic process was previously shown in Figure 1. Selenium is transported from the core to the surface of the earth through igneous extrusions and volcanic gases. Soils may obtain Se from rocks, volcanic activities, industrial waste, irrigation water and fertilizers. Selenium and other trace elements are released through coal combustion and enter aquatic systems either by direct discharge or indirect input. Irrigation drainage effluent may be discharged into water bodies or into wet lands that are important wild life habitats (118).

In aquatic system Se is predominantly associated with the sediments, which act as both sink and reservoir, or with plants and animals living there, very small amounts are found dissolved in water. Aquatic bacteria can concentrate Se to high levels and provide a link into the food chain. The ultimate fate of Se and other trace elements is their return to sediments or other translocation systems. Other routes of escape for Se from an aquatic system include volatilization (118).

The occurrence of soluble Se compounds in some Se soils and other geological materials suggests that natural waters would be effective in leaching

Table 12. Some Selected Groundwater Models (75).

Constituents	Method	Number of Types	solution	Aquifer	Code Name
PRZM	U	Single	Numerical	H,I	
PESTAN	U	Single	Analytic	HM,I	
RAPCON	U	Single	Analytic	HM,I	
PATH	S	Single	Analytic	HM,I	
CLEARY'S CODE	S	Single	Analytic	HM,I	
BAIRN (GETOUT)	S	Multiple	Analytic	HM,I	
AT123D	S	Single	Both	HM,I	
GRDFLX GROUND	S	Multiple	Both	HM,A	

Source: Whelan and Brown (1984)

Notes: All codes can deal with nonconservative substances and multiple dispersion mechanisms in one phase, except PATHS, which assumes conservative substances and advection only.

U--Unsaturated Zones.

S--Saturated Zones.

H--Heterogeneous.

HM--Homogeneous.

I--Isotropic.

A--Anisotropic.

and transporting the element from drainage areas to flood plains and other large water bodies. While considering the recent available information, the overall speciation data shows SeO_3^{2-} to be the dominant form of Se, with Se (-2) and Se(0) having the lowest concentrations (116). Nevertheless, the data also indicated that every river is unique with respect to its speciation and concentration of Se, and broad generalizations are therefore, inappropriate. Cutter (117) has obtained speciation data for largest river system of California, the San Joaquin and Sacramento rivers. The San Joaquin, which drains the southern portion of the agriculturally important central valley of California, has total Se concentration of an order of magnitude higher than those of the Sacramento draining the northern valley. In San Joaquin, selenate is the dominant form, while selenite and selenide or elemental Se are primary species in Sacramento (116).

The content and speciation of Se in ground water and drinking water is of the most direct concern to humans. Selenium as a minor constituent in drinking water in a concentration range of less than 0.1 - 100 $\mu\text{g}/\text{liter}$. Safe drinking water act of USEPA, has established an upper limit of 0.01 mg/liter which is rarely exceeded. However, water derived from some of the cretaceous zones may have high concentrations of both Se and total soluble salts (117). In a study in central Montana, it was reported that water from wells drilled into any of the geologic formations, cretaceous Colorado group, contained as much as 1000 mg/liter Se (117). An important source of drinking water, ground water, has total Se concentration ranging from less than 0.6-342 nmoles/kg . From these a worldwide average of 30 $\text{nmoles Se}/\text{kg}$ can be extrapolated. All the available data shows that Selenate is the major Se species in ground water. Humic substances in ground water interfere with ground water Se speciation (116).

Selenium concentrations in surface water averages 2 $\mu\text{g}/\text{liter}$ or less. Drainage from irrigation and soil leaching are principal sources of Se in surface water. High concentrations of Se also occur in subsurface drainage waters from irrigated soils in much of the San Joaquin valley. However, the occurrence of elevated Se levels in ground water within this region is not uniform. Some areas having relatively low concentrations of Se occur among the nearby surrounding areas with much higher Se levels (119).

2. Speciation of Selenium in Oklahoma Rural Groundwaters

Table 13 lists levels of Selenite in groundwaters from each of the 77 counties in Oklahoma. The results of this investigation indicate that Oklahoma's rural groundwaters contain primarily Selenite with no detectable Selenate present. This is in contrast to what is being reported for ground water samples by most other investigators. Selenate is being considered as the predominant species of Se in groundwaters due to its suspected high mobility and less adsorptive characteristics. It is apparent from this data that most of the counties exceed the allowable drinking water limit set for Se.

Figure 31 is a sampling distribution map for the state of Oklahoma. All dotted markings are approximate locations in each county where samples for groundwater and soils have been collected. The objective was to establish a well distributed sampling scheme.

3. Distribution of Total Selenium in Groundwater

Increased mobility of Se into the environment via anthropogenic activities, and the potential oxidation-reduction behaviour of the element has made it imperative to study the aquatic chemistry of Se. For this purpose, Se species are divided into two different categories: dissolved Se (that passes through filters with 0.45 μ m openings) and particulate Se (of particle size > 0.45 μ m), typically suspended sediment and other suspended solids. Element and colloidal phase, not truly dissolved, but passing through the filter is deemed to consist of Selenium (-2,0). In dissolved state, Se may exist in three of its four oxidation states; Se (-2), Se (+4) and Se (+6).

Particulate Se may exist in the same oxidation states as dissolved Se and can be found in different phases of the particulate matter. In sediments, Se may be within the organic material, Iron and manganese oxides, carbonates or other mineral phases. The actual chemical forms of the Se may be adsorbed to or co-precipitated with these phases (primarily selenites, selenates). Selenide can be covalently bound in the organic portion of the sediment. In addition, Se may be found in anoxic sediments as insoluble metal selenides precipitates, an insoluble elemental solution or as ferroselite and selenium containing pyrite.

Table 13. Speciation of Se in groundwater as estimated from selenite measurement.

COUNTY	SELENITE (ppm)
ADAIR	0.225
ALFALFA	0.212
ATOKA	2.360
BEAVER	0.177
BECKHAM	0.318
BLAINE	0.590
BRYAN	1.597
CADDO	0.296
CANADIAN	2.160
CARTER	0.333
CHEROKEE	0.016
CHOCTAW	0.064
CIMARRON	1.720
CLEVELAND	1.717
COAL	0.889
COMANCHE	1.520
COTTON	0.856
CRAIG	0.162
CREEK	0.967
CUSTER	0.074
DELAWARE	1.061
DEWEY	0.460
ELLIS	0.250
GARFIELD	1.880
GARVIN	0.270
GRADY	0.799
GRANT	4.033
GREER	4.190
HARMON	11.280
HARPER	0.096
HASKELL	5.310
HUGHES	0.203
JACKSON	1.860
JEFFERSON	0.884
JOHNSON	0.225
KAY	3.00
KINGFISHER	1.228
KIOWA	10.730
LATIMER	0.688
LEFLORE	0.645
LINCOLN	0.285
LOGAN	2.040
LOVE	0.492
MAJOR	0.447
MARSHALL	0.243
MAYES	0.120

(Table 13 Continued)

MACLAIN	0.093
McCURTAIN	0.092
McINTOSH	1.092
MURRAY	3.404
MUSKOGEE	0.048
NOBLE	0.373
NOWATA	0.403
OKFUSKEE	0.580
OKLAHOMA	2.260
OKMULGEE	0.850
OSAGE	0.230
OTTAWA	0.206
PAWNEE	1.940
PAYNE	1.116
PITTSBURG	0.426
PONTOTOC	0.152
POTTAWATIMI	0.426
PUSHMATAHA	1.141
ROGER MILLS	0.161
ROGERS	1.485
SEMINOLE	9.490
SEQUOYAH	1.151
STEPHANS	6.210
TEXAS	0.728
TILLMAN	3.363
TULSA	1.034
WAGONER	0.946
WASHINGTON	0.796
WASHITA	1.460
WOODS	0.192
WOODWARD	0.298

Figure 31. MAP OF OKLAHOMA & ITS ASSOCIATED COUNTIES

● = Soil and water sampling sites.

Selenium exists in four oxidation states in aqueous systems; -2, 0, +4, +6. The reduced state, -2, is represented by the selenide species and the elemental state, 0, exists in different allotropic forms, whereas the two higher oxidation states are represented by selenites, +4, and selenate, +6.

The aquatic chemistry of Se is complicated since it can exist in four different oxidation states and as a variety of inorganic and organic compounds (120). The concentration, speciation and association of Se in a given environment depends on the pH and redox conditions, the solubility of its salts, the biological interactions and reaction kinetics. Many reactions in aqueous media involve transfer of electrons and protons. Such reactions can be represented in an Eh-pH diagram. The activity of the electrons is related to the Eh in the same manner as pH is related to the activity of the protons in solutions. Redox potential is a very useful parameter in describing and predicting the behavior of many important elements that occur in more than one oxidation state (121).

Figures 32 and 33 show the stability (Eh-pH) diagram for the different species of selenium in aqueous systems. Several species of selenium exist in the aqueous environment, however, the most dominant ones are those that are involved in oxidation reduction reactions. The main species involved are:

- a) Elemental Se, Se(0) - It is present in colloidal form and is presumed to result from decomposition of seleniferous minerals by bacteria, fungi and algae. The Eh-pH diagram indicates that elemental Se is stable in reducing environment. All crystalline forms are insoluble in water. In a study by Sarathchandra (122) (27) 1981, it is reported that elemental Se can be oxidized to selenites and trace amounts of selenates by certain micro-organisms.

It is clear from figure 4 that a large portion of the stability domain of elemental selenium covers that of water. Therefore, it is stable in water and aqueous solutions at all pH values free of oxidizing and reducing agents. The stability of elemental selenium is demonstrated by its occurrence in sandstone in dry alkaline environments (123) (4). Selenium exists in three allotropic forms; gray rhombic, which is the most stable, red-monoclinic, and the black amorphous form. The red and black amorphous allotropes are the most likely forms of

Figure 33. Relation of Oxidation-Reduction Potentials of Some Se Compounds to pH.

Figure 32. An Eh-pH diagram for the Se-H₂O system.

selenium in soils and the aquatic environment. The red allotrop is found when selenium is precipitated from aqueous solution. Elemental selenium burns in air to form selenium dioxide, which is a solid substance (mp 340 degrees centigrade). During the combustion of fossil fuels selenium dioxide is formed, but it is readily reduced to elemental selenium by sulfur dioxide which is also found during the combustion of these materials. Contamination of water by elemental selenium would probably pose a minimal toxicity hazard.

- b) Selenide, Se (-2): It may be found in the dissolved states as hydrogen selenide in an anoxic waters or as organic selenides, primarily seleno-amino acids bound in soluble peptides, in oxic and anoxic waters (124). Equilibrium constants and solubility products show that selenide must exist in reducing environment as hydrogen selenide.

Selenide is a foul smelling, poisonous gas. It is a weak acid, and when dissolved in water, it is easily oxidizes to elemental Se (125). Selenium is reduced to hydrogen selenide or other selenides at relatively low redox potentials. Therefore, these compounds are unstable in aqueous systems. Hydrogen selenide by itself is not expected to exist in the aquatic environment since the Se/H₂O Se couple falls even below the H⁺/H₂. Aqueous solutions of H₂Se are actually unstable in air due to its decomposition into elemental Se and water. Under moderately reducing conditions, heavy metals are precipitated as selenides, which have extremely low solubilities. The precipitation of Se as heavy metal selenides can be an important factor affecting the cycling of the element in soils and natural waters.

- c) Selenite (SeO₃⁻²) - Which according to a study in fresh water by Turner and Dickson (126) exists as HSeO₃⁻ at pH 6 and 31% (HSeO₃⁻) + 69% (Selenite) at pH 9. Other thermodynamic data show that Selenite is favored under mildly oxidizing conditions. Selenous acid is a weak acid and is protonated when pH values are acidic to neutral. Most Selenite salts are less soluble than the corresponding Selenate salts. Selenite is reduced to elemental Se by mildly reducing agents (127).

- d) Selenate, Se (+4) - The +4 oxidation state of Se is stable in well oxidized

environments. Selenic acid is a strong acid and therefore, not protonated over pH range of natural waters (127). Dissolved Se is found as Selenate in fresh waters from pH 6-9. Selenate salts are very soluble and conversion of selenate to selenite is a very slow process.

Selenates occupy the upper area of the Eh-pH diagram and therefore, are stable under alkaline oxidizing conditions. Most selenate salts are similar in solubility to the sulfates of the same metals. Soluble selenates would be expected in alkaline soils or alkaline weathering rocks in dry areas. Selenate appears to be the most significant form of Se as far as environmental pollution is concerned because of its stability at alkaline pH values, its solubility and its ready availability to plants.

Figure 34 shows the Pe-pH diagram for Se in an aqueous system under standard conditions. The redox range is considered to be bounded by the $\text{H}_2\text{O}/\text{O}_2$ and $\text{H}_2/\text{H}_2\text{O}$ couples (128). The boundary is represented by the line,

$$\text{Pe} = 14.75 - 1.00 \text{ pH} \quad (1)$$

This line corresponds to Pe/pH conditions for which provided very important facts.

$$\log \text{PO}_2/\text{H}_2\text{O}_2 = 6 \quad (2)$$

It can be seen from the predominance area diagrams (Figure 35) that Selenate, hydrogen selenite, and selenite are each predominant for some Pe/pH range within the overall conditions set on the system. Selection of the predominant form in the system is also based on the thermodynamic data.

The standard free energies of formation of some selenium species are shown in Table 2, which were used to develop the redox relationship (129). To predict the behaviour of Se in aquatic environment, the system can be divided into four broad categories - bulk water, interstitial water, suspended solids and sediment solids. Various transformations occurring in the system can, thus be predicted by making use of the above categories.

As can be seen from the predominance area diagram (Figure 35), the boundary between the selenate ion, HSeO_3^- , and selenite ion falls below the boundary

Figure 34. Predominance Area Diagram for Se in Aqueous Systems Under Standard Conditions.

Table 14. Standard free energies of formation of some Selenium species.

Mineral name	ΔG_f (Kcal/mol)
Elemental Selenium	0.0
Hydrogen selenide	5.3
Hydrogen selenide ion	10.5
Selenide ion	30.9
Selenious acid	-101.87
Selenite ion	-88.40
Selenic acid	-105.42
Selenium dioxide	-41.5

determined by H_2O/O_2 couple. However, the oxidation potential in the natural aqueous system does not reach the boundary defined by the couple. Sato (128) proposed that the maximum oxidation potential in most aqueous systems may fall on or below the line defined by H_2O/O_2 couple which is given by

$$\log PO_2/H_2O = 6 \quad (3)$$

If this boundary is accepted as the upper limit on the oxidation potential in most aqueous systems, selenate may be slightly predominant under neutral to alkaline conditions, if the oxidation potential reaches the maximum potential predicted. Under acidic conditions, or under alkaline conditions with the oxidation potentials falling below the maximum predicted, selenite will be predominant. While predicting the relative amounts of selenates and selenites in natural waters, the kinetics for the reduction of the selenate ion to the selenite ion or to the elemental Se is also to be considered.

In a study conducted by Deveral and Millard (130) on shallow ground waters in San Joaquin valley, it is reported that Se is much more enriched in the coastal range alluvial soil zone and is strongly related to the selenity of the soil. The mobility and distribution of Se has been attributed to the geologic origin of the alluvial deposits.

Sampling and analysis for Se in San Joaquin valley in California has revealed volatile methylated Se compounds (methyl selenides) and dimethyl selenonium compounds (DMSe-R) were documented in a study by Cooke and Bruland (131). Selenious acid species are predominant in solutions over most of the area of moderately oxidizing conditions encountered in oxygenated waters. Between pH 3.5 and 9.0 biselenite ion is predominant in water. At pH values below 7.0 selenites are rapidly reduced to elemental Se under mildly reducing conditions.

Figure 35 shows the distribution of the total amount of Se in Oklahoma soils, as indicated on the map. Although no particular trend can be established by distributing the data on the map, it appears isolated pockets of land near the coal mine districts contain intermediate to high levels of selenium. Therefore, it may be conceivable that coal mining contributed to the release of selenium to the surrounding environment.

The main factors affecting Se concentrations are the degree of groundwater salinity and the geologic source of the alluvial soil material. In a study in

Figure 35. TOTAL SELENIUM LEVELS IN OKLAHOMA SOILS

Total Selenium Level	
	Total Selenium < 0.5 ppm
	Total Selenium < 1.0 ppm
	Total Selenium < 1.5 ppm
	Total Selenium < 2.0 ppm
	Total Selenium < 4.0 ppm
	Total Selenium < 10.0ppm

the western San Joaquin valley, Ca, it was found that high groundwater Se concentrations generally are in the areas where saline soils and groundwaters are common (132). A better understanding of the origin, distribution and mobility of Se and its relation to the chemical composition of the groundwater in the agricultural areas is essential for effective water management.

This part of the study attempted to assess the relationship between Se concentration and various parameters that affect its distribution and mobility. The approach taken in this study was to evaluate the effect of geologic source material on Se concentration by analyzing the interrelationship between pH and other parameters.

The data obtained in the laboratory experiment and during the course of field investigation will be discussed in the light of following parameters:

- (i) Principal groundwater resources, recharge areas and geology of aquifers in Oklahoma.
- (ii) Relation of concentration of Se with pH.
- (iii) Interrelationship of total amount with depth of water.
- (iv) Comparison of coal mining areas with the other areas in context of the total amount of Se present.
- (v) Copper deposits and Se concentrations in Oklahoma.

4. Relating Selenium Level to Principal Aquifers and Geology in Oklahoma

Figure 36 shows the distribution of the principal bedrock aquifers in Oklahoma (Oklahoma Geological Survey, 1972). The term aquifer refers to those rocks and sediments that are saturated with good-to-fair quality water and are sufficiently permeable generally to yield significant volumes of water from wells. The term recharge areas refers to those portions of the land surface where surface water (precipitation, surface runoff, streams, rivers and lakes) enters the subsurface and eventually migrates downward to the zone of saturation in the aquifers.

Oklahoma's bedrock aquifers are wide spread in distribution and differ in composition. Most of the aquifers are sands or sandstone, some are mainly limestones or dolomites. The main aquifers in the state are described below:

(Updated 1979)

Figure 36. Principal bedrock aquifers of Oklahoma.

Ogallala Formation - Loosely cemented layers of fine to medium grained sand, silt, clay and gravel in western Oklahoma and pan handle. Thickness generally ranges from 100 to 700 ft. Wells commonly yield 25 to 1500 gpm of water that is of good quality. (generally less than 500 mg per liter dissolved solids)

Antlers Sandstone - Loosely cemented fine grained sand and sandstone with some layers of shale and clay. It is situated in southeastern Oklahoma and includes underlying holly creek formations of eastern Maccurtain county. Antlers aquifer typically ranges from 200 to 700 ft thick. Wells commonly yield 10 to 4 gpm of water.

Elk City Sandstone - Fine grained sandstone with minor amounts of silt and clay. Maximum thickness is about 185 ft. Wells commonly yield 25 to 300 gpm of good quality water. Its geographical location is in southwestern Oklahoma.

Rush Springs Sandstones and Morrow Formations - Fine grained sandstone with some layers of gypsum, shale and dolomite in western Oklahoma. Thickness ranges from 400 ft in the south to 200 ft in the north. Wells yield 25 to 300 gpm of water that is of good quality.

Cedar Hills Sandstone - Fine grained sandstone interbedded with layers of siltstone and shale in north western Oklahoma. Thickness typically is about 180 ft.

Garber Sandstone and Wellington Formation - It is situated in central Oklahoma. Fine grained sandstone irregularly interbedded with shale and siltstone. Thickness of the aquifer ranges from about 300 ft in the south to about 800 ft in the north. Wells commonly yield 25 to 400 gpm of water that is of good quality.

Oscar Group - Area designated Os-a consists of fine grained sandstone interbedded with shale and siltstone in central Oklahoma. Contains some conglomerate in the south. The thickness of the aquifer ranges from about 150 ft in the south to 300 ft in the north.

Arbuckle and Timbered Hills Group - Limestone and Dolomite interbedded with some sandstone and shale in Wichita mountains - Lawton region of southwestern Oklahoma. Maximum thickness is about 5000 to 6000 ft. Wells commonly yield 25 to 600 gpm of water that is of good to fair quality.

It has been reported that sedimentary rocks usually have Se concentrations much higher than the earth's average of 0.09 ppm (133). Lakin and Davidson gave ranges of Se contents of shale, sandstones and carbonate rocks of 0.24 to 277, 0.05 to 1.12 and 0.0 to 30 ppm, respectively. Igneous rocks are generally impoverished in Se as they are in Sulfur because of volatilization of these elements by volcanism (133).

Selenium concentrations in magmatic and sedimentary rocks are given in table 15. Analyzing the amounts of Se on figure 37, we find that Se enriched groundwater is found in southwestern and northeastern parts of Oklahoma. On the southwestern parts the principal water sources blaine and dog creek formations and rush spring sandstone formations. These aquifers are underlain by fine grained sandstone with some layers of gypsum, shale and dolomite which corresponds with the values in table 16.

It has already been reported that samples derived from south Dakota, Nebraska, Missouri, New Mexico, Colorado and Arkansas tend to have high Se levels. On the eastern side, Oklahoma is surrounded by Missouri and Arkansas while on the western side we have New Mexico and Colorado.

Moreover, the groundwater formations in northeastern parts of Oklahoma consists of limestone beds that tend to have high amounts of Se (table 15). Above all the north eastern parts of Oklahoma are surrounded by Missouri and Arkansas (established high Se content states) and the aquifers in the area (figure 37) is Keokuk and Reeds spring formations that runs across Oklahoma and parts of Missouri too. Rock weathering has been established as the major source of Se in the environment.

5. pH and Selenium Content in Groundwater

Figure 38 shows the graphical representation of pH with concentration of Se in the groundwater. Most natural waters tend to have low concentrations of Se. Notable exceptions can occur if waters are alkaline or if they leach and drain Seleniferous rocks and soil. One example of the pH effect is in the data

Figure 38. Relationship between pH of water and depth to groundwater.

Table 15. Selenium concentrations in Magmatic and sedimentary rocks.

Rock type	Se concentrations mg/kg
Magmatic rocks	
Ultramafic rocks	0.02 - 0.05
Maic rocks	0.01 - 0.05
Intermediate rocks	0.02 - 0.05
Acid rocks	0.01 - 0.05
Acid rocks - volcanic	0.02 - 0.05
Sedimentary Rocks	
Argillaceous sediments	0.4 - 0.6
Shales	0.6
Sandstone	0.05 - 0.08
Phosphorites	1 - 100
Limestones, Dolomites	0.03 - 0.10

Table 16. pH values and depth to groundwater of water samples collected from different counties in Oklahoma.

County	pH	Depth to Groundwater (ft.)
ADAIR	6.67	70.0
ALFALFA	7.87	90.0
ATOKA	7.15	165.0
BEAVER	8.01	100.0
BECKHAM	7.52	140.0
BLAINE	7.90	200.0
BRYAN	7.53	150.0
CADDO	7.00	UNKNOWN
CANADIAN	7.57	UNKNOWN
CARTER	7.25	30.0
CHEROKEE	7.42	30.0
CHOCTAW	5.78	50.0
CIMARRON	8.06	280.0
CLEVELAND	8.07	100.0
COAL	5.85	75.0
COMANCHE	7.60	100.0
COTTON	7.53	30.0
CRAIG	7.18	117.0
CREEK	7.18	UNKNOWN
CUSTER	7.66	160.0
DELAWARE	7.26	120.0
DEWEY	7.55	28.0
ELLIS	7.75	150.0
GARFIELD	7.35	50.0
GARVIN	8.06	120.0
GRADY	7.79	>100.0
GRANT	8.17	100.0
GREER	7.52	654.0
HARMON	7.78	200.0
HARPER	8.03	80.0
HASKELL	7.45	25.0
HUGHES	7.66	90.0
JACKSON	7.47	54.0
JEFFERSON	7.28	16.0
JOHNSON	6.94	125.0
KAY	6.86	25.0
KINGFISHER	7.46	48.0
KIOWA	7.60	18.0
LATIMER	7.22	UNKNOWN
LEFLORE	6.95	135.0
LINCOLN	7.14	UNKNOWN
LOGAN	7.18	75.0

(Table 16 continued)

LOVE	6.56	110.0
MAJOR	7.65	58.0
MARSHALL	6.23	100.0
MAYES	7.26	100.0
MACLAIN	7.75	48.0
McCURTAIN	6.02	80.0
McINTOSH	6.75	UNKNOWN
MURRAY	7.42	100.00
MUSKOGEE	6.73	10.00
NOBLE	7.28	90.00
NOWATA	7.83	40.00
OKFUSKEE	7.65	UNKNOWN
OKLAHOMA	7.90	57.0
OKMULGEE	7.41	UNKNOWN
OSAGE	6.93	80.00
OTTAWA	7.40	UNKNOWN
PAWNEE	7.39	UNKNOWN
PAYNE	7.34	30.00
PITTSBURG	7.07	70.00
PONTOTOC	7.00	150.00
POTTAWATIMIE	7.30	90.00
PUSHMATAHA	7.20	UNKNOWN
ROGER MILLS	7.75	150.0
ROGERS	1.485	84.0
SEMINOLE	6.76	180.0
SEQUOYAH	7.19	UNKNOWN
STEPHANS	7.48	95.00
TEXAS	8.09	400.0
TILLMAN	7.62	30.00
TULSA	7.02	4.00
WAGONER	7.12	23.00
WASHINGTON	6.81	25.00
WASHITA	7.72	120.0
WOODS	7.73	150.0
WOODWARD	8.08	46.0

Page 135 unavailable

of Scott and Voegli (134). When the pH of various Colorado rivers falls in the range of 6.1 to 6.9, the river water Se concentration is generally less than 0.01 mg/L. However, when the pH of the river is between 7.8 and 8.2, the Se concentration ranged from 0.01 to 0.4 mg/L. One recent example of waters leaching and draining seleniferous rocks and soils is in the San Joaquin Valley, California (134). The pH data in Table 16 shows that most of the water samples are in the alkaline range. A plot of this data (Figure 39) for pH vs depth to groundwater showed a rising trend which correlates with the data presented by other researchers.

6. Relationships Between Total Selenium and Depth to Groundwater

The information provided for well depth (Table 16) was based upon personal communication. Although we don't see any trend in the concentration of Se with respect to depth to water, yet we would anticipate that the deeper wells would show high levels of Se as compared to shallow wells. This analogy is based on the fact that the major source of Se in water is rock weathering which indicates that water nearer to the rock will show high levels of Se concentration. In this case, more accurate information regarding depth of water wells will result from the hydrology and hydrogeological labs. More information regarding permeability, hydraulic conductivity, flow conditions etc. will also be needed to establish a relationship.

D. SELENIUM IN COAL MINE SPOILS

The data available on Se concentrations in coal mine spoils and the associated plants in the western energy region of the United States indicated that the selenium in most coal mine spoils would not likely pose a serious environmental problem. The relation of selenium contents in the coal mine spoils and the associated plants in these coal mine spoils sites are shown in Table 17. The associated plants of sweetclover and alfalfa were grown within 1 m of the spoils samples. It is evident that the Se concentrations in all these coal mine spoils are low and no high levels of Se in these plants were observed. Also, crested wheatgrass, a commonly used reclamation species, was analyzed at the Dave Johnston Mine spoil site, Wyoming, to assess the possible effect of the coal mine

Table 17. The relation of selenium concentrations (ppm) in coal mine spoils and the associated materials. (adapted from Richard, J.E. and Hansford, T.S., 1982)

Coal Mine Spoil Site	Coal	Yellow Spoil	Sweet Clover	Alfalfa
Beulah North Mine, North Dakota	0.19	0.15	0.18	
Dave Johnston Mine, Wyoming	0.28	0.37	0.34	
Hidden Valley Mine, Wyoming	0.31	0.53	/	
Kincaid Mine, North Dakota	0.22	0.17	/	
Savage Mine, Montana	0.20	1.30	1.10	
Velva Mine, North Dakota	0.21	0.49	0.33	
Big Sky Mine, Montana	0.17	/	0.22	

spoils on the chemical composition of this species. Selenium concentrations showed no significant difference between the samples growing on 10-15 cm of the topsoil on the spoils and the samples from nearby soils. The mean selenium concentrations of crested wheatgrass grown in the soils and the reclaimed spoils were 0.23 ppm and 0.27 ppm, respectively (135). Information available suggested that the relative amount of Se in coal mine spoils is small and coal mine spoils enriched in selenium are not found. Furthermore, selenium contamination is a localized environmental problem mainly associated with the geological formation of the area. Therefore, in most cases the scale of potential selenium contamination caused by coal mine spoils will be relatively small.

Selenium released from coal mine spoils can be dispersed and transported into the environment through several pathways. The main routes of entry of Se from coal mine spoils into the surrounding environment are erosion and runoff. In both cases Se reaches the land and the surface waters, and leaches into groundwaters. In order to predict and identify the environmental impact associated with such sources, the method applied must be able to follow Se throughout the environment and to calculate the concentrations in all media of the region surrounding the mine spoil source.

An outline for the environmental impact assessment process of Se from coal mine spoils was shown in Figures 27 and 28, respectively. Figure 27 traces Se from coal mine spoil through the various environmental transport mechanisms. The figure shows Se originating from various sources subsequently reaches surface and ground water. Selenium that entered the environmental media is dispersed, and transferred within the media. This figure also suggests that such general processes and interactions between media must be considered while determining the distribution and extent of contamination of the surrounding environment. Figure 28 shows that Se concentrations in the environment are passed through the food web and other exposure pathways to generate health risks for the regional population.

1. Factors that Affect Selenium Accumulation

Biological activity plays a strong role in the distribution of Se in the environment. The accumulation of Se in the plants and animals is highly variable and as noted before, can favourably or adversely affect their growth, survival

and reproduction.

The speciation and the form of Se can change as a result of biological and physical processes. Selenate and Selenite can be reduced to red amorphous Se by numerous bacteria and yeasts. This process significantly limits the availability of Se to plants. Inorganic Se compounds can be converted to volatile organic compounds such as dimethyle selenide or demethyle diselenide by plants, microorganisms and animals (136).

Several inorganic processes control the distribution of Se. One is the adsorption of Se by particles. Selenite has a stronger affinity for particles, particularly Fe oxyhydrides than selenate, and that adsorption is strongly influenced by pH. Sulfide minerals such as Galena and Pyrite tend to act as carriers for Se. Some sulfide minerals have been reported to contain up to 20% Se.

Industrial activities are also high contributors to Se level in the environment. This element is widely used in electronics because of its photosensitive and semiconducting properties; in the glass industry as a decolorizer and pigment; in ceramic industry to introduce color glazes; in rubber industry as a sulfur supplement; and it is also used in photographic exposures; metal finishing operations etc. The effluent from these industries is discharged to landfills, streams and open land management which would contribute significantly to environmental Se (137).

Agricultural activities are also responsible for some of the selenium released into the environment. Fertilizers made from rock phosphate may contain as much as 200 mg Se/kg. These concentrations are generally much higher than those measured in fertilizers derived from rock carbonates, synthetic nitrogen fertilizers and potassium sulfates. Selenium deficient soils are often sulfur deficient, especially for the production of legumes. Increasing the concentration of sulfates in the forage also may have detrimental effect on Se availability to the animals (136).

2. Selenium in Active vs Abandoned Mine Spoils

Figure 14 showed the outline of the coal fields and areas of surface mining for coal in the state of Oklahoma. It is mainly situated in the northeastern parts of Oklahoma. With reference to Figure 35 we find that this area has higher

levels of Se as compared to the other areas in Oklahoma. It, thus, agrees with the established fact that Se may leach from the coal deposits and enter the aquatic environment. It has also been reported that most of the bottom ash and the ash from the precipitators are transported to the landfills as solid residues or flushed with water to ashponds where Se is leached from ash and seeps down to groundwater (138).

The development of large scale coal mining operations in the western USA has raised concerns regarding the potential for Se contamination of soils, surface water and ground waters in and adjacent to these mining operations. It is expected that the Se content of the Oklahoma coal may be in the same range as those in the neighbouring states.

3. Factors Controlling Se Speciation in Soils.

a. Eh and pH Variables

There are many forms of Se in soil systems. This is no surprise since Se exists in soils in four oxidation states. Various techniques have been employed to indicate whether Se is water soluble, exchangeable, or easily reduced (139). One way of predicting which Se species could be present is by comparing the redox potential (Eh) and pH at which various species would be stable with the equilibrium Eh and pH values of the soil through the use of Eh and pH diagrams. The relationships among Eh, pH and forms of Se are shown in Figure 33. At low pH and high oxidation-reduction potential, SeO_4^{2-} is the predominant species. As the pH increases and oxidation-reduction potentials decrease, SeO_3^{2-} becomes the more dominant species. As pH and Eh or both are varied, the chemical composition of the soil solution changes.

Selenides exist as hydrogen selenide which decomposes rapidly in air to Se^0 and water (NAS, 1976) and as metal selenides. Elrashidi et al. (140) reported that selenide species are stable at low redox conditions. Such selenides are PbSe , SnSe and Cu_2Se . Elemental Se is stable in acidic, reducing environments and appears to be an inert sink for Se introduced into the environment. The National Academy of Science (1976) suggests that Se^0 poses a minimal environmental toxicity hazard. Since Se is associated with S in fossil fuels, the burning of Se^0 produces SeO_2 which is reduced to elemental Se by SO_2 . Some

fly ash produced from fossil fuel combustion may contain much elemental Se. Technology could be developed to recover the Se. Selenite would form mineral salts which generally are less soluble than SeO_4^{2-} salts. Geering et al. (141) found that SeO_3^{2-} forms a ferric-selenite adsorption complex which removes Se from environmental cycling. If soluble Se is in the Se^{4+} state, it is highly susceptible to being adsorbed. Under acidic conditions and in the presence of reducing agents such as SO_2 , SeO_3^{2-} is reduced to Se^0 . Selenite-Se may not present a pollution hazard. Selenates are expected in dry, alkaline soils. Selenate salts have solubilities similar to sulfate salts. Selenate, which is stable at alkali pH and more soluble, poses the greatest environmental concern.

b. Selenium - Redox Potential as Master Variable

Oxidation and reduction reactions play important roles in determining the mobilities of several metals and aqueous forms of biologically important elements as nitrogen and sulfur. These reactions also supply the necessary energy for non-photosynthetic forms of life (142). These reactions are normally called redox potentials and have been referred to as master variables in environmental chemistry (143). Two early investigations that recognized the importance of redox potential measurements were published by ZoBell (144) and Bass-Becking et al. (145). ZoBell pioneered the work on redox measurements in marine sediments and Baas-Becking et al. defined the limits of the natural environment using pH and redox potential. Elrashidi et al. (140) indicates that the major features of Se chemistry affecting its solubility and mobility are associated with changes in oxidation state. The inorganic forms of Se expected in soil are, not only governed by the oxidation state, but also by pH, dissociation constants and solubility products. Oxidation-reduction potential is biologically necessary and may control the conditions under which Se may assume higher states as SeO_4^{2-} or lower oxidation states as Se^0 or Se^{2-} . It becomes important to describe the behavior of Se in soil as affected by the disturbance of topsoil and overburden in coal strip mines associated with the mining activity and subsequent reclamation. Important metals, other than Se, associated with coal mine spoils are Fe, Ca, Mo, Cu, Ni, and Hg. An Eh-pH diagram can be constructed from redox couples that could play an important role in affecting the oxidation state of Se, and ultimately its availability to plants and animals.

c. Selenium - Soil Chemistry

Dissolution and precipitation of soil solid phases control the composition of the soil solution. Solubilities determine the mobility of soil chemicals and affect their subsequent possible availability to plants. Redox reactions are important because they modify solubility and affect mineral transformations. Soil chemistry is concerned with the definition of chemical systems and reactions that occur in the soil environment. Soil environments may be natural or artificially created, such as using laboratory soil columns. These soil environments may be composed of more than one solid phase in contact with an aqueous or gaseous phase or both. Living organisms affect soil equilibrium relationships by removing soil constituents as nutrients or by releasing nutrients through decomposition of organic matter. Chemical reactions may occur in only the solid phase or aqueous phase or gaseous phase or at phase interfaces. The principles of equilibria governed by the thermodynamics of chemical reactions is used to investigate the many soil reactions. The common, generalized model for a chemical reactions is:

Water quality can be altered, for example, if A represents a soluble constituent of an aqueous phase and B a solid phase. The chemical reaction process between A and B may yield components C and D which, respectively, may be a new soluble constituent of the aqueous phase and a new solid phase. For the generalized model, the equilibrium expression is:

$$K = [C]^c [D]^d / [A]^a [B]^b \quad (2)$$

Equilibrium constants calculated from equations using activities provide true constants which are true for solutions of all ionic strengths. Activities can be calculated from thermodynamic data. Activities of chemical species are not always known and concentration constants are then used. With concentration constants, ionic strengths must be determined and applied.

Ionic strengths are defined as (147):

$$I = \frac{1}{2} \sum c_i Z_i^2 \quad (3)$$

where I is the ionic strength, c_i is the molar concentration and Z_i is the oxidation state of the specie.

Activities are defined as:

$$a_i = \gamma_i c_i \quad (4)$$

where γ_i is the activity coefficient. Activity is defined as the effective concentration of the specie. Activity coefficients are estimated using the extended Debye-Huckel equation (147):

$$\log \gamma_i = -AZ_i^2 (I^{1/2} / 1 + BaI^{1/2}) \quad (5)$$

where $B = 0.33 \times 10^8$ for water at 25 °C, $A = 0.509$ for water at 25 °C and " a " is the effective size of the hydrated ion expressed in Å. Guntelberg (146) suggests using $3A$ for " a " such that Ba is unity. When $Ba = 1$, it is useful for estimating unknown activity coefficients. The activity coefficients for Se species were taken as unity when developing equations to represent total Se in solution (140).

If the soil composition is unknown, ionic strength can be easily determined from electrical conductivity measurements. The relationship was developed by Griffin and Jurinak (148) and is given as:

$$I = 0.013 EC \quad (6)$$

where EC is electrical conductivity measured in millimhos/cm².

In very dilute solutions, the concentration of an ion is equal to its activity. The value, K^0 , is the thermodynamic equilibrium constant, but for dilute solutions, K^c , the concentration constant, is useful. The constant, K^c , can easily be converted to K^0 if the activity coefficients are known from ionic strengths.

$$K^0 = K^c \left(\frac{\text{products}}{\text{reactants}} \right) \quad (7)$$

In any homogeneous or heterogeneous reaction, chemical potentials account for changes in the energy of a system due to a change in its chemical content. The chemical potential of each species multiplied by the number of moles of each species is equal to the free energy (150). For dilute solutions (< 0.01 M), the potential of each solute is:

$$u_i = u_i^0 + RT \ln c_i \quad (8)$$

where u_i^0 is the standard chemical potential at standard conditions. The chemical potential is dependent on temperature and pressure. At higher concentrations, c_i is replaced by the effective concentration, a_i .

The redox reaction, $2H^+ + SeO_4^{2-} + 2e^- \rightleftharpoons SeO_3^{2-} + H_2O$ ($\log K^0 = 29.02$ at $25^\circ C$ and 1 atm pressure), involves both selenate and selenite ions. Of particular interest are SeO_4^{2-} , the most mobile and available to plants, and SeO_3^{2-} , the more readily adsorbed and unavailable for plant uptake. At equilibrium, the rates to the right and left are equal. The driving force of any chemical reaction to the right or left is related to the concentration of products or reactants. The law of mass action is fundamental to the thermodynamic equilibrium constant. At a given temperature, the product of the activities of reaction products, each raised to the power indicated by its numerical coefficient as determined by a balanced chemical reaction, divided by the product of the activities of the reactants, each raised to its appropriate power, is a constant. Considering the redox reaction previously stated, a thermodynamic equilibrium constant is expressed as:

$$K^0 = (SeO_3^{2-})(H_2O) / (SeO_4^{2-})(e^-)^2(H^+)^2 \quad (9)$$

The brackets, (), indicate the activity of the chemical species. In this reaction, electrons are treated as reactants, and are thus, included in the equilibrium expression, raised to a power of 2 as indicated by the balanced reaction. The redox reactions are necessary in determining aqueous forms of Se.

An interrelationship between chemical reactions and their accompanying energy changes allows the development of a relationship between the equilibrium constant and the standard free energy of formation. Standard free energy or

Gibb's free energy, G°_f , is derived from the summation of the free energy of products minus the free energy of reactants. By convention, the G°_f for the stable elemental configuration is zero which for Se is the gray-hexagonal allotrope. Also, G°_f for the hydrogen ion is zero. The standard free energy of change of reaction, G°_r , is related to the equilibrium constant by:

$$G^\circ_r = - RT \ln K_{eq} \quad (10)$$

where R is the gas constant, 0.001987 kcal/deg, and T is the Kelvin temperature. At standard temperature, 25 °C, Equation 10 becomes:

$$G^\circ_r = - 1.364 \log K_{eq} \quad (11)$$

after converting ln to log.

The soil solution would involve reactions with dissolved species. These reactions can then be expressed as activities of the dissolved species. What happens when Se is put in water or a soil solution? Initially, Se probably occurred as a free element or as a metal selenide in unweathered rock (NAS, 1976). Microbial activity and the weathering process influences the oxidation of Se. In acid soils, Se would be present as SeO_3^{2-} ; and in alkaline soils, Se would be present as SeO_4^{2-} .

The redox conditions in the soil environment which affect selenium speciation, and thus, selenium availability, are Eh, pH, soil moisture conditions and concentrations of soil gases such as O_2 and CO_2 .

The equilibrium redox reactions (140) reported for selenite/selenate are:

d. Selenium - Redox Conditions

Oxidation-reduction reactions are common in the soil environment. Redox equilibria are generally expressed in terms of Eh which is a millivolt potential difference between a platinum electrode and a reference electrode (a standard hydrogen electrode). Redox reactions are expressed as half-reactions indicating a loss or gain of electrons. The chemical species gaining electrons is the oxidizing agent and subsequently undergoes reduction. The species losing electrons is the reducing agent and itself is oxidized. Since the half-reactions are balanced indicating a transfer of electrons, the number of electrons (e^-) can be considered as either product or reactant. The redox potential can be expressed as pe (-log of the electron activity) rather than as Eh (millivolt measurements). A platinum electrode is used to measure redox potential at the selected coal mine spoil sites. The reference electrode uses the standard hydrogen half-reaction such that Eh will be defined as the potential of the cell: Pt, $\text{H}_2/\text{H}^+//$ reduced, oxidized, Pt. Using appropriate substitution and numerical values Eh can be expressed in terms of pe.

e. pe-pH Limits for Selenium in the Natural Environment

Soil systems often consist of an aqueous environment where water dissociation into hydrogen gas (H_2) and oxygen gas (O_2) imposes limits on oxidation - reduction in soils. Equilibria reactions for the dissociation of water are:

for the reduction reaction and

for the oxidation reaction.

The thermodynamic equilibrium expression, K° , for Eq. 19 is:

$$K^\circ = (\text{H}_2 (\text{g}))^{1/2} / (\text{e}^-)^2 (\text{H}^+) \quad (21)$$

and expressed as logarithms:

$$\log K^\circ = 1/2 \log (\text{H}_2 (\text{g})) - \log (\text{e}^-) - \log (\text{H}^+) \quad (22)$$

such that

$$\log K^\circ = 1/2 \log (\text{H}_2 (\text{g})) + \text{pe} + \text{pH} \quad (23)$$

By definition K° for the dissociation of water is defined as 1 (unity) when $[\text{H}^+]$ is 1 M and the $\text{H}_2 (\text{g})$ is measured as the partial pressure of $\text{H}_2 (\text{g})$ at 1 atmospheric pressure. When the partial pressure of $\text{H}_2 (\text{g})$ is 1 atm., $\text{pe} + \text{pH} = 0$. However, $\text{pe} + \text{pH} = 0$ represents the most reduced condition in a soil aqueous environment.

For the oxidized reaction (20), the K° expression is given by:

$$K^\circ = [\text{H}_2\text{O}]^{1/2} / [\text{H}^+] [\text{e}^-] [\text{O}_2 (\text{g})]^{1/4} \quad (24)$$

Since (H_2O) is nearly unity in a very dilute system, the logarithm form is:

$$\log K^\circ = -\log [\text{H}^+] - \log (\text{e}^-) - 1/4 \log [\text{O}_2 (\text{g})] \quad (25)$$

and

$$\log K^\circ = \text{pH} + \text{pe} - 1/4 \log [\text{O}_2 (\text{g})] \quad (26)$$

where

$$\text{pe} + \text{pH} = \log K^\circ + 1/4 \log [\text{O}_2 (\text{g})] \quad (27)$$

When $[O_2 (g)]$ equals 1 atm pressure (partial pressure of oxygen gas), then $pe + pH = \log K^0$. A measurement of the soil gases (O_2 and CO_2 in particular) helps determine oxidized or reduced conditions. Also, the $pe + pH$ parameter provides a description of the redox environment in soil aqueous systems. The oxidation state of selenium affects both the mobility and solubility of Se species. The parameter, as described, not only addresses pe , but also pH , the $- \log$ of the activity of H^+ . Since Eh is measured, it is then useful to convert Eh into pe .

The Nernst equation:

$$E = E^0 - (R T / n F) \ln Q \quad (28)$$

can then be used to obtain an expression for Eh related to pe . The relationship between Eh and pe is derived from the Nernst equation and the redox reactions which occur between the platinum electrode and the reference electrode used to measure Eh . The overall cell reaction (147) (Lindsay, 1979) is:

With the reference electrode being the standard hydrogen electrode, (H^+) and $(H_2 (g)) = 1$ and E in the Nernst equation becomes Eh . Applying the Nernst equation to the described cell reaction gives:

$$E = E^0 - (R T / n F) \ln (H^+)^n (\text{reduced species}) / (H_2(g))^{n/2} (\text{oxidized species}) \quad (30)$$

With $(H^+) = 1$ and $[H_2 (g)] = 1$, Equation 30 reduces to:

$$Eh = E^0 - (RT / nF) \ln(\text{reduced species})/(\text{oxidized species}) \quad (31)$$

Combining Eq. 31 with the K^0 expression for a general half reaction gives:

$$Eh = E^0 - (RT / nF) (\log K^0 - n pe) \quad (32)$$

where $\ln$ is changed to $\log$ base 10. E^0 is the standard cell potential and K^0 described in Eq. 32 is the thermodynamic equilibrium, expression for a general half-reaction:

Since SeO_4^{2-} is the most mobile species and most readily absorbed by plants, the conditions under which transformations from SeO_3^{2-} to SeO_4^{2-} are important.

$$E^0 = (2.303 RT / nF) \ln K^0 \text{ is derived from the } G^0$$

expression and the standard cell potential, Equation 33 becomes:

$$Eh = (2.303 RT / F) pe \quad (34)$$

At R, the gas constant, equals 1.987 cal/degree - mole, T, the absolute Kelvin temperature, at 25 °C equals 298.15 K and F, the Faraday constant, equals 23.061 kcal/volt - equivalent, Equation 34 becomes:

$$Eh \text{ (millivolts)} = 59.2 pe \quad (35)$$

Equation 35 shows how Eh and pe can both be used to express redox relationships. These equations are developed from Sposito, Lindsay, Sawyer and McCarty (151) (1978) and Garrels and Christ (152) (1965).

The roles of pH and Eh are very important in determining the rates of selenium oxidation, even as it applies to selenium oxidation in coal mine spoils. The redox equations establish the importance of pH and Eh (or pe) as important parameters in the investigation of redox potential for selenium transformation.

f. Limitations of Redox Measurements

Eh is a useful parameter to map variations for oxidation-reduction in a natural environment. Redox potentials near or above $pe + pH = 18$ are not reliable when using platinum electrodes. Platinum electrodes don't function well in highly oxidized soils (147). The problems associated with Eh field measurements include (1) direct attack on the Pt electrode by oxygen forming PtO , by sulfates forming PtS and by a chloride complex forming Pt^0 ; (2) release of gases as H_2S ; (3) trace components controlling the potential; (4) mixed

potentials occurring at the electrode; and (5) the difficulty of interpreting Eh as oxidation-reduction potentials.

g. Kinetic Evaluation of Selenium

Equilibrium calculations predict concentrations that may not exist in natural waters because the reaction is controlled by reaction rates. Equilibrium considerations predict ferrous ions will oxidize completely to ferric ions in waters where dissolved oxygen is present. However, Fe^{+2} remains stable under a stream of oxygen gas at low pH values. At a pH > 7 to 8 the oxidation rate is quite rapid and is limited by the supply of oxygen. Thus, pH effects whether equilibrium or kinetic considerations better describe a system (153). In order to evaluate Se kinetically, the reaction order must be determined. Consider the redox reaction:

If the reaction rate is given as,

$$\text{rate} = k [\text{A}]^a [\text{B}]^b \dots \quad (37)$$

then the order of the reaction is,

$$\text{order} = a + b + \dots \quad (38)$$

The reaction orders that are considered are first order and second order.

The integrated equation for a first order reaction is:

$$\ln [\text{A}]/[\text{A}_0] = -kt \quad (39)$$

This equation can also be written as:

$$\log [\text{A}] = \log [\text{A}_0] - kt/2.303 \quad (40)$$

[A] is the final concentration and $[A_0]$ the initial concentration. If the reaction is first order, a plot of $\log [A]$ versus t should be a straight line with a negative slope $k/2.303$ and a y intercept of $\log [A_0]$.

The equation for a second order reaction when $[A] = [B]$ is:

$$1/[A] = kt + 1/[A_0] \quad (41)$$

If $[A]$ does not equal $[B]$ then Equation 41 becomes:

$$1/([A_0] - [B_0]) \ln ([A][B_0]/([A_0][B])) = kt \quad (42)$$

If the concentration of B_0 is much greater than A_0 , then a psuedo first order reaction can be forced. The equation becomes:

$$\ln [A]/[A_0] = -kt \quad (43)$$

If the reaction is second order, plotting $1/[A]$ versus t will be a straight line with slope k and y intercept $-1/[A_0]$ if $[A]$ equals $[B]$. When $[A]$ does not equal $[B]$, then a plot of $1/([A_0] - [B_0]) \ln ([A][B_0]/([A_0][B]))$ versus t will be a straight line with slope k .

At controlled pH and Eh, oxidation of SeO_3^{2-} to SeO_4^{2-} will be measured. At selected time intervals, an aliquot of soil suspension will be removed from the reaction vessel. The aliquot will be analyzed for Se speciation with ion chromatography. The rate constant, overall reaction order, and the order with respect to SeO_3^{2-} can experimentally be determined. This information can provide insight into the transformation rate of selenite to selenate in mine spoil. Selenate, the more soluble species, would then more readily leach from the spoil site, possibly contributing to a potential environmental concern.

h. Adsorption of Se Species in a Soil Environment

Adsorption is an abiotic assimilation of gas, vapor or dissolved matter by the surface of a solid or liquid. Solutes that adsorb strongly onto subsurface materials are retarded in their migration through both saturated and unsaturated zones. In moderately to highly oxidized conditions, it is possible that an

adsorption mechanism may control Se distribution between solid surfaces and the soil solution phase (140). A very important process in determining which chemical species is available for adsorption is the oxidation-reduction potential of a soil. Ahlrichs and Hossner (154) found very little SeO_4^{2-} adsorbed in a leaching soil column consisting of a composite of sandy loam textured stripmine overburden. The column was eluted with 0.01M CaCl_2 adjusted to pH 2, 3, 5, 7, and 9. SeO_3^{2-} was not eluted from this column at any pH. Most SeO_3^{2-} was retained in the first few centimeters of column depth. SeO_3^{2-} movement is affected by adsorption which is strongly dependent on pH. Any field practices that induce pH variations affect Se mobility. Rajan and Watkinson (155) proposed that SeO_3^{2-} adsorption is controlled by ligand exchange reactions. SeO_3^{2-} replaces such species as OH^- , SO_4^{2-} and SiO_4^{2-} ions. Se is dissociated as SeO_4^{2-} in soils with pH common to surface soils. SeO_3^{2-} is more stable in acid and neutral soils (Geering, et al., 1968). In alkaline soils SeO_3^{2-} slowly oxidizes to SeO_4^{2-} , the mobile form of Se.

The adsorption of SeO_4^{2-} along with SO_4^{2-} and Cl^- was quantitatively expressed as a percentage of initial concentration lost during an equilibration period (156). No loss of SeO_4^{2-} was reported from solution at any pH value using four alluvial soils from the San Joaquin Valley, California. Se concentrations in solutions of calcium-saturated kaolinite and montmorillonite clay suspensions were governed by adsorption mechanisms (157). With the prevalence of clays and iron oxides in soils, adsorption reactions may play a magnificant role in Se distribution and subsequent availability.

4. Selenium Speciation at the Henryetta Spoil Site

The Eh and pH data collected from the Henryetta site was plotted and presented in Figures 39. The various symbols, . , . , and + represent sample groupings from 1 ft, 3 ft, and 5 ft depths, respectively. This stability diagram for selenium delineates the various species that are predominantly found at given pH and redox potentials. It is apparent from figure 40 that the most stable selenium species are selenite, elemental selenium, and selenate. Between pH range of 3 and 6, these species seem to be predominant over the other forms of selenium. There is more selenite than elemental selenium or selenate, and elemental selenium is more stable over these pH ranges than selenate. It appears

Figure 38. An Eh-pH Diagram for the Se-H₂O System Enscribing Selenium Values from the Spoil Site.

that due to the very long equilibration time (over 50 years), primarily selenate would be expected to be stable in these environments. Since selenate is very soluble and mobile, it is not expected to be a dominant species in coal mine spoils. Oxidation of elemental selenium to selenite could happen in the pH and redox potentials ranges found at the Henryetta site, and may have contributed to the observed high selenite level.

5. Copper Deposits and Selenium Content

Selenium was discovered by Berzelius in 1870 in the residual slime from the preparation of sulfur dioxide from copper pyrites. Selenium, as usually recovered from these ores as Se bearing minerals, is not in a sufficient quantity to be considered a source of Se. Electrolytic refining of Copper and sludge from the sulfuric acid production accounts for much of the unrefined Se emissions (158). Figure 40 shows the map of northeastern Oklahoma, and adjoining parts of Colorado and New Mexico where copper minerals were mined more than 80 years ago. It is possible to anticipate that selenium will be found in higher concentrations in these areas.

SECTION VIII

SUMMARY, CONCLUSIONS, AND RECOMMENDATIONS

A. Summary and Conclusions

The objective of the research program was to evaluate the environmental impact of selenium that emanates from coal mine spoils. As background information a comprehensive literature review was conducted on the chemistry of selenium, its origin, solubility, speciation, toxicity, and regulation. An environmental impact assessment procedure was developed that could predict the possible contamination of selenium from coal mine spoils. Groundwater samples were collected from every county in Oklahoma to assess possible contamination with selenium. Laboratory procedures for selenium transformation in coal mine spoils was developed to predict its mobility and speciation. An elaborate lysimeter was installed at the spoil site in Henryetta, Oklahoma and used to gather data on the oxidation-reduction potential of selenium under natural environmental conditions.

The literature review served as a background information source for selenium. The origin of selenium, its chemistry in soils and minerals, its toxicity to animals and plants, and its deficiency symptoms have been studied at greater length. However, its aqueous chemistry, its transformation in other natural systems is not very well understood. Anthropogenic sources of selenium, such as fossil fuels, fly ash, and other geologic materials need to be evaluated for their contribution to the environmental impact.

The environmental impact assessment procedure that has been developed was a modification of a mathematical model which has been developed by other investigators. The modification allows the prediction of selenium levels in soils, surface waters, and groundwaters. It requires several input parameters that can be used in the model. For example, to predict contamination of a river which is a distance away from a coal mine spoil site, some selected input parameters will be required. These parameters may include erosion pattern, slope, leaching rate, seasonal flow rate of the river, adsorption of selenium on the soil, initial concentration of selenium in the spoil, etc. Unfortunately,

due to the limited duration of the project the model which has been developed has not been tested.

The purpose of sampling soil and groundwater from each county in Oklahoma was to evaluate possible contamination of these resources with selenium that may originate from various activities, such as coal mining, uranium mining, ore mining, and fertilizer additions. Surface soil samples were collected from the vicinity of each water well that was also sampled. These samples indicated that some counties in Oklahoma contain selenium levels much higher than what has been predicted. Over 10 percent of these counties contain greater than 5 ppm total selenium in the soil, which is more than the 0.01 to 2 mg Se/kg range for most soils. This value however does not equate Oklahoma to be a seleniferous environment. While high selenium levels in soils may be tolerable, comparative values in drinking waters can be considered health hazard.

Water samples collected from each county also indicated that greater than 80 percent of the groundwaters in Oklahoma contain higher selenium levels than the allowable limit for drinking waters, which is 0.01 mg Se/L. However, based on the recent allowable limit (to be passed in 1992) of 0.05 mg Se/L in drinking waters, only 9 of the 77 counties (Tulsa, Kay, Alfalfa, Dewey, Custer, Washita, Kiowa, Harmon, and Tillman) exceeded the permissible level. Among these counties, six are located in the Southwestern part of the state in the vicinity which once was a large uranium mine. Such mines have been linked with high levels of selenium in the spoils and runoff. Tulsa county which is in the Northeastern part of the state is located near abandoned coal and ore mines and several industrial activities. These facilities may serve as sources of selenium. On the other hand, counties located near abandoned coal mines contained selenium within the acceptable level.

The field lysimeter setup consisted of devices that measured soil moisture, pH, Eh, temperature, and gas. The lysimeter was buried at depths of 1 ft, 3 ft, and 5 ft. The Eh electrodes were constructed, tested, and assembled in the laboratory. Moisture tensimeters were purchased from a supplying company and assembled on site. All parts of the lysimeter were constructed, assembled, and installed by graduate students that worked on the project. Parameters measured in the field included soil moisture, pH, Eh, soil and ambient air temperature, and soil gas. An abandoned coal mine field in Henryetta, Oklahoma was selected as the site for the study. The site was sectioned into three categories: spoil,

reclaimed, and undisturbed (control). Each section had a lysimeter that consisted of triplicate access tubes for each of the parameters stated above. Soil moisture was measured by buried tensiometers, soil air by disposable vacutainers, Eh by platinum electrode, and soil temperature by a thermometer. Soil and spoil samples were also collected from different depths using a motorized auger.

Data collected in the field and in the laboratory indicated that selenium level in the coal mine spoil was low. The amount found was much lower than those found in the soils from various counties in Oklahoma. The form of selenium found was selenite which is known to be less mobile than selenate. The pH of the spoil (overburden) ranged from 3.9 at the 1 ft depth to 4.2 at the 5 ft depth. The pH of the reclaimed site was the same as that of the spoil. The control soil had a pH range of 5.3 at the 1 ft depth and 6.2 at the 5 ft depth. Spoil and soil moisture tension readings were higher at the 1 ft depth and successively lower at the lower depths. This was found to be consistent with changes in the ambient environment.

Evaluation of the field and laboratory data indicated that the spoil (overburden) has equilibrated long enough (over 50 years since active mining has ceased) that selenite will not be expected to leach out of the system. Therefore, based on this study, abandoned coal mine overburden may not contribute as a point source for selenium in the environment. Microbial activity as well as oxidation-reduction reactions could play important roles in transforming stable and soluble selenium species into volatile forms. These forms of selenium associated with minerals in the overburden may have already been lost.

2. Recommendations

This project has revealed that selenium from coal mine spoils is not a major environmental contaminant. Since the site selected for this study has been inactive for over 50 years, perhaps a more recent mine site may reveal a different conclusion. However, literature review has indicated that other anthropogenic sources, such as fly ash from coal firing plants contain a considerable amount of selenium in them. Since most of the fly ash produced in this country is disposed of in landfills, it could leach selenium into the

environment. It is also the opinion of the investigators that microbial transformation of selenium in active mines spoils, seleniferous minerals, and fly ash be investigated. The recent change in the regulation of selenium levels in drinking water seems to indicate that selenium may not be as toxic as it was once considered.

REFERENCES

1. Rosenfeld, Irene and Orville Beath, Chemistry of Selenium; Selenium, pp 299-329, McGraw Hill publishing Co., 1964.
2. McNeal, J. M., and L. S. Balistrieri, Geochemistry and Occurrence of Selenium - An Overview; American Society of Agronomy Inc. Special Publication No. 23; pp 15-50; 1989.
3. Schroeder, H. A. et al., Diseases due to Selenium, Journal of Chronic Diseases, 23:227, 1970.
4. Faust, Samuel and Osman Aly, Trace Elements in Aquatic Environment; Chemistry of Natural Waters; John Willey Publishers. pp 301-380, 1981.
5. USEPA, National Interim Primary Drinking Water Regulations, EPA-570/9-76-003, Washington, DC 1976.
6. Luttrell, G. W., Geology of Selenium, US Geological Survey Bulletin No 1019 M, Washington, DC 1959.
8. Lakin, H. W., In: Trace Elements in the Environment, Advances in Chemistry series 123, pp 96, 1973
9. Byers, H. G. et al., Commercial Uses of Selenium, Industrial Engineering and Chemical Engineering, Edition 28, pp 821, 1936.
10. Connor, J. J. and Shacklette, H. T., Background Geochemistry of Some Rocks, Soils, Plants and Vegetables in the Conterminous US, US Geological Survey, No. 574-F, Pl26, 1975.
11. National Academy of sciences (NAS) Selenium, Washington, 1976.
12. Goldberg, E. D. and K. K. Turekian, Marine Chemistry, Radioactivity in the Marine Environment NAS-NRC, Washington, 1971.
13. Mayland, James and Panter, Selenium in Seleniferous Environment, S.S.S.A., Selenium in Agriculture and in Environment, #23, 1989.
14. Sudhirender Sharma and Ramendra Singh, Selenium in Soil, Plants and Animal System, CRC Vol 13, Issue 1, 1989.
15. Johnson, C. M., Residue Reviews: Selenium in Environment, Vol. 62, pp 102-125, 1976.
16. Alina Kobata-Pendias, Element of Group VI, Trace Elements in Soils and Plants, CRC press, pp. 185-191, 1984.
17. Garrett Fleming, Essential Micronutrients II, Iodine and Selenium, Applied Trace Elements, pp. 199-234.

18. Ohlendorf, H. M., Bioaccumulation and Effects of Selenium in Wildlife, In: Selenium in Agriculture and the Environment, SSSA Special Publication No. 23, 1989.
19. Robberecht, H. and R. von Grieken, Selenium in Environment and Waters: Determination, Speciation, and Concentration Levels, *Talanta* 29,: 823-844, 1982.
20. Bertine, K. K. and E. D. Goldberg, Fossil Fuel Combustion and the Major Sedimentary Cycle, *Science*, 173: 233-235, 1971.
21. Anderson, A. and K. O. Nilsson, Enrichment of Trace Elements from SAewage Sludge Fertilizer in Soils and Plants, *Ambio* 1, 176, 1972.
22. Pratley, J. E. and J. D. McFarlane, The Effect of Sulfate on the Selenium Content of Pasture Plants, *Austral. Jour. Exp. Agric. Animal Husbandry*, No. 14, p. 533, 1974.
23. Andren, Talmi, Selenium in Coal Fired Steam Plant Emmissions; *Environmental Science and Technology*, Vol. 9, pp 856-858, 1975.
24. Eisenberg S. H., Chemical Characteristics of Selected Fly Ash Leachates, *Journal of Environmental Science and Health*, pp 383-402, part 21, 1986.
25. Pillay, Kaminski, Neutron Activation Analysis of Selenium Content of Fossil Fuels, *Nucl. Appl. Tech.*, 7:478-483.
26. Selenium in Medical and Biological Effects of Environmental Pollutants, NAS pp. 23, 1976.
27. Gregory A cutter, Selenium in Fresh Water Systems, Occurrence and Distribution of Selenium, CRC press Inc pp. 243-260.
28. Mayland, James and Soudergger, Selenium in Seleniferous Environment, SSSA Special Publication No. 23, pp15-44, 1989.
29. Harry Ohlendorf, Bioaccumulation and Effects of Selenium in Wildlife, SSSA Special Publication No. 23, pp. 133-177, 1989.
30. Cook and Bouland, Aquatic Chemistry of Selenium, *Enviromental Science and Technology*, No. 21, pp. 1214-12, 1987.
31. Owen Bricker, Redox Potential, *Water Analysis*, No.1, pp. 55-83, 1987.
32. Susan Gibson, Use of Transport/Transformation Matrices, M.S. Thesis, University of Oklahoma, 1981.
33. Steven Deveral, Millard, Distribution and Mobility of Selenium in Shallow Groundwater of the Western San Joaquin Valley, *Environmental Science and Technology*, No. 22, pp. 697-702, 1988.

34. Standard Methods for Examination of Water and Wastewater, Preliminary Treatment of Samples, pp. 3-5 to 3-9, 17th edition, 1989.
35. Flameless Atomic Absorption Spectroscopy, Information Manual, pp. 313-335, 1980.
36. Alina Kabata-Pendias, Elements of Group VI, Trace Elements in Soils and Plants, CRC Press, pp. 185-191, 1984.
37. Lansche, A.M. 1965. Selenium. In: Mineral facts and problems. Bull. 630, U.S. Bureau of Mines.
38. Connor J.J., and Shacklette, H.T., 1975. Background geochemistry of some rocks, soils, plants, and vegetables in the conterminous United States. U.S. Geological Survey Professional Paper 574-F, p126.
39. National Academy of Sciences (NAS). 1976. Selenium. NAS, Washington, D.C.
40. Goldberg, E.D and K.K. Turekian. 1971. Marine Chemistry. Radioactivity in the marine environment. NAS-NRC, Washington, DC.
41. Lakin, H.W. 1973. Selenium in our environment. In: Trace elements in the environment. Adv. Chem. Ser. 123, 96.
42. Swaine, D.J. 1955. The trace element content of soils. Commonw. Bur. Soil Sci., Tech. Commun., p.48
43. C.M. Johnson. 1976. Selenium in the environment. Residue Reviews. Vol. 62, pp. 111.
44. Allaway, W.H. 1971. Distribution of selenium. In: Selenium in nutrition. Washington, D.C. Nat. Acad. Sci.
45. Harry M. Ohlendorf. 1989. Bioaccumulation and effects of selenium in wildlife. Selenium in Agriculture and the environment. SSSA Special Publication Number 23.
46. Robberecht, H., and R. von Grieken. 1982. Selenium in Environment Waters: Determination, speciation and concentration levels. Talanta 29: 823-844.
47. Bertine, K.K., and E.D. Goldberg. 1971. Fossil fuel combustion and the major sedimentary cycle. Science. 173:233-235.
48. Hashimoto, Y., and S. Yanagisawa. 1970. Possible sources of atmospheric pollution of selenium. Environmental Science and Technology. 4, 157.
49. Andersson, A., and K.O. Nilsson. 1972. Enrichment of trace elements from sewage sludge fertilizer in soils and Plants. Ambio 1, 176.
50. Pratley, J.E., and J.D. McFarlane. 1974. The effect of sulphate on the selenium content of pasture plants. Austral. J. Expt. Agr. Animal Husbandry. 14, 533.

51. Mayland, H.F., and J.L. Sonderegger. 1989. Selenium in Seleniferous Environments. *Selenium in Agriculture and the Environment*, pp. 19.
52. Pillay, K.K. S. and J.W. Kaminski. 1969. Neutron activation analysis of the selenium content of fossil fuels. *Nucl.Appl.Technol.* 7:478-483.
53. Eisenberg et al. 1986. Chemical characteristics of selected flyash leachates. *J. Environmental Science. Health Part A* 21:383-402.
54. Andren, A.W. and Y. Talmi. 1975. Selenium in coal-fired steam plant emissions. *Environ. Sci. Technol.* 9:856-858
55. Boon, D.Y., and P.J. Smith. 1985. Carbonaceous materials: problems associated with reclamation. *Am.Soc. Surface Mining Recl.* 2:248-256.
56. Richard, J.E. and Hansford, T.S. 1982. Geochemistry of some rocks, mine spoils, stream sediments, soils, plants, and waters in the western energy region of the conterminous united states. *U.S. Geological Survey Professional Paper* 1237.
57. Elrashidi, E.A., et al. 1987. Chemical equilibria of selenium in soils: A theoretical development. *Soil Science.* Vol.144, No.2, P141-152.
58. Rajan, S.S. 1979. Adsorption of selenite, phosphate, and sulfate on hydrous alumina. *J. Soil Sci.* 30: 709-718.
59. Elrashidi, E.A., et al. 1989. Solubility, speciation, and transformation of selenium in soils. *Selenium in Agriculture and the environment*. SSSA special publication No.23. P51-63.
60. Shirft, A. 1973. Metabolism of selenium by plants and microorganisms, in: *organic selenium compounds: Their chemistry and biology*. P763-814.
61. Wagner et al. 1967. Preparation and properties of trimethylsulfonium-tetrahydrofolate methyltransferase. *J. Biol. Chem.* 242: 1287-1293.
62. Doran, J.W., and Alexander, M., 1977. Microbial transformations of selenium. *Appl. Environ. Microbiol.* 33:31-37.
63. Kadota, H., and Ishida, Y., 1972. Production of volatile sulfur compounds by microorganisms. *Annu. Rev. Microbiol.* 26:127-138.
64. Lewis, B.G., et al. 1974. Volatile selenium in higher plants. The production of dimethyl selenide in cabbage leaves by enzymetic cleavage of Se-methyl Selenomethionine selenonium salt. *Plant Soil.* 40:107- 118.
65. Segal, W., and Starkey, R., 1969. Microbial decomposition of methionine and identity of the resulting sulfur products. *J. Bacteriol.* 98:908-913.
66. Coch, E.H., and Greene, R.C. 1971. The utilization of selenomethionine. *Biochim.Biophys. Acta.* 230:223-236.

67. John W. Doran. 1982. Microorganisms and the biological cycling of selenium. Microbial ecology. Vol.6.
68. Collins, J. M., et al. 1973. Regulatory features of the cysteins desulfhydrase of salmonella typhimurium. Biochim. Biophys. Acta. 313:156-162.
69. Thressa, C.S. 1987. Selenium biochemistry. J. Science. Vol. 183. P915-924.
70. Reuveny, Z. 1977. Proc. Natl. Acad. Sci. U.S.A. 74:619-624.
71. Anderson, J.W., and A.R. Scarf. 1987. Selenium and plant metabolism. La Trobe Univ. Bundoora, Victoria, Australia.
72. Nissen, P., and A.A. Benson. 1964. Absence of selenate esters and "selenolipid" in plants. Biochim. Biophys. Acta 82:400-402.
73. Ronald Eisler. 1985. Selenium hazards to fish, wildlife, and invertebrates: A synoptic review. U.S. Department of Interior.
74. National Academy of Science-National Research Council. 1976. Selenium-medical and biological effects of environmental pollutants. NAS-NRC, Washington, DC.
75. Rosenfeld I., O.A. Beath. 1964. Selenium. Geobotany, biochemistry, toxicity and nutrition. Academic press, New York.
76. Fishbien, L. 1977. Toxicology of selenium and tellurium. Advances in modern toxicology. Vol.2. Toxicology of trace elements. Hemisphere publ. Corp., Washington, DC.
77. Bonucci, E., and R. Sadun. 1973. Experimental calcification of the myocardium: Ultrastructural and histochemical investigations. Amer. J. Path. 71: 167-192.
78. U.S. Environmental Protection Agency. 1980. Ambient water quality criteria for selenium. USEPA Rep. 440/5-80-70. USEPA, Washington, DC.
79. Niimi, A.J., and Q.N. LaHam. 1975. Selenium toxicity on the early life stages of zebrafish (Brachydanis rerio). J. Fish Res. Board Canada. 32:803-806.
80. Stephen B.M. 1989. Selenium in Agricultural and drainage: essential nutrient or toxic threat? J. Drainage Engineering. Vol.115. No.1. P21-27.
81. Sorensen, et al. 1984. Histopathological, hematological, condition-factor, and organ weight changes associated with selenium accumulation in fish from Belew Lake, North Carolina. Arch. Environ. Contam. Toxicol. 13:153-162.
82. Browne and Dumont. 1979. Toxicity of selenium to developing xenopus laevis embryos. J. Toxicol. Environ. Health. 5:699-709.

83. Adams, et al. 1977. Survey of selenium content in the aquatic biota of western lake Erie. J.Great Lake Res. 3:10-14.
84. Cumbie, et al. 1978. Selenium accumulation associated with fish mortality and reproductive failure. Pro. Annu. Conf. Southeast. Assoc. Fish Wildl. Agencies. 32:612-624.
85. Harr, J.R. 1979. Biological effects of selenium. Toxicity of heavy metals in the environment. Part 1. Narcl Dekker, New York.
86. Ohlendorf, H.M., et al. 1988. Embryonic mortality and abnormalities of aquatic birds: apparent impacts by selenium from irrigation drain water. Sci. Total. Environ.
87. Smith, M.I., et al. 1936. The selenium problem in relation to public health. A preliminary survey to determine the possibility of selenium intoxication in the rural population living on seleniferous soil. U.S. Pub. Health Rep. 51:1496.
88. Guangqi yang, et al. 1983. Endemic selenium intoxication of humans in China. The American Journal of Clinical Nutrition. 37:872-881.
89. Beath, O.A. 1962. The story of selenium in Wyoming. University of Wyoming, Laramie.
90. Hadjimarkos, D.M. 1969. Selenium: A caries enhancing trace element. Caries Res. 3:14.
91. Muhleman, N. and K. Konig. 1964. Caries activity of male and female Osborne-bonded rats in different environments. Helv. Odontol. Acta. 8:79.
92. Nelson, et al. 1943. Liver tumors following cirrhosis caused by selenium in rats. Cancer Research. Vol.3. P230.
93. Schroeder, H.A., and M. Mitchener. 1971. Selenium and tellurium in rats: Effects on growth, survival and tumors. J. Nutr. 101:1531.
94. Shamberger, R.J., and D.V. Frost. 1969. Possible protective effects of selenium against human cancer. Can. Med. Assoc. J. 100:682.
95. Shapiro, J.R. 1972. Selenium and carcinogenesis. A review. Ann. N.Y. Acad. Sci. 192:215.
96. Shamberger, R.J., et al. 1972. Antioxidations in cereals and in food preservatives and declining gastric cancer mortality. Cleveland Clin. Quart. 39:119-124.
97. U.S. Food and Drug Administration, 1974. Selenium vitamin E, injection, veterinary. Fed. Reg. 38 (123), 16858.
98. Van Rij, A.M., et al. 1979. Selenium deficiency in total parenteral nutrition. Am. J. Clin. Nutr. 32:2076.

99. Diplock, A.T. 1987. Trace elements in human health with special reference to selenium. Am. J. Clin. Nutr. 45:1313.
100. U.S. Public Health Service. 1962. Drinking Water Standards. U.S. Dept. of Health Edu. Welfare, Publ. No. 96.
101. Drinking water and health, Recommendations of the National Academy of Science. 1977. Fed. Reg. 42: 132:35764.
102. U.S.-EPA. 1975. Evaluation of land application systems. Technical Bulletin. 430/9-75-001.
103. U.S.-EPA. 1986. Ambient water quality criteria for selenium. EPA 440/5-80-070.
104. Patterson.J.W. 1976. Directory of Federal and State Water pollution standards. Illinois Inst. for environmental quality.
105. Ronald.C.F., et al. 1977. Economic impact of the selenium effluent standards in Illinois. Illinois Inst. for environmental quality.
106. Effluent treatment and disposal. 1986. The Institution of Chemical Engineers Symposium Series No. 96.
107. U.S.-EPA. 1976. Rationale for recommended list of priority pollutants. Memo to director of effluent guideline division.
108. Bolten G., et al. 1987. Risk assessment of toxic emissions: Alternative models and practice. EPRI EA-5359 Final Report.
109. Zison, et al. 1977. Water quality assessment: A screening method for nondesignated 208 areas, U.S. Environmental Protection Agency, EPA-600/9-77-023, Athens, Goergia.
110. Whelan, G., and S.M.Brown. 1984. Contaminant assessment modeling under the Resource Conservation and Recovery Act. Battelle Pacific Northwest Laboratories, Draft Report, Richland, Washington.
111. Oster, C.A. 1982. Review of groundwater flow and transport models in the unsaturated Zone. Battle Pacific Northwest Laboratories, PNL-4427, NUREG/CR-2917, Richland, Washington.
112. Thomas, S.D., et al. 1982. A summary of repository siting models, U.S. Nuclear Regulatory Commission, NUREG/CR-2782, Washington,D.C.
113. Wang, et al. 1980. The state-of-the-Art of Numerical Modeling of Thermodynamic Flow in Fractured Rock Masses, Lawrence Berkeley Laboratory, LBL-10524, Berkeley, CA,1980.
114. James A Erdman and Richard J. Ebens. 1979. Element content of crested wheat grass grown on reclaimed coal spoils and on soils nearby. J. of Range Management, 32(2), P159-161

115. Bautista, E.M. and M.Alexander. 1972. Reduction of inorganic compounds by soil microorganisms. Soil Sci. Soc. Am. Proc. 36: 918-920.
116. Robert.L.M., et al. 1989. Effects of soil flooding on selenium transformation and accumulation by rice. Soil. Sci. Soc. Am. J. Vol.53. p122.
117. Marcia Wood. May, 1989. Selenium-loving plants cleanse the soil. Agricultural Research. P8.
118. Karlson,U., and W.T.Frankenberger, Jr. 1989. Accelerated rates of selenium volatilization from California soils. Soil. Sci. Soc. Am. J. 53: 749 -753.
119. McConnell, K.P., and O.W. Portman. 1952. Toxicity of dimethyl selenide in the rat and mouse. Proc. Soc. Exp. Biol. Med. 79: 230-231.
120. Alan Martin. 1936. Toxicity of selenium to plants and animals. American Journal of Botany. Vol.23. No.7. p. 471-483.
121. Hurd-Karrer. 1933. Inhibition of selenium injury to wheat plants by sulfur. Science. 78:560.
122. Thomas, J.S., and G.S.Logsdon. 1978. Treatment technology to meet the interim primary drinking water regulations for inorganics. J. AWWA. July, 1978. P379-396.
123. Thompson-Eagle, E.T., and W.T. Frankenberger, Jr. 1990. Volatilization of selenium from agricultural evaporation pond water. J. Environment Quality. 19: 125-131.
124. Lindsay, W.L., Chemical Equilibria in Soils, John Wiley and Sons, New York, 1979.
125. Marker, W. Mrs., Personal Communication, 11990. 126. Soil Survey Okmulgee County, Oklahoma, U.S. Department of Agriculture, Washington, D.C., May, 1990.
127. Iinstrumental Methods of Analysis, Willard, Dean, Meritt, and Settle, 6th Ed., Wadsworth Publishing Co., Belmont, C.A., 1981.

APPENDIX A

Data was collected from the Heneryetta experimental study site from July 1990 to July 1991. Access tubes 1-9 were used to obtain measurements from three depths; 30, 90, and 150 cm. The dash (-) does not imply missing data, but rather that a particular access tube was not used to measure that specific parameter. Access tube labeled 0 was used to obtain subsurface temperature and soil samples which were used for pH determinations and as a source of soil for experimental procedures. Many dashes may appear, but they are useful to align columns.

Table 1. Measurements of soil water, pH, Eh, Total Se, and Subsurface Temperature at the Henryetta Experimental Field Site.

Date and Experimental Site	Component	Depth - cm -	Measurement Access Tube											
			0	1	2	3	4	5	6	7	8	9		
7-26-90	Reclamation	Eh (mv)	-	-	-	-	-	-	-	-	-	-	-	-
		0	-	-	-	-	-	-	-	-	-	-	-	-
		30	-	410	534	-	-	-	-	-	420	-	-	-
		90	-	-	-	470	-	384	-	-	-	-	465	-
	150	-	-	-	-	451	-	417	-	-	460	-	-	
	Soil Moisture (centibars)	0	-	-	-	-	-	-	-	-	-	-	-	-
		30	-	-	-	-	66	-	54	-	-	80	-	-
		90	-	-	19	15	-	-	-	-	-	14	-	-
		150	-	25	-	-	-	04	-	04	-	-	-	-
	Temperature °C	0	31	-	-	-	-	-	-	-	-	-	-	-
30		-	-	-	-	-	-	-	-	-	-	-	-	
90		-	-	-	-	-	-	-	-	-	-	-	-	
150		-	-	-	-	-	-	-	-	-	-	-	-	
Control	Eh (mv)	-	-	-	-	-	-	-	-	-	-	-	-	
	0	-	-	-	-	-	-	-	-	-	-	-	449	
	30	-	-	-	495	-	-	-	475	-	-	-	-	
	90	-	367	-	-	403	-	065	-	-	-	-	-	
150	-	335	-	-	390	409	-	-	-	-	-	-		

Table 1. (continued)

Date and Experimental Site	Component	Depth - cm -	Measurement Access Tube										
			0	1	2	3	4	5	6	7	8	9	
	Soil Moisture (centibars)	0	-	-	-	-	-	-	-	-	-	-	-
		30	-	-	06	-	-	38	-	-	-	32	-
		90	-	-	-	28	-	-	-	27	-	-	28
		150	-	-	10	-	-	-	09	-	-	14	-
	Temperature °C	0	31	-	-	-	-	-	-	-	-	-	-
		30	-	-	-	-	-	-	-	-	-	-	-
		90	-	-	-	-	-	-	-	-	-	-	-
		150	-	-	-	-	-	-	-	-	-	-	-
Overburden	Eh (mv)	0	-	-	-	-	-	-	-	-	-	-	-
		30	-	521	-	-	-	365	-	-	-	-	500
		90	-	-	349	-	440	-	-	376	-	-	-
		150	-	-	-	-114	-	-	345	-	441	-	-
	Soil Moisture (centibars)	0	-	-	-	-	-	-	-	-	-	-	-
		30	-	-	-	12	-	-	09	-	12	-	05
		90	-	54	-	-	-	41	-	-	-	-	-
		150	-	-	40	-	15	-	-	20	-	-	-
	Temperature °C	0	31	-	-	-	-	-	-	-	-	-	-
		30	-	-	-	-	-	-	-	-	-	-	-
		90	-	-	-	-	-	-	-	-	-	-	-
		150	-	-	-	-	-	-	-	-	-	-	-

Table 1. (continued)

Date and Experimental Site	Component	Depth - cm -	Measurement Access Tube									
			0	1	2	3	4	5	6	7	8	9
7-31-90												
Reclamation	Eh (mv)	0	-	-	-	-	-	-	-	-	-	-
		30	-	-	-	-	-	-	-	-	-	-
		90	-	-	-	-	-	-	-	-	-	-
		150	-	-	-	-	-	-	-	-	-	-
	Soil Moisture (centibars)	0	-	-	-	-	-	-	-	-	-	-
		30	-	-	-	-	54	-	67	-	-	00
		90	-	-	19	22	-	-	-	-	17	-
		150	-	05	-	-	-	26	-	04	-	-
	Temperature °C	0	27	-	-	-	-	-	-	-	-	-
		30	-	-	-	-	-	-	-	-	-	-
		90	-	-	-	-	-	-	-	-	-	-
		150	-	-	-	-	-	-	-	-	-	-
Control	Eh (mv)	0	-	-	-	-	-	-	-	-	-	-
		30	-	-	-	-	-	-	-	-	-	-
		90	-	-	-	-	-	-	-	-	-	-
		150	-	-	-	-	-	-	-	-	-	-

Table 1. (continued)

Date and Experimental Site	Component	Depth - cm -	Measurement Access Tube									
			0	1	2	3	4	5	6	7	8	9
	Soil Moisture (centibars)	0	-	-	-	-	-	-	-	-	-	-
		30	-	-	00	-	-	00	-	-	00	-
		90	-	-	-	36	-	-	-	00	-	24
		150	-	-	09	-	-	-	06	-	09	-
	Temperature °C	0	27	-	-	-	-	-	-	-	-	-
		30	-	-	-	-	-	-	-	-	-	-
		90	-	-	-	-	-	-	-	-	-	-
		150	-	-	-	-	-	-	-	-	-	-
Overburden	Eh (mv)	0	-	-	-	-	-	-	-	-	-	-
		30	-	-	-	-	-	-	-	-	-	-
		90	-	-	-	-	-	-	-	-	-	-
		150	-	-	-	-	-	-	-	-	-	-
	Soil Moisture (centibars)	0	-	-	-	-	-	-	-	-	-	-
		30	-	-	-	01	-	-	11	-	04	-
		90	-	59	-	-	-	48	-	-	-	04
		150	-	-	44	-	76	-	-	21	-	-
	Temperature °C	0	27	-	-	-	-	-	-	-	-	-
		30	-	-	-	-	-	-	-	-	-	-
		90	-	-	-	-	-	-	-	-	-	-
		150	-	-	-	-	-	-	-	-	-	-

Table 1. (continued)

Date and Experimental Site	Component	Depth - cm -	Measurement Access Tube									
			0	1	2	3	4	5	6	7	8	9
8-15-90												
Reclamation	Eh (mv)	0	-	-	-	-	-	-	-	-	-	-
		30	-	414	494	-	-	-	-	457	-	-
		90	-	-	-	465	-	460	-	-	-	451
		150	-	-	-	-	396	-	483	-	319	-
	Soil Moisture (centibars)	0	-	-	-	-	-	-	-	-	-	-
		30	-	-	-	-	38	-	67	-	-	00
		90	-	-	20	-	-	-	-	30	23	-
		150	-	07	-	-	-	30	-	06	-	-
	Temperature °C	0	32	-	-	-	-	-	-	-	-	-
		30	-	-	-	-	-	-	-	-	-	-
		90	-	-	-	-	-	-	-	-	-	-
		150	-	-	-	-	-	-	-	-	-	-
Control	Eh (mv)	0	-	-	-	-	-	-	-	-	-	485
		30	-	-	-	434	-	-	-	-056	-	-
		90	-	451	-	-	470	-	-007	-	-	-
		150	-	384	-	-	441	387	-	-	-	-

Table 1. (continued)

Date and Experimental Site	Component	Depth - cm -	Measurement Access Tube									
			0	1	2	3	4	5	6	7	8	9
Soil Moisture (centibars)	0	-	-	-	-	-	-	-	-	-	-	-
	30	-	-	08	-	-	-	03	-	-	05	-
	90	-	-	-	37	-	-	-	04	01	-	16
	150	-	-	09	-	-	-	-	-	-	03	-
Temperature °C	0	27	-	-	-	-	-	-	-	-	-	-
	30	-	-	-	-	-	-	-	-	-	-	-
	90	-	-	-	-	-	-	-	-	-	-	-
	150	-	-	-	-	-	-	-	-	-	-	-
Overburden Eh (mv)	0	-	-	-	-	-	-	-	-	-	-	-
	30	-	557	-	-	-	-	066	-	-	-	498
	90	-	-	528	-	-	577	-	-	578	-	-
	150	-	-	-	527	-	-	-	556	-	526	-
Soil Moisture (centibars)	0	-	-	-	-	-	-	-	-	-	-	-
	30	-	-	-	26	-	-	-	01	-	56	-
	90	-	54	-	-	-	-	44	-	-	-	10
	150	-	-	48	-	18	-	-	-	29	-	-
Temperature °C	0	32	-	-	-	-	-	-	-	-	-	-
	30	-	-	-	-	-	-	-	-	-	-	-
	90	-	-	-	-	-	-	-	-	-	-	-
	150	-	-	-	-	-	-	-	-	-	-	-

Table 1. (continued)

Date and Experimental Site	Component	Depth - cm -	Measurement Access Tube													
			0	1	2	3	4	5	6	7	8	9				
8-22-90	Reclamation	Eh (mv)	0	-	-	-	-	-	-	-	-	-	-	-	-	-
			30	-	408	479	-	-	-	-	-	-	461	-	-	-
			90	-	-	-	414	-	456	-	-	-	-	-	-	459
			150	-	-	-	-	399	-	499	-	-	-	321	-	-
	Soil Moisture (centibars)		0	-	-	-	-	-	-	-	-	-	-	-	-	-
			30	-	-	-	28	-	69	-	-	-	-	-	-	00
			90	-	-	22	-	-	-	32	-	-	24	-	-	-
			150	-	08	-	-	30	-	-	-	08	-	-	-	-
	Temperature °C		0	31	-	-	-	-	-	-	-	-	-	-	-	-
			30	31	-	-	-	-	-	-	-	-	-	-	-	-
			90	29	-	-	-	-	-	-	-	-	-	-	-	-
			150	27	-	-	-	-	-	-	-	-	-	-	-	-
Control	Eh (mv)		0	-	-	-	-	-	-	-	-	-	-	-	-	
			30	-	-	-	465	-	-	-	-	-176	-	-	489	
			90	-	475	-	-	482	-	096	-	-	-	-	-	
			150	-	385	-	-	440	376	-	-	-	-	-	-	

Table 1. (continued)

Date and Experimental Site	Component	Depth - cm -	Measurement Access Tube										
			0	1	2	3	4	5	6	7	8	9	
	Soil Moisture (centibars)	0	-	-	-	-	-	-	-	-	-	-	-
		30	-	-	14	-	-	09	-	-	04	-	-
		90	-	-	-	30	-	-	-	00	-	14	-
		150	-	-	12	-	-	-	04	-	00	-	-
	Temperature °C	0	34	-	-	-	-	-	-	-	-	-	-
		30	28	-	-	-	-	-	-	-	-	-	-
		90	26	-	-	-	-	-	-	-	-	-	-
		150	24	-	-	-	-	-	-	-	-	-	-
Overburden	Eh (mv)	0	-	-	-	-	-	-	-	-	-	-	-
		30	-	538	-	-	-	087	-	-	-	-	521
		90	-	-	-	-	577	-	-	586	-	-	-
		150	-	-	-	532	-	-	580	-	561	-	-
	Soil Moisture (centibars)	0	-	-	-	-	-	-	-	-	-	-	-
		30	-	-	-	24	-	-	02	-	65	-	00
		90	-	54	-	-	-	63	-	-	-	-	-
		150	-	-	51	-	19	-	-	31	-	-	-
	Temperature °C	0	37	-	-	-	-	-	-	-	-	-	-
		30	-	-	-	-	-	-	-	-	-	-	-
		90	29	-	-	-	-	-	-	-	-	-	-
		150	28	-	-	-	-	-	-	-	-	-	-

Table 1. (continued)

Date and Experimental Site	Component	Depth - cm -	Measurement Access Tube									
			0	1	2	3	4	5	6	7	8	9
8-29-90	Reclamation	Eh (mv)	0	-	-	-	-	-	-	-	-	-
		30	-	416	464	-	-	-	-	293	-	-
		90	-	-	-	377	-	482	-	-	-	506
		150	-	-	-	-	403	-	519	-	332	-
	Soil Moisture (centibars)	0	-	-	-	-	-	-	-	-	-	-
		30	-	-	-	-	04	-	00	-	-	00
		90	-	-	22	-	-	-	-	33	26	-
		150	-	10	-	-	-	32	-	09	-	-
	Temperature °C	0	41	-	-	-	-	-	-	-	-	-
		30	33	-	-	-	-	-	-	-	-	-
		90	29	-	-	-	-	-	-	-	-	-
		150	27	-	-	-	-	-	-	-	-	-
	pH	0	-	-	-	-	-	-	-	-	-	-
		30	3.4	-	-	-	-	-	-	-	-	-
		90	4.3	-	-	-	-	-	-	-	-	-
		150	4.9	-	-	-	-	-	-	-	-	-

Table 1. (continued)

Date and Experimental Site	Component	Depth - cm -	Measurement Access Tube										
			0	1	2	3	4	5	6	7	8	9	
Control	Eh (mv)	0	-	-	-	-	-	-	-	-	-	-	-
		30	-	-	-	493	-	-	-	188	-	454	
		90	-	462	-	-	484	-	207	-	-	-	
		150	-	383	-	-	422	367	-	-	-	-	
	Soil Moisture (centibars)	0	-	-	-	-	-	-	-	-	-	-	
		30	-	-	26	-	-	16	-	-	12	-	
		90	-	-	-	24	-	-	-	06	-	12	
		150	-	-	12	-	-	-	07	-	02	-	
	Temperature °C	0	42	-	-	-	-	-	-	-	-	-	
		30	29	-	-	-	-	-	-	-	-	-	
		90	27	-	-	-	-	-	-	-	-	-	
		150	25	-	-	-	-	-	-	-	-	-	
	pH	0	-	-	-	-	-	-	-	-	-	-	
		30	5.8	-	-	-	-	-	-	-	-	-	
		90	6.9	-	-	-	-	-	-	-	-	-	
		150	6.9	-	-	-	-	-	-	-	-	-	
Overburden	Eh (mv)	0	-	-	-	-	-	-	-	-	-	-	
		30	-	550	-	-	-	111	-	-	-	495	
		90	-	-	578	-	591	-	-	602	-	-	
		150	-	-	-	580	-	-	598	-	575	-	

Table 1. (continued)

Date and Experimental Site	Component	Depth - cm -	Measurement Access Tube									
			0	1	2	3	4	5	6	7	8	9
	Soil Moisture (centibars)	0	-	-	-	-	-	-	-	-	-	-
		30	-	-	-	30	-	-	03	-	66	-
		90	-	55	-	-	-	60	-	-	-	12
		150	-	-	54	-	22	-	-	42	-	-
	Temperature °C	0	41	-	-	-	-	-	-	-	-	-
		30	33	-	-	-	-	-	-	-	-	-
		90	30	-	-	-	-	-	-	-	-	-
		150	28	-	-	-	-	-	-	-	-	-
	pH	0	-	-	-	-	-	-	-	-	-	-
		30	3.9	-	-	-	-	-	-	-	-	-
		90	4.0	-	-	-	-	-	-	-	-	-
		150	4.2	-	-	-	-	-	-	-	-	-
9-12-90												
Reclamation	Eh (mv)	0	-	-	-	-	-	-	-	-	-	-
		30	-	391	484	-	-	-	-	397	-	-
		90	-	-	-	376	-	284	-	-	-	568
		150	-	-	-	-	399	-	537	-	-106	-

Table 1. (continued)

Date and Experimental Site	Component	Depth - cm -	Measurement Access Tube									
			0	1	2	3	4	5	6	7	8	9
Soil Moisture (centibars)	0	-	-	-	-	-	-	-	-	-	-	-
	30	-	-	-	00	-	-	00	-	-	-	00
	90	-	-	22	-	-	-	-	42	-	19	-
	150	-	08	-	-	-	33	-	-	10	-	-
Temperature °C	0	27	-	-	-	-	-	-	-	-	-	-
	30	29	-	-	-	-	-	-	-	-	-	-
	90	28	-	-	-	-	-	-	-	-	-	-
	150	26	-	-	-	-	-	-	-	-	-	-
pH	0	-	-	-	-	-	-	-	-	-	-	-
	30	4.2	-	-	-	-	-	-	-	-	-	-
	90	4.2	-	-	-	-	-	-	-	-	-	-
	150	4.2	-	-	-	-	-	-	-	-	-	-
Control Eh (mv)	0	-	-	-	-	-	-	-	-	-	-	488
	30	-	-	-	484	-	-	-	-	466	-	-
	90	-	448	-	-	-	445	-	211	-	-	-
	150	-	354	-	-	-	431	373	-	-	-	-
Soil Moisture (centibars)	0	-	-	-	-	-	-	-	-	-	-	-
	30	-	-	67	-	-	-	63	-	-	54	-
	90	-	-	-	32	-	-	-	-	08	03	-
	150	-	-	11	-	-	-	-	06	-	-	12

Table 1. (continued)

Date and Experimental Site	Component	Depth - cm -	Measurement Access Tube										
			0	1	2	3	4	5	6	7	8	9	
	Temperature °C	0	32	-	-	-	-	-	-	-	-	-	-
		30	27	-	-	-	-	-	-	-	-	-	-
		90	26	-	-	-	-	-	-	-	-	-	-
		150	25	-	-	-	-	-	-	-	-	-	-
	pH	0	-	-	-	-	-	-	-	-	-	-	-
		30	5.3	-	-	-	-	-	-	-	-	-	-
		90	6.1	-	-	-	-	-	-	-	-	-	-
		150	6.2	-	-	-	-	-	-	-	-	-	-
	Overburden Eh (mv)	0	-	-	-	-	-	-	-	-	-	-	505
		30	-	534	-	-	-	118	-	-	-	-	-
		90	-	-	564	-	602	-	594	-	-	-	-
		150	-	-	-	555	-	-	599	-	561	-	-
Soil Moisture (centibars)	0	-	-	-	-	-	-	-	-	-	-	-	
	30	-	-	-	67	-	-	02	-	00	-	20	
	90	-	63	-	-	-	65	-	-	-	-	-	
	150	-	-	69	-	22	-	-	52	-	-	-	
Temperature °C	0	27	-	-	-	-	-	-	-	-	-	-	
	30	29	-	-	-	-	-	-	-	-	-	-	
	90	30	-	-	-	-	-	-	-	-	-	-	
	150	28	-	-	-	-	-	-	-	-	-	-	

Table 1. (continued)

Date and Experimental Site	Component	Depth - cm -	Measurement Access Tube									
			0	1	2	3	4	5	6	7	8	9
	pH	0	-	-	-	-	-	-	-	-	-	-
		30	4.0	-	-	-	-	-	-	-	-	-
		90	4.0	-	-	-	-	-	-	-	-	-
		150	3.9	-	-	-	-	-	-	-	-	-
	Total Se (mg/kg)	0	-	-	-	-	-	-	-	-	-	-
		30	0.12	-	-	-	-	-	-	-	-	-
		90	0.09	-	-	-	-	-	-	-	-	-
		150	< 0	-	-	-	-	-	-	-	-	-
	Reclamation	Eh (mv)	0	-	-	-	-	-	-	-	-	-
			30	418	471	-	-	-	-	406	-	-
		90	-	-	364	-	-	423	-	-	586	
		150	-	-	-	-	406	-	617	319	-	
	Soil Moisture (centibars)	0	-	-	-	-	-	-	-	-	-	
		30	-	-	-	-	00	-	00	-	00	
		90	-	-	26	-	-	-	-	55	38	
		150	-	10	-	-	-	34	-	10	-	

9-24-90

Table 1. (continued)

Date and Experimental Site	Component	Depth - cm -	Measurement Access Tube									
			0	1	2	3	4	5	6	7	8	9
Temperature °C		0	22	-	-	-	-	-	-	-	-	-
		30	21	-	-	-	-	-	-	-	-	-
		90	26	-	-	-	-	-	-	-	-	-
		150	26	-	-	-	-	-	-	-	-	-
PH		0	-	-	-	-	-	-	-	-	-	-
		30	4.7	-	-	-	-	-	-	-	-	-
		90	4.4	-	-	-	-	-	-	-	-	-
		150	4.5	-	-	-	-	-	-	-	-	-
Control Eh (mv)		0	-	-	-	-	-	-	-	-	-	502
		30	-	475	-	515	-	-	-	-	-	-
		90	-	472	-	-	481	-	285	-	-	-
		150	-	398	-	-	406	418	-	-	-	-
Soil Moisture (centibars)		0	-	-	-	-	-	-	-	-	-	-
		30	-	-	02	-	-	00	-	-	02	-
		90	-	-	-	40	-	-	-	00	-	12
		150	-	-	10	-	-	-	02	-	00	-
Temperature °C		0	25	-	-	-	-	-	-	-	-	-
		30	27	-	-	-	-	-	-	-	-	-
		90	24	-	-	-	-	-	-	-	-	-
		150	24	-	-	-	-	-	-	-	-	-

Table 1. (continued)

Date and Experimental Site	Component	Depth - cm -	Measurement Access Tube									
			0	1	2	3	4	5	6	7	8	9
pH		0	-	-	-	-	-	-	-	-	-	-
		30	6.4	-	-	-	-	-	-	-	-	-
		90	7.4	-	-	-	-	-	-	-	-	-
		150	6.2	-	-	-	-	-	-	-	-	-
Overburden	Eh (mv)	0	-	-	-	-	-	-	-	-	-	-
		30	-	521	-	-	-	197	-	-	-	536
		90	-	-	583	-	605	-	-	602	-	-
		150	-	-	-	565	-	-	607	-	559	-
Soil Moisture (centibars)		0	-	-	-	-	-	-	-	-	-	-
		30	-	06	-	00	-	-	-	-	03	-
		90	-	14	-	-	-	66	-	-	-	26
		150	-	-	75	-	24	-	-	55	-	-
Temperature °C		0	24	-	-	-	-	-	-	-	-	-
		30	22	-	-	-	-	-	-	-	-	-
		90	27	-	-	-	-	-	-	-	-	-
		150	27	-	-	-	-	-	-	-	-	-
pH		0	-	-	-	-	-	-	-	-	-	-
		30	4.2	-	-	-	-	-	-	-	-	-
		90	4.0	-	-	-	-	-	-	-	-	-
		150	4.1	-	-	-	-	-	-	-	-	-

Table 1. (continued)

Date and Experimental Site	Component	Depth - cm -	Measurement Access Tube									
			0	1	2	3	4	5	6	7	8	9
	Total Se (mg/kg)	0	-	-	-	-	-	-	-	-	-	-
		30	0.14	-	-	-	-	-	-	-	-	-
		90	< 0	-	-	-	-	-	-	-	-	-
		150	0.45	-	-	-	-	-	-	-	-	-
10-5-90												
Reclamation	Eh (mv)	0	-	-	-	-	-	-	-	-	-	-
		30	-	370	454	-	-	-	-	-010	-	-
		90	-	-	-	374	-	399	-	-	-	580
		150	-	-	-	-	420	-	596	-	272	-
	Soil Moisture (centibars)	0	-	-	-	-	-	-	-	-	-	-
		30	-	-	-	18	-	-	00	-	00	-
		90	-	-	20	-	-	-	-	60	49	-
		150	-	12	-	-	-	36	-	15	-	-
	Temperature °C	0	24	-	-	-	-	-	-	-	-	-
		30	22	-	-	-	-	-	-	-	-	-
		90	24	-	-	-	-	-	-	-	-	-
		150	25	-	-	-	-	-	-	-	-	-

Table 1. (continued)

Date and Experimental Site	Component	Depth - cm -	Measurement Access Tube									
			0	1	2	3	4	5	6	7	8	9
pH		0	-	-	-	-	-	-	-	-	-	-
		30	5.0	-	-	-	-	-	-	-	-	-
		90	5.2	-	-	-	-	-	-	-	-	-
		150	5.2	-	-	-	-	-	-	-	-	-
Control Eh (mv)		0	-	-	-	-	-	-	-	-	-	-
		30	-	-	499	-	-	-	-	061	512	-
		90	-	434	-	491	-	-	260	-	-	-
		150	-	399	-	409	423	-	-	-	-	-
Soil Moisture (centibars)		0	-	-	-	-	-	-	-	-	-	-
		30	-	16	-	-	-	10	-	-	04	-
		90	-	-	44	-	-	-	-	01	-	14
		150	-	08	-	-	-	-	05	-	00	-
Temperature °C		0	24	-	-	-	-	-	-	-	-	-
		30	22	-	-	-	-	-	-	-	-	-
		90	23	-	-	-	-	-	-	-	-	-
		150	22	-	-	-	-	-	-	-	-	-
pH		0	-	-	-	-	-	-	-	-	-	-
		30	7.0	-	-	-	-	-	-	-	-	-
		90	6.3	-	-	-	-	-	-	-	-	-
		150	6.7	-	-	-	-	-	-	-	-	-

Table i. (continued)

Date and Experimental Site	Component	Depth - cm -	Measurement Access Tube											
			0	1	2	3	4	5	6	7	8	9		
Overburden	Eh (mv)	0	-	-	-	-	-	-	-	-	-	-	-	-
		30	-	493	-	-	-	-	206	-	-	-	-	517
		90	-	-	537	-	586	-	-	-	572	-	-	-
		150	-	-	-	555	-	-	-	589	-	550	-	-
	Soil Moisture (centibars)	0	-	-	-	-	-	-	-	-	-	-	-	-
		30	-	-	-	10	-	-	-	30	-	13	-	-
		90	-	21	-	-	-	-	24	-	-	-	15	-
		150	-	-	60	-	25	-	-	-	40	-	-	-
	Temperature °C	0	26	-	-	-	-	-	-	-	-	-	-	-
		30	24	-	-	-	-	-	-	-	-	-	-	-
		90	25	-	-	-	-	-	-	-	-	-	-	-
		150	25	-	-	-	-	-	-	-	-	-	-	-
	pH	0	-	-	-	-	-	-	-	-	-	-	-	-
		30	4.3	-	-	-	-	-	-	-	-	-	-	-
		90	4.1	-	-	-	-	-	-	-	-	-	-	-
		150	4.2	-	-	-	-	-	-	-	-	-	-	-
	Total Se (mg/kg)	0	-	-	-	-	-	-	-	-	-	-	-	-
		30	0.29	-	-	-	-	-	-	-	-	-	-	-
		90	0.33	-	-	-	-	-	-	-	-	-	-	-
		150	0.12	-	-	-	-	-	-	-	-	-	-	-

Table 1. (continued)

Date and Experimental Site	Component	Depth - cm -	Measurement Access Tube										
			0	1	2	3	4	5	6	7	8	9	
10-19-90													
Reclamation	Eh (mv)	0	-	-	-	-	-	-	-	-	-	-	-
		30	-	388	421	-	-	-	-	-	317	-	-
		90	-	-	-	399	-	-	443	-	-	-	610
		150	-	-	-	-	443	-	605	-	-	261	-
	Soil Moisture (centibars)	0	-	-	-	-	-	-	-	-	-	-	-
		30	-	-	-	-	05	-	61	-	-	-	00
		90	-	-	33	-	-	-	-	62	58	-	-
		150	-	12	-	-	-	-	40	18	-	-	-
	Temperature °C	0	17	-	-	-	-	-	-	-	-	-	-
		30	17	-	-	-	-	-	-	-	-	-	-
		90	19	-	-	-	-	-	-	-	-	-	-
		150	21	-	-	-	-	-	-	-	-	-	-
	pH	0	-	-	-	-	-	-	-	-	-	-	-
		30	4.2	-	-	-	-	-	-	-	-	-	-
		90	4.0	-	-	-	-	-	-	-	-	-	-
		150	4.5	-	-	-	-	-	-	-	-	-	-

Table 1. (continued)

Date and Experimental Site	Component	Depth - cm -	Measurement Access Tube										
			0	1	2	3	4	5	6	7	8	9	
Control	Eh (mv)	0	-	-	-	-	-	-	-	-	-	-	520
		30	-	-	-	482	-	-	-	-	-	-	-
		90	-	467	-	-	492	-	309	-	-	-	-
		150	-	413	-	-	442	467	-	-	-	-	-
	Soil Moisture (centibars)	0	-	-	-	-	-	-	-	-	-	-	-
		30	-	-	11	-	-	04	-	-	03	-	-
		90	-	-	-	56	-	-	-	01	-	15	-
		150	-	-	08	-	-	-	04	-	00	-	-
	Temperature °C	0	16	-	-	-	-	-	-	-	-	-	-
		30	16	-	-	-	-	-	-	-	-	-	-
		90	18	-	-	-	-	-	-	-	-	-	-
		150	20	-	-	-	-	-	-	-	-	-	-
pH	0	-	-	-	-	-	-	-	-	-	-	-	
	30	5.6	-	-	-	-	-	-	-	-	-	-	
	90	6.4	-	-	-	-	-	-	-	-	-	-	
	150	6.8	-	-	-	-	-	-	-	-	-	-	
Overburden	Eh (mv)	0	-	-	-	-	-	-	-	-	-	-	495
		30	-	436	-	-	-	223	-	-	-	-	-
		90	-	-	568	-	591	-	-	531	-	-	-
		150	-	-	-	523	-	-	603	-	551	-	-

Table 1. (continued)

Date and Experimental Site	Component	Depth - cm -	Measurement Access Tube									
			0	1	2	3	4	5	6	7	8	9
Soil Moisture (centibars)	0	-	-	-	-	-	-	-	-	-	-	-
	30	-	-	-	05	-	-	12	-	06	-	-
	90	-	13	-	-	-	56	-	-	-	-	10
	150	-	-	59	-	27	-	-	35	-	-	-
Temperature °C	0	17	-	-	-	-	-	-	-	-	-	-
	30	17	-	-	-	-	-	-	-	-	-	-
	90	18	-	-	-	-	-	-	-	-	-	-
	150	20	-	-	-	-	-	-	-	-	-	-
pH	0	-	-	-	-	-	-	-	-	-	-	-
	30	3.4	-	-	-	-	-	-	-	-	-	-
	90	3.8	-	-	-	-	-	-	-	-	-	-
	150	3.6	-	-	-	-	-	-	-	-	-	-
Total Se (mg/kg)	0	-	-	-	-	-	-	-	-	-	-	-
	30	0.28	-	-	-	-	-	-	-	-	-	-
	90	0.62	-	-	-	-	-	-	-	-	-	-
	150	< 0	-	-	-	-	-	-	-	-	-	-

Table 1. (continued)

Date and Experimental Site	Component	Depth - cm -	Measurement Access Tube									
			0	1	2	3	4	5	6	7	8	9
10-31-90												
Reclamation	Eh (mv)	0	-	-	-	-	-	-	-	-	-	-
		30	-	-	430	-	-	-	-	290	-	-
		90	-	-	-	500	-	460	-	-	-	650
		150	-	-	-	-	530	-	600	-	325	-
	Soil Moisture (centibars)	0	-	-	-	-	-	-	-	-	-	-
		30	-	-	-	-	51	-	72	-	-	71
		90	-	-	37	-	-	-	-	64	65	-
		150	-	14	-	-	-	44	-	24	-	-
	Temperature °C	0	22	-	-	-	-	-	-	-	-	-
		30	18	-	-	-	-	-	-	-	-	-
		90	20	-	-	-	-	-	-	-	-	-
		150	20	-	-	-	-	-	-	-	-	-
	pH	0	-	-	-	-	-	-	-	-	-	-
		30	3.7	-	-	-	-	-	-	-	-	-
		90	4.7	-	-	-	-	-	-	-	-	-
		150	4.1	-	-	-	-	-	-	-	-	-

Table 1. (continued)

Date and Experimental Site	Component	Depth - cm -	Measurement Access Tube										
			0	1	2	3	4	5	6	7	8	9	
Control	Eh (mv)	0	-	-	-	-	-	-	-	-	-	-	533
		30	-	-	-	462	-	-	-	-043	-	-	-
		90	-	487	-	-	476	-	311	-	-	-	-
		150	-	314	-	-	444	476	-	-	-	-	-
	Soil Moisture (centibars)	0	-	-	-	-	-	-	-	-	-	-	-
		30	-	-	15	-	-	08	-	-	05	-	-
		90	-	-	-	56	-	-	-	02	-	15	-
		150	-	-	11	-	-	-	06	-	01	-	-
	Temperature °C	0	26	-	-	-	-	-	-	-	-	-	-
		30	17	-	-	-	-	-	-	-	-	-	-
		90	18	-	-	-	-	-	-	-	-	-	-
		150	19	-	-	-	-	-	-	-	-	-	-
	pH	0	-	-	-	-	-	-	-	-	-	-	-
		30	5.9	-	-	-	-	-	-	-	-	-	-
		90	6.7	-	-	-	-	-	-	-	-	-	-
		150	6.7	-	-	-	-	-	-	-	-	-	-
Overburden	Eh (mv)	0	-	-	-	-	-	-	-	-	-	-	-
		30	-	550	-	-	-	540	-	-	-	545	-
		90	-	-	655	-	610	-	-	590	-	-	-
		150	-	-	-	580	-	-	640	-	630	-	-

Table 1. (continued)

Date and Experimental Site	Component	Depth - cm -	Measurement Access Tube									
			0	1	2	3	4	5	6	7	8	9
Soil Moisture (centibars)	0	-	-	-	-	-	-	-	-	-	-	-
	30	-	-	-	18	-	-	-	21	-	12	-
	90	-	18	-	-	-	-	66	-	-	-	20
	150	-	-	44	-	-	31	-	-	38	-	-
Temperature °C	0	24	-	-	-	-	-	-	-	-	-	-
	30	20	-	-	-	-	-	-	-	-	-	-
	90	20	-	-	-	-	-	-	-	-	-	-
	150	21	-	-	-	-	-	-	-	-	-	-
pH	0	-	-	-	-	-	-	-	-	-	-	-
	30	3.5	-	-	-	-	-	-	-	-	-	-
	90	3.7	-	-	-	-	-	-	-	-	-	-
	150	3.6	-	-	-	-	-	-	-	-	-	-
Total Se (mg/kg)	0	-	-	-	-	-	-	-	-	-	-	-
	30	< 0	-	-	-	-	-	-	-	-	-	-
	90	0.16	-	-	-	-	-	-	-	-	-	-
	150	< 0	-	-	-	-	-	-	-	-	-	-

Table 1. (continued)

Date and Experimental Site	Component	Depth - cm -	Measurement Access Tube									
			0	1	2	3	4	5	6	7	8	9
11-16-90												
Reclamation	Eh (mv)	0	-	-	-	-	-	-	-	-	-	-
		30	-	370	415	-	-	-	-	338	-	-
		90	-	-	-	544	-	420	-	-	-	634
		150	-	-	-	-	454	-	591	-	306	-
	Soil Moisture (centibars)	0	-	-	-	-	-	-	-	-	-	-
		30	-	-	-	-	54	-	70	-	-	72
		90	-	-	40	-	-	-	-	64	68	-
		150	-	15	-	-	-	47	-	30	-	-
	Temperature °C	0	17	-	-	-	-	-	-	-	-	-
		30	15	-	-	-	-	-	-	-	-	-
		90	16	-	-	-	-	-	-	-	-	-
		150	18	-	-	-	-	-	-	-	-	-
	pH	0	-	-	-	-	-	-	-	-	-	-
		30	4.3	-	-	-	-	-	-	-	-	-
		90	4.2	-	-	-	-	-	-	-	-	-
		150	4.1	-	-	-	-	-	-	-	-	-

Table 1. (continued)

Data and Experimental Site	Component	Depth - cm -	Measurement Access Tube									
			0	1	2	3	4	5	6	7	8	9
Control	Eh (mv)	0	-	-	-	-	-	-	-	-	-	-
		30	-	-	-	508	-	-	-	-081	-	475
		90	-	215	-	-	534	-	338	-	-	-
		150	-	-024	-	-	483	470	-	-	-	-
	Soil Moisture (centibars)	0	-	-	-	-	-	-	-	-	-	-
		30	-	-	02	-	-	00	-	-	00	-
		90	-	-	-	48	-	-	-	00	-	16
		150	-	-	10	-	-	-	04	-	00	-
	Temperature °C	0	18	-	-	-	-	-	-	-	-	-
		30	15	-	-	-	-	-	-	-	-	-
		90	16	-	-	-	-	-	-	-	-	-
		150	18	-	-	-	-	-	-	-	-	-
	pH	0	0	-	-	-	-	-	-	-	-	-
		30	5.9	-	-	-	-	-	-	-	-	-
		90	6.8	-	-	-	-	-	-	-	-	-
		150	7.1	-	-	-	-	-	-	-	-	-
Overburden	Eh (mv)	0	-	-	-	-	-	-	-	-	-	-
		30	-	-001	-	-	-	127	-	-	-	253
		90	-	-	577	-	611	-	-	572	-	-
		150	-	-	-	567	-	-	614	-	568	-

Table 1. (continued)

Date and Experimental Site	Component	Depth - cm -	Measurement Access Tube									
			0	1	2	3	4	5	6	7	8	9
Soil Moisture (centibars)	0	-	-	-	-	-	-	-	-	-	-	-
	30	-	-	-	02	-	-	10	-	00	-	-
	90	-	12	-	-	-	56	-	-	-	-	08
	150	-	-	40	-	36	-	-	22	-	-	-
Temperature °C	0	16	-	-	-	-	-	-	-	-	-	-
	30	16	-	-	-	-	-	-	-	-	-	-
	90	18	-	-	-	-	-	-	-	-	-	-
	150	19	-	-	-	-	-	-	-	-	-	-
pH	0	-	-	-	-	-	-	-	-	-	-	-
	30	3.9	-	-	-	-	-	-	-	-	-	-
	90	3.7	-	-	-	-	-	-	-	-	-	-
	150	3.8	-	-	-	-	-	-	-	-	-	-
11-30-90												
Reclamation Eh (mv)	0	-	-	-	-	-	-	-	-	-	-	-
	30	-	412	455	-	-	-	-	339	-	-	-
	90	-	-	-	459	-	417	-	-	-	-	640
	150	-	-	-	-	445	-	588	-	376	-	-

Table 1. (continued)

Date and Experimental Site	Component	Depth - cm -	Measurement Access Tube										
			0	1	2	3	4	5	6	7	8	9	
Soil Moisture (centibars)	0	-	-	-	-	-	-	-	-	-	-	-	64
	30	-	-	-	-	48	-	54	-	-	-	-	-
	90	-	-	40	-	-	-	-	62	55	-	-	-
	150	-	17	-	-	-	48	-	32	-	-	-	-
Temperature °C	0	12	-	-	-	-	-	-	-	-	-	-	-
	30	10	-	-	-	-	-	-	-	-	-	-	-
	90	08	-	-	-	-	-	-	-	-	-	-	-
	150	09	-	-	-	-	-	-	-	-	-	-	-
pH	0	-	-	-	-	-	-	-	-	-	-	-	-
	30	4.2	-	-	-	-	-	-	-	-	-	-	-
	90	5.0	-	-	-	-	-	-	-	-	-	-	-
	150	-	-	-	-	-	-	-	-	-	-	-	-
Control Eh (mv)	0	-	-	-	-	-	-	-	-	-	-	-	491
	30	-	-	-	491	-	-	-	-064	-	-	-	-
	90	-	251	-	-	625	-	328	-	-	-	-	-
	150	-	-062	-	-	455	465	-	-	-	-	-	-
Soil Moisture (centibars)	0	-	-	-	-	-	-	-	-	-	-	-	-
	30	-	-	00	-	-	00	-	-	00	-	00	-
	90	-	-	-	48	-	-	-	00	-	-	14	-
	150	-	-	08	-	-	-	05	-	-	00	-	-

Table 1. (continued)

Date and Experimental Site	Component	Depth - cm -	Measurement Access Tube									
			0	1	2	3	4	5	6	7	8	9
Temperature °C	0	10	-	-	-	-	-	-	-	-	-	-
	30	09	-	-	-	-	-	-	-	-	-	-
	90	11	-	-	-	-	-	-	-	-	-	-
	150	13	-	-	-	-	-	-	-	-	-	-
pH	0	-	-	-	-	-	-	-	-	-	-	-
	30	6.0	-	-	-	-	-	-	-	-	-	-
	90	7.1	-	-	-	-	-	-	-	-	-	-
	150	7.2	-	-	-	-	-	-	-	-	-	-
Overburden	0	-	-	-	-	-	-	-	-	-	-	-
	30	-	571	-	-	-	-	064	-	-	-	348
	90	-	-	625	-	-	640	-	-	608	-	-
	150	-	-	-	682	-	-	-	603	-	565	-
Soil Moisture (centibars)	0	-	-	-	-	-	-	-	-	-	-	-
	30	-	-	-	13	-	-	-	07	-	07	-
	90	-	09	-	-	-	-	68	-	-	-	03
	150	-	-	32	-	-	19	-	-	15	-	-
Temperature °C	0	14	-	-	-	-	-	-	-	-	-	-
	30	11	-	-	-	-	-	-	-	-	-	-
	90	15	-	-	-	-	-	-	-	-	-	-
	150	17	-	-	-	-	-	-	-	-	-	-

Table 1. (continued)

Date and Experimental Site	Component	Depth - cm -	Measurement Access Tube									
			0	1	2	3	4	5	6	7	8	9
	pH	0	-	-	-	-	-	-	-	-	-	-
		30	4.2	-	-	-	-	-	-	-	-	-
		90	-	-	-	-	-	-	-	-	-	-
		150	-	-	-	-	-	-	-	-	-	-
05-23-91												
Reclamation	Eh (mv)	0	-	-	-	-	-	-	-	-	-	-
		30	353	408	-	-	-	-	-	313	-	-
		90	-	-	580	-	377	-	-	-	247	-
		150	-	-	-	-	552	-	520	-	509	-
	Soil Moisture (centibars)	0	-	-	-	-	-	-	-	-	-	-
		30	-	-	-	-	08	-	08	-	-	20
		90	-	-	-	-	-	-	-	06	-	-
		150	-	-	-	-	-	13	-	-	-	-
	Temperature °C	0	26	-	-	-	-	-	-	-	-	-
		30	24	-	-	-	-	-	-	-	-	-
		90	20	-	-	-	-	-	-	-	-	-
		150	20	-	-	-	-	-	-	-	-	-

Table 1. (continued)

Date and Experimental Site	Component	Depth - cm -	Measurement Access Tube									
			0	1	2	3	4	5	6	7	8	9
pH		0	-	-	-	-	-	-	-	-	-	-
		30	-	-	-	-	-	-	-	-	-	-
		90	-	-	-	-	-	-	-	-	-	-
		150	-	-	-	-	-	-	-	-	-	-
Control	Eh (mv)	0	-	-	-	-	-	-	-	-	-	-
		30	-	-	-	349	-	-	-	385	-	-
		90	-	170	-	-	296	-	125	-	-	-
		150	-	-002	-	-	130	408	-	-	-	-
	Soil Moisture (centibars)	0	-	-	-	-	-	-	-	-	-	-
		30	-	-	-	-	-	-	-	-	-	-
		90	-	-	-	-	-	-	-	-	-	-
		150	-	-	-	-	-	-	-	-	-	-
	Temperature °C	0	28	-	-	-	-	-	-	-	-	-
		30	23	-	-	-	-	-	-	-	-	-
		90	20	-	-	-	-	-	-	-	-	-
		150	19	-	-	-	-	-	-	-	-	-
	pH	0	-	-	-	-	-	-	-	-	-	-
		30	-	-	-	-	-	-	-	-	-	-
		90	-	-	-	-	-	-	-	-	-	-
		150	-	-	-	-	-	-	-	-	-	-

Table 1. (continued)

Date and Experimental Site	Component	Depth - cm -	Measurement Access Tube										
			0	1	2	3	4	5	6	7	8	9	
Overburden	Eh (mv)	0	-	-	-	-	-	-	-	-	-	-	-
		30	-	501	-	-	-	046	-	-	-	-	284
		90	-	-	492	-	557	-	-	557	-	-	-
		150	-	-	-	468	-	-	595	-	512	-	-
	Soil Moisture (centibars)	0	-	-	-	-	-	-	-	-	-	-	-
		30	-	-	-	-	-	-	-	-	-	-	-
		90	-	-	-	-	-	-	-	-	-	-	-
		150	-	-	14	-	10	-	-	-	-	-	-
	Temperature °C	0	28	-	-	-	-	-	-	-	-	-	-
		30	20	-	-	-	-	-	-	-	-	-	-
		90	23	-	-	-	-	-	-	-	-	-	-
		150	22	-	-	-	-	-	-	-	-	-	-
05-30-91													
Reclamation	Eh (mv)	0	-	-	-	-	-	-	-	-	-	-	-
		30	-	-199	-239	-	-	-	-	-198	-	-	-
		90	-	-	-	570	-	364	-	-	-	245	-
		150	-	-	-	-	542	-	520	-	437	-	-

Table 1. (continued)

Date and Experimental Site	Component	Depth - cm -	Measurement Access Tube									
			0	1	2	3	4	5	6	7	8	9
	Soil Moisture (centibars)	0	-	-	-	-	-	-	-	-	-	-
		30	-	06	-	-	-	08	-	-	-	14
		90	-	-	-	-	-	-	03	-	-	-
		150	-	15	-	-	05	-	-	-	-	-
	Temperature °C	0	29	-	-	-	-	-	-	-	-	-
		30	27	-	-	-	-	-	-	-	-	-
		90	25	-	-	-	-	-	-	-	-	-
		150	22	-	-	-	-	-	-	-	-	-
	pH	0	-	-	-	-	-	-	-	-	-	-
		30	-	-	-	-	-	-	-	-	-	-
		90	-	-	-	-	-	-	-	-	-	-
		150	-	-	-	-	-	-	-	-	-	-
Control	Eh (mv)	0	-	-	-	-	-	-	-	-	-	-
		30	-	-	297	-	-	-	-	-015	-	-044
		90	-	-025	-	-	-341	-	332	-	-	-
		150	-	-421	-	-	342	461	-	-	-	-
	Soil Moisture (centibars)	0	-	-	-	-	-	-	-	-	-	-
		30	-	-	12	-	-	02	-	-	07	-
		90	-	-	-	04	-	-	-	08	-	-
		150	-	-	08	-	-	-	22	-	14	-

Table 1. (continued)

Date and Experimental Site	Component	Depth - cm	Measurement Access Tube									
			0	1	2	3	4	5	6	7	8	9
Temperature °C	0	29	-	-	-	-	-	-	-	-	-	-
	30	26	-	-	-	-	-	-	-	-	-	-
	90	23	-	-	-	-	-	-	-	-	-	-
	150	21	-	-	-	-	-	-	-	-	-	-
pH	0	-	-	-	-	-	-	-	-	-	-	-
	30	-	-	-	-	-	-	-	-	-	-	-
	90	-	-	-	-	-	-	-	-	-	-	-
	150	-	-	-	-	-	-	-	-	-	-	-
Overburden	0	-	-	-	-	-	-	-	-	-	-	-
	30	-	410	-	-	-	-	046	-	-	-	118
	90	-	-	548	-	-	603	-	-	567	-	-
	150	-	-	-	444	-	-	-	608	-	507	-
Soil Moisture (centibars)	0	-	-	-	-	-	-	-	-	-	-	-
	30	-	-	-	16	-	-	-	02	-	09	-
	90	-	16	-	-	-	-	32	-	-	-	03
	150	-	-	17	-	-	10	-	-	16	-	-
Temperature °C	0	30	-	-	-	-	-	-	-	-	-	-
	30	29	-	-	-	-	-	-	-	-	-	-
	90	23	-	-	-	-	-	-	-	-	-	-
	150	22	-	-	-	-	-	-	-	-	-	-

Table 1. (continued)

Date and Experimental Site	Component	Depth - cm -	Measurement Access Tube									
			0	1	2	3	4	5	6	7	8	9
	pH	0	-	-	-	-	-	-	-	-	-	-
		30	-	-	-	-	-	-	-	-	-	-
		90	-	-	-	-	-	-	-	-	-	-
		150	-	-	-	-	-	-	-	-	-	-
6-12-91												
Reclamation	Eh (mv)	0	-	-	-	-	-	-	-	-	-	-
		30	-	-330	-078	-	-	-	-	-282	-	-
		90	-	-	-	552	-	339	-	-	-	310
		150	-	-	-	-	540	-	531	-	387	-
	Soil Moisture (centibars)	0	-	-	-	-	-	-	-	-	-	-
		30	-	-	-	-	04	-	00	-	-	04
		90	-	-	02	-	-	-	-	02	-	-
		150	-	15	-	-	-	04	-	-	-	-
	Temperature °C	0	32	-	-	-	-	-	-	-	-	-
		30	25	-	-	-	-	-	-	-	-	-
		90	24	-	-	-	-	-	-	-	-	-
		150	22	-	-	-	-	-	-	-	-	-

Table 1. (continued)

Date and Experimental Site	Component	Depth - cm -	Measurement Access Tube									
			0	1	2	3	4	5	6	7	8	9
pH		0	-	-	-	-	-	-	-	-	-	-
		30	3.9	-	-	-	-	-	-	-	-	-
		90	3.7	-	-	-	-	-	-	-	-	-
		150	-	-	-	-	-	-	-	-	-	-
Control Eh (mv)		0	-	-	-	-	-	-	-	-249	-	484
		30	-	-	-	-084	-	-	-	-	-	-
		90	-	-301	-	-	429	-	303	-	-	-
		150	-	-327	-	-	301	443	-	-	-	-
Soil Moisture (centibars)		0	-	-	-	-	-	-	-	-	-	-
		30	-	-	13	-	-	03	-	-	07	-
		90	-	-	-	00	-	-	-	08	-	02
		150	-	-	09	-	-	-	22	-	11	-
Temperature °C		0	34	-	-	-	-	-	-	-	-	-
		30	24	-	-	-	-	-	-	-	-	-
		90	22	-	-	-	-	-	-	-	-	-
		150	21	-	-	-	-	-	-	-	-	-
pH		0	-	-	-	-	-	-	-	-	-	-
		30	4.7	-	-	-	-	-	-	-	-	-
		90	4.5	-	-	-	-	-	-	-	-	-
		150	-	-	-	-	-	-	-	-	-	-

Table 1. (continued)

Date and Experimental Site	Component	Depth - cm -	Measurement Access Tube										
			0	1	2	3	4	5	6	7	8	9	
Overburden	Eh (mv)	0	-	-	-	-	-	-	-	-	-	-	-
		30	-	325	-	-	-	018	-	-	-	-	110
		90	-	-	537	-	606	-	-	576	-	-	-
		150	-	-	-	531	-	-	605	-	00	-	-
	Soil Moisture (centibars)	0	-	-	-	-	-	-	-	-	-	-	-
		30	-	-	-	10	-	-	00	-	11	-	-
		90	-	15	-	-	-	28	-	-	-	02	-
		150	-	-	18	-	10	-	-	17	-	-	-
	Temperature °C	0	35	-	-	-	-	-	-	-	-	-	-
		30	27	-	-	-	-	-	-	-	-	-	-
		90	24	-	-	-	-	-	-	-	-	-	-
		150	22	-	-	-	-	-	-	-	-	-	-
	pH	0	-	-	-	-	-	-	-	-	-	-	-
		30	3.8	-	-	-	-	-	-	-	-	-	-
		90	-	-	-	-	-	-	-	-	-	-	-
		150	-	-	-	-	-	-	-	-	-	-	-

Table 1. (continued)

Date and Experimental Site	Component	Depth - cm -	Measurement Access Tube																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																															
			0	1	2	3	4	5	6	7	8	9																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																						
07-03-91	Reclamation	Eh (mv)	0	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Table 1. (continued)

Data and Experimental Site	Component	Depth - cm -	Measurement Access Tube										
			0	1	2	3	4	5	6	7	8	9	
Control	Eh (mv)	0	-	-	-	-	-	-	-	-	-	-	-
		30	-	-	-	127	-	-	-	-112	-	-	273
		90	-	-373	-	-	361	-	275	-	-	-	-
		150	-	-462	-	-	325	511	-	-	-	-	-
	Soil Moisture (centibars)	0	-	-	-	-	-	-	-	-	-	-	-
		30	-	-	12	-	-	-	-	-	06	-	-
		90	-	-	-	02	-	04	-	08	-	-	-
		150	-	-	08	-	-	-	20	-	12	-	-
	Temperature °C	0	26	-	-	-	-	-	-	-	-	-	-
		30	26	-	-	-	-	-	-	-	-	-	-
		90	26	-	-	-	-	-	-	-	-	-	-
		150	24	-	-	-	-	-	-	-	-	-	-
Overburden	Eh (mv)	0	-	-	-	-	-	-	-	-	-	-	-
		30	-	354	-	-	-	034	-	-	-	-	088
		90	-	-	561	-	497	-	-	601	-	-	-
		150	-	-	-	501	-	-	577	-	032	-	-
	Soil Moisture (centibars)	0	-	-	-	-	-	-	-	-	-	-	-
		30	-	-	-	10	-	-	00	-	09	-	-
		90	-	12	-	-	-	24	-	-	-	-	00
		150	-	-	-	-	10	-	-	-	13	-	-

Table 1. (continued)

Date and Experimental Site	Component	Depth - cm -	Measurement Access Tube									
			0	1	2	3	4	5	6	7	8	9
Temperature °C	0	25	-	-	-	-	-	-	-	-	-	-
	30	25	-	-	-	-	-	-	-	-	-	-
	90	24	-	-	-	-	-	-	-	-	-	-
	150	24	-	-	-	-	-	-	-	-	-	-
07-09-91												
Reclamation	Eh (mv)	0	-	-	-	-	-	-	-	-	-	-
	30	-	295	-054	-	-	-	-	364	-	-	-
	90	-	-	-	503	-	294	-	-	-	149	-
	150	-	-	-	-	506	-	518	-	323	-	-
Soil Moisture (centibars)	0	-	-	-	-	-	-	-	-	-	-	-
	30	-	-	-	-	04	-	54	-	-	08	-
	90	-	-	-	-	-	-	-	34	-	-	-
	150	-	16	-	-	-	04	-	-	-	-	-
Temperature °C	0	30	-	-	-	-	-	-	-	-	-	-
	30	30	-	-	-	-	-	-	-	-	-	-
	90	27	-	-	-	-	-	-	-	-	-	-
	150	25	-	-	-	-	-	-	-	-	-	-

Table 1. (continued)

Date and Experimental Site	Component	Depth - cm -	Measurement Access Tube									
			0	1	2	3	4	5	6	7	8	9
Control	Eh (mv)	0	-	-	-	-	-	-	-	-	-	-
		30	-	-	-	450	-	-	-	420	-	512
		90	-	021	-	-	433	-	198	-	-	-
		150	-	280	-	-	286	307	-	-	-	-
	Soil Moisture (centibars)	0	-	-	-	-	-	-	-	-	-	-
		30	-	-	02	-	-	37	-	-	64	-
		90	-	-	-	14	-	-	-	12	-	08
		150	-	-	12	-	-	-	22	-	15	-
	Temperature °C	0	34	-	-	-	-	-	-	-	-	-
		30	29	-	-	-	-	-	-	-	-	-
		90	26	-	-	-	-	-	-	-	-	-
		150	23	-	-	-	-	-	-	-	-	-
Overburden	Eh (mv)	0	-	-	-	-	-	-	-	-	-	-
		30	-	373	-	-	-	005	-	-	-	236
		90	-	-	460	-	488	-	-	552	-	-
		150	-	-	-	545	-	-	577	-	386	-

Table 1. (continued)

Date and Experimental Site	Component	Depth - cm -	Measurement Access Tube									
			0	1	2	3	4	5	6	7	8	9
Soil Moisture (centibars)	0	-	-	-	-	-	-	-	-	-	-	-
	30	-	-	-	20	-	-	02	-	18	-	-
	90	-	19	-	-	10	-	-	-	-	02	-
	150	-	-	18	-	-	40	-	18	-	-	-
Temperature °C	0	34	-	-	-	-	-	-	-	-	-	-
	30	32	-	-	-	-	-	-	-	-	-	-
	90	29	-	-	-	-	-	-	-	-	-	-
	150	27	-	-	-	-	-	-	-	-	-	-

project. In this case periodic calibration and maintenance was affirmed.

a. Data Accuracy: The accuracy of the analytical operations was determined from the recovery of spiked selenium standard samples. The percent recovery of the analytical method accuracy was calculated from the following general equation:

$$\% \text{ accuracy} = 100 (X - X_0) / X_0$$

where, X is the selenium measured in the unspiked sample
 X_0 is the known value of the spiked sample

The percent recovery for each selenium species using the Ion Chromatograph was over 90 percent. The corresponding recovery for the Atomic absorption unit was over 95 percent.

2. Data Precision: The precision of the sample analysis was based upon the analysis of replicate samples and is expressed as the relative percent difference of the mean.

$$\% \text{ precision} = \frac{\text{Replicate 1} - \text{Replicate 2}}{\text{Average}} \times 100$$

Pages 211 and 213 are unavailable

END

**DATE
FILMED**

5 / 13 / 93