23
2-10-81
JWC

(2)

Dr. 228i

R1860

ORNL-5725

ornl

MASTER

OAK
RIDGE
NATIONAL
LABORATORY

**Engineering Physics Division
Progress Report
Period Ending November 30, 1980**

OPERATED BY
UNION CARBIDE CORPORATION
FOR THE UNITED STATES
DEPARTMENT OF ENERGY

REPRODUCTION OF THIS DOCUMENT IS UNLIMITED

ORNL-5725
Distribution Category UC-34c
Physics - Nuclear

Contract No. W-7405-eng-26

ENGINEERING PHYSICS DIVISION PROGRESS REPORT
FOR PERIOD ENDING NOVEMBER 30, 1980

F. C. Maienschein, Director

Date Published - December 1980

OAK RIDGE NATIONAL LABORATORY
Oak Ridge, Tennessee 37830
operated by
UNION CARBIDE CORPORATION
for the
DEPARTMENT OF ENERGY

Reports previously issued in this series are as follows:

ORNL-2081	Period Ending September 10, 1956
ORNL-2389	Period Ending September 1, 1957
ORNL-2609	Period Ending September 1, 1958
ORNL-2842	Period Ending September 1, 1959
ORNL-3016	Period Ending September 1, 1960
ORNL-3193	Period Ending September 1, 1961
ORNL-3360	Period Ending September 1, 1962
ORNL-3499, Vols. I and II	Period Ending August 1, 1963
ORNL-3714, Vols. I and II	Period Ending August 1, 1964
ORNL-3858, Vols. I and II	Period Ending August 1, 1965
ORNL-3973, Vols. I and II	Period Ending May 31, 1966
ORNL-4134	Period Ending May 31, 1967
ORNL-4280	Period Ending May 31, 1968
ORNL-4433	Period Ending May 31, 1969
ORNL-4592	Period Ending May 31, 1970
ORNL-4705	Period Ending May 31, 1971
ORNL-4800	Period Ending May 31, 1972
ORNL-4902	Period Ending May 31, 1973
ORNL-4997	Period Ending August 31, 1974
ORNL-5101	Period Ending October 31, 1975
ORNL-5280	Period Ending February 28, 1977
ORNL-5504	Period Ending November 30, 1978

CONTENTS

	<u>Page</u>
Introduction	xxiii
1. MEASUREMENTS OF NUCLEAR CROSS SECTIONS AND RELATED QUANTITIES	
1.0. Introduction	1-3
1.1. ORELA Measurements to Meet Fusion Energy Neutron Cross Section Needs D. C. Larson	1-5
1.2. Comparison of Neutron Total Cross Section Measurements with Optical Model Predictions from 2 to 90 MeV D. C. Larson, D. M. Hetrick, and J. A. Harvey	1-5
1.3. Neutron Total Cross Sections of Hydrogen, Carbon, Oxygen and Iron from 500 keV to 60 MeV D. C. Larson, J. A. Harvey, and N. W. Hill	1-5
1.4. Measurement of the ${}^7\text{Li}(n,n'\gamma){}^7\text{Li}^*(0.478\text{-MeV})$ Cross Section from 0.5 to 5.0 MeV D. K. Olsen, G. L. Morgan, and J. W. McConnell	1-6
1.5. Measurement of ${}^{238}\text{U}(n,n'\gamma)$ and ${}^7\text{Li}(n,n'\gamma)$ Gamma-Ray Production Cross Sections D. K. Olsen, G. L. Morgan, and J. W. McConnell	1-6
1.6. Measurement of ${}^{238}\text{U}(n,n'\gamma){}^{238}\text{U}^*$ Cross Sections D. K. Olsen, G. L. Morgan, and J. W. McConnell	1-7
1.7. ${}^{238}\text{U}$ Neutron Inelastic Scattering at 82 keV R. R. Winters, G. L. Morgan, R. L. Macklin, D. K. Olsen, J. A. Harvey, and N. W. Hill	1-7
1.8. ${}^{238}\text{U}$ Inelastic Neutron Scattering at 82 keV R. R. Winters, N. W. Hill, R. L. Macklin, J. A. Harvey, D. K. Olsen, and G. L. Morgan	1-7
1.9. The ${}^{238}\text{U}$ Neutron-Induced Fission Cross Section for Incident Neutron Energies Between 5 eV and 3.5 MeV F. C. Difilippo, R. B. Perez, G. de Saussure, D. K. Olsen, and R. W. Ingle	1-8
1.10. High-Resolution Fission Cross Section of ${}^{231}\text{Pa}$ S. Plattard, G. F. Auchampaugh, N. W. Hill, G. de Saussure, R. B. Perez, and J. A. Harvey	1-8
1.11. High-Resolution Measurement of the ${}^{231}\text{Pa}(n,f)$ Cross Section from 0.4 eV to 12 MeV S. Plattard, G. F. Auchampaugh, G. De Saussure, N. W. Hill, J. A. Harvey, and R. B. Perez	1-9
1.12. The Triple-Humped Fission Barrier of ${}^{232}\text{Pa}$ S. Plattard, G. F. Auchampaugh, N. W. Hill, G. de Saussure, R. B. Perez, and J. A. Harvey	1-11
1.13. Propriétés Spectroscopiques de Quelques Structures Fines Observées dans le Seuil de la Réaction ${}^{231}\text{Pa}(n,f)$ S. Plattard, G. F. Auchampaugh, N. W. Hill, G. de Saussure, R. B. Perez and J. A. Harvey	1-11

1.14.	Some Spectroscopic Properties of Fine Structures Observed Near the $^{231}\text{Pa}(n,f)$ Fission Threshold	1-12
	S. Plattard, G. F. Auchampaugh, N. W. Hill, G. de Saussure, J. A. Harvey, and R. B. Perez	
1.15.	Measurement of the Average Number of Prompt Neutrons Emitted per Fission of ^{235}U Relative to ^{252}Cf for the Energy Region 500 eV to 10 MeV	1-12
	R. Gwin, R. R. Spencer, R. W. Ingle, J. H. Todd, and H. Weaver	
1.16.	Interim Report on the ORNL Absolute Measurements of $\bar{\nu}_p$ for ^{252}Cf	1-13
	R. R. Spencer, R. Gwin, R. Ingle, and H. Weaver	
1.17.	Absolute Measurement of $\bar{\nu}_p$ for ^{252}Cf by the Large Liquid Scintillator Tank Technique	1-13
	F. R. Spencer	
1.18.	Precise Measurement and Analysis of Neutron Transmission Through ^{232}Th ..	1-13
	D. K. Olsen, R. W. Ingle, and J. L. Portney	
1.19.	The $\text{Th}(n,xy)$ Reaction Cross Section for Neutrons of Energy Between 0.3 and 20 MeV	1-14
	G. L. Morgan	
1.20.	Cross Sections for the $\text{Cu}(n,xn)$ and $\text{Cu}(n,xy)$ Reactions Between 1 and 20 MeV	1-14
	G. L. Morgan	
1.21.	Cross Sections for the $\text{Ti}(n,xn)$ and $\text{Ti}(n,xy)$ Reactions Between 1 and 20 MeV	1-14
	G. L. Morgan	
1.22.	The $\text{O}(n,xy)$ Reaction Cross Section for Incident Neutron Energies Between 6.5 and 20.0 MeV	1-15
	G. L. Morgan and G. T. Chapman	
1.23.	Measurement and Analysis of the $^{23}\text{Na}(n,xy)$ Reaction Cross Section for $0.2 \leq E_n \leq 20$ MeV	1-15
	D. C. Larson and G. L. Morgan	
1.24.	Status Report(s) to the DOE Nuclear Data Committee	1-16
	F. G. Perey and J. C. (Gentry) Lundy	
1.25.	Electron Antineutrino Spectrum for $^{235}\text{U}(n_{th},f)$	1-16
	J. K. Dickens	
1.26.	Fission Product Decay Heat for Thermal Reactors	1-16
	J. K. Dickens	
1.27.	Fission-Product Energy Release for Times Following Thermal-Neutron Fission of ^{235}U Between 2 and 14000 s	1-17
	J. K. Dickens, T. A. Love, J. W. McConnell, and R. W. Peelle	
1.28.	Fission Product Yields for Thermal-Neutron Fission of Plutonium-239	1-17
	J. K. Dickens and J. W. McConnell	
1.29.	Delayed Beta- and Gamma-Ray Production Due to Thermal-Neutron Fission of ^{239}Pu : Tabular and Graphical Spectral Distributions for Times After Fission Between 2 and 14000 s	1-18
	J. K. Dickens, T. R. England, T. A. Love, J. W. McConnell, J. F. Emery, K. J. Northcutt, and R. W. Peelle	

1.30.	Fission-Product Energy Release for Times Following Thermal-Neutron Fission of Plutonium-239 and Plutonium-241 Between 2 and 14000 Seconds	1-18
	J. K. Dickens, T. A. Love, J. W. McConnell, and R. W. Peelle	
1.31.	Yields of Short-Lived Fission Products Produced by Thermal-Neutron Fission of Plutonium-239	1-19
	J. K. Dickens, J. W. McConnell, and K. J. Northcutt	
1.32.	Fissions Determination in ^{239}Pu Sample	1-19
	J. K. Dickens and J. W. McConnell	
1.33.	Gamma Rays Following Alpha Decay of ^{245}Cm and the Level Structure of ^{241}Pu	1-20
	J. K. Dickens and J. W. McConnell	
1.34.	Yields of Fission Products Produced by Thermal-Neutron Fission of ^{245}Cm	1-20
	J. K. Dickens and J. W. McConnell	
1.35.	Half Life of ^{132}Te	1-20
	J. K. Dickens	
1.36.	Absolute Yield of 140.5 keV Gamma Ray Following Decay of ^{99}Mo	1-21
	J. K. Dickens and T. A. Love	
1.37.	Method for Sampling from Fission Neutron Energy Spectra	1-21
	F. H. Froehner and R. R. Spencer	
1.38.	Preliminary Study of Pseudorandom Binary Sequence Pulsing of ORELA	1-21
	N. M. Larson and D. K. Olsen	
1.39.	Procedures Manual for the Oak Ridge Electron Linear Accelerator	1-22
	H. A. Todd	

2. NUCLEAR CROSS-SECTION EVALUATIONS AND THEORY

2.0.	Introduction	2-3
2.1.	A Consistent Nuclear Model for Compound and Precompound Reactions with Conservation of Angular Momentum	2-4
	C. Y. Fu	
2.2.	Development and Applications of Multi-Step Hauser-Feshbach/Pre-Equilibrium Model Theory	2-4
	C. Y. Fu	
2.3.	Neutron Emission Spectra Induced by 14-MeV Neutrons from the Evaluated Nuclear Data File (ENDF/B-V) - A Critical Review	2-4
	D. M. Hetrick, D. C. Larson, and C. Y. Fu	
2.4.	Evaluation of Photon Production Data from Neutron-Induced Reactions	2-5
	C. Y. Fu	
2.5.	Evaluation of Neutron Cross Sections for Fissile and Fertile Nuclides in the keV Range	2-5
	L. W. Weston	
2.6.	Evaluation of Neutron and Gamma-Ray-Production Cross Sections for Natural Iron (ENDF/B-V MAT 1326)	2-6
	C. Y. Fu and F. G. Perey	

2.7.	Evaluation of Resonance Parameters for Neutron Interaction with Iron Isotopes for Energies up to 400 keV	2-6
	C. M. Perey and F. G. Perey	
2.8.	Simultaneous Evaluation of $^{32}\text{S}(n,p)$, $^{56}\text{Fe}(n,p)$, $^{65}\text{Cu}(n,2n)$ Cross Sections	2-6
	C. Y. Fu, D. M. Hetrick, and F. G. Perey	
2.9.	Evaluation of ^{23}Na for ENDF/B-V	2-6
	D. C. Larson	
2.10.	An Evaluation of Cross Sections for Neutron-Induced Reactions in Sodium	2-7
	D. C. Larson	
2.11.	Calculation of the $^{23}\text{Na}(n,2n)$ Cross Section	2-7
	D. C. Larson	
2.12.	Evaluation of the Fission and Capture Cross Sections of ^{240}Pu and ^{241}Pu for ENDF/B-V	2-7
	L. W. Weston and R. Q. Wright	
2.13.	Review of Microscopic Neutron Cross Section Data for the Higher Plutonium Isotopes in the Resonance Region	2-8
	L. W. Weston	
2.14.	GLUCS: A Generalized Least-Squares Program for Updating Cross Section Evaluations with Correlated Data Sets	2-8
	D. M. Hetrick and C. Y. Fu	
2.15.	User's Guide for SAMMY: A Computer Model for Multilevel R-Matrix Fits to Neutron Data Using Bayes' Equations	2-9
	N. M. Larson and F. G. Perey	
2.16.	Logical Inference and Evaluation	2-9
	F. G. Perey	

3. NUCLEAR CROSS-SECTION PROCESSING, TESTING, AND SENSITIVITY ANALYSIS

3.0.	Introduction	3-3
------	--------------------	-----

Cross-Section Processing and Testing

3.1.	VITAMIN-C: The CTR Processed Multigroup Cross-Section Library for Neutronics Studies	3-5
	R. W. Roussin, C. R. Weisbin, J. E. White, N. M. Greene, R. Q. Wright, and J. B. Wright	
3.2.	VITAMIN-E: An ENDF/B-V Multigroup Cross-Section Library for LMFBR Core and Shield, LWR Shield, Dosimetry and Fusion Blanket Technology	3-5
	C. R. Weisbin, R. W. Roussin, J. J. Wagschal, J. E. White, and R. Q. Wright	
3.3.	VITAMIN-E: A Multipurpose ENDF/B-V Coupled Neutron-Gamma Cross Section Library	3-6
	J. Barhen, D. G. Cacuci, W. E. Ford, III, R. W. Roussin, J. J. Wagschal, C. R. Weisbin, J. E. White, and R. Q. Wright	

3.4.	A New Cross Section Library for Light Water Reactor Shielding and Pressure Vessel Dosimetry Applications	3-6
	G. L. Simmons and R. W. Roussin	
3.5.	A Comparison of the Use of EURLIB-III and Other Multigroup Cross-Section Libraries for a 1 Meter Concrete Slab Problem	3-7
	M. Metghalchi, R. W. Roussin, J. T. West, and B. Nakhai	
3.6.	Sample Problems for the Novice User of the AMPX-II System	3-11
	W. E. Ford, III, R. W. Roussin, L. M. Petrie, B. P. Diggs, and H. E. Comolander	
3.7.	Nuclear Data and Benchmarks for Reactor Shielding (Meeting Papers)	3-11
	R. W. Roussin, D. K. Trubey, B. F. Maskewitz, J. D. Drischler, and J. H. Marable	
3.8.	Determination of Current-Weighted Total Cross Sections in the Unresolved Energy Region	3-12
	J. Barhen and D. G. Cacuci	
3.9.	Computation of Analytical Bounds for Cross-Section Self-Shielding Factors	3-15
	J. Barhen and D. G. Cacuci	
3.10.	Processing ENDF/B-V Uncertainty Data into Multigroup Covariance Matrices	3-18
	J. D. Smith, H. L. Dodds, F. G. Perey, and C. R. Weisbin	
3.11.	Implementation of ENDF/B-IV and V Data in LWR Design Codes: EPRI-CELL and EPRI-CPM	3-21
	O. Ozer, R. E. MacFarlane, and M. L. Williams	
3.12.	Comparison of Several Multigroup Libraries for LWR Shielding Problems	3-23
	R. W. Roussin, M. Metghalchi, J. West, and B. Nakhai	
3.13.	Relative Consistency of ENDF/B-IV and -V with Fast-Reactor Benchmarks	3-26
	Y. Yeivin, J. J. Wagschal, J. H. Marable, and C. R. Weisbin	
3.14.	Data Testing of ENDF/B-IV and -V	3-26
	J. J. Wagschal and Y. Yeivin	
3.15.	An Overview of CSEWG Shielding Benchmark Problems	3-27
	R. E. Maerker	
3.16.	Benchmark Shielding Problems Obtained from Integral Tests of Neutron Cross Sections	3-29
	B. W. Wehring, J. J. Dornig, N. E. Hertel, D. T. Ingersoll, and R. H. Johnson	

Development of Sensitivity Analysis Methods

3.17.	A Review of the Theory and Application of Sensitivity and Uncertainty Analysis: Proceedings of a Seminar-Workshop, Oak Ridge, Tennessee, August 22-24, 1978	3-31
	C. R. Weisbin, R. W. Roussin, H. R. Hendrickson, and E. W. Bryant	
3.18.	Sensitivity and Uncertainty Analysis of Reactor Performance Parameters	3-31
	C. R. Weisbin, R. W. Peelle, J. H. Marable, P. J. Collins, E. Kujawski, E. Greenspan, and G. de Saussure	

3.19.	A Review of the Capabilities of the ORNL FORSS Sensitivity and Uncertainty Analysis System	3-32
	R. W. Roussin, C. R. Weisbin, and J. L. Lucius	
3.20.	A Users Manual for the FORSS Sensitivity and Uncertainty Analysis Code System	3-33
	J. L. Lucius, C. R. Weisbin, J. H. Marable, J. D. Drischler, R. Q. Wright, and J. E. White	
3.21.	The COVERX Service Module of the FORSS System	3-33
	J. D. Drischler	
3.22.	A User's Guide for the JULIET Module of the FORSS Sensitivity and Uncertainty Analysis Code System	3-33
	J. L. Lucius, E. M. Oblow, and G. W. Cunningham, III	
3.23.	Time-Dependent Generalized Perturbation Theory for Coupled Neutron-Nuclide Problems	3-34
	E. Greenspan, M. L. Williams, and J. H. Marable	
3.24.	Constrained Sensitivity Theory	3-34
	E. Greenspan and M. L. Williams	
3.25.	Developments in Sensitivity Theory	3-37
	D. G. Cacuci, E. Greenspan, J. H. Marable, and M. L. Williams	
3.26.	Recent Advances and Applications of Differential Sensitivity Theory in Reactor Safety	3-38
	D. G. Cacuci, P. J. Maudlin, C. V. Parks, and C. F. Weber	
3.27.	Sensitivity Theory for General Systems of Nonlinear Equations	3-38
	D. G. Cacuci, C. F. Weber, E. M. Oblow, and J. H. Marable	
3.28.	Differential Sensitivity Theory for Nonlinear Equations with Nonlinear Responses	3-39
	C. F. Weber, D. G. Cacuci, and E. M. Oblow	
3.29.	Application of Sensitivity Theory for Extrema of Functionals to a Transient Reactor Thermal-Hydraulics Problem	3-42
	D. G. Cacuci and C. F. Weber	
3.30.	A Systematic Methodology for the Reduction of Uncertainties in Transient Thermal-Hydraulics by Using In-Bundle Measurement Data	3-45
	J. Barhen, D. G. Cacuci, J. J. Wagschal, and C. B. Mullins	
3.31.	Generalized Sensitivity Theory Applied to the Space and Time Dependent Thermal-Hydraulics Conservation Equations	3-45
	P. J. Maudlin, C. V. Parks, and C. F. Weber	
3.32.	Applications of Differential Sensitivity Theory for Problems with Discontinuities	3-47
	C. F. Weber, D. G. Cacuci, and C. V. Parks	
3.33.	An Efficient Procedure to Evaluate Second-Order Sensitivities for Nonlinear Problems with Nonlinear Responses	3-50
	J. Barhen and D. G. Cacuci	

Cross-Section Adjustment and Analysis of Integral Experiments

3.34.	ORACLE: An Adjusted Cross-Section and Covariance Library for Fast-Reactor Analysis	3-53
	Y. Yeivin, J. H. Marable, C. R. Weisbin, and J. J. Wagschal	
3.35.	The Adjustment of Cross Sections Based on Integral Experiments in Fast Benchmark Assemblies	3-54
	J. H. Marable	
3.36.	Cross Section Adjustment Applied to Estimation of Uncertainty in the Breeding Ratio of an LMFBR	3-54
	J. H. Marable, C. R. Weisbin, and G. de Saussure	
3.37.	Specifications for Adjusted Cross Section and Covariance Libraries Based Upon CSEWG Fast Reactor and Dosimetry Benchmarks	3-54
	C. R. Weisbin, J. H. Marable, P. J. Collins, C. L. Cowan, R. W. Peelle, and M. Salvatores	
3.38.	Determination and Application of Generalized Bias Operators Using an Inverse Perturbation Approach	3-55
	Y. Ronen, D. G. Cacuci, and J. J. Wagschal	
3.39.	Cross-Section Adjustment: Sensitivity to Uncertainties	3-55
	J. J. Wagschal, R. E. Maerker, and B. L. Broadhead	
3.40.	The Significance of LaGrange Multipliers in Cross-Section Adjustment	3-58
	J. J. Wagschal and Y. Yeivin	
3.41.	Response-Parameter Correlations in Uncertainty Analysis	3-61
	J. Barhen, J. J. Wagschal, and Y. Yeivin	
3.42.	S_n Transport Calculations of the PCA Experiments with Some Estimated Uncertainties	3-64
	R. E. Maerker	
3.43.	Uncertainties and Biases Arising from Methods Approximations: the Calculation of Reaction Rates in the PCA 8/7 Configuration	3-66
	R. E. Maerker and J. J. Wagschal	
3.44.	Sensitivity and Uncertainty Analysis for the Mixed-Oxide Thermal Lattice U-L212	3-65
	R. L. Childs, G. de Saussure, J. L. Lucius, J. D. Drischler, V. C. Baker, J. H. Marable, and R. M. Westfall	
3.45.	Detailed Error Analysis of Average Fission Cross-Section Measurements in NBS Standard Neutron Fields	3-67
	J. J. Wagschal, R. E. Maerker, and D. M. Gilliam	
3.46.	Covariances of Fission-Integral Measurements at the NBS ^{252}Cf and ISNF Facilities and at the ORNL-PCA Facility	3-69
	J. J. Wagschal, R. E. Maerker, and D. M. Gilliam	
3.47.	The NBS Intermediate-Energy Standard Neutron Field (ISNF) Revisited	3-70
	B. L. Broadhead and J. J. Wagschal	
3.48.	The ISNF: A New CSEWG Dosimetry Benchmark (Computational Problems and Their Solution)	3-72
	B. L. Broadhead and J. J. Wagschal	

3.49.	Estimation of the Uncertainties in the ENDF/B-V ²³⁵ U Fission Spectrum	3-74
	R. E. Maerker, J. H. Marable, and J. J. Wagschal	
3.50.	Influence of Fission Spectra Uncertainties on Calculated Fast Reactor Parameters	3-76
	J. L. Lucius and J. H. Marable	
3.51.	Sensitivity and a priori Uncertainty Analysis of the CFRMF Central Flux Spectrum	3-78
	J. M. Ryskamp, R. A. Anderl, B. L. Broadhead, W. E. Ford, II', J. L. Lucius, J. H. Marable, and J. J. Wagschal	

Application of Sensitivity and Uncertainty Analysis to Reactor Physics and Safety

3.52.	Uncertainty in the Breeding Ratio of a Large Liquid-Metal Fast Breeder Reactor: Theory and Results	3-81
	J. H. Marable, C. R. Weisbin, and G. de Saussure	
3.53.	Generalized Sensitivity Theory Applied to the MELT-IIIA Fast Reactor Safety Code	3-82
	P. J. Maudlin and C. V. Parks	
3.54.	Perturbation and Sensitivity Theory for Reactor Burnup Analysis	3-85
	M. L. Williams	
3.55.	A Technique for Sensitivity Analysis of Space- and Energy-Dependent Burnup Calculations	3-85
	M. L. Williams, J. R. White, and T. J. Burns	
3.56.	Evaluation of Integral Parameter Correlations and Reactor Performance Using Nuclear Data Covariances	3-89
	C. D. Rinaldis, J. M. Kallfelz, E. Kujawski, and J. H. Marable	
3.57.	Design and Sensitivity Analysis of a CDS-Type Heterogeneous Core	3-92
	J. M. Kallfelz, D. Biswas, C. L. Cowan, J. H. Marable, M. L. Williams, C. R. Weisbin, J. D. Drischler, T. B. Fowler, and J. R. White	
3.58.	Implementation of Generalized Perturbation Theory into the 3-D Nodal Code SIMULATE	3-92
	S. M. Bowman, M. L. Williams, and H. L. Dodds	
3.59.	Least Squares Methodology Applied to LWR-PV Damage Dosimetry, Experience and Expectations	3-95
	J. J. Wagschal, B. L. Broadhead, and R. E. Maerker	
3.60.	Extrapolation of Surveillance Dosimetry Information to Predict Pressure Vessel Fluences	3-95
	J. J. Wagschal, R. E. Maerker, and Y. Yeivin	
3.61.	The Void Coefficient in a Unit Cell for U-Pu Water Breeder Reactors	3-97
	Y. Ronen, M. Cojocaru, and A. Radkowski	
3.62.	A Nonlinear Sensitivity and Uncertainty Analysis in Support of the Blowdown Heat Transfer Program	3-99
	Y. Ronen, M. A. Bjerke, D. G. Cacuci, and J. Barhen	

3.63.	Quarterly Progress Report on Blowdown Heat Transfer Separate-Effects Program for October-December 1979	3-100
	W. G. Cradick, R. E. Bohanan, D. G. Cacuci, J. H. Cook, D. K. Felds, R. M. Flanders, R. C. Hagar, C. R. Hyman, G. S. Mailen, L. J. Ott, and M. D. White	
3.64.	Sensitivity Theory Applied to a Transient Thermal-Hydraulics Problem	3-100
	C. F. Weber	
3.65.	Generalized Perturbation Theory Using Two-Dimensional, Discrete Ordinates Transport Theory	3-101
	R. L. Childs	
3.66.	DOS Perturbation Modules DGRAD/VIP/TPERT	3-101
	E. T. Tomlinson, R. L. Childs, and R. A. Lillie	

4. ENGINEERING PHYSICS DIVISION INTEGRAL EXPERIMENTS AND THEIR ANALYSES

4.0.	Introduction	4-3
	<u>Integral Experiments Supporting Fusion Reactor Design</u>	
4.1.	Calculation of Neutron and Gamma Ray Energy Spectra for Fusion Reactor Shield Design: Comparison with Experiment	4-4
	R. T. Santoro, R. G. Alsmiller, Jr., J. M. Barnes, and G. T. Chapman	
4.2.	Integral Experiments for Fusion Reactor Design: Analysis	4-4
	R. T. Santoro, R. G. Alsmiller, Jr., J. M. Barnes, and E. M. Oblow	
4.3.	Integral Experiments for Fusion Reactor Design: Experimentation	4-5
	G. T. Chapman and G. L. Morgan	
4.4.	Analysis of ORNL Fusion Reactor Shield Integral Experiments	4-5
	R. T. Santoro, R. G. Alsmiller, Jr., J. M. Barnes, G. T. Chapman, G. L. Morgan, E. M. Oblow, and P. W. Peele	
4.5.	Fusion Reactor Shielding Benchmark	4-7
	G. T. Chapman, G. L. Morgan, J. W. McConnell, R. T. Santoro, R. G. Alsmiller, Jr., and J. M. Barnes	
4.6.	ORNL Fusion Reactor Shielding Integral Experiments	4-7
	R. T. Santoro, R. G. Alsmiller, Jr., J. M. Barnes, and G. T. Chapman	
4.7.	Comparison of Calculated and Experimental Neutron Attenuation and Streaming Data for Fusion Reactor Design	4-8
	R. T. Santoro, R. G. Alsmiller, Jr., J. M. Barnes, and G. T. Chapman	
4.8.	The Use of a Small Accelerator as a Source of 14-Mev Neutrons for Shielding Studies	4-8
	G. T. Chapman, G. L. Morgan, and J. W. McConnell	
	<u>Integral Experiments Supporting Gas Cooled Fast Breeder Reactor Design</u>	
4.9.	Analysis of the TSF GCFR Single-Cell Neutron Streaming Experiment	4-9
	C. O. Slater and J. R. Knight	

4.10.	Analysis of the ORNL/TSF GCFR Grid-Plate Shield Design Confirmation Experiment	4-10
	C. O. Slater, S. N. Cramer, and D. T. Ingersoll	
4.11.	Measurement and Calculation of the Effectiveness of the GCFR Grid Plate Shield	4-12
	C. O. Slater, S. N. Cramer, D. T. Ingersoll, and M. L. Williams	
4.12.	GCFR Radial Blanket and Shield Experiment: Objectives, Preanalysis, and Specifications	4-12
	D. T. Ingersoll, D. E. Bartine, and F. J. Muckenthaler	
4.13.	GCFR Radial Blanket and Shield Experiment	4-13
	F. J. Muckenthaler, J. L. Hull, and J. J. Manning	
4.14.	Analysis of the ORNL-TSF Radial Blanket and Shield Integral Experiments	4-13
	D. T. Ingersoll and L. R. Williams	
4.15.	Recent Shielding Experiments at the ORNL Tower Shielding Facility	4-16
	D. E. Bartine, D. T. Ingersoll, and C. O. Slater	
4.16.	Design of Deep-Penetration Integral Experiment for Thorium Blanket and Radial Shield Mockups	4-18
	D. T. Ingersoll, D. E. Bartine, and F. J. Muckenthaler	
4.17.	Deep Penetration Integral Experiment for a Thorium Blanket Mockup	4-20
	D. T. Ingersoll and F. J. Muckenthaler	

Integral Experiments Supporting Liquid Metal Fast Breeder Reactor Design

4.18.	Study of Neutron Transmission Through Planar and Cylindrical Annular Slits in Iron Shields	4-20
	C. E. Clifford, F. J. Muckenthaler, F. R. Mynatt, and L. S. Abbott	
4.19.	Analysis of a TSF Experiment on Secondary Gamma-Ray Production in Reinforced Concrete Shields	4-21
	R. L. Childs, F. J. Muckenthaler, and L. S. Abbott	

5. DEVELOPMENT OF METHODS FOR SHIELD AND REACTOR ANALYSES

5.0.	Introduction	5-3
5.1.	A Modified Approach to Diffusion Acceleration in Neutron Transport Problems	5-4
	J. E. Aull, W. A. Rhoades, and H. L. Dodds	
5.2.	The Stability of the Mesh-Cornered Synthetic Method of Diffusion Acceleration of the DOT-IV Transport Code	5-6
	J. E. Aull	
5.3.	Acceleration of the Inner Iteration of the DOT-IV Transport Code Using a New Source Correction Scheme	5-6
	J. E. Aull	

5.4.	Effectiveness of Three Rebalance Methods in Deep Penetration Problems	5-7
	W. A. Rhoades and E. T. Tomlinson	
5.5.	Evaluation of Flux Extrapolation Models for Discrete Ordinates Shielding Analysis	5-7
	E. T. Tomlinson and W. A. Rhoades	
5.6.	Flux Extrapolation Models Used in the DOT IV Discrete Ordinates Neutron Transport Code	5-9
	E. T. Tomlinson, W. A. Rhoades, and W. W. Engle, Jr.	
5.7.	DOGS - A Collection of Graphics for Support of Discrete Ordinates Codes	5-9
	D. T. Ingersoll and C. O. Slater	
5.8.	A Review of the Theory and Application of Monte Carlo Methods: Proceedings of a Seminar-Workshop, Oak Ridge, Tennessee, April 21-23, 1980	5-10
	D. K. Trubey and B. L. McGill	
5.9.	Experience with TRIPOLI at ORNL	5-10
	S. N. Cramer and R. W. Roussin	
5.10.	MORSE: Current Status of the Two Oak Ridge Versions	5-10
	M. B. Emmett and J. T. West, III	
5.11.	A Repair for Scattering Expansion Truncation Errors in Transport Calculations	5-11
	M. B. Emmett, R. L. Childs, and W. A. Rhoades	
5.12.	BRESE-II: Auxiliary Routines for Implementing the ALBEDO Option in the MORSE Monte Carlo Code	5-13
	V. R. Cain and M. B. Emmett	
5.13.	The Iterative Behavior of Diffusion Theory Flux Eigenvalue Neutronics Problems	5-13
	D. R. Vondy and T. B. Fowler	
5.14.	Input Data Requirements for Special Processors in the Computation System Containing the VENTURE Neutronics Code	5-13
	D. R. Vondy, T. B. Fowler, and G. W. Cunningham	
5.15.	Exposure Calculation Code Module for Reactor Core Analysis: BURNER	5-14
	D. R. Vondy and G. W. Cunningham	
5.16.	PREMOR: A Point Reactor Exposure Model Computer Code for Survey Analysis of Power Plant Performance	5-14
	D. R. Vondy	
5.17.	Development and Verification of Multicycle Depletion Perturbation Theory	5-15
	J. R. White and T. J. Burns	
5.18.	The Development, Implementation, and Verification of Multicycle Depletion Perturbation Theory for Reactor Burnup Analysis	5-17
	J. R. White	
5.19.	Thermal Reactor Benchmark Calculations Using Resonance Profiles	5-18
	J. Barhen and W. Rothenstein	
5.20.	OZMA - A Code to Calculate Resonance Reaction Rates in Reactor Lattices Using Resonance Profile Tabulations	5-18
	J. Barhen and W. Rothenstein	

5.21. SPQR: A Monte Carlo Reactor Kinetics Code	5-19
S. N. Cramer and H. L. Dodds	
5.22. Thermal-Hydraulic/Heat Transfer Code Development for Sphere-Pac-Fueled LMFBRs	5-19
David G. Morris	
5.23. Evaluation and Modification of the Probability Table Method for Bubble Reactivity Worth Calculations	5-20
T. J. Hoffman and E. U. Vaughan	
5.24. User's Guide for the Revised SPEC-4 Neutron Spectrum Unfolding Code	5-20
J. O. Johnson and D. T. Ingersoll	
5.25. On Validating Major Computer Codes	5-20
R. Vondy	
5.26. The Current Status of Methods for Shielding Analysis	5-22
W. W. Engle Jr.	
5.27. Computer Techniques in Shielding and Dosimetry (Lectures)	5-23
T. A. Gabriel and W. W. Engle, Jr.	
5.28. Neutronic Calculational Methods (Meeting Presentations)	5-23
D. R. Vondy and W. A. Rhoades	

6. ANALYSES FOR SPECIFIC SYSTEMS OR APPLICATIONS

6.0. Introduction	6-3
<u>Liquid Metal Fast Breeder Reactor Program</u>	
6.1. Neutronic Analysis of LMFBRs During Severe Core Disruptive Accidents ...	6-6
E. T. Tomlinson	
6.2. Analysis of the Clinch River Breeder Reactor (CRBR) Source Range Flux Monitor (SRFM) Count Rate History During Refueling of the First Four Cycles	6-6
D. L. Selby and H. E. Knee	
6.3. Uncertainties Associated with Monitoring the Shutdown Operations in the Clinch River Breeder Reactor Heterogeneous Core Using the Source Range Flux Monitor	6-7
D. L. Selby and H. E. Knee	
6.4. A Review of Methods for Treatment of Source Effects in the Modified Source Multiplication Method for Monitoring the Reactivity in Refueling the CRBR	6-7
J. T. Mihalcz	
6.5. ORNL Breeder Reactor Safety - LOA 2, 3, 4, and 5 Quarterly Technical Progress Report for April-June 1979	6-8
M. H. Fontana	
6.6. Preconceptual Study of Proliferation-Resistant Heterogeneous Sphere-Pac-Fueled LMFBR Cores	6-8
D. L. Selby	
6.7. The Analysis of the ZPR-9 Reverse Approach to Critical (RAC) Low Level Flux Monitor Experiment	6-9
D. L. Selby, G. F. Flanagan, P. B. Fox, and D. B. Simpson	

6.8.	Theoretical Evaluation of Ex-Vessel Monitoring for Initial Fuel Loading of a Liquid-Metal Fast Breeder Reactor	6-9
	J. T. Mihaľcz, D. L. Selby, and H. E. Knee	
6.9.	FY 1977 Progress Report of the Clinch River Breeder Reactor Source Range Flux Monitor Assessment Study for the Reference Homogeneous Core	6-11
	M. B. Emmett, W. W. Engle, Jr., G. F. Flanagan, H. E. Knee, D. L. Loyd, D. L. Selby, and L. R. Williams (D. L. Selby, Ed.)	
6.10.	FY 1978 Progress Report of the Clinch River Breeder Reactor Source Range Flux Monitor Assessment Study for the Reference Heterogeneous Core	6-12
	W. W. Engle, Jr., H. E. Knee, D. L. Loyd, J. T. Mihaľcz, and D. L. Selby (D. L. Selby, Ed.)	
6.11.	Evaluation of Single-Rod Withdrawal Techniques for use in Constructing Inverse Count Rate Curves During Initial Loading of the First Core in the Clinch River Breeder Reactor (CRBR)	6-12
	W. T. Swain and D. L. Selby	
6.12.	Investigation of Alternate Schemes for Reloading the Clinch River Breeder Reactor Core at the End of Cycle Two (EC2)	6-13
	D. L. Loyd, D. L. Selby, and W. M. Simpkins	
6.13.	Radiation Analysis of the Conceptual Design Study 1000-Mw(e) Loop-Design LMFBR	6-13
	W. A. Rhoades, M. B. Emmett, J. R. Knight, and W. W. Engle, Jr.	

Gas-Cooled Fast Breeder Reactor Program

6.14.	Gas-Cooled Fast Reactor Program Annual Progress Report for Period Ending December 31, 1979	6-13
	U. Gat and P. R. Kasten	
6.15.	Analysis of the Initial Shielding Design for the Upflow Gas-Cooled Fast Reactor (GCFR)	6-14
	C. O. Slater, E. T. Tomlinson, and L. R. Williams	
6.16.	Analysis of the Conceptual Shielding Design for the Upflow Gas-Cooled Fast Breeder Reactor	6-15
	C. O. Slater, D. A. Reed, S. N. Cramer, M. B. Emmett, and E. T. Tomlinson	
6.17.	Analysis of the New GCFR Upper and Lower Plenum Flow-Through Shield:	6-15
	S. N. Cramer, D. A. Reed, M. B. Emmett, and C. A. Rouse	
6.18.	Preliminary Neutronic Analysis of a Fast Mixed-Spectrum Reactor (FMSR)	6-16
	T. J. Burns and J. R. White	
6.19.	Analysis of Fission Product Effects in a Fast Mixed-Spectrum Reactor Concept	6-16
	J. R. White and T. J. Burns	
6.20.	Critical Experiments in a Zero Power Fast Reactor Lattice with Breeder Zones of Thorium and Uranium	6-17
	U. Schmocker, R. Chawla, K. Gmur, M. Jermann, C. McCombie, R. Richmond, S. Seth, D. E. Bartine, D. T. Ingersoll, and J. R. White	

6.21.	Analysis of a Swiss Thorium Blanket Integral Experiment	6-18
	J. R. White, D. T. Ingersoll, U. Schmocker, and K. Gmur	
6.22.	Analysis of the Thorium Axial Blanket Experiments in the PROTEUS Reactor	6-18
	J. R. White and D. T. Ingersoll	
6.23.	Neutron Spectrum Evaluation in the Thorium Axial Blankets of the PROTEUS Reactor	6-19
	M. Jermann and D. T. Ingersoll	
6.24.	Alternative Heterogeneous GCFR Fuel Cycles	6-19
	J. R. White and T. J. Burns	
6.25.	Preliminary Evaluation of Alternate-Fueled Gas Cooled Fast Reactors	6-22
	J. R. White and T. J. Burns	
6.26.	US/FRG Joint Report on the Pebble Bed High Temperature Reactor Resource Conservation Potential and Associated Fuel Cycle Costs	6-22
	E. Teuchert, H. J. Rutten, B. A. Worley, and D. R. Vondy	
6.27.	Comparative Evaluation of Pebble-Bed and Prismatic Fueled High-Temperature Gas-Cooled Reactors	6-22
	P. R. Kasten, D. E. Bartine, T. J. Burns, B. A. Worley, and L. S. Abbott	

Light-Water Reactor Programs

6.28.	Calculation of the TMI-2 Source-Range Monitor Reading for Several Core Water Levels	6-23
	R. L. Childs, D. L. Selby, J. C. Robinson, R. G. Canada, and R. L. Monday	
6.29.	Calculations of the Skyshine Gamma-Ray Dose Rates from Independent Spent Fuel Storage Installations (ISFSI) Under Worst Case Accident Conditions	6-26
	J. V. Pace, III, S. N. Cramer, and J. R. Knight	
6.30.	Theoretical Characterization of a Dual Purpose Gamma Thermometer	6-26
	T. J. Burns and J. O. Johnson	
6.31.	A Statistical Sensitivity Analysis of a Simple Nuclear Waste Repository Model	6-26
	Y. Ronen, J. L. Lucius, and E. M. Oblow	

Alternate Fuel Cycles

6.32.	Interim Assessment of the Denatured ²³³ U Fuel Cycle: Feasibility and Nonproliferation Characteristics	6-27
	L. S. Abbott, D. E. Bartine, T. J. Burns, C. Sege, and I. Spiwak	
6.33.	The Use of Thorium in Fast Breeder Reactors	6-28
	D. E. Bartine	

Magnetic Fusion Energy Program

6.34. Shielding of Fusion Reactors	6-28
R. G. Alsmiller, Jr.	
6.35. Shielding Calculations for the TFTR Neutral-Beam Injectors	6-28
R. T. Santoro, R. A. Lillie, R. G. Alsmiller, Jr., and J. M. Barnes	
6.36. Dose Rates from Induced Activity in the TFTR Test Cell	6-31
R. G. Alsmiller, Jr., J. Barish, R. T. Santoro, R. A. Lillie, J. M. Barnes, and M. M. H. Ragheb	
6.37. Estimated Nuclear Effects in the Neutron Beam Injectors of a Large Fusion Reactor.....	6-34
R. A. Lillie, R. T. Santoro, and R. G. Alsmiller, Jr.	
6.38. One-Dimensional Gamma-Ray Shielding Calculations for the EBT-P	6-35
R. A. Lillie, T. A. Gabriel, B. L. Bishop, and V. C. Baker	
6.39. Calculated Irradiation Response of Materials Using Fission Reactor (HFIR, ORR, and EBR-II) Neutron Spectra	6-37
T. A. Gabriel, B. L. Bishop, and F. W. Wiffen	
6.40. Design of Materials Irradiation Experiments Utilizing Spectral Tailoring	6-37
T. A. Gabriel, R. A. Lillie, and B. L. Bishop	
6.41. Monte Carlo Simulation of Neutron Particle Transport in a Neutral-Beam Injector	6-40
R. A. Lillie, R. G. Alsmiller, Jr., T. A. Gabriel, R. T. Santoro, and S. W. Schwensterly	
6.42. Neutronics - Tritium Breeding	6-42
R. T. Santoro	
6.43. An Optimization of the Fission-Fusion Hybrid Concept	6-42
M. J. Saltmarsh, W. R. Grimes, and R. T. Santoro	

High-Energy Physics Program

6.44. Skyshine at Neutron Energies ≤ 400 MeV	6-42
R. G. Alsmiller, Jr., J. Barish, and R. L. Childs	
6.45. MAGIK - A Monte Carlo System for Computing Induced Residual Activation Dose Rates	6-43
J. Barish, T. A. Gabriel, and R. G. Alsmiller, Jr.	
6.46. Photon Dose Rate in the Vicinity of a High-Energy Proton Beam Scraper	6-44
R. G. Alsmiller, Jr., and J. Barish	
6.47. The Response of a Uranium-Plastic Calorimeter to Low GeV (≤ 10 GeV) Protons	6-44
T. A. Gabriel and B. L. Bishop	
6.48. Calculated Response of a Total Liquid Argon Calorimeter to Protons and Electrons in the 0.5-5.0 GeV Energy Range	6-44
T. A. Gabriel and B. L. Bishop	

6.49.	Liquid Argon as an Electron/Photon Detector in the Energy Range of 50 MeV to 2 GeV: A Monte Carlo Investigation	6-45
	M. S. Goodman, G. Denis, M. Hall, A. Karpovsky, R. Wilson, T. A. Gabriel, and B. L. Bishop	
6.50.	Calculated Particle Production Spectra and Multiplicities from Nucleon-Fissile Element Collisions at Medium Energies	6-45
	F. S. Alsmiller, R. G. Alsmiller, Jr., T. A. Gabriel, R. A. Lillie, and J. Barish	
6.51.	A Phenomenological Model for Particle Production from the Collision of Nucleons at Medium Energies with Fissile Elements	6-45
	F. S. Alsmiller, R. G. Alsmiller, Jr., T. A. Gabriel, R. A. Lillie, and J. Barish	
6.52.	Thermal-Neutron Flux Generation by High-Energy Protons in Thick Uranium Targets	6-48
	R. G. Alsmiller, Jr., T. A. Gabriel, J. Barish, and F. S. Alsmiller	

Miscellaneous Studies

6.53.	Molten-Salt Reactors for Efficient Nuclear Fuel Utilization Without Plutonium Separation	6-50
	J. R. Engel, W. A. Rhoades, W. R. Grimes, and J. F. Dearing	
6.54.	Conceptual Design Characteristics of a Denatured Molten-Salt Reactor with Once-Through Fueling	6-50
	J. R. Engel, H. F. Bauman, J. F. Dearing, W. R. Grimes, H. E. McCoy, and W. A. Rhoades	
6.55.	Concept Evaluation of a Nuclear Design for Electronuclear Fuel Production: Evaluation of ORNL's Proposed TMF-ENFP	6-51
	T. J. Burns, D. E. Bartine, and J. P. Renier	
6.56.	Nondestructive Assay of Subassembly of Various Spent or Fresh Fuels by Active Neutron Interrogation	6-52
	G. L. Ragan, C. W. Ricker, M. V. Chiles, D. T. Ingersoll, and G. G. Slaughter	
6.57.	System for Nondestructive Assay of Spent Fuel Subassemblies - Comparison of Calculations and Measurements	6-52
	G. L. Ragan, C. W. Ricker, M. M. Chiles, D. T. Ingersoll, G. G. Slaughter, and L. R. Williams	
6.58.	Calculation of Neutron Die-Away Times in a Large-Vehicle Portal Monitor	6-53
	R. A. Lillie, R. T. Santoro, and R. G. Alsmiller, Jr.	
6.59.	Resonance Integral Calculations for Isolated Rods Containing Oxides of ^{238}U and ^{232}Th	6-53
	V. C. Baker and J. H. Marable	
6.60.	One-Dimensional Model of Fluidized Bed Combustor Dynamics	6-54
	R. B. Perez	
6.61.	The Status of Reactor Shielding Research in the U.S.	6-54
	F. C. Maienschein	

7. ENERGY MODEL VALIDATION

7.0.	Introduction	7-3
7.1.	A Sensitivity Approach to the Validation of Long-Range Energy-Economic Forecasts	7-4
	E. M. Oblow, C. R. Weisbin, and R. G. Alsmiller, Jr.	
7.2.	The Quantification of Uncertainties in the Parameters of a Long-Term Energy Model	7-5
	R. W. Peele, D. J. Downing, and D. J. Bjornstad	
7.3.	Interim Report on Model Evaluation Methodology and the Evaluation of LEAP	7-5
	F. G. Alsmiller, Jr., J. Barish, D. Bjornstad, D. J. Downing, K. E. Ford, J. Horwedel, C. J. Lee, J. McAdoo, E. M. Oblow, R. W. Peele, F. G. Perey, L. Stewart, and C. R. Weisbin	
7.4.	Highlights of the ORNL Model Evaluation Methodology and the Evaluation of LEAP	7-6
	C. R. Weisbin and R. G. Alsmiller, Jr.	
7.5.	Specification of the Equations for LEAP Model 22C	7-6
	M. Goldstein, R. G. Alsmiller, Jr., and J. Barish	

8. SYSTEMS RELIABILITY AND OPERATIONS RESEARCH

8.0.	Introduction	8-3
8.1.	Criteria for Safety-Related Nuclear Plant Operator Actions: A Preliminary Assessment of Available Data (I)	8-4
	P. M. Haas and T. F. Bott	
8.2.	Criteria for Safety-Related Nuclear Plant Operator Actions: A Preliminary Assessment of Available Data (II)	8-4
	P. M. Haas and T. F. Bott	
8.3.	A Systems Approach to Defining Operator Roles	8-5
	R. A. Kisner and G. F. Flanagan	
8.4.	Approaches to Acceptable Risk: A Critical Guide	8-5
	B. Fischhoff, S. Lichtenstein, P. Slovic, R. Koenzy, and S. Derby	
8.5.	Nuclear Power Plant Simulators: Their Use in Operator Training and Requalification	8-6
	D. W. Jones, D. K. Baer, C. C. Francis, J. M. Winders, P. M. Haas, L. S. Abbott, and R. L. Dietz	
8.6.	Sodium Component Reliability Data Collection at CREDO	8-7
	T. F. Bott, P. M. Haas, and J. J. Manning	
8.7.	Development of the Centralized Reliability Data Organization (CREDO) ...	8-10
	T. F. Bott, G. W. Cunningham, N. M. Greene, P. M. Haas, S. D. Hudson, H. E. Knee, and J. J. Manning	
8.8.	SACRD: A Data Base for Fast Reactor Safety Computer Codes -- General Description	8-10
	N. M. Greene, V. M. Forsberg, G. B. Raiford, J. W. Arwood, D. B. Simpson, and G. F. Flanagan	

8.9.	SACRD: A Data Base for Fast Reactor Safety Computer Codes -- Contents and Glossary of Version 1 of the System	8-10
	N. M. Greene, V. M. Forsberg, G. B. Raiford, J. W. Arwood, J. B. Simpson, and G. F. Flanagan	
8.10.	Technical Note: SACRD - A Data Base for Fast Reactor Computer Codes	8-11
	N. M. Greene, G. F. Flanagan, and H. Alter	
8.11.	SACRD - A Data Base for Fast Reactor Safety Computer Codes -- Operational Procedures	8-12
	V. M. Forsberg, J. W. Arwood, N. M. Greene, and G. B. Raiford	
8.12.	A Methodology and a Preliminary Data Base for Examining the Health Risks of Electricity Generation from Uranium and Coal Fuels	8-12
	A. A. El-Bassioni	

9. INFORMATION ANALYSIS AND DISTRIBUTION

9.0.	Introduction	9-3
9.1.	Information Analysis Centers	9-5
	B. Talmi Carroll and B. F. Maskewitz	
9.2.	Survey of USA Major Data Base Management Systems	9-5
	B. F. Maskewitz and C. E. Price	
9.3.	The USA NRC/RSR Data Bank System and Reactor Safety Research Data Repository (RSRCR)	9-7
	B. F. Maskewitz and S. F. Bankert	
9.4.	The Technical Data Management Center: A Focal Point for Meteorological and Other Environmental Transport Computing Technology	9-10
	B. L. McGill, B. F. Maskewitz, and D. K. Trubey	
9.5.	Radiation Streaming in Power Reactors	9-11
	G. P. Lahti, R. R. Lee, and J. C. Courtney, Editors	
9.6.	Data Bases for Rapid Response to Power Reactor Problems	9-11
	B. F. Maskewitz	
9.7.	Radiation Shielding Information Center: A Source of Computer Codes and Data for Fusion Neutronics Studies	9-12
	B. L. McGill, R. W. Roussin, D. K. Trubey, and B. F. Maskewitz	
9.8.	The Validation of Computing Technology Through Sharing	9-12
	B. F. Maskewitz	
9.9.	User's Manual for LADTAP II - A Computer Program for Calculating Radiation Exposure to Man from Routine Release of Nuclear Reactor Liquid Effluents	9-13
	D. B. Simpson and B. L. McGill	
9.10.	Directory of Computer Users in Nuclear Medicine	9-13
	J. J. Erickson, J. Gurney, and W. J. McClain	
9.11.	Bibliography, Subject Index, and Author Index of the Literature Examined by the Radiation Shielding Information Center	9-14
	D. K. Trubey, R. W. Roussin, J. Gurney, A. B. Gustin, and E. W. Bryant	
9.12.	On the Polynomial Form of Gamma-Ray Buildup Factor Functions	9-14
	M. Metghalchi	

APPENDIX

	<u>Page</u>
Scientific and Professional Activities	A-3
Engineering Physics Division Seminars at ORNL	A-11
Publications and Papers Presented at Scientific Meetings	A-15
Papers Presented at Scientific Meetings	A-25
Author Index	A-35
Organization Chart	A-41

INTRODUCTION

This progress report for the ORNL Engineering Physics Division covers a two-year period, with the publication schedule determined by the Division's information meetings. We have examined the alternate option of publishing annual reports independent of the information meeting schedule, but have judged that the cost/benefit ratio is more favorable for continuation of the present arrangement.

This report primarily includes abstracts and summaries of reports and papers that have been published and thus describes only work that has been completed and brought to the publication stage. As a result, there is relatively little here to reflect research in several new areas, although two new sections (7 and 8) that are expected to expand in the future have been introduced. Section 7 includes abstracts of a few reports in the new area of energy-model validation. An important aspect of this program is the use of the sensitivity-analysis techniques developed for reactor-physics and shielding analysis in an attempt to better understand the sensitivities of energy models to variations in input data and model parameters. The necessary economics input into this program is provided by economists from the ORNL Energy Division. Section 8 indicates the scope of the rapidly growing work in LWR systems reliability and operations safety, together with the continuing data-base activities for LMFBR safety and reliability. Most of the LWR-related work is sponsored by the Nuclear Regulatory Commission and to date has largely but not entirely been carried out by subcontractors.

Figure 1 shows the substantial changes in programmatic emphasis in the Division since 1974. As noted, a rapid growth of work for "Other Fission Reactors" has been experienced, with much of this category consisting of NRC research that is nonneutronic in character and thus away from our historical strengths. Interest in these areas has been an outgrowth of safety and reliability studies for LMFBRs. In general, research of this type is not so well defined and disciplined as is reactor physics, but it is clearly very relevant and potentially useful in the short term. The "Other" category in the figure is now dominated by energy-model validation. Overall, about one-third of the division's funding is for work in nonneutronic categories.

With funding from several sources, the program of measuring, evaluating, processing, and adjusting nuclear data (described in Sections 1, 2, and 3) appears to maintain continuity, as it must to achieve progress. The pervasive role of sensitivity and uncertainty analysis in validating data and methods, in designing integral experiments, and in design support tends to make the placement of particular activities in this report quite arbitrary. This forward integration, which requires and stresses communication among measurers, evaluators, and analysts and with their colleagues in other laboratories and at reactor vendors, surely represents one of our greatest strengths and contributions. We will strive to increase even more the collaboration with system designers in all of the areas in which we work.

Fig. 1. Trends in Engineering Physics Division Funding.

Over the eight-year period covered by Fig. 1, research for the Defense Nuclear Agency and for fast-breeder reactor programs has gradually and consistently diminished in amount. While the research for the Defense Nuclear Agency is expected to remain roughly constant, the downward trend could be reversed for breeder reactors if projects are again pursued vigorously to establish nuclear energy as a major long-term source of electricity. The economics of breeder reactors are substantially impacted by the radiation shields and their effects upon seismic loads. The Division's Tower Shielding Facility, now in part-time operation, remains the only experimental facility for fission-reactor shield studies in the U.S. As is indicated in Section 4, the Division's integral-experiment program for fission reactors has been joined by a well-established series of integral experiments for shielding studies of fusion reactors, the latter performed with a dedicated 14-MeV neutron source which is located at ORELA (Oak Ridge Electron Linear Accelerator).

The methods development work and design-support analysis work described in Sections 5 and 6 can be expected to change in the future. Methods development has decreased in magnitude, so that it appears to be necessary to focus ever more sharply upon a very few tools which must solve the vast majority of future radiation transport problems. The area of design-support

analysis will be impacted by the current termination of the Gas-Cooled Fast Reactor Program and reduced emphasis upon studies of alternate fuel cycles.

As might be deduced from a survey of this report, a large fraction of the Division's program (nearly 50%) is carried out by subcontractors and by individuals from other ORNL divisions. In essentially all cases the work is performed under the direct of the Division and supported by Division programs. Thus to properly reflect the organization of the Division, the organization chart on page A-41 includes all persons who spend at least one-half of their time on EPD work. Many staff members from the Computer Sciences Division and the Instrumentation and Controls Division have been working full time on Engineering Physics Programs for years or even for decades.

1. MEASUREMENTS OF NUCLEAR CROSS SECTIONS AND RELATED QUANTITIES

1.0 INTRODUCTION

The ORELA continues to be a major world source of nuclear data for fusion reactor development as well as for fission reactor design. The work represented by the abstracts below and motivated by fusion system requirements includes not only neutron and gamma-ray emission spectra similar to those measured in the past but also some cross sections for neutron energies up to several ten's of MeV. The latter have become of interest because the FMIT (Fusion Materials Irradiation Test) facility being constructed at Hanford has a neutron spectrum extending to these energies, so that corresponding cross-section information is required. Some feasibility studies are also underway to determine whether ORELA can be used to study (n,p) and (n, α) reactions important to materials irradiation effects.

A series of papers has covered our work on subthreshold neutron fission, the area in which our results have been of most interest to nuclear physicists. For this work, narrow resolution and highly purified samples have been crucial to obtaining definitive data. Except for studies on ^{238}U , most of the work in this area has been on a cooperative basis with members of the ORNL Physics Division and scientists from other laboratories. Though the main hurried push is largely dissipated to establish suddenly credible nuclear data files for ^{233}U and ^{232}Th for analysis of alternative reactor systems that would produce less Pu, the time lag in obtaining samples and undertaking experiments leaves us midway through our own efforts. Important results are now available for the low resonance region in thorium, thorium gamma-ray production cross sections, and the energy dependence of the number of prompt neutrons/fission for ^{233}U , while work in the other reactions of interest is underway. Our past experience suggests that interest in these cross sections will recur, and that we must complete the sensible sets of measurements that have been initiated.

The program to obtain definitive measurements of the ^{252}Cf (spontaneous fission) standard for the number of neutrons emitted per fission and the energy dependence of $\bar{\nu}$ for the major isotopes is progressing well; the experimental work for the standard is complete and that for the energy dependence is far well along. This extensive effort should go far toward removing the number of neutrons per fission as a significant source of uncertainty in reactor calculations; it has already led to improved consistency among the various parameters important to thermal reactor analysis.

Other than in this work on $\bar{\nu}$, cross sections of particular interest to thermal reactors have not received much attention in recent years at ORELA or elsewhere because of the common understanding that data are well in hand and because of the dominance of reactor manufacturer's organizations in determining what cross sections were to be used in practical calculations. With increased interest among the utilities in performing their own analyses using public data and the improved ability of analysis tools to make use of valid cross sections, interest has increased in obtaining correct and precise data for the thermal (<1 eV) cross sections for the major nuclides. We are getting underway with plans for new measurements so that ORELA's power can be fully applied to this application area.

The significant results of the ORNL fission-product decay heat program have now all been sent for publication, but spin-off from this program continues. The decay heat (beta and gamma ray) measurements themselves covered the short time region of most importance to coolant loss accidents and for which inadequate information was available when the program was started. Results have been documented for ^{235}U and $^{239,41}\text{Pu}$. An off-shoot of these measurements has been a series of papers on fission yield distributions for several fissile nuclides, including some for which only submicrogram samples were available. Another interesting off-shoot of the decay heat work has been an estimate of the gross neutrino spectrum following ^{235}U fission, an estimate important for consideration of inverse beta-decay processes.

For the ORELA itself, development efforts continue on the electron injection system in hopes of compressing the charge that can be accelerated into as narrow a pulse as possible. The effort to obtain this result using klystron prebunching has not yet become operational because of extensive vacuum problems in the ferrite-loaded acceleration

and deceleration "gaps" constructed for this purpose. Tests performed with a fraction of the structures in operation have indicated that a significant share of the expected pulse compression can be achieved, but to date the full system has not been demonstrated even on a trial basis. A new set of "gap" structures is being machined using an improved fabrication method that should not be subject to the same corrosion-induced failures in thin kovar sections.

1.1. ORELA MEASUREMENTS TO MEET FUSION ENERGY NEUTRON CROSS SECTION NEEDS*

D. C. Larson

(Abstract of paper presented at Symposium on Neutron Cross Sections from 10-50 MeV, Brookhaven National Laboratory, Upton, N. Y., May 12-14, 1980; BNL-NCS-51245, Vol. 1, 1980, p. 277)

Major neutron cross section measurements made at the Oak Ridge Electron Linear Accelerator (ORELA) that are useful to the fusion energy program are reviewed. Cross sections for production of gamma rays with energies $0.3 < E_\gamma < 10.5$ MeV have been measured as a function of neutron energy over the range $0.1 < E_n < 20.0$ MeV for Li, C, N, O, F, Na, Mg, Al, Si, Ca, Ti, V, Cr, Mn, Fe, Ni, Cu, Zn, Nb, Mo, Ag, Sn, Ta, W, Au, Pb and Th. Neutron emission cross sections have been measured for ^7Li , Al, Ti, Cu and Nb for $1 < E_n < 20$ MeV. Some results of recent neutron total cross section measurements from 2-80 MeV for eleven materials (C, O, Al, Si, Ca, Cr, Fe, Ni, Cu, Au and Pb) of interest to the FMIT project will be presented. Finally, future directions of the ORELA program will be outlined.

* Research sponsored by DOE Office of Basic Energy Sciences.

1.2. COMPARISON OF NEUTRON TOTAL CROSS SECTION MEASUREMENTS WITH OPTICAL MODEL PREDICTIONS FROM 2 TO 80 MeV

D. C. Larson D. M. Hetrick[†] J. A. Harvey[‡]

(Abstract of Bull. Am. Phys. Soc. 25, 543, 1980)

We have recently measured transmission of neutrons through samples of polyethylene, C, O, Al, Si, Ca, Cr, Fe, Ni, Cu, Au and Pb for use in shielding design studies for the Fusion Material Irradiation Test (FMIT) facility. The energy range covered was from 2 ~ 80 MeV. The measurements were made at the Oak Ridge Electron Linear Accelerator (ORELA) using the Be block target and the 80-m flight path. Results from these measurements will be compared with predicted total cross sections obtained from standard optical model parameter sets. In particular, results will be shown for the Becchetti-Greenlees and Wilmore-Hodgson parameter sets, as well as selected "best-fit" sets of some of the materials. Comparison of the predicted total cross section with measured values will provide guidance as to the choice of the best set as a function of mass and energy range for use in shielding calculations.

* Research sponsored by the DOE Office of Basic Energy Sciences.

[†]UCC-ND Computer Sciences Division.

[‡]Physics Division.

1.3. NEUTRON TOTAL CROSS SECTIONS OF HYDROGEN, CARBON, OXYGEN AND IRON FROM 500 keV TO 60 MeV

D. C. Larson J. A. Harvey[†] N. W. Hill[‡]

(Abstract of paper in Nuclear Cross Sections for Technology, NBS Special Publication 594, p. 34, 1980)

The neutron total cross sections for hydrogen, carbon, oxygen, and iron have been measured from 0.5 to 60 MeV using the Oak Ridge Electron Linear Accelerator (ORELA) as the source of neutrons. The flight path was 80 m, and the repetition rate was 1000 sec⁻¹.

with a burst width of 10 ns. The resulting cross sections are graphically compared with ENDF/B-V evaluations up to 20 MeV, and with selected data from 20-60 MeV.

* Research sponsored by DOE Office of Basic Energy Sciences.

† Physics Division.

‡ Instrumentation and Controls Division.

1.4. MEASUREMENT OF THE ${}^7\text{Li}(n,n'\gamma){}^7\text{Li}^*(0.478\text{-MeV})$ CROSS SECTION FROM 0.5 TO 5.0 MeV*

D. K. Olsen G. L. Morgan† J. W. McConnell

(Abstract of Nucl. Sci. Eng. 74, 219-222, 1980)

Employing a 95-cm³ Ge(Li) detector, positioned 20 m from the Oak Ridge Electron Linear Accelerator white neutron source, the cross section for 478-keV gamma-ray production from 0.48- to 5.0-MeV incident neutrons on ${}^7\text{Li}$ was determined. The incident neutron flux was measured with a solid-state, recoil-proton detector and polyethylene radiator.

These results, which are an unambiguous measurement of neutron inelastic scattering to the 478-keV ${}^7\text{Li}$ state, are listed and compared with recent measurements from other workers and the ENDF/B-V evaluation.

* Research sponsored by DOE Office of Reactor Research and Technology.

† Now at Los Alamos Scientific Laboratory.

1.5. MEASUREMENT OF ${}^{238}\text{U}(n,n'\gamma)$ AND ${}^7\text{Li}(n,n'\gamma)$ GAMMA-RAY PRODUCTION CROSS SECTIONS*

D. K. Olsen G. L. Morgan† J. W. McConnell

(Abstract of ORNL/TM-8832, September, 1979)

Time-of-flight techniques and a 95-cm³ Ge(Li) detector positioned 20 m from the ORELA white neutron source have been utilized to measure 125° cross sections for the production of gamma rays in ${}^{238}\text{U}$ and ${}^7\text{Li}$ samples by 0.48- to 5.0-MeV neutrons. The incident neutron flux was determined with a proton-recoil telescope which used a solid-state, recoil-proton detector. Altogether, 28 cross sections for ${}^{238}\text{U}$ transitions from levels with 680 to 1224 keV of excitation were measured. In addition, 7 branching ratios for weak ${}^{238}\text{U}$ transitions and the ${}^7\text{Li}(n,n'\gamma){}^7\text{Li}^*(478\text{ keV})$ cross section were measured. From these data and other level-decay information, preliminary neutron inelastic scattering cross sections were constructed and compared with those at 680, 732, 827, 965, 1048, and 1170-keV of excitation from the proposed ENDF/B-V evaluation.

* Research sponsored by DOE Office of Reactor Research and Technology.

† Now at Los Alamos Scientific Laboratory.

1.6. MEASUREMENT OF $^{238}\text{U}(n,n'\gamma)^{238}\text{U}^*$ CROSS SECTIONS*D. K. Olsen G. L. Morgan[†] J. W. McConnell*(Abstract of paper in Nuclear Cross Sections for Technology, NBS Special Publication 594, p. 677, 1980)*

Production cross sections for gamma-ray transitions produced by 0.5 to 5.0-MeV neutrons on ^{238}U have been measured employing a 95-cm³ Ge(Li) detector at 125°, the ORELA neutron source, and a recoil proton telescope. From these data and other decay scheme information, inelastic scattering cross sections for levels from 680 to 1224 keV of excitation have been constructed and compared with statistical model calculations and the ENDF/B-V evaluation.

*Research sponsored by DOE Office of Reactor Research and Technology.

[†]Now at Los Alamos Scientific Laboratory.1.7. ^{238}U NEUTRON INELASTIC SCATTERING AT 82 keV*R. R. Winters[†] G. L. Morgan[‡] R. L. Macklin[§]
D. K. Olsen J. A. Harvey N. W. Hill[¶]*(Abstract of Bull. Am. Phys. Soc. 25, 543, 1980)*

Knowledge of inelastic neutron scattering on ^{238}U is important for fast reactor design, particularly the threshold cross section to the first-excited 2^+ level at 45 keV. Consequently, we have measured as a function of angle the ratio of the 2^+ inelastic yield to the elastic yield using 82-keV "window" neutrons produced from the ORELA flux filtered through ~30 cm of iron. Au and ^{238}U samples were employed at a ~9 m flight path. Scattered neutrons were detected 0.406 m from the samples with a NE-110 scintillator viewed by three photomultipliers in coincidence. The yield ratios were determined with the aid of the elastic line shape from the Au sample and have been corrected for the combined effects of elastic anisotropy and multiple scattering. With this ratio and the accurately known total cross section, the inelastic cross section at 82 keV was determined.

*Research sponsored by DOE Office of Basic Energy Sciences.

[†]Denison University, Granville, Ohio.[‡]Now at Los Alamos Scientific Laboratory.[§]Physics Division.[¶]Instrumentation and Controls Division.1.8. ^{238}U INELASTIC NEUTRON SCATTERING AT 82 keV*R. R. Winters[†] N. W. Hill[‡] R. L. Macklin[§]
J. A. Harvey[§] D. K. Olsen G. L. Morgan[¶]*(Abstract of paper to be published in Nucl. Sci. Eng.)*

Using a thick iron filter to produce an 82 keV group of nearly monoenergetic pulsed neutrons from the Oak Ridge Electron Linear Accelerator white neutron source, the differential and integrated neutron inelastic scattering cross sections from the first excited state of ^{238}U have been measured. We find that the angular distribution is

forward-peaked and we obtain estimates of the Legendre coefficients P_0 , P_1 , and P_2 . The measured integrated inelastic cross section is 381 ± 21 mb, in good agreement with the ENDF/B-V evaluation and with other statistical and optical model calculations.

*Research sponsored by DOE Office of Basic Energy Sciences.

†Denison University, Granville, Ohio.

‡Instrumentation and Controls Division.

§Physics Division.

¶Now at Los Alamos Scientific Laboratory.

1.9. THE ^{238}U NEUTRON-INDUCED FISSION CROSS SECTION FOR INCIDENT NEUTRON ENERGIES BETWEEN 5 eV AND 3.5 MeV*

F. C. Difilippo[†] R. B. Perez G. de Saussure D. K. Olsen R. W. Ingle[‡]
[Abstract of Phys. Rev. C 21(4), 1400, 1980, and of ORNL/TM-6780, March, 1979]

A measurement of the ^{238}U neutron-induced fission cross section has been performed in the neutron energy range between 5 eV and 3.5 MeV. The favorable signal-to-background ratio and high resolution of this experiment resulted in the identification of 85 sub-threshold fission resonances or clusters of resonances in the neutron energy region between 5 eV and 200 keV. The fission data below 100 keV are characteristic of a weak coupling situation between Class I and Class II levels. The structure of the fission levels at the 720 and 1210 eV fission clusters is discussed. There is an apparent enhancement of the fission cross section at the opening of the 2^+ neutron inelastic channel in ^{238}U at 45 keV. An enhancement of the subthreshold fission cross section between 100 and 200 keV has been tentatively interpreted in terms of the presence of a Class II, partially damped vibrational level. There is a marked structure in the fission cross section above 200 keV up to and including the plateau between 2 and 3.5 MeV.

*Research sponsored by DOE Office of Reactor Research and Technology.

†IAEA Fellow now with Comision Nacional de Energia Atomica, Argentina.

‡Instrumentation and Controls Division.

1.10. HIGH-RESOLUTION FISSION CROSS SECTION OF ^{231}Pa *

S. Plattard[†] G. F. Auchampaugh[‡] N. W. Hill[§]
G. de Saussure R. B. Perez J. A. Harvey[¶]

(Abstract of paper in Nuclear Cross Sections for Technology, NBS Special Publication 604, p. 491, 1980)

The ^{231}Pa fission cross section was measured with high resolution at ORELA from 0.1 to 12 MeV and between 0.4 eV and 10 keV. The data show evidence for (1) fractionated vibrational structures in the threshold region of the fission cross section, and (2) narrow fission resonances above 0.4 eV with an average fission width $\langle\Gamma_f\rangle = 8$ μeV .

*Research partially supported by DOE.

†Centre d'Etudes de Bruyeres-le-Chatel, France.

‡Los Alamos Scientific Laboratory.

§Instrumentation and Controls Division.

¶Physics Division.

1.11. HIGH-RESOLUTION MEASUREMENT OF THE $^{231}\text{Pa}(n,f)$ CROSS SECTION FROM 0.4 eV TO 12 MeV*

S. Plattard[†] G. F. Auchampaugh[‡] G. de Saussure
N. W. Hill[§] J. A. Harvey[§] R. B. Perez

(Reprint of Trans. Am. Nucl. Soc. 24, 198, 1981)

Protactinium-231 neutron-induced fission is one of the reactions contributing to stop the generation of unwanted quantities of ^{232}U produced along with ^{233}U in a liquid-metal fast breeder reactor using the $^{232}\text{Th}/^{233}\text{U}$ breeding cycle. Indeed, ^{232}U production is troublesome because of its short lifetime and because its decay chain yields too many alpha particles and gamma rays including a 2.51-MeV penetrating gamma radiation causing extra shielding problems. Since ^{231}Pa is not listed in ENDF/B-IV and only scarce data of the $^{231}\text{Pa}(n,f)$ cross section (σ_f) are available from ENDF/B-V, a high-resolution measurement of σ_f is mostly desirable to estimate properly the production rate of ^{232}U . In addition to this reactor physics pre-occupation, the opportunity was taken to study some fundamental aspects of the fission process, mainly to shed light on the existence of a shallow third minimum in the fission barrier of ^{231}Pa , as calculated by Moeller and Nix.²

The neutron source was provided by ORELA operating in (a) the 8-ns pulse-width mode at a frequency of 800 Hz for $E_n > 0.12$ MeV (run 1), and (b) the 40-ns pulse-width mode at a frequency of 450 Hz for $E_n < 10$ keV (run 2). A typical energy resolution of 500 eV was achieved at $E_n = 0.2$ MeV.¹

A sealed gaseous scintillator (58% He-2% H₂ at STP) located on a flight path perpendicular to the electron beam (at 41.68 m for run 1 and 18.30 m for run 2) was used to detect the fission fragments. Five out of the six detector cells contained each 53 mg of ^{231}Pa under oxide form painted on both sides of a 20-cm-diam $\times$ 12.5- μ m-thick semicircular titanium backing to a density 0.3 mg/cm². The remaining cell was loaded with 140 mg of uranium enriched to 93% in ^{235}U and electroplated on both sides of a semicircular stainless-steel disk to a density of 0.5 mg/cm².

For $0.12 < E_n$ (MeV) < 12 , the shape of σ_f was obtained from the $^{235}\text{U}(n,f)$ cross section derived from ENDF/B-IV, the value of σ_f was normalized between 0.9 and 1.1 MeV to the data of Sicre.³ Figure 1.11.1 presents a plot of the data where narrow peaks and strong fluctuations are predominant below 1 MeV. Besides a total lack of structures, the ENDF/B-V data plotted for comparison are systematically higher than our results. The striking feature of Fig. 1.11.2, where a more detailed picture of σ_f is presented from 0.12 to 0.42 MeV, lies in the occurrence of sharp peaks, some of them being nearly completely resolved, such as the 2.5-keV wide resonance at 156.7 keV. For comparison, the data of Sicre have been plotted over the same energy range and are generally lower than the present data. This is due partly to a better resolution of the present measurement and also because Sicre normalized his cross section to a $^{235}\text{U}(n,f)$ evaluation of Sowerby et al.⁴ instead of ENDF/B-IV.

For $0.4 < E_n$ (eV) $< 10^6$, a cross-section measurement was possible, thanks to a high purity of the ^{231}Pa samples (< 0.1 ppm of fissile materials) and, for the first time above 1.3 eV, narrow fission resonances were observed. The normalization procedure⁵ yields to $\sigma_f \sqrt{E_n}$, where peak values for σ_f can reach typically 80 mb. Rather than being clustered around definite energies as observed for other subthreshold fission cross sections,⁶ these resonances are uniformly distributed. The average fission width (Γ_f) = 8 μ eV is in very good agreement with the 7- μ eV value recommended in ENDF/B-V and with the 7.7- μ eV calculated value when using the ^{231}Pa fission barrier parameters of Sicre.³

Features of the fundamental aspects of this measurement have been reported in Ref. 5. We would like only to point out that occurrence of a pure vibrational state at $E_n = 156.7$ keV ($K^\pi = 3^+$) together with a nearby state of opposite parity ($K^\pi = 3^-$) centered around $E_n = 173.3$ keV favors the evidence for a third asymmetrically deformed minimum in the ^{231}Pa fission barrier.

*Research sponsored by the U.S. DOE, Office of Energy Research.

[†]Bryères-le-Châtel-France.

[‡]Los Alamos Scientific Laboratory.

[§]Physics Division.

Fig. 1.11.1. ^{231}Pa Fission Cross Section from 0.2 to 12 MeV. The data are plotted at intervals which correspond to a timing-channel width of 2 ns. The straight lines connecting the ENDF/B-V data points are just to guide the eye.

Fig. 1.11.2. ^{231}Pa Fission Cross Section from 0.12 to 0.42 MeV. The error bars correspond to one standard deviation. For clarity, the data points of Sicre are plotted with no error bars. The straight lines connecting the ENDF/B-V data points are just to guide the eye.

1. F. M. Mann and R. E. Schenter, Nucl. Sci. Eng., 65, 544 (1978).
2. P. Moeller and J. R. Nix, Proc. Physics and Chemistry of Fission, IAEA Vienna, 1, 103 (1974).
3. A. Sicre, PhD Thesis, Université de Bordeaux, France (1976), Rapport CENBG 76.
4. M. G. Sowerby, B. H. Patrick, and D. S. Mather, Ann. Nucl. Sci. Eng., 1, 7-8 (1974).
5. S. Plattard, G. F. Auchampaugh, N. W. Hill, G. de Saussure, R. B. Perez, and J. A. Harvey, Proc. Int. Conf. Nuclear Cross Sections for Technology, Knoxville (USA), paper EB7 to be published (Oct. 1979).
6. A. Michaudon, Adv. Nucl. Physics, 6, 1, Plenum Press (1973).

1.12. THE TRIPLE-JUMPED FISSION BARRIER OF ^{232}Pa *

S. Plattard[†] G. F. Auchampaugh[‡] N. W. Hill[§]
 G. de Saussure R. B. Perez J. A. Harvey[¶]

(Abstract from *Bull. Am. Phys. Soc.* 25, 487, 1980)

The neutron induced fission cross section (σ_f) of ^{231}Pa was measured at ORELA from 0.4 eV to 12 MeV at flight paths of 41.68 m for $E_n > 0.1$ MeV and 18.30 m for $E_n < 10$ keV. The fission fragments were detected in a sealed gas scintillator loaded with 265 mg of ^{231}Pa and 130 mg of ^{235}U . From 0.15 MeV up to 1 MeV, σ_f exhibits prominent structures particularly below 380 keV where two narrow (~ 2.6 keV FWHM) and well separated peaks are centered around 156.7 and 173.3 keV respectively. Occurrence of two such resonances with $K^\pi = 3^+$ and 3^- is very likely the signature of a vibrational level ($K = 3$) trapped in the asymmetrically deformed third well of the ^{232}Pa potential energy surface. In addition, uniformly distributed narrow fission resonances have been observed for the first time above a neutron energy of 1.3 eV. This feature, together with a measured average fission width of 8 μeV for these resonances, indicates that (1) the first minimum of the ^{232}Pa fission barrier is on the order of, or lower than, the neutron separation energy in ^{232}Pa and (2) the third minimum is rather shallow (0.5 to 1 MeV).

* Research partially supported by DOE.

[†] Centre d'Etudes de Bruyeres-le-Chatel, France.

[‡] Los Alamos Scientific Laboratory.

[§] Instrumentation and Controls Division.

[¶] Physics Division.

1.13. PROPRIETES SPECTROSCOPIQUES DE QUELQUES STRUCTURES FINES OBSERVEES DANS LE SEUIL DE LA REACTION $^{231}\text{Pa}(n,f)$ *

S. Plattard[†] G. F. Auchampaugh[‡] N. W. Hill[§]
 G. de Saussure R. B. Perez J. A. Harvey[¶]

(Abstract of paper presented at *Journées d'Etudes sur la Fission, L'Alpe D'Auzes*, 6-10 Octobre 1980)

La section efficace de la réaction $^{231}\text{Pa}(n,f)$, (σ_f), et l'anisotropie des fragments de fission ont été mesurées entre 0,12 et 0,45 MeV, respectivement avec une résolution nominale de 0,19 ns/m et 1,6 ns/m. La détermination du moment angulaire et de la parité de certaines structures fines indique la possibilité pour la barrière de fission de ^{232}Pa de posséder un 3ème minimum à une déformation asymétrique du noyau. Par ailleurs, la mesure de σ_f au-dessous de 100 eV a permis d'observer au-dessus de 1,3 eV, pour la première fois, des résonances étroites ayant une largeur de fission $\langle \Gamma_f \rangle > 8 \mu\text{eV}$. L'examen de σ_f dans cette gamme d'énergie n'indique pas l'existence d'un effet de structure intermédiaire comme c'est le cas pour d'autres actinides dits non fissiles.

* Research partially sponsored by DOE.

[†] Centre d'Etudes de Bruyeres-le-Chatel, France.

[‡] Los Alamos Scientific Laboratory.

[§] Instrumentation and Controls Division.

[¶] Physics Division.

1.14. SOME SPECTROSCOPIC PROPERTIES OF FINE STRUCTURES OBSERVED NEAR THE $^{231}\text{Pa}(n,f)$ FISSION THRESHOLD*

S. Plattard[†] G. F. Auchampaugh[‡] N. W. Hill[§] G. de Saussure
J. A. Harvey[‡] R. B. Perez

(Abstract of paper to be published in *Physical Review Letters*.)

The ^{231}Pa neutron-induced fission cross section from 140 keV to 400 keV was resolved into finer structures. For some of the fractionated vibrational resonances in this energy region, the assignment of spectroscopic parameters may support evidence for an asymmetrically deformed third minimum in the ^{232}Pa fission barrier. Also, for the first time, narrow fission resonances are observed above 1.3 eV exhibiting an average fission width $\langle\Gamma\rangle_{\text{obs}} = 8 \text{ } \mu\text{eV}$.

* Research partially supported by Department of Energy.

[†] Centre d'Etudes de Bruyeres-le-Chatel, France.

[‡] Los Alamos Scientific Laboratory.

[§] Instrumentation and Controls Division.

[¶] Physics Division.

1.15. MEASUREMENT OF THE AVERAGE NUMBER OF PROMPT NEUTRONS EMITTED PER FISSION OF ^{235}U RELATIVE TO ^{252}Cf FOR THE ENERGY REGION 500 eV TO 10 MeV*

R. Gwin R. R. Spencer R. W. Ingle[†] J. H. Todd[†] H. Weaver

(Abstract of ORNL/TM-7146, January, 1980)

The average number of prompt neutrons emitted per fission, $\bar{\nu}_p(E)$, has been measured for ^{235}U relative to $\bar{\nu}$ for the spontaneous fission of ^{252}Cf over the neutron energy range from 500 eV to 10 MeV. The samples of ^{235}U and ^{252}Cf were contained in fission chambers located in the center of a large liquid scintillator. Fission neutrons were detected by the large liquid scintillator. The present values of $\bar{\nu}_p(E)$ for ^{235}U are about 0.8% larger than those measured by Boldeman. In earlier work with the present system, it was noted that Boldeman's value of $\bar{\nu}_p(E)$ for thermal energy neutrons was about 0.8% lower than obtained at ORELA. It is suggested that the thickness of the fission foil used in Boldeman's experiment may cause some of the discrepancy between his and the present values of $\bar{\nu}_p(E)$. For the energy region up to 700 keV, the present values of $\bar{\nu}_p(E)$ for ^{235}U agree, within the uncertainty, with those given in ENDF/B-V. Above 1 MeV the present results for $\bar{\nu}_p(E)$ range about the ENDF/B-V values with differences up to 1.3%.

* Research sponsored by DOE Office of Reactor Research and Technology.

[†] Instrumentation and Controls Division.

1.16. INTERIM REPORT ON THE ORNL ABSOLUTE MEASUREMENTS OF $\bar{\nu}_p$ FOR ^{252}Cf *

R. R. Spencer R. Gwin R. Ingle† H. Weaver

(Abstract of ORNL/TM-8808, September, 1979)

An initial effort has been made to measure absolutely the average number of prompt neutrons, $\bar{\nu}_p$, emitted in spontaneous fission of ^{252}Cf to an unprecedented accuracy of $\pm 0.25\%$. Fission neutrons were counted with a large, gadolinium poisoned, liquid scintillator. A "white source" of neutrons from the ORELA was used to calibrate the detector efficiency as a function of neutron energy. Source neutrons were scattered into the large scintillator by a thin NE-213 proton-recoil detector which employed pulse shape discrimination to eliminate unwanted γ -ray background. The resulting neutron-energy and scattering angle-dependent efficiencies were used to normalize a Monte Carlo calculation of the scintillator efficiency for fission neutrons. Under the assumptions that the effects of parasitic charged particle reactions and multiple neutron scattering in the proton-recoil counter have negligible influence on the efficiency calibration, the value of the average number of prompt neutrons emitted per ^{252}Cf fission was found to be 3.783 ± 0.010 . This report is intended as a documentary and guide for future measurements incorporating improvements suggested by the analysis of this first determination.

* Research sponsored by DOE Office of Basic Energy Sciences.

† Instrumentation and Controls Division.

1.17. ABSOLUTE MEASUREMENT OF $\bar{\nu}_p$ FOR ^{252}Cf BY THE LARGE LIQUID SCINTILLATOR TANK TECHNIQUE*

R. R. Spencer

(Abstract of paper in Nuclear Cross Sections for Technology, NBS Special Publication 594, p. 728, 1980)

A vigorous effort to dispel the scandal of the $\sim 2\%$ dispersion in reported experimental values of ^{252}Cf $\bar{\nu}$, the average number of neutrons emitted in spontaneous fission, has been underway over the past 5 years. The goal is to reduce the uncertainty in this fundamental parameter to the $\pm 0.25\%$ level needed for reactor physics application. Both new measurements and reevaluation of older measurements are involved. At ORNL a new measurement is being carried out using the large liquid scintillator neutron detector. Findings of the most recent experiment, incorporating improvements suggested in a preliminary study, will be discussed.

* Research sponsored by DOE Office of Basic Energy Sciences.

1.18. PRECISE MEASUREMENT AND ANALYSIS OF NEUTRON TRANSMISSION THROUGH ^{232}Th *

D. K. Olsen R. W. Ingle† J. L. Portney‡

(Abstract of paper presented at ANS Topical Meeting on Advances in Reactor Physics and Shielding, Sun Valley, Idaho, September 14-17, 1980)

Three sets of transmission time spectra through up to eight samples of ^{232}Th have been measured for neutron energies from 6.0 MeV to 0.1 MeV using a flight-time technique over 22- and 40-m path lengths, the ORELA pulsed neutron source, and a 1-mm thick lithium glass detector. The resulting total cross section from 0.1 to 20.0 eV seems to be smaller than that contained in the ENDF/B-V evaluation. Least-squares analysis of the transmissions from 9 to 440 eV using a multilevel Breit-Wigner formalism results in neutron widths

consistent with those previously reported. An average radiation width of 25.2 MeV is obtained for 19 low-energy s-wave resonances.

* Research sponsored by DOE Office of Reactor Research and Technology.

† Instrumentation and Controls Division.

‡ 1980 Summer Student, Oak Ridge Associated Universities.

1.19. THE $\text{Th}(n, \gamma)$ REACTION CROSS SECTION FOR NEUTRONS OF ENERGY BETWEEN 0.3 AND 20 MEV*

G. L. Morgan†

(Abstract of *Nucl. Sci. Eng.* 72, 359, 1979, and of ORNL/TM-6758, August, 1979)

Differential cross sections for neutron-induced gamma-ray production from thorium have been measured for incident neutron energies between 0.3 and 20.0 MeV. The Oak Ridge Electron Linear Accelerator was used as a neutron source. A NaI spectrometer at 125 deg detected the gamma rays. Data include the doubly differential cross section, $d^2\sigma/d\Omega dE_\gamma$, for gamma-ray energies between 0.3 and 10.6 MeV and the integrated gamma-ray yield as a function of the incident neutron energy.

* Research sponsored by DOE Office of Reactor Research and Technology.

† Now at Los Alamos Scientific Laboratory.

1.20. CROSS SECTIONS FOR THE $\text{Cu}(n, xn)$ AND $\text{Cu}(n, \gamma)$ REACTIONS BETWEEN 1 AND 20 MEV*

G. L. Morgan†

(Abstract of ORNL-5489, February, 1979)

Differential cross sections for the production of secondary neutrons and gamma rays from neutron interactions in natural copper have been measured at 130 deg. (lab) for incident neutron energies in the range 1 to 20 MeV. An electron linac was used as a pulsed, white neutron source. Incident neutron energies were determined using time-of-flight techniques for a source-to-sample distance of 48 m. Secondary spectra were determined by unfolding the pulse-height distributions observed in a NE-213 scintillation counter. The results are compared to the current evaluated nuclear data file (ENDF/B-IV, MAT 1295).

* Research sponsored by DOE Office of Reactor Research and Technology.

† Now at Los Alamos Scientific Laboratory.

1.21. CROSS SECTIONS FOR THE $\text{Ti}(n, xn)$ AND $\text{Ti}(n, \gamma)$ REACTIONS BETWEEN 1 AND 20 MEV*

G. L. Morgan†

(Abstract of ORNL-5583, August, 1979)

Differential cross sections for the production of secondary neutrons and gamma rays from neutron interactions in natural titanium have been measured at 130 deg. (lab) for

incident neutron energies in the range 1 to 20 MeV. An electron linac was used as a pulsed, white neutron source. Incident neutron energies were determined using time-of-flight techniques for a source-to-sample distance of 48 m. Secondary spectra were determined by unfolding the pulse-height distributions observed in a NE-213 scintillation counter. The results are compared to the current evaluated nuclear data file (ENDF/B-IV, MAT 1286).

*Research sponsored by DOE Office of Reactor Research and Technology.

†Now at Los Alamos Scientific Laboratory.

1.22. THE $O(n, \gamma)$ REACTION CROSS SECTION FOR INCIDENT NEUTRON ENERGIES BETWEEN 6.5 AND 20.0 MEV*

G. L. Morgan[†] G. T. Chapman

(Abstract of ORNL-5575, September, 1979)

Differential cross sections for the neutron-induced gamma-ray production from oxygen have been measured for incident neutron energies between 6.5 and 20.0 MeV. The Oak Ridge Electron Linear Accelerator (ORELA) was used to provide the neutrons and a NaI spectrometer to detect the gamma rays at 125°. The data presented are the double differential cross section, $d^2\sigma/d\Omega dE$, for gamma-ray energies between 1.6 and 10.6 MeV for coarse intervals in incident neutron energy. The integrated yield for gamma rays of energies greater than 1.6 MeV with higher resolution in the neutron energy is also presented. The experimental results are compared with the Evaluated Nuclear Data File (ENDF).

*Research sponsored by Defense Nuclear Agency under Subtask NAQ10.

†Now at Los Alamos Scientific Laboratory.

1.23. MEASUREMENT AND ANALYSIS OF THE $^{23}\text{Na}(n, \gamma)$ REACTION CROSS SECTION FOR $0.2 \leq E_n \leq 20$ MEV*

D. C. Larson G. L. Morgan[†]

(Abstract of Nucl. Sci. Eng. 75, 151-158, 1980)

Differential cross sections for neutron-induced gamma-ray production from sodium have been measured for incident-neutron energies between 0.2 and 20.0 MeV. Gamma rays with energies $0.35 \leq E_\gamma \leq 10.6$ MeV were detected with a sodium iodide spectrometer at 125 deg. The data presented are the double differential cross section, $d^2\sigma/d\Omega dE$, for coarse intervals in incident-neutron energy. The measured results are compared with existing data, with calculations based on multistep Hauser-Feshbach theory, and with a benchmark gamma-ray production measurement performed at the Oak Ridge Tower Shielding Facility (TSF). Average agreement between our measured results and model calculations is within 15%. The cross sections measured at the TSF are typically 30% larger than our results, except for gamma-ray energies between 1.1 and 1.5 MeV where the TSF benchmark predicts a yield 20 times greater than we observe. Results of the present measurement have been incorporated for the gamma-ray production in the Evaluated Nuclear Data File.

*Research sponsored by DOE Office of Basic Energy Sciences.

†Now at Los Alamos Scientific Laboratory.

1.24. STATUS REPORT(S) TO THE DOE NUCLEAR DATA COMMITTEE*

F. G. Perey J. C. (Gentry) Lundy

[Abstract of ORNL/TM-6873, April, 1973 (and of ORNL/TM-7310, April, 1980)]

This report was prepared for the DOE Nuclear Data Committee and covers work performed at ORNL since April 1973 (April, 1979) in areas of nuclear data of relevance to the U.S. applied nuclear energy program. The report was mostly generated through a review of abstracts of work completed to the point of being subjected to some form of publication in the open literature, formal ORNL reports, ORNL technical memoranda, progress reports, or presentation at technical conferences. As much as possible we have reproduced the complete abstract of the original publication with only minor editing. In a few cases progress reports were written specifically for this publication. The editors have selected the materials to be included in this report on the basis of perceived interests of DOE Nuclear Data Committee members and cannot claim completeness.

*Research sponsored by DOE Office of Basic Energy Sciences.

1.25. ELECTRON ANTINEUTRINO SPECTRUM FOR $^{235}\text{U}(n_{\text{th}}, f)^*$

J. K. Dickens

(Abstract of paper to be published in *Physical Review Letters*)

The $\bar{\nu}_e$ spectrum has been computed for fission-product decay following a 30-day irradiation of ^{235}U by thermal neutrons. Estimated uncertainties lie in the range 7-15% for $E_\nu < 6$ MeV. Analysis relied on comparisons of calculated β -ray data with recently obtained experimental β -ray spectra. The $\bar{\nu}_e$ spectrum is softer than all other calculated $\bar{\nu}_e$ spectra. Cross sections (10^{-44} cm²) were calculated as $\sigma(\bar{\nu}_e + p \rightarrow n + e^+) = 58 \pm 3$, $\sigma(\bar{\nu}_e + d \rightarrow n + p + e^+) = 2.7 \pm 0.2$, and $\sigma(\bar{\nu}_e + d \rightarrow n + n + e^+) = 1.04 \pm 0.13$.

*Research sponsored by DOE Office of Basic Energy Sciences.

1.26. FISSION PRODUCT DECAY HEAT FOR THERMAL REACTORS*

J. K. Dickens

(Abstract of paper in *Nuclear Cross Sections for Technology*, NBS Special Publication 404, p. 26, 1980)

In the past five years there have been new experimental programs to measure decay heat (i.e., time dependent beta-plus gamma-ray energy release rates from the decay of fission products) following thermal-neutron fission of ^{235}U , ^{239}Pu , and ^{241}Pu for times after fission between 1 and $\sim 10^5$ sec. Experimental results from the ORNL program stress the very short times following fission, particularly in the first few hundred sec. Complementing the experimental effort, computer codes have been developed for the computation of decay heat by summation of calculated individual energies released by each one of the fission products. By suitably combining the results of the summation calculations with the recent experimental results, a new Decay Heat Standard has been developed for application to safety analysis of operations of light water reactors. The new standard indicates somewhat smaller energy release rates than those being used at present, and the overall uncertainties assigned to the new standard are much smaller than those being used at present.

*Research sponsored by U.S. Nuclear Regulatory Commission, Office of Nuclear Regulatory Research.

1.27. FISSION-PRODUCT ENERGY RELEASE FOR TIMES FOLLOWING THERMAL-NEUTRON FISSION OF ^{235}U BETWEEN 2 AND 14000 s*

J. K. Dickens T. A. Love J. W. McConnell R. W. Peelle

(Abstract of Nucl. Sci. Eng. 74, 116, 1980)

Fission-product decay energy-release rates have been measured for thermal-neutron fission of ^{235}U . Spectral data were obtained using scintillation spectrometers for beta and gamma rays separately, and were processed to the form of total yield and total energy-release integrals for each set of time-interval parameters. The irradiations were for 1, 10, and 100 s, and measurements were made covering times following irradiation from 1.7 to 13950 s. The separate beta- and gamma-ray energy-release data were summed to obtain the total ($\beta + \gamma$) energy-release rates for the cases studied. The data are processed to provide two standard representations of decay energy release, the one following a pulse of fissions, and the other following an infinite period of irradiation. A complete representation of estimated uncertainties is given in the form of a variance-covariance matrix. For the pulse representation of the data, diagonal components correspond to uncertainties in the range of 3 to 4%, with correlation coefficients in the range from 0.1 to 0.5. The experimental data are compared with other experimental data. The present results are generally smaller than other data, in some cases by more than the estimated uncertainties.

The present results are smaller than the proposed 1973 American Nuclear Society (ANS) Decay-Heat Standard by as much as 10% for times following fission between 2 and 400 s, and are also smaller than the presently proposed (1978) ANS Decay-Heat Standard by 5 to 8% for the time interval 2 to 600 s. The reasons for these differences are discussed, and the importance for analyses using the new standard is presented.

*Research jointly sponsored by the U.S. Nuclear Regulatory Commission, Office of Nuclear Regulatory Research, and by DOE Office of Reactor Research and Technology.

1.28. FISSION PRODUCT YIELDS FOR THERMAL-NEUTRON FISSION OF PLUTONIUM-239*

J. K. Dickens J. W. McConnell

(Abstract of Nucl. Sci. Eng. 73, 42, 1980)

Absolute cumulative yields have been determined for 49 fission products representing 36 mass chains created during thermal-neutron fission of ^{239}Pu , including 3 mass chains for which no prior data exist. Using Ge(Li) spectroscopy, spectra were obtained of gamma rays from decay of fission products between 1550 s and 31 days after a 100-s irradiation. Data were obtained for all fission products simultaneously. Gamma rays were assigned to the responsible fission products by matching gamma-ray energies and half-lives. Gamma-ray data associated with decay of ^{135}I and ^{140}Ba - ^{140}La , in particular, were thoroughly studied; uncertainties were obtained for the two largest intensity gamma rays from decay of ^{135}I that are smaller than previously evaluated uncertainties.

Fission product yields were obtained from the data by first determining the appropriate gamma-ray activity as of the end of the irradiation, then correcting for detector efficiency and gamma-ray branching ratio, and, finally, dividing by the number of fissions created in the sample. The number of fissions was determined by direct comparison of gamma rays emanating from fission products created during a careful irradiation of a well-calibrated ^{239}Pu -loaded fission chamber.

The resulting fission product yields are compared with previous measurements and with recommended yields given in two recent (and independent) evaluations. The present results are significantly larger for mass chains 101 and 105, somewhat smaller for mass chains 87 and 151, and in reasonable agreement with the remaining mass chains. Uncertainties assigned to the present results range between 2.5 and 25%, and are smaller than or comparable to uncertainties assigned to previous experimental (or evaluated) yields for 14 mass chains.

* Research jointly sponsored by U.S. Nuclear Regulatory Commission, Office of Nuclear Regulatory Research; DOE Office of Reactor Research and Technology; and Electric Power Research Institute.

1.29. DELAYED BETA- AND GAMMA-RAY PRODUCTION DUE TO THERMAL-NEUTRON FISSION OF ^{239}Pu : TABULAR AND GRAPHICAL SPECTRAL DISTRIBUTIONS FOR TIMES AFTER FISSION BETWEEN 2 AND 14000 s*

J. K. Dickens J. R. England† T. A. Love J. W. McConnell
J. F. Emery† K. J. Northcutt† R. W. Peelle

[Abstract of ORNL/NUREG-66 (NUREG/CR-1172) January, 1980]

Fission-product decay energy-release rates have been measured for thermal-neutron fission of ^{239}Pu . Samples of mass 1 and 5 μg m were irradiated for 1 to 100 s using the fast pneumatic-tube facility at the Oak Ridge Research Reactor. The resulting beta- and gamma-ray emissions were separately counted for times-after-fission between 2 and 14,000 s, giving spectral distributions $N(E_\gamma)$ vs E_γ and $N(E_\beta)$ vs E_β . The gamma-ray spectra were obtained using a NaI detector, and the beta-ray spectra were obtained using an NE-110 detector with an anticoincidence mantle. The raw data were unfolded to provide spectral distributions of moderate resolution. These distributions are given in graphical and tabular form as differential spectral intensity $I(E)$ (MeV^{-1} fission $^{-1}$) averaged over gamma-ray energy intervals ranging from 10 keV for $E_\gamma < 0.18$ MeV to 100 keV for $E_\gamma > 6.8$ MeV, and beta-ray energy intervals ranging from 20 keV for $E_\beta < 0.25$ MeV to 160 keV for $E_\beta > 6.4$ MeV. Counting-time intervals ranged from 1 s for times-after-fission (t_w) < 6 s to 4000 s for $t_w \sim 10^4$ s.

For comparisons the graphical representations show calculated spectra obtained using the CINDER-10 summation code and the ENDF/B-IV fission yield and decay scheme data base.

* Research sponsored by U.S. Nuclear Regulatory Commission, Office of Nuclear Regulatory Research.

† Los Alamos Scientific Laboratory.

‡ Analytical Chemistry Division.

1.30. FISSION-PRODUCT ENERGY RELEASE FOR TIMES FOLLOWING THERMAL-NEUTRON FISSION OF PLUTONIUM-239 AND PLUTONIUM-241 BETWEEN 2 AND 14000 SECONDS*

J. K. Dickens T. A. Love J. W. McConnell R. W. Peelle

(Abstract of paper to be published in Nuclear Science and Engineering)

Absolute fission-product decay energy-release rates have been measured for thermal-neutron fission of ^{239}Pu and ^{241}Pu . Spectra data were obtained using scintillation spectrometers for beta and gamma rays separately, and were processed to the form of total yield and total energy-release integrals per fission for each set of time-interval parameters. The irradiations were for 1, 5, and 50 (^{241}Pu) or 100 (^{239}Pu) s, and measurements were made covering times following irradiation from 1.7 to 13950 s. The separate beta- and gamma-ray energy-release data were summed to obtain the total ($\beta+\gamma$) energy-release rates for the cases studied. The data are processed to provide two standard representations of decay energy release, the one following a fission pulse, and the other following an infinite fission period. Complete representations of estimated uncertainties are given in the form of variance-covariance matrices for the first time. For the pulse representation of the data, diagonal components correspond to uncertainties in the range of 3 to 6%, with correlation coefficients in the range from 0.1 to 0.5. Comparisons with other

experimental data show that the present results are generally smaller than the other data, in some cases by more than the estimated uncertainties.

The present results are also smaller than the present (1979) ANS Decay-Heat Standard for ^{239}Pu by 2 to 4% for the time interval 2 to 14000 s. For ^{241}Pu decay heat, the present data are larger than previously obtained experimental ^{235}U data but smaller than the adopted ^{235}U standard in the (1979) ANS Decay-Heat Standard. The importance of these comparisons for analyses using the new standard is present.

* Research sponsored by U.S. Nuclear Regulatory Commission, Office of Nuclear Regulatory Research.

1.31. YIELDS OF SHORT-LIVED FISSION PRODUCTS PRODUCED BY THERMAL-NEUTRON FISSION OF PLUTONIUM-239*

J. K. Dickens J. W. McConnell K. J. Northcutt†

(Abstract of a paper to be published as a Technical Note to Nuclear Science and Engineering)

The absolute yields of 29 fission products representing 23 different mass chains produced by thermal-neutron fission of ^{239}Pu and having half-lives between 30 and 1100 s have been determined using Ge(Li) spectroscopy methods. Spectra of 30 gamma rays emitted in the decay of the fission products between 35 s and 1950 s after a 5-s irradiation were obtained. Gamma rays were assigned to the responsible fission products by matching gamma-ray energies and half-lives. Fission-product yields were then obtained from the data by first determining the appropriate gamma-ray activity as of the end of the irradiation, correcting for detector efficiency and gamma-ray branching ratio, and, finally, dividing by the number of fissions created in the sample. The number of fissions was determined by direct comparison of gamma rays emanating from fission products created during a careful irradiation of a well-calibrated ^{239}Pu -loaded fission chamber.

The resulting fission-product yields are compared with previous measurements and with recommended yields given in two recent (and independent) evaluations. Uncertainties assigned to the present results range between 6 and 45%, and are smaller than or comparable to uncertainties assigned to previous experimental or evaluated yields for six mass chains.

* Research sponsored by U.S. Nuclear Regulatory Commission, Office of Nuclear Regulatory Research.

† Analytical Chemistry Division.

1.32. FISSIONS DETERMINATION IN ^{239}Pu SAMPLE*

J. K. Dickens J. W. McConnell

(Abstract of EPRI Report NP-997, February, 1979)

A sample of ^{239}Pu of nominally 40 mg mass was irradiated for 24 hours at the IRT Corporation ^{252}Cf facility as part of their program to measure fission-product decay heat. The number of fissions created in this irradiation was measured at ORNL by studying the gross gamma-ray spectra measured with high resolution for cooling times between 13 and 32 days. The number of fissions was determined to be $(1.326 \pm 0.019) \times 10^{11}$ using yields measured for the 228-keV (^{132}Te), 497-keV (^{103}Ru), and 1597-keV (^{140}La) gamma rays and calibration factors based on absolute fission counting.

* Research sponsored by Nuclear Power Division, Electric Power Research Institute.

1.33. GAMMA RAYS FOLLOWING ALPHA DECAY OF ^{245}Cm AND THE LEVEL STRUCTURE OF ^{241}Pu *

J. K. Dickens J. W. McConnell

[Abstract of Phys. Rev. C 22(3), 1344, 1960]

Relative intensities for K x rays and gamma rays emanating from ^{245}Cm have been measured using several Ge photon detectors. The absolute intensity for the dominant 175-keV gamma ray in ^{241}Pu was determined to be 9.5 photons per 100 ^{245}Cm alpha decays with an uncertainty of $\pm 7\%$. Eleven gamma rays have been placed as transitions among levels in ^{241}Pu .

*Research sponsored by DOE Office of Basic Energy Sciences.

1.34. YIELDS OF FISSION PRODUCTS PRODUCED BY THERMAL-NEUTRON FISSION OF ^{245}Cm *

J. K. Dickens J. W. McConnell

(Abstract of paper to be published in The Physical Review)

Absolute yields have been determined for 105 gamma rays emitted in the decay of 95 fission products representing 54 mass chains created during thermal-neutron fission of ^{245}Cm . These results include 17 mass chains for which no prior yield data exist. Using a Ge(Li) detector, spectra were obtained of gamma rays between 30 s and 0.3 year after very short irradiations of thermal neutrons on a 1 μg sample of ^{245}Cm . On the basis of measured gamma-ray yields and known nuclear data, total chain mass yields and relative uncertainties were obtained for 51 masses between 84 and 156. The absolute overall normalization uncertainty is $< 8\%$. The measured A-chain cumulative yields make up 81% of the total light mass ($A \leq 121$) yield and 92% of the total heavy mass yield.

The results are compared with fission-product yields previously measured with generally good agreement. The mass-yield data have been compared with those for thermal-neutron fission of ^{239}Pu and for $^{252}\text{Cf}(\text{s.f.})$; the influences of the closed shells $Z = 50$, $N = 82$ are not as marked as for thermal-neutron fission of ^{239}Pu but much more apparent than for $^{252}\text{Cf}(\text{s.f.})$. Information on the charge distribution along several isobaric mass chains was obtained by determining fractional yields for 12 fission products. The charge distribution width parameter, based upon data for the heavy masses, $A = 128$ to 143, is independent of mass to within the uncertainties of the measurements.

Gamma-ray assignments were made for decay of short-lived fission products for which absolute gamma-ray transition probabilities are either not known or in doubt. Absolute gamma-ray transition probabilities were determined as $(51 \pm 8)\%$ for the 374-keV gamma ray from decay of ^{116}Rh , $(35 \pm 7)\%$ for the 1096-keV gamma ray from decay of ^{133}Sb , and $(21.2 \pm 1.2)\%$ for the 255-keV gamma ray from decay of ^{142}Ba .

*Research sponsored by DOE Office of Basic Energy Sciences.

1.35. HALF LIFE OF ^{132}Te *

J. K. Dickens

[Abstract of Radiochem. Radioanal. Letters 39 (2), 107, 1979]

The half life of ^{132}Te has been measured by γ -ray spectroscopy. γ -ray spectra of fission-product decay following thermal-neutron fission of ^{239}Pu were obtained for decay times between one and thirty days. Decay of the 228.2-keV γ -ray from ^{132}Te was analyzed to obtain the half life of ^{132}Te . The measured ^{132}Te half life was 76.29 ± 0.21 hr.

Similar measurements were made for the 140.5-keV γ -ray from decay of ^{99}Mo , the 364.5-keV γ -ray from decay of ^{131}I , and 293.2-keV γ -ray from decay of ^{143}Ce . The half lives obtained were 66.16 ± 0.30 for ^{99}Mo , 191.93 ± 1.34 hr for ^{131}I , and 33.31 ± 0.32 hr for ^{143}Ce .

* Research sponsored by the Electric Power Research Institute.

1.36. ABSOLUTE YIELD OF 140.5 keV GAMMA RAY FOLLOWING DECAY OF ^{99}Mo *

J. K. Dickens T. A. Love

(Abstract of Nucl. Instr. Methods 176, 535, 1980)

The absolute intensity for the dominant 140.5 keV gamma ray in ^{99}Tc was determined to be 90.7 ± 0.6 per 100 ^{99}Mo disintegrations for ^{99}Mo decay in equilibrium with the decay of the ^{99}Tc daughter. Relative intensities for K X-ray and gamma rays emanating from ^{99}Mo in equilibrium with its ^{99}Tc daughter were measured using several Ge photon detectors. These include a direct measurement of the very weak 142.6 keV gamma ray. Combining these intensities with an evaluated set of electron-conversion coefficients provided a set of absolute intensities and uncertainties for the observed gamma rays.

A complete discussion of the method of analysis, showing relationships among uncertainties of measured and evaluated data, is given.

* Research sponsored by U.S. Nuclear Regulatory Commission, Office of Nuclear Regulatory Research.

1.37. METHOD FOR SAMPLING FROM FISSION NEUTRON ENERGY SPECTRA*

F. H. Froehner[†] R. R. Spencer

(Abstract of ORELA/TM-7631, 1980)

A simple method for fast and efficient sampling from the Watt fission neutron energy spectrum is described. As a limiting case the Maxwellian energy distribution can also be sampled. A short FORTRAN routine written for this purpose and results obtained with it are presented. The routine is shown to give accurate results, and requires < 1 ms/sample on a DEC KA-10 processor.

* Research sponsored by DOE Office of Basic Energy Sciences.

[†] On leave from Kernforschungszentrum Karlsruhe, Germany.

1.38. PRELIMINARY STUDY OF PSEUDORANDOM BINARY SEQUENCE PULSING OF ORELA*

N. M. Larson[†] D. K. Olsen

(Abstract of ORNL/TM-6633, March, 1980)

It has been suggested that pseudorandom binary sequence (PRBS) pulsing might enhance the performance of the Oak Ridge Electron Linear Accelerator (ORELA) for neutron-induced, time-of-flight (TOF) cross-section measurements. In this technical memorandum, equations are developed for expected count rates, statistical variances, and backgrounds for a pulsing scheme in which a PRBS is superimposed on the periodic equal-intensity ORELA bursts. Introduction of the PRBS modification permits neutrons of different energies

originating from different bursts to reach the detector simultaneously, and the signal corresponding to a unique flight time to be extracted mathematically. Relative advantages and disadvantages of measurements from conventional and PRBS pulsing modes are discussed in terms of counting statistics and backgrounds. Computer models of TOF spectra are generated for both pulsing modes, using as examples a 20-meter ^{233}U fission-chamber measurement and a 155-meter ^{238}U sample-in transmission measurement. Detailed comparisons of PRBS vs conventional results are presented. This study indicates that although PRBS pulsing could enhance ORELA performance for selected measurements, for general ORELA operation the disadvantages from PRBS pulsing probably outweigh the advantages.

* Research sponsored by DOE Office of Reactor Research and Technology.

† UCC-ND Computer Sciences Division.

1.39. PROCEDURES MANUAL FOR THE OAK RIDGE ELECTRON LINEAR ACCELERATOR*

H. A. Todd†

(Abstract of OREL/TM-6801, March, 1979)

The Procedures Manual for the Oak Ridge Electron Linear Accelerator, Second Edition, contains specific information pertaining to operation and safety of the facility. Items such as the interlock system, radiation monitoring, emergency procedures, night shift and weekend operation, and maintenance are discussed in detail.

* Work sponsored by Department of Energy.

† Instrumentation and Controls Division.

2.0 INTRODUCTION

Our major cross-section evaluation efforts have been to assess the adequacy of the recently released fifth version of the official evaluated nuclear data file (ENDF/B-V), to document the contributions of our group to the file, to patch up weak points in the file's coverage, and to develop improved evaluation techniques for inclusion of theoretical information and for the combination of experimental measurements.

For incident neutron energies above 10 MeV, the secondary and tertiary reactions observed become sufficiently complex, and the available detail in the experimental observations becomes so sparse, that evaluators rely on "evaluation codes," aggregates of nuclear model codes, to keep track of knowledge available through nuclear models and allow determination of all the necessary cross-section detail while maintaining consistency with any directly pertinent experimental data. The first two abstracts deal with important extensions of the Oak Ridge evaluation code to treat the nonisotropic angular distributions always observed in preequilibrium reactions in a manner that is coherent with the multistep Hauser-Feshbach treatment of the equilibrium or compound nuclear reactions at the same energy. The third paper demonstrates in a simple way that only the more sophisticated evaluation groups using such nuclear model codes were able to reproduce in ENDF/B-V the observed neutron spectra from 14-MeV neutrons. This is an energy region important to fusion technology.

A number of the abstracts cover papers that summarize evaluation efforts and document particular sets of cross sections for which the ORNL group has responsibility. In this documentation we strove both to explain what was done and to make apparent further improvements that are needed.

The simultaneous evaluation of $^{32}\text{S}(n,p)$, $^{56}\text{Fe}(n,p)$, and $^{65}\text{Cu}(n,2n)$ is an interesting precursor to a significant international effort to combine in an appropriate way the major cross section ratio measurements that have been performed to obtain the "dosimetry" reaction cross sections, activation cross sections conveniently used in efforts to characterize neutron spectra important to radiation damage studies. Such ratio measurements were not properly utilized in most past evaluations, but such combination has become practical through use of generalized least-squares programs such as "GLUCS" described in one of the abstracted reports. Similarly, work on a multilevel K-matrix analysis program that allows proper combination of experimental results has born fruit already in "Sammy" which is now available in its first published version. Both of these data combination program developments will help make possible evaluation of the variance-covariance matrices of evaluated cross section quantities. The international recognition of the need for such information and development of techniques for its codification has depended greatly on leadership from our ORNL group.

2.1. A CONSISTENT NUCLEAR MODEL FOR COMPOUND AND PRECOMPOUND REACTIONS WITH CONSERVATION OF ANGULAR MOMENTUM*

C. Y. Fu

(Abstract of ORNL/TM-7042, May 1980; of paper in *Nuclear Cross Sections for Technology*, NBS Special Publication 594, p. 757, 1980; and of paper to be published in *Phys. Rev. C*)

The exciton model of precompound reaction is modified such that it automatically reduces to the usual evaporation formula after equilibrium has been reached. The result is further modified to conserve angular momentum in a form compatible with the Hauser-Feshbach formula. This allows a consistent description of intermediate excitations from which tertiary reaction cross sections can be calculated for transitions to discrete residual levels with known spins and parities. Level densities used for the compound component of reaction cross sections are derived from direct summation of the particle-hole state densities used for the precompound component. Predicted neutron, proton, and alpha-particle production cross sections and spectra from 14-MeV neutron-induced reactions are compared with experimental data. Model parameters of general validity are fixed beforehand. Two parameters are determined from calculations for ^{56}Fe and then used with reasonable success for predicting cross sections for twelve other nuclides.

* Research sponsored by DOE Office of Basic Energy Sciences.

2.2. DEVELOPMENT AND APPLICATIONS OF MULTI-STEP HAUSER-FESHBACH/PRE-EQUILIBRIUM MODEL THEORY*

C. Y. Fu

(Abstract of paper presented at Symposium on Neutron Cross Sections from 10-50 MeV, Brookhaven National Laboratory, May 12-14, 1980; BNL-NCS-51245, Vol. 2, p. 675, July, 1980)

A recently developed model that combines compound and precompound reactions with conservation of angular momentum is discussed. This model allows a consistent description of intermediate excitations from which tertiary reaction cross sections can be calculated for transitions to the continuum as well as to the discrete residual levels with known spins and parities. Predicted neutron, proton, and alpha-particle production cross sections and emission spectra from 14-MeV neutron-induced reactions are compared favorably with angle-integrated experimental data for 12 nuclides. The model is further developed to include angular distributions of outgoing particles. The random phase approximation used for the compound stage is partially removed for the precompound stages, allowing off-diagonal terms of the collision matrix to produce both odd and even terms in the Legendre polynomial expansion for the angular distribution. Calculated double differential cross sections for the 14.6-MeV $^{23}\text{Na}(n,n'\alpha)$ reaction are compared with experimental data.

* Research sponsored by DOE Office of Basic Energy Sciences.

2.3. NEUTRON EMISSION SPECTRA INDUCED BY 14-MeV NEUTRONS FROM THE EVALUATED NUCLEAR DATA FILE (ENDF/B-V) - A CRITICAL REVIEW*

D. M. Hetrick† D. C. Larson C. Y. Fu

(Abstract of paper in *Nuclear Cross Sections for Technology*, NBS Special Publication 594, p. 765, 1980, and of ORNL/TM-6637, April, 1979)

Neutron emission spectra induced by 14.6-MeV incident neutrons, retrieved from ENDF/B-V, are graphically compared with experimental data by Hermsdorf et al. and Clayeux and Voignier. The elements selected for the comparisons include Na, Mg, Al, Si, Ca, Ti,

V, Cr, Fe, Ni, Cu, Nb, W, and Pb. In addition to comparing the evaluated total neutron emission spectra with experimental data, individually evaluated spectra from contributing reactions are presented. Only a few of the evaluated spectra were found to agree well with the measured spectra; namely, those evaluations which utilized advanced nuclear model codes with precompound effects and competing binary and tertiary reactions. Recommendations for removing several defects in most evaluations are made.

*Research sponsored by DOE Office of Basic Energy Sciences.

†UCC-ND Computer Sciences Division.

2.4. EVALUATION OF PHOTON PRODUCTION DATA FROM NEUTRON-INDUCED REACTIONS*

C. Y. Fu

(Abstract of paper presented at Workshop on Evaluation Methods and Procedures, Brookhaven National Laboratory, Upton, New York, September 22-25, 1980)

The evaluation methods and procedures used for generating the photon production data in the current Evaluated Nuclear Data File (ENDF/B-3, Version V) are reviewed. There are 42 materials in the General Purpose File of ENDF/B-V that contain data for prompt photon production. Almost all evaluations had substantial experimental data bases, but less than half of them employed any of the following evaluation methods. Only a few used theoretical techniques that are sophisticated enough to ensure internal consistency with other particle production data. Comments are made on four evaluation methods: the empirical formalism of Howerton et al., the Troubetzkoy model, the multi-particle Hauser-Feshbach/Precompound model, and the Yost method. Critiques are also made on three procedures used for conserving photon energies in neutron capture reactions. The presence of photon production data in the file is useful for studying energy balance, since photon production generally accounts for a large portion of the reaction energy output. Problems found in energy balance checks are discussed.

*Research sponsored by DOE Office of Basic Energy Sciences.

2.5. EVALUATION OF NEUTRON CROSS SECTIONS FOR FISSION AND FERTILE NUCLIDES IN THE keV RANGE*

L. W. Weston

(Abstract of paper presented at Workshop on Evaluation Methods and Procedures, Brookhaven National Laboratory, Upton, New York, September 22-25, 1980)

Procedures for evaluation of radiative capture, elastic and inelastic processes, and fission in the keV region of neutron energies are described. The use of theoretical tools along with the available ENDF utility codes allows the evaluator to extend and expand upon the experimental data which are often sparse or discrepant. A few problems with the utility codes are noted and suggestions made for improvement and extension. Some ENDF/B-V cross sections for important nuclei are plotted in detail and show significant need for improvement in the shape of the individual partial cross sections to be consistent with theoretical predictions within the constraints of the experimental data. In particular, uranium and plutonium isotopic evaluations, which are of critical importance to fast reactors, deserve careful attention using improved methodology.

*Research sponsored by DOE Office of Reactor Research and Technology.

2.6. EVALUATION OF NEUTRON AND GAMMA-RAY-PRODUCTION CROSS SECTIONS FOR NATURAL IRON (ENDF/B-V MAT 1326)*

C. Y. Fu F. G. Perey

(Abstract of ORNL/TM-7523, in press)

This document deals with the evaluation of neutron and gamma-ray-production cross sections for natural iron. Improvements for ENDF/B-V MAT 1326 are described and graphically compared with the previous version. A summary of the previous version and a general description of the current status of the evaluation are also given.

Research sponsored by DOE Office of Reactor Research and Technology.

2.7. EVALUATION OF RESONANCE PARAMETERS FOR NEUTRON INTERACTION WITH IRON ISOTOPES FOR ENERGIES UP TO 400 keV*

C. M. Perey F. G. Perey

(Abstract of ORNL/TM-6405, September, 1980)

This report documents the evaluation of the resolved resonance parameters of iron isotopes 54, 56, and 57 in the neutron energy region below 400 keV. Estimates of the uncertainties in the resonance parameters and correlation between the partial widths Γ_n and Γ_γ are given when significant. Some details about the procedures used to evaluate the resonance parameters, their uncertainties and correlations are reported. This evaluation was performed for the general purpose file of the Evaluated Nuclear Data File (ENDF/B-V MAT 1326).

* Research sponsored by DOE Office of Basic Energy Sciences.

2.8. SIMULTANEOUS EVALUATION OF $^{32}\text{S}(n,p)$, $^{56}\text{Fe}(n,p)$, $^{65}\text{Cu}(n,2n)$ CROSS SECTIONS*

C. Y. Fu D. M. Hetrick† F. G. Perey

(Abstract of paper in *Nuclear Cross Sections for Technology*, NBS Special Publication 594, p. 63, 1980)

Previously available evaluations of cross sections and covariances were used as input for incorporating additional correlated data sets, particularly cross-section ratios. A generalized least-squares technique was employed. The output evaluations have not only updated cross sections and covariances, but also cross-reaction covariances, all of which include the additional data incorporated.

* Research jointly sponsored by DOE Office of Basic Energy Sciences and by Electric Power Research Institute.

† UCC-ND Computer Sciences Division.

2.9. EVALUATION OF ^{23}Na FOR ENDF/B-V*

D. C. Larson

(Abstract of paper in *Nuclear Cross Sections for Technology*, NBS Special Publication 594, p. 58, 1980)

Version V of the Evaluated Nuclear Data File (ENDF) for sodium is described. Major changes have been made in the total, capture, inelastic scattering and $(n,2n)$ cross sections, as well as the elastic scattering angular distributions and gamma-ray-production

files. ENDF/B-IV and V are compared where major changes were incorporated. New measurements needed to fill data gaps or resolve discrepancies among existing data sets are discussed.

* Research sponsored by DOE Office of Reactor Research and Technology.

2.10. AN EVALUATION OF CROSS SECTIONS FOR NEUTRON-INDUCED REACTIONS IN SODIUM*

D. C. Larson

(Abstract of ORNL-5662, September, 1980)

An evaluation of the neutron-induced cross sections of ^{23}Na has been done for the energy range from 10^{-5} eV to 20 MeV. All significant cross sections are given, including differential cross sections for production of gamma rays. The recommended values are based on experimental data where available and use results of a consistent model code analysis of available data to predict cross sections where there are no experimental data. This report describes the evaluation that was submitted to the Cross Section Evaluation Working Group (CSEWG) for consideration as a part of the Evaluated Nuclear Data File, Version V, and subsequently issued as MAT 1311.

* Research sponsored by DOE Office of Reactor Research and Technology.

2.11. CALCULATION OF THE $^{23}\text{Na}(n,2n)$ CROSS SECTION*

D. C. Larson

(Abstract of paper presented at Meeting of The American Physical Society, Minneapolis, Minnesota, October 9-11, 1980, and of paper to be published in *Nuclear Science and Engineering*)

The $^{23}\text{Na}(n,2n)$ reaction produces the radioactive product ^{22}Na , which has a half-life of 2.61 years. For sodium-containing systems this reaction can result in a radioactive contamination problem. Currently available experimental cross sections for this reaction are in strong conflict. Extensive multi-step Hauser-Feshbach calculations have been done for neutron-induced reactions on sodium and will be presented. These consistent calculations reproduce data for the (n,n') , $(n,p\gamma)$, $(n,\alpha\gamma)$ reactions, a neutron emission measurement and a gamma-ray production measurement. The resulting cross sections for the $(n,2n)$ reaction are found to be in good agreement with one of the experimental data sets (Liskien and Paulson, Nucl. Phys. 63, 393, 1965).

* Research sponsored by DOE Office of Reactor Research and Technology.

2.12. EVALUATION OF THE FISSION AND CAPTURE CROSS SECTIONS OF ^{240}Pu AND ^{241}Pu FOR ENDF/B-V*

L. W. Weston R. Q. Wright†

(Abstract of paper in *Nuclear Cross Sections for Technology*, NBS Special Publication 694, p. 464, 1980)

Since there were appreciable new data which were not available for ENDF/B-IV, new evaluations for ^{240}Pu and ^{241}Pu were carried out for ENDF/B-V. The evaluation of the fission and capture cross sections will be reviewed and problem areas discussed. The neutron energy range of concern was from 10^{-5} eV to 20 MeV. Significant changes were

made over the entire neutron energy region because of the new experimental data available. The problems in the evaluations due to discrepancies in the nuclear data will be emphasized, particularly the 1-eV resonance in ^{240}Pu and the 0.3-eV resonance in ^{241}Pu . The evaluation of the fission and capture cross sections for ENDF/B-V represents an improvement over the previous evaluation; however, there continues to be a need for accurate experimental data.

* Research sponsored by DOE Office of Reactor Research and Technology.

† UCC-ND Computer Sciences Division.

2.13. REVIEW OF MICROSCOPIC NEUTRON CROSS SECTION DATA FOR THE HIGHER PLUTONIUM ISOTOPES IN THE RESONANCE REGION*

L. W. Weston

(Abstract of paper presented at Specialist Meeting on the Nuclear Data of Higher Plutonium and Americium Isotopes for Reactor Applications, Brookhaven National Laboratory, New York, November 20-22, 1978)

The microscopic neutron cross section data for plutonium-240, -241, and -242 in the resonance region are reviewed. In the context of importance to reactors the data on plutonium-240 are acceptable except for the resonance parameters of the 1-eV resonance. Plutonium-241 has discrepancies in the cross sections from thermal to 3 eV and to a lesser extent in the fission and capture cross section in the unresolved resonance region. The plutonium-242 cross sections appear to be known with sufficient accuracy as compared with the other plutonium isotopes.

* Research sponsored by DOE Office of Reactor Research and Technology.

2.14. GLUCS: A GENERALIZED LEAST-SQUARES PROGRAM FOR UPDATING CROSS SECTION EVALUATIONS WITH CORRELATED DATA SETS*

D. M. Hetrick† C. Y. Fu

(Abstract of ORNL/TM-7341, October, 1980)

The PDP-10 FORTRAN IV computer programs INPUT.F4, GLUCS.F4, and OUTPUT.F4, which employ Bayes' theorem (or generalized least-squares) for simultaneous evaluation of reaction cross sections, are described. Evaluations of cross sections and covariances are used as input for incorporating correlated data sets, particularly ratios. These data are read from Evaluated Nuclear Data File (ENDF/B-V) formatted files. Measured data sets, including ratios and absolute and relative cross section data, are read and combined with the input evaluations via the least-squares technique. The resulting output evaluations have not only updated cross sections and covariances, but also cross-reaction covariances. These output data are written into ENDF/B-V format.

* Research jointly sponsored by Electric Power Research Institute and DOE Office of Basic Energy Sciences.

† UCC-ND Computer Sciences Division.

2.15. USER'S GUIDE FOR SAMMY: A COMPUTER MODEL FOR MULTILEVEL R-MATRIX FITS TO NEUTRON DATA USING BAYES' EQUATIONS*

N. M. Larson[†] F. G. Perey

(Abstract of ORNL/TM-7485, November, 1980)

In this report we describe a method for determining the parameters of a model from experimental data based upon the utilization of Bayes' theorem. This method has several advantages over the least-squares method as it is commonly used; one important advantage is that the assumptions under which the parameter values have been determined are more clearly evident than in many results based upon least squares. Bayes' method has been used to develop a computer code which can be utilized to analyze neutron cross-section data by means of the R-matrix theory. The required formulae from the R-matrix theory are presented, and the computer implementation of both Bayes' equations and R-matrix theory is described. Results of our analysis of ⁶⁰Ni transmission data from ORELA and of several artificial data sets, and a comparison of our results with those of an earlier multilevel R-matrix code, are also presented. Finally, details about the computer code and complete input/output information are given.

*Research sponsored by DOE Office of Basic Energy Sciences.

[†]UCC-ND Computer Sciences Division.

2.16. LOGICAL INFERENCE AND EVALUATION*

F. G. Perey

(Abstract of paper presented at Workshop on Evaluation Methods and Procedures, Brookhaven National Laboratory, Upton, New York, September 22-25, 1980)

Most methodologies of evaluation currently used are based upon the theory of statistical inference. It is generally perceived that this theory is not capable of dealing satisfactorily with what are called systematic errors. Theories of logical inference should be capable of treating all of the information available, including that not involving frequency data. A theory of logical inference as an extension of deductive logic via the concept of plausibility and the application of group theory is presented. Some conclusions, based upon the application of this theory to evaluation of data, are also given.

*Research jointly sponsored by DOE Office of Basic Energy Sciences and Office of Reactor Research and Technology.

3. NUCLEAR CROSS-SECTION PROCESSING, TESTING, AND SENSITIVITY ANALYSIS

3.0 INTRODUCTION

The MINX-AMPX multigroup cross-section processing systems, which at the time of our last report had been packaged and released for distribution through the Radiation Shielding Information Center, have been upgraded through the updating of the individual modules to reflect state-of-the-art technology. Currently, the AMPX system, now designated as AMPX-II, consists of 45 computer codes (modules) and it is used routinely to produce specialized cross-section libraries, both alone and when linked with other processing codes. In particular, AMPX is commonly linked with the MINX neutron processing code, in which most of the major processing improvements were implemented: e.g., in the area of resonance reconstruction, linearization, and Doppler broadening; in the treatment of the unresolved resonance region; in the systematic shielding of the scattering transfer matrices, leading to the availability of elastic removal shielding factors required for spectral correction procedures; in the development of transfer coefficients for hybrid group/point-energy discrete ordinates schemes; and in the processing of ENDF/B-V uncertainty files into multigroup covariance matrices.

The Data Library Collection (DLC) of processed and tested multigroup cross sections in the Radiation Shielding Information Center (RSIC) continues to expand, with both fine-group and broad-group cross-section sets being made available to requesters. Among these is VITAMIN-C (DLC-41), a general-purpose fine-group library originally developed within the Division to meet the cross-section needs for fusion reactor and LMFBF neutronics calculations. VITAMIN-C, generated with the MINX-AMPX system and based on ENDF/B-IV data, has now been collapsed into several broad-group libraries generated for special purposes, one being BUGLE-80 (DLC-75), a library which, along with VITAMIN-C itself, has been cited by the American Nuclear Society as a standard for typical LWR and concrete shielding problems. BUGLE-80 contains 47 neutron groups and 20 gamma-ray groups, whereas VITAMIN-C has 171 neutron groups and 36 gamma-ray groups. During this reporting period both of these libraries have been compared in standard problems with several other multigroup libraries, including the EJRLIB-III library developed in Italy (see papers 3.5 and 3.12).

The first phase of the update of VITAMIN-C, denoted as VITAMIN-E and based on ENDF/B-V data, has also become available during this reporting period and has been tested against CSEWG benchmarks (CSEWG = Cross Section Evaluation Working Group). This library, which has 174 neutron groups and 37 gamma-ray groups, is expected to have a broad range of applicability in transport calculations for fission reactors (LWR and LMFBF), and in fusion and weapons radiation research, as well as in the analysis of foreign reactors and in benchmark validation.

Also during this reporting period the Division fulfilled its responsibility for testing the quality of ENDF/B cross sections prior to the release of ENDF/B-V. Our data testing activities will continue, with the chairmanship of the Data Testing and Applications Committee of the newly reorganized CSEWG residing in the Division. An important facet of this program is establishing benchmark problems based on tests of the cross-section data against integral experiments, whose specifications include covariance files that are so essential to any credible uncertainty analysis.

Multigroup sensitivity profiles and covariances matrices for group cross sections and for fission spectrum parameters are now a part of RSIC's Data Library Collection, with several sets available for fast- and thermal-reactor benchmarks and for fast-reactor shielding benchmarks. Sensitivity profiles derived from a preanalysis of an ORNL fusion integral experiment are also available. In addition, covariance files have been developed for several weighted flux spectra in standard neutron field facilities.

The ORNL FORSS sensitivity and uncertainty analysis system, a collection of code systems and stand-alone codes that was featured in a 1978 RSIC Workshop, has now been documented and packaged for distribution through RSIC. As has been reported previously, this system includes cross-section processing, uncertainty file processing, neutronics calculations, source calculations, sensitivity profile generation, uncertainty analysis, data adjustment, and estimation of accuracy requirements for nuclear data to meet predetermined design constraints and error margins. Much, but not all, of the FORSS methodology is under a single driver. Development of the FORSS system continues as it is being applied to increasingly more complicated systems. Included among major developments in

sensitivity theory are treatment of responses that are functions (time-dependent and space-dependent); of nonlinear, multidimensional systems; and of certain types of discontinuous functions and parameters. The sensitivity-analysis system also can now handle responses in multidimensional time-dependent systems that include burnup, depletion, etc.

The cross-section adjustment feature of FORSS — the UNCOVER module — has recently been used to generate the Oak Ridge adjusted cross-section and covariance library (ORACLE). Based on ENDF/B-V data (as embodied in the VITAMIN-E library) and information from fast reactor and dosimetry integral experiments, the library was developed by combining the data from 27 integral experiments with the ENDF/B-V data in a least-squares data adjustment.

One of the major recent applications of sensitivity and uncertainty analysis has been the estimation of the uncertainty in the breeding ratio of a large LMFBR. Others include an extensive analysis of the Coupled Fast Reactivity Measurement Facility (CFRMF) and the design and sensitivity analysis of a CDS-type LMFBR Heterogeneous Core.

During this reporting period the FORSS system has also been applied to the development of an advanced methodology for the determination of LWR pressure vessel damage. Recent work considers the inclusion of the ORNL Pool Critical Assembly (PCA) benchmark. Bias factors for group fluxes, sensitivities of the flux to the fission spectrum and structural material cross sections, ENDF/B-V based cross sections and covariance matrices, and new fission spectrum covariance matrices are being employed.

Sensitivity theory is also being extended into new areas such as thermal hydraulics, reactor depletion, and multiconstraint and extrema problems. An advanced uncertainty analysis methodology for transient nonlinear systems was developed and successfully applied to the analysis of a blowdown thermal hydraulics problem. With this methodology a significant reduction in the uncertainties of the time-dependent system parameters and responses was achieved for the first time, a task deemed impossible with previous approaches mainly based on response-surface techniques.

A FORSS analysis of the National Bureau of Standards Intermediate Energy Standard Neutron Field (NBS-ISNF) was performed to obtain the most likely estimates of the NBS-ISNF flux spectrum and several dosimetry cross sections, as well as their covariances based on several integral experiments. In summary, there appears to be a large potential for applying sensitivity theory in many areas, including non-neutronic areas (see Section 7), and the Division is expected to play a leading role in programs of this type.

CROSS-SECTION PROCESSING AND TESTING

3.1. VITAMIN-C: THE CTR PROCESSED MULTIGROUP CROSS-SECTION LIBRARY FOR NEUTRONICS STUDIES*

R. W. Roussin C. R. Weisbin J. E. White[†] N. M. Greene[†]
 R. Q. Wright[†] J. B. Wright

(Abstract of ORNL/RSIC-37, July, 1980)

The program for the development, generation, validation and distribution of a general purpose Processed Multigroup Cross Section Library (PMCSL) for use in controlled thermonuclear research (CTR) neutronics studies is described. In 1979, the Radiation Shielding Information Center (RSIC) coordinated an effort to establish the CTR-PMCSL based on input requirements specified by the Energy Research and Development Administration [ERDA, now Department of Energy (DOE)] DCTR (now Office of Fusion Research) contractors. By collaborating with the ORNL Engineering Physics Division Shielding Analysis and Reactor Physics Group [which had a similar mission for the ERDA Division of Reactor Demonstration and Development (DRDD) community] it was possible to define a single 171 neutron, 36 gamma-ray group cross-section library useful for both CTR and LMFBR neutronics analysis. The master library was generated using the MINX neutron processor and the gamma-ray processor from the AMPX system. Preliminary release of the library was made to a group of ERDA contractors in AMPX and CCCC interface forms, along with appropriate retrieval and manipulation programs. Results of initial testing of the library at ORNL are described. The preliminary release was intended to stimulate implementation and testing at several installations for the purpose of improving the quality of the libraries which ultimately received general distribution under the designation DLC-41/VITAMIN-C and DLC-53/VITAMIN-4C. The successful application of VITAMIN-C as a general purpose fine-group master library has resulted in its designation by the ANS 6.1.2 Working Group on Shielding Cross Sections as an Averaged Data Set conforming to that group's "Proposed Standard on Neutron and Gamma-Ray Cross Sections for Nuclear Radiation Protection Calculations."

*Research sponsored jointly by the Department of Energy, the Nuclear Regulatory Commission under Interagency Agreement DOE No. 40-548-75, and the Defense Nuclear Agency under Interagency Agreement DOE No. 40-46-64.

[†]UCC-ND Computer Sciences Division.

3.2. VITAMIN-E: AN ENDF/B-V MULTIGROUP CROSS-SECTION LIBRARY FOR LMFBR CORE AND SHIELD, LWR SHIELD, DOSIMETRY AND FUSION BLANKET TECHNOLOGY*

C. R. Weisbin R. W. Roussin J. J. Wagschal[†]
 J. E. White[†] R. Q. Wright[†]

(Abstract of ORNL-5505, February, 1979)

The Department of Energy (DOE) Office of Fusion Energy (OFE) and the Division of Reactor Research and Technology (DRRT) jointly sponsored the development of a coupled fine-group cross section library. This 171-neutron, 36-gamma-ray group library was based upon ENDF/B-IV and was intended to be applicable to fusion reactor neutronics and LMFBR core and shield analysis. Versions of the library are available from the Radiation Shielding Information Center (RSIC) at the Oak Ridge National Laboratory in both AMPX and CCCC formats. Computer codes for energy group collapsing, interpolation on Bondarenko factors for resonance self-shielding and temperature corrections, and various other useful data manipulations are also available.

The experience gained in the generation, validation and utilization of this library along with its broad range of applicability has led to the request for updating this data set using ENDF/B-V. Additional support in this regard has been provided by the Defense Nuclear Agency (DNA) and by the Electric Power Research Institute (EPRI) in support of weapons analyses and light water reactor shielding and dosimetry problems, respectively.

The purpose of this report is to provide detailed specifications and rationale for the proposed ENDF/B-V update (designated VITAMIN-E) to the VITAMIN-C library.

* Research jointly sponsored by DOE Office of Fusion Energy, DOE Office of Reactor Research and Technology, the Defense Nuclear Agency, and the Electric Power Research Institute.

† On leave from The Hebrew University, Jerusalem, Israel.

‡ UCC-ND Computer Sciences Division.

3.3. VITAMIN E: A MULTIPURPOSE ENDF/B-V COUPLED NEUTRON-GAMMA CROSS SECTION LIBRARY*

J. Barhen D. G. Cacuci W. E. Ford, III[†] R. W. Roussin,
J. J. Magschal[‡] C. R. Weisbin J. E. White[†] R. Q. Wright[†]

*(Abstract of paper in Nuclear Cross Sections for Technology,
NBS Special Publication 594, p. 204, 1980)*

The U.S. Department of Energy (DOE) Office of Fusion Energy (OFE) and the Division of Reactor Research and Technology (DRRT) jointly sponsored the development of a coupled fine-group cross section library (VITAMIN-C). The experience gained in the generation, validation and utilization of the VITAMIN-C library along with its broad range of applicability has led to the request for updating this data set using ENDF/B-V. Additional support in this regard has been provided by the Defense Nuclear Agency (DNA) and by EPRI in support of weapons analyses and light water reactor shielding and dosimetry problems, respectively. The rationale for developing the multipurpose ENDF/B-V based VITAMIN-E library is presented, with special emphasis on new models used in the data generation algorithms. The library specifications and testing procedures are also discussed in detail. The distribution of the VITAMIN-E library is currently subject to the same restrictions as the distribution of the ENDF/B-V data.

* Research jointly sponsored by DOE Office of Fusion Energy, DOE Office of Reactor Research and Technology, the Defense Nuclear Agency, and the Electric Power Research Institute.

† UCC-ND Computer Sciences Division.

‡ On leave from The Hebrew University, Jerusalem, Israel.

3.4. A NEW CROSS SECTION LIBRARY FOR LIGHT WATER REACTOR SHIELDING AND PRESSURE VESSEL DOSIMETRY APPLICATIONS*

G. L. Simmons[†] R. W. Roussin

(Abstract of paper presented at ANS Topical Meeting, Advances in Reactor Physics and Shielding, Sun Valley, Idaho, September 14-17, 1980)

A new cross-section library for use in shielding and pressure vessel dosimetry applications is described. This library is generated from a fine-group library from ENDF/B-IV data and contains detailed treatment of resonance self-shielding and temperature effects. It contains 47 neutron and 20 gamma-ray groups with a P_3 Legendre expansion of the scattering angular distribution. Extensive comparisons have been made between this new library and previously used data sets. Both libraries are available from the Radiation Shielding Information Center at Oak Ridge, Tennessee.

* Research sponsored by the Electric Power Research Institute.

† Science Applications, Inc., La Jolla, CA.

3.5. A COMPARISON OF THE USE OF EURLIB-III AND OTHER MULTIGROUP CROSS-SECTION LIBRARIES FOR A 1 meter CONCRETE SLAB PROBLEM*

M. Metghalchi[†] R. W. Roussin J. T. West B. Nakbati[‡]

(Reprint of ESIS Newsletter No. 31, October, 1979)

EURLIB, a 100 neutron and 20 gamma group cross-section library, was constructed with the collaboration of European scientists at the University of Stuttgart, Germany and Ispra, Italy.¹ EURLIB-III is the version of EURLIB now available in RSIC.² The ENDF/B-IV and the AMPX code system were used in the construction of EURLIB-III.^{3,4} During the last few years this library has been commonly used in European research centers and there are some published reports stating "the shielding library EURLIB has proved a valuable method for common evaluation of different benchmark experiments, which on the other hand, provide the best check for the group cross section."^{5,6}

So, it was interesting to see what would be the difference between EURLIB and some American libraries in a special shielding calculation. In fulfillment of this idea the neutron and secondary gamma-ray spectrum through 1 meter of ordinary concrete, using EURLIB-III and five other libraries available in RSIC have been calculated. These multi-group cross-section libraries are CASK,⁷ FEWGL,⁸ VITAMIN-C,⁹ BUGLE,¹⁰ and EPR.¹¹

CASK is a 22 neutron and 18 gamma group library which has received widespread use throughout industry. FEWGL is a 37 neutron and 21 gamma group library and was developed for the United States Defense Nuclear Agency contractors. VITAMIN-C is a 171 neutron and 36 gamma group library and was developed for the breeder reactor and also fusion neutronics communities. BUGLE, a 46 neutron and 16 gamma group was collapsed from VITAMIN-C at ORNL. Finally, EPR is a 100 neutron and 21 gamma group library and was generated for use in neutronic calculations for conceptual designs of the Experimental Power Reactor (EPR) and other fusion-reactor models.

The problem was modeled as a mono-directional unit source normal to the surface of a 1-meter thick slab of ordinary concrete, type 04.¹² The transport calculation was performed using ANISN¹³ with an S_8 angular quadrature, or P_3 Legendre expansion of the scattering matrix and 1 cm intervals. The source spectrum were A: a watt fission spectrum; B: case A which connected at 10 MeV to a Gaussian fusion spectrum. Dose rates were calculated through the slab by means of the ANS standard of flux-to-dose response functions,¹⁴ using the AMPX-II code system module DOSE.

Results of these calculations are summarized in Tables 3.5.1 and 3.5.2. The neutron dose (Table 3.5.1) at the exit face of the slab has a rather large component due to thermal neutrons. Since the various libraries may have different treatment in the thermal range (for example, EPR has thermal group cross sections in 800°K), Table 3.5.1 also shows the neutron dose due to neutrons with energies above thermal (0.414 eV). Here we see that the various libraries are in reasonable agreement with EURLIB giving the lowest result and VITAMIN-C the highest. The EURLIB results are near the other library with 100 neutron groups, EPR, as might be expected. Spectral results for EURLIB-III and EPR, shown in Figs. 3.5.1-3.5.4 confirm the consistency expected for the two 100 group libraries. The differences in non-thermal neutron dose between EURLIB-III and VITAMIN-C are due to higher calculated spectral results obtained using the fine group (171 neutron) library. Comparative plots of EURLIB-III and VITAMIN-C results are shown in Figs. 3.5.5-3.5.8.

Gamma-ray dose rates, summarized in Table 3.5.2, show large variations among the various libraries. These are influenced strongly by the thermal neutron flux results in a non-trivial way and no attempt has been made to separate gamma-ray dose into components from thermal and non-thermal neutrons.

Table 3.5.1. Comparison of Neutron Dose Rates at the Exit Face of a 1 meter Ordinary Concrete Slab Calculated with Various Multigroup Libraries

LIBRARIES	PER CENT OF DEVIATION FROM EURLIB-III			
	FISSION SOURCE		FISSION + FUSION SOURCE	
	Epithermal and fast neutrons	Thermal, epithermal and fast neutrons	Epithermal and fast neutrons	Thermal, epithermal and fast neutrons
VITAMIN-C (171 n, 36 g)	+ 19.01	+ 5.2	+ 19.1	+ 14.7
EPR (100 n, 21 g)	+ 2.0	+ 29.7	+ 3.0	+ 13.9
BUGLE (45 n, 16 g)	+ 3.3	- 6.6	+ 0.8	+ 12.9
FEWG1 (37 n, 21 g)	+ 3.0	- 11.5	+ 7.0	+ 2.1
CASK (22 n, 18 g)	+ 1.2	- 13.3	+ 16.3	- 4.9

Table 3.5.2. Comparison of Gamma-Ray Dose Rate at the Exit Face of a 1 Meter Concrete Slab Calculated with Various Multigroup Libraries

LIBRARIES	Per cent of deviation from EURLIB-III	
	Fission source	Fission + fusion source
VITAMIN-C (171 n, 36 g)	+ 20.5	+ 25.0
EPR (100 n, 21 g)	+ 46.0	+ 38.5
BUGLE (45 n, 16 g)	+ 23.6	+ 28.9
FEWG1 (37 n, 21 g)	+ 13.5	+ 19.9
CASK (22 n, 18 g)	+ 30.4	+ 28.5

Fig. 3.5.1. Comparison of Neutron Spectrum Calculational Results for the Epithermal Energy Region Using EURLIB-III and EPR (Fission Source).

Fig. 3.5.2. Comparison of Neutron Spectrum Calculational Results for the Fast Energy Region Using EURLIB-III (Fission Source).

Fig. 3.5.3. Comparison of Neutron Spectrum Calculational Results for the Epithermal Energy Region Using EURLIB-III and EPR (Fission Plus Fusion Source).

Fig. 3.5.4. Comparison of Neutron Spectrum Calculational Results for the Fast Energy Region Using EURLIB-III and EPR (Fission Plus Fusion Source).

Fig. 3.5.5. Comparison of Neutron Spectrum Calculational Results for the Epithermal Energy Region Using EURLIB-III and VITAMIN-C (Fission Source).

Fig. 3.5.6. Comparison of Neutron Spectrum Calculational Results for the Fast Energy Region Using EURLIB-III and VITAMIN-C (Fission Source).

Fig. 3.5.7. Comparison of Neutron Spectrum Calculation Results for the Epithermal Energy Region Using EURLIB-III and VITAMIN-C (Fission Plus Fusion Source).

Fig. 3.5.8. Comparison of Neutron Spectrum Calculation Results for the Fast Energy Region Using EURLIB-III and VITAMIN-C (Fission Plus Fusion Source).

* U.S. work funded by DOE Office of Reactor Research and Technology.

† Atomic Energy Organization of Iran, Tehran.

‡ University of Tennessee.

1. G. Gonano, G. Hehn, M. Mattes, R. Nicks, and H. Rief, "Standard Neutron Energy Group Structure for Shielding Benchmark Experiments," ESIS Newsletter, Ispra, No. 12, January 1975.
2. "EURLIB, 100 Group Neutron Cross-Section Library, for Use in the European Shielding Benchmark Program," available as RSIC Data Library Collection, DLC-358/EURLIB-III.
3. G. Hehn, "Experience with the Group Cross-Section Library EURLIB and Updating to ENDF/B-IV," Proceedings of the Specialist Meeting on Sensitivity Studies and Shielding Benchmarks, Paris, 1975.
4. E. Caglioti, G. Gonano, G. Hehn, Mattes, R. Nicks, H. Penkuhn and H. Rief, "The Development of the Coupled Shielding Standard Library EURLIB-III," ESIS Newsletter, Ispra, No. 19, Oct. 1976.
5. E. Caglioti, G. Hehn, V. Hernberger, M. Mattes, R. Nicks, and H. Penkuhn, "Generation and Testing of the Shielding Data Library EURLIB for Fission and Fusion Technology," Proceedings of 5th International Conference on Reactor Shielding, April 1977, Knoxville, TN, U.S.A., pp. 482.
6. C. McCombie, G. Gmur, M. Jermann, R. Richmond, U. Schmocker, and S. Seth, "Benchmark Shielding Experiments for Testing Iron and Steel Data," Proceedings of an American Nuclear Society Topical Meeting, Gatlinburg, TN, U.S.A., April 10-12, 1978.
7. "CASK 40 Grouped Coupled Neutron and Gamma-Ray Cross-Section Data," (1973), available as DLC-23E/CASK from the Radiation Shielding Information Center, ORNL.
8. D. E. Bartine, J. R. Knight, J. V. Pace, III, and R. W. Roussin, "Production and Testing of the WNA Few-Group Coupled Neutron-Gamma Cross-Section Library," ORNL/TM-4840 (March 1977). Also available as DLC-31/(DPL-1F/FEWG1) from the Radiation Shielding Information Center, ORNL.

9. R. W. Roussin, C. R. Weisbin, J. E. White, N. M. Greene, R. Q. Wright, and J. B. Wright, "The CTR Processed Multigroup Cross-Section Library for Neutron Studies," ORNL/RSIC-37 (1975). Also available as DLC-41/VITAMIN-C from the Radiation Shielding Information Center, ORNL.
10. "BUGLE: Coupled 45 Neutron, 16 Gamma-Ray, P_5 , Cross-Sections for Studies by the ANS 6.1.2 Shielding Standards Working Group on Multigroup Cross-Sections," R. W. Roussin, informal memo (1977). Available as DLC-47/BUGLE from the Radiation Shielding Information Center, ORNL.
11. W. E. Ford, III, R. T. Santoro, R. W. Roussin, and D. M. Plaster, "Modification Number One to the 100n-21y Cross-Section Library," ORNL/TM-5249 (March 1976). Also available as DLC-37D/EPR from the Radiation Shielding Information Center, ORNL.
12. J. C. Celnik, "Specifications for Power Reactor Shielding Benchmark Problems," ANS 6.2 Informal notes (Nov. 17, 1976).
13. W. W. Engle, Jr., "ANISN, A One-Dimensional Discrete Ordinates Transport Code with Anisotropic Scattering," K-1693, ORNL (1976).
14. "American National Standard, Neutron and Gamma-Ray Flux-to-Dose Rate Factors," ANSI/ANS-6.1.1, 1977.

3.6. SAMPLE PROBLEMS FOR THE NOVICE USER OF THE AMPX-II SYSTEM*

W. E. Ford, III[†] R. W. Roussin M. Petrie[†]
 B. R. Diggs[†] H. E. Comolander

(Abstract of ORNL/CSD/TM-72, January 1979)

Contents of the IBM version of the AMPX system distribution by the Radiation Shielding Information Center (AMPX-II) are described. Sample problems which demonstrate the procedure for implementing AMPX-II modules to 1) generate point cross sections; 2) generate multigroup neutron, photon production, and photon interaction cross sections for various transport codes; 3) collapse multigroup cross sections; 4) check, edit, and punch multigroup cross sections; and 5) execute a one-dimensional discrete ordinates transport calculation are detailed.

*Work supported by the Defense Nuclear Agency under Subtask No. V99QAXNA010.

[†]UCC-ND Computer Sciences Division.

3.7. NUCLEAR DATA AND BENCHMARKS FOR REACTOR SHIELDING (MEETING PAPERS)*

(Abstracts of two papers presented at Specialists' Meeting on Nuclear Data and Benchmarks for Reactor Shielding, OECD Headquarters, Paris, France, October 27-29, 1980)

Status of Multigroup Cross-Section Libraries Available from the Radiation Shielding Information Center (R. W. Roussin, D. K. Trubey, and B. F. Maskewitz)

Multigroup cross-section libraries for shielding applications in formats for direct use in discrete ordinates codes have long been a part of the Radiation Shielding Information Center's (RSIC) Data Library Collection (DLC). In recent years libraries in more flexible and comprehensive formats which allow the user to derive his own problem-dependent sets have been added to the collection. The current status of both types is described as well as projections for adding data libraries based on ENDF/B-V.

Status of Multigroup Sensitivity Profiles and Covariance Matrices Available from the Radiation Shielding Information Center (R. W. Roussin, J. D. Drischler, and J. H. Marable)[†]

In recent years multigroup sensitivity profiles and covariance matrices have been added to the Radiation Shielding Information Center's Data Library Collection (DLC). Sensitivity profiles are available in a single package. DLC-45/SENPRO, and covariance matrices are found in two packages, DLC-44/COVERX and DLC-77/COVERV. The contents of these packages are described and their availability is discussed.

*Work funded by the U.S. Nuclear Regulatory Commission, Defense Nuclear Agency, DOE Office of Reactor Research and Technology, DOE Office of Fusion Energy, and the Electric Power Research Institute.

[†]See also paper 3.19.

3.8. DETERMINATION OF CURRENT-WEIGHTED TOTAL CROSS SECTIONS IN THE UNRESOLVED ENERGY REGION*

J. Barhen D. G. Cacuci

(Reprint of Trans. Am. Nucl. Soc. 32, 310, 1979)

As part of the preliminary ENDF/B-V data testing, recommendations were made by General Electric¹ to reassess the computation of the effective pointwise current-weighted cross sections in the unresolved energy region. Programs based on the shielding factor method (e.g., ETOX,² ENDRUN,³ MINX,⁴ NJOY⁵) require these data for generating multigroup constants (diffusion coefficients and shielded scattering matrices⁶) used in design codes. This type of cross section was either not dealt with in previous publications,^{7,8} or the treatments proposed for their computation^{2,3,9} involved approximations to such important effects as interference scattering¹⁰ and within sequence overlap, many of which could be avoided. In addition, the extension of the unresolved energy region to higher energies in ENDF/B-V, to include competitive widths, increases the computational complexity. Because of the potential cost penalties associated with design uncertainties¹¹ in large LMFBRs, it was necessary to develop a procedure that takes these effects fully into account. The new methodology presented here is to be used at ORNL in the generation of multigroup libraries based on the final version of ENDF/B-V.

The effective pointwise total cross section, function of the temperature T and the Bondarenko parameter σ_B , is defined as

$$\sigma_{t,n}(E^*, \sigma_B, T) = \frac{\frac{1}{E_H - E_L} \int_{E_L}^{E_H} \frac{dE}{|\sigma_B + \sigma_n(E, T)|^n}}{\frac{1}{E_H - E_L} \int_{E_L}^{E_H} \frac{dE}{|\sigma_B + \sigma_n(E, T)|^{n+1}}} \sigma_B \quad (1)$$

with $n = 0$ or 1 corresponding to flux or current weighting, respectively: E^* denotes the energy point, contained in the interval $[E_L, E_H]$, at which average resonance parameters are specified. Our procedure is based on the transformation

$$\sigma_B + \sigma_n(E, T) = \sigma_p + \sum_{\lambda} x_{\lambda}(E, T) \quad (2)$$

where x_{λ} refers to resonance component λ (i.e., resonance i in sequence ν) of the total cross section, expressed in terms of the usual symmetric and antisymmetric line shape functions

$$x_{\lambda} = \sigma_0 \lambda (\psi_{\lambda} + \epsilon \lambda \chi_{\lambda}) \quad (3)$$

According to the ENDF specifications, the effective potential cross section σ_p includes the smooth corrections contribution (σ_{F3}) from scattering, fission (if relevant), and capture, but not from the competitive reaction

$$\sigma_p = \sigma_{p0}(E^*) + \sigma_{F3}(E^*) + \sigma_B \quad (4)$$

To evaluate the integrals in Eq. (1), the identity

$$\frac{1}{(\sigma_B + \sigma_p(E,T))^n} = \frac{1}{\sigma_p^n} \left[1 - \sum_{\lambda} \frac{x_{\lambda}}{\sigma_p + \sum_{\mu} x_{\mu}} \right]^n$$

is used. In expanding the right-hand side (RHS) of Eq. (5), contributions of resonances in the same and in different sequences are separated. Consistent with the use of a two-level long-range correlation,¹² terms of the form

$$\frac{x_j^i}{\sigma_p + x_j^i} \sum_{j \in \alpha} \frac{x_j^i}{\sigma_p + x_j^i + x_k^j} \sum_{k \in \beta} \frac{x_k^j}{\sigma_p + \sum_{\mu} x_{\mu}}$$

are ignored; furthermore, only first-order sequence-sequence overlap contributions are retained.

Sophisticated techniques have been developed by Hwang⁷ and implemented in the MC²-2 code⁸ for computing flux-weighted pointwise cross sections. However, since MC²-2 does not use the shielding factor method, current-weighted effective pointwise cross sections were not treated. An efficient numerical evaluation of $\bar{\sigma}_{t,1}$ should rely, in part, on these techniques. Integration over energy and statistical averaging over the distributions of partial widths yields

$$\bar{\sigma}_{t,1}(E^*, \rho_B, T) = \sigma_p \frac{1 - \bar{A}}{1 - 3\bar{A} + \bar{B}} - \sigma_B \quad (6)$$

where

$$\bar{A} = \sum_{\nu} \left[\frac{(\sigma_{p\nu})}{(D_{\nu})} - (O_{\nu}) \right] \cdot \left\{ 1 - \sum_{\nu' \neq \nu} \left[\frac{(\sigma_{p\nu'})}{(D_{\nu'})} - (O_{\nu'}) \right] \right\} \quad (7)$$

and

$$\bar{B} = \sum_{\nu} \left[\frac{(\sigma_{p\nu})}{(D_{\nu})} + \frac{(\sigma_{p\nu})}{(D_{\nu})} \right] \quad (8)$$

J_{ν} and O_{ν} denote, respectively, the generalized J-integral⁷ and the within-sequence overlap term. The new and more complicated integrals J_{ν}^* appearing in the expression of $\bar{\sigma}_{t,1}$ are evaluated using either asymptotic expansions

$$J_{\nu,i}^* \approx \frac{1}{\beta_{\lambda}^2} \left\{ \frac{\pi}{2} (1 + 4a_{\lambda}^2) \psi(\sqrt{2} \Theta_{\lambda,0}) - \frac{2}{\beta_{\lambda}} (1 + a_{\lambda}^2) \left[\int_0^{\infty} \psi_{\lambda}^i d\eta \right]_{\text{ass}} \right\} \quad (9)$$

or Gauss-Jacobi quadratures⁷ for

$$J_{\nu,i}^* \approx \frac{1}{2} \int_{-1}^1 \frac{\psi_{\lambda}^i (\beta_{\lambda}^2 + \psi_{\lambda}^2) + a_{\lambda}^2 x_{\lambda}^i (\beta_{\lambda}^2 + a_{\lambda}^2 x_{\lambda}^2) + 2\beta_{\lambda} \psi_{\lambda} (\psi_{\lambda}^2 - a_{\lambda}^2 x_{\lambda}^2) - 2\psi_{\lambda}^2 a_{\lambda}^2 x_{\lambda}^2}{(1\beta_{\lambda} + \psi_{\lambda})^2 - a_{\lambda}^2 x_{\lambda}^2} d\eta \quad (10)$$

Finally, the group-averaged current-weighted total cross section is given by¹³

$$\sigma_{t,1}^g(\sigma_B, T) = \frac{\int_E C(E^*) \frac{\sigma_{t,1}(E^*, \sigma_B, T)}{\sigma_B + \sigma_{t,1}(E^*, \sigma_B, T)} \frac{dE^*}{\sigma_B + \sigma_{t,1}(E^*, \sigma_B, T)}}{\int_E C(E^*) \frac{1}{\sigma_B + \sigma_{t,1}(E^*, \sigma_B, T)} \frac{dE^*}{\sigma_B + \sigma_{t,1}(E^*, \sigma_B, T)}} \quad (11)$$

where $C(E^*)$ represents the slowly varying broad energy behavior of the flux.

The methodology described above has been implemented in the MINX code. Flux- and current-weighted shielding factors were processed, from preliminary ENDF/B-V data, over a wide range of temperatures and σ_B 's for various degrees of sophistication in the computational model. Important conclusions from this study include:

1. Nonphysical effects, observed⁶ in existing procedures at infinite dilution [i.e., $\sigma_{t,1}^g \neq \sigma_{t,0}^g$], were eliminated with the new treatment.

2. Significant differences in the computed data due to various contributing effects and/or to different processing methods were found for important fast breeder materials such as ²³⁸U and ²³⁹Pu. In particular, the effect of within-sequence overlap, which increases with energy, can account for a 2% change of $\sigma_{t,1}^g$ in ²³⁸U and a 5% change in ²³⁹Pu. A specific case is illustrated in Table 3.8.1.

3. The inclusion of competitive widths is significant. Pointwise differences as high as 11% were observed in the infinitely dilute current-weighted cross sections between the standard⁴ and the modified versions of MINX. The magnitude of the effect is much smaller ($\approx 5\%$) for the group averaged cross sections.

Table 3.8.1. Relative Differences in Processed Effective Pointwise Current-Weighted Total Cross Sections Using Various Computational Models (²³⁸U, ENDF/B-V, T=300, $\sigma_B=1$)

Energy Range	Methods	
	A - C	B - C
3.354 10 ³ ev - 5.531 10 ³ ev	0.112	0.0002
5.531 10 ³ ev - 9.118 10 ³ ev	0.104	0.0002
9.118 10 ³ ev - 1.503 10 ⁴ ev	0.089	0.002
1.503 10 ⁴ ev - 2.478 10 ⁴ ev	0.080	0.005
2.478 10 ⁴ ev - 4.086 10 ⁴ ev	0.060	0.007
4.086 10 ⁴ ev - 6.738 10 ⁴ ev	0.040	0.007
6.738 10 ⁴ ev - 1.111 10 ⁵ ev	0.008 ^a	0.011
1.111 10 ⁵ ev - 1.832 10 ⁵ ev	-0.043	0.023

(A) "Standard" MINX⁴ or NJOY⁵: Includes sequence-sequence overlap only.

(B) Updated MINX: Sequence-sequence overlap and interference scattering.

(C) Updated MINX: Interference scattering, sequence-sequence, and within-sequence overlap.

^aSome cancellation effects occur.

*Research sponsored by DOE Office of Reactor Research and Technology.

1. Meeting of the Processing Code Subcommittee of the CCWG, Germantown, MD (November 2-3, 1977).
2. R. E. Schenter et al., BNWL-1002 (1969).
3. B. A. Hutchins et al., GEAP-13592 (1970).
4. C. P. Weisbin et al., LA-6486-MS, ENDF-237 (1976).
5. R. E. MacFarlane et al., LA-7584-MS (1976).
6. C. R. Weisbin, Letter to CSEWG-CEWG (January 17, 1979).
7. R. N. Hwang, Nucl. Sci. Eng., 52, 157 (1973).
8. H. Henryson, II, et al., ANL-8144 (1976).

9. R. B. Kidman et al., Nucl. Sci. Eng., 48, 189 (1972).
10. E. Kujawski, GEAP-14073-2 (1976).
11. J. H. Marable et al., Proc. AMS Topical Meeting, CONF-780401 (1978).
12. F. J. Dyson, J. Math. Phys., 3, 1966 (1962).
13. D. G. Cacuci, ORNL Intralaboratory Correspondence (September 1978).

3.9. COMPUTATION OF ANALYTICAL BOUNDS FOR CROSS-SECTION SELF-SHIELDING FACTORS*

J. Barhen D. G. Cacuci

(Reprint of Trans. Am. Nucl. Soc., 33, 351, 1979)

The shielding factor method (SFM) is a frequently used economical procedure for computing the effective multigroup cross sections needed in reactor analysis. While initially developed and employed in codes used by the fast reactor community,¹⁻⁴ the method has been receiving increased attention in recent years from the electric utility industry for applications to power reactors.⁴⁻⁶ A fundamental problem regarding the method's applicability is to determine the limits of the range of values within which a cross-section shielding factor is restricted, and whether these limits are physically meaningful. In a previous paper⁷ strict upper and lower bounds for the transport f-factor and for the sum of reaction f-factors were derived and discussed. The purpose of the present work is to present extensions of the methodology of Ref. 7.

Strict upper and lower bounds for individual reaction f-factors have now been derived, allowing for cross-section discontinuities (e.g., between the resolved and unresolved regions). The resulting expressions were coded in BRINE, a stand-alone module easily incorporable into existing SFM cross-section processors. BRINE will be used to check the shielding factors in the multipurpose ENDF/B-V-based VITAMIN-E library,⁸ now under production at ORNL.

The computation of analytical bounds for the self-shielding factors involves separate treatments of the resolved and unresolved regions, since the corresponding cross-section representations differ. Moreover, particular care is required in handling those groups where cross-section discontinuities, allowed by the ENDF specifications,⁹ occur. For illustrative purposes, the methodology for deriving a strict upper bound for a flux-weighted reaction f-factor in the resolved resonance region will now be presented. Complete results covering all possible cases are summarized in Table 3.9.1.

The reaction self-shielding factor $f_G^{x,r}(\sigma_B, T)$ is defined¹⁻³ as

$$f_G^{x,r}(\sigma_B, T) = \frac{I_G[C(E)]}{I_G[C(E)\sigma_x^r(E,0)]} \times I_G \left[\frac{C(E)\sigma_x^r(E,T)}{\sigma_B + \sigma_t^r(E,T)} \right] \bigg/ I_G \left[\frac{C(E)}{\sigma_B + \sigma_t^r(E,T)} \right] \quad (1)$$

$C(E)$ represents the slowly varying broad energy behavior of the flux. The symbol I_G denotes integration over energy, in group G . The various definite integrals involved are clearly finite. The Diaz-Goldmann-Metcalf inequality,¹⁰ applied to a pair of positive real-valued functions g and h defined on G , gives

$$I_G[g^2] \cdot I_G[h^2] \leq (I_G[g \cdot h])^2 \cdot \left[\frac{1}{2} + \frac{1}{4} \left(B^2 + \frac{1}{B^2} \right) \right], \quad (2)$$

Table 3.9.1. Summary of Analytical Bounds Satisfied by the Cross Section of Self Shielding Factors

Shielding Factor Type	Resolved Region or Smith Cross Sections	Unresolved Region Cross Sections	Group Constant k Cross Section Boundary, e.g., The Known/Unresolved Boundary
Reaction Fluor-weighted	$U.B. = [N_G^{A,r}]^2 A_G^{A,r}$	$U.B. = [N_G^{A,u}]^2 A_G^{A,u}$	$U.B. = [N_G^A]^2 A_G^A$
	$L.B. = \frac{1}{[N_G^{A,r}]^2} A_G^{A,r}$	$L.B. = \frac{1}{[N_G^{A,u}]^2} A_G^{A,u}$	$L.B. = \frac{1}{[N_G^A]^2} A_G^A$
	$A_G^{A,r} = \frac{I_G[C(E)^r(E,T)]}{I_G[C(E)^r(E,0)]}$	$A_G^{A,u} = \frac{I_G[C(E)^u(E,T)]}{I_G[C(E)^u(E,0)]}$	$A_G^A = \frac{I_G[C(E)^u(E,T)] + I_G[C(E)^r(E,T)]}{I_G[C(E)^r(E,0)] + I_G[C(E)^u(E,0)]}$
	$q_G^r = C(E)^r(E,T)$	$q_G^u = C(E)^u(E,T)$	$q_G^A = C(E)^A(E,T)$
	$h_G^r = \frac{C(E)^r(E,T)}{1_B + I_G^r(E,T)}$	$h_G^u = \frac{C(E)^u(E,T)}{1_B + I_G^u(E,T)}$	$h_G^A = \frac{C(E)^A(E,T)}{1_B + I_G^A(E,T)}$
	$[B_G^{A,r}]^2 = \left[\frac{N_G^{A,r}}{N_G^{A,r}} \right]^2 \left[\frac{1_B + \frac{1}{N_G^{A,r}}}{1_B + \frac{1}{N_G^{A,r}}} \right]^2$	$[B_G^{A,u}]^2 = \left[\frac{N_G^{A,u}}{N_G^{A,u}} \right]^2 \left[\frac{1_B + \frac{1}{N_G^{A,u}}}{1_B + \frac{1}{N_G^{A,u}}} \right]^2$	$[B_G^A]^2 = \left[\frac{N_G^A}{N_G^A} \right]^2 \left[\frac{1_B + \frac{1}{N_G^A}}{1_B + \frac{1}{N_G^A}} \right]^2$
Total Current-weighted	Derived in Ref. 1	Derived in Ref. 2	$U.B. = \frac{1}{A_G}$ $L.B. = \frac{1}{[N_G^A]^2} A_G^{A,u}$ $A_G^A = \frac{I_G[C(E)^u(E,T)] + I_G[C(E)^r(E,T)]}{I_G[C(E)^r(E,0)] + I_G[C(E)^u(E,0)]}$ $[B_G^A]^2$ derived as above. Note that: $h_G^A = \frac{C(E)^A(E,T)}{[1_B + I_G^A(E,T)][1_B + I_G^A(E,T)]}$

- Notes: 1. For computational efficiency BRINE allows optional use of B^2 (see table) instead of B^2 , $[N_G^A] + \frac{1}{2}(B^2 + \frac{1}{2})$.
2. Notations are self-explanatory: $I_G^{A,r} = \sup[I_G^r(E,T)]$ for $1 \leq A, G$, etc. (q_G^r, h_G^r) = functions used in deriving the upper bound.
3. U.B. = upper bound; L.B. = lower bound.

where $\Gamma^2 = (M_g M_h / m_g m_h)$, and M_g, m_g, M_h , and m_h denote $\text{Sup } g, \text{Inf } g, \text{Sup } h$, and $\text{Inf } h$ over group G , respectively. M_g and m_g can be taken to be the maximum and minimum values, respectively, attained by the function g in the energy interval (group) G . M_h and m_h can be taken similarly for the function h . Consider now two additional functions $\bar{g}$ and $\bar{h}$, defined on G such that

$$g(E)h(E) = \bar{g}(E)\bar{h}(E) \text{ for } E \in G. \quad (3)$$

Then the Cauchy-Schwarz inequality¹⁰ gives

$$[I_G[g \cdot h]]^2 = [I_G[\bar{g} \cdot \bar{h}]]^2 \leq I_G[g^2] \cdot I_G[h^2]. \quad (4)$$

Choosing now,

$$h^2(E) \equiv \frac{C(E) \cdot \sigma_x^r(E, T)}{\sigma_B + \sigma_x^r(E, T)} \quad \text{and} \quad \bar{h}^2 \equiv \frac{C(E)}{\sigma_B + \sigma_x^r(E, T)}, \quad (5)$$

$$\text{and } g^2(E) \equiv C(E),$$

forces $\bar{g}^2(E)$ to be equal to $C(E) \cdot \sigma_x^r(E, T)$, and yields the following strict upper bound for $f_G^{x,r}(\sigma_B, T)$:

$$f_G^{x,r}(\sigma_B, T) \leq \frac{I_G[C(E) \cdot \sigma_x^r(E, T)]}{I_G[C(E) \cdot \sigma_x^r(E, 0)]} \cdot \left[\frac{1}{2} + \frac{1}{4} \left(B^2 + \frac{1}{B^2} \right) \right]. \quad (6)$$

The strict lower bound for $f_G^{x,r}(\sigma_B, T)$ is derived similarly, leading to

$$f_G^{x,r}(\sigma_B, T) \leq \frac{I_G[C(E) \cdot \sigma_x^r(E, T)]}{I_G[C(E) \cdot \sigma_x^r(E, 0)]} \cdot \left[\frac{1}{2} + \frac{1}{4} \left(B^2 + \frac{1}{B^2} \right) \right]^{-1}. \quad (7)$$

Discontinuities in cross sections at a finite number of points E^k in a given group G may occur, as specified by the ENDF procedures.³ In this case, Lebesgue-Stieltjes integrable extensions of the functions $g, h, \bar{g}$, and $\bar{h}$ can readily be constructed. The methodology outlined in Eqs. (2) through (7) is then directly applicable to the "extended" g and h functions. However, extra care needs to be exercised when evaluating M_g, m_g, M_h , and m_h since cross-section discontinuities may introduce additional "jump" constants. This is shown in Table 3.9.1.

Important conclusions from this study include:

1. A general methodology for computing strict upper and lower bounds for self-shielding factors has been developed.
2. The complete range of self-shielding factors computed by cross-section processing codes was addressed, and ENDF/B-specified cross-section discontinuities were taken into account.
3. Initial results obtained with data from a preliminary ENDF/B-V file confirm the necessity of replacing any arbitrarily imposed bounds on the shielding factors (e.g., $f_x \leq 1$ forced within some older generation codes²) by analytically derived bounds.
4. The stand-alone module BRINE will provide SFM users with a practical tool to check the f -factors.

*Research sponsored by DOE Office of Reactor Research and Technology.

1. R. E. Schenter et al., BNWL-1002 (1969); R. W. Hardie et al., BNWL-954 (1969).
2. B. A. Hutchins et al., GEAP-13703, GEAP-13740 (1971).
3. C. R. Weisbin et al., LA-6486-MS (1976).
4. R. E. MacFarlane et al., LA-7584-MS (1976).
5. W. R. Cobb et al., ARMP System documentation, 11.5, EPRI-RP-118 (1977).
6. A. Ahlin et al., ARMP System, 11.6, EPRI-RP-118-1 (1977).
7. D. G. Cacuci, ORNL-RSIC-41, 227 (1978).
8. C. R. Weisbin et al., ORNL-5505 (February 1979).
9. D. Garber et al., ENDF-102, BNL-NCS-50486 (1975).
10. D. S. Mitrinovic, *Analytical Inequalities*, Springer Verlag, NY (1970).

3.10. PROCESSING ENDF/B-V UNCERTAINTY DATA INTO MULTIGROUP COVARIANCE MATRICES*

J. D. Smith[†] H. L. Dodds[†] F. G. Perey C. R. Weisbin

(Reprint of *Trans. Am. Nucl. Soc.* 33, 822, 1979; see also ORNL/TM-7221, by J. D. Smith, June, 1980)

The purpose of this work is to develop the capability of processing ENDF/B-V uncertainty data into multigroup covariance matrices.¹ These matrices, coupled with conventional sensitivity analysis,² allow not only for propagation of uncertainties in basic nuclear data (i.e., ENDF/B-V) to uncertainties in reactor performance parameters such as k -effective and breeding ratio, but also provide valuable feedback to the nuclear data community as to which measurements need further refinement.

Previous work consisted of processing limited ENDF/B-IV data (ENDF/B-IV contained uncertainties for nitrogen, oxygen, and carbon only) using an uncertainty processor, PUFF,³ developed by extending the MINX⁴ cross-section processor. Many additional unofficial cross-section uncertainty evaluations have been prepared at ORNL in an ENDF/B-IV format.⁵ In the present work, the capability of processing newly formatted ENDF/B-V data has been developed. Specifically, processing capabilities have been added for new uncertainty relationships (LB = 5),⁶ explicit cross reaction and cross material relationships, and derived uncertainties. Derived is used here in the context that a reaction type (and therefore its uncertainties) may be determined by summing other reaction types (e.g. the total cross section is the sum of its partial cross sections). Derived is also used in the context that some reaction types are determined by ratio measurements to a reference reaction type (e.g., ²³⁹Pu fission cross section is measured as a ratio to the ²³⁵U fission cross section). Capabilities have also been added to produce the off-diagonal submatrices resulting from derived (in the context of summing) uncertainties. Processing uncertainties in the average number of neutrons per fission ($\bar{\nu}$) has also been included.⁶ Finally, an important accomplishment of this work has been to separate the uncertainty processing from the cross-section processing, originally suggested by LASL, to provide not only for a modular code system, but to reduce computing costs.

This new processing capability has been implemented in a new version of the PUFF code, named PUFF-II, and requires that the user supply only the multigroup cross sections (e.g. VIAMIN-C or -E libraries^{7,8}) and corresponding flux spectrum. Separate sub-routines have been added to put the output in a standard format (COVERX⁵).

Fig. 3.10.1. Standard Deviation and Correlation Matrix of the $^{239}\text{Pu}(n,f)$ Cross Sections - ENDF/B-V.

This uncertainty processing capability is improved relative to other uncertainty processors,^{9,10} in both the approach taken in producing the covariance matrices and in the handling of new data. Specifically, the approach taken is to produce the covariance matrices on a "super user grid" formed as the union of the user grid and the boundaries of the derived energy region in all cases except when the material being processed is derived via ratio measurements. For derived ratio measurements, the covariance matrices are formed on a "supergrid" formed as the union of the user grid and the uncertainty file energy grid. This eliminates approximations with respect to the uncertainty file while minimizing the order of the matrices needed. These matrices are subsequently collapsed to the user grid. The approach discussed in Ref. 9 is to produce all matrices on the user grid and is thus more prone to numerical errors (due to the energy structure), when derived uncertainties are to be processed, than our method. The approach discussed in Ref. 10 is to produce the covariance matrices on the fine grid of the cross section. Thus, this method requires more core storage than our method, especially when the number of matrices is large. Also, derived ratio measurements are not currently handled by the method in Ref. 10. In our approach, the only approximation that is made is associated with the interpolation of the fine-group cross section onto the supergrid.

An illustration of the results obtained using this new processing capability is presented in Fig. 3.10.1, which shows the correlation matrix³ and standard deviation for ^{239}Pu (ENDF/B-V material number 1399) fission cross section (reaction type number 18) in a 6-group user grid. The 6-group grid was chosen to facilitate comparison to the previously processed B-IV version of ^{239}Pu . A comparison of this version V result to the ORNL in-house version IV results indicates there is less correlation in the low energy range. Version V had little or no off-diagonal correlation in the low energy range while version IV's off-diagonal low energy correlation ranged from 27 to 50%. Also, the standard deviation of the version V ^{239}Pu fission cross section is ~4% higher in energy group 1, while it is ~2% lower in energy group 6 than the version IV results. The differences in the intermediate energy ranges were less significant than those of the extremes.

In conclusion, we have developed and demonstrated an uncertainty processing capability for handling most of the ENDF/B-V uncertainty data which is divorced from cross-section processing. Future work is being directed toward processing uncertainties in resolved resonance parameters and toward applying these methods in fast reactor data adjustment.¹¹

* Research sponsored by DOE Office of Reactor Research and Technology.

† University of Tennessee.

1. F. G. Perey, Unpublished notes of CSEWG minutes on processing uncertainty files.
2. J. L. Lucius, C. R. Weisbin, J. H. Marable, J. D. Drischler, R. Q. Wright, and J. E. White, "A User's Manual for the FORSS Sensitivity and Uncertainty Analysis Code System," ORNL-5316 (1977).
3. C. R. Weisbin, E. M. Oblow, J. Ching, J. E. White, R. Q. Wright, and J. D. Drischler, "Cross Section and Method Uncertainties: The Application of Sensitivity Analysis to Study Their Relationship in Radiation Transport Benchmark Problems," ORNL/TM-4847 (ENDF-218) (August 1975); see also, Radiation Shielding Information Center Code Collection PSR-93, ORNL.
4. C. R. Weisbin, P. D. Soran, R. E. MacFarlane, D. R. Harris, R. J. LaBauve, J. S. Hendricks, and J. E. White, "MINX, A Multigroup Interpretation of Nuclear Cross Sections from ENDF/B," Los Alamos Scientific Lab.; see also, Trans. Am. Nucl. Soc., 16, 127 (1973).
5. J. D. Drischler and C. R. Weisbin, "Compilation of Multigroup Cross-Section Covariance Matrices for Several Important Reactor Materials," Appendix A, ORNL-5318 (ENDF-235) (October 1977).
6. F. G. Perey, "The Data Covariance Files for ENDF/B-IV," ORNL/TM-5938 (ENDF-249) (July 1977).
7. "VITAMIN C: 171 Neutron, 36 Gamma-Ray Group Cross Sections in KAPX and CCCC Interface Formats for Fusion and LMFBR Neutronics, RSIC Data Library Collection," DLC-41 (1970).
8. C. R. Weisbin, R. W. Roussin, J. J. Wagschal, J. E. White, and R. Q. Wright, "VITAMIN-E: An ENDF/B-V Multigroup Cross-Section Library for LMFBR Core and Shield, LWR Shield, Dosimetry and Fusion Blanket Technology," ORNL-5505 (ENDF-274) (February 1979).
9. Tang Wu and C. W. Maynard, "Uncer: A University of Wisconsin Version of Uncertainty Files Processor for ENDF/B-V," UWFD-211 (1978).
10. R. W. MacFarlane, R. J. Burrett, D. W. Muir, and R. M. Boicourt, "The NJOY Nuclear Data Processing System: User's Manual," LA-7584-M (December 1978).
11. C. R. Weisbin, J. H. Marable, P. Collins, C. Cowan, R. W. Peelle, and M. Salvatores, "Specifications for Adjusted Cross Section and Covariance Libraries Based upon CSEWG Fast Reactor and Dosimetry Benchmarks," ORNL-5517 (ENDF-276) (June 1979).

3.11. IMPLEMENTATION OF ENDF/B-IV AND V DATA IN LWR DESIGN CODES: EPRI-CELL AND EPRI-CPM*

O. Ozer[†] R. E. MacFarlane[‡] M. L. Williams

(Reprint of Trans. Am. Nucl. Soc. 33, 820, 1979)

The selection and processing of a nuclear data base for use in the analysis of light-water reactors (LWRs) can have a critical impact on the accuracy of the calculated parameters. The two primary programs developed under EPRI support for LWR analysis, EPRI-CELL and CPM,¹ require data libraries consisting of infinitely dilute multigroup cross sections, composition- and energy-dependent resonance shielding factors, and energy transfer matrices including upscattering in the thermal range. The behavior of heavy actinide and fission product nuclides is represented as a series of linearized chains consistent with the CINDER² methodology.

Data libraries originally distributed with the programs were selected from sources known to give adequate results for the analysis of light-water-moderated, critical ^{235}U lattice experiments and PWR applications. Thus, the EPRI-CELL libraries were derived from sections of ENDF/B-versions I, II, and III, and from older sources, using the programs SUPERTOG AND FLANGE-II. The CPM libraries were generated from ENDF/B-III and then modified to force agreement with EPRI-CELL for the UO_2 lattices at HFP conditions.

In developing a new set of libraries for use in LWR analysis, it was considered necessary that nuclear data uncertainties be separated from uncertainties due to approximations in the mathematical models or data processing.

For this reason, EPRI has supported the development or adaptation of a number of rigorous analysis programs based on transport theory and point energy Monte Carlo models.³ Calculations of benchmark experiments using ENDF/B-IV data in the above programs have provided information for the development of ENDF/B-V as well as target values to be used in the validation of CELL/CPM data processing procedures.⁴

The procedures selected for preparing new ENDF/B-based CELL/CPM libraries have been based on the NJOY⁵ system developed at the Los Alamos Scientific Laboratory. This system reduces the ENDF/B data files into a fine-group intermediate library which can be easily collapsed to the format required by CELL, and CPM, as well as a number of other programs. Use of a common intermediate library allows for the effort of processing and validation to be shared among many users. Under EPRI support the NJOY system has been enabled to produce all the information required by CELL and CPM, including thermal scattering kernels derived from the ENDF/B scattering law data, $S(\alpha, \beta)$, and resonance shielding factors produced with the use of a homogeneous medium flux calculation and a detailed resonance profile representation for the absorbing nuclei mixed in with a moderator.

Initial validation tests were carried out using an interim set of ENDF/B-IV-based libraries in EPRI-CELL and CPM for the analysis of UO_2 critical lattices. The CELL/CPM results were compared with the more rigorous calculations using REPC-HAMMER⁶ at EPRI, MCNP⁷ at LASL, and ANISN, KENO-PX⁸ at Oak Ridge National Laboratory (ORNL). A sample comparison of CELL eigenvalues, and reaction ratios with REPC-HAMMER results obtained for CSENG benchmark 18 BAPL UO_2 -1 is shown on Table 3.11.1.

Major discrepancies observed with the early versions of the NJOY libraries were traced back to differences in the definition of the resonance-region shielding factors for CELL, CPM, and other transport theory codes. A procedure was developed for converting the NJOY-produced cross-section shielding factors to resonance integral shielding factors required by CPM. This procedure is based on an intermediate resonance representation of the flux within a group and utilizes the same intermediate resonance λ -factors as earlier versions of the CPM library. Similarly, a flux-disadvantage correction factor was introduced into EPRI-CELL to convert the shielded fuel region cross sections provided by NJOY to cell-averaged cross sections required by EPRI-CELL.

Table 3.11.1. Calculations of the BAPL-UO₂-1 Lattice with ENDF/B-IV Data
(Comparison of EPRI-CELL and REPC-HAMMER results)

Quantity	Experiment	EPRI-CELL CALCULATIONS			REPC-HAMMER
		Production Library	ENDF/B-IV Initial	ENDF/IV with Disadvantage Factor	ENDF/B-IV
k_{∞}	—	1.1330	1.1015	1.122	1.1322
k_{eff}	1.00	.9978	.9697	.988	.9929
ρ^{28}	1.39 + .01	1.374	1.6143	1.468	1.418
δ^{25}	.084 + .002	.0856	.0884	.0839	.0828
δ^{28}	.078 + .004	.0700	.0734	.0720	.0731
C^*	—	.8075	.873	.828	.810

Convergence problems in the thermal section of EPRI-CELL were traced back to the use of acceleration techniques in the thermal flux iteration and were resolved by using a rebalancing technique ensuring fast convergence for both the old and new libraries.

The inclusion of such corrections has resulted in much closer agreement between CELL/CPM and the more rigorous methods using the same ENDF/B-IV data base. This agreement is considered to be sufficient to prove the adequacy of the NJOY data processing procedures and opens the way for the preparation of ENDF/B-V-based libraries.

The latter libraries will be used in an extensive benchmarking program attempting to evaluate the adequacy of ENDF/B-V data for use in LWR analysis.

* Research sponsored by the Electric Power Research Institute.

† Electric Power Research Institute, Palo Alto, California 94304.

‡ Los Alamos Scientific Laboratory, Los Alamos, New Mexico 87545.

1. "Advanced Recycle Methodology Program System Documentation," EPRI-CCM-3 (September 1977).
2. T. R. England, W. B. Wilson, and M. G. Stamatiatos, "Fission Product Data for Thermal Reactors," EPRI NP-356 (December 1976).
3. H. Lichtenstein, H. Steinberg, E. Troubetzkoy, M. O. Cohen, and C. Chui, "Progress in the Development of a Reactivity Capability in the SAM-CE System for Validating Fuel Management Codes," EPRI NP-638 (February 1978).
4. L. Levitt, B. Magurno, and P. Rose, "Improvement of Reference Nuclear Data for Commercial Power Reactor Analysis and Design," EPRI NP-556 (October 1977).
5. R. E. MacFarlane, R. J. Barrett, D. W. Muir, and R. M. Boicourt, "The NJOY Nuclear Data Processing System: User's Manual," LA-7584-M (ENDF-272) (December 1976).
6. J. Barhen, W. Rothenstein, and E. Taviv, "The HAMMER Code System," EPRI NP-565 (October 1978).
7. "MCNP-A General Monte Carlo Code for Neutron and Photon Transport," LASL Group TD-6, LA 7396-M.
8. L. M. Petrie and N. F. Cross, "KENO-IV-An Improved Monte Carlo Criticality Program," ORNL-4938 (November 1975).

3.12. COMPARISON OF SEVERAL MULTIGROUP LIBRARIES FOR LWR SHIELDING PROBLEMS*

R. W. Roussin M. Metghalchi[†] J. West[‡] B. Nakhat[§]

(Reprint of Trans. Am. Nucl. Soc. 32, 644, 1960)

Several commonly used multigroup cross-section libraries have been applied to the one-dimensional (1-D) analysis of neutron and gamma-ray transport in two problems of potential interest in shielding analyses of light-water reactors (LWRs). The calculations were made to provide a comparison of the performance of the various libraries relative to the fine-group ¹LC-41/VITAMIN-C library¹ (171 neutron and 36 gamma-ray groups). In addition, the results are intended to provide a useful guide in the preparation of a broad-group library conforming to the standard under preparation by the ANS 6.1.2 Shielding Standards Working Group on Multigroup Cross Sections.²

Calculations using the ANISN³ discrete ordinates code were made for a fission source incident on a 1-m-thick slab of concrete and for a model⁴ of a typical LWR proposed by the ANS 6.2 Shielding Standards Working Group on Benchmark Problems as a benchmark problem. Neutron and gamma-ray dose rates based on the ANS 6.1.1 Standard⁵ were used as a basis of comparison, while detailed spectrum results helped to pinpoint areas of greatest variation among the results.

In addition to VITAMIN-C, libraries used for the LWR problem were DLC-37/EPR (100 n, 21 g),⁶ DLC-47/BUGLE (45 n, 16 g),⁷ and DLC-23/CASK (22 n, 18 g).⁸ Libraries for the concrete problem included in addition DLC-31/FEWGI (37 n, 21 g)⁹ and DLC-37/EURLIB (100 n, 20 g).¹⁰ (The latter were not used in the LWR calculation because they did not contain all required materials.)

Total, neutron, and gamma-ray dose rates at the exit of the concrete slab and at the outer surface of the LWR pressure vessel are summarized in Table 3.12.1. The results are expressed in percent difference relative to the VITAMIN-C fine-group answers. As discussed in a previous paper,¹¹ comparisons are made relative to fine-group results because no adequate experimental benchmarks are available at this time.

Table 3.12.1. Comparison of Dose Rate Results Calculated with Various Cross-Section Libraries for a Concrete Slab and an LWR Reactor Model

Library	Concrete Slab (Fission Source)			LWR Reactor Model (Draft ANS 6.2 Benchmark)		
	Total Dose	Neutron Dose	Gamma Dose	Total Dose	Neutron Dose	Gamma Dose
VITAMIN-C (171n,36g)	7.03-8 ^a	5.22-8	1.81-8	5.73+5	5.56+5	1.71+4
BUGLE (45n,16g)	-7.5% ^b	-11.5% ^b	+4.0% ^b	+10.9% ^b	+11.0% ^b	+7.6% ^b
EURLIB (100n,20g)	-9.2%	-5.2%	-20.5%	Not used	Not used	Not used
CASK (22n,18g)	-9.6%	-17.9%	+14.2%	+1.3%	+0.6%	+22.7%
FEWGI (37n,21g)	-14.1%	-16.1%	-8.1%	Not used	Not used	Not used
EPR ^c (100n,21g)	+37.9% ^c	+34.7% ^c	+47.2%	0.4%	-1.0%	+45.7%

^aRead 7.03×10^{-8} .

^bPercent difference relative to VITAMIN-C results.

^cEPR thermal group at 800 K (all others at 300 K) results in higher thermal flux (-50% of neutron dose).

For the concrete slab, all libraries except EPR under-predict but are within 20% of the VITAMIN-C total and neutron dose rates. Gamma-ray dose rates are also within 20% of the VITAMIN-C results, with BUGLE and CASK yielding larger dose rates and the other libraries yielding smaller dose rates. The high neutron dose rate for EPR results from the fact that the thermal group in that library was generated for 800 K, while all other libraries were generated for 300 K. This results in a much larger thermal flux for the fission source in concrete problems calculated with EPR. The enhanced thermal flux contributes about 50% of the neutron dose rate for the EPR result. For the LWR case, total and neutron dose rates predicted by CASK and EPR agree to within 1% with the VITAMIN-C dose rates, but the gamma-ray dose rates are somewhat higher (>20%) than the VITAMIN-C results. The BUGLE results for all three responses are within about 10% of those of VITAMIN-C.

One objective of this study was to help guide the preparation of a broad-group library conforming to the proposed ANS 6.1.2 Standard. The BUGLE library was prepared prior to the development of the specifications now in the draft standard, and results of this investigation have provided valuable input to the ANS 6.1.2 working group. An example of this kind of feedback is illustrated in Fig. 3.12.1, which compares BUGLE and VITAMIN-C results for the neutron spectrum above 1 MeV leaving the pressure vessel of the LWR model.¹² The higher BUGLE spectrum between 10 and 13.5 MeV, also noted in other work by Simmons,¹² is the result of a poor choice of weighting spectrum in the high-energy region above 10 MeV. Other regions in the energy spectrum are also being examined (and will be reported) with the purpose of producing a new version of BUGLE that conforms to the draft specification and yields acceptable results for the LWR problem and other types of LWR models. It is likely that some groups will be added between 0.414 and 10 eV and that the weighting spectrum for collapsing will be more relevant to typical LWR problems.

Fig. 3.12.1. Results of Calculations of the Fast-Neutron Spectrum Leaving the Pressure Vessel of the LWR Model Using the BUGLE and VITAMIN-C Cross-Section Libraries.

*Research sponsored by Nuclear Regulatory Commission.

†Atomic Energy Organization of Iran, Tehran.

‡UCC-ND Computer Sciences Division.

§University of Tennessee.

1. R. W. Roussin, C. R. Weisbin, J. E. White, N. M. Greene, R. Q. Wright, and J. B. Wright, "The CTR Processed Multigroup Cross Section Library for Neutronics Studies," ORNL/RSIC-37 (1975); available as DLC-41/VITAMIN-C from the Radiation Shielding Information Center, ORNL.
2. D. R. Harris, Chairman ANS 6.1.2, "Neutron and Gamma-Ray Cross Sections for Nuclear Radiation Protection Calculations (N410)," *Proposed American National Standard* (Nov. 1978).
3. W. W. Engle, Jr., "ANISN-A One-Dimensional Discrete Ordinates Transport Code with Anisotropic Scattering," K-1693, ORNL (1967).
4. J. C. Celnik, "Specifications for Power Reactor Shielding Benchmark Problems," ANS 6.2 Informal Notes (Nov. 17, 1976).
5. "Neutron and Gamma-Ray Flux-to-Dose-Rate Factors," American National Standard ANSI N666 (1978).
6. W. E. Ford, III, R. T. Santoro, R. W. Roussin, and D. M. Plaster, "Modification Number One to the 100n-21 γ Cross Section Library," ORNL/TM-5249 (Mar. 1976); available as DLC-37D/EPR from the Radiation Shielding Information Center, ORNL.
7. "BUGLE: Coupled 45 Neutron, 16 Gamma-Ray, P₅, Cross Sections for Studies by the ANS 6.1.2 Shielding Standards Working Group on Multigroup Cross Sections," P. W. Roussin, informal memo (1977); available as DLC-47/BUGLE from the Radiation Shielding Information Center, ORNL.
8. "CASK-40 Group Coupled Neutron and Gamma-Ray Cross-Section Data," (1973); available as DLC-23E/CASK from the Radiation Shielding Information Center, ORNL.
9. D. E. Bartine, J. R. Knight, J. V. Pace III, and R. W. Roussin, "Production and Testing of the DNA Few-Group Coupled Neutron-Gamma Cross-Section Library," ORNL/TM-4840 (Mar. 1977); available as DLC-31/(DPL-1F/FEWGI) from the Radiation Shielding Information Center, ORNL.
10. G. Gonano, G. Hehn, M. Mattes, R. Nicks, and H. Rief, "Standard Energy Group Structure for Shielding Benchmark Experiments," *European Shielding Information Service Newsletter No. 12* (Jan. 1975), available as DLC-35B/EURLIB-III from the Radiation Shielding Information Center, ORNL.
11. J. T. West, G. P. DeBeer, B. Nakhai, and R. W. Roussin, "Developing an ANS Coupled Cross-Section Standard for Concrete Shielding," *Trans. Am. Nucl. Soc.* 28: 642 (1978).
12. G. L. Simmons, Science Applications, Inc., La Jolla, California, Private Communication.

3.13. RELATIVE CONSISTENCY OF ENDF/B-IV AND -V WITH FAST-REACTOR BENCHMARKS*

Y. Yeivin[†] J. J. Wagschal[†] J. H. Marable C. R. Weisbin*(Abstract of paper in Nuclear Cross Sections for Technology, NBS Special Publication 594, p. 182, 1980)*

The consistency of eleven selected fast-reactor and two neutron-field integral experiments with the ENDF/B-IV and -V libraries was examined by considering contributions to chi-square. Integral measurements least consistent with each given library were identified one at a time, and the particular cross sections which were significantly adjusted at each step were also identified. The results of this analysis demonstrate that, with respect to twelve out of the thirteen integral measurements considered, ENDF/B-V is a marked improvement over Version IV in the sense that (a) the integral data are significantly more consistent with Version V than with Version IV, (b) fewer cross sections need to be adjusted to achieve agreement between all the experimental data and the corresponding values calculated by Version V, and (c) the necessary adjustments are smaller.

* Research sponsored by DOE Office of Reactor Research and Technology.

[†] On leave from The Hebrew University, Jerusalem, Israel.

3.14. DATA TESTING OF ENDF/B-IV AND -V*

J. J. Wagschal[†] Y. Yeivin[†]*(Summary of paper presented at annual meeting of the Israeli Nuclear Society, Haifa, Israel, December 17, 1979)*

The motivation and plan for a large-scale undertaking at ORNL to produce an adjusted cross-section library for fast-reactor core-physics analysis has been elaborated in a recently published report.¹ Although some consider the ideal ultimate product of adjustment to be an improved basic data (energy-point) library, the more immediate and practical goal is the generation of a multigroup cross section and covariance library to estimate core physics performance with a minimum of data-related bias and to quantify performance uncertainties. In the last decade adjusted multigroup libraries have been used extensively by reactor designers throughout the world, and many now consider that least-squares adjustment of group constants is a more practical way to extrapolate measured performance parameters to similar systems. For other than a very restricted use of the adjusted library, the quality of the input data is critical, and therefore the emphasis here is on using carefully analyzed integral data (including uncertainties and correlations) and on adjusting cross sections for which evaluated uncertainty files are available.

Unless convincingly demonstrated, the validity of any adjusted nuclear data library can be challenged. Nevertheless, the adjustment procedure can point to cross sections and integral data which deserve re-examination, as well as to modeling and calculational methods inadequacies. With this in mind, procedures were developed to analyze the consistency of the data used to adjust the cross sections. The first such procedure to be applied was originally intended to identify definitely irregular integral data (in a comparative sense). A similar procedure has been successfully applied in the past to achieve improved agreement between measured data and corresponding calculated values.²

This procedure turned out to be a very practical and effective tool for "data testing," and the purpose of the present paper is to report preliminary results of the application of this procedure to data testing of ENDF/B-V. Since this procedure has also been applied to ENDF/B-IV data, we are able to present a comparison of these two libraries. In fact, much more can be gained from a comparative analysis of two or several libraries than from data testing of just one given library, be it even the latest and supposedly the "best."

The consistency of eleven selected fast-reactor and two-neutron-field integral experiments with the ENDF/B-IV and -V libraries was examined by considering contributions to chi-square. Integral measurements least consistent with each given library were identified one at a time, and the particular cross sections which were significantly adjusted at each step were also identified. The results of this analysis demonstrate that, with respect to twelve out of the thirteen integral measurements considered, ENDF/B-V is a marked improvement over Version IV in the sense that (a) the integral data are significantly more consistent with Version V than with Version IV, (b) fewer cross sections need to be adjusted to achieve agreement between all the experimental data and the corresponding values calculated by Version V, and (c) the necessary adjustments are smaller.

* ORNL research sponsored by DOE Office of Reactor Research and Technology.

† On leave from The Hebrew University, Jerusalem, Israel.

1. C. R. Weisbin et al., ORNL-5517 (1979).
2. A. Pazy et al., Nucl. Sci. Eng. 55, 280 (1974).

3.15. AN OVERVIEW OF CSEWG SHIELDING BENCHMARK PROBLEMS*

R. E. Maerker

(reprint of Trans. Am. Nucl. Soc. 22, 661, 1979)

The fundamental philosophy behind the choosing of CSEWG shielding benchmarks is that the accuracy of a certain range of cross-section data be adequately tested.[†] The benchmarks, therefore, consist of measurements and calculations of these measurements. Calculations for which there are no measurements provide little information on the adequacy of the data, although they can perhaps indicate the sensitivity of results to variations in data.

The criteria a measurement must meet are the usual ones, plus a few unusual ones; i.e., (a) simple geometry, (b) few materials, (c) well-known source, (d) well-known detector response, (e) well-defined measured quantity relative to the same normalization as the source, (f) repeatability, (g) estimates of uncertainties due to various sources of error and their covariances should be given, (h) adequate documentation, and (i) independent verification. In addition, practical considerations dictate that the material and cross-section sensitivity be appropriate for some significant application.

The term "benchmark candidate" is used to designate any single measurement or any single calculation of a measurement that is documented in an appropriate benchmark format; the term "benchmark" is reserved to designate two or more "benchmark candidates" (for example, a measurement and a calculation of the measurement or two uncorrelated measurements of the same quantity) which together, in the opinion of CSEWG, provide sufficient independent verification as to warrant the benchmark label.

The benchmark format for a measurement should include a brief description of the expected cross-section sensitivity as well as a summary of the measurement method and extent of the data reduction. The date of the measurement as well as pertinent references should be given. Tables and figures defining the actual geometry and material compositions, including auxiliary shielding, should be presented in enough detail that the source incident on the shield, the current leaking the shield, and the flux incident on the detector can be accurately calculated. The energy-angle-space-time distribution of the source must be given as well as the energy-angle-space-time dependence of the detector response function if an integral quantity is measured. If some of these characteristics for either the source or the detector response function were not measured, then the rationale for the data provided should be noted. The measured results must be presented in units relative to the same normalization as the source is given; i.e., the calculation should predict the same absolute measured results starting with the source described earlier. Thus, only "shape" comparisons with arbitrary normalizations are unacceptable. Finally, uncertainties due to various sources of error should be listed together with any correlations among the various measurements.

The benchmark format for a calculation of a measurement should include a brief description of the calculational method, together with any calculated sensitivities of the measurement to input data. The calculational model should be presented containing all pertinent dimensions and a discussion of the assumptions made in arriving at the model. The details of the calculation, including method parameters used and the source and detector descriptions, should be presented. The manner in which the measured quantities are determined from the calculation should also be described; i.e., by simple folding of unperturbed fluxes or by inclusion of the detector into the calculational geometry. The source of the basic nuclear data and the processing of the data into the form used in the calculation should be discussed. The estimation of uncertainties in the results due to method uncertainties arising from use of various parameters quantified in the calculation (P_i , S_n , mesh, group structure, etc.) as well as due to data uncertainties would also be valuable. Finally, it would be highly desirable in each calculational candidate to define in addition a one-dimensional (1-D) model and use it to calculate the measured results, even though the geometry and the source may be somewhat compromised. The advantage of this additional calculation is the scaling of the higher dimensional calculated results to the 1-D results so that subsequent calculations (using future ENDF/B evaluations for example) need only be 1-D. Thus, ratios of calculated results using the two geometries but the same cross sections together with the 1-D model used might very well encourage others to calculate a benchmark that otherwise might be too expensive and/or time consuming.

Table 3.15.1 summarizes the list of presently available shielding benchmark experiments.

Table 3.15.1. Summary of Presently Available Shielding Benchmarks
Designation^a and Title

SDT1.	Iron Broomstick Experiment - An Experimental Check of Neutron Total Cross Sections
SDT2.	Oxygen Broomstick Experiment - An Experimental Check of Neutron Total Cross Sections
SDT3.	Nitrogen Broomstick Experiment - An Experimental Check of Neutron Total Cross Sections
SDT4.	Sodium Broomstick Experiment - An Experimental Check of Neutron Total Cross Sections
SDT5.	Stainless-Steel Broomstick Experiment - An Experimental Check of Neutron Total Cross Sections
SDT8.	Specifications for the Zero Power Plutonium Reactor Shield Experiment for the Fast Test Reactor (ZPPR/FTR-2)
SDT10.	Calculational Models for LLL Pulsed Spheres ^b
SDT11.	The ORNL Benchmark Experiment for Neutron Transport Through Iron and Stainless Steel. Part I
SDT12.	The ORNL Benchmark Experiment for Neutron Transport Through Sodium
SB2.	Experiment on Secondary Gamma-Ray Production Cross Sections Arising from Thermal-Neutron Capture in Each of 14 Different Elements Plus a Stainless Steel
SB3.	Experiment on Secondary Gamma-Ray Production Cross Sections Averaged Over a Fast-Neutron Spectrum for Each of 13 Different Elements Plus a Stainless Steel
SB4.	Measurements and Calculations of the ORNL CRBR Upper Axial Shield Experiment ^c

^aThe SDT (Shielding Data Testing) series is being selectively replaced by the newer SB (Shielding Benchmark) series.

^bSupplemented by earlier documentation of experimental results.

^cDistribution limited at this time.

* Research sponsored by DOE Office of Reactor Research and Technology.

† Much of this philosophy was expounded by L. Harris and E. Straker in an informal document circulated among and approved by members of the CSEWG Shielding Subcommittee several years ago, and is reproduced to a large extent in this paper.

3.16. BENCHMARK SHIELDING PROBLEMS OBTAINED FROM INTEGRAL TESTS OF NEUTRON CROSS SECTIONS*

B. W. Wehring[†] J. J. Dorning[†] N. E. Hertel[†]
D. T. Ingersoll R. H. Johnson[‡]

(Reprints of *Trans. Am. Nucl. Soc.* 33, 666-667, 1960)

The results of integral tests of neutron cross sections¹⁻³ have been reanalyzed to provide benchmark shielding problems. The integral tests consisted of comparing measurements and calculations of the energy spectrum of neutrons leaking out of a bare homogeneous spherical shell containing a neutron source at its center. To provide the maximum information from these tests, optimized window widths⁴ (effective experimental resolution) were used to smooth both the unfolded spectrum and the calculated spectrum. This procedure yielded a window-width dependence on neutron energy which was both complicated and unique to each measurement. To provide results appropriate for benchmark shielding problems, the unfolded and calculated spectra have been smoothed using both constant-energy window widths and constant-lethargy window widths.

Benchmark shielding data, both measurements and calculations, have been obtained for spherical assemblies of beryllium (IR, 3.17 cm; OR, 10.16 cm), polyethylene (IR, 3.05 cm; OR, 22.86 cm), niobium (IR, 3.09 cm; OR, 12.70 cm), iron (IR, 7.65 cm; OR, 38.10 cm), and tungsten (IR, 3.10 cm; OR, 22.12 cm). All of the materials were full density except for tungsten which had a density of 12.26 g/cm³. A ²⁵²Cf source provided a fission neutron source for each of the spherical assemblies; a neutron generator provided a 14-MeV DT fusion neutron source for the iron and tungsten assemblies. Besides the obvious practicality of these sources, they also are well suited for benchmark problems because they are well known.⁵

The measurements were made for neutron energies between 1 and 15 MeV using an NE-213 liquid-scintillation proton-recoil spectrometer⁶ and were unfolded using the FORIST unfolding code.⁷ This code is a refinement of the FERDOR code and incorporates an iterative procedure to optimize the energy resolution of the results. The neutron response matrix⁸ used for FORIST is one based primarily on experimental results and is supplied with the FORIST code package available from RISC.³ The measurements using the neutron generator were done on an absolute basis by using an associate particle detector which also served as a monitor of 2.5-MeV DD neutron contamination.

The neutron leakage spectra were calculated using the discrete ordinates S_N transport code ANISN and, for some cases, the continuous-energy Monte Carlo transport code VIM. The cross-section data used in these calculations were derived from ENDF/B-IV where possible. A Maxwellian fission spectrum with a temperature of 1.43 MeV described the ²⁵²Cf neutron source. All ANISN calculations were performed with S_3P_3 . Calculations done utilizing the multidimensional capabilities of the VIM code demonstrated that the reentrant hole needed for the neutron generator had negligible effect on the neutron leakage spectra at the detector location.³ The VIM results for the iron sphere also demonstrated that the Bondarenko self-shielding formalism used for iron appropriately adjusts cross-section values.¹⁰

The smoothing of the calculated leakage was done by the matrix equation

$$L_i = \sum_{j=1}^N G_{ij} L_j$$

where L_j is the group leakage calculated by the transport codes for the j 'th neutron energy group, $\bar{L}_i$ is the smoothed group leakage for the i 'th group, and G_{ij} is given by

$$G_{ij} = (E_j - E_{j+1})^{-1} \int_{E_{j+1}}^{E_j} dE' \int_{E_{i+1}}^{E_i} dE (2\pi\sigma_j^2)^{1/2} \\ \times \exp[-(E - E')^2 / (2\sigma_j^2)]$$

The standard deviation σ_j is equal to 0.425 times the window width evaluated for the j 'th energy group; E represents neutron energy. Figure 3.16.1 shows an example of the results obtained when constant-lethargy window widths are employed. The quantity plotted is $1/2(E_i + E_{i+1})\bar{L}_i$ which closely approximates lethargy leakage — number of neutrons leaking out of the sphere per unit lethargy interval for one source neutron.

The measurements and calculations done at the University of Illinois to provide integral tests of neutron cross sections satisfy the requirements for benchmark shielding problems: few materials, simple geometry, well-known source, well-known detector response, and well-defined measured quantity. By smoothing with simple window widths, benchmark shielding data have been obtained which can be easily used by others. These benchmark data will be fully documented and submitted to CSEWG¹¹ for consideration as CSEWG benchmarks.

Fig. 3.16.1. Neutron Leakage Spectrum for a ^{252}Cf Source Located at the Center of the Beryllium Sphere. The experimental results are shown as vertical error bars (± 1 standard deviation error due to counting statistics). The calculations were smoothed with constant-lethargy window width of 0.15.

* Research sponsored by Department of Energy.

† University of Illinois.

‡ University of Texas, Austin, TX.

§ Purdue University.

1. R. H. Johnson, "Integral Tests of Neutron Cross Sections for Iron, Niobium, Beryllium, and Polyethylene," PhD Thesis, University of Illinois at Urbana-Champaign (1975).
2. D. T. Ingersoll, "Integral Testing of Neutron Cross Sections Using Simultaneous Neutron and Gamma-Ray Measurements," PhD Thesis, University of Illinois at Urbana-Champaign (1977).
3. N. E. Hertel, "High-Energy Neutron Transport Through Tungsten and Iron," PhD Thesis, University of Illinois at Urbana-Champaign (1979).
4. R. H. Johnson, B. W. Wehring, and J. J. Dornig, Trans. Am. Nucl. Soc., 22, 798 (1975).
5. R. H. Johnson, B. W. Wehring, and J. J. Dornig, Trans. Am. Nucl. Soc., 22, 799 (1975).
6. R. H. Johnson, D. T. Ingersoll, B. W. Wehring, and J. J. Dornig, Nucl. Instr. Methods, 145, 337 (1977).

7. "FORIST Spectra Unfolding Code," PSR-92, Radiation Shielding Information Center, Oak Ridge National Laboratory.
8. D. T. Ingersoll, B. W. Wehring, and R. H. Johnson, Proc. Radiation Shielding Information Center Seminar-Workshop, Radiation Energy Spectra Unfolding, ORNL/RSIC-40, p. 47 (1976).
9. Radiation Shielding Information Center, Oak Ridge National Laboratory, Oak Ridge, TN 37930.
10. N. E. Hertel, B. W. Wehring, and R. H. Johnson, Proc. Radiation Shielding Information Center Seminar-Workshop, Multigroup Nuclear Cross-Section Processing, ORNL/RSIC-41, p. 181 (1978).
11. Cross Section Evaluation Working Group coordinated by National Nuclear Data Center, Brookhaven National Laboratory, Upton, L.I., N.Y. 11973.

DEVELOPMENT OF SENSITIVITY ANALYSIS METHODS

3.17. A REVIEW OF THE THEORY AND APPLICATION OF SENSITIVITY AND UNCERTAINTY ANALYSIS: PROCEEDINGS OF A SEMINAR-WORKSHOP, OAK RIDGE, TENNESSEE, AUGUST 22-24, 1978*

Edited and Compiled by:

C. R. Weisbin R. W. Roussin H. R. Hendrickson E. W. Bryant

(Abstract of ORNL/RSIC-42, December, 1978)

This review consists of manuscripts of 25 papers submitted to the Radiation Shielding Information Center Seminar-Workshop on "Theory and Application of Sensitivity and Uncertainty Analysis" held at Oak Ridge, Tennessee, August 22-24, 1978. The papers are grouped in three sessions which were conducted at the Seminar. Additional papers which were submitted, but not given orally, are also included in this report. The sessions were titled, "Sensitivity and Uncertainty Analysis for Fast and Thermal Reactors," "Sensitivity and Uncertainty Analysis for Dosimetry and Fusion Reactor Applications," and "Advances and Future Extensions for Sensitivity and Uncertainty Analysis."

A summary of the papers presented and the discussions and comments which were made is also included to provide an indication of the state-of-the-art of sensitivity and uncertainty analysis.

* Seminar jointly sponsored by Department of Energy, the U.S. Regulatory Commission, the Defense Nuclear Agency, and the Electric Power Research Institute.

3.18. SENSITIVITY AND UNCERTAINTY ANALYSIS OF REACTOR PERFORMANCE PARAMETERS* (with illustrations for fast reactors)

C. R. Weisbin R. W. Peelle J. H. Marable P. J. Collins[†]
E. Kujawski E. Greenspan G. de Saussure

(Excerpt from introduction to Vol. 14 of *Advances in Nuclear Science and Technology*, Plenum Press, in press)

The intent of this book is to present a comprehensive review of a sensitivity-based methodology developed to utilize differential and integral information in the estimation of reactor performance parameters and their associated uncertainties. It is generally

recognized that uncertainties in calculated reactor design parameters such as breeding ratio, power distribution, reactivity worth, etc. may necessitate excessive and expensive design margins. For example, adequate design margins are required to account for uncertainties in the predicted peak thermal power which affects fuel and cladding temperatures, and fluence-induced creep and swelling in structural materials. Additional design margins are included to account for uncertainties in required enrichment. Excess reactivity results in increased control requirements while underprediction of enrichment would require limiting operating conditions. Thus, the establishment of a systematic approach for quantifying these uncertainties and assessing their principal components is a necessary step before a significant reduction in these uncertainties, and the associated design margins, can be achieved. The necessary complex techniques have now become fairly well developed and deserve a comprehensive review and evaluation of the type presented here.

Since the methodology described in this text depends critically on the information provided by the communities of data measurers, evaluators, method developers and related professionals, the book should be useful and interesting to these groups. We hope that in addition to providing uncertainty analysis tools to the reactor designer, this book will suggest a mechanism for feedback to the various supporting technologies and a means for establishing priorities for required new research. While much of the material presented here may be found in the journal literature in similar form, this work is intended to provide a rather complete coverage within one volume.

An outline of the book is as follows:

- I. Introduction (C. R. Weisbin)
- II. Uncertainty in the Nuclear Data Used for Reactor Calculations (R. W. Peelle)
- III. Computational Methodology and Associated Uncertainties (E. Kujawski[‡] and C. R. Weisbin)
- IV. Integral Experiment Information for Fast Reactors (P. J. Collins[†])
- V. Sensitivity Functions for Uncertainty Analysis (E. Greenspan[§])
- VI. Combination of Differential and Integral Data (J. H. Marable, C. R. Weisbin, and G. de Saussure)
- VII. New Developments in Sensitivity Theory (E. Greenspan[§])
- VIII. Summary (C. R. Weisbin)

* Research sponsored by Department of Energy.

† Argonne-West, Idaho Falls.

‡ General Electric Company, Sunnyvale.

§ University of Illinois.

3.19. A REVIEW OF THE CAPABILITIES OF THE ORNL FORSS SENSITIVITY AND UNCERTAINTY ANALYSIS SYSTEM*[†]

R. W. Roussin C. R. Weisbin J. L. Lucius[‡]

(Abstract of paper presented at Specialists' Meeting on Nuclear Data and Benchmarks for Reactor Shielding, OECD Headquarters, Paris, France, October 27-29, 1980)

The ORNL FORSS Sensitivity and Uncertainty Analysis System was demonstrated in the 1978 Radiation Shielding Information Center (RSIC) Workshop. The first versions of this code system for both IBM and CDC computers are now packaged and are available from RSIC. Features of the FORSS system are described and guidelines for its use are given. An assessment of the status of the system and plans for future updates are provided. Examples of applications of the system to fast reactor and fusion integral experiments, to reactor dosimetry problems, and to the adjustment of a cross-section library are discussed.

* Research sponsored by the Department of Energy, the U.S. Nuclear Regulatory Commission, the Defense Nuclear Agency, and the Electric Power Research Institute.

† See also paper 3.7.

‡ UCC-ND Computer Sciences Division.

3.20. A USERS MANUAL FOR THE FORSS SENSITIVITY AND UNCERTAINTY ANALYSIS CODE SYSTEM*

J. L. Lucius[†] C. R. Weisbin J. H. Marable
J. D. Drischler D. Q. Wright[†] J. E. White[†]

(Abstract of EBRD-710, in press)

FORSS is a code system used to study relationships between nuclear reaction cross sections, integral experiments, reactor performance parameter predictions and associated uncertainties. This report describes the computing environment and the modules currently used to implement FORSS Sensitivity and Uncertainty Methodology.

* Research sponsored by DOE Office of Reactor Research and Technology.

[†] U.C.-ND Computer Sciences Division.

3.21. THE COVERX SERVICE MODULE OF THE FORSS SYSTEM*

J. D. Drischler

(Abstract of EBRD-710, in press, 1971, 1972)

The COVERX Service Module includes seven execution paths to aid in understanding and using multigroup cross-section covariance matrices contained in the standard interface file COVERX. The execution paths provide the following operations on COVERX file(s):

1. List the contents of a COVERX file.
2. Allow adding new multigroup cross-section covariance matrices to an existing COVERX file.
3. Allow deletion of multigroup covariance matrices from an existing COVERX file.
4. Merge two COVERX files and create a new file.
5. Change the mode of a file from unformatted to formatted and conversely.
6. Allow modification of the records contained in a COVERX file.
7. Selectively edit or copy a file.

* Research sponsored by DOE Office of Reactor Research and Technology.

3.22. A USER'S GUIDE FOR THE JULIET MODULE OF THE FORSS SENSITIVITY AND UNCERTAINTY ANALYSIS CODE SYSTEM*

J. L. Lucius[†] E. M. Obrow G. W. Cunningham, III[†]

(Abstract of ORNL/TM-6894, February, 1974)

JULIET is the FORSS module that calculates generalized sources, responses (e.g., criticality, reaction rate ratios, reactivity worths), normalization parameters and sensitivity coefficients. JULIET is organized into execution paths which are in effect submodules. This permits a problem to be segmented for solution at the user's discretion (i.e., multiple entry points). JULIET normally operates with fluxes generated by the FORSS version of ANISN; however, the execution path concept permits interaction with other neutronics codes such as DOT and VENTURE.

The proposed CCCC file MATXS is the cross-section data base for JULIET permitting the calculation of sensitivity coefficients with respect to partial cross sections. The sensitivity coefficients calculated by JULIET are placed in the proposed CCCC file SENPRO where they may be accessed by other modules in the FORSS system or transmitted to other installations.

* Research sponsored by DOE Office of Reactor Research and Technology.

† UCC-ND Computer Sciences Division.

3.23. TIME-DEPENDENT GENERALIZED PERTURBATION THEORY FOR COUPLED NEUTRON-NUCLIDE PROBLEMS*

E. Greenspan[†] M. L. Williams J. H. Marable

(Abstract of Nucl. Sci. Eng. 75, 210, 1980)

A generalized time-dependent nonlinear perturbation theory for coupled fields of neutrons, nuclides, and delayed neutron precursors is presented in a unified, yet detailed, formulation for diverse areas of applications, including depletion analysis, xenon poisoning, reactor kinetics, and pulsed neutron problems. Several applications of this formulation are discussed including cross-section sensitivity analysis and reactor design and operation sensitivity analysis.

* Research sponsored by DOE Office of Reactor Research and Technology.

† On leave from the Nuclear Research Center-Negev, Beer-Sheva, and the Ben-Gurion University of the Negev, Israel.

3.24. CONSTRAINED SENSITIVITY THEORY*

E. Greenspan[†] M. L. Williams

(Reprint of Trans. Am. Nucl. Soc. 34, 823, 1980)

In sensitivity and uncertainty analysis of "to-be-built" reactors, it is customary^{1,2} to use k-reset sensitivity functions-accounting for the combined effects of the change (or uncertainty) in the input data and of the alteration in some design variable applied to maintain criticality. Critical reactors are usually subjected to several constraints, such as power peaking factor and breeding ratio constraints, in addition to the criticality constraint. In this summary we present perturbation theory formulations which can account, simultaneously, for several constraints both in critical reactors and in source-driven systems (such as radiation shields and blankets of fusion devices). All the sensitivity and uncertainty analyses of source-driven systems carried out so far used unconstrained sensitivity functions despite the fact that such systems can also be subjected to a variety of constraints.

Two approaches are used for deriving the constrained perturbation theory (CPT)—the external constraint approach (using perturbation theory techniques) and the internal constraint approach (using variational techniques). The formulations presented pertain to problems subjected to equality constraints in which the number of control variables equals the number of constraints.

Consider performance parameters such as ratios of bilinear, linear flux, or linear adjoint functionals expressed formally as $R \equiv R[\phi, \phi^*, h]$, where h is the "realization vector."³ Suppose the reactor is subjected to n constraints $F_i[\phi, \phi^*, h]$, $i = 1, \dots, n$. The flux and adjoint functions are the solution of the eigenvalue equations $(A - \lambda B)\phi = 0$ and $(A^* - \lambda B^*)\phi^* = 0$. Following the approach of Ref. 3, we construct the following functional for R :

$$K[\phi, \phi^*, \lambda, h, q, p_1, p_2, \dots, p_n] = R[\phi, \phi^*, h] - \langle r^*, (A - \lambda B)\phi \rangle - \langle r, (A^* - \lambda B^*)\phi^* \rangle - \sum_{i=1}^{n-1} f_i^* (F_i[\phi, \phi^*, h_i] - F_{i0}) \quad (1)$$

where q is the input (or perturbation variable, the p_j 's are the control variables, r^* , r , and f_i^* are Lagrange multipliers (yet to be determined), F_{i0} is the value F_i has to have and $\langle \cdot \rangle$ denotes integration over phase space. The variation in K is

$$\begin{aligned} \delta K = & \left[\left\{ \frac{\partial R}{\partial q} - r^* \frac{\partial H}{\partial q} - \frac{\partial H^*}{\partial q} + \sum_{i=1}^{n-1} f_i^* \frac{\partial F_i}{\partial q} \right\}, \delta q \right] \\ & + \left[\left\{ \frac{\partial R}{\partial \phi} - H^* r^* - \sum_{i=1}^{n-1} f_i^* \frac{\partial F_i}{\partial \phi} \right\}, \delta \phi \right] \\ & + \left[\left\{ \frac{\partial R}{\partial \phi^*} - H r - \sum_{i=1}^{n-1} f_i \frac{\partial F_i}{\partial \phi^*} \right\}, \delta \phi^* \right] \\ & + \sum_{j=1}^n \left[\left\{ \frac{\partial R}{\partial p_j} - r^* \frac{\partial H}{\partial p_j} - r \frac{\partial H^*}{\partial p_j} + \sum_{i=1}^{n-1} f_i^* \frac{\partial F_i}{\partial p_j} \right\}, \delta p_j \right], \end{aligned} \quad (2)$$

from which we get the Euler-Lagrange equations which make δK independent, to first order, of the alterations in the flux, adjoint, and control variables,

$$(A^* - \lambda B^*)r^* = \frac{\partial R}{\partial \phi} - \sum_{i=1}^{n-1} f_i^* \frac{\partial F_i}{\partial \phi}, \quad (3)$$

$$(A - \lambda B)r = \frac{\partial R}{\partial \phi^*} - \sum_{i=1}^{n-1} f_i \frac{\partial F_i}{\partial \phi^*}, \quad (4)$$

and

$$\frac{\partial R}{\partial p_j} - \left[r^*, \frac{\partial H}{\partial p_j} \phi \right]_\rho - \left[r, \frac{\partial H^*}{\partial p_j} \phi^* \right]_\rho - \sum_{i=1}^{n-1} f_i^* \frac{\partial F_i}{\partial p_j} = 0, \quad j = 1, \dots, n. \quad (5)$$

In the above, $[\dots]_\rho$ is to imply integration over the phase space variables or parts thereof, as appropriate for each of the terms; $H = A - \lambda B$ and $\partial H / \partial v = \partial A / \partial v - \lambda \partial B / \partial v$. The eigenvalue λ is not varied because of the criticality constraint. Criticality is maintained by the appropriate selection of the magnitude of the fundamental-mode contamination of r^* and r (Ref. 3). Setting $r^* = r_p^* + b^* \phi^*$ and $r = r_p + b \phi$, where r_p^* and r_p are free of any component of ϕ^* and ϕ and are the solution of Eqs. (3) and (4), the Lagrange multipliers $(b + b^*)$ and f_i^* are the solution of the linear set of equations [obtained from Eq. (5)],

$$(b + b^*) \left[\phi^*, \frac{\partial H}{\partial p_j} \phi \right]_\rho + \sum_{i=1}^{n-1} f_i^* \frac{\partial F_i}{\partial p_j} = \left[r_p^*, \frac{\partial H}{\partial p_j} \phi \right]_\rho - \left[r_p, \frac{\partial H^*}{\partial p_j} \phi^* \right]_\rho, \quad j = 1, \dots, n. \quad (6)$$

With these Lagrange multipliers the CPT for R becomes

$$\frac{dR}{dq} = \frac{\partial R}{\partial q} - \sum_{i=1}^{n-1} f_i^* \frac{\partial F_i}{\partial q} - (b+b^*) \left[z^*, \frac{\partial H}{\partial q} \right] - \left[z_p^*, \frac{\partial H}{\partial q} \right] - \left[z_p^*, \frac{\partial H^*}{\partial q} \delta^* \right] \quad (7)$$

We shall now derive the equivalent CPT using the external constraints approach. The performance parameter is considered to be a functional of q and, through the constraints, on the p_i so that

$$\frac{dR}{dq} = \left(\frac{\partial R}{\partial q} \right) + \sum_{i=1}^n \left(\frac{\partial R}{\partial p_i} \right) \frac{\partial p_i}{\partial q} \quad (8)$$

where $(\partial R / \partial q)$, etc. is the conventional unconstrained generalized perturbation theory expression for R (whereas $\partial R / \partial q$, etc. accounts only for the explicit dependence of R on q). The $\partial p_i / \partial q$ terms are to be obtained from the solution of the set of n linear equations expressing the constraint conditions

$$\left(\frac{\partial F_j}{\partial q} \right) + \sum_{i=1}^n \left(\frac{\partial F_j}{\partial p_i} \right) \left(\frac{\partial p_i}{\partial q} \right) = 0, \quad j = 1, \dots, n \quad (9)$$

The formulation of Eqs. (8) and (9) is applicable both for critical reactors and for source-driven systems; the type of the system comes through the specific expression for $(\partial R / \partial p_i)$, etc. Consider, for example, a single constraint problem. Then, from Eqs. (8) and (9) we find

$$\frac{dR}{dq} = \left(\frac{\partial R}{\partial q} \right) - \left(\frac{\partial R}{\partial p_1} \right) \left(\frac{\partial p_1}{\partial q} \right) \quad (10)$$

which is of the form of the well-known k-reset sensitivity function. For a doubly constrained problem, Eqs. (8) and (9) give

$$\begin{aligned} \frac{dR}{dq} = & \left(\frac{\partial R}{\partial q} \right) + \left(\frac{\partial R}{\partial p_1} \right) \left[\frac{\left(\frac{\partial F_1}{\partial q} \right) \left(\frac{\partial F_2}{\partial p_2} \right) - \left(\frac{\partial F_1}{\partial p_2} \right) \left(\frac{\partial F_2}{\partial q} \right)}{\left(\frac{\partial F_1}{\partial p_2} \right) \left(\frac{\partial F_2}{\partial p_1} \right) - \left(\frac{\partial F_1}{\partial p_1} \right) \left(\frac{\partial F_2}{\partial p_2} \right)} \right] \\ & + \left(\frac{\partial R}{\partial p_2} \right) \left[\frac{\left(\frac{\partial F_1}{\partial q} \right) \left(\frac{\partial F_2}{\partial p_1} \right) - \left(\frac{\partial F_1}{\partial p_1} \right) \left(\frac{\partial F_2}{\partial q} \right)}{\left(\frac{\partial F_1}{\partial p_2} \right) \left(\frac{\partial F_2}{\partial p_1} \right) - \left(\frac{\partial F_1}{\partial p_1} \right) \left(\frac{\partial F_2}{\partial p_2} \right)} \right] \quad (11) \end{aligned}$$

Its application requires the calculation of 9 unconstrained sensitivity functions, for which one has to solve 3 sets of generalized equations. It can be shown that the corresponding expression obtained from the internal constraint approach [Eq. (7)] can be reduced to an identical form. The internal constraint formulation might need the solution of only one, through more complicated, set of generalized functions.

The CPT enables deriving GPT expressions for reaction rates in homogeneous systems (not possible with unconstrained GPT). Expressing ρ as the product of a shape function ϕ and amplitude f , we construct the functional

$$k[\phi, f, h, q, p] = R[\phi, f, h] - \beta^* (A - \beta B) \phi - f^* [f \langle \Sigma_f \phi \rangle - P_0] - a^* [\langle \phi, \phi \rangle - 1] \quad (12)$$

which accounts for reactivity (through the β^* term) and power level constraints. Following the procedure leading to Eqs. (2) through (7), we find that the resulting CPT for $R = \langle \phi, \phi \rangle$ is the equivalent to the k-reset GPT for a performance parameter of the form of the reaction rate ratio $\langle \phi, \phi \rangle / \langle \phi_f, \phi_f \rangle$.

The CPT presented provides the basis for sensitivity and uncertainty analysis of critical reactors and source-driven systems as part of the design procedure, accounting for any number of realistic constraints. It can also be useful for the design and optimization of nuclear systems.

*Research sponsored by the Electric Power Research Institute.

†On leave from Nuclear Research Center-Negev, Beer-Sheva, Israel and Department of Nuclear Engineering, Ben-Gurion University of the Negev, Beer-Sheva, Israel.

1. C. R. Weisbin et al., Nucl. Sci. Eng. 66, 307 (1978).
2. See, for example, J. H. Marable and C. R. Weisbin, "Uncertainty in the Breeding Ratio of a Large LMFBFR," Proc. Topl. Mtg. Advances in Reactor Physics, Gatlinburg, Tennessee, E. G. Silver, Ed. (Apr. 10-12, 1978).
3. M. L. Williams, Nucl. Sci. Eng. 70, 20 (1979).

3.25. DEVELOPMENTS IN SENSITIVITY THEORY*

D. G. Cacuci E. Greenspan† J. H. Marable M. L. Williams

(Abstract of paper presented at ANS Topical Meeting on Advances in Reactor Physics and Shielding, September 14-17, 1980)

A review of recent developments in sensitivity theory is presented with an emphasis on (a) extensions to new areas such as thermal hydraulics, reactor depletion, multi-constraint and extrema problems, and (b) recent mathematical refinements to and extensions of the basic theory. The diverse new areas of application are discussed from a unified theoretical viewpoint based on nonlinear functional analysis. Several new applications of sensitivity theory are presented for problems in constrained reactor physics calculations, irradiation experiment analysis, reactor burnup calculations, and transient thermal-hydraulic analysis. Future directions of the research are suggested.

*Research sponsored by DOE Office of Reactor Research and Technology and the Electric Power Research Institute.

†On leave from the Nuclear Research Center-Negev, Beer-Sheva, and the Ben-Gurion University of the Negev, Israel.

3.26. RECENT ADVANCES AND APPLICATIONS OF DIFFERENTIAL SENSITIVITY THEORY IN REACTOR SAFETY*

D. G. Cacuci P. J. Maudlin[†] C. V. Parks[†] C. F. Weber[†]

(Abstract of paper to be presented at ANS/ENS International Topical Meeting on Advances in Mathematical Methods for Nuclear Engineering Problems, Munich, West Germany, April 27-29, 1981)

The development of a sensitivity theory based on the use of adjoint functions has progressed significantly since its original application in the fields of reactor physics and shielding. Successes in these areas have created considerable interest in utilizing the methodology for problems in other areas. Nonlinear examples in heat transfer have been among the earliest of such applications. The first investigation in this area was performed by E. M. Oblow, who presented a sensitivity analysis of a simple heat transfer problem. His incipient ideas have since been refined into a comprehensive and rigorous formulation referred to as Differential Sensitivity Theory (DST). Successful applications to complicated thermal problems have indicated that DST can be used in the more complex situations encountered in reactor safety. The general objective of this paper is to review these recent theoretical advances and practical applications, as well as to present some additional results.

* Research sponsored by Reactor Research and Technology.

[†]UCC-ND Computer Sciences Division.

3.27. SENSITIVITY THEORY FOR GENERAL SYSTEMS OF NONLINEAR EQUATIONS*

D. G. Cacuci C. F. Weber[†] E. M. Oblow J. H. Marable

(Abstract of Nucl. Sci. Eng. 75, 28, 1980)

General sensitivity theory is presented for treating problems characterized by systems of nonlinear equations with nonlinear responses. The concept of the Frechet derivative is shown to be fundamental to both differential and variational approaches. These two approaches, unified through the Frechet derivative, form an operator viewpoint of sensitivity theory, leading to identical expressions for the adjoint equations and for the sensitivity functions. Also presented is an alternative sensitivity formalism for systems of nonlinear matrix equations, such as those arising from the application of numerical methods to many practical problems. This approach significantly enlarges the scope and versatility of sensitivity theory as it allows direct treatment of parameters that are purely of numerical-methods origin.

To demonstrate the usefulness and practical applications of both operator and matrix formalisms, a significantly nonlinear transient problem in fast reactor thermal hydraulics is considered. Following the derivation and comparative analysis of the adjoint equations and sensitivity expressions using both formalisms, an extensive sensitivity study for this problem is presented. Conclusions about the future applicability of the general theory are also discussed.

* Research sponsored by the Nuclear Regulatory Commission, Division of Reactor Safety Research.

[†]UCC-ND Computer Sciences Division.

3.28. DIFFERENTIAL SENSITIVITY THEORY FOR NONLINEAR EQUATIONS WITH NONLINEAR RESPONSES*

C. F. Weber[†] D. G. Cacuci E. M. Oblow

(Reprint of Trans. Am. Nucl. Soc. 33, 338, 1979)

The application of differential sensitivity theory to transient nonlinear problems is extended by considering a nonlinear response. It has been shown¹ that for any system governing the behavior of unknown functions and an integral response depending on those unknown functions, a general procedure for this type of sensitivity analysis is to differentiate the response and the system with respect to an arbitrary parameter α . Response dependence on α could be determined by solving this "differentiated system," but to obtain sensitivity information for a large number of parameters it is expedient to use an alternative method. This method computes the solution to a system that is mathematically adjoint to the differentiated system and uses these adjoint functions to calculate the response. Previous work^{1,2} considered only responses that are linearly dependent on the unknown function. It is the objective of this article to demonstrate the successful extension of the theory to a nonlinear response that involves a derivative of the unknown function.

The problem to be considered is a simplified model of a reactor fuel pin and surrounding coolant, as described in Ref. 2. The unknown functions are the fuel rod and coolant temperatures $T = T(r, z, t)$ and $T_c = T_c(z, t)$, respectively. Under given transient conditions, the response to be considered is the maximum linear heat rate (power added to coolant per unit axial length), given by

$$R_1 = 2\pi R_c \left[-k(T) \frac{\partial T}{\partial r} \right]_{(R_c, \bar{z}, \bar{t})} \quad (1)$$

where R_c is the cladding outer radius, and the particular values $\bar{z}$ and $\bar{t}$ are determined from the temperature distribution.

As has been stated, previous studies have been limited to linear integral responses of the form

$$R_2 = 2\pi \iiint f(r, z, t) T(r, z, t) r dr dz dt + \iint g(z, t) T_c(z, t) dz dt \quad (2)$$

where f and g are arbitrary linear weight functions or distributions. Differentiating Eq. (2) with respect to the parameter α yields

$$\frac{dR_2}{d\alpha} = 2\pi \iiint f(r, z, t) \phi(r, z, t) r dr dz dt + \iint g(z, t) \chi(z, t) dz dt \quad (3)$$

where $\phi \equiv \partial T / \partial \alpha$ and $\chi \equiv \partial T_c / \partial \alpha$ represent the implicit response dependence on α through the temperature functions T and T_c , respectively. For sensitivity analysis of such responses the weight functions f and g become source terms in the previously mentioned adjoint system. A similar procedure can be formulated for the response of Eq. (1).

To fit the form of Eq. (2), Eq. (1) can be written

$$R_1 = -2\pi \iiint k[T(r, z, t)] \frac{\partial T}{\partial r} \delta(r - R_c) \delta(z - \bar{z}) \chi \delta(t - \bar{t}) r dr dz dt \quad (4)$$

Differentiating Eq. (4) with respect to the arbitrary parameter α produces the following analog of Eq. (3):

$$\frac{dR_1}{d\alpha} = \frac{\partial R_1}{\partial \alpha} + 2\pi R_c \iiint k_c \delta(r-R_c) \delta(z-\bar{z}) \delta(t-\bar{t}) dr dz dt, \quad (5)$$

where

$$\frac{\partial R_1}{\partial \alpha} = -2\pi \iiint \left(\frac{\partial k}{\partial \alpha} + k \frac{\partial T}{\partial r} \right) \delta(r-R_c) \delta(z-\bar{z}) \delta(t-\bar{t}) r dr dz dt, \quad (6)$$

and use was made of the following identities in deriving the second term on the right-hand side of Eq. (5):

$$\begin{aligned} \int \left(\frac{\partial k}{\partial \alpha} + k \frac{\partial T}{\partial r} \right) \delta(r-R_c) r dr &= \int \frac{\partial(kT)}{\partial r} \delta(r-R_c) r dr \\ &= -k_c \int \delta(r-R_c) dr. \end{aligned}$$

Comparing Eqs. (3) and (5) shows that an appropriate adjoint source term for this problem is

$$f(r, z, t) = \frac{P_c}{r} k_c \delta(r-R_c) \delta(z-\bar{z}) \delta(t-\bar{t}). \quad (7)$$

A computer program was written to compute the unknown temperature functions T and T_1 , and the solutions to the adjoint problem using Eq. (7) as a source term. This program also computed a relative sensitivity coefficient

$$\left(\frac{dR_1/R_1}{d\alpha/\alpha} = \frac{dR_1}{d\alpha} \cdot \frac{\alpha}{R_1} \right)$$

for each important problem parameter. Using these coefficients, a first-order prediction of the response change for a small change in the parameter α is

$$R_1(\alpha + \Delta\alpha) = R_1(\alpha) + \Delta\alpha \frac{dR_1}{d\alpha}(\alpha) = R_1(\alpha) \left[1 + \frac{dR_1/R_1}{d\alpha/\alpha} \cdot \frac{\Delta\alpha}{\alpha} \right]. \quad (8)$$

To validate these sensitivity predictions, the temperature problem was re-solved using perturbed data. The sensitivity coefficients, predictions, and actual perturbed response values are shown in Table 3.28.1 for the response of Eq. (1). As seen in the table, the predicted and recalculated perturbed responses agree very well, even for significant parameter changes of 25%. Thus, as in previous cases with linear responses, the differential sensitivity methodology is useful and applicable to responses containing both nonlinear terms and derivatives.

* Research sponsored by Nuclear Regulatory Commission, Division of Reactor Safety Research.

† UCC-ND Computer Sciences Division.

1. E. M. Oblow, Nucl. Sci. Eng. 6B, 322 (1978).
2. G. F. Webster and E. M. Oblow, "Sensitivity Theory for a Transient Thermal-Hydraulics Problem," ORNL/TM-6900 (October 1979).

Table 3.28.1. Sensitivity Results for the Linear Heat Rate Response
(Original Response = 253.6 W/cm)

Parameter α	$\frac{dR/R}{d\alpha/\alpha}$	$\frac{\Delta\alpha}{\alpha}$	Predicted Response (W/cm)	Recalculated Perturbed Response (W/cm)	Response Ratio ^a
$(T_o)_f$ (initial fuel temperature)	0.9654	0.05	265.8	265.5	0.9989
		0.10	278.1	277.5	0.9979
		0.25	314.8	314.1	0.9978
		-0.10	229.1	229.8	1.0031
h_g (gap conductance)	0.4480	0.05	259.3	259.0	0.9988
		0.10	265.0	264.0	0.9962
		0.25	282.0	277.6	0.9844
		-0.10	242.2	241.8	0.9983
T_{cl} (coolant inlet temperature)	-0.3139	-0.05	257.6	257.4	0.9992
		-0.10	261.6	261.1	0.9981
		-0.25	273.5	272.4	0.9960
		0.10	245.6	246.0	1.0016
k_f (fuel thermal conductivity)	0.2649	0.05	257.0	256.8	0.9992
		0.10	260.3	259.8	0.9981
		0.25	270.4	268.1	0.9915
		-0.10	246.9	246.6	0.9988
Q_f (fuel heat source)	0.2347	0.05	256.6	256.5	0.9996
		0.10	259.6	259.5	0.9996
		0.25	268.5	268.3	0.9993
		-0.10	247.6	247.7	1.0004
w (coolant mass flow rate)	0.0645	0.10	255.2	255.0	0.9992
		0.25	257.7	256.7	0.9961
		-0.10	252.0	251.9	0.9996
$(T_o)_c$ (initial clad temperature)	0.0286	0.25	255.4	255.4	1.0000
		-0.25	251.8	251.8	1.0000
$(\rho C_p)_f$ (fuel density - specific heat)	-0.0185	0.25	252.4	252.6	1.0008
		-0.25	254.1	255.1	1.0012
T_{co} (initial coolant temperature)	0.0183	0.25	254.8	254.8	1.0000
		-0.25	252.4	252.3	0.9996
h_c (coolant-clad heat transfer coefficient)	0.0064	0.25	254.0	253.9	0.9996
		-0.25	253.2	253.1	0.9996

^a (Recalculated Response) : (Predicted Response).

3.29. APPLICATION OF SENSITIVITY THEORY FOR EXTREMA OF FUNCTIONALS TO A TRANSIENT REACTOR THERMAL-HYDRAULICS PROBLEM*

D. G. Cacuci C. F. Weber[†]

(Reprint of Trans. Am. Nucl. Soc. 34, 312, 1980; also summary of paper presented at ANS Topical Meeting on Nuclear Reactor Thermal-Hydraulics, Saratoga, New York, October 6, 1980)

A generalized sensitivity theory based on adjoint functions has been developed recently for systems governed by coupled nonlinear equations and nonlinear responses,¹⁻³ and has been applied successfully to several reactor thermal-hydraulics sample problems. This theory has now been significantly extended to include treatment of a new class of responses which are extrema (in phase-space variables) of functionals of the system's state vector and input parameters. Examples of such responses of great interest in reactor safety and design are the maximum cladding and maximum fuel temperatures. A novel theoretical aspect has to be considered when developing a sensitivity theory for such problems, since changes in the input parameters will induce changes both in the magnitude and in the position in phase space of the response. It is the objective of this article to present a practical application of this theory.

The problem considered here is a simplified model¹ of a reactor fuel rod subjected to a power transient, and surrounded by coolant. Mathematically, this model is represented by a system of coupled nonlinear partial differential equations, whose solutions are the fuel rod and coolant temperatures $T = T(r, z, t)$ and $T_c = T_c(z, t)$, respectively. The response R of interest in this problem is the maximum cladding temperature, i.e.,

$$R(\alpha) = T[r_0(\alpha), z_0(\alpha), t_0(\alpha); \alpha] \\ = \iiint T(r, z, t; \alpha) \delta(r - r_0) \delta(t - t_0) \delta(z - z_0) 2\pi r dr dt dz, \quad (1)$$

where r_0, z_0, t_0 are the coordinates of the point in the (r, z, t) -phase space where the maximum cladding temperature occurs, and α denotes an arbitrary input parameter. Note that, in general, the coordinates r_0, z_0 , and t_0 are themselves functions of α .

A computer program was written to compute the unknown temperature functions T and T_c , and the solution to the adjoint problem^{1,3} with $\delta(r - r_0)\delta(z - z_0)\delta(t - t_0)$ as the adjoint source term. Using the adjoint solutions, the program also computed the sensitivity coefficients $dR/d\alpha$ for each important problem parameter. These sensitivity coefficients were used to predict the response behavior when changes $\Delta\alpha$ occur in these parameters. First-order perturbation analysis predicts that the magnitude of the perturbed maximum cladding temperature is given by

$$R(\alpha + \Delta\alpha) \approx T[r_0(\alpha + \Delta\alpha), z_0(\alpha + \Delta\alpha), t_0(\alpha + \Delta\alpha); \alpha + \Delta\alpha] \\ = R(\alpha) + \frac{dR}{d\alpha} \Delta\alpha + O[(\Delta\alpha)^2] \quad (2)$$

Note here that, when determining $dR/d\alpha$, the term

$$\frac{dt_0}{d\alpha} \iiint T(r, z, t; \alpha) \delta'(t - t_0) \delta(r - r_0) \delta(z - z_0) 2\pi r dr dt dz = 0 \quad (3)$$

in view of well-known properties of $\delta'(t - t_0)$ and the definition of an extremum. Similar results hold for the terms involving $\delta'(r - r_0)$ and $\delta'(z - z_0)$, respectively.

As previously mentioned, changes $\Delta\alpha$ around α also induce changes in the position in phase space of the perturbed maximum. For the present sample problem, the changes in the coordinates r_0 and z_0 are negligible. However, noticeable changes occur in the time coordinate t_0 . It can be shown that, to first order, the coordinate $t_0(\alpha+\Delta\alpha)$ of the perturbed maximum $R(\alpha+\Delta\alpha)$ is given by

$$t_0(\alpha+\Delta\alpha) = t_0(\alpha) + \frac{dt_0}{d\alpha} \Delta\alpha + O[(\Delta\alpha)^2] \quad (4)$$

where

$$\frac{dt_0}{d\alpha} = - \left[\frac{\frac{\partial}{\partial t} \left(\frac{dR}{d\alpha} \right)}{\frac{\partial^2 R}{\partial t^2}} \right] [r_0(\alpha), z_0(\alpha), t_0(\alpha)] \quad (5)$$

To validate these sensitivity predictions, the sample problem was re-solved using perturbed data. The sensitivity coefficients, magnitude predictions, and actual magnitude of the perturbed maximum are shown in Table 3.29.1. As seen in the table, the predicted and recalculated magnitudes of the perturbed maximum agree very well.

The most important sensitivity results concerning the "time coordinate" $t_0(\alpha)$ of the maximum cladding temperature are presented in Table 3.29.2. Again, the predictions are close to the recalculated perturbed values of t_0 , even though the nonlinearities are more pronounced. The results presented in Table 3.29.2 show that an increase in the gap conductance causes the perturbed maximum cladding temperature to occur sooner (in time), while an increase in the inlet coolant temperature delays this occurrence.

In conclusion, the results of this study validate the new sensitivity theory for nonlinear problems with extrema of functionals as responses.

*Research sponsored by the Nuclear Regulatory Commission, Division of Reactor Safety and Research.

†UCC-ND Computer Sciences Division.

1. D. G. Cacuci, C. F. Weber, E. M. Oblow, and J. H. Marable, "Generalized Sensitivity Theory for Systems of Coupled Nonlinear Equations," ORNL/NUREG/TM-349 (January 1980).
2. C. F. Weber, D. G. Cacuci, and E. M. Oblow, "Differential Sensitivity Theory for Nonlinear Equations with Nonlinear Responses," Trans. Am. Nucl. Soc. 33, 338 (1979).
3. D. G. Cacuci, C. F. Weber, E. M. Oblow, and J. H. Marable, "Sensitivity Theory for General Systems of Nonlinear Equations," article submitted to Nuclear Science & Engineering.

Table 3.22.1. Maximum Cladding Temperature Response Sensitivity Results
Unperturbed Response $R(\alpha) = 568^\circ\text{C}$

Parameter (α)	Sensitivity ^c	$\frac{\Delta\alpha}{\alpha}$ (%)	Predicted Perturbed Response ^b	Recalculated Perturbed Response ^b
Fuel outer radius	4.4670	+1	594	600
		-1	543	546
Gap outer radius	-4.4123	+1	543	547
		-1	593	599
Inlet coolant temperature	0.5239	+10	598	598
		+25	643	643
Coolant mass flow rate	-0.2602	-5	576	576
		-10	583	584
		-25	605	616
		+10	553	555
Gap width (at constant clad thickness)	-0.1426	+25	548	550
		-25	588	593
Gap conductance	0.1421	+5	572	572
		+10	576	576
		+25	588	587
		-10	560	560
Fuel heat source	0.0632	+10	572	572
		+25	577	578
		-10	565	565
Clad outer radius	0.0568	+5	570	569
		-5	567	567
Coolant-clad heat transfer coeff.	0.0033	-25	569	569
		+25	568	568
Axial discretization parameter	-0.2170	+10	556	557
		-10	581	581
Time discretization parameter	-0.00002	+10	568	568
		-10	568	568

^cRelative Sensitivity $\frac{dR/R}{d\alpha/\alpha}$

^bPredicted Perturbed Response = $R(\alpha) + \Delta\alpha \frac{dR}{d\alpha}$

^bRecalculated Perturbed Response = $R(\alpha + \Delta\alpha)$

Table 3.29.2. Sensitivity Results for $t_0(a)$ for $R(a) =$
Maximum Cladding Temperature

[Unperturbed Response Occurred at $t_0(\cdot) = 0.825s$]

Parameter (a)	$\frac{dt_0}{da}$	$\frac{\Delta t_0}{\Delta a}$ (%)	Predicted Perturbed $t_0(a)^c$	Recalculated Perturbed $t_0(a)^d$
Inlet coolant temperature	0.3485	10	0.860	0.872
Gap conductance	-0.3020	10	0.795	0.787
Coolant mass flow rate	-0.0930	10	0.816	0.814

^cPredicted Perturbed "time coordinate" $t_0(a+\Delta a)$

$$= t_0(a) + \frac{dt_0}{da} \Delta a.$$

^dRecalculated Perturbed "time coordinate" $t_0(a+\Delta a)$.

3.30. A SYSTEMATIC METHODOLOGY FOR THE REDUCTION OF UNCERTAINTIES IN TRANSIENT THERMAL-HYDRAULICS BY USING IN-BUNDLE MEASUREMENT DATA*

J. Barhen D. G. Cacuci J. J. Wagschal[†] C. B. Mullins

(Abstract of paper presented at AHS Topical Meeting, Advances in Reactor Physics
and Shielding, San Valley, Idaho, September 14-17, 1980)

The development of a systematic methodology for the reduction of uncertainties in transient thermal-hydraulics by using in-bundle measurement data is presented. The adjustment of the system parameters and responses and the reduction in their respective uncertainties is treated as a time-dependent constrained minimization problem. An on-line (i.e., real time) large scale optimization scheme is also outlined. Although formulated within the framework of reactor safety analysis, the proposed methodology can be directly applied to other areas, for instance to time-dependent fuel cycle optimization and uncertainty analysis.

* Research sponsored by U.S. Nuclear Regulatory Commission, Division of Reactor Safety Research.

[†] On leave from The Hebrew University, Jerusalem, Israel.

3.31. GENERALIZED SENSITIVITY THEORY APPLIED TO THE SPACE AND TIME DEPENDENT THERMAL-HYDRAULICS CONSERVATION EQUATIONS*

P. J. Maudlin[†] C. V. Parks[†] C. F. Weber[†]

(Summary of paper presented at 1980 Annual Meeting of American Nuclear Society,
Mechanical Engineering, Chicago, Illinois, November 16-21, 1980)

The application of various sophisticated sensitivity theories¹⁻⁴ to large thermal-hydraulic computer codes is very beneficial to the model developer, the analyst, and the experimentalist. The model developer can use sensitivity theory to identify the important modeling parameters, and also to verify computer solutions. The analyst can use sensi-

tivity theory to significantly reduce the computational effort required to obtain sensitivity coefficients: instead of re-running a computer code to obtain a coefficient for a single input parameter, as few as two runs can provide sensitivities to all input parameters. The experimentalist can use sensitivity theory in conjunction with uncertainty theory to identify the important experimental parameters, thus yielding valuable information in the design or modification of experimental hardware.

This work describes an application of a differential sensitivity theory, introduced by Usachev⁵ and later developed by Oblow³ and Cacuci,⁴ called Generalized Sensitivity Theory (GST). The application of GST to the thermal-hydraulics conservation equations involves the development and solution of equations that are adjoint to the conservation or forward equations differentiated with respect to an arbitrary modeling parameter α . The forward and adjoint solutions are then integrated together to provide the sensitivity coefficient $\frac{dR/R}{d\alpha/\alpha}$, where R is the response function (e.g., a peak or average temperature, pressure, or velocity). The main advantage of GST is that sensitivities for a large input parameter field can be obtained from the information provided by only two computer code runs: a forward base case and its corresponding adjoint.

Single-phase conservation equations for mass, momentum and thermal energy in time and three-dimensional space are

$$\frac{D\rho}{Dt} = -\rho \nabla \cdot \vec{V}, \quad (1a)$$

$$\rho \frac{D\vec{V}}{Dt} = -\nabla P - \nabla \cdot \tau + \rho \vec{g}, \quad (1b)$$

$$\rho C_p \frac{DT}{Dt} = -\nabla \cdot \vec{q} - \tau : \nabla \vec{V} + \rho (\vec{V} \cdot \vec{g}) + Q, \quad (1c)$$

where the velocity $\vec{V}$, pressure P , and temperature T are considered the dependent variables (see Ref. 6 for a description of notation). All other quantities in Eqs. (1) are assumed to be functions of $\vec{V}$, P or T .

Assuming a response function of the form

$$R = \int_V \int_t F[T(\vec{r}, t), P(\vec{r}, t), \vec{V}(\vec{r}, t)] d\vec{r} dt, \quad (2)$$

where F can include delta or unit step functions to yield a peak or average temperature, pressure, or velocity response, the adjoint equations corresponding to Eqs. (1) can be shown to be

$$-\rho \nabla \cdot \vec{V}^* = \frac{D}{Dt}(\rho P^*) + \rho P^* \nabla \cdot \vec{V} + \vec{\Omega} + T^* [\rho C_p \nabla T + \nabla \cdot \tau : \nabla \vec{V}] - \nabla \cdot (T^* \tau^T) + \vec{F}_V^*, \quad (3a)$$

$$-\nabla \cdot \vec{P}^* = F_P, \quad (3b)$$

$$-\rho C_p \frac{DT^*}{Dt} - \rho C_p T^* \nabla \cdot \vec{V} - k \nabla^2 T^* - T^* \left[\frac{\partial \rho}{\partial T} \vec{g} \cdot \vec{V} - \frac{\partial \tau}{\partial T} : \nabla \vec{V} \right] + \frac{\partial \rho}{\partial T} \left[\frac{D\vec{V}}{Dt} - \frac{D\vec{V}}{Dt} \cdot \vec{P}^* \right] + \vec{g} \cdot \vec{P}^* - \frac{\partial (T^* \tau^T)}{\partial T} : \nabla \vec{P}^* + F_T. \quad (3c)$$

The components of $\vec{\Omega}$ and $\nabla_{\vec{V}}$ are defined as

$$\Omega_i \equiv \rho P^* \cdot \frac{\partial \vec{V}}{\partial x_i} - \frac{\partial (T^* \tau^T)}{\partial V_i} : \nabla \vec{P}^*, \quad (3d)$$

$$\nabla_{\vec{V}} \equiv \frac{\partial}{\partial V_i}. \quad (3e)$$

and $\vec{F}_v = (F_{v_1}, F_{v_2}, F_{v_3})$, F_p , F_T are partial derivatives of F with respect to velocity components, pressure or temperature.

The mathematical form of the sensitivity coefficients for any parameter appearing in Eq. (1) falls out of the derivation of the adjoint equations. For example, the sensitivity of the peak temperature to the heat generation rate, Q , is

$$\frac{d(T_{\max})}{dQ/Q} = \int_t^{\infty} \int_V T^* Q d\vec{r} dt. \quad (4)$$

Once the forward and adjoint solutions have been obtained, all quantities on the right side of Eq. (4) are known. Sensitivity coefficients for all other parameters appearing in Eqs. (1) can be easily calculated in an analogous manner. Full details of the derivation of Eq. (3), along with adjoint boundary conditions, initial conditions, and sensitivity coefficients will be presented in the full paper. Also included will be a two-dimensional space and time numerical example, and discussion of several realistic computer code applications presently underway.

*Research sponsored by the DOE Division of Nuclear Research and Applications.

†UCC-ND Computer Sciences Division.

1. M. D. McKay, J. W. Bolstad, and D. E. Whitman, "An Application of Statistical Techniques to the Analysis of Reactor Safety Codes," Proc. of the National Topical Meeting on Probabilistic Analysis of Nuclear Reactor Safety, Los Angeles, California (May 1978).
2. J. K. Vario, J. M. Kyser and L. Myne, "Statistical Sensitivity Analysis of a Safety Evaluation Code," Proc. of the International Meeting on Fast Reactor Safety Technology, 1, 59, Seattle, Washington (1979).
3. E. M. Obloy, "Sensitivity Theory for Reactor Thermal-Hydraulics Problems," Nucl. Eng. 68, 322 (1978).
4. D. G. Cacuci, C. F. Weber, E. M. Obloy and J. H. Marable, "Sensitivity Theory for General Systems of Nonlinear Equations," Nucl. Sci. Eng., in press (1980).
5. L. M. Usachev, "Perturbation Theory for the Breeding Ratio and for Other Number Ratios Pertaining to Various Reactor Processes," J. Nucl. Energy, Pts. a/B 18, 571 (1964).
6. R. B. Bird, W. E. Stewart, and E. N. Lightfoot, Transport Phenomena, Wiley & Sons, Inc., New York (1960).

3.32. APPLICATIONS OF DIFFERENTIAL SENSITIVITY THEORY FOR PROBLEMS WITH DISCONTINUITIES*

C. F. Weber[†] D. G. Cacuci C. V. Parks[†]

(Reprint of Trans. Am. Nucl. Soc. 34, 1980)

The application of sensitivity theory using adjoint functions is considered for reactor safety problems involving various types of data discontinuities. Although applications to nonlinear problems have been demonstrated,^{1,5} some doubts still remain concerning the usefulness of this sensitivity methodology for reactor safety analysis. Problems involving pronounced nonlinearities or discontinuities (e.g., phase changes) are most often cited as possible examples that are not amenable to treatment by this method. It is the purpose of this paper to demonstrate that, in fact, differential sensitivity analysis is both possible

and useful for certain parameters arising in the discontinuous data behavior often encountered in reactor safety problems.

The first problem to be considered is a simplified model of an LMF fuel pin and surrounding coolant, as described in Ref. 4. The unknown functions are the fuel rod and coolant temperatures $T = T(r, z, t)$ and $T_c = T_c(z, t)$, respectively. Transient conditions are obtained by imposing a power variation and by simulating the onset of critical heat flux (CHF) followed by reflood. This simulation is obtained by employing a discontinuous, piecewise constant representation of the coolant-cladding heat transfer coefficient

$$h_c(t) = \begin{cases} h_1 & 0 \leq t < t_1 \\ h_2 & t_1 \leq t < t_2 \\ h_3 & t_2 \leq t \end{cases} \quad (1)$$

Equation (1) can also be written as

$$h_c(t) = h_1 H(t_1 - t) + [H(t - t_1) - H(t - t_2)]h_2 + H(t - t_2)h_3, \quad (2)$$

where H is the Heaviside step function.

Letting α represent any of the parameters in Eq. (2), it can be shown⁴ that the sensitivity derivative of an integral response R with respect to α is

$$\frac{dR}{d\alpha} = -2R_c \int_t \int_z \frac{\partial h_c}{\partial \alpha} [(T - T_c)(\phi - \phi_c)] r = R_c dz dt, \quad (3)$$

where R_c = cladding outer radius, and ϕ, ϕ_c = adjoint functions for the fuel rod and coolant, respectively. Differentiating Eq. (2) (in the distributional sense) with respect to h_1 , h_2 , or t_1 , and substituting for $\partial h_c / \partial \alpha$ in Eq. (3) yields the relative sensitivity coefficients appearing in Table 3.32.1 for $\alpha = h_1, h_2, t_1$.

Table 3.32.1. Simulation of Critical Heat Flux
R = Peak Cladding Temperature Response = 1017°C

Parameter (α)	$\frac{dR/R}{d\alpha/\alpha}$	$\frac{\Delta\alpha}{\alpha}$ (%)	Predicted Perturbed Response (°C)	Recalculated Perturbed Response (°C)
h_1	-0.0028	-10	1017	1017
h_2	-0.0255	-10	1020	1019
t_1	-0.0696	-10	1024	1024

As in earlier work,¹⁻⁵ a first-order perturbation analysis was used to verify these results. Each sensitivity coefficient was used to predict the new values of the response that would result if the parameter were changed by -10%, yielding entries in the column headed "Predicted Perturbed Response." Direct recalculation using perturbed parameters yielded entries in the column "Recalculated Perturbed Response." As seen in the table, both predicted and recalculated responses agree closely, giving confidence in the validity of the sensitivity coefficients.

In the first problem, the discontinuity occurred in a function of the independent variable t . As an example of a discontinuity occurring in a function of a dependent variable, consider the problem of determining the steady-state temperature distribution of a fast reactor fuel pin and coolant when fuel restructuring occurs. As modeled in the safety analysis code MELT-IIIA,⁶ the fuel restructures if its temperature is above a given value $T = \bar{T}$, creating a discontinuous change in the physical properties of the fuel. In particular, the thermal conductivity assumes the general form

$$k(T) = \begin{cases} k_1(T) & T < \bar{T} \text{ (unrestructured)} \\ k_2(T) & T > \bar{T} \text{ (restructured)} \end{cases},$$

which can be rewritten as

$$k(T) = k_1(T)H(\bar{T} - T) + k_2(T)H(T - \bar{T}) \quad (4)$$

For an integral response R and a parameter α occurring in the thermal conductivity, the response sensitivity derivative for this problem is

$$\frac{dR}{d\alpha} = -2\pi \int_z \int_r \frac{\partial k}{\partial \alpha} \frac{\partial T}{\partial r} \frac{\partial \phi}{\partial r} r dr dz, \quad (5)$$

where, as before, $\phi = \phi(r, z)$ represents the adjoint function in the fuel rod. Letting $\bar{k}_1$ and $\bar{k}_2$ denote scale factors of $k_1(T)$ and $k_2(T)$, respectively, Eq. (4) is differentiated with respect to $\bar{k}_1$, $\bar{k}_2$, or $\bar{T}$ and substituted into Eq. (5) to obtain sensitivity coefficients for the parameters $\alpha = \bar{k}_1, \bar{k}_2, \bar{T}$. These coefficients appear in Table 3.32.2 along with the results of a perturbation analysis. As in the first example, recalculated results using perturbed data agree favorably with the sensitivity predictions, thus validating both the sensitivity coefficients and the theory in general.

Table 3.32.2. Sensitivity to Thermal Conductivity Parameters
R = Peak Fuel Temperature Response = 2777K

Parameter (α)	$\frac{dR/R}{d\alpha/\alpha}$	$\frac{\Delta\alpha}{\alpha}$ (%)	Predicted Perturbed Response (K)	Recalculated Perturbed Response (K)
$\bar{k}_1$	-0.1512	10	2725	2726
		-10	2819	2832
$\bar{k}_2$	-0.1876	10	2735	2732
		-10	2829	2833
$\bar{T}$	0.1260	5	2794	2794
		10	2812	2804
		-5	2760	2758
		-10	2742	2746

*Research sponsored by Nuclear Regulatory Commission, Division of Reactor Safety Research.

†UCC-ND Computer Sciences Division.

1. D. G. Cacuci, C. F. Weber, E. M. Oblow, and J. H. Marable, "Sensitivity Theory for General Systems of Nonlinear Equations," submitted for publication to Nucl. Sci. Eng.
2. D. G. Cacuci, C. F. Weber, E. M. Oblow, and J. H. Marable, "Generalized Sensitivity Theory for Systems of Coupled Nonlinear Equations," ORNL/NUREG/TM-349, Oak Ridge National Lab. (1980).
3. E. M. Oblow, Nucl. Sci. Eng., 68, 322 (1978).
4. C. F. Weber and E. M. Oblow, "Sensitivity Theory for a Transient Thermal-Hydraulics Problem," ORNL/TM-6900, Oak Ridge National Lab. (1979).
5. C. F. Weber, D. G. Cacuci, and E. M. Oblow, Trans. Am. Nucl. Soc. 33, 338 (1979).
6. A. E. Waltar et al., "MELT-III, A Neutronics, Thermal-Hydraulics Computer Program for Fast Reactor Safety Analysis," Vol. 1, HEDL-TME 74-47, Hanford Engineering Development Lab. (1974).

3.33. AN EFFICIENT PROCEDURE TO EVALUATE SECOND-ORDER SENSITIVITIES FOR NONLINEAR PROBLEMS WITH NONLINEAR RESPONSES*

J. Berhen D. G. Cacuci

(Reprint of Trans. Am. Nucl. Soc. 35, 266-267, 1980)

In sensitivity and uncertainty analyses of markedly nonlinear system responses, the evaluation of the Hessian matrix of second-order derivatives of the response R with respect to the system's input parameters $\bar{\alpha}$ becomes of crucial importance. For example, the Hessian is needed even for a task as simple (in principle) as determining the expectation value of the nonlinear response.¹

Currently, the two classes of most widely used techniques for estimating second-order derivatives are the "brute force" methods, and statistical methods most often labeled as "response surface" methods. In the "brute force" technique, the input parameters are varied individually and in pairs, and the resulting values of R (assumed to be quadratic in $\bar{\alpha}$) are used to obtain approximate values for $\partial^2 R / \partial \alpha_i \partial \alpha_j$. Engineering judgment must be used to drastically limit the number of $\partial^2 R / \partial \alpha_i \partial \alpha_j$ that are actually computed, since to compute all of them is prohibitively expensive [it would require $N(N+3)/2 + 1$ runs, where N is the number of input parameters]. The number of computer runs required by the "response surface" methods is also very large. Various sophisticated statistical techniques are being used to reduce the number of runs; this necessarily introduces limitations in the number of $\partial^2 R / \partial \alpha_i \partial \alpha_j$ that are estimated, as well as approximations regarding their estimated values. For example, even a resolution IV star-point design² is incapable of estimating all cross-derivatives of a quadratic approximation of the response. It has also been pointed out³ that statistical methods yield no confidence limits on sensitivities (i.e., $\partial R / \partial \alpha_i$, $\partial^2 R / \partial \alpha_i \partial \alpha_j$) except via addition of significant prior knowledge.

The purpose of this article is to present an efficient and economical procedure to estimate the Hessian $H(\bar{\alpha}_0)$ of the response R . For this purpose, consider the following Taylor expansion of $R(\bar{\alpha})$ around $\bar{\alpha}_0$ (the base case configuration of the vector of N input parameters):

$$R(\bar{\alpha}) = R(\bar{\alpha}_0) + (\bar{\alpha} - \bar{\alpha}_0)^T S(\bar{\alpha}_0) + \frac{1}{2} (\bar{\alpha} - \bar{\alpha}_0)^T H(\bar{\alpha}_0) (\bar{\alpha} - \bar{\alpha}_0) + O(\|\bar{\alpha} - \bar{\alpha}_0\|^3), \quad (1)$$

where $\bar{\alpha} = (\alpha_1, \dots, \alpha_N)^T$ represents any new configuration of the N input parameters. Interchanging now the roles of $\bar{\alpha}$ and $\bar{\alpha}_0$ in Eq. (1) gives

$$R(\bar{\alpha}_0) = R(\bar{\alpha}) + (\bar{\alpha}_0 - \bar{\alpha})^T S(\bar{\alpha}) + \frac{1}{2} (\bar{\alpha}_0 - \bar{\alpha})^T H(\bar{\alpha}) (\bar{\alpha}_0 - \bar{\alpha}) + O(\|\bar{\alpha}_0 - \bar{\alpha}\|^3). \quad (2)$$

Adding Eqs. (1) and (2), and neglecting higher order terms, yields

$$\bar{S}(\bar{\alpha}_0) - \bar{S}(\bar{\alpha}) + \frac{1}{2} [H(\bar{\alpha}_0) + H(\bar{\alpha})](\bar{\alpha} - \bar{\alpha}_0) = 0, \quad (3)$$

by forcing $(\bar{\alpha} - \bar{\alpha}_0) \neq 0$ not to be orthogonal to the left-hand side of Eq. (3).

Let J_N denote the set of integers $\{1, 2, \dots, N\}$. Select now a series of configurations $\bar{\alpha}_i$, $i \in J_N$, and a very small positive number δ such that $\|H(\bar{\alpha}_i) - H(\bar{\alpha}_0)\| \leq c \|\bar{\alpha}_i - \bar{\alpha}_0\|^p$ is satisfied in the ball $\|\bar{\alpha}_i - \bar{\alpha}_0\| \leq r$ [where $c > 0$, $p \in (0, 1)$, and $cr^p = \delta$]. Evaluating Eq. (3) at each $\bar{\alpha}_i$ [where $H(\bar{\alpha}) = H(\bar{\alpha}_0)$], gives

$$\Delta \bar{S}_i = H(\bar{\alpha}_0) \Delta \bar{\alpha}_i, \quad i \in J_N, \quad (4)$$

where $\Delta \bar{\alpha}_i \equiv \bar{\alpha}_i - \bar{\alpha}_0$ and $\Delta \bar{S}_i \equiv \bar{S}_i - \bar{S}_0$.

An algorithm has been developed to compute $H_0(\bar{\alpha}_0)$ assuming $\Delta \bar{\alpha}_i$ and $\Delta \bar{S}_i$ to be known. For example, $\Delta \bar{S}_i$ can be calculated exactly and efficiently (one computer run per response) by employing the concepts of sensitivity theory for nonlinear systems.⁴ Inversion of matrices is avoided in our algorithm by introducing the matrix A_i defined as

$$A_i \cdot \Delta \bar{\alpha}_j = H(\bar{\alpha}_0) \cdot \Delta \bar{\alpha}_j, \quad j \in J_{i-1}. \quad (5)$$

Equation (5) is separated into two groups:

$$A_i \cdot \Delta \bar{\alpha}_j = H(\bar{\alpha}_0) \Delta \bar{\alpha}_j, \quad j \in J_{i-2} \quad (6)$$

and

$$A_i \Delta \bar{\alpha}_{i-1} = H(\bar{\alpha}_0) \Delta \bar{\alpha}_{i-1}. \quad (7)$$

Writing Eq. (5) for the stage $(i-1)$ and subtracting it from Eq. (6) shows that

$$\Delta A_{i-1} \Delta \bar{\alpha}_j = 0, \quad j \in J_{i-2}, \quad (8)$$

where the "updating matrix" ΔA_{i-1} has been defined as

$$\Delta A_{i-1} = A_i - A_{i-1}. \quad (9)$$

Substituting Eqs. (4) and (9) in Eq. (7) gives

$$\Delta A_{i-1} \Delta \bar{\alpha}_{i-1} = \Delta \bar{S}_{i-1} - A_{i-1} \Delta \bar{\alpha}_{i-1}. \quad (10)$$

A rank-one solution of Eq. (10) takes the form

$$\Delta A_{i-1} = \frac{(\Delta \bar{S}_{i-1} - A_{i-1} \Delta \bar{\alpha}_{i-1})(\Delta \bar{S}_{i-1} - A_{i-1} \Delta \bar{\alpha}_{i-1})^T}{(\Delta \bar{S}_{i-1} - A_{i-1} \Delta \bar{\alpha}_{i-1})^T \Delta \bar{\alpha}_{i-1}}. \quad (11)$$

The additional requirement that the set $\{\Delta \bar{\alpha}_i | i \in J_N\}$ forms an orthogonal base in the N -dimensional space is now imposed. This guarantees that

$$A_N + \Delta A_N = H(\bar{\alpha}_0), \quad (12)$$

where A_N and ΔA_N are obtained recursively from Eqs. (9) and (11), respectively.

The methodology presented here has been applied to experiment 3.036AR,⁵ a transient nonlinear thermal-hydraulics experimental problem design for acquisition of transient film boiling data. This experiment is one in a series of experiments performed within

the ORNL PWR-BDHT Separate Effects Program.⁶ The highly nonlinear response selected here was the mass flow at junction 11 of the THTF⁵ test section at 1.15 s after initiation of blowdown; at this time, water quality departs from zero in this subvolume due to flow decrease and power surge. The pertinent information needed to apply the proposed methodology is given in Table 3.33.1. Also given in this table are the results (labeled "Predicted Hessian") obtained by applying the proposed methodology. To validate these results, the Hessian was recomputed (exactly) by direct calculations; these values are labeled "Recalculated Hessian." As seen in Table 3.33.1 the "predicted" and "recalculated" values agree very well; this gives confidence in the general applicability of the proposed methodology.

Important conclusions from this study include:

1. A methodology for evaluating, at little cost, the Hessian matrix of second-order sensitivities has been developed.
2. Since the first-order sensitivities (obtained efficiently by employing sensitivity theory^a) are all that is needed, the maximum potential of the proposed methodology is exploited when applied to problems involving a large number of input parameters and relatively few responses. Presently, prohibitive costs pose nearly insurmountable difficulties when applying direct methods to such problems.
3. The method has been shown to be applicable to highly nonlinear problems and responses; for such problems, a competitive alternative (such as a second-order adjoint-based sensitivity theory) has not yet been formulated.

Table 3.33.1. Computation of Second-Order Sensitivities for a Transient Thermal-Hydraulic Example^a

Input Parameters ^b	Response ^c	Sensitivities
$\bar{\alpha}_0 = \begin{pmatrix} 20.1005 \\ 1460.98 \end{pmatrix}$	$R = 23.5358$	$\bar{S}_0 = \begin{pmatrix} -4.0966 \\ -0.23787 \end{pmatrix}$
Input Variations ^d	Sensitivity Variations	
$\Delta \bar{\alpha}_1 = \begin{pmatrix} 0.3709 \\ 0.0 \end{pmatrix} \quad \Delta \bar{\alpha}_2 = \begin{pmatrix} 0.0 \\ 8.0 \end{pmatrix}$	$\bar{S} = \begin{pmatrix} 0.75120 \\ 0.21505 \end{pmatrix}$	$\bar{S} = \begin{pmatrix} 4.6386 \\ 0.04907 \end{pmatrix}$
Predicted Hessian	Recalculated Hessian	
$\begin{pmatrix} 2.0253 & 0.57979 \\ 0.57979 & 0.006135 \end{pmatrix}$	$\begin{pmatrix} 2.0255 & 0.57432 \\ 0.57432 & 0.006134 \end{pmatrix}$	

^aORNL-PWR Blowdown Experiment 3.036AR.⁵

^b α_0^1 = inlet mass flow.

^c α_0^2 = outlet pressure.

^d R = mass flow at junction 11 of the reactor test section, 1.15 s after break.

^e $\Delta \alpha_k$ represents one standard deviation of corresponding input parameter.

*Research sponsored by Electric Power Research Institute.

1. Y. Ronen, M. A. Bjerke, and D. G. Cacuci, "Nonlinear Sensitivity and Uncertainty Analysis for the BDHT Program," ORNL/TM-7399, Oak Ridge National Lab. (1980); see also, F. G. Perey, "Introduction to the Theory of Logical Inference and Application to Nuclear Data Uncertainties," to be published, Pergamon Press; Private Communication (1980).
2. D. J. Varacalle et al., "Local Conditions and Uncertainty Band Calculations for Semi-scale Test S-02-9," COTAP-TR-048, EG&G Idaho (Jan. 1979).
3. C. R. Weisbin and R. G. Alsmiller, "Highlights of the ORNL Model Evaluation Methodology and the Evaluation of LEAP," to be presented at symposium, "Energy Modeling III: Dealing with Energy Uncertainty," Chicago (Aug. 4-8, 1980).
4. D. G. Cacuci et al., "Generalized Sensitivity Theory for Systems of Coupled Nonlinear Equations," NUREG/CR-1003 (ORNL/NUREG/TM-349) (Jan. 1980).
5. C. B. Mullins et al., ORNL/BDHT-2430 (June 1980).
6. A primary objective of the Oak Ridge National Laboratory PMR-PDHT program is to obtain information for use in developing models to determine the margin of safety extant in the design of PWRs and, in particular, the calculation of transient heat transfer coefficients. For additional details, see: W. G. Craddock et al., ORNL/NUREG-45 (Sep. 1978); see also, ORNL/NUREG/TM-303 to 306 (June 1980).

CROSS-SECTION ADJUSTMENT AND ANALYSIS OF INTEGRAL EXPERIMENTS

3.34. ORACLE: AN ADJUSTED CROSS-SECTION AND COVARIANCE LIBRARY FOR FAST-REACTOR ANALYSIS*

Y. Yeivin[†] J. H. Marable C. R. Weisbin J. J. Wagschal[†]

(Abstract of paper presented at ANS Topical Meeting on Advances in Reactor Physics and Shielding, Sun Valley, Idaho, September 11-17, 1980)

Integral-experiment responses for six benchmark fast critical-reactor assemblies and two standard neutron fields are combined with corresponding ENDF/B-V-calculated responses in a least-squares data adjustment using evaluated covariances from ENDF/B-V and supporting covariance evaluations. The purpose is to produce an adjusted cross-section and covariance library which is based on well-documented data and methods and which is suitable for fast-reactor design. By use of such a library, data- and methods-related biases of calculated performance parameters should be reduced and uncertainties of the calculated values minimized. Consistency of the extensive data base is analyzed using the chi-square test. This adjusted library, ORACLE, will be available shortly. Feedback from designers, evaluators, experimentalists, and analysts is solicited.

* Research sponsored by DOE Office of Reactor Research and Technology.

[†] On leave from The Hebrew University, Jerusalem, Israel.

3.35. THE ADJUSTMENT OF CROSS SECTIONS BASED ON INTEGRAL EXPERIMENTS IN FAST BENCHMARK ASSEMBLIES*

J. H. Marable

(Abstract of paper presented at Workshop on Evaluation Methods and Procedures, Brookhaven National Laboratory, September 22-25, 1980)

The adjustment of multigroup cross sections using fast benchmark integral experiments is reviewed. The question of whether such adjustments lead to actual improvements in differential data or only to the determination of parameters in an artificial mathematical model is discussed. Data bases required for adjustment are also discussed, and the concept of calculated-response correctors (calculational biases) based on modeling and calculational approximations is presented. Linear and nonlinear adjustments are illustrated graphically. The need for careful examination of both input and output data, application of the χ^2 -test, and confrontation with evaluators and experimentalists for feedback is emphasized. Applications based on ENDF/B-IV and ENDF/B-V are discussed. It is pointed out that in addition to being a practical tool for creating libraries incorporating integral experiment information, in addition to the possibility of leading to improved nuclear data, least squares adjustment is required for the understanding of the complex of differential nuclear data, integral data, reactor modeling, cross section processing, analysis and calculational methods.

* Research sponsored by DOE Office of Reactor Research and Technology.

3.36. CROSS SECTION ADJUSTMENT APPLIED TO ESTIMATION OF UNCERTAINTY IN THE BREEDING RATIO OF AN LMFBR*

J. H. Marable C. R. Weisbin G. de Saussure

(Abstract of paper in Nuclear Cross Sections for Technology, NBS Special Publication 594, p. 177, 1980)

Eleven fast-reactor benchmark experiments and two neutron-field benchmark experiments were applied to a least-squares adjustment of a 26-group cross section library based primarily on ENDF/B-IV. The covariance data includes correlations between cross sections for different energies, reactions, and materials, and between integral experiments, and covariances of calculational bias factors due to specific modeling and calculational procedures. The results of the adjustment are applied to the determination of the uncertainties in the multiplication factor and in the breeding ratio of a large LMFBR design model fixed by the Large Core Code Evaluation Working Group (LCCSWG).

* Research sponsored by DOE Office of Reactor Research and Technology.

3.37. SPECIFICATIONS FOR ADJUSTED CROSS SECTION AND COVARIANCE LIBRARIES BASED UPON CSEWG FAST REACTOR AND DOSIMETRY BENCHMARKS*

C. R. Weisbin
J. H. Marable
P. J. Collins[§]

C. L. Cowan[†]
R. W. Peele[‡]
M. Salvatores[‡]

(Abstract of ORNL-5517, June, 1979)

The present work proposes a specific plan of cross-section library adjustment for fast reactor core physics analysis using information from fast reactor and dosimetry integral experiments and from differential data evaluations. This detailed exposition of the proposed approach is intended mainly to elicit review and criticism from scientists and engineers in the research, development, and design fields. This major attempt to

develop useful adjusted libraries is based on the established benchmark integral data, accurate and well-documented analysis techniques, sensitivities, and quantified uncertainties for nuclear data, integral experiment measurements, and calculational methodology. The adjustments to be obtained using these specifications are intended to produce an overall improvement in the least-squares sense in the quality of the data libraries, so that calculations of other similar systems using the adjusted data base with any credible method will produce results without much data-related bias. The adjustments obtained should provide specific recommendations to the data evaluation program to be weighed in the light of newer measurements, and also a vehicle for observing how the evaluation process is converging.

This report specifies the calculational methodology to be used, the integral experiments to be employed initially, and the methods and integral experiment biases and uncertainties to be used. The sources of sensitivity coefficients, as well as the cross sections to be adjusted, are detailed. The formulae for sensitivity coefficients for fission spectral parameters are developed. A mathematical formulation of the least-square adjustment problem is given including biases and uncertainties in methods.

* Research sponsored by DOE Office of Reactor Research and Technology.

§ Argonne National Laboratory, Idaho Falls, Idaho.

† General Electric Company, Sunnyvale, California.

‡ CEA Centre d'Etude Nucleaire CADARACHE, France.

3.38. DETERMINATION AND APPLICATION OF GENERALIZED BIAS OPERATORS USING AN INVERSE PERTURBATION APPROACH*

Y. Ronen[†] D. G. Cacuci J. J. Wagschal[‡]

(Abstract of ORNL/TM-7458, November 1980)

A methodology that rests on the introduction of a generalized bias operator is developed to serve as an alternative to both the conventional bias factor method and the data adjustment technique. This methodology is not as broad in scope as the data adjustment technique, but it can be applied to designs as effectively as the less sophisticated, engineering-oriented bias factor method. It is inexpensive and relatively simple from a computational standpoint, and can reflect either calculational or experimental biases. The generalized bias operator can be used to improve the agreement between "reference" and calculated values of all integral performance parameters in systems to be designed. Illustrative numerical results are presented and discussed.

* Research sponsored by the Electric Power Research Institute.

† On leave from Ben Gurion University of the Negev, Beer-Sheva, Israel.

‡ On leave from The Hebrew University, Jerusalem, Israel.

3.39. CROSS-SECTION ADJUSTMENT: SENSITIVITY TO UNCERTAINTIES*

J. J. Wagschal[†] R. E. Maerker B. L. Broadhead[‡]

(Reprint of Trans. Am. Nucl. Soc. 33, 698, 1979)

It is well known by now that the correct procedure of cross-section adjustment calls for detailed analyses of all possible uncertainty sources.¹ Uncertainty sources include neutron differential cross sections, neutron spectra, integral experiments, modeling,

methods, and possibly a few more. A detailed uncertainty analysis involves not only standard deviations, but also the correlations between data. Considerable time and effort are being expended on sophisticated calculations of covariances among many sources of uncertainties.^{2,3} Although conceptually correct, and thus yielding credible results, one should always keep in mind what approximation can be made without an appreciable loss of credibility. The sensitivity of the adjustment procedure to various degrees of sophistication in the input uncertainty representation is tested on five integral experiments measuring average ²³⁵U, ²³⁸U, and ²³⁹Pu fission cross sections in two geometrically simple standard neutron fields.

To minimize and possibly eliminate modeling uncertainties, the NBS ²⁵²Cf field⁴ and ISRF⁵ were selected for our analysis. The integral experimental values and their corresponding covariances were taken from a recent reevaluation,⁵ and the calculations of the ISNF reaction rate ratios using preliminary ENDF/B-V data are described in Ref. 6. The calculated values in the ²⁵²Cf field were obtained by folding preliminary ENDF/B-V fission cross sections and a Maxwellian fission spectrum with a temperature of 1.42 MeV (Ref. 7). The deviation of the calculated (C) from the experimental (E) values and the relative experimental standard deviations are given in Table 3.39.1. Using only the experimental standard deviations we get χ^2/N equal to 10.31.

Table 3.39.1. Experimental and Calculational Uncertainties in Integral Experiments

Integral Experiment		$\frac{C - E}{C} (\%)$	Relative Standard Deviation (%)			
			Experiment	Calculation Due To		
Field	Reaction			σ_f	$\sigma_f(X)^a$	σ
²⁵² Cf	25f	2.74	2.10	1.93	1.93	0.03
²⁵² Cf	49f/25f	-3.66	1.33	1.96	3.37	0.10
²⁵² Cf	28f/25f	-4.46	1.06	1.19	3.02	1.67
ISNF	49f/25f	-1.49	1.28	2.09	2.83	1.09
ISNF	28f/25f	-2.97	0.62	2.07	2.83	3.71

^a $\sigma_f(X)$ = neglecting cross nuclei correlations in σ .

However, it turns out that the uncertainties in the calculated values due to the propagation of the fission cross-section uncertainties alone—even with the strong correlations between fission cross sections of different nuclei—is usually larger than the experimental uncertainty, as is seen in Table 3.39.1. This reduces χ^2/N to 2.6. Including also the covariance of the flux in the ISNF and in the ²⁵²Cf field (fission spectrum) reduces χ^2/N further to 1.7. The flux uncertainty propagated error is most pronounced in the 28f/25f ratios due to the 28f threshold and is almost negligible for 25f in the ²⁵²Cf field. The main source of uncertainty in our "simple" experiment is the propagated uncertainty of the differential fission cross section.

Having familiarized ourselves with some properties of the uncertainties in $(C - E)/C$, we proceed to results of an adjustment using the UNCOVER module of the FORSS⁸ system. Intuitively we have to decrease the fission cross section of ²³⁵U to lower the 2.74% discrepancy shown in the first row of Table 3.39.1. This by itself will reduce the discrepancy in all the ratios, and the remaining discrepancy can be resolved by increasing the ²³⁸U and ²³⁹Pu fission cross sections. Exactly, this is the outcome of the adjustment procedure (see column "Intuitive" in Table 3.39.2) when we (a) do not allow for a flux uncertainty, (b) neglect the correlations between integral experiments, and (c) neglect the correlations between the fission cross sections of ²³⁸U, ²³⁹Pu, and ²³⁵U. The differences between the adjusted integral values A and the original experimental values E normalized to the original calculated values C are given in the top part of Table 3.39.2, and typical

Table 3.39.2. Comparison of Adjustments with Various Uncertainty Representations

Integral Experiment		Original $\frac{C-E}{C}$ (%)	$\frac{A-E}{C}$ (%)			
Field	Reaction		"Intuitive" ^a	"Best" ^a	NO X ^b	NO 1 ^c
²⁵² Cf	25f	2.74	0.51	1.43	0.52	1.65
²⁵² Cf	49f/25f	-3.66	-0.42	-1.18	-0.25	-1.27
²⁵² Cf	28f/25f	-4.46	-0.38	-0.67	-0.13	-0.86
ISNF	49f/25f	-1.49	0.27	-0.97	-0.18	0.32
ISNF	28f/25f	-2.97	0.00	-0.35	-0.09	-0.06

Cross Section, Flux	"Typical" Group Uncertainty (%)	Recommended Adjustment (%)				
25f	3.50	-2.49	-4.71	-2.35	-3.78	
28f	3.77	0.74	-4.56	0.68	-3.65	
49f	4.09	0.91	-2.26	0.78	-1.51	
X28	1.93	-	-2.59	-0.63	-2.61	
φISNF	1.29	-	-0.55	-0.16	-0.41	

^aSee text.^bNO X = neglecting only cross-nuclei correlations in σ.^cNO 1 = neglecting only correlations between integral experiments.

recommended changes in the preliminary ENDF/B-V nuclear data and flux for one particular energy group are given in the bottom part of Table 3.39.2. The corresponding original $(C-E)/C$ values and original uncertainties in the fission cross sections and flux are given for comparison. The results of the "best" adjustment—using all covariance information on the integral experiments, flux and cross sections—and similar results neglecting one type of correlation at a time appear in the following columns of Table 3.39.2.

A careful discussion of the results is beyond the limited space of this paper. However, since the fission cross sections of ²³⁵U, ²³⁸U, ²³⁹Pu are strongly correlated through high accuracy ratio measurements of differential fission cross sections, their corrections should have the same sign ("best" and NO 1 in Table 3.39.2). Neglecting the correlations between the fission cross sections of different nuclei results in corrections of *changing sign* ("intuitive" and NO X in Table 3.39.2). Neglecting the correlations between integral experiments, on the other hand, results only in a quantitatively different result ("best" and NO 1, or "intuitive" and NO X). Neglecting the flux uncertainty altogether results only in minor changes in the recommended adjustment ("intuitive" and NO X).

Analyzing the simple fission ratio integral experiments, we conclude

1. Unless one wants to adjust the flux (for instance, in dosimetry applications), the flux covariance is of minor importance.
2. The propagated uncertainties in the fission cross sections are the major contributor to the total calculational uncertainty. (This will not be the case in more complicated situations when methods and modeling come into play.)
3. The adjustments are not as sensitive to the correlations of the integral experiments as they are to the correlations between the fission cross sections of different materials. The latter influence the results substantially.
4. Beware of false intuition!

*Research sponsored by the Electric Power Research Institute.

†On sabbatical leave from the Racah Institute of Physics, The Hebrew University of Jerusalem, Israel.

‡University of Tennessee.

§A definition of χ^2 can be found, for instance, in Ref. 1. For N integral experiments and "good" data, χ^2/N should be ~ 1 .

1. J. H. Marable and C. R. Weisbin, "Theory and Application of Sensitivity and Uncertainty Analysis," ORNL/RSIC-42, 25-48 (1979).
2. F. G. Perey, "The Data Covariance Files for ENDF/B-V," ORNL/TM-5938 (1977).
3. J. J. Wagschal, R. E. Maerker, and D. M. Gilliam, "Detailed Error Analysis of Average Fission Cross-Section Measurements in NBS Standard Neutron Fields," Trans. Am. Nucl. Soc. 33, 823 (1979).
4. J. A. Grundl and E. D. McGarry, "Compendium of Benchmark and Test Region Neutron Fields for Pressure Vessel Irradiation Surveillance," in NUREG/CR-0551 (1978).
5. C. M. Eisenhauer, J. A. Grundl, and A. Fabry, National Bureau of Standards, Special Publication 493 (March 1977).
6. B. L. Broadhead and J. J. Wagschal, "The NBS Intermediate-Energy Standard Neutron Field (ISNF) Revisited," Trans. Am. Nucl. Soc. 33, 848 (1979).
7. J. W. Boldeman, D. Culley, and C. R. Cawley, "The Fission Neutron Spectrum from the Spontaneous Fission of ^{252}Cf ," Trans. Am. Nucl. Soc. 32, 733 (1979).
8. J. L. Lucius et al., "A User's Manual for the FORSS Sensitivity and Uncertainty Analysis Code System," ORNL-5316.

3.40. THE SIGNIFICANCE OF LAGRANGE MULTIPLIERS IN CROSS-SECTION ADJUSTMENT*

J. J. Wagschal[†] Y. Yeivin[‡]

(Reprint of Trans. Am. Nucl. Soc. 34, 776, 1980; also summary of ESIS Newsletter 33, April, 1980)

This summary offers what we believe is the natural derivation of the explicit prescriptions incorporated in least-squares adjustment codes. We do not pretend to present any really new results, except perhaps for underlining the central role of the Lagrange multipliers, when adjustment of cross sections by integral data is treated for what it truly is; namely, a conditional-minimum problem. The evaluation of the Lagrange multipliers necessitates the inversion only of a "small" matrix, the order of which is the number of integral data by which the cross sections are adjusted. The complete solution of the adjustment problem, i.e., the adjusted differential and integral parameters and their respective uncertainty (variance-covariance) matrices, is then given in terms of the Lagrange multipliers by simple expressions, involving no additional matrix inversions.

Let us first review what adjustment is all about, which we mainly do to introduce a convenient notation. Consider an evaluated (energy-point or multigroup) cross-section library $\sigma \equiv (\sigma_i)$, $i = 1, 2, \dots, N$, with the corresponding uncertainty matrix $C_\sigma \equiv \text{cov}(\sigma_i, \sigma_j) \equiv E[(\delta\sigma)(\delta\sigma)^T]$; and a set of experimental integral data (responses) $r \equiv (r_i)$, $i = 1, 2, \dots, n$, with its uncertainty matrix $C_r \equiv \text{cov}(r_i, r_j)$. Consider also the corresponding set of the calculated responses, $r = r(\sigma)$, and their sensitivities to the cross sections; i.e., the matrix of the $n \times N$ derivatives $S \equiv (\partial r_i / \partial \sigma_j)$. Note that since $r(\sigma + \delta\sigma) = r(\sigma) + S\delta\sigma$, the uncertainty matrix corresponding to the calculated responses is

$$C_r = E[(\delta r)(\delta r)^T] = E[(S\delta\sigma)(S\delta\sigma)^T] = SE[(\delta\sigma)(\delta\sigma)^T]S^T = SC_\sigma S^T, \quad (1)$$

which just reflects the propagation of the σ uncertainties through the calculation of r . Denote the deviations of the calculated responses from their respective experimental values by $d \equiv (d_i)$: $d = r - r$, and note that the deviations' uncertainty matrix is simply $C_d = C_r + C_\sigma$. Let the (unknown) adjusted cross sections be σ' , and the adjusted responses $r^d = r(\sigma')$. Then we further denote the actual adjustments by $x = \sigma' - \sigma$ and $y = r' - r$. We now assume that the approximation $r' = r + S(\sigma' - \sigma)$ is valid, so that, in our notation,

$$y = d + Sx \quad (2)$$

Then, the adjustment proposition is that the optimal adjustments are those values of x and of y which minimize the quadratic form

$$Q = x^T C_\sigma^{-1} x + y^T C_r^{-1} y \quad (3)$$

subject to condition (2).

Now, a straightforward, seemingly natural course to solving this minimum problem is to eliminate y from Eq. (3), by means of Eq. (2), and then solve the resulting unconditional-minimum problem. In other words, the problem is reduced to finding the cross-section adjustments x which minimize

$$Q' = x^T (C_\sigma^{-1} + S^T C_r^{-1} S) x + 2x^T S^T C_r^{-1} d \quad (4)$$

The solution of this minimum problem satisfies the N equations

$$\frac{\partial Q'}{\partial x} = 2[(C_\sigma^{-1} + S^T C_r^{-1} S)x + S^T C_r^{-1} d] = 0 \quad (5)$$

so that

$$x = -(C_\sigma^{-1} + S^T C_r^{-1} S)^{-1} S^T C_r^{-1} d \quad (6)$$

This expression is rather awkward, as it involves the inversion of a "small" ($n \times n$) and two "large" ($N \times N$) matrices. However, it may be shown that

$$(C_\sigma^{-1} + S^T C_r^{-1} S)^{-1} S^T C_r^{-1} = C_\sigma S^T (C_r + S C_\sigma S^T)^{-1} = C_\sigma S^T C_d^{-1} \quad (7)$$

where the expression on the right-hand side involves the inversion only of one small matrix, C_d . Thus, Eq. (6) actually reduces to the relatively simple expression

$$x = -C_\sigma S^T C_d^{-1} d \quad (8)$$

The response adjustments are now also given by a simple expression,

$$y = d + Sx = (I - S C_\sigma S^T C_d^{-1}) d = [I + (C_r - C_d) C_d^{-1}] d = C_r C_d^{-1} d \quad (9)$$

While the solution of the adjustment problem, as outlined above, is certainly legitimate, it is obviously not that straightforward. At least from a methodical point of view, the more natural course is to treat adjustment as a conditional-minimum problem, which is what it really is, and to solve it by the method of Lagrange multipliers. To amplify this argument, we note that to evaluate both x and y , as given by Eqs. (8) and (9), we only have to evaluate $C_d^{-1} d$. The question then arises as to a more fundamental significance, if any, of this vector. It turns out that the components of this very vector are the Lagrange multipliers in the conditional-minimum formulation of the adjustment problem. Certainly, such insight could not have been gained without resort to this method of solution.

In the conditional-minimum formulation, the form

$$R(x,y) = Q(x,y) + 2\lambda^T(Sx - y) \quad (10)$$

where Q is the form of Eq. (3) and 2λ is the n -dimensional vector of Lagrange multipliers, is to be (unconditionally) minimized; i.e., x and y satisfy the equations

$$\frac{\partial R}{\partial x} = 2(C_0^{-1}x + S^T\lambda) = 0 \quad , \quad \frac{\partial R}{\partial y} = 2(C_r^{-1}y - \lambda) = 0 \quad (11)$$

Thus indeed

$$x = -C_0 S^T \lambda \quad , \quad y = C_r \lambda \quad (12)$$

and, by Eq. (2),

$$d = y - Sx = (C_r + SC_0 S^T)\lambda = C_d \lambda \quad , \quad \lambda = C_d^{-1}d \quad (13)$$

Geometrically speaking, the last equation means that λ and d are the covariant and contravariant components, respectively, of one and the same vector with respect to the "metric" C_d . In the hypothetical situation of uncorrelated deviations with standard normal distributions (i.e., with $C_d = I$), we would indeed have $\lambda = d$. Incidentally, Eq. (13) also means that $C_\lambda = C_d^{-1}$.

Let us now derive the uncertainty matrices corresponding to the adjusted parameters. First, from Eq. (12), it immediately follows that

$$C_x = C_0 S^T C_\lambda S C_0 \quad , \quad C_y = C_r C_\lambda C_r \quad (14)$$

Then, since for instance $r' = r + y$,

$$C_{r'} = C_r + C_y + 2E[(\delta y)(\delta r)^T] \quad (15)$$

However, as $\delta y = C_\lambda \delta \lambda = C_r C_\lambda (r - r)$, and because σ (and, therefore, r) and r are uncorrelated as implied by Eq. (3), we conclude that

$$E[(\delta y)(\delta r)^T] = -C_r C_\lambda C_r = -C_y \quad (16)$$

A similar derivation may, of course, be carried out for $C_{\sigma'}$, and the two final expressions are

$$C_{\sigma'} = C_\sigma - C_x \quad , \quad C_{r'} = C_r - C_y \quad (17)$$

To sum up, we have demonstrated (a) that the vector of Lagrange multipliers, λ , and its associated matrix, C_λ , are indeed the essence of the complete solution of the adjustment problem; and (b) that λ is just the geometrical counterpart of the vector of deviations d , with the latter's uncertainty matrix as "metric."

* Research sponsored by DOE Office of Reactor Research and Technology.

† On Sabbatical leave from the Racah Institute of Physics, The Hebrew University, Jerusalem, Israel.

3.41. RESPONSE-PARAMETER CORRELATIONS IN UNCERTAINTY ANALYSIS*

J. Barhen J. J. Wagschal† Y. Yeivin†

(Reprint of Trans. Am. Nucl. Soc. 35, 246-247, 1980)

In a recent note¹ it has been demonstrated that the complete solution of the cross-section adjustment problem, i.e., the explicit prescriptions for the adjusted "differential" parameters and "integral" responses and for their respective uncertainty (variance-covariance) matrices, is rather simple and very lucid when expressed in terms of the Lagrange multipliers and their uncertainty matrix. The meaning of the Lagrange multipliers, and their straightforward relation to the discrepancies between the calculated and experimental responses were also elaborated. For reasons of simplicity, the experimental responses were assumed to be uncorrelated with the input parameters. This has certainly been a very sound working hypothesis in the application of the methodology to the adjustment of neutron cross sections ("parameters") by fast-reactor core-integral data ("responses"), for which least-squares adjustment had first been developed.²

However, with the coming of age of uncertainty analysis³ and its application in an increasing number of additional fields, such *a priori* correlations should be definitely considered. The most recent applications of adjustment, in reactor transient thermal hydraulics,⁴ pressure-vessel damage analysis,⁵ and energy-economy modeling,⁶ involve problems with definite and significant response-parameter correlations. Furthermore, whenever significant parameter adjustments are to be expected, because of poorly known initial parameter values, or in highly nonlinear problems (with significant second or higher order derivatives of the responses with respect to the parameters), the linearity assumption, on which the conventional adjustment algorithms are based, is likely to break down. Such problems are then solved iteratively, so that even when no *a priori* response-parameter correlations are assumed, they appear after the first iteration and necessitate a more general formalism.

The purpose of this note is thus to present a generalized Lagrangian adjustment methodology, explicitly incorporating correlations between input parameters and responses.⁷ This methodology is currently being applied to a wide range of problems.⁴⁻⁶

We shall employ the notation of Ref. 1, except for replacing the "given cross-section library" $\sigma \equiv (\sigma_i)$ by a set of arbitrary input parameters $\alpha \equiv (\alpha_i)$, $i = 1, 2, \dots, I$, to underline the wider range of possible applications. We shall also slightly modify the notation for the uncertainty matrices: $C_{\alpha\alpha}$ will denote the given-parameter uncertainty matrix $\langle \delta\alpha\delta\alpha^t \rangle$, and C_{rr} will denote the $N \times N$ experimental-responses uncertainty matrix. A new matrix, $C_{\alpha r}$, is introduced here to denote the $I \times N$ response-parameter covariances $\langle \delta\alpha_i \delta r_n \rangle$. The uncertainty matrix of the calculated responses, $r = r(\alpha)$, was shown¹ to be $SC_{\alpha\alpha}S^t$, where $S \equiv (\partial r_n / \partial \alpha_i)$.

Let the discrepancies between r and r be denoted by d . Their uncertainty matrix is computed as

$$C_{dd} = \langle \delta(r - r) \delta(r - r)^t \rangle = C_{rr} + C_{rr} - SC_{\alpha\alpha}S^t - C_{\alpha\alpha}S^t \quad (1)$$

In terms of the actual adjustments, $x = \alpha' - \alpha$ and $y = r' - r$, the linearization assumption is

$$y = Sx + d \quad (2)$$

To find x and y , we have to minimize the quadratic loss function

$$Q(x, y) = (y, x)^t \begin{bmatrix} C_{rr} & C_{ra} \\ C_{ar} & C_{\alpha\alpha} \end{bmatrix}^{-1} (y, x) \quad (3)$$

where $(y, x)^t \equiv (y_1, \dots, y_N, x_1, \dots, x_I)$, subject to the linearization constraint. Applying Lagrange's technique for constrained minimization problems to Eqs. (2) and (3) results in the following generalized expressions for the adjustments:

$$x = (C_{ar} - C_{aa} S^t) \lambda, \quad y = (C_{rr} - C_{ra} S^t) \lambda \quad (4)$$

The Lagrange multipliers λ are directly related to the discrepancies between the calculated and experimental responses

$$\lambda = C_{dd}^{-1} d \quad (5)$$

In deriving Eq. (4), use was made of the following identity:

$$\begin{pmatrix} C_{rr} & C_{ra} \\ C_{ar} & C_{aa} \end{pmatrix}^{-1} = \begin{pmatrix} C_{rr}^{-1} + C_{rr}^{-1} C_{ra} A^{-1} C_{ar} C_{rr}^{-1} & -C_{rr}^{-1} C_{ra} A^{-1} \\ -A^{-1} C_{ar} C_{rr}^{-1} & A^{-1} \end{pmatrix} \quad (6)$$

where $A = C_{aa} - C_{ar} C_{rr}^{-1} C_{ra}$. From Eqs. (4) one immediately obtains C_{xx} , C_{yy} , and C_{xy} by the "sandwich" rule. In particular,

$$\begin{aligned} C_{xy} &= (C_{ar} - C_{aa} S^t) C_{\lambda\lambda} (C_{rr} - S C_{ar}) \\ C_{\lambda\lambda} &= C_{dd}^{-1} \end{aligned} \quad (7)$$

It is also easy to verify that $C_{ax} = C_{xa} = -C_{xx} = C_{ry} = C_{yr} = -C_{yy}$, and $C_{ay} = C_{xr} = -C_{xy}$. The uncertainty matrices of the adjusted quantities are, therefore,

$$\begin{aligned} C_{\alpha\alpha} &= \langle \delta(\alpha + x) \delta(\alpha + x)^t \rangle = C_{aa} + C_{ax} + C_{xa} + C_{xx} \\ &= C_{aa} - C_{xx} \\ C_{rr} &= \langle \delta(r + y) \delta(r + y)^t \rangle = C_{rr} + C_{ry} + C_{yr} + C_{yy} \\ &= C_{rr} - C_{yy} \\ C_{\alpha r} &= \langle \delta(\alpha + x) \delta(r + y)^t \rangle = C_{ar} + C_{ay} + C_{xr} + C_{xy} \\ &= C_{ar} - C_{xy} \end{aligned} \quad (8)$$

Let us now consider a very simple example, to illustrate the effect of the response-parameter correlations. We consider two parameters and one response, such that $r(\alpha_1, \alpha_2) = \alpha_1 \alpha_2$. As a possible "physical" interpretation of this model one might think of r as the effective collision multiplication factor of a bare homogeneous multiplying assembly, of α_1 as the multiplicity per collision of the medium, and of α_2 as the average collision probability in the assembly. We consider a critical assembly, so that $r = 1$. For the two parameters we assume $\alpha_1 = 1.5 \pm 2\%$ and $\alpha_2 = 0.66 \pm 1\%$. Two values for the relative standard deviation of r are considered: 0.1 and 1%. Also, either $\text{cor}(r, \alpha_1) = 0$ or $\text{cor}(r, \alpha_1) = 1$. The results of the four cases are given in Table 3.41.1.

Table 3.41.1. Sample Problem: Adjusted Response and Parameters, Reduced Relative Standard Deviations and Modified Correlations, as Functions of Input Relative Standard Deviations and Correlations

Relative Std Dev. (%)	Case 1			Case 2			Case 3			Case 4		
	0.1	2.0	1.0	0.1	2.0	1.0	1.0	2.0	1.0	1.0	2.0	1.0
Input Correlations	1	0	0	1	1	0	1	0	0	1	1	0
	0	1	0	1	1	0	0	1	0	1	1	0
	0	0	1	0	0	1	0	0	1	0	0	1
r	0.99998	1.51210	0.66133	1.00042	1.51249	0.66145	0.97031	1.51007	0.66111	1.00505	1.51515	0.66337
	0.0999	0.898	0.895	0.966	0.964	0.893	0.913	1.157	0.912	0.707	1.407	0.700
Adjusted Correlations	1	0.090	0.023	1	1	-1	1	0.636	0.202	1	1	-1
	0.090	1	-0.994	1	1	-1	0.536	1	-0.628	1	1	-1
	0.023	-0.994	1	-1	-1	1	0.202	-0.628	1	-1	-1	1

The first conclusion from this elementary numerical experiment is that the full input correlation between r and α_1 results in complete loss of any independence among the three adjusted quantities. On the other hand, with uncorrelated input response and parameters, we see that for the accurate input response, r , the adjusted response $\bar{r}$ is practically uncorrelated to the adjusted parameters α_1 and α_2 , which in turn are almost fully anti-correlated; whereas for the relatively poor r , we have $\bar{r}$, α_1 , α_2 all significantly correlated. Such behavior might have been anticipated in analogy to the reduced mass of a system of two unequal or equal masses [see Eq. (7)].

A more significant conclusion concerns the change in the values of the adjusted response and parameters as functions of the (r, α_1) correlation when r is poorly known. As far as the standard deviations of the adjusted values are concerned, the general rule seems to be that they decrease as a result of forcing the (r, α_1) correlation on the input data. In retrospect, these conclusions justify the omission of any (r, α) correlation in the adjustment of cross sections by reactor core performance data, since the latter are usually much better measured than the former, and the interest was mainly in the adjusted values of the parameters.

To sum up: (a) the need for extending the "conventional" data adjustment procedures to include *a priori* response-parameter correlations, in view of the expanding range of applications, was recognized; (b) the generalized formalism was developed and presented in a clear and compact fashion; (c) it was applied to a sample problem as an illustration of a few general conclusions. The generalized methodology is currently being applied to a variety of real, complex problems.

*Research sponsored by U.S. Nuclear Regulatory Commission, Office of Nuclear Regulatory Research.

†On leave from the Hebrew University of Jerusalem, Israel.

1. J. J. Wagschal and Y. Yeivin, "The Significance of Lagrange Multipliers in Cross-Section Adjustment," Trans. Am. Nucl. Soc. 34, 776 (1980).
2. M. Humi, J. J. Wagschal, and Y. Yeivin, "Multi-Group Constants from Integral Data," Proc. 3rd Int. Conf. Peaceful Uses At. Energy, 2, 398 (1964); see also, G. Cecchini, U. Farinelli, A. Gandini, and M. Salvatores, *ibid.*, p. 388.
3. C. R. Weisbin, R. W. Prell, J. H. Marable, P. Collins, E. Kujawski, E. Greenspan, and G. de Saussure, "Sensitivity and Uncertainty Analysis of Reactor Performance Parameters," Adv. Nucl. Sci. Tech. 14, Plenum Press (1980).

4. J. Barhen, D. G. Cacuci, J. J. Wagschal, and C. B. Mullins, "A Systematic Methodology for the Reduction of Uncertainties in Transient Thermal-Hydraulics by Using In-Bundle Measurement Data," Conference on Advances in Reactor Physics and Shielding, Sun Valley (1980).
5. J. J. Wagschal, R. E. Maerker, and B. L. Broadhead, "LWR-PV Damage Estimate Methodology," Conf. Adv. Reactor Physics and Shielding, Sun Valley (1980).
6. R. G. Alsmiller, Jr., J. Barish, D. Bjornstad, D. J. Downing, W. E. Ford, J. Horwedel, C. J. Lee, J. McAdoo, E. H. Oblow, R. W. Peelle, F. G. Perey, L. Stewart, and C. R. Weisbin, "Interim Report on Model Evaluation Methodology and the Evaluation of LEAP," ORNL/TM-7245 (1980).
7. A global covariance matrix B_{exp} covering responses, parameters, and biases can be found in J. H. Marable et al., Nucl. Sci. Eng. 75, 30 (1980). However, the Lagrangian formalism and the simple explicit form for the inverse of the global covariance matrix given in Eq. (6) of the present work enable the explicit analytical representation of all the results. Codes that are currently capable of handling off-diagonal covariance submatrices are UNCOVER² and NOGA.⁴
8. J. H. Marable, "Input Instructions for UNCOVER," handout H of materials used in the RSIC Workshop on the ORNL FORSS Sensitivity and Uncertainty Analysis Code System.

3.42. S_n TRANSPORT CALCULATIONS OF THE PCA EXPERIMENTS WITH SOME ESTIMATED UNCERTAINTIES*

R. E. Maerker

(Reprints of Trans. Am. Nucl. Soc. 24, 628, 1981)

Detailed flux calculations have been carried out for both the 8/7 and 12/13 configurations involving the pool critical assembly (PCA) at Oak Ridge.² In addition, estimates of uncertainties in the calculations arising from both methods approximations and input data uncertainties for two important detector locations in the 8/7 configuration have been made.

The geometry of the PCA core is that of a 60-cm-high $\times$ 38-cm-wide $\times$ 40-cm-deep rectangular parallelepiped with vertical MTR-type fuel plates consisting of 0.1524 cm of aluminum and enriched uranium alternating with 0.295-cm water gaps. The core is followed in a horizontal direction by a 2.5-cm aluminum slab (the "window"), a water gap of either 8- or 12-cm thickness, a 6-cm stainless-steel slab (the simulated thermal shield), a second water gap of either 7 or 13 cm, a 22.5-cm carbon steel slab (the simulated pressure vessel), and a 30.5-cm void box (the simulated reactor cavity). Since the 68.6- $\times$ 68.6-cm slabs extend beyond the dimensions of the core, and the pool water even further, the effective height of the configuration is controlled by the active core height.

The two-dimensional (2-D) P_{1,S_n} discrete ordinate calculations were performed with DOT-IV,³ using XY geometry with space-dependent Z buckling. The X and Z directions are along the width and height of the configurations, respectively, and Y represents the horizontal depth along which the configuration is built up. The treatment of the finite height of the core in calculating centerline ex-core fluxes in essentially an infinite medium represents one of the larger sources of uncertainty in the calculations. The scheme that leads to the smallest uncertainty (and bias factor closest to unity) of all the options investigated for the PCA is one in which the measured ex-core bucklings in each configuration are used and the measured in-core bucklings are neglected. The resulting DB^2 absorption cross sections used in conjunction with infinite Z geometry produce the best agreement (within 2%) at all ex-core detector locations with the centerline reaction rates calculated using finite Z geometry and no buckling.

The calculations were of the fixed-source type, with the source distribution taken from measurements of the power distribution that were supplemented by 2-D core calculations.⁴ The DOT-IV source description was confined to one of the outside quadrants of the core. Reflecting boundary conditions were used to expand the description to the entire core midplane. The

DOT-IV source was normalized so that the integral over the entire core was one neutron per second, using the measured vertical profiles in the core. The quadrant integrated neutron source intensity so obtained was $5.704 \cdot 10^{-3} \text{ s}^{-1}$.

A 51-group energy structure was used in the DOT-IV calculations.⁵ Since most of the quantities to be compared with measurement are threshold activation rates, however, a finer group structure is necessary to calculate these activities more accurately. The DOT-IV calculations were thus supplemented with a pair of ANISN calculations for each configuration, using a suitable 1-D model. One of the ANISN calculations used the same 51-group structure as was used in DOT-IV; the other used the 171-group structure of VITAMIN-C.⁶ Estimates of the 171-group 2-D fluxes were then obtained from the ANISN calculations

$$g'(171, \text{DOT}) = g'(171, \text{ANISN}) \cdot g(51, \text{DOT}) / g(51, \text{ANISN}), g' = g, \quad (1)$$

where the scaled 51-group ratio on the right-hand side of Eq. (1) is a constant for all g' in g . (The 51-group set is a subset but not a collapsed set of the 171-group set.) All cross sections involved in the transport were based on ENDF/B-IV and expanded through P_3 .

The methods approximation expressed by Eq. (1) was checked in the MeV range for several detector locations in the 8/7 configuration by performing a DOT-IV calculation using the first 61 groups for the 171-group set and comparing the fine-group fluxes with those calculated using Eq. (1) and the first 14 groups of the 51-group set. The agreement for each fine-group flux was found to lie within $\pm 2.2\%$ over the range investigated (15 to 0.9 MeV), and the threshold activities agreed to within 0.9%.

In the DOT-IV calculations, the alternating fuel plate and water core geometry was homogenized to reduce the number of Y intervals. The consequent corrections in the activities from using this approximation were determined from 1-D calculations and found to lie in the 2 to 3% range.

The convergence criterion for the DOT-IV calculations was set at 10^{-3} , and as many as 100 inner iterations using the weighted flux extrapolation mode were required for some groups below 10 keV because of the slow convergence of the scattered fluxes in the iron and water geometry. Generally, the converged solutions required an average of about 50 iterations in the energy region below 10 keV, and 10 iterations in the MeV range. Total CPU times, including restarts for further convergence, averaged about 100 min on the IBM 360/195 for each configuration, with storage averaging about 600K bytes.

Reaction rates using both ENDF/B-IV and -V dosimetry cross sections were calculated from the 620-group SAND-II representations for the $^{27}\text{Al}(n,n)$, $^{56}\text{Fe}(n,p)$, $^{32}\text{S}(n,p)$, $^{58}\text{Ni}(n,p)$, $^{238}\text{U}(n,f)$, $^{135}\text{In}(n,n')$, $^{237}\text{Np}(n,f)$, $^{197}\text{Au}(n,\gamma)$, and $^{235}\text{U}(n,f)$ reactions. $^{103}\text{Rh}(n,n')$ activities were calculated from another evaluation.⁷ Comparisons between the results of these calculations with preliminary measurements at several detector locations indicate agreement to within $\pm 10\%$ if the WATT fission spectrum for ^{235}U of ENDF/B-V is used.

*Research sponsored by the Nuclear Regulatory Commission under Lower Water Pressure Vessel Irradiation Programs.

1. The notation x/y refers to the nominal thickness in cm of the two water gaps that define a given configuration. See text.
2. The PCA experiments are to serve as a benchmark test for transport calculations of interest to the dosimetry community and to those interested in estimating embrittlement effects arising from pressure vessel exposure. See W. N. McElroy et al., "LWR Pressure Vessel Surveillance Dosimetry Improvement Program," HEDL SA-1949, Proc. NRC Seventh Water Reactor Safety Research Inf. Mtg., Gaithersburg, MD (Nov. 5-9, 1979).
3. W. A. Rhoades, D. B. Simpson, R. L. Childs, and W. W. Engle, Jr., "The DOT-IV Two-Dimensional Discrete Ordinates Transport Code with Space-Dependent Mesh and Quadrature," ORNL/TM-6529 (1979).

4. See "Description of the Nuclear Regulatory Commission Computational Blind Test on the Pool Critical Assembly Pressure Vessel Facility," distributed to all interested participants (1979).
5. This group structure is: an in-house (ORNL) structure that is built into the AMPX system.
6. R. W. Roussin, C. R. Weisbin, J. E. White, R. Q. Wright, M. M. Greene, W. E. Ford, III, J. B. Wright, and B. R. Diggs, "Experience in Developing and Using the VITAMIN-C 171-Neutron, 36-Gamma Ray Group Cross Section Library," in A Review of Multigroup Nuclear Cross-Section Processing, Proc. Seminar-Workshop, ORNL/RSIC-41, p. 107 (1978).
7. This evaluation by R. Dierckx, Ispra, was provided by F. B. K. Kam, ORNL.

3.43. UNCERTAINTIES AND BIASES ARISING FROM METHODS APPROXIMATIONS: THE CALCULATION OF REACTION RATES IN THE PCA 8/7 CONFIGURATION*

R. E. Maerker J. J. Wagschal[†]

(Abstract of paper presented at Specialists' Meeting on Accuracies in Correlation between Property Change and Exposure Data from Reactor Pressure Vessel Steel Irradiations, KFA-Julich, FRG, September 24-27, 1979)

In the determination of the energy spectrum of the neutron fluxes at the surveillance and 1/4 T positions of LMRs by analyzing measured reaction rates, a calculation of these fluxes is both useful and informative in guiding the unfolding, regardless of the particular unfolding procedure used. It should thus be an important part of an unfolding procedure to be able to calculate not only the fluxes but also to estimate both the corrections to this calculation arising from various methods approximations and the uncertainties in these corrections. In at least one unfolding procedure, that utilizing a generalized least squares technique, knowledge of all uncertainties including those arising from calculational methods approximations is an essential part of the input.

The particular problem addressed in this paper is the estimation of some correction factors (i.e., "biases" or "bias factors") and their uncertainties arising from various approximations used in calculating the fluxes and reaction rates in the Pool Critical Assembly (PCA) at Oak Ridge for the 8/7 configuration. In addition, the uncertainties in the calculated fluxes and reaction rates arising as a result of uncertainties in the non-nuclear data input are estimated. These latter uncertainties give rise to no bias since the most probable values of the data were used in the calculation, but they do contribute to the overall uncertainty of the calculation and for that reason are included in this presentation.

* Research sponsored by the Electric Power Research Institute and by the Nuclear Regulatory Commission under Light Water Reactor Pressure Vessel Irradiation Program.

[†] On leave from The Hebrew University, Jerusalem, Israel.

3.44. SENSITIVITY AND UNCERTAINTY ANALYSIS FOR THE MIXED-OXIDE THERMAL LATTICE U-L212*

R. L. Childs[†]
G. de Saussure
J. L. Lucius[†]
J. D. Drischler

V. C. Baker[†]
J. H. Marable
R. M. Westfall[†]

(Abstract of NP-1248, Research Project 975-3, Key Phase Report, December 1979)

The sensitivities of a mixed-oxide (2 wt% PuO₂, 8% ²⁴⁰Pu) fueled, light-water moderated critical lattice experiment carried out at Battelle Northwest Laboratories

under EPRI sponsorship have been determined. A two-dimensional diffusion theory analysis was performed and the sensitivity of the eigenvalue (k) and four reaction rate ratios to changes in nuclear data have been determined. The sensitivity analysis capability was extended to include upscattering and multi-dimension ability. A covariance matrix has been developed for ^{239}Pu , and the uncertainty associated with calculated performance parameters due to uncertainties in nuclear data has been obtained. This uncertainty has been found to be comparable in size to experimental or calculational model uncertainties. Sensitivity coefficients have been used to estimate the impact of cross section changes proposed for a preliminary version of the ENDF/B-V library.

A study of the large ^{240}Pu resonance at 1.05 eV indicated the linear perturbation theory not to be adequate for predicting the effect of cross section changes of the magnitude proposed for ENDF/B-V. Similarly, a need for a more rigorous treatment of the ^{236}U resonance shielding factor changes has also been indicated.

* Research sponsored by Electric Power Research Institute.

† UCC-ND Computer Sciences Division.

3.45. DETAILED ERROR ANALYSIS OF AVERAGE FISSION CROSS-SECTION MEASUREMENTS IN NBS STANDARD NEUTRON FIELDS*

J. J. Wagschal[†] R. E. Maerker D. M. Gilliam[†]

(Reprint of Trans. Am. Nucl. Soc. 32, 822, 1979)

Integral measurements together with accompanying uncertainty estimates have been used for the past fifteen years in cross-section adjustments.^{1,2} As the field of cross-section adjustment came of age, the crude uncertainty estimates were replaced—only in principle, initially—by a quantitative cross-section uncertainty covariance description and by uncertainty correlations of integral experiments.^{3,4} The current interest in the fission reaction rate ratio measurements in the NBS standard neutron fields, by people involved in fast reactor cross sections,⁵ as well as by people in LWR pressure vessel surveillance dosimetry,⁶ calls for a careful new look at the uncertainty analysis of these measurements. In this work the various contributions to the uncertainties in the different measurements are listed and discussed. Special attention is devoted to components that are common to a few measurements, thus leading to a covariance. Such components are not only experimental error estimates but also uncertainties in common corrections applied to a number of experiments. The joint detailed list serves as a guide to experimenters for reporting their results. The resulting combined standard deviation for each cross-section ratio as well as the resulting correlation matrix is also presented.

The measurements of integral, neutron-induced, fission cross-section ratios in the NBS ^{252}Cf spontaneous fission field⁷ and in the NBS intermediate-energy standard neutron field (ISNF)⁸ were all performed using the NBS back-to-back double fission chambers.⁹ In all runs a highly enriched ^{235}U deposit was placed in one chamber and deposits of either ^{238}U , ^{239}Pu , or ^{237}Np were placed in the other chamber. The measurement of the integral absolute ^{235}U fission cross section in the NBS ^{252}Cf field¹⁰ also employed the same experimental technique. The experimental results, deposit foil identification, and relative uncertainty components, all obtained by reviewing the original laboratory notebooks, are listed in Table 3.45.1. It should be noted that in addition to frequently having physically the same foils in a few measurements, similar data reduction techniques were used to obtain the final results. Such common data reduction techniques include, for example, the extrapolation to zero pulse height, scattering by the platinum backing, self-absorption, and others. All these common factors lead to the correlation matrix given in Table 3.45.2.

In Table 3.45.1 we have three different measurements of the ratio of ^{238}U fission-to- ^{235}U fission in the ISNF field using natural uranium, depleted and highly depleted uranium foils. The values reported earlier in the literature⁸ were labeled as preliminary, but after finding no epithermal-neutron perturbations in additional experiments in the ISNF this disclaimer is being removed. The three measurements were properly (taking into account their

Table 3.45.1. Relative (%) Uncertainty Components

[illegible]

²See *id.*

2 preliminary, see text.

*0.5 correlation with 25 reference mass uncertainty.

0.25 correlation with 25 reference mass uncertainty.

^aMass ratio determined in the thermal neutron beam.

375-i-1 is the 37 reference mass.

Table 3.45.2. Combined Values, Relative Standard Deviations, and Correlation Matrix of Fission Measurements in NBS Standard Fields
(Matrix is symmetric, only lower triangle given.)

Field	Reactions	Value (b)	Relative Standard Deviation (%)	²⁵² Cf				ISNF		
				25	28/25	37/25	49/25	28/25	37/25	49/25
²⁵² Cf	25	1.205	2.1	1						
	28/25	0.2644	1.1	0.40	1					
	37/25	1.105	2.1	-0.09	0.25	1				
	49/25	1.500	1.3	-0.19	0.13	0.32	1			
ISNF	28/25	0.0920	0.62	0.14	0.65	0.14	0	1		
	37/25	0.510 ₂	2.0	-0.14	0.16	0.98	0.32	0.09	1	
	49/25	1.155	1.3	-0.21	0.11	0.32	0.95	0.02	0.33	1

covariances) combined and only the combined measurement is listed in Table 3.45.2. The same applies to the two measurements of the ^{239}Pu ratios that were performed with different ^{240}Pu content in the deposit foils. The ^{237}Np ratio in the ISNF is being reported here for the first time. It is labeled preliminary since only one run was performed so far. It should be noted that the major source of error in all ratio measurements is the foil mass uncertainty.

In conclusion, our detailed new error analysis leads to slightly lower standard deviations than reported previously,^{7,10} and indicates clearly the correlations between the measurements and hopefully could serve as a guide for future documentations of experiments.

* Research sponsored by the Electric Power Research Institute.

† On leave from The Hebrew University, Jerusalem, Israel.

‡ National Bureau of Standards.

1. G. Cecchini, U. Farinelli, A. Gandini, and M. Salvatores, *Proc. 3rd Int. Conf. Peaceful Uses At. Energy*, Geneva, 2, 388 (1964).
2. H. Humi, J. J. Wagschal, and Y. Yeivin, *Proc. 3rd Int. Conf. Peaceful Uses At. Energy*, Geneva, 2, 398 (1964).
3. F. G. Perey, "The Data Covariance Files for ENDF/B-V," ORNL/TM-5938 (July 1977).
4. J. J. Wagschal, A. Yaari, and Y. Yeivin, *Advanced Reactors: Physics, Design and Economics*, p. 536, Pergamon Press, Oxford (1975).
5. C. R. Weisbin et al., "Specifications for Adjusted Cross Section and Covariance Libraries Based upon CSEWG Fast Reactor and Dosimetry Benchmarks," ORNL-5517 (June 1979).
6. J. A. Grundl and E. D. McGarry, "Compendium of Benchmark and Test Region Neutron Fields for Pressure Vessel Irradiation Surveillance," NUREG/CR-0551 (1978).
7. D. M. Gilliam, C. Eisenhauer, H. T. Heaton, II, and J. A. Grundl, "Nuclear Cross Sections and Technology," Washington, NBS-SP-425, 1, 270 (1975).
8. D. M. Gilliam, "Neutron Standards and Applications," Washington, NBS-SP-493, 299 (1977).
9. J. A. Grundl, D. M. Gilliam, N. D. Dudey, and R. J. Papek, *Nucl. Technol.* 25, 237 (1975).
10. H. T. Heaton, II et al., "Nuclear Cross Sections and Technology," Washington, NBS-SP-425, 1, 266 (1975).

3.46. COVARIANCES OF FISSION-INTEGRAL MEASUREMENTS AT THE NBS ^{252}Cf AND ISNF FACILITIES AND AT THE ORNL-PCA FACILITY*

J. J. Wagschal[†] R. E. Maerker D. M. Gilliam[‡]

(Summary of paper presented at Third ASTM-EURATOM Symposium on Reactor Dosimetry, Insa (Varese), Italy, October 1-5, 1979)

In order to reduce the uncertainty in the predicted lifetime of the pressure vessel of a LWR as determined by dosimetry metrologists, one should perhaps begin by using a generalized linear least squares method to provide the "best" agreement between integral dosimetry measurements in standard or benchmark fields and the differential cross-section experiments. In this method the uncertainties and correlations of all the data play leading roles.

The covariances have been obtained for fission integral measurements in the NBS fields by reverting to information extracted from published articles as well as from the original laboratory notebooks. Also, uncertainties arising from various sources of error were reanalyzed as a result of further discussions with the NBS experimenters themselves. The new analysis centered on the obtaining of correlations of these uncertainties, so that a "covariance" matrix of these measurements could be derived. Simple methods were used to correctly average different measurements of the same quantity taking into account the various individual correlations, and to obtain the proper correlations of this average with other experiments.

The purpose of this paper is basically to present the details of the procedures mentioned above to generate the covariance matrix of a series of measurements of interest to the dosimetry community. The hope is that enough detail and motivation is provided that in the future experimenters themselves will determine the covariances of their measurements, since in principle little additional information is needed over that already used in determining the usual estimates of the "errors" in the measured quantities.

This work outlines possible covariances between the NBS and the ORNL-PCA measurements. The full covariances will be calculated as soon as the PCA measurements are fully analyzed.

* Research sponsored by the Electric Power Research Institute.

† On leave from The Hebrew University, Jerusalem, Israel.

‡ National Bureau of Standards.

3.47. THE NBS INTERMEDIATE-ENERGY STANDARD NEUTRON FIELD (ISNF) REVISITED*

B. L. Broadhead† J. J. Magschal‡

(Reprint of Trans. Am. Nucl. Soc. 33, 848, 1979)

Currently the ISNF¹ is receiving increased interest as a dosimetry standard field in several areas of application from cross-section adjustment studies for fast reactor applications,² to damage evaluations in light-water reactor pressure vessels, which is the subject of an ongoing program at ORNL being sponsored by the Electric Power Research Institute.

Previous studies have analyzed the ISNF with Maxwellian³ (ENDF/B-IV), energy-dependent Watt³ (ENDF/B-V), and NBS-evaluated⁴ (Maxwellian multiplied by segmented adjustment functions) ²³⁵U fission spectra along with ENDF/B-IV cross sections. This work carefully analyzes the ISNF field and determines the impact of ENDF/B-V cross sections for 28f, 25f, and 49f on the reported calculated vs experimental reaction rate ratio discrepancies. In addition, detailed uncertainty estimates for both the calculations and the experiments are included. Finally, new preliminary results for 37f/25f in the ISNF are reported.

Studies previously cited have shown that neither the NBS-evaluated nor the Maxwellian ²³⁵U fission spectrum performed very well ($|C/E - 1| > \sim 5\%$) in the analysis of simple 1-D geometry benchmark fields. For this reason this work dealt only with the energy-dependent Watt spectrum, which is the ²³⁵U ENDF/B-V fission spectrum. Neutronic calculations were performed using the XSDRNP module of the AMPX system⁵ in the 171-group VITAMIN-C⁶ structure with S_8 angular quadrature and up to $l = 3$ scattering moments. Increasing the S_8 quadrature to S_{16} and refining (doubling) the spatial mesh showed small ($< 0.5\%$) changes in the group fluxes and negligible ($< 0.1\%$) changes in the fission rate ratios. No new estimate was made of the effects of higher scattering moments; however, experience indicates they should be very small. Also, this analysis considered the ISNF field to be contained in the central 5-cm-diam spherical region of the NBS thermal column cavity,¹ while Soran et al.⁴ used the central point in Monte Carlo calculations and a 0.58-cm sphere in S_8 calculations. These effects are very likely to be small. The actual experimental configuration using the NBS double fission chamber lies between the point model and the 5-cm-diam spherical model. Also, Soran et al. have shown that discrete energy vs continuous energy effects are on the order of 0.5%.

Table 3.47.1 shows reaction rate ratios obtained from folding the ISNF spectrum with both ENDF/B-IV and preliminary ENDF/B-V 28f, 25f, and 49f cross sections in 171 groups. Also shown in Table 3.47.1 are the experimental ratio values and their uncertainties. The 28f/25f measured value and its uncertainty have changed slightly due to a new evaluation of the experiment (see details in Ref. 7). For the 37f/25f, the ENDF/B-IV C/E is 0.978, which is almost within the experimental uncertainty of 2%. For the case of 28f/25f, C/E's using ENDF/B-IV and preliminary ENDF/B-V were 0.962 and 0.972, respectively. Clearly these discrepancies are outside the 0.6% experimental uncertainties. This is also true of the 49f/25f case with C/E's of 0.973 and 0.985 for ENDF/B-IV and preliminary ENDF/B-V, respectively, and an experimental uncertainty of 1.3%. Thus, the effect of using preliminary ENDF/B-V fission cross sections is to decrease the discrepancy by approximately 1%.

Table 3.47.1. Reaction Rate Ratio Values in the ISNF Field

Response	ENDF/B-IV Fission Cross Sections	ENDF/B-V Fission Cross Sections	Experimental Value	Estimated Calculational Uncertainty ^a (%)	Experimental Uncertainty (%)
28f/25f	0.0885	0.0894	0.0920	4.2(2.1)	0.6
37f/25f ^b	0.499	-	0.510	-	2.0
49f/25f	1.124	1.138	1.155	2.4(2.1)	1.3

^aCombined flux and preliminary ENDF/B-V fission cross-section contributions (cross section only).

^bPreliminary.

If we then include estimates of the uncertainties in these ratios due to flux spectrum uncertainties and 28f, 25f, and 49f cross-section uncertainties also shown in Table 3.47.1, these calculated ratios appear to be well within the combined experimental and calculational uncertainties. The techniques utilized in the estimation of uncertainties in these calculated ratios are described in Refs. 3 and 8. Although the individual uncertainty values used to obtain this overall uncertainty estimate are preliminary and in some cases quite crude, clearly this estimated uncertainty is of value in interpreting the magnitude of the calculated vs experimental discrepancy.

In conclusion, these results show that using the latest data (ENDF/B-V fission cross sections of 28, 25, and 49) and taking into account uncertainties in various input data, the calculated vs experimental discrepancies in the ISNF can be resolved. This is true even if method uncertainties, which we have shown to be small, are neglected. Thus, the ISNF has much potential for use as a benchmark field for intermediate-energy spectrum applications.

*Research sponsored by the Electric Power Research Institute.

†University of Tennessee.

‡On leave from The Hebrew University, Jerusalem, Israel.

1. C. M. Eisenhauer, J. A. Grundl, and A. Fabry, National Bureau of Standards, Special Publication 493 (March 1977).
2. C. R. Weisbin, J. H. Marable, P. Collins, C. Cowan, R. W. Peelle, and M. Salvatores, "Specifications for Adjusted Cross Section and Covariance Libraries Based upon CSEWG Fast Reactor and Dosimetry Benchmarks," ORNL 5517 (ENDF-276) (1979).
3. B. L. Broadhead and J. H. Marable, "Sensitivity and Uncertainty Analysis Applied to the NBS-ISNF," Proc. RSIC Seminar and Workshop, Theory and Application of Sensitivity and Uncertainty Analysis, Oak Ridge, TN (August 1978).

4. P. D. Soran, R. J. LaBauve, C. M. Eisenhauer, and D. C. George, "Neutron Analysis of the NBS Intermediate-Energy Standard Neutron Field (ISNF)," *Trans. Am. Nucl. Soc.* 32, 777 (1979).
5. N. H. Greene, W. E. Ford III et al., "AMPX: A Modular Code System for Generating Coupled Multigroup Neutron-Gamma Libraries from ENDF/B," *ORNL/TN-3706* (March 1976).
6. R. W. Roussin, C. R. Weisbin et al., "The CTR Processed Multigroup Cross Section Library for Neutronic Studies," *ORNL/RSIC-37* (1978).
7. J. J. Wagschal, R. E. Maerker, and D. M. Gilliam, "Detailed Error Analysis of Average Fission Cross-Section Measurements in NBS Standard Neutron Fields," *Trans. Am. Nucl. Soc.*, 33, 223 (1979).
8. B. L. Broadhead, H. L. Dodds, Jr., J. L. Lucius, F. G. Perey, and C. R. Weisbin, "Calculation of the Flux Covariance Matrix for the National Bureau of Standards Intermediate-Energy Standard Neutron Field (NBS-ISNF)," *Trans. Am. Nucl. Soc.*, 30, 599 (1978).

3.48. THE ISNF: A NEW CSEWG DOSIMETRY BENCHMARK (COMPUTATIONAL PROBLEMS AND THEIR SOLUTION)*

B. L. Broadhead[†] J. J. Wagschal[‡]

(Reprint of *Trans. Am. Nucl. Soc.* 35, 466-468, 1980)

The Intermediate Energy Standard Neutron Field (ISNF)¹ is currently being utilized as a dosimetry standard field in cross-section adjustment studies as a part of an ongoing reactor pressure vessel damage analysis program at ORNL being sponsored by the Electric Power Research Institute. Also, it is under consideration as a CSEWG dosimetry benchmark.²

This study updates previously reported results³⁻⁵ with the inclusion of ENDF/B-V ISNF flux spectrum calculations. Several anomalies which became evident during these calculations are presented and discussed. All calculations were performed by the XSDRNPM module of the AMPX⁶ system with 73 or 80 spatial intervals, 174-group ENDF/B-V cross sections (VITAMIN-E structure),⁷ up to P_3 scattering moments, and angular quadratures of S_8 , S_{16} , and S_{32} . The 1-D model is given in Ref. 1. In previous work,⁵ 73 spatial intervals were used. Seven additional intervals in the area surrounding the source make up the 80-interval model.

The description of the weighting schemes available in standard neutron transport codes can be found in various references,^{8,9} and they include diamond difference (herein called linear), weighted diamond difference (herein called weighted), step (step), diamond difference with step fixup for negative fluxes (linear/step), and diamond difference with weighted diamond difference fixup (linear/weighted).

Previous ISNF spectrum calculations⁵ (ENDF/B-IV-VITAMIN-C) were performed using the traditional linear/step differencing scheme and convergence was achieved in every group (171 groups). However, the linear/step produced nonconvergence using ENDF/B-V data (see footnote, Table 3.48.1). It is noted that only the step, linear, and linear/weighted schemes reached full convergence. However, the linear scheme produced negative scalar fluxes at low energies due to neutron propagation through the boron shell. Comparison of the point flux values at the ISNF Center for all five weighting schemes reveals: (a) the linear/weighted and linear step values are very close, (b) the weighted and step values are much higher, and (c) the linear values fall in between. This indicates further refinement of the calculations is needed. Additional intervals were thus added in the region with the steepest spatial gradient from interval to interval and an 80-mesh model resulted. Very little effect on the point values was realized, the convergence was not improved, and a wide spread of point values was still present. S_{16} quadrature was then used with some improvement in the agreement among various weighting schemes resulting. S_{32} showed further improvement such that with the expected exception of the step scheme, most point

Table 3.48.1. ISNF Calculational Results

S ₈ Calculations (73 intervals)					
	Step	Linear/step ^a	Linear/weighted	Weighted ^a	ENDF/B-IV Linear/Step
ϕ_{11}^b	1.103×10^{-9}	1.072×10^{-9}	1.070×10^{-9}	1.103×10^{-9}	
$49_f/25_f$	1.160	1.136	1.136	1.142	1.138
$28_f/25_f$	0.0967	0.0887	0.0886	0.0916	0.0894
$37_f/25_f$	0.5400	0.5024	0.5023	0.5193	0.5065
S ₃₂ Calculations (80 intervals)					
	Step	Linear/step	Linear/weighted	Weighted	
ϕ_{11}^b	1.075×10^{-9}	1.087×10^{-9}	1.088×10^{-9}	1.089×10^{-9}	
$49_f/25_f$	1.150	1.135	1.136	1.135	
$28_f/25_f$	0.0944	0.0884	0.0885	0.0895	
$37_f/25_f$	0.5262	0.5012	0.5022	0.5066	

^aDid not converge to 1.0×10^{-4} in at least one group.

^b ϕ_{11} is the group 1 flux in the first interval (central region).

values agree to within 0.5%. It may seem surprising that the simple spherical geometry of the ISNF would require such a high-order quadrature for flux convergence. However, this is just another manifestation of ray effects. These ray effects are due to effectively free streaming from the outer shell source and reflection from the graphite to a small central zone.

We now feel the solutions have converged to the extent that we can be confident in the solutions, even for high-quality benchmarking purposes.

An anomaly encountered during this study is that the P_3 approximation appears to break down quite drastically at high (first several groups) energies. The most notable result is the existence of negative angular fluxes for inward-directed angular fluxes in the region exterior to the shell source (i.e., in the graphite) for group 1 (17.3 to 19.6 MeV and perhaps other groups as well). Group 1 inward-flowing fluxes in graphite are due to outward-directed source neutrons that must have backscattered in order to become inwardly directed. However, the kinematics of scattering in carbon predict the removal of the neutron from group 1 in such a scatter. Thus, the inward-directed flux in this region for the first few groups should be very near zero. The P_3 approximation thus breaks down due to the strongly forward peaked solution. The effects of this breakdown may be 4 to 5% overprediction of the first few group fluxes. However, these fluxes are approximately five orders of magnitude below the peak flux and should affect the integral results only minutely.

The final results for the integral quantities are shown in Table 3.48.1. Notice some differences also exist among the various differencing schemes, but again with the exception of the step scheme, agreement is approximately within 1%. The integral values for the weighted scheme are to be used by ORNL in benchmarking the ISNF for dosimetry applications. It is interesting to note the agreement between these values (obtained by an S_{32} calculation) and previous values (obtained by S_8 using ENDF/B-IV) for the ISNF flux calculation.

In summary, a careful analysis of ISNF flux calculations revealed several anomalies and led to slight changes in the ISNF benchmark calculational model. These anomalies affect the order of angular quadrature, number of scattering moments, and weighting scheme. This detailed study of ISNF calculational modeling has led to high-quality results suitable for benchmarking purposes.

* Research sponsored by the Electric Power Research Institute.

† University of Tennessee.

‡ On leave from The Hebrew University of Jerusalem, Israel.

1. C. M. Eisenhauer, J. A. Grundl, and A. Fabry, National Bureau of Standards, Special Publication 493 (March 1977).
2. Ben Magurno, Private Communication, Chairman, Special Applications File Subcommittee of Cross Section Evaluation Working Group (May 1980).
3. B. L. Broadhead and J. H. Marable, "Sensitivity and Uncertainty Analysis Applied to the NBS-ISNF," Proc. RSIC Seminar and Workshop Theory and Application of Sensitivity and Uncertainty Analysis, Oak Ridge, Tennessee (August 1978).
4. P. D. Soran, R. J. LaBauve, C. M. Eisenhauer, and D. C. George, Trans. Am. Nucl. Soc., 32, 777 (1979).
5. B. L. Broadhead and J. J. Wagschal, Trans. Am. Nucl. Soc. 33, 848 (1979).
6. N. M. Greene et al., "ANPX: A Modular Code System for Generating Coupled Multigroup Neutron-Gamma Libraries from ENDF/B," ORNL-TM-3706, Oak Ridge National Laboratory (March 1976).
7. C. R. Weisbin et al., "VITAMIN-E: An ENDF/B-V Multigroup Cross Section Library from LMFBR Core and Shield LMR Shield, Dosimetry and Fusion Blanket Technology," ORNL-5505 (ENDF-274), Oak Ridge National Laboratory (February 1979).
8. H. Greenspan, C. N. Kelber, and D. Okrent, Computing Methods in Reactor Physics, Gordon and Breach, N.Y. (1968).
9. S. A. Dupree, H. A. Sandmeier, G. E. Hansen, W. W. Engle, Jr., and F. R. Mynatt, "Time-Dependent Neutron and Photon Transport Calculations Using the Method of Discrete Ordinates," LA-4775 (ORNL-4662) (SAI 70-125) (May 1971).

3.49. ESTIMATION OF THE UNCERTAINTIES IN THE ENDF/B-V ^{235}U FISSION SPECTRUM*

R. E. Maerker J. H. Marable J. J. Wagschal†
(Reprint of Trans. Am. Nucl. Soc. 35, 555-558, 1980)

The uncertainty of the fission spectrum is useful for calculating uncertainties of reactor performance parameters,¹ for the adjustment of cross sections,² and for applications using the dosimetry unfolding technique.³ However, the ENDF/B-V evaluation of the ^{235}U fission spectrum does not include the uncertainties, although the evaluation of this covariance is high on the list of CSEWG covariance priorities. The ENDF/B-V evaluation of the spectrum χ for ^{235}U fission neutrons is given in the form of the Watt formula

$$\chi_w(E) = (4/\pi a^2 b)^{1/2} \sinh(bE) \exp(-ab/4) \exp(-E/a), \quad (1)$$

where parameters a and b are specified as functions of the incident-neutron energy E . For energies below 1.5 MeV, the values for a and b are 0.998 and 2.249 MeV⁻¹, respectively.

The actual value of the fission spectrum $\chi(E)$ will be an energy-dependent factor $f(E)$ times the Watt spectrum $\chi_W(E)$, where the factor $f(E)$ accounts for the possibility that the Watt formula may not give the fission spectrum precisely at all energies. The factor $f(E)$ has an average value of unity when the average is weighted by $\chi_W(E)$.

The uncertainty in the fission spectrum will be determined by the standard deviations of a and b and by their correlation if the factor $f(E)$ has negligible uncertainty; e.g., $f(E)$ is identically unity.

A similar problem was faced by Lucius and Marable⁴ in evaluating the uncertainty of the fission spectrum as given in ENDF/B-IV by a Maxwellian expression dependent on a single parameter, the Maxwellian temperature. They solved the problem by finding (a) the uncertainty in the mean energy $\bar{E}$ which led to the uncertainty in the Maxwellian expression, and (b) the uncertainty in the relative width w defined by $(E^2 - \bar{E}^2)^{1/2}/\bar{E}$, which was assumed to represent the uncertainty in the ratio of the actual spectrum to the Maxwellian spectrum. They assumed that there was no correlation between the two parameters $\bar{E}$ and w and justified this on the basis of showing the resulting uncertainties in the fission spectrum gave reasonable agreement with experimental uncertainties.

By assuming the factor $f(E)$ is unity with no uncertainty, transformation formulae between parameters (a,b) and parameters $(\bar{E},w)$ have been derived. Evaluations other than ENDF/B-V have given uncertainties for a and b , but no value of the correlation was given. Using relative uncertainties for a and b of 1.2 and 5.9%, respectively,⁵ the corresponding uncertainties in $\bar{E}, w$, and their correlation are plotted in Fig. 3.49.1 as a function of the correlation α_{ab} between a and b .

The results shown by Fig. 3.49.1 are quite clear. The uncertainty in the relative width of the ENDF/B-V Watt spectrum depends only weakly on the assumed correlation α_{ab} between a and b and is less than 0.5% in contrast to the estimated 5% uncertainty in the width of the ENDF/B-IV Maxwellian spectrum. The uncertainty in the mean energy $\bar{E}$ is strongly dependent on the assumed value of α_{ab} but is of the order of 3% or less, which is not much different from the 2% estimate for ENDF/B-IV. The correlation of $\alpha_{\bar{E}w}$ is dependent on α_{ab} , but in contrast to the zero estimate for ENDF/B-IV, is always negative and is greater than 0.35 in magnitude.

Fig. 3.49.1. Standard deviations of $\bar{E}$, w , (right-hand scale) and their correlation (left-hand scale) as functions of the a , b , correlation.

It is to be concluded that the ENDF/B-V evaluation for the ^{235}U fission spectrum has, in comparison with ENDF/B-IV, greatly decreased the uncertainty in the width of the spectrum. The uncertainty in the mean energy $\bar{E}$ is still around 2%, and the two parameters $\bar{E}$ and w have a substantial negative correlation.

*Research sponsored by Electric Power Research Institute.

†On leave from The Hebrew University, Jerusalem, Israel.

1. J. H. Marable, C. R. Weisbin, and G. de Saussure, Nucl. Sci. Eng. 75, 30 (1980).
2. C. R. Weisbin, R. W. Peelle, J. H. Marable, P. Collins, E. Kujawski, E. Greenspan, and G. de Saussure, Advances in Nuclear Science and Technology, 14, Plenum Press (1980).
2. J. J. Majschal, B. L. Broadhead, and R. E. Maerker, "Least Squares Methodology Applied to LWR-PV Damage Dosimetry, Experience and Expectations," Int. Conf. Nuclear Cross Sections for Technology, Knoxville, TN (Oct. 1979).
4. J. L. Lucius and J. H. Marable, Trans. Am. Nucl. Soc. 32, 731 (1979).
5. P. I. Johansson and B. Holmqvist, Nucl. Sci. Eng. 62, 695 (Table IV on page 707) (1977).

3.50. INFLUENCE OF FISSION SPECTRA UNCERTAINTIES ON CALCULATED FAST REACTOR PARAMETERS

J. L. Lucius[†] J. H. Marable

(Reprint of Trans. Am. Nucl. Soc. 32, 731-732, 1979)

This paper is concerned with the question, "What effect do fission spectra uncertainties have on calculated fast reactor parameters?" We attempt to answer this by (a) considering the sensitivities to fission spectrum parameters of four performance parameters in the fast reactor benchmark ZPR-6/7,¹ (b) estimating the uncertainties in these calculated performance parameters due to uncertainties in the fission spectra, (c) reporting the change in ZPR-6/7 calculated performance parameters due to fission spectra changes going from ENDF/B-IV to proposed ENDF/B-VP, and (d) determining what fast benchmark integral experiments are trying to tell us about ENDF/B-IV fission spectrum parameters as variables in a least-squares adjustment procedure.

Relative sensitivities of four ZPR-6/7 performance parameters to fission spectrum parameters were calculated using a 1-D model and ENDF/B-IV cross sections. Table 3.50.1 shows sensitivities (S_T) to ENDF/B-IV Maxwellian temperatures and sensitivities (S_a, S_b) to proposed Version-V Watt parameters a and b , defined by

$$\chi(e) = A \exp(-E/a) \sinh(bE) \quad (1)$$

The ^{239}Pu fission spectrum is seen to be dominant.

To compare spectra defined by different parameters, we introduce $\bar{E}$ and M , which are the mean energy and the relative root-mean-square width about the mean defined by

$$M = (\bar{E}^2 - \bar{E}^2)^{1/2} / \bar{E} \quad (2)$$

Using $\bar{E}$ and M , we interpret the Maxwellian sensitivities S_T as the relative sensitivities to $\bar{E}$ keeping M fixed. For a Watt spectrum, the relative sensitivity to $\bar{E}$ is found by subtracting S_b from S_a . Sensitivities to $\bar{E}$ are essentially the same for both Maxwellian and Watt spectra. The Watt form of the ^{239}Pu fission spectrum leads to relative sensitivities to M of -0.04, -0.04, 0.08, and -0.4 for k , $F49/F25$, $C28/F49$, and $F28/F25$, respectively.

Table 3.50.1. Sensitivities and Uncertainties Associated with the Fission Spectra for Fast Reactor Benchmark ZPR-6/7

Response in ZPR-6/7	$\frac{\Delta R^c}{R}$ $\left(\frac{VP-IV}{IV} \times 100\%\right)$	Nuclide	Relative Sensitivities			Uncertainties ^b (%)
			Maxwell.	Watt		
			S _T	S _a	S _b	
k	.26	²³⁹ Pu	.112	.159	.036	.33
		²⁴⁰ Pu	.003			.01
		²⁴¹ Pu	.003			.01
		²³⁸ U	.020	.033	.008	.08
		²³⁵ U	.002	.003	.001	.01
C28/F49	-.44	²³⁹ Pu	-.076	-.110	-.031	.45
		²⁴⁰ Pu	-.002			.01
		²⁴¹ Pu	-.002			.01
		²³⁸ U	-.010	-.017	-.006	.04
		²³⁵ U	-.001	-.001	-.003	.01
F49/F25	.24	²³⁹ Pu	.034	.049	.014	.24
		²⁴⁰ Pu	.001			.01
		²⁴¹ Pu	.001			.01
		²³⁸ U	.005	.008	.003	.02
		²³⁵ U	.001	.001	.001	.01
F28/F25	2.43	²³⁹ Pu	.893	1.298	.328	2.93
		²⁴⁰ Pu	.025			.10
		²⁴¹ Pu	.019			.07
		²³⁸ U	.123	.200	.058	.49
		²³⁵ U	.011	.015	.003	.04

^aThis column² presents the percent changes in the responses due to differences in the ENDF/B-IV and ENDF/B-VP fission spectra.

^bThis column presents the estimated standard deviations (in percent) of the responses due to estimated uncertainties in the fission spectrum (as discussed in the text).

There is presently no detailed covariance file for the ²³⁹Pu fission spectrum. Estimates, however, of uncertainties in various parameters exist. For example, the standard deviation in the mean energy is estimated at 2% (Ref. 3). Wagschal, assuming a Maxwellian with 2% uncertainty in the temperature, finds resulting uncertainties over significant portions of the spectra to be low by a factor of 2 (Ref. 4). The uncertainties in Table 3.50.1 for nuclides other than ²³⁹Pu have been calculated using the Maxwellian sensitivities S_T and the 2% uncertainty in the mean energy multiplied by two.

For ²³⁹Pu, the change in $\bar{E}$ and M going from ENDF/B-IV to ENDF/B-VP, assuming fissions induced by 1-MeV neutrons, was +0.24% and -5%. Using this 5% as an estimate of the uncertainty in M , together with the estimated 2% uncertainty in $\bar{E}$ (assuming no correlation), leads to the uncertainties shown for ²³⁹Pu in Table 3.50.1. These represent uncertainties associated with ENDF/B-IV fission spectra. The uncertainty in the threshold-dominated reaction rate F28/F25 is substantial, and it and the uncertainty in k are larger than corresponding recently evaluated experimental uncertainties.⁵ In going from Version IV spectra to Version VP, the major contributor to response changes shown in Table 3.50.1 was the 5% decrease in the relative width M of ²³⁹Pu. The contribution from the 0.25% increase in the mean energy (corresponding to fissions induced by 1-MeV neutrons) was small.

Eight benchmark integral experiments were included in a data adjustment. Adjustable differential data included ν , σ_f , and σ_c for ²³⁵U, ²³⁸U, and ²³⁹Pu; σ_c for ²⁴⁰Pu; σ_{el} for ⁰; and ²³⁸U inelastic scattering. The adjustment was as described in Ref. 6 with the following two changes: (a) fission spectrum sensitivities to $\bar{E}$ and M for ²³⁹Pu fission

were included for all eight responses, and (b) the covariance matrix for the integral experiments was based on a new evaluation.⁵ The resulting adjustment, characterized by a chi-square-per-degree-of-freedom of 0.84, led to a 1% increase in $\bar{E}$ and a 4% decrease in M .

In summary, the following statements are made concerning the ^{239}Pu fission spectrum which is dominant in fast plutonium-fueled reactors as represented by ZPR-6/7. Relative sensitivities with respect to the mean fission neutron energy $\bar{E}$ are 0.12 for k , 0.04 and -0.08 for spectral indices F49/F25 and C28/F29, respectively, and 1.0 for F28/F25, which involves a threshold reaction. Relative sensitivities to dimensionless relative width M are -0.04 for k , -0.04 and 0.08 for F49/F25 and C28/F49, respectively, and -0.4 for F28/F25. Based on rather incomplete uncertainty files for the fission spectrum (an estimated 2% in $\bar{E}$ and 5% in M , uncorrelated), uncertainties in calculated values of four APR-6/7 integral parameters due to uncertainties in the ^{239}Pu fission spectrum are estimated to be 0.3, 0.2, 0.4, and 3.0% for k , F49/F25, C28/F49, and F28/F25, respectively. This last uncertainty is quite significant. In going from ENDF/B-IV to ENDF/B-VP, the change in the mean energy $\bar{E}$ increased 0.25% while the change in the relative width M decreased 5%. This is in reasonable agreement with the application of eight fast benchmark integral experiments in a least-squares adjustment procedure, the results of which suggested a 1% increase in the mean energy $\bar{E}$ and a 4% decrease in the relative width M .

* Research sponsored by DOE Office of Reactor Research and Technology.

† UCC-ND Computer Sciences Division.

1. "Cross-Section Evaluation Working Group Benchmark Specifications," BNL-19303 (ENDF-202), Brookhaven National Laboratory (November 1974).
2. R. Q. Wright, Private Communication (January 1979).
3. R. W. Peelle, Private Communication (April 1978).
4. J. J. Wagschal, Private Communication (January 1979).
5. P. J. Collins and M. J. Lineberry, "The Use of Cross Section Sensitivities in the Analysis of Fast Reactor Integral Parameters," Proc. RSIC Seminar and Workshop, Theory and Application of Sensitivity and Uncertainty Analysis, Oak Ridge, TN (August 1978).
6. J. H. Marable and C. R. Weisbin, "Uncertainties in the Breeding Ratio of a Large LMFBR," Proc. Am. Nucl. Soc. Topl. Mtg., p. 231, Gatlinburg, TN (April 1978).
7. E. Kujawski, letter to Dr. S. Pearlstein, "ENDF/B-V Summary Documentation for Pu-239," (January 1979)

3.51. SENSITIVITY AND A PRIORI UNCERTAINTY ANALYSIS OF THE CFRMF CENTRAL FLUX SPECTRUM*

J. M. Ryskamp[†] R. A. Anderl[†] B. L. Broadhead[†] W. E. Ford, III[§]
J. L. Lucius[§] J. H. Marable J. J. Wagschal[†]

(Reprint of Trans. Am. Nucl. Soc. 35, 556-557, 1980)

The Coupled Fast Reactivity Measurements Facility (CFRMF), located at the Idaho National Engineering Laboratory, is a zoned-core critical assembly with a fast-neutron-spectrum zone in the center of an enriched ^{235}U , water-moderated thermal driver.¹ The central fast zone is produced by a water-free filter assembly which tailors the neutron energy spectrum incident on it from the thermal driver. The filter consists primarily of a large depleted uranium block clad externally with stainless steel and Boral. It has an axial experiment hole lined with stainless-steel-clad concentric cylinders of ^{10}B and ^{235}U . Spanning the neutron energy range ($1 \text{ keV} < E_n < 10 \text{ MeV}$), the central neutron spectrum is a Cross-Section Evaluation Working Group (CSEWG) benchmark field for data testing of fission product, actinide, and dosimeter cross sections important to fast reactor technology.

An accurate knowledge of the central neutron spectrum is important to data-testing analyses which utilize integral reaction-rate data measured for samples placed in the CFRMF field. The purpose of this paper is to present the results of a study made with the AMPX-II² and FORSS³ code systems to determine the central-spectrum flux covariance matrix due to uncertainties and correlations in the nuclear data for the materials that constitute the facility. AMPX-II is a code system for generating coupled multigroup neutron-gamma-ray cross-section libraries from data in ENDF format. FORSS is a code system used to study relationships between nuclear cross sections, integral experiments, reactor performance parameter predictions and associated uncertainties.

The starting cross-section data base was a preliminary 100-group ENDF/B-V library which has been used extensively at ORNL for fast reactor data testing. A 15-region cylindrical model was defined for the CFRMF. A 100-group self-shielded cross-section library was generated for this problem with BONAMI2 (Bondarenko treatment). Detailed transport calculations (S_0 , P_3) were made with XSDRNPM, and 26-group cross sections were obtained for each region by collapsing the 100-group cross sections.

The 15-region, 26-group XSDRNPM cross sections were input to FANISM, which generated 26-group angular fluxes and generalized adjoints (28 FANISM runs with S_0 , P_3). These fluxes and adjoints, as well as the 26-group microscopic cross sections, were combined by JULIET to obtain 26-group sensitivity coefficients for the important data of each nuclide in each material. The BUBBLE code, an *ad hoc* code written specifically for this purpose, was used to combine the sensitivities with the cross-section and fission-spectrum covariance matrices (ENDF/B-V) to generate a relative-flux covariance matrix.⁴

The JULIET code was modified to compute the necessary generalized adjoint sources. The response functions for this analysis are the relative neutron fluxes for each group g averaged over the central region J :

$$R_g = \frac{\phi_{gJ}}{\sum_i \phi_{ij}} = \frac{\sum_{ij} \phi_{ij} \delta_{ig} \delta_{jJ}}{\sum_{ij} \phi_{ij} \delta_{jJ}} \quad (1)$$

where δ_{ig} is the Kronecker delta, and i and j are group and interval indices, respectively. The generalized adjoint sources were computed from

$$S_{i'j'}^* = \frac{1}{R_g} \frac{\partial R_g}{\partial \phi_{i'j'}} = \frac{\delta_{i'g} \delta_{j'J}}{\phi_{gJ}} - \frac{\phi_{j'J}}{\sum_i \phi_{ij}} \quad (2)$$

Sensitivity coefficients were generated for all important reactions identified for CFRMF material constituents. Several sensitivities are quite large, including those for ^{10}B capture, ^{238}U elastic and inelastic scattering, ^{238}U capture, H total, Fe total, ^{238}U χ and ν , and ^{235}U χ and ν . The main coupling between the thermal driver core and the central fast-flux spectrum is through the ^{235}U fission spectrum. Total sensitivities for ^{238}U determined by adjoint sensitivity theory compared well with those computed by the direct method.

Table 3.51.1 lists the central relative flux, the relative standard deviations, and the flux correlation matrix. Since this matrix is symmetric, only the lower triangle is shown. The uncertainties in the fast-group fluxes are due mainly to uncertainties in the fission spectrum and the inelastic-scattering cross sections of ^{238}U . The ^{238}U scattering data have large uncertainties as well as large sensitivities, so they are the main contributors to the flux standard deviations throughout the energy range. Capture cross-section uncertainties for ^{238}U are large contributors at lower energies, while fission cross-section uncertainties for ^{238}U are large contributors at the highest energies. Hydrogen is important at lower energies. The ^{10}B cross-section sensitivities are very high, but the corresponding uncertainties are low, so ^{10}B does not affect the spectrum standard deviations as much as the ^{238}U data.

Table 3.51.1. CFRMF Central Relative Flux per Unit Lethargy and Flux Correlation Matrix with Relative Standard Deviations Due to Cross-Section Uncertainties

Upper Boundary (eV)	Central Relative Flux	1 Rel. Std. Dev.	Group Index	CFRMF Central Flux Correlation Matrix (10*2)																						
1.7330+7	0.6684-3	12.99	1	100																						
1.0000+7	0.1097-1	8.83	2	56	100																					
6.0633+6	0.5029-1	8.50	3	29	91	100																				
3.6788+6	0.1065+0	2.14	4	14	83	98	100																			
2.2313+6	0.1424+0	6.84	5	08	79	97	100	100																		
1.3534+6	0.2197+0	3.67	6	06	73	90	94	95	100																	
8.2085+5	0.3272+0	2.47	7	-05	-53	-64	-66	-66	-45	100																
4.9787+5	0.3149+0	2.39	8	-07	-72	-88	-91	-91	-79	88	100															
3.1097+5	0.2493+0	2.52	9	-10	-79	-96	-98	-99	-93	68	93	100														
1.8316+5	0.1801+0	5.09	10	-07	-41	-59	-51	-51	-61	-05	25	44	100													
1.1109+5	0.1283+0	4.17	11	-10	-48	-56	-57	-57	-73	-18	23	51	90	100												
6.7380+4	0.8945-1	4.37	12	-09	-45	-48	-48	-48	-54	06	33	50	-10	32	100											
4.0868+4	0.5201-1	5.15	13	-10	-35	-49	-39	-38	-40	14	32	41	-34	06	94	100										
2.4788+4	0.3529-1	3.29	14	-17	-42	-44	-43	-42	-43	20	36	44	-30	06	85	95	100									
1.5034+4	0.2341-4	3.53	15	-21	-46	-47	-45	-43	-43	25	38	42	-1	10	55	66	85	100								
9.1188+3	0.1619-1	3.53	16	-22	-46	-46	-44	-43	-41	26	37	40	02	14	34	45	63	86	100							
5.5308+3	0.1403-1	3.02	17	-27	-54	-54	-51	-50	-48	31	43	46	13	21	31	38	53	72	91	100						
3.3546+3	0.1008-1	2.89	18	-28	-57	-56	-53	-51	-50	32	45	49	21	26	32	38	52	71	87	99	100					
2.0347+3	0.8847-2	2.68	19	-31	-61	-61	-57	-55	-54	35	48	53	23	30	33	39	54	74	84	93	99	100				
1.2341+3	0.8104-2	2.97	20	-28	-51	-54	-51	-50	-48	31	43	47	21	27	29	35	50	70	80	90	99	100				
7.4852+2	0.5149-2	2.95	21	-28	-66	-55	-52	-50	-48	32	43	47	21	27	29	36	50	71	82	95	96	99	100			
4.5400+2	0.3193-2	2.88	22	-29	-57	-56	-53	-51	-50	32	44	48	22	28	30	36	51	72	83	94	97	100	100			
2.7536+2	0.2358-2	3.10	23	-27	-53	-52	-49	-48	-46	30	41	45	20	26	28	34	49	61	74	84	94	98	100	100		
1.6702+1	0.5474-3	2.98	24	-29	-55	-54	-51	-49	-48	31	43	46	21	27	29	36	51	73	84	94	97	99	99	100	100	
1.0130+2	0.8697-3	4.00	25	-22	-41	-41	-38	-37	-36	22	31	34	15	19	21	27	46	64	74	84	93	97	97	98	98	100
6.1642+1	0.1644-5	3.14	26	-28	-53	-52	-48	-47	-45	29	40	44	20	25	27	34	52	69	88	89	91	92	93	93	94	92

Finally, the full flux-spectrum covariance matrix for the CFRMF is strongly correlated. Thus, there is a strong motivation for including the off-diagonal elements in data-testing and cross-section adjustment application.

* Research sponsored by DOE Office of Reactor Research and Technology.

† EG&G Idaho.

‡ University of Tennessee.

§ UCC-ND Computer Sciences Division.

¶ On leave from The Hebrew University of Jerusalem, Israel.

1. J. W. Rogers, D. A. Millsap, and Y. D. Harker, "CFRMF Neutron Field Flux Spectral Characterization," Nucl. Tech. 25, 330 (1975).
2. N. M. Greene et al., "AMPX: A Modular Code System for Generating Coupled Multigroup Neutron-Gamma Libraries from ENDF/B," ORNL/TM-3706 (1976).
3. J. L. Lucius et al., "A Users Manual for the FORSS Sensitivity and Uncertainty Analysis Code System," ORNL-5316 (1977).
4. B. L. Broadhead et al., "Calculation of the Flux Covariance Matrix for the National Bureau of Standards - Intermediate Energy Standard Neutron Field," Trans. Am. Nucl. Soc. 30, 590 (1978).

APPLICATION OF SENSITIVITY AND UNCERTAINTY ANALYSIS TO REACTOR PHYSICS AND SAFETY

3.52. UNCERTAINTY IN THE BREEDING RATIO OF A LARGE LIQUID-METAL FAST BREEDER REACTOR: THEORY AND RESULTS

J. H. Marable C. R. Weisbin G. de Saussure

(Abstract of Nucl. Sci. Eng. 75, 30, 1380)

Using an extensive data base of sensitivities and evaluated covariances, this work incorporates 11 fast-reactor benchmark experiments and 2 neutron-field benchmark experiments into the adjustment of a 26-group cross-section library based primarily on Evaluated Nuclear Data File (ENDF)/B-IV. The covariance data include correlations between cross sections for different energies, reactions, and materials, and between integral experiments, and covariances of calculational bias factors due to specific modeling and calculational procedures. The adjustments of the group cross sections are examined in some detail and are smaller than the estimated standard deviations. The results of the adjustment are applied to the determination of the uncertainties in the multiplication factor and in the breeding ratio of a large liquid-metal fast breeder reactor design model fixed by the Large Core Code Evaluation Working Group. For this static model the adjustment procedure reduces the calculated uncertainty in k_{eff} from 3.1% to 0.5% and in breeding ratio for the critical reactor from 3.5% to 1.9%.

* Research sponsored by DOE Office of Reactor Research Technology.

3.53. GENERALIZED SENSITIVITY THEORY APPLIED TO THE MELT-IIIA FAST REACTOR SAFETY CODE*

P. J. Maudlin[†] C. V. Parks[†]

(Reprint of Trans. Am. Nucl. Soc. 34, 520, 1980)

Sophisticated techniques^{1,2} for the evaluation of modeling parameter sensitivities for large computer codes are very beneficial to the model developer, the analyst, and the experimentalist. The substantial advantages of using these techniques are currently being recognized by the industry in the area of reactor safety. This summary describes an application of the technique introduced by Obiw,² called Generalized Sensitivity Theory (GST), to the neutronics/thermal/hydraulics fast reactor safety code MELT-IIIA.³ Previous GST work with MELT⁴ contained a thermal application only; this summary expands the adjoint MELT code (MELTADJ) described in Ref. 4 to include hydraulics.

The application of GST involves the development and solution of equations that are adjoint to the forward equations (those used in the code simulation). The forward and adjoint solutions are then integrated to provide the sensitivity coefficients $(dR/R)/(da/a)$, where R is the response function and a is the modeling parameter for which the sensitivity is desired. The main advantage of GST is that sensitivities to a large input parameter field can be obtained from the information provided by only two computer code runs: a forward base case and its corresponding adjoint.

Note that GST should not be confused with generalized perturbation theory which is typically applied in the first order to obtain estimates containing errors of second order; the strict application of GST theoretically yields exact derivative results.⁵

The forward conservation equations for the fuel pin temperature T , sodium coolant velocity u , sodium pressure P , and sodium temperature T_c solved in MELT-IIIA are:

pin energy:

$$\rho C_p \frac{\partial T}{\partial t} + \frac{1}{r} \frac{\partial}{\partial r} \left(-rk \frac{\partial T}{\partial r} \right) = Q_{gen} \quad (1)$$

sodium continuity:

$$\frac{D}{Dt} (A_0) = -A_0 \frac{\partial u}{\partial z} \quad (2)$$

sodium momentum:

$$\rho \frac{Du}{Dt} = -\rho \frac{fu^2}{2D} - \frac{\partial P}{\partial z} - \sum_i \delta(z-z_i)^{1/2} \rho u^2 K_L - \rho \quad (3)$$

sodium energy:

$$A_0 C_p \frac{DT_c}{Dt} = \frac{\partial}{\partial z} \left(A_k \frac{\partial T_c}{\partial z} \right) + 2\pi Rh(T-T_c) \quad (4)$$

The notation D/Dt designates the one-dimensional substantial or total derivative, and the $\delta(z-z_i)$ term is a dirac delta function representation of the abrupt area change pressure losses that occur at spatial locations z_i .

Assuming a temperature response function of the form:

$$R = \int_t \int_r [fT(r,t) + gT_c(r,t)] dr dt \quad (5)$$

where f and g can be specified as delta or step functions to yield peak or average temperature responses in the fuel, cladding, or coolant, the corresponding adjoint (or importance) conservation description to Eqs. (1) through (4) is

pin energy*:

$$-\rho C_p \frac{\partial T^*}{\partial t} - k \frac{1}{r} \frac{\partial}{\partial r} \left(r \frac{\partial T^*}{\partial r} \right) = f \quad (6)$$

sodium continuity*:

$$-A_0 \frac{\partial u^*}{\partial z} = \frac{\partial}{\partial t} (\rho P^*) + u P^* \frac{\partial \rho}{\partial z} - \rho \frac{f_u}{D} P^* - A_0 C_p T_C^* \frac{\partial T_C}{\partial z} - P^* \sum_i \delta(z-z_i) \rho u K_L \quad (7)$$

sodium momentum*:

$$\frac{\partial P^*}{\partial z} = 0 \quad (8)$$

sodium energy*:

$$\begin{aligned} -A_0 C_p \frac{\partial T_C^*}{\partial t} - \rho C_p \frac{\partial}{\partial z} (A u T_C^*) &= g + A k \frac{\partial^2 T_C^*}{\partial z^2} \\ + 2 \pi R h (T^* - T_C^*) + A \frac{\partial \rho}{\partial T} \frac{D u^*}{D t} + \frac{1}{\rho} \frac{\partial \rho}{\partial T} \frac{\partial P}{\partial z} P^* \end{aligned} \quad (9)$$

The superscript * designates adjoint functions. The procedure for deriving Eqs. (5) through (9), along with the appropriate adjoint boundary conditions, initial conditions, and mathematical form of the sensitivity coefficients, is illustrated in detail in Ref. 2.

Table 3.53.1 presents MELT input field sensitivity results for an FFTF geometry, single-phase power ramp transient (power increases 1% per 5 s); this base case transient is described in more detail in Ref. 4. A peak temperature response is chosen for this investigation. The input parameters for which sensitivities are obtained are listed in column one. Columns two and three give the mathematical form and numerical value of the GST sensitivity coefficients. Column four gives the "exact" numerical values of "brute-force" coefficients recalculated using 1% perturbations of the forward MELT input parameters.

The good agreement between GST and the recalculated coefficients in Table 3.53.1 validates the GST approach. The computer time savings of using GST in lieu of recalculation for just the small subset of the MELT input field shown in Table 3.53.1 is 83%. This savings percentile increases as the number of input parameters investigated in the sensitivity study increases, eventually approaching the upper limit of 100% when investigating the input fields of very large computer programs.

* Research sponsored by U.S. DOE Office of Nuclear Energy Programs, Division of Nuclear Research and Applications.

† UCC-NC Computer Sciences Division.

1. J. K. Vario, J. M. Kyser, and L. Myne, "Statistical Sensitivity Analysis of a Safety Evaluation Code," Proc. Int. Mtg. on Fast Reactor Safety Technology in Seattle, Washington, 1, 59 (1979).
2. E. M. Oblow, "Sensitivity Theory for Reactor Thermal-Hydraulics Problems," Nucl. Eng. 68, 322 (1978).

Table 3.53.1. Comparison of Several Peak Fuel Temperature Sensitivity Coefficients Chosen from the MELT Thermal-Hydraulics Input Parameter Field

Input Parameter α	Mathematical Form of GST Sensitivity Coefficient	$\frac{dR}{d\alpha/\alpha}$ in %/1%	
		GST	MELT Recalculation
Q_{gen}	$\langle T^* Q_{gen} \rangle$	15.1	15.4
$(\rho C_p)_{fuel}$	$-\langle T^* \frac{\partial T}{\partial t} \rho C_p \rangle$	-1.1	-1.1
$(\rho C_p)_{clad}$	$-\langle T^* \frac{\partial T}{\partial t} \rho C_p \rangle$	-1×10^{-4}	--
k_{fuel}	$-\langle \frac{\partial T^*}{\partial r} \frac{\partial T}{\partial r} k \rangle$	-9.4	-9.4
k_{clad}	$-\langle \frac{\partial T^*}{\partial r} \frac{\partial T}{\partial r} k \rangle$	-0.3	-0.3
k_{gap}	$-\langle \frac{\partial T^*}{\partial r} \frac{\partial T}{\partial r} k \rangle$	-2.6	-2.7
$\rho_{coolant}$	$\langle P^* \frac{\partial P}{\partial z} - T_c^* \frac{DT_c}{Dt} A \rho C_p \rangle - \langle P^* 2f_{loop} w^2 \rangle_{z=0}$	-0.37	-0.37
T_{inlet}	$\langle T_c^* T_c A \rho C_p w \rangle_{z=0} + \langle u^* A u \frac{\partial \rho}{\partial T_c} \rangle_{z=0}$	3.7	3.7
Pump Head	$\langle P^* \Delta P_{pump} \rangle$	-0.69	-0.69
f_{loop}	$-\langle P^* (A \rho u)_{loop} f_{loop} \rangle$	0.20	0.20
$(\rho g H)_{cold leg}$	$\langle P^* (\rho g H)_{cold leg} \rangle$	-0.30	-0.30
C_p coolant	$-\langle T_c^* \frac{DT_c}{Dt} A \rho C_p \rangle$	-1.4	-1.4

"< >" denotes integration over the appropriate space and time domain.

3. A. E. Waltar et al., "MELT-III: A Neutronics, Thermal-Hydraulics Computer Program for Fast Reactor Safety Analysis," HEOL-TME 74-47, Hanford Engineering Development Lab. (1974).
4. C. V. Parks, E. T. Tomlinson, and E. M. Obrow, "The Application of Generalized Perturbation Theory to Fast Reactor Safety Sensitivity Studies," Proc. Int. Mtg. on Fast Reactor Safety Technology in Seattle, Washington, 1, 69 (1979).
5. E. M. Obrow, "Sensitivity Theory from a Differential Viewpoint," Nucl. Sci. Eng. 59, 187 (1976).

3.54. PERTURBATION AND SENSITIVITY THEORY FOR REACTOR BURNUP ANALYSIS*

M. L. Williams

(Abstract of ORNL/TM-7096, December 1979)

Perturbation theory is developed for the nonlinear burnup equations describing the time-dependent behavior of the neutron and nuclide fields in a reactor core. General aspects of adjoint equations for nonlinear systems are first discussed and then various approximations to the burnup equations are rigorously derived and their areas for application presented. In particular, the concept of coupled neutron/nuclide fields (in which perturbations in either the neutron or nuclide field are allowed to influence the behavior of the other field) is contrasted to the uncoupled approximation (in which the fields may be perturbed independently).

Adjoint equations are derived for each formulation of the burnup equations, with special attention given to the quasi-static approximation, the method employed by most space- and energy-dependent burnup codes. It is shown that, based on this formulation, three adjoint equations (for the flux shape, the flux normalization, and the nuclide densities) are required to account for coupled variations in the neutron and nuclide fields. The adjoint equations are derived in detail using a variational principle. The relation between coupled and uncoupled depletion perturbation theory is illustrated.

Solution algorithms are given for numerically solving the adjoint burnup equations, and the implementation of these procedures into existing computer codes is discussed. A physical interpretation is given for the burnup adjoint functions, which leads to a generalization of the principle of "conservation of importance" for coupled fields. Analytic example problems are solved to illustrate properties of the adjoint functions.

Perturbation theory is used to define sensitivity coefficients for burnup-dependent responses. Specific sensitivity coefficients are written for different types of nuclear data and for the initial condition of the nuclide field. Equations are presented for uncertainty analysis of burnup calculations.

Uncoupled depletion sensitivity theory is applied to the analysis of an irradiation experiment being used to evaluate new actinide cross section data. The computed sensitivity coefficients are used to determine the sensitivity of various nuclide concentrations in the irradiated sample to actinide cross sections. Uncertainty analysis is used to calculate the standard deviation in the computed values for the plutonium isotopics.

Coupled depletion sensitivity theory is used to analyze a 3000 MW_{th} denatured LMFBR model (2 region, sphere). The changes in the final inventories of ²³²U, ²³³U, and ²³⁹Pu due to changes in concentrations of several nuclides at the beginning of cycle are predicted using depletion perturbation theory and are compared with direct calculation. In all cases the perturbation results show excellent agreement with the direct changes.

* Research sponsored by DOE Office of Reactor Research and Technology.

3.55. A TECHNIQUE FOR SENSITIVITY ANALYSIS OF SPACE- AND ENERGY-DEPENDENT BURNUP CALCULATIONS*

M. L. Williams J. R. Whit[†] T. J. Burns

(Reprint of Trans. Am. Nucl. Soc. 32, 766-768, 1979)

In this paper, expressions for depletion sensitivity coefficients are presented that can be applied to responses depending on both the neutron and the nuclide fields encountered in burnup analysis. The sensitivity coefficients are based on perturbation theory for coupled neutron-nuclide fields in which the nonlinear coupling between the neutron flux and nuclide densities are treated in detail.^{1,2} Sensitivity coefficients both for changes in nuclear data and changes in the initial condition of the nuclide field are discussed. An example application to an LMFBR burnup analysis is cited.

In depletion calculations, one must deal with both the neutron flux field $\phi(r, E, t)$ and the nuclide density field $N(r, t)$, which obey the nonlinear burnup equations. In general, the computed "response" will be a functional of both fields, $R = R(N, \phi)$. For example, R may be the end-of-cycle k_{eff} . It is customary to solve the burnup equations in a quasi-static manner by breaking the time domain into a number of broad time intervals,

$$(t_0, t_1), (t_1^+, t_2), \dots, (t_{f-1}^+, t_f)$$

Over these intervals the flux can be approximated by a stepwise continuous function, expressed in terms of a shape function and a normalization factor,

$$\phi(r, E, t) = \phi_i \psi_i(r, E), \quad t_i^+ < t < t_{i+1}^-$$

The shape function is found by solving the diffusion equation at the beginning of the interval, and is normalized to unity. The normalization factor is chosen to satisfy the specified power production. Using this flux, the nuclide field is then computed over the interval by solving the transmutation equation, with the initial condition $N(r, t_i) = N(r, t_i^+)$.

Using a variational technique, it will be shown that three coupled linear equations can be derived for the adjoint system to the burnup equations. These are†

Flux-normalization adjoint:

$$P_i^* = \frac{\int_{t_i^+}^{t_{i+1}^-} (N^*(\psi_i R)_{E,N})_V dt + \frac{\partial R}{\partial \phi_i}}{(\psi_i \sigma_f N_i)_{E,V}} \quad \text{at } t = t_i \quad (1)$$

Flux-shape adjoint:

$$[L^*(N_i) - \lambda_i F^*(N_i)] \Gamma_i^* = Q_i^*, \quad \text{at } t = t_i \quad (2)$$

where

$$Q_i^* = \frac{\partial R}{\partial \psi_i} + \phi_i \int_{t_i^+}^{t_{i+1}^-} N^*(\vec{r}, t) R(\sigma) N(\vec{r}, t) dt - \phi_i P_i \sigma_f N_i$$

and $\lambda = 1/k$.

Nuclide adjoint:

$$M^* N^* + \frac{\partial R}{\partial N} = - \frac{\partial}{\partial t} N^*, \quad t_i^+ < t < t_{i+1}^- \quad (3)$$

together with time boundary conditions

$$N^*(t_f) = \frac{\partial R}{\partial N}(t_f), \quad \text{at } t = t_f$$

and

$$N^*(r, t_i^-) = \left[N^*(r, t_i^+) - \Gamma_i^* \frac{\partial}{\partial N_i} (L - \lambda F) \psi_i + \phi_i P_i \sigma_f \psi_i \right]_E \quad \text{at } t_i, \quad i \neq f$$

This expression for $N^*(r, t_i^-)$ specifies a "jump condition" on the nuclide adjoint. In these equations,

$L^* - \lambda F^*$ = adjoint of diffusion operator $L - \lambda F$,

M^* = transpose of transmutation operator M ,

R = cross-section elements of transmutation operator.

Using the forward and adjoint burnup solutions, the sensitivity coefficient S_α for differential data $\alpha(r, E)$ can be defined such that

$$\frac{\Delta R}{R} = \left[S_\alpha(r, E) \cdot \frac{\Delta \alpha(r, E)}{\alpha(r, E)} \right]_{V, E}$$

The sensitivity coefficient for a change in the initial concentration of nuclide m is defined by

$$\frac{\Delta R}{R} = \left[S_m(r) \cdot \frac{\Delta N_m(r, 0)}{N_m(r, 0)} \right]_V$$

Based on this theory, a time-dependent sensitivity module called DEPTH has been developed and integrated with the VENTURE/BURNER modular code system.³ A simplified test problem has been utilized to examine the adequacy of the sensitivity module as well as the coupled neutron/nuclide perturbation concept in general. Although two- and three-dimensional modeling is possible, a 1-D spherical reactor model with three core regions and two blanket zones was chosen to benchmark the capability. Nine-group cross sections generated using a fast reactor spectrum were employed for all calculations. Test responses included k_{eff} and various nuclide inventories after some period of reactor operation. The effects of several perturbations were investigated including fissile, fertile, and structural material variations (i.e., design changes).

A comparison of some typical perturbation results with direct calculations is given in Table 3.55.1 for the case of a 20% denatured LMFBR after 91 days of reactor operation. The last two columns indicate that accurate results can be obtained using this perturbation approach. Further investigation has shown that the observed differences relative to the direct calculations can be attributed to nonlinear effects. In all cases, if the amount of perturbation is reduced to only a few percent, the direct and perturbation results become identical.

Also displayed in Table 3.55.1 are the relative contributions of the three adjoint functions. The N^* effect is the same result that would be obtained from uncoupled perturbation theory.⁴ It is the P^* and r^* effects that differentiate the coupled from the uncoupled perturbation formulation. It should be noted, however, that the r^* effect is negligible for many of the cases tabulated. This is important since the majority of the overall computational effort was expended in calculating this term. This imbalance becomes more pronounced as the size of the problem increases. Therefore, an option to bypass the $r^*(F, E)$ calculation has been built into the DEPTH module. The consequence of this option is a fast, inexpensive, but slightly less general perturbation theory result. It should be emphasized, however, that the maximum cost of a full adjoint calculation is roughly the same as the reference forward depletion calculation.

The depletion perturbation theory capability summarized above represents an attractive alternative computational method for burnup analysis. Since space- and time-dependent sensitivity coefficients are a by-product of this approach, a more detailed understanding of various neutronic processes is possible. Time-dependent perturbation theory may also lead to improvements in core optimization techniques since the effect of initial design changes on responses such as end-of-cycle k_{eff} , fissile inventory, net fissile gain, breeding ratio, etc. can be easily determined.

Table 3.55.1. Comparison of Coupled Neutron/Nuclide Perturbation Theory Results with Direct Calculations

Specified response ($T_f = 91$ days)	Case ^a	Percent change in response				
		Perturbation results				Direct calculation
		K^{Δ} effect	P^{Δ} effect	Γ^{Δ} effect	Net	
K_{eff}	1	-0.9094	0.0040	-0.0093	-0.9137	-0.9017
	2	4.2584	0.3015	-0.0164	4.5436	4.4312
	3	1.8353	0.1644	0.0461	2.0458	2.0380
	4	-0.0654	-	-0.0127	-0.0781	-0.0653
^{232}U Inventory	1	2.1705	-0.1189	0.0534	2.1050	2.0985
	2	7.3401	-8.8703	2.5673	1.0370	1.2806
	3	4.0213	-4.8351	1.5027	0.6890	0.8531
	4	-	-	-2.8108	-2.8108	-2.7300
^{233}U Inventory	1	0.1834	0.0029	-0.0058	0.1805	0.1801
	2	5.8030	0.2162	-0.0465	5.9726	6.0735
	3	4.1991	0.1178	0.0929	4.4099	4.4145
	4	-	-	-0.0698	-0.0698	-0.0687
^{239}Pu Inventory	1	-	-0.0154	-0.0306	-0.0460	-0.0468
	2	-	-1.0646	-0.2058	-1.2704	-1.2716
	3	-	-0.6253	-0.1330	-0.7583	-0.7425
	4	-	-	0.1294	0.1294	0.1291

^aCase 1 - 10% increase in initial ^{232}Th concentration in all core zones.

Case 2 - 10% increase in initial ^{233}U concentration in all core zones.

Case 3 - 10% increase in initial ^{233}U concentration in core zone #3.

Case 4 - 10% increase in initial stainless steel concentration in all core zones.

* Research sponsored by DOE Office of Reactor Research and Technology.

† UCC-ND Computer Sciences Division.

‡ $[\]_{x,y}$. . . indicates integration over x,y

1. M. L. Williams and C. R. Weisbin, "Sensitivity and Uncertainty Analysis for Functionals of the Time-Dependent Nuclide Density Field," ORNL-5393 (1978).
2. M. L. Williams, "Development of Depletion Perturbation Theory for Coupled Neutron-Nuclide Fields," ORNL/TM-5958 (1972).
3. D. R. Vondy, T. B. Fowler, G. W. Cunningham, and L. M. Petrie, "A Computation System for Nuclear Reactor Core Analysis," ORNL-5158 (April 1977).
4. A. Gandini, "Time-Dependent Generalized Perturbation Theory for Burnup Analysis," CNEN RT/FI(75), 4, CNEN, Rome (1975).

3.56. EVALUATION OF INTEGRAL PARAMETER CORRELATIONS AND REACTOR PERFORMANCE USING NUCLEAR DATA COVARIANCES*

C. D. Rinaldis[†] J. M. Kallfelz[†] E. Kujawski[‡] J. H. Marable

(Reprint of Trans. Am. Nucl. Soc. 33, 859, 1979)

A previous study¹ in our joint investigations illustrated the importance of considering the strong interplay of nuclear, mechanical, and thermal-hydraulic (T-H) aspects in assessment of reactor design. In this summary we discuss methods for utilizing covariance information to evaluate integral parameter correlations and the associated economic uncertainties.

We illustrate the impact of such correlations with an example which employs only nuclear data covariance files, but the method is meant to include non-nuclear data as well. Indeed, the inclusion of the latter has become more practical with the growth of data banks which contain information on uncertainties of T-H and mechanical properties² and the development of sensitivity theory for T-H problems.³

ENDF/B covariance matrices [COV] contain information on both the standard deviation, SD, and correlation of various cross sections.⁴ The use of [COV] to calculate SD for the breeding ratio, BR, and the multiplication constant, k, have been discussed in Ref. 5. For an integral parameter, I, e.g., BR or k,

$$\text{VAR}(I) = \sum_{i,j} \frac{\partial I}{\partial \sigma_i} \frac{\partial I}{\partial \sigma_j} \text{COV}(\sigma_i, \sigma_j) \quad (1)$$

where the partial derivatives are sensitivity coefficients⁵ and the variance, VAR, is SD².

This formalism can be extended to estimate the standard deviation of electricity cost using

$$\text{VAR}(\$) = \sum_{i,j} \frac{\partial \$}{\partial I_i} \frac{\partial \$}{\partial I_j} \text{COV}(I_i, I_j) \quad (2)$$

where

\$ = fuel cycle cost (or another reference value, such as core cost¹)

I_i = integral parameter i

$\text{COV}(I_i, I_j)$ = covariance matrix element describing the correlation between I_i and I_j . For $i = j$ this element is SD².

If we consider only nuclear parameters,

$$\text{COV}(I_k, I_l) = \sum_{i,j} \frac{\partial I_k}{\partial \sigma_i} \frac{\partial I_l}{\partial \sigma_j} \text{COV}(\sigma_i, \sigma_j) \quad (3)$$

The cost sensitivity coefficients, $\partial \$ / \partial I_i$, can be calculated with COROPT,⁶ while the $\text{COV}(I_k, I_l)$ can be calculated with the methods described in Refs. 5 and 7.

If one assumes no correlation, the [COV] matrix in Eq. (2) has only diagonal terms, and

$$\text{VAR}(\$) = \sum_i \left[\frac{\partial \$}{\partial I_i} \text{SD}(I_i) \right]^2 \quad (4)$$

Expression (4) is similar to the expression used in Ref. 8 to obtain the uncertainty ranges of fuel costs and various integral parameters, at a time when detailed covariance information for neutron cross sections was not available.

For the following example we limited the integral parameters to BR and the critical enrichment, ϵ , so the results of Eq. (2) are not the true variance since not all significant integral parameters are included. Furthermore, the absolute values are influenced by uncertainties in the economic parameters we used (from the sample case in Ref. 6) and differences in methods used to determine the integral parameters in COROPT and the codes used in Ref. 5. However, the difference between the results for the relative variance, $\text{VAR}(\$/\$^2)$, from Eqs. (2) and (4), calculated in a consistent manner, is significant. It demonstrates the influence on the estimated cost uncertainties of considering the integral parameter correlation.

The reactor considered for this example is that described in the first problem issued by the Large Core Code Evaluation Working Group (LCCENG).⁹ The calculation of the integral parameter [COV] matrix of Eq. (3) was accomplished with the cross-section [COV] matrix and sensitivity coefficients available from the work reported in Ref. 5, while the cost sensitivity coefficients of Eqs. (2) and (4) were calculated with COROPT.⁶ It should be noted that ENDF/B-IV covariance matrices were used, and the values of the cross section [COV] could be considerably different if adjusted cross-section values⁵ were used.

The integral data sensitivity coefficients $\partial\$/\partial I$ used were consistent in that they were both true partial derivatives, with all other parameters fixed. Thus, the COROPT runs were sensitivity runs with no "reoptimization"^{1,6} of the design after the integral parameter change, while the BR sensitivity coefficients used from Ref. 5 were those without an enrichment change for "k-reset." Note that the correlation between BR and the critical enrichment is included in Eq. (2).

The $\text{COV}(\epsilon, \text{BR})$ matrix element was derived from that for $\text{COV}(k, \text{BR})$ using the calculated value

$$\frac{k}{\epsilon} \frac{d\epsilon}{dk} = -1.82$$

(ϵ is the critical enrichment; hence, the negative sign.)

Calculated values of interest are given in Table 3.56.1. The correlation coefficient, defined in the table footnote (b) of 0.89 indicates the strong correlation between BR and ϵ . As expected, considering this correlation reduces the relative variance of the fuel cycle cost appreciably, with an associated reduction in $\text{SD}(\$)$. This demonstrates the importance of considering such correlations in evaluating the uncertainties in the economic performance of various reactor designs. As suggested in Ref. 1, such uncertainties may influence the decision process.

*Research sponsored by DOE Office of Reactor Research and Technology.

†Georgia Institute of Technology.

‡General Electric Company.

1. E. Kujawski, J. M. Kallfelz, and J. H. Marable, "Nuclear Uncertainties as a Consideration in Reactor Designs," Trans. Am. Nucl. Soc. 32, 791 (1979).
2. M. M. Greene et al., "SACRD: A Data Base for Fast Reactor Safety Computer Codes-General Description," ORNL-5477 (January 1979).
3. E. M. Oblow, "Sensitivity Theory for Reactor Thermal-Hydraulics Problems," Nucl. Sci. Eng. 68, 332 (1978).

Table 3.56.1. Some Calculated Results for an Example Considering Two Integral Parameters, BR and ϵ (see text)^{a,b}

(For these values \$ is the fuel cycle cost, 4.335 mill/kWh.)

Parameters	From Eq. (2) (with correlation)	From Eq. (4) (without correlation)
$\frac{VAR(\$)}{(\$)^2}$	3.41 -03	4.99 -03
$\frac{SD(\$)}{\$}$	5.84 -02	7.06 -02
${}^rSD(\$)$	0.25 mill/kWh	0.31 mill/kWh

^aThe following calculated values were used to obtain the above results:

$$\frac{BR}{\$} \frac{\partial \$}{\partial BR} = -1.14; \frac{\epsilon}{\$} \frac{\partial \$}{\partial \epsilon} = 0.35$$

$$[COV] = \begin{bmatrix} \frac{SD^2(\epsilon)}{\epsilon^2} & \frac{COV(BR, \epsilon)}{BR \cdot \epsilon} \\ \frac{COV(\epsilon, BR)}{\epsilon \cdot BR} & \frac{SD^2(BR)}{BR^2} \end{bmatrix} = \begin{bmatrix} 1.31-03 & 1.95-03 \\ 1.95-03 & 3.70-03 \end{bmatrix}$$

^bNote that $\frac{SD(\epsilon)}{\epsilon} = 3.6\%$, $\frac{SD(BR)}{BR} = 6.1\%$, and

$$\text{Correlation coefficient} = \frac{COV(\epsilon, BR)}{SD(\epsilon) \cdot SD(BR)} = 0.89$$

4. F. G. Perey, G. de Saussure, and R. B. Perez, "Estimated Data Covariance Files of Evaluated Cross Sections—Examples for ^{235}U and ^{238}U ," in Advanced Reactors: Physics, Design, and Economics, p. 578, J. M. Kallfelz and R. A. Karam, Eds., Pergamon Press, Oxford and NY (1975).
5. J. H. Marable and C. R. Weisbin, "Uncertainties in the Breeding Ratio of a Large LMFBR," Proc. ANS Physics Division Topl. Mtg., Gatlinburg, Tennessee (April 1978).
6. G. V. Neill and D. P. Johnson, "COROPT: A Computer Program for Finding Optimum LMFBR Mixed-Oxide Fuel Cores," GEFR-00006, UC-798, General Electric, Sunnyvale, CA (January 1977).
7. C. R. Weisgin et al., "Applications of FORSS Sensitivity and Uncertainty Methodology to Fast Reactor Integral Experiment Analysis," Nucl. Sci. Eng. 66, 307 (1978).
8. P. Greebler, B. A. Hutchins, and R. B. Linford, "Sensitivity of Fast Reactor Economics to Uncertainties in Nuclear Data," Nucl. Appl. 4, 297 (1968).
9. E. Kujawski and H. S. Bailey, "Benchmark Analysis of Liquid Metal Fast Breeder Reactor Nuclear Design Methods," Nucl. Sci. Eng. 64, 90 (September 1977).

3.57. DESIGN AND SENSITIVITY ANALYSIS OF A CDS-TYPE HETEROGENEOUS CORE*

J. M. Kallfelz[†] D. Biswas[†] C. L. Cowan[†]
 J. H. Marable M. L. Williams C. R. Weisbin
 J. D. Drischler T. B. Fowler J. R. White

(Abstract of paper presented at ANS Topical Meeting on Advances in Reactor Physics and Shielding, Sun Valley, Idaho, September 14-17, 1980)

The design of a heterogeneous LMFBR of the type being considered for the Conceptual Design Study (CDS) is analyzed, using sensitivity analysis methods. Nuclear data sensitivities for k_{eff} , the breeding ratio, and parameters related to the peak linear power (space-dependent power densities) are determined with generalized perturbation theory. These sensitivities are folded with extensive nuclear data covariance information to determine the associated integral parameter uncertainties and correlations. The effects of non-localized energy deposition were investigated by folding the results of coupled (n- γ) calculations with kerma factors.

*Research sponsored by DOE Office of Reactor Research and Technology.

[†]Georgia Institute of Technology.

[‡]General Electric Company, Sunnyvale.

3.58. IMPLEMENTATION OF GENERALIZED PERTURBATION THEORY INTO THE 3-D NODAL CODE SIMULATE*

S. M. Bowman[†] M. L. Williams H. L. Dodds[†]

(Reprint of Trans. Am. Nucl. Soc. 34, 306, 1980)

Determining the effects of changes in design and data parameters on reactor performance can be very expensive when many perturbations must be considered for a complex system. To substantially reduce the cost involved in calculations such as these, generalized perturbation theory (GPT) capability has been implemented into the 3-D LWR nodal reactor analysis code SIMULATE.¹ This capability makes 3-D sensitivity analysis of a realistic LWR practical for the first time. Applications to design analysis will be discussed.

SIMULATE solves an eigenvalue equation, which can be written in matrix form as¹

$$(M - \lambda F)S = 0 \quad (1)$$

where

$M, F \equiv$ nodal coupling coefficients which may be complicated expressions in terms of nodal macroscopic cross sections

$\lambda \equiv$ eigenvalue $= 1/k_{eff}$

$S \equiv$ fission neutron source vector.

The nodal coupling coefficients can be calculated by any one of several options in SIMULATE (e.g., coarse-mesh diffusion theory, FLARE, ROCS, PRESTO).¹

SIMULATE was first modified to solve the adjoint of Eq. (1):

$$(M^* - \lambda F^*)S^* = 0 \quad (2)$$

where ** represents the adjoint operator. The first-order approximation of the change in k_{eff} is then calculated by²

$$\Delta \lambda = \frac{1}{k'_{eff}} - \frac{1}{k_{eff}} = \frac{S^{*T}(\Delta M - \lambda \Delta F)S}{S^{*T}FS} \quad (3)$$

where k_{eff} and k'_{eff} represent the unperturbed and the perturbed quantities, respectively. The effect of a design parameter change (e.g., a change in nodal enrichment) can be related to changes in nodal coupling coefficients by a first-order Taylor series expansion

$$\Delta M \equiv \frac{\partial M}{\partial p} \Delta p; \quad \Delta F \equiv \frac{\partial F}{\partial p} \Delta p,$$

where $p \equiv$ the design parameter that is changed. Substituting the above relations into Eq. (3) relates Δp to $\Delta \lambda$.

Predicting changes in responses other than k_{eff} with perturbation theory requires the solution of the generalized, or fixed source, adjoint equation³

$$(M^{*} - \lambda F^{*})\Gamma^{*} = Q^{*} \quad (4)$$

where Q^{*} is defined such that

$$S^{*T}Q^{*} = 0 \quad (5)$$

SIMULATE has also been modified to solve Eq. (4), using the method of successive approximations. Some care must be exercised in solving Eq. (4), because the matrix on the lhs is singular. A routine to sweep out the "fundamental mode contamination" has been added.⁴ Methods have been implemented to improve convergence of the solution.

To predict the change in some response ratio R , Q^{*} is set equal to dR/dS and Eq. (4) is solved by SIMULATE. Then r^{*} is substituted into the following equation:

$$\frac{\Delta R}{R} \equiv \frac{-\Gamma^{*T}(\Delta M - \lambda \Delta F)S}{R} \quad (6)$$

An important response in LWR analysis is the power peaking in a node. Power peaking for node m can be defined as $h_m \cdot S$, where $h_m = 0$ for all nodes except $m = CIf/vEf$ for node m , and c is a conversion constant. The total power can be defined as $h_{Tot} = CIf/vEf$ for all nodes. Then

$$R \equiv \frac{h_m \cdot S}{h_{Tot} \cdot S}$$

and

$$Q^{*} = \frac{dR}{dS} = R \left[\frac{h_m}{(h_m \cdot S)} - \frac{h_{Tot}}{h_{Tot} \cdot S} \right]$$

Several perturbation calculations were performed for a nine-node sample problem and compared to the exact solutions determined by direct calculations with SIMULATE. In each case, 5% perturbations were made in coupling coefficients. The error in the prediction of k'_{eff} , as shown in Fig. 3.58.1, was less than 0.08% for all cases.

Using the same nine-node configuration, changes in the power peaking for node 1 due to perturbations in the coupling coefficients were calculated by generalized perturbation theory and compared to the exact solution. Good agreement between the GPT results and direct results was achieved, as shown in Fig. 3.58.2.

1	2	3
1.403	0.678	1.403
1.252	0.799	1.252
4	5	6
0.678	0.678	0.678
0.799	0.798	0.799
7	8	9
1.403	0.676	1.403
1.252	0.799	1.252

a node number

b S (source)

c S* (adjoint source)

$\rho = 0.0962$

Matrix Coefficients Perturbed	Amount of Perturbation	k_{eff} (GPT)	k_{eff} (Direct)	% Error in k_{eff} (GPT)
$\mu_{12} = \mu_{21} = \mu_{25}$	5%, 5%, 5%	0.8970	0.8969	0.01
μ_{21}	5%	0.8965	0.8968	-0.03
μ_{12}	5%	0.8969	0.8968	0.03
μ_{25}	5%	0.8993	0.9000	-0.08

Fig. 3.58.1. Sample Problem Configuration and Comparison of GPT Results with Direct k_{eff} Calculations by SIMULATE.

1	2	3
0.0953	-0.0170	-0.0100
2.374	0.381	-0.428
4	5	6
-0.0170	-0.0170	-0.0170
2.381	0.150	0.898
7	8	9
-0.0100	-0.0170	-0.0100
-0.428	-0.898	-1.116

a node number

b Q^*

c P^*

Power Peaking Node 1 (unperturbed) = 1.432

Matrix Coefficient Perturbed	Amount of Perturbation	Power Peaking Node 1 (GPT)	Power Peaking Node 1 (Direct)	% Error in Power Peaking
μ_{35}	5%	1.400	1.394	0.41
μ_{12}	5%	1.464	1.464	0.14
μ_{27}	5%	1.353	1.361	-0.59

Fig. 3.58.2. Sample Problem Configuration and Comparison of GPT Results with Direct Calculations by SIMULATE for Nodal Power Peaking.

In summary, SIMULATE, a 3-D nodal LWR reactor analysis code, has been successfully modified to solve both the k-adjoint and the generalized adjoint equations. First-order perturbation theory has been applied to predict with good accuracy the effects of design parameter changes on various responses such as k_{eff} and the nodal power peaking.

*Research sponsored by ORNL Exploratory Studies Program, Department of Energy.

†University of Tennessee.

1. D. M. Ver Planck, "Manual for the Reactor Analysis Program SIMULATE," EPRI Report for RP710-2 (1978).
2. J. J. Duderstadt and L. J. Hamilton, Nuclear Reactor Analysis, John Wiley & Sons, Inc., NY (1976).
3. W. M. Stacey, Variational Methods in Nuclear Reactor Physics, Academic Press, NY (1974).
4. R. L. Childs, "Generalized Perturbation Theory Using Two-Dimensional, Discrete Ordinates Transport Theory," Doctoral Dissertation, University of Tennessee, Department of Nuclear Engineering (1979); see also paper 3.65.

3.59. LEAST SQUARES METHODOLOGY APPLIED TO LMR-PV DAMAGE DOSIMETRY, EXPERIENCE AND EXPECTATIONS*

J. J. Wagschal[†] B. L. Broadhead[‡] R. E. Maerker

(Abstract of paper in *Nuclear Cross Sections for Technology*, NBS Special Publication 594, p. 956, 1980; also Abstract of paper presented at *ANS Topical Meeting on Advances in Reactor Physics and Shielding*, Sun Valley, Idaho, September 14-17, 1980)

The development of an advanced methodology for Light Water Reactors (LMR) Pressure Vessel (PV) damage dosimetry applications is the subject of an ongoing EPRI-sponsored research project at ORNL. This methodology includes a generalized least squares approach to a combination of data. The data include measured foil activations, evaluated cross sections and calculated fluxes. The uncertainties associated with the data as well as with the calculational methods are an essential component of this methodology. Activation measurements in two NBS benchmark neutron fields (²⁵²Cf ISNF) and in a prototypic reactor field (Oak Ridge Pool Critical Assembly - PCA) are being analyzed using a generalized least squares method. The sensitivity of the results to the representation of the uncertainties (covariances) was carefully checked. Cross element covariances were found to be of utmost importance.

* Research sponsored by Electric Power Research Institute.

[†] On leave from The Hebrew University, Jerusalem, Israel.

[‡] University of Tennessee.

3.60. EXTRAPOLATION OF SURVEILLANCE DOSIMETRY INFORMATION TO PREDICT PRESSURE VESSEL FLUENCES*

J. J. Wagschal[†] R. E. Maerker Y. Yeivin[‡]

(Reprint of *Trans. Am. Nucl. Soc.* 34, 631, 1980)

The traditional method of extrapolating comparisons between measured and calculated saturated foil activities at a surveillance position located near a reactor pressure vessel is to normalize the calculated fluxes to the unfolded measurements and assume the fluxes at the pressure vessel may be scaled by the same factors.¹ This simple method fails to take into account any uncertainty information involved in the measurements or the calculations and consequently offers no estimate of the uncertainty in the derived extrapolated fluence. Knowledge of this uncertainty is almost as important as knowledge of the fluence itself, for it strongly impacts on the decision of when to shut down the reactor because of pressure vessel embrittlement.

A new method for obtaining both the fluence and an estimate of its uncertainty at any position extrapolated from information obtained at a surveillance position has been formulated. The technique involves a least-squares adjustment of the more sensitive nuclear data used, the measured activations, and the biases arising from methods approximations, followed by a corresponding modification of the calculated extrapolated fluence. Adjustment of the calculated fluence at the surveillance position is not necessary. Necessary input for the method includes uncertainties of the more sensitive nuclear data in the calculation, the dosimetry measurements, and the biases in the form of a priori covariance matrices; in addition, the sensitivities of the activations and the extrapolated fluences to the nuclear data used in the calculation and to the biases must be available from previous sensitivity calculations.

Let the vector $a \equiv (a_i)$, $i = 1, 2, \dots, n$, with a corresponding uncertainty matrix $C_a \equiv \text{cov}(a_i, a_j) \equiv \langle (\delta a_i)(\delta a_j) \rangle$, represent a series of dosimetry measurements at the surveillance position, and the vector $\bar{a} \equiv (\bar{a}_i)$ represent a calculation of these same activations. Further,

let the vector $\sigma \equiv (\sigma_i), i = 1, 2, \dots, M$, with a corresponding uncertainty matrix $C_\sigma \equiv \text{cov}(\sigma_i, \sigma_j)$, represent the nuclear data used in the calculation as well as the biases arising from methods approximations. If we define the sensitivities of the calculated activations to the generalized cross sections σ as $S_a \equiv (\partial \bar{a}_i / \partial \sigma_j)$, with S_a being an $n \times M$ matrix, then since $\bar{a}(\sigma + \delta\sigma) = \bar{a}(\sigma) + \delta \bar{a} \approx \bar{a}(\sigma) + S_a \delta\sigma$, the uncertainty matrix corresponding to the calculated activations is

$$C_{\bar{a}} = \langle (\delta \bar{a})(\delta \bar{a})^T \rangle = \langle S_a (\delta\sigma)(\delta\sigma)^T S_a^T \rangle = S_a \langle (\delta\sigma)(\delta\sigma)^T \rangle S_a^T = S_a C_\sigma S_a^T \quad (1)$$

which reflects the propagation of the σ uncertainties through the calculation of $\bar{a}$.

If we denote the deviations of the calculated activations from their respective experimental values by $d \equiv (d_i) = \bar{a} - a$, then the uncertainty matrix of d , denoted by C_d , is

$$C_d = C_{\bar{a}} + C_a = C_{\bar{a}} + S_a C_\sigma S_a^T \quad (2)$$

The least-squares solution² for the "best" combination of measured and calculated dosimetry data at the surveillance position results in the adjusted vector σ^* given by

$$\sigma^* = \sigma - C_\sigma S_a^T C_d^{-1} d \quad (3)$$

with a new covariance of

$$C_{\sigma^*} = C_\sigma - C_\sigma S_a^T C_d^{-1} S_a C_\sigma \quad (4)$$

We note that the nuclear data (i.e., dosimetry cross sections, cross sections involved in the transport calculation, fission spectrum) and the biases resulting from methods approximations (i.e., geometric modeling, source distribution as a function of time and position, $P_1 S_N$ quantization, etc.) are the only data that are to be adjusted at the surveillance position.

If we denote by the vector $\phi \equiv (\phi_i), i = 1, 2, \dots, g$, the calculated fluence at the extrapolated position, and $S_\phi \equiv (\partial \phi_i / \partial \sigma_j)$, the sensitivities of each group fluence to the nuclear data and biases, then

$$\phi^* = \phi + S_\phi (\sigma^* - \sigma) = \phi - S_\phi C_\sigma S_a^T C_d^{-1} d \quad (5)$$

where we have substituted from Eq. (3) the expression for the adjustment in σ resulting from the discrepancy between the calculated and measured dosimetry data at the surveillance position.

The covariance of the a priori calculated fluence is

$$C_\phi = S_\phi C_\sigma S_\phi^T \quad (6)$$

and the covariance matrix of the adjusted fluence becomes

$$C_{\phi^*} = S_\phi C_\sigma S_\phi^T + S_\phi C_\sigma S_a^T C_d^{-1} S_a C_\sigma S_\phi^T - 2 \langle S_\phi C_\sigma S_a^T C_d^{-1} (\delta d)(\delta \phi)^T \rangle \quad (7)$$

Since

$$\langle (\delta d)(\delta \phi)^T \rangle = \langle (\delta \bar{a})(\delta \sigma)^T S_\phi^T \rangle = S_a \langle (\delta \sigma)(\delta \sigma)^T \rangle S_\phi^T = S_a C_\sigma S_\phi^T \quad (8)$$

then

$$C_{\phi} = S_{\phi} C_{\phi} S_{\phi}^{\dagger} - S_{\phi} C_{\phi} S_{\phi}^{\dagger} C_{\phi}^{\dagger} S_{\phi} C_{\phi} S_{\phi}^{\dagger} \quad (9)$$

Equations (5) and (9) represent the adjusted fluence and its uncertainty at the extrapolated position. They involve the inversion of only a "small" $n \times n$ matrix together with some matrix multiplication.

*Research sponsored by the Electric Power Research Institute.

†On leave from The Hebrew University, Jerusalem, Israel.

1. "Standard Recommended Practice for Extrapolating Reactor Vessel Surveillance Dosimetry Results," E560, 1979 Annual ASTM Standards, Part 45, Nuclear Standards, pp. 1104-6.
2. J. J. Wagschal and Y. Yeivin, "The Significance of Lagrange Multipliers in Cross-Section Adjustment," *Trans. Am. Nucl. Soc.* 34, 776 (1980).

3.61. THE VOID COEFFICIENT IN A UNIT CELL FOR U-Pu WATER BREEDER REACTORS*

Y. Ronen† M. Cojocaru† A. Radkowsky†

(Reprint of *Trans. Am. Nucl. Soc.* 34, 784, 1980)

The possibility of breeding with the Pu-U fuel cycle in light or heavy water has been established.^{1,2} For such lattices the void coefficient in a unit cell was calculated. It was found³ that for the light-water lattices the void coefficient is negative, whereas for heavy-water lattices the void coefficient is positive. However, it was shown that by introducing a relatively small amount of light water to the heavy water, a negative void coefficient is obtained while retaining many of the heavy-water lattice properties.

In this paper, the results of an investigation of the value of the void coefficient during burnup in a unit cell of the heavy-/light-water lattices was investigated and the results are presented.

The lattices under study had a moderator-to-fuel volume ratio of 0.4. The moderator was a combination of heavy and light water (80% D₂O + 20% H₂O). The fuel was a combination of natural uranium and 38,900 MWd/MT PWR discharged plutonium.⁴ The fuel composition was ²³⁹Pu -4.92%, ²⁴⁰Pu -1.97%, ²⁴¹Pu -1.58%, ²⁴²Pu -0.44%, ²³⁵U -0.64%, and ²³⁸U -90.45%. The fuel diameter was 0.823 cm with a Zircaloy cladding of 0.06 cm. The fuel, cladding, and moderator temperatures were those of a hot reactor.

The lattices were calculated with the WIMS-D code and data.^{5,6} Values representative of a 900-MW(e) PWR reactor were used for the radial and axial bucklings; i.e., $B^2 = 2.62 \times 10^{-4} \text{ cm}^{-2}$ and $B_z^2 = 0.784 \times 10^{-4} \text{ cm}^{-2}$, respectively. The transport calculations were done in four energy groups: 10-0.821 MeV, 821-5.53 keV, 5530-0.625 eV, and 0.625-0 eV. The cross sections in the four energy groups were recalculated for each case using a 69-energy-group library with a 69-energy-group calculated neutron spectrum. The burnup calculations were done with a constant power rating of 19 MW/MT.

The value of the void coefficient (vc) during burnup is given in Fig. 3.61.1. From these results it is seen that the vc becomes positive during burnup. Analysis of the behavior of the vc during burnup reveals that the vc value is affected by two major parameters: (a) the amount of ²⁴⁰Pu, and (b) the ratio of ²⁴¹Pu/²³⁹Pu. Other parameters, such as fission products, have very little effect.

The effect of the $^{241}\text{Pu}/^{239}\text{Pu}$ ratio is given in Fig. 3.61.2, which shows that the lower the ratio of $^{241}\text{Pu}/^{239}\text{Pu}$, the more positive is the vc. The reason for this behavior is explained by the behavior of $\eta(E)$ of these isotopes. For ^{239}Pu , $\eta(E)$ is essentially constant up to 60 keV. Thus, when voiding the reactor, the neutron spectrum is hardened and more neutrons above 3 keV are absorbed by ^{239}Pu which, in turn, increases k_{eff} . Thus, the lower the ratio $^{241}\text{Pu}/^{239}\text{Pu}$, the stronger the ^{239}Pu influence becomes.

The effect of ^{240}Pu is given in Fig. 3.61.3, where N_0 is the amount of ^{240}Pu at the beginning-of-life (1.97%). From this figure, it is apparent that the lower the concentration of ^{240}Pu , the more negative the vc. When the reactor is voided, the neutron spectrum becomes harder, and therefore fewer neutrons are found in the thermal and the resolved resonance groups. Thus, hardening the neutron spectrum tends to decrease the number of neutrons available for absorption in ^{240}Pu due to the thermal cross section of ^{240}Pu and due to the big resonance near 1 eV. In addition, hardening the neutron spectrum tends to increase the number of fast fissions in ^{240}Pu . As a result, hardening of the neutron spectrum in the presence of ^{240}Pu tends to increase the k_{eff} and thus the value of vc.

Fig. 3.61.1. The Void Coefficient $\Delta k/(1 - \rho/c_0)$ During Burnup.

Fig. 3.61.2. The Effect of the $^{241}\text{Pu}/^{239}\text{Pu}$ Ratio on the Void Coefficient $\Delta k_{\infty}/(1 - \rho/\rho_0)$.

fig. 3.61.3. The Effect of ²⁴⁰Pu on the Void Coefficient $\Delta k/(1 - \rho/\rho_0)$.

In the lattices that have been investigated, the ratio of ²⁴¹Pu/²³⁹Pu decreases during burnup, whereas the amount of ²⁴⁰Pu increases. Thus, these effects tend to increase k_{eff} when hardening the neutron spectrum during voidage and thus increase the positive value of the vc as illustrated in Fig. 3.61.1.

*Research sponsored by DOE Office of Energy Information.

†On leave from Ben Gurion University of the Negev, Beer-Sheva, Israel.

1. A. Radkowsky et al., "Epithermal to Intermediate Spectrum Pressurized Heavy Water Breeder Reactor," (1975) U.S. Patent 3859165.
2. M. C. Edlund, Trans. Am. Nucl. Soc. 24, 508 (1976).
3. Y. Ronen et al., Ann. Nucl. Energy 5, 211 (1978).
4. R. C. Smith et al., Nucl. Tech. 18, 97 (1973).
5. J. R. Askew, F. J. Fayers, and P. B. Kemshell, J. Br. Nucl. Energy Soc. 43, 282 (1966).
6. C. J. Taubman, "The WIMS-69 Group Library Tape 166259," AFEW-M1324, U.K. Atomic Energy Establishment, Winfrith (1975).

3.62. A NONLINEAR SENSITIVITY AND UNCERTAINTY ANALYSIS IN SUPPORT OF THE BLOWDOWN HEAT TRANSFER PROGRAM*

Y. Ronen† M. A. Bjerke† D. G. Cacuci J. Barhen

[Abstract of ORNL/NUREG/TM-412 (NUREG/CR-1723) November, 1980]

A nonlinear uncertainty analysis methodology based on the use of first and second order sensitivity coefficients is presented. As a practical demonstration, an uncertainty analysis of several responses of interest is performed for Test 177, which is part of a

series of tests conducted at the Thermal-Hydraulic Test Facility (THTF) of the ORNL Engineering Technology Division Pressurized Water Reactor-Blowdown Heat Transfer (PWR-BDHT) program. These space- and time-dependent responses are: mass flow rate, temperature, pressure, density, enthalpy, and water quality - in several volumetric regions of the experimental facility.

The analysis shows that, over parts of the transient, the responses behave as linear functions of the input parameters; in these cases, their standard deviations are of the same order of magnitude as those of the input parameters. Otherwise, the responses exhibit nonlinearities and their standard deviations are considerably larger. The analysis also shows that the degree of nonlinearity of the responses is highly dependent on their volumetric locations.

* Research sponsored by Nuclear Regulatory Commission, Office of Nuclear Regulatory Research.

† On leave from Ben Gurion University of the Negev, Beer-Sheva, Israel.

‡ UCC-ND Computer Sciences Division.

3.63. QUARTERLY PROGRESS REPORT ON BLOWDOWN HEAT TRANSFER SEPARATE-EFFECTS PROGRAM FOR OCTOBER-DECEMBER 1979*

W. G. Craddick [†]	D. K. Felde [†]	G. S. Mailen [†]
R. E. Bohanan [†]	R. M. Flanders [†]	L. J. Ott [†]
D. G. Cacuci	R. C. Hagar [†]	M. D. White [†]
D. H. Cook [†]	C. R. Hyman [†]	

(Abstract of ORNL/NUREG/TM-231 (NUREG/CR-1306) June 1980)

The Blowdown Heat Transfer Program has been asked by the Nuclear Regulatory Commission to conduct a series of bundle uncover and recovery tests with the Thermal-Hydraulic Test Facility (THTF) to gain data on the thermal-hydraulic phenomena that might occur in a reactor core during a small-break loss-of-coolant accident. A single fuel rod simulator was tested in the Forced Convection Test Facility under conditions more severe than those anticipated for the uncover and recovery tests to assess rod survivability. Results were positive, and two of the series of uncover and recovery tests were conducted in the THTF. Development and assessment of analytical tools needed for planning and analyzing bundle 3 testing are continuing. An isothermal blowdown in the THTR was conducted. Spurious trips of the bundle safety circuitry have prevented completion of rod characterization testing. Design and procurement for the in-bundle densitometer are continuing.

* Research sponsored by Nuclear Regulatory Commission, Office of Nuclear Regulatory Research.

† Engineering Technology Division.

3.64. SENSITIVITY THEORY APPLIED TO A TRANSIENT THERMAL-HYDRAULICS PROBLEM*

C. F. Weber

(Abstract of Thesis for the Master of Science Degree,
The University of Tennessee, June, 1979)

A new method for sensitivity analysis of transient nonlinear problems is developed and applied to a reactor thermal-hydraulics problem. The method resembles the differential sensitivity methods currently used in the linear problems of reactor physics, but it is applicable to nonlinear systems as well. The equations governing heat transfer and fluid flow in a fuel pin and surrounding coolant are given and used to derive a second

set of equations (commonly known as the "adjoint equations") used in the sensitivity analysis. Both systems contain one second-order parabolic and one first-order hyperbolic partial differential equation. Difference equations are derived to approximate both systems and the convergence properties of these discrete systems are evaluated, yielding a useful analysis of the numerical solution. The solution functions are used to derive sensitivity coefficients for any desired integral response. These sensitivity coefficients are used in a first-order perturbation theory to predict changes in a response resulting from changes in parameter values. The results of a test problem are shown, verifying that this procedure is indeed useful for a wide variety of sensitivity calculations.

*Research sponsored by Nuclear Regulatory Commission, Office of Nuclear Regulatory Research.

3.65. GENERALIZED PERTURBATION THEORY USING TWO-DIMENSIONAL, DISCRETE ORDINATES TRANSPORT THEORY*

R. L. Childs†

(Abstract of ORNL/CSD/TM-127, June, 1980)

Perturbation theory for changes in linear and bilinear functionals of the forward and adjoint fluxes in a critical reactor has been implemented using two-dimensional discrete ordinates transport theory. The computer program, DOT IV, was modified to calculate the generalized functions Γ and Γ^* . Demonstration calculations were performed for changes in a reaction-rate ratio and a reactivity worth caused by system perturbations. The perturbation theory predictions agreed with direct calculations to within about 2%. A method has been developed for calculating higher λ eigenvalues and eigenfunctions using techniques similar to those developed for generalized functions. Demonstration calculations have been performed to obtain these eigenfunctions.

*Research sponsored by Nuclear Regulatory Commission, Office of Nuclear Regulatory Research.

†UCC-ND Computer Sciences Division.

3.66. DOS PERTURBATION MODULES DGRAD/VIP/TPERT*

E. T. Tomlinson† R. L. Childs† R. A. Lillie

(Abstract of ORNL/CSD/TM-116, May 1980)

The perturbation modules DGRAD, VIP, and TPert have been upgraded to run under the DOS DRIVER. A brief discussion of each module, its function, and its input requirements is presented in this report. One transport theory and one diffusion theory sample problem are also presented.

*Research sponsored by Nuclear Regulatory Commission, Office of Nuclear Regulatory Research.

†UCC-ND Computer Sciences Division.

4. ENGINEERING PHYSICS DIVISION INTEGRAL EXPERIMENTS AND THEIR ANALYSES

4.0 INTRODUCTION

Integral experiments are performed as part of the Engineering Physics Division's on-going research in the development and application of radiation shielding methods. Two basic types of experiments are performed. Design-specific experiments are highly prototypic of specific aspects of existing shield designs and investigate complex geometric configurations which usually involve radiation transport in three dimensions. Data verification experiments frequently involve deep-penetration problems, or multiple-layered shield configurations with varying material regions, and provide information to determine the adequacy of basic and processed cross-section data.

Integral experiments performed at the Oak Ridge Electron Linear Accelerator (ORELA) under the Division's Magnetic Fusion Energy program are designed to provide data against which ORNL and all other organizations involved in shielding calculations for fusion devices can test their calculational methods and interaction data (see also Introduction to Section 6).

The Tower Shielding Facility (TSF) continues to be the primary source of integral data for fission reactor shielding design. The TSF is unique in that it provides a high neutron flux, which allows deep-penetration measurements, and a spacious environment, which allows room for assembling large, prototypic geometric configurations. Reliable, proven detector capabilities include energy spectra and integral bonner-ball measurements for neutrons.

The experiments performed at the TSF during the last few years have been sponsored by the Gas Cooled Fast Reactor (GCFR) program. Recent experiments have examined data accuracy with measurements on laminated shields containing graphite, stainless steel, and boronated graphite; a prototypic design for the B₄C exit shield assemblies; and methods applicability for shield heterogeneities via measurements of neutron streaming through slits in graphite and steel-lined graphite assemblies. While these experiments were intended to produce relevant information for the GCFR program, they are also of interest to the Liquid Metal Fast Breeder Program (LMFBR), which is currently contemplating an alternate shielding materials qualification program.

During this report period final documentation was also prepared for the remaining LMFBR shielding experiments, including an examination of streaming through annular slits and measurement of secondary gamma-ray production in reinforced concrete.

INTEGRAL EXPERIMENTS SUPPORTING FUSION REACTOR DESIGN

4.1. CALCULATION OF NEUTRON AND GAMMA RAY ENERGY SPECTRA FOR FUSION REACTOR SHIELD DESIGN: COMPARISON WITH EXPERIMENT*

R. T. Santoro R. G. Alsmiller, Jr. J. M. Barnes[†] G. T. Chapman

(Abstract of ORNL/TM-7360, August, 1980; also submitted to Nucl. Sci. Eng.)

Integral experiments that measure the transport of ~14 MeV D-T neutrons through laminated slabs of proposed fusion reactor shield materials have been carried out at ORNL. Measured and calculated neutron and gamma ray energy spectra are compared as a function of the thickness and composition of stainless steel type 304, borated polyethylene, and Hevimet (a tungsten alloy), and as a function of detector position behind these materials. The measured data were obtained with a NE-213 liquid scintillator using pulse-shape discrimination methods to resolve neutron and gamma ray pulse height data and spectral unfolding methods to convert these data to energy spectra. The calculated data were obtained using two-dimensional discrete ordinates radiation transport methods in a complex calculational network that takes into account the energy-angle dependence of the D-T neutrons and the nonphysical anomalies of the S_n method. The transport calculations incorporate ENDF/B-IV cross-section data from the VITAMIN C data library. The measured and calculated neutron energy spectra are in good agreement behind slab configurations of stainless steel type 304 and borated polyethylene (~10% for all neutron energies above 850 keV). When 5 cm of Hevimet is added to a 45-cm-thick SS-304 plus BP slab assembly, the agreement is less favorable. The agreement among the measured and calculated gamma ray spectra for energies above 750 keV ranges from ~25% to a factor of ~5, depending on the slab composition.

*Research sponsored by DOE Office of Fusion Energy.

[†]UCC-ND Computer Sciences Division.

4.2. INTEGRAL EXPERIMENTS FOR FUSION REACTOR DESIGN: ANALYSIS*

R. T. Santoro R. G. Alsmiller, Jr. J. M. Barnes[†] E. M. Oblov

(Abstract of paper in *Nuclear Cross Sections for Technology*, NBS Special Publication 501, p. 526, 1980)

Integral experiments that measure the energy spectra of neutrons and gamma rays due to the transport of ~14-MeV D-T neutrons through laminated SS-304 and borated polyethylene shield assemblies have been performed. Measured and calculated energy spectra and integrated flux distributions are compared for a typical shield assembly as a function of detector location.

*Research sponsored by the U.S. DOE Division of Development and Technology, Office of Fusion Energy.

[†]UCC-ND Computer Sciences Division.

4.3. INTEGRAL EXPERIMENTS FOR FUSION REACTOR DESIGN: EXPERIMENTATION*

G. T. Chapman G. L. Morgan†

(Abstract of paper in *Nuclear Cross Sections for Technology*, NBS Special Publication 594, p. 591, 1980)

Integral experiments that measure the energy spectra of neutrons and gamma rays due to the transport of ~ 14 -MeV $T(d,n)^4\text{He}$ neutrons through thick steel and borated polyethylene shield configurations have been performed at the Oak Ridge National Laboratory. Descriptions of the facility and experimental techniques are given along with curves showing data representative of the results.

* Research sponsored by the U.S. DOE Division of Development and Technology, Office of Fusion Energy.

† Now at Los Alamos Scientific Laboratory.

4.4. ANALYSIS OF ORNL FUSION REACTOR SHIELD INTEGRAL EXPERIMENTS*

R. T. Santoro R. G. Alsmiller, Jr. J. M. Barnes† G. T. Chapman
G. L. Morgan E. M. Oblow R. W. Peelle

(Reprint of *Trans. Am. Nucl. Soc.* 33, 665, 1979)

The nuclear performance of the blanket and shield in a fusion reactor will have a substantial impact on the overall operation and capital cost of the reactor.¹ It is necessary, therefore, to have experimental verification of the nuclear data and radiation transport methods that will be used to carry out the nuclear design calculations for these assemblies. Integral experiments are being performed at the Oak Ridge National Laboratory to provide the experimental data needed for this verification. The verification will be made by extensive comparisons between calculated results and these experimental data. Measurements of the transport of 14-MeV neutrons through laminated shields containing materials that are anticipated for use in fusion applications and the effect of introducing penetrations in the shields will be made. This paper summarizes the results of measurements and calculations to determine neutron and photon spectra behind laminated shields of varying composition and thickness.²

The experiments are carried out using 14-MeV neutrons having a source strength of $\sim 10^4$ n/s produced in the interactions of 200-keV deuterons with tritium saturated in a titanium target. The target is enclosed in an iron can which has the purpose of tailoring the neutron distribution to correspond to that incident on the first wall of a fusion reactor. The target, iron can, and the shield assembly are supported in a concrete superstructure. Shields of various thicknesses are constructed by arranging 5.08-cm-thick $\times$ 152-cm-square stainless-steel Type 304 (SS-304), borated polyethylene (BP), and Hevimet (tungsten alloy) slabs in selected sequences. Neutron and gamma-ray spectra are measured at various positions relative to the deuteron-target axis and as a function of shield thickness using an NE-213 liquid scintillator. Neutron and gamma-ray pulse-height spectra are simultaneously obtained using pulse-shape-discrimination methods and unfolding techniques are used to resolve the energy spectra from the pulse-height data.

The calculated neutron and gamma-ray energy spectra are obtained using two-dimensional (2-D) radiation transport methods. The experimental configuration is represented in r - z geometry with cylindrical symmetry about the axis of the deuteron beam using 92 axial and 76 radial mesh intervals to describe the geometry. The neutron source used in the calculations takes into account the angle-energy relationship of the neutrons emitted from the D-T reaction and takes into account deuteron slowing down in the target. Separate calculations are performed to determine the first collision and uncollided flux distributions in the geometry meshing using black absorbers about the neutron source to define the angular interval into which neutrons in a given energy interval are emitted. These data are

then combined to form a single source term for input into the discrete ordinates code DOT³ which completes the radiation transport. The transport calculations are carried out using an S_8 angular quadrature and a P_3 Legendre expansion of the transport cross sections, and a 53-neutron-21-gamma-ray multigroup cross section obtained by collapsing the 171-neutron-36-gamma-ray Vitamin C (Ref. 4) data set using the ANISN⁵ code.

Neutron and gamma-ray spectra have been measured and calculated for shield configurations consisting of

1. six SS-304 slabs
2. configuration (1) plus one SS-304 and one BP slab
3. configuration (2) plus one SS-304 and one BP slab
4. configuration (3) plus one SS-304 slab
5. configuration (4) plus one Hevinet (tungsten alloy) slab.

These configurations represent laminated shields having thicknesses ranging from 30.48 to 60.96 cm.

The neutron energy spectra measured and calculated behind the 30.48-cm-thick SS-304 shield configuration are compared in Fig. 4.4.1. The two solid lines indicate the statistical uncertainty band in the unfolded neutron spectrum and the dots are the calculated results. The calculated data were obtained by smoothing the flux per unit energy in each multigroup energy interval with an energy-dependent Gaussian distribution that characterizes the neutron response of the detector. The calculated and experimental data are in reasonable agreement.

Fig. 4.4.1. Comparison of the Measured and Calculated Neutron Spectra Behind 30.48 cm of SS-304. The detector is positioned 100 cm off the deuteron-target axis.

Comparisons of the neutron and gamma-ray energy spectra and the integrals of these for all of the shield configurations will be presented and discussed. Also, a brief overview of the continuing experimental program will be given.

*Research sponsored by DOE Office of Fusion Energy, Division of Development and Technology.

†UCC-ND Computer Sciences Division.

1. M. A. Abdou, "Radiation Exposure and Maintainability in Fusion Reactors," Trans. Am. Nucl. Soc., 32, 70 (1979).
2. Y. Seki, R. T. Santoro, E. H. Oblow, and J. L. Lucius, "Macroscopic Cross Section Sensitivity for TNS Integral Experiments," Trans. Am. Nucl. Soc., 28, 662 (1978).
3. W. A. Rhoades and F. R. Mynatt, "The DOT-III Two-Dimensional Discrete Ordinates Code," ORNL/TM-4280, Oak Ridge National Laboratory, (September 1973).
4. ORNL/RSIC-37, Radiation Shielding Information Center, Oak Ridge National Laboratory, (1975) available as DLC/41-Vitamin C.
5. W. W. Engle, Jr., "A Users Manual for ANISN, A One-Dimensional Discrete Ordinates Code with Anisotropic Scattering," K-1693, Oak Ridge Gaseous Diffusion Plant (1967).

4.5. FUSION REACTOR SHIELDING BENCHMARK*

G. T. Chapman	G. L. Morgan [†]	J. W. McConnell
R. T. Santoro	R. G. Alsmiller, Jr.	J. M. Barnes [‡]

(Abstract of paper to be published as an American Nuclear Society Benchmark Problem.)

The experimental geometry used in the fusion reactor shielding attenuation experiments at ORNL and the experimental data obtained are given in sufficient detail that they may be used by investigators to test their calculational methods. A detailed description of the calculational methods used at ORNL and comparisons between the calculated results and all of the experimental data are also included.

*Research sponsored by DOE Office of Fusion Energy.

†Now at Los Alamos Scientific Laboratory.

‡UCC-ND Computer Sciences Division.

4.6. ORNL FUSION REACTOR SHIELDING INTEGRAL EXPERIMENTS*

R. T. Santoro	R. G. Alsmiller, Jr.	J. M. Barnes [†]	G. T. Chapman
---------------	----------------------	---------------------------	---------------

(Summary of invited paper presented at the Fourth ANS Topical Meeting, Technology of Controlled Nuclear Fusion, King of Prussia, Pennsylvania, October 14-17, 1980)

Integral experiments that measure the neutron and gamma-ray energy spectra resulting from the attenuation of ~ 14 MeV $T(D,n)^4He$ reaction neutrons in laminated slabs of stainless steel type 304, borated polyethylene, and a tungsten alloy (Hevimet) and from neutrons streaming through a 30-cm-diameter iron duct ($L/D = 3$) imbedded in a concrete shield have been performed at the Oak Ridge National Laboratory. The facility, the NE-213 liquid scintillator detector system, and the experimental techniques used to obtain the measured data are described. The two-dimensional discrete ordinates radiation transport codes, calculational models, and nuclear data used in the analysis of the experiments are reviewed. The measured and calculated neutron energy spectra (>850 keV) obtained for the attenuation experiments are in excellent agreement ($\sim 10\%$) for shield compositions and thicknesses up to 412 g/cm² thick. The calculated gamma-ray spectra (>750 keV) agree with the measured data to within 15% for the slabs containing stainless steel and borated polyethylene and within a factor of 5 when Hevimet is included in the shield composition.

The calculated neutron spectra obtained for the streaming experiments are in good agreement (~10-15%) with the measured data for the on-axis detector position. For the off-axis detector locations, the calculations overestimate the measurements by as much as a factor of 5 depending on detector location. Current evidence suggests that the angular distributions for elastic and inelastic neutron scattering are not properly represented in the discrete ordinates analysis and more accurate methods are required. The calculated and measured gamma-ray spectra agree within ~30%.

* Research sponsored by DOE Office of Fusion Energy.

† UCC-ND Computer Sciences Division.

4.7. COMPARISON OF CALCULATED AND EXPERIMENTAL NEUTRON ATTENUATION AND STREAMING DATA FOR FUSION REACTOR DESIGN*

R. T. Santoro R. G. Alsmiller, Jr. J. M. Barnes[†] G. T. Chapman

(Abstract of paper presented at Eleventh Symposium on Fusion Technology, Oxford, England, September 18-19, 1980)

Integral experiments that measure the neutron and gamma-ray energy spectra resulting from the attenuation of ~14-MeV $T(D,n)^4He$ reaction neutrons in laminated slabs of stainless steel type 304, borated polyethylene, and a tungsten alloy (Hevimet) and from neutrons streaming through a 30-cm-diameter iron duct ($L/D = 3$) imbedded in a concrete shield have been performed at the Oak Ridge National Laboratory. The facility, NE-213 liquid scintillator detector system, and experimental techniques used to obtain the measured data are described. The two-dimensional discrete ordinates radiation transport codes, calculational models, and nuclear data used in the analysis of the experiments are reviewed. The measured and calculated neutron energy spectra (>850 keV) obtained for the attenuation experiments are in excellent agreement (~10%) for shield compositions and thicknesses up to 412 g/cm² thick. The calculated gamma-ray spectra (>750 keV) agree with the measured data to within 15% for the slabs containing stainless steel and borated polyethylene and within a factor of 5 when Hevimet is included in the shield composition. The calculated neutron spectra obtained for the streaming experiments are in good agreement (~10-15%) with the measured data for the on-axis detector position. For the off-axis detector locations, the calculations overestimate the measurements by as much as factor of 5 depending on detector location. Current evidence suggests that the angular distributions for elastic and inelastic neutron scattering are not properly represented in the discrete ordinates analysis and more accurate methods are required. The calculated and measured gamma-ray spectra agree within ~30%.

* Research sponsored by DOE Office of Fusion Energy.

† UCC-ND Computer Sciences Division.

4.8. THE USE OF A SMALL ACCELERATOR AS A SOURCE OF 14-MEV NEUTRONS FOR SHIELDING STUDIES*

G. T. Chapman G. L. Morgan[†] J. W. McConnell

(Summary of paper presented at Sixth Conference on the Application of Accelerators in Research and Industry, North Texas State University, Denton, Texas, November 3-6, 1980)

It is important in calculating complex shields such as those proposed for the fusion reactors to ascertain that the neutron cross-section data sets used in the calculations are as accurate as possible and that the calculational methods used to transport the neutrons are as reliable as practical. To assure that both these criteria are met, a project at the Oak Ridge National Laboratory (ORNL) is being conducted in which a small

accelerator is used to provide 14-MeV neutrons via the $T(d,n)^4He$ reaction and an NE-213 detector is used to measure the neutron and gamma-ray pulse-height spectra of the radiations transported through and/or created in very thick laminated shields of stainless steel (type 304) and borated polyethylene. To produce the neutron flux required, the targets are made by depositing about 4 mg/cm² of TiT onto a 1.27-cm circular area of a 0.254-cm thick copper disk. The NE-213 detector is operated in standard, state-of-the-art electronic circuits. A surface-barrier alpha counter and a small NE-213 detector are located permanently at a distance of about 150 cm from the target to monitor the reaction rate in the target. The pulse-height data are unfolded to produce energy spectra by using the computer program FERD. These results are then compared almost immediately with spectra obtained using two-dimensional radiation transport methods incorporating 53-neutron, 21-gamma-ray energy-group cross section data derived from the VITAMIN-C data set (ENDF/B). Laminated stainless-steel and borated polyethylene shields having thicknesses up to 412 g/cm² have been measured.

* Research sponsored by DOE Office of Fusion Energy.

† Now at Los Alamos Scientific Laboratory.

INTEGRAL EXPERIMENTS SUPPORTING GAS COOLED FAST BREEDER REACTOR DESIGN

4.9. ANALYSIS OF THE TSF GCFR SINGLE-CELL NEUTRON STREAMING EXPERIMENT*

C. O. Slater J. R. Knight†

(Abstract of ORNL/GCFR-80/16, July, 1980)

This report describes the preanalysis and postanalysis of an experiment identified as the single-cell pin streaming experiment for the Gas Cooled Fast Breeder Reactor. The purpose of the experiment, performed at the Tower Shielding Facility, was to provide a data base for testing an angular quadrature set developed for use in discrete ordinates analyses of neutron streaming through the helium coolant passages of the GCFR core. The experimental configuration was similar to a single cell of the GCFR core. It consisted of a pipe centered in a water-filled tank, the pipe being successively filled with air, an iron pin surrounded by air, or an aluminum-clad depleted UO₂ pin surrounded by air. The pins occupied about one-half the volume of the pipe. The TSF reactor provided the source neutrons, which for the measurements were both uncollimated and tightly collimated down to an area smaller than the pin cross-sectional area. The preanalysis, performed with the discrete ordinates code DOT and checked with the Monte Carlo code MORSE, predicted that the cases with the collimated source were too close to the background case (cell and collimators filled with water) to give reliable results and also that the iron pin and UO₂ pin would give similar results. The predictions were confirmed by the measurements and thus the postanalysis, performed with DOT, was limited to the empty cell and the iron pin case. The results showed that for detectors on the cell axis, predictions of neutron streaming through the empty cell were too low by 4 to 40% and those for the iron pin case varied from a 13% underprediction to a 61% overprediction. While good agreement between the calculations and measurements was obtained in several instances, it did not confirm the adequacy of the quadrature since the uncollided response was a large part of the total response and its calculation was independent of the quadrature set. On the other hand, the poor results obtained for the collided response did not clearly indicate an inadequate quadrature since the large detector size compared to the pipe diameter contributed greatly to the uncertainty in the analysis.

* Research sponsored by DOE Office of Advanced Nuclear Systems and Projects.

† UCC-ND Computer Sciences Division.

4.10. ANALYSIS OF THE ORNL/TSF GCFR GRID-PLATE SHIELD DESIGN CONFIRMATION EXPERIMENT*

C. O. Slater S. N. Cramer D. T. Ingersoll

(Reprint of Trans. Am. Nucl. Soc. 32, 641, 1973)

The shielding program for the gas-cooled fast breeder reactor¹ (GCFR) has included an integral experiment² performed at the ORNL Tower Shielding Facility to provide data for testing the adequacy of the GCFR shield design methods, in particular as they are being applied to the design of a shield for the grid plate that will support the GCFR core. The primary objective of the experiment was to provide data on the effectiveness of a prototype shield in reducing the fast-neutron flux to the grid plate, and its secondary objective was to determine the extent to which neutrons are collimated through the grid plate. This paper describes an analysis of the experiment and discusses the adequacy of the analysis technique for application to GCFR shield design problems.

An extensive preanalysis program³ determined the features that had to be included in the experiment to make it prototypic of the GCFR design. The resulting experimental configuration consisted of three sections and represented the GCFR from the core/blanket region through the grid plate region (see Fig. 4.10.1). The first section, protected from the direct radiation of the TSF reactor by a concrete shadow shield, contained seven hexagonally shaped fuel subassemblies simulating the GCFR core. The subassemblies were spaced 0.318, 0.635, or 1.27 cm apart, and each contained 2% ²³⁵U-enriched aluminum-clad fuel pins, 127 cm long x 1.27 cm in diameter. For some measurements, 91 fuel pins per subassembly were used; while for others, 127 pins per subassembly were used. In one case a control rod channel was mocked up by removing pins from a central subassembly initially containing 91 fuel pins.

Fig. 4.10.1. Sketch of the Near-Prototypic Configuration of the ORNL/TSF GCFR Grid-Plate Shield Design Confirmation Experiment.

The second section of the configuration consisted of 45-cm-long hexagonally shaped grid-plate shield subassemblies that were aligned with the fuel subassemblies. Following GCFR design dimensions, each shield subassembly was fabricated with inner and outer iron liners, and the void between the liners was filled with B₄C. The final section of the configuration consisted of the grid-plate mockup, a thick (63.5-cm) iron plate penetrated by seven 16.5-cm-diam. holes. (The grid plate was used only with the subassemblies containing 127 fuel pins and spaced 1.27 cm apart.) Neutron measurements were made beyond each section of the configuration.

Analysis of the experiment was performed with the discrete ordinates transport code DOT-IV⁴ and the Monte Carlo code MORSE,⁵ together with numerous auxiliary codes. In general, calculations with DOT-IV agree reasonably well with measurements made close behind or not too far from the configurations. Table 4.10.1 shows that at 138.1 cm behind the fuel section the DOT-calculated results are in good agreement with the measurements, while at 34.29 cm behind the grid plate they overpredict by up to 54%. At distances of 305 cm beyond the grid plate, the overprediction is about a factor of 2. The MORSE results are in somewhat better agreement with the measurements, particularly at the large distances.

Table 4.10.1. Comparison of DOT-Calculated Detector Responses with Measured Values Behind the GCFR Grid Plate Shield Experiment Configurations

Response type	Location	
	138.1 cm behind fuel subassemblies ²	34.29 cm behind grid plate
Bonner ball (counts/min-M)		
3-in. ball		
Calculated (C)	356	59.0
Measured (E)	280	42.6
C/E	1.17	1.38
6-in. ball		
Calculated (C)	1470	-
Measured (E)	1270	-
C/E	1.16	-
10-in. ball		
Calculated (C)	647	-
Measured (E)	600	-
C/E	1.08	-
Flux (neutrons/cm ² -min-M) ²		
E > 0.9 MeV		
Calculated (C)	233	41.2
Measured (E)	219	26.6
C/E	1.06	1.54
E > 0.12 MeV		
Calculated (C)	656	146
Measured (E)	656	99.2
C/E	1.00	1.48

²Subassemblies spaced at 1.27 cm and each containing 127 fuel pins.

²NE-213 and hydrogen counter spectrometer measurements.

Of particular concern in the GCFR design is the maximum fast-neutron exposure to the grid plate. To investigate this, the experiment included Hornyak button measurements along a radial traverse as close behind the grid-plate shield as possible. The results indicated a peak-to-minimum fast-neutron exposure ratio of 1.4 to 1.5. Corresponding calculations yielded a ratio of 1.2 to 1.3. Because it was discovered that the Hornyak button detector response function used in the calculations was improperly normalized, a direct comparison of the calculated and measured values was not possible. However, the calculated count rate for a 5-in. Bonner ball 30.5 cm behind the shield on the centerline was 15% higher than the measured count rate and presumably approximately the same differential would apply to the Hornyak button results. Thus, to obtain the calculated-to-measured grid-plate peak exposure ratio, the calculated Hornyak button results were assumed to be 15% higher than the measured results at the radial center of the traverse. This resulted in a calculated-to-measured ratio of the peak values of 0.98, which is well within the uncertainty of the experiment ($\pm 10\%$).

In summary, it can be stated that for regions through the grid-plate subassemblies the calculated and measured values are in good agreement—to within 20%. For large distances beyond the grid plate, however, the calculated values are as much as a factor of 2 higher than the measured results. This indicates that for the upper axial regions of the GCFR (above the grid plate) the analysis methods will yield conservative values.

* Research sponsored by DOE Office of Advanced Nuclear Systems and Projects.

1. General Atomic Co. Project Staff, "300-MW(e) Gas-Cooled Fast Breeder Reactor Demonstration Plant," GA-A13045, General Atomic Company (1974).
2. F. J. Muckenthaler, J. L. Hull, and J. J. Manning, "The GCFR Grid-Plate Shield Design Experiment," Trans. Am. Nucl. Soc. 28, 631 (1978); see also ORNL/TM-6580 (Jan. 1979).
3. D. T. Ingersoll, C. O. Slater, and M. L. Williams, "Design of a Prototypic GCFR Grid-Plate Shield Confirmation Experiment," Trans. Am. Nucl. Soc. 28, 630 (1978).
4. W. A. Rhoades, D. B. Simpson, R. L. Childs, and W. W. Engle, Jr., "The DOT IV Two-Dimensional, Discrete-Ordinates Transport Code with Space-Dependent Mesh and Quadrature," ORNL-5283 (to be published).
5. M. B. Emmett, "The MORSE Monte Carlo Radiation Transport Code System," ORNL-4972 (Feb. 1975).

4.11. MEASUREMENT AND CALCULATION OF THE EFFECTIVENESS OF THE GCFR GRID PLATE SHIELD*

C. O. Slater S. N. Cramer D. T. Ingersoll M. L. Williams

(Abstract of paper to be published in Nuclear Technology)

Results are presented for the analysis of the ORNL/TSF GCFR Grid-Plate Shield Design Confirmation Experiment. The experiment was designed with three major objectives: (1) to verify our ability to calculate the energy and angular distribution of neutrons streaming in fuel pin arrays, (2) to verify our ability to calculate the maximum fast-neutron exposure to the grid plate, and (3) to verify our ability to calculate the energy and angular distribution of neutrons leaving the top of the grid plate. The overall objective was to verify the grid-plate shield design (i.e., the design would perform as well or better than indicated by calculation). The comparisons between calculated and measured responses indicated that objectives (1) and (2) were achieved. Objective (3) was achieved in part in that the energy distribution seemed to be calculated well. On the other hand, depending on the quadrature, there was either conservative overprediction or gross underprediction of the detector responses. For the design calculation, it was estimated that the nonconservative case might mean up to a factor of 4 underprediction of the fluxes in the GCFR upper plenum. The overall objective was achieved since there was good agreement between calculated and measured responses in the vicinity of the grid-plate shields.

* Research sponsored by DOE Office of Advanced Nuclear Systems and Projects.

4.12. GCFR RADIAL BLANKET AND SHIELD EXPERIMENT: OBJECTIVES, PREANALYSIS, AND SPECIFICATIONS*

D. T. Ingersoll D. E. Bartine F. J. Muckenthaler

(Abstract of ORNL/TM-6956, September, 1979)

An integral experiment has been designed for the verification of radiation transport methods and nuclear data used for the design of the radial shield for the proposed 300 MW(e) gas-cooled fast breeder reactor (GCFR). The scope of the experiment was chosen to include a thorium oxide radial blanket mockup as well as several shield configurations in order to reduce the uncertainties in the calculated source terms for the radial shield, and to reduce the uncertainties in the calculated radiation damage to the prestressed concrete reactor vessel (PCRV). Additionally, the measurements are intended to bound the

uncertainties in calculated gamma-ray heating rates within the blanket and shield. Although designed specifically for the GCFR, the experiment will provide generic data regarding deep penetration in ThO_2 and common shield materials, which should also benefit LMFBR designers.

Considerable preanalysis of the experiment was performed to solve design and fabrication problems. The analysis consisted of one-dimensional neutron and gamma-ray transport calculations in slab geometry representing the experimental configurations. Also, sensitivity calculations were performed for several of the detectors to be used in the experiments. Results showed that the detectors were highly sensitive to the nuclear cross sections of the materials which are of primary importance. Based on the intended objectives and the results of the preanalysis, a detailed measurement schedule was prepared which includes a description of configurations, detectors, and detector positions.

It was concluded that the final design and the measurement schedule is sufficient to meet the experiment objectives.

* Research sponsored by DOE Office of Advanced Nuclear Systems and Projects.

4.13. GCFR RADIAL BLANKET AND SHIELD EXPERIMENT*

F. J. Muckenthaler J. L. Hull[†] J. J. Manning

(Abstract of ORNL/TM-7237, in press)

This report presents integral neutron flux, energy spectra, and gamma-ray heating measurements made for the Radial Blanket and Shield Experiment at the Oak Ridge National Laboratory Tower Shielding Facility as part of a continuing Gas Cooled Fast Breeder Reactor program. The experimental configurations were divided into four basic segments: a spectrum modifier inserted into the Tower Shielding Reactor II beam; blanket slabs consisting of either ThO_2 or UO_2 placed directly behind the spectrum modifier; an inner radial shield behind the blankets; and an outer radial shield to complete the mockup. The segments were added in sequence, with selected measurements made within and beyond each segment.

The integral experiment was performed to provide verification of calculational methods and nuclear data used in designing a radial shield for the GCFR and determining the effectiveness of the design. The ThO_2 blanket measurements were needed to bracket the uncertainties in the nuclear cross sections for calculating both the neutron transmission through the blanket and the gamma-ray heating rates within the blanket. Measurements with a UO_2 blanket were included both as a reference for the ThO_2 analysis, neutron transmission through UO_2 having been successfully calculated in previous experiments, and to provide comparison information for other breeder reactor designs.

* Research sponsored by DOE Office of Advanced Nuclear Systems and Projects.

[†] Operations Division.

4.14. ANALYSIS OF THE ORNL-TSF RADIAL BLANKET AND SHIELD INTEGRAL EXPERIMENT*

D. T. Ingersoll L. R. Williams

(Reprint of Trans. Am. Nucl. Soc. 35, 470-472, 1980)

An integral experiment has been performed for verification of radiation transport method and nuclear data used in the design of the radial shield for the proposed gas-cooled fast breeder reactor demonstration plant (GCFR). The experiment was conducted in 1979 at the ORNL Tower Shielding Facility (TSF) and consisted of integral and spectral measurements of the neutron and gamma-ray flux transmitted through slabs of materials

which modeled a GCFR-type radial blanket and radial shield. Both uranium-oxide and thorium-oxide blankets were investigated as well as several shield designs comprising stainless steel, graphite, and boronated graphite. Detailed analysis of the measurements has been performed at ORNL and has identified a few data deficiencies, especially regarding secondary gamma-ray production. Also, ENDF/B-V-based cross sections for thorium were seen to give consistently better results than previous ENDF/B-IV data.

The experimental configurations consisted of 1.5-m square slabs placed contiguously along the beam centerline of the TSF reactor source. The largest configuration investigated (shown in Fig. 4.14.1) included a radial mockup of the GCFR from inside the radial blanket to 30 cm into the prestressed concrete reactor vessel. Measurements were made using Bonner balls (BB), NE-213 and spherical hydrogen counters, and thermoluminescent dosimeters (TLD). The detectors were positioned on the reactor beam centerline and were located behind the slab configurations except for the TLDs which were placed between the separate slabs. A complete description of the experiment is given in Ref. 1.

Fig. 4.14.1. Plan View of the Experiment Geometry for Mockup of a GCFR ThO_2 Radial Blanket and Radial Shield.

Analysis of the experiment utilized one- and two-dimensional (1- and 2-D) transport methods and a host of auxiliary codes to compute detector responses and to display the results. The neutron and gamma-ray fluxes at spatial locations within the blanket and shield configurations were calculated using the DOT-IV discrete ordinates code.² Fluxes at external positions were determined using the FALSTF³ code which uses the scattering source produced by DOT-IV to estimate a total last-flight source from the 2-D configuration.

The calculated fluxes were compared directly to the unfolded neutron spectra which ranged from 0.05 to 20 MeV and the gamma-ray spectra which ranged from 1 to 12 MeV. The comparisons are generally within 20 to 30% for neutrons, with somewhat larger discrepancies above 4 MeV for the shield configurations. However, the gamma-ray comparisons show

discrepancies ranging from 30% to a factor of 10. For most cases, the general shape of the calculated gamma-ray spectra agree with the measurement, although the magnitude is always underpredicted. An inadequate angular representation for the secondary gamma-ray production data has been identified as a possible reason for the observed discrepancies.

Calculated neutron fluxes were folded with analytic energy-dependent response functions to predict the integral counting rates observed for the 3-, 6-, and 10-in. Bonner ball detectors. The BB responses are such that the 3-in. ball represents primarily epithermal flux while the 6- and 10-in. balls represent total and fast flux, respectively. Calculated-to-experimental ratios (C/E) for many of the major configurations are given in Table 4.14.1. It is apparent from Table 4.14.1 that cases containing a UO_2 blanket tend to underpredict the measured data while the ThO_2 cases generally overpredict the data. Also, the disagreements tend to increase with more attenuation and with greater distance between the configuration and the detector.

Table 4.14.1. Calculated-to-Experimental Ratios for Bonner Ball Detectors

Configuration ^a	Distance to Detector (cm)	C/E		
		3-in. BB	6-in. BB	10-in. BB
(II-A) SM + 30-cm UO_2	30.5	0.98	0.91	0.83
	285.4	0.89	0.86	0.77
	304.8	0.88	0.84	0.77
(II-B) SM + 30-cm UO_2 + ref. inner shield	30.5	0.89	0.79	0.71
	304.8	0.82	0.72	0.64
	1277.2	0.97	0.83	0.73
(V-B) SM + 30-cm UO_2 + 15-cm C	30.5	0.97	0.87	0.73
	304.8	0.94	0.84	0.72
	1294.4	1.30	1.15	0.95
(V-C) SM + 30-cm UO_2 + 15-cm C + 15-cm BG + 4.5-cm SS	30.5	0.91	0.81	0.72
	304.8	0.82	0.75	0.69
	1270.0	0.91	0.84	0.73
(I-E) SM + 45-cm ThO_2	30.5	1.02	1.03	0.99
	304.8	1.01	1.09	0.88
	1296.4	1.27	1.36	1.20
(III-B) SM + 45-cm ThO_2 + ref. inner shield	30.5		1.09	1.00
	304.8	1.19	1.03	0.97
	1263.0	1.36	1.22	1.10
(IV-C) SM + 45-cm ThO_2 + ref. inner shield + ref. outer shield	30.5	1.08	1.06	0.98
	304.8	1.04	1.13	1.01
	1210.5	1.38	1.23	1.00

^aSM = spectrum modifier; C = graphite; BG = boronated graphite; SS = stainless steel; ref. inner shield = 15-cm BG + 15-cm SS; ref. outer shield = 5-cm BG + 5-cm SS.

Similar analysis was performed for the $\text{CaF}_2:\text{Mn}$ TLD measurements. Differences between calculated and measured gamma-ray heating are less than 10% within the UO_2 blankets and adjacent shields, while the ThO_2 blankets show 70% discrepancies when ENDF/B-IV-based cross sections were used. This is due to the absence of gamma-ray production data for thorium in ENDF/B-IV. When ENDF/B-V-derived data for Th were used, the TLD discrepancies were reduced to less than 10%.

The Radial Blanket and Shield experiment and corresponding analysis benefitted the GCFR program by providing required verification of the adequacy of design methods and data and by highlighting further data needs. Specifically, it was shown that neutron transmission through laminated shields containing steel, graphite, and boronated graphite could be calculated well, even for large attenuation. Also, it was shown that ENDF/B-V thorium data were a significant improvement over ENDF/B-IV data for both total neutron removal and gamma-ray production. Although the experiment was performed and analyzed for the GCFR program, most of the data and conclusions are valid for other fast reactor concepts.

* Research sponsored by DOE Office of Advanced Nuclear Systems and Projects.

1. F. J. Muckenthaler, J. L. Hull, and J. J. Manning, "GCFR Radial Blanket and Shield Experiment," ORNL/TM-7237 (in publication).
2. W. A. Rhoades, D. B. Simpson, R. L. Childs, and W. W. Engle, Jr., "The DOT-IV Two-Dimensional Discrete Ordinates Transport Code with Space-Dependent Mesh and Quadrature," ORNL/TM-6529 (1979).
3. R. L. Childs, "FALSTF User's Manual," draft report.

4.15. RECENT SHIELDING EXPERIMENTS AT THE ORNL TOWER SHIELDING FACILITY*

D. E. Bartine D. T. Ingersoll C. O. Slater

(Reprint of *Trans. Am. Nucl. Soc.* 33, 664, 1979)

Through the early portion of this decade, the experimental activities at the ORNL Tower Shielding Facility were dominated by the LMFBR program and included measurements of neutron transmission, neutron streaming, and gamma-ray heating in numerous LMFBR blanket, shield, and pipe chaseway mockups. Since 1975 the emphasis has shifted to shielding-related experiments for the gas-cooled fast breeder reactor (GCFR). The low density coolant and relatively open core design of the GCFR creates special problems for the shield designer, resulting in the need for verification experiments to test shielding data, methods, and final shield designs. The GCFR integral shielding experiments performed to date include: (a) a generic pin streaming experiment,¹ (b) a prototypic grid plate shield design confirmation experiment,² and (c) a radial blanket and shield data verification experiment.³ The purpose of this paper is to briefly describe the GCFR shielding experiments and to highlight the aspects of the experiments which could result in new benchmark shielding problems.

The generic pin streaming experiment was an attempt to verify existing discrete ordinates and Monte Carlo methods for calculating axial neutron streaming in a fuel pin lattice. The configuration consisted of 894 ²³⁵U-enriched UO₂ fuel pins loaded with a triangular pitch into a cylindrical pipe which was positioned such that the axis of the pipe coincided with the collimated reactor beam centerline. Integral and spectral neutron measurements were made behind the pin array on the beam centerline and at several positions off the centerline. Two-dimensional (2-D) discrete ordinates methods and 3-D Monte Carlo methods were used to predict the measured results. Several 2-D models were used for the calculations which represented the fuel pin array as either a completely homogenized region, or as concentric rings with alternating fuel and void regions.

The results of the analysis showed that the homogeneous and heterogeneous modeling of the pin array was sufficient to bracket the measured data, with the homogeneous model yielding an axial neutron leakage which was too low and the heterogeneous model yielding results which were too high. A refinement of the concentric rings which represent the pin array causes the calculated leakage to approach the measurements, but only very slowly. The Monte Carlo calculations gave a better comparison with the measurements than the discrete ordinates method, but only with significant computational effort. It was concluded that an accurate calculation of the axial streaming in a fuel pin array should use Monte Carlo methods for absolute normalization and discrete ordinates methods for detailed energy and spatial distributions.

One objection which has been raised regarding the use of the generic pin streaming experiment as a benchmark problem for relevant methods was that the dominant source of leakage neutrons was determined to be uncollided neutrons from the modified reactor beam, rather than from within the pins themselves. The followup GCFR experiment used a shadow shield arrangement to eliminate this problem by creating a fission source in the pins. The experiment, which was performed to verify the effectiveness of the GCFR grid-plate shield design, was constructed and performed in a modular fashion providing detailed measurements relating to fuel pin streaming, shield effectiveness in a prototypic design, and neutron transmission through a prototypic grid plate.

The analysis of this extensive experiment has recently been completed and has shown that only state-of-the-art transport methods yielded an agreement with the measurements within the desired 20% accuracy. As before, combining discrete ordinates and Monte Carlo calculations gave effective results. Interestingly, it was found that an accurate calculation of the angular distribution of neutrons transmitted through the relatively large grid plate penetrations was more difficult than determining the axial streaming in the fuel pins. Modeling difficulties appeared to be a large contributing factor.

Whereas the two previous experiments have been predominantly for methods verification, and hence would lead to methods-oriented benchmark problems, the most recent TSF experiment emphasized data testing. Measurements were made of neutron and gamma-ray transmission through slab mockups of the GCFR radial blanket and radial shield configuration. In particular, both UO and ThO blankets were investigated with the emphasis on the thorium, and graphite, stainless steel, and boronated graphite shield arrangements were investigated. Gamma-ray heating measurements were also made throughout the configurations.

The relative simplicity of the geometry of the experiment provides the potential for several benchmark shielding problems. Good agreement between calculations and measurements was achieved for some configurations which will provide a benchmark for more approximate methods and/or new cross-section data. Other configurations, noticeably the ThO blanket mockup, showed significant disagreement, which might help to guide future evaluations of the nuclear data.

In conclusion, three distinctly different integral experiments have been performed at the Tower Shielding Facility in recent years which could provide several new benchmark shielding problems. The new benchmarks would emphasize both methods and data and will include neutron streaming, neutron and gamma-ray transmission, and gamma-ray heating.

Perhaps the most difficult aspect of preparing benchmark problems from the experiments is to dedicate the time required to produce the high-quality documentation which is expected of a good benchmark. With the prevailing attitude toward applications, it is frequently the case that new projects are begun concurrently with the analysis of a recently completed experiment. The value of current benchmark problems needs to be realized, and sufficient emphasis given to this important area.

*Research sponsored by DOE Office of Advanced Nuclear Systems and Projects.

1. C. O. Slater and M. B. Emmett, "Final Analysis of a TSF Experiment on Neutron Streaming Through a Lattice of GCFR-Type Fuel Pins," ORNL/GCR-78/5 (February 1978).
2. C. O. Slater, S. N. Cramer, and D. T. Ingersoll, "Analysis of the ORNL/TSF GCFR Grid-Plate Shield Design Confirmation Experiment," Trans. Am. Nucl. Soc. 32, 641 (1979).
3. D. T. Ingersoll, D. E. Bartine, and F. J. Muckenthaler, "Design of Deep-Penetration Integral Experiment for Thorium Blanket and Radial Shield Mockups," Trans. Am. Nucl. Soc. 32, 643 (1979).

4.16. DESIGN OF DEEP-PENETRATION INTEGRAL EXPERIMENT FOR THORIUM BLANKET AND RADIAL SHIELD MOCKUPS*

D. T. Ingersoll D. E. Bartine F. J. Muckenthaler

(Reprints of Trans. Am. Nucl. Soc. 82, 642, 1979)

The design of reactor shielding is a complex effort involving intimate relationships between radiation transport, thermomechanical forces, material properties, and economics. To aid the shield designer in achieving the optimum compromise of these considerations, several analytic tools have been developed, such as discrete ordinates and Monte Carlo codes. For advanced reactors, where little operating experience is available, verification of these design methods and the design-based data is important. Integral experiments perform this function by (a) providing data against which the methods and data can be tested, or (b) providing direct verification of the effectiveness of the final design.

An integral experiment has been designed for the verification of radiation transport methods and nuclear data used for the design of the radial shield for the proposed 300-MW(e) gas-cooled fast breeder reactor (GCFR).¹ The scope of the experiment was chosen to include a thorium oxide radial blanket mockup as well as several shield configurations. The blanket measurements are needed to reduce the large uncertainties that exist in the cross-section data required for calculating neutron transmission through a thorium blanket, hence reducing the uncertainties in the calculated source terms for the radial shield. Similarly, the shield measurements are needed to reduce the uncertainties in the calculated radiation damage to the prestressed concrete reactor vessel (PCRV). Additionally, the measurements are intended to bound the uncertainties in calculated gamma-ray heating rates within the blanket and shield. Although designed specifically for the GCFR, the experiment will provide generic data regarding deep penetration in ThO_2 and common shield materials, which should also benefit LMFBR designers.

With the relatively high cost of fabricating and performing large-scale experiments, it was important that sufficient preanalysis be performed to produce a time- and cost-efficient experiment design and schedule. More importantly, some assurance had to be given that the results would satisfy the original intent of the experiment. For this integral test, it was desirable to design a one-dimensional (1-D) mockup of the GCFR radial blanket and shield, and to provide sufficient flexibility for several alternative shield designs to be investigated. It was also necessary that the neutron source be representative of anticipated GCFR source spectra for both the blanket and the shield configurations. In addition, the materials, the dimensions, and the detectors and their locations had to be chosen so the observed detector responses would be sufficiently sensitive to the quantities of interest to yield results that could be extended reliably to the GCFR design.

The preanalysis was performed primarily using the 1-D ANISN² transport code and the SWANLAK³ sensitivity code. The neutron source employed was the Tower Shielding Facility (TSF) reactor at ORNL coupled with a spectrum modifier to produce a source energy distribution similar to the GCFR core leakage spectrum. The composition of the spectrum modifier was selected based on calculated neutron spectra emerging from several trial compositions.

Previous experience has shown that 1-D configurations can be adequately modeled at the TSF by placing slabs with lateral dimensions exceeding 1.5 m into the 80-cm-diam collimated beam.⁴ Detector measurements are then made on the beam centerline behind the slab configuration. Figure 4.16.1 shows the experimental arrangement for a ThO_2 blanket mockup. The concrete that surrounds the configuration provides a biological shield for TSF personnel while the lithiated paraffin minimizes the "reflector effect" of the concrete. The effect of the concrete was quantified by comparing 1- and 2-D calculations for a representative configuration.

Sensitivity analysis was used to determine an acceptable arrangement for the gamma-ray heating measurements within the thorium blanket. It was determined that for a thermoluminescent detector (TLD) sandwiched between two 13-cm-thick ThO_2 slabs encased in 0.95-mc SS-304, approximately 20% of the TLD response resulted from gamma-ray production in the stainless steel immediately adjacent to the detector. The remaining 80% of the TLD

Fig. 4.16.1. Plan View of Blanket Configuration for the Proposed Experiment.

response resulted primarily from $\text{Th}(n, \gamma)$ reactions inside the blankets. Although this signal-to-noise ratio appeared sufficiently high to infer the desired data regarding thorium gamma-ray production, the SS-304 background was further reduced by redesigning one of the three blanket slabs as two 6.6-cm slabs encased in 0.48-cm SS-304. This retained the proper $\text{ThO}_2/\text{SS-304}$ atom ratio while allowing less steel to border the TLD. This feature also permitted neutron transmission measurements to be made in finer thickness increments.

We conclude that the design and measurement schedule for the proposed radial blanket and shield experiment will provide a definitive evaluation of the relevant transport methods and nuclear data that are being used currently to design both GCFR and LMFR radial blankets and shields. This type of evaluation will provide a timely contribution to current assessments of alternative fuel cycles in fast and thermal reactor systems.

* Research sponsored by DOE Office of Advanced Nuclear Systems and Projects.

1. General Atomic Co. Project Staff, "300-MW(e) Gas-Cooled Fast Breeder Reactor Demonstration Plant," GA-A13045, General Atomic Co. (1974).
2. W. W. Engle, Jr., "A Users Manual for ANISN - A One-Dimensional Discrete Ordinates Transport Code with Anisotropic Scattering," K-1693 (1967).
3. D. E. Bartine, F. R. Mynatt, and E. M. Oblow, "SWANLAKE, A Computer Code Utilizing ANISN Radiation Transport Calculations for Cross Section Sensitivity Analysis," ORNL/TM-3809 (1973).
4. R. E. Maerker and F. J. Muckenthaler, "The Absolute Neutron Spectrum Emerging Through the Large Beam Collimator from the TSR-II Reactor at the Tower Shielding Facility," ORNL/TM-5183 (1976).

4.17. DEEP PENETRATION INTEGRAL EXPERIMENT FOR A THORIUM BLANKET MOCKUP*

D. T. Ingersoll F. J. Muckenthaler

(Abstract of paper in Nuclear Cross Sections for Technology, NBS Special Publication 594, p. 122, 1980)

An integral experiment has been performed for verification of radiation transport methods and nuclear data used for design of the radial shield for the gas-cooled fast breeder reactor (GCFR). The experiment included a thorium oxide blanket mockup and several shield configurations. The blanket measurements were needed to reduce uncertainties in the cross-section data used for calculating neutron transmission through a thorium blanket and to bound the uncertainties in calculated gamma-ray heating rates within the blanket.

Measured neutron spectra and integral flux data are compared to 1D calculations of the transmitted flux. Calculations using ENDF/B-IV and ENDF/B-V data for thorium are compared and show the version V data to be superior above 1 MeV. The experiment, which is primarily sensitive to the total removal cross section, also showed V to be an improvement below 1 MeV, but still discrepant from the measurements.

*Research sponsored by DOE Office of Advanced Nuclear Systems and Projects.

INTEGRAL EXPERIMENTS SUPPORTING LIQUID METAL FAST BREEDER REACTOR DESIGN

4.18. STUDY OF NEUTRON TRANSMISSION THROUGH PLANAR AND CYLINDRICAL ANNULAR SLITS IN IRON SHIELDS*

C. E. Clifford F. J. Muckenthaler F. R. Mynatt L. S. Abbott

(Abstract of ORNL/TM-3513, September, 1980)

During a 1970 study of the shielding effectiveness of the rotating top plugs in the reactor pressure vessel head of the Fast Flux Test Facility, an experiment was performed at the Tower Shielding Facility to measure the streaming of neutrons through planar and cylindrical annular slits in a thick iron shield. The reactor beam used as the neutron source was modified to represent as nearly as possible the energy spectrum of the neutrons emerging from the surface of the FFTF sodium pool, the modifier design being based on a series of discrete ordinates transport calculations. The experiment showed that neutron streaming through straight planar slits and straight cylindrical annular slits greatly increased the peak neutron transmission through the shield, but that the introduction of a single offset in a slit reduced the streaming effect dramatically. Introducing a second offset had considerably less effect. An analysis of the experiment using discrete ordinates methods was limited in 1970 by the lack of accurate cross sections for iron and an inadequate technique for calculating the neutron transmission through bulk iron. As a result, the calculated results are not in complete agreement with the experimental results. However, the further development of the calculational method required for this analysis resulted in improved techniques that have been successfully applied in subsequent studies in the FFTF program.

*Research sponsored by DOE Office of Reactor Research and Technology.

4.19. ANALYSIS OF A TSF EXPERIMENT ON SECONDARY GAMMA-RAY PRODUCTION IN REINFORCED CONCRETE SHIELDS*

R. L. Childs F. J. Muckenthaler L. S. Abbott

(Abstract of ORNL-6272, September, 1980)

The effect that reinforcing iron within the large concrete shields proposed for Liquid Metal Fast Breeder Reactors would have on the production of secondary gamma rays through the shields was investigated in a Tower Shielding Facility experiment and an accompanying analysis.[†] In the experiment concrete slabs of various thicknesses and with and without reinforcement were positioned in a Tower Shielding Reactor II beam modified to represent a fast reactor spectrum, and measurements were made beyond the slabs with Bonner ball neutron detectors and a sodium iodide gamma-ray spectrometer. In addition, energy deposition rates were measured within the slabs by ion chambers and thermoluminescent dosimeters (TLDs). In the analysis, calculations of the experiment were performed in two-dimensional geometry with the discrete ordinates code DOT. With few exceptions, the calculated and measured values consistently disagreed for reasons not yet fully understood; however, in spite of the difference in absolute values, both the calculations and the measurements indicated that the increase in the secondary gamma-ray flux due to the reinforcement was at most 20%.

* Research sponsored by DOE Office of Reactor Research and Technology.

† This report describes work performed in 1974 and 1975.

5. DEVELOPMENT OF METHODS FOR SHIELD AND REACTOR ANALYSES

5.0. INTRODUCTION

Methods development work in the Division continues in the shielding area (discrete ordinates and Monte Carlo) and in the reactor analysis area, primarily with the VENTURE system. An interesting new effort is directed toward depletion perturbation theory for reactor burnup analysis.

Methods for Shielding Analysis

A new version of the basic two-dimensional discrete ordinates code, DOT 4.3, has been developed and is now undergoing testing and documentation. This code includes diffusion acceleration, and has improved convergence rates and adaptability to non-IBM computers. The Discrete Ordinates System, a set of codes which includes and supports DOT calculations, was expanded to include plotting and perturbation capability. Studies investigated the use of alternate difference models, intensive comparison of DOT with TWOTRAN leading to an understanding of the differences between these codes, and a repair for scattering expansion truncation error.

An international review of Monte Carlo codes included ORNL experience with the French TRIPOLI code as well as the ORNL MORSE code. A new point Monte Carlo code was developed and tested for deep-penetration calculations. Several improvements were made in the MORSE-related packages, including implementing albedo capability and modernizing input file formats.

Methods for Reactor Analysis

The core analysis package based around the VENTURE three-dimensional diffusion theory neutronics code now includes depletion and fuel management capability. Special procedures have been incorporated to model discrete fuel replacement with recycle, applicable to fast breeder or prismatic core gas cooled reactor concepts, and to model continuous fueling which is applicable to the pebble bed gas cooled reactor or CANDU heavy water core concepts. Thermal hydraulics capability has been incorporated to treat the pebble bed core. Weighting functions can be generated for sensitivity and uncertainty analysis, including burnup-dependent perturbation theory. Continuing methods development supports project application needs, including stability analysis.

Reactor Lattice Analysis in the Resonance Range

The accurate computation of resonance reaction rates in heterogeneous reactor lattices is one of the most challenging problems in LWR physics. Under EPRI sponsorship a new methodology (i.e., OZMA) was developed for solving the point-energy integral or discrete ordinates transport equations on a dense energy grid as required to handle resonance profiles. The new approach eliminates simultaneously most of the approximations involved in simple treatments of resonance shielding, and the statistical problems inevitable in Monte Carlo calculations.

5.1. A MODIFIED APPROACH TO DIFFUSION ACCELERATION IN NEUTRON TRANSPORT PROBLEMS

J. E. Aull W. A. Rhoades H. L. Dodds[†]

(Reprint of Trans. Am. Nucl. Soc. 22, 306-307, 1979)

State-of-the-art neutron transport problems are expensive, and rapid convergence is an important objective. Alcouffe¹ showed that diffusion acceleration can improve convergence, but his method had an important limitation which made application to deep-penetration problems difficult. Alcouffe's method required a special difference approximation to assure convergence to the proper transport result. This approximation was incompatible with the weighted-difference strategy² used to mitigate the effects of extrapolation. This paper will show a modification that makes the method independent of the extrapolation strategy.

The result of a transport iteration on one energy group can be expressed as

$$\tilde{\phi}^k(r, \Omega) + \sigma^T(r, \Omega) \tilde{\phi}^k(r, \Omega) = Q(r, \Omega) + \int \sigma^S(r, \Omega' \cdot \Omega) \tilde{\phi}^{k-1}(r, \Omega') d\Omega' \quad (1)$$

where the tilde denotes an unimproved flux result. This result is inconsistent due to the use of flux results from the previous iteration in calculating the scattering source. Alcouffe's source correction scheme (SCS) improves this result by solving a corrected diffusion equation:

$$-\nabla \cdot D(r) \nabla \phi^k(r) + \sigma^R(r) \phi^k(r) = Q_0(r) - \nabla \cdot \bar{J}^k(r) - \nabla \cdot D(r) \nabla \tilde{\phi}^k(r) \quad (2)$$

where

$$\phi^k(r) = \int \phi^k(r, \Omega) d\Omega \quad (3)$$

$$J^k(r) = \int \Omega \phi^k(r, \Omega) d\Omega \quad (4)$$

$$\sigma_0^S(r) = \iint \sigma^S(r, \Omega' \cdot \Omega) d\Omega' d\Omega \quad (5)$$

$$\sigma^R(r) = \sigma^T(r) - \sigma_0^S(r) \quad (6)$$

$$Q_0(r) = \int Q(r, \Omega) d\Omega \quad (7)$$

The scattering inconsistency does not appear in these. The last two terms on the right assure rebalance consistency in the continuous form; i.e., that

$$\phi^k(r) \nabla \cdot \bar{J}^k(r) \quad (8)$$

when

$$\nabla \cdot \bar{J}^k(r) = \nabla \cdot \bar{J}^{k-1}(r) \quad (9)$$

In our modified approach, we integrate Eq. (1) over direction and rearrange, using Eqs. (3) through (7)

$$\nabla \cdot \bar{J}^k(r) = Q_0(r) - \sigma^R(r) \phi^k(r) - \sigma_0^S(r) [\phi^k(r) - \tilde{\phi}^{k-1}(r)] \quad (10)$$

With this, Eq. (2) becomes a new correction formulation

$$-\nabla \cdot D(r) \nabla \phi^k(r) + \sigma^R(r) \phi^k(r) = -\nabla \cdot D(r) \nabla \bar{\phi}^k(r) + \sigma^R(r) \bar{\phi}^k(r) + \sigma_c^S(r) [\bar{\phi}^k(r) - \phi^{k-1}(r)] \quad (11)$$

This always satisfies Eq. (8) when Eq. (9) is satisfied. Any accurate difference formulation can be used for the diffusion flow terms in Eq. (11), if the same formulation is used on both sides. If a poorly behaved problem tends to produce negatives, they can be suppressed by artificially restricting ϕ^k to positive values. Alternatively, a limited source can be used

$$-\nabla \cdot D(r) \nabla \phi^k(r) + \sigma^R(r) \phi^k(r) = -\nabla \cdot D(r) \nabla \bar{\phi}^k(r) + \max\{0, \sigma^R(r) \bar{\phi}^k(r) + \sigma_c^S(r) [\bar{\phi}^k(r) - \phi^{k-1}(r)]\} \quad (12)$$

In practice, little difference between the results of Eq. (11) and (12) has been noted, although Eq. (12) might not perform as well where σ^R is small, such as in graphite.

Several problems were solved using both the standard¹ and the modified version of SCS. The problems use two-dimensional slab geometry and have void boundaries (Fig. 5.1.1). The solutions were performed using the DOT IV code,³ P-3 scattering expansion, S-8 directional quadrature, and the theta-weighted difference strategy.² An isotropic fixed source was distributed along the bottom row of mesh cells. The material assignments and convergence results are shown in the figure. In each case, the standard approach reached a nonzero minimum, and then would go no lower. When this happened, the rebalance was "turned off" by replacing ϕ^k with

$$\bar{\phi}^k(r) + [\phi^k(r) - \bar{\phi}^k(r)]/\lambda \quad (13)$$

where λ was increased with each iteration.

Notes:

1. Numbers inside figure indicate zone number.
2. Mesh boundaries are indicated at left and bottom.

Problem number				Iterations to convergence	
	1	2	3	Standard method (convergence Forced)	Modified method
1	concrete	concrete	concrete	16	9
2	sodium	sodium	sodium	10	6
3	steel	steel	steel	20	10
4	sodium	steel	concrete	15	10

Fig. 5.1.1. Problem Description and Results.

It is evident that the modified approach is superior to the standard SCS method on these problems. Application to larger examples has been similarly successful. Since the transport and diffusion difference techniques can now be developed separately, future improvements will be facilitated by the modification.

* Research sponsored by DOE Office of Reactor Research and Technology.

1. R. E. Alcouffe, Nucl. Sci. Eng., 64, 344 (1977).
2. W. A. Rhoades and W. W. Engle, Jr., Trans. Am. Nucl. Soc., 27, 776 (1977).
3. W. A. Rhoades, D. B. Simpson, R. L. Childs, and W. W. Engle, Jr., "The DOT IV Two-Dimensional Discrete-Ordinates Transport Code with Space-Dependent Mesh and Quadrature," ORNL/TM-6529 (August 1978).

5.2. THE STABILITY OF THE MESH-CORNERED SYNTHETIC METHOD OF DIFFUSION ACCELERATION OF THE DOT-IV TRANSPORT CODE*

J. E. Aull

(Abstract of ORNL/TM-7097, October, 1979)

Three methods for accelerating the discrete ordinates equations using variations of the synthetic method are examined. It is found that the use of difference equations written about the mesh corners, rather than a specific form of the equations, brings stability. These methods are compared with three other methods in test problems covering the stability domain of interest.

* Research sponsored by Defense Nuclear Agency.

5.3. ACCELERATION OF THE INNER ITERATION OF THE DOT-IV TRANSPORT CODE USING A NEW SOURCE CORRECTION SCHEME*

J. E. Aull

(Abstract of ORNL/TM-7404, July, 1980; also thesis for Master of Science Degree, The University of Tennessee, 1979)

A detailed description of the steady state Boltzmann transport equation is given. Then the discrete ordinates method of solving the transport equation is described.

The conventional rebalance method, the source correction scheme of rebalance and a new source correction scheme involving a correction equation with a modified flow term are derived. Difference equations for each version of the source correction scheme are presented. The different versions of the source correction scheme and the conventional rebalance method are compared on several test problems in one- and two-dimensional slab geometry.

Results are shown which demonstrate that the new source correction scheme is superior to the conventional rebalance method. It is also seen that the new source correction scheme is compatible when used with a weighted difference formulation in the inner iteration of the transport solution.

* Research sponsored by Defense Nuclear Agency.

5.4. EFFECTIVENESS OF THREE REBALANCE METHODS IN DEEP PENETRATION PROBLEMS*

W. A. Rhoades E. T. Tomlinson[†]

(Abstract of Trans. Am. Nucl. Soc. 53, 717, 1978)

The space-rebalance method brought important new capability to discrete-ordinates calculations by using an easily-solved procedure. Later, diffusion synthetic acceleration used the diffusion equation as the auxiliary equation. Application of this new approach has been slow, partially due to concomitant restrictions. Aull et al. showed a reformulation which brought compatibility with weighted-difference and negative-fixup schemes. Miller showed that the differential forms of the conventional space rebalance (CRB) and the newer methods could be derived from a common framework. This paper will, similarly, cast the difference form of Aull's consistent diffusion acceleration (CDA) into the same form as CRB and will indicate a third approach suggested by this comparison. Variations of these methods will be tested on deep-penetration problems.

* Research sponsored by DOE Office of Reactor Research and Technology.

[†] UCC-ND Computer Sciences Division.

5.5. EVALUATION OF FLUX EXTRAPOLATION MODELS FOR DISCRETE ORDINATES SHIELDING ANALYSIS*

E. T. Tomlinson[†] W. A. Rhoades

(Reprint of Trans. Am. Nucl. Soc. 34, 650-651, 1980)

There has been a long-standing discrepancy in the results calculated by the discrete ordinates transport codes DOT¹ and TWOTRAN.² This has been attributed to two differences:

1. the use of different extrapolation models relating the three unknown boundary fluxes and the mean flux to the three known boundary fluxes, and
2. the use, by DOT, of zero-weight directions to initiate the azimuthal direction sweep.

In this study, it was shown that the two codes could be made to give identical results, and the suitability of the various models for shielding calculations was examined.

Since the DOT-IV code already contains several extrapolation models, it was a straightforward matter to add the "linear-zero" model used in TWOTRAN. The TWOTRAN method of initiating the azimuthal sweep with a non-zero-weight direction was also implemented. Then by comparing results it was found that TWOTRAN contained a discrepancy that required repair. Special equations are required when overextrapolation occurs in the initiating directions. These equations were missing from TWOTRAN. The result was that TWOTRAN used values left in core from previous calculations. Repairing this discrepancy resulted in agreement between the two codes to the full limit of machine precision.

While the unmodified TWOTRAN gave anomalous results to certain shielding problems, both modified codes gave satisfactory results whether or not the zero-weight directions were used in the quadrature set.

The various models used all degenerate to the basic linear (diamond difference) model away from the domain of potential negative flux generation, and they give the same result for finely meshed core problems. In this study, the mesh in a representative shielding problem was refined in successive steps until all spacing was less than the two meanfree-path threshold for negative generation in all directions of traverse. Isotropic scattering and an S-8 symmetrical quadrature set were chosen. The results were extrapolated to zero mesh spacing using a three-parameter fit.

The results, shown in Fig. 5.5.1, indicate that each of the flux extrapolation models converges to a solution as the mesh spacing decreases, but that the converged solution depends on the model. It was shown that all of the models generated negative values, even for the finest mesh, and required fixup according to their separate procedures.

Fig. 5.5.1. Top Leakage as a Function of Mesh Size for Various Flux Extrapolation Models.

This effect can be understood by examining the linear equation for the mean flux:

$$\bar{N} = \frac{VS + 2 \left[\frac{1}{2} \bar{A} N_{i-c} + 2 \left(\frac{1}{2} \bar{B} N_{j-d} + \frac{1}{2} \bar{A} N_{m-1/2} \right) \right]}{V \bar{A} + 2 \left[\frac{1}{2} \bar{A} + 2 \left(\frac{1}{2} \bar{B} + \frac{1}{2} \bar{A} \right) \right]}$$

In the case of small mesh spacing and small or zero N_{i-c} and $N_{m-1/2}$, which occurs at the right boundary of the problem in Fig. 5.5.1, this becomes:

$$\bar{N} = \frac{\frac{1}{2} \bar{B} N_{j-d}}{\frac{1}{2} \bar{A} + \frac{1}{2} \bar{B}}$$

Since $\bar{A}$ and $\bar{B}$ are usually of comparable magnitude, $\bar{N}$ for some directions will be less than $1/2 N_{j-d}$, resulting in a negative value of N_{j+d} . This effect is not seen in the 1-D geometries. It results in the use of negative fixup procedures in typical shielding calculations no matter how fine the mesh becomes. In such cases, the converged result depends on the extrapolation model, and convergence of the iterative process also becomes more difficult.

As to which model is preferable, the figure shows that the weighted model converges to a higher leakage flux in this problem, in agreement with general experience. It is preferred for shielding problems in which maximum leakage is sought, but is unsuitable for core calculations for the same reason. It usually converges faster than the other models. The remaining models are approximately equivalent in result, although the theta-weighted³ model sometimes converges faster than the linear-zero models. The error due to finite mesh size can be larger than the difference between models.

* Research sponsored by Defense Nuclear Agency.

† UCC-ND Computer Sciences Division.

1. W. A. Rhoades, D. B. Simpson, R. L. Childs, and W. W. Engle, Jr., "The DOT-IV Two-Dimensional Discrete Ordinates Transport Code With Space-Dependent Mesh and Quadrature," ORNL/TM-6529 (January 1979).
2. K. D. Lathrop and F. W. Brinkley, "TWOTRAN-II: An Interfaced, Exportable Version of the TWOTRAN Code for Two-Dimensional Transport," LA-4848-MS (July 1973).
3. W. A. Rhoades and W. W. Engle, Jr., "A New Weighted-Difference Formulation for Discrete-Ordinates Calculation," Trans. Am. Nucl. Soc. 27, 776 (1977).

5.6. FLUX EXTRAPOLATION MODELS USED IN THE DOT IV Discrete ORDINATES NEUTRON TRANSPORT CODE*

E. T. Tomlinson[†] W. A. Rhoades W. W. Engle, Jr.

(Abstract of ORNL/TM-7032, May, 1980)

The DOT IV code solves the Boltzmann transport equation in two dimensions using the method of discrete ordinates. Special techniques have been incorporated in this code to mitigate the effects of flux extrapolation error in space meshes of practical size. This report presents the flux extrapolation models as they appear in DOT IV. A sample problem is also presented to illustrate the effects of the various models on the resultant flux. Convergence of the various models to a single result as the mesh is refined is also examined. A detailed comparison with the widely used TWOTRAN II code is reported. The features which cause DOT and TWOTRAN to differ in the converged results are completely observed and explained.

*Research sponsored by Defense Nuclear Agency.

[†]UCC-ND Computer Sciences Division.

5.7. DOGS - A COLLECTION OF GRAPHICS FOR SUPPORT OF DISCRETE ORDINATES CODES*

D. T. Ingersoll C. O. Slater

(Abstract of ORNL/TM-7188, March, 1980)

A collection of computer codes called DOGS (Discrete Ordinates Graphics Support) has been developed to assist in the display and presentation of data generated by commonly used discrete ordinates transport codes. The DOGS codes include: EGAD for plotting two-dimensional geometries, ISOPLOT4 for plotting 2-D fluxes in a contour line fashion, FORM for plotting 2-D fluxes in a 3-D surface fashion, ACTUAL for calculating 2-D activities, TOOTH for calculating and plotting space-energy contribution fluxes, and ASPECT for plotting energy spectra. All of the codes use FIDO input formats and DISPLA graphics software including the DISSPOP post processors. The codes are generally tailored for minimum input requirements when used with the ANISN and DOT discrete ordinates codes, but include many special options for alternate uses and flexible plot enhancements. All of the DOGS codes function independently, and are operational on the ORNL and CTC IBM 360/370 computer systems.

*Research sponsored by DOE Office of Advanced Nuclear Systems and Projects.

5.8. A REVIEW OF THE THEORY AND APPLICATION OF MONTE CARLO METHODS:
PROCEEDINGS OF A SEMINAR-WORKSHOP, OAK RIDGE, TENNESSEE,
APRIL 21-23, 1980*

Edited by
D. K. Trubey B. L. McGill

(Abstract of ORNL/RSIC-44, August, 1980)

This report consists of 24 papers which were presented at the seminar on Theory and Application of Monte Carlo Methods, held in Oak Ridge on April 21-23, plus a summary of the three-man panel discussion which concluded the seminar and two papers which were not given orally. These papers constitute a current statement of the state of the art of the theory and application of Monte Carlo methods for radiation transport problems in shielding and reactor physics.

*Work jointly sponsored by Defense Nuclear Agency and by U.S. Nuclear Regulatory Commission.

5.9. EXPERIENCE WITH TRIPOLI AT ORNL*

S. N. Cramer R. W. Roussin

(Abstract of RSIC-44, pp. 296-304, August, 1980)

Initial use of the TRIPOLI code at Oak Ridge National Laboratory (ORNL) involves calculation of sample problems for both neutron and gamma rays. Comparison with existing MORSE results indicates that the computing efficiency of TRIPOLI is somewhat better for the problems studied. Calculation of a thick (90 cm) concrete and steel integral experiment with TRIPOLI gives good agreement with the experimental results. This calculation involved the neutron count rate and unfolded energy spectra as measured in an NE213 detector behind the sample. It was necessary to expand the standard TRIPOLI cross section energy structure near the 2.3 MeV minimum in the total cross section of oxygen (a major constituent of concrete) to correctly calculate the count rate near this energy. A drawback of the TRIPOLI code is the lack of an automated method of performing coupled neutron and gamma-ray production calculations.

*Research jointly sponsored by Defense Nuclear Agency and DOE Office of Reactor Research and Technology.

5.10. MORSE: CURRENT STATUS OF THE TWO OAK RIDGE VERSIONS*

M. B. Emmett† J. T. West, III†

(Abstract of ORNL/RSIC-44, pp. 316-312, August, 1980)

There are two versions of the MORSE Monte Carlo radiation transport computer code system at Oak Ridge National Laboratory. MORSE-CG is the most well-known and has undergone extensive use for many years. Development of MORSE-SGC was originally begun in order to restructure the cross section handling and thereby save storage, but the more recent goal has been to incorporate some of the KENO ability to handle multiple arrays in the geometry and to improve on 3-D plotting capabilities. New capabilities recently added to MORSE-CG include a generalized form for a Klein-Nishina estimator, a new version of BREESE, the albedo package, which now allows multiple albedo materials, and a revised DOMINO which handles DOT-IV tapes.

*Research sponsored by Defense Nuclear Agency.

†UCC-ND Computer Sciences Division.

5.11. A REPAIR FOR SCATTERING EXPANSION TRUNCATION ERRORS IN TRANSPORT CALCULATIONS*

M. B. Emmett[†] R. L. Childs[†] W. A. Rhoades

(Reprint of *Trans. Am. Nucl. Soc.* 33, 719, 1979)

Legendre expansion of angular scattering distributions is usually limited to P_3 in practical transport calculations. This truncation often results in nontrivial errors, especially alternating negative and positive lateral scattering peaks. The effect is especially prominent in forward-peaked situations such as the within-group component of the Compton scattering of gammas. Increasing the expansion to P_7 often makes the peaks larger and narrower. Ward demonstrated an accurate repair,¹ but his method requires special cross-section sets and codes. The DOT IV code provides fully compatible, but heuristic, repair of the erroneous scattering. An analytical Klein-Nishina estimator, newly available in the MORSE code, allows a test of this method.

In the MORSE calculation, particle scattering histories are calculated in the usual way, with scoring by an estimator routine at each collision site. Results for both the conventional P_3 estimator and the analytical estimator were obtained.

In the DOT calculation, the source moments are expanded into the directional representation at each iteration. Optionally a sorting procedure removes all negatives, and removes enough small positive values to restore particle conservation. The effect of this is to replace the alternating positive and negative values with positive values of plausible magnitude. The accuracy of those values is examined herein.

In the chosen test problem, 1.25-MeV gammas emerge from a hole in a ground surface and scatter in air. This simple geometry is representative of scattering situations in many shielding problems, as well as air transport problems. The desired result is a high flux within a 7.13-deg source cone, a smaller positive value within the first-scatter cone, 33 deg, and almost zero beyond that, where any single scatter would remove the particle from the energy group.

Figure 5.11.1 shows the radial variation of the flux at a height of 250 cm and indicates that the P_3 MORSE and the unfixed P_3 DOT results for the in-group flux show the expected oscillations, and the magnitudes are not negligible. The analytical MORSE result drops abruptly to near zero outside the first-scatter cone, as it should, and the fixed DOT also drops rapidly. At 1950-cm height (Fig. 5.11.2) there is also good agreement inside the beam. The less-rapid falloff of the fixed DOT outside the beam is more apparent here, although the net effect is a monotonic transition to very small values.

Figure 5.11.3 shows that a large plume of negative fluxes in the unfixed result extends far out into space, and a significant plume of false positives extends along the ground. It was not feasible to test Ward's method because of the requirement for special data and codes.

In examining the total dose from all energy groups, both negative and incorrect positive results were found in the unfixed results. The negative source fixup in DOT removed this erratic behavior without the requirement for special data and codes. While it cannot match the accuracy of the analytical MORSE, the error is an overestimate of the flux near the cutoff boundary, acceptable in many, if not all, calculations. The fixup is found to be of substantial practical value.

* Research sponsored by DOE Office of Nuclear Energy Programs, Division of Reactor Research and Technology.

[†] Computer Sciences Division.

1. J. T. Ward, Jr., "An Improved Multigroup Representation of Differential Compton Scattering Cross Sections," *Trans. Am. Nucl. Soc.* 21, 529 (1975).

5.12. BREESE-II: AUXILIARY ROUTINES FOR IMPLEMENTING THE ALBEDO OPTION IN THE MORSE MONTE CARLO CODE*

V. R. Cain[†] M. B. Emmett[‡]

(Abstract of ORNL/TM-6607, July, 1979)

The routines in the BREESE (Bechtel Reactor Edge Streaming Evaluator) package implement the albedo option in the MORSE Monte Carlo Code by providing (1) replacements for the default routines ALBIN and ALBD0 in the MORSE Code, (2) an estimating routine ALBD0E compatible with the SAMBO package in MORSE, and (3) a separate program that writes a tape of albedo data in the proper format for ALBIN. These extensions of the package initially reported in 1974 were performed jointly by ORNL, Bechtel Power Corporation, and Science Applications, Inc.

The first version of BREESE had a fixed number of outgoing polar angles and the number of outgoing azimuthal angles was a function of the value of the outgoing polar angle only. An examination of differential albedo data led to this modified version which allows the number of outgoing polar angles to be dependent upon the value of the incoming polar angle and the number of outgoing azimuthal angles to be a function of the value of both incoming and outgoing polar angles.

* Research sponsored by Defense Nuclear Agency.

[†] Science Applications, Inc.

[‡] UCC-ND Computer Sciences Division.

5.13. THE ITERATIVE BEHAVIOR OF DIFFUSION THEORY FLUX EIGENVALUE NEUTRONICS PROBLEMS*

D. R. Vondy T. B. Fowler

(Abstract of ORNL/TM-6843, May, 1979)

Information is presented about the iterative behavior of selected reactor neutronics problems applying the finite-difference diffusion theory approximation to neutron transport. Several problems were solved different ways to examine the effects of variations in the iteration procedures on the rate of convergence. Estimates of dominant error vector eigenvalues and their dependence on the inner iteration procedures are shown. This information is important because it serves as a guide for code development and application, lacking a thorough theoretical analysis of the iterative behavior.

* Research sponsored by DOE Office of Reactor Research and Technology.

5.14. INPUT DATA REQUIREMENTS FOR SPECIAL PROCESSORS IN THE COMPUTATION SYSTEM CONTAINING THE VENTURE NEUTRONICS CODE*

D. R. Vondy T. B. Fowler G. W. Cunningham[†]

(Abstract of ORNL-5229/R1, July, 1979)

This report presents user input data requirements for certain special processors in a nuclear reactor computation system. These processors generally read data in formatted form and generate binary interface data files. Some data processing is done to convert from the user-oriented form to the interface file forms. The VENTURE diffusion theory neutronics code and other computation modules in this system use the interface data files which are generated.

* Research sponsored by DOE Office of Reactor Research and Technology.

† UCC-ND Computer Sciences Division.

5.15. EXPOSURE CALCULATION CODE MODULE FOR REACTOR CORE ANALYSIS: BURNER*

D. R. Vondy G. W. Cunningham[†]

(Abstract of ORNL-5180, February, 1979)

This report documents the code module BURNER for nuclear reactor exposure calculations. The computer requirements are shown, as are the reference data and interface data file requirements, and the programmed equations and procedure of calculation are described. The operating history of a reactor is followed over the period between solutions of the space, energy neutronics problem. The end-of-period nuclide concentrations are determined given the necessary information. A steady state, continuous fueling model is treated in addition to the usual fixed fuel model. The control options provide flexibility to select among an unusually wide variety of programmed procedures. The code also provides user option to make a number of auxiliary calculations and print such information as the local gamma source, cumulative exposure, and a fine scale power density distribution in a selected zone. The code is used locally in a system for computation which contains the VENTURE diffusion theory neutronics and other modules.

* Research sponsored by DOE Office of Reactor Research and Technology.

† UCC-ND Computer Sciences Division.

5.16. PREMOR: A POINT REACTOR EXPOSURE MODEL COMPUTER CODE FOR SURVEY ANALYSIS OF POWER PLANT PERFORMANCE*

D. R. Vondy

(Abstract of ORNL-5580, October, 1979)

The PREMOR computer code was written to exploit a simple, two-group point nuclear reactor power plant model for survey analysis. Up to thirteen actinides, fourteen fission products, and one lumped absorber nuclide densities are followed over a reactor history. Successive feed batches are accounted for with provision for from one to twenty batches resident. The effect of exposure of each of the batches to the same neutron flux is determined.

The requirements for a critical system and desired power level are satisfied by a direct iteration procedure that adjusts the actinide feed composition as necessary. Elaborate exits report such results as the neutron absorption distribution, nuclide concentrations, fuel cost and ore requirements, and such integral information as the simple fuel conversion ratio and doubling time, fuel consumption rate, effective neutron production per absorption and reactivity importance of the nuclides, at selected points in the history. Only the essential amount of calculation is done to produce adequate results for parameter studies at a low cost of computation. Iteration may be done to an optimum fuel cost, or succeeding problems solved to vary the neutron loss fraction. Locally a load module is available for application which was generated from the Fortran source program. The code has been used extensively for analysis of the graphite moderated, gas cooled reactor concept. This report documents the equations programmed and discusses application.

* Research sponsored by DOE Office of Advanced Nuclear Systems and Projects.

5.17. DEVELOPMENT AND VERIFICATION OF MULTICYCLE DEPLETION PERTURBATION THEORY*

J. R. White[†] T. J. Burns

(Reprint of Trans. Am. Nucl. Soc. 34, 624, 1960)

Recently, Williams¹ has developed a coupled neutron/nuclide depletion perturbation theory (DPT) applicable to multidimensional and multigroup reactor analysis problems. This theoretical framework has been verified using the newly developed DEPTH² module within the context of the VENTURE modular code system.³ The accuracy and usefulness of this alternative calculational method for burnup analyses has been demonstrated for a variety of final-time response functionals. However, these examples were restricted to single-cycle depletion analyses due to the theoretical assumption that the nuclide density field was continuous in time. Clearly, in multicycle problems, the nuclide concentrations must vary discontinuously with time to model refueling and shuffling operations or discrete control rod movements. Thus, the purpose of this work is to generalize the original DPT framework to include nuclide discontinuities and to verify that this generalization can be employed in realistic multi-cycle applications.

The discontinuity in the nuclide field due to refueling and shuffling operations can be represented as

$$N(r, t_i) = P_{sd}(r, t_i)N(r, t_i^-) + M(r, t_i) \quad (1)$$

where

$N(r, t_i)$ = nuclide density vector following the refueling operation

$N(r, t_i^-)$ = nuclide density vector immediately preceding the refueling operation

$P_{sd}(r, t_i)$ = shuffling/discharge operator at time t_i , and

$M(r, t_i)$ = vector describing the addition of feed material to the reactor at t_i .

With only slight interpretational differences, the above equation also describes nuclide discontinuities other than the refueling process.

Inclusion of the condition expressed by Eq. (1) in the forward burnup equations introduces a discontinuity in the adjoint equations required for DPT. Williams¹ has shown that the discrete power normalization and flux shape discontinuities of the quasi-static burnup approximation introduce the "P* effect" and "r* effect" jump conditions on the adjoint importance function, $N^*(r, t)$. In much the same way, the forward refueling discontinuity manifests itself as an "adjoint refueling" jump condition. These time-step boundary conditions on the adjoint importance function are given by

$$N^*(r, t_i) = N^*(r, t_i^+) + P^*(r, t_i^+)_{\text{effect}} + r^*(r, t_i^+)_{\text{effect}} \quad (2)$$

and

$$N^*(r, t_i^-) = P_{sd}^*(r, t_i)N^*(r, t_i) \quad (3)$$

where P_{sd}^* is the adjoint refueling operator.

Two points regarding Eqs. (2) and (3) deserve discussion. First, it should be noted that the time boundaries are reversed relative to Eq. (1), which is consistent with the time direction for the solution of the adjoint burnup equations. Second, the use of zone-averaged quantities (as in most depletion codes) results in a matrix representation of the P_{sd} operator; describing the zone to zone shuffling and discharge operations. Hence, the adjoint operator, P_{sd}^* , becomes simply the transpose of the P_{sd} . Thus, if zone i is moved

to zone m in the forward calculation, the importance associated with the nuclide in zone m would be shuffled to zone z in the adjoint case. Additionally, if zone m was discharged in the forward computation, the corresponding adjoint operation would be to set the zone m importance functions to zero.

The central theme in the above development is that a fuel management operation in a multicycle forward calculation implies that a corresponding importance management operation be performed in the multicycle adjoint case. Equation (1) describes the forward fuel management operation while Eq. (3) describes its adjoint.

Numerical calculations directed at confirming the validity and usefulness of multicycle DPT have been performed using the DEPTH module. A two-dimensional (R,Z), nine-group calculational model of a GCFR was utilized. One-third of each of the four core zones and associated axial blankets were refueled on an annual basis. In addition, one-sixth of the radial blanket zones were replaced each cycle. The ^{239}Pu inventory at the end of the fourth cycle (EOC4) was selected as a representative response function to examine the capability of the multicycle DPT generalization.

Table 5.17.1 contrasts the predicted EOC4 ^{239}Pu inventory based on multicycle DPT with direct calculation for several perturbations. The nuclide perturbations to the reference system included both isolated changes such as the 10% ^{239}Pu increase to core zone 1 and multiple nuclide variations over the four cycles as in the fission product perturbations (addition of 10^{21} atoms/cm³ to initial and reload batches in CZ1). As indicated by Table 5.17.1, multicycle DPT agrees extremely well with direct forward calculation.

Table 5.17.1. DPT vs Direct Calculation for an EOC4 ^{239}Pu Inventory Response in a 2-D, Nine-Group GCFR Calculational Model

Design Variation	Time of Perturbation	Change in Response (kg)		Diff. (%)
		DPT Result	Direct Result	
Δ FISSP	initial core	56.23		
	1st reload	30.61		
	2nd reload	21.46		
	3rd reload	10.97		
	SUM	119.27	115.98	2.8
Δ ^{239}Pu	initial core	-27.68	-27.21	1.7
Δ ^{239}Pu	1st reload	- 2.35	- 2.43	-3.3

One noteworthy capability of DPT is its ability to account for the "memory" of the reactor. Assemblies initially loaded in the core regions are not physically present during the fourth cycle due to the refueling scheme specified. Yet, the effects of perturbations to the initial core are predicted with remarkable accuracy. For example, the effect of the isolated initial core ^{239}Pu perturbation on the EOC4 ^{239}Pu inventory was predicted to within 1.7%!

The above development and verification of multicycle DPT greatly extends the potential useful application of time-dependent perturbation theory. The effect of various design options on important "equilibrium cycle" responses can now be investigated without several costly multicycle forward burnup calculations. In addition, the ability of DPT to quantify the time-dependent importance of a nuclide through several reactor cycles may prove invaluable in fuel management and core design optimization studies.

*Research sponsored by U.S. DOE Office of Nuclear Energy Programs, Division of Reactor Research and Technology.

† UCC-ND Computer Sciences Division.

1. M. L. Williams, "Development of Depletion Perturbation Theory for Coupled Neutron/Nuclide Fields," Nucl. Sci. Eng. 70, 20 (1979).
2. M. L. Williams, J. R. White, and T. J. Burns, "A Technique for Sensitivity Analysis of Space-and Energy-Dependent Burnup Calculations," Trans. Am. Nucl. Soc. 32, 766 (1979).
3. D. R. Vondy et al., "A Computation System for Nuclear Reactor Core Analysis," ORNL-5158 (1977).

5.18. THE DEVELOPMENT, IMPLEMENTATION, AND VERIFICATION OF MULTICYCLE DEPLETION PERTURBATION THEORY FOR REACTOR BURNUP ANALYSIS*

J. R. White†

(Abstract of ORNL/TM-7305, August, 1980)

A generalized depletion perturbation formulation based on the "quasi-static" method for solving realistic multicycle reactor depletion problems is developed and implemented within the VENTURE/BURNER modular code system. The present development extends the original formulation derived by M. L. Williams to include nuclide discontinuities such as fuel shuffling and discharge. This theory is first described in detail with particular emphasis given to the similarity of the forward and adjoint quasi-static burnup equations. The specific algorithm and computational methods utilized to solve the adjoint problem within the newly developed DEPTH (Depletion Perturbation Theory) module are then briefly discussed. Finally, the main features and computational accuracy of this new method are illustrated through its application to several representative reactor depletion problems.

The examples utilized in the study cover the range from one-group one-dimensional reactor models to more complex multigroup two-dimensional calculational representations. A set of multicycle calculations are also presented as a test of the adjoint formulation for problems involving discontinuous nuclide fields. Final-time nuclide inventories, k_{eff} , and the microscopic ^{238}U capture to ^{239}Pu fission ratio were utilized as representative responses of interest. Perturbations to the reference system included variations in the fissile, fertile, structural and coolant material concentrations within the fast reactor models utilized. Material concentrations were perturbed locally and globally so as to change the distribution as well as magnitudes of the nuclide and neutron fields within the system. The question of nonlinear behavior for certain perturbation/response pairs was also investigated by varying the magnitude of the material perturbations.

The comparison of predicted responses with direct computation for this large calculational data base clearly demonstrates the remarkable predictive capability of the adjoint depletion formulation implemented within the DEPTH module. This new method can accurately account for variations in the time-dependent neutron and nuclide fields arising from variations in the time-step initial conditions. Thus, multicycle depletion perturbation theory represents an attractive alternate computational method for certain types of burnup analyses, with the greatest cost benefits being associated with repetitive-type scoping calculations.

*Research sponsored by DOE Office of Reactor Research and Technology.

† UCC-ND Computer Sciences Division.

5.19. THERMAL REACTOR BENCHMARK CALCULATIONS USING RESONANCE PROFILES*

J. Barhen W. Rothenstein[†]

[Abstract of paper presented at Symposium on Nuclear Data Problems for Thermal Reactor Applications, Brookhaven National Laboratory, May 22-24, 1978; proceedings published as BNL-NC-25047 (ENDF-270)]

Thermal lattice benchmark calculations using ENDF/B-IV data were made by means of a modified version of the HAMMER code which uses detailed resonance profile tabulations in the resolved resonance region. A number of different procedures were used to calculate the resonance reaction rates. These included the standard Nordheim Integral Treatment (NIT), a similar treatment using resonance profiles (NITPRO), as well as a RABBLE multi-region treatment with profiles (RABPRO) included directly in the HAMMER code. A more sophisticated procedure (OZMA-1) allowing for the computation of the anisotropic angular flux in the multiregion unit cell was developed separately. The resonance reaction rates produced by the OZMA-1 code were introduced into HAMMER for the subsequent lattice analysis.

The different methods are compared and results are given for the TRX-1 and TRX-2 lattices, as well as for the MIT benchmarks. The new procedures give results which are quite close to previous Monte-Carlo calculations. They are also in reasonable agreement with the latest experiments, within the limitations of the current ENDF/B specifications for the ^{238}U resonance cross sections. The recent multilevel formalisms developed by G. de Saussure will probably suffice to close the remaining gap between calculations and experiment.

* Work sponsored by Electric Power Research Institute.

[†] Technion, Israel Institute of Technology, Haifa.

5.20. OZMA - A CODE TO CALCULATE RESONANCE REACTION RATES IN REACTOR LATTICES USING RESONANCE PROFILE TABULATIONS*

J. Barhen W. Rothenstein[†]

(Abstract of EPRI-709-2, in press)

In thermal reactor lattice analysis the resonance shielding problem is usually handled on the basis of quite drastic approximations. These may include individual resonance treatments, line shape functions for Doppler broadening, the assumption of complete flux recovery between resonances, and a very rough description of the lattice geometry, such as two regions only. In addition very simple formulae (such as rational approximations) are frequently used for the fuel collision and escape probabilities, which are an essential part of the resonance absorption calculation.

The other extreme in resonance absorption calculations is the Monte Carlo method, which is the most obvious tool for eliminating simplifying assumptions. Accurately pre-processed cross sections can then be used together with a precise description of the lattice geometry. Good overall statistical accuracy can be attained in reasonable computer times, but the accuracy becomes progressively worse if more detailed information is required in certain energy groups, specified resonances or geometrical subregions. Second-order effects such as temperature changes of resonance reaction rates are particularly difficult to estimate with Monte Carlo techniques.

The OZMA code implements a new methodology for solving the neutron transport equation at many discrete energies in the resolved resonance region using accurately preprocessed Doppler broadened cross section tables. The procedure eliminates simultaneously most of the approximations involved in simple treatments of resonance shielding, and the statistical problems inevitable in Monte Carlo calculations. A special example in this connection is the treatment of the Doppler effect as a function of fuel burn-up which is described in a separate report and makes use of both the OZMA and the HAMMER codes.

The present report describes the resonance absorption calculations which are performed in the OZMA code and the manner in which the results can be utilized in the HAMMER program (EPRI NP-565, 1978). The results of the OZMA code by themselves are useful in the validation of simpler techniques frequently applied for the calculation of effective resonance integrals.

*Research sponsored by Electric Power Research Institute.

†Technion, Israel Institute of Technology, Haifa.

5.21. SPQR: A MONTE CARLO REACTOR KINETICS CODE*

S. N. Cramer H. L. Dodds†

(Abstract of ORNL/TM-7086, February, 1980)

The SPQR Monte Carlo code has been developed to analyze fast reactor core accident problems where conventional methods are considered inadequate. The code is based on the adiabatic approximation of the quasi-static method. This initial version contains no automatic material motion or feedback. An existing Monte Carlo code is used to calculate the shape functions and the integral quantities needed in the kinetics module. Several sample problems have been devised and analyzed. Due to the large statistical uncertainty associated with the calculation of reactivity in accident simulations, the results, especially at later times, differ greatly from deterministic methods. It was also found that in large uncoupled systems, the Monte Carlo method has difficulty in handling asymmetric perturbations.

*Research sponsored by DOE Office of Reactor Research and Technology.

†Department of Nuclear Engineering, University of Tennessee.

5.22. THERMAL-HYDRAULIC/HEAT TRANSFER CODE DEVELOPMENT FOR SPHERE-PAC-FUELED LMFBR*

D. G. Morris†

(Abstract of ORNL/TM-7100, June, 1980)

Sphere-pac fuel has received much attention recently in light of the development of proliferation-resistant fuel cycles for the Fast Breeder Reactor Program in the United States. However, for sphere-pac fuel to be a viable alternative to conventional pellet fuel, a means to analyze the thermal behavior of sphere-pac-fueled pin bundles is needed. To meet this need, a thermal-hydraulic/heat transfer computer code has been developed for sphere-pac-fueled fast breeder reactors. The code, COBRA-3SP, is a modified version of COBRA-3M incorporating a three-region sphere-pac fuel pin model which permits fuel restructuring. With COBRA-3SP, steady-state and transient analysis of sphere-pac-fueled pin bundles is possible. The validity of the sphere-pac fuel pin model has been verified using experimental results of irradiated sphere-pac fuel.

*Research sponsored by DOE Office of Reactor Research and Technology.

†Engineering Technology Division.

5.23. EVALUATION AND MODIFICATION OF THE PROBABILITY TABLE METHOD FOR BUBBLE REACTIVITY WORTH CALCULATIONS*

T. J. Hoffman[†] E. U. Vaughan[‡]

(Abstract of paper to be published in Nuclear Science and Engineering)

The probability table representation of neutron transport in bubbly media, developed by Hoffman and Petrie for neutron flights initiated by collision, is extended to neutron flights initiated at interfaces. Both forms are compared with appropriate Monte Carlo estimates of one-flight transmission through bubbly slabs, with encouraging results for slabs thicker than the bubble diameter. These forms are then combined into a modified probability table method. Application of the modified method to transport calculations requires high spatial and angular resolution but shows that the interface modification can have a substantial effect on calculated bubble worths. Fortunately, the results agree well with the simple Benoist method which does not require high resolution.

*Research sponsored by DOE Office of Reactor Research and Technology.

[†]UCC-ND Computer Sciences Division.

[‡]Energy Systems Group, Rockwell International, Conoga Park, California.

5.24. USER'S GUIDE FOR THE REVISED SPEC-4 NEUTRON SPECTRUM UNFOLDING CODE*

J. O. Johnson[†] D. T. Ingersoll

(Abstract of ORNL/TM-7384, August, 1980)

The SPEC-4 computer code was developed in the United Kingdom to solve the spectrum unfolding problem for spherical gas-filled proton-recoil neutron spectrometers. This report describes the ORNL version of SPEC-4 which has been applied to the analysis of data from the Tower Shielding Facility. Recent modifications are described which largely pertain to the graphical output routines. In addition, the input requirements are presented in considerable detail including suggestions and recommendations based on actual operating experience. Finally, auxiliary programs are discussed which can aid the SPEC-4 user.

*Research sponsored by DOE Office of Reactor Research and Technology.

[†]University of Tennessee, Knoxville, Tennessee.

5.25. ON VALIDATING MAJOR COMPUTER CODES*

D. R. Vondy

(Reprint of Trans. Am. Nucl. Soc. 35, 255-256, 1980)

A major computer code may be used reliably only after experience has been gained with its application. Many computer codes cannot be *qualified* for use as they exist in the sense of associating a high level of *quality assurance* with the results they produce, even in rather limited application. Why is *qualification* often possible only after revisions are made in the programmed instructions?

A primary reason is the lack of understanding of the requirements by developers. A cause is the difficulty of doing thorough *validation*: it takes considerable effort and has a high associated cost that may not be adequately covered in a development project. Returns diminish with continuing investment in effort, so termination is often too early.

The tester becomes bored and expects no reward for further effort. The priority for such effort, assigned by the developer or the manager, may be too low relative to that for other effort needed to satisfy demands of active projects. Continuing extension is usual for a useful code, so testing is impacted. Changes cause devalidation that results in dequalification, and this is much more serious than is often realized.

What about the application-oriented code developer who produces an answer close to a measured experimental result? This is indeed a form of validation in some sense qualifying the implemented calculational procedure, which is important but quite inadequate. Results of great interest to a developer may be of but minor interest and importance in project application along with special methods of solution, prompting a change in emphasis. The mathematicians quite properly point out that only mathematical problems are being solved, and since these usually have unique solutions, mathematical verification is all that is needed for validation. Proving that coded algorithms return numerically correct results is an important step. However, when the calculational procedures contain involved logic choices, and there are many possible combinations of alternatives and side effects, so to speak, proofing is not easy. Individual codes interact with data interfacing and decision making at many points along the calculational path based on intermediate results. Accurate answers are not known to complicated problems, so we turn to benchmarking techniques.¹ With increasing sophistication comes elaborate user control and associated instructions for use that need to be precise and understandable, usually in some physical sense rather than mathematical. Documentation of requirements is involved,² and thorough descriptions of current procedures generally do not exist. Programming style is involved to some extent.^{3,4} Errors elude detection in proof testing — a goof on one source deck card out of perhaps 40,000 or more will produce erroneous results, perhaps only occasionally and not when test problems are solved.

Consider that a code is to be used routinely on a production basis to support decision making by individuals not very familiar with (nor interested in) the detailed solution schemes, and having no contact with the developers. Certainly the user expects a reliable solution to be generated for the problem he thinks he presented. This cannot happen with some codes and will not be the case with some others! What fraction of the results produced by computers solving major problems is reliable? Can it be very high?

Somehow the validation difficulties are simply to be surmounted, not considered worthy of discussion like other aspects of development and application. The challenge is serious even though some minds find it to be of no scientific interest. Are developers properly motivated? Properly rewarded? Should there be discrediting and penalties, or is the field too unstable or lacking in maturity?

Hear this, developers:

A problem was treated. Are the produced results reliable? How is a user to know? How can he determine if the problem solved was the one he intended? What problem was solved? Can he tell? Did the problem lie within the area where a reliable solution is expected? There is little need for your code if it cannot easily be qualified for application by others.

How can we help developers? Red tape and paper work can be counter-productive. Developers need justification for proofing effort and a reasonable distribution of priorities within a development project. They need application testing assistance and feedback of information from use, interaction with users supporting an active project involving code application. They need answers to such questions as:

What are the requirements to support qualification?

How can these best be satisfied?

What is known from experience regarding the importance of various aspects such as structuring and logic constructs, the impact on programming methods, proofing code changes, levels of quality assurance, impacts of software and hardware changes, etc.?

What is a reasonable fraction of the development cost to invest in proofing?

How should the nature of the code(s) affect the proofing process?

To what extent is independent testing and disinterested (second-party) review essential in a specific situation?

What are the primary responsibilities of the developers when development is done in more than one step with more than one party?

A formal document describing validation of codes may indeed be useful, perhaps more so to the administrators or managers than to the developers. Certainly a simple set of reasonable instructions is needed for contractual agreements on methods (software) development that promotes improved products and admits judging conformance. Likely advice would be more useful and important than anything suggesting regulations. But advice is useless unless heeded and will be ignored unless the reasons are understood. So how is the developer's attention to be attracted? How can those individuals involved in support of development become more knowledgeable?

Improved code validation must come about by responsible action of the developers calling on the information available to them. They need to know more about the subject. We seek ways to draw on the expertise that was evolved. In a rapidly expanding technical field such as software development, skills evolve primarily from self-education on the job rather than via formal training. There must be concern about educating these technical people; surely the old ones, but especially the new ones. If a task group were developing a code under your direction, what would you tell them?

* Research sponsored by DOE Office of Reactor Research and Technology.

1. "Benchmark Problem Book," (ANS M&C Division effort), Argonne Code Center, ANL Report ANL-7416/S2 (Rev., June 1977).
2. ANSI M413-1974 Standard, "Guidelines for the Documentation of Digital Computer Programs."
3. ANS-Std 3-1971 Standard, "Recommended Programming Practices to Facilitate the Interchange of Digital Computer Program."
4. ANSI/ANS-10.5-1979, "Guidelines for Considering User Needs in Computer Program Development."

5.26. THE CURRENT STATUS OF METHODS FOR SHIELDING ANALYSIS*

W. W. Engle, Jr.

(Abstract of paper presented at ANS Topical Meeting on 1980 Advances in Reactor Physics and Shielding, Sun Valley, Idaho, September 14-17, 1980)

Current methods used in shielding analysis and recent improvements in those methods are discussed. The status of methods development is discussed based on needs cited at the 1977 International Conference on Reactor Shielding. Additional areas where methods development is needed are discussed.

* Research sponsored by DOE Office of Reactor Research and Technology.

5.27. COMPUTER TECHNIQUES IN SHIELDING AND DOSIMETRY (LECTURES)*

(Notes on lectures presented at meeting held at Ettore Majorana Center, Erice, Sicily, Italy, October 25 - November 3, 1978; full lectures published in Computer Techniques in Radiation Transport and Dosimetry, Plenum Press, 1980)

Lecture 3: The Methods and Applications of Discrete Ordinates in Low Energy Neutron-Photon Transport (ANISN, DOT). Part I, Methods (W. W. Engle, Jr.)

The discrete ordinates method of solution of the Boltzmann transport equation as applied in the neutron and gamma-ray transport codes ANISN and DOT is presented and discussed.

Lecture 4: The Methods and Applications of Monte Carlo in Low Energy (≤ 20 MeV) Neutron-Photon Transport (MORSE). Part I, Methods (T. A. Gabriel)

The Monte Carlo method of solution of the Boltzmann transport equation as applied in the neutron and gamma-ray transport code MORSE is presented and discussed.

Lecture 5: The Methods and Applications of Discrete Ordinates in Low Energy Neutron-Photon Transport (ANISN, DOT). Part II, Applications (W. W. Engle, Jr.)

The applications discussed in this lecture have been published previously. The following references contain complete descriptions of these and other applications of the discrete ordinates method in low energy neutron and photon transport: L. S. Abbott and F. R. Mynatt, ORNL-5027 (July 1975); W. W. Engle, Jr. and M. B. Emmett, ORNL-5166 (June 1976); W. W. Engle, Jr., et al., ORNL/TM-5338 (March 1976); plus papers in Proceedings of the Fifth International Conference on Reactor Shielding (April 1977) (by W. W. Engle, Jr., F. R. Mynatt, and M. L. Williams; by D. E. Bartine, C. O. Slater, and L. R. Williams; by R. E. Maerker and F. J. Muckenthaler; and by C. O. Slater and M. B. Emmett).

Lecture 6: The Methods and Applications of Monte Carlo in Low Energy (≤ 20 MeV) Neutron-Photon Transport (MORSE). Part II, Applications (T. A. Gabriel)

The Monte Carlo method of solution of the Boltzmann transport equation as applied in the neutron and gamma-ray transport code MORSE is presented and discussed.

Lecture 8: Cross Section Processing Codes and Data Bases (AMPX). (W. W. Engle, Jr.)

The AMPX system, a collection of computer programs in a modular arrangement in continuing development at the Oak Ridge National Laboratory, is presented and discussed.

Lecture 9: Radiation Shielding Information Center and Biomedical Computing Technology Information Center (T. A. Gabriel)

The goals and scopes of the Radiation Shielding Information Center (RSIC) and the Biomedical Computing Technology Information Center (BCTIC) are presented and discussed.

*Research sponsored by DOE Office of Reactor Research and Technology.

5.28. NEUTRONIC CALCULATIONAL METHODS (MEETING PRESENTATIONS)*

(Notes on papers presented at DOE/CEA-BMPT Specialist Meeting on Neutronic Calculational Methods, Karlsruhe, FRG, November 22-23, 1979)

Solving the Nuclear Reactor Core Problems (D. R. Vondy)

Reactor core analysis methods were addressed. The three-dimensional neutron flux problem presents a challenge. Although the discrete ordinates approach shows only limited

potential, the Monte Carlo method now has application when limited results are desired. The workhorse method of representing neutron transport within a reactor core remains diffusion theory in spite of its limitations, and current interest lies in techniques that reduce computation costs and/or improve modeling. Reliable capability for solving the more global problems, such as those considering the variable time, evolves slowly with appreciable investment of development effort.

The Utility and Capability of DOT IV (M. A. Rhoades)

This slide presentation covered the general philosophy and capabilities of DOT IV. Many relatively new features and testing results were illustrated, and existing problems and aspirations for future improvements were discussed.

* Research sponsored by DOE Office of Reactor Research and Technology.

6.0. INTRODUCTION

The analyses performed by the Division for specific systems or applications continue to reflect the diversified interests of the sponsoring agencies. The majority of the effort was directed toward the Liquid Metal Fast Breeder Reactor, the Gas Cooled Reactor, and the Magnetic Fusion Energy programs. Significant levels of effort were also directed toward high-energy physics calculations, primarily for charged particles, and for light water reactor investigations, including analysis of specific aspects of the Three Mile Island accident and the investigation of a dual-purpose power and water level gamma thermometer. Other areas of investigation included the molten salt reactor, non-destructive fuel assay, and weapons radiation transport calculations for the Defense Nuclear Agency.

Liquid-Metal Fast Breeder Reactor Program

In the Clinch River Breeder Reactor (CRBR) supporting analysis, evaluation continues of the performance of the Source Range Flux Monitor (SRFM) during shutdown operation. This effort was divided into two categories, initial loading and re-load. An initial fuel loading plan was devised and tested by carrying out experiment ZPPR-11A at Argonne National Laboratory. A method for constructing inverse count rate curves using a single control rod withdrawal technique was developed for Westinghouse-Advanced Reactor Division. Analysis of a proposed reloading scheme indicated difficulties in SRFM interpretation, leading to a revised reloading scheme which was proposed to the CRBR project office. Uncertainties in the interpretation of the SRFM data were also analyzed and reduced where possible.

As part of the Proliferation Resistant Preconceptual Core Design Study, two sphere-pac fueled cases were designed and compared with similar pellet fueled cores. The study results indicated little effect on performance due to sphere pac fuels, and generally indicated very little effect on breeding in a heterogeneous core due to lower fuel smear density compared with results for previous studies of homogeneous cores.

In the shielding area, work continues on items related to the startup phase for the Fast Flux Test Facility (FFTF), including planning for neutron and gamma measurements to be made in the head compartment. Clinch River Breeder Reactor design verification calculations are geared toward obtaining uncertainty estimates for shield designs. Supporting analysis for the Conceptual Design Study included initial calculations for both loop and pool designs, with follow-up analysis for a loop concept.

Gas-Cooled Reactor Programs

A large effort was devoted to the investigation of the Gas Cooled Fast Reactor (GCFR) conceptual shielding design. A complete analysis was performed for the upflow design, and a special investigation was directed toward radiation streaming through the flow-through shields designed for use in the upper and lower axial plenums. In a cooperative program, analysis was performed for Swiss experimental measurements taken in simulated GCFR core configurations containing thorium. Studies were made of alternate GCFR concepts, including heterogeneous core configurations and the use of thorium based fuels. A Fast Mixed Spectrum Reactor (FMSR) concept, helium cooled, was also the subject of a neutronic analysis and a study of very high burnup fission product effects.

Work continued on the Pebble Bed High Temperature Reactor, which is being developed in the Federal Republic of Germany. A joint report on pebble bed reactor performance and fuel cycle economics was issued cooperatively with the Kernforschungsanlage (KFA) laboratory at Jülich. A major assessment was performed to compare postulated costs and benefits of prismatic and pebble bed type cores for high-temperature gas cooled reactors.

Light-Water Reactor Programs

As part of the immediate effort at ORNL related to the Three Mile Island accident, radiation damage effects to the pressurizer water level monitors were investigated, and

doses were estimated for postulated storage facilities for contaminated water from the sump area. In the follow-on effort, an analysis was made of the count rates measured during and after the accident by the shutdown monitor. This investigation resulted in an events sequence chart which was compared with an independent sequence generated from thermal hydraulic analysis of the accident.

An investigation was launched into the interpretability of the gamma thermometer for a power level monitor in Pressurized Water Reactors (PWRs), including the questions of fission product gamma background and local power vs area power measurements. In the course of this investigation the need for a water level monitor was indicated as the result of the Three Mile Island accident investigation, and an adapted design for the gamma thermometer which monitors both power and liquid level was developed. Other investigations included gamma-ray skyshine from spent-fuel storage facilities, analysis of a waste repository facility.

Magnetic Fusion Energy Program

The Division's Magnetic Fusion Energy Program is divided into three areas: integral experiments, neutronics calculations in support of radiation damage studies and the design of fusion energy devices, and molecular flow calculations to aid in the design of neutral beam injectors. The integral experiments, reported in Section 4, are designed to provide data against which ORNL and all other organizations involved in shielding calculations for fusion devices can test their methods and interaction data. The principle problems are the prediction of neutron streaming through the huge ducts that are designed into fusion reactor blankets and shields for neutral particle injection, for vacuum pumps, diagnostics, etc. and the integral experiments are designed to address these problems.

The radiation damage calculations are carried out to aid in the design of experiments. The ORNL Metals and Ceramics Division is attempting to develop experiments that can be performed at fission reactors to yield damage data for metals that will be exposed in fusion reactors, and the calculations are done to support these experiments.

A variety of neutronics calculations have been performed for various proposed fusion devices. The most extensive series of calculations are for the TFTR (Tokamak Fusion Test Reactor) but during the past year calculations related to the Experimental Test Facility (ETF) and the EBTR (Elmo Bumpy Torus Reactor) have also been performed.

The effectiveness of the cryopanel in maintaining the vacuum in neutral beam injectors is an essential feature of the injector design. In the past year it has been shown that reliable molecular flow calculations can be carried out, using an adaptation of the Monte Carlo code MORSE, and a variety of injector design calculations have been performed.

High Energy Physics Program

The Division's calculations of the transport of high-energy particles continue to be done on request from groups outside of ORNL. With the methods and interaction data that have been developed and the experience that has been gained, calculations are routinely performed at ORNL that were not possible a few years ago. During this reporting period several calculations have been carried out to determine the shielding requirements for the 400-GeV proton storage rings (ISABELLE) at the Brookhaven National Laboratory. In particular, a series of skyshine calculations to determine the required roof thickness over the ISABELLE experimental areas were performed. These calculations, while intended primarily for ISABELLE, were carried out in a manner that provides generic data that can be used to estimate skyshine effects at many high-energy accelerators and fusion reactors.

As part of the program during the past year a model of high-energy fusion has been incorporated into the ORNL high-energy transport code, HETC, and the validity of the model has been demonstrated by comparing calculated results with experimental data. The use of fissionable targets in pulsed neutron sources is being studied at several institutions, both in the U.S. and Europe, and this revised code is now available for use in these studies.

Our other work in the high-energy program continues to be directed at aiding in the design of instrumentation (ionization calorimeters) to measure the energy of various high-energy particles. The calorimeters that have been built and tested at accelerators have all been found to be satisfactory, which has encouraged the development of more sophisticated (and more complicated) devices, each design being for a different purpose. The agreement of our calculations with the experimental tests is especially gratifying since the instruments are very large and expensive, and "testing" design variations with a series of calculations rather than with numerous mockups is much more economical.

LIQUID-METAL FAST BREEDER REACTOR PROGRAM**6.1. NEUTRONIC ANALYSIS OF LMFBRs DURING SEVERE CORE DISRUPTIVE ACCIDENTS***E. T. Tomlinson[†]*(Abstract of ORNL/CRD-35, January, 1979)*

A number of numerical experiments were performed to assess the validity of diffusion theory and various perturbation methods for calculating the reactivity state of a severely disrupted liquid metal cooled fast breeder reactor (LMFBR). The disrupted configurations correspond, in general, to phases through which an LMFBR core could pass during a core disruptive accident (CDA). Two reactor models were chosen for this study, the two-zone homogeneous Clinch River Breeder Reactor and the Large Heterogeneous Reactor Design Study Core. The various phases were chosen to approximate the CDA results predicted by the safety analysis code SAS3D. The calculational methods investigated in this study include the eigenvalue difference technique based on both discrete ordinate transport theory and diffusion theory, first-order perturbation theory, exact perturbation theory, and a new hybrid perturbation theory. Selected cases were analyzed using Monte Carlo methods. It was found that in all cases, diffusion theory and perturbation theory yielded results for the change in reactivity that significantly disagreed with both the discrete ordinate and Monte Carlo results. These differences were, in most cases, in a nonconservative direction.

* Research sponsored by DOE Office of Reactor Research and Technology.

[†]UCC-ND Computer Sciences Division.

6.2. ANALYSIS OF THE CLINCH RIVER BREEDER REACTOR (CRBR) SOURCE RANGE FLUX MONITOR (SRFM) COUNT RATE HISTORY DURING REFUELING OF THE FIRST FOUR CYCLES*

D. L. Selby H. E. Knee

(Abstract of ORNL-5557, September, 1979)

An annual shutdown for refueling is scheduled for all operating cycles of the Clinch River Breeder Reactor (CRBR). Operating procedures require that during refueling the Source Range Flux Monitor (SRFM) provide a warning to the operator to assure that the reactor does not approach criticality any closer than that level from which criticality could be attained by a single refueling error, with adequate margin for the associated uncertainties. The present procedure requires the use of a changing count rate alarm set point. This alarm set point would represent the subcriticality level corresponding to the worst single refueling error plus appropriate uncertainties.

This report is a summary of the work performed at ORNL to determine and analyze the count rate history during each step to refueling through the first four cycles. In addition, relative alarm point values were determined and an effort was made to estimate the amount of conservatism associated with the method used to monitor refueling.

It was found that during a typical refueling the source strength and count rate dropped by factors of 31 and 17 respectively while the subcriticality went from -27.9(\$ to -18.0(\$). An examination of the count rates and the alarm set points calculated showed that the alarm set point was never exceeded and was only approached in the last two steps of the refueling.

* Research sponsored by DOE Office of Reactor Research and Technology.

6.3. UNCERTAINTIES ASSOCIATED WITH MONITORING THE SHUTDOWN OPERATIONS IN THE CLINCH RIVER BREEDER REACTOR HETEROGENEOUS CORE USING THE SOURCE RANGE FLUX MONITOR*

D. L. Selby H. E. Knee

(Abstract of ORNL-5608, October, 1980)

The Source Range Flux Monitor (SRFM) is designed to follow the reactor's low-power neutron flux to assure that the reactor does not approach critical any closer than the worst single refueling error during any subcritical operation other than an intentional approach to critical. The method used to achieve this objective must relate the SRFM detector count rate and the system reactivity level. This can be done by using the Source Multiplication Equation and applying uncertainty analysis. An analysis for the reference homogeneous core was performed to determine and evaluate the uncertainties in the monitoring method.

After the uncertainty analysis was performed, the reference core was changed to the heterogeneous configuration. There was sufficient concern about the effect of this change on the value of the uncertainties to necessitate reanalysis. This report is a summary of the analytical work performed to assess these uncertainties.

This study demonstrated that the core change resulted in very little change in uncertainties. The only major effect of the change to a heterogeneous core appears to be the increased decoupling of the core's central region for the SRFM detector.

*Research sponsored by DOE Office of Reactor Research and Technology.

6.4. A REVIEW OF METHODS FOR TREATMENT OF SOURCE EFFECTS IN THE MODIFIED SOURCE MULTIPLICATION METHOD FOR MONITORING THE REACTIVITY IN REFUELING THE CRBR*

J. T. Mihalcz[†]

(Abstract of ORNL-5568, September, 1979)

There are three methods by which source effects can be treated in the interpretation of modified source multiplication measurements in refueling a liquid-metal fast breeder reactor: (1) measurement of and correction for axial and radial source intensity distributions; (2) use of an additional source to override burnt-in source effects so they can be neglected; and (3) calculations. The implementation of these methods and their adequacy for the Clinch River Breeder Reactor (CRBR) are discussed. Of the three methods, the use of an additional source is the only method where an increase or decrease in the count rate definitely means a corresponding increase or decrease in reactivity.

*Research sponsored by DOE Office of Reactor Research and Technology.

[†]Instrumentation and Controls Division.

6.5. ORNL BREEDER REACTOR SAFETY - LOA 2, 3, 4, AND 5
QUARTERLY TECHNICAL PROGRESS REPORT
FOR APRIL-JUNE 1979*

M. H. Fontana[†]

(Excerpts from summary of ORNL/TM-7147, February, 1980)

Task 02 - ORNL LOA 3 Tasks: Analytical Models for Energetics Accommodation (G. F. Flanagan, E. T. Tomlinson,[‡] C. V. Parks,[‡] E. H. Obrow, and P. J. Maudlin[†])

The final copy of the paper to be presented in August at the International Meeting on Fast Reactor Safety has been completed. Version II of MELTADJ (solution of coupled thermal/kinetics adjoint equations) is near completion, and work has begun on an SCG code.

Task 06 - ORNL LOA Support and Integration: Breeder Reactor Reliability Data Analysis Center (G. F. Flanagan, T. F. Bott, M. H. Greene,[‡] P. H. Haas, S. D. Hudson, H. E. Klee, J. J. Manning, and M. A. Woodside[†])

A draft of the LADJ Data Reporting Form Input Guide was completed and distributed for review. The initial meeting of the CREDO Steering Committee was held, and several working groups were formed. Arrangements for onsite data collection at EBR-II and FFTF were completed. Collection of EBR-II engineering, event, and operating data continued. Progress on the DBMS and Statistical package continued.

Task 07 - ORNL LOA Support and Integration: Central Data Base for Breeder Reactor Safety Codes (G. F. Flanagan, J. W. Arnold,[‡] V. M. Forsberg,[‡] M. H. Greene,[‡] G. L. Johnson,[‡] and G. B. Raiford[†])

The SACCG meeting was held at ORNL on May 16 and 17. A large part of the work this quarter centered around this meeting. "Data use" survey information, uncertainty data in SACRD, post-Version I data in the data base, and a list of properties unavailable in SACRD were prepared for the meeting. Following the meeting, work commenced in several areas related to suggested action items. In addition to this work, the necessary routines were initiated for storing uncertainty data, much work was done on radiological data, and work continued on the QA report. Along with the above, work continued on entering, verifying, and modifying data in the SACRD data base.

* Research sponsored by DOE Office of Reactor Research and Technology.

[†] Engineering Technology Division.

[‡] UCC-ND Computer Sciences Division.

6.6. PRECONCEPTUAL STUDY OF PROLIFERATION-RESISTANT HETEROGENEOUS
SPHERE-PAC-FUELED LMFBR CORES*

D. L. Selby

(Abstract of ORNL/TM-699[†], September, 1979)

In October 1977, a multi-institutional Proliferation-Resistant Preconceptual Core Design Study (PRPCDS) was initiated which extended to September 1978. The objective of the study was to establish the proliferation resistance and performance potential of a wide range of sodium-cooled fast breeder reactor core designs. Each participating organization was responsible for publishing the results from its part of the study, and this report describes ORNL's work on the Vibro-Pac fuel design concept. Special characteristics of Vibro-Pac fuel (low density, etc.) were considered in terms of effects on Doppler coefficient, fuel time constant, breeding performance, etc. in a heterogeneous

core configuration. A comparison was made with a reference pellet pin design. No significant differences between Vibro-Pac and high density pellet pins were identified.

* Research sponsored by DOE Office of Reactor Research and Technology.

6.7. THE ANALYSIS OF THE ZPR-9 REVERSE APPROACH TO CRITICAL (RAC) LOW LEVEL FLUX MONITOR EXPERIMENT*

D. L. Selby G. F. Flanagan P. B. Fox[†] D. B. Simpson

(Abstract of ORNL-5181, July, 1979)

An experiment was performed in the ZPR-9 facility at Argonne National Laboratory to determine the adequacy of the ex-core Low Level Flux Monitors (LLFMs) for monitoring the initial approach to critical in the Fast Flux Test Facility (FFTF). While the purpose of the LLFMs (which are located in the radial shield) is to monitor refueling operations, if they prove to be adequate for monitoring the initial loading operation they would be more convenient and less expensive than in-core detectors. No in-core detectors are needed for normal operation of the reactor, and adding them for the initial core loading would require expensive design changes for the addition of specially cooled thimbles.

From the analysis performed it was determined that the detectors were located so close to the core that spatial effects in the core became a dominant factor. The detector response was influenced more by localized events than by events occurring over the core as a whole. This made interpretation very difficult, if not impossible.

* Research sponsored by DOE Office of Reactor Research and Technology.

[†]UCC-ND Computer Sciences Division.

6.8. THEORETICAL EVALUATION OF EX-VESSEL MONITORING FOR INITIAL FUEL LOADING OF A LIQUID-METAL FAST BREEDER REACTOR*

J. T. Mihalcz[†] D. L. Selby H. E. Knee

(Reprint of Trans. Am. Nucl. Soc. 32, 787-789, 1979; also to be published as ORNL-5677)

Transport theory calculations were used to assess the feasibility of monitoring the fuel loading to initial criticality of the Clinch River Breeder Reactor (CRBR) with a detector in a cavity outside the reactor vessel. Such monitoring of the CRBR with an ex-vessel detector will be different from monitoring of previous LMFBRs^{1,2} where in-vessel detectors were used. The feasibility of ex-vessel monitoring depends mainly on two criteria: (a) sensitivity - will counting statistics be adequate, and (b) interpretability - will the count rate be interpreted to obtain the neutron multiplication or reactivity? Satisfying these criteria will assure that the reactor can be loaded safely to initial criticality.

The sensitivity criterion can be satisfied by inserting an additional neutron source (much more intense than the inherent neutron source of the fuel subassemblies) into the core center and using ex-vessel detectors with high sensitivity, such as multiple BF₃ counters mounted in a graphite moderator block. These calculations also determined the intensity of the additional source required to produce adequate counting rates at the ex-vessel detectors.

The interpretability of the ex-vessel detector count rates as the initial fuel loading sequence proceeds was assessed by comparing the calculated inverse count rate

curves for the additional source present with those calculated without the additional source and a detector located in the center of the core.

The proposed initial fuel loading sequence is as follows: first, a neutron source will be inserted in the central subassembly of the core, which has been loaded with dummy subassemblies (no fuel pins) for hydraulic flow testing. Next, all control rods and the core and radial blanket subassemblies will be inserted. The fuel assemblies will be loaded from the core center to the outside rows, with an effort to equalize the reactivity change associated with fuel subassembly insertion in the latter part of the loading. This equalization will be accomplished by loading the outer rows symmetrically.

The ENDF/B-IV cross sections³ were processed with a modified version of the AMPX system³ to produce the 45-group cross-section set required to accurately predict the neutron penetration through sodium and steel. Three-dimensional (3-D) calculations using the KENO-IV Monte Carlo code⁴ determined energy- and region-dependent (one row of fuel or blanket per region) axial leakages, which were then used in 2-D S_N calculations to correct for axial leakage effects.

Because of the complexity, calculations for ex-vessel detector response were done in two steps. First, the discrete ordinates code DOT-IV (Ref. 5) with an r,θ mockup of the central region through the fixed radial shield (60-deg sector, which includes core, radial blanket, and shield) was used to obtain an angular-dependent boundary source. Then, the ^{108}B reaction-rate cross section was used as a source in an r,θ DOT-IV adjoint-source calculation to determine the importance to detector response of neutrons from the boundary source. The angular-dependent boundary source was combined with the angular and spatially dependent importance from the adjoint calculation to obtain the detector response.

Figure 6.8.1 shows (a) the inverse count rate for a fission chamber at the core center resulting from the neutron multiplication of the inherent source of neutrons from the fuel subassemblies, and (b) the inverse count rate for an ex-vessel detector resulting from the neutron multiplication of the additional neutron source (2×10^{10} n/s) at the core center. These inverse count rates are plotted as a function of the number of fuel subassemblies inserted (with the secondary and the row 4 primary control rods withdrawn). In addition to the dependence of the inverse count rate on neutron multiplication, the shape of the inverse count rate curve for the centrally located fission chamber depends on the effects of both the inherent source and the fuel being added around the detector. The shape of the ex-vessel detector curve is affected by the increase in the scattering materials between the additional neutron source and the ex-vessel detectors as fuel subassemblies are inserted. These calculations show that both types of monitoring of the initial loading provide meaningful extrapolations to the same delayed criticality condition. The reaction rates in an ex-vessel BF_3 detector were 35, 71, 320, 480, 1630, and 10,500 counts/s per gram of ^{108}B for full loadings of rows 1, 2, 3, 4, 5, and 6, respectively.

Fig. 6.8.1. Inverse Count Rate vs Number of Fuel Assemblies Loaded for Both the SRFM and an In-Core Detector.

These calculations show that monitoring of the CRBR with an ex-vessel detector is feasible. This conclusion should be verified by initial experiments with mockups of the CRBR before the sensibility of ex-vessel monitoring is demonstrated. However, since such prototypic verification experiments may not be possible due to the size limitations of

the critical experiment facilities, it might not be possible to mock up the ex-vessel detector core configuration experimentally. An in-vessel detector with remote signal transmission will be capable of monitoring the initial loading.⁶ The in-vessel detector response can be verified experimentally in mockup experiments prior to the initial loading of the CRBR. The initial loading can be monitored with both an ex-vessel and in-vessel detector simultaneously if the in-vessel detector is located sufficiently far from the central source (in radial blanket or shield) so that its response will be primarily from core fission neutrons and not directly from the source.

*Research sponsored by DOE Office of Reactor Research and Technology.

†Instrumentation and Controls Division.

1. P. P. Clauzon, J. Boyer, J. Boundow, J. Martin, and J. Mougnoit, "Experimental Physics Results at the Startup of Phenix," Int. Conf. Physics Fast Reactors, Tokyo (Oct. 16-23, 1972).
2. Personal Communication from D. C. G. Smith and R. C. Wheeler, Dounreay Experimental Reactor Establishment (1974).
3. M. M. Greene, J. L. Lucius, L. M. Petrie, W. E. Ford, III, J. C. White, and R. Q. Wright, "AMPX: A Modular Coded System for Generating Coupled Multi-Grouped Neutron Gamma Libraries from ENDF/B," ORNL/TM-3706 (1976).
4. L. H. Petrie and N. F. Cross, "KENO-IV: An Improved Monte Carlo Criticality Program," ORNL-4938 (Nov. 1975).
5. W. A. Rhoades, D. B. Simpson, R. L. Childs, and W. W. Engle, Jr., "The DOT-IV Two-Dimensional, Discrete-Ordinates Transport Code with Space-Dependent Mesh and Quadrature," ORNL-5283 (1978).
6. J. T. De Lorenzo, ORNL, Personal Communication (1979).

6.9. FY 1977 PROGRESS REPORT OF THE CLINCH RIVER BREEDER REACTOR SOURCE RANGE FLUX MONITOR ASSESSMENT STUDY FOR THE REFERENCE HOMOGENEOUS CORE*

M. B. Emmett[†] W. W. Engle, Jr. G. F. Flanagan H. E. Knee
 D. L. Loyd[‡] D. L. Selby L. R. Williams
 Edited By: D. L. Selby

(Abstract of ORNL-5548, September, 1979)

In 1974 ORNL was requested by ERDA [Energy Research and Development Administration, now Department of Energy (DOE)] to participate in the analysis of the Source Range Flux Monitoring scheme for the Clinch River Breeder Reactor Plant (CRBRP) largely because of ORNL's involvement in similar work for the Fast Flux Test Facility (FFTF). This report summarizes the analysis performed by ORNL on the Source Range Flux Monitor (SRFM) during FY 1977.

Interpretability of Inverse Kinetics Rod Drop (IKRD) was examined and found to be feasible. The absolute count rate at beginning-of-life (BOL) full shutdown was calculated and determined to be below minimum recommended levels. However, geometry and material changes in the SRFM were identified which could be employed to achieve the desired minimum levels. Generalized perturbation interpolation schemes to estimate detection efficiency changes were investigated and found to be feasible but not very practical. In addition, the uncertainties associated with the devised subcritical monitoring procedure were examined.

*Research sponsored by DOE Office of Reactor Research and Technology.

†UCC-ND Computer Sciences Division.

‡Technology for Energy Corporation, Knoxville, Tennessee.

6.10. FY 1978 PROGRESS REPORT OF THE CLINCH RIVER BREEDER REACTOR SOURCE RANGE
FLUX MONITOR ASSESSMENT STUDY FOR THE REFERENCE HETEROGENEOUS CORE*

W. W. Engle, Jr. H. E. Knee D. L. Loyd[†]
J. T. Mihalcz[‡] D. L. Selby
Edited By: D. L. Selby

(Abstract of ORNL-5627, September, 1980)

In 1974 ORNL was requested by ERDA [Energy Research and Development Administration, now Department of Energy (DOE)] to participate in the analysis of the Source Range Flux Monitoring scheme for the Clinch River Breeder Reactor Plant (CRBRP) largely because of ORNL's involvement in similar work for the Fast Flux Test Facility (FFTF). This report summarizes the analysis performed by ORNL on the Source Range Flux Monitor (SRFM) during FY 1978.

Ex-vessel techniques for monitoring initial load to critical were examined and found to be adequate in a theoretical sense. The count rate history during refueling of the first four cycles was examined. It was determined that by considering other factors a new reloading scheme could be developed which would have a relatively smooth decaying count rate curve over the entire refueling procedure. In addition to the above, the absolute count rate at beginning-of-life (BOL) full shutdown was calculated for the new detector block design and found to be adequate for monitoring shutdown operations.

*Research sponsored by DOE Office of Reactor Research and Technology.

[†]Technology for Energy Corporation, Knoxville, TN.

[‡]Instrumentation and Controls Division.

6.11. EVALUATION OF SINGLE-ROD WITHDRAWAL TECHNIQUES FOR USE IN CONSTRUCTING
INVERSE COUNT RATE CURVES DURING INITIAL LOADING OF THE FIRST CORE
IN THE CLINCH RIVER BREEDER REACTOR (CRBR)*

W. T. Swain[†] D. L. Selby

(Abstract of ORNL/TM-7204, September, 1980)

The feasibility of initial loading using single-rod withdrawal techniques was investigated by considering three stages in the fuel loading: (1) all fuel assemblies loaded except Rows 9 and 10, (2) all fuel assemblies loaded except Row 10, and (3) the core fully loaded. This investigation identified two important factors affecting the feasibility of any method for criticality prediction involving single-rod withdrawals. First, for a given fuel configuration any single correction factor used to infer the inverse count rate for a "near-critical" control rod configuration is extremely sensitive to differences in detector efficiencies associated with different single control rod withdrawals. Second, even if the efficiencies could be assumed constant, the results indicate that the correction factor is still a function of fuel configuration.

It was concluded that any practical method for monitoring the approach to critical with single-rod withdrawals would require extensive calculations based on the design data to be verified. It was therefore recommended that single-rod withdrawal techniques not be considered acceptable methods for monitoring the CRBR initial approach to critical.

*Research sponsored by DOE Office of Reactor Research and Technology.

[†]Technology for Energy Corporation, Knoxville, TN.

6.12. INVESTIGATION OF ALTERNATE SCHEMES FOR RELOADING THE CLINCH RIVER BREEDER REACTOR CORE AT THE END OF CYCLE TWO (EOC2)

D. L. Loyd[†] D. L. Selby W. M. Simpkins[†]

(Abstract of ORNL/TM-7538, to be published)

Alternate refueling schemes for the Clinch River Breeder Reactor (CRBR) core were examined to develop a relatively smooth decreasing count rate curve during refueling. Of the four refueling schemes investigated, two gave marginal improvement in the smoothness of the count rate curve while the other two showed marked improvement. It was found that a relatively smooth decreasing count rate curve could be obtained by using the following general refueling sequence: 1) replace the internal blankets by starting at the core center and moving out; and 2) replace the fuel elements by starting at Row 8 and moving out through Row 10, following with Row 7 and moving toward the core center to complete the refueling. The scheme recommended follows these guidelines.

*Research sponsored by DOE Office of Reactor Research and Technology.

[†]Technology for Energy Corporation, Knoxville, Tennessee.

6.13. RADIATION ANALYSIS OF THE CONCEPTUAL DESIGN STUDY 1000-MW(e) LOOP-DESIGN LMFBR

W. A. Rhoades M. B. Emmett[†] J. R. Knight[†] W. W. Engle, Jr.

(Abstract of ORNL/TM-7492, to be published)

One of the designs considered in DOE's Conceptual Design Study (CDS) was developed by Rockwell's Energy Systems Group. A thorough analysis of neutron and gamma fields in this reactor was performed. Certain dose rates of concern were calculated. Extensive contour plots of the results, of potential value, are included.

*Research sponsored by DOE Office of Reactor Research and Technology.

[†]UCC-ND Computer Sciences Division.

GAS-COOLED FAST BREEDER REACTOR PROGRAM

6.14. GAS-COOLED FAST REACTOR PROGRAM ANNUAL PROGRESS REPORT FOR PERIOD ENDING DECEMBER 31, 1979*

U. Gat[†] P. R. Kasten[†]

(Excerpta from Section 2, "GCFR Shielding and Physics," of ORNL-4074, November, 1980)

2.1. Introduction (D. T. Ingersoll)

Activities performed in the GCFR Shielding and Physics Program during 1979 include completion of the grid-plate shield design verification experiment postanalysis; completion of the radial blanket and shield experiment and associated preanalysis, and initiation of postanalysis; design support analysis for preliminary upflow shield designs; preliminary feasibility assessment of the fast mixed-spectrum reactor concept; and analysis of critical experiments performed at the Swiss Federal Institute for Reactor Research (EIR), Würenlinger, Switzerland.

2.2. Grid-Plate Shield Design Confirmation Experiment^{**} (C. O. Slater, S. N. Crämer, and D. T. Ingersoll)

A few final calculations for the postanalysis of the Grid Plate Shield Design Confirmation Experiment were performed to aid in the interpretation of the experiment as it is related to the GCFR design.

2.3. Radial Blanket and Shield Experiment^{**} (D. T. Ingersoll and F. J. Muckenthaler)

An integral experiment was designed for the verification of radiation transport methods and nuclear data used for the design of the radial shield for the proposed 300-MW(e) GCFR. The experiment was performed at the Tower Shielding Facility March-September, 1979, and the postanalysis continued through 1980.

2.4. Shielding Analysis in Support of the Upflow GCFR Design (C. O. Slater, E. T. Tomlinson,[§] L. R. Williams, and D. A. Reed[¶])

A DOT-IV calculation was performed on an R-Z mockup of the upflow GCFR from 34 cm below the core midplane through a portion of the top plug of the reactor (upper plenum shield calculations). The radial shield analysis concentrated mainly on the portion of the reactor with Z-levels between the bottom of the grid plate and the top of the exit shield region. The lower plenum shield calculation, like the upper plenum mockup, also included the outlet duct from the main helium circulator. Work was begun on the analysis of very different upper and lower plenum shield designs for a 400-MW(e) two-loop GCFR.

2.5. GCFR Reactor Physics Analysis (T. J. Burns, J. R. White,[§] and D. T. Ingersoll)

The Fast Mixed-Spectrum Reactor (FMSR) concept has been proposed (by Brookhaven National Laboratory) as a means of alleviating certain nonproliferation concerns relating to civilian nuclear power. A preliminary study directed at assessing the neutronic feasibility of the concept has been performed at ORNL. Also, an extensive program of reactor physics experiments in GCFR fuel pin lattices was completed recently at the PROTEUS critical facility located at EIR Laboratory in Switzerland, and detailed analyses have been performed at EIR and at ORNL.

* Research sponsored by Office of Advanced Nuclear Systems and Projects.

† Engineering Technology Division.

‡ ORNL Central Management.

** See also Section 4.

§ UCC-ND Computer Sciences Division.

¶ University of Tennessee.

6.15. ANALYSIS OF THE INITIAL SHIELDING DESIGN FOR THE UPFLOW GAS-COOLED FAST REACTOR (GCFR)*

C. O. Slater E. T. Tomlinson[†] L. R. Williams

(Abstract of ORNL/TM-7246, May, 1980)

Presented here are the results of a preliminary analysis of the initial shield design for a gas-cooled fast reactor in which the coolant flow has been reversed from downward to upward. Calculations were performed on two levels: (1) localized, heterogeneous cell calculations to determine the effects of radiation streaming, and (2) streaming-corrected full-model homogeneous calculations to obtain global radiation levels. The method used to obtain and apply the streaming factors is explained. The results indicate that with a few exceptions the shielding design is very effective. Possible problems exist in (1) the core barrel, where the total neutron fluence limit of 10^{21}cm^{-2} is exceeded, and (2) the grid plate, where the neutron fluence is near the fluence limit predicted by damage function analysis.

*Research sponsored by DOE Office of Advanced Nuclear Systems and Projects.

†UCC-ND Computer Sciences Division.

6.16. ANALYSIS OF THE CONCEPTUAL SHIELDING DESIGN FOR THE UPFLOW GAS-COOLED FAST BREEDER REACTOR*

C. O. Slater D. A. Reed[†] S. N. Cramer
M. B. Emmett[†] E. T. Tomlinson[†]

(Abstract of ORNL-5868, in press)

Conceptual Shielding Configuration III for the Gas-Cooled Fast Breeder Reactor (GCFR) was analyzed by performing global calculations of neutron and gamma-ray fluences and correcting the results as appropriate with bias factors from localized calculations. Included among the localized calculations were the radial and axial cell streaming calculations, plus extensive preliminary calculations and three final confirmation calculations of the plenum flow-through shields. The global calculations were performed on the GCFR mid-level and the lower and upper plenum regions. Calculated activities were examined with respect to the design constraint, if any, imposed on the particular activity. The spatial distributions of several activities of interest were examined with the aid of isoplots (i.e., symbols are used to describe a surface on which the activity level is everywhere the same).

In general the results showed that most activities were below the respective design constraints. Only the total neutron fluence in the core barrel appeared to be marginal with the present reactor design. Since similar results were obtained for an earlier design (see ORNL/TM-7246), it has been proposed that the core barrel be cooled with inlet plenum gas to maintain it at a temperature low enough that it can withstand a higher fluence limit. Radiation levels in the prestressed concrete reactor vessel (PCRV) and liner appeared to be sufficiently below the design constraint that expected results from the Radial Shield Heterogeneity Experiment should not force any levels above the design constraint.

A list was also made of a number of issues which should be examined before completion of the final shielding design.

*Research sponsored by DOE Office of Advanced Nuclear Systems and Projects.

†University of Tennessee.

‡UCC-ND Computer Sciences Division.

6.17. ANALYSIS OF THE NEW GCFR UPPER AND LOWER PLENUM FLOW-THROUGH SHIELDS*

S. N. Cramer D. A. Reed[†] M. B. Emmett[†] C. A. Rouse[‡]

(Abstract of paper presented at ANS Topical Meeting, Advances in Reactor Physics and Shielding, Sun Valley, Idaho, September 14-17, 1980)

Analysis of the proposed GCFR upper and lower plenum flow-through shields has been performed using both discrete ordinate (DOT) and Monte Carlo (MORSE) methods. Several shields having one change of direction in the coolant path (chevron) and two changes of direction (herringbone) were investigated. The shields were modeled as unit cells with periodic boundary conditions. From plenum fluence calculations and design constraints at the reactor vessel liner, it was determined that all the shield configurations analyzed should be adequate for the necessary radiation attenuation.

* Research sponsored by DOE Office of Advanced Nuclear Systems and Projects.

† University of Tennessee.

‡ UCC-ND Computer Sciences Division.

§ General Atomic Company.

6.18. PRELIMINARY NEUTRONIC ANALYSIS OF A FAST MIXED-SPECTRUM REACTOR (FMSR)*

T. J. Burns J. R. White†

(Abstract of ORNL/TM-6854, August, 1979)

The Fast Mixed-Spectrum Reactor (FMSR) concept has been proposed (by Brookhaven National Laboratory) as a means of alleviating certain non-proliferation concerns relating to civilian nuclear power. In particular, the concept is envisioned as operating on a natural uranium feed (after initial startup), thus eliminating the need for fuel reprocessing. The primary basis for the concept involves the production, *in situ*, of the fissile material required for criticality from the fertile feed material. The results of a preliminary study directed at assessing the neutronic feasibility of the concept are reported in this document.

The study evolved through four major phases. Scoping calculations were first performed using an available GCFR cross-section library and a reference FMSR calculational model. These initial calculations indicated the need for a more detailed broad-group representation of the cross sections than that utilized in the GCFR library due to the large spectral and spatial gradients inherent in the FMSR design. Further, large differences in the fission product cross sections relative to those employed in the reference calculation were observed. Hence, spatially dependent broad-group nuclear data, including a detailed fission product cross section, were generated specifically for the FMSR. The next phase of the study involved the calculation of the major physics parameters relating to the FMSR using these new cross sections. Multicycle calculations using the new FMSR cross sections indicated that alternate designs (relative to the benchmark) would be required in order to meet criticality requirements. Finally, some possible design variations and modeling questions were briefly investigated.

No definitive conclusion as to the feasibility of the FMSR concept can be made from the preliminary analysis reported here, however. Specifically, due to the large number of potential design changes which can be made, further study is required in order to determine feasibility. This investigation, however, has indicated several areas in which further work is required before the basic feasibility of the concept can be either proved or disproved.

* Research sponsored by DOE Office of Advanced Nuclear Systems and Projects.

† UCC-ND Computer Sciences Division.

6.19. ANALYSIS OF FISSION-PRODUCT EFFECTS IN A FAST MIXED-SPECTRUM REACTOR CONCEPT*

J. R. White† T. J. Burns

(Abstract of ORNL/TM-791, February, 1980)

The Fast Mixed-Spectrum Reactor (FMSR) concept has been proposed by BNL as a means of alleviating certain nonproliferation concerns relating to civilian nuclear power. This

breeder reactor concept has been tailored to operate on natural uranium feed (after initial startup), thus eliminating the need for fuel reprocessing. The fissile material required for criticality is produced, in situ, from the fertile feed material. This process requires that large burnup and fluence levels be achievable, which, in turn, necessarily implies that large fission product inventories will exist in the reactor. It was the purpose of this study to investigate the effects of large fission product inventories and to analyze the effect of burnup on fission product nuclide distributions and effective cross sections. In addition, BNL requested that a representative 50-group fission product library be generated for use in FMSR design calculations.

Results from the brief investigation of the effects of the large fission product inventory in the FMSR indicated that care needs to be taken when modeling the effects of fission products on reactor performance. They not only have direct reactivity effects, but they also affect power and flux distributions and breeding performance. It was found that deletion of the fission products in a reference FMSR design resulted in a 5.4% reactivity gain at the beginning-of-life (equilibrium model) and about a 4.2% gain on the new equilibrium cycle, with the difference being caused by the radial redistribution of the neutron flux.

The effect of burnup on effective fission product cross sections was then analyzed with somewhat surprising results. The final conclusion was that a one-lump fission product model is sufficiently accurate for reliable FMSR design studies. Although a multi-nuclide fission product set which explicitly accounts for the more important chains would be a more accurate representation, the added complexity and cost would outweigh the additional accuracy. It is felt that the uncertainty in the one-lump model is tolerable for preliminary design calculations and probably lies well within the uncertainty of the individual fission product cross sections.

Finally, based on the above conclusions, a 50-group fission product library was generated. The library contains a single fission product lump for each of six spectral regions of a 1-d FMSR model.

*Research sponsored by DOE Office of Advanced Nuclear Systems and Projects.

†UCC-ND Computer Sciences Division.

6.20. CRITICAL EXPERIMENTS IN A ZERO POWER FAST REACTOR LATTICE WITH BREEDER ZONES OF THORIUM AND URANIUM*

U. Schmocke†	R. Chawla†	K. Gaur†	M. Jermann†
C. McCombie†	R. Richmond†	S. Seth†	D. E. Bartine
	D. T. Ingersoll	J. R. White†	

[Abstract of paper (IAEA-SM-244/73) presented at the International Symposium on Fast Reactor Physics, Aix-en-Provence, France, September 24-28, 1979]

Increased interest in alternate fuel cycles and in nonconventional fast reactor core designs has emphasized the need for reliable benchmark experiments against which the relevant nuclear data and methods can be checked. In the PROTEUS critical assembly we have recently completed an extensive series of measurements in GCFR lattices with internal and axial blankets of UO_2 , ThO_2 and Th metal.

The GCFR lattice consists of a PuO_2/UO_2 pin-fueled zone in a thermally driven assembly. Central values and spatial distributions have been monitored for nuclide reaction rates including fission in ^{239}Pu , ^{233}U , ^{238}U , and ^{232}Th , capture in ^{238}U and ^{232}Th and $(n,2n)$ in ^{232}Th . In addition, differential spectrum measurements using proton-recoil counters were performed.

The results of the experiments have been compared with calculations based on the UK FGL5 nuclear data library (in which thorium cross sections are derived from ENDF/B-4

values). Further analyses are in progress. Conclusions to date are that uranium blankets are significantly better calculated by our data and methods than are thorium blankets. The discrepancies between calculation and experiment in thorium systems are, however, not of a magnitude which casts major doubts upon current survey calculations for reactor systems with heterogeneous cores.

* ORNL research supported by DOE Office of Advanced Nuclear Systems and Projects.

† Swiss Federal Institute for Reactor Research, CH-5303 Würenlingen, Switzerland.

‡ Indian Institute of Technology, Kanpur, India.

§ General Atomic Company.

¶ UCC-ND Computer Sciences Division.

6.21. ANALYSIS OF A SWISS THORIUM BLANKET INTEGRAL EXPERIMENT*

J. R. White[†] D. T. Ingersoll U. Schmocker[‡] K. Gmür[‡]

(Abstract of paper in *Nuclear Cross Sections for Technology*, NBS Special Publication 594, p. 126, 1980)

A detailed postanalysis of the ThO₂ axial blanket experiment (CORE 14) performed at the PROTEUS critical facility is presently being completed at ORNL. The purpose of the analysis is to compare measured reaction rates along the axial centerline of the test zone with results calculated utilizing various data libraries. In particular, the analysis is investigating the adequacy of the available thorium data. The cross section data supplied by EIR is compared to ENDF/B-4 data collapsed to the broad-group level via the AMPX modular code system. Furthermore, a comparison of C/E values using ENDF/B-4 and new ENDF/B-5 thorium data is given. Finally, some theory and modeling questions are investigated. Detailed results from the above analyses are presented which support the conclusion that the presently available ²³²Th data appears inadequate for accurate GCFR fuel cycle studies.

* ORNL research sponsored by DOE Office of Advanced Nuclear Systems and Projects.

† UCC-ND Computer Sciences Division.

‡ Swiss Federal Institute for Reactor Research, CH-5303 Würenlingen, Switzerland.

6.22. ANALYSIS OF THE THORIUM AXIAL BLANKET EXPERIMENTS IN THE PROTEUS REACTOR*

J. R. White[†] D. T. Ingersoll

(Abstract of ORNL/TM-7471, in press)

Detailed analysis has been completed for the ThO₂ and Th-metal axial blanket experiments performed at the Swiss PROTEUS critical facility. The purpose of the analysis was to compare reaction rates and neutron spectra measured in prototypic GCFR configurations with results calculated utilizing various computational methods and cross-section data libraries, including ENDF/B-V thorium data. The comparisons were intended to verify the adequacy of available thorium data for use in accurate fast reactor alternative fuel cycle studies.

The PROTEUS configurations allowed the analysis of infinitely dilute thorium data in a PuO₂/UO₂ fast lattice spectrum at core center as well as the analysis of resonance

self-shielding effects in the thorium-bearing axial blankets. The results of these comparisons, although inconclusive in the axial blanket regions, indicate that significant deficiencies still exist in the latest evaluated infinitely-dilute thorium data file. Specifically, the analysis showed that the ^{232}Th capture is underpredicted by ENDF/B-IV data, and the discrepancies are further exaggerated by ENDF/B-V data. On the other hand, ENDF/B-V ^{232}Th fission data appear to be significantly improved relative to ENDF/B-IV data, while discrepancies are extremely large for the $(n,2n)$ process in both data files. Finally, the (n,n') cross sections for thorium also appear improved in ENDF/B-V, except for a small energy range just above the 50 keV threshold. Therefore, these combined data deficiencies suggest that relatively large uncertainties should be associated with many of the results obtained from recent fast reactor alternate fuel cycle analyses.

* Research sponsored by DOE Office of Advanced Nuclear Systems and Projects.

† UCC-ND Computer Sciences Division.

6.23. NEUTRON SPECTRUM EVALUATION IN THE THORIUM AXIAL BLANKETS OF THE PROTEUS REACTOR*

M. Jermann† D. T. Ingersoll

(Abstract of paper presented at ANS Topical Meeting, Advances in Reactor Physics and Shielding, Sun Valley, Idaho, September 14-17, 1980)

Experiments have been performed in the EIR-PROTEUS critical facility for the purpose of validating nuclear data and analytic methods used for fast reactor design. Neutron spectrum measurements in GCFR-type ThO_2 and Th-metal axial blankets were made between 14 MeV and 2.3 MeV using spherical gas proton-recoil detectors. The measurements were compared to analytic predictions as a test of the basic nuclear data and multigroup processing. Results based on both ENDF/B-IV and ENDF/B-V thorium data showed that the blanket spectra were primarily sensitive to the inelastic scattering process and that ENDF/B-V Th-232 (n,n') cross sections were superior to ENDF/B-IV data above 300 keV. However, ENDF/B-IV data gave better agreement with measurements near the 50 keV (n,n') threshold.

* ORNL research sponsored by DOE Office of Advanced Nuclear Systems and Projects.

† Swiss Federal Institute for Reactor Research, CH-5303 Würenlingen, Switzerland.

6.24. ALTERNATIVE HETEROGENEOUS GCFR FUEL CYCLES*

J. R. White† T. J. Burns

(Reprint of Trans. Am. Nucl. Soc. 32, 403-405, 1979)

Recent changes in the U.S. nuclear energy policy have led to a greatly expanded study of proliferation-resistant nuclear fuel cycles. Several preliminary investigations¹⁻³ have been performed to assess the feasibility of these alternative fuel cycle concepts for LMFBRs. The intent of this paper is to summarize the results of a similar evaluation of alternative-fueled gas-cooled fast reactors (GCFRs). The study included both the homogeneous concept and an advanced heterogeneous design. However, since alternative-fueled homogeneous GCFR characteristics have been reported elsewhere,⁴ the emphasis of this paper is on the heterogeneous model. Results from the classical homogeneous calculational model consisting of four core zones are used only as a basis for comparison of the two concepts.

The reference reactor utilized for this preliminary evaluation was based on an early General Atomic 1200-MW(e) homogeneous design.⁵ A heterogeneous design with 60-deg

symmetry was constructed from the same fuel and blanket assemblies as used in the reference case. After some iteration, the final core design had four fissile rings, each separated by a row of fertile blanket assemblies. As in the reference design, a three-row radial blanket encompassed the core regions. Criticality adjustments were possible with 24 control rods and 6 safety rods placed symmetrically throughout the core. The principal neutronic analysis tool used in this evaluation was the CITATION⁶ computer code. Nine-group cross sections generated from ENDF/B-IV data were used throughout the study.

Early in the study an effort was made to verify that the R-Z concentric annuli reactor model used in the depletion calculations described below was a realistic simplification of the three-dimensional (3-D) fast reactor. The position and relative worth of the control rods in the 2-D model were of particular interest. Table 6.24.1 contrasts the results of 2-D and 3-D static BOL calculations for a 1200-MW(e) GCFR with (Pu-U)₂O₂ fuel assemblies and ThO₂ radial and internal blankets. This comparison indicates that the simplified R-Z calculational model produces accurate results with a significant reduction in cost and effort. It should also be noted that the radial power distributions for the two reactor models are in good agreement.

Table 6.24.1. Comparison of 2-D and 3-D Calculational Models for a Pu-UO₂/ThO₂ Heterogeneous GCFR

	No control in core		Control rod fully inserted	
	2-D Model	3-D Model	2-D Model	3-D Model
Beginning-of-Life-Parameters				
K_{eff}	1.0100	1.0100	0.9646	0.9653
Max power density (W/cm ³)	419.0	421.6	428.5	440.6
Max linear heat rate (kW/ft)	11.8	11.9	12.1	12.4
Fissile enrichment	0.283	0.286	0.283	0.286
Total breeding ratio	1.527	1.521	1.545	1.541
²³³ U component	1.122	1.121	1.138	1.137
Fissile Pu component	0.405	0.400	0.407	0.404

A three-step calculational procedure was employed for the fuel burnup calculations. An initial depletion calculation was performed to determine the reload enrichment necessary to achieve an effective multiplication factor of unity at the end of the equilibrium cycle (i.e., cycle for which the discharge isotopics are identical with the preceding cycle). A fuel management scheme in which 1/3 of each fissile region, 1/2 of each fertile row, and 1/6 of the radial blanket assemblies were replaced annually was utilized, and a capacity factor of 0.75 was assumed. Additional computations were performed to determine the minimum first-cycle fissile loading consistent with criticality requirements over the initial cycles. Finally, using the initial core and reload specifications determined in the above two steps, a final burnup calculation was done in which the control material was adjusted to maintain a just-critical configuration at each depletion time step.

The primary alternative fuel cycle scenario analyzed using the above procedure was the energy center/dispersed reactor concept in which proliferation-resistant denatured reactors are coupled to ²³³U-production reactors operating in secure energy centers. Various alternative fissile/fertile combinations were analyzed as proposed fuel for reactors both inside and outside the energy center.

Table 6.24.2 presents the equilibrium cycle results for these various alternative fuel cycle heterogeneous GCFR reactors. The penalties incurred by substituting the alternative fuels into the reference reactor are apparent. More important, however, is the observation that the minimum denaturing (cases 4 and 5) for the present model was approximately 29% $^{233}\text{U}/\text{U}$. This high ^{233}U concentration in the fresh fuel essentially eliminates this GCFR concept as a proliferation-resistant denatured fuel cycle option. On the other hand, the large breeding ratio and ^{233}U production capability of cases 1, 2, and 3 make the Pu-fueled heterogeneous GCFR an attractive energy center reactor.

Table 6.24.2. Equilibrium Cycle Results for Alternative Fuel Cycle 1200-MW(e) Heterogeneous GCFR Reactors

Case	Driver	Description		²³³ U in U	MOC S.R.	Initial fissile loading	Mass balances (kg/yr)					CFBR ^c (yr)
		Axial blanket	Inner & radial blanket				Discharge		Net gain			
							²³³ U	Pu	²³³ U	Pu		
1	(Pu-U)O ₂	UO ₂	UO ₂	-	1.536	5163	1721	-	2139	-	418	11.4
2	(Pu-U)O ₂	UO ₂	ThO ₂	-	1.456	5647	1882	797	1450	797	-433	14.3
3	(Pu-Th)O ₂	ThO ₂	ThO ₂	-	1.371	6110	2037	1025	1309	1025	-728	19.0
4	(²³³ U-U)O ₂	UO ₂	ThO ₂	29.2	1.246	5510	1837	1816	244	-21	244	22.8
5	(²³³ U-U)O ₂	ThO ₂	ThO ₂	29.2	1.241	5510	1837	1889	165	52	165	23.5
6	(²³³ U-U-Th)O ₂	ThO ₂	ThO ₂	43.0	1.218	5665	1889	1984	104	95	104	26.3
7	(²³³ U-Th)O ₂	ThO ₂	ThO ₂	100.0	1.168	6017	2006	2162	-	156	-	35.6

^cCompound fissile doubling time assuming no reprocessing losses.

Characteristics of the heterogeneous GCFR fueled with Pu drivers will be presented in more detail. Symbiotic system parameters such as the equilibrium power support ratio and system growth rate will be discussed for various scenarios with the GCFR transmuter as the primary ^{233}U source. Finally, comparisons with "equivalent" homogeneous designs will be presented.

*Research sponsored by DOE Office of Advanced Nuclear Systems and Projects.

†UCC-ND Computer Sciences Division.

1. T. J. Burns and D. E. Bartine, "Feasibility of Denatured LMFBRs," Trans. Am. Nucl. Soc. 26, 285 (1977).
2. T. J. Burns, J. R. White, D. E. Bartine, J. M. Kallfelz, and D. M. Rowland, "Denatured Fast Reactor Symbiosis," Trans. Am. Nucl. Soc. 27, 454 (1977).
3. T. J. Burns and J. R. White, "Preliminary Evaluations of Alternative LMFBR Fuel Cycle Options," ORNL-5389 (October 1978).
4. C. J. Hamilton, "Preliminary Study of Alternate Fuel Cycles for the Gas-Cooled Fast Breeder Reactor," GA-A14536, General Atomic (August 1977).
5. Letter to D. E. Bartine from R. J. Carbone, General Atomic #760422032 (April 1976).
6. T. B. Fowler, D. R. Vundy, and G. W. Cunningham, "Nuclear Reactor Core Analysis Code: CITATION," ORNL/TM-2496, rev. 2 (July 1971).

6.25. PRELIMINARY EVALUATION OF ALTERNATE-FUELED GAS COOLED FAST REACTORS*

J. R. White[†] T. J. Burns

(Abstract of ORNL/TN-7432, December, 1980)

A preliminary evaluation of various alternative fuel cycles for the Gas-Cooled Fast Reactor (GCFR) is presented. Both homogeneous and heterogeneous oxide-fueled GCFRs are considered. The scenario considered is the energy center/dispersed reactor concept in which proliferation-resistant denatured reactors are coupled to ^{233}U production reactors operating in secure energy centers. Individual reactor performance characteristics and symbiotic system parameters are summarized for several possible alternative fuel concepts. Comparisons are made between the classical homogeneous GCFR and the advanced heterogeneous concept on the basis of breeding ratio, doubling time, and net fissile gain. In addition, comparisons are made between a three-dimensional reactor model and the R-Z heterogeneous configuration utilized for the depletion and fuel management calculations. Lastly, thirty-year mass balance data are given for the various GCFR fuel cycles studied.

*Research sponsored by DOE Office of Advanced Nuclear Systems and Projects.

[†]UCC-ND Computer Sciences Division.

6.26. US/FRG JOINT REPORT ON THE PEBBLE BED HIGH TEMPERATURE REACTOR RESOURCE CONSERVATION POTENTIAL AND ASSOCIATED FUEL CYCLE COSTS*

E. Teuchert[†] H. J. Rütten[†] B. A. Worley D. R. Vondy

(Abstract of ORNL-5582, November, 1979)

Independent analyses at ORNL and KFA have led to the general conclusion that the flexibility in design and operation of a high-temperature gas-cooled pebble-bed reactor (PBR) can result in favorable ore utilization and fuel costs in comparison with other reactor types, in particular, with light-water reactors (LWRs). Fuel reprocessing and recycle show considerable promise for reducing ore consumption, and even the PBR throwaway cycle is competitive with fuel recycle in an LWR. The best performance results from the use of highly enriched fuel. Proliferation-resistant measures can be taken using medium-enriched fuel at a modest ore penalty, while use of low-enriched fuel would incur further ore penalty. Breeding is possible but net generation of fuel at a significant rate would be expensive, becoming more feasible as ore costs increase substantially. The ^{233}U inventory for a breeder could be produced by prebreeders using ^{235}U fuel.

*ORNL research sponsored by DOE Office of Advanced Nuclear Systems and Projects.

[†]Kernforschungsanlage Jülich GmbH, FRG.

6.27. COMPARATIVE EVALUATION OF PEBBLE-BED AND PRISMATIC FUELED HIGH-TEMPERATURE GAS-COOLED REACTORS*.[†]

P. R. Kasten[†] D. E. Bartine T. J. Burns
B. A. Worley L. S. Abbott

(Abstract of ORNL-5694, in press)

A comparative evaluation has been performed of the High Temperature Gas Cooled Reactor (HTGR) and the Federal Republic of Germany's Pebble Bed Reactor (PBR) for potential commercial applications in the U.S. The evaluation considered two reactor sizes [1000 and 3000 MW(t)] and three process applications (steam cycle, direct cycle, and process

heat, with outlet coolant temperatures of 750, 850, and 950°C, respectively). The primary criterion for the comparison was the levelized (15-year) cost of producing electricity or process heat. Emphasis was placed on the cost impact of differences between the prismatic-type HTGR core, which requires periodic refuelings during reactor shutdowns, and the pebble bed PBR core, which is refueled continuously during reactor operations. Detailed studies of key technical issues using reference HTGR and PBR designs revealed that two cost components contributing to the levelized power costs are higher for the PBR: capital costs and operation and maintenance costs. A third cost component, associated with non-availability penalties, tended to be higher for the PBR except for the process heat application, for which there is a large uncertainty in the HTGR nonavailability penalty at the 950°C outlet coolant temperature. A fourth cost component, fuel cycle costs, is lower for the PBR, but not sufficiently lower to offset the capital cost components. Thus the HTGR appears to be slightly superior to the PBR in economic performance. Because of the advanced development of the HTGR concept, large HTGRs could also be commercialized in the U.S. with lower R&D costs and shorter lead times than could large PBRs. On the basis of these results, it is recommended that the U.S. gas-cooled thermal reactor program continue giving primary support to the HTGR. At the same time, the U.S. should maintain a cooperative PBR program with FRG, emphasizing work in the key areas of reactor control and instrumentation.

* Research sponsored by DOE Office of Advanced Nuclear Systems and Projects.

† Contributions to evaluation made by G. A. Aramayo, J. G. Delene, S. J. Ditto, W. P. Eatherly, E. P. Epler, V. H. Guthrie, F. J. Homan, M. L. Myers, D. J. Naus, A. R. Olsen, M. F. Osborne, P. L. Rittenhouse, D. R. Vondy, and R. P. Wichner, ORNL; L. W. Perry, R. M. Zamora, and J. A. Hodde, Management Analysis Company; L. Abraham, A. Barsell, B. B. Haldy, D. Hanson, J. A. Oita, D. P. Orvis, J. N. Sharmahd, and E. O. Winkler, General Atomic Company; C. R. Davis, W. B. Scott, and G. R. Pflasterer, General Electric Company; and D. Harmon, Gas-Cooled Reactor Associates.

‡ ORNL Central Management.

LIGHT-WATER REACTOR PROGRAMS

6.28. CALCULATION OF THE TMI-2 SOURCE-RANGE MONITOR READING FOR SEVERAL CORE WATER LEVELS*

R. L. Childs[†] D. L. Selby
J. C. Robinson[‡] P. G. Canada[‡] R. L. Monday[‡]

(Reprint of Trans. Am. Nucl. Soc. 34, 558, 1980)

The strip chart record of the source range monitor (SRM) readings for the first few hours following the reactor trip on March 28, 1979 is reproduced in Fig. 6.28.1. The purpose of the work described here is to calculate the expected SRM reading for various core water levels. These results are needed to relate the detector reading to conditions in the core. The SRM information can be used in conjunction with thermal-hydraulic and other information to develop a plausible reconstruction of the core uncover.

For the first 15 min or so after the reactor trip, the SRM falls rapidly on an 80-s period characteristic of delayed neutrons. Then there is a transition to a slower period characteristic of the decay of fission products. The decay of these fission products is accompanied by the release of energetic gamma rays, which produce photoneutrons via the (γ, n) reaction with deuterium in the reactor coolant. The curve labeled "expected" in Fig. 6.28.1 was determined by one-dimensional (1-D) ANISN¹ calculations using the same general calculational procedure to be described shortly for 2-D calculations. The "expected" curve was normalized to agree with the observed curve at 104 min. This normalization is based on the assumption that when all pumps stopped at 100 min the core and downcomer were temporarily filled with water. This assumption results in agreement between the observed count rate and the "expected" curve in the 15- to 20-min time period. Also, the "expected" curve agrees in shape with data from a trip at Oconee-1 on November 18, 1978.

Calculations of the SRM response as a function of the water-level in the core involve both reactor physics and shielding considerations. As water is removed, the photo-neutron source decreases. Also, the reactivity of the core decreases, which decreases the fission neutron source from subcritical source multiplication. However, the lower water levels result in less shielding of the detector which tends to increase the detector count rate. These opposing effects must be represented adequately to obtain meaningful results. A 2-D, R-Z cylindrical model was developed for these calculations. A homogenized core with control rods and burnable poison present and a coolant boron content of 1030 ppm was assumed. This model results in a k_{eff} of 0.93 for the normal shutdown case and a k_{eff} of 0.88 for a largely uncovered one. The core barrel, thermal shield, downcomer region, reactor vessel, SRM, and biological shield were included in the model. A 16-energy-group neutron cross-section library in the Hansen-Roach² group structure was selected for the calculations. The calculational procedure included the following steps:

1. The gamma-ray source as a function of energy was obtained from an ORIGEN³ calculation.
2. The gamma-ray flux in regions where water is present was calculated using DOT-IV (Ref. 4) (P_3 , S_4 , 10 gamma groups).
3. The photoneutron source from the $D(\gamma, n)$ reaction was used as a source to calculate the core fission source with DOT-IV (16 neutron groups, diffusion theory). (The γ -n source was calculated to be ≈ 100 times the effective fixed source over the first few hours following shutdown.)
4. A shielding calculation was performed to obtain the detector count rate resulting from these sources. (P_0 or P_1 , S_4 or S_5 , 16 or 51 neutron groups.)

A model of the core void fraction as a function of axial position for different water levels was obtained from an experiment performed at the LOFT facility for the Electric Power Research Institute.⁵ The calculational procedure described above was repeated for several water levels to obtain the results shown in Fig. 6.28.2. Since boiling is assumed not to occur in the downcomer region, the core water level is higher than the downcomer water level when the core is uncovered. Thus, a shielding streaming path is present in the downcomer. The results in Fig. 6.28.2 indicate that the SRM count rate would exceed the normal shutdown count rate by a factor of 10 when the core is first uncovered and by a factor of 100 when about two-thirds of the core is exposed. Notice in Fig. 6.28.1 that the observed count rate increased by a factor of 100 from the minimum at 104 min (shortly after the pumps stopped) to the peak at about 130 min. The observed count rate increased by a factor of 10 at about the 110-min mark, which would suggest that the first core uncovering occurred at this time. This conclusion is consistent with temperature readings.

In summary, source range monitor readings have been calculated for several core water levels. These calculated results have been used to interpret the actual SRM readings at TMI-2.

* Research sponsored by the Electric Power Research Institute.

† Computer Sciences Division.

‡ Technology for Energy Corporation.

1. W. W. Engle, Jr., "A User's Manual for ANISN, A One-Dimensional Discrete Ordinates Transport Code with Anisotropic Scattering," K-1693, Computing Technology Center (1967).
2. G. E. Hansen and W. H. Roach, "Six and Sixteen Group Cross Sections for Fast and Intermediate Critical Assemblies," LAMS-2543 (1961).
3. M. J. Bell, "ORIGEN - The ORNL Isotope Generation and Depletion Code," ORNL-4628 (May 1973).
4. W. A. Rhoades, D. B. Simpson, R. L. Childs, and W. W. Engle, Jr., "The DOT IV Two-Dimensional Discrete-Ordinates Transport Code with Space-Dependent Mesh and Quadrature," ORNL/TM-6529, Oak Ridge National Laboratory (January 1979).
5. David Cain, EPRI-NSAC, Private Communication (September 1979).

Fig. 6.28.1. TMI-2 Source Range Monitor Count Rate After the Reactor Trip.

Fig. 6.28.2. Calculated Source Range Monitor Count Rate as a Function of Water Level for 120 min After Shutdown.

6.29. CALCULATIONS OF THE SKYSHINE GAMMA-RAY DOSE RATES FROM
INDEPENDENT SPENT FUEL STORAGE INSTALLATIONS (ISFSI)
UNDER WORST CASE ACCIDENT CONDITIONS*

J. V. Pace, III[†] S. N. Cramer J. R. Knight[†]

(Abstract of OERI/NUREG/TM-806 (NUREG/CR-0723), September, 1980)

Calculations of the skyshine gamma-ray dose rates from three spent fuel storage pools under worst case accident conditions have been made using the discrete ordinates code DOT-IV and the Monte Carlo code MORSE and have been compared to those of two previous methods. The DNA 37N-21G group cross-section library was utilized in the calculations, together with the Claiborne-Trubey gamma-ray dose factors taken from the same library. Plots of all results are presented. It was found that the dose was a strong function of the iron thickness over the fuel assemblies, the initial angular distribution of the emitted radiation, and the photon source near the top of the assemblies.

*Research sponsored by Nuclear Regulatory Commission.

[†]Computer Sciences Division.

6.30. THEORETICAL CHARACTERIZATION OF A DUAL PURPOSE GAMMA THERMOMETER*

T. J. Burns J. O. Johnson[†]

(Abstract of ORNL/TM-7567, in press)

A preliminary analytical and computational study was performed to investigate the potential of a modified gamma thermometer (GT) as both a power level monitor and fluid level monitor for a Pressurized Water Reactor (PWR). This study consisted of two fundamental parts: a radiation field characterization and a thermal-hydraulics analysis.

The radiation transport analysis was performed to determine the volumetric heat source within the GT due to gamma heating. Both fission product decay gammas and neutron induced gammas were included in the analysis. Further, a sensitivity analysis was performed to characterize the origin of the neutron induced gammas (by neutron reaction and material) contributing to the volumetric heat source. Utilizing this source, a series of thermal hydraulic calculations was performed to model certain reactor transients of interest (i.e., reactor scram, LOCA, etc.), in order to characterize the gamma thermometer response relative to power level monitoring and fluid level indication.

The results of this preliminary study confirm the feasibility of utilizing the GT as a dual function (power level and fluid level) measurement device. The study also indicates that each function can be accomplished virtually independent of the other. Therefore, the results provide encouragement and incentive to pursue the GT as a viable nuclear instrument.

*Research sponsored by Department of Energy.

[†]University of Tennessee, Department of Nuclear Engineering.

6.31. A STATISTICAL SENSITIVITY ANALYSIS OF A SIMPLE
NUCLEAR WASTE REPOSITORY MODEL*

Y. Ronen[†] J. L. Lucius[†] E. M. Oblow

(Abstract of ORNL/TM-7310, June, 1980)

This report represents a preliminary step in what should be a comprehensive sensitivity analysis of the modeling of a nuclear waste repository. The purpose of the complete analysis will be to determine which modeling parameters and physical data

are most important in determining key design performance criteria and then to obtain the uncertainty in the design for safety considerations. In the present report the theory for a statistical screening design methodology is developed for later use in the overall program. The theory was applied to the test case of determining the relative importance of the sensitivity of near field temperature distribution in a single-level salt repository to modeling parameters. The exact values of the sensitivities to these physical and modeling parameters were then obtained using direct methods of recalculations.

The sensitivity coefficients found to be important for the sample problem were the spent fuel thermal loading density, the distance between the rows of spent fuel assemblies and their effective width. Other important parameters were those related to the salt properties as a point of interest in the repository. In particular, the screening methodology singled out four parameters related to the salt as having high sensitivities: the salt conductivity, heat capacity and density, and the initial temperature of the salt at the point of interest. These predictions of the screening theory were confirmed by direct recalculations which also reveal the time behavior of these sensitivities. It was found that the sensitivities of the spent fuel power, the distance between the fuel assemblies, their width and the salt density and heat capacity increase (in absolute value) during the 50-year period studied. The sensitivity of the initial temperature decreases (in absolute value) whereas the sensitivity of the salt conductivity is important at the time the temperature of the salt is equal to the response temperature.

It was found that nonlinearity effects of the input parameters on the responses are negligible.

* Research sponsored by DOE Office on Nuclear Waste Isolation.

† On leave from Ben-Gurion University of the Negev, Beer Sheva, Israel.

‡ UCC-ND Computer Sciences Division.

ALTERNATE FUEL CYCLES

6.32. INTERIM ASSESSMENT OF THE DENATURED ^{233}U FUEL CYCLE: FEASIBILITY AND NONPROLIFERATION CHARACTERISTICS*

L. S. Abbott D. E. Bartine T. J. Burns C. Sege† I. Spiewak‡

(Abstract of ORNL-5388, December, 1978; ORNL-5388
Revised, December, 1979; and ORNL-5388
Executive Summary, December, 1979)

A fuel cycle that employs ^{233}U denatured with ^{238}U and mixed with thorium fertile material is examined with respect to its proliferation-resistance characteristics and its technical and economic feasibility. The rationale for considering the denatured ^{233}U fuel cycle is presented, and the impact of the denatured fuel on the performance of Light-Water Reactors, Spectral-Shift-Controlled Reactors, Gas-Cooled Reactors, Heavy-Water Reactors, and Fast Breeder Reactors is discussed. The scope of the R,D&D programs to commercialize these reactors and their associated fuel cycles is also summarized and the resource requirements and economics of denatured ^{233}U cycles are compared to those of the conventional Pu/U cycle. In addition, several nuclear power systems that employ denatured ^{233}U fuel and are based on the energy center concept are evaluated. Under this concept, dispersed power reactors fueled with denatured or low-enriched uranium fuel are supported by secure energy centers in which sensitive activities of the nuclear cycle are performed. These activities include ^{233}U production by Pu-fueled "transmuters" (thermal or fast reactors) and reprocessing. A summary chapter presents the most significant conclusions from the study and recommends areas for future work.

* Research sponsored by Department of Energy.

† Department of Energy.

‡ Engineering Technology Division.

6.33. THE USE OF THORIUM IN FAST BREEDER REACTORS*

D. E. Bartine

(Abstract of paper in *Nuclear Cross Sections for Technology*, NBS Special Publication 594, p. 719, 1980; also Abstract of paper presented by T. J. Burns at Workshop on Thorium Utilization in the Nuclear Power Program, MITRE Corporation, October 26-27, 1979)

Recently several fuel cycles involving thorium have been suggested for use in fast breeder reactors. These cycles involve the use of thorium in fuels containing ^{233}U and fissile plutonium and the use of both internal and conventional thorium blanket elements. Studies were performed in the Engineering Physics Division at ORNL to determine the performance of fast breeder reactors utilizing such cycles. In addition, there is a current effort toward analyzing reaction rates, spectra, and integral measurements of prototypic fast reactor configurations involving thorium. These experiments were performed at the PROTEUS facility of the EIR laboratory at Würenlingen, Switzerland, and at the Tower Shielding Facility at ORNL. The analysis of these experiments provides insight regarding data needs for fast reactor applications involving the thorium cycle.

Results of the fast breeder fuel cycle analysis indicate a significant penalty from replacing Pu/UO_2 fuel with $\text{U-233}/\text{ThO}_2$ fertile blanket elements. Preliminary analysis of the experiments indicates improved agreement with neutron spectra involving deep penetration in ThO_2 radial blankets by utilizing ENDF/B-V thorium cross section data as compared with ENDF/B-IV. However, thorium capture rates now appear significantly underpredicted.

*Research sponsored by DOE Office of Reactor Research and Technology.

MAGNETIC FUSION ENERGY PROGRAM

6.34. SHIELDING OF FUSION REACTORS*

R. G. Alsmiller, Jr.

(Abstract of paper in *Nuclear Cross Sections for Technology*, NBS Special Publication 594, p. 239, 1980)

The blanket and shield assemblies of fusion reactors will contain a significant number of very sizable penetrations (neutral beam injection ducts, pumping ports, etc.). The combination of high-energy neutrons and large penetrations will introduce severe design problems that are quite different from those encountered previously. Fusion reactors with their penetrations are very complex geometric structures and in calculating nuclear effects (heating, activation, etc.) tradeoffs must be made between computing efficiency and the accuracy in the geometric modeling. The types of problems that arise due to large penetrations will be illustrated by the calculations that have been carried out to aid in the design of the shielding for the neutral beam injectors of the Tokamak Fusion Test Reactor being built at Princeton University.

*Research sponsored by DOE Office of Fusion Energy.

6.35. SHIELDING CALCULATIONS FOR THE TFTR NEUTRAL-BEAM INJECTORS*

R. T. Santoro R. A. Lillie R. G. Alsmiller, Jr. J. M. Barnes†

(Reprint of *Trans. Am. Nucl. Soc.* 32, 661, 1979; also *Summary of ORNL/TM-6949*, July, 1979, and *Nucl. Tech.* 47, 412, 1980)

Two-dimensional (2-D) neutronics calculations have been carried out to determine the shielding requirements for the neutral-beam injectors to be used with the Tokamak Fusion Test Reactor (TFTR). Neutral deuterium is injected into the tritium plasma through a

duct that passes through a concrete pillbox-shaped shield (igloo) that surrounds the reactor. The reactor and igloo are housed in a large concrete building (test cell). The thickness of the concrete in the igloo and in the roof and walls of the test cell are sufficiently thick to reduce the biological dose rate from neutrons and secondary gamma rays outside the test cell to an acceptable limit of 0.5 mrem/D-T pulse. However, some of the neutrons produced in the D-T pulse stream through the injection duct resulted in an increase in the dose rate on the roof and outside the test cell wall. The purpose of this study was to determine the location and thickness of additional concrete shielding around the neutral-beam injector necessary for maintaining the dose rate outside the test cell at the acceptable limit.

Two series of calculations were performed. In the first, only the igloo and test cell were included in the calculational model to determine the biological dose rate outside the test cell with no injectors present. In the second, the injector and the test cell were modeled to determine the dose rate outside the test cell from radiation streaming through the injection duct. The details of many of the calculational procedures may be found in Ref. 1 and are only briefly summarized here.

The D-T neutron source distribution was taken to be that at strong post-compression of the plasma² and was transported using the 2-D discrete ordinates code DOT³ with the TFTR, igloo, and test cell modeled in r-z geometry with toroidal symmetry about the z-axis. The flux distributions from this calculation were folded with neutron⁴ and gamma-ray⁵ flux-to-dose conversion factors to obtain the biological dose rates on the test cell outer surfaces.

The contribution to the dose rate from neutrons streaming through the injection duct and from the radiation leaking through the igloo wall and interacting in the injector were obtained in a second calculation. The neutral-beam injector and the test cell were modeled in r-z geometry with symmetry about the axis of injection. The source for this analysis was obtained by processing the outward-directed angular flux at the surface of the igloo obtained in the calculation using the toroidal geometry with the interface code DOMINO.⁶ The normalized probability distribution functions in energy, space, and angle generated by DOMINO were sampled using the MORSE code⁷ to obtain the radiation current through a 200-cm-radius disk located in front of the injector. These data were then processed with the code GRTUNCL⁸ to obtain the first-collision and uncollided flux distributions of the radiation leaking through the igloo that interacted in the injector. The neutrons from the plasma streaming directly through the duct were also calculated using GRTUNCL to obtain the uncollided flux and first-collision source in the injector and test cell wall that are in line-of-sight with the plasma. The direct streaming and leakage distributions were appropriately combined and used as the source term in DOT for completing the radiation transport through the injector.

All of the calculations were carried out using a 35n, 21γ energy group, P₃-expanded transport cross-section library obtained by collapsing the 171n, 36γ Vitamin C data set.⁹ An S₈ angular quadrature was used in all of the DOT calculations. The dose rates were normalized to a source strength of 3.5×10^{18} n/D-T pulse.

The dose equivalent per pulse as a function of distance along the test cell roof (from the roof center to the outer edge) and along the wall (from the injector centerline to the roof) is shown in Figs. 6.35.1 and 6.35.2, respectively. In both figures, the curve labeled "without injector" was obtained from the calculation including only the reactor, igloo, and test cell and is the dose rate outside the test cell with no injector present. The curves labeled "unshielded injector" and "shielded injector" were obtained from the calculation including only the injector and test cell and these represent the additional dose outside the test cell due to the presence of the injector. For the shielded injector, 30 cm of concrete line the lateral surface of the injector and 60 cm of concrete is used to attenuate the neutrons streaming out of the back of the injector. The total dose is obtained by adding the curve without the injector and either of the two remaining curves.

The TFTR is designed to operate with several neutral-beam injectors. Therefore, the curves obtained when the injector is present must be multiplied by the number of injectors and then added to the curve obtained without the injector. This may result in a slight overestimate of the dose since all of the injectors are not at the same distance from a

Fig. 6.35.1. Dose Equivalent Rate as a Function of Distance Along the Test Cell Roof.

Fig. 6.35.2. Dose Equivalent Rate as a Function of Distance Along the Test Cell Wall.

given point on the roof. With this in mind, it appears that some shielding of the lateral surfaces of the injector may be required to maintain the dose rate on the roof at the acceptable level. The amount and location of the shielding will depend on orientation of the injectors about the reactor. It is necessary, however, to include the 60-cm-thick shield behind the injectors to reduce the contribution to the dose outside the wall from neutrons streaming directly through the injection duct.

* Research sponsored by DOE Office of Fusion Energy.

† UCC-ND Computer Sciences Division.

1. R. T. Santoro, R. A. Lillie, R. G. Alsmiller, Jr., and J. M. Barnes, "Two- and Three-Dimensional Neutronics Calculations for the TFTR Neutral Beam Injectors," ORNL/TM-6354, Oak Ridge National Lab. (1978).
2. B. Pritchard, Princeton Plasma Physics Laboratory, Private Communication.
3. W. A. Rhoades and F. R. Mynatt, "The DOT-11 Two-Dimensional Discrete Ordinates Code," ORNL/TM-4280, Oak Ridge National Lab. (1973).
4. NCRP Report No. 38, "Protection Against Neutron Radiation," National Council on Radiation Protection and Measurements (1971).
5. H. C. Claiborne and D. K. Trubey, Nucl. Technol. 8, 450 (1970).
6. M. B. Emmett, C. E. Burgart, and T. J. Hoffman, "DOMINO, A General Purpose Code for Coupling Discrete Ordinates and Monte Carlo Radiation Transport Calculations," ORNL-4835, Oak Ridge National Lab. (1973).
7. M. B. Emmett, "The MORSE Monte Carlo Radiation Transport System," ORNL-4972, Oak Ridge National Lab. (1975).
8. R. L. Childs, Oak Ridge National Lab., Private Communication.
9. ORNL/R5IC-37, Radiation Shielding Information Center, Oak Ridge National Lab. (1975), available as DLC-41/Vitamin C.

6.36. DOSE RATES FROM INDUCED ACTIVITY IN THE TFTR TEST CELL*

R. G. Alsmiller, Jr. J. Barish[†] R. T. Santoro R. A. Lillie
 J. M. Barnes[†] M. M. H. Ragheb[‡]

[Reprint of Trans. Am. Nucl. Soc. 32, 668, 1973; also summary of ORNL/TN-6304, August, 1979, and Nucl. Tech. 48, 187 (1980)]

The tokamak fusion test reactor (TFTR), which will operate on a D-T cycle, is being constructed at Princeton University. In this paper calculated results of the induced activity in the TFTR test cell are presented. Calculated results similar to those presented here have been presented previously by Friedenber¹. In the work of Friedenber the effects of a neutral-beam injector and the large penetrations through the primary shield needed to accommodate neutral-beam injection were neglected, while here they are taken into account. Furthermore, the calculational procedure used to obtain the results presented here differs from that of Friedenber in that the photon transport calculations are carried out by Monte Carlo methods rather than discrete ordinates methods. The use of Monte Carlo methods allows all of the time-dependent calculations to be carried out after the photon transport calculations² and greatly facilitates the consideration of a large number of D-T pulse sequences and times after machine shutdown.

In Fig. 6.36.1 a very schematic diagram of the TFTR test cell is shown. The scalar neutron fluxes used here are those obtained previously by Santoro et al.,³ for the same geometry as that considered here. The compilation of Muir⁴ was the primary source of activation cross-section data, but a few reaction cross sections from ENDF/B-IV⁵ were used.

The photon spectra from each radioactive nuclei considered in the calculation were obtained from the Evaluated Nuclear Data Files that are available from the Nuclear Data Project at the Oak Ridge National Laboratory.⁶ Calculations of photon transport were performed with the Monte Carlo code MORSE⁷ using cross-section data taken from Ref. 8. The photon fluxes were converted to dose equivalent rate using the flux-to-dose equivalent rate conversion factors of Claiborne and Trubey.⁹

In Fig. 6.36.1 the numbers between the arrows indicate the approximate positions where the activation dose equivalent rates will be presented, and the arrows indicate the spatial intervals over which the dose rates have been averaged. In Table 6.36.1 the total activation dose equivalent rates, i.e., the dose rates from all residual nuclei considered, are presented for the case of 1000 D-T pulses applied at the rate of 100 D-T pulses per day for each of 10 consecutive days. The duration of a D-T pulse is 0.5 s and the time between pulses is 5 min. In the table the dose rates are given for 1 h, 1 day, and 1 week after the last pulse. The error on each entry in the table is the statistical error, one standard deviation, expressed in percent. Results are presented separately for the case of the test cell with no injector present and for the contribution from an injector. The geometries are such that the two contributions are additive, but it must be understood that when the two contributions are additive only an upper limit on the dose rate is obtained. This is because in the photon transport calculation "without injector" the injector structure is not present to attenuate the photons. The calculated results when there is no injector present are comparable to those obtained by Friedenber,¹ but are not exactly the same because the concrete compositions used here are not exactly the same as those used in the calculations of Friedenber.

Calculated results similar to those given in Table 6.36.1 for a variety of different pulse repetition sequences, times after the last pulse, and other positions in the test cell have also been obtained and will be presented. Furthermore, for each total dose equivalent rate obtained the contribution to this dose equivalent rate from each residual nuclei considered is available and some of this information will also be presented.

*Research sponsored by DOE Office of Fusion Energy.

[†]UCC-ND Computer Sciences Division.

[‡]University of Wisconsin.

Table 6.36.1. Dose Equivalent Rate vs Time After Last Pulse
100 Pulses on Each of Ten Consecutive Days
Pulse Length = 0.5 s, Time Between Pulses = 5 min, Dose Equivalent Rate (mrem/h)

Position ^a	1 Hour After Last Pulse		1 Day After Last Pulse		1 Week After Last Pulse	
	Test Cell Without Injector	Injector Contribution	Test Cell Without Injector	Injector Contribution	Test Cell Without Injector	Injector Contribution
1	$1.9 \cdot 10^2 \pm 11^b$	$1.1 \cdot 10^{-2} \pm 19$	$4.7 \cdot 10^1 \pm 14$	$3.8 \cdot 10^{-3} \pm 20$	$8.8 \cdot 10^{-1} \pm 11$	$2.1 \cdot 10^{-5} \pm 19$
2	$6.8 \cdot 10^1 \pm 11$	$9.0 \cdot 10^{-2} \pm 38$	$1.7 \cdot 10^1 \pm 13$	$1.0 \cdot 10^{-2} \pm 24$	$2.8 \cdot 10^{-1} \pm 9$	$3.7 \cdot 10^{-4} \pm 38$
3	$6.5 \cdot 10^1 \pm 15$	$1.6 \cdot 10^0 \pm 17$	$1.6 \cdot 10^1 \pm 15$	$4.9 \cdot 10^{-2} \pm 11$	$3.2 \cdot 10^{-1} \pm 12$	$9.2 \cdot 10^{-3} \pm 31$
4	$6.5 \cdot 10^1 \pm 17$	$2.0 \cdot 10^2 \pm 5$	$1.9 \cdot 10^1 \pm 22$	$6.0 \cdot 10^1 \pm 6$	$4.4 \cdot 10^{-1} \pm 18$	$1.9 \cdot 10^0 \pm 3$
5	$9.9 \cdot 10^1 \pm 11$	$1.5 \cdot 10^1 \pm 17$	$2.4 \cdot 10^1 \pm 14$	$4.2 \cdot 10^{-1} \pm 7$	$7.7 \cdot 10^{-1} \pm 8$	$2.2 \cdot 10^{-1} \pm 10$
6	$5.6 \cdot 10^1 \pm 17$	$1.8 \cdot 10^2 \pm 9$	$1.4 \cdot 10^1 \pm 22$	$4.7 \cdot 10^0 \pm 3$	$4.5 \cdot 10^{-1} \pm 18$	$1.9 \cdot 10^0 \pm 5$
7	$3.1 \cdot 10^1 \pm 17$	$4.7 \cdot 10^1 \pm 4$	$9.5 \cdot 10^0 \pm 16$	$1.2 \cdot 10^2 \pm 2$	$1.7 \cdot 10^{-1} \pm 24$	$5.9 \cdot 10^{-1} \pm 1$
8	$3.6 \cdot 10^1 \pm 26$	$5.9 \cdot 10^{-1} \pm 9$	$1.1 \cdot 10^1 \pm 28$	$1.4 \cdot 10^{-1} \pm 8$	$1.4 \cdot 10^{-1} \pm 27$	$4.2 \cdot 10^{-3} \pm 17$
9	$2.0 \cdot 10^1 \pm 13$	$2.0 \cdot 10^{-1} \pm 88$	$5.6 \cdot 10^0 \pm 15$	$6.8 \cdot 10^{-2} \pm 90$	$1.3 \cdot 10^{-1} \pm 50$	$1.8 \cdot 10^{-4} \pm 43$
10	$5.3 \cdot 10^{-3} \pm 31$	$1.4 \cdot 10^{-3} \pm 17$	$1.8 \cdot 10^{-3} \pm 32$	$4.7 \cdot 10^{-4} \pm 17$	$5.0 \cdot 10^{-6} \pm 20$	$7.6 \cdot 10^{-7} \pm 16$
11	$8.2 \cdot 10^{-2} \pm 13$	$1.2 \cdot 10^{-3} \pm 21$	$2.8 \cdot 10^{-2} \pm 13$	$4.2 \cdot 10^{-4} \pm 21$	$6.4 \cdot 10^{-5} \pm 10$	$9.0 \cdot 10^{-7} \pm 13$
12	$1.2 \cdot 10^{-2} \pm 29$	$3.6 \cdot 10^{-3} \pm 14$	$3.9 \cdot 10^{-3} \pm 28$	$1.2 \cdot 10^{-3} \pm 15$	$6.4 \cdot 10^{-6} \pm 26$	$1.9 \cdot 10^{-6} \pm 12$

^aSee Fig. 6.36.1.

^bStatistical error, one standard deviation, expressed in percent.

1. R. A. Friedenber, "Construction of Isodose Contour Maps for the TFTR," Trans. Am. Nucl. Soc. 28, 657 (1978).
2. R. G. Alsmiller, Jr., T. A. Gabriel, and J. Barish, "Photon Dose Rate from Induced Activity in the Beam Stop of a 400 GeV Proton Accelerator," Nucl. Instr. Methods, 155, 399 (1978).
3. R. T. Santoro et al., "Shielding Calculations for the TFTR Neutral Beam Injectors," Trans. Am. Nucl. Soc., 32, 661 (1979).
4. D. W. Muir, "DLC-33 Data Library MONTAGE," Radiation Shielding Information Center, Oak Ridge National Laboratory (1975).
5. D. J. Garber and C. Brewster, "ENDF/B Cross Sections," BNL-17100 (ENDF-200), 2nd ed. (1975).
6. W. B. Ewbank, "Evaluated Nuclear Structure Data Files (ENSDF) for Basic and Applied Research," Proc. Fifth CODATA Conf. (June 28-July 1, 1976); see also, D. C. Kocher, W. B. Ewbank, and M. J. Martin, "Standardized Radioactivity Decay Data Sets for Use in Radioactivity Dosimetry," IAEA Symposium on National and International Standardization of Radiation Dosimetry, Atlanta, GA (Dec. 5-9, 1977).
7. M. B. Emmett, "The MORSE Monte Carlo Radiation Transport Code System," ORNL-4972, Oak Ridge National Laboratory (1975).
8. D. M. Plaster, R. T. Santoro, and W. E. Ford, III, "Coupled 100-Group Neutron and 21-Group Gamma-Ray Cross Sections for EPR Calculations," ORNL/TM-4872, Oak Ridge National Laboratory (1975).
9. H. C. Claiborne and D. K. Trubey, "Gamma Ray Dose Rates in a Slab Phantom," Nucl. Am. Tech. 8, 450 (1970).

Fig. 6.36.1. Schematic Diagram of TFTR Test Cell with a Neutral-Beam Injector.

6.37. ESTIMATED NUCLEAR EFFECTS IN THE NEUTRON BEAM INJECTORS OF A LARGE FUSION REACTOR*

R. A. Lillie R. T. Santoro R. G. Alsmiller, Jr.

(Summary of ORNL/TM-7526, in press)

Estimates are given for the nuclear heat loads on the cryopanel, radiation damage (energy deposition rate) in ion gun insulators, and dose equivalent rates from induced activity in the components for the Engineering Test Facility (ETF) neutral beam injectors. The estimates have been obtained by scaling similar results, obtained by careful neutronics analysis for the Tokamak Fusion Test Reactor (TFTR). The approximate nature of the scaling procedure introduces considerable uncertainty in the results, but they are, hopefully, correct to within an order of magnitude and may be substantially more accurate.

The total nuclear heat loads on the cryopanel in a single ETF neutral beam injector range between 12.0 and 67.5 watts with a shield plug and between 750 and 4250 watts without a shield plug. The total nonnuclear heat load on the cryopanel in a single TFTR neutral beam injector is reported to be 60 watts. For the purposes of this study, it was assumed that the ETF and TFTR have similar neutron beam injectors and cryopanel. Based on this assumption, a nonnuclear heat load of 60 watts should also be seen by the cryopanel in a single ETF neutral beam injector. These heat load values strongly suggest the use of shield plugs, for without shield plugs, the capital and operating costs associated with nuclear heating dominate the overall neutral beam injector cryogenic systems costs. Based on the premise that shield plugs are employed in the ETF injector ducts, the nuclear heat loads estimated in this analysis for the ETF NBI cryopanel do not appear to present any major problems from either an operational or cost viewpoint.

The effects of radiation damage on the ion gun insulators is dependent on the damage threshold of the particular type of insulator that is ultimately used. If a damage threshold of 10^5 rads is assumed with no shield plug in the injector duct then the insulator will begin to fail after approximately 5.4 days of continuous operation and with a shield plug the insulator will fail after approximately 340 days of continuous operation.

The TFTR neutral beam injectors are shielded by 30.5 cm of concrete on the sides and 61 cm of concrete at the rear, so this is the shielding used in obtaining the estimates given here. With no shield plug in the injector duct the dose equivalent rates from induced activity just outside of the shielding are of the order of 10^5 mrem/hr, 1 hour after the reactor is turned off. With a shield plug this dose is reduced by a factor of approximately 63. Dose equivalent rates for various operating scenarios and time after reactor shutdown are given in the report.

All of the results presented here indicate that a shield plug in the injector duct is very desirable. However, the use of shield plugs will most certainly introduce mechanical and maintenance problems. In addition, these plugs exclude the desirable option of a beam driven tokamak design. An alternate approach to reducing the radiation levels in the sensitive beam line components would be to place shadow shields in the injectors. The determination of the size, material, and placement of such shields is, however, beyond the scope of this paper. An analysis of this type would require extensive radiation transport calculations coupled with molecular flow calculations since shadow shields will most definitely cause changes in beam line performance.

As noted above, the approximate nature of the scaling procedures used in this work introduces considerable uncertainty in the results. The importance of this statement cannot be overemphasized. Although the approximations used in obtaining the scale factors introduce very little error, as shown in the appendix, the uncertainty in the calculated results associated with the assumptions upon which the scale factors are based cannot be easily assessed. For this reason, a strong need for supportive detailed radiation transport calculations definitely exists.

*Research sponsored by DOE Office of Fusion Energy.

6.38. ONE-DIMENSIONAL GAMMA-RAY SHIELDING CALCULATIONS FOR THE EBT-P*

R. A. Lillie T. A. Gabriel B. L. Bishop[†] V. C. Baker[†]

(Reprint of Trans. Am. Nucl. Soc., 34, 642, 1980; also summary of ORNL/TN-7156, November, 1980; and paper to be published in Nuclear Technology.)

Due to the expected large loss of electrons on the magnetic coil assemblies and other components of the proposed EBT-P plasma device, the induced gamma-ray field from bremsstrahlung will be very intense. These gamma rays will yield increased heating loads on the superconducting cryogenic coils as well as produce a significant biological hazard. In this summary, the results from a series of one-dimensional (1-D) calculations in which the gamma-ray heating loads were determined are presented for several coil shield configurations. Also, 1-D results which indicate the level of biological dose for varying thicknesses of either lead or concrete that have been proposed for the primary shielding are given.

The transport of electrons, positrons, and gamma rays through the magnet assembly was carried out using the EGS-PEGS code system.¹ This Monte Carlo code package takes into account all physical processes which are important in the energy range of interest.

The EGS-PEGS code system could have been used for the entire set of calculations, except for the large statistical uncertainties associated with the calculated results at large shielded distances from the radiation source. To circumvent this problem, the EGS-PEGS code system was only used to generate gamma-ray spectra. These spectra were then input to the 1-D discrete ordinates transport code ANISN.² This code has been used extensively for 1-D shielding calculations and is very applicable to deep penetration problems.

The 1-D geometries employed in EGS-PEGS and ANISN and in both the coil heating and biological dose calculations consisted of a series of infinitely long concentric cylinders as shown in Fig. 6.38.1. In the heating calculations (Fig. 6.38.1a), electrons were assumed to be isotropically incident on the front face of the 0.01-m-thick aluminum liner for the transport utilizing the EGS-PEGS code system. Although the bremsstrahlung gamma rays produced by the electrons were somewhat smeared radially throughout the aluminum, the gamma-ray source was placed at a radius of 0.213 m for the ANISN calculations.

The biological dose calculations were performed using the geometry illustrated in Fig. 6.38.1b. In these calculations, the biological dose rates for up to 0.305 m of lead and 1.83 m of concrete were obtained with and without 0.0318 m of ²³⁸U coil shielding. The bremsstrahlung spectra used in the heating calculations were again used for these calculations.

Fig. 6.38.1. One-Dimensional Geometric Models.

The rate at which electrons are lost from the plasma was assumed to be proportional to a Maxwellian distribution weighted by $E^{3/2}$; i.e.,

$$\text{Loss} = A \times \exp(-E/kT)/E,$$

where E represents the electron energy and T represents the plasma temperature. This distribution was normalized to a maximum power loss of 1 MW yielding a normalization constant of $A = 6.242 \times 10^{18}/kT$.

The cumulative bremsstrahlung spectra for the various kT values were obtained from the following expression:

$$h(E_Y, kT) = \frac{\int_{0.239}^{10 \text{ MeV}} g(E_Y, E_e) \exp(-E_e/kT) / E_e dE_e}{\int_{0.239}^{10 \text{ MeV}} \exp(-E_e/kT) / E_e dE_e}$$

where $g(E_Y, E_e)$ represents the bremsstrahlung spectrum produced from electrons of energy E_e . The integral was also extended to 20 MeV for a kT of 2.0 MeV assuming the bremsstrahlung spectra from electrons with energies greater than 10 MeV were the same as that produced by 10-MeV electrons. This spectrum will be denoted by the use of an * above the kT value.

The total energy deposition rates obtained are presented in Fig. 6.38.2 for electron temperatures of 1.0, 1.5, 2.0, and 2.0* MeV as a function of coil shield thickness. The energy deposition rate for the tungsten shield was only calculated using the $kT = 2.0^*$ -MeV spectrum since this spectrum yields the greatest heating.

The calculated biological dose rates as a function of lead shield thicknesses are presented in Fig. 6.38.3. These results were obtained with and without 0.0318 m of ^{238}U coil shielding for the electron temperatures of interest. The isotropic gamma-ray sources used in these calculations were the same as those used in the heating calculations. For a kT value of 2.0* MeV in the absence of any ^{238}U coil shielding, 0.318 m of Pb is required to reduce the biological dose rate to 2.5 mrem/h. (The corresponding amount of concrete is 1.92 m.) Since no reduction of the gamma-ray spectrum was assumed to occur due to shielding by the components of the machine, these results should represent the maximum required shielding to obtain a 2.5 mrem/h radiation level.

Fig. 6.38.2. Total Energy Deposition Rate in Cu Coils vs Coil Shield Thickness for Several Electron Temperatures.

Fig. 6.38.3. Biological Dose Rate vs Lead Shield Thickness With and Without 0.0318 m of ^{238}U Coil Shield for Several Electron Temperatures.

²Since very low energy electrons do not contribute significantly to either the gamma-ray heating or the biological dose, only electrons with energies above 0.239 MeV were considered.

* Research sponsored by DOE Office of Fusion Energy.

† UCC-ND Computer Sciences Division.

1. R. L. Ford and W. R. Nelson, "The EGS Code System: Computer Programs for Monte Carlo Simulation of Electromagnetic Cascade Showers (Version 3)," SLAC-210, Stanford Linear Accelerator Center (1978).
2. W. W. Engle, Jr., "A Users Manual for ANISN, A One-Dimensional Discrete Ordinates Code with Anisotropic Scattering," ORGDP-K-1693, Oak Ridge Gaseous Diffusion Plant (1967).

6.39. CALCULATED IRRADIATION RESPONSE OF MATERIALS USING FISSION REACTOR (HFIR, ORR, AND EBR-II) NEUTRON SPECTRA*

T. A. Gabriel B. L. Bishop[†] F. W. Wiffen[‡]

(Abstract of ORNL/TM-6361, August, 1979)

In order to plan radiation damage experiments in fission reactors keyed toward fusion reactor applications, it is necessary to have available for these facilities displacement per atom (dpa) and gas production rates for many potential materials. This report supplies such data for the elemental constituents of alloys of interest to the United States fusion reactor alloy development program. The calculations are presented for positions of interest in the HFIR, ORR, and EBR-II reactors. DPA and gas production rates in alloys of interest can be synthesized from these results.

* Research sponsored by DOE Office of Fusion Energy.

† UCC-ND Computer Sciences Division.

‡ Metals and Ceramics Division.

6.40. DESIGN OF MATERIALS IRRADIATION EXPERIMENTS UTILIZING SPECIAL TAILORING*

T. A. Gabriel R. A. Lillie B. L. Bishop[†]

(Reprint of Trans. Am. Nucl. Soc. 34, 228, 1980)

The helium production to displacement per atom (He/DPA) ratio expected at the first wall of a fusion reactor for stainless-steel alloys can be, within reasonable limits, reproduced in "real" time in fission reactors such as the Oak Ridge Research Reactor (ORR) due to the helium production characteristics of $\text{Ni}(^{58}\text{Ni} + n_{\text{th}} \rightarrow ^{59}\text{Ni} + n_{\text{th}} + ^{56}\text{Fe} + \alpha)$. The reproduction of the He/DPA ratio can be accomplished by intermittent modification of the thermal-to-fast neutron flux ratio since the He production will be dominated by the thermal fluence and the fast fluence will determine the DPA.¹ This report summarizes some of the neutronic calculations that are being carried out to determine the amount of change as a function of time necessary in the thermal-to-fast ratio and the design of the experimental capsules that will produce the needed changes.

The results of the preliminary calculations, shown in Fig. 6.40.1, are for one melt of stainless steel and indicate the level of changes required in the thermal flux and DPA rate. There is nothing unique about the data as other modifications of the thermal flux and DPA rate can yield the same desired end points. The solid straight line represents the He vs DPA expected at the first wall of a fusion reactor. Approximately 10 DPAs and 140-ppm helium per year will be obtained for this composition of stainless steel for a 1 MW/m² wall loading. To obtain this level of damage in the ORR will require ~1.3 yr of irradiation. The □'s, ■'s, ○'s, and ●'s represent the calculated data obtained using a representative ORR neutron spectrum, but with variations of the thermal flux and DPA rates.

(These data have been extended out to ~90 DPAs.) Initially, the thermal flux is increased by 20% and the DPA rate is decreased by 20%. Following this initial period, the remainder of the time of irradiation requires various reductions in the thermal flux and various increases in the DPA rates.

The data in Fig. 6.40.1 only indicate the level of change required in the thermal flux and DPA rates. Methods to yield the desired changes were obtained from 3-D neutron diffusion calculations using the VENTURE² computer code with the ORR core configurations shown in Fig. 6.40.2. The experimental capsule, which for these calculations has been assumed to be 40% stainless steel and 60% void, will be located in the center of the C-3 core piece. The calculations were carried out for various Al plus H₂O (ORR core 1a) and various Ta, Al, and H₂O (ORR core 1b) compositions which comprise the core piece. The variations of the thermal-neutron flux and DPA rate are shown in Fig. 6.40.3a. These data have been used to preliminarily specify the design of the core piece for the first two periods of irradiation. During the first period of irradiation, as presently planned, the core piece will be composed of ~37% Al and ~63% H₂O since this composition yields the changes suggested by the data given in Fig. 6.40.1. During the second period, the core piece will be composed of 100% Al. The changes in the thermal-neutron flux and the DPA rate resulting from adding additional fuel (20 g to B-3, 20 g to C-4, and 20 g to D-3) around the C-3 core piece are shown on the left side of Fig. 6.40.3a. The calculations were done for a 100% Al core piece surrounding the experimental capsule. The results indicate that the thermal flux can be reduced by ~4% and the DPA rate can be increased by ~6%.

Fig. 6.40.1. He vs DPA Expected on First Wall of a Fusion Reactor and What Can Be Obtained in the ORR Reactor by Spectral Tailoring.

Fig. 6.40.2. ORR Core Loading for Neutronics Calculations.

Fig. 6.40.3. Variation in the DPA and Thermal-Neutron Flux in the C-3 Position in ORR as a Function of Core Piece Composition and Fuel Loading Around C-3: (a) $H_2O + Al$ Core Piece, (b) $Ta + Al + H_2O$ Core Piece.

The results of the calculations involving the Ta core piece are shown in Fig. 6.40.3b. As can be seen, the thermal-neutron flux is reduced substantially, by more than an order of magnitude. The displacement rate is also reduced, but only by about 40%. Since the Ta core piece is to be used during the later phases of the irradiation experiment, it is desired that the thermal flux be reduced while the displacement rate is either increased or at least held to a very moderate decrease. To compensate for this reduction in the displacement rate, the 98% Ta core piece calculation was repeated with additional fuel added to the core pieces around C-3: 55 g to B-3, 30 g to B-4, 75 g to C-4, and 85 g to D-3. This additional fuel resulted in about a 10% further decrease in the thermal flux but also yielded a substantial increase of about 20% in the displacement rate. From the data presented, the use of the ORR reactor to reproduce in "real" time the He/DPA expected rate in fusion reactors appears very promising.

* Research sponsored by DOE Office of Fusion Energy.

† UCC-ND Computer Sciences Division.

1. T. A. Gabriel, B. L. Bishop, and F. W. Wiffen, "Calculated Irradiation Response of Materials Using Fission Reactor (HFIR, ORR, and EBR-II) Neutron Spectra," ORNL/TM-6361, (August 1979).
2. D. R. Vondy, T. B. Fowler, and G. W. Cunningham, "VENTURE, A Code Block for Solving Multigroup Neutron Problems Applying Finite-Diffusion-Theory Approximations to Neutron Transport," ORNL-5062 (October 1975).

6.41. MONTE CARLO SIMULATION OF NEUTRAL PARTICLE TRANSPORT IN A NEUTRAL-BEAM INJECTOR*

R. A. Lillie R. G. Alsmiller, Jr. T. A. Gabrieli
R. T. Santoro S. W. Schwenterly†

(Reprint of Trans. Am. Nucl. Soc. 33, 43, 1979)

The overall design of neutral-beam injectors, which will be used to inject high-energy neutral deuterons into the plasma of fusion reactors, is heavily dependent on the behavior of low-energy stray neutrals. These stray neutrals impede the flow of high-energy deuterons into the plasma and thus must be removed from the beam line geometry with cryogenic pumps. Altering the design, location, and/or orientation of the cryopumps may cause direct changes in the overall neutral-beam injector performance. Analytic determination of the system characteristics describing these changes requires an accurate simulation of stray neutral particle transport utilizing a detailed model of a neutral-beam injector. The results from calculations using an existing Monte Carlo radiation transport code and employing such a model are summarized here.

The geometric model employed in these calculations consisted of a fairly detailed representation of the PDX-prototype neutral-beam injector currently being tested at the Oak Ridge National Laboratory. The primary components of the model included the neutralizer tube, ion bending magnet and beam dump, beam line vacuum enclosure, drift chamber, calorimeter, and the various cryogenic pump assemblies. Within each pump assembly, the major coolant tubes, end caps, liquid-helium-cooled pumping panels, and the liquid-nitrogen-cooled chevrons, which shield the pumping panels from hot neutrons, were modeled in great detail.

The stray neutral particle transport calculations were performed using a slightly modified version of the MORSE Monte Carlo radiation transport code.¹ Unlike conventional radiation transport problems, neutral particle transport simulation requires an essentially media-free environment where particle-media interactions predominantly occur only at the surfaces of the various components within the neutral-beam enclosure. These interactions were treated by incorporating a variety of internal boundary conditions into an existing external boundary condition routine. The major boundary condition imposed on the component surfaces utilized the assumption of molecular roughness. Neutrals striking these surfaces were reflected independent of their incidence direction according to the cosine law.² Neutrals incident on the liquid-helium-cooled pumping panels were removed from the system by assuming a 0.9 sticking or capture probability. The 10% which were not captured, i.e., did not stick, were assumed to emerge at angles equally distributed within ± 10 deg of 75 deg from the panel normal.

Additional modifications were required to account for the change in neutral temperature which occurs at each surface collision and to obtain estimates of the stray neutral pressure using the ideal gas law. Neutrals of temperature T_1 striking a surface of temperature T_0 were assumed to emerge at temperature T_2 given by

$$T_2 = T_1 - \alpha(T_1 - T_0) \quad , \quad (1)$$

where α represents the surface accommodation coefficient which normally varies between 0.9 and 1.0. The stray neutral pressure p_j within volume V_j was estimated using

$$p_j = \text{constant} \times \sum_i \frac{RT_{i,j} T_i}{V_j} \quad , \quad (2)$$

where $RT_{i,j}$ represents the residence time of the i 'th neutral of temperature T_i in volume V_j .

A few of the results from the Monte Carlo Calculations are given in Table 6.41.1. The stray neutral source in these calculations was uniformly distributed over the entrance of the neutralizer tube. Initial directions were obtained by sampling from a cosine distribution about the entrance normal and an initial temperature of 1000K was assumed for each source neutral. Temperatures of 4 and 77K were maintained on the liquid-helium-cooled

pumping panels and liquid-nitrogen-cooled chevrons, respectively, with all other surfaces assumed to be at room temperature; i.e., 293K. The accommodation coefficients were assumed to be 1.0 for all surfaces and a sticking probability of 1.0 was imposed on the pumping panels.

Table 6.41.1. Neutral-Beam Injector System Characteristics

Geometry	Neutrals Captured/ Source Neutral		Energy Deposition on Pumping Panel	
	Steady State	< 50 ms	J/Source Neut.	J/Captured Neut.
Full	0.82(0.05) ^a	0.74(0.06)	1.4×10^{-21} (0.07)	1.7×10^{-21} (0.08)
No Chevrons	0.84(0.06)	0.82(0.07)	4.4×10^{-21} (0.06)	5.3×10^{-21} (0.07)

Steady-State Stray Neutral Pressures (Torr/Source Neut.)				
	Neutralizer Tube			Drift Chamber
	Entrance	Center	Exit	Exit
Full	5.2×10^{-24} (0.11)	3.6×10^{-24} (0.11)	1.4×10^{-24} (0.19)	8.4×10^{-26} (0.42)
No Chevrons	5.3×10^{-24} (0.09)	3.4×10^{-24} (0.07)	1.3×10^{-24} (0.10)	4.7×10^{-26} (0.47)

^aValues in parentheses represent one fractional standard deviation.

The adequacy of the methodology and assumptions described above has been partially substantiated by determining the transmission probability of the neutralizer tube. This calculation yields a value of 0.218 (0.018) which compares extremely well with the transmission probability of 0.22 obtained for molecular flow through a cylindrical tube.²

The results in Table 6.41.1 reflect the changes in system characteristics due to a drastic alteration in cryopump design—removal of the chevrons. This significant design change caused a relatively small 10% increase in capture rate, i.e., the increased number of neutral captures in <50 ms, and a very desirable factor of 2 decrease in the stray neutral pressure at the drift chamber exit. However, these desirable changes were more than offset by the factor of 3 increase in the heat load on the pumping panels as illustrated by the increased energy deposition. These results represent the system characteristics with only the two-primary cryopumps operational; i.e., only those located on either side of the neutralizer tube in the beam line vacuum enclosure. Calculations to determine the effect on injector performance due to a variety of system changes, in particular the addition of two auxiliary drift chamber cryopumps, have been performed and the results from these calculations will be presented and discussed.

* Research sponsored by DOE Office of Fusion Energy.

† Fusion Energy Division.

1. M. B. Emmett, "The MORSE Monte Carlo Radiation Transport System," ORNL-4972 (February 1975).
2. D. H. Davis, "Monte Carlo Calculation of Molecular Flow Rates Through a Cylindrical Elbow and Pipes of Other Shapes," J. Appl. Phys., 37, 1169 (1960).

6.42. NEUTRONICS - TRITIUM BREEDING*

R. T. Santoro

Abstract of paper presented at the Fusion Energy Research, R. T. Santoro, and J. H. Nixson, Eds., Elsevier Applied Science Publishers, Ltd., London, England, in press.

The neutronics of tritium breeding are reviewed. The ramifications of breeding are delineated with respect to overall blanket design. A brief commentary on the one-dimensional discrete ordinates method for estimating tritium production is presented. Some examples of the tritium breeding capability of prototypic blanket designs are summarized along with examples of the influence on calculated tritium breeding ratios of cross section uncertainties.

*Research sponsored by DOE Office of Fusion Energy.

6.43. AN OPTIMIZATION OF THE FISSION-FUSION HYBRID CONCEPT*

M. J. Saltmarsh[†] W. R. Grimes[‡] R. T. Santoro

Abstract of paper presented at Third IAEA Symposium on Fusion-Fission Hybrids, Princeton, New Jersey, January, 1979; also abstract of DOE TTA-79-16, April, 1979.

The hybrid is examined in the role of a fissile fuel producer. The advantages of the concept are parameterized in terms of the performance of the fusion device and the breeding blanket, and some of the more troublesome features of existing design studies are discussed. The analysis suggests that hybrids based on D-T fusion devices are unlikely to be economically attractive and that they present formidable blanket technology problems. An alternative approach based on a semicatalyzed D-D fusion reactor and a molten salt blanket is suggested. This concept is shown to emphasize the desirable features of the hybrid, to have considerably greater economic potential, and to mitigate many of the disadvantages of D-T based systems.

*Research sponsored by Department of Energy.

[†]Fusion Energy Division.

[‡]Chemical Technology Division.

HIGH-ENERGY PHYSICS PROGRAM6.44. SKYSHINE AT NEUTRON ENERGIES ≤ 400 MeV*R. G. Alsmiller, Jr. J. Barish[†] P. L. Childs[‡]

Abstract of IAEA TM-7416, London, 1977.

The dose equivalent at an air-ground interface as a function of distance from an assumed azimuthally symmetric point source of neutrons can be calculated as a double integral. The integration is over the source strength as a function of energy and polar angle weighted by an importance function that depends on the source variables and on the distance from the source to the field point. The neutron importance function for a source 15 m above the ground emitting only into the upper hemisphere has been calculated using the two-dimensional discrete ordinates code, DOT, and the first collision source code, GRTUNCL, in the adjoint mode. This importance function is presented for neutron energies ≤ 400 MeV, for source cosine intervals of 1 to .8, .8 to .6, .6 to .4, .4 to .2 and 2

to 0, and for various distances from the source to the field point. As part of the adjoint calculations a photon importance function is also obtained. This importance function for photon energies < 14 MeV and for various source cosine intervals and source-to-field point distances is also presented. These importance functions may be used to obtain skyshine dose equivalent estimates for any known source energy-angle distribution.

To illustrate the use of the results, the dose equivalent as a function of distance from one of the target areas at the Alternating Gradient Synchrotron at the Brookhaven National Laboratory has been calculated and is compared with the experimental data of C. Distenfeld and D. Colvett. The energy-angle distribution of the neutron source used in this calculation was taken from the measurements of R. Hadey, A. R. Baldwin and F. W. Waterman.

To aid in the design of the roof over a target area for the 400 GeV proton accelerator, ISABELLE, being constructed at the Brookhaven National Laboratory, the dose equivalent as a function of distance from the target area and as a function of roof thickness has been calculated and is presented. The energy-angle distribution of the neutrons emerging from the roof over the target area was calculated as a function of roof thickness using the high-energy transport code, HETC. The dose equivalent from these neutrons has been calculated using the importance results. Also, in one case, the dose equivalent has been calculated directly with the discrete ordinates codes and a comparison between dose equivalent as a function of distance obtained by direct calculation and using adjoint methods is given.

* Research sponsored by DOE Office of High Energy and Nuclear Physics.

† UCC-ND Computer Sciences Division.

6.45. MAGIK - A MONTE CARLO SYSTEM FOR COMPUTING INDUCED RESIDUAL ACTIVATION DOSE RATES*

J. Barish[†] T. A. Gabriel R. G. Alsmiller, Jr.

(Abstract of ORNL-3561, August, 1979)

The photon dose rate from the induced activity produced by sustained bombardment of materials by neutrons and charged particles may present a significant radiation hazard. To minimize this hazard, the material configuration must be so designed that the photon dose rate decays to an acceptable level soon after the source beam is turned off. MAGIK calculates the time-independent photon dose rates that result from activities produced by nucleon-nucleus and meson-nucleus collisions over a wide range of energies. The system has been used both for high-energy accelerator studies and for fusion reactor studies. In the MAGIK system the lengthy photon transport calculations are carried out independent of time, and the time dependence is introduced in the final program, thereby permitting study of various operating scenarios with a minimum computing cost.

* Research sponsored by DOE Office of High Energy and Nuclear Physics and by Princeton Plasma Physics Laboratory, Princeton University.

† UCC-ND Computer Sciences Division.

6.46. PHOTON DOSE RATE IN THE VICINITY OF A HIGH-ENERGY PROTON BEAM SCRAPER*

R. G. Alsmiller, Jr. J. Barish[†]*(Abstract of ORNL/TM-7045, October, 1979; and Nucl. Instr. Methods 172, 466, 1980)*

Calculated results are presented of the photon dose rate from the induced activity in the vicinity of a beam scraper for a 400 GeV proton accelerator. Proton energies of 30 and 400 GeV are considered since 30 GeV protons will be used for beam alignment studies. Results are given at various positions with respect to the scraper and as a function of time after the beam is turned off. In the case of the 30 GeV protons both borated and non-borated concrete have been considered as the material of the accelerator tunnel and the beam scraper shield. In the geometry considered here, the presence of the boron in the concrete has only a small effect on the dose rates.

* Research sponsored by DOE Office of High Energy and Nuclear Physics.

[†]UCC-ND Computer Sciences Division.

6.47. THE RESPONSE OF A URANIUM-PLASTIC CALORIMETER TO LOW GeV (≤ 10 GeV) PROTONS*T. A. Gabriel B. L. Bishop[†]*(Abstract of ORNL/TM-6709, January, 1979; and Nucl. Instr. Methods 164, 609, 1979)*

The calculated response of a uranium-plastic calorimeter for incident 1-10 GeV protons is presented and compared to previously published data for a uranium-liquid argon calorimeter.

* Research sponsored by DOE Office of High Energy and Nuclear Physics.

[†]UCC-ND Computer Sciences Division.

6.48. CALCULATED RESPONSE OF A TOTAL LIQUID ARGON CALORIMETER TO PROTONS AND ELECTRONS IN THE 0.5-5.0 GeV ENERGY RANGE*

T. A. Gabriel B. L. Bishop[†]*(Abstract of ORNL/TM-6889, July, 1979; and Nucl. Instr. Methods 169, 427, 1980)*

The calculated response of a $50 \times 50 \times 200$ cm³ total liquid argon calorimeter to protons and electrons in the 0.5-5.0 GeV energy range is presented. The device is segmented into alternating x and y planes ($50 \times 1 \times 1$ or $1 \times 50 \times 1$ cm³) so that spatial and angular resolution can be obtained for both coordinates. For 2 GeV incident electrons the calculated values (σ) for the energy resolution and upper limit values for the spatial and angular resolutions are 2.0%, 1.5 cm, and 28 mrad, respectively. Sampling fluctuations is one method used to discriminate between incident electrons and protons. An electron acceptance level of >95% with <5% proton contamination is possible at the 2 GeV energy deposition level. The device is also analyzed by treating each of the small sampling sections as flash tubes. As expected, the energy resolution increased but the spatial and angular resolutions remained essentially unchanged.

* Research sponsored by DOE Office of High Energy and Nuclear Physics.

[†]UCC-ND Computer Sciences Division.

6.49. LIQUID ARGON AS AN ELECTRON/PHOTON DETECTOR IN THE ENERGY RANGE
OF 50 MeV TO 2 GeV: A MONTE CARLO INVESTIGATION*

M. S. Goodman[†] G. Denis[†] M. Hall[†] A. Karpovsky[†]
R. Wilson[‡] T. A. Gabriel B. L. Bishop[‡]

(Abstract of paper presented at 1980 Nuclear Science Symposium of the Institute of Electrical and Electronics Engineers, Orlando, Florida, November 6-7, 1980; also abstract of ORNL/TM-7566, December, 1980)

Using Monte Carlo techniques, the characteristics of a proposed electron/photon detector based on the total absorption of electromagnetic showers in liquid argon have been investigated. The energy range studied was 50 MeV to 2 GeV. Results are presented on the energy and angular resolution predicted for the device, along with detailed predictions of the transverse and longitudinal shower distributions. Comparisons are made with other photon detectors, and possible applications are discussed.

*Work performed at ORNL sponsored by DOE Office of High Energy and Nuclear Physics.

[†]Harvard University, Department of Physics.

[‡]UCC-ND Computer Sciences Division.

6.50. CALCULATED PARTICLE PRODUCTION SPECTRA AND MULTIPLICITIES
FROM NUCLEON-FISSILE ELEMENT COLLISIONS AT MEDIUM ENERGIES*

F. S. Alsmiller R. G. Alsmiller, Jr. [†] T. A. Gabriel
R. A. Lillie J. Barish[‡]

(Abstract of paper in Nuclear Science Symposium for Technology, NSE Special Publication 604, p. 400, 1980)

A fission channel has been added to the intranuclear-cascade-evaporation model of nuclear reactions so that this model may be used to obtain the differential particle production data that are needed to study the transport of medium-energy nucleons and pions through matter. The earlier work of Hahn and Bertini on the incorporation of fission-evaporation competition into the intranuclear-cascade-evaporation model has been retained and the statistical model of fission has been utilized to predict particle production from the fission process. Approximate empirically derived kinetic energies and deformation energies are used in the statistical model. The calculated residual nuclei distributions are in reasonable agreement with experimental data, but the neutron multiplicities at the higher incident nucleon energies >500 MeV are sensitive to the level density parameter used.

*Research sponsored by DOE Office of Basic Energy Sciences.

[†]UCC-ND Computer Sciences Division.

6.51. A PHENOMENOLOGICAL MODEL FOR PARTICLE PRODUCTION FROM THE COLLISION
OF NUCLEONS AT MEDIUM ENERGIES WITH FISSILE ELEMENTS*

F. S. Alsmiller R. G. Alsmiller, Jr. [†] T. A. Gabriel
R. A. Lillie J. Barish[‡]

(Reprint of Trans. Am. Nucl. Soc. 35, 475, 1980)

The addition of a detailed fission channel, including fragment mass, charge, kinetic energy, and excitation energy distributions, to the evaporation stage of the Monte Carlo computer code,¹ MECC-7, for nuclear cross sections and particle production data has been

reported in an earlier paper.² In this code the intranuclear-cascade-evaporation model, as developed by Bertini,^{3,4} and Hahn,⁵ is applied to nucleon- and pion-nucleus nonelastic collisions at all incident energies between 20 MeV and 3 GeV. Data regarding such collisions between medium-energy protons and uranium nuclei are of particular importance in designing the targets and shielding for facilities to produce an intense source of low-energy neutrons.^{6,7} In this paper, significant revisions to the model described in Ref. 2 are discussed and comparison between calculated results and experimental data that were not available when Ref. 2 was published will be presented.

The statistical theory of fission originated by Fong^{8,9} is used as a guide. Fong-type fission channel calculations for use at high energies have also been given by Barashenkov and Toneyev,¹⁰ Barashenkov and Shmakov,¹¹ and by Takahashi.¹² In addition, Atchison¹³ has recently prepared a phenomenological model.

The model described here relies heavily on experimental data of Epperson¹⁴ for post-evaporation average mass, total kinetic energy, and variance distributions versus A_2 , the mass number of the heavy residual nucleus. We used data for 7-, 10-, 15-, 20-, 25-, and 30-MeV protons incident on ^{235}U to compute the preevaporation distributions, which are shifted in A_2 (to the value A_2^0) by average neutron multiplicities, $\bar{\nu}_n(E_f)$ and weighted by fission probabilities, $P_f(E_f)$ obtained from the code. E_f is the excitation energy of the fissioning nucleus. Fission fragments lose kinetic energy at each evaporation step due primarily to the loss of mass.¹⁵ In this paper we applied a $\Delta K_E = 0.8$ -MeV correction per emitted nucleon to the average relative kinetic energy, $\bar{K}_E(A_2^0, E_f)$, obtained as a solution of the superposition equations of Ref. 2. The final kinetic energy distributions computed for incident protons on ^{235}U now agree fairly well with Epperson's measurements.¹⁴ For $E_f \leq 31.5$, the total excitation energy, $\bar{E}(A_2^0, E)$,

$$\bar{E}(A_2^0, E_f) = E_f + \Delta \bar{E}_C(A_2^0, E_f)$$

of the two fission fragments at scission time is obtained by fitting a variation of Fong's mass yield formula to the calculated preevaporation mass distribution. At all higher E_f , the functions $\bar{K}_E$ and $\Delta \bar{E}_C$ defined by Eq. () are held constant at their $E_f = 31.5$ values.

The parameter, a , used in the nuclear level density formula, is that given by LeCouteur and Lang,¹⁶

$$a = \frac{A}{B_0} \left[1 + \gamma_0 \left(\frac{A-Z}{Z} \right)^2 \right]; \quad \gamma_0 = 1.5,$$

and is taken to be the same for fission as for evaporation. The value of B_0 is one of the most important parameters in determining neutron multiplicities as well as neutron energy spectra. It is taken to be independent of E_f , and the nuclear mass and charge numbers, A, Z . Numerical values of B_0 can be varied to fit the experimental data.

In Table 6.51.1 the calculated and experimental¹⁷ average number of emitted neutrons per fission from fission induced in ^{235}U , ^{238}U , and ^{239}Pu by neutrons with energy 22.79 and 28.23 MeV are presented and compared. Calculated results are given for B_0 values of 8, 10, and 15 MeV. The errors on the calculated results are the statistical errors (one standard deviation) due to the Monte Carlo nature of the calculations. For ^{235}U and ^{239}U all of the calculated results are slightly low, but the values for $B_0 = 8$ MeV are in the best agreement with the experimental data. For ^{239}Pu , both $B_0 = 8$ and 10 MeV give results that are in reasonable agreement with the data.

Comparisons with experimental neutron multiplicities at higher energies (> 3 GeV) indicate that a B_0 value of approximately 10 MeV is needed to obtain agreement.^{2,11} Calculated results of neutron energy spectra, average kinetic energy of residual nuclei, and residual mass distribution have also been obtained and will be presented. In particular, the residual mass distribution will be compared with experimental data. The agreement between calculated and experimental results that have been obtained gives some confidence that design calculations carried out using the data obtained from this model will be reliable.

Table 6.51.1. The Average Number of Neutrons Emitted per Fission for Neutron-Induced Fission in Various Elements

Average Number of Neutrons Emitted per Fission				
Neutron Energy MeV	Experimental	Calculated		
		$B_0 = 8 \text{ MeV}$	$B_0 = 10 \text{ MeV}$	$B_0 = 15 \text{ MeV}$
^{235}U				
22.79	5.493 $\pm$.049	4.96 $\pm$.09	4.79 $\pm$.08	4.67 $\pm$.08
28.28	6.080 $\pm$.090	5.51 $\pm$.09	5.34 $\pm$.09	5.23 $\pm$.09
^{238}U				
22.79	5.513 $\pm$.043	5.15 $\pm$.10	4.88 $\pm$.10	4.80 $\pm$.10
28.28	6.137 $\pm$.067	5.79 $\pm$.11	5.46 $\pm$.11	5.32 $\pm$.11
^{239}Pu				
22.79	6.000 $\pm$.077	6.02 $\pm$.08	5.93 $\pm$.08	5.81 $\pm$.07
28.28	6.479 $\pm$.104	6.61 $\pm$.08	6.49 $\pm$.08	6.33 $\pm$.08

* Research sponsored by DOE Office of Basic Energy Sciences.

† UCC-ND Computer Sciences Division.

‡ The fission-amended model has also been incorporated in the high energy transport code HETC (Ref. 7).

1. H. W. Bertini et al., "Instructions for the Operation of Codes Associated with MECC-7 (Originally MECC-3), A Preliminary Version of an Intranuclear Cascade Calculation for Nuclear Reactions," ORNL-4654 (1971).
2. F. S. Alsmiller et al., "Calculated Particle Production Spectra and Multiplicities from Nucleon-Fissile Element Collisions at Medium Energies," Proc. Int. Conf. Nuclear Cross Sections for Technology, Knoxville, TN (October 22-26, 1979).
3. H. W. Bertini, "Nonelastic Interactions of Nucleons and π Mesons with Complex Nuclei at Energies Below 3 GeV," Phys. Rev., C6, 631 (1972).
4. H. W. Bertini, "Spallation Reactions: Calculations" in Spallation Nuclear Reactions and their Applications, D. Reidel Publishing Co., Boston, MA (1976).
5. R. L. Hahn and H. W. Bertini, "Calculations of Spallation-Fission Competition in the Reaction of Protons with Heavy Elements at Energies $\leq 3 \text{ GeV}$," Phys. Rev., C6, 660 (1972).
6. J. M. Carpenter, "Pulse Spallation Neutron Sources for Slow Neutron Scattering," Nucl. Inst. Methods, 145, 91 (1977).
7. T. W. Armstrong and K. C. Chandler, "Operating instructions for the High-Energy Nucleon-Meson Transport Code HETC," ORNL-4744 (1972).
8. P. Fong, "Statistical Theory of Nuclear Fission," Gordon and Breach Science Publishers, New York, NY (1969).
9. P. Fong, "Kinetic Energy and Prompt Neutron Distributions in Fission," Phys. Rev. Letters, 11 (1963).
10. V. S. Barashenkov and V. D. Tonev, "Interactions of High-Energy Particles and Atomic Nuclei, Chap. 10, FTD-ID(RS)T-1069-77 (1977).

11. V. S. Barashenkov and S. Ju. Shmakov, "Nuclear Fission Induced by High-Energy Protons," Communication of the Joint Institute of Nuclear Research, Dubna, USSR (1979).
12. H. Takahashi, "Fission Reaction in High Energy Proton Cascade," to be published in the Proc. Symp. Neutron Cross Sections for 10 to 50 MeV, held at the Brookhaven National Laboratory (May 12-14, 1979).
13. F. Atchison, "The Inclusion of Fission in the High Energy Particle Transport Code, HETC," Bull. Am. Phys. Soc., 24, 874 (1979).
14. D. H. Epperson, "Systematics of Mass Yield Distributions for Nuclear Fission of Neptunium," Dissertation, Dept. of Physics, Duke University (1978).
15. J. Terrell, "Neutron Yields from Individual Fission Fragments," Phys. Rev., 127, 380 (1962).
16. K. J. LeCouteur and D. W. Lang, "Neutron Evaporation and Level Densities in Excited Nuclei," Nucl. Phys., 13, 36 (1959).
17. P. Manero, V. A. Konshin, "Status of Energy-Dependent $\bar{\nu}$ -Values for the Heavy Isotopes ($Z > 90$) from Thermal to 15 MeV and of $\bar{\nu}$ -Values Spontaneous Fission," At. Energy Rev., 10, 637 (1972).

6.52. THERMAL-NEUTRON FLUX GENERATION BY HIGH-ENERGY PROTONS IN THICK URANIUM TARGETS*

R. G. Alsmiller, Jr., T. A. Gabriel J. Barish[†] F. S. Alsmiller

(Reprint of Trans. Am. Nucl. Soc. 35, 477-478, 1980)

For several applications, e.g., in designing facilities to produce an intense source of low-energy neutrons by using medium-energy protons¹ and for studies of the feasibility of converting fertile-to fissile material using medium-energy protons,² it is necessary to carry out calculations of the transport of medium- and low-energy nucleons and pions through fissionable material. The high-energy transport code HETC³ has often been used to carry out such transport calculations,^{2,4} but because this code did not take into account high-energy fission, the results were very approximate. Recently, a fission channel has been added to the intranuclear-cascade-evaporation model of nuclear reactions⁵ and this revised cross-section model has now been incorporated into the transport code, HETC, so that medium-energy nucleon and pion transport calculations in fissionable material may be carried out. The transport code, HETC, used here is in all respects the same as that described in Ref. 3, except that when a nucleon-nucleus or pion-nucleus non-elastic collision occurs the probability that fission occurs and the particle production from the excited residual nuclei following fission are taken into account.

To test the validity of the revised code, calculations have been carried out and compared with the experimental data of Fraser et al.⁶ In the experiment, protons of various energies were incident on a depleted uranium target (10.2-cm diam $\times$ 60 cm long) surrounded by a large tank of water, and the number of thermal-neutron captures in the water per incident proton was measured. The calculations were carried out using the geometry of the experiment and the number of thermal-neutron captures in the water was calculated. The parameter, B_0 , that occurs in the level density expression in the intranuclear-cascade-evaporation model was taken to be 10 MeV (Ref. 5). The low-energy (<15 MeV) neutron transport calculations were carried out with MORSE,⁷ using cross-section data based on ENDF/B-IV.⁸

Comparisons between the calculated results and the experimental data of Fraser et al.¹ are shown in Table 6.52.1. The calculated error bars are statistical only and indicate one standard deviation in the Monte Carlo calculations. At the proton energies of 540 and 960 MeV the calculated and experimental results are in very good agreement, but for incident protons of 1470 MeV the calculated results are larger than the experimental data.

Transport calculations similar to those considered here have also been carried out by Barashenkov et al.⁹ for protons incident (at the center) of an infinite natural uranium system. In Table 6.52.1 the results from Ref. 9 are compared with similar results obtained here for the case of 1-GeV incident protons. The quantities compared are the total number of fissions (i.e., fissions in both ²³⁵U and ²³⁸U) per incident proton and the total number of neutron captures per incident proton.

Comparisons similar to those in Table 6.52.1 with a variety of other experimental data will also be presented.

Table 6.52.1. Comparison Between Calculated Results and the Experimental Data of Fraser et al.,⁶ and the Calculated Results of Barashenkov et al.⁹

Proton Incident on a Depleted Uranium Target Surrounded by Water		
Incident Proton Energy (MeV)	Thermal-Neutron Captures in H ₂ O	
	Experiment ⁶	Calculated Here
540	15.1 ± 0.8	15.2 ± 0.8
960	32.3 ± 1.6	33.7 ± 1.0
1470	44.8 ± 2.2	53.6 ± 1.5

1-GeV Protons Incident at the Center of an Infinite Natural Uranium System		
	Calculated Barashenkov et al. ⁹	Calculated Here
Number of fissions per incident proton	28	23 ± 1
Number of captures per incident proton	102	86 ± 3

* Research sponsored by DGE Office of Basic Energy Sciences.

† UCC-ND Computer Sciences Division.

1. J. M. Carpenter, "Pulse Spallation Neutron Sources for Slow Neutron Scattering," Nucl. Instr. Methods 145, 91 (1977).
2. Proc. Inf. Mtg. Accelerator Breeding, NTIS CONF-770107, Brookhaven National Laboratory (June 18-19, 1977).
3. T. W. Armstrong and K. C. Chandler, "Operating Instructions for the High-Energy Nucleon-Meson Transport Code HETC," ORNL-4744, Oak Ridge National Laboratory (1972).
4. "IPNS - A National Facility for Condensed Matter Research," ANL-77-88, Argonne National Laboratory (1978).
5. F. S. Alsmiller et al., "Calculated Particle Production Spectra and Multiplicities from Nucleon-Fissile Element Collisions at Medium Energies," Proc. Int. Conf. Nuclear Cross Sections for Technology, Knoxville, Tennessee (Oct. 22-26, 1979).
6. J. S. Fraser et al., "Neutron Production in Thick Targets Bombarded by High Energy Protons," Phys. Canada, 21, 17 (1965).
7. M. B. Emmett, "The MORSE Monte Carlo Radiation Transport System," ORNL-4972, Oak Ridge National Laboratory (1975).
8. ORNL/RSIC-37, Radiation Shielding Information Center, Oak Ridge National Laboratory (1975).
9. V. S. Barashenkov, V. D. Toneev, and S. E. Cheyrinon, "Interaction of High-Energy Deuteron Beams in Matter," Soviet At. Energy, 37, 1256 (1974).

MISCELLANEOUS STUDIES

6.53. MOLTEN-SALT REACTORS FOR EFFICIENT NUCLEAR FUEL UTILIZATION WITHOUT PLUTONIUM SEPARATION*

J. R. Engel[†] W. A. Rhoades W. R. Grimes[‡] J. F. Dearing[†]

(Abstract of *Nucl. Technol.* 48, 50, 1978)

Molten-salt reactors (MSRs), because of the fluid nature of the fuel, appear to provide an attractive approach to efficient fuel utilization in the thorium-²³³U cycle as well as a means for limiting the availability of plutonium and the general proliferation risks associated with nuclear power generation.

High-enrichment ²³³U systems could, in principle, be operated with positive breeding gains to effectively eliminate plutonium as a nuclear fuel. However, such systems would be proliferation sensitive. Concept modifications (short of denaturing the uranium fuel) can be conceived to enhance the proliferation resistance of high-enrichment MSRs, but it is doubtful that sufficient enhancement could be achieved to make the systems suitable for deployment other than at "secure" sites.

Denaturing the uranium in an MSR introduces some plutonium into the fuel cycle and generally degrades its breeding performance. Nevertheless, a denatured MSR with full-scale on-site fuel reprocessing appears to be capable of break-even breeding. In addition, the plutonium (most of which is consumed in situ) would be of poor quality and would never be isolated from all other undesirable nuclides. Thus, such systems would provide for efficient utilization of uranium resources in a proliferation-resistant environment while limiting the amount of plutonium (and transplutonium actinides) that would have to be handled as waste. The development of commercial MSRs by early in the 21st century appears to be technologically feasible.

*Research sponsored by DOE Office of Fuel Cycle Evaluation.

[†]Engineering Technology Division.

[‡]Chemical Technology Division.

6.54. CONCEPTUAL DESIGN CHARACTERISTICS OF A DENATURED MOLTEN-SALT REACTOR WITH ONCE-THROUGH FUELING*

J. R. Engel[†] H. F. Bauman[†] J. F. Dearing[†]
W. R. Grimes[‡] H. E. McCoy[§] W. A. Rhoades

(Abstract of *ORNL/TM-2207*, July, 1980)

A study was made to examine the conceptual feasibility of a molten-salt power reactor fueled with denatured ²³⁵U and operated with a minimum of chemical processing.

Because such a reactor would not have a positive breeding gain, reductions in the fuel conversion ratio were allowed in the design to achieve other potentially favorable characteristics for the reactor. A conceptual core design was developed in which the power density was low enough to allow a 30-year life expectancy of the moderator graphite with a fluence limit of 3×10^{26} neutrons/m² ($E > 50$ keV). This reactor could be made critical with about 3450 kg of 20% enriched ²³⁵U and operated for 30 years with routine additions of denatured ²³⁵U and no chemical processing for removal of fission products. The lifetime requirement of natural U₃O₈ for this once-through fuel cycle would be about 1810 Mg (~2000 short tons) for a 1-GWe plant operated at a 75% capacity factor. If the uranium in the fuel at the end of life were recovered (3160 kg fissile uranium at ~10% enrichment), the U₃O₈ requirement could be further reduced by nearly a factor of 2. The lifetime net plutonium production for this fuel cycle would be only 736 kg for all isotopes (238, 239, 240, 241, and 242).

A review of the chemical considerations associated with the conceptual fuel cycle indicates that no substantial difficulties would be expected if the soluble fission products and higher actinides were allowed to remain in the fuel salt for the life of the plant. Some salt treatment to counteract oxide contamination and to maintain the oxidation potential of the melt probably would be necessary, but these would require only well-known and demonstrated technology.

Although substantial technology development would be required, the denatured molten-salt reactor concept apparently could be made commercial in about 30 years; if the costs of intermediate developmental reactors are included, the cost for development is estimated to be \$3750 million (1978 dollars). The resulting system would be approximately economically competitive with current-technology light-water reactor systems.

* Research sponsored by DOE Office of Fuel Cycle Evaluation.

† Engineering Technology Division.

‡ Chemical Technology Division.

§ Metals and Ceramics Division.

6.55. CONCEPT EVALUATION OF A NUCLEAR DESIGN FOR ELECTRONUCLEAR FUEL PRODUCTION: EVALUATION OF ORNL'S PROPOSED TMF-ENFP

T. J. Burns D. E. Bartine J. P. Renier[†]

(Abstract of ORNL/TM-6828, May, 1979)

The use of an external neutron source, generated via an accelerator, represents a potential means for producing the fissile isotopes ^{233}U and ^{239}Pu . One promising accelerator-breeder concept employs a sodium-cooled ternary metal fertile blanket (^{239}Pu , ^{238}U , and ^{232}Th) surrounding a central column of sodium. A preliminary assessment of the neutronic characteristics and the relevant economic parameters for this system, designated the TMF-ENFP (Ternary Metal Fueled Electronuclear Fuel Producer) is described here.

The rationale for selecting the particular configuration utilized was addressed from the standpoints of fissile production, heat generation, and target interaction. The basic assumption assumed a 300-mA beam of 1-GeV protons from the accelerator. A calculational model of the target blanket assembly was developed which met certain prespecified design limitations. A preliminary assessment of the nuclear performance, thermal-hydraulic, and economic parameters was made. For the latter, the use of the TMF-ENFP in conjunction with the denatured ($^{233}\text{U}/^{238}\text{U}$) fuel cycle in both PWRs and CANDUs was considered.

The basic accelerator-driven blanket concept requires a tradeoff between fissile production and the heat-removal capability. Moreover, the centrally located proton beam results in a significant gradient in the power density (Peak/Average ~ 2). Fissile production of the TMF-ENFP configuration considered was 5.8 kg/day of ^{233}U . Such a production rate would support a maximum of 5.58 GW(e) of denatured PWR capacity [or alternatively 11.58 GW(e) of denatured CANDU capacity]. The cost of the TMF-ENFP/thermal reactor system is judged to be competitive with current-generation LEU-PWRs operating from a $> \$80/\text{lb } \text{U}_3\text{O}_8$ resource base.

* Research sponsored by DOE Office of Fuel Cycle Evaluation.

† UCC-ND Computer Sciences Division.

6.56. NONDESTRUCTIVE ASSAY OF SUBASSEMBLIES OF VARIOUS SPENT OR FRESH FUELS BY ACTIVE NEUTRON INTERROGATION*

R. L. Ragan[†] C. W. Ricker[†] M. M. Chiles[†]
D. T. Ingersoll G. G. Slaughter[‡]

(Abstract of paper presented at Twentieth Annual Meeting, Institute of Nuclear Materials Management, Albuquerque, New Mexico, July 16-19, 1979)

Recent studies show that subassemblies containing various spent fuels could be assayed rapidly and accurately by a nondestructive assay system using active neutron interrogation and prompt-neutron detection. Subassembly penetration is achieved by 24-keV (Sb-Be) interrogation neutrons; the spent-fuel neutron background is overridden by using strong interrogating sources and prompt-neutron signals, and background gammas are absorbed by lead. Experiments have demonstrated the potential for assaying, with better than 5% accuracy, three spent plutonium-fueled subassemblies per hour. Calculations, validated by experiments, predict even better performance for fresh or uranium-fueled subassemblies; several performance estimates are given.

*Research sponsored by DOE Nuclear Power Division.

[†]Instrumentation and Controls Division.

[‡]Physics Division.

6.57. SYSTEM FOR NONDESTRUCTIVE ASSAY OF SPENT FUEL SUBASSEMBLIES - COMPARISON OF CALCULATIONS AND MEASUREMENTS*

G. L. Ragan[†] C. W. Ricker[†] M. M. Chiles[†]
D. T. Ingersoll G. G. Slaughter[‡] L. R. Williams

(Abstract of paper presented at ANS Topical Meeting on Measurement Technology for Safeguards and Material Control, Kiawah Island, Charleston, South Carolina, November 26-29, 1979; see p. 447 in proceedings, NBS Special Publication 582)

A nondestructive assay system was developed for determining the total fissile content of spent fuel subassemblies at the head end of a reprocessing plant. The system can perform an assay in 20 min with an uncertainty of < 5%. Antimony-beryllium neutrons (23 keV) interrogate the subassemblies, and proton recoil counters detect the resulting fission neutrons. Pulse-height discrimination differentiates between the low-energy interrogation neutrons and the higher-energy fission neutrons.

To optimize the performance of the system, 51-energy-group neutron-transport calculations were made, first with a one-dimensional (1-D) computer model, followed by a 2-D computer model. The performance of the as-built system was calculated using a 2-D model. The cross-sections were from the ENDF/B-IV data file and were processed for use in liquid-metal-cooled fast breeder reactor (LMFBR) calculations.

Calculated and measured results were compared for (1) interrogation-neutron penetrability, (2) fission-neutron detectability, (3) radial variation of assay sensitivity, (4) axial variation of assay sensitivity, and (5) the variation of detector count rate as a function of the number of fuel rods in a special 61-rod, LMFBR-type subassembly.

The calculational procedures were validated by comparison with experimental measurements, thus permitting further exploration of system performance by means of additional calculations. In this manner, the following system characteristics were investigated: the relative assay sensitivities of various fissile nuclides; the applicability of the system to a wide variety of fuels, either fresh or spent; the effect on assay accuracy of uncertainties in the isotopic abundances in the fuel; and the efficacy of possible methods of determining isotopic abundances in the sample.

*Research sponsored by DOE Nuclear Power Division.

†Instrumentation and Controls Division.

‡Physics Division.

6.58. CALCULATION OF NEUTRON DIE-AWAY TIMES IN A LARGE-VEHICLE PORTAL MONITOR*

R. A. Lillie R. T. Santoro R. G. Alsmiller, JR.

(Abstract of ORNL/TM-7299, May, 1980; also to be published in *Nuclear Technology*)

Monte Carlo methods have been used to calculate neutron die-away times in a large-vehicle portal monitor. These calculations were performed to investigate the adequacy of using neutron die-away time measurements to detect the clandestine movement of shielded nuclear materials. The geometry consisted of a large tunnel lined with He^3 proportional counters. The time behavior of the (n,p) capture reaction in these counters was calculated when the tunnel contained a number of different tractor-trailer load configurations. Neutron die-away times obtained from weighted least-squares fits to these data were compared. The change in neutron die-away time due to the replacement of cargo in a fully loaded truck with a spherical shell containing 240 kg of borated polyethylene was calculated to be less than 3 percent. This result, together with the overall behavior of neutron die-away time versus mass inside the tunnel, strongly suggested that measurements of this type will not provide a reliable means of detecting shielded nuclear materials in a large vehicle.

*Research sponsored by Department of Energy.

6.59. RESONANCE INTEGRAL CALCULATIONS FOR ISOLATED RODS CONTAINING OXIDES OF ^{238}U AND ^{232}Th *

V. C. Baker† J. H. Marable

(Abstract of ORNL/TM-6376, February, 1980)

This report discusses results of resonance integral calculations for UO_2 and ThO_2 isolated rods. The calculations were performed with ENDF/B-IV cross-section data and the multigroup transport code ANISN. The findings reported demonstrate by comparison to semiempirical relationships (based on experimentally derived results) the suitability of the method used for determining resonance integrals.

The calculations were based on a cylindrical rod in an H_2O moderator of large radius. Multigroup cross sections were obtained by a MINX-SPHINX-AMPX sequence, and ANISN was used to account for the neutron flux and capture rates. A special approach was used to determine a neutron source distribution such that the flux in the moderator region was forced to behave in an asymptotic way, thus providing a means by which to calculate the "ideal" resonance integral experiment.

The UO_2 resonance integrals calculated were in exceptionally good agreement with experimental values based on isolated rods. The ThO_2 results were approximately 6% lower than experimental values, and efforts to understand the discrepancy are discussed.

*Research sponsored by Department of Energy.

†JCC-ND Computer Sciences Division.

6.60. ONE-DIMENSIONAL MODEL OF FLUIDIZED BED COMBUSTOR DYNAMICS*

R. B. Perez

(Abstract of ORNL/TM-7141, January, 1990)

The I&C Division undertook an exploratory study of the physics of fluidized bed combustors (FBCs). Specific goals of this study were to: (1) compile and understand the basic multiphase equations describing the various processes which determine the behavior of an FBC, (2) develop a one-dimensional model for further dynamic studies of the system, (3) identify those areas of expertise in the I&C Division which could be applied to FBC systems, and (4) develop a systematic approach for using diagnostic techniques developed at I&C to aid the industry.

A detailed study of current literature treating the physics of multiphase systems was conducted. The resulting equations of continuity, chemical reactions, momentum transport, and energy balance were reduced to a more tractable one-dimensional system.

The present work has accomplished the first two goals cited above, thus providing the groundwork for development of tools for the surveillance and control of coal-fired power plants.

* Research sponsored by Department of Energy.

6.61. THE STATUS OF REACTOR SHIELDING RESEARCH IN THE U.S.*

F. C. Maienschein

(Abstract of paper presented at ANS Topical Conference on Advances in Reactor Physics and Shielding, Sun Valley, Idaho, September 14-17, 1980)

While reactor programs change, shielding analysis methods are improved slowly. Version-V of ENDF/B provides improved data and Version-VI will be cost-effective if advanced fission reactors are to be developed in the U.S. Benchmarks for data and methods validation are collected and distributed in the U.S. in two series, one primarily for FBR-related experiments and one for LWR calculational methods. For LWR design, cavity streaming is now handled adequately, if with varying degrees of elegance. Investigations of improved detector response for LWRs rely upon transport methods. The great potential importance of pressure-vessel damage is reflected in widespread studies to aid in the prediction of neutron fluences in vessels. For LMFBRs, the FFTF should give attenuation results on an operating reactor. For larger power reactors, the advantages of alternate shield materials appear compelling. A few other shielding studies appear to require experimental confirmation if LMFBRs are to be economically competitive. A coherent shielding program for the GCFR is nearing completion. For the fusion-reactor program, methods verification is under way, practical calculations are well advanced for test devices such as the TFTR and FMIT, and consideration is now given to shielding problems of large reactors, as in the ETF study. Some of the potential controlling factors for fusion-reactor design, such as heating and induced activation, can now be sorted out in a preliminary way.

* Research sponsored by DOE Office of Reactor Research and Technology.

7.0 INTRODUCTION

In energy model validation the Engineering Physics Division has entered into an area of research in which techniques developed for nuclear research, in particular, sensitivity analysis, are being applied to nonnuclear problems. The real question, which we believe can be answered in the affirmative, is whether the analytical tools of physical scientists can be successfully applied to the socioeconomic problems that bear on human behavior. In our initial work in this area we have developed an approach to evaluating computer codes that have been developed for energy-economic modeling and have applied that approach to the Long Term Energy Analysis Package (LEAP) of the DOE Energy Information Administration (EIA). LEAP is an energy model that is currently being used by EIA to make projections of possible energy futures with emphasis on the period 1995-2020. The model's main function is to allocate supplies of various technologies for an essentially fixed demand. The results are intended to guide R&D decisions for new technologies.

In our evaluation of LEAP, our first goal is to bring it to the point of being an "open" code: that is, a code that is well-documented, has been closely scrutinized in its internals by members of the industry at large, has been widely used, and is frequently modified by its users. Our second goal is to develop a sensitivity theory for determining the important input data used in the code and the degree of importance of that data to the calculated results.

We have already contributed significantly to the documentation of LEAP. We have critically reviewed the mathematical algorithms in the code, have identified problems in convergence, and have made recommendations for data definition and data sources, as well as identified errors in the data base. We have prepared a report specifying what the equations in the model are and have described the economic foundations of the model and its limitations, at all times working closely with the code modelers. We are currently "packaging" the model for transfer to others and are writing a final documentation report.

We have also used LEAP to demonstrate that sensitivity theory can be applied in energy-economic analysis. To date the sensitivity methodology for this application has largely been based on direct sensitivity techniques of the statistical design or response surface methodology; however, the more sophisticated and more powerful "adjoint" approach is also being investigated.

In addition to energy-economic modeling, we are beginning work in modeling and forecasting uranium mining and milling and in aiding forecasts in the national utility financial system. We have also begun a modeling program to assist in projecting the optimum use of fossil fuel resources.

7.1. A SENSITIVITY APPROACH TO THE VALIDATION OF LONG-RANGE ENERGY-ECONOMIC FORECASTS*

E. M. Oblow C. R. Weisbin R. G. Alsmiller, Jr.

Summary of paper presented at Second Symposium of the Institute of Gas Technology on Energy Modeling, Colorado Springs, Colorado, August 18-19, 1979

The Office of Energy Information Validation (OEIV) of the Department of Energy's Energy Information Administration (EIA) is currently sponsoring a program at the Oak Ridge National Laboratory to develop and demonstrate a methodology for the validation of forecasts from energy-economic modeling codes. In conjunction with EIA's interest in forecasting the long-range impact of new technologies and energy research and development on future energy use, the energy-economic modeling code LEAP (Long-Term Energy Analysis Program) has been chosen as the focus of this research program. The work is being carried out by an interdisciplinary team of experts in operations research, statistics, economics, and sensitivity theory. The overall goals of the program with respect to LEAP validation are fivefold: (1) assess the scientific basis for the models and data used in the code, (2) assess its range of applicability, (3) develop a sensitivity theory for determining the important data used by the code in specific applications, (4) quantitatively estimate uncertainties for all important data, leading to an estimate of uncertainties in the code's forecasts and (5) estimate confidence limits in the forecasting results and recommend how these might be reduced. In this paper a more detailed description of the sensitivity methodology will be given.

Two basic approaches to studying the sensitivity of LEAP forecasts to model parameters and data will be taken. The first will involve direct sensitivity techniques of the statistical design or response surface methodology class and the second will employ a more general approach based on adjoint sensitivity theory. In the first case, existing "screening designs" will be adapted to current needs to study the effects of changes in large blocks of data used by LEAP (i.e. to find the sensitivity of a calculated result to elements of LEAP's data base). These "screening designs" are very efficient ways of using the results of relatively few reruns of large computer codes to quantitatively determine which parameters or data were most important in a particular problem (i.e., to come up with a relative ranking of data importance). The method has been used successfully in nuclear reactor safety applications and will be most useful in obtaining a preliminary list of the most important data needed for accurate long range forecasting. In addition, the technique is well defined and should require little research and development activity to be applicable to energy modeling problems.

For the more basic job of quantitatively assessing data importance for the entire LEAP data base (i.e. all data sensitivities) an adjoint approach will have to be developed. This latter methodology has been used widely in the physical sciences to address sensitivity problems but has not been applied to date to energy-system modeling problems. There are good reasons to believe the approach will be applicable to this new area, but considerable research and development will be needed to establish this fact. The major reason for using this approach is the ability of the technique to quantitatively determine the sensitivity of a calculated result to all elements of a code's data base with a single solution to an adjoint equation. This property can be used to efficiently direct the validation effort to those sectors or data elements within the model that are most important in determining the most important results of a forecasting scenario being studied.

*Research sponsored by the DOE Office of Energy Information Administration.

7.2. THE QUANTIFICATION OF UNCERTAINTIES IN THE PARAMETERS OF A LONG-TERM ENERGY MODEL*

R. W. Peelle D. J. Downing[†] D. J. Bjornstad[‡]

(Abstract of paper presented at Second Symposium of the Institute of Gas Technology on Energy Modeling, Colorado Springs, Colorado, August 13-17, 1979)

Even if the form of an energy-economy model's equations can be assumed to specify correctly our technological processes and the relevant behaviors of our society over the necessary time range, there is uncertainty in model results induced by our imperfect knowledge of the numerical values of the model's parameters and input data. Some of this uncertainty is typically "covered" by provision of alternative scenarios with assumptions, but up to now modelers have rarely dealt in detail with the inherent uncertainty of input data. However, when model output or "response" can be represented by a first-order Taylor expansion in the input data about the nominal solution point, knowledge of the variance-covariance (uncertainty) matrix of the input data is sufficient to determine the uncertainty in the computed response induced by the input uncertainties. Some guidelines are given for the evaluation of the required input uncertainty matrices. Illustrative examples are given from our beginning efforts to develop an uncertainty matrix for the important parameters of the Long-Term Energy Analysis Package used within the Energy Information Administration of the Department of Energy.

*Research sponsored by DOE Office of Energy Information Administration.

[†]UCC-ND Computer Sciences Division.

[‡]Energy Division.

7.3. INTERIM REPORT ON MODEL EVALUATION METHODOLOGY AND THE EVALUATION OF LEAP*

R. G. Alsmiller, Jr. J. Barish[†] D. Bjornstad[‡] D. J. Downing[†]
W. E. Ford, III[†] J. Horwedel[†] C. J. Lee[§] J. McAdoo[†]
E. M. Oblow R. W. Peelle F. G. Perey
L. Stewart[‡] C. R. Weisbin

(Excerpt from Executive Summary of ORNL/TM-7245, April, 1980)

This report describes progress made at the Oak Ridge National Laboratory (ORNL), from January through October 1979, toward development and demonstration of a methodology for evaluating energy-economic modeling codes and important results derived from these codes. Model projections now or in the near future will never be the sole guide in policy choices; however, the amount of effort and the quality of scientific talent now dedicated to model development do emphasize the growing role of models in policy analysis. Indeed, it is the understanding of the limitations and ranges of validity of these computer projections that may ultimately determine their final role. The ORNL model evaluation program is attempting to build a "technology" for model evaluation to complement the technology for model construction. The basic components of traditional evaluation techniques have included review of the model's theoretical basis, data, parameters and computational algorithms relative to the intended uses of model results. However, this entire evaluation sequence has been comprehensively applied in only a few cases.

*Research sponsored by DOE, Office of Energy Information Administration.

[†]UCC-ND Computer Sciences Division.

[‡]Energy Division.

^SKnox College, Galesburg, Illinois.

^TLos Alamos Scientific Laboratory.

7.4. HIGHLIGHTS OF THE ORNL MODEL EVALUATION METHODOLOGY AND THE EVALUATION OF LEAP*

C. R. Weisbin R. G. Alsmiller, Jr.

*(Abstract of paper presented at Third Symposium of the Institute of Gas
Technology on Energy Modeling, Chicago, Illinois, August 4-8, 1980)*

This paper describes progress made at the Oak Ridge National Laboratory toward development and demonstration of a methodology for evaluating energy-economic modeling codes and important results derived from these codes. To bolster traditional evaluation methods with more quantitative procedures of interest to the Office of Validation Analysis of the Energy Information Administration, ORNL is applying sensitivity theory as part of a comprehensive effort to quantify the importance of various data and model parameters to key results of interest. Two types of sensitivity analysis approaches, screening and adjoint perturbation theory, are discussed. Other essential program elements described in some detail include computational experience, assessment of model structure and rationale, and evaluation of the model input data. Preliminary findings from application of this approach to the Long-Term Energy Analysis Program (LEAP) used in obtaining projections (Model 22C) for the 1978 EIA Annual Report to Congress are presented.

*Research sponsored by DOE, Office of Energy Information Administration.

7.5. SPECIFICATION OF THE EQUATIONS FOR LEAP MODEL 22C*

M. Goldstein R. G. Alsmiller, Jr. J. Barish[†]

(Abstract of ORNL-8707, in press)

This report describes the equations implemented in the LEAP Model 22C. The equilibrium equations of each of the processes contained in the LEAP Model 22C are specified, and the interrelations of the various equations are discussed. No attempt is made to derive the equations or to discuss their validity from an economic point of view.

*Research sponsored by DOE, Office of Energy Information Administration.

[†]UCC-ND Computer Sciences Division.

8.0 INTRODUCTION

Systems reliability and operational research is a new area of development within the Engineering Physics Division. It consists of research in risk assessment, risk analysis, common cause methodology, systems analysis, operations research and the data analysis needed to support these efforts. Two previously existing data analysis efforts, SACRO and CREDO, are included.

Since 1979, the Division has been involved in risk-related programs for the Nuclear Regulatory Commission, especially programs involving acceptable risk and common cause methodology (i.e., fires and floods), and two reports have been produced (see papers 8.4 and 8.12 in this report). However, because of a lack of expertise in this area among Division staff, most of this work has been subcontracted and the Division's role has been that of program management and technical direction. In the future the subcontracting effort will be gradually reduced and more in-house effort expended on such programs as staff is added in this area.

Finally, the division has initiated several areas of research dealing with operations research. These areas specifically support NRC research needs in the area of human factors. One program seeks to obtain correlations between simulator and field response data, including planning and carrying out simulator experiments (see papers 8.2 and 8.5), and also deals with assessment of simulator capability. A second program is assessing the role of a nuclear power plant operator (generalized task analysis) during emergency conditions and seeks to formulate criteria to enable objective assessment of the impact on nuclear reactor safety of proposed operational aids, such as improved diagnostic and analysis systems, upgraded control room design, expanded use of computers, etc.

Over all these systems, reliability and operations oriented programs are expected to expand into a major area of work within the Division. It is expected that most of the effort will be suggested either by the Nuclear Regulatory Commission or by the Department of Energy for LMFBR-related research.

8.1. CRITERIA FOR SAFETY-RELATED NUCLEAR PLANT OPERATOR ACTIONS: A PRELIMINARY ASSESSMENT OF AVAILABLE DATA (I)*

P. M. Haas T. F. Bott

(Abstract of ORNL/NUREG/TM-330, July, 1979)

An increasing recognition of the profound importance of operator action on nuclear power plant reliability and safety has prompted formulation of ANSI Standard N660 by an American Nuclear Society Writing Group (58.8). This standard attempts to address operator action in terms of the time required for response to a PSAR Chapter 15 event.

This report reviews the history and content of ANSI Standard N660 and outlines a program for building a data base on operator response to such events. A preliminary assessment of the availability of field data at nuclear plants, as well as methods for collecting these data, are presented. Augmentation of field data by simulator studies and calibration of the simulator to field data are discussed. Field data collected in a pilot study are presented along with the results of operator opinion surveys. A statistical analysis of data on response time for inadvertent safety injection is included.

It is concluded that sufficient field data exist to allow calibration of simulator studies, but not a data base comprised solely of field data. Data sources and collection techniques are recommended. Conclusions based on operator interviews are presented and a program for further studies is outlined.

* Research sponsored by U. S. Nuclear Regulatory Commission, Office of Nuclear Regulatory Research, under Interagency Agreement DOE 40-551-75.

8.2. CRITERIA FOR SAFETY-RELATED NUCLEAR PLANT OPERATOR ACTIONS: A PRELIMINARY ASSESSMENT OF AVAILABLE DATA (II)*

P. M. Haas T. F. Bott

(Abstract of paper presented at Joint Conference, 8th Advances in Reliability Technology Symposium and 3rd European Reliability Data Bank Seminar, University of Bradford, United Kingdom, April 9-11, 1980; proceedings published in NCSR-823, Vol. 2, pp. 197-217, July 1980)

The need for a quantitative data base on reliability of nuclear power plant operators has long been recognized by human factors and reliability analysts, and the great need for further assessment of operator performance under accident conditions has been dramatically emphasized by the incident at Three Mile Island-2. In the U.S., an effort has been underway for a number of years to develop a design standard to define when required manual operator action can be accepted as part of a nuclear plant design basis. Insufficient data are available to provide quantitative guidelines for the standard.

To provide the necessary data base to support such standards and the necessary quantitative assessment of operator reliability, the U. S. Nuclear Regulatory Commission is sponsoring a study at Oak Ridge National Laboratory to develop the data base. A preliminary assessment completed in April, 1979 concluded that sufficient data from U.S. operating experience did not exist to provide an adequate data base. A program of research using full-scope nuclear plant simulators and results that are correlated to field data was suggested. That program was recently initiated. This paper reviews the approach, results, and conclusions of the preliminary assessment and summarizes the planned research program of simulator studies.

* Research sponsored by U. S. Nuclear Regulatory Commission, Office of Nuclear Regulatory Research, under Interagency Agreement DOE 40-551-75.

8.3. A SYSTEMS APPROACH TO DEFINING OPERATOR ROLES*

R. A. Kisner[†] G. F. Flanagan

(Abstract of paper presented at Symposium on Nuclear Power Systems, Orlando, Florida, November 5-7, 1980)

This paper briefly describes the elements of a systems approach for defining the role of the operating crew of a nuclear power plant. A systems approach aims at solving the multifaceted and interrelated problems produced by complex man-machine systems. Through systems analysis and engineering, an organized and systematic approach to the proper allocation of roles between man and machine can be made. This approach is utilized here to develop a methodology for specifying the optimum role of the crew in a nuclear plant system and also defining the internal structure of the crew for the purpose of ensuring the safe and economic operation of the plant.

*Research sponsored by U. S. Nuclear Regulatory Commission, Office of Nuclear Regulatory Research, under NRC Interagency Agreement 40-550-75.

[†]Instrumentation and Controls Division.

8.4. APPROACHES TO ACCEPTABLE RISK: A CRITICAL GUIDE*

B. Fischhoff[†] S. Lichtenstein[†] P. Slovic[‡]
R. Keeney[†] S. Derby[§]

(Abstract of NUREG/CR-1614, ORNL/Sub-7656, December, 1980)

Acceptable-risk decisions are an essential step in the management of technological hazards. In many situations, they constitute the weak (or missing) link in the management process. The absence of an adequate decision-making methodology often produces indecision, inconsistency, and dissatisfaction. The result is neither good for hazard management nor good for society.

This report offers a critical analysis of the viability of various approaches as guides to acceptable-risk decisions. It does so by:

- (1) Defining acceptable-risk decisions and examining some frequently proposed, but inappropriate, solutions.
- (2) Characterizing the essential features of acceptable-risk problems that make their resolution so difficult. These are: uncertainty about how specific problems are to be defined, difficulties in ascertaining crucial facts, the problematic nature of the value issues that arise, the vagaries of human behavior that render responses to hazards unpredictable, and inability to assess the adequacy of decision-making processes and the degree to which their conclusions are to be trusted.
- (3) Creating a taxonomy of decision-making methods, identified by how they attempt to address the features of acceptable-risk problems listed below. The major categories discussed here are:
 - Professional adjustment: allowing technical experts to devise solutions;
 - Bootstrapping: searching for historical precedents that embody guides to future decisions; and
 - Formal analysis: theory-based procedures for modeling problems and calculating the best decision.
- (4) Specifying the objectives that an approach should satisfy in order to guide social policy. These are: comprehensiveness, logical soundness, practicality, openness to evaluation, political acceptability, institutional compatibility, and conduciveness to learning.

(5) Rating the success of the approaches in meeting these objectives. Namely: How well does each approach satisfy each objective? How satisfactory are the approaches relative to one another? How might one choose the most adequate approach for different decision problems?

*Research sponsored by U.S. Nuclear Regulatory Commission, Office of Nuclear Regulatory Research, under Interagency Agreement 40-550-75.

†Decision Research, Branch of Perceptronics, 1201 Oak Street, Eugene, OR 97401.

‡Woodward-Clyde Consultants, 3 Embarcadero Center, San Francisco, CA 94111.

§Stanford University, Stanford, CA 94305.

8.5. NUCLEAR POWER PLANT SIMULATORS: THEIR USE IN OPERATOR TRAINING AND REQUALIFICATION*

D. W. Jones[†] D. K. Baer[†] C. C. Francis[†] J. M. Winders[†]
P. M. Haas L. S. Abbott R. L. Dietz[†]

[Abstract of ORNL/NUREG/TM-395 (NUREG-CR-1482), July 1980]

This report presents the results of a study performed for the Nuclear Regulatory Commission to evaluate the capabilities and use of nuclear power plant simulators either built or being built by the U.S. nuclear power industry; to determine the adequacy of existing standards for simulator design and for the training of power plant operators on simulators; and to assess the issues about simulator training programs raised by the March 28, 1979, accident at Three Mile Island Unit 2. Nuclear plant simulators have generally used state-of-the-art technology for the time at which they were designed, and their general scope and fidelity has been satisfactory for most of the anticipated training needs. The PWR simulators can duplicate the multiple malfunctions that occurred at TMI-2; however, improvements in the existing technology would probably be required to model the saturated conditions that developed in the TMI-2 coolant system or to model balance-of-plant systems, should such capability be ruled to be desirable. The NRC has no specific requirements for using simulators in training programs; however, the NRC recognizes that training on simulators both reduces power plant down time and allows training in handling programmed malfunctions. It therefore accepts successful completion of approved simulator training programs by both cold and hot license candidates as fulfilling the requirements for reactor operator experience and it endorses the ANSI/ANS standard covering simulator training programs (No. 3.1). It has not endorsed the ANSI/ANS standard for the simulators themselves (No. 3.5), except indirectly by accepting training programs using simulators that meet the ANSI/ANS-3.5 standard. The nuclear industry has voluntarily met the requirements of both ANSI/ANS-3.1 and ANSI/ANS-3.5 and has also developed additional standards. While this is commendable, it is the conclusion of this study that both ANSI/ANS standards should be expanded, strengthened, and endorsed by the NRC; that simulator training should be required; and that a well-defined regulatory structure for simulators and simulator training programs should be developed. The most obvious deficiency in the present standards is the absence of a methodology and data base to comprehensively and objectively assess the relative importance of specific malfunctions and thereby define the most important exercises to be included in a training program. This deficiency was considered to be sufficiently serious that the present study was expanded to include the development of a preliminary methodology and to illustrate its application.

*Research sponsored by U. S. Nuclear Regulatory Commission, Office of Nuclear Regulatory Research, under NRC Interagency Agreement 40-551-75.

†Center for Nuclear Studies, Memphis State University, Memphis, TN.

8.6. SODIUM COMPONENT RELIABILITY DATA COLLECTION AT CREDO*

T. F. Bott P. M. Haas J. J. Manning
(Reprint of Trans. Am. Nucl. Soc. 32, 480, 1979)

The Centralized Reliability Data Organization (CREDO) has been established at Oak Ridge National Laboratory (ORNL) by the U. S. Department of Energy (DOE) to provide a national center for collection, evaluation, and dissemination of reliability data for advanced reactors. The general goals and program plan for development of CREDO have been outlined previously.^{1,2} The current schedule calls for development at a moderate pace, with the first major distribution of data in late FY-1980.

While the system is being developed and continuous data collection at the two U. S. reactor sites (EBR-II and FFTF) is being established, data on advanced reactor components, which have been in use at U. S. test loops and experimental reactors, have been collected and analyzed. Engineering, operating, and event data on sodium valves, pumps, flow-meters, rupture disks, heat exchangers, and cold traps have been collected from more than a dozen sites. This paper summarizes the results of analyses of the data performed to date.

Sodium Valve Data

By far, the most abundant data available are on sodium valves. A total of more than 700 valves ranging in size from 1/4 to 6 in., representing a total of more than 37 million valve-hours of operation, are included in the data base. The operating and event (failure) history of each valve was extracted from site log books and other records in as much detail as possible.

The data were analyzed by treating them as progressively censored life tests. First, point and interval (90% confidence) estimates of the failure rate were calculated under the frequently made assumption of exponentiality. Then, the hazard plotting technique developed by Nelson³ was used to identify time-dependent variation in failure rates. By plotting on different types of paper (linear for the exponential model, log-log for the Weibull model) the appropriate model can be selected, and the model parameters can be estimated. Table 8.6.1 lists for a number of different data sets the point and interval estimates of the failure rate λ , the value of λ estimated from the linear hazard plot, the Weibull scale (α) and shape (β) parameters estimated from the log-log hazard plots, and the inverse of the mean-time-to-failure $\bar{\mu}$ calculated for the prescribed Weibull distribution. The estimated failure rates are typical of those presented in the literature for water and steam valves.² Most of the plots for data sets with more than a few failures did indicate exponential behavior for at least a portion of the lifetime. However, the majority of the data sets were better represented over the complete span of operating time by a Weibull model.

For most of the data sets, the estimated value of β is less than unity, which suggests a decreasing failure rate (DFR) with time. Two sets (GPL and LMEC) have β 's greater than unity, which suggests an increasing failure rate (IFR). Barlow and Campo⁴ have presented a graphical method for analyzing data which provides (among other things) a means for quantifying the tendency toward either DFR or IFR. The method applies a derived statistic called the "total-time-on-test" transform (designated here as H_T). The resulting graphical procedure provides an indication of whether the data are exponential or whether the exponential hypothesis should be rejected. If the latter is the case, it gives an estimate of the level of significance for rejecting the hypothesis.

The indication from the H_T plots and the significance levels for rejecting the exponential hypothesis are listed in the last two columns of Table 8.6.1. For TTL, EBR-II, the MSAR loops, and SRE, the indication of DFR behavior is quite strong. There are a number of reasons that a decreasing failure rate may be indicated, in addition to the classical "wear-in" behavior. One is that maintenance and operating practices may improve with experience, and reduce the number of failures. This may well have been the case at EBR-II, where there is a constant sample size and the number of failures per year did decrease over a period of years.

EM Sodium Pumps

Data collected on other sodium components are being analyzed. At the present time, the quantity and completeness of the data are sufficient to make initial quantitative estimates for three groupings of EM pumps. Operating histories of 12 EBR-II pumps with a total of 680,165 operating hours (maximum lifetime of 71,600 for any one pump) were combined to yield an estimated failure rate of $1.6 \times 10^{-5}/h$. Data from three sodium test loops at HEDL were pooled to form a sample consisting of 10 pumps with a total of 354,800 operating hours (maximum lifetime of 55,000 h). There were two reported failures, and the estimated failure rate is $5.6 \times 10^{-6}/h$. Data from three MSAR loops (six pumps, 186,000 operating hours and nine reported failures) yield an estimate of $5.9 \times 10^{-5}/h$ for the EM pump failure rate at that site. No attempt has been made to pool data from different sites.

The information available and analysis performed to date on these EM pumps are far from complete. The results should be used with caution and should not be extrapolated to current pumps in sodium reactors without very careful consideration. However, the data do reflect actual operating experience in the U. S., and results should be useful for at least a first approximation to predict behavior of current pumps.

Conclusions

A considerable base of historic data on sodium valves has been accumulated and analyzed. Quantitative estimates of failure behavior have been made; numerical estimates of failure rates are similar to those reported for water and steam valves. Fewer data and results are available for other sodium components, but quantitative estimates have been made on selected sets of EM pump data from EBR-II and test loop experience which should be useful to some extent in predicting behavior of current pumps.

* Research jointly sponsored by the Nuclear Power Development Division and the Reactor Research and Technology Division of the DOE Office of Nuclear Energy Programs.

1. G. F. Flanagan et al., "CREDO: A Reliability Data Analysis Center for Advanced Reactors," Trans. Am. Nucl. Soc. 27, 638 (1977).
2. T. F. Bott and P. M. Haas, "Initial Data Collection Efforts of CREDO: Sodium Valve Failures," 5th Symposium on Reliability Technology, University of Bradford, Bradford, United Kingdom, NCSR-R20 (Sept. 1978).
3. W. Nelson, "Hazard Plotting for Incomplete Failure Data," J. Quality Technol. 1, 1 (Jan. 1969).
4. R. E. Barlow and R. Campo, "Total Time on Test Processes and Applications to Failure Data Analysis," in Reliability and Fault Tree Analysis, Barlow, Fussell, and Singpurwalla, Eds., Society of Industrial and Applied Mathematics (1975).
5. G. Snair, G. Mirliss, and W. Dewart, "Summary of LMEC Sodium Valve Operating History," TI-00-LME-023 (1978).
6. Personal Communication, LMEC (ETEC) personnel (1978).
7. THORS Loop Records, prepared by P. Gnadt, ORNL Engineering Tech. Division.
8. Series of Published Operating Reports; e.g., "Effect of High Temperature Sodium on Austenitic and Ferritic Steels," Quarterly Progress Report, April-May-June 1966, MSAR 66-149 (July 1966).
9. LMEC-MEMO-69-7, rev. 1 (1970); plus EBR-II operating records.
10. TTL, PAL, and CRCTA Loop Operating Records, extracted by D. R. Ward, ORNL, with assistance of HEDL staff.
11. GPL Operating Records, extracted and summarized by WARD staff.
12. W. J. Freede and J. P. Thorel, "AI/LMEC Experience with Freeze-Seal and Bellows-Seal Valves," TI-00-LME-14 (Jan. 17, 1972).

Table 8.6.1 Estimated Parameters from Sodium Valve Failure Data

Data Set Description* (Population)	Exponential Model, λ ($10^{-5}/h$)			Weibull Model			Trend	Significance %
	MLE	Interval	Estimate from Plot	$x(h)$	β	$1/\lambda(h^{-1})$		
LMC^{1,6}								
Manual, Freeze Seal (93)								
All Modes	3.8	1.9-6.1	3.2	1.74E 05	1.30	6.2E-06	Possibly Exponential	1 Crossing
Inoperative	3.4	1.7-6.2						
External Leakage	0.4	0.02-2.0						
Manual, Bellows Seal (21)								
External Leakage	0.0	0.0-11.5						
Pneumatic (41)								
Inoperative	7.9	2.2-20.4						
THORS⁷ (66 Valves, All Bellows Seal)								
All Modes	10.9	6.5-16.8	10.0	2.61E 05	0.61	1.6E-06	DFR	7
Inoperative	10.1	5.9-15.9						
External Leakage	0.8	0.4-3.6						
MSAR⁸ (All Manual, Bellows Seal Valves; All Modes Combined)								
Loop-1: High Carbon (50)	20.5	15.1-30.9	42.0	3.69E 05	0.73	1.3E-06	DFR	4
Loop-2: High Oxygen (54)	24.1	17.2-32.9	25.0	3.55E 05	0.83	1.4E-06	DFR	3
Loop-3: Reactor Sodium (45)	7.1	2.9-16.0						
EBR-II⁹								
Manual, Bellows Seal (64)	0.9	0.5-1.7						
Pneumatic/Motor Operated Bellows Seal (29)	2.9	1.6-4.8						
All Valves	1.6	1.02-2.3		9.94E 05	0.55	0.38E-06	DFR	5
TTL¹⁰ (All Bellows Seal Remote Actuated-53) All Modes								
	88.2	69.6-118.3	70.4	1.3E 04	0.52	41.0E-06	DFR	3
PAL¹⁰ (All Bellows Seal Remote Activated-40) All Modes (14 out of 17 failures by Mode 3 - stuck)								
	14.9	9.5-22.3	11.6	2.4E 05	0.45	0.63E-06	DFR	12.5
CRCTA¹⁰ (All Bellows Seal Remote Actuated-36) All of 7 failures by Mode 3 O stuck								
	5.3	2.5-9.9	6.6	2.1E 05	0.90	2.3E-06	DFR	14
GPL 1 & 2¹¹ (All Bellows Seal Remote Activated-36) All Modes (only 5 failures total; 2 by External Leakage, 3 by Sticking)								
	8.5	3.3-17.9	23.2	2.3E 04	1.39	47.6E-06	DFR	20
SRE^{9,12} (All Bellows Seal)								
	13.7	9.3-19.4	14.8	1.22E 05	0.70	3.8E-06	DFR	4
Manual (71)								
All 23 reported failures by Mode 2 - External Leakage								

* Acronyms: LMEC - Liquid Metal Engineering Center (Rockwell International); THORS - Thermal Hydraulic Out-of-Reactor Safety (Oak Ridge National Laboratory); MSAR - Mine Safety Appliance Research; TTL - Transient Test Loop (Hanford Engineering Development Laboratory); PAL - Prototype Applications Loop (Hanford Engineering Development Laboratory); CRCTA - Composite Reactor Components Test Activity (Hanford Engineering Development Laboratory); GPL - General Purpose Loop (Westinghouse Electric Corporation/Advance Reactors Division); SRE - Sodium Reactor Experiment.

8.7. DEVELOPMENT OF THE CENTRALIZED RELIABILITY DATA ORGANIZATION (CREDO)*

T. F. Bott G. W. Cunningham† N. M. Greene† P. M. Haas
S. D. Hudson H. E. Knee J. J. Manning

(Abstract of paper presented at Joint Conference, 6th Advances in Reliability Technology Symposium and 3rd European Reliability Data Bank Seminar, University of Bradford, United Kingdom, April 9-11, 1980; proceedings published in NCSR-R24, pp. 309-334, July 1980)

The Centralized Reliability Data Organization (CREDO) has been established by the Reactor Research and Technology Division of the Department of Energy (RRT/DOE) at Oak Ridge National Laboratory (ORNL). Its primary functions are collection, evaluation and dissemination of reliability/availability data pertaining to advanced reactors. Associated information and analysis services will be provided to users. Interface and cooperative data exchange with existing U. S. and international data banks is an integral part of CREDO's program plan. This paper outlines the design and operation of the proposed system and summarizes the status of its development. The schedule for developing CREDO has been lengthened as appropriate to the current schedule for development of advanced reactors in the U. S., but the initial development phase is nearing completion, and demonstration of system capabilities is anticipated prior to the end of FY 1980.

* Research jointly sponsored by the Nuclear Power Development Division and the Reactor Research and Technology Division of the DOE Office of Nuclear Energy Programs.

† UCC-ND Computer Sciences Division.

8.8. SACRD: A DATA BASE FOR FAST REACTOR SAFETY COMPUTER CODES -- GENERAL DESCRIPTION*

N. M. Greene† V. M. Forsberg† G. B. Raiford†
J. W. Arwood† D. B. Simpson G. F. Flanagan

(Abstract of ORNL-5477, Vol. 1, September, 1978)

SACRD† is a data base of material properties and other handbook data needed in computer codes used for fast reactor safety studies. Data are available in the thermodynamics, heat transfer, fluid mechanics, structural mechanics, aerosol transport, meteorology, neutronics, and dosimetry areas. Tabular, graphical and parameterized data are provided in many cases. A general description of the SACRD system is presented in this document.

* Research sponsored by DOE Office of Nuclear Energy Programs, Division of Reactor Research and Technology.

† UCC-ND Computer Sciences Division.

‡ SACRD is an acronym for Safety Analysis Computerized Ractor Data.

8.9. SACRD: A DATA BASE FOR FAST REACTOR SAFETY COMPUTER CODES -- CONTENTS AND GLOSSARY OF VERSION 1 OF THE SYSTEM*

N. M. Greene† V. M. Forsberg† G. B. Raiford†
J. W. Arwood† D. B. Simpson G. F. Flanagan

(Abstract of ORNL-5477, Vol. 2, September, 1978)

SACRD is a data base of material properties and other handbook data needed in computer codes used for fast reactor safety studies. This document lists the contents of Version 1 and also serves as a glossary of terminology used in the data base. Data are

available in the thermodynamics, heat transfer, fluid mechanics, structural mechanics, aerosol transport, meteorology, neutronics and dosimetry areas. Tabular, graphical and parameterized data are provided in many cases.

* Research sponsored by DOE Office of Nuclear Energy Programs, Division of Reactor Research and Technology.

† UCC-ND Computer Sciences Division.

8.10. TECHNICAL NOTE: SACRD — A DATA BASE FOR FAST REACTOR COMPUTER CODES*

N. M. Greene† G. F. Flanagan H. Alter†

[*Excerpt from Nuclear Safety 20(3), 276, 1979*]

An effort to provide a central computerized data collection for fast reactor safety computer codes was initiated in 1975. This data base was intended to encompass non-problem-dependent data related to liquid-metal-cooled fast breeder reactors, especially at extreme conditions where little or no data are available; however, the scope was subsequently expanded to cover other advanced reactor concepts needing property data at accident conditions.

A central data base has many potential advantages. The single source of data makes it easier to compare results from different calculational schemes since all codes can use identical data. An evaluated reference source helps remove the problem of having to justify the use of a set of data since the data have already received a thorough screening and review. Most important, however, is the improvement and expansion of the available data, which can be assured with a data base that is maintained on a continuing basis. For these reasons the Division of Reactor Research and Technology of the Department of Energy requested Oak Ridge National Laboratory to accept the responsibility for establishing the SACRD (Safety Analysis Computerized Reactor Data) data base and coordinating activities related to it.

The organizational structure of SACRD is very similar to those associated with several other successful data banks, in particular, the Evaluated Nuclear Data File (ENDF) and the Nuclear Systems Materials Handbook (NSMH). The direction of SACRD is guided by a central committee of experts and interested persons, with subcommittees typically composed of five to ten members. Present subcommittees are Thermophysical Properties, Structural Mechanical Properties, Fuel Mechanical Properties, Aerosol Transport Properties, Radiological Data, Neutronic Data, and External Code Interfaces and Formats.

Version 1 of SACRD was released in January 1979. This release consisted of (1) a document summarizing goals and operational procedures, (2) a document identifying terms used to classify and catalog SACRD data and also serving as a data catalog, (3) a magnetic tape containing all the information collected in Version 1, and (4) a computer program that searches and edits the magnetic tape. These items were sent to representatives of all major laboratories and vendors involved in the advanced reactor safety area in the United States.

New data have been added to SACRD since the release of Version 1. These additional data will be listed in current SACRD data catalogs as interim data and will become part of the official data base in the next general release, which is scheduled two to three years after the release of Version 1. These interim data will be distributed on request.

An effort is underway to collect uncertainty information related to the data already in Version 1. This information will form a new data collection for SACRD and will be available through the same procedures as for other data.

* Research sponsored by DOE Office of Nuclear Energy Programs, Division of Reactor Research and Technology.

† UCC-ND Computer Sciences Division.

‡ Branch Chief, Safety Analysis Branch, DOE Division of Reactor Research and Technology.

8.11. SACRD - A DATA BASE FOR FAST REACTOR SAFETY COMPUTER CODES - OPERATIONAL PROCEDURES*

V. M. Forsberg[†] J. W. Arwood[†]
N. M. Greene[†] G. B. Raiford[†]

(Abstract of ORNL/CSD-53, September, 1980)

SACRD (Safety Analysis Computerized Reactor Data) is a data base of nondesign-related information used in computer codes for fast reactor safety analyses. This document reports the procedures used in SACRD to help assure a reasonable level of integrity of the material contained in the data base. It also serves to document much of the computer software used with the data base.

* Research sponsored by DOE Office of Nuclear Energy Programs, Division of Reactor Research and Technology.

[†]UCC-ND Computer Sciences Division.

8.12. A METHODOLOGY AND A PRELIMINARY DATA BASE FOR EXAMINING THE HEALTH RISKS OF ELECTRICITY GENERATION FROM URANIUM AND COAL FUELS*

A. A. El-Bassioni[†]
With Contributions from Other SAI Staff Members

(Abstract of NUREG/CR-1539, ORNL/Sub-7615/1, August, 1980)

An analytical model was developed to assess and examine the health effects associated with the production of electricity from uranium and coal fuels. The model is based on a systematic methodology that is both simple and easy to check, and provides details about the various components of health risk.

A preliminary set of data that is needed to calculate the health risks was gathered, normalized to the model facilities, and presented in a concise manner. Additional data will become available as a result of other evaluations of both fuel cycles, and they should be included in the data base.

An iterative approach involving only a few steps is recommended for validating the model. After each validation step, the model is improved in the areas where new information or increased interest justifies such upgrading. Sensitivity analysis is proposed as the best method of using the model to its full potential.

Detailed quantification of the risks associated with the two fuel cycles is not presented in this report. The evaluation of risks from producing electricity by these two methods can be completed only after several steps that address difficult social and technical questions. Preliminary quantitative assessment showed that several factors not considered in detail in previous studies are potentially important.

* Research sponsored by U.S. Nuclear Regulatory Commission, Office of Nuclear Regulatory Research, under Interagency Agreement 40-550-75.

[†]Science Applications, Inc.

9.0. INTRODUCTION

Since it was established in 1962, the Division's Radiation Shielding Information Center (RSIC) has become a model of technology transfer, especially as a result of its technical activities associated with computer code and data exchange. In addition to RSIC, the Division now has two other information analysis and data centers: the Reactor Safety Research Data Repository (RSRDR) and a Technical Data Management Center (TDMC), both established under sponsorship of the Nuclear Regulatory Commission to validate and standardize computing technology and to organize, manage, and disseminate selected data bases for use in NRC licensing and regulatory processes. Management of the work of RSIC, RSRDR, and TDMC falls under the umbrella of the Engineering Physics Information Centers (EPIC) (see page A-41). Management of the Biomedical Computing Technology Information Center (BTIC), a center initiated in the Division in 1975 and developed into a successful prototype, was transferred in FY 1980 into a medical research environment at Vanderbilt University.

Radiation Shielding Information Center (RSIC)

RSIC, now in its 18th year, continues to be our largest and most widely used information center. Established to promote the exchange of shielding technology, it acts as a resource base for both government and civilian agencies in the United States and in foreign countries and performs such diverse functions as providing bibliographic information; testing, assembling, and distributing computer codes; preparing, testing, and distributing multigroup cross-section libraries, both fine-group and broad-group; collecting and distributing other types of data bases; holding seminars to educate the shielding community on particular techniques, especially computer techniques; helping to establish shielding benchmark problems and shielding standards; and generally providing problem assistance to requesters.

The RSIC scope includes the physics of interaction of radiation with matter; radiation production, protection, and transport; radiation detectors and measurements; engineering design techniques; shielding materials properties; computer codes useful in research and design; and nuclear data compilations. The goals of RSIC are to function as a technical institute to provide information (bibliographic and other data, computer codes, technical advice) upon request; collect, evaluate, enrich, distill, and repackage information to extend the state-of-the-art, bringing into the public domain technology more usable and more valuable than the sum of the input; and to initiate and effect research and development in areas of need that can be managed by RSIC personnel.

Results from some of the RSIC activities during the current reporting period have already been cited in Section 3.0, in particular, the development and validation, in collaboration with other Division staff members, of the 171-neutron and 36-gamma-ray group VITAMIN-C and VITAMIN-E data libraries and of others derived from them. Other data activities have also been mentioned. RSIC has continued to participate in the work of the Cross Section Evaluation Working Group (CSEWG), with the Shielding Subcommittee presently chaired by an RSIC staff member. Other staff members are actively involved with the American Nuclear Society in developing radiation protection and shielding standards and standards for computer programming and computer code documentation.

In the area of computing technology, RSIC now makes available 556 computer code packages and 78 data packages. The RSIC Newsletter is currently mailed monthly to 1663 people. During FY 1980, more than 3500 letters/telephone calls of requests were processed by RSIC, resulting in 9400 separate activities required to satisfy the requests. A total of 96 (37 foreign) persons came for an orientation visit and/or to use the center's facilities.

An important highlight for the year was a seminar-workshop on Theory and Application of Monte Carlo Methods (April 1980), the proceedings of which were published as ORNL/RSIC-44. The seminar-workshop was well attended and this contributed materially to an advancement in the state-of-the-art at a number of institutions.

The RSIC computer-based information system (SARIS), now having more than 7000 literature references, is accessible on-line nationally through the DOE RECON system. The sixth indexed bibliography was printed from the data files using computer-based type-setting programs.

The computer-based statistical record system (ADES), initiated on the central DEC System 10, is now operable on the EPIC minicomputer (ECLIPSE).

Reactor Safety Research Data Repository (RSRDR)

RSRDR, the repository and distribution center for reactor safety research data, sponsored by the Division of Reactor Safety Research of the U.S. Nuclear Regulatory Commission (NRC), was established in FY 1978. RSRDR serves as the archival repository and response center of the NRC/RSR Data Bank System, which also includes Data Base Managers and a Data Bank Processing System located at the Idaho National Engineering Laboratory (INEL). The stored data (currently 34 Semiscale and LOFT test data tapes) are available on demand to NRC contractors, to contributors to the Data Bank, and to other individuals or organizations working in the field of reactor safety.

Technical Data Management Center (TDMC)

TDMC was established to serve NRC licensing and regulation programs with goals and priorities determined by an advisory committee of NRC staff members chaired by the contract monitor within the Division of Technical Information and Document Control of the NRC Office of Administration. The objectives of the program are to define, develop, and maintain a center for the acquisition, analysis, packaging, documenting, and dissemination of technical data (numeric, methodology, computing technology) for use by NRC staff, licensees, contractors, and others engaged in related work. A further objective is to develop the methodology necessary to process the data for accurate analysis and for efficient retrieval of documented data upon request.

Current work in progress (FY 1980) includes program enhancement and documentation for radiological assessment and for the meteorological evaluation of effluent releases from nuclear power plants. The work also includes application of the "open code/data package concept" to the SCALE (Standardized Computing-Analysis for Licensing Evaluation) System, methodology developed at ORNL to provide analytical capabilities (criticality safety, radiation shielding, heat transfer) to be applied to safety analyses of equipment and facilities proposed for licensing by NRC. The initial version of the automated SCALE system, released in FY 1980, consists of a system driver, functional modules, a numeric nuclear data base, a materials information processor, and system control modules for out-of-core criticality safety studies.

9.1. INFORMATION ANALYSIS CENTERS*

E. Talmi Carroll[†] B. F. Maskewitz

(Excerpt from Introduction to Chapter 9 of "Manual Center of Information Science and Technology," Vol. 18, W. B. Williams, ed., Knowledge Industry Publications, Inc., 4801a Plains, D.C., 1981.)

The Panel sees the specialized information center as a major key to the rationalization of our information system. We believe the specialized information center should be primarily a technical institute rather than a technical library. It must be led by professional working scientists and engineers who maintain the closest contact with their technical professions [and] can make new syntheses [with] the data at their fingertips.

U.S. PRESIDENT'S SCIENCE ADVISORY
COMMITTEE (PSAC)

The recommendation above from the U.S. PRESIDENT'S SCIENCE ADVISORY COMMITTEE (PSAC) in 1963 introduced the concept of the formalized unit called the information analysis center (IAC) to both the technical and the information communities. Centers for analyzing scientific information have existed since man's earliest attempts to understand his universe. KERTESZ (1970) points out that the great compilers of the nineteenth century, such as Beilstein and Gmelin, were really one-man analysis centers in the truest meaning of the concept. Their data compilations are the precursors of the most acclaimed products of the formalized IACs of the twentieth century. WEINBERG (1964), who was chairman of the U.S. President's Advisory Committee, looked back to the likes of Mendel and Bohr when he projected that the function of the IAC would be similar to the efforts of the great theorists who reduce the need for the larger body of literature by aggregating diverse data and ideas into a higher level of insight. This was how the IACs would help solve the crisis caused by the post-World War II information explosion.

An 18-year literature review of the IAC is the goal of this chapter. We attempt to summarize what has been published so that those who want only an overview will find it here. Those who want more detail will find an extensive bibliography.

*Work supported by U.S. Department of Energy.

[†]Franklin Research Center.

9.2. SURVEY OF USA MAJOR DATA BASE MANAGEMENT SYSTEMS*

B. F. Maskewitz C. E. Price[†]

(Summary of paper presented at DBMS-76 and the 10th International Seminar on Computational Aspects of the Finite Element Method, Berlin, Germany, August 14-21, 1976)

There is much ambiguity surrounding the terms "Data Management System" (DMS) and "Data Base Management System" (DBMS); the following will attempt to establish some definitions and understanding. A DMS is a collection of software for "handling" data - data maintenance (input, corrections, additions, deletions), query, and output (report generation). As shown in Fig. 9.2.1, a DBMS is only a portion of the DMS. For the the purpose of this survey, however, the DBMS is defined to include the Adjunct Systems shown in the figure, and the two terms are used interchangeably as 'DBMS'.

Data base management systems are generally one of two orientations:

1. Host Language Based Systems - Data-handling capability with associated language is added to a host procedural programming language (like COBOL). These systems are considered to be designer tools that aid an analyst/programmer in implementing data systems.

*Adjunct Systems may be "bundled" with some DBMS.
 DBMS costs around \$50,000.
 DMS costs around \$100,000.

Fig. 9.2.1. Data Management System (DMS).

2. Self-Contained Systems - These systems are not extensions of an existing programming language, but have their own, usually more simple and English-like, non-procedural language for handling data. Such systems are user tools that allow persons with less computer training to implement and use data-handling systems.

Some systems have both characteristics, or combine features from each. For example, a DBMS, which is host language based, may have a self-contained interface for on-line query. Conversely, a self-contained system may support interfaces to other languages.

Another characteristic of DBMS which needs consideration is the file structure used (the way data is stored) and consequently the data models supported. (This governs the way a user must visualize his stored data). A textbook is necessary to explain all this, but two basic file structures are the (1) chained or linked and (2) inverted. Chained files are usually used with the host-language-based systems whereas self-contained systems use inverted files.

A data base management system provides each user, large or small, the ability to manage all of his data economically with a single, centralized facility. It must be able to create, maintain, update and retrieve the data base; it should allow concurrent on-line and batch processing against the same data base; it should enable multiple users to simultaneously access and update the data base; and, most of all, it must simplify application development. The cost of making data available for decision-making needs is

affected in three ways: (1) reduced lead time to organize the data in a useful form; (2) reduced costs of retrieving and updating the area; and (3) reduced maintenance cost through data-independent language features.

There are many DBMSs being marketed now, both by hardware vendors and independent software companies. Many are "of age" with years of experience and use behind them. However, newer, more powerful systems are being developed, so the field is volatile and better systems may be available later.

Over the last two years, the increase in the quantity and quality of DBMSs produced in the U.S. has been overwhelming. According to a recent Frost & Sullivan report, DBMSs constitute "the single most significant software product to come along since the advent of computer operating systems." Cost savings from the use of DBMSs, minis, and distributed networks have revolutionized the industry.

Over 8,000 private companies, small businesses, large corporations and government offices in the U.S. and Canada alone have installed DBMSs. Estimates forecast that by 1982, 50% of commercial and government users of electronic data-processing equipment will be using DBMS packages. Companies now using more than one DBMS are common. Many users have found that different DBMS packages are better suited for different types of applications, even within one environment.

The results of a survey¹ of proprietary software usage among 6,000 data-processing executives indicate that both the data-processing community and data-processing applications are changing. Major changes are in the increasing emphasis on minicomputer usage, especially in distributed environments, and in the continuing conversion to data base management. There has also been large-scale transition from centralized data bases to minicomputer "Black Boxes" that offer an integrated data base providing increased applications for the entire organization.

These, and other developments will be covered in this survey of selected major DBMSs in use in the U.S. In addition to those marketed by vendors (ADABAS, DATA BOSS 2, DATACOM/DB, DMS 1100, IDMS, IMS/VS, INQUIRE, MODEL 204, SYSTEM 2000, TOTAL, and many others), several in the public domain (such as JOSHUA, ORCHIS, RECON, DOE/STOR, etc.) will be included.

An exhibit of PR material citing the features of many of the DBMSs covered in the survey will complement the presentation, and copies will be available to delegates.

* Research sponsored by the U.S. Nuclear Regulatory Commission, Office of Nuclear Regulatory Research, under Interagency Agreement 40 89 55 11 9.

† UCC-ND Computer Sciences Division.

1. "User Ratings of Proprietary Software," DATAPRO 70 report available for \$12 from Datapro Research Corp., 1805 Underwood Blvd., Delran, N. J. (USA) 08075.

9.3. THE USA NRC/RSR DATA BANK SYSTEM AND REACTOR SAFETY RESEARCH DATA REPOSITORY (RSRDR)*

B. F. Maskewitz S. F. Bankert[†]

(Summary of paper presented at SMIRT-5 and the 4th International Seminar on Computational Aspects of the Finite Element Method, Berlin, Germany, August 17-21, 1979)

The United States Nuclear Regulatory Commission (NRC), through its Division of Reactor Safety Research (RSR) of the Office of Nuclear Regulatory Research, has established the NRC/RSR Data Bank Program to collect, process, and make available data from the many domestic and foreign water reactor safety research programs. An increasing number of requests for data and/or calculations generated by NRC contractors led to the initiation of the program which allows timely and direct access to water reactor safety data in a manner most useful to the user.

The program consists of three main elements: data sources, service organizations, and a data repository. Data sources include experimental facilities, both domestic and foreign, which are actively producing test data applicable to water reactor safety research and providing experimental results and literature. The service organizations are NRC contractors responsible for implementing NRC defined tasks as follows: (a) identify and coordinate input from data sources; (b) provide an interactive computer system (NRC/RSR Data Bank Processing System) and application support for data retrieval, processing and analysis; and (c) provide measurements (collected experimental data) and computed parameters (local conditions data derived from the experimental data) to a data repository. The data repository is responsible for storage, retrieval, and dissemination, upon request, of measurement data and computed parameters. Data bank managers, appointed by NRC, select the experimental data to be included in the data bank, develop local conditions calculational methods, and generate local conditions data. All data are available realtime to NRC and NRC-designated personnel through the data bank processing system and to others through the repository.

NRC provides financial support and overall guidance of the program.

1. The Data Bank Concept. The concept of a national data bank for storing and disseminating water reactor safety data is based on the premise that a single organization can create and operate a more efficient and cost effective information support program than could the individual facilities which generate the data. Each of the major test facilities has a specific purpose in the water reactor safety effort, but they serve a mutual goal in providing data to the overall water reactor safety research objective of a safe, acceptable nuclear industry.

The NRC/RSR Data Bank Program encompasses the water reactor safety data produced by domestic research programs as well as those produced by foreign programs with which national cooperative agreements have been established. The program operates with a central data bank interacting with NRC, the experimental facilities, and data bank repositories, which, in turn interact with an external user community. The centralization of the data provides a means of sharing the data with government and industry in a timely, reliable, cost-effective manner. The costs of developing and operating duplicate data bases and support systems are eliminated and the data dissemination burden of the experimental programs is minimized.

2. The Data and Its Sources. The NRC/RSP Data Bank System is designed to manage data pertinent to research investigating the loss of coolant and other accidents for both pressurized water reactors and boiling water reactors. Data sources include experimental programs sponsored by NRC, other government agencies, private industry, and foreign governments. Specific examples include data from: Semiscale, Loss of Fluid Test (LOFT), Two Loop Test Apparatus (TLTA), Thermal Hydraulic Test Facility (THTF), Full Length Emergency Cooling Heat Transfer Facility (FLECHT), other Heat Transfer Loops, and Two Phase Pump Performance Facilities. These data were generated in NRC-sponsored experimental programs conducted at U.S. Department of Energy laboratories at Idaho National Engineering Laboratory (INEL) and at the Oak Ridge National Laboratory (ORNL), at NRC-sponsored programs within Westinghouse Corporation, General Electric Company, and within other industrial facilities, domestic and foreign.

An international collaboration in a two- and three-dimensional LOCA Reflood Program between the Federal Republic of Germany (FRG), Japan, and the United States will establish new data sources for the program. Included are two (2-D) test facilities in Japan at Tokai: Cylindrical Core Test Facility (CCTF), now started, and Slab Core Test Facility (SCTF), in the planning and construction stage. The FRG collaboration includes a 3-D Upper Plenum Test Facility (UPTF), in the planning and construction stage at PKL, Erlangen, and PKL is also the source for other data. In addition, a USA-Sweden Agreement allows for the use of the MARVIKEN reactor facilities to do experimental Break Flow Tests (BFT), now providing data for the program.

Other data sources will be included in the program as indicated by the NRC/RSP overall research and development requirements.

3. Service Organizations. Several service organizations provide for data screening and parameter selection through appointed data managers: fuel behavior verification

(INEL), steam water mixing (Battelle Columbus Laboratories), integral systems (INEL), heat transfer (INEL) and pump (MPR). EG&G Idaho, Inc. established at INEL a center for data bank administration, initial data processing, and dynamic, on-line access to the data by NRC personnel and contractors. The data are available to others through a repository established at the Oak Ridge National Laboratory (ORNL) specifically for public access.

The several data managers under NRC guidance select data for inclusion in the data bank and forward it to the INEL center for processing into the Data Bank Processing System (DBPS) using software developed for handling data in both batch and interactive modes. DBPS is implemented in the INEL CDC CYBER 70/76 computer environment. Data are stored on disks and on tapes.

The DBPS is sufficiently general to accommodate any type of data or applications, although it is most applicable to large quantities of scientific data. The DBPS is built around the structure of the data bank, which consists of a directory file and a data file. The directory file contains records which briefly describe the data in a specific data file entry (for example, a pressure measurement) and provides a locator for the actual data. Within the data file, each data record contains a word indicating the size of the record and a pointer to the next record in the data set. With this approach, the DBPS can locate data of interest without actually bringing the data into core. The DBPS retrieves the data piece by piece using the locators in the data file.

The INEL center notifies the NRC-authorized remote users that the data are available for on-line access and generates a copy of the data on magnetic tape to send to the data repository.

4. Reactor Safety Research Data Repository (RSRDR). The Reactor Safety Research Data Repository (RSRDR) is established at the Oak Ridge National Laboratory (ORNL) as one of a cluster of information centers in the Engineering Physics Division. An integral part of the NRC/RSR Data Bank System, it serves as the archival repository and response center of the NRC/RSR Data Bank System. The Repository provides a common source of experimental data for the NRC regulatory and safety research efforts and for the nuclear power industry.

The data is in the form of raw measured data (acquired from each instrument from selected facilities and experiments) that has not been processed with the exception of conversion to engineering units and application of calibration factors. It is available on demand to NRC contractors, to contributors to the Data Bank, and to other individuals or organizations working in the field of reactor safety. A nominal cost recovery fee is charged. However, charges may be waived on determination that the data is to be used in NRC-sponsored programs, or is otherwise supplied in the best interests of the NRC mission.

The RSRDR is compiling a directory of individuals and institutions interested in information concerning the data and the NRC/RSR Data Bank Program. Anyone wishing to be included may contact RSRDR. The Repository is set up to make its information quickly available, and in a form easily handled by the requesting installation. Transmittal arrangements can be made by contacting: Reactor Safety Research Data Repository (RSRDR), Engineering Physics Information Centers (EPIC) - 6025, Oak Ridge National Laboratory, P.O. Box X, Oak Ridge, Tennessee 37830. Telephone: 574-6176 (area code 615); or (FTS) 624-6176.

5. Conclusion. The NRC/RSR Data Bank Program specializes in water reactor safety experimental data, but it has a number of other scientific applications in which large amounts of numeric data are generated and require compiling, storage, and a means of access to make them available to multiple users. With the increased data gathering instrumentation that is being employed in upcoming experimental programs, the data bank concept and an associated processing system will become a necessity if the data are to be made available to those who need it. The concept of the NRC/RSR Data Bank Program is a good basis on which to build data bank programs in other areas.

* Research sponsored by the U.S. Nuclear Regulatory Commission, Office of Nuclear Regulatory Research, under Interagency Agreement 40-89-55-11-9.

† EG&G Idaho, Inc., Idaho Falls, Idaho 83401.

9.4. THE TECHNICAL DATA MANAGEMENT CENTER: A FOCAL POINT FOR METEOROLOGICAL AND OTHER ENVIRONMENTAL TRANSPORT COMPUTING TECHNOLOGY*

B. L. McGill B. F. Maskewitz D. K. Trubey

(Summary of paper presented at Symposium on Intermediate Range Atmospheric Transport Processes and Technology Assessment, Gatlinburg, Tennessee, October 1-3, 1980)

The ORNL Engineering Physics Information Centers (EPIC), the umbrella organization under which the Radiation Shielding Information Center (RSIC) functions, has established a center for extending the RSIC "open code/data package" concept to the Technical Data Management Center (TDMC) where meteorological and other environmental transport computing technology is collected, analyzed, packaged, documented and disseminated. TDMC is a national technology resource sponsored by the U.S. Nuclear Regulatory Commission (NRC).

"Open" Package Concept. "Open" codes and data libraries are those which become well-documented, closely scrutinized by the industry at large, widely used and frequently modified, i.e., open to the same critical examination given to any valid scientific information. The concept is realized when the developer, the center, and the user collaborate to assess and improve the state of the art. Positive feedback and this close interrelationship results in changes that are reflected in the "open code/data package" as updated versions. Dissemination of the packages with a training and consultant service promotes wider usage with consequent feedback to the Center. The concept serves to promote standardized methods with consequent quality assurance.

TDMC tests the various computer codes and data by running sample problems, packages them for transportability; disseminates, and assists in their implementation as needed; follows their use, and collects useful feedback; and, in interacting with the users and developers, will reflect into the "open code or data package" any resulting corrections, extensions, or other improvements.

In an effort to promote standardization and improve portability, TDMC selects specific computing technology, and under NRC direction, enhances, standardizes, improves, and documents it in order to place it in the public domain. The resulting product then receives the "open" code package treatment as described above.

Purpose and Scope. The Center's purposes are to avoid duplication of effort, advance the state of the art, and make widely available standardized methods, including computing technology and computer-readable data.

The scope of the current collection of TDMC environmental transport codes includes: atmospheric, wet and dry deposition, surface and ground water and terrestrial foods calculations. Also included are external dosimetry codes for inhalation and ingestion calculations.

The TDMC scope, its information products, and services will be displayed in a poster session. An effort will be made to give an indication of the state of the art of methodology in current usage as reflected in computing technology in the public domain. Conference attendees will be invited to become participants in the TDMC experiment through the sharing of their information and technology. A directory of those interested is in compilation and a newsletter will begin publication in the near future.

*Work funded by the U.S. Nuclear Regulatory Commission, Office of Administration, under Interagency Agreement 40-548-75.

9.5. RADIATION STREAMING IN POWER REACTORS*

G. P. Lahti[†] R. R. Lee[‡] J. C. Courtney[§]
 Editors

[Abstract of ORNL/RSIC-43 (ANS/SD-79/16), January 1979]

These proceedings consist of 14 papers given at a special session on "Radiation Streaming in Power Reactors" held on November 15 at the American Nuclear Society 1978 Winter Meeting in Washington, D. C. The papers describe the methods of calculation, the engineering of shields, and the measurement of radiation environments within the containments of light water power reactors. Comparisons of measured and calculated data are used to determine the accuracy of computer predictions of the radiation environment. Specific computational and measurement techniques are described and evaluated. Emphasis is on radiation streaming in the annular region between the reactor vessel and the primary shield and its resultant environment within the primary containment.

*Proceedings of the Special Session American Nuclear Society (ANS) Winter Meeting, Washington, D. C., November 15, 1978; cosponsored by the ANS Divisions of Mathematics and Computation (M&C) and Radiation Protection and Shielding (RP&S).

[†]Sargent & Lundy.

[‡]Combustion Engineering, Inc.

[§]Louisiana State University Nuclear Science Center.

9.6. DATA BASES FOR RAPID RESPONSE TO POWER REACTOR PROBLEMS*

B. F. Maskewitz

(Excerpt from paper presented at Seventh International CODATA Conference, Kyoto, Japan, October 8-11, 1980)

Almost two years has passed since the TMI-2 accident first captured news headlines with threat of an impending nuclear disaster. The incident has been thoroughly studied (Andrews II, 1980) and both government and industry response has been positive and long term in nature. There has been a reorganization of priorities within government research and regulatory bodies and two major institutions have been formed, the Nuclear Safety Analysis Center (NSAC) (Zebroski, 1980) of the Electric Power Research Institute (EPRI) and the Institute of Nuclear Power Operations (INPO), an independent professional organization established by the U.S. electric utilities in Atlanta, Georgia, to deal specifically with the technical and operational aspects of nuclear safety.

Much of the confusion which added to the problems of dealing with the TMI-2 accident as it was happening and immediately afterwards was due to the inability of the staff to quickly access needed information and data. In its aftermath, the several commissions and study groups made strong recommendations for remedies. The nuclear industry is now making an assessment of its needs and of the availability of data bases for rapid response to questions about power reactor problems. An effort is being made to generate new data bases to fill voids in the available information base and also to improve data base management schemes for dynamic, rapid access to the data.

This paper reviews several planned and existing data bases established for both dynamic on-line access and more considered response to nuclear power reactor problems. The relationship of the data bases to specific problem areas of reactor licensing and regulation is not always clear but some are accessible as a national technology resource in the United States. Embedded in engineering physics research and development programs and managed by knowledgeable scientists and engineers, these data bases are an integral part of the related national programs. At least two of the data bases serve an international scientific community.

*Research sponsored by DOE Office of Fusion Energy and DOE Office of Reactor Research and Technology.

9.7. RADIATION SHIELDING INFORMATION CENTER:
A SOURCE OF COMPUTER CODES AND DATA FOR FUSION NEUTRONICS STUDIES*

B. L. McGill R. W. Roussin D. K. Trubey B. F. Maskewitz

(Abstract of paper presented at Fourth American Nuclear Society Meeting on the Technology of Controlled Nuclear Fusion, King of Prussia, Pennsylvania, October 14-17, 1980)

The Radiation Shielding Information Center (RSIC), established in 1962 to collect, package, analyze, and disseminate information, computer codes, and data in the area of radiation transport related to fission, is now being utilized to support fusion neutronics technology. The major activities include: (1) answering technical inquiries on radiation transport problems, (2) collecting, packaging, testing, and disseminating computing technology and data libraries, and (3) reviewing literature and operating a computer-based information retrieval system containing material pertinent to radiation transport analysis. The computer codes emphasize methods for solving the Boltzmann equation such as the discrete ordinates and Monte Carlo techniques, both of which are widely used in fusion neutronics. The data packages include multigroup coupled neutron-gamma-ray cross sections and kerma coefficients, other nuclear data, and radiation transport benchmark problem results.

* RSIC activities are sponsored by the Department of Energy, the Nuclear Regulatory Commission, and the Defense Nuclear Agency.

9.8. THE VALIDATION OF COMPUTING TECHNOLOGY THROUGH SHARING*

B. F. Maskewitz

(Abstract of paper presented at Eighth Annual Conference of the MUMPS Users' Group, Atlanta, Georgia, June 6-8, 1979)

The computer with its associated operating systems software is gaining in popularity as a valuable tool in medical applications in a time of escalating costs, a climate of waning public credibility, and increasing questioning of medical practices by public officials. Computer usage in medicine trails that in other scientific fields where standardization and resulting wide usage is sought through efforts by the scientific community to verify and validate its own computing technology via sharing through an information clearinghouse established for the purpose. The Biomedical Computing Technology Information Center (BCTIC), established by the U.S. Department of Energy (DOE) as a focal point for the sharing of computer programs and data, offers a clearinghouse through which MUMPS Users' Group (MUG) members can collaborate in advancing the state of the art with consequent verified/validated applications programs with resultant quality assurance.

This paper examines accepted methods and procedures for verifying and validating computing technology; cites national trends which require a more credible practice in the use of computers in medicine; reviews successful techniques for validation in related areas; and details BCTIC operations and procedures which make it a suitable vehicle for MUG applications programs to be enhanced via the BCTIC "open code and data package" concept in collaboration with the MUG code developer/user.

* Work funded by DOE Office of Health and the Environment, Division of Human Health Studies.

9.9. USER'S MANUAL FOR LADTAP II - A COMPUTER PROGRAM FOR CALCULATING
RADIATION EXPOSURE TO MAN FROM ROUTINE RELEASE
OF NUCLEAR REACTOR LIQUID EFFLUENTS*

D. B. Simpson B. L. McGill

[Excerpt from preface of ORNL/NUREG/TOMC-1 (NUREG/CR-1276), May, 1980]

The main purpose of this manual is to provide a user's guide to the preparation of input for the LADTAP II computer program and to make available in one document essential information for its understanding and use. The basic methodology, published in NRC Regulatory Guides 1.109 and 1.113, is included as appendices with the permission of Technical Information and Document Control Division, Office of Administration, U.S. Nuclear Regulatory Commission. Background information on the original LADTAP code development is referenced.

A brief abstract is prepared for use by indexing services. A detailed abstract is furnished for the technical person who needs to make a quick judgment prior to requesting the complete code package from the disseminating agency.

*Work supported by U.S. Nuclear Regulatory Commission, Office of Administration, under Interagency Agreement DOE 40-548-75.

9.10. DIRECTORY OF COMPUTER USERS IN NUCLEAR MEDICINE*

J. J. Erickson[†] J. Gurney W. J. McClain[‡]

(Excerpt from ORNL/BCTIC-1/R1, September, 1979)

The *Directory of Computer Users in Nuclear Medicine* consists primarily of detailed descriptions and indexes to these descriptions. A typical *Installation Description* contains the name, address, type, and size of the institution and the names of persons within the institution who can be contacted for further information. If the department has access to a central computer facility for data analysis or timesharing, the type of equipment available and the method of access to that central computer are included. The dedicated data processing equipment used by the department in its nuclear medicine studies is described, including the peripherals, languages used, modes of data collection, and other pertinent information.

Following the hardware descriptions are listed the types of studies for which the data processing equipment is used, including the language(s) used, the method of output, and an estimate of the frequency of the particular study. Particularly useful are the equipment and studies indexes from which institutions using specific equipment or performing particular studies can easily be found.

All information included in this directory was obtained from the users by means of questionnaires distributed by BCTIC and accumulated by the Nuclear Medicine Department, Vanderbilt Medical Center.

*Assembled by the Biomedical Computing Technology Information Center in Cooperation with Vanderbilt University; work partially supported by the Bureau of Radiological Health Food and Drug Administration.

[†]Division of Nuclear Medicine, Vanderbilt University Hospital, Nashville, Tennessee.

[‡]UCC-ND Computer Sciences Division.

9.11. BIBLIOGRAPHY, SUBJECT INDEX, AND AUTHOR INDEX OF THE LITERATURE
EXAMINED BY THE RADIATION SHIELDING INFORMATION CENTER*

D. K. Trubey R. W. Roussin J. Gurney
A. B. Gustin E. W. Bryant

(Abstract of ORNL/RSIC-5, Vol. 6, February, 1980)

An indexed bibliography is presented of literature selected by the Radiation Shielding Information Center since the previous volume was published in 1978 in the area of radiation transport and shielding against radiation from nuclear reactors, x-ray machines, radio-isotopes, nuclear weapons (including fallout), and low energy accelerators (e.g., neutron generators). The bibliography was typeset from data processed by computer from magnetic tape files. In addition to lists of literature titles by subject categories (accessions 4951-6200), an author index is given.

Most of the literature selected for Vol. VI was published in the years 1976-1979.

*Work jointly supported by Department of Energy, Defense Nuclear Agency, and the U.S. Nuclear Regulatory Commission.

9.12. ON THE POLYNOMIAL FORM OF GAMMA-RAY BUILDUP FACTOR FUNCTIONS*

M. Metghalchi†

(Abstract of Nucl. Sci. Eng. 70, 207, 1979)

A three-parameter polynomial form of the buildup factor function was introduced. The parameters were calculated for aluminum, water, and iron. It was found that buildup factors calculated by these polynomials, in most cases, were more accurate than those using the Taylor, Berger, Capo, or quadratic (Trubey) formulas when compared with Goldstein-Wilkins data.

*Research sponsored by DOE Office of Reactor Research and Technology.

†Atomic Energy Organization of Iran, Esfahan Nuclear Technology Centre, No. 1294, Vanak Sq., Tehran, Iran.

SCIENTIFIC AND PROFESSIONAL ACTIVITIES

November 1, 1978 - October 31, 1980

- R. G. Alsmiller, Jr. Chairman, Subcommittee 7, DOE Advisory Panel on Accelerator Radiation Safety for Review of 400-GeV Proton-Proton Colliding Beam Facility (ISABELLE) at Brookhaven National Laboratory
Member, Department of Energy Advisory Panel on Pulsed Neutron Sources
Member, Department of Energy Advisory Panel on Accelerator Radiation Safety
Chairman, Admissions Committee, American Nuclear Society
Best Paper Award, American Nuclear Society, Radiation Protection and Shielding Division, June 1979, "Shielding Calculations for the TFTR Neutral-Beam Injectors," with R. T. Santoro, R. A. Lillie, and J. M. Barnes
Invited paper, "Shielding of Fusion Reactors," International Conference on Nuclear Cross Sections for Technology, Knoxville, Tennessee, October 1979
Invited paper, "ORNL Fusion Reactor Shielding Integral Experiments," Fourth ANS Topical Meeting on the Technology of Controlled Nuclear Fusion, King of Prussia, October 1980, with R. T. Santoro, J. M. Barnes, and G. T. Chapman
Invited paper, "Analysis of ORNL Fusion Reactor Shield Integral Experiments," with R. T. Santoro et al., Winter Meeting of the American Nuclear Society, San Francisco, California, November 1979
- J. Barhen Member, Data Testing Subcommittee, Cross Section Evaluation Working Group (CSEWG)
Invited talk, "Use of ENDF/B Covariance Files at ORNL," Brookhaven National Laboratory, May 1980
Referee, proposals reviews, National Science Foundation
Referee, proposal reviews, Office of Basic Energy Sciences, Department of Energy
- D. E. Bartine Treasurer, Radiation Protection and Shielding Division, American Nuclear Society (June 1979 - June 1981)
Member, ANSI6.1, Cross Sections for Shielding Standards Committee
Member, Program Committee, Joint Reactor Physics and Shielding Topical Meeting, Sun Valley, Idaho, September 1980
Advisor to Nuclear Engineering Department, University of Missouri at Rolla, Evaluation of Long-Term Facility Requirements
Invited paper, "Recent Shielding Experiments at the ORNL Tower Shielding Facility," 1979 Winter Meeting of the American Nuclear Society, San Francisco, California, November 1979
Invited paper, "The Use of Thorium in Fast Breeder Reactors," International Conference on Nuclear Cross Sections for Technology, Knoxville, Tennessee, October 1979
Invited paper, "GCFR Shielding Physics Design and Experimental Program," Helium Breeder's Association Meeting, Rancho Bernardo, California, June 1980
Seminar, University of Missouri at Rolla, December 1979
Seminar, "Gas-Cooled Reactors - The Importance of Their Development," EIR, Würenlingen, Switzerland, September 1978
Speakers' Bureau presentation, "The Morality of Energy," Hiwassee College, February 1978
ORNL Colloquium presentation, "Reactor Physics Aspects of Non-proliferation Studies"
- T. J. Burns Invited paper, "Thorium Utilization in Fast Breeder Reactors," MITRE Symposium on Thorium Utilization, November 1979
Referee, *Nuclear Science and Engineering*

- S. N. Cramer
Invited lecture, "Monte Carlo Development at ORNL," Casaccia, Italy, July 1979
- G. de Saussure
Chairman, International Meetings Subcommittee of National Program Committee, American Nuclear Society
Member, National Program Committee, American Nuclear Society
Member, Program Committee, Reactor Physics Division, American Nuclear Society
Member, Steering Subcommittee of National Program Committee, American Nuclear Society
Referee, *Nuclear Science and Engineering*
Referee, *The Physical Review*
Honorary Professor, Nuclear Engineering Department, University of Tennessee
Member, Thesis Committee, Ph.D. Thesis, U. of Tennessee (C. Yang and B. Broadhead)
- J. K. Dickens
Member, American Nuclear Society Standards Working Group 5.1: Decay Heat Standard
Member, American Nuclear Society Standards Working Group 5.2: Fission Product Yields
Member, American Nuclear Society Standards Committee 5
Referee, *Nuclear Science and Engineering*
Referee, *Nuclear Data Sheets*
Staff member, ORNL Senior Planning Group (1978-79)
Technical Staff, ORNL Master Plan (1978-79)
Designated by IAEA Working Group on Fission Product Nuclear Data as the correspondent on worldwide experimental measurements of fission product decay heat (1977-continuing)
Speakers' Bureau Presentations: "Nuclear Safety: The Hypothetical Loss of Coolant Accident," Vanderbilt University, March 1979; "Nuclear Safety: The Hypothetical Loss of Coolant Accident," Carnegie-Mellon Institute, April 1979; "Nuclear Safety," Motlow State Community College, Tullahoma, April 1980; "Nuclear Energy," South Knoxville Rotary Club, March 1980
Seminar, "Decay Heat and Reactor Safety Analysis," University of Illinois, Nuclear Engineering Department, October 1979
Invited paper, "Fission Product Decay Heat for Thermal Reactors," International Conference on Nuclear Cross Sections for Technology, Knoxville, Tennessee, October 1979
- W. W. Engle, Jr.
Member, American Nuclear Society Program Committee, Mathematics and Computation Division, 1980
Invited paper, "The Current Status of Methods for Shielding Design," American Nuclear Society Topical Meeting, 1980 Advances in Reactor Physics and Shielding, Sun Valley, Idaho, September 1980
Seminar, "Current Techniques in Discrete Ordinates Calculations," sponsored by the Institut für Kernenergetik and Energiesysteme, presented at the U. of Stuttgart, Stuttgart, Germany, November 1978
- G. F. Flanagan
Chairman Elect, Reactor Safety Division Program Committee, American Nuclear Society, 1980
Chairman, Action Steering Committee, American Nuclear Society
Member, National Program Committee, ANS, representing the Nuclear Reactor Safety Division
Member, Standards Committee 5.4, IEEE
Member, Standards Committee 19.3, American Nuclear Society
Founding and Charter member of the Society for Risk Analysis
Associate Editor, *Risk Analysis Journal*
Member, Technical Program Committee, ANS, ENS, CNS Thermal Reactor Safety Conference, Chicago, Illinois, October 1982
Member, Ph.D. Recruiting Program, ORNL

G. F. Flanagan
(continued)

Assistant Professor, University of Tennessee, "Fast Reactor Safety"
Member, WATtec Sponsors Committee
Registration Chairman, "Fuel Cycles of the 80's," Topical Meeting, Gatlinburg, Tennessee, September 1980
Speakers' Bureau presentations: "Are Today's Power Reactors Safe?--Pros and Cons," Auburn University, January 1979; "Nuclear Power Plant Safety," Southwestern University debate; "Nuclear Power After TMI," radio talk show, Knoxville, Tennessee

C. Y. Fu

Member, Evaluation Methods Subcommittee, Cross Section Evaluation Working Group (CSEWG)
Invited lecturer on Nuclear Theory for Applications, 1980 Winter College on Nuclear Physics and Reactors, 1980, Trieste, Italy
Invited paper, "Evaluation of Photon Production Data from Neutron-Induced Reactions," Conference on Evaluation Methods and Procedures, September 1980, Brookhaven National Laboratory
U.S. Interpreter, Washington, D. C., for drafting The Cooperation Accord in the Field of Nuclear Physics Research Between the Department of Energy of the USA and the State Scientific and Technological Commission of the People's Republic of China, May 1980

T. A. Gabriel

Member, Four-Laboratory Group (SLAC, DESY, CERN, ORNL) which is developing a calculational and experimental data base for shielding electron accelerators
Advisor to SLAC, ANL, and BNL on high-energy transport calculations for shielding, target design, and detector systems
Consultant to the Nuclear Research Center, Karlsruhe, W. Germany
Invited lecture, "Intranuclear Cascade Calculations Applied to Hadronic Decay," presented at Purdue University, Lafayette, Indiana, February 1980
Invited lecture, "CALOR: A Reasonable Approach to High Energy Calorimetry," presented as part of the Invited Lecture Series, Harvard University, Boston, Massachusetts, May 1980
Invited lecture, "Calculational and Experimental Calorimeter Design for Application in High Energy Physics," (with M. Goodman) presented at ORNL, March 1979
Invited lecture, "Detector Design Calculations," presented at the Nuclear Research Center, Karlsruhe, W. Germany, July 1980
Invited Lecture, "Shielding and Target Design of Neutron Spallation Sources," presented at the Nuclear Research Center, Jülich, W. Germany, July 1980

J. Gurney

Consultant, BCTIC, Vanderbilt University, Nashville, Tennessee

R. Gwin

Member, ORNL Criticality Committee

P. M. Haas

Member, IEEE Nuclear Power Engineering Committee, SC-5, Reliability
Member, IEEE Working Group on Human Factors, SC 5.5
Member, Journals, Periodicals, and Critical Reviews Committee, American Nuclear Society
Section Editor, *Nuclear Safety*, Accident Analysis Section
Invited paper, Seventh Water Reactor Safety Research Information Meeting, November 1979
Invited paper, Eighth Water Reactor Safety Research Information Meeting, October 1980

D. T. Ingersoll

Member, Program Committee, American Nuclear Society, Radiation Protection and Shielding Division
Member, Shielding Data Testing Subcommittee, Cross Section Evaluation Working Group (CSEWG)
Seminar, "Recent Shielding Experiments at the ORNL Tower Shielding Facility," presented at EIR, Würenlingen, Switzerland, January 1980

- D. T. Ingersoll
(continued) Commendation for supporting analysis following the accident at the Three Mile Island Nuclear Plant, June 1979
- H. E. Knee Member, Centralized Reliability Data Organization Steering Committee
- D. C. Larson Cochairman, General Purpose Evaluations Subcommittee, Cross Section Evaluation Working Group (CSEWG)
Member, Evaluation Methods Subcommittee, CSEWG
Member, ORNL Proposal Review Committee (Seed money)
Member, ORNL Graduate Fellow Selection Panel
Reviewer, *Nuclear Science and Engineering*
- R. A. Lillie Best Paper Award, American Nuclear Society, Radiation Protection and Shielding Division, June 1979, "Shielding Calculations for the TFTR Neutral-Beam Injectors," with R. T. Santoro, R. G. Alsmiller, Jr., and J. M. Barnes
Cochairman, Engineering Physics Division Seminars
- R. E. Maerker Member, ASTM E10.05 Subcommittee, 1978-1980
Invited paper, "Sn Transport Calculation of the PCA Experiments with Some Estimated Uncertainties," American Nuclear Society, June 1980
Invited paper, "Uncertainties and Biases Arising from Methods Approximations: The Calculation of Reaction Rates in the PCA 8/7 Configuration," Conference held in Julich, FRG, September 1979
Lecturer and chairman of discussion on PCA "blind test" calculations at National Bureau of Standards, May 1980
Chairman, Shielding Data Testing Subcommittee, Cross Section Evaluation Working Group (CSEWG)
Member, Shielding Subcommittee, CSEWG
- F. C. Maienschein Member, Nuclear Energy Agency Committee on Reactor Physics (NEACRP)
Member, ORNL Awards Advisory Committee
Chairman, ORNL Computing Steering Committee (OCSC)
Invited paper, "The Status of Reactor Shielding Research in the U.S.," American Nuclear Society Topical Conference on 1980 Advances in Reactor Physics and Shielding, Sun Valley, Idaho, September 1980
Deputy Chairman and Member of Program Committee, International Conference on Nuclear Cross Sections for Technology, Knoxville, Tennessee, October 1979
- J. H. Marable Member, Data Testing Subcommittee, Cross Section Evaluation Working Group (CSEWG)
Member, ORNL Criticality Committee
- B. F. Maskewitz Member, American Nuclear Society Board of Directors (1980-83)
Member, American Nuclear Society Planning Committee (1979-82)
Chairman, ANS NEED Planning Subcommittee (1980-81)
Member, American Nuclear Society, Radiation Protection and Shielding Division, Honors and Awards Subcommittee (1980-81)
Member, Program Committee for 1982 Conference of the American Society for Information Science
Chairman, Nominations, Radiation Protection and Shielding Division, American Nuclear Society (1975-79)
Member, N.E.E.D. Committee, American Nuclear Society
Member, ORNL Honors and Awards Advisory Committee
Member, ANS-10 Subcommittee of the ANS Standards Committee
Member, Society for Nuclear Medicine Council on Computers
Member, Organizing Committee for the Annual Scientific Symposium of the Society of Nuclear Medicine Council on Computers

B. F. Maskewitz
(continued)

Referee, Computer Code Abstracts, Nuclear Science and Engineering
Referee, Information Science Papers, 1979-1980, National Computer
Conference

Archivist, MUMPS Development Committee

Member, Standards Committee, Society for Computer Medicine

Member, Advisory Committee, National Science Foundation sponsored
Ultrasound Tissue Signature Project (Carnegie-Mellon Institute of
Research, Pittsburgh (1978-1979)

Member, Committee for Review of DOE-NEA Information Exchange
Agreement

Engineering Physics Division Technology Utilization Officer

Speakers' Bureau Presentations: Energy Forum, Western Pennsylv-
ania Branch of Women's League for Conservative Judaism, Pitts-
burgh, Pa., May 1980; "Energy," Women's League for Conservatism
Judaism, New Orleans, May 1980

Invited paper, "Data Bases for Rapid Response to Power Reactor
Problems," Seventh International COOATA Conference, Kyoto, Japan
October 1980

Invited lecture, "Shielding Research at the Oak Ridge National
Laboratory," Japan Atomic Energy Research Institute, Tokai,
Japan, October 1980

Invited lecture, "The Radiation Shielding Information Center,
An International Technology Resource," Korean Atomic Energy
Research Institute, Seoul, Korea, October 1980, and to the Insti-
tute of Nuclear Energy Research, Taipei, Taiwan, October 1980

Invited paper, "A Review of Data Base Management Systems (DBMS),"
5th International Conference on Structural Mechanics in Reactor
Technology (SMIRT-5), August 1979, Berlin, FRG; also served
on DBMS for SMIRT-5

Invited lecture on RSIC and shielding research activities during
the FGR Shielding Specialists Meeting, Alzenau-Wasserlos, FRG,
and to the French Shielding Specialists Meeting, CEA/CEN/Saclay
Laboratory, Gif-sur-Yvette, France, August 1979

Invited talk, "RSIC Activities to Promote Reciprocity in Inter-
national Computing Technology Exchange," 1979 Meeting of the OECD
Nuclear Energy Agency Data Bank Steering Committee, August 1979

B. L. McGill

Invited poster session, "A Source of Computer Codes and Data for
Fusion Neutronics Studies," with R. W. Roussin, D. K. Trubey, and
F. B. Maskewitz, Fourth Topical Meeting on the Technology of Con-
trolled Fusion, King of Prussia, Pennsylvania, October 1980

Poster Session, "The Technical Data Management Center, A Focal
Point for Meteorological and Other Environmental Transport Com-
puting Technology," with B. F. Maskewitz, and D. K. Trubey,
Symposium on Intermediate Range Atmospheric Transport Processes
and Technology Assessment, NOAA, October 1980

F. J. Muckenthaler

Citation for Technical Achievement, American Nuclear Society,
Radiation Protection and Shielding Division, June 1980

D. K. Olsen

Invited seminar, "A Measurement of the Gamma-Ray Production Cross
Section $^{238}\text{U}(n,n'\gamma)$ and $^{72}\text{I}(n,n'\gamma)$," Kernforschungszentrum,
Karlsruhe, July 1979

Invited seminar, "Measurement of ^{238}U Inelastic Scattering with
 γ -Ray Production Cross Sections," CBNM, Geel, Belgium, July 1979
Consultant, Centre d'Etudes de Bruyeres-le-Chateau, France,
April-August 1979

R. W. Peelle

Chairman, Cross Section Evaluation Working Group (CSEWG) Data
Uncertainty and Correlation Subcommittee

Member, DOE Nuclear Data Committee

Referee, *Physical Review*, *Nuclear Science and Engineering*

- F. G. Perey
U. S. Member, Nuclear Energy Agency Nuclear Data Committee (NEANDC)
Chairman, Neutron Standards Subcommittee, NEANDC
Member, Department of Energy Nuclear Data Committee
Member, INDC Standards Committee
Named Corporate Research Fellow, January 1979
- R. W. Roussin
Member, Panel on Reference Nuclear Data, representative for American Nuclear Society, Radiation Protection and Shielding Division
Member, ANS 6.2.2 Shielding Benchmark Subcommittee
Coordinator, Workshop on the TRIPOLI-II Monte Carlo Code, April 1980
Chairman, Shielding Testing and Applications Subcommittee, Cross Section Evaluation Working Group (CSEWG)
Member, Executive Committee, Radiation Protection and Shielding Division, American Nuclear Society
Lecturer, University of Tennessee, Tennessee Industrial Week Course, "An Engineering Approach to Monte Carlo Analysis," 1978 and 1979
Invited paper, "Status of Multigroup Sensitivity Profiles and Covariance Matrices Available from the Radiation Shielding Information Center," with J. D. Drischler and J. H. Marable, presented at the NEACRP Specialists Meeting on Cross Sections and Benchmarks for Reactor Shielding, Paris, France, October 1980
- R. T. Santoro
Member, Publications Committee, American Nuclear Society
Best Paper Award, American Nuclear Society, Radiation Protection and Shielding Division, "Shielding Calculations for the TFTR Neutral-Beam Injectors," with R. G. Alsmiller, Jr., R. A. Lillie, and J. M. Barnes, June 1979
Seminar, "Neutronics Investigations for Fusion Reactor Blanket and Shields," Georgia Institute of Technology, Nuclear Engineering Department, April 1980
Task Leader, Assessment of Advanced Technology Options, A NASAP Study
Invited paper, "Analysis of ORNL Fusion Reactor Shield Integral Experiments," with R. G. Alsmiller, Jr., J. M. Barnes, G. T. Chapman, G. L. Morgan, E. M. Oblo and R. W. Peelle, American Nuclear Society Meeting, November 1979
Invited paper, "ORNL Fusion Reactor Shielding Integral Experiments," with R. G. Alsmiller, Jr., J. M. Barnes, and G. T. Chapman, 4th ANS Topical Meeting on the Technology of Controlled Nuclear Fusion, King of Prussia, Pennsylvania, October 1980
- D. L. Selby
Chairman, Nominating Committee, American Nuclear Society Local Section
Awards Coordinator, Engineering Physics Division
Speakers' Bureau Presentations: "Nuclear Energy," Sue Bennett College, London, Kentucky; "Nuclear Safety," Dyersburg State Community College
Commendations for supporting analyses following the accident at the Three Mile Island Nuclear Plant, Department of Energy and the Oak Ridge National Laboratory, June 1979
- C. O. Slater
Member, Program Committee, American Nuclear Society, Radiation Protection and Shielding Division
- R. R. Spencer
Invited paper, "Absolute Measurement of $\bar{\nu}_p$ for ^{252}Cf by the Large Liquid Scintillator Tank Technique," International Conference on Nuclear Cross Sections and Technology, Knoxville, Tennessee, October 1979
Reviewer, *Nuclear Science and Engineering, The Physical Review*

- D. K. Trubey**
 Chairman, Honors and Awards Committee, Radiation Protection and Shielding Division, American Nuclear Society
 Chairman, ANS-6 Radiation Protection and Shielding Subcommittee, Standards Committee, American Nuclear Society
 Chairman, ANS-6.4.3 Standards Committee, Gamma-Ray Attenuation Data, American Nuclear Society
 Member, ANS-6.5 Shielding Glossary, American Nuclear Society
 Member, Working Group on Code Interfaces and Formats, Safety Analysis Data Coordinating Group
 Coordinator, Metrication, Engineering Physics Division
 Secretary, Tower Shielding Facility Safety Committee, EPD
 Organizer, Seminar-Workshop on Theory and Application of Monte Carlo Methods, Oak Ridge, Tennessee, 1980
 Lecturer, NRC-sponsored health physics and radiation protection course conducted by ORAU, March and August 1980
 Invited paper, "Recent Trends in Radiation Shielding - An RSIC Perspective," Third National Symposium on Radiation Physics, Waltair, A.P., India, February 1979; also presented as invited lecture at JAERI, Tokai-Mura, Japan)
- D. R. Vondy**
 Member, Program Committee, American Nuclear Society, Mathematics and Computation Division
 Member, M&C Benchmark Committee, American Nuclear Society
 Member, ANS-10 Standards Committee, American Nuclear Society
 Alternate Member, ANSI Standards Committee, X-3, ANS
 Alternate Member, X-3 Fortran Committee X3J3, ANS
 Member, DOE, Office of Reactor Development and Technology, Physics and Safety Section, Large Core Methods Evaluation Committee and Cooperative Computer Coding Committee
 Lecturer, Tennessee Industries Week, "Computational Methods in Nuclear Reactor Analysis," University of Tennessee
- C. R. Weisbin**
 Member, ASTM E10.05 Subcommittee
 Member, 1982 Reactor Physics Program Committee, American Nuclear Society
 Member, TVA/ORNL Task Force; representation for Fuel and Core Design
 Chairman, Program Committee, Reactor Physics Division, American Nuclear Society
 Chairman, Data Testing Subcommittee, Cross Section Evaluation Working Group (CSEWG)
 Member, Physics of Reactor Design Standards Committee, ANS-19
 Member, Codes and Formats, Fission Products and Shielding, CSEWG
- L. W. Weston**
 Cochairman, General Purpose Evaluation Subcommittee, Cross Section Evaluation Working Group (CSEWG)
 Invited paper, "Evaluation of Neutron Cross Sections for Fissile and Fertile Nuclides in the keV Range," Workshop on Nuclear Data Evaluation Methods and Procedures, Brookhaven National Laboratory, September 1980
- M. L. Williams**
 Member, Thermal Reactor Data Testing Subcommittee, Cross Section Evaluation Working Group (CSEWG)
 Invited paper, "Implementation of ENDF/B-IV and V Data in LWR Design Codes: EPRI-CELL and CPM," with O. Ozer, EPRI, and R. B. MacFarlane, LASL, San Francisco ANS Conference, November 1979
- B. A. Worley**
 Member, ANS Program Committee, Reactor Physics Division
 Coordinator, EPD United Way Campaign, 1980
- J. B. Zipperer**
 Invited paper, "The Unique Number 15," American Mathematical Society Meeting, Providence, Rhode Island, Winter, 1978
 Referee, National Computer Conference, 1981

ENGINEERING PHYSICS DIVISION SEMINARS AT ORNL

C. Y. Fu, D. K. Olsen, and R. A. Lillie were seminar coordinators during most of the period covered by this report. Current seminar coordinators are G. de Saussure and B. A. Worley. The following seminars were held during 1979-1980.

- R. G. Alsmiller, Jr., Engineering Physics Division, "Monte Carlo Simulation of Turbulent Atmosphere Transport and Comparisons with Experimental Data"
- R. G. Alsmiller, Jr. and E. M. Obloz, Engineering Physics Division, "Long-term Energy Analysis Program (LEAP) as Illustrated by a Simple Problem"
- J. B. Ball, Physics Division, "A Status Report on the Heavy Ion Facility"
- J. W. Behrens, National Bureau of Standards, "Measurements of Fission Cross-Section Range"
- M. Becker, Rensselaer Polytechnic Institute, "Limitations in the Structure of LEAP and Their Implication for Model and Data Validation"
- Z. W. Bell, Engineering Physics Division, "Fine Structures in the Photoneutron Cross Sections of ^{208}Pb "
- D. Biswas, Georgia Institute of Technology, "Nuclear Analysis of SUPER PHENIX"
- C. Bowman, National Bureau of Standards, "Molecular Effects in Boron Trifluoride (n, α) Reactions"
- Y. Chao, Carnegie-Mellon University, "A New Approach to the Adjustment of Group Cross Sections Fitting Integral Measurements"
- R. L. Childs, Computer Sciences Division, and W. A. Rhoades, Engineering Physics Division, "Efficiency Improvements in the DGT-IV Flux Calculations"
- A. Dubi, Los Alamos Scientific Laboratory, "Contributon Monte Carlo"
- J. Frehaut, Bruyères-le-Châtel, France, "Measurement of $\bar{\nu}$ at Bruyères-le-Châtel"
- F. H. Froehner, Kernforschungszentrum Karlsruhe, "Efficient Estimation of Strength Functions and Average Level Spacings from Resonance Parameters"
- F. H. Froehner, Kernforschungszentrum Karlsruhe, "Fast Doppler Broadening of Untabulated R-Matrix Multilevel Cross Sections"
- C. Y. Fu, Engineering Physics Division, "A Consistent Nuclear Model for Compound (Multistep Hauser-Feshbach) and Precompound Reactions"
- P. W. Gaffney, Computer Sciences Division, "Implementation of the Numerical Algorithms Group (NAG) Subroutine Library on the ORELA DEC-10"
- A. Gandini, CNEN, Casaccia, Italy, "Recent Advances in Perturbation Theory for Reactor Analysis"
- M. Goodman, Harvard University, and T. A. Gabriel, Engineering Physics Division, "Calculational and Experimental Calorimeter Design for Application in High Energy Physics"
- J. Gonnord, CEA/CEN/Saclay, France, "The Monte Carlo Tripoli Code - An Overview"

- R. Hart, Harvard University, "Work at Grenoble on the Weak Interactions of Nucleons"
- D. Hillis, University of California, Berkeley, "Experimental Study of Nuclei in High Angular Momenta"
- H. H. Hogue, Y-12 Development Division, UCC-MO, "Elastic and Inelastic Neutron Scatterings in the P-Shell (^6Li , ^9Be , ^{12}C , etc.)"
- H. B. Hurt, Health Division, "Understanding Stress"
- L. Koblinger, Central Research Institute for Physics, Budapest, Hungary, "Status of Dosimetry and Health Physics Research in Hungary"
- D. Lancaster, Massachusetts Institute of Technology, "Internal Blankets in Gas-Cooled Fast Breeder Reactors"
- N. Larson, Computer Sciences Division, "SAMMY: A Model for Multilevel R-Matrix Fits to Neutron Scattering Data Using Bayes"
- S. H. Levine, Pennsylvania State University, "Fuel Management Optimization: A New Approach"
- R. A. Lillie, Engineering Physics Division, "Monte Carlo Simulation of Neutral Particle Transport in a Neutral Beam Injector"
- R. C. Little, Rensselaer Polytechnic Institute, "Total (^{232}Th) and Capture (^{99}Tc , ^{232}Th) Cross Section Measurements at RPI"
- F. C. Maienschein and E. M. Obloy, Engineering Physics Division, "Technical and Non-technical Impressions of Shielding and Reactor Physics Activities in the USSR and Elsewhere"
- D. M. Nesbitt, Decision Focus, Inc., "An Overview of the DFI Energy-Economy Model"
- E. Neymotin, U.S.S.R., "Neutron Transport in Moving Media"
- T. W. Oakes, Industrial Safety and Health Physics Division, "Environmental Protection Awareness"
- E. M. Obloy and R. G. Alsmiller, Jr., Engineering Physics Division, "Adjoint Sensitivity Theory and Its Potential Application to the Long-Term Energy Analysis Program (LEAP)"
- D. K. Olsen, Engineering Physics Division, "Preliminary Study of Binary-Pseudo-Random Pulsing of ORELA"
- J. D. Pearson, Energy Information Administration, Department of Energy, "A Comparison of Four Long-Term Forecasts Which Result From the Leap Model"
- F. G. Perey, Engineering Physics Division, "Data Adjustments - When, How, and Why"
- F. G. Perey and E. M. Obloy, Engineering Physics Division, "Development of Screening Sensitivity Theory and Application to LEAP"
- F. G. Perey, Engineering Physics Division, "Introduction to Probability Theory and Applications to Neutron and Reactor Physics Problems" (a series of 27 lectures)
- M. Petilli, CNEN Casaccia, Rome, Italy, "Neutron Spectrum Evaluation in L-54 Reactor by Activation Measurements"
- S. Plattard, Bruyères-le-Châtel, France, "Is There Any Experimental Evidence for a New Metastable Shape of Light Actinide Nuclei?"
- F. Rad, Bates Laboratory, MIT, "The Nuclear 3-Body Problems in the Breakup Channels"

- G. Reffo, CNEN, Bologna, Italy, "Phenomenological Approach to Level Densities"
- W. A. Rhoades, Engineering Physics Division, and E. T. Tomlinson, Computer Sciences Division, "A Comparison of Codes for Deep Penetration Transport Studies"
- E. M. Robinson, Industrial Safety and Applied Health Physics, "Safe Driving for the Conservation of Gasoline"
- R. W. Roussin, Engineering Physics Division, "Report on the October 25 & 26 CSEWG Meeting"
- R. Rydin, University of Virginia, "Xenon Control and Neutronics Requirements for Analysis"
- R. T. Santoro, Engineering Physics Division, "Analysis of Integral Experiments for Fusion Reactor Design"
- R. L. Stark, PROSE, Inc., "PROSE: A Direct Programming Language for Computing in Calculus"
- L. Stewart, Los Alamos Scientific Laboratory, "Input Data Used for 1978 LEAP Projections"
- E. T. Tomlinson, Computer Sciences Division, and W. A. Rhoades, Engineering Physics Division, "Evaluation of the Flux Extrapolation Models in DOT-IV"
- R. Uppuluri, Computer Sciences Division, "Analysis of Paired Comparisons on Ranked Data"
- D. R. Vondy, T. B. Fowler, Engineering Physics Division, and G. W. Cunningham, Computer Sciences Division, "A Comparison of Codes for Deep Penetration Transport Studies"
- D. R. Vondy, Engineering Physics Division, "General Discussion on Core Analysis Methods"
- H. Weigmann, Central Bureau for Nuclear Measurements, Geel, Belgium, "Exploring the Deformation Potential of Actinide Nuclei by Neutron-Induced Fission"
- C. R. Weisbin and R. W. Peelle, Engineering Physics Division, "The ORNL Energy-Economic Model Validation Program"
- R. M. Westfall and M. A. Bjerke, Computer Sciences Division, "An Interface-Currents Integral Transport Model for Treating Doubly Heterogeneous Multisystem Geometries"
- J. R. White, Computer Sciences Division, "The Development, Implementation, and Verification of Multicycle Depletion Perturbation Theory"
- G. Winkler, Institute for Radium Research, Vienna, Austria, "Fast Neutron Activation and Scattering Research at the University of Vienna and Argonne"

PUBLICATIONS AND PAPERS PRESENTED AT SCIENTIFIC MEETINGS

PUBLICATIONS*

- ABBOTT, I. S., D. E. BARTINE, T. J. BURNS, C. SEGE,** AND I. SPIEMAK**
 "Interim Assessment of the Denatured ^{233}U Fuel Cycle: Feasibility and Nonproliferation Characteristics," ORNL-5388 (December 1978). (5.32)
- ALSMILLER, F. S.,** R. G. ALSMILLER, JR., H. W. BERTINI,** AND C. L. BEGOVICH**
 "Monte Carlo Simulation of Turbulent Atmospheric Transport and Comparisons with Experimental Data," J. Appl. Meteorology 18(1), 17 (1979). (1979)
- ALSMILLER, R. G., F. S. ALSMILLER, ** AND J. BARISH**
 "Calculations Pertaining to the Design of a Prebuncher for a 150-MeV Electron Linear Accelerator: II. Radial Motion," ORNL/TM-5419/V2 (May 1979). (1977)
- ALSMILLER, R. G., JR., F. S. ALSMILLER,** J. BARISH,** AND T. A. LEWIS**
 "Calculations Pertaining to the Design of a Prebuncher for a 150-MeV Electron Linear Accelerator," Part. Accel. (9), 187 (1979). (1977)
- ALSMILLER, R. G., JR., AND J. BARISH**
 "Photon Dose Rate in the Vicinity of a High-Energy Proton Beam Scraper", ORNL/TM-7048 (October 1979); Nucl. Instr. Methods, 172, pp. 455-458 (1980). (6.46)
- ALSMILLER, R. G., JR., J. BARISH,** D. BJORNSTAD,** D. J. DOWNING,** W. E. FORD, III,** J. HORNEDEL,** C. J. LEE,** J. McADOO,** E. M. OBLON, R. W. PEELLE, F. G. PEREY, L. STEWART,** AND C. R. WEISBIN
 "Interim Report on Model Evaluation Methodology and the Evaluation of LEAP," ORNL/TM-7245 (April 1980). (7.3)
- ALSMILLER, R. G., JR., J. BARISH,** AND R. L. CHILDS**
 "Skyshine at Neutron Energies < 400 MeV," ORNL/TM-7512 (October 1980). (6.44)
Accel.
- ALSMILLER, R. G., JR., J. BARISH,** R. T. SANTORO, R. A. LILLIE, J. M. BARNES,** AND M. M. H. RAGHEB**
 "Dose Rates from Induced Activity in the TFTR Test Cell", Nucl. Tech. (48), 187 (1980); ORNL/TM-6904 (August 1979). (6.36)
- AULL, JOHN E.**
 "Acceleration of the Inner Iteration of the DOT-IV Transport Code Using a New Source Correction Scheme", Master of Science Thesis, The University of Tennessee (August 1979); ORNL/TM-7404 (July 1980). (5.3)
- "The Stability of the Mesh-Cornered Synthetic Method of Diffusion Acceleration of the DOT-IV Transport Code", ORNL/TM-7097 (October 1979). (5.2)
- BAKER, V. C.,** AND J. H. MARABLE
 "Resonance Integral Calculations for Isolated Rods Containing Oxides of ^{238}U and ^{232}Th ", ORNL/TM-6376 (February 1980). (6.59)
- BARISH, J.,** T. A. GABRIEL, AND R. G. ALSMILLER, JR.
 "MAGIK - A Monte Carlo System for Computing Induced Residual Activation Dose Rates", ORNL-5561 (August 1979). (6.45)
- BARNES, J. M.,** B. L. BISHOP,** R. T. SANTORO, AND T. A. GABRIEL
 "The Effects of Fe-Ni-Co-V Structural Alloys on Fusion Reactor Neutronic Performance", Nucl. Tech., 47, p. 496, (March 1980). (1979)

*Numbers shown in parentheses following the publication correspond to an abstract in this report. In most cases, abstracts not included here were published in a previous progress report for which the year is indicated.

**Not a Division member.

BURNS, T. J., D. E. BARTINE, AND J.-P. RENIER**

"Concept Evaluation of a Nuclear Design for Electronuclear Fuel Production: Evaluation of ORNL's Proposed TMF-ENFP," ORNL/TM-6828 (May 1979). (6.55)

BURNS, T. J., AND J. R. WHITE**

"Preliminary Neutronic Analysis of a Fast Mixed-Spectrum Reactor (FMSR)", ORNL/TM-6854 (August 1979). (6.18)

CACUCI, D. G., C. F. WEBER,** E. M. OBLON, AND J. H. MARABLE

"Generalized Sensitivity Theory for Systems of Coupled Nonlinear Equations," ORNL/NUREG/TM-349 (January 1980); Nucl. Sci. Eng., 75, pp. 88-110 (1980). (3.27)

CAIN, V. R.,** AND M. B. EMMETT**

"BREESE-II: Auxiliary Routines for Implementing the Albedo Option in the MORSE Monte Carlo Code," ORNL/TM-6807 (July 1979). (5.12)

CARROLL, B. TALMI,** AND B. F. MASKIEWITZ

"Information Analysis Centers," Chapter 5 of Annual Review of Information Science and Technology, Vol. 15, M. E. Williams, Ed., Knowledge Industry Publications, Inc., White Plains, NY (1980). (9.1)

CHILDS, R. L.**

"Generalized Perturbation Theory Using Two-Dimensional, Discrete Ordinates Transport Theory," Ph.D. in Nuclear Engineering; ORNL/CSD/TM-127 (June 1980). (3.65)

CHILDS, R. L.,** G. de SAUSSURE, J. L. LUCIUS,** J. D. DRISCHLER, V. C. BAKER,** J. H. MARABLE, AND R. M. WESTFALL**

"Sensitivity and Uncertainty Analysis for the Mixed-Oxide Thermal Lattice U-L212," EPRI NP-1248, Project 975-3 (December 1979). (3.44)

CHILDS, R. L.,** F. J. MUCKENTHALER, AND L. S. ABBOTT

"Analysis of a TSF Experiment on Secondary Gamma-Ray Production in Reinforced Concrete Shields," ORNL-5272 (September 1980). (4.19)

CLIFFORD, C. E.,** F. J. MUCKENTHALER, F. R. MYNATT, AND L. S. ABBOTT

"Study of Neutron Transmission Through Planar and Cylindrical Annular Slits in Iron Shields," ORNL/TM-3513 (September 1980). (4.18)

CRADDICK, W. G.,** R. E. BOHAIAN,** D. G. CACUCI, D. H. COOK,** D. K. FIELDS,** R. M.

FLANDERS,** R. C. HAGAR,** C. R. HYMAN,** G. S. MAILEN,** L. J. OTT,** AND M. D. WHITE**
"Quarterly Progress Report on Blowdown Heat Transfer Separate-Effects Program for October-December 1979," ORNL/NUREG/TM-381 (NUREG/CR-1306) (June 1980). (3.63)

CRAMER, S. N. AND H. L. DODDS**

"SPQR: A Monte Carlo Reactor Kinetics Code," ORNL/TM-7086 (February 1980). (5.21)

de S SAUSSURE, G., D. K. OLSEN, R. B. PEREZ, AND F. C. DIFILIPPO**

"Evaluation of the ^{238}U Neutron Cross Sections for Incident Neutron Energies up to 4 keV," Prog. Nucl. Energy 3, 87 (1979). (1979)

DICKENS, J. K.

"Fission Yields for Thermal-Neutron Fission of ^{241}Pu ," Nucl. Sci. Eng. 70, 177 (1979). (1979)

"Half Life of ^{132}Te ," Radiochem. Radioanal. Letters, 39(2), 107 (1979). (1.35)

DICKENS, J. K., T. R. ENGLAND,** T. A. LOVE, J. W. McCONNELL, J. F. EMERY,** K. J. NORTH CUTT,** AND R. W. PEELE

"Delayed Beta- and Gamma-Ray Production Due to Thermal-Neutron Fission of ^{239}Pu : Tabular and Graphical Spectral Distributions for Times After Fission Between 2 and 14000 s," ORNL/NUREG-66 (Jan. 1980). (1.29)

DICKENS, J. K., AND T. A. LOVE

"Absolute Yield of 140.5-keV Gamma Ray Following Decay of ^{99}Mo ," Nucl. Instr. Methods, 175, 535 (1980). (1.36)

- DICKENS, J. K., T. A. LOVE, J. W. McCONNELL, AND R. W. PEELLE
 "Fission-Product Energy Release for Times Following Thermal-Neutron Fission of ^{235}U Between 2 and 14000 S", Nucl. Sci. Eng. **74**, 106 (1980). (1.27)
- DICKENS, J. K., AND J. W. McCONNELL
 "Fission-Product Yields for Thermal-Neutron Fission of Plutonium-239", Nucl. Tech. **73**, 42 (1980). (1.28)
- "Gamma Rays Following Alpha Decay of ^{245}Cm and the Level Structure of ^{241}Pu ", Phys. Rev. C, **22**(3), 1344 (September 1980). (1.33)
- "Fissions Determination in ^{239}Pu Sample", EPRI NP-997 (February 1979). (1.32)
- DIFILIPPO, F. C.,** R. B. PEREZ, G. de SAUSSURE, D. K. OLSEN, AND R. W. INGLE**
 "The ^{238}U Neutron-Induced Fission Cross Section for Incident Neutron Energies Between 5 eV and 3.5 MeV", ORNL/TM-6788 (March 1979); Phys. Rev. **21**, 1400 (1980). (1.9)
- DRISCHLER, J. D.
 "The COVERX Service Module of the FORSS System", ORNL/TM-7181 (April 1980). (3.21)
- EL-BASSIONI, A. A.,**
 "A Methodology and a Preliminary Data Base for Examining the Health Risks of Electricity Generation from Uranium and Coal Fuels", ORNL/Sub-7615/1 (NUREG/CR-1539) (August 1980). (8.12)
- EMMETT, M. B.,** W. W. ENGLE, G. F. FLANAGAN, H. E. KNEE, D. L. LOYD,** D. L. SELBY, AND L. R. WILLIAMS
 "FY 1977 Progress Report of the Clinch River Breeder Reactor's Source Range Flux Monitor Assessment Study for the Reference Homogeneous Core", ORNL-5548 (September 1979). (6.9)
- ENGEL, J. R.,** H. F. BAUMAN,** J. F. DEARING,** W. R. GRIMES,** H. E. MCCOY,** AND W. A. RHOADES
 "Conceptual Design Characteristics of a Denatured Molten-Salt Reactor with Once-Through Fueling", ORNL/TM-7207 (July 1980). (6.54)
- ENGEL, J. R.,** W. A. RHOADES, W. R. GRIMES,** AND J. F. DEARING**
 "Molten-Salt Reactors for Efficient Nuclear Fuel Utilization without Plutonium Separation", Nucl. Tech. **46**, 30 (1979). (6.53)
- ENGLE, W. W., JR., H. E. KNEE, D. L. LOYD,* J. T. MIHALCZO,* AND D. L. SELBY
 "FY 1978 Progress Report of the Clinch River Breeder Reactor Source Range Flux Monitor Assessment Study for the Reference Heterogeneous Core", ORNL-5627 (September 1980). (6.10)
- ERICKSON, JON J.,** JANE GURNEY, AND WILLIAM J. McCLAIN**
 "Directory of Computer Users in Nuclear Medicine", ORNL/BCTIC-1/R1 (September, 1979). (9.10)
- FISCHHOFF, B.,** S. LICHTENSTEIN,** P. SLOVIC,** R. KEENEY,** S. DERBY**
 "Approaches to Acceptable Risk: A Critical Guide", ORNL/SUB-7656 (NUREG/CR-1614) (December 1980). (8.4)
- FONTANA, M. H.**
 "ORNL Breeder Reactor Safety - LOA 2, 3, 4, and 5 Quarterly Technical Progress Report for April-June 1979", ORNL/TM-7147 (February 1980). (6.5)
- FORD, W. E., III,** R. W. ROUSSIN, L. M. PETRI,** B. R. DIGGS,** AND H. E. COMOLANDER
 "Sample Problems for the Novice User of the AMPX-II System", ORNL/CSD/TM-72 (AMPX-7) (January 1979). (3.6)
- FORSBERG, V. M.,** J. W. ARWOOD,** M. N. GREENE,** AND G. B. RAIFORD
 "SACRD - A Data Base for Fast Reactor Safety Computer Codes - Operational Procedures", ORNL/CSD-53 (September 1980). (8.11)

FU, C. Y., AND F. G. PEREY

"Neutron Scattering Cross Sections of Carbon Below 2 MeV Recommended from R-Matrix Fits to Data", Atom. Data Nucl. Data Tables 22(3), 249 (1978). (1979)

GABRIEL, T. A., AND B. L. BISHOP**

"The Response of a Uranium-Plastic Calorimeter to Low GeV (< 10 GeV) Protons," ORNL/TM-6709 (January 1979); Nucl. Instr. Methods, 164, 609 (1979). (6.47)

GABRIEL, T. A., AND B. L. BISHOP**

"Calculated Response of a Total Liquid Argon Calorimeter to Protons and Electrons in the 0.5- to 5.0-GeV Energy Range", ORNL/TM-6889 (July, 1979); Nucl. Instr. Methods 169, 427 (1980). (6.48)

GABRIEL, T. A., B. L. BISHOP,** AND F. W. WIFFEN**

"Calculated Irradiation Response of Materials Using Fission Reactor (HFIR, ORR, and EBR-II) Neutron Spectra", ORNL/TM-6361 (August 1979). (6.39)

GAT, U.,** AND P. R. KASTEN**

Gas-Cooled Fast Reactor Program Annual Progress Report for Period Ending December 31, 1979 ORNL-5675 (November 1980). (6.14)

GOODMAN, M.S.,** G. DENISY,** M. HALL,** A. KARPOVSKY,** R. WILSON,** T. A. GABRIEL, AND B. L. BISHOP**

"Liquid Argon as a Total Energy Electron/Photon Detector," ORNL/TM-7556 (December 1980). (6.49)

GREENE, N. M.,** G. F. FLANAGAN, AND H. ALTER**

"SACRD: A Data Base for Fast Reactor Safety Computer Codes", Nuclear Safety, 20, No. 3, 276 (1979). (8.10)

GREENE, N. M.,** V. M. FORSBERG,** G. B. RAIFORD,** J. W. ARWOOD,** D. B. SIMPSON, AND G. F. FLANAGAN

SACRD: A Data Base for Fast Reactor Safety Computer Codes -- Contents and Glossary of Version 1 of the System," ORNL-5477. Vol. 2 (September 1978). (8.9)

GREENE, N. M.,** V. M. FORSBERG,** G. B. RAIFORD,** J. W. ARWOOD,** D. B. SIMPSON, AND G. F. FLANAGAN

"SACRD: A Data Base for Fast Reactor Safety Computer Codes, General Description," ORNL-5477/V1 (January 1979). (8.8)

GREENSPAN, E.,** M. L. WILLIAMS, AND J. H. MARABLE

"Time-Dependent Generalized Perturbation Theory for Coupled Neutron-Nuclide Problems," Nucl. Sci. Eng., 73, 210 (1980). (3.23)

GWIN, R., R. R. SPENCER, R. W. INGLE,** J. H. TODD, AND H. WEAVER

"Measurement of the Average Number of Prompt Neutrons Emitted per Fission of ^{235}U Relative to ^{252}Cf for the Energy Region 500 eV to 10 MeV", ORNL/TM-7148 (January 1980). (1.15)

HAAS, P. M., AND T. F. BOTT

"Criteria for Safety-Related Nuclear Plant Operator Actions: A Preliminary Assessment of Available Data", ORNL/NUREG/TM-330 (July 1979). (8.1)

HETRICK, D. M.,** AND C. Y. FU

"GLUCS: A Generalized Least-Squares Program for Updating Cross Section Evaluations with Correlated Data Sets," ORNL/TM-7341 (October 1980). (2.14)

HETRICK, D. M.,** D. C. LARSON, AND C. Y. FU

"Status of ENDF/B-V Neutron Emission Spectra Induced by 14-MeV Neutrons," ORNL/TM-6637 (ENDF-280) (April 1979). (2.3)

INGERSOLL, D. T., D. E. BARTINE, AND F. J. MUCKENTHALER

"GCFR Radial Blanket and Shield Experiment: Objectives, Preanalysis, and Specifications," ORNL/TM-6956 (September 1979). (4.12)

INGERSOLL, D. T., AND C. O. SLATER

"DOGS - A Collection of Graphics for Support of Discrete Ordinates Codes", ORNL/TM-7188 (March 1980). (5.7)

JOHNSON, J. O., AND D. T. INGERSOLL

"User's Guide for the Revised SPEC-4 Neutron Spectrum Unfolding Code", ORNL/TM-7384 (August 1980). (5.24)

KASTEN, P. R.,** R. G. WYMER,** W. D. BURCH,** B. L. VONDRA,** A. L. LOTTS,** A. R. OLSEN,** W. L. CARTER,** R. H. RAINEY,** AND D. R. JOHNSON** (EDITED BY L. S. ABBOTT)
"Research and Development Requirements for the Recycle of Bred Fuels in Uranium and Thorium Fuel Cycles", ORNL/TM-6504 (May 1979).

LAHTI, GERALD P.,** ROBERT R. LEE,** AND JOHN C. COURTNEY**

"Radiation Streaming in Power Reactors - Proceedings of the Special Session, American Nuclear Society (ANS) Winter Meeting, Washington, D.C., November 15, 1978," ORNL/RSIC-43 (ANS/SD-79/16) (February 1979). (9.5)

LARSON, D. C.

"An Evaluation of Cross Sections for Neutron-Induced Reactions in Sodium", ORNL-5662 (ENDF-299) (September 1980). (2.10)

LARSON, D. C., AND G. L. MORGAN

"Measurement and Analysis of the $^{23}\text{Na}(n,xy)$ Reaction Cross Section for $0.2 \leq E_n \leq 20$ MeV", Nucl. Sci. Eng. 75, 151 (1980). (1.23)

LARSON, N. M.,** AND D. K. OLSEN

"Preliminary Study of Pseudorandom Binary Sequence Pulsing of ORELA", ORNL/TM-6632 (ENDF 290) (March 1980). (1.38)

LARSON, N. M.,** AND F. G. PEREY

"User's Guide for SAMMY: A Computer Model for Multilevel R-Matrix Fits to Neutron Data Using Bayes' Equations," ORNL/TM-7485 (ENDF-297) (November 1980). 2.15

LICHTENSTADT, I,** A. RON,** N. SACK,** AND J. J. WAGSCHAL

"Time-Dependent Neutrino Transport Out of Dense Stellar Cores", Astrophysics and Space Sci. 71, 219 (1980).

LILLIE, R. A., R. G. ALSMILLER, JR., AND J. T. MIHALCZO**

"Design Calculations for a 14-MeV Neutron Collimator," ORNL/TM-6487 (August 1978); Nucl. Tech. 43, 373 (1979). (1979)

LILLIE, R. A., T. A. GABRIEL, B. L. BISHOP, AND V. C. BAKER*

"One-Dimensional Gamma Ray and Photoneutron Shielding Calculations for the EBT-P," ORNL/TM-7136 (November 1980). (6.38)

LILLIE, R. A., AND R. T. SANTORO

"Radiation Transport in Earth for Neutron and Gamma Ray Point Sources Above an Air-Ground Interface," ORNL/TM-6655 (March 1979); Nucl. Tech., 47, 200 (1980). (1979)

LILLIE, R. A., R. T. SANTORO, AND R. G. ALSMILLER, JR.

"Estimated Nuclear Effects in the Neutral Beam Injectors of a Large Fusion Reactor", ORNL/TM-7526 (December 1980). (6.37)

"Calculation of Neutron Die-Away Times in a Large-Vehicle Portal Monitor," ORNL/TM-7299 (May 1980). (6.58)

MARABLE, J. H., C. R. WEISBIN, AND G. de SAUSSURE

"Uncertainty in the Breeding Ratio of a Large LMFBR: Theory and Results," Nucl. Sci. Eng. 75, 30 (1980). (3.52)

METGHALCHI, M.**

"On the Polynomial Form of Buildup Factor Functions," Nucl. Sci. Eng. Technical Note, 70, 207 (1979). (9.12)

METGHALCHI, M.,** R. W. ROUSSIN, J. T. WEST,** AND B. NAKHAI**

"A Comparison of the Use of EURLIB-III and Other Multigroup Cross-Section Libraries for a 1 Meter Concrete Slab Problem," ISIS Newsletter, ISPRA, Italy, No. 31 (1979). (3.5)

MIHALCZO, J. T.** (D. L. SELBY)

"A Review of Methods for Treatment of Source Effects in the Modified Source Multiplication Method for Monitoring the Reactivity in Refueling The CRBR", ORNL-5568 (September 1979). (6.4)

MORGAN, G. L.

"Cross Sections for the $^{15}\text{N}(n,p_0)$, (n,α_0) , and (n,α_1) Reactions from 0.5 to 15 MeV", Nucl. Sci. Eng. 70, 163 (1979). (1979)

"The $\text{Th}(n,x\gamma)$ Reaction Cross Section for Incident Neutron Energies Between 0.3 and 20.0 MeV", ORNL/TM-6758 (August 1979); Nucl. Sci. Eng. 72, 359 (1979). (1.19)

"Cross Sections for the $\text{Cu}(n,xn)$ and $\text{Cu}(n,x\gamma)$ Reactions Between 1 and 20 MeV", ORNL-5499 (ENDF-273) (February 1979). (1.20)

"Cross Sections for the $\text{Ti}(n,xn)$ and $\text{Ti}(n,x\gamma)$ Reactions Between 1 and 20 MeV", ORNL-5563 (August 1979). (1.21)

"The $\text{O}(n,x\gamma)$ Reaction Cross Section for Incident Neutron Energies Between 6.5 and 20.0 MeV", ORNL-5575 (September 1979). (1.22)

MORGAN, G. L., D. K. OLSEN, AND J. W. McCONNELL

"A Proton-Recoil Telescope for In-Line Absolute Neutron Fluence Measurements," Nucl. Instr. Methods 157, 525 (1978). (1979)

MORRIS, D. G.**

"Thermal-Hydraulic/Heat Transfer Code Development for Sphere-Pac-Fueled LMFBRs," ORNL/TM-7100 (June 1980). (5.22)

MUCKENTHALER, F. J., J. L. HULL, AND J. J. MANNING

"The GCFR Grid Plate Shield Design Confirmation Experiment," ORNL/TM-6580 (January 1979). (1979)

OLSEN, D. K., G. de SAUSSURE, R. B. PEREZ, F. C. DIFILIPPO,** R. W. INGLE,** AND H. WEAVER

"Measurement and Resonance Analysis of 150-m Neutron Transmissions Through Four ^{238}U Samples," Nucl. Sci. Eng. 69, 202 (1979). (1979)

OLSEN, D. K., G. L. MORGAN, AND J. W. McCONNELL

"Measurement of $^{238}\text{U}(n,n'\gamma)$ and $^7\text{Li}(n,n'\gamma)$ Gamma-Ray Production Cross Sections," ORNL/TM-6832 (September 1979). (1.5)

"Absolute Measurement of the $^7\text{Li}(n,n'\gamma)^7\text{Li}^*$ (0.478-MeV) Cross Section," Nucl. Sci. Eng. 74, 219 (1980). (1.4)

PAGE, J. V., III,** S. N. CRAMER, AND J. R. KNIGHT**

"Calculations of the Skyskine Gamma-Ray Dose Rates from Independent Spent Fuel Storage Installations (ISFSI) Under Worst Case Accident Conditions", ORNL/NUREG/TM-316 (September 1980). (6.29)

PEREY, C. M. AND F. G. PEREY

"Evaluation of Resonance Parameters for Neutron Interaction with Iron Isotopes for Energies up to 400 keV," ORNL/TM-6405 (ENDF-298) (September 1980). (2.7)

PEREY, F. G., AND J. C. (GENTRY) LUNOY

"Status Report(s) to the DOE Nuclear Data Committee," ORNL/TM-6873 (April 1979) and ORNL/TM-7309 (April 1980). (1.24)

PEREZ, R. B.

"One-Dimensional Model of Fluidized Bed Combustor Dynamics," ORNL/TM-7141 (January 1980). (6.60)

PEREZ, R. B.

"On the Expansion of the Propagator in Power Series of the Coupling Constant,"
J. Math. Phys. 20(2), 241 (1979). (1979)

PEREZ, R. B., G. de SAUSSURE, R. L. MACKLIN,** AND J. HALPERIN**

"Statistical Tests for the Detection of Intermediate Structure: Application to the Structure of the ^{238}U Neutron Capture Cross Section Between 5 keV and .1 MeV,"
Phys. Rev. C, 20(2), 528 (1979). (1979)

POSTMA, H.,** ET AL. (J. K. DICKENS)

"Oak Ridge National Laboratory Institutional Plan FY80-FY85," ORNL/PPA-79/8
(November 1979).

RAGHEB, M. M. H.,** R. T. SANTORO, J. M. BARNES,** AND M. J. SALTmarsh**

"The Nuclear Performance of Molten Salt Fusion-Fission Symbiotic Systems for Catalyzed DD and DT Plasmas," ORNL/TM-6560 (March 1979); Nucl. Tech. 48, 216 (1980). (1979)

RHOADES, W. A., D. B. SIMPSON, R. L. CHILDS,** AND W. W. ENGLE, JR.

"The DOT-IV Two-Dimensional Discrete Ordinates Transport Code with Space-Dependent Mesh and Quadrature," ORNL/TM-6529 (January 1979). (1979)

RONEN, Y., M. A. BJERKE,** D. G. CACUCI, AND J. BARNEN

"A Nonlinear Sensitivity and Uncertainty Analysis in Support of the Blowdown Heat Transfer Program," ORNL/NUREG-TM-412 (November 1980). (3.62)

RONEN, Y.,** D. G. CACUCI, AND J. J. WAGSCHAL**

"Determination and Application of Generalized Bias Operators Using an Inverse Perturbation Approach," ORNL/TM-7458 (November 1980). (3.38)

RONEN, Y.,** J. L. LUCIUS,** AND E. M. OBLON

"A Statistical Sensitivity Analysis of a Simple Nuclear Waste Repository Model,"
ORNL/TM-7310 (June 1980). (6.31)

ROUSSIN, R. W., C. R. WEISBIN, J. E. WHITE,** N. M. GREENE,** R. Q. WRIGHT,** AND J. B. WRIGHT**

"VITAMIN-C: The CTR Processed Multigroup Cross-Section Library for Neutronics Studies," ORNL/RSIC-37 (ENDF-296) (July 1980). (3.1)

SALTmarsh, M. J.,** W. R. GRIMES,** AND R. T. SANTORO

"An Optimization of the Fission-Fusion Hybrid Concept", ORNL/PPA-79/3 (April 1979)
(6.43)

SANTORO, R. T., R. G. ALSMILLER, JR., AND J. M. BARNES**

"Nuclear Accident Dosimetry: Calculations and Comparison with Experimental Data,"
Health Phys. 36, 189 (1979). (1979)

SANTORO, R. T., R. G. ALSMILLER, JR., J. M. BARNES, AND G. T. CHAPMAN

"Calculation of Neutron and Gamma Ray Energy Spectra for Fusion Reactor Shield Design: Comparison with Experiment," ORNL/TM-7360 (August 1980). (4.1)

SANTORO, R. T., R. A. LILLIE, R. G. ALSMILLER, JR., AND J. M. BARNES**

"Two- and Three-Dimensional Neutronics Calculations for the Tokamak Fusion Test Reactor Neutral Beam Injectors," Nucl. Sci. Eng. 70, 225 (1979). (1979)

"Shielding Calculations for the TFTR Neutral Beam Injectors" ORNL/TM-6949 (July 1979);
Nucl. Tech. 47 (1980). (6.35)

SEKI, Y.,** R. T. SANTORO, E. M. OBLON, J. M. BARNES,** AND J. L. LUCIUS**

"Cross Section Sensitivity Analysis of a Streaming Experiment with a Two-Dimensional Model," ORNL/TM-6588 (February 1979). (1979)

SEKI, Y.,** R. T. SANTORO, E. M. OBLON, AND J. L. LUCIUS**

"Comparison of One- and Two-Dimensional Cross-Section Sensitivity Calculations for a Fusion Reactor Shielding Experiment," ORNL/TM-6667 (January 1979); Nucl. Sci. Eng. 73, 87 (1980). (1979)

SELBY, D. L.

"Preconceptual Study of Proliferation-Resistant Heterogeneous Sphere-Pac-Fueled LMFBR Cores", ORNL/TM-6996 (August 1979). (6.6)

SELBY, D. L., G. F. FLANAGAN, P. B. FOX,** AND D. B. SIMPSON

"The Analysis of the ZPR-9 Reverse Approach to Critical (RAC) Low Level Flux Monitor Experiment," ORNL-5181 (July 1979). (6.7)

SELBY, D. L., AND H. E. KNEE

"Analysis of the Clinch River Breeder Reactor (CRBR) Source Range Flux Monitor (SRFM) Count Rate History During Refueling of the First Four Cycles," ORNL-5557 (September 1979). (6.2)

"Uncertainties Associated with Monitoring the Shutdown Operations in the Clinch River Breeder Reactor Heterogeneous Core Using the Source Range Flux Monitor," ORNL-5608 (September 1980). (6.3)

SIMPSON, D. B. AND B. L. MCGILL

"User's Manual for LADTAP II - A Computer Program for Calculating Radiation Exposure to Man from Routine Release of Nuclear Reactor Liquid Effluents," ORNL/NUREG/TMDC-1 (NUREG/CR-1276) (May 1980). (9.9)

SLATER, C. O. AND J. R. KNIGHT**

"Analysis of the TSF GCFR Single-Cell Neutron Streaming Experiment", ORNL/GCFR-80/16 (July 1980). (4.9)

SLATER, C. O., E. T. TOMLINSON,** AND L. R. WILLIAMS

"Analysis of the Initial Shielding Design for the Upflow Gas-Cooled Fast Reactor (GCFR)" ORNL/TM-7246 (May 1980). (6.15)

SMITH, J. D.**

"Processing ENDF/B-V Uncertainty Data Into Multigroup Covariance Matrices" M.S. Thesis, The University of Tennessee (March 1980); ORNL/TM-7221 (June 1980). (3.10)

SPENCER, R. R., R. GWIN, R. INGLE,** AND H. WEAVER

"Interim Report on the ORNL Absolute Measurements of $\bar{\nu}_p$ for ^{252}Cf ", ORNL/TM-6805 (September 1979). (1.16)

SWAIN, W. T.,** AND D. L. SELBY

"Evaluation of Single-Rod Withdrawal Techniques for Use in Constructing Inverse Count Rate Curves During Initial Loading of the First Core in the Clinch River Breeder Reactor (CRBR)", ORNL/TM-7204 (September 1980). (6.11)

TEUCHERT, E.,** H. J. RUTTEN,** B. A. WORLEY, AND D. R. VONDY

"US/FRG Joint Report on the Pebble Bed High Temperature Reactor Resource Conservation Potential and Associated Fuel Cycle Costs", ORNL-5582 (November 1979). (6.26)

TODD, H. A.**

"Procedures Manual for the Oak Ridge Electron Linear Accelerator," ORNL/TM-6801 (March 1979). (1.39)

TOMLINSON, E. T.**

"Neutronic Analysis of LMFBRs During Severe Core Disruptive Accidents," ORNL/CSD-35 (January 1979). (6.1)

TOMLINSON, E. T.,** R. L. CHILDS,** AND R. A. LILLIE

"DOS Perturbation Modules DGRAD/VIP/TPERT," ORNL/CSD/TM-116 (May 1980). (3.66)

TOMLINSON, E. T.,** W. A. RHOADES, AND W. W. ENGLE, JR.

"Flux Extrapolation Models Used in the DOT IV Discrete Ordinates Neutron Transport Code," ORNL/TM-7033 (May 1980). (5.6)

TRUBEY, D. K. AND B. L. MCGILL

"A Review of the Theory and Application of Monte Carlo Methods - Proceedings of a Seminar-Workshop, Oak Ridge, Tennessee, April 21-23, 1980," ORNL/RSIC-44 (August 1980). (5.8)

TRIBEY, D. K., R. W. ROUSSIN, J. GURNEY, A. B. GUSTIN, AND E. W. BRYANT

"Bibliography, Subject Index, and Author Index of the Literature Examined by the Radiation Shielding Information Center," ORNL/RSIC-5/V6 (May, 1980). (9.11)

YONDY, D. R.

"Computer Code Abstracts for BURNER, PERTUBAT, AND RODMOD," Nucl. Sci. Eng. 72, 365 (1979). (1979)

"PREMOR: A Point Reactor Exposure Model Computer Code for Survey Analysis of Power Plant Performance", ORNL-5580 (October 1979). (5.16)

YONDY, D. R., AND G. W. CUNNINGHAM**

"Exposure Calculation Code Module for Reactor Core Analysis: BURNER", ORNL-5180 (February 1979). (5.15)

YONDY, D. R., AND T. B. FOWLER

"The Iterative Behavior of Diffusion Theory Flux Eigenvalue Neutronics Problems," ORNL/TM-6843 (May 1979). (5.13)

YONDY, D. R., T. B. FOWLER, AND G. W. CUNNINGHAM**

"Input Data Requirements for Special Processors in the Computation System Containing the VENTURE Neutronics Code", ORNL-5229/R1 (July 1979). (5.14)

YONDY, D. R., AND B. A. MORLEY

"Pebble Bed Reactor Core Physics and Fuel Cycle Analysis", ORNL-5484 (October 1979). (1979)

WAGSCHAL, J. J.,** AND Y. YEIVIN**

"The Significance of Lagrange Multipliers in Cross-Section Adjustment," ESIS Newsletter 33, 3-4 (April 1980). (3.40)

WEBER, C. F. ** AND E. M. OBLON

"Sensitivity Theory Applied to a Transient Thermal-Hydraulics Problem". ORNL/TM-6900 (October, 1979). (3.64)

WEISBIN, C. R., J. H. MARABLE, P. J. COLLINS,** C. L. COWAN,** R. W. PEELE, AND M. SALVATORES**

"Specifications for Adjusted Cross-Section and Covariance Libraries Based Upon CSCWG Fast Reactor and Dosimetry Benchmarks," ORNL-5517 (June 1979). (3.37)

WEISBIN, C. R., R. W. ROUSSIN, H. R. HENDRICKSON, AND E. W. BRYANT

"A Review of the Theory and Application of Sensitivity and Uncertainty Analysis: Proceedings of a Seminar-Workshop, Oak Ridge, Tennessee, August 22-24, 1978," ORNL/RSIC-42 (February 1979). (3.17)

WEISBIN, C. R., R. W. ROUSSIN, J. J. WAGSCHAL,** J. E. WHITE,** AND R. Q. WRIGHT**

"VITAMIN-E: An ENDF/B-V Multigroup Cross Section Library for LMFBR Core and Shield, LWR Shield, Dosimetry, and Fusion Blanket Technology," ORNL-5505 (February 1979). (3.2)

WHITE, J. R.**

"The Development, Implementation and Verification of Multicycle Depletion Perturbation Theory for Reactor Burnup Analysis," ORNL/TM-7305 (August 1980). (5.18)

WHITE, J. R.,** AND T. J. BURNS

"Analysis of Fission Product Effects in a Fast Mixed-Spectrum Reactor (FMSR)", ORNL/TM-7091 (February 1980). (6.19)

"Preliminary Evaluation of Alternate-Fueled Gas Cooled Fast Reactors," ORNL/TM-7432 (December 1980). (6.25)

WHITE, J. R.,** AND D. T. INGERSOLL

"Analysis of the Thorium Axial Blanket Experiments in the PROTEUS Reactor," ORNL/TM-7471 (December 1980). (6.22)

WILLIAMS, M. L.

"Perturbation and Sensitivity Theory for Reactor Burnup Analysis", Ph.D. Thesis, The University of Tennessee, August 1979; ORNL/TM-7096 (December 1979). (3.54)

"Development of Depletion Perturbation Theory for Coupled Neutron/Nuclide Fields," ORNL/TM-5958 (September 1978); Nucl. Sci. Eng. 70, 20 (1979). (1979)

PAPERS PRESENTED AT SCIENTIFIC MEETINGS*

Symposium on Nuclear Data Problems for Thermal Reactor Applications, Brookhaven National Laboratory, May 22-24, 1978; NBL-BC-25047 (ENDF-270)

BARIEN, J. AND W. ROTHENSTEIN,** "Thermal Reactor Benchmark Calculations Using Resonance Profiles" (5.19)†

Computer Techniques in Shielding and Dosimetry, Ettore Majorana Center, Erice, Sicily, Italy, October 25 - November 3, 1978; Computer Techniques in Radiation Transport and Dosimetry, Plenum Press, 1980

ENGLE, W. W., JR.

"Lecture 3: The Methods and Applications of Discrete Ordinates in Low Energy Neutron-Photon Transport (ANISN, DOT). Part I: Methods," p. 59. (5.27)

"Lecture 5: The Methods and Applications of Discrete Ordinates in Low Energy Neutron-Photon Transport (ANISN, DOT). Part II: Applications," p. 97. (5.27)

"Lecture 8: Cross Section Processing Codes and Data Bases (AMPX)," p. 123. (5.27)

GABRIEL, T. A.

"Lecture 4: The Methods and Applications of Monte Carlo in Low Energy (<20 MeV) Neutron-Photon Transport (MORSE), Part I: Methods" p. 77, (5.27)

"Lecture 6: The Methods and Applications of Monte Carlo in Low Energy (<20 MeV) Neutron-Photon Transport (MORSE), Part II: Applications," p. 99. (5.27)

"Lecture 9: Radiation Shielding Information Center and Biomedical Computing Technology Information Center," p. 125. (5.27)

Specialist Meeting on the Nuclear Data of Higher Plutonium and Americium Isotopes for Reactor Applications, Brookhaven National Laboratory, Upton, New York, November 20-22, 1978; BNL-50991, May 1979

WESTON, L. W., "Review of Microscopic Neutron Cross Section Data for the Higher Plutonium Isotopes in the Resonance Region," p. 1. (2.13)

Third US/USSR Symposium on Fusion-Fission Hybrids, Princeton, New Jersey, January, 1979

SALTmarsh, M. J.,** W. R. GRIMES,** AND R. T. SANTORO, "An Optimization of the Fission-Fusion Hybrid Concept" (6.43)

1979 Annual Meeting of the American Nuclear Society, Atlanta, GA, June 3-7, 1979; Trans. Am. Nucl. Soc. 32 (1979)

ALSMILLER, R. G., JR., J. BARISH,** R. T. SANTORO, J. M. BARNES,** AND M. M. H. RAGHEB,** "Dose Rates from Induced Activity in the TFTR Test Cell," p. 668. (6.36)

AULL, J. E.,** W. A. RHOADES, AND H. L. DODDS,** "A Modified Approach to Diffusion Acceleration in Neutron Transport Problems," p. 306. (5.1)

BARIEN, J., AND D. G. CACUCI, "Determination of Current-Weighted Total Cross Sections in the Unresolved Energy Region," p. 310. (3.8)

BOTT, T. F., P. M. HAAS, AND J. J. MANNING, "Sodium Component Reliability Data Collection at CREDS," p. 480. (8.6)

INGERSOLL, D. T., D. E. BARTINE, AND F. J. MUCKENTHALER, "Design of Deep-Penetration Integral Experiment for Thorium Blanket and Radial Shield Mockups," p. 643. (4.16)

*Compiled November 30, 1980; includes papers submitted for future meetings.

**Not a Division member.

†Numbers in parentheses indicate related abstract in this report.

LUCIUS, J. L.,** AND J. H. MARABLE, "Influence of Fission Spectra Uncertainties on Calculated Fast Reactor Parameters," p. 731. (3.50)

MINALCZO, J. T.,** D. L. SELBY, AND H. E. KNEE, "Theoretical Evaluation of Ex-Vessel Monitoring for Initial Fuel Loading of a Liquid-Metal Fast Breeder Reactor," p. 787. (6.8)

ROUSSIN, R. W., M. NETHALCHI,** J. T. WEST,** AND B. NAKAH,** "Comparison of Several Multigroup Libraries for LWR Shielding Problems," p. 644. (3.12)

SANTORO, R. T., R. A. LILLIE, R. G. ALSHILLER, JR., AND J. M. BARNES, "Shielding Calculations for the TFTR Neutral-Beam Injectors," p. 661. (6.35)

SLATER, C. O., S. N. CRAMER, AND D. T. INGERSOLL, "Analysis of the ORNL/TSF GCFR Grid-Plate Shield Design Confirmation Experiment," p. 641. (4.10)

WHITE, J. R.,** AND T. J. BURNS, "Alternative Heterogeneous GCFR Fuel Cycles," p. 403. (6.24)

WILLIAMS, M. L., J. R. WHITE,** AND T. J. BURNS, "A Technique for Sensitivity Analysis of Space- and Energy-Dependent Burnup Calculations," p. 766. (3.55)

Eighth Annual Conference of the MUMPS Users' Group, Atlanta, GA, June 6-8, 1979

MASKENITZ, B. F., "The Validation of Computing Technology Through Sharing" (9.8)

Twentieth Annual Meeting, Institute of Nuclear Materials Management, Albuquerque, NM, July 16-19, 1979

RAGAN, G. L.,** C. W. RICKER,** M. M. CHILES,** D. T. INGERSOLL, AND G. G. SLAUGHTER,** "Nondestructive Assay of Subassemblies of Various Spent or Fresh Fuels by Active Neutron Interrogation" (6.56)

Second Symposium of the Institute of Gas Technology on Energy Modeling, Colorado Springs, CO, August 13-17, 1979

OBLON, E. M., C. R. WEISBIN, AND R. G. ALSHILLER, JR., "A Sensitivity Approach to the Validation of Long-Range Energy-Economic Forecasts" (7.1)

PEELLE, R. W., D. J. DOWNING,** AND D. J. BJORNSTAD,** "The Quantification of Uncertainties in the Parameters of a Long-Term Energy Model" (7.2)

SHIRT-5 and the 5th International Seminar on Computational Aspects of the Finite Element Method, Berlin, Germany, August 13-21, 1979

MASKENITZ, B. F., AND C. E. PRICE,** "Survey of USA Major Data Base Management Systems" (9.2)

MASKENITZ, B. F., AND S. F. BANKERT,** "The USA NRC/RSR Data Bank System and Reactor Safety Research Data Repository (RSRDR)" (9.3)

Specialists' Meeting on Accuracies in Correlation Between Property Change and Exposure Data from Reactor Pressure Vessel Steel Irradiations, KFA-Jülich, Federal Republic of Germany, September 24-27, 1979

MAERKER, R. E., AND J. J. WAGSCHAL,** "Uncertainties and Biases Arising from Methods Approximations: The Calculation of Reaction Rates in the PCA 8/7 Configuration" (3.43)

International Symposium on Fast Reactor Physics, Aix-en-Provence, France, September 24-28, 1979

SCHNOCKER, U.,** R. CHAMLA,** K. GIER,** M. JERMAN,** C. MCCOMBIE,** R. RICHMOND,** S. SEYN,** D. E. BARTINE, D. T. INGERSOLL, AND J. R. WHITE,** "Critical Experiments in a Zero Power Fast Reactor Lattice with Breeder Zones of Thorium and Uranium" (6.20)

Third ASI-EURATOM Symposium on Reactor Dosimetry, Ispra (Varese), Italy, October 1-5, 1979

WAGSCHAL, J. J.,** R. E. MAERKER, AND D. M. GILLIAM,** "Covariances of Fission-Integral Measurements at the NBS ^{252}Cf and ISNF Facilities and at the ORNL-PCA Facility" (3.46)

International Conference on Nuclear Cross Sections for Technology, The University of Tennessee, Knoxville, October 22-26, 1979; NBS Special Publication No. 594

ALSMILLER, F. S., R. G. ALSMILLER, JR., T. A. GABRIEL, R. A. LILLIE, AND J. BARISH,** "Calculated Particle Production Spectra and Multiplicities from Nucleon-Fissile Element Collisions at Medium Energies," p. 422. (6.50)

ALSMILLER, R. G., JR., "Shielding of Fusion Reactors," p. 239. (6.34)

BARNEN, J., D. G. CACUCI, W. E. FORD, III,** R. W. ROUSSIN, J. J. WAGSCHAL,** C. R. WEISBIN, J. E. WHITE,** AND R. Q. WRIGHT,** "VITAMIN-E: A Multipurpose ENDF/B-V Coupled Neutron-Gamma Cross Section Library," p. 204. (3.3)

BARTINE, D. E., "The Use of Thorium in Fast Breeder Reactors," p. 119. (6.33)

CHAPMAN, G. T., AND G. L. MORGAN,** "Integral Experiments for Fusion Reactor Design: Experimentation," p. 591. (4.3)

DICKENS, J. K., "Fission Product Decay Heat for Thermal Reactors," p. 25. (1.26)

FU, C. Y., "A Consistent Nuclear Model for Compound and Precompound Reactions with Conservation of Angular Momentum," p. 757. (2.1)

FU, C. Y., D. M. HETRICK,** AND F. G. PEREY, "Simultaneous Evaluation of $^{32}\text{S}(n,p)$, $^{56}\text{Fe}(n,p)$, $^{65}\text{Cu}(n,2n)$ Cross Sections," p. 63. (2.8)

HETRICK, D. M.,** D. C. LARSON, AND C. Y. FU, "Neutron Emission Spectra Induced by 14-MeV Neutrons from the Evaluated Nuclear Data File (ENDF/B-V) - A Critical Review," p. 765. (2.3)

INGERSOLL, D. T., AND F. J. MUCKENTHALER, "Deep Penetration Integral Experiment for a Thorium Blanket Mockup," p. 122. (4.17)

LARSON, D. C., "Evaluation of ^{23}Na for ENDF/B-V," p. 58. (2.9)

LARSON, D. C., J. A. HARVEY,** AND N. W. HILL,** "Neutron Total Cross Sections of Hydrogen, Carbon, Oxygen and Iron from 500 keV to 60 MeV," p. 34. (1.3)

MARABLE, J. H., C. R. WEISBIN, AND G. de SAUSSURE, "Cross Section Adjustment Applied to Estimation of Uncertainty in the Breeding Ratio of an LMFBR," p. 177. (3.36)

OLSEN, D. K., G. L. MORGAN,** AND J. W. MCCONNELL, "Measurement of $^{238}\text{U}(n,n'\gamma)^{238}\text{U}$ Cross Sections," p. 677. (1.6)

PLATTARD, S.,** G. F. AUCHAMPAUGH,** N. W. HILL,** G. de SAUSSURE, R. B. PEREZ, AND J. A. HARVEY,** "High-Resolution Fission Cross Section of ^{231}Pa ," p. 411. (1.10)

SANTORO, R. T., R. G. ALSMILLER, JR., J. M. BARNES,** AND E. M. OBLow, "Integral Experiments for Fusion Reactor Design: Analysis," p. 596. (4.2)

SPENCER, R. R., "Absolute Measurement of $\bar{\nu}$ for ^{252}Cf by the Large Liquid Scintillator Tank Technique," p. 728. (1.17)

WAGSCHAL, J. J.,** B. L. BROADHEAD,** AND R. E. MAERKER, "Least Squares Methodology Applied to LWR-PV Damage Dosimetry, Experience and Expectations," p. 956. (3.59)

WESTON, L. W., AND R. Q. WRIGHT,** "Evaluation of the Fission and Capture Cross Sections of ^{240}Pu and ^{241}Pu for ENDF/B-V," p. 464. (2.12)

WHITE, J. R.,** D. T. INGERSOLL, U. SCHMOCKER,** AND K. GNUC,** "Analysis of a Swiss Thorium Blanket Integral Experiment," p. 126. (6.21)

YEIVIN, Y.,** J. J. WAGSCHAL,** J. H. MARABLE, AND C. R. WEISBIN, "Relative Consistency of ENDF/B-IV and -V with Fast-Reactor Benchmarks," p. 182. (3.13)

Workshop on Thorium Utilization in the Nuclear Power Program, MITRE Corporation, October 26-27, 1979

BARTINE, E., (presented by T. J. BURNS) "The Use of Thorium in Fast Breeder Reactors," (0.33)

1979 Winter Meeting of the American Nuclear Society, San Francisco, CA, November 11-15, 1979; Trans. Am. Nucl. Soc. 33 (1973)

BARNEN, J., AND D. G. CACUCI, "Computation of Analytical Bounds for Cross-Section Self-Shielding Factors," p. 351. (3.9)

BARTINE, D. E., D. T. INGERSOLL, AND C. O. SLATER, "Recent Shielding Experiments at the ORNL Tower Shielding Facility," p. 664. (4.15)

BROADHEAD, B. L.,** AND J. J. WAGSCHAL,** "The NBS Intermediate-Energy Standard Neutron Field (ISNF) Revisited," p. 848. (3.47)

EMMETT, M. B.,** R. L. CHILDS,** AND W. A. RHOADES, "A Repair for Scattering Expansion Truncation Errors in Transport Calculations," p. 719. (5.11)

LILLIE, R. A., R. G. ALSMILLER, JR., T. A. GABRIEL, R. T. SANTORO, AND S. W. SCHWENTERLY,** "Monte Carlo Simulation of Neutron Particle Transport in a Neutral-Beam Injector," p. 43. (6.41)

MAERKER, R. E., "An Overview of CSENG Shielding Benchmark Problems," p. 661. (3.15)

OZER, O.,** R. E. MacFARLANE,** AND M. L. WILLIAMS, "Implementation of ENDF/B-IV and V Data in LWR Design Codes: EPRI-CELL and EPRI-CPM," p. 820. (3.11)

RHOADES, W. A., AND E. T. TOMLINSON,** "Effectiveness of Three Rebalance Methods in Deep Penetration Problems," p. 717. (5.4)

RINALDIS, C. D.,** J. M. KALLFELZ,** E. KUJAWSKI,** AND J. H. MARABLE, "Evaluation of Integral Parameter Correlations and Reactor Performance Using Nuclear Data Covariances," p. 859. (3.56)

SANTORO, R. T., R. G. ALSMILLER, JR., J. M. BARNES,** G. T. CHAPMAN, G. L. MORGAN,** E. M. OBLON, AND R. W. PELLE, "Analysis of ORNL Fusion Reactor Shield Integral Experiments," p. 665. (4.4)

SMITH, J. D.,** H. L. DODDS,** F. G. PEREY, AND C. R. WEISBIN, "Processing ENDF/B-V Uncertainty Data into Multigroup Covariance Matrices," p. 822. (3.10)

WAGSCHAL, J. J.,** R. E. MAERKER, AND B. L. BROADHEAD,** "Cross-Section Adjustment: Sensitivity to Uncertainties," p. 698. (3.39)

WAGSCHAL, J. J.,** R. E. MAERKER, AND D. M. GILLIAM, "Detailed Error Analysis of Average Fission Cross-Section Measurements in NBS Standard Neutron Fields," p. 823. (3.45)

WEBER, C. F.,** D. G. CACUCI, AND E. M. OBLON, "Differential Sensitivity Theory for Nonlinear Equations with Nonlinear Responses," p. 338. (3.2E)

WEHRING, B. W.,** J. J. DORNING,** N. E. HERTEL,** D. T. INGERSOLL, AND R. H. JOHNSON,** "Benchmark Shielding Problems Obtained from Integral Tests of Neutron Cross Sections," p. 666. (3.16)

DOE/CEA-BMFT Specialist Meeting on Neutronic Computational Methods, Karlsruhe, Federal Republic of Germany, November 22-23, 1979

RHOADES, W. A., "The Utility and Capability of DOT IV." (5.28)

VONDY, D. R., "Solving the Nuclear Reactor Core Problems." (5.28)

American Nuclear Society Topical Meeting on Measurement Technology for Safeguards and Material Control, Kiawah Island, Charleston, SC, November 26-29, 1979; NBS Special Publication No. 582

RAGAN, G. L.,** C. W. RICKER,** M. M. CHILES,** D. T. INGERSOLL, G. G. SLAUGHTER,** AND L. R. WILLIAMS, "System for Nondestructive Assay of Spent Fuel Subassemblies - Comparison of Calculations and Measurements," p. 447. (6.57)

Annual Meeting of the Israel Nuclear Society, Haifa, Israel, December 17, 1979

WAGSCHAL, J. J.,** AND Y. YEIVIN,** "Data Testing of ENDF/B-IV and -V." (3.14)

Joint Conference, 6th Advances in Reliability Technology Symposium and 3rd European Reliability Data Bank Seminar, University of Bradford, United Kingdom, April 9-11, 1980

BOTT, T. F.,** G. W. CUNNINGHAM,** N. M. GREENE,** P. M. HAAS, S. D. HUDSON, H. E. KNEE, AND J. J. MANNING, "Development of the Centralized Reliability Data Organization (CREDO)," NCSR-R24, pp. 309-334, July 1980

HAAS, P. M., AND T. F. BOTT,** "Criteria for Safety-Related Nuclear Plant Operator Actions: A Preliminary Assessment of Available Data (II)," NCSR-R23, Vol. 2, pp. 197-217, July 1980

Seminar-Workshop on the Theory and Application of Monte Carlo Methods, Oak Ridge, TN, April 21-23, 1980; ORNL/RSIC-44, August, 1980

CRAMER, S. N., AND R. W. ROUSSIN, "Experience with TRIPOLI at ORNL," p. 295. (5.9)

EMMETT, M. B.,** AND J. T. WEST, III, "MORSE: Current Status of the Two Oak Ridge Versions," p. 305. (5.10)

1980 Spring Meeting of the American Physical Society, Washington, D.C., April 21-May 1, 1980; Bull. Am. Phys. Soc. 25 (1980)

PLATTARD, S.,** G. F. AUCHAMPAUGH,** N. W. HILL,** G. de SAUSSURE, R. G. PEREZ, AND J. A. HARVEY,** "The Triple-Humped Fission Barrier of ^{232}Pa ," p. 487. (1.12)

WINTERS, R. R.,** G. L. MORGAN,** R. L. MACKLIN,** D. K. OLSEN, J. A. HARVEY,** AND N. W. HILL,** " ^{238}U Neutron Inelastic Scattering at 82 keV," p. 543. (1.7)

Symposium on Neutron Cross Sections from 10-40 MeV, Brookhaven National Laboratory, Upton, NY, May 12-14, 1980; BNL-NCS-51245 (1980)

FU, C. Y., "Development and Applications of Multi-Step Hauser-Feshbach/Pre-Equilibrium Model Theory," Vol. 2, p. 675. (2.2)

LARSON, D. C., "ORELA Measurements to Meet Fusion Energy Neutron Cross Section Needs," Vol. 1, p. 277. (1.1)

1980 Annual Meeting of the American Nuclear Society, Las Vegas, NV, June 9-12, 1980;
Trans. Am. Nucl. Soc. 34 (1980)

BOMMAN, S. M.,** M. L. WILLIAMS, AND H. L. DODDS,** "Implementation of Generalized Perturbation Theory into the 3-D Modal Code SIMULATE," p. 305. (3.59)

CACUCI, D. G., AND C. F. WEBER,** "Application of Sensitivity Theory for Extrema of Functionals to a Transient Reactor Thermal-Hydraulics Problem," p. 312. (3.29)

CHILDS, R. L.,** D. L. SELBY, J. C. ROBINSON,** R. G. CANADA,** AND R. L. MONDAY,** "Calculation of the TMI-2 Source-Range Monitor Reading for Several Core Water Levels," p. 558. (6.28)

GABRIEL, T. A., R. A. LILLIE, AND B. L. BISHOP,** "Design of Materials Irradiation Experiments Utilizing Spectral Tailoring," p. 228. (6.40)

GREENSPAN, E.,** AND M. L. WILLIAMS, "Constrained Sensitivity Theory," p. 823. (3.24)

LILLIE, R. A., T. A. GABRIEL, B. L. BISHOP,** AND V. C. BAKER,** "One-Dimensional Gamma-Ray Shielding Calculations for the EBT-P," p. 642. (6.38)

MAERKER, R. E., "S_n Transport Calculations of the PCA Experiments with Some Estimated Uncertainties," p. 628. (3.42)

MAUDLIN, P. J.,** AND C. V. PARKS,** "Generalized Sensitivity Theory Applied to the MELT-III A Fast Reactor Safety Code," p. 520. (3.53)

PLATTARD, S.,** G. F. AUCHAMPAUGH,** G. de SAUSSURE, N. W. HILL,** J. A. HARVEY,** AND R. B. PEREZ, "High Resolution Measurement of the ²⁵¹Pu(n,f) Cross Section from 0.4 eV to 12 MeV," p. 768. (1.11)

RONEN, Y.,** M. COJOCARU,** AND A. RADKOWSKY,** "The Void Coefficient in a Unit Cell for U-Pu Water Breeder Reactors," p. 784. (3.61)

TOMLINSON, E. T.,** AND W. A. RHOADES, "Evaluation of Flux Extrapolation Models for Discrete Ordinates Shielding Analysis," p. 650. (5.5)

WAGSCHAL, J. J.,** R. E. MAERKER, AND Y. YEIVIN,** "Extrapolation of Surveillance Dosimetry Information to Predict Pressure Vessel Fluences," p. 631. (3.60)

WAGSCHAL, J. J.,** AND Y. YEIVIN,** "The Significance of LaGrange Multipliers in Cross-Section Adjustment," p. 776. (3.40)

WEBER, C. F.,** D. G. CACUCI, AND C. V. PARKS,** "Applications of Differential Sensitivity Theory for Problems with Discontinuities," p. 314. (3.32)

WHITE, J. R.,** AND T. J. BURNS, "Development and Verification of Multicycle Depletion Perturbation Theory," p. 824. (5.17)

Third Symposium of the Institute of Gas Technology on Energy Modeling, Chicago, IL, August 4-8, 1980

WEISBIN, C. R., AND R. G. ALSMILLER, JR., "Highlights of the ORNL Model Evaluation Methodology and the Evaluation of LEAP," (7.4)

American Nuclear Society Topical Meeting on Advances in Reactor Physics and Shielding, Sun Valley, ID, September 14-17, 1980

BARNEN, J., D. G. CACUCI, J. J. WAGSCHAL,** AND C. B. MULLINS, "A Systematic Methodology for the Reduction of Uncertainties in Transient Thermal-Hydraulics by Using In-Bundle Measurement Data" (3.30)

CACUCI, D. G., E. GREENSPAN,** J. H. MARABLE, AND M. L. WILLIAMS, "Developments in Sensitivity Theory" (3.25)

CRAMER, S. M., D. A. REED,** M. B. EMMETT,** AND C. A. ROUSE,** "Analysis of the New GCFR Upper and Lower Plenum Flow-Through Shields" (6.17)

ENGLE, W. W., "The Current Status of Methods for Shielding Analysis" (5.26)

JERMANN, M.,** AND D. T. INGERSOLL, "Neutron Spectrum Evaluation in the Thorium Axial Blankets of the PROTEUS Reactor." (6.23)

KALLFELZ, J. M.,** D. BISWAS,** C. L. CONAN,** J. H. MARABLE, M. L. WILLIAMS, C. R. WEISBIN, J. D. DRISCHLER, T. B. FOWLER, AND J. R. WHITE,** "Design and Sensitivity Analysis of a CDS-Type Heterogeneous Core" (5.57)

MAIENSCHIN, F. C., "The Status of Reactor Shielding Research in the U.S." (6.61)

OLSEN, D. K., R. W. INGLE,** AND J. L. PORTNEY,** "Precise Measurement and Analysis of Neutron Transmission Through ^{232}Th " (1.18)

SIMMONS, G. L.,** AND R. W. ROUSSIN, "A New Cross Section Library for Light Water Reactor Shielding and Pressure Vessel Dosimetry Applications" (3.4)

WAGSCHAL, J. J.,** B. L. BROADHEAD,** AND R. E. MAERKER, "Least Squares Methodology Applied to LWR-PV Damage Dosimetry, Experience and Expectations" (3.59)

YEIVIN, Y.,** J. H. MARABLE, C. R. WEISBIN, AND J. J. WAGSCHAL,** "ORACLE: An Adjusted Cross-Section and Covariance Library for Fast-Reactor Analysis" (3.34)

Eleventh Symposium on Fusion Technology, Oxford, England, September 15-19, 1980

SANTORO, R. T., R. G. ALSMILLER, JR., J. M. BARNES,** AND G. T. CHAPMAN, "Comparison of Calculated and Experimental Neutron Attenuation and Streaming Data for Fusion Reactor Design" (4.7)

Workshop on Evaluation Methods and Procedures, Brookhaven National Laboratory, Upton, NY, September 22-25, 1980

FU, C. Y., "Evaluation of Photon Production Data from Neutron-Induced Reactions" (2.4)

MARABLE, J. H., "The Adjustment of Cross Sections Based on Integral Experiments in Fast Benchmark Assemblies" (3.35)

PEREY, F. G., "Logical Inference and Evaluation" (2.16)

WESTON, L. W., "Evaluation of Neutron Cross Sections for Fissile and Fertile Nuclides in the keV Range" (2.5)

Symposium on Intermediate Range Atmospheric Transport Processes and Technology Assessment, Gatlinburg, TN, October 1-3, 1980

MCGILL, B. L., B. F. MASKEWITZ, AND D. K. TRUBEY, "The Technical Data Management Center: A Focal Point for Meteorological and Other Environmental Transport Computing Technology" (0.4)

American Nuclear Society Topical Meeting on Nuclear Reactor Thermal-Hydraulics, Saratoga, NY, October 6, 1980

CACUCI, D. G., AND C. F. WEBER,** "Application of Sensitivity Theory for Extrema of Functionals to a Transient Reactor Thermal-Hydraulics Problem" (3.29)

Journées d'Etudes sur la Fusion, L'Alpe D'Huez, 6-10 Octobre 1980

PLATTARD, S.,** G. F. AUCHAMPAUGH,** N. W. HILL,** G. de SAUSSURE, R. B. PEREZ, ET J. A. HARVEY,** "Propriétés Spectroscopiques de Quelques Structures Fines Observées dans le Seuil de la Réaction $^{231}\text{Pa}(n,f)$ " (1.13)

Seventh International CODATA Conference, Kyoto, Japan, October 8-11, 1980

MASKEWITZ, B. F., "Data Bases for Rapid Response to Power Reactor Problems." (9.6)

Meeting of the American Physical Society, Minneapolis, MN, October 9-11, 1980

LARSON, D. C., "Calculation of the $^{23}\text{Na}(n,2n)$ Cross Section" (2.11)

Fourth American Nuclear Society Meeting on the Technology of Controlled Nuclear Fusion, King of Prussia, PA, October 14-17, 1980

McGILL, B. L., R. W. ROUSSIN, D. K. TRUBEY, AND B. F. MASKEWITZ, "Radiation Shielding Information Center: A Source of Computer Codes and Data for Fusion Neutronics Studies." (9.7)

SANTORO, R. T., R. G. ALSMILLER, JR., J. M. BAKNES,** AND G. T. CHAPMAN, "ORNL Fusion Reactor Shielding Integral Experiments." (4.6)

Specialists' Meeting on Nuclear Data and Benchmarks for Reactor Shielding, OECD Headquarters, Paris, France, October 27-29, 1980

ROUSSIN, R. W., J. D. DRISCHLER, AND J. H. MARABLE, "Status of Multigroup Sensitivity Profiles and Covariance Matrices Available from the Radiation Shielding Information Center." (3.7)

ROUSSIN, R. W., D. K. TRUBEY, AND B. F. MASKEWITZ, "Status of Multigroup Cross-Section Libraries Available from the Radiation Shielding Information Center." (3.7)

ROUSSIN, R. W., C. R. WEISBIN, AND J. L. LUCIUS,** "A Review of the Capabilities of the ORNL FORSS Sensitivity and Uncertainty Analysis System" (3.19)

Sixth Conference on the Application of Accelerators in Research and Industry, North Texas State University, Denton, Texas, November 3-5, 1980

CHAPMAN, G. T., G. L. MORGAN,** AND J. W. McCONNELL, "The Use of a Small Accelerator as a Source of 14-MeV Neutrons for Shielding Studies." (4.8)

Symposium on Nuclear Power Systems, Orlando FL, November 5-7, 1980

KISNER, R. A.,** AND G. F. FLANAGAN, "A Systems Approach to Defining Operator Roles." (8.3)

1980 Nuclear Science Symposium of the Institute of Electrical and Electronics Engineers, Orlando, FL, November 5-7, 1980

GOODMAN, M. S.,** G. DENIS,** M. HALL,** A. KARPOVSKY,** R. WILSON,** T. A. GABRIEL, AND B. L. BISHOP,** "Liquid Argon as an Electron/Photon Detector in the Energy Range of 50 MeV to 2 GeV: A Monte Carlo Investigation." (6.49)

1980 Annual Meeting of the American Society of Mechanical Engineers, Chicago, IL, November 18-19, 1980

MAUDLIN, P. J.,** C. V. PARKS,** AND C. F. WEBER,** "Generalized Sensitivity Theory Applied to the Space and Time Dependent Thermal-Hydraulics Conservation Equations." (3.31)

1980 Winter Meeting of the American Nuclear Society, Washington, D.C., November 18-21, 1980; Trans. Am. Nucl. Soc. 35 (1980)

ALSMILLER, F. S., R. G. ALSMILLER, JR., T. A. GABRIEL, R. A. LILLIE, AND J. BARISH,** "A Phenomenological Model for Particle Production from the Collision of Nucleons at Medium Energies with Fissile Elements," p. 475. (6.51)

ALSMILLER, R. G., JR., T. A. GABRIEL, J. BARISH,** AND F. S. ALSMILLER, "Thermal-Neutron Flux Generation by High-Energy Protons in Thick Uranium Targets," p. 477. (6.52)

BARHEN, J., AND D. G. CACUCI, "An Efficient Procedure to Evaluate Second-Order Sensitivities for Nonlinear Problems with Nonlinear Responses," p. 266. (3.33)

BARHEN, J., J. J. WAGSCHAL,** AND Y. YEIVIN,** "Response-Parameter Correlations in Uncertainty Analysis," p. 246. (3.41)

BROADHEAD, B. L.,** AND J. J. WAGSCHAL,** "The ISNF: A New CSEWG Dosimetry Benchmark (Computational Problems and Their Solution)," p. 466. (3.48)

INGERSOLL, D. T., AND L. R. WILLIAMS, "Analysis of the ORNL-TSF Radial Blanket and Shield Integral Experiments," p. 470. (4.14)

MAERKER, R. E., J. H. MARABLE, AND J. J. WAGSCHAL,** "Estimation of the Uncertainties in the ENDF/B-V ^{235}U Fission Spectrum," p. 355. (3.49)

RYSKAMP, J. M.,** R. A. ANDERL,** B. L. BROADHEAD,** W. E. FORD, III,** J. L. LUCIUS,** J. H. MARABLE, AND J. J. WAGSCHAL,** "Sensitivity and a priori Uncertainty Analysis of the CFRMF Central Flux Spectrum," p. 556. (3.51)

VONDY, D. R., "On Validating Major Computer Codes," p. 255. (5.25)

ANS/ENS International Topical Meeting on Advances in Mathematical Methods for Nuclear Engineering Problems, Munich, Federal Republic of Germany, April 27-29, 1981

CACUCI, D. G., P. J. MAUDLIN,** C. V. PARKS,** AND C. F. WEBER,** "Recent Advances and Applications of Differential Sensitivity Theory in Reactor Safety." (3.26)

A-34

Blank

AUTHOR INDEX

- Abbott, L. S. 4.18, 4.19, 6.27, 6.32, 8.5
- Alsmiller, F. S. 6.50, 6.51, 6.52
- Alsmiller, R. G., Jr. 4.1, 4.2, 4.4, 4.5, 4.6, 4.7, 6.34, 6.35, 6.36, 6.37, 6.41, 6.44, 6.45, 6.46, 6.50, 6.51, 6.52, 6.58, 7.1, 7.3, 7.4, 7.5
- Alter, H. 8.10
- Anderl, R. A. 3.51
- Arnold, J. W. 6.5
- Arwood, J. W. 8.8, 8.9, 8.11
- Auchampaugh, G. F. 1.10, 1.11, 1.12, 1.13, 1.14
- Aull, J. E. 5.1, 5.2, 5.3
- Baer, D. K. 8.5
- Baker, V. C. 3.44, 6.38, 6.59
- Bankert, S. F. 9.3
- Barhen, J. 3.3, 3.8, 3.9, 3.30, 3.33, 3.41, 3.62, 5.19, 5.20
- Barish, J. 6.36, 6.44, 6.45, 6.46, 6.50, 6.51, 6.52, 7.3, 7.5
- Barnes, J. M. 4.1, 4.2, 4.4, 4.5, 4.6, 4.7, 6.35, 6.36
- Bartine, D. E. 4.12, 4.15, 4.16, 6.20, 6.27, 6.32, 6.33, 6.55
- Bauman, H. F. 6.54
- Bishop, B. L. 6.38, 6.39, 6.40, 6.47, 6.48, 6.49
- Biswas, D. 3.57
- Bjerke, M. A. 3.52
- Bjornstad, D. 7.2, 7.3
- Bohanan, R. E. 3.63
- Bott, T. F. 6.5, 8.1, 8.2, 8.6, 8.7
- Bowman, S. M. 3.58
- Broadhead, B. L. 3.39, 3.47, 3.48, 3.51, 3.59
- Bryant, E. W. 3.17, 9.11
- Burns, T. J. 3.55, 5.17, 6.14, 6.18, 6.19, 6.24, 6.25, 6.27, 6.30, 6.32, 6.33, 6.55
- Cacuci, D. G. 3.3, 3.8, 3.9, 3.25, 3.26, 3.27, 3.28, 3.29, 3.30, 3.32, 3.33, 3.38, 3.62, 3.63
- Cain, V. R. 5.12
- Canada, R. G. 6.28
- Carroll, B. Talmi 9.1
- Chapman, G. T. 1.22, 4.1, 4.3, 4.4, 4.5, 4.6, 4.7, 4.8
- Chawla, R. 6.20
- Childs, R. L. 3.44, 3.65, 3.66, 4.19, 5.11, 6.28, 6.44
- Chiles, M. M. 6.56, 6.57
- Clifford, C. E. 4.18
- Cojocaru, M. 3.61
- Collins, P. J. 3.18, 3.37
- Comolander, H. E. 3.6
- Cook, D. H. 3.63
- Courtney, J. C. 9.5
- Cowan, C. L. 3.57
- Craddick, W. G. 3.63
- Cramer, S. N. 4.10, 4.11, 5.9, 5.21, 6.14, 6.16, 6.17, 6.29
- Cowan, C. L. 3.37
- Cunningham, G. W. 3.22, 5.14, 8.7
- Dearing, J. F. 6.53, 6.54
- Derby, S. 8.4
- de Saussure, G. 1.9, 1.10, 1.11, 1.12, 1.13, 1.14, 3.18, 3.36, 3.44, 3.52
- Dickens, J. K. 1.25, 1.26, 1.27, 1.28, 1.29, 1.30, 1.31, 1.32, 1.33, 1.34, 1.35, 1.36
- Dietz, R. L. 8.5
- Diffilip, F. C. 1.9
- Diggs, B. R. 3.6

- Dodds, H. L. 2.10, 3.58, 5.1, 5.21
 Dorning, J. J. 3.16
 Downing, D. J. 7.2, 7.3
 Drischler, J. D. 3.7, 3.20, 3.21, 3.44, 3.57
 El-Bassioni, A. A. 8.12
 Emery, J. F. 1.29
 Emmett, M. E. 5.10, 5.11, 5.12, 6.9, 6.13, 6.16, 6.17
 England, T. R. 1.29
 Engel, J. R. 6.53, 6.54
 Engle, W. W., Jr. 5.6, 5.26, 5.27, 6.9, 6.10, 6.13
 Erickson, J. J. 9.10
 Felds, D. K. 3.63
 Fischhoff, B. 8.4
 Flanagan, G. F. 6.5, 6.7, 6.9, 8.3, 8.8, 8.9, 8.10
 Flanders, R. M. 3.63
 Ford, W. E., III 3.3, 3.6, 3.51, 7.3
 Fontana, M. H. 6.5
 Forsberg, V. M. 6.5, 8.8, 8.9, 8.11
 Fowler, T. B. 3.57, 5.13, 5.14
 Fox, P. B. 6.7
 Francis, C. C. 8.5
 Froehner, F. H. 1.37
 Fu, C. Y. 2.1, 2.2, 2.3, 2.4, 2.6, 2.8, 2.14
 Gabriel, T. A. 5.27, 6.38, 6.39, 6.40, 6.41, 6.45, 6.47, 6.48, 6.49, 6.50, 6.51, 6.52
 Gat, U. 6.14
 Gilliam, D. M. 3.45, 3.46
 Guier, K. 6.20, 6.21
 Goldstein, M. 7.5
 Goodman, M. S. 6.49
 Greene, N. M. 3.2, 6.5, 8.7, 8.8, 8.9, 8.10, 8.11
 Greenspan, E. 3.18, 3.23, 3.24, 3.25
 Grimes, W. R. 6.43, 6.53, 6.54
 Gurney, J. 9.10, 9.11
 Gustin, A. B. 9.11
 Gwin, R. 1.15, 1.16
 Haas, P. M. 6.5, 8.1, 8.2, 8.5, 8.6, 8.7
 Hagar, R. C. 3.63
 Hall, M. 6.49
 Harvey, J. A. 1.2, 1.3, 1.7, 1.8, 1.10, 1.11, 1.12, 1.13, 1.14
 Hendrickson, H. R. 3.17
 Hertel, N. E. 3.16
 Hetrick, D. M. 1.2, 2.3, 2.8, 2.14
 Hill, P. W. 1.3, 1.7, 1.8, 1.10, 1.11, 1.12, 1.13, 1.14
 Hoffman, T. J. 5.23
 Horwedel, J. 7.3
 Hudson, S. D. 6.5, 8.7
 Hull, J. L. 4.13
 Hyman, C. R. 3.63
 Ingersoll, D. T. 3.16, 4.10, 4.11, 4.12, 4.14, 4.15, 4.16, 4.17, 5.7, 5.24, 6.14, 6.20, 6.21, 6.22, 6.23, 6.56, 6.57
 Ingle, R. W. 1.9, 1.15, 1.16, 1.18
 Jermann, M. 6.20, 6.23
 Johnson, G. L. 5.5
 Johnson, J. O. 5.24, 6.30
 Johnson, R. H. 3.16
 Jones, D. W. 8.5
 Kallfelz, J. M. 3.56, 3.57
 Karpovsky, A. 6.49

- Kasten, P. R. 6.14, 6.27
- Keeney, R. 8.4
- Kisner, R. A. 8.3
- Knee, H. E. 6.2, 6.3, 6.5, 6.8, 6.9, 6.10, 8.7
- Knight, J. R. 4.9, 6.13, 6.29
- Kujawski, E. 3.18, 3.56
- Lahti, G. P. 9.5
- Larson, D. C. 1.1, 1.2, 1.3, 1.23, 2.3, 2.9, 2.10, 2.11, 2.15
- Larson, M. M. 1.38, 2.15
- Lee, C. J. 7.3
- Lee, R. R. 9.5
- Lichtenstein, S. 8.4
- Lillie, R. A. 3.66, 6.35, 6.36, 6.37, 6.38, 6.40, 6.41, 6.50, 6.51, 6.58
- Love, T. A. 1.27, 1.29, 1.30, 1.36
- Loyd, D. L. 6.9, 6.10, 6.12
- Lucius, J. L. 3.19, 3.20, 3.22, 3.44, 3.50, 3.51, 6.31
- Lundy, J. C. 1.24
- MacFarlane, R. E. 3.11
- Macklin, R. L. 1.7, 1.8
- Maerker, R. E. 3.15, 3.39, 3.42, 3.43, 3.45, 3.49, 3.59, 3.60
- Maienschein, F. C. 6.61
- Mailen, G. S. 3.63
- Manning, J. J. 4.13, 6.5, 8.6, 8.7
- Marable, J. H. 3.7, 3.13, 3.18, 3.20, 3.23, 3.25, 3.27, 3.34, 3.35, 3.36, 3.37, 3.44, 3.49, 3.50, 3.51, 3.52, 3.56, 3.57, 6.59
- Maskewitz, B. F. 3.7, 9.1, 9.2, 9.3, 9.4, 9.6, 9.7, 9.8
- Maudlin, F. J. 3.26, 3.31, 3.53, 6.5
- McAdoo, J. 7.3
- McClain, W. J. 9.10
- McCombie, C. 6.20
- McConnell, J. W. 1.4, 1.5, 1.6, 1.27, 1.28, 1.29, 1.30, 1.31, 1.32, 1.33, 1.34, 4.5, 4.8
- McCoy, H. E. 6.54
- McGill, G. L. 5.8, 9.4, 9.7, 9.9
- Metghalchi, M. 3.5, 3.12, 9.12
- Mihalczo, J. T. 6.4, 6.8, 6.10
- Monday, R. L. 6.28
- Morgan, G. L. 1.4, 1.5, 1.6, 1.7, 1.8, 1.19, 1.20, 1.21, 1.22, 1.23, 4.3, 4.4, 4.5, 4.8
- Morris, D. G. 5.22
- Muckenthaler, F. J. 4.12, 4.13, 4.16, 4.17, 4.18, 4.19, 6.14
- Mullins, C. B. 3.30
- Mynatt, F. R. 4.18
- Nakhai, B. 3.12
- Northcutt, K. J. 1.29, 1.31
- Oblow, E. M. 3.22, 3.27, 3.28, 4.2, 4.4, 6.5, 6.31, 7.1, 7.3
- Olsen, D. K. 1.4, 1.5, 1.6, 1.7, 1.8, 1.9, 1.18, 1.38
- Ott, L. J. 3.63
- Ozer, Odelli 3.11
- Pace, J. V., III 6.29
- Parks, C. V. 3.26, 3.31, 3.32, 3.53, 6.5
- Peelle, R. W. 1.27, 1.29, 1.30, 3.18, 3.37, 4.4, 7.2, 7.3
- Perey, C. M. 2.7
- Perey, F. G. 1.24, 2.6, 2.7, 2.8, 2.15, 2.16, 3.10, 7.3
- Perez, R. B. 1.9, 1.10, 1.11, 1.12, 1.13, 1.14, 6.60
- Petrie, L. M. 3.6
- Plattard, S. 1.10, 1.11, 1.12, 1.13, 1.14
- Portney, J. L. 1.18
- Price, C. E. 9.2
- Radkowsky, A. 3.61

- Ragan, G. L. 6.56, 6.57
 Ragheb, M. M. H. 6.36
 Raiford, G. B. 6.5, 8.8, 8.9, 9.11
 Reed, D. A. 6.16, 6.17
 Renier, J. P. 6.55
 Rhoades, W. A. 5.1, 5.4, 5.5, 5.6, 5.11, 5.28, 6.13, 6.53, 6.54
 Richmond, R. 6.20
 Ricker, C. W. 6.56, 6.57
 Rinaldis, D. 3.56
 Robinson, J. C. 6.28
 Ronen, Y. 3.38, 3.61, 3.62, 6.31
 Rothenstein, W. 5.19, 5.20
 Rouse, C. A. 6.17
 Roussin, R. W. 3.1, 3.2, 3.3, 3.4, 3.5, 3.6, 3.7, 3.12, 3.17, 3.19, 5.9, 9.7, 9.11
 Rutten, H. J. 6.26
 Ryskamp, J. M. 3.51
 Saltmarsh, M. J. 6.43
 Salvatores, M. 3.37
 Santoro, R. T. 4.1, 4.2, 4.4, 4.5, 4.6, 4.7, 6.35, 6.36, 6.37, 6.41, 6.42, 6.43, 6.58
 Schmocker, U. 6.20, 6.21
 Schwenterly, S. W. 6.41
 Sege, C. 6.32
 Selby, D. L. 6.2, 6.3, 6.6, 6.7, 6.8, 6.9, 6.10, 6.11, 6.12, 6.28
 Seth, S. 6.20
 Simmons, G. L. 3.4
 Simpkins, W. M. 6.12
 Simpson, D. B. 6.7, 8.8, 8.9, 9.9
 Slater, C. O. 4.9, 4.10, 4.11, 4.15, 5.7, 6.14, 6.15, 6.16
 Slaughter, G. G. 6.56, 6.57
 Slovic, P. 8.4
 Smith, J. D. 3.10
 Spencer, R. R. 1.15, 1.16, 1.17, 1.37
 Spiewak, I. 6.32
 Stewart, L. 7.3
 Swain, W. T. 6.11
 Teuchert, E. 6.26
 Todd, J. H. 1.15, 1.39
 Tomlinson, E. T. 3.66, 5.4, 5.5, 5.6, 6.1, 6.5, 6.14, 6.15, 6.16
 Trubey, D. K. 3.7, 5.8, 9.4, 9.7, 9.11
 Vaughan, E. U. 5.23
 Vondy, D. R. 5.13, 5.14, 5.15, 5.16, 5.25, 5.28, 6.26
 Wagschal, J. J. 3.2, 3.3, 3.13, 3.14, 3.30, 3.34, 3.38, 3.39, 3.40, 3.41, 3.43, 3.45, 3.46, 3.47, 3.48, 3.49, 3.51, 3.59, 3.60
 Weaver, H. 1.15, 1.16
 Weber, C. F. 3.26, 3.27, 3.28, 3.29, 3.31, 3.32, 3.64
 Wehring, B. W. 3.16
 Weisbin, C. R. 3.1, 3.2, 3.3, 3.10, 3.13, 3.17, 3.18, 3.19, 3.20, 3.34, 3.36, 3.37, 3.52, 3.57, 7.1, 7.3, 7.4
 West, J. T. 3.5, 3.12, 5.10
 Weston, L. W. 2.5, 2.12, 2.13
 Westfall, R. M. 3.44
 White, M. D. 3.63
 White, J. E. 3.1, 3.2, 3.3, 3.20
 White, J. R. 3.55, 3.57, 5.17, 5.18, 6.14, 6.18, 6.19, 6.20, 6.21, 6.22, 6.24, 6.25
 Wiffen, F. W. 6.39
 Williams, L. R. 4.14, 6.9, 6.15, 6.57, 6.14
 Williams, M. L. 3.11, 3.23, 3.24, 3.25, 3.54, 3.55, 3.57, 3.58, 4.11
 Wilson, R. 6.49
 Winders, J. M. 8.5
 Winters, R. R. 1.7, 1.9

Woodside, M. A. 6.5

Worley, B. A. 6.26, 6.27

Wright, J. B. 3.1

Wright, R. Q. 2.12, 3.1, 3.2, 3.3, 3.20

Yeivin, Y. 3.13, 3.14, 3.34, 3.40,
3.41, 3.60

ENGINEERING PHYSICS DIVISION

1051 1 584744