Coal Liquefaction Process Streams Characterization and Evaluation

The Application of ^{252}Cf -Plasma Desorption Mass Spectrometry to Analysis of Direct Coal Liquefaction Heavy Products

Topical Report

DOE/PC/89883--58

Prepared by:

DE93 007942

Lehigh University
Department of Chemistry
Seeley G. Mudd Building 6
Bethlehem, PA 18015

John W. Larsen
Andrzej R. Lapucha

Prepared for:

CONSOL Inc.
Research & Development
4000 Brownsville Road
Library, PA 15129

F. P. Burke
R. A. Winschel
S. D. Brandes

October 1992

Under Contract to:

United States Department of Energy
Contract No. DE-AC22-89PC89883

U.S. DOE Patent Clearance was provided by
Chicago Operations Office on October 20, 1992.

PROJECT ASSESSMENT

Introduction

Under subcontract from CONSOL Inc. (U.S. DOE Contract No. DE-AC22-89PC89883), Lehigh University studied the use of californium plasma desorption mass spectrometry (^{252}Cf -PDMS), gel permeation chromatography (GPC), and medium pressure liquid chromatography (MPLC) for analysis of tetrahydrofuran-soluble coal derived resids. The full report authored by the Lehigh researchers is presented here. The following assessment briefly highlights the major findings of the project, and evaluates the potential of the methods for application to coal derived materials. These results will be incorporated by CONSOL into a general overview of the application of novel analytical techniques to coal derived materials at the conclusion of this contract.

Summary

This study demonstrated the feasibility of using ^{252}Cf -PDMS, GPC, and MPLC for the examination of the tetrahydrofuran (THF)-soluble portion of distillation resid materials derived from direct coal liquefaction. The ^{252}Cf -PDMS technique was used to determine molecular weight distributions of twenty-five THF-soluble resids. In order to determine if ^{252}Cf -PDMS responds differently to different chemical classes of compounds, Lehigh separated five of the samples into chemically distinct fractions by MPLC, then analyzed the parent samples, their fractions, and the re-mixed fractions by ^{252}Cf -PDMS and GPC. Irreversible alteration of the samples upon separation was noted by Lehigh. This was confirmed by use of gas chromatographic (GC) analyses. The noted irreversible alterations prevented a direct comparison of the remixed materials and the original samples. Thus, the selective response of ^{252}Cf -PDMS to different chemical classes of compounds could not be confirmed or ruled out. The number average molecular weights (M_n) obtained by ^{252}Cf -PDMS and GPC agreed well. However, the weight average molecular weights (M_w) obtained by GPC are always higher than the corresponding ^{252}Cf -PDMS results. Number average molecular weights and weight average molecular weights obtained with ^{252}Cf -PDMS and GPC were compared with those obtained by field ionization mass spectrometry (FIMS), previously reported by SRI International¹ for the parent resid samples from which the Lehigh THF-soluble samples were

derived. Both GPC and ^{252}Cf -PDMS gave higher weight average molecular weights (M_w) than FIMS, but all three methods gave similar number average molecular weights (M_n). Vapor phase osmometry (VPO) and ebulliometry (two additional methods for determination of average molecular weights) were considered for use on these samples, but not attempted due to lack of time. Further development of the ^{252}Cf -PDMS and GPC methods as process development tools appears to be justified based on the results of this study.

Program Description

This report describes the work performed at Lehigh University under a subcontract from CONSOL Inc., Research and Development. CONSOL's prime contract to the U.S. Department of Energy (Contract No. DE-AC22-89PC89883, "Coal Liquefaction Process Streams Characterization and Evaluation") established a program for the analysis of direct coal liquefaction derived materials. The program involves a number of participating organizations whose analytical expertise is being applied to these materials. This Participants Program has two main objectives. The broad objective is to improve our understanding of fundamental coal liquefaction chemistry to facilitate process improvement and new process development. The specific approach to achieving this objective is to provide a bridge between direct coal liquefaction process development and analytical chemistry by demonstrating the application of various advanced analytical methods to coal liquefaction materials. The methodologies (or techniques) of interest are those which are novel in their application for the support of coal liquefaction and those which have not been fully demonstrated in this application. CONSOL is providing well-documented samples from different direct coal liquefaction production facilities to the program participants. The participants are required to interpret their analytical data in context to the processing conditions under which the samples were generated. The methodology employed is then evaluated for its usefulness in analyzing direct coal liquefaction derived materials.

Participant's Methodology

Lehigh used ^{252}Cf -PDMS, GPC, MPLC, and GC to analyze the THF-soluble portion of 850°F⁺ distillation resid. These materials are solids at room

temperature. All of the samples were produced at the Wilsonville pilot plant. Two major processing parameters were varied among the Wilsonville runs. These were feed coal and reactor configuration (thermal/catalytic (T/C) or catalytic/catalytic (C/C), and high/low (H/L) or low/high (L/H) reactor temperature). Samples were taken from three locations: between the reactors, after the second-stage reactor, and at the recycle oil tank. These samples are expected to represent different extents of coal liquefaction. Twelve of the samples were composites of samples taken over long periods of single runs. Two interstage samples were obtained from single run periods and were chosen to represent H/L and L/H reactor temperature sequences. Six samples were chosen from two different run periods within a single run to test the effects of T/C, H/L operation as compared to C/T, L/H operation. Two recycle samples were obtained from different run periods within a single run in which the major operating variable was the use of different catalysts. The ^{252}Cf -PDMS, GPC, MPLC, and GC experimental procedures are described on pages 5 through 8 of the attached report.

Participant's Major Findings

The following principal observations for the application of ^{252}Cf -PDMS, GPC, and MPLC to coal liquefaction materials were reported by Lehigh. An expanded discussion can be found in the attached report, pages 9 through 29.

The number average molecular weights of the samples determined by GPC were of the same order of magnitude as those obtained by ^{252}Cf -PDMS. The weight average molecular weights determined by GPC were consistently higher, by a factor of about 1.5, than those obtained by ^{252}Cf -PDMS. The authors suggest three possible reasons for the observed differences (see page 20 in the attached report).

In comparison to FIMS data¹, ^{252}Cf -PDMS mass spectra show similarities in the 100 - 1200 m/z range. Below 100 m/z, incomplete subtraction of ^{252}Cf -PDMS peaks, which arise from the Mylar disc on which the sample is supported, confound the spectra. At m/z greater than 1200, the ^{252}Cf -PDMS spectra exhibit an envelope of material. The FIMS technique was limited by volatility of the samples and the FIMS results were reported only up

to $m/e = 1400$, where resolution of the spectrum was good.² The additional material detected by ^{252}Cf -PDMS ($m/e > 1400$) increases the determined weight average molecular weights of the samples to twice the FIMS values. However, the number average molecular weights are identical (within experimental error, ± 10 Da).

To determine if the ^{252}Cf -PDMS technique discriminates by chemical class in the ionization process, MPLC was used to separate five samples into distinct chemical classes (oils, asphaltenes, and preasphaltenes). The parent samples, the MPLC fractions, and the remixed fractions were analyzed by GPC and ^{252}Cf -PDMS. Remixed samples had a consistently lower M_n than the original THF-soluble resid sample. No clear pattern was apparent for M_w ; however, the polydispersity (ratio of M_w/M_n) obtained from either method was consistently higher for all remixed samples. Gas chromatography was used to examine the original and remixed materials to examine possible causes for the differences. It was determined that the remixed materials were significantly different from the original samples. It was, therefore, not possible to determine whether or not discrimination by chemical class occurs in the ionization process of the ^{252}Cf -PDMS experiment. Examination of the ^{252}Cf -PDMS profiles of the separated fractions showed individual mass ions in the oils and asphaltene fractions and remixed fractions. These were not apparent in the original THF-soluble resid sample or in the preasphaltene fraction.

CONSOL Evaluation

The ^{252}Cf -PDMS and GPC techniques were shown to be capable of determining molecular weight distributions and average molecular weight values of direct coal liquefaction resid samples. The question of discrimination by chemical class by the ionization process of the ^{252}Cf -PDMS technique is yet unanswered. It is possible with the ^{252}Cf -PDMS method to detect materials with molecular weights on the order of 30,000 Da. The THF-soluble coal-derived resids examined in this study exhibited molecular weight envelopes which extended to approximately 3000 Da. It may be possible that some of the higher molecular weight material ($m/e > 1400$, which is the upper limit reported by the FIMS method) is the result of recombination reactions occurring post ionization². Although the FIMS technique is limited by volatility, the number average molecular weights

obtained by the ^{252}Cf -PDMS technique on THF-soluble portions of the resid agree well with the FIMS results.

Samples obtained from different runs with different processing parameters could not be distinguished by comparison of the number or weight average molecular weights obtained by the ^{252}Cf -PDMS or GPC techniques. A more detailed examination of the ^{252}Cf -PDMS profiles may prove to be of some utility in discerning differences in the process-derived resid samples.

The ^{252}Cf -PDMS equipment used in this study was a Bio-ion Model 20 spectrometer; it costs about \$220,000. It requires approximately one-half hour to prepare a solvent-soluble sample and approximately fifteen minutes to acquire data.

Further Development

There are a number of avenues for further development of the ^{252}Cf -PDMS and GPC techniques for coal liquefaction derived resids. Lehigh suggested a more extensive study of the application of the ^{252}Cf -PDMS and GPC techniques to a larger selection of resid samples, and other coal-derived samples, of high molecular weight. It is recommended by CONSOL that the molecular weight profiles obtained from ^{252}Cf -PDMS be carefully examined to detect any systematic variations which can be attributed to changes in processing conditions. The appearance of individual low-mass ions in the oils and asphaltene fractions which are not apparent in the whole original THF-soluble resid spectrum should be further investigated in light of the corresponding appearance of these same mass ions in the FIMS spectra¹ and field desorption mass spectrometry (FDMS) spectra³. It also is recommended that a further study be made to determine if chemical class discrimination affects the results from ^{252}Cf -PDMS.

Participant's Statement of Work

The analysis of coal products by ^{252}Cf -Plasma Desorption Mass Spectrometry (^{252}Cf -PDMS) has been only briefly explored. ^{252}Cf -PDMS is a technique which has been used for a variety of applications in the biochemical field and has shown some utility in the examination of petroleum heavy oils and bottoms. It has not, however, been fully demonstrated in its

application to the chemistry of coal conversion. As such, it fits well within the scope of the participants program.

The application of ^{252}Cf -PDMS to a reasonably large sample set (25 samples) will allow a demonstration of the value of this technique. These samples have been selected (see attached list) so that the utility of ^{252}Cf -PDMS for addressing the issue of resid reactivity can be evaluated. The twenty-five samples will be supplied to Lehigh with the following information: elemental analyses, ash content, ash elemental analysis, phenolic -OH concentration, calorific value, hydrogen classes by ^1H -NMR, and the full history of the sample (plant, process conditions, age, and storage conditions). Additionally, spectra obtained by other mass spectrometric techniques, such as field ionization mass spectrometry (FIMS) and field desorption mass spectrometry (FDMS), will be supplied for samples, as available. All samples are the tetrahydrofuran-soluble portion of non-distillable residual materials. Sample size will be approximately 1g. Most samples will be brittle pitch-like materials that will be supplied as approximately minus 60 mesh powder.

The question of whether or not discrimination is inherent in the ionization process in ^{252}Cf -PDMS will be addressed by preliminary separation of five of the samples (designated in the attached list) into aliphatic rich and aromatic rich fractions. These samples will be separated into chemical classes using liquid chromatographic techniques on a silica gel support. Material retained on the column will be recovered by dissolution of the silica gel in NaOH solution. Each fraction obtained will then be examined by ^{252}Cf -PDMS. The sample fractions will then be remixed and spectra obtained. Each of the five samples and their fractions will be examined by gel permeation chromatography, vapor phase osmometry, and, if possible, by ebulliometry to obtain comparative molecular weight data.

Repeat analyses will be performed as necessary to determine reproducibility.

References

1. Malhotra, R.; McMillen, D. F. "Coal Liquefaction Process Streams Characterization and Evaluation; Characterization of Coal Liquids

by Field Ionization Mass Spectrometry and Iodotrimethylsilane Derivatization, Topical Report," DOE/PC 89883-39, January 1992.

2. Personal communication with R. Malhotra, SRI International.
3. Campbell, J. A.; Linehan, J. C.; Robins, W. H. "Coal Liquefaction Process Streams Characterization and Evaluation; Characterization of Coal Derived Materials by Field Desorption Mass Spectrometry, Two-Dimensional Nuclear Magnetic Resonance, Supercritical Fluid Extraction, and Supercritical Fluid Chromatography/Mass Spectrometry, Topical Report," DOE/PC 89883-51, July 1992.

THE APPLICATION OF ^{252}Cf -PLASMA DESORPTION MASS SPECTROMETRY
TO ANALYSIS OF DIRECT COAL LIQUEFACTION HEAVY PRODUCTS.

John W. Larsen and Andrzej R. Lapucha

Lehigh University
Department of Chemistry
Seeley G. Mudd Building 6
Bethlehem, PA 18015-3172.

August 1992

Final Report

Prepared as subcontract for
CONSOL INC.

Research and Development
Under United States Department of Energy
Contract No. DE-AC22-89PC89883

TABLE OF CONTENTS

	Page
1. Executive summary	2
2. Introduction	3
3. Experimental section	5
4. Results and discussion	9
5. Conclusions	29
6. Recommendations	31
7. References	32
8. Appendix 1	
9. Appendix 2	

EXECUTIVE SUMMARY

Californium Plasma Desorption Mass Spectrometry (PDMS) has been used to analyze heavy distillation residues obtained from direct coal liquefaction processes. The characteristics of the ^{252}Cf -PDMS technique for the analysis of these non-polar materials were determined, especially the efficiency with which molecules of different chemical type are ionized and detected. The molecular weight distributions of several THF soluble portions of non-distillable residual materials ($850^{\circ}\text{F}+$ "resids") obtained from the Wilsonville pilot plant were determined. These data are compared to results obtained by Field Ionization Mass Spectrometry (FIMS) and Gel Permeation Chromatography (GPC). In general, number average molecular weights for all three techniques agreed well. Both GPC and PDMS gave higher weight average molecular weights than FIMS and agreed with each other for samples having weight averages below 2000 amu. The molecular weight distributions for these resids produced under a range of conditions are quite similar. The separation of the resids into chemical classes by Medium Pressure Column Chromatography (MPLC) on silica gel is irreversible. PDMS is a rapid effective method for obtaining molecular weight distributions for direct liquefaction resids.

INTRODUCTION

Determining accurate molecular weight distributions for coal derived materials is a long-standing experimental problem. The materials to be analyzed are usually complex mixtures of molecules covering a very broad molecular weight range and a broad range of chemical types. In this situation, it is very difficult to separate only by molecular size. Association and adsorption complicate all techniques. Detection is also a problem because many detectors are responding differently to different chemical classes. The difficulties in measuring molecular weight distributions are probably less with coal conversion products than with coal extracts or other materials whose structures have not been simplified by removal of heteroatoms during hydrogenation. The range of functional groups has been greatly reduced and the molecular weight range narrowed from that of starting coal. The most convenient approaches to measuring the molecular weight distribution of these materials are Gel Permeation Chromatography and a variety of mass spectrometries.

The use of Plasma Desorption Mass Spectrometry to analyze heavy distillation residues obtained from direct coal liquefaction processes is the subject of this work. Field Ionization and Field Desorption Mass Spectrometry have been applied to the analysis of coal liquefaction products.¹⁻⁸ ^{252}Cf -PDMS, a different kind of mass spectrometry,⁹⁻¹⁴ has been incompletely explored for the analysis of coal products.^{15, 16}

The ^{252}Cf plasma desorption technique utilizes energetic fission fragments from the decay of ^{252}Cf to volatilize and ionize a solid sample. The ionization source is typically a 5-15 μCi ^{252}Cf sample sandwiched between two thin sheets of nickel foil. To obtain a mass spectrum, a sample is dissolved in an appropriate solvent and the solution is deposited (often electrosprayed) onto an 0.8 cm diameter circular foil disk made of aluminized poly(ethylene terephthalate) (Mylar disk).

^{252}Cf -PDMS is capable of producing mass spectra primarily consisting of molecular ions from a wide variety of compounds, including amino acids,^{9,17} glycolipids,¹⁸ peptides,¹⁹ proteins,⁹ nucleotides,²⁰ and other natural products.^{21,22} Geoporphyrins,²³ fatty acids,²⁴⁻²⁶ polynuclear aromatic hydrocarbons,²⁷ polyethers²⁸ and other synthetic polymers²⁹⁻³⁵ have been analyzed by PDMS. Recently, PDMS was applied to ionic coordination compounds³⁶ and crown ether - metal complexes.³⁷

Gel Permeation Chromatography (GPC), originally designed for polymer analysis,^{38,39} has been used to determine the molecular weight distributions of coal and crude oil extracts.⁴⁰⁻⁵⁰ The limits of the method and lack of calibration standards for coal derived materials are well known.⁴¹ When analyses are performed using the same columns, solvent and experimental conditions, the relative average molecular weights (M_n and M_w) values can be satisfactorily compared.

EXPERIMENTAL SECTION

Materials. Twenty five THF soluble portions of solid non-distillable residuals (850°F+ "resids") obtained from the Wilsonville pilot plant during direct liquefaction of different coals were the subject of this study. They are brittle, pitch-like materials, supplied as -60 mesh brown powders. Despite different coal feeds and processing conditions, all the samples show similarities. Table IV and Table V summarize physico-chemical parameters of five selected resids. A complete list is supplied in Appendix 1.

Plasma Desorption Mass Spectrometry. Mass spectra were obtained using a Bio-Ion 20 commercial time-of-flight mass spectrometer (Applied Biosystems Inc., Foster City, CA) equipped with a PDP-11 microcomputer data acquisition system (DAS). The instrument has 13 $\mu\text{Ci } ^{252}\text{Cf}$ source and a short 15 cm flight tube. We used a positive 10kV acceleration voltage and the time resolution was set to 1ns/channel. Data collection for each spectrum was terminated when 10^6 primary ion events were acquired. Using H^+ and Na^+ as calibrants, the mass accuracy of the instrument is 0.1 - 0.2% of the measured mass. The mass resolution (M/dM) is typically below 500. With the time-of-flight technique, the theoretical mass range is not limited by the instrument. The practical limit is set by sample to be analyzed.

The simplest sample preparation technique for PDMS is to apply a droplet of a sample solution directly onto a support disk. In some cases the electrospray technique produces better spectra.⁵¹ Resid

samples were dissolved in THF (10 mg/mL) and 40 μ L of each solution was electrosprayed onto aluminized Mylar or nitrocellulose coated aluminized Mylar disks using the Bio-Ion electrospray apparatus. Thin homogenous coverages were obtained. Aluminized Mylar and nitrocellulose coated aluminized Mylar disks were obtained from Applied Biosystems Inc. and used without modification.

We developed a software package that can be used on any IBM compatible PC to calculate number average (M_n) and weight average (M_w) molecular weights using data imported from the Bio-Ion 20 PDP-11 computer. In addition, this software package allows us to subtract the background spectrum which comes from the Mylar film. The software package supplied with the spectrometer (BIOION Data Acquisition System) adds counts from the surrounding channels to enhance the signal-to-noise ratio. This is undesirable for the determination of molecular weight distributions and has been removed from our data analysis.

Gel Permeation Chromatography. The molecular weight distributions of five selected THF soluble resins (#7, #13, #16, #19 and #22 provided by CONSOL Inc.) dissolved in pyridine have been measured by a computer interfaced GPC with a mass sensitive detector. The components of the instrument were all commercially available. It consists of a Waters Liquid Chromatograph (Model ALL 201) equipped with a Rainin loop injector and four μ -styragel columns ($10^4 + 10^3 + 500 + 100 \text{ \AA}$). The mass detector (Applied Chromatography Systems Ltd. Model 750/14) works by nebulizing the liquid stream emerging from the column and then passing this uniform distribution of droplets down a heated tube in a flow of dry

nitrogen, evaporating the solvent. The resulting solid passes a light scattering detector whose output is directly proportional to the mass of solid material passing in front of it. Between the mass detector and the columns is a digital thermal pulse flow meter. The outputs from the mass sensitive detector and the flow meter are directed to a Zenith Model 158 microcomputer, the former through a 12 bit resolution A to D converter (Data Translation Model DT 2805). The programs for data collection and manipulation were written in Asyst (McMillan Software Co.). The instrument was calibrated as previously described,⁴⁵ with commercially available polystyrene standards (Polymer Laboratories Ltd., UK). HPLC grade pyridine was used as the eluting solvent with a flow rate of 0.96-1.00 mL/min. 50 μ L of each sample with concentration of 10 mg/mL was loaded through the 100 μ L loop of the injector valve. Data for each run were collected for 60 minutes.

Medium Pressure Liquid Chromatography (MPLC) was used to separate the THF soluble portions of resids into the following compound classes: oils (hexane solubles), asphaltenes (benzene soluble/hexane insoluble) and preasphaltenes (pyridine soluble/benzene insoluble). The chromatography system used for these separations consists of a Kontes Flex column (2.5 x 20 cm) equipped with a flow adapter, teflon tubing, an FMI (Fluid Metering Inc.) Lab Pump Model RPSY with 1/4" piston, and an ISCO Model 1220 fraction collector. Silica gel (Merck Grade 60, 230-400 mesh, 60 Å) and HPLC grade solvents hexane, benzene and pyridine (Aldrich) were the stationary phase and eluents. 30 g of silica gel was dispersed in 80 mL of hexane and this slurry was put into the column. To pack

the stationary phase, 500 mL of hexane was pumped through the column at a flow rate of ca. 6-8 mL/min. 700-800 mg of the resid samples were dissolved in 2 mL of THF and deposited carefully on the top of the column. Elution was made with sequential 250 mL amounts of hexane, benzene and pyridine (flow rate of 6-8 mL/min). Three different colored fractions, one from each solvent, were collected. Solvents were removed using a rotary evaporator and aspirator vacuum, and residues were vacuum oven dried. At least 98.6% of all samples was recovered.

Gas Chromatography. A Hewlett Packard 5880 A gas chromatograph equipped with FID detector, split injection port and an intermediate phase polarity Supelco SPB-20 capillary column (15 m long, 0.25 mm ID, 0.25 μ m film thickness) was used for the qualitative comparison of the original resids and samples prepared by remixing chromatographically separated fractions (recreated "originals"). Samples dissolved in THF were injected using the following conditions: 1) carrier gas and flow rate: He, 10mL/min; 2) oven temperature: 100-250°C programmed at 10°C/min; 3) injection port temperature: 250°C; 4) detector temperature: 250°C; 5) split ratio: 100:1.

Vapor Pressure Osmometry and Ebulliometry. The time which could be spent on this project (6 months) was not sufficient for these approaches to be explored.

RESULTS AND DISCUSSION

Twenty five THF soluble samples of solid 850°F+ materials ("resids") obtained from the Wilsonville pilot plant during direct liquefaction of different coals were analyzed by ^{252}Cf - Plasma Desorption Mass Spectrometry. Molecular weight distribution curves were obtained and number average molecular weights (M_n) and weight average molecular weights (M_w) were calculated from these curves. All of the molecular weight distribution curves are contained in Appendix 2. These data are compared to results obtained on the same samples by Malhotra and McMillen using Field Ionization Mass Spectrometry (see Table I).⁸

The optimum PDMS conditions were established using resid #7. The amount of material deposited on the Mylar disk, the type of support, the addition of NaCl to enhance the spectrum intensity, the accelerating voltage, and the number of counts per spectrum were varied.

Disks were coated by electrospray using 40 μL of THF solutions of the analyte (resid #7) having concentrations of 10 $\mu\text{g}/\mu\text{L}$ and 20 $\mu\text{g}/\mu\text{L}$ respectively. The spectra show only very small differences in the intensity of the peaks. A pair of spectra are shown in Fig. 1a and 1b.

As is known from the literature, several matrix materials improve the molecular ion yield compared to direct desorption from a metal foil.^{52, 53} The most commonly used matrix is nitrocellulose. Solutions of resid #7 were electrosprayed onto Mylar and onto nitrocellulose coated Mylar disks. Mass spectra of the analyzed

Figure 1. PDMS Spectra of Resid #7 : with 10 $\mu\text{g}/\mu\text{L}$ (a) and 20 $\mu\text{g}/\mu\text{L}$ (b) concentration, electrosprayed on uncoated Mylar (c) and nitrocellulose coated Mylar (d), with (e) and without addition of NaCl (f)

Figure 1. PDMS Spectra of Resid #7 : with 10 $\mu\text{g}/\mu\text{L}$ (a) and 20 $\mu\text{g}/\mu\text{L}$ (b) concentration, electrosprayed on uncoated Mylar (c) and nitrocellulose coated Mylar (d), with (e) and without addition of NaCl.(f)

resid obtained using nitrocellulose coated Mylar did not show any significant improvement in ion intensities compared to uncoated Mylar, as shown by the spectra in Fig. 1c and 1d.

When polymers are applied directly to targets, they often give poor peak shapes and low responses. Addition of sodium chloride to the polymer solution prior to electrospraying increases the number of sodium attachments, enhancing the overall response.^{31,54} This approach was tried with resid #7. Unfortunately, mass spectra with and without NaCl (Figure 1e and 1f) were almost identical. However, the presence of sodium chloride improves the instrument calibration because the signal produced by trace amounts of Na⁺ is used to calibrate the mass spectrum.

Increasing the acceleration voltage from +10kV to +15kV gave a peak intensity enhancement of about 25%. A similar enhancement was observed when the acquisition was increased fourfold.

Negative ion PDMS spectra of resid #7 recorded at -10kV, showed poor peak shapes and a response about 80% lower than the corresponding positive ion spectrum.

On the basis of the above observations, we chose the following routine operation conditions:

- nitrocellulose coated aluminized Mylar disks as sample holders
- 40 μ L (10mg/mL in THF) samples with a few crystals of NaCl
- acceleration voltage +10kV
- acquisition of 10^6 counts (time ~ 13 min.)

Figure 2 shows the plasma desorption mass spectra of Mylar film (a) and of resid #7 (b) in the range between 1 and 5000 m/z. The

Figure 2. PDMS Spectra of the Mylar Background (a) and of Resid #7 (b).

Gaussian shape of the curve is characteristic of PDMS spectra of recycle resids and coal extracts. These mass spectra were sent via KERMIT communication software to a Zenith 386 20MHz PC computer and converted from binary to a format readable by Statgraphics by our "home made" software package (called CFINT). Statgraphics was used to calculate the number average and weight average molecular weights. In addition, CFINT allows the subtraction of data files making it possible to subtract the background which comes from Mylar from a resid spectrum. Statgraphics was also used to smooth by simple moving average (five points on either side of target) and to plot the molecular weight distribution curves. Figure 3 shows the software converted spectrum of resid #7 which includes the Mylar background (a) and of resid #7 with the Mylar background subtracted (b).

The following equations were used to calculate number average and weight average molecular weights from the PDMS molecular weight distribution curves, where N_i = i-th ion intensity and M_i = i-th ion mass:^{55, 56}

$$M_n = \frac{\sum_i N_i M_i}{\sum_i N_i}$$

$$M_w = \frac{\sum_i N_i M_i^2}{\sum_i N_i M_i}$$

Figure 3. Software Converted PDMS Spectrum of Resid #7 which Includes the Mylar Background (a) and of Resid #7 with the Mylar Background Subtracted (b).

Table I. Number Average and Weight Average Molecular Weights
Obtained from Field Ionization Mass Spectrometry
and Plasma Desorption Mass Spectrometry.

Resid #	FIMS			PDMS		
	M_n	M_w	M_w/M_n	M_n	M_w	M_w/M_n
1	600	710	1.2	590	1420	2.4
2	600	710	1.2	580	1390	2.4
3	600	680	1.1	610	1380	2.3
4	620	700	1.1	610	1360	2.2
5	580	660	1.1	610	1360	2.2
6	600	700	1.2	590	1400	2.4
7	620	730	1.2	600	1360	2.3
8	600	720	1.2	590	1440	2.4
9	620	710	1.2	590	1350	2.3
10	610	710	1.2	600	1320	2.2
11	600	700	1.2	610	1370	2.3
12	580	690	1.2	570	1330	2.3
13	570	680	1.2	570	1340	2.4
14	570	680	1.2	570	1360	2.4
15	610	700	1.2	600	1330	2.2
16	590	690	1.2	590	1340	2.3
17	610	710	1.2	610	1220	2.0
18	- ^a)	-	-	610	1280	2.1
19	-	-	-	580	1300	2.2
20	-	-	-	590	1270	2.2
21	-	-	-	620	1350	2.2
22	-	-	-	600	1460	2.4
23	-	-	-	620	1350	2.2
24	-	-	-	590	1240	2.1
25	-	-	-	590	1350	2.3

-^a) not available

In Table I, PDMS results are compared with those obtained from FIMS.⁸ The PDMS M_n values are essentially identical to those from FIMS. PDMS M_w values however, are about twice the field ionization results. Careful analysis and comparison of the corresponding PDMS and FIMS mass spectra show similarities in the mass range of 100 - 1200 m/z. Below 100 m/z the PDMS spectra are disturbed by remnants of peaks from the aluminized Mylar disks (mainly aluminum oxide cluster ions from the film).⁵⁷ This is due to imperfect subtraction of these intense peaks. There are significant differences between the results of these two techniques above 1200 amu. The FIMS spectra do not show any peaks with molecular weights higher than 1200 - 1300 m/z (Figure 4). The PDMS molecular weight distribution does not reach the base line until 2000 - 2500 m/z. PDMS is detecting a significant population of higher mass material that does not appear in FIMS spectra. Perhaps the field ionization technique is not able to efficiently volatilize high boiling, high molecular weight species leading to lower M_w values. Alternatively, the PDMS desorption process may lead to condensation reactions giving rise to new high molecular weight species.^{24,27} The origin of the high molecular weight "tail" requires further investigation.

Next, the PDMS results were compared with those obtained using Gel Permeation Chromatography. Several analyses of commercially available polystyrene samples of different molecular weight were performed to confirm reliability of our Gel Permeation Chromatography system. The data in Table II show generally fair to good agreement with the reported polystyrene molecular weights.

Exceptional is the case of polystyrene of MW 90,000. The GPC results are much lower than expected. The data demonstrate that the system can be safely used up to 15,000 amu. All the recycle oil samples contained material of molecular weight lower than 3500. Polystyrene has not been considered to be an adequate standard for coal-derived materials because of differences in molecular shape and functionality between coal products and polystyrene. It has not proved to be an adequate standard for coal extracts. The problems with polystyrene standards increase with the molecular weight of the materials in question. The resids which are being studied here are of relatively low molecular weight and have had most of their heteroatom content removed. Both of these factors should improve their fit to the polystyrene standard. The improvement is such that polystyrene seems to be an adequate standard.

The following formulas were used to calculate molecular weights from the GPC curves, where h_i is the GPC curve height at the i -th volume increment and M_i the molecular weight of the species eluted at the i -th retention volume:^{55, 56}

$$M_n = \frac{\sum_i h_i}{\sum_i (h_i/M_i)}$$

$$M_v = \frac{\sum_i h_i M_i}{\sum_i h_i}$$

In plasma desorption mass spectrometry, non-polar polymers, especially polystyrene, give very low responses and/or poor peak

shapes. We were able to obtain satisfactory PDMS data only for polystyrene of MW 580. Polystyrenes with higher molecular weights gave no peaks in the expected range, even in the presence of alkali metal cations,⁵⁸ but did give peaks in the "fingerprint" region between 0 - 200 m/z.^{59,60}

**Table II. Number Average and Weight Average Molecular Weights
Obtained from Gel Permeation Chromatography and
Plasma Desorption Mass Spectrometry.**

Sample	GPC			PDMS		
	M _n	M _w	M _w /M _n	M _n	M _w	M _w /M _n
Polystyrene ^{a)}						
MW. 580	470	570	1.2	500	590	1.2
Polystyrene						
MW. 1240	900	1140	1.3	-	-	-
Polystyrene						
MW. 2350	1900	2240	1.2	-	-	-
Polystyrene						
MW. 3600	3020	3420	1.1	-	-	-
Polystyrene						
MW. 15000	6950	15050	2.2	-	-	-
Polystyrene						
MW. 90000	26600	28280	1.1	-	-	-
Resid#7	600	1930	3.2	600	1370	2.3
Resid#13	570	2050	3.6	570	1340	2.4
Resid#16	610	1840	3.0	590	1340	2.3
Resid#19	500	1430	2.9	580	1300	2.2
Resid#22	700	2160	3.1	600	1460	2.4

^{a)} Polystyrene standards. Their given molecular weights are weight averages.

M_n and M_w values of the five resids (#7, #13, #16, #19 and #22), selected for chromatographic separation are also collected in Table II. Results obtained from GPC are compared with those from PDMS. GPC M_n values are in similar to those from PDMS and also from FIMS (Table I). GPC M_w values are always higher than the corresponding PDMS results. There are three possible explanations for this phenomenon. 1) The integral of GPC molecular weight distribution curve is very sensitive to small amounts of high molecular weight analytes. The slope of the detector response is very steep and the analysis weights this pattern of the curve very heavily in the calculation of M_w . The presence of very small amounts of high molecular weight material may give rise to the high GPC M_w values. The results will be very sensitive to experimental errors in the high molecular weight part of the elution curve. 2) The recycle oils are fragmenting in PDMS. 3) The less polar polymeric materials in the resids give very low PDMS responses or no peaks at all. PDMS may not be detecting all of the sample.

We cannot chose one of these three possibilities. The good agreement between two mass spectrometric techniques and GPC in measuring of M_n is gratifying. If number average molecular weights are desired, any of the three techniques can be satisfactorily used.

A central question for the use of PDMS is the possible variable response of the technique to different chemical classes. Will a C_{10} aliphatic compound behave similarly to a C_{10} aromatic component? To address this issue, we separated several resids into chemical classes and studied them individually. Our initial plan was to sum the spectra of the individual fractions weighted by their relative

amounts and compare the resulting spectrum with that of the unseparated resid. This will reveal any differences in ionization or desorption efficiencies. As it turned out, the chromatographic separation altered the samples so much that there was no point in re-adding the spectra.

Medium Pressure Liquid Chromatography was used to separate five carefully selected recycle oils samples into the following categories: oils (hexane solubles), asphaltenes (benzene soluble/hexane insoluble) and preasphaltenes (pyridine soluble/benzene insoluble). The following fractions were obtained: yellow/orange oils (hexane), brownish/red waxes (benzene) and black solids (pyridine). Yields of the corresponding fractions are presented in Table III.

Table III. Composition of Five Recycle Oils (mg) Based on MPLC Separations.

Sample	Hexane Sol. Fr. ^{a)}	Benzene Sol. Fr.	Pyridine Sol. Fr.	Total yield (%)
#7 (730)	270	230	220	98.6
#13 (700)	210	250	230	98.6
#16 (800)	310	250	230	98.8
#19 (780)	260	290	220	98.7
#22 (820)	260	250	300	98.8

^{a)} Soluble Fractions

Table IV. Origin of the Analyzed Samples.

Resid	Coal Feed	Source/Conditions
#7	Illinois No.6	Catalytic/Catalytic
#13	Texas Lignite	Thermal/Catalytic
#16	Pittsburgh No.8	Catalytic/Catalytic
#19	Wyodak	Thermal/Catalytic; H/L ^{a)}
#22	Wyodak	Catalytic/Thermal; L/H ^{a)}

^{a)} H/L=High/Low; L/H=Low/High (First Stage/Second Stage Reactor Temperature)

Figure 4. FIMS Spectrum of Resid #7.

Table V. Analysis of the Soluble Portion of the
Distillation Resids.

Weight %	Res.#7	Res.#13	Res.#16	Res.#19	Res.#22
C	88.75	89.39	90.54	90.90	89.46
H	8.15	7.12	6.74	6.32	6.69
N	0.66	1.23	0.91	1.11	1.13
S	0.14	0.09	0.39	0.03	0.05
O	2.30	2.17	1.42	1.64	2.67

Proton Dist.(%)

Cond. Aromatics	16.7	22.4	26.1	32.2	22.5
Uncond. Aromatics	4.4	4.3	5.4	5.1	5.1
Cyclic Alpha	17.9	19.2	18.9	18.1	16.8
Alkyl Alpha	9.4	9.5	9.4	9.2	9.3
Cyclic Beta	18.6	15.9	14.8	13.6	14.4
Alkyl Beta	20.4	18.5	14.6	13.9	21.2
Gamma	12.5	10.3	10.8	7.8	10.8
Phenolic -OH Conc.	0.50	0.71	0.69	0.67	0.89

Table VI. Number Average and Weight Average Molecular Weights

Obtained from Gel Permeation Chromatography and
Plasma Desorption Mass Spectrometry.

Resid #	GPC			PDMS		
	M_n	M_w	M_w/M_n	M_n	M_w	M_w/M_n
7	600	1930	3.2	600	1370	2.3
7H ^{a)}	210	410	2.0	250	390	1.6
7B ^{b)}	360	610	1.7	330	550	1.7
7P ^{c)}	1330	3410	2.6	790	1720	2.2
7HBP ^{d)}	560	2190	3.9	520	1840	3.5
13	570	2050	3.6	570	1340	2.4
13H	170	480	2.8	160	430	2.7
13B	330	550	1.7	320	530	1.7
13P	960	2400	2.5	710	1770	2.5
13HBP	400	1640	4.1	420	1650	3.9
16	610	1840	3.0	590	1340	2.3
16H	150	290	1.9	150	290	1.9
16B	350	630	1.8	350	570	1.6
16P	990	2330	2.4	760	1820	2.4
16HBP	510	1650	3.2	520	1650	3.2
19	500	1430	2.9	580	1300	2.2
19H	120	330	2.8	140	360	2.6
19B	260	450	1.7	260	450	1.7
19P	630	1430	2.3	720	1500	2.1
19HBP	310	940	3.0	340	990	2.9
22	700	2160	3.1	600	1460	2.4
22H	170	480	2.8	210	480	2.3
22B	310	620	2.0	320	650	2.0
22P	1120	2950	2.6	750	1700	2.3
22HBP	570	2370	4.2	620	2070	3.3

^{a)}H - hexane soluble fraction; ^{b)}B - benzene soluble fraction;

^{c)}P - pyridine soluble fraction ; ^{d)}HBP - remixed fractions

Studies comparing the original resid with the resid reconstituted by mixing the separated fractions show differences between them (see Table VI). The chromatographic separations made permanent changes in the structure of these recycle oils. PDMS results are generally similar to GPC data, especially for oils and asphaltenes. Preasphaltenes give higher average molecular weights in GPC than in PDMS.

Gas chromatographic analyses of the five selected original resids showed one broad peak with a retention time of 28.7 minutes. Hexane and benzene solubles gave one sharp peak at 24.9 min. Pyridine solubles did not elute within 60 minutes at 250°C. The fractions were remixed to recreate the "original" material. This remixed "original" gave one peak at 24.9 min, significantly different from the virgin original material. This rough test indicates that the liquid chromatographic separations made some permanent changes in the structure of original resids. Structural data on chromatographically separated resids should be used cautiously.

²⁵²Cf-PDMS and GPC results for the five fractionated resids are collected in Table VI, Figures 5 (a-d) and 6 (a-b). Analysis of remixed fractions after four weeks standing did not show any significant changes despite the fact that a little precipitation was observed. In all cases, the remixed fractions have a lower molecular weight distribution (M_n values) than the original. There are two possible explanations: 1) disruption of intermolecular non-covalent association, 2) covalent bond cleavage. If non-covalent associations

Figure 5. Software Converted PDMS Spectra of Oils (a), Asphaltenes (b), Preasphaltenes (c) and Remixed Fractions (d) Compared to the Original Resid #7.

Figure 6. GPC Molecular Weight Distribution of Hexane, Benzene and Pyridine Fractions (a), and Remixed Fractions (b) Compared to the Original Resid #7.

were being disrupted, they should reform with time. There is no evidence for this. It seems likely that some chemistry is occurring on the silica gel, though we do not have conclusive proof of it.

As can be seen in Table VI, molecular weights of Resid #19 are much lower than the corresponding fractions of the other samples. This sample has the highest percentage of condensed aromatics and is low in sulphur and beta and gamma protons (Table V). For this sample PDMS and GPC M_n and M_w values are in overall good agreement. Resids #7 and #22 contain relatively low amounts of condensed aromatics, large amounts of cyclic and alkyl beta and gamma protons, and the highest percentage of oxygen. These resids have much higher molecular weights, especially for the pyridine soluble and remixed fractions. Comparison of PDMS molecular weight distributions to the GPC and FIMS shows that number average molecular weights generally agree well. Both GPC and PDMS give higher weight average molecular weights than does FIMS. For hexane and benzene solubles and remixed fractions, both techniques agree well for weight averages below 2000 amu.

GPC M_w values of the original resids were always higher than the corresponding PDMS results. After chromatographic separation, this is the case only for the pyridine soluble fractions (preasphaltenes). Like dissolves like and non-polar materials dissolve in the polystyrene column packing more than do polar molecules. If a non-polar standard is used, polar molecules, being relatively insoluble, will elute faster and report a higher molecular weight than is real. This may be the origin of the PDMS-GPC differences for the polars.

Both the pyridine soluble and the original resid samples give smooth PDMS molecular weight distributions with no individual peaks standing out. The hexane and benzene soluble fractions show sharp, intense peaks at m/z 208, 224, 254, 266, 282, 392 etc. These peaks are also present in the spectra of remixed fractions as seen in Figure 7 (a-b). A series of prominent peaks between 240 and 340 Daltons were also observed in the FIMS data and assigned to benzo-perylene derivatives.⁸ We cannot distinguish between two possible explanations. 1) Chromatographic separations change the recycle oils in a way which makes their individual components more accessible for PDMS analysis. This could be by irreversible dissociation or bond cleavages. 2) The chemical generation of new molecules by reaction on the silica gel.

CONCLUSIONS

1. ^{252}Cf -PDMS is easy to operate, fast and less expensive than most other mass spectrometric techniques and is suitable for quantitative measurements of the molecular weight distributions of some coal conversion products.

2. Comparison of PDMS molecular weight distributions to the GPC and FIMS shows that, in general, number average molecular weights agree well. Both GPC and PDMS give higher weight average molecular weights than does FIMS.

3. In order to realize the full potential of PDMS for analytical determinations of low molecular weight species and/or

Figure 7. PDMS Spectra of Original Resid #7 (a) and the Remixed Fractions (b).

fragment ion studies, the CFINT conversion/subtraction utility appears to be an alternative to eliminate the majority of background interfering peaks.

RECOMMENDATIONS

Further studies of the applications of PDMS to coal derived materials are recommended, especially with the goal of extending the technique of higher molecular weights.

Research to establish the origin of the high molecular weight "tail" in the PDMS spectra is recommended.

Study of the changes in resids caused by chromatography on silica gel is urgently needed.

The application of PDMS to the determination of molecular weight distributions of coal derived "resids" is recommended.

Acknowledgment. We wish to thank Dr. Patrick Wernett for writing the CFINT software and Dr. Osamu Yamada for writing the software used with GPC experiments, and William Anderson for his instrumental advice and expertise.

REFERENCES

- (1) St. John, G.A.; Buttrill, S.E.; Anbar, M. *Organic Chemistry of Coal*; Larsen, J.W., Ed., ACS Symposium Ser., No. 71, pp. 223-239.
- (2) Solomon, P.R.; Hamblen, D.G.; Best P.E. *DOE Quarterly Reports*, Contract No. DE-AC21-81FE05122, 1981.
- (3) Solomon, P.R.; Hamblen, D.G. *Chemistry of Coal Conversion* (Schlosberg R.H., Ed.); Plenum Press, New York, 1985, pp. 128-129.
- (4) Aczel, T.; Laramee, J.; Hansen, G.J. *Proceedings of the 30th Annual Conference on Mass Spectrometry and Allied Topics*, 1982, pp. 808-809.
- (5) Aczel, T.; Dennis, L.W.; Reynolds, S.D. *Proceedings of the 35th Annual Conference on Mass Spectrometry and Allied Topics*, 1987, pp. 1066-1067.
- (6) Larsen, B.S.; Fenselau, C.C.; Whitehurst, D.D.; Angelini, M.M. *Anal. Chem.* 1986, 58, 1088-1091.
- (7) Rechsteiner, C.E.; Attoe, T.H.; Boduszynski, M.M. *Proceedings of the 33rd Annual Conference on Mass Spectrometry and Allied Topics*, 1985, pp. 937-938.
- (8) Malhotra, R.; McMillen, D.F. *Characterization of Coal Liquids by Field Ionization Mass Spectrometry*, DOE Final Report, Contract No. DE-AC22-89PC89883, January 1992.
- (9) Macfarlane, R.D.; Torgeson, D.F. *Science* 1976, 191, 920-925.
- (10) Macfarlane, R.D. *Anal. Chem.* 1983, 55, 1247A-1264A.

- (11) Cotter, R.J. *Anal. Chem.* **1988**, 60, 781A-793A.
- (12) Campana, J.E. *Anal. Instrum.* **1987**, 16, 1-14.
- (13) Macfarlane, R.D.; Hill, J.C.; Jacobs, D.L. *Anal. Instrum.* **1987**, 16, 51-69.
- (14) Kamensky, I.; Craig, A.G. *Anal. Instrum.* **1987**, 16, 71-91.
- (15) Lytle, J.M.; Tingey, G.L.; Macfarlane, R.D. *Anal. Chem.* **1982**, 54, 1881-1883.
- (16) Zingaro, R.A.; Macfarlane, R.D.; Garcia, J.M.; Vindiola, A.G.; Zoeller, J.H. *Chemistry of Coal Liquefaction*, ACS Symposium Ser., Vol. 29, No. 5, 1984, pp. 22-30.
- (17) Bondarenko, P.V.; Zubarev, R.A.; Knysh, A.N.; Rozynov, B.V. *Org. Mass Spectrom.* **1991**, 26, 765-769.
- (18) Jardine, I.; Scanlan, G.; McNeil, M.; Brennan, P.J.; Lindhart, R.J. *Proceedings of the 35th Annual Conference on Mass Spectrometry and Allied Topics*, 1988, pp. 1289-1290.
- (19) Alai, M.; Demirev, P.; Fenselau, C.; Cotter R.J. *Anal. Chem.* **1986**, 58, 1303-1307.
- (20) Scanlan, G.; Benson, L.; Tsarbopoulos, A.; Jardine, I. *Proceedings of the 36th Annual Conference on Mass Spectrometry and Allied Topics*, 1987, pp. 80-81.
- (21) Chait, B.T. *Int. J. Mass Spectrom. Ion Processes* **1989**, 92, 297-329.
- (22) Hunt, J.E.; Michalski, T.J.; Katz J.J. *Int. J. Mass Spectrom. Ion Phys.* **1983**, 53, 335-336.
- (23) Wood, K.V.; Bonham, C.C.; Chou, M.M. *Energy Fuels* **1990**, 4, 747-748.
- (24) Zingaro, R.A.; Vindiola, A.G.; Zoeller, J.H. *Int. J. Mass*

- Spectrom. Ion Phys.* **1983**, *53*, 349-352.
- (25) van Veelen, P.A.; Tjaden, U.R.; van der Greef, J. *Int. J. Mass Spectrom. Ion Processes* **1991**, *110*, 93-101.
- (26) Bolbach, G.; Viari, A.; Galera, R.; Brunot, A.; Blais, J.C. *Int. J. Mass Spectrom. Ion Processes* **1992**, *112*, 93-100.
- (27) Zoeller, J.H.; Zingaro, R.A.; Macfarlane, R.D. *Int. J. Mass Spectrom. Ion Processes* **1987**, *77*, 21-30.
- (28) Chait, B.T.; Shpungin, J.; Field, F.H. *Int. J. Mass Spectrom. Ion Processes* **1984**, *58*, 121-137.
- (29) Jordan, E.A.; Macfarlane, R.D.; Martin, C.R.; McNeal, C.J. *Int. J. Mass Spectrom. Ion Phys.* **1983**, *53*, 345-348.
- (30) Macfarlane, R.D.; McNeal, C.J.; Martin, C.R. *Anal. Chem.* **1986**, *58*, 1091-1097.
- (31) Gehrig, C.C.; Wood, K.V. *Proceedings of the 38th ASMS Conference on Mass Spectrometry and Allied Topics*, **1990**, pp. 255-256.
- (32) Feld, H.; Leute, A.; Zurmuhlen, R.; Benninghoven, A. *Anal. Chem.* **1991**, *63*, 903-910.
- (33) Quinones, L.; Schweikert, E.A. *J. Vac. Sci. Technol. (A)* **1988**, *6*, 946-949.
- (34) Park, M.A.; Cox, B.D.; Schweikert, E.A. *J. Vac. Sci. Technol. (A)* **1991**, *9*, 1300-1306.
- (35) Lacey, M.P.; Keough, T. *Anal. Chem.* **1991**, *63*, 1482-1487.
- (36) van Veelen, P.A.; Tjaden, U.R.; van der Greef, J.; Hage, R. *Org. Mass Spectrom.* **1991**, *26*, 74-80.
- (37) Malhotra, N.; Roepstorff, P.; Hansen, T.; Becher, J. *J. Am. Chem. Soc.* **1990**, *112*, 3709-3710.

- (38) Collins, M.J.; Zeronian, S.H.; Marshall, M.L. *J. Macromol. Sci.-Chem.* 1991, 28A, 775-792.
- (39) Sanayei, R.A.; O'driscoll, K.F. *J. Macromol. Sci.-Chem.* 1991, 28A, 987-1000.
- (40) Wong, J.L. *Coal Science and Chemistry*, Volborth, A., Ed. Elsevier, Amsterdam, 1987, pp 461-471.
- (41) Bartle, K.D.; Mills, D.G.; Mulligan, M.J.; Ameachina, J.C.; Taylor, N. *Anal. Chem.* 1986, 58, 2403.
- (42) Bartle, K.D.; Mulligan, M.J.; Taylor, N.; Martin, T.G.; Snape, C.E. *Fuel* 1984, 63, 1556-1559.
- (43) Larsen, J.W.; Choudry, P. *J. Org. Chem.* 1979, 44, 2856-2859.
- (44) Larsen, J.W.; Mohammadi, M.; Yiginsu, J.; Kovac, J. *Geochim. Cosmochim. Acta* 1984, 48, 135-141.
- (45) Larsen, J.W.; Wei, Y.C. *Energy Fuels* 1988, 2, 344-350.
- (46) Buchanan, D.H.; Warfel, L.C.; Bailey, S.; Lucas, D. *Energy Fuels* 1988, 2, 32-36.
- (47) Himmel, M.E.; Tatsumoto, K.; Grohmann, K.; Johnson, D.K.; Chum, H.L. *J. Chromatog.* 1990, 498, 93-104.
- (48) Khan, Z.H.; Hussain, K. *Fuel* 1989, 68, 1998-1202.
- (49) Reynolds, J.G.; Biggs, W.R. *Acc. Chem. Res.* 1988, 21, 326-332.
- (50) Evans, N.; Haley, T.M.; Mulligan, J.; Thomas, K.M. *Fuel* 1986, 65, 694-703.
- (51) McNeal, C.J.; Macfarlane, R.D.; Thurston, R.J. *Anal. Chem.* 1979, 51, 2036.
- (52) Macfarlane, R.D. *Acc. Chem. Res.* 1982, 15, 268.
- (53) Jonsson, G.P.; Hedin, A.B.; Hakansson, P.L.; Sungqvist, B.U.; Save, G.B.S.; Nielsen, P.F.; Roepstorff, P.;

- Johansson, K.E.; Kamensky, L.; Lindberg, M.S.L. *Anal. Chem.* **1986**, *58*, 1084-1087.
- (54) Blais, J.C.; Viari, A.; Cole, R.B.; Tabet, J.C. *Int. J. Mass Spectrom. Ion Processes* **1990**, *98*, 155-166.
- (55) Yon, W.W.; Kirkland, J.J.; Bly, D.D. *Modern Size-Exclusion Liquid Chromatography*, John Willey & Son, 1979, pp. 8-9.
- (56) Billmeyer, F.W. *Textbook of Polymer Science*, 2nd ed., John Willey & Son, 1971, p. 78.
- (57) Juvet, R.S.; Allmaier G.D.; Schmidt, E.R. *Anal. Chim. Acta* **1990**, *241*, 241-248.
- (58) Demirev, P.; Fenyo, D.; Sundqvist, B.U.R. *Org. Mass Spectrom.* **1991**, *26*, 471-475.
- (59) Park, M.A., Gibson, K.A.; Quinones, L.; Schweikert, E.A. *Science* **1990**, *248*, 988-990.
- (60) Park, M.A.; Schweikert, E.A.; da Silveira, E.F. *J. Phys. Chem.* **1992**, *96*, 3206-3210.

APPENDIX 1

Samples

²⁵²Cf-PDMS ANALYSES

<u>Ref #</u>	<u>Coal Feed</u>	<u>Source/Conditions</u>	<u>Comments</u>
1	Illinois No.6	W; Run 257 G; C/C; L/H	Interstage
2	Illinois No.6	W; Run 257 F; C/C; H/L	Interstage
3	Illinois No.6	W; Run 250; T/C	Second Stage Product
4	Illinois No.6	W; Run 250; T/C	Recycle
5	Illinois No.6	W; Run 250; T/C	Interstage
6	Illinois No.6	W; Run 257; C/C	Second Stage Product
7	Illinois No.6	W; Run 257; C/C	Recycle
8	Illinois No.6	W; Run 257; C/C	Interstage
9	Wyodak	W; Run 251-II; T/C	Second Stage Product
10	Wyodak	W; Run 251-II; T/C	Recycle
11	Wyodak	W; Run 251-II; T/C	Interstage
12	Texas Lignite	W; Run 255 B; T/C	Second Stage Product
13	Texas Lignite	W; Run 255 B; T/C	Recycle
14	Texas Lignite	W; Run 255 B; T/C	Interstage
15	Pittsburgh No.8	W; Run 259; C/C	Second Stage Product
16	Pittsburgh No.8	W; Run 259; C/C	Recycle
17	Pittsburgh No.8	W; Run 259; C/C	Interstage
18	Wyodak	W; Run 260 C; T/C; H/L	Second Stage Product
19	Wyodak	W; Run 260 C; T/C; H/L	Recycle
20	Wyodak	W; Run 260 C; T/C; H/L	Interstage
21	Wyodak	W; Run 260 E; C/T; L/H	Second Stage Product
22	Wyodak	W; Run 260 E; C/T; L/H	Recycle
23	Wyodak	W; Run 260 E; C/T; L/H	Interstage
24	Illinois No.6	W; Run 261 D; C/C; L/H	Recycle
25	Illinois No.6	W; Run 261 E; C/C; L/H	Recycle

Chromatographic Separation/²⁵²Cf-PDMS, GPC

<u>Ref #</u>	<u>Coal Feed</u>	<u>Source/Conditions</u>	<u>Comments</u>
7	Illinois No.6	W; Run 257; C/C	Recycle
13	Texas Lignite	W; Run 255 B; T/C	Recycle
16	Pittsburgh No.8	W; Run 259; C/C	Recycle
19	Wyodak	W; Run 260 C; T/C; H/L	Recycle
22	Wyodak	W; Run 260 E; C/T; L/H	Recycle

 Note: All samples are THF-soluble distillation resids; C/C=Catalytic/Catalytic;
 T/C=Thermal/Catalytic; H/L=High/Low (First Stage/Second Stage) Reactor Temperature;
 L/H=Low/High (First Stage/Second Stage) Reactor Temperature; W=Wilsonville

ANALYSIS OF THF SOLUBLE PORTION
OF THE DISTILLATION RESID

Ref. No. 1

Plant: Wilsonville
Run Number: 257 G
Sample Designator: R-1235
Sampling Point: Interstage
Feed Coal: Illinois No.6
 Burning Star #2 Mine

Ultimate (Wt%, as Det.)

Carbon:	88.11
Hydrogen:	7.76
Nitrogen:	0.87
Sulfur:	0.45
Oxygen (diff.):	2.81

Proton Distribution (%)

Condensed Aromatics	15.4
Uncondensed Aromatics	4.5
Cyclic Alpha	17.7
Alkyl Alpha	9.8
Cyclic Beta	18.9
Alkyl Beta	21.9
Gamma	11.8

Phenolic -OH Concentration (meq/g): 0.81

Phenolic Peak Location (cm⁻¹): 3295

ANALYSIS OF THF SOLUBLE PORTION
OF THE DISTILLATION RESID

Ref. No. 2

Plant: Wilsonville
Run Number: 257 F
Sample Designator: R-1235
Sampling Point: Interstage
Feed Coal: Illinois No.6
Burning Star #2 Mine

Ultimate (Wt%, as Det.)

Carbon:	89.45
Hydrogen:	7.96
Nitrogen:	0.77
Sulfur:	0.23
Oxygen (diff.)	1.59

Proton Distribution (%)

Condensed Aromatics	16.4
Uncondensed Aromatics	3.2
Cyclic Alpha	18.4
Alkyl Alpha	8.9
Cyclic Beta	20.5
Alkyl Beta	20.8
Gamma	11.7

Phenolic -OH Concentration (meq/g): 0.59

Phenolic Peak Location (cm^{-1}): 3296

ANALYSIS OF THF SOLUBLE PORTION
OF THE DISTILLATION RESID

Ref. No. 3

Plant: Wilsonville
Run Number: 250
Sample Designator: V-1067
Sampling Point: Second Stage Product
Feed Coal: Illinois No.6
Burning Star #2 Mine

Ultimate (Wt%, as Det.)

Carbon:	89.91
Hydrogen:	7.14
Nitrogen:	1.02
Sulfur:	0.27
Oxygen (diff.):	1.66

Proton Distribution (%)

Condensed Aromatics	20.4
Uncondensed Aromatics	5.6
Cyclic Alpha	18.7
Alkyl Alpha	9.8
Cyclic Beta	17.2
Alkyl Beta	17.2
Gamma	11.2

Phenolic -OH Concentration (meq/g): 0.55

Phenolic Peak Location (cm^{-1}): 3297

ANALYSIS OF THF SOLUBLE PORTION
OF THE DISTILLATION RESID

Ref. No. 4

Plant: Wilsonville

Run Number: 250

Sample Designator: V131B

Sampling Point: Recycle Stream

Feed Coal: Illinois No. 6

Burning Star No. 2 Mine

Ultimate (Wt%, as Det.)

Carbon:	89.18
Hydrogen:	7.39
Nitrogen:	0.89
Sulfur:	0.25
Oxygen (diff.)	

Proton Distribution (%)

Condensed Aromatics	20.9
Uncondensed Aromatics	4.4
Cyclic Alpha	18.6
Alkyl Alpha	9.8
Cyclic Beta	16.8
Alkyl Beta	17.6
Gamma	11.8

Phenolic -OH Concentration (meq/g): 0.74

Phenolic Peak Location (cm⁻¹):

ANALYSIS OF THF SOLUBLE PORTION
OF THE DISTILLATION RESID

Ref. No. 5

Plant: Wilsonville
Run Number: 250
Sample Designator: R1236
Sampling Point: Interstage
Feed Coal: Illinois No.6
Burning Star No.2

Ultimate (Wt%, as Det.)

Carbon:	89.38
Hydrogen:	6.51
Nitrogen:	1.16
Sulfur:	0.50
Oxygen (diff.)	

Proton Distribution (%)

Condensed Aromatics	30.8
Uncondensed Aromatics	5.2
Cyclic Alpha	19.0
Alkyl Alpha	10.3
Cyclic Beta	13.0
Alkyl Beta	12.9
Gamma	8.8

Phenolic -OH Concentration (meq/g): 1.07

Phenolic Peak Location (cm⁻¹):

ANALYSIS OF THF SOLUBLE PORTION
OF THE DISTILLATION RESID

Ref. No. 6

Plant: Wilsonville
Run Number: 257
Sample Designator: V1067
Sampling Point: 2nd Stage Product
Feed Coal: Illinois No.6
Burning Star #2

Ultimate (Wt%, as Det.)
Carbon: 88.32
Hydrogen: 8.16
Nitrogen: 0.65
Sulfur: 0.15
Oxygen (diff.) 2.72

Proton Distribution (%)
Condensed Aromatics 17.7
Uncondensed Aromatics 3.0
Cyclic Alpha 18.9
Alkyl Alpha 9.3
Cyclic Beta 19.5
Alkyl Beta 19.6
Gamma 11.9

Phenolic -OH Concentration (meq/g): 0.57
Phenolic Peak Location (cm⁻¹): 3301

ANALYSIS OF THF SOLUBLE PORTION
OF THE DISTILLATION RESID

Ref. No. 7

Plant: Wilsonville
Run Number: 257
Sample Designator: V131B
Sampling Point: Recycle Stream
Feed Coal: Illinois No. 6
 Burning Star No.2

Ultimate (Wt%, as Det.)
Carbon: 88.75
Hydrogen: 8.15
Nitrogen: 0.66
Sulfur: 0.14
Oxygen (diff.) 2.30

Proton Distribution (%)
Condensed Aromatics 16.7
Uncondensed Aromatics 4.4
Cyclic Alpha 17.9
Alkyl Alpha 9.4
Cyclic Beta 18.6
Alkyl Beta 20.4
Gamma 12.5

Phenolic -OH Concentration (meq/g): 0.50
Phenolic Peak Location (cm⁻¹): 3302

ANALYSIS OF THF SOLUBLE PORTION
OF THE DISTILLATION RESID

Ref. No. 8

Plant: Wilsonville
Run Number: 257
Sample Designator: R1235
Sampling Point: Interstage
Feed Coal: Illinois No. 6
Burning Star No.2 Mine

Ultimate (Wt%, as Det.)
Carbon: 88.41
Hydrogen: 8.04
Nitrogen: 0.86
Sulfur: 0.26
Oxygen (diff.) 2.43

Proton Distribution (%)
Condensed Aromatics 17.8
Uncondensed Aromatics 4.9
Cyclic Alpha 18.6
Alkyl Alpha 9.2
Cyclic Beta 18.1
Alkyl Beta 19.7
Gamma 11.7

Phenolic -OH Concentration (meq/g): 0.68

Phenolic Peak Location (cm⁻¹): 3300

ANALYSIS OF THF SOLUBLE PORTION
OF THE DISTILLATION RESID

Ref. No. 9

Plant: Wilsonville
Run Number: 251-II
Sample Designator: V-1067
Sampling Point: Second Stage Product
Feed Coal: Wyodak Seam
Clovis Point Mine

Ultimate (Wt%, as Det.)

Carbon:	89.88
Hydrogen:	6.75
Nitrogen:	1.22
Sulfur:	0.05
Oxygen (diff.):	2.10

Proton Distribution (%)

Condensed Aromatics	26.5
Uncondensed Aromatics	3.5
Cyclic Alpha	21.3
Alkyl Alpha	9.6
Cyclic Beta	15.1
Alkyl Beta	16.3
Gamma	7.7

Phenolic -OH Concentration (meq/g): 0.81

Phenolic Peak Location (cm⁻¹): 3298

ANALYSIS OF THE SOLUBLE PORTION
OF THE DISTILLATION RESID

. Ref. No. 10

Plant: Wilsonville
Run Number: 251-II
Sample Designator: V-131B
Sampling Point: Recycle
Feed Coal: Wyodak Seam
Clovis Point Mine

Ultimate (Wt%, as Det.)

Carbon:	89.72
Hydrogen:	7.08
Nitrogen:	1.04
Sulfur:	0.06
Oxygen (diff.)	2.10

Proton Distribution (%)

Condensed Aromatics	23.4
Uncondensed Aromatics	3.6
Cyclic Alpha	19.9
Alkyl Alpha	8.7
Cyclic Beta	15.9
Alkyl Beta	19.0
Gamma	9.5

Phenolic -OH Concentration (meq/g): 0.75

Phenolic Peak Location (cm^{-1}): 3297

ANALYSIS OF THF SOLUBLE PORTION
OF THE DISTILLATION RESID

Ref. No. 11

Plant: Wilsonville
Run Number: 251-II
Sample Designator: R-1258
Sampling Point: Interstage
Feed Coal: Wyodak Seam
Clovis Point Mine

Ultimate (Wt%, as Det.)

Carbon:	89.38
Hydrogen:	6.13
Nitrogen:	1.33
Sulfur:	0.15
Oxygen (diff.)	3.01

Proton Distribution (%)

Condensed Aromatics	31.9
Uncondensed Aromatics	5.1
Cyclic Alpha	18.1
Alkyl Alpha	9.4
Cyclic Beta	12.6
Alkyl Beta	14.3
Gamma	8.5

Phenolic -OH Concentration (meq/g): 1.17

Phenolic Peak Location (cm^{-1}): 3292

ANALYSIS OF THF SOLUBLE PORTION
OF THE DISTILLATION RESID

Ref. No. 12

Plant: Wilsonville
Run Number: 255 B
Sample Designator: V-1067
Sampling Point: Second Stage Product
Feed Coal: Texas Lignite
Martin Lake

Ultimate (Wt%, as Det.)

Carbon:	89.40
Hydrogen:	7.00
Nitrogen:	1.28
Sulfur:	0.13
Oxygen (diff.):	2.19

Proton Distribution (%)

Condensed Aromatics	23.1
Uncondensed Aromatics	3.7
Cyclic Alpha	20.8
Alkyl Alpha	9.5
Cyclic Beta	16.2
Alkyl Beta	17.9
Gamma	8.7

Phenolic -OH Concentration (meq/g): 0.77

Phenolic Peak Location (cm^{-1}): 3298

ANALYSIS OF THF SOLUBLE PORTION
OF THE DISTILLATION RESID

Ref. No. 13

Plant: Wilsonville
Run Number: 255 B
Sample Designator: V-131B
Sampling Point: Recycle
Feed Coal: Texas Lignite
 Martin Lake

Ultimate (Wt%, as Det.)

Carbon:	89.39
Hydrogen:	7.12
Nitrogen:	1.23
Sulfur:	0.09
Oxygen (diff.):	2.17

Proton Distribution (%)

Condensed Aromatics	22.4
Uncondensed Aromatics	4.3
Cyclic Alpha	19.2
Alkyl Alpha	9.5
Cyclic Beta	15.9
Alkyl Beta	18.5
Gamma	10.3

Phenolic -OH Concentration (meq/g): 0.71

Phenolic Peak Location (cm⁻¹): 3298

ANALYSIS OF THF SOLUBLE PORTION
OF THE DISTILLATION RESID

Ref. No. 14

Plant: Wilsonville
Run Number: 255 B
Sample Designator: R-1235
Sampling Point: Interstage
Feed Coal: Texas Lignite
 Martin Lake

Ultimate (Wt%, as Det.)

Carbon:	89.06
Hydrogen:	6.70
Nitrogen:	1.37
Sulfur:	0.19
Oxygen (diff.):	2.68

Proton Distribution (%)

Condensed Aromatics	26.7
Uncondensed Aromatics	5.4
Cyclic Alpha	19.1
Alkyl Alpha	9.7
Cyclic Beta	13.8
Alkyl Beta	16.4
Gamma	8.8

Phenolic -OH Concentration (meq/g): 1.03

Phenolic Peak Location (cm^{-1}): 3295

ANALYSIS OF THF SOLUBLE PORTION
OF THE DISTILLATION RESID

Ref. No. 15

Plant: Wilsonville
Run Number: 259
Sample Designator: V1067
Sampling Point: 2nd Stage Product
Feed Coal: Pittsburgh Seam
Ireland Mine

Ultimate (Wt%, as Det.)

Carbon:	89.80
Hydrogen:	6.80
Nitrogen:	1.00
Sulfur:	0.41
Oxygen (diff.):	1.99

Proton Distribution (%)

Condensed Aromatics	28.6
Uncondensed Aromatics	3.6
Cyclic Alpha	21.7
Alkyl Alpha	9.1
Cyclic Beta	14.8
Alkyl Beta	13.5
Gamma	8.7

Phenolic -OH Concentration (meq/g): 0.70

Phenolic Peak Location (cm^{-1}): 3296

ANALYSIS OF THF SOLUBLE PORTION
OF THE DISTILLATION RESID

Ref. No. 16

Plant: Wilsonville
Run Number: 259
Sample Designator: V131B
Sampling Point: Recycle Stream
Feed Coal: Pittsburgh Seam
Ireland Mine

Ultimate (Wt%, as Det.)

Carbon:	90.54
Hydrogen:	6.74
Nitrogen:	0.91
Sulfur:	0.39
Oxygen (diff.)	1.42

Proton Distribution (%)

Condensed Aromatics	26.1
Uncondensed Aromatics	5.4
Cyclic Alpha	18.9
Alkyl Alpha	9.4
Cyclic Beta	14.8
Alkyl Beta	14.6
Gamma	10.8

Phenolic -OH Concentration (meq/g): 0.69

Phenolic Peak Location (cm⁻¹): 3296

ANALYSIS OF THF SOLUBLE PORTION
OF THE DISTILLATION RESID

Ref. No. 17

Plant: Wilsonville
Run Number: 259
Sample Designator: R1235
Sampling Point: Interstage
Feed Coal: Pittsburgh Seam
Ireland Mine

Ultimate (Wt%, as Det.)

Carbon:	89.79
Hydrogen:	6.49
Nitrogen:	1.06
Sulfur:	0.63
Oxygen (diff.):	2.03

Proton Distribution (%)

Condensed Aromatics	30.7
Uncondensed Aromatics	2.6
Cyclic Alpha	20.9
Alkyl Alpha	10.2
Cyclic Beta	13.8
Alkyl Beta	13.4
Gamma	8.4

Phenolic -OH Concentration (meq/g): 0.92

Phenolic Peak Location (cm⁻¹): 3295

ANALYSIS OF THF SOLUBLE PORTION
OF THE DISTILLATION RESID

Ref. No. 18

Plant: Wilsonville
Run Number: 260 C
Sample Designator: V-1067
Sampling Point: Second Stage Product
Feed Coal: Wyodak and Anderson Seam
Black Thunder Mine

Ultimate (Wt%, as Det.)
Carbon: 89.74
Hydrogen: 6.46
Nitrogen: 1.12
Sulfur: 0.04
Oxygen (diff.) 2.64

Proton Distribution (%)
Condensed Aromatics 30.5
Uncondensed Aromatics 4.7
Cyclic Alpha 20.8
Alkyl Alpha 9.4
Cyclic Beta 13.8
Alkyl Beta 13.0
Gamma 7.8

Phenolic -OH Concentration (meq/g): 0.61

Phenolic Peak Location (cm^{-1}): 3294

ANALYSIS OF THF SOLUBLE PORTION
OF THE DISTILLATION RESID

Ref. No. 19

Plant: Wilsonville
Run Number: 260 C
Sample Designator: V-131B
Sampling Point: Recycle
Feed Coal: Wyodak and Anderson Seam
Black Thunder Mine

Ultimate (Wt%, as Det.)

Carbon:	90.90
Hydrogen:	6.32
Nitrogen:	1.11
Sulfur:	0.03
Oxygen (diff.):	1.64

Proton Distribution (%)

Condensed Aromatics	32.2
Uncondensed Aromatics	5.1
Cyclic Alpha	18.1
Alkyl Alpha	9.2
Cyclic Beta	13.6
Alkyl Beta	13.9
Gamma	7.8

Phenolic -OH Concentration (meq/g): 0.67

Phenolic Peak Location (cm⁻¹): 3296

ANALYSIS OF THF SOLUBLE PORTION
OF THE DISTILLATION RESID

Ref. No. 20

Plant: Wilsonville
Run Number: 260 C
Sample Designator: R-1235
Sampling Point: Interstage
Feed Coal: Wyodak and Anderson Seam
Black Thunder Mine

Ultimate (Wt%, as Det.)

Carbon:	90.41
Hydrogen:	6.25
Nitrogen:	1.14
Sulfur:	0.04
Oxygen (diff.):	2.16

Proton Distribution (%)

Condensed Aromatics	32.8
Uncondensed Aromatics	4.6
Cyclic Alpha	20.0
Alkyl Alpha	9.4
Cyclic Beta	12.7
Alkyl Beta	14.5
Gamma	6.0

Phenolic -OH Concentration (meq/g): 0.97

Phenolic Peak Location (cm^{-1}): 3295

ANALYSIS OF THE SOLUBLE PORTION
OF THE DISTILLATION RESID

Ref. No. 21

Plant: Wilsonville
Run Number: 260 E
Sample Designator: V-1067
Sampling Point: Second Stage Product
Feed Coal: Wyodak and Anderson Seam
Black Thunder Mine

Ultimate (Wt%, as Det.)

Carbon:	89.24
Hydrogen:	6.92
Nitrogen:	1.19
Sulfur:	0.07
Oxygen (diff.):	2.58

Proton Distribution (%)

Condensed Aromatics	24.8
Uncondensed Aromatics	4.8
Cyclic Alpha	18.0
Alkyl Alpha	9.1
Cyclic Beta	14.4
Alkyl Beta	19.5
Gamma	9.5

Phenolic -OH Concentration (meq/g): 0.93

Phenolic Peak Location (cm⁻¹): 3296

ANALYSIS OF THF SOLUBLE PORTION
OF THE DISTILLATION RESID

Ref. No. 22

Plant: Wilsonville
Run Number: 260 E
Sample Designator: V-131B
Sampling Point: Recycle
Feed Coal: Wyodak and Anderson Seam
Black Thunder Mine

Ultimate (Wt%, as Det.)

Carbon:	89.46
Hydrogen:	6.59
Nitrogen:	1.13
Sulfur:	0.05
Oxygen (diff.):	2.67

Proton Distribution (%)

Condensed Aromatics	22.5
Uncondensed Aromatics	5.1
Cyclic Alpha	16.8
Alkyl Alpha	9.3
Cyclic Beta	14.4
Alkyl Beta	21.2
Gamma	10.8

Phenolic -OH Concentration (meq/g): 0.89

Phenolic Peak Location (cm⁻¹): 3297

ANALYSIS OF THF SOLUBLE PORTION
OF THE DISTILLATION RESID

Ref. No. 23

Plant: Wilsonville
Run Number: 260 E
Sample Designator: R-1235
Sampling Point: Interstage
Feed Coal: Wyodak and Anderson Seam
Black Thunder Mine

Ultimate (Wt%, as Det.)

Carbon:	89.54
Hydrogen:	6.96
Nitrogen:	1.13
Sulfur:	0.05
Oxygen (diff.)	2.32

Proton Distribution (%)

Condensed Aromatics	23.3
Uncondensed Aromatics	4.0
Cyclic Alpha	18.2
Alkyl Alpha	9.1
Cyclic Beta	15.2
Alkyl Beta	20.4
Gamma	9.8

Phenolic -OH Concentration (meq/g): 0.96

Phenolic Peak Location (cm^{-1}): 3296

ANALYSIS OF THF SOLUBLE PORTION
OF THE DISTILLATION RESID

Ref. No. 24

Plant: Wilsonville
Run Number: 261 D
Sample Designator: V-131B
Sampling Point: Recycle
Feed Coal: Illinois No.6
Burning Star #2 Mine

Ultimate (Wt%, as Det.)
Carbon: 90.19
Hydrogen: 5.93
Nitrogen: 1.61
Sulfur: 0.23
Oxygen (diff.) 2.04

Proton Distribution (%)
Condensed Aromatics 25.3
Uncondensed Aromatics 4.1
Cyclic Alpha 18.3
Alkyl Alpha 9.2
Cyclic Beta 16.1
Alkyl Beta 17.1
Gamma 9.9

Phenolic -OH Concentration (meq/g): 0.77

Phenolic Peak Location (cm⁻¹): 3297

ANALYSIS OF THF SOLUBLE PORTION
OF THE DISTILLATION RESID

Ref. No. 25

Plant: Wilsonville
Run Number: 261 E
Sample Designator: V-131B
Sampling Point: Recycle
Feed Coal: Illinois No.6
Burning Star #2 Mine

Ultimate (Wt%, as Det.)

Carbon:	90.52
Hydrogen:	5.22
Nitrogen:	1.25
Sulfur:	0.28
Oxygen (diff.)	2.73

Proton Distribution (%)

Condensed Aromatics	33.1
Uncondensed Aromatics	4.6
Cyclic Alpha	19.4
Alkyl Alpha	9.5
Cyclic Beta	13.3
Alkyl Beta	12.5
Gamma	7.7

Phenolic -OH Concentration (meq/g): 0.83

Phenolic Peak Location (cm⁻¹): 3296

APPENDIX 2

Plot of RESID1.COUNTS vs RESID1.mass

1B

Plot of RESID2.COUNTS vs RESID2.mass

2B

Plot of RESID3.COUNTS vs RESID3.mass

3B

Plot of RESID4.COUNTS vs RESID4.mass

4B

Plot of RESID5.COUNTS vs RESID5.mass

5B

Plot of RESID6.COUNTS vs RESID6.mass

6B

Plot of RESID7.COUNTS vs RESID7.mass

7B

Plot of RESID8.COUNTS vs RESID8.mass

8B

Plot of RESID9.COUNTS vs RESID9.mass

9B

Plot of RESID10.COUNTS vs RESID10.mass

10B

Plot of RESID11.COUNTS vs RESID11.mass

11B

Plot of RESID12.COUNTS vs RESID12.mass

12B

Plot of RESID13.COUNTS vs RESID13.mass

13B

Plot of RESID14.COUNTS vs RESID14.mass

14B

Plot of RESID15.COUNTS vs RESID15.mass

15B

Plot of RESID16.COUNTS vs RESID16.mass

16B

Plot of RESID17.COUNTS vs RESID17.mass

17B

Plot of RESID18.COUNTS vs RESID18.mass

Plot of RESID19.COUNTS vs RESID19.mass

19B

Plot of RESID20.COUNTS vs RESID20.mass

20B

Plot of RESID21.COUNTS vs RESID21.mass

21B

Plot of RESID22.COUNTS vs RESID22.mass

22B

Plot of RESID23.COUNTS vs RESID23.mass

23B

Plot of RESID24.COUNTS vs RESID24.mass

24B

Plot of CONSOL25.COUNTS vs CONSOL25.mass

25B

END

DATE
FILMED

4 / 7 / 93