DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency Thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DISCLAIMER

Portions of this document may be illegible in electronic image products. Images are produced from the best available original document.

UCRL--50021-80-Vol.2

DE83 002430

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

Volume 2

1980 Laser Program Annual Report

Scientific Editors: Lamar W. Coleman

William F. Krupke

Publication Editor: John R. Strack

MS date: June 1981

NOTICE

PORTIONS OF THIS REPORT ARE ILLEGIBLE. It has been reproduced from the best available copy to permit the broadest possible availability.

Lawrence Livermore National Laboratory
University of California • Livermore, California • 94550

Available from: National Technical Information Service • U.S. Department of Commerce
5285 Port Royal Road • Springfield, VA 22161 • \$19.00 per copy • (Microfiche \$3.50)

MASTER

EXB
DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

Contents

Volume 1

Section 1—Laser Program Overview

Introduction	1-1
Summary of Major Activities	1-4
Lead Laboratory Program for 1.06- μ m and Shorter-Wavelength Target Experiments	1-11
Program Resources	1-13
Program Facilities	1-14

Section 2—Solid State Laser Systems and Technology

Introduction	2-1
Operating Systems	2-2
Novette	2-38
Nova	2-53
Research and Development	2-184
Basic Research	2-304

Volume 2

Section 3—Target Design

Introduction	3-1
Ignition and Scientific Breakeven	3-3
A Calculational Comparison of D-T, Neon, and Argon Implosions	3-11
Charged-Particle Fusion	3-17
Plasma Theory	3-24
LASNEX and Atomic Theory	3-71

Section 4—Target Fabrication

Introduction	4-1
Glass-Sphere Development and Production	4-3
Coatings and Layers	4-9
Double-Shell Technology	4-29
Characterization and Analysis	4-34
Cryogenic Systems Development	4-50
Target Factory Studies	4-60
Fusion Target Development Facility (FTDF)	4-63

Section 5—Diagnostics

Introduction	5-1
Three-Channel Soft X-ray Streak Spectrometer	5-2
Pinhole Imaging Streak Camera	5-5
Multilayer X-ray Interference Mirrors for an Improved SXRSC Spectrometer	5-9
Target Spatial Definition for Low-Energy X-ray Spectral Measurements	5-10
Production and Characterization of Soft X Rays for Diagnostics Calibrations	5-13
Hyper-Filter-Fluorescer Spectrometer for X Rays Above 120 keV	5-15
Streak-Camera Recording of Simultaneous Optical and X-ray Signals	5-19
A 662-keV X-ray Calibration Facility	5-21
22 $\times$ Microscope Streak Camera	5-23
Microchannel Plate Reflector	5-31
Fuel Density Measurements Using Bromine L X-ray Line Imaging and Stark Profiles	5-32
Fabrication of High-Aspect-Ratio Microstructures for High-Energy X-ray and Particle-Imaging Applications	5-34
Point Imaging with X Rays (PIX)	5-36
Evaluation of X-ray Backlighting Diagnostics for Nova and Novette Laser Targets	5-38
Direct Fuel (ρR) Measurements by Neutron Activation	5-40

Debris Collection and Background Measurements with Bromine-Filled Targets	5-45
Automated Radiation-Chemistry Diagnostic System	5-49
Stimulated Brillouin and Raman Side-Scattering Diagnostics System	5-52
4 ω Optical Probing	5-53
Analysis of Bremsstrahlung Emission as an Electron-Density Diagnostic	5-56
CCD Applications in ICF Diagnostics	5-62
Automated Streak-Camera Calibration Using a CCD Readout	5-67
Optically Driven Semiconductor (Auston) Switch	5-68
A Fast Optically Triggered Silicon Switch for Framing-Camera Applications	5-70
Novette Target Alignment and Viewing Optics (TAV)	5-72
Section 6—Management and Analysis of Experimental Data	
Introduction	6-1
Fusion Experiments Analysis Facility	6-3
Beam Spatial Profile Analysis	6-7
Dante Temporal Unfolds	6-11
Pyroelectric Detector Data Processing	6-15
Raman Spectrograph Data Processing	6-18
Crystal Spectrograph Data Analysis	6-21
CCD Streak-Camera Processing	6-22
Novette Diagnostic-Configuration Data Base and Graphic Presentation	6-28
Target Shot Books and Archiving	6-32
Section 7—Laser Fusion Experiments and Analysis	
Introduction	7-1
Target-Interaction Experiments at 0.53 μm and 0.35 μm	7-2
Analysis and Summary of Wavelength-Scaling Experiments and Comparisons with Simulations	7-22
Stimulated Raman Scattering in Large Plasmas	7-35
Space-Time-Resolved X-ray Measurements from Accelerated Disk Targets	7-44
Backlighter Characterization Experiments	7-53
Angular Distribution of High-Energy X Rays from Shiva-Irradiated Targets	7-65
Ultra-High-Pressure Laser-Driven Shocks in Gold	7-69

Volume 3

Section 8—Advanced Lasers

Introduction	8-1
Pulse Compressor Systems	8-3
Laser Theory and Design Introduction	8-32
Advanced Concepts	8-55
Advances in Atomic and Molecular Physics	8-70

Section 9—Energy and Military Applications

Introduction	9-1
Accomplishments Associated with the HYLIFE Chamber Concept	9-4
A New Liquid Metal Chamber of High Repetition-Rate-Operation: the JADE Chamber	9-91
Ultra-High-Pressure Shock-Wave Experiments	9-99

Section 10—Advanced Isotope Separation

Introduction	10-1
AIS Facilities	10-5
Laser Research and Development	10-17
Atomic-Vapor Physics	10-30
Computational Facilities	10-47
Alternative Applications of Technology	10-51
Planning Methodology	10-58

Section 3 Target Design

Target Design

Contents

Introduction	3-1
Ignition and Scientific Breakeven	3-3
Introduction	3-3
Ignition and SBE at 10 kJ	3-4
Ignition and SBE at 0.1 to 1 MJ	3-5
Ignition vs SBE	3-7
Main Fuel Ignition	3-8
Main Fuel Diagnostics in 0.1- to 1-MJ Ignition and SBE Experiments	3-8
Implosion Diagnostics in 0.1- to 1-MJ Ignition and SBE Experiments	3-9
Coupling Experiments with 0.1- to 1-MJ Drivers	3-10
Summary	3-10
A Calculational Comparison of D-T, Neon, and Argon Implosions	3-11
Introduction	3-11
Physics of Moderate-Density Implosions	3-11
Calculational Parameters	3-12
Comparison of Calculational Results	3-12
Summary	3-16
Charged-Particle Fusion	3-17
Introduction	3-17
Ion-Beam Target Gain for a Range of Beam-Input Parameters	3-17
Transport of Heavy-Ion Beams to the Target	3-19
Plasma Theory	3-24
Introduction	3-24
Laser Plasma Coupling in Reactor-Size Targets	3-25
Heating and Hot-Electron Generation in Underdense Plasmas	3-30
Theory and Simulation of One-Dimensional Raman Forward Scattering	3-34
Heated Electron Distributions from Laser Absorption on Ion Acoustic Turbulence	3-37
Analysis of Short-Pulse Absorption Experiments at 1.06-, 0.53-, and 0.27- μm Laser Wavelengths	3-39
Effect of Supersonic Flow on Density Profiles	3-44
A Model for Stimulated Brillouin Scatter Induced by Nonabsorbed Light	3-48
Stimulated Brillouin Scatter with Broadband Thermal Noise	3-52
Filamentation Growth Rates in Collisional ICF Plasmas	3-56
Implicit Large-Timestep Particle Simulations	3-57
Relevance of Ion-Acoustic Instability to Thermal-Transport Inhibition in Plasmas Produced by Nd Lasers	3-59
Anomalous DC Resistivity Due to Ion Turbulence	3-63
Absorption, Electron Heating, and Electron-Energy Transport Inhibition Due to Ion Turbulence	3-65
Absorption, Electron Heating, and Electron-Energy Transport in Microwave Simulations of P-Polarized Laser Light-Plasma Interactions	3-67

LASNEX and Atomic Theory	3-71
The LASNEX Computer Code—An Overview	3-71
Dynamic Memory Management for LASNEX	3-74
Computer Simulation of Suprathermal Transport for Laser Fusion	3-78
Atomic Physics in Inertial Fusion	3-83
Pressure Ionization	3-83
Two-Temperature Equation of State for Dense Plasmas	3-85
Semiclassical Atoms in Dense Plasmas	3-86

References	3-91
-----------------------------	-------------

Target Design

Introduction

Our target-design program combines the efforts of the plasma, code development, and design groups in

- Developing theories of beam-plasma interaction, implosions, and thermonuclear microexplosions.
- Building plasma and implosion-burn computer codes.
- Using these theoretical and computational tools to design targets and simulate experiments.

During Shiva experiments in 1980, we used laser-driven hohlraum targets to implode deuterium-tritium (D-T) to more than 100 times liquid density and to temperatures higher than 500 eV. These results are in excellent agreement with our preshot theoretical predictions. We have also developed simple theoretical models that correctly predict hohlraum temperatures and scaling of suprathermal electrons, and our theoretical predictions of the importance of Raman processes in targets with sufficiently long plasma-scale lengths were experimentally confirmed.

One of the most significant recent developments in inertial-confinement fusion (ICF) is the experimental confirmation of theoretical predictions of excellent laser-plasma coupling at short wavelengths for both x-ray driven and directly irradiated targets. Our Argus data on disk targets at 2ω are in good agreement with short-wavelength experiments conducted at other laboratories. The Argus 2ω hohlraum experiments show strong suppression of hot electron formation, as compared with 1ω experiments. Theoretical scaling from the preliminary results of Shiva hohlraum experiments predicts that the hot-electron problem will be adequately controlled in both Nova and reactor targets by the use of 3ω light. However, to confirm this scaling, additional experiments are required to measure the high-temperature (hundreds of keV) tail of the suprathermal distribution, since these electrons dominate the preheating of some types of targets at the sizes to be used for Nova and for reactors. Experiments are also required with larger underdense plasmas and with well-diagnosed plasma conditions to confirm our theoretical analysis, which predicts that the hot electrons are predominantly generated by Raman and $2\omega_p$ processes.

The goals of ignition and scientific breakeven (SBE) are theoretically possible with short-wavelength 10-kJ drivers. However, these goals will first be achieved with 0.1- to 1-MJ drivers now under construction (Nova at LLNL and PBFA-II at Sandia National Laboratory in Albuquerque). Ideal target-performance limits must be approached at 10 kJ, but there are significant reserve and

Fig. 3-1

margin for error at 0.1 to 1 MJ. Unfortunately, the feasibility and scale of both ignition and SBE are only weakly coupled with the feasibility and scale of high-gain fusion microexplosions.

To obtain funding for drivers large enough to conduct multimegajoule-scale experiments—which are theoretically predicted to provide gains sufficiently high for civilian and military applications—we must first experimentally demonstrate that the required high gains could be achieved at the multimegajoule size, and we must confirm theoretical estimates of the required reactor-driver wavelength, voltage, energy, power, and efficiency. Because these drivers are so large and expensive, this information must be known before the reactor driver can be designed and constructed.

Consequently, we have devised a scenario of experiments that can be performed with the 0.1- to 1-MJ Nova and PBFA-II drivers to obtain the necessary information. The objectives of these experiments include

- Achievement of central ignition, and determination of the main fuel density, temperature, and mix.
- Diagnosis of the implosion dynamics—including symmetry, fluid instabilities, and preheat—by observation of the inner surfaces of the imploding shells.
- Determination of the laser-plasma coupling at plasma scale lengths relevant to multimegajoule drivers.

We have been analyzing both directly driven and hohlraum ICF targets since the early 1960s. Using our Nd:glass lasers, we first imploded D-T to thermonuclear conditions in electron-driven targets in late 1974 and in hohlraum targets in early 1976.

Implosion symmetry is a central issue for both approaches. Radiation-driven targets have a fuel capsule inside an enclosure, which approximates a hohlraum. The capsule is driven by a nearly uniform flux of soft x-ray radiation, leading to a symmetric implosion. In directly driven targets, a sufficiently symmetric implosion is achieved by use of multiple, overlapped driver beams (each of which is relatively uniform) and by electron-conduction smoothing between the region where the beam is absorbed and the ablation surface. This smoothing is enhanced by increasing both the temperature and the width (relative to the spatial scales of the dominant nonuniformities) of the smoothing region. The width of the smoothing region is increased by use of longer-wavelength laser light (or lower-energy ions) in the early stage of the implosion and by exploding a standoff shell to generate an atmosphere. The laser frequency (and ion energy) may be increased during the implosion to achieve efficient absorption and ablation. Both hohlraum and directly imploded targets suffer an energy penalty to achieve symmetry: on the one hand, by losses to the radiation case; on the other, by losses to the plasma atmosphere.

In 1980, we made important advances in charged-particle target designs, including adaptation of a hohlraum target design to the projected PBFA-II light-ion driver. This target achieves ignition in computer calculations when driven by ≈ 2 MJ of light ions.

For direct implosion, we are pursuing both single- and double-shell capsule designs with low-density outer shells. This low-density feature makes possible high gains without depending on unproven methods of controlling fluid instabilities. Although the double-shell design has a higher calculated gain than the single-shell design, there are serious uncertainties caused by the presence of the high-Z shell (Z = atomic number) surrounding the ignitor. Unstable mixing of this high-Z material into the ignitor D-T and into the main-fuel D-T may make ignition significantly more difficult, thereby degrading the burn efficiency

and target gain. In addition, the ignition threshold of the outer fuel occurs at an uncomfortably large driver energy (≈ 3 MJ). Because of these problems, it is important to pursue both the single- and double-shell designs. However, both of these designs fail to approach their performance potential, largely because central ignition occurs before the main fuel can implode to high densities. Because of driver cost and efficiency constraints, it is important to develop improved target designs with higher gains at lower energies. We are now working on several promising concepts.

Our estimates of fusion-reactor driver requirements and our calculated target gain curves are unchanged from previous years (Fig. 3-1). We expect to achieve the best-estimate levels initially with our single- and double-shell target designs and to then follow a learning curve leading toward the more optimistic levels with advanced target concepts. The best estimate in the figure, which is based on realistic assumptions about implosion instabilities and thermonuclear ignition and burn, assumes efficient beam-target coupling with either ion beams or short-wavelength lasers.

Author: J. H. Nuckolls

Ignition and Scientific Breakeven

Introduction

In this article, we answer the questions

- Can the goals of ignition and SBE be achieved with 10-kJ lasers?
- How much less difficult are these goals at 0.1 to 1 MJ?
- What is the significance of these goals in the overall strategy of inertial confinement fusion?
- What additional implosion, thermonuclear, and coupling experiments must be performed to determine the feasibility and scale of high-gain fusion microexplosions?

Ignition and SBE are theoretically attainable with 10-kJ short-wavelength lasers, provided that the stringent requirements for symmetry, fluid stability, pulse shaping, and frequency shaping can be satisfied. (The threshold of ignition is reached when the deposited fusion energy doubles the D-T reaction rate.) However, these goals will be achieved first with the 0.1- to 1-MJ drivers now being constructed (short-wavelength Nova and, possibly, light-ion PBFA-II); ideal target performance must be achieved for success at 10 kJ, but there is significant reserve and margin for error at 0.1 to 1 MJ. Less time and effort will be required to build the larger drivers than to asymptotically approach the target

performance limits with 10-kJ drivers.

Similarly, because ignition corresponds to a target gain that is substantially less than SBE, ignition may be achieved within a few years after the 0.1- to 1-MJ drivers and target diagnostics become fully operational—much sooner than SBE.

The feasibility and scale of ignition and SBE are only weakly coupled with the same parameters of high-gain fusion microexplosions. (Gains > 100 are required for both civilian and military applications of ICF.) In ignition-scale experiments of 0.1 to 1 MJ, sufficient thermonuclear energy will be deposited in the central region of the D-T to heat a much larger mass of D-T surrounding the central region to thermonuclear temperatures. However, this outer main fuel will not ignite and achieve high target gains because neither its temperature nor its density-thickness product will be great enough. Although SBE involves a higher target gain than ignition, the outer fuel will still not be ignited at the 0.1- to 1-MJ scale; consequently, this additional gain is of secondary importance. Neither the feasibility of high gain nor the required scale and efficiency of the reactor driver will be demonstrated in these ignition and SBE experiments.

Although the main fuel will not achieve high gains in 0.1- to 1-MJ ignition and SBE experiments, it is possible in these experiments to measure the critical main-fuel parameters (density, density times thickness, temperature, and mix) when the central

ignitor explodes. In addition, difficulties related to implosion symmetry, stability, and preheat, which may arise in achieving central ignition and in compressing the main fuel, may be diagnosed and corrected. Laser-plasma coupling can be measured at plasma scale lengths corresponding to high-gain targets designed for multimegajoule-sized drivers. With the results of these experiments, the feasibility of high gains and the required wavelength, voltage, energy, power, and efficiency of the reactor drivers may be predicted with increased confidence and accuracy. This combination of experiments is a key element in the overall strategy of ICF.

There is a second important consequence of the weak coupling between the feasibility and scale of ignition and SBE and of high-gain fusion microexplosions. Even though estimates of the size of the driver that will first achieve ignition and SBE have greatly increased, reactor-driver requirements have not increased. The increase lies not in the estimates of the minimum-sized driver required to achieve ignition and SBE, but, rather, in the estimates of the size of the driver that will first achieve breakeven. Our current estimates of the driver energy necessary to initiate a microimplosion with a gain of 100 are in good agreement with the estimates we published in 1972.¹

Ignition and SBE at 10 kJ

In the early to mid-1970s, scientists at Lebedev, KMSF, Los Alamos, and LLNL published papers that estimated that SBE could be achieved with less than 10 kJ of laser energy.^{1,2} In 1972,¹ we addressed the possibility of degraded laser-plasma coupling—caused by plasma instabilities and electron preheat and decoupling—and proposed a series of remedies: short-wavelength lasers, hollow pellets, high-Z materials, and reduced laser intensities. Additional options were known, but could not be published in 1972: use of directly driven multishell/multilayer targets, and targets with thermal-radiation coupling. Subsequently, these degraded coupling mechanisms have been observed, and these options and remedies have been incorporated into some of our target designs.

Early plans for Shiva included the uniform-illumination and short-wavelength capabilities required to develop the 10-kJ SBE target concepts. However, these capabilities were not developed because of inadequate funds.

A theoretical analysis³ of the gains that may be achieved by laser-driven targets was presented in 1979. In this analysis, the variation of ablation efficiency with laser intensity and the effect of electron thermal transport inhibition are considered. The analysis shows that a gain of 50 can be achieved with 30 kJ of 0.25- μm laser light focused to an intensity of $\sim 2 \times 10^{15} \text{ W/cm}^2$ on a hollow shell (with an aspect ratio of ~ 20). Preliminary experimental measurements of ablation pressure with 1- and 0.25- μm light imply that $2 \times 10^{15} \text{ W/cm}^2$ of 0.25- μm light will couple efficiently to a target.⁴ However, there are two errors in this analysis that bias the results in the conservative direction. First, the internal energy of Fermi degenerate D-T is too large by a factor of $2^{2/3}$ (see Ref. 5). Second, the electron temperature in the ablated material was limited to 9 keV (by limiting the laser intensity) to make the ablative process 10% efficient with implosion velocities of $3 \times 10^7 \text{ cm/s}$. This ablative efficiency was imposed so that very high gains could be achieved in reactor-scale targets. However, for 10-kJ SBE targets, the optimum implosion velocity is greater than $3 \times 10^7 \text{ cm/s}$, and the optimum electron temperature is greater than 9 keV. When these two errors are corrected, the analysis predicts a gain of ~ 10 with 10 kJ of 0.2- μm light—in good agreement with our 1972 estimates.

This more recent theoretical analysis does not discuss the difficult symmetry, fluid-stability, and preheat requirements outlined in our 1972 work. These requirements must be satisfied to approach target performance limits in the real world; a highly symmetrical implosion must be achieved. To limit low- to intermediate-order modes of asymmetry, a large number of laser beams may be used, but these beams must be highly reproducible and carefully controlled. In addition, a combination of laser frequency shaping and low-density atmosphere—or some other means of symmetrizing the absorbed energy (e.g., thermal radiation)—must be used. Extremely well-controlled pulse shaping is

required to stably and isentropically implode a thin shell, without allowing the inside surface to separate excessively from the outside surface, while at the same time driving the central D-T to ignition at the instant the remaining D-T has achieved a sufficiently high density. Flexible pulse shaping and symmetry diagnostics are needed to experimentally iterate to the optimum implosion.

Because the ideal performance must be approached so closely at 10 kJ, a large number of experimental iterations will be required, and the time and effort required is likely to be large. Consequently, it is faster and less costly to build a laser large enough for ignition and SBE to be achieved with a substantially less demanding implosion. Even with 0.1- to 1-MJ drivers, a large number of target experiments will be required to diagnose the implosion symmetry, preheat, and velocity—and other potential problem areas—and to optimize the target performance. Based on our experience with Shiva, ignition may be achieved within a few years after Nova and its target diagnostics become fully operational. Even more time will be required to achieve SBE, which is close to the performance limits of the Nova target designs. Since the target physics scales roughly with the cube root of driver energy, the driver must be on the order of 10 times larger to relax by twofold many of the

critical requirements for implosion, ignition, and burn.

Ignition and SBE at 0.1 to 1 MJ

Two drivers are under construction that should be capable of achieving ignition and SBE if the projected driver parameters are realized. The proposed Nova Nd:glass laser will be capable of focusing several hundred kilojoules (hundreds of terawatts) of frequency doubled or tripled light onto a target on the scale of a few millimetres. The PBFA-II light-ion driver is designed to focus ~ 1 MJ (40 TW) of light ions with temperatures of several thousand electron volts onto a centimetre-scale target. Both of these drivers should be completed by the mid-1980s.

In the USSR, the Angara V multimegajoule relativistic electron-beam machine is being constructed. However, beam-target coupling with these high-energy electrons will be much less efficient than with ions or short-wavelength laser light. Similarly, for the 40-kJ Antares CO₂ laser (in the US), efficient coupling of 10.6- μ m laser light to the target is a critical problem.

One promising directly driven target for both Nova and PBFA-II is the low-density double-shell design we have developed,⁶ as shown in Fig. 3-2. The important feature of this design that distinguishes it from other

Fig. 3-2. Directly irradiated single- and double-shell target designs.

double-shell designs⁷ is the low-density outer shell, which may be made thick enough to withstand fluid instabilities without relying on unproven stabilization mechanisms. At the same time, the required driver power and focused intensity are greatly reduced, and with multimegajoule drivers, there is a capability of very high gain. The central ignitor consists of a small amount of D-T contained in a thick high-Z shell. The main fuel is a hollow frozen layer of D-T supported by the low-density outer shell (this fuel is not ignited by 0.1- to 1-MJ drivers in SBE and ignition experiments).

This 0.1- to 1-MJ double-shell target has several important advantages over the single-shell targets (Fig. 3-2) designed for 10-kJ SBE experiments. The double-shell central ignitor fuel is compressed to 1000 times liquid D-T density. To achieve SBE at 10 kJ, the single-shell fuel must be compressed to a much higher density—10 000 times liquid. Because of the target structure and the greatly reduced compression, pulse shaping is not required for double-shell ignition and SBE experiments, where only the central ignitor is initiated.

Pulse shaping is essential for the 10-kJ single-shell targets. In the double-shell target, the ignitor D-T is contained in a high-Z shell, which strongly inhibits escape of thermal radiation, and the D-T ignites at temperatures of 3 to 4 keV and a density thickness product of $\lesssim 0.2 \text{ g/cm}^2$. (To compensate for such factors as the effects of instabilities and mixing, the double-shell Nova target is designed to implode to twice as high an ignition temperature as calculated by LASNEX for the ideal case, and the burn efficiency is degraded to 70% of the ideal calculations. Low-density single-shell targets probably do not require such large over-design factors.) The corresponding ignition parameters for the single-shell 10-kJ SBE target are significantly more difficult: 8 to 12 keV and 0.5 to 1 g/cm^2 . Because of the relaxed ignition conditions and the velocity multiplication that occurs in the double-shell design when the outer shell collides with the high-Z shell, the velocity to which the outer shell must be driven is nearly twofold smaller than the implosion velocity required by the single-shell 10-kJ SBE target ($2 \times 10^7 \text{ cm/s}$ vs $4 \times 10^7 \text{ cm/s}$, respectively). Consequently, the required laser power and focused

intensity are substantially reduced. The higher-density 10-kJ target has a higher convergence ratio and more severe symmetry requirements. The preheat sensitivity of the 10-kJ target is much greater: the ablator/preheat/fuel layers are thinner, with reduced self-shielding, and the fuel must be isentropically compressed. The single-shell 10-kJ target is degraded by main-fuel preheat (which increases compression entropy), while the double-shell target is degraded by preheat-induced decompression of the high-Z shell as the outer shell is coasting inward to collision.

The single-shell target difficulties are much less severe at the 0.1- to 1-MJ scale than at the 10-kJ scale. For example, 30 times more D-T mass may be imploded with 300 kJ. Consequently, at 10 000 times liquid density, the ρR is approximately $30^{1/3}$ larger, or, at $\rho R \approx 1$, the required compression is $30^{1/2}$ times smaller. The required ignition velocity may be reduced roughly twofold (with a larger ρR , a smaller fraction of the D-T mass can be brought to ignition temperature). Since the target shells are $30^{1/3}$ -fold thicker, there is more self-shielding against electron and x-ray preheat. Single-shell targets are also constructed of relatively thick (thickness/radius $\lesssim 0.1$) low-density materials. Both the single- and double-shell targets are promising candidates for Nova ignition and SBE experiments.

The nominal double-shell target fails to ignite at less than ~ 100 -kJ because compression of its central ignitor is ≈ 1000 times liquid density. Consequently, at less than ~ 100 -kJ, the density-thickness product is not large enough either to contain the D-T alpha particles or to sufficiently inhibit electron thermal conduction. Higher densities may be achieved by making the D-T a hollow, frozen shell in contact with the inner surface of the Au shell. Then, at 25- to 50-kJ, target performance is limited by electron and x-ray preheat because the shells are too thin for effective self-shielding. At 10 kJ, there is a high risk of failure from asymmetries, fluid instabilities, and preheat.

The central ignitor parameters of a double-shell target designed to achieve SBE with Nova⁶ are

- D-T mass, $\sim 4 \mu\text{g}$.
- D-T density, 300 g/cm^3 .
- D-T radius (compressed), $13 \mu\text{m}$.

- ρR , 0.40 g/cm^2 .
- Implosion velocity, $3 \times 10^7 \text{ cm/s}$.
- No-mix temperature (temperature achieved by D-T before significant deceleration of the Au/D-T interface), 3 keV .
- Burn efficiency, 10% .

Ignition vs SBE

For double-shell targets, the threshold in ρR for ignition of D-T is $\sim 0.2 \text{ g/cm}^2$. This threshold is determined by the range of the 3.5-MeV D-T alpha particles in hot D-T, by thermal electron conduction to the cooler boundaries of the hot D-T region, and by the D-T ion-electron coupling time (at D-T ignition temperatures, most of the D-T alpha energy is deposited in the electrons). To ignite D-T at smaller values of ρR , magnetic fields sufficiently large to limit the alpha range and reduce the thermal conduction must be used.

If the driver has energy large enough that the ρR of the ignitor region is $\lesssim 0.4 \text{ g/cm}^2$ —twice the threshold value—and if the uncertainty in the energy of this threshold is much less than a factor of 2, then ignition is much easier to achieve than SBE. On the other hand, if—as for the 10- to 70-kJ case—the target barely exceeds a ρR threshold, or if the location of the threshold is not known to a high enough accuracy, then ignition is not necessarily significantly easier to achieve than SBE. In addition, estimates of the energy required to achieve ignition are reliable, whereas estimates of the SBE energy can easily be in error by a factor of 10. Both the Nova and PBFA-II targets have a ρR of $\approx 0.4 \text{ g/cm}^2$.

The advantages of ignition may be understood as follows. Consider a target for which a fraction, a , of the incident laser energy is transferred by implosion to the D-T thermal energy. If the required ignition temperature is T_i , then the condition for SBE is

$$\epsilon_{\text{TN}} \approx c_p T_i a^{-1} \quad (1)$$

where ϵ_{TN} is the thermonuclear energy per gram generated by the ignited D-T. The condition for ignition is

$$\frac{1}{5} \epsilon'_{\text{TN}} \approx c_p T_i \quad (2)$$

since one-fifth of the thermonuclear energy is carried by the 3.5-MeV alpha particles, which are confined by the D-T. The ratio of the SBE and ignition burn efficiencies, ϵ_{TN} and ϵ'_{TN} , respectively, is

$$\frac{\epsilon_{\text{TN}}}{\epsilon'_{\text{TN}}} \approx \frac{1}{5a} \quad (3)$$

For the double-shell targets, $a \approx 0.01$ for coupling to the central ignitor region. Then, $\epsilon_{\text{TN}} \approx 20 \epsilon'_{\text{TN}}$. Since $T_i \approx 4 \text{ keV}$, the burn efficiency required for SBE is $\sim 10\%$ and that for ignition is $\sim 1\%$.

Alternatively, if the compressed ρR is accurately known, and if the D-T is not significantly contaminated by mixing, then ignition may have equal to approximately one-half the burn efficiency of SBE, and a degradation in energy-coupling efficiency of up to an order of magnitude may be accommodated.

Recall that $\epsilon_{\text{TN}} \sim \rho R \sim \rho^{2/3} M^{1/3} \sim E_{\text{driver}}^{1/3}$ for a given ρ , and gain is approximately

$$\frac{M \epsilon_{\text{TN}}}{E_{\text{driver}}} \sim E_{\text{driver}}^{1/3} \quad (4)$$

For example, if the double-shell Nova SBE target should absorb only one-half as much energy as predicted (or if it should couple only one-half as much to the D-T because of the unstable double-shell collision), then the gain is reduced from 1 to $2^{-4/3}$. (The target mass must be reduced twofold to match the absorbed laser energy, thereby reducing the ρR and D-T burn efficiency by $2^{1/3}$.) To recover this factor of $2^{4/3}$, the laser must be made more than 10 times larger. However, this degraded target exceeds the condition for ignition: a factor of 2 decrease in ρR would be needed to abort ignition, whereas the half-sized target has suffered a ρR decrease of only $2^{1/3}$. Since the target ρR is almost a factor of 2 above threshold, a several-fold error in energy coupling can be tolerated before ignition fails. Consequently, ignition is predicted with significantly higher confidence than SBE. (An important exception occurs if the driver generates barely tolerable levels of suprathreshold preheat. Then, if the target is made smaller, its self-shielding may decrease exponentially.)

What is the additional significance of achieving SBE over ignition? Their scientific values are equal; in both cases, the D-T may ignite and burn efficiently. At the 0.1- to 1-MJ level, neither ignition nor SBE demonstrates either the feasibility of high gains or the scale at which these high gains may be achieved. The thermonuclear yield generated by the central ignitor in either ignition or SBE experiments may be used to fully diagnose the critically important conditions in the outer main fuel. In fact, threshold-of-ignition yields (reaction rate doubled by deposited thermonuclear energy) are sufficient to diagnose the outer main fuel. These conditions will determine the scale at which the main fuel will ignite and what target gain will be achieved. Similar considerations apply to single-shell targets. Ignition-level thermonuclear yields may be used to fully diagnose the D-T fuel.

Main Fuel Ignition

Assume the central ignitor in the Nova-scale double-shell target experiment has a burn efficiency of 10%. The corresponding specific thermonuclear energy is 3×10^{10} J/g. Approximately 20% of this energy is deposited in the D-T or in the inner edge of the Au pusher by the alpha particles. To satisfy fluid stability requirements, the Au pusher mass is ~ 50 times the D-T mass (thickness/radius $\lesssim 0.1$ at beginning of implosion). Consequently, the average specific energy is $\sim 10^8$ J/g, corresponding to a temperature in the Au of ~ 3 keV. If all this energy is converted to kinetic energy by hydrodynamic expansion, then the corresponding velocity is $\sim 5 \times 10^7$ cm/s. Since the Au is compressed to an order-of-magnitude higher density than the outer main D-T fuel, the inner part of this D-T (next to the outer part of the Au) is shocked to a temperature of 5 keV by a free surface moving at 10^8 cm/s and is compressed to density of ~ 100 g/cm³. Neutron heating is much less than shock heating. The outer Au radius is approximately twice that of the ignitor D-T outer radius, and only approximately one-fourth of the 14-MeV energy is lost in an average D-T scatter. Also the ranges of the D and T knockons (from 14-MeV scatters) are much larger than the

thickness of the D-T fuel. Since thermal-radiation losses from the main fuel are not significantly reduced by external shells or by self-absorption, a temperature of 8 to 12 keV is required for effective ignition. The ρR is also marginal. Although the total ρR of the outer fuel is ~ 0.4 g/cm² only about 10% of the outer fuel mass (or ~ 0.2 g/cm²) is shocked to as much as 5 keV. This is because $\gtrsim 10\%$ of the Au explodes with the free-surface velocity, and the total masses of the Au and main fuel are approximately equal.

In a directly driven multimegajoule reactor-scale double-shell target, the ignitor has a ρR of ~ 1 g/cm² and has a 50% burn efficiency. The peak explosion velocity approaches 2×10^8 cm/s. Then, more than 0.5 g/cm² of the main fuel is shocked to more than 10 keV. This temperature and ρR are sufficiently high so that ignition will occur even if there is substantial mixing of low-Z materials. Thermonuclear burn propagates into the remaining ~ 1 g/cm² of the main fuel, generating very high target gains.

At the 0.1- to 1-MJ scale, it is possible that single-shell targets will achieve somewhat higher gains than double-shell targets. The ignitor and fuel regions are not separated by inert material, and the main fuel is more highly compressed. However, for shells with modest aspect ratios, the pulse-shaping requirements are severe. (For ultrathin shells, preheat, implosion symmetry, and fluid instabilities are serious problems.) Since the single-shell implosions are more sensitive, more time and effort will be required to approach performance limits. Even if these moderately higher gains were achieved, neither the feasibility of high gain nor the required scale and efficiency of the reactor driver would be demonstrated by these experiments. However, the fuel conditions could be diagnosed to determine the required scale and efficiency of the reactor driver.

Main Fuel Diagnostics in 0.1- to 1-MJ Ignition and SBE Experiments

Although the main fuel will not ignite and achieve high gains in 0.1- to 1-MJ ignition and SBE experiments, it is possible to measure the critical parameters of the main fuel when

the central region is ignited. Two diagnostic approaches are promising: imaging of the x rays and neutrons, and radiochemistry.

As a result of the central ignitor explosions, the inner part of the outer fuel is shocked to multi-keV temperatures, and the remainder is shocked to ~ 1 keV. Since the amount of high-Z material between the main fuel and ablator is only ~ 0.01 g/cm², the 10-keV bremsstrahlung x-ray tail escapes and may be imaged and spectrally analyzed with a multichannel x-ray pinhole camera. A fuel tracer with a K edge near 10 keV should emit detectable lines (e.g., krypton and bromine at ~ 12 keV). This line radiation might be imaged to determine the extent of mixing.

A neutron pinhole system is under consideration that would be capable of imaging a 14-MeV, 10^{14} neutron source to an accuracy of ~ 10 μ m (see Ref. 8). On the order of 10^{14} to 10^{15} neutrons should be generated in and scattered from the outer fuel, and this fuel has an outer radius of ~ 100 μ m.

Neutron reactions with tracers such as bromine in the outer fuel may be used to determine the main fuel ρR . Shiva experiments have demonstrated that the debris can be collected and transferred to the counter in ~ 1 min and counted with a background of ~ 1 cpm (see Ref. 9). Since the source is $\lesssim 10^{14}$ neutrons, tracers with small neutron cross sections may be used.

With these techniques, it should be possible to determine the boundaries, density, ρR , temperature, and mix of the main fuel at ignition of the central ignitor. The results of these measurements can be used to predict the driver size required to ignite the main fuel, what burn efficiency will result, and, hence, how efficient the driver must be for practical power production. These techniques and arguments apply to both single- and double-shell targets.

Implosion Diagnostics in 0.1- to 1-MJ Ignition and SBE Experiments

The cost of multimegajoule laser and heavy-ion reactor drivers is very high ($\sim \$1$ billion), and the cost increases with increasing energy. Consequently, it is important to achieve a sufficiently high target gain with the smallest

possible driver energy. For example, it is important to realize gain with the KrF laser, whose efficiency is high enough only if the conservative target gain can be achieved. The onset of high target gain occurs at the threshold for main fuel ignition. To achieve high gain close to this threshold, it is necessary to develop a capability for diagnosing and correcting those effects—both anticipated and unanticipated—that may cause the real implosion to deviate significantly from the theoretical calculations. This implosion diagnostic capability will enable us to respond to one likely outcome of the initial main-fuel diagnostic experiments: the implied energy or efficiency requirements may be larger than our estimates. With effective implosion diagnostics, it should be possible to improve the target performance, at least to the conservative set of theoretical predictions, and to determine how much the conservative assumptions used in these calculations may be relaxed.

In the 0.1- to 1-MJ double-shell target, the compressed radius of the D-T in the central ignitor is ~ 13 μ m, and the implosion velocity of the inner Au surface is $\sim 3 \times 10^7$ cm/s. It is necessary to resolve an error equal to approximately one-half the compressed radius, or 7 μ m. The corresponding temporal resolution is $7 \mu\text{m} / 3 \times 10^7 \text{ cm/s} \approx 20$ ps. The initial radius of the outer shell is ~ 1 mm (convergence ratio $\approx 1000 \mu\text{m} / 13 \mu\text{m} \sim 80$). The implosion time is ~ 5 to 10 ns. The ablator is very-low-Z material, Be or LiH, and there is a thin region of TaCOH-containing high-Z material just inside the ablator.

An x-ray backlighting source may be used to measure the radius and the velocity-time histories of the outer shell. However, the backlighting approach has limitations. It is not clear that the motion of the Au shell (or of the D-T in single-shell targets) can be adequately diagnosed. The imploded TaCOH may obscure the Au surface (and inner D-T), and some blowoff and mixing may occur. It does not appear possible to determine the temperature and density at the inner surfaces, even though these conditions strongly affect the implosion dynamics. It will be extremely difficult to measure the symmetry of the outer-shell implosion to the required 1% accuracy (7 μ m out of 500 μ m and 20 ps out of 2000 to 5000 ps when the

radius of the outer shell has converged twofold).

In addition to the backlighting diagnostics of the outer shell, it is necessary to diagnose the inner surfaces of the outer and inner shells. These surfaces may be observed during the first part of their implosions through a hollow tube of high-density material that is inserted through a hole in the capsule; the shells slide along the hollow tube during implosion. The diagnostics could be performed, for example, with an imaging optical streak-camera pyrometer,¹⁰ and preheat temperatures in the range of a few electron volts could be measured. Similarly, the symmetry and strength of the initial shock breakout could be determined. Fluff ejection caused by shock interaction with imperfections in the surface may be observed.

Penetration of the Au shell (or the outer shell) because of fluid instabilities might be diagnosed by the temperature increase (caused by mixing of outer hot material with inner cold material). An intense optical emission that arises when the Au shell strikes a few precisely positioned pins or shells may be used to observe the motion and symmetry of this shell during part of its convergence. When this shell has converged to 50% of its original radius, errors of 1% in the outer shell will be amplified to errors of 8%, since the outer shell converges fourfold before striking the inner shell, and may then be observed. Low-density blowoff may be discriminated against optically conducting pins with opaque caps of various thicknesses so that conditions with a significant $\rho\Delta X$ within the surface may be diagnosed.

The opportunities for creative diagnostics and experiments are clearly rich and numerous. With the combination of inner-shell implosion diagnostics, x-ray backlighting diagnostics, and neutron and x-ray imaging and radiochemical diagnostics of the central ignitor and main fuel, we should be able to develop a sufficient mastery of target dynamics so that the limiting target performance may be approached.

Coupling Experiments with 0.1- to 1-MJ Drivers

When the target is scaled up from the 0.1- to 1-MJ range to the multimegajoule range, the

plasma scale lengths increase approximately twofold. The quality factors for excitation of the Raman, Brillouin, and $2\omega_p$ plasma instabilities, as well as for filamentation, are proportional to the plasma scale lengths in the 0.1 to 1 times critical density range.¹¹ These processes generate suprathermal electrons, which may preheat the capsule, and the stimulated scattering instabilities reduce the laser-light absorption. We can use the Nova laser to generate the appropriate plasma scale lengths and to measure these processes in a sector of a sphere. Alternatively, we can generate the plasma distribution by a small gas jet, which is then irradiated by the Nova laser.

The risk of degraded coupling with larger targets may be greatly reduced by increasing the frequency of the laser light. Then, the collisional absorption via inverse bremsstrahlung wins the competition with collisionless processes.¹² A Nova laser with frequency doubling and tripling capabilities can be used to demonstrate efficient coupling at scale lengths relevant to multimegajoule size targets.

Summary

Although both ignition and SBE are theoretically possible with 10-kJ drivers, these goals will first be achieved with 0.1- to 1-MJ drivers. However, the feasibility and scale of ignition and SBE are only weakly coupled with the like parameters of high-gain fusion microexplosions.

We have considered a combination of experiments that can be performed with 0.1- to 1-MJ drivers to determine the driver energy, power, efficiency, wavelength, and voltage required to initiate high-gain fusion microexplosions. These experiments include ignition of the central ignitor; determination of the main fuel conditions via the central-ignitor thermonuclear energy; diagnosis of the implosion dynamics, including symmetry, fluid instabilities, and preheat; and determination of the laser-plasma coupling for multimegajoule reactor-scale targets.

Author: J. H. Nuckolls

A Computational Comparison of D-T, Neon, and Argon Implosions

Introduction

The peak conditions attained in contemporary laser-driven implosions of neon and argon gas are relatively easy to diagnose because these gases characteristically radiate at frequencies high enough to escape through the microspheres used to compress the gas. Imploded densities of 4 to 6 g/cm³ have been reported with these high-Z gases.^{13,14} These experiments have used the relative diagnostic ease of these high-Z implosions to study the effects of laser illumination symmetry, ablator thickness, and pusher instabilities on the peak imploded density.

There are limitations to using these gases to study questions relevant to D-T implosions. For example, the high radiation losses from neon and argon (the phenomena that makes them attractive from a diagnostic point of view) cause these gases to implode in a manner dissimilar to that of D-T. Therefore, inferences about D-T implosions deduced from neon and argon implosions must be made carefully. We have done comparative calculations to evaluate the effects of the gas fill on the implosion characteristics.

Physics of Moderate-Density Implosions

Implosions that give densities of 1 to 10 g/cm³ are dominated by a single shock that arises in the ablator, propagates through the pusher and the fill gas, reflects off itself at the center of the capsule, and partially stagnates the pusher (Fig. 3-3). The shock arises in the ablator, passes through the pusher (accelerating it), passes through the gas (accelerating it), reflects off itself at the center of the microsphere, and, returning to the pusher, slows it down substantially. Following this stagnation, the gas is more slowly compressed to peak conditions. Thermal losses from the bulk of the gas to the relatively cooler gas near the pusher determine the back pressure on the pusher

and, hence, its radius-vs-time trajectory relative to the shock.

In D-T, these thermal losses are dominated by thermal conduction, while radiative losses are small in comparison. For high-Z gases, since thermal conductivity goes down approximately as Z^{-1} (Ref. 15), while bremsstrahlung losses go up as Z^2 (Ref. 16) and bound-free radiative losses increase as Z^4 (Ref. 17), the thermal losses will be dominated by radiative losses; by comparison, losses by thermal conduction will be small. In addition, because of the strong Z dependence, thermal losses from high-Z gases will greatly exceed those from D-T.

For all three gases, the compression portion of the implosion following the initial passage of the shock can be adequately described by the simple expression

$$P = P_0 \left(\frac{R_0}{R} \right)^{3\gamma_{\text{eff}}},$$

where γ_{eff} is less than the perfect monatomic gas value of 5/3 because of thermal losses. From the discussion above, we expect, and the calculations show, that γ_{eff} is higher for D-T than for either neon or argon.

We can also describe the shock propagation through the gas by means of a

Fig. 3-3. Implosion of a glass microsphere characterized by a single strong shock.

A Calculational Comparison of D-T, Neon, and Argon Implosions

γ_{eff}^s (which will, in general, differ from that defined above). Neon and argon are not fully stripped in these implosions, so they have ionization states available to be excited by the passage of the shock, which reduces their γ_{eff}^s . In addition, at the initial densities of interest in contemporary implosion studies, neon and argon are thin to radiation generated at the shock front.¹⁸ This radiation loss also results in a lower γ_{eff}^s : γ_{eff}^s is ~ 1.2 for neon and argon, while γ_{eff}^s is $\sim 5/3$ for D-T; by contrast, if the radiation losses are turned off, γ_{eff}^s is ~ 1.3 for neon and argon.

Since the ratio of densities before and after the shock (for strong shocks) is given by

$$\rho_f = \rho_0 (\gamma_{\text{eff}}^s + 1) / (\gamma_{\text{eff}}^s - 1) ,$$

the density jump during the shock passage in neon and argon will be higher than for D-T. Because of the radiation precursor, and because the gas is preheated by suprathermal electrons before arrival of the shock, the initial gas pressure is high enough that the strong shock approximation is no longer valid. However, the high-Z gases still exhibit twice the shock-density jump seen in the D-T.

Calculational Parameters

The calculational model is derived from that used by Mead et al.¹⁹ to calculate the "10X" targets imploded using the Shiva laser system

during 1979. These were simple Teflon-coated, D-T filled glass microspheres (Fig 3-4) that were diagnosed by three techniques to have achieved peak densities in the range of 1 to 3 g/cm³ and yields of from 1 to 8 × 10⁸ neutrons. The density is close to the range of recently reported densities for argon and neon implosions,^{13,14} so we expect this implosion model to provide a test of the sensitivity of current implosion experiments to the fill gas.

The implosion is driven by a 200-ps FWHM Gaussian pulse of 1.06-μm laser light, which produces a 720-J pulse of ~ 30 -keV suprathermal electrons. Besides providing drive, these electrons also preheat the glass microsphere and the fill gas. For purposes of these comparisons, the implosion is assumed to be one dimensional, although the actual D-T implosions did experimentally show some asymmetry.

All calculations started with a gas-fill density of 0.01 g/cm³. They were done on the LASNEX code²⁰ using the nonlocal thermodynamic equilibrium (NLTE) modeling for the fill gas.^{21,22}

Comparison of Calculational Results

Comparing gas conditions at the time of peak density (Table 3-1), we see that the D-T implosion reaches higher temperatures, lower densities, and lower pressures than the high Z gas implosions. The difference in temperatures is caused by the higher thermal losses from the high-Z gases. The difference in densities is partly caused by the difference in pressure and partly caused by a difference in the number of particles per unit mass. Using the perfect gas law, $\rho \propto P\bar{A}/(\bar{Z}T_e + T_i)$, where ρ = gas density, P = gas pressure, $\bar{A}$ = mean atomic weight of gas, $\bar{Z}$ = mean ionization state, T_e = electron temperature, and T_i = ion temperature, we find that a factor of 2 in the density difference between D-T and argon is attributable to the difference in $\bar{A}/(\bar{Z} + 1)$ ratio (the average mass per particle), a factor of 1.4 is caused by the temperature difference, and the remaining factor of 5.3 is caused by the difference in final pressures. Similar numbers hold true for neon.

The difference in final pressures is not easily understood because it is the cumulative effect of all the physics differences

Fig. 3-4. Targets tested in the "10X" campaign on Shiva during 1979, and the basis of the present calculational comparison.

throughout the implosion. These various effects are unraveled in the following discussion, where the most important features of the implosion are described qualitatively for D-T and argon. (Neon is intermediate between these two, but more akin to argon in its behavior.)

In simple implosions, as described above, there is an initial shock that is generated in the plastic ablator and then passes through the glass pusher into the fill gas. The shock accelerates the pusher as it passes through it, and it also accelerates the fill gas, giving it the same initial velocity as the pusher. In the implosion model used here, the range of the suprathermal electrons is comparable to the total thickness of the ablator plus the pusher. Thus, suprathermal electron deposition occurs in the pusher as well as in the ablator; in contrast with implosions driven by low-temperature suprathermal electrons [Fig. 3-5(a)], the pusher never experiences a strong shock [Fig. 3-5(b)]. The low-temperature, electron-driven implosion clearly shows a strong initial shock in the pusher that is absent from the present model because of the long deposition length of its 30-keV suprathermal electrons. The temperatures shown in Fig. 3-5 are for the inside surface of the glass pusher.

The pusher continues to accelerate (Fig. 3-6) throughout the early portion of the implosion because of continued deposition of suprathermal electrons. Pressure buildup in the fill gas causes the D-T curve to deviate from the argon curve in Fig. 3-6 after 0.40 ns. Argon has higher thermal losses and, therefore, lower gas pressures, so its pusher has a higher velocity. The early implosion (before 0.40 ns) shows a continual acceleration because of continued suprathermal electron deposition in the pusher. The kink at 0.53 ns for D-T and at 0.56 ns

▲ Fig. 3-5. Comparison of pusher ion temperature for an implosion. (a) Driven by low-temperature suprathermal electrons. (b) The present model.

◀ Fig. 3-6. Pusher velocity vs time for argon and D-T, using the present calculational model.

Gas	Maximum density (g/cm ³)	Electron temperature (keV)	Ion temperature (keV)	Pressure (Mbar)	Ionization state
D-T	2.06	0.61	0.67	1.0×10^3	1.0
Ne	18.7	0.48	0.49	4.4×10^3	8.9
Ar	29.3	0.49	0.50	5.3×10^3	14.6

Table 3-1. Calculational results at time of maximum density.

for argon is the end of the deceleration caused by the reflected shock.

The accelerating pusher creates a shock in the fill gas (Fig. 3-7). The effect of the reflected shock on the implosion is clearly visible, as is the higher peak compressed density (smaller radius at turnaround) of argon.

As the initial shock passes through the fill gas, it compresses and heats the gas. The gas behind the shock continues to be compressed, both because of the accelerating pusher and because of the spherically convergent geometry. This compression is relatively mild, since it is communicated via sound waves rather than shock waves. Compression continues until the shock, reflecting off itself at the center of the microsphere, returns through the gas.

As the reflected shock travels outward from the center of the microsphere, it converts the kinetic energy of each element of gas into internal energy as it passes. The

gas behind the reflected shock (i.e., the gas between the reflected shock and the center of the microsphere) is, therefore, almost stagnant. The reflected shock diminishes in strength as it travels outward because of the pressure gradient. The amount that it dissipates before it hits the pusher depends on how strong the thermal losses to the pusher were before the shock hit the center of the microsphere. Since argon has larger thermal losses, it has a stronger gradient and a weaker reflected shock, and its pusher stalls less than the pusher compressing the D-T gas. [Compare Fig. 3-7(a) with Fig. 3-7(b).] This thermal gradient also creates a pressure gradient in the gas that begins to decelerate the pusher even before the reflected shock returns to it. After the reflected shock interacts with the pusher, the velocity of the pusher is considerably diminished.

The final portion of the implosion is a compression, which proceeds more rapidly for the high-Z gases than for D-T. The behavior of the gas during this part of the implosion is dominated by its thermal losses to the pusher.

These processes can be made more explicit by following the trajectory of the zone, through pressure-density space, in the LASNEX calculation, which contains the mean-mass point (Fig. 3-8). This zone, which is initially at a radius of $55.6 \mu\text{m}$ and contains 2.5% of the total gas mass, is significant because 50% of the total gas mass lies outside (or inside) $55.6 \mu\text{m}$. The zone is a good indicator of the mass-averaged behavior of the total gas mass. (In particular,

the peak density of this zone is very close to the mass-averaged peak density of all the fill gas.) The zone is preheated by the suprathermal electrons, then it experiences the initial shock, a period of compression, the reflected shock, and the final compression. These processes are treated individually below.

Preheat. The suprathermal electrons preferentially heat the electrons in the fill gas. The ion temperature, therefore, lags behind the electron temperature. In D-T, where the ions and electrons contribute equally to the pressure, this temperature difference has a larger effect than in argon, where the bulk of the pressure comes from the electrons (Z times as many as ions). In addition, D-T and argon have different numbers of particles per unit mass $[(\bar{Z} + 1)/\bar{A}]$. These differences, and a small difference in the equation of state, account for the slightly higher pressure in the preheated D-T relative to argon just before the initial shock (Fig. 3-8).

The Initial Shock. The shock preferentially heats the ions, which then couple to the electrons.²³ This coupling takes approximately 100 to 200 ps in the high-Z gases and noticeably broadens the pressure and density jumps during the shock relative to D-T. (Because the latter gas has a smaller ion mass, it reaches equilibrium four times faster and has an increase in ion temperature across the shock wave that is 16 times smaller than is the case for the other gases.)

The initial shock is not a strong shock—i.e., the pressure jump during the shock is not large compared with the density

Fig. 3-7 Comparison of implosion trajectories using the present calculational model. (a) D-T. (b) Argon.

jump—because of the high pressure in the preheated gas before the arrival of the shock. The density jump in the D-T (here, ~ 2.6 , as shown in Fig. 3-8) is smaller than that in the argon (~ 5.4) because argon has an increased number of internal degrees of freedom that give it a lower γ_{eff} during the shock process. More quantitative comparisons with simple shock theory are stymied here because of the continually accelerating pusher. Implosions whose pushers are dominated by a single-shock acceleration show good agreement with shock theory for both D-T and argon.

Compression Following Initial Shock. The particular element of gas that is being followed here has a relatively long period of compression between the initial shock and the reflected shock. It is well described by the expression

$$P = P_0 \left(\frac{\rho}{\rho_0} \right)^{\gamma_{\text{eff}}},$$

where γ_{eff} is 1.54 for D-T and only 1.39 for argon, because of the higher thermal losses from argon. (In simpler implosions where the pusher does not continue to accelerate following the initial shock, the γ_{eff} for D-T is very close to $5/3$.)

As the pusher radius decreases, the density of the gas increases. If the gas were of uniform density, the pusher radius would vary inversely with the $1/3$ power of the density. Thus, the horizontal axis of Fig. 3-8 can be loosely interpreted as the pusher radius, which decreases to the right. This figure, therefore, shows that, at a given pusher radius (before peak density), the D-T pressure is greater than the argon pressure because of the preheat pressure difference accentuated by the difference in γ_{eff} . After 0.40 ns into the implosion, when the gas pressure acting on the pusher begins to determine the acceleration of the pusher, the velocity of the pusher for argon implosions is higher than that for D-T implosions (at the same radius) because the pressure of argon is lower (Fig. 3-6). Pressure buildup in the fill gas causes the curves to deviate after 0.40 ns. Argon has higher thermal losses and, therefore, lower gas pressures, so its pusher has a higher velocity.

The initial velocity of the shock in argon is very close to that in D-T. This, combined with the higher velocity of the pusher in

the argon implosions, means that the reflected shock returns to the pusher at a smaller radius in argon than in D-T. Equivalently, the mean-mass zone sees the reflected shock at a smaller density in D-T than in argon (Fig. 3-7).

Reflected Shock. The reflected shock is not as strong as the initial shock, and the density jumps reflect this, being 1.5 for D-T and 2.0 for argon. When the reflected shock reaches the pusher, the gas is left almost stagnant; except for thermal losses to the pusher, it would be stagnant.

For simple implosions where the pusher is driven by a single strong shock, the shock travels at $(\gamma + 1)/2$ times the pusher velocity. Neglecting spherical convergence, the reflected shock will return to the pusher when its radius is $(\gamma - 1)/(\gamma + 3)$ times the initial radius. For a gas with $\gamma = 5/3$, this is one-seventh of the initial radius, or a density increase of $7^3 = 343$. The D-T density increase (~ 62) is less than this, because the pusher is slowed down substantially by gas back pressure, while the shock velocity increases because of spherical convergence. For high-Z gases, where $\gamma \sim 1 + \epsilon$, the density increase is $81/\epsilon^3$. For argon, $\epsilon \sim 0.3$, which leads us to expect a density increase of ~ 1000 ; however, argon shows a lesser increase in density than expected (~ 340) because its pusher is also slowed down.

Fig. 3-8. Comparison of trajectories of mean-mass zone through pressure-density space in LASNEX calculations for D-T and argon.

Final Compression. Thermal losses dominate the final-compression region. The hydrodynamic energy input is down because the pusher velocity has been reduced substantially. If the thermal losses are reduced or limited, the pressure can continue to increase. For argon, the radiative mean free path becomes less than the size of the D-T cavity, because a drop in the ion temperature reduces the $\bar{Z}$, and the implosion becomes isothermal (Fig. 3-9). For D-T, thermal conduction losses compete effectively with hydrodynamic gains, and the temperature drops, maintaining an almost constant pressure.

Fig. 3-9. Comparison of trajectories of mean-mass zone through ion temperature-density space in calculations for D-T and argon.

Fig. 3-10. Trajectory of mean-mass zone for simple strong shock D-T implosion shown in Fig. 3-5(a).

However, the deceleration of the pusher is not constant for D-T (which we might naively expect, given the constant gas pressure). The deceleration actually increases following the interaction of the reflected shock with the pusher, which momentarily reduces the deceleration to zero, giving a late-time velocity vs time profile that is distinctly nonlinear. Indeed, the velocity vs time profile for argon is much closer to a constant deceleration, even though the pressure is increasing as R^{-3} (Fig. 3-6).

The details of this final-compression region for D-T depend sensitively on the temperature gradient existing in the pusher when the reflected shock hits the pusher (stagnation). For this implosion, the pusher never experiences a strong shock, because the long deposition time of the suprathermal electrons driving the implosion leads to deposition in the pusher as well as the ablator, and the temperature of the pusher at stagnation is caused primarily by compression heating (Fig. 3-5). This leads to a large temperature difference between the D-T gas and the bulk of the pusher, with resultant large thermal losses caused by thermal conduction. In simple single-shock implosions, where the pusher is also subjected to a single strong shock, the temperature difference is smaller, and D-T heats up during the final compression (Fig. 3-10). In fact, the D-T pressure continues to increase during the final compression, in contrast with the behavior of the high-temperature suprathermal-electron-driven implosions under consideration here (Fig. 3-8).

Summary

The higher Z of argon and neon means that different physical phenomena govern their implosions than govern D-T implosions. This, combined with their higher mass per particle, gives them substantially different calculated implosion histories than those of D-T.

In particular, the calculated peak ion temperature is higher for D-T, and occurs earlier in the implosion, than for the high- Z gases (Fig. 3-9). Since diagnostics give maximum signals when the temperature is maximum, this implies that the diagnostics for D-T implosions are not sampling the same portion of the implosion as are the

diagnostics in argon implosions. This further complicates the comparison of argon implosions with D-T implosions.

Finally, mixing of the pusher material into the D-T gas by Rayleigh-Taylor instabilities may cause serious yield degradations if the pusher experiences any deceleration significantly before peak ion temperature (such as occurs in the implosions modeled here because of the reflected shock). Such mixing will depend on the relative densities of the pusher and the gas, which will be determined primarily by the mass per particle of the pusher relative to the gas. This implies that the glass pusher density will be approximately two times the density of the D-T, while the argon will be approximately 1.2 times the density of the glass. In other words, the argon/glass interface will be unstable during those portions of the implosion when the D-T/glass interface is stable, and vice versa. If mixing is important, the information gained from high-Z implosions will be largely irrelevant to D-T implosions.

Author: J. C. Stevens

Charged-Particle Fusion

Introduction

We have made several advances in the LLNL Charged-Particle Fusion Program during 1980. The advances described in this portion of the report are in heavy-ion fusion; however, we have also made important progress in radiation-coupled targets designed for the PBFA-II light-ion machine to be built at Sandia National Laboratory in Albuquerque. For heavy ions, we have completed an initial numerical survey of target gain as a function of total ion-beam energy, focal-spot radius, and range, which is a function of ion kinetic energy and atomic weight. This survey provides important guidance for the optimization of accelerators. The calculated target gain is higher than that reported in the Laser Program Annual Report for 1979,²⁴ thereby enhancing the outlook for heavy-ion fusion.

A second area of advance involves beam propagation across the chamber to the target. Previous studies have shown that heavy-ion beams will propagate well in low-pressure ($\gtrsim 10^3$ Torr) environments (and perhaps at higher pressures), but, for a given focal-spot radius, space-charge forces place constraints on ion-charge state and kinetic energy. Our new studies show that neutralization with electrons relieves these constraints. Furthermore, it appears relatively easy to achieve such neutralization.

There have also been important developments in heavy-ion accelerators during 1980. In particular, the development of large arrays of electrostatically focused ion beams²⁵ has generated significant interest. This development is expected to increase the technical feasibility and reduce the cost of heavy-ion accelerators.

Author: R. O. Bangerter

Ion-Beam Target Gain for a Range of Beam-Input Parameters

We have made an initial survey of target gain vs beam energy, focal radius, and ion range. This survey provides data for understanding the trade-offs among accelerator designs.

To design efficient, cost-optimized particle accelerators for heavy-ion inertial fusion, it is necessary to calculate target gain as a function of ion-beam parameters. The important ion-beam parameters are total beam energy, E , focal-spot radius, r , and ion range, R , expressed in units of mass per area. Peak beam power, P , is also an important parameter, but, for a given target design, the power is a function of energy (or vice versa).

We would expect specific energy deposition, which is proportional to E/r^2R , to be an important parameter. Thus, we could hope that, within some range of values of radius and range, the gain might depend on r^2R rather than on r and R independently. With this motivation, we have attempted to describe our LASNEX calculations of gain as a function of E and $r^\epsilon R$. Our results are represented to within a few percent with $\epsilon \approx 3/2$. So far, our calculations have covered only a small range in r ; they can be considered valid for $0.1 < r/E^{1/3}$

Fig. 3-11. Target gain vs ▲ driver energy input for double-shelled targets.

Fig. 3-12. Target gain vs ▼ driver energy input for single-shelled targets.

< 0.2 , where r is in cm and E is in MJ. The input energy scales roughly as target mass; therefore, the expression $r/E^{1/3}$ simply corresponds to the fact that mass of a target scales as r^3 .

Our results for double-shelled targets are shown in Fig. 3-11, and our results for single-shelled targets are shown in Fig. 3-12. The solid curves in Figs. 3-11 and 3-12 are best estimates of target gain for different values of $r^{3/2}R$, where r is the focal radius of the beam (cm) and R is the range (in g/cm²) of the ions. In calculating these curves, we have adopted conservative ignition criteria, as described in our 1979 Annual Report.²⁶ As a specific example, a 10-GeV Pb-ion beam focused to $r = 0.2$ cm gives $r^{3/2}R = 0.012$; thus, the 0.01-gain curve would be roughly appropriate for this case. The bands defined by the dashed lines in Figs. 3-11 and 3-12 correspond to short-wavelength laser targets.

In earlier reports, we assumed that the gain of heavy-ion targets would lie at the lower edge of the bands shown in Figs. 3-11 and 3-12 (Refs. 27 and 28). The present gains are typically higher on the basis of improved calculations, but we emphasize that these results are preliminary. Target performance for heavy-ion fusion may improve as other designs and modifications are pursued.

The optimistic curves (dotted) in Figs. 3-11 and 3-12 are based on the same criteria as the optimistic curves in Ref. 26 and represent reasonable upper bounds on gain for the types of targets being considered. The difference between the optimistic and best-estimate curves is indicative of large uncertainties in target gain; however, the relative gain for different $r^{3/2}R$ can be calculated with good precision.

The gain curves for single-shelled targets given in Fig. 3-12 are lower than those of double-shelled targets, but they decrease less rapidly with decreasing energy and are more interesting at lower input energy. This is especially true for ion-beam fusion because the lower target gain of single-shelled targets is compensated by the expected high efficiency of particle accelerators. Single-shelled targets also have the advantage of being simpler and easier to fabricate. However, for a given input energy, the power requirement for a single-shelled target is approximately twice as great as for a double-shelled target. The peak power requirement

is given as a function of energy in Fig. 3-13; the numerical labels on the curves in Fig. 3-13 refer to different values of $r^{3/2}R$. As in the case of target gain, these curves are somewhat uncertain, but should be adequate for accelerator design. The pulse length is not equal to E/P because our targets require pulse shaping.

Figure 3-14 gives ion range as a function of ion kinetic energy for several representative ions. These curves are based on aluminum target material at a temperature of 200 eV and a density of 0.2 g/cm², values typical of target conditions. (Aluminum was chosen for illustrative purposes.) The range is relatively independent of the material chosen, being approximately a factor of 2 larger for high-Z material than for low-Z material. The dependence on temperature and density is rather weak for ions having velocities large compared to thermal electron velocities. For example, we calculate a 21% increase in range, relative to the curves in Fig. 3-14, for 10-GeV lead ions incident on room-temperature aluminum at solid density. Note that heavier ions allow the use of higher kinetic energies and, therefore, lower beam currents than do lighter ions.

Authors: R. O. Bangerter, J. W-K. Mark, and A. R. Thiessen

Transport of Heavy-Ion Beams to the Target

We have made progress this year in confirming the usefulness of vacuum-propagation modes for transporting heavy-ion beams across fusion-reaction chambers from the focusing magnets to the target. Typically, we are interested in transporting ~20-ns pulses of heavy ions (e.g., Ti, Pb, or U) at peak currents up to about 15 kA across a 10-m distance to a 0.25-cm focal spot. This amounts to delivering several megajoules of beam energy at powers >100 TW. Simple ballistic focusing in hard vacuum ($<10^{-4}$ Torr) is sufficient for some applications. However, if we wish to operate a fusion chamber such as HYLIFE (see "Accomplishments Associated with the HYLIFE Chamber Concept" in Section 9) in the pressure range of 10^{-4} to 10^{-3} Torr, additional effects such as beam stripping and ionization of the medium must be

Fig. 3-13. Peak power ▲ requirement as a function of input energy for single- and double-shelled targets.

Fig. 3-14. Ion range in g/cm² as a function of ▼ ion kinetic energy.

considered. Neutralization by coinjected electrons is found to be helpful in widening the choice of ion charge state, ion kinetic

energy, focal-spot radius, and fusion-chamber radius for vacuum transport. Also, the pinch mode of propagation at 2 to 50 Torr appears still to be a viable alternative. In the following paragraphs, we discuss the physics of these modes of propagation, some of their relations to fusion-chamber design, and, briefly, our recent preliminary investigations regarding focusing and deposition experiments achievable by test-facility accelerators.

The Propagation Physics of Heavy-Ion Beams. From the point of view of propagation across fusion chambers in reactor scenarios and of focusing to high intensities in deposition experiments, heavy-

ion beams are considered "stiff" because of their high ion mass and kinetic energy, their relatively low current, and their (anticipated) low level of beam emittance. Several windows appear to be available for efficient transport, as indicated in Table 3-2. The vacuum propagation regimes 1, 1n, 2, and 2n will be discussed first because they have relatively simple physics; therefore, the conclusions are less subject to uncertainties. The regimes 4, 5, and 5e require propagation in gas and exhibit more complicated physics.

In the hard-vacuum propagation regime ($<10^{-4}$ Torr), ions are ballistically focused from the initial aperture, R_0 , and the ion trajectories are almost straight lines. The final radius, R_f , at the neck is determined by the beam emittance at the entrance enhanced by the internal space-charge forces of the beam. In particular, the anharmonic component of such forces results in beam blowup, which we attribute to an effective growth of rms emittance (or "beam temperature"). The physical mechanism for this effective emittance growth is shown in Fig. 3-15. Because of the accumulated action of anharmonic space-charge forces over the ≈ 10 m of propagation distance, particles at different radial positions no longer focus to the same point; the net result is an enlarged focal spot. This growth in effective emittance is governed by

$$\epsilon_{gv} = (2.3 \text{ mrad-cm}) \left(\frac{L}{10\text{m}} \right) Z_i^2 \times \left(\frac{I_b}{10 \text{ kA}} \right) \left(\frac{200}{A_i} \right) \left(\frac{0.3}{\beta\gamma} \right)^3 \left(\frac{\lambda}{0.388} \right), \quad (5)$$

where L is the distance of propagation from the final lens and Z_i , A_i , β , and I_b are the ion charge, atomic weight, velocity (divided by speed of light), and total beam current, respectively. Also, $\gamma = (1 - \beta^2)^{-1/2}$. The dimensionless parameter, λ , depends on the radial profile of the beam, which is zero for a square profile and is 0.388 for a Gaussian profile. As a result, the final emittance, ϵ_f , of the beam at the focal radius is

$$\epsilon_f^2 = \epsilon_{ba}^2 + \epsilon_{gv}^2, \quad (6)$$

where ϵ_{ba} = initial emittance from accelerator. The focal-spot radius is given by

Fig. 3-15. Particle orbits in a 1-kA beam of 10-GeV U^{+1} ions with Gaussian-beam profile and rms radius at entrance of 10 cm.

Table 3-2. Heavy-ion beam transport appears possible in several pressure regimes.

10^{-6}	1, 1n	1. Vacuum, no instabilities, growth in effective rms emittance.
10^{-4}	2, 2n	2. Mild stripping and plasma effects, growth in effective rms emittance.
10^{-2}	3	1n-2n. Neutralization controls emittance growth and target chargeup.
1	4	3. Stripping and plasma effects. Instabilities expected to defocus beam.
10^2	5, 5e	4. May be a window. Two-stream instability collisionally suppressed, filamentation okay at low current, multiple scattering not serious. This window can shrink to zero for some parameters.
	6	5. Self-pinch modes appear possible.
		5e. Injecting counterstreaming electrons helps pinched mode.
		6. Multiple scattering destroys propagation.

$$R_f \approx \epsilon_f \left(\frac{L}{R_0} \right) \quad (7)$$

In soft vacuum (10^{-4} to 10^{-3} Torr), two additional phenomena affect the growth of effective emittance. One of these phenomena, beam ionization of the background gas, provides free electrons that, when captured, will reduce repulsive space-charge forces within the beam. This is illustrated in Fig. 3-16, where growth of effective emittance for a 1-kA, 10-GeV uranium beam is plotted vs propagation distance in lithium vapor at pressures up to 3.6×10^{-3} Torr. The electrons produced by the ionization partially neutralize the beam and reduce space-charge forces. The effect saturates, however, at a pressure of 1 to 2×10^{-3} Torr. Above $\sim 1.2 \times 10^{-3}$ Torr, the reduction in effective emittance saturates because each beam particle has ionized at least one lithium atom. The second phenomenon is beam-charge stripping, which increases the growth of effective emittance. For lithium vapor, this becomes important for pressures above 10^{-3} Torr and for propagation distances $\lesssim 10$ m.

Figure 3-17 illustrates both these phenomena by showing the heavy-ion distribution function, $rn(r)$, at the focal spot. In this illustration, particle distribution per unit interval in radial position is plotted vs radial position for a 2-kA beam of 10-GeV U^{+1} ions with initial aperture of $R_0 = 10$ cm

and focal distance of 10 m. For the particular choice of parameters, the spread in particle distribution at the focal spot is quite large if the beam is transported through a vacuum reactor, which is illustrated in the right frame of Fig. 3-17. Ionization of lithium reduces the spread significantly, as can be seen in the left frame;

Fig. 3-16. Reduction in growth of effective rms emittance caused by ionization of the medium by the beam.

Fig. 3-17. Comparison of beam propagation in Li vapor with that in vacuum.

Fig. 3-18. Effect of neutralization by coinjection of electrons. (a) With neutralization (black curve). (b) Without neutralization (red curve).

Fig. 3-19. Envelope of pinched-beam pulse for a 4-kA beam of 10-GeV U^{+1} ions.

however, a population of stripped uranium ions is present with a somewhat larger spread.

Active neutralization of the ion beam by coinjection of electrons is another attractive possibility for reducing growth of effective emittance by up to a factor of 10. By using a

two-dimensional electrostatic-particle simulation code (HIPPO), we have found that the thermal spread within the coinjected electron beam may be as great as 10% of the injection energy without significantly reducing neutralization. In Figs. 3-18(a) and 3-18(b), we illustrate the focal spot with active beam neutralization as predicted by HIPPO for a 4-kA, 10-GeV U^{+1} beamlet propagating 10 m to a 2.5-mm-radius target and compare this spot size with the spot size for the same beam current without neutralization. Thus, for the same total current on target, active neutralization allows use of fewer beamlets. Space-charge limited-flow type of electron injection is not as efficient in neutralizing the ion beam, but can reduce effective emittance growth by up to a factor of 3.

At higher gas pressure (~ 2 to 50 Torr), the self-pinch mode²⁹ of beam propagation offers the possibility of small focal-spot radius over large distances. This mode is similar to the pinched modes employed for light-ion propagation except that no external current channel is required. Although the beam is quickly stripped to a high charge state, the beam space charge is neutralized and the current is nearly neutralized.

Because of the low beam emittance, the small residual net current is sufficient to pinch the beam body. The beam head sees no net current and is, therefore, freely expanding, as illustrated in Fig. 3-19. This figure illustrates the envelope of the pinched beam pulse for a 4-kA beam of 10 GeV U^{+1} ions (initial emittance of 1 mrad-cm into 5 Torr neon). Plotted as height is the rms radius of the beam as a function of distances from beam head and from entrance port. These calculations, based on a one-dimensional envelope code, include effects of beam stripping, emittance growth caused by gas scattering and anharmonic self-force, and beam-generated conductivity. Two-stream instability and the hose instability are believed to be suppressed for the self-pinch heavy-ion beams. (These two instabilities are known to inhibit electron-beam propagation outside of the pressure windows 5.) Injection of counter-streaming electrons³⁰ has been suggested as a means to ensure the self-pinch propagation of heavy-ion beams.

Some Implications for Combustion-Chamber Design. Table 3-3 gives the typical parameters that we have adopted for dis-

cussion of useful regimes of beam propagation in fusion-chamber design. The parameters are essentially those accepted at the 1980 Los Alamos informal workshop on heavy-ion beam transport. The reference values represent a typical, realistic choice that we have made for comparison. We now indicate some restrictions or permissible deviations from these reference values, as appropriate to each regime of beam transport. It has also been agreed at the Los Alamos workshop to begin using beam ions that are not uranium, but the revision of the atomic physics in the beam transport codes have yet to be carried out.

As can be seen from Eqs. (5) through (7), ballistic transport in hard vacuum ($<10^{-4}$ Torr) would have some difficulty achieving exactly the reference parameters because of effects caused by growth of effective emittance. However, if 15-GeV ions are used with $N \lesssim 16$ beams and a propagation distance of $L \gtrsim 8$ m, then we can focus to the 0.25-cm spot radius. If this propagation mode were used, the smaller propagation distance places some restrictions on dry-wall³¹ fusion chambers, but should not be a problem because we could use a lower-gain target with reduced wall loading. (The heavy-ion accelerators are expected to have 20 to 30% efficiency and a high repetition rate.) Vacuum pumping problems may be more of a restriction in this pressure range than beam transport.

As we have seen, soft vacuum (10^{-4} to 10^{-3} Torr) might be easier for transport than hard vacuum because of partial beam neutralization caused by ionization of the medium. The use of $N > 10$ beams is compatible with our reference parameters. If the beams are neutralized with coinjected electrons, then the difference between the two vacuum propagation modes becomes minimal. Even when the accelerator gives very few beams, say $N \approx 4$, it is compatible with our reference parameters. Both dry-wall³¹ and liquid-metal wall^{32,33} fusion chambers can be used in this regime.

The self-pinch mode of beam propagation allows higher fusion chamber pressures and, therefore, allows gas-protection schemes for the chamber walls. In addition, the smaller beam ports allow a reduction in pumping requirements from those of the vacuum regimes. The self-pinch mode also allows higher ion charge states to be used in

the accelerator. Even though there is higher risk because the physics is more complicated, the resultant propagation mode is so intriguing that problems such as conductivity vs current neutralization, effects of knockon electrons, and various possible instabilities ought to be given further study. Note that self-pinch electron beams have been observed to propagate 5 to 10 m in 5-Torr neon gas.³⁴

In summary, we find that the requirements on beam transport for fusion applications allow considerable freedom in designing accelerator drivers and fusion chambers. We can have any number of beams ($N > 4$ in > 2 clusters), and beamlet currents of $I_n \leq 4$ kA are possible. Ion type, kinetic energy, and charge state are relatively unrestricted. If $Z > 4$ is used, we might require neutralization or demonstration of pinch-mode of propagation. Distance from the lens to the target can be $L \leq 15$ m, and larger propagation distances are possible for the pinch mode. It has been suggested that target charging might cause problems by attracting and accelerating electrons; neutralization of the incident beams eliminates this concern.

Comments on Achievable Focused-Beam Intensities in Heavy-Ion Fusion Accelerator Test Facilities. We briefly consider the possibility for near-term experiments. Preliminary results suggest³⁵ that the emergent beams for some test-facility accelerators could be ballistically focused to an intensity of close to 100 TW/cm². Our numerical examples are based on the parameters of a recent design proposal³⁶ for

Table 3-3. Reference parameters for beam in fusion chamber.

		Reference value	Range (approx)
Ion kinetic energy	$= W_i$	$= 10$ GeV	5–20 GeV
Ion charge state	$= Z_i$	$= 1$	≥ 1 –8
Ion atomic number	$= A_i$	$= 238$	≥ 200
Beam energy (total)	$= E_a$	$= 3$ MJ	3–10 MJ
Beam power (total)	$= P_a$	$= 150$ TW	100–300 TW
Beam current (total)	$= I_a$	$= 15$ kA	~10–30 kA
Beam focal radius	$= R_f$	$= 0.25$ cm	0.14–0.5 cm
Beam duration, if square pulse	$= \tau_b$	$= 20$ ns	
Beamlet current $= I_a/N$	$= I_b$		< 4 –6 kA
Beamlet emittance input	$= \epsilon_{ba}$		≥ 1 mrad-cm
Distance, target to last lens	$= L$	$= 10$ m	5–15 m
Chamber pressure (equivalent Li)	$= P_{eq}$		10^{-6} – 10^2 Torr

a multibeam induction linear accelerator test facility. Focusing and transport in this case are facilitated by the low rms emittance of $\sim 5 \times 10^{-2}$ mrad-cm per beamlet (e.g., Na ions at 100 MeV) and by the fact that the intensity increases very rapidly with decreasing focal distance; the latter effect is caused by the decrease in spot radius according to Eqs. (5) through (7). The beam from this proposed test facility consists of 100-MeV singly ionized ions, and the focal distance has been chosen to be $L \sim 0.7$ m in a vacuum. The above intensity is reached if we choose one of the following:

- Compression of the emergent beam pulse of thallium ions by a factor of 10 to reach 0.1 TW in 10 ns.
- Using the lighter sodium ions to increase the current by a factor of 3, and compressing the pulse by a factor of 3 to 4 to 0.1 TW in 30 ns.
- Using sodium ions and neutralizing the beam before it enters the target chamber to prevent beam blowup caused by space-charge forces.

Conceivably, the intensities might reach 400 TW/cm² in this design³⁶ if we focus to $L \approx 0.5$ m or if we take more care in using the above three features. However, to reach $\approx 1\,000\,000$ K (≈ 100 eV) in disk-heating experiments, it is sufficient to have $\sim 1.7 \times 10^{14}$ W/cm², which can be reached by 0.3 TW of Na ions focused to a spot ~ 1.5 mm in diameter.

Thus, with this proposed test facility (among others), we can look forward to performing a number of interesting beam-focusing and transport experiments. Deposition experiments in which disks will be heated to ≥ 100 eV are expected. We could also reach as much as 1 to 3 kA of incident ion current on these disks with beam intensities almost comparable to those of reactor targets. Thus, if anomalous plasma effects on deposition emerge, the conditions should be available for testing some of them. On the other hand, these plasma effects might well be more severe for intermediate ions, such as sodium, than for truly heavy ions. Also, the ≈ 4 to 5 MeV/nucleon achievable is still an order of magnitude smaller than the more realistic heavy-ion deposition conditions in reactor targets (where relatively classical deposition is expected). Further studies on test-facility

designs and beam focusing are essential to confirm our estimates.

Authors: W. A. Barletta, W. M. Fawley, E. P. Lee, J. W-K. Mark, and S. S. Yu

Plasma Theory

Introduction

This has been an exciting and productive year for our laser plasma theory group. The wavelength dependence of laser-plasma coupling continued to be a major focus of our work. Improved coupling of shorter-wavelength laser light with targets has long been predicted.³⁷ As the wavelength of the laser light decreases, the underdense plasma penetrated by the light becomes simultaneously denser and cooler and, hence, more collisional. This greater collisionality both enhances favorable effects, such as inverse bremsstrahlung absorption, and weakens the collective processes that can degrade the quantity or quality of the absorption.

Predictions of improved coupling of shorter-wavelength light with targets were supported by experiments from many different laboratories.³⁷⁻⁴⁰ Indeed, an absorption efficiency as high as 90% for an intensity of about 10^{15} W/cm² has been observed at LLNL with $0.35\text{ }\mu\text{m}$ light (see "Analysis and Summary of Wavelength-Scaling Experiments and Comparisons with Simulations" in Section 7). The quality of the absorption is also greatly improved; i.e. the heated electrons are much cooler, and very few extremely energetic electrons are generated. More experiments are needed to extend these very promising results to the regime of large underdense plasmas.

Another highlight of 1980 was the observation of sizable levels of Raman-scattered light (see "Stimulated Raman Scattering in Large Plasmas" in Section 7), an important effect predicted⁴¹⁻⁴³ for large underdense plasmas. The observation of this process emphasizes again that the size of the underdense plasma is a very important parameter for the coupling. Since Raman scatter occurs from electron plasma waves, hot electrons are self-consistently produced

in the nonlinear state. Because these hot electrons are of great importance to target design, we have given a great deal of attention to estimating their temperature. For plasma densities $\gtrsim 0.2 n_{cr}$, our simulations⁴⁴ show that the heated electrons arising from Raman backscatter have a quasi-Maxwellian velocity distribution with a temperature of about $mv_p^2/2$, an estimate based on the energy of an electron traveling at the phase velocity, v_p , of the unstable plasma wave. For densities near $0.25 n_{cr}$, the two-plasmon decay instability also becomes important. The effect of this instability, which has the same maximum growth rate as the Raman, is that a much larger spectrum of plasma waves is unstable. Here, our simulations with large regions of underdense plasma and a background electron temperature of 3 keV (see "Heating and Hot-Electron Generation in Underdense Plasmas" in this section) indicate that the heated electron temperature, Θ_h , in keV is about $8 \times 10^{-4} (I\lambda_\mu^2)^{1/3}$, where I is the laser light intensity in W/cm^2 and λ_μ is the wavelength in μm . An explicit dependence on the background plasma temperature is also expected and is currently under investigation.

Our ability to calculate Brillouin scattering continued to improve. Our most recent calculations^{45,46} emphasize that velocity and density gradients and the structure of the noise source from which the scatter grows often play a very important role in current experiments. Experiments at UCLA⁴⁷ on Brillouin scatter of microwaves have provided valuable information on the nonlinear regime. The reflectivity was observed to saturate with intensity at a level that was in quite good agreement with our nonlinear theory.⁴⁸ This theory invokes the formation of ion tails, and the formation of such ion tails was directly observed in these experiments. Laser experiments with well-diagnosed plasma conditions and an improved understanding of the angular distribution of the scatter are needed to improve our calculations of the scattering.

Finally, we have continued our investigations of other plasma processes that can affect the laser-plasma coupling. Filamentation continues to appear as potentially quite important, since this process can greatly increase the intensity of

the light. Experimental evidence^{49,50} for filamentation is beginning to accumulate. Ion turbulence, caused by a wide variety of processes (even parametric instabilities), is being more extensively examined as an absorption mechanism in underdense plasma with a density near $0.5 n_{cr}$. Finally, experiments with shorter-wavelength light are being used to test and improve our understanding of electron transport.

Author: W. L. Kruer

Laser Plasma Coupling in Reactor-Size Targets

There is considerable interest in the intensity-wavelength window for obtaining good inverse bremsstrahlung (collisional) absorption of laser light while minimizing collective effects that can degrade the quantity or quality of the absorption. We present here an overview of coupling processes that can be significant in the large regions of underdense plasma expected in reactor-size targets. Simple estimates are given for the intensity-wavelength regimes⁵¹ in which the different processes can be important. Although these estimates are rather crude, they serve to illustrate the region of parameter space in which optimum coupling can be expected.

A very important characteristic of a reactor target is the large size of the underdense plasma. The characteristic size, R , is typically on the order of 0.5 cm, which corresponds to many thousands of laser-light wavelengths for 1- μm light. The peak intensity of the light used to drive the target can vary considerably with the details of the design. Typically, the peak intensity is in the range of 10^{14} to $10^{16} W/cm^2$.

Both the absorption efficiency and the heated velocity distribution are crucial features of the laser-target coupling. Optimum conditions are to directly heat as many electrons as possible and, in particular, to avoid the generation of extremely energetic tails of hot electrons, which have a long range and can preheat the inner fuel. Preheat is a very important issue, since it can preclude achievement of the very large

compressions⁵² needed for ignition and burn. In practice, less than 0.1% of the input energy can be allowed to end up as preheat in the fuel. Depending upon details of the target design, electrons with energies $\lesssim 200$ to 500 keV can preheat the fuel. If an appreciable number of such electrons are generated, thicker ablators are required, which increases the energy needed to drive the target.

Inverse Bremsstrahlung Absorption. The optimum absorption mechanism is also the simplest—inverse bremsstrahlung absorption. To a plasma physicist, inverse bremsstrahlung is just collisional heating. As electrons oscillate in the electric field of the laser light, they are randomly scattered by the ions. Coherent energy of oscillation is thereby converted into random thermal energy. The heating rate is then the oscillatory energy times the electron-ion collision frequency, ν_{ei} . By conservation of energy, this heating represents a damping of the light wave. Hence,

$$\frac{\nu E_L^2}{8\pi} = \nu_{ei} n m \frac{v_{os}^2}{2}, \quad (8)$$

where $v_{os} = eE_L/m\omega_0$, n is the plasma density, E_L (ω_0) is the electric field (frequency) of the light, and ν is an effective collision frequency that describes the damping of the light wave. This damping rate is then⁵³

$$\nu = \frac{n}{n_{cr}} \nu_{ei} \approx 3 \times 10^{-6} \ln \Lambda \frac{nZ}{\theta_{ev}^{3/2}} \frac{n}{n_{cr}}, \quad (9)$$

where Z is the ion charge state, θ_{ev} is the electron temperature in eV, and Λ is the usual expression determined by the minimum and maximum cut-off parameters. Note that ν has dependences that are characteristic of the properties of Coulomb collisions; i.e., ν increases with density and charge state and decreases as the plasma heats. The absorption length is the velocity of light divided by ν . It is apparent that this absorption can be very high in large regions of underdense plasma.

Inverse bremsstrahlung produces “soft” heated distributions; i.e., the slow particles are preferentially heated, since the electron-ion collision frequency varies as

v^{-3} , where v is the velocity of an electron. In fact, the heated-electron distribution can fall off with velocity even faster than does a Maxwellian distribution. This occurs if the rate at which electrons gain energy by collisional absorption ($\nu_{ei} v_{os}^2$) exceeds the rate at which this energy is equilibrated by electron-electron collisions ($\nu_{ee} v_e^2$); if $Z v_{os}^2 / v_e^2 > 1$. Here, ν_{ee} is the electron-electron collision frequency, and v_e is the electron thermal velocity. In this limit,⁵⁴ a super-Gaussian heated distribution is generated: $f \sim \exp(-v^5/u^5)$, where u is a velocity characteristic of the collisional heating.

The intensity-wavelength window for efficient inverse bremsstrahlung absorption can be estimated rather simply. The condition that the absorption be $\lesssim 70\%$ is that the size, R , of the underdense plasma be greater than an absorption length, $\nu_{ei} R / c > 1$. We next relate the plasma temperature to the laser-light intensity via a free-streaming estimate that allows for moderately inhibited electron transport,⁵⁵ i.e., $I \approx 0.1 n \theta_e v_e$. Combining these estimates gives a bound on the intensity in W/cm^2 ,

$$I \lesssim 5 \times 10^{14} \frac{ZR(\text{cm})}{\lambda_\mu^4}, \quad (10)$$

where Z is the ion charge, R is the plasma size in cm, and λ_μ is the laser-light wavelength in micrometres. For reactor targets, $R \lesssim 0.5$ cm; hence, $I \gtrsim 2.5 \times 10^{14} Z / \lambda_\mu^4$, which is a readily accessible intensity for target design using lasers with $\lambda_\mu \leq 1$. The wavelength enters so strongly since $\nu_{ei} \sim n / \theta_e^{3/2}$. As the wavelength decreases, the light propagates through denser, and cooler, plasma.

Recent experiments^{56,57} with 0.5- to 0.25- μm light are quite consistent with our simple estimates of inverse bremsstrahlung absorption. For example, in LLNL experiments (see “Analysis and Summary of Wavelength Scaling Experiments and Comparisons with Simulations” in Section 7) in which gold targets were irradiated with 0.5- μm light, the measured absorption was $\geq 70\%$ for $I \gtrsim 3 \times 10^{15} \text{ W}/\text{cm}^2$. If we estimate an ion charge state of 30 and a plasma size of $\sim 100 \mu\text{m}$ for these experiments, Eq. (10) gives $I \leq 2 \times 10^{15} \text{ W}/\text{cm}^2$. When Be ($Z = 4$) targets were irradiated, the absorption dropped below

70% for an intensity which was about a factor of 10 lower, again as expected. These are very promising results, indicating that there is a very significant classical regime available for target design using short-wavelength lasers. Of course, it is important to carry out experiments with larger regions of underdense plasma to test if other coupling mechanisms impose additional restrictions on the laser-light intensity.

Collective Effects on the Coupling. This naturally brings us to a discussion of the other coupling mechanisms, which are related to collective plasma effects. It is well known that, due to the long range of the Coulomb force, a plasma supports waves. These are collective modes of oscillation that correspond to charge-density fluctuations. In laser fusion applications, there are primarily two plasma waves of interest. The first is a high-frequency electron plasma wave that occurs at the natural frequency with which electrons oscillate. The second is a low-frequency ion acoustic wave that is the analog of a sound wave in an ordinary gas. The important point is that the laser light can excite these waves, which, in turn, can heat the plasma or scatter the light. In other words, collective effects can either increase or decrease the absorption.

Just as importantly, collective processes can change the character of the absorption. We have already pointed out that collisional absorption generates soft heated velocity distributions. In marked contrast, absorption via plasma waves typically leads to suprathermal electron generation. Consider an electrostatic wave with an electric field, $E \sin(kx - \omega t)$. Slow electrons just experience an oscillatory motion that, in the absence of collisions, leads to no heating. However, fast electrons (i.e., those with $v \sim \omega/k \gg v_e$) see a nearly constant field and can be efficiently accelerated. Hence, faster electrons are preferentially heated, leading to a heated velocity distribution characterized by energetic tails.

Resonance Absorption. Resonance absorption is the simplest example of absorption via plasma waves. The physics of this coupling is straightforward. Consider a plasma with density, $n(x)$, and a high-frequency electric field, $E_L \sin \omega_0 t$, that oscillates electrons along the density gradient. This oscillation clearly generates a

charge-density fluctuation, δn , at frequency ω_0 ,

$$\delta n = n(x + x_{os}) - n(x) = x_{os} \cdot \nabla n, \quad (11)$$

where $x_{os} = -eE/m\omega_0^2 \cos \omega_0 t$. Hence, whenever a component of the laser-light electric field, E_L , oscillates electrons along a variation in density, a charge-density fluctuation is directly driven. Near the critical density, this driven fluctuation is at just the frequency at which the plasma naturally responds, so an electron plasma wave is resonantly excited. For high-intensity light, the plasma wave grows in amplitude until it saturates by accelerating electrons, producing energetic tails. Note that resonance absorption takes place whenever $E_L \cdot \nabla n \neq 0$, i.e., for so-called p-polarized light.

Since resonance absorption operates on the zero-order density gradient due to plasma expansion, it is a fairly ubiquitous phenomena and has been the subject of many calculations.⁵⁸⁻⁶⁰ Although resonance absorption is basically a linear process, nonlinear effects play a crucial role in the heating. Important features predicted quite some time ago were

- Nonlinear steepening of the density profile near the critical density due to the pressure of the locally generated plasma wave and the reflecting light wave.
- Polarization-dependent absorption, which is partially reduced by critical-surface rippling.
- An absorption efficiency of typically about 20 to 30% when averaged over the rippled surface.
- Heated electrons in a quasi-Maxwellian distribution with temperature $\theta_h \propto (I\lambda_0^2)^{0.4}$ (Ref. 59), where I is the intensity of the light and λ_0 is the wavelength.

Resonance absorption is clearly less of an issue for short-wavelength lasers both because less energy is resonantly absorbed when inverse bremsstrahlung reduces the amount of light reaching the critical surface and because the resonantly heated electron temperature decreases.

The calculations of resonance absorption have been supported by many different experiments⁶¹ with high-intensity laser light and small underdense plasmas. Of particular interest to the issue of wavelength scaling are

recent experiments⁵⁶ at Ecole Polytechnique with 1-, 0.5-, and 0.25- μm laser light. High-energy x-ray data from these experiments indicate that the resonantly heated electron temperature scales as $(I\lambda_0^2)^{0.46}$. Both the magnitude of the temperature and its scaling appear to be in quite reasonable agreement with calculations.

Plasma Instabilities. In the large regions of underdense plasma that are characteristic of reactor targets, collective effects can become considerably more complex for intense laser light, primarily because plasma waves are also excited by instabilities.⁶² As shown in Table 3-4, most of these instabilities can be most simply described as the resonant decay of the laser light into two other waves. The frequency-matching conditions then determine the region of plasma density for which the various instabilities occur. The ion acoustic-decay instability, which corresponds to decay of the light wave into an ion acoustic wave and an electron plasma wave, takes place near the critical density, n_{cr} . If the product waves are two electron plasma waves, we have the two-plasmon-decay ($2\omega_{\text{pe}}$) instability, which occurs near $0.25 n_{\text{cr}}$. The Raman instability represents the decay of the light wave into a scattered light wave and an electron plasma wave, a process that occurs for $n \gtrsim 0.25 n_{\text{cr}}$. The analogous scattering process, in which the electron plasma wave is replaced by an ion acoustic wave, is called the Brillouin instability; this instability operates throughout the underdense plasma. Finally, there is the filamentation instability, a process that also occurs for $n \lesssim n_{\text{cr}}$. Any local increase in the laser-light intensity pushes plasma aside, forming a density depression that, by refracting the light rays inward, further enhances the intensity. The net result can be the breakup of the incident light beam into intense filaments. Self-focusing of the entire light beam is a subset of this instability.

Table 3-4. Principal instabilities that can be driven by laser light propagating in plasma.

Resonant coupling of laser light into two other waves	
• Ion-acoustic decay instability	$\omega \rightarrow \omega_{\text{pe}} + \omega_{\text{ia}}$ at $n \approx n_{\text{cr}}$
• Two-plasmon decay instability	$\omega \rightarrow \omega_{\text{pe}} + \omega_{\text{pe}}$ at $n \approx 0.25 n_{\text{cr}}$
• Raman instability	$\omega \rightarrow \omega_{\text{sc}} + \omega_{\text{pe}}$ at $n \lesssim 0.25 n_{\text{cr}}$
• Brillouin instability	$\omega \rightarrow \omega_{\text{sc}} + \omega_{\text{ia}}$ at $n \lesssim n_{\text{cr}}$
Filamentation light	at $n \lesssim n_{\text{cr}}$
NOTE: ω_{pe} is electron plasma frequency; ω_{ia} is ion acoustic frequency; and $\omega(\omega_{\text{sc}})$ is frequency of incident (scattered) light wave.	

Raman and $2\omega_{\text{pe}}$ Instabilities. Wherever one of the product waves is an electron plasma wave, very energetic electrons can be generated. The ion acoustic-decay instability tends to be limited by the steepening of the density profile near the critical density, since it is most efficient quite near there. Of particular concern for hot-electron generation are the two-plasmon-decay instability ($n \approx 0.25 n_{\text{cr}}$) and the Raman instability, which produces its most energetic electrons near $0.25 n_{\text{cr}}$. Computer simulations^{63,64} of these instabilities in large regions of plasma with density near $0.25 n_{\text{cr}}$ show more than 10% absorption into electrons with a characteristic temperature on the order of 100 keV.

Both these instabilities have now been observed in experiments.^{65,66} For example, when disks were irradiated at LLNL⁶⁶ with a 1-ns pulse of 1.06- μm light at $I \sim 10^{16}$ W/cm², scattered light with wavelengths of ~ 1.5 to $2 \mu\text{m}$ was observed. Such light is a signature of Raman scatter. The signal levels indicated that only a fraction of a percent of the incident laser light was being affected, but we expect higher signals with the larger underdense plasmas of the future. Supporting these expectations are very recent experiments with gold disks in which a 2-ns pulse of 1.06- μm light was focused to a spot of about 1 mm; the observed signal due to Raman scatter corresponded to $\lesssim 1\%$ of the incident laser light.

The linear theory of these instabilities allows us to estimate their threshold intensities as a function of laser-light wavelength. As a first approximation, the minimum threshold intensity is generally set by the density gradient, which limits the region over which the resonant coupling can be satisfied. The threshold is given by

$$I_T \sim 10^{13} \frac{\theta_{\text{ev}}}{L_{\mu} \lambda_{\mu}} \quad (12)$$

and

$$I_T \sim 5 \times 10^{17} \frac{1}{L_{\mu}^{4/3} \lambda_{\mu}^{2/3}} \quad (13)$$

for the $2\omega_{\text{pe}}$ instability and for the Raman instability, respectively. Here I_T is the intensity in W/cm², θ_{ev} is the electron

temperature in eV, and L_μ (λ_μ) is the local-density gradient length (laser-light wavelength) in micrometres. Note that, for $L_\mu \sim 5 \times 10^3$, the threshold intensities are rather low ($\sim 10^{13}$ W/cm²), even for 0.25- μ m light. Fortunately, collisional absorption can raise the threshold intensity for short-wavelength light. A crude estimate is that the maximum gradient length to be used in the threshold condition is the inverse bremsstrahlung absorption length for light propagating to that density. If we apply this condition to the $2\omega_{pe}$ instability, which has a threshold lower than Raman near $0.25 n_{cr}$, provided that $\theta_{ev} \gtrsim 5 \times 10^4 (\lambda_\mu/L_\mu)^{1/3}$, we obtain

$$I_T \sim 3 \times 10^{13} \frac{Z}{\theta_{ev}^{1/2}} \frac{1}{\lambda_\mu^3} \quad (14)$$

For 0.5- μ m light in a high-Z plasma, this threshold intensity is $\sim 3 \times 10^{14}$ W/cm². For a high-Z plasma irradiated with short-wavelength light, this estimate is conservative, since collisions also directly damp the unstable waves.⁶⁷ How much we can exceed the threshold intensity before the onset of severe preheat is a nonlinear question not well resolved.

Brillouin and Filamentation Instabilities.

There is concern that plasma instabilities, in addition to producing very energetic electrons that can preheat the target, can significantly degrade the absorption. Here, the principal culprit is the Brillouin instability, which represents the resonant decay of the incident light wave into a scattered light wave and an ion acoustic wave. Since the ion sound frequency is much less than the light-wave frequency, the Manley-Rowe relations show that nearly all of the energy of the incident photons can be transferred to scattered photons. Hence, if this instability were efficient, most of the laser-light energy could be scattered away from the target.

We note that the scattered light may still be absorbed before it leaves the plasma. This is particularly true for light that is side-scattered in a high-Z plasma. Calculations of Brillouin backscatter are representative and indicate two complementary limits. For high-intensity light (i.e., for an intensity far above instability threshold), the reflectivity is primarily just a function of the amount of

plasma traversed,⁶⁸ i.e., $r = f(n/n_{cr}, L/\lambda_o)$. Reflectivities of 50% or more have been computed for large underdense plasmas ($L/\lambda_o \sim 10^2$ to 10^3). For low-intensity light that is near instability threshold, and for moderately damped ion waves, the instability can be described as convective growth with spatial gain rate K , given by

$$K \approx \frac{\pi}{2} \frac{1}{\lambda_o} \left(\frac{v_{os}}{v_e} \right)^2 \frac{n}{n_{cr}} / \left[\frac{\nu_i}{\omega_i} \left(1 + \frac{3}{Z} \frac{\theta_i}{\theta_e} \right) \right] \quad (15)$$

where $\nu_i(\omega_i)$ is the ion-wave damping rate (frequency), and $\theta_i(\theta_e)$ is the ion (electron) temperature.

A number of different experiments^{69,70} indicate that sizable Brillouin scatter is possible for high-intensity light in large underdense plasmas. For example, in experiments at NRL⁶⁹ with 1.06- μ m light at $I \sim 10^{16}$ W/cm², about 40% of the light was back reflected when a prepulse was used to prepare a sizable region of underdense plasma. In these experiments, the frequency shift, intensity dependence of the reflectivity, and ray-retrace properties of the reflected light confirmed that Brillouin scatter was responsible for the enhanced backscatter.

The filamentation instability is similar to the Brillouin instability in that the response of the plasma ions to the light wave is the crucial feature. Not surprisingly, filamentation has a similar spatial gain coefficient,

$$K_F \approx \frac{\pi}{2} \frac{1}{\lambda_o} \frac{n}{n_{cr}} \left(\frac{v_{os}}{v_e} \right)^2 / \left(1 + \frac{\theta_i}{Z \theta_e} \right) \quad (16)$$

Note that K_F differs from K_{BS} by the factor ω_i/ν_i , which represents the resonance associated with the ion acoustic wave. When the ion wave due to the Brillouin instability is heavily damped, the two instabilities have about the same gain length, as expected physically. Until quite recently,⁷¹ there has been little direct experimental information on filamentation in laser-produced plasmas.

Finally, a crude estimate of the threshold intensities for the Brillouin and filamentation instabilities can be given. A common treatment of the two instabilities will be used in this estimate, since we postulate that, in the low-intensity regime, the ion and electron

temperatures are comparable and the ion waves are moderately damped. This assumption is best for low- Z plasmas irradiated with short-wavelength light, but we note that a fair conservatism is built into the estimate (only one instability gain length is allowed, and the effect of gradients on the Brillouin instability is ignored). To be specific, we assume a simple model for a uniformly irradiated, spherically expanding underdense plasma,

$$n = n_{cr} \left(\frac{r_c}{r} \right)^2 \quad (17)$$

and

$$I = I_0 \left(\frac{r_c}{r} \right)^2, \quad (18)$$

where r_c is the radius of the critical surface and, again, we model the electron transport by $I \approx 0.1 n \theta_e v_e$. The threshold intensity is then estimated by simply requiring inverse bremsstrahlung absorption before a growth length for filamentation is accumulated, i.e.,

$$\int \frac{n}{n_{cr}} \left(\frac{v_{os}}{v_e} \right)^2 \frac{dr}{\lambda_0} = 1 \quad (19)$$

This condition on intensity becomes

$$I_0 = 10^{14} \left(\frac{Z}{26} \right)^{3/4} \frac{1}{\lambda_{\mu}^{11/4}}, \quad (20)$$

where I_0 is the intensity in W/cm^2 for $0.33\text{-}\mu\text{m}$ light and $Z = 3$, $I \sim 4 \times 10^{14} \text{ W}/\text{cm}^2$.

Summary. We have given a brief overview of important laser-plasma coupling processes and have estimated the intensity-wavelength regime in which the various processes can be significant. If we use short-wavelength laser light, collisional absorption is quite potent over a substantial range of intensities. Recent experiments with short-wavelength light and small underdense plasmas indeed show a significant regime of high absorption. Minimizing collective effects in reactor-size plasmas can impose more substantial restraints on the intensity. However, there still appears to be a regime for target design in which collisional absorption is high and collective effects are minimized. Our current estimates indicate

that this regime is accessible with short-wavelength ($\sim 0.5\text{-}$ to $0.25\text{-}\mu\text{m}$) laser light at an intensity on the order of $10^{14} \text{ W}/\text{cm}^2$. Clearly, further experiments are needed to more quantitatively define this very promising intensity-wavelength window for laser fusion applications.

Author: W. L. Kruer

Heating and Hot-Electron Generation in Underdense Plasmas

We report on our ongoing study⁷² of electron heating due to the high-frequency instabilities at and below quarter-critical density for parameters appropriate to present and projected laser fusion experiments. Specifically, we are studying the $2\omega_{pe}$ instability, in which the incident electromagnetic wave at frequency ω decays into two electron plasma waves; and the Raman instability, in which the decay waves are a plasma wave and an electromagnetic wave. From the frequency-matching conditions, the $2\omega_{pe}$ instability occurs near quarter-critical density, and the Raman instability occurs at or below quarter-critical density.

There is a considerable literature on both instabilities encompassing both analytical results⁷³ and simulation studies.^{74,75} Our earlier simulation studies⁷⁴ were directed towards high intensities and steep density profiles. Current experiments at laser wavelengths of $1\text{ }\mu\text{m}$ and below have longer pulse lengths and more moderate intensities, and the incident laser light traverses large regions of relatively flat, underdense plasma. For reactor targets, we envision more than 1000 free-space wavelengths of underdense plasma. Our present work explores that parameter regime.

The generation of very-high-energy electrons by $2\omega_{pe}$ and Raman instabilities is a major concern for target designs. Both short- and long-pulse experiments are characterized by underdense background electron temperature in the 1- to 10-keV range. At these high background temperatures, Landau damping limits the decay plasma-wave spectrum to high-phase-velocity waves, from

which it is straightforward to estimate suprathermal electron temperatures ≥ 100 keV. As we proceed to the large underdense plasmas of reactor-sized targets, we expect increased absorption into this unwelcome high-energy electron component, since these instabilities have a larger volume in which to operate.

We present results from kinetic simulations⁷⁶ in both one and two spatial dimensions for the plasma density region at quarter-critical and below. In the 1.5-dimensional kinetic simulations, Raman back and forward scattering are isolated, and relatively long regions of underdense plasma may be studied. A major result of the 1.5-dimensional simulations^{77,78} is that the Raman instability generates a heated-electron distribution that is Maxwellian. The temperature of this heated distribution, T_{hot} , is determined principally by the phase velocity of the decay plasma wave. Therefore, T_{hot} from Raman scattering below quarter-critical density depends on density and temperature, but is roughly independent of the incident intensity.

In conjunction with the simulations, a model for these instabilities has been developed that is applicable to the convective regime below quarter-critical density. In this Raman model, the electron distribution consists of a thermal Maxwellian and a self-consistent Maxwellian tail at temperature T_{hot} that Landau damps the plasma wave. The energy absorbed by the electrons from the damped plasma wave is balanced against the heat flux carried off by the hot electrons; this determines the density of the Maxwellian tail. The reflection from the damped plasma wave is computed by a procedure analogous to that used in the Brillouin model for reflection from damped ion waves.⁷⁹ The resulting model encompasses the 1.5-dimensional simulations of Raman backscatter below quarter-critical density.

Several interesting features emerge from this study. If the finite background temperature is high enough, the scattered light may be red-shifted,⁷⁷ a result not contained in the cold-plasma treatment of Raman scattering. For example, at 10 keV for $n/n_c = 0.15$, the backscattered light is at frequency $\omega_s = 0.49 \omega$, rather than 0.61ω . Also, long regions of underdense plasma are needed for significant Raman scattering. A typical 1.5-dimensional simulation result

yields 10% reflection for 127 free-space wavelengths of⁸⁰ simulated plasma at density $0.1 n_c$ and temperature 1 keV. Therefore, the Raman instability is expected to become more significant as experiments progress to larger regions of underdense plasma.

Landau damping of the decay plasma wave limits Raman backscattering for low plasma densities and high background temperature. Under these conditions, forward Raman scattering then dominates in the 1.5-dimensional kinetic simulations of large, flat plasma slabs.⁷⁸ For a slab $254 \lambda_0$ long at density $0.1 n_c$ and temperature 10 keV, the simulation shows 25% absorption due to forward scattering and the production of energetic electrons out to energies of millions of electron volts. (However, as discussed below, the high-intensity threshold for forward scattering fortunately reduces its role in experiments.)

With two-dimensional kinetic simulations using ZOHAR,⁷⁶ we complement and extend the model of Raman backscattering. Here, we are concerned with a richer spectrum of decay plasma waves and a more complex instability saturation mechanism.

First, as expected, if there is a large region of plasma below quarter-critical density, we find considerable Raman backscatter, even in the presence of the $2\omega_{pe}$ instability. For a simulation in two dimensions that includes Raman backscattering, we consider a plasma slab with a linear density gradient from 0.195 to $0.235 n_c$ in $25 \lambda_0$, corresponding to a density scale length to critical of $580 \lambda_0$. The background electron temperature is 3 keV, $ZT_e/T_i = 3$, and the incident laser intensity is $3 \times 10^{15} \text{ W/cm}^2$ for $1\text{-}\mu\text{m}$ light. We find a T_{hot} of 90 keV and 8% reemission in the $\omega/2$ signal. Both the Raman model and the corresponding one-dimensional simulation predict $T = 75$ keV and 13% emission into $\omega/2$. Thus, when both Raman and $2\omega_{pe}$ instabilities occur, the Raman model underestimates the heated-electron spectrum and overestimates the $\omega/2$ emission. As we include more of the region below quarter-critical density, the Raman model becomes more applicable.

To explore the intensity dependence of T_{hot} , we looked at a set of simulations that include two-dimensional effects. We studied a flat plasma slab close to quarter-critical density (specifically, at $0.23 n_c$). This slab is $21 \lambda_0$ long, the background electron

temperature is 3 keV, $ZT_e/T_i = 3$, and v_0/c varies from 0.03 to 0.07. These limits correspond to intensities from 1×10^{15} to 6×10^{15} W/cm² for 1- μ m light, and, in this range, $v_0/v_e < 1$, where v_e is the electron thermal velocity.

For this parameter regime, the linear growth phase⁸⁰ of the $2\omega_{pe}$ instability and the initial saturation are relatively well understood. The expected modes grow, and the growth rate is $\sim 0.3 \gamma_{\max}$, where $\gamma_{\max} = k_0 v_0/4$, again in agreement with the detailed linear theory.

These simulations illustrate the role of the ions in saturating the high-frequency instabilities. The initial saturation is accompanied by a rapid increase in the ion energy, and the electrostatic energy then drops. We ascribe these features to the saturation mechanism identified in detail in Ref. 74. The beating of the high-frequency instability decay waves drives up ion fluctuations. These ion fluctuations then couple the electron plasma decay waves to shorter-wavelength, more strongly damped perturbations. This mechanism should lead to a softer spectrum of heated electrons than the one predicted from the phase velocities of the $2\omega_{pe}$ decay waves.

In all the kinetic simulations, the heated-electron distribution is roughly Maxwellian. Near quarter-critical density, T_{hot} is intensity dependent, with $T_{\text{hot}} \propto (I\lambda_0^2)^{1/3}$. As normalization, at 3×10^{15} W/cm² for 1- μ m light, the simulation result for T_{hot} is 110 keV. For current parameters, the T_{hot} due to the high-frequency instabilities in the neighborhood of quarter-critical density is at least a factor of 2 higher than the temperature commonly ascribed to resonance absorption for the same irradiation conditions.

The two-dimensional kinetic simulations confirm that the amount of $\omega/2$ that is detected is an underestimate of the

absorption by the high-frequency instabilities in the quarter-critical density region. First, for flat slabs near quarter-critical density, the absorption is a weak function of intensity. At 3×10^{15} W/cm², the 40% absorption far exceeds the 0.5% $\omega/2$ emission. And even for the slab extending below quarter-critical density, 8% of the incident light returns as $\omega/2$ emission, while 32% of the incident energy appears in the heated-electron distribution.

This lack of a direct estimate of absorption from the $\omega/2$ emission occurs for two reasons, neither of which can be addressed in the 1.5-dimensional simulations. The $2\omega_{pe}$ instability is an absorption mechanism at quarter-critical density unaccompanied by direct $\omega/2$ emission. Furthermore, the decay $\omega/2$ may be reabsorbed, since this electromagnetic wave is produced near its critical density.

We need the intensity thresholds of these high-frequency instabilities to incorporate our simulation results into the planning and interpretation of experiments. For most experiments to date, gradient stabilization is the main instability saturation mechanism. In this context, the instability thresholds in Table 3-5 are for a linear density gradient, L_μ , from zero to critical, expressed in μ m. The laser wavelength, λ_μ , is also given in μ m, and the background electron temperature, T_e , is in keV.

Of the instabilities considered, forward Raman scattering has the highest threshold. Raman backscattering, the subject of the 1.5-dimensional simulations and the model described earlier, also has a rather high intensity threshold. However, many of the ideas in that study apply to Raman sidescattering, which is more accessible experimentally.

For these high-frequency instabilities, $2\omega_{pe}$ usually has the lowest intensity threshold. The ordering given is most applicable to short-pulse, high-intensity experiments; however, if the background electron temperature is high enough, and if the density profile is shallow enough, Raman sidescattering may have a lower intensity threshold than $2\omega_{pe}$.

For long laser pulses and moderate intensities, competition with inverse bremsstrahlung absorption becomes significant, and we can compute a minimum intensity below which each of these high-frequency instabilities will not occur. For

Table 3-5. Intensity thresholds for linear density gradient.

$2\omega_{pe}$:	$k_0 L \left(\frac{v_0}{v_e} \right)^2 > 48 \frac{\sqrt{3}}{2} \rightarrow I > \frac{1.77 \times 10^{16} T_e}{\lambda_\mu L_\mu} \text{ W/cm}^2$
Sidescatter and Raman at absolute pressure and temperature:	$k_0 L \left(\frac{v_0}{c} \right)^{3/2} > 8 \rightarrow I > \frac{1.88 \times 10^{18}}{(\lambda_\mu)^{2/3} L_\mu^{4/3}} \text{ W/cm}^2$
Backscatter below $n_c/4$ (convective):	$k_0 L \left(\frac{v_0}{c} \right)^2 > 8 \rightarrow I > \frac{1.74 \times 10^{18}}{\lambda_\mu L_\mu} \text{ W/cm}^2$
Forward scatter needs very long density gradients:	$k_0 L \left(\frac{v_0}{c} \right)^2 > 8 \left(\frac{\omega_0}{\omega_{pe}} \right)^2 \rightarrow I > \frac{1.74 \times 10^{18}}{\lambda_\mu L_\mu} \frac{n_c}{n} \text{ W/cm}^2$

this preliminary estimate, we suppose a linear density gradient and constant temperature in the underdense plasma, and we assume that gradient stabilization is the main instability saturation mechanism. We then find a minimum intensity as a function of laser wavelength.

Consider first the $2\omega_{pe}$ instability that is localized to the quarter-critical density region. If there is a steep profile, there is negligible inverse bremsstrahlung before quarter-critical density is reached. The incident intensity is approximately equal to the intensity at quarter-critical density and has to exceed the gradient stabilization threshold (given in Table 3-5) for the instability to occur. As the density gradient becomes longer, the instability will occur at lower incident intensity. Most experiments to date have occurred in this parameter regime.

In the opposite limit of an extremely shallow profile, there is presumably significant absorption by inverse bremsstrahlung before quarter-critical density is reached. The $2\omega_{pe}$ will then occur only if enough intensity remains at quarter-critical density to exceed the gradient stabilization threshold condition. For this limit, as the gradient increases, the threshold intensity also increases. Therefore, there is a gradient scale length that corresponds to the lowest intensity required for the instability to occur. The intensity is at this minimum when the gradient scale length is approximately equal to the inverse bremsstrahlung absorption length. For typical high-Z irradiations with 1- μ m light, this intensity minimum occurs for scale lengths in the 500 to 600 μ m range. We emphasize that most experiments to date do not have underdense scale lengths long enough to be in this parameter regime. Instead, for current irradiations, the gradient stabilization threshold should be used to predict the onset of the $2\omega_{pe}$ instability.

Similar arguments may be applied to Raman scattering. Then, for the high-frequency instabilities at quarter-critical density, we find the intensity thresholds given in Table 3-6. Again, these are minima below which the indicated instability will not occur; they are not predictors of instability onset for current experiments with their relatively steep density profiles. However, this exercise does give estimates of threshold intensities as functions of incident laser wavelength and background temperature for

long-scale-length irradiations. Both $2\omega_{pe}$ and Raman sidescattering are possible in future green-light irradiations in the intensity range of 10^{14} to 10^{15} W/cm².

Collisional damping of the $2\omega_{pe}$ and Raman instabilities is a significant stabilization mechanism for moderate-intensity irradiations of high-Z disks. We estimate this effect by evaluating the product

$$\gamma_{\max}\tau_{ei} \sim 14(I_{14})^{1/2} \lambda_{\mu}^2 T_e^{3/2} Z^{-1}, \quad (21)$$

where τ_{ei} is the electron-ion collision time, T_e is in keV, and I_{14} is the incident intensity in units of 10^{14} W/cm². As an example, consider an underdense plasma with $T_e = 3$ keV and $Z = 50$ that is irradiated by 1- μ m laser light at 10^{15} W/cm². In the two-dimensional simulations, $\gamma \sim 0.3 \gamma_{\max}$ and, then, $\gamma\tau_{ei} \sim 1.7$.

We generally find less stringent threshold intensities if we assume that collisional damping, rather than gradient stabilization, is the dominant instability saturation mechanism. Note, however, that collisional damping does lead to a stronger wavelength dependence, with $I \sim \lambda_{\mu}^{-4}$.

The quarter-critical density region is receiving increased experimental attention. Following some early experiments,⁸¹ there is now renewed interest in the detection of scattered light with frequency $\omega/2$. The larger underdense plasmas in present-day irradiations make it more likely that significant $\omega/2$ emission will be observed. Also, for incident light in green (2ω) and blue (3ω) wavelengths, the $\omega/2$ emission is much easier to detect experimentally. Ongoing efforts are underway at LLNL⁸² and at the Rutherford Laboratory.⁸³

The $2\omega_{pe}$ instability has been studied extensively by a group at the National Research Council of Canada.^{84,85} Two years ago, they observed profile steepening at quarter-critical density,⁸⁴ as predicted from the simulations of the $2\omega_{pe}$ instability.⁷⁴ Now

Table 3-6. Intensity thresholds for high-frequency instabilities.

Instability	Threshold in W/cm ² , where T_e is in keV	$Z = 3$ $T_e = 3$ keV	$Z = 50$ $T_e = 7$ keV
$2\omega_{pe}$	$I > \frac{9 \times 10^{11} Z}{\lambda_{\mu}^3 T_e^{1/2}}$	$\frac{1.6 \times 10^{12}}{\lambda_{\mu}^3}$	$\frac{1.7 \times 10^{13}}{\lambda_{\mu}^3}$
Sidescatter Raman at $n_c/4$	$I > \frac{9.8 \times 10^{11} Z^{4/3}}{\lambda_{\mu}^{11/3} T_e^2}$	$\frac{4.7 \times 10^{11}}{\lambda_{\mu}^{11/3}}$	$\frac{3.6 \times 10^{12}}{\lambda_{\mu}^{11/3}}$
Backscatter below $n_c/4$	$I > \frac{3.3 \times 10^{13} Z}{\lambda_{\mu}^3 T_e^{3/2}}$	$\frac{1.9 \times 10^{13}}{\lambda_{\mu}^3}$	$\frac{8.9 \times 10^{13}}{\lambda_{\mu}^3}$

they have the first direct experimental evidence for hot-electron generation by the $2\omega_{pe}$ instability.⁸⁵ They used a CO₂ laser in the 10^{14} -W/cm² range to irradiate cold (100 to 200 eV) plasmas of known maximum density and then detected hot electrons in the 35- to 400-keV range. There is a unique identification of the $2\omega_{pe}$ instability in the correlations made with hot-electron production. As expected for the $2\omega_{pe}$ instability in cold plasmas, the hot-electron emission peaks at 45° with respect to the incident beam in both the forward and backward directions. The characteristic hot-electron emission pattern is confined to the plane of polarization of the incident light, as predicted. If the maximum plasma density is 0.1 n_c , the emission pattern disappears. Further, this hot electron production is correlated with $3\omega/2$ emission, the usual experimental signature of the $2\omega_{pe}$ instability.

In summary, absorption by the high-frequency instabilities that occur at and below quarter-critical density produces a heated-electron distribution that is Maxwellian with $T_{hot} \propto (I\lambda_0^2)^{1/3}$ near quarter-critical density. The amount of $\omega/2$ detected serves only as a lower bound on the absorption by these high-frequency instabilities. Competition with inverse bremsstrahlung absorption and collisional damping reduce the potency of $2\omega_{pe}$ and Raman instabilities, especially for shorter-wavelength light.

Authors: B. F. Lasinski, A. B. Langdon, K. G. Estabrook, and W. L. Kruer

Theory and Simulation of One-Dimensional Raman Forward Scattering

The Raman instability is an important consideration for reactor-target design because these targets will be characterized by large regions of underdense plasma. The most critical feature of the Raman process is its ability to generate high-energy electrons, which may lead to significant preheat. Raman backscattering has been studied for some time⁸⁶⁻⁹¹ through simulations, theory,

and experiment. Recently, we have observed a longer wavelength instability in simulations with electrons heated to energies of millions of electron volts (Raman forward scattering). In this article, we present theoretical comparisons between the growth rates and wavelengths of both back and forward scattering. We find that, for large background temperatures, the back-scattering mode is highly damped, and the longer-wavelength forward scattering becomes comparable or dominant to backscatter. Fortunately, forward scatter is sensitive to the density gradient, and we describe thresholds.

Both forward and back Raman scattering⁸⁸⁻⁹⁰ are the parametric decay of an incident photon into a scattered photon plus a longitudinal electron plasma wave (epw) according to $\omega_0 = \omega_s + \omega_{epw}$. Wave-number matching requires $\omega_0/c(1 - n/n_{cr})^{1/2} \pm \omega_s/c(1 - \omega_{pe}^2/\omega_s^2)^{1/2} + k_{epw}$, where $\omega_{pe}^2 = \omega_{pe}^2 + 3k_{epw}^2(T_e/m_e)$, ω_0 (ω_s) is the angular frequency of the incident (reflected) light wave, ω_{epw} is the frequency of the electron plasma wave, k_{epw} is the wave number of the epw, and the $+$ ($-$) refers to forward (back) scattering. As can be seen from the frequency-matching condition, this process can occur for electron densities $n \leq n_{cr}/4$, where n_{cr} is the critical density. Both forward and backscattering accelerate electrons in the direction of the incident laser beam. The back and forward refer to the direction of the scattered light. Since forward scattered light is still going in the general direction of the critical surface, the scattered light has a chance of being subsequently absorbed.

The simulations were 1.5- and 2-dimensional, kinetic (particle in cell), and electromagnetic and had relativistic electrons. The light-boundary condition allows the light to pass through each end as in vacuum. Particles leaving the boundary were reemitted back into the plasma with the initial temperature. Figure 3-20 shows the hot-electron distribution observed in a sample computer simulation with both back and forward scattering occurring. Note that there are three characteristic temperatures. The cold temperature was initially loaded into the simulation and represents the experimental "thermals." The next highest temperature is from the heating due to Raman backscattering and was discussed in

last year's annual report⁸⁷ and also in "Heating and Hot-Electron Generation in Underdense Plasmas" in this section. The highest temperature is due to Raman forward scattering. In "Heating and Hot-Electron Generation in Underdense Plasmas," two-dimensional simulations⁹² that include the $2\omega_{pe}$ instability are discussed.

The one-dimensional competition between Raman back and forward scattering is described by the linear theory plotted in Figs. 3-21 and 3-22. The back and forward scattering are found by solving $1 - Z'/(2k^2\lambda_D^2) = Z'_0/[8\lambda_D^2(c^2k^2 \pm 2kk_0c^2 \mp 2\omega\omega_0 - \omega^2)]$, where Z' is the Fried-Conte function, v_0 is the oscillatory velocity of the electron in the laser vacuum electric field, λ_D is the electron Debye length and k_0 is $\omega_0/c(1 - n/n_{cr})^{1/2}$. For $T_{cold} = 1$ keV (Fig. 3-21), the growth rate of forward scattering is several times less than for backscattering. It needs a longer system, higher v_{os} , longer time, or higher density to be significant. However, for large background temperatures, such as 10 keV (Fig. 3-22), the epw wavelength in backscattering is so short that electron Landau damping tends to make backscatter less competitive relative to forward scattering. The epw associated with Raman forward scattering is typically greater than a light wavelength and becomes longer as the plasma density decreases, resulting in a much higher heated-electron temperature.⁸⁸ The temperature is ~ 100 keV at $0.25 n_{cr}$ and ~ 800 keV at $0.1 n_{cr}$, as determined by the phase velocity of the wave.^{86,87} Fortunately, as seen in Figs. 3-21

and 3-22, the growth rate drops rapidly at the lower densities, where the highest temperatures are predicted.

In simulations of $n/n_{cr} = 0.1$, $T_e = 10$, length = $254 \lambda_0$, and $I\lambda_0^2\mu = 2.5 \times 10^{15}$, we have seen 25% absorption with energies out

Fig. 3-20. Particle number vs energy, showing the Maxwellian nature of the Raman-heated electrons.

Fig. 3-21. Linear theory for Raman scattering for cold electron temperature = 1 keV and $I(\lambda_0/1.06 \mu m)^2 = 10^{16}$ W/cm².

Fig. 3-22. Linear theory $\blacktriangle$ for Raman scattering for cold electron temperature = 10 keV and $I(\lambda_0/1.06 \mu\text{m})^2 = 10^{16} \text{ W/cm}^2$.

Fig. 3-23. Spectrum analysis of transmitted light from one-dimensional simulation.

to several million electron volts, mostly due to forward scattering, with more absorption at higher densities. Whereas the spectrum of backscattered light consists of mostly one peak,⁹¹ the spectrum of forward-scattered light has a cascade of peaks at $\omega_0 \pm m\omega_{epw}$, where m is an integer (Fig. 3-23) showing both the Stokes and anti-Stokes lines. This spectrum provides the best chance for experimentalists to clearly observe Raman forward scattering. However, the upshifted line could be confused with the $2\omega_{pe}$ line for forward scattering occurring at quarter-critical density. Probably the most conclusive evidence would come from a careful

experiment in which the density would be held below $0.25 n_{cr}$; the experimenter would look at the upshifted line or look for the downshifted line in the direction of the laser. Figs. 3-21(c) and 3-22(c) give the forward-scattered frequencies.

The nonlinear behavior of forward scattering is analogous to that of backscattering, as was discussed in last year's annual report.^{87,93} As with backscattering, the heated electrons increase the damping of the epw and, consequently, decrease the amplitude of the wave. Figure 3-24 shows this process in a phase space plot of the electron-distribution function. The laser enters from the left and, after $\sim 80 \lambda_0$, drives the forward scattering process out of the noise. The long wavelength modulations starting at $\sim 80 \omega_0$ represent the forward scatter, which is not heavily self-damped, since the heated electrons rapidly convect away. However, the last 90 wavelengths of plasma, which previously had vigorous forward scattering, now are mostly damped away by the electrons heated in the section closer to the laser. The initial absorption peaked at 94%, then decreased to an average of 26% as the self-consistent damping limited the absorption.

Fortunately, forward scattering is sensitive to the density gradient,⁹⁴ and simulations confirm the theoretically estimated threshold, where $I\lambda_0^2 \mu \lesssim 5 \times 10^{17} (n_{cr}/\langle n \rangle)^2 \times (\Delta n/n_{cr}) (\lambda_0/\Delta x)$, where the density changes by Δn in length Δx at average density $\langle n \rangle$, ($n/n_{cr} \gtrsim 0.15$). The density-gradient stabilization criterion and the inverse bremsstrahlung absorption length can be combined to determine a forward-scattering intensity threshold (similar to that described in Refs. 86 and 87 for backscattering): $I \gtrsim 1.4 \times 10^{14} n_{cr}/n z^{-0.4} \lambda_0^{-2.3} \tau^{-0.4}$, which is

$6 \times 10^{14} \text{ W/cm}^2$ for $z = 40$, $\tau = 1 \text{ ns}$, $n/n_{cr} = 0.1$, and $\lambda_0 \mu\text{m} = 1 \mu\text{m}$, where τ is the pulse length in nanoseconds.

In conclusion, Raman forward scattering can heat electrons to energies of $\sim \text{MeV}$, provided the rather stringent density-gradient threshold is exceeded. In the long density gradients expected in reactor targets, forward scattering could be a problem for high-intensity light. Although we have not tested the effect of bandwidth on forward scattering, it is likely that a large bandwidth, or splitting the laser frequency into several lines, could drive forward scattering below threshold (similar to backscattering).^{86,87}

Authors: K. G. Estabrook, W. L. Kruer, and B. F. Lasinski

Heated Electron Distributions from Laser Absorption on Ion Acoustic Turbulence

A laser-light absorption mechanism that has been discussed for many years⁹⁵⁻⁹⁷ is ion turbulence driven by a relative drift between the ions and electrons. The drift is assumed to be caused by an electric field that accelerates thermal electrons back into the heating region to replace fast electrons streaming into the target. This is the same ion turbulence often assumed to be responsible for transport inhibition. As the electric field of the laser light oscillates electrons, some of the laser power is irreversibly absorbed when that oscillating motion couples with the ion waves to drive electron plasma waves (epw) that heat electrons as they damp. The wavelength of the epw is dominantly determined by the ion acoustic fluctuations and, as the wavelength becomes shorter, the damping—and absorption—increase and the phase velocity—and heated electron energy—decrease. Faehl and Kruer⁹⁵ used theory and simulations to describe the fraction of light absorbed and the electron distributions produced by a given wavelength of ion fluctuations. This paper extends their work by using experimentally measured ion-electron drift turbulence spectra⁹⁸⁻¹⁰² as input to determine important features of the

Fig. 3-24. Electron phase space from a one-dimensional kinetic simulation.

absorption. We use kinetic simulations to measure the heated-electron distribution and find it to be approximately a Maxwellian distribution of temperature $\approx (m_e/2)v_p^2$, where v_p is the phase velocity of the epw. Much hotter electrons than previously assumed are found to be generated, since the measured ion-turbulence spectra peak at a rather long wavelength.

The experiments⁹⁸⁻¹⁰² use much smaller densities and much longer time scales than those of laser fusion, but the relative parameters ($k\lambda_D$, $v_d/v_e \sim 0.1$) scale similarly. Here, $k = 2\pi/\lambda_{epw}$, λ_D is the Debye length, v_d is the drift velocity, and v_e is the electron thermal velocity. Data from all these experiments show that the peak of the spectra from electron-ion drift turbulence is at a surprisingly long wavelength ($k\lambda_D < 0.2$). The significance of the long wavelength is that the epw will have a reasonably large phase velocity, $v_p/v_e = [3 + 1/(k\lambda_D)^2]^{1/2}$, and, hence, a fairly hot electron temperature, $T_{hot}/T_{cold} = 1.5 + 1/(2k^2\lambda_D^2)$, or about 13 for $k\lambda_D \sim 0.2$. We have calculated the fraction of light absorbed

as a function of plasma density divided by critical density (n/n_c), and the peak $k\lambda_D$ of the ion waves, using the complex dielectric function of the electron plasma waves at that wavelength and frequency.^{95,96} The absorption was summed over the k spectrum of the ion waves, with the intensity of the higher frequencies falling off as $f^{-2.5}$. We find the absorption vs density peaks strongly for $0.8 < n/n_c < 0.9$.

The experimentalists actually measure the frequency rather than the wavelength, which is related by $f/f_{pi} = k\lambda_D(1 + 3T_i/T_e)/(1 + k^2\lambda_D^2)^{1/2}$. Here, f is the ion acoustic frequency and f_{pi} is the ion plasma frequency; $f_{pi} = (4\pi ne^2/1/2)$, where n is the plasma density. The experiments do not agree on where the frequency peak is and find it between $f/f_{pi} \approx k\lambda_D \approx 0.05$ and 0.2 . This is unfortunate, since the total absorption depends sensitively on the $k\lambda_D$ of the peak. Since absorption by relatively long-wavelength ion drift turbulence occurs most strongly at relatively high n/n_c , there will most likely be a strong density gradient there, i.e., little volume for the absorption to occur. This process is similar to parametric decay. Our two-dimensional simulations¹⁰³ showed that parametric decay absorbed about 15% in a self-consistent density gradient.

Figure 3-25 shows the results of one-dimensional electrostatic simulations¹⁰⁴ with a fixed spectrum of ion turbulence that matched the experimental spectrum. In Fig.

3-25, ω_o is the laser angular frequency, and the Δ s are from one-dimensional simulations using fixed ion-turbulence spectra from Refs. 97 through 101. Since the simulations were one-dimensional, the simulated effective collision frequency has been reduced a factor of 2 to account for the wide range of angles of ion acoustic turbulence in three-dimensional simulations. To convert the graph in Fig. 3-25 into an effective collision frequency, multiply by an assumed turbulence level, $[(\delta n/n)(n/n_c)]^2$, where $\delta n/n$ is the peak amplitude of the ion density turbulence and has been measured⁹⁸⁻¹⁰² to be typically 0.15 to 0.3. The insert in Fig. 3-25 is an experimental spectrum from Ref. 98.

A plot of the electron kinetic energy in the simulations revealed that the heating was at first very slow as the epw grew from noise; then the heating became quite rapid as the epw trapped electrons, and the kinetic energy rose to typically a few times its initial value. Finally, the plasma in this periodic simulation became so hot that the epw became very highly damped, and the heating rate dropped to a small value. The measurements of the effective collision frequency, ν^* , were taken during the period of most rapid heating. Nonlinear effects that the simple theory does not include are

- As the electron plasma-wave amplitude becomes large, the wave becomes steeper, which means that, basically, there are significantly large amplitudes in higher modes (higher $k\lambda_D$) that damp (heat) faster.
- As the epw heats, there are more electrons at the phase velocity of the wave, which allows more electrons to be accelerated and hence, results in faster heating (until damping reduces the electric field).

In conclusion, we have considered laser light absorption due to drift-excited ion turbulence by using experimental spectra. We find that quite hot electrons can be heated, since the experimental spectra peak at rather long wavelengths. The absorption efficiency is sensitive to the magnitude of the fluctuations, the wavelength at which they peak, and the detailed steepening of the density profile near the critical density.

Author: K. G. Estabrook

Fig. 3-25. Effective collision frequency from ion-electron drift-induced turbulence as a function of density for turbulent spectra having peaks at the indicated $k\lambda_D$.

Analysis of Short-Pulse Absorption Experiments at 1.06-, 0.53-, and 0.27- μm Laser Wavelengths

Introduction. The choice of an optimum laser wavelength for laser fusion remains an outstanding issue, both experimentally and theoretically. In particular, from the point of view of laser-plasma coupling, incident wavelengths on the order of 0.33 to 0.25 μm have some strong potential advantages¹⁰⁵ over wavelengths in the 1- to 3- μm range. To shed more light on this issue, a series of experiments comparing laser light absorption at wavelengths of 1.06, 0.53, and 0.27 μm has recently been completed at École Polytechnique.¹⁰⁶ Here, we summarize our theoretical analyses of these experiments.

We emphasize laser pulse lengths between 60 and 100 ps because, for these pulse lengths, the plasma expansion should remain one-dimensional, given the laser spot diameters used in the experiments (50 to 70 μm). Short laser pulses have the additional interpretational advantage that stimulated Brillouin scattering is not an important part of the energy balance.¹⁰⁶ The École Polytechnique experimental data on laser-light absorption fraction vs incident intensity are shown in Fig. 3-26. Irradiation was with an f/1.3 lens. It is clear that, at comparable laser intensities, absorption is dramatically higher for short-wavelength laser light. Figure 3-27 shows representative unfolds of measured x-ray spectra in the range $h\nu = 500 \text{ eV}$ to 20 keV.

To analyze these data, we used a computer code, FILM,¹⁰⁷ which is a Lagrangian one-dimensional hydrodynamics code. FILM was used for this analysis in planar geometry, with a fully ionized, perfect-gas equation of state. Hot electrons created by resonance absorption at the critical surface are transported in a multigroup fashion; flux-limited diffusion in the dense part of the target is matched to a collisionless treatment of the outer coronal regions.¹⁰⁷ The source hot-electron temperature at the peak of the laser pulse was a specified input parameter, T_h . Before and after the peak of the pulse, the source hot-electron temperature

varied with laser intensity, I , as $T_h(t) \propto [I(t)/I_{\text{max}}]^{0.4}$.

In the calculations described here, there was no ponderomotive force, and the laser beam had a Gaussian temporal shape. The inverse bremsstrahlung absorption was

Fig. 3-26. Absorption fraction vs incident laser intensity for short-pulse experiments.

Fig. 3-27. Unfolds of multichannel x-ray spectra for $\text{C}_{10}\text{H}_8\text{O}_4$ targets.

calculated by using a mean ion charge defined by $Z_{ib} = \langle Z^2 \rangle / \langle Z \rangle$, where the relevant mean charge for the hydrodynamics was $\langle Z \rangle$. The inverse bremsstrahlung absorption coefficient was the usual classical linear value. The target material was plastic, $C_{10}H_8O_4$, so its mean $\langle Z \rangle = (4.6)$ was not large. Targets were 20- to 50- μm thick and were large in their transverse dimensions.

In the calculations presented here, there was no inhibition of the suprathreshold electron transport. We were left, therefore, with three free input parameters

- The hot-electron temperature, T_h , was chosen to reproduce the slope of the hard x-ray spectrum. This choice was relatively unambiguous and clear-cut in the absence of inhibition of the suprathresholds.
- The second input parameter was the fraction, f_{ia} , of the laser energy reaching critical that was put into the hot-electron distribution. From a theoretical point of view, this fraction represents resonance absorption and should lie between 15 to 30%, so long as the laser intensity is high enough. For low laser intensities (e.g., $I_L < 10^{13} \text{ W/cm}^2$ at 1.06- μm laser wavelength), resonance absorption is presumed to primarily heat the thermal-electron population.¹⁰⁸ This latter phenomenon was modeled by dumping a prescribed fraction of the energy reaching critical into the thermal-electron population there.
- The third free parameter was the flux limit applied to thermal-electron heat transport. The conductive heat flux was taken to be

$$\vec{q} = \min \left(-\kappa \nabla T_e, -0.6 f n_e m_e v_{te}^3 \nabla T_e / |\nabla T_e| \right) \quad (22)$$

where κ is the classical conductivity (Ref. 109); T_e , m_e , and n_e are electron temperature, mass, and density, respec-

tively; and $v_{te} = (T_e/m_e)^{1/2}$ is the electron thermal speed. The quantity f in Eq. (22) is the flux-limit and is a phenomenological parameterization of the many different physical processes that seem capable of inhibiting electron heat flow in laser-produced plasmas.¹¹⁰ The numerical algorithm for electron conduction was similar to the new algorithm described in Ref. 111.

Results at 0.27- μm Laser Wavelength. For this ultraviolet wavelength, the experimentally observed absorption fraction was about 93% at an incident intensity of $\sim 2.7 \times 10^{14} \text{ W/cm}^2$ with a 70- μm -diam focal spot. The pulse length was about 60 ps.

Figure 3-28 shows the absorption fractions calculated by FILM for these conditions, using $T_h = 1.5 \text{ keV}$ and $f_{ra} = 20\%$. As the flux limit, f , is varied from 0.05 to 1.0, the predicted total absorption rises from 66 to 94%. (Recall that the flux limit, f , used here is $1/0.6 = 1.67$ times the flux limit usually encountered in the literature.) The increased absorption at higher values of f is due to more-efficient inverse bremsstrahlung, since the coronal temperatures fall as f increases.

It is evident from Fig. 3-28 that, if inverse bremsstrahlung and resonance absorption are the only two absorption mechanisms present, the thermal flux limit, f , cannot be smaller than about 0.15 to 0.2 and still match the observed absorption of 93%.

Alternatively, to use a low flux limit of $f = 0.05$, which is consistent with many $\lambda_L = 1.06\text{-}\mu\text{m}$ experiments¹¹⁰ and with recent thin-foil experiments at $\lambda_L = 0.27 \mu\text{m}$,¹¹² we must postulate an additional absorption mechanism capable of making up the difference between the observed 93% absorption and the predicted 66% absorption for $f = 0.05$. Thus, to explain these data, we require an additional process, such as ion-acoustic turbulence,¹¹³ that must absorb $\sim 25\%$ of the incident energy.

The experimental and calculated x-ray spectra are illustrated in Fig. 3-29, where the violet line represents the experimental unfold and the two black lines represent spectra calculated by FILM for different flux limits, using $T_h = 1.5 \text{ keV}$. (These FILM calculations assumed no inhibition of hot-electron transport.) Both black lines are too low in the region below about 5 keV because the code spectrum is calculated using only optically thin bremsstrahlung, which is an

Fig. 3-28. Absorption fractions predicted by hydrodynamics code FILM at 0.27- μm laser wavelength for different values of the thermal heat flux limit, f .

adequate representation at the higher photon energies, but not in the region below a few thousand electron volts.

In the spectrum above 4 keV, the circles in Fig. 3-29 show FILM's x-ray spectrum for relatively uninhibited thermal transport, $f \geq 0.2$. In this case, the predicted level of hard x rays is in fairly good agreement with the experimental data. FILM indicates that about 5% of the incident energy appears in the form of hot electrons. Recall that the predicted and observed absorptions were also in good agreement for $f \geq 0.2$. Hence, one set of theoretical assumptions consistent with the absorption and spectral data at 0.27- μm laser wavelength is

- Classical inverse bremsstrahlung absorption.
- Roughly 20% of the energy reaching critical is resonantly absorbed into a hot-electron distribution.
- No additional absorption mechanisms are indicated.
- Suprathermal electron transport is uninhibited.
- The thermal-electron flux limit is not small: $f \geq 0.2$.

On the other hand, as we mentioned before, there is a previous body of data suggesting that the thermal flux limit, f , may be quite small: $f \approx 0.05$. The squares in Fig. 3-29 show FILM's predicted x-ray spectrum for $f = 0.05$, assuming no inhibition of suprathermal electron transport. Using its transport model with uninhibited suprathermals, FILM predicts a level of hard x rays that is too high, relative to the experiment, and an absorption fraction that is too low. Thus, if the flux limit is really as low as $f = 0.05$, we conclude that the additional physical mechanism needed to explain the high observed absorption should put its energy into thermal rather than suprathermal electrons to avoid making the predicted hard x-ray spectrum even higher relative to the experimental spectrum. Additionally, if the transport of suprathermal electrons were strongly inhibited, the high level of the hard x-ray spectrum predicted for $f = 0.05$ might be decreased toward the observed value. This possibility will be explored more fully in the discussion on 1.06- μm laser absorption.

Results at 0.53- μm Laser Wavelength. For the case of green laser light, the observed variation of absorption with incident laser

intensity (the green line in Fig. 3-26) allows a more sensitive test of the physics model in FILM. As in the case of ultraviolet light, we assumed in FILM that there was classical inverse bremsstrahlung absorption and that 20% of the light energy reaching critical produced fast electrons. We chose a peak hot-electron temperature, T_h , to reproduce the correct slope of the hard x-ray spectrum, and we varied the assumed value for the thermal flux limit, f . Suprathermals were not inhibited. The laser pulse length was 80 ps, and the focal spot diameter was about 50 μm .

Figure 3-30 shows the fractional absorption vs incident laser intensity, I_L . The green line represents the trend of the experimental data from Ref. 106, with the shot-to-shot variations of $\pm 5\%$ smoothed over; the variations are indicated by the error bar on the right. The individual points represent FILM calculations at $I_L = 1.3 \times 10^{15} \text{ W/cm}^2$ ($T_h = 4 \text{ keV}$), $I_L = 4.2 \times 10^{14} \text{ W/cm}^2$ ($T_h = 2 \text{ keV}$), $I_L = 10^{14} \text{ W/cm}^2$ ($T_h = 0.9 \text{ keV}$), and hot-electron transport is not inhibited.

It is clear from Fig. 3-30 that, if the only absorption mechanisms present are inverse bremsstrahlung and resonance absorption, FILM implies that the thermal heat flow cannot be very inhibited: $f \lesssim 0.6$. The two lower values of the flux limit, $f = 0.1$ and 0.05, predict absorptions that are too small by about 20 and 25%, respectively.

Fig. 3-29. Experimental and calculated x-ray spectrum for 0.27- μm laser wavelength and $\text{C}_{10}\text{H}_8\text{O}_4$ target.

If, on the other hand, we argue that heat flux is very inhibited, and the flux limit is actually as low as $f = 0.05$, Fig. 3-30 shows that we are then forced to hypothesize an additional mechanism capable of absorbing about 25% of the incident laser energy. Hence, these conclusions about the absorption of green laser light are quite similar to our conclusions for ultraviolet light in the discussion above.

Comparison of the high-energy x-ray spectra with FILM predictions for green laser light was possible at incident intensities of 4.2×10^{14} and $1.3 \times 10^{15} \text{ W/cm}^2$, where the best-fit hot-electron temperatures were 2 and 4 keV, respectively. The predicted level of hard x rays was somewhat higher for $f = 0.05$ than for $f = 0.6$, because more light is predicted to reach critical when the heat flux is very inhibited. The FILM calculation using $f = 0.6$ was in better agreement with the hard x ray data than were the strongly inhibited cases; however, the differences were not so large as those shown for ultraviolet incident light in Fig. 3-29. In general, FILM calculations with inhibited suprathermal electrons indicate that, for $0.53\text{-}\mu\text{m}$ laser light, no more than 10 to 15% of the incident energy went into the hot-electron population at these intensities.

Results at $1.06\text{-}\mu\text{m}$ Laser Wavelength. The experiments for $1.06 \mu\text{m}$ used 100-ps pulse lengths and a $60\text{-}\mu\text{m}$ focal-spot diameter. It was found that absorption was nearly

constant, at about 30%, for incident intensities above about $5 \times 10^{13} \text{ W/cm}^2$ (Fig. 3-26). These data suggest that resonance absorption on a steepened and rippled critical surface¹¹⁴ could be responsible for most of the absorption in this intensity range and that inverse bremsstrahlung is small by comparison. Such an interpretation is roughly consistent with FILM calculations of absorption for these intensities. Since inverse bremsstrahlung is weak in this case, the total absorption calculated by FILM is not very sensitive to the value of the thermal flux limit, f .

The hard x-ray spectra, however, raise some important questions about this simple absorption scenario. The difficulty is that, when the suprathermal electron transport is not inhibited, FILM predicts a level of hard x-ray emission that is a factor of 10 to 30 too high, if 20 to 30% of the laser light is assumed to be absorbed by resonance absorption. Studies of x-ray spectral variations using FILM have consequently led us to two possible absorption models (Model I and Model II) for $1.06\text{-}\mu\text{m}$ laser light that seem consistent with the observed x-ray spectra.

In Model I, the observed absorption is due to 20 to 30% resonance absorption, as postulated above, but the suprathermal electron transport is strongly inhibited. The additional transport inhibition acts to confine hot electrons to the low-density corona, where they do not radiate efficiently. Instead, a large fraction of the suprathermal electron energy is presumably lost in the form of fast-ion acceleration. This type of scenario is supported by recent thin-foil experiments on transport.¹¹² The hypothesis of inhibited suprathermals needs more thorough investigation, however, using appropriate numerical transport models.

In Model II, if suprathermal electron transport is not strongly inhibited, comparison of the hard x-ray spectrum with FILM indicates that only 2 to 5% of the incident laser energy is going into a hot-electron population for $1.06\text{-}\mu\text{m}$ laser light. In this case, to explain the observed 30% absorption, we would need to postulate an additional mechanism capable of absorbing about 25% of the incident energy into a thermal population of electrons (inverse bremsstrahlung is too weak to provide such

Fig. 3-30. Fractional absorption vs incident laser-light intensity for $0.53\text{-}\mu\text{m}$ laser wavelength.

large absorptions in this high-intensity regime).

Model II makes us uneasy from a theoretical point of view because extensive computer simulations¹¹⁵ show that resonance absorption can readily absorb 20 to 30% of the light reaching critical in this parameter regime. Thus, we are hard pressed to explain why resonance absorption should have dropped to only 2 to 5% in the experiments under consideration here. For theoretical reasons, we tend to favor Model I because we can think of mechanisms such as mega-Gauss dc magnetic fields¹¹⁶ that would be capable of inhibiting the transport of suprathermal electrons, particularly for 1.06- μ m laser light.

Discussion. The data shown in Fig. 3-26 make it clear that, when laser intensity and spot size are held fixed, laser-light absorption is much more efficient at short laser wavelengths. Analyses of the detailed trends of these data using a computer hydrodynamics code, FILM, has allowed us to arrive at two alternative physics models consistent with the absorption data and the hard x-ray spectra. For 0.27- and 0.53- μ m incident laser light, either of two possibilities exists:

- Transport of both thermal and suprathermal electrons is relatively uninhibited, and the two dominant absorption mechanisms are inverse bremsstrahlung and resonance absorption.
- Thermal transport is very inhibited, as suggested by previous experiments,^{110,112} and there is a further, presently unidentified, mechanism capable of absorbing about 25% of the incident energy into a roughly thermal electron distribution. A likely candidate for such a mechanism would be absorption due to ion-acoustic turbulence.¹¹³

In addition, our analyses of the x-ray spectra produced by 1.06- μ m laser light suggest that, in this case, hot-electron transport may be strongly inhibited.

These conclusions have inherent limitations, however, and we point out some of them here. From the experimental point of view, there is some uncertainty in the actual values of the laser pulse length and the spot size and, hence, in the appropriate incident laser intensity to use in the FILM simulations. Since it is clear from Fig. 3-30

that the predicted absorption fraction depends on intensity, we have an uncertainty in our conclusions about the magnitude of the flux limit, f . We can estimate this uncertainty from Fig. 3-30. If the actual value of I_L were lower than we had thought, the green curve would shift to the left by an appropriate amount. For example, consider an error of a factor of 2 in I_L . In this case, the FILM-calculated absorptions for $f = 0.05$ and $f = 0.1$ would still lie well below the error limits for the experimentally measured values, and our conclusions would not be qualitatively changed. However, if the actual value of I_L were lower by a factor of 4 or more, our uncertainty would begin to be quite large.

A second question in our modeling of these experiments concerns the amount of lateral transport. If a substantial fraction of the incident laser intensity were to be spread out laterally beyond the edge of the focal spot, then we should use an appropriately lower incident laser intensity, I_L , to model these experiments with a one-dimensional hydrodynamics code. In the code studies reported here, this effect was not included, since we had no experimental evidence on the existence or magnitude of such a lateral transport effect.

From the theoretical point of view, there are several aspects of the physics model used in FILM that are undoubtedly far too idealized, e.g., the ideal-gas equation of state, the assumption of fully ionized atoms, and the purely planar geometry. These aspects introduce some degree of theoretical uncertainty into our conclusions. We are actively investigating such issues to determine the extent to which our results will be modified by the inclusion of more sophisticated physics treatments in the hydrodynamics model.

Author: C. E. Max

Major Contributors: C. Garban-Labaune, F. Amiranoff, and E. Fabre (École Polytechnique, Palaiseau, France), and W. C. Mead

Effect of Supersonic Flow on Density Profiles

Introduction. We have investigated density profiles near the critical surface in the presence of supersonic flow. A spherical-particle code models the free expansion of a plasma with an initial Gaussian density profile, and a homogeneous driver simulates the incident laser light. Three types of profiles are found, depending on driver strength and Mach number of the flow at critical: the widely studied subsonic variety; a supersonic variety with stable, overdense bumps; and a transsonic variety, in which overdense bumps form behind the critical surface and pass through it. A plateau lies between pairs of bumps, and the wavebreaking amplitude increases dramatically when this plateau is near critical. We also make comparisons with experimental data.

Dawson et al.¹¹⁷ created a model for the quasi-self-similar free expansion of a plasma with a Gaussian radial-density profile. Demanding spherical symmetry, setting $\gamma = 5/3$, integrating their differential equation, and appropriately identifying the constants of integration, we obtain, for number density, fluid velocity, and temperature,

$$n = N / [(2\pi)^{3/2} R^3] \exp(-r^2/2R^2) \quad (23)$$

and

$$v_d = r (1/R) (dR/dt) \quad (24)$$

where the characteristic length, R , is given by

$$R^2 = \sigma_0^2 + c_0^2 t^2 \quad (25)$$

and σ_0 and c_0 are the dispersion in space and the sound speed, respectively, at $t = 0$, the time when the plasma has minimum size. N is the total number of particles, and T_0/σ_0^2 is the original temperature. The units may be any self-consistent set of units.

The radius of a spherical surface of constant density, $n = n_1$, is given by

$$r(n_1, t) = R \{ 3 \{ -\ln[2\pi(n_1/N)^{2/3} R^2] \} \}^{1/2} \quad (26)$$

The velocity with which plasma moves relative to this surface is given by

$$V_r = v_d - dr(n_1, t)/dt = (c_0^2 t/R) \times \{ 3 \{ -\ln[2\pi(n_1/N)^{2/3} R^2] \} \}^{1/2} \quad (27)$$

where V_r varies between 0 and infinity, in contrast to the self-similar expansion of a planar plasma, where $v_r = c_s$, the sound speed.¹¹⁸

Simulations. We attempted to recover this behavior with a 1.5-dimensional electrostatic spherical-geometry particle code. The code used a spherical divergence to calculate the electric field from Gauss' law. Twenty thousand particles were used, resolved on a grid of 2048 points. They were advanced in time using a particle-in-cell algorithm of the usual type,¹¹⁹ with an additional algorithm to include the acceleration due to the effect of angular momentum. Initial conditions were of two kinds: a Gaussian density distribution with a linear velocity profile, as above; or a sphere of uniform density of radius a . In the first case, the expansion process adhered very closely to the model's predictions from the initial conditions. In the second case, the expansion approached the model very rapidly, in a time $t \approx a/c_h$, as seen in Fig. 3-31.

Profiles from Resonant Absorption. To study resonance absorption in the presence of supersonic flow, we introduced a homogeneous oscillating electric field, like those often used to study resonance absorption in one-dimensional Cartesian-geometry particle codes.¹²⁰ The electric field excites a large-amplitude electron plasma wave that locally modifies the density gradient. For low driver intensities and limited times, resonance absorption and associated profile modification act as perturbations on the self-similar expansion described above. We can then study these effects in the presence of supersonic flow, with self-consistently determined electric field of the resonantly driven wave, momentum deposition due to electron ejection from the critical surface, and other features of the absorption. The model does not include the ponderomotive pressure due to the laser light itself, but this is usually smaller than the pressure of the resonantly driven wave.^{121,122}

Empirically, we found that the expansion was not too seriously disturbed for $v_o/v_{te} \leq 1$, where $v_o = (eE_o/m\omega_o)^{1/2}$, E_o and ω_o are the driver amplitude and angular frequency, respectively, $v_{te} = (T_e/m)^{1/2}$ is the electron mean thermal velocity, and T denotes the cold, or background, plasma temperature. The hot electrons produced by resonant absorption also accelerate the ions at large radii, where the plasma density is low. However, this disturbance does not affect the region near the critical surface in the simulations described here. We ran the simulation for times $\omega_o t \approx 1200$ to 1500. The driver was turned on smoothly over a period of $200/\omega_o$. The mass ratio M/m was 2048, except for some examples of type III profiles (see below), where a mass ratio of 128 was used to speed up the ion time scale.

We found three types of profiles:

- Type I—the density step observed in many previous simulations.¹²¹
- Type II—a profile similar to the shock-plus-d front.¹²³
- Type III—a cyclical oscillation of the critical surface similar to that described

by Powers et al.¹²⁴ Properties of this profile were most easily analyzed in a reference frame moving with the critical surface.¹²⁵

The density step prevailed during the early stages of spherical expansion for Mach numbers $M_r = v_r/c_s < 1$. We also observed it in expansions at large r , where spherical effects are unimportant. In these simulations, we set the inner simulation boundary at $r \approx 10^5 \lambda_D$. Particles striking this boundary were reemitted thermally. Initially, the $100\lambda_D$ to the right of this radius were filled with plasma of density n_{mx} , which was allowed to expand into the vacuum beyond. A capacitor field drove resonance absorption at $n_c = 0.1 n_{mx}$, where n_{mx} is the maximum initial density in the simulation. The results, as expected, were very similar to those for planar expansions, with formation of the usual density step.

When the relative Mach number $M_r = v_r/c_s > 1$, we observed structures similar to the shock-plus-d fronts. A typical profile is shown in Fig. 3-32. The density decreases with radius in the overdense

Fig. 3-31. (a) Dispersion in space as a function of time for three Gaussian-loaded free expansions. (b) Slope of fluid velocity as a function of time.

plasma, reaching a minimum at r_b and then a maximum at r_u . From r_u , the density drops through critical to a minimum at n_i , then increases slightly before resuming its fall. Similarly, the velocity has a maximum at r_b , a minimum at r_u , and a maximum at r_ℓ . In the frame moving with the critical surface, the profile is relatively static. Number flux and pressure balance are approximately preserved across the critical surface

$$n_u v_u \approx n_\ell v_\ell \quad (28)$$

$$n_u T + \rho_u v_u^2 \approx n_\ell T + \rho_\ell v_\ell^2 + (n_\ell/n_c) (E_w^2/8\pi) \quad (29)$$

Here, n_i , ρ_i , and v_i are number density, mass density, and velocity, respectively, at radius r_i . E_w is the electric field due to the electron plasma wave at n_c . In the frame moving with the critical surface, $v_u < c_s$. Both n_u and n_i are in good agreement with those observed for similar v_o/v_{te} in one-dimensional Cartesian simulations.¹²² In the laboratory reference frame, $v_b \leq c_s$. Number flux and pressure are approximately balanced between r_b and r_u in the frame moving with the critical surface

$$n_b v_b \approx n_u v_u \quad (30)$$

$$n_b T + \rho_b v_b^2 \approx n_u T + \rho_u v_u^2 \quad (31)$$

These observations suggest that a given v_o/v_{te} always produces the same profile. The only change in the case of supersonic flow is that, at some point upstream of the critical density, a compression front forms at r_b , where the plasma velocity begins to decrease, until it becomes subsonic near r_u . To preserve flux balance, the density in the compression front (between r_b and r_u) must decrease as the velocity increases with r .

If $n_b < n_c$, the above profile is no longer stable. A bump forms behind the critical surface with the same n_u , n_i , v_u , and v_i as those in type I or II, but the driver field excites electron plasma waves in the area near r_b . Static pressure balance is no longer maintained. The lead surface of the bump moves forward with Mach number $M \gtrsim 1$ in the laboratory frame; its trailing surface moves slightly faster. It leaves behind a plateau at $n \gtrsim n_c$. Due to the long density gradient there, the waves break at high amplitude. The maximum magnitude of the electric field and the electron kinetic energy both increase dramatically, as do the heated electron temperature and the fraction of particles heated. A new density bump forms rapidly behind the plateau, and it, in turn, moves forward. The process repeats indefinitely (see Fig. 3-33).

Appealing to flux balance between r_b and r_u in the frame of the critical surface, and using the fact that the profile near critical is like the profiles for subsonic flow, we can

Fig. 3-32. Example of type II profiles. (a) Density. (b) Velocity.

estimate the criterion for profiles of type II to become type III. For instability, $n_b \leq n_c$, $v_b v_b \approx n_u v_u$, and $v_u \approx c_s$. Thus, the criterion for instability is

$$M_b = v_b/c_s \geq n_u/n_c \quad (32)$$

Values of n_u as a function of v_o/v_{te} are now available.¹²² The agreement of this criterion with our simulations is good (see Fig. 3-34). The frequency with which the profile "burps", once a type III profile has been established, can be estimated as

$$\nu_{bp} \approx \Delta r/c_s \quad (33)$$

In the regime in which we were able to observe regular burps ($v_o/v_{te} \leq 0.3$), this scaling agreed well with the simulations. This behavior is similar to that seen in a fluid-code simulation of normally incident laser light,^{124,125} and in simulations of microwave irradiation of plasmas.¹²⁶

In an actual experiment or an electromagnetic simulation, the driver would not be

as strong on the plateau as it would be at the outer critical surface during the period when the bump is still overdense, since the electric field would have to tunnel through to the plateau before exciting the plasma wave there. The bumps seen in our simulations have thicknesses $\Delta r \leq 30 \lambda_D$. Thus, for $T = 100$ eV, $\lambda_b = 1 \mu\text{m}$, $\Delta r \approx 0.25 \lambda_b$, so the capacitor model is reasonable. Larger drivers may produce thicker bumps.

Comparison with Experiment. Spherical glass shells irradiated with $1.06\text{-}\mu\text{m}$ light produced flashes of 2ω light, indicating an increase in the amplitude of the resonantly driven field, concomitant with large outward excursions in the position of the critical surface.¹²⁷ These occurrences, called flares, took place near the end of the laser pulse as the critical surface moved inward. The observed time between bursts was longer than described by these simulations, so that other instabilities (perhaps filaments or bubbles) may have been operating. Spatially broad, bright light extending across shell targets irradiated with $1.06\text{-}\mu\text{m}$ laser light has been reported.¹²⁸ The 2ω light spectrum

Fig. 3-33. Type III profile for $M/m = 128$ and $c_s = 0.1 v_{te}$.

from these flares consists of a broad red-shifted "pedestal" and a well-defined 2ω line, indicating the presence of parametric instabilities that would be enhanced by a large volume of plasma just below critical. This contrasts with other experiments in which the 2ω light had no pedestal. Intermittent flashes of $3/2\omega$ light have been observed.¹²⁹

Supercritical bumps in CO_2 laser irradiation experiments have been observed¹³⁰ by using a $1.06\text{-}\mu\text{m}$ light interferometer. These supercritical bumps were much thicker than the bumps we observed, but the strongly steepened profile suggests a larger v_o/v_{te} than any we consider here.

Supercritical bumps in $1.06\text{-}\mu\text{m}$ light irradiation of glass microballons have also been seen.^{131,132} The bump formed late in the experiment as the critical surface continued to move outward. The experimenters believe that a temperature step at critical density was important in the formation of the bump. Very long gradients ($L \approx 100\text{ }\mu\text{m}$) observed at n_c , late in the laser pulse, led to the hypothesis that the critical surface might be oscillating.¹³³ Microwave experiments have produced density profiles similar to those of type II.¹³⁴ In the example shown, the driver strength is $v_o/v_{te} \approx 0.4$. An overdense bump forms above n_c with $\Delta r = 35\lambda_D = 0.28\lambda_b$ and remains stationary for the length of the experiment ($\omega_0 t \approx 70\,000$). However, the plasma was argon with a correspondingly longer time scale. An overdense bump below n_c was also observed. Similar structures occurred as transients in our simulations, particularly when the driver

was turned on after the flow had become supersonic.

Summary. We have investigated density profiles near the critical surface in the presence of supersonic flow. A spherical-particle code models the free expansion of a plasma with a Gaussian density profile, and a homogeneous driver simulates the incident laser light. Three types of profile are found, depending on driver strength and Mach number of the flow at critical: the widely studied subsonic variety; a supersonic variety with stable overdense bumps; and a transonic variety, in which overdense bumps form behind the critical surface and pass through it. A plateau lies between pairs of bumps, and the wavebreaking amplitude increases dramatically when this plateau is near critical.

Authors: C. R. Gwinn, K. G. Estabrook, and W. L. Kruer

A Model for Stimulated Brillouin Scatter Induced by Nonabsorbed Light

In our 1979 annual report,¹³⁵ we gave a theory for the enhancement of stimulated Brillouin scatter (SBS) by nonabsorbed light returning from the critical surface. In the past year, we have generalized the theory to include a rigorous treatment of gradient effects, thus allowing detailed comparisons with AURUS¹³⁶ numerical simulations of SBS using laser and target parameters of laboratory experiments.¹³⁷ Here, we briefly review the improved theory and discuss some preliminary results obtained with it.

We begin with the one-dimensional electromagnetic (EM) wave equation and plasma fluid equations

$$\frac{\partial^2 F}{\partial t^2} + \nu_h \frac{\partial E}{\partial t} - c^2 \frac{\partial^2 E}{\partial x^2} + \omega_p^2 E = 0, \quad (34)$$

$$\frac{\partial n}{\partial t} + \frac{\partial}{\partial x}(nv) = 0, \quad (35)$$

and

Fig. 3-34. Instability threshold for transition from type II to type III profile.

$$n \left(\frac{\partial v}{\partial t} + v \frac{\partial v}{\partial x} \right) = - \frac{\partial}{\partial x} (nc_s^2) - \frac{Zne^2}{2mM\omega_0^2} \frac{\partial}{\partial x} \langle E^2 \rangle \quad (36)$$

Here, c is the speed of light, $\omega_0(\omega_p)$ is the laser (plasma) frequency, $n(v)$ is the ion density (fluid velocity), $m(M)$ is the electron (ion) mass, ν_h is the EM damping frequency, and $c_s^2 = (ZT_e + 3T_i)/M$, where Z is the average ionic charge state.

We decompose E into left-going ($-$) and right-going ($+$) waves and the plasma density into a slowly varying background, n_0 , and a fluctuating part, n_1 , which is assumed small:

$$E = E_+ \exp(i\chi_+) + E_- \exp(i\chi_-) \quad (37)$$

$$n = n_0 + n_1 = n_0 + \text{Re} [\tilde{n} \exp(i\chi_1)] \quad (38)$$

E and n are slowly varying amplitudes and $\chi_{\pm}$ and χ_1 are the rapidly varying phases. We take $\chi_{\pm}$, χ_1 , and n_0 real, while $E_{\pm}$ and $\tilde{n}$ may be complex. Substitution of Eqs. (37) and (38) into Eq. (34) yields

$$\begin{aligned} & (c^2 k_{\pm}^2 + \omega_{p0}^2 - \omega_{\pm}^2) E_{\pm} \\ & - i \left(2\omega_{\pm} \frac{\partial E_{\pm}}{\partial t} + E_{\pm} \frac{\partial \omega_{\pm}}{\partial t} + 2c^2 k_{\pm} \frac{\partial E_{\pm}}{\partial x} \right. \\ & \left. + c^2 E_{\pm} \frac{\partial k_{\pm}}{\partial x} + \nu_h \omega_{\pm} E_{\pm} \right) + \frac{\partial^2 E_{\pm}}{\partial t^2} \\ & + \frac{\partial E_{\pm}}{\nu_h \partial t} - c^2 \frac{\partial^2 E_{\pm}}{\partial x^2} = - \frac{\omega_0^2}{2n_c} E_{\mp} [\tilde{n}^p \exp \\ & \pm i(\chi_- - \chi_+ - \chi_1) + \tilde{n}^m \exp \mp i(\chi_+ \\ & - \chi_- - \chi_1)] \quad (39) \end{aligned}$$

where n_c is the critical density and $\omega_{p0}^2 = 4\pi n_0 e^2/m$. The superscript $p(m)$ means conjugate (*) for the $+$ ($-$) equation only. We have adopted the shorthand notation: $\omega_{\pm} = -\partial \chi_{\pm} / \partial t$, $k_{\pm} = \partial \chi_{\pm} / \partial x$. We adopt the convention that E_- is the incident, or pump, wave, while E_+ is the scattered wave. The second term on the right-hand side of Eq. (39) now represents the forward scattered, or Stokes, wave, and we will neglect it. We solve Eq. (39) in the Wentzel-Kramers-Brillouin (WKB) approximation, using the 0th order (in $\partial/\partial t$, $\delta/\delta x$, and ν_h) terms to solve for the phases,

$\chi_{\pm}$, and the first-order terms to solve for the amplitudes, $E_{\pm}$.

Thus, we neglect the second-order terms. They are small so long as $(\partial/\partial t)\omega_{\pm}^{-1} \ll 1$ and $(\delta/\delta x)k_{\pm}^{-1} \ll 1$. The second condition is violated near the critical density, where $k_{\pm} \rightarrow 0$. The density profiles of interest, however, drop abruptly through critical in a sharp step-like structure due to resonance absorption, radiation pressure, or transport inhibition. Thus, the WKB approximation is invalid only in the extremely thin critical layer, which we replace by a simple boundary condition.

To 0th order in $\partial/\partial t$, $\partial/\partial x$, and ν_h , we have the nonlinear partial differential equations for the light wave phases, $\chi_{\pm}$

$$\omega_{\pm}^2 = \omega_{p0}^2 + c^2 k_{\pm}^2 \quad (40)$$

We let $\chi_{\pm} = -\omega_0 t + \phi_{\pm}$ (Ref. 138), where $\phi_{\pm}$ contains the rapid spatial variations of the phase, but only a slow time dependence. Then, we may approximate Eq. (40):

$$\omega_0^2 \approx \omega_{p0}^2 + c^2 \left(\frac{\partial \phi_{\pm}^2}{\partial x} \right) \quad (41)$$

Integrating, we have

$$\chi_{\pm}(x) = \int_{x_L}^x k_{\pm} dx - \omega_0 t + \text{constant} \quad (42)$$

and

$$\chi_{\pm}(x) = \int_{x_c}^x k_{\pm} dx + \chi_{\pm}(x_c) + \text{constant} \quad (43)$$

where $k_{\pm} = \pm(\omega_0/c)(1 - \omega_{p0}^2/\omega_0^2)^{1/2}$ and $x_c(x_L)$ is the position of the critical surface (laser). By relating $\chi_+(x_c)$ and $\chi_-(x_c)$ as we have in Eq. (43), we are explicitly making E_+ the light returning from the critical surface, rather than some other noise wave. Taking the time derivative of $\chi_{\pm}$ shows that the EM frequencies, $\omega_{\pm}$, have two components. The first component is the familiar Doppler shift, which comes from the derivative of the integration limits, dx_c/dt , dx_L/dt . A second component, however, $\int dx \partial k_{\pm} / \partial t$, results from the changing plasma density along the flight path of the light. This second

component is, in general, comparable to the Doppler shift.¹³⁸

We obtain the field-amplitude equations from the first order (in $\partial/\partial t$, $\partial/\partial x$, and ν_h) terms of Eq. (39)

$$\begin{aligned} 2\omega_{\pm} \frac{\partial E_{\pm}}{\partial t} + E_{\pm} \frac{\partial \omega_{\pm}}{\partial t} + 2c^2 k_{\pm} \frac{\partial E_{\pm}}{\partial x} \\ + c^2 E_{\pm} \frac{\partial k_{\pm}}{\partial x} + \nu_h \omega_{\pm} E_{\pm} \\ = -\frac{i\omega_0^2}{2} \frac{\tilde{n}^p}{n_c} E_{\mp} \exp \pm i(\chi_- - \chi_+ - \chi_1) \end{aligned} \quad (44)$$

These amplitude equations are easily transformed into equations for the left- and right-going intensities

$$\begin{aligned} \frac{\partial}{\partial t} (\omega_{\pm} |E_{\pm}|^2) + c^2 \frac{\partial}{\partial x} (k_{\pm} |E_{\pm}|^2) + \nu_h \omega_{\pm} |E_{\pm}|^2 \\ = \frac{\omega_0^2}{2} \text{Im} \left[\frac{\tilde{n}^p}{n_c} E_{\mp} E_{\pm}^* \exp \right. \\ \left. \pm i(\chi_- - \chi_+ - \chi_1) \right] \end{aligned} \quad (45)$$

Finally, we will be concerned only with quasi-steady state systems. In this case, we may estimate $\partial/\partial t \sim c_s/L$ in Eq. (45), while $\partial/\partial x \sim 1/L$, where L is a hydrodynamic scale length or an SBS gain length. Then, the first term is of order c_s/c , compared with the second, and may be neglected. If Eq. (45) is used to study the propagation of pulses, then $\partial/\partial t \sim c/L$, and this term must be retained.¹³⁹

Next, we solve for the ion-wave amplitude, $\tilde{n}$. We assume that the ion-wave damping rate, ν_i , is large enough that $l_p \ll L_h$, where $l_p = c_s/\nu_i$ is the ion-wave damping length, and L_h is a typical scale length for variations of the hydrodynamics and, hence, of the EM frequencies and wave numbers, $\omega_{\pm}$, $k_{\pm}$. In this case, an ion wave generated in one region cannot propagate far enough to reach a region with significantly different $\omega_{\pm}$, $k_{\pm}$. Therefore, near steady state, the ion-wave frequency and wave number, ω_i and k_i , must be equal to those of the local ponderomotive force driver. With the phase of the ion wave thus determined, the ion wave amplitude is given by the 0th order (in $\partial/\partial t$ and $\partial/\partial x$) terms in the driven-ion-wave equation. In deriving this equation, therefore, we are

justified in neglecting all terms explicitly involving gradients of n_0 and v_0 . Linearizing Eqs. (35) and (36), we obtain

$$\begin{aligned} \frac{\partial^2 n_1}{\partial t^2} + 2\nu_0 \frac{\partial n_1}{\partial t} + (\nu_0^2 - c_s^2) \frac{\partial^2 n_1}{\partial x^2} \\ + \nu_1 \left(\frac{\partial n_1}{\partial t} + \nu_0 \frac{\partial n_1}{\partial x} \right) \\ = \frac{Zn_0 e^2}{4mM \omega_0^2} \frac{\partial^2 |E|^2}{\partial x^2} \end{aligned} \quad (46)$$

Using Eq. (37) we find the ponderomotive force drive is

$$\begin{aligned} \frac{\partial^2 |E|^2}{\partial x^2} \\ = -2(k_- - k_+)^2 \text{Re}[(E_- E_+^* \\ \exp i(\chi_- - \chi_+)] \end{aligned} \quad (47)$$

where we have neglected $\partial E_{\pm}/\partial x \ll k_{\pm} E_{\pm}$. Since the phases of $\tilde{n}$ and the driver are equal, $\chi_1 = \chi_- - \chi_+$. Substituting for Eq. (38), we find that $\tilde{n}$ is given by

$$\begin{aligned} [(\omega_1 - k_1 v_0)^2 - k_1^2 c_s^2 + i\nu_1(\omega_1 - k_1 v_0)] \tilde{n} \\ = \frac{Zn_0 e^2 k_1^2}{2mM \omega_0^2} E_- E_+^* \end{aligned} \quad (48)$$

where $\omega_i = \omega_- - \omega_+$ and $k_i = k_- - k_+$. In obtaining Eq. (48), we have neglected $\partial \tilde{n}/\partial t$ and $c_s \partial \tilde{n}/\partial x$ compared to $\nu_i \tilde{n}$ (the heavy damping limit). This is valid for $l_p \ll L_s$, where L_s is the SBS gain length to be derived below.

Combining Eqs. (45) and (48) yields

$$\begin{aligned} \omega_{\pm} \nu_h |E_{\pm}|^2 + c^2 \frac{\partial}{\partial x} (k_{\pm} |E_{\pm}|^2) \\ = \pm \frac{1}{4} \frac{n_0}{n_c} \left(\frac{e^2 |E_{\mp}|^2}{m^2 \omega_0^2} \right) \left(\frac{Zm \omega_0^2}{Mc_s^2} \right) \end{aligned} \quad (49)$$

and

$$\times \left(\frac{\nu_1}{\omega_s} \right)^{-1} P(\eta) |E_{\pm}|^2, \quad (50)$$

where the resonance function, $P(\eta)$, is defined as

$$P(\eta) = \frac{\left(\frac{\nu_1}{\omega_s} \right)^2 \eta}{(\eta^2 - 1)^2 + \left(\frac{\nu_1}{\omega_s} \right)^2 \eta^2}, \quad (51)$$

and where $\omega_s = 2k_0\sqrt{\epsilon}c_s$ and $\epsilon = 1 - n_0/n_c$. The argument of the resonance function, P , is $\eta = v_0/c_s + \omega_i/\omega_s$, which has a simple physical interpretation. It is the beat frequency of the incident and reflected light waves as seen in the local plasma rest frame, normalized to the sound frequency in that frame: $v_0/c_s + \omega_i/\omega_s = [(\omega_- - k_-v_0) - (\omega_+ - k_+v_0)]/\omega_s$.

Defining the normalized intensities $I_{\pm} = \sqrt{\epsilon} |E_{\pm}|^2/E_0^2$, where E_0 is the incident field, we find the final equations

$$\frac{\partial I_{\pm}}{\partial x} \pm \frac{I_{\pm}}{L_A} = \frac{I_{\pm} I_{\mp}}{L_S}, \quad (52)$$

where the local SBS gain length is given by

$$L_S^{-1} = \frac{k_0}{4} \frac{n_0}{\epsilon n_c} \left(\frac{mv_{osc}^2}{T_e} \right) \times \left[\left(1 + \frac{3T_i}{ZT_e} \right) \left(\frac{v_i}{\omega_s} \right) \right]^{-1} P(\eta). \quad (53)$$

In these latter two equations, $L_A = c\sqrt{\epsilon}/v_h$ is the local absorption length, and $v_{osc} = eE_0/m\omega_0$.

Equations (52) form a coupled set of nonlinear differential equations. In a numerical solution of this set, iteration is required because the two boundary conditions, $I_-(\text{vacuum}) = I_{\text{incident}}$ and $I_+(\text{critical surface}) = (1 - D) I_-(\text{critical surface})$ (where D is the resonance absorption fraction), are to be applied at opposite ends of the computational mesh. For typical LASNEX zoning conditions, it often happens that the entire SBS region [where $P(\eta) \sim 1$] is confined to only a few zones due to strong gradients of density and velocity. In such situations, the active region is partitioned into subintervals when Eqs. (52) are integrated.

To model the phenomenon of SBS ion wavebreaking, an effective nonlinear ion-wave damping is employed to modify v_i of Eq. (51) according to

$$\left(\frac{v_i}{\omega_s} \right) = \max \left[\left(\frac{v_i}{\omega_s} \right)_{LD} \left(\frac{v_i}{\omega_s} \right)_{NL} \right], \quad (54)$$

where $(v_i/\omega_s)_{LD}$ is the Landau damping rate determined by the temperature ratio,

$\tau = T_i/ZT_e$ (Ref. 140), and $(v/\omega_s)_{NL}$ is chosen through Eq. (48) to keep $\tilde{n}$ below the wave-breaking threshold $|\tilde{n}| < n_{wb}$ (Ref. 141), where

$$n_{wb} = \frac{n_0}{2} \left[(1 + I)^{1/2} - (3I)^{1/2} \right]^2. \quad (55)$$

It should be clear from the preceding discussion that the rarefaction density and velocity profiles below the step at critical density play an important role in determining the strength of backscattering induced by the nonabsorbed light. Thus, we have taken care to incorporate the model including momentum deposition due to resonant-absorption production of hot electrons at critical density¹⁴² and the rarefaction shock formation associated with two-group (hot and cold) electron expansion of the target corona.¹⁴³ Furthermore, we have attempted to obtain more self-consistent coupling of the absorption region with the interior of the target by including the strong dependence of T_{hot} from resonant absorption on T_{cold} , the local background temperature.¹⁴² Finally, we have included tabulated data for the subcritical flow parameters from collisionless particle simulations¹⁴² of the critical density region for use in our interaction model and for calculating inverse bremsstrahlung absorption whenever the hydrodynamical zoning fails to adequately resolve the fine structure of the region.

Because the effective noise spectrum in the model is a single high-intensity line ($I_+ \sim I_-$) (namely, the light returning from the critical surface), SBS is confined to a single resonant region on the inhomogeneous profile where the wave matching conditions are satisfied, ($\eta = 1$). This is illustrated by the plasma profiles in Fig. 3-35, which were taken from a LASNEX simulation of an Au disk irradiated with a 1-ns pulse of 1- μm light. The peak intensity is $3 \times 10^{14} \text{ W/cm}^2$, thermal transport is inhibited, and non-LTE ionization physics is employed. Figure 3-35(a) plots the electron-density and temperature profiles at the peak of the laser pulse, while Fig. 3-35(b) gives the corresponding expansion-velocity profile. The resulting profile of the SBS resonance parameter, η , is shown in Fig. 3-35(c). Because of the strong gradients, the resonance function, $P[\eta(r)]$, has a very small

spatial extent, $\sim 10 \mu\text{m}$, limiting the effective $Q = \int dx/L_s$ to the relatively small value of ≈ 2.5 . However, the large effective "noise" level means that substantial depletion of the incident power will occur even with this small value of Q . This is illustrated dramatically by Fig. 3-35(d), which shows the power of the incident (P_-) and reflected (P_+) beams. The sharp drop in P_- near $r = 340 \mu\text{m}$ is due to SBS and corresponds to the peak in the SBS resonance function, $P(\eta)$, shown in Fig. 3-35(c). From Fig. 3-35(d), it is evident that the scattering efficiency of the SBS resonance is about 50%, so that one-half of the incident energy is denied access to the critical surface where absorption is most efficient. Instantaneous absorption is about 36% (two-thirds of this is inverse bremsstrahlung, one-third is resonance absorption). However, the time-integrated absorption, 48%, is higher because SBS is less efficient at early and late times in the pulse. This absorption figure is in good agreement with the experimental value.

We have developed a model of SBS induced by nonabsorbed light. Preliminary results are encouraging. In the coming year we hope to further test the model using the large body of experimental results that are now accumulating.

Authors: C. J. Randall and J. R. Albritton

Stimulated Brillouin Scatter with Broadband Thermal Noise

Introduction. We have considered stimulated Brillouin scatter (SBS) in an inhomogeneous plasma, taking into account the existence of broadband thermal noise, from which SBS can grow. The interest in this somewhat unusual limit of SBS lies in the fact that, for real laser-fusion plasmas, the physical length of the underdense region can be larger than the gradient scale lengths characterizing

Fig. 3-35. Output for simulated irradiation of Au disk, showing spatial profiles at peak of laser pulse.

velocity and density variations. Under these conditions,¹⁴⁴ the incident light wave couples resonantly with a different frequency component of the thermal noise at each point in the gradient. In this case, we should take account of contributions to SBS from all the different frequencies to find the total amount of backscatter and the total amount of light reaching the critical surface.

To do so, we shall derive a nonlinear equation governing the depletion of the pump wave by backscatter as it propagates toward the critical surface. We solve this equation, first neglecting and then including classical absorption (inverse bremsstrahlung). The solutions predict that, when the incident intensity is below a given threshold value, virtually all the incident light energy reaches the critical surface. For intensities above this threshold, when inverse bremsstrahlung is small, we predict the maximum intensity, $I_{\max}$, of light that can reach critical. When classical absorption is not negligible, we likewise predict the maximum intensity that can be absorbed by inverse bremsstrahlung.

Equation for the Pump-Wave Amplitude.

We consider an inhomogeneous plasma with velocity gradient length, L_g . We neglect multiple backscattering and assume that SBS is convective and that the ion acoustic waves remain linear. Under these circumstances, noise of a given frequency, ω , is resonant at a particular resonant position, $x_r(\omega)$, and SBS amplifies each particular frequency component of thermal noise by the factor¹⁴⁵ $\exp Q(x_r)$, where

$$Q(x) = \frac{\pi^2}{2} \frac{n(x)}{n_c} \frac{I_0(x)}{c n_e T_e} \frac{L_g}{\lambda_0} \quad (56)$$

Here, n is the electron density, n_c is the critical density, I_0 is the pump wave intensity, T_e is the electron temperature, and λ_0 is the wavelength of the pump wave.

In this limit, where L_g is less than the physical length of the plasma, L , the ion-wave damping rate, ν_i , does not affect the total SBS amplification. This is a consequence of the plasma inhomogeneity.¹⁴⁶ For a given noise frequency, the three wave-matching conditions are only satisfied over a distance, $(\nu_i/\omega_{ia})L_g$, around the point of exact resonance. Here, ω_{ia} is the ion acoustic frequency. Within this distance, the SBS spatial amplification rate is proportional to

ω_{ia}/ν_i . Thus, the damping cancels out when the total amplification (the rate times the distance) is calculated.

The total change in the pump intensity as it propagates toward critical is found by summing over many different noise frequencies, each of which is amplified by an equation analogous to Eq. (56). When the condition

$$\left(\frac{\nu_i}{\omega_{ia}} \right) L_g \ll L \quad (57)$$

is satisfied, each frequency component undergoes amplification over only a small portion of the total underdense plasma. This is shown schematically in Fig. 3-36, which illustrates the amplification profile of a fixed-frequency noise wave in an inhomogeneous plasma. Therefore, we consider the pump-wave electric field as roughly constant over each of these small-scale amplification regions. The total loss rate of pump intensity, I_0 , is thus

$$\frac{dI_0(x)}{dx} = \int d\omega \left(\frac{dI_N}{d\omega} \right) \exp Q(x) \delta[x - x_r(\omega)] \quad (58)$$

For simplicity, consider a case where the noise source is uniform: $dI_N/d\omega = \text{constant}$. Then, Eq. (58) integrates to

$$\frac{dI_0(x)}{dx} = \left[\frac{dI_N}{d\omega} \left(\frac{dx_r}{d\omega} \right)^{-1} \right]_{x=x_r} \exp Q(x) \quad (59)$$

When inverse bremsstrahlung absorption is important, the additional term $\kappa_{ib}(x)I_0(x)$ must be added to the right side of Eq. (59).

Fig. 3-36. Amplification profile of a fixed-frequency noise wave in an inhomogeneous plasma.

Solutions Without Inverse Bremsstrahlung.

First, we describe the solutions to Eq. (59) without classical absorption. The quantity $(dx_r/d\omega)_{x=x_r}$ in Eq. (59) can be shown to be of order L_g/ω_s , and the left side of Eq. (59) is of order I_0/L_g . Thus, the factor in square brackets on the right side of Eq. (59) is small compared to the left side of Eq. (59),

$$\frac{\left(\frac{dI_N}{d\omega}\right)\left(\frac{dx_r}{d\omega}\right)^{-1}_{x=x_r}}{dI_0/dx} \sim \frac{I_N}{I_0} \ll 1, \quad (60)$$

when the noise level, I_N , is due to thermal fluctuations. (Reference 147 describes the case where there is a large noise level due to light backreflected from the critical surface. Here, we assume that $I_N \ll I_0$.)

Now imagine beginning to propagate the pump wave, $I_0(x)$, into the plasma, starting from low-density regions where $n(x) \ll n_c$ (Fig. 3-37). The quantity $Q(x)$ in Eq. (59) can be rewritten as

$$Q(x) = \frac{\pi^2}{2} \frac{n(x)}{n_c} \frac{L_g(x)}{\lambda_0} \frac{I_0(x)}{cn_c T_e} \equiv f(x) I_0(x) \quad (61)$$

In general, $f(x)$ will increase as the density, n , increases. At very low densities (large x), $f(x)$ is tiny, and the right side of Eq. (59) is small, of order I_N/I_0 relative to the left side. As a result, the pump intensity, I_0 , remains constant at its initial value, I_0^0 . Indeed, the right side of Eq. (59) will continue to remain small relative to the left side until the pump has propagated to a position such that

$$Q(\hat{x}) = \hat{Q} \equiv \ln(I_0^0/I_N) \sim 15 - 25 \quad (62)$$

for plausible noise levels. Before this point is reached, $I_0(x) \cong I_0^0$.

From the point $\hat{x}$ on, the right side of Eq. (59) is large enough to make I_0 decrease on a

length of order L_g . However, even a tiny change in the value of the exponent $Q(x) = f(x)I_0(x)$ is able to make a drastic change in the value of dI_0/dx . For example, if at some x , $I_0(x)$ were to become just a bit larger than $\hat{Q}/f(x)$, then dI_0/dx would become very large and negative, thus bringing I_0 back to the value $\hat{Q}/f(x)$. Conversely, if $I_0(x)$ were smaller than $\hat{Q}/f(x)$, I_0 would remain constant for a while until $I_0 f(x)$ could again rise to the value $\hat{Q}$. Thus, we conclude that $I_0(x)$ must stay practically equal to the value of $\hat{Q}/f(x)$ as the pump propagates toward the critical surface.

The solution of Eq. (59) is thus

$$I_0(x) \equiv \min \left\{ \begin{array}{l} I_0^0 \\ \hat{Q}/f(x) \end{array} \right. = \left[\frac{\ln(I_0^0/I_N)}{\frac{\pi^2}{2} \frac{n(x)}{n_c} \frac{L_g(x)}{\lambda_0} \frac{1}{cn_c T_e}} \right] \quad (63)$$

This behavior is illustrated in Fig. 3-38. It is seen in Eq. (63) that the pump intensity, I_0 , varies on the same spatial scale as that characterizing the velocity profile.

The present model allows a prediction of the pump intensity that finally reaches the critical surface. This is of interest because of the importance of hot-electron generation, resonance absorption, and profile steepening at critical. Equation (63) says that

$$I_0(n_c) = \min \left\{ \begin{array}{l} I_0^0 \\ \frac{2}{\pi^2} \left(\frac{\lambda_0}{L_g(n_c)} \right) n_c c T_e \ln(I_0^0/I_N) \end{array} \right. \quad (64)$$

Thus, we numerically estimate the maximum intensity reaching critical as

$$I_{\max} \approx 7 \times 10^{13} \text{ W/cm}^2 \left\{ \left[\frac{\ln(I_0^0/I_N)}{20} \right] \left(\frac{1 \mu\text{m}}{\lambda_0} \right) \left(\frac{T_e}{1 \text{ kev}} \right)^{1/2} \times \left(\frac{1 \text{ ns}}{\tau_L} \right) \left(\frac{\text{A}}{Z} \right)^{1/2} \right\} \quad (65)$$

where we have taken $L_g \cong \tau_L (ZT_e/\text{Am}_p)^{1/2}$. Note from Eq. (65) that the maximum energy reaching the critical surface, $I_{\max} \tau_L$, is independent of the pulse length, τ_L .

Fig. 3-37. Plasma profile for SBS. The density decreases and the velocity increases with x .

The Role of Inverse Bremsstrahlung Absorption. In the presence of classical absorption, Eq. (59) is replaced by

$$\frac{dI_0(x)}{dx} = \left[\frac{dI_N}{d\omega} \left(\frac{dx_r}{d\omega} \right)^{-1} \right]_{x=x_r} \exp Q(x) + \kappa_{ib}(x) I_0(x) \quad (66)$$

and

$$\kappa_{ib} \approx 3.3 Z \ln \Lambda \left(\frac{1 \text{ kev}}{T_e} \right)^{-3/2} \left(\frac{1 \mu\text{m}}{\lambda_0} \right)^{-2} \times \frac{(n/n_c)^2}{(1 - n/n_c)^{1/2}} \text{ cm}^{-1} \quad (67)$$

It is clear that, when $\int_{x_c}^{\infty} dx \kappa_{ib}(x) < 1$, inverse bremsstrahlung is not important, and the results of the previous discussion hold. Here, x_c is the position of the critical surface.

The more interesting case is where the optical depth of inverse bremsstrahlung reaches unity at some position, x_{ib} , in the underdense plasma:

$$\int_{x_{ib}}^{\infty} dx \kappa_{ib}(x) \approx 1 \quad (68)$$

In this situation, there are two different types of behavior, depending on the value of $Q(x_{ib})$:

- Case 1: $Q(x_{ib}) < \ln(I_0^0/I_N)$. When $Q(x_{ib}) < \ln(I_0^0/I_N) \equiv \hat{Q}$, it is clear that Brillouin scatter never becomes important. This is because inverse bremsstrahlung makes the pump intensity, $I_0(x)$, decrease even faster than $1/f(x)$, so that the threshold condition $Q = \hat{Q}$ is never attained. In this limit, the absorption fraction on the way to the critical surface is just $1 - \exp(-\int_{x_c}^{\infty} \kappa_{ib}(x) dx)$.
- Case 2: $Q(x_{ib}) > \ln(I_0^0/I_N)$. In this situation, both inverse bremsstrahlung and Brillouin scatter play important roles. The Brillouin gain is proportional to n/n_c , while inverse bremsstrahlung absorption is proportional to $(n/n_c)^2(1 - n/n_c)^{-1/2}$. Hence, inverse bremsstrahlung dominates at high densities, while SBS is more important at low densities.

Figure 3-39 illustrates the evolution of the pump intensity in this case. Assume that $I_0^0 > \hat{Q}/f(x_c)$, so that SBS is important somewhere in the underdense plasma. At

large x (low values of n/n_c), inverse bremsstrahlung is negligible. We have $I_0^0 f(x) < \ln(I_0^0/I_N)$, and the pump intensity stays constant in space until the position $\hat{x}$ is reached, where $I_0^0 f(\hat{x}) = \ln(I_0^0/I_N) \equiv \hat{Q}$.

Between $x = x_c$ and $x = x_{ib}$, defined in Eq. (68), the evolution of the pump intensity is roughly the same as in the case of zero classical absorption: $I_0(x) \approx \hat{Q}/f(x)$. Thus, we see that, until the position x_{ib} , where $\int_{x_{ib}}^{\infty} dx \kappa_{ib}(x) \approx 1$, the pump intensity behaves approximately as in Eq. (63).

For $x < x_{ib}$ [i.e., at densities higher than $n(x_{ib})$], the inverse bremsstrahlung term on the right side of Eq. (66) becomes larger than the Brillouin scatter contribution

$$\frac{\kappa_{ib}(x) I_0(x)}{\frac{dI_N}{d\omega} \left(\frac{dx_r}{d\omega} \right)^{-1} \exp Q(x)} \sim \frac{\kappa_{ib} I_0^0}{\frac{I_N}{L_g} \exp \hat{Q}} \sim \kappa_{ib} L_g > 1 \quad (69)$$

for $x < x_{ib}$. Thus, between the critical surface and x_{ib} , inverse bremsstrahlung dominates, and we have

Fig. 3-38. Pattern of pump depletion, $I_0(x)$, for case when inverse bremsstrahlung is negligible.

Fig. 3-39. Pattern of pump depletion, $I_0(x)$, for case of strong inverse bremsstrahlung.

$$I_0(x) \equiv [\hat{Q}/f(x_{ib})] \exp \int_x^{x_{ib}} dx \kappa_{ib}(x), \quad (70)$$

$$x < x_{ib}$$

In particular, the maximum absorbed intensity is roughly $I_{\max}^{\text{abs}} \approx \hat{Q}/f(x_{ib})$, or

$$I_{\max}^{\text{abs}} \approx \frac{2}{\pi^2} \frac{n_c}{n(x_{ib})} \left(\frac{\lambda_0}{L_g(x_{ib})} \right) n_c T_e \ln(I_0^0/I_N). \quad (71)$$

We can estimate the numerical magnitude of the maximum absorption by using a simple model for the density profile, $n(x)/n_c = \exp(-x/L_g)$, and assuming uniform electron temperature. We then have $x_{ib} \approx K(n/n_c)^2$, where $K = \text{constant}$, and

$$\frac{n(x_{ib})}{n_c} \equiv \left[\frac{2}{L_g K} \right]^{1/2} \quad (72)$$

Substituting this expression into Eq. (71), we find that the maximum absorbed intensity is approximately

$$I_{\max}^{\text{abs}} \approx 2 \times 10^{14} \frac{\text{W}}{\text{cm}^2} \left[\left(\frac{Z}{10} \right)^{1/2} \left(\frac{1 \mu\text{m}}{\lambda_0} \right)^2 \times \left(\frac{1 \text{ nsec}}{\tau_L} \right)^{1/2} \right], \quad (73)$$

where we have assumed $\ln(I_0^0/I_N) = 20$, $A/Z = 2$, and $\ln \Lambda = 10$.

Thus, the absorption increases for shorter laser wavelengths and higher- Z target materials, consistent with usual inverse bremsstrahlung scalings. Note, however, that the maximum absorbed intensity falls as the pulse length becomes longer. This is because longer laser pulses produce longer gradients in the low-density plasma; thus, they favor SBS over inverse bremsstrahlung absorption. The total absorbed energy, $I_{\max}^{\text{abs}} \tau_L$, does increase at longer pulse lengths, $\propto \tau_L^{1/2}$, due to the effect of inverse bremsstrahlung. (Recall that, without classical absorption, we showed previously that the maximum energy reaching critical was independent of pulse length.)

Summary. We have developed a new model for Brillouin scatter, taking into account both broadband thermal noise and inverse bremsstrahlung absorption. This

model predicts that, when classical absorption is weak, there is a maximum intensity that can reach the critical surface, which is of order 10^{14} W/cm^2 for nanosecond laser pulse lengths. When inverse bremsstrahlung is strong, the model yields a maximum absorbed intensity of the order of 10^{15} W/cm^2 for nanosecond pulse lengths and moderate- Z target materials.

Author: C. E. Max

Major Contributors: A. Ramani and R. Pellat
(École Polytechnique, Palaiseau, France)

Filamentation Growth Rates in Collisional ICF Plasmas

Thermal self-focusing of laser light results from electron density depressions, at peaks of the light intensity, due to thermal pressure resulting from locally increased heating by inverse bremsstrahlung. This mechanism may become important in a collisional underdense plasma in large targets. We have done some analysis to help determine when this thermal mechanism dominates the more-familiar ponderomotive force mechanism and to estimate the time scales for thermal self-focusing.

Consider a filamentary perturbation with growth rate, γ , and wave vector, k , perpendicular to laser-light wave vector, k_0 . In a plasma region that is homogeneous to zero order, we find the density, $n_e^{(1)}$, and temperature, $T^{(1)}$, responses to the nonuniformity in light intensity by linearizing the hydrodynamic and heat flow equations

$$\left(\frac{\gamma^2}{k^2 c_s^2} + 1 \right) n_e^{(1)} T = - n_e T^{(1)} - \frac{1}{2} n_e T \frac{(\bar{v}_0^2)^{(1)}}{v_e^2} \quad (74)$$

and

$$\left(\frac{3}{2} \gamma + \frac{128}{3\pi} \frac{v_e^2}{v_{ei}} + \frac{3}{4} \nu_{ei} \frac{v_0^2}{v_e^2} \right) n_e T^{(1)} = \left(\gamma + \nu_{ei} \frac{v_0^2}{v_e^2} \right) n_e^{(1)} T + \frac{1}{4} n_e m_e \nu_{ei} \frac{(\bar{v}_0^2)^{(1)}}{v_e^2} \quad (75)$$

Here, v_0^2 is the peak electron oscillation velocity in the electromagnetic field, $(v_0^2)^{(1)}$ is the light intensity perturbation given in terms of the mean-squared oscillation velocity, $v_e^2 = T/m_e$, c_s is the isothermal sound speed, and ν_{ei} is the electron-ion scattering frequency. Other symbols have their usual meanings. The intensity perturbation is found from $n_e^{(1)}$ by the method that is standard in analysis of ponderomotive-force filamentation. Consistency of the three perturbations gives the dispersion relation

$$\left(1 + \frac{4\gamma^2 \omega_0^2}{c^4 k^4}\right) \left[1 + \frac{\gamma^2}{k^2 c_s^2} + \frac{1}{A} \left(\frac{\gamma}{\nu_{ei}} + \frac{v_0^2}{v_e^2}\right)\right] = \frac{1}{2} \frac{\omega_p^2}{c^2 k^2} \frac{v_0^2}{v_e^2} \left(1 + \frac{1}{2A}\right), \quad (76)$$

where

$$A = \frac{3}{2} \frac{\gamma}{\nu_{ei}} + \frac{128}{3\pi} k^2 \lambda_{mfp}^2 + \frac{3}{4} \frac{v_0^2}{v_e^2}, \quad (77)$$

in which $\lambda_{mfp} = v_e/\nu_{ei}$ is a scattering mean free path. On the right-hand side are the terms driving filamentation; on the left-hand side are opposing and response terms. In the limit $A \rightarrow \infty$, we recover the ponderomotive filamentation dispersion relation.

Several effects retard the growth of thermal filaments. As the plasma is heated locally in the filament, $T^{(1)}$ is reduced by pdV work due to expansion, by heat capacity and conduction, and by the reduction in inverse bremsstrahlung opacity due to temperature rise. These effects contribute to the term A , which must be less than unity if thermal filamentation is to dominate the ponderomotive mechanism. We find that the growth times are always longer than the electron scattering time ($\gamma \gtrsim \nu_{ei}$), that the beam (or filament) radius must be many ($\lesssim 10$) electron mean free paths in size ($k\lambda_{mfp} \gtrsim 1$), and the intensity must be low ($v_0^2 \gtrsim v_e^2$, or $I\lambda_m^2/T_e \gtrsim 10^{16}$). Outside these regimes, the ponderomotive force mechanism is dominant, and the thermal mechanism may be ignored.

Numerical solutions of Eq. (76) determine minimum growth times and clarify the competition of the two mechanisms. The time scale for thermal filamentation can be

very short compared to laser pulse lengths; e.g., we find numerically a growth time of 1 ps for 0.25- μ m light at an intensity of 4×10^{14} W/cm² in a 1-keV, $Z = 25$ plasma at an electron density of 8×10^{21} cm⁻³ (one-half the critical density). The thermal mechanism extends the parameter regime in which filamentation may be relevant to laser fusion.

Author: A. B. Langdon

Implicit Large-Timestep Particle Simulations

We have made several advances in the quest for more efficient simulation of low-frequency plasma phenomena. Our most adaptable and reliable tools for study of kinetic plasma behavior are the particle codes, but the stability of these codes has previously required resolution of the electron plasma period in the time integration, even when the phenomenon under study took place on the much-longer ion time scale.

Analogous limitations on time step in other problems, such as heat-flow and chemical-rate equations, are overcome through the use of implicit time integration schemes. In particle codes, although implicit methods have been analyzed theoretically,¹⁴⁸ their application has been inhibited by the very large number of nonlinear equations to be solved simultaneously, about equal to the number of particle coordinates plus the number of zone quantities (electric and magnetic fields).

We have begun to experiment with two methods for solution of these equations in two steps. In both methods, equations are first set up for the fields. Although these equations involve information from the particles, the number of equations to solve simultaneously is only the number of field quantities, defined on the zones. Since the number of zones is much less than the number of particles, and the resulting matrix equations are sparse and of low bandwidth, their solution is convenient with known methods. Once the fields are known, the particle coordinates can be readily solved in a serial manner, one particle at a time. Here, we will discuss simulations having only the electrostatic field.

First, we consider finite-difference equations of motion for the particles that have the necessary stability at large time-step and are accurate for the low-frequency phenomena to be studied. In Ref. 149, a centered expression for the time derivative is employed. In Ref. 150, the derivatives are biased, using a scheme such as

$$v_{n+1} - v_n = \left(\frac{3}{4} a_{n+1} + \frac{1}{4} a_{n-1} \right) \Delta t \quad (78)$$

and

$$x_{n+1} - x_n = \left(\frac{3}{4} v_{n+1} + \frac{1}{4} v_{n-1} \right) \Delta t \quad (79)$$

where subscripts denote time levels.

This scheme damps unwanted high-frequency oscillations, while low frequencies are very weakly damped, as desired: $(\text{Im}\omega)/\omega = O(\omega\Delta t)^3$. Such schemes are members of a class whose application to plasma simulation has been analyzed in detail in Ref. 148 and in our present work. We have also devised a different class of schemes, whose simplest members are

$$2(v_{n+1/2} - v_{n-1/2}) - (v_{n-1/2} - v_{n-3/2}) = a_{n+1}\Delta t \quad (80)$$

and

$$x_{n+1} - x_n = v_{n+1/2}\Delta t \quad (81)$$

This scheme has the same order of accuracy as Eqs. (78) and (79), while requiring less storage of time levels. The presence of the acceleration at only the $n+1$ time level increases the damping of high-frequency oscillations. The optimum design of these difference equations is the first issue in practical implementation of large time-step methods.

In all implicit schemes, the new positions, x_{n+1} , depend on the accelerations, a_{n+1} , due to the electric field, E_{n+1} . But this field is not yet known, as it depends on the density ρ_{n+1} of particle positions $\{x_{n+1}\}$. The solution of these coupled particle and field equations is the other major implementation issue.

In the first method to be tried for this solution, the fields at the new time level are predicted by solving coupled field and fluid equations, in which the pressure tensor is

approximately evaluated from particle velocities known at the earlier time. After the fields are known, the particles are advanced to the new time level, and, if desired, an improved pressure tensor is calculated and the process iterated. This approach has been described in detail in Refs. 149 and 150.

It is also practical to predict the future electric field, E_{n+1} , quite directly by means of a linearization of the particle-field equations. Since this method and its implementation in the experimental code BAAL have not been described previously, we outline the concept here.

The position x_{n+1} of a particle at time level t_{n+1} , as given by an implicit time-integration scheme, can be written as

$$x_{n+1} = \beta\Delta t^2 a_{n+1} + x_{n+1}^{(0)} \quad (82)$$

where $0 < \beta \lesssim 1$ and $x_{n+1}^{(0)}$ is the position obtained from the equation of motion with the acceleration a_{n+1} neglected. Since $x_{n+1}^{(0)}$ depends only on positions and accelerations at times t_n and earlier, it is known. In its simplest form, the BAAL algorithm is derived by linearization of the particle positions relative to $x_{n+1}^{(0)}$.

We can regard the actual position, x_{n+1} , as $x_{n+1}^{(0)}$ plus a displacement $\delta x = \beta\Delta t^2 a_{n+1}$. Form the charge density $\rho_{n+1}^{(0)}$ from $\{x_{n+1}^{(0)}\}$; the actual charge distribution is then $\rho_{n+1}^{(0)}$ plus the change $\delta\rho$ brought about by displacing particles by the amount $\delta x = x_{n+1} - x_{n+1}^{(0)}$. Linearized, this increment to ρ is (Ref. 148)

$$\delta\rho = -\nabla \cdot [\rho_{n+1}^{(0)}(x) \delta x(x)] \quad (83)$$

To the same order of approximation, the displacement $\delta x(x)$ of all particles with $x_{n+1}^{(0)} \cong x$ is obtained with a_{n+1} evaluated at x , i.e.,

$$\delta x(x) \cong \beta\Delta t^2 (q/m) E_{n+1}(x) \quad (84)$$

We then have

$$\delta\rho(x) = -\nabla \cdot [\chi(x) E_{n+1}(x)] \quad (85)$$

where the effective susceptibility is

$$\chi(x) = \beta[\rho_{n+1}^{(0)}(x) q/m] \Delta t^2 = \beta\omega_p^2(x) \Delta t^2 \quad (86)$$

Note that χ depends only on the particle positions $\{x_{n+1}^{(0)}\}$ and not at all on velocity

information, as required in the moment equation methods.

With these two source contributions, the Poisson equation becomes, in rationalized cgs units,

$$\nabla \cdot \mathbf{E}_{n+1} = \rho_{n+1}^{(0)} - \nabla \cdot (\chi \mathbf{E}_{n+1}) \quad (87)$$

or

$$-\nabla \cdot [1 + \chi] \nabla \phi_{n+1} = \rho_{n+1}^{(0)} \quad (88)$$

This elliptic equation is solved by standard methods. The field $-\nabla \phi_{n+1}$ and Eq. (84) are then used to calculate the positions, $\{x_{n+1}\}$. This algorithm is reminiscent of the method for solution for the vector potential, A , in some magnetostatic plasma simulation codes.^{151,152}

Should it be necessary, we have shown how to refine the approximations used above by linearization about a more-accurate prediction of x_{n+1} than $x_{n+1}^{(0)}$, by iteration, and by a more-accurate evaluation of δx .

In our spatial-difference representation of these equations, Eq. (83) becomes the gradient of a zonal ϕ with respect to particle position, and δx in Eq. (84) depends on the electric field in two zones, using the usual interpolation. In this way, we are assured that the density ρ_{n+1} of final particle positions $\{x_{n+1}\}$ satisfies the code's representation of the Poisson equation, $-\nabla^2 \phi_{n+1} = \rho_{n+1}$, so that desirable features built into the time-differencing scheme will be realized in practice.

We are delineating the limitations of these methods and learning how to surmount them. For example, it is observed that a nonphysical cooling of the electrons occurs when uncentered equations of motion are used. This side effect is related to the damping of low-frequency oscillations; both are smaller in our scheme above with third-order damping than in lower-order algorithms.¹⁴⁹ Our analysis provides guidance to design algorithms that retain desirable dissipation of high-frequency oscillations while minimizing this unwanted cooling.

Both the moment equation formulation of Ref. 149 and the BAAL approach have been verified in application to ion-acoustic oscillations, two-stream instability, and corona expansion into vacuum, where results have already been obtained by methods

whose reliability is known but which are less efficient in these problems. The moment equation method is being applied to electron transport.¹⁴⁹

Authors: A. B. Langdon, A. Friedman, B. I. Cohen, and J. Denavit (Northwestern University, Evanston, Ill.)

Relevance of Ion-Acoustic Instability to Thermal-Transport Inhibition in Plasmas Produced by Nd Lasers

Introduction. A number of researchers have reported inhibited thermal-electron transport in laser-heated plasmas. Some of the most quantitative measurements to date have been performed using 1.06- μm Nd lasers to irradiate low-Z foil, disk, or layered-disk targets with ~ 100 -ps pulses at intensities of 10^{15} to 10^{16} W/cm².¹⁵³⁻¹⁵⁸

Under these conditions, the laser-plasma interactions are largely collective.¹⁵⁴ The energy absorbed at the critical density (n_{crit}) is partitioned between a cool (~ 1 - to 2-keV) background group of thermal electrons (with $n_t \sim n_{\text{crit}}$) and a hot (~ 10 -keV) suprathermal electron group ($n_s \sim 0.01$ to $0.1 \times n_{\text{crit}}$).

In these plasmas, the electron mean free path is longer than the density scale height. A crude idea of the magnitude of energy transport can be obtained using the free-streaming limit

$$Q_{fs} = n_e m_e v_e^3 \equiv n_e (kT_e)^{3/2} \quad (89)$$

To apply this to laser-heated plasmas, the heat-flux estimate is usually made using a flux-limit factor, f . Heuristic arguments for Maxwellian distributions have typically placed $f \approx 0.2$ to 0.6 (Ref. 159). Naively, then, in our laser-heated example, we would expect energy flux to be carried roughly equally by thermal and suprathermal electrons, since $n_t T_t^{3/2} \sim n_s T_s^{3/2}$.

However, calculations that attempt to self-consistently model the energy deposition, transport, and hydrodynamics have shown that calculated ion and x-ray emission properties generally agree best with experiments^{153,154,156-158} under the assumption

that $f_i \leq 0.03$. That is, the transport due to thermal electrons must be reduced by a factor of $\lesssim 10$ from that that might be considered "classical."

We note here the importance of self-consistency: to derive transport coefficients from a hydrocode simulation of an experiment, all energy deposited must be accounted for quantitatively. We also note that most hydrocodes use flux-limited diffusion and have various levels of approximation in the electric-field coupling between thermal and suprathermal electrons. Other aspects of the modeling can alter the inferred transport coefficients to some extent, as well.

Electron transport coefficients have been inferred from three main types of plasma diagnostics. We believe the x-ray emission from the overdense plasma is one of the most reliable indicators of electron transport coefficients. When x-ray imaging or target layering is used to diagnose the extent of the heated region, the most direct and model-independent connection with electron transport can be made. Ion measurements indicating behavior of thin-foil disassembly are also somewhat useful, although great care is required to avoid systematic errors in the use of ion charge collectors. Lowest confidence is placed in inferring transport properties from absorption calculation, since the absorption processes themselves are highly nonlinear and not understood sufficiently quantitatively.

Based upon the calculational and diagnostic criteria, we find indications, as stated previously, that thermal electron transport is reduced by a factor of ≥ 10 from classical expectations. The experimental and calculational bases of this inhibition are broad and, taking all results together, the evidence is quite convincing, although other interpretations that fit some of the data have been advanced (see Refs. 160 and 161 and "Analysis of Short-Pulse Absorption Experiments at 1.06-, 0.53-, and 0.27- μm Laser Wavelengths" in this section).

The ion-acoustic instability has been suggested^{153,162} as one mechanism that could produce thermal-electron transport inhibition. We have specifically examined the behavior of the ion-acoustic instability as observed using two-dimensional particle-in-cell computer simulations. In this report, we discuss the published work of several

researchers, and we find agreement among the simulations of various workers at the order-of-magnitude level. We show that the anomalous collision frequencies derived from particle simulations of the ion-acoustic instability are much too small to account for the transport inhibition inferred from plasmas irradiated with Nd lasers. Finally, we discuss some of the laser-fusion plasma conditions that have been omitted from the simulations.

Simulation Characteristics. Particle simulations are a very general and brute-force technique for studying plasma phenomena. As a result, they offer an opportunity to glimpse details of plasma behavior that are inaccessible to both theoretical models and real plasma diagnostics. Associated with this advantage are the burdens of overcoming computational speed and cost limitations and of understanding complex interactions. We limit attention here to simulations that adequately pass certain basic requirements for qualitative and quantitative realism.

We consider only two-dimensional calculations, since the "large"-amplitude behavior of ion-acoustic turbulence depends on the existence of a broad angular spectrum of wave $\vec{k}$ - vectors.¹⁶³⁻¹⁶⁵ Three-dimensional effects are crudely determined¹⁶⁶ to be only moderately significant (probably less than a factor of 3 change in anomalous collision frequency).

We require a minimum spatial resolution of 6 cells per wavelength. Since the fastest-growing linearly unstable mode, k_w , satisfies $k_w \lambda_D \approx 0.5$ to 1.0, the cell dimension must be ~ 0.5 to 1.0 Debye length (λ_D). We also require that the system size be greater than $\sim 30\lambda_D$, so that periodic boundary conditions do not limit the modes that can grow.

We are forced to rely mainly upon simulations that predate laser-fusion applications. The boundary conditions used in all published work to date are periodic, with a one-dimensional applied electric field or a current resulting from an initial drift of electrons relative to ions. Some simulations have investigated effects of a weak imposed magnetic field perpendicular to the current, either in or perpendicular to the simulation plane.¹⁶⁵ Some differences in behavior arise with various boundary conditions. None of the published simulations represent all of the physics

occurring in a laser-produced plasma. In particular, the use of drifting Maxwellian is quantitatively and, perhaps, qualitatively different from the physical situation of interest to many laser-fusion applications: heat-conduction in a steep temperature (and density) gradient.

Several factors influence numerical accuracy and noise, including choices of code algorithms. The time step must be short compared with the electron plasma period, ω_{pe}^{-1} . Typically, $\Delta t \gtrsim 0.5 \times \omega_{pe}^{-1}$. The numbers of particles per cell and per Debye-sphere affect numerical noise, as well. Empirical tests must be performed to show that numerical heating of the particles is negligible for the simulations considered.

The realism, simulation run time, and cost are tied to the ion-electron mass ratio, M_i/m_e . This occurs because ion turbulence evolves on an ion-acoustic time scale, with the sound speed $c_s \propto \sqrt{M_i}$, while the fastest time scale is $\omega_{pe} \propto 1/\sqrt{m_e}$. We consider only work that uses mass ratios of 100 to 1600, large enough to unambiguously separate ion and electron time scales.

General Ion-Acoustic Instability Behavior.

Several overall characteristics of particle simulations are in agreement with expectations of theory. The ion-acoustic instability arises when $T_e \gg T_i$ and a current flow drives an electron drift with velocity $v_d > c_s$, the ion sound speed. The mechanism of growth is inverse Landau damping. The electrons that have a velocity component parallel to the drift direction that matches the ion sound speed fairly well transfer their energy to ion waves. The amplitude of the waves grows, increasing the effectiveness of the transfer of energy from electrons to ions, hence yielding exponential growth in time. If $T_i \lesssim ZT_e$, the ion waves are strongly damped. These characteristics are clearly demonstrated by particle simulations.

The fastest-growing modes, theoretically, are those with $k \approx \sqrt{2/2\lambda_D^{-1}}$. Numerical simulations show fastest growth in just this region.^{163,167} The range of growing modes is "broad" in angle^{163,165} and $|\vec{k}|$ (Refs. 165 and 167) when $v_d \sim v_{Te}$.

Simulations show three distinct phases of growth of ion sound turbulence.^{164,165} The early phase grows exponentially in time. The middle phase grows roughly linearly in time and marks the onset of nonlinear modifications of the plasma processes. The final

phase is the saturated phase. Here, the behavior depends somewhat on the boundary conditions chosen, and workers differ to some extent on the late-time evolution.

We find three boundary conditions:

- Case (1). Initial drift imposed, $\vec{E} = 0$.
- Case (2). Initial drift imposed, $\vec{E}$ field applied to enforce $J = \text{constant}$.
- Case (3). The same as case (2), but with applied transverse $\vec{B}$ -field to prevent electron runaway.

In case (1) (Ref. 168), the instability dies away because the drift is not maintained. In case (2) (Ref. 164), the instability dies away, as well. This occurs partly because of a significant electron-runaway component that carries part of the current, "shorting" out the bulk drift to some extent, even though the total current, J , is held constant. Case (3) (Ref. 165) still allows the instability to die away, although somewhat more slowly. Here the electron heating and ion-tail formation result in decreased drive and increased damping for the instability. Note that T_e/T_i decreases as the simulations proceed.

The electron distribution function, f_e , changes as the electrons are heated. The enhanced collisions with the ion-wave turbulence increase the resistive heating of the electrons, raising T_e . Simulations show significant modifications to the shape of the electron distribution function as well. The portion of f_e with $v_e \approx v_d$ can be flattened somewhat,¹⁶⁸ and f_e evolves to a flat-topped, super-Maxwellian shape¹⁶⁹ in the velocity region, $|\vec{v}_e| \gtrsim v_{Te}$.

A runaway-electron tail is produced if the drift is driven by an applied electric field.¹⁶³ The population of the runaway tail seems to reach a substantial, fairly steady fraction of the total electron population.

The ion distribution function undergoes similar interactions. As the waves grow, ion trapping or nonlinear Landau damping heats the bulk of the ion distribution and, to some extent, damps wave growth. The shape of the ion distribution becomes non-Maxwellian. Ion trapping accelerates some ions to velocities comparable to the ion-wave phase velocity, up to $\sim 2 c_s$, forming a suprathermal ion tail. As this occurs, the tail ions can Landau damp the waves.

Saturation Mechanisms. Comparison of simulation results with theory helps to determine the saturation mechanism for

ion-acoustic turbulence. However, much controversy has surrounded this determination, and various groups of workers have fixed on different effects as being dominant. The difficulty arises because nearly all the simulations show that several dynamic processes occur, but many alternative estimates and theories can be forwarded to quantitatively select the dominant process.

The most long-lived and consistently defended picture selects Landau damping of the ion waves by ion tail formation as the dominant saturation mechanism.^{164,169} The field energy required for significant ion trapping has been estimated as¹⁶⁴

$$\frac{W}{nT} = \frac{1}{72} \left(1 - \sqrt{\frac{3T_i}{2T_e}} \right)^4 \quad (90)$$

This is quite a low level; much lower, for example, than estimated for nonlinear Landau damping.¹⁶⁴ It also corresponds quantitatively with the level in simulations at which the ion tail begins to form and the instability growth shifts from exponential to linear in time. Not long after this, the ion tail is fully developed and instability growth ceases.

For a closely related physical case, Lampe et al., select ion trapping and ion Landau damping on the basis of one-dimensional simulations and theoretical estimates.^{168,170} In their simulations, a weak, transverse magnetic field was applied to suppress electron runaway. However, the large-amplitude phenomenology closely follows that of ion sound, for the most part.

Table 3-7. Summary of results of published two-dimensional simulations of ion-acoustic instability.

Ref	M_i/m_e	T_e/T_i	v_d/v_e	α	β
163	100-1600	50 ^b	1.0	$2. \times 10^{-4}$	0.25
165 ^c	400-1600	50 ^b	1.0	$4. \times 10^{-4}$	(0.25)
165 ^d	400	50 ^b	1.0	1×10^{-3}	(0.25)
169 ^c	100-1600	10-50	0.7-1.0	$(4. \times 10^{-4})^e$	0.25
172 ^f	25-1600	10-50	0.5	$3. \times 10^{-5}$	0.25

^aThe parameter range studied for M_i/m_e , T_e/T_i , and v_d/v_e is shown. The parameters α and β for the scaling relation of Eq. (3), giving ν^*/ω_{pe} , are derived where possible. Values deduced with information from other sources are shown in parentheses.

^bValue at $t = 0$. Late-time value not specified.

^cA weak transverse magnetic field perpendicular to the simulation plane was applied as a boundary condition.

^dA weak transverse magnetic field in the simulation plane was applied as a boundary condition. Note that this is somewhat nonphysical and tends to increase ν^* .

^eValues of ν^* not specified. To derive values of ν^* and α , the data of Ref. 163 were used to infer ν^* from $(W/nT_e)_{\max}$ of this work.

^fUsed field-smoothing operator.

Some workers¹⁶⁸ have emphasized the importance of modifications of the electron distribution function in saturating ion sound. This mechanism undoubtedly plays some role and seems theoretically to lead to turbulence levels somewhat above, but nonetheless comparable to, those seen in two-dimensional simulations.^{168,171}

Scaling Laws. Scaling laws have been sparsely derived from simulations. There are two problems with these "laws." Some workers stress that the amplitudes of the instability are so plasma-history dependent that great restraint must be applied in using scaling laws at all.^{163,164} Furthermore, the best simulations are costly and tend not to have been used for wide and detailed parameter studies.

Most simulation results for the maximum collision frequency, ν^* , can be crudely summarized by the scaling relation¹⁷² ($Z = 1$)

$$\frac{\nu^*}{\omega_{pe}} = \alpha \left(\frac{m_e}{M_i} \right)^\beta \frac{T_e}{T_i} \frac{v_d}{v_{Te}} \quad (91)$$

From the various published works, values for α , β , and ranges of M_i/m_e , T_e/T_i , and v_d/v_{Te} are presented in Table 3-7. If β could not be extracted from the reference, $\beta = 0.25$ has been assumed for the sake of deriving α in a fairly standard form. Note that three of the results in Table 3-7 include an applied magnetic field in the simulation. This does not seem to be a major influence on ν^* , except when $\vec{B}$ is in the simulation plane, where artificial electron trapping can occur.¹⁶⁵

It is difficult to consider the data of Table 3-7 as being definitive; we note significant quantitative discrepancies. Again, we note that most of the simulations were performed with $v_d/v_{Te} \sim 1$. Nonetheless, the order of magnitude of α appears likely to be $\alpha \sim 10^{-4}$. From this, for example, we calculate $\nu^*/\omega_{pe} \sim 10^{-3}$ for $M_i/m_e = 1836$, $Z = 1$, $T_e/T_i = 20$, and $v_d/v_{Te} = 1$, using the scaling of Eq. (91) with $\beta = 0.25$.

Quantitative Application to Nd-Laser Plasmas. As noted at the outset, the heat flow carried by thermal electrons appears to be reduced by a factor of 10 or more from classical expectations in many plasmas produced by Nd lasers. To reduce heat flow by a factor of ~ 10 below classical, the

electron collision rate must be enhanced by a factor of ~ 10 above the classical electron-ion collision rate, ν_{ei} . Let us ask whether ion sound can produce the required collision enhancement.

First, we calculate the classical electron-ion collision frequency in such a plasma. We assume $n_e = 10^{21}$ electrons/cm³, $Z = 4$, $\ln \Lambda = 7$, and $T_e = 1$ keV. Classically, the heat flow is mainly carried by electrons with energy in the range of 2 to 3 kT_e , so we take $\epsilon_e = 2$ keV. This gives $\nu_{ei}/\omega_{pe} \approx 1.4 \times 10^{-3}$. Hence, the classical mean free path for these electrons is $\lambda_{MFP} \approx 7 \mu\text{m}$. This is somewhat longer than the expected scale length near the critical surface, so, classically, the free-streaming heat-flux estimate made with $f = 0.2$ to 0.6 might be expected to be relevant. Therefore, a collision frequency of $\lesssim 10^{-2} \omega_{pe}$ is necessary to decrease the heat flux to the value inferred from experiments.

Next, we find the relevant anomalous collision frequency. We note that, for this plasma, $ZT_e/T_i \approx 40$ to 80 is reasonable. However, v_d/v_{Te} is probably somewhat lower than used for the estimate above, say $v_d/v_{Te} \approx 0.1$ to 0.3 . This places $\nu^*/\omega_{pe} \approx 0.5$ to 3.0×10^{-4} . This collision frequency is lower than ν_{ei} by a factor of ~ 10 and is a factor of ~ 100 below the value required to reduce the heat flow to the desired level.

So, we see that the order of magnitude of the anomalous collision frequency due to ion sound seems too low to account for the anomalous flux limitation seen in low- Z , Nd-laser-produced plasmas. This occurs because classical collisional rates are significant and the electron drift speeds are rather low in the plasma of interest here.

Remaining Issues. Finally, we note that there are hopeful directions, or at least serious questions, that need to be answered before dismissing the relevance of ion sound to laser-fusion plasmas.

Recently, interest has grown in the area of double layers: localized, large ion-density fluctuations that can enhance plasma resistivity.^{173,174} Although this does not so far look quantitatively much more attractive than ion sound, and still seems to require $v_d/v_{Te} \sim 1.0$, the phenomenon can create $\nu^*/\omega_{pe} \approx 0.03$ at high drifts. Can this process produce significant turbulence at lower v_d/v_{Te} ?

Within the confines of short-wavelength ion turbulence itself, we find that there

remains some work to be done before the scenario presented above can be considered definitive. Even for the simplest case discussed here, discrepancies of a factor of 10 exist among simulation results of various workers. Perhaps more importantly, none of the simulations to date have incorporated laser-fusion physics in much detail. For example, effects of steep gradients in T_e , T_i , and n_e and the presence of convection might significantly alter the dynamics of ion sound growth, saturation, and long-time evolution. The results of driving ion sound using a thermal-conduction source may differ from those obtained using current drive. Also, the presence of the laser light itself, and the localized energy deposition near the critical density, has been shown to produce various turbulent effects.¹⁷⁵ Perhaps examination of some of these effects, coupled with more direct attention to heat-flow rates, would reveal a significant effect.

Summary. Levels of ion turbulence and effective collision frequency observed in two-dimensional plasma simulations seem to agree only at the order-of-magnitude level and apply only to the simplest possible plasma conditions. Based on the simulation results available to date, no convincing connection can be drawn between ion sound and thermal-transport inhibition in Nd-laser-produced plasmas. Serious omissions from particle simulations to date must be addressed before dismissing this mechanism entirely.

Author: W. C. Mead

Major Contributors: A. B. Langdon, D. Colombant (Naval Research Laboratory), M. G. Haines (Imperial College, London), and P. Holstein (C. E. A. Limeil)

Anomalous DC Resistivity Due to Ion Turbulence

Introduction. In laser-driven pellets, hot electrons leave the critical surface and enter the corona. Then, cold electrons must return to the critical surface to maintain charge neutrality.¹⁷⁶ If the return current is above a threshold, then ion waves are driven by the drift instability. The threshold is a function of ZT_e/T_i ; e.g., for $ZT_e/T_i = 15$, the

threshold drift velocity is $V_T \approx 0.03 v_c$, where v_c is the cold electron thermal speed, $v_c = \sqrt{kT_e/m}$. If the electron drift velocity is significantly larger than the threshold, then the ion waves will become turbulent. The electrons will be scattered by the ion turbulence, resulting in anomalous dc resistivity. Since the electron current is impressed on the plasma, a dc electric field results.

Electron Drift Velocity in Laser-Driven Pellets. We can use a simple model to calculate the electron drift velocity in laser-driven pellets; this model is shown in Fig. 3-40. The density, n_u , is determined by the ponderomotive force of the electromagnetic and electrostatic waves. We assume that hot electrons do not return to the critical surface (this will give an upper limit on the electron drift velocity). Then, equating the current of hot electrons to the return current of cold electrons, we obtain

$$n_u V_d = \sqrt{\frac{2}{\pi}} n_h v_h = \frac{q_h}{KT_h} = \frac{fI}{KT_h} \quad (92)$$

where V_d is the electron drift velocity. Here, we have assumed that the hot electrons have a half-Maxwellian velocity distribution. We can express Eq. (92) as

$$\frac{V_d}{v_c} = A \frac{fI\lambda^2}{T_c^{3/2}} \left(\frac{n_c}{n_u} \right) \left(\frac{T_c}{T_h} \right) \quad (93)$$

where A is a constant. We use a simplified theory¹⁷⁷ of resonant absorption for $ZT_e/T_i \gg 1$ (see "Absorption, Electron Heating, and Electron-Energy Transport in Microwave Simulations of P-Polarized Laser Light-Plasma Interactions" in this section), and obtain

$$\frac{V_d}{v_c} = 3.9 \times 10^{-8} \left[\frac{fI\lambda^2}{T_c^{3/2}} \right]^{0.68} \left(\frac{n_c}{n_u} \right) \quad (94)$$

Fig. 3-40. Schematic of the plasma density profile near the critical surface.

where the units are I (W/cm^2), λ (μm), and T_e (eV). The density of the overdense region, n_u , is calculated using a fluid code for p-polarization (see "Absorption, Electron Heating, and Electron-Energy Transport Inhibition Due to Ion Turbulence" in this section). We find that $n_u/n_c \approx 1$ for $v_{os}/v_e^2 \ll 1$ and that $n_u/n_c \approx v_{os}^2/2v_e^2 \propto I\lambda^2/T_e$ for $v_{os}^2/v_e \gg 1$. Thus, we see that the drift velocity increases with power for low power ($v_{os}^2/v_e^2 \ll 1$); i.e., $V_d/v_c \propto [fI\lambda^2/T_c^{3/2}]^{0.68}$ and decreases slowly with power for high powers ($v_{os}^2/v_e^2 \gg 1$); i.e., $V_d/v_c \propto f^{0.68}/(I\lambda^2)^{0.32}$. The largest value occurs near $v_{os}/v_e \approx 1$ and for a typical case ($I = 10^{15} \text{ W}/\text{cm}^2$, $f = 0.3$, $\lambda = 1.06 \mu\text{m}$, and $T_c = 0.4 \text{ keV}$) we obtain (Ref. 176) $n_u/n_c \approx 2.4$. The peak value is about $V_d/v_c|_{\text{peak}} \approx 0.24$. This is a rather low value of the drift velocity ($V_d/v_c \ll 1$).

The Anomalous DC Resistivity at Low Drift Velocities ($V_d/v_c \ll 1$). There is an extensive literature (theoretical, computational, and experimental) on anomalous dc resistivity due to ion-acoustic turbulence. (Ref. 177 reviews most of the literature). Sagdeev¹⁷⁸ and Kadomstev¹⁷⁹ have developed an approximate theory that gives (for $ZT_c/T_i \gg 1$ and $V_d \gg V_T$) an anomalous collision frequency of

$$\frac{\nu_{\text{eff}}}{\omega_{pe}} = 10^{-2} \frac{V_d}{v_c} \frac{ZT_c}{T_i} \quad (95)$$

Eq. (95) gives a very large anomalous collision frequency; e.g., for the case above, $V_d/v_c = 0.24$ and $ZT_e/T_i = 15$, we obtain $\nu_{\text{eff}}/\omega_{pe} \approx 4 \times 10^{-2}$ from Eq. (95), or a mean free path of $\lambda_{\text{eff}} = v_c/\nu_{\text{eff}} \approx 25 \lambda_{De}$, or $\lambda_{\text{eff}} \approx 0.1 \mu\text{m}$ for $n_c \approx 10^{21} \text{ cm}^{-3}$ and $T_e = 0.4 \text{ keV}$, a very short mean free path. In addition, this collision frequency [Eq. (95)] decreases slowly with T_c ($\nu_{\text{eff}} \sim T_c^{1/2}$, since ZT_c/T_i tends to be roughly constant).

Steady-state collision frequencies this large have been measured^{180,181} at low drift velocities. In addition, the measured¹⁸² wave-number spectrum of the ion waves agree fairly well with the theory due to Kadomstev.¹⁷⁹ However, particle-simulation calculations¹⁸³ have indicated much lower collision frequencies (10 to 100 times lower). In addition, these calculations have shown that anomalous dc resistivity is a transient phenomena; i.e., on an asymptotic time scale, the effect is drastically reduced. Recent

calculations¹⁸⁴ give the asymptotic resistivity as only an order of magnitude larger than that due to binary collisions. Thus, there is apparently an enormous discrepancy between results from measurements and particle simulations.

A Simplified Model of Anomalous DC Resistivity. To gain insight into the problem, we have developed¹⁸⁵ a simplified model of anomalous dc resistivity due to ion-acoustic turbulence. The potential in the plasma has hills and valleys due to the ion-acoustic turbulence, and each hill or valley scatters the electron through a small angle. Thus, the electron random walks through the ion turbulence. The electron has traveled a mean free path when, on the average, it has been scattered through an angle of $\pi/2$. The collision frequency as a function of electron speed is given by

$$\frac{\nu_{\text{eff}}(v)}{\omega_{pe}} = \frac{\pi}{8} \langle k\lambda_{De} \rangle \frac{e^2 \langle \phi^2 \rangle}{k^2 T_c^2} \left(\frac{v_c}{v} \right)^3, \quad (96)$$

where v is the electron speed, $k\lambda_{De}$ is the average wave number of the ion waves, and $\langle \phi^2 \rangle$ is the mean square potential fluctuations due to the ion turbulence. Eq. (96) agrees with detailed theory.

The important conclusions¹⁸⁵ that result from the simplified model are

- The turbulence scatters the electrons with very little energy transfer; the waves traveling essentially perpendicularly to the direction of motion of the electron scatter that electron. Thus, the turbulence must be almost isotropic to effectively scatter electrons.
- Since the collision frequency varies as v^{-3} , just like the binary collision frequency, electron runaway should occur.
- Since the threshold for the instability increases rapidly as the ion temperature increases (due to ion Landau damping, the threshold drift velocity, $V_T \approx 1.3 v_c$, if $ZT_c = T_i$), ion heating can quench the instability.

Thus, we expect that anomalous dc resistivity will be drastically reduced in an infinite, homogeneous plasma. The point is that, after enough time, the return current will be carried by the runaway electrons, which are essentially collisionless. The periodic simulation calculations¹⁸³ and

theory¹⁸⁴ confirm this result as mentioned above.

In a laser driven pellet, however, the plasma density in the overdense region increases with distance into the corona, so the return current is large only near the critical surface. Thus, the current is impressed over a finite region, and we should expect that periodic simulation calculations would not give the correct result. This idea agrees with the measurements^{180,181}; i.e., in the measurements where large, steady-state collision frequencies were observed at low drift velocities, the resistive region of the plasma was rather short ($L \approx 200$ to $1000 \lambda_{De}$).

Anomalous DC Resistivity in Finite-Length Systems. We have begun¹⁸⁵ simulation calculations of finite-length systems. So far, we have roughly modeled the infinite-length system in a periodic calculation by applying a constant dc electric field and observing the current carried by the thermal electrons and the current carried by the runaway electrons. We find that, after some time, the current is almost entirely carried by the runaway electrons. However, during this time, the runaway electrons have traversed the problem several times, so they would have exited a finite system. The implied resistivity of the thermal electrons is very large. We are changing the code so that we can more accurately model a finite system.

Authors: J. DeGroot, W. Woo (University of California at Davis), and C. Barnes (Los Alamos)

Absorption, Electron Heating, and Electron-Energy Transport Inhibition Due to Ion Turbulence

Introduction. Isotropic ion-acoustic turbulence¹⁸⁶ scatters electrons, resulting in a very short mean free path; i.e., $\lambda_{\text{eff}} = \lambda_{De}(\delta n/n)^{-2}$, where $\delta n/n$ is the rms amplitude of the density fluctuations. Thus, the rate at which electrons transport laser energy in the corona can be drastically reduced. We see that the mean free path due to turbulence increases much more slowly with temperature than the electron-ion mean free path. In particular, $\lambda_{\text{eff}} \sim T_e^{1/2}$, as opposed to $\lambda_{ei} \sim T_e^{3/2}$ (with constant Z), since experiments show that

$\delta n/n$ does not change rapidly with temperature. Thus, the plasma can remain collisional even for high electron temperatures. In addition, the thermal electrons are heated and the laser-light absorption is increased. Ion-acoustic turbulence is driven by a sufficiently large return current (see "Anomalous DC Resistivity Due to Ion Turbulence" in this section). In addition, ion turbulence is driven by the parametric decay of the laser light into electron plasma and ion-acoustic waves.¹⁸⁶ This instability occurs in the underdense region. In microwave simulations of laser-plasma interactions, isotropic, large-amplitude ion-acoustic turbulence is observed for microwave powers larger than only a few times the threshold power (see "Absorption, Electron Heating, and Electron-Energy Transport in Microwave Simulations of P-Polarized Laser Light-Plasma Interactions" in this section). We have constructed¹⁸⁷ a model and a hydrodynamic computer code that includes ion turbulence due to both the drift and

parametric instabilities. This model will be described below. We are presently performing calculations with this code to determine if the strong thermal electron flux limitation which is required for the results from LASNEX to agree with laser experiments could be due to ion turbulence.

Threshold for Parametric Instability on the Underdense Shelf. We assume that the underdense plasma has the shelf-step profile; i.e., an underdense shelf with density, n_s , followed by a rapid density rise to a density greater than the critical density. The density of the underdense shelf is mainly determined by the electromagnetic pressure.¹⁸⁸ Then, the laser light will decay into electron and ion waves if the shelf is long enough and the laser power is above a threshold. The length of the shelf is determined by the laser pulse. Pulse lengths for reactor pellets ($\lesssim$ ns) are long (enough time to create a shelf $\approx L_s/C_s \gtrsim 0.1$ ns for a shelf with $L_s \approx 500 \lambda_{De} \approx 4 \mu\text{m}$ and $T_e \approx 1$ keV). The threshold peak electric field on the shelf, E_t , is given by¹⁸⁶

$$\frac{E_t}{\sqrt{4\pi n_c k T_e}} = 4 \left(\frac{\Gamma_i \Gamma_e}{\omega_i \omega_e} \right)^{1/2}, \quad (97)$$

where Γ_i and Γ_e are ion- and electron-wave amplitude-damping rates, respectively, and ω_i and ω_e are ion- and electron-wave frequencies, respectively. For the cases we shall consider [$(v_{os}/v_e \lesssim 0.2$, where $v_{os} = eE_o/m\omega_o$, E_o is the peak electric field of the incident laser light, and $v_e = (kT_e/m)^{1/2}$], the damping is dominated by Landau damping in all but strongly collisional plasmas. The wave number of the most unstable wave, k , is determined by frequency matching; i.e., $\omega_o = \omega_e + \omega_i \approx \omega_{pe}(1 + 3k^2\lambda_{De}^2)^{1/2}$. Solving for the unstable wave number, we obtain $k\lambda_{De} = [(n_c/n_s - 1)/3]^{1/2}$. Thus, we see that, as the shelf density decreases (due to higher powers), k increases. Landau damping of the electron wave increases with k , so the threshold power will increase with laser power.

We solved¹⁸⁸ numerically the steady-state hydrodynamic equations to obtain the average shelf density (average because the shelf density varies with position due to the standing electromagnetic wave pattern) as a function of laser power. The results are shown in Fig. 3-41 (circles). The amplitude

Fig. 3-41. Laser pump power as a function of underdense shelf density.

of the electromagnetic wave on the shelf is given approximately by

$$E_s = \frac{2E_0}{(1 - n_s/n_c)^{1/4}}, \quad (98)$$

where E_0 is the electric field amplitude of the incident laser light. The factor of 2 is due to the standing electromagnetic wave, and the denominator is due to the dielectric of the plasma. Thus, the threshold is given by

$$\left. \frac{v_{os}}{v_e} \right|_t = \frac{E_0}{\sqrt{4\pi n_c k T_e}} = 2 \left(1 - \frac{n_s}{n_c} \right)^{1/4} \times \left(\frac{\Gamma_i \Gamma_e}{\omega_i \omega_e} \right)^{1/2}, \quad (99)$$

where we get $E_s = E_t$ from Eq. (97). The threshold power $[(v_{os}/v_e)^2 \propto I \lambda^2 / T_e]$ is shown in Fig. 3-41 (solid line) as a function of shelf density for $ZT_e/T_i = 10$. The threshold decreases as ZT_e/T_i increases because ion-wave Landau damping decreases rapidly with ZT_e/T_i . Notice that the laser power for any shelf density (circles in Fig. 3-41) is much greater than the threshold for $ZT_e/T_i = 10$. Thus, using the microwave experiments as a guide, we expect that large-amplitude ion turbulence will be excited if $ZT_e/T_i \lesssim 10$.

Hydrodynamic Model. We see that, if ZT_e/T_i is large enough, parametric instabilities drive ion turbulence. In addition to heating the thermal electrons, hot electrons will be produced¹⁸⁹ due to acceleration of the suprathermal electrons by the electron plasma waves. We have constructed¹⁸⁷ a hydrodynamic model that includes

- The electromagnetic pressure, so that the shelf density is calculated self-consistently.
- Hot electrons due to resonant absorption and electron plasma-wave turbulence driven by the parametric instability.
- Ion turbulence driven by the drift and parametric instabilities.
- Thermal electron heating due to ac and dc anomalous dc resistivity.
- Electromagnetic wave propagation through the underdense region.

Preliminary results for low laser power (2×10^{14} W/cm², 1- μ m wavelength laser) indicate that the thermal electrons are strongly heated (1 keV in the corona to

3 keV in the underdense plasma) and the electron mean free path is very short in the critical and underdense regions ($\lambda_{eff} \simeq 50 \lambda_{De}$).

Authors: W. Woo and J. S. DeGroot
(University of California at Davis)

Major Contributor: P. Rambo (University of California at Davis)

Absorption, Electron Heating, and Electron-Energy Transport in Microwave Simulations of P-Polarized Laser Light-Plasma Interactions

Introduction. We have extended our measurements of the interaction of p-polarized microwaves with essentially collisionless plasma in the Prometheus I device.¹⁹⁰ We have also begun measurements¹⁹¹ of the interaction of a focused beam (f/1) of microwaves with essentially collisionless plasma. Finally, we have developed¹⁹² a simplified theory of the hot electron temperature (T_h), density (n_h), and the density scale length at the critical density (L_c) due to resonant absorption.

Our important results are

- The parametric decay instability¹⁹³ that occurs on the underdense shelf results in significant laser-light absorption and hot-electron production if the shelf density is high enough ($n_s \lesssim 0.6 n_c$) and long enough ($L \lesssim 500 \lambda_{De}$). These conditions will be met if the laser power is low enough ($I \gtrsim 10^{15}$ W/cm² for a 1- μ m wavelength laser).
- The turbulent heating process is quite different when absorption due to the parametric instability dominates resonant absorption. The hot-electron temperature is lower, and the hot-electron density is much higher. Also, the thermal-electron temperature in the critical region is much higher, and the thermal-electron energy flux inhibition is much stronger.
- The measured T_h and n_h due to resonant absorption in both the Prometheus I and Thor devices agree quite well with the simplified theory that we developed¹⁹² and with particle-simulation calculations

for laser parameters. Thus, our microwave experiments are a very good model of the resonant absorption of p-polarized laser light.

Prometheus I Measurements. P-polarized, moderate-power microwaves ($0.1 < v_{os}/v_{eo} < 1$, where $v_{os} = eE_o/m\omega_o$ and E_o is the electric field amplitude of the incident microwaves) are obliquely incident ($\theta = 45^\circ$) onto an inhomogeneous, essentially collisionless plasma in the Prometheus I device.¹⁹⁰ We find that absorption, electron heating, and electron-energy transport are strong functions of the length of the underdense shelf.¹⁹⁰ The ponderomotive force due to the electrostatic waves strongly modifies the plasma density profile near the critical surface. The modified plasma density profile has a subcritical density shelf of length L_s , followed by a steep density increase to a density greater than the critical density. The scale length of the steep density increase is $L_c = (1/n_c \, dn/dx)^{-1}$.

The length of the underdense shelf is an externally variable parameter in Prometheus I. There are two important limiting regimes

- Case (1). If the shelf is short ($L_s/\lambda_{De} < 200$), resonant absorption dominates.
- Case (2). If the shelf is long ($L/\lambda_{De} > 500$), parametric decay dominates absorption.

Case (1) has the following properties:

- Strong profile modification.
- Very weak ion turbulence.
- T_h , n_h , and L_c agree with particle simulations and theory for resonant absorption.
- There is a weak dc electric field in the critical region; therefore, there are weak thermal-electron heating and weak inhibition of thermal-electron energy transport.

Case (2) has the following properties:

- Weak profile modification and high density ($n \lesssim 0.6 n_c$) underdense shelf.
- Strong ion turbulence ($\Delta n/n \lesssim 20\%$) due to the drift and the parametric instabilities.
- T_h , n_h , and L_c do not agree with simulations and theory for resonant absorption. T_h is lower, n_h is much higher, and L_c is much longer for the long underdense shelf.
- A strong dc electric field exists in the critical region; therefore, there is strong thermal-electron heating and strong

inhibition of the thermal-electron energy flux.

We also measured the threshold¹⁹⁴ for the parametric decay instability and found that the ion waves are excited near the critical density for microwave powers near threshold. This is as expected for the parametric instability, in which the high-frequency wave decays into electron plasma and ion-acoustic waves.¹⁹³ The measured threshold is very low, i.e., $(v_{os}/v_{eo})_t = 0.02$, as shown in Fig. 3-42 (P_{th}). The rms ion-wave amplitude is quite large for powers of only a few times threshold (i.e., $\Delta n/n = 13\%$ for $v_{os}/v_{eo} = 0.04$, as shown in Fig. 3-42).

These ion waves will scatter electrons, resulting in a very short electron mean free path if the ion waves are turbulent and nearly isotropic. (The point is that ion waves traveling essentially perpendicularly to the electron direction of motion scatter that electron.) The mean free path of a thermal electron due to the turbulence is

$\lambda_{eff} \approx \lambda_{De}(\Delta n/n)^{-2}$ (see "Anomalous DC Resistivity Due to Ion Turbulence" in this section). For example, with $\Delta n/n = 13\%$, $\lambda_{eff} \approx 60\lambda_{De}$, a very short mean free path. We used a small double probe to measure the angular distribution of the ion waves.¹⁹⁴

Near threshold, the ion waves are coherent, and they only propagate along the direction of the microwave electric field, as expected. However, for powers of 20 times threshold ($v_{os}/v_{eo} \approx 0.1$, where significant absorption and suprathermal electron production is observed), the ion waves are turbulent and essentially isotropic. Thus, it is clear why the thermal-electron energy transport is severely inhibited—the thermal electrons are being scattered by the ion waves.

Thor Measurements. A focused beam ($f/1$) of very-high-power ($v_{os}/v_{eo} < 3$) microwaves is incident onto an inhomogeneous plasma in the Thor device. The purpose of this device is to investigate crater formation¹⁹⁵ and the uniformity of the production of hot electrons within the focal spot. To date, we have measured T_h and n_h in the range of powers $1 \lesssim v_{os}/v_{eo} \lesssim 3$. We find excellent agreement between the Thor results, particle-simulation results, and the simplified theory to be developed below.

Simplified Theory of Resonant Absorption. Using the basic ideas of Kruer¹⁹⁶ and Estabrook and Kruer,¹⁹⁷ we have constructed a simplified theory of resonant

absorption that agrees quite well with results from particle-simulation calculations and microwave simulations. In this model of resonant absorption, the plasma is viewed as contained within a capacitor that is driven by an external electric field. The external field resonantly drives up electron plasma waves near the critical surface. The amplitude of the driven waves is limited by warm wave breaking¹⁹⁶, i.e., the oscillation velocity of the electrons brings some of the supra-thermal electrons into resonance with the wave. These electrons are accelerated by the wave, giving rise to damping of the driven wave.

We start by obtaining an estimate for the steepened density profile, assuming that the force due to the density gradient is balanced by the ponderomotive force; i.e.,

$$\frac{\partial p}{\partial x} = -\frac{1}{16\pi} \frac{\partial E_w^2}{\partial x}, \quad (100)$$

where E_w is the amplitude of the driven electric field and $p = p_e + p_i$ is the total plasma pressure. We estimate

$$\frac{\partial p}{\partial x} \approx \frac{n_c k T_c}{L_c} (1 + 3T_i/T_e), \quad (101)$$

where L_c is the scale length of the pressure, n_c is the critical density, T_c is the cold (thermal) electron temperature, and T_i is the ion temperature. We assumed an adiabatic equation of state for the ions, with $\gamma_i = 3$, and an isothermal equation of state for the electrons. We also estimate

$$\frac{\partial E_w^2}{\partial x} \approx k E_w^2, \quad (102)$$

where k is the mean wave number of the driven wave. Combining Eqs. (100), (101), and (102), we obtain

$$\frac{L_c}{\lambda_{De}} = 4(1 + 3T_i/T_e) \left(\frac{v_c}{v_w} \right)^2 \frac{v_p}{v_c}, \quad (103)$$

where $v_p = \omega_o/k$, the phase velocity of the driven wave; $v_w = eE_w/m\omega_o$, the quiver velocity of an electron in the driven wave; $v_c = \sqrt{KT_c/m}$, the cold electron thermal speed; and $\lambda_{De} = \sqrt{KT_c/4\pi n_c e^2}$, the cold-electron Debye length.

Kruer¹⁹⁷ has shown that there is another relation between these quantities,

$$\frac{v_w}{v_c} \frac{v_p}{v_c} = 2 \frac{L_c}{\lambda_{De}} \frac{v_d}{v_c}, \quad (104)$$

where $v_d = eE_d/m\omega_o$. Here, E_d is the amplitude of the driver electric field in the capacitor model. Combining Eqs. (103) and (104), we eliminate L_c to obtain

$$\frac{v_w}{v_c} = \left[8 \left(1 + 3T_i/T_e \right) \frac{v_d}{v_c} \right]^{1/3}. \quad (105)$$

This is a new equation for the amplitude of the driven electron plasma wave when limited by wave breaking. Equation (105) agrees quite well with one-dimensional particle-simulation calculations.¹⁹⁸

Next, we assume that the hot-electron temperature should be approximately the kinetic energy that an electron obtains by making one pass through the potential of the driven wave,¹⁹⁷ i.e.,

$$KT_h = e\phi_w = eE_w/k. \quad (106)$$

Notice that we assumed that the wave was stationary in time, which seems to be incorrect. The point is that we are calculating the energy gained by a resonant electron; a resonant electron "sees" an effectively stationary wave. Combining Eqs. (105) and (106), we obtain

$$\frac{T_h}{T_c} = \frac{v_w}{v_c} \frac{v_p}{v_c} = 2 \frac{L_c}{\lambda_{De}} \frac{v_d}{v_c}. \quad (107)$$

Fig. 3-42. Root-mean-square ion-wave amplitude $\Delta n/n = \langle [\delta n(t)]^2/n \rangle^{1/2}$ as a function of microwave power.

Plasma Theory

We use warm plasma theory¹⁹⁶ to relate v_p to v_w . Then, by plotting T_h/T_i and L/λ_{De} versus v_d/v_c , we find (for $T_e/T_i = 3$)

$$\frac{T_h}{T_c} = 16.4 (v_d/v_c)^{0.47} \quad (108)$$

and

$$\frac{L_c}{\lambda_{De}} = 8.2 (v_c/v_d)^{0.53} \quad (109)$$

Equation (108) agrees within 10% with the results obtained for $v_d/v_c < 1$ using a one-dimensional electrostatic particle simulation code.¹⁹⁹

We use energy conservation¹⁹⁷ to relate the driver field to the electric field of the incident light; i.e.,

$$\frac{fE_{oc}^2}{8\pi} = \frac{\omega_0 L E_d^2}{8} \quad (110)$$

where f is the fractional absorption and E_o is the amplitude of the laser electric field in vacuum. The term on the left-hand side of Eq. (110) is the absorbed laser flux, and the term on the right-hand side of Eq. (110) is the energy absorbed per area in the capacitor. We can rewrite Eq. (110) as

$$\frac{v_d}{v_c} = \frac{v_o}{v_c} \left(\frac{f c}{\pi v_c} \right)^{1/2} \left(\frac{\lambda_{De}}{L_c} \right)^{1/2} \quad (111)$$

where $v_o = eE_o/m\omega_o$. Since L_c/λ_{De} is a function of v_d/v_c [see Eq. (109)], we see that

$$\frac{v_d}{v_c} \propto f \lambda^2 / T_c^{3/2} \quad (112)$$

Because T_h/T_c and L_c/λ_{De} are functions of v_d/v_c [Eqs. (108) and (109)], we see that T_h/T_c and L_c/λ_{De} are only functions of a universal parameter, $f \lambda^2 / T_c^{3/2}$.

We obtain n_h/n_c by equating the absorbed laser flux to the energy flux of the hot electrons; i.e.,

$$fI = q_h = 0.8 n_h v_h k T_h \quad (113)$$

where $v_h = \sqrt{kT_h/m}$ and we have assumed that the hot electrons have a half-Maxwellian energy distribution.

Plotting T_h/T_c and L_c/λ_{De} versus v_d/v_c , we find

$$\frac{T_h}{T_c} = a \left[\frac{f \lambda^2}{T_c^{3/2}} \right]^\ell \quad (114)$$

$$\frac{n_h}{n_c} = b \left[\frac{f \lambda^2}{T_c^{3/2}} \right]^m \quad (115)$$

and

$$\frac{L_c}{\lambda_{De}} = c \left[\frac{f \lambda^2}{T_c^{3/2}} \right]^n \quad (116)$$

Fig. 3-43. Hot-electron temperature as a function of the parameter $f \lambda^2 / T_c^{3/2}$.

where the units are $I(W/cm^2)$, $\lambda(\mu m)$, and $T_e(eV)$, and the parameters have the following values:

T_c/T_i	= 1	3	∞
a	$= 4.6 \times 10^{-3}$	4.6×10^{-3}	3.8×10^{-3}
ℓ	= 0.333	0.323	0.323
b	$= 5.3 \times 10^{-7}$	5.3×10^{-7}	7.1×10^{-7}
m	= 0.500	0.516	0.516
c	$= 6.2 \times 10^4$	6.2×10^4	5.1×10^4
n	= -0.33	-0.35	-0.35

The theoretical predictions for T_h/T_c are shown as solid lines in Fig. 3-43, along with results from one-dimensional electrostatic and two-dimensional electromagnetic^{197,200} simulation calculations and Prometheus I and Thor microwave simulations. The agreement is generally quite good. The theoretical predictions for L_c/λ_{De} agree quite well with two-dimensional electromagnetic simulation calculations.¹⁹⁷ Thus, we see that our simplified model for T_h/T_c and L_c/λ_{De} gives results that are in good agreement with computer and microwave simulations of resonant absorption.

Authors: K. Mizuno and J. S. DeGroot
(University of California at Davis)

Major Contributors: D. A. Rasmussen,
F. Kehl, and W. Woo (University of
California at Davis)

LASNEX and Atomic Theory

The LASNEX Computer Code— An Overview

Introduction. We developed the LASNEX code to design targets and analyze experiments for the inertial-confinement fusion (ICF) program. The LASNEX code has also been valuable as a check on the approximations used in other codes. In the following discussion, we present a brief overview of the LASNEX code, including its physics models, structure, and user interface. This article updates an older LASNEX review.^{201,202}

Physics Models. LASNEX solves a large set of coupled nonlinear partial differential equations that determine the temporal evolution of the many spatially dependent quantities, such as temperature, density, and velocity. The spatial variation of most of these quantities is described in two-dimensional, axially symmetric geometry on a mesh composed of arbitrarily shaped quadrilaterals. Typically, the mesh is allowed to move along with the material motion according to the Lagrange hydrodynamic method,²⁰³ but, at user request, the mesh within material regions can move in any fashion. In particular, we can explicitly follow translational and compressional flows while allowing turbulent flows to pass through the mesh.²⁰⁴ This prevents severe mesh distortion and increases the overall accuracy of the solution.

Figure 3-44 is a schematic representation of the physical processes calculated by LASNEX. Circles in this figure represent forms in which energy can exist within a plasma; the arrows represent interaction mechanisms and generally show the direction of energy flow. In this article, we will briefly discuss each physical process, concentrating on the numerical approximations used to calculate them.

A LASNEX calculation can be driven by several different types of sources and boundary conditions. Some sources, such as temperature, pressure, and velocity profiles, can be imposed quite arbitrarily, while the beam deposition sources interact with the plasma in a more complete and physically consistent manner. Laser, electron, and ion beams are calculated by tracking a number of rays through the spatial mesh. Power on the ray is decremented as deposition occurs. For laser beams, the rays are bent according to the laws of refraction.²⁰⁵ Laser deposition results from classical inverse bremsstrahlung absorption and from parameterized formulas representing Brillouin, Raman, and resonant-absorption processes.²⁰⁶ Absorption by these noncollisional processes creates a high-energy electron population that can be characterized by a Maxwellian distribution at an elevated temperature.²⁰⁷ Charged-particle beam deposition is calculated from stopping-power formulas that account for straggling and partial ionization.²⁰⁸ Momentum deposition from all beams and

the ponderomotive force of lasers²⁰⁹ are consistently implemented.

Suprathermal electrons are created by beam sources in a spectrum characteristic of the deposition process. These electrons are then transported and thermalized by a multigroup diffusion method that is relativistically correct and that allows for arbitrary isotropic distributions.^{210,211} The isotropy assumption is valid in high-Z materials, where scattering rates are large, and may also be reasonable in low-Z materials if self-generated magnetic fields are strong enough. Electron transport is iterated, along with the determination of a self-consistent electrostatic potential, in a way that assures zero net current. Suprathermal electrons lose energy to thermal electrons by Coulomb collisions and by doing ohmic work through the electric field. These electrons produce frequency-dependent bremsstrahlung photons and affect the material hydrodynamic motion by contributing to the plasma pressure.

The thermal electrons are assumed to be in an equilibrium distribution. Their energy is shared with ions through Coulomb collisions, and this energy is transported using tensorial plasma conductivities in a magnetic field. LASNEX calculates atomic physics using the average-atom approximation, which can be run in either local thermodynamic equilibrium (LTE) or non-LTE modes.^{212,213} In LTE, the atomic

populations are in equilibrium with the local thermal-electron temperature; in non-LTE, the populations are found by solving rate equations and, in general, depend as well on the photon and suprathermal electron distribution functions. In either case, the thermal-electron pressure and specific heat include Fermi degeneracy, partial ionization, and Coulomb corrections. These average-atom models also provide frequency-dependent radiative opacities caused by bound-bound, bound-free, and free-free for use in the photon transport routines.

LASNEX has three distinct methods of calculating radiation transport:

- Single-group diffusion, which assumes that the photons are in a Planck distribution characterized by a local radiation temperature. This method uses only Rosseland mean opacities and is valid if the problem is very thick to radiation.
- Multigroup diffusion, which assumes arbitrary isotropic photon distributions and performs decently on emission and preheat calculations, where the photon frequency dependence is more important than its angular dependence. Photon energy redistribution caused by Compton scattering is treated in the Fokker-Planck approximation.²¹⁴
- The P_n transport method,²¹⁵ in which the photon angular distribution is expanded in spherical harmonics, has been implemented for one-dimensional problems,

Fig. 3-44. Schematic representation of the physical processes calculated by the LASNEX code.

and has proved to be useful both in actual design calculations and in testing the accuracy of various extensions to diffusion theory.

All radiation-transport models deposit momentum when a photon is absorbed or scattered.

The thermal ions are assumed to be in a Maxwellian distribution, and diffusion methods are used to spatially mix different types of ions and to transport thermal energy. Real ion viscosity (momentum diffusion) is optionally included in the hydrodynamics equations, although it is typically small by comparison with the usual artificial viscosity.

LASNEX calculates most interesting thermonuclear reactions between isotopes of H, He, Li, Be, and B. Charged particles and neutrons produced are transported by multigroup diffusion methods that take into account nuclear scattering, in-flight reactions, and momentum deposition. The charged-particle transport is an extension of diffusion that retains particle inertia as it undergoes straight-line energy loss to electrons.^{216,217} All burn products either escape from the problem or deposit their energy back into the thermal-electron and ion fields.

Magnetic fields are generated automatically in two-dimensional problems, or can be imposed by user-specified sources that self-consistently couple the plasma to an external LRC circuit. Transport coefficients in a magnetized plasma are essentially those derived by Braginskii,²¹⁸ optionally modified to approximate the effects of various collisionless processes. In laser plasmas, the dominant effect of magnetic fields is the modification of transport coefficients for all charged particles. For magnetic-pinch and exploding-wire calculations, the hydrodynamic $\vec{j} \times \vec{B}$ force is also important.

A large number of the physical processes calculated by LASNEX involve the solution of diffusion equations on the arbitrary quadrilateral mesh. Since the mesh lines are not necessarily orthogonal, this requires a nine-point diffusion operator, as discussed by Kershaw.²¹⁹ The resulting matrix is solved by the Incomplete Cholesky-Conjugate Gradient method.²²⁰

Possible improvements in the LASNEX physics models include the generalization of

two-dimensional magnetic field geometries and their consistent implementation with suprathermal electrons; extension of atomic physics to lower temperatures, where material strength, molecular chemistry, and Fermi degeneracy are important; and development of models to approximate the many collisionless plasma physics processes that LASNEX cannot simulate directly.

Code Structure and User Interface. Over the years, LASNEX has been redesigned several times. It has evolved a hierarchical structure in which individual modules exhibit substantial functional independence. This type of organization, known as structured design,^{221,222} is essential if a code is to be developed simultaneously by many individuals, each with their own areas of responsibility and expertise. We have also found significant improvements in the code's efficiency, reliability, and flexibility.

The ability to choose at execute time between alternative modules for the same physical process has allowed us to develop and debug new physics packages while simultaneously maintaining a stable code for production use. Redundant physics models also allow a user to validate the correctness of each model and to trade off computer time for accuracy according to the needs of his or her particular problem. To save computer space, only those modules needed for a particular calculation are actually resident in memory. The same is true for data arrays that are allocated and reused with near-optimal efficiency through the use of a formal memory manager.²²³

LASNEX was developed in an interactive computing environment. We have built a strong interface that allows users to investigate and modify their problems while the problems are running. Graphical displays, as well as numerical edits of the problem, can be produced at any time; this allows the user to quickly ascertain whether the problem is running correctly and efficiently. If the problem is set up incorrectly, it can be terminated before it wastes significant computer resources; if the computational mesh has become tangled, the user can interactively straighten the mesh, thereby increasing both efficiency and accuracy.

We are currently enhancing the user interface by developing a standard and powerful language, GOAL (Graphics

Oriented Applications Language). GOAL will be used consistently for problem generation, display, modification, and postprocessing. Through the use of functions, macros, do loops, and other control structures, GOAL should allow a user to specify what he or she wants in a concise and easily remembered fashion. Eventually, we anticipate that much of the work involved in optimizing a design or performing a parameter study can be automated in a GOAL program, where conditional logic will look at the results of several LASNEX problems and then decide what problem to run next.

Author: G. B. Zimmerman

Dynamic Memory Management for LASNEX

Introduction. A large code system such as LASNEX (Fig. 3-45) needs a formal scheme for memory management. During our conversion of LASNEX to the Cray-1, we

have developed a memory manager that has two primary functions:

- It is the means by which a program gains access to dynamic memory space.
- It remembers all relevant information about every request for memory.

It is the combination of these two functions that permitted a good design of Cray LASNEX. The structure of the LASNEX code is described in the following paragraphs.

LASNEX is partitioned into a set of smaller processes, each of which is virtually independent of every other process except for the data and the memory space it occupies. These latter must necessarily be shared by all processes. In the past, this situation has been addressed by forcing all data into globally accessible blocks of memory (e.g., COMMON). All processes have direct access to every scalar and every array; some processes will modify the data intended for other processes (Fig. 3-46). This state of affairs results in a very tight binding of the modules in the code system. In fact, modules that were originally independent entities gradually became closely tied to other modules.

LASNEX contains a huge mass of data that must be cyclically referenced and updated. In total, the memory requirements for this processing exceed the physical limits of the machine by a factor of 2 or 3. Disk access is not acceptable because it is too slow; thus, the technique of overlaying data is necessary (Fig. 3-47). However, overlaying the data has the disadvantage of causing the program to be much more difficult to understand and modify. In the past, we maintained a sophisticated memory map by hand. As LASNEX matured, we were forced to use memory less efficiently.

Design of the Memory Manager. We developed a formal memory manager to resolve the problems discussed above. This was especially critical in our conversion of LASNEX to the Cray. The memory manager provided the necessary control for many people to work independently on the conversion effort.

The following list of functions was incorporated into our memory manager:

- An allocate memory function.
- A deallocate memory function.
- A use function to access previously allocated space.

Fig. 3-45. Some characteristics of large code systems.

- A new size function to increase or decrease the allocated space.
- A delete function to forget everything about an array name and the space allocated to it.
- A pack memory function to squeeze out an unused space.
- A function to store a pattern into allocated memory as an aid in debugging.
- A function to cause an array to never be moved.
- A set of functions to access the attributes of an array (e.g., length or data type).
- A set of functions to inquire about the state of managed memory (e.g., return the largest contiguous block of unused space).

The following requirements were placed on the design of the memory manager:

- Allow symbolic references to managed memory.
- Return pointers to allocated memory.
- Make relatively few calls for the system to expand or contract the field length.
- Dynamically expand itself to allow any number of managed arrays.
- To be implemented in such a way that a 2 to 3% overhead in size and speed was possible.
- Reuse deallocated space.
- To be simple to use, machine independent, and code independent.
- Remember attributes of all managed arrays (e.g., name, length, address, and status).
- Check for errors and consistency.

The environment in which this memory manager would operate was to have the following characteristics:

- The majority of the arrays were to be of equal size.
- A few arrays were to be exceptionally large or exceptionally small.
- Between 1 million and 100 million references to the memory manager were to be possible in a single run.
- The data types of arrays were to range from full-precision floating point to character and bit strings.

Combining these features of the memory manager into a single set of modules required a thorough design. The design was broken into three levels: a core level, a basic user level, and a high level to perform complex functions.

The core of a memory manager consists of a set of tables and a set of modules that

maintain the status of memory and all managed arrays. Two tables are required to meet these requirements: the free-space table, and the memory log. The free-space table contains the length and location of all holes in memory that are available for allocation. When a block of memory has to be allocated, a hole that is large enough is found and removed from the free-space table; later, when the block is released, the resulting hole is returned to the free-space table. Knuth has an excellent discussion of allocation schemes.²²⁴

The memory log is the repository of all the information pertaining to managed arrays. In particular, it contains the name, length, address, pointer address, and status flags of all managed arrays.

Internal management performs the following functions:

- Expand or contract field lengths.
- Add, find, or delete holes from the free-space table.
- Make entries in the memory log.
- Search the memory log for names or memory addresses. (Knuth has a detailed discussion of searching.²²⁵)

Fig. 3-46. Common-coupled data can be referenced and modified by any module.

- Pattern memory.

The next level above the internal management functions is the first level to which LASNEX has direct access. The following functions are performed at this level:

- Allocate space for array.
- Release array.
- Use array.
- Delete array.
- Change size of array.
- Respond to array-attribute inquiries.

It is this level that connects all the internal modules together into an operational memory manager. We pass a name and a length to the allocate space function; it then returns a pointer to the allocated space. When we are finished with the array, the release or delete function is called. Other functions are called, as appropriate.

The highest level of memory manager modules contains functions to perform powerful and sometimes complex manipulations of the memory log or free-

space table. This set of functions includes the following:

- Initialization of the memory manager.
- Allocation of an array of specified data type.
- Pack memory and reset active array pointers.
- Set additional array attributes.
- Provide inquiry functions for additional array attributes.
- Respond to memory status inquiries.

Benefits of the Memory Manager. The primary purpose of our memory manager is to efficiently manage memory. However, once this objective is realized, many other advantages become apparent.

The memory manager is simple to use. Parts of LASNEX that would normally have used static arrays easily make use of the memory manager; its usage is as simple as using READ or WRITE statements. When space is needed, it is called for; when it is no longer needed, it is returned. The memory manager is being used by several programs in the LASNEX group, and new software, generated by us, is greatly simplified.

The control logic for LASNEX is simplified. Rather than relegating the allocation and deallocation of memory to the top levels, any module is allowed to allocate and release memory via the memory manager. Thus, the control logic is made more efficient. Program structure is maintained by thinking of the memory manager as a very low-level module that any other module is allowed to access. This latter aspect leads into the advantages that a memory manager has for structured design and structured programming (Fig. 3-48).

As mentioned earlier, one of the problems in LASNEX is global access to data. It was noted that traditional solutions allow every module direct access to any variable in memory (Fig. 3-46); this results in a potentially rigid binding of the modules. A memory manager largely eliminates the need for global (COMMON) arrays and, thus, solves this problem.

In a program based on the memory manager, any module requiring access to any array must go through the memory manager. Thus, a unique port to memory is established (Fig. 3-48), access to all dynamic memory is simple and uniform, and all access to data is well defined. Inadvertent

Fig. 3-47. Overlaying data memory allows a large code's data base to reside completely within the confines of physical memory.

data references (e.g., a local scalar with the same name as a global array) are avoided. With the elimination of global arrays, a looser coupling between code processes can be achieved. Each process can now be thought of as an independent program; it can allocate its own memory, define its own data structures, gain access to arrays previously allocated, and release space it no longer requires before returning to the main control logic. To gain access to data computed by other processes, a process makes a formal request to the memory manager. If the data exist, a pointer to it is returned; If the data do not exist, an error is returned.

The modularity of LASNEX is maintained by the memory manager, since it is a set of very-low-level modules. The readability and understandability of LASNEX is enhanced by the memory manager because all references to arrays in memory go through a single set of well-understood modules.

LASNEX system design is also aided by the existence of the memory manager. Designing new modules is easy; they have little or no effect on existing modules. The same is true with deleting or rewriting old modules. Design time is reduced significantly, and maintenance costs are reduced even more significantly.

As a team of code designers and programmers working on LASNEX, we make effective use of a memory manager. We have delegated responsibility for large pieces of the code to individuals on the team. Having too many designers could impede the code design effort. Duplicate variable names and inconsistent data types are just two potential problems. The consistency and error checks made by the memory manager can detect such problems early. The memory manager does not allow two arrays of the same name to be active simultaneously; when LASNEX attempts to allocate the second one, an error condition results. To gain access to an array, its data type is required in addition to its name; the memory manager uses this information to determine if this is a valid reference to the data. These features of a memory manager allow several areas of LASNEX to be independently designed and implemented.

In LASNEX, we maintain explicit control over when the allocation of arrays takes

place; however, we lose control of where in memory the arrays are allocated. Perhaps some more-sophisticated modules could have been added to permit ordered allocation, but the price would have been additional code and table space in the memory manager. We eliminated the need for ordered allocation by a careful design of LASNEX.

Finally, like any good idea, the memory manager can be abused. Forcing every single array in a piece of LASNEX to be managed results in a very inefficient program. DIMENSION and COMMON statements still have a place in a good implementation. We use them and the memory manager judiciously.

A well-structured, efficient, large code system like LASNEX demands a memory manager. The benefits are many, the disadvantages few.

Author: J. R. Kohn

Fig. 3-48. A formal memory manager is a unique, well-defined mechanism to dynamically access memory.

Computer Simulation of Suprathermal Transport for Laser Fusion

Introduction. The relativistic multigroup diffusion equations describing suprathermal electron transport in laser-fusion plasmas were derived in an earlier report.²²⁶ In this article, we describe a successful numerical scheme based on these equations. This scheme and the corresponding equations are now being used to model laser-fusion experiments.

Basic Equations. Let p = the electron momentum, ϵ = the kinetic energy, $\epsilon = \sqrt{(mc^2)^2 + (pc)^2}$, $\gamma = \epsilon/(mc^2)$, u = the velocity, and $u = p/(m\gamma)$. Let η be the electron density, normalized so the number of electrons equals $\int d^3x d\epsilon \eta(\epsilon, x, t)$, and let Φ be the corresponding flux. Then our basic equations are derived as²²⁶

$$\frac{\partial \eta}{\partial t} + \vec{\nabla} \cdot (\vec{v} \eta) = -\vec{\nabla} \cdot \Phi + \frac{(\vec{\nabla} \cdot \vec{v})}{3} \frac{\partial}{\partial \epsilon} (pu\eta) + \frac{\partial}{\partial \epsilon} (e\vec{E} \cdot \Phi) + \frac{2}{m_e} \frac{\partial}{\partial \epsilon} \left[\frac{(c_e \ln \Lambda_e)}{u} \eta \right] \quad (117)$$

and

$$\frac{-2(m\gamma)^2}{p^3} \left[\sum C_k \ln \Lambda_k \right] \Phi - \frac{e}{c} (\vec{\Phi} \times \vec{B}) = 1/3 pu \vec{\nabla} \eta - \frac{e\vec{E}}{3} p^3 \frac{\partial}{\partial \epsilon} \left(\frac{\eta}{pm\gamma} \right) \quad (118)$$

The first two terms of Eq. (117) are

$$\frac{\partial \eta}{\partial t} + \vec{\nabla} \cdot (\vec{v} \eta) = \frac{1/V}{dt} d(V\eta) \quad (119)$$

where $V = (\text{matter density})^{-1}$ = specific volume, $\vec{v}$ = the matter velocity, and $d/dt = (\partial/\partial t + \vec{v} \cdot \vec{\nabla})$. The left-hand side of Eq. (117) is, therefore, the total Lagrangian time derivative. In a Lagrangian code, the left-hand side of Eq. (117) is the change in the number of electrons in a given zone in one timestep divided by the volume of the zone and the timestep.

The $(\vec{\nabla} \cdot \vec{v})/3 \partial/\partial \epsilon (pu\eta)$ term is a Doppler shift of the electrons to compensate the $P_e dV$ work done by the fast electrons on the matter. Note that from Eqs. (117) and (119),

$$\begin{aligned} \frac{d}{dt} \int d\epsilon (\eta \epsilon V) &= V \frac{(\vec{\nabla} \cdot \vec{v})}{3} \int \epsilon \frac{\partial}{\partial \epsilon} (pu\eta) d\epsilon + \text{other terms} \\ &= \frac{-dV}{dt} \int d\epsilon \left(\frac{pu}{3} \right) \eta + \text{other terms,} \end{aligned}$$

but $\int d\epsilon \eta (pu/3) = P_e$, which is the fast-electron contribution to the matter pressure.

The $\partial/\partial \epsilon (e\vec{E} \cdot \Phi)$ term is the energy loss of the fast electrons caused by ohmic heating of the background plasma. From Eqs. (117) and (119), we obtain

$$\begin{aligned} \frac{d}{dt} \int d\epsilon (\eta \epsilon V) &= V \int \epsilon \frac{\partial}{\partial \epsilon} (e\vec{E} \cdot \Phi) d\epsilon + \text{other terms} \\ &= V (\vec{E} \cdot \vec{j}) + \text{other terms,} \end{aligned}$$

where $\vec{j} = -e \int d\epsilon \phi$ is the total suprathermal current density.

The $(2/m_e) \partial/\partial \epsilon [(c_e \ln \Lambda_e/u) \eta]$ term is the beam energy loss caused by collision with thermal electrons.

Equation (118) is a multigroup version of Ohm's law. The coefficient of the flux, $-2(m\gamma)^2/p^3 C_k \ln \Lambda_k = R(\epsilon, x)$, is the resistance. The forces driving the flux are $-(e/c)(\vec{\Phi} \times \vec{B})$, the $1/c (\vec{J} \times \vec{B})$ force, where $\vec{J} = -e\Phi$ = the current density per unit energy, $1/3 pu \vec{\nabla} \eta$, the $-\vec{\nabla} p_e(\epsilon)$ force, where $p_e(\epsilon) = 1/3 pu\eta$ = electron pressure per unit energy, and $(e\vec{E}/3)p^3 \partial/\partial \epsilon (\eta/pm\gamma)$, which is the multigroup form of the electric field force, as can be seen from

$$\frac{e\vec{E}}{3} \int p^3 \frac{\partial}{\partial \epsilon} \left(\frac{\eta}{pm\gamma} \right) d\epsilon = -e\vec{E} \int \eta d\epsilon = -e\vec{E} n_e$$

The magnetic field is determined from the electric field by

$$\frac{1}{c} \frac{\partial \vec{B}}{\partial t} = -\vec{\nabla} \times \vec{E} \quad (120)$$

The electric field, E , is determined from the quasi-neutrality assumption

$$\begin{aligned} 4\pi \vec{j} &= \vec{\nabla} \times \vec{B} \\ \vec{j} &= -e \int \Phi d\epsilon \end{aligned} \quad (121)$$

and Φ is given in terms of $\vec{E}$ by Eq. (118). In one-dimensional problems, $\vec{B} = 0$, and $\vec{E}$ is obtained from the condition

$$\vec{j} = -e \int \Phi d\epsilon = 0 \quad (122)$$

Finally, the effects of bremsstrahlung are included by adding to Eq. (117) an additional term of the form

$$\left(\frac{\partial n}{\partial t} \right)_{\text{Brem}} = n_i \left[\int_0^\infty dk \eta(\epsilon + k) u_k \frac{d\sigma}{dk} - \eta(\epsilon) u \int_0^\epsilon dk \frac{d\sigma}{dk} \right],$$

where n_i = the ion density, k = the photon energy, $u_k = c\sqrt{(\epsilon + k)^2 - (mc^2)^2}/(\epsilon + k)$, and $d\sigma/dk$ = the bremsstrahlung cross section.²²⁷

For a typical high-Z plasma (e.g., Pb), above 15 to 20 MeV more energy is lost through bremsstrahlung than through scattering of plasma electrons. Even at 1 MeV in Pb, bremsstrahlung losses are 10% of the total energy loss; therefore, bremsstrahlung is an important loss mechanism. This term is also important for diagnostic purposes and for the study of preheat problems.

Equations (117) and (118) can be cast into a more elegant form in the special case that the electric field has no transverse part. Then $\vec{E} = -\vec{\nabla}\phi$, and defining

$$\epsilon_T = \epsilon - e\Phi(x, t), \quad (123a)$$

$$\eta_T(\epsilon_T, x, t) = \eta(\epsilon, x, t), \quad (123b)$$

and

$$\Phi_T(\epsilon_T, x, t) = \Phi(\epsilon, x, t), \quad (123c)$$

Eqs. (117) and (118) become

$$\begin{aligned} \frac{\partial \eta_T}{\partial t} + \vec{\nabla} \cdot (\vec{v} \eta_T) = -\vec{\nabla} \cdot \Phi_T + \left(\frac{\vec{\nabla} \cdot \vec{v}}{3} \right) \frac{\partial}{\partial \epsilon_T} (p \eta_T) \\ + \frac{2}{m_e} \frac{\partial}{\partial \epsilon_T} \left[\frac{(C_e \ln \Lambda_e)}{u} \eta_T \right] - e \frac{\partial \phi}{\partial t} \frac{\partial \eta_T}{\partial \epsilon_T} \\ + \left(\frac{\partial \eta_T}{\partial t} \right)_{\text{Brem}} \end{aligned} \quad (124)$$

and

$$\begin{aligned} \frac{-2(m\gamma)^2}{p^3} \left[\sum C_k \ln \Lambda_k \right] \Phi_T - \frac{e}{c} (\Phi_T \times \vec{B}) \\ = \frac{p^3}{3} \vec{\nabla} \cdot \left(\frac{\eta_T}{p m \gamma} \right) \end{aligned} \quad (125)$$

This form has the advantage that the electric field no longer appears explicitly in the diffusion equations.

Numerical Scheme. Because the scheme has only been satisfactorily implemented in one space dimension, only this case will be discussed. Thus, we will assume $\vec{B} = 0$ and $\vec{E} = -\vec{\nabla}\phi$.

The principle is that fully implicit differencing [i.e., all quantities on the right-hand side of Eq. (117) are evaluated at the end of the timestep] is required, so when the timestep gets much larger than the relaxation time, the code will calculate the steady-state solution (with the given electromagnetic fields, background plasma conditions, and boundary conditions). This is very difficult to achieve for Eqs. (117) and (118) because, in addition to the usual diffusion in space, the electric-field terms yield a diffusion term in energy of the form

$$\frac{(e\vec{E})^2}{3} \frac{\partial}{\partial \epsilon} \left(\frac{p^3}{R(\epsilon, x)} \right) \frac{\partial}{\partial \epsilon} \left(\frac{\eta}{p m \gamma} \right),$$

and a term of the form $1/3 \sum_i e E_i \partial/\partial \epsilon \times [p u / R(\epsilon, x)] (\nabla \cdot \eta)$. These terms couple all energy bins and spatial zones in such a complicated way that, with available computing power, it becomes very difficult to solve the set of linear equations generated by implicit differencing.

Thus, Eqs. (124) and (125), where the electric fields no longer appear, are far easier to solve with finite difference methods. In solving Eq. (125) for Φ , a flux limiter is included so that the basic inequality, $|\Phi| \leq u\eta$, will not be violated. There are four terms in Eq. (124) that still couple different energy bins. The first two,

$$\left(\frac{\vec{\nabla} \cdot \vec{v}}{3} \right) \frac{\partial}{\partial \epsilon_T} (p \eta_T)$$

and

$$\left(\frac{\partial \eta_T}{\partial t} \right)_{\text{BREM}}$$

are done implicitly, but split off from each other and the transport and thermal-loss calculation. This works well, since the hydrodynamic timestep controller requires that $(\vec{\nabla} \cdot \vec{v})(\Delta t) < (1/10)$ and, for laser problems, bremsstrahlung losses are small enough that the energy shift in one timestep is always small. The thermal loss term,

$$+ \frac{2}{m_e} \frac{\partial}{\partial \epsilon_T} \frac{(C_e \ln \Lambda_e)}{n} \eta_T,$$

is implicitly differenced as

$$\frac{\alpha(\epsilon_{i+1}) \eta(\epsilon_{i+1}, t + \Delta t) - \alpha(\epsilon_i) \eta(\epsilon_i, t + \Delta t)}{(\Delta \epsilon)_i},$$

where $\alpha(\epsilon_i) = (2/m_e) C_e \ln \Lambda_e / u$. This form of differencing guarantees that $\eta(\epsilon_i, t) > 0$ implies $\eta(\epsilon_i, t + \Delta t) > 0$ and also enables one to solve the ordinary spatial-diffusion equation for each energy bin separately and, then include $\alpha(\epsilon_{i+1}) \eta(\epsilon_{i+1}, t + \Delta t)$ as a source term in the ordinary diffusion equation for the next lower (*i*th) energy bin.

The third term,

$$-e \frac{\partial \phi(\vec{x}, t)}{\partial t} \frac{\partial \eta_T}{\partial \epsilon_T},$$

is automatically taken care of when we map the kinetic energy bins into the total energy bins in each zone at the beginning of each timestep and then back into the kinetic energy bins after the transport and thermal-loss calculation. This mapping and remapping takes care of the shift in ϵ_T in each zone caused by the change in $\phi(x, t)$ during the last timestep [see Eq. (123a)].

The diffusion term,

$$\vec{\nabla} \frac{p^3}{3R(\epsilon, x)} \vec{\nabla} \left(\frac{\eta_T}{p m y} \right),$$

is differenced fully implicitly with the thermal-loss term using a standard three-point coupling scheme.

Thus, for each cycle, we map the values of η from the kinetic energy bins into the total energy bins. Then, we calculate fully implicitly the transport and thermal loss for each total energy bin, working down through the bins and using the thermal loss from the

*i*th bin as a source for the (*i*-1)st bin. Then, we remap the values of η from the total energy bins back into the kinetic energy bins. Calculating the transport and thermal loss in total energy space has the major advantage that the physical inequality $\eta > 0$ is maintained, whereas difference schemes for Eqs. (117) and (2) in kinetic energy space are plagued with severe $\eta < 0$ problems.

We also have a group of thermal electrons (electrons whose energy is low enough that they are described by the usual thermal equations). These electrons are transported fully implicitly using the standard equations

$$\frac{\partial \eta_{TH}}{\partial t} = - \vec{\nabla} \cdot \phi_{TH} \quad (126)$$

and

$$\phi_{TH} = \alpha_{TH} [- \vec{\nabla} \cdot (T_e \eta_{TH}) - e \vec{E} \cdot \eta_{TH}] \quad (127)$$

Equations (126) and (127) are differenced using the method of Chang and Cooper²²⁸

$$\begin{aligned} V_i (\eta'_i - \eta_i) = & G_{(i+1/2)} \left(\frac{Y_{(i+1/2)}}{Z_{(i+1/2)} - Z_{(i+1/2)}^{-1}} \right) \\ & \times (Z_{(i+1/2)} T_{i+1} \eta'_{i+1} - Z_{(i+1/2)}^{-1} T_i \eta'_i) \\ & - G_{(i-1/2)} \left(\frac{Y_{(i-1/2)}}{Z_{(i-1/2)} - Z_{(i-1/2)}^{-1}} \right) \\ & \times (Z_{(i-1/2)} T_i \eta'_i - Z_{(i-1/2)}^{-1} T_{i-1} \eta'_{i-1}) \end{aligned}$$

Here, η' and η are the thermal electron densities at the end of the current and the previous cycle, respectively, V_i is the zone volume, and T_i is the thermal-electron temperature at the end of the previous cycle.

$$Y_{i+1/2} = -2e(\phi_{(i+1)} - \phi_i) / (T_{(i+1)} + T_i)$$

and

$$Z_{i+1/2} = \text{EXP}(Y_{(i+1/2)}/2),$$

where ϕ_i = the electrostatic potential in zone *i*, $G_{i+1/2}$ is the diffusion coefficient and geometric factors multiplied by the timestep. This difference scheme has the following virtues:

- $\eta > 0$ initially $\Rightarrow \eta > 0$ for all time.

- $(dj_{TH}/dE) > 0$ always holds. (See discussion on electric-field determination, below.)
- The steady-state solution is $\eta'_i = Z_{(i+1/2)}^2 \eta_{(i+1)}$, which is the analytically correct steady state.

Next, we add the total number of electrons (thermal plus suprathermal) in each zone and look at the difference between this total and the total ionic charge. This difference (the numerical violation of charge neutrality) is used to update the electric field, and we obtain values for E that will better preserve charge neutrality in the next timestep.

We then calculate the thermal loss energy,

$$\delta_i = \frac{2}{me} \int \frac{(C_e \ln \Lambda_e)}{u} \eta_i(\epsilon) d\epsilon$$

Then, we take the thermal-electron current, $-e\Phi_{TH}$, across each interface times the potential drop between that pair of zones and update the thermal-electron temperature in those two zones. Thus, the $\vec{E} \cdot \vec{j}$ exchange energy is

$$(-e\Phi_{TH})_{i+1/2} (\phi_i - \phi_{i+1}) = \Delta_{i+1/2}$$

Then, the electron temperature is updated

$$(Te)'_i = (Te)_i + [\delta_i + (\Delta_{i-1/2} + \Delta_{i+1/2})/2] / C_i$$

where C_i = the specific heat of the i th zone.

We then set the number of thermal electrons in each zone equal to the ionic charge minus the number of suprathermals, so that next timestep we start anew with exact charge neutrality.

We then do a fully implicit, split-off treatment of the Doppler shift because of the $(P \cdot dV)$ work. In each zone, this is upward or downward differenced in kinetic energy space, depending on whether $dV < 0$ (electrons are Doppler shifted upward) or $dV > 0$ (electrons are Doppler shifted downward).

Finally, we calculate the bremsstrahlung emission and downward shift of the electron kinetic energy fully implicitly, downward differenced, and split off from the other calculations.

Bin Rezoning. To make the mapping from kinetic energy space to total energy space, and back again, as easy as possible, equal-width energy bins were initially used. In

some cases, it was important to resolve both the suprathermals carrying the bulk of the energy and the very-high-energy suprathermals responsible for preheat and the high-energy tail of the x-ray spectrum. In this case, equally spaced bins are inadequate, and we use a more general bin structure with $(\Delta\epsilon)_{(i+1)} = \rho(\Delta\epsilon)_i$, where ρ is a constant > 1 . To resolve $\eta(\epsilon)$ well, both at early times when $\bar{\epsilon} = (\int \epsilon \eta d\epsilon d^3x) / (\int \eta d\epsilon d^3x)$ is small and at the peak of the laser pulse when ϵ is large, it was necessary to rezone the bins. Each timestep, $\bar{\epsilon}$, is recalculated, and, if

$$\left| \frac{\epsilon_{\max} - P\bar{\epsilon}}{P\bar{\epsilon}} \right| > 0.2,$$

we rezone the bins so that

$$\epsilon_{\max} = P\bar{\epsilon}$$

Here, $\epsilon_{\max}$ is the kinetic energy of the highest bin, and P is an adjustable parameter whose default value is 25.

Electric-Field Determination. In the past, we tried to determine E directly from Eq. (122) by putting the densities and the diffusion coefficients from the last cycle into Eqs. (118) and (127), adding them to get $\int \Phi d\epsilon = 0$, and then solving this for $\vec{E}$. This did not work well because the actual transport was being done in total energy space after mapping, so the values for j that we obtained with this $\vec{E}$ were often very large; i.e., with finite numbers of zones and bins, the numerical current produced by mapping and transporting the electrons in total energy space is quite different from what we would get by a simple differencing of Eqs. (118) and (127). Thus, the $\vec{E}$ field never caused the numerical j to go to zero, and these large violations of charge neutrality made the rest of the physics, particularly the $\vec{E} \cdot \vec{j}$ exchange energy, behave very poorly.

In our new treatment, in each timestep after transporting the thermals and suprathermals, we add the charge in each zone to determine a total current, $j_{(i+1/2)}$ (the numerical charge neutrality violation), that flowed for this cycle across the $(i + 1/2)$ interface. Based on our transport Eqs. (118) and (127), we calculate for each bin $[dj(\epsilon)/dE]_{i+1/2}$ and for the thermals a $(dj_{TH}/dE)_{i+1/2}$. Adding these up, we obtain

$$\left(\frac{dj}{dE}\right)_{(i+1/2)} = \left(\frac{dj_{TH}}{dE}\right)_{i+1/2} + \int \left(\frac{dj(\epsilon)}{dE}\right)_{i+1/2} d\epsilon$$

the change in the total current across the $(i+1/2)$ zone interface produced by a change in the potential drop between the i th and $(i+1)$ st zones. Thus, the error we made in choosing the electric field was

$$j_{(i+1/2)} / \left(\frac{dj}{dE}\right)_{(i+1/2)}$$

so, in the next cycle, we take

$$E'_{(i+1/2)} = E_{(i+1/2)} - \alpha j_{(i+1/2)} / \left(\frac{dj}{dE}\right)_{(i+1/2)}$$

If very accurate E fields are required to minimize the $\vec{E} \cdot \vec{j}$ energy errors, we iterate this electric-field correction each cycle until the error is less than the admissible error. Thus, we relax E towards the correct values that will make the numerical charge neutrality violation go exactly to zero. This will work so long as $(dj/dE) > 0$. The parameter α has a value of ≈ 1 . In general, $\alpha = 1$ works quite well; however, since (dj/dE) is not exact because previous time-step values for the densities and diffusion coefficients have been used, and because coupling between $j_{i+1/2}$ and $E'_{i+1/2}$ (where $i \neq i'$) has been ignored, occasionally $\vec{E}$ will go into oscillation. Then, taking $\alpha = 1/2$ or $\alpha = 1/3$ restores convergence. It was also found that, occasionally, the boundary conditions (mainly laser-energy production rate in a given zone) changed so suddenly that the needed change in E was very large and $-j/(dj/dE)$ was a very bad overestimate of $\Delta \vec{E} = E' - E$. For this reason, in any one timestep, $|\Delta E|$ was limited to be $\leq \Delta \epsilon$, the bin width.

Flux Limiters. The flux-limit condition is

$$|\Phi(\epsilon)| \leq u\eta(\epsilon)$$

Now,

$$\begin{aligned} \Phi(\epsilon) &= -D(\epsilon) \left[(1/3)pu \vec{\nabla} \eta - \frac{e\vec{E}}{3} p^3 \frac{\partial}{\partial \epsilon} \left(\frac{\eta}{pmy} \right) \right] \\ &= D(\epsilon) \vec{g}(\epsilon) \end{aligned}$$

The flux limit is included by altering D to

$$\tilde{D}(\epsilon) = D(\epsilon) / \{1 + D(\epsilon) |g(\epsilon)| / [u\eta(\epsilon)]\}$$

Note that $\vec{g}(\epsilon)$ is not the usual $1/3 pu \vec{\nabla} \eta$, but includes an electric-field term. This is important because, if we use the conventional flux limiter, we can end up severely cutting down the diffusion coefficient. Then, in fact, Φ is zero because the electric field is balancing the $\vec{\nabla} \eta$ force.

Another potential problem with flux limiters comes from the physically desirable inequality, $(dj/dE) > 0$, which is necessary for the stability of the E-field relaxation scheme. Numerically, this depends on

$$\frac{\partial [p^3 D(\epsilon)]}{\partial \epsilon} > 0$$

This certainly is true of $D(\epsilon)$, but once we flux-limit $D(\epsilon)$, we may have values of ϵ for which

$$\frac{\partial [p^3 \tilde{D}(\epsilon)]}{\partial \epsilon} < 0$$

This resembles conduction and insulation bands in semiconductors, where an increase in the electron potential energy in zone $(i+1)$ relative to zone i can actually cause more current, instead of less, to flow from zone i to $(i+1)$. Clearly, this would make the electric-field calculation go unstable, so we require that

$$\epsilon' > \epsilon \text{ implies } p'^3 \tilde{D}(\epsilon') \geq p^3 \tilde{D}(\epsilon)$$

Mapping. Our total energy bins have the same width, $\Delta \epsilon$, as our kinetic energy bins. Each zone has an electron potential energy, $-e\phi_i = V_i$. In the zone, $i(\text{MIN})$, with minimum potential,

$$V_{i(\text{MIN})} = \text{MIN} \{V_i\} = V_{\text{MIN}}$$

we let the total energy bins coincide with the kinetic energy bins. The number of total energy bins is equal to NB (the number of kinetic energy bins) $+ (V_{\text{MAX}} - V_{\text{MIN}})/(\Delta \epsilon)$. Therefore, in the $i(\text{MIN})$ zone, $\epsilon_{\text{kinetic}} = \epsilon_{\text{total}}$, and, in any other zone, i ,

$$\epsilon_{\text{kinetic}} = \epsilon_{\text{total}} - (V_i - V_{\text{MIN}})$$

The electrons are mapped from a given kinetic energy bin into the two total energy bins whose kinetic energies overlap with it; the mapping is done in proportion to the area of overlap.

Quantities such as $D(\epsilon)$, $\bar{\epsilon}_{\text{kinetic}}$, and $(\text{pm}\gamma)^{-1}$ for the i th total energy bin are determined by taking the corresponding quantities for the two kinetic energy bins that contributed electrons to the i th total energy bin and averaging them, using the fraction of the electrons in the i th bin contributed by each as weights. In particular, if $\epsilon_{\text{kinetic}} < 0$ for a given total energy bin, then $D(\epsilon) = 0$ for that bin, and this causes electrons to be reflected when their kinetic energy reaches zero as they move up a potential hill.

The remapping is arranged to make the $\bar{E} \cdot j$ energy come out right. The thermal $(\bar{E} \cdot j)$ energy $= -e(\phi_{i+1} - \phi_i)j_{\text{TH}i+1/2}$. Since the suprathermal current $j_s = -j_{\text{TH}}$, if the bins were infinitely fine, the mapping followed by transport followed by any remapping would produce a change in the suprathermal energy $= -e(\phi_{i+1} - \phi_i)j_{s, i+1/2}$ that conserves energy. However, since the bin structure is rather coarse, instead of $-e(\phi_{i+1} - \phi_i)j_{s, i+1/2}$, we get

$$-e(\phi_{i+1} - \phi_i \pm \Delta\epsilon) j_{s, i+1/2},$$

where $\Delta\epsilon =$ the bin width, which can produce large violations of energy conservation after many timesteps. To prevent this when we remap, we choose the weights for the two kinetic energy bins into which each total energy bin can remap its electrons, so that

$$-e(\phi_{i+1} - \phi_i) j_{\text{TH}} - e(\phi_{i+1} - \phi_i \pm \Delta\epsilon) j_s$$

will be minimized.

Author: D. S. Kershaw

Atomic Physics in Inertial Fusion

Pressure Ionization. In dense plasmas, the process of pressure ionization causes bound atomic states to merge into the continuum. In this article, we examine the physical criteria for pressure ionization to justify the procedure used by our code. We have found

that the description chosen for pressure ionization has a substantial effect on predicted values of the plasma thermodynamic and radiative properties. In particular, for the opacity, it is important to assure that the oscillator strength of pressure-ionized states is properly shifted to continuum (bound-free) absorption.

At sufficiently high density, atoms come into close physical proximity. Electrons of the n th quantum shell ($n =$ principal quantum number) have an average orbit radius of $r_n = a_0 n^2 / Z^*$, where $a_0 = 0.529 \times 10^{-8}$ cm is the Bohr radius. These orbit radii grow with n and eventually encounter neighboring ions.

The density effects become important when

$$n_i \geq 1.6 \times 10^{24} \text{ cm}^{-3} \left(\frac{Z^*}{n^2} \right)^3 \quad (128)$$

Equation (128) is obtained²²⁹ by comparing the orbit radius, r_n , with the ion-sphere radius, $R_0 = (3/4 \pi N_i)^{1/3}$. A different criterion would be obtained by comparing r_n with the Debye length, D (Refs. 230 and 231):

$$n_i = 1.9 \times 10^{23} \text{ cm}^{-3} \frac{1}{n^4} \left(\frac{kT}{10 \text{ eV}} \right) \quad (129)$$

For dense plasmas, the Debye length is meaningless, and Eq. (128) is clearly the correct criterion.

The intuitive idea of pressure ionization can be described by three simple criteria. Remarkably, these criteria are mathematically equivalent, so that the three mechanisms always coincide. The three criteria are

- Pressure ionization occurs when corresponding electron-wave functions on adjacent atoms overlap, leading to a broadening of atomic states into energy bands.²³² This occurs when

$$r_n \cong R_0 \quad (130a)$$

- Pressure ionization occurs when the binding energy of an outer electron is exceeded by the (negative) electrostatic potential of neighbor ions,

$$13.6 \text{ eV} \frac{(Z^*)^2}{n^2} \approx \frac{Z^* e^2}{R_0} \quad (130b)$$

The right-hand side of Eq. (130b) is interpreted as the bottom of the continuous spectrum. Since $r_n = a_0 n^2 / Z^*$, Eq. (130b) is equivalent to Eq. (130a).

- Pressure ionization occurs when enough free electrons are compressed inside the orbit (radius = r_n) to significantly reduce its binding. Assuming that Z^* free electrons are uniformly distributed over the ion volume, the fractional number inside the orbit r_n is approximately

$$\delta Z_{\text{free}} \approx Z^* \left(\frac{r_n}{R_0} \right)^3 \quad (130c)$$

In Eq. (130c), δZ_{free} is essentially equal to Z^* for an outer electron being pressure ionized. This criterion is again identical to Eq. (130a) and is equivalent to Eq. (128).

If a plasma is compressed at constant temperature, R_0 decreases, and successively deeper core states are pressure ionized. Alternatively, if the temperature is raised at constant density, Z^* rises and r_n decreases, thereby increasing the number of bound states.

The criteria of Eq. (130) are used in our LASNEX ionization package to provide in-line calculation of atomic data.²³² Although these criteria are clearly appropriate for dense plasmas, the literature of continuum lowering is filled with controversy.²³³ It is often assumed that Eq. (129) governs low-density pressure ionization, a prediction obtained by equating the orbit radius, r_n , to the Debye length, D .

Equation (129) can only be used in low-density plasmas where the Debye-Huckel model is valid (i.e., $R_0 \ll D$). The question concerns large orbits whose radii obey $R_0 \ll r_n \ll D$. These states are often analyzed by solving the Schrödinger equation in the Debye-Huckel potential.²³⁴⁻²³⁶ We find this model to be questionable, since a bound state with an orbit that obeys the inequality $R_0 \ll r_n \ll D$ encircles many ions of the plasma. The "Rydberg atoms" with such large orbits are very delicate, and, in a plasma, they are subject to strong physical perturbations:

- The energy-levels are displaced by Debye screening of the ion potential. For small r_n , the calculated shift is²³⁵

$$E = + \frac{Z^* e^2}{D} - \frac{e^2 a_0}{4D^2} \times [3n^2 - \ell(\ell + 1)] + \dots \quad (131)$$

By itself, Eq. (131) predicts small red shifts of spectral lines.

- The electron energy and effective mass are changed by forward scattering by plasma particles.²³⁷ This effect is not included in Eq. (131).
- Nonforward scattering by plasma particles leads to collisional destruction (lifetime) of the excited state. We compare the orbit circumference, $2\pi r_n$, with the electron mean free path, L , evaluated for velocity $v_n = Z^* e^2 / \hbar n$:

$$\begin{aligned} \frac{2\pi r_n}{L} &= 2\pi r_n \left(\frac{4\pi Z^2 e^4}{m^2 v^4} n_i \ln \Lambda \right) \\ &= 6\pi \left(\frac{r_n}{R_0} \right)^3 \ln \Lambda \end{aligned} \quad (132)$$

For electron states having $R_0 \ll r_n \ll D$, we find $2\pi r_n / L \ll 1$. The electrons are scattered many times before they complete one orbit; therefore, it is unphysical to calculate quantized energies in the Debye-Huckel potential.

- In addition to scattering, there is inhomogeneous line broadening associated with thermal fluctuations of the adjacent plasma, leading to the well-known Inglis-Teller limit.²³⁸ This effect causes bound states to hybridize when

$$\epsilon_{n+1} - \epsilon_n \approx r_n \frac{Z e^2}{R_0^2} \quad (133)$$

This condition is already satisfied whenever $r_n > R_0$.

For these reasons, we conclude that discrete hydrogenic states having $R_0 \ll r_n \ll D$ do not exist in a plasma. The electronic energy spectrum in this energy range is complicated because the electrons interact simultaneously with many atoms. Treatment of these states based on the Debye-Huckel

potential, in particular Eq. (131), appears to be unjustified. Similar conclusions concerning Eq. (131) are reached by Nakayama and DeWitt²³⁹ and by Peacock.²³¹ These remarks refer to low-density plasma ($R_0 \ll D$); at higher density, we cannot use the Debye-Huckel potential in any case.

At present, the LASNEX atomic physics model²³² calculates pressure ionization on the basis of Eq. (128). The discussion given here explains why we use this approach in preference to Eq. (129).

Author: R. M. More

Two-Temperature Equation of State for Dense Plasmas. Plasmas produced by laser irradiation of solids often evolve too rapidly for equality of electron and ion temperatures. Electron-ion heat transfer is strongly impeded by the large ratio of electron and ion masses. If the plasma density is very low, it is reasonable to assume a two-fluid model of interpenetrating ideal gases having separate temperatures and additive properties. In laser plasmas involving heavy elements, the Coulomb interactions are strong enough to significantly modify the ideal-gas equation of state, and a better description is needed.

We have examined the two-temperature plasma from a theoretical viewpoint as a prototype nonequilibrium plasma.²⁴⁰ There are several processes that exchange heat with only one species and thereby induce an electron-ion temperature difference; e.g.,

- Laser heating via inverse bremsstrahlung or resonance absorption deposits absorbed energy directly into the electron velocity distribution.
- Emission of bremsstrahlung or recombination radiation removes energy from the electron distribution. In an optically thin plasma, radiative cooling drains energy from electrons without affecting the ion velocity distribution.
- A strong hydrodynamic shock wave deposits thermal energy mainly in ions at the shock interface. This occurs because ions carry most of the momentum of the moving fluid.

Estimates of the electron-ion heat-exchange time show that the time to equilibrate electron and ion temperatures often exceeds flow or deposition time scales. Most

numerical simulations of ICF targets allow unequal electron and ion temperatures.

We consider the nonequilibrium plasma characterized by unequal electron and ion temperatures.²⁴⁰ The ion pair interactions in such a two-temperature plasma have the approximate form

$$U(r) = \frac{(Ze)^2}{r} e^{-r/D_e} , \quad (134)$$

where D_e is the Debye length associated with electron screening. A sudden energy deposition in the electrons that rapidly raises their temperature is communicated to the ions on two separate time scales:

- Nearly instantaneously (time $\sim 1/\omega_p$), as an alteration of the electron screening length, D_e , ion-pair potential, $U(r)$, and subsequent thermal motion of the ions.
- More slowly, via collisions that transfer random thermal energy from electrons to ions.

The Coulomb interactions transfer energy (but not heat) between the two species in a time much shorter than the temperature relaxation time.

A straightforward statistical treatment²⁴⁰ shows that pressure, energy, and other variables are functions of electron temperature T_e , ion temperature T_i and volume, V . Changes of the energy $E(T_e, T_i, V)$, obey

$$dE = T_e dS_e + T_i dS_i - p dV , \quad (135)$$

where S_e and S_i are separate electron and ion entropies. The pressure and energy do not separate into additive contributions except at low densities.

The generalized condition of thermodynamic consistency is found to be

$$\left(\frac{\partial E}{\partial V} \right)_{T_e, T_i} = T_e \left(\frac{\partial p}{\partial T_e} \right)_{T_i, V} + T_i \left(\frac{\partial p}{\partial T_i} \right)_{T_e, V} - p . \quad (136)$$

This equation is an important restriction on any approximate model for thermodynamic properties of nonequilibrium plasmas. The partial derivative $\partial p / \partial T_e$ is defined as a derivative for constant ion temperature,

T_I ; Eq. (136) reduces to the usual thermodynamic consistency condition in the case of thermal equilibrium plasmas.

Specific heat coefficients are now defined by

$$T_e dS_e = dQ_e = C_{ee} dT_e + C_{ei} dT_I \quad (137a)$$

and

$$T_I dS_I = dQ_I = C_{ie} dT_e + C_{II} dT_I \quad (137b)$$

These equations apply to an infinitesimal transformation occurring at constant volume, V . By use of a Maxwell relation generated from Eq. (135), we can show

$$T_e C_{ie} = T_I C_{ei} \quad (138)$$

The off-diagonal coefficients (e.g., C_{ei}) are found to be negative for specific systems, such as the Debye-Huckel plasma. A more natural set of coefficients is defined by inverting the equation to calculate temperature changes from heat deposited:

$$dT_e = A_{ee} dQ_e + A_{ei} dQ_I \quad (139a)$$

and

$$dT_I = A_{ie} dQ_e + A_{II} dQ_I \quad (139b)$$

For these coefficients, the symmetry is $T_I A_{ei} = T_e A_{ie}$. If an amount of heat, dQ_e , is instantaneously added to electrons (e.g., by a short laser pulse) then, according to Eq. (139), both electron and ion temperatures change. The change in ion temperature is produced indirectly by the change in electron screening.

Equations (135) through (139) are derived by assuming a canonical ensemble distribution function for the position and velocity distributions of electrons and ions.²⁴⁰ The two-temperature effects are largest at dense-plasma conditions, where the electron-ion interaction energy is a significant perturbation of the ideal-gas equation of state.

Analytic formulas for the electron-ion energies are available in the low-density limit. A two-temperature Debye-Huckel theory is given by Salpeter²⁴¹ and Ecker and Kroll²⁴² in the context of plasma Thompson scattering. This theory is easily adapted to the calculation of thermodynamic

properties.²⁴⁰ The interaction free energy, dF_c , is found to be

$$dF_c = -\frac{1}{3} N_e (4\pi n e^4) \left[(Z^2 + 2Z) \frac{D}{kT_I} + \frac{T_I}{kT_e^2} D + 2 \frac{T_e - T_I}{kT_e^2} D_e \right] \quad (140)$$

From this equation, the plasma pressure correction and the specific heat matrix are obtained by differentiation. These analytic results are accurate only where the Debye-Huckel model is applicable; higher-density plasmas must be treated by numerical methods.

Author: R. M. More

Semiclassical Atoms in Dense Plasmas.

Analysis of laser-plasma experiments requires an understanding of atomic properties at high temperature and high plasma density. Sommerfeld²⁴³ used the semiclassical WKB theory to describe the main regularities of x-ray spectra from inner shells of neutral atoms. We extend this theory to ions in plasmas and show that it provides a solid foundation for the widely used average-atom model. This approach gives a clear interpretation of screened charges and quantum defects. New results include improved screening constants and nonhydrogenic formulas for matrix elements important to line radiation and electron excitation.

The WKB energy-quantization condition is

$$\int_{r_1}^{r_2} q(r) dr = \left(n_r + \frac{1}{2} \right) \pi \quad (141)$$

$\times n_r = 0, 1, 2, \dots$

where n_r is the number of oscillations (nodes) in the radial-wave function related to the principal quantum number, n , by $n_r = n - \ell - 1$. The wave number, $q(r)$, is defined by

$$q(r) = \left(\frac{E + eV(r)}{\hbar^2/2m} - \frac{(\ell + 1/2)^2}{r^2} \right)^{1/2}; \quad (142)$$

$q(r)$ vanishes at inner and outer turning points, r_1 and r_2 , respectively, and $V(r)$ is the electrostatic potential. Equation (141) determines electron energy levels $E = E_{n,\ell}$ in the nonrelativistic WKB approximation.

The radial wave function $R_{n,\ell}(r)$ is

$$R_{n,\ell}(r) = \frac{C_{n,\ell}}{q(r)} \sin \left(\frac{\pi}{4} + \int_{r_1}^r q(r') dr' \right) \quad (143)$$

The normalization $C_{n,\ell}$ of the wave function is approximately determined by replacing the $\sin^2$ by $1/2$:

$$1 = \int_0^\infty \left(R_{n,\ell}(r) \right)^2 dr = \frac{1}{2} \left| C_{n,\ell} \right|^2 \int_{r_1}^{r_2} \frac{dr}{q(r)} \quad (144)$$

Averages of any function, $f(r)$, can be evaluated by the same approximation.

For hydrogen-like atoms, these formulas can be evaluated by contour integration; the results are extended to the arbitrary ion by assuming that each electron experiences an effective charge, Q_n .

For each radius r a screened charge $Z(r)$ is determined from the electrostatic potential by

$$V(r) = \frac{Z(r)e}{r} \quad (145)$$

Another effective charge $Q(r)$ is obtained from the electric field at radius, r :

$$E(r) = -\frac{dV}{dr} = \frac{Q(r)e}{r^2} \quad (146)$$

The relation of $Z(r)$ and $Q(r)$ is

$$Q(r) = Z(r) - rZ'(r) \quad (147)$$

where $Z' = dZ/dr$. The term $Q(r)$ is the nuclear charge minus inner screening associated with electrons at $r' \leq r$. The quantity $rZ'(r)$ is associated with outer screening because a shell of charge located at radius greater than r adds a constant to the potential, $V(r)$, and makes a linear contribution to $Z(r)$ (Ref. 244).

The distinction between effective charges $Z(r)$ and $Q(r)$ is especially important in the calculation of radiative processes.

For each electron shell defined by principal quantum number, n , the charge $Z(r)$ is expanded around an average radius, r_n , giving

$$V(r) = eZ'_n + \frac{Q_n e}{r} + \frac{\delta Z_n(r)}{r} \quad (148)$$

Here, $Q_n = Q(r_n)$ and $Z'_n = Z'(r_n)$. The outer screening produces a constant potential, eZ'_n ; the second term is a Coulomb potential that includes only inner screening. The residual non-Coulomb potential is described by $\delta Z_n(r)$.

To simplify the formulas, we represent the energy level, $E_{n,\ell}$, in terms of a wave vector, K :

$$E_{n,\ell} = E_n^0 - \frac{\hbar^2}{2m} K^2 \quad (149)$$

Here, $E_n^0 = -e^2 Z'_n$ is the potential produced by outer electrons.

As a first approximation, we neglect δZ_n and work with

$$q_0(r) = \left(-K^2 + \frac{2Q_n}{a_0 r} - \frac{(\ell + 1/2)^2}{r^2} \right)^{1/2} \quad (150)$$

where $a_0 = \hbar^2/me^2$ is the Bohr radius. This approximation is most accurate for circular orbits ($\ell = n - 1$) that have a minimum extension in radius; $q_0(r)$ is zero at points r_1^0 , r_2^0 . The turning points are close together for $\ell = n - 1$, and it is reasonable to select r_n as $1/2 (r_1^0 + r_2^0)$. This choice gives

$$r_n = a_0 \frac{n^2}{Q_n} \quad (151)$$

We next apply the quantization condition, Eq. (141). The result can be simplified by defining the quantum defect

$$\Delta_{n,\ell} = \frac{1}{\pi} \int_{r_1}^{r_2} q(r') dr' - \frac{1}{\pi} \int_{r_1^0}^{r_2^0} q^0(r') dr' \quad (152)$$

The integral involving $q_0(r)$ is

$$\int_{r_1^0}^{r_2^0} q_0(r') dr' = \frac{Q_n}{a_0 K} - \left(\ell + \frac{1}{2} \right) \quad (153)$$

Combining this with Eq. (151), we find the WKB approximation to the energy levels

$$E_n = E_n^0 - \frac{Q_n^2 e^2}{2a_0(n - \Delta_{n\ell})^2}, \quad (154)$$

where $E_n^0 = -e^2 Z_n'$ is an energy shift associated with outer screening; $Q_n =$ effective charge, including only inner screening; and $\Delta_{n\ell} =$ quantum defect produced by interactions with electrons interior to r_n . If the potential is exactly hydrogenic, $\Delta_{n\ell}$ is zero.

The WKB theory described here reproduces the main regularities of x-ray spectral terms.²⁴³ For example, the splitting of irregular or screening doublets is $T_I = E_{n\ell} - E_{n,\ell-1}$, which is proportional to $(\Delta_{n\ell} - \Delta_{n,\ell-1})$. It is easily shown from Eq. (151) that $\Delta_{n\ell} \propto n/Q_n$, so that $T_I \propto Q_n/n^2$, which is correct. For the regular or spin doublets, $T_R = E_{n,\ell,j=\ell+1/2} - E_{n,\ell,j=\ell-1/2}$. We can evaluate this spin-orbit splitting using a WKB matrix element given in Table 3-8. The result is

$$T_R = \alpha^2 \frac{2Q_n^2 e^2}{2a_0 n^4} \left(\frac{n}{(\ell + 1/2)^2} \right), \quad (155)$$

which is again approximately correct. To match the experimental x-ray spectra, it is important that the inner-screened charge,

Q_n , appear in these splittings, as implied by the WKB model.

In Table 3-9, the quantities Q_n , Z_n , E_n^0 , and $\Delta_{n\ell}$ are given for Fe at 7.59 g/cm³ and 200 eV. These quantities are generated using the Thomas-Fermi-Dirac theory for the atomic potential, $V(r)$. They are compared with numbers obtained from a relativistic self-consistent field model developed by D. Liberman.²⁴⁵ The agreement is remarkable.

To calculate physical averages using WKB wave functions, it is necessary to evaluate radial integrals. The required integrals are generated by expansion of the contour integral

$$I(r) = \oint_c \frac{dz}{(z-r)q_0(z)} = \frac{2\pi}{K} + \frac{2\pi i}{q^0(r)}, \quad (156)$$

where c encloses the branch cuts of $q(r)$. Useful averages are given in Table 3-8 (many of these formulas are exact for hydrogen atoms).

The WKB theory gives a simple derivation of the XSNQ atomic model,^{246,247} as well as suggesting a class of improvements. The energy eigenvalue E_n for electrons of the n th shell is taken to be

$$E_n = E_n^0 - \frac{Q_n^2 e^2}{2a_0 n^2} \quad (157)$$

Table 3-8. Expectation values.

$\langle r \rangle$	$\frac{a_0}{2Q_n} \left[3n^2 - \left(\ell + \frac{1}{2} \right) \right]^2$	$\frac{a_0}{2Q} [3n^2 - \ell(\ell+1)]$
$\langle r^2 \rangle$	$\frac{a_0^2 n^2}{2Q_n^2} \left[5n^2 - 3 \left(\ell + \frac{1}{2} \right) \right]^2$	$\frac{a_0^2 n^2}{2Q^2} [5n^2 + 1 - 3\ell(\ell+1)]$
$\left\langle \frac{1}{r} \right\rangle$	$\frac{Q_n}{a_0 n^2}$	$\frac{Q}{a_0 n^2}$
$\left\langle \frac{1}{r^2} \right\rangle$	$\frac{Q_n^2}{a_0^2} \frac{1}{n^3 \left(\ell + \frac{1}{2} \right)}$	$\frac{Q^2}{a_0^2} \frac{1}{n^3 \left(\ell + \frac{1}{2} \right)}$
$\left\langle \frac{1}{r^3} \right\rangle$	$\frac{Q_n^3}{a_0^3} \frac{1}{n^3 \left(\ell + \frac{1}{2} \right)^3}$	$\frac{Q^3}{a_0^3} \frac{1}{n^3 \left(\ell + \frac{1}{2} \right) (\ell+1)}$
$\left\langle \frac{1}{r^4} \right\rangle$	$\frac{Q_n^4}{a_0^4} \frac{3n^2 - \left(\ell + \frac{1}{2} \right)^2}{2n^5 \left(\ell + \frac{1}{2} \right)^5}$	$\frac{Q^4}{a_0^4} \frac{3n^2 - \ell(\ell+1)}{2n^5 \left(\ell + \frac{3}{2} \right) (\ell+1) \left(\ell + \frac{1}{2} \right) \ell \left(\ell - \frac{1}{2} \right)}$
$\left\langle \frac{-p^4}{8m^3 c^2} \right\rangle$	$\frac{\alpha^2 Q_n^4 e^2}{2a_0 n^4} \left(\frac{3}{4} - \frac{3}{8} \frac{n}{\ell + \frac{1}{2}} - \frac{3}{8} \frac{\ell + \frac{1}{2}}{n} \right)$	$\frac{\alpha^2 Q^4 e^2}{2a_0 n^4} \left(\frac{3}{4} - \frac{n}{\ell + \frac{1}{2}} \right)$

Subshell splittings $E_{n,\ell} - E_{n,\ell'}$ produced by quantum defects $\Delta_{n,\ell}$ or spin-orbit interactions are neglected; this approximation is acceptable for calculation of ionization, but must be refined for calculation of the emission spectra. The orbit radius r_n is taken to be $a_0 n^2 / Q_n$.

The screened nuclear charge Q_n depends on the electron populations P_m of shells inside radius r_n . As a simple approximation, this dependence is represented by a linear formula

$$Q_n = Z - \sum_{m < n} \sigma(n,m) P_m - \frac{1}{2} \sigma(n,n) P_n, \quad (158)$$

where $P_n = 0, 1, 2, \dots, 2n^2$ is the population of the n th shell and Z is the nuclear charge. The coefficient $\sigma(n,m)$ describes screening of the n th shell by the m th. A satisfactory approximation for the outer screening is obtained by assuming

$$E_n^0 = \frac{1}{2} \frac{e^2}{r_n} \sigma(n,n) P_n + \sum_{m > n} \frac{e^2 P_m}{r_m} \sigma(m,n) \quad (159)$$

This form is justified by noting that eP_m/r_m is the potential inside a spherical shell of charge eP_m having radius r_m . The screening coefficients $\sigma(n,m)$ describe the spatial extent of the charge distribution; i.e., the $n = 3$ shell is not entirely inside the $n = 4$ shell.

The total ion energy E_{ion} is not simply the sum of one-electron eigenvalues E_n because that sum counts the electron-electron interactions twice. Instead, we have

$$E_{\text{ion}} = \sum_n E_n P_n - U_{ee} \quad (160)$$

and

$$U_{ee} = - \frac{1}{2} \sum_n P_n \left\langle \psi_n \left| eV(r) - \frac{Ze^2}{r} \right| \psi_n \right\rangle. \quad (161)$$

The electron-electron interaction energy, U_{ee} , is evaluated using formulas from the WKB model (Table 3-10), with the result

$$E_{\text{ion}} = \sum_n \left(- \frac{Q_n^2 e^2}{2a_0 n^2} \right) P_n \quad (162)$$

This equation counts the interaction of each shell with the nucleus and with other electrons inside r_n . From this equation, we can establish the consistency condition

$$\frac{\partial E_{\text{ion}}}{\partial P_n} = - \frac{Q_n^2 e^2}{2a_0 n^2} + E_n^0 = E_n \quad (163)$$

This equation is the equivalent of Koopman's theorem for the model Hamiltonian defined by Eqs. (155) through (158).

Equation (161) is important to the achievement of thermodynamic consistency when the model is applied to high-temperature plasmas. For this reason, any future generalization of the theory to include quantum defects must endeavor to preserve the consistency constraint expressed by Eq. (161).

Table 3-9. TFD/WKB energy levels.

State	Q_n	Z_n	E_n^0 (keV)	$\Delta_{n,\ell}$	E_n (keV)	E_n (Lieberman)
1s	25.52	22.97	-7.086	0.0063	-7.206	-7.284
2s	21.95	16.98	-0.896	0.0968	-1.071	-1.063
2p	21.95	16.98	-0.896	0.444	-0.976	-0.961, 0.948
3s	17.193	11.376	-0.144	0.285	-0.244	-0.238
3p	17.193	11.376	-0.144	0.205	0.213	-0.206, 0.203
3d	17.193	11.376	-0.144	0.069	0.167	0.154, 0.153

NOTE: Iron, $\rho = 7.59 \text{ g/cm}^3$ and $T = 200 \text{ eV}$.

N	M = 1	2	3	4	5	6	7	8	9	10
1	0.3125	0.9380	0.9840	0.9954	0.9970	0.9970	0.9990	0.999	0.9999	0.9999
2	0.2345	0.6038	0.9040	0.9722	0.9979	0.9880	0.9900	0.9990	0.9999	0.9999
3	0.1093	0.4018	0.6800	0.9155	0.9796	0.9820	0.9860	0.9900	0.9920	0.9999
4	0.0622	0.2430	0.5150	0.7100	0.9200	0.9600	0.9750	0.9830	0.9860	0.9900
5	0.0399	0.1597	0.3527	0.5888	0.7320	0.8300	0.9000	0.9500	0.9700	0.9800
6	0.0277	0.1098	0.2455	0.4267	0.5764	0.7248	0.8300	0.9000	0.9500	0.9700
7	0.0204	0.0808	0.1811	0.3184	0.4592	0.6098	0.7374	0.8300	0.9000	0.9500
8	0.0156	0.0624	0.1392	0.2457	0.3711	0.5062	0.6355	0.7441	0.8300	0.9000
9	0.0123	0.0493	0.1102	0.1948	0.2994	0.4222	0.5444	0.6558	0.7553	0.8300
10	0.0100	0.0400	0.0900	0.1584	0.2450	0.3492	0.4655	0.5760	0.6723	0.7612

Table 3-10. New screening constants $\sigma(N, M)$.

LASNEX and Atomic Theory

The practical application of the model described here is based on the set of screening constants, $\sigma(n,m)$. A widely used set of coefficients was derived by Mayer²⁴⁸ from perturbation theory based on hydrogenic wave functions. The Mayer coefficients are satisfactory for highly stripped ions, but require modification for nearly neutral atoms because their

predictions are not accurate in that case. An alternative set of coefficients has been developed by least-squares fitting to a data base containing 800 ionization potentials.²⁴⁹ These new coefficients give an improved representation of the ionization of heavy atoms (Table 3-10).

Author: R. M. More

1. J. H. Nuckolls, L. L. Wood, A. R. Thiessen, and G. B. Zimmerman, "Laser-Compression of Matter to Super High Densities: Thermonuclear (CTR) Applications," <i>Nature</i> 239, 139 (1972). 2. Yu. V. Afans'ev, N. G. Basov, P. P. Volosevich, E. G. Gamalii, O. N. Krokhin, S. P. Kurdyumov, E. I. Levanov, V. B. Rozanov, A. A. Samarskii, and A. N. Tikhonov, "Laser Initiation of Thermonuclear Reaction in Inhomogeneous Spherical Targets," <i>JETP Lett.</i> 21, 68 (1975); K. A. Brueckner, "Laser Driven Fusion," <i>IEEE PS-1</i>, 13 (1973); J. S. Clarke, H. N. Fisher, and R. J. Mason, "Laser-Driven Implosion of Spherical DT Targets to Thermonuclear Burn Conditions," <i>Phys. Rev. Lett.</i> 30, 89 (1973).	3. R. E. Kidder, <i>Consequences of Intensity Constraints on Inertial Confinement Fusion</i>, Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-83342 (1979). 4. M. H. Key et al., Science Research Council, Rutherford Laboratory, Chilton, Didcot, Oxfordshire, England, RL-80-023 (1980). 5. R. E. Kidder, <i>Consequences of Intensity Constraints on Inertial Confinement Fusion</i>, Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-83342, Rev. 1 (1980).	<p>Ignition and SBE at 10 kJ
3-4</p>
6. J. D. Lindl, <i>Low Aspect Ratio Double Shell Targets for High Density and High Gain and a Comparison with Ultra Thin Shells</i>, Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-79735, Rev. 1 (1977).	7. R. C. Kirkpatrick, C. C. Cremer, L. C. Madsen, H. H. Rogers, and R. S. Cooper, "Structured Fusion Target Designs," <i>Nuclear Fusion</i> 15, 333 (1975).	<p>Ignition and SBE at 0.1 to 1 MJ
3-5</p>
8. H. G. Ahlstrom, L. W. Coleman, F. Rienecker, Jr., and V. W. Slivinsky, "Diagnostics of Shiva Nova High-Yield Thermonuclear Events," <i>J. Opt. Soc. Am.</i> 68, 1731 (1978).	9. <i>Laser Program Annual Report—1978</i>, Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-78 (1979), p. 6-45.	<p>Main Fuel Diagnostics in 0.1- to 1-MJ Ignition and SBE Experiments
3-8</p>
10. <i>Laser Program Annual Report—1979</i>, Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-79 (1980), p. 5-26.		<p>Implosion Diagnostics in 0.1- to 1-MJ Ignition and SBE Experiments
3-9</p>
11. W. L. Kruer and K. G. Estabrook, <i>Nonlinear Behavior of Stimulated Scatter in Large Underdense Plasmas</i>, Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-83743 (1979).	12. C. E. Max and Kent Estabrook, <i>Comments Plasma Phys. Contr. Fusion</i> 5, 239 (1980).	<p>Coupling Experiments with 0.1- to 1-MJ Drivers
3-10</p>
13. B. Yaakobi, S. Skupsky, R. L. McCrory, C. F. Hooper, H. Deckmen, P. Bourke, and J. M. Soures, <i>Phys. Rev. Lett.</i> 44, 1072 (1980).	14. H. Azechi, Y. Kato, N. Miyanaga, T. Mochizuki, E. Morikawa, T. Sasaki, K. Yamada, K. Yoshida, and C. Yamanaka, in <i>Proc. CLEOS/ICF, WB8</i> (Washington, D.C., 1980).	<p>A Calculational Comparison of D-T, Neon, and Argon Implosions—Introduction
3-11</p>
15. L. Spitzer, <i>Physics of Fully Ionized Gases</i> (Interscience Publishers, New York, 1962), p. 144. 16. J. Bond, K. Watson, and J. Welch, <i>Atomic Theory of Gas Dynamics</i> (Addison-Wesley Publishing Company, Reading, Mass., 1965), p. 138.	17. J. Bond, K. Watson, and J. Welch, <i>Atomic Theory of Gas Dynamics</i> (Addison-Wesley Publishing Company, Reading, 1965), p. 131. 18. Y. Zel'dovich and Y. Raizer, <i>Physics of Shock Waves and High Temperature Hydrodynamic Phenomena</i>, Vol. II (Academic Press, New York, 1967), p. 526.	<p>Physics of Moderate-Density Implosions
3-11</p>
19. W. C. Mead, C. D. Orth, D. S. Bailey, G. F. McClellan, and K. G. Estabrook, <i>Analysis of Dense Pusher Laser-Driven Implosion for Intermediate Densities</i>, Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-83163 (1979). 20. G. B. Zimmerman and W. L. Kruer, <i>Comments Plasma Phys.</i> 2, 85 (1975).	21. <i>Laser Program Annual Report—1977</i>, Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-77 (1978), p. 4-31. 22. W. A. Lokke and W. H. Grasberger, <i>XSNQ-U: A Non-LTE Emission and Absorption Coefficient Subroutine</i>, Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-52276 (1977).	<p>Calculational Parameters
3-12</p>

References

Comparison of Calculational Results 3-12

23. Y. Zel'dovich and Y. Raizer, *Physics of Shock Waves and High Temperature Hydrodynamic Phenomena*, Vol. II (Academic Press, New York, 1967), p. 515.

Charged-Particle Fusion 3-17

24. *Laser Program Annual Report—1979*, Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-79 (1980), p. 8-109.
25. A. W. Mashke, *Space-Charge Limits for Linear Accelerators*, Brookhaven National Laboratory, Brookhaven, Mass., BNL 51022 (1979) and BNL 51029 (1979).

Ion-Beam Target Gain for a Range of Beam-Input Parameters 3-17

26. *Laser Program Annual Report—1979*, Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-79 (1980), p. 3-2.
27. *Laser Program Annual Report—1979*, Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-79 (1980), p. 8-109.
28. K. A. Brueckner (Ed.), *Assessment of Drivers and Reactors for Inertial Confinement Fusion*, Electric Power Research Institute, Palo Alto, Calif., EPRI AP-1371, Project 1346-1, Final Report (1980).

Transport of Heavy-Ion Beams to the Target 3-19

29. S. S. Yu, H. L. Buchanan, E. P. Lee, and F. W. Chambers, *Beam Propagation Through a Gaseous Reactor-Classical Transport*, Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-82029 (1979).
30. H. L. Buchanan, F. W. Chambers, E. P. Lee, S. S. Yu, R. J. Briggs, and M. N. Rosenbluth, in *Proc. of the Third Intern. Topical Conf. on High-Power Electron and Ion-Beam Research and Technology* (Novosibirsk, 1979).
31. E. W. Suvov, J. S. Karbowski, T. V. Prevenslik, L. Green, A. Y. Lee, R. E. Godl, H. J. Carber, M. Sniderman, R. V. Babcock, M. D. Neihemow, L. H. Taylor, R. J. Eusoz, W. C. Brenner, D. H. Sink, E. M. Iwinski, and R. J. Ravas, "The Westinghouse ICF Power Plant Study," in *Proc. 4th ANS Topical Meeting Technol. Contr. Nucl. Fusion* (King of Prussia, Pa., October 1980) (in press).
32. M. J. Monsler, J. A. Blink, J. Hovingh, W. R. Meier, and P. E. Walker, *Electric Power from Inertial Confinement Fusion: The HYLIFE Concept*, Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-81866 (1978).
33. J. H. Pitts, J. Hovingh, W. R. Meier, M. T. Monsler, E. G. Powell, and P. E. Walker, *Potential Design Modifications for the High-Yield Lithium Injection Fusion Energy (HYLIFE) Reaction Chamber*, Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-82895 (1979).
34. R. J. Brigg, J. C. Clark, T. J. Fessenden, R. E. Hester, and E. J. Lauer, "Transport of Self-Focused Relativistic Electron Beams," in *Proc. 2nd Intern. Topical Conf. High-Power Electron and Ion Beam Res. and Technol.*, J. H. Nation and R. Sudan, Eds. (Cornell University, 1977), p. 319.
35. J. W-K. Mark, R. O. Bangerter, W. M. Fawley, S. S. Yu, G. Krafft, and T-S. F. Wang, *Heavy-Ion Inertial Fusion: Comments on Achievable Temperatures for Disk Heating Experiments Using Proposed Accelerator Test Facilities*, Lawrence Livermore National Laboratory, Livermore, Calif., proceedings of the Fourth International Topical Conference on High-Power Electron and Ion-Beam Research and Technology (Palaiseau, France), in press.
36. W. B. Herrmannsfeldt, *High-Intensity, Multimegajoule Heavy-Ion Accelerator*, Lawrence Berkeley National Laboratory, Berkeley, Calif., HIFAN-122 (1980).

Plasma Theory— Introduction 3-24

37. C. E. Max and K. G. Estabrook, *Comments Plasma Phys. Contr. Fusion* 5, 239 (1980).
38. E. Fabre, *Bull. Am. Phys. Soc.* 25, 992 (1980).
39. W. Seka et al., *Bull. Am. Phys. Soc.* 25, 895 (1980).
40. D. C. Slater, *Bull. Am. Phys. Soc.* 25, 992 (1980).
41. B. I. Cohen, A. N. Kaufman, and K. M. Watson, *Phys. Rev. Lett.* 29, 581 (1972).
42. D. W. Forslund, J. M. Kindel, and E. L. Lindman, *Phys. Fluids* 18, 1003 (1975).
43. W. L. Kruer, K. G. Estabrook, and K. H. Sinz, *Nucl. Fusion* 13, 952 (1973); W. L. Kruer, K. G. Estabrook, B. F. Lasinski, and A. B. Langdon, *Phys. Fluids* 23, 1326 (1980).
44. K. G. Estabrook, W. L. Kruer, and B. F. Lasinski, *Phys. Rev. Lett.* 45, 1399 (1980).
45. K. G. Estabrook, J. A. Harte, E. M. Campbell, F. Ze, D. W. Phillion, M. D. Rosen, and J. T. Larsen, *Phys. Rev. Lett.* 46, 724.
46. C. J. Randall, J. A. Albritton, and J. J. Thomson, *Theory and Simulations of Simulated Brillouin Scatter Excited by Non-Absorbed Light in Laser Fusion Systems*, Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-84330 (1980).
47. H. E. Huey, A. Mase, N. C. Luhmann, Jr., W. F. DiVergilio, and J. J. Thomson, *Phys. Rev. Lett.* 45, 795 (1980).
48. W. L. Kruer and K. G. Estabrook, *Nonlinear Behavior of Stimulated Scatter in Long Underdense Plasmas*, Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-83743 (1979).
49. M. J. Herbst, J. A. Stamper, R. R. Whitlock, S. P. Obenschain, B. H. Ripin, and S. E. Bodner, *Bull. Am. Phys. Soc.* 25, 857 (1980).
50. C. E. Clayton, C. Joshi, and A. Yasuda, *Bull. Am. Phys. Soc.* 25, 907 (1980).

51. C. E. Max and K. G. Estabrook, *Comments Plasma Phys. Contr. Fusion* **5**, 239 (1980).
52. J. H. Nuckolls, L. L. Wood, A. R. Thiessen, and G. B. Zimmerman, *Nature* **329**, 139 (1972).
53. T. W. Johnston and J. M. Dawson, *Phys. Fluids* **16**, 722 (1973).
54. A. B. Langdon, *Phys. Rev. Lett.* **44**, 575 (1980).
55. W. L. Kruer, *Comments Plasma Phys. Contr. Fusion* **5**, 69 (1979).
56. E. Fabre, *Bull. Am. Phys. Soc.* **25**, 992 (1980).
57. W. Seka et al., *Bull. Am. Phys. Soc.* **25**, 895 (1980); D. C. Slater, *Bull. Am. Phys. Soc.* **25**, 992 (1980).
58. V. L. Ginzburg, *The Properties of Electromagnetic Waves in Plasmas* (Pergamon Press, New York, 1964), p. 260; J. P. Friedberg, R. W. Mitchell, R. R. Morse, and L. F. Rudinski, *Phys. Rev. Lett.* **28**, 795 (1972).
59. K. G. Estabrook, E. J. Valeo, and W. L. Kruer, *Phys. Fluids* **18**, 1151 (1975); D. W. Forslund, J. M. Kindel, K. Lee, E. Lindman, and R. L. Morse, *Phys. Rev. A* **11**, 679 (1975).
60. K. G. Estabrook and W. L. Kruer, *Phys. Rev. Lett.* **40**, 42 (1978); D. W. Forslund, J. M. Kindel, and K. Lee, *Phys. Rev. Lett.* **39**, 284 (1977); J. A. Albritton and A. B. Langdon, *Phys. Rev. Lett.* **22**, 1794 (1980).
61. J. J. Thomson and W. L. Kruer, *Comments Plasma Phys. Contr. Fusion* **3**, 129 (1978).
62. P. K. Kaw, W. L. Kruer, C. S. Liu, and K. Niskikawa, *Advances in Plasma Physics*, Vol. 16 (John Wiley, New York, 1976), p. 1-270.
63. A. B. Langdon, B. F. Lasinski, and W. L. Kruer, *Phys. Rev. Lett.* **43**, 113 (1979).
64. K. G. Estabrook, W. L. Kruer, and B. F. Lasinski, *Phys. Rev. Lett.* **45**, 1399 (1980).
65. R. G. Watt, R. D. Brooks, and Z. A. Pietrzyk, *Phys. Rev. Lett.* **41**, 170 (1978).
66. D. W. Phillion, *Bull. Am. Phys. Soc.* **25**, 993 (1980).
67. *Laser Program Annual Report—1979*, Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-79 (1980), p. 3-25.
68. W. L. Kruer and K. G. Estabrook, *Nonlinear Behavior of Stimulated Scatter in Large Underdense Plasmas*, Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-83743 (1979).
69. B. H. Ripin et al., *Phys. Rev. Lett.* **39**, 611 (1977).
70. W. L. Kruer, *Comments Plasma Phys. Contr. Fusion* **4**, 13 (1978).
71. M. J. Herbst et al., *Bull. Am. Phys. Soc.* **25**, 857 (1980); C. E. Clayton, C. Joshi, and A. Yasuda, *Bull. Am. Phys. Soc.* **25**, 907 (1980).
72. *Laser Program Annual Report—1979*, Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-79 (1980), p. 3-25.
73. C. S. Liu and M. N. Rosenbluth, "Parametric Decay of Electromagnetic Waves into Two Plasmons and Its Consequences," *Phys. Fluids* **19**, 967 (1976).
74. A. B. Langdon, B. F. Lasinski, and W. L. Kruer, "Nonlinear Saturation and Recurrence of the Two-Plasmon Decay Instability," *Phys. Rev. Lett.* **43**, 133 (1979).
75. A. B. Langdon, B. F. Lasinski, and W. L. Kruer, *Plasma Heating at One-Quarter Critical Density*, Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-75018 (1973).
76. A. B. Langdon and B. F. Lasinski, "Electromagnetic and Relativistic Plasma Simulation Models," in *Methods in Computational Physics*, Vol. 16, B. Alder and S. Fernbach, Eds. (Academic Press, New York, 1976), p. 327.
77. W. L. Kruer, K. G. Estabrook, B. F. Lasinski, and A. B. Langdon, "Raman Backscatter in High Temperature, Inhomogeneous Plasmas," *Phys. Fluids* **23**, 1326 (1980).
78. K. G. Estabrook, W. L. Kruer, and B. F. Lasinski, "Heating by Raman Backscatter and Forward Scatter," *Phys. Rev. Lett.* **45**, 1399 (1980).
79. D. W. Phillion, W. L. Kruer, and V. C. Rupert, "Brillouin Scatter in Laser Produced Plasmas," *Phys. Rev. Lett.* **39**, 1529 (1977).
80. *Laser Program Annual Report—1977*, Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-77 (1978), p. 4-49.
81. J. L. Bobin, M. Decroisset, B. Meyer, and Y. Vitel, "Harmonic Generation and Parametric Excitation of Waves in a Laser-Created Plasma," *Phys. Rev. Lett.* **30**, 594 (1973).
82. D. W. Phillion, *Observation of Raman-Scattered Light in 1.06 μ m Laser-Irradiated Plasma*, Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-84148 (1980).
83. J. Elazar, W. Toner, and E. R. Wooding, *Backscattered Radiation at $\omega_0/2$ from Neodymium Laser Plasma Interactions*, Rutherford Laboratory, Chilton, Didcot, England, RL-80-026 (1980).
84. H. A. Baldis, J. C. Samson, and P. B. Corkum, "Two-Plasmon Decay and Profile Modification Produced by 10.6- μ m Radiation at Quarter-Critical Density," *Phys. Rev. Lett.* **41**, 1719 (1978).
85. N. A. Ebrahimi, H. A. Baldis, C. Joshi, and R. Benesch, "Hot Electron Generation by the Two-Plasmon Decay Instability in the Laser-Plasma Interaction at 10.6 μ m," *Phys. Rev. Lett.* **45**, 1179 (1980).
86. K. G. Estabrook, W. L. Kruer, and B. F. Lasinski, "Heating by Raman Backscatter and Forward Scatter" *Phys. Rev. Lett.* **45**, 1399 (1980).
87. *Laser Program Annual Report—1979*, Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-79 (1980), p. 3-20.
88. *Laser Program Annual Report—1979*, Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-79 (1980), p. 6-32; D. W. Phillion, (to be published).
89. C. S. Liu, M. N. Rosenbluth, and R. B. White, *Phys. Fluids* **17**, 121 (1974); D. W. Forslund, J. M. Kindel, and E. L. Lindman, *Phys. Fluids* **18**, 1002 (1975); W. Manheimer, and H. Klein, *Phys. Fluids* **17**, 1889 (1974); B. I. Cohen, A. N. Kaufman, and K. M. Watson, *Phys. Rev. Lett.* **29**, 581 (1972); W. L. Kruer, K. G. Estabrook, and K. H. Sinz, *Nuc. Fusion* **13**, 952 (1973); J. J. Thomson, *Phys. Fluids* **21**, 2082 (1978); T. Tajima and J. M. Dawson, *Phys. Rev. Lett.* **43**, 267 (1979).

**Laser Plasma
Coupling in Reactor-
Size Targets**
3-25

**Heating and Hot-
Electron Generation
in Underdense
Plasmas**
3-30

**Theory and
Simulation of
One-Dimensional
Raman Forward
Scattering**
3-34

References

Theory and Stimulations of One-Dimensional Raman Forward Scattering (cont.)

90. J. F. Drake and Y. C. Lee, *Phys. Rev. Lett.* **31**, 1197 (1973).
91. W. L. Kruer, K. G. Estabrook, B. F. Lasinski, and A. B. Langdon, *Phys. Fluids* **23**, 1326 (1980).
92. A. B. Langdon, B. F. Lasinski, and W. L. Kruer, *Phys. Rev. Lett.* **43**, 133 (1979); A. B. Langdon and B. F. Lasinski, *Phys. Rev. Lett.* **34**, 934 (1975).
93. D. W. Phillion, W. L. Kruer, and V. C. Rupert, *Phys. Rev. Lett.* **39**, 1529 (1977).
94. M. N. Rosenbluth, *Phys. Rev. Lett.* **29**, 565 (1972).

Heated Electron Distributions from Laser Absorption on Ion Acoustic Turbulence 3-37

95. R. J. Faehl and W. L. Kruer, "Laser Light Absorption by Short Wavelength Ion Turbulence," *Phys. Fluids* **20**, 55 (1977).
96. W. M. Manheimer, D. G. Colombant, and B. H. Ripin, "Efficient Light Absorption by Ion-Acoustic Fluctuations in Laser-Produced Plasmas," *Phys. Rev. Lett.* **38**, 1135 (1977).
97. J. M. Dawson and C. Oberman, "High-Frequency Conductivity and the Emission and Absorption Coefficients of a Fully Ionized Plasma," *Phys. Fluids* **5**, 517 (1962).
98. R. L. Stenzel, "Experiments on Current-Driven Three Dimensional Ion Sound Turbulence. Part II: Wave Dynamics," *Phys. Fluids* **21**, 99 (1978).
99. M. Yamada and M. Raether, "Saturation of the Ion-Acoustic Instability in a Weakly Ionized Plasma," *Phys. Rev. Lett.* **32**, 99 (1974).
100. Y. Amagishi, "Turbulent-Like Spectrum of Ion Waves in a Beam-Plasma System," *Phys. Rev. Lett.* **29**, 405 (1972).
101. Y. Kawai and M. Guyot, "Observation of Anomalous Resistivity Caused by Ion Acoustic Turbulence," *Phys. Rev. Lett.* **39**, 1141 (1977).
102. W. M. Bollen, J. S. DeGroot, K. Mizuno, R. B. Spielman, and R. L. Walraven, "Experimental Investigation of Current Driven Ion Acoustic Turbulence and Anomalous DC Resistivity," *Bull. Am. Phys. Soc.* **24**, 935 (1979).
103. K. G. Estabrook, E. J. Valeo, and W. L. Kruer, "Two-Dimensional Relativistic Simulations of Resonance Absorption," *Phys. Fluids* **18**, 1151 (1975).
104. K. G. Estabrook and J. E. Tull, *An 880 Nanosecond Particle in Cell Mover for the CDC 7600*, Lawrence Livermore National Laboratory, Livermore, Calif., UCID-17050 (1977).

Analysis of Short-Pulse Absorption Experiments at 1.06-, 0.53-, and 0.27- μ m Laser Wavelengths 3-39

105. C. E. Max and K. G. Estabrook, *Comments Plasma Phys. Contr. Fusion* **5**, 239 (1980).
106. C. Garban-Labaune, E. Fabre, R. Fabbro, F. Amiranoff, and M. Weinfeld, "Absorption Experiments with a Neodymium Laser at Different Wavelengths," in *Rapport d'Activité 1979, GRECO Interaction Laser-Matière* (École Polytechnique, Palaiseau, France), p. 64.
107. J. Virmont, R. Pellat, and P. Mora, *Phys. Fluids* **21**, 567 (1978); D. Shvarts, C. Jablon, I. B. Bernstein, J. Virmont, and P. Mora, *Nucl. Fusion* **19**, 1457 (1979); E. Goldman, *Plasma Phys.* **15**, 289 (1977).
108. V. L. Ginzburg, *The Propagation of Electromagnetic Waves in Plasmas* (Addison-Wesley, Reading, 1964), pp. 205-229 and 364-368.
109. L. Spitzer, Jr., *Physics of Fully Ionized Gases* (Wiley-Interscience, New York, 1964), Section 5.5.
110. W. L. Kruer, *Comments Plasma Phys. Contr. Fusion* **5**, 69 (1979).
111. C. E. Max, C. F. McKee, and W. C. Mead, *Phys. Fluids* **23**, 1620 (1980).
112. R. Fabbro, E. Fabre, F. Amiranoff, and M. Weinfeld, in *Rapport d'Activité 1979, GRECO Interaction Laser-Matière* (École Polytechnique, Palaiseau, France), p. 113.
113. R. Faehl and W. L. Kruer, *Phys. Fluids* **20**, 55 (1977); W. M. Manheimer, *Phys. Fluids* **20**, 265 (1977).
114. J. J. Thomson et al., *Phys. Fluids* **21**, 707 (1978).
115. K. G. Estabrook, E. J. Valeo, and W. L. Kruer, *Phys. Fluids* **18**, 1151 (1975); J. P. Friedberg et al., *Phys. Rev. Lett.* **28**, 795 (1972).
116. J. A. Stamper et al., *Phys. Rev. Lett.* **26**, 1012 (1971).

Effect of Supersonic Flow on Density Profiles 3-44

117. J. Dawson, P. Kaw, and B. Green, *Phys. Fluids* **12**, 875 (1969).
118. J. Denavit, *Phys. Fluids* **22**, 1384 (1979).
119. K. G. Estabrook and J. E. Tull, *An 880 Nanosecond Particle in Cell Mover for the CDC 7600*, Lawrence Livermore National Laboratory, Livermore, Calif., UCID-17050 (1977).
120. J. P. Friedberg, R. W. Mitchell, R. L. Morse, and L. I. Rudinski, *Phys. Rev. Lett.* **28**, 795 (1972); P. Koch and J. Albritton, *Phys. Rev. Lett.* **32**, 1420 (1974).
121. K. G. Estabrook, E. J. Valeo, and W. L. Kruer, *Phys. Lett.* **A49**, 109 (1974); K. G. Estabrook, E. J. Valeo, and W. L. Kruer, *Phys. Fluids* **18**, 1151 (1975); D. Forslund, J. Kindel, K. Lee, E. Lindman, and R. L. Morse, *Phys. Rev.* **A11**, 679 (1975); K. Lee, D. W. Forslund, J. M. Kindel, and E. L. Lindman, *Phys. Fluids* **20**, 51 (1977); R. D. Jones, C. H. Aldrich, and K. Lee, Los Alamos National Laboratory, Los Alamos, N. Mex., Preprint LA-UR-80-1325 (1980).
122. J. R. Albritton and A. B. Langdon, *Phys. Rev. Lett.* **45**, 1794 (1980).
123. C. E. Max and C. F. McKee, *Phys. Rev. Lett.* **39**, 21 (1977).
124. L. V. Powers, G. R. Montry, and R. L. Berger, *Nucl. Fusion* **19**, 659 (1979).
125. J. Virmont, R. Pellat, and A. Mora, *Phys. Fluids* **21**, 567 (1978).
126. W. Woo, R. B. Spielman, and J. S. DeGroot, *Bull. Am. Phys. Soc.* **23**, 792 (1978).
127. S. M. Jackel, *Spatially and Temporally Resolved Harmonic Emission Studies of Laser Plasmas*, Ph.D. thesis, University of Rochester, Rochester, N.Y. (1977).

-
128. N. G. Basov, V. Yu. Bychenko, O. N. Krokhin, M. V. Osipov, A. A. Rupashov, V. P. Silin, G. V. Sklizkov, A. N. Starodub, V. T. Tikhonchuk, and A. S. Shikanov, *Sov. J. Quantum Electron.* **9**, 1081 (1979).
129. A. J. Cole, R. G. Evans, D. Gray, J. D. Murdoch, S. M. L. Sim, and W. T. Toner, Rutherford Laboratory, Chilton, Didcot, England, RL-79-036 (1979); P. D. Carter, S. M. L. Sim, H. C. Barr, and R. G. Evans, *Phys. Rev. Lett.* **44**, 1407 (1980).
130. R. Fedosejevs, M. D. J. Burgess, G. D. Enright, and M. C. Richardson, *Phys. Rev. Lett.* **43**, 1664 (1979).
-
131. A. Raven and O. Willi, *Phys. Rev. Lett.* **43**, 4 (1979).
132. R. Benattar and C. Popovics, *Phys. Rev. Lett.* **45**, 1108 (1980).
133. Yu. A. Zakharenkov, N. N. Zorev, O. N. Krokhin, Yu. A. Mikhailov, A. A. Rupasov, G. V. Sklizkov, and A. S. Shikanov, *JETP Lett.* **21**, 259 (1975).
134. *Laser Program Annual Report—1978*, Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-78 (1979), p. 3-26.; R. B. Spielman, *Experimental Observation of Strong Profile Modification by an Electromagnetic Wave in an Inhomogeneous Plasma*, Ph.D. thesis, University of California, Davis, Calif. (1978).
-
135. *Laser Program Annual Report—1979*, Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-79 (1980), p. 3-39.
136. *Laser Program Annual Report—1978*, Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-78 (1979), p. 3-53.
137. C. J. Randall, J. A. Albritton, and J. J. Thomson, "Theory and Simulations of Stimulated Brillouin Scatter Excited by Non-Absorbed Light in Laser Fusion Systems" (to be published in *Phys. Fluids*).
138. T. Dewandre, J. R. Albritton, and E. A. Williams, "Doppler Shift of Laser Light Reflected from Expanding Plasmas" (to be published in *Phys. Fluids*).
-
139. D. W. Forslund, J. M. Kindel, and E. L. Lindman, *Phys. Fluids* **18**, 1002 (1975).
140. *Laser Program Annual Report—1978*, Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-78 (1979), p. 3-65.
141. J. M. Dawson, W. L. Kruer, and B. Rosen, *Dynamics of Ionized Gases*, M. Lighthill, I. Imai, and H. Sato, Eds. (Univ. of Tokyo Press, Tokyo, 1973), pp. 47-61.
142. J. R. Albritton and A. B. Langdon, *Phys. Rev. Lett.* **22**, 1794 (1980).
143. B. Bezzerides, D. W. Forslund, and E. L. Lindman, *Phys. Fluids* **21**, 2179 (1978).
-
144. M. N. Rosenbluth, *Phys. Rev. Lett.* **29**, 565 (1972).
145. D. Pesme, G. Laval, and R. Pellat, *Phys. Rev. Lett.* **31**, 203 (1973).
146. A. N. Kaufman and B. I. Cohen, *Phys. Rev. Lett.* **30**, 1306 (1973).
-
147. C. J. Randall, J. J. Thomson, and K. G. Estabrook, *Phys. Rev. Lett.* **43**, 924 (1979); C. J. Randall, J. A. Albritton, and J. J. Thomson, *Theory and Simulations of Stimulated Brillouin Scatter Excited by Non-Absorbed Light in Laser Fusion Systems*, Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-84330 (1980).
-
148. A. B. Langdon, *J. Comput. Phys.* **30**, 202 (1979).
149. R. J. Mason, "Implicit Moment Particle Simulation of Plasmas" (to be published in *J. Comput. Phys.*).
150. J. Denavit, "Time Filtering Particle Simulations with $\omega_{pe}\Delta t \gg 1$ " (to be published in *J. Comput. Phys.*).
-
151. A. Friedman, R. L. Ferch, R. N. Sudan, and A. T. Drobot, *Plasma Phys.* **19**, 1101 (1977); A. Mankofsky, A. Friedman, and R. N. Sudan, "Numerical Simulation of Injection and Resistive Trapping of Ion Rings" (to be published in *Plasma Phys.*).
152. D. O. Dickman, R. L. Morse, and C. W. Nielson, *Phys. Fluids* **12**, 1708 (1969).
-
153. R. C. Malone, R. L. McCrory, and R. L. Morse, *Phys. Rev. Lett.* **34**, 721 (1975).
154. R. A. Haas, W. C. Mead, W. L. Kruer, D. W. Phillion, H. N. Kornblum, J. D. Lindl, D. MacQuigg, V. C. Rupert, and K. G. Tirsell, *Phys. Fluids* **20**, 322 (1977).
155. F. C. Young, R. R. Whitlock, R. Decoste, B. H. Ripin, D. J. Nagel, J. A. Stamper, J. M. McMahon, and S. E. Boder, *Appl. Phys. Lett.* **30**, 45 (1977).
156. B. Yaakobi and T. Bristow, *Phys. Rev. Lett.* **38**, 350 (1977).
157. D. L. Banner, W. C. Mead, E. M. Campbell, and W. L. Kruer, "Electron Transport Analysis Using Layered Slab Targets," *Laser Program Annual Report—1979*, Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-79 (1980), p. 6-12.
158. Y. L. Teng, R. Fedosijevs, R. Sigel, K. Eidmann, R. Petsch, and G. Spindler, "High Speed Photography of Laser-Irradiated Thin Foils," in *14th European Conf. Laser Interact. Matter* (Sept. 15-19, 1980, Palaiseau, France); R. Fabbro, F. Amiranoff, E. Fabre, C. Garban-Labaune, J. Virmont, and M. Weinfeld, "Transport Experiments at Different Wavelengths," in *14th European Conf. Laser Interact. Matter* (Sept. 15-19, 1980, Palaiseau, France); G. Thiell, B. Meyer, J. Lauriou, D. Galmiche, G. Morin, and D. Redon, "Transport Processes Studies in Thin Foil Laser Irradiated Experiments," in *14th European Conf. Laser Interact. Matter* (Sept. 15-19, 1980, Palaiseau, France).
-
- Effect of Supersonic Flow on Density Profiles**
(cont.)
- A Model for Stimulated Brillouin Scatter Induced by Nonabsorbed Light**
3-49
- Stimulated Brillouin Scatter with Broadband Thermal Noise**
3-52
- Implicit Large-Timestep Particle Simulations**
3-57
- Relevance of Ion-Acoustic Instability to Thermal-Transport Inhibition in Plasmas Produced by Nd Lasers**
3-59

References

Relevance of Ion-Acoustic Instability to Thermal-Transport Inhibition in Plasmas Produced by Nd Lasers (cont.)

159. L. L. Cowie and C. F. McKee, *Astrophys. J.* **211**, 135 (1977).
160. S. J. Gitomer and D. B. Henderson, *Phys. Fluids* **22**, 364 (1979).
161. M. H. Key et al., *Transport Inhibition Experiment at 1.06 μm* , Rutherford Laboratory, Chilton, Didcot, England, RL-79-036 (1979).
162. W. M. Manheimer and H. H. Klein, "Reexamination of Strongly Flux-Limited Thermal Conduction in Laser-Produced Plasmas," *Phys. Fluids* **18**, 1299 (1975).
163. D. Biskamp and R. Chodura, *Phys. Rev. Lett.* **27**, 1553 (1971).
164. D. Biskamp and R. Chodura, *Plasma Phys. Contr. Nucl. Fusion Res.* **2**, 265 (1971).
165. D. Biskamp and R. Chodura, *Phys. Fluids* **16**, 893 (1973).
166. D. Biskamp, K. U. Von Hagenow, and H. Welter, *Phys. Lett.* **A39**, 351 (1972).
167. M. Lampe, W. M. Manheimer, J. B. McBride, J. H. Orens, R. Shanny, and R. N. Sudan, *Phys. Rev. Lett.* **26**, 1221 (1971).
168. J. A. Wesson, A. Sykes, and H. R. Lewis, *Plasma Phys.* **15**, 49 (1973).
169. C. T. Dum, R. Chodura, and D. Biskamp, *Phys. Rev. Lett.* **32**, 1231 (1974).
170. M. Lampe, W. M. Manheimer, J. B. McBride, J. H. Orens, K. Papadopoulos, R. Shanny, and R. N. Sudan, *Phys. Fluids* **15**, 662 (1972).
171. M. Z. Caponi and R. C. Davidson, *Phys. Rev. Lett.* **31**, 86 (1973).
172. E. L. Lindman, *J. de Physique* **38**, Colloque C6, 9 (1977).
173. J. S. DeGroot, C. Barnes, A. E. Walstead, and O. Buneman, *Phys. Rev. Lett.* **38**, 1283 (1977).
174. T. Sato and H. Okuda, *Phys. Rev. Lett.* **44**, 740 (1980).
175. C. E. Max and C. F. McKee, "Effects of Flow on Density Profiles in Laser-Irradiated Plasmas," *Laser Program Annual Report—1977*, Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-77 (1978), p. 4-55.

Anomalous DC Resistivity Due to Ion Turbulence 3-63

176. *Laser Program Annual Report—1979*, Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-79 (1980), p. 3-64; C. L. Yee, *Electron Energy Transport and Anomalous DC Resistivity*, Ph.D. Dissertation, PRG-R-46 (unpublished), University of California, Davis, Calif. (1980); C. L. Yee and J. S. DeGroot, *Electron Energy Transport Inhibition Due to Anomalous DC Resistivity*, University of California, Davis, Calif., PRG-R-49 (1980) (to be submitted to *Phys. Rev. Lett.*).
177. H. deKluiver, *Current Driven Turbulence in Plasmas*, FOM—Instituut voor Plasmafysica, Rijnhuizen, Jutphaas, The Netherlands, 77-106 (unpublished).
178. R. Z. Sagdeev, *Magneto-Fluid and Plasma Dynamics* (American Physical Society, Providence, R.I., 1969), p. 281.
179. B. B. Kadomtsev, *Plasma Turbulence* (Academic Press, New York, 1965), p. 71.
180. A. Hirose, I. Alexeff, W. D. Jones, S. T. Kush, and K. E. Lonngren, "Anomalous Resistivity in a Steady State Current-Carrying Discharge Tube Plasma," *Phys. Rev. Lett.* **25**, 1563 (1970); Y. Kawai, M. Hasegawa, and H. Nakashima, "Observation of Anomalous Electric Conductivity in a Current Carrying Discharge Tube Plasma," *J. Phys. Soc. Japan* **38**, 1227 (1975); Y. Kawai, Ch. Hollenstein, and M. Guyot, "Ion Acoustic Turbulence in a Large Volume Plasma," *Phys. Fluids* **21**, 970 (1978); Ch. Hollenstein, M. Guyot, and E. S. Weibel, "Stationary Potential Jumps in a Plasma," *Phys. Rev. Lett.* **45**, 2110 (1980).
181. K. Mizuno, R. B. Spielman, J. S. DeGroot, and W. M. Bollen, *Electron Heating Due to Resonant Absorption*, University of California, Davis, Calif., PRG-R-44 (1980) and *Proc. Joint Conf. 4th Kiev Intern. Plasma Theory and 4th Intern. Congress Waves and Instabilities in Plasmas* (Nagoya, Japan, April 7, 1980), p. 306; W. M. Bollen and J. S. DeGroot, *Current Driven Ion Acoustic Turbulence*, University of California, Davis, Calif., PRG-R-50 (1980) (submitted to *Phys. Fluids*).
182. S. M. Hamberger, J. Jancarik, L. E. Sharp, and D. A. Aldcroft, "Experiments on Plasma Heating by the Dissipation of Current Driven Turbulence," in Vol II, *Proc. 4th Int. Conf. Plasma Phys. Contr. Nucl. Fusion Res.* (Madison, Wis. 1971), p. 37; Y. Kawai, Ch. Hollenstein, and M. Guyot, "Ion Acoustic Turbulence in a Large Volume Plasma," *Phys. Fluids* **21**, 970 (1978).
183. D. Biskamp and R. Chodura, "Computer Simulation of Anomalous dc Resistivity," *Phys. Rev. Lett.* **27**, 1553 (1971); D. Biskamp, K. U. Von Hagenow, and H. Welter, "Computer Studies of Current Driven Ion Sound Turbulence in Three Dimensions," *Phys. Lett.* **39A**, 351 (1972); J. Orens and J. M. Dawson, *Anomalous DC Plasma Resistivity Due to Ion Acoustic Turbulence*, Naval Research Laboratory, Washington, D. C., Report 2850 (1974) (unpublished).
184. W. Horton, Jr., D. Choi, and R. A. Koch, "Scaling Laws and Asymptotic States for Ion Acoustic Turbulence," *Phys. Fluids* **22**, 797 (1979); W. Horton, Jr., and D. Choi, *Phys. Rep.* **49**, 273 (1979).
185. J. S. DeGroot, C. Barnes, and W. Woo, "Anomalous DC Resistivity at Low Drift Velocities," *Bull. Am. Phys. Soc.* **25**, 985 (1980).

186. K. Nishikawa, *J. Phys. Soc. Japan* **24**, 916 and 1152 (1968).
187. W. Woo, P. Rambo, H. Wang, and J. S. DeGroot, "Electron Heating and Transport Inhibition Due to Parametrically Excited Ion Turbulence," *Bull. Am. Phys. Soc.* **25**, 909 (1980).
188. W. Woo, J. S. DeGroot, and C. Barnes, "Rippling of the Critical Surface by Four-Wave Processes in a Laser-Irradiated Plasma," *Phys. Fluids* **23**, 2291 (1980); K. Lee, D. W. Forslund, J. M. Kindel, and E. L. Lindman, "Theoretical Derivation of Laser Induced Plasma Profiles," *Phys. Fluids* **20**, 51 (1977).
189. J. J. Thomson, R. J. Faehl, W. L. Kruer, and S. Bodner, "Electron Heating Due to Parametric Instability Turbulence," *Phys. Fluids* **17**, 973 (1974).
190. K. Mizuno, R. B. Spielman, J. S. DeGroot, and W. M. Bollen, *Electron Heating Due to Resonant Absorption*, University of California, Davis, Calif., PRG-R-44 (1980), and *Proc. Joint Conf. 4th Kiev Intern. Plasma Theory and 4th Intern. Congress Waves and Instabilities in Plasmas* (Nagoya, Japan, April 7, 1980), p. 306.
191. D. A. Rasmussen, K. Mizuno, and J. S. DeGroot, "Profile Modification and Hot Electron Production Due to the Absorption of a Focused Beam of Very High Power Microwaves," *Bull. Am. Phys. Soc.* **25**, 909 (1980).
192. J. S. DeGroot, W. L. Kruer, and W. Woo, *Simplified Theory of Resonant Absorption*, University of California, Davis, Calif., PRG-R-48 (to be published) (to be submitted to *Phys. Fluids*).
193. K. Nishikawa, *J. Phys. Soc. Japan* **24**, 916 and 1152 (1968).
194. K. Mizuno, F. Kehl, R. A. James, J. S. DeGroot, and W. Woo, "Electron Heating and Heat Transport Due to Resonant Absorption and Parametric Instabilities," *Bull. Am. Phys. Soc.* **25**, 909 (1980).
195. C. Randall and J. S. DeGroot, "Effect of Crater Formation on the Absorption of Laser Light," *Phys. Rev. Lett.* **42**, 179 (1979).
196. W. L. Kruer, "Wavebreaking Amplitudes in Warm, Inhomogeneous Plasmas," *Phys. Fluids* **22**, 1113 (1979).
197. K. G. Estabrook and W. L. Kruer, "Properties of Resonantly Heated Electron Distributions," *Phys. Rev. Lett.* **40**, 42 (1978).
198. C. P. DeNeef and J. S. DeGroot, "Electron Acceleration by a Localized Electric Field," *Phys. Fluids* **20**, 1074 (1977).
199. J. R. Albritton and A. B. Langdon, "Profile Modification and Hot Electron Production from Resonant Absorption," *Phys. Rev. Lett.* **45**, 1794 (1980).
200. D. W. Forslund, J. M. Kindel, and K. Lee, "Theory of Hot Electron Spectra at High Laser Intensity," *Phys. Rev. Lett.* **39**, 284 (1977).
201. G. B. Zimmerman, *Numerical Simulation of the High Density Approach to Laser Fusion*, Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-74811 (1973).
202. G. B. Zimmerman and W. L. Kruer, *Comm. Plasma Phys. Cont. Thermonuclear Fusion* **2**, 85 (1975).
203. W. Schultz, *Methods in Computational Physics*, Vol. 3 (Academic Press, New York, 1970), p. 1.
204. F. W. Harlow and A. A. Amsden, *J. Comp. Phys.* **16**, 1 (1974).
205. *Laser Program Annual Report—1974*, Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-74 (1975), p. 368.
206. K. G. Estabrook and J. A. Harte, *On Reducing Brillouin Scatter*, Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-82620, Rev. 2 (1979).
207. *Laser Program Annual Report—1978*, Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-78 (1979), p. 3-31.
208. *Laser Program Annual Report—1979*, Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-79 (1980), p. 3-72.
209. J. A. Harte and G. B. Zimmerman, *Ponderomotive Force in a Hydrodynamic Simulation Code*, Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-79860 (1977).
210. D. S. Kershaw, *Interaction of Relativistic Electron Beams with High-Z Plasmas*, Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-77047 (1975).
211. D. S. Kershaw, *Computer Simulation of Superthermal Transport for Laser Fusion*, Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-83494 (1979).
212. W. A. Lokke and W. H. Grasberger, *XSNQ-U: A Non-LTE Emission and Absorption Coefficient Subroutine*, Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-52276 (1977).
213. G. B. Zimmerman and R. M. More, "Pressure Ionization in Laser-Fusion Target Simulation," *J. Quant. Spectroscopy Radiat. Transfer* **23**, 517 (1979).
214. J. Chang and G. Cooper, *J. Comp. Phys.* **6**, 1 (1970).
215. D. S. Kershaw, *Flux Limiting on Nature's Own Way*, Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-78378 (1976).
216. E. G. Corman, W. E. Loewe, G. E. Cooper, and A. M. Winslow, *Nucl. Fusion* **15**, 377 (1975).
217. *Laser Program Annual Report—1979*, Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-79 (1980), p. 3-76.
218. S. Braginskii, *Reviews of Plasma Physics*, Vol. 1 (Consultants Bureau, New York, 1965), p. 205.

Absorption, Electron Heating, and Electron-Energy Transport Inhibition Due to Ion Turbulence
3-65

Absorption, Electron Heating, and Electron-Energy Transport in Microwave Simulations of P-Polarized Laser Light-Plasma Interactions
3-67

The LASNEX Computer Code—An Overview
3-71

References

The LASNEX Computer Code—An Overview (cont.)	219. D. S. Kershaw, <i>Differencing of the Diffusion Equation in Lagrangian Hydrodynamics Codes</i>, Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-82747 (1980) (to be published in <i>J. Comp. Phys.</i>). 220. D. S. Kershaw, "The ICCG Method for the Iterative Solution of Systems of Linear Equations," <i>J. Comp. Phys.</i> 26, 43 (1978).	221. G. J. Myers, <i>Software Reliability Principles and Practices</i> (John Wiley & Sons, New York, 1976). 222. E. Yourdon and L. L. Constantine, <i>Structured Design: Fundamentals of a Discipline of Computer Program and Systems Design</i> (Prentice-Hall, Englewood Cliffs, N.J., 1979). 223. J. R. Kohn, in <i>Proc. 20th IEEE Computer Society Int. Conf.</i> (San Francisco, Calif., February 25–28, 1980), pp. 73–76.
Dynamic Memory Management for LASNEX 3-74	224. D. E. Knuth, <i>The Art of Computer Programming</i>, Vol. 1 (Addison-Wesley Publishing Company, Reading, Mass. 1973).	225. D. E. Knuth, <i>The Art of Computer Programming</i>, Vol. 3 (Addison-Wesley Publishing Company, Reading, Mass. 1973).
Computer Simulation of Suprathermal Transport for Laser Fusion 3-78	226. D. S. Kershaw, <i>Interaction of Relativistic Electron Beams with High-Z Plasmas</i>, Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-77047 (1975).	227. W. Heitler, <i>The Quantum Theory of Radiation</i> (Oxford University Press, 1954), pp. 245–254. 228. J. S. Chang and G. Cooper, "A Practical Difference Scheme for Fokker-Planck Equations," <i>J. Comp. Phys.</i> 6, 1 (1970).
Pressure Ionization 3-83	229. A. Unsold, <i>Z. Astrophys.</i> 24, 355 (1948). 230. D. Burgess, Culham Laboratory, Abingdon, UK, unpublished report CLM-P 567 (1978). 231. N. J. Peacock, Culham Laboratory, Abingdon, UK, unpublished report CLM-P 519 (1977). 232. G. Zimmerman and R. More, <i>J. Quant. Spectrosc. Radiat. Transfer</i> 23, 517 (1980). 233. S. Brush and B. Armstrong, JILA Report 79, in <i>Proc. Workshop Conf. Lowering Ionization Pot.</i> (University of Colorado, Boulder, Colo., 1965). 234. J. Weisheit and B. Shore, <i>Astrophys. J.</i> 194, 519 (1974).	235. A. Vinogradov, I. Sobelman, and E. Yukov, <i>Sov. J. Quant. Electron.</i> 4, 149 (1974). 236. F. J. Rogers, H. Graboske, and H. DeWitt, <i>Physics Lett.</i> 34A, 127 (1971). 237. E. Fermi, <i>Nuovo Cimento</i> 11, 157 (1934); A. Abrikosov, L. Gorkov, and I. Dzialoshinski, <i>Methods of Quantum Field Theory in Statistical Physics</i> (Prentice-Hall, Englewood Cliffs, N.J., 1963). 238. H. Griem, <i>Plasma Spectroscopy</i> (McGraw-Hill, New York, 1964). 239. T. Nakayama and H. DeWitt, <i>J. Quant. Spectrosc. Radiat. Transfer</i> 4, 623 (1964).
Two-Temperature Equation of State for Dense Plasmas 3-85	240. R. M. More, <i>Two-Temperature Equation of State for Dense Plasmas</i>, Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-84379 (unpublished preprint) (1980).	241. E. Salpeter, <i>J. Geophys. Res.</i> 68, 1321 (1963). 242. E. Ecker and W. Kroll, <i>Z. Naturforschung</i> 19a, 1447 (1964).
Semiclassical Atoms in Dense Plasmas 3-86	243. A. Sommerfeld, <i>Atomic Structure and Spectral Lines</i> (Methuen and Co., London, 1934). 244. J. Slater, <i>Quantum Theory of Matter</i> (McGraw-Hill, New York, 1951). 245. D. Liberman, <i>Phys. Rev.</i> B20, 4981 (1979). 246. W. A. Lokke and W. Grasberger, Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-52276 (1977).	247. G. Zimmerman and R. More, <i>J. Quant. Spectrosc. Radiat. Transfer</i> 23, 517 (1980). 248. H. Mayer, unpublished report LA-647, Los Alamos National Laboratory (1947). 249. Dr. J. Scofield, unpublished.

Section 4 Target Fabrication

Target Fabrication

Contents

Introduction	4-1
Glass-Sphere Development and Production	4-3
Introduction	4-3
New High-Temperature Furnace	4-3
Production of Large Glass Spheres	4-4
Metal Sphere Development	4-4
Diagnostic Gas Fills	4-6
D-T Fill Techniques	4-7
Liquid-Droplet and Dried-Gel Production Systems	4-8
Coatings and Layers	4-9
Introduction	4-9
Molecular Beam Levitation Development	4-10
Polymer Coatings	4-12
Metal-Seeded Organic Coating	4-16
Charged-Particle Coating and Milling	4-18
Copper-Coated Shells	4-20
Batch Coating Process for Microspheres	4-23
MBL Coating of Soft Metals on Microspheres	4-26
Advances in Beryllium Coatings	4-28
Double-Shell Technology	4-29
Introduction	4-29
Micromachining of Sputter-Coated Beryllium	4-29
Step-Jointed Hemishells	4-31
Lead Styrene Hemishells	4-33
Characterization and Analysis	4-34
Introduction	4-34
Molecular-Beam-Levitated Coating of Second Shells	4-34
Microradiography	4-36
Interferometric Sphere-Mapping System	4-39
Production Improvements	4-40
Microtopography	4-43
Microsectioning	4-47
Cryogenic Systems Development	4-50
Introduction	4-50
Solid Hydrogen Granules	4-50
Formation of Condensed Fuel Layers	4-51
Cryogenic Target Systems	4-58
Mechanical Survivability of Targets in a Cryogenic Environment	4-60
Target Factory Studies	4-60
Target Production	4-61
Tritium System	4-62

Fusion Target Development Facility (FTDF)	4-63
Facility Planning	4-63
Tritium Handling	4-65

References	4-69
-----------------------------	-------------

Target Fabrication

Introduction

“Target fabrication” is a collective term encompassing the exploration and application of new and old science and technology for the purpose of constructing the many kinds of laser fusion targets that are required, e.g., Fig. 4-1. The disciplines involved include physics, chemistry, materials science, mechanical technology, cryogenics, and electronics. The targets may be flat disks made of a single material (gold, nickel, copper, etc.) or of layers of different materials, or they may be simple or multilayered spherical shells of glass, organic polymers, and other materials. The spherical shell targets may contain various gases such as bromine, argon, deuterium, tritium, and traces of several others, and they may be either at room temperature or cold enough that the gases they contain are liquid or solid.

To diagnose the behavior of a target when it is irradiated by a laser, we must provide angular and spatial isolation of the diagnostic lines of sight between the target and the observing instruments. This is done with shields, which are made in a variety of flat, curved, and angular shapes to fit the particular requirements of the experiment. For example, if the diagnostic apparatus must simply view an isolated region of a target, a flat shield with an observation hole interposed between the target and the diagnostic apparatus may be sufficient. On the other hand, more complex requirements such as separation of lines of sight and isolation of two regions of observation of a target's implosion may call for a complicated shield or shields with several convolutions and suitably located observation ports or holes. These shields are very small—a few hundred

Introduction

micrometres to several millimetres in size. Micromachining techniques must be used to make many of the parts, and we have also borrowed techniques from integrated circuit technology.

Our primary tasks are (1) to produce the targets needed for current experiments, and (2) to explore and develop the technology needed to produce targets of the future—for experiments with the Novette and Nova lasers and other drivers, and for the high-energy, high-repetition-rate systems envisioned for laser-fusion power plants. Thus, much of our work is not specific to any particular target configuration or material, but must include research and development of materials and techniques versatile enough to be applicable to targets that have not yet been designed.

Our resources and efforts are in large part directed toward unclassified target-fabrication technology. For example, of the nearly 1100 targets constructed and delivered in 1980 for use in our current experimental programs, 1020 were unclassified and only 170 were classified.

In the following sections of this report we describe much of our scientific and technological development work. This includes developments and achievements that are applicable to a wide variety of targets and to the related micro-technology in general. The relatively smaller portion of our work that is only applicable to radiation-driven targets will be reported under separate cover in the classified portion of this annual report.

The areas in which the major part of our work is done include:

- Hollow-sphere development and production.
- Coating and layering research and application.
- Cryogenics.
- Characterization and material analysis.
- D-T fuel fill.

Of no less importance for the future, although now representing smaller efforts, are studies of reactor targets and high-production systems for producing them (i.e., target factories).

There have been many accomplishments in 1980, the highlights of which are discussed in detail in the following sections. These include:

- Production of large glass spheres (diameter greater than 0.5 mm).
- Filling of glass shells with diagnostic gases such as bromine.
- Producing high-Z coatings on spheres (i.e., coating them with a matrix material seeded with another, high-Z material).
- Development of high-quality microradiography and computerized image analyses.
- Development and production use of coating processes in which the microsphere is supported by molecular beam levitation (Fig. 4-1).
- Production of mating, edge-stepped hemishells.
- Assembly of double-shell targets.

Of course, one of our greatest accomplishments has been the production of the targets needed for the day-to-day experiments with both the Argus and Shiva laser systems.

Author: C. D. Hendricks

Glass-Sphere Development and Production

Introduction

During the year we have continued to provide target-quality glass microspheres to meet the needs of the target experiments program as well as Target Fabrication's own internal needs for research and development within the group. We have expanded the capability of the dried gel method so that it now can produce very large spheres as well as a more concentric product. A new high-temperature furnace has been designed and built, and a new method for handling the microspheres for the D-T fuel filling operation has been developed. We have continued to provide diagnostic gas fills and to improve the process for adding bromine to the glass spheres. Finally, late in the year we began two experiments to study the fabrication of metal spheres. These advances are discussed in more detail in the articles that follow.

Author: R. L. Morrison

New High-Temperature Furnace

The production of glass microspheres in batches in which approximately 90% of the spheres are concentric to stringent target specifications requires that the viscosity of the glass be as low as possible. To obtain a low viscosity, the glass furnace must be capable of at least a 1500°C continuous operating temperature. The commercially available furnaces we have used for the past two years are capable of continuous operation at 1500°C, but at the price of extremely high operating and maintenance costs. The cost of labor and replacement parts for these furnaces has amounted to over 25% of the total resources of the glass technology group. To eliminate this drain on resources we have designed, developed, and are using a new high-temperature furnace (Fig. 4-2) that is capable of operating at 1500°C continuously and to 1600°C for short periods. The new design eliminates the use of both firebrick and silicon-carbide heating elements. We replaced the firebrick with the latest, state-of-the-art materials—low-density alumina ceramics—and we replaced the silicon-carbide heating elements with a newly designed platinum, 40%-rhodium element embedded in an alumina rod.

Fig. 4-2. New high-temperature furnace with improved heating elements produces glass microspheres of better quality at lower cost than previous furnaces.

Figure 4-2 is a general view of our new high-temperature furnace. The design of the heating element rods is the critical feature making the furnace a low-maintenance unit. Each rod is composed of a ceramic tube containing two full-length small holes into which the platinum-rhodium furnace wire is inserted. The holes are sized so that the furnace wire fits snugly. After the wire is inserted, the elements are heated to 1500°C for several hours, allowing the wire to fuse to the ceramic and crystallize. With the platinum fused to the wall of the strong and ridged ceramic tube, electrical continuity is maintained where ordinarily the wire would break due to crystallization and embrittlement.

There have been several benefits from the new furnace design. Power consumption has been reduced to one-quarter that of the old style furnace, as a result of the energy-efficient design and the excellent insulating quality of the low density ceramic. At this writing, maintenance has been nil. The furnaces are very light and inexpensive to mount.

Author: R. L. Morrison

Major Contributor: R. K. Stump

Production of Large Glass Spheres

Some of our capsule designs require larger fuel containers than those 70 to 300 μm in diameter that we have used for the past

several years. Predictions have been made that the larger glass spherical shells will deform under the "free-fall" production technique that is used in our vertical high-temperature furnaces.¹ We established a goal for 1980 to investigate this prediction as well as to check the overall state of the art for producing large glass spheres more than 600 μm in diameter.

For a furnace of a given height and temperature with atmospheric air, there is a maximum amount of glass precursor material that can be melted, refined into glass, and blown into a microsphere in the short time it is in the furnace. The heat capacity of the microsphere precursor determines this limit. The 8-ft-high, 1500°C furnace we currently use for producing the larger spheres will melt and refine enough glass to produce spheres approximately 700 to 800 μm in diameter, with wall thickness approximately 3 to 4 μm , in an air atmosphere.

We have been able to increase the size of spheres produced in this same equipment as a result of investigating the mechanism of heat transfer to the microspheres.² We have demonstrated that the heat is transferred virtually 100% by thermal conductivity. By substituting He (which has a higher thermal conductivity) for air in our furnaces, we have been able to produce spheres as large as 1.7 mm in diameter. These spheres meet target specifications for sphericity. In other words, for spheres as large as 1.7 mm, we have found no sign of deformation. Figure 4-3 shows 1.3-mm spheres which are spherical to within strict target specifications.

We have set another goal: to produce spheres 3 mm in diameter. To accomplish this goal we will use an 1800°C furnace which will be designed to operate at above atmospheric pressure as well as at reduced pressure. With this facility we expect to be able to make satisfactory 3-mm spheres.

Author: R. L. Morrison

Metal Sphere Development

Some target designs require the use of metal fuel capsules, as well as metal hemishells that can be assembled into outer shells. Late in the year we began to investigate the fabrication of these metal shells. We are

Fig. 4-3. Large glass microspheres (1.3 mm in diameter, with walls 6 to 8 μm thick), meeting strict target specifications, were produced by replacing furnace air with helium.

performing two types of experiments: in one we are trying to make metal spheres with the liquid droplet systems³ currently used for producing glass spheres (Figs. 4-4 and 4-5); in the other, we are blowing the metal spheres individually (Figs. 4-6 and 4-7).

The initial experiments, using the liquid droplet technique, were done with solutions of silver nitrate and other metal nitrates. Silver nitrate has shown the most promising results so far. We began by preparing a water solution of silver nitrate. The liquid drops blow and dry to a melted shell of silver nitrate salt (silver nitrate melts at 212°C). Figure 4-4 is a photograph of such a shell. The silver nitrate begins to decompose to nitrogen dioxide and silver oxide (silver nitrate decomposes at 444°C). The silver oxide decomposes immediately because its decomposition temperature is 300°C. These initial processes take place in the drying and transition section of the drop tower, before the droplets reach the high temperature furnace. When all the silver nitrate has decomposed there is a very fragile shell of silver particles remaining, which melt and flow together into a metal shell as the melting point of 961°C is exceeded in the high temperature furnace. Figure 4-5 is an optical photomicrograph of some crude silver spheres made in this way. We have had difficulty controlling the process so far. The shells tend to burst, leaving metal spheres that are almost entirely solid. One of our goals is to study and learn to control this

process, as we have learned to control the process for blowing glass shells, and to find a blowing agent for the metal spheres.

Fig. 4-4. Optical photomicrograph of spheres of silver nitrate salt produced in an early stage of the liquid droplet process, collected before they entered the high-temperature decomposition and melting zone of the furnace.

Fig. 4-5. Optical photomicrograph ▲ of the first crude silver spheres made by the liquid droplet process.

Fig. 4-6. Optical photomicrograph of individually blown melted gold sphere ▼ with quartz blowing probe inserted.

We have also produced spheres from copper and nickel nitrates, but with these materials we need a hydrogen furnace atmosphere in order to eliminate oxide formation. To handle this atmosphere safely we must modify the furnace; so further experiments with these materials will probably be postponed in favor of the more highly desired gold spheres. Gold chloride and gold bromide also form concentrated water solutions which should be adaptable to this process.

In the second series of experiments we melt individual pieces of gold and blow them into spheres using argon and a 10- μ m-diameter quartz capillary. We melt the gold inside a polished hemispherical depression located at the center of a graphite resistance-heating element ($1/4 \times 1/32 \times 1-1/4$ in.). Using a micromanipulator, we position the quartz capillary, which easily punctures the melted gold. Figure 4-6 is a photomicrograph of a melted gold sphere with the quartz blowing probe inserted into it. Viewing the operation with a stereo-microscope, we blow the shells to the desired size, then turn off the heat and remove the capillary. Figure 4-7 shows a general view of the apparatus. The entire operation is performed in an argon atmosphere to insure cleanliness and to prevent the heating element from burning.

When the gold melts, it does not wet the graphite heating element, and therefore it forms into a sphere. The high alternating

current in the graphite causes the sphere to spin about its vertical axis. This spinning force provides the bubble centering force necessary to produce a concentric shell. If the shells produced by this method are not concentric to within target specifications, or if they possess surface flaws, we may be able to improve them by heating them to just below the melting temperature in a graphite heating element at the top of a furnace and then allowing them to free-fall in an atmosphere of hydrogen and helium at reduced pressure (the low pressure prevents shell distortion due to drag). We will continue to work on this process for making gold shells in the coming year.

Author: R. L. Morrison

Diagnostic Gas Fills

Various diagnostic schemes for determining fuel ρr measurements have required the addition of special gases to fusion target microspheres. X-ray line imaging has been used to measure the broadening of lines emitted from an argon seed gas.⁴ Argon seed gas has also been proposed for a neutron activation scheme, but direct measurements of fuel ρr by this method would require neutron yields approximately 100 times those currently available. Present neutron yields are sufficient, however, for a neutron activation scheme utilizing bromine gas doping of the D-T fuel in target spheres.⁵

Last year we began a series of experiments leading to the development of a method for introducing bromine into glass microspheres.⁶ For the proposed diagnostic scheme to work, most of the bromine must be in the gas phase inside the target sphere (less than 10% of the total bromine can be in the glass of the shell). We have produced spheres with less than 10% of the total bromine in the glass of the shell,⁷ but we have had difficulty in determining the proportions of bromine and hydrogen bromide inside the spheres. If significant quantities of bromine gas survive the fuel fill, then liquid bromine (boiling point 59°C) may condense on the inside surface of the fuel capsule at room temperature and render the neutron-activation diagnostic scheme for fuel ρr inaccurate.

Fig. 4-7. Apparatus for individually blowing metal microspheres.

Analytical techniques are not available to determine nondestructively the relative amounts of bromine and hydrogen bromide in a target capsule. Therefore, late this year we began a series of experiments to introduce hydrogen bromide rather than bromine into the fuel capsules. Since HBr boils at -67°C , all the bromine atoms, present as HBr, will be in the gas phase. As long as HBr is the only bromine-containing species present, we have the analytical techniques to detect it, mainly by neutron activation and x-ray fluorescence. The ability to confirm that a target contains HBr mixed with the fuel makes it practicable to measure the fuel ρ by neutron activation of Br.

Author: R. L. Morrison

D-T Fill Techniques

Maintaining cleanliness of the target capsules before, during, and after the D-T filling procedure⁸ is a problem of varying magnitude depending upon the atmospheric conditions and the operator's handling techniques. Atmospheric conditions can be very troublesome, especially on days of low humidity, when the target spheres and their containers develop static electric charges. The charged spheres are susceptible to picking up dust and dirt from the atmosphere and from surface contact during transfer. We use careful handling techniques and laminar flow benches to minimize contamination, but we inevitably contaminate the spheres to some degree each time they are exposed to the atmosphere.

The beryllium fill tubes⁹ into which the spheres are placed to be filled with D-T are another source of contamination, because they collect glass shards from previous batches of spheres. The fill tubes are small, 6 in. long by 0.093 in. in diameter, which makes them difficult to inspect or clean.

Since each batch of target-quality capsules is very expensive, we considered it important to develop an improved technique for handling the capsules during the filling operation. Our approach was to make a small container by wrapping 0.25-mil gold foil around a special mandrel. This container is approximately $3/4$ in. long by 0.083 in. in diameter, with a flared top which acts as a

funnel. We place the gold foil container in a hole in an aluminum block, to secure it while it is being filled with target capsules. Above the block containing the gold foil container is another aluminum block held in position by guideposts at the corners. A glass funnel is cemented into a depression machined in the center of the upper block. The inside surface of the glass funnel has a sputtered coating of chromium in contact with the aluminum block by means of a strip of silver paint, thus providing a ground for any static charge. We fill the gold foil container by pouring the spheres into the funnel. Then we remove the upper block and funnel, and close the gold foil container by pinching the top with needle-nose tweezers. We enclose the gold foil containers in numbered transport containers for delivery to the fill facility. Figures 4-8 and 4-9 show

Fig. 4-8. Assembled apparatus for loading the microspheres into the gold foil containers.

Fig. 4-9. Disassembled apparatus for loading microsphere fuel capsules into gold foil containers to keep them clean during the D-T fill operation; in foreground is mandrel for shaping the gold foil containers.

the apparatus assembled and disassembled. At the fill facility the gold foil containers are removed from the transport containers and placed in the beryllium fill tubes. After being filled with D-T they are put back into the transport containers and returned to the target area, where they are opened with needle-nose tweezers and put into appropriate containers for inspection. This technique has proved effective in protecting the target capsules from contamination during the filling operation.

Author: R. L. Morrison

Major Contributor: R. K. Stump

Liquid-Droplet and Dried-Gel Production Systems

This past year a great many target-quality spheres have been required for experiments within the target fabrication group. In addition there has been an increased programmatic demand for glass spheres for targets. The 1980 programmatic requirements showed a continued trend for an increasing variety of sphere diameters and aspect ratios.

We are continuing to use the liquid droplet method,¹⁰ which is superior to the dried gel method¹¹ for producing batches of highly concentric spheres.¹² Once concentric spheres are produced in the approximate range of diameter and wall thickness, the diameter distribution can easily be narrowed

by sieve cutting. After sieve cutting we narrow the wall thickness distribution by density cutting,¹³ if the liquids and combinations of liquids are available in the density range of interest. Fortunately, many of the glass spheres currently being requested are in a bulk density range where these liquids are available. The gas density separation techniques for the lighter spheres have not been very successful and therefore are currently not being used.

The dried gel method is potentially very promising for target sphere production. It can produce much larger spheres than can be produced by the liquid droplet method. It can produce a much larger variety of diameters and aspect ratios, and it can produce a much larger quantity of spheres in a given amount of time. However, to be more useful this method requires improvement in overall batch concentricity and either a narrower wall thickness distribution or an improved density separation scheme below a bulk density of 0.6 g/cm^3 .

During 1980 we improved the capability of the dried gel method for producing highly concentric spheres. Previously we were able to produce approximately one concentric sphere in 10. We are now able to produce batches which yield approximately 50% concentric spheres. We improved the yield by introducing water vapor (steam) into the furnace tube, which lowers the viscosity of the glass and consequently improves the concentricity of the spheres. The concentration of water vapor used is approximately 20 vol%.

Glass Shell Study. Stringent surface requirements on our glass microspheres have been a constant source of concern. As discussed in a previous report,¹⁴ the principal problems are devitrification and weathering (the gradual degradation of the glass surface). We have been concentrating our efforts on a better understanding of and solution to the weathering problem.

We use a sodium silicate glass. Our recent data on individual glass shells shows an alkaline content of 10 to 18% Na_2O and 1.5 to 2.5% K_2O . This is consistent with batch averages obtained by wet chemistry methods.

The chemical activity of the Na^+ ions with water in the atmosphere causes weathering. First tiny crystallites appear, which then

Fig. 4-10. Ion-probe depth profile of surface of glass sphere that had been given a regular wash and then stored for five days in dry argon, showing high surface concentration of sodium and potassium.

grow as they convert to hydrates. These attract CO_2 from the air to form carbonates. In a humid atmosphere this chemical action occurs rapidly, rendering the spheres useless in a few days' time.

In order to reduce this rapid deterioration, we routinely wash the spheres sequentially in a solution of 0.5 N HNO_3 and 0.1 N NH_4F at 90°C, distilled water, acetone, and 200-proof ethanol. This procedure is intended to leach out the sodium ions near the surface. The extent of depletion depends on the duration of the wash. Ion-probe depth profiles show that in a typical wash the Na depletion ranges from 0.2 to 0.6 μm . After being washed, the spheres are stored in a dry argon atmosphere.

While this wash procedure gets rid of the weathering products, it does not permanently passivate the glass surface. Figure 4-10 is an ion-probe depth profile of a washed sphere after five days' storage in dry argon. Note that there is a high concentration of sodium and potassium at the surface. This may be residue from the wash process, or it may be the result of subsequent handling; the origin is unclear. It is clear, however, that this alkali-rich zone will initiate more weathering.

An additional factor in the weathering process is the mobility of the Na^+ ion. Due to the concentration gradients across the wall of the glass, Na^+ ions can migrate into the sodium-depleted zones and move toward the surface where Na is being removed by a combination of weathering and leaching. In time the chemical activity of the Na^+ ions with atmospheric water will recommence. Often the glass can be rewashed to restore the smooth surface. Sometimes the surface undergoes too much alteration, and instead of being resurrected the spheres are simply washed to destruction.

There is one unfortunate side-effect of passivating the surface by means of an alkali-leaching process: The diffusion rate of tritium through the glass is increased, as a consequence of decreasing the alkali content of the glass. That is, the D-T will tend to leak away faster through the walls of the sphere. This effect is most marked with thin glass walls, where the Na-depleted zone represents an appreciable fraction of the total wall.

The probability of losing gas through the wall increases at elevated temperatures such

as are incurred during metal sputtering. Possible solutions to these problems lie in changing glass compositions, using different coating processes, or modifying handling and storage techniques. We are working to assess and help implement these alternatives.

Authors: R. L. Morrison and I. M. Moen

Major Contributors: V. F. Draper, C. Chen, S. C. Aceves, K. A. Miller, and J. W. Wittmayer

Coatings and Layers

Introduction

We outlined in our 1979 Annual Report¹⁵ the basic problems facing us in developing and producing coatings and layers. During 1980, we have made significant advances toward solving some of the problems, particularly those related to particulate-induced cone defects on coating surfaces, clumping and sticking together of microspheres during coating, and the microsphere levitation scheme for contact-free coating. We now routinely produce target-quality coatings of fluorocarbon and hydrocarbon polymers as well as several metals: Au, Pt, Cu, and Be. These coatings can be deposited in a batch process, where thousands of microspheres are coated at once, or by means of the molecular beam levitator (MBL), with which a coating can be applied to a single, well-characterized microsphere. Some of the experimental coating methods developed earlier have matured to become our standard coating schemes of the 1980s, most notably the MBL, batch coating, and electroplating methods. As the demand for coatings and layers increases with the complexity of the new targets, particularly the Nova targets, we are continuing to improve our existing technology and develop new coating schemes to meet the new challenges. Metal-seeded organic coating and charged-particle plating are among the concepts discussed in the following articles.

Authors: E. J. Hsieh and W. L. Johnson

Molecular Beam Levitation Development

Molecular beam levitation is a technique for supporting a single, specially selected microsphere on directed beams of argon gas. The gas pressure is low enough that the support force is provided by molecular impact rather than gas dynamic effects. The molecular beams are formed by an array of

microscopic capillaries called a "collimated hole structure." A centering ring deflects some of the gas molecules and gives them horizontal components of momentum, so that they provide a centering force for the microsphere in addition to the vertical support force.

The molecular beam levitator (MBL) has been mated with a plasma polymerization coater to provide high-quality polymer coatings for targets. We reported this work

Fig. 4-11. Block diagram showing the components of the automatic MBL.

Fig. 4-12. Optics for detecting the "glint" on a levitated microsphere.

last year.¹⁶ Further use of the MBL in a fluorocarbon plasma coater is described in "Advances in Beryllium Coatings," and its use in providing seamless second shells is described in "Molecular-Beam-Levitated Coating of Second Shells." The MBL coating technology has been extended to include sputter-deposited metallic coatings. This application depended on overcoming the problems of large electrostatic forces experienced by a microsphere with a conductive coating in a gas discharge. Solutions to these difficulties, as well as results of the MBL sputter process, are discussed in "Advances in Beryllium Coatings."

In this section, we describe development of an automated MBL system that should allow much longer coating runs and thicker deposited layers of several types. Whereas an operator must monitor the present MBL system, continually adjusting the levitation gas flow to compensate for the increasing weight of the microsphere as the coating builds up, the new system will incorporate means for monitoring and controlling the levitation of the microsphere automatically. The automatic levitation system has three parts: the optical portion, consisting of optical transmitter (or illuminator) and receiver; the detection electronics, which provide a dc signal proportional to the height of the levitated microsphere; and the gas flow electronics, which control the levitation gas. The block diagram in Fig. 4-11 shows the components of the automated MBL system.

Figure 4-12 shows the optical portion of the system. We illuminate the microsphere coaxially with respect to the receiver, using a sharply diverging cone of light from a 2-mW He-Ne laser. Coaxial illumination produces a "glint" which appears to come from the center of the microsphere regardless of its position within the illumination field. The levitator reflects much more light than the microsphere, however, so we have taken great pains, using the various apertures and stops shown in Fig. 4-12, to block any light except that reflected from the microsphere. The glint of reflected light from the microsphere is imaged at approximately its actual size on a photodiode detector.

The intensity of the glint will change during the course of a coating run due to the changing reflectivity of the microsphere; thus it is important to derive a signal that is a

linear function of the microsphere height but is independent of the reflected light intensity. We are currently evaluating a lateral-effect photodiode (United Detector Technology, PIN SC/4D) for detecting the glint from the levitated microsphere. This detector produces two current signals, i_1 and i_2 :

$$i_1 \propto I_0 \left(1 + \frac{x}{L} \right), \quad (1)$$

$$i_2 \propto I_0 \left(1 - \frac{x}{L} \right), \quad (2)$$

where I_0 is the total light intensity striking the detector face, L is the width of the detector face, and x is the position of the centroid of light measured with respect to the detector center. A preamplifier converts these current signals into voltages, then feeds them into sum and difference amplifiers. The sum signal,

$$V_{\text{sum}} \propto 2I_0, \quad (3)$$

and difference signal,

$$V_{\text{diff}} \propto 2I_0 \left(\frac{x}{L} \right), \quad (4)$$

are fed into separate, synchronous amplifiers to provide additional signal filtering and amplification. A ratiometer then divides the two signals, giving a ratio that depends only on the relative position of the glint on the detector face (Fig. 4-13):

Fig. 4-13. Ratio signal versus displacement for different incident-light intensities.

$$\frac{V_{\text{diff}}}{V_{\text{sum}}} \propto \frac{x}{L} \quad (5)$$

In Fig. 4-13 we have plotted this ratio, $V_{\text{diff}}/V_{\text{sum}}$, versus displacement, x , for several values of light intensity. The result is linear and independent of intensity over a dynamic range of 90 dB.

The final portion of the automated MBL, namely the gas flow electronics, uses the dc signal, $V_{\text{diff}}/V_{\text{sum}}$, to control the levitation gas. A two-level comparator compares this signal, which is proportional to the position of the levitated microsphere, with an upper and lower reference level. The output of the comparator controls the gas incrementer through a logic section. For example, if the levitated microsphere were too high, $V_{\text{diff}}/V_{\text{sum}}$ would be greater than the upper reference level, and the logic section would send a low-frequency pulse train to the gas incrementer, causing a decrease in gas flow. Conversely, if the microsphere were too low, the gas flow would be increased in a like manner. When the microsphere is within the "window" between the two levels, the clock to the gas incrementer is off. The gas incrementer is a clock-controlled digital potentiometer that replaces the set-point potentiometer in an MKS 170M-48A valve controller. A clock can step the potentiometer either up or down in small, fixed increments, resulting in corresponding incremental changes to the levitator gas flow. The MKS 170M-48A controls a Veeco PV-10 valve which regulates the gas flow,¹⁶ completing the control loop.

The electronics portions of the automatic levitator have all been tested and have performed successfully. We are using the gas-incrementing device on the fluorocarbon coating system described in the next article. Before using the entire automatic levitator in a coating discharge we must solve some remaining problems. For example, in the present design the microsphere levitates inside a centering ring,¹⁶ and as a result we must view it at a 30° angle (see Fig. 4-12). The amount of light reflected in the glint is approximately six orders of magnitude less than the light reflected from the levitator itself. Our present scheme is capable of detecting a 10-nW signal, which is only five orders of magnitude less than the background scattered light. We are pursuing two courses to solve this problem: a more

sensitive detector using an injection laser and avalanche photodiodes; and a new levitation arrangement, without a centering ring, in which the background scattered light will be much less. Both schemes are in preliminary stages of development.

Author: J. K. Crane

Major Contributors: G. R. Cameron, W. L. Johnson, C. W. Jordan, G. R. Korbel, R. M. Krenik, J. A. Monjes, and R. D. Smith

Polymer Coatings

During 1980 we advanced molecular beam levitation from a development project to a production technique which we now use for coating a variety of targets with CF or CH polymers. We also continued our studies of plasma polymerization processes. We were able to identify factors affecting deposition rate, intrinsic stress, and surface smoothness. Using this knowledge, we have expedited production of targets and improved the quality and yield of the coating process. Also during 1980 we built a new plasma coater, development of which proceeded rapidly as a result of our improved understanding of plasma polymerization.

Molecular Beam Levitation and Coating.

Last year we described our efforts at coating microspheres in a contact-free manner by levitating them on molecular beams while coating them in a plasma coater.¹⁷ The ability of the molecular beam levitator (MBL) to support single spheres without contact has enabled us to deposit polymer coatings without the defect growths caused by particles picked up during batch coating. It has further enabled us to improve our technique for processing and coating the outer shell of double-shell targets (see "Molecular-Beam-Levitated Coating of Second Shells" later in this section)¹⁸ and to provide polymer coatings on metal shells, as we discuss below. Finally, with the automatic levitation-gas incrementer ("Molecular Beam Levitation Development"), we are also able to provide thick coatings in long runs with little operator attention.

Figure 4-14 shows a schematic diagram of the current plasma-coating system with its MBL. The microshell is supported a few

micrometres above the capillary array, with the centering ring providing lateral stability.

We can use capillary arrays with 25-, 50-, or 100- μm tube sizes, depending on the target diameter and mass. The stability of a levitated sphere is affected by its size, its weight, and the diameters of the capillaries in the array. In general, small spheres need small capillaries, and more massive shells need larger capillaries. The exact capillary array needed for any specific coating task

must be determined empirically. Typically, for targets 140 μm in diameter with 5- μm walls, we start levitating with an array of 50- μm capillaries and coat for eight hours. The capillaries themselves gradually become coated, reducing levitator gas flow. To coat further we change to a 100- μm capillary array. Following this procedure, with one change of the capillary array, we have deposited coatings as thick as 62 μm on microshells (e.g., Fig. 4-15).

Fig. 4-14. Schematic diagram of the plasma-coating system, showing the molecular beam levitator which supports the microshell.

Fig. 4-15. Fluorocarbon-coated microshell targets coated with a molecular beam levitator. The coating thickness is 16.5 μm .

Fig. 4-16. Defect diameter in plasma polymer coatings on a 140- μm -diameter microsphere as a function of coating thickness, for several sizes (radii) of hemispherical substrate irregularities.

Fig. 4-17. Fluorocarbon coating 62 μm thick deposited on a copper-coated microshell.

To demonstrate the effectiveness of the contact-free coating, in Fig. 4-15 we show fluorocarbon coatings deposited using the MBL. Choosing a microshell with surface irregularities resulted in a defective coating, as shown in Fig. 4-15(a). The coating defect sizes are consistent with predictions based on our defect growth model developed last year,¹⁹ which is summarized in Fig. 4-16. By carefully choosing only the cleanest microshells, we were able to produce coatings with no defects larger than 0.1 μm [Fig. 4-15(b)].

Fig. 4-18. Transmitted-light micrograph made with crossed polarizers shows the uniformity of the fluorocarbon coating on the copper-coated microshell. ►

The MBL coater was especially useful for coating microshells with 15 μm of fluorocarbon over a 3- μm copper diagnostic layer which, being soft, might be damaged in a batch coating process. We use a capillary array and glass centering ring to solve the electrostatic sticking problems reported with metal-coated microshells (see "Molecular Beam Levitation Development"). We deposited coatings up to 62 μm thick on copper-coated microshells with target-quality surfaces. Figure 4-17 shows a copper-coated microshell with an overcoating of 62 μm of fluorocarbon. The coating is broken to permit inspection of the copper-polymer interface. The quality of the sputtered copper layer is important for maintaining a target-quality surface on the plastic layer. Figure 4-18 is a transmitted-light micrograph of the same type of target, illustrating the concentricity of the fluorocarbon.

Coating Technology Improvements. During the year we continued to investigate several of the problems relating to plasma coating: intrinsic stress, coating rate, growth of gas-phase particles, effect of residence time on coating, and growth of coating defects. An understanding of these problems is vital to the production of the highest quality targets, and to the development of an expanding array of materials for future targets.

As we discussed in the 1979 Annual Report,²⁰ intrinsic stress is a persistent

problem in coatings. Intrinsic tensile stress leads to cracking of coatings on microshell targets, causing contamination of the coater environment. Intrinsic compressive stress causes the buckling of coatings, which can explode quartz reaction tubes in the plasma coater. Previously, we have reduced flaking due to intrinsic stress by surrounding the discharge region of the coater with a water-filled jacket.²⁰ We have now found that intrinsic stress can also be fought chemically. Addition of a 7-mTorr partial pressure of nitrogen to the fluorocarbon coater, or addition of at least 80% hydrogen during hydrocarbon coating, eliminates tensile-stress cracking. Together, all of these measures enable us to deposit thick, stress-free coatings on targets.

The low hydrocarbon coating rates and consequent long runs (up to 100 h) have emphasized the need for stability and reliability in the coating apparatus. Process yields could be greatly increased if the coating rate on microshells could be increased from 1 $\mu\text{m}/\text{h}$ to several $\mu\text{m}/\text{h}$. In an effort to increase the deposition rate, we have studied its variation with process conditions. Figure 4-19 shows coating rate

on a flat substrate as a function of discharge power. The rate initially rises as the population of active species increases. Beyond 15 W of power the rate falls because

Fig. 4-19. Deposition rate as a function of power for trans-2-butene at two different hydrogen flow rates (pressure 73 mTorr, trans-2-butene flow rate 0.3 sccm).

Fig. 4-20. Deposition rate as a function of power for trans-2-butene at two different hydrogen pressures (flow rates: hydrogen, 1.9 sccm; trans-2-butene, 0.3 sccm).

Fig. 4-21. The flow rates of both trans-2-butene and hydrogen affect the surface finish of the hydrocarbon coating.

Fig. 4-22. (a) Microshell coated with $17.2\text{ }\mu\text{m}$ of hydrocarbon using the smooth coating conditions of 0.3 sccm trans-2-butene and 10.0 sccm hydrogen. (b) High-magnification examination of the surface reveals no defect larger than $0.1\text{ }\mu\text{m}$.

the flowing stream of organic gas becomes depleted from coating the reaction tube rather than the desired substrate. Thus, the optimum power for rapid coating is 15 W.

We found that the residence time of the coating gas in the plasma reactor also affects coating deposition rate. By increasing the flow rate at constant pressure, we reduce residence time proportionately. Figure 4-19 shows that the reduced residence time (as indicated by an increased hydrogen flow) causes an increase in the coating rate. Again the competition between the walls of the reactor tube and the desired substrate is responsible for this behavior. We can also reduce residence time by reducing pressure while maintaining flow rate. This effect is shown in Fig. 4-20. At lower pressure the gas moves through the reactor more rapidly, giving a higher deposition rate on the desired substrate.

Our residence time studies have also revealed information about gas-phase particle growth. By adjusting the gas composition and residence time, the extent of gas-phase polymerization can be limited. Figure 4-21 (overleaf) shows the effect of trans-2-butene and hydrogen flow rates on surface smoothness (all coatings were deposited at a pressure of 75 mTorr). Increasing the trans-2-butene flow rate produces a rougher surface because of increased particle formation. Increased hydrogen flow improves the surface, especially at the lowest trans-2-butene flow, because of the reduced residence time in the discharge. The lower rate of particle production at a high hydrogen flow rate, 10.0 sccm (standard cubic centimetres per minute), and a low trans-2-butene flow rate, 0.3 sccm, results in a smooth surface, as shown in Fig. 4-22 (at this flow the

maximum coating rate is obtained with 20 W discharge power). It may also be possible to produce smooth coatings at the higher trans-2-butene flows that are necessary for increased coating rates, by employing a larger capacity pump. We are currently investigating this approach.

Author: S. A. Letts

Major Contributors: J. K. Crane, W. L. Johnson, C. W. Jordan, R. M. Krenik, D. J. Lenz, S. E. Mayo, R. D. Smith, and L. A. Witt

Metal-Seeded Organic Coating

Some target designs for Nova call for a metal-seeded organic coating. This layer is to be an organic polymer material containing several atomic percent of a high-Z metal. We currently use an rf helical resonator to deposit hydrocarbon and fluorocarbon coatings on glass microspheres, as discussed in the preceding section, producing coatings of target quality. We have used this same device to produce tungsten coatings²¹ from tungsten fluoride, and to seed the hydrocarbon and fluorocarbon polymers with a variety of volatile materials: nitrogen, oxygen, chlorine, and bromine. Building on these results, we are beginning the development of metal-seeded organic coatings using our current plasma-coating technology.

Figure 4-23 shows those elements which can occur in a volatile form, and which consequently may be suitable for plasma deposition with the helical resonator. We have done some preliminary experiments with lead, in the form of tetraethyl lead.

Using the helical resonator, we have deposited a lead-seeded organic material which is similar in surface finish to our early efforts with hydrocarbon and fluorocarbon coatings ($0.5\text{-}\mu\text{m}$ defects). The x-ray fluorescence analysis of these coatings showed a large lead composition. We will continue our work with tetraethyl lead upon completion of the new coating system described below.

We are building a new coating system (Fig. 4-24), similar to the fluorocarbon and

hydrocarbon coaters,²¹ which has been designed with some features for handling organometallic gases. Many organometallic substances have a low vapor pressure, requiring operation at elevated temperatures; consequently we have chosen all the gas control components to be capable of operating at 100°C . Since many organometallic substances are either toxic, carcinogenic, pyrophoric, or unstable, safety is an important consideration. We have designed the metal-seeded coater system to

H																	He
Li	Be											B	C	N	O	F	Ne
Na	Mg											Al	Si	P	S	Cl	Ar
K	Ca	Sc	Ti	V	Cr	Mn	Fe	Co	Ni	Cu	Zn	Ga	Ge	As	Se	Br	Kr
Rb	Sr	Y	Zr	Nb	Mo	Tc	Ru	Rh	Pd	Ag	Cd	In	Sn	Sb	Te	I	Xe
Cs	Ba	La	Hf	Ta	W	Re	Os	Ir	Pt	Au	Hg	Tl	Pb	Bi	Pa	At	Rn
Fr	Ra	Ac															

U

Fig. 4-23. The elements in the shaded squares (some in pure form, others as compounds) can be applied to targets as organometallic coatings by means of plasma deposition.

Fig. 4-24. Schematic diagram of the new metal-seeded organic coater.

include several levels of containment, as well as protection interlocks. We can collect condensable by-products in two cold traps in series, designed especially to operate with high partial pressures of hydrogen. Material collected in the cold traps can be distilled into a pressure bottle, then removed from the apparatus for disposal. The entire coating system will be contained within a ventilated hood, interlocked to protect both the operator and the equipment. During power failures, an alarm will sound, gas flows will turn off automatically, and all valves will return to the fail-safe position.

To summarize, in 1980 we demonstrated the feasibility of coating metal-seeded organics by producing a lead-containing polymer coating using existing plasma-coating technology. We also designed a new system for coating with a variety of organometallic gases. The new system is in an advanced stage of construction; early in 1981 it will be ready for development of the next generation of laser-fusion target coatings.

Author: S. A. Letts

Major Contributors: M. G. Finley, W. L. Johnson, C. W. Jordan, R. M. Krenik, and S. E. Mayo

Charged-Particle Coating and Milling

We are investigating charged particles, from singly ionized particles to charged clusters or droplets, for use in high-resolution milling or drilling and precisely controlled coating operations. Liquid-metal ion sources are capable of providing either single-atom ions or charged droplets, depending upon certain operating parameters such as current, vapor pressure, and liquid-metal feed. In these devices, a low-vapor-pressure liquid metal such as Au, Ga, or Bi is made to flow around a sharpened tungsten needle (tip radius 1 to 10 μm). We bias this needle positively, at ~ 10 kV with respect to an extractor

electrode (see Fig. 4-25), resulting in the emission of charged particles from the coated tip. In an ion-producing mode, with ions accelerated to 60 keV or greater, this source can be a high-resolution milling tool.²² By decelerating the ions to a few volts, or by operating in a charged-droplet-producing mode, this liquid-metal source may be capable of generating coatings.²³

Our approach to this preliminary investigation is twofold: we are conducting ion milling experiments, using a system at Hughes Research in Malibu,²² to determine if such a device would be useful for target fabrication; and in our own laboratory we are investigating the liquid-metal ion source, to determine the operating conditions for generating ions or charged droplets and depositing them to form rudimentary metal coatings on biased substrates.

Ion Milling. Advanced target designs require fuel containers that are relatively thick (~ 10 to $50 \mu\text{m}$) and filled with 100 atmospheres of D-T mixed with various diagnostic gases. Using the ion milling technique, it may be possible to drill a small hole (0.1 to $0.5 \mu\text{m}$ in diameter) through the fuel container wall, fill the container under high pressure, then plug the hole by melting the surrounding region. This scheme requires a capability for drilling holes of very high aspect ratio (for example, hole depth up to 100 times hole diameter) in high-Z metals, a feat not possible using laser or e-beam drilling.

Seliger,²² at Hughes Research Laboratory in Malibu, has developed a Ga liquid-metal source and ion optics capable of drilling, or

Fig. 4-25. Diagram of a liquid-metal ion source.

more accurately sputtering, holes $\sim 0.1 \mu\text{m}$ in diameter in virtually any material with the focused 60-keV ion beam. Last year we conducted experiments on the Hughes ion column to evaluate its ability to drill high-aspect-ratio holes. Figure 4-26 shows a drawing of the ion beam column. The gallium ion source is imaged by a single-gap accelerating lens. An electrostatic deflector enables the focused beam to be scanned orthogonally across the target. This system has been capable of sputtering lines and holes in thin films as narrow as 38 nm. In Fig. 4-27 we show a gold foil that has been scribed and drilled with this high-resolution ion source. We are currently evaluating drilling and milling rate data to determine if the time required to perform these operations is acceptable.

Charged Particle Coating. We have produced rudimentary gold coatings using a charged-droplet source developed in our laboratory. This source emits different-sized charged particles, ranging from Au^+ and Au^{++} ions to charged clusters ($\sim 0.1 \mu\text{m}$ in diameter). The broad distribution of charge-to-mass ratios for these different particles produces a corresponding distribution of arrival energies for the coating species. Figure 4-28 shows a coating of gold in which the presence of droplets is clearly

distinguishable. By changing the bias of the coating substrate to increase the arrival energy of the coating flux, we obtain a denser, more uniform coating as shown in Fig. 4-28(b). This coating is $2 \mu\text{m}$ thick and has a surface finish of $0.1 \mu\text{m}$. Improvement

Fig. 4-26. Schematic of the 57-kV gallium scanning ion probe.

Fig. 4-27. Sample of slots and holes cut in gold foil with the Hughes ion-milling technique (Ref. 22).

Fig. 4-28. Gold coating from droplets: (a) low incident energy produces discrete particles, (b) high incident energy produces dense material.

of the source to provide a narrower cluster-size distribution should result in better surfaces. If this technology can be developed, we will have a simple, easy-to-control process that may provide the capability for producing advanced coatings.

Authors: W. L. Johnson and J. K. Crane

Major Contributors: W. E. Elsholz, D. J. Lenz, and B. Seliger and G. Stevens (both of Hughes Research)

Copper-Coated Shells

We have used electroplating to produce copper coatings on glass microspheres. Copper is of particular interest as a diagnostic layer for use in making neutron activation *pr* measurements, and it is difficult to deposit by other methods such as sputter coating (see "MBL Coating of Soft Metals on Microspheres").

We modified the vibrating-cathode and tapered-cathode cells,²⁴ which showed promise in applying gold plating to glass microspheres, to adapt them for use in copper plating. With the modified cells, and with changes in operating parameters and solution composition, we succeeded in plating copper on Pt-struck glass microspheres filled with D-T, for use as diagnostic targets. The following discussion describes the modifications we made, the results achieved, and the remaining obstacles to volume production of high-quality electroplated targets.

The 150-nm-thick sputtered Pt strike coating on the glass, which had provided a satisfactory substrate for gold plating, was

found to be very difficult to use as a strike for copper coating.²⁴ Since the Pt adhered poorly to the glass, stress in the electroplated copper often pulled the Pt away from the microsphere surface, causing voids and extreme surface roughness in the copper coating. We found a way around this difficulty by using preplating and changes in the solution composition to reduce stress in the copper coating, so that the Pt strike performed satisfactorily. We discovered that copper plating at currents a factor of 10 less than normal for the first 15 minutes enhanced the overall surface smoothness both by reducing voids and by reducing the grain size apparent in the coating.

We investigated sputtered Cr as a strike for both copper and gold electroplated coatings. Although the Cr strike adhered much better to the glass microsphere than did the Pt strike, the Cr surface proved highly resistant to electroplating of either copper or gold. We tried three techniques to reduce or remove chromium oxide so that electroplating could occur. We found treatment by the Reid-Ogburn²⁵ process to be too drastic and inconsistent to provide useful results. When we tried plating immediately (within 5 minutes) after sputtering the Cr strike on glass microspheres, we were completely unsuccessful. Soaking microspheres coated with freshly sputtered Cr in HCl of various concentrations did not improve results, nor did attempts to apply a strike of Ni over the adherent Cr strike. Our conclusion was that for all its difficulties the sputtered Pt is the best available strike.

The difference in the copper plating and gold plating environments is nowhere more evident than in the anode reactions. In contrast to gold electroplating, the anode is an active element during copper plating.

Uniform oxidation of the anode is necessary to provide platable copper ions in uniform concentrations around the cathode. We found that use of oxygen-free, high-purity copper in the anode and careful degreasing of the anode before beginning the plating operation were essential to achieving satisfactory plating behavior. Preoxidation of anodes in plating baths under operating conditions for 1-1/2 hours was necessary to provide reliable anode behavior. We found careful storage of anodes, either in plating solutions or protected from laboratory contaminants, improved the consistency of plating results.

The commercially available pyrophosphate copper-plating solution we used is sold in a two-part form. We prepare the plating solution by mixing these parts and making a subsequent pH adjustment with either concentrated NH_4OH or gaseous NH_3 . Figure 4-29 shows the range of grain sizes obtained under three different operating conditions.

The "normal" grain size was obtained by copper-plating from a solution of recommended concentration and pH but at room temperature. We chose to operate at room temperature because the reductions in grain size obtained by elevating the

temperature were not spectacular, and because room-temperature operations were simpler, safer, and faster to conduct.

We obtained the grain refinement shown in the micrograph in Fig. 4-29(b) by increasing the relative pyrophosphate concentration by 10% and increasing the overall solution concentrations (at pH 8.4) by the same amount. These two small solution changes provided the marked reduction in grain size illustrated. We held the current density and the temperature constant to produce improvements in the product from that shown in Fig. 4-29(a).

The most dramatic grain refinement in the copper coatings came when we applied the dc-pulse plating technique. A 4.5-V, 50-mA, 1-ms-duration dc pulse was repeated every 4 ms. Rise and fall times at 50-mA currents were less than 50 ns. We used a Tektronix Hall-effect probe to sense cell current. Figure 4-29(c) displays the grain achieved by the combination of solution changes and dc-pulse plating. The grain size in copper coatings was relatively insensitive to current or voltage; we had to change these parameters by a factor of 2 or more to achieve noticeable grain-size changes. Duty cycles of less than 25% simply increased the time required to reach the desired coating

(a) Normal

(b) Grain refined

(c) Grain refined and pulse plated

(d) Electroless solution

Fig. 4-29. Grain size reductions in copper plating on a Pt-struck glass microsphere filled with D-T (pyrophosphate plating solution at room temperature).

thickness, without affecting grain size. Increases in duty cycle beyond 25% led to results identical to those obtained with conventional dc plating. Figure 4-30 shows a highly magnified view of the surface of a copper coating that was dc-pulse-plated on a microsphere.

We found that results of reasonable quality could only be obtained at currents of 0.4 mA/cm^2 or less. This is a factor of 5 less than currents reported by Mayer and Catlett.²⁶ Our optimum currents were so much less than theirs primarily because our solution flow rate within the cells was so low that the plating occurred under approximately static or zero-flow conditions. Therefore, to prevent serious solution instabilities, we had to reduce the plating rate by lowering the current.

In order to electroplate copper, we modified both the vibrating-cathode and

tapered-cathode²⁴ cells by adding a solution-pulse valve. We installed the valve at the cell exit, opening it momentarily at fixed times during the plating to provide a sudden increase or pulse in the average solution flow. When the valve was closed, either a small flow or zero flow could be maintained through a variable-conductance bypass line. The vibrating-cathode cell utilized only the solution pulse to provide microsphere motion. We discontinued the mechanical agitation of the cathode in the cell. To provide a reproducible initial cathode surface, we gold-plated the cathodes in both cells. After each run we removed the copper deposited on the cell cathode with nitric acid. These changes significantly improved the copper-plating process.

Figure 4-31 shows a radiograph of a copper-coated sphere which has been overcoated with a fluorocarbon ablator (see "Polymer Coatings" for details). This example demonstrates that, in addition to meeting the surface and uniformity properties required of the copper coating, the electroplated copper microsphere has withstood handling and analysis as well as the application of an adherent, uniform, and smooth ablator. We expect that further progress in surface smoothness and yields will make electroplated metal coatings an indispensable part of laser fusion targets.

We have begun to realize some of the advantages of electroplating technology: rapid deposition at low temperature, relatively simple equipment, and the capability of depositing soft metals. We hope to extend the technology so as to produce cells that can operate independently of the density of the substrate, and we hope to improve our understanding of the details of the plating process. Alloy plating raises the prospect of mechanically strong coatings for fuel containers, thereby inviting a variety of new implosion diagnostics. With greater understanding we can improve and extend our electroplating capabilities and begin to understand techniques for achieving the high-volume production of targets that will be required for an operating ICF power plant.

Author: J. D. Illige

Major Contributors: C. W. Jordan, R. M. Krenik, D. Lenz, and C. M. Yu

Fig. 4-30. Surface finish of copper electroplated on glass microsphere.

Fig. 4-31. (a) Micro-radiograph of $140 \mu\text{m}$ diameter glass microsphere, electroplated with $2.5 \mu\text{m}$ of copper, and overcoated with a fluorocarbon ablator. (b) Corresponding densitometer trace.

Batch Coating Process for Microspheres

Laser fusion targets will need a variety of metal coatings on glass microspheres. Physical vapor deposition (PVD) is the most versatile coating process for metals and alloys. Developing a PVD batch-coating process for providing these coatings is therefore an important step in laser fusion target fabrication (Fig. 4-32). The spherical shape of the substrates, coupled with their small diameters ($\sim 100\ \mu\text{m}$), makes the coating process very difficult. With a spherical substrate, an obliquely incident coating flux cannot be avoided.²⁷ The resulting coating surface is generally rough and porous under most coating conditions, far from meeting the 30-nm surface smoothness required. Achieving uniform coating thickness requires that the microspheres be kept in constant random motion during coating. However, this motion deprives the microspheres of effective cooling and electrical biasing, which

are important parameters for achieving smoother coatings.

Sputtering has an advantage over other PVD processes because the sputtered coating molecule has a higher kinetic energy when striking the substrate surface. The higher momentum of the coating molecules helps in leveling the coating surface and filling in the voids normally formed by the obliquely incident coating flux. However, the microspheres exposed to the sputtering plasma have a strong tendency to stick to each other or to the pan, thus becoming motionless. This sticking problem can prevent uniform coatings.

Our earlier work led to the first successful batch coating of microspheres with platinum²⁸ by the magnetron sputtering process. The microspheres were contained in a screened cage so that they could be vibrated vigorously to offset the sticking problem. In addition to vibrating the spheres, we also found it necessary to dope the sputtering gas with oxygen to reduce microsphere sticking. This doping affected both the material properties of the Pt coating

Fig. 4-32. Improved fixturing for batch sputter-coating without confinement screen over the bouncer pan.

and the mechanisms responsible for the microspheres' sticking.²⁹

Unfortunately, adjusting the O₂ flow to achieve the optimum material properties was often in conflict with alleviating the sticking effects. The screen that confined the microspheres presented its own problems. It obstructed vision needed for monitoring the microspheres' motions, and by its physical shadowing it reduced the coating rate. It could become a source of contaminants when shedding occurred, and finally, it could not be used for long runs because of the gradual closure of its openings due to coating buildup and mesh breakage resulting from stress.

During 1980 we have improved our understanding of the sticking mechanisms and the role of the O₂ dopant gas, with the result that we have been able to reduce the agitation force needed to overcome the microsphere sticking problems. Building on the initial success of the screened-cage configuration, we have improved the batch process to allow coating of microspheres without the confinement screen, as shown in Fig. 4-32. We can now make long runs (more than 12 hours) with higher coating rates and less chance of coating defects due to contaminants.

Without the impediment of the screen, the microspheres' motion can be clearly observed. The improved vision allows the operator to use minimum dopant gas and bouncer drive to keep the microspheres in constant motion, resulting in better coatings. Typical Pt-coated microspheres made with this process are shown in Fig. 4-33. The important factors affecting the microspheres' motion are dopant gas level, bouncer bias

(electrically floating), and conductivity of the microsphere surface. Bouncer drive level and sputtering power and pressure are of secondary importance.

Microsphere Sticking Mechanisms. The microsphere sticking problem seems to include at least three mechanisms³⁰: first, solid state bonding which includes cold welding and van der Waals bonding; second, net charge attraction of nonconducting microspheres; and third, polarization attraction of metal-coated microspheres in a nonuniform electric field.

One form of solid state bonding is the joining of two clean surfaces of soft metals like Au, Cu, and Al on impact. This cold welding typically forms a rigid, permanent bond after plastic deformation of the two surfaces.²⁸ However, some bonding is reversible, suggesting that a second bonding mechanism besides cold welding is involved. We have seen Pt-coated microspheres clump together upon exposure to hydrogen gas, and release rapidly after exposure to oxygen gas (without plasma).³⁰ This reversibility indicates that no chemical bonds are involved, but rather that van der Waals or induction bonding, dependent on close-range metal-to-metal contact, is involved.

Net charge attraction of nonconducting microspheres is a relatively minor problem, because it disappears when the microsphere surface becomes conductive and can discharge on contact. Bouncing uncoated glass microspheres in vacuum invariably causes the microspheres to clump due to triboelectric charging of the nonconducting glass.³¹

The polarization attraction²⁷ of metal-coated microspheres in a nonuniform electric

Fig. 4-33. Smooth Pt coating on microsphere produced by the screenless batch-coating process.

- 2 μm thick
- 10 mg/cm³ D-T fill
- Surface finish < 100 nm

field region, such as a plasma sheath, is probably the principal source of sticking. Unlike net charge attraction, polarization attraction is not neutralized by contact with the image surface. An electric field will induce a dipole moment in a metal-coated microsphere. However, the electric field strength in the plasma sheath is very nonuniform, decreasing rapidly with distance from the bouncer surface (because of the positive-ion space charge), and vanishing at the edge of the plasma sheath, as shown in Fig. 4-34. The field gradient will always exert an attractive force on the induced dipole in the direction of the stronger field.³² This polarization attraction force depends on the sputtering power level, the total gas pressure, and the conductivity of the microsphere coating surface.

Dopant Gas and Sticking. We reported earlier²⁹ on the effect of O_2 dopant gas on the morphology and grain size of the Pt coatings on microspheres. Further investigation³⁰ shows that the dopant gas is probably incorporated interstitially in the Pt structure, and not exclusively trapped at grain boundaries. The O_2 content in the film, as measured by Auger electron spectroscopy, is linearly proportional to the doping level during sputtering. The result correlates well with the increasing brittleness of the Pt coatings with increasing oxygen partial pressure, as reported earlier. The doping of the Pt film also increases the resistivity. In one experiment,³⁰ the sheet resistance of a thin Pt film increased when exposed to O_2 and decreased when H_2 was introduced. The resistance change was reversible and could be cycled back and forth. Not coincidentally, the introduction of H_2 during sputtering causes the Pt-coated microspheres to clump together, and O_2 unclumps the microspheres. Again, the sticking and unsticking are reversible and can be repeated.

We can deduce the role of O_2 dopant gas in minimizing sticking during sputter-coating from the above experimental results. First of all, hardening of the Pt coatings on the microspheres with O_2 dopant decreases the tendency for solid state bonding, both cold welding and van der Waals. Secondly, the increase in resistivity of the microsphere coating may decrease the polarization attraction force through reduction of the effective induced dipole moment on the microsphere. On a moving microsphere, the

net dipole moment will be reduced when the dipole relaxation time is comparable to the microsphere reorientation time. The increase in resistivity causes a proportionate increase in relaxation time, thus a reduction in the sticking problem of the microspheres.

Future Plans. The principal remaining problem with the present batch-coating process is D-T loss during coating. The microspheres are heated by the sputtering process, and as a result the D-T they contain is diffused through their walls faster. Experiments have been done to compare the rate of D-T loss between uncoated microspheres in an oven and those undergoing sputter coating for an equivalent time; the results suggest that the coated microspheres reached a temperature of approximately 200°C . Efforts to reduce the equilibrium temperature by cryogenic cooling of the fixturing and by using an opposing magnet to reduce electron bombardment of the microspheres have had little apparent effect on D-T loss rate (within rather wide error bars).

We are now investigating resputtering as an energy source to the microsphere. In a normal rf sputter-coating process, there is always a percentage of material being resputtered from the coating on the microspheres. The bombarding ions and neutrals contribute to the temperature rise of the microspheres. Preliminary study shows

Fig. 4-34. Schematic illustration showing polarization attractive forces due to nonuniform electric field in plasma sheath near charged surface.

that the coating rate is not proportional to the sputtering power, which strongly suggests that resputtering is occurring on the electrically floating microspheres at higher power levels. Experiments are now in progress to measure the D-T loss rate under minimum-resputtering coating conditions.

Author: E. J. Hsieh

Major Contributors: S. F. Meyer, A. Plake, and G. Jameson

MBL Coating of Soft Metals on Microspheres

The microsphere batch-coating process discussed in the previous article works well for metals that are relatively immune to vacuum welding,³³ but not for soft metals like Au, Al, and Cu. Such soft metals are sometimes needed as diagnostic layers in targets for laser fusion experiments. The molecular beam levitator (MBL)³⁴ can

Fig. 4-35. Molecular beam levitation (MBL) fixture for dc and rf magnetron sputter coatings.

Fig. 4-36. Target-quality Cu coating on microsphere was produced by MBL technique. ▼

provide contact-free support of a glass microsphere during soft metal coating. The MBL scheme supports one glass microsphere at a time and can be adapted for magnetron sputtering with minor modifications.

Previous MBL work showed levitation instability due to electrostatic problems with metal coatings.^{34,35} A sudden change in the levitation condition occurred when the microsphere had acquired a continuous metal coating, causing the microsphere either to be ejected or to stick to the levitator. We avoid this problem by pre-metallizing the microsphere with a flash coating before levitation, thus preventing the sudden change in levitation condition. We have constructed the MBL fixture shown in Fig. 4-35 to allow operation in either a dc or rf argon sputtering discharge. Important new features of this fixture are the electrical isolation and water-cooling of the collimated hole structure (CHS). The electrical isolation of the CHS reduces the electrostatic force on a levitating microsphere. Water-cooling the CHS reduces heat to the microsphere. We do not use the centering ring³⁶ because the microsphere tends to seek its own preferred position above the CHS when magnetron sputtering is done with low pressures (0.3 to 1.5 Pa). Using dc sputtering, we have produced the first target-quality coatings of copper on microspheres, such as in Fig. 4-36.

Coating Process. We levitate the microsphere a few hundred micrometres above the CHS and approximately 4.5 cm below the target ring of the Sloan S-310 Sputtergun. The sputtering pressure is between 0.3 and 1.5 Pa and the levitation flow is 0.2 to 0.3 sccm of Ar, using a 25- μ m CHS. We sputter at a relatively low dc power (200 W), as a compromise between coating rate and levitation stability. The initial lift-off of the microsphere from the CHS surface is very delicate, so we have installed a shutter over the CHS to isolate the microsphere from the plasma during lift-off. With the levitation gas flowing, we jar the CHS support slightly, causing the microsphere to lift off. As the shutter is opened, exposing the microsphere to the plasma and coating flux, we increase the levitation gas flow to counteract the downward force.

The rf sputtering technique is desirable because it can be used for both conductive and nonconductive materials. But we have

more difficulty levitating when rf sputtering is used. Therefore we make a slow transition from dc to rf power with the shutter closed. The maximum rf power that we have been able to use is 140 W.

Present Status. We have successfully adapted the MBL for coating soft metals (Au and Cu) on individual microspheres, producing target-quality copper coatings with dc sputtering. Using this technique we obtained a surface finish of 300 nm (peak to peak) on a 2- μ m-thick copper coating, as shown in Fig. 4-37. As Fig. 4-38 shows, the coating is of uniform thickness all around

Fig. 4-37. Smooth surface finish (300 nm peak to peak) of 2- μ m Cu coating produced by MBL technique.

Fig. 4-38. Good thickness uniformity of Cu coating on microsphere, as viewed by radiography. ▼

the sphere. We are continuing work on improving levitation stability, reducing the dependence on premetallization of the microspheres, and achieving higher coating rates with rf sputtering.

Authors: M. J. Rocke, S. F. Meyer, and E. J. Hsieh

Major Contributors: G. T. Jameson and P. Rocke

Fig. 4-39. Thick Be coating ($> 18 \mu\text{m}$) on microsphere, produced by three consecutive runs.

(a) Surface morphology

Fig. 4-40. Thick Be coating ($> 40 \mu\text{m}$) on hemispherical Cu mandrel can be micromachined into a suitable hemispherical shell for use in a second shell target. ▼

(b) Cross section view

Advances in Beryllium Coatings

We have made good progress this year with beryllium coatings on glass microspheres and copper hemispherical mandrels. Proposed laser-fusion targets require thick, dense, smooth Be coatings on both microspheres and hemispherical mandrels for second-shell applications. We are continuing to use the rf magnetron sputtering process³⁷ to make the Be coatings because it provides high production rates at low sputtering pressures ($\sim 0.4 \text{ Pa}$). Under these sputtering conditions we obtain a smooth, dense Be coating if the substrate temperature is kept low.³⁸

Our most significant advances have been in achieving long continuous runs ($> 12 \text{ h}$) of coating Be on microspheres, and in producing dense Be coatings on hemispherical copper mandrels.

Be Coating on Microspheres. The batch coating process for microspheres described in "Batch Coating Process for Microspheres" was developed in conjunction with the experimental effort to achieve thick Be coatings on microspheres. The screened-cage configuration offered some degree of success but failed to yield thick Be coatings. The low sputtering yield of Be in combination with the physical shadowing of the screen gave a very low Be coating rate on microspheres. Low coating rates are undesirable, because longer coating runs

(a) Unsymmetrical coating

(b) Sputter-etched surface

lead to more coating defects. The length of a coating run is ultimately limited by the breakage of the screen due to stress buildup from the thick Be coating that collects on it.

At this stage of development, neither the surface finish nor the density of the Be coating can meet the target specifications. The surface morphology and cross-sectional structure of this thick coating of Be on a microsphere are shown in Fig. 4-39. The characteristic hexagonal crystalline structure of Be shows clearly on the surface, indicating a rather high substrate deposition temperature. The large columnar grain growth shown in the cross-sectional view also points to a high substrate temperature.

Be Coating on Mandrels. The primary interest in coating beryllium on mandrels is for second-shell applications (see "Double-Shell Technology"). We use hemispherical copper mandrels as the Be substrates.

A Be coating with an average thickness of $40\text{ }\mu\text{m}$ is shown in Fig. 4-40. The lopsidedness of the coating is the result of off-center positioning of the mandrel in the coating chamber. We can correct this defect by rotating the positions of the mandrels during coating. The slight etching on the surface of the coating is due to resputtering; it is difficult to achieve absolute rf electrical isolation, which would prevent resputtering, in an rf plasma.

Author: E. J. Hsieh

Major Contributors: S. F. Meyer, R. J. Burt, G. A. Gleeson, and M. J. Rocke

Double-Shell Technology

Introduction

In 1980 we continued to improve our capabilities for producing double-shell targets. In previous reports we have described the coating and machining techniques used to produce free-standing hemispherical shells of CII polymer, which can be joined together in pairs to provide the second shells of double-shell targets.³⁹ This

year we have achieved some notable improvements. For example, we have coated beryllium on hemispherical copper mandrels to produce Be hemishell blanks which we have machined into finished Be hemishells with less than $1\text{ }\mu\text{m}$ of surface roughness. Around the equators of these hemishells we have machined mating, step-shaped joints to minimize the effect of the seam when two shells are joined into a sphere.

We have also made progress toward machining hemispherical shells of lead styrene. A pair of these shells can be joined to form the inner layer of a two-layer second shell. This high-Z-seeded layer serves as a pusher and preheat shield.

Author: B. W. Weinstein

Micromachining of Sputter-Coated Beryllium

One of the approaches we are considering for producing the outer shell of a double-shell target is to make Be hemishell blanks by sputter-coating a thick Be layer onto a hemispherical copper mandrel, and then to precision machine the blanks into hemishells having the required surface finish.⁴⁰ Our experience shows that thick Be coatings ($>20\text{-}\mu\text{m}$) on water-cooled Cu mandrels usually have coarse surfaces ($>3\text{-}\mu\text{m}$), due to oblique coating flux and sputter-etching, and large variations in thickness due to asymmetry of the coating and the nonplanar nature of the substrate. It is important to know whether sputter-coated beryllium can be precision machined, given its brittle nature. Experiments have been conducted, in conjunction with personnel of Rockwell International's Rocky Flats Plant (Future Systems Group), in which representative sputtered Be coatings were cut on an ultraprecision single-point diamond lathe. Preliminary results show that sputter-coated Be can be machined to a surface finish smoothness of less than $1\text{ }\mu\text{m}$ on the hemispherical mandrel, and that a satisfactory Be second shell can be obtained with a slight modification of the mandrel design.

Fig 4-41. Machined ▲ hemispherical surface of thick Be coating on mandrel.

Fig. 4-42. Uniform density of a machined Be coating on copper mandrel, shown by radiography.

Fig. 4-43. Proposed new mandrel design for machined beryllium second shell.

Sample Preparation and Machining

Results. We obtained the precision-machined 260- μm hemispherical Cu mandrels from Rocky Flats Plant. After a sequence of solvent ultrasonic cleanings and a final hydrogen plasma etch, we sputter-coated the mandrels with beryllium as described in "Advances in Beryllium Coatings." Nine coated mandrels were prepared for micromachining with a minimum Be thickness of approximately 20 μm . We examined them under scanning electron microscopes and optical microscopes before shipping them back to Rocky Flats for machining. The one shown in Fig. 4-40 is typical; all the coatings are uneven, and the thickness ratio between the pole and equator can be as large as two to one. We sputter-coated the mandrels at different fixturing positions to test the coating thickness distributions and differences in machinability. Hydrogen doping was used in one of the Be coatings.

The machining results at Rocky Flats are encouraging. The Be coatings were found to be very brittle but could be machined when precautionary steps were taken. The hydrogen doped Be coating was too brittle for machining; however, four of the nine Be-coated mandrels were successfully machined into hemispherical shells. The others broke, usually during the "parting cut" at the equator. We did not observe any significant effects of fixturing positions on machinability of the Be coatings.

Typical machined Be coating surfaces, as shown in Fig. 4-41, have better than 1- μm finishes. The jagged surface at the equator is

due mainly to the columnar structure of the Be coating. The coating fractures easily along the radial columnar growth, which is why some of the hemispherical shells broke during the parting cut.

Radiographic examination of the machined Be coating shows that the coating density is uniform with good step coverage. Typical radiography of a machined mandrel is shown in Fig. 4-42.

Future Plans. The breakage problem and the jagged surface at the equator will be our main concern in future experiments. We can do very little to suppress the columnar grain growth of the Be coating without introducing other undesirable results. But we can attack the problem by eliminating the parting cut at the equator when forming the hemispherical shell. We propose that the Cu hemispherical mandrels be modified in shape as shown in Fig. 4-43. The flat shoulder in the new mandrel design provides a smooth surface at the equator of the hemispherical shell. The shoulder shape may be modified in the future to avoid a radial joint.

We have shown that the sputtered Be coatings can be machined, and now, with the new mandrel design, the chances of fabricating a satisfactory Be shell are good.

Author: E. J. Hsieh

Major Contributors: S. F. Meyer, C. Durbin (Rocky Flats), G. A. Gleeson, and C. W. Hatcher

and, finally, removing and cleaning the finished hydrocarbon hemishell. These hemishells are then characterized and used in target fabrication.

Hemishells have been made both at LLNL and at Rockwell International's Rocky Flats Plant. In the LLNL version of this process, a solution of 1,2-polybutadiene in vinyl toluene is laid down and cured on the copper mandrel. Figure 4-44 shows a typical

Fig. 4-44. Polymer systems used for making precision-machinable hydrocarbon hemishell blanks.

Step-Jointed Hemishells

We described a procedure for making machined hemishells (i.e., hemispherical shells) and assembling them into double-shell targets in the 1979 Laser Annual Report⁴¹; this procedure continues to be used with certain refinements. We begin by precision-machining a copper mandrel of proper radius and surface finish, coating it with a machinable hydrocarbon material (Fig. 4-44), which serves as the blank for the hemishell, machining the outer surface of the blank to the desired dimensions and finish,

Double-Shell Technology

Fig. 4-45. Mating pair of hemishells with stepped or rabbeted joints to insure proper alignment when fitted together (scanning electron microscope photo).

Fig. 4-46. Close-up of stepped joints, showing sharpness of corners required to eliminate voids (scanning electron microscope photo). ▼

chemical structure of the cured hydrocarbon material. We have improved the machinability of the material by modifying the heating cycle. We cure the resin in air (rather than in inert gas) to increase cross-linking, which compensates for the partial volatilization of the monomer and curing agent in the thin-walled blank. We have increased the size of the shank of the copper mandrel to prevent any unwanted displacement during the thermal cure of the polymer blank, thus insuring precise relocation in the lathe. We separate the machined hemishells from the copper mandrels by dissolving the copper in nitric acid.

In an attempt to preserve the mandrels for reuse, we tried separating the hemishells from them by immersion in an ultrasonic bath. As bath liquids we tried water, water containing powerful fluorinated wetting agents, alcohols, and a silicone fluid. We also applied a bead of silicone rubber in the groove formed behind the hemishell in machining the equatorial plane, cured the rubber, and then swelled it in hexane to provide a dislodging force. None of these techniques worked reliably in detaching the hemishells, and sometimes the hemishells that did detach were cracked.

In the Rocky Flats version of hemishell machining, a molten droplet of resin is applied to a premachined, heated copper mandrel that is already in the lathe, and allowed to harden. The resin is a blend of 85% polystyrene and 15% 1,4-butadiene/styrene copolymer. This material is machinable and can withstand the thermal and physical stresses inherent in the application and machining processes.

The joining of two hemishells in proper alignment is a difficult task. One solution is to machine complementary mating surfaces in the edges of the hemishells to provide positive alignment. Rocky Flats workers have machined stepped or rabbeted joints into the equatorial edges of hemishells as shown in Fig. 4-45. The steps are of equal width and height (25 μm). A 20-nm-radius diamond tool is used to machine sharp, clean corners (Fig. 4-46). Such hemishells require some modification in the use of the ultrathin-film HGM support system.

Author: L. E. Lorensen

Lead Styrene Hemishells

Many double-shell target designs have, as a preheat shield on the inside of the second shell, a layer of some matrix material seeded with another, high-Z material. This layer shields the inner sphere of the target from high-energy electrons and x rays.

As a step toward producing targets of this type, we are developing techniques for machining hemishells of lead styrene polymer. Such a hemishell could be used as a preheat shield inside a polystyrene ablator layer.

The lead styrene material with which we have been experimenting was developed by KMS Fusion.⁴² It consists of organometallic molecules containing about 2 at.% (38 wt%) lead. The material has a density of 1.6 g/cm³, which is close to that of ablators such as polystyrene (1.0 g/cm³). Since the molecular structure of lead styrene is similar to that of polystyrene, we should be able to use the same machining process for both materials.

We have described our micromachining techniques for making polystyrene hemispheres in previous reports.⁴³ One of the most successful techniques is that used at Rockwell International's Rocky Flats Plant, in which a hemispherical copper mandrel is cut to the inside dimensions of the desired hemishell. The mandrel is heated and a layer of polystyrene thermoplastic is applied to it. Once the styrene layer has cooled and hardened, its outside surface is machined to the desired dimensions. The mandrel is then dissolved away, leaving a free-standing polymer hemishell. This process has been very successful, providing most of the hemishells used in our experiments.

The first lead styrene sample we attempted to machine was formed by homopolymerization with AIBN in benzene at 60°C. This material had a molecular weight of 3502, as determined by vapor phase osmometry, and a degree of polymerization of 6.5. We found that it could be easily applied to the mandrel, but that it was very brittle, consistently fracturing during the machining process. By blending it with the polystyrene already being used at Rocky Flats, we were able to produce a material which could be applied to the mandrel and machined.

The blended material was about 1 at.% lead (23 wt% lead). Unfortunately, it was still too brittle, resulting in cracking of the hemispheres and crazing of the outer surface. A scanning electron microscope photo of the surface of a hemisphere produced from this material is shown in Fig. 4-47.

We performed a second set of experiments using lead styrene formed by bulk thermal polymerization at 124°C. This material has a much higher molecular weight, and is highly cross-linked. We found that it could not be applied to the mandrel thermally, because it decomposed before softening. By blending this high-molecular-weight lead styrene with the previous low-molecular-weight sample, we were able to obtain a material which could be applied to the mandrel and machined. Although this blended material still exhibited cracking of the walls and crazing of the surface, we found the results generally encouraging. With proper control of the addition of plasticizers, we are confident that we can produce a material with the desired machining characteristics.

Once we are successful at machining lead styrene hemishells, there are several possible ways of producing a double-layer second shell. One possibility is to assemble two lead styrene hemishells around the inner capsule and then overcoat the entire assembly with a CH ablator. The work toward developing this capability is described in "Molecular-Beam-Levitated Coating of Second Shells" later in this section. Another possibility is to machine a second set of polystyrene

Fig. 4-47. Surface crazing of a low-molecular-weight lead styrene hemisphere made by micromachining. We hope to overcome this problem by proper control of the polymerization process.

Characterization and Analysis

hemishells, which would then be assembled around the lead styrene hemishells and inner capsule. A third possibility is to apply a second layer of ordinary styrene over the machined lead styrene hemishell before it is removed from the mandrel. The outer surface could then be machined to the proper size.

The lead styrene polymer softens at a lower temperature than does ordinary polystyrene, so thermal overcoating is not possible with present materials. Fortunately we have an alternative coating process in which a liquid monomer is applied at room temperature and cured either at slightly elevated temperatures (140°F) or by exposure to ultraviolet light. This coating process is described in a previous report.⁴³

Although more work is needed, we believe that further development of these processes will provide high-quality double-layer second shells needed for ICF targets.

Author: B. W. Weinstein

Major Contributors: L. Case and C. Durbin (both of Rockwell International), L. Kool and R. Nolen (both of KMS Fusion), and L. E. Lorenson

Characterization and Analysis

Introduction

Accurate measurement and materials analysis remain key components of ICF target development and production. During

1980 we have improved our measurement capabilities in a number of areas. To improve our measurements of optically nontransparent targets, we have developed a monoenergetic x-ray source which produces high-resolution microradiographs, and we have implemented a least-squares fitting algorithm on our microcomputer-based radiographic analysis system, AXIAS. We have continued with development of automated surface-mapping capabilities, using both interferometry and electron backscattering. We have also developed microsectioning techniques for target spheres which allow us to examine the inner structure of the target wall and cross-check our nondestructive measurements. Improvements in our routine measurements provide faster and more reliable handling of samples. The following sections describe these advances in detail.

Author: B. W. Weinstein

Molecular-Beam-Levitated Coating of Second Shells

A technique for producing the outer shell of double-shell targets is to assemble a pair of thin hemishells around the inner capsule, support this preassembly in a molecular beam levitator (described in "Molecular Beam Levitation Development"), and coat it with CH ablator material in a coating plasma. The advantage of this procedure is that it yields a seamless ablative layer—an important requirement for obtaining a symmetric implosion.

In early experiments with this technique we produced a prolate target with a large

Fig 4-48. These electron micrographs show an assembled double-shell target that has been coated with CF plastic.

Fig. 4-49. Process for assembling and coating double-shell targets (as shown in Fig. 4-50).

Fig. 4-50. Parts of an assembly like the one diagrammed in the previous figure. ▼

seam defect (Fig. 4-48).⁴⁴ The preassembly process generates this defect in the coating in the following way: a misalignment of the two hemishells results in a small ledge at the seams, and excess film from the inner target support⁴⁵ protrudes from the preassembly seam, forming a skirt of unwanted material. For the final coating to attain target quality, the preassembly defect must be less than $0.1 \mu\text{m}$.⁴⁶

In Fig. 4-49 we show the procedure that has resulted in a markedly improved surface finish of our coated assemblies. First, we assemble the hemishells about the considerably smaller inner target, which is sandwiched between the hydrocarbon films.⁴⁵ Figure 4-50 shows the parts to be assembled. As a result of our manufacturing and assembly experience, the match of the hemishells in the assembly and the glue joints at the seam have improved greatly. In

Fig. 4-51. (a) View of the finished coated assembly made from the parts shown in Fig. 4-50. (b) View of the area of the coated assembly's seam where the hemishells were best matched.

the second step we plasma-etch the assembly to reduce the protruding skirt of hydrocarbon film. Finally, we coat the assembly, using the molecular beam levitator, in our fluorocarbon coater.

In Fig. 4-51(a) we show an assembly coated with 30 μm of CF. The high-resolution view, Fig. 4-51(b), shows the region of the seam. The surface finish of this coated assembly is close to the high quality required for a target. As we improve our matching of the hemishells and the yields of the etching and coating processes, we are confident we can provide seamless double-shell targets.

Authors: J. K. Crane and W. L. Johnson

Major Contributors: S. A. Letts and R. D. Smith

thickness from 1 to 100 μm when applied to glass microspheres whose diameters may range from 70 to 200 μm .

To characterize an individual microsphere, we mount it between two thin membranes which are transparent to the x rays, as shown in Fig. 4-52. Then we place it in contact with a glass film plate and expose it to an x-ray source. The information about coating thickness and uniformity is thus recorded as optical density variations on the photographic plate. By magnifying the image on a radiograph and taking an optical density scan across the magnified image, we can retrieve this information, as shown in Fig. 4-53. Detailed explanations of these techniques are given in previous annual reports.^{47,48}

One of the major improvements we have made is the development and subsequent routine use of a monoenergetic, but energy-selectable, x-ray source for producing the radiographs. This source replaces the bremsstrahlung source we had used previously. The advantage of a monoenergetic source is that it allows us to maximize the information recorded on the film, by choosing the correct x-ray energy for a particular target or application. This point is easily understood by considering the two extreme cases. At very low x-ray energy the target microsphere is opaque, and the film records a uniform area of nonexposure. At too high an energy the microsphere is transparent to the x rays, and the film records a uniform overexposure. The optimum energy is chosen according to the absorption path length the x rays take through the target (a function of sphere diameter and coating thickness) and the coating material's absorption cross section for x rays (a function of x-ray energy).

Microradiography

In characterizing targets, we use microradiography to measure the thickness and uniformity of opaque coatings that have been applied to glass microspheres. These coatings can be either metal (beryllium, copper, platinum) or an organic polymer (CH_x or CF_x), and they can range in

Fig. 4-52. Microsphere is held between two thin membranes against a glass film plate for exposure to x rays.

Once we have determined the energy we wish to use for a given target, we choose an appropriate anode material for the monoenergetic source. By controlling the accelerating voltage we can selectively excite a fluorescence x-ray line of the anode material. The bremsstrahlung radiation is also produced, but we can maximize the ratio of fluorescence line to bremsstrahlung background by choosing the correct voltage. The spectrum can be further improved by absorption filtering of the unwanted radiation.

An example of the advantage of choosing the correct x-ray energy can be seen in Figs. 4-54 and 4-55. These are radiographs of the same target, in the same orientation, but made with different x-ray energies. The target is a glass microsphere that has been coated with $2\text{ }\mu\text{m}$ of copper and then coated with $10\text{ }\mu\text{m}$ of CH_x polymer. Figure 4-54 was made using the L line of copper, and the x rays penetrated only the polymer coating. The image shows clearly that this is an asymmetric coating, thicker on the left side.

Keeping the microsphere in the same orientation as before, we then used the $\text{K}_{\alpha,\beta}$ lines of the copper anode to examine the copper coating (Fig. 4-55). The polymer is no

Fig. 4-54. Glass microsphere coated with $2\text{ }\mu\text{m}$ of copper and overcoated with $10\text{ }\mu\text{m}$ of polymer. (a) Nonuniform plastic outer coating shows up when microsphere is radiographed with copper L line. (b) Horizontal trace of optical density.

Fig. 4-55. Same microsphere with same orientation as in previous figure. (a) Nonuniform copper coating beneath plastic outer coating shows up when microsphere is radiographed with copper $\text{K}_{\alpha,\beta}$ lines. (b) Horizontal trace of optical density.

Fig. 4-53. X-ray path length as a function of wall thickness and uniformity.

Fig. 4-56. Glass microsphere coated with 15 μm of Be. (a) Density change in Be coating shows up when microsphere is radiographed with copper L line. (b) Horizontal trace of optical density.

Fig. 4-57. Output of the AXIAS analysis system using least-squares fitting routine. ▼

Table 4-1. Comparison of optical and radiographic measurements made on the same glass microsphere.

Parameter	Optical measurement	Radiographic measurement
Diameter (μm)	221 ± 1	222 ± 2
Wall thickness (μm)	5.9 ± 0.3	6.6 ± 0.5
Nonconcentricity (μm)	0.60 ± 0.01	0.57 ± 0.05

Table 4-2. Typical uncertainties and limits of accuracy obtained with the least-squares fitting routine developed for AXIAS data.

Parameter	Typical uncertainty	Limit of accuracy
Diameter	1%	1.0 μm
Wall thickness	1%	0.5 μm
Nonconcentricity	3% (of wall thickness)	0.05 μm

longer visible, since it is transparent to these higher energy x rays. (The inner glass microsphere is likewise transparent.) Figure 4-55 shows that the copper coating is also asymmetrical, thicker on the right side. The thick area of the polymer coating is over the thin area of the copper. This happened because the copper-coated ball was suspended in a molecular beam levitator,⁴⁹ allowing the heavy side (thicker coating) to remain down while the polymer coating was applied from the top.

Another example of the detail we can achieve with the monoenergetic source is demonstrated in Fig. 4-56, which is a radiograph of a glass microsphere coated with 15 μm of beryllium, made using the copper L line. The coating appears as two distinct layers, because of a density change in the beryllium which resulted from a change in coating parameters during the coating run.

We have further improved our x-ray radiography by implementing a least-squares fitting routine in the analysis of the x-ray image. The Automated X-Ray Image Analysis System (AXIAS)⁵⁰ produces and stores a digitized cross-section scan of the optical density of the film, and displays it on a TV monitor. Until recently, we analyzed this density scan manually by using calibrated cursors on the monitor. By setting the cursors on the outside edge and the least dense point, we could measure the wall thickness with an accuracy of $\pm 1 \mu\text{m}$. Symmetry defects were measured by noting differences in wall thickness measurements from side to side. This limited our sensitivity to defects in concentricity to $\pm 1 \mu\text{m}$.

The least-squares fitting routine eliminates the need for the cursors. It does a four-parameter fit on the data from the density scan. The four parameters are again the two outside edges and the two least dense points. Running on the same microprocessor system that acquires the data, the fitting routine can return values of the diameter, thickness, and nonconcentricity in 2 to 3 minutes. Figure 4-57 shows a density scan and the corresponding fit.

To verify the accuracy of the system, we used it to analyze several glass microspheres that had been characterized optically with an interferometer. Comparisons of optical measurements versus radiographic measurements on a typical microsphere are shown in Table 4-1. The fact that the radiographic measurements overlap the more accurate optical measurements (within the respective uncertainties) is seen as a verification of the radiographic technique.

The experimentally tested uncertainties in the measurement of microsphere parameters can be stated as a percentage of the values measured. There is, however, a minimum absolute uncertainty representing the limit of accuracy of the technique. Table 4-2 lists typical uncertainties of the radiographic measurements and the corresponding limits of accuracy of this technique.

With our new analysis capabilities we can now select a microsphere, radiograph it, and analyze the data to the accuracies listed in Table 4-1, all within 45 minutes. This makes the microradiography system a useful and production-oriented tool for examining opaque targets.

Author: J. T. Weir

Major Contributors: D. M. Gouveia, S. Perkins, N. R. Riley, and R. M. Singleton

Interferometric Sphere-Mapping System

During the year, we tested the optics for our automated sphere-mapping (ASM) system,⁵¹ which is under continuing development, and finalized the design of a sphere rotation system to be incorporated in it. When complete, the ASM system will be able to measure height defects over the total surface of an opaque or transparent microsphere in only a few minutes. The ASM optics were fully discussed in the 1979 Annual Report.⁵¹ In this section we detail the improvements to the sphere rotation system, which makes possible the total surface examination.

The ASM sphere rotation system, shown in Fig. 4-58, provides $\sim 1\text{-}\mu\text{m}$ positioning stability and rapid computer-controlled rotation of the sample sphere, together with

five-axis fine adjustment of the flat rotator tips that contact the sphere. The x-y stages, which move the drive plate and the cage, will be supported by air bearings and driven by dc servo motors with precision linear position encoders to achieve $1\text{-}\mu\text{m}$ accuracy. The drive plate and the driven plate are coupled by three caged spheres that are allowed to rotate but not translate.⁵² Thus when the drive plate moves (together with the drive cage which is connected to it) in a given direction for a given distance, the driven plate moves an equal distance but in the opposite direction. These equal and opposite motions ensure that the sample sphere will rotate without translating.

This rotation system is a considerable improvement over the rotator used on the TOPO II system.^{52,53} Among its major innovations are: rotator tips centered between the driven plate and the drive plate; very stable rotator tips, remotely adjustable about five axes; and laminated ferromagnetic surfaces to reduce eddy current losses generated by the clamping magnets during plate motion.

Fig. 4-58. ASM sphere rotator subjects the total surface of the microsphere to examination for height defects (see text for details).

Fig. 4-59. In the ASM system, the controlling computer correlates surface data from the optics with sphere position data to generate a map of the sphere's surface with 10-nm resolution.

Centering the rotator tips between the drive and driven plates greatly reduces tip vibration. The remotely adjustable rotator tips are much more convenient to use, can be more precisely adjusted, and are immune to potential harm from manual adjustments of the tips. The laminated ferromagnetic surfaces greatly reduce axial loads caused by eddy current losses, thus giving smoother acceleration of the drive plate and increasing driver bearing lifetimes.

The sphere rotator is integrated into the ASM system as diagrammed in Fig. 4-59.

Author: D. L. Willenborg

Major Contributors: J. A. Monjes, A. L. Richmond, and B. W. Weinstein

Production Improvements

Accurate measurements play a central role in the production of ICF targets. For target spheres and hemispheres, the diameter, wall

thickness (especially the uniformity of thickness), and surface finish must be measured with great precision. The thickness and uniformity of disks and mounting films must also be measured accurately. The amount of D-T fill and other tracer gases must be measured for each target prior to its use.

Most of the standard procedures we use have been described in previous publications.⁵⁴ This year several improvements have been made to our available capabilities. These include coupling of a laser interferometer to one of our Zeiss microscopes, to improve the speed and accuracy of measurements of hemispheres and other small parts; addition of antistatic equipment to reduce the handling problems that occur with small objects when they acquire electrostatic charges; and implementation of the first version of an automated x-ray microradiograph analysis.

Improved Measurements with Laser Interferometer. When using an interference microscope to measure ICF targets, we measure the movement of the interferometer optics as we accurately locate each surface or

interface with a white-light interference pattern. The motion of the optics can be measured in a number of ways. The simplest is to count fringes under monochromatic illumination. Fringe counting can be done with an accuracy of about 1/10 fringe, or $\pm 0.03 \mu\text{m}$, but it is very tedious and time-consuming. For layers thin enough that both surfaces are in focus simultaneously, we use a calibrated optical path compensator. This is much faster than fringe counting and has an accuracy of about $\pm 0.1 \mu\text{m}$. For rapid measurements of large displacements, we have been using calibrated mechanical probes, which have an accuracy of about $\pm 1 \mu\text{m}$.

To provide the speed of a mechanical probe and the accuracy of fringe counting, we have mated a laser interferometer to one of our Twyman-Green interference microscopes as shown in Fig. 4-60. The laser interferometer measures the position of the interferometer optics with an accuracy of $\pm 0.01 \mu\text{m}$. Measurement accuracy is limited only by the ability of the operator to locate the center of the white-light fringe pattern, which is generally $\pm 0.03 \mu\text{m}$. This arrangement provides both high accuracy

and high speed. The only drawback is the substantial cost of the laser interferometer.

Antistatic Measures. Many of the difficulties encountered in handling target microspheres and other tiny target components are caused by static electricity. Target spheres often clump together, making examination and selection of an individual sphere impossible. Spheres are sometimes strongly attracted to the vacuum chucks we use for manipulation; at other times they are strongly repelled. The effects are highly unpredictable. Many factors are involved, including the type of coating, the relative humidity, and the storage and handling history of the parts. In addition, beta decay of tritium causes surface and bulk charging of D-T-filled target spheres.

During the past year we have tried several methods of minimizing the effects of static electricity, including grounding straps for personnel and equipment, grounded mats for work stations, antistatic fluids and storage containers, and electrostatic discharging devices. So far, the most effective solution has been to use an electrostatic discharger (Fig. 4-61) to neutralize the vacuum chucks, the target containers, and the targets

Fig. 4-60. Laser interferometer coupled to an interference microscope provides rapid, accurate measurement of targets and eliminates the need for counting fringes

themselves immediately before attempting to transfer a target. The discharger has a set of sharp emission points, arranged in a ring, which are held at high voltage to form a cloud of ionized air. Any static charge on an object placed in the center of the ring is neutralized in a few seconds.

This procedure is particularly important for handling metal-coated target spheres with a glass vacuum chuck. If there is any static charge on the vacuum chuck, then as the chuck approaches a conducting target sphere, the sphere will become polarized and will be attracted to the chuck. However, as soon as it touches the chuck, the sphere picks up some of the charge and is repelled. This effect often makes it impossible to pick up a sphere, or causes the sphere to be lost entirely. With the static discharger, these problems are eliminated.

Another important application of static discharging is in sandwiching target spheres between the plastic films in which they are held for x-ray radiography. Without discharging, these films often become so highly charged that insertion and retrieval of the spheres is impossible. In this case also, electrostatic discharging has proven very effective in neutralizing the charge, allowing normal handling.

Automated Microradiograph Analysis. In previous reports^{54,55} we described development of the AXIAS system for analysis of x-ray microradiograph images of target spheres. During 1980 we implemented the first production version of AXIAS. The system provides rapid, on-line digitization of radiographic images, storing the data in computer memory for processing and analysis. For diameter and wall thickness measurements, the system displays a trace of film density versus position along a sphere diameter. To reduce film grain noise, this density trace is obtained by averaging along arcs in a wedge-shaped slice of data centered on the sphere. The data are averaged along sphere radii. For examples of x-ray images analyzed with the AXIAS system, see "Microradiography," earlier in this section. The system provides electronic cursors which are used to locate the edges of the sphere and of each layer of the wall. The operator positions the cursors and the system automatically reads out the separation between them, providing rapid measurements with an accuracy of 0.5 to 1.0 μm .

This system represents a significant improvement in the speed and accuracy of our radiographic measurements. These measurements will improve still further as

Fig. 4-61. Electrostatic charges that accumulate on targets and handling tools can make the tiny targets unmanageable; this discharging ring neutralizes such static charges, to facilitate handling of the targets.

planned refinements to the AXIAS system are implemented.

Author: B. W. Weinstein

Microtopography

Surface finish is a major control factor in target production, and it receives a large share of our research effort. Surface finishes can be directly related to coating parameters, so there is a need for rapid repeatable measurement techniques having spatial resolutions less than $2\text{ }\mu\text{m}$ and height sensitivity better than 10 nm , and covering enough area to be representative.

We routinely use the scanning electron microscope (SEM) as a surface measurement tool because of its $<10\text{-nm}$ resolution, its great depth of field, and the ease of sample preparation; however, it has the disadvantage that only a small section of the sample can be examined at one time. This year we have continued development of a new SEM technique which uses back-scattered electrons to measure height, length, and width simultaneously, and which covers larger areas at one time.⁵⁶ Building on our initial system, we have improved the

electronics, written additional software, and demonstrated that both high spatial resolution and sensitivity to large, gently sloping features can be obtained.

Figure 4-62 illustrates the system configuration as installed on our Cambridge S-180 SEM. Early tests showed that the technique was limited by the electronic noise, amplifier drift, and instabilities in the original commercial components. We replaced the original external preamplifier with a new unit built with matched, low-noise amplifiers placed directly on the detector mount, paying special attention to grounding and shielding. To improve signal processing, we built a new main amplifier using optical isolators to eliminate ground loops to the LSI-11 computer. We incorporated direct beam control from the digital-to-analog converter, along with a computer-controlled switch to change the SEM scanning source from the internal generator to the computer. The results of these improvements are a hundredfold reduction in noise, virtual elimination of 60-Hz ripple, and drift so low that we can maintain detector balances for weeks.

The results achieved with the system on a sample consisting of a group of $60\text{-}\mu\text{m}$ glass spheres mounted in silver epoxy, are shown

Fig. 4-62. Block diagram of backscattered-electron microtopography system.

Characterization and Analysis

in Fig. 4-63. The SEM picture, Fig. 4-63(a), was taken in the conventional way, using secondary electrons. The oblique SEM shot in Fig. 4-63(b) shows the same region again, to indicate typical heights. The microtopographic scan of the sample, Fig. 4-63(c), was made with backscattered electrons, at the same stage-tilt angle as was used for the sample during the secondary electron measurements of Figs. 4-63(a) and (b).

The first thing we notice about the microtopographic scan of Fig 4-63(c) is the good detail on the silver epoxy mounting surface, with large and small waves clearly apparent, as well as the good detail on the tops of the spheres. However, the measured heights of the spheres are twice their actual values (as determined in the SEM scans), and the widths are shown as almost three times the actual values. These

Fig. 4-63. Comparison of conventional SEM scans (made with secondary electrons) and our microtopographic scan (made with backscattered electrons) of a sample in which 60- μm glass spheres are mounted in silver epoxy: (a) SEM scan. (b) Higher magnification SEM scan at an oblique angle. (c) Microtopographic scan corresponding to SEM scan (a).

Fig. 4-64. (a) Orientation of the backscattered-electron detectors, electron beam, and sample for height measurements. (b) Origin of the width measurement error due to shadowing.

exaggerations are due to the geometry of the detectors in relation to the samples, as described below.

Figure 4-64 shows the orientation of the four silicon diode detectors used in measuring the backscattered electrons. In designing the system we chose to use a 45° angle in order to obtain good height sensitivity. The original algorithm⁵⁷ for calculating height is based on a 30° angle; however, the correction for 45° is easily made once the system characteristics are measured. To obtain a 45° angle we placed the sample 15 mm below the detector plane [Fig. 4-64(a)]. Controls on the sample stage allow us to vary this distance from 8 to 22 mm. At 8 mm the height measurements are 2-1/2 times the actual heights, and at 22 mm the heights are only 60% too large. A distance of 30 mm would be required to provide the 30° angle assumed in the original algorithm, but 30 mm is not obtainable with this stage because of mechanical limitations. The trend of the data indicates that the height measurements would be correct with a 30-mm distance.

Errors in measuring the width of a defect occur when a portion of the defect blocks the backscattered electrons from the detector [Fig. 4-64(b)], creating shadow zones. When such blockage occurs, the system cannot correctly calculate heights (and hence widths), and a sloped line results on the display. For a spherical defect, the length of the shadow is governed by the geometric angle of the detector system, as shown in Fig. 4-64(b). Our use of 45° for the geometric angle, rather than 30° , has made this problem worse, and therefore we may go back to 30° . Outside these shadow zones, valid height (and width) measurements are obtained.

With the microtopographic system, accelerating voltages from 10 to 40 kV and beam currents from 100 pA to 20 nA produce a height measurement error of less than 5%. The only limitation on these parameters is the need to keep backscattered signal intensities high enough to be detectable. We normally observe signal-to-noise ratios of better than 100 at the standard operating conditions of 20 kV and 0.5 nA of beam current.

We have made additional tests to evaluate the system. Defects 30 nm high and $0.17 \mu\text{m}$

wide on a heavily gold-coated sphere are shown in Fig. 4-65. Although 30-nm-wide cracks in the gold are not seen in the topographic reconstruction, all three bump defects are easily resolved. Low and wide features, $<10 \text{ nm}$ wide, which are not visible in the conventional SEM scan made with secondary electrons, are revealed in the topographic reconstruction made from the backscattered electron scan.

A small $0.25\text{-}\mu\text{m}$ particle on a chip of glass is shown in Fig. 4-67. The feature of note here is the capability of detecting both a small particle at a lower magnification and the long $10\text{-}\mu\text{m}$ waves of the glass fracture. This detection of $0.25\text{-}\mu\text{m}$ -amplitude waves having $10\text{-}\mu\text{m}$ spatial width and no distinct features at the edges is beyond the capability of the SEM operating in its normal mode; thus we have extended the region of the SEM's applicability into the regime formerly reserved for interferometer methods, which are well adapted for measuring subtle defects. The ultimate height sensitivity of our SEM adaptation should be near 1 nm.

A continuing problem with SEM examinations of samples made of glass and other insulating materials is the severe image distortion caused by electrostatic charges that build up on the surface of the samples. One way around this problem is to cover the sample surface with a conductive coating, but in many cases such a coating is not

Fig. 4-65. High resolution test of the microtopographic system, showing 38-nm-high defects and 13-nm waves on a gold-coated sphere; 30-nm-wide cracks in the gold, visible in the SEM picture, are below the spatial resolution limit of the microtopographic instrument and are not detected.

desirable, and analysis must be performed on the sample in spite of the static charging. Figure 4-66 shows a typical example of how a static charge on the surface of an uncoated glass sphere affects the SEM picture. The

conventional secondary-electron SEM scan shows what appear to be drastic defects and wide gray-level variations which hide detail in most of the image; these are not real features on the sample surface, but rather are image distortions caused by the strong effect of the static surface charge on the low-energy (5-eV) secondary electrons. But the backscattered electrons in our microtopographic system have energies approaching 20 keV, and hence they are little affected by static charges. Thus the backscattered electron scan is free of the distortions seen in the secondary electron scan, with the result that it detects both the large defect and a barely noticeable smaller one to the upper left.

Having demonstrated that we can effectively measure small defects, we have included a "root-mean-square-and-arithmetic-average" finish-measuring routine in the software. Figure 4-68 shows the surface of a platinum-coated sphere characterized by large defects and a small amount of roughness. In an area between the

Fig. 4-66. (a) SEM scan of a portion of the surface of an electrostatically charged glass sphere produces a distorted image in which defects are hidden. (b) Microtopographic scan of same portion of charged sphere reveals two defects, the larger of which is $4.4\text{ }\mu\text{m}$ high.

Fig. 4-67. (a) High-magnification scan shows $25\text{-}\mu\text{m}$ -wide defect on surface of glass chip, but no other features. (b) Lower magnification SEM scan of the glass chip, showing area scanned in (a). (c) Microtopographic scan of area in (a) shows the defect as well as larger wavelike features.

large bumps the microtopographic system measures the correct surface finish of 30 nm, is verified by the oblique SEM shot. Slopes are favorable, so even the widths are measured correctly. A microtopographic analysis takes only 2 minutes, whereas almost 30 minutes is required for comparable data by the two-shot method.

The microtopographic system has demonstrated rapid surface measurements on statically charged and opaque samples, and it has also increased the analysis range of the SEM. One of the limitations to the speed of analysis is in having to make two scans per area in order to set up the scales of the graphics terminal. Addition of a disk storage system large enough for one frame will permit scaling after the data has been taken, as well as curve-fitting to improve roughness calculations. We are also developing faster software and investigating alternate detectors with better gain characteristics.

Ultimately this system could be coupled with a 4π stage to obtain full-surface measurements on target spheres and provide

a unique high-resolution surface mapping capability for target selection.

Author: C. M. Ward

Major Contributors: D. L. Willenborg, D. W. Perkins, G. J. Greiner, E. A. Pyle, and G. F. Jacobson

Microsectioning

We have extended our metallographic lapping techniques to cut cross sections through uncoated, plastic-coated, and metal-coated hollow glass microspheres. The example in Fig. 4-69 shows the cross section of a gold-coated glass microsphere.

Examining such sections aids in target development by revealing the dimensions, uniformity, and internal structure of the glass shells and coatings (Figs. 4-70 to 4-74).

Fig. 4-68. Platinum-coated sphere with 30-nm surface finish. (a) Oblique SEM scan shows major defects. **(b)** Higher magnification SEM scan shows details of surface roughness between large defects. **(c)** Microtopographic scan agrees well with SEM scan in (b).

Fig. 4-69. Optical view of cross-sectioned glass microsphere with gold coating.

Fig. 4-70. SEM view of extreme surface relief caused by variations in hardness between inner glass shell, thin copper coating, and outer CF layer. ▼

Fig. 4-71. SEM view of properly lapped section of glass shell with gold coating, showing little surface relief except for one break in the coating. ▲

Fig. 4-72. Optical view in reflected light of polished section of thick-walled bare glass shell. ►

To obtain the cross section of a microsphere we embed it in a mounting material and then grind away the mount and sphere together until we have ground half way through the sphere. The small size of target microspheres makes them hard to locate and identify when incorporated in a relatively massive piece of mounting material. In order to be able to see and locate the sphere optically we need a transparent mounting material. Location is sometimes aided by centering the sphere in a small plastic ring included in the mount.

Because a bare glass shell in a transparent medium looks very much like a bubble, the transparent mounting material should have a minimum of bubbles. Successful mounting materials include epoxy, polymethyl methacrylate (PMMA), cast Lucite, and sintered polyvinyl chloride (PVC). The sphere can be kept from floating away in the uncured (liquid) mounting material by sticking it down with double-sided tape or precasting it into a thin sheet of Lucite or PMMA which is then incorporated in the mounting material.

Polymer-coated microspheres require a mounting process without solvents, because solvents might dissolve or soften the coating. Both cast Lucite and PMMA use strong solvents, so epoxy and sintered PVC are preferred. Mounting a sample in PVC exposes it to pressures of 4000 psi and temperatures of 125°C in the sintering process, which can damage some coatings. In such cases epoxy mounts are used, in spite of the problems with entrained bubbles.

We do the grinding and polishing on metallographic paper with SiC grit bonded to it and on cloth loaded with diamond grit, in either water or oil suspension. The large

differences in hardness between glass shells, metal coatings, and polymer coatings can result in large differences in cutting rates. Figure 4-70 shows an example of a glass sphere with copper and CF coatings that has been ground slowly on a napped cloth; the extreme surface relief due to the uneven cutting rates has caused the glass to break.

We can minimize this problem by grinding rapidly with fairly coarse diamond grit on a hard napless cloth. A sequence of 600-grit SiC paper followed by 9- μm diamond on nylon cloth and a short final polish with 3- μm diamond results in much less surface relief, as shown in Fig. 4-71. We backfill very thin-walled glass spheres with epoxy, after grinding through the wall, to provide support and prevent breakage. Even so, the reliability of sectioning fragile or complex targets is still in need of improvement.

The transparent mount gives us a means of determining when we have ground halfway through the sphere and reached the midplane, which is the only section of the sphere that shows the true wall thickness. Viewing the ground-away side of the sphere in reflected light, as in Fig. 4-72, shows the flat polished surface of the section. Viewing the sphere in transmitted light, as in Fig. 4-73, outlines the equator of the sphere (i.e., outer circle of the midplane section of the sphere). When the two views coincide, so that the outer circle of the exposed section coincides with the equator, we know we have reached the midplane and have a section that shows the layers in true thickness. A sequence of double exposures with reflected and transmitted light in Fig. 4-75 shows this approach to the midplane.

The techniques described here produce accurate cross sections with high reliability ($\sim 90\%$) as compared with previously reported techniques,⁵⁸ which gave a very low

Fig. 4-73. Optical view in transmitted light outlines equator of glass shell.

Fig. 4-74. Optical cross-sectional view of glass microsphere with CF coating.

Fig. 4-75. Sequence of optical double exposures showing the ground-away section of a sphere (viewed with reflected light) together with the outline of the sphere's equator (viewed with transmitted light). (a) Section part way into sphere. (b) Section nearing equator. (c) Section at the equator.

Cryogenic Systems Development

Fig. 4-76. SEM view of cross-sectioned glass shell with Pt coating. Shell has been backfilled with epoxy to support the wall.

yield (<1%). As Figs. 4-74 and 4-76 show, after a sphere is sectioned, it is examined with either an optical or electron microscope to determine dimensions and defects in the sphere and coatings.

Author: W. G. Halsey

Major Contributors: A. T. Buckner, V. K. Chen, D. Diaz, C. W. Hatcher, L. E. Lorensen, E. A. Pyle, and A. R. Ulrich

Cryogenic Systems Development

Introduction

The Cryogenic Systems Development Group has continued a series of projects from last year, aimed at (1) developing techniques for fabricating ICF targets containing condensed D-T fuel, and (2) supplying the cryogenic support systems necessary for performing implosion experiments on these targets in the laser target chamber. One

project is experimenting with fill tubes and frozen granules of hydrogen isotopes as possibilities for forming thick fuel layers in advanced targets. Another is studying the structure and dynamics of fuel layers formed by a fast-refreeze technique in bare and coated glass microspheres. Still another is designing and testing cryogenic hardware for holding and positioning cryogenic targets, and for shielding them from infrared room-temperature radiation. In addition to these continuing projects, we have begun to study the compatibility and survivability of target materials at cryogenic temperatures.

Solid Hydrogen Granules

In our 1979 Annual Report⁵⁹ we discussed our initial efforts to evaluate the use of ultrafine granules of frozen hydrogen isotopes to fill spherical annular spaces in advanced ICF targets, and we described the apparatus that we constructed to produce this granular material. Briefly, a jet of liquefied hydrogen is broken into uniform droplets by means of a piezoelectric transducer, and the droplets are frozen into spherical granules by evaporation in a low pressure atmosphere. The frozen granular material can then be packed into spaces left for it in target structures.

Last year we had run the apparatus to begin to study the operating parameters. We have now improved the optics for the system so that we can see the jet breakup and the individual droplets, and determine the effect of piezoelectric frequency on droplet size and spacing.

Representative results are shown in Fig. 4-77. The nozzle tip, visible at the top of each photograph, is about 1 mm across at the end. The jet diameter is about 8 μm , and the droplets have diameters of about 7 μm . Figure 4-77(a) shows the liquid jet with the

Fig. 4-77. Jet of liquid hydrogen is broken up into droplets for freezing into solid spherical granules. (a) Jet breakup as caused by natural instabilities. (b) Breakup caused by piezoelectric transducer at 105 kHz. (c) Breakup by piezoelectric transducer at 216 kHz.

piezoelectric transducer not operating; here the jet breaks up at random as a result of natural instabilities. The transducer is on in Fig. 4-77(b) and (c). In theory,⁶⁰ the spacing between droplets should vary as the reciprocal of driving frequency, which is the approximate behavior observed as we vary the drive from 105 kHz in Fig. 4-77(b) to 216 kHz in Fig. 4-77(c).

The droplet radius should vary as the one-third power of the reciprocal of the drive frequency, so we would expect the droplets to be smaller in Fig. 4-77(c) than in Fig. 4-77(b). This does appear to be the case, although the difference in diameters should be only about 1.5 μm , which is beyond the resolving power of the optics.

Our experience with this system led us to design a completely new, compact microdroplet generator with improved pressure regulation, better optical and mechanical access, greater flexibility, and cleaner vacuum systems. We will also incorporate in this new system a cryogenic catcher for the frozen granules, something we were not conveniently able to do with the original system. The new generator and the cold catcher are currently under construction.

Author: T. P. Bernat

Major Contributors: B. H. Ives, M. J. Moss, and K. Kim (University of Illinois)

Formation of Condensed Fuel Layers

Liquid Layers Inside Spherical Shells. We have been studying the structure of layers of liquid D_2 and D-T condensed on the inside surfaces of hollow glass microspheres. The structure is strongly affected by the thermal environment of the microsphere, as was pointed out by Henderson et al.⁶¹ In our own earlier work,⁶² at the University of Illinois, liquid D_2 was formed on the interior of glass microspheres exposed to a cold gas jet. In this arrangement we were able to make use of thermal gradients around the sphere to form rather uniform layers. We found that at temperatures well above the triple point, uniform layers were formed even when the thermal gradients were small. We now believe that the thermal gradients in these

early experiments were not small. On the basis of new experiments done at LLNL, we believe that liquid layers formed in an isothermal environment exhibit a substantial gravitational sag from the liquefaction point to the triple point.

We performed the new experiments in a cryogenic cell designed to provide a uniform temperature environment. The body of the cell, made of thick OFHC copper, was attached to a commercial cryostat whose temperature could be controlled within 0.01 K from 20 to 40 K. The windows on the cell for optical access were an infrared-absorbing Schott glass that prevented any room-temperature radiation from reaching the test microsphere. We mounted two silicon diode thermometers on opposite ends of the cell to look for any temperature gradient. During the experiments, these thermometers always agreed to within their calibration accuracies, indicating an isothermal cell.

Inside the cryogenic cell we mounted a hollow glass microsphere (140 μm in diameter, with 6- μm -thick walls) filled with 20 mg/cm^3 of D-T. The sphere itself was supported between two 50-nm-thick Formvar films, and 200 to 300 mTorr of helium exchange gas provided thermal contact between the sphere and the cell. We aligned the windows of the cell with the probe branch of a Mach-Zehnder interferometer, using an argon ion laser as the illumination source, and projected an interferogram of the microsphere onto a vidicon camera for storage on magnetic tape, as shown in Fig. 4-78. (The heating laser shown in the figure was not used in these experiments.) We also made photographs by replacing the vidicon with an ordinary camera.

Figure 4-79 shows typical results of our study. Figure 4-79(a) is an interferogram of the microsphere at 39 K, above the liquefaction point for the fuel. In making this interferogram, a linear phase gradient was added to the reference beam to correct for a slight imperfection in the microsphere,⁶³ giving rise to the fringe lines in the background. This gradient was held constant for Figs. 4-79(b) and (c), which are interferograms at 30 and 20 K, respectively. In all three photographs, the center of the bull's-eye pattern corresponds to minimum optical path length; for Figs. 4-79(b) and (c), the

Fig. 4-78. Arrangement of Mach-Zehnder interferometer and target-heating laser.

Fig. 4-79. Interferogram of liquid D-T layers showing gravitational sag. (a) 39 K, no liquefaction. (b) 30 K. (c) 20 K.

optical path includes the liquid layer. In Fig. 4-79(b), the center of the pattern has shifted upward by 10% of the target radius; in Fig. 4-79(c), it has shifted upward by 19% of the radius. This pattern shift indicates that the liquid layer is becoming steadily thicker at the bottom of the sphere as its average thickness increases with decreasing temperature.

A completely accurate profile of the liquid layer might be obtainable from the interferogram using ray-tracing codes. However, much can be gained from simpler first-order calculations. We have modeled the D-T layer inside the sphere as shown in Fig. 4-80. The glass sphere is assumed to be perfect, or to have at most a concentricity defect that is removable by the phase gradient technique.⁶³ We assume the inner surface of the D-T to be a sphere, with its center offset from that of the outer sphere by an amount e . By an extension of the work of Stone et al.⁶⁴ to this case, we have calculated that

$$e \approx Q [L + T(N' - 1)/(N - 1)] \quad (6)$$

where Q is the distance that the center of the interference pattern has moved upward, expressed as a fraction of the target radius, T is the glass wall thickness, L is the average thickness of the D-T layer, and N and N' are the refraction indices of the D-T and the glass, respectively.

The approximations made in deriving Eq. (6) are that the shell and layer are both thin, and that e is small compared to both the target radius and the thickness L . For the layer at 30 K, L is approximately $1.3 \mu\text{m}$, and e calculates to be $2.7 \mu\text{m}$; for the layer at 20 K, L is $2.6 \mu\text{m}$ and e calculates to be $4.5 \mu\text{m}$. In both cases, the calculation of e is inaccurate, since the answer violates the condition $e < L$. We can only draw the conclusion that at neither temperature is the

liquid D-T shell even close to being uniform in thickness, and that in fact the thickness of the layer at the top of the shell is much less than $1\text{ }\mu\text{m}$. This is consistent with our estimate of a thickness of only 100 nm at the top of the shell, based on a best guess of the van der Waals attraction between the glass and the D-T.

We have seen this gravitational sag of the liquid layers at all temperatures below the liquefaction point (34.5 K). However, we have never seen any interference pattern that could be interpreted as being due to a meniscus; this observation is consistent with a zero-degree contact angle between D-T and glass at all temperatures down to the triple point, and with a fairly smooth transition region between a profile determined by surface tension effects and one determined by van der Waals attraction between the D-T and the glass substrate.

We can conclude that, since surface tension is never strong enough to cause a D-T droplet to form, uniform layers of solid D-T could be created by allowing a target to free-fall in a cryogenic tower. We can also conclude that targets containing uniform liquid layers of D-T must necessarily contain designed-in thermal gradients.

Fill Tubes for Cryogenic Targets. Some multilayered, high-gain target designs incorporate thick annular layers of solid D-T fuel and in some cases a voidless solid or liquid igniter core. Fuel filling by the current high-temperature diffusion technique will be inapplicable to such targets, since most of them are not based on a glass fuel capsule and since the fill pressure may exceed the bursting strength of the capsule. (With the diffusion technique, a voidless fill would require a fill pressure in excess of 1000 atmospheres). Also, we doubt that the technique of rapid vaporization and refreeze of the fuel to form uniform layers of solid D-T will scale to large targets with

high fuel fills, and it may not be useful with smaller targets with thick ablative layers on the exteriors.

One approach that may overcome many of these problems is to feed the fuel into the target microsphere in gaseous form, through one or more small fill tubes, with the microsphere kept cold enough to condense the gas on the inside. We have been investigating the applicability of this technique in layering and voidless filling. Our initial experiments were performed with a 1-mm-diam blown glass microsphere equipped with a 0.05-mm-i.d. fill tube, in the cryogenic chamber of a variable-temperature cryostat described in the 1979 Annual Report.⁶⁵ We introduced purified hydrogen gas into the sphere through a vacuum-jacketed capillary that passed through the liquid helium reservoir. The capillary was kept free of frozen hydrogen by an interior concentric wire heater, which also allowed control over the temperature of the entering hydrogen gas.

Figure 4-81 shows the results of these first efforts. In Fig. 4-81(a) the sphere is partially

Fig. 4-80. Offset sphere model for liquid layers. Center of the inner surface is at a distance e above the center of the outer surface. N and N' are indexes of refraction.

Fig. 4-81. Experiments with fill tubes. (a) Partial liquid fill. (b) Liquid and solid together. (c) Thin solid layer formed from the gas phase. ▼

filled with hydrogen liquid condensed from gas fed in through the capillary. Liquid was prevented from condensing in the capillary itself because of a temperature gradient established by the incoming gas.

Figure 4-81(b) shows the sphere completely filled with condensed hydrogen. The bottom half of the hydrogen is solidified, with liquid in the top half. A meniscus, concave from above, is clearly visible. We were able to solidify the entire amount of hydrogen without creation of any voids due to contraction. This result, again, depended on allowing no solid to form in the fill tube and block it.

Figure 4-81(c) shows the results of solidifying a layer of hydrogen on the inside of the sphere directly from the gas phase. To do this, we reduced the sphere temperature to about 10 K before introducing the gas. In this case the fill tube did eventually clog with solid hydrogen.

In further work we will experiment with techniques of keeping the fill tube clear even

when condensing into the sphere below the triple point, and without developing temperature gradients in the sphere. We will also investigate the effects of temperature and condensation rate on the homogeneity and smoothness of the frozen layer.

Finally, we are constructing test spheres with thinner walls and of higher optical quality, with much smaller fill tubes than those in our first experiments. Using a Nd:YAG laser we have drilled 50- μm holes in 1-mm-diam $\times$ 6- μm -wall glass spheres that were made by the dried-gel technique here at LLNL.⁶⁶ One such sphere, held by a vacuum chuck and with a hole already drilled, is shown in Fig. 4-82(a). We have been able to attach 50- μm -o.d. fill tubes to the sphere with a quick-setting epoxy, as shown in Fig. 4-82(b). The resulting joint is vacuum-tight, even after repeated rapid cycling between room temperature and liquid nitrogen temperature. These new spheres will be used in layering experiments in the near future.

Condensed D-T Layers Inside Multilayer Targets. Some proposed high-yield cryogenic targets consist of polymer-coated glass microspheres with the D-T fuel frozen out in a solid layer on the interior wall of the microsphere. To ensure high yield the ablation-driven shell implosion must be highly symmetric, necessitating a smooth, uniform fuel layer. We have begun a systematic investigation of solid D-T layer formation on the inside of polymer-coated glass microspheres, with the object of determining the optimal conditions for uniform layer formation (Figs. 4-83 to 4-86).

When a target filled with D-T gas is slowly cooled to cryogenic temperatures by reducing the temperature of its environment, a highly nonuniform frozen D-T layer forms. Rapid cooling is important in obtaining a uniform layer. Previous to our investigation, two techniques for forming uniform layers inside bare glass microspheres had been developed, one at LLNL⁶⁷ and one at Los Alamos.⁶⁸ Both techniques cool a D-T-filled target well below the condensation temperature, then subject it to a brief heat pulse from an external heater or heating laser, which revaporizes the D-T fill. After the heating pulse, the target cools rapidly again, resulting in the formation of a uniform D-T layer by rapid refreeze to the target wall.

Fig. 4-82. (a) Thin glass sphere 1 mm in diameter with a 50- μm laser-drilled hole through the wall. (b) Fill tube 50 μm in o.d. epoxied in place.

The rate of target cooling and layer formation is determined by the time-dependent transport of heat from the D-T fill through the target walls into the surrounding helium exchange gas. The heat of sublimation liberated by the condensing D-T fill is an order of magnitude greater than the total enthalpy change of the rest of the target in going from 20 to 10 K. This heat liberated due to phase transformation represents a principal thermal driving force in the dynamics of layer formation. During layer formation, if a liquid layer is present it must freeze in less than the sag time (time in which the fluid layer is redistributed under the influence of gravity) in order to avoid creation of an undesirable layering thin at the top and thick at the bottom.

We were concerned that the presence of a thick polymer coating on the glass

microsphere might increase the thermal time constant enough to cause significant layer nonuniformity from too slow a refreeze. To test this possibility, we experimentally investigated solid D-T layer formation in a 140- μm -diameter glass microsphere with a 5- μm wall and a 15- μm CF plastic coating. The target tested had 11 ng of D-T fill, which if frozen out uniformly could produce a 1.4- μm solid layer.

We mounted the target between two 50-nm parylene films pressed between two copper washers and suspended it in a temperature-controllable cryogenic chamber. (This system has been described previously in the 1977 Annual Report.⁶⁹) Thermal contact between the target and the surrounding cryogenic chamber is maintained with low-pressure (typically 200-mTorr) helium exchange gas. We

Fig. 4-83. Geometry of illumination of target by heating laser.

determine the uniformity of the frozen D-T layer by optical interferometry, using 488-nm light from an argon ion laser. The transparent target is placed in the optical path of one arm of a Mach-Zehnder interferometer, as diagrammed in Fig. 4-78. The microscope objective used to image the target is also used to focus a 632-nm light pulse from a He-Ne heating laser onto the target, to vaporize the D-T fill.

The geometry of the heating laser's illumination of the target is shown in Fig. 4-83; energy deposition is confined to two end caps comprising roughly 40% of the shell area. This arrangement reduces laser energy loss due to first-surface reflection, by not allowing large angles of incidence of the laser light on the target surface. The energy

deposited by the heating laser must vaporize the fill rapidly, to avoid diffusion heating of the ambient exchange gas and cryochamber. Absorption of laser energy at optical wavelengths by target materials is quite low. For the target previously mentioned, we have determined that less than 5% of the incident 632-nm radiation is absorbed. This determination was made at room temperature (300 K); it represents an upper limit on absorption efficiency due to our inability to measure the amount of reflected laser light.

Determination of D-T layer structure from optical interferograms of thick-walled, multilayered targets is a complicated process, involving ray tracing and requiring two or more viewing angles to remove projection ambiguities. Interferometric information about the frozen fuel layer near the edges of the target image is especially difficult to extract. The bulk of the optical path difference (OPD) accrued by light in passing through the target is due to passage through the polymer and glass layers, which have relatively high refraction indexes; passage through the solid or vapor D-T fill with its relatively low refraction index makes only a minor contribution to the total OPD. Consequently, when we cool the target and freeze out the vapor as a solid layer, the resultant shift in interference fringes is due to small OPD shifts produced by rearrangement of the fill.

For a spherical fuel capsule with minimal concentricity defects, a bull's-eye interference pattern results, indicating a high degree of spherical symmetry. Such a pattern is evident for the target we tested, Fig. 4-84, when the D-T fill is maintained in the gas phase (temperature above 35 K). When we slowly cooled the target below the D-T triple point, an extremely irregular solid layer usually formed, producing a disordered interference pattern such as is shown in Fig. 4-85. But when we used the technique of cooling the gas-filled target well below the condensation temperature, heating it briefly with a laser pulse to vaporize the condensed fuel, then letting it cool rapidly again to refreeze the fuel, we obtained an interferogram typified by Fig. 4-86, indicating formation of a smooth solid layer of D-T.

While we are able to "eyeball estimate" that the layer is smooth to perhaps 0.1 μm by

Fig. 4-84. Interferogram of target with D-T fill in vapor phase, temperature 30 K. White outline indicates out-of-focus edge of microsphere.

Fig. 4-85. Interferogram of target after slow cooling to 10 K: irregularity of interference fringe pattern indicates presence of nonuniform solid D-T layer.

Fig. 4-86 After 1-second exposure to He-Ne heating laser, interferogram of target at 10 K indicates presence of smooth layer of solid D-T.

examining the interference fringes, we unfortunately can say little about the "P1 defect," or offset of the center of the solid fuel shell from that of the fuel container. Determination of this offset would provide an estimate of the fuel thickness difference between the top and bottom of the target. If we use the approximate analysis described for liquid layers in the early part of this article and summarized in Eq. (6), we find for our experimental target—assuming the refractive index of both glass and plastic to be 1.5 and that of the fuel to be 1.14, and assuming a fuel layer of average thickness $2\text{ }\mu\text{m}$, but with the top only $1\text{ }\mu\text{m}$ thick and the bottom $3\text{ }\mu\text{m}$ thick—that the center of the bull's-eye fringe pattern would be shifted by only 1.4% of the radius. This shift is below the limits of our detection ability. The insensitivity of the position of the center of the fringe pattern to shifts in the center of the fuel layer is a result of the minor perturbation that the low-refraction-index fuel layer represents in the total optical path length through the thick-walled, high-refraction-index fuel capsule. This observation points up the need to develop characterization techniques that are sensitive to the fuel layer alone, rather than to the fuel capsule. One possibility that we are pursuing is real-time holographic interferometry. This capability in conjunction with computer ray-tracing codes should allow accurate layer determination at the 5 to 10% level.

We anticipate a number of problems associated with cryoforming D-T layers in thickly coated targets by the laser pulse technique, problems whose effects we should be able to evaluate more easily with an improved ability to determine layer structure. For example, under irradiation from the heating laser, the target may possibly develop both radial and angular temperature variations as a result of differences in optical absorption of various target components, or as a result of nonuniform target illumination by the heating laser beam. An angular distribution of temperature, if present, will serve as an initial boundary value for the subsequent target cool-down. The persistence of such an initial temperature distribution during subsequent cool-down could cause nonuniform freezing and resultant layer nonuniformity.

Since the glass microspheres are filled by diffusion at elevated temperatures (i.e., the empty microspheres are put in a pressure chamber that is filled with D-T, and the pressurized D-T forces itself through the walls of the glass spheres to get to the inside), the final equilibrium fill consists of a mixture of D_2 , D-T, and T_2 . Components of this mixture could separate out upon cooling to produce isotopic inhomogeneities and nonsphericity in the fuel layer. Rapid enough freezing should prevent the formation of such compositional inhomogeneities, but we do not know the relevant time scales.

We think we could obtain detailed information about layer formation dynamics from thermal transport codes if accurate thermophysical data for target materials were available. Unfortunately, accurate data on the wavelength-dependent relative or absolute optical absorption coefficients of the CF polymers, glass shell, and solid D-T target components is not readily available. Such information would allow us, for example, to make predictions about laser heating efficiency at $1.06\text{ }\mu\text{m}$ from data we have obtained at 632 nm. Accurate thermal diffusivity data for target component materials as well as values for thermal boundary resistance are also necessary for either precise computer modeling or approximate analytic treatment of thermal transport and layering. We are therefore undertaking the experimental determination of low-temperature thermal and optical properties of shell materials.

Our ultimate objective is to investigate the statistics of fuel layer uniformity for any target as a function of system parameters, in order to determine optimum operating conditions. Parameters which may be varied include exchange gas pressure; cold-chamber wall temperature; heating-laser wavelength, power, and pulse length; and target illumination geometry. A statistical confidence level for a certain degree of D-T layer uniformity in a cryogenic ICF target is required, since preshot in situ determination of layer uniformity may not be feasible.

Authors: T. P. Bernat and D. H. Darling

Major Contributors: B. H. Ives and K. Kim
(University of Illinois)

Cryogenic Target Systems

We have continued in our efforts to develop the hardware and "life-support" systems to allow irradiation of cryogenic ICF targets in a laser target chamber. This hardware consists of (1) a cryogenic target mount, or pylon, for holding, cooling, and positioning the target, and (2) a retractable cryogenic shield which can cover a target to supply cooling through an exchange gas, and which at the same time protects the target by intercepting ambient radiation. Both the cryogenic pylon and the retractable shield are being developed, fabricated, and tested through a cooperative effort with the National Bureau of Standards in Boulder, Colo.

Cryogenic Pylon. As we reported in our 1979 Annual Report, a prototype pylon had been built and its cryogenic performance had been tested.⁷⁰ We have modified the design of this apparatus so that it can be inserted into the Shiva target chamber with minimum impact on the present target-positioning system. This required the inclusion of a vacuum-sealed ball joint in the outer tube of

the pylon to allow some flexing as the pylon, with target installed, is pushed through the guides in the target-positioning mechanism, on its way into the target chamber. The ball joint design is shown in Fig. 4-87.

We have also redesigned the cryogenic tip of the pylon to allow easier mounting of targets. Since the cryogenic pylon, once in use, will have to support all targets shot, both cryogenic and noncryogenic, its design is fairly crucial. We have chosen a conical friction mount, as shown in Fig. 4-87. The male and female portions of the mount are made from OFHC copper for high thermal conductivity, and are both lapped against tool-steel mandrels. When they are engaged dry, as they would be for noncryogenic targets, and with the 3° taper shown in Fig. 4-88, a steady pull of 1.9 kg is required for separation. Sealing these mating parts with a soap-glycerine mixture, which is commonly used for demountable cryogenic seals, increases the separation resistance to 2.4 kg. We have also included a bayonet-type pin for positioning the target.

Finally, we have redesigned the drive system for radial motion of the target holder to allow for vacuum-insulated cryogenic

Fig. 4-87. Cryogenic pylon with new drive mechanism and ball joint.

Fig. 4-88. Target mounting arrangement for cryogenic pylon uses mating copper parts held together by friction.

lines along the axis of the pylon, as shown in Fig. 4-87. Heavy acme drive threads are machined into the vacuum housing of the pylon, which allow a coaxially mounted stepping motor, under computer control, to advance or retract the pylon. We also redesigned the linkage between the stepping motor and the pylon to facilitate this drive mechanism.

As of this writing, the redesign is complete, the parts have been fabricated, and our colleagues at NBS in Boulder are assembling the final version of the cryogenic pylon. We anticipate its use in either the Shiva or Novette systems in the near future.

Cryogenic Shield Retractor. While the first cryogenic targets we shoot will require only the cryogenic pylon, subsequent targets will require shielding against ambient radiation. As we discussed in our 1979 Annual Report,⁷⁰ this shielding must be rapidly removed from the target a few tens of milliseconds before the shot. A prototype shield and retractor, developed at NBS in Boulder, underwent initial mechanical and thermal testing last year. NBS made use of the test results to improve the design, which now gives substantially better performance.

The cryogenic end of the assembled prototype is pictured in Fig. 4-89. The target shield is the small cylinder with windows, at the tip of the structure. (A thermocouple has been installed for test purposes.) The gold-coated shield is soldered to a thin aluminum sleeve, which is also gold-coated on the outside for high reflectance, and which is thermally coupled (by helium gas) to an internal coaxial cryogenic cold finger. In the retracting operation, the aluminum sleeve slides at high velocity over the cold finger. We have coated both the interior of the outer aluminum tube and the exterior of the cold finger with nickel to prevent galling. A dry lubricant between the two also facilitates easy motion.

In operation, we retract the shield by applying a sudden current to an internal electromagnet, which imparts a large impulse to a repulsion plate attached to the aluminum sleeve. The sleeve slides back over the cold finger and locks into place with a latching mechanism. In so doing, it collapses a metal bellows that serves to contain the exchange gas surrounding the cold finger, and to absorb the impact of the moving shield. The bellows are visible in the opening of the outer copper case in Fig. 4-89.

Among the changes to the original prototype were a harder aluminum alloy for the magnetic repulsion plate, a longer stack of bellows, and the addition of a stainless steel spring around the bellows to provide sufficient restoring force so that the shield could be returned to its full forward position upon unlatching. After these modifications, it was necessary to remeasure the retraction time. In a sequence of ten such measurements, the shield always cleared the target in well under 3 ms. The mechanism failed to latch in one test, but it left the target exposed for about 20 ms, which should be long enough to fire the laser.

The thermal performance of the shield and retractor is now reproducible and adequate. The shield routinely attains a temperature of

Fig. 4-89. The cryogenic shield and retractor.

around 10 K when fully exposed to ambient thermal radiation. In future tests, we will determine the ability of the shield to provide total cooling to a target held on a room-temperature, insulated mount.

Author: T. P. Bernat

Major Contributors: D. H. Roberts and P. Ludtke (National Bureau of Standards, Boulder)

Mechanical Survivability of Targets in a Cryogenic Environment

Proposed high-yield ICF targets employ frozen D-T fuel layers. Polymer ablation coatings on the exterior of the glass fuel capsules are often an integral part of such targets. However, cooling to cryogenic temperatures will generate large stresses in the polymer coating and glass shell, due to differences in coefficients of thermal expansion of the two materials. Rapid warming or cooling resulting in nonuniform temperature distributions within the target may generate additional stresses due to differential thermal expansion. If thermally generated stresses are large enough, cracking of the polymer coating may occur, resulting in destruction of the target.

To test the survivability of polymer coatings, we thermally cycled CF- and CH-coated glass microspheres between room temperature (300 K) and liquid helium temperature (4.2 K). We cooled the targets in a probe assembly which we dipped into the liquid helium in a storage Dewar. Helium exchange gas thermally coupled the targets to the cryogen. Target warming and cooling rates were controlled primarily by the rates at which the probe was inserted into and withdrawn from the helium storage Dewar. Temperature was monitored with a thermocouple (Au:Fe-Chromel) suspended in the exchange gas adjacent to the targets.

The CF-coated targets we tested were 140- μ m glass microspheres with 5- μ m walls and 15- μ m polymer coatings (designated "140 $\times$ 5 + 15 CF"), and the CH-coated targets were 140 $\times$ 5 + 15 CH, 200 $\times$ 5 + 25 CH, and 200 $\times$ 5 + 20 CH. Our

pre cycling characterization of the targets consisted of making scanning electron micrographs of two or three representative targets, selected randomly from each batch tested, and making optical photomicrographs of the actual targets cycled. After cycling, all of the targets were again optically photomicrographed. Scanning electron micrographs were then taken of two or three of the thermally cycled targets, randomly selected.

Target cooling rates were maintained at 15 K/min or $\sim$ 250 K/min. Target warming rates were $\gtrsim$ 15 K/min, except for one case where room-temperature air was vented into the system, producing very rapid (and possibly differential) target warming.

Survivability of CF- and CH-coated targets cycled at 15 K/min and 250 K/min was excellent, with no coating failure attributable to thermal cycling. No appreciable differences were noticeable in the optical and SEM photos taken before and after cooling. Nearly complete coating failure occurred for CF-coated targets that were subjected to an extreme warming rate produced by venting of room-temperature gas into the cryogenic target environment. Extensive cracking of the polymer occurred, and shards of polymer shell delaminated from the underlying microsphere.

We will extend our testing of cryogenic survivability to glass microspheres coated with beryllium and noble metals and with thick polymers (up to 100 μ m thick).

Author: D. H. Darling

Target Factory Studies

The fabrication of laser fusion targets involves the processing of metal, ceramic, and organic materials to meet target design specifications. The processing systems required to meet these specifications must also meet target production criteria—e.g., input/output rates, yields, etc. In addition, tritiated fuel for the target must be provided by a tritium processing system. Tritium flow rates and inventories are important factors that must be considered during target production. We have derived mathematical expressions that represent "target factory"

processing systems, to form a basis for a parametric study. The input and output rate of a process system, the efficiency of each step, and the number of process steps and production lines are used to develop an understanding of their effect on target production. These parameters are also used to predict the tritium flow rate and inventory of a production system involving the processing of tritiated fuel.

operating at a rate r_G for a time t_g . For a single production line ($v = m = p = 1$), we can express the rate and yield of each system as follows:

SD&DT System

Input rate: $r_G = G/t_g$.

Output rate: $r_F = F/t_F$.

$$\text{Yield: } F = \left[\prod_{i=1}^u f_i \right] G$$

Target Production

The production of inertial confinement fusion targets may be viewed as consisting of three main processing systems: the shell development and D-T fill (SD&DT) system, the coating process (CP) system, and the cryogenic (CRY) system. As shown in Fig. 4-90, we have represented each as a general production system composed of multiple-step processes. The symbols used in the figure are defined in Table 4-3.

The input of the target factory is based on a droplet generator shell-forming process

Definition	SD&DT	CP	CRY
Number of input items	G	A	C
Number of output items	F	B	I
Rate of input of item to be processed	r_G	r_A	r_C
Rate of output of processed item	r_F	r_B	r_I
Time interval for the slowest process step	t_F	t_L	t_C
Number of processing steps	u	n	s
Number of production lines	v	m	p
Production yield factor	f	y	q

Table 4-3. Definitions of the parameters represented in the target factory diagram.

Fig. 4-90. General production diagram of the three processing systems that make up a proposed target factory.

CP System

Input rate: $r_A = A/t_L$.
Output rate: $r_B = B/t_L$.

$$\text{Yield: } B = \left[\prod_{i=1}^n y_i \right] A$$

Fig. 4-91. Block diagram of a tritium system interfacing a cryogenic process.

CRY System

Input rate: $r_C = C/t_C$.
Output rate: $r_I = I/t_C$.

$$\text{Yield: } I = \left[\prod_{i=1}^s q_i \right] C$$

Using these relationships along with expressions relating the output and input rates between systems, we derive an equation for the target injection rate R into the fusion chamber^{71,72}:

$$R = \left[\prod_{i=1}^s q_i \right] \left[\prod_{i=1}^n y_i \right] \left[\prod_{i=1}^u f_i \right]_p \times \left(\frac{t_g}{t_F} \right) \left(\frac{r_G r_C r_A}{r_B r_F} \right)$$

From an equation of this type we can perform a parametric study to examine how the target production rate is affected by proposed processing systems. By recognizing the production processes that may have difficulty in meeting the requirements for target production, we can focus our research efforts or emphasize more favorable systems.

Tritium System

We have examined the tritium inventories and flow rates of a proposed target factory with regard to production of targets to meet the reactor injection rate for laser fusion. The approach has been to interface a tritium system with the multiple-processing cryogenic system. A basic block diagram of the tritium system is presented in Fig. 4-91. It consists of three sections: fill process and storage, recovery, and tritium source. We have derived parametric expressions for each section in terms of tritium flow rates and inventories resulting from both a pipeline and a production mode of operation.

Fill Process and Storage. In the analysis we have assumed that the target fill takes place within the cryogenic processing steps just before injection into the reactor.^{71,72} Figure 4-92 shows the fill process section interfacing a multiple processing system having an output connected to a storage section. The purpose of the storage is to maintain a supply of targets in case of a production interruption.

Fig. 4-92. General tritium-fill process interfacing a multiple-processing cryogenic system.

We have derived an expression in terms of R for the tritium inventory of the fill process and storage section during the production mode⁷³:

Inventory in fill =

$$\frac{m_f R t_C}{\prod_{i=m}^s q_i} \left\{ 1 + \sum_{i=m}^{s-1} \left[\prod_{j=m}^i q_j \right] \right\},$$

Inventory in storage = $m_f N R t_C$,

where m_f is the amount of tritium per target, and N is the number of times that the fill process section must be activated to supply the storage section with an inventory of targets.

Recovery. Figure 4-93 shows the recovery section as a multiple processing section with x number of processing steps having yield factors represented by r . The recovery section includes a redundant recovery system (RRS) to account for yield factors of $r < 1.0$. The RRS may be thought of as an environmental gas purification or gettering system that can contribute to the recovery output at an efficiency represented by z .

The inventory of tritium in the fill recovery section is the amount within the recovery processing and in the RRS. An expression for the tritium inventory in terms of R has been derived⁷³:

Inventory in recovery =

$$\frac{m_f R t_C}{\prod_{i=m}^s q_i} \left\{ 1 - \left[\prod_{i=m}^s q_i \right] \right\} \left\{ 2 - \left[\prod_{i=1}^x r_i \right] \right\} + \sum_{i=1}^{x-1} \left[\prod_{j=1}^i r_j \right] \left\{ \right\}.$$

Source. The tritium source supplies the fuel to fill targets. Its output is connected to the $s = m$ step of the fill process section. The tritium source section was analyzed as having an output dependent on the rate of target production and an input from both the recovery section and the reactor system.^{73,74} During production the amount of tritium needed in the operation of an ICF power plant is the sum of the inventories of each tritium section in the target factory plus the tritium inventory associated with the reactor system.

Fig. 4-93. Multiple-processing recovery section including a redundant recovery system (RRS).

Target fabrication and target production are areas that must blend together in the concept of a target factory. We are currently involved in studies that will lead to an understanding and development of these areas to meet both target design and target production criteria. Preliminary results have indicated that a parametric study of this type will be important in deciding what factors will have a major influence on the operation and cost of a target factory for laser fusion.

Author: J. W. Sherohman

Fusion Target Development Facility (FTDF)

Facility Planning

Construction of the new Fusion Target Development Facility began in the latter part of the year (see Section 1 of this Annual Report for details of the construction). This facility will consolidate the different groups of Target Fabrication into a central location, providing each group with the particular features necessary for its function in producing advanced targets.

The floor plan for the FTDF, shown in Fig. 4-94, was designed to locate the different laboratories and functions according to their interactions with others in the overall target fabrication operation. For example, the characterization group and the assembly development group, both of which interact

Fusion Target Development Facility (FTDF)

with several of the other groups, are centrally located for easy access. A fuel fill facility is conveniently located between the sphere production and cryogenics laboratories, the logical place for it. The surface analysis laboratory, whose function is essential in coating development, is situated between the two coating laboratories. This type of layout should encourage communications between appropriate groups while minimizing unnecessary traffic.

Several noteworthy features have been included in the design of FTDF to meet the needs of the individual groups within Target Fabrication. The ceiling height in the sphere production laboratory will be 20 feet to accommodate the height of the new high-temperature ovens for fuel capsule production and development. The D-T fueling of targets, which previously has been done in another part of LLNL, will now be performed in our own facility, allowing finer

Fig. 4-94. Floor plan of ▲ the Fusion Target Development Facility (FTDF).

Fig. 4-95. Primary containment for the tritium-handling system is provided by a sealed glove box.

Fusion Target Development Facility (FTDF)

control and monitoring of the procedure. In addition, we can use this facility for research into cryogenic fill techniques necessary for some advanced targets.

Several areas in FTDF will be equipped with vibration-isolated floors, advancing our capabilities for characterization, precision machining, and levitation or handling of targets, and providing optimum conditions for high-resolution Auger spectroscopy and SEM surface analysis. Class 100 clean rooms will be located in the assembly development and characterization areas, providing the proper environment for assembling and examining the delicate targets. There will be toxic chemical work areas in the two coating laboratories, for research into beryllium and organometallic coatings, plus several smaller containment areas or glove boxes for

handling these materials safely. A central computer facility is being designed, which will be available for use by each group.

The new FTDF will provide many of the special laboratory features needed for advanced target fabrication development, in an environment which should be conducive to better communication and cooperation among the different groups.

Author: J. F. Wengert

Tritium Handling

The Fusion Target Development Facility will contain a tritium-handling system for filling target shells with tritiated fuel (Figs. 4-95 to 4-98). This system, which will be

Fig. 4-96. Tritiated waste or effluent is either recovered on a uranium getter bed or stored in a recovery tank.

Fusion Target Development Facility (FTDF)

enclosed in a sealed glove box, will provide for filling of both cryogenic and noncryogenic target shells. The system design is based on current filling technology—diffusion filling of glass microspheres with D-T gas—but it also includes means for filling spheres with higher density (liquid) D-T fuel.

The primary containment system for handling tritium, as shown in Fig. 4-95, is a sealed glove box. Secondary containment is provided for both the tritiated gas source and the target permeation cells. The system was designed according to the redundant valve principle and constructed from certified 316 stainless steel, using the highest quality of testing and inspection.⁷⁵ Construction was by welding, with each joint x-rayed and inspected.

Figure 4-96 shows the method for recovery of the primary waste effluent. The tritiated waste can either be collected on a uranium bed or stored in a recovery tank. In either

case, the tritiated gas can be gettered or stored for recycling.

The effluent recovery system, shown in Fig. 4-97, is a closed-loop, low-pressure gas purification system. Its titanium reactor is used to process the effluent gas stored in the recovery tank, or to process the ambient gas inside the glove box. Secondary containment is provided for the vacuum pump, metal-bellows transfer pump, circulation blower, and titanium reactor.

The complete fill system, as shown in Fig. 4-98, is monitored by auxiliary components—e.g., tritium monitors, and moisture and oxygen analyzers. The primary system can be pressure-checked before each fill, using a helium-deuterium gas supply. A sample-bottle port is also available, for analyzing the content of the tritium gas. In addition, a second vacuum pump and a catalytic molecular sieve reactor are shown attached to the air lock; all the gases from the air lock, recovery system, or glove box

Fig. 4-97. Purification system uses a titanium reactor to process tritium gas stored in the recovery tank or leaked to the atmosphere inside the glove box.

▲ Fig. 4-98. The complete tritium-handling system, showing the auxiliary components that are included as safeguards.

Fig. 4 99. Artist's conception of the tritium-handling system in the Fusion Target Development Facility.

Fusion Target Development Facility (FTDF)

are processed through this reactor before being released to the stack. Finally, a seismic valve is located on the primary gas source for automatic shutoff in the event of a seismic disturbance.

An artist's conceptualization of the finished tritium-handling system is given in Fig. 4-99. The present system (i.e., for diffusion filling of targets) will be contained in one wing of the sealed glove box. The other wing will be used for future cryogenic

research. The design allows for expansion of the system by the addition of still another wing, to form a tee assembly. This tritium handling system is presently under construction and should be operable by the completion date for the Fusion Target Development Facility.

Author: J. W. Sherohman

Major Contributor: D. H. Roberts

1. T. G. Wang, D. D. Elleman, M. C. Lee, and J. M. Kendall, Proposal submitted to DOE by Jet Propulsion Laboratory, California Institute of Technology, Pasadena, Calif.	2. R. L. Morrison, <i>Furnace Physics as Applied to Inertial Confinement Fusion Target Microsphere Production</i>, Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-85172 (1980).	<p>Production of Large Glass Spheres
4-4</p>
3. <i>Laser Program Annual Report—1978</i>, Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-78 (1979), pp. 4-2 to 4-7.		<p>Metal Sphere Development
4-4</p>
4. J. T. Larsen, V. W. Slivinsky, S. M. Lane, and N. M. Ceglio, <i>Diagnosis of Laser Produced Implosions Using Argon X-ray Lines</i>, Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-83313 (1979).	6. <i>Laser Program Annual Report—1979</i>, Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-79 (1980), p. 4-2.	<p>Diagnostic Gas Fills
4-6</p>
5. E. M. Campbell, S. M. Lane, Y. L. Pan, J. T. Larsen, R. J. Wahl, and R. H. Price, <i>Determination of Fuel pR of ICF Targets by Neutron Activation</i>, Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-83073 (1979).	7. Ibid., p. 4-4.	
8. <i>Laser Program Annual Report—1979</i>, Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-79 (1980), p. 4-4.	9. P. C. Souers, R. T. Tsugawa, and R. R. Stone, <i>Fabrication of Glass Microballoon Laser Targets</i>, Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-51609 (1974), p. 27.	<p>D-T Fill Techniques
4-7</p>
10. <i>Laser Program Annual Report—1978</i>, Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-78 (1979), pp. 4-2 to 4-7.	12. <i>Laser Program Annual Report—1977</i>, Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-77 (1978), p. 4-5.	<p>Liquid-Droplet and Dried-Gel Production Systems
4-8</p>
11. <i>Laser Program Annual Report—1979</i>, Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-79 (1980), pp. 4-2 to 4-3.	13. See Ref. 11, p. 4-2. 14. See Ref. 12, p. 5-13.	
15. <i>Laser Program Annual Report—1979</i>, Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-79 (1980), pp. 4-8 to 4-35.		<p>Coatings and Layers—Introduction
4-9</p>
16. J. K. Crane, R. D. Smith, W. L. Johnson, C. W. Jordan, S. A. Letts, G. K. Korbel, and R. M. Krenik, "The Use of Molecular Beams to Support Microspheres During Plasma Coating," Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-84488 (1980), prepared for	submission to the 27th National American Vacuum Society Symposium, Detroit, Mich., October 14-17, 1980. Also <i>Laser Program Annual Report—1979</i>, Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-79 (1980), p. 4-26.	<p>Molecular Beam Levitation Development
4-10</p>
17. <i>Laser Program Annual Report—1979</i>, Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-79 (1980), pp. 4-26 and 4-29.	18. Ibid., p. 4-29. 19. Ibid., pp. 4-8 to 4-13. 20. Ibid., p. 4-9.	<p>Polymer Coatings
4-12</p>
21. <i>Laser Program Annual Report—1978</i>, Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-78 (1979), p. 4-11.		<p>Metal-Seeded Organic Coating
4-16</p>
22. R. L. Seliger, J. W. Ward, V. Wang, and R. L. Kuben, "A High Intensity Scanning Ion Probe with Submicrometer Spot Size," <i>Appl. Phys. Lett.</i> 34, 310 (1979).	23. W. L. Johnson, J. K. Crane, and C. D. Hendricks, "Charged Particle Coating," presented at 27th National American Vacuum Society Symposium, Detroit, Mich., October 14-17, 1980. Also Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-84499 (1980).	<p>Charged-Particle Coating and Milling
4-18</p>
24. <i>Laser Program Annual Report—1979</i>, Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-79 (1980), pp. 4-23 to 4-26.	26. A. Mayer and D. S. Catlett, "Plating Discrete Microparticles for Laser-Fusion Targets," <i>Plating</i> 65, 42 (March 1978).	<p>Copper-Coated Shells
4-20</p>
25. W. E. Reid and F. Ogburn, "The Adhesion of Electrodeposited Nickel to Chromium at Elevated Temperatures," <i>J. Electrochem. Soc.</i> 107, 91 (1960).		

References

Batch Coating Process for Microspheres
4-23	27. S. F. Meyer, "Metallic Coating of Microspheres," presented at the 27th National American Vacuum Society Symposium, Detroit, Mich., October 14-17, 1980. Also Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-84463 (1980).
28. <i>Laser Program Annual Report—1979</i> , Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-79 (1980), pp. 4-17 to 4-23.
29. S. F. Meyer, E. J. Hsieh, and R. J. Burt, "RF Magnetron Sputtering of Thick Pt Coatings on Glass Microspheres," <i>Thin Solid Films</i> 72 , 373 (1980).	30. E. J. Hsieh and S. F. Meyer, "Recent Advances in Pt Coating of Microspheres by a Batch Magnetron Sputtering Process," presented at the 27th National American Vacuum Society Symposium, Detroit, Mich., October 14-17, 1980. Also Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-84478 (1980).
31. C. D. Hendricks, in <i>Electrostatics and Its Applications</i> , edited by A. D. Moore (Wiley, New York, 1973), Ch. 4, pp. 64 to 67.
32. H. A. Pohl, <i>op. cit.</i> , Ch. 14, pp. 336 to 362.
MBL Coating of Soft Metals on Microspheres
4-26	33. S. F. Meyer, E. J. Hsieh, and R. J. Burt, "RF Magnetron Sputtering of Thick Platinum Coatings on Glass Microspheres," <i>Thin Solid Films</i> 72 , 373 (1980). Also <i>Laser Program Annual Report—1979</i> , Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-79 (1980), p. 4-19.
34. J. K. Crane, <i>Molecular Beam Levitation</i> , Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-83379 (1980).	35. A. T. Lowe and C. D. Hosford, "Magnetron Sputter Coating of Microspherical Substrates," <i>J. Vac. Sci. Technol.</i> 16 , 197 (1979).
36. <i>Laser Program Annual Report—1979</i> , Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-79 (1980), p. 4-28.
Advances in Beryllium Coatings
4-28	37. <i>Laser Program Annual Report—1979</i> , Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-79 (1980), pp. 4-14 to 4-17.	38. R. J. Burt, S. F. Meyer, and E. J. Hsieh, "RF Magnetron Sputtering of Thick Film Amorphous Be," <i>J. Vac. Sci. Technol.</i> 17 , 407 (1980).
Double-Shell Technology—Introduction
4-29	39. <i>Laser Program Annual Report—1979</i> , Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-79 (1980), p. 4-29.	
Micromachining of Sputter-Coated Beryllium
4-29	40. <i>Laser Program Annual Report—1979</i> , Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-79 (1980), pp. 4-29 to 4-32.	
Step-Jointed Hemishells
4-31	41. <i>Laser Program Annual Report—1979</i> , Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-79 (1980), p. 4-29.	
Lead-Styrene Hemishells
4-33	42. <i>Inertial Fusion Research Technical Annual Report</i> , KMS Fusion, Ann Arbor, Mich. (in press), Ch. 1.	43. <i>Laser Program Annual Report—1979</i> , Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-79 (1980), pp. 4-29 to 4-32.
Molecular-Beam-Levitated Coating of Second Shells
4-34	44. <i>Laser Program Annual Report—1979</i> , Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-79 (1980), pp. 4-33 to 4-35.
45. <i>Ibid.</i> , p. 4-32.	46. S. A. Letts, D. W. Myers, and L. A. Witt, "Ultrasmooth Plasma Polymerized Coatings for Laser Fusion Targets," presented at the 27th National American Vacuum Society Symposium, Detroit, Mich., October 14-17, 1980. Also Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-84475 (1980).
Microradiography
4-36	47. <i>Laser Program Annual Report—1978</i> , Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-78 (1979), pp. 4-25 to 4-29.	48. <i>Laser Program Annual Report—1979</i> , Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-79 (1980), pp. 4-38 to 4-42.
49. <i>Ibid.</i> , pp. 4-26 to 4-28.
50. <i>Ibid.</i> , pp. 4-38 to 4-40.
Interferometric Sphere-Mapping System
4-39	51. <i>Laser Program Annual Report—1979</i> , Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-79 (1980), pp. 4-42 to 4-45.	52. J. A. Monjes, B. W. Weinstein, D. L. Willenborg, and A. L. Richmond, <i>Microsphere Rotator for Automated Interferometric Target Characterization</i> , Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-83375 (1979).

53. <i>Laser Program Annual Report—1978</i> , Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-78 (1979), pp. 4-21 to 4-25.		Interferometric Sphere-Mapping System (cont.)
54. <i>Laser Program Annual Report—1979</i> , Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-79 (1980), p. 4-35.	55. R. M. Singleton and J. T. Weir, <i>Microradiographic Characterization of Metal and Polymer Coated Microspheres</i> . Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-84471 (1980).	Production Improvements 4-40
56. <i>Laser Program Annual Report—1979</i> , Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-79 (1980), pp. 4-49 to 4-51.	57. L. J. Lebedzick, "An Automated Topographical Surface Reconstruction in the SEM," <i>Scanning</i> 2, 230-237 (1979).	Microtopography 4-43
58. <i>Laser Program Annual Report—1976</i> , Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-76 (1977), pp. 4-136 to 4-139.		Microsectioning 4-47
59. <i>Laser Program Annual Report—1979</i> , Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-79 (1980), pp. 4-55, 4-56.	60. J. M. Schneider, N. R. Lindblad, C. D. Hendricks, Jr., and J. M. Crowley, <i>J. Appl. Phys.</i> 38, 2599-2605 (1960).	Solid Hydrogen Granules 4-50
61. T. M. Henderson, R. J. Simms, and R. B. Jacobs, <i>Advances in Cryogenic Engineering</i> , K. D. Timmerhaus, Ed. (Plenum Press, New York, 1978), Vol. 23, pp. 682 to 689.	66. <i>Laser Program Annual Report—1978</i> , Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-78 (1979), pp. 4-2 to 4-7.	Formation of Condensed Fuel Layers 4-51
62. <i>Laser Program Annual Report—1979</i> , Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-79 (1980), pp. 4-58, 4-59.	67. R. L. Woerner and C. D. Hendricks, "Fabrication of Cryogenic Laser Fusion Targets," in the Technical Digest of the Proceedings of the Topical Meeting on Inertial Confinement Fusion, San Diego, Calif., February 7-9, 1978.	
63. B. W. Weinstein and C. D. Hendricks, <i>Appl. Opt.</i> 17, 3641-3646 (1978).	68. J. F. Miller, "A New Method of Producing Cryogenic Laser Fusion Targets," <i>Advances in Cryogenic Engineering</i> , K. D. Timmerhaus, Ed. (Plenum Press, New York, 1978), Vol. 23, p. 669.	
64. R. R. Stone, D. W. Gregg, and P. C. Souers, <i>J. Appl. Phys.</i> 46, 2693-2700 (1975).	69. <i>Laser Program Annual Report—1977</i> , Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-77 (1978), pp. 5-38 to 5-42.	
65. See Ref. 62, pp. 4-56, 4-57.		
70. <i>Laser Program Annual Report—1979</i> , Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-79 (1980), p. 4-59.		Cryogenic Target Systems 4-58
71. J. W. Sherohman and C. D. Hendricks, <i>Preliminary Analysis of a Target Factory for Laser Fusion</i> , Lawrence Livermore National Laboratory, Livermore, Calif., UCID-18719 (1980).	73. J. W. Sherohman, <i>Parametric Expressions of Tritium Flow Rates and Inventories in a Target Factory</i> , Lawrence Livermore National Laboratory, Livermore, Calif., UCID-18877 (1980).	Target Factory Studies 4-60
72. J. W. Sherohman and W. R. Meier, <i>A Parametric Study of a Target Factory for Laser Fusion</i> , Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-84264 (1980).	74. W. R. Meier, <i>Build-Up of Tritium in a Liquid Lithium Breeding Blanket for an Inertial-Confinement Fusion Chamber</i> , Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-85245 (1980).	
75. Stanley Hanel, <i>Application of Quality Assurance Guidelines to the High Pressure Gas System, Building 331</i> , Lawrence Livermore National Laboratory, Livermore, Calif., Internal Document UCIR-968 (1975).		Tritium Handling 4-65

Section 5 Diagnostics Technology

Diagnostics

Contents

Introduction	5-1
Three-Channel Soft X-ray Streak Spectrometer	5-2
Pinhole Imaging Streak Camera	5-6
Multilayer X-ray Interference Mirrors for an Improved SXRSC Spectrometer	5-9
Target Spatial Definition for Low-Energy X-ray Spectral Measurements	5-10
Production and Characterization of Soft X Rays for Diagnostics Calibrations	5-13
Hyper-Filter-Fluorescer Spectrometer for X Rays Above 120 keV	5-15
Streak-Camera Recording of Simultaneous Optical and X-ray Signals	5-19
A 662-keV X-ray Calibration Facility	5-21
22× Microscope Streak Camera	5-23
Microchannel Plate Reflector	5-31
Fuel Density Measurements Using Bromine L X-ray Line Imaging and Stark Profiles	5-32
Fabrication of High-Aspect-Ratio Microstructures for High-Energy X-ray and Particle-Imaging Applications	5-34
Point Imaging with X Rays (PIX)	5-36
Evaluation of X-ray Backlighting Diagnostics for Nova and Novette Laser Targets	5-38
Direct Fuel $\langle\rho R\rangle$ Measurements by Neutron Activation	5-40
Debris Collection and Background Measurements with Bromine-Filled Targets	5-45
Automated Radiation-Chemistry Diagnostic System	5-49
Stimulated Brillouin and Raman Side-Scattering Diagnostics System	5-52
4ω Optical Probing	5-53
Analysis of Bremsstrahlung Emission as an Electron-Density Diagnostic	5-56
CCD Applications in ICF Diagnostics	5-62
Automated Streak-Camera Calibration Using a CCD Readout	5-67
Optically Driven Semiconductor (Auston) Switch	5-68
A Fast Optically Triggered Silicon Switch for Framing-Camera Applications	5-70
Novette Target Alignment and Viewing Optics (TAV)	5-72
References	5-76

Diagnostics

Introduction

We report significant progress in the development, improvement, and implementation of diagnostic instrumentation during the last year; some of this capability is represented in Fig. 5-1. Seven articles in this section review a major effort in the area of sub-keV-x-ray instrumentation. Our soft x-ray streak camera (SXRSC) has been developed into an absolute spectrometer, providing time-resolved spectral measurements in the range from 10 to 20 ps, with the ability to produce data like those shown in Fig. 5-1(a). The SXRSC was

Fig. 5-1

absolutely calibrated using soft x rays produced at our Monojoule Diagnostic Laser Facility. During the year we added spatial discrimination to both the SXRSC and the Dante spectrometer. We also developed new schemes to provide better energy discrimination in this x-ray region, using microchannel-plate reflectors and x-ray interference mirrors. Typical spectral selectivity and reflection efficiency data for the latter component are depicted in Fig. 5-1(b). This was also the year that the 22 $\times$ Wolter microscope/streak camera was implemented on the Shiva target chamber. This instrument provided us with the ability to take high-spatial-resolution ($\sim 4\ \mu\text{m}$) time-resolved x-ray images of our target experiments; a sample image is shown in Fig. 5-1(c). We have also advanced our understanding of the characteristics of high-energy x-ray line emitters [Fig. 5-1(d)] which are potential backlighting sources for intermediate- and high-density targets.

In the area of high-energy x-ray measurements, our 100-keV filter-fluorescer spectrometer (FFLEX) measurements were extended to 250 keV, beyond the energy at which fluorescent edges are available [Fig. 5-1(e)]. We have now done calibrations for this system out to 660 keV. Imaging the source of suprathermal x rays is very helpful in understanding the effect on target performance of suprathermal-electron generation. To this end we have developed techniques to fabricate high-aspect-ratio microstructures, for imaging high-energy x rays and providing data for the intensity contour map shown in Fig. 5-1(f).

Significant progress has been made toward a direct diagnostic for fuel areal density, ρR . A bromine seed gas was added to the fuel in target capsules, to determine the fraction of the fuel tracer that could be retrieved in a target irradiation experiment. We also imaged the Br x-ray line emission in these experiments, to provide a measure of the fuel density. Further progress has been made in our efforts to automate our radio-chemistry measurements.

In the area of optical measurements, we have designed a new stimulated Brillouin or Raman side-scatter diagnostic instrument, and constructed the data-collection system. For our Novette laser facility we have planned and are developing 4ω optical probing, which will provide us with essential plasma density-distribution information for both directly irradiated and hohlraum fusion targets. We have also pursued the analysis of bremsstrahlung emission as an electron-density diagnostic.

Our continued commitment to developing new diagnostic capabilities exemplifies our aggressive approach to data acquisition. Our primary goal is to provide timely and complete data for use in understanding and improving laser-plasma interaction and target-implosion performance, while always analyzing and interpreting our diagnostics data for integration into new experimental and diagnostic designs.

Authors: V. W. Slivinsky and D. T. Attwood

Three-Channel Soft X-Ray Streak Spectrometer

We have initiated absolute-intensity measurements of the low-energy x-ray flux at Shiva, using a soft x-ray streak camera

(SXRSC). As presently configured, the SXRSC¹ is sensitive to x rays from 100 eV to 30 keV and has a temporal response of 15 ps. This represents a substantial increase in temporal resolution over our previous absolutely calibrated soft x-ray diagnostics, which used windowless x-ray diodes in our Dante spectrometers.² The Dante instruments, limited by oscilloscope

Three-Channel Soft X-ray Streak Spectrometer

bandwidths, have demonstrated 140-ps resolution for limited spectral bands using state-of-the-art oscilloscopes, and 500-ps resolution for total spectral measurements with our present capabilities.

In addition to its improved time response, the SXRSC spectrometer fielded at Shiva has other advantages. The SXRSC incorporates an active-readout charge-coupled device (CCD) array, enabling fast image processing and rapid data analysis (see "CCD Applications in ICF Diagnostics" later in this section). The present SXRSC system, including the CCD array, has a dynamic range of over 2×10^2 , allowing determination of the x-ray pulse-form and spectral shape two orders of magnitude below peak values. In this article, we briefly discuss its use in recent experiments, and present some initial data (from a disk target at Shiva) which demonstrate the capabilities and the potential of the instrument.

We have described the concept of using the SXRSC as a spectrometer, defining three subkilovolt x-ray channels with x-ray mirrors and transmission filters, in previous reports.³ The hardware, as fielded on Shiva four metres from the target, is shown in Fig. 5-2. A two-dimensional CCD active-readout detector is used as the data-acquisition system. The system is directly accessed by the Shiva computer, allowing retrieval and

processing of data immediately after the system shot. This improvement over film recording permits us to bypass the time-consuming steps of film development and image digitization.

We have absolutely calibrated the SXRSC, including the CCD array, using the same calibrations procedures described

Fig. 5-3. Absolute x-ray spectral response for the three x-ray channels used on Shiva (see p. 5-4).

Fig. 5-2. Photograph of the SXRSC in place at Shiva.

Three-Channel Soft X-ray Streak Spectrometer

Fig. 5-4. SXRSC data: (a) color-enhanced two-dimensional array indicating positions of the three x-ray channels and (b) time history of the raw data of the three x-ray channels.

Fig. 5-5. Temporal dependence of the average flux from the three x-ray energy channels.

previously for film.³ The CCD array facilitates the calibration procedure, however, by allowing real-time preliminary data analysis and faster shot turnaround. The CCD array also reduces data scatter by about 30% compared with film recording. In

Fig. 5-3 (p. 5-3) we plot the absolute response functions, and give filter and mirror specifications, for the three channels used at Shiva. The label on the vertical axis ("bit") refers to the digitization value of the pixel charge in the CCD array. It is arbitrarily set by the electronic digitizer, and does not change throughout the calibration or during data acquisition.

To demonstrate the potential of the spectrometer, we present results from a disk shot on Shiva, and then compare those data with Dante results. For the shot, the upper 10 beams of Shiva illuminated a gold disk at an angle of 60° with respect to the disk normal. The SXRSC viewing angle was normal to the disk, while a Dante spectrometer viewed the disk 30° to its normal. At these angles, differences in measured emission due to angular distribution effects should be minimal. The 10 beams, with a total energy of 3.9 kJ, were overlapped and focused to produce a peak intensity of $3 \times 10^{15} \text{ W/cm}^2$ in a 600-ps laser pulse.

The raw data from this shot are shown in Fig. 5-4, in the color-enhanced plot of the two-dimensional CCD array data. The vertical lines mark the channels for the three x-ray energies. To the right in the figure is the time history of the signal for the three channels. The data are analyzed using the

response functions shown in Fig. 5-3. The spectral unfold is done by averaging the response functions over the energy bins, assuming a flat x-ray spectrum; this process has been described elsewhere.⁴ The x-ray channels are well defined for this experiment, so that necessary corrections in the signal due to emissions from other regions in the x-ray spectra are, at most, a few percent for this case.

The flux for the three x-ray energies is shown in Fig. 5-5. The estimated error in the calibration is about $\pm 30\%$. This includes only errors in the absolute calibrations. We have not included errors in unfolding the data, which are introduced mainly in the method of averaging the channel response functions. We have compared results using this method of analysis with results from a full spectral-unfolding fit, and found them to yield similar results. The error of the relative time histories is much smaller, in fact less than the line width at the peak, and is governed primarily by detection statistics in the instrument.

The data can be summed to obtain the total subkilovolt flux as a function of time. The integral flux from 160 to 720 eV is plotted in Fig. 5-6. We observed the pulse width to be 960 ps FWHM, which is a little longer than the input laser pulse width of 900 ps FWHM.

We calculate the spectral flux by integrating the flux in each channel over time. The results are plotted in Fig. 5-7, which also shows results from Dante measurements on the same shot. Note that the two instruments are in agreement below 500 eV. At 650 eV, however, the instruments differ by a factor of 8. The source of this discrepancy is presently not understood. The SXRSC uses much thicker filters than Dante, and we are investigating possible errors in calibrating the thicker filters. The thicker filters provide narrower channels and better energy resolution. The thinner Dante filters, on the other hand, measure a much larger spectral region. Large structure in the spectrum would therefore have a much more dramatic affect on the narrower channels used by SXRSC. The Dante data do indicate some structure in this region, but not nearly enough to explain our results. We will continue comparisons between the two instruments, investigating the systematics of the data. We also plan to review our analysis

Fig. 5-6. The total flux, obtained by integrating the spectral flux from Fig. 5-5.

Fig. 5-7. Comparison of integrated fluences from the SXRSC and Dante, for a gold-disk irradiation experiment.

and calibration procedures for possible sources of error.

In summary, we have demonstrated the ability of the SXRSC to make absolute spectral measurements in the soft x-ray region. We will continue to upgrade and refine calibrations of the SXRSC and its data analysis procedures to improve data accuracy. By expanding the number of x-ray channels to seven in the next year, we can increase our spectral resolution and range of coverage to around 700 eV. Implementation of multilayer mirrors (described in the next article) will vastly improve channel spectral definition. These improvements in the SXRSC will result in the more accurate soft x-ray fluence measurements required to understand the physics of formation and the dynamics of x-ray-emitting plasmas.

Author: R. L. Kauffman

Major Contributors: H. Medeck and E. L. Pierce

Pinhole Imaging Streak Camera

To provide spatial resolution for the multichannel soft x-ray streak spectrometer of the previous article, we have designed and demonstrated the use of a coaxial combination x-ray-pinhole and visible-alignment camera. This instrument will permit us to improve our time-resolved x-ray fluence measurements by identifying and defining the target's emission area.

A schematic of the instrument is shown in Fig. 5-8. The x-ray beam is defined by a pinhole mounted on an X-Y-Z positioner. This beam is reflected by four grazing-incidence mirrors into the streak camera's photocathode. Each mirror defines an upper energy limit for the respective channel. Note that the mirrors are staggered in radial distance; this allows appropriate variation in the grazing-incidence angle, and thus in the upper x-ray energy cutoff in the separate channels. In addition, the four mirrors are staggered sideways, to reflect four portions of the beam into corresponding portions of the photocathode. Two absorption filters are inserted between each of the mirrors and the photocathode, to define a low-energy limit for the spectrum of the x-ray fluence. By using two filters with each mirror, we obtain eight independent x-ray channels. The

entire path of the x-ray fluence, including the streak camera tube, is under a vacuum of 10^{-5} Torr or better during the data collection.

The SXRSC component of the system is described in our 1978 Annual Report.⁵ At the present time data are recorded on photographic film, but in the future the streak camera will be retrofitted with a CCD.

Alignment of the instrument consists of

- Selecting a portion of the emitting target.
- Passing its ray fluence through the pinhole.
- Reflecting four portions of the beam into the four grazing mirrors.
- Reassembling the four portions along the photocathode slit without overlapping or excessive gap.

Diffraction of visible light at the pinhole, which is due to the pinhole's small diameter, makes it impossible to use the pinhole itself on an optical alignment. The approach we have adopted consists of mounting the pinhole in coincidence with the optical axis of an optical lens. In this way an optical alignment camera is superimposed on the x-ray pinhole camera. The focal length of the optical lens is selected so as to have a magnification identical to that of the x-ray pinhole camera. A hole at the center of the lens allows for the propagation of the x-ray beam defined by the pinhole. It should be noted that the optical image of the target at the photocathode, provided by the lens, is

Fig. 5-8. Schematic of the imaging soft x-ray spectrometer.

identical in position, size and orientation to the x-ray image provided by the pinhole. Furthermore the arrangement of the four portions of the target image along the photocathode will be identical to the one achieved with the x-ray fluence.

The absorption filters are optically opaque, but they are located close to the photocathode, and no error is introduced by aligning at their surface. The optical image of the target is obtained by illuminating the target with a low-power helium-neon laser. We can obtain either a bright target image on a dark background, or a target shadow on a bright background, using front or rear illumination of the target, respectively. The x-ray mirrors used in this camera are of good optical quality, reflecting both light and x rays; this makes optical alignment valid for these components.

The most critical component to be aligned is the pinhole-lens assembly. Such alignment can be performed under vacuum, using the X-Y-Z positioner; this allows for a last-minute check and adjustment just prior to the laser shot. Alignment is also required for the grazing-incidence mirrors, each with an independent five-degrees-of-freedom mount. The mirror alignment is less critical than the pinhole alignment, and it is performed with the instrument and target chamber in open air.

For pinholes whose diameter is much larger than the wavelength corresponding to the x-ray radiation, the resolution may be improved by reducing the pinhole diameter. A limit is reached when diffraction becomes important; further reduction in diameter worsens the resolution. The optimum resolution is on the order of the pinhole diameter. An additional consideration for the selection of a pinhole diameter is the intensity of the x-ray source, since the x-ray fluence at the cathode must be compatible with the streak camera sensitivity.

We can vary the magnification of the camera by changing the pinhole position for the fixed target-from-cathode separation of 4 m. The magnification is limited by the requirement that the image not exceed the length (13 mm) of the photocathode slit. Thus the range of available magnifications, 10 $\times$ to 50 $\times$, limits the lateral field of view at the target to between 1.3 mm and 260 μ m, respectively. In many cases, however, we plan to use this imaging scheme to provide spatial discrimination for the imaging

spectrometer, defining an emission area for the various x-ray channels, rather than providing detailed spatial data within that emission area.

The pinhole imaging camera has been installed on Shiva, but to date we have performed only limited tests. The main emphasis has been a demonstration of the imaging capability and the suitability of the alignment technique. A typical experimental result is shown in Fig. 5-9. In these preliminary tests, we chose a magnification of 14.4 and a pinhole diameter of 35 μ m. We used only one mirror, Ni at 3 $^\circ$, together with a 0.4- μ m Fe filter. The instrument was mounted on a port with a horizontal axis, and the streak camera slit was also horizontal. A helium-neon laser used to backlight the target was mounted on the opposite port. The target was a gold disk 600 μ m in diameter and tilted 45 $^\circ$ with respect to both the upper laser-beam cluster and the camera axis. The upper beam cluster was focused to a 400- μ m-diam spot centered with the disk, and the pulse duration was 35 ns with an energy of 350 J.

We aligned the instrument by backlighting the gold disk target. The resulting dark, elliptical image (8.6 mm wide by 5.6 mm high) projected at the cathode surface was centered on the cathode slit along both vertical and horizontal directions. This way the irradiated area was also centered with the cathode.

Figure 5-9(a) is a plot of the digitized photographic film, with reference lines of constant x-ray intensity. We can also obtain both spatial and temporal energy profiles, as shown in Figs. 5-9(b) and (c). In Fig. 5-9(a), the abscissa is the spatial coordinate and the ordinate is the streaking time; only the first 16 ns of the plasma are shown. The record shows an initial plasma diameter on the order of 400 μ m, coincident with the irradiated area. The plasma grows toward the irradiating laser beam. Because of the angle under which the instrument observes the plasma (90 $^\circ$ with respect to the irradiating laser beam), no growth is observed on the streak.

The goal for this test was to assess the operation of the instrument. In this respect, we concluded that

- The alignment technique is adequate, as shown by the centering of the plasma along the cathode slit.
- Both the spatial resolution and the

Fig. 5-9. SXRSC spectrometer results of a gold-disk irradiation at Shiva.

magnification of the instruments are the expected ones, as indicated by the width of the streak.

- The x-ray fluence achieved during this test is somewhat low. The threshold is indicated by the background noise, appearing as a granular background in Fig. 5-9(a) and as spikes away from the plasma profile in Fig. 5-9(b). From this last figure, we observe that the highest signal is about 20 times the background signal. From the calibration of the streak

camera we estimate that we can record without saturation a signal 10 times higher.

In the future, we will use the pinhole-imaging streak camera in two basic configurations. In one case, we will employ it as an eight-channel imaging streak spectrometer, with low spatial resolutions ($\sim 100 \mu\text{m}$) for discrimination only. In this configuration, we will use eight absorption filters, two for each of the four grazing-angle mirrors. In the other basic configuration, we will use the

instrument as a single-channel detector with moderate spatial resolution ($\sim 30 \mu\text{m}$).

Authors: H. Medeck and R. L. Kauffman

Multilayer X-ray Interference Mirrors for an Improved SXRSC Spectrometer

Improved spectral characterization of time-resolved emissions of soft x rays from laser plasmas continues to be a priority diagnostics development effort. We are now

implementing novel multilayer x-ray interference mirrors on a soft x-ray streak camera. These multilayer mirrors, which function as synthetic crystals for Bragg diffraction of x rays, provide significantly higher spectral resolution ($E/\Delta E \sim 10$ to 90) than current high-throughput spectral-discrimination techniques ($E/\Delta E \sim 3$ to 5).^{6,7}

Our SXRSC spectrometer system (Fig. 5-10) will use this narrow bandwidth to unambiguously measure the x-ray emission history in five narrow energy channels from 100 to 1000 eV. Narrow energy channels enhance our ability to calibrate the instrument using pulsed, laser-driven x-ray sources which emit a broad spectrum of

Fig. 5-10. Five-channel SXRSC spectrometer, using multilayer x-ray interference mirrors.

Fig. 5-11. Characterization of blackbody radiation with multilayer x-ray interference mirrors.

Target Spatial Definition for Low-Energy X-ray Spectral Measurements

radiation with narrow spectral features. Figure 5-11 shows the position and width of these narrow-band channels in the subkilovolt energy region. The curves correspond to the emission distribution of 100-, 150-, and 200-eV black bodies. The energy channels (the shaded regions in the figure) are defined by five multilayers of different d-spacing and material combinations, which are set at a 25° Bragg angle. Each channel is filtered with a thin-foil absorption filter (Fig. 5-10).

The x-ray interference mirrors are fabricated by T. W. Barbee of Stanford University, using a multilayer sputtering technique.⁸ They consist of periodic layers of alternate low-Z and higher-Z materials, which provide spatially modulated x-ray scattering properties. Available materials are limited to those with acceptable sputtering and interface characteristics; from these candidates a selection is made to obtain the optimum combination of x-ray scattering and absorption properties at the x-ray energy of interest. The channel resolution, $E/\Delta E$, is approximated by the effective number of layers, N_{eff} , which scatter the incident signal. Thus for high resolution, overall absorption must be minimized. The peak reflectivity is enhanced by a high scattering efficiency and by a large N_{eff} .

The periodic d-spacing of the multilayer is selected to give the desired diffraction angle from the Bragg condition, $\lambda = 2d \sin \theta$. We have chosen d-spacings such that the multilayers which define the five different energy channels are oriented at a single diffraction angle. The multilayers are positioned side by side and coplanar at this angle with respect to the target radius. This design does not require reconfiguration for different target distances, which simplifies instrument alignment (Fig. 5-11).

Small-angle reflection from the multilayer surface can introduce significant background signal with a broad spectral character; such reflections are particularly strong in the

low-energy region. We therefore set the multilayers at a relatively large diffraction angle of 25° to suppress this background. Absorption-edge filters are used to further attenuate this surface reflection background, while transmitting the signal within the channels.

Table 5-1 gives the multilayer d-spacings, material combinations, energy bandwidths, peak reflectivities, reflectivities integrated over the angular bandwidth of the multilayers, and the absorption filters which comprise the 25° five-channel system. These multilayer characteristics have been evaluated by B. L. Henke of the University of Hawaii, using fluorescent line sources corresponding to the intended channel energies.

The necessary multilayer mirrors for this system are currently in hand, and we have constructed alignment and housing facilities. Mounting and alignment of the multilayer system is in progress, with system tests following soon.

Author: G. L. Stradling

Target Spatial Definition for Low-Energy X-ray Spectral Measurements

The main advantages of using filtered x-ray diode (XRD) systems to measure low-energy x-ray spectra from laser-fusion targets, are the reliability and good absolute accuracy (20 to 35%) of these systems. Because of oversized forward collimators, each of our XRD detector systems views a rather large region (1.5 to 2.5 cm) in the center of the target chamber. To minimize the sensitivity of the XRD system to extraneous sources of x rays, we have worked on two general methods of providing better spatial definition at the target: a pinhole imaging method and a mirror-imaging system.

Table 5-1. Multilayer interference mirror and filter characteristics.

Channel Energy	100 eV	267 eV	489 eV	705 eV	943 eV
d-spacing at 25° (Å)	143	55	30	21	15
Scattering material/spaces	V/C	Ti/C	W/C	W/C	W/C
Width ΔE (eV)	15	7	14	8	10
Integrated reflectivity (mrad)	0.27	1.9	0.88	0.46	0.12
Peak reflectivity (%)	6.5	10.6	4.5	5.1	1.6
Filter material/thickness	Be/1 μm	C/2.65 μm	Ti/7000 Å	Al/7000 Å	Al/7000 Å

The pinhole imaging method involves a set of collimating apertures for each XRD channel. Since the pinholes need to be located at a survivable distance (100 to 150 mm) from the target, the target definition of these systems always suffers from umbra and penumbra ambiguity. Consider a pinhole of diameter d located a distance h from the source, and a detector of diameter D located a distance L from the pinhole (see Fig. 5-12). We define the source umbra as the region of diameter U in the source plane that is viewed by all of the detector. As shown in Fig. 5-12, this region is determined by a set of rays from the outer limits of the detector through the outer limits of the pinhole. We similarly define the source penumbra as the region of diameter P , outside of which the detector sees no source emission. The umbra and penumbra are given by

$$P = U + \frac{2Dh}{L}$$

and

$$U = d \left(1 + \frac{h}{L} \right) - \frac{h}{L}$$

It is clear that, for ideal pinhole definition of the source, the penumbra should not significantly exceed the umbra. Unfortunately, we have a system with a relatively large penumbra, because of the following conflicting requirements:

- The pinhole must be placed far enough from the source to survive.
- Sufficiently large detector diameters must be used.
- The distance L must be short enough to obtain adequate detector signals.

All of these factors tend to increase the amount by which the penumbra exceeds the umbra. For our prototype five-channel Dante system, shown in Fig. 5-13, $D = 12$ mm and $L = 1565$ mm. With $h = 150$ mm, we find that the penumbra exceeds the umbra by 2.3 mm, resulting in a serious umbra-penumbra ambiguity regardless of the umbra diameter; i.e., if the umbra diameter is zero, the penumbra diameter is still 2.3 mm.

Since our targets have emission regions that generally are less than 1 mm, it is not possible to achieve adequate spatial

definition using the pinhole-imaging method. We cannot, for example, define an accurate area on the surface of a disk target. We will therefore use pinhole imaging mainly to shield the detector system from large low-energy plumes; for this application, the source-emission region of interest will be entirely within the umbra, U . This pinhole-imaging system may also be useful for complex targets, such as the backlighter type, that feature two emission regions relatively far apart.

Because of the basic limitations of pinhole imaging, we began design work on a second system, the imaging Dante system (IDS).

Fig. 5-12. Comparison of pinhole-imaging and mirror-imaging geometry.

Target Spatial Definition for Low-Energy X-ray Spectral Measurements

This system uses a grazing-incidence elliptical mirror as a transfer optic, with a resolution of 10 to 20 μm , to produce an image of the target outside the target chamber. Figure 5-14 shows a conceptual design for the IDS prototype. Low-energy x rays emitted from a point on the target are focused by the mirror to a point more than 3 m from the target, thus forming an image of the x-ray emission in this plane. The imaging mirror features a gold surface and a

2° reflection angle, to yield fairly uniform reflectivity below 1.5 keV. A diamond (low-Z) pinhole can then be placed at the equivalent plane of the target to serve as the x-ray defining aperture with a typical pinhole diameter of 200 μm . The detectors are positioned in a ring array 3 m beyond the pinhole (Fig. 5-14), to observe the apertured secondary image. This displacement from the target, which is an intense x-ray source, enormously increases pinhole survivability;

Fig. 5-13. Five-channel Dante system with pinhole imaging.

Fig. 5-14. IDS prototype:
(a) x-ray/optical schematic and (b) mechanical system. ▼

because of the mirror dispersion and the difference in solid angle, the fluence on the IDS pinhole is reduced by over five orders of magnitude compared to the fluence on a pinhole mounted close to the target.

IDS will have a pointing capability on every shot, and will incorporate eight or more x-ray channels as well as a combined UV/optical detector. A typical arrangement might consist of eight XRDs with different filters, to obtain different energy bites of the low-energy x-ray spectrum. A combination of filtered XRDs and flat-response detectors might also be used, the latter to obtain more precision in the total low-energy x-ray emission. IDS is designed to survive the Nova environment; the same system is suitable for development and testing on Novette.

Authors: K. G. Tirsell, R. H. Price, and M. W. Kobierecki

Production and Characterization of Soft X Rays for Diagnostics Calibrations

Our primary facility for developing and calibrating fast-time-response x-ray diagnostics is the Monojoule facility, a 20-GW, 50-ps, 1.06- μm laser. When focused on thick metal targets, a 50-ps laser pulse creates an x-ray burst 70 to 100 ps in duration (depending on photon energy), with a total soft x-ray fluence on the order of 5 mJ/sr (see Ref. 9). In this regime of pulse length and laser intensity, the soft x-ray spectrum for many targets is dominated by line structure. We have begun investigations of the structure of emissions from various target materials; these measurements can improve intensity calibrations for fast detectors (such as our soft x-ray streak camera) by better characterizing our x-ray source. Detailed study of line spectra can also aid in understanding both the physical processes occurring in these laser-generated plasmas and their resultant x-ray emission spectra.

Initially, we have used a convex crystal spectrograph to resolve soft x-ray spectra produced by targets of intermediate atomic number (Sc through Cr) that strongly radiate L-shell lines in the soft x-ray regions. The spectrograph design is similar to Henway designs used with Argus and Shiva.¹⁰ We use a lead behenate ($2d = 120 \text{ \AA}$) crystal as a resolving element; this Langmuir-Blodgett pseudocrystal provides excellent coverage over much of the soft x-ray region.

An example of the data covering the spectral range from 400 to 900 eV is shown in Fig. 5-15, a composite of about 30 shots with a 150-ps, 3-J laser pulse, requiring about 90 min to accumulate. We use Kodak type 101-01 film, which is sensitive over the soft x-ray region of interest.¹¹ To prevent film fogging, we use a 4000- $\text{\AA}$ Fe filter as a light and UV shield; this filter has an L-edge cutoff at 708 eV, which can also be used as an energy calibration point. The transmission efficiency folded with the crystal reflectivity is also plotted (as a dashed line) in Fig. 5-15, indicating that the instrument's efficient detection window is from 450 to 700 eV; the feature at 520 eV is due to absorption from oxygen in the lead behenate crystal. In most spectra, we observe two sets of features due to first- and second-order diffraction of the L-series lines, as shown in Fig. 5-15. The second-order structure is better resolved and is used for analysis when available.

As the atomic number (Z) of the target is increased, higher-energy photons are emitted. Figure 5-16 compares the spectrum

Fig. 5-15. Example of the spectrum obtained from a Cr target.

from targets of Sc, V, and Cr. This trend to higher energies reflects the increase in L-shell binding energy due to increasing Z . We have begun to identify some prominent features of the spectra; most of the structure can be explained as lines from isoelectronic atomic structures of lithium through neon. The spectra from these configurations can be quite complicated, since many of the observed peaks are unresolved structures composed of numerous lines. We have denoted the

position of some known x-ray transitions from different configurations.¹² The general trend seems to suggest that, as the atomic number of the element increases, the relative populations of configurations having more bound electrons are preferred. Thus, for Cr, we observe more Ne-like lines relative to F-like lines than we observe with the Sc spectrum. To verify this observation, we need detailed line-intensity ratios, including corrections for the spectrometer response function. For Cr, lines from higher

Fig. 5-16. X-ray spectra produced with approximately the same laser parameters from Sc, V, and Cr targets.

ionization states lie above the filter cutoff, which may bias our observations toward lower ionization states.

In summary, we have begun cataloging soft x-ray spectra obtained from our Monojoule calibration facility. The spectra contain much structure due to their line features. We plan to expand coverage of our spectral range, using other UV/x-ray filters with different cutoff energies, to map out the entire spectrum. We also will use lower-Z targets to produce K x rays in this spectral range. K-shell spectra are much simpler and could possibly produce x rays over a much narrower spectral band; a narrow-band, or monoenergetic, x-ray source would simplify instrument calibration procedures. In addition, we plan to implement a more efficient spectrograph, to reduce the repetition rate needed to accumulate a spectrum, and to allow studies of laser intensity and pulse-length dependencies of the x-ray spectrum. With a better-characterized source, we can perform faster and more accurate calibrations of our subkilovolt x-ray streak cameras.

Authors: R. L. Kauffman and D. P. Gaines

Major Contributors: R. A. Perkins and G. L. Stradling

Hyper-Filter-Fluorescer Spectrometer for X Rays Above 120 keV

The technique of spectral analysis using K-edge filters and fluorescers has been developed at LLNL and Los Alamos in the last three decades, and the standard filter-fluorescer spectrometer is now a powerful tool for measuring the x-ray spectrum from high-fluence x-ray sources.¹³ This measuring technique is limited to energies less than 120 keV, however, because there are no practical K-edge absorption materials available for use above 120 keV. To overcome this shortcoming, we have developed a new apparatus that will enable us to use the filter-fluorescer for x-ray spectral measurements above 120 keV.

We call this new apparatus the hyper-filter-fluorescer spectrometer (HFFS), both to distinguish it from the conventional filter-fluorescer spectrometer (FFLEX) and to denote that it extends the useful energy range of spectral measurement. The use of "hyper" was chosen to imply a "strange" way of using the FFLEX for measuring x rays at "higher" energies. We present here the method of using the HFFS for measuring the suprathreshold x-ray spectrum from laser-driven fusion targets.

As shown in Fig. 5-17, an FFLEX channel consists of a prefilter, a fluorescer, a detector, and (usually) a postfilter, which is useful but not essential. Figure 5-18 shows the prefilter transmission, the fluorescer cross section, the postfilter transmission, and the combined response function of these three components. Note that the absorption edge (E_p keV) of the prefilter is at a higher energy than that of the fluorescer (E_f keV); i.e., $E_p > E_f$, resulting in the sharp response function between E_f and E_p shown in Fig. 5-18(d). Subtracting E_f from E_p thus produces the well-defined band-pass of this spectrometer channel. In addition to this basic approach to the FFLEX concept, we often add a postfilter that improves the signal-to-noise ratio by preferentially transmitting the K fluorescence lines ($K\alpha$) while absorbing unwanted x rays, such as higher-shell fluorescence or background x rays.

With its narrow, sharp response function, the FFLEX is very useful in measuring gross structures of an x-ray spectrum, especially in cases where the source intensity is so high that it is necessary either to reduce the x-ray fluences on the detector or to avoid placing detectors directly in the beamline. There is, however, an undesirable response at energies above the FFLEX band-pass, as shown in Fig. 5-18(d). Since this response contributes to the detector signal, a knowledge of the magnitude of this unwanted component can be critical in producing an accurate spectrum. Kornblum et al.¹⁴ suggested a scheme to measure this component by using a fluorescer of the same material as the prefilter, thus reducing the bandwidth between the K edges to zero while retaining the higher-energy response. This approach to providing spectral discrimination for energies above 120 keV is important, because it yields a half-width

Hyper-Filter-Fluorescer Spectrometer for X Rays Above 120 keV

narrower than that obtainable with a simple filter-detector system. Figure 5-19 shows the response function of such a channel; it uses tantalum for both the prefilter and the fluorescer while using a 3-mm NaI(Tl) detector as the x-ray-to-optical converter. The high-energy tail is significantly reduced due to the fast decrease in detector sensitivity (Fig. 5-20).

The problem with the approach described above is that it produces an undesirable spectral response just below the absorption edge of the fluorescer (see Fig. 5-19). This component of the spectral response introduces a large error in the detector signal when the spectrum being measured is a rapidly decreasing function of the x-ray energy. It is particularly troublesome for measuring x rays from a gold target, since the window occurs in the region where the Au K-lines are present. It is important,

therefore, to eliminate this portion of the spectral response by making the response function in the region where the Au K-lines dominate small in comparison to the bremsstrahlung continuum. This reduction of the unwanted part of the response function can be accomplished with the HFFS approach, which we now describe (Figs. 5-21 and 5-22).

We have seen in Fig. 5-18(d) that a sharp, positive band-pass can be constructed by the absorption edges of the prefilter (E_p) and of the fluorescer (E_f) such that $E_p > E_f$. But it is also possible to virtually eliminate the response between E_p and E_f and leave just the tail by choosing $E_f > E_p$, reversing the K-edge energy order of the conventional FFLEX. Figure 5-22 illustrates this reverse approach to producing narrow-band spectral discrimination above 120 keV. As in the conventional FFLEX channel, we are

Fig. 5-17. Schematic of a filter-fluorescer spectrometer.

detecting the K x rays produced in the fluorescer material, not the actual 120-keV incident x rays. Thus, by imposing $E_f > \text{Au K-lines} > E_p$, we ensure that no gold lines from the fusion target will be detected by the x-ray detector. Furthermore, the high-energy transmission in Fig. 5-18(d) is now enhanced for the spectral measurement at higher energies [Fig. 5-22(d)]. It is because of

this unusual way of using the FFLEX for x-ray measurement at energies higher than practical K-edge energies that we have called the system a hyper-filter-fluorescer spectrometer.

The peak position of the HFFS channel can be adjusted by properly choosing the materials and thicknesses for the prefilter, fluorescer, and postfilter. The small response window just below E_p in Fig. 5-22(d) can be removed by a thicker postfilter. The high-energy response portion of the channel shown in Fig. 5-22(d) can be narrowed by

Fig. 5-19. A filter-fluorescer response function, using a tantalum prefilter and fluorescer and a 3-mm NaI(Tl) detector.

Fig. 5-20. Sensitivity of a 3-mm NaI(Tl) detector as a function of x-ray energy.

Fig. 5-18. Response function of the conventional filter-fluorescer spectrometer (FFLEX).

Hyper-Filter-Fluorescer Spectrometer for X Rays Above 120 keV

means of the rapidly decreasing response with energy of a thin NaI(Tl) detector. Examples of the physical components of four HFFS channels, with detected energy maxima at 150, 200, 250, and 300 keV, are given in Table 5-2. The results presented in the table were calculated with the FLUORESCER code,¹⁵ which was written for the CDC 7600 computer. Response functions for these four channels are given in Fig. 5-21.

Fig. 5-21. Response functions of four HFFS channels at 150, 200, 250, and 300 keV.

X-ray energy (keV)	Prefilter		Fluorescer		Postfilter		Detector NaI (Tl) (mm)
	Material	Thickness (mm)	Material	Thickness (mm)	Material	Thickness (mm)	
150	Dy	1.27	Au	0.0762	Au	0.254	3
200	Hf	1.37	Pb	0.127	Pb	0.381	3
250	Hf	1.27	Pb	0.254	Yb	0.559	3
300	Au	2.03	Pb	0.0508	Pb	0.508	3

Note: Response functions of the four channels are given in Fig. 5-23.

Table 5-2. Parameters of four HFFS channels.

The most commonly used method for measuring x-ray spectra above 100 keV employs a simple filter-detector combination. The filter provides low-energy discrimination while the detector provides high-energy discrimination. An example of a 250-keV peak-energy channel generated using a lead filter, a tantalum filter, and a 3-mm NaI(Tl) x-ray detector is illustrated in Fig. 5-23. For low energies, a large response

Fig. 5-22. Response function of the HFFS.

◀ Fig. 5-23. Response function of a simple filter-detector channel using lead and tantalum filters and a 3-mm NaI(Tl) detector.

due to the lead absorption edge at 88 keV is suppressed by the tantalum K-edge at 67 keV, which results in two reduced response regions below 100 keV. It is very difficult to remove these two undesirable spectral transmission regions. Also, on the high-energy side, the falloff of the response function is slower than that of the HFFS because, for the HFFS, the high-energy cutoff is due to the joint contribution of the filter-fluorescer cutoff [Fig. 5-22(d)] and the falloff in detector response (Fig. 5-20). Thus the HFFS has a narrower spectral response than the simple filter-detector system, which makes the HFFS superior in providing well-defined spectral channels to measure the suprathermal x-ray spectrum from laser-irradiated fusion targets.

The HFFS is also useful when the x-ray fluence is high enough to endanger the detector in the beamline. On the other hand, the HFFS may be too insensitive for low-fluence experiments. In the latter case, the simple filter-detector scheme must be employed.

In Fig. 5-24, we show the composite spectrum for a laser-irradiated target where the points below 100 keV were obtained with a conventional FFLEX, while the data at 150 and 200 keV were obtained by using the two HFFS channels of Table 5-2. The data at 250 and 350 keV were obtained with simple filter-detector channels; at these energies, the x-ray fluence was too low for

Fig. 5-24. Composite high-energy x-ray spectrum obtained with the FFLEX and HFFS from a tantalum disk target.

the HFFS. Figure 5-24 clearly illustrates the existence of two x-ray-inferred suprathermal temperatures in the laser-plasma interaction. At these fluence levels, the HFFS can be a versatile tool for x-ray spectral measurements between 120 and 220 keV.

Author: C. L. Wang

Major Contributors: H. N. Kornblum, T. D. Schwinn, and V. W. Slivinsky

Streak-Camera Recording of Simultaneous Optical and X-ray Signals

The generation of suprathermal electrons is a significant issue in the laser fusion program. If we are to better understand the processes involved and model their effects on target implosions, it is important that we know the temporal evolution of suprathermals with respect to the driving pulse. To obtain such data with good temporal resolution (10 ps) and dynamic range (10^3) on a single instrument, we have recently used one of our S-1 optical streak cameras¹⁶⁻¹⁸ to simultaneously record both reflected or scattered 1.06- μ m laser light and suprathermal (≈ 30 keV) x rays from the target.

Fig. 5-25. Simultaneously detected x rays and scattered 1.06- μm laser light: (a) streak camera photograph and (b) temporal characteristics.

Fig. 5-26. Streak-camera measurement of a 1.06- μm pulse propagated through 5 m of graded-index optical fiber.

Although designed for visible and near-infrared photons, the S-1 photocathode, which contains silver and cesium, is moderately efficient for the detection of x rays. The major limitation in the experiments reported here is the 2.8-mm glass streak-tube vacuum window on which the cathode is deposited; this window absorbs x rays below about 25 keV, thus preventing them from reaching the photocathode. For these experiments, therefore, we increased the camera-slit width from the standard 50 to 1500 μm , which improved the sensitivity of the streak camera by a factor of 30. Our studies show that for these cameras this can be done without loss of temporal resolution and with only a small degradation in spatial resolution. We used a contact slit cut through a 6-mm lead sheet; this sheet covered the glass

window, to prevent very-high-energy (>100 keV) x rays from penetrating the streak-tube window and interacting directly with normally unused areas of the photocathode and the streak-tube output phosphor.

Figure 5-25(a) shows typical data from one of our experiments. The optical signal is on the left and the x-ray signal is on the right. The optical signal has been transmitted through a 1.06- μm bandpass filter which blocks other visible wavelengths, and through 0.75 in. of lead glass which blocks very energetic x rays. The x-ray signal is filtered by thin tin and aluminum foils, which also block 1.06- μm and other visible radiation. The central region where the optical and x-ray filters overlap is a background measurement of the high-energy x rays that penetrate the shielding and interact with the photocathode and output phosphor. Note that time proceeds vertically, as indicated by the arrow. Figure 5-25(b) shows temporal signatures of the 1.06- μm laser and 30-keV suprathermal x-ray signals; these data were obtained by taking lineouts of the raw data in Fig. 5-25(a) and correcting for recording film characteristics. Our preliminary measurements have 25-ps resolution. The absolute timing error between the two signals (caused by film alignment during the reading process) is known to be less than 50 ps.

Note that in this particular experiment, the suprathreshold x rays were generated early in the envelope of scattered $1.06\text{-}\mu\text{m}$ light. The shape of the suprathreshold x-ray signal, as recorded with the wide-slit camera (which we call OX-1), is in good agreement with the shape recorded with our usual X-1 x-ray streak camera,¹⁹ which is not sensitive to $1.06\text{-}\mu\text{m}$ light. This agreement (which we have observed throughout our experiments) is particularly interesting, because the X-1 camera is also sensitive to thermal x rays, and thus provides the link for establishing the temporal relationship between $1.06\text{-}\mu\text{m}$ light and thermal x rays.

Having developed an ability to unambiguously record optical and x-ray signals with a single streak camera, and having obtained some significant data that affect our modeling of target performance, we are now actively pursuing two experimental improvements. We are feeding part of one $1.06\text{-}\mu\text{m}$ incident Shiva laser beam directly to the camera via a fiber-optic link, which will allow us to compare the x-ray signal with both the incident and the scattered laser-light envelopes. We have demonstrated in our experimentation that $0.53\text{-}\mu\text{m}$ and $1.06\text{-}\mu\text{m}$ light transmission through short graded-index optical fiber can be done without significant temporal dispersion. This is shown in Fig. 5-26, which compares a $1.06\text{-}\mu\text{m}$ pulse transmitted through fiber-optic cable with a simultaneously recorded portion of the incident beam propagated entirely through air. We are also having a modified S-1 streak tube built with a thin ($8\text{ }\mu\text{m}$) mica window that will extend our lower-x-ray energy limit to about 2.5 keV when used with the

appropriate low-pass x-ray mirror filter. This modification will enable us to use a single instrument to simultaneously detect incident and scattered laser light, as well as suprathreshold and near-thermal x rays.

Author: R. A. Lerche

Major Contributors: H. Medeck and G. E. Phillips

A 662-keV X-ray Calibration Facility

We have routinely performed x-ray detector calibration for laser fusion diagnostics, using our x-ray facilities. For these calibrations, electrons or ions are directed onto solid targets, yielding characteristic sub-keV to 100-keV x rays. We have recently intensified our interest in extending the measurement of the suprathreshold x-ray spectrum in laser fusion experiments well beyond 100 keV, and eventually to 500 keV. This makes it necessary to calibrate our detectors accurately above 100 keV (Figs. 5-27 to 5-29).

Early efforts to calibrate an x-ray detector at 662 keV, using an $8\text{-}\mu\text{Ci}$ ^{137}Cs source, typically gave results that disagreed with normalized calculations by a factor of nearly 2. The goal of the work reported here is to set up a simple 662-keV x-ray calibration facility, with good geometry and adequate intensity, capable of calibrating our filter-fluorescer spectrometer (FFLEX) detectors.

Fig. 5-27. Schematic of the 662-keV ^{137}Cs x-ray calibration facility.

A 662-keV X-ray Calibration Facility

We have obtained a 6-mCi ^{137}Cs point source, encapsulated in a metal rod 5.1 cm long and 0.64 cm in diameter. The source emits monoenergetic 662-keV γ rays, and its

extensively measured spectrum is characteristic of the container and collimator geometries and the detector response. We took an autoradiograph to determine the exact location of the active region, and hence to obtain precise alignment of the source and detector collimator. For shielding and collimation, we used a lead pig which accepts the entire detector unit and provides at least 10 cm of shielding on the sides and 15 cm in front. A 25-mm hole was bored in the front section for collimation. This experimental setup is sketched in Fig. 5-27.

The absolute intensity of the ^{137}Cs source was determined by calibrating it with an 8- μCi ^{137}Cs IAEA standard. We used a Harshaw integral detector unit, which has a 10-cm by 10-cm sodium iodide crystal, to measure the fluences from both sources. This unit was placed in the pig in the same position that the FFLEX detectors occupy during calibration. The fluence observed gave an activity level of 5.77 mCi, indicating that the source provides adequate signals for the FFLEX detectors, but does not demand complicated equipment for safe handling procedures.

The spectra of the IAEA standard source and the 5.77-mCi source are compared in Fig. 5-28. The 32-keV x-ray peak in the IAEA source spectrum is a result of its thin-layer encapsulation, which allows the 32-keV energy to reach the detector. The thicker-walled rod of the 5.77-mCi source, however, conveniently filters out this unwanted energy. The IAEA spectrum also shows a 75-keV Pb K x-ray fluorescence peak, which is produced when the source is placed at the entrance of the 2.5-cm-diam, 15-cm-long Pb collimator. This in turn is a result of the low activity level (8 μCi) of the IAEA source, which necessitates close proximity to the collimator in order to obtain a reasonable fluence on the detector. The 5.77-mCi source, on the other hand, was positioned about 75 cm back from the collimator entrance, thereby reducing the Pb x-ray peak to a negligible level and at the same time allowing an acceptable dead time in the pulse-height analyzer.

Because the collimator material is thick and dense (15 cm of lead), we were concerned about 662-keV photons scattering off the collimator walls and into the detector being calibrated. This contamination can be reduced to a negligible level, however, by

Fig. 5-28. γ -ray spectra of (a) the IAEA standard ^{137}Cs source and (b) the 5.77-m Ci ^{137}Cs source.

Fig. 5-29. The sensitivity of a calibrated 3-mm NaI(Tl) detector coupled to a photomultiplier. ▼

calibrating the detectors far enough from the collimator such that the inverse square law is observed. After taking a series of measurements at increasing distances, to establish a safe position, we determined that a distance of 50 cm between the source and the defining collimator aperture provided sufficient fluence on the detector for easily measurable output currents, while essentially eliminating any significant scattering.

We have calibrated a number of FFLEX detectors of different sensitivities using this facility; Fig. 5-29 shows a sample result, obtained by coupling a 3-mm NaI(Tl) detector to a photomultiplier. Data below 100 keV were obtained with an x-ray machine, and the 662-keV point was obtained with our ^{137}Cs calibration facility. We calculated the curve using tabulated total absorption coefficients,²⁰ and normalized it to the experimental points below 100 keV.

The single point at 662 keV is in excellent agreement with the calculation, giving us confidence in the accuracy of the calculated detector sensitivity above 100 keV.

Authors: G. R. Leipelt, C. L. Wang, and H. N. Kornblum

22× Microscope Streak Camera

In 1980 we took a significant step forward in the measurement of target dynamics, an area that we are just beginning to address experimentally. We commissioned the streaked axisymmetric x-ray microscope system (Fig. 5-30), and began the parallel development of

Fig. 5-30. Detail of ASXRMS.

22× Microscope Streak Camera

several advanced subsystems which will improve the system's performance during the coming year. The new subsystems include an advanced axisymmetric x-ray microscope (ASXRMS), a 22× Kirkpatrick-Baez x-ray microscope (KBXRMS), and an automated

vacuum control system. Each of these subsystems is described below.

The streaked ASXRMS is also known as the Shiva Backlighting System; Fig. 5-30 shows the system at its location on the target chamber at Shiva. A brief description of the

Fig. 5-31. Additional detail of ASXRMS.

Fig. 5-32. Optics of the ASXRMS used at Shiva.

Fig. 5-33. Energy-dependent reflectivity of the ASXRMS.

streaked ASXRMS in its early design and construction stages appears in last year's annual report.²¹ After fabrication was completed, the system was in place by the end of May 1980. Alignment was carried out the first week in June, and the first streaked image showing target motion was obtained in mid-month. Figure 5-31 shows other key components of the Shiva Backlighting System in detail.

This system provides the required resolution in both time (15 ps) and space (3 to 5 μm) for measuring the dynamics of laser-fusion targets during irradiation. The temporally and spatially resolved data will provide important new physics information on x-ray emission, energy transport, and fluid dynamics.

The streaked ASXRMS uses a 22-power grazing-incidence x-ray reflector that focuses x rays by total external reflection from iridium-coated nickel surfaces.²¹⁻²³ The x rays first reflect from a hyperboloid surface of revolution, and then from an ellipsoid surface of revolution (Fig. 5-32). The x-ray grazing angle on the surfaces is 1° . Although the effective collecting solid angle of the full x-ray mirror (Fig. 5-33) is about 1.1×10^{-5} sr below 2 keV, it is useful to adjust the aperture of the annular optic to a sector with only 5% of the collecting area (5.5×10^{-7} sr). Limiting the aperture in this way increases the depth of field to $\pm 150 \mu\text{m}$; the breadth of field of the optic is $\pm 250 \mu\text{m}$.

We have measured the resolution of the ASXRMS (Fig. 5-34) to be 2.5 μm FWHM in the full-aperture case and 1.6 μm FWHM in the 5%-aperture case. The compound resolution of the streaked ASXRMS is limited to about 4.5 μm , however, by the ASXRMS magnification (22 $\times$) and the streak-camera resolution ($\approx 100 \mu\text{m}$). The resolution of the ASXRMS itself is only about 2 μm , so it does not contribute significantly to the overall resolution.

In order to test the minimum dimension resolvable with the streaked ASXRMS under field operating conditions (at the target chamber), we built and irradiated an x-ray-backlit resolution-grid target. Figure 5-35 shows the target and the results. The grid was made up of gold wires 3 μm thick and spaced 25 μm apart. The dark lines, just resolvable on the streaked image of the target, verified that objects with dimensions less than the anticipated 4.5 μm could, indeed, be resolved.

An ultrafast SXRSC of LLNL design^{24,25} is used to temporally resolve the image produced by the ASXRMS. The streak camera is sensitive to x rays with energies ranging from 100 eV to over 30 keV. The sensitivity of the streak camera at low x-ray energies is determined by the gold-coated and cesium-iodide-coated ultrathin carbon foils ($\approx 50 \mu\text{g}/\text{cm}^2$) used for the photocathode. While these foils provide sensitivity to very low photon energies, their fragility

Fig. 5-34. Resolution of the ASXRMS.

Fig. 5-35. Resolution-grid target for testing the dynamic resolution of the streaked ASXRMS.

Fig. 5-36. Beryllium-filter channel (0.8 to 2.0 keV) transmission folded with the ASXRMS transmission.

Fig. 5-37. Teflon filter channel (670 eV) transmission folded with the ASXRMS transmission.

puts stringent requirements on the pumping rates of the vacuum system. An automated vacuum controller (described later) and a complex system of valves provide safe and reliable operation for the system in routine use.

The streaked ASXRMS is capable of measuring absolute intensity distributions, although at present the sensitivity of the instrument has been calibrated only to a factor-of-2 accuracy. The measured threshold sensitivity at 1.5 keV is 4.4×10^{25} keV/cm² s-sphere, which matches the predicted value.

When the energy response of the streak camera is combined with the energy-dependent reflectivity of the mirror, a band of x-ray energies is established that has a useful overall sensitivity from 100 eV to 2 keV. Portions of this range can be selected with various filters. During 1980 we used the ASXRMS system with two different channels: one for energies from 0.8 to 2 keV, formed by a beryllium filter and the mirror cut off (Fig. 5-36); and, for other experiments, a 670-eV channel (Fig. 5-37) formed by a filter using the fluorine K-edge in teflon. Additional channels that may be of interest are carbon (280 eV), nickel (850 eV), and zinc (1.0 keV).

In measuring target dynamics with streaked x-ray imaging, it is critically important to determine the exact locus of points being observed on the target. If we

desire, for instance, to observe the dynamics of the final compression of an imploding fuel capsule, it is essential that the streak camera slit be placed across the center of the target image within only a few micrometres. The solution to this positioning problem is to provide an optical viewing system on the same line of sight as the x-ray imaging system.

Figure 5-31 shows the objective lens of the optical-alignment system mounted in the center of the ASXRMS mirror; this objective lens has the same focal length as the x-ray mirror, and the object and image focal points of the lens and mirror are superimposed. We then use two alignment cameras and a pellicle, inserted in the beam line, to observe both the image projected on the photocathode and the image projected on a reticle at the viewing window (Fig. 5-38). The reticle is accurately coaligned to the streak camera slit.

With these alignment procedures we have achieved alignment accuracies of better than $5\text{ }\mu\text{m}$ during shot sequences. We can view the image at the viewing window with either the unaided eye or a small pocket viewer, and a two-beam illumination system allows simultaneous viewing of the target in both transmitted (shadow image) and reflected light. Figure 5-38 shows a $150\text{-}\mu\text{m}$ glass microballoon at the Shiva target chamber center, viewed at the alignment reticle. The reticle lines have a width equal to $4\text{ }\mu\text{m}$ at the target plane.

From June to December 1980, the streaked ASXRMS was fielded on three target-irradiation series: Enterprise, Pinlite,

and NPIRE. The Enterprise series obtained information on

- The dynamics of the blowoff of laser-irradiated disk targets, observed by self-emission at 1.5 keV (Figs. 5-39 and 5-40).
- The acceleration of disks driven by the laser, observed with x-ray backlighting at 1.5 keV (Fig. 5-41).

The Enterprise data and their interpretation are discussed in "Space-Time Resolved X-ray Measurements from Accelerated Disk Targets" in Section 7.

During the Pinlite experimental series, the streaked ASXRMS was used to observe the

Fig. 5-39. Streaked x-ray image of a laser-irradiated gold disk at $7.7 \times 10^{14}\text{ W/cm}^2$.

◀ Fig. 5-38. A $150\text{-}\mu\text{m}$ glass microballoon viewed through the streaked ASXRMS alignment system.

Fig. 5-40. Streaked x-ray image of a laser-irradiated gold disk at $3 \times 10^{15}\text{ W/cm}^2$.

22× Microscope Streak Camera

670-eV emission from a disk irradiated by the laser at low intensity.

The x-ray backlighting system presently uses an axisymmetric x-ray microscope (22×) that was fabricated in 1977. Since that time, there have been significant advances in the technology of x-ray optical fabrication. During 1980 we have developed two new x-ray optics to provide advanced capabilities for the streaked x-ray microscope system: a 22× Mod II Wolter Axisymmetric X-ray Microscope (ASXRMS) and a 22× Kirkpatrick-Baez X-Ray Microscope (KBXRMS). The new 22× Mod II

Fig. 5-41. Streaked image of an x-ray backlit aluminum disk accelerated by laser irradiation.

ASXRMS will provide a larger effective solid angle (approximately 10 times larger), a higher x-ray energy cut off (3.5 keV), and a point-spread function with less energy in the wings. The KBXRMS will allow the streaked x-ray microscope system to operate at energies up to 10 keV with a very narrow energy window ($E/\Delta E \sim 30$), while maintaining the other characteristics of the streaked x-ray microscope system.

The 22× Mod II ASXRMS (Fig. 5-42) was completed by Visidyne, Inc., and their subcontractor, Random Devices, Inc., and delivered to the LLNL Laser Fusion Diagnostics Group in November. This mirror has a surface figure with an accuracy of 25 to 30 Å and a surface roughness better than 10 to 15 Å. We believe it is the most accurate aspheric optic of this complexity ever produced. Figure 5-43 compares images of an array of 2-μm-diam pinholes taken using the new mirror and the mirror currently used in the streaked ASXRMS system at Shiva, with 1.9-keV x rays. Figure 5-43 also compares the deviation from ideal surface profile of the old and new mirrors.

It should be noted that in Fig. 5-43 the photo taken with the new mirror has been given a heavy exposure to bring out the wings of the point-spread function, which extend out to more than 150 μm and account for much of the exposure between the pinhole images. The point-spread function of the older mirror has been successfully calculated theoretically from surface metrology data. The level of x-ray scattering

(a)

Fig. 5-42. 22× Mod II ASXRMS with nickel hyperboloid-ellipsoid reflecting surfaces.

(b)

in the new mirror is substantially reduced, and the resolution is improved to less than $1\text{ }\mu\text{m}$. Characterization of the new mirror will be completed in 1981, and it will then replace the older mirror in the ASXRMS system at Shiva.

The components of the 22× KBXRMS (Fig. 5-44) were fabricated during 1980; construction will be completed after the multilayer x-ray reflective coatings are deposited. X rays are focused in a KBXRMS by reflection at a small grazing angle from two cylindrical mirrors. Each cylindrical mirror by itself would form a line focus; when the mirrors are placed at right angles, however, and the x rays reflect once from each mirror, a point focus is produced. This is similar to crossing two optical refractive cylindrical lenses to produce a point focus.

The KBXRMS unit is designed to operate interchangeably with the ASXRMS in the streaked x-ray microscope at Shiva; the KBXRMS (like the ASXRMS) includes an alignment lens on its optical axis. The design resolution of the 22× KBXRMS is $3\text{ }\mu\text{m}$.

Fig. 5-43. Comparison of old and new ASXRMS surfaces and image quality. ▼

▲ Fig. 5-44. 22× KBXRMS with multilayer x-ray reflective coatings.

Fig. 5-45. X-ray backlighting vacuum control system.

Fig. 5-46. Vacuum map and control panel.

The reflective coatings on the KBXRMS mirrors will be of the multilayer interference type.²⁶ Each coating will have ~100 layers, with each layer only 10 to 20 Å thick. Alternating layers (comprising “layer pairs”) are of high and low index of refraction at the x-ray energy to be reflected. The layer pair spacing, d , is given by

$$d = \frac{\lambda}{2 \sin \theta}$$

where λ is the wavelength of the x rays to be reflected and θ is the grazing angle, 2° , for the new mirrors. Mirror coatings made in this way have a narrow band-pass for x-ray energies which they reflect. $E/\Delta E$ typically ranges from 25 to 75.

The coatings for the various versions of the 22× KBXRMS will have d-spacings chosen such that the x-ray bandpass energies match the x-ray emission-line energies of the x-ray backlighting sources of interest. Among the x-ray lines of interest are the He-like titanium line at 4.7 keV, and the He-like nickel line at 7.9 keV. Other x-ray lines with energies between these two will also be chosen. If mirrors without coatings are used in the new 22× KBXRMS, the unit will also serve as a subkilovolt x-ray microscope. The 22× KBXRMS is planned for use in high-energy x-ray backlighting, and should be useful for targets with cores compressed to 100 (or more) times the density of liquid D-T.

The streaked x-ray microscope vacuum controller is another subsystem that has undergone significant development during the past year. Early in the mechanical-design stages of the streaked x-ray microscope system, it became obvious that we would ultimately need an automated vacuum controller. This necessity was a consequence of both the complexity of the system and the high value of some of the optical and mechanical components. Automating the vacuum controller would make the system easy to use for target-room personnel and would also protect the system from user mistakes that could lead to costly and time-consuming component damage. Time constraints necessitated the use of a simpler, hard-wired vacuum controller with minimal interlocks, to ensure the streaked x-ray microscope was operational at the earliest possible date. The hard-wired controller provided reasonable safety when operated by the specially trained target-room personnel. The hardwired controller also allowed us to gain experience with the streaked x-ray microscope vacuum system, and to learn

what features should be incorporated into the automated system.

Our design philosophy for the automated vacuum controller is based on the design of the power conditioning and control system at Shiva.²⁷ The requirements of the final design were

- Both automatic and manual operation.
- Manual-mode interlocks.
- Limited remote-control and monitoring capability.
- Capability of handling 128 inputs and 128 outputs.
- Residence of all control intelligence in software, rather than hardware.
- Compatibility with existing Shiva controls.
- Easy and safe use by inexperienced operators.
- Easy reconfiguration with software.

The conceptual block diagram shown in Fig. 5-45 illustrates both the method of interfacing into the existing Shiva power-conditioning bus and the interconnection of the various types of hardware components within the system. The vacuum map and manual control panel shown in Fig. 5-46 provides for the common interface of the entire system, as well as the human interface to monitor and control functions on experiments. The many lights and pushbuttons on the front panel are either directly controllable or monitorable via software. This type of vacuum control system provides for quick system changes and easy operator use on very complex experiments; it is being tested at Shiva, and the software for its final implementation is in progress.

Authors: R. H. Price, B. A. Jones, and J. R. Zickuhr

Major Contributors: K. L. Andrus, D. L. Banner, T. Barbee (Stanford Research Center), D. E. Campbell, A. Cappabianca, J. J. Garr, K. J. Haney, R. L. Hanks, D. L. Holeman, D. W. Hughes, M. W. Kobierecki, L. N. Koppel, W. B. Laird, H. Medeck, W. M. Ploeger, K. D. Poor, G. Random (Random Devices Inc.), R. Rudd (Bendix), T. L. Schwab, V. W. Slivinsky, J. B. Tassano, C. E. Thompson, and T. Zehnpfennig (Visidine Inc.)

Microchannel Plate Reflector

We have used grazing-incidence x-ray mirrors as components of various soft x-ray spectrometers, including a broadband x-ray spectrometer, a soft x-ray streak camera, and a diffraction crystal spectrograph. The abrupt decrease in mirror reflectivity that occurs for photon energies greater than a certain critical energy (the value of which is a function of the mirror material and the grazing angle) has been exploited to define spectrometer channels and to provide discrimination against high-energy x rays in certain x-ray instruments.

Although single-surface mirrors offer the benefits described above, the use of these mirrors poses several practical problems. At grazing angles of incidence of the order of several degrees, a very long mirror must be employed to obtain a satisfactory instrument aperture; such long mirrors are difficult to fabricate and cause an increase in the size of the instrument package. During 1980, we tested a very compact multisurface mirror as an alternative to the long single-surface mirror. We found that a microchannel plate (MCP), used passively as an x-ray collimator, performs satisfactorily and predictably as an x-ray mirror.

An MCP is a glass wafer perforated by a large number of parallel smooth-bore channels, usually of circular cross section. As shown in Fig. 5-47, x rays will pass through the MCP only after suffering reflections on the channel walls, provided the angle θ

Fig. 5-47. Schematic of a microchannel plate used as a single-reflection x-ray mirror.

between the x-ray direction and the channel axes satisfies $\theta \geq \arccot L/D$, where L and D are the channel length and diameter, respectively. Coincidentally, the values of L/D with which an MCP can be built ($15 \lesssim L/D \lesssim 80$) produce minimum values of θ that correspond to the angles for which

Fig. 5-48. Measured x-ray reflectivity of a microchannel plate with $L/D = 40$.

Fig. 5-49. Measured x-ray reflectivity of a microchannel plate with $L/D = 80$.

Fig. 5-50. Real (δ) and complex (β) parts of the index of refraction, $\delta + i\beta$, of the channel walls in a microchannel plate. (The values of δ and β were chosen to fit the shape of the measured reflections—red curves—in Figs. 5-48 and 5-49.)

grazing-incidence x-ray mirrors are commonly used.

To experimentally investigate the performance of an MCP used as an x-ray mirror, we obtained several 18-mm-diam lead-glass MCP wafers with L/D values of 80 and 40 from Galileo Electro-Optics. An x-ray vacuum diffractometer, maintained by the LLNL X-ray Measurements Group, was used to measure the reflectivity of the samples over a range of angles of incidence. Figures 5-48 and 5-49 plot the reflectivity of the $L/D = 40$ MCP at $\theta = 1.43^\circ$ and of the $L/D = 80$ MCP at $\theta = 0.72^\circ$; the values of θ are those that satisfy $\theta = \arccot L/D$ in each case.

The reflectivities of the samples do vary in the way expected of grazing-incidence mirrors, with critical energies of about 1.1 and 2.1 keV. From a large set of measurements, we determined the real (δ) and complex (β) parts of the index of refraction of the channel walls, assuming that most of the x rays suffered only a single reflection while passing through the MCP. These data are shown in Fig. 5-50, where the values of δ and β were chosen to fit the shape of the measured reflection curves. We found that the MCP reflectivity is from 3 to 5 times less than that calculated for analogous single-surface mirrors.

We believe that the MCP has promise for use as a grazing-incidence x-ray mirror in applications that can tolerate a moderate loss in reflectivity. The MCPs may also find use as neutral-density x-ray filters for energies below the critical energy in high-level radiation fields and as debris shields for x-ray spectrometer systems.

Author: L. N. Koppel

Fuel Density Measurements Using Bromine L X-ray Line Imaging and Stark Profiles

Last year we suggested that compressed-fuel density can be determined in thick-walled ablatively driven targets, using x-ray spectroscopic methods.²⁸ Essentially, we

proposed that the D-T fuel mixture must be seeded with gases whose x-ray lines are produced at relatively low electron temperatures and easily transported through the thick, dense-glass pusher plasmas typical of 10X to 100X targets. Figure 5-51 illustrates the advantage of using bromine as a diagnostic seed gas; compared to argon, the energy of the bromine L → M shell transitions occurs in the minimum-opacity regime of the heated-glass pusher.

Conveniently, the mixing of bromine gas with the D-T fuel is also an important candidate for developing the radiochemistry technique for direct fuel ρR measurement.²⁹

In this article we describe a short series of spectroscopic measurements on bromine-seeded 10X-style fuel capsules that were directly irradiated with ~4-kJ pulses of 1.06- μ m laser light with a pulse width of ~200 ps (Ref. 30). Aside from determining radiochemistry collector efficiencies, the primary purpose of this set of target irradiations was to verify that identifiable bromine x-ray lines are produced, and that these x rays can be spatially imaged and their stark profile measured. Since the use of L x rays to determine plasma density from Stark-broadened line shapes is somewhat unconventional, a parallel effort was initiated to calculate Li-like bromine L x-ray line shapes for moderate-density (10^{23} to 10^{24} e⁻/cm³) plasmas.

On one shot in the measurement series we observed some bromine L x-ray lines (see Fig. 5-52). The energies and relative intensities (gf values)³¹ of these lines are shown in Table 5-3. A Stark-broadening analysis for plasma density was performed on the two strongest transitions, those being $1s^23d(^2D_{3/2}) \rightarrow 1s^22p(^2P_{3/2})$ and $1s^23d(^2D_{5/2}) \rightarrow 1s^22p(^2P_{3/2})$. Using a new Stark-broadening theory³² and a line-profile-fitting code,³³ we were able to derive the electron density of the fuel at the time of maximum bromine L x-ray emission. Figure 5-53

▲ Fig. 5-51. The effect of glass pusher opacity on Br and Ar x-ray lines.

Fig. 5-52. Portion of a microballoon x-ray spectrum showing bromine L lines.

Initial configuration	Final configuration	E_x (eV)	gf
$1s^23s$	$1s^22p_{1/2}$	2101	0.0303
	$1s^22p_{3/2}$	2044	0.0725
$1s^23d_{3/2}$	$1s^22p_{1/2}$	2144	1.29
	$1s^22p_{3/2}$	2088	0.266
$1s^23d_{5/2}$	$1s^22p_{3/2}$	2093	2.38
$1s^23p_{1/2}$	$1s^22s$	2191	0.256
$1s^23p_{3/2}$	$1s^22s$	2208	0.471

◀ Table 5-3. Transition energies and gf values for Li-like bromine x-ray lines.

Fig. 5-53. Comparison of measured (data points) and theoretical (curve) Br L x-ray line shapes.

gives a comparison of measured (data points) and theoretical (curve) line shapes. The density was determined to be $\rho_e \sim (3 \pm 2) \times 10^{23} \text{ e}^-/\text{cm}^3$. This corresponds to a relatively low-density implosion ($\sim 10\times$ liquid D-T), which was to be expected from the target design and irradiation conditions. More noteworthy, however, is the mere observation of these lines, since we anticipated their identification and line-profile analysis to be much more difficult.

We have planned experiments to utilize bromine line spectroscopy in more sophisticated targets, and will attempt a comparison with fuel and pusher density determinations made using the radio chemistry diagnostic. Successful application of the method requires a higher fill pressure of bromine; this problem area is discussed in "Diagnostic Gas Fills" in Section 4.

Authors: D. L. Matthews and R. W. Lee
(Imperial College, London)

Fabrication of High-Aspect-Ratio Microstructures for High-Energy X-ray and Particle-Imaging Applications

As laser fusion target performance continues to improve toward the achievement of higher compressed $\rho\Delta R$, we must adapt our imaging diagnostics, designed to probe the inner structure of the compression, to the use of higher-energy radiations. Compressed tamper materials (such as glass) with $\rho\Delta R$ in excess of 10^{-1} g/cm^2 strongly attenuate low-energy (1 to 6 keV) x rays, and prevent the escape of many thermonuclear-burn reaction products (such as 3.5-MeV α particles from D-T reactions and 3-MeV protons from D-D reactions). We have therefore focused our interest on the use of high-energy (10 to 100 keV) x rays to probe the structure of compressed targets, and on the use of highly penetrating thermonuclear reaction products (such as neutrons from D-T reactions and 14.7-MeV protons from D-He³ reactions) for imaging the region of thermonuclear burn. In pursuit of such goals, we have developed techniques for the fabrication of very thick (50 to 200 μm) gold Fresnel zone plates, with narrow (3 to 15 μm) line widths for high-resolution coded imaging of high-energy x rays and D-He³ protons.³⁴

Conventional UV lithographic techniques have proved inadequate for the fabrication of zone-plate structures thicker than 40 μm (Ref. 35). We have therefore switched to a dry etching technique called reactive ion etching (RIE),³⁶ and successfully used it to produce zone-plate patterns up to 134 μm thick (Figs. 5-54 and 5-55). The RIE technique is schematically illustrated in Fig. 5-56. The thick polymer layer to be etched uniformly coats a gold plating base supported by a thick glass substrate. On top of the polymer is a thin aluminum zone-plate pattern produced by conventional UV lithographic techniques. This assembly is placed on the cathode of an rf glow discharge in oxygen.

Although details of the etching process are not fully understood, it appears that oxygen ions—extracted from the positive column, accelerated across the cathode fall, and impinging on the polymer surface—act as a catalyst for a reactive process which locally volatilizes the polymer. The aluminum zone-plate pattern on the polymer surface is not significantly attacked by the etching process, so it can act as a pattern mask for the process.

The success of the RIE process is sensitive to discharge parameters; we have found, however, that it operates successfully with rf power = 0.3 W/cm², O₂ pressure = 10⁻² Torr, and bias voltage = 525 V. With these

parameters, RIE yields an etching rate in the polymer of approximately 1900 Å/min.

Figures 5-54 and 5-55 each show three views of recent RIE results in two different polymers: polyimide, and Spurr low-viscosity embedding material (SLVEM), a high-purity epoxy. These polymer patterns are used as molds for a subsequent electroplating step in the zone-plate fabrication process.³⁷ Both patterns have aspect ratios (of height to minimum line width) close to 10:1; the pattern in Fig. 5-55 is 50 μm high with a minimum line width of 5 μm, and the pattern in Fig. 5-56 is 134 μm

Fig. 5-55. Etched zone-plate pattern in 134-μm-thick SLVEM.

◀ Fig. 5-54. Etched zone-plate pattern in 50-μm-thick polyimide.

Point Imaging with X Rays

high with a minimum line width of $15\text{ }\mu\text{m}$. In Fig. 5-55, the textured surface in the etched regions is caused by redeposition of

Fig. 5-56. Schematic of ▲ reactive ion etching (RIE) technique.

Fig. 5-57. Schematic of ▼ PIX method.

sputtered cathode material onto the sample during the etch process; this problem has been solved by masking the base anode surface. In Fig. 5-56, trace amounts of epoxy still remain in some of the etched areas.

We have encountered problems when attempting to exceed 10:1 aspect ratios in samples thicker than $100\text{ }\mu\text{m}$. We believe such problems are due to fringing field effects within the thick pattern that alter the oxygen ion trajectories. We are exploring new processes that will alleviate fringing field effects and allow us to produce gold zone plates with aspect ratios greater than 10:1 and thicknesses greater than $200\text{ }\mu\text{m}$.

Authors: N. M. Ceglio, G. F. Stone, and A. M. Hawryluk (Massachusetts Institute of Technology)

Major Contributors: D. R. Ciarlo, D. Okubo, and G. L. Howe

Point Imaging with X Rays (PIX)

One of our diagnostic-program goals is to develop the capability for taking two-dimensional pictures of imploding fuel capsules so that we can determine implosion velocities and measure implosion sphericity and the fluid stability of shell interfaces. X-ray backlighting is our leading candidate for achieving this goal, and one backlighting option is to stop the action via a short x-ray pulse that has been produced by a short laser pulse.

It is becoming clear that, as we proceed to larger laser systems and larger fuel capsules that achieve higher values of ρr for the fuel, we will need higher x-ray energies for backlighting to provide sufficient penetration capability. Targets in the Novette chamber will require a 5-keV backlighter to characterize the implosion; Nova targets will require 8 keV to image the outer target shell and 75 keV to penetrate the inner shell of typical target structures.

Measurements of the efficiency of converting laser light to x-ray lines are reported in "Characterization of X-Ray Backlighting Sources" in Section 7: Using those measurements, we calculated that in order to backlight a large (millimetre-scale)

target with an extended source at 8 keV we would require a 10-kJ (100-TW) laser. This would be an extremely expensive back-lighting source. An alternative scheme is to go in the opposite direction: rather than provide a millimetre-scale backlighting source behind the target, we can focus the laser down to produce a point source and then use that x-ray source in projection mode. This method of point-imaging with x rays (PIX) is illustrated in Fig. 5-57. The Cu filter is used to selectively transmit the line radiation from the Cu K α source to the recording medium. Synthetic multilayer x-ray dispersion elements³⁸ are also being considered as wavelength-selective mirrors to filter x-ray energy incident on the recording film.

We believe that the 10-kJ requirement for an extended source can be relaxed to 1 kJ (a 10-TW laser) using the PIX concept. With 1 kJ of incident laser energy and a conversion efficiency of 10^{-4} (see "Characterization of X-Ray Backlighting Sources" in Section 7), the x-ray fluence at the film plane in Fig. 5-57 is

$$(1 \text{ kJ} \times 10^{-4}) \frac{1}{4\pi(10)^2} \approx 10^{-4} \frac{\text{J}}{\text{cm}^2} \quad (1)$$

Only 10^{-7} J/cm^2 is necessary to provide adequate film exposure. If the laser is focused to a 100- μm spot size, and if the x-ray spot size is the same as the laser spot size, then the "camera" resolution is 100 μm . If, however, we limit the x-ray source by replacing the large Cu backlighting source with a 10- μm Cu microdot on a thin parylene substrate, then the Cu K x rays (at 8.0 keV) will be emitted from a much smaller target, and the camera resolution will be reduced to 10 μm . The price we must pay is that the x-ray fluence at the film plane is reduced by a factor of $(100/10)^2$, but this is still an order of magnitude more than is needed to provide adequate film exposure directly without using electronic amplification.

This method for two-dimensional imaging can be extended to higher x-ray energies (75 keV) by making the backlighter target a Au fluorescer (75 keV) whose shape is a long rod, 5 μm in diameter and 80 μm long. This diameter is chosen to be one range for 100-keV electrons (laser intensity is 10^{17} W/cm^2), and the length is thin for the Au K α fluorescence.

We can also extend PIX to provide multiexposure snapshots of the implosion by using a series of 100-ps, 1-kJ laser pulses separated in time to provide a sequence of short x-ray bursts. The backlighter target would actually be a stack of microdots 2 mm apart; each microdot would be so thin that it can be completely vaporized by a single laser pulse. The n th microdot in the stack would not be there when the $(n + 1)$ laser pulse arrived. The microdot elements will be chosen to provide appropriate x-ray lines tailored to each target type. Several film packs gated with a microchannel plate would record the images. This multiexposure concept is illustrated in Fig. 5-58.

We are planning experiments to test the PIX concept with Shiva. The first set of experiments, dubbed PIXE, will determine if we can, indeed, produce an intense, short burst of 8-keV x rays.

Author: V. W. Slivinsky

Major Contributor: R. H. Price

Fig. 5-58. Extended PIX concept, using three x-ray flashes for stop-action backlighting.

Evaluation of X-ray Backlighting Diagnostics for Nova and Novette Laser Targets

During the past year we performed experiments at Shiva to determine the characteristics of high-energy line emitters which are potential backlighting sources for intermediate- and high-density targets (see "Backlighter Characterization Experiments" in Section 7). We will here assess the impact of the data discussed in that article, on the basis of a "typical" Nova target.³⁹

It should be remembered that the questions of symmetry and stability which backlighting addresses can be studied with specially designed targets. For example, a target similar to the "typical" one, but with a lower-Z outer pusher, could be used to diagnose the inner/outer shell collision at 8 to 9 keV, while much of the outer-shell motion could be seen with easily obtained low-energy backlighting sources.

Table 5-4 summarizes the pertinent parameters of the typical Nova target which are used in the following analysis, and gives the requirements imposed on imaging schemes by these parameters.

Backlighting can be used to obtain two types of data about the target presented in the table. The first type, two-dimensional snapshots, (1) provides information on symmetry and stability, (2) requires precise knowledge of flash time, (3) is obtained either with short backlighter flashes or fast

shuttered systems, and (4) allows us to obtain stability information by imaging a sector of the target. One-dimensional time-resolved data, on the other hand, (1) provide dR/dt (velocity) and rough symmetry information, (2) require long backlighting pulses, (3) allow us to obtain dR/dt by imaging only half of the target, and (4) require that we image the full target to obtain any information on symmetry.

Backlighting at or above 20 keV would provide valuable information, but we need to develop new imaging schemes for this energy range (see the previous article). Data obtained thus far show that the laser intensities required to turn on backlighter lines increase with the line energy, while the conversion efficiency decreases slightly. At this time it is quite unlikely that laser power requirements for any new imaging system will be less than that required for backlighting at 8 to 9 keV. We will therefore discuss requirements on the basis of the characteristics of Ni and Zn lines, which are useful for backlighting the outer pusher.

Two-dimensional flash imaging could be performed using either zone-plate cameras or Kirkpatrick-Baez/Barbee microscopes (see "22× Microscope Streak Camera" earlier in this section). If large sources are available, the above instruments could be used with gated microchannel plates (see "Optically Driven Semiconductor (Auston) Switch" later in this section). For a spot diameter of 1 mm and a laser-pulse duration of 50 to 100 ps, the constraining factor is the laser intensity required to turn on the appropriate x-ray line. At a laser wavelength of $1.06 \mu\text{m}$, the energy required is 10^{16} W/cm^2 (5 to 10 kJ). Recent data obtained at $0.35 \mu\text{m}$ show that lines can be excited at short pulse lengths at a much lower intensity than is necessary at $1.06 \mu\text{m}$. If we optimistically predict that x-ray lines can indeed be turned on at lower laser intensity for a wavelength of $0.53 \mu\text{m}$, we would still need on the order of 10 TW of $0.53\text{-}\mu\text{m}$ light. This option is therefore marginal at best.

If an adequate point source can be found, pinhole imaging of x rays (see the previous article) could be used instead of the systems described above. For point sources, the source size (5 to $10 \mu\text{m}$) is defined by the required resolution. Assuming $f/2$ optics and a $10\times$ diffraction-limited laser spot ($50 \mu\text{m}$

Table 5-4. Characteristics of a typical Nova target, and requirements they impose on x-ray backlighting schemes.

Shell	Dimension	Material	Characteristic time for backlighting	
Outer	2 mm	Low-Z ablator, TaCOH pusher	5 ns	
Inner	300 μm	High-Z pusher, low-Z fuel	2 ns	
Requirements				
X-ray energy	Characteristic dimension	Resolution		Comment
(ke V)	(μm)	(μm)	(ps)	
9 to 10	1000	5 to 10	50 to 100	Outer-pusher stability or velocity
	2000	5 to 10	50 to 100	Outer-pusher symmetry
20 to 25	200	2	10	Inner/outer-pusher collision
100	20	2	20 to 40	Inner pusher

at $1.06\ \mu\text{m}$) the required laser power to turn on the x-ray line at a wavelength of $1.06\ \mu\text{m}$ is 200 GW. The limitation is now due to the minimum x-ray flux required for imaging. Initial estimates of the laser power necessary to obtain the appropriate x-ray flux level from a $5\text{-}\mu\text{m}$ spot is 10 TW; for a $10\text{-}\mu\text{m}$ spot, 2.5 TW would be necessary. This level is available with a Nova beam.

Streaked radiography can be performed using a Kirkpatrick-Baez/Barbee microscope or microfresnel lenses coupled to a streak camera. If the appropriate alignment capability is available, only half of a target diameter need be used for dR/dt determination. Any attempt at diagnosing symmetry (large perturbation only), however, will require imaging the full diameter of the target onto a streak camera slit, or the full target onto a framing camera photocathode.

Until a major effort is mounted towards improving the tube characteristics, streaked radiography is limited by the streak camera performance. Hence the 12-mm useful slit width imposes a maximum magnification of 12:1 (radius image only) or 6:1 (diameter image). The given $100\text{-}\mu\text{m}$ resolution of the streak tube translates at best into $8\text{-}\mu\text{m}$ resolution at the target: this value is just within the limits of desired resolution.

Laser energy estimates can be made using projected microscope/streak camera requirements. To have three orders of magnitude of dynamic range with the 12:1 magnification system, the x-ray flux required at the target is $10^{27}\ \text{keV}/\text{cm}^2\text{-sr}$. Under these circumstances, the required laser intensity is dictated by the threshold required to turn on the 8- to 9-keV x-ray lines at a laser wavelength of $1.06\ \mu\text{m}$. At $\lambda = 0.53\ \mu\text{m}$, however, it is probable that the lines can be turned on for $I_L \sim 4 \times 10^{15}\ \text{W}/\text{cm}^2$. Recall that the conversion efficiencies at $\lambda = 1.06\ \mu\text{m}$ and $0.53\ \mu\text{m}$ are similar. Hence, for an astigmatic focus of 1 mm by $50\ \mu\text{m}$ and a 5-ns streak, the requirements will be met for $I_L \sim 4 \times 10^{15}\ \text{W}/\text{cm}^2$ (10 kJ). These laser parameters can be obtained with a Nova beam, and will provide a dynamic range of 10^3 . A Shiva beam could also be used if a reduced dynamic range is acceptable.

While large fields of view and high backlighting energies are necessary to investigate

the "typical" Nova target, backlighting can be used for other experiments. As mentioned previously, targets with lower-Z pushers (both outer and inner) would provide normalization data for computed symmetry and stability analyses; low-Z pushers combined with seeded fuel might provide means of clearly identifying the inner boundary of the inner pusher. Backlighting can also be used to investigate optical depths of various types of plasmas encountered in our experiments.

These applications require lower-energy backlighters which can be turned on at low laser intensity for long pulses. For instance, streaked radiography at 4.5 keV can be performed with a 1-TW laser over a 1-mm by $50\text{-}\mu\text{m}$ field of view with close to three orders of magnitude of dynamic range. A separate backlighting arm capable of producing 1 to 2 TW would therefore enable us to perform numerous experiments without perturbing the symmetry of irradiation. A laser beam on the order of those used at Shiva would provide useful flexibility.

Novette Targets

We can perform a similar analysis for Novette targets. The "typical" Novette target considered here has a glass pusher which can be backlit at 4.7 keV for much of its travel. The Novette target is smaller in size than the Nova target; Table 5-5 summarizes its characteristics. In addition, numerous experiments designed to study specific issues of hydrodynamic motion, symmetry, and stability can be profitably performed at Novette using low-energy ($\lesssim 4.7\ \text{keV}$) backlighting.

	Dimension	Material	Characteristic time for backlighting
Ablator	$250\ \mu\text{m}$	Low-Z	2.0 ns
Pusher	$200\ \mu\text{m}$	SiO_2	2.0 ns
Fuel	—	—	0.9 ns
Energies required			
Shock through ablator			1.7 keV
Pusher motion: outer edge, and inner edge at early times			4.7 keV
Pusher inner edge, late time but not to peak compression ^a			8 to 9 keV

^aExperimental data are difficult to interpret without significant help from calculated behavior.

Table 5-5. Characteristics of a typical Novette target, and the backlighter energies they require.

Backlighting at Novette can best be provided with the following:

- A separate backlighting arm, allowing two-sided irradiation at 300 GW, for pulse lengths of 2 to 3 ns minimum duration, with backlighting at or below 4.7 keV.
- The use of a Novette arm for some experiments at higher x-ray energies, using one-sided target irradiations.

More experiments will be performed to increase our knowledge of backlighter characteristics and in particular to determine the potential of the PIX systems. The use of shorter laser wavelengths to lower the threshold of line excitation will allow streaked or framing radiography to be performed at higher backlighting energies.

In summary, our current knowledge of potential backlighting sources and recording instruments show that backlighting will be a useful tool at Novette, for 1.06- μm irradiation of the backlighters. At Nova, shorter wavelengths will be needed to irradiate the backlighting sources.

Authors: V. C. Rupert and D. L. Matthews

Direct Fuel $\langle \rho R \rangle$ Measurements by Neutron Activation

The compressed-fuel areal density, $\langle \rho R \rangle$, is one of the most important quantities in ICF, as it is one of the parameters we can use to track our progress towards thermonuclear ignition. For simple targets, several methods have been used to estimate the fuel $\langle \rho R \rangle$, including

- Measurement of α -particle collisional energy downshifts.^{40,41}
- Two-dimensional spatial imaging of α particles⁴² and suprathreshold x rays.⁴³
- One-dimensional spatial imaging of x-ray lines emitted from a trace of diagnostic gas mixed with the D-T fuel.^{44,45}
- Stark-broadening measurements of diagnostic-gas x-ray lines (see "Fabrication of High-Aspect-Ratio Microstructures for High-Energy X-ray and Particle-Imaging Applications," earlier in this section).
- X-ray backlighting.⁴⁶

With the exception of backlighting, these methods are not applicable to more advanced targets, where pushers attain high $\langle \rho R \rangle$'s and thus become opaque to α particles and x rays. To avoid this difficulty, we have developed a technique whereby the compressed $\langle \rho R \rangle$ of the pusher is first measured by neutron activation^{47,48} and then used, in conjunction with other measured target parameters, as input in computer simulations to derive the fuel $\langle \rho R \rangle$.⁴⁵ Several methods have been suggested for measuring the fuel $\langle \rho R \rangle$ of advanced targets directly, including

- Ion-beam probing.⁴⁹
- Measurement of knock-on deuterons and tritons produced by collisions with 14-MeV neutrons.⁵⁰⁻⁵²
- Measurement of the ratio of D-D to D-T reactions in initially tritium-free targets.⁵³

We have been studying still another approach that involves neutron activation of a diagnostic (tracer) gas mixed with the fuel. In this article, we explain this tracer technique and possible variations that are applicable to the next generation of target designs. We also assess the present feasibility of this technique for use with current targets, and we discuss some of the attendant difficulties.

For simplicity, we assume the following:

- The target has spherical symmetry.
- Both the fuel and tracer are confined to a sphere of radius R at peak burn.
- The neutrons are produced uniformly over the fuel volume for a time that is short compared to any hydrodynamic time.
- The densities of the fuel and tracer are spatially uniform.

With these assumptions, the number of activated tracer atoms, N^* , is given by

$$N^* = \frac{3}{4} \left(\frac{\sigma}{A} \right) N_0 Y_n f \langle \rho R \rangle_{\text{tracer}} \quad (2)$$

where σ is the cross section of the neutron-induced reaction, A is the atomic weight of the tracer, N_0 is Avogadro's number, Y_n is the total neutron yield, f is the isotopic abundance of the source nuclide in the tracer, and $\langle \rho R \rangle_{\text{tracer}}$ is the density-radius product of the tracer. The factor of 3/4 is included because $3/4 \rho R$ represents the average attenuation length for neutrons that are distributed uniformly and emitted

isotropically within a sphere of radius R and that interact with atoms at constant density, ρ , within that volume.

Using the above assumptions, we can also show that

$$\langle \rho R \rangle_{\text{tracer}} = \langle \rho R \rangle_{\text{fuel}} \left(\frac{\rho_{\text{tracer}}}{\rho_{\text{fuel}}} \right), \quad (3)$$

where $\rho_{\text{tracer}}/\rho_{\text{fuel}}$ is the initial density ratio of the fuel and tracer. Thus, the fuel $\langle \rho R \rangle$ can be experimentally determined from independent measurements of the number of activated atoms, the total neutron yield, and known initial target parameters.

The number of decays of the activated atoms that can be detected is given by

$$N = N^* I \eta_c \eta_d e^{-\lambda t_L} (1 - e^{-\lambda \Delta t}), \quad (4)$$

where I is the probability of decay by the mode used for detection, η_c is the fraction of activated atoms collected, η_d is the detector efficiency, λ is the decay constant, t_L is the loading time between the implosion and the beginning of the counting period (for our present system this is ~ 30 s), and Δt is the length of the counting period, usually taken to be about twice the half-life. For current-generation targets, high-density performance is achieved with low thermonuclear yields, so the numbers of activations and of subsequently detected decays are typically very small (10 to 100 counts). For N detected decays and a background rate, B , Poisson statistics give a counting error of

$$\% \text{ Counting error} = \frac{100 \sqrt{N + 2B\Delta t}}{N}. \quad (5)$$

Consequently, we see that it is necessary to have a very low-background, high-efficiency detection system.

The selection of a suitable diagnostic gas for our neutron activation technique is dictated by numerous factors:

- Target fabrication constraints and diagnostic interpretation require that the tracer be a gas that mixes uniformly with the fuel.
- The atomic number of the tracer preferably should be low so as not to seriously degrade target performance.
- Selected nuclei must either have a large natural isotopic abundance or be available in an isotopically enriched form to minimize the neutron-yield requirement.
- The neutron-interaction cross section at 14 MeV should be large.
- The half-life of the activated nuclei should be short enough that the specific activity is high but long enough that the target debris can be effectively retrieved. For present experiments, this requirement limits us to nuclei with half-lives from 0.5 to 20 min.
- The decay scheme must have a predominant decay route that produces radiation that can be easily detected.
- An isotope of the tracer element must exist that can be used as a radioactive mass-fraction tracer for collection-fraction determination. A 4π -sr collection of the target debris from an ICF implosion experiment is exceedingly difficult.⁵⁴ The use of a radioactive mass-fraction tracer readily allows the measurement of collection efficiency for arbitrary collection designs.

Tables 5-6 and 5-7 list candidate tracer gases. Table 5-6 gives those tracers whose activation products decay by $\beta\gamma$ or β^+

Gas	HBr	Ar	N ₂	⁷⁸ Kr
Reaction	⁷⁹ Br(n,2n) ⁷⁸ Br	⁴⁰ Ar(n, γ) ³⁷ S	¹⁴ N(n,2n) ¹³ N	⁷⁸ Kr(n,p) ⁷⁸ Br
σ (millibarn)	862	13	6	107
f	0.503	0.996	0.996	0.99 ^b
Decay mode (MeV)	β^+ (2.55)	β^- (1.75), (3.103)	β^+ (1.20)	β^+ (2.55)
I	0.92	0.94	1.0	1.0
η_d	0.55	0.30 ^a	0.45 ^a	0.55
$t^{1/2}$ (min)	6.45	5.505	9.96	0.833
B (cpm)	1.5	0.5	1.5	1.5
$\langle \rho R \rangle Y_n$ (10%)	9.2×10^6	4.7×10^8	8.1×10^8	4.0×10^7
$\langle \rho R \rangle Y_n$ (30%)	1.9×10^6	7.7×10^7	1.8×10^8	5.7×10^6
^a Estimated				
^b Enriched				

Table 5-6. Candidate tracer gases that produce activation products which decay by $\beta\gamma$ or γ^+ emission.

Direct Fuel $\langle\rho R\rangle$ Measurements by Neutron Activation

emission, while Table 5-7 lists gases whose activation products decay by isomeric transitions. In addition to containing the relevant parameters discussed above, the last two lines of each table give the fuel $\langle\rho R\rangle$ -neutron-yield product [$\langle\rho R\rangle Y_n$] that would produce counting errors of 30% and 10%. We use the values on these two lines as figures of merit in judging the sensitivity of each tracer. For these $\langle\rho R\rangle Y_n$ values, we assume the spherical implosion of a capsule containing 50 atm of D-T mixed with 0.1 atm of tracer gas. We further assume that 50% of the target debris is collected, that the sample loading time is 30 s, and that the counting time is twice the half-life. Enriched isotopic abundances were used when known to be available.

We see that enriched ^{80}Kr has the lowest $\langle\rho R\rangle Y_n$ requirement of any of the suggested tracers. Furthermore, because the microballoon fabrication technique that we use introduces the diagnostic gases and the D-T fuel into the microballoon at elevated temperatures, a noble-gas tracer like ^{80}Kr is less likely than other tracer gases (e.g., HBr) to react with the glass wall. We do not presently have the facilities, however, for recovering and recycling an isotopically enriched gas after the fill process. Recovery is necessary due to the very high cost of these gases.

All of the activation products listed in Table 5-7 decay by the emission of one or two gamma rays with energies of 100 to 500 keV. These gamma rays can be efficiently detected by a large-volume ($>120\text{ cm}^3$) high-purity germanium-well detector. The collector foil could be placed in the well of such a detector to give nearly 4π coverage. Existing systems have absolute

detection efficiencies of 80% at 100 keV and use NaI anticoincidence shields to reduce the background to $\sim 0.1\text{ cpm/keV}$.

It will be convenient to have a selection of tracers that decay in a manner similar to that given in Table 5-7, because the future generations of targets will have multiple shells, and some targets may have a central igniter fuel separate from the main fuel which is in an outer shell. In such multishell targets, the $\langle\rho R\rangle$ of each shell material and fuel region must be measured. These simultaneous $\langle\rho R\rangle$ measurements could be accomplished by placing a different tracer from Table 5-7 in each of the various target regions; the $\langle\rho R\rangle$ values would then be found from the peak areas of the isomeric gamma rays, which are easily resolved by the detector mentioned above. A difficulty may arise, however, with regard to the collection of target debris. We believe the process by which the target material attaches to our collector foils is chemical in nature (see the following article); thus, noble-gas collection efficiencies may be low.

Despite some of the advantages of the noble-gas tracers mentioned above, we have elected, at least initially, to investigate the feasibility of using HBr as a tracer. HBr is attractive because it requires a relatively low $\langle\rho R\rangle Y_n$ product, and it can be introduced into our glass microballoons with only minor modifications to existing drop towers. HBr also has the advantage over noble gases in that our existing NaI-plastic coincidence spectrometer, shown in Fig. 5-59, can be used with (D-T + Br)-filled glass microballoons to simultaneously measure both the pusher and fuel $\langle\rho R\rangle$. Simultaneous measurement is possible because activated bromine decays by the emission of a

Table 5-7. Candidate tracer gases that produce activation products that decay by isomeric transitions.

Isotope	^{80}Kr	^{126}Xe	^{128}Xe	^{136}Xe
Reaction	$^{80}\text{Kr}(n,2n)^{79\text{m}}\text{Kr}$	$^{126}\text{Xe}(n,2n)^{125\text{m}}\text{Xe}$	$^{128}\text{Xe}(n,2n)^{127\text{m}}\text{Xe}$	$^{136}\text{Xe}(n,2n)^{135\text{m}}\text{Xe}$
σ (millibarn)	415	700	840	750
f	0.90 ^a	0.02 ^a	0.019	0.99 ^a
Decay mode (keV)	$\gamma(130)$	$\gamma(141), \gamma(112)$	$\gamma(297)$	$\gamma(527)$
I	1.0	1.0	1.0	0.996
η_d	0.75	0.80	0.40	0.16
$t_{1/2}$ (min)	0.833	0.95	1.17	15.3
B(cpm)	0.1	0.2	0.1	0.1
$\langle\rho R\rangle Y_n$ (10%)	8.0×10^6	1.9×10^8	3.1×10^8	1.4×10^7
$\langle\rho R\rangle Y_n$ (30%)	9.1×10^5	2.2×10^7	3.6×10^7	2.0×10^6
^a Enriched				

positron, which we can detect by observing the positron kinetic energy deposited in the plastic detector in coincidence with annihilation radiation appearing as a 1022-keV signal in the NaI(Tl) detector.

Using a ^{64}Cu source, we have determined that the positron detection efficiency is 55%. The pusher $\langle \rho R \rangle$, on the other hand, is determined by observing the $\beta\gamma$ emission from the decay of ^{28}Al , an activation product

created in the pusher by $^{28}\text{Si}(n,p)^{28}\text{Al}$ reactions. The β particle, having an endpoint energy of 3 MeV, is detected in the plastic detector in coincidence with the 1780-keV γ ray detected by the NaI(Tl) detector. The measured detector efficiency for the decay of ^{28}Al is 35%.

Before HBr can be used to make a fuel $\langle \rho R \rangle$ measurement on current targets, we must eliminate some uncertainties having to

Fig. 5-59. NaI-plastic coincidence spectrometer.

Direct Fuel $\langle \rho R \rangle$ Measurements by Neutron Activation

do with debris collection, counting background, and target characterization. Preliminary experiments addressing the collection of bromine target debris are described in the following article. These experiments indicate that it may be possible to collect about 50% of the activated bromine atoms on titanium collector foils.

We have found, however, that titanium can be activated by fast (> 3.8 MeV) protons from the target, resulting in the formation of ^{47}V , which decays by positron emission and contributes to the background for ^{78}Br detection. Other sources of background include the usual cosmic-ray and natural-radioactivity components as well as

Fig. 5-60. NaI(Tl) anticoincidence guard detectors surrounding the well detector.

Fig. 5-61. Number of expected counts as a function of target performance.

Compton-scattered 1780-keV gamma rays from ^{28}Al . All these background sources, except for the foil activation background, can be reduced by the use of two very large NaI(Tl) anticoincidence detectors, each 50 cm in diameter and 38 cm long, that completely surround our 25-cm by 25-cm well detector (Fig. 5-60). The guard detectors operate in anticoincidence with the inner detectors and offer a 10-cm-thick active shield against incoming stray radiation. They also serve as anti-Compton detectors for photons originating from a sample located in the well detector. The background reduction afforded by the guard detectors has not yet been determined, but we expect it to be at least a factor of 2.

To make a fuel $\langle\rho R\rangle$ measurement, it is necessary that most of the Br be mixed with the fuel rather than located at the fuel-pusher interface or within the pusher itself. Chemical analyses of a large batch of microballoons filled in a Br_2 -containing drop tower showed only 5% of the bromine to be trapped in the glass walls. We have designed a more sensitive analysis that uses the Los Alamos Omega West reactor to irradiate our Br-filled microballoons; by thermal-neutron capture, ^{82}Br (half-life = 35 h) is formed from natural ^{81}Br , a 50%-abundant isotope. By comparing the measured ^{82}Br activity with the activity of a known quantity (0.1 mg) of iron that serves as a fluence monitor, we will soon be able to accurately assay the quantity of bromine in a single microballoon. Furthermore, by comparing the ^{82}Br activity of a microballoon to the activity found in the glass shards after the microballoon is crushed, we can find the fractional quantity of bromine in the fuel region (assuming that the bromine mixed with the fuel escapes when the microballoon is crushed).

Taking the best estimates of background and collection efficiency, we show in Fig. 5-61 the number of expected counts as a function of the $P_T\langle\rho R\rangle Y_n$ product, where P_T is the tracer partial pressure in atmospheres. Note that, if we assume that 50% of the activated Br atoms are collected and that the HBr pressure is 0.1 atm, the operating range of our plastic-coated microballoon targets indicates that we can detect a sufficient number of decays to produce a counting error of less than 30% in a fuel $\langle\rho R\rangle$ measurement. Calculations indicate that this 1-part-per-1000 mixture of HBr will not

perturb the implosion; however, for targets producing more nearly isentropic compression of the fuel, this may not be the case.⁵⁵

Author: S. M. Lane

Major Contributors: C. K. Bennett, E. M. Campbell, C. W. Hatcher, C. J. Larsen, R. L. Morrison, Y. L. Pan, W. M. Ploeger, and R. L. Woerner

Debris Collection and Background Measurements with Bromine-Filled Targets

We are investigating the use of diagnostic gases mixed with the fuel in ICF targets, for the purpose of making direct fuel $\langle\rho R\rangle$ measurements by neutron activation (see the previous article). We have chosen bromine in the form of HBr as the diagnostic gas having the most promise for this work, because of its relatively high nuclear-activation cross section and because its decay characteristics allow a simultaneous fuel and pusher $\langle\rho R\rangle$ measurement. To make these measurements, we first must develop methods of

- Mixing the bromine into the fuel.
- Accurately assaying the amount of bromine in the D-T fuel.
- Collecting the activated debris after the implosion.
- Detecting the bromine decays above a background that is due in part to activation of the collector foil by target-produced neutrons and protons.

Techniques developed to fill microballoons with HBr are discussed in "Diagnostic Gas Fills" in Section 4. We are developing ways of assaying the bromine content of a single target, using neutron activation and x-ray fluorescence techniques, but that work is still in progress and is not discussed here. During the past year, however, we performed a preliminary study of the third and fourth items in the above list, in a series of six shots at the Shiva laser facility. In this article we discuss the results of these experiments, in which we

Debris Collection and Background Measurements with Bromine-Filled Targets

estimated the bromine collection fraction on Ti and V foils and measured the background due to Ti, V, and Mg foil activation.

The experimental arrangement (shown in Fig. 5-62) includes a conically shaped debris collector 0.5 cm from the target. The collector consists of an aluminum housing 4.2 cm in diameter at the open end, 1.0 cm in diameter at the closed end, 11.5 cm in length, and lined with 50- μ m-thick titanium or vanadium foil, or 75- μ m-thick magnesium foil. Opposite the collector and 2.5 cm from

Fig. 5-62. Diagnostic array for preliminary bromine experiments.

the target was a dish-shaped tantalum reflector that served to redirect target debris towards the collector. A zone-plate camera⁵⁶ observed the target through a 0.7-cm-diam hole in the reflector. The camera was used to obtain symmetry information, by imaging x rays in broad-band channels at 2 to 4 keV, 3 to 5.5 keV, 4.5 to 7.5 keV, 8 to 12 keV, and 12 to 22 keV. We also detected x rays emitted from the target, using an imaging crystal spectrograph with an energy range of 2.0 to 2.15 keV placed 5 cm from the target, and a crystal spectrograph with an energy range of 2 to 5 keV placed 105 cm from the target. These spectrographs recorded the $1s^2 2p \ ^2P_{1/2,3/2} \rightarrow 1s^2 3d \ ^2D_{3/2,5/2}$ transitions from lithium-like bromine atoms, which were used to find the electron density by fitting the Stark-broadened line profiles. These x rays could also be used to image (in one dimension) the extent of the target core. Thus both Stark-broadening and spatial imaging could help to corroborate a future neutron-activation fuel (ρR) measurement (see "Fuel Density Measurements Using Bromine L X-ray Line Imaging and Stark Profiles," earlier in this section). Finally, the neutron yield was determined by measuring the number of activations occurring in a copper disk placed 26 cm from the target.⁵⁷

The experimental targets were glass microballoons with inner diameter of 140 μ m, wall thickness of 2 to 4 μ m, a 15- μ m-thick teflon ablator, and containing 30 atm of D-T gas. Targets were illuminated by all 20 beams of the Shiva laser, which delivered a total of 4 kJ in a 200-ps Gaussian pulse. For these preliminary experiments, it was convenient for target fabrication purposes to fill the microballoons with the more reactive Br_2 instead of HBr . We suspect from the Stark-broadening information and the thermal-neutron-activation data that a substantial fraction of the bromine was not in the gas phase, but had reacted with the glass wall instead. To first order, this should not effect the collection-fraction measurements. Two of the bromine-filled microballoons were irradiated for six hours at the Los Alamos Omega West reactor, where ^{82}Br , which has a half-life of 35 hours, was formed in a thermal-neutron flux of $8 \times 10^{13} \text{ n/cm}^2\text{-s}$ from the 50%-abundant isotope ^{81}Br . The long irradiation times were necessary because of the small amount of Br (estimated to be 0.5 ng) present in the target. ^{82}Br

Fig. 5-63. γ -spectrum from 0 to 3 MeV, obtained with a Ge(Li) detector. ▼

decays by β^- emission followed by a number of different possible γ cascades involving 26 separate γ rays, of which the most abundant have energies of 554 keV (70%) and 776 keV (83%). This large number of gamma rays necessitated the use of a high-resolution detector. We used a 40-cm³, 10%-efficient Ge(Li) well detector (the efficiency percentage is a comparison to a 7.5-cm by 7.5-cm NaI detector). This detector gave a count rate of 1/s in the 554-keV peak when the irradiated target was placed against the detector face. A typical spectrum is shown in Fig. 5-63. The large peaks at 1369, 1732, 2243, and 2754 keV are due to ²⁴Na ($t_{1/2}$ = 15 h) produced by thermal-neutron capture (5% of the glass atoms are sodium). The expanded portion shows the ⁸²Br 776-keV γ ray.

For background measurements, we detected radiation emanating from the collector foil using the $\beta\gamma$ coincidence spectrometer described in the previous

article. Figure 5-64 shows how the conical collector foil is installed in the plastic beta-detector by (a) slitting the foil and (b) placing the foil between the two-part plastic fluor which is optically coupled to a photomultiplier tube (c). This assembly is then placed in the well of a 25- by 25-cm NaI(Tl) detector (d) to give an overall ²⁸Al detection efficiency of 38%. This sample-loading process can be completed within 30 to 40 seconds after the implosion. The spectrometer recorded $\beta\gamma$ coincidence events for γ energy channels at 1780 and 1022 keV. To measure the background in the 1022-keV channel, we used targets not containing bromine. The 1780-keV channel was used to detect the decay of ²⁸Al formed in the glass pusher by the ²⁸Si (n,p) ²⁸Al reaction, and the 1022-keV channel is to be used to detect positron-annihilation radiation resulting from the decay of ⁷⁸Br formed in the ⁷⁹Br (n,2n) ⁷⁸Br reaction. In the scheme we are presently pursuing, we hope to

Fig. 5-64. Assembly of the $\beta\gamma$ coincidence spectrometer.

Debris Collection and Background Measurements with Bromine-Filled Targets

simultaneously use the former reaction to measure $\langle \rho R \rangle$ for the pusher, and the latter reaction to measure $\langle \rho R \rangle$ for the fuel.

For the two activated targets, the fraction of collected debris was measured by comparing the ^{82}Br target activity to the ^{82}Br activity found on the collector foil. Both titanium and vanadium foils were used. We measured the bromine collection fraction, η_{Br} , for only a 1/3 section of each foil, because of limitations in the size of the detector well. There was also insufficient time to count the remaining pieces, because of the constraints of the 35-hour half-life of ^{82}Br and the 24-hour counting periods necessary to acquire a statistically significant

number of counts. The greater ^{24}Na activity, however, allowed us to find the sodium collection fraction, η_{Na} , for both entire foils. The results displayed in Fig. 5-65 show that, for the portions counted, η_{Br} for the vanadium foil was about the same as η_{Na} , whereas η_{Br} exceeds η_{Na} for titanium foil.

From these data, we can make a few tentative conclusions. First, the sodium collection fraction for titanium foils is quite different from that for vanadium; yet these are two adjacent elements on the periodic chart, having many similar physical properties. From this we conclude that the relevant mechanisms involved in determining the relative sticking fractions are probably chemical rather than physical in nature. Furthermore, because both foils are good conductors, we conclude that electrostatics do not play a central role in the sticking process. We also see that titanium is a much more efficient collector foil than vanadium. In fact, if the bromine debris is distributed in the same fashion as the sodium debris, it would be possible with vanadium to collect 16% of the total bromine debris compared to 17% of the sodium, while titanium would collect 39% of the bromine

Fig. 5-65. Collection-fraction results from activated bromine-filled targets using vanadium and titanium foils.

	Vanadium	Titanium	Magnesium
Natural and cosmic radiation: (with guard)	8 (2 to 4)	8 (2 to 4)	8 (2 to 4)
Compton-scattered 1780-keV gamma rays: (with guard)	10 (3 to 5)	34 (9 to 17)	7 (2 to 3)
Foil activation:	0	10	31
Total: (with guard)	18 (6 to 9)	52 (21 to 31)	46 (35 to 38)

Table 5-8. β^+ background in a 10-min counting period beginning 40 s after a shot producing 4×10^8 neutrons.

Fig. 5-66. Time histories of the 1022-keV and the 1780-keV coincidence channels for target shots using Ti, V, and Mg collector foils.

compared to 28% of the sodium. In 1979 we performed two collector-fraction measurements using the same type of target and with identical laser conditions as for the above experiments, but with a titanium-lined collector that was cylindrical in shape. For this case we found that $\eta_{\text{Na}} = 55\%$. This result, taken with the results of the current experiments, implies that a bromine collection fraction of 50 to 80% could be attained with a Ti-lined cylindrical collector.

In addition to studying debris collection, we conducted four shots with targets not containing bromine, to investigate the contribution to the β^+ background from foil activation induced by fast neutrons or protons emanating from the target. Figure 5-66 shows the time histories of both the 1780-keV and 1022-keV coincidence channels from shots with Ti, V, and Mg foils, along with the measured neutron yields. (The fourth shot was a repeat of the vanadium shot, which gave results identical to those shown.) In this figure the time at which the foil containing the target debris is loaded into the detector is denoted by $t = 0$. Before $t = 0$, the 1022-keV background is 0.5 to 1.0 cpm, due to cosmic radiation and natural radioactivity. After $t = 0$, two additional components appear, one due to foil activation and the other to Compton-scattered 1780-keV gamma radiation from the decay of collected ^{28}Al atoms. This latter component decays with a characteristic half-life of 2.2 min. With a ^{28}Al source we have found that 5% of the decays result in an event of this type, while 38% of the decays produce a full energy event in the 1780-keV channel.

The time history of the 1022-keV channel (from the shot using titanium foil) shows a 30-min component that we have identified as being due to fast-proton activation of the collector foil by the reaction $^{47}\text{Ti}(n,p)^{47}\text{V}$. The activation product decays by β^+ emission with a half-life of 31.3 min. The threshold for this reaction is 3.8 MeV; we estimate $\sim 10^9$ protons above this energy are required to produce the observed signal. The shot with magnesium foil also exhibits foil activation, which we attribute in this case to the $^{25}\text{Mg}(n,p)^{25}\text{Na}$ reaction. The 1022-keV channel is 300 keV wide and responds to the decay of ^{25}Na ($t_{1/2} = 60$ s) which emits a β^- particle and a 975-keV gamma ray. The number of counts due to foil activation in the first 10 minutes (approximately the counting period for ^{78}Br) can be determined by

subtracting the components due to the other sources. The contribution of each component in this time period is given in Table 5-8. The cosmic, natural, and Compton-scattered 1780-keV components can be reduced by a large NaI(Tl) guard detector (mentioned in the previous article) that completely surrounds the $\beta\gamma$ detectors and operates in anticoincidence with them. As shown in Table 5-8, we estimate this detector will reduce these components by a factor of 2 to 4.

The preliminary experiments reported here indicate that titanium foil is twice as efficient as vanadium for collecting bromine. Using titanium it may be possible with the proper geometry to collect 50% or more of the bromine debris. Unfortunately, titanium is also very efficient at collecting ^{28}Al , which can produce the largest contribution to the background. This component may be reduced, however, by the use of a guard detector or by designing targets with thinner glass walls. Titanium debris collectors also suffer from proton activation. Magnesium will probably find no application as a collector foil, because it is easily activated by neutrons.

For near-term targets that produce few target activations, we need the high collection-efficiency of titanium; the background components must be estimated and subtracted from the signal. For future targets that produce an abundance of counts, a vanadium collector which is not activated by protons or neutrons will provide a less ambiguous result.

Author: S. M. Lane

Major Contributors: C. K. Bennett, E. M. Campbell, N. M. Ceglio, C. W. Hatcher, G. L. Howe, L. N. Koppel, R. W. Lee, D. L. Matthews, and G. F. Stone

Automated Radiation-Chemistry Diagnostic System

During 1980, we built and implemented a microprocessor-based system to control the acquisition and presentation of data from neutron-activation experiments made with

Automated Radiation-Chemistry Diagnostic System

Shiva. We also developed a computer system that will be the core of a small counting laboratory that will be able to simultaneously

- Control experiments.
- Acquire data from several detectors.
- Process, analyze, display, and store data.
- Be available for program development.

Our first radiation-chemistry (rad-chem) experiments involved the activation of ^{28}Si by the interaction of D-T neutrons with the glass pusher.^{58,59} The activation product, ^{28}Al , decays by beta-gamma emission and has a half-life of 2.24 min.

Figure 5-59 shows the beta-gamma coincidence counting system that detects and records these decays. The system consists of a NaI(Tl) detector and an NE-102 plastic beta-fluor. Both of these scintillation

detectors are coupled to photomultiplier tubes that, in turn, are connected to preamplifiers, to spectroscopy amplifiers that perform pulse shaping, and then to single-channel analyzers (SCA).

If the signal outputs from the beta and gamma SCAs are in coincidence with each other, the coincidence unit responds with a logic pulse. These logic pulses are fed into our microprocessor-based data-acquisition chassis (see Fig. 5-67) that was designed to control and record the experimental data. This instrument is capable of handling four independent detector inputs simultaneously, including a recently acquired large NaI(Tl) guard detector that operates in anticoincidence with the other detectors for background reduction. For each experiment, we can assign a run number and a counting

Fig. 5-67. Front-panel view of the microprocessor-based counting and recording unit.

Fig. 5-68. Circuitry of the microprocessor-based data-acquisition chassis.

period from the front-panel key pad. Once the unit is armed, it waits for a zero-time signal that arrives at shot time via a fiber optic trigger; a built-in real-time clock records the shot time. We then manually load the sample of collected debris into the detector assembly and initiate counting from the key pad. When the system is activated, it records the sample loading time (time interval between the shot and the commencement of counting), turns on the high voltage to the beta-fluor photo-multiplier, and starts counting. The accumulated number of counts for each input is both displayed on the front panel and recorded on a built-in thermal printer.

This data-acquisition unit is based on an Intel 8085 8-bit microprocessor. The circuit design (Fig. 5-68) relies extensively on the family of Intel support devices that provide input/output, counter timers, and memory functions. Some special features were designed into this unit to facilitate initial debugging and future diagnosis of circuit problems. The memory contains test diagnostics to check the printer, keyboard, display, RAM, internal counters, and remote/computer interface. The internal firmware is continually checking itself for possible errors by computing a check

character and comparing this to a previously computed character. This instrument has been operational at Shiva for over a year.⁶⁰

The rad-chem experiment is currently being extended to the activation of other materials, notably bromine mixed with the D-T fuel for the purpose of a direct-fuel (ρR) measurement (see the previous article). In this scheme, ^{82}Br , which is formed from natural ^{81}Br by thermal-neutron capture, is used as a collection-fraction tracer. As is the case with many of the activation products involved in these new diagnostic schemes, ^{82}Br decays in a more complex fashion than ^{28}Al . Thus, the low resolution of NaI(Tl) detectors is no longer sufficient, and these detectors must be replaced by a high-resolution Ge(Li) detector.

The analysis of 4 to 8 thousand-channel spectra collected with a high-resolution detector is greatly simplified by computer-assisted techniques. Specifically, we require the ability to do peak searching, background smoothing and subtraction, determination of proper analytic peak shapes, peak fitting, and determination of peak area. These functions are all required to convert peak centroids to energies and peak areas to counts per minute. With this in mind (Fig. 5-69), and with an eye towards the future

Fig. 5-69. Diagram of the neutron-activation analysis facility.

Stimulated Brillouin and Raman Side-Scattering Diagnostics System

when much more sophisticated activation analyses will be performed on fusion targets using these high-resolution detectors, we have built a computer system capable of handling these requirements.

The computer system (Fig. 5-69) is based on a DEC LSI-11/23 microcomputer that runs the real-time, multitasking operation system, RSX-11M. The computer will be capable of controlling our multichannel analyzer (Canberra Series-80) and two of the microprocessor-based acquisition units discussed above. Data will be stored on both cartridge and floppy disk. We will also have direct data-transfer capability to the VAX computers used by Fusion Experiments and by Nova Control and Analysis. This computer system has been acquired and is operating; it is currently being used to develop applications software.

Author: B. A. Jones

Major Contributor: R. L. Hanks

Stimulated Brillouin and Raman Side-Scattering Diagnostics System

We have recently completed plans to investigate stimulated Brillouin and Raman side-scattering in $1\omega_0$, $2\omega_0$ and $3\omega_0$ incident-

light experiments. Most experimental investigations of these parametric instabilities in the past involved analyzing directly back-reflected light, but theoretical studies have shown that the threshold intensities for both the Brillouin and the Raman side-scattering processes are different from back-scattering threshold intensities. In the case of the Raman instability, for example, the threshold for side-scattering is lower than that for backscattering. Furthermore, in a plasma with a large temperature gradient, the threshold for Brillouin scattering is significantly reduced in the strong (laser) field limit. These potentially deleterious instabilities become a source of concern in light of the large extent of underdense coronal plasma surrounding ICF targets, thought necessary to achieve directly laser-driven inertial confinement fusion.

We plan to measure the angular distribution of the intensity of both stimulated Brillouin and stimulated Raman side-scattering, as a function of the incident laser wavelength, the irradiation spot size, and the irradiation intensity. We will obtain both time-integrated and time-resolved spectral data, and we also plan to study the angular distribution of laser-induced harmonic generation in plasmas, as a function of the same basic irradiation parameters just mentioned.

We have designed and built side-scattered-light collection systems for Argus and Shiva. The Shiva design will also adapt to any

Fig. 5-70. Schematic of the side-scattered light-collection system.

similarly configured system, such as the Novette target chamber. The basic system will direct side-scattered light into a spectrometer for spectral analysis. The experimental setup, shown in Fig. 5-70, consists of a telescope collector, a fiber-optic data link, a fiber-optic slit housing input, and a Czerny–Turner 0.5-m spectrograph. The output of the spectrograph is then recorded on film, or relayed to either a CCD array or streak camera if time resolution is desired.

The Argus data-collection system consists of a catadioptric telescope, which is located inside the chamber (in a vacuum) because of a lack of access ports. The telescope, on a kinematic mount attached to the chamber wall, views the target at a prescribed angular position. The output of the telescope is focused into a single-fiber fiber-optic cable ~ 1 mm in diameter (the fiber is made of special broad-band-transmitting glass). The fiber-optic cable is fed out of the chamber through a specially designed fiber-optic vacuum feed-through (Fig. 5-71). There are two types of feed-throughs, one for the near-infrared and visible spectrum, and one for UV; five feed-throughs are mounted on one chamber flange, to allow for five different data channels. The fiber-optic cables terminate at the input slit of the spectrograph, through a fiber-optic slit housing.

Scattered-light collection is simpler at Shiva, where the telescope is mounted on the outside of the target chamber and views the target through a viewing port. The output of the telescope is focused into a fiber optic which is directly coupled to the spectrograph by means of a slit housing. Alignment of the collector telescope to the target is accomplished by connecting a fiber-optic illuminator to the back of the telescope; the target is then illuminated by a beam of light

emanating from the telescope. This procedure guarantees that optical photons emitted by the target will lie within the acceptance cone of our collectors. Another important component of the system is a 0.5-m Czerny–Turner spectrograph, including five precision gratings blazed to cover most of the wavelength range expected in the experiments.

To do a systematic angular distribution study for Raman or Brillouin side-scattering will require simultaneous light-collection from at least three angular positions in a single shot. To ensure speedy and accurate data analysis while minimizing the cost, the spectrograph output will have to be fed into an automatic data-storage/analysis system which has a multisignal capability and can be interfaced with our computing facility. We have found the optical multichannel analyzer (OMA) to be most attractive for this purpose.

Authors: F. Ze and M. W. Kobierecki

Major Contributors: D. W. Phillion and A. Cappabianca

4 ω Optical Probing

When fusion targets are irradiated by long laser pulses, there is ample time for a large plasma atmosphere to form around the target. The interaction between the laser light and this underdense plasma can have important consequences; if Raman scattering occurs, for example, suprathermal electrons can be generated. To increase our understanding of these interactions, it is desirable to have a direct experimental measurement of the density profile.

Fig. 5-71. Fiber-optic vacuum feedthrough.

4 ω Optical Probing

We have used a simple analytic model to examine the potential of UV interferometry for density measurements in large-volume plasmas. We begin our model for a disk target experiment by assuming that the plasma is purely one-dimensional. In Fig. 5-72, the plasma is represented as extending from $x = 0$ to $x = L$. We further simplify our analysis by assuming a density profile given by $n = n_0 (1 - z/\ell)$. This profile will give results similar to an exponential profile ($n = n_0 e^{-z/\ell}$), provided $z \ll \ell$; it also has the advantage of simplifying analytical calculations.

We wish to trace a probe ray through the plasma, calculating the amount of refraction and the optical path length. We also wish to calculate the apparent origin of the ray when viewed through a hypothetical imaging lens, and the interferogram this image would form in an ideal interferometer. Considering a double-pulse holographic interferometer, the interference pattern will be formed by the interaction of a first ray, which goes through the plasma, and a second ray, which goes through the same image point but is unrefracted in the vacuum (i.e., no plasma is present). This is illustrated in Fig. 5-72, in

Fig. 5-72. Experimental geometry for 4 ω optical probing; the z direction is greatly exaggerated for clarity.

Object plane x_1 (μm)	Apparent ray height z_1 (μm)	Fringe number F	Actual density $n(z_1)/n_c$	Calculated density $\tilde{n}(z_1)/n_c$
0	-19.8	17.8	0.35	0.28
150	-7.94	15.9	0.29	0.25
250	0	14.7	0.25	0.23
350	7.94	13.4	0.21	0.21
500	19.8	11.5	0.15	0.18

Table 5-9. Ray trace for
 $L = 500 \mu\text{m}$, $\ell = 50 \mu\text{m}$,
 $n_0 = n_c/4$, and $z_0 = 0$.

which the solid line is the probe light incident in the plasma; the dashed line shows that, for a lens with an object plane at $x = x_1$, the ray appears to originate at (x_1, z_1) ; and the dotted line is a ray through (x_1, z_1) when no plasma is present. Note that the z direction is greatly exaggerated, for clarity.

We must solve the ray equation⁶¹

$$\frac{\partial}{\partial s} \left(\mu \frac{\partial \mathbf{r}}{\partial s} \right) = \nabla \mu, \quad (6)$$

where μ , the index of refraction, is given by

$$\mu = \left(1 - \frac{\omega_p^2}{\omega^2} \right)^{1/2} = \left[1 - \frac{n_0}{16n_c} \left(1 - \frac{z}{\ell} \right) \right]^{1/2}. \quad (7)$$

We have assumed that the probe is the fourth harmonic of the laser frequency; for a 1- μm laser, this gives $n_c = 10^{21} \text{ cm}^{-3}$. The solution to the ray equation is then given by

$$x = 2 \left[(1 + \alpha z_0) \left(\frac{z - z_0}{\alpha} \right) \right]^{1/2} \quad (8)$$

where

$$\alpha = \frac{n_0/\ell}{16n_c - n_0} \quad (9)$$

We can solve for z_2 (see Fig. 5-72) by setting $x = L$. Additionally, the refraction angle θ is given by

$$\theta = \arctan \left[\left(\frac{\alpha L}{2} \right) \left(\frac{1}{1 + \alpha z_0} \right) \right] \quad (10)$$

and the optical path length (OPL) between $(0, z_0)$ and (L, z_2) is

$$\text{OPL} = \int_{(0, z_0)}^{(L, z_2)} \mu ds = \left(\frac{2}{\alpha} + \frac{2}{3} z_2 + \frac{4}{3} z_0 \right) \times \left[\left(\frac{n_0}{16n_c} \right) \left(\frac{1}{\ell} \right) (z_2 - z_0) \right]^{1/2}. \quad (11)$$

Using the fact that for an ideal lens in a vacuum, the optical path length from (x_1, z_1) to the image point is the same whether one uses the dashed or dotted paths in Fig. 5-72, we can calculate the optical path difference (vacuum minus plasma) in terms of the

number of probe wavelengths, or the interference fringe number F :

$$F = \frac{1}{\lambda_p} \left[x_1 + (L - x_1) \sec \theta - \text{OPL} \right], \quad (12)$$

where λ_p is the probe wavelength. Finally, given F , we can approximate the result of a classical Abel inversion⁶² of the data, which assumes no refraction, by using

$$\tilde{n}(z_1) = 16n_c \left[1 - \left(1 - \frac{F\lambda_p}{L} \right)^2 \right]. \quad (13)$$

We can now postulate various plasma parameters, and numerically explore the results of probing to different densities and imaging various regions of the plasma. Consider, for example, a uniformly illuminated disk with a diameter L of $500 \mu\text{m}$, and suppose $\ell = 50 \mu\text{m}$, $n_0 = n_c/4$, and $z_0 = 0$. Table 5-9 shows the results for these parameters of varying the object plane of the imaging lens, x_1 . We see that adequate results are obtained when the lens is focused near the middle of the plasma. The perfect agreement between actual and calculated density at $x_1 = 2L/3$ is a characteristic of our (assumed) linear density profile; other profiles (exponential, for example) give best agreement for other focal positions. Without an a priori knowledge of the profile, center focusing is the best general position.

Continuing the example, we can investigate other important properties. For example, the angle of refraction θ is 4.5° . This means that the imaging lens must be $f/6.3$ or faster to collect this light. Table 5-10 shows the results of tracing two adjacent rays for center focusing ($x_1 = 250 \mu\text{m}$). These two rays produce interference fringes which are exactly 2π rad out of phase and $3.2 \mu\text{m}$ apart in space. Thus, in this example, the optical system must be capable of $3\text{-}\mu\text{m}$ resolution.

We can also consider a further complication: time integration. The interferometer will record fringes for a time τ equal to the pulse width of the probe light. If the location of a given density is moving with a phase velocity V , then the fringes will be smeared over a distance $\Delta z = V\tau$. If Δz is greater than, or equal to, the distance between adjacent fringes, then the interferogram will be unreadable. Inverting the procedure, if we estimate V , we can place a requirement on τ .

LASNEX typically estimates $V \sim 2 \times 10^7 \text{ cm/s}$ for $n_0 \sim n_c/4$. Using our previous example, we find $\tau \leq \Delta z/V = (3.2 \mu\text{m})/(2 \times 10^7 \text{ cm/s}) = 16 \text{ ps}$.

After examining a number of different examples, we have reached the following conclusions regarding interferometric probing of large disk targets ($\sim 500 \mu\text{m}$ in diameter) with UV ($\lambda \sim 0.26 \mu\text{m}$) light:

- Densities measured would range from $1 \times 10^{19} \text{ cm}^{-3}$ to $0.25 \times 10^{21} \text{ cm}^{-3}$, depending on the scale lengths (ℓ) and velocities (V).
- A very short ($\tau \leq 20 \text{ ps}$) probe pulse is necessary. The regenerative amplifier being developed at LLNL is appropriate as a laser source (see "Long Pulse Oscillator Development" in Section 2).
- The speed of the collecting lens should be about $f/6$. A slower lens will not collect the light, due to refraction. A faster lens does not improve the system either, since light undergoing strong refraction comes from high densities, where velocity-smearing will obliterate the closely spaced fringes; also, without an a priori knowledge of the plasma density profile, light undergoing strong refraction will be badly mis-imaged.
- With the light collection restricted to an $f/6$ aperture, for imaging near the center of the plasma, a classical Abel inversion will reproduce the actual density profile with good accuracy ($\pm 10\%$). For uniform irradiation of a disk, it is not unreasonable to assume that the plasma is rotationally symmetric about the disk axis. Under these conditions, we need no longer assume that the plasma is one-dimensional. The Abel inversion will correctly generate the two-dimensional, axially symmetric plasma-density distribution.

We are currently planning UV probe capability for the Novette laser. This system will use $f/6$ optics. The laser probe pulse will be generated using a synchronous AMQ oscillator to produce a short (100 ps) pulse which is further shortened by a regenerative amplifier, to a pulse width of 20 ps. The pulse will be frequency-quadrupled and then Raman-shifted, to avoid interference from

Table 5-10. Fringe separation for $L = 500 \mu\text{m}$, $\ell = 50 \mu\text{m}$, object plane $x_1 = 250 \mu\text{m}$, and $n/n_c = 0.23$.

Starting position z_0 (μm)	Apparent height z_1 (μm)	Fringe number F	Fringe spacing z_1 (μm)
0	0	14.7	3.2
3.2	3.2	13.7	3.2

harmonics generated by the target-irradiation pulse. We anticipate measuring density profiles up to $\sim 2 \times 10^{20} \text{ cm}^{-3}$, for large ($\sim 500 \mu\text{m}$) disk targets.

Author: R. E. Turner

Major Contributors: D. T. Attwood and J. M. Auerbach

Analysis of Bremsstrahlung Emission as an Electron-Density Diagnostic

Optical bremsstrahlung emission from laser-heated plasmas enables us to measure the line integral $\int (n_e^2) dx$, where n_e is the electron density, provided other optical radiation processes are not important. The bremsstrahlung emission rate depends only weakly upon the electron temperature for photon energies that are much less than the mean electron energy. We are analyzing the feasibility of experiments in which we would image the optical radiation from a low-density, high-temperature coronal plasma onto the slit of a streak camera. The time-dependence of the line integral $\int (n_e^2) dx$ will thus be measured over one spatial dimension. If this spatial dimension is across an axially symmetric plasma, Abel inversion may be performed in combination with the optical framing camera being developed at LLNL,⁶³ we could use this technique to obtain snapshots of the plasma, giving us pictures at several discrete times of the line integrals $\int (n_e^2) dx$ perpendicular to the image plane.

For bremsstrahlung analysis to work as an electron-density diagnostic, we must make an absolute measurement of the optical intensity, and also be able to accurately calculate what the bremsstrahlung emission should be for known plasma conditions. Fortunately, the physics in this area are fairly well-known, and the calculation of the bremsstrahlung cross section is essentially classical. The only uncertainty is how to find the minimum and maximum values for the momentum transfer, Q , to the nucleus. The

ratio of the two momenta appears as the argument of the logarithm factor in the cross-section formula. Sommerfeld⁶⁴ has solved Schrödinger's equation in first-order perturbation theory, to obtain the bremsstrahlung cross section for an electron scattered from an unscreened nucleus of any atomic number Z . His solution uses the Coulomb wave functions, but neglects spin, retardation, and all relativistic effects.

It is also possible to estimate $Q_{\min}$ and $Q_{\max}$ by judiciously combining classical arguments with kinematic arguments based on the quantum nature of light.⁶⁵ The Sommerfeld solution is not simple, so we have obtained an asymptotic expression for the cross section when the photon energy is much less than the electron energy. We compare this asymptotic expression to both the Bethe-Heitler solution and the classical solution in the respective limits in which these two solutions are valid. The problem is even more complicated when we have a partially stripped ion in a plasma. For our work, we assume the ion scatters electrons like an unscreened nucleus, with an atomic number equal to the ionization state of the ion.

The plasma has two effects on the bremsstrahlung cross section:

- The density of radiation states, $n(\omega)d\omega$, into which the optical photon may be emitted, is altered. This results in a multiplicative correction factor to the bremsstrahlung cross section.
- Distant collisions may be screened by the cloud of electrons surrounding both the incident electron and the ion.

We will show that for our typical experimental conditions, the collision of a thermal electron with an ion at an impact parameter equal to the electron Debye length, λ_{De} , takes place too slowly for optical emission. For significant optical radiation to occur, the collision must be fast on the time scale of an optical period. Even if this is not the case, it is possible to estimate fairly accurately the effect of plasma-electron screening upon the cross section.

We first estimate the amount of line and free-bound optical radiation, compared to the optical bremsstrahlung radiation. These arguments will show that for high- Z plasmas that are not too tenuous, bremsstrahlung radiation should predominate. Afterwards we will discuss details of the bremsstrahlung

cross-section calculation, most notably the logarithm factor in the cross-section formula, and the origin of the plasma correction factor. We also show that the bremsstrahlung emission rate may be obtained from the inverse bremsstrahlung absorption coefficient.

The bremsstrahlung emission per unit volume is given by⁶⁶

$$j_{f-f}(\omega) = \frac{16}{3} \sqrt{\frac{2}{\pi}} \frac{\bar{Z} n_e^2 r_0^3 m_e c^2}{\beta_{te}} \times \ln \left(\frac{Q_{\max}}{Q_{\min}} \right) \sqrt{1 - \frac{\omega_{pe}^2}{\omega^2}}, \quad (14)$$

where $j_{(f-f)}(\omega)$ is in ergs/(cm³-s-Hz), $\bar{Z}$ is the ionization state, n_e is the electron density, r_0 is the classical electron radius (2.818 $\times 10^{-13}$ cm), m_e is the electron mass (0.911 $\times 10^{-27}$ g), c is the speed of light, and $\beta_{te} = kT_e/m_e c^2$ is the thermal-electron velocity expressed as a fraction of c ; the last factor in the equation is the plasma correction factor, which is discussed later. This equation demonstrates the potential of this measurement technique, since the bremsstrahlung emission per unit volume depends strongly on n_e and rather weakly on T_e .

The line radiation, which might mask or confuse the bremsstrahlung signal we wish to measure, can be estimated by assuming each ion radiates with oscillator strength f_{osc} in the optical frequency band being observed. The spontaneous emission per unit volume is

$$P_{line} = \sum_{k,l} N_i(E_k) f_{\sigma_{kl}}(\omega) \hbar \omega n(\omega) d\omega, \quad (15)$$

where $\sigma_{kl}(\omega)$ is the polarization- and direction-averaged cross section for the transition $k \rightarrow l$, $n(\omega)d\omega$ is the number of photon states per unit volume in the angular frequency interval $d\omega$, $N_i(E_k)$ is the number of ions in the state E_k , and the sum is taken over states k, l such that $E_k > E_l$ and $\omega_{kl} = (E_k - E_l)/\hbar$ is in the optical frequency band being observed. The number density of states $n(\omega)$ differs between a plasma and in a vacuum. In k space the integration over states has the form

$$\sum_{\lambda} \int \frac{V d^3 k}{(2\pi)^3}, \quad (16)$$

where V is the volume and $\sum_{\lambda}$ represents the summation over polarization states or modes.

For an isotropic plasma, the integration over wave number can be changed to one over the angular frequency, ω , such that

$$\sum_{\lambda} \int \frac{V d^3 k}{(2\pi)^3} \rightarrow \int \frac{V \omega^2 d\omega}{\pi^2 v_p^2 v_g}, \quad (17)$$

where v_p is the phase velocity and v_g is the group velocity. The integrand in Eq. (17) is the number of radiation states per unit of angular frequency, ω . In an isotropic plasma, the velocities v_p and v_g are inversely related by $v_p v_g = c^2$. The phase velocity ω/k is $c/\sqrt{1 - \omega_{pe}^2/\omega^2}$. The density of states $n(\omega)$ per unit volume and per unit angular frequency is then

$$n(\omega) = \frac{\omega^2}{\pi^2 c^3} \sqrt{1 - \frac{\omega_{pe}^2}{\omega^2}}. \quad (18)$$

By definition, the oscillator strength f_{kl} for the transition $k \rightarrow l$ is given by⁶⁷

$$\int \sigma_{kl}(\omega) d\omega = 2\pi^2 r_0 c f_{kl}, \quad (19)$$

where r_0 is again the classical electron radius. Define the effective oscillator strength, f_{osc} , in the frequency band of interest as

$$\sum_{k,l} N_i(E_k) \int \sigma_{kl}(\omega) d\omega = N_i 2\pi^2 r_0 c f_{osc}, \quad (20)$$

where again the summation i over states k and l , such that $\omega_{kl} = (\omega_k - \omega_l)$, is positive and in the optical frequency band being observed. The oscillator strength f_{osc} is an effective oscillator strength, which we expect to be 2 or 3 (at most) for highly ionized gold. The line emission is then roughly

$$P_{line} = 2\hbar \omega N_i \frac{r_0}{c} \omega^2 f_{osc} \sqrt{1 - \frac{\omega_{pe}^2}{\omega^2}}, \quad (21)$$

where the angular frequency, ω , is in the optical frequency band being observed.

Taking the ratio of the line emission to the bremsstrahlung emission, we find

$$\frac{P_{line}}{P_{brem}} = \frac{3\pi}{2} \sqrt{\frac{\pi}{2}} \left(\frac{n_e}{n_c} \right) \times \left[\frac{\beta_{te}}{\alpha \bar{Z}^2 \ln \left(\frac{Q_{\max}}{Q_{\min}} \right)} \right] \left(\frac{f_{osc} \omega}{\Delta \omega} \right), \quad (22)$$

where $\Delta\omega$ is the bandwidth of the light being observed, n_c is the critical electron density at the optical frequency ω , $\bar{Z}$ is the ionization state, β_{te} is the thermal-electron velocity expressed as a fraction of the speed of light, $\alpha = 1/137$ is the fine-structure constant, and f_{osc} is the effective oscillator strength with which each ion is radiating into lines in the frequency band $\Delta\omega$. We expect $\omega f_{osc}/\Delta\omega$ to be less than 2 or 3 on the average. If $\bar{Z}$ is large and n_e/n_c is not too small, the line emission should be only a small fraction of the bremsstrahlung emission. Taking $T_e = 1$ keV, $\bar{Z} = 50$, and $\lambda = 0.4 \mu\text{m}$, we find

$$\frac{P_{line}}{P_{brem}} = \frac{0.0035}{n_e/n_c} \left(\frac{f_{osc}\omega}{\Delta\omega} \right) \quad (23)$$

Provided n_e/n_c is not too small, bremsstrahlung should be the predominant source of optical radiation. If $n_e = n_c/10$ for 1.06- μm laser light, then for observation in the blue region of the spectrum $n_e/n_c = 0.014$, and the line and bremsstrahlung radiation could be comparable.

The plasma must also be optically thin, so that we can be sure we are measuring the integrated optical emission. On the other hand, if the plasma depth is too small, the emission will not be detectable. There is no problem in detecting a line-integrated emissivity of about $200 \text{ W}/(\text{cm}^2\text{-}\mu\text{m})$. For $T_e = 1$ keV, $\bar{Z} = 50$, and $n_e = 2.46 \times 10^{20} \text{ cm}^{-3}$, the bremsstrahlung emission rate is $\sim 10^{10} \text{ W}/(\text{cm}^3\text{-}\mu\text{m})$ in the blue spectral region. A blackbody will emit at the rate $3.02 \times 10^7 T(\text{keV})/[\lambda(\mu\text{m})]^4 \text{ W}/(\text{cm}^2\text{-}\mu\text{m})$, so sensitivity is not a problem. If the electron density is high or the plasma is long ($\lesssim 1$ mm for these conditions), we would want to look at a shorter wavelength. Ultraviolet imaging capability should therefore be planned for Novette.

The remainder of this article discusses the calculation of the bremsstrahlung cross section. The correct calculation of the logarithm factor in the cross-section formula is particularly important, since the argument of the logarithm is rather small for the plasma conditions we are interested in. Uncertainty factors of 2 or 3 in this argument then make a large difference in the calculated bremsstrahlung emission rate. We first summarize the classical and kinematic constraints determining Q_{min} and Q_{max} , before discussing the exact quantum-

mechanical solution for the cross section and, in particular, before discussing the asymptotic form of this solution we have derived.

The maximum momentum transfer is determined by the simple kinematic constraint that even in a head-on collision, no more than twice the electron momentum goes to the nucleus. If a photon is emitted, the incident electron will recoil with a momentum p that is less than its initial momentum, p_0 , since it loses some energy to the photon. (If the incident electron is nonrelativistic, the photon momentum is negligible.) In the Born approximation, for which the incident-electron wave function is assumed to be a plane wave, the minimum momentum transfer is also determined kinematically; $Q_{min} = p_0 - p$, and the logarithm factor is $\log [(p_0 + p)/(p_0 - p)]$, which is the Bethe-Heitler result.⁶⁸ The Born approximation is only valid, however, when the electron energy greatly exceeds $Z^2 \text{ Ry}$ (1 Ry = 13.61 eV); this is certainly not true in the high- Z plasmas we are interested in diagnosing and for which this technique offers so much promise.

When the Born approximation breaks down, i.e., when the parameter $\eta = Ze^2/hv > 1$, Q_{min} may then be determined classically by finding the maximum impact parameter, b_{max} , for which optical radiation can occur. This will be either λ_{De} or v/ω , whichever is smaller. The latter limit comes about because no significant radiation at a given frequency can occur unless the collision time is shorter than the period. The minimum momentum transfer is

$$Q_{min} \approx \frac{\lambda' Ze^2}{b_{max} v} \quad (24)$$

where λ' is a factor of order unity, which represents our ignorance of the exact value to use for Q_{min} .

For $b_{max} = \lambda_{De}$, we find

$$\frac{Q_{max}}{Q_{min}} \approx \frac{3N_{De}}{2} \quad (25)$$

where N_{De} is the number of electrons in a Debye sphere whose volume is

$$V_D = \frac{4}{3} \pi \lambda_{De}^3 \quad (26)$$

where

$$\lambda_{De} = \sqrt{\frac{kT_e}{4\pi n_e e^2}} \quad (27)$$

When b_{max} is determined by λ_{De} , there is no frequency-dependence at all to the bremsstrahlung emission rate, except for the plasma correction factor $\sqrt{1 - \omega_{pe}^2/\omega^2}$.

For the experiments we foresee, the maximum-impact parameter will be determined by the quantity v/ω rather than by the electron Debye length. For v/ω to be less than λ_{De} , the wavelength λ_0 must satisfy the inequality

$$\lambda_0 \lesssim \sqrt{\frac{\pi}{n_e r_0}} \quad (28)$$

Taking $n_e = 2.46 \times 10^{20}$ electrons/cm³ (which is $n_c/4$ for 1.06- μ m light), we find $v/\omega < \lambda_{De}$ when $\lambda_0 < 2\mu$ m. Which limit we use depends only on the electron density, and not at all on the electron temperature. For this limit,

$$\frac{Q_{max}}{Q_{min}} = \frac{\lambda m c^2}{\alpha Z \hbar \omega} \left(\frac{kT_e}{m_e c^2} \right)^{3/2}, \quad (29)$$

where α is the fine-structure constant and $\hbar$ is Planck's constant. In this limit there is no dependence on n_e in the logarithm.

We now discuss the Sommerfeld solution for the differential bremsstrahlung cross section, and derive the asymptotic expansion for small photon energies. We show that this expansion becomes the Bethe-Heitler solution when $\eta = Ze^2/\hbar v \ll 1$, and that it becomes the classical solution when $\eta \gg 1$. In particular, we show that if we rewrite Eq. (29) for an electron of velocity v as

$$\frac{Q_{max}}{Q_{min}} = \frac{\lambda m v^2}{\eta \hbar \omega}, \quad (30)$$

we find the parameter $\lambda = 1.123$ when $\eta \gg 1$. The Sommerfeld cross section is for an electron of specific velocity. To obtain the bremsstrahlung emission rate, we must integrate $n_e(v) N_i \hbar \omega \sigma_v(\hbar \omega)$ over the electron velocity v . The electron distribution function is $n_e(v)$, and the bremsstrahlung cross section for emitting a photon of energy $\hbar \omega$ in an electron-ion collision at relative velocity v is $\sigma_v(\hbar \omega)$.

The exact Sommerfeld solution for the differential bremsstrahlung cross section can be integrated to obtain an expression for the total cross section in terms of hypergeometric functions with complex parameters but with a negative real argument x , which becomes extremely large in magnitude when the photon energy is small compared to the electron energy. Unfortunately, the power series representing the hypergeometric function near the origin diverges when the magnitude of its argument exceeds a value of 1. By analytic continuation, however, we can express this hypergeometric function in terms of two hypergeometric series about infinity, i.e., expanded in powers of x^{-1} .

When multiplied by a power of x which depends upon the complex parameters, each of the two hypergeometric series in x^{-1} satisfies the same differential equation as the original hypergeometric function. Since there are only two independent solutions to a second-order linear differential equation, such as the one the hypergeometric function satisfies, the analytic continuation of the power series in x can be expressed as a sum of the two power series in x^{-1} .

Before going further, it is necessary to quote the Sommerfeld result⁶⁴ for the bremsstrahlung cross section:

$$\frac{v \sigma(v)}{\sigma_0} = \frac{\pi^2 x_0}{[\exp(2\pi\eta_0) - 1][1 - \exp(-2\pi\eta)]} \times \frac{d}{dx} \left| F(i\eta_0, i\eta; 1; x) \right|^2 \Big|_{x=x_0}, \quad (31)$$

where

$$\sigma_0 = \frac{16}{3} Z^2 \alpha^3 \left(\frac{\hbar}{p_0} \right)^2 \quad (32)$$

and $x_0 = -4\eta\eta_0/(\eta - \eta_0)^2$. The velocities v_0 and v are the initial and final electron velocities, respectively. We use identity 15.3.7 in Abramowitz and Stegun⁶⁹ for the analytic continuation of the hypergeometric function:

$$\begin{aligned} F(a, b; c; z) &= \frac{\Gamma(c) \Gamma(b-a)}{\Gamma(b) \Gamma(c-a)} \\ &\times (-z)^a F(a, 1-c+a; 1-b+a; \frac{1}{z}) \\ &+ \frac{\Gamma(c) \Gamma(a-b)}{\Gamma(a) \Gamma(c-b)} \\ &\times (-z)^b F(b, 1-c+b; 1-a+b; \frac{1}{z}), \end{aligned} \quad (33)$$

for $\arg(-z) < \pi$. Applying this identity, we find

$$\begin{aligned} & \left| \frac{d}{dx} F(i\eta_0, i\eta; 1; x) \right|^2 \\ &= \left| \frac{\Gamma(i\eta - i\eta_0)}{\eta_0 \Gamma(i\eta_0) \Gamma(i\eta)} \right|^2 \\ &\times \left| \frac{d}{dx} F(i\eta_0, i\eta_0, 1 + i\eta_0 - i\eta, \frac{1}{x}) \right| \\ &\times \left\{ 1 - e^{[f(x)\delta\eta + ig(x)\delta\eta]} e^{-\delta\eta \ln(-x)} \right\}^2, \end{aligned} \quad (34)$$

where $\delta\eta = \eta - \eta_0$, and the real functions $f(x)$ and $g(x)$ are defined by:

$$\begin{aligned} & e^{[f(x)\delta\eta + ig(x)\delta\eta]} \\ &= \frac{\Gamma(1 - i\delta\eta) \Gamma(1 - i\eta_0) \Gamma(1 + i\eta) i\eta_0}{\Gamma(1 + i\delta\eta) \Gamma(1 + i\eta_0) \Gamma(1 - i\eta) i\eta} \\ &\times \frac{\Gamma(i\eta, i\eta; 1 + i\eta - i\eta_0; x^{-1})}{\Gamma(i\eta_0, i\eta_0; 1 + i\eta_0 - i\eta; x^{-1})}. \end{aligned} \quad (35)$$

So far, no approximation has been made. When $\delta\eta$ is small, the two terms in the analytic continuation nearly cancel. The lowest-order contributions to the derivative of the absolute value of F^2 come from the changing relative phase of the two terms. The hypergeometric power series is

$$\begin{aligned} F(a, b; c; z) &= 1 + \frac{ab}{1!c} z \\ &+ \frac{a(a+1)b(b+1)}{2!c(c+1)} z^2 + \dots \end{aligned} \quad (36)$$

The argument $z = x^{-1}$ is so small that we can actually assign a value of 1 to the hypergeometric functions of x^{-1} , when $\delta\eta \ll 1$. We have found that the higher-order terms give fractional errors of order $\mathcal{O}(\delta\eta^2)$ in the value for $\nu\sigma(\nu)/\sigma_0$. To the $\mathcal{O}$ th order,

$$f(x) + ig(x) = \alpha + i\beta \quad (37)$$

where the constants α and β are determined by

$$e^{(\alpha + i\beta)} = \frac{\Gamma(1 - i\delta\eta) \Gamma(1 - i\eta_0) \Gamma(1 + i\eta_0 + i\delta\eta) i\eta_0}{\Gamma(1 + i\delta\eta) \Gamma(1 + i\eta_0) \Gamma(1 - i\eta_0 - i\delta\eta) i\eta} \quad (38)$$

If we define $\theta(x) = -\delta\eta \ln(-x) + \beta\delta\eta$, we find that

$$\begin{aligned} & \left| \frac{d}{dx} F(i\eta_0, i\eta; 1; x) \right|^2 \\ &\equiv \left| \frac{\Gamma(i\eta - i\eta_0)}{\eta_0 \Gamma(i\eta_0) \Gamma(i\eta)} \right|^2 \\ &\times \left(\left| \frac{d}{dx} \left[1 - e^{\alpha\delta\eta} e^{i\theta(x)} \right] \right|^2 \right) \end{aligned} \quad (39)$$

and that

$$\left| \frac{d}{dx} \left[1 - e^{\alpha\delta\eta} e^{i\theta(x)} \right] \right|^2 \equiv 2\theta(x) \frac{d\theta(x)}{dx} e^{\alpha\delta\eta} \quad (40)$$

We assume both $\alpha\delta\eta$ and $\theta(x)$ are much less than one. To evaluate the absolute value of a gamma function of a pure imaginary number, we appeal to the relation

$$\left| \Gamma(ix) \right| = \sqrt{\frac{\pi}{x \sinh \pi x}}, \quad x \text{ real} \quad (41)$$

We finally find that

$$\begin{aligned} \frac{\nu\sigma(\nu)}{\sigma_0} &\approx (1 + \pi\delta\eta) \left[\ln \left(\frac{2\eta_0}{\delta\eta} \right) - \frac{\beta}{2} \right] \\ &+ \mathcal{O}(\delta\eta^2), \end{aligned} \quad (42)$$

where

$$\begin{aligned} \beta &= 2 \frac{d}{d\eta} \arg \\ &\times \left[\Gamma(1 + i\eta_0 - i\eta) \Gamma(1 - i\eta_0) \Gamma(1 + i\eta) \right] \Big|_{\eta=\eta_0}. \end{aligned} \quad (43)$$

The argument or phase of a product of gamma functions is taken in Eq. (43). Since the argument of a complex number equals the imaginary part of its logarithm, we can determine the behavior of β by using the rational fraction expansion to $\log \Gamma(z)$ to obtain⁷⁰

$$\frac{\beta}{2} = \sum_{k=0}^{\infty} \frac{\eta_0^2}{(\eta_0^2 + k^2)k} \quad (44)$$

Notice that β goes to zero when η_0 goes to zero. Thus when η_0 and $\delta\eta$ are very small, we have

$$\frac{\nu\sigma(\nu)}{\sigma_0} \xrightarrow[\eta \rightarrow 0]{\delta\eta \rightarrow 0} \ln \left(\frac{2\eta_0}{\delta\eta} \right) \quad (45)$$

The exact Bethe-Heitler result is

$$\left. \frac{\nu\sigma(\nu)}{\sigma_0} \right|_{\text{Bethe-Heitler}} = \ln \left(\frac{\eta + \eta_0}{\eta - \eta_0} \right), \quad (46)$$

and Eq. (42) limits correctly. Now we check the classical limit of large η_0 . Notice that when η_0 is large, the series expansion for $\beta/2$ approximately equals the sum

$$\sum_{k=1}^{\eta_0} 1/k,$$

and that this sum is approximately equal to $\ln \eta_0 + \gamma$, where $\gamma = 0.577\dots$ is the Euler-Mascheroni constant. It has been rigorously proven that this is indeed the correct limit for $\beta/2$ for the case of large η_0 . Thus we find

$$\frac{\nu\sigma(\nu)}{\sigma_0} \xrightarrow[\delta\eta \ll 1]{\eta_0 \rightarrow \infty} \ln \left(\frac{2}{\eta - \eta_0} \right). \quad (47)$$

Now

$$\eta - \eta_0 \equiv \frac{-Ze^2}{\hbar v^2} \delta v, \quad (48)$$

when

$$\frac{\delta v}{v} \ll 1, \quad (49)$$

and $m v \delta v = \hbar \omega$ by energy conservation. Thus

$$\frac{\nu\sigma(\nu)}{\sigma_0} \xrightarrow[\delta\eta \rightarrow 1]{\eta_0 \rightarrow \infty} \ln \left(\frac{1.123 \text{ mv}^2}{\eta \hbar \omega} \right), \quad (50)$$

and we have proved our earlier assertion about the value of the factor λ , which represented our uncertainty in $Q_{\text{max}}/Q_{\text{min}}$.

Finally, we derive the bremsstrahlung emission rate, $j_{f-f}(\omega)$, from the inverse-bremsstrahlung intensity absorption coefficient, $\kappa(\omega)$, by requiring detailed balance between the two processes when the radiation field and the electrons are in thermodynamic equilibrium at some temperature T . In equilibrium, the absorbed power density, $v_g u_p(\omega)$, must equal the emitted power density $j_{f-f}(\omega)$. The energy

density, $u_p(\omega)$, of the thermal radiation field in a plasma is given by

$$u_p(\omega) = \left(\frac{\hbar \omega^3}{\pi^2 c^3} \frac{1}{e^{(\hbar \omega/kT)} - 1} \right) \left(\frac{c^3}{v_p^2 v_g} \right). \quad (51)$$

The first term in parentheses is the energy density, $u_v(\omega)$, for a thermal radiation field of temperature T in a vacuum. The second term is the ratio of the density of states per unit frequency in a plasma to that in a vacuum. Since

$$v_p = \frac{c}{\sqrt{1 - \frac{\omega_{pe}^2}{\omega^2}}} \quad (52)$$

and

$$v_g = c \sqrt{1 - \frac{\omega_{pe}^2}{\omega^2} g}, \quad (53)$$

we have

$$u_p(\omega) = u_v(\omega) \sqrt{1 - \frac{\omega_{pe}^2}{\omega^2}}. \quad (54)$$

There is another simple argument from which we can obtain the above relation. Assume the plasma is surrounded by a vacuum; assume also that the interior of the plasma is at a uniform density, but at its edges the density smoothly decreases to zero over a distance of many optical wavelengths, so there are no Fresnel reflection losses. If the radiation field inside the plasma is to be in thermodynamic equilibrium with the radiation field outside, then the power flow in any radiation pencil going into the plasma must equal the outward power flow into that same pencil. The radiation pencil is characterized by a differential solid angle $d\Omega$, a differential cross-sectional area dA , and a direction, θ , which specifies the angle the pencil makes with the normal to the plasma boundary. Primed quantities will apply to the plasma. Relations between $d\Omega$ and $d\Omega'$ and between dA and dA' can be found using Snell's law, which states that

$$\frac{\sin \theta'}{\sin \theta} = \frac{v_p}{c}. \quad (55)$$

CCD Applications in ICF Diagnostics

We find that

$$d\Omega' = \frac{\sin \theta'}{\sin \theta} \frac{\cos \theta}{\cos \theta'} \frac{v_p}{c} d\Omega, \quad (56)$$

$$dA' = \frac{\cos \theta}{\cos \theta'} dA, \quad (57)$$

and

$$u_p(\omega) = u_v(\omega) \left(\frac{c^3}{v_p^2 v_g} \right). \quad (58)$$

We set $cu_v(\omega)dAd\Omega$ equal to $v_g u_p(\omega) dA'd\Omega'$ to obtain $u_p(\omega) = u_v(\omega) [c^3/(v_p^2 v_g)]$ again. We now continue with the derivation of the bremsstrahlung emission rate from the inverse-bremsstrahlung absorption coefficient.

The classical inverse-bremsstrahlung absorption coefficient for $\hbar\omega \ll kT$ is given by⁷¹

$$\kappa = \frac{4\sqrt{2}\pi}{3} \left(\frac{\bar{Z} r_0^2}{\beta_{te}^3} \right) \frac{\ln \left(\frac{Q_{\max}}{Q_{\min}} \right)}{\sqrt{1 - \frac{\omega_{pe}^2}{\omega^2}}} \left(\frac{n_e^2}{n_c} \right). \quad (59)$$

Fig. 5-73. CCD applications in ICF diagnostics.

The intensity of a ray is attenuated with distance x as $\exp(-\kappa x)$. If we now set $j_{f-f}(\omega)$

equal to $\kappa v_g u_p(\omega)$ and make the low-frequency approximation $\exp(\hbar\omega/kT) - 1 \approx \hbar\omega/kT$, we recover Eq. (27).

In conclusion, the physics of bremsstrahlung emission seems to be well in hand. The strength of the measurement technique is that only a gross error in estimating the electron temperature will make a significant change in the inferred electron density. The ionization state Z must be accurately known, but fortunately we believe it can be accurately calculated given T_e and n_e . An error by a given factor in the length of the plasma, the ionization state, or the absolute calibration of the instrument measuring the bremsstrahlung emission, will cause the inferred electron density to be in error only by the square root of that factor.

Author: D. W. Phillion

CCD Applications in ICF Diagnostics

During the past two years we have developed a series of diagnostic instruments using charge-coupled devices (CCDs) as active

imaging arrays; these instruments have a wide range of applications. During 1980 a major part of our effort went into testing prototype instruments, integrating instruments into the Shiva laser operation, and preparing to provide production instruments for our diagnostics program. We also continued to develop new instruments and identify new CCD applications.

Figure 5-73 illustrates the present CCD applications at LLNL, and the developmental stage for each application:

- Red boxes indicate instruments that are operational, and that are in or close to production status.
- Blue boxes indicate that feasibility studies are in progress.
- Green boxes indicate areas where we are evaluating concepts and preliminary designs.

Our CCD instruments use variations of the RCA 52501 charge-coupled imaging device. We designed each instrument for its specific application, but because we used similar imaging devices in all of the instruments, we were able to maintain a set of common interfaces throughout the series. Each instrument has two interface ports:

- A video port provides real-time viewing of the CCD array's image, or instant playback of the image stored in the image memory. This allows immediate data

validation and speeds the testing, calibration, and alignment of the instrument or system. The video port also serves as the primary system interface for the CCD imaging camera.

- A digital port gives each instrument the capability to transmit the CCD array's digitized image to the memory unit. The memory stores the image and provides an interface to the computer system.

We can use either or both ports, depending upon the application.

The capability to digitize and transmit the CCD array's image to a computer data base provides the experimenter with computer-processed data within minutes. The CCD instrument replaces film output, which required several days to process and analyze.

CCD Streak Camera Readouts

We have two CCD streak camera readout systems installed and operating in the Shiva laser system. Figure 5-74 is a photograph of a 1.06- μm optical streak camera and CCD readout, installed on Shiva in March, 1980. This instrument monitors Shiva's temporal beam profiles at shot time (see "Output Sensor Design" in Section 2). Figure 5-2 (earlier in this section) is a photograph of the SX-2, an SXRSC installed on the Shiva

Fig. 5-74. Shiva-beam optical streak camera with CCD readout.

target chamber. This instrument, installed in January, 1980, is currently used to record the x-ray spectrum/time history of laser-irradiated targets. These two streak cameras are similar in operation except for the type of cathode; the optical camera uses an S-1 1.06- μm -light-sensitive cathode, and the x-ray camera uses an x-ray-sensitive cathode. The CCD readout electronics are identical in both cameras, and are packaged to fit the backs of their respective cameras.

Figure 5-75 shows the SXRSC diagnostic system schematically. The multichannel x-ray filter/reflector package forms a linear array on the streak camera's cathode, which generates a streaked phosphor image of this array. A coherent fiber-optic minifier reduces the phosphor image to an appropriate size on the CCD array. Because of the large flux of $\sim 300\text{-keV}$ x rays emanating from some Shiva targets, it is necessary to shield the CCD electronics. It is also necessary to deactivate the readout electronics at shot time, in order to obtain reliable readout operation. At shot time, the laser-system timing circuits trigger the streak camera and the CCD readout. This enables the CCD array to store the streak camera's phosphor image as electrical charges. The readout electronics are inactive while the charges are being stored, and they remain inactive until shot-related interference has subsided. The readout then digitizes the CCD array's image and transmits it to the

Fig. 5-75. Schematic of the SXRSC data-acquisition system at Shiva.

image memory. The memory stores the digitized image so that it can be retrieved later and archived by the Shiva data-acquisition system.

Unique features of the CCD streak-camera readouts include a streak-camera status monitor and internally stored streak-camera calibration data:

- The status monitor allows the computer system to check that proper voltages are present and that the camera is operational; this aids in the identification of diagnostic-system failures.
- The streak camera readout includes a programmable read-only memory (PROM) that contains the streak camera's serial number and calibration data. The streak camera's temporal-calibration procedure includes programming the PROM (see the following article).
- A "zero-time" trigger is another feature that makes these cameras easy to use. The CCD readout can be triggered at the same time as the streak camera, eliminating the need for a precisely timed pretrigger.

Figure 5-4(a) (earlier in this section) is a color-enhanced sample of a soft x-ray temporal record, obtained in a Shiva experiment utilizing the SXRSC/CCD readout described above. The image in the figure is that of the CCD array (i.e., the streaked output of the camera), with cursors added later to indicate the x-ray channels and energies. Figure 5-4(b) is the computer-analyzed output, showing plots of time vs intensity for the channels indicated in Fig. 5-4(a). The high-intensity pulse in the 450-eV channel is an artifact resulting from unconverted hard x rays; subsequent realignment of the camera has eliminated this artifact.

The data in Fig. 5-4 were available within minutes of the shot; as previously mentioned, we can validate such data immediately for calibration, alignment, and timing. The power of this feature becomes more evident when we operate the CCD instruments on one of our smaller support lasers, which require only minutes between shots. The results of the previous shot are available immediately to modify the next experiment.

CCD Imaging Camera

We have designed a CCD imaging camera for beam-profile imaging and diagnostic recording in the Nova beam-alignment control system (Figs. 5-76 to 5-78). The camera provides a standard composite video signal to Nova's TV switching network, replacing the vidicon camera used at Shiva. The CCD has the following advantages:

- Larger (>200) linear dynamic range; the dynamic range in future options will be even larger.

- Better anti-blooming properties; saturated picture elements have less influence on adjacent elements.
- A higher damage threshold.
- $1.06\text{-}\mu\text{m}$ interference patterns are more easily overcome.

Figure 5-76(a) is a photograph of a production-model CCD imaging camera. The camera head, shown in Fig. 5-76(b), contains the CCD array with a fiber-optic bundle glued to its face. The fibers have a 22° tilt from normal, so that the $1.06\text{-}\mu\text{m}$ -light direct-image interference pattern is converted to a fine-grain interference pattern

▲ Fig. 5-76. Nova CCD components: (a) beam-alignment imaging camera and (b) camera head.

Fig. 5-77. Schematic of data handling for the CCD imaging camera used in the Nova beam-alignment control system.

that cannot be resolved by the CCD imaging array—an essential feature in this application.

Figure 5-77 schematically illustrates the CCD camera in the Nova beam-alignment control system. The composite video-out of the camera is the primary connection to the system. The camera transmits the beam image through the TV network switcher to the video processor, or to the video monitors. The array processor receives beam-image data from the video processor and calculates beam-control data, which it transmits to the central system so that the beam can be repositioned. Any camera in the alignment system can store an image of the beam temporal profile at shot time. This operation is optional, and is accomplished by connecting the digital port of the cameras in the desired areas to memory units. The memory units provide an interface to Novanet, Nova's fiber-optic computer-to-computer/device local communications network.⁷²

Image Memory

Production units of the CCD image memory are now operating at Shiva, in our streak camera lab, at the Monojoule laser facility, and in other labs. The image memory stores digitized images transmitted to it by CCD instruments. The CCD instrument must digitize and transmit the image rapidly, to avoid large dark current build-up in the array and a resulting loss of dynamic range. Therefore, the memory must receive and store the 320-line by 512-pixel array at video rates. The image in memory can be cumbersome because of its size (160 kilobytes of data); to provide flexibility in accessing the image, the memory is arranged as an x-y addressable matrix, with records that can be read or written by row or by column. Once in memory, the digitized image can be accessed by computer, or by the instrument itself for instant video playback on a TV monitor. We can also have the computer add cursors, captions, and data plots to the image, by writing them into memory and then "playing back" the composite image.

The memory unit provides standardization and flexibility in system interfacing. Any CCD instrument that uses a digital port connects to an image memory, which

provides a standard hardware-system and software-system interface. Once a CCD instrument has been interfaced, other CCD instruments can easily be added. There are three types of plug-in image memory interfaces available:

- LSI-11 stand-alone computer interfaces.
- Shiva power-conditioning-bus interfaces.
- Novalink fiber-optic interfaces.⁷²

Ultrafast CRT

In present-day ICF experiments, the time scale for many phenomena ranges from hundreds of ps to several ns. Thus the time resolution necessary for measuring many of the associated electrical signals from diagnostic instruments is on the order of 100 ps. These time-resolution requirements translate to instrument bandwidths in the multigigahertz range. A large-bandwidth transient digitizer⁷³ (fast oscilloscope) is therefore an important instrument for many laser-fusion diagnostics.

In cooperation with Tektronix, we have experimented with a modified Tektronix R-7912 transient digitizer. The instrument's CRT and front end, the direct input's impedance-matching device, were modified to increase the bandwidth. We replaced the CRT's diode target array with a CCD array. The CCD's lower dead voltage allowed the beam potential to be lowered from 12 to 7 kV. This, and the better match between the beam velocity and the deflection structure, improved the deflection sensitivity.

Improved deflection sensitivity is necessary because increasing the front-end bandwidth requires a direct input with no amplification. Operation at the higher sweep speeds associated with higher bandwidths, in addition to the loss of front-end amplification, causes fewer electrons per pixel to be deposited on the CRT's beam target, resulting in lower amplitude signals. The CCD array has the capability to resolve and store these low-amplitude signals, which we can amplify later, during the digitization process. In addition, we can enhance the image by subtracting the CCD's digitized static background image from the digitized signal image. Figure 5-78 shows a modified CRT and a sample of the transient digitizer's output, a single 100-ps FWHM pulse from a Hewlett-Packard 33002A comb generator.

Fig. 5-78. Schematic of the ultrafast CCD/CRT used in the modified R-7912 transient digitizer.

New CCD Applications

As part of our effort to identify new areas for CCD applications (see Fig. 5-73), we have designed experiments to test the feasibility of new instrumentation in these areas. Typical of this work are our target-alignment activities. We have determined that we can generate an image by directly injecting electrons into the CCD array through contact with a needle point. This property can be used to aid in aligning laser beams onto a laser-fusion target. The front and back surfaces of the array are sensors separated by 10 μm . The target position can be indicated on one surface by direct contact of a needle attached to the target, while the laser beams are imaged and aligned on the opposite surface. Because the surfaces are separated by only 10 μm , the laser beams are precisely aligned to the target.

In summary, we have made significant progress during the past year towards our goal of implementing fast, computer-compatible CCD systems for recording and

retrieving data. Sample systems are in place in a variety of applications throughout the laser program. Production units are near completion and should be available for much wider implementation in the coming year. These systems will have a significant impact on our ability to retrieve and analyze laser and target data in Novette and Nova ICF experiments.

Authors: J. Cheng, J. T. Noonan, and G. R. Tripp

Major Contributors: J. F. Kimmons, L. Riley (Tektronix), R. Savoye (RCA), and R. J. Schnetz

Automated Streak-Camera Calibration Using a CCD Readout

We calibrate streak-camera sweep rates with a train of equally spaced optical pulses formed by placing an etalon in the path of a

single laser pulse. Normally, data are recorded on hard film that is developed, then digitized by using a microdensitometer. Technicians use the resulting lineouts to construct a plot of the sweep rate vs output location and, at a later time, to correct for sweep-circuit nonlinearities.

By replacing hard film with a CCD readout,⁷⁴ we can immediately display and analyze lineouts by using an on-line computer. A recently developed LSI-11 computer code, SCCAL, automatically generates lineouts after a laser shot and calculates calibration coefficients for linearizing the data.

SCCAL prompts the user to identify the sweep board that has been installed and to supply the streak-camera serial number, the etalon spacing, the CCD column for lineouts, and the desired order of fit; SCCAL then prepares the CCD readout to record streak-camera output on a laser shot. Figure 5-79 shows a sample lineout displayed on the computer graphics terminal immediately

Fig. 5-79. CCD lineout of streak-camera image.

Fig. 5-80. Plot of CCD sweep rate vs position. ▼

after a laser shot. The pulse train is formed with a 93-ps etalon placed in the path of a single, 40-ps 0.53- μm (frequency-doubled) laser pulse.

Based on the lineout, the user decides whether or not the shot data are worth keeping. If the data are acceptable, the lineout is automatically written onto a floppy disk, and a plot is generated showing sweep rate vs CCD element. The plot contains both raw data points and a polynomial least-squares fit to the data.

After the calibration curve is generated, the user can change the order of fit, take another shot, or exit the code. Just prior to exiting the code, the computer writes a floppy-disk file that contains the streak-camera calibration data. Figure 5-80 shows a second-order polynomial least-squares calibration curve fitted to data obtained on seven calibration shots.

Sweep-rate calibration and dc sweep-voltage optimization, which normally require hard film and a week or more for processing and digitizing, can be done better and without delay using a streak camera equipped with a CCD readout. The CCD also generates statistically meaningful calibration information in a form we can readily use to linearize streak-camera readouts.

Author: R. A. Lerche

Major Contributor: G. E. Phillips

Optically Driven Semiconductor (Auston) Switch

Laser-fusion experiments require detailed knowledge of the compression dynamics of the target. We are studying an electro-optic technique for taking a snapshot of the target while it is backlit by an x-ray source. In this way, surface interfaces and fuel geometry can both be examined. The parameters of critical importance for the electro-optic technique are

- Temporal and spatial resolution must be adequate to resolve important features.

- Dynamic range must be sufficient for information retrieval.

The snapshot approach requires gating the image detector with much less than a 500-ps aperture time, and electro-optic considerations dictate that electrical gating signals be on the order of 1 kV in amplitude.

Generation of such an electrical pulse is a critical step in the success of this approach.

One technique that we are studying uses the gallium arsenide (GaAs) Auston switch (Fig. 5-81),⁷⁵ and during 1980 we performed experiments with this switch using the Monojoule⁷⁶ laser facility. The laser was operated at a reduced output of 1 mJ or less with a pulse width of 50 ps. The experiments demonstrated the viability of this technology for generating fast, high-voltage electrical pulses.

The Auston switch is an electrically biased, optically driven slab of a high-resistivity semiconductor, such as Si or GaAs, that becomes electrically conductive when irradiated by 10 to 1000 μJ of optical

Fig. 5-81. Schematic of ▲ biasing, excitation, and recording functions of GaAs switch.

Fig. 5-82. Coaxial-structure mounting of GaAs switch. ▼

A Fast Optically Triggered Silicon Switch for Framing-Camera Applications

energy. GaAs was chosen for the first experiments because of its ability to operate at high levels (≥ 5 kV) of dc bias. We directed our experiments in two areas:

- Generation of pulses with fast leading edges.
- Generation of high-energy, very narrow electrical pulses.

The latter area has important applications in measuring the impulse response of very fast electrical systems.

Experiments were done using the Thompson-CSF TSN 660 oscilloscope, which has a characterized rise time of 100 ps, corresponding to an impulse response of 90 ps FWHM. An electro-optic schematic showing the biasing, excitation, and recording functions used throughout the experiments is shown in Fig. 5-81. The measured rise time of the GaAs switch mounted in a coaxial structure (Fig. 5-82)

was typically only 90 ps (Fig. 5-83), indicating that the oscilloscope rise time is faster than originally thought and that the switch rise time is somewhat faster. The peak amplitude of 1600 V demonstrates efficient switching, approaching the theoretical maximum of one-half the 3400-V bias voltage.

The GaAs switch was then packaged in a second coaxial structure with a charge line only 5 mm long to generate an approximation of a voltage-impulse function. The response of the oscilloscope to this pulse is shown in Fig. 5-84. Peak amplitude is 360 V and FWHM is 87 ps, essentially that of the oscilloscope itself. The source of the ripple following the main pulse is not yet known, but is most likely due to the switch mounting structure. This impulse generator is a powerful tool for time-domain characterization of electrical systems with bandwidths of up to at least 8 GHz.

Future plans include application of the switch to generate gating pulses for an x-ray image intensifier and to precisely characterize the impulse generator. The latter application is expected to lead to the design of an impulse source suitable for general use.

Author: J. D. Wiedwald

Major Contributors: R. H. Price, W. E. Kisic, A. S. Blum, and D. E. Campbell

Fig. 5-83. Rise time of GaAs switch.

Fig. 5-84. Approximation of voltage-impulse function in GaAs switch.

A Fast Optically Triggered Silicon Switch for Framing-Camera Applications

This year we have successfully operated a photoconductive, laser-activated silicon switch. Tested in a streak camera sweep circuit, the switch generated a voltage rise rate of 10 kV/ns—seven times faster than our fastest previous rate with other switches. Our conventional avalanche transistor sweep circuit⁷⁷ produces a sweep voltage rise rate of about 1.5 kV/ns and linearity of 10%, which is adequate for our streak camera application. The new LLNL optical framing camera,⁷⁸ however, requires an 8-kV/ns

A Fast Optically Triggered Silicon Switch for Framing-Camera Applications

ramp in order to realize the 100-ps frame times, and improved linearity in order to minimize image distortion. We have fabricated and tested the new, faster switch for framing-camera application.

Silicon and GaAs devices are reported to have demonstrated the ability to switch up to 10 kV in about 40 ps (Refs. 79–81), which makes them very attractive for fast-switching applications. Patterned after the work done by Mourou at the University of Rochester,⁸¹ we fabricated several 1-mm-gap and 2-mm-gap silicon and GaAs switches (Fig. 5-85). We tested the devices by using them as the switching elements of a resonant sweep voltage ramp generating circuit in an optical streak camera (Fig. 5-86). A single 35-ps pulse from a YAG oscillator was used as the optical source. Part of the pulse was split off, passed through a 93-ps etalon for timing calibration, and analyzed by the streak camera. The rest of the pulse was used to activate the switch.

A silicon switch, first described by Auston,⁸² is one of the simplest types of solid-state electron devices. Basically, it is a slab of semiconductor that serves as a photoconductor; assembled in a wide-bandwidth transmission line, it can serve as a ps rise-time switch or photon detector. When irradiated, electron-hole pairs are generated in the bulk material for each incoming photon that has an energy equal to or greater than the band-gap energy of the material. Photons with energy less than the band-gap energy can also generate electron-hole pairs, when deep-lying energy bands are provided within the forbidden energy gap by appropriate doping of the semiconductor.

Bulk conductivity, σ , is given by the relationship

$$\sigma = ne\mu$$

where n is the carrier density (in number/cm³), e is the electronic charge (in Coulomb), and μ is the carrier mobility (in centimeters squared per volt-second). A high photon-density rate will generate a proportionately high carrier-density rate and, therefore, the bulk conductivity can be considerably increased by the incoming laser beam.

In our laboratory we have fabricated these switches using 70-k Ω -cm Si. The geometrical "gap" is defined by the separation of the

electrodes on the switch. Standard microelectronics fabrication techniques are used to deposit the aluminum film electrodes on the silicon chip. These aluminum contacts are subsequently annealed. Pattern definition of the electrodes is made by conventional photolithographic techniques. In some

Fig. 5-85. Silicon and GaAs switches fabricated at LLNL in 1980.

Fig. 5-86. Silicon-switch breadboard of a sweep driver mounted on a streak camera.

switches we also produce a thermally grown 1- μm -thick SiO_2 passivation layer, to prevent possible reaction between the bulk silicon and the epoxy used to reduce electrical surface breakdown. With this technique we have achieved reliable operation at gap voltages of 5 kV/mm. We fabricated the GaAs switches using semi-insulating Cr-doped substrates, and again used standard photolithographic and microelectronics fabrication techniques to define and deposit Au-Ge, heat-annealed, ohmic contacts.

A major parameter in the performance of the Si switch is the carrier lifetime. The voltage rise time of the observed signal is determined by the photon-intensity rise time (as limited by the bandwidth of the transmission line); the fall-time of the signal, however, is determined by the carrier lifetime. Once carriers have been generated in the bulk solid, these carriers will be sustained for a period equivalent to the lifetime. For the silicon switches, having 70-k Ω -cm (almost intrinsic at 300 K), the nominal carrier lifetime should be in the ms range. We have been unable to do this measurement, however, because resistive heating of the bulk silicon from the applied bias voltage causes the bulk resistance to drop to about 100 Ω in only several hundred nanoseconds, effectively removing the bias voltage. In our application, this requires that the bias be pulsed on about 100 ns before arrival of the laser pulse.

For GaAs switches the carrier lifetime is less than 100 ps. Also, GaAs has high enough resistivity to permit a dc bias voltage. Recombination time for GaAs is so short, however, that the "switch" action essentially

follows the laser pulse and the switch opens again as soon as the laser pulse ends—an inconvenience in our streak and framing applications. Therefore, for electron-tube deflection applications, the Si switch is preferred. On the other hand, for fast-pulse and detector applications in the range below 100 ps, GaAs switches are preferred. For even faster switches, polycrystalline or amorphous silicon is preferred because of the much shorter (~ 10 ps) carrier lifetime.

The test results in Fig. 5-87 show that a sweep rate of 10.5 kV/ns was achieved with about 7 kV bias on the 2-mm-gap silicon switch. The 93-ps etalon pulses are separated by 19.5 mm in the photo, and the deflection sensitivity factor is 50 V/mm for the streak tube. Due to the resonant nature of the sweep-circuit design, we realized a peak-to-peak deflection-plate voltage of about 14 kV. This resulted in a substantial overscan (2 kV is needed for full-scale deflection) and, therefore, improved the linearity to about 1%. The silicon-switch ramp generator appears to be adequate to satisfy the framing-camera sweep requirements. We will pursue its development as our primary candidate for this application.

Author: S. W. Thomas

Major Contributors: R. Kalibjian and R. L. Peterson

Novette Target Alignment and Viewing Optics (TAV)

To view and align the Novette laser targets, we will use two of the existing Shiva target-alignment multiple-field instruments^{83,84} shown in Fig. 5-88. In addition, we will employ three newly designed single-translating-field (STF) instruments (Fig. 5-89). The multiple-field instruments will be used mainly to align the 5-mm-diam surrogate target. The STF instruments, which also have the capability of aligning the surrogate target, will be used primarily to position and view the laser-fusion target at several magnifications and with a resolution of better than 7 μm .

Fig. 5-87. Si switch test data (streak-camera output).

Novette Target Alignment and Viewing Optics (TAV)

The STF is a telemicroscopic instrument with an objective lens pair which relays the image of the target onto a fixed reticle having magnification $M \approx 1$. A second lens pair relays the image through a magnifying and focusing stage onto the TV detector. The objective lens pair and reticle are fixed after initial alignment, and serve as the bench mark defining the center of the chamber. The second lens pair is mounted on two orthogonal (x and y axis) translation stages which are normal to the optical axis (z axis) of the instrument. By translating the lens pair along the x and y axes, we can explore a field of 1 cm^2 at the target plane.

The magnifying and focusing stage consists of a lens wheel whose four sets of lenses relay the image to the TV detector at $1/4\times$, $1\times$, $4\times$, and $10\times$ magnification. In addition, the lens wheel is mounted on a translation stage which permits focusing of the lenses $\pm 0.5 \text{ cm}$ in the target plane. The STF instrument can therefore explore an object-space volume of 1 cm^3 at the target chamber center, with four different magnifications. Illumination of the target is provided by a He-Ne laser and a rotating optical wedge which removes the "speckle" pattern caused by constructive and destructive interference of the coherent laser beam on the vidicon surface.

The STF instrument was designed to provide a stable and accurate bench mark to define (within $10 \mu\text{m}$) the center of the chamber, for ease of operation and simple maintenance.

The instrument consists of three modules. The objective and reticle module is the key component of the STF instrument, because it defines the center of the chamber. The module houses the objective lens pair, the reticle, the reflector, and the blast shield. These components are mounted on a rigid internal framework (mounted rigidly to the target chamber), and shrouded with an external cover for protection. A mirror in back of the reticle optically couples this module to the next one; we avoid mechanical coupling between this and the next module to keep external loads from affecting the location of the reticle (the bench mark).

The relay and x, y translation module houses the relay lens pair, the x and y translation stages, and a folding mirror housing which is fastened mechanically to the next module.

The magnifying and imaging module houses the lens wheel for the four magnifications, the focusing stage, and a TV detector. The lens wheel and all translation stages are actuated by stepping motors, and can be operated remotely.

Fig. 5-88. Shiva target-alignment multiple-field instrument to be fielded on Novette.

Novette Target Alignment and Viewing Optics (TAV)

Fig. 5-89. Novette target-alignment viewer single-translating-field (STF) instrument.

The modular design of the STF instrument provides flexibility in the selection of mounting locations about the chamber. The folding mirrors within the modules give us the freedom to locate and mount the relaying and magnifying modules in virtually any location within the optical path length of the instrument.

Since the first module is not mechanically coupled to the second and third modules, the STF reticle is a reliable bench mark for defining the center of the chamber. Two such devices will locate the chamber center within $\pm 10 \mu\text{m}$, well within the restricted fields

Novette Target Alignment and Viewing Optics (TAV)

of view of hard-to-align instruments such as the 22× x-ray microscope system. The modular design of the STF ensures reliability, easy servicing, and flexible mounting which can explore a large (1 cm³) volume.

Authors: M. W. Kobierecki

Major Contributors: L. G. Seppala,
A. Cappabianca, R. V. Bantz, and K. R.
Manes

References

Three-Channel Soft X-ray Streak Spectrometer
5-2	1. <i>Laser Program Annual Report—1978</i> , Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-78 (1979), pp. 6-2 to 6-5.
2. <i>Laser Program Annual Report—1979</i> , Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-79 (1980), pp. 5-2 to 5-4.	3. <i>Laser Program Annual Report—1979</i> , Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-79 (1980), p. 5-7 to 5-14.
4. R. L. Kauffman, H. Medeck, and E. L. Pierce, <i>A Pulsed Calibration of the Soft X-ray Streak Camera</i> , Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-83095 (1979).
Pinhole Imaging Streak Camera
5-6	5. <i>Laser Program Annual Report—1978</i> , Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-78 (1979), p. 6-2.	
Multilayer X-ray Interference Mirrors for an Improved SXRSC Spectrometer
5-9	6. <i>Laser Program Annual Report—1978</i> , Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-78 (1979), pp. 6-2 to 6-5.
7. <i>Laser Program Annual Report—1979</i> , Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-79 (1980), pp. 5-7 to 5-14.	8. T. W. Barbee, Jr., and D. L. Keith, "Layered Synthetic Microstructures; Applications as X-ray Dispersion Elements," in <i>Lithography/Microscopy Beamline Workshop</i> , C.R. Dannemiller, Ed., SSRL Rept. No. 79/02 (1979), p. 185.
Production and Characterization of Soft X Rays for Diagnostic Calibrations
5-13	9. <i>Laser Program Annual Report—1979</i> , Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-79 (1980), p. 5-7.
10. <i>Laser Program Annual Report—1976</i> , Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-76 (1977), p. 3-7.
11. L. N. Koppel, "Sub-kilovolt X-ray Calibration of Photographic Film," in <i>Advances in X-ray Analysis</i> , W. L. Pickles, C. S. Barrett, J. B.	Newkirk, and C. D. Rund, Eds. (Plenum Press, New York, 1975), Vol. 18, p. 146.
12. R. L. Kelly and L. J. Palumbo, <i>Atomic and Ionic Emission Lines Below 2000 Å</i> , Naval Research Laboratory, Washington, D.C., NRL-7599 (1973).
Hyper-Filter-Fluorescer Spectrometer for X Rays Above 120 keV
5-15	13. <i>Laser Program Annual Report—1977</i> , Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-77 (1978), p. 3-64; <i>Laser Program Annual Report—1978</i> , Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-78 (1979), p. 6-8.
14. H. N. Kornblum, B. L. Pruett, K. G. Tirsell, and V. W. Slivinsky, <i>Filter Fluorescer Experiment on the Argus Laser</i> , Lawrence Livermore National	Laboratory, Livermore, Calif., UCRL-81471 (1978); also H. N. Kornblum, Lawrence Livermore National Laboratory, Livermore, Calif., private communication (1980).
15. T. L. Harper, <i>The Fluorescer Code: Better the 2nd Time Around</i> , Lawrence Livermore National Laboratory, Livermore, Calif., UOPB 72-22 (1972).
Streak-Camera Recording of Simultaneous Optical and X-ray Signals
5-19	16. <i>Laser Program Annual Report—1977</i> , Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-77 (1978), pp. 3-42 to 3-45.
17. <i>Laser Program Annual Report—1976</i> , Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-76 (1977), pp. 3-55 to 3-60.	18. <i>Laser Program Annual Report—1975</i> , Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-75 (1976), pp. 399-401.
19. <i>Laser Program Annual Report—1978</i> , Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-78 (1979), pp. 6-2 to 6-5.
A 662-keV X-ray Calibration Facility
5-21	20. R. D. Evans, <i>The Atomic Nucleus</i> (McGraw-Hill Book Company, New York, 1955), p. 717.	
22× Microscope Streak Camera
5-23	21. <i>Laser Program Annual Report—1979</i> , Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-79 (1980), p. 5-54.
22. <i>Laser Program Annual Report—1977</i> , Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-77 (1978), pp. 3-68 to 3-72.
23. <i>Laser Program Annual Report—1978</i> , Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-78 (1979), pp. 6-23 to 6-29.
24. <i>Laser Program Annual Report—1978</i> , Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-78 (1979), pp. 6-2 to 6-5.	25. <i>Laser Program Annual Report—1979</i> , Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-79 (1980), pp. 5-7 to 5-17.
26. <i>Laser Program Annual Report—1979</i> , Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-79 (1980), p. 5-25.
27. <i>Laser Program Annual Report—1979</i> , Lawrence Livermore National Laboratory, Livermore, Calif., UCRL 50021-79 (1980), pp. 2-37 to 2-42.

-
28. <i>Laser Program Annual Report—1979</i>, Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-79 (1980), p. 5-42. 29. E. M. Campbell, S. M. Lane, Y. L. Pan, J. T. Larsen, R. J. Wahl, and R. H. Price, "Determination of Fuel R of ICF Targets by Neutron Activation," Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-83073 (1979). 30. J. M. Auerbach, W. C. Mead, E. M. Campbell, D. L. Matthews, D. S. Bailey, C. W. Hatcher, L. N. Koppel, S. M. Lane, P. H. Y. Lee, K. R. Manes, G. McClellan, D. W. Phillion, R. H. Price, V. C. Rupert, V. W. Slivinsky, and C. D. Swift,	"Compression of Polymer-Coated Laser-Fusion Targets to Ten Times Liquid DT Density," <i>Phys. Rev. Lett.</i> 44, 1672 (1980). 31. J. H. Scofield, Lawrence Livermore National Laboratory, Livermore, Calif., private communication (1980). 32. R. W. Lee, <i>Line Shapes for Some Specific Transitions in Hydrogenic Lithium-like and Helium-like Ions</i>, Lawrence Livermore National Laboratory, Livermore, Calif., UCID-18876 (1980). 33. R. W. Lee and D. L. Matthews, <i>Using Spectral Line Profiles as a Diagnostic of the Plasma Electron Density</i>, Lawrence Livermore National Laboratory, Livermore, Calif. (to be published).	<p>Fuel Density Measurements Using Bromine L X-ray Line Imaging and Stark Profiles
5-32</p> |
|--|---|--|
-
34. N. M. Ceglio and L. W. Coleman, <i>Phys. Rev. Lett.</i> 39, 20 (1977); N. M. Ceglio and J. T. Larsen, <i>Phys. Rev. Lett.</i> 44, 579 (1980). 35. D. R. Ciarlo and N. M. Ceglio, <i>Ultrathick Photoresist Processing</i>, Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-83587 (1980).	36. J. M. Moran and D. Maydan, <i>Bell Syst. Tech. J.</i> 58, 1027 (1979); J. L. Vassen, <i>J. Electrochem. Soc.: Solid State Sci. Tech.</i> 126, 319 (1979); and F. Kalk, University of Rochester, Laboratory for Laser Energetics, Rochester, N.Y., private communication (July, 1980). 37. N. M. Ceglio and H. I. Smith, <i>Rev. Sci. Instrum.</i> 49, 15 (1978).	<p>Fabrication of High-Aspect-Ratio Microstructures for High-Energy X-ray and Particle-Imaging Applications
5-34</p> |
|--|---|---|
-
38. L. N. Koppel, Lawrence Livermore National Laboratory, Livermore, Calif., private communication (1980).		<p>Point Imaging with X Rays (PIX)
5-36</p> |
|---|--|--|
-
39. J. D. Lindl, <i>Low Aspect Ratio Double Shells for High Density and High Gain</i>, Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-80104 (1977).		<p>Evaluation of X-ray Backlighting Diagnostics for Nova and Novette Laser Targets
5-38</p> |
|---|--|--|
-
40. R. R. Goforth, F. J. Mayer, H. Brysk, and R. A. Cover, <i>J. Appl. Phys.</i> 47, 4850 (1976). 41. V. W. Slivinsky, H. G. Ahlstrom, K. G. Tirsell, J. T. Larsen, S. Glaros, G. B. Zimmerman, and H. O. Shay, <i>Phys. Rev. Lett.</i> 35, 1083 (1975). 42. <i>Laser Program Annual Report—1976</i>, Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-76 (1977), p. 5-65. 43. <i>Laser Program Annual Report—1979</i>, Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-79 (1980), p. 5-37. 44. <i>Laser Program Annual Report—1979</i>, Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-79 (1980), p. 5-42. 45. <i>Laser Program Annual Report—1979</i>, Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-79 (1980), p. 6-52. 46. M. H. Key et al., <i>Phys. Rev. Lett.</i> 45, 1801 (1980). 47. <i>Laser Program Annual Report—1978</i>, Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-78 (1979), p. 6-45. 48. <i>Laser Program Annual Report—1979</i>, Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-79 (1980), p. 5-39.	49. T. R. Fisher and J. D. Perez, <i>Appl. Phys. Lett.</i> 37, 702 (1980). 50. N. M. Ceglio and E. V. Benton, <i>Solid State Track Detectors in the Inertial Confinement Fusion Program at LLL</i>, Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-82550 (1980). 51. D. C. Slater, KMS Fusion, Dearborn, Mich., private communication (1980). 52. S. Skupsky and S. Kacenjar, <i>Measuring Fuel ρR for Inertial Fusion Experiments Using Neutron, Elastic Scattering Reactions</i>, University of Rochester, Rochester, N.Y., UR-LLE, Report 109 (1980). 53. T. E. Blue, D. B. Harris, and G. H. Miley, <i>Bull. Am. Phys. Soc.</i> 25, 940 (1980). 54. E. M. Campbell, H. G. Hicks, W. C. Mead, L. W. Coleman, C. W. Hatcher, J. H. Dellis, M. J. Boyle, J. T. Larson, and S. M. Lane, <i>J. Appl. Phys.</i> 51, 6065 (1980). 55. J. Stevens and L. Suter, Lawrence Livermore National Laboratory, Livermore, Calif., private communication (1980).	<p>Direct Fuel (ρR) Measurements by Neutron Activation
5-40</p> |
|---|--|---|
-
56. <i>Laser Program Annual Report—1979</i>, Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-79 (1980), p. 5-37.	57. <i>Laser Program Annual Report—1977</i>, Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-77 (1978), p. 3-82.	<p>Debris Collection and Background Measurements with Bromine-Filled Targets
5-45</p> |
|---|---|--|
-

References

Automated Radiation-Chemistry Diagnostic System
5-49	58. S. M. Lane, E. M. Campbell, and C. K. Bennett, <i>Appl. Phys. Lett.</i> 37 , 7 (1980).
59. <i>Laser Program Annual Report—1979</i> , Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-79 (1980), p. 5-39.	60. B. A. Jones, <i>Rad Chem Data Acquisition Chassis Users Manual</i> , Lawrence Livermore National Laboratory, Livermore, Calif., UCID-18570 (1980).
4ω Optical Probing
5-53	61. E. W. Marchand, <i>Gradient Index Optics</i> (Academic Press, New York, 1978), p. 44.	62. R. N. Bracewell, <i>Fourier Transform and Its Applications</i> (McGraw-Hill, New York, 1965), p. 262.
Analysis of Bremsstrahlung Emission as an Electron-Density Diagnostic
5-56	63. <i>Laser Program Annual Report—1975</i> , Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-75 (1976), pp. 424-425.
64. A. Sommerfeld, <i>Ann. Phys. (Leipzig)</i> 11 , 257 (1931); A. Sommerfeld and A. Mave, <i>Ann. Phys. (Leipzig)</i> 23 , 589 (1935). Sommerfeld's solution is further treated in Bethe and Salpeter, <i>Quantum Mechanics of One- and Two-Electron Atoms</i> (Springer Verlag, Berlin, 1957), Section 78.
65. J. D. Jackson, <i>Classical Electrodynamics</i> (John Wiley & Sons, New York, 1975), 2nd ed., Chapter 15.
66. Boyd and Sanderson, <i>Plasma Dynamics</i> (Barnes & Noble, Inc., New York, 1969), Section 9-6.
67. D. D. Clayton, <i>Principles of Stellar Evolution and Nucleosynthesis</i> (McGraw-Hill, New York, 1968), Section 3-3.	68. W. Heitler, <i>The Quantum Theory of Radiation</i> (Oxford at the Clarendon Press, 1954), 3rd ed., Chapter 5, Section 25.
69. Abramowitz and Stegun, <i>Handbook of Mathematical Functions</i> (Dover Publications, New York, 1968).
70. Whittaker and Watson, <i>A Course of Modern Analysis</i> (Cambridge at the University Press, 1963), Chapter 12.
71. R. E. Kidder, <i>Interaction of Intense Photon and Electron Beams with Plasmas</i> , Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-71775 (1969).
CCD Applications in ICF Diagnostics
5-62	72. <i>Laser Program Annual Report—1979</i> , Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-79 (1980), p. 2-102.	73. <i>Laser Program Annual Report—1979</i> , Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-79 (1980), p. 5-17.
Automated Streak-Camera Calibration Using a CCD Readout
5-67	74. <i>Laser Program Annual Report—1979</i> , Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-79 (1980), p. 5-17.	
Optically Driven Semiconductor (Auston) Switch
5-68	75. P. LeFur and D. H. Auston, "A Kilovolt Picosecond Optoelectrical Switch and Pockel Cell," <i>Appl. Phys. Lett.</i> 28 , 1 (1976).	76. <i>Laser Program Annual Report—1974</i> , Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-74 (1975), p. 290.
A Fast Optically Triggered Silicon Switch for Framing-Camera Applications
5-70	77. S. W. Thomas, G. R. Tripp, and L. W. Coleman, "Ultrafast Streaking Camera for Picosecond Laser Diagnostics," in <i>Proc. 10th International Congress on High Speed Photography</i> (Nice, France, September 25-30, 1972).
78. <i>Laser Program Annual Report—1976</i> , Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-76 (1977), p. 3-60.
79. G. Mourou and W. Knox, "High-Power Switching with Picosecond Precision," <i>Appl. Phys. Lett.</i> 35 , 7 (1979).	80. W. Marculis, W. Sibbett, J. R. Taylor, and D. J. Bradley, "Reduction of Jitter in Streak-Camera Synchronization with Picosecond Laser Pulses," <i>Opt. Commun.</i> 32 , 2 (1980).
81. G. Mourou and W. Knox, "A Picosecond Jitter Streak Camera," <i>Appl. Phys. Lett.</i> 36 , 8 (1980).
82. P. LeFur and D. Auston, <i>Appl. Phys. Lett.</i> 28 , 21 (1976).
Novette Target Alignment and Viewing Optics (TAV)
5-72	83. <i>Laser Program Annual Report—1977</i> , Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-77 (1978), p. 3-11.	84. J. A. Monjes, K. R. Manes, W. C. O'Neal, and F. Rienecker, Jr., <i>The Shiva Target Alignment and Viewing Instruments</i> , Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-80453, Rev. 1 (1980).

Section 6 Management and Analysis of Experimental Data

Management and Analysis of Experimental Data

Contents

Introduction	6-1
Fusion Experiments Analysis Facility	6-3
Beam Spatial Profile Analysis	6-7
Dante Temporal Unfolds	6-11
Pyroelectric Detector Data Processing	6-15
Raman Spectrograph Data Processing	6-18
Crystal Spectrograph Data Analysis	6-21
CCD Streak-Camera Processing	6-22
Optical Streak Camera	6-23
Soft X-ray Streak Camera	6-26
Novette Diagnostic-Configuration Data Base and Graphic Presentation	6-28
Target Shot Books and Archiving	6-32
References	6-34

Management and Analysis of Experimental Data

Introduction

Target-irradiation experiments at LLNL are designed to study a wide range of the aspects of laser-target interactions and ICF target physics. Generally, we design and execute sequences of tens of shots, called an experimental series, to study a particular aspect of the physics. We analyze the data from each target shot, combine these data with results from other shots in the same series and from other experimental series, and compare them with current theory and simulation results.

Figure 6-1 diagrams our data-acquisition and data-analysis processes. Data processing and correlation must be done promptly, completely, and accurately; one of our goals is the capability to perform the basic mechanics of these procedures without consuming large amounts of the experimenters' time. In the last few years, we have automated the acquisition of most shot data, using the Shiva computer system, and we have also begun to automate data processing activities to continue our improvements in the speed and accuracy of data processing.

The Data Management and Analysis group has the responsibility to design, develop, and maintain resources for the prompt analysis of data. The major processing areas of interest are

- Quick-look data processing. Some diagnostic results are available immediately after a shot; we use these data to roughly characterize and evaluate the shot.
- Fully automated analysis. Data are completely and thoroughly analyzed.

- Interactive analysis. Experimenters can interactively analyze data to verify calibrations, establish diagnostic characteristics, and process special data.
- Individual shot archiving. We must archive the complete raw data from a shot, including the configuration of the experiment, the calibrations, and the parameter files needed to reprocess the data.
- Shot summary. Results from a shot are summarized automatically.
- Experimental-series data base. We must develop tailored data bases for each experimental series so that we can correlate and compare data from different shots in the series.
- Analytical tools. Experimenters need a set of programming tools that can be used to quickly and easily process data from new diagnostics.

To meet these needs, we are developing and acquiring computational expertise, tools, and resources, including

- Responsive, interactive computing systems.
- Data-base definitions and processing tools.
- Rapid film digitization.
- Programming tools.

For our interactive computing capability, we have purchased a VAX 11/780 computer with Ramtek interactive color displays. This system is installed in the fusion experiments analysis facility (FEAF), which will handle classified data. The FEAF (see the following article) will centralize the data processing now being done on the Shiva PDP 11/70 and Octopus systems and is central to the design of the Novette and Nova computer-control systems, as the dedicated classified-data analysis machine.

During the past year, we have increased our understanding of data-base management technology and have defined several custom data bases. We have purchased a relational data-base management system, called ORACLE, for test and evaluation. We feel this system can greatly augment our efforts in data manipulation, archiving, and retrieval. We are currently using ORACLE to reconstruct several existing data bases to see if it will meet our needs for Novette and Nova data analyses.

Rapid film digitization remains a goal of our program, since we see a continued use of film for data recording on specialized instruments. The successful use of directly computer-interfaced CCD cameras on the streak cameras and other devices is reducing our need in this area, but not totally. We have begun investigating new digitization devices as well as methods for directly integrating the digitization process into the FEAF.

The development of new analysis codes is augmented by the availability of the programming languages MATHSY and Praxis. Many of the shot-data analysis routines are written in MATHSY and are operational on the LLNL Octopus CDC 7600 and Cray-1 computers. We are moving the MATHSY system onto the FEAF VAX 11/780, thus allowing the analysis routines to be integrated with the routines transported from the Shiva PDP 11/70. Praxis was developed for Nova controls programming (see "Praxis" in Section 2); however, it is also applicable to data manipulation and analysis programming tasks and is in use at the FEAF.

During the coming year, we will continue development in the areas discussed above, directing our efforts towards the activation of the Novette facility. We will define a security implementation plan for the FEAF and test the one-way data-communication link between the FEAF and the Novette control system. This one-way link will allow the transfer of unprocessed shot data from

Novette and Nova into the classified FEAF. In addition, we will develop definitions of the data bases and tools necessary for analyzing Novette data. Our program focus is such that, when Novette becomes operational in 1982, we will be able to provide completely automated reduction, analysis, and archiving of shot data.

Author: J. R. Greenwood

Fusion Experiments Analysis Facility

The hardware and software systems we use for the analysis of target and laser diagnostic data from Shiva and Argus have served us well. These systems have also shown, however, that they require significant improvement. After a typical shot, it has taken days or even weeks to completely reduce and process the data, with a high price paid in terms of manpower. This slow and costly analysis process has resulted from several factors

- The facilities and equipment needed for data reduction were not centrally located in the laboratory complex. One full-time staff position was devoted to hand-carrying data from the facility where they were obtained to another facility where they were analyzed.
- The data formats of the unclassified Shiva and Argus control and data-acquisition computers (responsible for data collection) are incompatible with the classified laboratory computer system (used for data analysis). In addition, data from classified shots must be physically transferred via magnetic tape to the laboratory computer system (Octopus) for analysis.
- Our Shiva PDP 11/70 control and analysis computer is overloaded.
- Effective interactive data-processing capability on the Octopus system is inadequate.
- The operational speed of the microdensitometer used to digitize film data from Shiva and Argus is too slow.
- We have no dedicated image-processing facilities.

After careful review of all the data-flow and data-analysis procedures, we determined that the most efficient way to handle and analyze the target and laser diagnostic data would be to concentrate all the necessary

computational resources in one classified facility. We have designed and implemented the fusion experiments analysis facility (FEAF), shown schematically in Fig. 6-2, to provide those resources and to respond to the data reduction and analysis needs of the Argus and Shiva target-irradiation facilities. In addition, we have planned for future needs that will arise from the Novette and Nova facilities now under construction. A rendering of the FEAF computer center is shown in Fig. 6-3, and the floor plan of the center is shown in Fig. 6-4.

One of our goals in designing the FEAF has been to provide rapid in-depth analysis of the target and laser diagnostic data. To this end, we require that the FEAF

- Be close to target-irradiation facilities and accessible to users.
- Perform all classified and unclassified data reduction and analysis from Novette and Nova.
- Allow permanent operation of Novette and Nova as unclassified facilities, except during the brief periods when classified experiments take place.
- Provide interactive color-graphics capability for image analysis.
- Provide film-digitization capability with direct data transfer to the analysis computer.
- Allow future upgrades of the system to handle future computational requirements.
- Give responsive interactive access to the facility to the personnel responsible for data analysis.
- Automate direct postshot data transfer from the unclassified laser facilities to the FEAF.

The central analysis computer chosen for the FEAF is a VAX 11/780 computer, shown in Fig. 6-5. This computer system is compatible with the Argus, Shiva, Novette, and Nova computers, thus permitting transfer of existing and future software between systems without modification. An

Fusion Experiments Analysis Facility

Fig. 6-2. Fusion experiments analysis facility (FEAF).

important feature of the FEAF is a digital image-processing and graphic-display capability that will improve the analyses of two-dimensional optical and x-ray images and of streak-camera data. The image-processing hardware consists of two color

displays and a hard-copy color camera. The system configuration of FEAF is summarized as follows:

- A VAX-11/780 CPU with fast floating-point unit and memory cache.
- A 4-Mbyte main memory.

Fig. 6-3. Rendering of the FEAF computer center.

Fusion Experiments Analysis Facility

- A VAX/VMS virtual-memory operating system and support utilities.
Two Versatec printer/plotters.
- Two 176-Mbyte RP06 disks for user storage.
- A 10-Mbyte removable disk cartridge for data transfers.
- Twenty CRT terminals, simultaneously operable without loss of efficiency.
- Two 125-ips 9-track tape drives and a TU77 controller for data transfers, backups, and data-base operations.
- Color-image processing system, two color-graphic displays, and two trackball cursor controls.
- A hard-copy color-graphic device (film and slides).

From January through March of 1980, we designed the system and obtained DOE approval for the major hardware purchases. In April and May, we placed purchase orders for most of the principal components and long-lead-time items. Due to lack of an appropriate permanent space in a classified area, we proposed, and had approved, an extension to our main office building that would be specially designed for computer operations. The new addition is now in final design. The location provides easy access to the users' offices and is close to the target irradiation area, thus reducing data transfer problems. This extension of approximately 2500 ft² will house all the classified and most of the unclassified computer operations for

Fig. 6-4. Floor plan for the FEAF computer center.

Fig. 6-5. FEAF main computer room.

Fig. 6-6. Sample high-▲
 quality graphic output
 available with new software.

Fig. 6-7. FEAFF
 communications
 network.▼

Fusion Experiments and will still provide sufficient room for expansion.

Until the end of 1981, when the new space will become available, the FEAFF is temporarily housed in a computer room that was upgraded by adding an independent air conditioning system, clean power, fire and thermal protection, and raised floors with cable trenches. Also included in the temporary facility are an image-processing room with the color-graphics equipment and an area for users' terminals and printer-plotter equipment.

Equipment for the FEAFF started arriving in September 1980. The VAX 11/780 was put into operation at the temporary facility in November with a minimum amount of memory (1 Mbyte) and with peripheral equipment comprising two RP06 disk drives, one TU77 tape drive, two Versatec printer-plotters, and eight terminals.

To reduce software development costs, we have purchased several software packages that support standard programming tasks. We acquired the packages DISSPLA and TELL-A-GRAPH, for example, and use them for all our graphics needs. These packages, which have already reduced software development time, produce high-quality graphs such as that shown in Fig. 6-6. With the help of these software tools, we are now upgrading our analysis codes and transferring them from the Shiva PDP 11/70 into the FEAFF. In less than two months of operation, we have improved the speed with which we analyze target diagnostic data; the quality and complexity of our graphic output have also been greatly enhanced with the new graphic software.

In the conceptual design of the FEAFF, we took into account the need to maintain shot-related data bases for carefully analyzing the relationship between all data accumulated from Shiva and Argus operations from the beginning to present experiments. These data bases should be easily accessible (i.e., on line), so there is a need for large disk storage. We also want the ability to rapidly combine aspects of several individual data bases to create new data bases. The most efficient way to manipulate and maintain these variable data bases appears to be with a data-base management system (DBMS). We are presently evaluating a relational DBMS, called ORACLE, and other systems to determine if they satisfy our requirements for

handling scientific data bases. If any of these systems prove satisfactory, we will standardize on one of them and establish data bases for all the diagnostic data.

In December 1981, when the new addition is complete, we will transfer the FEAF to its permanent location and clear the facility so that we can start data processing from classified experiments. (Target and laser diagnostic data are presently hand-carried to the FEAF temporary location on magnetic tape.) We will also implement a one-way Novette fiber-optics communication link,¹ as indicated in Fig. 6-7. These one-way communication links will permit transfer of data from an uncleared area into a cleared one, with hardware protection against transfers in the opposite direction. Classified and unclassified data will be transferred directly to the FEAF via these links, which will permit the operation of Nova and Novette as uncleared facilities except during the brief periods when classified shots take place. After a shot, target and laser diagnostic data will be promptly transferred and analyzed.

Additional computer hardware, consisting of 3 Mbyte of memory, another TU77 tape drive, and various communication and interface hardware, is scheduled to be delivered shortly. This equipment will give the FEAF enough capacity to handle all the data analysis needs for the Fusion Experiments program through 1982.

The effectiveness and analytic results of the FEAF during its short initial operational period have reinforced our decision that a medium-sized, dedicated computer facility is an efficient approach for our complex interactive data analysis.

Author: J. E. Vernazza

Beam Spatial Profile Analysis

Laser-plasma interaction phenomena are critically dependent on the intensity of the laser light irradiating the target. These phenomena include stimulated Brillouin and Raman scattering processes, production of thermal x rays, production of suprathermal electrons, and many others. In addition, the

distribution of light intensity irradiating a spherical target greatly influences the quality of the implosion. In view of these significant effects, it is essential to know the characteristics of the beams irradiating a target.

We have developed and implemented data-processing schemes to analyze the laser beams at the target for the Shiva and Argus laser systems. At both laser systems, we have used film cameras to record target-plane equivalent images of the beam energy distribution for the actual laser pulse.² Film records produce the most accurate data on the beam energy distributions; developing and digitization, however, are tedious, lengthy processes. We have begun to use CCD cameras, Quantex image digitizers, and image-processing software on the Shiva PDP 11/70 computer to record and analyze the focal spots produced by the Shiva amplifier chains when a continuous-wave (cw) laser propagates through each chain (Fig. 6-8). Large diameters or large eccentricities in these cw focal spots warn experimenters of alignment problems or defective components that must be corrected before the target experiment is carried out. In this article, we describe the Shiva cw focal-spot analysis

Fig. 6-8. Color contour plot of a digitized Shiva cw focal spot.

Fig. 6-9. Color-graphics ▲ display of QPIN output showing the centroid and the best-fit circle-to-pinhole image.

Fig. 6-10. Color-graphics display of QPIN output showing FWHM dimensions of spot and line profiles. ▼

software and then describe the latest software for analyzing beam far-field energy distributions on film.

In each Shiva incident-beam diagnostics module (IBD),³ an imaging lens is positioned to focus the cw beam onto the sensing area of a vidicon. Thus, the vidicon sees a focal plane equivalent to that of the f/6 target-irradiating lens of the beam monitored by the IBD. The quality of the vidicon image is the same as the quality of the beam incident on the target, since diffraction-limited optics are used in both optical systems. The focal-spot energy distribution is recorded with a Quantex video digitizer and stored in a PDP 11/34 computer used for Shiva laser alignment. The full digitized image is 512 × 512 pixels, but only the central 64-X-64-pixel region that contains the focal-spot image is stored on the disk. The data file is transferred via DECNET from the PDP 11/34 disk to the PDP 11/70 disks for processing. The graphics and analysis processing is then performed.

One of the image-processing codes produces a contour plot of a beam far-field image, which is displayed on a color monitor. A sample plot on the screen of such a monitor is shown in Fig. 6-8. Although this plot gives qualitative data on the shape of the far-field intensity distribution, more quantitative data, such as the dimensions and intensity profile, are necessary for the focal-spot verification procedure. To provide this information, we have written two codes to analyze the arrays of vidicon and CCD data.

Before determining the dimensions of an energy distribution, we must know the conversion factor of pixels to micrometres. This factor is determined by analyzing the image of a pinhole of known diameter, which is in the amplifier chain for each beam. We have written a code (QPIN) that calculates the centroid of the image, fits a circle to the image, determines the diameter in pixels, and then determines the scale conversion factor. The results of the fit are displayed with the pinhole image (Fig. 6-9). In addition to the conversion factor, the figure shows line profiles of the energy distribution along two perpendicular axes passing through the centroid of the pinhole.

Once the calibration factors are calculated and stored, that file does not need to be updated unless the IBD optics are changed.

Using the conversion factors, the dimensions of the focal spot for each beam are calculated using the code QBEAM. Figure 6-10 shows a typical output on the color display. The FWHM is given for horizontal and vertical axes passing through the centroid, and the energy profiles along these axes are also shown. The flat top on each profile in Fig. 6-10 is due to saturation of the camera. More optical neutral-density filters in the IBD module can be used to eliminate the saturation effects.

The IBD optics are designed so that the vidicon focal spot is nine times larger than the corresponding focal spot from the f/6 target-chamber lens. Thus, the focal spot in the center of the target chamber (Fig. 6-10) is an ellipse with FWHM values of $73\text{ }\mu\text{m}$ (horizontal) and $76\text{ }\mu\text{m}$ (vertical)—almost a circle. Records of focal-spot images are also produced as symbolic plots on an electrostatic plotter. The sample graph shown in Fig. 6-11 is the equivalent of the data shown in Fig. 6-8.

The output of the codes described here all provide pre-experiment data. The codes that we now describe provide data necessary for the analysis of target experiments.

Film from Shiva and Argus equivalent-plane cameras is digitized using a Photometric Data Systems microdensitometer interfaced to a PDP 11/20 computer. Digitized data are stored on magnetic tape and transferred to the LLNL Octopus computer system, on which the analysis is performed. (The process of digitizing film-recorded laser-energy distributions and processing these data to produce energy contour plots is described in Ref. 2.)

During the last year, we have developed additional software to statistically describe the properties of laser far-field energy distributions. The entire processing package is contained in a MATHSY⁴ code named BEAM ANL (BEAM ANaLysis), which performs the following functions:

- First, the code reads in from a disk file the microdensitometer data that represent the digitized data and scanning parameters.
- Second, using a calibration file containing the energy-density vs film-density data (D-log E curve), the code converts each data point in the digitized image array from units of film density to units of energy per unit area. This first set of functions is always performed; a second

optional set of functions is provided for performing an analysis of the beam profile.

A typical result for $2\omega_0$ experiments is shown in Fig. 6-12. The graph shows intensity distribution in the target plane, with intensity defined here as the energy density divided by the FWHM of the laser pulse. Magnification refers to the magnification between the far-field camera plane and the target plane. In this case, the magnification is 32.50, so the program divides film coordinates on the PDS tape by 32.50. We again note the large energy densities at the periphery of the distribution that are due to diffraction rings.

BEAM ANL can also first calculate the centroid of the energy-density distribution and then calculate an azimuthally averaged radial distribution of the energy-density distribution; i.e., for a given distance from the centroid, the program averages all data values around 360° of azimuth.

If requested, the code generates a three-dimensional contour map of the energy-density distribution. Figure 6-13 gives a sample plot of a laser-energy distribution in the equivalent target plane for $0.53\text{-}\mu\text{m}$ light at Argus. The high-energy densities at the periphery of the spot correspond to the

Fig. 6-11. Versatec symbolic contour plot of a digitized Shiva cw focal spot.

Beam Spatial Profile Analysis

diffraction rings created by using a hard aperture at the beginning of the laser amplifier chain.

The program can also produce a histogram distribution function, as shown in

Fig. 6-12. Radial average intensity distribution of focal spot from Argus $2\omega_0$ experiment.

Fig. 6-13. Three-dimensional contour graph of focal spot from Argus $2\omega_0$ experiment.

Fig. 6-14, where the ordinate is called $f(I)$ and I is the intensity in W/cm^2 . Consider two intensities, I_1 and I_2 ; the energy distribution function $f(I)$ is defined such that

$$\frac{\Delta E}{E} = \int_{I_1}^{I_2} f(I) dI \quad (1)$$

where $\Delta E/E$ is the fraction of energy in the laser pulse that was contained in the portion of the focal spot having intensities between I_1 and I_2 . Such a curve is useful in estimating the relative effects of simultaneously occurring laser-plasma interaction processes that are intensity dependent.

In conjunction with the analysis of Fig. 6-14, the running integral of the energy distribution is calculated as

$$\int_0^I f(I') dI' \quad (2)$$

This gives the fraction of energy in the beam due to intensities at and below the value of I . A sample running integral is shown in Fig. 6-15. The curve indicates that 50% of the

beam energy was supplied at intensities at or below $3.5 \times 10^{13} \text{ W/cm}^2$ and only 20% of the beam energy was due to intensities above 10^{14} W/cm^2 .

BEAM ANL can also produce a two-dimensional Fourier transform of the far-field intensity distributions. At the present time, we are not using this option; in the future, however, when diffraction-theory codes will be used to predict the intensity distributions that are used, the Fourier components of actually used intensity distributions will be compared to the Fourier components of the simulation codes to verify the relevance of the latter to the experiments at hand.

Our beam-profile analysis codes have provided invaluable data in the inter-

pretation of Argus and Shiva experiments. When implemented on the FEAF VAX computer, BEAM ANL will have color-graphics capability in addition to its current options. The CCD beam-analysis codes will be used extensively on the Novette and Nova systems, where they will provide laser technicians and experimenters with preshot beam-quality data. The images will allow determination of substandard beam quality and subsequent timely correction of faults so that improper irradiations of costly targets can be avoided.

Author: J. M. Auerbach

Major Contributors: G. S. Chinen, B. J. DeMartini, K. J. Pettipiece, and R. E. Turner

Fig. 6-14. Energy far ▲ field distribution function for focal-spot intensity distribution.

Fig. 6-15. A sample running integral of the focal-spot intensity distribution, as ▼ calculated in Eq. (2).

Dante Temporal Unfolds

A crucial parameter for laser-fusion target design is the time history of the thermal (low-energy) x-ray flux, which we record using Dante spectrometers⁵ and soft x-ray streak cameras (SXRSC).⁶ The SXRSC has a temporal response of 10 to 15 ps; hence, for a thermal x-ray pulse of 1 ns or more in duration, the output of the streak camera accurately represents the time history of the x-ray pulse itself. The fastest Dante diagnostic channels have temporal responses of 200 to 500 ps. Thus, for typical ablative-implosion target irradiations at Argus and Shiva, where the laser pulses are typically $\sim 1 \text{ ns}$, the Dante output is significantly modified due to the impulse response time of the instrument.

The problem of determining the source function from the recorded data requires a knowledge of the impulse response function; we must then process the data to generate the resolution-limited representation of the source function. For continuous functions such as Dante waveforms, this process can be accomplished simply and elegantly using Fourier transforms.

In applying this procedure, we must have previously measured the system temporal impulse response function, $h(t)$. This function is the output response of the system to an input delta function $\delta(t)$. If $S(t)$ is a source function applied to the system, and

$R(t)$ is the response of the system to this function, then S , h , and R are related mathematically by the equation

$$R(t) = \int_{-\infty}^{\infty} S(t - \tau)h(\tau)d\tau \quad (3)$$

The problem, given $R(t)$, $h(t)$, and the relationship of Eq. (3), is to find $S(t)$. This problem is easily solved using Fourier transforms.

First, we define the Fourier transforms of R , h , and S in the frequency domain ω as

$$\mathcal{R}(\omega) = \int_{-\infty}^{\infty} R(t)e^{i\omega t}dt \quad (4)$$

$$\mathcal{H}(\omega) = \int_{-\infty}^{\infty} h(t)e^{i\omega t}dt \quad (5)$$

and

$$\mathcal{P}(\omega) = \int_{-\infty}^{\infty} S(t)e^{i\omega t}dt \quad (6)$$

The convolution theorem of Fourier analysis states that, if $S(t)$, $h(t)$, and $R(t)$ are related by Eq. (1), then

$$\mathcal{R}(\omega) = \mathcal{P}(\omega) \cdot \mathcal{H}(\omega) \quad (7)$$

Thus, $S(t)$ can be found by calculating $\mathcal{R}(\omega)/\mathcal{H}(\omega)$ and then inverting back into the time domain by the relationship

$$S(t) = \frac{1}{2\pi} \int_{-\infty}^{\infty} \frac{\mathcal{R}(\omega)}{\mathcal{H}(\omega)} e^{-i\omega t} d\omega \quad (8)$$

We have developed software to automatically perform the operations in Eqs. (4) through (8) and, thus, automatically process Dante-data waveforms to produce the unfolded source functions. The fast Fourier transform (FFT) requires the use of 2^M data points, where M is an integer; for the Dante processing, we use 512 points ($M = 9$). The computer codes use the FFT algorithm,⁷ which reduces the number of calculations for an array of N values in the time domain to $N \log_2 N$, down from the standard value of N^2 .

The impulse response functions are derived from experimental measurements. We made measurements for three types of detector electronic systems

- A TSN 660 oscilloscope.
- A direct-access oscilloscope with a Tektronix R7912 transient digitizer.
- An amplified oscilloscope with a Tektronix R7912 digitizer.

The TSN 660 oscilloscope uses Polaroid film as its recording medium and is not used for automated processing; therefore, we discuss only the processing associated with the direct-access and amplified oscilloscope systems listed above.

Using the experimental technique described in the following paragraph, we derive the impulse response function for each scope (direct-access or amplified) and R7912

Fig. 6-16. Impulse response function for the direct-access oscilloscope system.

Fig. 6-17. Impulse response function for the amplified oscilloscope system.

digitizer system. The results for all systems are almost identical, except for very minor variations. As a result, we use two typical impulse response functions for data processing: one for direct-access scope systems, and one for amplified scope systems. This results in a much more efficient data-processing sequence with no loss in accuracy.

In our experimental measurements, we irradiated gold disks at Shiva with 1-kJ, 100-ps laser pulses. The thermal x-ray emission was measured simultaneously with several Dante channels and the SXRSC. The Dante channels provide the system response $R(t)$, and the SXRSC, with its 10-ps resolution, provides the source function $S(t)$. Then, $h(t)$ is found by using Eqs. (4) through (8) and solving for the system impulse response $h(t)$ by the relation

$$h(t) = \frac{1}{2\pi} \int_{-\infty}^{\infty} \frac{\mathcal{R}(\omega)}{\mathcal{H}^o(\omega)} e^{-i\omega t} d\omega \quad (9)$$

The derived standard impulse response functions for direct-access and amplified scope systems are shown in Figs. 6-16 and 6-17, respectively. The impulse response function data, along with the data defining the time base on which they are specified, are stored in two disk files that are manipulated by the processing software.

The first task of the unfold processing is to obtain the Dante channel waveform data from the consolidated Shiva shot-data files. This is done by the Dante processing code,⁸ which produces as output a file of 512 values of voltage from each transient digitizer record. Also included in these data are the sampling interval (in nanoseconds) between adjacent data samples and the relative time of the start of the waveform for each channel.

The unfold calculations, the file manipulations, and graphic output operations are accomplished by two codes. The first, UFP, performs the unfold:

- The appropriate impulse response function (for either scope system) is selected and redefined from its standard time base, $t_1(i)$, to the time base of the Dante waveform, $t_2(j)$. This process is illustrated in Fig. 6-18(a); as shown in the figure, linear interpolation is used. This operation is necessary for the Fourier transform calculations that follow.

- Next, the code searches back from the peak of the Dante pulse and finds the point at which the waveform first reaches its baseline value [Fig. 6-18(b)].
- The time base of the impulse response function is then shifted so its leading edge is slightly ahead of this point, as shown in Fig. 6-18(b). This process results in an unfolded waveform with its leading edge at the time origin.
- Next, the FFT calculations are carried out. These are just numerical equivalents of Eqs. (4) through (8). Before the inverse Fourier transform of Eq. (8), the quotient $\mathcal{R}(\omega)/\mathcal{H}(\omega)$ is filtered by a window function that drops to zero at the 20th frequency component. This eliminates all data noise and numerical noise

Fig. 6-18. UFP calculations.

(a) conversion of time base

(b) alignment of impulse response function to Dante waveform

Dante Temporal Unfolds

components from the unfolded waveform. A check must be made, however, to insure that this filtering does not remove any principal characteristics of the waveform. This check is done by taking the filtered transform, $\mathcal{P}(\omega)$, multiplying it by $\mathcal{H}(\omega)$, and then taking the inverse transform. The result should be the original Dante waveform minus the noise. These refolded waveforms are copied, along with the unfolded waveforms for all processed channels, on a disk file for use with subsequent programs.

At this point, UFP has completed its functions, and a second code, UFG, completes the unfold processing.

UFG produces graphic records of the unfolded and refolded waveforms for use by the experimenter and also writes a file of the unfolded waveforms; this file is copied and transferred to Octopus for further processing. The file is named SHOT-NUMBER.UNF, where SHOTNUMBER is the 8-digit shot number corresponding to the data. For each channel, the file contains the unfolded waveform data along with the time base interval, channel number, and CAMAC crate, station, and unit.

UFG uses the graphics software package DISSPLA to produce the waveform plots (Figs. 6-19 and 6-20). Figure 6-19 shows the results of an unfold for a direct-access scope

Fig. 6-19. Sample graphics output for a direct-access oscilloscope Dante channel.

Fig. 6-20. Sample graphics output for an amplified oscilloscope Dante channel.

channel. The unfolded waveform, along with its peak voltage, is shown on the left plot. On the right-hand graph are plotted the superimposed original and refolded waveforms, along with the impulse response function in its position (calculated in UFP) slightly left of the leading edge of the waveform. Note that the two waveforms (original and refold) are essentially identical, differing by 2 parts out of 900.

Figure 6-20 shows similar data for an amplified scope channel. Note that these data consist of both a Dante pulse (left) and a fiducial pulse (right). Note also the larger width of the amplified-scope impulse response function. As in Fig. 6-19, the refolded and original waveforms are nearly identical. The unfolded waveform always has a larger peak value and smaller FWHM than the original waveform as a result of an unfold process in which the impulse response function is a pulse with finite extent (not a delta function).

Conversion of Dante unfolds to time-dependent thermal x-ray spectra is accomplished on the Octopus computer system with the code UNSPEC.⁸ A voltage value for corresponding times is selected from each Dante-channel unfolded waveform. Each voltage value is related to an x-ray flux spectral component through the channel spectral-response functions. The result is an x-ray spectrum for a particular instant of time. This process is repeated for a preselected number of points on the channel waveforms to produce a representative spectrum for analysis.

Author: J. M. Auerbach

Major Contributors: K. G. Tirsell and R. A. Heinle

Pyroelectric Detector Data Processing

Our Raman spectrograph at Shiva provides time-integrated measurements of the light spectrum of stimulated Raman scattering (SRS). To obtain some temporal information on the SRS light, we installed a Moletron P5-01 fast pyroelectric detector on the Shiva target chamber, on a port adjacent to the Raman spectrograph port. The output of the pyroelectric detector was

typically 100 to 600 mV; therefore, we used a Tektronix 7104 oscilloscope to record the signals, since it was the fastest recording device available with the required voltage sensitivity. A timing fiducial, appearing near the end of the trace, was added to the pyroelectric signal through a "power tee" at the oscilloscope input. The fiducial signal was obtained from a fast photodiode (an ITT F4014 with an S1 photocathode) that samples one of the incident Shiva beams.

The pyroelectric detector has a fast rise time (10 to 90%) of about 200 ps, but it also has a long exponential tail with a time constant of about 1.5 ns, as shown in Fig. 6-21. To extract as much timing information as possible, particularly for very long signals, it is necessary to deconvolve Shiva pyroelectric signals using the impulse response of the detector. The impulse response was obtained by recording the signal from the detector when it was irradiated with a 50-ps (FWHM) 1.06- μm laser pulse from our Monojoule laser facility.

We calibrated the voltage responsivity of the detector using the 1.06- μm Argus laser beam after the first preamplifier. A beam

Fig. 6-21. Pyroelectric detector impulse response.

splitter (nominally 50%/50% at 45°) provided the reference beam to monitor the pulse energy, which was varied by the insertion of neutral-density filters in front of the splitter. We measured the exact beam-splitting ratio in place and checked the beam uniformity with precision apertures. A PIN diode calibrated to $\pm 5\%$ accuracy monitored the energy density (in J/cm²) that was incident upon the pyroelectric detector. The laser pulse was temporally Gaussian with a 700-ps FWHM.

We found the peak voltage responsivity of the detector to be linear at 7.4 V/MW up to an output amplitude $\lesssim 600$ mV, which corresponds to an incident energy density of ~ 7 mJ/cm². Calibration data supplied by Molelectron Corp. indicated a voltage responsivity of 13 V/MW. However, since the pyroelectric detector is too slow for its signal to follow the short laser pulse, we should divide the V-ns integral of the signal by the FWHM of the laser pulse to get a calibration of 11 V-ns/(MW-ns). It is this number that should be compared with the Molelectron measurement of 13 V/MW.

We plan to test one of these detectors to determine the energy densities at which permanent damage is done to the detector and at which the responsivity becomes nonlinear. Careful determination of thresholds for damage and nonlinear responsivity will allow us to expose these pyroelectric detectors to a wider range of energy densities while maintaining high confidence in the validity of the measurements.

The calibration measurements were plotted as J/cm² vs peak voltage from the

pyroelectric detector, before deconvolution, and were least-squares fitted with a straight line. Measured voltages from the detector during Shiva target irradiations then translate into the energy density of SRS light that fell on the active element of the detector. The range of wavelengths that can reach the active element is defined by windows and color filters that are placed in the light path between the Shiva targets and the detector. We chose the wavelengths 1.4 to 2.1 μ m because they are what the Raman spectrometer at Shiva specifies as important for Raman scattering of incident 1.06- μ m laser radiation.

To derive the "true" SRS light emission from the target (in J/sr) from the "detected" energy (in J/cm²), we must, of course, apply calibration factors to the measurements to account for the

- Solid angle subtended by the light collector on the Shiva chamber (0.985×10^{-3} sr).
- Reflectivity of the light-collector mirrors (0.9).
- Fiber-optic transmission (0.8).
- Fraction of the area illuminated by the fiber optic that is intercepted by the active element of the detector (6.09×10^{-2}). This factor was calculated on the assumption that the light emerged from the fiber optic with the same solid angle with which it was focused into the fiber optic. The area of the pyroelectric detector (0.785 mm²) and distance from the end of the fiber optic (7 mm) were both known.
- Transmission of the Infrasil window and the 4-64 and 7-56 color filters at 1.74 μ m (0.194).
- Factor due to the power tee at the oscilloscope where the timing fiducial is added (0.5).
- Variable factor, A, for the varying attenuation of the neutral-density filters that are inserted.

All these factors multiplied together equal (4.19×10^{-6}) A sr. We found that this calibration gave sensible and consistent results when compared to measurements from the independently calibrated Raman spectrograph at Shiva.

We also calibrated the voltage responsivity of the pyroelectric detector after deconvolution of the detector signals. We used the same procedure as described above, except that we plotted the deconvolved (voltage time) integral of the pyroelectric

Fig. 6-22. Detector impulse response deconvolved with itself.

signal vs incident energy (in J/cm²). Both calibration procedures yielded the same results (within $\pm 5\%$) for SRS from the Shiva targets. We therefore conclude that deconvolution of the pyroelectric signals, while useful for extracting time and amplitude details from very wide non-Gaussian pulses (associated with irradiations 2 ns or longer), is not necessary for shorter Gaussian pulses (associated with irradiations $\gtrsim 900$ ps).

We performed the deconvolution using the fast Fourier transform in MATHSY, an interactive programming language. The Fourier transform of the impulse response is first normalized so that the amplitude of its zero-frequency component is one; the area of the inverse Fourier-transformed impulse response will then also be one. A new function, $\tilde{H}(\omega)$, is then derived from the Fourier-transformed impulse response function, $\mathcal{F}(\omega)$, by

$$\tilde{H}(\omega) = \begin{cases} \frac{1}{\mathcal{F}(\omega)} & \text{if } \left| \frac{1}{\mathcal{F}(\omega)} \right| \leq M \text{ and } |\omega| < \omega_c \\ M \frac{|\mathcal{F}(\omega)|}{\mathcal{F}(\omega)} & \text{if } \left| \frac{1}{\mathcal{F}(\omega)} \right| > M \text{ and } |\omega| < \omega_c \\ 0 & \text{if } |\omega| \geq \omega_c \end{cases}, \quad (10)$$

where M and ω_c are defined below. The deconvolved signal is then

$$\mathcal{A}(t) = \mathcal{F}^{-1} [\tilde{H}(\omega) \tilde{\mathcal{P}}(\omega)] \quad (11)$$

where $\mathcal{F}^{-1}$ denotes the inverse Fourier transform; $\mathcal{P}(\omega)$ is the Fourier transform of the signal $\mathcal{P}(t)$, which is obtained by digitizing the oscilloscope trace; and $\mathcal{A}(t)$ is the deconvolved signal. The magnitude of $\tilde{H}(\omega)$ cannot be allowed to become too great, or any small high-frequency noise will be amplified so greatly that it will become larger than the signal. The maximum frequency amplification, M , was chosen to be five, compared to one for the amplification of the zero-frequency component. The very-high-frequency noise can be eliminated with a high-frequency cutoff, ω_c , without degrading the time resolution.

A useful test of the deconvolution procedure is to deconvolve the impulse response with itself, using the same values

for the parameters M and ω_c as are used in reducing the experimental data. The measured impulse response is shown in Fig. 6-21 while the deconvolution procedure gave the result shown in Fig. 6-22. The amplification of any frequency component relative to the zero-frequency amplification was limited to five. Ideally, the deconvolved impulse response would reproduce the 50-ps pulse; however, the procedure outlined above yields a pulse with about 350 ps between half-maximum points, compared with 800 ps for the raw signal, and shows ringing on either side. Thus, there may be temporal structure on a time scale faster than several hundred picoseconds, but our deconvolution procedure would not bring it out.

When the experimental data are reduced, only the Raman light signal is deconvolved; the fiducial is subtracted before the deconvolution is done and then added back afterwards. We encounter a slight complication, since the fiducial is superimposed upon the long exponential tail of the pyroelectric detector signal. Thus, we must first obtain a smooth fit to the tail through the fiducial; only then can we separate that part of the signal that is due to the Raman light from that part due to the fiducial. At present, the fiducial signal is not deconvolved with its impulse response.

Figure 6-23 is a photograph of an oscilloscope trace of the pyroelectric detector signal for a Shiva experiment in which a gold disk was irradiated at 5×10^{14} W/cm² with a 2.2-ns pulse. The oscilloscope was set at 1 ns/cm and 100 mV/cm. The laser irradiation period of 2.2 ns was achieved by delaying successive pairs of beams in the upper beam cluster by 550 ps; the last pair then arrived 2.2 ns after the first pair. In Fig. 6-24, which gives the signal from Fig. 6-23 after deconvolution (the red line), we see

Fig. 6-23. Pyroelectric detector signal for a Shiva gold-disk experiment.

Fig. 6-24. The Raman light signal of Fig. 6-23, after deconvolution, compared with calculated laser intensity on the target.

that each step in the signal corresponds to a peak in the Raman light emission. Also, the peaks in the Raman light emission occur when the calculated laser intensity on the target (the black line) is highest. The calculation uses the actual beam energies and time delays and the actual oscillator pulse width. Note that most of the Raman light detected was emitted near the end of the laser pulse.

We have found that, for long-pulse experiments (~ 2 ns), deconvolution of the pyroelectric signals makes their temporal structure more evident. However, in measuring time intervals between signal peaks and fiducial peaks, we have found that the raw data yield intervals within 50 ps of the deconvolved data.

Authors: D. L. Banner and D. W. Phillion

Raman Spectrograph Data Processing

For laser-plasma interaction experiments, it is important that we understand the contribution of stimulated Raman scattering to suprathermal electron generation.⁹ To determine the Raman contribution, we measure the scattered light from the instability region; we use the spectrum of the

scattered light to infer plasma densities and temperatures; and we then use these density measurements to describe the dynamics of suprathermal electron generation.

We have described a spectrograph for recording the spectrum of Raman scattered light in last year's Annual Report.¹⁰ The sensor in the spectrograph is an array of indium arsenide detectors that gives a set of charge pulses proportional to the incident energy. This type of signal lends itself to easy digitization and subsequent computer data processing. In this article, we describe the automated data processing (on the FEAF VAX 11/780) that provides experimenters with a spectrum of the Raman scattered light. We first describe the interface between the detectors and the computer and then describe the data processing.

Each of the 36 elements of the InAs detector is connected to a module of an LLNL programmable charge integrator; each module has an identifier number from 1 to 36. Four gain settings on each module allow a maximum analog-to-digital conversion count of 4095, corresponding to a nominal charge ranging from 1250 to 5×10^5 pC. This maximum nominal charge we denote by M . Each programmable charge integrator is calibrated off-line using a precision charge source for each gain setting. This defines the factor, F , that gives the exact charge as $M \times F$. In the first stage of the processing, we obtain the counts from an analog-to-digital converter (ADC) interfaced with each integrator module; these counts are then related to the charge output of the InAs detector. This is accomplished by knowing M and F and calculating the conversion factor in pC/count by

$$C = \frac{MF}{4095}$$

To find the charge from the detector, we multiply the output of an ADC by the value for C . This, in turn, indicates the light energy incident on the detector, which is, of course, the spectral component of interest.

The flow chart in Fig. 6-25 summarizes the codes, data files, and output used for Raman spectrograph computer processing. The code RAMAN first extracts the count data for the 36 detector channels from the shot disl file, which is identified by the CAMAC parameters for the charge integrator

Raman Spectrograph Data Processing

modules. These CAMAC assignment parameters (crate, preamplifier module, and channel) are found in the file RAMAN.PAR (Table 6-1), an input data file of the processing code. Next, the subroutine GETSD¹¹ returns the gain-setting identifier (an integer from 1 to 8), along with the ADC counts for all detector channels. While GETSD extracts these data from the shot-data file, the values of M and their associated scaling factors, F, are in the programmable charge integrator calibration file, PROCHIN.CAL. Using M and F, RAMAN now calculates C.

For each detector channel, the conversion factor, C, is then multiplied by the background-corrected ADC count (CNT) to obtain the charge (CH) due to the Raman scattered light. To perform the background correction, we obtain background counts in a baseline shot, taken prior to the actual target shot, and subtract them from the shot-data counts such that

$$CH = (C) (CNT) \quad .$$

The Raman spectrograph uses a series of glass filters in front of the detectors to selectively define the frequency of the

detected light. To convert the charge data into a spectrum, the transmission coefficient of each filter (and, in the case of multiple filters, the total transmission coefficient) must be determined from the transmission function for all filter elements that are used. Thus for a given wavelength, λ , a coefficient, T_λ , is given by

$$T_\lambda = f(\lambda) \quad ,$$

where, for each filter used, we define a function, $f(\lambda)$, from a series of discrete wavelengths and the corresponding transmissions. We precisely measure the transmissions, and we use a straightline interpolation to determine the transmission coefficient of any wavelength between the measured data.

The number of filters, along with their identifiers, is found in the file WAVEFILE.PAR. The identifiers correspond to files that contain the response functions of the filters (with wavelengths in μm) along with their corresponding transmission coefficients. In the case of multiple filters, if T_λ is a coefficient for a given filter at λ , then the total transmission,

Fig. 6-25. Raman spectrograph data processing.

Det	Crate	Station	CH	Preamp
1	9	2	0	46
2	9	2	1	46
3	9	2	2	46
4	9	2	3	46
5	9	4	0	43
6	9	4	1	43
7	9	4	2	43
8	9	4	3	43
9	9	6	0	34
10	9	6	1	34
11	9	6	2	34
12	9	6	3	34
13	9	8	0	13
14	9	8	1	13
15	9	8	2	13
16	9	8	3	13
17	9	10	0	29
18	9	10	1	29
19	9	10	2	29
20	9	10	3	29
21	9	12	0	30
22	9	12	1	30
23	9	12	2	30
24	9	12	3	30

Table 6-1. Setup parameters for Raman spectrographic data reduction (number of diodes: 24).

Raman Spectrograph Data Processing

T_{λ} , is given by

$$T_{\lambda} = \prod_{i=1}^N T_{\lambda_i} \quad (12)$$

where N is the number of filters in use.

The flux, FX (in $J/sr-\mu m$), is given by

$$FX = \frac{CH}{(S)(T_{\lambda})}$$

Fig. 6-26. Nonlinear $\blacktriangle$ response of the InAs detector-array elements.

$\blacktriangle$ Fig. 6-27. Sample RAMAN graphic output.

Det	CR	Stn	CH	Preamp	Lambda	Sens	Backgrd	Trans	Cnts	PC	M(Q)	Flux(J/μm)
1	9	2	0	46	1.480	0.147E+04	-1	0.208E-03	-90	0.322E+02	1.0621	111.576
2	9	2	1	46	1.510	0.202E+04	-5	0.246E-03	-116	0.403E+02	1.0835	87.805
3	9	2	2	46	1.540	0.259E+04	-5	0.316E-03	-142	0.502E+02	1.1119	68.260
4	9	2	3	46	1.570	0.344E+04	-4	0.383E-03	-186	0.665E+02	1.1643	58.714
5	9	4	0	43	1.600	0.389E+04	-1	0.479E-03	-223	0.809E+02	1.2163	52.833
6	9	4	1	43	1.630	0.485E+04	-5	0.537E-03	-222	0.787E+02	1.2081	36.486
7	9	4	2	43	1.660	0.439E+04	-5	0.577E-03	-223	0.797E+02	1.2117	38.104
8	9	4	3	43	1.690	0.328E+04	-4	0.599E-03	-194	0.693E+02	1.1738	41.377
9	9	6	0	34	1.720	0.332E+04	-1	0.591E-03	-157	0.570E+02	1.1330	32.942
10	9	6	1	34	1.750	0.361E+04	-5	0.564E-03	-137	0.481E+02	1.1055	26.081
11	9	6	2	34	1.780	0.530E+04	-5	0.569E-03	-111	0.378E+02	1.0766	13.471
12	9	6	3	34	1.810	0.608E+04	-4	0.602E-03	-92	0.324E+02	1.0628	9.419
13	9	8	0	13	1.840	0.591E+04	-1	0.629E-03	-79	0.296E+02	1.0556	8.391
14	9	8	1	13	1.870	0.579E+04	-5	0.705E-03	-70	0.242E+02	1.0429	6.179
15	9	8	2	13	1.900	0.634E+04	-5	0.782E-03	-63	0.218E+02	1.0376	4.567
16	9	8	3	13	1.930	0.608E+04	-4	0.881E-03	-57	0.197E+02	1.0330	3.803
17	9	10	0	29	1.960	0.644E+04	-1	0.970E-03	-49	0.176E+02	1.0286	2.898
18	9	10	1	29	1.990	0.641E+04	-5	0.112E-02	-46	0.150E+02	1.0232	2.138
19	9	10	2	29	2.020	0.515E+04	-5	0.130E-02	-25	0.722E+01	1.0093	1.090
20	9	10	3	29	2.050	0.392E+04	-4	0.151E-02	-20	0.587E+01	1.0071	0.999
21	9	12	0	30	2.080	0.251E+04	-1	0.176E-02	5	0.000E+00	0.0000	0.000
22	9	12	1	30	2.110	0.209E+04	-5	0.203E-02	7	0.000E+00	0.0000	0.000
23	9	12	2	30	2.140	0.131E+04	-5	0.238E+02	5	0.000E+00	0.0000	0.000
24	9	12	3	30	2.170	0.353E+03	-4	0.282E-02	12	0.000E+00	0.0000	0.000

Table 6-2. Reduced spectro-graphic data from the processing code RAMAN.

where CH is the charge output of the detector, T_λ is the transmission coefficient, and S is the sensitivity of the detector in pC/J/sr- μ m. The sensitivity value for all detectors is maintained in file RAMAN.LAM.

In the last steps of the spectral calculations, RAMAN corrects the flux measurement to account for the nonlinear response (Fig. 6-26) of the InAs detector-array elements. To best approximate the correction function, we have determined two analytic fits to a plot like that in Fig. 6-26. These fits are

$$CF = \frac{[e^{(CH/147.7)^{5/4}} - 1]^{4/5}}{(CH/147.7)} \quad (13)$$

for values of CH < 350 pC, and

$$CF = 4.246 \left(\frac{CH}{350} \right)^{2.1} \quad (14)$$

for values of CH > 350 pC. After applying this correction factor, we have the final form of the spectrum of Raman light, integrated over all wavelengths to give the total Raman scattered-light energy per solid angle. A sample of RAMAN tabular output of reduced spectrographic data is given in Table 6-2, and a sample of RAMAN graphic output is given in Fig. 6-27.

Author: G. S. Chinen

Crystal Spectrograph Data Analysis

At present, the x-ray crystal spectrographs that we use in ICF experiments use photographic film to record the spectra of target x-ray emissions. The instruments are designed so that there is a one-to-one correlation between the photon energy analyzed by a diffraction crystal and the distance along the length of the film where the diffracted x rays strike the film.¹² In some experiments, a collimating slit is placed between the x-ray source and the crystal, in which case the extent of a spectral line along

the width of the film is a measure of the size of the source for that spectral line.

Figure 6-28 illustrates examples of spectrograms for a titanium disk target; these data were recorded at Shiva as part of the shot series for characterizing our x-ray backlighting source (described in "Angular Distribution of High-Energy X Rays from Shiva-Irradiated Targets" in Section 7). Note the intense, characteristic lines of He-like titanium at photon energies in the neighborhood of 4.7 keV.

Our data-reduction and analysis routine for spectrograph film accomplishes the following tasks:

- The film is digitized to produce a file of binary data that contains film optical-density values and corresponding spatial coordinate values for a preselected region of the film.
- Computer analysis of the digitized film data converts the film-density spatial coordinate data into a spectrum that shows spectral intensity as a function of x-ray photon energy.
- Permanent records of the reduced spectrum are produced both as hard-copy graphs and as a computer file.

Fig. 6-28. Titanium disk spectra: (a) x-ray lines radiated by a titanium backlighting-source target and (b) spatially resolved 4.7-keV lines, with the spectrograph slit rotated about 15° out of the plane of the target.

In this article, we describe the steps involved in processing the data from spectrograms, like Fig. 6-28(a), that do not contain spatial information.

We use a PDS microdensitometer to digitize the film-recorded spectrograms. To establish a measure of the background levels on the film, we obtain two sets of lengthwise scans for each measurement: one set through the crystal-diffracted signal, and a second set across a region in which this signal was absent. The beam of light that probes the film has a rectangular cross section that is narrow in the direction of dispersed photon energy. We have observed that use of a beam with a cross section 25 by 250 μm appears to improve the visibility of sharp spectral lines. A scan set usually contains five individual scans, each one displaced widthwise from the previous scan. This procedure also improves the signal-to-noise ratio of the diffracted

Fig. 6-29. Reduced spectrum of x-ray lines radiated by highly ionized titanium.

data when the scans are averaged in the subsequent analysis.

The digitized information is transferred to magnetic tape and then to the disks of the Octopus system, where it is processed using codes written in MATHSY¹³ and the special-purpose code, SPEC, according to the following sequence:

- The code combination first reads in and averages the foreground and background scan sets, fits a smooth function to the background, and subtracts it from the foreground data to produce a density record that can be attributed to the diffracted signal only.
- Next, the analyst inspects the record and identifies a particular displayed spectral feature as a known x-ray energy. This procedure produces a proper registration between position on the film and dispersed photon energy.
- The code then proceeds automatically to calculate the spectrum, using previously stored algorithms for the dispersion and the film and crystal sensitivities. An example of a reduced spectrum is shown in Fig. 6-29.

The finished products of this analysis are graphs of the spectral intensity and the running integral of intensity, which is produced from the MATHSY output by the general analysis and the plotting code, GAP. Hard copies of the reduced data are distributed to the Experiments Group shot books, which contain all target diagnostic data. An ASCII list of the data used in the graphs is stored on a computer tape that can be read by any Octopus user.

Author: L. N. Koppel

Major Contributors: J. M. Auerbach and K. J. Pettipiece

CCD Streak-Camera Processing

Ultrafast optical cameras and x-ray streak cameras are prime diagnostics in laser-plasma interaction experiments. The intensity history of the laser pulse incident on the target is important in determining which plasma processes dominate during a target irradiation, and the time history of the

x-ray emission is important in diagnosing the performance of fusion targets. In the past, streak-camera outputs were recorded either on film or with linear Si diode arrays. The process of developing, digitizing, and analyzing the film data required several days, and the linear diode arrays lacked the ability of the streak camera to record many (~ 10) data channels. Since we strongly desire timely evaluation of each shot in an experimental series, we were motivated by the delay in data processing and the reduction in data-recording capability to use calibrated two-dimensional Si diode arrays to provide on-line digital recording of the two-dimensional output of our streak cameras.

We have now implemented CCD (charge-coupled device) recording arrays on our streak cameras. We couple these electro-optic arrays to the image intensifiers of the streak camera with fiber-optic arrays.¹⁴ The CCD integrated circuit measures 9.75 by 14.62 mm, the longer dimension being parallel to the sweep direction of the streak camera. There are a total of 163 840 elements in the array (320 elements per horizontal row and 512 per vertical column). The maximum charge out of an element corresponds to a count of 255 from the analog-to-digital converter interfaced to the array. Thus, the raw-data file manipulated by the processing software consists of 163 840 points ranging from 0 to 255. Each number corresponds to the amount of light from the region of the streak-camera phosphor that is coupled to an element of the array.

The CCD arrays are presently interfaced to the Shiva PDP 11/34 power-conditioning computer for initial data retrieval; data are transferred to the Shiva PDP 11/70 for analysis. The data processing for the optical cameras and SXRSCs is divided into preprocessing, analysis, and graphics. The first division arises from the need to have an interactive preprocessing level for establishing the proper parameters prior to analysis. The second and third divisions are due to the package sizes of the hard-copy graphics and the color-display graphics, which prevent us from combining analysis with graphics on the Shiva PDP 11/70. This restriction will be removed when the analysis is performed on the FEAF VAX 11/780 (see "Fusion Experiments Analysis Facility" earlier in this section).

Optical Streak Camera

The operator-interactive preprocessing step is designed to create a parameter file, OPTCCD.PAR, which contains

- The nominal input beam width (in ps).
- The sweep speed (ps/mm) used for the streak camera; the speed is identified by the sweep card being used.
- The etalon (partially reflecting mirror pair) array spacing (in mm).
- The spatial row through which a lineout is taken to determine the pulse (see the following article), enabling the operator to more accurately select the next two parameters.
- The temporal column, which defines the center of the pulse, and the increment about this column; these two parameters define the boundaries used to average the temporal lineout.

The program that establishes OPTCCD.PAR is CCDCOL. It begins by displaying the contour of the data from the CCD array. It next queries the operator for the spatial row that corresponds to the primary etalon pulse center (the fourth item above); CCDCOL then takes a lineout across this row to determine the pulse shape, as shown in the sample CCDCOL display in Fig. 6-30.

After determining the spatial lineout, the operator can then choose both the optimum temporal column, which corresponds to the center of the pulse in time, and the increment on both sides of this column to determine the boundaries for the temporal lineout. Note that CCDCOL counts the number of points that are saturated (i.e., those with values greater than 255) during the spatial as well as temporal lineouts. A sample lineout generated by CCDCOL is shown in Fig. 6-31, with the boundaries and saturation count indicated. Note the saturated region of the primary pulse; its dip is due to the zeroing of any saturated data points.

After the parameter file OPTCCD.PAR is established, we can begin analyzing the optical streak camera data (Fig. 6-32). The primary objective of the data analysis is to calculate the temporal profile and the full width at half maximum (FWHM) of the laser pulse and the deviation of this width from the FWHM of the oscillator pulse (the first item in the parameter file). In the case of

Optical Streak Camera

Fig. 6-30. Operator-interactive display of optical streak-camera preprocessing routine, CCDCOL.

Fig. 6-31. Sample temporal lineout generated by CCDCOL.

Fig. 6-32. Optical CCD streak camera data reduction.

Fig. 6-33. Graphics output of VADER indicating the primary pulse.

Soft X-ray Streak Camera

Shiva beam 10, which has an etalon array,¹⁵ the program calculates the sweep speed of the streak camera (in ps/mm).

The primary routine for the analysis is VADER. The routine simply calculates the temporal profile of the pulse and then calculates the FWHM (in ps). In the event of saturated data, the lineout is labeled "SATURATED DATA," and the waveform parameters are set to zero.

For beam 10, the analysis is a bit more involved, since the etalon array generates three streak pulses. VADER first calculates the sweep speed, S , from

$$S = \frac{(2d/c)}{(D/512)(C_2 - C_1)} \quad (15)$$

Fig. 6-34. Power scale plot generated by VADER from optical streak-camera data.

Fig. 6-35. Relative intensity scale generated by VADER.

where d is the etalon spacing file (in mm), c is the speed of light (in mm/ps), D is the vertical dimension (14.64 mm) of the CCD chip, and C_2 and C_1 are the centroid positions of the primary and secondary etalon pulses measured in CCD array columns. This calculated sweep speed is then compared with the sweep speed indicated by the parameter file to determine whether the etalon spacing is properly set.

The FWHM of the first pulse from the etalon is then calculated and compared with that of the oscillator pulse FWHM that is displayed by VADER, as shown in Fig. 6-33. This comparison is helpful in determining pulse-broadening effects. In the event of a saturated first pulse, VADER displays an operator warning message; since the centroid of the first pulse [C_1 in Eq. (15)] cannot be accurately determined, the calculated sweep speed, S , is then indeterminate and is set to zero.

The analysis routine, SKYWALK, uses beam-energy values to calculate the power history of a beam (in TW). SKYWALK is similar to VADER, but VADER is used in the diagnostic data processing package, while SKYWALK is used for setup and checkout of the laser system itself. Graphics for the data analysis are handled by the codes JAWA and CP30. The power-scale plot in Fig. 6-34 is generated by CP30, and the relative intensity scale in Fig. 6-35 is generated by JAWA. The power scale is calculated by dividing the beam energy (in J) by the integral of the counts-vs-time data obtained from the optimum temporal profile; this produces a conversion factor of TW/counts.

Soft X-ray Streak Camera

As for the optical streak camera data, the first phase of the analysis of the soft x-ray streak camera data is operator-interactive preprocessing. The program YODA establishes the parameter file SXRCCD.PAR, which contains the filter identifiers being used and the beginning and ending columns used in the lineout. These boundary columns are known before processing begins, unlike those for the

optical streak camera, since the filters physically define the regions.

YODA first displays the data on a color graphics display and reads in the latest copy of SXRCCD.PAR; it then displays the filter boundaries defined by SXRCCD.PAR (Fig. 6-36). If the operator wishes to change any filter identifier or any boundary settings, he or she is prompted to do so. YODA then rewrites SXRCCD.PAR with the new values.

The next level of analysis is simpler than the corresponding analysis for the optical streak camera. The analysis routine, OBIWAN, generates the lineout (with the background subtracted), calculates the waveform parameters, and displays the results (Figs. 6-37 and 6-38). As before, saturated data are so indicated, and, if any pulse has a maximum of less than five counts, a "NO PULSE" message is displayed on the color monitor. Finally, OBIWAN generates a data file, called "Shot #".SXR (where "Shot #" is the actual 8-integer shot number), for completing the

Fig. 6-36. SXRSC data reduction.

Fig. 6-37. Sample display of OBIWAN analysis of SXRSC data.

processing. The data file serves as an input file for the graphics routine, CHUWAKA, that generates the hard copy (Fig. 6-39). The data file is also transferred via magnetic tape to the Octopus system for the final spectral-unfold processing.

Further development for the overall analysis scheme on the FEAF VAX is now being done. The interactive processing implemented on the VAX is being redesigned to minimize the necessary interaction. The operator still has the responsibility, however, to ensure that the hardware configuration (filters, etalon spacings, sweep speed cards, etc.) corresponds to the current software parameter files.

Fig. 6-38. Initial YODA display showing filter boundaries defined by SXRCCD.PAR.

Fig. 6-39. SXRS CCD processing (relative intensity counts).

The second major area of improvement is in program consolidation. Since the virtual-memory capability of the VAX removes program-size restrictions, the analysis and graphics routines are being combined into one program. We have also obtained a more powerful and versatile graphics package, DISSPLA, that has improved the quality of our color graphics and hard copy.

Author: G. S. Chinen

Major Contributors: J. M. Auerbach and R. G. Ozarski

Novette Diagnostic-Configuration Data Base and Graphic Presentation

The Shiva target-chamber diagnostic data base¹⁶ and its associated processing software¹⁷ have been an invaluable aid in planning experiments. This data base for configuring diagnostic instruments has provided our experimenters with maps and tables of the status and position of the 200 or more diagnostic instruments installed on the Shiva target chamber. The various forms of output allow experimenters to easily plan for the installation of new instruments for future experiments, while providing neat, compact, and accurate records of the diagnostics used in past experiments. In view of the vital function of this data-processing scheme, we have extended it for use with the target chamber of the planned Novette laser system.

Since the Shiva target chamber is to be used in Novette, conversion of the data-base structure was a relatively simple task. The major modification consisted of removing the entries for the ports through which the 20 Shiva beams enter the chamber and replacing those entries by two large apertures through which the Novette beams will enter to irradiate the targets. Similarly, the graphics software that draws the target-chamber configuration was altered to show 2 beams instead of 20.

In a format similar to the Shiva data base, the Novette target-chamber data base, TCNOVT, is arranged by port coordinates in a spherical coordinate system with

independent variables θ and ϕ ; θ is the polar angle that originates at one beam axis and terminates at the other, and ϕ is the azimuthal angle that originates at the target positioner and rotates in the right-handed convention with respect to the $\phi = 0^\circ$ direction.

Sample entries for the data base are shown in Table 6-3. Table 6-3(a) shows the data for a 4-in.-diam port located at $\theta = 60^\circ$, $\phi = 36^\circ$; this port has a FREE status. The OUTSIDE DIM line would give the length that an object would protrude outwards from the port cover. Table 6-3(b) gives the format for a port at $\theta = 60^\circ$, $\phi = 0^\circ$; this port is IN USE. The diagnostic information starts with the line beginning with EXP; the entry XRSC02 is the six-character label for the diagnostic instrument at this port, x-ray streak camera No. 2. All diagnostics are labeled with a unique six-character group. The first four letters are standard diagnostic codes, presented in Table 6-4. The

remaining two characters identify particular units of the same diagnostic instrument. Each EXP line also contains the status of the diagnostic for a given time: IN USE or NOT USED. The sample entry in Table 6-3(b) also shows the distance (DIST) that the diagnostic protrudes into the target chamber and its transverse dimensions at that innermost point (DELTA X and DELTA Y). These three parameters are used to calculate the solid angle subtended by the instrument. Table 6-3(c) gives a sample entry for a port that holds several diagnostics; these are listed sequentially, starting with EXP lines and terminating with EOEXP (end-of-experiment) lines. Each experimental data entry is terminated by an EOEXP line; each port entry ends with an EOP (end-of-port) line.

We have developed data-processing codes on the FEAF VAX 11/780 to manipulate the contents of the data base for various operations. A code named PLTNOVT

Table 6-3. Sample entries in the Novette diagnostic data-base code, TCNOVT.

(a)				
!				
Port	Free			
Theta		60.		
Phi		36.		
Size		4.	10.16	
Outside Dim		0.	0.	
!				
EOP				
!				

(b)				
!				
Port	In Use			
Theta		60.		
Phi		0.		
Size		4.	10.16	
Outside Dim		480.	1219.2	
!				
!	X-ray Streak Camera			
!				
Exp	XRSC02	XS	2.	In Use
Owner	Medeki			
Delta X		10.16		
Delta Y		10.16		
Radial Dist		0.0		
EOEXP	XRSC02	XS	2.	
!				
EOP				
!				

(c)				
!				
!				
Port	In Use			
Theta		75.		
Phi		306.		
Size		4.	10.16	
Outside Dim		48.	121.92	
!				
Module	EBMD04			
!				
!	Plasma Calorimeter			
!				
Exp	LC2704	EBMD	4.	In Use
Owner	Rupert			
Delta X		10.16		
Delta Y		10.16		
Radial Dist		0.0		
EOEXP	LC2704	EBMD	4.	
f				
!	Laser Calorimeter			
!				
Exp	LC2104	EBMD	1.	In Use
Owner	Rupert			
EOEXP	LC2104	EBMD	1.	
!				
!	Scattered Light Photodiode			
!				
Exp	SLPD04	EBMD	1.	In Use
Owner	Phillion			
EOEXP	SLPD04	EBMD	1.	
!				

Novette Diagnostics

Table 6-4. Diagnostic instrument labels and identification codes.

Description	Four letter code	Symbol	Color	Category code
LC-21 laser calorimeter	LC-21	L1	Yellow	1
LC-27 plasma calorimeter	LC-27	L7	Green	4
Scattered light photodiode	SLPD	PD	Yellow	1
Scattered light streak camera	SLSC	SS	Yellow	1
Plasma calorimeter particle diagnostics	PLSC	PC	Green	4
Ion calorimeter	ICAL	IC	Green	4
X-ray calorimeter	XCAL	XC	Red	2
Alpha time of flight	ATOF	AT	Violet	5
Alpha zone plate	AZPC	AZ	Violet	5
X-ray microscope	XRMS	XM	Red	2
Filter fluorescer	FFLE	FF	Red	2
X-ray zone plate	XZPC	XZ	Red	2
X-ray streak camera	XRSC	XS	Red	2
Dante S	DANS	DS	Red	2
Dante N	DANN	DN	Red	2
Neutron time of flight	NTOF	NT	Blue	3
Neutron yield (copper)	NCUA	NC	Blue	3
Neutron yield (lead)	NPBA	NP	Blue	3
Radiochemistry	RDCH	RC	Blue	3
Neutron yield (oxygen)	NOXD	NX	Blue	3
Neutron yield (NE111)	NYLD	NY	Blue	3
Light box calorimeter	BCAL	BX	Yellow	1
Target viewing instrumentation	TAVI	TV	White	6
Target positioner	TARP	TP	White	6
X-ray angular distribution	XRAD	XA	Red	2
2-5 keV spectrometer	SP25	SP	Red	2
Pinhole box calorimeter	PCAL	PC	Yellow	1
Energy balance module	EBMD	EB	Yellow/green	1
X-ray pinhole camera	XPHC	XP	Red	2
Sputtering calorimeter	LC38	L8	Green	4
Sputtering calorimeter	LC39	L9	Green	4
Faraday cup	FCUP	FC	Green	4
Mirror Dante	DANM	DM	Red	2
Neutron interval timer	NINT	NI	Blue	3
Argon imaging spectrometer	SPAI	AI	Red	2
Silicon imaging spectrometer	SPSI	SI	Red	2
Low-energy spectrometer	SPLE	LE	Red	2
Brillouin spectrometer	BSSP	BS	Yellow	1
Raman spectrometer	RSSP	RS	Yellow	1
Optical pyrometer	OPPY	OP	Yellow	1
Soft x-ray streak camera	SXRS	SX	Red	2
X-ray UCP	XUCP	XU	Red	2
X-ray int streak camera	XSIN	XI	Red	2
Silver act. detector	NAGA	NG	Blue	3
XC-29 x-ray calorimeter	XC29	X9	Red	2
Low energy x-ray angular distribution	LXAD	LX	Red	2
Debris shield	BSXX	BS	White	6
Vacuum port	VACP	VC	White	6
Laser window	BEAM	BM	White	6
Vent port	VENT	NV	White	6
Vacuum gauge	VACG	VG	White	6

produces polar plots of the target-chamber diagnostic configuration. The sample plot shown in Fig. 6-40 is a polar representation of a sphere; the radial coordinate represents the spherical polar angle, θ , and the azimuthal coordinate represents the spherical azimuthal angle, ϕ . The solid angles subtended by the two Novette beams are represented by the two shaded areas.

Each instrument is represented by an ellipse centered at its designated location on the target chamber and having axes corresponding to the solid-angle parameters, $\Delta\theta$ and $\Delta\phi$, that it subtends on the target-chamber sphere. Each ellipse is labeled by one or more two-letter codes corresponding

to the diagnostics it represents; these two-letter label symbols are presented in Table 6-4. The solid-angle parameters are calculated from the distance the diagnostic protrudes in the chamber and its transverse dimensions at its innermost point. If a diagnostic map shows overlapping ellipses, the experimenter is alerted that one or more instruments are interfering with the field of view of another; thus, the diagnostic experimenter can use the map to prevent or remedy interference problems. Maps of diagnostic configurations can also be plotted on color-graphics displays, in which colors, rather than symbols, label the various diagnostics.

Fig. 6-40. Sample PLTNOVT polar plot of the target-chamber diagnostic configuration.

Option	Operation	Result
A	Enter port coordinates	Receive name, owner and solid-angle parameters of all diagnostics on that port
B	Enter 6-character diagnostic name	Receive owner name and solid-angle parameters
C	Enter 4-letter diagnostic code	Receive names, owners, coordinates, and solid-angle parameters of all diagnostics corresponding to that code
D	Enter experimenter's name	Receive name and coordinates of all his/her diagnostics
E	Enter category code	Receive name, owner, and coordinates of all diagnostics in the category
X		Terminate the program

Table 6-5. User options in the diagnostic-search code, CKNOVT.

A second code, named CKNOVT, allows the user to make parameter searches of the diagnostic data base. This code eliminates the need for an experimenter to scan through a large printout of the data base to obtain a very small amount of information. With CKNOVT, the user can search the data base with the computer and rapidly obtain answers on a video terminal. These and other options available to the user are shown in Table 6-5. If the user wants to know the locations of all LC-27 plasma calorimeters, for example, he or she would select option C, enter the four-letter code LC-27, and receive the list of coordinates on the terminal.

The Novette target diagnostic data base is being gradually expanded to include electronic (CAMAC) information, detector characteristics, and calibration factors. With this large amount of data, the data base will ultimately be used to provide parameters for diagnostic data-processing codes as part of a more sophisticated data-base management system.

Author: J. M. Auerbach

Major Contributors: K. A. Coulson, C. E. Thompson, and J. E. Vernazza

Target Shot Books and Archiving

Within about two weeks after any target shot, results from the shot are analyzed and then summarized (with the data) in the experiment shot book. Shot books provide

the reference for comparisons to preshot expectations, diagnostic calibration and reliability, and evaluation of trends and target performance. Currently, all the shot books from target experiments on Janus, Cyclops, Argus, and Shiva are stored in a central vault.

The individual shots in these books are grouped by experimental series. Data from each shot are entered into the following categories of data and parameters:

- Shot summary. All shots go into this shot-book index.
- Shot logistics. This file contains setup sheets, check lists, port status, and data sheets on various diagnostics.
- Laser. Under this heading, we include the laser-system summary prepared by the operations group, data from the equivalent plane camera, and LITAR and PLANAR¹⁸ calculations of laser intensities on targets.
- Target. This section contains information on target-alignment diagnostics; target construction; target-alignment record-lens presets; and photos of the target alignment, with a cw laser beam irradiating the target in its correct position for alignment.
- Energy balance. Data from photodiodes, plasma calorimeters, and reflected-light laser calorimeters are kept under this heading in the shot book.
- Scattered-light spectroscopy. This heading contains data from the Raman spectrometer and the optical multichannel analyzer, along with Brillouin data and optical-pyrometer data.
- X rays. Filter fluorescer, Dante, x-ray microscope, x-ray streak camera, x-ray crystal spectrum, and zone plate camera images are collected here.
- Charged particles. Under this heading, we archive Thompson parabola data, alpha-particle time-of-flight spectrometer data, and ion spectrometer data.
- Neutrons. Photos of oscilloscope traces of neutron scintillation (NE111), printouts and graphs for copper and lead neutron-activation detector systems, and neutron time-of-flight spectrometer data are stored here.
- High-density diagnostics. This section of the shot book contains a record of radiochemistry system measurements and seed-gas spectroscopic data.

- TACAI raw data. Under this heading, we log computer printouts of raw data.

A large percentage of the shot books are classified, adding security to the list of storage requirements. The shot books are kept in appropriate vaults, but the number of books creates a space problem. To alleviate this problem, we are consolidating data on microfiche.

After we microfiche unclassified shot books (Fig. 6-41), we destroy the original and place the microfiche in an experiment-series binder, along with all articles that were written concerning the series. Each binder thus contains raw information from multiple shots, along with summaries and conclusions about the complete series. This process reduces the amount of space required for storage and allows unclassified data results to be more easily stored and accessed.

We are also having the classified shot books microfiched, and we are grouping them by experimental series. This is a more time-consuming process, however, since we must conform to security requirements. The average classified shot book is approximately 50 pages long, while unclassified books are slightly shorter; there are usually 30 to 40 shots per experimental series. Once the classified shot books are documented, they are taken to the print room where they are microfiched. The original copies are then destroyed, and the microfiche is recorded as a new classified document and stored in a vault.

We expect that it will take one year to convert all shot books to microfiche, but this conversion will result in a ten-fold reduction

Fig. 6-41. Flow chart of process for converting shot books to microfiche.

in necessary storage space. An ongoing microfiche process will be established for new shots to further minimize the storage space required for housing these valuable documents.

Author: K. A. Coulson

References

Fusion Experiments
Analysis Facility
6-3	1. <i>Laser Program Annual Report—1979</i> , Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-79 (1980), p. 2-124.	
Beam Spatial Profile
Analysis
6-7	2. <i>Laser Program Annual Report—1979</i> , Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-79 (1980), p. 5-84.
3. <i>Laser Program Annual Report—1977</i> , Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-77 (1978), p. 2-36.	4. <i>Laser Program Annual Report—1976</i> , Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-76 (1977), p. 2-359.
Dante Temporal
Unfolds
6-11	5. K. G. Tirsell, H. N. Kornblum, and V. W. Slivinsky, "Time Resolved Sub-keV X-Ray Measurements Using Filtered X-Ray Diodes," Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-81478 (1979).
6. <i>Laser Program Annual Report—1979</i> , Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-79 (1980), p. 5-7.	7. J. W. Cooley, P. A. W. Lewis, and P. O. Welch, <i>IEEE Trans. Educ.</i> 12 , 27 (1969).
8. <i>Laser Program Annual Report—1979</i> , Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-79 (1980), p. 5-73.
Raman Spectrograph
Data Processing
6-18	9. <i>Laser Program Annual Report—1979</i> , Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-79 (1980), p. 3-20.
10. <i>Laser Program Annual Report—1979</i> , Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-79 (1980), p. 5-27.	11. <i>Laser Program Annual Report—1979</i> , Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-79 (1980), p. 5-71.
Crystal Spectrograph
Data Analysis
6-21	12. L. N. Koppel and J. D. Eckels, "High Resolution X-Ray Crystal Spectrographs," Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-79781 (1977).	13. <i>Laser Program Annual Report—1976</i> , Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-76 (1977), p. 2-359.
CCD Streak-Camera
Processing
6-22	14. <i>Laser Program Annual Report—1979</i> , Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-79 (1980), p. 5-17.	15. E. S. Bliss, D. R. Speck, and W. W. Simmons, "Direct Interferometric Measurements of Non-Linear Refractive Index Coefficient n_2 in Laser Materials," <i>Appl. Phys. Lett.</i> 25 , 12 (1974).
Novette Diagnostic-
Configuration Data
Base and Graphic
Presentation
6-28	16. <i>Laser Program Annual Report—1979</i> , Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-79 (1980), p. 5-68.	17. <i>Laser Program Annual Report—1978</i> , Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-78 (1979), p. 6-67.
Target Shot Books
and Archiving
6-32	18. <i>Laser Program Annual Report—1979</i> , Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-79 (1980), p. 5-91.	

Section 7 Laser Fusion Experiments and Analysis

Laser Fusion Experiments and Analysis

Contents

Introduction	7-1
Target-Interaction Experiments at 0.53 μm and 0.35 μm	7-2
Introduction	7-2
Experimental Conditions	7-3
Absorption	7-7
X-ray Conversion Efficiency	7-10
Suprathermal X Rays	7-16
Transport Experiments at 3ω	7-20
Analysis and Summary of Wavelength-Scaling Experiments and Comparisons with Simulations	7-22
Features of LASNEX Modeling	7-22
Wavelength-Scaling Trends	7-23
Absorption and Scattering	7-24
Multikilovolt X Rays and Suprathermal Electrons	7-26
Subkilovolt X-ray Emission	7-30
Role of Electron Conduction	7-33
Summary	7-33
Stimulated Raman Scattering in Large Plasmas	7-35
Introduction	7-35
Diagnostics	7-37
Shiva Experiments	7-37
Argus Green-Light Experiments	7-41
Comparison with Theory	7-41
Summary	7-44
Space-Time-Resolved X-ray Measurements from Accelerated Disk Targets	7-44
Gold-Disk Irradiation Experiments	7-44
Aluminum-Disk Irradiation Experiments: Self-Emission and X-ray Backlighting	7-48
Backlighter Characterization Experiments	7-53
Introduction	7-53
Backlighter Sources	7-54
Parameter Space	7-54
Experimental Setup	7-55
Conversion Efficiencies	7-55
Nature of Line Emissions	7-57
Temporal Behavior of X-ray Emission	7-59
Spatial Extent of X-ray Emission Region	7-60
Low-Energy X-ray Broadband Conversion Efficiency	7-61
Hard X-ray Emission	7-62
Light Emission Near $\omega/2$	7-63
Experiment Summary	7-63

Angular Distribution of High-Energy X Rays from Shiva-Irradiated Targets	7-65
Ultra-High-Pressure Laser-Driven Shocks in Gold	7-69
References	7-74

Laser Fusion Experiments and Analysis

Introduction

Theoretical analyses have predicted that submicrometre laser wavelengths have advantages for some of the physics aspects of laser-plasma interactions that are important to inertial-confinement fusion (ICF). Some recent experimental work at other laboratories¹⁻³ has begun to provide verification of these predictions.

In 1980, we used our Argus laser facility to examine the wavelength scaling of absorption and stimulated scattering processes, x-ray conversion efficiency, and hohlraum target performance. Although the Argus laser is capable of delivering 1 kJ in 1-ns pulses per 28-cm-diam beam at 1.06 μm , we used only ~ 100 J in one beam because of the limited aperture (9 cm) of available frequency-conversion crystals. The frequency-doubled (2ω) and frequency-tripled (3ω) experiments were conducted with ≤ 30 J of 0.53- μm or 0.35- μm laser energy on target.

The data obtained on disk targets in this experimental series continue to confirm that increased absorption and a reduced energy fraction and temperature of suprathermal electrons are obtained for shorter laser wavelengths. These experiments also showed an increased efficiency for converting the shorter-wavelength laser light to x rays and further supported the theoretical predictions that shorter laser wavelengths are more favorable for laser-driven ICF. The description and results of our wavelength-scaling experiments are the subject of the first portion of this section.

Our major efforts in the Shiva target-experiments program have been directed toward

- Achieving and diagnosing high density in the deuterium-tritium (D-T) fuel ($>100 \times$ liquid D-T density).
- Understanding the conditions of laser-irradiated targets necessary to achieve high fuel density.
- Scaling to Nova ignition and high-gain (>100) reactor target conditions.

Fuel densities of $\sim 100 \times$ liquid D-T density were obtained and diagnosed in 1979 and 1980 by using radiation-driven fuel capsules. The fuel density was measured by neutron activation of Si, which was used as a diagnostic material in the target structure. This measurement technique has been used for many different target types, some of which were directly irradiated. On the latter experiments, several other diagnostic methods were also used to verify the density of the compressed fuel. Measurements of the areal density of the Si diagnostic material, $(\rho\Delta r)_{\text{Si}}$, are plotted in Fig. 7-1 against the peak fuel density. These data are our evidence for having achieved "100X."

Although our major thrust on Shiva has been the understanding and development of laser-driven hohlraum targets, we also have investigated the phenomena associated with direct-illumination targets and, by using directly driven implosions, have validated our diagnostic techniques. In addition, we have used direct-illumination slab targets to provide the highest-pressure laboratory-produced shock waves in Al for the study of high-pressure, high-density, and high-temperature equations of state. Direct-illumination slab targets are also being studied as high-intensity auxiliary x-ray sources for x-ray backlighting in studies of pusher dynamics and implosions. We are also continuing our studies of the spatial generation, transport, and isotropy of suprathermal electrons.

Authors: H. G. Ahlstrom and J. H. Nuckolls

Target-Interaction Experiments at 0.53 μm and 0.35 μm

Introduction

During 1980, we began an experimental program to examine the effects of laser wavelength on laser-plasma interaction processes that are basic to laser fusion. Although systematic wavelength-scaling experiments have only recently been initiated at several laboratories,⁴ many phenomena relevant to laser fusion have long been predicted to depend strongly on wavelength, particularly at wavelengths less than 1.0 μm . These phenomena include absorption, stimulated scattering, suprathermal electron production, electron transport, and x-ray conversion efficiency.⁵

The primary goals of this part of the LLNL program are to measure the laser-light absorption of high-Z and low-Z plasmas (where Z = atomic number) and the partition of absorbed energy among the thermal and suprathermal electron populations as a function of both laser intensity and laser wavelength. Collisional absorption (inverse bremsstrahlung) leads to efficient heating of a thermal-electron population, and the absorbed energy is effectively converted into thermal x-rays by collisional coupling to high-Z ions.⁶

Collective phenomena (e.g., resonance absorption,⁷ two-plasmon decay,⁸ and stimulated Raman scattering⁹) produce suprathermal electrons, which are deleterious to electron-driven implosion systems because they cause fuel preheat and poor momentum coupling to the imploding

shell. Therefore, another design goal of our wavelength-scaling experiments is to observe whether suprathermal-electron production is reduced with decreasing laser wavelength, as theoretically predicted.⁵

For this wavelength-scaling program, we are using our multiwavelength, two-beam Argus laser facility, in which we employ nonlinear potassium dihydrogen phosphate (KDP) crystals to convert the frequency of one of the beams to both the second harmonic (2ω) and third harmonic (3ω) of its fundamental (1ω) 1.06- μm output. When completed, the program will have included experiments at all three of these wavelengths (1.06, 0.53, and 0.35 μm). Details of the facility configuration and a discussion of the efficiency of large-aperture harmonic conversion can be found in "Operations Summary," "Target Experiments—532 nm," "Target Experiments—355 nm," and "Frequency Conversion," all in Section 2.

At the close of 1980, the 2ω experiments had been completed, the 3ω experiments were near completion (expected in mid-January 1981), and the 1ω comparative experiments were scheduled for early 1981. In the following article, we discuss the irradiation conditions used in the 2ω and 3ω experiments and our attempt to both diagnose and make similar the experimental conditions at the different wavelengths. That article is followed by a series of articles discussing absorption results, scattering, thermal x-ray conversion efficiency, suprathermal x-ray measurements, and a summary of our experimental results compared with LASNEX computer simulations. In the latter article, the comparisons will concentrate on the 2ω results since the 1ω and 3ω experiments have not yet been completed.

In addition to the articles cited above, other articles on short-wavelength laser-plasma interaction experiments can be found later in this section. In "Backlighter Characterization Experiments," we discuss the results of a limited number of experiments conducted to observe the effect of laser wavelength on the production of line radiation from intermediate- and high-Z plasmas. In "Transport Experiments at 3ω ," we summarize a layered-disk experiment designed to examine electron transport at 3ω . No analogous 2ω transport experiments were conducted, although comparative 1ω transport experiments are planned for 1981.

Author: E. M. Campbell

Major Contributors: R. E. Turner, F. Ze, V. C. Rupert, K. R. Manes, W. C. Mead, C. E. Max, and K. G. Estabrook

Experimental Conditions

Our choices of the target-irradiation conditions for the wavelength-scaling experiments were dictated by both operational and physics considerations. Irradiation conditions were selected so that experiments at 1ω , 2ω , and 3ω could be performed under conditions as nearly identical as possible. As described in "Argus Operations" in Section 2, the limited size of the nonlinear KDP crystals, coupled with the damage susceptibility of thin-film dielectric coatings, restricted the incident 2ω and 3ω laser energy to approximately 30 J at pulse lengths on the order of 500 to 700 ps (FWHM). In addition, threshold detection levels of many of the diagnostics required the energy on target to be greater than 3 J. In Table 7-1, we summarize the operational constraints imposed by the experimental facility.

In the experiments, we were interested in the irradiation conditions that will be encountered in the design of advanced targets (i.e., those targets designed to achieve high fuel density with subsequent ignition). Such targets will have dimensions on the order of 1000 μm and will be irradiated with laser pulses longer than 1 ns.¹⁰ At a given wavelength, the intensity window of interest is determined by both hydrodynamic and plasma-instability considerations.¹¹

Focusing optics: f/2.2
Linearly polarized
 E_{laser} : 3 to 30 J
Pulse width: 500 to 700 ps

Table 7-1. Laser operating conditions at 2ω and 3ω .

The lowest useful intensity is associated with the high-radial-convergence, large-aspect-ratio (target radius/target-wall thickness) implosions that are necessary to achieve thermonuclear conditions in the fuel with low ablation pressure.¹¹ Hydrodynamic calculations indicate this lower-bound intensity to be on the order of 3×10^{13} W/cm² (see Ref. 12). The high-intensity limit (at a fixed wavelength) is determined by the onset of plasma instabilities that can lead to poor absorption and hydrodynamic coupling, to preheat, and to degradation of implosion symmetry.¹³

Given the conditions described above, we designed the experiments so that we could study the interaction physics associated with large-volume irradiations at moderate values of $I\lambda^2$. Although the limited laser energy and power available at the different wavelengths (~ 30 J, ~ 60 GW) restrict the scope of the experiments, it is still possible, using the existing facility, to begin exploring wavelength scaling of the interaction and coupling physics that occur in highly collisional, moderate-scale-length plasmas.

Our choice of irradiation conditions, based on the above arguments, is shown in Table 7-2. In the majority of our experiments, we maintained the laser pulse width between 500 and 700 ps (FWHM). We did not increase the pulse width because the plasma scale length, which was not directly measured, was expected to be limited by two-dimensional expansion. Also, for pulses in excess of 900 ps, we would have had to use pulse stacking.

To achieve moderate intensities (i.e., $3 \times 10^{13} \lesssim I \lesssim 3 \times 10^{14}$ W/cm²), we illuminated the target in the intermediate field of the effective f/2.2 focusing lens with spot sizes on the order of ~ 150 μm in diameter (a

Intensity (W/cm ²)	Spot diameter (μm)	Laser energy (J)
$\sim 3 \times 10^{13}$	150	3 to 4
$\sim 3 \times 10^{13}$	430	25
$\sim 3 \times 10^{14}$	150	25 to 30
$\sim 3 \times 10^{14}$	80	10 to 12
$\sim 10^{15}$	80	30 to 35
$> 3 \times 10^{15}$	20 to 30	30

Table 7-2. Irradiation conditions chosen.

Target-Interaction Experiments at 0.53 μm and 0.35 μm

Fig. 7-2. Temporal dependence of 1ω and 2ω laser light.

circle of this diameter contains $\lesssim 95\%$ of the beam energy). On selected experiments, the laser energy and the spot diameter were increased to 25 J and $430\ \mu\text{m}$, respectively, to achieve peak intensities of $\lesssim 3 \times 10^{13}\ \text{W}/\text{cm}^2$. To obtain intensities on the order of

$10^{15}\ \text{W}/\text{cm}^2$, we were forced to reduce the beam diameter to $\sim 80\ \mu\text{m}$. On several shots, to produce the highest average intensity, we placed the targets near the far field of the lens, where the minimum spot diameters were on the order of 20 to $30\ \mu\text{m}$ (with both

Fig. 7-3. Temporal dependence of 1ω and 3ω laser light.▼

2ω and 3ω). These experiments, in particular, are compromised by severe beam-intensity modulations and by two-dimensional effects (lateral transport and plasma-flow divergence).

During these experiments, we diagnosed the target-irradiation conditions as accurately as possible. The laser and diagnostic layout that was used is described in "Argus Operations" in Section 2. A calorimeter measured the incident laser energy impinging on the target from the south Argus beam at the harmonic wavelength, and streak cameras recorded the temporal shape of both the $1.06\text{-}\mu\text{m}$ pulse and the harmonic output. Figure 7-2 shows the temporal shapes for the 1ω and 2ω pulses, and Fig. 7-3 shows the temporal shapes for the 1ω and 3ω pulses.

The laser-energy distribution at the target plane was measured using the transmitted-beam multiple-image camera (TBMIC).

This camera images the target plane with an $f/2.2$ lens mounted on the opposing (north) side of the vacuum chamber. By firing the laser with the target removed, but after the focusing has been set, we recorded an accurate image of the laser-energy pattern in the target plane. Figures 7-4(a) and 7-5(a) show examples of the 2ω and 3ω beams, respectively, for an irradiation of $\sim 3 \times 10^{13}\text{ W/cm}^2$; the image plane is approximately $300\ \mu\text{m}$ from best focus. Astigmatism in the 2ω image is apparent in Fig. 7-4(a). Experiments performed during system setup and subsequent target experiments showed that this astigmatism was not an artifact of

Fig. 7-4. Spot size and energy-weighted intensity distribution with 2ω laser light.

Fig. 7-5. Spot size and energy-weighted intensity distribution with 3ω laser light.

the imaging system. We found these patterns to be quite reproducible from shot to shot for the same focusing geometry, provided care was taken to obtain good exposures on the film. Furthermore, the relative energy distribution deduced from a low-power shot (using only laser preamplifiers) was the same as that obtained from a full-energy shot for the same focusing geometry. This is not surprising, since we were operating Argus far below its design power. (There were no nonlinear beam-propagation effects in the laser glass, so the beam quality at the doubling crystal did not vary appreciably with laser power.) The distribution we see in the target plane is primarily due to intensity-independent aberrations and to diffraction.

Fig. 7-6. Fraction of the incident energy at intensity I or less.

Table 7-3. Diagnostics used for experiments.▼

Absorption
Energy balance, employing laser calorimeter and box calorimeter
Scattered light
Brillouin backscattered light (SBS)
High-dispersion Czerny-Turner spectrometer coupled to optical multichannel analyzer and streak camera
Raman-scattered light (SRS)
Schottky diodes coupled with narrow-band (12.5-nm) interference filters
Low-energy x rays
X-ray yield
3 multichannel Dante systems
2 flat calorimeters
X-ray temporal response
Soft x-ray streak camera (3 channels)
Suprathermal x rays
4-channel spectrometer (24 keV, 46 keV, 70 keV, $h\nu > 70 \text{ keV}$)
8-channel spectrometer (high channels at 24 keV, 46 keV, 70 keV)
X-ray imaging
2 multichannel zone plate cameras
1 Kirkpatrick-Baez x-ray microscope (4 channels)
Pinhole camera (4 channels)
X-ray spectroscopy
Crystal spectrometer
Grazing-incidence spectrometer

It should be noted that, since these data are recorded by a time-integrating camera, what is actually measured is the energy density. However, we see no change in the distribution for higher or lower laser powers, so we feel justified in dividing the energy density by the laser pulse width to obtain an average intensity.

A TBMIC photograph of the low-power beam was obtained immediately before each target shot. These images were then digitized and processed using the code BEAM ANL (see "Beam Profile Analysis" in Section 6) to produce an energy-weighted intensity-distribution function, $f(I)$, as shown in Figs. 7-4(b) and 7-5(b). The nominal intensity for these shots was $3 \times 10^{13} \text{ W/cm}^2$. The area under the curve between any two intensities, I_1 and I_2 , is equal to the fraction of the incident energy between these intensities. Figure 7-6 shows a plot of

$$\int_0^I f(I') dI' \quad (1)$$

(i.e., the fraction of the energy that arrives on target having an intensity between zero and I) using the data from Fig. 7-4. The examples shown in Figs. 7-4, 7-5, and 7-6 illustrate the inadequacy of characterizing a laser irradiation by a single-intensity value. When considering intensity-dependent effects, such as the generation of suprathermal electrons, the entire distribution of intensities must be taken into consideration.

The targets used in the experiments were simple disks, typically 600 μm in diameter and 25 μm thick. The diameter was large enough to ensure that the laser spot would not be near an edge but small enough to be easily aligned and focused in the TBMIC. The thickness was great enough to guarantee that the laser would not burn through the disk during the laser pulse.

We used gold targets for most measurements of radiation-conversion efficiency, but we also used lower-Z materials—Ti, Be, and CH (polyethylene)—to facilitate comparison with theoretical results and with computer simulations.

A wide variety of diagnostics was employed in the experiments. The instruments, their location, and the types of measurement are shown in Table 7-3 and in Fig. 7-7. Although the Argus target chamber

Fig. 7-7. Locations of the major x-ray measuring diagnostics on the Argus target chamber.

is cylindrical, it is represented in Fig. 7-7 as a sphere to emphasize the coordinates of the diagnostics. The diagnostics will be discussed more fully in the following articles.

Authors: R. E. Turner and E. M. Campbell

Major Contributors: F. Ze and V. C. Rupert

Absorption

In our 1979 Annual Report,¹⁴ we presented early results of our 2ω absorption experiments. These experiments were made primarily with high-Z plasmas (Au disks) at a peak intensity of 2 to $4 \times 10^{14}\ \text{W}/\text{cm}^2$. In 1980, we extended these experiments over a range of incident intensities from $\sim 3 \times 10^{13}\ \text{W}/\text{cm}^2$ to in excess of $10^{15}\ \text{W}/\text{cm}^2$ at laser wavelengths of $0.53\ \mu\text{m}$ and $0.35\ \mu\text{m}$ (2ω and 3ω , respectively). In addition to Au, the targets included low-Z (Be and CH) microdisks.

We inferred absorption measurements by energy balance, using a target-enclosing box calorimeter to measure scattered light¹⁵ in conjunction with incident, transmission, and backreflected laser calorimeters. The combination of the box calorimeter and focusing and transmission $f/2$ optics covered 98% of 4π sr about the target. To allow for complete coverage in the backscatter direction, we slightly reduced the defining hard aperture of the image-relayed laser¹⁶ so that the $f/2$ focusing lens had an effective f-number of $f/2.2$. This enabled us to accurately and reliably align the box calorimeter, which had an $f/2$ aperture in the south panel (through which the laser was injected), while avoiding an annular region of undetected scattered light between the box calorimeter and the collection cone of the focusing lens. Plasma and x-ray energy ($h\nu < 10\ \text{keV}$) were prevented from reaching the light absorber of the calorimeter (NG-1 for 2ω and GG-19 for 3ω) by a WG-280 shield.

To measure the absorption of various low- and high-Z materials as a function of the peak intensity of $0.53\text{-}\mu\text{m}$ light, we irradiated microdisks of the materials at normal

Target-Interaction Experiments at 0.53 μm and 0.35 μm

Fig. 7-8. Absorption results at 2ω .

Fig. 7-9. Backscatter fraction vs intensity.

incidence; the results are shown in Fig. 7-8. For intensities below 10^{15} W/cm^2 , we obtained the data by using beam diameters of ~ 80 to $150 \mu\text{m}$ at the target; for intensities above 10^{15} W/cm^2 , we placed the target in the far field of the lens to obtain a spot size of $\sim 30 \mu\text{m}$. At a nominal intensity of $\sim 3 \times 10^{14} \text{ W/cm}^2$, we observed no difference in absorption as we reduced the beam diameter from 150 to $80 \mu\text{m}$.

As discussed in "Beam Profile Analysis," in Section 6, and in "Experimental Conditions," in this section, the nonuniform spatial distribution of energy in the laser beam results in a spread of intensities at the target. The intensities used in plotting Fig. 7-8 are mean values, obtained with the code BEAM ANL, and the limits for each experiment represent the range covering 20 to 80% of the incident energy.

The data shown in Fig. 7-8 exhibit trends that are consistent with an increased role of collisional absorption, i.e., absorption increasing with Z and decreasing with intensity. However, some of the reduction in absorption at the highest intensities may be due to stimulated Brillouin scattering (see "Analysis and Summary of Wavelength-Scaling Experiments and Comparisons with Simulations" in this section), to poor beam

Fig. 7-10. Preliminary absorption results at 3ω .

quality, and to enhanced two-dimensional effects due to the small laser spot.

Also shown in Fig. 7-8 are the results obtained by the École Polytechnique Group using both 2-ns and 80-ps pulses on polymer targets.¹⁷ Their experiments are in reasonable agreement with the results presented here. Pulse-length differences are difficult to compare because of the small laser spots (the École Polytechnique Group reports that their laser spots are $50 \pm 15 \mu\text{m}$ in diameter) and because, inevitably, two-dimensional effects, particularly for the long-pulse experiments, complicate interpretation of their data. Furthermore, their polymer targets contained moderate-Z constituents that could have affected the inverse-bremsstrahlung contribution to total absorption.

In Fig. 7-9, we present the fraction of the 2ω light that was scattered back into the focusing optics as a function of Z and intensity for normal-incidence irradiation. The back reflection increases with intensity, as expected. It is not possible, however, to decipher the relative contributions to total backscattered energy of stimulated scattering from the underdense plasma and of reflection from the critical surface.

One interesting observation is the difference in the backscatter fraction between CH and Be targets. The total absorptions of the two plasmas were very similar (Fig. 7-8), although much less of the scattered light from Be was collected by the focusing optics.

We show the preliminary results of our 3ω absorption experiments in Fig. 7-10. The plot displays the absorbed-energy fraction for Au and Be microdisks as a function of peak laser intensity. The disks were irradiated at an angle of 30° with respect to the laser-beam axis, and the irradiation conditions were similar to those described in "Experimental Conditions" in this section. Additional experiments, described below, showed no angular dependence in the absorption, at least up to incidence angles of 30° , so the results shown in Fig. 7-10 can be compared with those shown in Fig. 7-8. It may be seen that the absorption at 3ω is greater than that obtained at 2ω , particularly for intensities greater than $\sim 3 \times 10^{14} \text{ W/cm}^2$, for both high- and low-Z plasmas. In addition, the absorption of Au remains

Fig. 7-11. Absorption vs angle of incidence at 3ω .

nearly constant over the intensity range spanned in the experiments.

In Fig. 7-11, we show the absorption fraction for both Au and Be plotted against the incident angle, θ_{inc} , for a fixed peak intensity of $\sim 10^{15} \text{ W/cm}^2$. The experiments were done with p polarization, although no polarization dependence was expected for these irradiation conditions. For Au, the absorption is seen to be weakly dependent on angle of incidence, decreasing to 76% at a 60° incidence. The Be (low-Z) is more angle dependent, with the absorption decreasing by more than a factor of 2 from the normal-incidence result as the beam-to-target normal angle is increased to 60° .

In addition to the high target absorption, little direct backscatter was observed over the intensity range of these experiments. For example, at a peak intensity of 10^{15} W/cm^2 , the backscattered light collected by the f/2 focusing lens amounted to only 1.5% of the incident energy for Au and to 5% for Be, both at normal incidence.

We should again stress the preliminary nature of the 3ω absorption results. Uncertainties in the calibration of the instruments are represented by the error bars in Figs. 7-10 and 7-11. We are now assessing another area of uncertainty, the degree to which the box-calorimeter measurements may have been affected by the accumulated deposits of target debris on the internal plasma shield.

Authors: F. Ze and E. M. Campbell

Major Contributors: V. C. Rupert and R. E. Turner

X-ray Conversion Efficiency

Introduction. One of our main goals in the experiments on laser-wavelength scaling is to obtain a comprehensive data base on soft (sub-keV) x-ray emission from laser-irradiated targets. During 1980, we used the Argus beam that had been converted to second-harmonic wavelength ($\lambda = 530 \text{ nm}$), along with arrays of filtered XRD Dante detectors, to continue our measurements of sub-keV x rays.^{18,19} Table 7-4 lists the nominal 2ω experimental conditions that we

Table 7-4. Nominal 2ω experimental conditions.

Laser wavelength	$\lambda = 0.53 \mu\text{m}$	
Targets	Au, Be, Ti	
Target dimensions	600 μm in diameter 2 to 14 μm thick	
Focusing optics	$f/2$	
Pulse width (FWHM)	600 to 700 ps	
Beam modulation (peak/average)	3:1	

Intensity (W/cm^2)	Incident laser energy (J)	Spot size (μm)
3×10^{13}	5	180
	25	450
3×10^{14}	25	180
	12	(80) ^a
2×10^{15}	32	80
$3 \text{ to } 5 \times 10^{15}$	20	30

^aWe have only limited data for these particular experimental conditions.

used. In this article, we discuss the absolute measurements of soft x-ray spectra emitted from disk targets irradiated by second-harmonic beams with energies ranging from 3 to 40 J and with a pulse width of 600 ps FWHM.²⁰ The nominal test conditions are described in "Experimental Conditions," earlier in this section. Similar x-ray emission experiments are in progress with third-harmonic irradiation; however, because these experiments are not yet complete, we will discuss only the results obtained at the second harmonic (2ω).

We have obtained the most accurate values of x-ray conversion efficiency to date by measuring the dependence of time-integrated x-ray emission spectra on both laser intensity and emission angle. To obtain these values, we used several laser irradiation intensities in the range from 10^{13} to $10^{15} \text{ W}/\text{cm}^2$, and we measured the angular distribution of x-ray energy, which was integrated from 0.1 to 1.8 keV.

Experimental Configuration. The system of detectors consisted of two five-channel arrays, designated Dante-L and Dante-W; an eight-channel Dante T system; and two flat-response detectors (FF and FT). For comparison purposes, one of the flat-response detectors, FT, was located for the most part on the Dante-T system. Figure

Fig. 7-12. Experimental configuration used for measuring x-ray conversion efficiency.

Target rotation angle, θ	Dante system ^a	Viewing angle with respect to normal, β
+10°	L W FF T, FT	38.5° Not used 45° 80°
+15°	L W FF T, FT	36° Not used 40° 75°
+30°	L W FF T, FT	30° Not used 25° 60°
-30°	L W FF T	69° 69° 86° Not used

^aL, W, and T are designated names of Dante Systems, FF is a flat-response calorimeter, and FT is another flat-response calorimeter that was usually mounted on Dante T.

Laser $2\omega_0$ (0.53 μm)
3 to 40 J, 600 ps FWHM
P-polarized, $f/2.2$
Spot size, 30 to 150 μm diameter

7-12 shows the experimental configuration. The viewing angle, β , for each system is defined as the angle between the target normal and the system axis. As summarized in Fig. 7-12, we obtained a variety of viewing angles by rotating the targets through moderate angles, from -30° to $+30^\circ$, about the normally incident laser direction.

Most of the targets were gold disks, nominally 600 μm in diameter and 25 μm thick; however, a few disks of titanium and beryllium were also tested. Laser intensities ranging from $\sim 3 \times 10^{13}$ to 3 to 5×10^{15} W/cm^2 were obtained by varying both the laser energy and the irradiation spot size.

Sub-keV Spectra from Gold Disks. The sub-keV x-ray emission spectra that we measured at several viewing angles and at different laser intensities are shown in Figs. 7-13 through 7-15. Spectral points for each shot were determined by using the total charge measured for each channel, the channel response functions, and an iterative unfolding code that converges a trial spectrum to a best-fit spectrum.¹⁸ Each spectral point is located at the median channel energy, which is determined by folding the best-fit spectrum with the channel response, integrating, and locating the 50% rise of the running integral. The spectra in Figs. 7-13 through 7-15 were obtained by first normalizing the measured spectrum from each shot to incident laser energy and then averaging the results from two to four shots. These spectra are expressed in units of $\text{J}/\text{keV} \cdot \text{sr} \cdot J_{\text{inc}}$, where J is the x-ray energy and J_{inc} is the incident laser energy.

At the nominal intensity of 3×10^{13} W/cm^2 , with a spot size of 180 μm , both the amplitudes and shapes of the spectra are relatively insensitive to the viewing angle. We note that spectral intensities drop only a little at large values of β . We suggest that the peaks in some of the spectra at ~ 0.5 keV (Fig. 7-13) are due to oxygen K-line contamination; the Dante-T system, unlike the five-channel systems, has an extra channel at the appropriate energy for detection of this contamination.

At an intensity of 3×10^{14} W/cm^2 , and with a 180- μm spot, the slopes of the spectra below 0.8 keV decrease with increasing (Fig. 7-14). Above 0.8 keV, the spectral shapes are similar, but the amplitudes decrease for viewing angles greater than 70° .

At intensities in the range from 1 to 2×10^{15} W/cm^2 , and above, the spectra become much more sensitive to β . In general, we note that the slopes of the spectra decrease even more significantly with increasing β (Fig. 7-15).

At a given viewing angle, β , the x-ray spectra can be compared for different laser intensities. An example is shown in Fig. 7-16 for the case $\beta = 30^\circ$. We note that the spectral amplitude is highest at 3×10^{14}

Fig. 7-13. Dante low-energy x-ray spectra of Au-disk targets at 3×10^{13} W/cm^2 .

Fig. 7-14. Dante low-energy x-ray spectra of Au-disk targets at 3×10^{14} W/cm^2 .

W/cm^2 , while the spectrum at 3×10^{13} W/cm^2 drops much more steeply with increasing energy.

Angular Dependence as a Function of X-ray Channel Energy. The angular dependence of individual Dante channels is shown in Figs. 7-17 through 7-19 for conditions of 3×10^{13} W/cm^2 with a 180- μm spot, 3×10^{14} W/cm^2 with a 180- μm spot, and 2×10^{15} W/cm^2 with an 80- μm spot, respectively. For the analysis of angular dependence, we used

Fig. 7-15. Dante low-energy x-ray spectra of Au-disk targets at 2×10^{15} W/cm^2 .

Fig. 7-16. Dante low-energy x-ray spectra for various laser intensities at $\beta = 30^\circ$.

channels 1 through 5, common to all Dante systems, which had median energies at 300, 450, 700, 820, and 1100 eV, respectively.

At 3×10^{13} W/cm^2 (Fig. 7-17), the spectral intensity of each of the channels at 700 eV and below (channels 1 through 3) increases with $\cos \beta$, with the increase becoming more gradual for the higher-energy channels, while the spectral intensities of the two channels above 700 eV (channels 4 and 5) are practically flat. Put another way, the radiation patterns for the channels above 700 eV would be semicircular on a polar plot, whereas, with decreasing energy, the radiation patterns for the channels at 700 eV and below would be increasingly forward peaked.

At 3×10^{14} W/cm^2 (Fig. 7-18), the spectral intensities of channels 1 and 2 increase the most with increasing $\cos \beta$, those of channels 3 and 4 increase less rapidly, while that of channel 5 is practically flat. Note that, for channels 1 through 4, the spectral intensities below 1 keV are bunched quite closely.

At 2×10^{15} W/cm^2 (Fig. 7-19), the spectral intensities of channels 1 through 3 increase with increasing $\cos \beta$, while the intensities of channels 4 and 5 are more or less insensitive to $\cos \beta$.

Titanium, Gold, and Beryllium Spectra.

Titanium spectra all show a prominent peak in the 600- to 900-eV region due to L-line emission. Figure 7-20 shows a Ti spectrum for a 2ω wavelength, an intensity of 3×10^{14} W/cm^2 , and a 60° viewing angle. Also shown in Fig. 7-20 is a spectrum obtained previously with 1ω irradiation under somewhat different conditions (60° angle, 3 to 5×10^{14} W/cm^2 intensity, 450 to 500- μm spot, and 900-ps FWHM pulse length).²¹ Because of the sharp peak at ~ 690 eV, we were able to obtain a value of $Z = 16 \pm 1$ for the dominant charge state from the measured 1ω spectrum, in agreement with code calculations.²¹

For the Ti spectrum obtained with 2ω irradiation, we note that the emission level of x rays is increased by a factor of 2 or more in comparison with 1ω irradiation, partly due to the increased light absorption at the shorter wavelength. Furthermore, for the shorter-wavelength irradiation, the group of L-lines has a significantly broader peak, from 540 to 700 eV, making it much more difficult to accurately obtain a dominant

charge state. Instead, we can only estimate that the average ionic charge state is substantially lower than 16 and that the variation in Z over the FWHM of the x-ray emission region is broader than in the 1ω case.

Examples of gold and beryllium spectral emissions are shown in Figs. 7-21 and 7-22, respectively, for both 2ω and 1ω irradiation. Beryllium disks irradiated with 2ω light yield x-ray spectra that decay almost exponentially as energy increases. Despite the rather different irradiation conditions, it is reasonable to conclude that 2ω irradiation increases the low-energy x-ray emission for both Au and Ti, as compared with 1ω irradiation, but that the increase for Be is not significant.

A comparison of 2ω irradiation data for Be and Au disks at $3 \times 10^{14} \text{ W/cm}^2$ and at two viewing angles (30° and 60°) is shown in Fig. 7-23. Note the large differences in spectral intensities between the two different target materials and the basic differences in spectral shape.

Angular Dependence of Integrated X-ray Energy for Gold Disks. Figures 7-24 through 7-27 show the angular distribution of x-ray energy, integrated between 0.1 and 1.8 keV, for gold targets at various irradiation intensities. Most of the data points have been obtained by integrating the measured Dante spectra and averaging the results from two or more shots, while the rest of the data points are from flat-response detectors. The error bars in Figs. 7-24 through 7-27 represent shot-to-shot fluctuations in the data and do not include any systematic errors that are independent of angle, e.g., the 20 to 25% uncertainty in detector responses.

At $3 \times 10^{13} \text{ W/cm}^2$, the normalized Dante integral for each spot size decreases very slowly from 0 to 60° , then drops off faster when β exceeds 60° , as shown in Fig. 7-24. For viewing angles greater than 70° , the angular distributions are similar for the two spot sizes (180 and $450 \mu\text{m}$). Below 70° (i.e., above $\cos \beta \approx 0.4$), the integrated x-ray emission for the case of the $180\text{-}\mu\text{m}$ spot is consistently lower.

At $3 \times 10^{14} \text{ W/cm}^2$, the normalized Dante integral has a distribution that varies more linearly with $\cos \beta$ (Fig. 7-25). At $2 \times 10^{15} \text{ W/cm}^2$, the normalized Dante integral drops gradually as β increases from 0 to 90° (Fig. 7-26). Note that the fluctuations in the data are rather significant in this case. The

Fig. 7-17. Angular dependence of individual Dante channels at $3 \times 10^{13} \text{ W/cm}^2$. ▲

Fig. 7-18. Angular dependence of individual Dante channels at $3 \times 10^{14} \text{ W/cm}^2$. ▼

Target-Interaction Experiments at 0.53 μm and 0.35 μm

relatively low emission at an intensity of $4 \times 10^{15} \text{ W/cm}^2$, shown in Fig. 7-27, is due both to an increase in intensity and to a decrease in laser spot size (to 30 μm).

Fig. 7-19. Angular $\blacktriangle$ dependence of individual Dante channels at $2 \times 10^{15} \text{ W/cm}^2$.

Fig. 7-23. Comparison of Au-disk and Be-disk spectra with 2ω irradiation at $3 \times 10^{14} \text{ W/cm}^2$ for $\beta = 30^\circ$ and 60° . $\blacktriangledown$

Fig. 7-20. Ti-disk $\blacktriangle$ spectra at $\beta = 60^\circ$.

Fig. 7-21. Au-disk x-ray spectra at $\beta = 60^\circ$. $\blacktriangledown$

Fig. 7-22. Be-disk x-ray spectra at $\beta = 60^\circ$. $\blacktriangledown$

X-ray Conversion Efficiency. Integrating the normalized Dante integrals over β and the azimuthal angle, we obtain the “uncorrected” conversion efficiency, $E_{\text{x ray}}/E_{\text{laser}}$. Dividing this value by the absorption efficiency, we obtain the conversion efficiency for the total x-ray energy from 0.1 to 1.8 keV. The results for 2ω irradiation of Au disks are plotted in Fig. 7-28. We should point out that, in all cases, the contribution to the total x-ray integral above 1.8 keV is negligible. Since the response of our lowest energy channel drops rapidly below 200 eV, we definitely have uncertainty in the lower energy region; consequently, we have not extrapolated the x-ray energy integral to zero. Comparing spectral shapes at various intensities, we note that, for gold at $3 \times 10^{13} \text{ W/cm}^2$, the spectrum drops more steeply with increasing x-ray energy; consequently, there may be a relatively greater contribution to the total integral from x rays with energies below 100 eV. This greater proportion of lower-energy x rays would tend to raise the conversion efficiency for the $3 \times 10^{13} \text{ W/cm}^2$ case relative to the other Au results, which would not be as significantly affected by low-energy contributions.

Titanium- and beryllium-disk data are not as extensive—and the angular distributions are not so well defined—as are the comparable data obtained from gold disks. We obtained Ti x-ray conversion-efficiency values of $27 \pm 8\%$ and $18 \pm 5\%$ for intensities

▲ Fig. 7-24. Angular distribution of the normalized Dante x-ray spectral integrals at $3 \times 10^{13} \text{ W/cm}^2$ for Au disks.

▲ Fig. 7-25. Angular distribution of the normalized Dante integrals at $3 \times 10^{14} \text{ W/cm}^2$ for Au disks.

▲ Fig. 7-26. Angular distribution of the normalized Dante integrals at $2 \times 10^{15} \text{ W/cm}^2$ for Au disks.

of 3×10^{14} and $2 \times 10^{15} \text{ W/cm}^2$, respectively, and a Be x-ray conversion-efficiency value of $1.5 \pm 0.2\%$ for an intensity of $3 \times 10^{14} \text{ W/cm}^2$, all at 2ω .

Discussion of Results. Gold x-ray conversion-efficiency values are found to be highest, nominally 54%, at an incident intensity of $3 \times 10^{14} \text{ W/cm}^2$ and to decrease with increasing intensity above about $5 \times 10^{14} \text{ W/cm}^2$. Our measurements at $3 \times 10^{13} \text{ W/cm}^2$ suggest that the conversion efficiency does not rise significantly as the intensity decreases below 10^{14} W/cm^2 . We definitely observe cooler spectra at the lower intensity; thus, with the present lower bound of 100 eV, an increasingly larger fraction of the total x-ray yield is not accounted for. The observed decreases in conversion efficiency with decreasing spot size are not enough to obscure the above conclusions.

We note from Figs. 7-13 through 7-15 that, with increasing intensity, the spectra tend to decrease more significantly at low energies as the viewing angle gets larger. We suggest that the "low-energy dip" of the soft x-ray spectra at large β and high laser intensity may be due to the presence of a cool, absorbing plasma surrounding the hot emitting region. Such a plasma could arise from lateral transport, the effects of which

are more important for the smallest laser spots at the highest intensities; alternatively, the plasma could arise from cavity formation caused by the increasing radiation pressure.²²

Authors: P. H. Y. Lee and K. G. Tirsell

Major Contributors: E. M. Campbell, F. Ze, and R. E. Turner

Suprathermal X Rays

We have measured x-ray fluences with photon energies between 5 and 70 keV that were produced by irradiating microdisks of various materials with second-harmonic (0.53- μm) and third-harmonic (0.35- μm) laser wavelengths. Irradiation energies varied from 3 to 35 J, incident intensities varied from 3×10^{13} to $3 \times 10^{15} \text{ W/cm}^2$, and laser pulse widths were nominally 600 to 700 ps. Further details concerning test conditions are given in "Experimental Conditions" earlier in this section.

Figure 7-29 shows the locations of the three different instruments that we used to obtain data on the suprathermal x-ray emissions. (Suprathermal x rays have energies typically greater than 10 to 20 keV.) The four-channel system was used primarily for shots with the microdisk targets at negative angles (counterclockwise rotation about the target stalk), so that the detectors viewed the laser-irradiated side of the target. The FFLEX^{23,24} detector was used primarily for positive or slightly negative target angles. The seven-channel system was used as a backup to FFLEX and was able to provide some duplicate coverage of FFLEX measurements for x-ray energies below 30 keV.

Because most of the shots produced relatively low x-ray fluences, the majority of the data we obtained from FFLEX came from the straight-through K-edge filter channels rather than from the less-sensitive filter/fluorescer channels. Although the four-channel system uses K-edge filter channels (Fig. 7-30) that are essentially

Fig. 7-27. Angular distribution of the normalized Dante integrals at $4 \times 10^{15} \text{ W/cm}^2$ for Au disks.

Fig. 7-28. X-ray conversion efficiency at 2ω irradiation for Au disks.

Target-Interaction Experiments at 0.53 μm and 0.35 μm

identical in spectral coverage to those of FFLEX, the four-channel system is about 20 times more sensitive because of its closer proximity to the target (67 cm vs 3 m). For some of the shots that produced a low x-ray fluence, the four-channel system was the only one of the three suprathreshold x-ray spectrometer systems that produced usable data.

The K-edge filter channels have response functions that produce well-defined energy bands in the region of the K-notch, but these channels also have significant response to higher energies; the filter/fluorescer channels greatly reduce this high-energy response. Fortunately, for rapidly falling spectra such as we have measured for most of the 2ω and 3ω target irradiations, the high-energy response caused no significant problem. The spectrum folded-response functions shown in Figs. 7-31 through 7-33 were generated by folding the response functions with a spectrum that was an average of the data obtained at 2ω with a laser intensity of $3 \times 10^{14} \text{ W/cm}^2$.

Figure 7-34 compares data obtained from FFLEX with data obtained from the four-channel system for 2ω irradiation of Au microdisks. For this particular shot, FFLEX viewed the target microdisk at 80° to the normal, while the four-channel system was at

65° to the normal. Figure 7-35 shows a similar comparison of FFLEX with the seven-channel system, where FFLEX was at

Fig. 7-29. Diagram of instrument locations.

Fig. 7-30. Arrangement of K-edge filter channel.

Fig. 7-31. FFLEX spectrum folded-response functions for 2ω and 3ω .

Fig. 7-32. Four-channel system spectrum folded-response functions for 2ω and 3ω , (cf. Fig. 7-33 opposite).

Fig. 7-35. Seven-channel system compared with FFLEX.▶

Fig. 7-34. Four-channel system compared with FFLEX.

40° to the normal and the seven-channel system was at about 80° to the normal. Error bars, which are representative of all our data, are shown on some of the data points.

Figure 7-36 shows variations in the fluence for gold disks for different laser-beam incident intensities at the 0.53- μm wavelength. The two data points at each intensity indicate the typical repeatability of the measurements; the variations probably are mostly dependent upon small variations in the incident laser beam (see "Experimental Conditions" earlier in this section). Figure 7-37 shows comparable results for the

Target-Interaction Experiments at 0.53 μm and 0.35 μm

Fig. 7-33. Seven-channel system spectrum folded-response functions for 2ω and 3ω .

Fig. 7-36. Dependence of 2ω x-ray fluence on laser-beam intensity. ▼

Fig. 7-37. Dependence of 3ω x-ray fluence on laser-beam intensity.

0.35- μm wavelength. The data in these two figures have been averaged, normalized, and combined to emphasize typical variations between 2ω and 3ω data, and the resultant data are discussed in "Analysis and Summary of Wavelength-Scaling Experiments and Comparisons with Simulations" in this section.

Author: B. Pruett

Major Contributors: H. N. Kornblum, S. S. Glaros, and V. W. Slivinsky

Transport Experiments at 3ω

Future target designs for Nova are dependent upon our knowledge of the physics of laser-plasma interactions that occur in long-scale-length collisional plasmas. Such an interaction regime can result from submicrometre irradiation with a long pulse and moderate intensity.

To date, much of the modeling of collisional absorption has been based on integrated experiments in which observables,

such as target absorption and x-ray emission, have been measured.²⁵ Interpreting these experimental observables in terms of phenomena, such as transport inhibition, is not conclusive because the majority of the measurements are integrated over space and time and are dependent on many interacting, nonlinear phenomena of the interaction physics. High-Z plasmas present additional complications due to temperature-dependent, nonlocal thermodynamic-equilibrium radiation transport.

To obtain more detailed and less ambiguous comparisons of carefully chosen experimental observables with simulation models of electron transport, we are conducting experiments with layered targets of moderate- and low-Z materials.²⁶⁻²⁹ The approach to clarifying the physics of energy transport by using a layered slab target is illustrated in Fig. 7-38, which shows a schematic of the density, temperature, and x-ray emission profiles of a laser-irradiated plasma. In Fig. 7-38, the electron density is denoted by n_e , the electron temperature by T_e , and the position of the critical density by n_{crit} . Laser energy is deposited in the plasma up to the critical surface and conducted inward to higher density, where the x-ray emission rate increases to a maximum. The flow of heat inward depends upon the characteristics of the heated-electron distribution and the effectiveness of electron conduction in the overdense region.

Our layered-disk experiments probe the region of maximum x-ray generation by replacing varying amounts of the absorption-transport-emitting region with a low-Z material. The choice of a low-Z material, such as Be, eliminates the difficulties associated with radiation transport. In the most common form of experiment, disks of moderate-Z target material (Al) are coated with several different thicknesses of low-Z material (Be) and are then irradiated. As the low-Z layer is thickened, the observed x-ray spectrum (continuum and line radiation) is altered from that characteristic of the substrate Z to that representative of the low-Z material.

Layered-target experiments have been performed at several laboratories.²⁶⁻²⁹ Experiments performed at NRL²⁶ and at LLNL²⁷ with short-pulse ($\tau_L \sim 100$ ps), high-intensity ($I \sim 10^{15}$ W/cm²) 1.06- μm

Fig. 7-38. Density, temperature, and x-ray emission profiles of laser-heated plasma.

irradiation imply a substantial reduction in electron heat transport. Yaakobi²⁸ observed similar results for longer-pulse ($\tau_L \sim 250$ ps), moderate-intensity ($I \sim 10^{14}$ W/cm²) 1.06- μm experiments. However, recent 3-ns, low-intensity ($I_L < 10^{14}$ W/cm²) experiments conducted at NRL²⁹ with 1.06- μm light have measured electron-energy transport depths that they interpret as being consistent with classical electron conduction.

We are now using layered-disk targets to extend this type of measurement to highly collisional laser-plasma interaction regimes, i.e., short-wavelength (0.35 μm) and moderate-intensity (3×10^{14} W/cm²). These experiments were still in progress at the end of 1980; thus, no results are presented in this article. However, we describe the experiment, including target design and diagnostic configuration.

The irradiation parameters are listed in Table 7-5. These parameters were chosen both to place the experimental conditions well into the regime of collisional absorption and to be within the capabilities of the Argus laser.

The target, shown schematically in Fig. 7-39, consists of a Be layer of variable thickness coated on an Al substrate. The majority of these targets are mounted on a titanium shield, which serves both to monitor lateral transport and to prevent energy from flowing around the edge and to the rear of the target. The target normals are at 30° with respect to the axis of the incident laser beam to provide adequate observation angles for the diagnostics.

The diagnostics that were employed for these experiments are listed in Table 7-6. The total sub-keV x-ray yield is determined by two multichannel x-ray spectrometer systems, Dante T and Dante L.³⁰ We have added a 2000- $\text{\AA}$ -thick Al L-edge filtered channel to the Dante T system to measure the energy yield below 100 eV. High-resolution (15-ps) temporal evolution of the sub-keV x rays is monitored by a three-channel (200, 500, and 700 eV) x-ray streak camera.³¹ The highest energy channel of this instrument responds to Ti L lines and is used to monitor lateral conduction. A spectrometer that uses potassium acid phthalate (KAP) and pentaerythritol tetracetate (PET) crystals to spectrally disperse the x rays is used to simultaneously

monitor both Al (axial transport) and Ti (lateral transport) line production. X-ray imaging is obtained with a four-channel Kirkpatrick-Baez microscope,³² which is occasionally supplemented by a pinhole camera. High-energy x-ray yields ($5 \text{ keV} \leq h\nu \leq 70 \text{ keV}$) were measured using two K-edge spectrometers (see "Suprathermal X Rays" in this section).

The x-ray diagnostics are supplemented by measurements of the time it takes the shock wave, which is induced by absorption of the laser energy, to transit the thickness of the target.³² An S-20 streak camera, which views the rear of the target, measures the arrival

Fig. 7-39. Layered target for transport experiments.

Irradiation	Conditions	◀ Table 7-5. Irradiation parameters.
Laser wavelength	0.35 μm	
Peak intensity	$2 \text{ to } 3 \times 10^{14} \text{ W/cm}^2$	
Laser energy	25 to 30 J	
Pulse width (FWHM)	~ 600 ps	
Irradiation dimension (diam)	$\sim 150 \mu\text{m}$	
Focus-lens f/No.	f/2.2	
Target orientation	30° (p polarization)	▼ Table 7-6. Diagnostics.

Instrument	Purpose	LOS ^a (deg)
Dante T (9 channels) x-ray yield	Low-energy	60
Dante L (5 channels)	Low-energy x-ray yield	30
Soft x-ray streak camera (3 channels)	Temporal characteristics of low-energy x rays	62.5
X-ray microscope (4 channels)	Two-dimensional x-ray image	69.3
Pinhole camera (4 channels)	Two-dimensional x-ray image	0 to 30
Crystal spectrometer	Al line radiation, Ti line radiation	62
Four-channel system	Hard x rays ($h\nu > 5 \text{ keV}$)	120
FFLEX (5 channels)	Hard x rays ($h\nu > 5 \text{ keV}$)	25
Optical streak camera	Shock-transit time	150

^aLine-of-sight of diagnostic with respect to target normal.

time of the shock wave by observing the onset of optical emission from the shock-heated material. To allow for accurate measurement of the shock velocity time, we ion-milled a channel, $4\text{ }\mu\text{m}$ deep and $45\text{ }\mu\text{m}$ wide, at the rear of each target. Preheating of the target by suprathermal electrons has been eliminated by the highly collisional thermal-electron interaction regime used in the experiments. The shock strengths inferred from these measurements will be valuable for evaluating two-dimensional effects (lateral transport), ablation pressures, and the coupling efficiency of laser energy into the overdense plasma.

Authors: E. M. Campbell and W. C. Mead

Major Contributors: C. W. Hatcher, N. C. Holmes, R. J. Trainor, F. Ze, and R. E. Turner

Analysis and Summary of Wavelength-Scaling Experiments and Comparisons with Simulations

In this article, we discuss the results of initial wavelength-scaling experiments performed with the Argus laser. (Details of the specific diagnostics and experimental measurements are discussed in preceding articles in this section.) The analyses of these experiments must necessarily be somewhat tentative since, at the time of this writing, the $0.35\text{-}\mu\text{m}$ experiments were still in progress, the $1.06\text{-}\mu\text{m}$ experiments had not yet been started, and we were still developing and testing our physics and calculational models. Consequently, we will discuss primarily the $0.53\text{-}\mu\text{m}$ experiments and compare the experimental results in some detail with the results of LASNEX modeling.

Where appropriate, we will call on both preliminary $0.35\text{-}\mu\text{m}$ results and previous $1.06\text{-}\mu\text{m}$ experiments and calculations, the latter of which have somewhat different irradiation parameters. A comparison of

these two bodies of data will enable us to see the more evident wavelength-scaling trends, although detailed quantitative conclusions must await completion of the entire set of scaling experiments. The results to date are very interesting; we have found considerable support for theoretical predictions and have defined several areas where improved understanding is needed.

Features of LASNEX Modeling

Extensive simulations of these wavelength-scaling experiments have been performed using the LASNEX code.³³ The LASNEX modeling used for the calculations presented here is largely consistent with that employed for many previous simulations of experiments.³⁴⁻³⁶ We mention here some of the key features of the LASNEX modeling and discuss their importance to the present calculations.

Most model testing has been performed in one-dimensional spherical geometry, using a radius of curvature equal to twice the diameter of the laser spot. These calculations, which allow for plasma flow divergence, have been compared in detail with several full, two-dimensional simulations. We find that pseudo two-dimensional calculations are quite adequate for most of the plasma characteristics and diagnostic properties of interest in these experiments.

The absorption model includes classical absorption due to inverse bremsstrahlung, collective absorption via resonance absorption, and, most recently, a model for stimulated Brillouin backscatter. The ponderomotive force is included, but is found to be negligible compared with thermal-plasma pressures resulting from localized energy deposition and ablation near the critical surface.

The inverse-bremsstrahlung modeling used for calculations presented in this work uses the classical absorption cross section. We did not explicitly include the nonlinear opacity reduction reported by Langdon.³⁷ We believe that other absorption mechanisms that are also neglected in the modeling, such as short-wavelength ion turbulence,³⁸ could approximately

compensate for the moderate nonlinear reduction of inverse bremsstrahlung calculated for these plasmas. In addition, the strong dependence of the inverse-bremsstrahlung opacity on the density, temperature, and ionization state of the plasma leads to significant quantitative uncertainty in the absorption model, which can be as large as the omitted nonlinear effects.

The model for resonance absorption^{39,40} is very simple. A dump-fraction is set to deposit a specified fraction of the light reaching the critical-density surface into a suprathermal electron distribution. The setting of this dump-fraction can be motivated either by theory or by matching to observed levels of hard x rays. The temperature of the suprathermal-electron source is set by a semiempirical scaling law that has been matched both with plasma simulations and with earlier experiments.^{39,41,42} Other processes that generate suprathermal electrons, such as stimulated Raman scattering (SRS)⁴³ and two-plasmon decay ($2\omega_{pe}$), are not yet incorporated into the code.⁴⁴

The model has been extended recently in one major area: the one-dimensional absorption model now has a calculation of the level of stimulated Brillouin backscatter.⁴⁵ On the basis of LASNEX-calculated plasma profiles, the model calculates the evolution of ion-wave turbulence. The turbulence level is transferred to a calculated back-reflection fraction according to a model⁴⁵ based on theory and plasma simulations. The backscattered light is tracked outward through the plasma and may rescatter once.

The atomic physics model used for the LASNEX calculations discussed here is identical with that employed previously by Rosen et al.³⁶ This model includes a solution of the time-dependent ionization and radiation-rate equations in an average-atom treatment.⁴⁶ The use of a full non-LTE model is essential for the mid- to high-Z target-irradiation parameters in these experiments, since very steep density and temperature gradients are produced by the absorption near the critical surface and the high-Z plasmas have very large radiative rates. Large errors in the coronal ionization state and temperatures would be made if LTE were forced.

The electron-conduction modeling used here is the same as that used for modeling many previous experiments.³⁴⁻³⁶ Thermal electrons, modeled by a single Maxwellian group, are transported by flux-limited diffusion. The value for the thermal-flux limit is taken as $f_t = 0.03$, which provides flux limitation at essentially the same level as the ion-acoustic-turbulence model in LASNEX. A large body of evidence supports using this value for LASNEX simulations of 1.06- μm experiments.^{34,36,47} The suprathermal electrons are modeled using multigroup flux-limited diffusion with no anomalous flux limit reduction, but with fairly self-consistent electric-field coupling (via $J_{\text{tot}} = 0$) to the thermal electrons.³⁴

Wavelength-Scaling Trends

Most of the advantages of using shorter-wavelength lasers to drive fusion micro-implosions accrue because the shorter-wavelength light deposits its energy in higher plasma densities. Hence, corona temperatures (at a given intensity) are lower, and collision rates are higher; most of the collective laser-plasma interaction effects then have higher thresholds and lower growth rates,⁴⁸ and inverse-bremsstrahlung absorption becomes increasingly effective. Thus, at submicrometre wavelengths, we expect to obtain higher absorption, reduced suprathermal-electron production, and higher thermal and hydrodynamic coupling efficiencies.⁴⁹

As an example of the above effects, we show in Fig. 7-40 a set of early LASNEX predictions of wavelength scaling. The plot, for gold-disk target irradiation at a peak

Fig. 7-40. LASNEX wavelength-scaling predictions.

intensity of $3 \times 10^{14} \text{ W/cm}^2$ with a 600-ps Gaussian pulse (FWHM), shows the total absorption ($E_{\text{ABS}}/E_{\text{INC}}$), the fraction of the absorbed energy that produces suprathermal electrons by resonance absorption at the critical surface ($E_{\text{HOT}}/E_{\text{ABS}}$), and the efficiency with which absorbed energy is converted into x rays ($E_{\text{RAD}}/E_{\text{ABS}}$). The LASNEX model used for these calculations is identical with that used to analyze previous experiments conducted at a wavelength of $1.06 \mu\text{m}$.³⁶ That model used a fixed resonance-absorption dump-fraction of 0.30 at the critical surface as the only source for suprathermal electrons and did not explicitly include either stimulated Brillouin scattering or nonlinear inverse-bremsstrahlung opacity reduction.

As previously discussed, Brillouin scattering is incorporated in the more recent LASNEX calculations described in the remainder of this article, but the opacity reduction is not; however, both factors affect this modest-intensity case ($I \sim 3 \times 10^{14} \text{ W/cm}^2$) only slightly. The qualitative trends associated with increased collisionality are shown quantitatively by the simulations. Deposition of the laser energy into high-density plasma, where subkilovolt x rays are produced, most effectively results in an improved x-ray conversion efficiency as the laser wavelength decreases. The absorbed energy in suprathermal electrons decreases with decreasing wavelength because the laser intensity at the critical density is reduced by more effective absorption in the underdense corona. Although not shown in Fig. 7-40,

there is also a reduction in the suprathermal electron temperature due to the scaling with $I\lambda^2$ (Ref. 39), the reduced laser intensity at critical density, and the lower background electron temperature.

In Fig. 7-41, we show LASNEX-calculated plasma profiles near the peak of the laser pulse for gold-disk target irradiation at $3 \times 10^{14} \text{ W/cm}^2$ with a laser wavelength of $0.53 \mu\text{m}$; the 25-J laser pulse was Gaussian with a 600-ps FWHM. Qualitatively, the profiles are quite similar to those calculated for $1.06\text{-}\mu\text{m}$ wavelength at the same irradiation condition. However, the temperature of the critical surface at the peak of the laser pulse has dropped from 1.6 to 0.8 keV, and the maximum coronal temperature has decreased from 2.6 to 2.1 keV.

In the following subsections, we discuss LASNEX simulations of, and the expected trends for, key features of the Argus wavelength-scaling experiments made to date.

Absorption and Scattering

Figure 7-42 shows the results of $0.53\text{-}\mu\text{m}$ absorption measurements that were made using the box calorimeter for beryllium-, plastic-, and gold-disk targets at normal incidence (see "Absorption" earlier in this section). The horizontal bars in Fig. 7-42 represent the intensity spread (30 to 70%) on a given shot. When qualitatively compared with the simple absorption modeling, the measurements show that absorption increases at decreasing intensity and increasing target Z, as expected for collisional absorption by inverse bremsstrahlung.

We observe increased absorption at $0.53 \mu\text{m}$, as compared with similar $1.06\text{-}\mu\text{m}$ experiments using gold-disk targets. For example, the absorption measured at $3 \times 10^{14} \text{ W/cm}^2$ is $80 \pm 5\%$ for $0.53\text{-}\mu\text{m}$ wavelength and 600-ps pulse duration, while earlier $1.06\text{-}\mu\text{m}$ experiments³⁶ obtained $53 \pm 5\%$ at 900 ps. Thus, for gold-disk targets under the conditions described in the previous sentence, the absorption for $0.53\text{-}\mu\text{m}$ light is higher by roughly a factor of 1.5 than that for $1.06\text{-}\mu\text{m}$ light. Preliminary

Fig. 7-41. LASNEX-calculated plasma profiles for gold-disk target.

results at 0.35- μm wavelength indicate that this increase continues (see "Absorption" in this section), with absorption fractions greater than 90% for intensities up to $\sim 10^{15} \text{ W/cm}^2$.

Lower-Z targets also show significantly higher absorption at 0.53 μm , as compared with data from prior 1.06- μm experiments. Measurements for plastic-disk (CH) targets irradiated at 1.06 μm , $5 \times 10^{14} \text{ W/cm}^2$, 75 J, and 300 ps, using the Cyclops laser, showed 25% absorption,³⁵ while the recent 0.53- μm experiments show that absorption is increased by about a factor of 2 at this intensity. Here, too, our preliminary 0.35- μm experiments show a further increase in absorption. Short-pulse wavelength-scaling experiments performed by Fabre et al.⁵⁰ exhibit similar absorption trends for low-Z targets.

Plotted in Fig. 7-42 for comparison with the 2ω data are the absorptions calculated by LASNEX using the nominal inverse-bremsstrahlung opacity; a thermal-flux inhibitor, f_t , of 0.03; a dump-fraction, f_d , of 0.03; and the stimulated Brillouin scattering package. In modeling these experiments, we have been forced by the measurements of high-energy x rays (discussed below) to reduce the amount of absorption via collective processes. The resonance-absorption dump-fraction has been reduced to 0.03 to better match the fluence of high-energy x rays. This value is considerably lower than the value that has usually been

used (0.3), which was motivated on the basis of simulations of resonance absorption.^{39,40} A similar conclusion regarding the dump-fraction was drawn by Rosen et al.³⁶ in an earlier analysis of long-pulse ($\tau_L \sim 900 \text{ ps}$) 1.06- μm experiments. This reduction in the dump-fraction may be due to an extended density scale length at the critical surface, by stimulated Brillouin scattering, or both.

As may be seen in Fig. 7-42, the calculations reproduce the observed behavior to within ~ 10 to 15%. The largest errors occur for the high-intensity points and, particularly, for the beryllium targets, precisely where additional collective absorption would occur if a dump-fraction of 0.3 had been employed. However, this large dump-fraction is not supported by the multikilovolt x-ray measurements. Other processes could also provide the required 10 to 15% absorption: short-wavelength ion turbulence,³⁸ slightly increased thermal-electron transport (which would make inverse bremsstrahlung more effective), or a reduction in stimulated Brillouin scatter.

Significant levels of Brillouin scattering are calculated in the $\sim 2 \times 10^{15} \text{ W/cm}^2$ beryllium-disk simulations. The beryllium-disk experiment has the longest gradient lengths in the underdense plasma, and its laser intensity lies the farthest above threshold. Here, we calculate that 70% of the incident light is backscattered on its way to the critical surface. When the Brillouin level becomes this high, significant multiple

Fig. 7-42. Measured and calculated absorptions for 0.53- μm irradiations of beryllium-, plastic-, and gold-disk targets.

scattering is expected, and we calculate about 30% of the Brillouin scattered light is rereflected inward.

Experimentally, the spectrum of the backscattered light near $0.53\ \mu\text{m}$ indicates the presence of stimulated Brillouin scattering.⁵¹ The time-resolved back-scattered light is predominantly red-shifted for all of the targets for intensities in excess of $\sim 3 \times 10^{14}\ \text{W}/\text{cm}^2$. In addition, striking qualitative differences are observed between the backscatter of low-Z (Be) and high-Z (Au) targets.⁵¹ Interpretation of these spectra and their strong dependence on Z remain subjects for continued effort. At present, simulations imply stronger blue shifts than are measured; the blue shifts in the simulations arise from both the calculated supersonic plasma flow at the critical density and the decreasing optical path in the expanding plasma.⁵² Nonetheless, the backscatter spectra indicate that Brillouin scattering is operating in the higher-intensity irradiations, even for these relatively short-scale-length experiments.

Multikilovolt X Rays and Suprathermal Electrons

The fluence of multikilovolt x rays has been measured so that we can infer the levels of suprathermal electrons generated by the laser-plasma interactions ("Suprathermal X Rays"). The detectors span the x-ray energy range from about 5 to 70 keV. K-edge filtered spectrometer signals have been unfolded ("Suprathermal X Rays") to determine the spectra emitted by the targets. For the 2ω experiments, we find that the shot-to-shot variations about the mean are a factor of approximately 3 to 5 in fluence, but on the order of 50% in slope.

In Fig. 7-43, we show the dependence of hard x-ray spectra on both intensity and target material for $0.53\text{-}\mu\text{m}$ irradiation of 25 J in 600-ps Gaussian pulses. The high-energy x-ray fluence increases dramatically with intensity, as shown for Au disks in Fig. 7-43(a). This increase has been qualitatively observed in many other experiments.³⁷

Fig. 7-43. Measured high-energy x-ray spectra for disk targets irradiated with $0.53\text{-}\mu\text{m}$ light.

Analysis and Summary of Wavelength-Scaling Experiments and Comparisons with Simulations

Figure 7-43(b) shows that the hard x-ray yield increases with target Z , as would be expected for thick-target bremsstrahlung emission. In addition, the data presented in Fig. 7-43(b) are also suggestive of a hardening of the spectrum with increasing atomic number of the target.⁵³

The measured x-ray fluence from high- Z plasmas at these intermediate photon energies (10 to 70 keV) is a superposition of free-bound emission from the thermal background electrons and of bremsstrahlung radiation generated by the suprathermal electrons as they slow down in the overdense plasma. Irradiation with short-wavelength lasers enhances the former process, because of the increasing density and light-absorption efficiency of the underdense plasma, while decreasing the latter process, because of the reduced generation of suprathermal electrons. Thus, the anticipated spectrum in the 10- to 70-keV photon-energy range with 0.53- μm irradiation should exhibit more curvature (i.e., changes in spectrum slope between adjacent x-ray energy channels) than the near-exponential behavior generally seen in this spectral regime at 1.06 μm .⁵³ This qualitative change in spectrum slope is seen both in experiments [Fig. 7-43(b)] and in LASNEX simulations, although the calculated spectrum shows some quantitative departures from the measured spectrum, as discussed below.

Order-of-magnitude estimates of the amount of energy in suprathermal electrons that would produce the observed hard x-ray fluence ($h\nu \lesssim 30$ keV) can be made by assuming that the radiation is produced by thick-target bremsstrahlung radiation from a three-dimensional, Maxwellian suprathermal electron distribution.⁵⁴ The x-ray fluence (in keV/keV-sphere) at the photon energy equal to the hot electron temperature ($h\nu = kT_H$) is given by

$$\phi_h \sim 6.3 \times 10^9 Z E_H \text{ (keV/keV-sphere)} \quad (2)$$

where Z is the atomic number of the matter in which the electrons are slowing down, and E_H is the energy (in joules) contained in the hot Maxwellian distribution.⁵⁴ In this simple estimate, we neglect losses of suprathermal electron energy to

hydrodynamic plasma expansion, but we generally find that these estimates agree with LASNEX calculations to within a factor of 2 to 4.

To estimate the hot-electron fraction, we must determine the hot-electron temperature, kT_H . Experimental difficulties arise due to the large thermal x-ray background and the small suprathermal electron population, which, combined, result in curvature of the spectrum at intermediate photon energies and in very small fluence levels at high photon energies ($h\nu > 50$ keV). To minimize the thermal-emission background, we use the x-ray fluence in the two highest-energy channels of the K-edge filter spectrometer (typically $h\nu \sim 46$ and ~ 70 keV) to infer a suprathermal "temperature," and we then extrapolate the spectra to find the fluence at the photon energy of kT_H .

The results of such an analysis are presented in Table 7-7 for the 2ω experiments. The table entries indicate the spectral region analyzed to obtain the kT_H and E_H values. While the inferred suprathermal electron populations fluctuate to some extent, the levels are generally quite low, accounting for less than $\sim 1\%$ of the absorbed energy.

The results at $2 \times 10^{15} \text{ W/cm}^2$ also suggest some increase in kT_H with increasing target Z . (Note that, at the lower intensity of $\sim 3 \times 10^{14} \text{ W/cm}^2$, the hardening of the x-ray spectrum with increasing Z is not conclusively suggested by the data.) This increase in kT_H is consistent with previous 1.06- μm experiments.⁵⁴ Theoretically, this

Table 7-7. Estimates of hot-electron populations.

Target material	Irradiation intensity (W/cm^2)	Photon frequency range (keV)	kT_H (keV)	F_H (%)
Be	$\sim 3 \times 10^{14}$	24 to 46	7.0 ± 0.7	1.0
Ti	$\sim 3 \times 10^{14}$	24 to 46	6.4 ± 1.5	0.1
Au	$\sim 3 \times 10^{14}$	46 to 70	12 ± 4	0.3
Be	$\sim 2 \times 10^{15}$	24 to 46	9.3 ± 1.5	0.5
Ti	$\sim 2 \times 10^{15}$	24 to 46	13 ± 6	0.5
Au	$\sim 2 \times 10^{15}$	46 to 70	19 ± 7	0.1

Notes: (1) Estimates are order-of-magnitude estimates derived from hard x-ray fluence measurements.

(2) For the 2ω experiments, kT_H is the "temperature" inferred from the slope of the x-ray spectrum, while F_H is the fraction of the incident laser energy contained in a Maxwellian electron distribution that could produce the observed x-ray fluence. The estimate neglects hydrodynamic losses, which LASNEX shows to be a factor of 2 to 4.

increase can be at least partially explained. Plasma-kinetic simulations of resonance-absorption heating⁵⁵ suggest that the combined effects of albedo (reflection of electrons from the highly collisional overdense medium back into the corona) and of reheating of the hot electrons nearly cancel, yielding no significant Z dependence for kT_H due to recirculation of the hot electrons through the critical surface. However, LASNEX simulations for those experiments that do not include an explicit Z dependence in the T_H resonance-absorption model do show a weak Z dependence of, roughly, $T_H \sim Z^{0.15}$. This dependence results from Z -dependent conduction⁴¹ and from inverse-bremsstrahlung heating rates⁴⁷ that raise the background temperature in higher- Z plasmas. The resonance absorption, T_H , is, in turn, increased by this increased background temperature. Thus, theory suggests a weaker Z dependence than has previously been suggested,⁵⁵ i.e., $T_H \sim Z^{0.25}$. This discrepancy is neither large nor clearly outside the bounds of reasonable experimental errors.

The current LASNEX modeling of absorption and suprathermal electrons does not adequately match the experimentally observed hard x-ray yields. Figure 7-44 shows a comparison of LASNEX calculations, made with various dump-

fraction values, with the hard x-ray data from gold disks irradiated under conditions of $2 \times 10^{15} \text{ W/cm}^2$, $0.53 \mu\text{m}$, 25 J , and 600 ps . We note that all these simulations show excessive emission for intermediate photon frequencies (10 to 30 keV). A similar discrepancy can be seen in earlier $1.06\text{-}\mu\text{m}$ experiments.³⁶ The best agreement with the high-energy photon spectrum is obtained by using $f_d = 0.03$.

As discussed above, when we perform LASNEX calculations with the usual $f_d = 0.3$ (uppermost curve in Fig. 7-44), the calculated hard x-ray fluences are about a factor of 10 too large, as compared with measurements. A similar discrepancy in the hard x-ray fluence was seen in short-pulse, high-intensity $1.06\text{-}\mu\text{m}$ experiments.⁴¹ LASNEX simulations of those experiments, using $f_d = 0.3$, yielded calculated x-ray fluences considerably higher than those measured.

Some of the discrepancies between the experiments and the simulations would be resolved if the absorption processes generated considerably fewer suprathermal electrons or if the suprathermals were confined to low-density regions of the plasma so that the bremsstrahlung radiation would be much reduced. The latter hypothesis is very difficult to support, since simulations have shown that the loss-rate

Fig. 7-44. Comparison of measured and calculated high-energy x-ray spectra for gold disks.

ratio of radiative to hydrodynamic energy must be altered by a very large factor to reduce the hard x-ray emission by a factor of ~ 10 . Using the suprathermal electron modeling of LASNEX, even with a very large (~ 100 -fold) reduction in the suprathermal transport coefficient, we are unable to adequately reduce the hard x-ray emission. Furthermore, two-dimensional calculations that include thermoelectric magnetic-field generation do not show the required severe inhibition of suprathermal electron transport, so it seems difficult to provide a sufficiently strong confinement mechanism for the suprathermals. In addition, estimates based upon suprathermal electron orbiting,⁵⁶ which is not incorporated into the present LASNEX suprathermal transport model, suggest that electrons would be inadequately confined to low-density plasma unless the corona were considerably larger than calculated by LASNEX or by isothermal estimates.

Thus, for this work, we have adopted the reduced resonance-absorption hypothesis, using $f_d = 0.03$. We suggest that resonance absorption may be efficient with short-wavelength lasers ($\lambda_L < 1 \mu\text{m}$) only for laser pulse widths less than 100 ps, since slower rise times create longer density gradients as the plasma develops. This longer scale length could, in turn, make the resonant region inaccessible,⁴⁰ thus reducing the momentum deposited by hot electrons (ejected down the density gradient by resonance absorption) and further inhibiting self-steepening at the critical surface. Quantitative estimates suggest that a scale length of several micrometres—long enough to inhibit resonance absorption—could be easily obtained at the critical surface. In any case, improved understanding of suprathermal electron production and transport is necessary.

The present LASNEX modeling for suprathermal electron generation does not include parametric processes, such as stimulated Raman scattering (SRS) and two-plasmon decay ($2\omega_{pe}$), that occur in the underdense plasma ($N_e \gtrsim N_c/4$). These processes, which require long-scale-length plasmas, may become the dominant source of suprathermal electrons in long-pulse, high-energy experiments.^{57,58} For example, in the moderate $I\lambda^2$ irradiations ($I\lambda^2 < 10^{15} \text{ W}\cdot\mu\text{m}/\text{cm}^2$) and plasma scale lengths (calculated value at $N_c/4 \sim 100 \mu\text{m}$)

employed in the $0.53\text{-}\mu\text{m}$ experiments, the threshold for Raman sidescatter is only slightly exceeded.⁵⁸

The expected small values were confirmed by using an array of filtered pin diodes to measure the scattered light in the wavelength range from 0.6 to $1 \mu\text{m}$.⁵⁸ For Au disks irradiated with a peak intensity of ~ 1 to $3 \times 10^{15} \text{ W}/\text{cm}^2$, an array of detectors at 40° to the incident laser direction implied scattered light levels of $\sim 5 \times 10^{-5}$ of the absorbed energy. If the scattered light levels were due to SRS, a similar amount of energy in suprathermal electrons would be inferred (neglecting reabsorption). The hard x-ray yields, however, imply a suprathermal fraction, F_{HOT} , of $\sim 5 \times 10^{-3}$ to 10^{-2} .

Although low levels of SRS were expected and were inferred experimentally, since the threshold for $2\omega_{pe}$ decay is about a factor of 10 lower than for Raman sidescatter,⁵⁷ it is possible that this instability is occurring more rigorously in these experiments. However, no means of isolating this process (e.g., directed electron emission)⁵⁹ were available in the $0.53\text{-}\mu\text{m}$ experiments.

Detailed comparisons of the characteristics of suprathermal electrons generated at different wavelengths must await completion of directly comparable wavelength-dependence experiments to avoid overreliance on theory and modeling. Furthermore, many aspects of the experiments (e.g., the beam quality) must be closely analyzed before reliable conclusions can be drawn. Nonetheless, to show the substantial reduction in the hard x-ray yield as the laser wavelength is reduced from 0.53 to $0.35 \mu\text{m}$, we reproduce the early results from the 3ω experiments in Fig. 7-45. This figure shows the hard x-ray fluence produced from a gold microdisk as the laser intensity is increased (see also "Suprathermal X Rays" in this section).

As we have discussed above, it is possible to infer the suprathermal-electron population and effective temperature. However, it is clear from Fig. 7-43(c) that the high thermal background and the limited number of detector channels severely limit the confidence of such an analysis. Nonetheless, if we use only the two highest energy channels for a peak intensity of $10^{15} \text{ W}/\text{cm}^2$, a "temperature" of $\sim 10 \text{ keV}$ is obtained with only $\sim 10^{-4}$ of the absorbed energy appearing in the suprathermal electrons.

Fig. 7-45. Hard x-ray yields from Au microdisks as a function of peak intensity for 3ω irradiation.

Subkilovolt X-ray Emission

We have made very detailed measurements of the subkilovolt x-ray emission from the Argus wavelength-scaling target irradiations. Here, we discuss only the irradiation results obtained at $0.53\ \mu\text{m}$. The preliminary results at $0.35\ \mu\text{m}$ appear qualitatively similar, but with slightly enhanced subkilovolt x-ray yield.

We have performed extensive measurements of the time dependence of sub-keV x-ray emission, with a time resolution of about 15 ps, by using an LLNL x-ray streak camera.⁶⁰ These measurements are dependent on knowledge of details of the plasma heating and cooling processes. Figure 7-46 shows the observed time dependence of emission power in two x-ray

energy bands for three gold-disk irradiations at $3 \times 10^{14}\ \text{W/cm}^2$, 25 J, and 600 ps with $0.53\text{-}\mu\text{m}$ light. The rise and fall times are reproducible to within about 10%. The rise time corresponds quite closely with that of the incident laser pulse, but the fall time is longer because the plasma continues to radiate the absorbed energy as it cools. The corresponding results from LASNEX simulations are overlaid with arbitrary time and peak-power normalizations. Agreement is good to about 20%, with the measured emission time being shorter than that calculated.

The emission-time measurements support two systematic trends, which are also seen in the LASNEX simulations. First, as shown in Fig. 7-47(a), the emission-power FWHM decreases at increasing sub-keV photon energies. This result is expected for a cooling plasma that is roughly in equilibrium. Second, as shown in Fig. 7-47(b), the emission FWHM increases with increasing irradiation intensity. The LASNEX calculations track this trend; however, this calculated result is rather subtle. The code shows that the dominant cooling processes are radiation and hydrodynamic expansion and that the ratio of these cooling processes shifts from 2:1 at $3 \times 10^{13}\ \text{W/cm}^2$ to 1:2 at $2 \times 10^{15}\ \text{W/cm}^2$. The small shift in net cooling time is then caused by the differences between these two strong scalings and by the somewhat smaller effects of electron conduction.

The broadband spectrum of sub-keV x rays emitted at 60° to the target normal is shown in Fig. 7-48 for $0.53\text{-}\mu\text{m}$ irradiations of gold-disk targets at $3 \times 10^{14}\ \text{W/cm}^2$, 25 J, and 600 ps. The spectrum was obtained by temporal integration of the prompt x-ray emission and by spectral unfolding of the signals obtained with the eight-channel Dante-T x-ray diode detector system with K- and L-edge filters (see "X-ray Conversion Efficiency" in this section). At the detector resolution ($\Delta E/E \sim 0.1$ to 0.4), the spectrum is quite similar to that observed in previous $1.06\text{-}\mu\text{m}$ irradiations.³⁷ The LASNEX calculation plotted in Fig. 7-48 yields closely corresponding spectral shape and fluence. The calculation shows a significant contribution to the emission around 0.8 keV from the broad group of N-shell line transitions that are excited in partially stripped gold at $\sim 200\text{-eV}$ temperatures.

To determine the total sub-keV x-ray conversion efficiency, we have observed the emission at several angles with respect to the disk normal by using several multiple-diode systems and three angles of incidence. Examples of measured angular distributions have been discussed in "X-ray Conversion Efficiency" in this section and are reproduced in Fig. 7-49 for gold-disk irradiations with $0.53\text{-}\mu\text{m}$ light at intensities of $3 \times 10^{14} \text{ W/cm}^2$ and $\sim 4 \times 10^{15} \text{ W/cm}^2$. The temporally and spectrally integrated fluence ($0.1 \text{ keV} < h\nu < 1.8 \text{ keV}$) is plotted as a function of the cosine of the angle, β , between the detector and the target normal. The angles of incidence employed were less than 30° to ensure that tilting of the target would have as little effect as possible on the emission pattern and relevant physics.

The LASNEX-calculated angular distributions are also shown in Fig. 7-49 for comparison with the experimental data. Both the two-dimensionally calculated and the measured angular distributions are

flatter at $\sim 4 \times 10^{15} \text{ W/cm}^2$ than at $3 \times 10^{14} \text{ W/cm}^2$. This flattening occurs because the smaller spot diameter employed at $\sim 4 \times 10^{15} \text{ W/cm}^2$ (30 to $50 \mu\text{m}$ vs $150 \mu\text{m}$ for $3 \times 10^{14} \text{ W/cm}^2$) makes the diameter of the emitting region comparable to its thickness (calculated to be $50 \mu\text{m}$ at this intensity). At $3 \times 10^{14} \text{ W/cm}^2$, the $150\text{-}\mu\text{m}$ spot diameter is considerably larger than the time-integrated thickness of the emission region, yielding a more strongly peaked Lambertian-like emission pattern.

Finally, we integrate over the angular distribution to obtain the total energy emitted in x rays between 0.1 and 1.8 keV . The conversion efficiency is plotted in Fig. 7-50 for titanium and gold disks and is normalized by the energy absorbed in each case. We have estimated the absorption fractions for the titanium targets by interpolating the measured absorptions for Be and Au; we have also included the additional uncertainty contained in the conversion-efficiency error bars. The

Fig. 7-46. Measured and calculated sub-keV x-ray radiated power vs time for Au disks.

Fig. 7-47. Scaling of radiated sub-keV emission FWHM for irradiation of gold disks at $0.53 \mu\text{m}$, $3 \times 10^{14} \text{ W/cm}^2$, 25 J , and 600 ps .

calculated x-ray conversion efficiencies are seen to agree well with the measured values, except for the gold irradiations at 3×10^{13} W/cm². In general, the conversion efficiency increases with increasing target Z and with decreasing intensity. These trends indicate generally improved conversion efficiency as the plasma conditions become more collisional.

The discrepancy between calculated and measured conversion efficiency for the 0.53- μ m, 3×10^{13} -W/cm² case is quite interesting and has received considerable

attention in analyses. Comparing the simulations with the experiments, we find most of the observed features of the 3×10^{13} -W/cm² experiment to be in close correspondence with calculations. For example, the absorption characteristics, the sub-keV (broadband) x-ray spectrum, and the sub-keV x-ray temporal and spatial distributions all appear to be well-matched by the modeling. One suggestive clue has been found: the observed 2.5-keV M-line emission drops by a factor of 5 between 3×10^{14} and 3×10^{13} W/cm², while the calculated M-line yield drops by only a factor of 1.5. This relatively small calculated drop leads to one possible explanation of the conversion-efficiency discrepancy: the simulation overestimates the effective ionization state of gold in the 3×10^{13} -W/cm² calculations. This overestimation could also affect the total x-ray conversion efficiency. We will investigate this area further.

We may draw on related 1.06- μ m experiments to obtain a rough idea of the wavelength-scaling of the x-ray conversion efficiency. In earlier 1.06- μ m experiments³⁶ at 3×10^{14} W/cm², 400 J, and 900 ps, with slightly different parameters, we measured the x-ray conversion efficiency somewhat more crudely and obtained about 33%,

Fig. 7-48. Broadband sub-keV spectrum emitted at 60° to the target normal for gold disks.

Fig. 7-49. Measured and calculated sub-keV angular distributions for gold-disk irradiations at 0.53 μ m, 25 J, and 600 ps.

compared with $52 \pm 15\%$ for the current $0.53\text{-}\mu\text{m}$ experiments at $3 \times 10^{14} \text{ W/cm}^2$, 25 J, and 600 ps. Although considerable refinement is expected in the wavelength-scaling results, we feel justified in concluding that the x-ray conversion efficiency does increase as the laser wavelength decreases, at least qualitatively, in accord with predictions.

Role of Electron Conduction

Electron conduction carries the energy from the laser-deposition region near the critical density into the higher-density plasma. Thus, in low-Z plasmas, electron conduction determines the mass ablation rate and the ablation pressure, while in high-Z plasmas, it delivers the absorbed energy to the region where radiative processes occur strongly. In general, the corona density and temperature profiles also depend fairly sensitively on electron transport, so the laser-plasma interactions are affected by the transport coefficients.

For the LASNEX calculations presented in this article, we have used inhibited thermal transport with a flux-limit parameter of $f_t = 0.03$, which represents "anomalous" inhibition by a factor of ~ 10 below "classical" expectations. This parameter yields the best overall agreement with the current $0.53\text{-}\mu\text{m}$ experiments for both low- and high-Z targets.

We present in Table 7-8 some comparisons of calculations performed with and without inhibited thermal transport. Many aspects of the simulations diverge from experimental results when transport is not inhibited. We find that, without thermal-transport inhibition, the absorption calculated is generally too high, even when all nonlinear absorption reductions are taken into account. Further, the sub-keV x-ray conversion efficiencies calculated for mid- and high-Z targets at high intensity are too large. However, a few aspects of the simulations improve with uninhibited transport; e.g., calculations without inhibition do not exhibit the excessive mid-energy x-ray emission that is seen in the inhibited-conduction modeling.

On balance, the model with thermal-transport inhibition provides better

	Experiment	LASNEX	
		Inhibited	Classical
Absorption (%)			
Be	35 ± 10	22 ^a	44 ^a
Au	45 ± 10	46 ^a	75 ^b
X-ray conversion efficiency (%)			
Ti	17 ± 7	15	34
Au	33 ± 10	35	45

^aValue obtained using $f_d = 0.03$, as suggested by the measured hard x-ray fluences. Using $f_d = 0.3$ would raise the calculated absorption by 5 to 10%.

^bValue of f_d has little effect on this calculated absorption value.

Table 7-8. Comparison of LASNEX calculations.

Fig. 7-50. Measured and calculated x-ray conversion efficiency as a function of intensity for titanium and gold disks.

agreement with the data. We emphasize that the inference of electron transport, derived from integrated disk irradiations such as the present experiments, is somewhat uncertain. The convolution of many physical effects makes the inference of electron-transport coefficients uncertain, especially for the high-Z targets for which the atomic physics and radiative-transport models are important. Experiments specifically designed to determine the behavior of electron transport at a wavelength of $0.35 \mu\text{m}$ are in progress (see "Transport Experiments at 3ω " in this section).

Summary

We have presented an overview of the results of wavelength-scaling experiments in which beryllium-, titanium-, and gold-disk targets

were irradiated with 0.53- μm light in 25-J, 600-ps pulses at intensities ranging from 3×10^{13} to $\sim 4 \times 10^{15} \text{ W/cm}^2$.

We find that the light is efficiently absorbed and that intensity scaling and Z scaling match expectations for strong collisional absorption by inverse bremsstrahlung. The LASNEX absorption model, including classical inverse bremsstrahlung and stimulated Brillouin scattering, tracks the absorption to within 10 to 15%. At the highest intensity, the absorption model requires either a resonance-absorption dump-fraction of about 30% or about 10 to 15% of additional absorption by some other means.

We observe some evidence that Brillouin scattering is operating at moderate levels in these experiments. Measured spectra for the backreflected light show features that, while difficult to interpret in detail, indicate that Brillouin scattering occurs in the higher-intensity irradiations ($I > \sim 3 \times 10^{14} \text{ W/cm}^2$). Large qualitative differences are observed between low-Z and high-Z backreflected spectra. The highest calculated levels of Brillouin scattering are about 50% for the $2 \times 10^{15} \text{ W/cm}^2$ beryllium-disk case.

Stimulated Raman scattering is also occurring, although at very small fractions ($\gtrsim 10^{-5}$) of the incident laser energy. For the short-scale-length plasmas investigated here, these levels seem theoretically reasonable.

We have measured the intensity and Z scaling of the fluence and slope of hard x rays. The simplest interpretation of the measured fluence suggests that the suprathermal-electron population contains less than about 1% of the incident energy for all irradiation conditions employed. LASNEX calculations can be brought into crude agreement with the measured hard x-ray fluence by assuming that about 3% of the light reaching the critical surface is resonantly absorbed. Improved theoretical understanding of the apparently low levels of suprathermal populations is a matter for continuing study.

We have performed extensive temporal, spectral, and angular observations of sub-keV x-ray emission from titanium- and gold-disk targets. The x-ray emission time is slightly longer than the laser pulse width, and the fall time is slower than the rise time,

reflecting the plasma cool-down processes. The variations of emission time with intensity and photon frequency are tracked well by LASNEX simulations. Broadband sub-keV spectral and angular distributions are similar to those calculated, and these distributions seem to be adequately understood. We have observed efficient conversion of absorbed laser light into x rays by using 0.53- μm light to irradiate gold disks. Our LASNEX calculations reproduce both the Z scaling and the intensity scaling of the total x-ray conversion efficiency quite well, except for the gold target at $3 \times 10^{13} \text{ W/cm}^2$. Surprisingly, we measure lower conversion efficiency at $3 \times 10^{13} \text{ W/cm}^2$ than at $3 \times 10^{14} \text{ W/cm}^2$ in these 0.53- μm irradiations. This phenomenon remains to be investigated further.

We obtain the best overall LASNEX simulations of these experiments by using a value for inhibited thermal transport, f_0 , of 0.03. However, electron transport is tied closely enough to other physical processes to render fairly uncertain the deconvolution of electron-transport coefficients from comparisons with the measured observables. Other experiments that would employ, for example, layered targets are required to isolate electron thermal transport.

We can form some initial conclusions concerning wavelength scaling by comparing 0.53- μm experiments with similar 1.06- μm experiments. We find absorption increasing with decreasing wavelength, and we tentatively infer a reduction in the suprathermal-electron population and the hard x-ray slope as the wavelength decreases. Finally, we find that the efficiency of converting absorbed light into sub-keV x rays increases as the wavelength decreases. More quantitative wavelength-scaling results will be forthcoming as the current Argus experiments continue.

Authors: E. M. Campbell and W. C. Mead

Major Contributors: K. G. Estabrook, W. L. Kruer, R. E. Turner, P. H. Y. Lee, F. Ze, K. G. Tirsell, and B. L. Pruett

Stimulated Raman Scattering in Large Plasmas

Introduction

Laser-fusion targets for energy production will be much larger than the ICF targets presently used in experiments. For long-pulse irradiation of the energy-production targets at even moderate intensity ($I\lambda^2 = 5 \times 10^{14} \text{ W}\cdot\mu\text{m}^2/\text{cm}^2$), intense stimulated Raman scattering (SRS) may create a hot-electron environment that would make difficult the achievement of a high density in the target material. The Raman instability has a small gain coefficient, and, for the instability to go strongly, there must be hundreds of wavelengths of rather homogeneous plasma for $I\lambda^2$ values typical of ICF targets. It is not surprising that, until recently, intense SRS has not been observed in laser-plasma interactions. Our measurements show that SRS is much more intense at longer pulse lengths and that it can occur not only near the quarter-critical electron density ($N_c/4$) but also at much lower densities.

The Raman instability^{61,62} is a three-wave parametric process in which the laser light wave decays into another light wave and an electron plasma wave (epw). Energy and momentum conservation require that the frequencies and wave vectors of the epw and the Raman light wave sum to equal the frequency and wave vector of the incident light wave. The epw is usually not appreciably damped by collisions but, rather, loses its energy to fast electrons by wave breaking.

SRS has been observed by others⁶³⁻⁶⁸ and has been predicted by computer simulations.^{69,70} Recent simulation results obtained by the Plasma Theory Group are discussed in "Heating and Hot-Electron Generation in Underdense Plasmas" and in "Theory and Simulation of One-Dimensional Raman Forward Scatter" in Section 3. The earliest observation of $\omega/2$ light, which is a signature of resonant SRS, was reported by Bobin.⁶³ In Bobin's experiments, a line spectrum was

observed centered at 2ω with a $60\text{-}\text{\AA}$ width between half-intensity points, compared to $30\text{-}\text{\AA}$ width for the incident laser light. This $\omega/2$ light can be attributed either to resonance-Raman scattering or to linear mode conversion of the electron plasma waves, produced by the $2\omega_{pe}$ instability, into light waves.

Studies of the threshold behavior of the Raman instability near quarter-critical electron density have been reported by J. Elazer et al.⁶⁴ In their experiments, the $\omega/2$ light (defined by a 5% bandwidth interference filter centered at twice the laser wavelength of $1.05 \mu\text{m}$) was collected by the nearly f/1 target-chamber lens. The threshold intensity decreased by an order of magnitude, from $\sim 10^{15} \text{ W}/\text{cm}^2$ to $\sim 10^{14} \text{ W}/\text{cm}^2$, when the focal spot diameter was increased from 50 to $150 \mu\text{m}$. The laser pulse length was 2 ns for both intensities, but the target material was different. The maximum conversion efficiency into $\omega/2$ light was about 4×10^{-7} , but the maximum laser energy at which these experiments were done was only slightly greater (less than 50% at $10^{15} \text{ W}/\text{cm}^2$) than the threshold energy. (The experiments were done by holding the spot size and pulse length constant while varying the laser energy.)

Watt⁶⁵ has seen Raman scattering of CO_2 laser light in experiments where a 20-cm length of plasma, formed in a solenoid, was irradiated by a CO_2 laser. Baldis⁶⁶ has observed $\omega/2$ electron plasma waves in a CO_2 -irradiated plasma using Thompson scattering; in a continuation of this work, N. A. Ebrahim, H. A. Baldis, C. Joshi, and R. Benesch⁶⁷ have directly observed the fast electrons produced at $N_c/4$. The fastest electrons (60 keV) emerged in jets in the plane of polarization and at 45° to the density gradient. This polarization dependence indicates that the $2\omega_{pe}$ instability was dominant. However, Ebrahim also observed fast electrons of 10 or 15 keV temperature out of the plane of polarization, suggesting Raman backscatter at lower densities.

Many one-and-one-half-dimension particle code simulations of SRS have been done by Estabrook.⁶⁹ For example, in one simulation, $1.06\text{-}\mu\text{m}$ light at $3 \times 10^{15} \text{ W}/\text{cm}^2$ was incident upon a 10-keV plasma, with the

initial density of the plasma rising linearly from zero to $0.4 N_c$ in $105 \lambda_0$. Approximately 15% of the incident light was Raman backscattered.

Recent experiments at the Shiva laser facility have shown that, when very large regions of plasma are irradiated by $1.06\text{-}\mu\text{m}$ light, intense SRS can occur even at the modest intensity of $5 \times 10^{14} \text{ W/cm}^2$. We measured about 140 J/sr in Raman-scattered light when a tantalum disk was irradiated by 4 kJ in a 2.2-ns pulse. Most of this Raman-scattered energy came near the end of the approximately rectangular laser pulse. Both the spectrum and the time dependence of the Raman light were measured simultaneously along different lines of sight.

The Raman light intensity at one wavelength ($1.8 \mu\text{m}$) has been measured at the Shiva facility as a function of intensity for two pulse lengths: 100 and 600 ps (Fig. 7-51). These measurements were made at Shiva with a liquid-nitrogen-cooled indium arsenide detector. At very low intensities ($\approx 10^{14} \text{ W/cm}^2$), we find that the Raman light intensity is extremely small. However, the relative Raman light intensity increases by about three orders of magnitude at $3 \times$

10^{15} W/cm^2 when the pulse length increases from 100 to 600 ps. (The spot sizes and targets were similar for both pulse lengths.) This is a highly significant result, since it shows SRS may be a problem in large plasmas.

We also present preliminary Raman light measurements for $5320\text{-}\text{\AA}$ (green-light) irradiation of disk targets at the Argus facility. The spectrum and angular distribution of the Raman light were measured by an array of photodiodes with 12.5-nm bandpass interference filters centered at 650, 750, 800, 850, 900, 950, and 1000 nm . We did not make measurements at $1.06 \mu\text{m}$, since 10% of the unconverted $1.06\text{-}\mu\text{m}$ light enters the target chamber. The laser light was focused by a 10-cm-diam $f/2$ simple lens. Dispersion-induced displacement of the green and infrared foci caused the intensity of residual $1.06\text{-}\mu\text{m}$ light at the target to be extremely low; most of the $1.06\text{-}\mu\text{m}$ light missed the target. Even though the level of Raman scattering was very small, the signal on some shots was still two orders of magnitude above our detection limit. On several of the higher-intensity shots at $\sim 10^{15} \text{ W/cm}^2$, we observed a peak in the Raman

Fig. 7-51. Raman light measurements made with a liquid-nitrogen-cooled InAs detector.

light spectrum at a wavelength of 800 nm; this peak occurred out of the plane of polarization.

In the balance of this article, we discuss the Raman light diagnostics used in these experiments, the Shiva experimental results, and the Argus experimental results; then, we present our interpretations of these results and, finally, a summary of all the information in this article.

Diagnostics

The spectrum was measured by a 24-element indium arsenide array cooled to liquid-nitrogen temperature and operated in the photovoltaic mode. Each element in the array was 5 mm in height and 0.25 mm in width and was spaced 0.35 mm, center-to-center, from the adjacent elements. The signal from each element went into a separate charge integrator and a sample-and-hold unit.

The Czerny–Turner spectrograph consisted of two paraboloidal mirrors with 6-in. focal lengths and a grating of 75 lines/mm that was blazed for $1.8\ \mu\text{m}$ and used in the first order. The light was brought from the target chamber by a quartz optical fiber that was 15 m long and 1 mm in diameter. The fiber optic butted against the 0.25-mm-wide entrance slit. A line image was formed on the InAs array by inserting a cylindrical lens in the spectrograph. The spectral range of 1.48 to $2.17\ \mu\text{m}$ was covered, with a dispersion of $0.03\ \mu\text{m}/\text{channel}$. The calculated dispersion was verified by bringing in light of known wavelength. For instance, the $6328\text{-}\text{\AA}$ He–Ne line in third order appears at the channel centered at $1.898\ \mu\text{m}$. Thus, we could quickly check that the grating angle had not changed: it was necessary only to remove a single filter from in front of the InAs array.

Optical filters, both at the light collector on the target chamber and in front of the InAs array, ensured that only Raman-scattered light was detected. The InAs array looked through a Corning 7-56 color filter, which absorbed visible light and which had been coated to be highly reflective at the laser wavelength of $1.06\ \mu\text{m}$. With this coating, the filter essentially transmitted only light with wavelengths longer than $1.1\ \mu\text{m}$.

The light collector had both a CS No. 4-64 filter, which absorbed near infrared, and a CS No. 7-56 filter, which absorbed visible light. Also the target-chamber window was coated to be highly reflective at $1.06\ \mu\text{m}$. The InAs array was shielded against x rays by 0.25 in. of lead and looked through a lead-glass window.

The entire optical system was calibrated in situ except that, for convenience, we used a different, nearly identical, 15-m fiber-optic cable and light collector. The light collector was coupled to a blackbody source whose spectral intensity, in $\text{J}/(\text{sr}\cdot\mu\text{m})$, was precisely known. The photovoltaic current of each element was then measured; the load resistance was small ($1000\ \Omega$), and, generally, the current was only a few nanoamperes in magnitude. We also measured the linearity of one InAs element with a pulsed light-emitting diode, finding substantial non-linearity. The absolute calibration of this array seems to be low by a factor of several when we compare its measurements to those made by more accurate diagnostics such as calorimeters, the pyroelectric detector, or discrete InAs detectors.

A Molecron P5-01 fast pyroelectric detector was absolutely calibrated to give us an independent measurement of the Raman light energy and, more importantly, of the time dependence. However, due to the relatively slow time response of the pyroelectric detector, the signal had to be deconvolved (see “Pyroelectric Detector Data Processing” in Section 6).

Many of the $1.06\text{-}\mu\text{m}$ irradiation measurements at Shiva were made with discrete InAs detectors, 2 mm in diameter, that were cooled to liquid-nitrogen temperature and reverse-biased by 1 V. The spectral window was determined by an interference filter; this diagnostic and its calibration have been previously described.⁷⁰

Shiva Experiments

The Raman light experiments were add-ons to several other experiments; e.g., experiments with 100- and 600-ps Gaussian pulses designed to characterize possible x-ray line sources for radiography, layered-target

experiments at 600 ps to study suprathermal electrons, and slab acceleration experiments with ≈ 2.2 -ns rectangular pulses.

All the experiments were done with the upper 10 laser beams of Shiva, which are focused with f/6 lenses. (On Shiva, 10 beams come from the top and another 10 beams come from the bottom.) Each 10-beam lens cluster (upper or lower) consists of two nested pentagonal rings of five equally spaced beams each. The inner beam axes are 9.7° away from the lens cluster axis; the outer beam axes are 17.7° away. For our experiments, the 10 upper beams were superimposed on the targets, which were tilted either 0° or $\approx 45^\circ$ with respect to the axis of symmetry of the beam cluster.

Figure 7-52 shows the location of the two diagnostics and the target orientation for the 45° tilt angle. The spherical coordinates, θ

and ϕ , are the polar and azimuthal angles, respectively. The polar angle, θ , is zero along the cluster symmetry axis (+ in the figure), while the normal to the disk is at $\theta = 45^\circ$ and $\phi = 270^\circ$. The angles Θ_N specify the angles between the detector lines of sight and the target normal. The disk targets were irradiated either in this orientation or at normal incidence. Both diagnostics look at 20° to the lens-cluster axis. The discrete InAs detector and the pyroelectric detector looked at 42° and 62° , respectively, to the target normal for the 45° target tilt or, of course, at 20° for the 0° target tilt.

The experiments that were designed to systematically characterize possible x-ray shadowgraph sources also offered the opportunity to study the Raman instability over a wide range of intensities with both 100- and 600-ps laser pulses. These pulse widths were measured between the half-maximum points of the nearly Gaussian-shaped laser pulse. Figure 7-51 shows the results obtained by the discrete InAs detector, while Table 7-9 shows the results for the pyroelectric detector. No Raman light spectra were obtained for these experiments.

All the experiments shown in Fig. 7-51 were done with a $1.8\text{-}\mu\text{m}$ interference filter, which had an $800\text{-}\text{\AA}$ FWHM bandpass, and all, except for one marked 0° tilt, were done at a 45° tilt angle. Most of the Raman light spectra we have measured show the intensity to be near its maximum at $1.8\text{ }\mu\text{m}$. When the pulse length was increased from 100 to 600 ps, the relative Raman light intensity increased by three orders of magnitude for a detected laser-light intensity at the target of $3 \times 10^{15}\text{ W/cm}^2$. Also, we observed a higher Raman light intensity at $3 \times 10^{15}\text{ W/cm}^2$ when the target was tilted 45° and the InAs detector looked at 42° to the normal than when the target was irradiated at normal incidence and the InAs detector looked at only 20° to the normal. (This observation was confirmed by the pyroelectric detector (Table 7-9, Hf disk experiment), which measures the total Raman light intensity, not just the spectral intensity at one wavelength.)

We also found that at 600 ps and for 4000-J laser energy, less Raman light was generated for the highest intensities of 10^{16} to 10^{17} W/cm^2 than at $3 \times 10^{15}\text{ W/cm}^2$. Evidently, the effects of the lessened

Fig. 7-52. Location of the Raman light diagnostics for the Shiva experiments.

Experiment description						
Target	Energy (kJ)	Pulse length (ps)	Intensity (W/cm^2)	Tilt angle (deg)	Viewing angle (deg)	Measured intensity (J/sr)
Ti disk	0.53	625	3.6×10^{15}	45	62	4
Hf disk	2.6	600	4.6×10^{15}	45	62	112
Ti disk	3.32	600	2.0×10^{16}	45	62	7
Ti disk	3.83	710	3.5×10^{16}	45	62	7
Zn disk	3.84	659	$\sim 10^{17}$	45	62	6
Layered gold disk	2.97	600	3×10^{15}	0	20	10
Layered gold disk	3.19	600	3.2×10^{15}	0	20	29
Layered gold disk	3.25	600	3.3×10^{15}	0	20	29
Layered gold disk	1.77	600	1.8×10^{15}	0	20	2.3

Table 7-9. Pyroelectric detector measurements made at Shiva of the Raman light intensity.

interaction length and the greater Landau damping overcame the effect of the greater intensity.

Most of the Raman light spectra show little light near $\omega/2$; we believe this is most probably due to absorption. Experiments on lower-Z plasmas would confirm or contradict this hypothesis. Figure 7-53 shows a spectrum from one of the layered-disk targets that was irradiated at normal incidence at 3.3×10^{15} W/cm² with 3.25 kJ in 600 ps. The spectrum is extremely broad and only begins to drop off rapidly for wavelengths longer than $2.08 \mu\text{m}$. We see the peak, but we cannot see to a wavelength short enough for the Raman light intensity to drop off rapidly. The pyroelectric detector measured 29^{+30}_{-15} J/sr in Raman light.

In comparison, the spectrum for a tantalum disk irradiated with a 2.2-ns, 4-kJ pulse having an intensity of 4.6×10^{14} W/cm² shows significant Raman scattering only at wavelengths much shorter than $2\lambda_0$; the spectrum falls off rapidly for wavelengths longer than $1.8 \mu\text{m}$ (Fig. 7-54). We expect in large, cool, high-Z plasmas that the longer wavelength Raman light will be absorbed before it can escape the plasma. This effect should not be so severe for the hotter, smaller plasma formed in the 3.25-kJ,

600-ps, 3.3×10^{15} -W/cm² experiment (Fig. 7-53). These targets were tilted 45° with respect to the lens cluster axis; the spectrograph looked at 25° to the target normal while the pyroelectric detector looked at 44° to the target normal.

The pyroelectric detector on this shot measured 140^{+140}_{-70} J/sr in Raman light. The deconvolved signal from the pyroelectric detector (Fig. 7-55) shows pronounced structure, as expected, since the target was irradiated in Gatling-gun fashion. The

▲ Fig. 7-54. Raman light spectrum for a tantalum disk irradiated with the upper 10 beams of Shiva.

Fig. 7-53. Raman light spectrum from a layered disk irradiated with the upper 10 beams of Shiva.

Stimulated Raman Scattering in Large Plasmas

10 upper Shiva beams were staggered in time by pairs, with each successive pair of 600-ps pulses arriving approximately 550 ps later, to produce a rectangular irradiation pulse at the target. The narrow Raman light signal in Fig. 7-55 is shown for a time reference. It is the deconvolved Raman light signal from another experiment. The overlaid Gaussian-shaped pulses later in time in Fig. 7-56 are fiducial signals, which are obtained from a photodiode that samples one of the

Fig. 7-55. Deconvolved signals from a fast P5-01 pyroelectric detector.

Fig. 7-56. Calculated time dependence of the laser power on target.

incident laser beams. This fiducial signal is wider than the laser pulse due to the relatively slow time response of the photodiode. Figure 7-56 shows the calculated laser power on target. The calculation used the actual beam energies and laser pulse width. The time scale is defined so the peak power of the first pair is at $t = 0$. The power is low early in the pulse because one beam of the first pair failed. The actual beam energies and delay times were used in calculating the curve in Fig. 7-56.

The comparison of two shots in Fig. 7-55 proves the Raman light is most intense late in the 2.2-ns irradiation period. The laser power was also somewhat higher during this time (Fig. 7-56). The fiducials from the two shots have been overlaid so that the relative timing can be compared. Neither the optical delay of the laser beam used for the fiducial signal nor the optical delay of the first pair of laser beams incident on the target was changed for the 2.2-ns experiments. Thus, the first pair of laser beams in the 2.2-ns experiments should have irradiated the target at the same time relative to the fiducial as all 10 beams for the 600-ps experiment. We see that the large peak in the 2.2-ns shot occurs 2.1 ns after the peak in the 600-ps experiment. Since the last pair of beams is delayed 2.14 ns relative to the first pair, the Raman instability is strongest during the last period of irradiation. This result is not surprising because the plasma has the longest scale length at that time. It is possible that the Mylar shield that was in place near the target enhances the Raman scattering, since the Raman light can be reflected from the Mylar shield and make a second pass through the irradiated tantalum-plasma "Raman amplifier."

Very little Raman light was observed during the first period of irradiation. Not only was the plasma scale length smallest in that period but also the intensity was only one-half as great then, since no energy was obtained from one beam of the first pair, as mentioned earlier. The first detected Raman peak arrives about 550 ps after the Raman-light peak for the 600-ps shot, so we can associate this peak with the second pair of beams. The middle Raman light peak in Fig. 7-55 corresponds with the middle peak in the laser power on target (Fig. 7-56).

We irradiated six tantalum disks with 2.2-ns, 4-kJ laser pulses, each with an

intensity of $5 \times 10^{14} \text{ W/cm}^2$, and we observed about the same level of Raman scattering on all of them. The hard x-ray spectrum measured by the filter/fluorescer has a hot (40-keV) tail. The level at 50 keV is about 10^{13} keV/keV , implying that at least 40 J are in a 40-keV Maxwellian distribution of suprathermal electrons, assuming the electrons were collisionally slowed in gold. The actual energy in suprathermal electrons will be larger, since they can lose some of their energy to fast ions rather than to collisional slowing and since there was much lower-Z material around which could have stopped some of the high-energy electrons.

Argus Green-Light Experiments

Raman light measurements have also been made for the 5320-Å green-light experiments carried out on gold disks at the Argus laser facility (Fig. 7-57). These measurements were made with an array of silicon PIN 6/LC photodiodes, which are made by United Detector Technology. The diodes were reverse-biased by 45 V, and the signals went into charge integrators. The 5320-Å laser light was blocked with Schott RG610 red sharp cut-on color filters. The interference filters have a 125-Å FWHM nominal bandpass and are fully blocked to 0.01%. Shielding against x rays was provided by a lead-glass window, with a lead-equivalent thickness of 0.125 in., and by a photodiode housing made out of a tungsten alloy. The experimental results shown in Fig. 7-57 are atypical, in that we chose a shot where the Raman light signal was relatively large. The gold disk was irradiated at about 10^{15} W/cm^2 with 32 J in about 600 ps. The lens was f/2, the laser light was linearly polarized, and the disk was tilted 10° in the plane of polarization. One ring of photodiodes looked in the plane of polarization, and another ring of photodiodes looked out of the polarization plane. Most of the diodes looked at light coming back at 25 or 30° to the laser beam. The angles, θ_N , in Fig. 7-57 specify how far away from the target normal the photodiode looked. The data show that the Raman scattering occurs at very low electron density and that there is an extremely strong polarization dependence. Such a strong polarization dependence would only be expected for sidescatter.

Comparison with Theory

Here we present our conclusions about where the Raman scattering is occurring, whether backscattering or sidescattering predominates, and what the growth lengths are.

The coupled mode equations for Raman scatter are^{61,62}

$$\left(\frac{\partial^2}{\partial t^2} + 2\gamma_R \frac{\partial}{\partial t} - c^2 \nabla^2 + \omega_{pe}^2 \right) \tilde{A}_1 = \frac{-4\pi e^2}{m_e} (n_e \tilde{A}_0)_{\text{transverse}} \quad (3)$$

and

$$\left(\frac{\partial^2}{\partial t^2} + 2\nu_L \frac{\partial}{\partial t} - 3v_{te}^2 \nabla^2 + \omega_{pe}^2 \right) n_e = \frac{n_0 e^2}{m_e^2 c^2} \nabla^2 (\tilde{A}_0 \cdot \tilde{A}_1)_{\text{longitudinal}} \quad (4)$$

where ω_{pe} is the electron plasma frequency; n_0 is the equilibrium density; n_e is the fluctuation in electron density caused by the epw; m_e is the electron rest mass; e is the electron charge; $\tilde{A}_0$ and $\tilde{A}_1$ are the vector potentials for the incident and Raman-scattered wave, respectively; c is the speed of light; and v_{te} is the electron thermal velocity. Units are unrationalized cgs, and the Coulomb gauge is used.

We assume the plasma is only weakly inhomogeneous and that the epw is strongly damped. By weakly inhomogeneous and strongly damped, we mean that the epw is

Fig. 7-57. Raman light spectrum for a gold disk irradiated with green light.

locally driven, and the Raman instability is convective or spatially growing, rather than absolute or temporally growing. We can then solve for the amplitude, n_e , of the epw anywhere if we just know the local fields A_0 and A_1 . We assume the fields to have the local harmonic dependence

$$\tilde{A}_0(\vec{r}, t) = \text{Re} \left\{ \tilde{e}_0 \tilde{A}_0 \exp [-i(\omega_0 t - \vec{k}_0 \cdot \vec{r})] \right\}, \quad (5)$$

$$\tilde{A}_1(\vec{r}, t) = \text{Re} \left\{ \tilde{e}_R \tilde{A}_1 \exp [-i(\omega_R t - \vec{k}_R \cdot \vec{r})] \right\}, \quad (6)$$

and

$$n_e(\vec{r}, t) = \text{Re} \left\{ \tilde{n}_e \exp [-i(\omega^* t - \vec{k}^* \cdot \vec{r})] \right\}. \quad (7)$$

The tilde denotes a complex quantity; an asterisk superscript means the complex conjugate is to be taken. The fields $\tilde{A}_0$, $\tilde{A}_1$, and $\tilde{n}_e$ are assumed to be slowly varying functions of position and time. We then obtain

$$\tilde{n}_e(\omega^*, k^*) = \frac{-k^{*2} \tilde{A}_0^* \tilde{A}_1 / 2 \tilde{e}_0^* \cdot \tilde{e}_R}{\omega_{BG}^2(k^*) - \omega^{*2} - 2i\nu_L \omega^* - 6i\nu_{te}^2 \text{Im} \tilde{n} \cdot \tilde{n}_R} \quad (8)$$

The quantity $\text{Im}(k)$ is the amplitude growth per unit distance for the Raman light wave. Its effect on the resonance denominator in Eq. (8) is usually small, and we will drop it. The vectors $\tilde{e}_0$ and $\tilde{e}_R$ are the unit electric polarization vectors, while $\tilde{n}_R$ and $\tilde{n}^*$ are unit vectors in the direction of $\vec{k}_R$ and $\vec{k}^*$, respectively. The angular frequency $\omega_{BG}(k^*)$ is the Bohm-Gross frequency for an epw with wave number k^* . From Eqs. (3) through (8), we find the growth per wavelength to be

$$\begin{aligned} \frac{1}{\tilde{A}_1} \frac{\partial \tilde{A}_1}{\partial(s/\lambda_0)} &= \lambda_0 \text{Im} k = \frac{\pi}{4} |\tilde{e}_0 \cdot \tilde{e}_R^*|^2 \left(\frac{k^{*2}}{k_0 k_R} \right) \left(\frac{v_0}{c} \right)^2 \\ &\times \left(\frac{-i\omega_{pe}^2}{\omega_{BG}^2(k^*) - \omega^{*2} - 2i\nu_L \omega^*} \right) \end{aligned} \quad (9)$$

Here, s is the path length along the ray path for the Raman light wave, and v_0 is the unswelled oscillatory velocity.

If the epw is resonantly driven, the growth is

$$\begin{aligned} \frac{1}{\tilde{A}_1} \frac{\partial \tilde{A}_1}{\partial(s/\lambda_0)} &= \frac{\pi}{8} |\tilde{e}_R^* \cdot \tilde{e}_0|^2 \\ &\times \left(\frac{k^{*2}}{k_0 k_R} \right) \left(\frac{\omega_{pe}}{\omega^*} \right) \left(\frac{v_c}{c} \right)^2 \left(\frac{\omega_{pe}}{\nu_L} \right). \end{aligned} \quad (10)$$

This result is a factor of 2 lower than that of Forslund, Kindel, and Lindman,⁷¹ but their paper assumed circularly polarized light rather than linearly polarized light and defined v_0 as the circular velocity of the electrons. Their gain coefficient is larger, since two orthogonal, linearly polarized electric fields drive the same epw.

Our data suggest that Raman sidescatter is at least as important as Raman backscatter. Looking at the expression for the growth rate, we would at first think backscatter would predominate due to the factor $k^{*2}/(k_0 k_R)$. Backscatter gives the largest epw number, k^* , and the smallest Raman light wave number, k_R . For sidescatter, though, the epw has a higher phase velocity and, consequently, is less Landau-damped. Also, for a normally irradiated disk, sidescatter may have a much longer interaction length than backscatter. The epw will cease to be resonantly driven if the electron density changes by a fractional amount, $\Delta N_e/N_e$, about equal to twice the fractional Landau damping, ν_L/ω_{pe} . By propagating transversely to the density gradient, the Raman light wave may see an almost constant electron density. Of course, the actual interaction length is determined in a complicated fashion by refraction of the Raman light wave, the finite spot size, curvature of the plasma-density contours, and plasma turbulence.

An estimate of the intensity e-folding growth length can now be made. Assuming sidescatter at one-tenth critical density, we find the intensity gain coefficient to be

$$\begin{aligned} \frac{1}{|\tilde{A}_1|^2} \frac{\partial |\tilde{A}_1|^2}{\partial(s/\lambda_0)} &\equiv 1.2 \left(\frac{\omega_{pe}}{\nu_L} \right) \left(\frac{\lambda^2}{1.37 \times 10^{18} \text{ W} - \mu\text{m}^2/\text{cm}^2} \right) \end{aligned} \quad (11)$$

The last expression in parentheses is v_0^2/c^2 . The Raman gain coefficient is small, and hundreds of wavelengths of underdense plasma are typically required for the instability to go.

The Raman light spectra strongly suggest that the Raman light we observed originated from sidescatter. Figure 7-58 compares the

solutions to the dispersion equations for sidescatter and backscatter for $\theta_e = 5$ keV. We believe that θ_e cannot be much below 5 keV in the experiments conducted at 5×10^{14} W/cm² and 2.2 ns. Each point represents a computer solution of the dispersion relations for the three waves, demanding conservation of frequency and wave vector.

Instead of the Bohm-Gross approximation to the epw dispersion relation, the exact plasma dispersion integral⁷² has been used to calculate a complex angular frequency, ω^* , given the real wave number, k^* . The computer solution demands that the real part of ω^* plus the real part of ω_R sum to equal ω_0 . This is not quite correct. For a steady-state solution, the angular frequencies will be real, and it will be the wave vectors that have an imaginary part. Drake et al.⁷³ give the correct, but much more complicated, solution to this problem.

The crux of our argument for the occurrence of Raman sidescatter is that backscattered Raman light with wavelengths as short as observed would have to originate at an extremely low density. Even for a 5-keV background electron temperature, the electron plasma waves would be strongly damped. If the Raman light had a wavelength, λ_R , equal to 1.75 μ m, backscatter would have the Raman instability occurring at 0.066 critical density and would have the wave-breaking energy be 18 keV. The fractional Landau damping would be $\nu_L/\omega_{pe} = 0.25$, the intensity e-folding growth length would be 340 μ m for $1 - 5 \times 10^{14}$ W/cm², and λ_0 is 1.06 μ m. Since our spot size in the 2.2-ns experiments was only $600 \times 850 \mu$ m, it would seem the Raman instability would be below threshold for backscatter at $\lambda_R = 1.75 \mu$ m. For sidescatter, 1.75- μ m Raman light originates at 0.104 critical density. The fractional Landau damping is only $\nu_L/\omega_{pe} = 0.026$, and about 50 μ m of plasma are needed for an intensity e-folding. Five or ten intensity e-folding lengths are certainly possible in this case; however, the plasma through which the Raman light wave passes must be rather homogeneous. The epw will be nearly resonantly driven only if $\Delta N_e/N_e \gtrsim 2\nu_L/\omega_{pe}$. Thus, the electron density would have to be constant to $\pm 6\%$ over a distance of 250 to 500 μ m; it is difficult to see how this can be possible except for sidescatter.

The effect of refraction must, of course, be considered. For the scale lengths of many hundreds of micrometres expected in the experiments conducted at 5×10^{14} W/cm² and 2.2 ns, refraction turns out to be negligible for densities below one-tenth critical density.

The radius of curvature, ρ , of a Raman light ray propagating transversely to the density gradient is given by

$$\frac{1}{\rho} = \frac{d}{dx} \sqrt{1 - \frac{N_e}{N_c(\lambda_R)}} / \sqrt{1 - \frac{N_e}{N_c(\lambda_R)}} \quad (12)$$

where $N_c(\lambda_R)$ is the critical electron density for light of wavelength λ_R , and x is the distance along the density gradient. If the ray bending angle over a distance $\ell/2$ is small, we have, to good approximation,

$$\Delta x \approx \frac{\ell^2}{8\rho} \quad (13)$$

We have specified a distance $\ell/2$ rather than ℓ because, presumably, the ray path is symmetrical about its turning point.

We also then have

$$\frac{\Delta N_e}{N_e} \approx \frac{\Delta x}{L} \approx \frac{\ell^2}{8\rho L} \quad (14)$$

If we now set $\Delta N_e/N_e$ equal to $2\nu_L/\omega_{pe}$, we find

$$\ell = \sqrt{32 \left(\frac{\nu_L}{\omega_{pe}} \right) \left(\frac{N_c(\lambda_R)}{N_e} \right) \left[1 - \frac{N_e}{N_c(\lambda_R)} \right]^{1/4}} \quad (15)$$

Fig. 7-58. Raman light wavelength for both side scatter and backscatter as a function of electron density.

Picking $\lambda_R = 1.75 \mu\text{m}$, $N_e = 0.104 N_c(\lambda_0)$, $\nu_L/\omega_{pe} = 0.03$, and $L = 500 \mu\text{m}$, we find that the maximum interaction length, ℓ , turns out to be $850 \mu\text{m}$, and the radius of curvature, ρ , of the Raman light ray turns out to be 3 mm . It does not matter, of course, whether it is refraction that causes the Raman light to curve away from the plasma or whether it is the plasma density contours that curve away from the Raman light ray. Either way, the Raman light ray still leaves the interaction region. The value for $1/\rho$ to use in Eq. (14) is the sum of these two curvatures.

Summary

The Shiva experiments demonstrate that the Raman instability can be several percent efficient, even at an intensity of $5 \times 10^{14} \text{ W/cm}^2$ for $1\text{-}\mu\text{m}$ laser light, when the plasma and the laser spot size are sufficiently large. We have also found experimentally that Raman scattering can occur not only near quarter-critical density but also at much lower densities. Indeed, little Raman light may be seen near $\omega/2$ simply due to absorption.

The $2\omega_{pe}$ instability also produces energetic electrons and is expected to become more significant with larger plasmas and larger laser spot sizes. We have not looked for the $2\omega_{pe}$ instability in these experiments, but this instability certainly should be studied in future experiments. W. L. Kruer et al.⁶⁹ report a two-dimensional particle code simulation in which the plasma went from 0.195 to $0.235 N_c$ in $25\lambda_0$. The background electron temperature was 3 keV , and the $1\text{-}\mu\text{m}$ laser light was normally incident with an intensity of $3 \times 10^{15} \text{ W/cm}^2$. The $2\omega_{pe}$ instability caused a large fraction of the 32% absorption.

We hope and expect the instabilities in the underdense plasma will be below threshold with ultraviolet laser light. At shorter wavelengths, the Raman gain coefficient will be smaller, and collisional damping for both the Raman light wave and the electron plasma wave will be much higher. Estabrook et al.⁷⁴ pointed out that, even in an infinite homogeneous plasma slab, the Raman instability may be stabilized by inverse bremsstrahlung absorption. (See also "Theory and Simulation of One-Dimensional Raman Forward Scatter" in Section 3.)

Author: D. W. Phillion

Major Contributor: D. L. Banner

Space-Time-Resolved X-ray Measurements from Accelerated Disk Targets

We designed a series of experiments to demonstrate the capabilities of our new axisymmetric streaked x-ray microscope (ASXRMS) (see "22X Microscope Streak Camera" in Section 5) and to use the new time-resolved imaging capability provided by the ASXRMS to study the dynamics of laser-target interactions. This series was divided into

- Observation of gold disks in self-emission.
 - Observation of aluminum disks both in self-emission and with x-ray backlighting.
- The results of these experiments contain a wealth of information on laser absorption, energy transport, and x-ray emission.

Gold-Disk Irradiation Experiments

Using the Shiva laser, we irradiated three $600\text{-}\mu\text{m}$ gold disks at normal incidence with 600-ps pulses at intensities ranging from approximately 7×10^{14} to $3 \times 10^{15} \text{ W/cm}^2$. The disks were observed with the ASXRMS at x-ray energies of 1.5 keV .

A relatively narrow region of x-ray emission was seen to form at the surface of the disk early in the pulse. This region then moved from the original surface position toward the incident laser beam at nearly constant velocity, and a region of negligible x-ray emission appeared between the emitting region and the original disk surface position. Figures 7-59 and 7-60 are iso-intensity contour plots in space and time of the ASXRMS data at $7.7 \times 10^{14} \text{ W/cm}^2$ and at $3 \times 10^{15} \text{ W/cm}^2$, respectively. The experiment parameters and results for three shots in this series are summarized in Table 7-10.

One striking feature shown in Figs. 7-59 and 7-60 is that the velocity of the peak of the x-ray emission region is essentially constant during the laser pulse. This behavior is unusual because simple physics models and one-dimensional numerical calculations (described later) of the plasma blow-off predict the velocity to be a function of the instantaneous laser intensity. The velocity data from the three gold-disk shots are shown in Fig. 7-61. The circles with error bars are the plasma velocities plotted as a function of peak laser intensity; the solid lines show the constant velocity of the x-ray emission region as a function of instantaneous laser intensity for each disk; and the dashed line is a least-squares fit to the data points for velocity vs peak laser intensity, which gives $V \propto I_p^{0.44 (+0.22)(-0.17)}$, where I_p is the peak incident laser intensity. A simple analytical model, described later, predicts a velocity dependence of $V \propto I_p^{0.45}$; again, however, the model indicates that the velocity should be a function of the instantaneous rather than the peak laser intensity.

The width of the x-ray emission region exhibits a behavior similar to that described for the velocity. Figure 7-62 shows the FWHM of the x-ray emission region as a function of time for each of the three disks. The two disks shot at near 10^{15} W/cm² show no variation of the FWHM, whereas the disk shot at 3×10^{15} W/cm² shows a significant variation in FWHM during the pulse. If we assume that the peak of the x-ray emission coincides with the peak of the laser pulse, a power-law dependence, $W \propto I_p^{0.16}$, can be derived for the FWHM of the x-ray emission region as a function of instantaneous laser intensity, I_i , for the 3×10^{15} -W/cm² shot.

Figure 7-63 shows the FWHM data plotted as a function of laser intensity, I . The circles with error bars are the peak FWHM plotted at peak laser intensity; the solid lines show the instantaneous FWHM as a function of instantaneous laser intensity; and the dashed line shows a power-law least squares fit to the data for peak FWHM vs peak laser intensity, $W_p \propto I_p^{0.7 \pm 0.25}$.

Again, we find that a simple model, described later, predicts a $W \propto I^{0.6}$ dependence for the FWHM of the x-ray emission region. However, we also find again that we would expect the intensity used in the simple model to be the instantaneous intensity rather than the peak intensity. At

Fig. 7-59. ASX RMS ▲ isointensity contour plot of data from a gold-disk shot at 7.7×10^{14} W/cm².

Fig. 7-60. ASX RMS isointensity contour plot of data from a gold-disk ▼ shot at 3×10^{15} W/cm².

Table 7-10. Gold-disk experiment ▼ parameters and results.

Shot	1	2	3
Laser energy (J)	426	480	4405
Laser pulse length (ps)	460	564	625
Laser intensity (10^{14} W/cm ²)	$7.7 \begin{cases} +2 \\ -1.6 \end{cases}$	$11.4 \begin{cases} +6 \\ -5 \end{cases}$	$30.0 (\pm 2)$
Absorption (kJ)	—	—	$1.4 (\pm 31\%)$
X-ray pulse length (ps)	758	702	861
Velocity XER ^a (10^6 cm/s)	7.2 ± 0.6	7.6 ± 0.6	12.8 ± 0.6
FWHM XER (μ m)	25 ± 4	23 ± 4	56 ± 4
Peak x-ray intensity ^b (10^{29} keV/cm ² ·s sphere)	2.3	2.4	1.5

^aXER = x-ray emission region.

^bPeak intensity (in both time and space) of the x-ray emission region.

this time, we have no explanation of why the velocity and FWHM of the x-ray emission region depend on the peak laser intensity, but only weakly, or not at all, on the instantaneous laser intensity.

We also examined the brightness of the x-ray emission region as a function of time during the laser pulse. Figure 7-64 shows the peak spatially resolved brightness of the x-ray emission region vs time for the three disk

Fig. 7-61. Velocity of the peak of the x-ray emission region as a function of laser intensity.

Fig. 7-62. FWHM vs time for the x-ray emission regions of three gold-disk shots.

Fig. 7-63. Summary of width of x-ray emission region vs laser intensity. ▶

shots. Here again, we find an unanticipated behavior: the shot at 3×10^{15} W/cm² shows a lower brightness at 1.5 keV than the two shots at $\sim 1 \times 10^{15}$ W/cm². Although the behavior shown in Fig. 7-64 is seemingly in contrast with the general trend of previous x-ray diode data, which show increasing x-ray emission with increasing laser intensity, this behavior is, in fact, not inconsistent with the previous data. Although the x-ray brightness of the emission region has decreased, the size (FWHM) of the region has increased more than enough to compensate for the decrease in brightness. Thus, the total integrated x-ray fluence that is emitted increases with laser intensity when the emission region is observed edge-on.

A sharp change in the temporal behavior of the x-ray emission fluence from gold disks at laser intensities between 0.5 and 3×10^{15} W/cm² has been observed previously⁷⁵ with the Dante time-resolved x-ray spectrometer.⁷⁶ McClellan et al. found that, when the laser intensity was increased from 5×10^{14} to 3×10^{15} W/cm², the x-ray emission pulse from gold disks became flattopped, apparently as the laser intensity crossed a certain threshold. When the Z of the disk targets was varied, a systematic variation was noted in the threshold intensity at which the break in the pulse shape occurred. With the pulse-shape data and other evidence, McClellan et al. attributed this behavior to the onset of severe flux inhibition.

Our data were taken under irradiation conditions similar to those in the above Dante experiments. As mentioned, we too observe a temporal flattening of the peak x-ray emission, although, when the emission region is viewed edge-on, the change in FWHM more than compensates for the

decrease in x-ray brightness at 3×10^{15} W/cm². When the emission region is viewed at near-normal incidence (as in the Dante measurements of McClellan et al.), no significant change in emission area would be expected; this would cause the Dante to observe the same flattopped, lower-intensity x-ray pulse that was observed by the ASX RMS (Fig. 7-64) at 3×10^{15} W/cm², as, indeed, it did.

The gold-disk irradiation experiments produced data in the form of self-emission space-time plots. These data are quite rich in their spatial and temporal information, and they have the potential of teaching us a great deal about the detailed physics processes occurring in laser-plasma interactions. The behavior of the 1.5-keV x-ray emission region is governed by the spatial and temporal evolution of the density, temperature, and ionization-state profiles. These, in turn, are governed by laser-absorption and energy-transport processes which, at present, are not well understood. Thus, by studying the 1.5-keV emission profiles through complex simulation modeling, we can attempt to learn about the more basic processes that govern the behavior of these profiles.

Before discussing the simulations, we note a striking fact: an extremely crude model of the physics of the laser-plasma interactions reproduces the observation that the velocity of the emission region scales as $I^{0.44 \pm 0.20}$. The model assumes that electron thermal conduction transports energy from the laser-absorption region (at critical density and below) to the overdense plasma. Since dense material radiates more efficiently than less-dense material at a given temperature, the emission peaks at the highest density reached by the thermal-conduction front. (Deeper into the disk, the plasma is even denser, but is too cool to radiate efficiently.) The model further assumes that the heated peak-emission region is expanding outward (toward the laser) at the ion sound speed, which scales as the square root of total pressure divided by density. Thus, $C_s \sim (P/\rho)^{1/2} \sim (\bar{Z}T)^{1/2}$. Equations of state for gold indicate that, for T less than 1 keV, $\bar{Z} \approx 1.6 [T(\text{eV})]^{1/2}$. Thus, the sound speed will scale as $T^{3/4}$.

The final assumption we make is that the temperature, which is falling rapidly near the thermal front as it propagates into the dense plasma, is proportional to the

temperature in the source region where the laser light is absorbed. That temperature has been shown⁷⁷ to scale as $I^{4/7}$ from theoretical arguments and as $I^{0.6}$ from experimental evidence,⁷⁷ where I is the instantaneous laser intensity; the empirical scaling agrees quite closely with the theoretical prediction. Thus, the peak velocity of the emission region should scale as $(I^{0.6})^{3/4}$, or $I^{0.45}$, which is the value deduced from the experiments. This crude model does not predict the observation that this velocity is constant throughout the laser pulse.

The actual velocities measured were in the 1×10^7 cm/s range. Since the model equates this velocity with a sound speed, the velocity corresponds to a temperature in the emitting region of about 500 eV. This temperature is quite reasonable in two respects: it is high enough to produce the 1.5-keV radiation that we detect; and it is about a factor of 10 lower than the hotter source temperature⁷⁸ in the underdense plasma. These two considerations support our view that the emission region is composed of the dense plasma just reached by the thermal front.

The second observation that can be dealt with in a very crude fashion is the width of the emission region, which was found to scale as $I^{0.7 \pm 0.25}$. If we determine the depth of penetration, d , of a thermal conduction front and assume that the emission width will scale with d , we find that equating $n\partial T/\partial t \sim nT/\tau_L$ with $\nabla \cdot \mathbf{q} \sim \nabla \cdot (nT \tau_{ei}/m) \cdot \nabla T \sim T^{7/2}/d^2 Z$ gives (with $Z \sim$

Fig. 7-64. Absolute peak x-ray emission vs time.

$T^{1/2}$), $d \sim T\tau_L^{1/2}$. Here, n , T , τ_L , q , and d are the density, temperature, laser duration, heat flux, and heat diffusion depth, respectively. Thus, at fixed τ_L , $d \sim T$. As before, we invoke the $T \sim I_L^{0.6}$ scaling; thus, $d \sim I_L^{0.6}$, as observed, but, again, d is dependent on the instantaneous rather than the peak laser intensity.

Since the crude model cannot account for all the observed behavior (e.g., the dependence of the spatial width principally on the peak laser intensity and weakly or not at all on the instantaneous laser intensity), we performed complex LASNEX simulations. The modeling was performed in two dimensions because refraction of the laser rays may be an important effect. The cooler plasma, which is heated by refracted laser light and which blows off the face near the disk edge into the line of sight of the diagnostic instrument, could be optically thick to the 1.5-keV x rays; thus, this plasma could obscure portions of the emission region emanating from the central laser-heated spot. The simulations were performed with the "standard" LASNEX physics model, which includes inhibited thermal transport (flux limiter = 0.03), non-LTE ionization physics, and emission opacities multiplied by 0.5 to somewhat reduce the total x-ray emission. The absorption package includes classical inverse bremsstrahlung and legislates that 20% of the laser energy that reaches the critical density be converted into hot electrons.

Once the simulation is complete, the data are processed with a code that allows us to simulate the ASXRMS by specifying its x-ray energy response, viewing angle, and spatial and temporal resolutions. We then

view the LASNEX-simulated plasma through a slit, streak it in time, and compare the results with the actual experiment. Figure 7-65 is an example of the computed 1.5-keV x-ray isoemission contours produced for the laser and target conditions corresponding to the 3×10^{15} -W/cm² experiment. Qualitatively, the figure resembles the experimental result. The calculated velocity of the emission region is about 1×10^7 cm/s, which is within 20% of the observed value. Similarly, a simulation of the experiment at an irradiation intensity of 7×10^{14} W/cm² shows a velocity of 5×10^6 cm/s, again within 20% of the observed value.

We are encouraged that the standard LASNEX model (described above) qualitatively reproduces the shape and speed of the emission profile, even though it does not quantitatively reproduce the width of the profile. By comparison, the LASNEX model that includes classical transport, rather than inhibited transport, does not reproduce either the qualitative shape or the speed, let alone the width, of the emission profile. This inability of LASNEX with classical transport to adequately match the observed emission is probably due to the inward energy transport being too fast, thus maintaining the emission region nearer the original face of the disk and effectively slowing it down.

It is quite time-consuming—which is to say expensive—to perform these two-dimensional LASNEX calculations. Consequently, we have not performed parametric studies to learn about the dependence of the emission behavior on various complicating effects, including detailed unknowns in opacities, laser pulse shapes, and laser spot sizes and refraction. In the absence of such knowledge, it is premature to rule out any particular physics model solely on the basis of its apparent inability to reproduce the emission behavior. The parametric dependence of emission on the various complicating effects will be studied in the coming year.

Aluminum-Disk Irradiation Experiments: Self-Emission and X-ray Backlighting

After our initial measurements of the x-ray emission dynamics of gold disks, we turned to x-ray backlit measurements of the motion

Fig. 7-65. LASNEX-generated 1.5-keV isoemission contours for gold disk irradiated at 3×10^{15} W/cm².

Space-Time-Resolved X-ray Measurements from Accelerated Disk Targets

of aluminum disks (slabs) accelerated by direct laser irradiation. (X-ray backlighting uses a laser-generated x-ray source and an x-ray camera to make a shadowgram of a laser fusion target. See "Backlighter Characterization Experiments" in this section.) The target configuration is shown

in Fig. 7-66, and a photograph of the target is shown in Fig. 7-67. The sample slab was mounted on a raised platform to ensure that the x-ray backlighter covered the region through which the sample would move, including its initial location. A 4- μm -thick Mylar shield, which has minimal attenuation

Fig. 7-66. Geometry of backlighting target for slab-acceleration experiments.

Fig. 7-67. Photograph of backlighting target for slab-acceleration experiments.

for 1.9-keV x rays, was placed between the backlighter source and the sample to protect the slab from scattered light and to attenuate the sub-keV x rays and fast electrons. The slit of the ASXRMS was aligned vertically, parallel to the laser-beam axis, so that the sample image would move along the slit as the sample accelerated. Taken together, the target design and the target alignment relative to the ASXRMS allowed simultaneous observation of both self-emission from the sample and the x-ray backlit shadow of the sample.

Selection of the target thickness and target material was the result of a compromise among the following:

- Low mass, to achieve high acceleration and velocity.
- Atomic number near that of typical ablaters and pushers.
- Thickness large enough to be resistant to preheat.
- Diameter small enough to have correct x-ray transmission characteristics, to minimize flatness and dimensional-

tolerance requirements, and to allow uniform irradiation of the entire sample.

- Diameter large enough to eliminate domination by two-dimensional effects.
- Ease of fabrication.

Balancing all the above considerations, we selected a 17- μm -thick aluminum slab for the sample to be accelerated.

The 10 upper laser beams of Shiva were used to irradiate the backlighter source, attached to the target, with a 2.8-ns pulse. We used tantalum as a backlighter source because ionized tantalum has a 1.9-keV x-ray line that falls just under the high-energy cutoff of the x-ray mirror used in the ASXRMS.

Figure 7-68 shows how the 2.8-ns backlighter pulse was formed by delaying the 10 upper Shiva beams in pairs so that the 600-ps pulses from each pair added to produce the longer pulse. (Note: the peak of the 600-ps drive pulse shown in Fig. 7-68 was chosen as the zero-time point.) The 10 lower Shiva beams were used to irradiate the aluminum sample with a 600-ps drive pulse, which was synchronous with the 600-ps pulse from the first pair of arms used for the backlighter pulse.

We were concerned about the uniformity of the backlighter source that was produced by delaying the beams in pairs. To provide temporal and spatial uniformity, the beams all had to have the correct energy and had to be correctly overlapped on the target. To determine the degree of uniformity of the backlighter, we carried out several

Fig. 7-68. Laser drive pulse and backlighter pulse for backlighting experiment.

Fig. 7-69. Backlighter characterization experiment.

backlighter characterization shots. One of these shots, in which the ASXRMS viewed the backlighting source directly, is shown in Fig. 7-69. Both spatial and temporal variations were apparent; however, they were not serious enough to impair the usefulness of this initial series of backlighting experiments.

We were able to improve the spatial and temporal uniformity of the backlighter during the series as we gained experience and improved our alignment techniques. In future experiments, the problem of spatial and temporal variations in the backlighter source will be eliminated by our ability to propagate pulses of different lengths in different laser chains. All arms used for the backlighter will be able to propagate the full-length backlighter pulse, while the other beams will propagate the shorter drive pulse. Thus, the spatial and temporal nonuniformities caused by stacking short pulses from different beams will be eliminated.

After characterizing the x-ray backlighting source, we examined the dynamics of x-ray self-emission from the aluminum sample. By separately examining the x-ray emissions from the backlighter and from the sample, we hoped to gain an unambiguous understanding of the image when both the sample and the backlighter were irradiated simultaneously. For an aluminum sample irradiated with a 600-ps pulse at 5.8×10^{14} W/cm², Fig. 7-70 compares a streaked image of the sample self-emission with a LASNEX simulation of the shot. Unlike the characteristics of gold disks, which were discussed earlier, the peak of the x-ray

emission region from the aluminum disk tends to stay fairly close to the surface of the disk, while a lower-density plume grows out in front of the disk. While we had some difficulty using LASNEX simulations to reproduce the detailed behavior of gold disks, we found that two-dimensional LASNEX (the standard model defined above) did very well at describing the time-resolved x-ray emission from the aluminum sample.

After separately characterizing the backlighter source and the self-emission from the aluminum sample, we simultaneously irradiated both the sample and the backlighter. Figure 7-71 shows the image obtained on one of these latter shots, together with an overlay indicating the original disk position and the predicted trajectory of the aluminum sample. Both one-dimensional LASNEX and a simple model predict approximately the same trajectory, which shows the same general velocity (8×10^6 cm/s) as that in the streak record; however, there are some deviations from the anticipated straightline behavior. Several explanations that may account for these deviations from linearity are

- Changes in backlighter intensity.
- Two-dimensional hydrodynamic effects.
- Suprathermal-electron fluorescence of the aluminum sample.
- Decompression of the sample due to preheat.

In Fig. 7-71, isointensity regions are displayed as a given color. Since the detected intensity is a function of both the backlighter intensity and the opacity of the sample, the

Fig. 7-70. Comparison of LASNEX-predicted, time-resolved self-emission with experimental results for aluminum-disk target shot.

location of an isointensity-isocolor region will shift with either a change in backlighter intensity or in sample opacity. The image in Fig. 7-71 shows an initially low backlighter intensity, with a sudden rise occurring about 1 ns after the start of the backlighter

Fig. 7-71. ASXRMS ▲ data from aluminum-slab acceleration experiment with x-ray backlighting.

signal. This increase in intensity is coincident with one of the deviations from linearity (feature A) in Fig. 7-71; therefore, feature A might be related to the increase in backlighter intensity.

A second explanation of feature A is related to the two-dimensional hydrodynamics of the aluminum sample. In an effort to produce uniform acceleration of the sample and to avoid bowing the sample surface during acceleration, we adjusted the laser spot size to overfill the sample disk. This technique was expected to provide a highly uniform distribution of intensity across the surface of the disk; however, we later discovered that, with uniform disk illumination, a plume quickly moves around the edge of the disk. Figure 7-72 shows this behavior in a two-dimensional LASNEX run, in which the laser is incident from the bottom of each part of the figure. Regions with densities above 0.3 g/cm³ (red, dark-green, and dark-blue contours) cause significant attenuation of 1.9-keV x rays. Figure 7-72(a) shows that the disk is relatively intact at early times. In Fig. 7-72(b), a plume of moderate density rushes past the edge of the disk, making the x-ray

Fig. 7-72. Two-dimensional LASNEX prediction of density contours for aluminum-slab acceleration experiment.

shadow move ahead quickly, as if due to sudden acceleration, and yielding the sharp change evident at 1.2 ns. In Fig. 7-72(c), the plume begins to decompress as it moves forward and expands. Finally, in Fig. 7-72(d), the plume continues to decompress and goes transparent as the disk moves forward and expands. This decompression and expansion produces an x-ray shadow that moves forward very slowly, giving the impression that the disk has decelerated, and yields feature B in Fig. 7-71.

A LASNEX simulation of the top 10 Shiva beams illuminating the backlighter with the Mylar shield showed no attenuation of the 1.9-keV backlighting photons by the shield, but it did show some attenuation of the soft x rays. However, enough soft x rays passed through the Mylar to shine on the back of the sample disk target and preheat it to about 30 eV. When this anomalous 30-eV preheat from the backlighter is considered along with a natural 10-eV preheat from hot electrons, which are generated by the main laser beam on the front of the sample disk and propagate through to the back of the sample, the simulation predicted a net 40- to 50-eV preheat on the cold side of the sample disk. These calculated preheat values are supported by actual preheat measurements, which show 10 eV without the backlighter and 50 eV with the backlighter. The same predictions for the electron preheat and the backlighter-caused photon preheat were also obtained by using the simple model. Although comparison of the experimental data with the LASNEX simulation does not show precise temporal agreement for features A and B, the shape of the streaked image is qualitatively correct; therefore, the mechanism shown in Fig. 7-72 for explaining the shape in Fig. 7-71 is physically plausible.

Another hypothesis to explain feature A is that a burst of superthermal electrons from the backlighter might cause fluorescence of the K_{α} line of the aluminum sample. Since the ASXRMS cannot discriminate well between the 1.56-keV aluminum K_{α} radiation and the 1.9-keV backlighter radiation, the fluorescence would tend to appear as an increased sample brightness and shift the intensity contours, possibly yielding feature A. This explanation is plausible, but it is difficult to pinpoint a

mechanism to generate the required ~ 0.5 -ns burst of superthermal electrons that would produce feature A.

Another possibility for the production of feature B is simple decompression of the aluminum sample due to preheat. As the sample becomes underdense, the intensity contour shifts downward, making it appear as if the sample had simply slowed down.

The answers to some of the questions concerning the analyses both of the gold x-ray self-emission experiments and of the aluminum backlit experiments will have to await further experiments; nevertheless, it is clear that our new high-resolution, time-resolved imaging capability has produced stimulating new insights into the dynamics of laser-fusion targets.

Authors: R. H. Price, M. D. Rosen, D. L. Banner, and J. R. Zickuhr

Major Contributors: K. L. Andrus, T. Barbee (Stanford University), D. E. Campbell, A. Cappabianca, J. J. Garr, K. J. Haney, R. L. Hanks, D. L. Holeman, D. W. Hughes, M. W. Kobierecki, L. N. Koppel, W. B. Laird, H. Medeck, W. M. Ploeger, K. D. Poor, G. Random (Random Devices, Inc.), R. Rudd, T. L. Schwab, V. W. Slivinsky, J. B. Tassano, C. E. Thompson, T. Zehnpfenning (Visidyne, Inc.), and the Target-Fabrication Team

Backlighter Characterization Experiments

Introduction

As we progress towards higher-density implosions, x-ray backlighting emerges as one of the few diagnostic tools capable of measuring the symmetry and stability of imploding shells and the size of the compressed core. However, the very nature of the targets that we wish to diagnose, with their high-Z pushers and large areal densities,⁷⁹ requires x-ray backlighting energies far in excess of any used in previously reported experiments.⁸⁰ This article presents the results of a series of characterization

experiments that we conducted on some of the backlighting materials⁸¹ appropriate for near-term experiments.

Backlighter Sources

The selection of materials that we tested was guided—and limited—by several considerations; e.g.,

- Prominent x-ray lines are preferred over continuum radiation. The x-ray lines provide a high-intensity, spectrally resolved signal that facilitates discrimination against the target-induced background. The well-defined wavelength greatly simplifies interpretation of the data, since the variation in transmitted x-ray intensity is purely a function of the target areal density, $\rho\Delta r$ (the photon path along the line of sight of the instrument), instead of being convolved with an energy-dependent opacity.
- High-energy lines are required to probe high-density targets. Significant measurements on the baseline Nova target will require backlighting the target with photon energies of 8 keV or more, while backlighting of Shiva and Novette targets can be done with 4.6-keV titanium lines. (See “Evaluation of X-ray Backlighting for Novette- and Nova-Class Targets” in Section 5.)
- Ease of handling and of procuring the backlighting target material is also an important consideration.
- Materials for which we have information from previous experiments⁸² were preferred so that we could maximize the extent of parameter space explored while minimizing the number of laser shots required.

For our series of backlighter characterization experiments, we selected titanium, nickel, and zinc as backlighter materials. In addition, we cursorily investigated the 1.8-keV M lines of hafnium because these lower-energy lines match the capability of the 22× Wolter microscope, which has been used for backlighting accelerating disks⁸³ (see “Space-Time Resolved X-ray Measurements from Accelerated Disk Targets” in this section).

Parameter Space

For the selected backlighters, we were primarily interested in determining the x-ray line conversion efficiency as a function of the laser-pulse duration, τ_L , and of the laser intensity on target, I_L . We also sought to determine the spatial and temporal characteristics of the x-ray emission relative to the corresponding laser parameters. By doubling and tripling the frequency of our basic 1.06- μm beam, we obtained preliminary data on the dependence of emission on laser wavelength.

The usefulness of a backlighting diagnostic hinges, in large part, on the amount of laser energy, E_L , required for the backlighter. For high-energy x-ray line emission, this laser energy can become significant, since line production exhibits a laser-intensity threshold which increases with line energy. The duration of the laser pulse also plays a significant role. Long pulses create hot plasma, and this plasma produces copious quantities of highly ionized atoms that radiate He- and Li-like lines. Short pulses produce suprathermal electrons which, by interacting with cold matter, induce fluorescence lines that dominate the radiated x-ray spectrum.

We are considering two basic methods of backlighting diagnostics, and a knowledge of the spatial, spectral, and temporal behavior of a particular line-emission source is necessary to determine how to match the source and the diagnostic scheme. The first method, described in “22× Microscope Streak Camera” in Section 5, provides temporally resolved information and requires a long-duration backlighter. The second method, described in “Point Imaging with X Rays (PIX)” in Section 5, is designed to obtain well-defined two-dimensional images by using very short backlighting flashes to freeze the motion of the imploding shells. This short-pulse technique prompted our interest in the duration of the x-ray line emission relative to the duration of the laser pulse.

Different imaging systems impose different requirements on the backlighter, e.g., that the backlighter be a point source (if PIX were used) or that it be an extended region (if a zone plate camera were used). Whether the latter option is viable depends

on the relative sizes of the target and backlighting regions.

Our main goal in this series of backlighter characterization experiments was to determine the emission characteristics of x-ray sources that are useful for backlighting purposes. However, the experiments also provided data on other parameters that are characteristic of the interaction of a laser beam with targets having different atomic numbers. Broadband x-ray spectra were obtained at both low (<2-keV) and high (up to 350-keV) energies, and the light scattered around 2λ (where $\lambda = 1.06 \mu\text{m}$ for our experiments) was analyzed.

Experimental Setup

The 10 upper beams of the Shiva laser were used to irradiate disk targets of the candidate backlighter materials. These targets were nominally $1000 \mu\text{m}$ in diameter and $25 \mu\text{m}$ thick and were tilted at 45° to the axis of the laser-beam cluster to optimize lines of sight for the diagnostic instruments.

The primary diagnostics used in these experiments were

- A crystal spectrometer that was designed to measure line emission in the appropriate range, from around 1.8 keV for hafnium to around 9 keV for zinc, at 21° from the target normal.
- The x-ray streak camera, which monitored the duration of x-ray emission at 32° from the target normal.
- A zone plate camera, located at 21° from the target normal, that was used to determine the camera response for various ratios of backlighter-to-target sizes.
- Two x-ray microscopes, located at 45° and 48° from the target normal in two orthogonal planes, that monitored the extent of the x-ray emission region below 2 keV. These microscopes provided an indication of where the laser beams were aligned on the target.

The Shiva laser was operated in two different configurations. For the long-pulse experiments, we tuned the oscillator to produce $\tau_L = 600 \text{ ps}$ (FWHM of a Gaussian pulse), we adjusted the laser amplifiers to vary the laser energy on target from 500 to 3800 J, and we varied the size of the laser beams to produce incident laser intensities

on the target ranging from 10^{14} to 10^{17} W/cm^2 . For the short-pulse experiments, we tuned the oscillator to produce nominal $\tau_L = 100 \text{ ps}$, we varied the laser energy on target from 200 to 900 J, and we spanned the range of laser intensities from 10^{14} to 10^{17} W/cm^2 .

Conversion Efficiencies

We define a conversion efficiency, ξ_x , for an x-ray line emitter as the number of photons per line, or line cluster (Fig. 7-73), divided by the incident laser energy. Conversion efficiencies are obtained by summing the contribution of all lines, as shown on Fig. 7-73. For all the materials and laser irradiation configurations tested during this experiment, $\xi_x \sim 10^{11}$ to 10^{12} photon/J. Typical energy-conversion efficiencies ($\eta_x = \xi_x \times \text{line energy}$) are shown in Table 7-11.

We irradiated two titanium disks at an intensity of $3 \times 10^{15} \text{ W/cm}^2$ with energies of 530 and 2380 J on target. (To maintain the same intensity on target for the different energies, we changed the size of the beams at

Fig. 7-73. Titanium K-shell x rays.

Target	$h\nu$ (keV)	I_L (W/cm^2)	τ_L (ps)	Energy conversion efficiency, η_x (%)
Ti	4.8	3×10^{15}	600	0.06
Ni	7.8	3×10^{16}	600	0.08
Zn	9.0	3×10^{16}	600	0.02

Table 7-11. Line-conversion efficiencies.

Backlighter Characterization Experiments

the target location.) In this pair of experiments, the measured conversion efficiencies (ξ_x) were 5.6×10^{11} photon/J at 530 J and 5.7×10^{11} photon/J at 2380 J. It thus appears that scaling of the line intensity with laser energy is linear.

Variations in ξ_x with I_L are best illustrated by the titanium data in Fig. 7-74, which were obtained over a wide range of laser intensities, pulse durations, and wavelengths. Whenever x-ray lines were observed, the conversion efficiency increased with decreasing laser intensity. At a given I_L , some slight differences were observed (within

error bars) among the data obtained at various laser wavelengths, with somewhat higher conversion efficiencies being observed for shorter wavelengths. However, again at a given I_L , no significant differences in ξ_x were seen when τ_L was varied from 100 ps to 2 ns at $\lambda = 1.06 \mu\text{m}$. The observed variation in ξ_x as a function of I_L is probably due to decreased laser absorption.

For a wavelength of $1.06 \mu\text{m}$ and $\tau_L = 100$ ps, no Ti lines were observed for $I_L < 3 \times 10^{16} \text{ W/cm}^2$, whereas, for $\tau_L = 600$ ps, line-emission data were obtained over the full range of I_L explored (from 3×10^{14} to $3 \times 10^{16} \text{ W/cm}^2$). We can speculate that some threshold laser intensity, I_T , exists at 600 ps as well, but that I_T lies below $3 \times 10^{14} \text{ W/cm}^2$ in this case. Interestingly, at $\tau_L = 100$ ps, the threshold for $0.53\text{-}\mu\text{m}$ light lies below 10^{15} W/cm^2 .

For the higher-energy backlighters (Ni and Zn), I_T , even at $\tau_L = 600$ ps, lies above 10^{16} W/cm^2 at $\lambda = 1.06 \mu\text{m}$; irradiations of Ni at intensities of 4×10^{14} and $3 \times 10^{15} \text{ W/cm}^2$ did not produce line emissions. Figure 7-75 shows the values of ξ_x that were obtained for Ni and Zn as a function of I_L . Because the energy required to produce an extended-region backlighter for Ni or Zn would be infeasibly large, it appears that these two backlighters will be useful only for systems requiring point sources (see "Point Imaging with X Rays (PIX)" in Section 5). However, preliminary experiments at $\lambda = 0.35 \mu\text{m}$ have shown that, for Ni at $\tau_L = 600$ ps, I_T has decreased to below $2 \times 10^{15} \text{ W/cm}^2$, while ξ_x remains essentially the same. Hence, shorter-wavelength lasers may

Fig. 7-74. Line-conversion efficiency as a function of laser intensity for Ti.

Fig. 7-75. Line-conversion efficiencies for Ni (7.6 keV) and Zn (8.6 keV).

be considered for backlighter irradiation when high-energy extended sources are required.

Within the limited set of available data, the maximum ξ_x obtained for each tested backlighter material decreases with x-ray line energy (Fig. 7-76). At $\lambda = 1.06 \mu\text{m}$, no significant differences are apparent between yields of K- and M-shell radiation; K and M emissions seem to follow the same trend of decreasing conversion efficiency with increasing line energy. However, K emission is preferred for backlighting purposes, since it provides a large line/continuum ratio.

In summary, within the parameter space investigated in this series of experiments, we found that ξ_x

- Is about 10^{11} to 10^{12} photons/J.
- Increases with decreasing laser intensity.
- Is weakly dependent on laser wavelength and nearly independent of laser pulse duration, except at threshold intensity.
- Is approximately zero below a threshold laser intensity, which increases with increasing laser wavelength, increasing atomic number of the target material, and decreasing laser-pulse duration.
- Increases with decreasing line energy.

Nature of Line Emissions

Two types of line emission occur when a target is irradiated with a laser beam: He-

and Li-like lines arising from highly stripped ions in a hot plasma (thermal lines); and K_α lines arising from essentially cold matter. The relative intensities of He- and Li-like lines and of K_α lines are functions of laser pulse length (τ_L), atomic number (Z) of the material being irradiated, and laser wavelength.

The effect of τ_L on line emission is shown in Fig. 7-77. A prominent nickel K_α line for $\tau_L = 100$ ps is contrasted with a much larger relative intensity of the He- and Li-like lines at $\tau_L = 600$ ps. For both shots illustrated in Fig. 7-77, the wavelength was $1.06 \mu\text{m}$, and the laser intensities were similar ($5 \times 10^{16} \text{ W/cm}^2$ at 100 ps vs $3 \times 10^{16} \text{ W/cm}^2$ at 600 ps). Similar results were found for the other materials tested. These results indicate that, as τ_L lengthens, the laser is more efficient at heating the plasma, and the volume of the highly ionized plasma increases, producing the intense thermal

Fig. 7-76. Maximum measured conversion efficiencies for various backlighters.

Fig. 7-77. Comparison of Ni spectra at different pulse lengths. ▼

Fig. 7-78. Ti spectra for $\blacktriangle$ different laser wavelengths.

Fig. 7-79. Ti K-shell x rays at $0.53 \mu\text{m}$.

lines. Conversely, at shorter τ_L , the high-intensity laser beam produces a large number of suprathermal electrons, which excite K_α lines in the cold matter,⁸⁴ while the short time scale limits the ionization of plasma into He- and Li-like states.

As the atomic number of the target material increases, the average energy of the electron-distribution function required to excite K_α line radiation also increases. The role of the suprathermal electrons in producing K_α line radiation may be seen by comparing the spectra of Ti and Ni (Figs. 7-73 and 7-77, respectively) obtained

under similar irradiation conditions. The ratio of suprathermal electron-induced K_α radiation to thermally induced He- and Li-like radiation was observed to be much larger for Ni ($Z = 28$) than for Ti ($Z = 22$), while, for Zn ($Z = 30$) only the K_α line was observed.

Spectral emissions as a function of laser wavelength are displayed in Fig. 7-78 for Ti. At the shorter wavelengths, all emissions are thermal (He- and Li-like) lines; the spectra show no sign of the cold K_α line that is seen at $\lambda = 1.06 \mu\text{m}$. The K_α lines are absent at the shorter wavelengths because the level of hot electrons decreases with decreasing wavelength (see "Suprathermal X Rays" in this section). Even at a pulse length that favors production of K_α lines ($\tau_L = 100 \text{ ps}$), no cold lines are detected (Fig. 7-79). As shown in Fig. 7-79, lines were obtained at $0.53 \mu\text{m}$ and 100 ps at an intensity where they could not be excited with $1.06\text{-}\mu\text{m}$ light.

The lowering of the threshold, I_T , for line production with decreasing laser wavelength may be related to a weakening of transport inhibition.⁸⁵ In addition, the increased electron density at the critical-density surface decreases collisional ionization time and, therefore, improves the probability of producing highly ionized and excited atoms that give rise to the He- and Li-like lines.

In summary,

- The x-ray spectra for Ni and Zn are strongly influenced by suprathermal electrons.
- At long laser pulses, He- and Li-like lines are dominant.
- At short laser pulses, cold K_α lines become significant with $1.06\text{-}\mu\text{m}$ irradiation.

- At laser wavelengths shorter than $1.06\ \mu\text{m}$, cold K_α lines are not detectable, substantiating the predicted decrease of hot electrons.

Temporal Behavior of X-ray Emission

Because the filtered x-ray streak camera⁸⁶ that we currently use is a broadband instrument that is not designed to distinguish between continuum and line emission, we are building a streaked crystal spectrograph to investigate the duration of x-ray line emission. The streak camera used for the present experiments had seven relatively broad channels ranging from 2.8 to 25.5 keV. Each line that was studied was contained in its own specific channel and could be detected by an increase in brightness of that channel relative to surrounding channels.

For Ni, the channel containing the line of interest showed a distribution in time that was more skewed than the distributions in the other channels (Fig. 7-80). In all shots, the high-energy x-ray channels ($h\nu > 4\ \text{keV}$) lagged the thermal channel ($h\nu \sim 2\ \text{keV}$) by 50 to 100 ps. The emission is more than twice as long as the laser pulse, except in the broad channel containing the line emission. The duration of the line emission itself might be even shorter than would be indicated by the envelope of the combined line and continuum emissions.

At a laser pulse length of 100 ps, the Ti lines, which were predominantly He- and Li-like lines, followed the thermal x-ray channel behavior, while the Ni and Zn lines occurred later in time (a few tens of picoseconds). The delayed timing of the Ni and Zn lines might imply a delay in suprathermal electron production; alternatively, the timing could be an indication that these electrons have traveled on the order of a millimetre in the corona before interacting with the cold matter. However, this delay in line production is not well understood at this time. In all cases, the FWHM of the x-ray emission exceeded the laser pulse duration. In the channel containing the emission lines, the FWHM x-ray emission $\cong 1.4$ to $2.4\ \tau_L$.

In general, the duration of the x-ray emission increased with intensity on target at a fixed Z, but decreased with increasing Z at a given intensity. Closer examination of the data (Fig. 7-80) suggests that the FWHM of the line emission might be somewhat shorter than the measured (continuum plus line) emission. However, the actual value of this FWHM cannot be determined until we can run experiments with the streaked crystal spectrograph.

At $\tau_L = 600\ \text{ps}$, only two shots yielded time information. Both of these shots showed an x-ray emission time that was approximately 25% shorter than the laser pulse duration. Since no absolute timing was available, we cannot state unambiguously when the x-ray emission occurred with respect to the laser pulse.

In summary,

- Onset of x-ray line emission appears to be delayed by a few tens of picoseconds for the higher-energy backlighters (lines produced by suprathermal electrons).
- Duration of the (broadband) x-ray emission exceeds the laser pulse duration by as much as a factor of 2 for short (100-ps) laser pulses.
- Duration of the (broadband) x-ray pulse was slightly shorter than the laser pulse for long (600-ps) laser pulses.

Fig. 7-80. Streak camera data for Ni irradiated at 100 ps.

Spatial Extent of X-ray Emission Region

So far, we have gathered little information on the spatial extent of the line-emission region in the plane of the backlighter, but we are planning additional experiments to obtain such information. Continuum x-ray emission in the 2-keV region was monitored with two x-ray microscopes, and, in this

energy region, the area of the emission region was found to closely match that of the laser spot. However, for backlighting purposes, the x-ray emission of interest is not in the thermal (2-keV) part of the spectrum. In particular, nickel and zinc lines, which are predominantly hot-electron generated when short laser pulses are used, could emanate from a much larger region than that directly irradiated by the laser.

The observed delay in x-ray line emission (mentioned above) is compatible with the

Fig. 7-81. Spatially resolved Ni spectrum.

Fig. 7-82. Spatially resolved Ti spectra. ▼

hypothesis that the lines are excited by electrons that have been reflected at some corona boundary and, therefore, could impact the target over a much wider area than the one in which they were generated. Indeed, zone plate camera data indicate that, at $\tau_L = 100$ ps, the x-ray emission region is larger than the nominal spot size. However, the image detected by the camera was that of a cold ball backlit by x rays, so the size of the x-ray emission area cannot be accurately determined; further experiments will be required to precisely measure this area.

On some shots, an imaging spectrograph was used to determine the spectral characteristics of the x-ray emission as a function of distance along the normal to the disk. The data obtained with the imaging spectrograph show a relatively large region of He-like line emission that compares well with computed estimates.⁸⁷ The cold K_α emission is confined to the disk surface, as would be expected from the hypothesis of hot electrons ionizing the cold matter.

For Ti at $\sim 4 \times 10^{14}$ W/cm², 1.06 μ m, and 600 ps, the measured x-ray emission FWHM was 125 μ m. At $\sim 3 \times 10^{16}$ W/cm², 1.06 μ m, and 600 ps, the nickel line (Fig. 7-81) exhibits a FWHM of 60 μ m. For these two cases, the laser spot sizes were 920 μ m and 100 μ m, respectively, on the target.

For identical laser intensities on target, identical wavelengths, and a laser spot size of ~ 100 μ m, the x-ray emission FWHM increases with laser pulse duration (Fig. 7-82). (Note: the length of emission scales slower than the duration of the laser pulse, but the FWHM for the short-pulse irradiation may be limited by the slit width of the spectrometer.) However, we do not know to what extent the observed increase in scale length is a genuine increase in plasma scale length and to what extent the observed increase is due to the smearing of a small emission region that traverses the viewing zone of our time-integrated instrument.

In summary,

- The thermal x-ray emission area matches the laser spot size.
- The x-ray line emission area in the plane of the disk may extend beyond the laser spot.
- For long (600-ps) laser pulses, the x-ray emission was observed to extend outward from the disk surface over a relatively large region.

Low-Energy X-ray Broadband Conversion Efficiency

During these backlighter characterization experiments, a Dante spectrometer⁸⁸ viewed the target at 55° with respect to the target normal, while another Dante had a 42° view. Figure 7-83 shows the dependence of the integrated x-ray flux (or total x-ray energy, E_x) on laser intensity for Ti, as measured by the Dante at 42°. Previous data for Au (Ref. 89) and the data shown in Fig. 7-74 display a slow decrease in x-ray continuum or line conversion efficiency with increasing laser intensity at long laser pulses (1000 ps); this decrease in conversion efficiency cannot be entirely ascribed to variations in absorbed energy.⁸⁹ As expected,⁸² the conversion efficiency increases with increasing Z , from 0.0018 J/sr/J for Ti to 0.0030 J/sr/J for Ni and Zn at laser intensities above 3×10^{16} W/cm². The value for Au at comparable conditions is 0.0065 J/sr/J. (All data in this paragraph were obtained with 1.06- μ m light.)

At short laser pulses (100 ps), the conversion efficiency for Ti is approximately constant with laser intensity and has a value close to that obtained at $\tau_L = 600$ ps for $I_L \sim 3 \times 10^{16}$ W/cm². Over the range of laser intensities investigated, we again observe an increase in conversion efficiency with Z , from ~ 0.0014 J/sr/J for Ti to ~ 0.0022 J/sr/J for Zn. X-ray spectral shapes were similar

Fig. 7-83. Conversion efficiency for broadband (180 eV to 2 keV) soft x-ray emission vs intensity for Ti.

Backlighter Characterization Experiments

at laser pulse durations of 100 and 600 ps (Fig. 7-84).

A complete, consistent explanation of the observed data is not yet available. We may note that, at low laser intensity (below about $3 \times 10^{14} \text{ W/cm}^2$), the laser pulse duration is the dominant parameter defining the plasma

Fig. 7-84. Ti broadband spectra.

Fig. 7-85. High-energy x-ray spectra for Ti and Zn irradiated with a short laser pulse.

scale length. Small laser spot sizes and steepened density profiles, both associated with high laser intensities (greater than 10^{15} W/cm^2), minimize differences in scale length between irradiations at 600 and 100 ps. Also, for both long and short laser pulses over the range of laser intensities that we have investigated, we found that, as the laser intensity increases, a larger fraction of the absorbed laser energy is deposited in hot electrons,⁹⁰ thus reducing the fraction of energy available to thermal electrons that heat the radiating overdense region.

Hard X-ray Emission

Measurements of hard x-ray emissions were made up to $h\nu = 350 \text{ keV}$. For short laser pulses, the high-energy x-ray tail can be characterized by temperatures on the order of 50 to 60 keV for all materials used (Ti, Ni, and Zn) and for laser intensities of 10^{16} to 10^{17} W/cm^2 . The inferred fraction of hot electrons⁹¹ ranges from 0.03 for Ti to 0.12 for Ni and Zn. However, the x-ray spectra appear to be extremely sensitive to details of the irradiation conditions. Figure 7-85 shows, for Ti and Zn, that the x-ray spectral intensity varies by as much as a factor of 2 for variations in incident laser energy of less than 6% and for laser intensities that are nominally identical on the target.

Little reliable data were obtained at $\tau_L = 600 \text{ ps}$ because the measured signals were often weak and noisy. The Ti temperature dropped from $\sim 56 \text{ keV}$ at 100 ps to $\sim 40 \text{ keV}$ at 600 ps for $3 \times 10^{16} \text{ W/cm}^2$, as shown in Fig. 7-86. The high-energy temperature for Ni, however, seems to have changed little,

although the fraction of hot electrons⁹¹ decreases significantly. The features observed between 60 and 80 keV are not fully understood at this time.

Light Emission Near $\omega/2$

Figure 7-52 shows the location of the two detectors (one pyroelectric and one indium arsenide) that were used to study stimulated Raman scattering.⁹² The measured intensities of the Raman light energy are summarized in Table 7-12, for Ti, Hf, and Zn, and in Fig. 7-87, for Ti, Ni, and Zn.

Unfortunately, data were not gathered simultaneously by the narrowband InAs detector, which was operational during the 100-ps experiment, and the wideband pyroelectric detector, which was used for the 600-ps experiments. Since the Raman spectral width is not known precisely, it is difficult to compare the data collected by the different detectors; however, later experiments show bandwidths on the order of one-third of a micrometre. Using this value to transform the Ti data obtained at 600 ps and $3.6 \times 10^{15} \text{ W/cm}^2$ (Table 7-12), we calculate an equivalent Raman spectral flux of $1.4 \times 10^{-2} \text{ J/(sr-}\mu\text{m)}/\text{J incident}$, or more than two orders of magnitude greater than the flux measured at 100 ps at the same laser intensity (Fig. 7-87).

A similar calculation for $I_L \sim 3 \times 10^{16}$ shows that the Raman flux at 600 ps is only a factor of 3 higher than the flux measured at 100 ps. However, it is probable that, as the laser intensity increases at $\tau_L = 600 \text{ ps}$, "the shorter interaction length associated with the smaller laser spot sizes used, and the greater Landau damping due to the higher electron temperature, lessen the increase in Raman scattered light flux expected at higher laser intensities."⁹²

Target disk	Laser energy (kJ)	Laser intensity (W/cm^2)	Measured Raman intensity (J/sr)
Ti	0.53	3.6×10^{15}	2.4
Hf	2.6	4.6×10^{15}	67.4
Ti	3.32	2.0×10^{16}	4.2
Ti	3.83	3.5×10^{16}	4.2
Zn	3.84	10^{17}	3.6

Note: Detector viewing angle: 62° w.r.t. target normal.

Experiment Summary

From the data collected during our first backlighter characterization experiments, a picture emerges that can be used to roughly predict the performance of a K-line emitter. This picture can be summarized by the dashed lines superposed on the data of Fig. 7-74, as shown in Fig. 7-88. The dashed lines indicate the trend suggested by the experimental data. (Note: the threshold location for the 600-ps data is merely artistic license, since no data are available as a guide.) For lower-Z materials, He- and Li-like lines dominate the emission spectrum, but the contribution from K_α radiation increases as the laser pulses shorten, as a result of an increase in the fraction of hot electrons.

Fig. 7-86. High-energy x-ray spectrum for Ti.

Fig. 7-87. Raman-shifted light intensity measured with the InAs detector at $1.8 \mu\text{m}$.

Table 7-12. Pyroelectric detector measurements of Raman light energy for 600-ps irradiations.

Backlighter Characterization Experiments

With increasing laser intensity, the reduced scale length (reduced emitting volume) and reduced absorption of the target result in decreasing intensity of the x-ray line emission. The reduced scale length is due both to the smaller spot sizes dictated by the use of our energy-limited laser and to the increased effect of ponderomotive forces. Also related to the decreasing emission intensity with increasing laser intensity are the saturation of the Raman scattered light intensity and a decrease in broadband soft x-ray conversion efficiency as laser intensity increases at a laser pulse duration of 600 ps.

Fig. 7-88. Conversion efficiency for Ti K-shell lines.

Fig. 7-89. Calculated density and temperature gradients of the laser pulse and corresponding line-emission profile of Ti.

For lines to be detected by our x-ray spectrometer, which has a dynamic range of 10^3 , a threshold laser intensity must be exceeded. This threshold depends on the laser pulse duration, as may be expected, since the density and temperature gradients that define the line-emission profile (Fig. 7-89) are strongly influenced by the laser pulse duration.

As the material Z increases and higher temperatures are needed to generate the x-ray lines, the laser intensity thresholds for long (600-ps) and short (100-ps) laser pulses become comparable and the contribution of cold K_α lines becomes more significant. The maximum attainable conversion (in photons/joule) decreases with increasing Z , although, at a given laser intensity, conversion factors vary little with Z .

Preliminary data indicate that, as laser wavelengths become shorter than $1.06 \mu\text{m}$, the x-ray lines are generated in hotter, denser matter with no cold line emission. The overall conversion efficiency at shorter wavelengths, at constant laser intensity, remains similar to that at $1.06 \mu\text{m}$, but the threshold intensity for generating the lines is lowered.

Finally, for short laser pulses, both the duration and extent of the x-ray line emitter exceed the corresponding laser pulse characteristics. The contribution of hot electrons to the generation of cold lines would explain both the longer duration and the larger extent. Moreover conditions (electron density, temperature) conducive to the generation of He- and Li-like lines can also prevail, with decreasing probability, beyond the laser interaction region because of the transverse gradient of these quantities.

Three important questions concerning x-ray sources remain to be answered before our backlighting capability can be optimized.

- Can x-ray lines be generated at a lower laser intensity? Experiments will be conducted with the Argus laser at a wavelength of $0.35 \mu\text{m}$ to verify the short-wavelength promise of the $0.53 \mu\text{m}$ results. Different irradiation schemes should also be tested to seek further improvement in our ability to generate lines at a lower laser intensity.
- Can point sources of x rays be obtained that will be adequate for making point-source shadowgraphs? Experiments are planned to examine this question by using

the Shiva laser. However, for the point-source experiments, the backlighting target will be considerably smaller than the laser beam focus, and much of the laser energy will be wasted. Serious consideration should be given to better, faster optics and shorter laser wavelengths as a means to minimize the beam focus size and, hence, maximize the efficiency of the x-ray point sources.

- Can short (~ 20 -ps) x-ray flashes be obtained? A study of the relationship between laser pulse duration and x-ray emission time must be performed as soon as the streaked spectrograph is available. Experiments at laser pulse durations of 20 ps will be planned for the Novette laser, where the Regen amplifier⁹³ will be available.

Positive answers to these three questions would lead to lower power requirements for the Nova backlighting beam at moderate x-ray energies (see "Evaluation of X-ray Backlighting for Novette- and Nova-Class Targets" in Section 5) and would bring the power requirements for high x-ray energies within reach. Positive answers would also provide an incentive for developing instruments with better space-time resolution for probing closer to the target core.

Authors: V. C. Rupert, D. L. Matthews, and L. N. Koppel

Major Contributors: N. M. Ceglio, R. A. Heinle, R. L. Kauffman, D. W. Phillion, R. H. Price, C. L. Wang, E. M. Campbell, R. E. Turner, F. Ze, R. W. Lee, and M. D. Rosen

Angular Distribution of High-Energy X Rays from Shiva-Irradiated Targets

In previous experiments with Shiva,⁹⁴ which were done either with a small, finite number of active detectors at fixed angles or with small-sized films subtending very limited solid angles, we found that the suprathermal x rays produced in laser-plasma interactions are anisotropic in the polar angular

distribution (with respect to the direction of the incident beam). To examine more completely the uniformity of x-ray emission as a function of both the polar and azimuthal angles, we have built a cylindrical x-ray film holder that is positioned around the target.

Figure 7-90 shows the experimental setup and coordinate system that we used for determining the angular distribution of x rays. The target is located at the origin, and a point on the cylinder is defined by the polar and azimuthal angles, θ and ϕ , respectively. To ensure that the x-ray emission is not affected by materials too close to the target, we made the diameter of the cylinder large, 22.9 cm. We chose the length of the cylinder, 30.5 cm, to be as long as practical without interfering with the

Fig. 7-90. Experimental setup and coordinate system.

Angular Distribution of High-Energy X Rays from Shiva-Irradiated Targets

incident laser beams. The axis of the cylinder coincides with the polar axis, which is also the centerline of the Shiva beam clusters.

Fig. 7-91. Composition of the film packets.

Thus, the film cylinder does not interfere with the target irradiation and provides maximum spatial coverage. In addition, we suspended a small film packet, 1 cm in diameter, from the top of the target chamber to provide a data point at $\theta = 0^\circ$.

Four film packets were placed at the four quadrants inside the film holder; the composition of the film packets is shown in Fig. 7-91. The 0.1-mm black plastic foil provides a light-tight envelope, while the 0.13-mm Cu filter provides 50% x-ray transmission at $E_x = 36.7$ keV, where E_x is the x-ray energy. Two pieces each of Kodak type AA, T, M, and R x-ray films cover a large detection dynamic range with redundancy. The 0.82-mm Cu filter and the 0.48-mm Cd filter provide 50% x-ray transmission at about 80 and 120 keV, respectively, when used in conjunction with the preceding materials.

We made two exposures with 1-mm-diam, 20- μ m-thick gold-disk targets. Ten of the Shiva laser beams, together delivering 4 kJ in 900 ps, were focused on a 0.25-mm-diam spot to produce a spatially averaged peak

Fig. 7-92. Typical patterns observed on the films behind the 36.7-, 80-, and 120-keV filters. The film strips are perpendicular to, and nearly centered on, the target plane.

Conditions: Au disk, 4.07 kJ, 0.9 ns, 10^{16} W/cm².

intensity of $\sim 10^{16}$ W/cm² at the target surface. The first exposure was obtained with the upper 10 beams, while the second exposure was obtained with the lower 10 beams to provide a check on symmetry and repeatability. Figure 7-92 shows the typical patterns observed on the films behind the 36.7-, 80-, and 120-keV filters. Note that the higher the x-ray dose, the brighter the print. The results of the two exposures are quite consistent and show near-perfect mirror images of each other.

Figure 7-93 presents the density profiles of the films shown in Fig. 7-92. We cannot overemphasize that the profiles shown in Fig. 7-93 are not the x-ray angular distribution. The angular distribution can only be obtained after the x-ray spectrum, source-to-film distance, x-ray attenuation, and film response are folded in. Some film sensitivities have yet to be calibrated, and the correction of x-ray attenuation would tend to raise the density profiles near both ends. Figure 7-93 is meant only to illustrate the structures in the density profile that may prompt understanding of the qualitative features of the data.

Some interesting features that have been established by our preliminary analyses of the films are

- Aside from the expected strong dip near the center of the film, there are intriguing shoulders on the density profiles for ~ 80 - and ~ 120 -keV x rays.
- Judging from the sharpness, the structures (dips and shoulders) must be geometrical in nature. Thus, the 80- and 120-keV x rays generated in this experiment are perfectly

adequate for either backlighting or shadow radiography.

- The x-ray distribution is azimuthally symmetrical.
- The x-ray fluence on the front side is higher than the fluence on the rear side of the disk.
- The target stalk, surrogate target ball, and target positioner had no effect on the recorded image.

We now try to explain the shoulder and dip in the density profiles (Fig. 7-94). The shoulder and dip are separated by 1.2 cm on

Fig. 7-93. Uncorrected density profiles of the films shown in Fig. 7-92.

Fig. 7-94. Hypothesized time-integrated plasma profile after irradiation of the target disk. ▼

the film, which corresponds to a 6.1° angle subtended at the target. What can give rise to a 6.1° angle at the target? Assume that the time-integrated plasma profile is roughly as

Fig. 7-95. Calculated emission region for 80-keV x rays.

Fig. 7-96. Configuration and location of new film packets for measuring x-ray angular distribution.

shown in Fig. 7-94. An x-ray emitting source $33 \mu\text{m}$ above the disk can project a dip in the shadow at 6.1° , and a shoulder can be generated in the shadow of the disk plane. Thus, contrary to the general impression, the disk plane is not at the dip, but is at the shoulder. This hypothesis is supported by the fact that the shoulder is near the center of the film where the target was supposed to be.

To test the hypothesis that the hard x-ray emitting source is indeed above the disk plane, we performed a one-dimensional LASNEX calculation of the experiment to obtain a crude idea of the expected characteristics of the high-energy x-ray source. The calculation used "standard" LASNEX modeling: a resonance absorption dump fraction of 0.3; the classical inverse bremsstrahlung cross section; the current stimulated Brillouin scattering model; and inhibited ($f = 0.03$) thermal-electron transport. The calculation was performed in one-dimensional spherical geometry with a radius of curvature ($490 \mu\text{m}$) equal to twice the irradiation spot diameter to mock up the two-dimensional coronal expansion. Of the 4 kJ incident in 900 ps, 520 J were absorbed, with 42 J absorbed by resonance absorption into a suprathermal electron distribution with $T_h \approx 45 \text{ keV}$. These results are roughly in line with other, similar, experiments performed with Shiva, though we do not have shots with exactly the same parameters for comparison.

The LASNEX calculation shows that, at the time of peak laser power, the critical-density surface lies $100 \mu\text{m}$ in front of the original disk surface. This is the position of highest density of 40- to 200-keV electrons in the calculation. We note that the experiment could also be affected by hot electrons produced at or below the quarter-critical surface by either $2\omega_{pe}$ or Raman instabilities, which are not incorporated in the model used here. If these mechanisms were significant, an additional source of hot electrons would add to the population of hot electrons in the corona.

The spatial distribution of x-ray emission produced by the coronal hot electrons depends upon the rate of transport to denser matter and the subsequent bremsstrahlung emission rate. LASNEX shows that the transport to higher density is not very efficient. At the time of the peak of the laser pulse, the population of 80-keV electrons

drops by well over an order of magnitude between the critical-density surface and the position of the original surface of the disk.

We have calculated the time-integrated x-ray source location for this one-dimensional LASNEX problem by using the code TDG to solve the radiation-rate and transport equations. We assumed a crude response function that roughly corresponds to the 80-keV filter-film channel, with response varying linearly from 0 at 40 keV to 1 at 80 keV to 0 at 120 keV. With the calculated spectrum and this response function, we find that 50- to 100-keV x rays account for about 70% of the signal. The spatial extent of the source is shown in Fig. 7-95. The source thickness is about $20 \pm 10 \mu\text{m}$, and the position of highest emission intensity lies $25 \pm 15 \mu\text{m}$ in front of the original disk surface. We have estimated these uncertainties from the geometry of the one-dimensional mockup. More reliable calculation results would be obtained by using a more precise filter-film response function and a full two-dimensional simulation.

Even after folding in the x-ray spectrum, x-ray absorption, and film response, we will still have some uncertainty in the angular distribution because we do not know whether the x-ray spectrum is independent of the emission angle. This uncertainty is the major deficiency in the present experimental approach; however, by taking advantage of the azimuthal symmetry established in this experiment, we can now design new detectors that will not only alleviate the above deficiency but also provide us with the additional advantages described below.

The new film packet will be a curved, narrow strip of films equidistant from the target in the θ plane ($\phi = \text{constant}$), as shown in Fig. 7-96. (The x-ray films to be used in the new packet are the same as those currently used.) The advantages of this packet configuration are the following:

- We can unambiguously determine whether the x-ray spectrum depends on the emission angle, θ . If the shape of the density profile is invariant of the x-ray energy, then the x-ray spectrum is independent of θ .
- We do not have to make either target-to-film distance corrections or x-ray transmission corrections for different values of θ ; therefore, the film density

profile itself represents the characteristics of the angular distribution, even before film calibration.

- The film packet occupies only a small portion of the target chamber solid angle and, therefore, does not require dedicated shots. If well planned, this experiment for determining the angular distribution of hard x rays can be carried out in all future target exposures without jeopardizing the prime goal of the shots, thus maximizing the physics output of the laser facility.

Authors: C. L. Wang, D. L. Banner, H. N. Kornblum, K. R. Manes, W. C. Mead, and V. W. Slivinsky

Major Contributors: K. L. Andrus, W. C. Cook, R. E. Leatherman, K. D. Poor, and J. E. Smith

Ultra-High-Pressure Laser-Driven Shocks in Gold

We have measured the velocities of ultra-high pressure laser-driven shocks produced in two gold-disk targets by the Shiva laser; inferred pressures as high as 3 TPa (30 Mbar) were generated in a preheat-free region in the gold. These experiments represent the initial step in a program to obtain high-quality equation-of-state data for pressures above 2 TPa.

The target disks, shown schematically in Fig. 7-97, were composed of $22 \mu\text{m}$ of vapor-deposited aluminum on $50\text{-}\mu\text{m}$ gold substrates. The disks, 5 mm in diameter, were mounted onto plastic washers, ~ 1 mm thick with inside diameters of ~ 3 mm and outside diameters of ~ 5 mm, so that the aluminum side faced the laser beam. This design was chosen to exploit the shock-impedance mismatch between aluminum and gold, which increases the amplitude of the shock as it passes from the aluminum into the gold. The $22\text{-}\mu\text{m}$ thickness of Al was chosen so that the shock would arrive at the Al-Au interface near the time of peak shock pressure in the aluminum. The thick gold layer was designed to limit preheat to an acceptable level.

Ultra-High-Pressure Laser-Driven Shocks in Gold

A flat-bottomed groove, nominally $15\text{ }\mu\text{m}$ deep and $75\text{ }\mu\text{m}$ wide, was ion-milled into the gold surface, as indicated in Fig. 7-97. The depth of the groove was measured with a stylus surface analyzer with an accuracy of $0.3\text{ }\mu\text{m}$. During the experiment, the groove was observed with an ultrafast streak camera, and the shock velocity was obtained

by measuring the time for the shock to move from the bottom to the top of the groove.

Each target was irradiated in the center of the aluminum surface by the lower 10 beams of the Shiva laser. Each beam was focused to a spot roughly $500\text{ }\mu\text{m}$ in diameter, and the beams were overlapped to produce a uniform distribution of laser

Fig. 7-97. Target design and side view of streak-camera system.

Fig. 7-98. Plan view of optical streak-camera system.▼

intensity so that the shock in the target would be planar.

The imaging and timing system of the streak camera (Figs. 7-97 and 7-98) was based on the design⁹⁵ used at the Argus facility; this system has a time resolution of 30 ps. Absolute timing of the streak camera was obtained by use of a fiducial signal, which was produced by frequency-doubling a portion of one Shiva beam and transporting the frequency-doubled light, with appropriate time delay, over a fiber optic to the streak-camera optics. This absolute timing permitted us to measure the transit time of the shock through the target to the bottom of the groove.

Table 7-13 lists the incident and absorbed energy, pulse length, spot size, and incident intensity for each of two experiments. The streak-camera data from both shots are shown in Fig. 7-99. The streak record shown in Fig. 7-99(a) shows the shock luminosity recorded in two color channels, one centered at 420 nm with a width of 78 nm and the other centered at 600 nm with a width of 64 nm. The record in Fig. 7-99(b) is from the 420-nm channel.

For temperatures below ~2 eV, two separate color channels are useful for inferring temperature via ratios of intensities in the two channels; however, at the temperatures inferred in these experiments (~5 eV), two separate channels offered little advantage over a single channel because the ratio of intensities varies only slightly. Temperatures that were inferred from absolute intensities recorded from single channels are listed in Table 7-14. For both experiments, Table 7-15 shows the groove depths, shock transit times to the bottom of the groove, and average shock velocities

(groove depth divided by transit time across the groove).

We relate the measured shock velocities (U_s) to shock pressures (P) through the Hugoniot relation for conservation of momentum across a shock front,

$$P = \rho_0 U_s U_p, \quad (16)$$

where ρ_0 is the initial density and U_p is the mass velocity behind the shock front. Equations for conservation of mass and energy, together with Eq. (16), relate five variables: pressure, density, shock velocity,

First shot	
Incident energy	3850 ± 300 J
Pulse length (FWHM)	$625 \pm \frac{25}{75}$ ps
Spot size	520 μ m
Incident intensity	$(2.9 \pm 0.3) \times 10^{15}$ W/cm ²
Absorbed energy	1460 ± 350 J
Second shot	
Incident energy	3535 ± 265 J
Pulse length (FWHM)	500 ± 50 ps
Spot size	520 μ m
Incident intensity	$(3.3 \pm 0.4) \times 10^{15}$ W/cm ²
Absorbed energy	1340 ± 350 J

Table 7-13. Laser parameters for two equation-of-state shots.

		Temperatures (eV)	
		600-nm channel	420-nm channel
First shot			
Measured	At groove	7	6
	At shoulder	5	4.5
Second shot			
Measured	At groove	—	3.5
	At shoulder	—	4.5

Table 7-14. Temperatures inferred from luminosity of free surface of target.

	First shot	Second shot
Groove depth (μ m)	18.8 ± 0.3	14.5 ± 0.3
Shock transit time (ps)	1085 ± 45	1175 ± 15
Average shock speed (cm/ μ s)	1.73 ± 0.07	1.23 ± 0.05

Table 7-15. Average shock speeds.

Fig. 7-99. Streak-camera data for two shots. ▼

mass velocity, and internal energy. An equation-of-state (EOS) experiment requires measurement of any two of these variables (usually mass and shock velocity), which, together with the conservation equations, completely determines a point on the Hugoniot.

In these experiments, we were able to measure only one of the five variables, the shock velocity. To infer the pressure from the shock velocity, therefore, we must resort to an EOS that previously has been either determined experimentally or calculated. It has been experimentally determined⁹⁶ for many materials, including gold, that a linear relationship between U_s and U_p ,

$$U_s = C_0 + S U_p, \quad (17)$$

adequately defines the Hugoniot for pressures below 0.5 TPa. In Eq. (17), C_0 and S are constants determined by least-squares fits to experimental data. Reliable Hugoniot data do not exist for gold in the pressure range from 1 to 10 TPa; consequently, we used Eq. (17) to infer the pressures in our experiments by extrapolating shock data from lower pressures.

The values of C_0 and S and of the initial gold density, ρ_0 , are $C_0 = 0.312 \text{ cm}/\mu\text{s}$, $S = 1.512$, and $\rho_0 = 19.29 \text{ g}/\text{cm}^3$. Using these values, together with our measured values of U_s , we calculated shock pressures of $>3.1 \text{ TPa}$ in one shot and $>1.5 \text{ TPa}$ in the other.

We also measured the x-ray spectra with the filter fluorescer instrument (FFLEX) during these experiments, and the FFLEX data are shown in Fig. 7-100. The spectra from both experiments indicate a hot electron temperature, T_{hot} , of about 40 keV. Using the formula suggested by Kruer,⁹⁷ these spectra can be roughly related to the amount of energy in hot electrons, E_{hot} , and the fraction of the incident energy, f_{hot} , that goes into the hot electrons. In both experiments, f_{hot} was about 0.03. Calculations⁹⁸ of electron preheat, using these values of T_{hot} and f_{hot} , show that the shock-velocity measurements were made in a preheat-free region of the target. This finding is consistent both with our streak-camera measurements, which showed no preheat above 0.5 eV (the limit of the instrument's sensitivity), and with numerical simulations.

The experiments were simulated with both one- and two-dimensional LASNEX calculations. These simulations did not explain why the second experiment yielded a slower average shock speed than the first experiment; in fact, the simulations predict that, under the given experimental conditions, exactly the opposite ordering of results would be expected. The simulations are quite sensitive to the assumed absorption of incident laser energy, however, and this absorption was not accurately measured in these experiments. The simulations showed the same qualitative trends for both experiments, most notably that high pressures at the aluminum-gold interface

Fig. 7-100. High-energy x-ray distributions measured by FFLEX.

were severely attenuated by rarefactions catching up with the advancing shock as it moved through the gold. We calculated that the pressure at the Al-Au interface of each of the two samples was from 7 to 9 TPa. In making these calculations, we used simulated conditions that resulted in shock transit times across both the groove and the whole Al-Au target that were comparable to the experimentally measured values.

The central purpose of our experiments was to demonstrate that we could generate extremely high-pressure laser-driven shocks in a target with low preheat. These experiments were successful, and they have given us valuable guidance for future calculations and future target designs. We are now preparing targets with multiple gold

steps to characterize shock decay. Targets for impedance-matching experiments are also being fabricated for future shots; these targets will consist of Cu and Au steps atop a base comprising a 22- μm layer of Al over a 32- μm layer of Au. Multiple steps of each overlay material will be used to measure shock decay. A copper-gold experiment conducted under the conditions described in this article should generate pressures exceeding 3 TPa in the gold and 2 TPa in the copper. Impedance-matching experiments made with the Janus laser are described in detail in "Military Applications" in Section 9.

Authors: N. C. Holmes, R. J. Trainor, D. L. Banner, D. W. Phillion, R. J. Harrach, M. D. Rosen, and Y. T. Lee

References

Introduction

7-1

1. A. G. M. Maaswinkel, K. Eidmann, and R. Sigel, *Phys. Rev. Lett.* **42**, 1625 (1979).
2. E. Fabre et al., "Experiences D'Interaction Laser-Matiere a Differentes Longueurs D'Ondes," *Entrpa* 15 (89-90), 47 (1979).
3. M. H. Key et al., "Review of Recent Work at the SRC Central Laser Facility at the Rutherford Laboratory, Abingdon," Thirteenth European Conference on Laser Interaction with Matter (Leipzig, 1979).

Target-Interaction Experiments at 0.53 μm and 0.35 μm

7-2

4. C. Garbau-Labaune, E. Fabre, and C. Max, *Bull. Am. Phys. Soc.* **25**, 894 (1980); D. J. Tanner, D. Mitrovich, J. Tarvin, R. L. Berger, and J. Larson, *Bull. Am. Phys. Soc.* **25**, 895 (1980); E. M. Campbell, V. C. Rupert, W. C. Mead, R. E. Turner, C. E. Max, K. G. Estabrook, and F. Ze, *Bull. Am. Phys. Soc.* **25**, 895 (1980).
5. C. E. Max and K. G. Estabrook, *Wavelength Scaling from a Plasma Physics Point of View*, Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-82671 (1979).
6. M. D. Rosen, D. W. Phillion, V. C. Rupert, W. C. Mead, W. L. Kruer, J. J. Thomson, H. N. Kornblum, V. W. Slivinsky, G. J. Caporaso, M. J. Boyle, and K. G. Tirsell, *Phys. Fluids* **22**, 2020 (1979).
7. K. G. Estabrook and W. L. Kruer, *Phys. Rev. Lett.* **40**, 42 (1978).
8. A. B. Langdon, B. F. Lasinski, and W. L. Kruer, *Phys. Rev. Lett.* **43**, 133 (1979).
9. *Laser Program Annual Report—1979*, Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-79 (1980), p. 3-20.

Experimental Conditions

7-3

10. *Laser Program Annual Report—1979*, Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-79 (1980), p. 3-1.
11. S. Bodner, *Bull. Am. Phys. Soc.* **25**, 969 (1980).
12. *Laser Program Annual Report—1978*, Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-78 (1979), p. 3-10; W. P. Crowley, *An Empirical Theory for Large Amplitude Rayleigh-Taylor Instability*, Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-72650 (1970).
13. D. W. Phillion, *Bull. Am. Phys. Soc.* **25**, 993 (1980); *Laser Program Annual Report—1978*, Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-78 (1979), p. 3-2.

Absorption

7-7

14. *Laser Program Annual Report—1979*, Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-79 (1980), p. 6-46.
15. *Laser Program Annual Report—1975*, Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-75 (1976), p. 40.
16. J. T. Hunt, J. A. Glaze, W. W. Simmons, and P. A. Renard, "Suppression of Self-Focusing Through Low-Pass Spatial Filtering and Relay Imaging," *Appl. Opt.* **17**, 2053 (1978).
17. C. Garbon-Labune, E. Fabre, and C. Max, *Bull. Am. Phys. Soc.* **25**, 894 (1980).

X-ray Conversion Efficiency

7-10

18. K. G. Tirsell, H. N. Kornblum, and V. W. Slivinsky, *Time Resolved, Sub-keV X-Ray Measurements Using Filtered X-Ray Diodes*, Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-81478 (1979).
19. *Laser Program Annual Report—1979*, Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-79 (1980), p. 6-41.
20. K. G. Tirsell and P. H. Y. Lee, "Sub-keV X-ray Emission from $2\omega_0$ Irradiation of Disk Targets," *Bull. Am. Phys. Soc.* **25**, 885 (1980).
21. *Laser Program Annual Report—1979*, Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-79 (1980), p. 6-19.
22. D. T. Attwood, D. W. Sweeny, J. M. Auerbach, and P. H. Y. Lee, "Interferometric Confirmation of Radiation-Pressure Effects in Laser-Plasma Interaction," *Phys. Rev. Lett.* **40**, 189 (1978).

Suprathermal X Rays

7-16

23. B. L. Pruett, K. G. Tirsell, H. N. Kornblum, S. S. Glaros, D. E. Campbell, and V. W. Slivinsky, *A Ten Channel Filter-Fluorescer Spectrometer*, Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-81477 (1978).
24. *Laser Program Annual Report—1978*, Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-78 (1979), p. 6-12.

Transport Experiments at 3ω

7-20

25. M. D. Rosen, D. W. Phillion, V. C. Rupert, W. C. Mead, W. L. Kruer, J. J. Thomson, H. N. Kornblum, V. W. Slivinsky, G. J. Caporaso, M. J. Boyle, and K. G. Tirsell, *Phys. Fluids* **22**, 2020 (1979).
26. F. C. Young, R. R. Whitlock, R. DeCoste, B. H. Repin, D. J. Nagel, J. A. Stamper, J. M. McMann, and S. E. Bodner, *App. Phys. Lett.* **30**, 45 (1977).
27. *Laser Program Annual Report—1979*, Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-79 (1980), p. 6-19.
28. B. Yaakobi and T. Bristow, *Phys. Rev. Lett.* **38**, 350 (1977).
29. B. H. Ripin, R. DeCoste, S. P. Obensharn, S. E. Bodner, E. A. McLean, F. C. Young, R. R. Whitlock, C. M. Armstrong, J. Grum, J. A. Stamper, S. H. Gold, D. J. Nagel, R. H. Lehmberg, and J. M. McMahon, *Phys. Fluids* **23**, 1012 (1980).
30. K. G. Tirsell, H. N. Kornblum, and V. W. Slivinsky, *Bull. Am. Phys. Soc.* **23**, 807 (1978).
31. *Laser Program Annual Report—1978*, Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-78 (1979), p. 5-7.
32. R. J. Trainor, J. W. Shaner, J. M. Auerbach, and N. C. Holmes, *Phys. Rev. Lett.* **42**, 1154 (1979).

33. G. B. Zimmerman, *Non-Maxwellian Ion Distributions in Compressed Laser Targets*, Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-75884 (1974); G. B. Zimmerman and W. L. Kruer, *Comm. Plasma Phys. and Controlled Fusion* **2**, 85 (1975).
34. R. A. Haas, W. C. Mead, W. L. Kruer, D. W. Phillion, H. N. Kornblum, J. D. Lindl, D. MacQuigg, V. C. Rupert, and K. G. Tirsell, *Phys. Fluids* **20**, 322 (1977).
35. H. D. Shay, R. A. Haas, W. L. Kruer, M. J. Boyle, D. W. Phillion, V. C. Rupert, H. N. Kornblum, F. Rainer, V. W. Slivinsky, L. N. Koppel, L. Richards, and K. G. Tirsell, *Phys. Fluids* **21**, 1634 (1978).
36. M. D. Rosen, D. W. Phillion, V. C. Rupert, W. C. Mead, W. L. Kruer, J. J. Thomson, H. N. Kornblum, V. W. Slivinsky, G. J. Caporaso, M. J. Boyle, and K. G. Tirsell, *Phys. Fluids* **22**, 2020 (1979).
37. A. B. Langdon, *Phys. Rev. Lett.* **44**, 575 (1980).
38. R. Faehl and W. L. Kruer, *Phys. Fluids* **20**, 55 (1977); W. M. Manheimer, *Phys. Fluids* **20**, 265 (1977).
39. E. J. Valeo and W. L. Kruer, *Phys. Rev. Lett.* **33**, 750 (1974); J. M. Kindel, K. Lee, and E. L. Lindman, *Phys. Rev. Lett.* **34**, 134 (1975).
40. K. G. Estabrook, E. J. Valeo, and W. L. Kruer, *Phys. Fluids* **18**, 1151 (1975).
41. *Laser Program Annual Report—1979*, Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-79 (1980), p. 6-14.
42. K. R. Manes, H. G. Ahlstrom, R. A. Haas, and J. F. Holzrichter, *J. Opt. Soc. Am.* **67**, 717 (1977).
43. W. L. Kruer, K. G. Estabrook, and K. H. Sing, *Nucl. Fusion* **13**, 952 (1973).
44. A. B. Langdon, B. F. Lasinski, and W. L. Kruer, *Phys. Rev. Lett.* **43**, 133 (1979).
45. K. G. Estabrook and J. Harte, *On Reducing Brillouin Scatter*, Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-82620, Rev. 2 (1979).
46. *Laser Program Annual Report—1979*, Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-79 (1980), p. 3-66.
47. W. L. Kruer, *Comm. Plasma Phys. and Controlled Fusion* **5**, 69 (1979).
48. C. E. Max and K. G. Estabrook, *Comm. Plasma Phys. and Controlled Fusion* **5**, 239 (1980).
49. C. E. Max, C. F. McKee, and W. C. Mead, *Phys. Fluids* **23**, 1620 (1980).
50. F. Amiranoff, R. Benattar, R. Fabbro, E. Fabre, C. Garban, and M. Weinfeld, *Bull. Am. Phys. Soc.* **24**, 1054 (1979).
51. *Laser Program Annual Report—1979*, Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-79 (1980), p. 6-12.
52. J. R. Albritton, Lawrence Livermore National Laboratory, Livermore, Calif., private communication (December 1979).
53. *Laser Program Annual Report—1979*, Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-79 (1980), p. 6-26.
54. A. H. Compton and S. K. Allison, *X-Rays in Theory and Experiment* (Van Nostrand Reinhold, New York, 1935).
55. *Laser Program Annual Report—1979*, Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-79 (1980), p. 3-25.
56. J. R. Albritton, I. B. Bernstein, E. J. Valeo, and E. A. Williams, *Phys. Rev. Lett.* **39**, 1536 (1977).
57. W. L. Kruer, K. G. Estabrook, B. F. Lasinski, and A. B. Langdon, *Phys. Fluids* **23**, 1326 (1980); K. G. Estabrook, W. L. Kruer, and B. F. Lasinski, *Phys. Rev. Lett.* **45**, 1399 (1980).
58. D. W. Phillion and D. L. Banner, *Behavior of the Raman and $2\omega_{pe}$ Instabilities in Large Plasmas Irradiated by Intense Laser Light*, Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-84854 (1980).
59. N. A. Ebrahim, H. A. Baldis, C. Joshi, and R. Benesch, *Phys. Rev. Lett.* **45**, 1179 (1980).
60. G. L. Stradling, R. L. Kauffman, E. M. Campbell, M. D. Rosen, and W. C. Mead, *Bull. Am. Phys. Soc.* **25**, 885 (1980).
61. C. S. Liu, *Advances in Plasma Physics*, Vol. 6, A. Simon and W. B. Thompson, Eds. (John Wiley, New York, 1976), p. 121.
62. C. S. Liu, M. N. Rosenbluth, and R. B. White, *Phys. Fluids* **18**, 1002 (1975).
63. J. L. Bobin, M. Decroisset, B. Meyer, and Y. Vitel, *Phys. Rev. Lett.* **30**, 594 (1973).
64. J. Elazar, W. Toner, and E. R. Wooding, *Annual Report to the Laser Facility Committee 1980*, Rutherford Laboratory (Laser Division), Oxon, England, RL-80-026 (1980), p. 3.10.
65. R. G. Watt, R. D. Brooks, and Z. A. Pietrzyk, *Phys. Rev. Lett.* **41**, 271 (1978).
66. H. A. Baldis, J. C. Samson, and P. B. Corkum, *Phys. Rev. Lett.* **41**, 1719 (1979).
67. N. A. Ebrahim, H. A. Baldis, C. Joshi, and R. Benesch, *Phys. Rev. Lett.* **45**, 1179 (1980).
68. C. Joshi, C. E. Clayton, A. Yasudo, and F. F. Chen, University of California, Los Angeles, have reported seeing Raman scatter in a preionized plasma (1980).
69. W. L. Kruer, K. G. Estabrook, B. F. Lasinski, and A. B. Langdon, *Phys. Fluids* **23**, 1326 (1980).
70. *Laser Program Annual Report—1979*, Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-79 (1980), p. 6-32.
71. D. W. Forslund, J. M. Kindel, and E. L. Lindman, *Phys. Fluids* **18**, 1017 (1974); D. Biskamp and H. Welter, *Phys. Rev. Lett.* **34**, 313 (1975); W. L. Kruer, K. G. Estabrook, and K. H. Sing, *Nucl. Fusion* **13**, 952 (1973); W. Manheimer and H. Klein, *Phys. Fluids* **17**, 1889 (1974); B. I. Cohen, A. N. Kauffman, and K. M. Watson, *Phys. Rev. Lett.* **29**, 581 (1972).
72. J. D. Jackson, "Plasma Physics," *J. Nucl. Energy (Part C)* **1**, 171 (1960). The program that evaluated the plasma-dispersion integral in this paper was written by K. G. Estabrook of LLNL.
73. J. F. Drake, P. K. Kaw, Y. C. Lee, G. Schmidt, C. S. Liu, and M. N. Rosenbluth, *Phys. Fluids* **17**, 778 (1974).
74. K. G. Estabrook, W. L. Kruer, and B. F. Lasinski, "Heating by Raman Back and Forward Scatter," *Phys. Rev. Lett.* **45**, 1399 (1980).

Analysis and Summary of Wavelength-Scaling Experiments and Comparisons with Simulations
7-22

Stimulated Raman Scattering in Large Plasmas
7-35

References

-
Space-Time-Resolved X-ray Measurements from Accelerated Disk Targets
7-44 | 75. G. McClellan, P. H. Y. Lee, and G. Caporaso, <i>Phys. Rev. Lett.</i> 44 , 658 (1980).
76. K. G. Tirsell, H. N. Kornblum, and V. W. Slivinsky, <i>Bull. Am. Phys. Soc.</i> 12 , 807 (1978).
77. M. D. Rosen, D. W. Phillion, V. C. Rupert, W. C. Mead, W. L. Kruer, J. J. Thomson, H. N. Kornblum, V. W. Slivinsky, G. J. Caporaso, M. J. Boyle, and K. G. Tirsell, <i>Phys. Fluids</i> 22 , 2027 (1979). | 78. M. D. Rosen, D. W. Phillion, V. C. Rupert, W. C. Mead, W. L. Kruer, J. J. Thomson, H. N. Kornblum, V. W. Slivinsky, G. J. Caporaso, M. J. Boyle, and K. G. Tirsell, <i>Phys. Fluids</i> 22 , 2025 (1979). |
|--|---|--|
-
Backlighter Characterization Experiments
7-53 | 79. <i>Laser Program Annual Report—1977</i> , Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-77 (1978), p. 4-18.
80. M. H. Key, P. T. Rumsby, R. G. Evans, C. L. S. Lewis, M. J. Ward, and R. L. Cooke, "Study of Ablatively Imploded Spherical Shells," <i>Phys. Rev. Lett.</i> 45 , 1801 (1980).
81. D. L. Matthews, L. N. Koppel, R. W. Lee, R. L. Kauffman, E. M. Campbell, R. E. Turner, D. T. Attwood, N. M. Ceglio, K. R. Manes, V. C. Rupert, and V. W. Slivinsky, "Characterization of X-ray Line Sources for X-ray Backlighting," <i>Bull. Am. Phys. Soc.</i> 25 , 898 (1980).
82. <i>Laser Program Annual Report—1979</i> , Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-79 (1980), p. 6-1; G. F. McClellan, P. H. Y. Lee, G. J. Caporaso, "Z Dependence of the Laser-Intensity Threshold for Inhibited Electron Thermal Conduction," <i>Phys. Rev. Lett.</i> 44 , 658 (1980).
83. <i>Laser Program Annual Report—1979</i> , Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-79 (1980), p. 5-54; R. H. Price, M. W. Kobiericki, J. R. Zickuhr, and H. G. Ahlstrom, "The Shiva Streaked Axisymmetric X-ray Microscope," <i>Bull. Am. Phys. Soc.</i> 25 , 889 (1980).
84. <i>Laser Program Annual Report—1977</i> , Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-77 (1978), p. 4-43.
85. C. E. Max and K. G. Estabrook, "Wavelength Scaling in Laser Fusion from a Plasma Physics Point of View," <i>Comm. Plasma Phys. Contr. Fusion</i> 5 , 239 (1980); F. Amiranoff, R. Fabbro, E. Fabre, C. Garban, J. Virmont, and M. Weinfeld, "Experimental Transport Studies in Laser Produced Plasma at 1.06 μm and 0.53 μm ," <i>Phys. Rev. Lett.</i> 43 , 522 (1979). | 86. D. T. Attwood, L. W. Coleman, J. T. Larsen, and E. K. Storm, "Time Resolved X-ray Spectral Studies of Laser Compressed Targets," <i>Phys. Rev. B</i> 37 , 499 (1976); <i>Laser Program Annual Report—1977</i> , Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-77 (1978), p. 6-17.
87. R. W. Lee and D. L. Matthews, "K X-ray Emission from High Power Laser Plasma Interactions," <i>Bull. Am. Phys. Soc.</i> 25 , 885 (1980).
88. <i>Laser Program Annual Report—1978</i> , Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-78 (1979), p. 6-5.
89. M. D. Rosen, D. W. Phillion, V. C. Rupert, W. C. Mead, W. L. Kruer, J. T. Thomson, H. N. Kornblum, V. W. Slivinsky, G. J. Caporaso, M. J. Boyle, and K. G. Tirsell, "The Interaction of 1.06 μm Laser Radiation with High Z Targets," <i>Phys. Fluids</i> 22 , 2020 (1979).
90. <i>Laser Program Annual Report—1979</i> , Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-79 (1980), p. 3-6.
91. W. L. Kruer, Lawrence Livermore National Laboratory, Livermore, Calif., private communication (1978).
92. D. W. Phillion and D. L. Banner, "Stimulated Raman Scattering in Large Plasmas," <i>Bull. Am. Phys. Soc.</i> 25 , 993 (1980).
93. J. E. Murray and D. J. Kuizenga, "Regenerative Compression of Laser Pulses," <i>Appl. Phys. Lett.</i> 37 , 27 (1980). |
|--|--|---|
-
Angular Distribution of High-Energy X Rays from Shiva-Irradiated Targets
7-65	94. C. L. Wang, H. N. Kornblum, and V. W. Slivinsky, <i>Angular Distribution of Suprathermal X Rays from Laser-Produced Plasma</i> , Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-83053 (1979).	
-
Ultra-High-Pressure Laser-Driven Shocks in Gold
7-69 | 95. <i>Laser Program Annual Report—1978</i> , Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50021-78 (1979), p. 6-40.
96. M. Van Thiel, <i>Compendium of Shock Wave Data</i> , Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-50108 Vol. 1, Rev. 1 (1977).
97. W. L. Kruer, Lawrence Livermore National Laboratory, Livermore, Calif., private communication (1979).
98. M. D. Rosen, <i>Analysis of Long Pulse Physics Experiments at LLL: Late 1977-Early 1979</i> , Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-83022 (1979); G. J. Caporaso and S. S. Wilson, <i>A Simple Model for Suprathermal Electron Deposition in High-Z Plasmas</i> , Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-83308 (1979); Y. T. Lee and R. J. Trainor, <i>Design of Laser-Generated Shock Wave Experiments—An Approach Using Analytic Models</i> , Lawrence Livermore National Laboratory, Livermore, Calif., UCRL-84787 (1980). | |
|---|---|--|
-

DISCLAIMER

This document was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor the University of California nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial products, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or the University of California. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government thereof, and shall not be used for advertising or product endorsement purposes.

Work performed under the auspices of the U.S. Department of Energy by Lawrence Livermore National Laboratory under Contract W-7405-Eng-48.

Lawrence Livermore National Laboratory

DO NOT MICROFILM
COVER