FINAL REPORT TO THE DOE

Design and Synthesis of Reactive Separation Systems

(Grant No. DE-FG02-88ER13946)

by

Michael F. Doherty

Department of Chemical Engineering
University of Massachusetts
Amherst MA 01003
USA

Abstract

During the last decade there has been a rapid upturn in interest in reactive distillation. The chemical process industry recognizes the favorable economics of carrying out reaction simultaneously with distillation for certain classes of reacting systems, and many new processes have been built based on this technology. Interest is also increasing by academics and software vendors. Systematic design methods for reactive distillation systems have only recently begun to emerge. In this report we survey the available design techniques and point out the contributions made by our group at the University of Massachusetts..

Introduction

Distillation with chemical reaction has been carried out for as long as distillation has been practiced. This, however, has not always been viewed as a good thing. Invariably, reactions are present not by design, but because they cannot be prevented. Homogeneous, self-catalyzed reactions such as esterifications, transesterifications and hydrolysis reactions being the biggest culprits. The advantages of combining reaction with distillation were recognized long ago (Backhaus (1921a, 1921b, 1921c, 1921d, 1922a, 1922b, 1922c, 1922d, 1922e, 1923a, 1923b), Keyes (1932), Carney (1937), McKeon et al. (1940), McKeon (1940), Langtin and Randall (1942), Leyes and Othmer (1945), Berman et al. (1948), Belck (1955), Corson et al. (1956), Hofmann (1958), Schoenemann (1958), Corrigan and Ferris (1969), Saito et al. (1971)) but the idea did not manage to capture the imagination of chemical engineers beyond aficionados of the subject. In recent years, however, a growing number of clever and determined engineers have designed and built commercial distillation systems in which chemical reactions are deliberately introduced in order to achieve the process goals. Although there are now many commercial reactive distillation systems, it is still not an easy task to bring a new process to production. The foremost difficulty is the (quite natural) reluctance on the part of both management and engineers caused by "having never done it this way before". This is usually compounded by shortening design and build schedules which prevents the basic research from taking place before attempting to build a reactive distillation system.

The forces involved are quite strong. Reactive distillations are often very economical; in some cases cutting total annualized production costs by an order of magnitude. However, reactive distillations normally require longer lead times for research, design, and pilot testing, in addition to a bold attitude on the part of management and engineers. There is almost always a conventional alternative to reactive distillation which is seductive because, "we have always done it this way". A few well-publicized successes, however, can carry a technology a long way, and this has certainly been the case for reactive distillation recently. Most of the major oil and chemical companies now have some activity in this area.

Combining reaction with distillation is not always advantageous. At the very least, it must be possible to achieve reasonable reaction rates at the relatively low temperatures and pressures normally encountered in distillation. Clearly, all high temperature and/or high pressure gas-phase reactions such as hydrogenations and hydrodealkylations are not candidates for reactive distillation. If the reaction is solid catalyzed then the catalyst life must be long (in the order of months, at least) in order to avoid constant start-up and shut-down.

Reactive distillation is potentially attractive whenever a liquid phase reaction must be carried out with a large excess of one reactant. Under such circumstances, conventional processes incur large recycle costs for the excess reactant. Reactive distillation, however, can normally be carried out closer to stoichiometric feed conditions, thereby eliminating recycle costs. Excess reactant is normally used:

- (1) to suppress side reactions, as in the case of butane alkylation. A simplified reaction scheme consists of

Excess butane keeps the concentrations of 1-butene and isooctane relatively low, thereby reducing the rate of reaction (2). In reactive distillation, however, the natural separation between isooctane and 1-butene prevents the second reaction from taking place and greatly reduces the amount of unwanted by-products formed. Because of this, the feeds to the column can be much closer to stoichiometric ratio.

- (2) to overcome limitations imposed by chemical equilibrium, as in the case of methyl acetate production

A common method of operating equilibrium-limited reactors is to use an excess of one reactant in order to increase the conversion of the limiting reactant. In reactive distillation, the continual separation of products from reactants causes the reaction to proceed in the forward direction by Le Chatelier's Principle. Again, it is possible with such an arrangement to get much closer to stoichiometric feed flows.

In some applications, chemical reaction has the beneficial effect of "reacting away" some of the azeotropes in the mixture and greatly simplifying the phase behavior. This almost always happens when the mixtures are nonideal (e.g., MTBE process, methyl acetate process, etc.). This effect is often the single most important feature of reactive distillation, and the least appreciated.

The design issues for reactive distillation systems are significantly more complex than those involved in ordinary distillations. First, a catalyst must be chosen; should it be heterogeneous, as in the MTBE process, or homogeneous, as in the methyl acetate process? This will influence not only the type of internals (e.g., plates, packing, catalyst baskets, etc.) but also the liquid holdup and its distribution throughout the column. Secondly, the reaction zone should be strategically placed within the column so as to get good performance. In some applications the entire column is reactive while in others only part is. In some instances the non-reactive zone(s) provide product purification by ordinary distillation (MTBE process) but in others the non-reactive zone breaks an azeotrope with an entrainer (extractive distillation column section), as in the methyl acetate process.

Other design issues include heat management (in the case of strongly exothermic reactions), reflux and reboil requirements, number of stages, position of feeds and control strategy.

Selected Commercial Processes

Reactive distillation is an attractive process alternative for a wide variety of difficult separations. Excellent surveys have been published by Sharma (1985) and Gaikar and Sharma (1989). We now describe a selection of commercial reactive distillation processes. These have been chosen to show the application of the technology in polymer processing, in the chemical industry and in petroleum refining.

Nylon 6,6 Process

Many important polyamides are formed by equilibrium-limited, liquid-phase polycondensation reactions of the form

and

where A and B are comonomers, C is a salt, P_i is a polymer with i repeat units and W is water. One of the most important examples of such a scheme is the case where A is adipic acid (nonvolatile), B is hexamethylene diamine (volatile) and the polymer is Nylon 6,6. The importance of reaction (4) relative to reactions (5) depends on the system temperature. Lower temperatures normally favor reaction (4). Temperatures above 200°C strongly favor reactions (5), and this is the regime where polymerization of Nylon 6,6 is normally carried out (see Steppan et al., 1987, 1989).

It is desirable to remove the water of reaction, as this will shift the equilibrium toward the polymer product. However, if the reactor is vented, an equilibrium concentration of any volatile reactants (hexamethylene diamine) is removed in the water-rich vapor. Since the reactants are valuable and stoichiometric balance is critical to attain high molecular weights, reactants *must* be separated from the water and returned to the reactor. The monomer loss must not only be low, it must also be constant since a fluctuating monomer loss causes unacceptable variability in the molecular weight of the polymer product. These requirements call for the use of a distillation column to be used in conjunction with the gas-liquid polymer reactor.

It is typical to require no more than 300 ppm hexamethylene diamine loss in the vented vapors (i.e., the water vapor leaving the column must be greater than 99.9997% pure). Such high purity separations are quite costly since they require high reflux ratios and a large number of stages. However, if a reactive entrainer stream, rich in A (adipic acid), is fed to the column, then the fast ionic reaction (4) will occur on each tray below the entrainer feed point. Such an arrangement allows for very high-purity distillates in relatively small columns.

Jacobs and Zimmermann (1977) and US Patent No. 3,900,450 awarded to E. I. du Pont de Nemours & Co. (Jaswal and Pugi, 1975) describe such a process for making Nylon 6,6 (see Figure 1). In this process the main salt feed is pre-heated in the total condenser and fed to the lower part of the column (it could also be fed directly to the reboiler adjoining the reactor). The reactive entrainer feed contains adipic acid, salt, water and traces of diamine.

In summary, the separation is between components B and W using a reactive entrainer A. Components A and B react according to

and component W is nonreactive. In addition, components A and C are nonvolatile. This is an example of a perfectly selective reacting entrainer. The entrainer removes B without introducing any volatile components to contaminate the purified water vapor. The desired purities can be achieved in an industrial 12-tray column with a modest reflux ratio of 0.5. A more detailed analysis of this system is given by Grosser et al. (1987). This idea has been applied to the separation of isomeric mixtures by Corson et al. (1956), Saito et al. (1971), Holve (1977), Terrill et al. (1985), Cleary and Doherty (1985), Duprat and Gau (1991a, 1991b).

Methyl Acetate Process

High-purity methyl acetate is used in large amounts as an intermediate in the manufacture of a variety of polyesters (e.g., photographic film base, cellulose acetate, Tenite cellulosic plastics, Estron acetate for cigarette filters and textile yarns, etc., see Mayfield and Agreda (1986), Agreda (1988)). The manufacture of high-purity methyl acetate by the reaction of methanol and acetic acid is difficult because of reaction equilibrium limitations and the formation of minimum boiling azeotropes between methyl acetate and methanol, and methyl acetate and water. Conventional processes use multiple reactors with a large excess of one reactant in order to achieve high conversion of the other. Since the reaction equilibrium constant is approximately 14, and reasonably independent of temperature, the reactor product contains all four reaction components. A conventional

separation system requires eight distillation columns to break the azeotropes and tangent pinches present in the mixture (Agreda et al. 1990).

A reactive distillation process with stoichiometrically balanced feeds was invented by Agreda and Partin (1984) and commercialized by Eastman Chemical Company in 1983. A schematic of the column is shown in Figure 2. Most of the reaction takes place in the middle section of the column below the sulfuric acid catalyst feed point. The lower section of the column, below the methanol feed, is mostly a methanol-water separation to get high purity water as bottom product. The top sections of the column, above the H₂SO₄ feed point, refine the methyl acetate to give high purity product. Composition and temperature profiles for the column are reported by Agreda et al. (1990) and are shown in Figure 3. The column is, in fact, an entire chemical plant in one unit, producing 400 million lb. of high purity methyl acetate product per year (Mayfield and Agreda, 1986). Figure 3 shows clearly that, in the words of Mayfield and Agreda (1986, p. 216), "In this single column, methyl acetate can be made with no additional purification steps and with no unconverted reactant streams to be recovered". More recently, Agreda and Lilly (1990) invented a variation on this process that is capable of producing ultra high-purity methyl acetate. These processes are exceptionally economical.

There are many potential applications of Eastman's technology to other esterification reactions (see Table 1 in Barbosa and Doherty, 1988a for a selection of examples, also, most of the papers cited in the Introduction treat esterification reactions). Nitrations also have potential for being carried out by reactive distillation (Belson, 1990).

It is also possible to hydrolyze methyl acetate in a reactive distillation column, as shown in the recent experiments by Fuchigami (1990). This has potential application in polyvinyl alcohol manufacture, where methyl acetate is produced as a by-product. Hydrolysis converts methyl acetate to the more desirable products, methanol and acetic acid.

MTBE Process

In the United States the Clean Air Act of 1990 placed great emphasis on reduced emissions from automobile exhaust. In addition, the elimination of leaded gasoline and the increased demand for premium-grade fuel has led to the development of less toxic, clean burning octane enhancers. One of the preferred classes of chemicals for this purpose is the ethers; notably methyl *tert*-butyl ether (MTBE), *tert*-amyl methyl ether (TAME) and ethyl *tert*-butyl ether (ETBE). Demand for MTBE has increased rapidly in recent years, and it is reputed to be the world's fastest growing chemical (Ainsworth, 1991).

MTBE is made from methanol and isobutene in an equilibrium-limited liquid-phase reaction catalyzed by a strong acid ion-exchange resin

Typically, the isobutene is mixed with other C₄ species (mostly n-butane, isobutane and n-butenes) that are inert under the process conditions.

The conventional process is carried out in a liquid-phase catalytic reactor with a slight excess of methanol (methanol/isobutene = 1.05 - 1.2 molar) to prevent isobutene reacting with itself to form a dimer. Isobutene conversion is in the order of 90 - 95%. The inerts and reaction products are separated by distillation. This is complicated by the

presence of minimum boiling azeotropes between MTBE and methanol and isobutene and methanol. In addition, unreacted isobutene is difficult to separate from n-butane and the n-butenes because of their low relative volatilities.

A reactive distillation process was invented by Smith (1982) in which catalyst bales are packed in the middle of a distillation column, as shown in Figure 4. Since the reaction is highly exothermic it is desirable, for good energy management, to carry out most of the reaction in the primary reactor(s) before the reactive column. A near-equilibrium mixture is fed to the reactive column where the remaining isobutene is reacted to extinction. This is achieved by placing the reactive section between a non-reactive stripping section and a non-reactive rectifying section. The stripping section separates MTBE (bottom product) from the reactants, which are continually forced up into the reaction zone. The rectifying section separates the inerts (plus any excess methanol) from reacting components which are forced down into the reaction zone. The net effect is a very economical process for making MTBE. Almost all new MTBE plants use this technology.

Smith and his associates at Chemical Research and Licensing Company (CR&L) have been awarded many patents over the last decade for various embodiments of reactive distillation technology for producing MTBE (e.g., Smith (1984), Smith (1990)). In addition they have extended the technology to a wide variety of similar catalytic reactions, as noted in Table 1, and to transesterifications (Hearn, 1985). Other companies are beginning to show interest in the idea and Elf has developed its own reactive distillation process for making MTBE and other ethers using alternating catalytic and non-catalytic trays or zones (Nocca et al. (1989), Quang et al. (1989)). More recently, a joint venture between UOP, Koch Engineering and Hüls AG has developed the Ethermax process for producing ethers by reactive distillation in which the catalyst is coated on Koch's Katamax structured packing (DeGarmo et al. 1992). Meanwhile, Mobil has developed a reactive distillation process for making isooctane alkylate along the lines discussed earlier in the context of reactions (1) and (2) (Hass and Kennedy, 1990).

Simulation

The conceptual stages of design for reactive distillation have been driven largely by results obtained from bench-scale experiments with 3-4 inch diameter columns (Shoemaker and Jones (1987), Agreda et al. (1990)). Since there are many adjustable design variables, including new ones such as the placement and size of the reactive zone, there is great incentive to use computer-aided simulation to help guide the experiments. This was critical to the success of Eastman's methyl acetate process which went from concept to the start of detailed engineering for the commercial plant in less than a year (Agreda et al. 1990). In addition, computer-aided simulation is useful for scale-up (Eastman's commercial methyl acetate process was five hundred times bigger than the largest pilot plant built, Mayfield and Agreda, 1986), and for operability and control studies.

The chemical process simulation companies have responded to the challenge, and most now offer reliable and flexible packages for simulating steady-state reactive distillation columns (e.g., Venkataraman et al. (1990), Bondy (1991)).

The earliest algorithms for computer-aided steady-state simulation of staged reactive distillation columns were reported by Suzuki et al. (1971), Saito et al. (1971), and Nelson (1971). The algorithm used by Saito et al. (1971) is rather specialized since it exploits certain features of the reaction system being studied (i.e., instantaneous reaction equilibrium, etc.). The algorithms used by Suzuki et al. (1971) and Nelson (1971) are

more general, employing quasi-linearization and modified Newton-Raphson methods, respectively.

Several other equation-solving methods have been studied over the years, including Newton-Raphson and quasi-Newton methods combined with the θ -method of convergence (Komatsu and Holland (1977), Izarraraz et al. (1980), Mommessin et al. (1980), Holland (1981)), relaxation methods, i.e., the method of false transients, (Jelinek and Hlavacek (1976), Komatsu (1977)), and homotopy-continuation (Chang and Seader (1988), Bondy (1991)). Continuation methods appear to work very reliably, as they do for many other classes of difficult problems.

Much less has been published on steady-state simulation of distillation with chemical reaction in packed columns, even though they occupy an important place in commercial applications. The only studies to be found in the literature are by Sawistowski and Pilavakis (1979, 1988) who developed a steady-state mass-transfer model for the two-phase reacting system which incorporates the kinetics of chemical reaction in the liquid phase as well as the effect of reaction on the fluxes.

Roat et al. (1986) report that steady-state simulations are inadequate for assessing the effectiveness of operability and control schemes for reactive distillation columns. Using a modified version of Eastman's methyl acetate column, they show that control schemes with good steady-state measures frequently fail under dynamic conditions, and that the failure was discovered only by using the full nonlinear dynamic simulation. To our knowledge, this is the only paper in the literature that addresses dynamic simulation of reactive distillation columns. There are good opportunities for productive research in this area, including such effects as the existence of multiple steady-states in reactive distillation systems and strategies for operating at the desired one.

Design Methods: Equilibrium Chemical Reactions

Design should not be confused with simulation. In design, we specify the state of the feeds to a system together with targets on the output streams (e.g., desired purities of selected components) and the goal is to find equipment sizes and configurations, together with operating conditions that will do the job economically. The biggest difficulty encountered in design is identifying feasible equipment configurations and ranges of operating conditions that are capable of meeting the desired process goals. For complex systems, such as reactive distillations, this is a non-trivial problem.

Simulation is the complement of this, where we specify the state of the feeds, the equipment sizes, values for all independent design variables and the equipment configuration, and calculate the values of the remaining variables, including the state of the product streams. Design, therefore, is that activity which logically takes place before simulation; the two are complementary in a natural way.

Steady-state simulation methods for reactive distillation are in good order and can be expected to improve further in the coming years. Design methods, on the other hand, have not received the attention they deserve and design tools are only available for the special case of equilibrium chemical reactions.

Equilibrium chemical reactions necessarily affect the structure and properties of the phase diagrams for the mixture undergoing reaction and thereby affect the feasibility of distillation. They do so not because of any extra nonidealities or effects of that sort, but

because they restrict the allowable range of temperatures and phase compositions by virtue of the additional equation(s) for chemical equilibrium. The effect of these restrictions can be quite startling. For example, the condition for azeotropy in reactive mixtures is *not* equality of compositions across phases ($y_i = x_i$, $i = 1, \dots, c$) but instead

$$\frac{y_1 - x_1}{v_1 - v_T x_1} = \frac{y_i - x_i}{v_i - v_T x_i} \quad i = 2, \dots, c \quad (7)$$

where

$$v_T = \sum_{i=1}^c v_i \quad (8)$$

This equation was derived by Barbosa and Doherty (1987a) and is discussed in detail in Barbosa and Doherty (1987b, 1988a, 1988b). Phase compositions that satisfy Eq. (7) are called *reactive-azeotropes* and correspond to stationary points on the phase diagram. Reactive azeotropes limit the products of a reactive distillation in exactly the same way that ordinary azeotropes limit the products of non-reactive distillations.

It is interesting, and important, to note that reactive-azeotropes can occur in *ideal* mixtures; moreover, chemical reaction can eliminate ordinary azeotropes from nonideal mixtures (Barbosa and Doherty, 1988a, 1988b). The physical explanation for the formation of reactive-azeotropes in both ideal and nonideal mixtures is quite simple. A temperature is reached where the rate of vaporization (or condensation) and the rate of reaction of each species are such that vaporization (or condensation) occurs without change of composition in either phase. This is precisely what is meant by an azeotropic state or transformation.

For isobaric liquid-vapor systems with a single chemical reaction, the number of degrees of freedom, F , is $F = c - 2$, where c is the total number of species present. For ternary mixtures this means that one of the compositions in one of the phases can be specified, and all remaining compositions, as well as the equilibrium temperature, are determined from the combined equations for phase and chemical equilibrium. Isobaric phase behavior for such mixtures is represented by a pair of *curves* in the temperature-composition prism, as opposed to a pair of *surfaces* for non-reactive systems.

As an example, consider a mixture of isobutene, methanol and MTBE at 1 atm pressure. The non-reactive mixture has two minimum-boiling binary azeotropes, one between methanol and MTBE, the other between methanol and isobutene. The phase diagram is conveniently represented in terms of its residue curve map, shown in Figure 5. There is a distillation boundary that connects the two azeotropes and which divides the composition triangle into two simple distillation regions. According to the methods developed recently for homogeneous azeotropic distillation (Doherty and Caldarola (1985), Foucher et al. (1990), Julka and Doherty (1990), Fidkowski et al. (1991)) a non-reactive column with a feed in the lower distillation region (typical of the reactor product composition from a liquid-phase MTBE reactor) is capable of delivering either of the following splits, depending on the column design:

- (1) distillate:- pure isobutene, bottom:- binary mixture of methanol + MTBE
- or
- (2) distillate:- ternary mixture of isobutene + methanol + MTBE with a composition in the vicinity of the distillation boundary, bottom:- pure MTBE

In either case further separation is required to break the azeotrope(s).

When the components are allowed to react according to Eq. (6) the reactive phase diagram in the T-x-y prism is shown in Fig. 6(a). The projection onto the temperature-isobutene face is shown in Figure 6(b). Notice that *both* non-reactive azeotropes have disappeared. Notice also (from the equilibrium curve on the base of Figure 6(a)) that it is not possible to obtain pure MTBE in either phase, although the maximum equilibrium composition of MTBE in the liquid phase is quite close to the MTBE vertex.

What is not obvious from either Figure 6(a) or Figure 6 (b) is the presence of a ternary reactive azeotrope (or severe tangent pinch) in this mixture. This can be seen more clearly if the phase diagram is plotted in different coordinates. Barbosa and Doherty (1987b, 1988b) pointed out that mole fractions are not the most convenient measures of composition for equilibrium reactive mixtures. It is more convenient to use transformed compositions, X_i , which represent the equivalent amount of reactants present in the equilibrium mixture. For reactions of the form

these variables are given by¹

$$X_A = \frac{x_A - (v_A/v_C) x_C}{1 - (v_T/v_C) x_C} \quad (10a)$$

$$X_B = \frac{x_B - (v_B/v_C) x_C}{1 - (v_T/v_C) x_C} \quad (10b)$$

The transformed composition variables have two convenient properties; they have the same numerical values *before* and *after* reaction, and they sum to unity

$$X_A + X_B = 1 \quad (11)$$

Therefore, only one of them is independent, which is in agreement with the number of independent compositions provided by the Gibbs Phase Rule. Phase diagrams plotted in terms of these variables tend to take on familiar shapes; moreover, the condition for reactive azeotropy (Eq. 7) when expressed in terms of transformed compositions assumes a more familiar form

$$X_i = Y_i \quad (12)$$

¹ The variables used here are due to Ung (1992). They are linearly related to the transforms proposed by Barbosa and Doherty (1987b, 1988b), but have more convenient properties.

Phase diagrams in transformed coordinates are shown in Figure 6 (c) ($T-X_1-Y_1$) and Figure 6 (d) (Y_1-X_1) for the reacting mixture of isobutene (component 1), methanol (2) and MTBE (3) at 1 atm pressure. They clearly indicate the presence of a reactive azeotrope (or severe tangent pinch) near the maximum composition of MTBE. This is very fortunate since it prevents the reactive section of a distillation column from taking the intermediate-boiling component, MTBE (b.p. 55.1°C at 1 atm) and forcing the reaction (Eq. 6) in the backwards direction (by Le Chatelier's Principle) to produce the light component, isobutene (-6.9°C), at the top of the reactive section, and the heavy component, methanol (64.7°C), at the bottom.

It is evident from Figure 6 (d) that equilibrium reactive systems of the type described by Eq. (9) have Y-X diagrams similar to the y-x diagrams for non-reactive binary mixtures. Barbosa (1987) has derived design equations for minimum reflux, number of stages, etc., for this class of systems in terms of the transformed coordinates X and Y. The method has been extended to reactions of the type

(e.g., the methyl acetate reaction) by Barbosa and Doherty (1988c, 1988d). They treat minimum reflux and design of both single- and double-feed columns, and present some initial ideas about column sequencing.

Design Methods: Kinetically Controlled Reactions

It is not always economical to operate reactive distillation columns close to reaction equilibrium conditions. In order to determine the effect of liquid holdup on the column design and economics it is necessary to have a design procedure that accommodates reaction kinetics. No such procedure has been published in the literature, although progress in this direction has been made by Buzad (1992). A summary of the ideas is given here; a more complete picture will be published separately.

Consider a reaction of the type

We assume that components A, B and C form an ideal liquid mixture and that the rate of reaction per mole of mixture is given by

$$r_A = r_B = k_f \left(x_3^2 - \frac{x_1 x_2}{K} \right) \quad (14)$$

where k_f is the forward rate constant (with units of inverse time) and K is the thermodynamic reaction equilibrium constant. Components 1, 2 and 3 correspond to A, B and C, respectively. For simplicity, we assume a single feed column, a saturated liquid feed, constant molar overflow (implies negligible heat of reaction), and that the molar liquid holdup is the same on each stage. For realistic design calculations it is necessary, and straightforward, to remove all these restrictions.

Material balances around the rectifying section, the stripping section, and the entire column give

Overall

$$x_{F,i} - \frac{D/B}{D/B + 1} x_{D,i} - \frac{1}{D/B + 1} x_{B,i} + Da \sum_{j=1}^{N_T} (x_{j,3}^2 - \frac{x_{j,1} x_{j,2}}{K}) = 0 \quad i=1,2 \quad (15)$$

Rectifying Section

$$y_{m+1,i} - \frac{r}{r+1} x_{m,i} - \frac{1}{r+1} x_{D,i} + \frac{F}{V} Da \sum_{j=1}^M (x_{j,3}^2 - \frac{x_{j,1} x_{j,2}}{K}) = 0 \quad i = 1, 2 \quad (16)$$

where m represents the stage index for the rectifying section, increasing down the column.

Stripping Section

$$x_{n+1,i} - \frac{s}{s+1} y_{n,i} - \frac{1}{s+1} x_{B,i} + \frac{F}{L_B} Da \sum_{j=1}^N (x_{j,3}^2 - \frac{x_{j,1} x_{j,2}}{K}) = 0 \quad i = 1, 2 \quad (17)$$

where n represents the stage index for the stripping section, increasing up the column.

In addition, we find

$$\frac{F}{V} = \frac{D/B + 1}{s}; \quad \frac{F}{L_B} = \frac{D/B + 1}{s + 1}; \quad \frac{D}{B} = \frac{s}{r + 1} \quad (18)$$

The Damkohler number, Da, which appears in Eqs. (15), (16) and (17) is a dimensionless quantity defined by $Da = H k_f / F$ and represents the ratio of a characteristic liquid residence time to the reaction time. Larger values of Da correspond to conditions closer to chemical equilibrium (i.e., "more reaction").

For given feed conditions and column pressure, this design model has five degrees of freedom, which we take to be the distillate and bottoms compositions (two mole fractions in each stream) and Da. The boundary value design procedure involves specifying these quantities and solving the finite difference model equations from the ends of the column towards the middle. If the target product compositions are feasible, then for the given value of Da there will be a *single* value of the reflux ratio (and corresponding number of stages in each column section) that satisfies the design equations. Unlike non-reactive distillation, there is no trade-off between r and N_T for fixed product purities and a specified value of Da.

In order to fix ideas we present two simple examples.

Example 1. Consider a column with pure reactant C as feed. The reactant undergoes an irreversible reaction

(i.e., K is set equal to a large number in Eqs. (14) to (17)). Component A is the lightest, B is the heaviest and C is intermediate boiling. They form an ideal mixture with constant

relative volatilities given by $\alpha_{AB} = 5$, $\alpha_{CB} = 3$. The objective is to obtain components A and B from the reactive distillation column in reasonably high purity.

For design purposes we specify a target distillate composition of $x_{D,1} = 0.99$, $x_{D,2} = 0.005$ and a bottoms composition of $x_{B,1} = 0.005$, $x_{B,2} = 0.99$. The final specification is $Da = 3$. The solution to the design equations is shown in Figure 7 (a). There are 8.8 stages in the stripping section and 20 stages in the rectifying section. The corresponding values of r and s are 0.77 and 1.77, respectively. The sections of the composition profiles beyond the second intersection have no physical meaning.

In order to check these results we simulated the reactive distillation column using a steady-state simulator. As with the design approach, the feed composition, feed quality and column pressure are given, leaving five degrees of freedom to be specified. These are taken to be the reflux and reboil ratios, the total number of stages, the feed stage and a value for the Damkohler number. The simulation results are shown in Figure 7 (b), which agree well with the design shown in Figure 7 (a).

Example 2. We now consider the case of a reversible reaction

with an equilibrium constant $K = 0.25$, which is assumed to be independent of temperature. The relative volatilities of components A, B and C remain unchanged.

In order to make the graph clearer, we specify a target distillate composition of $x_{D,1} = 0.80$, $x_{D,2} = 0.0025$ and a bottoms composition of $x_{B,1} = 0.010$, $x_{B,2} = 0.80$. Since the products are low-purity, not as much reaction is required, and we take Da to be 0.095. The resulting design is shown in Figure 8. There are 12.8 stages in the stripping section, 12.2 stages in the rectifying section, and the values of r and s are 2.51 and 3.48, respectively. The loop in the composition profile again disappears as the value of Da is increased.

Conclusions

Rapid progress has been made recently on the application and design of reactive distillation technology. The field has matured to the point where definite gaps in our knowledge can be identified. Research opportunities exist in many areas; a few personal favorites are discussed briefly below.

Thermodynamics. Phase equilibrium data for reactive mixtures are scarce. New VLE data for any of the reactions shown in Table 1 (or Table 1 of Barbosa and Doherty, 1988a) would be an excellent contribution to the field. The data can be represented quite efficiently using transformed composition coordinates, as described earlier in the article.

Simulation. Little has been published on steady-state simulation of packed-bed reactive distillation columns. There are good opportunities here for applying concepts and methods from reaction engineering to the distillation arena. Dynamic simulation of both packed and staged columns is practically virgin territory.

Synthesis and Design. Almost nothing systematic has been published on the synthesis of reactive separation systems. This is an important topic worthy of research. Design methods for equilibrium reactive systems are in good order, but little is known about the design of kinetically controlled systems.

Notation

B	bottoms flow rate (moles/time)
c	number of components in a mixture
Da	Damkohler number ($H k_f/F$, dimensionless)
D	distillate flow rate (moles/time)
F	feed flow rate to column (moles/time)
H	liquid holdup per stage (moles)
k_f	forward rate constant (s^{-1})
K	reaction equilibrium constant
L_B	liquid flow rate in stripping section (moles/time)
M	total number of reactive stages in the rectifying section
N_T	total number of reactive stages in the column
N	total number of reactive stages in the stripping section
r	reflux ratio
s	reboil ratio
T	temperature
V	vapor flow rate in column (moles/time)
x_i	mole fraction of component i in the liquid phase
y_i	mole fraction of component i in the vapor phase
v_i	stoichiometric coefficient, positive for products, negative for reactants
v_T	sum of all the stoichiometric coefficients in a reaction, Eq. (8)

Subscripts

B	bottom
D	distillate
F	feed
i	species

References

- Agreda, V. H., and L. R. Partin, "Reactive Distillation Process for the Production of Methyl Acetate", US Patent No. 4,435,595, March 6 (1984).
- Agreda, V. H., "Acetic Anhydride From Coal", *ChemTech*, 250-253, April (1988).
- Agreda, V. H., L. R. Partin and W. H. Heise, "High-Purity Methyl Acetate via Reactive Distillation", *Chem. Eng. Progr.*, 86 (2), 40 - 46 (1990).
- Agreda, V. H. and R. D. Lilly, "Preparation of Ultra High Purity Methyl Acetate", US Patent No. 4,939,294, July 3 (1990).
- Ainsworth, S. J., "Booming MTBE Demand Draws Increasing Number of Producers", *Chem. Eng. News*, June 10, 13-16 (1991).
- Backhaus, A. A., "Continuous Process for the Manufacture of Esters", US Patent No. 1,400,849, December 20 (1921a).
- Backhaus, A. A., "Apparatus for the Manufacture of Esters", US Patent No. 1,400,850, December 20 (1921b).
- Backhaus, A. A., "Apparatus for the Production of Esters", US Patent No. 1,400,851, December 20 (1921c).
- Backhaus, A. A., "Method for the Production of Esters", US Patent No. 1,400,852, December 20 (1921d).
- Backhaus, A. A., "Apparatus for Producing High-Grade Esters", US Patent No. 1,403,224, January 10 (1922a).
- Backhaus, A. A., "Apparatus for Esterification", US Patent No. 1,403,225, January 10 (1922b).
- Backhaus, A. A., "Apparatus for the Manufacture of Esters", US Patent No. 1,425,624, August 15 (1922c).
- Backhaus, A. A., "Process for the Manufacture of Esters", US Patent No. 1,425,625, August 15 (1922d).
- Backhaus, A. A., "Method for the Production of Ester-Condensation Products", US Patent No. 1,425,626, August 15 (1922e).
- Backhaus, A. A., "Process of Producing High-Grade Esters", US Patent No. 1,454,462, May 8 (1923a).
- Backhaus, A. A., "Process of Esterification", US Patent No. 1,454,463, May 8 (1923b).
- Bakshi, A., L. Smith, E. Jones and T. P. Hickey, "Low Cost Octane Enhancement. Catalytic Distillation Route", paper presented at EFCE Meeting, Distillation Perspectives, Amsterdam, Netherlands (1991).

- Barbosa, D., Ph.D. Dissertation, University of Massachusetts, Amherst (1987).
- Barbosa, D. and M. F. Doherty, "The Theory of Phase Diagrams and Azeotropic Conditions for Two-Phase Reactive Systems", *Proc. R. Soc. Lond.*, **A413**, 443-458 (1987a).
- Barbosa, D. and M. F. Doherty, "A New Set of Composition Variables For the Representation of Reactive Phase Diagrams", *Proc. R. Soc. Lond.*, **A413**, 459-464 (1987b).
- Barbosa, D. and M. F. Doherty, "The Influence of Equilibrium Chemical Reactions on Vapor-Liquid Phase Diagrams", *Chem. Eng. Sci.*, **43**, 529-540 (1988a).
- Barbosa, D. and M. F. Doherty, "The Simple Distillation of Homogeneous Reactive Mixtures", *Chem. Eng. Sci.*, **43**, 541-550 (1988b).
- Barbosa, D. and M. F. Doherty, "Design and Minimum Reflux Calculations for Single-Feed Multicomponent Reactive Distillation Columns", *Chem. Eng. Sci.*, **43**, 1523-1537 (1988c).
- Barbosa, D. and M. F. Doherty, "Design and Minimum Reflux Calculations for Double-Feed Multicomponent Reactive Distillation Columns", *Chem. Eng. Sci.*, **43**, 2377-2389 (1988d).
- Belck, L. H., "Continuous Reactions in Distillation Equipment", *AIChE J.*, **1**, 467-470 (1955).
- Belson, D. J., "A Distillation Method of Aromatic Nitration Using Azeotropic Nitric Acid", *Ind. Eng. Chem. Res.*, **29**, 1562-1565 (1990).
- Berman, S., H. Isbenjian, A. Sedoff and D. F. Othmer, "Esterification. Continuous Production of Dibutyl Phthalate in a Distillation Column", *Ind. Engng Chem.*, **40**, 2139-2148 (1948).
- Bondy, R. W., "Physical Continuation Approaches to Solving Reactive Distillation Problems", paper presented at AIChE Meeting, Los Angeles (1991).
- Buzad, G., Ph.D. Dissertation (in progress), University of Massachusetts, Amherst (1992).
- Carney, S. G., "Process and Apparatus for Conducting Chemical Reactions", US Patent No. 2,081,322, May 25 (1937).
- Chang, Y. A. and J. D. Seader, "Simulation of Continuous Reactive Distillation by a Homotopy-Continuation Method", *Comput. Chem. Engng*, **12**, 1243-1255 (1988).
- Cleary, W. and M. F. Doherty, "The Separation of Closely Boiling Mixtures by Reactive Distillation II. Experiments", *Ind. Eng. Chem. Process Des. Dev.*, **24**, 1071-1073 (1985).
- Corrigan, T. E. and W. R. Ferris, "A Development Study of Methanol Acetic Acid Esterification", *Can. J. Chem. Eng.*, **47**, 334-335 (1969).

- Corson, B. B., W. J. Heintzelman, R. C. Odioso, H. E. Tiefenthal and F. J. Pavlik, "Separation of Positional Isomeric Dialkylbenzenes", *Ind. Engng Chem.*, **48**, 1180-1182 (1956).
- DeGarmo, J. L., V. N. Parulekar and V. Pinjala, "Consider Reactive Distillation", *Chem. Eng. Progr.*, **88** (3), 43-50 (1992).
- Doherty, M. F. and G. A. Caldarola, "Design and Synthesis of Homogeneous Azeotropic Distillations III. The Sequencing of Columns for Azeotropic and Extractive Distillations", *Ind. Eng. Chem. Fundam.*, **24**, 474-485 (1985).
- Duprat, F. and G. Gau, "Reactive Distillation of Pyridine Mixtures with an Organic Acid. I. Determination of the Reactive Distillation Equilibrium", *Can. J. Chem. Eng.*, **69**, 1320-1326 (1991).
- Duprat, F. and G. Gau, "Reactive Distillation of Pyridine Mixtures with an Organic Acid. II. Parametric Sensitivity and Optimization of the Process", *Can. J. Chem. Eng.*, **69**, 1327-1335 (1991).
- Fidkowski, Z. T., M. F. Malone and M. F. Doherty, "Nonideal Multicomponent Distillation: Use of Bifurcation Theory for Design", *AIChE J.*, **37**, 1761-1779 (1991).
- Foucher, E. R., M. F. Doherty and M. F. Malone, "Automatic Screening of Entrainers For Homogeneous Azeotropic Distillation", *Ind. Eng. Chem. Res.*, **30**, 760-772 (1991).
- Fuchigami, Y., "Hydrolysis of Methyl Acetate in Distillation Column Packed with Reactive Packing of Ion Exchange Resin", *J. Chem. Eng. Japan*, **23**, 354-358 (1990).
- Gaikar, V. G. and M. M. Sharma, "Separations Through Reactions and Other Novel Strategies", *Sep. Purif. Meth.*, **18**, 111-176 (1989).
- Grosser, J. H., M. F. Doherty and M. F. Malone, "Modeling of Reactive Distillation Systems", *Ind. Eng. Chem. Res.*, **26**, 983-989 (1987).
- Hass, A. and C. R. Kennedy, "Hydrocarbon Processes Comprised of Catalytic Distillation Using Lewis Acid Promoted Inorganic Oxide Catalyst Systems", US Patent No. 4,935,577, June 19 (1990).
- Hearn, D., "Transesterification Method", US Patent No. 4,510,336, April 9 (1985).
- Hofmann, H., "Berechnung von Reaktoren für Gemischtpase-Reaktionen", *Chem. Eng. Sci.*, **8**, 113-122 (1958).
- Holland, C. D., *Fundamentals of Multicomponent Distillation*, McGraw-Hill, New York (1981). Chapter 8.
- Holve, W. A., "Theoretical Analysis of Changes in Relative Volatility via Reversible Metalation Reactions and Application to Fractionation", *Ind. Eng. Chem. Fundam.*, **16**, 1-7 (1977).

- Izarraraz, A., G. W. Bentzen, R. G. Anthony and C. D. Holland, "Solve More Distillation Problems. Part 9 - When Chemical Reactions Occur", *Hydrocarbon Processing*, 59(4), 195-203 (1980).
- Jacobs, D. B. and J. Zimmermann, In *Polymerization Processes*, Schildknecht, C. E., ed., Wiley, New York (1977). Chapter 12.
- Jaswal, I. and K. Pugi, "Preparation of Polyamides by Continuous Polymerization", US Patent No. 3,900,450, August 19 (1975).
- Jelinek, J. and V. Hlavacek, "Steady State Countercurrent Equilibrium Stage Separation with Chemical Reaction by Relaxation Method", *Chem. Eng. Comm.*, 2, 79-85 (1976).
- Julka, V. and M. F. Doherty, "Geometric Behavior and Minimum Flows for Nonideal Multicomponent Distillation", *Chem. Eng. Sci.*, 45, 1801-1822 (1990).
- Keyes, D. B., "Esterification Processes and Equipment", *Ind. Engng Chem.*, 24, 1096-1103 (1932).
- Komatsu, H., "Application of the Relaxation Method for Solving Reacting Distillation Problems", *J. Chem. Eng. Japan*, 10, 200-205 (1977).
- Komatsu, H. and C. D. Holland, "A New Method of Convergence for Solving Reacting Distillation Problems", *J. Chem. Eng. Japan*, 10, 292-297 (1977).
- Leyes, C. E. and D. F. Othmer, "Continuous Esterification of Butanol and Acetic Acid, Kinetic and Distillation Considerations", *Trans. Am. Inst. Chem. Engrs*, 41, 157-196 (1945).
- Longtin, B. and M. Randall, "Simultaneous Chemical Reaction and Fractional Distillation. Isomerization", *Ind. Eng Chem.*, 34, 292-295 (1942).
- McKeon, T. J., C. Pyle and R. T. Van Ness, "Process for Continuous Esterification", US Patent No. 2,208,769, July 23 (1940).
- McKeon, T. J., "Process for Continuous Esterification". US Patent No. 2,208,770, July 23 (1940).
- Mayfield, G. G. and V. H. Agreda, "The Eastman Chemical Process for Acetic Anhydride From Coal", *Energy Progr.*, 6, 214-218 (1986).
- Mommessin, P. E., G. W. Bentzen and C. D. Holland, "Solve More Distillation Problems. Part 10 - Another Way to Handle Reactions", *Hydrocarbon Processing*, 59 (7), 144-148 (1980).
- Nelson, P. A., "Countercurrent Equilibrium Stage Separation with Reaction", *AIChE J.*, 17, 1043-1049 (1971).
- Nocca, J.-L., J. Leonard, J.-F. Gaillard and P. Amigues, "Process for Manufacturing a Tertiary Alkyl Ether by Reactive Distillation", US Patent No. 4,847,431, July 11, (1989).

- Quang, D. V., J.-F. Gaillard, J. Leonard and J.-L. Nocca, "Process for Manufacturing a Tertiary Alkyl Ether by Reactive Distillation", US Patent No. 4,847,430, July 11 (1989).
- Roat, S. D., J. J. Downs, E. F. Vogel and J. E. Doss, "The Integration of Rigorous Dynamic Modeling and Control System Synthesis for Distillation Columns: An Industrial Approach", in *Chemical Process Control - CPC III*, Morari, M. and T. J. McAvoy, eds, Elsevier, New York (1986).
- Saito, S., T. Michishita and S. Maeda, "Separation of meta- and para-Xylene Mixture by Distillation Accompanied by Chemical Reactions", *J. Chem. Eng. Japan*, 4, 37-43 (1971).
- Sawistowski, H. and P. A. Pilavakis, "Distillation with Chemical Reaction in a Packed Column", *I. Chem. E. Symp. Ser.*, No. 56, 4.2/49-4.2/63 (1979).
- Sawistowski, H. and P. A. Pilavakis, "Performance of Esterification in a Reaction-Distillation Column", *Chem. Eng. Sci.*, 43, 355-360 (1988).
- Schoenemann, K., "Die Anwendung der Reaktionskinetik bei der Berechnung einiger typischer technischer Reaktoren", *Chem. Eng. Sci.*, 8, 161-176 (1958).
- Sharma, M. M., "Separations Through Reactions", *J. Separ. Proc. Technol.*, 6, 9-16 (1985).
- Shoemaker, J. D. and E. M. Jones, "Cumene by Catalytic Distillation", *Hydrocarbon Processing*, June, 57-58 (1987).
- Smith, L. A., "Catalytic Distillation Process", US Patent No. 4,307,254, December 22 (1981).
- Smith, L. A., "Catalytic Distillation Structure". US Patent No. 4,443,559, April 17 (1984).
- Smith, L. A., "Method for the Preparation of Methyl Tertiary Butyl Ether", US Patent No. 4,978,807, December 18 (1990).
- Smith, L. A., E. M. Jones and D. Hearn, "Catalytic Distillation - A New Chapter in Unit Operations", paper presented at Spring Meeting of AIChE, Houston (1991).
- Steppan, D. D., M. F. Doherty and M. F. Malone, "A Kinetic and Equilibrium Model for Nylon 6,6 Polymerization", *J. Appl. Polymer Sci.*, 33, 2333-2344 (1987).
- Steppan, D. D., M. F. Doherty and M. F. Malone, "A Flowing Film Model for Continuous Nylon 6,6 Polymerization", *Ind. Eng. Chem. Res.*, 28, 1324-1332 (1989).
- Suzuki, I., H. Yagi, H. Komatsu and M. Hirata, "Calculation of Multicomponent Distillation Accompanied by a Chemical Reaction", *J. Chem. Eng. Japan*, 4, 26-33 (1971).
- Terrill, D. L., L. F. Sylvestre and M. F. Doherty, "Separation of Closely Boiling Mixtures by Reactive Distillation. 1. Theory", *Ind. Eng. Chem. Proc. Des. Dev.*, 24, 1062-1071 (1985).

- Ung, S., Ph.D. Dissertation (in progress), University of Massachusetts, Amherst (1992).
- Velo, E., L. Puigjaner and F. Recasens, "Inhibition by Product in the Liquid-Phase Hydration of Isobutene to *tert*-Butyl Alcohol: Kinetics and Equilibrium Studies", *Ind. Eng. Chem. Res.*, 27, 2224-2231 (1988).
- Venkataraman, S., W. K. Chan and J. F. Boston, "Reactive Distillation Using ASPEN PLUS", *Chem. Eng. Progr.*, 86 (8), 45-54 (1990).

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

Table 1. Reactive Distillation Processes For Reactions of the Type $A + B \rightleftharpoons C$

Reaction	Reference	Assignee
isobutene ¹ + methanol $\rightleftharpoons$ MTBE ²	Smith (1984, 1990, 1991)	CR & L
isobutene + ethanol $\rightleftharpoons$ ETBE ³	Bakshi et al. (1991)	CR & L
isoamylene ⁴ + methanol $\rightleftharpoons$ TAME ⁵	Bakshi et al. (1991)	CR & L
isobutene + H ₂ O $\rightleftharpoons$ <i>tert</i> -butyl alcohol ⁶	Velo et al. (1988), Smith (1990)	CR & L
benzene + propylene $\rightleftharpoons$ cumene	Shoemaker and Jones (1987), Smith (1990)	CR & L
benzene + ethylene $\rightleftharpoons$ ethyl benzene	Smith et al. (1991)	CR & L
isobutane + 1-butene $\rightleftharpoons$ isooctane	Hass and Kennedy (1990)	Mobil

1. isobutene = 2-methyl pentene ($\text{CH}_3 - \text{C} = \text{CH}_2$)

2. MTBE = methyl *tert*-butyl ether ($\text{CH}_3 - \text{C} - \text{O} - \text{CH}_3$)

3. ETBE = ethyl *tert*-butyl ether ($\text{CH}_3 - \text{C} - \text{O} - \text{C}_2\text{H}_5$)

4. isoamylene is a mixture of 2-methyl 1-butene ($\text{CH}_3 = \text{C} - \text{CH}_2 - \text{CH}_3$)

and 2-methyl 2-butene ($\text{CH}_3 - \text{C} = \text{CH} - \text{CH}_3$)

5. TAME = *tert*-amyl methyl ether ($\text{CH}_3 - \text{CH}_2 - \text{C} - \text{O} - \text{CH}_3$)

6. *tert*-butyl alcohol = $\text{CH}_3 - \text{C} - \text{OH}$

Figure 1. Reactive distillation column for Nylon 6, 6 polymerization.
(Redrawn from Grosser, et al., 1987.)

Figure 2. Methyl acetate reactive distillation column.

Figure 3. (a) Composition and (b) temperature profiles for the Eastman methyl acetate column. (Redrawn from Agreda, et al., 1990.)

Figure 4. Catalytic distillation process for MTBE

Figure 5. Residue curve map for a nonreactive mixture of isobutene, methanol and MTBE.

(a)

(b)

(c)

(d)

Figure 6. Phase diagrams for a reactive mixture isobutene (1) + methanol (2) $\rightleftharpoons$ MTBE (3) at 1 atm pressure ($50 < K < 1600$). (a) T - x - y prism, (b) projection onto the T-isobutene face, (c) phase diagram in transformed coordinates T - X_1 - Y_1 , (d) Y_1 - X_1 diagram.

Figure 7. (a) Design calculations for the irreversible reaction $2C \rightarrow A + B$, and (b) simulation.

Figure 8. Design calculations for the reaction $2C \rightleftharpoons A + B$. Dashed line represents the reaction equilibrium curve.

END

**DATE
FILMED**

3 / 29 / 93