**STUDY OF LONG TERM OPTIONS
FOR
ELECTRIC VEHICLE AIR CONDITIONING**

**John Dieckmann
David Mallory**

Published July 1991

**Arthur D. Little
Cambridge, MA 02140**

**Prepared for EG&G Idaho, Inc.
Under Subcontract C89-102531
and for the
Idaho National Engineering Laboratory
U.S. Department of Energy
Assistant Secretary for Conservation and Renewable Energy (CE)
Under DOE Contract No. DE-AC07-76ID01570**

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

Table of Contents

1.0 Introduction	1-1
1.1 Project Approach	1-1
1.2 Scope of Work Summary	1-2
2.0 Summary	2-1
2.1 Vehicle Heating and Cooling Loads	2-1
2.1.1 Vehicle Thermal Load Model	2-1
2.1.2 Seasonal Range Of Heating And Cooling Loads	2-2
2.2 Evaluation of Cooling and Heating Cycles	2-4
2.2.1 Objective	2-4
2.2.2 Approach	2-5
2.2.3 Results	2-8
3.0 Vehicle Thermal Load Model	3-1
3.1 Detailed Model Description	3-3
3.1.1 Ventilation Loads	3-3
3.1.2 Metabolic Loads	3-4
3.1.3 Solar Loads	3-4
3.1.4 Conduction Loads	3-6
3.1.5 Transient Calculations	3-8
3.2 Vehicle Cooling Loads	3-9
3.3 Heating Loads	3-11
3.4 Comparison Of Results Of The Model With Wind Tunnel Test Data	3-11
4.0 Comparison Of Thermal Design Options	4-1
4.1 Description Of Thermal Design Options	4-1
4.1.1 Ventilation	4-1
4.1.2 Solar Load - Glazing Options	4-1
4.1.3 Conduction	4-2
4.1.4 Transient	4-3
4.2 Evaluation Of Thermal Design Options	4-3
4.2.1 Steady State Cooling Loads	4-6
4.2.2 Transient Cooling Loads	4-7
4.2.3 Steady State Heating Loads	4-7
5.0 Heat Pump Cycle Heating	5-1
5.1 Fuel Fired Heating Systems	5-3
5.2 Back-up Heat Sources	5-3
5.3 Ambient Air Coil Defrosting	5-7
5.4 Windshield Deicing	5-9

Table of Contents (Continued)

6.0 Vapor Cycle Cooling and Heating	6-1
6.1 Vapor Cycle Performance Characteristics - Selected Variable Speed System Configuration	6-7
6.1.1 Cooling Mode Performance	6-7
6.1.2 Heating Mode Performance	6-10
6.2 Non-CFC Alternatives to CFC-12	6-12
HFC-134a	6-13
Ternary Blend (HCFC-22/HFC-152a/HCFC-124)	6-15
HCFC-22	6-15
HFC-152a	6-16
HC-290 (Propane)	6-16
7.0 Alternative Cycles	7-1
7.1 Reverse Brayton Cooling Cycle	7-1
7.1.1 Simple Brayton Cooling Cycle	7-6
7.1.2 Open Reverse Brayton Cycle With Recuperator	7-8
7.1.3 Open Reverse Brayton Cycle With Moisture Removal Heat Exchanger	7-9
7.1.4 Membrane Water Removal	7-9
7.1.5 Reversed Heat Pump Cycle Operation	7-11
7.2 Reverse Stirling Cooling Cycle Systems	7-12
7.2.1 Performance Characteristics	7-14
Efficiency.	7-15
Capacity Characteristics (heat pump applications only).	7-17
System Configuration/Size.	7-18
Life/Reliability.	7-19
7.2.2 Stirling Cycle Heating Mode Operation	7-19
7.2.3 Capacity Variation	7-20
7.3 Magnetic Refrigeration Cycles	7-20
Appendix A Sample Input of Load Model	A-1
Appendix B Sample Output of Load Model	B-1
Appendix C Thermal Load Model Output for Electric G-Van at Wind Tunnel Test Conditions	C-1
Appendix D Thermal Load Model Output for EPRI Electric TE Van at Wind Tunnel Test Conditions	D-1
Appendix E Detailed Cooling and Heating Performance Estimates for Vapor Cycle Variations	E-1

Table of Figures

Figure 2-1	Mini-van Cooling Loads	2-6
Figure 2-2	Mini-van Heating Loads	2-7
Figure 2-3	Steady State Heating of Baseline Mini-van, Using Vehicle Waste Heat, Vapor Cycle Heat Pump, and Backup Electric Resistance Heat to the Extent Necessary	2-13
Figure 2-4	Transient Heating of Baseline Mini-van, Using Vapor Cycle Heat Pump, and Backup Electric Resistance heat to the Extent Necessary	2-13
Figure 2-5	Transient Heating Energy Consumption	2-14
Figure 3-1	Solar Radiation Angles for Windshield Case	3-5
Figure 3-2	Motor Vehicle Heat Transfer Characteristics	3-6
Figure 3-3	PG&E Electric G-Van Wind Tunnel Tests	3-12
Figure 3-4	Comparison of the Thermal Load Model Interior Air Temperature Cool Down Characteristic with Wind Tunnel Test Data of PG&E's Electric G-Van During a Standard GM Pulldown Test	3-14
Figure 5-1	Heat Load and Heating Capacity Relationship	5-2
Figure 5-2	Use of Liquid Cooling Loop for Major EV Driveline Components for Vehicle Interior Heating	5-5
Figure 5-3	Representative Driveline Component Efficiencies	5-6
Figure 5-4	Water Heat Storage to Modification to a Vapor Cycle Heat Pump to Supply Heat Required for Defrost Cycle	5-8
Figure 6-1	Baseline Constant Speed Belt Driven Compressor Vapor Compression System	6-3
Figure 6-2	Variable Speed Vapor Cycle Air Conditioner/Heat Pump Configuration	6-4
Figure 6-3	Variable Speed Compressor System Improvements	6-6
Figure 6-4	Steady State Part Load Cooling COP Comparison of Vapor Cycle Variations at Moderate Ambient	6-6
Figure 6-5	Steady State Cooling Performance of Selected Variable Speed Vapor Cycle Configuration	6-8
Figure 6-6	Comparison Transient Cooling Capacity with Transient Cooling Load	6-9
Figure 6-6	Transient Cooling Performance - Mid-Cooldown fro	6-9
Figure 6-7	Steady State Heating Performance of Selected Variable Speed Vapor Cycle Configuration - Mid-Cooldown from Hot Soak, at 90°F Vehicle Interior Temperature	6-9
Figure 6-8	Steady State Heating Performance of Selected Variable Speed Vapor Cycle Configuration	6-11

Table of Figures (Continued)

Figure 6-9	Comparison of Transient Heating Capacity with Transient Heating Load	6-11
Figure 6-10	Transient Heating COP of Selected Variable Speed Vapor Cycle Configuration	6-12
Figure 6-11	Comparison of Vapor Pressure-Temperature Curves of R12 and R134a	6-14
Figure 7-1	Basic Open Reverse Brayton Cycle	7-2
Figure 7-2	Reverse Brayton Cycle with Recuperator	7-3
Figure 7-3	Closed Gas Reverse Brayton Cycle with Recuperator	7-4
Figure 7-4	Open Reverse Brayton Cooling Cycle Performance	7-7
Figure 7-5	PV Diagram for Expansion Process with Moisture Condensation	7-8
Figure 7-6	Reverse Brayton Cycle with Moisture Removal Heat Exchanger	7-10
Figure 7-7	Reverse Brayton Cycle with Membrane Moisture Exchanger	7-10
Figure 7-8	Heating/cooling Mode Reversing for Reverse Brayton Cycle Heat Pump (Mode Dampers in Heating Mode)	7-11
Figure 7-9	Reverse Brayton Heating Cycle Performance Ambient Temperature versus Electric Motor Input COP Ambient Temperature versus Heating Capacity	7-12
Figure 7-10	Ideal Stirling Heat Pump Cycle	7-13
Figure 7-11	Kinematic Stirling Cycle Cooling Module Design Concept	7-16
Figure 7-12	Impact of Temperature Lift on Stirling Heat Pump COP	7-17
Figure 7-13	Stirling Cycle Heat Pump Heating Capacity versus Ambient Temperature	7-18
Figure 7-14	Heating/cooling Mode Reversing for Liquid Loop Coupled Reverse Stirling Cycle Heat Pump (mode valves in cooling mode)	7-20
Figure 7-15	Adiabatic Temperature Change versus Temperature for Various Applied Fields in Polycrystalline Gadolinium	7-21
Figure 7-16	Basic Non-Regenerative Magnetic Heat Pumping Cycle	7-22
Figure 7-17	Basic Regenerative Magnetic Heat Pumping Cycle	7-23
Figure 7-18	Magnetic Heat Pumping Operating on an Ericsson Cycle	7-23

Table of Tables

Table 2-1	Design Ambient Conditions for Six Climatic Regions in the United States	2-3
Table 2-2	Thermal Loads for Baseline Thermal Design Options for a Mini-van (Chrysler TE Van) at Several Climatic Conditions	2-4
Table 2-3	Thermal Loads for Baseline Thermal Design Options for a 4 Door Compact Sedan (Nissan Stanza) at Several Climatic Conditions	2-4
Table 2-4	Cooling/Heat Pump Cycle Comparison	2-9
Table 2-5	Cooling/Heat Pump Cycle:Cooling Performance Comparison	2-9
Table 2-6	Cooling/Heat Pump Cycle:Heating Performance Comparison	2-10
Table 2-7	Cooling/Heat Pump Cycle - Weight Breakdown	2-10
Table 2-8	Cooling Performance Comparison of Vapor Cycle Alternatives	2-11
Table 2-9	Heating Performance Comparison of Vapor Cycle Alternatives	2-12
Table 2-10	Estimated Range Penalties for Vehicle Heat Using Vehicle Waste Heat and Heat Pump	2-14
Table 3-1	Typical Automotive Glass Characteristics	3-5
Table 3-2	Comparison of the Thermal Load Model Calculate Steady State Cooling Loads with Wind Tunnel Test Data on PG&E's Electric G-Van	3-13
Table 3-3	Comparison of the Thermal Load Model Calculated Cooling Loads with Wind Tunnel test Data on EPRI's Electric TE Van	3-13
Table 4-1	Glazing Characteristics Used in the Analysis of Thermal Design Options	4-2
Table 4-2	Mini-van and Four Door Compact Sedan Body Style Characteristics	4-4
Table 4-3	Vehicle Thermal Load Operating Conditions	4-5
Table 4-4	Cooling Loads for Different Thermal Design Options for a Mini-van (Chrysler TE Van)	4-5
Table 4-5	Cooling Loads for Different Thermal Design Options for a Compact Sedan (Nissan Stanza)	4-6
Table 4-6	Heating Loads for Different Thermal Design Options	4-6
Table 5-1	Examples of Direct Fuel Fired Vehicle Heating Systems Used in Electric Vehicles	5-3
Table 5-2	Summary of Back-up Heat Sources	5-4
Table 5-3	Estimated Rate of Power Dissipation in the Main Controller and Traction Motor/Transmission for Selected Electric Vehicles	5-6
Table 6-1	Major Design Parameters of Selected Configuration of Vapor Cycle	6-7
Table 6-2	Refrigerant Alternatives for Automobile Air Conditioning	6-13

Table of Tables (Continued)

Table 7-1	Estimated COP and Capacities of Stirling Cycle Heat Pump for EV Space Conditioning	7-17
-----------	---	------

1.0 Introduction

There are strong incentives in terms of national energy and environmental policy to encourage the commercialization of electrically powered vehicles in the U.S. Among these incentives are reduced petroleum consumption, improved electric generation capacity utilization, reduced IC engine emissions, and, depending on the primary fuel used for electric power generation, reduced emissions of carbon dioxide. A basic requirement for successfully commercializing any motor vehicle in the U.S. is provision of adequate passenger comfort heating and air conditioning (cooling). Although air conditioning is generally sold as optional equipment, in excess of 80% of the automobiles and small trucks sold in the U.S. have air conditioning systems.

In current, pre-commercial electric vehicles, comfort heating is provided by a liquid fuel fired heater that heats water which is circulated through the standard heater core in the conventional interior air handling unit. Air conditioning is provided by electric motor driven compressors, installed in a system having, perhaps, an "upsized" condenser and a standard evaporator (front and rear evaporators in some instances) installed in the conventional interior air handler.

Although this approach is adequate in the near term for initial commercialization efforts, a number of short comings of this arrangement, as well as longer range concerns need to be addressed:

- Range penalties associated with the energy consumption of the air conditioning system need to be reduced.
- The size and weight penalties associated with the fuel fired heating system are significant.
- The cost of the fuel fired heating system is significant.
- The need to service two energy sources on the vehicle will reduce the acceptability of electric vehicles to consumers.
- In the long term, CFC-12 based automobile air conditioning systems will be phased out due to the CFC issue. The use of the alternative fluids and alternative cycles, in the unique context of electric vehicles should be considered.

In this project, the long term alternatives for cooling and heating electric vehicles cost effectively, efficiently (with minimum range penalties), and without adverse environmental impacts have been examined. Identification of options that can provide both heating and cooling is important, in view of the aforementioned disadvantages of carrying separate heating and cooling systems in the vehicle.

1.1 Project Approach

The overall objective of the project is to develop an accurate assessment of the alternative means of maintaining passenger comfort conditions in electric vehicles,

when either heating or cooling is required to meet these conditions. This assessment is being carried out in two major areas - determination of heating and cooling loads and identification of options for reducing these loads; and identification and evaluation of candidate cooling and cooling/heating cycles to meet these loads.

Task 1. Determine Cooling and Heating Loads.

Reduction of cooling and heating loads is particularly important in the context of electric vehicle climate control, because the penalties for excessive cooling or heating loads are much more severe in electric vehicles than in conventional IC engine powered vehicles. Larger thermal loads increase power consumption of both the heating and cooling equipment which increases the electric vehicle range penalty by consuming more power from the traction battery. Reductions in the thermal loads by applying thermal design changes to the vehicle can decrease heating and cooling requirements, directly reducing electric energy or fuel consumption for space conditioning and allowing for smaller, lighter equipment.

Task 2. Identify, Characterize, and Evaluate Cooling Cycles.

Cooling and cooling/heating cycles have been evaluated on the basis of their potential for providing significant improvements to the shortcomings noted above. In addition to an examination of vapor compression cycle based options, new or novel cycles having the potential to provide, with adequate development significant improvements in these areas have been identified and evaluated. Feasibility of reverse cycle operation and potential for meeting low ambient temperature heating loads have been evaluated, given the cost, weight, packaging, and operator convenience advantages of eliminating separate cooling and heating systems.

1.2 Scope of Work Summary

Task 1. Determine Cooling and Heating Loads.

The major elements of this task included:

- Developing a simple methodology for estimating steady state and transient cooling and heating loads, based on a reasonably detailed description of the vehicle configuration, the interior comfort condition, and the exterior ambient conditions. The mathematical model that was developed for this purpose was implemented in a Fortran computer program, HCLOADS.
- Assessing vehicle thermal design options for minimizing both transient and steady state loads. The vehicle thermal model was used as a tool for evaluating these design options.
- Developing a baseline set of design cooling and heating loads over a range of U.S. climates, for use in evaluating cooling and cooling/heating cycles. The baseline vehicle thermal design was selected from those options that were both effective in reducing loads and implementable in an intermediate time frame. Climatic extremes

were based on design ambient temperature data taken from the ASHRAE Fundamentals Handbook for several cities representing the range of climatic extremes in the Continental U.S.

Task 2 - Identify, Characterize and Evaluate Cooling and Heating Cycles.

The major elements of this task included:

- Evaluation of cooling cycle alternatives with respect to power consumption, weight, and cost. The major thrust of the task was the estimation of comparative heating and cooling efficiencies for cycle alternatives and variations, over a range of ambient conditions, for a vehicle having the baseline loads referred to above.
- Assessing the feasibility of heat pump cycle operation for heating, for each cooling cycle alternative. The key considerations are performance-capacity and COP versus ambient temperature, referenced to Continental U.S. regional climatic variations; back-up heat requirement and source; the level of hardware complexity required to implement the reverse cycle; defrosting of the ambient air heat exchanger; and windshield defrosting/deicing.

2.0 Summary

2.1 Vehicle Heating and Cooling Loads

2.1.1 Vehicle Thermal Load Model

Development of a thermal load model that could be used to predict electric vehicle cooling and heating loads was a key element of Task 1. The model is a useful design tool for electric vehicle space conditioning systems as well as being the basic tool used to evaluate vehicle thermal design options and to calculate the set of baseline thermal loads that were used in the Task 2 evaluation of cooling and heating cycle alternatives.

As described below, the model was developed by subdividing the thermal loads on the vehicle in sufficient detail to reflect the variables in vehicle construction and in ambient and operating conditions. Each component of the thermal load was then modeled by relatively simple radiant, conductive and convective heat transfer relationships. The components of the load are summed to obtain the total.

For computational efficiency, the model was developed into a Fortran computer program. The model has not been formally and extensively validated, an undertaking which would have been well beyond the scope of our current task. In Section 3.4, model results are compared with electric vehicle cooling loads measured in wind tunnel tests and generally are in agreement within about 15%.

The total thermal (cooling or heating) load on a vehicle can be divided into 5 major components:

- **Ventilation load**, the heat removed from, or added to fresh air to change the temperature from ambient to that of the interior air.
- **Metabolic**, body heat generated by the occupants.
- **Solar**, heat gained from transmission of solar radiation through windows.
- **Conduction**, heat conducted through the vehicle walls and windows, from the exterior surfaces of the vehicle to the interior.
- **Transient**, heat removed from, or added to interior surfaces when starting from a hot or cold soak condition.

Space cooling is needed when the ambient temperature is greater than the interior set point or when the interior set point temperature is greater than the ambient and incident solar radiation on the vehicle is sufficient to heat the vehicle interior. Space heating is needed when the ambient temperature is below the interior set point. The model does not distinguish between heating and cooling modes. The model simply calculates the heat transfer between the interior and exterior of a vehicle. The sign convention adopted in the model is heat gain to the vehicle is positive, and heat loss from the vehicle is negative. As a result, cooling loads are positive and heating loads are negative. The assumptions and equations used to calculate each major component of the thermal load are described in Section 3.1.

The model provides for inputs that describe the vehicle characteristics for the roof, body panels, glass, paint color, vehicle interior, vehicle speed, ventilation air flow rate, interior temperature/humidity set point, number of passengers and interior cool down rate, as well as the ambient conditions, including temperature, humidity, and insolation intensity/angle. The characterization of the vehicle includes description of the front, sides, roof and rear portions of the body. The two sides of the vehicle are assumed to be identical, which is true for most of the vehicles produced today, and therefore, the side characteristics are only input once. Only the portion of the body that provides a direct path to the interior is included in the inputs. Heat transfer through the trunk and engine compartment are considered negligible (for electric vehicles).

Window glass is characterized by area, transmissivity, absorptivity, and glass angle. The body panel thermal conduction characteristics are described in terms of surface area, absorptivity (a function of the paint color), interior finish, and insulation thickness and thermal conductivity, if present. To accurately describe the effect of solar radiation on the vehicle cooling or heating loads, the angle of the sun relative to the horizontal and the front of the vehicle are input into the model. The model accounts for vehicle operating conditions (the ambient and interior environments) in terms of: interior temperature set point, interior humidity set point, ventilation air flow rate, number of vehicle occupants, vehicle speed, ambient air temperature, ambient air humidity, solar radiation intensity.

Transient loads are determined on the basis of an assumed time constant for the exponential decay of the interior temperature, while accounting for interior volume, interior mass, interior surface area, and interior hot or cold soak temperature.

The electric vehicle space conditioning computer program, HCLOADS, is a Fortran program designed to estimate vehicle heating and cooling loads, based on the relationships developed in the thermal load model. Several other alternatives for implementing the thermal load model were considered, including a spreadsheet analysis. However, a Fortran program seemed to be the most efficient analysis method. The inputs are read into the program by means of an input data file, LOADDATA.DAT, and the output is printed into a file called HCLOADS.OUT.

2.1.2 Seasonal Range Of Heating And Cooling Loads

To provide a baseline for evaluating cooling and heating cycles, a set of baseline cooling and heating loads have been calculated for a set of cities representing the range of climatic extremes in the continental United States (lower 48 States). These cities are:

- Phoenix (hot, dry climate, representative of the southwest)
- Los Angeles (warm, dry climate, less severe than Phoenix extremes)
- Houston (hot, humid climate, representative of the Gulf Coast)
- Washington, D.C.
- Detroit, Michigan
- Minneapolis, Minnesota (the last three being progressively colder climates, to explore the limits of applicability of heat pump cycles)

Table 2-1 lists the design ambient temperature extremes for the heating and cooling season for those areas, based on the ASHRAE Fundamentals Handbook. Two sets of values are provided: the temperatures that are exceeded less than 1% and 5% of the cooling season, and the temperatures which are equal to or exceeded 99% and 97.5% of the heating season.

We selected a baseline vehicle thermal configuration and used the thermal load model to compute the heating and cooling loads at the 1% design cooling temperatures and the 99% design heating temperatures. The basic thermal design configuration selected is:

- Insulated roof
- All glazings are wavelength selective, e.g. PPG Sungate
- Recirculation mode only (45 CFM of ventilation make up air)
- 100 CFM of ventilation air, provided by operating the HVAC blower at approximately 5 volts and 20 watts (a reasonably efficient 20 watt DC/DC converter is required), is used to limit hot soak temperatures.
- Transient loads were calculated on the basis of an interior air temperature time constant of 6 minutes (see discussion in Sections 3.0, 3.1.5, and 3.4).

Tables 2-2 and 2-3 summarize the resulting design steady state loads, peak transient loads, and hot soak temperatures.

Table 2-1: Design Ambient Conditions For Six Climatic Regions In The United States

City	Design Heating Dry Bulb, °F		1% Design Cooling Temperatures, °F		5% Design Cooling Temperatures, °F	
	99%	97.5%	Dry Bulb	Wet Bulb	Dry Bulb	Wet Bulb
Phoenix	31	34	109	76	105	75
Los Angeles	37	40	93	72	86	70
Detroit	3	6	91	76	86	73
Minneapolis	-16	-12	92	77	86	73
Houston	28	33	97	80	93	79
Washington, D.C.	14	17	93	78	89	76

Table 2-2: Thermal Loads For Baseline Thermal Design Options For A Mini-van (Chrysler TE Van) At Several Climatic Conditions

City	Heating Load Btu/hr	Cooling Load Btu/hr	Peak Transient Load, Btu/hr		Hot Soak Temperature, °F
			Heating	Cooling	
Phoenix	3,420	8,721	11,300	16,800	127
Los Angeles	2,751	6,799	9,600	12,500	110
Detroit	6,546	7,321	19,200	12,300	107
Minneapolis	8,667	7,550	24,600	12,700	108
Houston	3,755	8,486	12,100	14,400	113
Washington, D.C.	5,318	7,858	16,100	13,300	109

Table 2-3: Thermal Loads For Baseline Thermal Design Options For A 4 Door Compact Sedan (Nissan Stanza) At Several Climatic Conditions

City	Heating Load Btu/hr	Cooling Load Btu/hr	Peak Transient Load, Btu/hr		Hot Soak Temperature, °F
			Heating	Cooling	
Phoenix	2,217	7,325	7,700	12,600	123
Los Angeles	1,711	5,869	6,500	9,400	108
Detroit	4,576	6,477	13,400	9,500	105
Minneapolis	6,177	6,679	17,300	9,800	106
Houston	2,470	7,478	8,300	11,100	111
Washington, D.C.	3,649	6,961	11,200	10,200	107

2.2 Evaluation of Cooling and Heating Cycles

2.2.1 Objective

The objective of Task 2 was to evaluate and compare the long term potential of vapor cycle and alternative cycle equipment for both cooling and heating electric vehicles. In view of the goal of developing zero emissions vehicles, the ability of heat pump cycles to adequately heat the vehicle interior at an acceptable level of energy consumption is of particular interest. The key points of comparison between alternative cycles are:

- **Efficiency:** a major objective of electric vehicle and electric vehicle component developers has been to increase the vehicle range on one battery charge to the levels needed to satisfy the requirements of a significant portion of the market for motor vehicles. Efficient accessories, especially the space conditioning equipment, are very important so that accessory operation does not significantly compromise the vehicle range.

- Feasibility of reversed, or heat pump cycle operation to provide heating. The key issues are the extent to which heating capacity falls with falling ambient temperature; design measures, such as variable speed operation, to provide additional heating capacity without significantly impacting cooling efficiency; back-up heating requirements; the extent to which vehicle waste heat can be recovered and used for space heating; and, based on this, identification of climatic regions where heat pump heating cycles are feasible and advantageous.
- For vapor cycle, the impact of the ongoing phase out of CFCs on long term vapor cycle alternatives; the feasibility and status of non-CFC alternatives to CFC-12.
- Cooling/heating system weight: added system weight results in increased energy consumption almost in proportion to the added weight, penalizing vehicle range, or requiring the addition of more battery capacity.

2.2.2 Approach

For each cooling/heating cycle that was evaluated, cooling and heating performance (capacity, COP, and electric power consumption, vs. ambient temperature) were evaluated for a set of baseline cooling and heating loads for an electric mini-van, under a consistent set of assumptions of air flow rates, motor efficiencies, etc. The baseline loads were calculated by using the electric vehicle thermal load model developed in Task 1, assuming that a combination of rather modest thermal design measures, as described in Section 2.1.2, were employed to reduce the vehicle steady state and hot soak cool down thermal loads, relative to conventional practice. These design measures include wavelength selective glass (e.g. PPG Sungate) used for all windows, roof top insulation, limitations on the ventilation make up air flow rate, and provision of an efficient low voltage mode of interior blower operation to limit hot soak temperatures when the vehicle is parked. The cooling and heating loads were calculated for a range of ambient conditions, assuming maximum solar load for cooling load calculations, and no solar heat gain for heating load calculations. Figure 2-1 is plot a of the steady state and transient cooling loads. Figure 2-2 is plot of the steady state and transient heating loads, vs. ambient temperature for a typical minivan with the thermal design improvements described above. The design ambient temperatures are indicated for a set of cities that are representative of the range of climatic conditions found in the continental U.S. (lower 48 states). Transient loads are shown in Figures 2-1 and 2-2 for several interior air time constants, averaged over the time period required for the transient load to fall to within 20 percent of the steady state load. As discussed in Section 3.4, the interior air cool down rate corresponding to a 6 minute interior air time constant approximates wind tunnel test data reasonably well. The transient loads for a 6 minute time constant, averaged over 20 minutes were used in this study as the basis for transient capacity requirements. The *peak* transient loads, for a 6 minute time constant are tabulated in Table 2-2; the peak loads are generally 20 percent greater than the 6 minute time constant/20 minute average transient loads shown in Figures 2-1 and 2-2.

In general, air conditioning system design capacities were established by the worst case (i.e. Phoenix) cooling load. The resulting heating capacities versus ambient temperature were then estimated, based on the design capacity, and the characteristics of the particular cycle and cycle variation, for comparison with the heating load vs. ambient temperature characteristic.

The preceding set of assumptions was chosen for two basic reasons:

- The assumptions selected represent a moderately aggressive approach to decreasing the energy consumption required to cool and heat electric vehicles, which is important to the long term success of electric vehicles.
- There are a large number of design parameters that can be varied for either a conventional or an electric vehicle air conditioning system. To keep numerical analyses tractable, and within the scope and budget of the study, it was necessary to select a reasonable set of assumptions and apply them consistently to different cycle alternatives that were evaluated.

Figure 2-1: Mini-van Cooling Loads (with Thermal Design Improvements described in Section 2.1.2)

Figure 2-2: Mini-van Heating Loads (with Thermal Design Improvements described in the text)

In general, the results of these analyses provide a reasonable basis for the comparison of these cycle alternatives. If the assumptions were modified -- e.g. higher motor efficiencies, more cooling air flow -- and applied to all cycle alternatives, the results for all of the cycle alternatives would tend to change in tandem. It should be noted that increased heating and cooling loads will result in a decrease in COP levels (for all cycles), given the increased temperature differentials that will occur as a result of increased heat transfer rates through the condenser and evaporator.

The emphasis in this study has been on developing estimates of performance for cycle alternatives and variants. Weight and cost estimates are approximate and have been developed with conventional automobile A/C component weights and cost taken as a point of departure.

The alternatives that were examined in this study were:

- Vapor cycle, with different design variations;
- Reverse Brayton cycle, with different design variations;
- Reverse Stirling cycle; and
- Magnetic refrigeration.

Thermoelectric heat pumps and thermally activated cycles (e.g. absorption) were not considered. Thermoelectrics are a poor alternative to vapor cycle for EV air conditioning. They are extremely costly in comparison with vapor cycle; at the temperature lifts typical of vehicle air conditioning, thermoelectric COP's are typically very poor, on the order of 0.3, before accounting for parasitics. Thermally activated cycles have much larger heat rejection requirements, and much greater performance sensitivity to the heat rejection temperature, than vapor cycle in particular and shaft power driven cycles in general. Given the limited frontal area available for the heat rejection heat exchanger, and the drag penalties associated with high cooling air flow rates, shaft power driven cycles are a better option. In addition, a fuel fired heat source is inconsistent with the goals of eliminating the fuel fired heater and reducing vehicle pollution levels to zero.

2.2.3 Results

2.2.3.1 Comparison of Alternative Cycles Tables 2-4 through 2-7 summarize the cooling performance, heating performance, and basic features of each cycle alternative that was evaluated in this study. In general, the results show vapor cycle equipment to be the highest in efficiency and lowest in weight and cost. The results in Tables 2-4 through 2-7 are based on a longer range view of these alternatives, i.e. it is assumed that each technology alternative has been fully developed for EV space conditioning. There is no reasonable prospect that reverse Brayton cycle COP levels can be improved significantly beyond the very low levels indicated in these tables. High component efficiency levels were assumed in the reverse Brayton cycle analyses, corresponding to the highest levels that have been achieved after decades of intensive development work for engine supercharging and aircraft applications. Variations to the basic simple open cycle, such as recuperators, would increase the COP by a modest amount, but the COP levels are still far below vapor cycle COP levels. As discussed in Section 7.3, the prospective efficiency levels of magnetic refrigeration cycles is low, while at the same time very high magnetic field strengths, normally associated with large, heavy, and expensive superconducting magnets, are required to produce a measurable cooling effect.

Table 2-4: Cooling/Heat Pump Cycle Comparison

Cycle Alternative	Phoenix* Cooling COP	Wash, D.C. Heating COP**	System Weight	Technical Maturity
Vapor Cycle - variable speed compressor	2.2	2.3	55	Standard technology for conventional auto A/C. Prototype EV A/C systems. No heat pumps to date.
Reverse Brayton cycle - simple open cycle	.55	1.0	55	Commercially produced for aircraft cooling. Auto A/C prototypes have been tested.
Reverse Stirling cycle - liquid loop coupled to interior air and to ambient air	1.8	2.4	100+	Commercially produced as small cryocoolers. No auto A/C hardware to date.
Magnetic refrigeration	low	low	300+	Laboratory bench top systems

- * At 109°F design ambient temperature, steady state
- ** At 14°F design ambient temperature steady state
- ... Long term viewpoint based on mature technology, mass production quantities, 1990 dollars

Table 2-5: Cooling/Heat Pump Cycle: Cooling Performance Comparison

Cycle Alternative	COP - Steady State*		COP - Cool Down*	
	110°F	90°F	110°F	90°F
Vapor cycle - variable speed compressor	2.2	2.8	2.4	2.9
Reverse Brayton cycle - simple open cycle	.55	.65	.71	.72
Reverse Stirling cycle - liquid loop coupled to interior air and to ambient air	1.8	2.0	1.8	2.0
Magnetic refrigeration	<<.5	<.5	<<.5	<.5

- * Vapor cycle and Stirling Cycle COP's are based on total electric power input to system: compressor motor, fan and pump motors, etc. Reverse Brayton cycle COP's are neglecting parasitics, which are a very small fraction of the input to the compressor/expander motor.

Table 2-6: Cooling/Heat Pump Cycle: Heating Performance Comparison

Cycle Alternative	Heating COP		Maximum Heating Capacity % of Phoenix Design Cooling Capacity	
	47°	14°	47°	14°
Vapor cycle - variable speed compressor, (maximum design capacity Phoenix cooling)	2.8	2.3	120%	75%
Vapor cycle - variable speed compressor, (maximum design capacity Detroit heating)	2.8	2.3	180%	115%
Reverse Brayton cycle - simple open cycle (maximum design capacity Phoenix cooling)	1.25	1.0	230%	160%
Reverse Stirling cycle - liquid loop coupled to interior air and to ambient air	2.5	2.4	125%	115%
Magnetic refrigeration				

2.2.3.2 Vapor Cycle Alternatives The comparison of cycle alternatives in the preceding section indicates that the vapor compression cycle is the most promising near term and longer term alternative for efficient, light weight, cost effective cooling and electrically powered heating of electric vehicles. Within the general context of the vapor compression cycle, a variety of design alternatives can be considered, including coil sizing and configuration, compressor type and capacity, compressor prime mover, and refrigerant selection. To stay within the constraints of the project scope and budget, a set of vapor cycle alternatives were examined that represent in turn the current EV climate control state of the art and successive improvements in efficiency. In each case, vehicle heating, as well as vehicle cooling performance was evaluated. The vapor cycle alternatives considered were:

Table 2-7: Cooling/Heat Pump Cycle - Weight Breakdown (In pounds)

Cycle Alternative	Motor & Compressor	Motor Drive Electrn. Package	Evaporator* and Blower	Condenser* and Fan*	Tubing, Hoses, Misc.	Total
Vapor cycle - variable speed compressor etc.	20	8	10	10	7	55
Reverse Brayton cycle - simple open cycle	20	15	---	10	10	55
Reverse Stirling cycle - liquid loop coupled to interior air and to ambient air	60**	10	10	10	10	100
Magnetic refrigeration	250	---	10	10	10	250 - 300 at least

* Or functional equivalent for alternative cycles

** Includes compressor/expander/regenerator and liquid loop pumps

- A baseline system derived entirely from production automobile air conditioning system components (except for the compressor drive motor). The heating and cooling performance was analyzed based on a design capacity meeting the thermal load characteristics presented in Section 2.1.2. These loads are representative of an electric mini-van or compact car with a relatively modest set of design measures having been implemented to reduce the thermal loads, as described in Section 3. With this performance level as a baseline, the following vapor cycle design measures to improve the efficiency are examined (with the baseline vehicle thermal design retained).
- Variable speed compressor drive -- allows better part load performance through more effective utilization of heat transfer surface and reduced parasitics and cycling losses. Also, increased compressor design capacity can be specified to provide quicker cool down and to meet lower ambient temperature heating loads, without significantly reducing cooling efficiency.
- Increased condenser and evaporator frontal area and/or air flow rate. Raises evaporator, reduces condenser temperatures, reducing compressor input power, but parasitics may be increased.
- An evaporator and interior air blower arrangement aimed at allowing higher air flow rates at lower fan power, increasing efficiency through reduced compressor power and reduced parasitics.
- The performance of the preceding are estimated first based on steady state operation. Performance is also estimated for the initial part of a hot soak pull down or, in heating mode, cold start-up.

Tables 2-8 and 2-9 summarize the heating and cooling performance, respectively.

Table 2-8: Cooling Performance Comparison of Vapor Cycle Alternatives

Alternatives	COP @ Ambient		Improvement vs. Baseline	
	90°F	110°F	90°F	110°F
Baseline - constant speed belt driven Scroll compressor	2.1*	2.0	---	---
Variable speed compressor (Maximum capacity: Phoenix cooling)	2.8	2.2	33%	10%
Variable speed compressor (Maximum capacity: 5°F heating)	2.7	2.2	30%	10%
With Large Face Area Condenser		2.4		20%
With Large Face Area Evaporator		2.5		25%
With High Flow Low Parasitic Evaporator Fan		2.9		45%

- * Clutch cycling losses, heat exchanger overload, and parasitics negate inherently higher COP at lower ambient.

Table 2-9: Heating Performance Comparison of Vapor Cycle Alternatives

Alternatives	COP @ Ambient		Improvement vs. Baseline	
	47°F	14°F	47°F	14°F
Baseline - constant speed belt driven Scroll compressor	1.5*	2.0	---	---
Variable speed compressor (Maximum capacity Phoenix cooling)	2.8	2.3	40%	15%
Variable speed compressor (Maximum capacity - 5°F heating)	2.8	2.3	40%	15%

* Includes effect of cycling losses.

2.2.3.3 Electric Vehicle Heating Most electric vehicles now use liquid fuel fired heaters to perform space heating and defrost functions. An alternative to the fuel fired heater is to use the air conditioning system as an electrically driven heat pump system. Heating would be provided by a combination of vehicle waste heat, the heat pump, and, when necessary, back up electric resistance heat. Such a system would simplify the space conditioning system design and reduce the overall size and weight of the space conditioning system by eliminating the need for a separate liquid fuel fired heater. It would also eliminate the need to service two energy sources on the vehicle thereby increasing consumer acceptance.

To illustrate the feasibility of this approach to vehicle heating, the minivan with improved thermal design example, above, was considered. This vehicle was assumed to have a heat pump whose maximum capacity is set to meet 150% of the steady state cooling load at the Phoenix design ambient. Recovery of heat dissipated in the traction motor inverter and the traction motor/transmission is assumed (Table 5-3 is a summary of the heat dissipation levels in these components for various electric vehicles). Figures 2-3 and 2-4 plot, versus ambient temperature, the sources of vehicle heat at steady state and during a warm up from hot soak (20 minute average). In general, recovered drive line waste heat and the heat pumps have sufficient capacity to meet the steady state heating load at design ambients throughout the Continental U.S. Large amounts of back up electric resistance heat would be needed to warm the vehicle in a reasonable period of time in colder climates, but in areas having mild winters, the heat pump provides sufficient capacity for warmup, as well as steady state operation. Figure 2-5 plots the energy consumption for the 20 minute average transient warm up in Figure 2-4. Table 2-10 summarizes the estimated range penalties, for this heating technique, for three driving cycles. They are quite modest, except for a series of short trips in a colder climate.

Figure 2-3: Steady State Heating of Baseline Mini-van, Using Vehicle Waste Heat, Vapor Cycle Heat Pump and Backup Electric Resistance Heat to the Extent Necessary

Figure 2-4: Transient Heating (20 Minute Average Load) of Baseline Mini-van, Using Vapor Cycle Heat Pump and Backup Electric Resistance Heat to the Extent Necessary

Figure 2-5: Transient Heating Energy Consumption (20 Minute Average Load)

Table 2-10: Estimated Range Penalties For Vehicle Heating (Minivan Example) Using Vehicle Waste Heat And Heat Pump (Including Parasitics)

	55 mi/hr*	FUDS*	FUDS/ Soaks**
Los Angeles Design Ambient (37°F)	1/2%	1%	5%
Los Angeles Heating Season Average Ambient (50°F)	1/4%	1/2%	3%
Washington, DC Design Ambient (14°F)	1%	4%	17%
Detroit Design Ambient (3°F)	2%	5%	22%
Minneapolis Design Ambient (-16°F)	4%	10%	36%

* Steady state, single trip, no initial cold soak, warmup time for inverter heat sink and motor/transmission neglected.

** Continuous series of 25 mile FUDS trips with full cold soak in between, no waste heat available from inverter or motor/transmission during first 20 minutes of each trip.

*** Vehicle energy consumption at FUDS and 55 mi/hr per ETX-II, Table 5-3

Beyond capacity and power consumption, two other practical issues must be considered relative to application of a heat pump to vehicle heating:

- Defrosting the ambient air heat exchanger: in the heating mode, when the ambient air coil fin surface, gradually building up and blocking airflow through the coil. In stationary heat pumps, the coil is defrosted by periodically reversing to cooling mode, but with back up supplied to the interior and the outdoor fan off. The outdoor coil is heated, melting the frost, then normal heat pump operation is resumed. In a moving vehicle, in cold weather, a means of blocking the air flow (e.g. louvers) during the defrost cycle may be needed to allow the coil to warm up quickly and melt the frost.
- Windshield defrosting: FMVSS 103 specifies minimum deicing performance, as measured by a specific test procedure. This requirement actually tends to drive the heating capacity requirement in some EV's. An electrically heated windshield (e.g. the Ford "Instaclear" option) is preferable.

2.2.3.4 Alternatives to CFC Working Fluids for Vapor Cycle Systems. CFC-12 has been used almost exclusively as the working fluid in automobile air conditioning, beginning with the introduction of automobile air conditioning in the 1930's. It has a very favorable set of properties for this application, including chemical stability, compatibility/solubility with air conditioning system materials of construction and low cost, effective lubricants, low toxicity, and nonflammability; and at the extreme temperatures that occur in automobile air conditioner condensers, pressure levels and compressor discharge temperature are moderate. Due to the role of CFCs in stratospheric ozone depletion and global warming, the production and consumption of CFC-12 and several other CFCs and halons will be phased out by the year 2000.

While the automobile industry, both in North America and worldwide, is in the product engineering stage of the process of phasing out CFC-12, probably to be replaced by non-ozone depleting HFC-134a, all current automobile air conditioning equipment still uses CFC-12. The vapor cycle efficiency estimates prepared in this report are ultimately derived from the performance of systems and components operating on CFC-12. As discussed below, the refrigerant alternatives to CFC-12 can be expected, when new system designs and lubricants have been fully developed, to result in small efficiency increases or decreases (less than 5%) relative to CFC-12. These small differences in efficiency will not alter the basic conclusions relative to cooling/heating cycle alternatives.

The major alternatives to CFC-12 that are being considered are discussed in Section 6.2. Two alternatives are HFC-134a and HCFC-22:

- HFC-134a is in the process of being adopted as the new refrigerant for automobile air conditioning by much of the automobile industry. Experience to date indicates that the efficiency is degraded by about 5% when used in a system whose components are sized as they would be for CFC-12. A combination of factors, including thermodynamic properties, transport properties, and solubility and lubricating performance of available lubricants seems to account for this difference. However, the auto industry is compensating for the efficiency difference by

upgrading heat exchangers, and lubricant development is ongoing, so much of the current efficiency deficit will probably be made up in the medium to long term. To the extent that EV air conditioning systems will utilize the automobile mass production base, EV systems are likely to be using HFC-134a as the working fluid.

- HCFC-22 has been considered as an automobile air conditioner working fluid, but a combination of high pressure, high discharge temperature, and high permeability through hose materials has prevented its use. All of these factors apply much less rigidly to EV's. With an electric drive, hoses are not necessary in the system (because the compressor is not engine mounted, eliminating the need to accommodate engine rocking), and temperature extremes associated with the recirculation of exhaust cooling air (when the vehicle is stationary) from the radiator back to the condenser do not apply to EV's. While HCFC-22 might be applied more readily to EV's than IC engine vehicles, HCFC-22 itself is currently scheduled for phase out in 2020, a timetable that may well be accelerated. In addition, currently available R-22 compressors are intended for stationary air conditioning applications, and are considerably heavier than automobile air conditioning compressors.

3.0 Vehicle Thermal Load Model

As outlined in the preceding section, development of a thermal load model that could be used to predict electric vehicle cooling and heating loads is a key element of Task 1. The model is a useful design tool for electric vehicle space conditioning systems as well as being the basic tool used to evaluate vehicle thermal design options and to calculate a set of baseline thermal loads to be used in the Task 2 evaluation of cooling and heating cycle alternatives.

As described below, the model was developed by subdividing the thermal loads on the vehicle in sufficient detail to reflect the variables in vehicle construction and in ambient and operating conditions. Each component of the thermal load was then modeled by relatively simple radiant, conductive and convective heat transfer relationships. The components of the load are summed to obtain the total.

For computational efficiency, the model was developed into a Fortran computer program. The model has not been formally and extensively validated, an undertaking which would have been well beyond the scope of our current task. In Section 3.4, model results are compared with electric vehicle cooling loads measured in wind tunnel tests and generally are in agreement within about 15%.

The total thermal (cooling or heating) load on a vehicle can be divided into 5 major components.

- **Ventilation load**, the heat removed from, or added to fresh air to change the temperature from ambient to that of the interior air.
- **Metabolic**, body heat generated by the occupants.
- **Solar**, heat gained from transmission of solar radiation through windows.
- **Conduction**, heat conducted through the vehicle walls and windows, from the exterior surfaces of the vehicle to the interior.
- **Transient**, heat removed from, or added to interior surfaces when starting from a hot or cold soak condition.

Space cooling is needed when the ambient temperature is greater than the interior set point or when the interior set point temperature is greater than the ambient and incident solar radiation on the vehicle is sufficient to heat the vehicle interior. Space heating is needed when the ambient temperature is below the interior set point. The model does not distinguish between heating and cooling modes. The model simply calculates the heat transfer between the interior and exterior of a vehicle. The sign convention adopted in the model is heat gain to the vehicle is positive, and heat loss from the vehicle is negative. As a result, cooling loads are positive and heating loads are negative. A description of the assumptions and equations used to calculate each major component follows in the next section.

The model provides for inputs that describe the vehicle characteristics for the roof, body panels, glass, paint color, vehicle interior, vehicle speed, ventilation air flow rate, interior temperature/humidity set point, number of passengers and interior cool down rate, as well as the ambient conditions, including temperature, humidity, and insolation

intensity/angle. The characterization of the vehicle includes description of the front, sides, roof and rear portions of the body. The two sides of the vehicle are assumed to be identical, which is true for most of the vehicles produced today, and therefore, the side characteristics are only input once. Only the portion of the body that provides a direct path to the interior is included in the inputs. Heat transfer through the trunk and engine compartment are considered negligible (for electric vehicles).

A description of the glass characteristics requires the following inputs:

- area, ft^2 .
- transmissivity.
- absorptivity.
- glass angle.

Describing the body panel characteristics requires the following information:

- surface area, ft^2 .
- absorptivity (a function of the paint color).
- interior finish.
- insulation thickness and thermal conductivity, if present.

To accurately describe the affect of solar radiation on the vehicle cooling or heating loads, the angle of the sun relative to the horizontal and the front of the vehicle are input into the model. The vehicle operating conditions characterize the ambient and interior environments. These inputs are listed below:

- interior temperature set point, °F.
- interior humidity set point, RH.
- ventilation air flow rate, CFM.
- number of vehicle occupants.
- vehicle speed, mph.
- ambient air temperature, °F.
- ambient air humidity, RH.
- solar radiation intensity, Btu/hr/ft^2

In order to determine the transient loads, inputs for the following are required:

- a time constant for the exponential decay of the interior temperature
- interior volume
- interior mass
- interior surface area
- interior soak temperature

These inputs do not affect the steady state load calculations. The interior surface mass and area are used to model the heat transfer between the interior surfaces and the interior air during a transient period. When the interior has reached steady state the interior surfaces and air are at the same temperature.

The electric vehicle space conditioning computer program, HCLOADS, is a Fortran program designed to estimate vehicle heating and cooling loads, based on the relationships developed in the thermal load model. Several other alternatives for implementing the thermal load model were considered, including a spreadsheet analysis. However, a Fortran program seemed to be the most efficient analysis method. The inputs are read into the program by means of an input data file, LOADDATA.DAT, and the output is printed into a file called HCLOADS.OUT.

3.1 Detailed Model Description

The following sections summarize the heat transfer relationships used to calculate each of the five components of the vehicle thermal load.

3.1.1 Ventilation Loads

The ventilation load results from cooling or heating the ambient air to the interior temperature. The following equation is used to calculate this load:

$$Q_{vent} = \dot{m}_{vent}(h_{ambient} - h_{interior})$$

Perfect gas relationships for dry and moist air, taken from the ASHRAE Handbook of Fundamentals, are used to calculate the enthalpy of the ambient air and the interior air:

$$h = 0.24T + W(1061 + .444T)$$

$$W = 0.62198 \frac{p_w}{p - p_w}$$

$$p_w = \phi p_{ws}$$

$$\ln(p_{ws}) = C_8/T_R + C_9 + C_{10}T_R + C_{11}T_R^2 + C_{12}T_R^3 + C_{13} \ln(T_R)$$

$$T_R = T + 459.67, \text{ } ^\circ\text{R, Rankine}$$

where

$$C_8 = -1.044039708 \times 10^{-4}$$

$$C_9 = -11.2946490$$

$$C_{10} = -2.7022355 \times 10^{-2}$$

$$C_{11} = 1.289036 \times 10^{-5}$$

$$C_{12} = -2.478068 \times 10^{-9}$$

$$C_{13}=6.5459673$$

h = enthalpy, Btu/lb_{air}

p_{ws} = partial pressure of saturated pure water

p_w = partial pressure of water vapor in ambient or interior air

W = humidity ratio of moist air, lb_{water}/lb_{air}

T = dry temperature of moist air, °F

ϕ = relative humidity

The ventilation air flow rate is an input variable and ranges from full vent mode, which is a function of the manufacturer and vehicle type, down to zero. We recommend the ventilation air be reduced to 15 cfm/person or a maximum of 45 cfm for passenger vehicles. The 15 cfm/person is the ASHRAE recommendation for office buildings.

3.1.2 Metabolic Loads

The metabolic load is assumed to be 500 Btu/hr per passenger. This value includes both latent and sensible components.

3.1.3 Solar Loads

The solar load calculations are a function of the radiant flux of the sun which is an input variable in the model. The equations allow for some variation of the vehicle angle relative to the incident solar radiation and the incident solar radiation angle relative to the horizontal. The model assumes that the solar radiation can only impinge on one side of the vehicle and the temperature of the second side is at the ambient temperature. The transmission of solar radiation through the glass is a function of surface area, incident solar radiation intensity and transmissivity of the glass. The transmissivity of several types of automotive glass are given in Table 3-1.

The following solar load equation and angle relationships have been used to calculate the vehicle solar load (the angles are defined in Figure 3-1):

$$Q_{solar} = Q_{insolation} \tau_{window} A_{window} \cos \theta_{solarincidence}$$

$$\theta_{solarincidence} = \cos^{-1}(1 - a/2)$$

$$a = \{\cos(\beta) - \cos(\theta)\cos(\phi)\}^2 + \{\cos(\theta)\sin(\phi)\}^2 + \{\sin(\beta) - \sin(\theta)\}^2$$

where

A = glass area

τ = transmissivity

θ = angle of sun above the horizon

β = angle of window from vertical plane

ϕ = angle of incidence solar radiation to the perpendicular plane of the window

Table 3-1: Typical Automotive Glass Characteristics

Glass Type	Visible Transmissivity	Entire Wavelength		
		Transmissivity	Absorptivity	Reflectance
Ordinary Glass	.90	.84	.08	.08
Infrared Absorption Glass	.76	.53	.41	.06
Infrared Reflective Glass	.73	.52	.11	.37
Solar Wavelength				
Airco's Solar Control Film	.70	.34	.21?	.45
Adjustable Transparency Glass	.60	.52		
decolored	.05	.06		
colored				
Aircool Tinted windshield	.70	.38	.24	.38
Standard Tinted Windshield	.79	.57	.37	.06
PPG Sungate Glass		.39	.30	.31

used in buildings, has not been examined in practical terms for motor vehicles

The information in Table 3-1 was assembled from the following SAE papers: 880050, 861362, 890311, and 890217.

Figure 3-1: Solar Radiation Angles for Windshield Case

3.1.4 Conduction Loads

The conduction load is a function of the ambient temperature, solar radiation, absorptivity of glass/body panels and the interior finish of the vehicle. The absorptivity of several glass types is shown in Table 3-1. The absorptivity of the body is a function of the paint color. A black surface has an absorptivity of 0.89 and a white finish 0.47. Figure 3-2 illustrates the heat transfer that occurs on a vehicle surface.

Figure 3-2: Motor Vehicle Heat Transfer Characteristics

The conduction heat transfer through the floor is considered negligible for all vehicle types. For cars conduction loads result from the glass, doors, firewall, trunk, and roof. We assume the conduction through the firewall and the trunk is negligible compared to other components of the conduction load.

The following conduction, convection and radiation relationships are used to calculate the vehicle quasi-steady state conduction load:

$$Q_{solar, absorbed} = Q_{convection} + Q_{conduction} + Q_{radiation, surface - air}$$

$$Q_{solar, absorbed} = Q_{solar} A_{surface} \epsilon_{surface} \cos \theta_{solar incidence}$$

$$Q_{convection, surface - ambiens} = h_{surface - ambiens} A_{surface} (T_{surface} - T_{ambiens})$$

$$Q_{conduction} = \frac{A_{surface} (T_{surface} - T_{interior})}{R_{thermal, interior}}$$

$$Q_{radiation, surface - air} = \epsilon_{surface} \sigma A_{surface} (T_{surface}^4 - T_{ambiens}^4)$$

Therefore,

$$Q_{solar} A_{surface} \epsilon \sin \theta_{sun} = h_{metal - ambiens} A_{surface} (T_{surface} - T_{ambiens}) + \frac{A_{surface} (T_{surface} - T_{interior})}{R_{thermal}} + \epsilon_{surface} \sigma A_{surface} (T_{surface}^4 - T_{ambiens}^4)$$

The thermal resistance, $R_{thermal}$, is dependent on the interior finish. A vehicle with a finished interior (this applies to most vehicles) has an outer sheet metal skin and an interior vinyl panel which are separated by an air gap. The thermal resistance, shown below, is a function of three natural (free) convection terms and two conduction terms.

$$R_{thermal, finished interior} = \frac{1}{h_{vinyl - interior}} + \frac{1}{h_{metal - air}} + \frac{1}{h_{air - vinyl}} + \frac{x_{metal}}{k_{metal}} + \frac{x_{vinyl}}{k_{vinyl}} + \frac{x_{gap}}{K_{insulation}}$$

An unfinished interior only applies to a panel van. However, these equations also apply to glass surfaces. The thermal resistance becomes a function of one natural convection term and one conduction term and can be calculated as follows:

$$R_{thermal, unfinished interior or glass} = \frac{1}{h_{free - convection, interior}} + \frac{x_{metal/glass}}{k_{metal/glass}}$$

In each of the thermal resistance equations, at least one conduction term exists. These terms are an order of magnitude smaller than the convection terms and can be considered negligible.

The natural convection heat transfer coefficient equation, stationary applications and interior calculations, for a horizontal surface is as follows:

$$h_{exterior} = .207(T_{surface} - T_{ambiens})^{1/3}, \text{ stationary vehicle}$$

This convective heat transfer coefficient equation results in a convective coefficient of approximately .6 Btu/hr/ft²°F for a 20 degree temperature difference. This value seems low for this type of condition. In order to compensate for this low value, we chose a base value for the exterior natural convection coefficient of 1.0 Btu/hr/ft²°F and 0.5 Btu/hr/ft²°F for the interior convection coefficient. An adjustment to the convective coefficient, which depends on the location, is made to account for the following:

- higher temperature differences
- breezes blowing over the vehicle
- interior air movement due to air conditioning/heating system

The forced convection (moving vehicle) heat transfer coefficient for any exterior surface orientation is calculated as follows:

$$h = 0.0385 \left(\frac{U_{\infty} d}{\nu_f} \right)^{0.782} \frac{k_f}{d}$$

subscript f implies that the value is taken at the film temperature

where

U_{∞} = vehicle speed, ft/s

k = thermal conductivity, Btu/hr-ft-°F

ν = kinematic viscosity, sq. ft/s

d = vehicle height, ft.

$$T_f = \frac{T_{surface} + T_{ambient}}{2}$$

The heat transfer equations are solved iteratively for the surface temperature, for areas that have incident solar radiation, and then the surface temperature is used to calculate the conduction term. Areas that do not have solar radiation impingement are considered to be at the ambient temperature, and the conduction term can be calculated directly.

3.1.5 Transient Calculations

Transient calculations involve all of above equations. In addition, the calculations require two more terms that identify the heat transfer from the hot dashboard (and rear deck for a car) to the interior air and the cool down (or heat up) rate of the interior. Typically, the interior air is 30-50°F cooler than these surfaces, generating a heat gradient from the surface to the interior air. This term can be modeled by a simple convection equation, which is listed below:

$$Q_{interior\ surface - interior\ air} = h A_{surface} (T_{surface} - T_{interior\ air})$$

We chose to model the cool down rate of the interior air as a time dependent interior temperature, decaying exponentially from the initial temperature to the interior comfort temperature set point, rather than formulating an air conditioning system capacity relationship. The following exponential equation expresses the time decay of the interior temperature:

$$T_{interior} = T_{set} + (T_{soak} - T_{set})e^{-ct}$$

where,

t = time, minutes

c = time constant, 1/minutes

T_{soak} = interior temperature after hot soak, °F

T_{interior} = interior temperature after time t, °F

For example, if we assume an interior temperature of 130°F after a hot soak, which is typical for a one hour soak time, an 8.5 minute period to reach 95°F, and an interior comfort temperature of 76°F, then the time constant becomes .123/min. This value was determined from wind tunnel tests (Appendix C) with the PG&E electric G-Van (conducted for EPRI).

3.2 Vehicle Cooling Loads

HCLOADS can be used to calculate steady state cooling loads, transient cooling loads and interior hot soak temperatures. Inputs for HCLOADS are read into the Fortran program using a data file called LOADDATA.DAT. A sample input data file is listed in Appendix A. The data file is thoroughly commented, including variable dimensions, to create an input file that is self explanatory. The output file, HCLOADS.OUT, includes the following information:

- input file data
- total steady state load (a sum of the ventilation, metabolic, solar and conduction loads)
- ventilation load
- metabolic load
- solar load
- conduction load
- roof exterior surface temperature
- transient loads

The input data file information is repeated to provide a means of checking the data at the same time the output is reviewed. The total steady state load, the ventilation load, the metabolic load, the solar load, and the conduction load, as well as their components, are printed below the input data as follows:

- ventilation load, Btu/hr.
 - sensible component.

- latent component.
- metabolic load, Btu/hr.
- solar load, Btu/hr.
 - windshield component.
 - rear window component.
 - side window component.
- conduction load, Btu/hr.
 - roof component.
 - side 1 component (panels with incident solar radiation).
 - side 2 component (panels without incident solar radiation).
 - side 1 window component (windows with incident solar radiation).
 - side 2 window component (windows without incident solar radiation).

The conduction terms for side 1, body panels and windows, are the heat transfer rates for the side of the vehicle with incident solar radiation. This side of the vehicle has surface temperatures above ambient and therefore, higher conduction rates than side 2. The side 2 conduction components are the heat transfer rates for the side of the vehicle which has no incident solar radiation. These surfaces are at the ambient temperature.

The transient load output includes time from the end of the soak/beginning of pull down or heat up, interior air temperature, interior surface temperature, total transient load (the load which must be met by the air conditioning system), ventilation load, metabolic load, solar load, conduction load, transient interior load (the heat transferred between the hot/cold soaked interior surfaces and the interior air). The interior air and surface temperatures begin at the interior soak temperature, which is an input variable. The metabolic and solar loads remain constant during the transient period. The conduction load, transient load, and ventilation load vary with the interior temperature. The total transient load approaches the steady state value as the interior cools. The cool down rate of the interior temperature can be varied to approximate vehicle test data by changing the interior air temperature time constant. The transient load is also affected by the interior soak temperature. This variable is a function of vehicle soak time, solar radiation, and ambient temperature. A sample output file is included in Appendix B.

The hot soak temperature can be estimated by executing HCLOADS with an assumed elevated interior temperature set point. The set point at which the steady state thermal load is zero is the interior hot soak temperature. This method is an over simplification in one major respect. The calculations assume that the incident solar radiation is in the same position until a steady state thermal balance between the interior of the vehicle and the exterior is reached. During a long soak the sun will not stay in the same position. Therefore, HCLOADS will calculate higher interior hot soak temperatures than those experienced in testing if the input angles are such that the vehicle incident solar

radiation is maximized. The error can be 20°F or more. However, the hot soak temperatures estimated by this method can be used to compare vehicle thermal design options.

To establish design loads for air conditioning sizing, the cooling load analysis should be performed for extreme operating conditions which include high ambient temperatures, high insolation and high metabolic loads. Currently, automobile air conditioning system sizing is based on a 110°F ambient temperature and full solar load (333 Btu/hr/ft²). However, the 110°F ambient is an extreme condition that occurs in limited regions of country, particularly the desert Southwest. Most regions, for example the LA Basin, will have less severe extreme conditions, with design ambients of 100°F or less. Therefore, we recommend that the latter be used for cooling load calculations. The two solar angle inputs to HCLOADS, elevation and azimuth of the sun, model the incident solar radiation on the vehicle. These two terms should be adjusted to orient solar radiation to achieve the maximum solar load.

3.3 Heating Loads

HCLOADS, can be used to calculate steady state heating loads. Automobile heaters are sized for extreme conditions for both heating and defrosting functions. Heating load calculations should be performed for ambients down to 0°F with no incident solar radiation, which would result in a lower heating load. Glass thermal design options for heating functions are not considered because extreme conditions with no solar load will be analyzed. Solar radiation, when present, will help to reduce heating loads. Glass options that decrease cooling loads by reducing the transmission of solar radiation will reduce the benefit of solar radiation in heating modes.

The input and output for heating loads, both steady state and transient, are the same as described in previous section.

3.4 Comparison Of Results Of The Model With Wind Tunnel Test Data

The thermal load model has not been formally validated. However, the vehicle space conditioning model output can be compared to wind tunnel test data to determine an estimate of the accuracy. Two electric vehicles, an EPRI TE Van and Pacific Gas and Electric's G-Van, have been tested under an EPRI contract for air conditioning design, installation and testing. Testing of the G-Van was completed in October, 1989 at Sanden's wind tunnel facility in Plymouth, Michigan and testing of the TE Van on April 12, 1990 in Chrysler hot room at the Highland Park facility (Appendices C and D).

The G-Van has white exterior paint and a red interior. Figure 3-3 shows two views of the test set up. Table 3-2 shows the comparison of cooling loads for 3 separate test conditions. The thermal load model output for the G-Van is included in Appendix D.

Figure 3-3: PG&E Electric G-Van Wind Tunnel Tests

Table 3-2: Comparison of The Thermal Load Model Calculated Steady State Cooling Loads With Wind Tunnel Test Data On PG&E'S Electric G-Van

Ambient Conditions	Vehicle Speed mi/hr	Interior Conditions	Cooling Mode	Cooling Load Test Results	Cooling Load HCLOADS Calculation
100°F, 40%RH	50	73°F, 20%RH	Fresh Air	25,600 Btu/hr	31,413 Btu/hr
110°F, 40%RH	35	75°F, 20%RH	Recirc	14,680 Btu/hr	15,965 Btu/hr
90°F, 50%RH	35	68°F, 23%RH	Recirc	12,330 Btu/hr	11,428 Btu/hr

The fresh air cooling mode data indicates that the thermal model over estimates the cooling load by 22.7%. However, this can be misleading because some uncertainties exist. First, the windshield model is slightly in error. The windshield transmissivity was modelled as if the glass was clear glass. Most automobile windshields have a portion near the top which is heavily tinted. This will cause this solar load component, a significant portion of the total solar load, to be over estimated. In addition, the G-Van interior air blower can deliver 263 CFM at max speed and the exact amount of air that is at the ambient condition (fresh air) is unknown. If only 25 cfm, or approximately 10% of the evaporator air is from the interior, the cooling load calculated by the model decreases to 29,051 Btu/hr, reducing the error to less than 14%. Therefore, we would expect the model to be accurate within 15%.

To compare the wind tunnel tests results for the G-Van in recirculation mode (max A/C on the dashboard switch), an estimate for the ventilation air into the vehicle is required. Using 65 CFM as the ventilation rate in the calculations, the thermal load model predicts the cooling loads within 9% for both test conditions.

A comparison of EPRI's TE Van wind tunnel tests to the calculated loads is presented in Table 3-3. An estimate for the ventilation air was assumed to be 25 CFM. The cooling loads estimates for both cases were within 12% of the wind tunnel test data. The thermal load model output for the EPRI electric TE Van is included in Appendix E.

Table 3-3: Comparison of The Thermal Load Model Calculated Cooling Loads With Wind Tunnel Test Data On EPRI'S Electric TE Van

Ambient Conditions	Interior Conditions	Cooling Mode	Cooling Load Test Results	Cooling Load HCLOADS Calculation
110°F, 20%RH	86.5°F, 23%RH	Recirc	5,430 Btu/hr	6,042 Btu/hr
89°F, 55%RH	75°F, 28%RH	Recirc	6,700 Btu/hr	6,602 Btu/hr

The modeling of the interior air cool down can also be checked against wind tunnel test results. Figure 3-4 compares the average PG&E G-Van interior temperature during the standard GM pull-down test to the interior temperature calculated by thermal model. The vehicle was hot soaked before the test began to 130°F. Exponential cool down rates,

with time constants of 3, 6, 8 and 10 minutes are plotted along with van cool down test data. The 6 and 8 minute time constants are reasonable approximations to the actual data.

Figure 3-4: Comparison of the Thermal Load Model Interior Air Temperature Cool Down Characteristic with Wind Tunnel Test Data of PG&Es Electric G-Van during a Standard GM Pulldown Test

4.0 Comparison Of Thermal Design Options

As discussed in the preceding section, vehicle thermal loads can be broken down into five basic components: metabolic, ventilation, solar, conduction, and transient. The metabolic, or vehicle occupant body heat load, depends on the vehicle occupants and will not be affected by vehicle thermal design measures. The remaining loads can be reduced considerably by available design options.

4.1 Description Of Thermal Design Options

4.1.1 Ventilation

Standard automotive practice in automobile air conditioning systems is to allow the vehicle occupants to select between full ventilation mode (often labeled "Normal" on the air conditioning controls) and recirculation (often labeled "Max" or "Max A/C"). In the former case, all of the air passing through the evaporator is ambient make up air which must be cooled and dehumidified to interior comfort conditions. Given the primary importance of accessory efficiency, it is reasonable to restrict make up air intake to levels consistent with indoor air quality requirements, on the order of 10 to 15 CFM per vehicle occupant. For recirculation air only cases, 45 CFM of make up air was assumed.

4.1.2 Solar Load - Glazing Options

Solar radiation has two major direct thermal impacts on a vehicle. A portion of the radiation is transmitted through the windows and is absorbed by interior surfaces. Another portion is absorbed, both by window glass and other exterior surfaces. The reflected portion has no direct thermal effect on the vehicle. In the vehicle thermal load model developed in this study, the effect of absorbed solar radiation is accounted for in the conduction load heat balances for each surface section of the vehicle. In general, absorbed solar radiation has a significant effect on hot soak temperatures, but a small effect on steady state loads when the vehicle is moving, because convection between ambient air and the vehicle exterior surfaces forces the vehicle surface temperature close to ambient, regardless of the absorbed solar load. The portion of the incident solar radiation that is transmitted through the window has a significant effect on both soak temperatures and the steady state load. Several types of reduced transmissivity window glass are either available or under development (listed in Table 4-1) which can reduce the transmitted solar load significantly. They can be grouped into four categories shown in Table 4-1:

- Clear glass, which is still widely used for all automotive windows and transmits a very high fraction of the total solar spectrum.
- "Current glazing" which includes standard tinted windshields, heavily tinted and infrared absorbing or reflecting glasses, which have a lower solar transmissivity, but absorb much of the solar radiation not transmitted. The transmissivity and absorptivity values listed in Table 4-1 are typical of the glazings in this category that have been used in OEM and aftermarket automotive glazings.

Table 4-1: Glazing Characteristics Used in The Analysis Of Thermal Design Options

Glazing Type	Transmissivity	Absorptivity
Clear Glass	0.84	0.08
Current Glazing	0.53	0.41
Wavelength Selective Glazing	0.39	0.30
Switchable Glazing		
Static Soak	0.06	0.47 (estimate)
Driving Mode	0.39	0.30

* Transmissivity assumed equal to wavelength selective glazing

- "Wavelength selective glazings" are glazings with special coatings that cause the transmissivity to vary with wavelength, so that the transmissivity of the visible portion of the solar spectrum is high (>70%, as required by Federal Motor Vehicle Safety Standard 205), with otherwise low transmissivity, so the overall solar transmissivity is low. This category includes PPG Sungate, glazings coated with Airco Solar Control Film, and the Aircool tinted windshield. PPG Sungate is commercially produced (used in the windshield of the Lumina APV) and was used to represent this category in Table 4-1. The others are in the advanced development stage and will be commercially available in the near future. These glazings are delicate and must be laminated in between sheets of glass, so currently, the glass is only used on the windshield which already has laminated layers. PPG Sungate glass is also used on all the windows of the GM Impact electric concept car.
- "Switchable glazings" have two transmissivity states which are altered by either an electrical impulse or an applied voltage. The low transmissivity state is used when the vehicle is parked, to reduce hot soak temperatures, while the high transmissivity state is used when the vehicle is being driven.

4.1.3 Conduction

The conduction load is segmented by roof, body, and window surfaces. In the vehicle thermal model, the heat balance for those surfaces exposed to direct solar radiation includes the absorbed solar radiation. Measures to insulate these surface areas from the vehicle interior reduce the heat transfer from the exterior to the interior. The addition of insulation to the vehicles was evaluated in two steps. First, roof insulation, 1.5 inches thick, was evaluated because the roof area has the hottest surface temperatures and the highest conduction load component, resulting from solar radiation. Next, insulating the roof and all body panels was evaluated. The body panel insulation thickness was assumed to be 2.5 inches. The thermal conductivity used for the insulation was 0.014 Btu/hr/ft²/°F, typical of aged polyurethane foam. Windows could, in principle, use double or triple paned glazing to provide a measure of insulation but this option was not considered because of the expected degree of difficulty and high cost of applying multiple glazings to an automotive application.

4.1.4 Transient

When a vehicle is parked outdoors in strong sunlight during the cooling season, the vehicle interior is heated by a combination of solar radiation transmitted through the windows and heat conducted from the exterior vehicle surfaces that have been heated by absorbed solar radiation. Options that were evaluated for reducing hot soak temperatures were reduced transmissivity glazings, as discussed above, roof top and body panel insulation, and forced ventilation of the vehicle interior, either by a separate ventilation fan or low speed/low wattage operation of the vehicle HVAC blower. For example, a sunroof is produced by PV Electric in West Germany that has photovoltaic glass and a transflow blower built into the interior trim. The blower consumes about 15 Watts which is produced by the photovoltaic coating. The unit is 4% efficient and costs approximately \$500.00 installed. Ventilation air (100 CFM) was used to evaluate this thermal design option for lowering the transient cooling load.

In the worst case cold soak condition, the vehicle interior reaches the ambient temperature or slightly below. This will occur when there is no solar load (at night or with heavy cloud cover).

4.2 Evaluation Of Thermal Design Options

Two vehicle styles, a mini-van (the Chrysler Caravan/Voyager has been used as an example) and a 4-door compact sedan (the Nissan Stanza has been used as an example), were selected to study and evaluate the effect of the thermal design options on heating and cooling loads. The vehicle characteristics for each body style are listed in Table 4-2. Each vehicle is modeled with clear glass and no insulation to generate base values from which all improvements can be judged. All heating and cooling load calculations, including hot soak temperatures, were completed with vehicle operating conditions listed in Table 4-3. During hot soak temperature determinations, the vehicle was assumed to be stationary with no occupants and no ventilation air.

The results for the cooling load analyses for varying degree of load reduction measures (steady state, transient, and hot soak temperatures) are listed in Tables 4-4 and 4-5 for the mini-van and compact sedan Stanza, respectively. The percent reduction in hot soak temperatures and cooling loads from the base case, fresh air mode operation, are listed below the calculated values (in parenthesis) in Tables 4-4 and 4-5. The results for the heating load calculations are listed in Table 4-6.

Table 4-2: Mini-van and Four Door Compact Sedan Body Style Characteristics

Vehicle Characteristic	Body Style	
	Mini-van	Compact Sedan
Windshield Area, ft ²	11.7	9.56
Windshield Angle, deg.	38.0	35.0
Windshield Transmissivity	.84	.84
Windshield Absorptivity	.08	.08
Side Window Area, ft ²	11.7	5.5
Side Window Transmissivity	.84	.84
Side Window Absorptivity	.08	.08
Rear Window Area, ft ²	7.3	6.0
Rear Window Angle, deg.	90.0	43.0
Rear Window Transmissivity	.84	.84
Rear Window Absorptivity	.08	.08
Vehicle Height, ft.	5.4	4.42
Roof Width, ft.	6	3.58
Roof Area, ft ²	60.0	17.0
Roof Insulation Thickness, in.	0.0	0.0
Side Panel Area, ft ²	40.0	12.0
Body Panel Insulation Thickness, in.	0.0	0.0
Body Panel Absorptivity	.9	.9
Interior Surface Area, ft ²	250	150
Interior Surface Mass, lb _m	175	150
Interior Volume, ft ³	300	95
Interior Finish		
Roof	yes	yes
Body Panel	yes	yes

Table 4-3: Vehicle Thermal Load Operating Conditions

Operating Condition	Cooling Mode	Heating Mode
Interior Air Temperature Set Point	75°F	75°F
Interior Air Humidity Set Point	50%RH	---
Ventilation Air, Fresh Air Mode	225 SCFM	225 SCFM
Ventilation Air, Recirc Mode	45 SCFM	45 SCFM
Vehicle Speed	30 MPH	30 MPH
Ambient Air Temperature	100°F	0°F
Ambient Air Humidity	40%RH	---
Number of Vehicle Occupants	4	3
Insolation	333 Btu/hr/ft ²	0
Interior Air Temperature Time Constant	3.0 Minutes	3.0 Minutes

Table 4-4: Cooling Loads* For Different Thermal Design Options For A Mini-van (Chrysler TE Van)

	Hot Soak Temp.	Steady State Load	Peak Transient Load
Fresh Air Mode, Clear Glass, No insulation	172°F	25,011 Btu/hr	42,493 Btu/hr
Recirc Mode, Clear Glass No Insulation	172°F (0%)	13,550 Btu/hr (-46%)	34,032 Btu/hr (-19.9%)
Recirc Mode, Current Glazing, No Insulation	163°F (-12.5%)	12,235 Btu/hr (-51.1%)	30,817 Btu/hr (-27.5%)
Recirc Mode, Wavelength Selective Glazing, No Insulation	153°F (-26.3%)	11,389 Btu/hr (-54.4%)	27,859 Btu/hr (-34.4%)
Recirc Mode, Clear Glass, Roof Insulation	175°F (+4%)	12,382 Btu/hr (-50.5%)	33,915 Btu/hr (-20.2%)
Recirc Mode, Wavelength Selective Glazing, Roof Insulation	151°F (-29.2%)	10,221 Btu/hr (-59.1%)	26,586 Btu/hr (-37.4%)
Recirc Mode, Wavelength Selective Glazing, Full Insulation	164°F (-11.1%)	9,071 Btu/hr (-63.7)	28,846 Btu/hr (-32.1%)
Recirc Mode, Wavelength Selective Glazing, Full Insulation, 100 CFM Vent Air During Static Soak	120°F (-72.2%)	9,071 Btu/hr (-63.7%)	19,070 Btu/hr (-55.1%)
Recirc Mode, Switchable Glazing, Full Insulation	137°F (-48.6%)	9,071 Btu/hr (-63.7%)	22,847 Btu/hr (-46.2%)
Recirc Mode, Switchable Glazing, Full Insulation, 100 CFM Vent Air During Static Soak	111°F (-84.7%)	9,071 Btu/hr (-63.7%)	17,070 Btu/hr (-59.8%)

* 100°F ambient temperature, detailed assumptions listed in Tables 4-1, 4-2 and 4-3.

Table 4-5: Cooling Loads* For Different Thermal Design Options For A Compact Sedan (Nissan Stanza)

	Hot Soak Temp.	Steady State Load	Peak Transient Load
Fresh Air Mode, Clear Glass, No insulation	211°F	21,809 Btu/hr	38,813 Btu/hr
Recirc Mode, Clear Glass No Insulation	211°F (0%)	10,349 Btu/hr (-52.5%)	30,906 Btu/hr (-20.4%)
Recirc Mode, Current Glazing, No Insulation	193°F (-16.2%)	9,233 Btu/hr (-57.7%)	27,070 Btu/hr (-30.2%)
Recirc Mode, Wavelength Selective Glazing, No Insulation	173°F (-34.2%)	8,515 Btu/hr (-61%)	23,329 Btu/hr (-39.9%)
Recirc Mode, Clear Glass, Roof Insulation	218°F (+6.3%)	9,985 Btu/hr (-54.2%)	31,770 Btu/hr (-18.1%)
Recirc Mode, Wavelength Selective Glazing, Roof Insulation	172°F (-35.1%)	8,152 Btu/hr (-62.6)	22,929 Btu/hr (-40.9%)
Recirc Mode, Wavelength Selective Glazing, Full Insulation	188°F (-20.7%)	7,837 Btu/hr (-64%)	25,265 Btu/hr
Recirc Mode, Wavelength Selective Glazing, Full Insulation, 100 CFM Vent Air During Static Soak	118°F (-83.7%)	7,837 Btu/hr (-64%)	14,469 Btu/hr (-62.7%)
Recirc Mode, Switchable Glazing, Full Insulation	145°F (-59.5%)	7,837 Btu/hr (-64%)	18,663 Btu/hr (-51.9%)
Recirc Mode, Switchable Glazing, Full Insulation, 100 CFM Vent Air During Static Soak	109°F (-92%)	7,837 Btu/hr (-64%)	13,081 Btu/hr (-66.3%)

* 100°F ambient temperature, detailed assumptions listed in Tables 4-1, 4-2 and 4-3.

Table 4-6: Heating Loads For Different Thermal Design Options

Test Condition	Mini-van		Compact Sedan	
	Steady State	Transient	Steady State	Transient
Fresh Air, No Insulation	25,500 Btu/hr	39,080 Btu/hr	20,605 Btu/hr	30,012 Btu/hr
Recirc Mode	10,930 Btu/hr	26,780 Btu/hr	6,015 Btu/hr	17,365 Btu/hr
Recirc, Roof Insulation	9,290 Btu/hr	25,460 Btu/hr	5,552 Btu/hr	16,978 Btu/hr
Recirc, Full Insulation	6,880 Btu/hr	23,580 Btu/hr	4,829 Btu/hr	16,415 Btu/hr

* 100°F ambient temperature, detailed assumptions listed in Tables 4-1, 4-2 and 4-3.

4.2.1 Steady State Cooling Loads

Steady state cooling loads are reduced by decreasing ventilation air, using low transmissivity glazings, and insulating the roof and body panels. Limiting the ventilation make up air flow rate to the minimum level necessary to maintain interior air quality is

single most important measure for reducing steady state cooling loads. Measures to reduce solar and conduction loads provide incremental, but in combination, significant additional load reductions. The insulation of the compact sedan is less advantageous than with vans, because considerably less surface area is exposed to heat transfer between the interior and exterior of the vehicle. The application of wavelength selective glass can substantially reduce cooling loads and hot soak temperatures. Since prototype cars, e.g. GM Impact, and production vehicles, e.g. Lumina APV, are using this type of glass, it could readily be applied to future electric vehicles. Insulation should be installed in the roof and body panels of all mid-size and up electric vehicles produced. The benefit of insulation for compacts and sub-compacts is much smaller. However, roof insulation can be installed in a compact with very little additional cost and complications to assembly.

4.2.2 Transient Cooling Loads

Reduced transmissivity glazing and a low powered ventilation fan are both effective methods to reduce hot soak temperatures and the associated transient cooling load. Roof and body insulation have a minimal impact. The ventilation fan is the most effective method to reduce the transient cooling load. When combined with PPG Sungate type glass, the transient cooling loads become lower than the steady state cooling loads encountered in today's automobiles. The combination of a switchable glazing, ventilation fan, and insulation will lower the hot soak temperatures to within 10°F of the ambient, and further decrease transient cooling loads, but commercial availability of switchable glazings will not occur for several more years. These design options for thermal load reductions will decrease the air conditioning size to less than 1 ton while providing excellent cooling performance in steady state and transient operating conditions periods.

4.2.3 Steady State Heating Loads

As indicated in Table 4-6, the same design measures that result in reduced cooling loads, provide substantial reductions in heating loads. Limiting ventilation make up air flow rates provides for the most significant reductions of heating loads. In vans, body and roof insulation provide for a significant incremental load reduction. The reduced heating loads increase the opportunity to use heat pumps or other reversible cycles to heat and cool an electric vehicle, even in low ambient temperatures.

5.0 Heat Pump Cycle Heating

Most electric vehicles now use liquid fuel fired heaters to perform space heating and defrost functions. An alternative to the combination of a fuel fired heater and a separate air conditioning system is to use an electrically driven heat pump system which can service both heating and air conditioning needs. Such a system would simplify the space conditioning system design and reduce the overall size and weight of the space conditioning system by eliminating the need for a separate liquid fuel fired heater. It would also eliminate the need to service two energy sources on the vehicle thereby increasing consumer acceptance.

The use of a reversed cooling, or heat pump, cycle to accomplish space heating is a well established technique for building space heating applications. For example, close to one fourth of the residential central air conditioning systems sold in the United States are heat pumps, providing both space cooling and space heating. In principle, each of the alternative cooling cycles considered in this study could be operated with a reverse cycle to provide vehicle heating (and windshield defrosting/defogging) when required.

There are several considerations that need to be taken into account to evaluate the applicability of a reverse cooling cycle to vehicle interior space heating:

- The heating capacity of any heat pump cycle will decrease as the ambient air temperature decreases. On the other hand, the vehicle space heating load increases with decreasing ambient temperature. As illustrated in Figure 5-1(a), for a given system in a given vehicle, below a certain ambient temperature commonly referred to as the "balance point", the heating capacity will be less than the heating load, and supplemental heat will be required to maintain a comfortable interior temperature. The balance point depends on the slopes of the capacity and load curves, and whether the system capacity was specified to meet a design cooling load or meet the heating load at a particular ambient temperature. In the latter case, the system will have excess cooling capacity, and cooling efficiency may suffer a significant penalty. As shown in Figure 5-1(b), a variable capacity system can be designed to meet a low ambient temperature, and operate at reduced capacity at higher ambients. System cooling efficiency will tend to be penalized by the over capacity to the extent that the efficiency at lower percentage of full capacity is lower than at full capacity. The capacity versus ambient temperature differs for different thermodynamic cycles and is discussed in the detail sections that follow. Back-up heat sources are discussed below.
- Defrosting the ambient air heat exchanger: in the heating mode, when the ambient air coil fin surface temperature is below 32°F, ambient air moisture will condense and freeze onto the fin surface, gradually building up and blocking airflow through the coil. Defrosting cycle design considerations are discussed below.
- Windshield defrosting is discussed below. FMVSS 103 specifies minimum deicing performance, as measured by a specific test procedure.

Figure 5-1: Heat Load and Heating Capacity Relationship

- To provide the capability to reverse the operation from cooling mode to heating mode requires additional components and working fluid plumbing and/or air ducting. In the detailed descriptions of the cycle alternatives in the next two sections, the specific means of providing reverse cycle operation are addressed.

The attractiveness of using a heat pump cycle varies with climatic region. In milder climates, back-up heat is required less frequently and the energy consumption per trip for heating (and the equivalent battery weight) compare favorably with the weight saved by eliminating the fuel fired heating system.

5.1 Fuel Fired Heating Systems

Table 5-1 lists some examples of fuel fired vehicle heaters that have been used in electric vehicles, and reflects the variety of approaches that have been utilized. Diesel fuel is the most commonly used fuel, and both direct air heaters and hot water heating systems, coupled to a conventional heater core, have been used. In addition to the heater, the complete system includes a fuel tank, fuel lines, an exhaust system, and associated mounting hardware and electrical wiring. Typical complete system weight and cost penalties are not insignificant (50 pounds dry weight and approximately 800 to 1,000 dollars, respectively). The energy (fuel) consumption does not contribute to traction power requirements, and, therefore, represents an increase in the total energy consumption of the vehicle. At a heat pump COP greater than 2.5, the primary energy consumption (fuel burned at the electric plant) of the heat pump will be less than with a typical fuel fired heater (battery charge-discharge efficiency of 75%; overall electric generating and transmission efficiency of 28%, approximately the U.S. average; heater fuel utilization efficiency of 70%; and fuel fired heater parasitics (fans, fuel pump, water pump) of 3 Watts per 100 Btu/hr delivered heating). At a COP of 2.5, a steady state heating load of 4,000 Btu/hr (design heating load for the Los Angeles area), and a battery energy storage density of 16 Watt-hr/pound, the energy stored in approximately 30 pounds of battery weight would be consumed for each hour of heat pump operation.

Table 5-1: Examples of Direct Fuel Fired Vehicle Heating Systems Used in Electric Vehicles

Vehicle	Manufacturer	Hot Water or Direct Air	Fuel	Heating Capacity Range, Btu/hr	Fuel Utilization Efficiency	Heating Unit Only Weight/lb	Installed System Weight, lb
ETX-II	ESPAR D3L or D4L	Air	Diesel	D3L 11,000 D4L 15,000	79% 72%	14 14	~55
TE-Van	ESPAR, D5W	Hot Water	Diesel	17,000	76%	9	56
G-Van 1991 production	Webasto, DW80	Hot Water	Diesel	26,000 (high) 7,700 (low)	77% 81%	10.5	~70
G-Van pre-production	ESPAR, D5W	Hot Water	Diesel	17,000	76%	9	~70

5.2 Back-up Heat Sources

When a heat pump cycle is used as the primary heat source, back-up heat is required when, at low ambient temperature, the steady state heating capacity is less than the steady state heat load. Back-up heat may be required to supplement the heat pump output to increase the warm up rate when starting from a cold soak. Table 5-2 lists generic alternative back-up heat sources. Electric resistance heat, which is generally used for back-up heat in residential heat pumps, is low cost, light weight, and has very rapid response due to small thermal mass of electric heating elements. Electric resistance heat can be used to heat air or to heat vehicle interior surfaces (e.g. window defrosters, seat heaters). For heating air, electric heating elements would be located

downstream of the heat pump interior air heat exchanger. Fixed resistance wire heating elements are simple and low cost. A recent development is a positive temperature coefficient resistance element (reference 15), whose resistance increases sharply near a transition temperature. A degree of passive, self regulation is provided by this characteristic, so that the heat output decreases as the inlet air temperature increases. The regulation so provided is coarse in a control sense, so a means of controlling the output is required. Electric resistance seat heaters, which are used in some luxury cars, may be an energy effective means of quickly providing an acceptable comfort level from a cold start.

Table 5-2: Summary of Back-up Heat Sources

Back Up Heat Source	Transient Response (Warm Up Rate)	Comment
Electric Resistance	Fast	Low Cost, but direct range penalty reduction
Fuel Fired Air Heaters	Fast	Cost - weight - emissions penalties See Table 5-1
Fuel Fired Water Heater Coupled to Heater Core	Moderate	Cost - weight - emissions penalties See Table 5-1
Vehicle Waste Heat Recovery	Slow	See Table 5-3, "Free " heat, in many EVs the inverter and motor/transmission are water cooled, heat is readily directed to vehicle heating

In principle, a fuel fired air heater could provide back-up heat, particularly in the coldest climates. Advantages include quick response and vehicle warmup from cold soak, and minimal adverse impact on the vehicle range. However, all of the disadvantages of fuel fired heaters would apply, effectively negating much of the potential advantage of the heat pump cycle.

Vehicle waste heat sources could be utilized as a primary or supplemental heat source. The battery pack, the main controller, and the motor/transmission are the major components in the conversion of energy stored in the battery into vehicle traction power. The latter two of these are reasonably compact, so heat dissipated in these components might be recovered and used for interior heating. The thermal response will be slower than with electric resistance or fuel fired heaters, but the heat recovered is energy that will be dissipated in any event. Heat can be recovered and managed most readily when the motor/transmission and inverter heat sinks are liquid cooled, as shown in Figure 5-2.

To develop an estimate of the steady state heating capacity that might be available from these sources, the "typical" EV drive train efficiencies shown in Figure 5-3 were applied to the energy consumption of a sample of electric vehicle prototypes, for constant speed operation at 55 MPH and for the FUDS (these assumptions are representative, however the characteristics of a specific vehicle need to be accounted for when designing a heating system for that vehicle). The motor and transmission were taken to be an integrated package, the most common arrangement in EVs. The calculations are

Figure 5-2: Use of Liquid Cooling Loop for Major EV Driveline Components for Vehicle Interior Heating

summarized in Table 5-3. For the compact car and mini-van, whose estimated heating loads were presented in Section 2.1.2 (given some modest thermal load control measures), the heat dissipation rate in the motor/transmission is a sizable fraction of the steady state heating load in a severe climate for these vehicles, and in excess of the design steady state heating requirements in milder climates. A lesser, but not insignificant, and concentrated and easily recoverable, amount of heat is dissipated in the main traction motor controller. A high percentage of the heat dissipated in a liquid cooled inverter heat sink can be recovered for interior heating, because the heat sink will not lose a substantial amount of heat via other thermal paths. The motor transmission will generally be exposed directly to ambient air, so a larger portion of the heat dissipation will be lost to ambient. In the estimate of potential electric heating performance in Section 2.2.3.3 recovery of 50% of the waste heat was assumed.

Figure 5-3: Representative Driveline Component Efficiencies (based on data from references 2, 3, and 7)

Table 5-3: Estimated Rate of Power Dissipation in the Main Controller and Traction Motor/Transmission for Selected Electric Vehicles

Vehicle	Driving Cycle*	DC Energy Consumption kWh/mi		Average Power** kW	Waste Heat Watts	
		Net	Gross		Controller	Mot/Trns
Impact	FUDS 55	.110	~.12	2.6	210	490
		.113	.113	6.2	125	600
EV Cort	FUDS 55	.341	.364	7.8	620	1430
		.257	.275	14.1	280	1380
ETV-I	FUDS 55	.280	~.31	6.8	540	1250
		~.20	.20	11.0	220	1080
ETX-I	FUDS 55	.335	.369	8.1	650	1490
		.260	.260	14.3	285	1400
ETX-II	FUDS 55	~.4	~.43	9.2	740	1700
		~.4	~.4	22	440	2150
TE-Van	FUDS 55	~.4	~.43	9.2	740	1700
		~.4	~.4	22	400	2150
G-Van	FUDS 55	.62	.67	14.6	1170	2700
		.63	.63	35	700	3400

* Average speed in FUDS is 20 mi/hr; 55 means constant 55 mi/hr (88 km/hr)

** Total of traction and regeneration power through controller and motor/transmission

The heat dissipation in batteries is comparable to the heat dissipation in the other major drive line components. Due to the size of the battery pack the dissipated heat is not as readily recovered and managed. Batteries that operate at normal temperatures, e.g., lead-acid or nickel-iron, are generally packaged in a battery tray having no specific provisions for thermal management and recovery of heat dissipated during charging and discharging. Even those battery packs having forced air cooling are not configured so that the exhaust cooling air could be used to heat the vehicle interior. As battery thermal management techniques aimed at maintaining optimum temperatures for battery energy output and cycle life are adopted, provision for use of the waste heat for interior heating could be included. Cooled high temperature batteries, e.g. sodium-sulfur, have a concentrated, or potentially concentrated, waste heat stream that could be applied readily to interior heating. Because the battery must be maintained at operating temperature, waste heat would be available instantly upon starting to operate the vehicle.

Given the penalties associated with accessory electric power consumption and with fuel fired heating systems, serious consideration should be given to using these heat sources as a primary source of "free" heat, analogous to the use of engine coolant heat for heating the interior of an ICE powered vehicle.

5.3 Ambient Air Coil Defrosting

As noted above, when the ambient air temperature is low enough so that the temperature of the fins in the ambient air coil is below 32°F and below the ambient air dew point, moisture will condense from the ambient air passing over the coil and freeze onto the fin surface. Generally, frosting will not occur at ambient temperatures above 45°F, or at relative humidities below about 30%. Over time, the thickness of the frost layer will increase, restricting the flow of air through the coil and significantly reducing the system heating capacity. To restore the system capacity, the accumulated frost must be removed from the fins, generally by melting and draining the liquid water from the coil.

The rate of frost build up to the point of significant system performance degradation depends on the ambient moisture content and the coil depth and frontal area relative to the system capacity. In residential heat pumps, operating at the DOE frost accumulation test conditions (ambient air at 30°F dewpoint, 35°F dry bulb temperature) that are representative of worst case frost accumulation conditions, defrosting is typically required once per hour. A similar, worst case, interval can be expected for a vehicle heat pump. Considering the finite range of electric vehicles, and the correspondingly finite operating interval before recharging the traction battery, in many instances defrosting may not be required between battery charging cycles.

Notwithstanding the preceding factors, the capability to defrost the ambient air coil, while the vehicle is being driven, will probably be needed.

In residential heat pumps, defrosting is typically carried out, either at a timed interval or on the basis of detection of the need for defrosting ("demand defrost"), by reversing the cycle back to cooling mode, but with the outdoor fan shut off and the back up heat source operating. With the fan off, the outdoor coil temperature quickly rises above freezing, melting the ice. For residential heat pumps, and on a seasonal basis (heating season), the energy efficiency penalty due to frost accumulation and defrosting is on the order of 5%. In a motor vehicle application, some additional factors must be considered:

- When the vehicle is moving, airflow will be forced through a front facing heat exchanger, even if the fan is not operating. To allow the coil to heat up rapidly during the defrost cycle, louvers that close to prevent airflow may be required; and
- The penalty to vehicle range for using back up electric resistance heat during the defrost cycle is more significant than the applicable penalties in most residential heating applications. An alternative heat source for defrosting may be merited, such as stored heat, extracted by subcooling the liquid refrigerant during normal heating operation, as illustrated in Figure 5-4.

Figure 5-4: Water Heat Storage Modification to a Vapor Cycle Heat Pump to Supply Heat Required for Defrost Cycle

All of the reversible cycles considered herein are subject to the same defrosting requirements, with the exception of the open reverse Brayton cycle. In heating mode, ambient air is taken directly into the compressor and the colder air leaving the expander is exhausted directly to ambient. The exhaust air may include entrained frost particles that condensed and froze during the expansion process. The other cycles extract heat from ambient air via finned heat transfer surfaces, all subject to frost build up under the conditions described above.

5.4 Windshield Deicing

Traditionally windshield defogging, defrosting, and deicing has been effected by warm air, heated by the heater core via hot engine coolant, being blown up over the interior surface of the windshield from vents located on the top of the dashboard, at the base of the windshield. In the past few years, electrically heated windshields have become available in certain production automobiles. For example, Ford offers this as an optional accessory, called the "Insta-Clear" Windshields, in all Lincoln Continentals and in the Ford Taurus and Crown Victoria, and the Mercury Sable and Gran Marquis. The windshields are manufactured internally by Ford. GM offers a similar option, the "Electra-clear" windshield, which is manufactured by Libby-Owens-Ford. To heat the windshield electric current is passed through a thin transparent metallic film coating between the windshield laminations. Approximately 1,000 Watts (1 watt/sq in) is dissipated, very quickly heating and clearing the windshield. It will remove a one tenth of an inch thick layer of ice in two to three minutes; usually it will clear the windshield in less than a minute. The electric energy consumption, therefore, is quite modest, on the order of 10 to 20 Watt hours per defrost/defog. Under very damp conditions, frequent operation, or continuous, low power operation may be needed. The current cost of this option is about \$300 retail. The approximate OEM cost is \$60 for the windshield metallic film. This technology has been commercially available for only the past few years. As it becomes more widely available and accepted, the cost can be expected to fall. An additional feature of the metallic coating is that it acts as a solar control film, limiting both visible and ultraviolet transmission, with characteristics similar to PPG "sungate" glass.

Defogging may be required under a variety of conditions, independent of whether the vehicle requires interior heating, cooling, or neither. The separation of the interior space conditioning and windshield/rear window clearing operation is therefore highly desirable. In view of this, the relatively modest energy consumption, the quick response, and the added feature of solar cooling load reduction, we have concluded that this is the preferred method for windshield defrosting. Heat pump cycle heating performance, therefore, has been evaluated with respect to interior space heating requirements only.

6.0 Vapor Cycle Cooling and Heating

Virtually all commercially produced refrigeration and air conditioning equipment is based on the vapor compression cycle. The overwhelming competitive dominance of vapor compression cycle equipment is attributable to the lower cost, higher efficiency, and higher reliability of equipment based on this cycle in comparison to cooling equipment that has been developed using other thermodynamic cycles as the basis of their cooling effect.

Nevertheless, the direct application of conventional automobile air conditioning equipment to electric vehicles results in significant performance penalties. All production mobile air conditioning systems utilize a vapor compression cycle system whose compressor is belt driven by the engine. The designs of these systems have been optimized for low cost, weight, and size. The cooling capacity is set to provide adequate comfort under very high ambient temperature and/or humidity conditions, with 100% ventilation make up air through the evaporator, in city driving conditions. Under all other conditions (higher vehicle and engine speed and lower ambient temperature/humidity and cooling load), the systems have considerable excess cooling capacity and consume excess power. Power consumption and efficiency, though not completely neglected as a design consideration, is of secondary importance to the design of conventional mobile air conditioning systems.

Because of all of the above enumerated factors, standard automobile air conditioning systems are not well suited to electric vehicle applications. In particular:

- Unlike conventional automobile air conditioning, where the engine idles when the vehicle is stationary and can, therefore, drive the air conditioning compressor, the traction motor of an electric vehicle does not rotate when the electric vehicle is stationary, and, therefore, cannot adequately power the air conditioning compressor in stop-go driving conditions.
- The availability of an electric power source (i.e., the traction battery pack), provides the opportunity to decouple the compressor speed from the engine speed and more closely match the compressor speed to the actual cooling requirements, with resulting improvements in both performance and efficiency.
- Because of the importance of maintaining the driving range of electric vehicles, efficiency over the normal range of driving cycles and ambient conditions is a primary design consideration for electric vehicles. Measures to reduce thermal loads and corresponding cooling capacity requirements, and to improve the cooling efficiency of the air conditioning systems are justified.

Another major issue that has faced the automobile air conditioning industry is the now in-process phase out of CFCs due to their role in both stratospheric ozone depletion and global warming. Automobile air conditioning systems have utilized CFC-12, almost without exception, since the 1930s when automobile air conditioning was introduced.

The automobile industry is preparing to phase out CFC-12, using a substitute refrigerant, HFC-134a, instead. The options relative to electric vehicles are discussed in subsection 6.2.

As discussed in the preceding sections, the potential use of the air conditioning system, in a reversed, heat pump, cycle for vehicle interior heating is of interest, given the penalties associated with a fuel-fired heater.

Performance was estimated for a range of vapor cycle system design alternatives, beginning with a system derived entirely from production automobile air conditioning system components (except for the compressor drive motor). The heating and cooling performance is analyzed based on a design capacity meeting the thermal load characteristics presented in Section 2.1.2. These loads are representative of an electric mini-van or compact car with a relatively modest set of design measures to reduce the thermal loads, as described in Section 2.1.2. With this performance level as a baseline, vapor cycle design measures to improve the efficiency were examined (with the baseline vehicle thermal design retained). These measures are:

- Variable speed compressor drive -- allows better part load performance through more effective utilization of heat transfer surface and reduced parasitics and cycling losses. Also, increased compressor design capacity can be specified to provide more rapid cooldown from a hot soak and to meet lower ambient temperature heating loads, without significantly reducing cooling efficiency
- Increased condenser and evaporator frontal area and/or air flow rate. Raises evaporator, reduces condenser temperatures, reducing compressor input power, but parasitics may be increased.
- An evaporator and interior air blower arrangement aimed at allowing higher air flow rates at lower fan power, increasing efficiency through reduced compressor power and reduced parasitics.

The performance of the preceding were estimated first based on steady state operation. Performance is also estimated for the initial part of a hot soak pull down or, in heating mode, cold start-up.

The baseline vapor compression system consists of available automotive hardware and was analyzed to generate both cooling and heating performance and to provide a basis of comparison with more advanced equipment. The major components and subassemblies are a belt driven, constant speed compressor assembly, an ambient air coil assembly, and an interior air coil assembly. A schematic of the baseline vapor compression system is shown in Figure 6-1, and is described in detail in Appendix E (E.1.1).

Figure 6-1: Baseline Constant Speed Belt Driven Compressor Vapor Compression System

The variable speed system is essentially the same as the baseline belt driven system with the exception of the compressor/drive motor. A schematic of the system is shown in Figure 6-2. The constant-speed belt driven scroll compressor assembly is replaced with a semi-hermetic, variable speed, brushless DC motor driven scroll compressor. The brushless DC motor directly drives the scroll compressor and the assembly is mounted within an aluminum housing. The motor/compressor speed is controlled to maintain a passenger-set air delivery temperature. The overall motor and control electronics efficiency is 85% for this system. Parasitic power consumption is reduced with the elimination of the compressor clutch. This type of compressor assembly is currently produced in prototype quantities by Sanden International. These prototype units have a 33cc displacement scroll set, a maximum speed of 6000 rpm, and a corresponding capacity of 18,000 Btu/hr at ASHRAE standard test conditions. A detailed description of this configuration is in Appendix E (E.2.1).

Figure 6-2: Variable Speed Vapor Cycle Air Conditioner/Heat Pump Configuration

The performance was calculated for several variations of the heat exchanger sizing and interior blower drive of the variable speed drive configuration (described in more detail in Appendix E):

- Increased face area condenser, 2.83 ft² versus 1.35 ft², otherwise identical to the baseline condenser (described in E.1.1). Condenser fan power is assumed to be the same as the baseline case.
- Improved evaporator #1: 33% increased face area and air flow (resulting in increased evaporator temperature and reduced compressor power). Interior blower power also increased 33%.
- Improved evaporator #2: 50% increased face area and air flow, coupled with larger cross section air delivery duct work, so that the interior blower power is increased by only 20%.

- Continuously variable speed, chopper or PWM driven, interior air blower. At reduced loads, the power consumption of the blower can be reduced drastically (power is proportional to the cube of the blower speed and air flow rate; for example, at one half the maximum flow rate, the power is only one eighth of the maximum).
- The "Roof" evaporator, a large face area, high air flow rate, low parasitic power evaporator configuration.

The detailed results of the performance analyses for the design variations listed above are in Appendix E. The performance analyses accounted for thermodynamic cycle performance (including motor/compressor efficiency), heat exchanger performance (assuming constant heat transfer effectiveness, with air side/refrigerant side heat transfer rates balanced), and parasitic power. Refrigeration cycle performance was calculated using a computer-based cycle model that incorporates the thermodynamic properties of most current and alternative refrigerants.

Figures 6-3 and 6-4 compare the steady state cooling COP for the variations described above, at design conditions (the Phoenix design ambient temperature of 109°F), and at part load conditions (at a moderate cooling season ambient temperature of 90°F), respectively. At design conditions, the semi-hermetic direct driven variable speed compressor yields a modest COP increase due to the elimination of clutch power and belt drive losses and the incrementally higher efficiency of the brushless DC compressor drive motor. Modest COP increases are obtained through increased heat exchanger sizing, with the exception of "improved evaporator #1," where increased interior blower power negates the reduction in compressor power that accompanies the increased evaporator capacity. The "roof" evaporator, though a departure from the conventional vehicle interior HVAC arrangement, yields a substantial increase in COP over all other options due to reduced compressor and parasitic power. The general range of COP levels shown in Figures 6-3 and 6-4 are compared with the COP levels of alternate cycles in Section 2.

At the part load conditions of Figure 6-4, the variable speed configurations yield larger percentage increases in the COP. The combination of an efficient, variable speed scroll compressor, a continuously variable speed interior air blower, and a high performance condenser is particularly attractive for near and medium term EV cooling applications. It operates at high COP levels over the cooling season range of ambient temperatures. It is based on technology that is currently in the advanced stages of development (the variable speed scroll compressor) or commercially available (the high performance condenser). The variable speed blower is commercially available in configurations that operate at 12 volts, used in electronic climate control systems.

Figure 6-3: Variable Speed Compressor System Improvements

Figure 6-4: Steady State Part Load Cooling COP Comparison of Vapor Cycle Variations at Moderate Ambient (90°F)

The following subsection summarizes the calculated performance for this configuration in a form that can be used together with an EV thermal load and an EV performance model to estimate the energy consumption and range penalties for a given combination of driving cycles, trip lengths, thermal soak periods, and ambient conditions.

6.1 Vapor Cycle Performance Characteristics - Selected Variable Speed System Configuration

The system configuration details are summarized in Table 6-1. The major features of this configuration are the variable speed compressor, the variable speed blower, and the large capacity condenser. To provide transient cooling performance that is comparable to conventional automobile air conditioning practice, the system design conditions cooling capacity is 150% of the design conditions steady state cooling loads. The performance characterization that follows is specifically applicable to this configuration as applied to an electric mini-van having the baseline thermal design features described in Section 2.1.2. For performance estimation purposes, the results can be scaled and extended to other vehicle configurations, but for design, detailed modeling of the specific vehicle and system configuration needs to be carried out.

Table 6-1: Major Design Parameters of Selected Configuration of Vapor Cycle

Parameter	Value	Comment
Nominal maximum cooling capacity	13,000 Btu/hr	150% of the calculated "Phoenix" steady state mini-van cooling load (Table 2-2)
Evaporator	Baseline design	Conventional automobile A/C
Condenser face area	2.83 ft ²	See Figure E-8
Condenser fan power	60 watts	
Interior blower power @ 265 cfm @ 200 cfm @ 150 cfm @ 100 cfm @ 50 cfm	230 watts 100 watts 45 watts 20 watts 10 watts	Efficient PWM or chopper driven variable speed motor. Power proportional to the air flow rate cubed.

¹ At maximum compressor speed, 109°F ambient temperature, 75°F interior temperature, and vehicle speed of 30 miles/hr.

6.1.1 Cooling Mode Performance

The steady state cooling COP (based on total electric power input) and capacity for this configuration are shown in Figure 6-5. The upper curve is the approximate, average capacity at maximum compressor speed during a transient cooldown from hot soak. The incremental increase in capacity over steady state is due to the higher return air temperature to the evaporator and the resulting increase in evaporator temperature. Figure 6-6 compares the transient cooling capacity with the six minute time constant/20 minute average transient cooling load of the baseline vehicle configuration (Section

2.1.2). In general, for the selected configuration, sufficient capacity is available to cool the vehicle at the six minute time constant rate, consistent with typical automobile air conditioning pull down performance. Transient performance is mapped in Figure 6-7, with plots of COP versus ambient temperature, at several cooling capacity levels.

Figure 6-5: Steady State Cooling Performance of Selected Variable Speed Vapor Cycle Configuration

Figure 6-6: Comparison Transient Cooling Capacity with Transient Cooling Load

Figure 6-7: Transient Cooling Performance of Selected Variable Speed Vapor Cycle Configuration - Mid-Cooldown from Hot Soak, at 90°F Vehicle Interior Temperature

6.1.2 Heating Mode Performance

The steady state heating mode performance is plotted in Figure 6-8, assuming that the entire steady state load is met by the heat pump. As discussed in Sections 2 and 5, a substantial portion of the steady state cooling load can be met by recoverable waste heat in the vehicle. The shortfall in capacity at the lowest ambient temperatures can be readily met by vehicle waste heat sources, as indicated in Figure 2-4. Figure 6-9 compares the six minute time constant/20 minute average transient heating load (Section 2.1.2) with the transient heating capacity of the selected variable speed configuration at the maximum compressor speed. At low ambient temperatures, there is a considerable short fall in capacity relative to load, due to the combination of increased load with decreasing ambient temperature and the characteristic fall off in vapor cycle capacity with decreased ambient temperature. In principle, a variable speed compressor could be sized so the heat pump cycle can meet the cold ambient transient load, and operate at reduced capacity at other conditions, but considerable over capacity results. In cooling mode in particular, operation would generally be at a small fraction of maximum capacity, where the part load motor and compressor efficiencies are degraded significantly. As discussed in Section 2.2.3.3, the vehicle range penalties for using back up electric resistance heat are reasonably modest for most driving patterns except at ambient temperatures below 0°F. High temperature batteries (e.g. sodium-sulfur) are also a potential source of back up heat during warm up. Transient COP is shown in Figure 6-10, with heat pump COP (total electric input basis) plotted against ambient temperature (not accounting for back up heat needed to meet the total load at colder ambient temperatures), at several capacity levels. It should be noted that at the low capacity levels, the air delivery temperature from the heat pump cycle is low, with a correspondingly low condensing temperature, which accounts for the unusually high COP levels projected at the low ambient temperatures.

Figure 6-8: Steady State Heating Performance of Selected Variable Speed Vapor Cycle Configuration

Figure 6-9: Comparison of Transient Heating Capacity with Transient Heating Load

Figure 6-10: Transient Heating COP of Selected Variable Speed Vapor Cycle Configuration

6.2 Non-CFC Alternatives to CFC-12

Current Federal legislation and regulations require the phase out of CFC-12 production by the year 2000. A variety of alternative refrigerants to replace CFC-12 in automobile air conditioning are under consideration, summarized in Table 6-2. The automobile industry is currently investing considerable product development resources into the adaptation of current systems to accommodate the use of HFC-134a, whose vapor pressure-temperature curve approximates that of CFC-12, as shown in Figure 6-11. Major characteristics of HFC-134a that require some system design adjustments include a steeper vapor pressure-temperature curve and lower critical temperature, and poor solubility with the mineral oil type lubricants most commonly used in automobile air conditioning systems. Higher efficiency (and higher cost) condensers are being developed and specified to reduce maximum condensing temperature and pressure levels. New lubricants, polyglycols, have been developed which are soluble with HFC-134a, but the overall effectiveness of their lubricating characteristics and the effect on compressor durability remain in doubt. While HFC-134a emissions will have a much more benign set of environmental effects than CFC-12 (0 ozone depletion potential, global warming potential less than 1/10 of CFC-12), HFC-134a is still a powerful greenhouse gas and the overall efficiency of HFC-134a cycles is somewhat lower than those using CFC-12 and comparable amounts of heat transfer surface. The most widely considered alternatives are described briefly below.

Table 6-2: Refrigerant Alternatives for Automobile Air Conditioning

Refrigerant	Ozone Depletion Potential	Global Warming Potential	Comments
CFC-12	1.00	4000	Standard Auto A/C refrigerant
HFC-134	0	380	Current industry favored alternative. Small efficiency penalty. Still not in large scale production
Ternary Blend (HFC-152a, HCFC-22, HCFC-124)	0.03	~200	Near drop in, except for material compatibility considerations
HCFC-22	0.05	480	Metal tubing required throughout system. Readily available through 2020. Higher pressure
HCFC-22/ HCFC142b	0.05	500	Close to R-12 performance, R22 hose permeability a limitation
HFC-152a	0	43	Flammable, higher efficiency, low environmental impact
Propane	0	60	Flammable, very low cost, higher efficiency, low environmental impact

¹ CO₂ = 1.00

Regardless of the relative merits of the working fluid described below, for the foreseeable future there will be two practical non-CFC alternatives for EV air conditioning systems: the refrigerant selected by the automobile industry to replace CFC-12 in IC engine vehicle air conditioning systems, and HCFC-22. In the former case, the development costs associated with the alternative will have been covered by industry and maximum utilization of the automobile air conditioning mass production base can be made. In the latter case (HCFC-22), the electric power source driving the compressor allows the entire system to be "hard piped", i.e., all interconnecting tubing can be metal tubing to adequately contain the HCFC-22 charge. Standard components from both the automobile and building air conditioning markets can be utilized, and the practical characteristics of HCFC-22 -- thermodynamics, heat transfer, lubrication, materials compatibility, etc. -- are known and well understood.

The basic characteristics and status of selected alternatives are described briefly below.

HFC-134a

HFC-134a is under development by a number of the large chemical companies as a replacement fluid for CFC-12. It has an ODP of zero. As indicated by Figure 6-11 its physical characteristics are similar to those of CFC-12 which holds out good potential for use in applications currently using CFC-12 with only modest modifications in system and component designs. Cycle analyses indicate that HFC-134a should result in only a minor decrease in efficiency (1% to 3%), accompanied by a small decrease in capacity, in a fully developed system as compared to CFC-12. Limited experience to date using HFC-134a in refrigeration and automotive air conditioning units has usually

Figure 6-11: Comparison of Vapor Pressure-Temperature Curves of R12 and R134a

resulted in efficiency decreases of approximately 10%. These tests have usually been undertaken with little equipment modification so that the components are not optimized for HFC-134a use. Interpreting the results of the tests is further complicated by the requirement to use highly viscous oils with questionable miscibility with the working fluid. Both these factors would tend to lower the efficiency in a non-optimized system due to increased bearing drag (particularly important in the household refrigerator) and possible oil fouling of heat exchangers. With the development of a compatible oil for use of the oil/working fluid combination, it is possible that the efficiency impact can be reduced to the 4% to 8% range.

One of the key factors impacting on the timing of availability of this working fluid is that it is still undergoing toxicity testing and the process will require about 3 years. To date, the toxicity testing has not indicated a problem and none is foreseen. Nevertheless, this complicates the task of making commitments for its production and use.

Ternary Blend (HCFC-22/HFC-152a/HCFC-124)

In early 1989 duPont announced the development of a Ternary Blend which shows promise of being a "near drop in" for CFC-12. Its ODP is approximately 0.03. The percentage of blend components can be modified to vary efficiency and capacity properties. It is reported that the fluid with 30% HFC-152a should result in small improvement (1% to 2%) in efficiency as compared to CFC-12. This is consistent with the improvement estimated by cycle analyses when using pure HFC-152a (about 2% to 5%). Although considered a "near azeotrope," some concern exists over the possible partial composition shifts in the circulating fluid due to different hose permeation rates of the three components. The inclusion of several fluids complicates the oil lubrication issue. Testing to date has been done with alkylbenzene oil (commercially available, e.g., under the "Xerol" trade name), which should require some changes in compressor design, desiccant dryer materials, and possible heat exchanger designs to approach efficiency potential.

There is little known about the thermodynamic or thermophysical properties of this new working fluid alternative and, in fact, all testing to date has been done with CFC-114 being used as a surrogate for HCFC-124. Further complicating the potential timing of availability of this fluid is the uncertain toxicity characteristics of HCFC-124.

HCFC-22

HCFC-22, which has been produced in large quantities for many years, is the refrigerant used in the vast majority of building air conditioning equipment using positive displacement compressors. It has very low ozone depletion and global warming potentials compared to CFC-12, and is not currently subject to regulation of quantities produced. Eventually the production of all of the HCFCs will be phased out, but current legislation sets 2020 as the year that production phase out begins. HCFC-22 is a strong greenhouse gas compared to some working fluid alternatives. The inherent cycle efficiency of HCFC-22 is comparable to that of CFC-12, but pressures are considerably higher. A thermodynamic characteristic of HCFC-22 is that the refrigerant gas

temperature rise during the compression process is considerably higher than for CFC-12, and for virtually all other working fluids. HCFC-22 has a much higher permeability through the refrigerant hose materials commonly used in automobile air conditioning than CFC-12, a frequently cited factor for the reluctance of the automobile industry to adopt it as a substitute. The use of hoses to connect an engine mounted compressor to the remainder of the system is generally considered to be necessary to accommodate final assembly tolerances and, more importantly, to prevent the transmission of engine and compressor vibration to the vehicle body. In an electrically driven system tailored for EV use, all of the above cited difficulties with using HCFC-22 can be overcome.

HFC-152a

HFC-152a, which is currently produced commercially, for use as a component of CFC-500 and as a component of aerosol propellant blends and foam blowing agents, has thermodynamic properties similar to those of CFC-12 which should lead to minimal equipment changes to allow its use. It has an ODP of zero and very low global warming potential. Cycle analyses indicate that this fluid could increase efficiency levels up to 5% as compared to CFC-12. The primary, and very serious, drawback to this fluid option is its moderate flammability. The fire hazard is less than that of hydrocarbons such as propane (another good working fluid) as indicated by such measures as flammability limits, ignition energies, and combustion energy. The impacts of this moderate level of flammability on the potential use of this fluid in refrigeration equipment is now being investigated under an EPA contract by the National Fire Protection Research Foundation and Underwriter's Laboratories, and at Arthur D. Little. The safety implications of the use of this fluid, and other flammable working fluids, in automobile air conditioning equipment is also under investigation at Arthur D. Little, under a separate contract sponsored by DOE. The favorable performance potential, and unusually benign environmental effects associated with emissions of this working fluid provides a strong incentive to objectively review design options for allowing its safe utilization, especially in equipment having a small refrigerant inventory. However, at this time, manufacturers are reluctant to consider use of the refrigerant due to liability concerns.

HC-290 (Propane)

Much of the preceding material concerning HFC-152a is applicable to propane, although propane has a higher degree of flammability. Although the theoretical thermodynamic efficiency of propane is about 5% less than CFC-12, superior transport properties result in a significant reduction in heat transfer temperature differentials in the evaporator and condenser, more than compensating for lower theoretical efficiency.

7.0 Alternative Cycles

Although vapor compression cycle based systems are the only type of mobile air conditioning equipment in commercial production, there are several alternative cycles that merit consideration as longer term alternatives, for one or more of the following reasons:

- No CFC, or CFC alternative, working fluid is involved (reverse Stirling, reverse Brayton, magnetic refrigeration); and
- When used as a heating cycle, the capacity does not decrease as steeply with falling ambient temperature with vapor cycle (reverse Stirling, reverse Brayton).

7.1 Reverse Brayton Cooling Cycle

Turbo component based reverse Brayton cycle, or "air cycle" cooling systems powered by jet or gas turbine engine bleed air, are widely used for aircraft avionics and space cooling applications, where the light weight of the turbo components, and the absence of both a dedicated prime mover and cold side heat exchangers (and the associated weight) are compelling advantages over alternatives such as vapor cycle cooling systems. For application to electric vehicle cooling and heating, the inherently lower efficiency of the reverse Brayton cycle (compared to vapor cycle) is a major obstacle, despite potential advantages such as lighter system weight and quick transient response.

There are two basic configurations for Brayton cycle cooling that can be considered:

- Open cycle configuration in which the air to be cooled is the working fluid; and
- Closed cycle configuration in which a pressurized gas is the working fluid.

The basic or simple open Brayton cycle cooling system is shown in Figure 7-1. Interior air is compressed, cooled by an ambient air cooled heat exchanger, and then expanded back to atmospheric pressure conditions. The shaft power recovered by the expander supplies some of the power required by the compressor. Cold air exits the expander and is directed to the automobile interior. Several configurations have been used for the compressor and expander subsystems, including turbo components, scrolls, and rotary vane equipment. For electric vehicle applications, a centrifugal expander and compressor, similar to those used in automobile and truck engine turbo-superchargers, is probably preferred because of low weight and compact packaging, and the existence of a large, well established technology and mass production base for this type of compressor and expander. Moreover, the available range of air flow rates and the efficiency optimum pressure ratios match the general range of air flow rates and pressure ratio needed for passenger car cooling.

The advantages of the open cycle Brayton cooling system option include:

- A relatively simple configuration requiring only one heat exchanger and no requirement to seal against working fluid leakage in shaft and static seals;

Figure 7-1: Basic Open Reverse Brayton Cycle

- A zero cost working fluid (air) having no environmental impacts; and
- Potential for very reliable operation since gas bearings can be used on the rotating components turbo equipment.

In open cycle applications having relatively high lifts, and where the air entering the compressor is return air from the conditioned or refrigerated space, the performance of the basic open cycle can be improved somewhat by adding a recuperator, as shown in Figure 7-2. The recuperator precools the compressed air before it enters the expander, resulting in a lower expander outlet temperature and increased cooling capacity. However, the power input to the compressor increases, because the inlet air to the compressor is heated as it passes through the other side of the recuperator. With a recuperator, the maximum COP is obtained at lower pressure ratio across the compressor, and the COP can be 10% to 20% higher than in the simple open cycle of Figure 7-1.

Figure 7-2: Reverse Brayton Cycle with Recuperator

In a closed cycle, as shown in Figure 7-3, cooling is delivered to the conditioned space via a heat exchanger, instead of direct discharge of cold working fluid from the expander into the conditioned space. This allows a wider choice of working fluids, higher pressure levels, and therefore, nominally higher cooling power density of the equipment, but necessitates the addition of the cooling load heat exchanger. The COP is subject to the same factors that drives the COP of open cycles. The low volume flow rate allows, and probably necessitates, the use of a lubricated, positive displacement compressor and expander operating at much lower speeds than turbomachinery. Obtaining a net savings in weight or a gain in COP over a turbomachinery based open cycle is problematical at best. The following material is focused on open cycle configurations, because the advantages of the open cycle configuration enumerated above significantly outweigh the potential advantages of closed cycle configurations, and will result in lighter weight, lower cost, and, probably, higher efficiency systems.

There is currently no commercial use of Brayton cycle cooling equipment in automobile or truck cooling applications. There is, however, considerable experience with open cycle equipment for other applications and as developed as part of experimental programs to assess the potential for this technology. This includes:

Figure 7-3: Closed Reverse Brayton Cycle with Recuperator

- The use of open Brayton cycle cooling equipment is commonplace for aircraft climate control based on the use of high speed turbines to minimize weight and size. Engine bleed air is generally used to supply some or all of the compressed air for the cycle.
- The development of prototype open cycle cooling systems for field military applications (mobile hospitals, etc.) One of these programs was based on the use of scroll expanders/compressors as developed at Arthur D. Little.
- Several prototype developments based on the use of various forms of vane equipment, for example, the systems developed by ROVAC for automotive and other applications.

While these developments have verified the relative simplicity of several configurations of open cycle cooling equipment, virtually all commercially successful applications of reverse Brayton cycle cooling are characterized by large premiums on weight and volume reduction and the availability of bleed air from a gas turbine or jet engine. Electrically powered (as opposed to bleed air powered) cooling equipment in aircraft is generally vapor compression cycle based, verifying the difficulty in attaining high efficiency levels with reverse Brayton air cycle conditioning/refrigeration applications (including vehicle conditioning).

When fully developed, a simple open air cycle cooling system could be expected to be somewhat lighter than a comparable vapor cycle system. To a first order, the weight of the turbo compressor-expander-motor package and the heat rejection heat exchanger can be expected to be comparable to that of a vapor cycle motor - compressor and condenser. The simple air cycle system weight is largely accounted for by these components, while the vapor cycle includes an evaporator assembly whose total vehicle weight penalty approaches 10 pounds.

The transient cooling response of air cycle equipment is nearly instantaneous, so that cold air would be delivered to the vehicle air conditioning supply louvers within seconds of start-up, so that comfort conditions, at least for the front seat passengers, are reached quickly.

The main development issues to be considered in evaluating an electric vehicle reverse Brayton cycle cooling system are:

- The prospects of obtaining an acceptable COP, given currently available and prospective component efficiencies; and
- The high speed motor required to drive the turbo compressor/expander.

Reverse Brayton cycle performance is very sensitive to compressor and expander isentropic efficiencies. To achieve a design condition COP (electric power input basis) on the order of 2, the general level of high efficiency electric vehicle vapor compression air conditioning equipment, requires turbomachinery efficiency in excess of 90%, and heat rejection heat exchanger effectiveness on the order of 90%. This level of turbomachinery efficiency is significantly in excess of current efficiency levels of 80% for turbomachinery in this size range, which are the result of many years of research and development, driven by the automobile and truck turbo-supercharger markets, where ample incentives exist for improved efficiency, as well as aircraft requirements. If 80% efficient turbomachinery were used with a 90% effective heat exchanger, the resulting system would have a shaft COP less than .7 (electric input basis COP of less than .6), more than tripling the power requirement to produce a given cooling capacity.

To develop a package size compatible with current electric vehicle constraints, to maximize the use of existing high performance turbocharger technology, and to obtain maximum efficiency requires the turbo expander and compressor to operate at high speed, approaching 100,000 RPM. Brushless DC or inverter driven AC motors capable of operating at these speeds and delivering shaft power outputs of several horsepower are representative of advanced motor technology that is used primarily in advanced aerospace applications.

A variety of configuration alternatives, modifications, and enhancements to the simple cycle, either proposed or already used in practice have been presented in the technical literature. While a thorough treatment is beyond the scope of this project, several are addressed in the subsections that follow:

- Basic dry air cycle
- Enhancement of performance over dry air by moisture removal (dehumidification);
- Recuperator;
- Dehumidification recuperator; and
- Membrane water removal.

For each of these variants, potential efficiency (electric power input basis COP) is estimated, for transient and steady state operation and versus ambient temperature.

7.1.1 Simple Brayton Cooling Cycle

Two sets of results will be discussed for the simple Brayton cooling cycle shown in Figure 7-1; dry air and moist air. Dry air results rely on simple ideal cycle calculations to generate predicted cycle COP and compressor power consumption levels. The moist air results take into account the condensation of water vapor from the process air that may occur in the expander. The net result is to slightly increase the expansion work, increasing the cooling capacity while decreasing the input power required, providing a net increase in the COP.

7.1.1.1 Dry Air Results. The dry air results were calculated on the basis of the following assumptions:

- 75% isentropic compressor efficiency
- 85% isentropic expander efficiency
- 90% heat exchanger efficiency (the cooling air flow rate is 2 to 3 times the process air flow rate to increase the effectiveness of the heat exchanger)
- 1.5% pressure drop on process air side of heat rejection heat exchanger
- Low side pressure drops neglected
- 80% motor efficiency
- The pressure ratio (2.2) was optimized to provide maximum COP at the Phoenix climatic condition, 109°F ambient temperature
- 45 CFM of ventilation make up air, total process air flow rate of 150 CFM (105 CFM recirculated from the vehicle interior)
- Steady state operation

The COP based on electric power input to the turbomachinery drive motor is plotted versus ambient temperature in Figure 7-4. The maximum COP is 0.67 at an ambient temperature of 80°F. Advanced vapor compression cooling systems for electric vehicles can achieve a COP (based on electric input power to the compressor) greater than 2.5 for this condition. The simple Brayton cooling cycle will require more than 3.7 times the power for the same cooling load. At high ambients, like the Phoenix climatic condition, the simple cycle requires over three times the input power (electric input power to the compressor) relative to high efficiency vapor compression systems.

Figure 7-4: Open Reverse Brayton Cooling Cycle Performance

7.1.1.2 Moist Air Results. The dry air analysis is an oversimplification, in that dehumidification accounts for a major portion of both building and mobile air conditioning loads. Reference 17 asserts that the effect of the moisture removal process -- condensation during the expansion process -- is a significant increase in cooling capacity and COP. To estimate the actual increase in capacity and COP, an example case with high inlet humidity was defined, and the incremental effect on the expansion work, cooling capacity, and COP was estimated. The parameters assumed were:

- Pressure ratio of 1.75 across the expander;
- Expander efficiency of 85%; and
- Inlet condition to expansion process: 100°F, 1.75 atm, saturated with water vapor, humidity ratio of .025.

First, the effect of the latent heat on the outlet temperature (higher) and outlet volume (larger) were estimated based on the sum of the latent and sensible energy decrease in the air equalling 110% of the dry air basis expansion work. The resulting outlet volume (accounting for increased outlet temperature and reduction in volume due to removed moisture) was plotted on the PV diagram of Figure 7-5. The percentage increase was calculated graphically based on the increased area of the PV diagram, approximately 3%. The overall effect of the 3% increase in expansion work is approximately a 5% increase in cooling capacity and a 3% decrease in net work, an 8% increase in the COP overall. An increase on this order, say 10%, is about the upper limit of this effect, because the example was based on conditions of extreme inlet humidity - corresponding to operating in full vent mode in the highest ambient humidity conditions encountered in the U.S. Gulf Coast states.

Figure 7-5: PV Diagram for Expansion Process with Moisture Condensation

A practical problem associated with this mode of moisture removal is that the condensation occurs as the air expands, in the form of fog, i.e., entrained fine water droplets which are not readily separated from the air stream.

7.1.2 Open Reverse Brayton Cycle With Recuperator

The results for the Brayton cooling cycle with a recuperator are shown in Figure 7-4, COP (compressor motor electric power input basis) versus ambient temperature. The assumptions used for the calculations were the same as those listed in the previous section and the recuperator was assumed to be 67% effective with a 1.5% pressure drop. The heat exchanger effectiveness is lower than the cooling air heat exchanger because of the balanced flow condition (same mass flow on both sides of the heat exchanger), and the limited size (heat transfer area) for placement inside the vehicle. The pressure ratio, 1.8, was optimized to achieve a maximum COP for the Phoenix climatic condition. The COP increased relative to the simple cycle by 5% at the lower ambient temperatures and by 10% at the high ambient temperatures, the Phoenix climatic condition. Even with these modest increases the power consumption (compressor electric input) is more than 3 times as much as with vapor compression at low ambients and more than 2 times the input power at high ambients.

7.1.3 Open Reverse Brayton Cycle With Moisture Removal Heat Exchanger

One method to improve humidity control with air cycle equipment is to incorporate a heat exchanger that precools the expander inlet air with expander outlet air, as shown in Figure 7-6. The temperature decrease at the expander inlet air stream causes moisture to condense, similar to the condensation process that occurs on the evaporator in a vapor compression system. The condensed moisture is easily separated and discharged from the process air, and higher levels of moisture removal are readily attained than in a simple cycle. However, this technique penalizes the thermodynamic performance. The lower expander inlet temperature decreases the expansion work, reducing the total cooling capacity while increasing the work from the electric drive motor that is required to power the compressor, decreasing the COP relative to the base cycle, either the simple cycle or the recuperator cycle.

7.1.4 Membrane Water Removal

A membrane heat exchanger is another method that has been proposed for the removal of water vapor from the Brayton cycle air stream before the expander inlet. The system schematic is shown in Figure 7-7. The membrane is constructed so that water molecules can penetrate the mesh, but the larger oxygen and nitrogen molecules cannot. The water vapor will continue to penetrate the membrane as long as the vapor pressure is higher on the process air side than on the cooling air stream side. The cooling air removes the water vapor transferred through the membrane. The potential advantage of this arrangement is that the rejection of the latent heat associated with the water vapor removed adds directly to the total cooling capacity and COP of the system.

To develop an estimate of the maximum efficiency improvement obtainable with a membrane moisture exchanger, the amount of moisture removed via a membrane moisture exchanger was estimated for a maximum humidity ambient condition. To find an upper limit for the performance improvement, the mass transfer effectiveness was assumed to be 100%, i.e., the exit water vapor partial pressure is equal to the water vapor partial pressure of the ambient cooling air. The pressure drop through the exchanger was neglected, and it was assumed that no air (other than water vapor) passes through the membrane. The worse case humidity load on a vehicle air conditioning system occurs in a climatic condition similar to Houston, having a design ambient of 97°F and 48% RH, with a vapor pressure of 0.42 psia, also taken as the water vapor pressure at the expander inlet. At a compression ratio of 1.9, cooling load of 8490 Btu/hr, a 97°F/48% RH ambient condition, and 80% recirculated interior air/20% ambient make up air at the cycle inlet, approximately 0.9 lb/hr of water vapor will be removed, increasing the cooling capacity by 900 Btu/hr or somewhat more than 10%. To realize this small potential increase in cycle efficiency requires the addition of the membrane heat exchanger. Assuming a material is available that freely passes moisture while being impervious to the oxygen, nitrogen, and argon that make up 99.9% of dry air, a practical exchanger having finite size and cost would have neither 100% mass transfer effectiveness nor zero pressure drop. Together these losses would largely negate the potential performance gain.

Figure 7-6: Reverse Brayton Cooling Cycle with Moisture Removal Heat Exchanger

Figure 7-7: Reverse Brayton Cycle With Membrane Moisture Exchanger

7.1.5 Reversed Heat Pump Cycle Operation

Figure 7-8 shows schematically the basic configuration of a reverse Brayton cycle heat pump that can be switched between heating and cooling mode. The cycle equipment has a fixed air flow pattern because the high temperature side of the system is compressed air, and the heat of compression must be transferred through a heat exchanger. Switching between cooling and heating mode is effected by switching the

ambient air and interior air streams between the high and low temperature sides of the cycle. Compared to the relatively simple and compact reversing valve used to switch a vapor cycle between heating and cooling mode, this arrangement of ducting and mode dampers will have a significant volume penalty.

Figure 7-8: Heating/cooling Mode Reversing for Reverse Brayton Cycle Heat Pump (Mode Dampers in Heating Mode)

An advantage of this arrangement is that the low side heat input is the open part of the cycle, so there is no need to defrost an ambient air heat exchanger. The expander and ductwork must be configured so that any frozen fog that condenses during the expansion process is readily exhausted, so that little or no ice builds up in the ductwork.

Figure 7-9 plots heating mode COP and capacity vs. ambient temperature for a simple reverse Brayton cycle as shown in Figure 7-8, with component performance as discussed in 7.1.1, and for a recuperator cycle as shown in Figure 7-2, with component performance as discussed in 7.1.2. While the overall COP levels are low, they do not decrease as rapidly nor does the capacity decrease as rapidly as with fixed speed vapor cycle equipment.

Figure 7-9: Reverse Brayton Heating Cycle Performance Ambient Temperature versus Electric Motor Input COP Ambient Temperature versus Heating Capacity

7.2 Reverse Stirling Cooling Cycle Systems

Figure 7-10 illustrates the ideal Stirling cooling system cycle. In a Stirling cycle system a working gas, usually helium, is alternately compressed and expanded. During the compression process heat is rejected at the peak cycle temperature (roughly corresponding to the condenser of the vapor compression cycle) and during the expansion process heat is extracted from the surroundings at the minimum cycle temperature (corresponding to the evaporator of the vapor compression cycle). Since the compression process is at the higher temperature and the expansion at the lower temperature, work must be added to the cycle. This is in contrast to the Stirling cycle engine, where expansion takes place at an elevated temperature and compression at low temperature, such that work is produced.

The kinematics of the ideal cycle can be described in step by step fashion with reference to Figure 7-10. Note that the compression and expansion spaces are at equal pressures (except for pressure losses through the regenerator) throughout the cycle. The pressure level varies with the internal volume during the cycle, as set by the piston positions, and with the distribution of working fluid between the compression and expansion spaces. The process steps are:

Figure 7-10: Ideal Stirling Heat Pump Cycle (Source: Reference 32)

- (1-2) Compression (isothermal in the ideal cycle) of the working gas and heat rejection. Compression work must be supplied in this step.
- (2-3) Displacement of the working gas to the expansion space, via the regenerator, with the gas exiting at the cold side temperature. No net work is involved in this step.
- (3-4) Expansion (isothermal in the ideal cycle) of the working gas, with heat transferred into the working gas from the cooling load. Work is recovered during this step.
- (4-1) Displacement of the working gas back to the compression space, via the regenerator, reheating the gas to the compression temperature while cooling the regeneration matrix.

Stirling cycle cooling equipment is currently used primarily in low temperature cryogenic applications (such as cooling of certain types of sensors) at temperatures below 80°K (approximately liquid nitrogen) where no working fluids or lubricants exist for operation of small capacity vapor compression equipment.

As indicated subsequently there is little doubt that Stirling cycle equipment would be more costly and of lower efficiency than vapor compression technology in most applications. However, it has a major advantage of using a gas such as helium, hydrogen, or nitrogen as a working fluid and, thereby, eliminating the environmental issues associated with CFCs and many of their alternatives.

There is relatively little analytical or operating experience with Stirling cycle equipment in the temperature ranges associated with most air conditioning and refrigeration applications, including mobile air conditioning. Sunpower Corporation developed an experimental Stirling air conditioning system as part of a Duplex Stirling engine heat pump program for the GRI. Limited testing with this system indicated the potential to achieve COP levels approximately 50% of Carnot (based on working fluid temperatures) which approaches that achievable with vapor compression equipment. Through license agreements the Sunpower technology was transferred to Kawasaki in Japan where experimental units again demonstrated respectable efficiency potential. In both cases the Stirling cooling cycle equipment was fabricated using readily available heat exchangers resulting in relatively bulky equipment.

The analyses of Stirling cycle systems is complicated by the oscillating nature of the fluid flow within the heat exchangers and the lack of fundamental data on the associated heat transfer and pressure drop phenomena. Most efforts to develop analytical models have been directed toward Stirling engine applications rather than cooling cycles. Due to the above mentioned complications in the modeling process, the models are essentially calibrated against actual operating experience and their accuracy is, therefore, generally limited to a narrow range of equipment. Oak Ridge National Laboratory used one of the computer based models to project the performance of a Stirling engine run in reverse i.e. in the cooling mode. These projections also indicated the potential for such equipment to have COPs approaching 40-50% of Carnot with properly designed heat exchangers. To date, there has not been an opportunity to verify the model results against operating experience.

7.2.1 Performance Characteristics

This subsection compares the performance potential of Stirling cooling technology with that of vapor compression technology relative to such key parameters as:

- Efficiency (both design conditions and seasonal);
- Capacity characteristics;
- Size;
- Reliability and life; and
- Cost.

The example used to display the performance characteristics is that of a residential air conditioning system. The general results are, however, relevant to a wide range of air conditioning/refrigeration applications.

Efficiency. As indicated above both analyses and limited experimental results suggest that properly designed Stirling cooling systems might achieve COP levels 40-50% of Carnot (electric input to the Stirling machine, parasitics not included) at typical design conditions for air conditioning and heat pump applications. This is as compared to about 50% for vapor compression systems (electric input to compressor only). The requirements for achieving high efficiency levels in Stirling equipment include very effective regenerator matrices (92% effectiveness) and large areas of highly effective and low pressure drop heat exchangers for addition and rejection of heat from the cycle. In addition, "dead" volume within the equipment must be minimized. This includes all internal volume within the cycle that is not involved in the compression or expansion displacement volume, primarily heat exchanger, recuperator, and connecting passage internal volume, and piston to cylinder head clearance volumes. There is inherently some tradeoff between maximizing heat exchanger performance while minimizing the dead volume. One conceptual design for a Stirling heat pump unit is shown on Figure 7-11. As indicated it includes very fine meshed heat exchangers to achieve the required heat exchanger areas combined with low pressure drops and low internal volume. The impact of heat exchangers on system cost will be a major issue impacting on the potential of this option.

Estimates of the cooling and heating COP levels that might be attained with well designed Stirling cycle equipment were developed, based on the following set of assumptions.

- Based on the earlier work of Kawasaki, a Stirling heat pump COP of 50% of Carnot can be achieved in the heating mode at a 47°F ambient (Carnot COP based helium working space temperatures).
- As shown in Figure 7-12, a small increase in percent of Carnot was credited to the Stirling heat pump when operated at greater temperature lifts, i.e., at lower ambient temperatures. The increase in efficiency (relative to Carnot) of the Stirling cycle heat pump is projected by N. Domingo, et al (ORNL Report No. CON-149, March 1984, Reference 32), and is also consistent with analyses of other gas-based cycles.

Figure 7-11: Kinematic Stirling Cycle Cooling Module Design Concept

- A small decrease in the percent of Carnot efficiency was applied to the Stirling heat when operated at lower lifts.
- The Stirling and vapor cycle use heat exchangers which result in the same air side approach temperatures to the working fluid (Freon or intermediate fluid for the Stirling package).
- The Stirling unit was penalized an additional $\Delta T = 6F$ in each space to account for the heat transfer between the helium and the intermediate liquid loop.
- For the Stirling package, the motor losses (85% efficiency assumed) were considered external to the helium loop but considered in the performance calculations.
- Parasitics are not included in the analysis.

Table 7-1 summarizes the resulting COP for several conditions.

Figure 7-12: Impact of Temperature Lift on Stirling Heat Pump COP

Table 7-1: Estimated COP and Capacities of Stirling Cycle Heat Pump for EV Space Conditioning

Rating Point	System Performance	Stirling
Cooling 90°F Ambient	COP (system) Capacity (Btu/hr)	2.5 18,000
Heating 47°F Ambient	COP (system) Capacity (Btu/hr)	2.6 18,000
Heating 17°F Ambient	COP (system) Capacity (Btu/hr)	2.5 16,000

The COPs are generally somewhat lower than the vapor cycle COPs at comparable conditions, but the capacity is much less sensitive to the overall lift, a potentially significant advantage.

Capacity Characteristics (heat pump applications only). With vapor compression heat pumps the thermal output decreases as the ambient air temperature decreases. As indicated on Figure 7-13, however, the thermal load increases so that at low outside temperatures some form of supplemental heat must be used, usually electric resistance heating. The capacity of Stirling cycle heat pumps would be virtually unaffected by

variations in outside temperature since the working gas pressures are not very sensitive to temperature levels over the relatively narrow temperature ranges involved. As a result Stirling heat pumps would maintain both capacity and efficiency as outside temperatures decrease eliminating the need for supplemental heat in most locations. While periodic defrosting would be required, the performance would be more tolerant of frost build up than in a vapor cycle, due to the relative insensitivity of the performance to the lift. Therefore, despite somewhat lower design point efficiencies than vapor compression technology, on a seasonal basis Stirling cycle equipment might have comparable or even higher efficiency-particularly in northern areas.

Figure 7-13: Stirling Cycle Heat Pump Heating Capacity versus Ambient Temperature

System Configuration/Size. Figure 7-11 shows schematically a design for a Stirling heat pump system for use in electric vehicles. Two water-glycol circulation loops are used to provide a means of thermally coupling the Stirling heat pump to the interior and ambient air coils. This is required since the compact low internal volume heat exchangers of the Stirling system necessitated by efficiency considerations require liquid thermal interchange (i.e. cannot be air coupled). In the complete system, the Stirling machine is analogous to the motor/compressor of the vapor cycle, and is likely to weigh more than the motor compressor. Detailed modeling and design studies,

beyond the scope of the present effort, are needed to quantify the difference. The remainder of the Stirling system - ambient air heat exchanger, interior air heat exchanger, and liquid loops would be close to the same size, weight, and configuration as the vapor cycle condenser, evaporator, and refrigerant lines.

Life/Reliability. Vapor compression equipment generally has excellent reliability and life characteristics as the result of being closed cycle and having good lubrication for bearings and seals. For automobile air conditioning applications, component design life is generally 2,000 operating hours. The primary design features of Stirling cycle cooling systems impacting on life/reliability are the bearings and seals in the unlubricated working space and, in the case of kinematic equipment, the shaft seals separating the high pressure working gas from the crankcase. Due to the lack of work on Stirling equipment for the class of applications under consideration there is no directly relevant experience on which to make life/reliability projections. However, there is related analyses and durability testing on Stirling engines which provides highly relevant insights on this issue.

- In recent years kinematic Stirling engines have up to 10,000 hours without the need for maintenance reflecting major progress in the design of rod seals and unlubricated piston rings;
- Free piston Stirling engines using gas bearings have also operated; and
- Analyses at Arthur D. Little indicates that a combination of properly designed internal seals combined with appropriate system operating parameters should allow operation of internal unlubricated seals for periods in excess of 10,000-20,000 hours, well above the 2,000 hr design life typical of automobile air conditioning equipment.

The above results are for Stirling engines where the temperature regimes and loadings on the seals and bearings are likely to be higher than in Stirling cooling systems. As such, there is a good chance that in properly designed equipment acceptable life and reliability characteristics could be obtained.

7.2.2 Stirling Cycle Heating Mode Operation

Figure 7-14 shows schematically a means of reversing from heating mode to cooling mode (using a simplified diagram of a linear free piston Stirling cycle cooler to illustrate the arrangement - the same interconnections to hot and cold side liquid heat transport loops would apply to the arrangements shown in Figures 7-10 and 7-11). The Stirling machinery has an inherently hot and cold side (not reversible), so the mode is changed by switching the connection of the ambient and interior liquid loops.

Steady state heating performance was discussed briefly above; the ambient air coil would require defrosting to about the same extent as other cycle alternatives.

Figure 7-14: Heating/Cooling Mode Reversing for Liquid Loop Coupled Reverse Stirling Cycle Heat Pump (mode valves in cooling mode)

7.2.3 Capacity Variation

The system illustrated schematically in Figure 7-11 is volumetric, so that to a first order the heat pumping capacity will vary linearly with speed. Variable speed operation of the Stirling unit, the liquid loop pumps, and the interior air handler would, therefore, provide performance improvements, similar to the variable speed performance improvements for vapor cycle systems, due to the elimination of cycling losses and reduction of parasitics.

7.3 Magnetic Refrigeration Cycles

When a strong magnetic field is applied to certain paramagnetic materials at cryogenic temperatures and to ferromagnetic materials at temperatures close to their Curie point, a decrease in entropy (related to an increase in the ordering in the electron spin state) occurs. A decrease in internal energy is associated with the decreased entropy and results in heat being released to the bulk of the material. If this process occurs adiabatically, the temperature of the material will increase; for the change to occur isothermally, heat must be rejected to the surroundings, say a fluid stream to be heated intentionally or a coolant. Within the range of magnetic field strengths that can be produced in the laboratory (on the order of 10 Tesla, or 100,000 Gauss, using superconducting magnets), the adiabatic temperature change is proportional to the strength of the magnetic field. Thermodynamically the process is reversible in that removal of the strong magnetic field will result in almost the complete reversal of the temperature rise, and in the almost complete recovery of the work that was required initially to apply the magnetic field, with only very small internal losses, at least for low cycle rates. The thermodynamic reversibility of the phenomena, with the inherent possibility of obtaining high cycle efficiencies, has led to interest in the development of room temperature heat pump cycles, spanning the heat load and heat sink temperature ranges characteristic of conventional refrigeration applications and building and mobile space conditioning applications.

The earliest experimental work with this phenomena was at liquid helium temperatures. The magnetic refrigeration effect was used to achieve a closer approach to absolute zero temperature than could be achieved with a liquid helium based cooling cycle alone. Ferromagnetic materials have been discovered that undergo the type of state change described above near room temperature. Metallic gadolinium (Gd, atomic number 64, one of the rare earths), and intermetallic compounds containing Gd are the best materials that have been identified for room temperature range cooling applications. Figure 7-15 plots the adiabatic temperature rise of Gd versus initial temperature and applied magnetic field. The maximum temperature rise occurs at the Curie temperature of 293K (68°F). At 7 Tesla and 68°F, the adiabatic temperature rise is 14°K (25°F).

Figure 7-15: Adiabatic Temperature Change versus Temperature for Various Applied Fields in Polycrystalline Gadolinium
(Source: Reference 21)

The basic closed cycle refrigeration process is as shown in Figure 7-16. In Step (a) the magnetic field is applied to the magnetic working material, which has finished absorbing heat from the cooling load. When the field is applied, internal energy released from the changed state raises the temperature of the material above the heat sink temperature. In Step (b), heat is rejected to the heat sink, cooling the material to the heat sink temperature. In Step (c), the magnetic field is removed, and the temperature of the material is reduced to below the cooling load temperature. Heat is absorbed from the cooling load in Step (d), after which the cycle is repeated. A Carnot cycle can be carried out, in principle (practicalities aside), by modifying this process so that the adiabatic temperature changes of Steps (a) and (c) are limited to that necessary to reach the temperature of the reservoir in Steps (b) and (d), respectively. Steps (b)

and (d) are then carried out isothermally, while continuing to increase or decrease, respectively, the applied field. A difficulty for practical cooling applications is that the adiabatic temperature rise, even with intense magnetic fields, is not very large, so the largest temperature lift of a Carnot type cycle with net cooling capacity is only 10 to 15°F. Recognizing this limitation, several researchers have developed regenerative, Stirling/Ericsson cycle analogue, thermomagnetic heat pumping cycles. The basic cycle is shown in Figure 7-17. An example of a magnetic Ericsson cycle conceptual design is shown in Figure 7-18. The key features of the experimental systems were:

Figure 7-16: Basic Non-Regenerative Magnetic Heat Pumping Cycle

- Providing for regenerative heat transfer between working material being transferred from the cold sink to the hot with working material being transferred from the hot sink to the cold, leaving the majority of the heat of the thermal magnetic effect available for cooling and heat rejection,
- Providing close fluid coupling to the working material, and configuring the working material so that at least one dimension is small enough (e.g. thin plates, small diameter wire, or spheres) so that the internal conduction heat transfer resistance of the working material is reasonably low.

Figure 7-17: Basic Regenerative Magnetic Heat Pumping Cycle

Figure 7-18: Rotary Magnetic Heat Pump Operating on an Ericsson Cycle
(Source: Reference 29)

Experimental systems reported in the literature include a linear, Stirling-like, device (Reference 20) where liquid in the cylinder acted as the heat storage/regeneration medium, and concentric, thin sheets of Gd, with gaps between formed a piston which was reciprocated in the cylinder, with the applied magnetic field cycled appropriately. With a 7T field, a no heat load temperature span of 47C was achieved. In a second approach, (Reference 22), a rotating Gd wheel was configured with appropriately located zones of applied field and heat transfer with a liquid loop. The fluid in the loop served as the heat transfer medium for both the regenerative heat transfer and the cooling load and heat rejection. The measured performance of the prototype system was 1/2 kW (1,700 Btu/hr) of continuous cooling across a 7K lift (near room temperature), at a COP of 26% of Carnot.

A number of factors severely limit the practical applicability (and potential competitiveness with vapor cycle) of the magnetic cooling cycle for practical air conditioning:

- A very strong magnetic field is required to produce a significant refrigeration effect, typically 5 Tesla or more, which far exceeds the magnetic field strength of any known permanent magnet materials. In fact, the strongest permanent magnet field strength reported in the magnetic refrigerating literature was 1.2 Tesla. Field strengths on the order of 5 to 10 Tesla are more typically associated with superconducting electromagnets.
- A very high regeneration effectiveness, with low parasitic power consumption and with temperature gradients maintained reversibly in an intermediate heat transfer fluid, is required to be able to even approach the lifts and COP level (as a fraction of the Carnot COP) that is typical of vapor compression cycle equipment. To put the regenerative heat transfer requirement in perspective, a heat transfer rate approximately 10 times the net cooling capacity, driven by 1/2 of the temperature difference usually employed in economically sized, water cooled vapor compression cycle equipment is required to obtain performance comparable to the vapor compression cycle (with a 7 T field). At lower field strengths, even higher regenerator performance levels are needed.

In short, significant fundamental development remains to be done to produce a device capable of approaching the performance routinely obtained with the much simpler vapor compression cycle. Without dramatic breakthroughs in high temperature superconductor technology or thermomagnetic materials, the requirement for a large regenerator capacity and the extremely high magnetic fields that are only available with cryogenically cooled, superconducting magnets together constitute an essentially insurmountable obstacle to the development of a low cost, compact thermomagnetic air conditioning system that would be suitable for vehicle air conditioning applications.

8.0 Conclusions and Recommendations

8.1 Thermal Loads

8.1.1 Conclusions

A simple model of vehicle space conditioning loads was developed for predicting electric vehicle heating and cooling loads. Although the model has not been validated, cooling loads calculated by the model agree with electric vehicle air conditioning system wind tunnel test data, within about 15%. The thermal model has been implemented in an easily used Fortran computer program. The model is an effective method to analyze thermal design changes to minimize heating and cooling loads. The model can also be used in conjunction with air conditioning and heating equipment models to predict traction battery power consumption under different types of operating conditions. Once power consumption values have been determined, an estimate for the electric vehicle range penalty of the heating and cooling equipment can be determined.

Several thermal design options were evaluated, including low transmissivity window glazings, insulation, restriction of fresh ventilation make up air flow rates, and a ventilation fan during a hot soak. The combination of an advanced glazing (wavelength selective glass such as PPG Sungate), restriction of fresh air and body insulation (especially the roof) will reduce the design cooling load by 64%. Limiting ventilation make up air flow rates to the minimum levels needed to maintain acceptable interior air quality, provides the largest cooling or heating load reduction. The availability of the PPG Sungate glazings in current production and prototype vehicles makes this type of glass and similar glazings which are in the advanced stages of commercial product development an excellent choice for installation in future electric vehicles. Incorporating insulation in body panels and reducing ventilation air are simple design changes, however, they do not comply with current automotive practice.

Ventilation during hot soak is an effective method for reducing hot soak temperatures and transient cooling loads. To provide the approximately 100 CFM ventilation air flow rate needed, a separate vent fan may be utilized or the interior air blower can be operated at 4 to 5 volts to the motor. With a reasonably efficient DC/DC converter, power consumption from the traction battery will be approximately 20 watts. Photovoltaic powered vent fans are available in the aftermarket at installed costs on the order of \$500.

The application of available thermal design options will reduce thermal loads on electric vehicles during the heating and cooling seasons. Use of this technology will reduce the power consumption of cooling equipment reducing associated range penalties. Decreased heating loads increase the possibility of using reversed cycles for heating allowing the elimination of the weight and cost of a separate fuel fired heating system.

A set of baseline design heating and cooling loads was developed for use in Task 2, assuming that commercially available load reduction measures were used. These loads are indicative of both the absolute magnitude of heating and cooling loads in electric vehicles with effective thermal designs and the comparative level of cooling vs. heating loads in various climatic regions.

8.1.2 Recommendations

Future designs of electric vehicles should consider the tradeoffs between the cost and weight of effective thermal load reduction design measures and the cost, weight, and power savings that can be realized from reducing the heating and cooling loads.

The use of several of the specific thermal design features that were evaluated in Task 1 should be considered for use in future EV's whose design specifications call for interior heating and/or air conditioning, either as standard or optional equipment. They are wavelength selective glazings, roof insulation, and provision of low powered ventilation to limit hot soak temperatures.

8.2 Evaluation of Cooling and Heating Cycles

8.2.1 Conclusions

The results of the study clearly show that in both the near term and the longer term, vapor cycle based cooling equipment will provide the highest efficiency and lowest cost means of meeting vehicle cooling loads, with a system weight comparable to, or significantly less than alternative cycles.

Prototype vapor cycle air conditioning systems for electric vehicles using an efficient variable speed compressor have been developed and tested, with considerable performance improvement over constant speed systems having been demonstrated. Further improvement in efficiency can be realized, for example:

- The seasonal cooling efficiency of vapor cycle can be increased significantly with a variable speed compressor and a variable speed (via PWM or equivalent, not series resistance) interior air blower.
- With the vapor cycle evaporator packaged into the traditional, behind the dash board interior HVAC air handler, a significant portion of the input power over the cooling season is consumed by the interior air blower. Space limitations in this location result in limited air duct and heat exchanger flow cross sectional area, limiting air flow rates and requiring a low air delivery temperature and evaporator temperature. If the interior cooling subsystem were repackaged to reduce air flow restrictions (e.g., the ceiling fan-coil described in Section 6.3), considerable savings in both fan power and compressor power could be obtained.

In electric vehicles having reasonably "tight" thermal designs, heating using a combination of vehicle waste heat and a heat pump cycle heating is both feasible and attractive in both the climatic areas having milder winters (e.g. Phoenix, Los Angeles, Gulf Coast) and for much of middle portions of the country. Back-up electric resistance heating requirements will be minimal and range penalties are modest.

A number of alternative cycles were evaluated in this study: reverse Brayton, reverse Stirling, and magnetic refrigeration. As noted above, the vapor compression cycle, even when subject to CFC issue driven restrictions in the selection of working fluid, provides

a balance of high efficiency, low cost, and light weight that is superior to current alternatives and is very likely to remain superior in the longer term, despite possible developments in alternate cooling cycles.

Even under optimistic assumptions regarding component efficiencies, heat exchanger effectiveness, and pressure drops, the various arrangements of reverse Brayton cycle systems will have an exceedingly low COP (less than 1/3 of the COP of a vapor cycle operating under comparable conditions. The resulting level of energy consumption is far too great to be adequately offset by its few potential advantages (marginally lighter weight, marginally quicker response on start up).

Magnetic refrigeration, which has been demonstrated at the laboratory benchtop level in the room temperature range, is not a promising technology for vehicle air conditioning. Very high magnetic fields, typical of superconducting electromagnets, are required to produce any significant cooling effect, and a highly effective solid to solid regenerator is required to span the normal temperature lifts encountered in automobile air conditioning systems, both factors being associated with high weight and cost.

Considerable effort has been expended on Stirling cycle prime movers and on Stirling cycle cooling equipment for cryogenic applications. To date, very little development effort has been focused on Stirling cycle equipment for the normal range of air conditioning and refrigeration applications. The system design concept presented in Section 7.2 is configured to minimize the system weight and maximize the efficiency. Based on preliminary estimates, a variable speed motor driven system of this design would probably be higher in weight, lower in cooling efficiency, and higher in cost than a vapor cycle counterpart. However, the heating performance is potentially superior to vapor cycle and all other alternatives, because a higher proportion of design capacity and COP is obtained at low ambient temperatures. A further advantage is that the Stirling cycle is inherently a non CFC cycle, most commonly using Helium as the working fluid. Given these potential advantages, a design and performance modeling study that would provide a basis for more precise performance, weight, and cost estimates may be justified.

8.2.2 Recommendations

Based on the preceding results and conclusions, the following recommendations address areas where additional development efforts are likely to result in significant improvements in electric vehicle space conditioning systems.

8.2.2.1 Development of Heat Pumps for Electric Vehicles. A significant finding of this study is that adequate electric vehicle heating can be provided by a combination of waste heat recovery from the controller and the motor/transmission, a vapor cycle heat pump, and limited amounts of electric resistance heat. Given the impetus provided by local air quality considerations to develop zero emission vehicles, the development of a prototype EV heating system along these lines would be a timely undertaking, that would demonstrate the feasibility of this concept and provide a means of addressing

basic engineering issues such as ambient air coil defrosting and interior humidity management/window defogging with limited ventilation make up air flow rates. The basic tasks in this program would be:

- Preliminary System Design and Test Plan;
- Detailed System Design - starting with the Preliminary Design, the detailed design of the system would be completed, specifying:
 - refrigerant tubing and hose runs and connecting fittings
 - electrical design including motor controls and system controls and integration with the vehicle electrical system
 - component mounting, including provisions for vibration isolation of the motor-compressor assembly
- System Fabrication and Installation
- Performance Testing
 - wind tunnel
 - track

8.2.2.2 Vapor Cycle Improvements for Electric Vehicle Space Conditioning. The application of high efficiency variable speed compressors, variable cool air delivery temperature, and high performance condensers, has resulted in significant improvements in EV air conditioning efficiency. Because the evaporator and interior air handling system is very closely integrated with the vehicle body and dashboard, EV air conditioners have generally utilized standard factory configurations of these components. Further improvement in performance can be obtained by modifying the evaporator and interior air handler design to allow higher air flow rates, while reducing air velocities. The result would be a higher evaporator temperature and a decrease in both fan power and compressor power, significantly increasing the COP. The ceiling evaporator/blower concept illustrated in Figures 6-9 and 6-10 is one configuration allowing for the air flow frontal area and blower matching required. Other locations where comparable results might be obtained include the under seat area or a portion of the trunk space. Given the potential efficiency improvement (over 50% on a seasonal basis), an initial design study to define a number of evaporator interior air distribution design alternatives, and to develop performance estimates, considering vehicle heating as well as cooling should be initiated.

8.2.2.3 Design Study of Stirling Cycle Heat Pump for EV Space Conditioning. As noted above, the Stirling Cycle has some potential to be an effective heat pump cycle for EV cooling and heating, because the heating capacity decreases only very gradually with decreasing ambient temperature, and the gas working fluid, generally hydrogen or helium, is not a CFC. However, current estimates of performance, weight, and cost are very rough, because very little research effort has been invested, and very little has been published in the open literature, concerning the application of this cycle to vehicle air conditioning.

A design and analytical study focused on the application of Stirling Cycle equipment to a specific vehicle electric space conditioning requirement seems to be merited. This study would develop a small number of alternative design configurations, model the performance using Stirling Cycle computer codes, and develop reasonably accurate performance, weight, and cost estimates. Engineering model level hardware development would follow, if justified by the results of the design study.

The major elements of the design study would be:

- Preparation of conceptual design configurations suited for electric vehicle space conditioning, powered by the DC electric power drawn from the traction battery. The objective would be to develop configurations that are compact and lightweight, yet amenable to the measures required to obtain efficiency levels of interest.
- Model these design configurations with second and third order computer codes. Trade-off heat exchanger performance, regenerator effectiveness, dead volume, pressure drops, and speed to arrive at an efficiency and weight optimized configuration providing the required capacity.
- Address capacity modulation options, including variable speed operation and operating pressure level modulation.
- Develop a conceptual layout of the best heat pump system alternative, including the basic Stirling cycle device, interface heat exchangers, liquid loops and pumps, and the prime mover.
- Develop overall system efficiency, weight, and mass production cost estimates for comparison with vapor cycle alternatives.

9.0 References

1. R. Sullivan and S. Selkowitz. Effects of Glazing and Ventilation Options on Automobile Air Conditioner Size and Performance, Applied Science Division, Lawrence Berkley Laboratory, University of California, December 30, 1988, TA-259, LBL-26552.
2. P. Young and R. Bernardi. Auto Solar Control, SAE Technical Paper #880050, 1988.
3. P. Young and R. Bernardi. A Solar Control Glass for Automobiles, Sae Technical Paper # 890311.
4. R. Goodman. Solar Control Glass for Increasing Passenger Comfort in Autos, SAE Technical Paper #890217.
5. T. Kase, M. Kawai, and M. Ura. A New Electrochromic Device for Automobile Glass - The Development of Adjustable Transparency Glass, SAE Technical Paper # 861362
6. Chapters 6&24, 1989 ASHRAE Handbook of Fundamentals.
7. Dieckmann, J.T. and Teagan, W.P., Air Conditioning Systems for Electric Vehicles Phase I/II Final Report, prepared by Arthur D. Little, Inc. under EPRI Research Project 2861-3, May, 1990.
8. Crumly, R.L., et.al., Performance Testing and System Evaluation of the Soleq Evcort Electric Vehicle. EG&G Idaho, Inc. DOE/ID-10232. March, 1989.
9. Crumly, R.L., et.al., Vehicle Performance Tests of the Ford/GE First Generation Single-Shaft (ETX-I) Alternating Current Propulsion System. EG&G Idaho, Inc. DOE/ID-10224. April, 1989.
10. Burke, A.F., Comparison of Simulation and Test for Electric Vehicles of Recent Design. EG&G Idaho, Inc. SAE-890818. March, 1989.
11. Burke, A.F., Electric Vehicle Design and Performance Using Advanced Batteries. EG&G Idaho, Inc. SAE Technical Paper Series #891663, August, 1989.
12. Electric Vehicle Test Procedure, SAE Recommended Practice, J227a.
13. General Motors Corporation, General Motors Technical Center. Press Release dated January 3, 1990, describing the "Impact" prototype electric vehicle.
14. Lindbert, L., and Andersson, M., Thermal Power Booster, SAE Technical Paper Series #900222, March, 1990.
15. Curhan, J., Improved Vehicle Heating with the Use of PTC Ceramic, SAE Technical Paper Series #900220, March, 1990.

16. Kawamoto, H., et.al., Comfort Evaluation of Heating and Air Conditioning Systems, SAE Technical Paper Series #860590, February, 1986.
17. Bessler, W., and Forbes, F., Electrically Driven Automotive Air Conditioner, SAE Technical Paper Series #870035, February, 1987.
18. Sugihara, A., and Lukas, H.G., Performance of Parallel Flow Condensers in Vehicular Applications, SAE Technical Paper Series #900597, March, 1990.
19. Goodremote, C.E., et.al., Compact Air Cooled Air Conditioning Condenser, SAE Technical Paper Series #880445, March, 1988.
20. Priebe, S., Air Conditioning of an Electric Vehicle Using the Brayton Cycle, EG&G Idaho, Inc. Conservation Programs
21. Payne, G.K., Air-Cycle Air Conditioning of Turbine-Powered General Aviation and Commuter Aircraft, SAE Technical Paper Series #850901, April, 1985.
22. Holly, H.C., The Closed-Loop Air-Cycle Option for Equipment Cooling on Aircraft, SAE Technical Paper Series #840940, July, 1984.
23. Edwards, T.C., The Rovac Automotive Air Conditioning System, SAE Technical Paper Series #750403, February, 1975.
24. Warner-ishi Turbocharging
25. Turbocharging and Turbochargers
26. Brown, G.V., Magnetic Heat Pumping Near Room Temperature, Journal of Applied Physics, Vol. 47, No. 8, August 1975.
27. Benford, S.M., and Brown, G.V., T-S Diagram for Gadolinium Near the Curie Temperature, Journal of Applied Physics, Vol. 52, No. 3, March, 1981.
28. Barclay, J.A., and Steyert, W.A., Magnetic Refrigerator Development, Final Report, prepared by Los Alamos Scientific Laboratory for EPRI, April, 1981.
29. Kirol, L.D., Mills J.I., et al, Magnetic Heat Pump Feasibility Assessment, prepared for DOE, Idaho Operations Office, Contract No. DE-AC07-761D01570, October, 1984.
30. Stirling Engine Technologies in Japan. Proceedings of International Symposium on the Stirling Engine and Its Application to Heat Pump Systems, Tokyo, 1-2 December, 1986.
31. "Status of Free-Piston Stirling Engine Driven Heat Pumps--Development, Issues and Options." Arthur D. Little, Inc., ORNL/Sub/84-00205/1, April, 1986.

32. Chen, F.C., "Testing of a Stirling Cycle Cooler", Analysis and Applications of Heat Pumps Presented at the 1988 Winter Annual Meeting of the ASME, Vol 8, pgs. 49-55.
33. Domingo, N., et. al, A Theoretical Analysis of a Kinematic Stirling-Cycle Heat Pump for Space Conditioning Applications, ORNL Report No. ORNL/CON-149, March, 1984.

Appendix A

Sample Input of Load Model

VEHICLE CONFIGURATION DESCRIPTION

```

VEHICLE TYPE      < Tavan window van, PASSENGER, INT FINSH >
WINDSHIELD TRANSMSSIVITY < .53 > WINDSHIELD AREA, SQ FT < 11.7 >
SIDE WINDOWS TRANSMSSVTY < .53 > SIDE WINDOWS AREA, SQ FT < 11.7 >
REAR WINDOW TRANSMSSVTY < .53 > REAR WINDOW AREA, SQ FT < 7.3 >
THETA SUN-VERTICAL < 48. > THETA WINDSHIELD, DEG < 38. >
PHI SUN-HORIZONTAL < 70. > THETA REAR WINDOW, DEG < 90. >
VEHICLE HEIGHT, FEET < 5.4 > ROOF WIDTH, FEET < 6.0 >
WINDSHIELD ABSORPTIVITY < .41 > ROOF AREA, SQ FT < 60. >
SIDE WINDOWS ABSORPTVTY < .41 > SIDE PANEL AREA, SQ FT < 40. >
REAR WINDOW ABSORPTVTY < .41 > BODY PANEL ABSORPTVITY < .9 >
ROOF INTER'R FINISH+/- < 1. > BODY INTERR FINISH +/- < 1.0 >
ROOF INSUL THICKNS, IN < 0.0 > BODY INSUL THICKNS, IN < 0.0 >
ROOF INSUL K, BTUH/FT-F < .014 > BODY INSL K, BTUH/FT-F < .014 >
INTERIOR SURF MASS, LBM < 175. > INTER SURF AREA, SQ FT < 250. >
INTERIOR VOLUME, CUBIC FT < 300. >

```

VEHICLE OPERATING CONDITIONS DESCRIPTION

```

INT AIR TEMP SETPNT, F < 075.0 > AMBIENT AIR TEMP, F < 100. >
INT AIR RH SETPOINT, % < .50 > AMBIENT AIR RH, % < .40 >
VENT AIR FLOW RATE, CFM < 045. > NUMBER OF OCCUPANTS < 4. >
VEHICLE SPEED, MPH < 35.0 > INT SOAK TEMP, F < 140.0 >
INT AIR TEMP TAU, MIN < 3.0 > INSOLATION, BTUH/SQ FT < 333. >

```

Appendix B

Sample Output of Load Model

ELECTRIC VEHICLE INTERIOR HEATING AND COOLING LOAD MODEL
PROGRAM HLOADS

VEHICLE CONFIGURATION DESCRIPTION DATA

VEHICLE TYPE IS Tavan window van, PASSENGER, INT FINSH

WINDSHIELD TRANSMISSIVITY=	.53	WINDSHIELD AREA=	11.70
SIDE WINDOW TRNSMSIVTY=	.53	SIDE WINDOW AREA=	11.70
REAR WINDOW TRNSMSIVTY=	.53	REAR WINDOW AREA=	7.30
THETA SUN--VERTICAL =	48.00	THETA WINDSHIELD =	38.00
PHI SUN--HORIZONTAL =	70.00	THETA REAR WINDOW=	90.00
VEHICLE HEIGHT IN FEET=	5.40	ROOF WIDTH IN FT =	6.00
WINDSHIELD ABSORBTIVITY=	.41	ROOF AREA IN SQ FT=	60.00
SIDE WINDOW ABSRBTIVITY=	.41	SIDE PANEL AREA, SQ FT	40.00
REAR WINDOW ABSRBTIVITY=	.41	BODY PANL ABSRBTIVITY	.90
FINISHED ROOF +/-	1.00	FINISHED SIDE PANEL +/-	1.00
ROOF INSUL THICKNESS, IN=	.00	BODY INSUL THICKNESS, IN=	.00
ROOF INSUL K, BTUH/FT-F=	.014	BODY INSUL K, BTUH/FT-F=	.014
INTERIOR SURFACE MASS, LB=	175.00	INT SURFACE AREA, SQ FT=	250.00
INTERIOR VOLUME, CUBIC FEET=	300.00		

VEHICLE OPERATING CONDITIONS

INTERIOR TEMP SETPOINT=	75.00	AMBIENT AIR TEMP=	100.00
INTERIOR REL HUM SETPOINT=	.50	AMBIENT AIR REL HUM=	.40
VENTILATION MAKEUP CFM=	45.00	NO OF VEH OCCUPANTS=	4.00
VEHICLE SPEED, MPH=	35.00	INTERIOR SOAK TEMP=	140.00
INTERIOR AIR TEMP TIME CONST=	3.00	INSOLATION, BTUH/SQ FT=	333.00

STEADY STATE THERMAL LOADS

TOTAL STEADY STATE LOAD= 12270.41 BTU/HR

VENTILATION LOAD=	2865.12 BTU/HR
SENSIBLE VENTILATION LOAD=	1215.00 BTU/HR
LATENT VENTILATION LOAD=	1650.12 BTU/HR
VENTILATION AIRFLOW=	45.00 CFM
ENTHALPY AMBIENT AIR=	42.26 BTU/LBM
ENTHALPY INTERIOR AIR=	28.11 BTU/LBM

METABOLIC LOAD= 2000.00 BTU/HR

SOLAR LOAD=	2798.56 BTU/HR
WINDSHIELD	1500.18 BTU/HR
REAR WINDOW	.00 BTU/HR
SIDE WINDOW(S)	1298.38 BTU/HR
INSOLATION=	333.00 BTU/HR-SQ FT

CONDUCTION LOAD=	4606.73 BTU/HR
ROOF	1521.04 BTU/HR
SIDE 1 PANELS	930.21 BTU/HR
SIDE 2 PANELS	469.44 BTU/HR
SIDE 1 WINDOWS	533.24 BTU/HR
SIDE 2 WINDOWS	365.46 BTU/HR
WINDSHIELD	559.32 BTU/HR
REAR WINDOW	228.02 BTU/HR
ROOF EXTERIOR SURF TEMP=	125.70 DEG F

TRANSIENT THERMAL LOADS

TIME	TINFAR	TINSRF	QTOT	QVENT	QMETAB	QSOLAR	QCOND	QTRAN
.00	140.00	140.00	1342.16	-347.86	2000.00	2798.56	-3108.55	.00
.50	130.02	140.00	14573.00	145.39	2000.00	2798.56	-1924.11	11553.16
1.00	121.57	139.41	17738.80	562.92	2000.00	2798.56	-921.51	13298.82
1.50	114.42	138.34	20209.08	916.35	2000.00	2798.56	-72.82	14566.99
2.00	108.37	136.92	22103.13	1215.52	2000.00	2798.56	645.57	15443.47
2.50	103.25	135.22	23521.12	1468.77	2000.00	2798.56	1253.68	16000.11
3.00	98.91	133.32	24547.17	1683.13	2000.00	2798.56	1768.44	16297.04
3.50	95.24	131.27	25251.81	1864.59	2000.00	2798.56	2204.17	16384.50
4.00	92.13	129.13	25694.17	2018.19	2000.00	2798.56	2573.00	16304.41
4.50	89.50	126.92	25923.64	2148.21	2000.00	2798.56	2885.22	16091.65
5.00	87.28	124.70	25981.57	2258.27	2000.00	2798.56	3149.50	15775.24
5.50	85.39	122.47	25902.40	2351.43	2000.00	2798.56	3373.21	15379.19
6.00	83.80	120.26	25714.79	2430.29	2000.00	2798.56	3562.58	14923.36
6.50	82.45	118.09	25442.58	2497.04	2000.00	2798.56	3722.88	14424.10
7.00	81.30	115.97	25105.52	2553.55	2000.00	2798.56	3858.56	13894.84
7.50	80.34	113.91	24719.89	2601.38	2000.00	2798.56	3973.42	13346.53
8.00	79.52	111.91	24299.14	2641.87	2000.00	2798.56	4070.65	12788.06
8.50	78.82	109.98	23854.25	2676.14	2000.00	2798.56	4152.94	12226.60
9.00	78.24	108.13	23394.23	2705.15	2000.00	2798.56	4222.61	11667.91
9.50	77.74	106.35	22926.37	2729.71	2000.00	2798.56	4281.58	11116.51
10.00	77.32	104.64	22456.52	2750.50	2000.00	2798.56	4331.50	10575.96
10.50	76.96	103.02	21989.40	2768.10	2000.00	2798.56	4373.75	10048.99
11.00	76.66	101.47	21528.71	2782.99	2000.00	2798.56	4409.52	9537.64
11.50	76.41	99.99	21077.36	2795.60	2000.00	2798.56	4439.79	9043.41
12.00	76.19	98.59	20637.56	2806.27	2000.00	2798.56	4465.42	8567.31
12.50	76.01	97.25	20210.98	2815.31	2000.00	2798.56	4487.11	8109.99
13.00	75.85	95.99	19798.82	2822.95	2000.00	2798.56	4505.48	7671.83
13.50	75.72	94.79	19401.91	2829.43	2000.00	2798.56	4521.02	7252.90
14.00	75.61	93.65	19020.77	2834.91	2000.00	2798.56	4534.18	6853.11
14.50	75.52	92.58	18655.65	2839.54	2000.00	2798.56	4545.32	6472.22
15.00	75.44	91.57	18306.63	2843.47	2000.00	2798.56	4554.74	6109.85
15.50	75.37	90.61	17973.63	2846.79	2000.00	2798.56	4562.73	5765.54
16.00	75.31	89.70	17656.39	2849.61	2000.00	2798.56	4569.48	5438.74
16.50	75.27	88.84	17354.64	2851.99	2000.00	2798.56	4575.20	5128.89
17.00	75.22	88.03	17067.96	2854.00	2000.00	2798.56	4580.04	4835.35
17.50	75.19	87.27	16795.89	2855.71	2000.00	2798.56	4584.14	4557.48
18.00	75.16	86.55	16537.94	2857.16	2000.00	2798.56	4587.61	4294.62
18.50	75.14	85.87	16293.59	2858.38	2000.00	2798.56	4590.54	4046.11
19.00	75.12	85.24	16062.30	2859.41	2000.00	2798.56	4593.03	3811.30
19.50	75.10	84.63	15843.53	2860.29	2000.00	2798.56	4595.13	3589.54
20.00	75.08	84.07	15636.71	2861.03	2000.00	2798.56	4596.91	3380.21
20.50	75.07	83.53	15441.30	2861.66	2000.00	2798.56	4598.42	3182.65
21.00	75.06	83.03	15256.76	2862.19	2000.00	2798.56	4599.69	2996.31
21.50	75.05	82.55	15082.56	2862.64	2000.00	2798.56	4600.77	2820.58
22.00	75.04	82.11	14918.18	2863.02	2000.00	2798.56	4601.69	2654.90
22.50	75.04	81.69	14763.13	2863.34	2000.00	2798.56	4602.46	2498.76
23.00	75.03	81.29	14616.90	2863.62	2000.00	2798.56	4603.12	2351.61
23.50	75.03	80.92	14479.07	2863.85	2000.00	2798.56	4603.67	2212.98
24.00	75.02	80.57	14349.14	2864.04	2000.00	2798.56	4604.14	2082.39
24.50	75.02	80.24	14226.72	2864.21	2000.00	2798.56	4604.54	1959.41
25.00	75.02	79.93	14111.37	2864.35	2000.00	2798.56	4604.88	1843.59
25.50	75.01	79.63	14002.74	2864.47	2000.00	2798.56	4605.16	1734.55
26.00	75.01	79.36	13900.41	2864.57	2000.00	2798.56	4605.40	1631.88
26.50	75.01	79.10	13804.06	2864.65	2000.00	2798.56	4605.61	1535.24
27.00	75.01	78.86	13713.35	2864.72	2000.00	2798.56	4605.78	1444.28
27.50	75.01	78.63	13627.93	2864.78	2000.00	2798.56	4605.92	1358.66
28.00	75.01	78.41	13547.54	2864.84	2000.00	2798.56	4606.05	1278.09
28.50	75.00	78.21	13471.86	2864.88	2000.00	2798.56	4606.15	1202.26
29.00	75.00	78.02	13400.64	2864.92	2000.00	2798.56	4606.24	1130.92
29.50	75.00	77.84	13333.61	2864.95	2000.00	2798.56	4606.32	1063.78
30.00	75.00	77.67	13270.53	2864.97	2000.00	2798.56	4606.38	1000.61

Appendix C

Thermal Load Model Output for Electric G-Van at Wind Tunnel Test Conditions

ELECTRIC VEHICLE INTERIOR HEATING AND COOLING LOAD MODEL
PROGRAM HLOADS

VEHICLE CONFIGURATION DESCRIPTION DATA

VEHICLE TYPE IS GVAN window van, PASSENGER, INT FINSH >

WINDSHIELD TRANSMISSIVITY=	.84	WINDSHIELD AREA=	12.50
SIDE WINDOW TRNSMSIVTY=	.53	SIDE WINDOW AREA=	10.90
REAR WINDOW TRNSMSIVTY=	.84	REAR WINDOW AREA=	5.10
THETA SUN--VERTICAL =	67.50	THETA WINDSHIELD =	56.00
PHI SUN--HORIZONTAL =	90.00	THETA REAR WINDOW=	90.00
VEHICLE HEIGHT IN FEET=	6.30	ROOF WIDTH IN FT =	6.00
WINDSHIELD ABSORBTIVTY=	.08	ROOF AREA IN SQ FT=	72.00
SIDE WINDOW ABSRBTIVTY=	.41	SIDE PANEL AREA, SQ FT	40.00
REAR WINDOW ABSRBTIVTY=	.08	BODY PANEL ABSRBTIVITY	.50
FINISHED ROOF +/-	1.00	FINISHED SIDE PANEL +/-	1.00
ROOF INSUL THICKNESS, IN=	.00	BODY INSUL THICKNESS, IN=	.00
ROOF INSUL K, BTUH/FT-F=	.014	BODY INSUL K, BTUH/FT-F=	.014
INTERIOR SURFACE MASS, LB=	200.00	INT SURFACE AREA, SQ FT=	300.00
INTERIOR VOLUME, CUBIC FEET=	360.00		

VEHICLE OPERATING CONDITIONS

INTERIOR TEMP SETPOINT=	73.00	AMBIENT AIR TEMP=	100.00
INTERIOR REL HUM SETPOINT=	.20	AMBIENT AIR REL HUM=	.40
VENTILATION MAKEUP CFM=	263.00	NO OF VEH OCCUPANTS=	.00
VEHICLE SPEED, MPH=	50.00	INTERIOR SOAK TEMP=	130.00
INTERIOR AIR TEMP TIME CONST=	4.50	INSOLATION, BTUH/SQ FT=	333.00

STEADY STATE THERMAL LOADS

TOTAL STEADY STATE LOAD= 31413.47 BTU/HR

VENTILATION LOAD=	24845.47 BTU/HR
SENSIBLE VENTILATION LOAD=	7669.08 BTU/HR
LATENT VENTILATION LOAD=	17176.39 BTU/HR
VENTILATION AIRFLOW=	263.00 CFM
ENTHALPY AMBIENT AIR=	42.26 BTU/LBM
ENTHALPY INTERIOR AIR=	21.26 BTU/LBM

METABOLIC LOAD= .00 BTU/HR

SOLAR LOAD=	2542.57 BTU/HR
WINDSHIELD	1806.39 BTU/HR
REAR WINDOW	.00 BTU/HR
SIDE WINDOW(S)	736.18 BTU/HR
INSOLATION=	333.00 BTU/HR-SQ FT

CONDUCTION LOAD=	4025.43 BTU/HR
ROOF	1401.54 BTU/HR
SIDE 1 PANELS	625.56 BTU/HR
SIDE 2 PANELS	514.63 BTU/HR
SIDE 1 WINDOWS	458.24 BTU/HR
SIDE 2 WINDOWS	383.57 BTU/HR
WINDSHIELD	462.43 BTU/HR
REAR WINDOW	179.47 BTU/HR
ROOF EXTERIOR SURF TEMP=	111.93 DEG F

ELECTRIC VEHICLE INTERIOR HEATING AND COOLING LOAD MODEL
PROGRAM HCLoads

VEHICLE CONFIGURATION DESCRIPTION DATA

VEHICLE TYPE IS GVAN window van, PASSENGER, INT FINSH >

WINDSHIELD TRANSMISSIVITY=	.84	WINDSHIELD AREA=	12.50
SIDE WINDOW TRNSMSIVTY=	.53	SIDE WINDOW AREA=	10.90
REAR WINDOW TRNSMSIVTY=	.84	REAR WINDOW AREA=	5.10
THETA SUN--VERTICAL =	67.50	THETA WINDSHIELD =	56.00
PHI SUN--HORIZONTAL =	90.00	THETA REAR WINDOW=	90.00
VEHICLE HEIGHT IN FEET=	6.30	ROOF WIDTH IN FT =	6.00
WINDSHIELD ABSORBTIVITY=	.08	ROOF AREA IN SQ FT=	72.00
SIDE WINDOW ABSRBTIVITY=	.41	SIDE PANEL AREA, SQ FT	40.00
REAR WINDOW ABSRBTIVITY=	.08	BODY PANEL ABSRBTIVITY	.50
FINISHED ROOF +/-	1.00	FINISHED SIDE PANEL +/-	1.00
ROOF INSUL THICKNESS, IN=	.00	BODY INSUL THICKNESS, IN=	.00
ROOF INSUL K, BTUH/FT-F=	.014	BODY INSUL K, BTUH/FT-F=	.014
INTERIOR SURFACE MASS, LB=	200.00	INT SURFACE AREA, SQ FT=	300.00
INTERIOR VOLUME, CUBIC FEET=	360.00		

VEHICLE OPERATING CONDITIONS

INTERIOR TEMP SETPOINT=	73.00	AMBIENT AIR TEMP=	100.00
INTERIOR REL HUM SETPOINT=	.20	AMBIENT AIR REL HUM=	.40
VENTILATION MAKEUP CFM=	238.00	NO OF VEH OCCUPANTS=	.00
VEHICLE SPEED, MPH=	50.00	INTERIOR SOAK TEMP=	130.00
INTERIOR AIR TEMP TIME CONST=	4.50	INSOLATION, BTUH/SQ FT=	333.00

STEADY STATE THERMAL LOADS

TOTAL STEADY STATE LOAD= 29051.73 BTU/HR

VENTILATION LOAD=	22483.73 BTU/HR
SENSIBLE VENTILATION LOAD=	6940.08 BTU/HR
LATENT VENTILATION LOAD=	15543.65 BTU/HR
VENTILATION AIRFLOW=	238.00 CFM
ENTHALPY AMBIENT AIR=	42.26 BTU/LBM
ENTHALPY INTERIOR AIR=	21.26 BTU/LBM

METABOLIC LOAD= .00 BTU/HR

SOLAR LOAD=	2542.57 BTU/HR
WINDSHIELD	1806.39 BTU/HR
REAR WINDOW	.00 BTU/HR
SIDE WINDOW(S)	736.18 BTU/HR
INSOLATION=	333.00 BTU/HR-SQ FT

CONDUCTION LOAD=	4025.43 BTU/HR
ROOF	1401.54 BTU/HR
SIDE 1 PANELS	625.56 BTU/HR
SIDE 2 PANELS	514.63 BTU/HR
SIDE 1 WINDOWS	458.24 BTU/HR
SIDE 2 WINDOWS	383.57 BTU/HR
WINDSHIELD	462.43 BTU/HR
REAR WINDOW	179.47 BTU/HR
ROOF EXTERIOR SURF TEMP=	111.93 DEG F

ELECTRIC VEHICLE INTERIOR HEATING AND COOLING LOAD MODEL
PROGRAM HLOADS

VEHICLE CONFIGURATION DESCRIPTION DATA

VEHICLE TYPE IS GVAN window van, PASSENGER, INT FINSH

>

WINDSHIELD TRANSMISSIVITY=	.84	WINDSHIELD AREA=	12.50
SIDE WINDOW TRNSMSIVTY=	.53	SIDE WINDOW AREA=	10.90
REAR WINDOW TRNSMSIVTY=	.84	REAR WINDOW AREA=	5.10
THETA SUN--VERTICAL =	67.50	THETA WINDSHIELD =	56.00
PHI SUN--HORIZONTAL =	90.00	THETA REAR WINDOW=	90.00
VEHICLE HEIGHT IN FEET=	6.30	ROOF WIDTH IN FT =	6.00
WINDSHIELD ABSORBTIVITY=	.08	ROOF AREA IN SQ FT=	72.00
SIDE WINDOW ABSRBTIVITY=	.41	SIDE PANEL AREA, SQ FT	40.00
REAR WINDOW ABSRBTIVITY=	.08	BODY PANEL ABSRBTIVITY	.50
FINISHED ROOF +/-	1.00	FINISHED SIDE PANEL +/-	1.00
ROOF INSUL THICKNESS, IN=	.00	BODY INSUL THICKNESS, IN=	.00
ROOF INSUL K, BTUH/FT-F=	.014	BODY INSUL K, BTUH/FT-F=	.014
INTERIOR SURFACE MASS, LB=	200.00	INT SURFACE AREA, SQ FT=	300.00
INTERIOR VOLUME, CUBIC FEET=	360.00		

VEHICLE OPERATING CONDITIONS

INTERIOR TEMP SETPOINT=	76.00	AMBIENT AIR TEMP=	110.00
INTERIOR REL HUM SETPOINT=	.20	AMBIENT AIR REL HUM=	.40
VENTILATION MAKEUP CFM=	65.00	NO OF VEH OCCUPANTS=	.00
VEHICLE SPEED, MPH=	35.00	INTERIOR SOAK TEMP=	130.00
INTERIOR AIR TEMP TIME CONST=	4.50	INSOLATION, BTUH/SQ FT=	333.00

STEADY STATE THERMAL LOADS

TOTAL STEADY STATE LOAD= 15950.03 BTU/HR

VENTILATION LOAD=	8441.65 BTU/HR
SENSIBLE VENTILATION LOAD=	2386.80 BTU/HR
LATENT VENTILATION LOAD=	6054.85 BTU/HR
VENTILATION AIRFLOW=	65.00 CFM
ENTHALPY AMBIENT AIR=	51.25 BTU/LBM
ENTHALPY INTERIOR AIR=	22.39 BTU/LBM

METABOLIC LOAD= .00 BTU/HR

SOLAR LOAD=	2542.57 BTU/HR
WINDSHIELD	1806.39 BTU/HR
REAR WINDOW	.00 BTU/HR
SIDE WINDOW(S)	736.18 BTU/HR
INSOLATION=	333.00 BTU/HR-SQ FT

CONDUCTION LOAD=	4965.80 BTU/HR
ROOF	1749.74 BTU/HR
SIDE 1 PANELS	780.03 BTU/HR
SIDE 2 PANELS	638.43 BTU/HR
SIDE 1 WINDOWS	558.17 BTU/HR
SIDE 2 WINDOWS	463.04 BTU/HR
WINDSHIELD	559.74 BTU/HR
REAR WINDOW	216.65 BTU/HR
ROOF EXTERIOR SURF TEMP=	124.60 DEG F

ELECTRIC VEHICLE INTERIOR HEATING AND COOLING LOAD MODEL
PROGRAM HCLoads

VEHICLE CONFIGURATION DESCRIPTION DATA

VEHICLE TYPE IS GVAN window van, PASSENGER, INT FINSH >

WINDSHIELD TRANSMISSIVITY=	.84	WINDSHIELD AREA=	12.50
SIDE WINDOW TRNSMSIVTY=	.53	SIDE WINDOW AREA=	10.90
REAR WINDOW TRNSMSIVTY=	.84	REAR WINDOW AREA=	5.10
THETA SUN--VERTICAL =	67.50	THETA WINDSHIELD =	56.00
PHI SUN--HORIZONTAL =	90.00	THETA REAR WINDOW=	90.00
VEHICLE HEIGHT IN FEET=	6.30	ROOF WIDTH IN FT =	6.00
WINDSHIELD ABSORBTIVITY=	.08	ROOF AREA IN SQ FT=	72.00
SIDE WINDOW ABSRBTIVITY=	.41	SIDE PANEL AREA, SQ FT	40.00
REAR WINDOW ABSRBTIVITY=	.08	BODY PANEL ABSRBTIVITY	.50
FINISHED ROOF +/-	1.00	FINISHED SIDE PANEL +/-	1.00
ROOF INSUL THICKNESS, IN=	.00	BODY INSUL THICKNESS, IN=	.00
ROOF INSUL K, BTUH/FT-F=	.014	BODY INSUL K, BTUH/FT-F=	.014
INTERIOR SURFACE MASS, LB=	200.00	INT SURFACE AREA, SQ FT=	300.00
INTERIOR VOLUME, CUBIC FEET=	360.00		

VEHICLE OPERATING CONDITIONS

INTERIOR TEMP SETPOINT=	68.00	AMBIENT AIR TEMP=	90.00
INTERIOR REL HUM SETPOINT=	.23	AMBIENT AIR REL HUM=	.50
VENTILATION MAKEUP CFM=	65.00	NO OF VEH OCCUPANTS=	.00
VEHICLE SPEED, MPH=	35.00	INTERIOR SOAK TEMP=	130.00
INTERIOR AIR TEMP TIME CONST=	4.50	INSOLATION, BTUH/SQ FT=	333.00

STEADY STATE THERMAL LOADS

TOTAL STEADY STATE LOAD= 11428.14 BTU/HR

VENTILATION LOAD=	5363.55 BTU/HR
SENSIBLE VENTILATION LOAD=	1544.40 BTU/HR
LATENT VENTILATION LOAD=	3819.15 BTU/HR
VENTILATION AIRFLOW=	65.00 CFM
ENTHALPY AMBIENT AIR=	38.28 BTU/LBM
ENTHALPY INTERIOR AIR=	19.94 BTU/LBM

METABOLIC LOAD= .00 BTU/HR

SOLAR LOAD=	2542.57 BTU/HR
WINDSHIELD	1806.39 BTU/HR
REAR WINDOW	.00 BTU/HR
SIDE WINDOW(S)	736.18 BTU/HR
INSOLATION=	333.00 BTU/HR-SQ FT

CONDUCTION LOAD=	3522.02 BTU/HR
ROOF	1347.74 BTU/HR
SIDE 1 PANELS	554.30 BTU/HR
SIDE 2 PANELS	413.10 BTU/HR
SIDE 1 WINDOWS	394.75 BTU/HR
SIDE 2 WINDOWS	299.61 BTU/HR
WINDSHIELD	372.33 BTU/HR
REAR WINDOW	140.19 BTU/HR
ROOF EXTERIOR SURF TEMP=	105.44 DEG F

ELECTRIC VEHICLE INTERIOR HEATING AND COOLING LOAD MODEL
PROGRAM HCLoads

VEHICLE CONFIGURATION DESCRIPTION DATA

VEHICLE TYPE IS GVAN window van, PASSENGER, INT FINSH

WINDSHIELD TRANSMISSIVITY=	.84	WINDSHIELD AREA=	12.50
SIDE WINDOW TRNSMSIVTY=	.53	SIDE WINDOW AREA=	10.90
REAR WINDOW TRNSMSIVTY=	.84	REAR WINDOW AREA=	5.10
THETA SUN--VERTICAL =	67.50	THETA WINDSHIELD =	56.00
PHI SUN--HORIZONTAL =	90.00	THETA REAR WINDOW=	90.00
VEHICLE HEIGHT IN FEET=	6.30	ROOF WIDTH IN FT =	6.00
WINDSHIELD ABSORBTIVITY=	.08	ROOF AREA IN SQ FT=	72.00
SIDE WINDOW ABSRBTIVITY=	.41	SIDE PANEL AREA, SQ FT	40.00
REAR WINDOW ABSRBTIVITY=	.08	BODY PANEL ABSRBTIVITY	.50
FINISHED ROOF +/-	1.00	FINISHED SIDE PANEL +/-	1.00
ROOF INSUL THICKNESS, IN=	.00	BODY INSUL THICKNESS, IN=	.00
ROOF INSUL K, BTUH/FT-F=	.014	BODY INSUL K, BTUH/FT-F=	.014
INTERIOR SURFACE MASS, LB=	200.00	INT SURFACE AREA, SQ FT=	300.00
INTERIOR VOLUME, CUBIC FEET=	360.00		

VEHICLE OPERATING CONDITIONS

INTERIOR TEMP SETPOINT=	70.50	AMBIENT AIR TEMP=	100.00
INTERIOR REL HUM SETPOINT=	.20	AMBIENT AIR REL HUM=	.40
VENTILATION MAKEUP CFM=	65.00	NO OF VEH OCCUPANTS=	.00
VEHICLE SPEED, MPH=	30.00	INTERIOR SOAK TEMP=	130.00
INTERIOR AIR TEMP TIME CONST=	6.00	INSOLATION, BTUH/SQ FT=	333.00

STEADY STATE THERMAL LOADS

TOTAL STEADY STATE LOAD= 13417.69 BTU/HR

VENTILATION LOAD=	6406.36 BTU/HR
SENSIBLE VENTILATION LOAD=	2070.90 BTU/HR
LATENT VENTILATION LOAD=	4335.46 BTU/HR
VENTILATION AIRFLOW=	65.00 CFM
ENTHALPY AMBIENT AIR=	42.26 BTU/LBM
ENTHALPY INTERIOR AIR=	20.35 BTU/LBM

METABOLIC LOAD= .00 BTU/HR

SOLAR LOAD=	2542.57 BTU/HR
WINDSHIELD	1806.39 BTU/HR
REAR WINDOW	.00 BTU/HR
SIDE WINDOW(S)	736.18 BTU/HR
INSOLATION=	333.00 BTU/HR-SQ FT

CONDUCTION LOAD=	4468.77 BTU/HR
ROOF	1654.50 BTU/HR
SIDE 1 PANELS	706.35 BTU/HR
SIDE 2 PANELS	549.67 BTU/HR
SIDE 1 WINDOWS	498.44 BTU/HR
SIDE 2 WINDOWS	393.17 BTU/HR
WINDSHIELD	482.68 BTU/HR
REAR WINDOW	183.96 BTU/HR
ROOF EXTERIOR SURF TEMP=	116.46 DEG F

TRANSIENT THERMAL LOADS

TIME	TINTAR	TINSRF	QTOT	QVENT	QMETAB	QSOLAR	QCOND	QTRAN
.00	130.00	130.00	5638.10	4665.15	.00	2542.57	-1569.62	.00
.75	121.71	130.00	15284.00	5251.05	.00	2542.57	-566.30	8056.67
1.50	114.69	129.22	18773.16	5747.01	.00	2542.57	283.00	10200.59
2.25	108.75	127.86	21409.72	6166.82	.00	2542.57	1001.90	11698.42
3.00	103.72	126.07	23354.28	6522.19	.00	2542.57	1610.44	12679.08
3.75	99.47	123.97	24740.02	6823.00	.00	2542.57	2125.56	13248.89
4.50	95.87	121.68	25677.11	7077.63	.00	2542.57	2561.59	13495.32
5.25	92.82	119.26	26256.55	7293.17	.00	2542.57	2930.68	13490.13
6.00	90.23	116.78	26553.29	7475.62	.00	2542.57	3243.11	13291.99
6.75	88.05	114.29	26628.91	7630.06	.00	2542.57	3507.58	12948.70
7.50	86.20	111.83	26533.79	7760.79	.00	2542.57	3731.45	12498.99
8.25	84.63	109.43	26309.08	7871.46	.00	2542.57	3920.94	11974.11
9.00	83.31	107.10	25988.18	7965.13	.00	2542.57	4081.35	11399.13
9.75	82.19	104.87	25598.11	8044.42	.00	2542.57	4217.13	10793.99
10.50	81.24	102.74	25160.60	8111.54	.00	2542.57	4332.06	10174.42
11.25	80.43	100.73	24692.99	8168.36	.00	2542.57	4429.36	9552.71
12.00	79.75	98.83	24209.01	8216.45	.00	2542.57	4511.71	8938.28
12.75	79.18	97.04	23719.46	8257.16	.00	2542.57	4581.42	8338.30
13.50	78.69	95.36	23232.66	8291.62	.00	2542.57	4640.43	7758.03
14.25	78.28	93.80	22754.99	8320.79	.00	2542.57	4690.38	7201.24
15.00	77.93	92.34	22291.18	8345.48	.00	2542.57	4732.66	6670.46
15.75	77.63	90.99	21844.71	8366.39	.00	2542.57	4768.46	6167.29
16.50	77.38	89.74	21417.94	8384.08	.00	2542.57	4798.75	5692.54
17.25	77.17	88.58	21012.43	8399.05	.00	2542.57	4824.40	5246.41
18.00	76.99	87.51	20629.08	8411.73	.00	2542.57	4846.11	4828.67
18.75	76.84	86.52	20268.22	8422.46	.00	2542.57	4864.48	4438.71
19.50	76.71	85.62	19929.84	8431.55	.00	2542.57	4880.04	4075.69
20.25	76.60	84.78	19613.55	8439.24	.00	2542.57	4893.20	3738.54
21.00	76.51	84.01	19318.76	8445.75	.00	2542.57	4904.35	3426.10
21.75	76.43	83.31	19044.71	8451.25	.00	2542.57	4913.78	3137.10
22.50	76.36	82.67	18790.53	8455.92	.00	2542.57	4921.77	2870.27
23.25	76.31	82.07	18555.22	8459.87	.00	2542.57	4928.53	2624.26
24.00	76.26	81.53	18337.79	8463.21	.00	2542.57	4934.25	2397.76
24.75	76.22	81.04	18137.21	8466.04	.00	2542.57	4939.10	2189.51
25.50	76.19	80.59	17952.44	8468.43	.00	2542.57	4943.20	1998.25
26.25	76.16	80.18	17782.45	8470.46	.00	2542.57	4946.67	1822.76
27.00	76.13	79.80	17626.25	8472.17	.00	2542.57	4949.61	1661.90
27.75	76.11	79.46	17482.87	8473.63	.00	2542.57	4952.09	1514.59
28.50	76.10	79.14	17351.41	8474.86	.00	2542.57	4954.20	1379.78
29.25	76.08	78.86	17230.96	8475.90	.00	2542.57	4955.98	1256.51
30.00	76.07	78.60	17120.70	8476.78	.00	2542.57	4957.49	1143.86
30.75	76.06	78.36	17019.84	8477.52	.00	2542.57	4958.76	1040.99
31.50	76.05	78.14	16927.66	8478.15	.00	2542.57	4959.85	947.09
32.25	76.04	77.95	16843.44	8478.69	.00	2542.57	4960.76	861.42
33.00	76.04	77.77	16766.54	8479.14	.00	2542.57	4961.53	783.30
33.75	76.03	77.61	16696.39	8479.52	.00	2542.57	4962.19	712.11
34.50	76.03	77.46	16632.40	8479.85	.00	2542.57	4962.74	647.24
35.25	76.02	77.32	16574.07	8480.12	.00	2542.57	4963.21	588.17
36.00	76.02	77.20	16520.92	8480.35	.00	2542.57	4963.61	534.38
36.75	76.02	77.09	16472.50	8480.55	.00	2542.57	4963.95	485.43
37.50	76.01	76.99	16428.42	8480.72	.00	2542.57	4964.23	440.90
38.25	76.01	76.90	16388.29	8480.86	.00	2542.57	4964.47	400.39
39.00	76.01	76.82	16351.77	8480.98	.00	2542.57	4964.68	363.55
39.75	76.01	76.74	16318.55	8481.08	.00	2542.57	4964.85	330.05
40.50	76.01	76.67	16288.35	8481.16	.00	2542.57	4965.00	299.62
41.25	76.01	76.61	16260.88	8481.24	.00	2542.57	4965.12	271.95
42.00	76.00	76.55	16235.90	8481.30	.00	2542.57	4965.23	246.81
42.75	76.00	76.50	16213.21	8481.35	.00	2542.57	4965.32	223.97
43.50	76.00	76.45	16192.59	8481.39	.00	2542.57	4965.39	203.24
44.25	76.00	76.41	16173.84	8481.43	.00	2542.57	4965.45	184.39
45.00	76.00	76.37	16156.83	8481.46	.00	2542.57	4965.51	167.30

Appendix D

Thermal Load Model Output for EPRI Electric TE Van at Wind Tunnel Test Conditions

ELECTRIC VEHICLE INTERIOR HEATING AND COOLING LOAD MODEL
PROGRAM HCLoads

VEHICLE CONFIGURATION DESCRIPTION DATA

VEHICLE TYPE IS Tavan window van, PASSENGER, INT FINSH

WINDSHIELD TRANSMISSIVITY=	.84	WINDSHIELD AREA=	11.70
SIDE WINDOW TRNSMSIVTY=	.53	SIDE WINDOW AREA=	11.70
REAR WINDOW TRNSMSIVTY=	.84	REAR WINDOW AREA=	7.30
THETA SUN--VERTICAL =	67.50	THETA WINDSHIELD =	38.00
PHI SUN--HORIZONTAL =	90.00	THETA REAR WINDOW=	90.00
VEHICLE HEIGHT IN FEET=	5.40	ROOF WIDTH IN FT =	6.00
WINDSHIELD ABSORBTIVITY=	.08	ROOF AREA IN SQ FT=	60.00
SIDE WINDOW ABSRBTIVITY=	.41	SIDE PANEL AREA, SQ FT	40.00
REAR WINDOW ABSRBTIVITY=	.08	BODY PANEL ABSRBTIVITY	.90
FINISHED ROOF +/-	1.00	FINISHED SIDE PANEL +/-	1.00
ROOF INSUL THICKNESS, IN=	.00	BODY INSUL THICKNESS, IN=	.00
ROOF INSUL K, BTUH/FT-F=	.014	BODY INSUL K, BTUH/FT-F=	.014
INTERIOR SURFACE MASS, LB=	175.00	INT SURFACE AREA, SQ FT=	250.00
INTERIOR VOLUME, CUBIC FEET=	300.00		

VEHICLE OPERATING CONDITIONS

INTERIOR TEMP SETPOINT=	86.50	AMBIENT AIR TEMP=	109.00
INTERIOR REL HUM SETPOINT=	.23	AMBIENT AIR REL HUM=	.20
VENTILATION MAKEUP CFM=	20.00	NO OF VEH OCCUPANTS=	.00
VEHICLE SPEED, MPH=	25.00	INTERIOR SOAK TEMP=	140.00
INTERIOR AIR TEMP TIME CONST=	3.00	INSOLATION, BTUH/SQ FT=	215.00

STEADY STATE THERMAL LOADS

TOTAL STEADY STATE LOAD= 6602.35 BTU/HR

VENTILATION LOAD=	943.33 BTU/HR
SENSIBLE VENTILATION LOAD=	486.00 BTU/HR
LATENT VENTILATION LOAD=	457.33 BTU/HR
VENTILATION AIRFLOW=	20.00 CFM
ENTHALPY AMBIENT AIR=	38.00 BTU/LBM
ENTHALPY INTERIOR AIR=	27.52 BTU/LBM

METABOLIC LOAD= .00 BTU/HR

SOLAR LOAD=	2048.53 BTU/HR
WINDSHIELD	1538.34 BTU/HR
REAR WINDOW	.00 BTU/HR
SIDE WINDOW(S)	510.20 BTU/HR
INSOLATION=	215.00 BTU/HR-SQ FT

CONDUCTION LOAD=	3610.48 BTU/HR
ROOF	1333.80 BTU/HR
SIDE 1 PANELS	615.58 BTU/HR
SIDE 2 PANELS	414.96 BTU/HR
SIDE 1 WINDOWS	394.83 BTU/HR
SIDE 2 WINDOWS	312.84 BTU/HR
WINDSHIELD	343.28 BTU/HR
REAR WINDOW	195.19 BTU/HR
ROOF EXTERIOR SURF TEMP=	130.96 DEG F

TRANSIENT THERMAL LOADS

TIME	TINTAR	TINSRF	QTOT	QVENT	QMETAB	QSOLAR	QCOND	QTRAN
.00	140.00	140.00	-553.72	-29.69	.00	2048.53	-2572.57	.00
.50	131.79	140.00	10083.46	149.10	.00	2048.53	-1623.32	9509.14
1.00	124.83	139.51	12475.11	300.44	.00	2048.53	-819.82	10945.95
1.50	118.95	138.64	14327.18	428.55	.00	2048.53	-139.67	11989.76
2.00	113.97	137.47	15732.75	536.99	.00	2048.53	436.06	12711.16
2.50	109.75	136.07	16770.04	628.79	.00	2048.53	923.40	13169.32
3.00	106.18	134.50	17504.67	706.49	.00	2048.53	1335.92	13413.72
3.50	103.16	132.81	17991.62	772.26	.00	2048.53	1685.11	13485.71
4.00	100.60	131.05	18276.95	827.94	.00	2048.53	1980.70	13419.78
4.50	98.44	129.24	18399.17	875.06	.00	2048.53	2230.90	13244.67
5.00	96.60	127.40	18390.42	914.96	.00	2048.53	2442.69	12984.24
5.50	95.05	125.57	18277.49	948.73	.00	2048.53	2621.97	12658.25
6.00	93.74	123.75	18082.64	977.31	.00	2048.53	2773.73	12283.07
6.50	92.63	121.97	17824.38	1001.51	.00	2048.53	2902.19	11872.15
7.00	91.69	120.22	17517.97	1021.99	.00	2048.53	3010.92	11476.52
7.50	90.89	118.52	17176.05	1039.33	.00	2048.53	3102.97	10985.22
8.00	90.22	116.88	16808.98	1054.00	.00	2048.53	3180.88	10525.56
8.50	89.65	115.29	16425.23	1066.43	.00	2048.53	3246.83	10063.43
9.00	89.16	113.76	16031.73	1076.94	.00	2048.53	3302.66	9503.59
9.50	88.75	112.30	15634.04	1085.84	.00	2048.53	3349.92	9149.74
10.00	88.41	110.90	15236.65	1093.38	.00	2048.53	3389.92	8704.82
10.50	88.12	109.56	14843.16	1099.76	.00	2048.53	3423.78	8271.09
11.00	87.87	108.28	14456.35	1105.15	.00	2048.53	3452.44	7850.22
11.50	87.66	107.07	14078.38	1109.72	.00	2048.53	3476.70	7443.42
12.00	87.48	105.91	13710.92	1113.59	.00	2048.53	3497.24	7051.55
12.50	87.33	104.82	13355.19	1116.87	.00	2048.53	3514.63	6675.16
13.00	87.20	103.78	13012.03	1119.64	.00	2048.53	3529.34	6314.51
13.50	87.09	102.79	12682.02	1121.99	.00	2048.53	3541.80	5969.70
14.00	87.00	101.85	12365.49	1123.97	.00	2048.53	3552.34	5640.64
14.50	86.93	100.97	12062.59	1125.65	.00	2048.53	3561.27	5327.14
15.00	86.86	100.13	11773.31	1127.08	.00	2048.53	3568.83	5028.88
15.50	86.81	99.34	11497.53	1128.28	.00	2048.53	3575.22	4745.49
16.00	86.76	98.60	11234.98	1129.30	.00	2048.53	3580.63	4476.51
16.50	86.72	97.89	10985.39	1130.16	.00	2048.53	3585.22	4221.47
17.00	86.69	97.23	10748.40	1130.90	.00	2048.53	3589.10	3979.87
17.50	86.66	96.60	10523.58	1131.51	.00	2048.53	3592.38	3751.15
18.00	86.63	96.01	10310.53	1132.04	.00	2048.53	3595.16	3534.80
18.50	86.61	95.45	10108.79	1132.48	.00	2048.53	3597.51	3330.27
19.00	86.60	94.92	9917.88	1132.86	.00	2048.53	3599.50	3136.99
19.50	86.58	94.43	9737.37	1133.17	.00	2048.53	3601.19	2954.47
20.00	86.57	93.96	9566.76	1133.44	.00	2048.53	3602.62	2782.17
20.50	86.56	93.52	9405.60	1133.67	.00	2048.53	3603.82	2619.57
21.00	86.55	93.11	9253.44	1133.86	.00	2048.53	3604.85	2466.20
21.50	86.54	92.72	9109.83	1134.02	.00	2048.53	3605.71	2321.55
22.00	86.53	92.35	8974.34	1134.16	.00	2048.53	3606.44	2185.20
22.50	86.53	92.00	8846.56	1134.28	.00	2048.53	3607.07	2056.68
23.00	86.53	91.68	8726.06	1134.38	.00	2048.53	3607.59	1935.56
23.50	86.52	91.37	8612.49	1134.46	.00	2048.53	3608.03	1821.46
24.00	86.52	91.08	8505.46	1134.53	.00	2048.53	3608.41	1713.98
24.50	86.52	90.81	8404.60	1134.59	.00	2048.53	3608.73	1612.75
25.00	86.51	90.55	8309.59	1134.64	.00	2048.53	3609.00	1517.42
25.50	86.51	90.31	8220.12	1134.69	.00	2048.53	3609.23	1427.67
26.00	86.51	90.09	8135.85	1134.72	.00	2048.53	3609.42	1343.17
26.50	86.51	89.87	8056.50	1134.75	.00	2048.53	3609.58	1263.63
27.00	86.51	89.67	7981.79	1134.78	.00	2048.53	3609.72	1188.76
27.50	86.51	89.49	7911.46	1134.80	.00	2048.53	3609.84	1118.28
28.00	86.50	89.31	7845.27	1134.82	.00	2048.53	3609.94	1051.97
28.50	86.50	89.14	7782.95	1134.84	.00	2048.53	3610.02	989.56
29.00	86.50	88.98	7724.32	1134.85	.00	2048.53	3610.09	930.84
29.50	86.50	88.84	7669.13	1134.86	.00	2048.53	3610.15	875.58
30.00	86.50	88.70	7617.20	1134.87	.00	2048.53	3610.20	823.59

ELECTRIC VEHICLE INTERIOR HEATING AND COOLING LOAD MODEL
PROGRAM HCLoads

VEHICLE CONFIGURATION DESCRIPTION DATA

VEHICLE TYPE IS Tavan window van, PASSENGER, INT FINSH

WINDSHIELD TRANSMISSIVITY=	.84	WINDSHIELD AREA=	11.70
SIDE WINDOW TRNSMSIVTY=	.53	SIDE WINDOW AREA=	11.70
REAR WINDOW TRNSMSIVTY=	.84	REAR WINDOW AREA=	7.30
THETA SUN--VERTICAL =	67.50	THETA WINDSHIELD =	38.00
PHI SUN--HORIZONTAL =	90.00	THETA REAR WINDOW=	90.00
VEHICLE HEIGHT IN FEET=	5.40	ROOF WIDTH IN FT =	6.00
WINDSHIELD ABSORBTIVITY=	.08	ROOF AREA IN SQ FT=	60.00
SIDE WINDOW ABSRBTIVITY=	.41	SIDE PANEL AREA, SQ FT	40.00
REAR WINDOW ABSRBTIVITY=	.08	BODY PANEL ABSRBTIVITY	.90
FINISHED ROOF +/-	1.00	FINISHED SIDE PANEL +/-	1.00
ROOF INSUL THICKNESS, IN=	.00	BODY INSUL THICKNESS, IN=	.00
ROOF INSUL K, BTUH/FT-F=	.014	BODY INSUL K, BTUH/FT-F=	.014
INTERIOR SURFACE MASS, LB=	175.00	INT SURFACE AREA, SQ FT=	250.00
INTERIOR VOLUME, CUBIC FEET=	300.00		

VEHICLE OPERATING CONDITIONS

INTERIOR TEMP SETPOINT=	75.30	AMBIENT AIR TEMP=	89.00
INTERIOR REL HUM SETPOINT=	.28	AMBIENT AIR REL HUM=	.55
VENTILATION MAKEUP CFM=	20.00	NO OF VEH OCCUPANTS=	.00
VEHICLE SPEED, MPH=	25.00	INTERIOR SOAK TEMP=	140.00
INTERIOR AIR TEMP TIME CONST=	3.00	INSOLATION, BTUH/SQ FT=	215.00

STEADY STATE THERMAL LOADS

TOTAL STEADY STATE LOAD=	6042.45 BTU/HR
VENTILATION LOAD=	1386.71 BTU/HR
SENSIBLE VENTILATION LOAD=	295.92 BTU/HR
LATENT VENTILATION LOAD=	1090.79 BTU/HR
VENTILATION AIRFLOW=	20.00 CFM
ENTHALPY AMBIENT AIR=	39.16 BTU/LBM
ENTHALPY INTERIOR AIR=	23.75 BTU/LBM
METABOLIC LOAD=	.00 BTU/HR
SOLAR LOAD=	2048.53 BTU/HR
WINDSHIELD	1538.34 BTU/HR
REAR WINDOW	.00 BTU/HR
SIDE WINDOW(S)	510.20 BTU/HR
INSOLATION=	215.00 BTU/HR-SQ FT
CONDUCTION LOAD=	2607.20 BTU/HR
ROOF	1097.86 BTU/HR
SIDE 1 PANELS	453.94 BTU/HR
SIDE 2 PANELS	252.66 BTU/HR
SIDE 1 WINDOWS	272.48 BTU/HR
SIDE 2 WINDOWS	190.49 BTU/HR
WINDSHIELD	220.92 BTU/HR
REAR WINDOW	118.85 BTU/HR
ROOF EXTERIOR SURF TEMP=	111.90 DEG F

TRANSIENT THERMAL LOADS

TIME	TINTAR	TINSRF	QTOT	QVENT	QMETAB	QSOLAR	QCOND	QTRAN
.00	140.00	140.00	-2837.62	-18.96	.00	2048.53	-4867.20	.00
.50	130.07	140.00	10026.29	197.63	.00	2048.53	-3719.72	11499.84
1.00	121.66	139.41	12918.52	380.96	.00	2048.53	-2748.41	13237.43
1.50	114.54	138.35	15158.22	536.15	.00	2048.53	-1926.23	14499.76
2.00	108.52	136.94	16857.97	667.52	.00	2048.53	-1230.27	15372.19
2.50	103.42	135.24	18112.35	778.72	.00	2048.53	-641.16	15926.26
3.00	99.10	133.35	19000.70	872.84	.00	2048.53	-142.49	16221.82
3.50	95.45	131.31	19589.54	952.52	.00	2048.53	279.62	16308.87
4.00	92.35	129.18	19934.58	1019.97	.00	2048.53	636.93	16229.16
4.50	89.74	126.98	20082.35	1077.06	.00	2048.53	939.38	16017.38
5.00	87.52	124.77	20071.74	1125.38	.00	2048.53	1195.40	15702.43
5.50	85.64	122.55	19935.31	1166.29	.00	2048.53	1412.27	15308.21
6.00	84.06	120.35	19699.64	1200.92	.00	2048.53	1595.71	14854.47
6.50	82.71	118.19	19387.29	1230.23	.00	2048.53	1751.00	14357.53
7.00	81.57	116.08	19016.73	1255.04	.00	2048.53	1882.44	13800.71
7.50	80.61	114.03	18603.21	1276.04	.00	2048.53	1993.71	13284.93
8.00	79.80	112.04	18159.27	1293.82	.00	2048.53	2087.89	12729.03
8.50	79.11	110.12	17695.19	1308.87	.00	2048.53	2167.61	12170.17
9.00	78.52	108.27	17219.30	1321.61	.00	2048.53	2235.10	11614.05
9.50	78.03	106.50	16738.35	1332.39	.00	2048.53	2292.22	11065.20
10.00	77.61	104.81	16257.78	1341.52	.00	2048.53	2340.58	10527.15
10.50	77.25	103.19	15781.89	1349.25	.00	2048.53	2381.51	10002.60
11.00	76.95	101.64	15314.10	1355.79	.00	2048.53	2416.16	9493.62
11.50	76.70	100.17	14857.00	1361.32	.00	2048.53	2445.49	9001.66
12.00	76.49	98.78	14412.63	1366.01	.00	2048.53	2470.31	8527.77
12.50	76.30	97.45	13982.41	1369.98	.00	2048.53	2491.33	8072.57
13.00	76.15	96.19	13567.40	1373.33	.00	2048.53	2509.12	7636.42
13.50	76.02	95.00	13168.31	1376.18	.00	2048.53	2524.17	7219.42
14.00	75.91	93.87	12785.51	1378.58	.00	2048.53	2536.92	6821.48
14.50	75.82	92.80	12419.22	1380.62	.00	2048.53	2547.71	6442.35
15.00	75.74	91.79	12069.38	1382.34	.00	2048.53	2556.84	6081.65
15.50	75.67	90.83	11735.84	1383.80	.00	2048.53	2564.57	5738.93
16.00	75.61	89.93	11418.33	1385.04	.00	2048.53	2571.12	5413.64
16.50	75.56	89.08	11116.50	1386.08	.00	2048.53	2576.66	5105.22
17.00	75.52	88.27	10829.87	1386.97	.00	2048.53	2581.35	4813.02
17.50	75.49	87.51	10558.01	1387.72	.00	2048.53	2585.32	4536.44
18.00	75.46	86.80	10300.35	1388.35	.00	2048.53	2588.67	4274.79
18.50	75.44	86.12	10056.37	1388.89	.00	2048.53	2591.52	4027.43
19.00	75.41	85.49	9825.52	1389.34	.00	2048.53	2593.93	3793.71
19.50	75.40	84.89	9607.20	1389.73	.00	2048.53	2595.96	3572.97
20.00	75.38	84.32	9400.88	1390.05	.00	2048.53	2597.69	3364.60
20.50	75.37	83.79	9205.97	1390.33	.00	2048.53	2599.15	3167.96
21.00	75.36	83.29	9021.96	1390.56	.00	2048.53	2600.39	2982.48
21.50	75.35	82.82	8848.29	1390.76	.00	2048.53	2601.43	2807.56
22.00	75.34	82.37	8684.43	1390.93	.00	2048.53	2602.32	2642.65
22.50	75.34	81.95	8529.89	1391.07	.00	2048.53	2603.07	2487.22
23.00	75.33	81.56	8384.18	1391.19	.00	2048.53	2603.70	2340.75
23.50	75.33	81.19	8246.82	1391.29	.00	2048.53	2604.24	2202.76
24.00	75.32	80.84	8117.38	1391.38	.00	2048.53	2604.69	2072.78
24.50	75.32	80.51	7995.43	1391.45	.00	2048.53	2605.08	1950.36
25.00	75.32	80.20	7880.53	1391.51	.00	2048.53	2605.40	1835.08
25.50	75.31	79.91	7772.32	1391.56	.00	2048.53	2605.68	1726.54
26.00	75.31	79.64	7670.40	1391.61	.00	2048.53	2605.91	1624.34
26.50	75.31	79.38	7574.45	1391.64	.00	2048.53	2606.11	1528.16
27.00	75.31	79.14	7484.09	1391.68	.00	2048.53	2606.28	1437.60
27.50	75.31	78.91	7399.05	1391.70	.00	2048.53	2606.42	1352.39
28.00	75.31	78.70	7318.99	1391.72	.00	2048.53	2606.54	1272.19
28.50	75.30	78.49	7243.63	1391.74	.00	2048.53	2606.64	1196.71
29.00	75.30	78.30	7172.73	1391.76	.00	2048.53	2606.73	1125.70
29.50	75.30	78.13	7105.98	1391.77	.00	2048.53	2606.80	1058.87
30.00	75.30	77.96	7043.18	1391.79	.00	2048.53	2606.86	996.00

Appendix E

Detailed Cooling and Heating Performance Estimates for Vapor Cycle Variations

Table of Contents

E Detailed Cooling and Heating Performance Estimates for Vapor Cycle Variations	E-1
E.1 Baseline Belt Driven Vapor Compression System	E-1
E.1.1 System Design	E-1
E.1.2 System Cooling Performance	E-4
E.1.3 Heat Pump Cycle Operation	E-9
E.2 Variable Speed, Semi-Hermetic Compressor and Variable Speed Interior Blower	E-10
E.2.1 System Design	E-10
E.2.2 Steady State Cooling Performance	E-11
E.2.3 Variable Speed Compressor System Steady State Heat Pump Cycle Heating	E-20
E.3 Vapor Compression Cycle Cooling and Heating Performance During Transient Operation	E-21
E.3.1 Variable Speed Compressor System Transient Cooling Performance	E-23
E.3.2 Variable Speed Compressor System Transient Heating Performance	E-24

Table of Figures

Figure E-1	Baseline Constant Speed Belt Driven Compressor Based Vapor Compression System	E-2
Figure E-2	Parallel Flow/Flat Tube Condenser, Baseline Dimensions	E-3
Figure E-3	Baseline System Cooling Mode Steady State Capacity and Baseline Vehicle Steady State Thermal Load	E-6
Figure E-4	Baseline System and Variable Speed System COPs	E-8
Figure E-5	Steady State Cooling COP versus Ambient Temperature	E-8
Figure E-6	Steady State Heating Capacity versus Ambient Temperature	E-9
Figure E-7	Variable Speed Vapor Cycle Air Conditioner/Heat Pump Configuration	E-11
Figure E-8	Parallel Flow/Flat Tube Condenser - Increased Face Area Dimensions	E-15
Figure E-9	Ceiling Mounted Evaporator Unit	E-18
Figure E-10	Rear View of Ceiling Evaporator Concept	E-19
Figure E-11	Comparison of Steady State Cooling COPs for Vapor Cycle Variations at the Design Ambient	E-20
Figure E-12	Steady State Part Load Cooling COP Comparison of Vapor Cycle Variations at Moderate Ambient	E-20
Figure E-13	Steady State Heating COP versus Ambient Temperature	E-22
Figure E-14	Transient Cooling Capacity Versus Ambient Temperature	E-24
Figure E-15	Transient Cooling COP Versus Ambient Temperature	E-25
Figure E-16	Transient Heating Capacity Versus Ambient Temperature	E-27
Figure E-17	Transient Heating COP Versus Ambient Temperature	E-27

Table of Tables

Table E-1	Parasitic Power	E-4
Table E-2	Assumptions for Calculation of Baseline System Cooling Performance	E-5
Table E-3	Baseline Belt Driven Vapor Compression Steady State Cooling Performance	E-7
Table E-4	Assumptions for Calculation of Baseline System Heating Performance	E-10
Table E-5	Belt Driven Constant Speed and Displacement Vapor Compression System Steady State Heating Performance	E-7
Table E-6	Assumptions for Calculating Variable Speed Compressor Based System Cooling Performance	E-12
Table E-7	Variable Speed, Brushless DC Motor/Scroll Compressor Steady State Cooling Performance	E-13
Table E-8	Improvements in Steady State COP and Power Consumption for the Variable Speed System as Compared to the Baseline System ..	E-14
Table E-9	Variable Speed Scroll Compressor/Brushless DC Motor Vapor Compression System Condenser and Evaporator Improvements at the Phoenix Steady State Cooling Condition	E-16
Table E-10	Variable Speed Compressor and Interior Blower Improvements in COP and Power Consumption	E-17
Table E-11	Variable Speed Compressor Vapor Compression System Steady State Reversed (Heat Pump) Cycle Heating Performance	E-23
Table E-12	Variable Speed, Brushless DC Motor/Scroll Compressor Transient Cooling Performance	E-26
Table E-13	Variable Speed Compressor System Transient Heating Performance	E-26

E Detailed Cooling and Heating Performance Estimates for Vapor Cycle Variations

The subsections that follow present the estimated performance for a range of vapor cycle system design alternatives, beginning with a system derived entirely from production automobile air conditioning system components (except for the compressor drive motor). The heating and cooling performance is analyzed based on a design capacity meeting the thermal load characteristics presented in Section 2.1.2. These loads are representative of an electric mini-van or compact car with a relatively modest set of design measures to reduce the thermal loads, as described in Section 2.1.2. With this performance level as a baseline, vapor cycle design measures to improve the efficiency are examined (with the baseline vehicle thermal design retained). These measures are:

- Variable speed compressor drive -- allows better part load performance through more effective utilization of heat transfer surface and reduced parasitics and cycling losses. Also, increased compressor design capacity can be specified to meet lower ambient temperature heating loads, without significantly reducing cooling efficiency
- Increased condenser and evaporator frontal area and/or air flow rate. Raises evaporator, reduces condenser temperatures, reducing compressor input power, but parasitics may be increased.
- An evaporator and interior air blower arrangement aimed at allowing higher air flow rates at lower fan power, increasing efficiency through reduced compressor power and reduced parasitics.
- The performance of the preceding are estimated first based on steady state operation. Performance is also estimated for the initial part of a hot soak pull down or, in heating mode, cold start-up.

E.1 Baseline Belt Driven Vapor Compression System

E.1.1 System Design

A baseline vapor compression system consisting of available automotive hardware, was analyzed to generate both cooling and heating performance and to provide a basis of comparison with more advanced equipment. The major components and subassemblies are a compressor assembly, an ambient air coil assembly, and an interior coil assembly. A schematic of the baseline vapor compression system is shown in Figure E-1.

The compressor assembly consists of a compressor, DC motor, drive belt and associated mounting brackets. The Sanden scroll compressor was chosen for this analysis because of its high isentropic efficiency, approximately 80%, which is 20 points above typical state-of-the-art reciprocating automotive compressors. The compressor is driven by a constant speed brush type permanent magnet DC motor operating at traction battery

voltage. Typical DC motors in the 2-4 hp size range have an efficiency of approximately 80%. The DC motor drives the compressor through a poly-vee belt. The transmission loss for this type of configuration is 2%.

Figure E-1: Baseline Constant Speed Belt Driven Compressor Based Vapor Compression System

The ambient air coil assembly consists of the heat exchanger (condenser in cooling mode and evaporator in heating mode), the fan blade, fan motor and shroud. The outdoor coil, shown in Figure E-2, is a parallel flow design, (e.g., Modine PF condenser), which has flat parallel tubes with inserts to enhance refrigerant heat transfer. Each tube is brazed to two cylindrical headers and corrugated fins are brazed between the tubes to enhance air side heat transfer. The coil size is typical of condenser sizes found in mini-vans. In this analysis, the condenser in the Chrysler mini-van was used as a basis for establishing the face area, with the dimensions indicated in Figure E-2. The outdoor fan (including motor) is also typical of equipment installed on current mini-vans (Chrysler T-Van condenser fan). The fan and motor deliver 1100 CFM of cooling air @ 30 mph through the Modine based design.

Figure E-2: Parallel Flow/Flat Tube Condenser, Baseline Dimensions

The interior coil assembly includes the interior heat exchanger (evaporator during cooling mode and condenser during heating mode), the interior blower and expansion device. The interior coil modelled in this analysis is based on the GM G-Van evaporator assembly. This assembly delivers more airflow (263 CFM at maximum fan speed) than other evaporator assemblies we have encountered. This higher airflow will raise the evaporating temperature during cooling mode, increasing the efficiency of the

system. However, the increased airflow requires more motor power to drive the blower. During high cooling loads, the extra blower motor is offset by decreased compressor power.

The baseline system inefficiencies result from the belt drive system, DC drive motor, and cyclic operation. The transmission efficiency was assumed to be 98% and the DC motor efficiency 80% as previously discussed. The cyclic losses result from on/off operation when the thermal load is less than the vapor compression system capacity. During the off cycle, the outdoor coil fan and interior blower operate at the same power consumption while the clutch opens and the compressor drive motor power decreases to 180W at this no load condition (based on tests of current electric vehicle systems installed in EPRI funded electric vehicles). The cyclic losses are assumed to be 15% at 50% on time (or lower) and decrease linearly to 0 at 100% on time. This loss is only applied to motor power during the on time part of the cycle.

The electrical power consumption of all components other than the compressor DC drive motor comprise the parasitic power in the vapor compression system. These components and their power consumption values are listed in Table E-1.

Table E-1: Parasitic Power

Ambient Air Coil Fan	60 watts
Compressor Clutch	45 watts
Interior Blower	230 watts
Total	335 watts

E.1.2 System Cooling Performance

The baseline constant speed belt driven vapor compression system was sized to meet a steady state cooling load at the Phoenix design cooling condition (109°F/22% RH ambient). This cooling load was calculated to be 8720 Btu/hr for a mini-van having thermal design options recommended in Task 1, and as discussed in Section 3.0 of this report. The thermal design options for the mini-van include reduced ventilation air, PPG sungate glass or the equivalent on all windows, and insulated roof/body panels. The cooling load is calculated for a full solar load, 4 passengers and 45 CFM of ventilation of air at 109°F ambient temperature and a 75°F interior temperature set point. Table E-2 lists the assumptions used in calculating system performance at this design point.

The scroll compressor volumetric and isentropic efficiency are based on calorimeter test data supplied to Arthur D. Little by Sanden International, and are assumed to be constant over the range of conditions of interest. While modeling the compressor with constant efficiency is not precisely accurate, there is very little change in the compressor efficiency over the modest range of speed and inlet conditions applicable to this

Table E-2: Assumptions for Calculation of Baseline System Cooling Performance

• Constant compressor efficiency;
• 87.5% Scroll compressor volumetric efficiency;
• 80% Scroll compressor isentropic efficiency;
• Constant convective heat transfer coefficient for both the interior and outdoor coils;
• 30 mph vehicle speed
• 9°F superheat at evaporator exit;
• 10°F subcooling at condenser outlet;
• 98% belt transmission efficiency;
• 80% DC motor efficiency;
• 180 watts DC motor power consumption at no load;
• Cyclic losses as explained in a previous section
• 60 watts outdoor fan power consumption;
• 230 watts interior blower power consumption;
• 45 watts compressor clutch power consumption;
• 263 CFM interior blower airflow; and
• Thermal control options recommended in Topical Report #1.

analysis. The condenser subcooling and evaporator superheat are typical values for the equipment modeled in this analysis. Negligible changes in convective heat transfer coefficient with variations in refrigerant temperatures or air inlet conditions allow for the assumption of a constant value.

At the Phoenix condition cooling requirement, the vapor compression system operates at the following cycle conditions and performance:

- 55.3°F evaporator outlet air (supply air to the vehicle interior);
- 80.8°F evaporator inlet air (return air, 45 CFM of ambient make up air plus recirculated air from the vehicle interior);
- 42.5°F evaporating temperature;
- 127.5°F condensing temperature;
- 726 watts compressor shaft power (input to compressor, not motor input);
- 3.52 compressor shaft power COP; and
- 2.02 total electric input COP (including parasitic power).

The COP (coefficient performance) is the cooling capacity divided by the electric power input. If the vehicle thermal design options were omitted except for ventilation air restriction and current tinted glass used on all windows, the cooling load would increase to 11,800 Btu/hr for the same conditions. The compressor shaft power would increase to 1186 watts and the COP based on total electric input would decrease to 1.87, a 7.5% decrease in COP. The combination of increased load and decreased COP would result in 46% increase in power consumption.

Off design cooling performance of the belt driven vapor compression system can be calculated assuming constant motor/compressor speed operation. Table E-3 shows the performance of the belt driven system at several different ambient conditions, representative of the range of maximum design ambients across the continental U.S. A comparison of cooling capacity for continuous operation and cooling load as a function of ambient temperature is shown in Figure E-3. The increased cooling capacity and reduced cooling loads at ambient temperatures lower than 109°F will generally result in cyclic operation of the compressor. At the lower ambients, the evaporating temperature will decrease slightly, while the condensing temperature will decrease dramatically, increasing the refrigerant enthalpy difference across the evaporator and the system capacity, as shown in Table E-3 and Figure E-3. In addition, the temperature and pressure difference between evaporator and condenser is reduced which results in decreased compressor power. Figure E-4 illustrates this trend by comparing COP based on compressor shaft power vs. ambient temperature. The combination of increasing capacity and decreasing compressor power as the ambient temperature decreases, causes the system COP to increase as seen in Table E-3, assuming the system operates continuously with the compressor clutch engaged. When cyclic operation and parasitics are considered, the COP increases much more gradually as the ambient temperature decreases, then decreases with lower ambients, as shown in Table E-3 and Figure E-5. The major factor decreasing the COP is constant operation of the interior blower and outdoor fan, and the motor power consumption during the no load periods.

Figure E-3: Baseline System Cooling Mode Steady State Capacity and Baseline Vehicle Steady State Thermal Load

Table E-3: Baseline Belt Driven Vapor Compression Steady State Cooling Performance

Location/ Ambient	RH%	Supply Air °F	Return Air °F	Evap. Temp. °F	Superheat °F	Cond. Temp. °F	Subcool. °F	Compressor Shaft Power, Watts	Capac. Btu/hr	Load Btu/hr	COP Comp. Shaft Pwr.	COP Tot. Elec. Input ¹	COP Tot. Elec. Input ²
Phoenix, 109°F	22	55.3	80.8	42.5	9	127.5	10	726	8,720	8,720	3.52	2.02	2.02
100°F	34	54.2	79.3	41.2	9	118.5	10	663	8,970	8,020	3.96	2.22	2.07
Memphis, 98°F	45	54.0	78.9	41.0	9	116.5	10	650	9,015	8,770	4.06	2.27	2.23
Detroit, 91°F	51	52.5	77.7	39.5	9	108.9	10	592	9,165	7,320	4.54	2.48	2.17
85°F	50	51.0	76.7	38	9	103	10	542	9,085	6,268	4.91	2.59	2.04
80°F	50	50.5	75.9	37.5	9	98.2	10	508	9,295	5,269	5.36	2.77	1.88

Table E-5: Belt Driven Constant Speed and Displacement Vapor Compression System Steady State Heating Performance

Amb. °F	Supply Air Temp. °F	Return Air Temp. °F	Evap. Temp. °F	Superheat °F	Cond. Temp. °F	Subcool °F	Compr. Shaft Power Watts ³	COP Compr. Shaft Power ⁴	COP Total Elec. Input ³	Heat. Capacity Btu/hr	Heat. Load Btu/hr
47	105.10	70.2	34.3	3	120	10	666	4.39	2.47	9,980	1,635
37	99.3	68.5	25.7	2	112.7	8.8	593	4.35	2.39	8,799	2,751
14	87	64.6	6	2	96.5	5.5	459	4.08	2.03	6,390	5,318
-16	73.1	59.4	20.5	0	79.1	4	321	3.58	1.54	3,920	8,670

¹ For continuous operation, no cyclic losses.

² Including cyclic losses.

³ Continuous operation, clutch remains fully engaged.

⁴ Include cyclic losses.

Figure E-4: Baseline System and Variable Speed System COPs (Compressor Shaft Power Basis)

Figure E-5: Steady State Cooling COP (Electric input, including parasitics) versus Ambient Temperature

E.1.3 Heat Pump Cycle Operation

The baseline vapor compression cycle is switched into heating mode by a reversing valve (Figure E-1) which directs the refrigerant from the compressor outlet to the interior coil (now the condenser) rather than the ambient air coil (now the evaporator). The refrigerant flow proceeds through the expansion device into the outdoor coil and back to the compressor, as shown in Figure E-6.

Figure E-6: Steady State Heating Capacity versus Ambient Temperature

The heating mode analysis was completed with the compressor operating at the same speed determined for the design cooling point (Phoenix condition). The belt driven vapor compression system is not designed to deliver a specific heating performance, rather the heating capacity generated at a given ambient is a function of the system which is designed for a specific cooling performance. The heating performance was calculated for several ambient conditions for a mini-van with thermal design options installed in the vehicle. The vehicle heating load was calculated for no solar load, 3 passengers, 45 CFM of ventilation air and a 75°F interior set point. Table E-4 lists the assumptions used in calculating the vapor compression system heating performance.

Table E-4: Assumptions for Calculation of Baseline System Heating Performance

• Constant compressor efficiency;
• 87.5% scroll compressor volumetric efficiency;
• 80% scroll compressor isentropic efficiency;
• Constant convective heat transfer coefficient for interior and outdoor coils;
• 30 mph vehicle speed;
• 10°F condenser subcooling at maximum heating capacity (47°F ambient);
• Evaporator superheat varied slightly depending on conditions;
• 98% belt transmission efficiency;
• 80% DC motor efficiency;
• 180 watts DC motor power consumption at no load;
• Cyclic losses as explained in a previous section;
• 60 watts outdoor fan power consumption;
• 230 watts interior blower power consumption;
• 45 watts compressor clutch power consumption; and
• 263 CFM interior blower airflow.

The condenser (interior coil) subcooling was scaled depending on the coil capacity. The subcooling was assumed to be 10°F at 47°F ambient and scaled to changes in condenser capacity. The evaporator (outdoor coil) superheat was adjusted from 0-3°F depending on the evaporating and ambient temperature.

The heating performance of the baseline system is shown in Table E-5 for several ambient conditions. A comparison of heating capacity and vehicle thermal load versus ambient temperature are shown in Figure E-6. The baseline belt driven system capacity meets the thermal load at approximately 9°F. At any ambient temperature below this value, the system heating capacity is below the thermal load and at any ambient temperature above 9°F, the system has excess capacity at steady state, initiating cyclic operation. The very low capacity at the Minneapolis design condition (-16°F ambient temperature) requires a large resistance heater which could generate 4,560 Btu/hr. To resize the baseline system for increased capacity at lower winter ambient temperatures would oversize the system in cooling mode, increasing the losses during summer months. At steady state, at mild winter ambient temperatures (37-47°F), the COP decreases because of cyclic operation and fixed parasitics.

E.2 Variable Speed, Semi-Hermetic Compressor and Variable Speed Interior Blower

E.2.1 System Design

The variable speed system is essentially the same as the baseline belt driven system with the exception of the compressor/drive motor. A schematic of the system is shown in Figure E-7. The constant-speed belt driven scroll compressor assembly is replaced with a semi-hermetic, variable speed, brushless DC motor driven scroll compressor. The

brushless DC motor directly drives the scroll compressor and the assembly is mounted within an aluminum housing. The motor/compressor speed is controlled to maintain a passenger-set air delivery temperature. The overall motor and control electronics efficiency is 85% for this system. Parasitic power consumption is reduced by 45 watts with the elimination of the compressor clutch. This type of compressor assembly is currently produced in prototype quantities by Sanden International. These prototype units have a 33cc displacement scroll set, a maximum speed of 6000 RPM and a corresponding capacity of 18,000 Btu/hr at ASHRAE standard test conditions.

Figure E-7: Variable Speed Vapor Cycle Air Conditioner/Heat Pump Configuration

E.2.2 Steady State Cooling Performance

The variable speed vapor compression system was sized to meet the steady state cooling load in Phoenix (8720 Btu/hr) for a mini-van style vehicle under the same condition as the baseline belt driven system. The assumptions used in the calculations listed in Table E-6.

The refrigeration cycle operating conditions and system performance characteristics for the variable speed system at the design cooling load and ambient temperature are as follows:

- 55.3°F evaporator return air temperature;
- 80.8°F evaporator supply air temperature;
- 42.5°F evaporating temperature;
- 127.5°F condensing temperature;
- 726 watts compressor shaft power;
- 3.52 compressor shaft power COP; and
- 2.23 total electric input COP (including parasitic)

Table E-6: Assumptions for Calculating Variable Speed Compressor Based System Cooling Performance

• Constant compressor efficiency;
• 87.5% scroll compressor volumetric efficiency;
• 80% scroll compressor isentropic efficiency;
• Constant convective heat transfer coefficient for interior and outdoor coils
• 30 mph vehicle speed;
• 9°F evaporator superheat
• 10°F condenser subcooling;
• 85% DC motor/controller efficiency;
• 60 watts outdoor fan power consumption;
• 230 watts interior blower power consumption; and
• 263 CFM interior airflow.

The increased performance of the variable speed system compared to the baseline design improves the COP (total electric power input basis) by 10% and reduces the total power consumption by the same amount.

Table E-7 presents off design performance at several other ambient conditions. Steady state capacity which equals the steady state load is plotted as a function of the ambient temperature with the baseline system capacity data in Figure E-3. Compressor shaft power COP function versus ambient temperature is plotted in Figure E-4, again with the baseline data. The variable speed system COP (compressor shaft power basis) increases faster than the baseline as ambient temperature decreases. As the ambient temperature decreases, the compressor speed and refrigerant mass flow will decrease to meet the load, reducing the condensing pressure/temperature and increasing the evaporating temperature/pressure. The compressor pressure ratio, as well as compressor enthalpy difference, will decrease and the evaporator enthalpy difference will rise with these changes. The net effect is to increase the COP based on compressor shaft power for variable speed system faster than the baseline as ambient temperature decreases since the COP (compressor shaft power basis) is simply a ratio of the enthalpy change across the evaporator over the enthalpy change across the compressor.

Table E-7: Variable Speed, Brushless DC Motor/Scroll Compressor Steady State Cooling Performance

Location/ Ambient	RH%	Supply Air °F	Return Air °F	Evap. Temp. °F	Superheat °F	Cond. Temp. °F	Subcooling °F	Compressor Shaft Power, Watts	Cooling Load & Capacity Btu/hr	COP Comp. Shaft Power	COP Total Electric Input
Phoenix, 109°F	22	55.3	80.8	42.5	9	127.5	10	726	8720	3.52	2.23
100°F	34	55.5	79.3	42.5	9	116.4	10	558	8020	4.21	2.48
Memphis, 98°F	45	54.5	78.9	41.5	9	116.0	10	616	8770	4.17	2.53
Detroit, 91°F	51	56.0	77.7	43.0	9	105.5	10	414	7320	5.18	2.76
85°F	50	55.5	76.7	42.5	9	97.0	10	304	6268	6.04	2.74
80°F	50	57.5	75.9	44.5	9	89.9	10	210	5269	7.35	2.79
Variable Speed Interior Blower and Variable Speed Compressor											
Detroit, 91°F	51	53.5	78.6	40.5	9	105.6	10	437	7320	4.41	3.18
85°F	50	53.8	77.3	40.8	9	97.1	10	316	6268	5.81	3.31
80°F	50	53.8	76.1	40.8	9	90.0	6	233	5270	6.63	3.42

Figure E-5 plots the steady state COP based on total electric input as a function of ambient temperature. The baseline COP curve diverges from the variable speed COP curve, rapidly decreasing, as the ambient temperature approaches 80°F. However, the variable speed COP based on total electric input begins to level off at ambients near 80°F. In this area of operation, the parasitic power begins to dominate the power consumption and any change to improve compressor performance has a minor impact. The improvement in steady state COP based on electric input and power consumption for the variable speed system as compared to the baseline system is listed in Table E-7.

Further improvements in vapor compression system performance can be achieved by improving the performance of the condenser and evaporator. The condenser face area can be increased to cover more of the vehicle grill area. If the condenser face area is approximately doubled from 1.35 sq. ft. to 2.83 sq. ft. keeping the air face velocity constant, the vapor compression system performance would improve significantly. The larger parallel flow condenser is shown in Figure E-8. Table E-8 compares the system performance for the baseline, variable speed compressor and variable speed compressor with improved condenser at a Phoenix cooling condition. The assumptions used in the calculations are as follows:

- 2.83 sq. ft. condenser area;
- 2,300 CFM condenser airflow rate; and
- 60 watt condenser fan parasitic power.

Table E-8: Improvements in Steady State COP and Power Consumption for the Variable Speed System as Compared to the Baseline System

Ambient Condition	COP Improvement %	Power Consumption Improvement, Watts
109°F	10	120
100°F	20	188
98°F	14	137
91°F	27	211
85°F	35	230
80°F	49	268

The condenser fan parasitic power was not increased because motor/fan combinations are available which deliver the correct airflow with 2 fans mounted side by side, connected electrically in series. The COP and electrical power consumption improve by 20% over the baseline and 9% over the variable speed compressor system. The larger condenser reduces the condensing pressure which reduces compressor power consumption and total power consumption.

To reduce the parasitic power consumption of the interior blower, the interior blower motor could be replaced by a variable speed motor. This would eliminate the resistance block, which is typically used to control the interior fan speed, by dissipating power

Figure E-8: Parallel Flow/Flat Tube Condenser - Increased Face Area Dimensions

through different resistances to decrease the voltage to the blower motor, reducing the speed. The voltage can be reduced much more efficiently by DC/DC conversion, as in pulse width modulated speed control. To illustrate the improvements obtained with a variable speed interior blower, the following assumptions were made for the interior air blower:

- 200 CFM interior blower airflow;
- No resistance to decrease blower speed; and
- 100 watts interior blower power consumption.

All other assumptions remained the same as those listed in Table E-6. Several ambient temperatures were considered and the results are listed in Table E-9. The reduced interior airflow increased the compressor power slightly, but the parasitic power was reduced significantly. Table E-10 lists the improvements in COP based on total electric input and power consumption for a vapor compression system with a variable speed compressor and variable speed interior blower as compared to the baseline and variable speed compressor systems.

Table E-9: Variable Speed Scroll Compressor/Brushless DC Motor Vapor Compression System Condenser and Evaporator Improvements at the Phoenix Steady State Cooling Condition

System	Supply Air °F	Return Air °F	Evap. Temp. °F	Superheat °F	Cond. Temp. °F	Subcooling °F	Cap. & Load Btu/hr	Compressor Shaft Power, Watts	COP Comp. Shaft Power	COP Total Electric Input	% Improve. in COP Elec. Input ¹
Baseline Design	55.3	80.8	42.5	9	127.5	10	8720	726	3.52	2.02	--
Variable Speed Compressor	55.3	80.8	42.5	9	127.5	10	8720	726	3.52	2.23	10
Variable Speed Compressor with Improved Condenser	55.5	80.8	42.5	9	120.5		8720	650	3.93	2.43	20
Variable Speed Compressor with Improved Evaporator #1	56.5	79.4	43.5	9	127.5	10	8720	715	3.57	2.11	4
Variable Speed Compressor with Improved Evaporator #2	58.8	78.8	49.8	5	127.5	10	8720	639	4.0	2.35	16
Variable Speed Compressor with Improved Evaporator #2 and Condenser	58.8	78.8	49.8	5	120.2	10	8720	564	4.53	2.55	26
Variable Speed Compressor with Roof Evaporator	56.5	79.4	46.0	5	127.2	10	8720	683	3.74	2.90	44

¹ Relative to Baseline Belt Driven System

Table E-10: Variable Speed Compressor and Interior Blower Improvements in COP and Power Consumption

Ambient	COP - Total Electric Input Improvement, %		Power Consumption Improvement, Watts	
	vs. Baseline	vs. Variable Speed Compressor	vs. Baseline	vs. Variable Speed Compressor
91°F	46.5	15	314	103
85°F	62	21	345	115
80°F	82	23	370	102

The interior air handling units used in automobile air conditioning systems generally have a low air flow rate in relationship to the cooling capacity, and the evaporator has a small face area. As a result, the typical evaporating temperature is about 15°F lower than in building air conditioning systems, and a significant COP penalty (about 25%) results. Measures to increase the evaporator capacity and interior HVAC air flow rates would increase the evaporator temperature, and improve the COP, subject to the effects of increased air handling power.

If the evaporator design is modified to increase the face area and airflow by 33% and no improvements in duct/air delivery system design are made, the air handling power increase would be approximately 33%, based on the assumption that the pressure drop would increase in the ducts but also decrease because no heater core is present. The results are listed in Table E-9. The COP and power consumption improve by 4% over the baseline but decrease by 6% when compared to the standard variable speed system. The results show that if no measures are introduced to reduce airflow pressure drop, the improvements will have a negative impact.

If the evaporator design is modified to increase the face area and airflow rate by 50% but only increase the air handling power consumption by 20%, an increase the overall COP (total electric input power basis) results, as seen in Table E-9. However, improvements in the air delivery system to minimize the pressure drop would have to be developed. When this evaporator design is combined with an improved condenser, the improvement over the baseline in COP, and power consumption increases to 26%. The system characteristics are listed in Table E-9. The increased evaporator airflow rate increases the evaporating temperature and pressure and the improved condenser decreases condensing temperature and pressure which reduces the overall pressure ratio of the compressor and the compressor power consumption, improving the COP and system power consumption.

Finally, the last improvement considered for the evaporator is to reconfigure the evaporator and blower assembly for significantly reduced air flow restriction, for example the interior roof evaporator blower shown in Figures E-9 and E-10. A low RPM, low power blower could supply the required airflow through a rectangular shaped low profile evaporator. The evaporator design could have characteristics similar to the following:

- 15 in x 30 in x 1.5 in high coil;
- 4.69 ft² face area;
- Tube fin evaporator design;
- 25 watt interior blower; and
- 350 cfm evaporator airflow.

Figure E-9: Ceiling Mounted Evaporator Unit

When combined with a variable speed compressor based system, the performance could improve the COP) by 44% at the Phoenix design cooling condition, when compared to the baseline. System characteristics are listed in Table E-9. If the roof evaporator is combined with the improved condenser, the COP improvement at a Phoenix type cooling condition would be more than 50%, compared to the baseline belt driven system.

Figure E-10: Rear View of Ceiling Evaporator Concept

Figure E-11 is a bar chart comparing the COP (based on electric power input) of all the design options for a Phoenix cooling condition; Figure E-12 compares the COPs at a representative part load operating condition, at a relatively moderate 90°F ambient temperature. Enlarging the condenser size and improving evaporator performance can decrease compressor power requirements for large improvements in system performance at high ambients. However, a variable speed interior blower would decrease parasitic power consumption at low ambients and improve system performance in this operating regime. Combining evaporator, condenser and interior blower performance improvements would significantly improve system performance and greatly reduce power consumption over all ambient operating temperatures. As indicated by Figure E-12, larger percentage improvements in the COP are realized by the variable speed options at part load conditions.

Figure E-11: Comparison of Steady State Cooling COPs for Vapor Cycle Variations at the Design Ambient ("Phoenix" Design Ambient of 109°F)

Figure E-12: Steady State Part Load Cooling COP Comparison of Vapor Cycle Variations at Moderate Ambient (90°F)

E.2.3 Variable Speed Compressor System Steady State Heat Pump Cycle Heating

Steady state heat pump cycle heating characteristics for mini-van loads are summarized in Table E-11 for a variable speed compressor system at several ambient conditions, when the design capacity is set to meet the steady state cooling load requirement in Phoenix. The capacity at full speed as a function of ambient temperature is plotted in Figure E-13. The capacity of the variable speed system is slightly larger than the baseline system because the motor losses are dissipated by rejecting heat to the surrounding refrigerant as it passes through the windings before entering the scroll compressor. However, the system does not have adequate capacity to meet steady state heating loads below an ambient temperature of about 10°F. The flexibility of having variable speed allows the maximum compressor speed to be increased to meet lower ambient temperature heating loads without significantly penalizing the heating performance at higher ambients on the cooling performance. For example, the compressor speed during heating mode could be increased to meet the steady state heating load at ambient temperatures down to -5°F, (the heating load is 7,500 Btu/hr for the mini-van with the baseline thermal design. The heating cycle performance and system characteristics are listed at the bottom of Table E-11. System heating capacity is plotted as a function of ambient temperature in Figure E-12 and is represented by the bold line. The variable speed capability allows the capacity to follow the load line down to an ambient temperature of -5°F where the capacity begins to decrease with lower temperatures. The maximum amount of back up heat required is 2,420 Btu/hr or 710 watts at the Minneapolis design ambient (-16°F). The system COP based on total electric power input (heating capacity/total electric power) is plotted in Figure E-13 as a function of ambient temperature. Figure E-13 also includes the effect on the vapor cycle COP curve when back up electric resistance heat is included in the COP calculation at ambients below -5°F.

These results show large improvements in COP at mild steady state cooling conditions when the variable speed interior blower is used in the system. The improvement in heating mode is larger because the interior coil is now the condenser. Reduced interior air flow rates decrease parasitic power and lower the condensing temperature which reduces the compressor power requirement. The reduction in both parasitic and compressor power has a larger impact on heating mode COP than a reduction in only parasitic power that occurs in mild cooling conditions when the variable speed blower is used. This trend is illustrated in Figure E-13 and vapor compression system characteristics are listed in Table E-7.

Figure E-13: Steady State Heating COP (Total Electric Input) Versus Ambient Temperature

E.3 Vapor Compression Cycle Cooling and Heating Performance During Transient Operation

The variable speed compressor system using the condenser and evaporator assembly from the baseline belt driven system was analyzed to generate cooling and heating performance information during transient operation. Improvements (an increase in COP and a decrease in power consumption) in steady state performance by modifying the condenser and evaporator assembly will also occur during transient operation. However, to minimize cycle calculations, only the variable speed compressor system with the baseline condenser and evaporator were considered for transient cycle analysis. The transient loads, both heating and cooling, were calculated for the same conditions and thermal design options as discussed in Section 3. The interior temperature and thermal load are averaged from output of the electric vehicle space conditioning program HCLOADS for the first 20 minutes when considering a six minute transient time constant.

Table E-11: Variable Speed Compressor Vapor Compression System Steady State Reversed (Heat Pump) Cycle Heating Performance

Location/Ambient	Supply Air °F	Return Air °F	Evap. Temp. °F	Superheat °F	Cond. Temp. °F	Subcooling °F	Heating Load Btu/hr	Heating Capacity Btu/hr	Compressor Shaft Power, Watts	COP Comp. Shaft Input	COP Total Electric Input
Variable Speed Operation @ Full Speed (Maximum Compressor Speed Sized to Meet Steady State Phoenix Cooling Condition)											
47°F	106.5	70.2	34.3	3	120.0	10	1635	10380	666	4.57	2.83
Los Angeles, 37°F	100.5	68.5	25.9	2	114.2	9	2751	9141	602	4.45	2.68
Detroit, 14°F	87.9	64.9	6.1	2	97.9	5.5	5318	6650	467	4.17	2.32
Minneapolis, -16°F	73.8	59.4	-20.5	0	79.9	4	8670	4111	323	3.73	1.80
System Performance with Sizing for -5°F Steady State Heating Load and Normal Variable Speed Operation											
Los Angeles, 37°F	78.1	68.5	33.1	2	82.2	9	2750	2750	102	7.90	1.88
Los Angeles, 37°F ¹	79.1	66.5	33.1	2	80.2	9	2750	2750	98	8.22	2.77
Detroit, 14°F	83.2	64.6	7.4	2	91.1	6	5320	5320	343	4.54	2.25
-5°F	87.5	61.3	-13.1	0	98.7	8	7500	7500	638	3.44	2.10
Minneapolis, -16°F	81.3	59.4	-22.7	0	90.6	6.5	8670	6250	545	3.36	1.97
Minneapolis, -16°F ²	89.7	59.4	-22.7	0	90.6	6.5	8670	8670	545		1.56**

¹ Includes variable speed interior blower

² Includes resistance heat

E.3.1 Variable Speed Compressor System Transient Cooling Performance

The variable speed compressor system was not designed to provide a specific performance during transient cooling periods. The system simply provides a cooling capacity that is dependent on equipment sized for steady state heating and cooling loads, and the ambient conditions. Table E-12 shows the system performance at three conditions for two system sizings; one to meet a Phoenix cooling load; and one to meet a 5°F ambient temperature heating load. Figures E-14 and E-15 illustrate cooling capacity and COP based on total electric input as a function of ambient temperature. The variable speed system sized to meet the -5°F ambient heating load has a 30-40% advantage in capacity at extreme transient cooling loads (high ambients). However, the extra capacity is at the expense of a large increase in power consumption. One possible system design would be to allow the variable speed compressor system to overspeed in transient cooling for a limited period (10 - 20 minutes). The overspeed value would equal the speed required to meet the -5°F ambient heating load. Once the time period was exceeded the system would slow to the design cooling speed which is the speed required to meet the steady state cooling load in Phoenix. The time period of overspeed could be sensitive to ambient temperature. As the ambient temperature decreases below 90°F, the time period for overspeed would decrease since the transient cooling load begins to approach the capacity of the variable speed system sized for a steady state Phoenix cooling load.

Figure E-14: Transient Cooling Capacity Versus Ambient Temperature

Figure E-15: Transient Cooling COP (electric input including parasitics) Versus Ambient Temperature

E.3.2 Variable Speed Compressor System Transient Heating Performance

The performance of the variable speed compressor system during transient periods is summarized in Table E-13. Figures E-16 and E-17 show transient capacity and COP based on electric power input versus ambient temperature for systems operating with resistance heat on and off. The large difference between transient load and capacity can be partially made up by solar radiation, on days when overcast is not heavy. Solar radiation would heat the vehicle interior and decrease the transient heating load.

Table E-12: Variable Speed, Brushless DC Motor/Scroll Compressor Transient Cooling Performance

Location/ Ambient	RH%	Supply Air °F	Return Air °F	Evap. Temp. °F	Super- heat °F	Cond. Temp. °F	Sub- cooling °F	Compressor Shaft Power, Watts	Cooling Capacity Btu/hr	Cooling Load Btu/hr ¹	COP Comp. Shaft Power	COP Tot. Elec. Input
Variable Speed Operation @ Maximum Compressor Speed to Meet Steady State Power												
Phoenix, 109°F	22	60.4	93.7	47.4	9	129.0	10	750	9520	13,460	3.71	2.38
Detroit, 91°F	51	55.7	85.6	42.7	9	110.2	10	596	9600	10,670	4.72	2.84
80°F	50	52.7	81.8	39.7	9	98.7	10	513	9591	8,970	5.48	3.14
Transient Operation at Compressor Speed Required to Meet Steady State Heating Load at -5° Ambient												
Phoenix, 109°F	22	53.5	93.7	39.5	9	136.7	10	1251	12507	13,460	2.92	2.08
Detroit, 91°F	51	50.5	85.6	37.5	9	118.5	10	1038	13263	10,670	3.74	2.57

Table E-13: Variable Speed Compressor System Transient Heating Performance

Location/Ambient	Supply Air °F	Return Air °F	Evap. Temp. °F	Superheat °F	Cond. Temp. °F	Subcooling °F	Compressor Power, Watts	Heating Capacity Btu/hr	Heating Load Btu/hr ¹	COP Comp. Shaft Power	COP Total Electric Input
Minneapolis, -16°F	57.7	35.9	-23.5	0	67	6	444	6225	19,720	4.11	2.25
Minneapolis, -16°F ²	66.1	35.9	-23.5	0	67	6	444	6225	19,720		1.21 ²
-5°F	67.6	41.4	-13.8	0	78.8	8	537	7490	17,200	4.09	2.38
-5°F	76.1	41.4	-13.8	0	78.8	8	537	7490	17,200		1.34 ²
Detroit, 14°F	84.3	49.4	2.3	2	99.2	8	732	9990	12,850	4.00	2.54
Detroit, 14°F ²	92.8	49.4	2.3	2	99.2	8	732	9990	12,850		1.89 ²
Los Angeles, 37°F	89.5	56.6	25.1	2	103.5	8	556	9396	7,590	4.95	2.92

¹ 20 minute average transient load

² Includes electric resistance heat to make up the difference between the load and the heat pump capacity

Figure E-16: Transient Heating Capacity Versus Ambient Temperature (System Sized to Meet Steady State Heating Load at -5°F)

Figure E-17: Transient Heating COP Versus Ambient Temperature

END

**DATE
FILMED**

6 / 22 / 93