DOE/PC/89774--T8

A-2

Effects of Catalytic Mineral Matter on CO/CO₂
Temperature and Burning Time for Char Combustion

APR 01 1993

RECEIVED

MAY 02 1993

DOE/PC/89774--T8

DE93 012276

Prof. John P. Longwell
Prof. Adel F. Sarofim

Chun-Hyuk Lee
Prof. Changhe Chen

Quarterly Progress Report No. 13
October-December, 1992
Reference Grant # DE-FG22-89PC89774

Prepared for

Jeffrey C. Bogdan
U.S. Department of Energy
Pittsburgh Energy Technology Center
P.O. Box 10940, MS 921-165
Pittsburgh, Pennsylvania 15236-0940

by

Massachusetts Institute of Technology
Department of Chemical Engineering
Cambridge, Ma 02139

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

Introduction

The high temperature oxidation of char is of interest in a number of applications in which coal must be burned in confined spaces. These include: the conversion of oil-fired boilers to coal using coal-water slurries, the development of a new generation of pulverized-coal-fired cyclone burners, the injection of coal into the tuyeres of blast furnaces, the use of coal as a fuel in direct-fired gas turbines and in large-bore low-speed diesels, and entrained flow gasifiers. In addition, there is a need to understand the temperature history of char particles in conventional pulverized-coal-fired boilers to better explain the processes governing the formation of pollutants and the transformation of mineral matter.

The temperature of char particle burning is the product of a strongly coupled balance between particle size and physical properties, heat transfer, surface reactivity, CO/CO₂ ratio and gas phase diffusion in the surrounding boundary layer and within the particle. In addition to the effects of particle temperature on burning rate, it has major effects on ash properties and mineral matter vaporization. Measurements of the temperature of individual burning char particles have become available in recent years and have clearly demonstrated large particle-to-particle temperature variations which depend strongly on particle size and on particle composition. These studies, done with pulverized coal, can not determine the CO/CO₂ ratio produced at the char surface or the catalytic effects of mineral matter in the individual char particles. Consequently, it has generally been assumed that CO is the only product of the carbon-oxygen reaction and that CO₂ is formed by subsequent gas phase reaction. More recent work, however, has pointed out the need to take CO₂ production into consideration in order to account for observed particle temperatures.

The importance of the CO/CO₂ ratio of carbon oxidation products is illustrated by examination of the heats of reaction for formation of these two products:

The heat released by formation of CO_2 is a factor of 3.5 higher than for CO so the temperature of a particle will depend strongly on the CO/CO_2 ratio produced. If gas diffusion through the boundary layer is fast, increased direct production of CO_2 produces a higher temperature and a higher burning rate. If the supply of oxygen to the surface is limited by diffusion through the boundary layer, production of CO_2 consumes half as much carbon as production of CO so carbon consumption rate is reduced even though temperature may be somewhat higher.

A few theoretical approaches have been attempted to model gas phase reactions using global reaction kinetics. Due to importance of CO oxidation in the boundary layer and its subsequent heat and mass transfer, we need to develop a gas phase model incorporating full reaction kinetics, heat, and mass transfer. In this report, effects of oxygen disassociation on heat transfer and modeling results of boundary gas phase reactions are reported.

Theory

Due to nonlinearity and high temperature, there is a need to develop an efficient method of evaluating integration of nonlinear terms in Galerkin Finite Elements Method.

(i) Conservation equation for species i

$$\rho_g v_r \frac{\partial Y_i}{\partial r} = -\frac{1}{r^2} \frac{\partial}{\partial r} (r^2 \rho_g Y_i V_i) + R_i$$

(ii) Energy balance equation for the gas phase

$$\rho_g C_{p,g} v_r \frac{\partial T}{\partial r} = \frac{1}{r^2} \frac{\partial}{\partial r} \left(r^2 \lambda_g \frac{\partial T}{\partial r} \right) - \rho_g \sum_{i=1}^n (Y_i V_i C_{p,i}) \frac{\partial T}{\partial r} - \sum_{i=1}^n R_i H_i$$

During the process of partial integration of Eq(i) and Eq(ii), we need to evaluate terms like following.

$$\int f(T(r), Y_i(r)) * \alpha_i(r) \Phi^i \Phi^j r^2 dr$$

To solve the problem, it is essential to evaluate these terms. The difficulty is, however, f is highly dependent on temperature and mass fractions of each species. If the function f represents terms like $\rho_g, \lambda_g, C_p, H_i$, and v_r , we can think of these as continuous piecewise constants.

Therefore, if the temperature and mass fraction distribution are given by initial guesses, $f(r)$ can be calculated at each point and the averaged value of $f(r)$ will be used for corresponding interval. $Y_i(r)$, $T(r)$ can be calculated, and new values will be used to update $f(r)$.

If $f(r)$ represents a reaction term, it needs special consideration due to the exponential dependence on temperature. If a linear combination of temperature or mass fraction is used to represent nodal value of reaction rate, the whole integration simplifies to be following by using the fact that only $\Phi^k(r_k) = 1$.

$$\begin{aligned} & \int R \left(\sum_{i=1}^N \alpha_i(r) \Phi^i \right) * \Phi^j r^2 dr \\ &= \int \sum_{k=1}^N R \left(\sum_{i=1}^N \alpha_i(r_k) \Phi^i(r_k) \right) \Phi^k * \Phi^j r^2 dr \\ &= \int \sum_{k=1}^N R(\alpha_k(r_k)) \Phi^k * \Phi^j r^2 dr \end{aligned}$$

This interpolation approach not only proved to be convenient but also gave numerical results that appear to be consistent with the behavior that would be expected¹

Results

Due to the high CO + OH reaction rate, we are having difficulty in convergence at high temperatures. As the reaction term grows and reaches to a size comparable to the diffusion term, numerical stability is affected and the convergence radius shrinks. We are in the middle of debugging, but we may need to use a Newton method with a very good initial guess or to incorporate a time dependent term.

With the full reaction rate, the program begins to diverge between 1400K-1500K. For qualitative purposes, temperature and mass fraction distribution curves by reducing gas phase reaction rate are shown in Fig.1 and Fig.2. The carbon consumption rate by solid phase reaction has been set to 0.075gC/cm²s. The surface temperature and bulk gas temperature are 2500K and 1700K. The partial pressure of oxygen is 0.8 atm. The gas phase reaction rate is calculated by setting CO concentration 10⁻¹⁰ to reduce CO+OH reaction rate. Due to the reduced CO oxidation rate, the mass fraction distributions of CO

Fig.1 $T(r)$ and $Y_i(r)$ at gas phase boundary layer

$(T_p=2500K, T_g=1700K, r_c=0.075gC/cm^2s)$

Fig.2 $Y_i(r)$ at the gas phase boundary layer

$(T_p=2500, T_g=1700K, r_c=0.075gC/cm^2s)$

and CO₂ are mainly a function of solid phase reaction rate. CO and CO₂ generated from solid phase reaction diffuse from the particle. We can see the major portion of gas phase reaction is confined to the region near the particle where temperatures are high enough ($T > 2400\text{K}$). The same tendencies can be seen for both stable species and radicals. Accurate results will be obtained by using full gas phase reaction rate.

Due to the instability of laser heating from the bottom of the chamber (reported earlier), we changed the laser heating method. CO₂ laser beam is now introduced from one side and the reflected beam from a concave mirror is focused in the center of the chamber. Balancing the beam intensities for both sides are now completed. However, the particle is not stable due to the laser power fluctuation and the control system. Further refinements are on the way.

Future Work

Modeling work will be completed during the next two quarters. And analysis based on the results from full gas phase model will be made and the effects of important parameters will be studied. Professor Chen will perform experimental measurements of CO₂/CO ratio using the electrodynamic balance.

References

1. J.C. Cavendish and Se H. Oh, "A Computationally Efficient Galerkin Technique for Approximating Transient Diffusion-Reaction Equation in Composite Media", *The Chemical Engineering Journal*, 17 (1979)

Nomenclature

'g' means gas mixture in the boundary layer

'i' means the i-th species in the gas mixture

[symbol]

$C_{p,i}$ specific heat of 'i' th species

$C_{p,g}$ gas mixture specific heat at constant pressure

H_i specific enthalpy

R, R_i mass production rate

R_o particle radius

r radial coordinate

r_c carbon consumption rate [gC/cm²s]

T temperature of the gas phase

T_o temperature at t=0

T_p particle temperature

t time

v_r fluid velocity in 'r' direction

V_i diffusion velocity of 'i' th species

X_i mole fraction

Y_i mass fraction

λ_g thermal conductivity

Φ basis function for Galerkin finite element method

ρ_g density of the gas mixture in the boundary layer

END

**DATE
FILMED**

6 / 3 / 93