The Mission: The Office of Transportation Technologies (OTT) is charged with long-term, high-risk, and potentially high-payoff research and development of promising transportation technologies that are unlikely to be undertaken by the private sector alone. OTT activities are designed to develop an advanced technology base within the U.S. transportation industry for future manufacture of more energy-efficient, fuel-flexible, and environmentally sound transportation systems. OTT operations are focused on three areas: advanced automotive propulsion systems including gas turbines, low heat rejection diesel, and electric vehicle technologies; advanced materials development and tribology research; and research, development, demonstration, test, and evaluation (including field testing in fleet operations) of alternative fuels.

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

This publication is one of a series of documents on the Conservation and Renewable Energy programs sponsored by the U.S. Department of Energy. An overview of all the programs is available, entitled *Programs for Research, Development, and Utilization of Conservation and Renewable Energy Technologies*. In addition, individual program overviews are available for each of the following offices:

- Utility Technologies
- Industrial Technologies
- Building Technologies
- Technical and Financial Assistance

Copies of any of these documents can be obtained by writing:

- Solar Energy Research Institute
- Technical Inquiry Service
- 1617 Cole Blvd.
- Golden, CO 80401-3393

Mapping the Route to Improved Transportation Technologies.....

Travel from one place to another, or transportation, consumes a tremendous amount of energy in our fast-paced society. In the 1970s, the oil crises created long lines at the gas pump, raised fuel costs significantly, and contributed to accelerated inflation. During that decade, finding alternatives to petroleum-based fuels and developing energy-efficient conservation technologies took on a new importance and major development efforts began. Today,

investigation of the most promising avenues leading to energy security and energy efficiency continues.

The United States has made significant progress in improving transportation energy efficiency since 1974. The average new car travels more than 12 miles farther on a gallon of fuel, commercial aircraft fly the same number of passenger miles on 30% less fuel, and trucks and trains transport the same amount of freight on 20% less fuel. These impressive gains in fuel efficiency have helped to slow oil consumption, but there is still much room for improvement.

In 1973, just before the oil crises, the United States imported 34% of its oil. Now, we are importing about 50%. An accompanying 15% rise in gasoline and diesel fuel consumption over the same period accounts for most of the import increase. This increase in consumption is directly related to the fact that the number of autos and trucks registered in the United States rose from approximately 98 million in 1970 to 189 million in 1990. Increasing numbers of these vehicles are the less fuel-efficient light trucks and high-performance cars preferred by today's consumers. In addition, vehicles are traveling more miles than ever before at faster, less fuel-efficient speeds.

The consumption of transportation goods and services represents about 15% of the total gross national product. About \$101 billion is spent annually on new automobiles and about \$77 billion on fuel and oil. For the average citizen, transportation accounts for

The consumption of transportation goods and services represents about 15% of the total gross national product.

There has been a dramatic improvement in average miles per gallon of new vehicles over the last 17 years.

MASTER

More vehicles are traveling more miles than ever before on our nation's highways.

More vehicles are traveling more miles than ever before on our nation's highways.

a significant share (approximately 13%) of household expenses. In addition, oil and motor vehicle imports are a major contributor to U.S. trade deficits. These high import levels pose a serious threat to the nation's energy security and economic strength and also represent a major challenge to the competitiveness and technological leadership of the United States in the area of motor vehicle production. And, the indirect costs of pollution, congestion, and accidental deaths and injuries resulting from America's reliance on the automobile impose a substantial cost burden on our society.

More than 63% of the petroleum used in our country is consumed in transport operations. The environmental consequences of this consumption are of increasing concern. The transportation sector is a major contributor to air pollution. Automobiles and light trucks alone produce 20% of the carbon dioxide (CO₂) emitted in the United States each year. Carbon dioxide is believed to be directly related to global climate change. Unburned

hydrocarbons, oxides of nitrogen (NO_x), and carbon monoxide (CO)—all by-products of automotive fuel combustion—are the major components of urban smog. In the United States, 75% of the CO comes from the automobile. The environmental and health issues directly related to our use of petroleum fuels must be addressed.

The Office of Transportation Technologies (OTT) of the U.S. Department of Energy (DOE) is addressing the complex issues of energy security, environmental stability, and economic growth as they relate to our transportation sector. The goals of OTT are twofold. The first is to improve the efficiency of the U.S. transportation sector by developing electric vehicle technologies and advanced turbine and diesel technologies with alternative fuel capabilities. These advanced propulsion systems will be highly energy efficient and will operate on a varied menu of fuels. A second goal, in concert with the engine research, is to promote the development of cost-effective alternative fuels derived from biomass and other renewable energy resources. Working closely with representatives from the engine, vehicle, parts, and fuel supply industries, OTT has identified specific technology needs that will lead to the attainment of these objectives.

Photo courtesy of Jerry Cleveland

Much of the smog over downtown Denver, Colo., can be attributed to automobile emissions.

Much of the smog over downtown Denver, Colo., can be attributed to automobile emissions.

OTT's research objectives focus on the two largest segments of the transportation sector: (1) automobiles and light-duty trucks and vans and (2) heavy-duty trucks and buses. Roughly 64% of all the transportation petroleum consumed in the United States is pumped into automobiles and light-duty trucks and vans. Heavy-duty trucks and buses consume another 15%. By focusing research and development (R&D) efforts in these two areas, even small gains in efficiency can produce large paybacks for the taxpayer's funding dollar. A 10% reduction in gasoline consumption in the U.S. automobile and light-duty vehicle fleet, attainable in the near term through increased efficiency, could save owners of new vehicles billions of dollars.

OTT objectives are ambitious and wide-ranging. They include:

- Increasing vehicle fuel efficiency by as much as 35% by 2010 and 100% by 2030
- Developing electric propulsion and battery system technology that will stimulate commercial production of electric vehicles with 100-mile ranges by 1995 and 250-mile ranges by 2010
- Developing and evaluating methanol-fueled fuel cell technologies for transportation applications; performance will be comparable to conventional engines with the added benefit of reduced emissions
- Developing a technology base for industry to use in building an infrastructure for the production, conversion, distribution, and use of alternative transportation fuels from biomass and other renewable resources
- Ensuring that air quality and environmental concerns are incorporated into policies governing the commercialization of new transportation technologies
- Encouraging industry and university research in energy-related technologies through expanded outreach activities, use of national laboratory user facilities, and educational fellowships and sabbaticals

Automobiles and light-duty trucks and vans consume roughly 64% of all transportation petroleum used in the United States each year.

- Developing an enabling technology base in high-performance materials needed for industry to implement more efficient transportation technologies.

OTT works closely with the Department of Transportation (DOT), the General Services Administration, and the Environmental Protection Agency (EPA) to ensure that legislatively mandated goals regarding alternative fuels, reduced emissions, and clean air are met.

OTT is structured to reflect the end-user orientation of DOE's organization and to effect timely technology transfer to industry. Three units comprise the office: (1) the Office of Alternative Fuels, which includes the Biofuels Systems Division and the Fuel Utilization Data and Analysis Division; (2) the Office of Propulsion Systems, which includes the Electric and Hybrid Propulsion Division and the Advanced Propulsion Division; and (3) the Office of Transportation Materials. The synergism of the research conducted under the three units of OTT, as well as that carried out by investigators from other government agencies, industry, and universities, holds promise for resolving our nation's transportation problems.

Through Alternative Fuels Research. . .

Past conservation practices and fuel-efficient vehicles have not been enough to decrease our nation's consumption of oil. Domestically produced alternative fuels are needed to safeguard U.S. energy security. Attention must also be paid to the environmental consequences of using such fuels. OTT's Office of Alternative Fuels considers these issues important and focuses on two major areas of development: biofuels systems research and fuel utilization data and analysis. Biofuels systems research centers on the production (growth) and conversion of biomass feedstocks into liquid fuels for transportation use, particularly alcohol fuels such as ethanol and methanol. In the fuel utilization data and analysis group, efforts are focused on establishing a comprehensive data base to demonstrate the environmental, economic, and performance

characteristics of alternative fuels. This effort will cover research on fuels including ethanol, methanol, compressed and liquefied natural gas (CNG and LNG), diesel fuel substitute from vegetable oils, liquid propane gas (LPG), and hydrogen.

Biofuels Systems Research

Biofuels are solid, liquid, and gaseous fuels derived from plant materials and wastes. The transportation sector's infrastructure is set up to use fuels in liquid form, making liquid biofuels an industry preference. By 2000, biofuels from nonfood crops and municipal solid waste could potentially cut our oil imports by 15%-20%, increasing U.S. energy security and giving American farmers alternative cash crop options. With proper crop management, production of biomass-fuel feedstocks can also reduce the net greenhouse gases from auto emissions. This reduction occurs because plants require CO₂ for growth, creating a "carbon cycle" when plant-derived fuels are burned in vehicle engines.

The Biofuels Systems Division is developing biomass feedstock production and conversion processes that combine to create pathways for the commercial production of economic, efficient, renewable energy fuels. These pathways integrate biomass feedstocks, which include woody and herbaceous energy crops, aquatic energy crops, municipal solid waste, and wood and agricultural residues, with thermochemical or biochemical conversion processes to produce ethanol, methanol, gasoline, diesel, and gaseous fuels. DOE is entering into a Memorandum of Understanding with the Department of Agriculture to conduct cooperative research in these areas.

Because plants require CO₂ for growth, a "carbon cycle" is created when fuels made from plants are burned in vehicle engines.

The first step in the biomass-to-fuel process requires the proper selection and successful cultivation of biomass feedstocks. The primary focus of biomass feedstock research is on the development of "energy crops." Energy crops are fast-growing hardwood trees and grasses that can be converted to liquid and gaseous fuels through new technology processes. The majority of DOE's terrestrial energy crops research is conducted by or through Oak Ridge National Laboratory (ORNL) in Oak Ridge, Tenn. ORNL researchers and their subcontractors are developing short-rotation woody crops and herbaceous, nonfood crops that display manageability and produce high yields at low costs. High yields must be achieved to guarantee a constant fuel supply if biomass fuels are to supplant a significant portion of the fossil fuels consumed in the United States.

An Oak Ridge National Laboratory scientist stands between rows of superior, two-year old poplar trees. Note that weed-free conditions are maintained.

Scientists involved in the short-rotation woody crops (SRWC) program have selected several species, suited to various regions across the United States, for genetic improvement, physiological characterization, and economic analysis to determine their suitability for large-scale production. Black locust, silver maple, sweetgum, sycamore, and poplar species all hold promise for achieving the program goal of an average of 10 dry tons per acre per year at a cost of \$2.00 per million Btu of energy produced. Researchers in the Pacific Northwest and in Hawaii have already reported yields in this range with hybrid poplar and eucalyptus crops, respectively.

In addition to SWRC, herbaceous energy crops—forage crops, grasses, and legumes—are promising candidates for liquid fuel production and for high-value chemical production as well. Herbaceous crops are very productive on a wide range of sites. Also, more is known about their growth and genetic characteristics because of previous in-depth agricultural studies. And unlike SRWC, they can be grown and harvested with conventional agricultural equipment.

DOE's herbaceous energy crops program (HECP) focuses on seven selected species. Field trials of these species have produced information on management costs, biomass production, and chemical composition. Thus far, perennial switchgrass has produced high yields (almost 9 dry tons/acre) in both the Southeast and Midwest, even under very dry conditions and with little added fertilizer. Likewise, annual sorghums have shown very high yields across the same region (more than 12 tons/acre in Indiana). Annual sorghums generally outproduce all other species under good growing conditions. However, the perennial grasses are much less sensitive to adverse conditions such as drought.

In addition to studies of annual and perennial grasses and legumes, the HECP includes a minor study on the production of oilseed crops for conversion to a diesel fuel substitute. Approximately 100,000 acres will be planted in winter rapeseed in the Southeast and Midwest this year, mostly for use in the cooking oil industry. But the plantings will be beneficial to the HECP study in terms of crop yield and management information. Rapeseed oil-to-fuel conversion is a one-step

Domestically produced alternative fuels are needed to safeguard U.S. energy security.

Energy cane, a relative of sugar cane, shows promise as a high-yield herbaceous energy crop for the Deep South.

process called transesterification that produces a substitute similar to diesel fuel derived from petroleum. In the Southeast, rapeseed readily adapts to a fall planting schedule, providing farmers with a second viable crop in addition to traditional summer crops.

The second, and equally important, step in the biomass-to-fuel process is the development of cost-effective, high-yield conversion processes. Alcohol fuels (ethanol and methanol) can be produced from biomass through either biochemical or thermochemical processes. Current research focuses on the biochemical conversion of biomass to ethanol and the thermochemical conversion of biomass to methanol.

Ethanol fuels are not new. Each year about 850 million gallons of ethanol are produced in the United States. Much of that ethanol is used as a gasoline additive to produce gasohol, a blend of 10% ethanol with 90% gasoline. This ethanol is produced primarily from corn. However, use of woody and herbaceous energy crops will provide a plentiful,

low-cost feedstock for the production of ethanol and other fuels.

It is estimated that more than 2.5 trillion tons of cellulosic biomass are produced annually in the United States. This resource includes not only energy crops but forest residues and wastes, agricultural residues, and municipal solid waste (which has a high percentage of cellulose) as well. This biomass resource could be converted to 300 billion gallons of ethanol per year, displacing approximately 200 billion gallons of gasoline with a domestically produced, environmentally favorable fuel.

The majority of DOE's ethanol research is performed through the Solar Energy Research Institute (SERI) in Golden, Colo. SERI scientists have developed ways to process the cellulose and hemicellulose (long chains of sugar molecules) in biomass feedstocks into sugars, which can then be fermented into ethanol. The composition of the biomass feedstock from energy crops is 75% cellulose and hemicellulose. The remaining 25% is mainly lignin, with trace amounts of organics and ash. Although the lignin

The simultaneous saccharification and fermentation process holds great promise as a cost-effective method of converting biomass to ethanol.

cannot be broken down, or hydrolyzed, to form sugars as can the cellulosic portion of the feedstock, it can be used as a fuel to run the conversion process or converted to other fuels or chemicals. The goal is to produce ethanol at a cost of \$0.55/gal by 1995.

Methanol is another alternative fuel being investigated by OTT researchers. Originally a by-product of charcoal production, today methanol (wood alcohol) is produced primarily from natural gas. It can also be made from biomass and coal. OTT's biomass-to-methanol research focuses on the thermal gasification of the biomass feedstock to form a synthesis gas (composed primarily of hydrogen and CO) followed by a catalytic conversion process to produce methanol. Raw synthesis gas must be cleaned and conditioned before it is converted to methanol. This process includes converting tars formed during biomass gasification and correcting the ratio of hydrogen and carbon monoxide to the desired level of 2 to 1. Researchers at SERI are examining catalysts that can simultaneously reduce synthesis gas tars and produce the desired hydrogen-carbon monoxide mix. The cost goal of the biomass-to-methanol conversion program is \$0.55/gal by 2000.

Ethanol and methanol have similar advantages and disadvantages in transportation fuel applications. They are both higher octane fuels than gasoline—methanol's high performance is recognized by race car drivers around the world. In dedicated-fuel vehicles, ethanol and methanol produce less ozone-forming emissions. Their major disadvantages are low energy density (a gallon of ethanol contains about two-thirds the energy of a gallon of gasoline) and unfavorable cold start characteristics resulting from their higher vaporization temperatures. The cold start problem can be overcome with the addition of a small amount of gasoline to the mix. Currently, both fuels are being used in blend form in areas of the United States—ethanol as gasohol (10% ethanol; 90% gasoline) in Iowa and the Midwest and methanol as M85 (85% methanol; 15% gasoline) in California.

The President takes off for a test drive of the Nebraska Corn Board's E-85 car. The vehicle is fueled by a blend of 85% ethanol and 15% gasoline.

Fuel Utilization Data and Analysis

DOE is also exploring other alternative fuel options including natural gas, LPG, hydrogen, and reformulated gasoline.

Compressed natural gas is already in use in transportation applications worldwide. More than 700,000 vehicles are operating on CNG in 38 countries—30,000 in the United States. Current natural gas vehicles (mostly vehicle conversions) can have favorable emissions characteristics, even when compared to alcohol fuels. CNG produces lower hydrocarbon and CO emissions than methanol in current applications and dedicated-CNG vehicles are expected to be even more environmentally sound. CNG vehicles can be cheaper to operate than gasoline-fueled vehicles because the fuel cost is generally less than gasoline, and maintenance costs can be less because CNG causes less corrosion and engine wear. CNG has disadvantages as well: it reduces power (a 3%-5% loss of efficiency in converted

Photo courtesy of Natural Fuels Corp.

Above – Compressed natural gas is one of several alternative fuels being investigated by DOE.
Below – Compressed natural gas vehicles have very favorable emissions characteristics.

vehicles); it requires cumbersome fuel tanks; and it is gaseous (as opposed to more common liquid transportation fuels) in composition.

OTT's Office of Alternative Fuels is pursuing research on CNG and other alternative fuels in response to the Alternative Motor Fuels Act (AMFA) passed by Congress in 1988. The act directs DOE and other government agencies to "assist clean-burning, non-petroleum transportation fuels to reach a threshold level of commercial application and consumer acceptability at which they can successfully compete with petroleum-based fuels."

Light-duty, heavy-duty, and bus vehicle evaluation programs are all being started in response to the AMFA mandate. Other studies will provide data on the performance, fuel economy, safety, emissions, and operating and maintenance costs of alcohol and natural gas fuels.

Government, industry, and university researchers have collected enormous amounts of alternative fuels data over the last several years. OTT has established two mechanisms to collect, verify, and analyze these and newly generated alternative fuels data: the Alternative Fuels Utilization Program (AFUP) and the Alternative Fuels Data Center. Industry played a large role in developing the long-range program plans for AFUP and the center. Representatives from DOE, ORNL, and SERI made numerous visits to industry, universities, and other laboratories to review the issues in alternative fuels utilization.

Under the AFUP, several technical areas are still under development to further improve the costs, efficiency, and performance of alternative-fueled vehicles. AFUP researchers are working to improve engine lubrication, wear, and emissions control in light-duty vehicles. AFUP researchers are also involved in developing emission control systems, ignition components, and fuel formulations for heavy-duty vehicles.

The newly created Alternative Fuels Data Center at SERI will be responsible for collecting and analyzing all available data on alternative fuels utilization. The staff of the center will design and operate a computerized system for the storage and retrieval of all information and develop a simple way to access the data base. The center staff will also establish a uniform data collection protocol for future tests and demonstrations. Reports

and data summaries will be published regularly to disseminate reliable and accurate information and to promote this much needed, unbiased user facility. Several private organizations have already expressed interest in having the center involved in their alternative fuels demonstration programs—yet another example of how industry and government can work together beneficially.

Propulsion Systems Research...

Innovative, energy-efficient propulsion system designs can further improve vehicle fuel economy as well as reduce the harmful environmental effects generated by the nation's transportation sector. Two advanced propulsion system approaches are being investigated by OTT's Office of Propulsion Systems: electric and hybrid propulsion systems and advanced heat-engine propulsion systems.

Electric and Hybrid Vehicle Research

OTT's Office of Propulsion Systems is actively working to address concerns about poor air quality and national dependence on foreign oil. Legislative efforts to mitigate these problems are also increasing. In some areas, such as California, legislative action could have a major impact on the demand for electric vehicles. The office's Electric and Hybrid Propulsion (EHP) programs cover a broad spectrum of research, development, testing, and evaluation aimed at providing industry with an advanced electric vehicle technology base—one that will furnish the private sector with the capability for large-scale commercialization of electric vehicle (EV) technology in the near future.

Electric and hybrid vehicles, along with those powered by fuel cells, present attractive alternatives to conventional petroleum-based vehicles. They emit no exhaust fumes because they have no exhaust system. None is needed because they do not burn petroleum fuels. They do, however, require advanced propulsion systems and sophisticated batteries. OTT and the many private sector participants in the programs have made significant progress in EV battery and fuel cell propulsion system technologies in the past several years, but a number of key

technological barriers must still be overcome, particularly those relating to battery and fuel cell improvements.

These improvements are crucial to reducing initial costs and increasing vehicle range, performance, and reliability, necessary for broad market acceptance of EVs as a viable transportation alternative. The EHP research and development program, in cooperation with private industry, concentrates on improving battery and fuel cell technologies as well as advancing propulsion system technology. Currently, near-term research and development programs are aimed at developing a battery design for light-duty vans, commonly used fleet vehicles that are a likely niche market for EV technology. Several battery couples, concepts, and configurations are being examined for incorporation into such light-duty vans and automobiles—sodium-sulfur and lithium-metal sulfide concepts are two of the most promising.

Batteries are the "fuel tanks" of electric vehicles. Efficient, durable, safe batteries are essential to EV technology development and widespread market acceptance. Several promising battery concepts have been selected as possible EV fuel storage systems. These technologies are being developed, in cooperation with many private sector and industry researchers, for evaluation and proof-of-concept testing.

Under the OTT-designated management of Sandia National Laboratories, Chloride Silent Power, Limited is developing a proof-of-concept, sodium-sulfur battery for EV applications. The battery holds promise to more than double the driving range of conventional lead-acid batteries, going from a 60-mile range to a range of approximately 150 miles. The battery also promises power

capabilities to accelerate a minivan, such as the ETX-II mentioned below, from 0 to 60 mph in 20 seconds. The technology still has some obstacles to overcome, however. OTT is addressing safety and environmental concerns, as well as disposal/recycling issues.

Unlike the sodium-sulfur battery, lithium-metal sulfide battery technology offers an intrinsically safe chemistry. DOE and the Electric Power Research Institute have a joint contract with SAFT America to complete the development and evaluation of a full-scale, proof-of-concept lithium-metal sulfide battery for EV applications. An experimental module has shown promising test results with a range of 150 miles. Both of these battery technologies are new configurations that will require significant refinement before they enter the commercial market.

Lead-acid battery technology is currently on the commercial market, however. But these lead-acid batteries do not provide the power and durability necessary for EV applications. Under the management of Argonne National Laboratory (ANL), Johnson Controls, Inc., is developing an advanced lead-acid battery for EVs. The objective of this effort is to improve the performance and life of lead-acid batteries to meet the mission requirements of EVs for near-term commercialization.

Lightweight, energy-efficient propulsion systems are also needed to maximize battery potential in EVs. Ford Motor Company and General Electric are the major subcontractors for the power train development of OTT's ETX-II, a light-duty electric van geared toward application in an urban/suburban environment. The ETX-II program is aimed at advancing electric propulsion technology through the integrated development of a sodium-sulfur battery subsystem (discussed above) and single-shaft alternating current (ac) power train technology. The ETX-II incorporates a rear-mounted motor and transaxle, a transistorized-inverter power module, and a multiprocessor system controller capable of regulating all the complex electrical and mechanical functions of the

New sodium-sulfur (top) and lithium-alloy/iron sulfide (bottom) batteries promise increased reliability for electric vehicle performance.

Performance goals for the prototype ETX-II include a range of 100 miles at a top speed of 60 mph.

vehicle. Performance goals include a range of 100 miles, a top speed of 60 mph, and an energy consumption of 0.4 kWh/mile.

Fuel cells also provide the advantages of reduced emissions, greater energy efficiency, and petroleum independence when compared to conventional internal combustion engines. DOE has a jointly funded program with DOT and the South Coast Air Quality Management District in Los Angeles to develop, evaluate, and show the feasibility of a methanol-fueled, phosphoric-acid fuel cell/battery technology being tested in three small urban buses. These buses will be evaluated by DOE and DOT. Fuel cells, generally heavy and bulky, are appropriate for such heavy-duty applications but are considered impractical for light-duty or passenger vehicle applications.

OTT is addressing this issue through research on the proton exchange membrane (PEM) fuel cell. PEM fuel cells offer the potential of significant advantages over the phosphoric-acid fuel cell because of faster

start-up capabilities, a 40% reduction in volume, and an estimated 25% reduction in weight. They may be less costly to produce. These advantages make the PEM fuel cell a likely candidate for passenger car applications, a major transportation market.

Testing and evaluation of these electric and hybrid propulsion concepts is integral to their commercial acceptance.

OTT and private sector laboratory testing is conducted at the Idaho National Engineering Laboratory (INEL). INEL has dynamometer and battery testing facilities to evaluate technologies in simulated driving cycles. These capabilities allow researchers to characterize performance and determine whether field testing or additional development is required. Batteries are subjected to the actual electrical power demands of EVs on a dynamometer and in test-bed vehicles. Auxiliary electronic systems are characterized in a realistic environment and advanced electric drive systems are tested on the dynamometer, track, and road.

Under the management of INEL, DOE conducts a cost-shared field test program with fleet operators from private industry, laboratories, universities, and other federal agencies across the nation. These fleet operators collect and analyze EV operating and maintenance data, identifying solutions to operational problems in the EV fleets.

Heat Engine Propulsion Research

Gas turbine and diesel engine technologies are a major focus of OTT's Office of Propulsion Systems research. Gas turbine engines produce relatively low noxious gas emissions and can run on a wide variety of petroleum and nonpetroleum fuels. They are easy to start in cold weather and run quietly. Gas turbines are low-maintenance engines requiring very little lubrication, no oil changes, and no radiator fluids or antifreeze. They also have the potential for high fuel economy if operating temperatures can be increased. Diesel engines, like gas turbines, are also unsurpassed for reliability and service life

Maglev technology could replace aircraft operations on selected routes.

They are the work horses of the heavy-duty transport sector.

The key to acceptable fuel economy for automotive gas turbines is operation at much higher temperatures (up to 2500°F) than conventional engine materials can withstand. The Office of Propulsion Systems sponsors a long-term effort in this area as a cornerstone of its advanced heat engine propulsion goals. The Advanced Turbine Technology Applications Program (ATTAP) intends to establish the technological

readiness of ceramic, high-temperature gas turbine engines. The feasibility of a ceramic, gas turbine engine was demonstrated in the Automotive Gas Turbine (AGT) Program, completed in 1987. The ATTAP extends that effort, taking full advantage of existing government-industry development teams, test rigs, and experimental engines. Allison Gas Turbine Division of General Motors (GM) and Garrett Auxiliary Power Division of the Allied-Signal Aerospace Corporation are both continuing in their roles as system integrators.

The AGT-5 ceramic automotive engine (right), developed by Allison, will be seated in GM's Chevy Express concept car (below).

Allison is developing a ceramic automotive engine, the AGT-5, which will have an operational life of 3500 hours at temperatures up to 2500°F. The AGT-5 will be placed in GM's Chevy Express concept car for demonstration.

Garrett is also incorporating ceramic components capable of withstanding extremely high temperatures and increased impact forces into its advanced engine designs. Both Garrett and Allison are developing ceramic turbine rotors, perhaps the most difficult to perfect of all ceramic engine components.

Ceramic engines that operate at such high temperatures (2500°F) are able to achieve high-cycle efficiencies and have the potential to meet OTT program goals by improving fuel economy at least 30% over conventional internal combustion engines. They can also meet or exceed federally regulated emission and noise level standards. Vehicle mileage of advanced turbine engines incorporating ceramic components is predicted to be approximately 36 mpg, compared to 25 mpg for a conventional engine in a 3000-lb vehicle. Mileage is expected to increase to 42 mpg using diesel fuel.

Ceramic components also play a major role in the advanced diesel engine development being pursued by the Heavy-Duty Transport Technology (HDTT) Program.

Conventional diesel engine systems use state-of-the-art metals technology and operate at relatively low temperatures and pressures. Fuel economy improvements can be obtained through the application of emerging technologies such as the low heat rejection (LHR) diesel engine concept; better exhaust gas utilization; advanced synthetic liquid lubrication; low-friction and low-wear materials; precision cooling of thermal critical areas, allowing elimination of the engine block water-cooling system; and computer-controlled fuel injection.

The LHR diesel engine design is based on reducing the heat loss to the engine block water-cooling system. This increases the energy available in the exhaust gas and

This ceramic turbine rotor, from Garrett, is one of the components being developed for the Advanced Turbine Technology Applications Program.

Photo courtesy of Garrett Auxiliary Power Division

decreases areas that require cooling. This concept uses thermal insulation of the combustion chamber components and exhaust passages as well as operation with higher lubricating oil sump temperatures. LHR engine concepts require the use of advanced materials and lubrication to provide reliability and durability at high, material peak-surface temperatures (in excess of 2000°F).

Under a cost-shared contract, the Detroit Diesel Corporation has developed a single cylinder test engine for the LHR concept. The engine features advanced electrohydraulic fuel injection and electrohydraulic valve actuation. It also incorporates ceramic valves, valve guides, and fire deck, as well as a ceramic air-gap exhaust port, and a hybrid (conventional/synthetic) lubrication system.

Cummins Engine Company and Caterpillar Tractor Company also have important cost-shared contracts under the HDTT program. Both companies are performing research on in-cylinder component development. Their designs eliminate the engine block water-cooling system; the efforts are now in the rig test phase. Fabrication, testing, analysis, and redesign efforts are planned to effectively integrate components into a fuel-efficient engine that meets emissions standards.

Compliance with federal and state emissions regulations is a major concern for the diesel engine industry. Diesel engines have a problem with particulate and NO_x emissions resulting from incomplete fuel combustion

The ceramic piston cap and valves shown here are being evaluated by Detroit Diesel Corporation for use in low heat rejection diesel engines.

and the presence of lubricant oils in the fuel mixture. The major challenge in managing these emissions is their simultaneous reduction because favorable adjustment of one type tends to unfavorably affect the other. To bring the industry into compliance, the HDTT program is directing several cost-shared projects with industry on high-temperature liquid lubricants, ceramic component friction and wear, diesel engine heat-transfer model development, and effective combustion and durability operation on natural gas and methanol fuels.

... and Transportation Materials Research.

The mission of OTT's Office of Transportation Materials is to support the development of an enabling technology base in materials and tribology needed for more efficient transportation technologies such as conventional and advanced heat engines. In fulfilling its mission, the Office of Transportation Materials works closely with the Office of Propulsion Systems and the Office of Alternative Fuels within OTT to identify materials limitations needing to be resolved in order to improve conventional engine efficiency and to facilitate the development of advanced heat engines. The research programs of OTT offices are coordinated and structured to meet overall program objectives.

Materials research activities currently are focused in four programmatic areas: ceramic technology, materials technology (other than structural ceramics), tribology, and the High Temperature Materials Laboratory (HTML). Oak Ridge National Laboratory (ORNL) manages the HTML and also serves as the technical manager of the office's ceramic technology program. Argonne National Laboratory (ANL) provides technical management of the tribology program.

The Office of Transportation Materials is focusing on ceramics for high-temperature gas turbine and low heat rejection (LHR) diesel engines. Monolithic and composite ceramic engine component and ceramic coating technologies are being developed for these applications because of the capabilities of ceramics to withstand the high temperatures and aggressive environments found in these engine systems. Compared to metal engine parts, ceramics are lightweight as well as heat and wear resistant. Ceramics can also provide lower friction and protection of metal engine parts.

Ceramic coatings and components exhibit some characteristics, however, that prevent their widespread use in automotive engine manufacture. Foremost among these are brittleness, which can lead to premature fracture or failure under steady-state and cyclic operating conditions, and high-temperature oxidation or corrosion. OTT researchers and others are working to overcome these and other limitations in order to realize the potential benefits of ceramic engines.

Ceramic technology development is supported through the Ceramic Technology for Advanced Heat Engines (CTAHE) project at ORNL. The goal of the project is to establish a technology base that will enable private industry to supply reliable, cost-effective

The research programs of OTT offices are coordinated and structured to meet overall program objectives.

Photo courtesy of ANL

A researcher at Argonne National Laboratory examines a ceramic rotor before x-raying it to detect flaws.

ceramics for use in engine manufacture and in other energy-conversion applications. The objectives of the project include improved and unique materials synthesis and processing technology to enhance the reliability and toughness of ceramic parts; ceramic wear and thermal barrier coatings; improved and new joining technology to produce reliable ceramic attachments; development of an understanding of the physical and chemical mechanisms that control the friction and wear of ceramic materials and coatings under heat engine operating conditions; and identification and understanding of the mechanisms that control the long-term mechanical reliability of structural ceramics in engine environments.

The CTAHE project includes a balanced emphasis on the three technology areas considered necessary to achieve reliability

in structured ceramics: materials and processing, design methodology, and data base development and life prediction. The research is conducted by industry (receiving more than half the government R&D funding), government laboratories, and universities. The industry contracts are generally cost shared, with industry participation at an average of 25%.

Ceramics research is conducted in coordination with OTT engine propulsion programs. Several ceramics companies are experimenting with candidate materials and processes in efforts to develop ceramic materials for rotors, stators, and other engine parts that will withstand the high temperature and stress environments found in these engines.

Some of the most promising materials being investigated include silicon nitride, silicon carbide, and oxide ceramics. The Norton Company and GTE are working to develop and demonstrate significant improvements in processing methods, process controls, and in-process nondestructive evaluation to produce reliable silicon nitride ceramics for advanced heat engines operating at 2500°F. The objective of both Norton and GTE is to minimize flaw size and number in finished molded-ceramic test specimens. The flaws limit ceramic strength and durability. OTT efforts in developing new materials, insulating coatings, joining techniques, and design analysis methods for advanced heat engines may contribute to annual fuel savings on the order of 30 million barrels of petroleum annually by 2000 (and possibly as much as 275 million barrels annually by 2010).

In addition to ceramics research, the Office of Transportation Materials' researchers are seeking to identify and resolve materials-related problems that may occur with the use of alternative fuels in internal combustion engines. Methanol, ethanol, natural gas, and other alternative fuels require special and different materials and engine adjustments in order to deliver their optimum environmental and performance benefits. One aspect of these materials technology problems is dealing with the near-term development of

Photo courtesy of ORNL

Assorted tubing and ceramic heat engine components, as well as cutting tools, can be made from Oak Ridge National Laboratory's fracture-resistant, whisker-reinforced ceramics.

cost-effective solutions to problems with fuel injectors caused by the use of alternative fuels in conventional engines. Another effort is being conducted to identify materials solutions to containment and handling problems associated with alcohol and natural gas fuels as well as the special materials requirements for electric propulsion and the transportation system infrastructure.

Ceramics, high-temperature, and alternative fuels materials responsibilities are augmented with several transportation-related tribological studies. Tribology is the science of lubrication, friction, and wear. The goals of this research are to develop a thorough knowledge of the mechanisms of lubrication, friction, and wear, and to exploit them for use in energy-efficient, cost-effective transportation technologies. Lubrication technologies initiated at Pennsylvania State University, under the DOE Energy Conversion and Utilization Technologies (ECUT) tribology program, are being developed by Detroit Diesel Corporation under the HDTT program. The research is applicable to high-performance engines that operate at temperatures too high for conventional liquid lubricants. The technique developed by Penn State researchers delivers the lubricant to hot engine surfaces in a vapor or gas phase and provides stable, effective lubrication despite the high temperatures.

Much of the testing and evaluation required for the verification of these materials, lubricants, and their analytical models and data bases is conducted through the High Temperature Materials Laboratory. The HTML is a user-oriented facility staffed by interdisciplinary professionals for use by industry, university, and government researchers. Six user centers make up the HTML: materials analysis, high-temperature mechanical properties, high-temperature X-ray diffraction, physical properties, ceramic specimen preparation, and residual stress measurements. Many of the industrial and academic users lack access to the specialized equipment available at the HTML, and few are associated with institutions that have such a variety

of state-of-the-art instrumentation in one central location. A permanent staff is on hand to assist private sector researchers at all times, and office accommodations for visiting researchers are available. Private research conducted at the HTML is intended to produce open literature publications and can be done at no charge. Proprietary investigations can also be performed, but on a full-cost recovery basis.

Researchers at the High Temperature Materials Laboratory at Oak Ridge National Laboratory are loading ceramic samples into a tensile tester.

Technology Transfer and Education — Paving the Road to a Cleaner, More Secure Future

OTT's fundamental technology transfer strategy is to use related industries as researchers for DOE's transportation technology efforts. More than 20% of the funding for OTT research comes from cost-shared government-industry contracts, a clear indication of the confidence and faith that industry has in OTT's renewable energy and conservation programs. Most of the research is performed by non-federal agencies, primarily in industry but also at universities and state and local government institutions.

OTT's mechanism for technology transfer provides these institutions with hands-on experience and training in advanced transportation technology fields.

Each autumn, OTT convenes contractors' coordination meetings where research results are reported and discussed. OTT participates in cooperative and cosponsored symposia and conferences with scientific and trade associations such as the Electric Vehicle Council, the Society of Automotive Engineers (SAE), and the American Ceramics Society. Annual reports to Congress on research progress are also prepared and made available to the public.

Several user facility activities are also managed for DOE under the OTT banner. The High Temperature Materials Laboratory and the Idaho National Engineering Laboratory are just two examples of facilities where private sector scientists are encouraged to participate in private or cooperative

investigations and to use staff and state-of-the-art equipment often unavailable to them.

Education is also an integral part of OTT's technology transfer efforts, in accordance with DOE's objectives to

- Further the educational skills and opportunities of today's student scientists and engineers
- Stimulate the application of conservation and renewable energy technology
- Generate interest in alternative vehicle technology and in science and engineering careers.

DOE is a cosponsor of student competitions such as the 1989 Methanol Challenge, the 1990 GM Sunrayce, and the upcoming SAE Natural Gas Vehicle Challenge. Thousands of students are involved in the planning, construction, and testing of cars entered in these competitions. And, as they construct their entries, they are learning about alternative fuel systems, fuel economy, emissions regulations, and innovative design concepts. Although most of the students participating in the competitions are mechanical, chemical, and electrical engineering college majors, the spectators are of all ages. Americans love their cars, and young and old alike are curious about these "new-fangled" machines. But all will agree that some new approach to transportation power is necessary. The Office of Transportation Technologies is rapidly progressing toward that new approach to getting from one place to another, leading our nation farther down the road to energy security and energy efficiency.

The University of Michigan "Sunrunner" team won first place in the DOE-cosponsored GM Sunrayce held in July 1990. The race was just one of the many energy-related educational activities supported by DOE.

Key Contacts

Deputy Assistant Secretary,
Transportation Technologies
U.S. Department of Energy
CE-30

Director, Office of Alternative Fuels
U.S. Department of Energy
CE-32

Director, Office of Propulsion Systems
U.S. Department of Energy
CE-33

Director, Office of Transportation Materials
U.S. Department of Energy
CE-34

U.S. Department of Energy
Forrestal Building
1000 Independence Avenue, SW
Washington, DC 20585

END

DATE FILMED

02 / 08 / 91