**Coal Slurry Combustion Optimization
On Single Cylinder Engine
Task 1.1.2.2.2
Combustion R&D**

Topical Report

Work Performed Under Contract No.: DE-AC21-88MC23174

**For
U.S. Department of Energy
Office of Fossil Energy
Morgantown Energy Technology Center
P.O. Box 880
Morgantown, West Virginia 26507-0880**

**By
GE Transportation Systems
2901 East Lake Road
Erie, Pennsylvania 16531**

September 1992

TABLE OF CONTENTS

	Page
1.0 Introduction	5
2.0 Experimental Hardware, Data Reduction & CWS Fuels	5
2.1 Test Engine, Instrumentation & Data Reduction	5
2.2 CWS Fuels Used	6
3.0 Test Results	7
3.1 The "Delayed Ignition" of CWS Fuel at Full Engine Load	7
3.2 Wall Impingement of CWS Fuel at Engine Full Load	9
3.3 CWS & Pilot Injection Timing Effect at Engine Full Load	10
3.4 Combustion Chamber Configuration	10
3.5 CWS Fuel Injection Pressure Effect	11
3.6 Coal Particle Size	12
3.7 Injector Hole Plugging	13
3.8 Low Inlet Manifold Pressure (MAP) Effect	13
3.9 Engine Lower Loads Combustion	13
4.0 Conclusions	15
References	16
Figures	
Appendices	
I Injection Timing Maps at Engine Full Load	
II Fuel Injection Rates & Relative Engine Performances of Nozzles	
III Engine Performance & Emissions Results	
IV Heat Release Records of All Test Runs	

LIST OF FIGURES

Figure 2.1.1	CWS Test Cylinder Combustion Chamber Layout
Figure 2.1.2	Accumulator Fuel Injection System Schematic
Figure 3.1.1	Combustion Results of "Delayed Ignition"
Figure 3.1.2	Temperature and Pressure of "Delayed Ignition"
Figure 3.2.1	CWS Injection Timing Effect
Figure 3.2.2	Combustion Results of CWS Injection Timing Change
Figure 3.2.3	Schematic of CWS Injection Wall Impingement
Figure 3.2.4	Photo of Piston Crown Fuel Impingement (1)
Figure 3.2.5	Photo of Piston Crown Fuel Impingement (2)
Figure 3.3.1	Fuel Injection Timing Maps
Figure 3.4.1	Effect of CWS Injector Hole Number
Figure 3.4.2	Schematic of Injector Spray Included Angle
Figure 3.4.3	Effect of CWS Injector Spray Included Angle
Figure 3.5.1	Effect of CWS Fuel Injection Pressure
Figure 3.5.2	Effect of CWS Fuel Injection Pressure on Combustion
Figure 3.5.3	Percent of Fuel Burnt at Various Injection Pressures
Figure 3.6.1	Effect of Fuel Particle Size on Combustion
Figure 3.6.2	Percent of Fuel Burnt of 5 & 8 Micron Fuels
Figure 3.6.3	Combustion of 8 Micron Fuels from Various Sources
Figure 3.6.4	Combustion of 8 Micron Fuel Using Larger Hole Nozzle
Figure 3.7.1	Effect of Partially Plugged Injector on Combustion
Figure 3.7.2	Effect of Fuel Dilution on Combustion
Figure 3.7.3	Unsuccessful Combustion Result of Heated Fuel
Figure 3.8.1	Effect of Inlet Air Pressure on Combustion
Figure 3.8.2	Effect of Inlet Air Pressure on Temperature and Pressure

Figure 3.9.1 Combustion Heat Release at Lower Load

Figure 3.9.2 Heat Release and Cylinder Pressure at Lower Loads (1)

Figure 3.9.2 Heat Release and Cylinder Pressure at Lower Loads (2)

1.0 Introduction

Under the sponsorship of the U.S. Department of Energy, Morgantown Energy Technology Center, GE Transportation System has been conducting a proof of concept program to use coal water slurry (CWS) fuel to power a diesel engine locomotive since 1988. Preliminary success was obtained with a converted mechanical fuel injection equipment (FIE) 12 cylinder engine burning mostly coal slurry fuel and powering a locomotive on the GE test Track for a short period of time. However, the mechanical FIE used by this engine could only provide about 95% combustion efficiency, and had to use high percentage of diesel pilot fuel.

As reported earlier [1], a high pressure electronically controlled accumulator injector using a diamond compact insert nozzle was developed for this project. The improved reliability and durability of this new FIE allowed for an improved and more thorough study of combustion of CWS fuel in a diesel engine. It was decided to include a diesel pilot fuel injector in the combustion system mainly due to engine start and low load operation needs. BKM, Inc. of San Diego, CA was contracted to develop the electronic diesel fuel pilot/starting FIE for the research engine. As a result, the experimental combustion study was very much facilitated due to the ability of changing pilot/CWS injection timings and quantities without having to stop the engine. Other parameters studied included combustion chamber configuration (by changing CWS fuel injector nozzle hole number/shape/angle), as well as injection pressure. The initial phase of this combustion study is now complete. The results have been adopted into the design of a 12 cylinder engine FIE, to be tested in 1992. This paper summarizes the main findings of this study.

The goal for this study is to maximize combustion efficiency (or carbon burnout), while maintaining tolerable peak cylinder firing pressure (P_{max}), and reasonable specific fuel consumption (SFC). High combustion efficiency is needed mainly for emissions control, although it has some effect also on SFC. It was found that due to the heat release concentration, or high relative cycle efficiency [Hsu, 1984] of the coal fuel diesel combustion, it is necessary to limit the P_{max} [Hsu, 1988b]. Low engine SFC depends on high relative cycle efficiency and high combustion efficiency. However, high relative cycle efficiency usually brings high P_{max} , therefore, a compromise has to be attained to prevent engine hardware mechanical failure.

At this point, optimization of the above parameters has resulted in a 99.5% combustion efficiency while holding P_{max} below 17 MPa at engine full load (195 kW/cyl or 2.03 MPa indicated mean effective pressure at 1050 rpm). The corresponding SFC is 8160 kJ/IkWh, which translates into about 44 % indicated thermal efficiency.

2.0 Experimental Hardware, Data Reduction & CWS Fuels

2.1 Test Engine, Instrumentation & Data Reduction

The basic test engine and data reduction processes have been described in detail in a previous report [2]. Briefly, the research single cylinder engine has a 229 mm bore, a 267 mm stroke and a rated

speed of 1050 rpm. The combustion chamber arrangement has a side mounted pilot diesel fuel injector and a centrally placed CWS injector as shown in Fig. 2.1.1. The block diagram of the CWS accumulator injection system is shown in Fig. 2.1.2. As mentioned previously, the pilot fuel injection system and the main CWS FIE are both electronically controlled. Their injection timings and quantities can be arbitrarily varied by the test engineer during engine operation.

The general instrumentation layout is the same as before. The high speed cylinder pressure, injection pressure, and needle lift data were all collected on a crank angle basis. Fifty cycles were averaged in the digital oscilloscope for further processing. The power generated by the coal-fired cylinder was determined by the indicated kW calculated with the recorded cylinder pressure trace. Thermodynamic first law calculations were done using cylinder pressure versus volume data to obtain average cylinder temperature and heat release. The water in the CWS was considered to evaporate instantaneously at the time of entrance into the engine cylinder at the corresponding pressure. In the heat release calculation, heat losses to the combustion chamber walls were estimated using the basic relationship outlined by Annand [3]. However, the heat transfer coefficients were modified in such a way that the total heat loss conformed with the fuel heat input rate and the combustion efficiency (carbon burnout).

The CWS combustion efficiency of each run was calculated by the ash balance method. An exhaust particulate sample was collected for each run by an absolute filter over a period of 20 minutes after the engine had stabilized on the test load. The ash/carbon ratio of the collected particulates was compared with the ash/carbon ratio in the original coal to obtain the combustion efficiency for the test run.

2.2 CWS Fuels Used

The basic CWS fuel was prepared by Otisca Industries, Inc. of New York using "Kentucky Blue Gem" coal. It was cleaned to 0.8 % ash as shown in Table 2.2.1. The solid loading of the slurry used was maintained at about 49% by weight.

Table 2.2.1. Coal Nominal Lot Analysis - Kentucky Blue Gem coal

<u>Proximate Analysis</u>		<u>Ultimate Analysis</u>	
% Ash	0.80	% Carbon	82.59
% Volatile	39.40	% Hydrogen	5.34
% Fixed Carbon	59.80	% Nitrogen	2.08
		% Chlorine	0.18
<u>Particle Size</u>		% Sulfur	1.01
Mass Mean Diameter (microns)	5.47	% Oxygen (diff.)	8.00
<u>Heating Value</u>		High Heating Value (kJ/kg)	34630

In addition, a limited amount of 8 microns mean particle size CWS fuel prepared by CQ Inc. of Pa using Pennsylvania "Taggart" coal was tested. The analysis of Taggart coal is shown in Table 2.2.2.

Table 2.2.1. Coal Nominal Lot Analysis - Taggart coal

<u>Proximate Analysis</u>		<u>Ultimate Analysis</u>	
% Ash	1.80	% Carbon	83.50
% Volatile	40.10	% Hydrogen	5.50
% Fixed Carbon	58.10	% Nitrogen	1.00
		% Sulfur	0.70
		% Oxygen (diff.)	7.50
<u>Particle Size</u>			
Mass Mean Diameter (microns)	8.0		
<u>Heating Value</u>	High Heating Value (kJ/kg)		35100

3.0 Test Results

3.1 The "Delayed Ignition" of CWS Fuel at Full Engine Load

In a previous paper published by Hsu [4], it was pointed out that when pilot fuel is used to ignite CWS fuel, the starting time of combustion of the CWS fuel is dictated by the start of pilot fuel ignition. This is again investigated under engine full load conditions (high inlet air temperature and pressure) as shown in Figure 3.1.1. The combustion analyses of three runs using the same CWS fuel injection timing of 25 deg BTDC while varying the pilot fuel timing from 35, 25 to 15 deg before top dead center (BTDC) are displayed. As already proven by previous work, the first small peak on the heat release trace corresponds to the combustion of the pilot fuel. The start of the rise of the heat release trace that follows immediately afterwards indicates the start of combustion, or ignition, of the CWS fuel. It is clearly seen that the overall start of combustion in the engine depended on the pilot fuel timing. It is also seen that, although the CWS fuel was injected at the same timing, the CWS fuel residence time before coal ignition (from the start of CWS injection to coal ignition time characterized by the start of the second rise of the heat release curve) depended on the pilot fuel timing.

In the right side upper table in Figure 3.1.1, the test conditions are listed. In the lower table of "Combustion Results", the criteria set forth to investigate combustion in this study (P_{max} , combustion efficiency, and SFC) are listed. The run with 15 deg pilot injection timing had the most favorable combustion. It had the lowest P_{max} , highest combustion efficiency, and lowest SFC. Some of the results can find explanation from the heat release traces. The highest P_{max} (35 deg BTDC pilot timing case) was caused by the large amount of fuel burning BTDC. Fuel burned BTDC has a predominant effect on P_{max} than that burned after TDC (ATDC) [5]. The lowest SFC (15 deg BTDC pilot timing case) can be explained by the concentrated fuel combustion close to TDC, as indicated by the highest "Relative Cycle Efficiency" of 92.4% listed in the same table. The effect of the latter has also been explained by Hsu [5]. In Figure 3.1.2, the cylinder pressure and temperature are plotted together with the heat release rate. The case of 15 deg BTDC pilot timing produced the highest maximum temperature occurring at about the end of the heat release period (30 - 40 deg ATDC), which probably contributed to the highest combustion efficiency obtained.

The difference in the shape of the three heat release traces is believed to be caused by the variance of CWS fuel residence time before coal ignition, which is shown in Table 3.1.1. The residence time of CWS before

ignition appears somewhat like the "ignition delay" for diesel fuel. However, the processes involved are very different. With normal diesel fuel operation, during the ignition delay period, both a physical evaporation process and a chemical kinetic reaction process take place (mainly the latter which depends on the fuel cetane number). For CWS fuel, the residence time is mainly needed for water evaporation. This is observed both in an engine study [5] and a furnace study [6]. The amount of dehydrated coal fuel that can be burned at ignition time depends on the amount of water evaporated at that instant. Clearly, the longer residence time the CWS fuel has in the cylinder before ignition, the more water is evaporated by the heat in the cylinder. Thus, more dehydrated coal is released for combustion immediately after ignition. Hence, a very high concentrated heat release rate could appear. On the other hand, it should be pointed out that when pilot fuel is injected early and starts to burn, the average cylinder temperature becomes higher at an earlier time, which can also accelerate evaporation. This can be seen for the three cases in Figure 3 and the average gas temperatures in the cylinder during coal residence time before ignition are listed in Table 2 as well (both in crankangle degree and absolute time scales). However, the higher temperature has less effect on evaporation than the residence time. This can be explained, on one hand, by the simplified basic droplet evaporation relationship as follows [7]:

$$dW = k_1 \cdot dt \cdot \ln(k_2 \cdot T_{cyl} + C)$$

dW - increment of evaporated water mass

dt - time increment

T_{cyl} - in cylinder temperature

k_1 - f(droplet diameter, thermal diffusivity, density)

k_2 - f(specific heat, latent heat)

C - f(specific heat, latent heat, droplet temperature)

In the above formula, it is seen that the in-cylinder temperature affects the evaporation mass in the exponential term, whereas, the residence time has a direct proportional effect. On the other hand, Table 3.1.1 indicates that the difference in average gas temperature for the three cases is very small (from 940 to 920 K, about 2%). However, the order of magnitude of change in the residence time available for evaporation is significantly greater (from 0.95 to 2.38 msec, about 250%). Thus, due to having the most amount of available dehydrated coal fuel at ignition, the case of 15 deg pilot injection producing the highest and most concentrated heat release rate is understood.

Table 3.1.1. Residence Time and Average Temperature Before Ignition

Pilot Fuel Timing	CWS Fuel Res Time	Avg Cyl Gas Temp
Deg BTDC	Deg CA (msec)	Deg K
35	6 (0.95)	940
25	11 (1.74)	930
15	15 (2.38)	920

From the above analysis, it is seen that CWS fuel can be ignited by pilot fuel anytime after being injected into the engine cylinder. However, the best combustion result was obtained by delaying the ignition as much as possible, as in the 15 deg pilot injection case. This can be appropriately named the "Delayed Ignition" case. In fact, the computer combustion model study under our general research contract also suggested the CWS fuel be injected highly in advance of the pilot fuel [8]. In the engine tests, it was also found that when pilot injection was further retarded, self ignition of CWS occurred, which was the limit of "Delayed Ignition". In such instances, pilot fuel no longer ignited the coal fuel, but rather enhanced combustion after coal self ignition. No detrimental effect on combustion or engine performance was observed for these cases either.

3.2 Wall Impingement of CWS Fuel at Full Engine Load

Since CWS self ignition is the limit of "Delayed Ignition", a further study was conducted to investigate ways to increase the self ignition delay of CWS fuel. One obvious way is to advance the injection timing of CWS fuel. Test runs were made by retarding the pilot injection timing beyond the self ignition of CWS fuel. The results of these tests are shown in Figure 3.2.1. Clearly, ignition delay increases as CWS injection timing is advanced (lowest curve). This is evidently due to lower mean in-cylinder compression temperature which the CWS experiences during the delay period. The mean in-cylinder temperature for the cases studied is shown on the upper curve. Interestingly, the actual ignition time in terms of crankangle position did not change much as shown by the middle curve.

However, test results showed overly advanced injection timing, although providing very long delay, also deteriorated combustion and engine performance. The combustion analysis of the test cases are shown in Figure 3.2.2. From the combustion results table in the lower right side of this figure, comparing the 1st (22 deg CWS inj., run #31) and the 2nd (32 deg CWS inj., run #33) case, SFC is clearly in favor of run #33 which had the longer delayed ignition. The combustion efficiency of the two are the same, while the Pmax of run #31 is much lower. This is because of the much lower heat release rate (solid line) due to short "Delayed Ignition". This trend did not hold true for further advancing the CWS injection timing from 32 deg BTDC to 42 deg, as shown by the third case (run #39, center line). For this last run, although Pmax remained the same, the combustion efficiency and SFC started to deteriorate (from 99.5% to 99.1% and from 8054 to 8876 kJ/kWh respectively). Further advancement of CWS injection timing to 47 deg BTDC (not shown in the figure) had drastically caused the combustion efficiency to drop to 98% and SFC to increase to over 9100 kJ/kWh.

The reason for the combustion deterioration cannot find explanation in the normal pure diesel fuel operation experience. Overly advanced injection timing in diesel fuel operation brings BTDC early combustion, which leads to high Pmax, diesel knock (long ignition delay), and bad SFC. In the coal fuel engine case, no overly early combustion is detected. By reviewing the data of a separate CWS fuel injection study included in the present contract [9], it is highly probable that the CWS fuel spray has reached the cold cylinder liner walls by the time of ignition for the very early injection timing case.

This is illustratively shown in Figure 3.2.3. Further analysis had shown that, even with the 32 deg injection case, CWS fuel spray should have hit the piston crown after less than 5 degree crankangle. The CWS was not ignited until at least 20 crankangle degrees later (about 10 deg BTDC). Therefore, piston crown impingement happened well before ignition. Probably the crown temperature was high enough not to deteriorate the overall vaporization and subsequent combustion. Inspection of piston crown after engine dismantling had shown definite impingement marks. They are shown in Fig. 3.2.4 and 3.2.5. A major difference in the combustion of CWS and pure diesel fuel in the engine may be that for the CWS case, fuel spray impingement is not only unavoidable, but, in fact is necessary (for "Delayed Ignition").

3.3 CWS & Pilot Injection Timing Effect at Engine Full Load

Fuel injection timing maps for full engine load operations have been generated for Pmax, combustion efficiency, and SFC, as shown in Figure 3.3.1. They are made by generating isometric lines using actual test results (triangles in the figure). For all the three indicators, in the full load usable range, pilot fuel injection timing seems not to have a major effect. This is probably due to the fact that, the combustion in the engine cylinder is mostly initiated by coal fuel self ignition. At about 37 deg BTDC CWS injection timing, maximum Pmax can be expected with each pilot fuel injection timing. The later the pilot fuel is introduced, the smaller its contribution to raising Pmax due to ATDC combustion. Introducing the CWS fuel before 37 deg BTDC (towards the right in the map), Pmax is reduced because of fuel spray cylinder liner impingement hindering heat release rate. CWS fuel "Delayed Ignition" effect again can be seen in the part where injection is after 37 deg BTDC (towards the left). The same explanation can be given to the combustion efficiency and SFC part of the map. However, the optimum CWS injection timing for these two indicators are not the same. This is probably because the optimum combustion efficiency depends mainly on the cylinder temperature, whereas the SFC depends on the concentration of heat release about TDC ("Relative Cycle Efficiency") and the combustion efficiency. Using this map, the injection timings of pilot and CWS fuel can be selected with the compromise needed for Pmax, combustion efficiency, and SFC. In the present case, the pilot timing is 12 and the CWS timing is 35 deg BTDC.

More extensive and detailed fuel injection maps were also plotted. They are shown in Appendix I.

3.4 Combustion Chamber Configuration

The first investigation on combustion chamber configuration was to compare a 10 hole (0.40 mm dia.) CWS injector nozzle with an 8 hole (0.46 mm dia.) having the same total flow area. The combustion indicators are summarized in Figure 3.4.1. It is seen that, both the injectors can have the same maximum Pmax value, same highest combustion efficiency, and lowest SFC. Only, they happened at different CWS injection timings. Normal pure diesel fuel operation experience would suggest the better "air utilization" of the 10 hole injector nozzle should indicate some advantage. Further investigation into the fuel

injection rate of the nozzles had shown that due to the hole size discrepancy, the hole discharge coefficients were different (0.88 for the 0.40 mm hole and 0.80 for the 0.46 mm hole). Since they were injected with the same injection pressure of 82.7 MPa, the spray exit velocity from injector hole for the former was 333 m/s, and the latter, 300 m/s. The higher exit velocity 10 hole nozzle would hit the cylinder liner wall at a smaller injection advance angle making its optimum value move correspondingly. This explanation suggests that for the two injectors tested, the initial air entrainment of the spray jet (hole number dependent) is not as important as the secondary atomization after spray impingement (depending on spray velocity) on the piston crown. Similar tests were done with different injector hole shapes. They included inverse trumpeted hole, rounded inner edged hole etc. Both 8 and 10 hole nozzles of different shapes were made. All of them seemed to suggest the same conclusion of spray velocity having the dominant effect. Based on these results, the 8 hole nozzle was selected for prototype due to much less tendency to hole plugging. A comprehensive comparison of the engine performances equipped with different CWS injection nozzles are shown in the figures of Appendix II.

An 8 hole nozzle with smaller spray included angle of 130 degrees (as compared to the original 150 degrees) was tested to avoid cylinder liner impingement of CWS spray. It is schematically shown in Figure 3.4.2. Test results as compared with the original are shown in Figure 3.4.3. It can be seen that the firing pressure was lower and the combustion efficiency never reached the previous level, although the SFC was close. However the fact that the combustion efficiency decreased was not acceptable to the combustion design. This may imply that too much attachment of the impinged CWS on the piston crown is unfavorable also. More work has to be conducted in the future to optimize CWS impingement in the combustion chamber.

3.5 CWS Fuel Injection Pressure Effect

An investigation into CWS injection pressure was conducted early in the combustion study. The injection pressure varied between 61 to 83 MPa. The P_{max} , combustion efficiency, and SFC results are compared in Figure 3.5.1. P_{max} and combustion efficiency are seen to increase with CWS injection pressure, while SFC decreases. Within the tested range, combustion performance definitely improved when higher injection pressure was used. The calculated heat release traces together with the cylinder pressure and the injector needle lift of the three runs are shown in Figure 3.5.2. Correspondingly, the CWS injection traces and the percentage of fuel burnt traces are shown in Figure 3.5.3. The highest heat release rate of the highest injection pressure case is evident. The injection starting times was the same (25 deg BTDC) and the CWS fuel was ignited at about the same time (10 deg BTDC). The higher heat release rate after ignition started is both the result of better atomization and more fuel being injected into the cylinder at the same instant. It is interesting to note that from the CWS ignition to the fall off of the peak heat release, there seems to be a fairly constant duration of 35 to 40 degrees crankangle. If the injection duration extends beyond the fall off period, then a hump, mentioned first by Hsu [10], of rather slow heat release rate appears towards the

end of the combustion period. It is in proportion to the extension of fuel injection duration beyond the 35 to 40 degrees crank angle period.

3.6 Coal Particle Size

In a previous report on CWS fuels effect on engine combustion [11], it was shown that the 3 micron mean particle size slurry burned faster than the 5 micron size fuel. Some more tests were conducted comparing 5 micron with 8 micron fuels made by the same manufacturer OTISCA.

The observation made was that, the 5 micron fuel can only use a small amount of pilot fuel to boost combustion after coal fuel "self-ignition" under engine full load conditions, whereas the 8 micron fuel must use a rather large amount of pilot fuel for ignition. A typical engine combustion and performance comparison is shown in Fig. 3.6.1. The much higher maximum and more concentrated heat release rate of the 5 micron fuel are clearly seen. The resultant engine performance showed lower SFC and higher cylinder firing pressure with the 5 micron fuel. The burning ability of the two fuels can be further analyzed by the "% Fuel Burnt" comparison as shown the Fig. 3.6.2. Although for most of the injection duration, the heat input rate (injection rate) and the resultant total heat in cylinder are almost identical, the percent of fuel burnt is very different. The initial higher "% Fuel Burnt" of the 8 micron fuel is due to the much larger pilot amount used (101 vs. 56 mm³ as shown in Fig. 3.6.1). However, the inability of the 8 micron coal fuel to burn is clearly indicated in the following lower fuel burnt percentage and the final combustion efficiency of only 96.7% as compared to the 99.4 % of the 5 micron fuel.

It is interesting to compare the recent OTISCA 8 microns fuel combustion with previously tested results [11] using other 8 micron fuels made by different manufacturers, namely CQ and AMAX. They are shown in Fig. 3.6.3. The similarity is evident. Thus, regardless of fuel manufacturer, the faster burning ability of smaller particle size fuel is again proven.

Table 3.6.1 Engine Full Load Performances

Coal Size Mic	Operating Conditions				Combustion Results			
	Inj Tim (BTDC)		Fuel Amt (%)		Pmax MPa	Comb Eff %	Rel. Eff %	SFC kJ/ kWh
	Pilot	CWS	Pilot	CWS				
5	12	35	4.0	96.0	17.1	99.5	97.5	8180
8	25	30	6.5	93.5	16.2	99.0	97.0	8320

In order to improve the engine performance using the larger 8 microns fuel, a 10 hole injector nozzle having higher flow rate was used instead of the previously tested 8 hole nozzle. After injection timing adjustments, the combustion and performance comparisons are shown in Fig. 3.6.4. The maximum heat release rate increased due to the higher injection rate and the SFC, as well as the combustion efficiency

improved as a result. However, more pilot fuel amount had to be used. Earlier pilot fuel injection timing was needed to start timely combustion. Table 3.6.1 compares the engine full load performances obtained with 5 and 8 micron fuels.

3.7 Injector Hole Plugging

It was found frequently during tests that the 5 micron particle size fuel tended to plug one or two injector holes (0.018" or smaller in diameter) while the engine was running whenever the coal loading exceeded 50% by weight in the slurry. The net result of one or two hole plugged was lower injection rate and longer injection duration. Consequently, lower overall heat release rate and higher fuel consumption accompanied. One such comparison is shown in the Fig. 3.7.1. One effective solution is to dilute the slurry with water to a lower percent solid loading. One such comparison was done with 49% versus 46% coal loading fuels. The performance and combustion are shown in Fig. 3.7.2. The results of fuel dilution and hole plugging are similar. Lower heat release rate and poorer fuel consumption are seen again with over diluted fuel. Therefore, it is essential to maintain the coal loading below the plugging limit and not over diluted. It is recommended to hold it with -0.5% of plugging limit.

Other circumstances might also cause injector hole plugging. One instance occurred while investigating the effect of fuel temperature on combustion. Electrical band heaters were used on the outside of fuel drums to heat up the fuel to 120 F temperature. However, the local high temperature at the heating band visibly caused coagulation of coal particles. The coagulated particles in turn plugged some of the injector holes. The benefit of higher fuel temperature was much over shadowed by the plugged hole effect. The test results of this comparison is shown in Fig. 3.7.3.

3.8 Low Inlet Manifold Pressure (MAP) Effect

A simulated engine run at high altitude was conducted by reducing the inlet MAP. Based on operation experiences, at 8000 ft. altitude, the engine inlet MAP would drop from the sea level 47 psia to 40 psia. There was not a problem of engine carrying full load with 40 psia MAP. The performance and combustion results are compared in Fig. 3.8.1. As shown in the figure, combustion was not as timely due to the higher fuel air ratio in the case of 40 psia. Cylinder firing pressure was lower and the SFC is worse. In Fig. 3.8.2, the cylinder average temperature histories were compared. The lower 40 psia case showed late rise in temperature due to delayed burning. Consequently, at the exhaust valve opening time of 125 deg ATDC, the exhaust temperature is shown to be higher.

3.9 Engine Lower Loads Combustion

Lower load operation is characterized by very low or no boost pressure in the inlet air manifold. As explained previously [4], it is not possible to self ignite the CWS due to the excessive temperature

drop after heat is extracted to vaporize the water in fuel. Pilot diesel fuel combustion heat is necessary to raise the temperature early in the cycle for water evaporation. A typical combustion heat release pattern of the notch 2 load (naturally aspirated, 536 rpm, 300 kPa BMEP) is shown in Figure 3.9.1. The first triangular heat release shape corresponds to the pilot diesel fuel combustion, which amounts to about 24% of energy as compared to about 4% at full engine load. The coal combustion efficiency was only about 93%, due to the low maximum combustion temperature of 1560 K which is much lower than the 1900 K at full engine load. The engine operation conditions and performance results at lower loads for two kinds of fuels are summarized in Table 3.9.1 and 3.9.2.

Table 3.9.1 Engine Operation Conditions and Results
(5 Micron Fuel)

Load	Operation Conditions						Combustion Results		
	RPM	MEP MPa	Inj. Tim. BTDC		Fuel Amt Percent		Pmax MPa	Comb. Eff. %	SFC kJ/kWh
			Pilot	CWS	Pilot	CWS			
N2	620	0.30	24	15	23.8	76.2	4.9	92.8	12165
N3	880	0.49	23	15	23.9	76.1	5.5	94.9	10450
N4	880	0.56	22	15	16.9	83.1	5.9	96.5	9255
N5	960	1.03	20	20	9.2	90.8	8.2	97.5	8560
N6	960	1.35	19	20	6.7	93.3	9.9	98.5	8258
N7	960	1.71	18	25	5.0	95.0	12.3	99.0	8403
N8	1050	1.98	12	35	4.0	96.0	17.1	99.5	8159

Table 3.9.2 Engine Operation Conditions and Results
(8 Micron Fuel)

Load	Operation Conditions						Combustion Results		
	RPM	MEP MPa	Inj. Tim. BTDC		Fuel Amt Percent		Pmax MPa	Comb. Eff. %	SFC kJ/kWh
			Pilot	CWS	Pilot	CWS			
N2	620	0.30	26	19	32.6	67.4	5.4	92.0	10899
N3	880	0.49	26	19	29.8	70.2	5.7	93.0	9567
N4	880	0.56	26	19	25.0	75.0	6.2	95.0	9362
N5	960	1.03	25	19	14.9	85.1	8.8	97.0	9171
N6	960	1.35	25	20	10.8	89.2	10.4	98.0	9090
N7	960	1.71	24	24	8.0	92.0	12.1	98.0	8786
N8	1050	1.98	25	30	6.5	93.5	16.2	99.0	8320

It is most interesting to note that when engine load increases, the optimum injection timing of the pilot fuel is retarded while that of CWS fuel is advanced. As anticipated, the pilot fuel amount needed becomes less when engine load is increased. The combustion efficiency increases with the engine load probably due to higher combustion and piston crown temperature.

Within the present program, a duty cycle coal usage target had been set for the study of overall economics of a coal fired locomotive. A typical locomotive operates about 60% of time at idle, which uses pure diesel fuel. Therefore, the target was set for 75% of coal energy consumption (25% diesel fuel) on a duty cycle basis. The above Table 3.9.1. type of operation can actually provide 81.3% coal usage. Table 3.9.2 provides 78% coal usage. Both of them exceed the planned goal.

The engine emission results were also recorded for the lower load operations. They are collected in Appendix III.

It is interesting to compare the engine lower loads combustion as the engine load changes. The heat release and cylinder pressure traces are figuratively shown in Fig. 3.9.2. It should, however, be indicated that when different batch of fuels are used, there might be some discrepancies. A second set of traces using a different fuel is shown in Fig. 3.9.3.

4.0 Conclusions

A detail study of the combustion of CWS fuel in a diesel engine has been made. The important findings are as follows.

- o Fully utilizing the residence time of CWS fuel in the cylinder to evaporate the water content by "Delayed Ignition" generally brings good combustion results. The limit of "Delayed Ignition" is the self ignition of CWS without pilot fuel.
- o It is advantageous to inject CWS fuel early and pilot fuel late in the cycle for "Delayed Ignition". The limit of CWS early injection is the fuel impingement onto the cold cylinder liner walls. When this happens, combustion deteriorates drastically.
- o The residence time needed to evaporate the water content of CWS fuel is very long and the spray jet travels very fast; therefore, impingement of the CWS before ignition seems to be unavoidable. As long as high temperatures exist, as in the full engine load case, impingement of CWS onto piston crown does not seem to hurt combustion.
- o Close to the optimized combustion zone for full engine load condition, the injection timing of the pilot fuel has less impact on combustion than that of CWS. The combustion efficiency can reach 99.5% and engine cycle efficiency is comparable to pure diesel fuel engine.
- o The effect of injector hole number or shape seemed to have less effect on combustion than the spray penetration velocity. This might be due to the fact that combustion started after secondary atomization of the spray impinging on piston crown.
- o Within the range tested (under 85 MPa), higher injection pressure brings better engine combustion results.

- o The coal particle size in CWS is a main factor that controls the coal fuel combustion rate in engine cylinder. The engine performance disadvantage of larger coal particle size can be overcome somewhat by increasing the fuel injection rate.
- o Under low load conditions, there is not enough heat in the cylinder to quickly evaporate the water content in CWS fuel without early pilot diesel fuel combustion. CWS injection timing has to be retarded. As the engine load is increased, the injection timings of pilot and CWS fuel move in opposite directions until early CWS and late pilot are reached.
- o The achievement so far is obtaining 99.5% combustion efficiency while holding cylinder firing pressure below the tolerable level of 17 MPa (2460 psi) under engine full load conditions. The corresponding SFC is 8160 kJ/IkWh (5790 BTU/IHP-HR), which translates into about 44% indicated thermal efficiency.

References

- [1] Coal-Fueled Diesel: Technology Development, Final Report to US DOE, Contract No. DE-AC21-85MC22181, GE Research and Development Center, March, 1989.
- [2] Preliminary Investigation of The Effects of Coal-Water Slurry Fuels on the Combustion in GE Coal Fueled Diesel Engine, Topical Report to US DOE, Contract No. DE-AC21-88MC23174, GE Transportation Systems, June, 1990.
- [3] Annand, W. J. D., "Heat Transfer in the Cylinder of Reciprocating Internal Combustion Engines," Proc. Instn. Mech. Engrs., Vol. 177, No. 36, 1963.
- [4] Hsu, B. D., "Progress on the Investigation of Coal-Water Slurry Fuel in a Medium Speed Diesel Engine: Part 1 - Ignition Studies," ASME Transactions, Journal of Engineering for Gas Turbines and Power, Vol. 110, No. 3, 1988, pp. 415-422.
- [5] Hsu, B. D., "Heat Release, Cycle Efficiency and Maximum Cylinder Pressure in Diesel Engine - The Use of an Extended Air Cycle Analysis," S.A.E. Transactions, 1984, p. 4.766.
- [6] Walsh, P. M., Zhang, M., Farmayan, W. F., Beer, J. M., "Ignition and Combustion of Coal-Water Slurry in a Confined Turbulent Diffusion Flame," presented at the 20th International Symposium on Combustion, Ann Arbor, MI, Aug. 1984.
- [7] Kanury, A. M., Introduction to Combustion Phenomena, Gordon and Breach Science Publishers, second edition, 1977.
- [8] Wahiduzzaman, S., Blumberg, P.N. and Hsu, B.D., "Simulation of Significant Design and Operating Characteristics of a Coal Fueled Locomotive Diesel Engine," ASME Publication, Coal Fueled Diesel Engines, ICE Vol. 14, 1991.
- [9] Caton, J.A., Kihm, K.D., Seshadri, A.K. and Zictermann, G., "Micronized Coal Water Slurry Sprays from a Diesel Engine Positive Displacement Fuel Injection System," Presented to the Combustion Institute, Central States Section, 1991 Spring Technical Meeting, Nashville, TN, April, 1991

- [10] Hsu, B. D., Leonard, G. L., and Johnson, R. N., "Progress on the Investigation of Coal-Water Slurry Fuel in a Medium Speed Diesel Engine: Part 3 - Accumulator Injector Performance," ASME Transactions, Journal of Engineering for Gas Turbines and Power, Vol. 111, No. 3, 1989, pp. 516-520.
- [11] Hsu, B.D. and Confer, G.L., "Progress on the Investigation of Coal-Water Slurry Fuel Combustion in a Medium Speed Diesel Engine: Part 4 - Fuels Effect," ASME Publication, Coal Fueled Diesel Engines, ICE Vol. 14, 1991.

CWS TEST CYLINDER LAYOUT

Figure 2.1.1 CWS Test Cylinder Combustion Chamber layout

**COAL-WATER-SLURRY FUELED DIESEL ENGINE
SYSTEM III FUEL INJECTION EQUIPMENT**

Figure 2.1.2 Accumulator Fuel Injection System Schematic

HEAT RELEASE AND COMBUSTION ANALYSIS MAP 320KPA MAT 360K 1050RPM

dQ/dA (kJ/deg)

HEAT
RELEASE

4.00

3.00

2.00

1.00

NEEDLE
LIFT

CWS

PILOT

-40

-20

TDC

20

40

60

80

100

120

CRANK ANGLE IN DEGREES

TEST CONDITIONS					
INJ ST	CWS INJ P	PILOT	TEST		
PILOT CWS	ST END	AMT	LOAD		
(# BTDC)	(MPa)	(mm ³)	(kW)		
15	25	69.6	38.0	73	188
25	25	69.8	37.7	71	192
35	25	69.7	36.5	71	192
LONG DELAY					
MED. DELAY					
SHORT DELAY					

COMBUSTION RESULTS			
CYL	BURN-OUT	REL. EFF.	SFC
P _{max}	(%)	(%)	(kJ/kWh)
(MPa)			
15.4	99.3	92.4	8414
16.1	99.2	91.9	8655
16.5	99.0	90.5	9008
RUN #			
28			
29			
30			

Figure 3.1.1 Combustion Results of "Delayed Ignition"

HEAT RELEASE AND COMBUSTION ANALYSIS MAP 320KPA MAT 360K 1050RPM

Figure 3.1.2 Temperature and Pressure of "Delayed Ignition"

Figure 3.2.1 CWS Injection Timing Effect

HEAT RELEASE AND COMBUSTION ANALYSIS MAP 320KPA MAT 360K 1050RPM

$dQ/d\alpha$ (kJ/deg)

HEAT
RELEASE

4.50

3.00

1.50

0.00

-0.50

-1.00

-1.50

-2.00

-2.50

-3.00

-3.50

-4.00

-4.50

-5.00

-5.50

-6.00

-6.50

-7.00

-7.50

-8.00

-8.50

-9.00

-9.50

-10.00

-10.50

-11.00

NEEDLE
LIFT

CWS

PILOT

TDC

CRANK ANGLE IN DEGREES

80

100

120

TEST CONDITIONS

	INJ ST PILOT CWS (* BTDC)	CWS INJ P ST END (MPa)	PILOT AMT (mm ³)	TEST LOAD (kW)
---	12	22	83.1	50.9
---	12	32	82.9	52.6
---	12	42	82.8	52.6
			71	187
			74	192
			93	178

COMBUSTION RESULTS

CYL P _{max} (MPa)	BURN- OUT (%)	REL. EFF. (%)	SFC (kJ/ kWh)	RUN #
15.3	99.5	94.3	8509	31
17.2	99.5	97.7	8054	33
17.2	99.1	97.5	8876	39

Figure 3.2.2 Combustion Results of CWS Injection Timing Change

Figure 3.2.3 Schematic of CWS Injection Wall Impingement

Figure 3.2.4 Photo of Piston Crown Fuel Impingement (1)

Figure 3.2.5 Photo of Piston Crown Fuel Impingement (2)

▲ Actual Test Point

Figure 3.3.1 Fuel Injection Timing Maps

Figure 3.4.1 Effect of CWS Injector Hole Number

Figure 3.4.2 Schematic of Injector Spray Included Angle

Figure 3.4.3 Effect of CWS Injector Spray Included Angle

Figure 3.5.1 Effect of CWS Fuel Injection Pressure

HEAT RELEASE AND COMBUSTION ANALYSIS MAP 320KPA MAT 360K 1050RPM

dQ/dA (kJ/deg)

HEAT
RELEASE

TEST CONDITIONS						
	INJ ST		CWS INJ P		PILOT AMT (mm ³)	TEST LOAD (kW)
	PILOT CWS (* BTDC)		ST	END		
			(MPa)			
— HIGH INJ P	20	25	82.9	53.3	80	195
— MED. INJ P	20	25	69.4	39.0	81	195
— LOW INJ P	20	25	60.2	28.9	81	195

COMBUSTION RESULTS				
CYL	BURN- OUT	REL. EFF.	SFC	RUN
P _{max} (MPa)	(%)	(%)	(kJ/ kWh)	
17.2	99.6	97.0	8055	16
16.1	99.2	93.0	8765	17
15.7	98.3	89.7	8839	18

NEEDLE
LIFT

CWS

PILOT

CRANK ANGLE IN DEGREES

-40 -20 TDC 20 40 60 80 100 120

Figure 3.5.2 Effect of CWS Fuel Injection Pressure on Combustion

FUEL INJECTION AND COMBUSTION EFFICIENCY ANALYSIS EFFECT OF CWS INJECTION PRESSURE

Figure 3.5.3 Percent of Fuel Burnt at Various Injection Pressures

HEAT RELEASE AND COMBUSTION ANALYSIS EFFECT OF COAL PARTICLE SIZE

Figure 3.6.1 Effect of Fuel Particle Size on Combustion

FUEL INJECTION AND COMBUSTION EFFICIENCY ANALYSIS EFFECT OF COAL PARTICLE SIZE

Figure 3.6.2 Percent of Fuel Burnt of 5 & 8 Micron Fuels

HEAT RELEASE AND COMBUSTION ANALYSIS DIFFERENT CWS WITH SIMILAR PARTICLE SIZE (8 MICRON)

TEST CONDITIONS						
INJ ST	CWS INJ P	PILOT	TEST			
PILOT CWS	ST	END	AMT			
(# BTDC)	(MPa)		(mm3)			
26	35	83.1	48.3	122	198	
28	40	80.1	47.3	101	187	
26	34	80.6	46.0	128	185	
--- CO INC --- OTISCA --- AMAX						

COMBUSTION RESULTS				
CYL P _{max} (MPa)	BURN-OUT (%)	REL. EFF. (%)	SFC (kJ/kWh)	RUN #
16.6	98.3	93.5	8685	62
15.1	96.7	93.0	9409	116
15.5	97.9	96.0	8769	45 [†]

Figure 3.6.3 Combustion of 8 Micron Fuels from Various Sources

HEAT RELEASE AND COMBUSTION ANALYSIS RESULT OF 8 MICRON COAL FUEL WITH DIFFERENT NOZZLES (1050RPM)

Figure 3.6.4 Combustion of 8 Micron Fuel Using Larger Hole Nozzle

HEAT RELEASE AND COMBUSTION ANALYSIS EFFECT OF NOZZLE HOLE PLUG (1050 RPM)

dQ/dA (kJ/deg)

HEAT
RELEASE

TEST CONDITIONS					
INJ ST PILOT CWS (# BTDC)	CWS INJ P ST END (MPa)	PILOT AMT (mm3)	TEST LOAD (kW)		
12	42	82.9	52.2	100	179
12	42	82.8	52.6	93	179

COMBUSTION RESULTS				
CYL P_{max} (MPa)	BURN- OUT (%)	REL. EFF. (%)	SFC (kJ/ kWh)	RUN #
16.6	99.1	96.9	8987	38
17.2	99.1	97.5	8876	39

Figure 3.7.1 Effect of Partially Plugged Injector on Combustion

HEAT RELEASE AND COMBUSTION ANALYSIS EFFECT OF CWS DILUTION (1050 RPM)

TEST CONDITIONS					
INJ ST	CWS INJ P	PILOT	TEST		
PILOT CWS	ST END	AMT	LOAD		
(* BTDC)	(MPa)	(mm ³)	(kW)		
12	81.8	61	195		
12	84.0	59	198		

COMBUSTION RESULTS			
CYL	BURN-OUT	REL. EFF.	SFC
P _{max}	(%)	(%)	(kJ/kWh)
16.9	99.2	97.1	8290
17.5	99.3	97.7	8051

Figure 3.7.2 Effect of Fuel Dilution on Combustion

HEAT RELEASE AND COMBUSTION ANALYSIS EFFECT OF HEATED CWS (1050 RPM)

TEST CONDITIONS						
INJ ST	CWS INJ P	PILOT	TEST			
PILOT CWS	ST END	AMT	LOAD			
(* BTDC)	(MPa)	(mm ³)	(kW)			
12	40	50.5	61			
12	40	52.0	57			

COMBUSTION RESULTS				
CYL	BURN-OUT (%)	REL. EFF. (%)	SFC (kJ/kWh)	RUN #
16.2	99.1	96.2	9003	67
17.0	99.1	97.3	8416	65

Figure 3.7.3 Unsuccessful Combustion Result of Heated Fuel

HEAT RELEASE AND COMBUSTION ANALYSIS EFFECT OF INLET MANIFOLD PRESSURE (1050 RPM)

TEST CONDITIONS					
INJ ST	CWS INJ P	PILOT	TEST		
PILOT CWS	ST END	AMT	LOAD		
(* BTDC)	(MPa)	(mm3)	(kW)		
—MAP 40 PSI	12 35	84.4 51.7	55 192		
---MAP 47 PSI	12 35	83.9 53.5	52 193		

COMBUSTION RESULTS			
CYL	BURN-OUT	REL. EFF.	SFC
P _{max} (MPa)	(%)	(%)	(kJ/kWh)
13.5	99.4	94.7	8586
17.1	99.5	97.5	8184
			RUN #
			56
			51

Figure 3.8.1 Effect of Inlet Air Pressure on Combustion

HEAT RELEASE AND COMBUSTION ANALYSIS EFFECT OF INLET MANIFOLD PRESSURE (190KW 1050RPM)

Figure 3.8.2 Effect of Inlet Air Pressure on Temperature and Pressure

HEAT RELEASE AND COMBUSTION ANALYSIS MAP 102KPA MAT 332K 620RPM 17KW

Figure 3.9.1 Combustion Heat Release at Lower Load

HEAT RELEASE AND COMBUSTION ANALYSIS ENGINE PART LOAD (CSET 1)

Figure 3.9.2 Heat Release and Cylinder Pressure at Lower Loads (1)

HEAT RELEASE AND COMBUSTION ANALYSIS ENGINE PART LOAD (SET 2)

Figure 3.9.2 Heat Release and Cylinder Pressure at Lower Loads (2)

APPENDIX I

Injection Timing Maps at Full Engine Load

INJECTION TIMING MAP (FULL LOAD)-GROUP 1

CYLINDER PEAK PRESSURE

P_{inj}-10000 PSI
 ▲ TEST POINT

INJECTION TIMING MAP (FULL LOAD)-GROUP 1 COMBUSTION EFFICIENCY (%)

PILOT TIMING (DEG BTDC)

P_{inj}-10000 PSI
▲ TEST POINT

INJECTION TIMING MAP (FULL LOAD)-GROUP 1 SPECIFIC FUEL CONSUMPTION

P_{inj} -10000 PSI
Δ TEST POINT

INJECTION TIMING MAP (FULL LOAD)-GROUP 1

RELATIVE EFFICIENCY (%)

PILOT TIMING (DEG BTDC)

P_{inj} -10000 PSI
 Δ TEST POINT

INJECTION TIMING MAP (FULL LOAD)-GROUP 2 CYLINDER PEAK PRESSURE

— $P_{inj}=12000$ PSI ▲ TEST POINT

INJECTION TIMING MAP (FULL LOAD)-GROUP 2 COMBUSTION EFFICIENCY (%)

—— $P_{inj}=12000$ PSI ▲ TEST POINT

INJECTION TIMING MAP (FULL LOAD)-GROUP 2 SPECIFIC FUEL CONSUMPTION

— $P_{inj}=12000$ PSI ▲ TEST POINT

INJECTION TIMING MAP (FULL LOAD)-GROUP 2

RELATIVE EFFICIENCY (%)

— $P_{inj}=12000$ PSI ▲ TEST POINT

APPENDIX II

Fuel Injection Rates & Relative Engine Performances of Nozzles

CWS INJECTION NOZZLE CHARACTERS

NUMBER	3	5	10	13	12
NAME	PREVIOUS	FLARE HOLE	SHARP EDGE		
HOLE NO	10	10	10	8	10
HOLE DIR (DEG)	150	150	150	130	150
HOLE DIA (IN)	.016	.016	.016	.018	.018
HOLE SHAPE	SIMPLE	SIMPLE	SIMPLE	SIMPLE	SIMPLE
EXIT V* (M/S)	332	360	300	284	294
DISCHARGE C	.88	.96	.8	.75	.79

$V = (2g * (P_{inj} - P_{cyl}) / W)^{1/2}$
 $G = C * N * A * V * W$
 N HOLE NUMBER
 W FUEL SPECIFIC WEIGHT
 * AT INJECTION PRESSURE 12000PSI
 NOZZLE HOLE EXIT VELOCITY
 NOZZLE FUEL FLOW RATE
 A HOLE AREA
 C HOLE DISCHARGE COEFFICIENT

FUEL INJECTION RATES OF DIFFERENT NOZZLES

FUEL INJECTION RATE (BTU/DEG-CA)

10HOLE0.016 10HOLE0.016F 8HOLE0.018 8HOLE0.018S

EFFECT OF DIFFERENT INJECTION NOZZLES

-□- 10HOLE0.016 -x- 10HOLE0.016F -▽- 8HOLE0.018 -◆- 8HOLE0.018S

EFFECT OF DIFFERENT INJECTION NOZZLES

-□- 10-HOLE 0.016 -x- 10-HOLE 0.016F -▽- 8-HOLE 0.018 -♦- 8-HOLE 0.0185

EFFECT OF DIFFERENT INJECTION NOZZLES

SPECIFIC FUEL CONSUMPTION (BTU/HP.HR)

-□- 10HOLE0.016 -x- 10HOLE0.016F -△- 8HOLE0.018 -◆- 8HOLE0.018S

EFFECT OF DIFFERENT INJECTION NOZZLES

-□- 10HOLE0.016 -x- 10HOLE0.016F -▽- 8HOLE0.018 -◆- 8HOLE0.0185

APPENDIX III

Engine Performance & Emissions Results

SINGLE CYLINDER ENGINE TEST SETUP
(NOZZLE 8 HOLE 0.018 IN)

NOTCH	N.8	N.7	N.6	N.5	N.4	N.3	N.2
SPEED (RPM)	1050	995	950	950	888	888	590
POWER* (KW)	135	110	82	55	20	14	10
POWER** (KW)	195	145	115	88	42	36	16
POWER** (IHP)	265	197	156	120	57	49	22
IMEP** (PSI)	300	235	195	150	76	66	44
MAP (PSI)	44	37	29	23	17	16	15
MAP (IN-HG)	60	45.5	29.4	16.6	4.8	2	.2
P DROP (IN-HG)	17.3	16	12.2	7.1	1.6	.1	0
MAT (F)	185	180	180	170	160	160	150
PILOT-T (BTDC)	15	18	19	20	22	23	24
CWS-T (BTDC)	35	22	18	17	16	16	15
P-PILOT (POSITION)	2.4	2.6	2.8	3	3.5	3.8	4
P-CWS (PSI)	12000	12000	12000	12000	8000	7000	7000

*PANEL REGULATED VALUE

**BY P-V DIAGRAM CALCULATION

ENGINE FULL LOAD AND PART LOAD

ENGINE FULL LOAD AND PART LOAD

ENGINE FULL LOAD AND PART LOAD

ENGINE FULL LOAD EMISSION TEST RESULT

ENGINE PART LOAD EMISSION TEST RESULT

ENGINE FULL LOAD AND PART LOAD

ENGINE FULL LOAD AND PART LOAD

APPENDIX IV

Heat Release Records of All Test Runs

SINGLE CYLINDER ENGINE RUNS (SETUP)

DATE	RUN	INJECTOR	RPM	KW	MAP (PSI)	MAT (DEG F)	P-INJ (PSI)	TIME-CWS DEG BTDC	TIME-PIL DEG BTDC	NOTES
1/11,91	13	#5	1050	188	47	185	12000	25	20	
1/11,91	14	#5	1050	188	47	185	10000	25	21	
1/11,91	15	#5	1050	188	47	185	8800	25	20	
1/15,91	16	#5	1050	188	47	185	12000	25	20	
1/15,91	17	#5	1050	188	47	185	10000	25	19	
1/15,91	18	#5	1050	188	47	185	8800	25	20	
1/16,91	19	#5	1050	188	47	185	10000	25	20	
1/16,91	20	#5	1050	188	47	185	10000	28	23	
1/16,91	21	#5	1050	188	47	185	10000	20	15	
1/29,91	22	#5	1050	188	47	185	10000	28	23	
1/29,91	23	#5	1050	188	47	185	10000	20	15	
1/29,91	24	#5	1050	188	47	185	10000	23	18	
2/04,91	25	#5	1050	188	47	185	10000	25	15	
2/04,91	26	#5	1050	188	47	185	10000	15	14	
2/04,91	27	#5	1050	188	47	185	10000	35	15	
2/04,91	28	#5	1050	188	47	185	10000	25	15	
2/06,91	29	#5	1050	188	47	185	10000	25	25	
2/06,91	30	#5	1050	188	47	185	10000	25	35	
2/14,91	31	#5	1050	188	47	185	12000	22	12	
2/14,91	32	#5	1050	188	47	185	12000	27	12	
2/14,91	33	#5	1050	188	47	185	12000	32	12	
2/19,91	34	#5	1050	188	47	185	12000	32	7	
2/19,91	35	#5	1050	188	47	185	12000	27	7	

SINGLE CYLINDER ENGINE RUNS (SETUP)

DATE	RUN	INJECTOR	RPM	KW	MAP (PSI)	MAT (DEG F)	P-INJ (PSI)	TIME-CWS DEG BTDC	TIME-PIL DEG BTDC	NOTES
2/19,91	36	#5	1050	188	47	185	12000	32	3	
2/19,91	37	#5	1050	188	47	185	12000	37	2	
2/27,91	38	#5	1050	188	47	185	12000	42	12	*
2/27,91	39	#5	1050	188	47	185	12000	42	12	*
2/27,91	40	#5	1050	188	47	185	12000	42	7	*
2/27,91	41	#5	1050	188	47	185	12000	47	8	
3/06,91	42	#5	1050	188	47	185	12000	47	13	*
3/06,91	43	#5	1050	188	47	185	12000	47	8	*
3/06,91	44	#5	1050	188	47	185	12000	47	2	*
3/20,91	45	#0	1050	188	47	185	10000	40	12	
3/20,91	46	#0	1050	188	47	185	10000	30	12	
3/20,91	47	#0	1050	188	47	185	10000	20	12	
3/21,91	48	#0	1050	188	47	185	12000	20	12	
3/21,91	49	#0	1050	188	47	185	12000	30	12	
3/21,91	50	#0	1050	188	47	185	12000	40	12	
3/26,91	51	#0	1050	188	47	185	12000	35	12	
3/26,91	52	#0	1050	188	47	185	12000	45	12	
3/26,91	53	#0	1050	188	47	185	12000	30	15	
3/26,91	54	#0	1050	188	47	185	12000	40	15	
3/27,91	55	#0	1050	188	40	185	12000	30	12	LOW MAP
3/27,91	56	#0	1050	188	40	185	12000	35	12	LOW MAP
3/27,91	57	#0	1050	188	40	185	12000	40	12	LOW MAP
4/03,91	58	#0	1050	188	47	185	12000	35	35	CQ FUEL *

SINGLE CYLINDER ENGINE RUNS (SETUP)

DATE	RUN	INJECTOR	RPM	KW	MAP (PSI)	MAT (DEG F)	P-INJ (PSI)	TIME-CWS DEG BTDC	TIME-PIL DEG BTDC	NOTES
4/03,91	59	#0	1050	188	47	185	12000	35	40	CQ FUEL_*
4/05,91	60	#0	1050	188	47	185	12000	35	38	CQ FUEL_*
4/05,91	61	#0	1050	188	47	185	12000	35	29	CQ FUEL_*
4/05,91	62	#0	1050	188	47	185	12000	35	26	CQ FUEL_*
4/08,91	63	#10	1050	188	47	185	12000	30	12	*_*
4/08,91	64	#10	1050	188	47	185	12000	35	12	*_*
4/08,91	65	#10	1050	188	47	185	12000	40	12	*_*
4/17,91	66	#10	1050	188	47	185	12000	35	12	HEATED CWS_*
4/17,91	67	#10	1050	188	47	185	12000	40	13	HEATED CWS_*
4/17,91	68	#10	1050	188	47	185	12000	30	12	HEATED CWS_*
5/09,91	69	#10	1050	188	47	185	12000	20	12	*_*
5/09,91	70	#10	1050	188	47	185	12000	45	12	
5/09,91	71	#10	1050	188	47	185	12000	40	15	
5/13,91	72	#10	1050	188	47	185	12000	30	15	
5/13,91	73	#10	1050	188	47	185	12000	35	12	COAL_46%
5/13,91	74	#10	1050	188	47	185	12000	40	12	COAL_46%
5/15,91	75	#10	1050	188	47	185	12000	40	12	COAL LOW
5/15,91	76	#10	1050	188	47	185	12000	35	12	
5/21,91	77	#10	1050	188	47	185	12000	25	12	INACCURATE
5/22,91	78	#10	1050	203	47	185	12000	20	7	INACCURATE
5/22,91	79	#10	1050	203	47	185	12000	25	7	INACCURATE
5/22,91	80	#10	1050	188	47	185	12000	29	7	INACCURATE
7/01,91	81	#13	1050	188	47	185	12000	30	12	

SINGLE CYLINDER ENGINE RUNS (SETUP)

DATE	RUN	INJECTOR	RPM	KW	MAP (PSI)	MAT (DEG F)	P-INJ (PSI)	TIME-CWS DEG BTDC	TIME-PIL DEG BTDC	NOTES
7/01,91	82	#13	1050	188	47	185	12000	40	12	
7/01,91	83	#13	1050	188	47	185	12000	50	12	
7/03,91	84	#13	1050	188	47	185	12000	40	12	
7/03,91	85	#13	1050	188	47	185	12000	30	12	
7/03,91	86	#13	1050	188	47	185	12000	30	15	
7/03,91	87	#13	1050	188	47	185	12000	40	15	
7/09,91	88	#0	1050	195	47	185	12000	35	15	INACCURATE
7/09,91	89	#0	1050	203	47	185	12000	35	15	INACCURATE
7/09,91	90	#0	590	16	17	185	6600	17	26	INACCURATE
7/11,91	91	#0	1050	188	47	185	12000	35	12	(NEW BATCH CWS
7/11,91	92	#0	950	88	23	170	12000	30	20	N5 FROM NOW ON
7/11,91	93	#0	950	88	23	170	12000	25	20	N5
7/11,91	94	#0	950	88	23	179	12000	20	20	N5
7/11,91	95	#0	950	88	23	170	12000	15	20	N5
7/12,91	96	#0	995	145	37	180	12000	25	18	N7
7/12,91	97	#0	995	145	37	180	12000	30	18	N7
7/12,91	98	#0	950	115	29	180	12000	30	19	N6
7/12,91	99	#0	950	115	29	180	12000	25	19	N6
7/12,91	100	#0	950	115	29	180	12000	20	19	N6
7/15,91	101	#0	888	42	17	160	7800	20	22	N4
7/15,91	102	#0	888	42	17	160	7800	15	22	N4
7/15,91	103	#0	888	36	16	160	7000	15	23	N3
7/15,91	104	#0	590	16	15	150	7000	15	24	N2

SINGLE CYLINDER ENGINE RUNS (SETUP)

DATE	RUN	INJECTOR	RPM	KW	MAP (PSI)	MAT (DEG F)	P-INJ (PSI)	TIME-CWS DEG BTDC	TIME-PIL DEG BTDC	NOTES
7/17,91	105	#0	1050	188	44	185	12000	35	12	
7/17,91	106	#0	1050	195	44	185	12000	35	15	
8/14,91	107	#0	1050	188	44	185	12000	35	15	
8/14,91	108	#0	1050	195	44	185	12000	35	15	
8/14,91	109	#0	1050	203	44	185	12000	35	15	
8/19,91	110	#0	995	145	37	180	12000	22	18	N7
8/19,91	111	#0	950	115	29	180	12000	18	19	N6
8/19,91	112	#0	950	88	23	170	12000	17	20	N5
8/21,91	113	#0	888	42	17	160	6700	16	22	N4
8/21,91	114	#0	888	36	16	160	5700	16	23	N3
8/21,91	115	#0	590	16	15	150	5200	15	24	N2
8/23,91	116	#0	1050	188	44	185	12000	40	28	8 MIC. CWS
8/23,91	117	#12	1050	188	44	185	12000	40	25	8 MIC. CWS

_____* PART OF CWS INJECTOR HOLES PLUGGED

SINGLE CYLINDER ENGINE RUNS (SETUP)
(8 MICRON COAL FUEL)

DATE	RUN	INJECTOR	RPM	KW	MAP (PSI)	MAT (DEG F)	P-INJ (PSI)	TIME-CWS DEG BTDC	TIME-PIL DEG BTDC	NOTES
1/21, 92	01'	#12	1050	188	44	185	12000	40	25	
1/21, 92	02'	#12	1050	188	44	185	12000	35	23	
1/22, 92	03'	#12	1050	188	44	185	12000	35	24	
1/22, 92	04'	#12	1050	188	44	185	12000	40	24	
1/22, 92	05'	#12	1050	188	44	185	12000	30	24	
1/23, 92	06'	#12	1050	188	44	185	12000	30	24	
2/20, 92	08'	#12	1050	188	44	185	12000	30	26	
2/20, 92	09'	#12	1050	188	44	185	12000	30	20	
3/12, 92	17'	#12	1050	188	44	185	12000	40	25	
3/12, 92	18'	#12	1050	188	44	185	12000	35	25	
3/13, 92	19'	#12	1050	188	44	185	12000	30	25	
3/13, 92	20'	#12	1050	188	44	185	12000	25	25	
3/13, 92	21'	#12	1050	188	44	185	12000	30	28	
3/13, 92	22'	#12	1050	188	44	185	12000	35	28	
3/16, 92	23'	#12	1050	188	44	185	12000	40	28	
3/16, 92	24'	#12	1050	188	44	185	12000	45	28	
3/19, 92	25'	#12	620	16	15	150	6800	19	26	N2
3/19, 92	26'	#12	888	36	16	160	7400	19	26	N3
3/19, 92	27'	#12	888	42	17	160	8400	19	26	N4
3/19, 92	28'	#12	970	88	23	170	12000	19	25	N5
3/19, 92	29'	#12	970	115	29	180	12000	20	25	N6
3/19, 92	30'	#12	970	145	37	180	12000	24	24	N7

HEAT RELEASE AND COMBUSTION ANALYSIS FOR CWS TESTS

ENTER: LOG NO., FILE NO. OF PRESSURE DATA, & RPM OF RUN
 13,113,1052
 ENTER THE MANIFOLD AIR PRESSURE (PSIA) & TEMPERATURE (DEG F)
 46.59,188.2
 ENTER TDC CORR.(+/- DEG), INJ ST(DEG BTDC) & INJ DURATION(DEG)
 -0.4,25,46

ENTER COAL FRACTION & DENSITY OF CWS USED: 0.496,1.088
 ENTER "1" FOR UKON OR "2" FOR TRITON USED IN CWS: 2
 ENTER COAL WT FRACTION OF TRITON USED IN CWS: 0.02
 ENTER CONSUMPTION (LB/SEC),TEMP(DEG F) OF CONSTITUENTS
 CWS: 5.6719E-2,69.9
 PILOT DIESEL: 1.2902E-3,63.4
 PURGE OIL: 1.8645E-4,85
 WT % OF COAL,PILOT DIESEL,PURGE OIL,TRITON & H2O IN FUEL
 47.9 % 2.2 % 0.2 % 1.0 % 48.7 %
 ENERGY % OF COAL,PILOT DIESEL,PURGE OIL,TRITON OF RUN
 92.9 % 5.5 % 0.6 % 1.0 %
 INJECTION PER STROKE OF CWS,PILOT DIESEL,PURGE OIL & TRITON
 2676 mm3/str 79 mm3/str 9 mm3/str 28 mm3/str
 TOTAL ENERGY IHP RATE: 1643176 KJ/HR 1557513 BTU/HR
 ** 20% PURGE OIL RETURNED TO FUEL TANK

HEAT RELEASE AND COMBUSTION ANALYSIS COMBUSTION TEST TR 4774 L13

HEAT RELEASE AND COMBUSTION ANALYSIS

ENTER NO. OF CYLINDERS: 4
 ENTER THE MANIFOLD AIR PRESSURE (PSIA) & TEMPERATURE (DEG F)
 14.117, 1052
 46.93, 187.2
 ENTER TDC CORR. (+/- DEG), INJ ST (DEG BTDC) & INJ DURATION (DEG)
 -0.4, 25.56

ENTER COAL FRACTION & DENSITY OF CWS USED: 0.496, 1.088
 ENTER "1" FOR UKON OR "2" FOR TRITON USED IN CWS: 2
 ENTER COAL WT FRACTION OF TRITON USED IN CWS: 0.02
 ENTER CONSUMPTION (LB/SEC), TEMP (DEG F) OF CONSTITUENTS
 CWS: 5.6038E-2, 68.99
 PILOT DIESEL: 1.3540E-3, 84.97
 PURGE OIL: 2.0282E-4, 85
 WT % OF COAL, PILOT DIESEL, PURGE OIL, TRITON & H2O IN FUEL
 47.8 % 2.4 % 0.3 % 1.0 % 48.6 %
 ENERGY % OF COAL, PILOT DIESEL, PURGE OIL, TRITON OF RUN
 92.5 % 5.8 % 0.7 % 1.0 %
 INJECTION PER STROKE OF CWS, PILOT DIESEL, PURGE OIL & TRITON
 2644 mm3/str 93 mm3/str 9 mm3/str 27 mm3/str
 TOTAL ENERGY INP RATE: 1629969 KJ/HR 1544994 BTU/HR
 ** 20% PURGE OIL RETURNED TO FUEL TANK

HEAT RELEASE AND COMBUSTION ANALYSIS TR:4774 L14

REPORT OF TEST SOLUTION FOR CWS TESTS

ENTER: LOG NO., FILE NO. OF PRESSURE DATA, & RPM OF RUN
 15,121,1051
 ENTER THE MANIFOLD AIR PRESSURE (PSIA) & TEMPERATURE (DEG F)
 46.57,189
 ENTER TDC CORR.(+/- DEG), INJ ST(DEG BTDC) & INJ DURATION(DEG)
 -0.4,25,67

ENTER COAL FRACTION & DENSITY OF CWS USED: 0.496,1.088
 ENTER "1" FOR UKON OR "2" FOR TRITON USED IN CWS: 2
 ENTER COAL WT FRACTION OF TRITON USED IN CWS: 0.02
 ENTER CONSUMPTION (LB/SEC),TEMP(DEG F) OF CONSTITUENTS
 CWS: 6.1165E-2,68.12
 PILOT DIESEL: 1.339E-3,96.31
 PURGE OIL: 2.0792E-4,85
 WT % OF COAL,PILOT DIESEL,PURGE OIL,TRITON & H2O IN FUEL
 47.9 % 2.1 % 0.2 % 1.0 % 48.7 %
 ENERGY % OF COAL,PILOT DIESEL,PURGE OIL,TRITON OF RUN
 93.0 % 5.3 % 0.6 % 1.0 %
 INJECTION PER STROKE OF CWS,PILOT DIESEL,PURGE OIL & TRITON
 2889 mm3/str 82 mm3/str 10 mm3/str 30 mm3/str
 TOTAL ENERGY INP RATE: 1768678 KJ/HR 1676472 BTU/HR
 ** 20% PURGE OIL RETURNED TO FUEL TANK

HEAT RELEASE AND COMBUSTION ANALYSIS TR 4774 L15

HEAT RELEASE CALCULATION FOR CWS TESTS

ENTER: LOG NO., FILE NO. OF PRESSURE DATA, & RPM OF RUN
 16.125.1052
 ENTER THE MANIFOLD AIR PRESSURE (PSIA) & TEMPERATURE (DEG F)
 46.6.187.4
 ENTER TDC CORR. (+/- DEG), INJ ST (DEG BTDC) & INJ DURATION (DEG)
 -.4.25.45

ENTER COAL FRACTION & DENSITY OF CWS USED: 0.493, 1.118
 ENTER "1" FOR UKON OR "2" FOR TRITON USED IN CWS: 2
 ENTER COAL WT FRACTION OF TRITON USED IN CWS: 0.02
 ENTER CONSUMPTION (LB/SEC), TEMP (DEG F) OF CONSTITUENTS
 CWS: 5.4172E-2, 72.4
 PILOT DIESEL: 1.3165E-3, 87
 PURGE OIL: 2.8695E-4, 85
 WT % OF COAL, PILOT DIESEL, PURGE OIL, TRITON & H2O IN FUEL
 47.5 % 2.4 % 0.3 % 1.0 % 48.9 %
 ENERGY % OF COAL, PILOT DIESEL, PURGE OIL, TRITON OF RUN
 92.4 % 5.9 % 0.7 % 1.0 %
 INJECTION PER STROKE OF CWS, PILOT DIESEL, PURGE OIL & TRITON
 2488 mm3/str 88 mm3/str 9 mm3/str 26 mm3/str
 TOTAL ENERGY INP RATE: 1567967 KJ/HR 1486224 BTU/HR
 ** 20% PURGE OIL RETURNED TO FUEL TANK

HEAT RELEASE AND COMBUSTION ANALYSIS TR 4774 L16

HEAT RELEASE CALCULATION FOR CWS TESTS

ENTER: LOG NO., FILE NO. OF PRESSURE DATA, & RPM OF RUN
 17.129.1050
 ENTER THE MANIFOLD AIR PRESSURE (PSIA) & TEMPERATURE (DEG F)
 46.61.187.1
 ENTER TDC CORR. (+/- DEG), INJ ST (DEG BTDC) & INJ DURATION (DEG)
 -0.4.25.57

ENTER COAL FRACTION & DENSITY OF CWS USED: 0.493.1.1178
 ENTER "1" FOR UKON OR "2" FOR TRITON USED IN CWS: 2
 ENTER COAL WT FRACTION OF TRITON USED IN CWS: 0.02
 ENTER CONSUMPTION (LB/SEC), TEMP (DEG F) OF CONSTITUENTS
 CWS: 5.9562E-2.70.72
 PILOT DIESEL: 1.3284E-3.90.36
 PURGE OIL: 2.1973E-4.85
 WT % OF COAL, PILOT DIESEL, PURGE OIL, TRITON & H2O IN FUEL
 47.6 % 2.2 % 0.3 % 1.0 % 49.0 %
 ENERGY % OF COAL, PILOT DIESEL, PURGE OIL, TRITON OF RUN
 92.9 % 5.4 % 0.7 % 1.0 %
 INJECTION PER STROKE OF CWS, PILOT DIESEL, PURGE OIL & TRITON
 2738 mm3/str 81 mm3/str 10 mm3/str 29 mm3/str
 TOTAL ENERGY IHP RATE: 1715237 KJ/HR 1625817 BTU/HR
 ** 20% PURGE OIL RETURNED TO FUEL TANK

HEAT RELEASE AND COMBUSTION ANALYSIS TR 4774 L17

HEAT RELEASE CALCULATION FOR CWS TESTS

ENTER: LOG NO., FILE NO. OF PRESSURE DATA, & RPM OF RUN
18,133,1050

ENTER THE MANIFOLD AIR PRESSURE (PSIA) & TEMPERATURE (DEG F)
46.66,197

ENTER TDC CORR.(+/- DEG), INJ ST(DEG BTDC) & INJ DURATION(DEG)
-0.4,25,66

ENTER COAL FRACTION & DENSITY OF CWS USED: 0.493,1.1178

ENTER "1" FOR UKON OR "2" FOR TRITON USED IN CWS: 2

ENTER COAL WT FRACTION OF TRITON USED IN CWS: 0.02

ENTER CONSUMPTION (LB/SEC),TEMP(DEG F) OF CONSTITUENTS

CWS: 5.9690E-2,69.4

PILOT DIESEL: 1.3325E-3,92.13

PURGE OIL: 2.4111E-4,85

WT % OF COAL,PILOT DIESEL,PURGE OIL,TRITON & H2O IN FUEL

47.6 % 2.2 % 0.3 % 1.0 % 49.0 %

ENERGY % OF COAL,PILOT DIESEL,PURGE OIL,TRITON OF RUN

92.8 % 5.4 % 0.7 % 1.0 %

INJECTION PER STROKE OF CWS,PILOT DIESEL,PURGE OIL & TRITON

2747 mm3/str 81 mm3/str 11 mm3/str 29 mm3/str

TOTAL ENERGY INP RATE: 1720107 KJ/HR 1630433 BTU/HR

** 20% PURGE OIL RETURNED TO FUEL TANK

HEAT RELEASE AND COMBUSTION ANALYSIS

TR 4774 L18

HEAT RELEASE CALCULATION FOR CWS TESTS

ENTER: LOG NO., FILE NO. OF PRESSURE DATA, & RPM OF RUN
 19,137,1053
 ENTER THE MANIFOLD AIR PRESSURE (PSIA) & TEMPERATURE (DEG F)
 46.59,188.1
 ENTER TDC CORR.(+/- DEG), INJ ST(DEG BTDC) & INJ DURATION(DEG)
 -0.4,25,56

ENTER COAL FRACTION & DENSITY OF CWS USED; 0.493,1.11
 ENTER "1" FOR UKOH OR "2" FOR TRITON USED IN CWS: 2
 ENTER COAL WT FRACTION OF TRITON USED IN CWS: 0.02
 ENTER CONSUMPTION (LB/SEC),TEMP(DEG F) OF CONSTITUENTS
 CWS: 5.7641E-2,69.62
 PILOT DIESEL: 1.2657E-3,87.94
 PURGE OIL: 2.0664E-4,85
 WT % OF COAL,PILOT DIESEL,PURGE OIL,TRITON & H2O IN FUEL
 47.6 % 2.1 % 0.3 % 1.0 % 49.0 %
 ENERGY % OF COAL,PILOT DIESEL,PURGE OIL,TRITON OF RUN
 93.0 % 5.3 % 0.7 % 1.0 %
 INJECTION PER STROKE OF CWS,PILOT DIESEL,PURGE OIL & TRITON
 2664 mm3/str 77 mm3/str 9 mm3/str 28 mm3/str
 TOTAL ENERGY IHP RATE: 1658214 KJ/HR 1571766 BTU/HR
 ** 20% PURGE OIL RETURNED TO FUEL TANK

HEAT RELEASE AND COMBUSTION ANALYSIS TR 4774 L19

HEAT RELEASE CALCULATION FOR CWS TESTS

ENTER: LOG NO., FILE NO. OF PRESSURE DATA, & RPN OF RUN
 20,141,1052
 ENTER THE MANIFOLD AIR PRESSURE (PSIA) & TEMPERATURE (DEG F)
 46.6,187.9
 ENTER TDC CORR.(+/- DEG), INJ ST(DEG BTDC) & INJ DURATION(DEG)
 -0.4,28,55

ENTER COAL FRACTION & DENSITY OF CWS USED: 0.493,1.11
 ENTER "1" FOR UKON OR "2" FOR TRITON USED IN CWS: 2
 ENTER COAL WT FRACTION OF TRITON USED IN CWS: 0.02
 ENTER CONSUMPTION (LB/SEC),TEMP(DEG F) OF CONSTITUENTS
 CWS: 5.6491E-2,70.45
 PILOT DIESEL: 1.3095E-3,90.57
 PURGE OIL: 1.9175E-4,85
 WT % OF COAL,PILOT DIESEL,PURGE OIL,TRITON & H2O IN FUEL
 47.6 % 2.3 % 0.2 % 1.0 % 48.9 %
 ENERGY % OF COAL,PILOT DIESEL,PURGE OIL,TRITON OF RUN
 92.7 % 5.6 % 0.6 % 1.0 %
 INJECTION PER STROKE OF CWS,PILOT DIESEL,PURGE OIL & TRITON
 2613 mm3/str 80 mm3/str 9 mm3/str 27 mm3/str
 TOTAL ENERGY INP RATE: 1629395 KJ/HR 1544450 BTU/HR
 ** 20% PURGE OIL RETURNED TO FUEL TANK

HEAT RELEASE AND COMBUSTION ANALYSIS TR 4774 L20

HEAT RELEASE CALCULATION FOR CWS TESTS

ENTER: LOG NO., FILE NO. OF PRESSURE DATA, & RPM OF RUN
 21,145,1051
 ENTER THE MANIFOLD AIR PRESSURE (PSIA) & TEMPERATURE (DEG F)
 46.82,188.2
 ENTER TDC CORR.(+/- DEG), INJ ST(DEG BTDC) & INJ DURATION(DEG)
 -0.4,20,59

ENTER COAL FRACTION & DENSITY OF CWS USED: 0.493,1.11
 ENTER "1" FOR UKOH OR "2" FOR TRITON USED IN CWS: 2
 ENTER COAL WT FRACTION OF TRITON USED IN CWS: 0.02
 ENTER CONSUMPTION (LB/SEC),TEMP(DEG F) OF CONSTITUENTS
 CWS: 5.9609E-2,70.8
 PILOT DIESEL: 1.2989E-3,92.67
 PURGE OIL: 2.2741E-4,85
 WT % OF COAL,PILOT DIESEL,PURGE OIL,TRITON & H2O IN FUEL
 47.6 % 2.1 % 0.3 % 1.0 % 49.0 %
 ENERGY % OF COAL,PILOT DIESEL,PURGE OIL,TRITON OF RUN
 93.0 % 5.3 % 0.7 % 1.0 %
 INJECTION PER STROKE OF CWS,PILOT DIESEL,PURGE OIL & TRITON
 2760 mm3/str 79 mm3/str 10 mm3/str 29 mm3/str
 TOTAL ENERGY INP RATE: 1714821 KJ/HR 1625423 BTU/HR
 ** 20% PURGE OIL RETURNED TO FUEL TANK

HEAT RELEASE AND COMBUSTION ANALYSIS TR 4774 L21

ENTER: LOW P. - HIGH P. AIR PRESSURE DATA, & RPM OF RUN
 11,143,145
 ENTER THE AMBIENT AIR PRESSURE (PSIA) & TEMPERATURE (DEG F)
 14.24,187.7
 ENTER IDC (DEG BTDC), INJ ST (DEG BTDC) & INJ DURATION (DEG)
 -0.4,28.55

ENTER COAL FRACTION & DENSITY OF CWS USED: 0.498,1.0856
 ENTER "1" FOR UNION OR "2" FOR TRITON USED IN CWS: 2
 ENTER COAL WT FRACTION OF TRITON USED IN CWS: 0.02
 ENTER CONSUMPTION (LB/SEC),TEMP (DEG F) OF CONSTITUENTS
 CWS: 5.4427E-2,67.31
 PILOT DIESEL: 1.1891E-3,84.33
 PURGE OIL: 1.8309E-4,85
 WT % OF COAL,PILOT DIESEL,PURGE OIL,TRITON & H2O IN FUEL
 48.1 % 2.1 % 0.2 % 1.0 % 48.5 %
 ENERGY % OF COAL,PILOT DIESEL,PURGE OIL,TRITON OF RUN
 93.1 % 5.3 % 0.6 % 1.0 %
 INJECTION PER STROKE OF CWS,PILOT DIESEL,PURGE OIL & TRITON
 2571 mm3/str 72 mm3/str 8 mm3/str 26 mm3/str
 TOTAL ENERGY IHP RATE: 1579524 KJ/HR 1497179 BTU/HR
 ** 20% PURGE OIL RETURNED TO FUEL TANK

HEAT RELEASE AND COMBUSTION ANALYSIS TR 4774 L22

HEAT RELEASE CALCULATION FOR CWS TESTS

ENTER: LOG NO., FILE NO. OF PRESSURE DATA, & RPM OF RUN
 23,153,1052
 ENTER THE MANIFOLD AIR PRESSURE (PSIA) & TEMPERATURE (DEG F)
 49.7,187.6
 ENTER TDC CORR.(+/- DEG), INJ ST(DEG BTDC) & INJ DURATION(DEG)
 -0.4,20,50

ENTER COAL FRACTION & DENSITY OF CWS USED: 0.498,1.0856
 ENTER "1" FOR UKON OR "2" FOR TRITON USED IN CWS: 2
 ENTER COAL WT FRACTION OF TRITON USED IN CWS: 0.02
 ENTER CONSUMPTION (LB/SEC),TEMP(DEG F) OF CONSTITUENTS
 CWS: 5.7461E-2,68.25
 PILOT DIESEL: 1.2586E-3,87.1
 PURGE OIL: 2.0042E-4,85
 WT % OF COAL,PILOT DIESEL,PURGE OIL,TRITON & H2O IN FUEL
 48.1 % 2.1 % 0.3 % 1.0 % 48.5 %
 ENERGY % OF COAL,PILOT DIESEL,PURGE OIL,TRITON OF RUN
 93.1 % 5.3 % 0.6 % 1.0 %
 INJECTION PER STROKE OF CWS,PILOT DIESEL,PURGE OIL & TRITON
 2717 mm3/str 77 mm3/str 9 mm3/str 28 mm3/str
 TOTAL ENERGY IHP RATE: 1668128 KJ/HR 1591164 BTU/HR
 ** 20% PURGE OIL RETURNED TO FUEL TANK

HEAT RELEASE AND COMBUSTION ANALYSIS TR 4774 L23

HEAT RELEASE CALCULATION FOR CWS TESTS

ENTER: LOG NO., FILE NO. OF PRESSURE DATA, & RPM OF RUN
 24,157,1052
 ENTER THE MANIFOLD AIR PRESSURE (PSIA) & TEMPERATURE (DEG F)
 48.23,187.9
 ENTER TDC CORR.(+/- DEG), INJ ST(DEG BTDC) & INJ DURATION(DEG)
 -0.4,23.46

ENTER COAL FRACTION & DENSITY OF CWS USED: 0.498,1.0856
 ENTER "1" FOR UKON OR "2" FOR TRITON USED IN CWS: 2
 ENTER COAL WT FRACTION OF TRITON USED IN CWS: 0.02
 ENTER CONSUMPTION (LB/SEC),TEMP(DEG F) OF CONSTITUENTS
 CWS: 5.5659E-2,70.83
 PILOT DIESEL: 1.2403E-3,85.52
 PURGE OIL: 1.9554E-4,85
 WT % OF COAL,PILOT DIESEL,PURGE OIL,TRITON & H2O IN FUEL
 48.1 % 2.2 % 0.2 % 1.0 % 48.5 %
 ENERGY % OF COAL,PILOT DIESEL,PURGE OIL,TRITON OF RUN
 93.8 % 5.4 % 0.6 % 1.0 %
 INJECTION PER STROKE OF CWS,PILOT DIESEL,PURGE OIL & TRITON
 2632 mm3/str 76 mm3/str 8 mm3/str 27 mm3/str
 TOTAL ENERGY INP RATE: 1616845 KJ/HR 1532554 BTU/HR
 ** 20% PURGE OIL RETURNED TO FUEL TANK

HEAT RELEASE AND COMBUSTION ANALYSIS TR 4774 L24

HEAT RELEASE CALCULATION FOR CWS TESTS

ENTER: LOG NO., FILE NO. OF PRESSURE DATA, & RPM OF RUN
25,161,1053

ENTER THE MANIFOLD AIR PRESSURE (PSIA) & TEMPERATURE (DEG F)
48.2,187.1

ENTER TDC CORR.(+/- DEG), INJ ST(DEG BTDC) & INJ DURATION(DEG)
-0.4,25,56

ENTER COAL FRACTION & DENSITY OF CWS USED: 0.49,1.076

ENTER "1" FOR UKON OP "2" FOR TRITON USED IN CWS: 2

ENTER COAL WT FRACTION OF TRITON USED IN CWS: 0.02

ENTER CONSUMPTION (LB/SEC),TEMP(DEG F) OF CONSTITUENTS

CWS: 5.6082E-2,69.7

PILOT DIESEL: 1.2174E-3,90.89

PURGE OIL: 2.2336E-4,85

WT % OF COAL,PILOT DIESEL,PURGE OIL,TRITON & H2O IN FUEL

47.4 % 2.1 % 0.3 % 0.9 % 49.3 %

ENERGY % OF COAL,PILOT DIESEL,PURGE OIL,TRITON OF RUN

93.0 % 5.3 % 0.7 % 1.0 %

INJECTION PER STROKE OF CWS,PILOT DIESEL,PURGE OIL & TRITON

2702 mm3/str 74 mm3/str 10 mm3/str 27 mm3/str

TOTAL ENERGY IHP RATE: 1628540 KJ/HR 1536057 BTU/HR

** 20% PURGE OIL RETURNED TO FUEL TANK

HEAT RELEASE AND COMBUSTION ANALYSIS TR 4774 L25

HEAT RELEASE CALCULATION FOR CWS TESTS

ENTER: LOG NO., FILE NO. OF PRESSURE DATA, & RPM OF RUN
 26.165,1051
 ENTER THE MANIFOLD AIR PRESSURE (PSIA) & TEMPERATURE (DEG F)
 48.2,197.2
 ENTER TDC CORR. (4/- DEG), INJ ST (DEG BTDC) & INJ DURATION (DEG)
 -0.4,15.67

ENTER COAL FRACTION & DENSITY OF CWS USED: 0.49,1.076
 ENTER "1" FOR UKON OR "2" FOR TRITON USED IN CWS: 2
 ENTER COAL WT FRACTION OF TRITON USED IN CWS: 0.02
 ENTER CONSUMPTION (LB/SEC), TEMP (DEG F) OF CONSTITUENTS
 CWS: 6.6710E-2,70.6
 PILOT DIESEL: 1.2406E-3,92.3
 PURGE OIL: 2.2796E-4,85
 WT % OF COAL, PILOT DIESEL, PURGE OIL, TRITON & H2O IN FUEL
 47.5 % 1.8 % 0.3 % 1.0 % 49.5 %
 ENERGY % OF COAL, PILOT DIESEL, PURGE OIL, TRITON OF RUN
 93.7 % 4.6 % 0.6 % 1.0 %
 INJECTION PER STROKE OF CWS, PILOT DIESEL, PURGE OIL & TRITON
 3186 mm3/str 76 mm3/str 10 mm3/str 32 mm3/str
 TOTAL ENERGY INP RATE: 1891968 KJ/HR 1793335 BTU/HR
 ** 20% PURGE OIL RETURNED TO FUEL TANK

HEAT RELEASE AND COMBUSTION ANALYSIS TR 4774 L26

HEAT RELEASE CALCULATION FOR CWS TESTS

ENTER: LOG NO., FILE NO. OF PRESSURE DATA, & RPM OF RUN
 27,169,1051
 ENTER THE MANIFOLD AIR PRESSURE (PSIA) & TEMPERATURE (DEG F)
 48.1,187.2
 ENTER TDC CORR.(+/- DEG), INJ ST(DEG BTDC) & INJ DURATION(DEG)
 -0.4,35,53

ENTER COAL FRACTION & DENSITY OF CWS USED: 0.49,1.076
 ENTER "1" FOR UKON OR "2" FOR TRITON USED IN CWS: 2
 ENTER COAL WT FRACTION OF TRITON USED IN CWS: 0.02
 ENTER CONSUMPTION (LB/SEC),TEMP(DEG F) OF CONSTITUENTS
 CWS: 5.5404E-2,71.14
 PILOT DIESEL: 1.2160E-3,91.34
 PURGE OIL: 2.0502E-4,85
 WT % OF COAL,PILOT DIESEL,PURGE OIL,TRITON & H2O IN FUEL
 47.4 % 2.1 % 0.3 % 0.9 % 49.3 %
 ENERGY % OF COAL,PILOT DIESEL,PURGE OIL,TRITON OF RUN
 92.9 % 5.4 % 0.7 % 1.0 %
 INJECTION PER STROKE OF CWS,PILOT DIESEL,PURGE OIL & TRITON
 2646 mm3/str 74 mm3/str 9 mm3/str 27 mm3/str
 TOTAL ENERGY INP RATE: 1585126 KJ/HR 1502489 BTU/HR
 ** 20% PURGE OIL RETURNED TO FUEL TANK

HEAT RELEASE AND COMBUSTION ANALYSIS TR 4774 L27

HEAT RELEASE CALCULATION FOR CWS TESTS

ENTER: LOG NO., FILE NO. OF PRESSURE DATA, & RPM OF RUN
 28,173,1053
 ENTER THE MANIFOLD AIR PRESSURE (PSIA) & TEMPERATURE (DEG F)
 48.0,188.1
 ENTER TDC CORR.(+/- DEG), INJ ST(DEG BTDC) & INJ DURATION(DEG)
 -0.4,25,58

ENTER COAL FRACTION & DENSITY OF CWS USED: 0.49,1.0995
 ENTER "1" FOR UKON OR "2" FOR TRITON USED IN CWS: 2
 ENTER COAL WT FRACTION OF TRITON USED IN CWS: 0.02
 ENTER CONSUMPTION (LB/SEC),TEMP(DEG F) OF CONSTITUENTS
 CWS: 5.6781E-2,67.17
 PILOT DIESEL: 1.1909E-3,84.05
 PURGE OIL: 1.3190E-4,85
 WT % OF COAL,PILOT DIESEL,PURGE OIL,TRITON & H2O IN FUEL
 47.4 % 2.1 % 0.2 % 0.9 % 49.4 %
 ENERGY % OF COAL,PILOT DIESEL,PURGE OIL,TRITON OF RUN
 93.4 % 5.2 % 0.4 % 1.0 %
 INJECTION PER STROKE OF CWS,PILOT DIESEL,PURGE OIL & TRITON
 2649 mm3/str 73 mm3/str 6 mm3/str 27 mm3/str
 TOTAL ENERGY IHP RATE: 1616550 KJ/HR 1532275 BTU/HR
 ** 20% PURGE OIL RETURNED TO FUEL TANK

HEAT RELEASE AND COMBUSTION ANALYSIS TR 4774 L28

HEAT RELEASE CALCULATION FOR CWS TESTS

ENTER: LOG NO., FILE NO. OF PRESSURE DATA, & RPM OF RUN
 29,177,1051
 ENTER THE MANIFOLD AIR PRESSURE (PSIA) & TEMPERATURE (DEG F)
 48.2,187.9
 ENTER TDC CORR.(+/- DEG), INJ ST(DEG BTDC) & INJ DURATION(DEG)
 -0.4,25,59

ENTER COAL FRACTION & DENSITY OF CWS USED: 0.49,1.0995
 ENTER "1" FOR UKON OR "2" FOR TRITON USED IN CWS: 2
 ENTER COAL WT FRACTION OF TRITON USED IN CWS: 0.02
 ENTER CONSUMPTION (LB/SEC), TEMP(DEG F) OF CONSTITUENTS
 CWS: 5.8173E-2,68.63
 PILOT DIESEL: 1.1636E-3,87.13
 PURGE OIL: 2.0195E-4,85
 WT % OF COAL,PILOT DIESEL,PURGE OIL,TRITON & H2O IN FUEL
 47.5 % 2.0 % 0.3 % 0.9 % 49.4 %
 ENERGY % OF COAL,PILOT DIESEL,PURGE OIL,TRITON OF RUN
 93.4 % 4.9 % 0.6 % 1.0 %
 INJECTION PER STROKE OF CWS,PILOT DIESEL,PURGE OIL & TRITON
 2719 mm3/str 71 mm3/str 9 mm3/str 28 mm3/str
 TOTAL ENERGY IHP RATE: 1655734 KJ/HR 1569416 BTU/HR
 ** 20% PURGE OIL RETURNED TO FUEL TANK

HEAT RELEASE AND COMBUSTION ANALYSIS TR 4774 L29

HEAT RELEASE CALCULATION FOR CWS TESTS

ENTER: LOG NO., FILE NO. OF PRESSURE DATA, & RPM OF RUN
 30.1, 1050
 ENTER THE MANIFOLD AIR PRESSURE (PSIA) & TEMPERATURE (DEG F)
 48.1, 187.5
 ENTER TDC CORR. (+/- DEG), INJ ST (DEG BTDC) & INJ DURATION (DEG)
 -0.4, 25, 62

ENTER COAL FRACTION & DENSITY OF CWS USED: 0.49, 1.0995
 ENTER "1" FOR UKON OR "2" FOR TRITON USED IN CWS: 2
 ENTER COAL WT FRACTION OF TRITON USED IN CWS: 0.02
 ENTER CONSUMPTION (LB/SEC), TEMP (DEG F) OF CONSTITUENTS
 CWS: 6.0025E-2, 69.23
 PILOT DIESEL: 1.1654E-3, 89.51
 PURGE OIL: 1.6172E-4, 85
 WT % OF COAL, PILOT DIESEL, PURGE OIL, TRITON & H2O IN FUEL
 47.5 % 1.9 % 0.2 % 1.0 % 49.5 %
 ENERGY % OF COAL, PILOT DIESEL, PURGE OIL, TRITON OF RUN
 93.7 % 4.7 % 0.5 % 1.0 %
 INJECTION PER STROKE OF CWS, PILOT DIESEL, PURGE OIL & TRITON
 2846 mm3/str 71 mm3/str 7 mm3/str 29 mm3/str
 TOTAL ENERGY INP RATE: 1725038 KJ/HR 1635107 BTU/HR
 ** 20% PURGE OIL RETURNED TO FUEL TANK

HEAT RELEASE AND COMBUSTION ANALYSIS TR 4774 L30

HEAT RELEASE AND COMBUSTION ANALYSIS

ENTER: LOG NO., FILE NO. OF PREFERENCE DATA, & RPM OF RUN
 31.5, 1053
 ENTER THE MANIFOLD AIR PRESSURE (PSIA) & TEMPERATURE (DEG F)
 46.97, 187.8
 ENTER TDC CORR. (+/- DEG), INJ ST (DEG BTDC) & INJ DURATION (DEG)
 -0.4, 22.48

ENTER COAL FRACTION & DENSITY OF CWS USED: 0.496, 1.09
 ENTER "1" FOR UKON OR "2" FOR TRITON USED IN CWS: 2
 ENTER COAL WT FRACTION OF TRITON USED IN CWS: 0.02
 ENTER CONSUMPTION (LB/SEC), TEMP (DEG F) OF CONSTITUENTS

CWS: 5.528E-2, 68.6
 PILOT DIESEL: 1.1689E-3, 80.96
 PURGE OIL: 1.8739E-4, 85

WT % OF COAL, PILOT DIESEL, PURGE OIL, TRITON & H2O IN FUEL

48.8 % 2.1 % 0.2 % 1.0 % 48.8 %

ENERGY % OF COAL, PILOT DIESEL, PURGE OIL, TRITON OF RUN

93.2 % 5.1 % 0.6 % 1.0 %

INJECTION PER STROKE OF CWS, PILOT DIESEL, PURGE OIL & TRITON

2604 mm3/str 71 mm3/str 9 mm3/str 27 mm3/str

TOTAL ENERGY INP RATE: 1595590 KJ/HR 1512400 BTU/HR

** 20% PURGE OIL RETURNED TO FUEL TANK

HEAT RELEASE AND COMBUSTION ANALYSIS TR 4774 L31

INJ ST: 22.4 DEG BTDC IGN ST: 10.0 DEG BTDC IGN LAG: 12.4 DEG CA

HEAT RELEASE CALCULATION FOR CWS TESTS

ENTER: LOG NO., FILE NO. OF PRESSURE DATA, & RPM OF RUN
32,9,1053

ENTER THE MANIFOLD AIR PRESSURE (PSIA) & TEMPERATURE (DEG F)
47.71,186.9

ENTER TDC CORR.(+/- DEG), INJ ST(DEG BTDC) & INJ DURATION(DEG)
-0.4,27.46

ENTER COAL FRACTION & DENSITY OF CWS USED: 0.493,1.088

ENTER "1" FOR UKON OR "2" FOR TRITON USED IN CWS: 2

ENTER COAL WT FRACTION OF TRITON USED IN CWS: 0.02

ENTER CONSUMPTION (LB/SEC),TEMP(DEG F) OF CONSTITUENTS

CWS: 5.4493E-2,70.7

PILOT DIESEL: 1.1359E-3,84.41

PURGE OIL: 2.0861E-4,85

WT % OF COAL,PILOT DIESEL,PURGE OIL,TRITON & H2O IN FUEL

47.6 % 2.1 % 0.3 % 1.0 % 49.0 %

ENERGY % OF COAL,PILOT DIESEL,PURGE OIL,TRITON OF RUN

92.9 % 5.3 % 0.7 % 1.0 %

INJECTION PER STROKE OF CWS,PILOT DIESEL,PURGE OIL & TRITON

2569 mm3/str 73 mm3/str 18 mm3/str 26 mm3/str

TOTAL ENERGY INP RATE: 1568300 KJ/HR 1466540 BTU/HR

** 20% PURGE OIL RETURNED TO FUEL TANK

HEAT RELEASE AND COMBUSTION ANALYSIS TR 4774 L32

HEAT RELEASE CALCULATION FOR CWS TESTS

ENTER: LOG NO., FILE NO. OF PRESSURE DATA, & RPM OF RUN
33,13,1052

ENTER THE MANIFOLD AIR PRESSURE (PSIA) & TEMPERATURE (DEG F)
47.69,187.1

ENTER TDC CORR.(+/- DEG), INJ ST(DEG BTDC) & INJ DURATION(DEG)
-0.4,32,45

ENTER COAL FRACTION & DENSITY OF CWS USED: 0.493,1.088

ENTER "1" FOR UKON OR "2" FOR TRITON USED IN CWS: 2

ENTER COAL WT FRACTION OF TRITON USED IN CWS: 0.02

ENTER CONSUMPTION (LB/SEC),TEMP(DEG F) OF CONSTITUENTS

CWS: 5.3714E-2,71.8

PILOT DIESEL: 1.2112E-3,97.9

PURGE OIL: 2.462E-4,85

WT % OF COAL,PILOT DIESEL,PURGE OIL,TRITON & H2O IN FUEL

47.6 % 2.2 % 0.3 % 1.0 % 48.9 %

ENERGY % OF COAL,PILOT DIESEL,PURGE OIL,TRITON OF RUN

92.7 % 5.5 % 0.8 % 1.0 %

INJECTION PER STROKE OF CWS,PILOT DIESEL,PURGE OIL & TRITON

2535 mm3/str 74 mm3/str 11 mm3/str 26 mm3/str

TOTAL ENERGY IHP RATE: 1550275 KJ/HR 1469455 BTU/HR

** 20% PURGE OIL RETURNED TO FUEL TANK

HEAT RELEASE AND COMBUSTION ANALYSIS

TR 4774 L33

HEAT RELEASE CALCULATION FOR CWS TESTS

ENTER: LOG NO., FILE NO. OF PRESSURE DATA, & RPM OF RUN
 34,17,1053
 ENTER THE MANIFOLD AIR PRESSURE (PSIA) & TEMPERATURE (DEG F)
 47.28,186.7
 ENTER TDC CORR.(+/- DEG), INJ ST(DEG BTDC) & INJ DURATION(DEG)
 -0.4,32,45

ENTER COAL FRACTION & DENSITY OF CWS USED: 0.498,1.127
 ENTER "1" FOR UKON OR "2" FOR TRITON USED IN CWS: 2
 ENTER COAL WT FRACTION OF TRITON USED IN CWS: 0.02
 ENTER CONSUMPTION (LB/SEC),TEMP(DEG F) OF CONSTITUENTS

CWS: 5.3975E-2,70.9

PILOT DIESEL: 1.2294E-3,86.71

PURGE OIL: 2.1311E-4,85

WT % OF COAL,PILOT DIESEL,PURGE OIL,TRITON & H2O IN FUEL

48.1 % 2.2 % 0.3 % 1.0 % 48.5 %

ENERGY % OF COAL,PILOT DIESEL,PURGE OIL,TRITON OF RUN

92.8 % 5.5 % 0.7 % 1.0 %

INJECTION PER STROKE OF CWS,PILOT DIESEL,PURGE OIL & TRITON

2456 mm3/str 75 mm3/str 10 mm3/str 26 mm3/str

TOTAL ENERGY INP RATE: 1571529 KJ/HR 1489601 BTU/HR

** 20% PURGE OIL RETURNED TO FUEL TANK

HEAT RELEASE AND COMBUSTION ANALYSIS TR 4774 L34

HEAT RELEASE CALCULATION FOR CWS TESTS

ENTER: LOG NO., FILE NO. OF PRESSURE DATA, & RPM OF RUN
 35,21,1052
 ENTER THE MANIFOLD AIR PRESSURE (PSIA) & TEMPERATURE (DEG F)
 47.19,187.1
 ENTER TDC CORR.(+/- DEG), INJ ST(DEG BTDC) & INJ DURATION(DEG)
 -0.4,27,47

ENTER COAL FRACTION & DENSITY OF CWS USED: 0.498,1.127
 ENTER "1" FOR UKON OR "2" FOR TRITON USED IN CWS: 2
 ENTER COAL WT FRACTION OF TRITON USED IN CWS: 0.02
 ENTER CONSUMPTION (LB/SEC),TEMP(DEG F) OF CONSTITUENTS
 CWS: 5.483E-2,72.15
 PILOT DIESEL: 1.2517E-3,90.32
 PURGE OIL: 2.1046E-4,85
 WT % OF COAL,PILOT DIESEL,PURGE OIL,TRITON & H2O IN FUEL
 49.1 % 2.2 % 0.3 % 1.0 % 48.5 %
 ENERGY % OF COAL,PILOT DIESEL,PURGE OIL,TRITON OF RUN
 92.8 % 5.5 % 0.7 % 1.0 %
 INJECTION PER STROKE OF CWS,PILOT DIESEL,PURGE OIL & TRITON
 2498 mm3/str 76 mm3/str 10 mm3/str 27 mm3/str
 TOTAL ENERGY INP RATE: 1596304 KJ/HR 1513095 BTU/HR
 ** 20% PURGE OIL RETURNED TO FUEL TANK

HEAT RELEASE AND COMBUSTION ANALYSIS TR 4774 L35

HEAT RELEASE CALCULATION FOR CWS TESTS

ENTER: LOG NO., FILE NO. OF PRESSURE DATA, & RPM OF RUN
 36,25,1051
 ENTER THE MANIFOLD AIR PRESSURE (PSIA) & TEMPERATURE (DEG F)
 47.13,187.3
 ENTER TDC CORR.(+/- DEG), INJ ST(DEG BTDC) & INJ DURATION(DEG)
 -.04,32,45

ENTER COAL FRACTION & DENSITY OF CWS USED: 0.498,1.127
 ENTER "1" FOR UKON OR "2" FOR TRITON USED IN CWS: 2
 ENTER COAL WT FRACTION OF TRITON USED IN CWS: 0.02
 ENTER CONSUMPTION (LB/SEC),TEMP(DEG F) OF CONSTITUENTS
 CWS: 5.3953E-2,72.85
 PILOT DIESEL: 1.2668E-3,94.24
 PURGE OIL: 1.1196E-4,95
 WT % OF COAL,PILOT DIESEL,PURGE OIL,TRITON & H2O IN FUEL
 48.1 % 2.3 % 0.2 % 1.0 % 48.5 %
 ENERGY % OF COAL,PILOT DIESEL,PURGE OIL,TRITON OF RUN
 92.9 % 5.5 % 0.4 % 1.0 %
 INJECTION PER STROKE OF CWS,PILOT DIESEL,PURGE OIL & TRITON
 2460 mm3/str 77 mm3/str 5 mm3/str 26 mm3/str
 TOTAL ENERGY INP RATE: 1568232 KJ/HR 1486476 BTU/HR
 ** 20% PURGE OIL RETURNED TO FUEL TANK

HEAT RELEASE AND COMBUSTION ANALYSIS TR 4774 L36

HEAT RELEASE CALCULATION FOR CWS TESTS

ENTER: LOG NO., FILE NO. OF PRESSURE DATA, & RPM OF RUN
 37.29,1051
 ENTER THE MANIFOLD AIR PRESSURE (PSIA) & TEMPERATURE (DEG F)
 47.2,187.3
 ENTER TDC CORR.(+/- DEG), INJ ST(DEG BTDC) & INJ DURATION(DEG)
 -0.4,37,46

ENTER COAL FRACTION & DENSITY OF CWS USED: 0.498,1.127
 ENTER "1" FOR UKON OR "2" FOR TRITON USED IN CWS: 2
 ENTER COAL WT FRACTION OF TRITON USED IN CWS: 0.02
 ENTER CONSUMPTION (LB/SEC), TEMP(DEG F) OF CONSTITUENTS
 CWS: 5.4389E-2,72.9
 PILOT DIESEL: 1.2446E-3,94
 PURGE OIL: 2.3355E-4,85
 WT % OF COAL,PILOT DIESEL,PURGE OIL,TRITON & H2O IN FUEL
 48.1 % 2.2 % 0.3 % 1.0 % 48.4 %
 ENERGY % OF COAL,PILOT DIESEL,PURGE OIL,TRITON OF RUN
 92.7 % 5.5 % 0.8 % 1.0 %
 INJECTION PER STROKE OF CWS,PILOT DIESEL,PURGE OIL & TRITON
 2490 mm3/str 76 mm3/str 11 mm3/str 27 mm3/str
 TOTAL ENERGY IHP RATE: 1524973 KJ/HR 1502344 BTU/HR
 ** 20% PURGE OIL RETURNED TO FUEL TANK

HEAT RELEASE AND COMBUSTION ANALYSIS TR 4774 L37

HEAT RELEASE AND COMBUSTION ANALYSIS FOR CWS TESTS

ENTER: LOG NO., FILE NO. OF PRESSURE DATA, & RPM OF RUN
 29.33, 1057
 ENTER THE MANIFOLD AIR PRESSURE (PSIA) & TEMPERATURE (DEG F)
 46.93, 187.0
 ENTER TDC CORR. (DEG), INJ ST (DEG BTDC) & INJ DURATION (DEG)
 -0.4, 42.57

ENTER COAL FRACTION & DENSITY OF CWS USED: 0.5, 1.095
 ENTER "1" FOR UKON OR "2" FOR TRITON USED IN CWS: 2
 ENTER COAL WT FRACTION OF TRITON USED IN CWS: 0.02
 ENTER CONSUMPTION (LB/SEC), TEMP (DEG F) OF CONSTITUENTS
 CWS: 5.4087E-2, 73.55
 PILOT DIESEL: 1.6445E-3, 99.6
 PURGE OIL: 2.1916E-4, 85
 WT % OF COAL, PILOT DIESEL, PURGE OIL, TRITON & H2O IN FUEL
 47.9 % 0.9 % 0.3 % 1.0 % 47.9 %
 ENERGY % OF COAL, PILOT DIESEL, PURGE OIL, TRITON OF RUN
 91.1 % 7.1 % 0.7 % 1.0 %
 INJECTION PER STROKE OF CWS, PILOT DIESEL, PURGE OIL & TRITON
 2535 mm3/str 100 mm3/str 10 mm3/str 26 mm3/str
 TOTAL ENERGY INP RATE: 1609340 KJ/HR 1525441 BTU/HR
 ** 20% PURGE OIL RETURNED TO FUEL TANK

HEAT RELEASE AND COMBUSTION ANALYSIS TR 4774 L38

HEAT RELEASE CALCULATION FOR CWS TESTS

ENTER: LOG NO., FILE NO. OF PRESSURE DATA, & RPM OF RUN
 39,37,1052
 ENTER THE MANIFOLD AIR PRESSURE (PSIA) & TEMPERATURE (DEG F)
 47.04,199.2
 ENTER TDC CORR.(+/- DEG), INJ ST(DEG BTDC) & INJ DURATION(DEG)
 -0.4,42,51

ENTER COAL FRACTION & DENSITY OF CWS USED: 0.5,1.095
 ENTER "1" FOR UKOH OR "2" FOR TRITON USED IN CWS: 2
 ENTER COAL WT FRACTION OF TRITON USED IN CWS: 0.02
 ENTER CONSUMPTION (LB/SEC),TEMP(DEG F) OF CONSTITUENTS
 CWS: 5.3530E-2,75.07
 PILOT DIESEL: 1.5230E-3,104.5
 PURGE OIL: 2.1294E-4,85
 WT % OF COAL,PILOT DIESEL,PURGE OIL,TRITON & H2O IN FUEL
 49.0 % 2.8 % 0.3 % 1.0 % 49.0 %
 ENERGY % OF COAL,PILOT DIESEL,PURGE OIL,TRITON OF RUN
 91.6 % 6.7 % 0.7 % 1.0 %
 INJECTION PER STROKE OF CWS,PILOT DIESEL,PURGE OIL & TRITON
 2510 mm3/str 93 mm3/str 10 mm3/str 26 mm3/str
 TOTAL ENERGY INP RATE: 1595700 KJ/HR 1503040 BTU/HR
 ** 20% PURGE OIL RETURNED TO FUEL TANK

HEAT RELEASE AND COMBUSTION ANALYSIS TR 4774 L39

HEAT RELEASE CALCULATION FOR CWS TESTS

ENTER: LOG NO., FILE NO. OF PRESSURE DATA, & RPM OF RUN

40,41,1051

ENTER THE MANIFOLD AIR PRESSURE (PSIA) & TEMPERATURE (DEG F)

47,188

ENTER TDC CORR. (+/- DEG), INJ ST (DEG BTDC) & INJ DURATION (DEG)

-0.4,42,51

ENTER COAL FRACTION & DENSITY OF CWS USED: 0.5,1.095

ENTER "1" FOR UKON OR "2" FOR TRITON USED IN CWS: 2

ENTER COAL WT FRACTION OF TRITON USED IN CWS: 0.02

ENTER CONSUMPTION (LB/SEC), TEMP (DEG F) OF CONSTITUENTS

CWS: 5.3935E-2,75.42

PILOT DIESEL: 1.4834E-3,102.1

PURGE OIL: 2.4205E-4,85

WT % OF COAL, PILOT DIESEL, PURGE OIL, TRITON & H2O IN FUEL

48.0 % 2.7 % 0.3 % 1.0 % 48.0 %

ENERGY % OF COAL, PILOT DIESEL, PURGE OIL, TRITON OF RUN

91.7 % 6.5 % 0.8 % 1.0 %

INJECTION PER STROKE OF CWS, PILOT DIESEL, PURGE OIL & TRITON

2531 mm3/str 91 mm3/str 11 mm3/str 26 mm3/str

TOTAL ENERGY INP RATE: 1595577 KJ/HR 1512395 BTU/HR

** 20% PURGE OIL RETURNED TO FUEL TANK

HEAT RELEASE AND COMBUSTION ANALYSIS TR 4774 L40

INJ ST: 42.4 DEG BTDC IGN ST: 21.9 DEG BTDC IGN LAG: 20.5 DEG CA

HEAT RELEASE CALCULATION FOR CWS TESTS

ENTER: LOG NO., FILE NO. OF PRESSURE DATA, & RPM OF RUN

41,45,1050

ENTER THE MANIFOLD AIR PRESSURE (PSIA) & TEMPERATURE (DEG F)

47.15,187.9

ENTER TDC CORR.(+/- DEG), INJ ST(DEG BTDC) & INJ DURATION(DEG)

-0.4,47,47

ENTER COAL FRACTION & DENSITY OF CWS USED: 0.5,1.095

ENTER "1" FOR UKON OR "2" FOR TRITON USED IN CWS: 2

ENTER COAL WT FRACTION OF TRITON USED IN CWS: 0.02

ENTER CONSUMPTION (LB/SEC),TEMP(DEG F) OF CONSTITUENTS

CWS: 5.6895E-2,78.06

PILOT DIESEL: 1.4765E-3,106

PURGE OIL: 2.1519E-4,85

WT % OF COAL,PILOT DIESEL,PURGE OIL,TRITON & H2O IN FUEL

48.1 % 2.5 % 0.3 % 1.0 % 48.1 %

ENERGY % OF COAL,PILOT DIESEL,PURGE OIL,TRITON OF RUN

92.1 % 6.2 % 0.7 % 1.0 %

INJECTION PER STROKE OF CWS,PILOT DIESEL,PURGE OIL & TRITON

2668 mm3/str 90 mm3/str 10 mm3/str 28 mm3/str

TOTAL ENERGY INP RATE: 1672393 KJ/HR 1585207 BTU/HR

** 20% PURGE OIL RETURNED TO FUEL TANK

HEAT RELEASE AND COMBUSTION ANALYSIS

TR 4774 L41

HEAT RELEASE CALCULATION FOR CWS TESTS

ENTER: LOG NO., FILE NO. OF P/PRESSURE DATA, & RPM OF RUN
42,43,1057

ENTER THE MANIFOLD AIR PRESSURE (PSIA) & TEMPERATURE (DEG F)
46.87,187.7

ENTER TDC CORR. (°) - (DEG), AND ST(DEG BTDC) & INJ DURATION(DEG)
-0.4,47.32

ENTER COAL FRACTION & DENSITY OF CWS USED: 0.506,1.11

ENTER "1" FOR UNON OR "2" FOR TRITON USED IN CWS: 2

ENTER COAL IN FRACTION OF TRITON USED IN CWS: 0.02

ENTER CONSUMPTION (LB/SEC),TEMP(DEG F) OF CONSTITUENTS

CWS: 5.6805E-2,79.9

PILOT DIESEL: 9.9408E 4,85.0

PURGE OIL: 1.7736E-4,82

WT % OF COAL,PILOT DIESEL,PURGE OIL,TRITON & H2O IN FUEL

49.1 % 1.7 % 0.2 % 1.0 % 48.0 %

ENERGY % OF COAL,PILOT DIESEL,PURGE OIL,TRITON OF RUN

54.2 % 4.2 % 0.6 % 1.1 %

INJECTION PER STROKE OF CWS,PILOT DIESEL,PURGE OIL & TRITON

2624 mm3/str 61 mm3/str 8 mm3/str 28 mm3/str

TOTAL ENERGY INP RATE: 1655175 KJ/HR 1569887 BTU/HR

* 20% PURGE OIL RETURNED TO FUEL TANK

HEAT RELEASE AND COMBUSTION ANALYSIS TR 4774 L42

HEAT RELEASE CALCULATION FOR CWS TESTS

ENTER: LOG NO., FILE NO. OF PRESSURE DATA, & RPM OF RUN
 43,53,1052
 ENTER THE MANIFOLD AIR PRESSURE (PSIA) & TEMPERATURE (DEG F)
 47.04,187.5
 ENTER TDC CORR.(+/- DEG), INJ ST(DEG BTDC) & INJ DURATION(DEG)
 -.4,47,52

ENTER COAL FRACTION & DENSITY OF CWS USED: 0.506,1.11
 ENTER "1" FOR UKON OR "2" FOR TRITON USED IN CWS: 2
 ENTER COAL WT FRACTION OF TRITON USED IN CWS: 0.02
 ENTER CONSUMPTION (LB/SEC),TEMP(DEG F) OF CONSTITUENTS
 CWS: 5.7033E-2,72.1
 PILOT DIESEL: 1.8929E-3,89.8
 PURGE OIL: 2.2536E-4,85
 WT % OF COAL,PILOT DIESEL,PURGE OIL,TRITON & H2O IN FUEL
 49.0 % 1.9 % 0.3 % 1.0 % 47.8 %
 ENERGY % OF COAL,PILOT DIESEL,PURGE OIL,TRITON OF RUN
 93.7 % 4.6 % 0.7 % 1.0 %
 INJECTION PER STROKE OF CWS,PILOT DIESEL,PURGE OIL & TRITON
 2638 mm3/str 67 mm3/str 10 mm3/str 28 mm3/str
 TOTAL ENERGY IMP RATE: 1671063 KJ/HR 1583946 BTU/HR
 ** 20% PURGE OIL RETURNED TO FUEL TANK

HEAT RELEASE AND COMBUSTION ANALYSIS TR 4774 L43

HEAT RELEASE CALCULATION FOR CWS TESTS

ENTER: LOG NO., FILE NO. OF PRESSURE DATA, & RPM OF RUN

44,57,1051

ENTER THE MANIFOLD AIR PRESSURE (PSIA) & TEMPERATURE (DEG F)

47,137.7

ENTER TDC CORR.(+/- DEG), INJ ST(DEG BTDC) & INJ DURATION(DEG)

-.4,47,53

ENTER COAL FRACTION & DENSITY OF CWS USED: 0.506,1.11

ENTER "1" FOR UKON OR "2" FOR TRITON USED IN CWS: 2

ENTER COAL WT FRACTION OF TRITON USED IN CWS: 0.02

ENTER CONSUMPTION (LB/SEC),TEMP(DEG F) OF CONSTITUENTS

CWS: 5.6368E-2,72.8

PILOT DIESEL: 1.1242E-3,90.0

PURGE OIL: 1.9438E-4,85

WT % OF COAL,PILOT DIESEL,PURGE OIL,TRITON & H2O IN FUEL

49.0 % 2.0 % 0.3 % 1.0 % 47.8 %

ENERGY % OF COAL,PILOT DIESEL,PURGE OIL,TRITON OF RUN

93.6 % 4.8 % 0.6 % 1.0 %

INJECTION PER STROKE OF CWS,PILOT DIESEL,PURGE OIL & TRITON

2609 mm3/str 69 mm3/str 9 mm3/str 28 mm3/str

TOTAL ENERGY INP RATE: 1653042 KJ/HR 1566864 BTU/HR

** 20% PURGE OIL RETURNED TO FUEL TANK

HEAT RELEASE AND COMBUSTION ANALYSIS

TR 4774 L44

INJ ST: 47.4 DEG BTDC

IGN ST: 21.4 DEG BTDC

IGN LAG: 26.0 DEG CA

PC: HEAT RELEASE CALCULATION FOR CWS TESTS

ENTER: LOG NO., FILE NO. OF PRESSURE DATA, & RPM OF RUN

45.81.10.1

ENTER THE MANIFOLD AIR PRESSURE (PSIA) & TEMPERATURE (DEG F)

46.3.18.1

ENTER THE MANIFOLD AIR DEG, INJ ST/DEG BTDC & INJ DURATION(DEG)

-1.4.48.59

ENTER LOAD FRACTION & DENSITY OF CWS USED: 0.516.1.109

ENTER "1" FOR URON OR "2" FOR TRITON USED IN CWS: 2

ENTER LOAD WT FRACTION OF TRITON USED IN CWS: 0.02

ENTER CONSUMPTION (LB/SEC), TEMP(DEG F) OF CONSTITUENTS

CWS: 5.45DE-2.79.2

PILOT DIESEL: 1.7345E-4.89.8

PURGE OIL: 1.7703E-4.05

WT % OF FUEL: PILOT DIESEL, PURGE OIL, TRITON & H2O IN FUEL

58.1 % 1.7 % 0.2 % 1.0 % 47.0 %

ENERGY % OF FUEL: PILOT DIESEL, PURGE OIL, TRITON OF RUN

94.2 % 0.2 % 0.6 % 1.1 %

INJECTION PER STROKE OF CWS, PILOT DIESEL, PURGE OIL & TRITON

2544 mm3/stk 60 mm3/stk 8 mm3/stk 28 mm3/stk

TOTAL ENERGY (HP RATE): 1631883 KJ/HR 1546888 BTU/HR

** 20% PURGE OIL RETURNED TO FUEL TANK

HEAT RELEASE AND COMBUSTION ANALYSIS TR 4774 L45

HEAT RELEASE CALCULATION FOR CWS TESTS

ENTER: LOG NO., FILE NO. OF PRESSURE DATA, & RPM OF RUN
 46,65,1050
 ENTER THE MANIFOLD AIR PRESSURE (PSIA) & TEMPERATURE (DEG F)
 47,187.5
 ENTER IDC CORR. (+/- DEG). INJ ST(DEG BTDC) & INJ DURATION(DEG)
 -0.4,30.61

ENTER COAL FRACTION & DENSITY OF CWS USED: 0.516,1.109
 ENTER "1" FOR UCON OF "2" FOR TRITON USED IN CWS: 2
 ENTER COAL WT FRACTION OF TRITON USED IN CWS: 0.02
 ENTER CONSUMPTION (LB/SEC) TEMP(DEG F) OF CONSTITUENTS

CWS: 5.7416E-2,70.5

PILOT DIESEL: 1.832E-3,91.4

PURGE OIL: 1.9695E-4,85

WT % OF COAL,PILOT DIESEL,PURGE OIL,TRITON & H2O IN FUEL

50.0 % 1.0 % 0.3 % 1.0 % 46.9 %

ENERG % OF COAL,PILOT DIESEL,PURGE OIL,TRITON OF RUN

54.1 % 4.3 % 0.6 % 1.1 %

INJECTION PER STROKE OF CWS,PILOT DIESEL,PURGE OIL & TRITON

2662 mm3/str 53 mm3/str 9 mm3/str 29 mm3/str

TOTAL ENERGY INP RATE: 1766925 KJ/HR 1617938 BTU/HR

** 20% PURGE OIL RETURNED TO FUEL TANK

HEAT RELEASE AND COMBUSTION ANALYSIS TR 4774 L46

HEAT RELEASE CALCULATION FOR CWS TESTS

ENTER: LOG NO., FILE NO. OF PRESSURE DATA, & RPM OF RUN
 47,69,1051
 ENTER THE MANIFOLD AIR PRESSURE (PSIA) & TEMPERATURE (DEG F)
 47.1,187.5
 ENTER TDC CORR.(+/- DEG), INJ ST(DEG BTDC) & INJ DURATION(DEG)
 -.4,20,67

ENTER COAL FRACTION & DENSITY OF CWS USED: 0.516,1.109
 ENTER "1" FOR UNION OR "2" FOR TRITON USED IN CWS: 2
 ENTER COAL WT FRACTION OF TRITON USED IN CWS: 0.02
 ENTER CONSUMPTION (LB/SEC),TEMP(DEG F) OF CONSTITUENTS

CWS: 8.4558E-2,71.4
 PILOT DIESEL: 1.046E-3,92.9
 PURGE OIL: 2.2034E-4,85

WT % OF COAL,PILOT DIESEL,PURGE OIL,TRITON & H2O IN FUEL
 50.1 % 1.6 % 0.3 % 1.0 % 47.0 %

ENERGY % OF COAL,PILOT DIESEL,PURGE OIL,TRITON OF RUN
 94.5 % 3.6 % 0.6 % 1.1 %

INJECTION PER STROKE OF CWS,PILOT DIESEL,PURGE OIL & TRITON
 2990 mm3/str 64 mm3/str 10 mm3/str 33 mm3/str

TOTAL ENERGY INP RATE: 1011251 KJ/HR 1811613 BTU/HR

** 20% PURGE OIL RETURNED TO FUEL TANK

HEAT RELEASE AND COMBUSTION ANALYSIS TR 4774 L47

HEAT RELEASE CALCULATION FOR CWS TESTS

ENTER: LOG NO., FILE NO. OF PRESSURE DATA, & RPM OF RUN
48,73,1893

ENTER THE MANIFOLD AIR PRESSURE (PSIA) & TEMPERATURE (DEG F)
47.1,137.2

ENTER TDC CORR.(+/- DEG), INJ ST(DEG BTDC) & INJ DURATION(DEG)
-.4,20,57

ENTER COAL FRACTION & DENSITY OF CWS USED: 0.498,1.089

ENTER "1" FOR UKON OR "2" FOR TRITON USED IN CWS: 2

ENTER COAL WT FRACTION OF TRITON USED IN CWS: 0.02

ENTER CONSUMPTION (LB/SEC),TEMP(DEG F) OF CONSTITUENTS

CWS: 5.986E-2,73.1

PILOT DIESEL: 9.435E-4,37.3

PURGE OIL: 1.807E-4,85

WT % OF COAL,PILOT DIESEL,PURGE OIL,TRITON & H2O IN FUEL

48.4 % 1.5 % 0.2 % 1.0 % 48.8 %

ENERGY % OF COAL,PILOT DIESEL,PURGE OIL,TRITON OF RUN

94.5 % 3.9 % 0.6 % 1.1 %

INJECTION PER STROKE OF CWS,PILOT DIESEL,PURGE OIL & TRITON

2819 mm3/stk 57 mm3/stk 8 mm3/stk 29 mm3/stk

TOTAL ENERGY INP RATE: 1710586 KJ/HR 1621408 BTU/HR

** 20% PURGE OIL RETURNED TO FUEL TANK

HEAT RELEASE AND COMBUSTION ANALYSIS TR 4774 L48

HEAT RELEASE CALCULATION FOR CWS TESTS

ENTER: LOG NO., FILE NO. OF PRESSURE DATA, & RPM OF RUN
49,77,1052

ENTER THE MANIFOLD AIR PRESSURE (PSIA) & TEMPERATURE (DEG F)
47.1,185.1

ENTER TDC CORR.(+/- DEG), INJ ST(DEG BTDC) & INJ DURATION(DEG)
-.4,30,52

ENTER COAL FRACTION & DENSITY OF CWS USED: 0.498,1.089

ENTER "1" FOR UKON OR "2" FOR TRITON USED IN CWS: 2

ENTER COAL WT FRACTION OF TRITON USED IN CWS: 0.02

ENTER CONSUMPTION (LB/SEC),TEMP(DEG F) OF CONSTITUENTS

CWS: 5.528E-2,74.9

PILOT DIESEL: 9.971E-4,91.7

PURGE OIL: 2.559E-4,85

WT % OF COAL,PILOT DIESEL,PURGE OIL,TRITON & H2O IN FUEL

48.3 % 1.8 % 0.3 % 1.0 % 48.7 %

ENERGY % OF COAL,PILOT DIESEL,PURGE OIL,TRITON OF RUN

93.7 % 4.4 % 0.8 % 1.0 %

INJECTION PER STROKE OF CWS,PILOT DIESEL,PURGE OIL & TRITON

2606 mm3/str 61 mm3/str 12 mm3/str 27 mm3/str

TOTAL ENERGY INP RATE: 1593173 KJ/HR 1510117 BTU/HR

** 20% PURGE OIL RETURNED TO FUEL TANK

HEAT RELEASE AND COMBUSTION ANALYSIS

TR 4774 L49

INJ ST: 30.4 DEG BTDC IGN ST: 20.0 DEG BTDC IGN LAG: 10.4 DEG CA

HEAT RELEASE ANALYSIS FOR CWS TESTS

ENTER: LOG NO., FILE NO. OF PRESSURE DATA, & RPM OF RUN
50.81.1951

ENTER THE MANIFOLD AIR PRESSURE (PSIA) & TEMPERATURE (DEG F)
46.9.187.4

ENTER TDC CORR. (DEG), INJ ST (DEG BTDC) & INJ DURATION (DEG)
-.4.48.51

ENTER COAL FRACTION & DENSITY OF CWS USED: 0.498.1.089

ENTER "1" FOR UKON OR "2" FOR TRITON USED IN CWS: 2

ENTER COAL WT FRACTION OF TRITON USED IN CWS: 0.02

ENTER CONSUMPTION (LB/SEC), TEMP (DEG F) OF CONSTITUENTS

CWS: 5.4291E-2.75.6

PILOT DIESEL: 9.253E-4.91.7

PURGE OIL: 2.448E-4.85

WT % OF COAL, PILOT DIESEL, PURGE OIL, TRITON & H2O IN FUEL

48.3 % 1.7 % 0.3 % 1.0 % 48.7 %

ENERGY % OF COAL, PILOT DIESEL, PURGE OIL, TRITON OF RUN

94.6 % 4.1 % 0.8 % 1.1 %

INJECTION PER STROKE OF CWS, PILOT DIESEL, PURGE OIL & TRITON

2562 mm3/str 56 mm3/str 11 mm3/str 26 mm3/str

TOTAL ENERGY INP RATE: 1568538 KJ/HR 1479183 BTU/HR

** 20% PURGE OIL RETURNED TO FUEL TANK

HEAT RELEASE AND COMBUSTION ANALYSIS TR 4774 L50

HEAT RELEASE CALCULATION FOR CWS TESTS

ENTER: LOG NO., FILE NO. OF PRESSURE DATA, & RPM OF RUN
51,85,1053

ENTER THE MANIFOLD AIR PRESSURE (PSIA) & TEMPERATURE (DEG F)
47.187.5

ENTER TDC CORR.(+/- DEG). INJ ST(DEG BTDC) & INJ DURATION(DEG)
-.4,35,50

ENTER COAL FRACTION & DENSITY OF CWS USED: 0.495,1.127

ENTER "1" FOR UKON OR "2" FOR TRITON USED IN CWS: 2

ENTER COAL NT FRACTION OF TRITON USED IN CWS: 0.02

ENTER CONSUMPTION (LB/SEC).TEMP(DEG F) OF CONSTITUENTS

CWS: 5.5627E-2,72.8

PILOT DIESEL: 8.5067E-4,83

PURGE OIL: 1.77E-4,85

WT % OF COAL,PILOT DIESEL,PURGE OIL,TRITON & H2O IN FUEL

48.2 % 1.5 % 0.2 % 1.0 % 49.1 %

ENERGY % OF COAL,PILOT DIESEL,PURGE OIL,TRITON OF RUN

94.6 % 2.8 % 0.6 % 1.1 %

INJECTION PER STROKE OF CWS,PILOT DIESEL,PURGE OIL & TRITON

2532 mm3/str 52 mm3/str 8 mm3/str 27 mm3/str

TOTAL ENERGY INP RATE: 1579698 KJ/HR 1497344 BTU/HR

** 20% PURGE OIL RETURNED TO FUEL TANK

HEAT RELEASE AND COMBUSTION ANALYSIS TR 4774 L51

HEAT RELEASE CALCULATION FOR CWS TESTS

ENTER: LOG NO., FILE NO. OF PRESSURE DATA, & RPM OF RUN

52,89,1052

ENTER THE MANIFOLD AIR PRESSURE (PSIA) & TEMPERATURE (DEG F)

47,187.8

ENTER TDC CORR.(+/- DEG), INJ ST(DEG BTDC) & INJ DURATION(DEG)

-.4,45,51

ENTER COAL FRACTION & DENSITY OF CWS USED: 0.495,1.127

ENTER "1" FOR UKON OR "2" FOR TRITON USED IN CWS: 2

ENTER COAL WT FRACTION OF TRITON USED IN CWS: 0.02

ENTER CONSUMPTION (LB/SEC),TEMP(DEG F) OF CONSTITUENTS

CWS: 5.593E-2,74.19

PILOT DIESEL: 9.2366E-4,86.47

PURGE OIL: 2.359E-4,85

WT % OF COAL,PILOT DIESEL,PURGE OIL,TRITON & H2O IN FUEL

48.1 % 1.6 % 0.3 % 1.0 % 49.0 %

ENERGY % OF COAL,PILOT DIESEL,PURGE OIL,TRITON OF RUN

94.1 % 4.0 % 0.8 % 1.1 %

INJECTION PER STROKE OF CWS,PILOT DIESEL,PURGE OIL & TRITON

2548 mm3/str 56 mm3/str 11 mm3/str 27 mm3/str

TOTAL ENERGY INP RATE: 1595630 KJ/HR 1512445 BTU/HR

** 20% PURGE OIL RETURNED TO FUEL TANK

HEAT RELEASE AND COMBUSTION ANALYSIS TR 4774 L52

HEAT RELEASE CALCULATION FOR CWS TESTS

ENTER: LOG NO., FILE NO. OF PRESSURE DATA, & RPM OF RUN
53,93,1051

ENTER THE MANIFOLD AIR PRESSURE (PSIA) & TEMPERATURE (DEG F)
47.4,187.8

ENTER TDC CORR. (+/- DEG), INJ ST(DEG BTDC) & INJ DURATION(DEG)
-.4,30,51

ENTER COAL FRACTION & DENSITY OF CWS USED: 0.495,1.127

ENTER "1" FOR UKON OR "2" FOR TRITON USED IN CWS: 2

ENTER COAL WT FRACTION OF TRITON USED IN CWS: 0.02

ENTER CONSUMPTION (LB/SEC),TEMP(DEG F) OF CONSTITUENTS

CWS: 5.5064E-2,75.1

PILOT DIESEL: 9.905E-4,89.7

PURGE OIL: 2.1895E-4,85

WT % OF COAL,PILOT DIESEL,PURGE OIL,TRITON & H2O IN FUEL

48.0 % 1.8 % 0.3 % 1.0 % 49.0 %

ENERGY % OF COAL,PILOT DIESEL,PURGE OIL,TRITON OF RUN

93.8 % 4.4 % 0.7 % 1.1 %

INJECTION PER STROKE OF CWS,PILOT DIESEL,PURGE OIL & TRITON

2511 mm3/str 60 mm3/str 10 mm3/str 27 mm3/str

TOTAL ENERGY INP RATE: 1575901 KJ/HR 1493745 BTU/HR

** 20% PURGE OIL RETURNED TO FUEL TANK

HEAT RELEASE AND COMBUSTION ANALYSIS TR 4774 L53

HEAT RELEASE CALCULATION FOR CWS TESTS

ENTER: LOG NO., FILE NO. OF PRESSURE DATA, & RPM OF RUN
 54,97,1051
 ENTER THE MANIFOLD AIR PRESSURE (PSIA) & TEMPERATURE (DEG F)
 46.8,187.8
 ENTER TDC CORR.(+/- DEG), INJ ST(DEG BTDC) & INJ DURATION(DEG)
 -.4,40,50

ENTER COAL FRACTION & DENSITY OF CWS USED: 0.495,1.127
 ENTER "1" FOR UKON OR "2" FOR TRITON USED IN CWS: 2
 ENTER COAL WT FRACTION OF TRITON USED IN CWS: 0.02
 ENTER CONSUMPTION (LB/SEC),TEMP(DEG F) OF CONSTITUENTS
 CWS: 5.4417E-2,75.35
 PILOT DIESEL: 1.0319E-3,291.51
 PURGE OIL: 2.2631E-4,85
 WT % OF COAL,PILOT DIESEL,PURGE OIL,TRITON & H2O IN FUEL
 48.0 % 1.9 % 0.3 % 1.0 % 48.9 %
 ENERGY % OF COAL,PILOT DIESEL,PURGE OIL,TRITON OF RUN
 93.6 % 4.6 % 0.8 % 1.0 %
 INJECTION PER STROKE OF CWS,PILOT DIESEL,PURGE OIL & TRITON
 2481 mm3/str 63 mm3/str 10 mm3/str 26 mm3/str
 TOTAL ENERGY INP RATE: 1561608 KJ/HR 1480197 BTU/HR
 ** 20% PURGE OIL RETURNED TO FUEL TANK

HEAT RELEASE AND COMBUSTION ANALYSIS TR 4774 L54

HEAT RELEASE CALCULATION FOR CWS TESTS

ENTER: LOG NO., FILE NO. OF PRESSURE DATA, & RPM OF RUN
 55.101,1053
 ENTER THE MANIFOLD AIR PRESSURE (PSIA) & TEMPERATURE (DEG F)
 40.4,127.1
 ENTER TDC CORR.(+/- DEG), INJ ST(DEG BTDC) & INJ DURATION(DEG)
 -.4,30.56

ENTER COAL FRACTION & DENSITY OF CWS USED: 0.483,1.116
 ENTER "1" FOR UKON OR "2" FOR TRITON USED IN CWS: 2
 ENTER COAL WT FRACTION OF TRITON USED IN CWS: 0.02
 ENTER CONSUMPTION (LB/SEC),TEMP(DEG F) OF CONSTITUENTS

CWS: 6.0083E-2,74.44
 PILOT DIESEL: 7.579E-4,87.66
 PURGE OIL: 2.1499E-4,85
 WT % OF COAL,PILOT DIESEL,PURGE OIL,TRITON & H2O IN FUEL
 47.1 % 1.2 % 0.3 % 0.9 % 50.4 %
 ENERGY % OF COAL,PILOT DIESEL,PURGE OIL,TRITON OF RUN
 95.1 % 3.2 % 0.7 % 1.1 %
 INJECTION PER STROKE OF CWS,PILOT DIESEL,PURGE OIL & TRITON
 2762 mm3/str 46 mm3/str 10 mm3/str 28 mm3/str
 TOTAL ENERGY IHP RATE: 1656534 KJ/HR 1570174 BTU/HR
 ** 20% PURGE OIL RETURNED TO FUEL TANK

HEAT RELEASE AND COMBUSTION ANALYSIS TR 4774 L55

HEAT RELEASE CALCULATION FOR CWS TESTS

ENTER: LOG NO., FILE NO. OF PRESSURE DATA, & RPM OF RUN
 56,105,1051
 ENTER THE MANIFOLD AIR PRESSURE (PSIA) & TEMPERATURE (DEG F)
 40.3,187
 ENTER TDC CORR.(+/- DEG), INJ ST(DEG BTDC) & INJ DURATION(DEG)
 -.4,35.54

ENTER COAL FRACTION & DENSITY OF CWS USED: 0.483,1.116
 ENTER "1" FOR UKON OR "2" FOR TRITON USED IN CWS: 2
 ENTER COAL WT FRACTION OF TRITON USED IN CWS: 0.02
 ENTER CONSUMPTION (LB/SEC),TEMP(DEG F) OF CONSTITUENTS
 CWS: 5.9045E-2,75.9
 PILOT DIESEL: 9.0635E-4,91.35
 PURGE OIL: 2.2442E-4,85
 WT % OF COAL,PILOT DIESEL,PURGE OIL,TRITON & H2O IN FUEL
 47.0 % 1.5 % 0.3 % 0.9 % 50.3 %
 ENERGY % OF COAL,PILOT DIESEL,PURGE OIL,TRITON OF RUN
 94.4 % 3.9 % 0.7 % 1.1 %
 INJECTION PER STROKE OF CWS,PILOT DIESEL,PURGE OIL & TRITON
 2720 mm3/str 55 mm3/str 10 mm3/str 28 mm3/str
 TOTAL ENERGY INP RATE: 1639903 KJ/HR 1554411 BTU/HR
 ** 20% PURGE OIL RETURNED TO FUEL TANK

HEAT RELEASE AND COMBUSTION ANALYSIS TR 4774 L56

HEAT RELEASE CALCULATION FOR CWS TESTS

ENTER: LOG NO., FILE NO. OF PRESSURE DATA, & RPM OF RUN
 57.109,1050
 ENTER THE MANIFOLD AIR PRESSURE (PSIA) & TEMPERATURE (DEG F)
 40.5,187.3
 ENTER TDC CORR.(+/- DEG), INJ ST(DEG BTDC) & INJ DURATION(DEG)
 -.4,40.55

ENTER COAL FRACTION & DENSITY OF CWS USED: 0.483,1.116
 ENTER "1" FOR UKON OR "2" FOR TRITON USED IN CWS: 2
 ENTER COAL WT FRACTION OF TRITON USED IN CWS: 0.02
 ENTER CONSUMPTION (LB/SEC), TEMP(DEG F) OF CONSTITUENTS
 CWS: 5.9362E-2,77.26
 PILOT DIESEL: 9.0631E-4,92.84
 PURGE OIL: 2.4377E-4,85
 WT % OF COAL,PILOT DIESEL,PURGE OIL,TRITON & H2O IN FUEL
 47.0 % 1.5 % 0.3 % 0.9 % 50.3 %
 ENERGY % OF COAL,PILOT DIESEL,PURGE OIL,TRITON OF RUN
 94.3 % 3.8 % 0.8 % 1.1 %
 INJECTION PER STROKE OF CWS,PILOT DIESEL,PURGE OIL & TRITON
 2737 mm3/str 55 mm3/str 11 mm3/str 28 mm3/str
 TOTAL ENERGY INP RATE: 1649316 KJ/HR 1563333 BTU/HR
 ** 20% PURGE OIL RETURNED TO FUEL TANK

HEAT RELEASE AND COMBUSTION ANALYSIS TR 4774 L57

HEAT RELEASE CALCULATION FOR CWS TESTS

ENTER: LOG NO., FILE NO. OF PRESSURE DATA, & RPM OF RUN
 58,113,105
 ENTER THE MANIFOLD AIR PRESSURE (PSIA) & TEMPERATURE (DEG F)
 47,107.9
 ENTER TDC CORR. (+/- DEG), INJ ST(DEG BTDC) & INJ DURATION(DEG)
 -.4,35,64

ENTER COAL FRACTION & DENSITY OF CWS USED: 0.495,1.112
 ENTER "1" FOR UKON OR "2" FOR TRITON USED IN CWS: 2
 ENTER COAL HT FRACTION OF TRITON USED IN CWS: 0.0001
 ENTER CONSUMPTION (LB/SEC), TEMP(DEG F) OF CONSTITUENTS
 CWS: 5.8204E-2,79.4
 PILOT DIESEL: 1.9166E-3,94.1
 PURGE OIL: 2.3007E-4,80
 WT % OF COAL, PILOT DIESEL, PURGE OIL, TRITON & H2O IN FUEL
 47.9 % 3.2 % 0.3 % 0.0 % 48.7 %
 ENERGY % OF COAL, PILOT DIESEL, PURGE OIL, TRITON OF RUN
 91.6 % 7.7 % 0.7 % 0.0 %
 INJECTION PER STROKE OF CWS, PILOT DIESEL, PURGE OIL & TRITON
 2716 mm3/str 117 mm3/str 11 mm3/str 0 mm3/str
 TOTAL ENERGY IHP RATE: 1746705 KJ/HR 1655645 BTU/HR
 ** 20% PURGE OIL RETURNED TO FUEL TANK

HEAT RELEASE AND COMBUSTION ANALYSIS TR 4774 L58

HEAT RELEASE CALCULATION FOR CWS TESTS

ENTER: LOG NO., FILE NO. OF PRESSURE DATA, & RPM OF RUN

59,117,1049

ENTER THE MANIFOLD AIR PRESSURE (PSIA) & TEMPERATURE (DEG F)

46.9,187.5

ENTER TDC CORR.(+/- DEG), INJ ST(DEG BTDC) & INJ DURATION(DEG)

-.4,35.66

ENTER COAL FRACTION & DENSITY OF CWS USED: 0.495,1.112

ENTER "1" FOR UKON OR "2" FOR TRITON USED IN CWS: 2

ENTER COAL WT FRACTION OF TRITON USED IN CWS: 0.0001

ENTER CONSUMPTION (LB/SEC),TEMP(DEG F) OF CONSTITUENTS

CWS: 5.9113E-2,79.6

PILOT DIESEL: 1.964E-3,97.8

PURGE OIL: 2.1021E-4,85

WT % OF COAL,PILOT DIESEL,PURGE OIL,TRITON & H2O IN FUEL

47.8 % 3.2 % 0.3 % 0.0 % 48.7 %

ENERGY % OF COAL,PILOT DIESEL,PURGE OIL,TRITON OF RUN

91.6 % 7.7 % 0.6 % 0.0 %

INJECTION PER STROKE OF CWS,PILOT DIESEL,PURGE OIL & TRITON

2764 mm3/str 120 mm3/str 10 mm3/str 0 mm3/str

TOTAL ENERGY INP RATE: 1773976 KJ/HR 1681493 BTU/HR

** 20% PURGE OIL RETURNED TO FUEL TANK

HEAT RELEASE AND COMBUSTION ANALYSIS

TR 4774 L59

HEAT RELEASE CALCULATION FOR CWS TESTS

ENTER: LOG NO., FILE NO. OF PRESSURE DATA, & RPM OF RUN

60,121,1055

ENTER THE MANIFOLD AIR PRESSURE (PSIA) & TEMPERATURE (DEG F)

47.2,188

ENTER TDC CORR.(+/- DEG). INJ ST(DEG BTDC) & INJ DURATION(DEG)

-.4,35,60

ENTER COAL FRACTION & DENSITY OF CWS USED: 0.49,1.109

ENTER "1" FOR UKOH OR "2" FOR TRITON USED IN CWS: 2

ENTER COAL WT FRACTION OF TRITON USED IN CWS: 0.0001

ENTER CONSUMPTION (LB/SEC),TEMP(DEG F) OF CONSTITUENTS

CWS: 5.7851E-2,72.5

PILOT DIESEL: 2.0909E-3,81.6

PURGE OIL: 7.301E-5,85

WT % OF COAL,PILOT DIESEL,PURGE OIL,TRITON & H2O IN FUEL

47.2 % 3.5 % 0.1 % 0.0 % 49.2 %

ENERGY % OF COAL,PILOT DIESEL,PURGE OIL,TRITON OF RUN

91.3 % 8.5 % 0.2 % 0.0 %

INJECTION PER STROKE OF CWS,PILOT DIESEL,PURGE OIL & TRITON

2697 mm3/str 127 mm3/str 3 mm3/str 0 mm3/str

TOTAL ENERGY INP RATE: 1724801 KJ/HR 1634958 BTU/HR

** 20% PURGE OIL RETURNED TO FUEL TANK

HEAT RELEASE AND COMBUSTION ANALYSIS

TR 4774 L60

HEAT RELEASE CALCULATION FOR CWS TESTS

ENTER: LOG NO., FILE NO. OF PRESSURE DATA, & RPM OF RUN
61,125,1054

ENTER THE MANIFOLD AIR PRESSURE (PSIA) & TEMPERATURE (DEG F)
47.3,180

ENTER TDC CORR.(+/- DEG), INJ ST(DEG BTDC) & INJ DURATION(DEG)
-.4,35,64

ENTER COAL FRACTION & DENSITY OF CWS USED: .464,1.107

ENTER "1" FOR UKON OR "2" FOR TRITON USED IN CWS: 2

ENTER COAL WT FRACTION OF TRITON USED IN CWS: 0.0001

ENTER CONSUMPTION (LB/SEC),TEMP(DEG F) OF CONSTITUENTS

CWS: 6.1585E-2,74.4

PILOT DIESEL: 2.0004E-3,88

PURGE OIL: 2.0383E-4,85

WT % OF COAL,PILOT DIESEL,PURGE OIL,TRITON & H2O IN FUEL

44.8 % 3.1 % 0.2 % 0.0 % 51.8 %

ENERGY % OF COAL,PILOT DIESEL,PURGE OIL,TRITON OF RUN

91.3 % 8.0 % 0.6 % 0.0 %

INJECTION PER STROKE OF CWS,PILOT DIESEL,PURGE OIL & TRITON

2879 mm3/str 122 mm3/str 9 mm3/str 0 mm3/str

TOTAL ENERGY INP RATE: 1738109 KJ/HR 1647497 BTU/HR

** 20% PURGE OIL RETURNED TO FUEL TANK

HEAT RELEASE AND COMBUSTION ANALYSIS TR 4774 L61

HEAT RELEASE CALCULATION FOR CWS TESTS

ENTER: LOG NO., FILE NO. OF PRESSURE DATA, & RPM OF RUN

63,129,1053

ENTER THE MANIFOLD AIR PRESSURE (PSIA) & TEMPERATURE (DEG F)

47.2,187.7

ENTER TDC CORR.(+/- DEG), INJ ST(DEG BTDC) & INJ DURATION(DEG)

-.4,35,67

ENTER COAL FRACTION & DENSITY OF CWS USED: 0.463,1.11

ENTER "1" FOR UKON OR "2" FOR TRITON USED IN CWS: 2

ENTER COAL WT FRACTION OF TRITON USED IN CWS: 0.015

ENTER CONSUMPTION (LB/SEC),TEMP(DEG F) OF CONSTITUENTS

CWS: 6.0688E-2,74.5

PILOT DIESEL: 2.0007E-3,88.1

PURGE OIL: 2.7989E-4,85

WT % OF COAL,PILOT DIESEL,PURGE OIL,TRITON & H2O IN FUEL

44.4 % 3.2 % 0.3 % 0.7 % 51.5 %

ENERGY % OF COAL,PILOT DIESEL,PURGE OIL,TRITON OF RUN

90.3 % 8.1 % 0.9 % 0.7 %

INJECTION PER STROKE OF CWS,PILOT DIESEL,PURGE OIL & TRITON

2913 mm3/str 122 mm3/str 13 mm3/str 21 mm3/str

TOTAL ENERGY IHP RATE: 1717682 KJ/HR 1628135 BTU/HR

** 20% PURGE OIL RETURNED TO FUEL TANK

HEAT RELEASE AND COMBUSTION ANALYSIS

TR 4774 L62

HEAT RELEASE CALCULATION FOR CWS TESTS

ENTER: LOW PUL. FREQ NO. OF PRESSURE DATA, & RPM OF RUN
63,133,1857

ENTER THE MANIFOLD AIR PRESSURE (PSIA) & TEMPERATURE (DEG F)
47,137.2

ENTER TDC CORR.(DEG) INJ ST(DEG BTDC) & INJ DURATION(DEG)
-4.30,47

ENTER COAL FRACTION & DENSITY OF CWS USED: 0.496,1.103

ENTER "1" FOR UKON OR "2" FOR TRITON USED IN CWS: 2

ENTER COAL WT FRACTION OF TRITON USED IN CWS: 0.02

ENTER CONSUMPTION (LB/SEC),TEMP(DEG F) OF CONSTITUENTS

CWS: 5.6223E-2,277.8

PILOT DIESEL: 9.0559E-4,89.1

PURGE OIL: 2.4277E-4,85

WT % OF COAL,PILOT DIESEL,PURGE OIL,TRITON & H2O IN FUEL

48.2 % 1.6 % 0.3 % 1.0 % 49.0 %

ENERGY % OF COAL,PILOT DIESEL,PURGE OIL,TRITON OF RUN

94.2 % 7.9 % 0.8 % 1.1 %

INJECTION PEP STROKE OF CWS,PILOT DIESEL,PURGE OIL & TRITON

2614 mm3/str 55 mm3/str 11 mm3/str 27 mm3/str

TOTAL ENERGY INP RATE: 1680764 KJ/HR 1522051 BTU/HR

** 20% PURGE OIL RETURNED TO FUEL TANK

HEAT RELEASE AND COMBUSTION ANALYSIS

TR4774 L63

HEAT RELEASE CALCULATION FOR CWS TESTS

ENTER: LOG NO., FILE NO. OF PRESSURE DATA, & RPM OF RUN

64,137,1051

ENTER THE MANIFOLD AIR PRESSURE (PSIA) & TEMPERATURE (DEG F)

47.3,186.9

ENTER TDC CORR. (+/- DEG), INJ ST(DEG BTDC) & INJ DURATION(DEG)

-1.4,35.47

ENTER COAL FRACTION & DENSITY OF CWS USED: 0.496,1.103

ENTER "1" FOR UNOH OR "2" FOR TRITON USED IN CWS: 2

ENTER COAL WT FRACTION OF TRITON USED IN CWS: 0.02

ENTER CONSUMPTION (LB/SEC),TEMP(DEG F) OF CONSTITUENTS

CWS: 5.4359E-2,79.33

PILOT DIESEL: 9.1898E-4,93.3

PURGE OIL: 2.0531E-4,85

WT % OF COAL,PILOT DIESEL,PURGE OIL,TRITON & H2O IN FUEL

49.2 % 1.6 % 0.3 % 1.0 % 49.0 %

ENERGY % OF COAL,PILOT DIESEL,PURGE OIL,TRITON OF RUN

94.3 % 4.0 % 0.7 % 1.1 %

INJECTION PER STROKE OF CWS,PILOT DIESEL,PURGE OIL & TRITON

2626 mm3/str 56 mm3/str 9 mm3/str 27 mm3/str

TOTAL ENERGY INP RATE: 1608380 KJ/HR 1524531 BTU/HR

** 20% PURGE OIL RETURNED TO FUEL TANK

HEAT RELEASE AND COMBUSTION ANALYSIS

TR 4774 L64

INJ ST: 35.4 DEG BTDC IGN ST: 20.4 DEG BTDC IGN LAG: 15.0 DEG CA

HEAT RELEASE CALCULATION FOR CWS TESTS

ENTER: LOG NO., FILE NO. OF PRESSURE DATA, & RPM OF RUN
 65,141,1049
 ENTER THE MANIFOLD AIR PRESSURE (PSIA) & TEMPERATURE (DEG F)
 47.3,187
 ENTER TDC CORR.(+/- DEG), INJ ST(DEG BTDC) & INJ DURATION(DEG)
 -.4,40,48

ENTER COAL FRACTION & DENSITY OF CWS USED: 0.496,1.103
 ENTER "1" FOR UKON OR "2" FOR TRITON USED IN CWS: 2
 ENTER COAL HT FRACTION OF TRITON USED IN CWS: 0.02
 ENTER CONSUMPTION (LB/SEC), TEMP(DEG F) OF CONSTITUENTS

CWS: 5.8807E-2,79.97
 PILOT DIESEL: 9.3720E-4,96.2
 PURGE OIL: 2.629E-4,85

WT % OF COAL,PILOT DIESEL,PURGE OIL,TRITON & H2O IN FUEL

48.2 % 1.6 % 0.3 % 1.0 % 48.9 %

ENERGY % OF COAL,PILOT DIESEL,PURGE OIL,TRITON OF RUN

94.1 % 4.0 % 0.8 % 1.1 %

INJECTION PER STROKE OF CWS,PILOT DIESEL,PURGE OIL & TRITON

2652 mm3/str 57 mm3/str 12 mm3/str 28 mm3/str

TOTAL ENERGY INP RATE: 1624892 KJ/HR 1540192 BTU/HR

** 20% PURGE OIL RETURNED TO FUEL TANK

HEAT RELEASE AND COMBUSTION ANALYSIS TR 4774 .L65

INJ ST: 40.4 DEG BTDC IGN ST: 22.4 DEG BTDC IGN LAG: 18.0 DEG CA

HEAT RELEASE CALCULATION FOR CWS TESTS

ENTER: LOG NO., FILE NO. OF PRESSURE DATA, & RPM OF RUN

66,145

12053

ENTER THE MANIFOLD AIR PRESSURE (PSIA) & TEMPERATURE (DEG F)

46.8, 187.8

ENTER TDC CORR. (+/- DEG), INJ ST (DEG BTDC) & INJ DURATION (DEG)

-.4, 35.52

ENTER COAL FRACTION & DENSITY OF CWS USED: 0.46, 1.08

ENTER "1" FOR UKON OR "2" FOR TRITON USED IN CWS: 2

ENTER COAL WT FRACTION OF TRITON USED IN CWS: 0.02

ENTER CONSUMPTION (LB/SEC), TEMP (DEG F) OF CONSTITUENTS

CWS: 5.5319E-2, 119.4

PILOT DIESEL: 9.7891E-4, 87.7

PURGE OIL: 3.2482E-4, 85

WT % OF COAL, PILOT DIESEL, PURGE OIL, TRITON & H2O IN FUEL

44.8 % 1.5 % 0.4 % 0.9 % 52.5 %

ENERGY % OF COAL, PILOT DIESEL, PURGE OIL, TRITON OF RUN

94.1 % 3.9 % 1.0 % 1.1 %

INJECTION PER STROKE OF CWS, PILOT DIESEL, PURGE OIL & TRITON

3152 mm3/str 60 mm3/str 15 mm3/str 30 mm3/str

TOTAL ENERGY INP RATE: 1760128 KJ/HR 1669367 BTU/HR

** 20% PURGE OIL RETURNED TO FUEL TANK

HEAT RELEASE AND COMBUSTION ANALYSIS

TR 4774 L66

HEAT RELEASE CALCULATION FOR CWS TESTS

ENTER: LOG NO., FILE NO. OF PRESSURE DATA, & RPM OF RUN
 67,149,1052
 ENTER THE MANIFOLD AIR PRESSURE (PSIA) & TEMPERATURE (DEG F)
 47.187.8
 ENTER TDC CORR.(+/- DEG), INJ ST(DEG BTDC) & INJ DURATION(DEG)
 -.4,40,51
 ENTER COAL FRACTION & DENSITY OF CWS USED: 0.46,1.00
 ENTER "1" FOR UKON OR "2" FOR TRITON USED IN CWS: 2
 ENTER COAL WT FRACTION OF TRITON USED IN CWS: 0.02
 ENTER CONSUMPTION (LB/SEC),TEMP(DEG F) OF CONSTITUENTS
 CWS: 6.697E-2,123.6
 PILOT DIESEL: 1.0024E-3,98.8
 PURGE OIL: 2.8566E-4,85
 WT % OF COAL,PILOT DIESEL,PURGE OIL,TRITON & H2O IN FUEL
 44.8 % 1.5 % 0.3 % 0.9 % 52.6 %
 ENERGY % OF COAL,PILOT DIESEL,PURGE OIL,TRITON OF RUN
 94.1 % 4.0 % 0.8 % 1.1 %
 INJECTION PER STROKE OF CWS,PILOT DIESEL,PURGE OIL & TRITON
 3181 mm3/str 61 mm3/str 13 mm3/str 30 mm3/str
 TOTAL ENERGY IHP RATE: 1773586 KJ/HR 1681124 BTU/HR
 ** 20% PURGE OIL RETURNED TO FUEL TANK

HEAT RELEASE AND COMBUSTION ANALYSIS TR 4774 L67

HEAT RELEASE CALCULATION FOR CWS TESTS

ENTER: LOG NO., FILE NO. OF PRESSURE DATA, & RPM OF RUN

68,153,1852

ENTER THE MANIFOLD AIR PRESSURE (PSIA) & TEMPERATURE (DEG F)

47.2,198.1

ENTER TDC CORR.(+/- DEG), INJ ST(DEG BTDC) & INJ DURATION(DEG)

-.4,30,52

ENTER COAL FRACTION & DENSITY OF CWS USED: 0.46,1.08

ENTER "1" FOR UKON OR "2" FOR TRITON USED IN CWS: 2

ENTER COAL WT FRACTION OF TRITON USED IN CWS: 0.02

ENTER CONSUMPTION (LB/SEC), TEMP(DEG F) OF CONSTITUENTS

CWS: 7.499E-2,126.8

PILOT DIESEL: 1.0397E-3,89.7

PURGE OIL: 2.8512E-4,85

WT % OF COAL,PILOT DIESEL,PURGE OIL,TRITON & H2O IN FUEL

44.8 % 1.4 % 0.3 % 0.9 % 52.6 %

ENERGY % OF COAL,PILOT DIESEL,PURGE OIL,TRITON OF RUN

94.5 % 3.7 % 0.8 % 1.1 %

INJECTION PER STROKE OF CWS,PILOT DIESEL,PURGE OIL & TRITON

3567 mm3/str 63 mm3/str 13 mm3/str 34 mm3/str

TOTAL ENERGY INP RATE: 1981199 KJ/HR 1877914 BTU/HR

** 20% PURGE OIL RETURNED TO FUEL TANK

HEAT RELEASE AND COMBUSTION ANALYSIS

TR 4774 L68

HEAT RELEASE CALCULATION FOR CWS TESTS

ENTER: LOG NO., FILE NO. OF PRESSURE DATA, & RPM OF RUN

69,157,1054

ENTER THE MANIFOLD AIR PRESSURE (PSIA) & TEMPERATURE (DEG F)

47.34,197.9

ENTER TDC CORR.(+/- DEG), INJ ST(DEG BTDC) & INJ DURATION(DEG)

-.4,20,52

ENTER COAL FRACTION & DENSITY OF CWS USED: 0.497,1.114

ENTER "1" FOR UKON OR "2" FOR TRITON USED IN CWS: 2

ENTER COAL WT FRACTION OF TRITON USED IN CWS: 0.02

ENTER CONSUMPTION (LB/SEC),TEMP(DEG F) OF CONSTITUENTS

CWS: 6.0493E-2,79.6

PILOT DIESEL: 9.583E-4,86.4

PURGE OIL: 1.9102E-4,85

WT % OF COAL,PILOT DIESEL,PURGE OIL,TRITON & H2O IN FUEL

48.3 % 1.6 % 0.2 % 1.9 % 48.9 %

ENERGY % OF COAL,PILOT DIESEL,PURGE OIL,TRITON OF RUN

94.5 % 3.9 % 0.6 % 1.1 %

INJECTION PER STROKE OF CWS,PILOT DIESEL,PURGE OIL & TRITON

2793 mm3/str 58 mm3/str 9 mm3/str 29 mm3/str

TOTAL ENERGY IHP RATE: 1726168 KJ/HR 1636178 BTU/HR

** 20% PURGE OIL RETURNED TO FUEL TANK

HEAT RELEASE AND COMBUSTION ANALYSIS

TR4774 L69

HEAT RELEASE CALCULATION FOR CWS TESTS

ENTER: LOG NO., FILE NO. OF PRESSURE DATA, & RPM OF RUN

70,161,1053

ENTER THE MANIFOLD AIR PRESSURE (PSIA) & TEMPERATURE (DEG F)

47,128

ENTER TDC CORR. (+/- DEG), INJ ST(DEG BTDC) & INJ DURATION(DEG)

-.4,45.44

ENTER COAL FRACTION & DENSITY OF CWS USED: 0.497,1.114

ENTER "1" FOR UKON OR "2" FOR TRITON USED IN CWS: 2

ENTER COAL WT FRACTION OF TRITON USED IN CWS: 0.02

ENTER CONSUMPTION (LB/SEC),TEMP(DEG F) OF CONSTITUENTS

CWS: 5.9671E-2,83.1

PILOT DIESEL: 1.0065E-3,90.7

PURGE OIL: 2.0991E-4,85

WT % OF COAL,PILOT DIESEL,PURGE OIL,TRITON & H2O IN FUEL

48.3 % 1.7 % 0.3 % 1.0 % 48.9 %

ENERGY % OF COAL,PILOT DIESEL,PURGE OIL,TRITON OF RUN

94.2 % 4.1 % 0.6 % 1.1 %

INJECTION PER STROKE OF CWS,PILOT DIESEL,PURGE OIL & TRITON

2747 mm3/str 61 mm3/str 10 mm3/str 29 mm3/str

TOTAL ENERGY INP RATE: 1708121 KJ/HR 1619072 BTU/HR

** 20% PURGE OIL RETURNED TO FUEL TANK

HEAT RELEASE AND COMBUSTION ANALYSIS

TR4774 L70

HEAT RELEASE CALCULATION FOR CWS TESTS

ENTER: LOG NO., FILE NO. OF PRESSURE DATA, & RPM OF RUN

71,165,1052

ENTER THE MANIFOLD AIR PRESSURE (PSIA) & TEMPERATURE (DEG F)

47.2,187.9

ENTER TDC CORR.(+/- DEG), INJ ST(DEG BTDC) & INJ DURATION(DEG)

-.4,40,43

ENTER COAL FRACTION & DENSITY OF CWS USED: 0.497,1.114

ENTER "1" FOR UKON OR "2" FOR TRITON USED IN CWS: 2

ENTER COAL WT FRACTION OF TRITON USED IN CWS: 0.02

ENTER CONSUMPTION (LB/SEC),TEMP(DEG F) OF CONSTITUENTS

CWS: 5.6915E-2,89

PILOT DIESEL: 9.5751E-4,90.5

PURGE OIL: 2.1515E-4,85

WT % OF COAL,PILOT DIESEL,PURGE OIL,TRITON & H2O IN FUEL

49.3 % 1.6 % 0.3 % 1.0 % 48.8 %

ENERGY % OF COAL,PILOT DIESEL,PURGE OIL,TRITON OF RUN

94.1 % 4.1 % 0.7 % 1.1 %

INJECTION PER STROKE OF CWS,PILOT DIESEL,PURGE OIL & TRITON

2623 mm3/str 58 mm3/str 10 mm3/str 28 mm3/str

TOTAL ENERGY INP RATE: 1629837 KJ/HR 1544869 BTU/HR

** 20% PURGE OIL RETURNED TO FUEL TANK

HEAT RELEASE AND COMBUSTION ANALYSIS

TR4774 L71

HEAT RELEASE CALCULATION FOR CWS TESTS

ENTER: LOG NO., FILE NO. OF PRESSURE DATA, & RPM OF RUN

72,169,1054

ENTER THE MANIFOLD AIR PRESSURE (PSIA) & TEMPERATURE (DEG F)

47,187.1

ENTER TDC CORR.(+/- DEG), INJ ST(DEG BTDC) & INJ DURATION(DEG)

-.4,30,43

ENTER COAL FRACTION & DENSITY OF CWS USED: 0.495,1.1

ENTER "1" FOR UKON OR "2" FOR TRITON USED IN CWS: 2

ENTER COAL WT FRACTION OF TRITON USED IN CWS: 0.02

ENTER CONSUMPTION (LB/SEC),TEMP(DEG F) OF CONSTITUENTS

CWS: 5.6078E-2,86.2

PILOT DIESEL: 9.3147E-4,91.5

PURGE OIL: 2.1305E-4,85

WT % OF COAL,PILOT DIESEL,PURGE OIL,TRITON & H2O IN FUEL

48.1 % 1.6 % 0.3 % 1.0 % 49.1 %

ENERGY % OF COAL,PILOT DIESEL,PURGE OIL,TRITON OF RUN

94.2 % 4.1 % 0.7 % 1.1 %

INJECTION PER STROKE OF CWS,PILOT DIESEL,PURGE OIL & TRITON

2612 mm3/str 57 mm3/str 10 mm3/str 27 mm3/str

TOTAL ENERGY INP RATE: 1598996 KJ/HR 1515636 BTU/HR

** 20% PURGE OIL RETURNED TO FUEL TANK

HEAT RELEASE AND COMBUSTION ANALYSIS

TR4774 L72

INJ ST: 30.4 DEG BTDC

IGN ST: 21.0 DEG BTDC

IGN LAG: 9.4 DEG CA

HEAT RELEASE CALCULATION FOR CWS TESTS

ENTER: LOG NO., FILE NO. OF PRESSURE DATA, & RPM OF RUN
 78,173,1052
 ENTER THE MANIFOLD AIR PRESSURE (PSIA) & TEMPERATURE (DEG F)
 47,186.8
 ENTER TDC CORR.(+/- DEG), INJ ST(DEG BTDC) & INJ DURATION(DEG)
 -.4,35,46

ENTER COAL FRACTION & DENSITY OF CWS USED: 0.46,1.185
 ENTER "1" FOR UKON OR "2" FOR TRITON USED IN CWS: 2
 ENTER COAL WT FRACTION OF TRITON USED IN CWS: 0.02
 ENTER CONSUMPTION (LB/SEC),TEMP(DEG F) OF CONSTITUENTS
 CWS: 6.0781E-2,96.33
 PILOT DIESEL: 9.9809E-4,98.94
 PURGE OIL: 1.9637E-4,85
 WT % OF COAL,PILOT DIESEL,PURGE OIL,TRITON & H2O IN FUEL
 44.7 % 1.6 % 0.2 % 0.9 % 52.5 %
 ENERGY % OF COAL,PILOT DIESEL,PURGE OIL,TRITON OF RUN
 94.0 % 4.3 % 0.6 % 1.1 %
 INJECTION PER STROKE OF CWS,PILOT DIESEL,PURGE OIL & TRITON
 2826 mm3/str 61 mm3/str 9 mm3/str 27 mm3/str
 TOTAL ENERGY INP RATE: 1614851 KJ/HR 1530664 BTU/HR
 ** 20% PURGE OIL RETURNED TO FUEL TANK

HEAT RELEASE AND COMBUSTION ANALYSIS TR4774 L73

HEAT RELEASE CALCULATION FOR CWS TESTS

ENTER: LOG NO., FILE NO. OF PRESSURE DATA, & RPM OF RUN
 74,177,1051
 ENTER THE MANIFOLD AIR PRESSURE (PSIA) & TEMPERATURE (DEG F)
 47,196.9
 ENTER TDC CORR.(+/- DEG), INJ ST(DEG BTDC) & INJ DURATION(DEG)
 -.4,40,46

ENTER COAL FRACTION & DENSITY OF CWS USED: 0.46,1.105
 ENTER "1" FOR UKON OR "2" FOR TRITON USED IN CWS: 2
 ENTER COAL WT FRACTION OF TRITON USED IN CWS: 0.02
 ENTER CONSUMPTION (LB/SEC),TEMP(DEG F) OF CONSTITUENTS
 CWS: 6.2155E-2,98.5
 PILOT DIESEL: 1.009E-3,101.4
 PURGE OIL: 2.5763E-4,85
 WT % OF COAL,PILOT DIESEL,PURGE OIL,TRITON & H2O IN FUEL
 44.7 % 1.6 % 0.3 % 0.9 % 52.5 %
 ENERGY % OF COAL,PILOT DIESEL,PURGE OIL,TRITON OF RUN
 93.9 % 4.3 % 0.8 % 1.1 %
 INJECTION PER STROKE OF CWS,PILOT DIESEL,PURGE OIL & TRITON
 2893 mm3/str 62 mm3/str 12 mm3/str 28 mm3/str
 TOTAL ENERGY INP RATE: 1653451 KJ/HR 1567252 BTU/HR
 ** 20% PURGE OIL RETURNED TO FUEL TANK

HEAT RELEASE AND COMBUSTION ANALYSIS TR4774 L74

HEAT RELEASE CALCULATION FOR CWS TESTS

ENTER: LOG NO., FILE NO. OF PRESSURE DATA, & RPM OF RUN

75,5,1055

ENTER THE MANIFOLD AIR PRESSURE (PSIA) & TEMPERATURE (DEG F)

47,187.4

ENTER TDC CORR.(+/- DEG), INJ ST(DEG BTDC) & INJ DURATION(DEG)

-.4,40,44

ENTER COAL FRACTION & DENSITY OF CWS USED: 0.487,1.099

ENTER "1" FOR UKON OR "2" FOR TRITON USED IN CWS: 2

ENTER COAL WT FRACTION OF TRITON USED IN CWS: 0.02

ENTER CONSUMPTION (LB/SEC), TEMP(DEG F) OF CONSTITUENTS

CWS: 5.9712E-2,79.9

PILOT DIESEL: 8.5615E-4,87.6

PURGE OIL: 1.8793E-4,95

WT % OF COAL,PILOT DIESEL,PURGE OIL,TRITON & H2O IN FUEL

47.4 % 1.4 % 0.2 % 0.9 % 50.0 %

ENERGY % OF COAL,PILOT DIESEL,PURGE OIL,TRITON OF RUN

94.8 % 3.6 % 0.6 % 1.1 %

INJECTION PER STROKE OF CWS,PILOT DIESEL,PURGE OIL & TRITON

2782 mm3/str 52 mm3/str 9 mm3/str 28 mm3/str

TOTAL ENERGY INP RATE: 1665133 KJ/HR 1578325 BTU/HR

** 20% PURGE OIL RETURNED TO FUEL TANK

HEAT RELEASE AND COMBUSTION ANALYSIS

TR4774 L75

INJ ST: 40.4 DEG BTDC

IGN ST: 23.1 DEG BTDC

IGN LAG: 17.3 DEG CA

HEAT RELEASE CALCULATION FOR CWS TESTS

ENTER: LOG NO., FILE NO. OF PRESSURE DATA, & RPM OF RUN

76,9,1054

ENTER THE MANIFOLD AIR PRESSURE (PSIA) & TEMPERATURE (DEG F)

47.1,197.3

ENTER TDC CORR.(+/- DEG), INJ ST(DEG BTDC) & INJ DURATION(DEG)

-.4,35,42

ENTER COAL FRACTION & DENSITY OF CWS USED: 0.487,1.099

ENTER "1" FOR UKON OR "2" FOR TRITON USED IN CWS: 2

ENTER COAL WT FRACTION OF TRITON USED IN CWS: 0.02

ENTER CONSUMPTION (LB/SEC),TEMP(DEG F) OF CONSTITUENTS

CWS: 5.6459E-2,83.8

PILOT DIESEL: 9.6627E-4,93.3

PURGE OIL: 2.7106E-4,85

WT % OF COAL,PILOT DIESEL,PURGE OIL,TRITON & H2O IN FUEL

47.3 % 1.7 % 0.4 % 0.9 % 49.8 %

ENERGY % OF COAL,PILOT DIESEL,PURGE OIL,TRITON OF RUN

93.8 % 4.2 % 0.9 % 1.1 %

INJECTION PER STROKE OF CWS,PILOT DIESEL,PURGE OIL & TRITON

2633 mm3/str 59 mm3/str 12 mm3/str 27 mm3/str

TOTAL ENERGY INP RATE: 1590254 KJ/HR 1507350 BTU/HR

** 20% PURGE OIL RETURNED TO FUEL TANK

HEAT RELEASE AND COMBUSTION ANALYSIS

TR4774 L76

HEAT RELEASE CALCULATION FOR CWS TESTS

ENTER: LOG NO., FILE NO. OF PRESSURE DATA, & RPM OF RUN
 81,29,1052
 ENTER THE MANIFOLD AIR PRESSURE (PSIA) & TEMPERATURE (DEG F)
 47.24,186.4
 ENTER TDC CORR. (+/- DEG), INJ ST (DEG BTDC) & INJ DURATION (DEG)
 -.4,30,55

ENTER COAL FRACTION & DENSITY OF CWS USED: 0.493,1.11
 ENTER "1" FOR UKOH OR "2" FOR TRITON USED IN CWS: 2
 ENTER COAL WT FRACTION OF TRITON USED IN CWS: 0.02
 ENTER CONSUMPTION (LB/SEC), TEMP (DEG F) OF CONSTITUENTS
 CWS: 5.6071E-2,91.5
 PILOT DIESEL: 1.1115E-3,96.8
 PURGE OIL: 2.4676E-4,85
 WT % OF COAL, PILOT DIESEL, PURGE OIL, TRITON & H2O IN FUEL
 47.7 % 1.9 % 0.3 % 1.0 % 49.1 %
 ENERGY % OF COAL, PILOT DIESEL, PURGE OIL, TRITON OF RUN
 93.3 % 4.8 % 0.8 % 1.0 %
 INJECTION PER STROKE OF CWS, PILOT DIESEL, PURGE OIL & TRITON
 2594 mm3/str 68 mm3/str 11 mm3/str 27 mm3/str
 TOTAL ENERGY IHP RATE: 1607074 KJ/HR 1523293 BTU/HR
 ** 20% PURGE OIL RETURNED TO FUEL TANK

HEAT RELEASE AND COMBUSTION ANALYSIS TR4774 L81

HEAT RELEASE CALCULATION FOR CWS TESTS

ENTER: LOG NO., FILE NO. OF PRESSURE DATA, & RPM OF RUN
 82,33,1851
 ENTER THE MANIFOLD AIR PRESSURE (PSIA) & TEMPERATURE (DEG F)
 47.01,186.4
 ENTER TDC CORR.(+/- DEG), INJ ST(DEG BTDC) & INJ DURATION(DEG)
 -.4,40,53
 ENTER COAL FRACTION & DENSITY OF CWS USED: 0.493,1.11
 ENTER "1" FOR UKON OR "2" FOR TRITON USED IN CWS: 2
 ENTER COAL WT FRACTION OF TRITON USED IN CWS: 0.02
 ENTER CONSUMPTION (LB/SEC),TEMP(DEG F) OF CONSTITUENTS
 CWS: 5.4455E-2,94.5
 PILOT DIESEL: 1.1346E-3,99.15
 PURGE OIL: 2.6311E-4,85
 WT % OF COAL,PILOT DIESEL,PURGE OIL,TRITON & H2O IN FUEL
 47.7 % 2.0 % 0.4 % 1.0 % 49.0 %
 ENERGY % OF COAL,PILOT DIESEL,PURGE OIL,TRITON OF RUN
 93.0 % 5.1 % 0.9 % 1.0 %
 INJECTION PER STROKE OF CWS,PILOT DIESEL,PURGE OIL & TRITON
 2521 mm3/str 69 mm3/str 12 mm3/str 26 mm3/str
 TOTAL ENERGY INP RATE: 1565844 KJ/HR 1484212 BTU/HR
 ** 20% PURGE OIL RETURNED TO FUEL TANK

HEAT RELEASE AND COMBUSTION ANALYSIS TR4774 L82

HEAT RELEASE CALCULATION FOR CWS TESTS

ENTER: LOG NO., FILE NO. OF PRESSURE DATA, & RPM OF RUN
 83,37,1050
 ENTER THE MANIFOLD AIR PRESSURE (PSIA) & TEMPERATURE (DEG F)
 47.03,186.5
 ENTER TDC CORR.(+/- DEG), INJ ST(DEG BTDC) & INJ DURATION(DEG)
 -.4,50,56

ENTER COAL FRACTION & DENSITY OF CWS USED: 0.493,1.11
 ENTER "1" FOR UKON OR "2" FOR TRITON USED IN CWS: 2.0000
 ENTER COAL WT FRACTION OF TRITON USED IN CWS: 0.02
 ENTER CONSUMPTION (LB/SEC),TEMP(DEG F) OF CONSTITUENTS
 CWS: 5.7758E-2,97.9
 PILOT DIESEL: 1.0753E-3,101
 PURGE OIL: 2.7805E-4,85
 WT % OF COAL,PILOT DIESEL,PURGE OIL,TRITON & H2O IN FUEL
 47.9 % 1.8 % 0.4 % 1.0 % 49.1 %
 ENERGY % OF COAL,PILOT DIESEL,PURGE OIL,TRITON OF RUN
 93.5 % 4.6 % 0.9 % 1.0 %
 INJECTION PER STROKE OF CWS,PILOT DIESEL,PURGE OIL & TRITON
 2677 mm3/str 66 mm3/str 13 mm3/str 28 mm3/str
 TOTAL ENERGY INP RATE: 1651807 KJ/HR 1565694 BTU/HR
 ** 20% PURGE OIL RETURNED TO FUEL TANK

HEAT RELEASE AND COMBUSTION ANALYSIS TR4774 L03

HEAT RELEASE CALCULATION FOR CWS TESTS

ENTER: LOG NO., FILE NO. OF PRESSURE DATA, & RPM OF RUN
84,41,1852
ENTER THE MANIFOLD AIR PRESSURE (PSIA) & TEMPERATURE (DEG F)
47,186.9
ENTER TDC CORR.(+/- DEG), INJ ST(DEG BTDC) & INJ DURATION(DEG)
-.4,40,53

ENTER COAL FRACTION & DENSITY OF CWS USED: 0.493,1.12
ENTER "1" FOR UKON OR "2" FOR TRITON USED IN CWS: 2
ENTER COAL WT FRACTION OF TRITON USED IN CWS: 0.02
ENTER CONSUMPTION (LB/SEC),TEMP(DEG F) OF CONSTITUENTS
CWS: 5.5235E-2,86.2
PILOT DIESEL: 1.0711E-3,92.8
PURGE OIL: 2.1677E-4,85
WT % OF COAL,PILOT DIESEL,PURGE OIL,TRITON & H2O IN FUEL
47.8 % 1.9 % 0.3 % 1.0 % 49.1 %
ENERGY % OF COAL,PILOT DIESEL,PURGE OIL,TRITON OF RUN
93.5 % 4.7 % 0.7 % 1.0 %
INJECTION PER STROKE OF CWS,PILOT DIESEL,PURGE OIL & TRITON
2532 mm3/str 65 mm3/str 10 mm3/str 27 mm3/str
TOTAL ENERGY INP RATE: 1580067 KJ/HR 1497693 BTU/HR
** 20% PURGE OIL RETURNED TO FUEL TANK

HEAT RELEASE AND COMBUSTION ANALYSIS TR4774 L84

HEAT RELEASE CALCULATION FOR CWS TESTS

ENTER: LOG NO., FILE NO. OF PRESSURE DATA, & RPM OF RUN

85,45,1051

ENTER THE MANIFOLD AIR PRESSURE (PSIA) & TEMPERATURE (DEG F)

47,186.9

ENTER TDC CORR.(+/- DEG), INJ ST(DEG BTDC) & INJ DURATION(DEG)

-.4,30,55

ENTER COAL FRACTION & DENSITY OF CWS USED: 0.493,1.12

ENTER "1" FOR UKON OR "2" FOR TRITON USED IN CWS: 2

ENTER COAL WT FRACTION OF TRITON USED IN CWS: 0.02

ENTER CONSUMPTION (LB/SEC),TEMP(DEG F) OF CONSTITUENTS

CWS: 5.6907E-2,89.2

PILOT DIESEL: 1.0724E-3,94.5

PURGE OIL: 2.5637E-4,85

WT % OF COAL,PILOT DIESEL,PURGE OIL,TRITON & H2O IN FUEL

47.8 % 1.8 % 0.3 % 1.0 % 49.1 %

ENERGY % OF COAL,PILOT DIESEL,PURGE OIL,TRITON OF RUN

93.5 % 4.6 % 0.8 % 1.0 %

INJECTION PER STROKE OF CWS,PILOT DIESEL,PURGE OIL & TRITON

2611 mm3/str 65 mm3/str 12 mm3/str 27 mm3/str

TOTAL ENERGY INP RATE: 1627452 KJ/HR 1542609 BTU/HR

** 20% PURGE OIL RETURNED TO FUEL TANK

HEAT RELEASE AND COMBUSTION ANALYSIS

TR4774 L85

HEAT RELEASE CALCULATION FOR CWS TESTS

ENTER: LOG NO., FILE NO. OF PRESSURE DATA, & RPM OF RUN

86,49,1050

ENTER THE MANIFOLD AIR PRESSURE (PSIA) & TEMPERATURE (DEG F)

47.3,186.5

ENTER TDC CORR.(+/- DEG), INJ ST(DEG BTDC) & INJ DURATION(DEG)

-.4,30,54

ENTER COAL FRACTION & DENSITY OF CWS USED: 0.493,1.12

ENTER "1" FOR UKON OR "2" FOR TRITON USED IN CWS: 2

ENTER COAL WT FRACTION OF TRITON USED IN CWS: 0.02

ENTER CONSUMPTION (LB/SEC),TEMP(DEG F) OF CONSTITUENTS

CWS: 5.5701E-2,92.7

PILOT DIESEL: 1.1173E-3,97.6

PURGE OIL: 2.8208E-4,85

WT % OF COAL,PILOT DIESEL,PURGE OIL,TRITON & H2O IN FUEL

47.7 % 2.0 % 0.4 % 1.0 % 49.0 %

ENERGY % OF COAL,PILOT DIESEL,PURGE OIL,TRITON OF RUN

93.1 % 4.9 % 0.9 % 1.0 %

INJECTION PER STROKE OF CWS,PILOT DIESEL,PURGE OIL & TRITON

2558 mm3/str 68 mm3/str 13 mm3/str 27 mm3/str

TOTAL ENERGY INP RATE: 1599326 KJ/HR 1515949 BTU/HR

** 20% PURGE OIL RETURNED TO FUEL TANK

HEAT RELEASE AND COMBUSTION ANALYSIS TR4774 L86

HEAT RELEASE CALCULATION FOR CWS TESTS

ENTER: LOG NO., FILE NO. OF PRESSURE DATA, & RPM OF RUN
 87,53,1049
 ENTER THE MANIFOLD AIR PRESSURE (PSIA) & TEMPERATURE (DEG F)
 42.2,136.2
 ENTER TDC CORR.(+/- DEG), INJ ST(DEG BTDC) & INJ DURATION(DEG)
 -.4,40,53

ENTER COAL FRACTION & DENSITY OF CWS USED: 0.493,1.12
 ENTER "1" FOR UKON OR "2" FOR TRITON USED IN CWS: 2
 ENTER COAL WT FRACTION OF TRITON USED IN CWS: 0.02
 ENTER CONSUMPTION (LB/SEC),TEMP(DEG F) OF CONSTITUENTS
 CWS: 5.4475E-2,96.1
 PILOT DIESEL: 1.1050E-3,99.62
 PURGE OIL: 2.7725E-4,85
 WT % OF COAL,PILOT DIESEL,PURGE OIL,TRITON & H2O IN FUEL
 47.7 % 2.0 % 0.4 % 1.0 % 49.0 %
 ENERGY % OF COAL,PILOT DIESEL,PURGE OIL,TRITON OF RUN
 93.1 % 4.9 % 0.9 % 1.0 %
 INJECTION PER STROKE OF CWS,PILOT DIESEL,PURGE OIL & TRITON
 2504 mm3/str 68 mm3/str 13 mm3/str 26 mm3/str
 TOTAL ENERGY INP RATE: 1565088 KJ/HR 1483496 BTU/HR
 ** 20% PURGE OIL RETURNED TO FUEL TANK

HEAT RELEASE AND COMBUSTION ANALYSIS TR4774 L87

HEAT RELEASE CALCULATION FOR CWS TESTS

ENTER: LOG NO., FILE NO. OF PRESSURE DATA, & RPM OF RUN
91,69,1053

ENTER THE MANIFOLD AIR PRESSURE (PSIA) & TEMPERATURE (DEG F)
46.9,197.2

ENTER TDC CORR. (+/- DEG), INJ ST(DEG BTDC) & INJ DURATION(DEG)
-.4,35,56

ENTER COAL FRACTION & DENSITY OF CWS USED: 0.491,1.12

ENTER "1" FOR UKON OR "2" FOR TRITON USED IN CWS: 2

ENTER COAL WT FRACTION OF TRITON USED IN CWS: 0.02

ENTER CONSUMPTION (LB/SEC), TEMP(DEG F) OF CONSTITUENTS

CWS: 5.9883E-2,86

PILOT DIESEL: 9.0127E-4,92

PURGE OIL: 2.2298E-4,85

WT % OF COAL,PILOT DIESEL,PURGE OIL,TRITON & H2O IN FUEL

47.8 % 1.5 % 0.3 % 1.0 % 49.5 %

ENERGY % OF COAL,PILOT DIESEL,PURGE OIL,TRITON OF RUN

94.5 % 3.7 % 0.7 % 1.1 %

INJECTION PER STROKE OF CWS,PILOT DIESEL,PURGE OIL & TRITON

2743 mm3/str 55 mm3/str 10 mm3/str 29 mm3/str

TOTAL ENERGY INP RATE: 1687710 KJ/HR 1599725 BTU/HR

** 20% PURGE OIL RETURNED TO FUEL TANK

HEAT RELEASE AND COMBUSTION ANALYSIS 4774 L91

HEAT RELEASE CALCULATION FOR CWS TESTS

ENTER: LOG NO., FILE NO. OF PRESSURE DATA, & RPM OF RUH
 92,73,963
 ENTER THE MANIFOLD AIR PRESSURE (PSIA) & TEMPERATURE (DEG F)
 22.8,172
 ENTER TDC CORR.(<+/- DEG>), INJ ST(DEG BTDC) & INJ DURATION(DEG)
 -.4,30,31

ENTER COAL FRACTION & DENSITY OF CWS USED: 0.491,1.12
 ENTER "1" FOR UKON OR "2" FOR TRITON USED IN CWS: 2
 ENTER COAL WT FRACTION OF TRITON USED IN CWS: 0.02
 ENTER CONSUMPTION (LB/SEC),TEMP(DEG F) OF CONSTITUENTS
 CWS: 3.4358E-2,93
 PILOT DIESEL: 1.1529E-3,97
 PURGE OIL: 2.1979E-4,85
 WT % OF COAL,PILOT DIESEL,PURGE OIL,TRITON & H2O IN FUEL
 46.8 % 3.2 % 0.5 % 0.9 % 48.5 %
 ENERGY % OF COAL,PILOT DIESEL,PURGE OIL,TRITON OF RUN
 89.9 % 7.9 % 1.1 % 1.0 %
 INJECTION PER STROKE OF CWS,PILOT DIESEL,PURGE OIL & TRITON
 1721 mm3/str 77 mm3/str 11 mm3/str 18 mm3/str
 TOTAL ENERGY INP RATE: 1017613 KJ/HR 964562 BTU/HR
 ** 20% PURGE OIL RETURNED TO FUEL TANK

HEAT RELEASE AND COMBUSTION ANALYSIS TR4774 L92

HEAT RELEASE CALCULATION FOR CWS TESTS

ENTER: LOG NO., FILE NO. OF PRESSURE DATA, & RPM OF RUN

93,77,963

ENTER THE MANIFOLD AIR PRESSURE (PSIA) & TEMPERATURE (DEG F)

22.8,172

ENTER TDC CORR.(+/- DEG), INJ ST(DEG BTDC) & INJ DURATION(DEG)

-.4,25,28

ENTER COAL FRACTION & DENSITY OF CWS USED: 0.491,1.12

ENTER "1" FOR UKON OR "2" FOR TRITON USED IN CWS: 2

ENTER COAL WT FRACTION OF TRITON USED IN CWS: 0.02

ENTER CONSUMPTION (LB/SEC),TEMP(DEG F) OF CONSTITUENTS

CWS: 3.0714E-2,95

PILOT DIESEL: 1.1409E-3,98.1

PURGE OIL: 3.2686E-4,85

WT % OF COAL,PILOT DIESEL,PURGE OIL,TRITON & H2O IN FUEL

46.5 % 3.6 % 0.8 % 0.9 % 48.2 %

ENERGY % OF COAL,PILOT DIESEL,PURGE OIL,TRITON OF RUN

89.5 % 8.6 % 1.9 % 1.0 %

INJECTION PER STROKE OF CWS,PILOT DIESEL,PURGE OIL & TRITON

1538 mm3/str 76 mm3/str 16 mm3/str 16 mm3/str

TOTAL ENERGY INP RATE: 924237 KJ/HR 876054 BTU/HR

** 20% PURGE OIL RETURNED TO FUEL TANK

HEAT RELEASE AND COMBUSTION ANALYSIS

TR4774 L93

HEAT RELEASE CALCULATION FOR CWS TESTS

ENTER: LOG NO., FILE NO. OF PRESSURE DATA, & RPM OF RUN
 94,81,953
 ENTER THE MANIFOLD AIR PRESSURE (PSIA) & TEMPERATURE (DEG F)
 22.9,172
 ENTER TDC CORR.(+/- DEG), INJ ST(DEG BTDC) & INJ DURATION(DEG)
 -.4,20,26
 ENTER COAL FRACTION & DENSITY OF CWS USED: 0.491,1.12
 ENTER "1" FOR UKON OR "2" FOR TRITON USED IN CWS: 2
 ENTER COAL WT FRACTION OF TRITON USED IN CWS: 0.02
 ENTER CONSUMPTION (LB/SEC),TEMP(DEG F) OF CONSTITUENTS
 CWS: 2.8563E-2,96.8
 PILOT DIESEL: 1.1304E-3,98.6
 PURGE OIL: 2.7804E-4,85
 WT % OF COAL,PILOT DIESEL,PURGE OIL,TRITON & H2O IN FUEL
 46.4 % 3.8 % 0.7 % 0.9 % 48.1 %
 ENERGY % OF COAL,PILOT DIESEL,PURGE OIL,TRITON OF RUN
 88.2 % 9.2 % 1.7 % 1.0 %
 INJECTION PER STROKE OF CWS,PILOT DIESEL,PURGE OIL & TRITON
 1430 mm3/str 75 mm3/str 14 mm3/str 15 mm3/str
 TOTAL ENERGY INP RATE: 863003 KJ/HR 818012 BTU/HR
 ** 20% PURGE OIL RETURNED TO FUEL TANK

HEAT RELEASE AND COMBUSTION ANALYSIS TR4774 L94

HEAT RELEASE CALCULATION FOR CWS TESTS

ENTER: LOG NO., FILE NO. OF PRESSURE DATA, & RPM OF RUN
 95,85,963
 ENTER THE MANIFOLD AIR PRESSURE (PSIA) & TEMPERATURE (DEG F)
 22.8,172
 ENTER TDC CORR.(+/- DEG), INJ ST(DEG BTDC) & INJ DURATION(DEG)
 -.4,15,26

ENTER COAL FRACTION & DENSITY OF CWS USED: 0.491,1.12
 ENTER "1" FOR UKON OR "2" FOR TRITON USED IN CWS: 2
 ENTER COAL WT FRACTION OF TRITON USED IN CWS: 0.02
 ENTER CONSUMPTION (LB/SEC),TEMP(DEG F) OF CONSTITUENTS
 CWS: 2.8505E-2,100.4
 PILOT DIESEL: 1.1198E-3,99.6
 PURGE OIL: 3.2349E-4,95
 WT % OF COAL,PILOT DIESEL,PURGE OIL,TRITON & H2O IN FUEL
 46.4 % 3.7 % 0.8 % 0.9 % 48.1 %
 ENERGY % OF COAL,PILOT DIESEL,PURGE OIL,TRITON OF RUN
 88.0 % 9.1 % 2.0 % 1.0 %
 INJECTION PER STROKE OF CWS,PILOT DIESEL,PURGE OIL & TRITON
 1428 mm3/str 75 mm3/str 16 mm3/str 15 mm3/str
 TOTAL ENERGY INP RATE: 863084 KJ/HR 810089 BTU/HR
 ** 20% PURGE OIL RETURNED TO FUEL TANK

HEAT RELEASE AND COMBUSTION ANALYSIS TR4774 L95

HEAT RELEASE CALCULATION FOR CWS TESTS

ENTER: LOG NO., FILE NO. OF PRESSURE DATA, & RPM OF RUN
 96,89,960
 ENTER THE MANIFOLD AIR PRESSURE (PSIA) & TEMPERATURE (DEG F)
 37,183
 ENTER TDC CORR.(+/- DEG), INJ ST(DEG BTDC) & INJ DURATION(DEG)
 -.4,25,46

ENTER COAL FRACTION & DENSITY OF CWS USED: 0.492,1.11
 ENTER "1" FOR UKON OR "2" FOR TRITON USED IN CWS: 2
 ENTER COAL WT FRACTION OF TRITON USED IN CWS: 0.02
 ENTER CONSUMPTION (LB/SEC),TEMP(DEG F) OF CONSTITUENTS
 CWS: 4.9215E-2,91
 PILOT DIESEL: 1.001E-3,94
 PURGE OIL: 2.189E-4,85
 WT % OF COAL,PILOT DIESEL,PURGE OIL,TRITON & H2O IN FUEL
 47.6 % 2.0 % 0.3 % 1.0 % 49.1 %
 ENERGY % OF COAL,PILOT DIESEL,PURGE OIL,TRITON OF RUN
 93.2 % 5.0 % 0.8 % 1.0 %
 INJECTION PER STROKE OF CWS,PILOT DIESEL,PURGE OIL & TRITON
 2495 mm3/str 67 mm3/str 11 mm3/str 26 mm3/str
 TOTAL ENERGY INP RATE: 1409796 KJ/HR 1336300 BTU/HR
 ** 20% PURGE OIL RETURNED TO FUEL TANK

HEAT RELEASE AND COMBUSTION ANALYSIS 4774 L96

HEAT RELEASE CALCULATION FOR CWS TESTS

ENTER: LOG NO., FILE NO. OF PRESSURE DATA, & RPM OF RUN

97,93,965

ENTER THE MANIFOLD AIR PRESSURE (PSIA) & TEMPERATURE (DEG F)

37,183

ENTER TDC CORR. (+/- DEG), INJ ST (DEG BTDC) & INJ DURATION (DEG)

-.4,30,46

ENTER COAL FRACTION & DENSITY OF CWS USED: 0.492,1.11

ENTER "1" FOR UKON OR "2" FOR TRITON USED IN CWS: 2

ENTER COAL WT FRACTION OF TRITON USED IN CWS: 0.02

ENTER CONSUMPTION (LB/SEC), TEMP (DEG F) OF CONSTITUENTS

CWS: 5.0827E-2,93

PILOT DIESEL: 1.0244E-3,97

PURGE OIL: 2.126E-4,85

WT % OF COAL, PILOT DIESEL, PURGE OIL, TRITON & H2O IN FUEL

47.6 % 2.0 % 0.3 % 1.0 % 49.2 %

ENERGY % OF COAL, PILOT DIESEL, PURGE OIL, TRITON OF RUN

93.3 % 4.9 % 0.8 % 1.0 %

INJECTION PER STROKE OF CWS, PILOT DIESEL, PURGE OIL & TRITON

2563 mm3/str 68 mm3/str 11 mm3/str 27 mm3/str

TOTAL ENERGY INP RATE: 1454610 KJ/HR 1378777 BTU/HR

** 20% PURGE OIL RETURNED TO FUEL TANK

HEAT RELEASE AND COMBUSTION ANALYSIS

4774 L97

HEAT RELEASE CALCULATION FOR CWS TESTS

ENTER: LOG NO., FILE NO. OF PRESSURE DATA, & RPM OF RUN

98,101,965

ENTER THE MANIFOLD AIR PRESSURE (PSIA) & TEMPERATURE (DEG F)

29,183

ENTER TDC CORR. (+/- DEG), INJ ST (DEG BTDC) & INJ DURATION (DEG)

-.4,30,38

ENTER COAL FRACTION & DENSITY OF CWS USED: 0.492,1.11

ENTER "1" FOR UKOH OR "2" FOR TRITON USED IN CWS: 2

ENTER COAL WT FRACTION OF TRITON USED IN CWS: 0.02

ENTER CONSUMPTION (LB/SEC), TEMP (DEG F) OF CONSTITUENTS

CWS: 4.1723E-2,97

PILOT DIESEL: 1.006E-3,99

PURGE OIL: 3.1965E-4,85

WT % OF COAL, PILOT DIESEL, PURGE OIL, TRITON & H2O IN FUEL

47.3 % 2.3 % 0.6 % 0.9 % 48.8 %

ENERGY % OF COAL, PILOT DIESEL, PURGE OIL, TRITON OF RUN

91.8 % 5.8 % 1.4 % 1.0 %

INJECTION PER STROKE OF CWS, PILOT DIESEL, PURGE OIL & TRITON

2104 mm3/str 67 mm3/str 16 mm3/str 22 mm3/str

TOTAL ENERGY INP RATE: 1213171 KJ/HR 1149925 BTU/HR

** 20% PURGE OIL RETURNED TO FUEL TANK

HEAT RELEASE AND COMBUSTION ANALYSIS

4774 L98

HEAT RELEASE CALCULATION FOR CWS TESTS

ENTER: LOG NO., FILE NO. OF PRESSURE DATA, & RPM OF RUN

99,105,965

ENTER THE MANIFOLD AIR PRESSURE (PSIA) & TEMPERATURE (DEG F)

29,103

ENTER TDC CORR. (+/- DEG), INJ ST (DEG BTDC) & INJ DURATION (DEG)

-.4,25,36

ENTER COAL FRACTION & DENSITY OF CWS USED: 0.492,1.11

ENTER "1" FOR UKON OR "2" FOR TRITON USED IN CWS: 2

ENTER COAL WT FRACTION OF TRITON USED IN CWS: 0.02

ENTER CONSUMPTION (LB/SEC), TEMP (DEG F) OF CONSTITUENTS

CWS: 3.9658E-2,99

PILOT DIESEL: 1.0112E-3,99.8

PURGE OIL: 3.006E-4,85

WT % OF COAL, PILOT DIESEL, PURGE OIL, TRITON & H2O IN FUEL

47.2 % 2.5 % 0.6 % 0.9 % 48.8 %

ENERGY % OF COAL, PILOT DIESEL, PURGE OIL, TRITON OF RUN

91.5 % 6.1 % 1.4 % 1.0 %

INJECTION PER STROKE OF CWS, PILOT DIESEL, PURGE OIL & TRITON

2000 mm3/str 67 mm3/str 15 mm3/str 21 mm3/str

TOTAL ENERGY INP RATE: 1156853 KJ/HR 1096544 BTU/HR

** 20% PURGE OIL RETURNED TO FUEL TANK

HEAT RELEASE AND COMBUSTION ANALYSIS

4774 L99

HEAT RELEASE CALCULATION FOR CWS TESTS

ENTER: LOG NO., FILE NO. OF PRESSURE DATA, & RPM OF RUN

100.0,109,965

ENTER THE MANIFOLD AIR PRESSURE (PSIA) & TEMPERATURE (DEG F)

29,183

ENTER TDC CORR.(+/- DEG), INJ ST(DEG BTDC) & INJ DURATION(DEG)

-.4,20,36

ENTER COAL FRACTION & DENSITY OF CWS USED: 0.492,1.11

ENTER "1" FOR UKON OR "2" FOR TRITON USED IN CWS: 2

ENTER COAL WT FRACTION OF TRITON USED IN CWS: 0.02

ENTER CONSUMPTION (LB/SEC),TEMP(DEG F) OF CONSTITUENTS

CWS: 3.7472E-2,100

PILOT DIESEL: 1.053E-3,100

PURGE OIL: 2.948E-4,85

WT % OF COAL,PILOT DIESEL,PURGE OIL,TRITON & H2O IN FUEL

47.1 % 2.7 % 0.6 % 0.9 % 48.7 %

ENERGY % OF COAL,PILOT DIESEL,PURGE OIL,TRITON OF RUN

90.9 % 6.7 % 1.4 % 1.0 %

INJECTION PER STROKE OF CWS,PILOT DIESEL,PURGE OIL & TRITON

1890 mm3/str 70 mm3/str 15 mm3/str 20 mm3/str

TOTAL ENERGY INP RATE: 1100473 KJ/HR 1043102 BTU/HR

** 20% PURGE OIL RETURNED TO FUEL TANK

HEAT RELEASE AND COMBUSTION ANALYSIS

4774 L100

HEAT RELEASE CALCULATION FOR CWS TESTS

ENTER: LOG NO., FILE NO. OF PRESSURE DATA, & RPM OF RUN
 101,113,890
 ENTER THE MANIFOLD AIR PRESSURE (PSIA) & TEMPERATURE (DEG F)
 17.160
 ENTER TDC CORR.(+/- DEG), INJ ST(DEG BTDC) & INJ DURATION(DEG)
 -.4,20,19

ENTER COAL FRACTION & DENSITY OF CWS USED: 0.491,1.11
 ENTER "1" FOR UKON OR "2" FOR TRITON USED IN CWS: 2
 ENTER COAL WT FRACTION OF TRITON USED IN CWS: 0.02
 ENTER CONSUMPTION (LB/SEC),TEMP(DEG F) OF CONSTITUENTS
 CWS: 1.4786E-2,93
 PILOT DIESEL: 1.3544E-3,88.9
 PURGE OIL: 2.1658E-4,85
 WT % OF COAL,PILOT DIESEL,PURGE OIL,TRITON & H2O IN FUEL
 44.1 % 8.3 % 1.0 % 0.9 % 45.7 %
 ENERGY % OF COAL,PILOT DIESEL,PURGE OIL,TRITON OF RUN
 78.1 % 18.8 % 2.3 % 0.9 %
 INJECTION PER STROKE OF CWS,PILOT DIESEL,PURGE OIL & TRITON
 818 mm3/str 99 mm3/str 12 mm3/str 8 mm3/str
 TOTAL ENERGY INP RATE: 504355 KJ/HR 478062 BTU/HR
 ** 20% PURGE OIL RETURNED TO FUEL TANK

HEAT RELEASE AND COMBUSTION ANALYSIS TR4774 L101

HEAT RELEASE CALCULATION FOR CWS TESTS

ENTER: LOG NO., FILE NO. OF PRESSURE DATA, & RPM OF RUN

102,117,890

ENTER THE MANIFOLD AIR PRESSURE (PSIA) & TEMPERATURE (DEG F)

17,160

ENTER TDC CORR. (+/- DEG), INJ ST (DEG BTDC) & INJ DURATION (DEG)

-.4, 15, 18

ENTER COAL FRACTION & DENSITY OF CWS USED: 0.491, 1.11

ENTER "1" FOR UKON OR "2" FOR TRITON USED IN CWS: 2

ENTER COAL WT FRACTION OF TRITON USED IN CWS: 0.02

ENTER CONSUMPTION (LB/SEC), TEMP (DEG F) OF CONSTITUENTS

CWS: 1.501E-2, 95.8

PILOT DIESEL: 1.2119E-3, 96.7

PURGE OIL: 2.1674E-4, 85

WT % OF COAL, PILOT DIESEL, PURGE OIL, TRITON & H2O IN FUEL

44.5 % 7.4 % 1.0 % 0.9 % 46.2 %

ENERGY % OF COAL, PILOT DIESEL, PURGE OIL, TRITON OF RUN

79.9 % 16.9 % 2.3 % 0.9 %

INJECTION PER STROKE OF CWS, PILOT DIESEL, PURGE OIL & TRITON

830 mm3/str 88 mm3/str 12 mm3/str 9 mm3/str

TOTAL ENERGY INP RATE: 500431 KJ/HR 474342 BTU/HR

** 20% PURGE OIL RETURNED TO FUEL TANK

HEAT RELEASE AND COMBUSTION ANALYSIS TR4774 L102

HEAT RELEASE CALCULATION FOR CWS TESTS

ENTER: LOG NO., FILE NO. OF PRESSURE DATA, & RPM OF RUN

103,121,880

ENTER THE MANIFOLD AIR PRESSURE (PSIA) & TEMPERATURE (DEG F)

15.9,160.4

ENTER TDC CORR.(+/- DEG), INJ ST(DEG BTDC) & INJ DURATION(DEG)

-.4,15,17

ENTER COAL FRACTION & DENSITY OF CWS USED: 0.491,1.11

ENTER "1" FOR UKON OR "2" FOR TRITON USED IN CWS: 2

ENTER COAL WT FRACTION OF TRITON USED IN CWS: 0.02

ENTER CONSUMPTION (LB/SEC),TEMP(DEG F) OF CONSTITUENTS

CWS: 1.3226E-2,99.4

PILOT DIESEL: 1.6569E-3,99.1

PURGE OIL: 2.2775E-4,85

WT % OF COAL,PILOT DIESEL,PURGE OIL,TRITON & H2O IN FUEL

42.7 % 11.0 % 1.1 % 0.9 % 44.3 %

ENERGY % OF COAL,PILOT DIESEL,PURGE OIL,TRITON OF RUN

72.9 % 23.9 % 2.5 % 0.8 %

INJECTION PER STROKE OF CWS,PILOT DIESEL,PURGE OIL & TRITON

731 mm3/str 121 mm3/str 12 mm3/str 8 mm3/str

TOTAL ENERGY INP RATE: 494079 KJ/HR 458042 BTU/HR

± 20% PURGE OIL RETURNED TO FUEL TANK

HEAT RELEASE AND COMBUSTION ANALYSIS TR4774 L103

HEAT RELEASE CALCULATION FOR CWS TESTS

ENTER: LOG NO., FILE NO. OF PRESSURE DATA, & RPM OF RUN
 104,125,620
 ENTER THE MANIFOLD AIR PRESSURE (PSIA) & TEMPERATURE (DEG F)
 14.8,155.7
 ENTER TDC CORR.(+/- DEG), INJ ST(DEG BTDC) & INJ DURATION(DEG)
 -.4,15,12

ENTER COAL FRACTION & DENSITY OF CWS USED: 0.491,1.11
 ENTER "1" FOR UKON OR "2" FOR TRITON USED IN CWS: 2
 ENTER COAL WT FRACTION OF TRITON USED IN CWS: 0.02
 ENTER CONSUMPTION (LB/SEC),TEMP(DEG F) OF CONSTITUENTS
 CWS: 9.4862E-3,104
 PILOT DIESEL: 1.1997E-3,98
 PURGE OIL: 2.4233E-4,85
 WT % OF COAL,PILOT DIESEL,PURGE OIL,TRITON & H2O IN FUEL
 42.4 % 11.0 % 1.7 % 0.8 % 44.8 %
 ENERGY % OF COAL,PILOT DIESEL,PURGE OIL,TRITON OF RUN
 71.7 % 23.0 % 3.6 % 0.8 %
 INJECTION PER STROKE OF CWS,PILOT DIESEL,PURGE OIL & TRITON
 745 mm3/str 124 mm3/str 19 mm3/str 8 mm3/str
 TOTAL ENERGY INP RATE: 352186 KJ/HR 333826 BTU/HR
 ** 20% PURGE OIL RETURNED TO FUEL TANK

HEAT RELEASE AND COMBUSTION ANALYSIS TR4774 L104

HEAT RELEASE CALCULATION FOR CWS TESTS

ENTER: LOG NO., FILE NO. OF PRESSURE DATA, & RPM OF RUN

105.129,1053

ENTER THE MANIFOLD AIR PRESSURE (PSIA) & TEMPERATURE (DEG F)

44.2,187

ENTER TDC CORR.(+/- DEG), INJ ST(DEG BTDC) & INJ DURATION(DEG)

-.4,35,55

ENTER COAL FRACTION & DENSITY OF CWS USED: 0.495,1.11

ENTER "1" FOR UKON OR "2" FOR TRITON USED IN CWS: 2

ENTER COAL WT FRACTION OF TRITON USED IN CWS: 0.02

ENTER CONSUMPTION (LB/SEC),TEMP(DEG F) OF CONSTITUENTS

CWS: 5.8204E-2,90

PILOT DIESEL: 1.197E-3,96

PURGE OIL: 2.68E-4,85

WT % OF COAL,PILOT DIESEL,PURGE OIL,TRITON & H2O IN FUEL

47.9 % 2.0 % 0.3 % 1.0 % 48.8 %

ENERGY % OF COAL,PILOT DIESEL,PURGE OIL,TRITON OF RUN

93.1 % 5.0 % 0.8 % 1.0 %

INJECTION PER STROKE OF CWS,PILOT DIESEL,PURGE OIL & TRITON

2690 mm3/str

73 mm3/str

12 mm3/str

28 mm3/str

TOTAL ENERGY INP RATE: 1678176 KJ/HR 1590689 BTU/HR

** 20% PURGE OIL RETURNED TO FUEL TANK

HEAT RELEASE AND COMBUSTION ANALYSIS

4774 L105

HEAT RELEASE CALCULATION FOR CWS TESTS

ENTER: LOG NO., FILE NO. OF PRESSURE DATA, & RPM OF RUN
 106,133,1051
 ENTER THE MANIFOLD AIR PRESSURE (PSIA) & TEMPERATURE (DEG F)
 44,187
 ENTER TDC CORR.(+/- DEG), INJ ST(DEG BTDC) & INJ DURATION(DEG)
 -.4,35,54
 ENTER COAL FRACTION & DENSITY OF CWS USED: 0.495,1.11
 ENTER "1" FOR UKON OR "2" FOR TRITON USED IN CWS: 2
 ENTER COAL WT FRACTION OF TRITON USED IN CWS: 0.02
 ENTER CONSUMPTION (LB/SEC),TEMP(DEG F) OF CONSTITUENTS
 CWS: 5.7248E-2,95
 PILOT DIESEL: 1.5085E-3,99
 PURGE OIL: 2.323E-4,85
 WT % OF COAL,PILOT DIESEL,PURGE OIL,TRITON & H2O IN FUEL
 47.6 % 2.6 % 0.3 % 1.0 % 48.6 %
 ENERGY % OF COAL,PILOT DIESEL,PURGE OIL,TRITON OF RUN
 91.9 % 6.3 % 0.7 % 1.0 %
 INJECTION PER STROKE OF CWS,PILOT DIESEL,PURGE OIL & TRITON
 2650 mm3/str 92 mm3/str 11 mm3/str 28 mm3/str
 TOTAL ENERGY IHP RATE: 1672132 KJ/HR 1584959 BTU/HR
 ** 20% PURGE OIL RETURNED TO FUEL TANK

HEAT RELEASE AND COMBUSTION ANALYSIS 4774 L106

HEAT RELEASE CALCULATION FOR CWS TESTS

ENTER: LOG NO., FILE NO. OF PRESSURE DATA, & RPM OF RUH
 107,137,1052
 ENTER THE MANIFOLD AIR PRESSURE (PSIA) & TEMPERATURE (DEG F)
 43.9,197.5
 ENTER TDC CORR.(+/- DEG), INJ ST(DEG BTDC) & INJ DURATION(DEG)
 -.4,35,53

ENTER COAL FRACTION & DENSITY OF CWS USED: 0.494,1.11
 ENTER "1" FOR UKON OR "2" FOR TRITON USED IN CWS: 2
 ENTER COAL WT FRACTION OF TRITON USED IN CWS: 0.02
 ENTER CONSUMPTION (LB/SEC),TEMP(DEG F) OF CONSTITUENTS
 CWS: 5.7542E-2,90
 PILOT DIESEL: 1.2830E-3,94.7
 PURGE OIL: 1.9687E-4,95
 WT % OF COAL,PILOT DIESEL,PURGE OIL,TRITON & H2O IN FUEL
 47.7 % 2.2 % 0.3 % 1.0 % 48.9 %
 ENERGY % OF COAL,PILOT DIESEL,PURGE OIL,TRITON OF RUN
 92.9 % 5.4 % 0.6 % 1.0 %
 INJECTION PER STROKE OF CWS,PILOT DIESEL,PURGE OIL & TRITON
 2662 mm3/str 78 mm3/str 9 mm3/str 28 mm3/str
 TOTAL ENERGY IHP RATE: 1659359 KJ/HR 1572853 BTU/HR
 ** 20% PURGE OIL RETURNED TO FUEL TANK

HEAT RELEASE AND COMBUSTION ANALYSIS 4774 L107

HEAT RELEASE CALCULATION FOR CWS TESTS

ENTER: LOG NO., FILE NO. OF PRESSURE DATA, & RPM OF RUN

108,141,1051

ENTER THE MANIFOLD AIR PRESSURE (PSIA) & TEMPERATURE (DEG F)

44.1,187.3

ENTER TDC CORR.(+/- DEG), INJ ST(DEG BTDC) & INJ DURATION(DEG)

-.4,35,56

ENTER COAL FRACTION & DENSITY OF CWS USED: 0.494,1.11

ENTER "1" FOR UKON OR "2" FOR TRITON USED IN CWS: 2

ENTER COAL WT FRACTION OF TRITON USED IN CWS: 0.02

ENTER CONSUMPTION (LB/SEC),TEMP(DEG F) OF CONSTITUENTS

CWS: 5.9805E-2,91.9

PILOT DIESEL: 1.2604E-3,97.7

PURGE OIL: 2.1639E-4,85

WT % OF COAL,PILOT DIESEL,PURGE OIL,TRITON & H2O IN FUEL

47.8 % 2.1 % 0.3 % 1.0 % 48.9 %

ENERGY % OF COAL,PILOT DIESEL,PURGE OIL,TRITON OF RUN

93.2 % 5.1 % 0.7 % 1.0 %

INJECTION PER STROKE OF CWS,PILOT DIESEL,PURGE OIL & TRITON

2769 mm3/str 77 mm3/str 10 mm3/str 29 mm3/str

TOTAL ENERGY INP RATE: 1720127 KJ/HR 1630452 BTU/HR

** 20% PURGE OIL RETURNED TO FUEL TANK

HEAT RELEASE AND COMBUSTION ANALYSIS

4774 L108

HEAT RELEASE CALCULATION FOR CWS TESTS

ENTER: LOG NO., FILE NO. OF PRESSURE DATA, & RPM OF RUN
189,145,1850

ENTER THE MANIFOLD AIR PRESSURE (PSIA) & TEMPERATURE (DEG F)

44.1,187.3

ENTER TDC CORR.(+/- DEG), INJ ST(DEG BTDC) & INJ DURATION(DEG)

-.4,35.58

ENTER COAL FRACTION & DENSITY OF CWS USED: 0.494,1.11

ENTER "1" FOR UKON OR "2" FOR TRITON USED IN CWS: 2

ENTER COAL WT FRACTION OF TRITON USED IN CWS: 0.02

ENTER CONSUMPTION (LB/SEC),TEMP(DEG F) OF CONSTITUENTS

CWS: 6.1455E-2,94.7

PILOT DIESEL: 1.2318E-3,100

PURGE OIL: 3.0239E-4,85

WT % OF COAL,PILOT DIESEL,PURGE OIL,TRITON & H2O IN FUEL

47.8 % 2.0 % 0.4 % 1.0 % 48.9 %

ENERGY % OF COAL,PILOT DIESEL,PURGE OIL,TRITON OF RUN

93.2 % 4.9 % 0.9 % 1.0 %

INJECTION PER STROKE OF CWS,PILOT DIESEL,PURGE OIL & TRITON

2848 mm3/str 75 mm3/str 14 mm3/str 30 mm3/str

TOTAL ENERGY INP RATE: 1767350 KJ/HR 1675213 BTU/HR

** 20% PURGE OIL RETURNED TO FUEL TANK

HEAT RELEASE AND COMBUSTION ANALYSIS

4774 L109

HEAT RELEASE CALCULATION FOR CWS TESTS

ENTER: LOG NO., FILE NO. OF PRESSURE DATA, & RPM OF RUN
110,149,965

ENTER THE MANIFOLD AIR PRESSURE (PSIA) & TEMPERATURE (DEG F)
36.7,192

ENTER TDC CORR.(+/- DEG), INJ ST(DEG BTDC) & INJ DURATION(DEG)
-.4,22,47

ENTER COAL FRACTION & DENSITY OF CWS USED: 0.491,1.11

ENTER "1" FOR UKON OR "2" FOR TRITON USED IN CWS: 2

ENTER COAL WT FRACTION OF TRITON USED IN CWS: 0.02

ENTER CONSUMPTION (LB/SEC),TEMP(DEG F) OF CONSTITUENTS

CWS: 5.0236E-2,81.6

PILOT DIESEL: 9.1237E-4,89.7

PURGE OIL: 1.701E-4,85

WT % OF COAL,PILOT DIESEL,PURGE OIL,TRITON & H2O IN FUEL

47.6 % 1.8 % 0.2 % 1.0 % 49.4 %

ENERGY % OF COAL,PILOT DIESEL,PURGE OIL,TRITON OF RUN

93.8 % 4.5 % 0.6 % 1.1 %

INJECTION PER STROKE OF CWS,PILOT DIESEL,PURGE OIL & TRITON

2533 mm3/str 61 mm3/str 8 mm3/str 26 mm3/str

TOTAL ENERGY INP RATE: 1425865 KJ/HR 1351531 BTU/HR

** 20% PURGE OIL RETURNED TO FUEL TANK

HEAT RELEASE AND COMBUSTION ANALYSIS 4774 L110

HEAT RELEASE CALCULATION FOR CWS TESTS

ENTER: LOG NO., FILE NO. OF PRESSURE DATA, & RPM OF RUN
 111,153,964
 ENTER THE MANIFOLD AIR PRESSURE (PSIA) & TEMPERATURE (DEG F)
 29.2,182.4
 ENTER TDC CORR.(+/- DEG), INJ ST(DEG BTDC) & INJ DURATION(DEG)
 -.4,18,36

ENTER COAL FRACTION & DENSITY OF CWS USED: 0.491,1.11
 ENTER "1" FOR UKON OR "2" FOR TRITON USED IN CWS: 2
 ENTER COAL WT FRACTION OF TRITON USED IN CWS: 0.02
 ENTER CONSUMPTION (LB/SEC), TEMP(DEG F) OF CONSTITUENTS
 CWS: 3.853E-2,86.8
 PILOT DIESEL: 1.353E-3,94.8
 PURGE OIL: 2.44E-4,85
 WT % OF COAL,PILOT DIESEL,PURGE OIL,TRITON & H2O IN FUEL
 46.8 % 3.4 % 0.5 % 0.9 % 48.5 %
 ENERGY % OF COAL,PILOT DIESEL,PURGE OIL,TRITON OF RUN
 89.6 % 8.3 % 1.1 % 1.0 %
 INJECTION PER STROKE OF CWS,PILOT DIESEL,PURGE OIL & TRITON
 1945 mm3/str 90 mm3/str 12 mm3/str 20 mm3/str
 TOTAL ENERGY INP RATE: 1145252 KJ/HR 1085547 BTU/HR
 ** 20% PURGE OIL RETURNED TO FUEL TANK

HEAT RELEASE AND COMBUSTION ANALYSIS 4774 L111

HEAT RELEASE CALCULATION FOR CWS TESTS

ENTER: LOG NO., FILE NO. OF PRESSURE DATA, & RPM OF RUN
 112,157,965
 ENTER THE MANIFOLD AIR PRESSURE (PSIA) & TEMPERATURE (DEG F)
 22.7,171.6
 ENTER TDC CORR.(+/- DEG), INJ ST(DEG BTDC) & INJ DURATION(DEG)
 -.4,17,26

ENTER COAL FRACTION & DENSITY OF CWS USED: 0.491,1.11
 ENTER "1" FOR UKON OR "2" FOR TRITON USED IN CWS: 2
 ENTER COAL WT FRACTION OF TRITON USED IN CWS: 0.02
 ENTER CONSUMPTION (LB/SEC),TEMP(DEG F) OF CONSTITUENTS
 CWS: 2.8548E-2,90.5
 PILOT DIESEL: 1.3905E-3,97.5
 PURGE OIL: 2.45E-4,85
 WT % OF COAL,PILOT DIESEL,PURGE OIL,TRITON & H2O IN FUEL
 46.1 % 4.6 % 0.6 % 0.9 % 47.8 %
 ENERGY % OF COAL,PILOT DIESEL,PURGE OIL,TRITON OF RUN
 86.5 % 11.0 % 1.5 % 1.0 %
 INJECTION PER STROKE OF CWS,PILOT DIESEL,PURGE OIL & TRITON
 1445 mm3/str 92 mm3/str 12 mm3/str 15 mm3/str
 TOTAL ENERGY INP RATE: 881751 KJ/HR 835783 BTU/HR
 ** 20% PURGE OIL RETURNED TO FUEL TANK

HEAT RELEASE AND COMBUSTION ANALYSIS 4774 L112

HEAT RELEASE CALCULATION FOR CWS TESTS

ENTER: LOG NO., FILE NO. OF PRESSURE DATA, & RPM OF RUN

113,161,882

ENTER THE MANIFOLD AIR PRESSURE (PSIA) & TEMPERATURE (DEG F)

17,161

ENTER TDC CORR.(+/- DEG), INJ ST(DEG BTDC) & INJ DURATION(DEG)

-.4,16,18

ENTER COAL FRACTION & DENSITY OF CWS USED: 0.493,1.11

ENTER "1" FOR UKON OR "2" FOR TRITON USED IN CWS: 2

ENTER COAL WT FRACTION OF TRITON USED IN CWS: 0.02

ENTER CONSUMPTION (LB/SEC), TEMP(DEG F) OF CONSTITUENTS

CWS: 1.42E-2,86

PILOT DIESEL: 1.33E-3,86

PURGE OIL: 1.72E-4,85

WT % OF COAL,PILOT DIESEL,PURGE OIL,TRITON & H2O IN FUEL

44.3 % 8.5 % 0.8 % 0.9 % 45.5 %

ENERGY % OF COAL,PILOT DIESEL,PURGE OIL,TRITON OF RUN

78.1 % 19.1 % 1.9 % 0.9 %

INJECTION PER STROKE OF CWS,PILOT DIESEL,PURGE OIL & TRITON

783 mm3/str 97 mm3/str 9 mm3/str 8 mm3/str

TOTAL ENERGY INP RATE: 486869 KJ/HR 460729 BTU/HR

** 20% PURGE OIL RETURNED TO FUEL TANK

HEAT RELEASE AND COMBUSTION ANALYSIS

TR4774 L113

HEAT RELEASE CALCULATION FOR CWS TESTS

ENTER: LOG NO., FILE NO. OF PRESSURE DATA, & RPM OF RUN
 114,165,891
 ENTER THE MANIFOLD AIR PRESSURE (PSIA) & TEMPERATURE (DEG F)
 15.6,161
 ENTER TDC CORR.(+/- DEG), INJ ST(DEG BTDC) & INJ DURATION(DEG)
 -.4,16,19
 ENTER COAL FRACTION & DENSITY OF CWS USED: 0.493,1.11
 ENTER "1" FOR UKON OR "2" FOR TRITON USED IN CWS: 2
 ENTER COAL WT FRACTION OF TRITON USED IN CWS: 0.02
 ENTER CONSUMPTION (LB/SEC),TEMP(DEG F) OF CONSTITUENTS
 CWS: 1.27E-2,89
 PILOT DIESEL: 1.38E-3,94
 PURGE OIL: 1.9E-4,85
 WT % OF COAL,PILOT DIESEL,PURGE OIL,TRITON & H2O IN FUEL
 43.6 % 9.7 % 1.0 % 0.9 % 44.8 %
 ENERGY % OF COAL,PILOT DIESEL,PURGE OIL,TRITON OF RUN
 75.5 % 21.5 % 2.2 % 0.8 %
 INJECTION PER STROKE OF CWS,PILOT DIESEL,PURGE OIL & TRITON
 701 mm3/str 101 mm3/str 10 mm3/str 7 mm3/str
 TOTAL ENERGY INP RATE: 449944 KJ/HR 426487 BTU/HR
 ** 20% PURGE OIL RETURNED TO FUEL TANK

HEAT RELEASE AND COMBUSTION ANALYSIS 4774 L114

HEAT RELEASE CALCULATION FOR CWS TESTS

ENTER: LOG NO., FILE NO. OF PRESSURE DATA, & RPM OF RUN
115,169,621

ENTER THE MANIFOLD AIR PRESSURE (PSIA) & TEMPERATURE (DEG F)
14.7,153

ENTER TDC CORR. (+/- DEG), INJ ST (DEG BTDC) & INJ DURATION (DEG)
-.4,15,12

ENTER COAL FRACTION & DENSITY OF CWS USED: 0.493,1.11

ENTER "1" FOR UKON OR "2" FOR TRITON USED IN CWS: 2

ENTER COAL WT FRACTION OF TRITON USED IN CWS: 0.02

ENTER CONSUMPTION (LB/SEC), TEMP (DEG F) OF CONSTITUENTS

CWS: 8.02E-3,93

PILOT DIESEL: 1.1E-3,96

PURGE OIL: 1.8E-4,85

WT % OF COAL, PILOT DIESEL, PURGE OIL, TRITON & H2O IN FUEL

42.3 % 11.9 % 1.5 % 0.8 % 43.5 %

ENERGY % OF COAL, PILOT DIESEL, PURGE OIL, TRITON OF RUN

70.7 % 25.4 % 3.1 % 0.8 %

INJECTION PER STROKE OF CWS, PILOT DIESEL, PURGE OIL & TRITON

628 mm3/str 114 mm3/str 14 mm3/str 7 mm3/str

TOTAL ENERGY INP RATE: 303270 KJ/HR 287459 BTU/HR

** 20% PURGE OIL RETURNED TO FUEL TANK

HEAT RELEASE AND COMBUSTION ANALYSIS

4774 L115

INJ ST: 15.4 DEG BTDC IGN ST: 20.0 DEG BTDC IGN LAG: -4.6 DEG CA

HEAT RELEASE CALCULATION FOR CWS TESTS

ENTER: LOG NO., FILE NO. OF PRESSURE DATA, & RPM OF RUN
 116,173,1051
 ENTER THE MANIFOLD AIR PRESSURE (PSIA) & TEMPERATURE (DEG F)
 44,187
 ENTER TDC CORR.(+/- DEG), INJ ST(DEG BTDC) & INJ DURATION(DEG)
 -.4,40,58

ENTER COAL FRACTION & DENSITY OF CWS USED: 0.491,1.12
 ENTER "1" FOR UKON OR "2" FOR TRITON USED IN CWS: 2
 ENTER COAL WT FRACTION OF TRITON USED IN CWS: 0.02
 ENTER CONSUMPTION (LB/SEC),TEMP(DEG F) OF CONSTITUENTS
 CWS: 6.0318E-2,95.3
 PILOT DIESEL: 1.6503E-3,96.3
 PURGE OIL: 2.7164E-4,95
 WT % OF COAL,PILOT DIESEL,PURGE OIL,TRITON & H2O IN FUEL
 47.2 % 2.7 % 0.3 % 0.9 % 48.9 %
 ENERGY % OF COAL,PILOT DIESEL,PURGE OIL,TRITON OF RUN
 91.6 % 6.6 % 0.8 % 1.0 %
 INJECTION PER STROKE OF CWS,PILOT DIESEL,PURGE OIL & TRITON
 2768 mm3/str 101 mm3/str 12 mm3/str 29 mm3/str
 TOTAL ENERGY INP RATE: 1754366 KJ/HR 1662906 BTU/HR
 ** 20% PURGE OIL RETURNED TO FUEL TANK

HEAT RELEASE AND COMBUSTION ANALYSIS 4774 L116

HEAT RELEASE CALCULATION FOR CWS TESTS

ENTER: LOG NO., FILE NO. OF PRESSURE DATA, & RPM OF RUN
117,177,1052

ENTER THE MANIFOLD AIR PRESSURE (PSIA) & TEMPERATURE (DEG F)
44,187

ENTER TDC CORR.(+/- DEG), INJ ST(DEG BTDC) & INJ DURATION(DEG)
-.4,40,42

ENTER COAL FRACTION & DENSITY OF CWS USED: 0.495,1.12

ENTER "1" FOR UKON OR "2" FOR TRITON USED IN CWS: 2

ENTER COAL WT FRACTION OF TRITON USED IN CWS: 0.02

ENTER CONSUMPTION (LB/SEC),TEMP(DEG F) OF CONSTITUENTS

CWS: 5.6214E-2,95.3

PILOT DIESEL: 1.8404E-3,96.3

PURGE OIL: 1.9052E-4,95

WT % OF COAL,PILOT DIESEL,PURGE OIL,TRITON & H2O IN FUEL

47.3 % 3.2 % 0.2 % 0.9 % 48.3 %

ENERGY % OF COAL,PILOT DIESEL,PURGE OIL,TRITON OF RUN

90.7 % 7.7 % 0.6 % 1.0 %

INJECTION PER STROKE OF CWS,PILOT DIESEL,PURGE OIL & TRITON

2577 mm3/str 112 mm3/str 9 mm3/str 27 mm3/str

TOTAL ENERGY INP RATE: 1665077 KJ/HR 1578272 BTU/HR

** 20% PURGE OIL RETURNED TO FUEL TANK

HEAT RELEASE AND COMBUSTION ANALYSIS 4774 L117

HEAT RELEASE CALCULATION FOR CWS TESTS

ENTER: LOG NO., FILE NO. OF PRESSURE DATA, & RPM OF RUN
1.1.1098

ENTER THE MANIFOLD AIR PRESSURE (PSIA) & TEMPERATURE (DEG F)
44.137

ENTER TDC CORR. (+/- DEG), INJ ST (DEG BTDC) & INJ DURATION (DEG)
-0.4, 40, 42

ENTER COAL FRACTION & DENSITY OF CWS USED: 0.49, 1.1

ENTER "1" FOR UNKNOWN OR "2" FOR TRITON USED IN CWS: 2

ENTER COAL WT FRACTION OF TRITON USED IN CWS: 0.02

ENTER CONSUMPTION (G/SEC), TEMP (DEG F) OF CONSTITUENTS

CWS: 5.649E-2, 74.5

PILOT DIESEL: 1.70E-3, 92

PURGE OIL: 2E-4, 80

WT % OF COAL, PILOT DIESEL, PURGE OIL, TRITON & H₂O IN FUEL

48.9 % 3.1 % 0.7 % 0.9 % 46.2 %

ENERGY % OF COAL, PILOT DIESEL, PURGE OIL, TRITON OF FUEL

98.2 % 7.6 % 9.6 % 1.0 %

INJECTION PER STROKE OF CWS, PILOT DIESEL, PURGE OIL & TRITON

2027 mm³/str 197 mm³/str 9 mm³/str 27 mm³/str

TOTAL ENERGY INP RATE: 1054201 KJ/HR 1507963 BTU/HR

W 20% PURGE OIL RETURNED TO FUEL TANK

HEAT RELEASE AND COMBUSTION ANALYSIS

TR4955 L1

HEAT RELEASE CALCULATION FOR CWS TESTS

ENTER: LOG NO., FILE NO. OF PRESSURE DATA, & RPM OF RUN

2.5.1054

ENTER THE MANIFOLD AIR PRESSURE (PSIA) & TEMPERATURE (DEG F)

44.187

ENTER TDC CORP. (+/- DEG), INJ ST (DEG BTDC) & INJ DURATION (DEG)

-4.35, 42

ENTER COAL FRACTION & DENSITY OF CWS USED: 0.49, 1.1

ENTER "1" FOR UKON OR "2" FOR TRITON USED IN CWS: 2

ENTER COAL WT FRACTION OF TRITON USED IN CWS: 0.02

ENTER CONSUMPTION (LB/SEC), TEMP (DEG F) OF CONSTITUENTS

CWS: 9.53EE-2, 78

PILOT DIESEL: 1.8E-3, 82

PURGE OIL: 2E-4, 85

WT % OF COAL, PILOT DIESEL, PURGE OIL, TRITON & H2O IN FUEL

46.9 % 3.1 % 0.3 % 0.9 % 48.8 %

ENERGY % OF COAL, PILOT DIESEL, PURGE OIL, TRITON OF RUN

98.6 % 7.7 % 0.6 % 1.0 %

INJECTION PER STROKE OF CWS, PILOT DIESEL, PURGE OIL & TRITON

2579 mm3/str 110 mm3/str 9 mm3/str 26 mm3/str

TOTAL ENERGY INP RATE: 1624524 KJ/HR 1539934 BTU/HR

** 20% PURGE OIL RETURNED TO FUEL TANK

HEAT RELEASE AND COMBUSTION ANALYSIS TR4985 L2

AGENT WILLIAM C. ROBERTSON, JR. FOR THE STATE

INTER: LOS ANGELES TEL. NO. OF PERSONS BEING A PART OF PCH
1-2-1975

ENTER THE NAME OF THE PROCEDURE (PCIM) & TEMPERATURE (CELS) IN
4.167

ENTER THE CORR. S. DIST. AND OTHER DATA IN THE APPROPRIATE
COLUMNS

ENTER LOUL PRODUCTION & DENSITY OF THE GLEB: 0.49, 1.1
ENTER MAX. NO. OF SEEDS PER GLEB FOR SORTING USED IN CWS: 2

CONFIDENTIAL
ENTER "1" FOR DEON OR "2" FOR TRITON USED IN Q49: 2
ENTER Q49 MT TRACTION OF TRITON USED IN Q49: 0.02

ENTER CONSUMPTION, LB/SEC, TEMPERATURE OF CONSTITUENTS

Q46: 5.64-2.75

PILOT DIESEL: 1.775 3.73

FORM: OIL: 1.23E-4.85

BT % OF COMB. FUEL DETERM. FURGE OIL, TRITON & H2O IN FUEL

47.0 3 0.0 3 0.5 3 0.2 3 0.8 3

ENERGY OF COAL, FUEL OIL, TURBINE OIL, TITAN OF RUN

FILE NO. 100-368689-143-1-94

INJECTION PER GALLON OF CUB. PILOT DIESEL, PURCE OIL & TRITON

3627 mm3/str 10% mm3/str 6 mm3/str 27 mm3/str

TOTAL ENERGY IN PATS: 1648922 KJ/HR 1502959 BTU/HR

TOTAL ENERGY IN FUEL IS 100%
 AT 20% PURGE OF AIR RETURNED TO FUEL TANK

HEAT RELEASE AND COMBUSTION ANALYSIS

٤٣

HEAT RELEASE CALCULATION FOR CWS TESTS

ENTER: LOG NO., FILE NO. OF PRESSURE DATA, & RPM OF RUN
 4.17.1057
 ENTER THE MANIFOLD AIR PRESSURE (PSIA) & TEMPERATURE (DEG F)
 44.187
 ENTER TDC CORR. (+ - DEGR), INJ ST(DEG BTDC) & INJ DURATION(DEG)
 -.4,40.40

ENTER COAL FRACTION & DENSITY OF CWS USED: 0.49,1.1
 ENTER "1" FOR DEON OR "2" FOR TRITON USED IN CWS: 2
 ENTER COAL WT FRACTION OF TRITON USED IN CWS: 0.02
 ENTER CONSUMPTION (LBS/SEC),TEMP(DEG F) OF CONSTITUENTS

CWS: 5.7E-3,72

PILOT DIESEL: 1.7E-3,80

PURGE OIL: 1.2E-4,85

AS % OF COAL,PILOT DIESEL,PURGE OIL,TRITON & H2O IN FUEL
 47.8 % 2.0 % 0.2 % 0.3 % 49.6 %

ENERGY % OF COAL,PILOT DIESEL,PURGE OIL,TRITON OF RUN
 51.4 % 7.2 % 0.4 % 1.0 %

INJECTION PER STROKE OF CWS,PILOT DIESEL,PURGE OIL & TRITON
 2648 mm3/stk 193 mm3/stk 6 mm3/stk 27 mm3/stk

TOTAL ENERGY IMP INTAKE: 1007444 KJ/HR 1571511 BTU/HR
 * 26% PURGE OIL RETURNED TO FUEL TANK

HEAT RELEASE AND COMBUSTION ANALYSIS L 4

HEAT RELEASE CALCULATION FOR CWS TESTS

ENTER: LOG NO., FILE NO. OF PRESSURE DATA, & RPM OF RUN

3.17.1055

ENTER THE MANIFOLD AIR PRESSURE (PSIA) & TEMPERATURE (DEG F)

44.187

ENTER TDC CORR. (+/- DEG), INJ ST (DEG BTDC) & INJ DURATION (DEG)

-1.4, 30.41

ENTER COAL FRACTION & DENSITY OF CWS USED: 0.49, 1.1

ENTER "1" FOR UKON OR "2" FOR TRITON USED IN CWS: 2

ENTER COAL WT FRACTION OF TRITON USED IN CWS: 0.02

ENTER CONSUMPTION (LB/SEC), TEMP (DEG F) OF CONSTITUENTS

CWS: 5.42E-3, 75

PILOT DIESEL: 2.04E-3, 85

PURGE OIL: 9E-5, 95

WT % OF COAL, PILOT DIESEL, PURGE OIL, TRITON & H2O IN FUEL

46.7 % 3.6 % 0.1 % 0.9 % 48.6 %

ENERGY % OF COAL, PILOT DIESEL, PURGE OIL, TRITON OF RUN

89.8 % 9.8 % 0.3 % 1.0 %

INJECTION PER STROKE OF CWS, PILOT DIESEL, PURGE OIL & TRITON

2523 mm3/stk 124 mm3/stk 4 mm3/stk 26 mm3/stk

TOTAL ENERGY INP RATE: 1004350 KJ/HR 1520710 BTU/HR

% 20% PURGE OIL RETURNED TO FUEL TANK

HEAT RELEASE AND COMBUSTION ANALYSIS

L5

HEAT RELEASE CALCULATION FOR CWS TESTS

ENTER: LOG NO., FILE NO. OF PRESSURE DATA, & RPM OF RUN

6.21.1057

ENTER THE MANIFOLD AIR PRESSURE (PSIA) & TEMPERATURE (DEG F)

44.187

ENTER TDC CORR. (+/- DEG), INJ ST (DEG BTDC) & INJ DURATION (DEG)

-4.35.45

ENTER COAL FRACTION & DENSITY OF CWS USED: 0.49, 1.1

ENTER "1" FOR UKON OR "2" FOR TRITON USED IN CWS: 2

ENTER COAL WT FRACTION OF TRITON USED IN CWS: 0.02

ENTER CONSUMPTION (LB/SEC), TEMP (DEG F) OF CONSTITUENTS

CWS: 5.48E-2.82

PILOT DIESEL: 1.44E-3.81

PURGE OIL: 1.5E-4.85

WT % OF COAL, PILOT DIESEL, PURGE OIL, TRITON & H2O IN FUEL

47.2 % 2.6 % 0.2 % 0.9 % 49.1 %

ENERGY % OF COAL, PILOT DIESEL, PURGE OIL, TRITON OF RUN

92.1 % 6.4 % 0.5 % 1.0 %

INJECTION PER STROKE OF CWS, PILOT DIESEL, PURGE OIL & TRITON

2546 mm3/str 87 mm3/str 7 mm3/str 26 mm3/str

TOTAL ENERGY IHP RATE: 1581670 KJ/HR 1499213 BTU/HR

* 20% PURGE OIL RETURNED TO FUEL TANK

HEAT RELEASE AND COMBUSTION ANALYSIS L5

HEAT RELEASE CALCULATION FOR CWS TESTS

ENTER: LOG NO., FILE NO. OF PRESSURE DATA, & RPM OF RUN

8.29,1057

ENTER THE MANIFOLD AIR PRESSURE (PSIA) & TEMPERATURE (DEG F)

44,187

ENTER TDC CORR. (+/- DEG), INJ ST(DEG BTDC) & INJ DURATION(DEG)

-.4,30,45

ENTER COAL FRACTION & DENSITY OF CWS USED: 0.49,1.1

ENTER "1" FOR UKON OR "2" FOR TRITON USED IN CWS: 2

ENTER COAL WT FRACTION OF TRITON USED IN CWS: 0.02

ENTER CONSUMPTION (LB/SEC), TEMP(DEG F) OF CONSTITUENTS

CWS: 5.779E-2,74

PILOT DIESEL: 1.565E-3,75

PURGE OIL: 1.275E-4,85

WT % OF COAL, PILOT DIESEL, PURGE OIL, TRITON & H2O IN FUEL

47.2 % 2.6 % 0.2 % 0.9 % 49.1 %

ENERGY % OF COAL, PILOT DIESEL, PURGE OIL, TRITON OF RUN

92.0 % 6.6 % 0.4 % 1.0 %

INJECTION PER STROKE OF CWS, PILOT DIESEL, PURGE OIL & TRITON

2695 mm3/str 95 mm3/str 6 mm3/str 28 mm3/str

TOTAL ENERGY INP RATE: 1669607 KJ/HR 1582566 BTU/HR

** 20% PURGE OIL RETURNED TO FUEL TANK

HEAT RELEASE AND COMBUSTION ANALYSIS 4855 LB

HEAT RELEASE CALCULATION FOR CWS TESTS

ENTER: LOG NO., FILE NO. OF PRESSURE DATA, & RPM OF RUN

9.33,1055

ENTER THE MANIFOLD AIR PRESSURE (PSIA) & TEMPERATURE (DEG F)

44,197

ENTER TDC CORR.(+/- DEG), INJ ST(DEG BTDC) & INJ DURATION(DEG)

-.4,30,45

ENTER COAL FRACTION & DENSITY OF CWS USED: 0.49,1.1

ENTER "1" FOR UKON OR "2" FOR TRITON USED IN CWS: 2

ENTER COAL WT FRACTION OF TRITON USED IN CWS: 0.02

ENTER CONSUMPTION (LB/SEC),TEMP(DEG F) OF CONSTITUENTS

CWS: 5.821E-2,78

PILOT DIESEL: 1.567E-3,79

PURGE OIL: 1.07E-4,95

WT % OF COAL,PILOT DIESEL,PURGE OIL,TRITON & H2O IN FUEL

47.2 % 2.6 % 0.1 % 0.9 % 49.1 %

ENERGY % OF COAL,PILOT DIESEL,PURGE OIL,TRITON OF RUN

92.1 % 6.5 % 0.3 % 1.0 %

INJECTION PER STROKE OF CWS,PILOT DIESEL,PURGE OIL & TRITON

2709 mm3/str 95 mm3/str 5 mm3/str 28 mm3/str

TOTAL ENERGY INP RATE: 1679961 KJ/HR 1592381 BTU/HR

** 20% PURGE OIL RETURNED TO FUEL TANK

HEAT RELEASE AND COMBUSTION ANALYSIS

4855 L9

HEAT RELEASE CALCULATION FOR CWS TESTS

ENTER: LOG NO., FILE NO. OF PRESSURE DATA, & RPM OF RUN

17,57,1050

ENTER THE MANIFOLD AIR PRESSURE (PSIA) & TEMPERATURE (DEG F)

44,197

ENTER TDC CORR. (+/- DEG), INJ ST(DEG BTDC) & INJ DURATION(DEG)

0.40,44

ENTER COAL FRACTION & DENSITY OF CWS USED: 0.49,1.1

ENTER "1" FOR UKON DR "2" FOR TRITON USED IN CWS: 2

ENTER COAL WT FRACTION OF TRITON USED IN CWS: 0.02

ENTER CONSUMPTION (LB/SEC), TEMP(DEG F) OF CONSTITUENTS

CWS: 5.96E-2,90

PILOT DIESEL: 1.51E-3,76

PURGE OIL: 1.22E-4,85

WT % OF COAL, PILOT DIESEL, PURGE OIL, TRITON & H2O IN FUEL

47.3 % 2.5 % 0.1 % 0.9 % 49.2 %

ENERGY % OF COAL, PILOT DIESEL, PURGE OIL, TRITON OF RUN

92.4 % 6.2 % 0.4 % 1.0 %

INJECTION PER STROKE OF CWS, PILOT DIESEL, PURGE OIL & TRITON

2787 mm3/str 92 mm3/str 6 mm3/str 29 mm3/str

TOTAL ENERGY INP RATE: 1714127 KJ/HR 1624764 BTU/HR

** 20% PURGE OIL RETURNED TO FUEL TANK

HEAT RELEASE AND COMBUSTION ANALYSIS

4855 L17

HEAT RELEASE CALCULATION FOR CWS TESTS

ENTER: LOG NO., FILE NO. OF PRESSURE DATA, & RPM OF RUN

16,61,1057

ENTER THE MANIFOLD AIR PRESSURE (PSIA) & TEMPERATURE (DEG F)

44,187

ENTER TDC CORR. (+/- DEG), INJ ST (DEG BTDC) & INJ DURATION (DEG)

0,35,44

ENTER COAL FRACTION & DENSITY OF CWS USED: 0.49,1.1

ENTER "1" FOR UKON OR "2" FOR TRITON USED IN CWS: 2

ENTER COAL WT FRACTION OF TRITON USED IN CWS: 0.02

ENTER CONSUMPTION (LB/SEC), TEMP (DEG F) OF CONSTITUENTS

CWS: 5.74E-2,83

PILOT DIESEL: 1.57E-3,79

PURGE OIL: 1.53E-4,85

WT % OF COAL, PILOT DIESEL, PURGE OIL, TRITON & H2O IN FUEL

47.1 % 2.7 % 0.2 % 0.9 % 49.1 %

ENERGY % OF COAL, PILOT DIESEL, PURGE OIL, TRITON OF RUN

91.9 % 6.6 % 0.5 % 1.0 %

INJECTION PER STROKE OF CWS, PILOT DIESEL, PURGE OIL & TRITON

2667 mm3/str 95 mm3/str 7 mm3/str 27 mm3/str

TOTAL ENERGY IHP RATE: 1660810 KJ/HR 1574228 BTU/HR

** 20% PURGE OIL RETURNED TO FUEL TANK

HEAT RELEASE AND COMBUSTION ANALYSIS

TR 4855 L19

HEAT RELEASE CALCULATION FOR CWS TESTS

ENTER: LOG NO., FILE NO. OF PRESSURE DATA, & RPM OF RUN
19,85,1056

ENTER THE MANIFOLD AIR PRESSURE (PSIA) & TEMPERATURE (DEG F)
44,187

ENTER TDC CORR. (+/- DEG), INJ ST (DEG BTDC) & INJ DURATION (DEG)
0,30,43

ENTER COAL FRACTION & DENSITY OF CWS USED: 0.49,1.1

ENTER "1" FOR UKON OR "2" FOR TRITON USED IN CWS: 2

ENTER COAL WT FRACTION OF TRITON USED IN CWS: 0.02

ENTER CONSUMPTION (LB/SEC), TEMP (DEG F) OF CONSTITUENTS

CWS: 5.739E-2,73

PILOT DIESEL: 1.6E-3,80

PURGE OIL: 1.33E-4,85

WT % OF COAL, PILOT DIESEL, PURGE OIL, TRITON & H2O IN FUEL

47.1 % 2.7 % 0.2 % 0.9 % 49.1 %

ENERGY % OF COAL, PILOT DIESEL, PURGE OIL, TRITON OF RUN

91.8 % 6.7 % 0.4 % 1.0 %

INJECTION PER STROKE OF CWS, PILOT DIESEL, PURGE OIL & TRITON

2669 mm3/str 97 mm3/str 6 mm3/str 27 mm3/str

TOTAL ENERGY INP RATE: 1661591 KJ/HR 1574968 BTU/HR

** 20% PURGE OIL RETURNED TO FUEL TANK

HEAT RELEASE AND COMBUSTION ANALYSIS TR 4855 L19

HEAT RELEASE CALCULATION FOR CWS TESTS

ENTER: LOG NO., FILE NO. OF PRESSURE DATA, & RPM OF RUN

20,65,1050

ENTER THE MANIFOLD AIR PRESSURE (PSIA) & TEMPERATURE (DEG F)

44,187

ENTER TDC CORR.(+/- DEG), INJ ST(DEG BTDC) & INJ DURATION(DEG)

0,25,47

ENTER COAL FRACTION & DENSITY OF CWS USED: 0.49,1.1

ENTER "1" FOR UKON OR "2" FOR TRITON USED IN CWS: 2

ENTER COAL WT FRACTION OF TRITON USED IN CWS: 0.02

ENTER CONSUMPTION (LB/SEC),TEMP(DEG F) OF CONSTITUENTS

CWS: 5.8436E-2.75

PILOT DIESEL: 1.43E-3.80

PURGE OIL: 1.4E-4.85

WT % OF COAL,PILOT DIESEL,PURGE OIL,TRITON & H2O IN FUEL

47.3 % 2.4 % 0.2 % 0.9 % 49.2 %

ENERGY % OF COAL,PILOT DIESEL,PURGE OIL,TRITON OF RUN

92.6 % 6.0 % 0.4 % 1.0 %

INJECTION PER STROKE OF CWS,PILOT DIESEL,PURGE OIL & TRITON

2733 mm3/str 87 mm3/str 6 mm3/str 28 mm3/str

TOTAL ENERGY IHP RATE: 1679186 KJ/HR 1590697 BTU/HR

** 20% PURGE OIL RETURNED TO FUEL TANK

HEAT RELEASE AND COMBUSTION ANALYSIS

TR4855 L20

RUN HEAT RELEASE CALCULATION FOR CWS TESTS

ENTER: LOG NO., FILE NO. OF PRESSURE DATA, & RPM OF RUN
21,69,1054

ENTER THE MANIFOLD AIR PRESSURE (PSIA) & TEMPERATURE (DEG F)
44,137

ENTER TDC CORR. (+/- DEG), INJ ST(DEG BTDC) & INJ DURATION(DEG)
0,30,48

ENTER COAL FRACTION & DENSITY OF CWS USED: 0.49,4110

ENTER "1" FOR UKON OR "2" FOR TRITON USED IN CWS: 2

ENTER COAL WT FRACTION OF TRITON USED IN CWS: 0.02

ENTER CONSUMPTION (LB/SEC), TEMP(DEG F) OF CONSTITUENTS

CWS: 5.72E-2,78

PILOT DIESEL: 1.44E-3,83

PURGE OIL: 1.46E-4,85

WT % OF COAL, PILOT DIESEL, PURGE OIL, TRITON & H2O IN FUEL

47.2 % 2.5 % 0.2 % 0.9 % 49.2 %

ENERGY % OF COAL, PILOT DIESEL, PURGE OIL, TRITON OF RUN

92.4 % 6.1 % 0.5 % 1.0 %

INJECTION PER STROKE OF CWS, PILOT DIESEL, PURGE OIL & TRITON

2665 mm3/str 89 mm3/str 7 mm3/str 27 mm3/str

TOTAL ENERGY INP RATE: 1645975 KJ/HR 1560166 BTU/HR

** 20% PURGE OIL RETURNED TO FUEL TANK

HEAT RELEASE AND COMBUSTION ANALYSIS TR4855 L21

HEAT RELEASE CALCULATION FOR CWS TESTS

ENTER: LOG NO., FILE NO. OF PRESSURE DATA, & RPM OF RUN
22,73,1054

ENTER THE MANIFOLD AIR PRESSURE (PSIA) & TEMPERATURE (DEG F)
44,187

ENTER TDC CORR. (+/- DEG), INJ ST (DEG BTDC) & INJ DURATION (DEG)
0,35,46

ENTER COAL FRACTION & DENSITY OF CWS USED: 0.49,1.1

ENTER "1" FOR UKON OR "2" FOR TRITON USED IN CWS: 2

ENTER COAL WT FRACTION OF TRITON USED IN CWS: 0.02

ENTER CONSUMPTION (LB/SEC), TEMP (DEG F) OF CONSTITUENTS

CWS: 5.62E-2,78

PILOT DIESEL: 1.42E-3,87

PURGE OIL: 1.46E-4,85

WT % OF COAL, PILOT DIESEL, PURGE OIL, TRITON & H2O IN FUEL

47.2 % 2.5 % 0.2 % 0.9 % 49.2 %

ENERGY % OF COAL, PILOT DIESEL, PURGE OIL, TRITON OF RUN

92.4 % 6.1 % 0.5 % 1.0 %

INJECTION PER STROKE OF CWS, PILOT DIESEL, PURGE OIL & TRITON

2618 mm3/str 86 mm3/str 7 mm3/str 27 mm3/str

TOTAL ENERGY INP RATE: 1617695 KJ/HR 1533360 BTU/HR

** 20% PURGE OIL RETURNED TO FUEL TANK

HEAT RELEASE AND COMBUSTION ANALYSIS TR4855 L22

INJ ST: 35.0 DEG BTDC IGN ST: 24.5 DEG BTDC 189 IGN LAG: 10.5 DEG CA

HEAT RELEASE CALCULATION FOR CWS TESTS

ENTER: LOG NO., FILE NO. OF PRESSURE DATA, & RPM OF RUN

23,77,1057

ENTER THE MANIFOLD AIR PRESSURE (PSIA) & TEMPERATURE (DEG F)

44.187

ENTER TDC CORR. (+/- DEG), INJ ST (DEG BTDC) & INJ DURATION (DEG)

0.48, 43

ENTER COAL FRACTION & DENSITY OF CWS USED: 0.49, 1.1

ENTER "1" FOR UKON OR "2" FOR TRITON USED IN CWS: 2

ENTER COAL WT FRACTION OF TRITON USED IN CWS: 0.02

ENTER CONSUMPTION (LB/SEC), TEMP (DEG F) OF CONSTITUENTS

CWS: 5.8E-2, 67

PILOT DIESEL: 1.32E-3, 76

PURGE OIL: 9.7E-5, 85

WT % OF COAL, PILOT DIESEL, PURGE OIL, TRITON & H2O IN FUEL

47.4 % 2.2 % 0.1 % 0.9 % 49.3 %

ENERGY % OF COAL, PILOT DIESEL, PURGE OIL, TRITON OF RUN

93.1 % 5.6 % 0.3 % 1.0 %

INJECTION PER STROKE OF CWS, PILOT DIESEL, PURGE OIL & TRITON

2695 mm3/str 80 mm3/str 4 mm3/str 28 mm3/str

TOTAL ENERGY IHP RATE: 1655992 KJ/HR 1569661 BTU/HR

** 20% PURGE OIL RETURNED TO FUEL TANK

HEAT RELEASE AND COMBUSTION ANALYSIS

TR 4855 L23

AIM

Association for Information and Image Management

1100 Wayne Avenue, Suite 1100
Silver Spring, Maryland 20910

301/587-8202

Centimeter

Inches

MANUFACTURED TO AIM STANDARDS
BY APPLIED IMAGE, INC.

3 of 3

HEAT RELEASE CALCULATION FOR CWS TESTS

ENTER: LOG NO., FILE NO. OF PRESSURE DATA, & RPM OF RUN

24,81,1058

ENTER THE MANIFOLD AIR PRESSURE (PSIA) & TEMPERATURE (DEG F)

44,187

ENTER TDC CORR.(+/- DEG), INJ ST(DEG BTDC) & INJ DURATION(DEG)

0.45,44

ENTER COAL FRACTION & DENSITY OF CWS USED: 0.49,1.1

ENTER "1" FOR UKON OR "2" FOR TRITON USED IN CWS: 2

ENTER COAL WT FRACTION OF TRITON USED IN CWS: 0.02

ENTER CONSUMPTION (LB/SEC),TEMP(DEG F) OF CONSTITUENTS

CWS: 5.88E-2,71

PILOT DIESEL: 1.53E-3,81

PURGE OIL: 8.2E-5,85

WT % OF COAL,PILOT DIESEL,PURGE OIL,TRITON & H2O IN FUEL

47.2 % 2.5 % 0.1 % 0.9 % 49.2 %

ENERGY % OF COAL,PILOT DIESEL,PURGE OIL,TRITON OF RUN

92.4 % 6.3 % 0.3 % 1.0 %

INJECTION PER STROKE OF CWS,PILOT DIESEL,PURGE OIL & TRITON

2729 mm3/str 93 mm3/str 4 mm3/str 28 mm3/str

TOTAL ENERGY INP RATE: 1691922 KJ/HR 1603718 BTU/HR

** 20% PURGE OIL RETURNED TO FUEL TANK

HEAT RELEASE AND COMBUSTION ANALYSIS TR4955 L24

HEAT RELEASE CALCULATION FOR CWS TESTS

ENTER: LOG NO., FILE NO. OF PRESSURE DATA, & RPM OF RUN
25,89,625

ENTER THE MANIFOLD AIR PRESSURE (PSIA) & TEMPERATURE (DEG F)
15,151

ENTER TDC CORR. (+/- DEG), INJ ST (DEG BTDC) & INJ DURATION (DEG)
0,19,13

ENTER COAL FRACTION & DENSITY OF CWS USED: 0.49,1.1

ENTER "1" FOR UKON OR "2" FOR TRITON USED IN CWS: 2

ENTER COAL HT FRACTION OF TRITON USED IN CWS: 0.02

ENTER CONSUMPTION (LB/SEC), TEMP (DEG F) OF CONSTITUENTS

CWS: 7.81E-3,76

PILOT DIESEL: 1.41E-3,75

PURGE OIL: 6E-5,95

WT % OF COAL, PILOT DIESEL, PURGE OIL, TRITON & H2O IN FUEL

40.9 % 15.2 % 0.5 % 0.8 % 42.6 %

ENERGY % OF COAL, PILOT DIESEL, PURGE OIL, TRITON OF RUN

66.6 % 31.6 % 1.0 % 0.7 %

INJECTION PER STROKE OF CWS, PILOT DIESEL, PURGE OIL & TRITON

614 mm3/str 145 mm3/str 5 mm3/str 6 mm3/str

TOTAL ENERGY INP RATE: 311704 KJ/HR 295454 BTU/HR

** 20% PURGE OIL RETURNED TO FUEL TANK

HEAT RELEASE AND COMBUSTION ANALYSIS 4855 L25

HEAT RELEASE CALCULATION FOR CWS TESTS

ENTER: LOG NO., FILE NO. OF PRESSURE DATA, & RPM OF RUN

26.93.886

ENTER THE MANIFOLD AIR PRESSURE (PSIA) & TEMPERATURE (DEG F)

16.164

ENTER TDC CORR. (+/- DEG), INJ ST(DEG BTDC) & INJ DURATION(DEG)

0.19.18

ENTER COAL FRACTION & DENSITY OF CWS USED: 0.49.1.1

ENTER "1" FOR UKON OR "2" FOR TRITON USED IN CWS: 2

ENTER COAL WT FRACTION OF TRITON USED IN CWS: 0.02

ENTER CONSUMPTION (LB/SEC), TEMP(DEG F) OF CONSTITUENTS

CWS: 1.214E-2, 78

PILOT DIESEL: 1.92E-3, 76

PURGE OIL: 8.4E-5, 85

WT % OF COAL, PILOT DIESEL, PURGE OIL, TRITON & H2O IN FUEL

41.7 % 13.6 % 0.4 % 0.8 % 43.4 %

ENERGY % OF COAL, PILOT DIESEL, PURGE OIL, TRITON OF RUN

69.4 % 28.9 % 0.9 % 0.8 %

INJECTION PER STROKE OF CWS, PILOT DIESEL, PURGE OIL & TRITON

673 mm3/str 139 mm3/str 5 mm3/str 7 mm3/str

TOTAL ENERGY INP RATE: 465028 KJ/HR 440785 BTU/HR

** 20% PURGE OIL RETURNED TO FUEL TANK

HEAT RELEASE AND COMBUSTION ANALYSIS

4855 L26

INJ ST: 19.0 DEG BTDC IGN ST: 24.8 DEG BTDC IGN LAG: -5.8 DEG CA

HEAT RELEASE CALCULATION FOR CWS TESTS

ENTER: LOG NO., FILE NO. OF PRESSURE DATA, & RPM OF RUN

27,97,887

ENTER THE MANIFOLD AIR PRESSURE (PSIA) & TEMPERATURE (DEG F)

17.162

ENTER TDC CORR. (+/- DEG), INJ ST (DEG BTDC) & INJ DURATION (DEG)

0.19, 20

ENTER COAL FRACTION & DENSITY OF CWS USED: 0.49, 1.1

ENTER "1" FOR UKON OR "2" FOR TRITON USED IN CWS: 2

ENTER COAL WT FRACTION OF TRITON USED IN CWS: 0.02

ENTER CONSUMPTION (LB/SEC), TEMP (DEG F) OF CONSTITUENTS

CWS: 1.45E-2, 79

PILOT DIESEL: 1.75E-3, 77

PURGE OIL: 1.36E-4, 85

WT % OF COAL, PILOT DIESEL, PURGE OIL, TRITON & H2O IN FUEL

43.0 % 10.7 % 0.6 % 0.9 % 44.8 %

ENERGY % OF COAL, PILOT DIESEL, PURGE OIL, TRITON OF RUN

74.2 % 23.6 % 1.4 % 0.8 %

INJECTION PER STROKE OF CWS, PILOT DIESEL, PURGE OIL & TRITON

803 mm3/stk 127 mm3/stk 7 mm3/stk 8 mm3/stk

TOTAL ENERGY IHP RATE: 519306 KJ/HR 492233 BTU/HR

** 20% PURGE OIL RETURNED TO FUEL TANK

HEAT RELEASE AND COMBUSTION ANALYSIS

4855 L27

INJ ST: 19.0 DEG BTDC IGN ST: 24.5 DEG BTDC IGN LAG: -5.5 DEG CA

HEAT RELEASE CALCULATION FOR CWS TESTS

ENTER: LOG NO., FILE NO. OF PRESSURE DATA, & RPM OF RUN

28,101,971

ENTER THE MANIFOLD AIR PRESSURE (PSIA) & TEMPERATURE (DEG F)

22.5,172

ENTER TDC CORR. (+/- DEG), INJ ST (DEG BTDC) & INJ DURATION (DEG)

0,10,29

ENTER COAL FRACTION & DENSITY OF CWS USED: 0.49,1.1

ENTER "1" FOR UKON OR "2" FOR TRITON USED IN CWS: 2

ENTER COAL WT FRACTION OF TRITON USED IN CWS: 0.02

ENTER CONSUMPTION (LB/SEC), TEMP (DEG F) OF CONSTITUENTS

CWS: 2.9E-2,80

PILOT DIESEL: 1.95E-3,77

PURGE OIL: 1.39E-4,85

WT % OF COAL, PILOT DIESEL, PURGE OIL, TRITON & H2O IN FUEL

45.5 % 6.0 % 0.3 % 0.9 % 47.3 %

ENERGY % OF COAL, PILOT DIESEL, PURGE OIL, TRITON OF RUN

84.1 % 14.1 % 0.8 % 0.9 %

INJECTION PER STROKE OF CWS, PILOT DIESEL, PURGE OIL & TRITON

1467 mm3/str 122 mm3/str 7 mm3/str 15 mm3/str

TOTAL ENERGY INP RATE: 916234 KJ/HR 868468 BTU/HR

** 20% PURGE OIL RETURNED TO FUEL TANK

HEAT RELEASE AND COMBUSTION ANALYSIS

4855 L20

INJ ST: 19.0 DEG BTDC IGN ST: 24.0 DEG BTDC IGN LAG: -5.0 DEG CA

HEAT RELEASE CALCULATION FOR CWS TESTS

ENTER: LOG NO., FILE NO. OF PRESSURE DATA, & RPM OF RUN

25.185.971

ENTER THE MANIFOLD AIR PRESSURE (PSIA) & TEMPERATURE (DEG F)

29.184

ENTER TDC CORR. (+/- DEG), INJ ST (DEG BTDC) & INJ DURATION (DEG)

0.28, 38

ENTER COAL FRACTION & DENSITY OF CWS USED: 0.49, 1.1

ENTER "1" FOR UKOH OR "2" FOR TRITON USED IN CWS: 2

ENTER COAL WT FRACTION OF TRITON USED IN CWS: 0.02

ENTER CONSUMPTION (LB/SEC), TEMP (DEG F) OF CONSTITUENTS

CWS: 2.9E-2, 81

PILOT DIESEL: 1.7E-3, 79

PURGE OIL: 1.55E-4, 85

WT % OF COAL, PILOT DIESEL, PURGE OIL, TRITON & H2O IN FUEL

46.4 % 4.2 % 0.3 % 0.9 % 48.3 %

ENERGY % OF COAL, PILOT DIESEL, PURGE OIL, TRITON OF RUN

88.2 % 10.1 % 0.7 % 1.0 %

INJECTION PER STROKE OF CWS, PILOT DIESEL, PURGE OIL & TRITON

1972 mm3/str 112 mm3/str 8 mm3/str 20 mm3/str

TOTAL ENERGY INP RATE: 1175394 KJ/HR 1114117 BTU/HR

20% PURGE OIL RETURNED TO FUEL TANK

HEAT RELEASE AND COMBUSTION ANALYSIS

4855 L29

HEAT RELEASE CALCULATION FOR CWS TESTS

ENTER: LOG NO., FILE NO. OF PRESSURE DATA, & RPM OF RUN

30,109,971

ENTER THE MANIFOLD AIR PRESSURE (PSIA) & TEMPERATURE (DEG F)

36.5,183

ENTER TDC CORR.(+/- DEG), INJ ST(DEG BTDC) & INJ DURATION(DEG)

0,24,44

ENTER COAL FRACTION & DENSITY OF CWS USED: 0.49,1.1

ENTER "1" FOR UKOH OR "2" FOR TRITON USED IN CWS: 2

ENTER COAL WT FRACTION OF TRITON USED IN CWS: 0.02

ENTER CONSUMPTION (LB/SEC),TEMP(DEG F) OF CONSTITUENTS

CWS: 4.87E-2,83

PILOT DIESEL: 1.53E-3,81

PURGE OIL: 1.43E-4,85

WT % OF COAL,PILOT DIESEL,PURGE OIL,TRITON & H2O IN FUEL

46.9 % 3.0 % 0.2 % 0.9 % 48.9 %

ENERGY % OF COAL,PILOT DIESEL,PURGE OIL,TRITON OF RUN

90.9 % 7.5 % 0.5 % 1.0 %

INJECTION PER STROKE OF CWS,PILOT DIESEL,PURGE OIL & TRITON

2463 mm3/str 101 mm3/str 7 mm3/str 25 mm3/str

TOTAL ENERGY INP RATE: 1423622 KJ/HR 1349405 BTU/HR

** 20% PURGE OIL RETURNED TO FUEL TANK

HEAT RELEASE AND COMBUSTION ANALYSIS

4855 L30

INJ ST: 24.0 DEG BTDC

IGN ST: 24.7 DEG BTDC

IGN LAG: -0.7 DEG CA

**DATE
FILMED**

8 / 31 / 93

END