AIM

Association for Information and Image Management

1100 Wayne Avenue, Suite 1100
Silver Spring, Maryland 20910
301/587-8202

Centimeter

Inches

MANUFACTURED TO AIM STANDARDS
BY APPLIED IMAGE, INC.

1 of 1

**COST EFFECTIVE ENERGY STRATEGIES FOR THE
REDUCTION OF CO₂ EMISSIONS IN THE UNITED STATES:
COUNTRY REPORT FOR ETSAP ANNEX IV**

S.C. Morris, J. Lee, W. Marcuse and G. Goldstein

February 1993

Biomedical and Environmental Assessment Group
Analytical Sciences Division
Department of Applied Science
Brookhaven National Laboratory
Upton, NY 11973 USA

This research was performed under the auspices of the United States
Department of Energy under Contract No. DE-AC02-76CH0016

MASTER

ED

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, not any of their contractors, sub- contractors, or their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency, contractor, or subcontractor thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency, contractor or subcontractor thereof.

ABSTRACT

The energy system of the United States of America was analyzed using MARKAL. The time period of the study was 1990-2030. Projected energy demands over this period for a Reference Scenario were largely modeled after the U.S. Energy Information Administration's 1992 Annual Energy Outlook for 1990-2010 and from the National Energy Strategy for the period 2010-2030. Expectations of maximum growth rates of conservation and renewable energy technologies were based on the same sources. Reductions in CO₂ emissions were achieved by setting absolute constraints on total emissions levels by year and by carbon taxes. A 10% reduction in CO₂ emissions was near the limit of technical feasibility for this scenario. This resulted in an overall cost increase of \$1.1 trillion present value, but marginal costs on CO₂ emissions reductions ranged up to \$3,300/ton. Over 70% of the CO₂ emissions reduction occurred in electrical generation, partly resulting from decreases in demand for electricity. Additional scenarios were run for conditions of low economic growth and with the addition of carbon sequestering technologies.

ACKNOWLEDGEMENTS

This work was supported by the Office of Environmental Analysis, Office of Domestic and International Energy Policy, U.S. Department of Energy. We thank Dr. E. Williams, head of that office, and Dr. L.D. Hamilton, Head of the Biomedical and Environmental Assessment Group at Brookhaven National Laboratory for their continuing encouragement and support. We also thank Professor A. Manne for his collaboration in work on MARKAL-MACRO, and our ETSAP colleagues for suggestions and assistance.

TABLE OF CONTENTS

ABSTRACT	iii
ACKNOWLEDGEMENTS	iv
INTRODUCTION.....	1
SCENARIOS, DATA AND ASSUMPTIONS	2
Database	2
Factors in the United States That May Affect Future Energy Patterns	3
Scenarios and Background Assumptions	4
Reference Scenario	4
Low Economic Growth Scenario	6
Carbon Removal and Sequestering Scenarios	6
Analysis Approach.....	6
RESULTS.....	7
CO2 Emissions and Costs of Reducing Emissions	7
Primary and Final Energy Use	10
Energy Intensity.....	12
Fuels and Their Shadow Prices	13
End-Use Energy Demands: Residential and Commercial	15
Shadow prices on demand	15
Changes in fuel mix	18
Changes in technology mix.....	19
Use of energy conservation.....	19
End-Use Energy Demands: Industrial	20
Shadow prices on demand	20
Change in fuel mix.....	22
Change in technology mix	22
Use of energy conservation.....	23
End-Use Energy Demands: Transportation.....	23
Shadow prices on demand	23

Changes in fuel mix	24
Change in technology mix	25
Electricity Generation	26
Carbon Removal and Sequestering	27
DISCUSSION AND CONCLUSIONS	28
Reference Scenario.....	28
Low Growth Scenario	29
Carbon Removal and Sequestering Scenarios	30
REFERENCES.....	30
APPENDIX I. Useful Energy Demand Projections for U.S. MARKAL Database.....	32

INTRODUCTION

This report gives the MARKAL analysis of the energy system in the United States done as part of the International Energy Agency's Energy Technology Systems Analysis Program (ETSAP) Annex IV. The aim of Annex IV was to explore national energy system options for reduction of greenhouse gases. This analysis focuses on least-cost strategies to reduce CO₂ emissions from the U.S. energy system. The period studied was 1990-2030 in 5-year steps. Useful energy demands were developed in a two-step process. First, a set of projected energy demands was developed, largely modeled after the reference case in the U.S. Energy Information Administration's 1992 Annual Energy Outlook (EIA, 1992) for the period 1990-2010 and the National Energy Strategy (EIA, 1990a,b,c) for the period 2010-2030. Assumptions behind these projections are detailed in Appendix I. Second, these energy demands were used as the underlying demands in a MARKAL-MACRO run. This accounted for price-elasticity effects and substitutability between energy and capital and labor. The useful energy demands that were the result of the MARKAL-MACRO run were then used as the exogenously specified demands in MARKAL for the ETSAP analyses. A parallel exercise was done for a low-growth set of energy demand projections. Both the MARKAL and MARKAL-MACRO analyses used a "no surprises" set of energy technologies based on assumptions from the same sources used as the basis of the demand projections. Supplemental cases, including additional technology options, were run with the reference and low-growth demands. This analysis included major changes from previous U.S. MARKAL analyses (Morris et al., 1990; Morris et al., 1992). The technology database used in these earlier analyses included more optimistic assumptions on the rate of technological advance and on upper bound of market penetration of new technologies. In addition to changes in the database, the energy demand structure in the model was improved.

MARKAL is a mathematical programming model that optimizes a network representation of an energy system with respect to several possible criteria. The network extends from energy resources (e.g., well fields and coal mines), through energy-transformation devices (e.g., refineries and power plants), followed by end-use devices (such as home furnaces, automobiles, commercial lighting appliances, and industrial electric drives) to satisfy demands for useful energy services. These energy service demands are exogenously specified (Appendix I). MARKAL essentially creates a market in which energy resources, supply technologies and end-use technologies compete to meet these energy service demands. Upper bounds can be set on the maximum extent of market penetration and rate of growth of market penetration for each technology, but, within those constraints, MARKAL determines the level of market penetration of each technology in the results.

CO₂ reductions were imposed on MARKAL in two ways: (1) absolute constraints were set on the level of CO₂ emissions, forcing the model to re-

configure the energy system to meet those constraints; and (2) taxes were assigned to fossil fuels in proportion to carbon content. These taxes affected the model's resource allocations within the energy system, but are not included in energy costs. MARKAL has several ways available to reduce emissions:

- Switching from fossil fuels to nuclear or renewable resources.
- Switching from high carbon fossil fuels to low-carbon fossil fuels such as natural gas.
- Replacing existing supply and end-use technologies with more efficient technologies.
- Investing in energy conservation technologies such as building insulation.
- Sequestering CO₂ or carbon.

MARKAL is strictly an energy systems model and examines only the energy sector. A limitation of this approach is that it does not include price elasticity effects on demand or other consumer behavioral effects except insofar as they are exhibited as price driven investments in the energy system to maintain existing levels of energy services. To overcome this limitation, we developed a new model, MARKAL-MACRO, that links MARKAL and MACRO (Manne and Wene, 1992; Hamilton et al., 1992). This introduces price elasticity of demand and substitutability between energy and other factors of production (capital and labor). In addition, MARKAL-MACRO also provides an indication of the effect of changes in the energy system, such as those imposed by CO₂ emission constraints, on the national economy as a whole. These effects are expressed as changes in GDP growth rates, consumption and overall investment. MARKAL-MACRO was used as an intermediary step in the reference case to provide these added sophistications. The energy service demands determined by MARKAL-MACRO for the Reference Case were used to drive MARKAL for the other cases to assure compatibility with submissions from other countries to ETSAP-IV. Issues of compatibility included (1) that others, using MARKAL, would use the same set of energy demands for all analyses with an economic growth scenario; and (2) reporting features to facilitate combining results from different countries.

SCENARIOS, DATA AND ASSUMPTIONS

Database

While the structure of the model is largely controlled by the level of detail in which useful energy service demands are specified, the richness of the analysis depends on the technology and resource database. This analysis used a database that includes 48 electric conversion technologies, 60 additional supply-side technologies, 120 end-use technologies and 17 energy resource types.

The U.S. MARKAL database was completely reviewed, expanded and updated as part of this work. The base year was established as 1990 (previously 1985); all costs were updated to 1990 U.S. dollars. Costs and efficiencies were reviewed and updated based primarily on data from the Department of Energy and the Electric Power Research Institute. Upper bound market penetration rates were established based on EIA's Reference case in their 1992 Annual Energy Outlook (EIA, 1992). This provides a less technologically optimistic view than that embodied in the earlier U.S. MARKAL database.

Additional technologies were included in a supplementary database that formed the basis for a supplementary analysis. These included various carbon removal technologies that allowed carbon removal from coal, oil and gas. These include and expand the set of carbon removal technologies analyzed in Morris et al. (1992b).

Factors in the United States That May Affect Future Energy Patterns

The future direction of several policy issues in the U.S. may affect energy patterns. These primarily involve interactions between energy and environmental policy. The two most important factors are the implications of the 1990 Clean Air Act Amendments (CAAA) and the push toward more demand-side management in the electricity sector.

The CAAA includes stringent new controls on NO_x emissions from electric power plants that will increase the cost of electricity and make non-fossil energy sources more attractive. It also provides for marketable permits to enforce further reductions in SO₂ emissions, and may lead to additional controls on emission of toxic materials from power plants and related technologies. The latter may affect the introduction of new, clean-coal technologies. These new burdens on electricity generation add to the move towards more demand-side management in an effort to reduce the need for generating capacity.

In addition to its effect on the electrical sector, the CAAA also forces states to take stringent measures to reduce ozone levels. These primarily affect transportation. They mandate some shift to alternative fuels, to use of more expensive and less efficient oxygenated gasoline, and provide corporations an incentive to reduce emissions associated with employees' travel to and from work.

States, rather than the Federal government, have led the drive toward more demand-side management in the electric sector, using the regulatory power of public utility commissions. Innovative approaches were applied in different states, including mandated demand-side management programs and economic incentives to electric utilities to reduce demand. The result was a considerable effort in this direction nationwide, with high expectations in many states that the need for new electric generating capacity can be sharply reduced from earlier expectations. In a related area, states have taken the initiative

(sometimes in the face of Federal opposition) to introduce externality costs in the overall cost accounting in the selection of new electrical generating facilities. This, in principal, is likely to lead to higher electric costs and a faster shift to less polluting sources of energy, including renewables.

Combined State and Federal initiatives opened the door for independent power producers to generate and sell electricity to utilities. Much of this power was produced by co-generation units, primarily gas turbines, but has also led to the introduction of some renewable sources of energy.

Energy taxes hold a double attraction; they tend to reduce demand for energy and they generate revenue. It seems likely that additional energy taxes will be imposed in the U.S. within the next year or two. It is not clear, however, if such a tax will take the form of a carbon tax, a gasoline tax, or an across-the-board energy tax. Each has different societal effects and different effects on the energy system.

Scenarios and Background Assumptions

Three scenarios were examined in this analysis: a "surprise free" reference scenario, a low economic growth scenario, and a carbon removal scenario. These are described individually below. The basic assumptions made in the Reference Scenario also apply to the other Scenarios unless otherwise stated.

Reference Scenario

The reference scenario was designed to be "surprise free" and was based on the reference case of the 1992 Annual Energy Outlook (AEO) (EIA, 1992). GDP in 1990 was $\$5.1 \times 10^{12}$. The AEO reference case was based on a GDP growth rate of 2.2%/year. Extrapolation of the AEO reference case from 2010 to 2013 was guided by analytical results of the National Energy Strategy (EIA, 1990a, b,c,d). A 1.8%/year GDP growth rate was assumed for 2010-2030. This resulted in a 2% average economic growth rate for the overall study period. This was the bottom of the high economic growth range for North America in the ETSAP-IV guidelines (ETSAP, 1991). Since this was based on the EIA reference case, we consider this to be both our reference scenario and our high economic growth scenario.

Although based on the AEO, we carefully considered growth rates of each of our demand categories and in some cases modified growth rates of useful energy demands. The largest change made from AEO estimates was a substantial reduction in the growth rate of automobile vehicle miles traveled. Reference Scenario demands and a discussion of their derivation are given in Appendix 1.

Population growth was not directly coupled with the energy reference scenario, but we used the U.S. Census Bureau Middle Series projections as a comparative basis. These estimates are given in Table 1.

Table 1. U.S. population projection (millions).

1990	1995	2000	2005	2010	2015	2020	2025	2030
248.7	260.1	268.2	275.6	282.6	289.0	294.4	298.3	303.2

Source: U.S. Bureau of Census, Middle series (series 14), Statistical Abstract of the U.S., 1991. Estimate for 2030 is our extrapolation. 1990 value is actual.

Oil prices were an important factor in the analysis. Prices of imported oil in the Reference Scenario are given in Table 2. These were taken from EIA (1992) and were within the ETSAP guidance ranges (ETSAP, 1991).

Table 2. Prices of oil imports in Reference Scenario (1990\$/bbl).

1990	1995	2000	2005	2010	2015	2020	2025	2030
21	24	27	29	32	35	37	40	42

Other Assumptions and miscellaneous information useful in interpreting the results are detailed in Table 3.

Table 3. Other Assumptions and miscellaneous Information associated with the U.S. analyses.

Discount Rate	5%/year
Monetary units	Millions of 1990 US dollars
Gross Private Domestic Investment	14.8% of GDP (1989)
Land surface	9,159,126 km ²
Heating degree days (65°F basis)	range: 199-9901
Cooling degree days (65°F basis)	range: 115-4389
Solar irradiation	average 1800 kWh/m ² (varies +/- 25%)

In the U.S., the Federal and state governments impose taxes on motor gasoline. Other fuels are subject to various state and local sales taxes. While the implications of these taxes are considered in the exogenously generated demand growth projections, they are not otherwise included in the MARKAL analysis.

Primary energy use is an important measure in comparisons among cases, directly and through secondary values such as energy intensity. Assumptions must always be made on how to express primary energy associated with renewable and nuclear energy sources. We did this by assuming a fossil-energy equivalent. Using this we calculated primary energy for conversion technologies by assuming efficiency of 33% in 1990 growing to 35% in 2030, reflecting improvements in fossil efficiency in the system. These fossil energy equivalents were used only in the calculation of primary energy use for reporting purposes; they had no role in the optimization.

Low Economic Growth Scenario

This scenario was similar to the Reference Scenario except the GDP growth rate was assumed to be 1.3%/year. This is reflected in a lower growth in useful energy demands than in the Reference Scenario. In all other respects, the Low Growth Scenario is exactly like the Reference Scenario.

Carbon Removal and Sequestering Scenarios

These scenarios included technologies that can separate carbon or CO₂ from fossil fuels or from the effluents of fossil-fuel combustion and sequester that carbon. These technologies also produced synthetic fuels such as hydrogen or methanol that gave the model greater flexibility as it configured the energy system. This set of additional technologies was run with useful energy demands from the Reference Scenario and the Low Growth Scenario.

Analysis Approach

In each scenario, a case with unconstrained carbon emissions was run and an attempt was made to run cases with CO₂ emissions stable at 1990 levels and continually decreasing linearly with emissions in 2030 at 10%, 20%, 30%, etc., below 1990 emission levels. The constraint on CO₂ emissions was made increasingly stringent until an infeasible solution was reached. An infeasible solution means it is impossible to achieve that level of CO₂ reduction given the assumptions in the database regarding the character and availability of resources and technologies. In addition to specific constraints on carbon emissions, the Reference Scenario was run unconstrained, but with a carbon tax. The tax rate used was \$15/ton carbon beginning in 1995 escalating at 10%/year, reaching \$422/ton in 2030.

RESULTS

CO₂ Emissions and Costs of Reducing Emissions

The reference case (no constraint on CO₂ emissions) projected increasing CO₂ emissions. The stability case and the 10% reduction case were technologically feasible. Annual carbon emissions for these cases are shown in Figure 1. For the unconstrained reference case, emissions in 2030 were 57% above 1990 levels. The 20% reduction case was infeasible. Average costs of CO₂ reduction in the tax case, the stability case and the 10% reduction case were \$19, \$50 and \$69 respectively (present value in 1990) per ton of carbon removed over the entire 1990-2030 study period (Table 4). Marginal costs of carbon removal (current year) were \$330/ton carbon to \$3,300/ton carbon in the stability case and \$430-\$7,700/ton carbon in the 10% reduction cases (Figure 2).

Figure 1. Annual carbon emissions for Reference Scenario.

Figure 2. Marginal costs of carbon removal for Reference and Low Growth Scenarios.

Since the demand for energy services grew at a slower rate in the Low Growth Scenario, it was easier for the system to reduce future CO₂ emissions. Energy service demands in 2030 averaged 15% lower than the Reference Scenario for industry, 7% lower for residential and commercial, and 24% lower for transportation. Although the technological database was the same as in the Reference Scenario, this difference in demand alone was sufficient to allow emission reductions up to 30% below 1990 levels. Average costs of emissions reduction over the entire 45-year study period are given in Table 4. In this table, emissions are the total over the 45-year duration of the study, while total system costs for the 45-year study are expressed as present value in 1990. Since MARKAL subtracts the value of all equipment remaining at the end of the study, these costs and emissions are comparable measures. The average cost per ton of carbon removed between cases is shown to increase as the carbon constraint becomes more stringent. Marginal costs of CO₂ reduction in the Low Growth Scenario were zero to \$1,500/ton carbon in the stability case and \$430/ton carbon to \$3,500/ton carbon in the 30% reduction case (Figure 2).

Table 4. Average Incremental Cost of Carbon Reduction.			
45-Year Totals			
Scenario	Cost, trillion \$	Carbon, billion tons	\$/ton
Reference Scenario			
Unconstrained	36.0	74.3	
Stable	36.7	59.9	50
-10% Carbon	37.2	56.9	145
Low Growth Scenario			
Unconstrained	31.2	64.7	
Stable	31.3	59.8	16
-10% Carbon	31.5	56.9	55
-20% Carbon	31.7	53.9	79
-30% Carbon	32.0	50.9	108

The High and Low-Growth Carbon Sequestering Scenarios applied the energy service demand growth rates of the Reference and Low Growth Scenario to an augmented database. Availability of carbon sequestering provided additional options for reducing carbon emissions, which would, if the model found them cost-effective, reduce overall cost per ton of carbon removal. This was indeed the case. At a high growth rate, nominal CO₂ reductions up to 50% were feasible. At a low growth rate, reductions up to 70% lower than 1990 were feasible. The overall average cost per ton of carbon emissions reduced are tabulated in Table 5. In this table, as for the Reference Case, emissions are the total over the 45-year duration of the study, while total system costs for the 45-year study are expressed as present value in 1990. Since MARKAL subtracts

the value of all equipment remaining at the end of the study, these costs and emissions are comparable measures. The average cost per ton of carbon removed between cases is shown to increase as the carbon constraint becomes more stringent. Marginal Costs of carbon removal are considerably higher than average costs and are shown for the Carbon Sequestering Scenarios are shown in Figures 3 and 4.

Figure 3. Marginal costs of carbon removal for Carbon Sequestering Scenario with high growth rate.

Figure 4. Marginal costs of carbon removal for Carbon Sequestering Scenario with low growth rate.

Table 5. Carbon Sequestering Scenarios Average Incremental Cost of Carbon Reduction.				
Scenario	Case	45-Year Totals		45-Year Average \$/ton
		System Cost billion \$	Emissions billion tons C	
Reference	Unconstrained	36007	74.65	
High Growth	Stability	36076	59.85	5
High Growth	-10%	36152	56.86	25
High Growth	-20%	36282	53.87	43
High Growth	-30%	36474	50.88	64
High Growth	-40%	36763	47.89	97
High Growth	-50%	37673	44.9	304
Low Growth	Unconstrained	31236	64.69	
Low Growth	Stability	31197	59.72	-8
Low Growth	-10%	31246	56.86	17
Low Growth	-20%	31305	53.87	20
Low Growth	-30%	31378	50.88	24
Low Growth	-40%	31494	47.88	39
Low Growth	-50%	31679	44.9	62
Low Growth	-60%	31942	41.9	88
Low Growth	-70%	32899	38.91	320

Primary and Final Energy Use

Primary energy supply for the Reference Scenario is summarized in Figure 5. Primary energy use increases over time in all scenarios, reflecting the increase in demand for energy services. The most striking features of the business-as-usual reference case are the rapid growth of renewables (3.5%/y) and the decline of nuclear (-2.9%/y). Coal (1.6%/y) grew faster than the average growth in primary energy, oil lower (0.6%/y), and natural gas about average (1.2%/y). As constraints on CO₂ were imposed, renewables were brought into the system faster, rising to a 5.1%/y growth rate with a 10% reduction in carbon emissions, and the downward trend of nuclear reversed to a 1.9%/y growth rate. Coal use dropped, with a 1.6%/y decline in the stability case and a 6.2%/y decline in the 10% reduction case. In the latter case, coal almost disappeared as an energy source. End-use conservation was included as a primary energy source in Figure 5 because we treat it as a fuel in MARKAL. It did not include efficiency changes in the supply side, which expressed themselves simply as a reduced need for primary energy to meet the same final demand. Conservation is discussed separately below by end-use.

Figure 5. Primary energy supply for Reference Scenario.

The Pattern of primary energy use in the Low Growth Scenario was similar to that in the Reference Scenario, but lower, corresponding to the lower growth rate in demand. With increasing emission constraints, renewables came in at a slower rate, coal went out at a slower rate.

In the Carbon Sequestering Scenarios under carbon emission constraint, coal had a positive growth rate between 1990 and 2030 in all cases, but growth was not steady. Coal use declined initially, during the early years when emission constraints were less stringent and could be met through other means. Coal then increased more rapidly as sequestering came more into play. Renewables still grew at reasonably high rates. Their growth was slower than in the Reference Scenario for the same level of emissions constraint, but as the constraint increased beyond what was possible in the Reference Scenario, renewables grew at an even faster rate than in the Reference Scenario.

Energy Intensity

Energy intensity is a measure of the efficiency with which energy is used in the economy. It is measured as the amount of energy used per unit GDP. The lower the energy intensity, the less energy is required to fuel the economy. Over time, and among cases, it shows the degree of decoupling between energy supply and the economy. It is given here in two units, primary energy per GDP and final energy per GDP. The first measures the total use of energy resources and reflects the efficiency of the energy supply system as well as the efficiency of end-users of energy. Final energy is the energy in fuels or electricity delivered to end users; thus, final energy/GDP does not include losses within the energy supply system.

While CO₂ emission constraints lead to a more expensive energy system than an unconstrained case, they also drive the energy system toward greater efficiency. This is reflected in Figures 6-7, which show the energy intensity of

selected cases. For each scenario, emission constraints led to lower energy intensity.

Figure 6. Primary energy intensity (PJ/GDP) for selected scenarios.

Figure 7. Final energy intensity (PJ/GDP) for selected scenarios.

Fuels and Their Shadow Prices

Shadow prices are the market clearing prices in MARKAL for each fuel. The relative changes of shadow prices of common fuels are shown in Figures 8-12 for representative cases. As CO₂ emission constraints are imposed, shadow prices for fossil fuels increase. This increase reflects the marginal value of the fuel if the emissions constraint could be relaxed sufficiently to allow one additional unit of fuel to be used. It can also be interpreted as the underlying price of the fuel plus an implicit carbon tax, that is, the tax on that fuel that would be necessary to achieve the reduction in CO₂ emissions forced on the system by

a direct constraint. This implicit tax can be determined by multiplying the marginal cost of carbon reduction (\$/ton) by the carbon emissions coefficient of the fuel (tons C/PJ). The underlying price is then the given shadow price minus the implicit tax. For example, in the Reference Case, the shadow price of coal rises from \$1.1/PJ in 1990 to \$2.73/PJ in 2030. In the Stable Emissions Case, it rises from \$1.1/PJ in 1990 to \$11.65/PJ in 2030, but when the implicit tax is subtracted, the underlying shadow price in 2030 is revealed as \$1.65/PJ, a 40% drop from the Reference Case. A similar, although lesser effect was seen with oil. The underlying shadow price of natural gas, however, increased with emission constraints, indicating the relatively favorable position of natural gas under CO₂ emission constraints compared to coal and oil.

Figure 8. Shadow price of natural gas for selected scenarios

Figure 9. Shadow price of gasoline for selected scenarios.

Figure 10. Shadow price of light heating oil for selected scenarios.

Figure 11. Shadow price of coal for selected scenarios.

Figure 12. Shadow price of summer day electricity.

End-Use Energy Demands: Residential and Commercial

Shadow prices on demand

The shadow prices of useful energy demands produced in MARKAL represent the decrease in total system cost that would follow a reduction in demand of one unit. They are thus shown as negative numbers, although they are discussed in the absolute sense, that is, those demands with the biggest marginal effect will be referred to as having the highest shadow prices. Figure 13 shows these prices for residential demand categories in the Reference Case. Miscellaneous uses (lighting and appliances) had higher shadow prices for all scenarios and cases run in both residential and commercial sectors. Figure 14 shows the effect on shadow prices on one demand, space heat, under different scenarios and CO₂ emission constraints. The shadow prices of all end-use demands in the Low Growth Scenario are lower than those in the Reference Scenario because of the lower system costs required to meet lower energy demands at the margin. The shadow prices of demand increased as CO₂ emission constraints were imposed on the energy system. The shadow prices generally dropped back to the levels in the Reference Case when carbon removal technologies were introduced to the technology base. Note the much lower shadow price for the 20% reduction case in the Carbon Sequestering Scenario using the Reference Scenario demands (RefC) than for even a 10% reduction case in the Reference Scenario. In the 50% CO₂ reduction case (only feasible for the Carbon Sequestering Scenarios) the shadow prices of all demands shot up sharply in 2030.

Figure 13. Marginal cost of meeting residential demands (\$/PJ) for the Reference Case (unbounded CO₂ emissions).

Figure 14. Marginal cost of meeting residential space heating demands (\$/PJ) under various scenarios: Reference with unbounded CO₂ emissions, Reference with 10% reduction in emissions, Low Growth with unbounded emissions, and Carbon Sequestering Scenario (high growth) with a 20% reduction in emissions.

Figure 15 shows the shadow prices for each demand category in the commercial sector for the Reference Scenario. The shadow prices of all commercial demands were much the same except for the lighting, which was considerably higher. Figures 16 and 17 show the effect of different scenarios and CO₂ emission constraints on the shadow prices of commercial space heat and lighting.

Figure 15. Marginal cost of meeting commercial demands (\$/PJ) for the Reference Case (unbounded CO₂ emissions).

Figure 16. Marginal cost of meeting commercial space heating demands (\$/PJ) under various scenarios: Reference with unbounded CO₂ emissions, Reference with 10% reduction in emissions, Low Growth with unbounded emissions, and Carbon Sequestering Scenarios (high growth) with a 20% reduction in emissions.

Figure 17. Marginal cost of meeting commercial lighting demands (\$/PJ) under various scenarios: Reference with unbounded CO₂ emissions, Reference with 10% reduction in emissions, Low Growth with unbounded emissions, and Carbon Sequestering Scenarios (high growth) with a 20% reduction in emissions.

Changes in fuel mix

As CO₂ constraints were imposed on the energy system in the Reference and Low Growth scenarios, the use of renewable energy increased in the residential and commercial sector replacing mainly gas and electricity (Figure 18). Under the Carbon Sequestering Scenario, more electricity was used to

replace the high-cost renewables at the 20% CO₂ reduction level as electricity could then be generated with greatly reduced CO₂ emissions by using converted carbon free fuels and CO₂ scrubbers.

Figure 18. Percentage share of each fuel in the residential and commercial sector for selected scenarios and cases.

This explains why demand shadow prices were lower in this scenario as compared to CO₂ constrained cases in the Reference Scenario. Under extreme CO₂ constraints (50% reduction), however, the use of electricity and renewables both increase significantly.

Changes in technology mix

The main changes in end-use technology mix across different CO₂ constraints were in residential and commercial heating. Figure 19 shows that the 10% CO₂ reduction case in the Reference Scenario required more efficient gas burners and a major shift to solar (with fossil fuel or electricity backup) in the later periods. In the Low Growth Scenario, a 20% reduction in total CO₂ emission caused a shift to more efficient gas burners for all time periods. With the introduction of higher efficiency coal technologies, the same change pattern prevailed in the 20% reduction case, eliminating the need for solar technologies. Under the 50% reduction case, however, almost all residential and commercial heating in the later periods was met by solar technologies.

Use of energy conservation

The market penetration of energy conservation measures in residential and commercial building shells did not change significantly among all cases (Figure 20). This was due to the fact that most conservation measures (except residential conservation level 3) were economically competitive without regard to CO₂ emission constraints. The peak contribution from conservation was estimated to be over 1600 PJ, which gradually declined in time as building structures associated with these measures were retired. Under CO₂ emission

constraint cases, an additional amount of 55 PJ was saved through the implementation of high-cost conservation measures applicable to residential houses.

Figure 19. Changes in technology mix for residential and commercial space heating over selected scenarios and cases.

Figure 20. Use of end-use conservation in residential and commercial sectors for selected scenarios and cases.

End-Use Energy Demands: Industrial

Shadow prices on demand

Figure 21 shows the shadow prices of useful energy demands in the industrial sector for the Reference Case. Figure 22-23 show the change in the shadow prices for two specific demands, industrial process heat and electrical-mechanical drive for selected scenarios and cases. The relatively large increases associated with CO₂ constraint in the Reference Scenario can be

attributed partially to the sector's higher dependence on coal compared to the residential and commercial sectors. The shadow prices were also sensitive to the assumptions in future technology developments. As shown in the 20% reduction case, these values dropped down to near their Reference Case levels when carbon removal and sequestering technologies were introduced.

Figure 21. Shadow prices of industrial demands in the Reference Case.

Figure 22. Shadow prices of industrial process heat demand under selected scenarios and cases.

Change in fuel mix

In the Reference and Low Growth Scenarios, the fuel mix was quite stable and showed only a small increase in the share of natural gas when CO₂ constraints were imposed on the energy system (Figure 24). The 50% reduction case combined with coal conversions and carbon removal technologies, however, showed a much greater increase in gas usage, replacing almost all coal consumption in industry in the later time periods. This was due to the

penetration of clean coal technologies that allowed more coal to be used at central stations with lower CO₂ emissions, releasing a large quantity of gas for end-use consumption.

Figure 23. Shadow prices of industrial electro-mechanical drive demand under selected scenarios and cases.

Figure 24. Percentage share of fuels in the industrial sector for selected scenarios and cases.

Change in technology mix

Figure 25 shows more efficient coal and gas burners were used to replace conventional coal burners when CO₂ emission limitations were applied to the Reference and Low growth Scenarios. To achieve a 50% CO₂ reduction, gas burners completely replaced coal burners after 2020.

Figure 25. Changes in technology mix for industrial steam and process heat for selected scenarios and cases.

Use of energy conservation

The market penetration of industrial conservation programs characterized in this study reached its upper bound in all cases, resulting in a peak energy saving of 1100 PJ. This saving declined in the later periods as the equipment associated with the conservation measures were retired from production. Industrial conservation measures included in the database were, for the most part, retrofit technologies to existing equipment and it was assumed that future demand projections included increasing energy efficiency.

End-Use Energy Demands: Transportation

Shadow prices on demand

The shadow prices of transportation demands were generally higher than those of other sectors (Figure 26). These high prices were due primarily to the high capital cost per unit capacity and the dominant use of petroleum products in all transportation modes. Figure 27 shows the change in shadow prices of one demand category, automobile transportation, for selected cases. As CO₂ reduction constraints were imposed on the energy system, shadow prices increased. As more efficient coal and gas conversion technologies were introduced to the system, resulting in an increased supply of methanol at competitive cost, these values dropped back to near their reference case levels.

Figure 26. Shadow prices (\$/PJ) on transportation sector demands for the Reference Case.

Figure 27. Changes in shadow prices for automobile energy demand for selected scenarios and cases.

Changes in fuel mix

The distribution of fuel used in transportation did not change significantly among cases. In automobile fuel consumption, for example, liquid fuels consistently dominated, except in the 50% CO₂ reduction case in which compressed natural gas took over more than 10% of the total fuel consumption (Figure 28). Among liquid fuels, methanol replaced a large fraction of the total from petroleum products in the 10% CO₂ reference and 20% CO₂ low cases. It almost totally replaced petroleum products in the later periods when coal and gas conversion technologies coupled with carbon sequestration were introduced.

Figure 28. Percentage share of different fuels in the transportation sector for selected cases.

Change in technology mix

Figure 29 shows that in the 10% CO₂ reduction case, under the Reference Scenario, more efficient automobiles began to replace almost half of the market share of standard automobiles in 2010. By 2020, the combination of efficient automobiles and methanol automobiles took over the entire market. In cases in which methanol manufactured from coal and gas became available in large quantity, methanol automobiles alone provided the means for passenger transport in the later periods in order to meet 20% to 50% CO₂ reductions.

Figure 29. Changes in automobile technology mix for selected cases.

Electricity Generation

Figure 30 shows that total electricity generated and their input fuel mix were sensitive to CO₂ emission constraints and the technological base assumptions. In the Reference Scenario, a 10% CO₂ reduction caused a complete shift from coal-power plants to a combination of gas, nuclear, and renewable energy based power plants by 2030, together with a decrease in electricity generation from over 19000 PJ to about 16000 PJ by the same year. More than 75% of the total system-wide reduction in CO₂ emissions were produced in electrical generation. The nominal 10% system-wide reduction in CO₂, when allocated in a least-cost way, led to a 42% reduction in emissions from electrical generation.

In the 20% CO₂ and 50% CO₂ cases, the introduction of carbon sequestration technologies reversed this trend, allowing a growing market for coal-based power plants equipped with CO₂ scrubbers. Contrary to the cases in the Reference Scenario, the clean coal technologies also allowed higher electricity production with minimal CO₂ emission increases so that "clean electricity" achieved greater market penetration, replacing carbon containing fuels. Looking specifically at the Reference Scenario, high-efficiency coal technologies (without sequestering) remained in the energy system in the stability case, but even these lost market share in the 10% reduction case (Figure 31)

Figure 30. Electricity generation by fuel for selected cases.

Figure 31. Market penetration of conventional and advanced, high efficiency coal technologies in the reference Scenario under different CO₂ emission constraints.

Figure 32. Amount of carbon sequestered in the Carbon Sequestering Scenarios with high and low demand growth.

Carbon Removal and Sequestering

The carbon sequestering technologies characterized in this study formed an integrated network that simulated the separation of carbon or CO₂ from fossil fuels in upstream conversion processes to pre-combustion (e.g., direct storage of CO₂ or carbon black in depleted gas wells) and post-combustion mitigation (e.g., CO₂ scrubbing and storage). The synthetic fuels such as methanol or hydrogen produced in the conversion processes provided clean energy to both supply and demand technologies and thus allowed greater use of high carbon content energy resources such as coal without significant increases in total CO₂ emission. As a result, up to 50% CO₂ reduction was achieved when these technologies were made available to the model. Figure 32 shows the amount of

CO₂ removed from the energy system in 20% and 50% reduction cases under Reference and Low growth rates. The total carbon removed per year started at over 77 million tons in 1995 in the 20% low case and peaked at almost 600 million tons in 2030 in the 50% Reference case. Carbon sequestration technologies also greatly reduced the average cost per ton of carbon removed. In the 20% CO₂ reduction cases, this average was about \$13 per ton of carbon removed, as compared to \$67 per ton of carbon removed to remove only 10% in the Reference Scenario without carbon sequestration.

DISCUSSION AND CONCLUSIONS

Results of the analysis were presented above by measure. For example, average and marginal costs of CO₂ reduction were presented for all scenarios under the same heading. To help bring information together, each scenario is discussed here as a unit. Emphasis is given to the Reference Scenario, while the others provide supplementary information.

Reference Scenario

Given the energy service demands and the "business-as-usual" penetration rates of new technologies in the Reference Case, the limit of technological feasibility was slightly better than a 10% reduction over 1990 emissions by 2030. A 20% reduction was technologically impossible. A 10% reduction in CO₂ emissions from 1990 levels increased present value energy systems costs by \$1.15 trillion (3.2%) over the reference case. The average incremental cost from unconstrained to stable emissions was \$50/ton and the average incremental cost from stable to a 10% reduction was \$145/ton. Marginal costs varied over time, but ranged from \$330/ton to \$3,300/ton. Greater reductions in CO₂ emissions would require either that demands be reduced, upper bounds on market penetration rates for non-carbon energy sources be increased, or greater strides be made in energy conservation and efficiency improvement.

Shadow prices on energy service demands increased substantially between the Stability Case and the 10% reduction case in the Reference Scenario. Changes varied by sector: shadow prices of residential sector demands increased 2-3 fold; shadow prices of commercial sector demands increased 1.4-3 fold; shadow prices of industrial sector demands increased 3-7 fold; but shadow prices of transportation sector demands increased only 1.1-1.2 times. These price increases would tend to drive demands down. Indeed, preliminary analyses with MARKAL-MACRO were able to achieve a 20% emissions reduction in the Reference Scenario because it allowed demands to fall in response to higher prices (Hamilton et al., 1992). Even a 20% reduction, however, is far from what is often claimed to be necessary to eliminate continuing increases of CO₂ concentrations in the atmosphere. Further exploration is needed with both models to determine the system's response in

terms of increased penetration rates of technology now in the database and the viability of additional new technologies not included in the database. Some indication of the possibilities can be seen in our analysis for the Stanford Energy Modeling Forum (Morris et al., 1992a). The growth in energy service demands in that analysis were lower than in our current Reference Scenario, and the upper limits on market penetration of conservation and renewable technologies were much higher. There, a \$15/ton carbon tax escalating at 10%/year achieved roughly a 20% reduction from 1990 levels, whereas in the current Reference Case, the same tax achieved less than stability in emissions.

The marginal costs of supplying energy service demands invariably increased as CO₂ constraints became more stringent. In the residential and commercial sectors, this was associated with an increase in direct use of solar energy sources displacing electricity and gas. In industry, the principal change is that coal was replaced by gas and that remaining coal use was concentrated in new and more efficient burners. Transportation remained strongly petroleum based even with CO₂ emissions constraint, but alcohol fuel (made from wood) penetrated 18% of the automobile market in the 10% CO₂ reduction case.

As shown in the results, a least-cost allocation of CO₂ emissions reduction hits hard on electricity generation. The nominal 10% system-wide reduction in CO₂, when allocated in a least-cost way, led to a 42% reduction in emissions from electrical generation.

Low Growth Scenario

The Low Growth Scenario further demonstrated the substantial effect on the ability to reduce emissions that can be achieved by reduced demand levels. Of course, one does not conclude from this that lower economic growth rates are desirable. It shows that the lower growth in energy demands associated with lower economic growth lead to lower CO₂ emission growth. While lower energy growth makes it technically feasible to achieve greater reduction in emissions, those reductions come at a substantial cost. That cost is more difficult to bear during times of low economic growth. The need to internalize this interaction among environment, energy and the economy was the primary driving force behind the development of MARKAL-MACRO.

Moreover, low economic growth rates impede improvements in energy intensity. The same trend is seen as in the Reference Scenario, that is, increasingly stringent CO₂ emissions constraints lead to decreasing energy requirements per unit GDP. The Unconstrained Low-Growth Case, however, exhibited higher energy intensity than the Reference Case. Even the 20% reduction case under low growth had a higher energy intensity than the Reference Case.

Indirectly, the Low Growth Scenario shows that reductions in energy demand can substantially contribute to achieving lower emission targets. Future

analyses should explore more aggressively the opportunities that new energy conservation technology or life-style changes could provide.

Carbon Removal and Sequestering Scenarios

Within the scope of the current analysis, only carbon removal technologies and carbon sequestering allowed CO₂ emission reductions of more than 20%. Perhaps more importantly, these technologies allowed 10-20% reductions in emissions at much lower cost than that of the 10% emissions reduction case in the Reference Scenario. Since CO₂ sequestering means forgoing the use of a substantial part of the energy content of fossil fuels, it seems inherently wasteful and undesirable. On the other hand, if our cost and efficiency estimates are reliable, it appears to be a more effective use of resources than the non-carbon energy sources with which it competes (and whose cost and efficiency estimates are equally as uncertain). A compromise position, which MARKAL found to be cost-effective, is to produce automotive fuels, such as methanol, that have lower carbon content than gasoline.

Another important aspect of the carbon sequestering scenario is that it allows the continued use of coal. In the Reference Scenario, CO₂ emissions reduction is virtually synonymous with reduction in coal use. This was reflected clearly in the change in primary energy supply as CO₂ emissions constraints increased (Figure 5). Thus, sequestering mitigates economic disruption in an important industry and allows continued use of a major domestic energy resource.

REFERENCES

- EIA. 1990a. Improving technology: modeling energy futures for the National Energy Strategy (SR/NES/90-01). U.S. Energy Information Administration, Washington, DC.
- EIA. 1990b. Energy consumption and conservation potential: supporting analysis for the National Energy Strategy (SR/NES/90-02). U.S. Energy Information Administration, Washington, DC.
- EIA. 1990c. Electricity supply: supporting analysis for the National Energy Strategy (SR/NES/90-03). U.S. Energy Information Administration, Washington, DC.
- EIA. 1990d. Renewable energy excursion: supporting analysis for the national energy strategy (SR/NES/90-04). U.S. Energy Information Administration, Washington, DC.
- EIA. 1992. Annual energy outlook 1992 (DOE/EIA-0383(93)). U.S. Energy Information Administration, Washington, DC.

ETSAP. 1991. Summary of guidelines for common scenario submissions, Energy Technology Systems Analysis Programme, Annex IV: Greenhouse gases and national energy options, Petten (15 November).

Hamilton, L.D., G.A. Goldstein, J. Lee, A.S. Manne, W. Marcuse, S.C. Morris, and C-O. Wene. 1992. MARKAL-MACRO: an overview (BNL-48377), Brookhaven National Laboratory, Upton, NY 11973.

Manne, A.S. and C-O. Wene. 1992. MARKAL-MACRO: a linked model for energy-economy analysis (BNL 47161). Brookhaven National Laboratory, Upton, NY 11973.

Morris, S.C., B.D. Solomon, D. Hill, J. Lee, and G. Goldstein. 1990. A least cost energy analysis of U.S. CO₂ reduction options, in J.D. Tester, D. Wood, and N. Ferrari (eds.), *Energy and the Environment in the 21st Century*, MIT Press, Cambridge, MA, pp. 865-876..

Morris, S.C., J. Lee and G. Goldstein, 1992a. U.S. MARKAL results for EMF-12. Brookhaven National Laboratory, Upton, NY 11973.

Morris, S.C., J. Lee, G. Goldstein and M. Steinberg. 1992b. Comparison of pre- and post-combustion carbon removal. *Energy Conversion and Management* 33: 747-754.

APPENDIX I

Useful Energy Demand Projections for U.S. MARKAL Database

Population and Economic Growth Assumptions

While not explicit parameters in MARKAL, assumptions concerning population and economic growth greatly affect energy demand projections. The following are the underlying assumptions for the Reference Case.

Middle population growth projection of 1990 census is 0.7%/y 1990-2000 and 0.5%/y 2000-2025. Of all the projections we have to deal with, this is the most "solid."

1992 AEO (p. 179) Projects GNP growth rate of 2.2%/y 1990-2010 in the Reference case. We reduce this to 1.8%/y from 2010 to 2030 to reflect the decrease in population growth rate after 2000.

GNP growth rates that exceed population growth lead to increased per capita income. 1992 AEO (p. 71) assumes a 1.8%/y increase in real disposal personal income from 1990-2010.

Approach to Useful Energy Demand Projections for MARKAL

MARKAL requires exogenously specified useful energy demands for each demand category. These projections were developed in a two-stage process. First, a set of projections was developed based on the 1992 Annual Energy Outlook for 1990-2010 and from the National Energy Strategy for 2010-2030. Some modifications were made. These are detailed below and summarized in Table A-1 under the columns "Actual 1990" and "Initial Projections." These projected energy demands were specified as the underlying growth rates in MARKAL-MACRO. This model allows substitution and price elasticity to operate. The MARKAL-MACRO results provide a modified set of energy demands. These are summarized in Table A-1 in the columns "MARKAL-MACRO Results." It was these modified demands that were used as the exogenously specified energy service demands in the U.S. MARKAL analyses for ETSAP Annex IV.

Residential

NES (90-02, p. 38) assumes housing stock growth of 0.83%/y (p. 38). 1992 AEO uses an 0.9%/y growth in total housing stock in the reference case (p. 75).

Growth rate of housing stock exceeds population growth rate. This reflects a shift to smaller families, more individuals living alone, and more second homes. This, in turn, leads to changes in composition of housing. Mobile homes and multi-family housing grow faster than single family homes (NES 90-02, p. 38).

Mobile homes, multi-family homes, and second homes have lower demands for useful energy than single family homes.

On the other, hand, since per capita income levels are projected to rise, people are likely to spend more on housing. All types of housing may grow in floor space per housing unit, existing energy uses increase in saturation level, and new energy uses may develop..

Space Heat

The demand for space heat is projected directly from the 1990 base using the housing stock growth rate. This includes the implicit assumption that the UED for space heat per housing unit remains constant over time. In the current formulation, we allow for retrofit of additional building shell improvements in buildings existing in 1990, but not for new construction, on the assumption that increasingly better building shell will be required by building codes and will be simply part of the cost of the basic house. The lack of accounting for these building shell improvements is compensated for by the lack of accounting for expected increases in the floor space per unit, with the change in unit types also thrown in. It might be argued that, even though people move into larger quarters, they strive to retain previous fuel costs, thus tending to keep per unit heating demands constant. The problem is further complicated by the fact that available data on energy demands is actually on fuel use, and estimation of useful energy demands are confounded by changes in heating device efficiency.

Key issues are: (1) shift in the split among housing types, presumably leading to lower UED/unit; (2) shift to larger units of all types, presumably leading to higher UED/unit; (3) more second homes, presumably leading to lower UED/unit; and (4) regional shifts of population within the country, leading to lower heating and higher air-conditioning demands for a southward shift, and the reverse for a northward shift.

We live with this for now. We plan, at the least, to make the implicit assumptions more explicit in the model itself, and, ideally, to find or develop a suitable model that can aid us in making predictions of UED that are driven by explicit assumptions about housing stock character.

Water heat

Demand for water heat is projected to grow at the same rate as housing units, although fewer people per unit would suggest a lower rate. Increasing wealth, however, may lead to greater saturation of clothes and dish-washing machines, hot tubs, heated swimming pools and possibly other uses of hot water.

Cooling

Demand for residential cooling is projected to grow faster than the growth in housing units due to an overall increase in use of air conditioning and a shift from partial air conditioning with room units to whole house air-conditioning. From 1978-1990, houses with no air conditioning decreased from 44 to 32% (2.7%/y). In the same period, use of central air conditioning grew from 23% to

39% (4.4 %/y) while individual units decreased slightly from 33% to 29% (-1.1%/y). Electric use for cooling in 1992 AEO reference case (p.75) grows at 0.7%/y 1990-2010. Assuming that central air grows from 39% saturation in 1990 to 70% in 2030 and room air decreases from 29% to 10%, and that room units supply half the UED of central units, a growth rate of 1.7%/y obtains.

Lighting and Appliances

1992 AEO gives a 1.3%/y increase in electricity use for refrigeration, lighting, and other household appliances, despite expected efficiency gains in refrigeration and lighting. For example, new Federal efficiency standards (1992 AEO, p. 9) of 961 kWh/y for refrigerators uses 56% of the energy of the LBL base 1989 refrigerator. Other household uses of electricity are on a rapid upward trend (e.g., Meier, 1992). On the other hand, efforts are beginning to address increased efficiency in new electronic devices. A 2%/y increase in UED does not seem unreasonable.

Commercial

1992 AEO projects commercial floorspace to grow at a rate of 1.8%/y 1990-2010 (p. 76). NES (90-02, p. 38) projected 1.7%/y growth 1990-2030. We apply the 1992 value through 2010, then decrease to the NES value in recognition of the decreasing population growth after 2000 and apply these values to all commercial sector energy demands. These rates are applied to all commercial energy demands except miscellaneous appliances, which includes microcomputers and other electronic office equipment and have been growing at a high rate, especially in office buildings. DeLaHunt (1988) found a 2.4%/y increase in energy use in "computers and miscellaneous equipment" (CME) in office buildings. Nguyen et al. (1988) provide data that suggest office buildings make up 58% of the CME energy demand of the total commercial sector (in California). Assuming other segments of the commercial sector grow in CME at the slower rate of 2%/y, overall growth rate is 2.2%/y. We reduce this in the 2010-2020 time period on the assumption that there will be some saturation and that conservation will begin to be built into this equipment (the latter we include in the growth trend, since we do not have sufficient information to characterized specific conservation technologies).

Transportation

Annual growth rates of travel indices from 1992 AEO (p. 78) are as follows:

Annual growth rate in travel indices from 1992 AEO, 1990-2010.	
Mode	Annual Growth Rate (%)
Light duty vehicles	1.7
Freight trucks	1.9
Air	3.9
Rail	1.3
Marine	1.2

Passenger Travel: Road vehicles

The AEO projections for light duty vehicles (cars and light trucks) are the result of econometric projections involving growth in disposable personal income, gasoline prices, average vehicle efficiency, and changes in the demographic composition of the driving age population. From the engineering view, however, they seem to be unreasonably high, leading to a 60% increase in the miles per person per year from 1990 to 2030. High rates of increase seem difficult in the face of low rates of population growth. It is possible that better, faster roads, including intelligent roads, may lead to an increase in miles traveled in time for commuting to work and for recreational travel. Current prospects seem to be in the opposite direction. Increased congestion in urban areas results in slower average speeds. Moreover, the 1990 Clean Air Act is requiring massive efforts to reduce ozone pollution that generally lead to fewer vehicle miles traveled. A seemingly overwhelming desire for personal means of transportation may lead to ways to counteract this trend, especially during a time of increasing wealth, but it is difficult to see how, without a decrease in useful energy demand (e.g., same number of vehicles in smaller, lighter cars on a smart highway). An increase in recreational travel per person may not be as affected by environmental constraints, but, with increasing wealth, the greater increase in air travel is likely to divert much of the potential mileage from recreational driving. Our preference would be for growth rates of 0.8%/y for autos with a somewhat higher rate for light trucks. Since virtually every official projection indicates substantially higher rates of growth in vehicle miles traveled, we feel we must give way to some degree. We opt for 1%/y.

Busses are a small energy segment not included in most projections. We give them a higher growth rate than cars on the assumption that they will absorb part

of the urban transportation growth not going to cars because of congestion and may be preferable due to increased use of bus lanes.

Air Transport

We follow the 1992 AEO projections for air transport from 1990-2010, moving to the NES estimate for 2010-2030, a period not covered in AEO 1992.

Freight Transport

Here the AEO rates seem too low. It seems reasonable that freight travel should be more closely coupled with industrial output, especially manufacturing output. We apply GNP growth rates directly to truck, rail, and ship transport.

Industry

AEO 1992 gives a 2.5%/y growth rate to manufacturing and 1.6%/y to non-manufacturing industry, with a rate of 2.3%/y overall (p. 77). We use the AEO 1992 total industrial growth rates except for iron and steel, which we assume does not grow.

Useful Energy Demand		code	Actual		Initial Projections		Results	
			1990 PJ	2030 PJ	Growth rate, %/y	2030 PJ	Growth rate, %/y	MARKAL-MACRO
Iron and Steel		I.I1	796.5	796.5	0	1134.0	0.89	
Aluminum		I.IA	316.0	697.4	2.00	677.5	1.93	
Industrial boilers		I.ID	4392.7	9694.2	2.00	8893.4	1.78	
Fabrication and electric drive		I.IE	2512.0	5543.7	2.00	5424.9	1.94	
Other industrial heat		I.IH	4824.5	10647.2	2.00	8725.7	1.49	
Subtotal Industry			12841.7	27379.0	1.91	24855.5	1.66	
Non-energy		N.NY	1150.0	2537.9	2.00	1844.2	1.19	
Subtotal non-energy			1150.0	2537.9	2.00	1844.2	1.19	
Residential space heating		R.R0	4041.8	5784.0	0.90	6193.5	1.07	
Residential water heating		R.R1	1100.4	1574.8	0.90	1681.9	1.07	
Residential cooling		R.R2	1371.0	4133.3	2.80	2572.2	1.59	
Residential lighting and appliances		R.R3	2255.1	4979.5	2.00	4761.9	1.89	
Subtotal Residential			8768.3	16471.6	1.59	15209.4	1.39	
Commercial space heating		R.R5	2483.4	4970.7	1.75	4547.8	1.52	
Commercial water heating		R.R6	120.9	242.0	1.75	224.0	1.55	
Commercial cooling		R.R7	2765.4	5535.3	1.75	5225.3	1.60	
Commercial light		R.R8	1210.4	2422.8	1.75	2537.2	1.87	
Commercial miscellaneous appliances		R.R9	945.4	2170.6	2.10	2114.6	2.03	
Subtotal Commercial			7525.5	15341.4	1.80	14649.0	1.68	
Automobile		T.T0	9634.2	12855.3	1.00	13723.5	1.17	
Light truck		T.T1	2584.8	3848.6	1.00	3907.8	1.04	
Heavy truck		T.T2	5063.9	11180.0	2.00	9454.4	1.57	
Bus		T.T3	137.2	230.0	1.30	230.0	1.30	
Air		T.T4	2732.5	11968.4	3.76	6989.3	2.38	
Ship		T.T5	1245.0	2747.7	2.00	2380.0	1.63	
Rail		T.T6	543.1	1198.1	2.00	1176.7	1.95	
Military Air		T.TX	580.3	580.3	0.00	580.3	0.00	
Subtotal transport			21521.0	44608.3	1.84	38442.0	1.46	
Total useful energy demands			51806.5	106338.2	1.81	95000.1	1.53	

**DATE
FILMED**

8 / 31 / 93

END