AIM

Association for Information and Image Management

1100 Wayne Avenue, Suite 1100
Silver Spring, Maryland 20910
301/587-8202

Centimeter

Inches

MANUFACTURED TO AIM STANDARDS
BY APPLIED IMAGE, INC.

1 of 2

Mechanism and Environmental Effects on MEOR
Induced by the Alpha Process

Final Report
By
Franz K. Hiebert
John Zumberge
Bruce Rouse
Arturo Cowes
Larry W. Lake

April 1993

Work Performed Under Contract No. DE-FG22-88BC14205

Prepared for
U.S. Department of Energy
Assistant Secretary for Fossil Energy

Fred Burtch, Project Manager
Bartlesville Project Office
P.O. Box 1398
Bartlesville, OK 74005

Prepared by
Alpha Environmental
7748 Highway 290 West
Austin, TX 78736

MASTER
REPRODUCTION OF THIS DOCUMENT IS UNLIMITED

Table of Contents

List of Tables	v
List of Figures	vi
Executive Summary	viii
Section 1. Introduction	1-1
Section 2. Review of Field and Reservoir Data, Shannon Sandstone, Teapot Dome Field, Wyoming	
Introduction.....	2-1
Teapot Dome Field	2-1
Shannon Sandstone	2-1
Reservoir Characteristics	2-2
Previous EOR	2-2
Geology.....	2-3
Structure.....	2-4
Facies	2-4
Mineralogy and Fabric.....	2-5
References.....	2-6
Tables and Figures.....	2-7
Section 3. Teapot Dome Field Work	
Introduction.....	3-1
Materials	3-2
Methods	3-3
Pretreatment.....	3-3
Treatment.....	3-4
Post-treatment	3-4
Results.....	3-5
Discussion	3-7
Conclusions.....	3-8
Tables and Figures.....	3-10
Section 4. Laboratory Core-Flood Testing of a Microbial Enhanced Oil Recovery Process Under Anaerobic Conditions	
Summary	4-1
Introduction.....	4-1
Experimental Procedures	4-2
Results.....	4-5
Discussion	4-6
Conclusions.....	4-13
Acknowledgements.....	4-13
References.....	4-13
Tables and Figures.....	4-15

Section 5. Chemistry of Oil Produced Before and After MEOR Treatment at Teapot Dome Field, Wyoming

Introduction.....	5-1
Methods and Materials	5-2
Results.....	5-3
Discussion	5-5
Conclusions.....	5-6
References.....	5-6
Tables and Figures	5-7

Section 6. Laboratory Investigation of Bacteria-Rock Interactions Under Simulated Shannon Sandstone Reservoir Conditions

Summary.....	6-1
Introduction.....	6-2
Objectives	6-9
Materials	6-9
Methods	6-11
Results.....	6-12
Discussion	6-13
Conclusions.....	6-15
References.....	6-15
Figures	6-19

Section 7. Appendices

Appendix 1.....	Appendix-1-1
Laboratory procedures for determining total hydrocarbon degrading bacteria population and preparation of media	
Appendix 2.....	Appendix-2-1
Allocation algorithm for used for calculating oil production.	
Appendix 3.....	Appendix-3-1
Oil and water production and total hydrocarbon degrading bacteria population in MEOR pilot wells	

List of Tables

Table 2-1. Summary of Shannon oil reserves.....	2-7
Table 2-2. Shannon Sandstone reservoir data.....	2-7
Table 2-3. Summary of petrographic examination of the U. and L. Shannon facies.....	2-8
Table 2-4. X-ray analysis of bulk and less than 5 micron sand fraction.....	2-9
Table 3-1. Population of total hydrocarbon degrading bacteria in MEOR pilot wells.....	3-10
Table 4-1. Summary of results of 12 core floods using decane and Shannon crude oil in Berea sandstone cores.....	4-15
Table 5-1. Population densities of Total Hydrocarbon Utilizing Bacteria (THUB) in the three wells samples for organic analysis before and after treatment.....	5-7
Table 5- 2. Ratios of pristane/phytane, pristane/C17, and phytane/C18 for oil sampled before and after MEOR treatment.....	5-7

List of Figures

Figure 1-1. Conceptual drawing of oil, brine, and MEOR bacteria in a water-wet oil reservoir.....	1-4
Figure 2-1. Structure map on the top of the Upper Shannon Sandstone, Teapot Dome Field, N. P. R. #3, Natrona County, Wyoming.....	2-10
Figure 2-2. Well locations of the MEOR pilot project superimposed on top of local geologic structure.....	2-11
Figure 2-3. Schematic cross section from south to north through the MEOR pilot area.....	2-12
Figure 2-4. Schematic facies distribution and structural relationship between the two wells treated with MEOR materials.....	2-13
Figure 2-5. X-ray analysis of the three most prominent lithologic facies in the MEOR pilot.....	2-13
Figure 3-1. Well location map of the Alpha Environmental MEOR pilot area at Teapot Dome Field, Wyoming.....	3-11
Figure 3-2a and 3-2b. Pre- and post-treatment oil and water production (24 hour test volumes) with historical and predicted oil production decline curve for the two MEOR treatment wells in the Teapot Dome pilot area.....	3-12
Figures 3-3a and 3-3b. Oil and water production for "bacterially active" (3a) and "non-active" (3b) wells in the Teapot Dome MEOR pilot area.....	3-13
Figure 3-4. Oil and water production and population level of total hydrocarbon degrading bacteria from producing wells treated with the MEOR materials in late August, 1988.....	3-14
Figure 4-1. Production results for core number 8.....	4-16
Figure 4-2. Production and pressure drop data for core number 9.....	4-17
Figure 4-3. Production and pressure drop data for core number 10.....	4-18
Figure 4-4. Production and pressure drop data for core number 11.....	4-19
Figure 4-5. Production and pressure drop data for core number 12.....	4-20
Figure 4-6. Hypothetical metabolic pathway for microbial formation of a fatty acid surfactant.....	4-21
Figure 5-1. Location of the three wells selected for analysis of oil before and after treatment with MEOR materials.....	5-8

Figure 5-2. Whole crude oil analysis by GC-FID for wells 61-SX-3, 78-SX-3, and 31-S-3.....	5-9
Figure 5-3. Well # 61-SX-3 (treatment well). Before and After MEOR treatment analysis of whole crude oil by GC-FID.....	5-10
Figure 5-4. Well #78-SX-3 (observation well). Before and after MEOR treatment analysis of whole crude oil by GC-FID.....	5-11
Figure 5-5. Well # 31-S-3 (observation well). Before and after MEOR treatment analysis of whole crude oil by GC-FID.....	5-12
Figure 5-6. Identification of tetradecanoic and hexadecanoic acid from asphaltine fraction of oil collected from well # 61-SX-3 by comparison with reference materials.....	5-13
Figure 5-7. Pyrolysis/GC/MS analysis of asphaltine fraction of oils collected from well #61-SX-3 before and 40 days after MEOR treatment.....	5-14
Figure 6.1. SEM image of Bar Margin facies of the Shannon Sandstone reservoir.....	6-19
Figure 6. 2. SEM image of isolated strain of Bacillus sp. from the mixed culture of MEOR bacteria utilized in this study.....	6-19
Figure 6. 3. Schematic design of microcosm with Shannon Sandstone.....	6-20
Figure 6. 4. SEM image of bacteria colonizing the surface of a quartz grain.....	6-21
Figure 6. 5. Bacteria concentrated in a pore throat between mineral grains in the Shannon Sandstone.....	6-21
Figure 6. 6. Mixed culture of MEOR bacteria colonizing the surface of a quartz overgrowth within an internal pore of the Shannon Sandstone after three days in a microcosm experiment.....	6-22
Figure 6. 7. Mixed culture of MEOR bacteria colonizing the surface of a clay-rich surface within an internal pore of the Shannon Sandstone after three days in a microcosm experiment.....	6-22

Executive Summary

This project was an interdisciplinary investigation of the enhanced oil recovery effects of a commercial microbial enhanced oil recovery (MEOR) system. The purpose was to investigate in parallel laboratory and field studies the response of a portion of the Shannon Sandstone reservoir to two single-well treatments with a commercial MEOR system, to investigate basic bacteria/rock interactions, and to investigate mechanisms of oil release. The MEOR system consisted of a mixed culture of hydrocarbon-utilizing bacteria, inorganic nutrients, and other growth factors. Parallel field and laboratory investigations into the effect and mechanisms of the treatment were carried out by independent principal investigators.

The Shannon Sandstone at the Naval Petroleum Reserve #3 (NPR #3), Teapot Dome Field, Wyoming, was the location of the pilot field treatment. Two producing wells were treated with MEOR materials. These wells and the surrounding 22 wells were monitored for production and microbiological changes over 16 months. Alpha Environmental Inc. supplied the biological treatment materials and carried out field treatment and microbiological portions of the research. NPR #3 staff provided logistical and production reporting support. Researchers at Ruska Laboratories and The University of Texas at Austin carried out basic laboratory research on oil chemistry, mechanisms of oil release, and bacteria/rock interactions.

The pilot area is a highly fractured offshore marine bar margin reservoir with a depleted solution gas drive. Wells are completed between -400 to -800 feet. Average daily oil production per well ranges from 0.5 to 2.0 BBLs.

The treated and adjacent observation wells showed production and microbiological perturbations that are attributed to the effects of treatment during the first four post-treatment months. Effects of treatment declined to background levels within four months of inoculation. No production response was recorded in control wells unaffected by microbial stimulation.

Laboratory research resulted in descriptions of colonization patterns of hydrocarbon-utilizing bacteria in the reservoir rock environment. Core-flooding research utilizing various components of the MEOR system did not result in the isolation of an oil-release mechanism or measure incremental oil recovery from cores at residual oil saturation to waterflood. Chemical analysis of pre- and post-treatment produced oil identified large organic acid molecules concentrated in the asphaltenic fraction of post-treatment oil, but not in the oil from untreated control wells. No significant changes were measured in the overall quality of the oil produced from MEOR treated wells.

SECTION 1

INTRODUCTION

Franz K. Hiebert
Alpha Environmental, Inc.

Many types of bacteria produce biochemicals that can be applied to oil reservoirs to enhance oil recovery. Microbial Enhanced Oil Recovery (MEOR) involves the injection of selected microorganisms and growth-enhancing chemicals into the reservoir, the transport, and growth of these cultures in-situ, so that their presence and biochemical activity will aid in enhancing production of residual oil (Donaldson, Chilingarian, and Yen, 1989).

MEOR is not a new concept, the roots of current research and field methods can be traced to the pioneering work of Beckmann (1926), Zobell (1947), and Kuznetsov (1961, 1962). During the past decade the U.S. Department of Energy (Office of Gas, and Petroleum Technology) has funded a program of MEOR research and demonstration projects that has carried the development of the field substantially forward (USDOE Progress Review Enhanced Oil Recovery, 1992). MEOR research and development is active internationally as well, with programs in England, Russia, Romania, China, Australia, Venezuela, Japan, Canada, and Norway. In addition to pure and applied research activity, several private companies in the United States, Russia, Australia, and England have commercialized MEOR processes and have field programs in progress (Abstracts, 4th International MEOR Conference, 1992). Two comprehensive review volumes focusing on the subject of MEOR have recently been published (Donaldson, Chilingarian, and Yen, 1989; Yen, 1990).

Several mechanisms of oil release have been postulated that result from microbial metabolism. Donaldson, Chilingarian, and Yen, (1989) summarized and correlated microbially generated products and their potential enhanced oil recovery effects as follows:

<u>Microbial Cause</u>	<u>EOR Related Effect</u>
Acids	Modification of reservoir rock
	Improvement of porosity and permeability
	Reaction with calcareous CO ₂ production

Gases	Reservoir repressurization
CO ₂ , CH ₄ , H ₂	Oil swelling
	Viscosity reduction
	Increase of permeability (carbonate dissolution)
Solvents	Reduce oil viscosity
alcohols,	
aldehydes	
ketones	
Surface-active agents	Lowering interfacial tension
organic acids	Emulsification
biosurfactants	
lipids	
Polymers	Mobility control
proteins	Plugging
polysaccharides	
Biomass	Selective or non-selective plugging
	Emulsification through adherence to hydrocarbons
	Modification of solid surfaces, e.g. wetting
	Degradation and alteration of oil
	Reduction of oil viscosity and oil pour point
	Desulfurization of oil

(After Janshekar, 1985)

For in-situ MEOR, microbial cultures must be kept alive and growing in the oil well, and in the reservoir. The reservoir must be evaluated and understood in terms of microbial ecology, and limiting factors on microbial growth either modified or somehow overcome.

The reservoir environment can be a hospitable or hostile environment for bacteria growth, depending on specific physical and chemical conditions. Some well-recognized barriers to microbial growth include high salinity, high temperature, low permeability to fluids, lack of critical inorganic nutrients such as nitrogen, phosphorous, potassium, and certain trace metals, lack of oxygen for aerobic bacterial utilization of hydrocarbon, or lack of fermentable organic substrate for anaerobic bacteria.

The MEOR system investigated and applied during this research program consists of a mixed culture of aerobic hydrocarbon-degrading bacteria, inorganic nutrients, and chemical additives to help overcome environmental and chemical barriers to microbial growth in the reservoir environment. The hypothesis of oil release is that biochemicals such as alcohols, aldehydes, and organic acids, produced during aerobic bacterial metabolism of alkanes, build up in reservoir pores and are concentrated at bacteria-fluid and bacteria-rock interfaces (Figure 1). These biochemicals act as solvents and surfactants which may decrease interfacial tension between oil and surrounding brine and rock just as in conventional micellar or surfactant chemical EOR operations (Lake, 1989).

Field demonstrations of this MEOR system indicated positive response of several types of stripper well operations to single well and enhanced waterflood treatment (DOE/BC/14014-9, Final Report April 1989; Portwood and Hiebert, 1992). The purpose of this project was to investigate in parallel laboratory and field studies the response of a portion of the well-characterized Shannon Sandstone reservoir at Teapot Dome, Wyoming to two single-well treatments with this MEOR system, to investigate basic bacteria/rock interactions, and to investigate mechanisms of oil release induced by this MEOR system.

Figure 1-1. Conceptual drawing of oil, brine, and MEOR bacteria in a water-wet oil reservoir. The oil release mechanism is postulated as follows: hydrocarbon-degrading bacteria transported by formation brines attach or concentrate at the fluid-rock interface. Bacterial metabolism of hydrocarbon substrates such as alkanes produce intermediate metabolic byproducts such as alcohols, aldehydes, and organic acids. These biochemicals act as solvents and surfactants which may decrease interfacial tensions just as in conventional micellar or surfactant chemical treatments. An incremental amount of the previously immobile oil may now be available to be swept to production wells in the oil/brine emulsion.

SECTION 2

REVIEW OF FIELD AND RESERVOIR DATA SHANNON SANDSTONE, TEAPOT DOME FIELD, WYOMING

Franz K. Hiebert
Alpha Environmental, Inc.

Introduction

The objectives of this review were to characterize the Shannon Sandstone reservoir as an environment for microbial growth, to guide the design of the MEOR field application, and to provide a basis for evaluating measurements of microbial transport and effect on oil production.

Teapot Dome Field

The Naval Petroleum Reserve No. 3 (NPR-3) covers approximately 9,500 acres in the southeastern edge of the Powder River Basin, 35 miles north of Casper Wyoming. NPR-3 is owned by the DOE and operated by the Director, Naval Petroleum and Oil Shale Reserves in Colorado, Utah and Wyoming (NPOSR-CUW) through a Management and Operations contract (Chappelle, 1988). NPR-3 is now a stripper field producing less than 3,000 BOPD and 12, 000 GPD natural gas liquids. The reserve was established in 1915, developed in the 1920's and was shut in for thirty years starting in 1928., NPR-3 was re-developed and has been operated for maximum efficient oil production rate since 1976. The Shannon Sandstone, the shallowest of the eight producing zones, was chosen as the reservoir within the Teapot Dome field for this MEOR program.

Shannon Sandstone

The Shannon Sandstone has been extensively studied by geologists, reservoir, and production engineers. Synthetic and detailed geologic studies and engineering reports

provide the basis of a reservoir model applicable to MEOR (Tillman and Martinsen, 1984; Ranganathan and Tye, 1986; Surtek, Inc., 1986; Core Labs, 1984).

Reservoir Characteristics

The Shannon's primary reservoir drive is solution gas and gravity drainage (Chappelle, 1988). A comprehensive study of the Shannon was performed by Surtek, Inc. (Obermyer, 1986) who estimated an IOIP of 144 MMSTB. Oil recovery as of January 31, 1988 is 4.6% of the IOIP, and primary production will result in only about 5.5% of the IOIP. The relatively poor recovery factor is the result of low reservoir energy, highly variable stratigraphy, and a faulted and fractured structure. Operators of the East Teapot Unit began a water flood of the Shannon in 1960 that was technically and economically unsuccessful because of channelling of water (Chappelle, 1988). All Shannon wells are now on ten-acre spacing. The Shannon sandstone has an extent within NPR-3 boundaries of approximately 3,500 acres and currently produces approximately 1,000 BOPD from over 350 wells (Chappelle, 1988). The initial pressure is estimated to have been 356 psi. Gas production data has been unavailable since 1981, when Shannon wells began to be vented to the atmosphere because of the low volumes of produced gas.

The economic limit for a Shannon well is approximately 0.22 BOPD. The reservoir economic limit is projected to be reached when a small group of wells is contributing a total of only around 12 BOPD. Primary Shannon production declines at a nominal rate of 17.7%/yr (Chappelle, 1988).

Previous EOR

Various enhanced oil recovery techniques have been tested in the Shannon Reservoir, all of which, except the steam flood, have been discontinued. Five EOR projects have been implemented including two gas injection projects, a steam-air in-situ combustion, an oxygen in-situ combustion, and a polymer-improved water flood (Figure 1). No incremental recovery was attributed to the gas injection tests. The polymer-

improved waterflood failed for economic reasons. A combined steam-gas injection system used a steam pre-heating phase, and was successful in producing incremental oil at costs that would eventually provide profitability of an expanded project. A steam-drive pilot was successful in producing incremental oil at costs sufficiently low to indicate the profitability of an expanded project. The process overcomes the poor quality of the reservoir rock to energize reservoir fluids.

The MEOR pilot project which is the subject of this report was located along the northern edge of section 3 and the southern edge of section 34 of the NPR-1 (Figure 2).

Geology

Chappelle (1988) described the Shannon as a member of the Upper Cretaceous Steele formation, which is a vertically stacked sequence of two sands and an intervening shale located 350 ft below the base of the Sussex sandstone. It is a bar sequence deposited in shallow water on a broad marine shelf. The average depth of the Shannon at NPR is 300- 400 ft, ranging from 200 to 1500 feet deep. The entire sand-shale sequence is about 160 ft thick.

The Shannon reservoir has four main facies. Listed in order of reservoir quality, they are: bar margin, interbar, bioturbated shelf sandstone, and bioturbated shelf sandstone and siltstone. These represent a sandstone which ranges from good to extremely poor reservoir quality, with porosity and permeability varying over a large range.

The productive interval of the Upper Shannon margin facies averages 12 ft thick; the Lower Shannon is a marginally productive interval consisting of Interridge sandstone facies averaging about 6 ft thick (Obernyer, 1986). Although the overall facies geometry is relatively constant throughout the pilot area, the internal units or subfacies within the facies vary vertically and laterally. Foot-by-foot descriptions of selected cores in the pilot

area include features 0.1 ft. thick and show a high degree of variability in the vertical sequence of internal features.

Structure

Teapot Dome field lies along a heavily faulted north-south anticline. The major portion of the Shannon production lies on the crest and the anticline's east flank. The MEOR pilot location is just to the east of the anticline crest.

The Shannon reservoir consists of horst and graben blocks perpendicular to the anticline axis. A high degree of natural fracturing is associated with these faults. Production information from previous EOR studies indicated channeling of injection fluids in a WNW-ESE and a general SSW direction (Obernyer, 1986).

Field observations in earlier pilot EOR projects indicated that directional flow paths other than along the fault orientations have strongly influenced pilot performances. High permeability sand lenses has been ruled out as a factor in causing directional flow throughout the reservoir because of the localization of the individual sand lenses (Obernyer, 1986). The MEOR pilot area is split between two structural blocks (Figure 3).

Facies

Four facies studied by Obernyer (1986) were recognized in the MEOR pilot area. They are :

A. Bar Margin Facies (BM)

1. medium-to fine-grained sandstones
2. presence of visible stratification in most sand lenses; high-angle cross-bedding predominates, rippled strata common
3. upper and lower contacts of sand lenses with adjacent bioturbated sandstones or laminated shales are sharp
4. total bar margin interval has less than 30% bioturbated sandstones; individual burrows are generally identifiable.

B. Interbar facies (I)

1. very-fine to fine-grained sandstone
2. structureless sand beds, little or no cross-bedding or rippling preserved
3. higher clay content than bar margin; lower permeability

4. predominantly gradational contacts between structureless sandstone beds and bioturbated sandstone beds.
5. Laminated shales are largely destroyed, showing evidence of partial to complete bioturbation
6. 30-75% of interval is bioturbated, individual burrows can be identified, but mottled bioturbation is pronounced.

C. Bioturbated Shelf Sandstone Facies (BSS)

1. very-fine-grained sandstone
2. high clay and silt content
3. 75-100% intensely bioturbated-mottled bioturbation

D. Bioturbated Shelf Siltstone Facies (BSSilt)

1. high clay content, some very-fine-grained sandstone
2. 100% intensely bioturbated-mottled bioturbation
3. no visible oil saturation.

Contacts between the facies are usually gradational. Occasionally, a sharp contact can be identified, such as where a bar margin directly overlays a bioturbated shelf sandstone facies. The stratigraphy of the two treatment wells, 61-SX-3 and 72-SX-3 is presented in relation to the local fault blocks in Figure 4.

Mineralogy and Fabric

Samples of BM/BSS facies transition and the BSS/Bsilt facies from a well 2000 ft south of the pilot area were studied by normal and fluorescence Petrography, X-ray diffraction analysis and SEM inspection. (Wilson, 1987). Fine-grained sandstone in the Lower Shannon contains significantly larger amounts of plagioclase and dolomite, whereas the coarser sandstone in the Upper Shannon has a greater abundance of quartz and chert. The Upper Shannon is classified as a sub-arkose, whereas the Lower Shannon was identified as a lithic arkose and arkosic litharenite (Tables 3 and Figure 5). All samples contain minor amounts of glauconite.

Reservoir quality is controlled largely by matrix content. The Shannon contains abundant matrix (>15%), and has low visible porosity (3.3 to 4.7%). Micropores (<0.001 mm) and mesopores (0.001 to 0.020 mm) are the dominant pore types.

The low content of kaolinite in all samples (Table 4) and low permeability in most samples indicate that migration of this component is unlikely to occur. Mud matrix and laminae containing mixed-layer swelling clays pose the most likely threat for formation damage.

The low permeability, high percentage of microporosity, and mineralogical composition of the Shanon facies do not represent major inhibiting factors for the application of the MEOR materials. However, the lack of energy drive in this reservoir represents a problem the proposed MEOR system cannot address. In order to free incremental oil, some sweep energy must be present in order to move the oil to the production wells. In recognition of the low drive energy of the pilot area, it was decided to treat each of two pumping wells with a "huff and puff" single well stimulation method (Yen, 1990), and observe 22 surrounding wells for evidence of microbial transport and/or effect.

References

- Obernyer, S., 1986, Geologic Evaluation of the Shannon Sandstone, Teapot dome Field, NPR #3, Natrona County Wyoming, SURTEK, Inc., Golden Colorado.
- Chappelle, H., 1988, Reserve Estimates: Naval Petroleum Reserve #3, Report to the Director, Naval Petroleum and Oil Shale Reserves in Colorado, Utah, and Wyoming.
- Ranganathan, V., and Tye, R. S., 1986, Petrography, diagenesis, and facies control on porosity in Shannon Sandstone, Hartzog Draw field, Wyoming, AAPG bull. v. 70, pp. 56-69.
- Tillman, R. S., and Martinsen, R. S., 1984, The Shanon shelf ridge complex, Salt Creek Anticline Area, Powder River Basin, Wyoming: SEPM special publication No. 34.
- Wilson, Michael, D., 1987, Reservoir quality analysis of three samples from the Upper and Lower Shannon Sands, Well #58-66, Teapot Dome, Natrona County, Wyoming, Core Laboratories, Inc.
- Yen, F. T. (Ed), 1990, Microbial Enhanced Oil Recovery: Principle and Practice, Boca Raton, CRC Press.

Table 2-1. Summary of Shannon Reserves (MMB,BCF)

IOIP	143.85
Oil production to date	6.59
Proved oil total	12.89
Unproved Oil probable	6.35
Unproved Oil Possible	25.38
IGIP	1.44
Gas production to date	0.28
Proved gas total	0.05

Table 2-2. Shannon Sandstone Reservoir Data

Productive depth: ft	300
Gross Pay thickness:ft	120
Permeability: md	0.1-1000
Porosity :%	19-21
Res. Temp: °F	60
Res pressure: psi	57
Ave. oil saturation: %	45
Initial gas solubility: scf/stb	10
Oil gravity: API	29-35
Oil viscosity at 60° F cp:	9-23.
Water cut : %	~40.

Table 2-3. Summary of petrographic examination of Upper and Lower Shannon facies from core taken near the MEOR pilot area (Wilson, 1987)

Framework Components	L. Shannon	L. Shannon	U. Shannon
(% framework fraction, reconstructed)	Bsilt	BSS	BM-BSS
Quartz species	45.7	57.1	64.9
Chert	9.5	11.4	14.9
Plagioclase	7.6	13.1	4.9
Potassium Feldspar	9.0	8.4	4.8
Galucontie	4.3	4.2	3.2
Micas and Chlorite	2.5	0.0	0.0
Micaceous Schist Fragments	4.3	1.3	3.7
Mud Clasts	0.0	0.8	0.0
Dolomite	15.7	1.3	1.1
Q	55.8	68.9	80.2
F	17.3	23.4	11.8
L	26.9	7.7	8.0
Pores (% total Rock)			
Intergranular Pores			
Macropores	0.3	6.7	2.0
Meso Pores	0.3	3.3	0.7
Micropores	2.7	2.7	2.0
Intragranular ores	0.0	0.6	0.0
Total viable porosity	3.3	13.3	4.7
Pore Fillers (%total rock)			
Carbonate cements	0.7	0.3	1.0
Quartz overgrowths	0.0	1.7	1.3
Pyrite	1.0	0.3	1.3
kaolinite	1.3	2.0	0.7
Summary Data			
Average Framwork size	0.13mm	0.17mm	0.20mm
Framework sorting	well	very well	well
Initial porosity (no matrix fill)	39.5	41.0	39.0
Intergranular volume	30.0	21.3	37.3
Compaction loss	9.5	19.7	1.7
Total Ductiles	11.1	6.4	7.0
Total Cement	3.0	4.6	5.3
Clay and Mud Matrix	23.7	4.0	27.3

Table 2-4. X-ray analysis of bulk and less than 5-micron sand fraction of samples from the Upper and Lower Shannon Sandstone.

Bulk (% grain volume)	L. Shannon		U. Shannon
	BSS	BSilt	BM-BSS
Quartz	78	67	55
Plagioclase	7	10	11
Potassium Feldspar	2	8	5
Dolomite	5	7	2
Siderite	1	0	0
Ankerite	0	0	3
Pyrite	1	1	1
Clay	7	6	22
less than 5 micron (%clay analysis)			
Kaolinite	13	28	41
Chlorite	18	26	49
Illite/Mica/Glauconite	44	24	0
Mixed layer smectite-Illite	24	21	10
Smectite	0	0	0

Figure 2-1. Structure map on the top of the Upper Shannon Sandstone, Teapot Dome Field, N. P. R. #3, Natrona County, Wyoming. Labeled areas indicate locations of previous EOR studies and the MEOR pilot area of this study. Each section = one square mile. Contours are 100 feet. Most wells are on ten acre spacing. (After Obernayer, 1986).

Figure 2-2. Well locations of the MEOR pilot project superimposed on top of local geologic structure.

**MEOR Study Area Contained
Within these Two Structural Blocks**

Figure 2-3. Schematic cross section from south to north through the MEOR pilot area.

Figure 2-4. Schematic facies distribution and structural relationship between the two wells treated with MEOR materials.

X-Ray Analysis

Figure 2-5. X-ray analysis of the three most prominent lithologic facies in the MEOR pilot.

SECTION 3

TEAPOT DOME FIELD WORK

Franz K. Hiebert, Arturo C. Cowes
Alpha Environmental, Inc.

Introduction

A survey of pre-treatment reservoir and fluid characteristics was conducted to establish a baseline for comparison with post-treatment changes. Samples of oil and water from each well in the pilot area were collected and analyzed to define pre-treatment conditions of oil chemistry and indigenous microbial population. Two pumping oil wells were treated on August 30, 1988 with the MEOR system.

Observation oil wells which surround the treatment wells were produced on their regular schedule. Oil, water, and gas production from each pilot well was recorded by periodic 24-hour flow tests in addition to statistical allocation calculations of fluid volumes produced by each well. The activity, population, and transport of hydrocarbon-degrading bacteria (HDB) in the oil reservoir was determined by analyzing fluids sampled from test wells for HDB population (i.e., determining the "well titer"). Oil production was correlated with HDB on a well-by-well basis.

Field work at Teapot Dome was organized into three categories:

- 1) Pretreatment activities,
 - a) site selection
 - b) sampling and analysis of reservoir fluids for background bacteria populations and analysis of compatibility of the MEOR bacteria with reservoir fluids

2) Treatment Activities, and

3) Post-Treatment Activities

- a) hydrocarbon bacteria population and distribution
- b) oil and water production
- c) evidence of bacterial by-products and chemical changes in produced fluids

Field work was carried out by staff of Alpha Environmental and the Naval Petroleum Reserve. The Director of the Naval Petroleum Reserve #3 provided logistical support at the Teapot Dome field. Samples of produced fluids were collected and sent to the laboratories of Alpha Environmental in Austin, Texas and to Ruska Laboratories in Houston, Texas for microbiological and organic chemical analysis. All oil, water, and gas production data was collected under normal operating procedures by the staff of Lawrence Allison-West, the operator of Teapot Dome under contract with the Department of Energy.

Materials

The MEOR system used for treatment of two wells consisted of four components:

- 1) an inorganic nutrient composed of

	<u>%</u>
monoammonium phosphate	9.9
urea	63.8
potassium nitrate	13.1
ammonium nitrate	11.3
micronutrients	1.9

- 2) "Alpha Biocatalyst" (trade name)

3) a corn starch substrate inoculated with a mixed culture of bacteria consisting of:

Acinetobacter genospecies 12,
Pseudomonas stutzeri,
Pseudomonas fluorescens,
Bacillus circulans,
Bacillus spore group I (not *B. cereus*)
Bacillus spore group II (four isolates), and
Coryneform sp.

4) Shannon reservoir formation water

The "Alpha Biocatalyst", a stimulant of microbiological activity, is an undefined media produced by the fermentation of a variety of types of complex organic matter, and is a proprietary formulation of Alpha Environmental Inc. The microbes are hydrocarbon-degraders; thus, the sole source of organic nutrient during the experiments is presumed to be oil and intermediate degradation products of oil.

Methods

Pretreatment

The choice of site for the MEOR treatment and observation research (pilot site) was restricted to areas not previously treated with EOR methods, and that offered a representative section of reservoir rock. An area was chosen at the crest of the northern end of the nose of the Teapot Dome anticline where oil was produced from each of the four main facies of the Shannon Sandstone (see Figure 1 of Section 2).

Two centrally located production wells were chosen as treatment wells and twenty two (22) surrounding production wells were selected as observation wells (Figure 1). Each treatment well is located in structurally isolated fault blocks, and there is no apparent fluid communication between analogous facies across the major block-forming faults. Previous experience with injected fluids in an area immediately to the south of the MEOR pilot site indicated that fluid flow was locally controlled

primarily by fracture networks (K. Cowan, personal communication). It was anticipated that MEOR treatment fluids injected at the treatment wells would migrate away from the well bores both in a generally radial pattern and directionally to the west and northwest along fracture zones perpendicular to major faulting. A majority of observation wells were located to the west of the treatment wells.

Prior to treatment, production fluids from each of the MEOR pilot wells were analyzed in order to determine the population level of indigenous total hydrocarbon-degrading bacteria. This data was used as a baseline for comparison of post-treatment population of total hydrocarbon-degrading bacteria in each well. Oil and water production record from each well were collected. Historical oil and water production and bacteria population was compared with the same post-treatment data through time.

Treatment

Wells #61-S-3, and 72-SX-3 were treated on August 30, 1988. The composition of the treatment for each was :

- 115 BBLS Shannon formation water,
- 5 BBLS Biocatalyst,
- 150 lbs dry bacteria (at a concentration of approximately 4.54×10^{14} bacteria/lb) and
- 5 lbs of inorganic nutrients.

The components were mixed, transported to the well site by tank truck and delivered to the reservoir through the well annulus by gravity feed. Both treatments took less than 30 minutes for fluid transfer from the tank truck to the well. The high rate of fluid flow into the well suggested that a larger volume of treatment fluids could have been applied, however, we have no estimate of the depth of initial fluid

penetration of the treatment into the reservoir. Both wells were shut-in for five days and then replaced on regular production pumping schedules. Surrounding observation wells were produced on their regular schedule.

Post-treatment

After treatment, samples of oil and water were collected at periodic intervals from each well to determine microbial population and distribution. Oil and water from each well was sampled on September 23, 1988, October 10, 1988, December 6, 1988, February 15, 1989, and March 15, 1989 and analyzed for population level of total hydrocarbon degrading bacteria (HDB). Populations were enumerated by serial dilution method and direct microscopic observation (Appendix 1). Duplicate control enumerations were performed on each sample.

Oil and water production data was collected from each well by two methods, 1) periodic 24-hour tests in which all fluids produced from a single well were collected in a separate tank and measured, and 2) monthly oil production figures for each well were calculated using an allocation algorithm developed by The Director of the Naval Petroleum Reserve #3 for Shannon Wells at Teapot Dome (Appendix 2).

Results

During the first three months after treatment, population levels of total hydrocarbon degrading bacteria increased by two or more orders of magnitude in 12 of the twenty-two surrounding observation wells. An irregular pattern of microbial first-arrival times at observation wells suggests that reservoir heterogeneities, including channeled fluid flow along fractures, controlled subsurface fluid and bacteria transport in the MEOR pilot area.

In September, twenty-three days after treatment, six wells (including the two treatment wells) had HDB populations which increased by two or more orders of magnitude over background levels. In October, thirty-three days after treatment, thirteen wells had HDB populations which increased by two or more orders of magnitude over background levels. In December, seventy days after treatment, only five wells showed any HDB population, and the remaining pilot wells showed zero population. Analysis of February samples confirmed the December findings of low to zero HDB populations in most wells. In some wells, the HDB population has fallen below pre-treatment levels. Table 1 presents population levels of HDB before and after MEOR treatment by well in the pilot area.

Chemical analysis of oil produced from the two treatment wells indicated a four-fold increase in organic acids known to be intermediate by-products of bacterial hydrocarbon oxidation concentrated in the asphaltene fraction of the oil (see Section 4).

Oil production results for the two treatment wells and for groupings of observation wells by bacterial activity level are presented in Figures 2 and 3. A "bacterially active well" is defined as one in which the level of total hydrocarbon-degrading bacteria population has increased by two or more orders of magnitude above the natural, pre-treatment background level. During the first three months after treatment, the thirteen bacterially active oil wells (including the two treatment wells) showed a trend of oil production above expected volumes based upon 24-hour test data (Figure 3a). Wells that did not experience an increase in bacterial population showed little to no change in oil production compared to past performance and to expected performance as defined by a decline function (Figure 3b).

Production data based upon allocation-derived production figures, tends to smooth the highs and lows of the 24-hour test data, but generally follows the trends derived from the active and non-active wells (Figure 4). Data collected after four months post-treatment do not show significant changes in long-term production trends, either above or below expected volumes (Appendix 3).

It is important to note that there is a large amount of natural variation in oil production volume in both the well test and allocation-based oil production data. Normal variations in production volume above and below the expected level are large and interfere with the interpretation of real production changes due to a specific treatment. The production results from bacterially active wells during the first three months establish a trend of increased oil production. The volume increase, however, did not exceed historically established margins of variation in the normal production data.

Discussion

In wells categorized as bacterially active, the increase in total oil production correlates with the total increase in HDB population during the first three months. The decline of oil production during the fourth-through-seventh-month period also correlates with the concurrent decline of the HDB population.

The sudden decline of microbial populations in the treatment and observation wells suggests that some chemical or environmental factor limited growth after four months of treatment. Several categories of factors could produce the observed results of sudden low bacterial populations.

The HDB may have exhausted an essential nutrient or growth factor in the reservoir environment and suspended metabolic and growth activity. If any essential growth factor becomes exhausted, or excessively diluted, microbial growth will cease and populations will decline through time. Crude oil, the carbon and energy source for the HDB in the reservoir, clearly is not the limiting factor. Inorganic nutrients such as nitrogen, phosphate trace elements, and oxygen are all essential chemical factors for metabolism. Any one or a combination of these factors may have been exhausted or restricted from bacterial use. Concentrations of nutrient levels through time were not measured.

Sampling techniques may also be responsible for an apparent drop in HDB population. A substantial population may exist in the subsurface but may not be captured in samples of well fluids. The community structure of the HDB inocula may adapt to reservoir conditions and change through time. The predominate type of bacteria in the HDB mixed community that was used as the well inocula may have shifted from suspended (in the reservoir fluid) to attached (to the surfaces of reservoir rocks). Evidence from batch reactor laboratory experiments with reservoir materials indicate that attached bacteria constitute an important element of the added HDB community (see Section 6). If bacteria attached to rock surfaces have become the dominate type in the reservoir during the seven months since treatment, sampling of well fluids may not provide a representative sample from which to determine an accurate population number.

Alternatively, a buildup of toxins, either natural microbial by-products or concentrated reservoir constituents, in the near-well bore environment may have curtailed HDB activity and population.

Conclusions

1. Increases in HDB population and increases in concentration of organic acids in produced fluids sampled during the first four months of the pilot suggest that microbial metabolism of hydrocarbon did occur in-situ, either in the reservoir or in the well bore.

2. Approximately half of the wells in the MEOR pilot area experienced at least a two order-of-magnitude increase in population after two central wells were treated with MEOR materials. HDB activity was either the result of the transport of added bacteria or the result of stimulation of indigenous bacteria by added nutrients.

3. HDB populations declined to pre-treatment levels four months after treatment.

4. During the four-month period in which the population levels of HDB were elevated, oil production began to increase in the "active wells". No evidence of perturbation in fluid production was evident in "non-active" wells. However, post-treatment oil production did not exceed historical normal variations in production rate over time.

Well #	7/7/88	8/29/88	9/23/88	10/10/88	12/6/88	2/15/89	3/15/89
Treatment							
61	0,0	0,0	5,5	4,4	1,1	1,0	1
72	0,0	4,4	8,7	8,7	0,0	0,0	0
Active-Observation							
68	1,2,4	3,2	5,5	0,0	0,0	1,1	1
78	2,2	0,0	2,2	2,4	0,0	0,0	1,2
31	0,0	1,1	3,3	2,2	1,1	1,0	0
51	0,0	3,3	2,2	4,5	0,0	0,0	1
71	1,1	0,0	0,0	0,0	0,0	1,2	1,2
33	1,0,0	0,0	0,0	8,7	0,01,0	0	
22	0,0	0,0	0,0	4,3	0,0	1,1	2,3
32	3,3	4,4	5,5	6,8	2,2	2,1	2
42	0,0	0,0	0,0	3,3	0,0	0,0	1,2
82	nd	0,0	3,2	8,7	0,0	0,0	1
63	0,0	0,0	1,1	2,2	0,0	1,0	0
34	0,0	0,0	nd	3,4	0,0	0,1	1,2
44	0,0	0,0	2,1	4,3	0,0	0,0	0
Non-Active Observation							
58	2,2	5,4	2,2	3,3	0,0	3,3	3
21	2,3,4	0,0	0,0	1,1	0,0	1,1	0,0
41	4,4	nd	2,2	1,1	1,2	1,1	1
52	3,3	1,1	0,1	3,3	0,0	0,0	0,1
62	0,0	2,2	3,2	3,3	0,0	0,1	1
53	0,0	0,0	0,0	0,0	0,0	0,0	1
73	7,7,5	0,0	0,0	4,4	1,1	2,2	0,1
64	0,0	2,0	1,1	2,2	0,0	0,1	1
45	0,1,1	0,0	0,0	0,0	0,0	0,0	0,1
Treatment							

Table 3-1. Population of total hydrocarbon degrading bacteria in MEOR pilot wells. Population concentration is reported as an order of magnitude of cells/ml of well fluid (i.e., 1×10^6 cells/ml is reported as 6). Multiple entries indicate duplicate analysis.

Figure 3-1. Well location map of the Alpha Environmental MEOR pilot area at Teapot Dome field, Wyoming.

24 HOUR TEST VOLUMES

Figure 3-2a and 3-2b. Pre- and post-treatment oil and water production (24 hour test volumes) with historical and predicted oil production decline curve for the two MEOR treatment wells in the Teapot Dome pilot area. Treatment dates are noted on the graphs.

Figures 3-3a and 3-3b. Oil and water production for "bacterially active" (3a) and "non-active" (3b) wells in the Teapot Dome MEOR pilot area. A "bacterially active" well is defined as one in which the level of HDB population has increased by two or more orders of magnitude above the natural, pre-treatment level. During the first three months after treatment, thirteen oil wells (including the two treatment wells) were measured as "active", and eleven showed no increased bacterial activity. Production is reported as allocated volumes, not twenty-four hour test volumes.

Figure 3-4. Oil and water production and population level of total hydrocarbon degrading bacteria from producing wells treated with the MEOR materials in late August, 1988. Population densities of bacteria are reported as an order of magnitude of cells/ml of well fluid (i.e., 1×10^6 cells/ml is reported as 6).

SECTION 4

LABORATORY CORE-FLOOD TESTING OF A MICROBIAL ENHANCED OIL RECOVERY PROCESS UNDER ANAEROBIC CONDITIONS

Bruce Rouse, Franz K. Hiebert, Larry W. Lake

Summary

Microbial enhanced oil recovery (MEOR) is a potentially attractive way to recover additional or incremental oil from a reservoir beyond conventional operations. The objective of this work was to determine the effectiveness of a commercial MEOR system in controlled laboratory corefloods. The experiments were carried out as support for a field test conducted in the Shannon Formation of the Teapot Dome reservoir.

Two sets of coreflood experiments were designed in order to carry out this research. The first set was designed to determine the incremental oil production of each of the components of the MEOR system, both individually and in all possible combinations. The second set of experiments attempted to maximize the opportunity for incremental oil production to occur. The results indicate that, under the conditions tested, there was no incremental increase in oil recovery as a result of the MEOR system.

Introduction

Microbial enhanced oil recovery (MEOR) is a potentially attractive way to recover additional or incremental oil from a reservoir beyond conventional

operations. The process is inexpensive, and many various approaches to MEOR have been field tested.^{1,2} Documented laboratory work is considerably rarer^{3,4}; one of the objectives of this work is to report on such work.

Microbial enhanced oil recovery can occur through the in situ formation of normal metabolic products that result from the use of a nutrient by microbes.⁴ The supplier of the MEOR system proposed the hypothesis that the mechanism for oil production is the formation of metabolic byproducts such as alcohols, aldehydes, and organic acids from the alkane fraction of crude oil. The fatty acids then act as a surfactant to establish a micellar flood to increase oil production as in conventional enhanced oil recovery.⁵

The MEOR fluid system under investigation here consists of three components: 1) an inorganic nutrient, composed of monoammonium phosphate (9.9%), urea (63.8%), potassium nitrate (13.1%), ammonium nitrate (11.3%), and micronutrients (1.9%); 2) a biocatalyst and 3) a powder of microbes and starch consisting of acinetobacter genospecies 12, pseudomonas stutzeri, pseudomonas fluorescens, bacillus circulans, bacillus spore group I (not B. cereus), bacillus spore group II (four isolates), and coryneform sp. The biocatalyst is a proprietary formulation. The microbes are hydrocarbon-degraders; thus, the sole source of organic nutrient during the experiments is presumed to be the oil itself.

Experimental Procedures

Prior to injection in the cores, the inorganic nutrient and microbial powder were mixed individually at concentrations three times that required for the final injection and the microbial sample was allowed to re-hydrate. Injection of the microbial slurry was done within two to three hours after mixing to provide the

microbes with a hydrocarbon nutrient source as soon as possible, since there is no available nutrient in the slurry. The first set of experiments was designed to test the individual and combined effects of the separate components of the system.

A series of eight 2" x 2" x 1' (5 cm x 5 cm x 30 cm) Berea cores were dried at 70°C for 48 hours and prepared by applying an epoxy coating and Plexiglass end-pieces. Each core was evacuated for 12 hours and saturated with sterile, filtered sea water. During this step we determined the volume of fluid required to completely saturate the core in order to determine the pore volume and porosity. Each core was then flooded, at high rate, with decane until no further brine was produced. The residual brine saturation for each core was calculated from the recovered effluent brine volumes. The cores were then flooded individually with the same sea water (filter sterilized Gulf of Mexico sea water) used for saturation until all oil production was complete. Residual oil saturations were calculated from the volume of oil produced from each core. These results are tabulated in Table 1. This procedure has become a standard in our laboratory for core flooding experiments.⁶⁻¹¹

We then subjected each core to a different experimental parameter as follows:

Core 1 - One pore volume (P.V.) of the inorganic nutrient material as a single component.

Core 2 - One P.V. of the biocatalyst as a single component.

Core 3 - One P.V. of a mixture of inorganic nutrient and biocatalyst.

Core 4 - One P.V. of the microbial slurry as a single component.

Core 5 - One P.V. of the microbial slurry and the inorganic nutrient.

Core 6 - One P.V. of the microbial slurry and the biocatalyst.

Core 7 - One P.V. of the three component system using the inorganic nutrient, biocatalyst and microbial material.

Core 8 - This core was flooded to a new residual brine using the Shannon crude oil and then flooded back to a new residual oil saturation using sea water. This was followed by injection of 1.1 P.V. of the three component system.

Cores 1 through 6 used sea water for the aqueous media to ensure that the final concentration of each component was constant for each of the cores. After incubating the cores at room temperature (25°C) for one week to provide an opportunity for microbial activity to occur, we waterflooded each of the cores using sea water at flow rates between 20 and 25 ft/day. The pump was set to a fixed metering rate; the actual displacement rate depended on the pore volume of the individual core samples.

After completion of this series of tests, we flooded core 8 with fresh water, followed by another sea water flood and then injection of a 0.2 P.V. slug of surfactant. The composition of the surfactant slug was 3 wt % TRS10-410, 3 wt %, isobutyl alcohol and 0.5 wt % NaCl. This composition was selected because of the considerable experience we have accumulated using this formulation in our laboratories.^{6-9,12,13} The surfactant slug was followed by a fresh water flood. The purpose of this test was to confirm that, in fact there was oil remaining in the core.

Since there was no incremental oil recovery in these tests, we prepared a second set of cores with the intent of bringing about the very best combination of circumstances for oil recovery. These cores were saturated, oil flooded to residual brine with Shannon crude and then flooded to residual oil with sea water. The detailed treatment regimens applied to these cores were as follows:

Core 9 - A pre-flush of 6 P.V. of a concentrated solution (a ten-fold or 10x increase over that used before) of the inorganic nutrient component was injected into the core to ensure that any removal of the inorganic nutrient by

reaction with core components was satisfied prior to introduction of the microbial component. A 1 P.V. slug of fermenter broth was used to ensure that the microbial culture was viable. To provide additional time for any microbial reaction to occur, the core was incubated at room temperature for 3 weeks. At the conclusion of the incubation period the core was flooded with fresh water rather than sea water, an action that would provide the salinity gradient necessary to produce and stabilize any oil bank front produced by the surfactant.

Core 10 - This core was pre-flushed with a 3.6 P.V. solution of the concentrated (10x) inorganic nutrient solution prior to injection of 1 P.V. of the microbial slurry prepared from dried microbes. The incubation time was increased to eight weeks before flooding with fresh water.

Cores 11 and 12 - These cores were treated the same as cores 9 and 10, respectively, except there was no inorganic nutrient pre-flush.

Results

Table 1 summarizes the results of the tests from all twelve of the cores.

Figures 1- 5 show the fractional flow of oil, fraction of the initial oil saturate oil in place and, where available, the pressure drop across the core as a function of the volume of fluid injected. The sequence of fluid used for each stage in the core flood is indicated across the top of each figure.

The most notable feature of all the experiments is the complete lack of any produced oil in excess of waterflooding. In the one core sample in which there was a small amount of additional oil produced (core 9) the time at which the production occurred is inconsistent with it being caused by microbial action, Figs. 1 and 2. The experiment produced no oil until after injection of slightly more than 1 P.V. of fresh water, at which time the pressure drop across the core was nearly twice that seen during the flood to residual oil saturation. Because of the increased pressure there is an additional capillary desaturation effect to mobilize a small amount of oil from the core.⁵ Further, comparison of the production history and oil cut results of core 9

(Fig. 2) with the production history and oil cut results for the TRS10-410 surfactant slug in core 8 (shown in Fig. 1) indicates that the normal surfactant flood results in a well defined oil bank which is produced early in the flood rather than late as was observed in core 9.

Discussion

Since we used cores 1 through 7 to determine the incremental oil recovery of decane as a base case, the effluent volumes were collected in bulk rather than in a fractional manner. The almost complete lack of oil recovery was somewhat unexpected and we initially attributed this to the lack of metabolic substrate diversity, i.e., the use of pure decane for the first 8 core studies. The result observed for core 8, however, in which crude oil was the carbon source(introduced following the decane flush), indicated that even with a variety of substrate moieties present, there was no apparent increased oil production. We considered several hypotheses to explain the lack of oil recovery.

1. The microbes had produced a surfactant from the substrate but the salinity gradient of the sea water flood prevented a stable microemulsion from forming and hence the oil recovery did not occur. In order to test this hypothesis, we flooded core 8 with fresh water. Such flooding should have activated any surfactants in place¹⁴, but the action did not result in the production of any additional oil from the core.
2. The post-incubation sea water flood flushed all of the surfactant from the core before it could mobilize oil and even before the salinity gradient occurred. Such a possibility means that the generated surfactant is in the "lower phase" (Type I)

microemulsion form, an eventually that is very unlikely, given the high salinity of sea water. However, to eliminate this possibility we used fresh water as the post flush in all subsequent experiments to establish the requisite salinity gradient necessary for the production of a stable micellar flood.

3. There would, of course, be no oil production if there were no residual oil in the core. However, the presence of the initial oil in place was confirmed by the injection of a surfactant slug with an appropriate salinity gradient. The recovery by this surfactant slug was entirely consistent with prior experience and consistent with the material balance calculations of the residual oil.

4. The microbes present in the core were non-viable. Several possible causes exist for this: the original powdered microbes could be dead, the microbes failed to reproduce or the microbes were killed within the core. In order to determine if the microbes were viable within the core we had several effluent samples from core 8 assayed for the presence of a viable culture. The results of these assays indicated the presence of a viable microbial population in all of the effluent samples tested. These results indicate that the microbes maintained an active condition throughout the experiment.

5. The microbes had insufficient residence time in the incubation period to generate enough surfactant to reach the critical micelle concentration (CMC). A surfactant concentration must be greater than the CMC for it to be active. This possibility was tested in the second set of experiments by increasing the incubation time prior to the waterflood.

6. It is possible that the chemical nature of the permeable medium was such that the inorganic nutrient materials were reacting with the rock matrix and being converted into a form which was unusable by the microbes. To test this, cores 9 and

10 were flooded with several pore volumes of a concentrated inorganic nutrient solution to satisfy any chemical reaction sites within the rock matrix. This flood was done prior to the introduction of the microbial culture to provide an optimized condition for microbial growth.

7. Although the assay indicated that the core samples contained a viable culture of microbes, some concern developed that the microbes present might not represent a strain which could use the Shannon crude as a substrate for the production of surfactants. The initial inoculum for the fermenter growth and subsequent harvested microbes represent a mixed culture. During the growth process a certain amount of competition will occur which will exert a selection pressure on the culture that will tend to result in the selective growth of certain strains of the microbes. If the crude oil used for the fermentation growth of the dried microbes was such that the selection pressure on the microbes was away from the Shannon crude components, even though the microbes were viable, they would not produce surfactant. To eliminate this, two new samples were obtained for the second set of experiments. One of the samples was a new dried powder which had been harvested from a different fermentation culture, and the second was a fresh mixed culture broth direct from the fermenter that was injected within four hours to insure that the microbial culture used was completely viable.

8. The third component of the system, the biocatalyst, could also account for the lack of response. A fresh sample of the stabilized biocatalyst was used in the second set of experiments.

The experiments done using cores 9 through 12 were designed to eliminate these as possible causes for the failure to produce additional oil from the previous

cores. The results of these experiments (Figs. 2 - 5), however, were again clearly negative.

The first two cores, which were subjected to a 3-week incubation period before waterflood, did not exhibit incremental oil recovery over the residual (Figs. 2 and 4). Based on this, the incubation period was increased to 8 weeks to provide a sufficient time frame for any surfactant production.

Core 9 did show a slight amount of oil production, however, this production did not occur until after injection of more than a full pore volume of fresh water. During this injection the pressure drop across the core increased continuously, probably because of pore plugging from either migration of fines or clay swelling (in general, there was no significant increase in pressure drop in these experiments). The result of increasing the pressure drop is to cause an increase in capillary number which results in the mobilization of a small amount of oil. Although the capillary desaturation curve using this particular crude oil in Berea sandstone was not measured, the time of the production of the oil from this core is inconsistent with it being produced as a result of a surfactant flood.

The results of the fresh water flood for cores 10 and 12 showed that even after eight weeks there was no evidence that the process resulted in any incremental oil recovery (Figs. 3 and 5). The extremely small amounts of produced oil noted can be attributed to a variety of other causes such as flushing a small amount of oil trapped in the recessed portion of the Plexiglass end-piece or a slight change in the pressure gradient.

The 3% TRS10-410 surfactant flood recovery for core 8 of these experiments clearly demonstrates that the micellar flood mechanism has a high efficiency under the conditions used. There remains the problem as to why the experiments using the

microbial flood failed, even when the conditions used were adjusted to maximize the potential for success.

The most likely explanation would seem to be that the conditions within the core could quickly become anaerobic. For the production of fatty acids from an alkane substrate it is necessary to metabolically introduce two oxygen atoms into the molecular structure (see Fig. 6). If we assume that 1) the CMC for the fatty acids is in the range of 1 mM/L and 2) that 100% of the available oxygen is used for the production of the surfactant, then a stoichiometric calculation shows that 32 mg/L of oxygen are required for the CMC to be reached. The solubility of a 100% atmosphere of oxygen at 25° C is about 45.2 mg/L, which, when corrected for a 20% oxygen atmosphere, is reduced to 9 mg/L of oxygen. The required oxygen for the assumed CMC exceeds the available oxygen by a factor of 3.5.

The assumptions made above regarding the minimum oxygen needs for the system are extremely liberal. Because of the type of surfactant being generated, it is likely that the CMC suggested above, which is in the range required for petroleum sulfonates and some ethoxylated surfactants^{15,16} is probably a factor of ten less than that which would be required. These low-CMC types of surfactants were specifically developed for their ability to generate the low interfacial tension necessary for solubilization of oils in enhanced oil production. The fatty acid salts will act as surfactants in fresh waters to solubilize small quantities of oils; however, in hard water, concentrated brines, or at high oil concentrations, their effectiveness is greatly reduced.

The assumption also relies on a 100% utilization of the available oxygen for the production of surfactant. In general biological systems have an energy conversion efficiency of less than 50% for all aspects of the metabolism. This feature requires an

even greater oxygen supply than originally proposed. The proposed mechanism for the MEOR system also suggests that the microbial population is in a growth phase or, at minimum, a stable population. The basic cellular energy needs for such a system exerts an additional oxygen requirement.

Finally, it is not likely that all of the fatty acids produced would be available for oil recovery. This will only be true if the fatty acids are present in the form of neutral salts of the acids. If they are present as free fatty acids there will be some loss to the reaction of the acids with the minerals within the rock itself, for example CaCO_3 . Multivalent salts of fatty acids have extremely limited solubility and would not be available to reduce the oil-water interfacial tension.

There is no clear evidence that Fig. 6 is the actual metabolic pathway, since this has not been studied in detail and some alternative metabolic pathway may be used which enables the system to work. It is well known that many microbes, and even multi-cellular organisms, have the capacity to undergo anaerobic metabolism over a prolonged period. Examination of known alternative metabolic pathways, however, are not encouraging.

The most common anaerobic microbial mechanism is the anaerobic production of CO_2 and alcohol. A suggestion that this metabolic pathway could produce enough carbon dioxide to improve reservoir sweep must consider that the oxygen present in the evolved gas is derived from the use of a carbohydrate (which contains the oxygen) as a substrate rather than a hydrocarbon. Of the twelve cores used in these experiments, only one, core 12, showed any indication of a pressure build up within the core during the incubation period. There was no incremental oil recovery in this core. If the microbes were using a carbohydrate source, for example the starch used in the harvesting process, as an energy source for anaerobic

metabolism, this core should have shown some incremental oil recovery. The lack of pressure build up in all but one of the cores, combined with the lack of oil production in the one core which did exhibit a pressure build up would indicate that this is not a significant consideration.

The second anaerobic mechanism that occurs with some frequency is that of sulfur reduction by certain groups of bacteria. The absence of hydrogen sulfide in the core samples was the norm with only core 5 showing evidence of the presence of H_2S . We observed no incremental oil recovery for this core although the presence of hydrogen sulfide was apparent from the odor of the gas released. Since hydrogen sulfide is the end-product of sulfur reduction, the absence of increased oil production in the presence of this metabolic pathway seems to exclude it from consideration as the requisite energy source.

Anecdotal reports suggest a change in the composition of some crude oils during surface clean up operations which could indicate a decreasing alkane chain length. Although this is consistent with a beta-oxidation process in the metabolism of free fatty acids, there are several problems with this as a metabolic pathway. The first remains that of the oxygen debt of the system to produce the fatty acids since this metabolic pathway requires the presence of a carboxylic acid moiety to initiate the reaction. The second difficulty is that, as the two carbon units are removed from the fatty acid, the chemical nature of the remaining carbon chain remains unaffected, i.e., it is still in the form of the fatty acid. If beta-oxidation is involved then the carbon chains would not be present as alkanes but rather as fatty acids.

Conclusions

There is no experimental evidence that under the conditions tested the microbial enhanced oil recovery process used here results in oil production in excess of that provided by waterflooding. The most likely cause for this failure is the absence of enough oxygen to generate either surfactants or polymers in situ.

Acknowledgements

Much of this work was supported by subcontract No. 19-88BC14205.00 from the U.S. Department of Energy through the Alpha Environmental Co., which also supplied the MEOR system. There was additional support supplied by the Enhanced Oil Recovery Program of the Center for Petroleum and Geosystems Engineering at The University of Texas at Austin at which Larry W. Lake holds a Shell Distinguished Chair.

References

1. Knapp, R.M. et al.: "Microbial Field Pilot Study," Final Report DOE/BC/14084-6, DE8900072, Department of Energy, (January 1989) quarter ending March 31, 1988.
2. Lazar, I.: "MEOR Field trials carried out over the World during the last 35 years," Microbial Enhancement of Oil Recovery - Recent Advances, E.C. Donaldson, (ed.) Elsevier, Amsterdam, NL (1991) 31.
3. Bryant, R.S.: "Laboratory Support for MEOR Field Projects," Progress Review DOE/BC 87/1, DE87991239, Enhanced Oil Recovery: Contacts for field projects and supporting research, Department of Energy, (1986) quarter ending Dec. 31, 1986.
4. Collected Papers: Microbial Enhanced Oil Recovery, E.C. Donaldson, G.V. Chilingarian, and T.F. Yen (eds.), Elsevier, Amsterdam, NL (1989).
5. Lake, L.W.: Enhanced Oil Recovery, Prentice-Hall, Inc., Englewood Cliffs, NJ (1989).

6. Camilleri, D.: "Micellar Polymer Flooding Experiments and Comparison with an Improved 1-D Simulator," M.S. thesis, The U. of Texas, Austin (1983).
7. Delshad, M.: "Measurement of Relative Permeability and Dispersion for Micellar Fluids in Berea Rock," M.S. thesis, The U. of Texas, Austin (1981).
8. Delshad, M.: "Relative Permeability and Dispersion Measurements for a Three-Phase Micellar/Polymer Mixture," M.S. thesis, The U. of Texas, Austin (1984).
9. Delshad, M.: "A study of Transport of Micellar fluids in Porous Media," Ph.D. dissertation, The U. of Texas. Austin (1986).
10. Pope, G.A. et al.: "Simulation of Heterogeneous Sand Stone Experiments Characterized Using C.T. Scanning," paper SPE 21757 presented at the 1991 SPA Western Regional Meeting, Long Beach, CA, March 20-22.
11. Wreath, D.G.: "A Study of Polymer Flooding and Residual Oil Saturation," M.S. thesis, The U. of Texas, Austin (1989).
12. MacAllister, D.J.: "Measurement of Two- and Three-Phase Relative Permeability for Micellar Fluids in Unconsolidated Sand," M.S. thesis, The U. of Texas, Austin (1982).
13. Prouvost, L., Pope, G.A., and Rouse, B.A.: "Microemulsion Phase Behavior: A Thermodynamic Modeling of the Phase Partitioning of Amphiphilic Species," SPEJ (Oct. 1985) , 693-703.
14. Nelson, R.C., and Pope, G.A.: "Phase Relationships in Chemical Flooding," SPEJ (1978) 19, 325.
15. Scamehorn, J.F., Schechter, R.S., and Wade, W.H.: "Adsorption of Surfactants on Mineral Oxide Surfaces from Aqueous Solutions, I: Isomerically Pure Anionic Surfactants," J. of Colloid and Interface Science (1982) 85.
16. Trogus, F.J. et al.: "Adsorption of Mixed Surfactant Systems," J. Pet. Tech. (1979) 31, 769.

Table 4-1. Summary of results of 12 core floods using decane and Shannon crude oil in Berea sandstone cores. Three different bacterial samples were used (see text) and soak times varied from 1 week to 8 weeks. The decrease in S_{or} indicates the % of the original oil in place recovered as a result of the microbial activity with the exception of the surfactant flood in core 8 which was done using a 0.2 P. V. slug of commercial surfactant.

CORE	TREATMENT	Porosity (%)	$S_{wr}(\%)$	$S_{or}(\%)$	Decrease in $S_{or}(\%)$	Oil used	Soak time weeks	Permeability md (Brine)	Permeability md (oil)
CORE 1	Inorganic Nutrient	20.78	44.26	23.73	0.00	Decane	1		
CORE 2	Biocatalyst	21.62	43.75	38.75	0.00	Decane	1		
CORE 3	Inorganic Nutrient + Biocatalyst	20.88	44.91	30.75	0.00	Decane	1		
CORE 4	Bacteria	23.73	45.43	29.66	0.65	Decane	1		
CORE 5	Inorganic Nutrient + bacteria	21.31	43.78	30.1	0.00	Decane	1		
CORE 6	Biocatalyst + Bacteria	20.53	43.69	32.04	0.65	Decane	1		
CORE 7	Inorganic Nutrient + Biocatalyst + Bacteria	20.83	45.37	30.21	0.00	Decane	1		
CORE 8	Pre-test with decane Inorganic Nutrient + Biocatalyst + Bacteria	23.01 (44.88)	43.23	30.75	0.00	Decane Shannon	1		
	3% TRS10-410/3% IBA/0.5% NaCl				26.26				
CORE 9	6 p.v. 10X Inorganic Nutrient - Fermenter Broth	19.59	37.82	38.19	1.04	Shannon	3	740	680
CORE 10	3.6 P.V. 10X Inorganic Nutrient - slurry	21.27	35063.	40.22	0.14	Shannon	8	900	830
CORE 11	Fermenter Broth	20.43	36.41	40.55	0.29	Shannon	3	670	610
CORE 12	Bacterial slurry	20.98	35.27	41.91	0.00	Shannon	8	790	665

Figure 4-1. Production results for core number 8. Flooding sequence is as shown on the figure. Bacterial injection was with re-constituted powder. Soak time was 1 week. Incremental oil production by the surfactant began shortly after the start of the surfactant flood, which indicates a well-developed oil bank.

Figure 4-2. Production and pressure drop data (normalized to pre-bacterial conditions) for core number 9. Core had been pre-flushed with 6 P. V. of a 10X inorganic nutrient solution prior to oil flooding. Bacterial injection was with fresh fermenter broth. Soak time was 3 weeks. No incremental oil drop production occurred until after a complete pore volume of fresh water had been injected and the pressure had risen excessively. Pressure is normalized to the initial water flood values.

Figure 4-3. Production and pressure drop data (normalized to pre-bacterial conditions) for core number 10. Core had been pre-flushed with 3.6 P. V. of a 10X inorganic nutrient solution prior to oil flooding. Bacterial injection was with re-constituted powder. Soak time was 8 weeks. Pump failure during bacterial injection necessitated injection at constant pressure for the latter part of this flood.

Figure 4-4. Production and pressure drop data (normalized to pre-bacterial conditions) for core number 11. No pre-flush was used. Bacterial injection was with fresh fermenter broth. Soak time was 3 weeks. Pressure data was lost during fresh water injection because of technical difficulties.

Figure 4-5. Production and pressure drop data (normalized to pre-bacterial conditions) for core number 12. No pre-flush was used. Bacterial injection was with re-constituted powder. Soak time was 8 weeks. Bacterial injection was done at constant pressure.

Figure 4-6. Hypothetical metabolic pathway for microbial formation of a fatty acid surfactant.

SECTION 5

CHEMISTRY OF OIL PRODUCED BEFORE AND AFTER MEOR TREATMENT AT TEAPOT DOME FIELD, WYOMING

John A. Zumberge and Franz K. Hiebert

Summary

Six samples of oil collected before and after MEOR treatment from three wells in the MEOR pilot area were analyzed by GC-FID, and pyrolysis/GC/MS to determine chemical characteristics of the oil and determine if metabolic byproducts of microbial metabolism of oil were present. No significant changes in the chemistry of the bulk produced oil were found. Fourfold increases in fatty acids were measured in the asphaltene fraction of post-treatment oil. Acetic and hexanoic acids were identified in the post treatment oil, but not in pre-treatment oil.

Introduction

Bacteria utilized in this MEOR pilot treatment are known to degrade hydrocarbons (Dunn, Swannell, Scholes, and Colcomb-Heiliger, 1990). In the most general terms, hydrocarbons are metabolized by bacteria via a sequence of oxidations to the corresponding alcohol, aldehyde, and monobasic fatty acid (Singer and Finnerty, 1984). Fatty acids can be transported into the extracellular environment or are further degraded within the cell to acetyl-CoA and ATP via the beta-oxidation pathway. Acetyl-CoA is then available as fuel for the Krebs-cycle. Each oxidation step is catalyzed by highly specific enzymes.

The microbial utilization of crude oil in the well bore and reservoir environment may change characteristics of the chemistry and/or molecular structure of certain fractions of the produced oil. Evidence of microbial activity in the down-hole environment may be investigated by analyzing produced oil for specific intermediate metabolic by-products of microbial metabolism of hydrocarbon.

Samples of crude oil produced from wells 61-SX-3, 78-SX-3, and 31-S-3 in the Teapot Dome Shannon Sandstone MEOR Pilot area were collected before and after treatment and analyzed by GC/FID and pyrolysis/GC/MS. The purpose was to:

1. characterize the oil prior to treatment, and
2. analyze the post-treatment produced oil for any alterations in the oil chemistry and for evidence of metabolic by-products of bacterial oil metabolism.

Methods and Materials

Three wells, 61-SX-3, 78-SX-3 and 31-S-3, were selected for oil sampling for chemical analysis (Fig.1). Well 61-SX-3 is located at the down-dip end of the MEOR pilot area and is one of two wells directly treated with MEOR materials. Well 78-SX-3 is an observation well (not treated with MEOR materials) located approximately 1000 feet northwest and downdip of Well # 61-SX-3, and in the same fault block. Well 31 -S-3 is an observation well located 2000' west of Well 61-SX-3, updip and across a fault with a throw of approximately 20 feet.

Samples of oil were collected from each well prior to treatment on July 8 and August 29, 1988. Oil samples were first analyzed to characterize the extent of natural biodegradation that existed prior to treatment with the MEOR materials. Samples of whole crude were analyzed using a PYRAN thermal extraction-GC-FID system to

determine n-paraffin (n-alkane) distributions and isoprenoid ratios (pristane/phytane). These parameters aid in the assessment of the degree of natural bacterial degradation. Aerobic bacteria tend to consume n-alkanes preferentially to branched alkanes (e. g. isoprenoids) and short chain alkanes over longer-chain alkanes.

Results

The overall distribution of n-alkanes, isoprenoids, and light ends among the oil from the three wells prior to treatment is similar (Fig. 2). The less-than n-C16 alkanes are greatly depleted relative to the more waxy components (n-C17+) and the isoprenoid pristane (Pr) is more abundant than n-C17. These oil samples have experienced natural mild biodegradation. Moderate biodegradation would cause complete removal of all n-alkanes where as severe biodegradation would also result in the loss of isoprenoids and some cyclic hydrocarbons. Invasion of the Shannon reservoir by oxygenated meteoric waters may have supported limited bacterial oxidation of the Shannon crude.

Treatment of Well #61-SX-3 occurred on August 30, 1988, and consisted of 200 BBLS of fluid with a mixed culture of hydrocarbon utilizing bacteria, inorganic nutrients, and organic chemicals (described in detail in the Field Methods section). The concentration of bacteria in the treatment fluid was approximately 1×10^{10} cells/ml. Post-treatment samples for comparison analysis were collected on October 10, 1988, forty days after treatment. Well 61-SX-3 was considered to have been biologically affected by the MEOR treatment, since the population level of total hydrocarbon utilizing bacteria (THUB) increased over two orders of magnitude above its background measurement. Well 61-SX-3 stayed active until December, 1988 (Table 1). Well 78-SX-3 was not considered "biologically active" after treatment.

Well 31-S-3 did show a two order-of-magnitude THUB increase in the first month following treatment of well 61-SX-3, but gradually tapered off in population level until December, 1988. All wells were found to have fallen to original low background levels of THUB populations by December, 1988.

GC-FID analysis of whole crude oils collected from the three wells forty days after treatment showed no major differences from pre-treatment results (Fig. 3, 4, 5). pristane/phytane, pristane/n-C17, and phytane/n-C18 ratios were calculated for each well before and after treatment and compared. No significant differences in isoprenoid ratios are apparent for the oils produced after bacterial treatment with respect to oils produced prior to treatment in the observation wells. In oil from treatment-well 61-SX-3 the Pr/n-C17 ratio declined from 1.30 to 1.27, which suggests a small degree of biodegradation above background levels (Table 2). MEOR treatment did not cause a substantial effect on the chemistry of the bulk oil produced from the treatment or observation wells during the forty day period of examination.

The asphaltene fraction of oil collected from well #61-SX-3, before and after MEOR treatment was collected and analyzed to determine if MEOR treatment contributed to changes in this fraction. The asphaltene fraction of crude oil is defined as that fraction which is insoluble in n-heptane solvents. Nitrogen, sulfur, and oxygen compounds as well as complex polar organic compounds are found in the asphaltene fraction.

Asphaltenes were separated from whole crude oil by precipitation with n-heptane solvents. The precipitates were analyzed with Ruska Instrument's PYRAN system, utilizing a standard sequential pyrolysis/GC/MS analyses. Small amounts of dodecanoic (C12), tetradecanoic (C14), hexadecanoic (C16), and octadecanoic (C18) fatty acids were identified in the oil collected prior to treatment. Unknown acids were

identified by comparison with known standards (Figure 6). Analysis of oil collected forty days after MEOR treatment indicate a four-fold increase in dodecanoic, tetradecanoic, hexadecanoic, and octadecanoic acids. In addition, hexanoic (C6) and acetic acid (C2) were identified in the post-treatment samples (Fig. 7).

Discussion

The activity of the MEOR bacteria introduced into well 61-SX-3 is postulated to occur at the oil/water interface within reservoir pores. Metabolism of hydrocarbon requires the presence of water. Therefore the volume of oil affected by microbial metabolism in relation to the bulk volume of oil in and/or released from the pores is small. The overall effect on the chemical composition of the bulk of produced oil should be negligible, since the ratio of bio-utilized oil to the total amount of oil produced from the well is small. Therefore measurement of changes in oil that occur at water/oil interface of well bore and reservoir surfaces may be masked by the bulk of the produced oil that is not affected by bacterial activity.

Asphaltenes represent an important fraction of crude oil to investigate for evidence of bacterial metabolism of oils since polar molecules are likely to be concentrated there. Fatty acids are built by biosynthesis from acetic acid blocks (2 carbon units). Fatty acids are one of the most important intermediate metabolic by-products of microbial oxidation of petroleum. The occurrence of increased levels of fatty acids in the post-treatment oil suggests that substantial bacterial utilization of petroleum occurred in the well bore and/or reservoir. In addition, the appearance of a substantial amount of acetic acid in the post treatment oil could be the result of pyrolysis or breakdown of larger biosynthesized fatty acids, offering further indication of biological activity induced by the MEOR treatment.

Conclusions

Chemical characteristics of the bulk oil were not significantly changed as a result of the MEOR treatment. Substantial increases in the amount of fatty acids measured in the post-treatment asphaltene fraction of oil from well #61-SX-3 suggests that hydrocarbons were oxidized by the introduced MEOR bacteria in the down-hole environment.

References

- Dunn, R., Swannell, R., Scholes, M., and Colcomb-Heiliger, K., 1990, "Oil Degradation by Alpha BioSea", Report # 3337 (MPBM) Warren Spring Laboratory, Stevenage, U.K.
- Singer, M. E., and Finnerty, W. R., 1984, "Microbial Metabolism of Straight Chain and Branched Alkanes", in R. A. Atlas (ed.) Petroleum Microbiology, Macmillan, New York, pp. 692.

Table 5-1. Population densities of Total Hydrocarbon Utilizing Bacteria (THUB) in the three wells sampled for organic analysis of the oils before and after treatment. Population densities are reported as an order of magnitude of cells per ml of well fluid (i.e., 1×10^6 cells per ml is reported as 6).

<u>Sample Date</u>	<u>Well 61-SX-3</u>	<u>Well 31-S-3</u>	<u>Well 78-SX-3</u>
7/8/88	0	0	2
8/29/88	0	1	0
8/30/88	Treatment	Treatment	Treatment
9/23/88	5	3	2
10/10/88	4	2	4
12/6/88	1	1	0
2/15/89	0	0	0

Table 5- 2. Ratios of pristane/phytane, pristane/C17, and phytane/C18 for oil sampled before and after MEOR treatment.

<u>Well</u>		<u>Pr/Ph (± 0.02)</u>	<u>Pr/C17 (± 0.02)</u>	<u>Ph/C18 (± 0.02)</u>
61-SX-3	Before	1.62	1.30	0.64
	After	1.63	1.27	0.64
78-SX-3	Before	1.60	1.24	0.63
	After	1.61	1.24	0.63
31-S-3	Before	1.62	1.26	0.65
	After	1.62	1.26	0.65

Figure 5-1. Location of the three wells selected for analysis of oil before and after treatment with MEOR materials. Selected wells are indicated by a circle around the well location.

Well 78-SX-3

Well 61-SX-3

Well 31-S-3

Figure 5-2. Whole crude oil analysis by GC-FID for wells 61-SX-3, 78-SX-3, and 31-S-3.

Figure 5-3. Well #61-SX-3 (treatment well). Before and after MEOR treatment analysis of whole crude oil by GC-FID. Whole crude analysis is compared on the right side of the page, enhancements of the Pr/Ph , Pr/C_{17} , and Ph/C_{18} values are compared on the left side of the page.

Figure 5-4. Well #78-SX-3 (observation well). Before and after MEOR treatment analysis of whole crude oil by GC-FID. Whole crude analysis is compared on the right side of the page, enhancements of the Pr/Ph, Pr/C17, and Ph/C18 values are compared on the left side of the page.

Before
Treatment

5-12

After
Treatment

Figure 5-5. Well #31-S-3 (observation well). Before and after MEOR treatment analysis of whole crude oil by GC-FID. Whole crude analysis is compared on the right side of the page, enhancements of the Pr/Ph, Pr/C17, and Ph/C18 values are compared on the left side of the page.

Unknown

Reference
Standard

Unknown

Reference
Standard

Figure 5-6. Identification of tetradecanoic and hexadecanoic acid from asphaltene fraction of oil collected from well #61-SX-3 by comparison with reference standards.

Figure 5-7. Pyrolysis/GC/MS analysis of asphaltene fraction of oils collected from well #61-SX-3 before and 40 days after MEOR treatment. Note relative increase in C12-C18 fatty acids and the appearance of C6 and C2 (acetic acid) in the after treatment asphaltenes.

SECTION 6

LABORATORY INVESTIGATION OF BACTERIA-ROCK INTERACTIONS UNDER SIMULATED SHANNON SANDSTONE RESERVOIR CONDITIONS

Franz K. Hiebert

Summary

Bacteria were cultured in two types of microcosms that model reservoir conditions. Mineral or rock components of the microcosms were calcite crystals, quartz sand, or Shannon Sandstone chips. The fluid component was formation water collected from the MEOR pilot area of the Shannon Sandstone reservoir at Teapot dome Field in Wyoming. Crude oil produced from the Shannon was used as the only source of organic carbon. The microcosms were inoculated with a mixed-community culture of hydrocarbon-utilizing bacteria and incubated for up to nine months. Standard microbiological methods were modified in order to study the interaction of inoculated bacteria and the mineral grains comprising the Shannon reservoir rock. Mineral grains and sandstone were examined for evidence of bacterial colonization and diagenesis periodically throughout the experiments.

Scanning Electron Microscopy was selected as the most appropriate reconnaissance tool for documenting bacteria-rock interactions. Several sample preparation techniques were evaluated for SEM analysis. Critical-point drying preserved bacterial morphology and details of the bacteria/mineral surface better than air drying, but air drying was found to be sufficient for reconnaissance observations. Bacteria colonized the surfaces of unconsolidated sediments and were concentrated in surface cracks. In experiments with rock, bacteria penetrated to the interior of 2 cm sandstone chips and colonized the surfaces of quartz, feldspar, and clay minerals. Isolated bacteria and microcolonies were the most commonly observed colonization pattern on sediment and rock surfaces. Pits and runnels in quartz overgrowth surfaces were observed beneath attached bacteria.

Introduction

Studies of how bacteria behave in, and affect the subsurface reservoir environment are important to the development of the technology of microbial enhanced oil recovery. The geochemical effects on minerals of bacterial metabolism within rock pores has been largely unrecognized and underappreciated by most geologists. Heterotrophic bacteria metabolize carbon substrates in order to gain the energy they need to reproduce. Organic matter, inorganic nutrients and minerals from the environment surrounding bacteria are actively transported into the cell via enzymatically catalyzed reactions, and metabolic by-products are discarded from the cell back to the environment (Brock, 1988). The cell spends energy to concentrate or dilute biochemicals and minerals at non-equilibrium concentrations for its own uses. Bacterial cells also have certain characteristics, such as electrical surface charge and the capability to concentrate ions at high concentrations on their surfaces, that increase their probability of affecting a rock-water interaction. In the subsurface sedimentary environment, bacterial activity occurs in the porespace microenvironment.

The purpose of this study was to investigate the hypothesis that bacterial metabolism of hydrocarbon and/or daughter products of hydrocarbon degradation within the pores of reservoir rock alters that geochemical microenvironment and causes diagenetic changes in minerals and rocks. The approach of this research was to conduct experiments with live mixed cultures of hydrocarbon utilizing bacteria in sedimentary environments that simulate the Shannon reservoir conditions.

Composition of Crude Petroleum

Crude oil is a complex mixture of tens of thousands of compounds that differ markedly in volatility, solubility, and susceptibility to biodegradation (Cooney, 1984)

The bulk of petroleum components can be grouped into three broad categories of hydrocarbon type. The straight chain and branched alkanes range from 27-72% of a crude petroleum, cyclic alkanes may constitute from 22-67%, and aromatics 6-14%. Other organic compounds in crude oil are characterized by the inclusion of nitrogen, sulfur, or oxygen in

their molecular structures and make up only a few percent of any crude oil. The effect of the MEOR culture on bulk oil and the asphaltene fraction are discussed in Section 5 of this volume, "Chemistry of Oil Before and After MEOR Treatment".

Metabolic Pathways Of Microbial Degradation of Alkanes

The Shannon crude oil is rich in paraffins (see Section 5). Straight chain alkanes are the most rapidly degraded fraction of crude oil by the mixed culture of bacteria used in these experiments. During metabolism of alkanes a variety of intermediate chemical byproducts are produced which are either further degraded inside the bacterium or released to the extracellular environment.

In the most general terms, alkanes are degraded by bacteria via a sequence of oxidations to the corresponding alcohol, aldehyde and monobasic fatty acid. The oxidation state of the oxidized carbon falls from -3 in the alkane to + 3 in the fatty acid, as the organism derives energy from breaking chemical bonds. The fatty acids are further degraded to acetyl-CoA and ATP via the beta-oxidation pathway. Acetyl-CoA is then available as fuel for the Krebs-cycle. Each oxidation step is catalyzed by highly specific enzymes.

The utilization of alkanes as a sole source of carbon for bacteria is strictly an aerobic process. Molecular oxygen is essential to the first, and rate limiting, step of the process. Three mechanisms have been proposed to describe the primary oxidation of an alkane to a corresponding alcohol, they are: 1) hydroxylation, 2) dehydrogenation, and 3) hydroperoxidation.

Hydroxylation occurs at the C-1 position, monoterminal methyl group. The first reaction requires an alkane, O₂, a monooxygenase enzyme and the co-enzyme NADH. The alkane and the oxygen are available to the cell from the external environment and, if hydrocarbon metabolism is internal, must be transported across the cell membrane. Water, enzymes and coenzymes are randomly dispersed in the cytoplasm of the cell. One of the oxygen atoms from O₂ bonds with the methyl group to form an alcohol with the same carbon

chain number, the other oxygen is reduced to water (Singer and Finnerty, 1988). This primary alcohol is further oxidized to the corresponding aldehyde. Methyl group oxidation of alkanes yields fatty acids of identical carbon number and these fatty acids are assimilated directly into cellular lipids, accumulate in the degradation environment and serve as oxidizable substrates. Fatty acids derived from alkane are oxidized by an inducible beta-oxidation system to the level of acetate for even-chain alkanes and to propionate for odd-chain alkanes (Singer and Finnerty, 1988). Acetate is subsequently oxidized in the Krebs cycle. Final end-products are new cells, CO₂ and H₂O.

The accumulation of fatty acids in the degradation environment may have a role as a stimulus to further alkane degradation. If the residual fatty acid (a water-soluble polar molecule) emulsifies alkane, alkane surface area and solubility increases. Thus more alkane is available from the bulk phase to microbial degradation mechanisms. Increased surface area or solubility allows the more rapid oxidation, or metabolism, of alkane.

Dehydrogenation of alkanes to alkenes has been proposed by several authors, most recently in 1973 (Gallo et.al., 1973a). This mechanism would result in the transformation of alkane to alcohol without the interaction of molecular oxygen, instead apparently relying on the breakup of water molecules to supply the oxygen to form the hydroxyl group at the terminal methyl group.

This mechanism has not been substantiated by enzymological studies (Singer and Finnerty, 1988).

Hydroperoxidation is another alternative mechanism for the first step of the alkane oxidation, in which a dioxygenase incorporates both oxygen atoms from O₂ into the terminal methyl group to form an n-alkyl hydroperoxide, which in turn is reduced to an alcohol:

Finnerty (1977) has proposed that in *Acinetobacter sp. HOI-N*, alkane is metabolized with the interaction of a peroxy acid directly to fatty acid with no alcohol intermediate. The final result of both pathways is a fatty acid, which is available for beta-oxidation.

There is no net difference between the hydroxylation, hydrogenation, and hydroperoxidation mechanism in final metabolic products, but the pathways are considerably different. This is significant as a measure of the diversity of mechanisms that have evolved to utilize alkanes as an energy source.

Bacterial Diagenesis

Many geologic investigations of ancient rocks suggest that bacteria have played an important role in rock formation and alteration. Kuznetsov et al., (1963), Ehrlich (1981), Krumbein (1983), and Chilingarian and Wolf (1988) have reviewed in broad terms bacterial roles in a variety of diagenetic processes in both silicate and carbonate rocks.

The role of bacteria in the precipitation of calcium carbonate has been reported from many field studies of ancient rock. Ashirov and Sazonova (1962) studied a calcite layer beneath the Pokrovka oil reservoir in the Volga-Ural Basin and determined that it was formed as the result of the reduction of calcium sulfate by sulfate reducing bacteria. Folk and Chafetz (1980,1983) and Chafetz and Folk (1984) reported that bacteria formed low magnesium, microporous calcite travertines and pisoliths in a variety of hot spring environments, and

described five morphologies of bacterially precipitated calcite aggregates. Chafetz and Meredith (1983) reported a bacterial role in the formation of travertine pisoliths in Idaho hot springs. Folk, Chafetz, and Tiezzi (1985) further described the role of hot spring bacteria in the deposition of Italian travertines. Tiezzi and Folk (1989) described calcite cements from within stromatactis-type cavities of the Mississippian Lodgepole formation in Montana as cloudy with bacterial bodies. They attributed the precipitation of these calcite cements to the biochemical activity of live bacteria in the original reef. Folk (1986, 1987) proposed that gray colored carbonate nodules in the Portoro Limestone of Italy are the result of local bacterial diagenesis. Hiebert (1988) described fossil bacteria trapped in calcite cements of the Posidonienschiefer Shale and proposed that when the bacteria were alive, they performed a catalytic role in the precipitation of the entombing cements.

The role of a variety of bacteria that initiate carbonate precipitation has been experimentally studied in varying degrees of detail in the lab. Drew (1910) was an early worker who noted that denitrifying marine bacteria could precipitate carbonate in tropical and temperate seawater. Zobell (1946) reviewed processes of bacterial participation in carbonate precipitation and suggested that 1) bacterial production of ammonia during metabolism caused a pH rise, 2) that sulfate reduction was necessary, and 3) that only certain bacteria were capable of initiating precipitation events. LaLou (1957) experimentally produced a carbonate scum on the surface of a mud-enriched seawater aquarium and attributed its formation to bacterial alteration of pH, CO₂ and H₂S. Oppenheimer (1961) reported that marine bacteria formed spherical aragonite grains on the Bahamian Bank. Berner (1969, 1971) systematically investigated carbonate during bacterial degradation of marine organisms. He found that the type of organic matter available to bacteria determined pore water conditions. He concluded that in restricted pore water conditions, the kinetics of base versus acid production during metabolism determined whether carbonate precipitated or dissolved. Sulfate reduction was reported to be an essential process for carbonate precipitation. McCallum and Guhathakurta (1970) noted bacterial bodies forming the nucleus of aragonite needles precipitated from

nutrient-enriched seawater solutions. Krumbein (1974) found that marine heterotrophic bacteria which precipitate aragonite, Mg-calcite and monohydro-calcite under both aerobic and anaerobic conditions were first coated, and then encapsulated with carbonate. Krumbein noted that the actual cells were destroyed by later crystal growth. Morita (1980) and del Moral *et al.*, (1987) also reported bacterial bodies incorporated in carbonate precipitated from nutrient enriched seawater in laboratory experiments.

The alteration of silicate minerals by microorganisms has been reported via several mechanisms. Eno and Reuzer (1955) experimented with *Aspergillus niger* (a fungus) and found that potassium was released from biotite, muscovite and microcline because of metabolically increased acidity of the soil environment. Webley, Duff, and Mitchel (1960) and Duff *et al.*, (1963) made studies of silica degrading soil bacteria. They correlated silicate degradation with bacterial production of organic acids, especially 2-ketogluconic acid. Savotsin (1972) studied non-heterotrophic silicate degrading bacteria from tropical soils and reported that 26% of total potassium was released from orthoclase in 40 days of growth, an order of magnitude faster rate than weathering with carbonic acid alone. In laboratory experiments with three strains of carbohydrate-utilizing bacteria, Rades-Rohkohl *et al.*, (1978) presented scanning electron micrographs of bacterially colonized synthetic quartz crystals covered with microdivots complete with bacterial bodies within each, but felt chemical data did not support an interpretation that bacteria dissolved quartz in her experiments. She reported total dissolved SiO₂ in solution decreased for six days, then increased to saturation in six days but did not result in statistically significant changes. Eckhardt (1979) found that organic acids produced by heterotrophic yeasts released 62% K, 33% Mg, 29% Fe, 59% Al and 6% Si from biotite over a 12 week growth experiment.

Erlich (1981) reviewed silicate dissolution by glucose-utilizing heterotrophic soil bacteria. He reported that the weathering and dissolution of silicate minerals was caused by chelation of cations by organic acids and bases and did not comment on any precipitation effects. Krumbein and Jens (1981) reviewed indirect physical evidence of bacterial

dissolution of silicates, and bacterial precipitation of silicates, but not mechanisms of dissolution. He proposed that carboxylic acids are important in silicate weathering as chelating agents and concluded that microcrystalline quartz can be mobilized under natural conditions by a variety of microorganisms. However, he left the question of direct or indirect bacterial dissolution open for future studies

Bennett and Siegal (1987) reported dissolution of quartz at near-neutral pH by organic acid complexation in a shallow, crude-oil contaminated sand aquifer in Bemidji, MN. They proposed that the source of organic acids was the microbial metabolism of crude oil. Bennett et al., (1988) suggested that biodegradation of the organic component of a silica complex could release the silica and create supersaturated conditions. Hiebert and Bennett (1992) reported direct evidence of enhanced weathering of in-situ quartz and feldspar minerals by crude oil degrading bacteria in the Bemidji aquifer.

Extent of Subsurface Bacterial Colonization

Attention to bacterial alteration of minerals has been focused on the surface and soil zone environments. Until recently, bacteria were thought to be absent from the deep subsurface (Ghiorse and Wilson, 1988). In fact, the subsurface is an excellent environment for bacterial life (Balkwill 1989, Fredrickson et al., 1989, Fliermans and Hazen, 1991). At low temperatures ($<80^{\circ}\text{C}$), interconnected porosity, abundant surface area, and the presence of dissolved organic matter in the interstitial pore water allow bacteria to grow in and move through a sedimentary rock environment. The small size of bacteria, their colloidal properties, and ability to adapt to extreme environmental conditions allow them to flourish in many subsurface environments. Bacteria introduced into oil wells for MEOR are known to flourish at depths of several thousand feet, to bottom-hole temperatures of about 80°C .

A Method of Studying Bacteria/Rock Interactions

While microcosms have been utilized for studies of bacteria and the fate of organic compounds, there has been little published research to date on the diagenetic effect that various

bacteria might have on the rock substrates included in microcosm experiments. In this work, microcosms were designed to simply model a subsurface sedimentary environment. The goal of the microcosm experiments was to produce bacterially colonized and altered geologic materials for analysis.

SEM and Sample Preparation

Scanning Electron Microscopy (SEM) is well suited to the study of bacteria/mineral interactions. SEM has ample depth of field and resolution to image micron size bacteria on rugged microtopographic surfaces (Weise and Rheinheimer 1978). The SEM images only the mineral surface, which is the crucial factor in bacteria/rock interactions.

In most cases typical geological sample preparation techniques destroy the delicate structure of bacterial tissue by heat, desiccation, and chemical additives. Desiccation is a highly destructive process to cell wall morphology. Surface morphology of cells can be preserved with the critical-point drying (CPD) technique (Costerton 1980, and Newbury 1981). Since the focus of this research is to study the bacteria-rock interaction, microbiological sample preparation techniques were adapted that preserved bacterial tissue on the mineral and rock surfaces of interest.

Objectives

The objectives were to develop and refine methods to study bacterial diagenesis and to make preliminary observations on bacterial colonization patterns and alteration of minerals.

Materials

Shannon Sandstone was selected and prepared as the geologic component of microcosms. Samples were selected from core drilled from the Cretaceous Shannon formation, Bar Margin facies, Natrona County Wyoming. The rock was broken into pieces

approximately 2 cm in diameter, steam autoclaved, allowed to dry in a covered beaker, and stored in sealed sterile bottles until used in experiments (Fig 1).

The cleaned mineral grains and rock were characterized in the SEM as controls for comparison with bacterially altered material. The samples were air dried, mounted on aluminum stubs and gold coated for 40 seconds at 40 milliamperes.

A light "sweet" crude oil from the Shannon reservoir of Teapot Dome Field in Natrona County, Wyoming was used as the organic nutrient for all the bacterial growth experiments. Chemical characteristics of the oil are described in Sections 2 and 5 of this report. The oil comes from the same formation as the sandstone used in the microcosm experiments. The fluid component of each experiment was Shannon formation water.

The microorganisms used in experiments were a mixed community of naturally occurring soil and subsurface bacteria that utilize hydrocarbon as energy and carbon source. Isolates that comprise the culture have been identified as follows:

Acinetobacter *genospecies* 12,

Pseudomonas *stutzeri*,

Pseudomonas *fluorescens*,

Bacillus *circulans*,

a species from *Bacillus* *spore group I* (not *B. cereus*),

four isolates from the *Bacillus* *spore group II* ,

and a species of coryneform bacteria.

All bacterial growth experiments were inoculated from fresh log-phase culture and all experiments were carried out with the complete mixed culture. Pure strains of bacteria were isolated from the mixed culture and morphologically characterized by scanning electron microscopy (Fig. 2).

Methods

Microcosms were constructed of 500 ml sterile beakers that contained components of rock, fluid, organic matter, and bacteria (Fig. 3). The beakers were covered, kept at room temperature and atmospheric pressure. The bacterial inoculum was adjusted so that the initial concentration of bacteria in the microcosm fluid was 1×10^6 cells/ml. A control for each microcosm was constructed with all the same components except for the bacterial inoculum. Mineral and rock material from controls were sampled and analyzed in the same manner as from the test microcosms.

Most experiments were conducted as batch growth experiments in which a finite amount of organic matter was introduced at the start of the experiment. This method represents a closed system with respect to nutrient supply and accumulation of metabolic by-products. Fluid composition, bacterial inoculum, and type of organic matter were held constant throughout all growth experiments. Amounts of aeration, if any, and agitation of fluids were varied throughout many experiments. The experiments were observed over a three-to nine-month period.

Two experiments and a control were maintained as semi-open systems in which the organic matter and media fluids were partially replaced on a daily basis. The basic design and components were similar to the batch system except that once every 24 hours, 250 ml of media was removed from the microcosm and replaced with fresh media plus 2.5 ml crude oil. In this system, nutrients were replaced, and by-products and cells removed. Minerals or rock fragments were sampled from the microcosms at periodic intervals with sterile instruments and prepared as described below for SEM analysis.

Air drying and critical point drying (CPD) techniques for SEM sample preparation were compared for their success in preserving bacterial morphology in relation to the mineral surface. Observations were made with a Philips Model 515 SEM and a JOEL JSM T330A Scanning Microscope.

Results

Air drying samples resulted in relatively poor preservation of bacterial bodies. The bodies appear flattened or otherwise distorted and spread-out across mineral surfaces. In some instances, three-dimensional morphologies were preserved but surface detail and normal shape was obliterated. Critical point drying of samples resulted in excellent cell morphology preservation. This method allowed detailed study of the bacteria/rock attachment and diagenetic effects at the cell/mineral surface.

Within three days of inoculation, bacteria had colonized some surfaces of unconsolidated quartz sand and penetrated to the center of 2 cm sandstone chips and colonized internal pore surfaces. On quartz sand grains, bacteria were observed to be concentrated in cracks and crevices, while sparse colonization was observed on exposed smooth surfaces (Figs. 4 and 5). Bacterial colonization of internal pore surfaces of sandstone chips showed a different colonization pattern. A variety of bacterial types were observed to colonize smooth quartz overgrowth surfaces, and clay surfaces with nearly equal density (Figs 6 and 7).

Bacteria were most commonly observed colonizing rock and mineral surfaces as single isolated cells. Microcolonies were also commonly observed. Within the pores of sandstone, microcolonies occurred randomly, even on the sharp terminations of quartz overgrowths. Most bacteria showed no sign of polymer adhesion, flagella, or attachment filament and may have adhered directly or by cryptic filaments at the bacteria/mineral contact (Marshall 1976, Rades-Rohkohl 1978, and Marshall 1980).

On smooth quartz surfaces, several types of bacteria (spheres, curved rods, and some straight rods) were observed to be attached in "micro-divots" and runnels which ranged from 0.1- 0.5 microns deep, and from between 1-3 microns in length and width. The margins of the divots are not sharply defined, rather they gently grade from the deepest directly beneath the bacteria outwards into the plane of the mineral surface. The bacterial divots were most commonly observed on the quartz overgrowths of the Shannon sandstone samples from the semi-open microcosm model. Not all types of bacteria were observed in divots. There appears

to be a high correlation between the occurrence of micro-divots and attached bacterial bodies. Few divots have yet been observed without an attached bacterium.

The divots are not apparent in top-down views of bacteria on mineral surfaces because of the lack of divot edges. The divots are visible only in side views (profiles) at an angle that allows observation of the bacteria/mineral surface contact. The divots are not an effect of the SEM. Stereo pair micrographs of bacteria in divots confirm that a real depression is present.

Discussion

The hydrocarbon-utilizing bacteria in these experiments colonize rock surfaces as individual cells and as microcolonies. Much of the literature that describes growth of bacteria in porous media reports that bacteria eventually form a continuous biofilm over the surface they colonize (Characklis and Cooksey 1983, Costerton et. al., 1985), yet in these experiments this general phenomena was not observed. The microcolonies observed in this work are unlikely to represent examples of stunted or nutrient-limited growth, since post-attachment growth on many mineral surfaces is indicated by dividing cells. One suggestion for the seemingly anomalous observations of this study is that most experimental work reported in the literature was performed with carbohydrate-utilizing bacteria. Hydrocarbon-utilizing bacteria may not produce the abundant extracellular slime (often composed of polysaccharide) as do carbohydrate-utilizing bacteria, and may not produce surface conditions that initiate biofilm formation.

The observation of maximum bacteria concentration in the cracks and crevasses of quartz grains collected from the microcosm experiments is consistent with work of Weise and Rheinheimer (1978), who found a correlation between site and density of bacterial colonization and rough spots on the microtopography of a sand grain from a high energy marine environment. In contrast, bacterial distribution on pore surfaces within sandstone was not controlled by surface microtopography. It is unclear what accounts for this difference. Several hypotheses may be suggested: 1) different types of bacteria preferentially select adhesion surfaces based on chemical or mineralogical characteristics other than roughness, such as

elemental composition, degree or type of organic matter on the mineral surface, or electrical characteristics of the surface, or 2) micro-scale fluid flow past the mineral surface could sort the bacteria into pockets of low-velocity flow, depositing the bacteria in cracks and depressions. Data from this work does not support one hypothesis over the other.

Different types of bacteria may preferentially colonize different types of minerals. Several hypotheses can be suggested for what controls this phenomena: 1) bacteria are attracted to minerals whose chemical composition includes nutrients essential to growth, 2) rough surface microtopography may offer a good attachment site, or represent a low velocity spot protected from fluid currents, or 3) organic matter adsorbed on certain minerals may attract motile chemotactic bacteria.

Bacterial Diagenesis

The observation of hydrocarbon-metabolizing bacteria producing microdivots on quartz surfaces is of geological significance. The bacteria could be forming the divots by several mechanisms, including: 1) by producing organic acids that complex and mobilize Si from the quartz surface, 2) by incorporating Si directly into their cell material, or 3) by a combination of the above. Bennett and Siegal (1987) proposed a bacterial mechanism for quartz dissolution in a crude oil contaminated aquifer. They presented evidence of an increase in the solubility of quartz brought about by bacterially produced dissolved organic acids and proposed that quartz was complexed and mobilized by the organic acids in neutral pH conditions. They also presented scanning electron micrographs of etch pits, slightly larger than the microdivots observed on microcosm quartz grains, but without bacterial bodies. Bennett and Hiebert (1992) and Hiebert and Bennett (1992) presented direct evidence of mineral-colonizing bacteria that accelerated the dissolution of silicate minerals in an oil-contaminated aquifer.

Organic acids are the primary intermediate byproduct of the microbial metabolism of crude oil. These acids are released into the environment as metabolic byproducts as well as being retained within the cell (Brock, 1988). The production and release of fatty acids is a

common net effect of the wide variety of metabolic pathways of hydrocarbon. Bacterial metabolism of crude oil may represent an alternative to thermal cracking of hydrocarbons as a source of organic acids in the subsurface. Bacterially generated fatty acids in the subsurface represent a mechanism for the dissolution, transport and, perhaps, precipitation of quartz (Bennett et al., 1988).

Conclusions

1. Microcosm and SEM methods are suitable for study of bacterial diagenesis.

Critical-point drying preserved bacterial morphology and details of the bacteria/mineral surface better than air drying, but air drying was found to be sufficient for reconnaissance observations.

2. Bacterial colonization patterns of sediment and rock vary. Colonization of sediment surfaces was found to be concentrated in cracks. Bacteria colonizing internal pore surfaces of sedimentary rock appeared to be more homogeneously distributed. Bacteria may preferentially colonize certain minerals over others.

3. Certain bacteria may cause quartz dissolution at the bacteria/mineral contact.

References

- Ashirov, K. B., and Sazonova, I. V., 1962, Biogenic sealing of oil deposits in carbonate reservoirs: (translated from) *Microbiologiya*, v. 31, no. 4, pp. 680-683.
- Balkwill, D. L., 1989. Numbers, diversity, and morphological characteristics of aerobic, chemoheterotrophic bacteria in deep subsurface sediments from a site in South Carolina, *Geomicrobiology*, vol. 7, no. 1/2, p. 33-52.
- Bennett, P. C., and Siegal, D. I., 1987. Increased solubility of quartz in water due to complexing by organic compounds, *Nature*, vol. 36, no. 6114, pp. 684-686.
- _____, Melcer, M. E., Siegal, D. I., and Hassett, J. P., 1988. The dissolution of quartz in dilute aqueous solutions of organic acids at 25° C, *Geochimica et Cosmochimica Acta*, vol. 52, pp. 1521-1530.
- Bennett, P.C., and Hiebert, F. K., 1992, Microbial mediation of silicate diagenesis in organic-rich natural waters, p.267-270, in *Water-Rock Interaction*, Y.K. Kharaka and A. S. Maest (Eds.) *Proceedings of the 7th International Symposium on Water-Rock Interactions*, Rotterdam, Balkema

- Berner, Robert A., 1969, Chemical changes affecting dissolved calcium during the bacterial decomposition of fish and clams in sea water: *Marine Geology*, v. 7, pp. 253-274.
- _____, 1971, Bacterial processes effecting the precipitation of calcium carbonate in sediments: *Johns Hopkins University Studies in Geology*, no.19, pp. 247-251.
- Brock, Thomas D., and Madigan, Michael, T., 1988, *Biology of Microorganisms*, Fifth Edition. Englewood Cliffs, New Jersey, pp. 835.
- Chafetz, H. S., and Meredith, J. C., 1983, Recent travertine pisolites (pisoids) from southeastern Idaho, USA in T.M. Peryt (ed.), *Coated Grains*: New York, Springer-Verlag, pp. 450-455.
- _____, and Folk, Robert, L., 1984, Travertines: depositional morphology and the bacterially constructed constituents, *Jour. Sed. Pet.*, vol. 54, no. 1, p.289-316.
- Characklis, W. G., and Cooksey, K. E., 1983, Biofilms and microbial fouling, *Advances in Applied Microbiology*, vol. 29, p. 93-138.
- Chilingarian, G. W., and Wolf, K. H., 1988. Diagenesis I, *Developments in Sedimentology* #41, Amsterdam: Elsevier, 591 pp.
- Cooney, 1984. in R.M.Atlas ed., *Petroleum Microbiology*, New York: Macmillan Publishing Co.
- Costerton, J. W., 1980. Some techniques involved in study of adsorption of microorganisms to surfaces, p. 403-426. in: *Adsorption of Microorganisms to Surfaces*, Gabriel Bitton and Kevin C. Marshall eds. New York: John Wiley and Sons, pp.439.
- _____, Marrie, T. J., and Cheng, K. J., 1985, Phenomena of bacterial adhesion, p. 3-43, in D. C. Savage and M. Fletcher eds., *Bacterial Adhesion*, London: Plenum Publishers.
- del Moral, A., Roldan, E., Navarro, J., Montilova-Sanchez, M., and Ramos-Cormenzana, A., 1987, Formation of calcium carbonate crystals by moderately halophilic bacteria, *Geomicrobiology Journal*, v. 5, pp. 79-87.
- Drew, G. H., 1910, The action of some denitrifying bacteria in tropical and temperate seas, and the bacterial precipitation of calcium carbonate: *J. Mar. Biol. Sci. Assoc. U. K.*, v. 9, pp. 142-155.
- Duff, R. B., Webley, D.M., and Scott, R. O., 1963, Solubilization of minerals and related materials by 2-ketogluconic acid producing bacteria, *Soil Science*, vol. 95, p. 105-114.
- Eckhardt, F. E. W., 1979, Über die einwirkung heterotropher mikroorganismen auf die zersetzung silikatisher minerale, *Z. Pflanzenernaehr. Bedenk.* v. 142, p. 434-445.
- Ehrlich, Henry Lutz, 1981. *Geomicrobiology*, New York: Marcel Dekker, Inc., 393 pp.
- Eno, Charles, F., and Reuzer, Herbert W., 1955, Potassium availability from biotite, muscovite, greensand, and microcline as determined by growth of *Aspergillus niger*, *Soil Science*, vol. 80, p. 199-209.

- Fliermans, C. B., and Hazen, T. C. (Eds.), 1991, Proceedings of the First International Symposium on Microbiology of the Deep Subsurface, Aiken, S.C., WSRC Information Services.
- Folk, Robert L., 1986, White card and smoking gun: bacterio-diagenetic nodules in the Triassic Portoro Limestones of Liguria, Italy: *Geol. Soc. Am. Abs. with Programs*, v. 18, p. 604.
- _____, 1987, Detection of organic matter in thin-sections of carbonate rocks using a white card: *Sedimentary Geology*, v. 54, pp. 193-200.
- _____, and Chafetz, H. S., 1980, Quaternary travertines of Tivoli (Roma) Italy: bacterially constructed carbonate rock: *Geol. Soc. Am. Abs. with Prog.*, v. 12, p. 428.
- _____, and _____, 1983, Pisolites (pisoids) in Quaternary Travertines of Tivoli, Italy, in T.M.Peryt (ed.) *Coated Grains*: New York, Springer-Verlag, pp. 474-487.
- _____, _____, and Tiezzi, P. A., 1985, Bizzare forms of depositional and diagenetic calcite in hot-springs travertines, central Italy. in N. Schneidermann and P. M. Harris (eds.), *Carbonate Cements*: SEPM Spec. Pub. 36., pp. 349-369.
- Fredrickson, J. K., Garland, T. R., Hicks, R. J., Thomas, J. M., Li, S. W., and McFadden, K. M., 1989. Lithotrophic and heterotrophic bacteria in deep subsurface sediments and their relation to sediment properties. *Geomicrobiology*, vol. 7, no. 1/2, p. 53-66.
- Gallo, M., Bertrand, J. C., Roche, B, and Azoulay, E. 1973a. Alkane oxidation in *Candida tropicalis*. *Biochim. Biophys. Acta*, vol. 296, p. 624-638.
- Ghiorse, W. C. and Wilson, J. T., 1988, Microbial ecology of the terrestrial subsurface, *Advances in Applied Microbiology*, vol. 33, p. 107-172.
- Hiebert, F. K., 1988, The role of bacteria in the deposition and diagenesis of the Posidonienschiefer, a Jurassic oil shale from southern Germany, Masters Thesis, The University of Texas at Austin, pp. 124.
- Hiebert, F. K. and Bennett, P. C., 1992, Microbial control of silicate weathering in organic-rich ground water, *Science*, vol. 258, p.278-281
- Krumbein, Wolfgang E., 1974, On the precipitation of aragonite on the surface of marine bacteria, *Naturwissenschaften* v. 61, p. 167.
- _____, 1983, *Microbial Geochemistry*, Oxford: Blackwell Scientific Publications, 330 pp.
- _____, and Jens, K., 1981, Biogenic rock varnishes of the Negev desert (Israel) an ecological study of iron and manganeses transformation by Cyanobacteria and Fungi, *Oecologia*, vol. 50, p. 25-38.
- Kuznetsov, Ivanov, M. V., and Lyalikova, N. N., 1963, *Introduction to Geological Microbiology*: New York, McGraw-Hill, 169 pp.
- LaLou, C. 1957, Studies on bacterial precipitation of carbonates in seawater: *Jour. Sed. Pet.*, v. 27, pp. 190-195.

- McCallum, M. F., and Guhathakurta, K., 1970, The precipitation of calcium carbonate from seawater by bacteria isolated from Bahama Bank sediments: *J. Appl. Bact.*, v. 33, p. 649-655.
- Marshall, K.C., 1976, *Interfaces in Microbial Ecology* Cambridge: Harvard University Press, pp. 156.
- _____, 1980, Adsorption of microorganisms to soils and sediments in: *Adsorption of Microorganisms to Surfaces*, Gabriel Britton and Kevin C. Marshall eds.
- Morita, R.M. 1980, Calcite precipitation by marine bacteria: *Geomicrobiology Journal*, v. 2, pp. 63-82.
- Newbury, D. E., 1981, Specimen Preparation, p. 211-262, in *Practical SEM Electron and Ion Microprobe Analysis*, J. I. Goldstein and H. Yakowitz Eds., New York: Plenum Press, pp. 582.
- Oppenheimer, C. H., 1961, Note on the formation of spherical aragonite bodies in the presence of bacteria from the Bahama Bank: *Geochim. Cosmochim. Acta*, v. 23, pp. 295-296.
- Rades-Rohkohl, E., Franzle, O., and Hirsch, P., 1978, Behavior, activities and effects of bacteria on synthetic quartz monocrystal surfaces. *Microbial Ecology*, vol 4, pp. 189-205.
- Savotsin, Peter, 1972, Microbial transformation of silicates, *Zeitschrift für Pflanzenernährung und Bodenkunde*, vol. 132, p. 37-45.
- Singer, M. E. and Finnerty, W. R. 1984. Microbial metabolism of straight-chain and branched alkanes, Perry, J. J., 1984. Microbial metabolism of cyclic alkanes, *in* R.M. Atlas ed., Petroleum Microbiology, New York: Macmillan Publishing Co., p. 1-59.
- Tiezzi, P. and Folk, R. L., 1988, Cloudy cements in bioherm cavities, Mississippian Lodgepole Limestone, Montana: product of bacterial activity during organic decay: *Sedimentary Geology* (in prep).
- Webley, D. M., Duff, R. B., and Mitchell, W. A., 1960, A plate method for studying the breakdown of synthetic and natural silicates by soil bacteria. *Nature*, vol. 188, no. 4752, p. 766-767.
- Weise, W. and Rheinheimer, G., 1978, Scanning electron microscopy and epifluorescence investigation of bacterial colonization of marine sand sediments, *Microbial Ecology*, vol. 4, pp. 175-188.
- Zobell, C. E., 1946, *Marine Microbiology*, Waltham, MA: Chronica Botanica Co., pp. 240.

Figure 6.1. SEM image of Bar Margin facies of the Shannon Sandstone reservoir. This sample was utilized in microcosm studies of bacterial colonization and alteration of mineral surfaces under sub-surface conditions. Porosity is approximately 20%. Scale bar = 1 mm.

Figure 6.2. SEM image of isolated strain of *Bacillus* sp. from the mixed culture of MEOR bacteria utilized in this study. Scale bar = 1 μ m.

Figure 6. 3. Schematic design of microcosm with Shanon Sandstone.

Figure 6. 4. SEM image of bacteria colonizing the surface of a quartz grain. Note the dividing bacteria in the right half of the image, indicating that growth occurred after colonization of the surface. The bacteria are concentrated in relict marine diatom husks. Scale bar = 10 μm .

Figure 6. 5. Bacteria concentrated in a pore throat between mineral grains in the Shannon Sandstone. No substantial biofilm development was noted during the examination of microcosm samples. Scale bar = 5 μm .

AIM

Association for Information and Image Management

1100 Wayne Avenue, Suite 1100
Silver Spring, Maryland 20910
301/587-8202

Centimeter

Inches

MANUFACTURED TO AIM STANDARDS
BY APPLIED IMAGE, INC.

2 of 2

Figure 6. 6. Mixed culture of MEOR bacteria colonizing the surface of a quartz overgrowth within an internal pore of the Shannon Sandstone after three days in a microcosm experiment. Scale bar = 5 μm .

Figure 6. 7. Mixed culture of MEOR bacteria colonizing the surface of a clay-rich surface within an internal pore of the Shannon Sandstone after three days in a microcosm experiment. Scale bar = 10 μm .

APPENDIX 1

Laboratory procedure for determining total hydrocarbon degrading bacteria population and preparation of growth media.

MODIFIED MPN PROCEDURE FOR THE DETERMINATION OF TOTAL HYDROCARBON DEGRADING BACTERIA IN AN OIL AND WATER SAMPLE

A. MATERIAL (per sample)

- 2 sets of 8 Erlenmeyer flasks labeled 1A-8A and 1B-8B filled with sterile N.S.W. media (see page APPENDIX 3-3)
- 2 Flasks each contain a stirring magnet for mixing
- Stirring plates
- 5.0 ml pipettes
- vortex mixer
- Orbital shaker
- Sterile crude oil
- Microscope with Nomarski DIC (or Phase contrast)

B. PREPARATION OF THE SAMPLE **OIL SAMPLE**

- Mix sample for one minute. Allow oil and water phases to separate and remove 10.0 ml waer near the oil/water interface. Remove 10ml and divide equally into the first two dilution flasks

C. SERIAL DILUTION PROCEDURE.

- After mixing remove 5.0 ml of liquid from flask 1A (While flask is still on a stirring plate) and transfer it to flask 2A. Shake flask 2A vigorously on a vortex mixer for approximately 15-20 seconds. After mixing remove 5.0 ml of liquid from flask 2A and transfer it to flask 3A.
- Continue your serial dilution all the way to flask 8A.
- For flasks 1B-8B, follow the same steps done on flasks 1A-8A.
- Add 4-5 drops of sterile crude oil to each of the dilution series flasks.
- Place flasks on an orbital shaker, and incubate at room temperature (25 deg. F. or above) and 200 r.p.m for 3 days.

D. DETERMINATION OF SAMPLE TITER

- After the incubation period, shake the flasks that you want to observe under the microscope on a vortex mixer for about 15-20 seconds.
- remove a drop of liquid from the flask and place it on a clean glass slide, cover the drop with a cover slip.
- Observe the drop under the microscope. One or more bacteria per field of view indicates a positive field. **If there is oil within the droplet, pay special attention to it, the bacteria sometimes tend to adsorb to the oil.**
- A dilution flask is considered positive when you obtain 10 or more positive fields.
- The titer of the sample is determined by the highest dilution number with 10 or more positive fields.

LABORATORY PROCEDURE FOR THE PREPARATION OF NUTRIENT SEA WATER MEDIA (N.S.W. MEDIA)

I.MATERIALS:

- A)Filtered Sea water
- B)Ammonium Sulfate
- C)Dipotassium Phosphate
- D) Liquid Iron or Iron Sulfate
- D)Aluminum foil
- E)125 ml Erlenmeyer flasks
- F)pH meter
- G)Autoclave
- H)1 x 3/8" Octagon shaped magnetic spinbar

II.PROCEDURE:

- To a liter of filtered sea water add the following:
 - 1.0 gram of Ammonium Sulfate
 - 0.1 gram of Dipotassium Phosphate
 - 5.0 mg of Iron Sulfate
- Mix solution for about 10 minutes to allow the salts to dissolve
- Adjust the pH to 7.6
- Pour 45.0 ml of N.S.W. Media into the 125 ml Erlenmeyer flasks
(add a magnetic spinbar to some of the flasks for Soil testing) and cover the mouth of the flasks with aluminum foil
- Sterilize the media in an autoclave.

III.CHECKING MEDIA STERILITY:

- Take 2-4 of the sterilized media flasks
- Add 5 drops of sterile crude oil to each flask
- Incubate on a rotary shaker for 3-4 days at room temperature (25 deg. C or above)
- Take a drop of liquid from the flask and observe under a microscope with Nomarski Differential Interference Contrast for microbial growth.

APPENDIX 2

Allocation algorithm used for calculating oil production from the Shannon Sandstone Reservoir, Teapot Dome Field, Wyoming.

LINEAR REGRESSION USING RAW TEST DATA
=====

OIL FOR 4/14/84 START DATE OF FEB 1
=====

	X	Y
2/24	24	33.10
2/26	26	32.20
3/1	30	25.60
3/16	45	20.10
4/1	61	25.20
4/14	74	17.20

$$\sum XY = 24(33.10) + 26(32.20) + 30(25.60) + 45(20.10) + 61(25.20) + (74)(17.20) = 6114.10$$

$$\sum X = 24 + 26 + 30 + 45 + 61 + 74 = 260$$

$$\sum Y = 33.10 + 32.20 + 25.60 + 20.10 + 25.20 + 17.20 = 153.40$$

$$\sum X^2 = (24)^2 + (26)^2 + (30)^2 + (45)^2 + (61)^2 + (74)^2 = 13374$$

$$N = 6$$

$$m = \frac{\sum XY - \frac{(\sum X)(\sum Y)}{N}}{\sum X^2 - \frac{(\sum X)^2}{N}} = \frac{6114.10 - \frac{(260)(153.40)}{6}}{13374 - \frac{(260)^2}{6}} = -0.25$$

$$b = \frac{\sum Y - m \sum X}{N} = \frac{153.40 - (-0.25)(260)}{6} = 36.40$$

$$Y = mX + b = (-0.25)(90) + 36.40 = 13.90 \quad \text{OIL POTENTIAL AT 4/30/84}$$

DECLINE CURVE BASED ON LOG Y
=====

OIL FOR 4/14/84 START DATE OF FEB 1
=====

	X	Y	log Y
2/24	24	33.10	1.52
2/26	26	32.20	1.51
3/1	30	25.60	1.41
3/16	45	20.10	1.3
4/1	61	25.20	1.40
4/14	74	17.20	1.23

$$\sum X \log Y = 24(1.52) + 26(1.51) + 30(1.41) + 45(1.3) + 61(1.40) + (74)(1.23) = 352.96$$

$$\sum X = 24 + 26 + 30 + 45 + 61 + 74 = 260$$

$$\sum \log Y = 1.52 + 1.51 + 1.41 + 1.3 + 1.4 + 1.23 = 8.37$$

$$\sum X^2 = (24)^2 + (26)^2 + (30)^2 + (45)^2 + (61)^2 + (74)^2 = 13374$$

$$N = 6$$

$$m = \frac{\frac{\sum X \log Y - \frac{(\sum X)(\sum \log Y)}{N}}{\sum X^2 - \frac{(\sum X)^2}{N}}}{\frac{352.96 - (260)(8.37)}{6}} = \frac{13374 - \frac{(260)^2}{6}}{6} = -0.0046$$

$$b = \frac{\log \bar{Y} - m \bar{X}}{N} = \frac{8.37 + (.0046)(260)}{6} = 1.6$$

$$\log Y = mX + b \quad X = (\log Y - b) / m$$

$$\text{EVALUATE } X_1 \text{ AT } \log Y_1 = 1 \quad (1 - 1.6) / -.0046 = 130$$

$$\text{EVALUATE } X_2 \text{ AT } \log Y_2 = 2 \quad (2 - 1.6) / -.0046 = -86.95$$

$$\Delta X = X_2 - X_1 = -87 - 130 = -217$$

$$a = 2.3 / -217 = -.0106$$

$$q = 10^{\frac{b - aX}{c}} = 10^{\frac{1.6 - .0106(90)}{c}} = 15.9 \quad \text{OIL POTENTIAL ON 4/30/84}$$

NOTES:

1. OIL POTENTIAL WILL BE BASED ON DECLINE CURVE (SECOND CALCULATION)
2. THE LAST FIVE TESTS WILL BE USED TO ESTABLISH DECLINE CURVE
3. DECLINE CURVE CAN BE RE-ESTABLISHED BY MAINTAINING A BEGINNING DATE ON STIMULATED WELLS
4. WELL TESTS FROM THE TEXTRONICS WILL BE TRANSFERRED TO THE HP FOR TESTS ON CURRENT DISKETTES (APPROX AUG 83 - PRESENT)
5. ALL ALLOCATION NUMBERS WILL BE ENTERED FOR EACH WELL. CORELAB TAPES COULD NOT BE FOUND IN FEDERAL BLDG.
6. WELL MOTOR DATA WILL BE MAINTAINED BY ELECTRICIANS:

HORSE-POWER
RPM
AMPS

APPENDIX 3

Oil and water production and population level of total hydrocarbon degrading bacteria from producing wells treated with the MEOR materials in late August, 1988. Population densities of bacteria are reported as an order of magnitude of cells/ml of well fluid (i.e., 1 X 10⁶ cells/ml is reported as 6)

**DATE
FILMED**

7 / 30 / 93

END