348
5/7/79

DOE/NASA CONTRACTOR
REPORT

lh. 2547

DOE/NASA CR-161166

LONG TERM WEATHERING EFFECTS ON THE THERMAL PERFORMANCE OF THE SOLARON (AIR) SOLAR COLLECTOR

Prepared by

Wyle Laboratories
Solar Energy Systems Division
Huntsville, Alabama 35805

MASTER

Under subcontract to

IBM Corporation, Federal Systems Division, Huntsville, Alabama 35805

Contract NAS8-32036

National Aeronautics and Space Administration
George C. Marshall Space Flight Center, Alabama 35812

For the U. S. Department of Energy

U.S. Department of Energy

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

Solar Energy

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency Thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DISCLAIMER

Portions of this document may be illegible in electronic image products. Images are produced from the best available original document.

NOTICE

This report was prepared to document work sponsored by the United States Government. Neither the United States nor its agents the United States Department of Energy, the United States National Aeronautics and Space Administration, nor any federal employees, nor any of their contractors, subcontractors or their employees, make any warranty, express or implied, or assume any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product or process disclosed, or represent that its use would not infringe privately owned rights.

PAGES i to ii
WERE INTENTIONALLY
LEFT BLANK

TABLE OF CONTENTS

		<u>Page No.</u>
	SUMMARY	iv
1.0	PURPOSE	1
2.0	REFERENCES	1
3.0	TEST REQUIREMENTS AND PROCEDURES	2
	3.1 Collector Thermal Efficiency Test Requirements	2
	3.2 Test Procedure	2
4.0	ANALYSIS OF RESULTS	4
	4.1 Thermal Performance Test	4
 TABLE I	 SOLARON (AIR) COLLECTOR PERFORMANCE RECHECK AFTER LONG TERM EXPOSURE TO NATURAL WEATHERING CONDITIONS	 7
 Figure 1.	 Solaron (Air) Collector Indoor Thermal Performance Test Results	 8

NOTICE

This report was prepared as an account of work sponsored by the United States Government. Neither the United States nor the United States Department of Energy, nor any of their employees, nor any of their contractors, subcontractors, or their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness or usefulness of any information, apparatus, product or process disclosed, or represents that its use would not infringe privately owned rights.

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

SUMMARY

Thermal performance tests were conducted on the Solaron double covered air solar collector, following long term exposure to natural weathering conditions. The collector was mounted on the weathering test stand at the Solar Test Facility at Marshall Space Flight Center, Alabama, with exposure to the natural ambient environment. The collector was under stagnation conditions from June 1, 1977, to September 20, 1978. The total weathering period was approximately fifteen and one-half months.

Visual inspection of the collector, prior to re-test, indicated a slight film on the inner cover plate and a significant discoloration of the absorber plate. The test results indicate that performance degradation has occurred. The change in the intercept of the efficiency curve on the ordinate axis is probably due to a change in the absorptivity of the absorber plate, because there was no obvious sign of a change in the transmissivity of the cover glass.

1.0 PURPOSE

The purpose of this report is to present the test procedures used and the test results obtained during an evaluation test program. The test program was conducted to obtain thermal performance data on a Solaron double-covered air solar collector under simulated conditions (Reference 2.1), following long term exposure to natural weathering conditions. The tests were conducted utilizing the Marshall Space Flight Center Solar Simulator in accordance with the test procedures specified in Reference 2.2 and the test requirements of Reference 2.3.

2.0 REFERENCES

2.1	DOE/NASA CR-150572	Indoor Test for Thermal Performance Evaluation of the Solaron (Air) Solar Collector
2.2	MTCP-FA-SHAC-400	Procedure for Operation of the MSFC Solar Simulator Facility
2.3	ASHRAE 93-77	Method of Testing to Determine the Thermal Performance of Solar Collectors

3.0 TEST REQUIREMENTS AND PROCEDURES

3.1 Collector Thermal Efficiency Test Requirements

Thermal performance evaluation criteria shall correspond to that of Reference 2.1. Data shall be obtained at inlet temperatures of 0, 50, and 100°F above the ambient temperature at an air flow rate of 38 SCFM at a solar insolation rate of 300 BTU/Hr·Ft² and a wind speed of 7.5 mph. The following data shall be recorded during the test at each test condition.

1. Ambient temperature.
2. Collector inlet air temperature.
3. Collector outlet air temperature.
4. Collector differential temperature.
5. Differential pressure across collector.
6. Air flow rate.
7. Insolation rate.
8. Wind speed.

3.2 Test Procedure

1. Mount test specimen on test table at a 45° angle with respect to the floor.
2. Assure that simulator lamp array is adjusted to an angle of 45° with respect to the floor.
3. Align the test table so that the test specimen's vertical centerline coincides with the vertical centerline of the lamp array and the distance from the top of the test specimen to the lens plane of the lamp array is 9 feet.
4. Insulate all pipes.
5. Assure that data acquisition system is operational.
6. Start air flow loop and establish a flow rate of 38 SCFM.
7. Establish the wind speed of 7.5 mph.
8. Power up simulator and establish a solar flux level of 300 BTU/Ft²·Hr.

3.0 TEST REQUIREMENTS AND PROCEDURES (Continued)

3.2 Test Procedure (Continued)

9. Determine the ambient air temperature.
10. Adjust the inlet temperature of the collector to the ambient air temperature value.
11. After steady state conditions have been established, record data for a minimum of five minutes.
12. Repeat steps 9, 10, and 11, changing the air inlet temperature as necessary until data has been obtained for each test condition specified in Paragraph 3.1.
13. Upon completion of testing, power down simulator and air loop.

4.0 ANALYSIS OF RESULTS

4.1 Thermal Performance Test

The analysis of data contained in this report is in accordance with the National Bureau of Standards recommended approach. This approach is outlined below.

The efficiency of a collector is stated as:

$$\eta = \frac{q_u/A}{I} = \frac{\dot{m} C_{tf} (t_{f,e} - t_{f,i})}{I} \quad (1)$$

where:

q_u = rate of useful energy extracted from the solar collector (BTU/Hr)

A = Gross collector area (Ft²)

I = Total solar energy incident upon the plane of the solar collector per unit time per unit area (BTU/Hr·Ft²)

$\dot{m}$ = Mass flow rate of the transfer liquid through the collector per unit area of the collector (Lbm/Ft²·Hr)

C_{tf} = Specific heat of the transfer liquid (BTU/Lb·°F)

$t_{f,e}$ = Temperature of the transfer liquid leaving the collector (°F)

$t_{f,i}$ = Temperature of the transfer liquid entering the collector (°F)

Rewriting Equation (1) in terms of the total collector area yield:

$$\eta = \frac{(\dot{m}A)C_{tf} (t_{f,e} - t_{f,i})}{(IA)} = \frac{\dot{M} C_{tf} (t_{f,e} - t_{f,i})}{P_i} \quad (2)$$

Notice that:

$P_i = IA$ = Total power incident on the collector

$\dot{M}A = \dot{M}$ = Total mass flow rate through the collector

Therefore, $\dot{M} C_{tf}(t_{f,e} - t_{f,i})$ = Total power collected by the collector.

4.0 ANALYSIS AND RESULTS (Continued)

4.1 Thermal Performance Test (Continued)

Substitution in Equation (2) results in:

$$\eta = \frac{P_{abs}}{P_{inc}} \quad (3)$$

where:

P_{abs} = Total collected power

P_{inc} = Total incident power

This value of efficiency is expressed as a percentage by multiplying by 100. This expression for percent efficiency is:

$$\text{Collector Efficiency} = \frac{P_{abs}}{P_{inc}} \times 100 \quad (4)$$

or from Equation (2), collector efficiency is defined by the equation:

$$\% \text{ Eff} = \frac{\dot{M} C_{tf} (t_{f,e} - t_{f,i})}{P_{inc}} \times 100 \quad (5)$$

Each term in Equation (5) was measured and recorded independently during the test.

The mean value of efficiency was determined over a five-minute period during which the test conditions remained in a quasi-steady state. Each five-minute period constitutes one "data point" as is graphically depicted on a plot of percent efficiency versus

$$\left((t_i - t_a)/I \right)$$

where:

t_i = Liquid inlet temperature ($^{\circ}\text{F}$)

t_a = Ambient temperature ($^{\circ}\text{F}$)

I = Incident flux per unit area ($\text{BTU}/\text{Hr} \cdot \text{Ft}^2$)

The abscissa term $\left((t_i - t_a)/I \right)$ was used to normalize the effect of operating at different values of I , t_i and t_a . The results are shown graphically in Figure 1 with the supporting test data given in Table I.

4.0 ANALYSIS AND RESULTS (Continued)

4.1 Thermal Performance Test (Continued)

Reference 2.3 uses the following terms relating to the thermal efficiency graph:

$F_R \alpha \tau$ = intercept of the efficiency curve on the ordinate axis

$F_R U_L$ = the negative of the slope of the efficiency curve

F_R = the solar heat removal factor

α = absorptance of the collector surface for solar radiation

τ = transmittance of the solar collector cover plate

U_L = solar collector heat transfer loss coefficient

A comparison of the before and after weathering efficiency curves indicates that the slope, $F_R U_L$, did not change significantly; however, the value of $F_R \alpha \tau$ did change drastically. With no noticeable change in the transmissivity of the cover plates, the conclusion would be that the overall absorptivity has degraded as a result of the weathering.

TABLE I
SOLARON COLLECTOR PERFORMANCE RECHECK
AFTER LONG TERM EXPOSURE TO NATURAL WEATHERING CONDITIONS
7.5 MPH WIND

Ambient Air Temperature (T_a), °F	75.0	77.5	79.0	80.2	80.6	80.9	74.7
Fluid Inlet Temperature (T_i), °F	83.6	82.5	85.8	85.9	125.2	167.0	163.4
Fluid Outlet Temperature (T_e), °F	128.3	127.5	133.3	133.1	152.2	170.6	168.5
Differential Fluid Temperature (ΔT), °F	44.7	45.0	47.5	47.2	27.0	3.6	5.1
Total Solar Flux (I), BTU/Hr·Ft ²	304.5	299.7	299.7	299.7	299.7	299.7	304.5
Flow Rate, SCFM	38	38	38	38	38	38	38
$(T_i - T_a)/I$ °F·Hr·Ft ² /BTU	.030	.017	.023	.019	.149	.287	.291
Efficiency (η), %	30.8	31.6	33.3	33.1	17.6	2.2	3.1

○ Before Long Term Weathering
□ After Long Term Weathering

Figure 1. Solaron (Air) Collector Indoor Thermal Performance Test Results