**SIMULATION OF LANDSCAPE DISTURBANCES
AND THE EFFECT OF CLIMATIC CHANGE**

Final Report

for Period July 15, 1990 - January 14, 1993

William L. Baker

**Department of Geography and Recreation
University of Wyoming
Laramie, Wyoming 82071**

April 1993

Prepared for

**THE U.S. DEPARTMENT OF ENERGY
AGREEMENT NO. DE-FG02-90ER60977**

MASTER

NOTICE

This report was prepared as an account of work sponsored by the United States Government. Neither the United States nor the Department of Energy, nor any of their employees, nor any of their contractors, subcontractors, or their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed or represents that its use would not infringe privately-owned rights.

TABLE OF CONTENTS

1. ABSTRACT	4
2. INTRODUCTION	5
3. OVERVIEW OF RESEARCH COMPLETED	5
4. RESEARCH STILL IN PROGRESS	11
5. BIBLIOGRAPHY	14
6. APPENDICES	16

A. Reprints

Baker, W.L. 1992. The landscape ecology of large disturbances in the design and management of nature reserves. *Landscape Ecology* 7: 181-194.

Baker, W.L. 1993. Spatially heterogeneous multi-scale response of landscapes to fire suppression. *Oikos* 66: 66-71.

Baker, W.L. and Y. Cai. 1992. The r.le programs for multiscale analysis of landscape structure using the GRASS geographical information system. *Landscape Ecology* 7: 291-302.

removed

B. Preprints

Baker, W.L. (in review). Spatial modeling of the restoration of landscape structure altered by fire suppression. *Environmental Management*, in review.

Baker, W.L. (in review). Longterm response of disturbance landscapes to human intervention and global change. *Landscape Ecology*, in review.

removed

C. SIMSCRIPT code for the DISPATCH model

D. Documentation for the r.le software programs

1. ABSTRACT

Altering the natural disturbance regime of a landscape produces changes in the structure of that landscape as the landscape adjusts to the new disturbance regime. A computer simulation model was designed to enable analyses of the longterm changes to be expected in landscapes as their disturbance regime changes. The model, DISPATCH, is the first dynamic spatial simulation model built around a geographical information system (GIS). The model also includes a new set of programs, the r.le programs, that is the first set of programs designed for calculating landscape structure measures within a GIS.

The DISPATCH model was used, in a series of experiments, to analyze the effects of human alterations of disturbance regimes (e.g., fire suppression, forest fragmentation) and global change (i.e., warming and cooling) on landscape structure. Landscapes do not adjust quickly to these alterations, requiring 1-2 times the rotation time (the amount of time required for the disturbance regime to disturb a land area equal to the area of a particular landscape), which in landscapes of the western United States and Canada can be several decades to several centuries, based on available data. Landscapes subjected to warming or to longterm fire suppression experience a decline in patch richness, Shannon diversity, the amount of edge and contrast, but an increase in distance between patches, angular second moment (texture measure) and patch size. In contrast, landscapes subjected to cooling, the short-term effects of fire suppression, fragmentation, or traditional prescribed burning tend to respond with increasing richness, Shannon diversity, edge, and contrast, but declining distance, angular second moment, and size. The pattern of response is different at different scales, with important implications for species.

2. INTRODUCTION

This is the final report for the last two years of a three-year project begun at the University of Kansas (DE-FG02-89ER60883), but continued after year 1 as this contract at the University of Wyoming. That earlier contract produced the following publications, which are the background for this final report:

Baker, W.L. , S.L. Egbert, and G.F. Frazier. 1991. A spatial model for studying the effects of climatic change on the structure of landscapes subject to large disturbances. *Ecological Modelling* 56: 109-125.

Baker, W.L. 1992. Effects of settlement and fire suppression on landscape structure. *Ecology* 73(5): 1879-1887.

The first of these publications describes the DISPATCH model and illustrates its use, while the second publication is an application of the DISPATCH model to a specific problem.

3. OVERVIEW OF RESEARCH COMPLETED

3.1. The DISPATCH model and r.le programs

The DISPATCH model was described in Baker et al. (1991). The model consists of three major components (Fig. 1). First, there is a driver program written in SIMSCRIPT II.5 (CACI 1987) that runs the model. The driver program contains code for reading in the

Fig. 1

model parameters and keeping track of model processes, including executing the disturbance regime, manipulating the maps of disturbances, and calling the r.le programs. The SIMSCRIPT II.5 code for the model is in Appendix D. The second component of the model is the GRASS geographical information system (GIS) (USA-CERL 1991), whose GIS function library is extensively used by the driver program, and which is used to store and manipulate the maps of landscape structure.

The third component of the model is the set of r.le programs, which we wrote to enable calculation of landscape structure measures as the model runs, and which requires some explanation. When we began this project there was no existing software for landscape structure analysis which could be called directly from a running simulation model. Indeed, no one had, to our knowledge, ever used a GIS as an integral part of a dynamic simulation model. DISPATCH is the first ecological model to do so, and its development required more effort than we had expected, particularly in creating the r.le programs and linking them with the simulation model.

Creating this set of programs proved difficult, as there were many algorithms that had to be designed and coded that are new GIS algorithms. We had some difficult technical problems to overcome, such as the inability of existing GIS algorithms to quickly and accurately convert a map from raster to vector. This problem alone required us to write difficult new algorithms for raster manipulation of polygon data. For example, we had to develop a new algorithm for determining when a point is within a polygon, a common GIS problem easily implemented in vector format, but one for which there was no algorithm for use with raster data (Laurini and Thompson 1992). Moreover, while we were writing the r.le programs GRASS was released in a major revision that required us to spend a large part of a year updating the code we had written.

The result of this substantial effort on the r.le programs is a software package tightly integrated with GRASS that is of general utility for calculating common landscape measures using this GIS either for static analyses or as a component of dynamic simulation models such as DISPATCH. Work on the algorithmic development was a Master's Thesis for Yunming Cai (Cai 1991). The r.le package is described in Baker and Cai (1992) which is reproduced in Appendix A, and the documentation for the package is in Appendix D. The code for the r.le package is available from USA-CERL's ftp server (129.229.20.254) in the "incoming" directory (file rle.tar.Z). The programs require GRASS and a Sun Sparcstation with Sun's operating system and Open Windows.

3.2. The DISPATCH model and simulation of fire suppression

The DISPATCH model described by Baker et al. (1991) in a conceptual overview was simplified and used to simulate changes in a natural disturbance regime produced by suppression of fires and the restoration of a natural fire regime in an area subjected to fire suppression with support from grant DE-FG02-89ER60883 at the Univ. of Kansas. The initial purpose of these simulations was primarily to use a simple version of the model to see how altering a disturbance regime affected model behavior and model output. The fire record for the Boundary Waters Canoe Area (BWCA) was used as it is one of the finest spatial fire history records available. The BWCA fire record consists of reconstructed maps of fires over three centuries, before and after human alteration of the disturbance regime (Heinselman 1973).

As it turned out, the results from this initial simulation work (Baker 1992) were more interesting than we had expected, and we took the liberty to follow up on these results, when the work was continued at the Univ. of Wyoming, because this modelling

work was consistent with the general theme of how landscape structure changes as a disturbance regime changes. The result is two additional articles on the fire suppression theme concerning: (1) the effects of fire suppression at multiple scales, and (2) the effects of reinstating a natural fire regime within the BWCA after a period of fire suppression.

The findings from the initial simulation of the effects on the whole BWCA are reported in Baker (1992) and briefly summarized here to provide background for discussing the two articles mentioned above. Fire suppression produced an immediate response in only a few measures of landscape structure (shape, Shannon diversity, and richness), a delay for several decades in the case of two other measures (age, fractal dimension), and a delay for hundreds of years in the case of still other measures (size, angular second moment). In contrast, a brief period of smaller and more frequent burning associated with the settlement period near the BWCA in general produced a stronger and more immediate response.

This led to the idea that the pattern of response of a landscape to alteration of its disturbance regime is governed by the rather odd dynamics of patch populations (Baker 1992). Patch population dynamics is a zero-sum-game in which patch births cause patch deaths, and the birth of larger patches usually means more patch deaths. The result is that both the size distribution of patch births (disturbance size distribution) and the distribution of times between patch births (disturbance interval distribution) control the pattern of response in the landscape.

3.3. The multiscale response to fire suppression

This pattern of response is quite different at different scales, and this has important implications for the species living in landscapes whose disturbance regime is changing.

The results of simulation experiments to examine the multiscale nature of the response are reported in Baker (1993), which is reproduced in Appendix A. The first significant finding of this research is that as the scale of observation becomes finer, there are more substantial differences (lags) in the timing of a suppression effect when parts of the same landscape are compared. For example, the effect of suppression on mean patch size is lagged 50 yr between the two halves of the BWCA, but as much as 100 yr between the four quarters of the BWCA.

This spatial lag occurs because the location of a suppression effect is really restricted to the region that would have burned had suppression not occurred, and this area radiates out from the location of an ignition. Thus the parts of the landscape that respond most rapidly to suppression are the places where post-suppression fires initiate. The remainder of the landscape remains unchanged. There is reason to believe that this result is very general; that is, as a disturbance regime shifts, the part of the landscape that responds most rapidly to the shift is the part that receives the new disturbances. The remainder of the landscape may remain adjusted to the old disturbance regime.

An important implication of this finding is that species with different home ranges or ecological neighborhoods will experience different patterns of change in the same landscape. Species that have small neighborhoods may experience rapid changes if their territories are within those parts of the landscape that respond immediately; however, these species should be able to locate habitat refugia in the parts of the landscape that have not changed. In contrast, species that have larger home ranges will tend to average out the spatially heterogeneous consequences of alteration in the disturbance regime, but they will not be able to find refugia as easily.

3.4. The restoration experiment

This purpose of this experiment was to see whether a landscape subjected to fire suppression would return to its pre-suppression landscape structure if the pre-suppression disturbance regime were reinstated. The results of this experiment are reported in Baker (in review), which is reproduced in Appendix B. The results suggest that the altered landscape structure produced by 82 years of fire suppression can be generally restored within 50-75 years after reinstatement of the pre-suppression disturbance regime. However, some measures responded more rapidly than did others.

3.5. The synthesis paper using the DISPATCH model

The simulation research with fire suppression suggested that landscapes might respond in an similar manner to similar changes in the disturbance regime, regardless of the source of the change (e.g., global warming, forest fragmentation), and a final set of experiments was undertaken to try to derive a general theory about the response of landscapes to alterations in their disturbance regimes. The results of this set of experiments are summarized in a paper submitted to Landscape Ecology, and reproduced in Appendix B. In this synthesis work we compared the results of simulating climatic changes (global warming and cooling) with the effect of human land uses (fragmentation and restoration) on the structure of a generalized temperate-zone forested disturbance landscape over 400 years.

We found that landscapes require 1-2 rotations (defined as the time required to disturb an area equal to the area of the particular landscape) to adjust to a new disturbance regime no matter how the disturbance regime is changed. However, the structure of the new landscape is strongly controlled by both the size and interval

distributions of the new disturbance regime. We found that the density of patches in the initial landscape had relatively little effect on the rate of adjustment. The result is that new disturbance regimes that decrease the rotation time, either because of larger disturbances or more frequent disturbances (or both), will result in more rapid adjustment in landscape structure than will regimes that increase the rotation time. It matters little whether the alteration in the disturbance regime comes from changes in climate or human land uses, so that there is a set of disturbance regime alterations that can be expected to produce similar patterns of change in landscape structure (Fig. 2). The actual amount of change in a particular measure and the comparative order in which different measures respond are determined by the relative amounts of change in the disturbance size and interval distributions. Two landscapes with the same rotation time will adjust in about the same time period, but may end up with quite different structures depending on the characteristics of these two distributions.

4. RESEARCH STILL IN PROGRESS

4.1. A physically-based model of flood disturbance on the Animas River

We collected extensive field data from the Animas River in southwestern Colorado's San Juan Mountains with the goal of developing a physically-based model of the effects of climatic fluctuations on the landscape structure produced by floods along this river. This model was to have been a refinement of the DISPATCH model for a specific location and disturbance regime. We used tree-ring analysis to reconstruct the year of origin of 86 flood-produced patches found along a 6 km reach of this river, and we mapped and

KINDS OF CHANGES:

EFFECT ON DISTURBANCE REGIME:

EFFECT ON LANDSCAPE STRUCTURE:

Lower Richness
 Lower Shannon Diversity
 Less Edge
 Less Contrast
 Larger Distance
 Larger Ang. Sec. Mom.
 Larger Size

Higher Richness
 Higher Shannon Diversity
 More Edge
 More Contrast
 Smaller Distance
 Smaller Ang. Sec. Mom.
 Smaller Size

digitized the boundary of each patch based on scanned aerial photography. We also collected data on the vegetation composition of each patch and its tree population structure. We surveyed 36 valley cross-sections along the reach and then attempted to use the GRASS GIS to construct a digital elevation model (DEM) of the reach. We used the cross-sectional data with the U.S. Army Corps of Engineers' HEC-2 model to reconstruct water surface elevations at each of the 36 valley cross-sections for 20 levels of streamflow spanning the range of historical streamflow, based on U.S.G.S. data from the Durango gauging station downstream of the study reach. We planned to use the GIS to produce interpolated maps of water depth for the reach for each of the 20 levels of discharge, and then to use these maps to determine the stream power that produced each of the 86 mapped disturbances. The final link was to reconstruct the regional synoptic weather pattern present on each day that produced one of the mapped disturbances.

From these data sets, we planned to calibrate a physical model that could be used to simulate changing synoptic weather patterns, the occurrence of floods, and the physical process by which an existing forest stand along the reach is destroyed as stream power exceeds the resisting ability of the trees. This model would then have been run with different climatic scenarios and the changing pattern of landscape structure would have been monitored with the r.le programs. This would enable an assessment of the possible changes in landscape structure along the river reach that might accompany climatic change.

However, we expended considerable time trying to develop a reasonable DEM for the reach from the 36 surveyed valley cross-sections, and this critical step was unsuccessful. As it turns out there are no existing algorithms that we could find that can adequately create a DEM from the kind of cross-sectional survey data that are traditionally

used to quantify stream morphology. Our mistake was to follow these traditional techniques. The problem is that cross-sections are traditionally placed in the center of rather uniform subreaches that have a consistent cross-sectional morphology. This does not produce a data density along the longitudinal profile that is comparable to the data density along the cross-section. Common interpolation algorithms, including quadrant specific algorithms, cannot adequately interpolate the longitudinal profile from these kinds of data. A dense, somewhat evenly spaced grid of points, or mapped contour lines is what is needed. Another problem is that considerable precision is needed in the interpolation as water depths at high discharge along this reach may only be 1-2 m.

We were very frustrated by this problem, but now know that a more extensive survey will be needed using a global positioning system. We are not giving up on completing this modelling effort as we believe it has potential to be very interesting, but funding to complete this research will have to be obtained elsewhere, and unfortunately the physically-based model and simulations cannot be completed until we can construct a precise DEM for the river reach.

4.2. Vegetation patterns and succession along the Animas River

As mentioned above, we collected data on the vegetation composition and tree population structure within each patch along the Animas River study reach. A Master's thesis is in progress, by Gillian Walford, to analyze these data. This thesis will consist of two publishable articles. The first is an analysis of vegetation variation along the reach in relation to the geomorphology of the river produced by disturbance. The second is an analysis of successional patterns along the reach following disturbance. A significant finding of this research is that a few of the disturbances have had much more effect than

the others. One of the disturbances, a major flood in 1927 A.D., may have completely changed the pattern of succession along the river reach. The implication of this is that not all disturbances are of equal importance. Modelling the effect of climatic change on disturbance regimes may be most meaningful from the species standpoint if focused on the kinds of disturbances represented by the 1927 flood, which resulted from a tropical cyclone that crossed Mexico and Arizona and then stalled against the San Juan Mountains.

This thesis research will provide a link between the modelling of landscape structure and the plant species that live in, and presumably are adapted to the changing structure of this disturbance landscape.

5. BIBLIOGRAPHY

Baker, W.L. 1992. Effects of settlement and fire suppression on landscape structure.

Ecology 73: 1879-1887.

Baker, W.L. 1993. Spatially heterogeneous multi-scale response of landscapes to fire suppression. Oikos 66: 66-71.

Baker, W.L., in review. Spatial modeling of the restoration of landscape structure altered by fire suppression. Environmental Management, in review.

Baker, W.L. and Y. Cai. 1992. The r.le programs for multiscale analysis of landscape structure using the GRASS geographical information system. Landscape Ecology 7: 291-302.

Baker, W.L., S.L. Egbert, and G.F. Frazier. 1991. A spatial model for studying the effects of climatic change on the structure of landscapes subject to large disturbances.

Ecological Modelling 56: 109-125.

CACI, Inc. 1987. SIMSCRIPT II.5 programming language. CACI Products Co., La Jolla, CA.

Cai, Yunming. 1991. GLE-Landscape ecological analysis software using the GIS GRASS. Master's thesis, University of Wyoming, Laramie, Wyoming. 137 pp.

Heinselman, M.L. 1973. Fire in the virgin forests of the Boundary Waters Canoe Area, Minnesota. Quat. Res. 3: 329-382.

Laurini, R. and D. Thompson. 1992. Fundamentals of spatial information systems. Academic Press, London.

USA-CERL. 1991. GRASS 4.0 user's reference manual. United States Army Construction Engineering Research Laboratory, Champaign, Illinois.

6. APPENDICES

APPENDIX C. SIMSCRIPT CODE FOR THE DISPATCH MODEL

```

////////////////////////////////////
" M O D E L   L A Y O U T                               "
"                                                         "
"   routine DISTINT selects a disturbance interval from a   "
"       distribution of disturbance intervals                 "
"   routine DISTGEN selects a disturbance size from a       "
"       distribution of disturbance sizes                     "
"   routine DISTPROB combines the layers in the GIS to create a "
"       layer, DISTPROB_REAL, containing the probability of  "
"       being disturbed at each location in the landscape   "
"   routine DISTLOC checks for possible disturbance          "
"       locations, and places the disturbance into the landscape "
"   routine DISTSPR moves the disturbance to adjoining      "
"       cells                                                 "
"   routine SAMPINT selects a time interval to wait before  "
"       measuring landscape structure                         "
"                                                         "
////////////////////////////////////
"
"
////////////////////////////////////
" M O D E L   I N S T A L L A T I O N / A D J U S T M E N T S "
"                                                         "
" The model and its subdirectories should be as follows:      "
"                                                         "
"   ~/model/          = directory containing model         "
"   ~/model/loadmodel  = command file that loads           "
"                       model.sim & libraries               "
"   ~/model/loadmodelg = command file that loads           "
"                       model.sim & libraries               "
"                       when using histograms               "
"   ~/model/model.sim   = this code                         "
"   ~/model/graphics.sg2 = optional SIMGRAPHICS II         "
"                       file when using histogram          "
"                       display mode                       "
"   ~/model/lib/model_lib.c = C code with tie to GRASS      "
"   ~/model/params/params.display = file containing parameters "
"                       specifying how to display          "
"                       used by model_lib.c                "
"   ~/model/params/params.model = file containing the model "
"                       parameters                         "
"   ~/model/params/params.reclass = file specifying parameters "
"                       specifying how to reclass          "
"                       the map into age classes           "
"                       used by model_lib.c                "
"   ~/model/params/rules.file = file specifying the colors  "
"                       to be used to display              "
"                       used by model_lib.c                "
"   ~/model/r.le.para/   = directory containing files      "
"                       specifying the sampling             "
"                       framework; created by               "
"                       r.le.setup                          "
"   ~/model/r.le.out/    = directory containing the        "
"                       output files from the               "
"                       r.le analyses                       "
"   ~/model/tempmap/     = directory containing the        "
"                       temporary maps created              "
"                       by the program                      "
"                                                         "
" To change this program for another installation, you must correct "
" the following:                                              "

```

```

1. Enter the correct directory path for the file
   distprob.ascii, which is read into the array
   DISTRPROB_INT in routine DISTPROB, and the correct
   recordsize

2. Adjust the values used to reclass the raw age layer into
   age classes for display by modifying file
   params.reclass currently in /home/grass/model/params

3. Adjust the class intervals for the histograms of mean
   disturbance size and interval by changing the values
   in the TALLIES section of the preamble

4. The number of class intervals is currently set at 15. If
   you change this, you will need to change the format
   for printing these out. See section #2 in the list
   of operations completed each year in the MAIN section
=====
MODEL SETUP : NON - HISTOGRAM MODE
=====
The following must also be completed before the model is started:

1. Start grass4.0, start the monitor by entering d.mon
   start=x0, then d.mon select=x0; resize the window.
2. Go to /home/grass/model and run r.le.setup to set up the
   sampling method for analyzing landscape structure.
3. Compile this code (simc -C model.sim) if not already done
4. Compile the model_lib.c file by typing gcc in the lib
   directory if not already done
5. Return to /home/grass/model and type loadmodel, then
   a.out to start the model
=====
MODEL SETUP : HISTOGRAM DISPLAY MODE
=====
The following must also be completed before the model is started:

1. Start grass4.0, start the monitor by entering d.mon
   start=x0, then d.mon select=x0; resize the window.
2. Go to /home/grass/model and run r.le.setup to set up the
   sampling method for analyzing landscape structure.
3. Remove the comment marks from the two sections with
   comment marks followed by the number one
4. Recompile this code (simc -C model.sim).
5. Make sure the SIMGRAPHICS II file graphics.sg2 exists in
   the /home/grass/model directory
6. Compile the model_lib.c file by typing gcc in the lib
   directory if not already done
7. Return to /home/grass/model and type loadmodelg, then
   a.out to start the model
=====
preamble
=====
DEFINE VARIABLES

```

```

////////////////////////////////////
//
//      * * * * *
//      * VARIABLE TYPES (E.G. REAL) MUST BE EXPLICITLY *
//      *   DECLARED                                     *
//      * * * * *
//
//      normally, mode is undefined
//
//
//      NONSIMSCRIPT ROUTINES in lib/model_lib.c
//
//      define annual_updt as a nonsimscript routine
//      which adds one to the AGE layer in grass
//      at the end of a year
//
//      define initdistmap as a nonsimscript routine
//      which initializes the disturbance map prior
//      to starting the model
//
//      define initlayer as a nonsimscript routine
//      which copies a random cell layer into the
//      initial layer for the model to start with
//
//      define make_distprob as a nonsimscript routine
//      which makes DISTPROB using grass
//
//      define putnum as a nonsimscript routine
//      which calls fprintf to print out the
//      disturbance map (DISTMAP)
//
//      define reclass_map as a nonsimscript routine
//      which reclasses the current AGE map prior to display
//
//      define save_grass_layer as a nonsimscript routine
//      which saves a GRASS layer to a file for later analysis
//
//      define screenputnum as a nonsimscript routine
//      which writes ascii disturbance map values to the
//      screen, one cell at a time
//
//      define show_map as a nonsimscript routine
//      which displays the AGE map in a GRASS graphics window
//
//      define sstruct as a nonsimscript routine
//      which calls landscape measurement modules
//
//      define update_map as a nonsimscript routine
//      which updates the current AGE map
//
//      define write_ascii as a nonsimscript routine
//      which adds header information to DISTMAP
//      so that it fits the GRASS format
//
//      define write_distprob_ascii as a nonsimscript routine
//      which takes the GRASS layer created in make_distprob
//      and writes it out as an ascii file
//
//
//      INTEGER VARIABLES

```

```

''
    define BUF as an integer variable
''
        used to hold temporary results
''

    define CURRENT_DISTURB_SIZE as an integer variable
''
        which contains the current disturbance size
''
        in pixels
''

    define DISTURB_INTERVAL as an integer variable
''
        which is the time in years between disturbances
''

    define DISTURB_INTERVAL_CHOICE as an integer variable
''
        which is 1 if the Weibull distribution of
''
        disturbance intervals is to be used, and is 2 if
''
        an empirical distribution of disturbance intervals
''
        is to be used.
''

    define DISTURB_SIZE_CHOICE as an integer variable
''
        which is 1 if disturbance size is based on an
''
        exponential distribution, and is 2 if size is
''
        based on a normal distribution
''

    define DISTURB_YR as an integer variable
''
        which is the year in which a disturbance occurs
''

    define DONE as an integer variable
''
        which is 0 when routine DISTLOC option 3 is not
''
        done and is 1 when it is done
''

    define i, j as integer variables
''
        used to index arrays
''

    define LOC_OPTION as an integer variable
''
        which indicates which option is to be used for
''
        choosing where to start the disturbance
''

    define MAP_CHOICE as an integer variable
''
        which is 1 if map output is to be displayed
''
        during model run, and is 0 if not
''

    define MAX_LOC_ROW and MAX_LOC_COL as integer variables
''
        which contain the row and column locations for the
''
        maximum disturbance probability in DISTPROB_REAL
''

    define MAXR, MAXC as integer variables
''
        which are the row and col of the neighboring pixel
''
        that contains the maximum disturbance probability
''

    define NROW, NCOL as integer variables
''
        which keep track of how many rows and columns
''
        there are in the model area
''

    define OVER as an integer variable
''
        which is used in routine DISTSPR option 2
''
        to determine whether a loop should be stopped
''

    define PREVDIST_COL, PREVDIST_ROW as integer variables
''
        which contain the location of the previous disturbed
''
        cell
''

```

```

define R, C as integer variables
''      which contain the row and col location as the
''      disturbance spreads from pixel to pixel
''

define SAMP_INTERVAL as an integer variable
''      which is the current time to wait before
''      measuring landscape structure
''

define LAST_SAMP_YR as an integer variable
''      which is the year the landscape structure
''      is measured
''

define LAST_SAVE_YR as an integer variable
''      which is the year the map was last saved
''

define SAVE_GAP as an integer variable
''      which is the number of years to skip before saving
''      a new copy of the AGE layer in the GRASS GIS
''

define SPREAD_OPTION as an integer variable
''      which contains 1 for option 1 or 2 for option 2
''

define START.YR, STOP.YR as integer variables
''      which are the starting and stopping years for the
''      simulation run
''

define STM_SIZE, STM_DISTURB, STM_LOC, STM_SAMP, STM_SPREAD
as integer variables
''      which specify the random number stream to use in
''      picking random numbers for disturbance size,
''      disturbance interval, disturbance location,
''      sampling interval, and disturbance spread
''

define TEMP_YEAR as an integer variable
''      which holds the YEAR for display
''

define TIES as an integer variable
''      which is the size of arrays TIESROW and PROBTIESROW
''

define YEAR as an integer variable
''      which keeps track of the current year in the model
''      run
''

define ZEROTIES as an integer variable
''      which keeps track of the number of zeros
''      among the 8 neighbors during the spread process
''

REAL VARIABLES

define DISTMAX as a real variable
''      which indicates the maximum potential value
''      in the GRASS DISTPROB layer
''

define DISTPROB_SUM as a real variable
''      which contains the cumulative sum of the disturb-
''      ance probabilities in the DISTPROB_REAL layer
''

define DISTPROB_TOT as a real variable
''      which contains the cumulative sum of the disturb-
''      ance probabilities in the 8 neighbors-used in

```



```

''         routine DISTSPR option 2
''
define DISTURB_SIZE as a real variable
''         which contains the size of the disturbance
''
define MAX as a real variable
''         which contains the value of the maximum disturbance
''         probability in the 8 neighboring pixels
''
define MAX_DISTPROB as a real variable
''         which contains the maximum disturbance probability in
''         DISTPROB_REAL. Used to find the location for
''         initiating a disturbance.
''
define MINIMUMDIST as a real variable
''         which is the minimum probability that must occur in
''         order for a disturbance to be initiated. This
''         is used with option 2 in routine DISTLOC
''
define RAND_LOC_VAL as a real variable
''         which contains the random value selected from
''         the cumulative sum of disturbance probabilities
''         in routine DISTLOC option 3
''
define RAND_SPR_VAL as a real variable
''         which contains the random value selected from
''         the cumulative sum of disturbance probabilities
''         in the 8 neighbors in routine DISTSPR option 2
''
define SAMP_MEAN as a real variable
''         which contains the mean interval between
''         measurements of landscape structure
''
define SAMP_STDEV as a real variable
''         which contains the standard deviation of
''         the mean interval between measurements of
''         landscape structure
''
define SIZE_EXPMEAN as a real variable
''         which contains the mean of the exponential
''         distribution of potential disturbance sizes
''
define SIZE_NORMEAN as a real variable
''         which contains the mean of the normal
''         distribution of potential disturbance sizes
''
define SIZE_NORSTDEV as a real variable
''         which contains the standard deviation of the
''         normal distribution of potential disturbance
''         sizes
''
define TEMP_INTERVAL as a real variable
''         which temporarily holds MEAN.DISTURB_INTERVAL
''         for display
''
define TEMP_SIZE as a real variable
''         which temporarily holds MEAN.DISTURB_SIZE for
''         display
''
define WEIBULL_SCALE as a real variable

```

```

''      which contains the Weibull scale parameter value.
''      This value is the value below which approximately
''      63% of the values in the distribution will lie
''
''      define WEIBULL_SHAPE as a real variable
''      which contains the Weibull shape parameter value.
''      This value ranges from 1.0 for an approximately
''      negative exponential distribution to 3.6 for an
''      approximately normal distribution to large values
''      (e.g. 20.0) for a highly negatively skewed
''      distribution
''
''      TEXT VARIABLES
''
''      define DISTURB_OUT as a text variable
''      which contains the name of the output file
''      for the history of disturbances that occur
''      during the model run
''
''      define DISTURB_TEMP as a text variable
''      which contains the word DISTURB, which is
''      the prefix for all DISTURB_OUT files
''
''      define FORMULA as a text variable
''      which contains the formula for calculating
''      disturbance probabilities
''
''      define GLEDIST as a text variable
''      which contains the r.le.dist landscape structure
''      analysis command and its parameters
''
''      define GLEPATCH as a text variable
''      which contains the r.le.patch landscape structure
''      analysis command and its parameters
''
''      define GLETEX as a text variable
''      which contains the r.le.dist landscape structure
''      analysis command and its parameters
''
''      define INIT_MAP as a text variable
''      which contains the name of the starting map
''      layer
''
''      define PARAMS_FILE_NAME as a text variable
''      which contains the name of the file containing
''      the model input parameters
''
''      define RUN as a text variable
''      which contains the ID for the run
''
''      define RUN_YR as a text variable
''      which contains the concatenation of RUN and YEAR
''
''      define YR_TXT1 as a text variable
''      which is used temporarily during concatenation
''      of RUN and YEAR
''
''      ARRAYS
''
''      define DISTMAP as an integer, 2-dimensional array

```

```

''      which is a map of the disturbance location
''
define DISTPROB_CUM as a real, 2-dimensional array
''      which is an array containing the cumulative sums
''      of disturbance probabilities in array DISTPROB_REAL
''
define DISTPROB_INT as an integer, 2-dimensional array
''      which is an array containing disturbance
''      probabilities
''
define DISTPROB_REAL as a real, 2-dimensional array
''      which is an array containing relativized disturbance
''      probabilities
''
define PROBTIESCOL as an integer, 1-dimensional array
''      which is the same as TIESCOL but used with option 2
''      in routine DISTLOC.
''
define PROBTIESROW as an integer, 1-dimensional array
''      which is the same as TIESROW but used with option 2
''      in routine DISTLOC.
''
define TIESCOL as an integer, 1-dimensional array
''      which holds column indices which are currently
''      tied as having the maximum probability of
''      disturbance. Used with option 1 in routine DISTLOC.
''
define TIESROW as an integer, 1-dimensional array
''      which holds row indices which are currently
''      tied as having the maximum probability of
''      disturbance. Used with option 1 in routine DISTLOC.
''
define ZEROTROW as an integer, 1-dimensional array
''      which holds row indices which are currently
''      tied as having a zero value in the disturbance
''      probability map.
''
define ZEROTCOL as an integer, 1-dimensional array
''      which holds column indices which are currently
''      tied as having a zero value in the disturbance
''      probability map.
''
''
''
RANDOM STEP VARIABLES
''
the system has an EMPIR_INTERVAL random step variable
define EMPIR_INTERVAL as an integer variable
''      which contains the empirical distribution of the
''      number of years between disturbances
''
''
FUNCTIONS
''
define CAN_CHECK as integer function
''      which keeps the disturbance from spreading off the map
''      or onto pixels that have already been disturbed
''
''
TALLIES
''

```

```

tally FREQ.DISTURB_INTERVAL(0 to 15 by 1)
  as the dynamic histogram of DISTURB_INTERVAL
tally FREQ.DISTURB_SIZE(0 to 3000 by 200)
  as the dynamic histogram of DISTURB_SIZE
tally MEAN.DISTURB_INTERVAL as the mean of DISTURB_INTERVAL
tally MEAN.DISTURB_SIZE as the mean of DISTURB_SIZE

//
//
// DISPLAY VARIABLES
//
// display variables include TEMP_YEAR, TEMP_SIZE,
// TEMP_INTERVAL
//
//
end
//
//
//
main
//
//
// READ IN NAME OF PARAMETERS FILE
//
//
// print 1 line thus
TYPE NAME OF PARAMETERS FILE:
// read PARAMS_FILE_NAME
//
//
// READ IN PARAMETERS AND RESERVE SPACE
//
//
// This section of the program reads in the model parameters
// from the parameters file. These parameters are:
//
// Line 1: XXXX XXXX Starting year and stopping year
// for model run
//
// Line 2: XXXX XXXX Row and column dimensions (in
// pixels) of the model area
//
// Line 3: XX XX XX XX Random number streams for the:
// (1) size distribution
// (2) disturbance interval
// distribution
// (3) location algorithm DISTLOC
// (4) sampling interval distribution
// (5) disturbance spread
//
// Line 4: X..X(20 chars) Run identification
//
// Line 5: X..X(20 chars) Name of starting map layer
//
// Line 6: X Display map output during the model
// run?
// 1 - do display
// 2 - don't display
//
// Line 7: XXX XXX XXX (1) Mean for the exponential size

```

```

distribution (real number)
(2) Mean for the normal size distribution (real number)
(3) St. deviation for the normal size distribution (real number)
Enter 0.0 for (2) and (3) if an exponential distribution is desired.
Enter 0.0 for (1) if a normal distribution is desired. If you enter a 0.0 for (3), sizes will all be equal to the mean (2).

Line 8: XXX.X XXX.X Shape and scale parameters for the Weibull interval distribution (real numbers)
Enter 0.0 0.0 if an empirical distribution will be entered instead.

Line 9: X Disturbance intervals?
      1 - Weibull distribution
      2 - empirical distribution

Line 10: XXXX XXXX XXXX (1) Number of years to skip before saving a new copy of a particular layer in the GRASS GIS for later display and analysis
(2) Last year a new copy of a particular layer was saved. Normally set equal to the starting year for the model run
(3) Last year that landscape structure was analyzed. Normally set equal to the starting year for the model run

Line 11: XXX.XX XXX.XX Mean and standard deviation (real) for normal distribution of time intervals between measurements of landscape structure. Set mean=0.0 if no measurement is desired. Set standard deviation =0.0 if fixed interval is desired

Line 12: X..X(80 chars) Landscape structure distance measure (r.le.dist) and parameters. Put 999 if not used. Enclose whole expression in single quotes (').

Line 13: X..X(80 chars) Landscape structure patch measure (r.le.patch) and parameters. Put 999 if not used. Enclose whole expression in single quotes (').

Line 14: X..X(80 chars) Landscape structure texture measure (r.le.tex) and parameters. Put 999 if not used. Enclose whole expression in single quotes (').

Line 15: XXXXXXXX Maximum potential value that raw disturbance probabilities will reach during the model run

```

```

''      Line 16: XX.XX      Minimum disturbance probability to be
''                          used with option 2 for locating
''                          disturbances
''
''      Line 17: X          Option for locating disturbances:
''                          1 - the disturbance is located
''                             randomly among locations
''                             that have tied disturbance
''                             probabilities
''                          2 - the disturbance is located
''                             randomly among locations that
''                             have a minimum probability of
''                             being disturbed
''                          3 - the disturbance is located
''                             in a probabilistic manner
''                             based on disturbance prob-
''                             abilities
''
''      Line 18: X          Option for spreading disturbances:
''                          1 - the disturbance is spread
''                             to the pixel, among the 8
''                             neighbors, that contains the
''                             highest disturbance
''                             probability.
''                          2 - the disturbance is spread
''                             probabilistically, according
''                             to the disturbance probabi-
''                             lities of the adjoining 8
''                             neighbors.
''
''      Line 19: X..X (120char) Equation for calculating disturbance
''                          probabilities from the layers in the
''                          GRASS GIS. Used by routine DISTPROB.
''                          Put the right side of the equation
''                          only, and put in single quotes.
''
''      Line 20+ X.XX XX ... Pairs of cumulative probability and
''                          sample values for the empirical
''                          disturbance interval distribution
''
''
''
''      * * * * *
''      * OPEN PARAMETERS FILE FOR INPUT *
''      * * * * *
''
open unit 1 for input, recordsize is 800,
  file name is PARAMS_FILE_NAME
use unit 1 for input
if ropenerr.v <> 0
  print 1 line thus
    Unable to open parameters file for input
  close unit 1
always
''
''
''      * * * * *
''      * READ IN THE STARTING AND STOPPING YEARS FOR THE *
''      * SIMULATION FROM PARAMETERS FILE LINE 1. *
''      * * * * *
''

```

```

read START.YR, STOP.YR

//
//
// *****
// * READ IN THE ROW & COLUMN DIMENSIONS OF THE *
// * MAP LAYERS, FROM PARAMETERS FILE LINE 2 *
// *****
//

read NROW, NCOL

//
//
// *****
// * READ IN THE RANDOM NUMBER STREAMS FROM PARAMETERS *
// * FILE LINE 3 *
// *****
//

read STM_SIZE, STM_DISTURB, STM_LOC, STM_SAMP, STM_SPREAD

//
//
// *****
// * READ IN THE RUN IDENTIFICATION FROM PARAMETERS FILE *
// * LINE 4 *
// *****
//

read RUN

//
//
// *****
// * READ IN THE STARTING MAP LAYER NAME FROM PARAMETERS *
// * FILE LINE 5 *
// *****
//

read INIT_MAP

//
//
// *****
// * READ IN THE CHOICE OF WHETHER TO DISPLAY MAP *
// * OUTPUT DURING THE MODEL RUN FROM PARAMETERS FILE *
// * LINE 6 *
// *****
//

read MAP_CHOICE

//
//
// *****
// * READ IN THE MEAN FOR THE EXPONENTIAL DISTRIBUTION *
// * OF POTENTIAL DISTURBANCE SIZES AND THE RANDOM NUMBER*
// * STREAM FROM PARAMETERS FILE LINE 7 *
// *****
//

read SIZE_EXPMEAN, SIZE_NORMEAN, SIZE_NORSTDEV

//
//
// *****
// * READ IN THE VALUE OF THE SHAPE AND SCALE PARAMETERS *
// * FOR THE WEIBULL DISTRIBUTION OF DISTURBANCE *
// * INTERVALS FROM PARAMETERS FILE LINE 8 *
// *****
//

read WEIBULL_SHAPE, WEIBULL_SCALE

```

```

//
//
// *****
// * READ IN THE CHOICE BETWEEN USING A WEIBULL DISTRI- *
// * BUTION (DISTURB_INTERVAL_CHOICE = 1) OR AN      *
// * EMPIRICAL DISTRIBUTION (DISTURB_INTERVAL_CHOICE = *
// * 2) OF DISTURBANCE INTERVALS FROM PARAMETERS FILE *
// * LINE 9                                           *
// *****
//
read DISTURB_INTERVAL_CHOICE
//
//
// *****
// * READ IN HOW MANY YEARS TO SKIP BEFORE SAVING    *
// * A LAYER IN GRASS FROM PARAMETERS FILE LINE 10    *
// *****
//
read SAVE_GAP, LAST_SAVE_YR, LAST_SAMP_YR
//
//
// *****
// * READ IN THE MEAN AND STANDARD DEVIATION FOR A    *
// * NORMAL DISTRIBUTION OF TIME INTERVALS BETWEEN    *
// * MEASUREMENTS OF LANDSCAPE STRUCTURE FROM PARAMETERS *
// * FILE LINE 11                                      *
// *****
//
read SAMP_MEAN, SAMP_STDEV
//
//
// *****
// * READ IN THE LANDSCAPE STRUCTURE MEASURE GLE.DIST *
// * AND ITS PARAMETERS FROM PARAMETERS FILE LINE 12 *
// *****
//
read GLEDIST as T *
//
//
// *****
// * READ IN THE LANDSCAPE STRUCTURE MEASURE GLE.PATCH *
// * AND ITS PARAMETERS FROM PARAMETERS FILE LINE 13 *
// *****
//
read GLEPATCH as T *
//
//
// *****
// * READ IN THE LANDSCAPE STRUCTURE MEASURE GLE.TEX  *
// * AND ITS PARAMETERS FROM PARAMETERS FILE LINE 14 *
// *****
//
read GLETEX as T *
//
//
// *****
// * READ IN THE MAXIMUM POTENTIAL VALUE FOR DISTPROB *
// * FROM PARAMETERS FILE LINE 15                      *
// *****
//

```



```

read DISTMAX
//
//
//      * * * * *
//      * READ IN THE MINIMUM DISTURBANCE PROBABILITY FROM *
//      * PARAMETERS FILE LINE 16                          *
//      * * * * *
//
read MINUMDIST
//
//
//      * * * * *
//      * READ IN THE OPTION FOR LOCATING DISTURBANCES FROM *
//      * PARAMETERS FILE LINE 17                          *
//      * * * * *
//
read LOC_OPTION
//
//
//      * * * * *
//      * READ IN THE OPTION FOR SPREADING DISTURBANCES FROM *
//      * PARAMETERS FILE LINE 18                          *
//      * * * * *
//
read SPREAD_OPTION
//
//
//      * * * * *
//      * READ IN THE FORMULA FOR CALCULATING DISTURBANCE *
//      * PROBABILITIES FROM PARAMETERS FILE LINE 19      *
//      * * * * *
//
read FORMULA
//
//
print 1 line with FORMULA thus
*****
//      * * * * *
//      * READ IN THE EMPIRICAL PROBABILITY DISTRIBUTION FOR *
//      * DISTURBANCE INTERVALS FROM PARAMETERS FILE LINES *
//      * 20+.                                             *
//      * * * * *
//
if DISTURB_INTERVAL_CHOICE = 2
  read EMPIR_INTERVAL
  always
  close unit 1
//
//
//
//      * * * * *
//      * OPEN UNIT 2 FOR OUTPUT OF DISTURBANCE INFO      *
//      * * * * *
//
let DISTURB_TEMP = "disturb."
let DISTURB_OUT = concat.f(DISTURB_TEMP,RUN)
open unit 2 for output,
  file name is DISTURB_OUT
use unit 6 for output
//

```

```

//
//
// *****
// * ALLOCATE MEMORY FOR ARRAYS *
// *****
//
//
// reserve DISTPROB_CUM(*,*) as NROW by NCOL
// reserve DISTPROB_INT(*,*) as NROW by NCOL
// reserve DISTPROB_REAL(*,*) as NROW by NCOL
// reserve DISTMAP(*,*) as NROW by NCOL
// reserve PROBTIESROW(*) as (NROW * NCOL)
// reserve PROBTIESCOL(*) as (NROW * NCOL)
// reserve TIESROW(*) as 8
// reserve TIESCOL(*) as 8
// reserve ZEROTROW(*) as 8
// reserve ZEROTCOL(*) as 8
//
//
//
//
// *****
// * MAIN PROGRAM *
// *****
//
//
// *****
// * INITIALIZE GRAPHICS ICONS TO DISPLAY HISTOGRAM *
// * OUTPUT DURING THE MODEL RUN *
// *****
//
//1 display TEMP_YEAR with "Zyear.grf"
//1 display TEMP_INTERVAL with "Zintmean.grf"
//1 display TEMP_SIZE with "Zsizemean.grf"
//1 show histogram FREQ.DISTURB_SIZE with "Zsizehist.grf"
//1 show histogram FREQ.DISTURB_INTERVAL
//1 with "Zinthist.grf"
//
//
// *****
// * INITIALIZE DISTURB_YR AND THE LAYER WITH WHICH THE *
// * MODEL BEGINS, GET THE FIRST DISTURBANCE INTERVAL, *
// * INITIALIZE THE DISTURBANCE MAP, MEASURE THE *
// * LANDSCAPE STRUCTURE OF THE INITIAL MAP IF SAMPLING *
// * WAS REQUESTED, AND GET THE FIRST SAMPLING INTERVAL *
// *****
//
//
// let DISTURB_YR = START.YR - 1
// call initlayer given INIT_MAP
// call DISTINCT
// call initdistmap
//
//
// let YR_TXT1 = ITOT.F(START.YR)
// let RUN_YR = CONCAT.F(RUN,"_",YR_TXT1)
//
//
// if LAST_SAMP_YR = START.YR
// call sstruct given RUN_YR, GLEDIST, GLEPATCH, GLETEx
// always
//
//
// if LAST_SAVE_YR = START.YR
// call save grass layer given RUN_YR

```

```

always
//
call SAMPINT
//
//*****
//      START THE ANNUAL LOOP      *
//*****
//
for YEAR = START.YR to STOP.YR
do
//
//      *****
//      * CONCATENATE THE RUN IDENTIFICATION AND YEAR TO USE *
//      * IN NAMING OUTPUT FILES                               *
//      *****
//
let YR_TXT1 = ITOT.F(YEAR)
let RUN_YR = CONCAT.F(RUN,"_",YR_TXT1)
//
let TEMP_YEAR = YEAR
//
//
//      *****
//      * PRINT INFORMATION ABOUT THE YEAR AND DISTURBANCES *
//      *****
//
print 2 lines with YEAR, DISTURB_YR, DISTURB_INTERVAL thus
~~~~~
START OF YR ****, LAST DISTURB YR ****, DISTURB INTERV **** YEARS
//
//
//      *****
//      * IF THE REQUIRED DISTURBANCE INTERVAL HAS PASSED *
//      * THEN:                                           *
//      * 1. GENERATE A DISTURBANCE AND RECORD THE YEAR *
//      * 2. PRINT THE DISTURBANCE INTERVAL AND SIZE    *
//      * 3. WRITE OUT THE DISTURBANCE YEAR, SIZE, AND  *
//      *   INTERVAL                                     *
//      * 4. INITIALIZE THE DISTURBANCE MAP              *
//      * 5. CALCULATE THE DISTURBABILITY OF THE LANDSCAPE *
//      * 6. LOCATE THE DISTURBANCE IN THE LANDSCAPE    *
//      * 7. SPREAD THE DISTURBANCE                     *
//      * 8. UPDATE THE AGE LAYER IN THE GIS             *
//      * 9. DETERMINE THE NEXT DISTURBANCE INTERVAL    *
//      * 10. END THE DISTURBANCE OPERATIONS            *
//      *****
//
If ((YEAR - DISTURB_YR) = DISTURB_INTERVAL)
//
//
//      *****
//      * 1. Generate a disturbance and store the year, then *
//      * use a temporary variable to produce a display of  *
//      * the cumulative mean disturbance size if the choice *
//      * was made to display graphic output during the model *
//      * run                                                *
//      *****
//
Call DISTGEN
let DISTURB_YR = YEAR

```

```

        let TEMP_SIZE = MEAN.DISTURB_SIZE
//
//
// *****
// * 2. Print the disturbance size *
// *****
//
        print 1 line with DISTURB_SIZE thus
DISTURB SIZE ***** PIXELS
//
//
// *****
// * 3. Write the disturbance year, disturbance size, *
// * and disturbance interval to a file *
// *****
//
        write YEAR, DISTURB_SIZE, DISTURB_INTERVAL as
            1 4, S 2, D(8,1), S 2, 1 4,/ using unit 2
//
//
// *****
// * 4. Initialize the disturbance map *
// *****
//
        let i = 0
        while i < NROW
        do
            let i = i + 1
            let j = 0
            while j < NCOL
            do
                let j = j + 1
                let DISTMAP (i, j) = 1
            loop
        loop
//
//
// *****
// * 5. Calculate the disturbability of the landscape *
// *****
//
        call DISTPROB
//
//
// *****
// * 6. Locate the disturbance in the landscape. *
// *****
//
        call DISTLOC
//
//
// *****
// * 7. Check to see if DISTPROB contains only 0's. If *
// * so, do nothing. If DISTPROB contains disturbable *
// * pixels, then spread the disturbance *
// *****

```

```

if R = 0
  print 1 line thus
    DISTPROB ALL 0's-NO DISTURBANCE
else
  call DISTSPR

```

```

*****
* 8. Update the age layer in the GRASS GIS to reflect *
* the effects of the disturbance. Use the following *
* external routines to do this:                      *
*   a. call putnum writes distmap.ascii, an ASCII   *
*       version of the DISTMAP array.                *
*   b. call write_ascii reads in distmap.ascii, and *
*       writes out distmap_whdr.ascii, which         *
*       contains the header information needed        *
*       to read DISTMAP data into GRASS.             *
*   c. call update_map reads distmap_whdr.ascii into*
*       GRASS using the GRASS Mimportcell           *
*       command, and then uses the Gmapcalc         *
*       command to change all the disturbed        *
*       locations in the AGE map to AGE=0           *
*****

```

```

for i = 1 to NROW
do
  for j = 1 to NCOL
do
  call putnum (DISTMAP(i,j), NROW, j, i)
loop
loop
call write_ascii
call update_map
always

```

```

*****
* 9. Determine the next disturbance interval, then  *
* use a temporary variable to produce the display of *
* cumulative mean disturbance interval if the choice *
* was made to display graphic output during the model *
* run                                                *
*****

```

```

Call DISTINT
let TEMP_INTERVAL = MEAN.DISTURB_INTERVAL

```

```

*****
* 10. End the operations that were done only if the *
* disturbance interval had passed and a new disturb- *
* ance had occurred                                *
*****

```

```

always

```

```

//
//
//
// *****
// * BEGIN THE OPERATIONS THAT HAPPEN EVERY YEAR *
// * REGARDLESS OF DISTURBANCE. THESE INCLUDE: *
// * 1. DISPLAY THE LAST DISTURBANCE MAP AND THE *
// * CURRENT MAP IF GRAPHIC OUTPUT WAS *
// * REQUESTED DURING THE MODEL RUN *
// * 2. SAVE THE MAP FOR LATER ANALYSIS, IF THE *
// * INTERVAL TO SKIP BEFORE SAVING HAS PASSED *
// * 3. ADD A YEAR TO THE AGE OF EACH PIXEL IN THE *
// * AGE LAYER OF THE GRASS GIS *
// * 4. PRINT INFORMATION ABOUT SAMPLING *
// * 5. ANALYZE LANDSCAPE STRUCTURE IF IT'S TIME *
// *****
//
// *****
// * 1. Display the last disturbance map and the current *
// * age map if graphic output was requested during the *
// * model run. Use external routines to do this *
// *****
//
//     if MAP_CHOICE = 1
//         call reclass_map
//         call show_map given RUN_YR
//     always
//
//
// *****
// * 2. Save a map for later analysis, if the time *
// * interval to skip before saving has passed. Use an *
// * external routine to save the map. *
// *****
//
//     if ((YEAR-LAST_SAVE_YR) = SAVE_GAP)
//         call save_grass_layer given RUN_YR
//         let LAST_SAVE_YR = YEAR
//     always
//
//
// *****
// * 3. Add a year to the age of each pixel in the age *
// * layer of the GRASS GIS. Use an external routine *
// * called annual_updt, which uses the GRASS Gmapcalc *
// * command to add 1 to every pixel in the AGE map *
// *****
//
//     call annual_updt
//
// *****
// * 4. Print information about sampling *
// *****
//
//     print 1 line with YEAR, LAST_SAMP_YR, SAMP_INTERVAL thus
// MIDDLE OF YR ****, LAST SAMPLING YR ****, SAMPLING INTERV **** YEARS
//
//

```

```

//      * * * * *
//      * 5. Analyze landscape structure using the external *
//      * routine sstruct if it's time to do so.          *
//      * * * * *
//
      if ((YEAR-LAST_SAMP_YR) = SAMP_INTERVAL)
        call sstruct given RUN_YR, GLEDIST, GLEPATCH, GLETEX
        let LAST_SAMP_YR = YEAR
        call SAMPINT
      always
//
//
// * * * * *
//      END THE ANNUAL LOOP AND THE MAIN PROGRAM          *
// * * * * *
//
      print 4 lines with YEAR thus
END OF YEAR ****
-----

      if YEAR = STOP.YR
        if LAST_SAVE_YR <> STOP.YR
          call save_grass_layer given RUN_YR
        always
        if LAST_SAMP_YR <> STOP.YR
          call sstruct given RUN_YR, GLEDIST, GLEPATCH, GLETEX
        always
      always
    loop
end
//
//
//
//
//
//
//
// * * * * *
//      * THIS ROUTINE SELECTS A DISTURBANCE SIZE FROM AN *
//      * EXPONENTIAL DISTRIBUTION OF DISTURBANCE SIZES WHOSE *
//      * MEAN IS SIZE_EXPMEAN OR FROM A NORMAL DISTRIBUTION *
//      * WITH MEAN SIZE_NORMEAN & STANDARD DEVIATION        *
//      * SIZE_NORSTDEV                                         *
//      * * * * *
//
//
      let DISTURB_SIZE = 0.0
      if SIZE_EXPMEAN > 0.0
        let DISTURB_SIZE = EXPONENTIAL.F(SIZE_EXPMEAN,STM_SIZE)
      else
        if SIZE_NORSTDEV = 0.0
          let DISTURB_SIZE = SIZE_NORMEAN
        else
          let DISTURB_SIZE = NORMAL.F(SIZE_NORMEAN,SIZE_NORSTDEV,

```

```

                                STM_SIZE)

    always
    always
    return

end
//
//
//
routine DISTINT
//
// *****
// * THIS ROUTINE SELECTS A DISTURBANCE INTERVAL FROM A *
// * WEIBULL DISTRIBUTION WHOSE PARAMETERS ARE *
// * WEIBULL_SCALE AND WEIBULL_SHAPE (IF DISTURB_INTER- *
// * VAL_CHOICE EQUALS 1), OR FROM AN EMPIRICAL *
// * DISTRIBUTION (IF DISTURB_INTERVAL_CHOICE EQUALS 2) *
// *****
//
    if DISTURB_INTERVAL_CHOICE = 0
        print 1 line thus
            No disturbance interval distribution selected!
    always
    if DISTURB_INTERVAL_CHOICE = 1
        let DISTURB_INTERVAL =
TRUNC.F(WEIBULL.F(WEIBULL_SHAPE,WEIBULL_SCALE,STM_DISTURB))
    always
    if DISTURB_INTERVAL_CHOICE = 2
        let DISTURB_INTERVAL = EMPIR_INTERVAL
    always
    return

end
//
//
//
routine DISTLOC
//
// *****
// * THIS ROUTINE INITIATES THE DISTURBANCE WITHIN A *
// * SINGLE CELL USING THREE OPTIONS: *
// * 1. THE DISTURBANCE IS INITIATED RANDOMLY *
// * AMONG TIED OCCURRENCES (IF THERE ARE ANY) OF *
// * MAXIMUM DISTURBANCE PROBABILITY. *
// * 2. THE DISTURBANCE IS INITIATED RANDOMLY *
// * AMONG THOSE CELLS THAT HAVE SOME MINIMUM *
// * PROBABILITY OF BEING DISTURBED. IF THERE ARE *
// * NO CELLS ABOVE THE MINIMUM VALUE, THEN NO *
// * DISTURBANCE OCCURS *
// * 3. THE DISTURBANCE IS INITIATED IN A PROB- *
// * ABILISTIC WAY. EACH CELL HAS A CHANCE OF *
// * BEING DISTURBED THAT IS PROPORTIONAL TO ITS *
// * DISTURBABILITY (DISTPROB) VALUE. *
// *****
//
//
// *****
// * Initialize PROBTIESROW, PROBTIESCOL, and TIES *
// *****
//
    for i = 1 to (NROW * NCOL)
do

```



```

        let PROBTIESROW(i) = 0
        let PROBTIESCOL(i) = 0
loop
let TIES = 0
//
//
//
//      * * * * *
//      * Option number 1 *
//      * * * * *
//
//
//      if LOC_OPTION = 1
//
//
//      a. Initialize the variables
//
//
//      i = 0
//      let MAX_DISTPROB=0.0
//      let MAX_LOC_ROW=0
//      let MAX_LOC_COL=0
//
//
//
//      b. Search the disturbance probability array for the maximum
//      value
//
//
//      while i < NROW
//      do
//          i = i + 1
//          j = 0
//          while j < NCOL
//          do
//              j = j + 1
//              if DISTPROB_REAL(i, j) > MAX_DISTPROB
//                  let MAX_DISTPROB = DISTPROB_REAL (i, j)
//                  let MAX_LOC_ROW = i
//                  let MAX_LOC_COL = j
//                  let TIES = 1
//                  let PROBTIESROW(1) = i
//                  let PROBTIESCOL(1) = j
//              else
//                  if DISTPROB_REAL(i, j) = MAX_DISTPROB
//                      let TIES = TIES + 1
//                      let PROBTIESROW(TIES) = i
//                      let PROBTIESCOL(TIES) = j
//                  always
//              always
//          loop
//      loop
//
//
//
//      c. Then set that location in the disturbance map layer,
//      DISTMAP, equal to 0, unless there are ties. If so, then
//      use the random number generator to choose among the ties
//
//
//      if TIES = 1
//          let DISTMAP(MAX_LOC_ROW,MAX_LOC_COL)=0
//          let R = MAX_LOC_ROW
//          let C = MAX_LOC_COL
//      else
//          let MAXR = RANDI.F (1, TIES, STM_LOC)
//          let R = PROBTIESROW (MAXR)

```

```

        let C = PROBTIESCOL (MAXR)
        let DISTMAP(R, C) = 0
    always
//
always
//
//
// *****
// * Option number 2 *
// *****
//
if LOC_OPTION = 2
//
//
// a. Initialize the variables
//
TIES = 0
i = 0
//
//
// b. Search the disturbance probability array for all cells
// that have a value above the minimum value for disturbance
//
while i < NROW
do
    i = i + 1
    j = 0
    while j < NCOL
    do
        j = j + 1
        if DISTPROB_REAL(i, j) > MINIMUMDIST
            let TIES = TIES + 1
            let PROBTIESROW(TIES) = i
            let PROBTIESCOL(TIES) = j
        always
    loop
loop
//
// c. If there are no ties, then no location is disturbable.
// Otherwise choose randomly among the tied locations.
//
if TIES = 0
    let R = 0
    let C = 0
else
    let MAXR = RANDI.F (1, TIES, STM_LOC)
    let R = PROBTIESROW (MAXR)
    let C = PROBTIESCOL (MAXR)
    let DISTMAP(R, C) = 0
always
//
always
//
//
// *****
// * Option number 3 *
// *****
//
if LOC_OPTION = 3
//

```

```

''
''      a. initialize variables and arrays
''
      let DISTPROB_SUM = 0.0
''
      let i = 0
      while i < NROW
      do
        let i = i + 1
        let j = 0
        while j < NCOL
        do
          let j = j + 1
          let DISTPROB_CUM(i,j) = 0.0
        loop
      loop

''
''      b. sum up the disturbance probabilities in the
''      DISTPROB_REAL layer, and make a new layer,
''      DISTPROB_CUM, which contains cumulative sums of
''      the values in DISTPROB_REAL
''
      let i = 0
      while i < NROW
      do
        let i = i + 1
        let j = 0
        while j < NCOL
        do
          let j = j + 1
          let DISTPROB_SUM = DISTPROB_SUM + DISTPROB_REAL(i,j)
          let DISTPROB_CUM(i,j) = DISTPROB_SUM
        loop
      loop

''
''      c. select a random number between 0 and the total of all
''      the disturbance probabilities (DISTPROB_SUM), then find
''      the cell in the DISTPROB_CUM layer that corresponds to
''      that random number. This is the cell where the disturb-
''      ance is initiated.
''
      let RAND_LOC_VAL = UNIFORM.F(0.0, DISTPROB_SUM, STM_LOC)
''

      let i = 0
      let DONE = 0
      while (i < NROW) AND (DONE = 0)
      do
        let i = i + 1
        let j = 0
        while (j < NCOL) AND (DONE = 0)
        do
          let j = j + 1
          if RAND_LOC_VAL <= DISTPROB_CUM(i,j)
          let R = i
          let C = j
          let DISTMAP(R,C) = 0
          let DONE = 1
        always
      do

```

```

        loop
    always
    return
end
"
"
"
routine DISTPROB
"
"
" *****
" * THIS ROUTINE CALCULATES THE DISTURBABILITY OF THE *
" * LANDSCAPE BY CALLING EXTERNAL ROUTINES TO *
" * COMBINE THE GRASS LAYERS TO PRODUCE A MAP OF *
" * DISTURBANCE PROBABILITIES. *
" *****
"
"
"
" 1. Call the external routine make_distprob to read
" the equation for calculating disturbance prob-
" abilities, to use the GRASS Gmapcalc command to
" calculate disturbance probabilities, to create
" a new GRASS layer called DISTPROB, and to write it
" out as an ASCII file called distprob.ascii
"
" call make_distprob given FORMULA
"
"
"
" 2. Read in DISTPROB_INT from unit 10. Note that the
" "recordsize" is the maximum length of what SIMSCRIPT
" assumes are variable-length records. Make this
" number more than three times the number of columns
" in the model area
"
"
"
" open unit 10 for input, recordsize is 2000,
" file name is "/home/grass/model/tempmap/distprob.ascii"
" use unit 10 for input
" if ropenerr.v <> 0
" print 1 line thus
" Unable to open distprob.ascii for input
" close unit 10
" always
" for i = 1 to NROW
" do
" for j = 1 to NCOL
" do
" read BUF using unit 10
" let DISTPROB_INT(i,j) = BUF
" loop
" loop
" close unit 10
"
"
"
" 3. Relativize raw DISTPROB_INT values using DISTMAX.
" Put relativized values in DISTPROB_REAL.
"
"
"
" for i = 1 to NROW
" do
" for j = 1 to NCOL

```

```

do
  if (DISTMAX = 0.0)
    print 1 line thus
      DISTMAX is 0.0 - Can't divide by it.
  else
    let DISTPROB_REAL(i,j) =
      REAL.F(DISTPROB_INT(i,j))/DISTMAX
    always
  loop
loop

end
''
''
''
routine DISTSPR
''
''
''
  * * * * *
''
  * THIS ROUTINE USES A SPREAD ALGORITHM TO MOVE THE *
''
  * DISTURBANCE TO ADJOINING CELLS, UNTIL THE DISTURB- *
''
  * ANCE SIZE IS EQUAL TO THE POTENTIAL DISTURBANCE *
''
  * SIZE. AT EACH LOCATION THE ALGORITHM LOOKS ONLY AT *
''
  * THOSE NEIGHBORS THAT ARE NOT OFF THE EDGE OF THE *
''
  * MAP AND ARE NOT ALREADY DISTURBED. THERE ARE TWO *
''
  * OPTIONS: *
''
  * 1. SPREAD THE DISTURBANCE TO THE PIXEL WITH THE *
''
  * HIGHEST DISTURBANCE PROBABILITY. *
''
  * 2. SPREAD THE DISTURBANCE PROBABILISTICALLY WITH *
''
  * THE PROBABILITY OF SPREAD TO A PIXEL PROP- *
''
  * ORTIONAL TO ITS DISTURBANCE PROBABILITY *
''
  * * * * *
''
''
''
  * * * * *
''
  * Option number 1 *
''
  * * * * *
''

if SPREAD_OPTION = 1
''
''
''
  a. initialize variables
''

  let CURRENT_DISTURB_SIZE = 1
  let DISTPROB_REAL (R, C) = 0.0
''
''
''
  b. check to see if disturbance has completed spreading
''

  while (CURRENT_DISTURB_SIZE<trunc.f(DISTURB_SIZE))
''
''
''
  c. enter the main 8 neighbor search loop
''

do
  let TIES = 0
  let MAX = 0.0
  let ZEROTIES = 0
''

  if CAN_CHECK (R + 1, C + 1) = 1
    if (DISTMAP(R + 1, C + 1) = 0)
      let ZEROTIES = ZEROTIES + 1

```

```

let ZEROTROW (ZEROTIES) = R + 1
let ZEROTCOL (ZEROTIES) = C + 1
let PREVDIST_ROW = R + 1
let PREVDIST_COL = C + 1
else
  if DISTPROB_REAL (R + 1, C + 1) > MAX
    let TIES = 1
    let TIESROW (TIES) = R + 1
    let TIESCOL (TIES) = C + 1
    let MAX = DISTPROB_REAL (R + 1, C + 1)
  else
    if (DISTPROB_REAL(R + 1, C + 1) = MAX)
      let TIES = TIES + 1
      let TIESROW (TIES) = R + 1
      let TIESCOL (TIES) = C + 1
    always
  always
always
//

if CAN_CHECK (R, C + 1) = 1
  if (DISTMAP(R, C + 1) = 0)
    let ZEROTIES = ZEROTIES + 1
    let ZEROTROW (ZEROTIES) = R
    let ZEROTCOL (ZEROTIES) = C + 1
    let PREVDIST_ROW = R
    let PREVDIST_COL = C + 1
  else
    if DISTPROB_REAL (R, C + 1) > MAX
      let TIES = 1
      let TIESROW (TIES) = R
      let TIESCOL (TIES) = C + 1
      let MAX = DISTPROB_REAL (R, C + 1)
    else
      if (DISTPROB_REAL(R, C + 1) = MAX)
        let TIES = TIES + 1
        let TIESROW (TIES) = R
        let TIESCOL (TIES) = C + 1
      always
    always
  always
always
//

if CAN_CHECK (R - 1, C + 1) = 1
  if (DISTMAP(R - 1, C + 1) = 0)
    let ZEROTIES = ZEROTIES + 1
    let ZEROTROW (ZEROTIES) = R - 1
    let ZEROTCOL (ZEROTIES) = C + 1
    let PREVDIST_ROW = R - 1
    let PREVDIST_COL = C + 1
  else
    if DISTPROB_REAL (R - 1, C + 1) > MAX
      let TIES = 1
      let TIESROW (TIES) = R - 1
      let TIESCOL (TIES) = C + 1
      let MAX = DISTPROB_REAL (R - 1, C + 1)
    else
      if (DISTPROB_REAL(R - 1, C + 1) = MAX)
        let TIES = TIES + 1
        let TIESROW (TIES) = R - 1

```

```

        let TIESCOL (TIES) = C + 1
    always
    always
    always
always
"

if CAN_CHECK (R + 1, C) = 1
    if (DISTMAP(R + 1, C) = 0)
        let ZEROTIES = ZEROTIES + 1
        let ZEROTROW (ZEROTIES) = R + 1
        let ZEROTCOL (ZEROTIES) = C
        let PREVDIST_ROW = R + 1
        let PREVDIST_COL = C
    else
        if DISTPROB_REAL (R + 1, C) > MAX
            let TIES = 1
            let TIESROW (TIES) = R + 1
            let TIESCOL (TIES) = C
            let MAX = DISTPROB_REAL (R + 1, C)
        else
            if (DISTPROB_REAL(R + 1, C) = MAX)
                let TIES = TIES + 1
                let TIESROW (TIES) = R + 1
                let TIESCOL (TIES) = C
            always
        always
    always
always
"

```

```

if CAN_CHECK (R - 1, C) = 1
    if (DISTMAP(R - 1, C) = 0)
        let ZEROTIES = ZEROTIES + 1
        let ZEROTROW (ZEROTIES) = R - 1
        let ZEROTCOL (ZEROTIES) = C
        let PREVDIST_ROW = R - 1
        let PREVDIST_COL = C
    else
        if DISTPROB_REAL (R - 1, C) > MAX
            let TIES = 1
            let TIESROW (TIES) = R - 1
            let TIESCOL (TIES) = C
            let MAX = DISTPROB_REAL (R - 1, C)
        else
            if (DISTPROB_REAL(R - 1, C) = MAX)
                let TIES = TIES + 1
                let TIESROW (TIES) = R - 1
                let TIESCOL (TIES) = C
            always
        always
    always
always
"

```

```

if CAN_CHECK (R + 1, C - 1) = 1
    if (DISTMAP(R + 1, C - 1) = 0)
        let ZEROTIES = ZEROTIES + 1
        let ZEROTROW (ZEROTIES) = R + 1
        let ZEROTCOL (ZEROTIES) = C - 1
        let PREVDIST_ROW = R + 1
        let PREVDIST_COL = C - 1
    else

```

```

if DISTPROB_REAL (R + 1, C - 1) > MAX
  let TIES = 1
  let TIESROW (TIES) = R + 1
  let TIESCOL (TIES) = C - 1
  let MAX = DISTPROB_REAL (R + 1, C - 1)
else
  if (DISTPROB_REAL(R + 1, C - 1) = MAX)
    let TIES = TIES + 1
    let TIESROW (TIES) = R + 1
    let TIESCOL (TIES) = C - 1
  always
always
always
always

```

```

if CAN_CHECK (R, C - 1) = 1
  if (DISTMAP(R, C - 1) = 0)
    let ZEROTIES = ZEROTIES + 1
    let ZEROTROW (ZEROTIES) = R
    let ZEROTCOL (ZEROTIES) = C - 1
    let PREVDIST_ROW = R
    let PREVDIST_COL = C - 1
  else
    if DISTPROB_REAL (R, C - 1) > MAX
      let TIES = 1
      let TIESROW (TIES) = R
      let TIESCOL (TIES) = C - 1
      let MAX = DISTPROB_REAL (R, C - 1)
    else
      if (DISTPROB_REAL(R, C - 1) = MAX)
        let TIES = TIES + 1
        let TIESROW (TIES) = R
        let TIESCOL (TIES) = C - 1
      always
    always
  always
always

```

```

if CAN_CHECK (R - 1, C - 1) = 1
  if (DISTMAP(R - 1, C - 1) = 0)
    let ZEROTIES = ZEROTIES + 1
    let ZEROTROW (ZEROTIES) = R - 1
    let ZEROTCOL (ZEROTIES) = C - 1
    let PREVDIST_ROW = R - 1
    let PREVDIST_COL = C - 1
  else
    if DISTPROB_REAL (R - 1, C - 1) > MAX
      let TIES = 1
      let TIESROW (TIES) = R - 1
      let TIESCOL (TIES) = C - 1
      let MAX = DISTPROB_REAL (R - 1, C - 1)
    else
      if (DISTPROB_REAL(R - 1, C - 1) = MAX)
        let TIES = TIES + 1
        let TIESROW (TIES) = R - 1
        let TIESCOL (TIES) = C - 1
      always
    always
  always
always

```



```

''
''
''      d. If at least one of the 8 neighbors has a disturbance
''      probability > 0.0
''
''          if MAX > 0.0
''
''              (1) If there is more than one neighboring pixel
''                  already disturbed or the disturbance has
''                  reached only 1 or 2 pixels, we're not on
''                  a "peninsula" or the disturbance has just
''                  started. Then find the maximum disturbance
''                  probability by randomly choosing among tied
''                  values. Disturb that pixel, move to it, and
''                  add one to the count of disturbance size.
''
''              if (ZEROTIES > 1) OR (CURRENT_DISTURB_SIZE < 3)
''                  let MAXR = RANDI.F (1, TIES, STM_SPREAD)
''                  let R = TIESROW (MAXR)
''                  let C = TIESCOL (MAXR)
''                  let DISTMAP(R, C) = 0
''                  let DISTPROB_REAL(R, C) = 0.0
''                  let CURRENT_DISTURB_SIZE = CURRENT_DISTURB_SIZE + 1
''
''              (2) If there is only one neighboring pixel already
''                  disturbed and if the disturbance has reached
''                  at least 3 pixels, then a "peninsula" could form.
''                  To stop this, move back to the already
''                  disturbed neighboring pixel and try to spread
''                  from there.
''
''              else
''                  let R = PREVDIST_ROW
''                  let C = PREVDIST_COL
''                  always
''
''          e. If all the neighboring pixels have a disturbance
''              probability of 0.0, this means that they have all
''              been disturbed already or have no probability
''              of being disturbed. Then choose randomly among
''              the 8 neighbors and move to that pixel.
''
''              else
''                  let MAXR = RANDI.F (1, ZEROTIES, STM_SPREAD)
''                  let R = ZEROTROW (MAXR)
''                  let C = ZEROTCOL (MAXR)
''                  always
''
''          loop
''
''      always
''
''
''      * * * * *
''      * Option number 2 *
''      * * * * *
''

```

```

if SPREAD_OPTION = 2
//
//
//
//      a. initialize variables
//
//      let CURRENT_DISTURB_SIZE = 1
//      let DISTPROB_REAL(R,C) = 0.0
//
//
//
//      b. check to see if disturbance has completed spreading
//
//
//      while (CURRENT_DISTURB_SIZE<trunc.f(DISTURB_SIZE))
//
//
//
//      c. total up the disturbance probabilities in the eight
//      neighbor cells. first checking to be sure the cell is
//      not off the map and has not already been disturbed.
//      Count up the number of 0.0 probabilities and keep
//      track of where previously disturbed cells are.
//
do
    let ZEROTIES = 0
    let PREVDIST_ROW = 0
    let PREVDIST_COL = 0
    let DISTPROB_TOT = 0.0
//
    if CAN_CHECK (R-1,C-1) = 1
        if (DISTMAP(R-1,C-1) = 1)
            let DISTPROB_TOT = DISTPROB_REAL(R-1,C-1) + DISTPROB_TOT
            let DISTPROB_CUM(R-1,C-1) = 0.0
            let DISTPROB_CUM(R-1,C-1) = DISTPROB_TOT
        else
            let DISTPROB_CUM(R-1,C-1) = 0.0
            let ZEROTIES = ZEROTIES + 1
            let ZEROTROW (ZEROTIES) = R - 1
            let ZEROTCOL (ZEROTIES) = C - 1
            let PREVDIST_ROW = R - 1
            let PREVDIST_COL = C - 1
        always
    always
//
    if CAN_CHECK (R-1,C) = 1
        if (DISTMAP(R-1,C) = 1)
            let DISTPROB_TOT = DISTPROB_REAL(R-1,C) + DISTPROB_TOT
            let DISTPROB_CUM(R-1,C) = 0.0
            let DISTPROB_CUM(R-1,C) = DISTPROB_TOT
        else
            let DISTPROB_CUM(R-1,C) = 0.0
            let ZEROTIES = ZEROTIES + 1
            let ZEROTROW (ZEROTIES) = R-1
            let ZEROTCOL (ZEROTIES) = C
            let PREVDIST_ROW = R-1
            let PREVDIST_COL = C
        always
    always
//
    if CAN_CHECK (R-1,C+1) = 1
        if (DISTMAP(R-1,C+1) = 1)
            let DISTPROB_TOT = DISTPROB_REAL(R-1,C+1) + DISTPROB_TOT
            let DISTPROB_CUM(R-1,C+1) = 0.0

```

```

        let DISTPROB_CUM(R-1,C+1) = DISTPROB_TOT
    else
        let DISTPROB_CUM(R-1,C+1) = 0.0
        let ZEROTIES = ZEROTIES + 1
        let ZEROTROW (ZEROTIES) = R-1
        let ZEROTCOL (ZEROTIES) = C+1
        let PREVDIST_ROW = R-1
        let PREVDIST_COL = C+1
    always
always
//

if CAN_CHECK (R,C-1) = 1
    if (DISTMAP(R,C-1) = 1)
        let DISTPROB_TOT = DISTPROB_REAL(R,C-1) + DISTPROB_TOT
        let DISTPROB_CUM(R,C-1) = 0.0
        let DISTPROB_CUM(R,C-1) = DISTPROB_TOT
    else
        let DISTPROB_CUM(R,C-1) = 0.0
        let ZEROTIES = ZEROTIES + 1
        let ZEROTROW (ZEROTIES) = R
        let ZEROTCOL (ZEROTIES) = C-1
        let PREVDIST_ROW = R
        let PREVDIST_COL = C-1
    always
always
//

if CAN_CHECK (R,C+1) = 1
    if (DISTMAP(R,C+1) = 1)
        let DISTPROB_TOT = DISTPROB_REAL(R,C+1) + DISTPROB_TOT
        let DISTPROB_CUM(R,C+1) = 0.0
        let DISTPROB_CUM(R,C+1) = DISTPROB_TOT
    else
        let DISTPROB_CUM(R,C+1) = 0.0
        let ZEROTIES = ZEROTIES + 1
        let ZEROTROW (ZEROTIES) = R
        let ZEROTCOL (ZEROTIES) = C+1
        let PREVDIST_ROW = R
        let PREVDIST_COL = C+1
    always
always
//

if CAN_CHECK (R+1,C-1) = 1
    if (DISTMAP(R+1,C-1) = 1)
        let DISTPROB_TOT = DISTPROB_REAL(R+1,C-1) + DISTPROB_TOT
        let DISTPROB_CUM(R+1,C-1) = 0.0
        let DISTPROB_CUM(R+1,C-1) = DISTPROB_TOT
    else
        let DISTPROB_CUM(R+1,C-1) = 0.0
        let ZEROTIES = ZEROTIES + 1
        let ZEROTROW (ZEROTIES) = R+1
        let ZEROTCOL (ZEROTIES) = C-1
        let PREVDIST_ROW = R+1
        let PREVDIST_COL = C-1
    always
always
//

if CAN_CHECK (R+1,C) = 1
    if (DISTMAP(R+1,C) = 1)
        let DISTPROB_TOT = DISTPROB_REAL(R+1,C) + DISTPROB_TOT
        let DISTPROB_CUM(R+1,C) = 0.0

```



```

        let C = C
    always
    always
    if CAN_CHECK (R-1,C+1) = 1
        if (RAND_SPR_VAL<=DISTPROB_CUM(R-1,C+1)) AND (OVER=0)
            let OVER = 1
            let R = R-1
            let C = C+1
        always
    always
    if CAN_CHECK (R,C-1) = 1
        if (RAND_SPR_VAL<=DISTPROB_CUM(R,C-1)) AND (OVER=0)
            let OVER = 1
            let R = R
            let C = C-1
        always
    always
    if CAN_CHECK (R,C+1) = 1
        if (RAND_SPR_VAL<=DISTPROB_CUM(R,C+1)) AND (OVER=0)
            let OVER = 1
            let R = R
            let C = C+1
        always
    always
    if CAN_CHECK (R+1,C-1) = 1
        if (RAND_SPR_VAL<=DISTPROB_CUM(R+1,C-1)) AND (OVER=0)
            let OVER = 1
            let R = R+1
            let C = C-1
        always
    always
    if CAN_CHECK (R+1,C) = 1
        if (RAND_SPR_VAL<=DISTPROB_CUM(R+1,C)) AND (OVER=0)
            let OVER = 1
            let R = R+1
            let C = C
        always
    always
    if CAN_CHECK (R+1,C+1) = 1
        if (RAND_SPR_VAL<=DISTPROB_CUM(R+1,C+1)) AND (OVER=0)
            let OVER = 1
            let R = R+1
            let C = C+1
        always
    always

```

```

let DISTMAP(R, C) = 0
let DISTPROB_REAL(R, C) = 0.0
let CURRENT_DISTURB_SIZE = CURRENT_DISTURB_SIZE + 1

```

```

(2) If there is only one neighboring pixel already
disturbed and if the disturbance has reached
at least 3 pixels, then a "peninsula" could form.
To stop this, move back to the already
disturbed neighboring pixel and try to spread
from there.

```

```

else
    let R = PREVDIST_ROW
    let C = PREVDIST_COL

```

```

        always
    //
    //
    //     e. If all the neighboring pixels have a disturbance
    //     probability of 0.0, this means that they have all
    //     been disturbed already or have no probability
    //     of being disturbed. Then choose randomly among
    //     the 8 neighbors and move to that pixel.
    //
    //
    //     else
    //         let MAXR = RANDI.F (1,ZEROTIES,STM_SPREAD)
    //         let R = ZEROTROW (MAXR)
    //         let C = ZEROTCOL (MAXR)
    //         always
    //
    //
    //     loop
    //     always
    //     return
end
//
//
//
routine SAMPINT
//
//
//     * * * * *
//     * THIS ROUTINE SELECTS AN INTERVAL TO WAIT, BEFORE *
//     * ANALYZING LANDSCAPE STRUCTURE, FROM A NORMAL *
//     * DISTRIBUTION *
//     * * * * *
//
//
//     let SAMP_INTERVAL = 0
//     if SAMP_STDEV = 0.0
//         let SAMP_INTERVAL = TRUNC.F(SAMP_MEAN)
//     else
//         let SAMP_INTERVAL = 0
//         while SAMP_INTERVAL < 1
//             do
//                 let SAMP_INTERVAL =
//                     TRUNC.F(NORMAL.F(SAMP_MEAN,SAMP_STDEV,STM_SAMP))
//             loop
//         always
//         return
end
//
//
//
function CAN_CHECK (rowval, colval)
//
//
//     * * * * *
//     * CAN_CHECK makes sure a disturbance doesn't spread *
//     * off the map. It returns a 0 if rowval or colval *
//     * are off the map. If not, it returns a 1 *
//     * * * * *
//
//
//     Define rowval and colval as integer variables
//
//
//     if (rowval > NROW) or (rowval < 1)
//         return with 0
//     else
//         if (colval > NCOL) or (colval < 1)
//             return with 0

```

```
        else
            return with 1
        //
    end
```

```
////////////////////////////////////
```

```

/*****
/*****
/* model_lib.c contains a set of C functions that act as independent */
/* library modules to be called by model.sim. model_lib.c has no */
/* "main" function, therefore, and will only produce an object module, */
/* not an executable program. Note that all of the functions that */
/* contain GRASS library calls begin with a call to G_gisinit - this is */
/* essential in all independent functions that access GRASS library */
/* functions (the program crashes without it). */
/*****
/*****/

/* C include files */
#include "stdio.h"
#include "stdlib.h"
#include "math.h"

/* GRASS include files */
#include "gis.h"
#include "dig_defines.h"
#include "dig_structs.h"

/* function declarations */
void annual_updt();
void initlayer();
void initdistmap();
void make_distprob();
void putnum();
void reclass_map();
void save_grass_layer();
void screenputnum();
void show_map();
void sstruct();
void update_map();
void write_ascii();
void write_distprob_ascii();

/*****
/* annual_updt uses the GRASS r.mapcalc program to update the AGE layer at the */
/* end of a year. All cells in the age layer are increased by 1. */
/* Variables: none */
/* Called by: model.sim (SimScript) */
/* Calls: G_gisinit, system */
/* Note: The age layer name is assumed to be a constant ("AGE_SCA"). */
/*****/
void annual_updt()

{
    char cmd[120];

    static char prog_name[] = "annual_updt";

    G_gisinit(prog_name);

    system("r.mapcalc tmp = 'tmp + 1'");
    sprintf(cmd, "/bin/rm %s/%s/.tmp/sun/*", G_location_path(), G_mapset());
    system(cmd);
}

```



```

/*****/
/* initlayer copies the starting layer into tmp, before */
/* the model is started, using the GRASS g.copy command */
/* Return value: none */
/* Called by: model.sim (SimScript) */
/* Calls: G_gisinit, system */
/*****/
void initlayer (init_map)
    char init_map[20];

{
    static char prog_name[] = "initlayer";

    char cmd[120];

    G_gisinit(prog_name);

    sprintf(cmd,"g.copy rast=%s,tmp",init_map);
    system(cmd);

}

/*****/
/* initdistmap initializes RC.DISTMAP before the model is started */
/* Return value: none */
/* Called by: model.sim (SimScript) */
/* Calls: G_gisinit, system */
/*****/
void initdistmap()

{
    static char prog_name[] = "initdistmap";

    G_gisinit(prog_name);

    system("r.mapcalc RC.DISTMAP = '(tmp * 0) + 1'");

}

/*****/
/* make_distprob takes the formula for combining the type, age, elevation, */
/* slope, and aspect layers from the parameters file and concatenates it with */
/* the GRASS r.mapcalc command to create a new GRASS layer named "distprob". */
/* Variables: formula */
/* Return value: none */
/* Called by: model.sim (SimScript) */
/* Calls: write_distprob_ascii, G_gisinit, system */
/* Notes: none */
/*****/
void make_distprob(formula)
    char formula[132];

{
    static char prog_name[] = "make_distprob";

    FILE *input_file;
    char cmd[132];
    static char outputlayer[] = "DISTPROB";

```

```

G_gisinit(prog_name);

sprintf(cmd, "r.mapcalc %s = %s", outputlayer, formula);
system(cmd);

write_distprob_ascii();

}

/*****
/* putnum creates an ascii disturbance map by writing current cell values to
/* a file, one cell at a time.
/* Variables:
/* x - cell value
/* size - row or column dimension of RC.DISTMAP
/* current - current value of j (column number)
/* row - current value of i (row number)
/* Called by: model.sim (SimScript)
/* Calls: none
*****/
void putnum (x, size, current, row)
    int x, size, current;

{
    FILE *fname;

    if ((current == 1) && (row == 1))
        fname = fopen ("/home/grass/model/tempmap/distmap.ascii", "w");
    else
        fname = fopen ("/home/grass/model/tempmap/distmap.ascii", "a");
    fprintf (fname, "%1d%c", x, ' ');
    if (size == current)
        fprintf (fname, "\n");
    fclose (fname);
}

/*****
/* reclass_map uses the GRASS r.reclass command to reclass the AGE layer*/
/* after it has been updated subsequent to a disturbance. The AGE
/* layer is reclassified according to rules stored in the file
/* /home/grass/model/params/params.reclass
/* Variables: none
/* Return value: none
/* Called by: model.sim (SimScript)
/* Calls: G_gisinit, system
*****/
void reclass_map ()

{
    static char prog_name[] = "reclass_map";

    G_gisinit(prog_name);

    system("r.reclass input=tmp output=map.recl < /home/grass/model/params/params.reclass");
}

/*****
/* save_grass_layer copies the current age layer to a new GRASS layer with

```

```

/* a unique name stored in variable 'run_yr'. */
/* Variables: run_yr - current run and year in the simulation run */
/* Called by: model.sim (SimScript) */
/* Calls: G_gisinit, system */
/* Notes: */
/*****/
void save_grass_layer (run_yr)
    char run_yr[20];

{
    static char prog_name[] = "save_grass_layer";
    char cmd[120];

    G_gisinit(prog_name);

    sprintf(cmd, "g.copy rast=tmp,%s", run_yr);
    system(cmd);

}

/*****/
/* screenputnum writes ascii disturbance map values to the screen, one cell at */
/* a time. */
/* Variables: */
/* x - cell value */
/* size - */
/* current - */
/* row - row number */
/* Called by: model.sim (SimScript) */
/* Calls: none */
/*****/
void screenputnum (x, size, current, row)
    int x, size, current;

{
    printf ("%1d%c", x, ' ');
    if (size == current)
        printf ("\n");

}

/*****/
/* show_map uses the GRASS "d." commands to display the latest */
/* disturbance map, then the updated and reclassified AGE layer together */
/* with a text display of the current run and year. */
/* Variables: run_yr - current run and year of simulation run */
/* Return value: none */
/* Called by: model.sim (SimScript) */
/* Calls: system, G_gisinit */
/*****/
void show_map(run_yr)
    char run_yr[20];

{
    static char prog_name[] = "show_map";

    FILE *textfile;
    static char ctrl_d = 4;

    G_gisinit(prog_name);

```

```

/* create the text file to be read by d.text */

if ( (textfile = fopen ("/home/grass/model/params/params.display", "w")) == 0)
{
    printf("\nError encountered trying to open params/params.display file for writing.\n");
    exit(-1);
}

/* see GRASS d.text and d.title documentation for
notes on text file format */

fprintf(textfile, ".C yellow\n");
fprintf(textfile, ".S 40\n");
fprintf(textfile, ".B 1\n");
fprintf(textfile, "        Simulation year: %s\n", run_yr);
fprintf(textfile, "%c", ctrl_d); /* signals end of text file for d.text */
fclose (textfile);

/* display the disturbance map, then the updated
age map and text */

system("d.colormode mode=fixed");
system("d.frame -e");
system("d.frame -c frame=map1 at=15,100,15,100");
system("d.frame -c frame=msg at=0,10,0,100");
system("d.frame -c frame=map2 at=85,100,85,100");
system("d.frame -s frame=map1");
system("cat /home/grass/model/params/rules.file | r.colors map=map.recl color=rules");
system("d.rast map=map.recl");
system("d.frame -s frame=map2");
system("cat /home/grass/model/params/rules.file | r.colors map=RC.DISTMAP color=rules");
system("d.rast map=RC.DISTMAP");
system("d.frame -s frame=msg");
system("d.text < /home/grass/model/params/params.display");
system("d.frame -c frame=leg at=15,100,0,13");
system("d.frame -s frame=leg");
system("d.legend map=map.recl");

}

/*****
/* sstruct uses the GRASS landscape measures (r.le.dist, r.le.patch, and
/* r.le.tex to measure the structure of the landscape
/* Variables: run_yr - current run and year of the simulation run
/* Called by: model.sim (SimScript)
/* Calls: r.le.dist, r.le.patch, r.le.tex, G_system
*****/
void sstruct(run_yr,rledist,rlepatch,rletex)
char run_yr[20];
char rledist[120], rlepatch[120], rletex[120];

{
    static char prog_name[] = "sstruct";
    char cmd[120];

    G_gisinit(prog_name);

/* run the selected landscape measure programs */

```

```

if (atoi(rledist)){
    G_system(rledist);
}

if (atoi(rlepatch)){
    G_system(rlepatch);
}

if (atoi(rletex)){
    G_system(rletex);
}

/* change the extension of the output files from
   .out to the contents of run_yr */

sprintf(cmd,"r.le.rename -a ext=%s",run_yr);
system(cmd);

}

/*****
/* update_map uses the GRASS r.mapcalc program to update the AGE layer based
/* on the current disturbance map. Cells that have experienced a disturbance
/* are given a value of 0 in the AGE layer, while the other cells remain
/* unchanged. This is done in r.mapcalc by multiplying the AGE layer by the
/* disturbance layer (note that the disturbance layer is a binary map of 1s
/* and 0s, where 0s indicate locations in the cell matrix where disturbances
/* have occurred.)
/* Variables: none
/* Called by: model.sim (SimScript)
/* Calls: G_gisinit, system
/* Note that the disturbance layer is first read in from an ascii file
/* ("/home/grass/model/tempmap/distmap_whdr.ascii") and converted
/* to a GRASS raster file ("RC.DISTMAP") using the GRASS command r.in.ascii.
*****/
void update_map()

{
    static char prog_name[] = "update_map";

    G_gisinit(prog_name);

    system("r.in.ascii input=/home/grass/model/tempmap/distmap_whdr.ascii output=RC.DISTMAP");
    system("r.mapcalc RC.DISTMAP = 'RC.DISTMAP + 1'");
    system("r.neighbors input=RC.DISTMAP output=RC.DISTMAP method=minimum size=5");
    system("r.mapcalc RC.DISTMAP = 'RC.DISTMAP - 1'");
    system("r.mapcalc tmp = 'RC.DISTMAP * tmp'");

}

/*****
/* write_ascii writes an ascii cell file in a form that can be used by the
/* GRASS command "r.in.ascii", which converts an ascii cell file into a
/* GRASS raster file. write_ascii first obtains information about the
/* current GRASS window using the G_get_set_window library function. The
/* window dimensions are then written as a header to the ascii cell file.
/* Finally, cell data are written to the ascii cell file one row at a time.
/* (The raw cell data are read from an ascii file that contains no header.)
*****/

```

```

/*****
void write_ascii ()

{

static char prog_name[] = "write_ascii";

int i, j, k, data[2500];
FILE *ascii_file, *input_file;
char *mapset;
struct Cell_head current_window;

G_gisinit(prog_name);

/* get current GRASS window information */

G_get_set_window(&current_window);

/* open data input file for reading */

if ( (input_file = fopen ("/home/grass/model/tempmap/distmap.ascii", "r")) == 0)
{
printf("\nFunction write_ascii: error trying to open distmap.ascii for reading.\n");
exit(-1);
}

/* open ascii output file for writing */

if ( (ascii_file = fopen ("/home/grass/model/tempmap/distmap_whdr.ascii", "w")) == 0)
{
printf("\nFunction write_ascii: error trying to open distmap_whdr.ascii file for writing.\n");
exit(-1);
}

/* write header information to ascii file */

fprintf(ascii_file, "north:\t%f\n", current_window.north);
fprintf(ascii_file, "south:\t%f\n", current_window.south);
fprintf(ascii_file, "east:\t%f\n", current_window.east);
fprintf(ascii_file, "west:\t%f\n", current_window.west);
fprintf(ascii_file, "rows:\t%d\n", current_window.rows);
fprintf(ascii_file, "cols:\t%d\n", current_window.cols);
fprintf(ascii_file, "\n");

/* write input data to ascii output file one
row at a time */

for(i = 0; i < current_window.rows; i++)
{
fprintf(ascii_file, "\n");
for(j = 0; j < current_window.cols; j++)
fscanf(input_file, "%d", &data[j]);
for(k = 0; k < current_window.cols; k++)
fprintf(ascii_file, "%ld ", (long)data[k]);
}

/* close files */

fclose(ascii_file);
fclose(input_file);

```

```

}

/*****
/* write_distprob_ascii takes the GRASS layer created in make_distprob and */
/* writes it out as an ascii file (with no header information) named */
/* "/home/grass/model/tempmap/distprob.ascii". This file is then read in by */
/* the model. */
/* Variables: none */
/* Return value: none */
/* Called by: make_distprob */
/* Calls: G_get_set_window, G_allocate_cell_buf, G_get_map_row_nomask */
*****/
void write_distprob_ascii()

{
    int i, j, fd, row;
    char *mapset;
    static char filename[] = "DISTPROB";
    CELL *cell;
    FILE *ascii_file;
    struct Cell_head now_window;

                                /* get current window information */

    G_get_set_window(&now_window);

                                /* locate and open distprob GRASS layer for
                                reading */

    if( (mapset = G_find_cell(filename,"")) == NULL)
    {
        printf("Unable to find file %s.\n",filename);
        exit(1);
    }

    if( (fd = G_open_cell_old(filename, mapset)) < 0)
        exit(-1); /* p.82 */

                                /* open ascii output file for writing */

    if ( (ascii_file = fopen ("/home/grass/model/tempmap/distprob.ascii", "w")) == 0)
    {
        printf("\nError encountered trying to open tempmap/distprob.ascii file for writing.\n");
        exit(-1);
    }

                                /* allocate memory for reading a row of the
                                DISTPROB map */

    cell = G_allocate_cell_buf();

                                /* get DISTPROB rows one at a time and then
                                print contents to ascii file */

    for(i = 0; i < now_window.rows; i++)
    {
        G_get_map_row_nomask(fd,cell,i);
    }
}

```

```
for(j = 0; j < now_window.cols; j++)  
    fprintf(ascii_file, "%1ld%c", (long)cell[j], ' ');  
fprintf (ascii_file, "\n");  
}
```

```
/* close up the files when done */
```

```
G_close_cell(fd);  
fclose(ascii_file);
```

```
}
```


APPENDIX D. DOCUMENTATION FOR THE R.LE PROGRAMS

The r.le Programs

**A set of GRASS programs
for the quantitative analysis of landscape structure**

**Version 2.0
January 1, 1993**

**William L. Baker, Principal Investigator
Yunming Cai, Research Assistant
Saleh Musleh, Research Assistant
Jerry Bucher, Research Assistant**

**Department of Geography and Recreation
University of Wyoming
Laramie, Wyoming 82071**

**This set of programs was developed in its entirety with funds from U.S.
Department of Energy Grants DE-FG02-89ER60883 and DE-FG02-90ER60977.
This support does not constitute an endorsement by DOE of the views expressed in
this document.**

TABLE OF CONTENTS

1. INTRODUCTION	3
1.1. Purpose of the r.le programs	3
1.2. Relationship of the r.le programs and GRASS	3
1.3. Overview of the r.le programs	3
2. THE r.le PROGRAMS	5
2.1. Operation	5
2.2. Data input	5
2.2.1. A caution about "0" data	11
2.2.2. A caution about islands and r.le.patch	11
2.2.3. The GRASS mask	12
2.3. The r.le.setup program	12
2.3.1. Sampling	12
2.3.2. Group/class limits	18
2.3.3. Color table	20
2.4. Syntax for the r.le analysis programs	21
2.5. The r.le.dist program	21
2.6. The r.le.patch program	25
Attribute measures	26
Size measures	27
Shape measures	28
Fractal dimension	30
Perimeter measures	30
2.7. The r.le.tex program	31
Diversity measures	32
Texture measures	33
Juxtaposition measures	34
Edge measures	37
2.8. Output from the r.le analysis programs	37
2.8.1. Moving window output maps	37
2.8.2. Output files and data formats from non-moving window analyses	38
r.le.dist	38
r.le.patch	41
r.le.tex	42
2.8.3. Data analysis with external statistical and graphics software	42
2.9. The r.le.null program	43
2.10. The r.le.rename program	43
2.11. The r.le.show program	44
2.12. The r.le.trace program	45
3. GLOSSARY	47
4. BIBLIOGRAPHY	49
5. APPENDICES	52
1. Limits	53
2. Time needed to complete analyses with the r.le programs	54
3. Help menus for the r.le programs	55

1. INTRODUCTION

1.1. Purpose of the r.le programs

Since the 1970s, with the availability of satellite data, there has been an increasing interest in the structure of the earth on the scale of kilometers or hundreds of kilometers. Landscape ecology is a multi-disciplinary pursuit, involving geographers, biologists, sociologists, remote sensors, and many others. The focus of landscape ecology is on the dynamics and structure of the biosphere, including human activities, on the scale of kilometers (Risser et al. 1984; Forman and Godron 1986; Urban et al. 1987). The science of landscape ecology expanded rapidly in the 1980s, and methods for the quantitative analysis of landscape structure also were developed (e.g. Mead et al. 1981; Gardner et al. 1987; Krummel et al. 1987; Milne 1988; Griffiths and Wooding 1988), yet there is no generally available software for the quantitative analysis of landscape structure that will work within a geographical information system (GIS).

The r.le programs have been designed to provide software for calculating a variety of common quantitative measures of landscape structure. The programs were specifically designed for analyzing the structure of landscapes output from a simulation model, but can be used to analyze the structure of nearly any landscape.

1.2. Relationship of the r.le programs and GRASS

The r.le programs are intended to be part of the Geographical Resources Analysis Support System (GRASS), a public-domain geographical information system (GIS), designed and developed through the Environmental Division of the U.S. Army Construction Engineering Research Laboratory in Champaign, Illinois (USA-CERL 1991) (Fig. 1). GRASS is primarily a raster-based GIS, but now has extensive vector handling capabilities. GRASS requires the UNIX operating system, but can be used on a variety of workstations, as well as 80386-class personal computers. The programs use GRASS version 4.0 and its XDRIVER.

The r.le programs directly use the GRASS database, GRASS libraries, and the GRASS data structure (Fig. 1) in the calculation of measures of landscape structure, and use GRASS for the entry of digitized data. GRASS also provides a number of separate image processing, data manipulation, and mapping programs which can be useful for preparing data for analysis with the r.le programs and for displaying output.

1.3. Overview of the r.le programs

The r.le programs are designed for analyzing landscapes composed of a mosaic of patches, but, more generally, these programs are capable of analyzing any two-dimensional raster or array whose entries are integer values. The r.le programs have options for controlling the shape, size, number, and distribution of

Figure 1

GRASS and r.le Programs

sampling areas used to collect information about the landscape. Sampling area shapes can be square, or rectangular with any length/width ratio. The size of sampling areas can be changed, so that the landscape can be analyzed at a variety of spatial scales. Sampling areas may be distributed across the landscape in a random, systematic, or stratified-random manner, or as a moving window.

The r.le programs can calculate a number of measures that produce single values as output (e.g. mean patch size in the sampling area), as well as measures that produce a distribution of values as output (e.g. frequency distribution of patch sizes in the sampling area) (Table 1). The programs include no options for graphing or statistically analyzing the results of the analyses. External software must be used.

The programs were developed on a SUN SPARCstation 1 workstation running the Sun OS 4.1.2 operating system and the Open Windows 3.0 windowing programs (Fig. 1). The code was written in the C programming language and makes use of functions provided in the GRASS programmers' library (Shapiro et al. 1989).

2. THE r.le PROGRAMS

2.1. Operation

To run the r.le programs, the user must first start GRASS (type "grass4.0") and set up the working environment in GRASS by specifying the GRASS location and map layers to be used. The sequence of operations usually is to first use r.le.setup to set up the sampling framework (e.g., regions, sampling unit size and shape, etc.) and then use the other r.le programs (e.g. r.le.tex, r.le.patch, r.le.dist) to make the desired measurements (Fig. 2). All of the r.le programs operate from the GRASS command prompt (>). The commands and their parameters are entered after the GRASS command prompt, and the programs then go through a sequence of operations to complete the setup and measurements (Fig. 3). Output from r.le.setup goes in the subdirectory "r.le.para" while output from the other r.le programs goes in the subdirectory "r.le.out". These subdirectories are created automatically when the programs are invoked, and are made subdirectories within the directory from which the programs are invoked.

2.2. Data input

The r.le programs work directly with map layers that have been input and preprocessed in GRASS. Data from Landsat Multi-Spectral Scanner (MSS) or Thematic Mapper (TM) can be downloaded into GRASS using the image processing programs in GRASS. GRASS also has programs for reading files produced by ERDAS and ARC/INFO, and for reading ASCII raster files. Vector information can be input using the GRASS digitizing programs. Vector information must be converted to raster data using the GRASS program "v.to.rast" prior to using the r.le

Figure 2

Figure 3

STRUCTURE OF r.le ANALYSIS PROGRAMS

r.le.dist - distance analysis
r.le.patch - patch analysis
r.le.tex - texture analysis

TABLE 1. Measures that can be calculated by the r.le programs. gp = attribute group, CC = center-to-center distance, CE = center-to-edge distance, EE = edge-to-edge distance.

r.le.dist

MEASURES:

- Mean distance
- Standard deviation distance
- Mean distance by gp
- Standard deviation distance by gp
- Number of distances by distance class
- Number of distances by distance class by gp

METHODS:

- Each patch to all adjacent neighbors CC
- Each patch to all adjacent neighbors CE
- Each patch to nearest patch of same gp CC
- Each patch to nearest patch of same gp CE
- Each patch to nearest patch of same gp EE
- Each patch to nearest patch of different gp CC
- Each patch to nearest patch of different gp CE
- Patches of 1 gp to nearest of specific gp CC
- Patches of 1 gp to nearest of specific gp CE
- Patches of 1 gp to nearest of specific gp EE

r.le.patch

ATTRIBUTE:

- Mean pixel attribute
- Standard deviation pixel attribute
- Mean patch attribute
- Standard deviation patch attribute
- Cover by gp
- Density by gp

SIZE:

- Mean patch size
- Standard deviation size
- Mean patch size by gp
- Standard deviation size by gp
- Number by size class
- Number by size class by gp

Table 1. Continued.

SHAPE:

Indices: Corrected perimeter/area
 Perimeter/area
 Related circumscribing circle

Measures:

Mean patch shape
 Standard deviation shape
 Mean patch shape by gp
 Standard deviation shape by gp
 Number by shape class
 Number by shape class by gp

FRACTAL DIMENSION

Perimeter-area fractal dimension

PERIMETER

Sum of perimeters
 Sum of perimeters by gp
 Mean perimeter length
 Mean perimeter length by gp
 Standard deviation perimeter length
 Standard deviation perimeter length by gp

r.le.tex

DIVERSITY

Richness
 Shannon
 Dominance
 Inverse Simpson's

TEXTURE**Measures**

Contagion (C)
 Angular second moment (ASM)
 Inverse difference moment (IDM)
 Entropy (ENT)
 Contrast (CON)

Methods

2-neighbor: horizontal (2N-H)
 2-neighbor: 45 degrees (2N-45)
 2-neighbor: vertical (2N-V)
 2-neighbor: 135 degrees (2N-135)

Table 1. Continued.

4-neighbor: horizontal/vertical (4N-HV)
4-neighbor: diagonal (4N-DIAG)
8-neighbor: (8N)

JUXTAPOSITION

Mean juxtaposition

Standard deviation juxtaposition

EDGE

Sum of edges

programs. Preprocessing capabilities of GRASS include programs to rectify imagery so that it matches a planimetric map and programs for classifying raw multi-band data.

The `r.le` programs were conceived for analyzing maps of patches. Any raster map can be considered to contain patchiness and can be analyzed using the programs, but a variety of landscape data can be more specifically considered "patch" data. Patches may be disturbance patches, remnant patches, environmental resource patches, introduced patches, or simply patchy entities on a map (Forman and Godron 1986). Patches may simply be landscape elements (Forman and Godron 1986), such as roads, dwellings, forest patches, grassland patches, hedgerows, or fields. Patches could also be types of forest in a forested landscape (e.g. deciduous forest, recently-burned forest, conifer forest), or types of grassland in a prairie landscape. Patches of different age occur in landscapes subject to disturbances (e.g. fires, floods), where the age of the patch represents the time since it was last disturbed. Patches could also be the types identified by completing a classification of spectral data in a Landsat image, or in a scanned aerial photograph. In general, patches are simply the result of grouping pieces of the landscape into units whose members share a common set of attributes.

2.2.1. A caution about "0" data

GRASS specifies that the integer "0" does not have the traditional meaning of zero. Instead "0" in GRASS means "no data." For this reason the `r.le` programs do not include "0" values in calculations. Raster pixels that contain "0" are excluded from all calculations and are skipped when the moving window is centered over them. If you have a patch that has the attribute "0" that you want to have included in the `r.le` calculations, you must recode it (use `r.reclass`) to some other attribute value (e.g., -999) prior to using the `r.le` programs. We hope that in future GRASS releases there will be a provision for the integer zero, which does on occasion have real meaning (e.g., age = 0 for newly created patches).

2.2.2. A caution about islands and `r.le.patch`

An island is a pixel or set of pixels with attribute *x* contained wholly within a surrounding patch whose attribute is not *x*. The `r.le.tex` program does not use patches, and the `r.le.dist` program does not need to distinguish islands, but the `r.le.patch` program must trace patches and recognize islands. This is because the size and perimeter of patches will be incorrect unless the islands they contain are identified, and size and perimeter are corrected to account for these islands.

Identifying that a patch is an island and then finding the surrounding patch is very difficult in raster format and is also very time consuming. The user is cautioned that if the map to be analyzed contains many islands then `r.le.patch` may be very slow.

Moreover, the tracing algorithm currently will only identify one level of

nesting of islands. If an island is inside another patch, it will be identified, but if an island is inside another island that is inside a patch, it will not be identified.

2.2.3. The GRASS mask

GRASS has a mask command (`r.mask`) that can be used to limit the parts of a map that are included in an analysis. The `r.le` analysis programs do respond to a mask if it is present, and the results of analyses will be limited to the area specified as "1" in the MASK file. Moreover, when the moving window sampling method is used, the moving window will only move through the area of the map that is specified as "1" in the MASK file. This can considerably speed up the moving window operation, if the masked area is a small part of the map.

2.3. The `r.le.setup` program

The `r.le.setup` program is used to set up the sampling and analysis framework that will be used by the other `r.le` programs. To run `r.le.setup` do the following:

1. After starting `grass4.0` and setting up your location and mapset, start a GRASS monitor window using the `d.mon` command.
2. Move the cursor back to the command window with the GRASS command prompt (`>`).
3. Type `r.le.setup` followed by a carriage return. This program runs only interactively.
4. You will now be queried for (1) the name of the map to be used as a backdrop for setting up the sampling scheme, (2) the name of a vector map to overlay on the raster map to aid in placing the sampling areas (optional), and (3) the name of a sitefile to overlay on the raster map to aid in placing the sampling areas (optional). These maps must already exist to be used here.
5. The raster map and overlay maps, if chosen, will be displayed and you will see the main `r.le.setup` menu.

The first menu allows the user to select how sampling will be done (regions, sampling units, moving window), setup the limits for groups and classes, and change the color table.

2.3.1. Sampling

Information about the structure of the landscape is obtained by overlaying a set of sampling areas on top of a map layer, and then calculating specific structural measures for the part of the map layer that corresponds to the area in each

sampling area.

A sampling area may be one of four things (Fig. 4). First, it is possible to treat the entire map layer as the one (and only) sampling area. Second, if the map layer can be divided into meaningful geographical regions, then it is possible to treat the regions themselves as sampling areas. The third option is that the sampling areas may be sampling units of fixed shape and size (also called scale) that are placed within the map layer as a whole. The fourth and final option is that the sampling area may be moved systematically across the map as a moving window. The following sections present additional details about these options for sampling areas.

2.3.1.1. Whole map layer

If the whole map layer is to be used as the one and only sampling area (Fig. 4), then `r.le.setup` does not need to be run. The user may complete an analysis by simply entering the appropriate `r.le` command with the `"sam=W"` parameter.

2.3.1.2. Regions

If regions are to be used as the sampling areas (Fig. 4), then select "REGIONS" from the first `r.le.setup` menu, and the user is asked to do the following:

1. "ENTER THE NEW REGION MAP NAME:". Only a new raster map name is acceptable. The user can type LIST to find out the existing raster map names in this location and mapset.
2. "PLEASE OUTLINE REGION # 1". The user should move the mouse cursor into the graphic monitor window and use the mouse buttons as instructed:
 Left button: where am I.
 to display the current coordinates of the cursor.
 Middle button: Mark a point.
 to enter a vertex of the region boundary.
 Right button: Mark LAST point.
 to close the region boundary by setting the last vertex to be equal to the first one.
3. A "REGION OPTIONS:" menu is displayed and the user should use the mouse to select one of the options:
 "DRAW MORE": repeat the above process and setup one more region.
 "START OVER": abandon the previous setup and start all over again.
 "DONE-SAVE": save the regions outlined so far and exit this procedure.

"QUIT-NO SAVE": quit the procedure without saving the regions.

Once the "DONE-SAVE" option is selected, the new raster map of the sampling regions is generated. It is displayed on the monitor window for several seconds, the monitor window is refreshed, the main menu is displayed again, and the program is ready for other setup work.

The user can also use the GRASS `r.digit` or `v.digit` programs to digitize circular or polygonal regions and to create a sampling regions map without using `r.le.setup`.

2.3.1.3. Sampling units

If sampling units are to be used as the sampling areas (Fig. 4), then choose "SAMPLING UNITS" from the first `r.le.setup` menu. The program checks the `r.le.para` subdirectory for an existing "units" file from a previous setup session and allows the user to rename this file (to save it) before proceeding. The `r.le.setup` program will otherwise overwrite the "units" file. Then the following choice is displayed followed by a series of other choices:

Define sampling units manually or graphically?

The next menu allows the user to choose to define the sampling units manually or graphically. When sampling units are defined manually, the user inputs the shape and size (scale) of the sampling units by specifying dimensions in pixels using the keyboard. When sampling units are defined graphically, the user uses the mouse to define the sampling units in the GRASS monitor window, and then actually places the sampling units for each scale onto the map. By placing the units graphically the user can directly determine the method of sampling unit distribution as well as the shape, size, and number of sampling units.

If the choice is made to define sampling units manually, the user next is prompted to use the mouse to outline the actual part (or whole) of the map that will be sampled, and the following series of questions must be answered:

How many different scales do you want?

Next the user is asked to specify the number of scales that will be used. The `r.le` programs allow the user to simultaneously sample the same map with the same measures at several scales. Currently there can be between 1 and 15 scales that can be sampled simultaneously. Substantial output can be produced if many scales are used.

Methods of sampling unit distribution

Sampling units must be placed spatially into the landscape. There are five options for doing this (Fig. 4):

1. **Random nonoverlapping:** Sampling units are placed in the landscape by randomly choosing numbers that specify the location of the upper left corner of each sampling unit, subject to the constraint that successive sampling units not overlap other sampling units or the edge of the landscape.
2. **Systematic contiguous:** Sampling units are placed side by side across the rows. If the placement of sampling units produces an imperfect fit (leftover area), then the left over area is shifted to the upper left corner of the sampling area, and a randomly selected starting point is chosen within the leftover area.
3. **Systematic noncontiguous:** The user must specify the amount of spacing (in pixels) between sampling units. Horizontal and vertical spacing are identical. Leftover area is allocated as it was with systematic contiguous sampling. Sampling units are again placed side by side (but spaced) across the rows. If the placement of sampling units produces an imperfect fit (leftover area), then the leftover area is shifted to the upper left corner of the sampling area, and a randomly selected starting point is chosen within the leftover area.
4. **Stratified random:** The user must specify the vertical and horizontal locations of strata, which partition the sampling area. The strata are rectangular areas within which single sampling units are randomly located.
5. **Centered over sites:** The user must specify the name of a sitefile containing point locations. A single sampling unit is placed with its center over each site in the site file. This is a useful approach for determining the landscape structure around points, such as around the location of wildlife observations.

The ratio (cols/rows-as a real number) for sampling unit of scale n ?

The user is next prompted to enter a ratio that defines the shape of the sampling units. Sampling units may have any rectangular shape, including square as a special case of rectangular. Rectangular shapes are specified by entering the ratio of columns/rows (horizontal dimension/vertical dimension) as a real number.

Figure 4

SAMPLING AREAS

WHOLE MAP LAYER

REGIONS

SAMPLING UNITS

Random
Nonoverlapping

Systematic
Contiguous

Systematic
Noncontiguous

Stratified
Random

Centered
Over Sites

MOVING WINDOW

Maximum size is m . What size for each sampling unit of scale n ?

The user is then given the maximum possible size for a sampling unit (in pixels) and asked to input the size of sampling units at each scale. Sampling units can be of any size, but the maximum size is the size of the landscape as a whole. All the sampling units, that make up a single sampling scale, are the same size.

Maximum units in scale n is p . How many sampling units do you want?

The maximum number of units that can be placed over the map, given the shape and size of the units, is then given. The user can then choose the number of sampling units to be used in the map layer. It may not always be possible to choose the maximum number, depending upon the shape of the sampling units.

2.3.1.4. Moving window:

Using this procedure a rectangular "window" or single sampling area is moved systematically across the map to produce a new map. This sampling procedure can only be used with the measures that produce a single value or with a single class or group when measures produce distributions of values (Table 1). The first class or group specified when defining class or group limits (section 2.3.2.) is used if distributional measures are chosen with the moving window sampling method. In this case, the user should manually edit the *r.le.para/recl_tb* file so that the desired group is listed as the first group in this file.

Sampling begins with the upper left corner of the window placed over the upper left corner of the total area to be sampled. It is strongly recommended that the user read the section on the GRASS mask (section 2.2.2) prior to setting up the moving window, as this mask can be used to speed up the moving window operation. The value of the chosen measure is calculated for the window area. This value is assigned to the location on the new map layer corresponding to the center pixel in the window if the window has odd (e.g. 3 X 3) dimensions. The value is assigned to the location on the new map layer corresponding to the first pixel below and to the right of the center if the window has even dimensions (e.g. 6 X 10). If this pixel has the value "0," which means "no data" in GRASS, then this pixel is skipped and a value of "0" is assigned to the corresponding location in the new map. The window is then moved to the right (across the row) by one pixel, and the process is repeated. At the end of the row, the window is moved down one pixel, and then back across the row. This option produces a new map layer, whose dimensions are smaller by approximately $(m-1)/2$ rows and columns, where m is the number of rows or columns in the window.

If the "MOVE-WINDOW" option in the main menu is selected, first the program checks for an existing "move_wind" file, in the *r.le.para* subdirectory, containing moving window specifications from a previous session. The user is given the option to avoid overwriting this file by entering a new file name for the

old "move_wind" file. The user is then prompted to do the following:

1. "Use the mouse to define the moving window?"

If yes, then the functions of the three mouse buttons are displayed: check size, move cursor, and define the moving window. The moving window is defined in the same way as a sampling unit. Once defined, it will be displayed wherever it is defined.

If no, then the prompt "Enter COLUMNS & ROWS of the window:" is displayed. Type in the number of rows and columns of the moving window using the GRASS cell array coordinate system. Then the moving window will be displayed in the top-left corner of the current window of the monitor screen.

2. "Will the moving window search the whole map?"

If yes, the module saves the input and returns to the main menu.

If no, the button instruction is displayed and the user should use the mouse cursor to outline the area that the moving window will search through. This is done in the same way as above. After the area is defined and displayed wherever it is defined the user is asked "Is the search area ok?" If not, the process is repeated. Otherwise the area is displayed, with the moving window in a different color, at the top-left corner of the area. The picture is displayed for a few seconds and then it is refreshed. Then the main menu is redisplayed for next selection.

2.3.2. Group/class limits

Group/class limits are setup by choosing "GROUP LIMITS" from the main menu upon starting r.le.setup. The program checks for existing group/class limit files in subdirectory r.le.para and allows the user to rename these files prior to continuing. The files are named recl_tb (attribute group limits), size (size class limits), shape_PA (shape index class limits for perimeter/area index), shape_CPA (shape index class limits for corrected perimeter/area index), and shape_RCC (shape index class limits for related circumscribing circle index). If the files are not renamed the program will overwrite them.

The r.le programs allow the attribute categories in the input map to be reclassified into several attribute groups, and reports the analysis results by each of these attribute groups. The same reclassing can be done with the measurement indices (e.g., size), except that each "cohort" (class) of the reclassified indices is called an index class instead of a group.

Attribute groups and index classes are defined in a different way. In the r.le programs attribute groups are defined as in the following example:

1, 3, 5, 7, 9 thru 21 = 1 (*comment*)

```
31 thru 50 = 2 (comment)
end
```

In this example, the existing categories 1, 3, 5, 7, {9, 10, ... 20, 21} are included in the new group 1, while {31, 32, 33, ..., 49, 50} are included in the new group 2. The characters in bold are the "key words" that are required in the definition. Each line is called one "reclass rule".

In the special case of the attribute groups for distance measurement using method 4, in which the "from" attribute group and "to" attribute group must be specified, the "from" and "to" groups are defined in a slightly different way, as in the following example:

```
1, 3, 5, 7, 9 thru 21 end (comment)
```

Here, the key word "end" is at the end of the line instead of in a new line. This rule is only used in the definition of the "from" and "to" attribute groups, because in this case both groups have one and only one reclass rule.

The GRASS reclass convention is adopted here with a little modification (see "r.reclass" command in the GRASS manual by Shapiro et al. 1989). The difference is that r.le only allows one rule for each group while the GRASS r.reclass command allows more than one. The definition of "from" and "to" groups is simply the extension of the GRASS reclass rule. The advantage of using the GRASS reclass convention is that the user can generate a permanent reclassified map, using GRASS programs, directly from the r.le setup results.

The r.le measurement index classes are defined by the lower limits of the classes, as in the following example:

```
0.0, 10.0, 50.0, 200.0, -999
```

This means:

```
if v >= 0.0 and v < 10.0 then v belongs to index class 1;
if v >= 10.0 and v < 50.0 then v belongs to index class 2;
if v >= 50.0 and v < 200.0 then v belongs to index class 3;
if v >= 200.0 then v belongs to index class 4;
```

where v is the calculated index value and -999 marks the end of the index class definition. The measurement index can be the size index, one of the three shape indices, or one of the three distance indices.

The program is currently designed to allow no more than 25 attribute groups, 25 size classes, 25 shape index classes, and 25 distance index classes.

As an alternative, the user may want to permanently group certain attributes prior to entering the r.le programs. For example, the user may want to group attributes 1-10, in a map whose attributes are ages, into a single attribute representing young patches. The user can do this using the GRASS r.reclass and r.resample commands, which will create a new map layer that can then be analyzed

directly (without setting up group limits) with the r.le programs.

2.3.3. Color table

The user may want to change the color table for the map in the GRASS monitor window to make the sampling areas, cursor, and rubber band more visible. There are several different color tables that can be tried until a suitable one is found. Note that if you choose one of the other color tables from the menu, the color table for that GRASS raster map gets changed. To change it back to what it was originally, select "SET-OLD" from the color table menu.

If the "Color Table" option in the main menu is selected, a menu titled "SELECT NEW COLOR TYPE" is displayed that has the following options:

- "ASPECT": generate a color table for aspect data.
- "GREY SCALE": generate a grey scale color table. Each color is a level of grey, increasing from black to white.
- "RAMPS": generate a color table with 3 sections: red only, green only, and blue only, each increasing from none to full intensity. This table is good for continuous data such as ages.
- "RAINBOW": generate a color table based on rainbow colors. the table generated here uses yellow, blue, indigo, violet, red. This table is good for continuous data such as ages.
- "RANDOM": generate random colors. Good as a first pass at a color table for nominal data. This option generates different color combinations for the color table each time. Therefore it can be used repeatedly until the satisfactory colors are displayed.
- "RED-YEL-GRN": generate a color table similar to that of "RAINBOW", except that the table starts at red, passes through yellow, and ends with green.
- "WAVE": generate a color table with 3 sections: red only, green only, and blue only, each increasing from none to full intensity and back down to none. This table is good for continuous data like ages.
- "SET OLD": assign the original color table to the input cell map if none of the above options improves the display during setup.

After one of these options is selected, the menu titled "WHAT'S NEXT" is displayed that has the following options:

- "START OVER": go back to the previous menu and reset the original color table.
- "MAIN MENU": exit from the color change module and go back to the main menu. The color table will be reset to that of the input file when the user leaves the r.le.setup program.
- "SAVE COLOR TAB.": exit from this module and permanently save the

currently displayed color table.

"QUIT SETUP": quit the `r.le.setup` program and don't save any changes.

The user can restore a user-developed color table (stored in "rules.file") by typing at the GRASS prompt "`cat rules.file | r.colors map=name color=rules`".

2.4. Syntax for the `r.le` analysis programs

The `r.le` analysis programs include `r.le.dist`, `r.le.patch`, and `r.le.tex`. These programs are designed to do landscape ecological analyses by computing the spatial measures selected from the measure list available with each program. Each program will be explained in the following sections. All three `r.le` analysis programs can be started at the GRASS prompt (`>`) using either a command-line or interactive method.

The interactive version of each program is invoked by simply typing the command followed by a carriage return. The GRASS parsing routine will then ask the user to answer questions and specify parameter values. The possible parameter values are listed along with a brief summary of their meanings.

The command-line version of each program is invoked by typing the name of the program, followed by a list of parameters and parameter values, on the command line, followed by a carriage return. Each command-line parameter is described briefly in help menus for each of the programs. To invoke the command-line help menu, type the name of the program, a space, and the word "help" (e.g. `r.le.tex help`).

2.5. The `r.le.dist` program

The `r.le.dist` program can be used to measure distances between patches and report those distances using several methods. See section 2.4. for an explanation of how to start the `r.le.dist` program. The syntax for the command-line version and the parameters for both interactive and command-line versions are as follows:

```
r.le.dist map=name sam=name run=name [reg=name] ski=value can=value
          di1=name[,name,...] di2=value[,...] [out=name]
```

where:

brackets `[]` indicate optional parameters or values

map is the GRASS raster map to be analyzed. This raster map must be available in the user's working GRASS database (`/location/mapset/`),
sam is the kind of sampling area: W, U, M, or R, where W = whole map, U = sampling units, M = moving window, or R = regions,
run is: F or B, where F = run in foreground, B = run in background,

reg is the name of the regions map to be used when *sam* = R, *ski* is to specify whether to skip some points when searching along the patch boundary. This is used to speed up the distance calculations.

ski ≤ 0 means don't skip;

ski > 0 means:

if *np* > *ski* + 50 - search every other boundary point;

if *np* > *ski* + 200 - search every third boundary point;

if *np* > *ski* + 500 - search every fourth boundary point;

if *np* > *ski* + 2000 - search every fifth boundary point;

where *np* is the number of total boundary pixels of a patch. This is effective with the center-edge and edge-edge distance measures. The default value is *ski* = 1, and maximum value is 10.

can is the maximum number of candidate patches on the nearest-neighbor-list for searching the nearest neighbor patch. It means when searching the nearest patch of a particular patch, find *can* "close" patches first using simple method, then find out the nearest patch from these *can* candidate patches with point-by-point calculation. The legal range of *can* is 1-30. If *can* < 1, *can* = 1; if *can* > 30, *can* = 30. The default value is *can* = 5.

di1 is the distance measure, which can have these values:

11 = Mean distance: This is simply the total of all the distances divided by the number of distances measured.

12 = Standard deviation of distance: This is the standard deviation of the distances in the sampling area. It is calculated as:

$$s = \sqrt{\frac{\sum_{i=1}^N (x_i - \bar{x})^2}{N}}$$

where x_i is distance i , $\bar{x}$ is the mean distance of all the distances, and N is the number of distances.

13 = Mean distance by group: This is the mean distance within the sampling area, as in M, but calculated separately for the patches within each group.

I4 = Standard deviation distance by group: This is the standard deviation of distances with the sampling area, as in S, but calculated separately for the patches within each group.

I5 = Number of distances by distance class: This is a tally of the number of distances within each of up to 25 user-specified distance classes.

I6 = Number of distances by distance class by group: This is a tally of the number of distances within each of up to 25 user-specified distance classes, as in C, but calculated separately for the patches within each group.

In the case of the moving window sampling method, only one of these values may be chosen, but with the whole map, regions, or sampling unit sampling methods, the following combinations of the above are the only options:

I1-2

I3

I4

I5

I6

di2 is the distance method. Distance can be measured and summarized in a variety of ways: (1) from each patch in the sampling area or only from patches belonging to a specific attribute group (gp), (2) to all adjacent neighboring patches or only to the single nearest neighbor patch, (3) regardless of the group of the neighbor or only to patches belonging to a specific group, (4) from center to center, from center to edge, or from edge to edge. There are nine combinations of these that represent the choices for *di2* (some examples are illustrated in Fig. 5):

From each patch in the sampling area
to all the adjacent neighbors of the patch

M0 = Distance is center-center

M1 = Distance is center-edge

to the nearest patch of the same gp

M2 = Distance is center-center

M3 = Distance is center-edge

M4 = Distance is edge-edge

to the nearest patch of a different gp

M5 = Distance is center-center

M6 = Distance is center-edge

From each patch of a specific gp

to the nearest patch of a specific gp

M7 = Distance is center-center

M8 = Distance is center-edge

M9 = Distance is edge-edge

Figure 5

A polygon is considered to be adjacent to another polygon if it shares either an edge or a single vertex with the polygon. Polygon center x and y coordinates are defined as the sum of the x and y coordinates of all the boundary points divided by the number of points. A center of gravity algorithm for finding polygon centers will be implemented in the next version. Distance from center to edge is measured from the center of one polygon to the closest point on the boundary of the other polygon. Distance from edge to edge is measured as the minimum distance between any points on the boundary of the two polygons. Note that with methods 0-1 a very large number of distances are calculated, whereas with methods 2-6 the number of distances measured is the same as the number of patches in the sampling area. With methods 7-9 the number of distances is the same as the number of patches in the sampling area that belong to the "from" group. Note that the distance between polygons A and B may be used more than once with any of the measures, as this distance may be calculated once with polygon A as the "from" polygon and once with polygon B as the "from" polygon. The distance between polygons A and B is the same no matter which is the "from" polygon if center-center distance is calculated, but it is not the same if center-edge distance is calculated.

out is the name of the output map to be used when *sam* = M

2.6. The r.le.patch program

This program can be used to calculate attribute, size, shape, fractal dimension, and perimeter measures for sets of patches in a landscape. See section 2.4. for an explanation of how to start the *r.le.patch* program. The syntax for the command-line version and the parameters for both interactive and command-line versions are as follows:

```
r.le.patch map = name sam = name run = name [reg = name]
           [att = name[,name,...]] [siz = name[,name,...]] [sh1 = name]
           [sh2 = name[,name,...]] [fra = name] [per = name[,name,...]]
           [out = name]
```

where:

brackets [] indicate optional parameters or values
map is the GRASS raster map to be analyzed. This raster map must be available in the user's working GRASS database (/location/mapset/),
sam is the kind of sampling area: W, U, M, or R, where W = whole map, U = sampling units, M = moving window, or R = regions,

run is: F or B, where F = run in foreground, B = run in background,
reg is the name of the regions map to be used when *sam* = R,
att is a set of attribute measures:

- A1 = Mean pixel attribute: This is the average value of the attributes of all the pixels in the sampling area. Each attribute is weighted by how many pixels it occupies. The mean pixel attribute, $\bar{x}$, is then:

$$\bar{x} = \frac{\sum_{i=1}^m (w_i * i)}{\text{size}}$$

where w_i is the number of pixels of attribute i , i is the attribute of these pixels, m is the number of attributes in the sampling area, and *size* is the size of the sampling area (in pixels). This measure is only meaningful when attributes represent interval/ratio data.

- A2 = Standard deviation of pixel attribute: This is simply the standard deviation of the attributes of the pixels in the sampling area. The standard deviation of pixel attributes, s , is then:

$$s = \sqrt{\left(\frac{\sum_{i=1}^N (x_i - \bar{x})^2}{N} \right)}$$

where x_i is the attribute of patch i , $\bar{x}$ is the mean attribute of all the patches, and N is the number of patches.

- A3 = Mean patch attribute: This is the average attribute of all the patches in the sampling area. It is calculated by summing up the attributes of each patch and dividing by the number of patches.
- A4 = Standard deviation of patch attributes: This is simply the standard deviation of the attributes of the patches in the sampling area. The standard deviation of patch attributes, s , is then:

$$s = \sqrt{\left(\frac{\sum_{i=1}^N (x_i - \bar{x})^2}{N} \right)}$$

where x_i is the attribute of patch i , $\bar{x}$ is the mean attribute of all the patches, and N is the number of patches.

A5 = Cover by group: This is a measure of the amount of land area covered by each group. Cover is expressed as the fraction of the sampling area occupied by each group.

A6 = Density by group: This is a measure of the number of patches in each group. It is expressed as first the fraction of the total number of patches that are in each group, and second as the raw number of patches that are in each group.

In the case of the moving window sampling method, only one of these values may be chosen, but with the whole map, region, and sampling unit sampling methods, the following combinations of the above are the only options:

A1-4

A5

A6

siz is a set of size measures:

S1 = Mean patch size: This measure, the mean size or area (in pixels) of the patches in the sampling area, is calculated for all patches in the sampling area, ignoring the group of each patch, by simply dividing the sampling area size by the number of patches.

S2 = Standard deviation of patch size: This is the standard deviation of the sizes (in pixels) of all the patches in the sampling area, ignoring the group of each patch. The standard deviation of patch size, s , is then:

$$s = \sqrt{\left(\frac{\sum_{i=1}^N (x_i - \bar{x})^2}{N} \right)}$$

where x_i is the size of patch i , $\bar{x}$ is the mean size of all the patches, and N is the number of patches.

- S3 = Mean patch size by group: This is the mean patch size within the sampling area, as in S1, but calculated separately for all the patches within each group.
- S4 = Standard deviation of patch size by group: This is the standard deviation of the sizes (in pixels) of all the patches in the sampling area, as in S4, but calculated separately for all the patches within each group.
- S5 = Number by size class: This is a measure of the number of patches in the sampling area that fall within each size class. This measure is calculated for all the patches in the sampling area, ignoring the group of each patch. The results can be reported for up to 25 size classes.
- S6 = Number by size class by group: This is a measure of the number of patches in the sampling area that fall within each size class. This measure is calculated separately for all the patches within each group. The results can be reported for up to 25 size classes.

In the case of the moving window sampling method, only one of these values may be chosen, but with the whole map, regions, and sampling unit sampling methods, the following combinations of the above are the only options:

S1-2
S3
S4
S5
S6

sh1 is a set of shape indices. There are three possible indices of patch shape here. These are only three of the simplest indices of two-dimensional shape (Austin 1984; MacEachren 1985):

- M1 = Perimeter/area: The total length of the perimeter of each patch is divided by its area, and the mean of these values is then calculated. Where patches extend outside of the sampling area, the sampling area edge is considered to be the edge of the patch. A problem with the ratio of perimeter/area as a shape index is that it varies with the size of the patch.
- M2 = Corrected perimeter/area: The formula for this index for each patch is: $(0.282 \times \text{perimeter})/(\text{area})^{1/2}$. The mean of these values for all the patches is then calculated. This index corrects for the size problem of index E. The index varies from a value of 0.0 for a circle to infinity for an infinitely long and narrow shape. It is 1.12 for a square.
- M3 = Related circumscribing circle: This index compares the area of the patch to the area of the smallest circle that

shape index classes.

In the case of the moving window sampling method, only one of these values may be chosen, but with other sampling methods, the following combinations of the above are the only options:

H1-2
H3
H4
H5
H6

fra is the fractal dimension, D , for the patches in a sampling area, and is a measure of the complexity of the perimeter. The current version implements only the perimeter-area interpretation of fractal dimension (Krummel et al. 1987). The formula for fractal dimension, d , is:

$$d=2*s$$

where s is the slope of the regression of the log of the patch perimeter versus the log of the patch area.

$F1$ = perimeter-area fractal dimension

per is the perimeter of a patch, which is the total length of external and internal boundary expressed as the number of pixel edges. The perimeter includes the edge of the sampling area when the edge of the sampling area intersects a patch. The perimeter is measured for each patch individually. Thus boundaries between adjoining patches get measured twice, once for each patch. The edge measures of *r.le.tex* do not measure shared boundaries twice. There are several possible measures of perimeter:

$P1$ = Sum of the perimeters: This is the total of all the perimeters for all the patches in the sampling area, ignoring the group to which the patch belongs.

$P2$ = Mean perimeter: This is the mean perimeter length for the patches in the sampling area, ignoring the group to which the patches belong. It is calculated by dividing the sum of the perimeters by the number of patches.

$P3$ = Standard deviation of perimeter: This is the standard deviation of perimeter length for all the patches in the sampling area, ignoring the group to which they belong.

can circumscribe the patch. The formula for each patch is:

$$RCC = \frac{2 * (area/\Pi)^{1/2}}{longest-axis}$$

This index varies from 0.0 to 1.0 as the compactness of the shape approaches that of a circle. A square has the value 0.79789.

sh2 is a set of shape measures:

- H1 = Mean patch shape: This measure is calculated for all patches in the sampling area, ignoring the group of each patch. The mean patch shape is simply the sum of the patch shape indices for every patch divided by the number of patches.
- H2 = Standard deviation of patch shape: This is the standard deviation of the shapes of all the patches in the sampling area, ignoring the group of each patch. The standard deviation of patch shape, *s*, is then:

$$s = \sqrt{\frac{\sum_{i=1}^N (x_i - \bar{x})^2}{N}}$$

where x_i is the shape of patch *i*, $\bar{x}$ is the mean shape of all the patches, and *N* is the number of patches.

- H3 = Mean patch shape by group: This is the mean patch shape within the sampling area, as in 1, but calculated separately for all the patches within each group.
- H4 = Standard deviation of patch shape by group: This is the standard deviation of the shapes of all the patches in the sampling area, as in 4, but calculated separately for all the patches within each group.
- H5 = Number by shape index class: This is the number of patches, in the sampling area, whose shape index value falls within each shape index class. This measure is calculated for all the patches in the sampling area, ignoring the group of each patch. The results can be reported for up to 25 shape index classes.
- H6 = Number by shape index class by group: This is the number of patches, in the sampling area, whose shape index value falls within each shape index class. This measure is calculated separately for all the patches in each group. The results can be reported for up to 25

The standard deviation of perimeter length, s , is then:

$$s = \sqrt{\left(\frac{\sum_{i=1}^N (x_i - \bar{x})^2}{N} \right)}$$

where x_i is the perimeter length of patch i , $\bar{x}$ is the mean perimeter length of all the patches, and N is the number of patches.

P4 = Sum of the perimeters by group: This is the total of all the perimeters for all the patches in the sampling area, as in P1, calculated separately for the patches belonging to each group.

P5 = Mean perimeter by group: This is the mean perimeter length for the patches in the sampling area, calculated separately for the patches belonging to each group. It is calculated by dividing the sum of the perimeters by the number of patches within each group.

P6 = Standard deviation of perimeter by group: This is the standard deviation of perimeter length for all the patches in the sampling area, as in P3, but calculated separately for the patches belonging to each group.

In the case of the moving window sampling method, only one of these values may be chosen, but with the whole map, regions, and sampling unit sampling methods, the following combinations of the above are the only options:

P1-3

P4

P5

P6

out is the name of the output map to be used when *sam* = M

2.7. The r.le.tex program

The *r.le.tex* program contains a set of measures of diversity, texture, juxtaposition, and edge. See section 2.4. for an explanation of how to start the *r.le.tex* program. The syntax for the command-line version and the parameters for both interactive and command-line versions are as follows:

```
r.le.tex map=name sam=name run=name [reg=name] [div=name]
[te1=name] [te2=name] [jux=name] [edg=name]
[out=name]
```


where:

brackets [] indicate optional parameters or values

map is the GRASS raster map to be analyzed. This raster map must be available in the user's working GRASS database (/location/mapset/),

sam is the kind of sampling area: W, U, M, or R, where W = whole map, U = sampling units, M = moving window, or R = regions,

run is: F or B, where F = run in foreground, B = run in background,

reg is the name of the regions map to be used when *sam* = R,

div is a set of measures of the diversity of patch attributes within the sampling area. The relative merits of the following measures have been evaluated by Peet (1974):

D1 = Richness: This is simply the number of different patch attributes present in the sampling area.

D2 = Shannon index (H'): This is an index that combines richness and evenness. Its formula is:

$$H' = -\sum_{i=1}^m p_i \ln(p_i)$$

where p_i is the fraction of the sampling area occupied by attribute i , and m is the number of attributes in the sampling area.

D3 = Dominance: This index is related to the Shannon index, but emphasizes the deviation from evenness. The formula for dominance, D , is:

$$D = \ln(n) - H'$$

where n is the number of attributes in the sampling area. This index was first proposed and used by O'Neill et al. (1988).

D4 = Inverse Simpson's index ($1/S$): This index also combines richness and evenness. It is a measure of the probability of encountering two pixels of the same attribute when taking a random sample of two pixels. Its formula is:

$$1/S = 1 / \sum_{i=1}^m p_i^2$$

where p_i is the fraction of the sampling area occupied by attribute i , and m is the total number of attributes

within the sampling area.

In the case of the moving window sampling method, only one of these values may be chosen, but with the whole map, regions, and sampling unit sampling methods, the following combination of the above is the only option:

D1-4

te1 is a set of texture measures that quantify the adjacency of similar attributes. They are in a sense simply local (neighborhood) measures of diversity. Most of the measures have been reviewed by Haralick et al. (1973), Haralick (1975), and Musick and Glover (1990). All of the measures require calculation of a grey-level co-occurrence matrix (GLCM), which is $m \times m$, where m is the number of attributes in the sampling area. The GLCM matrix contains entries, P_{ij} , which are the total number of times that attribute i is adjacent to attribute j . The total number of adjacencies is calculated by moving through the sampling area pixel-by-pixel. There are five measures of texture that can be calculated:

M1 = Contagion: This measure quantifies the degree of clumping, and is a modification of the entropy measure (N). The formula for contagion, C , is:

$$C = 2 * \ln(m) - ENT$$

The formula for this measure was printed incorrectly in O'Neill et al. (1988) as $2m * \ln(m) - ENT$.

M2 = Angular second moment: This is a measure of the homogeneity of the landscape. Larger values indicate more homogeneity. The formula for angular second moment, ASM , is:

$$ASM = \sum_{i=1}^m \sum_{j=1}^m (P_{ij})^2$$

M3 = Inverse difference moment: The formula for inverse

difference moment, *IDM*, is:

$$IDM = \sum_{i=1}^m \sum_{j=1}^m \frac{1}{1+(i-j)^2} P_{ij}$$

M4 = Entropy: Entropy is a maximum when all pixels of attribute *i* are as far apart from one another as possible. The formula for entropy, *ENT*, is:

$$ENT = - \sum_{i=1}^m \sum_{j=1}^m P_{ij} * \ln(P_{ij})$$

M5 = Contrast: This is a measure of the contrast or amount of local variation present in the landscape. The formula for contrast, *CON*, is:

$$CON = \sum_{i=1}^m \sum_{j=1}^m [(i-j)^2 * P_{ij}]$$

In the case of the moving window sampling method, only one of these values may be chosen, but with the whole map, region, and sampling unit sampling methods, the following is the only option, and it must be chosen, along with *te2*, to get texture measurements:

M1-5

te2 is a set of seven methods for analyzing the adjacencies for each pixel (Fig. 6):

T1 = 2N-H

T2 = 2N-45

T3 = 2N-V

T4 = 2N-135

T5 = 4N-HV

T6 = 4N-DIAG

T7 = 8N

jux is a set of two juxtaposition measures. Juxtaposition was described and used by Mead et al. (1981) and Henein and Cross (1983). Juxtaposition is a measure of the weighted length of edges surrounding a center pixel.

figure 6

TEXTURE METHODS

The juxtaposition for a center cell surrounded by eight neighbors is given by:

$$J = \frac{\sum_{n=1}^8 q_n * w_{ij}}{\sum_{n=1}^8 q_n}$$

where q_n is 2.0 if cell n horizontally or vertically shares an edge and is 1.0 if cell n diagonally shares an edge, and w_{ij} is a number between -1.0 and +1.0 which indicates the relative "quality" or weight to be given to edges between attributes m_i and m_j .

In calculating juxtaposition, diagonal neighbors get a quantity ranking, q , of 1.0, while horizontal and vertical neighbors get a quantity ranking of 2.0 because horizontal and vertical edges share more edge than do diagonal edges in a raster representation of patches.

Weights, w_{ij} , are assigned by the user to edges between different attributes. A weighting matrix, which is $m \times m$, where m is the number of different attributes, must be created with an editor and stored as an ASCII file named "weight" in the r.le.para subdirectory. The weighting matrix has the format:

	att_1	att_2	...	att_m
att_1	w_{11}	w_{12}	...	w_{1m}
att_2	w_{21}	w_{22}	...	w_{2m}
...	...	...	...	...
att_m	w_{m1}	w_{m2}	...	w_{mm}

where att_i is attribute i , expressed as an integer, of m attributes, and w_{ij} is the weight, expressed as a real number between -1.0 and +1.0, assigned when attribute i and attribute j share an edge. The two juxtaposition measures, then, are:

J1 = Mean juxtaposition: The program first calculates the juxtaposition for each pixel in the map layer by examining edges with attributes in the 8 cells surrounding each pixel. Then the program finds the

mean juxtaposition of all the cells in the sampling area, by summing all the juxtaposition values and dividing by the number of pixels.

J2 = Standard deviation of juxtaposition: This is the standard deviation for all the pixels in the sampling area. The standard deviation, s , is given by:

$$s = \sqrt{\left(\frac{\sum_{i=1}^N (x_i - \bar{x})^2}{N} \right)}$$

where x_i is the juxtaposition for cell i , $\bar{x}$ is the mean juxtaposition of all the cells, and N is the number of cells.

In the case of the moving window sampling method, only one of these values may be chosen, but with the whole map, region, and sampling unit sampling methods, the following combination of the above is the only option:

J1-2

edg is the length of patch boundary, but in summing edge for all the patches in a sampling area edges are counted only once when they are shared between two patches. An "edge" is considered to occur only between adjoining cells along a row or within a column. Diagonal neighbors with different attributes are not considered edge.

E1 = Sum of the edges: This is the total length of all the edges, counted only once, of all the patches in the sampling area. It differs from the total perimeter length which sums the length of each patch's total perimeter, effectively counting shared perimeters twice.

out is the name of the output map to be used when *sam* = M

2.8. Output from the r.le analysis programs

2.8.1. Moving window output maps and their interpretation

All three of the r.le analysis programs produce a new raster map when the moving window method of sampling is used. The name of the output map is specified with the "out" parameter. These maps are stored in the conventional GRASS database under the location and mapset in use at the time of the analysis.

GRASS allows raster maps to contain only integers, and this presents problems for analyses that produce real numbers as output (e.g., r.le.tex's Shannon

diversity measure). For this reason, the results of analyses for most measures are multiplied by 1, 10, 100, or 1000 to produce multiplied integer representations of the actual real numbers that should be output. Table 2 contains a list of each of the measures and the multiplier used. At the present time, these multipliers are embedded in the source code. In the future, they will be stored in a file, that can be edited, in the `r.le.para` subdirectory.

All moving window output maps are assigned a green-yellow-red color table, which can be changed by the user with the GRASS `r.colors` command.

2.8.2. Output files and data formats from non-moving window analyses

Several output files are produced by the `r.le` programs. Output files are stored in the `r.le.out` subdirectory. The output files and their format are as follows (gp = attribute group):

From `r.le.dist`:

I1-2.OUT

Scale Sampl. area# Mean distance Standard deviation distance

I3.OUT

Scale Sampl. area# Mean distance by gp

I4.OUT

Scale Sampl. area# Standard deviation distance by gp

I5.OUT

Scale Sampl. area# Number of distances in ea. distance class

I6.OUT

Scale Sampl. area#

No. in ea. index class-gp 1

No. in ea. index class-gp 2

... ...

No. in ea. index class-gp n

TABLE 2. Measures whose output value is a multiple of the real value, in maps output using the moving window sampling method. This multiplication is necessary because GRASS does not allow raster maps to have real numbers as attributes. Small real numbers would thus get rounded to the nearest integer (e.g., 3.24 = 3), destroying the precision in the number.

	Multiplier
r.le.dist	
Mean distance	10
Standard deviation distance	100
Mean distance by gpl	10
Standard deviation distance by gpl	100
Number of distances by distance class1	1
Number of distances by distance class by gpl	1
r.le.patch	
att	
Mean pixel attribute	10
Standard deviation pixel attribute	10
Mean patch attribute	10
Standard deviation patch attribute	10
Cover by gpl	1000
Density by gpl	1
siz	
Mean patch size	10
Standard deviation size	10
Mean patch size by gpl	10
Standard deviation size by gpl	10
Number by size class1	1
Number by size class by gpl	1
sh2	
Mean patch shape	1000
Standard deviation shape	1000
Mean patch shape by gpl	1000
Standard deviation shape by gpl	1000
Number by shape class1	1
Number by shape class by gpl	1
fra	
Perimeter-area fractal dimension	100
per	
Sum of perimeters	1
Mean perimeter	10
Standard deviation perimeter	10
Sum of perimeters by gpl	1
Mean perimeter by gpl	10
Standard deviation perimeter by gpl	10
r.le.tex	
div	
Richness	1
Shannon	100
Dominance	100
Inverse Simpson's	100
tel	
Contagion (C)	100
Angular second moment (ASM)	1000
Inverse difference moment (IDM)	1000
Entropy (ENT)	100
Contrast (CON)	10

TABLE 2. Continued.

<i>jux</i>	Mean juxtaposition	1000
	Standard deviation juxtaposition	1000
<i>edg</i>	Sum of edges	1

From r.le.patch:

A1-4.OUT
 Scale Sampl. area# Mn. pixel attrib. St. dev. pixel attrib.
 Mn. patch attrib. St. dev. patch attrib.

A5.OUT
 Scale Sampl. area# Cover by gp as a fraction

A6.OUT
 Scale Sampl. area# Density by gp as a raw number

S1-2.OUT
 Scale Sampl. area# Mn. size St. dev. size

S3.OUT
 Scale Sampl. area# Mean size-by gp

S4.OUT
 Scale Sampl. area# St. dev. size by gp

S5.OUT
 Scale Sampl. area# No. by size class

S6.OUT
 Scale Sampl. area#
 No. by size class-gp 1
 No. by size class-gp 2
 ...
 No. by size class-gp n

H1-2.OUT
 Scale Sampl. area# Mean shape St. dev. shape

H3.OUT
 Scale Sampl. area# Mean shape-by gp

H4.OUT
 Scale Sampl. area# Standard deviation shape-by gp

H5.OUT
 Scale Sampl. area# No. by shape index class

H6.OUT

Scale Sampl. area#
 No. in ea. index class-gp 1
 No. in ea. index class-gp 2

 No. in ea. index class-gp n

F1.OUT

Scale Sampl. area# Fractal dimension R2 SigB

P1-3.OUT

Scale Sampl. area# Sum of perim. Mean perim.
 Standard deviation perim.

P4.OUT

Scale Sampl. area# Sum of perim.-by gp

P5.OUT

Scale Sampl. area# Mean perim.-by gp

P6.OUT

Scale Sampl. area# Standard deviation perim.-by gp

From r.le.tex

D1-4.OUT

Scale Sampl. area# Richness Shannon Domin. Inv. Simpson's

T1-5.OUT

Scale Sampl. area# Contagion ASM IDM ENT Contrast

J1-2.OUT

Scale Sampl. area# Mean jux. St. dev. jux.

E1.OUT

Scale Sampl. area# Sum of edges

2.8.3. Data analysis with external statistical and graphics software

There are a number of more specialized measures of landscape structure which are not included in this program. Spatial autocorrelation analysis (Griffith 1987; Odland 1988), spatial spectral analysis (Ford and Renshaw 1984; Renshaw and Ford 1984), and geostatistics (Woodcock 1988; Mulla 1988; Oliver et al.

1989a, b) are all methods of spatial analysis that may provide useful quantitative information about landscape structure, but that also require specialized programming. Software for spatial autocorrelation analysis (Anselin 1989; Griffith 1989), spatial spectral analysis (Renshaw and Ford 1984), and geostatistical analysis (Robertson 1987) must be used separately from the *r.le* programs.

The data that are output by the *r.le* programs can be compared and analyzed graphically. There is currently no graphical display program built into the *r.le* programs, although maps and results from moving window analyses can be displayed using GRASS programs. The *r.le* program output data must be examined graphically using external software.

2.9 The *r.le.null* program

The *r.le.null* program is designed to generate a neutral structure map layer based on the theory of Gardner et al. (1987). This map layer can be used as a "null hypothesis" layer for testing the statistical significance of landscape measures. The syntax for the command-line version and the parameters for both interactive and command-line versions are as follows:

```
r.le.null map=name num=value att=value[,value,...]
           pro=value[,value,...]
```

where:

brackets [] indicate optional parameters or values
map is the GRASS raster map, with neutral structure, to be created,
num is the number of attributes (max = 24) to be generated within the neutral structure map,
att is attribute *i* of *num* attributes, where *i* is an integer,
pro is the probability for attribute *i* of *num* attributes. This probability is a decimal fraction usually ≤ 1.0 , which indicates what fraction of the neutral structure map will contain pixels with attribute *i*. The total probability of all the attributes can be less than or greater than 1.0. If less than 1.0, the rest of the map is filled with zeroes. If greater than 1.0, then the attributes after 1.0% is reached are ignored.

2.10 The *r.le.rename* program

The *r.le.rename* program is used to either add a suffix to all the files in the *r.le.out* subdirectory, or to rename the files one by one. It is necessary to rename the files before running an *r.le* program over again, because the *r.le* program will overwrite existing files each time the program is started. The syntax for the command-line version and the parameters for both interactive and command-line

versions are as follows:

```
r.le.rename [-a] [ext = name] [old = name[,name,...]
              [new = name[,name,...]
```

where:

brackets [] indicate optional parameters or values
 -a is a flag indicating that all files in the *r.le.out* subdirectory that have extension ".out" will have their extension changed to that specified by parameter *ext*. The other files in *r.le.out* will not be affected.
ext specifies the new extension with which to replace the .out extension of files in the *r.le.out* subdirectory,
old is an old name for file *i*, in the *r.le.out* subdirectory, to be changed,
new is the new name for file *i*, in the *r.le.out* subdirectory

2.11 The *r.le.show* program

The *r.le.show* program is designed to allow the user to visually check the sampling units or moving window that was setup using *r.le.setup*. The syntax for the command-line version and the parameters for both interactive and command-line versions are as follows:

```
r.le.show map = name sam = name
```

where:

brackets [] indicate optional parameters or values
map is the raster map to display as background to show the sampling units or moving window that were setup
sam specifies the type of sampling area to be displayed:
 U = sampling units
 M = moving window

After starting *r.le.show* the user is asked a series of questions about how and where to display the sampling units or moving window.

The first question is: "Draw a new frame in which to display sampling areas? (y/n) [y]". If the user wants the sampling areas displayed in their original shape, size, and location as an overlay on the original map layer as is normally the case, then the user should answer "n" to this question. Then use the mouse to select the current window, which will usually be the whole window. After selecting the window, the user will then be asked to "Please enter the sampling unit file name:

> > > " This is usually "units". The sampling units of each scale can be overlain on each other or the screen can be refreshed before displaying each new scale. The user is asked "Refresh the screen? (y/n) [y]". If a moving window is to be displayed, then the moving window file name is usually "move_wind".

If the user answers "y" to the first question, then the mouse can be used to outline a new window. After outlining the window, the user will then be asked to "Please enter the sampling unit file name: > > > " This is usually "units". The sampling units of each scale can be overlain on each other or the screen can be refreshed before displaying each new scale. The user is asked "Refresh the screen? (y/n) [y]". If a moving window is to be displayed, then the moving window file name is usually "move_wind".

2.12 The r.le.trace program

When sampling the whole map (sam = W), the r.le.trace program can be used to do three things: (1) display the boundary of each patch and show how the boundary is traced, (2) display the attribute, size, perimeter, and shape indices for each patch, and (3) save these data in an output file. The syntax for the command-line version and the parameters for both interactive and command-line versions are as follows:

```
r.le.trace map = name [out = name]
```

where:

brackets [] indicate optional parameters or values

map is the name of the raster map whose patches are to be traced

out is the name of an output file that can be used to store patch data

After r.le.trace is invoked, the program begins tracing and the message "r.le.trace" is working ..." is displayed. Then the user is asked "Display the traced boundary of a particular patch? (y/n) [n]" If the user types "y" then the program asks the user for "The patch number" that is to be displayed. The patch number is generated by the r.le.trace program as it goes through the map and traces the patches. It will not usually be known ahead of time, so this option will often not be used first. Upon entering the patch number the program displays the tracing operation in the window and then prints the patch attribute, patch size, patch perimeter, and the three patch shape indices. The program then asks "Display another patch (y/n) [n]"

If the user answers "n" to the question "Display the traced boundary of a particular patch? (y/n) [n]" then the program asks "Display the patches sequentially, with their size, perim., shape? (y/n) [n]" If the user answers "n" then the program quits. If the user answers "y" then the user is given the following options:

```
<CR> - show patch
s - skip one patch
```

r - refresh screen
q - quit display and save

<CR> begins displaying the patch boundary in white and the patch data starting with patch #1. "s" skips the display of the next patch boundary, but prints the patch data. "r" erases the boundaries from the screen and redisplay the map. "q" allows the user to quit the r.le.trace program, but not erase the map layer. If the *out* parameter was specified, then the attribute, size, perimeter, and shape indices for each patch are saved in this file automatically.

3. GLOSSARY

Attribute: One of several values that are possible for the cells in a GRASS cell file, or a polygon in a GRASS vector file.

Class: see "Index class"

Element type: a part (element) of the landscape that has been classified as belonging to a group of similar elements. For example, barns and houses are elements that might be classified as members of the "buildings" element type.

GRASS raster map: a two-dimensional raster array of integer values representing a geographic area. A GRASS raster map actually consists of the cell file itself plus several supporting files. Of these, the most important is the cell header file which contains information on the number of rows and columns in the cell file and the geographic area it covers. Other supporting files include the cell category file, the cell color table file, the cell history file, and the cell range file. These files are normally handled automatically in GRASS whenever a raster map is manipulated. (Refer to the GRASS User's Guide and the GRASS Programmer's Manual for further information.)

GRASS vector map: a polygonal representation of a geographic area, where the polygons are formed by points and line segments (also known as nodes and arcs). GRASS vector maps consist of an arc-node file (a "dig" file) and several supporting files. The arc-node file contains a header section, which includes the geographic location of the layer, and a list of arcs and their defining points and nodes. The vector index and pointer file ("dig_plus" file) contains the polygon topology, i.e., information on which arcs and nodes comprise which polygons. The vector category attribute file ("dig_att" file) lists the category, or attribute, for each polygon, while the vector category label file ("dig_cat" file) lists labels for the categories, if they have been supplied by the user. Although in most cases, the supporting files are handled automatically by GRASS, the user must in some cases deal with them separately. For example, when performing a raster to vector conversion, it is necessary to first create the arc-node file and then the topology file. (Refer to the GRASS User's Guide and the GRASS Programmer's Manual for further information.)

Group: a reclassing of related attributes into a single unit or "group." For example all patches that have not been disturbed in 1, 5, 6, or 9 years might be grouped into a 0-10 year age group.

Index class: the values of many of the indices may be reported in index classes in order to display the distribution of index values.

Moving window: a square sampling area, with odd dimensions (e.g. 3 pixels wide by 3 pixels high), that is moved pixel-by-pixel across the rows in a map layer. At each location the center pixel is assigned the value for a particular structural measure calculated for the part of the map layer corresponding to the window area.

Sampling area: a polygon, with a certain size and shape, that identifies the area on a map layer that is to be used in calculating the r.l.e measures.

4. BIBLIOGRAPHY

- Anselin, L. 1989. Spatial regression analysis on the PC: spatial econometrics using GAUSS. Draft manual, Department of Geography and Department of Economics, University of California, Santa Barbara, Calif. 97 pp.
- Austin, R.F. 1984. Measuring and comparing two-dimensional shapes. p. 293-312 in Gaile, G.L. and C.J. Willmott (eds.) *Spatial Statistics and Models*. D. Reidel Publ. Co., Boston.
- Ford, E.D. and E. Renshaw. 1984. The interpretation of process from pattern using two-dimensional spectral analysis: modelling single species patterns in vegetation. *Vegetatio* 56:113-123.
- Forman, R.T.T. and M. Godron. 1986. *Landscape Ecology*. John Wiley and Sons, New York. 619 pp.
- Gardner, R.H., B.T. Milne, M.G. Turner, and R.V. O'Neill. 1987. Neutral models for the analysis of broad-scale landscape pattern. *Landscape Ecology* 1:19-28.
- Griffiths, D.A. 1987. *Spatial Autocorrelation: A Primer*. Resource Publications in Geography, Association of American Geographers, Washington, D.C. 86 pp.
- Griffiths, D.A. 1989. Spatial regression analysis on the PC. Institute of Mathematical Geography, Syracuse University, Discussion Paper No. 1. 84 pp.
- Griffiths, G.H. and M.G. Wooding. 1988. Pattern analysis and the ecological interpretation of satellite imagery. *Proceedings of the IGARSS '88 Symposium [Edinburgh, Scotland-Sept. 13-16, 1988]*, p. 917-922.
- Haralick, R.M. 1975. Statistical and structural approaches to texture. *Proceedings of the IEEE* 67:786-804.
- Haralick, R.M., K. Shanmugam, and I. Dinstein. 1973. Textural features for image classification. *IEEE Transactions on Systems, Man, and Cybernetics* SMC-3:610-621.
- Heinen, J. and G.H. Cross. 1983. An approach to measure interspersion, juxtaposition, and spatial diversity from cover-type maps. *Wildlife Society Bulletin* 11:232-237.
- Kennedy, S.K. and W.-H. Lin. 1986. FRACT-a FORTRAN subroutine to calculate the variables necessary to determine the fractal dimension of closed forms.

Computers & Geosciences 12:705-712.

Krummel, J.R., R.H. Gardner, G. Sugihara, R.V. O'Neill, and P.R. Coleman. 1987. Landscape patterns in a disturbed environment. *Oikos* 48:321-324.

MacEachren, A.M. 1985. Compactness of geographic shape: Comparison and evaluation of measures. *Geografiska Annaler* 67B:53-67.

Mead, R.A., T.L. Sharik, S.P. Prisley, and J.T. Heinen. 1981. A computerized spatial analysis system for assessing wildlife habitat from vegetation maps. *Canadian Journal of Remote Sensing* 7:34-40.

Milne, B.T. 1988. Measuring the fractal geometry of landscapes. *Applied Mathematics and Computation* 27:67-79.

Mulla, D.J. 1988. Using geostatistics and spectral analysis to study spatial patterns in the topography of southeastern Washington state, U.S.A. *Earth Surface Processes and Landforms* 13:389-405.

Musick, H.B. and H.D. Grover. 1990. Image textural measures as indices of landscape pattern. p. 77-103 in Turner, M.G. and R.H. Gardner (eds.) *Quantitative methods in landscape ecology*. Springer-Verlag, New York.

Odlund, J. 1988. *Spatial Autocorrelation*. Sage Publications, Beverly Hills, California. 87 pp.

Oliver, M., R. Webster, and J. Gerrard. 1989a. Geostatistics in physical geography. Part 1: theory. *Transactions of the Institute of British Geographers* 14:259-269.

Oliver, M., R. Webster, and J. Gerrard. 1989b. Geostatistics in physical geography. Part 2: applications. *Transactions of the Institute of British Geographers* 14:270-286.

O'Neill, R.V., J.R. Krummel, R.H. Gardner, G. Sugihara, B. Jackson, D.L. Angeles, B.T. Milne, M.G. Turner, B. Zygmunt, S.W. Christensen, V.H. Dale, and R.L. Graham. 1988. Indices of landscape pattern. *Landscape Ecology* 1:153-162.

Peet, R.K. 1974. The measurement of species diversity. *Annual Review of Ecology and Systematics* 5:285-307.

Renshaw, E. and E.D. Ford. 1984. The description of spatial pattern using two-dimensional spectral analysis. *Vegetatio* 56:75-85.

Risser, P.G., J.R. Karr, and R.T.T. Forman. 1984. Landscape ecology:

directions and approaches. Illinois Natural History Survey Special Publication No. 2, Champaign, Illinois. 18 pp.

Robertson, G.P. 1987. Geostatistics in ecology: interpolating with known variance. *Ecology* 68:744-748.

Shapiro, M., J. Westervelt, D. Gerdes, M. Higgins, and M. Larson. 1989. GRASS 3.0 Programmer's Manual. USA-CERL ADP Report N-89/14. US Army Corps of Engineers Construction Engineering Research Laboratory, Champaign, Illinois.

Urban, D.L., R.V. O'Neill, and H.H. Shugart, Jr. 1987. Landscape ecology: a hierarchical perspective can help scientists understand spatial patterns. *BioScience* 37:119-127.

USA-CERL. 1991. GRASS 4.0 Reference Manual. United States Army Corps of Engineers Construction Engineering Research Laboratory, Champaign, Illinois.

Woodcock, C.E., A.H. Strahler, and D.L.B. Jupp. 1988. The use of variograms in remote sensing: II. Real digital images. *Remote Sensing of Environment* 25:349-379.

APPENDICES

APPENDIX 1 - LIMITS

A number of limits are embedded in the code. Exceeding these limits may produce unexpected outcomes.

Number of attribute groups	= 25
Number of index classes	= 25
Number of pixels in any one patch's edge	= 5000
Number of scales that can be used simultaneously	= 15
Number of sites when sampling units are centered over sites	= 200

APPENDIX 2 - TIME NEEDED TO COMPLETE ANALYSES WITH THE R.LE PROGRAMS

The r.le programs may require minutes or hours to complete a particular analysis. The amount of time required varies only with the size of the map in the case of r.le.tex. In the case of r.le.dist and r.le.patch the amount of time varies with the size of the map and its complexity (number of patches, number of islands). With the r.le.dist and r.le.patch programs much of the execution time is spent tracing the patches rather than completing measurement calculations. Thus increasing the number of measures that you select will not dramatically increase the required execution time. On a Sun Sparcstation 1 running at 12.5 MIPS it takes approximately 2 minutes to use r.le.patch with all the measurement options to analyze a 250 X 250 pixel map (sam=W), and about 8 minutes with a 500 X 500 pixel map. The r.le.dist program is a little faster. The r.le.tex program may only require 30 seconds and 2 minutes for these map sizes.

Moving window analyses can be extremely time consuming, particularly with r.le.dist and r.le.patch, where the patches must be traced inside each window. For these two programs the time required approximately doubles as the length of a side of the window doubles. Thus a 10 X 10 window requires about twice as much time as a 5 X 5 window. On a Sun Sparcstation 1 running at 12.5 MIPS r.le.tex required 15 minutes to complete a 5 X 5 moving window analysis of a 250 X 250 pixel map, while r.le.patch required approximately 5 hours for the same window and map. The amount of time required for a moving window analysis can be determined by starting the analysis and observing the expected completion time, which will be printed on screen while the program runs. The expected completion time is updated as the window moves, so allow it to run for awhile to get the best estimate.

APPENDIX 3 - HELP MENUS FOR THE r.le ANALYSIS PROGRAMS

Usage:

```
r.le.dist map=name sam=name run=name [reg=name] ski=value can=value
        di1=name[,name,...] di2=name [out=name]
```

Parameters:

```
map  Raster map to be analyzed
sam  Sampling method:
      W = whole map           U = units
      M = moving window       R = regions
      options: W,U,M,R
run  Run prog. in:  F = foreground   B = background
      options: F,B
reg  Input name of regions map only when sam = R; hit return otherwise
ski  Skip m boundary cells to speed up nearest neighbor search
      options: 0-10
can  Include n candidate patches to speed up nearest neighbor search
      options: 1-30
di1  Distance measures:
      moving window (only 1 choice & only the 1st class/gp is used):
          I1 = mean dist.           I2 = st. dev. dist.
          I3 = mean dist. by gp     I4 = st. dev. dist. by gp
          I5 = no. of dist. by dist. class
          I6 = no. of dist. by dist. class by gp
      whole map, units, or regions (multiple choices allowed):
          I1-2  I3  I4  I5  I6
      options: I1,I2,I3,I4,I5,I6,I1-2
di2  Distance methods (required if di1 was specified; choose only 1):
      (CC=Center-Center, EE=Edge-Edge, CE=Center-Edge):
          M0 = each patch to all adjacent neighbors CC
          M1 = each patch to all adjacent neighbors CE
          M2 = each patch to nearest patch of same gp CC
          M3 = each patch to nearest patch of same gp CE
          M4 = each patch to nearest patch of same gp EE
          M5 = each patch to nearest patch of diff. gp CC
          M6 = each patch to nearest patch of diff. gp CE
          M7 = patches of 1 gp to nearest of specific gp CC
          M8 = patches of 1 gp to nearest of specific gp CE
          M9 = patches of 1 gp to nearest of specific gp CE
      options: M0,M1,M2,M3,M4,M5,M6,M7,M8,M9
out  name of output map from moving window operations
```

Usage:

```
r.le.patch map=name sam=name run=name [reg=name]
[att=name[,name,...]] [siz=name[,name,...]] [sh1=name]
[sh2=name[,name,...]] [fra=name] [per=name[,name,...]] [out=name]
```

Parameters:

```
map  Raster map to be analyzed
sam  Sampling method:
      W = whole map           U = units
      M = moving window       R = regions
      options: W,U,M,R
run  Run prog. in:   F = foreground   B = background
      options: F,B
reg  Input name of regions map only when sam = R; hit return otherwise
att  Attribute measures:
      moving window (only 1 choice & only the 1st class/gp is used):
          A1 = mean pixel attribute      A2 = st. dev. pixel attribute
          A3 = mean patch attribute       A4 = st. dev. patch attribute
          A5 = cover by gp               A6 = density by gp
      whole map, units, or regions (multiple choices allowed):
          A1-4   A5   A6
      options: A1,A2,A3,A4,A5,A6,A1-4
siz  Size measures:
      moving window (only 1 choice & only the 1st class /gp is used):
          S1 = mean patch size           S2 = st. dev. patch size
          S3 = mean patch size by gp      S4 = st. dev. patch size by gp
          S5 = no. by size class          S6 = no. by size class by gp
      whole map, units, or regions (multiple choices allowed):
          S1-2   S3   S4   S5   S6
      options: S1,S2,S3,S4,S5,S6,S1-2
sh1  Shape method (choose only 1 method):
      M1 = perim./area                  M2 = corr. perim./area
      M3 = rel. circum. circle
      options: M1,M2,M3
sh2  Shape measures (required if sh1 was specified):
      moving window (only 1 choice & only the 1st class/gp is used):
          H1 = mean patch shape           H2 = st. dev. patch shape
          H3 = mean patch shape by gp      H4 = st. dev. patch shape by gp
          H5 = no. by shape class          H6 = no. by shape class by gp
      whole map, units, or regions (multiple choices allowed):
          H1-2   H3   H4   H5   H6
      options: H1,H2,H3,H4,H5,H6,H1-2
fra  Fractal measures:   F1 = perimeter-area fractal dimension.
      options: F1
per  Perimeter measures:
      moving window (only 1 choice & only the 1st class/gp is used):
          P1 = sum of perims.             P4 = sum of perims. by gp
          P2 = mean perim.                P5 = mean perim. by gp
          P3 = st. dev. perim.            P6 = st. dev. perim. by gp
      whole map, units, or regions (multiple choices allowed):
          P1-3   P4   P5   P6
      options: P1,P2,P3,P4,P5,P6,P1-3
out  name of output map from moving window operations
```

Usage:

```
r.le.tex map=name sam=name run=name [reg=name] [div=name] [te1=name]
      [te2=name] [jux=name] [edg=name] [out=name]
```

Parameters:

```
map  Raster map to be analyzed
sam  Sampling method:
      W = whole map           U = units
      M = moving window       R = regions
      options: W,U,M,R
run  Run prog. in:   F = foreground   B = background
      options: F,B
reg  Input name of regions map-only when sam = R; hit return otherwise
div  Diversity measures:
      moving window (only 1 choice & only the 1st class/gp is used):
      D1 = richness           D2 = shannon
      D3 = dominance          D4 = inverse simpson
      whole map, units, or regions (only the following choice):
      D1-4
      options: D1,D2,D3,D4,D1-4
te1  Texture measures:
      moving window (only 1 choice & only the 1st class/gp is used):
      T1 = contagion          T2 = ang. sec. mom.
      T3 = inv. diff. mom.    T4 = entropy
      T5 = contrast
      whole map, units, or regions (only the following choice):
      T1-5
      options: T1,T2,T3,T4,T5,T1-5
te2  Texture methods (choose only 1):
      M1 = 2N-H               M2 = 2N-45           M3 = 2N-V
      M4 = 2N-135             M5 = 4N-HV           M6 = 4N-DIAG
      M7 = 8N
      options: M1,M2,M3,M4,M5,M6,M7
jux  Juxtaposition measures: (weight file in r.le.para needed)
      moving window (only 1 choice & only the 1st class/gp is used):
      J1 = mean juxtaposition
      J2 = standard deviation of juxtaposition
      whole map, units, or regions (only the following choice):
      J1-2
      options: J1,J2,J1-2
edg  Edge measures: E1 = sum of edges
      options: E1
out  name of output map from the moving window operations
```

END

**DATE
FILMED**

6 / 22 / 93