Received by OSTI
DEC 06 1990

CONF-910116--8

WHC-SA-1036-FP

Thermal Analysis of the FSP-1 Fuel Pin Irradiation Test

DO NOT MICROFILM
COVER

Prepared for the U.S. Department of Energy
Assistant Secretary for Nuclear Energy

Westinghouse
Hanford Company Richland, Washington

Hanford Operations and Engineering Contractor for the
U.S. Department of Energy under Contract DE-AC06-87RL10930

Copyright License By acceptance of this article, the publisher and/or recipient acknowledges the U.S. Government's right to retain a nonexclusive, royalty-free license in and to any copyright covering this paper.

Approved for Public Release

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency Thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DISCLAIMER

Portions of this document may be illegible in electronic image products. Images are produced from the best available original document.

LEGAL DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, nor any of their contractors, subcontractors or their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or any third party's use or the results of such use of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof or its contractors or subcontractors. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

Printed in the United States of America

DISCLM-2.CHP (10-90)

Thermal Analysis of the FSP-1 Fuel Pin Irradiation Test

W. F. Lyon III

Date Published
November 1990

To Be Presented at
8th Symposium on Space
Nuclear Power Systems
Albuquerque, New Mexico
January 7-10, 1991

Prepared for the U.S. Department of Energy
Assistant Secretary for Nuclear Energy

**Westinghouse
Hanford Company**

P.O. Box 1970
Richland, Washington 99352

Hanford Operations and Engineering Contractor for the
U.S. Department of Energy under Contract DE-AC06-87RL10930

Copyright License By acceptance of this article, the publisher and/or recipient acknowledges the U.S. Government's right to retain a nonexclusive, royalty-free license in and to any copyright covering this paper.

Approved for Public Release

JMP **MASTER**
DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

THERMAL ANALYSIS OF THE FSP-1 FUEL PIN IRRADIATION TEST

**William F. Lyon III
Westinghouse Hanford Company
P. O. Box 1970 Mail Stop L5-02
Richland, WA 99352
(509) 376-8869**

CAMERA READY MANUSCRIPT prepared for:

Eighth Symposium
on Space Nuclear Power Systems
Albuquerque, New Mexico
7-10 January 1991

initial submission: 25 July 1990

Author to whom correspondence should be sent: William F. Lyon III

THERMAL ANALYSIS OF THE FSP-1 FUEL PIN IRRADIATION TEST

William F. Lyon III
Westinghouse Hanford Company
P.O. Box 1970, Mail Stop L5-02
Richland, WA 99352
(509) 376-8869

ABSTRACT

Thermal analysis of a pin from the FSP-1 fuels irradiation test has been completed. The purpose of the analysis was to provide predictions of fuel pin temperatures, determine the flow regime within the lithium annulus of the test assembly, and provide a standardized model for a consistent basis of comparison between pins within the test assembly. The calculations have predicted that the pin is operating at slightly above the test design temperatures and that the flow regime within the lithium annulus is a laminar buoyancy driven flow.

INTRODUCTION

In support of the SP-100 program, fuel pin irradiation tests are being conducted. The goal of these tests is (1) to characterize and assess the performance of the candidate fuel pin configurations and (2) to demonstrate the lifetime and safety of the SP-100 fuel system. Thermal analyses of selected fuel pin irradiation tests have been initiated to calculate fuel pin operating temperatures. The results of these analyses will support test design and aid in the interpretation of postirradiation examination (PIE) data. The analyses will also help to characterize the test environment and the sensitivity to variations in that environment. This paper summarizes the development and the results to date of the irradiation test thermal analyses.

The fuel pin irradiation tests currently being conducted are part of the Ground Engineering Phase of the SP-100 program. Earlier tests, such as SP-1 and SP-2 (Dutt et al. 1985), demonstrated the feasibility of a variety of high performance fuels and materials. In contrast, the current tests, FSP-1 and SP-3, emphasize fuel system performance (Hales et al. 1989). The initial test chosen for thermal analysis was the FSP-1 test, which was designed and fabricated by Westinghouse Hanford Company for irradiation in the Fast Flux Test Facility (FFTF) at the Hanford site. The FSP-1 experiment consisted of one test assembly containing 19 fuel assemblies, each comprised of two encapsulated uranium nitride (UN) fuel pins. These pins featured Nb-1%Zr cladding and either free-standing tungsten or rhenium (Re) liners. A schematic diagram of the FSP-1 fuel assemblies is shown in Figure 1. After reaching a projected peak burnup of 2.7 at.%, the FSP-1 test was reconstituted as FSP-1R by replacing 16 fuel pins (removed for examination) with 16 fresh pins (featuring Re liners bonded to the Nb-1%Zr cladding). The test is continuing irradiation in FFTF until it reaches its target burnup of 7.7 at.%.

FIGURE 1. SP-100 FSP Series Fuel Assembly Schematic.

MODEL CONFIGURATION AND DEVELOPMENT

A test pin removed from the FSP-1 experiment during reconstitution was chosen for the current analysis. Future plans include evaluation of all pins removed from the FSP-1 test. The code used to model the FSP-1 test capsules was TEMPEST N32, a three-dimensional, time-dependent, hydrothermal analysis code (Trent et al. 1989). This code was developed for the U.S. Department of Energy in support of the Liquid Metal Fast Breeder Reactor Program and is ideally suited for evaluation of components in liquid metal environments such as the FFTF.

As shown in Figure 1, each FSP-1 fuel assembly was composed of two encapsulated fuel pins. When inserted into the FFTF, one fuel capsule was situated above the core midplane while the other was below. Each fuel capsule was comprised of a 0.3048 m (12 in.) helium-filled UN fuel pin. The fuel pins were immersed in lithium and contained inside a tungsten-zirconium-molybdenum (TZM) subcapsule. The TZM subcapsule was further encapsulated in an ASTM 316 stainless-steel tube with an insulating helium/argon gas gap. The temperature within the assembly is controlled through a combination of core positioning and gas gap composition. Figure 2 illustrates the configuration of the model used in TEMPEST N32 to evaluate the designated test pin.

Of primary concern in the model development was the designation of the properties and boundary conditions used to represent the materials within the capsule. Due to the temperature sensitivity of the fluid properties, helium, lithium, and the helium/argon mixture were modeled as temperature dependent. The properties for the structural materials and fuel were evaluated at temperatures representative of in-core operating conditions. Energy deposition data was obtained from physics calculations performed in support of FSP-1R (Knutson 1989). The energy deposition for each material was then varied according to the axial flux profile. For the non-fissioning materials, the gamma heating profile was assumed to be proportional to the predicted flux profile. The reactor coolant temperatures adjacent to the assembly, corresponding to the pin location, were used as the external boundary conditions. Axial sodium temperatures were obtained from previous analyses of the FSP-1 test assembly using the SUPERENERGY-2 code (Basehore 1980, Cramer 1990).

ANALYSES, RESULTS, AND DISCUSSION

The results of the analyses provided predicted temperature profiles throughout the fuel assembly. Additionally, velocity vectors and temperature contours were calculated in the lithium annulus. The FSP-1 test pin selected for initial analysis targeted a 1500 K peak cladding temperature and a measured peak burnup of 2.29 at.%. This temperature value was used as the basis of comparison for the TEMPEST N32 predicted results. Based on the predicted temperature data, the flow regime within the lithium annulus was also determined.

Predicted Temperatures

Figure 3 illustrates the assembly axial temperature profiles generated by TEMPEST N32. The origin of the y-axis of Figure 3 is located at the base of the fuel column, which is approximately 0.165 m (6.5 in.) above core midplane. The TEMPEST N32 code predicted a peak cladding inner surface temperature of 1547 K. This value was slightly above the target peak cladding temperature of 1500 K.

FIGURE 2. FSP-1 TEMPEST N32 Model1.

FIGURE 3. Assembly Axial Temperature Profiles.

Figure 4 is a plot of the predicted radial temperature profile for the peak axial location. The figure indicates that the low conductivity gas regions were, as expected, responsible for the majority of the temperature drop across the system. The temperature drop across the helium/argon gap was 877 K. In contrast, the profile across the lithium annulus was relatively flat with a temperature drop of only 57 K.

Figure 5 is a plot of the temperature contours and velocity vectors in the assembly predicted by TEMPEST N32. (See Figure 2 for the relative locations of each part of the TEMPEST N32 model.) Each contour represents a temperature difference of approximately 25 K. The velocity vectors are quite small and exhibit clockwise rotation within the lithium annulus; this is characteristic of buoyancy driven flow. The maximum velocity was 0.1 m/s with its location corresponding to a large, negative temperature gradient of 1.17×10^4 K/m at the top edge of the fueled portion of the pin. As the flow moved vertically upward past this region, it encountered a slow moving, cold lithium region. The temperatures in this region averaged some 460 K less than the bottom of the assembly. Through this region, the flow slowed to 0.007 m/s. The plot also illustrates that the heat flow was primarily radial parallel to the fueled region. However, calculations based on the heat fluxes between the cladding outer surface and the TZM inner surface indicated that approximately 30% of the temperature drop across the lithium cavity was due to axial heat transport; this being a combination of natural convection and conduction.

Flow Regime Determination

The TEMPEST N32 code required that either laminar or turbulent flow be designated for the proper heat transfer correlations to be applied. Since the flow regime was previously unknown, both laminar and turbulent cases were analyzed. In order to determine the flow regime within the lithium annulus, semi-empirical correlations were applied to the predicted TEMPEST N32 results. The Rayleigh number, Ra_b , describes the ratio of buoyancy versus viscous forces and is given by,

$$Ra_b = \frac{g\beta(T_s - T_\infty)b^3}{\nu\alpha}$$

where g is gravitational acceleration, β is the volumetric expansion coefficient, T_s is the wall surface temperature, T_∞ is the free stream fluid temperature, b is the characteristic dimension, ν is the kinematic viscosity, and α is the thermal diffusivity. For concentric cylinders, a modified Rayleigh number, Ra_{cc}^* , was required and is given by Raithby and Hollands (1975) as

$$Ra_{cc}^* = \frac{\ln(D_o/D_i)}{b^{3/4}(1/D_i^{3/5} + 1/D_o^{3/5})^{5/4}} Ra_b^{1/4}$$

where D_o refers to the outer surface diameter, D_i is the inner surface diameter, and b is the annulus thickness.

FIGURE 4. Radial Temperature Profile for the Peak Axial Location.

FIGURE 5. Temperature Contour and Velocity Vector Plot. (The location of each assembly component is illustrated in Figure 2.)

The results of calculations yielded a Ra_{cc}^* of 2.9×10^3 for the laminar case and a Ra_{cc}^* of 3.6×10^3 for the turbulent case. The literature indicates that transition from laminar to turbulent flow for this geometry occurs in the Ra_{cc}^* range of 10^7 to 10^9 . This suggests that the flow regime within the lithium annulus is laminar. As mentioned previously, Figure 5 illustrates the reduction of velocity in the lithium flow field as it reaches the colder, more stagnant upper levels of the assembly. These low fluid velocities tend to support the laminar flow conclusion. It should be noted, however, that this may not be the case for every fuel assembly within the FSP-1 test. For pins located below core midplane, the orientation of the fueled region and the peak in the axial flux profile do not coincide. This may tend to increase the velocities within the annulus and drive the system closer to a laminar/turbulent transition flow regime.

CONCLUSIONS

A standardized model has been created for the thermal analysis of the FSP-1 test assembly. This model will allow a wide variety of studies to be conducted on fuel tests in support of the SP-100 project. The results of the analyses included predicted temperatures within the system and the determination of a laminar flow regime in the lithium annulus. The predicted peak cladding inner surface temperature was somewhat above the design temperature. However, based upon the excellent behavior of the fuel examined, this poses no problem and testifies to the robustness of the fuel design. Planned future studies include (1) expansion of the analysis to include all pins removed for PIE and (2) completion of a series of sensitivity studies to assess the effect of uncertainty in test parameters, such as component emissivities, on the temperatures within the system.

ACKNOWLEDGMENTS

The SP-100 irradiation testing is an interlaboratory effort supported by the U.S. Department of Energy, the Strategic Defense Initiative Office, and the National Aeronautics and Space Administration. The construction, performance, and examination of the tests are conducted by Westinghouse Hanford Company under Contract No. DE-AC06-87RL10930. Additionally, the author would like to recognize the contributions of Alvia Bridges and Bruce Makenas of Westinghouse Hanford Company and Don Trent of Battelle Pacific Northwest Laboratory.

REFERENCES

- Basehore, K. L. and N. E. Todreas (1980) *SUPERENERGY-2: A Multiassembly, Steady-State Computer Code for LMFBR Core Thermal-Hydraulic Analysis*, PNL-3379, Battelle Pacific Northwest Laboratory, Richland, WA.
- Cramer, E. R. (1990) Personal Communication, Westinghouse Hanford Company, Richland, WA, April 1990.
- Dutt, D. S., C. M. Cox, R. A. Karnesky, R. B. Matthews, and M. K. Millhollen (1985) "Performance and Testing of Refractory Alloy Clad Fuel Elements for Space Reactors," in *Proc. 20th Inter Soc. Energy Conversion Conference*, held in Miami Beach, FL, August 1985.
- Hales, J. W., B. J. Makenas and D. S. Dutt (1989) "SP-100 Fuel Pin Irradiation Testing," in *Trans. 6th Symposium on Space Nuclear Power Systems*, CONF-890103-Summs., held in Albuquerque, NM, 8-12 January, 1989.
- Knutson, B. J. (1990) "Updated Calculations of FSP-1 Fuel Pin Burnups," Internal Memo, FRRP:Kn90-003, Westinghouse Hanford Company, Richland, WA.
- Raithby, G. D. and K. G. T. Hollands (1975) "A General Method of Obtaining Approximate Solutions to Laminar and Turbulent Free Convection Problems," in *Advances in Heat Transfer*, Volume 11, T. F. Irvine and J. P. Harris, eds., Academic Press, NY, pp. 265-315.
- Trent, D. S. and L. L. Eyler (1989) *TEMPEST: A Three-Dimensional Time-Dependent Computer Program for Hydrothermal Analysis*, PNL-4348, Volume 1, Rev. 2, Battelle Pacific Northwest Laboratory, Richland, WA.

DISTRIBUTION

Number of copies

OFFSITE

4 8th Symposium Proceedings (3)
 Institute for Space Power
 Studies Chemical and Nuclear
 Engineering Department
 University of New Mexico
 Albuquerque, New Mexico 87131

R. Bruce Matthews
Los Alamos National Laboratory
P.O. Box 1663, MS: J576
Los Alamos, New Mexico 87545

ONSITE

11	D. S. Dutt	L5-60
	J. W. Hales	L5-02
	W. F. Lyon III (5)	L5-02
	C. Richins	A6-55
	Publication Services (3)	L8-07

DO NOT
THIS PAGE