**Summary Report: Preliminary Assessment
of Deep Injection Well
Associated Surface Soils at the
Idaho National Engineering Laboratory**

January 1993
EGG-ESQ-10614

EG&G Idaho, Inc.

Prepared by

Samuel Pole
S. B. Pole, Sr. Engineering Specialist
Environmental Technology Unit

1/7/93
Date

Reviewed by

Jay Johnson
J. A. Johnson, Scientist
Environmental Monitoring Unit

1/7/93
Date

Approved by

E. D. Walker
E. D. Walker, Sr. Scientist
Environmental Monitoring Unit

12/28/92
Date

Summary Report: Assessment of Deep Injection Well Associated Surface Soils at the Idaho National Engineering Laboratory

Samuel B. Pole

January 1993

**Idaho National Engineering Laboratory
EG&G Idaho, Inc.
Idaho Falls, Idaho 83415**

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

**Prepared for the U.S. Department of Energy
Office of Environmental Restoration and Waste Management
Under DOE Idaho Field Office
Contract DE-AC07-76ID01570**

MASTER
DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

ABSTRACT

This report summarizes sampling activities and analytical results of the chemical and radiological content of surface soils from storm water retention basins and drainage ditches associated with eight deep injection wells at the Idaho National Engineering Laboratory. The results of the sampling effort were intended to support permitting of the injection wells by the State of Idaho Department of Water Resources. In August 1992, the surface soils associated with eight storm water retention basins and ditches were sampled. All samples were collected and analyzed in accordance with a written sampling and analysis plan. The samples were analyzed by an off-Site contract laboratory, and the results were compared to local and regional soil analytical data to determine the presence of contaminants. The results indicated that the surface soils from the storm water retention basins and ditches did not have concentrations of metals or radionuclides greater than the range of concentrations found in local and regional soils. Volatile organic compounds were below detection limits.

CONTENTS

ABSTRACT	iii
1. INTRODUCTION	1
2. BACKGROUND	3
2.1 Location of the INEL	3
2.2 Description of the INEL and Surrounding Area	3
2.3 Hydrologic Setting	4
2.3.1 Surface Drainage	4
2.3.2 Ground Water	4
2.4 Description of Eight Deep Injection Wells at the INEL	4
2.4.1 Deep Injection Well Locations	5
2.4.2 Surface Completion	9
2.4.3 Subsurface Completion	9
2.4.4 Physical Observations	9
3. SAMPLING DESIGN	11
3.1 Sampling Objective and Scope	11
3.2 Analytical Objectives and Scope	11
4. SAMPLING PROCEDURES	13
5. SAMPLE ANALYSES	15
6. QUALITY ASSURANCE	16
6.1 Activity Specific Procedures	16
6.2 Deviations from Sampling and Analysis Plan	16
6.3 Validation and Data Entry	17
7. ANALYTICAL RESULTS	18
7.1 Metals	18
7.2 Volatiles	18

7.3 Radiological Results	19
8. SUMMARY OF RESULTS	20
8.1 Summary of Metals Analyses	20
8.2 Summary of Volatile Organic Analyses	20
8.3 Summary of Radiological Analyses Results	20
9. REFERENCES	22
Appendix A—Quality Assurance Sampling and Analysis Plan for the INEL Injection Well Retention Basins	A-1
Appendix B—Field Log Notes	B-1
Appendix C—Chain of Custody Forms	C-1
Appendix D—Summary of Inorganic Results Data	D-1
Appendix E—Summary of TCLP Volatile Organic Results Data	E-1
Appendix F—Summary of Analysis Results for Radionuclides	F-1
Appendix G—Summary of Soil Concentration Data for Comparison with Deep Well Retention Basin Associated Soils	G-1

Summary Report: Assessment of Deep Injection Well Associated Surface Soils at the Idaho National Engineering Laboratory

1. INTRODUCTION

The purpose of this sampling and analysis effort was to provide chemical and radiological data in support of permitting eight deep storm water injection wells at the Idaho National Engineering Laboratory (INEL) Site (see Figure 1). The information was requested by the State of Idaho Department of Water Resources (IDWR) for purposes of completing permit applications submitted to the State by the Department of Energy Idaho Field Office (DOE-ID). The permit applications were previously submitted to IDWR in compliance with State and Federal Underground Injection Control (UIC) program requirements.

The sampling of the surface soils associated with eight deep storm water injection wells at the INEL was to assess whether chemical or radiological contaminants may have been discharged to injection well storm water retention basins or drainage ditches and thereby potentially to the subsurface via the injection wells.

The principle objectives of this study were to

- Determine the radiological characteristics of surface soils near the injection wells' associated retention basins and to compare the data to INEL Site-wide radiological data
- Determine the chemical characteristics (total metals and volatile organics) of the surface soils associated with the deep injection wells.

A secondary objective was to comply with a request from IDWR that representatives from their office be granted the opportunity to observe the field sampling effort and to familiarize themselves with the location, construction, and operation of the eight deep storm water injection wells. This goal was met by arranging time in the field that fit the schedules of IDWR representatives. John Mitchell and John McLeod of IDWR observed the collection of soil from the storm water retention basins and drainage ditches associated with the eight deep injection wells on August 17 and 18, 1992.

Figure 1. Location of the Idaho National Engineering Laboratory.

2. BACKGROUND

2.1 Location of the INEL

The INEL is located in the southeastern portion of Idaho and encompasses approximately 890 mi². The INEL Site extends approximately 39 miles north to south and about 36 miles from east to west at its broadest part. The Site is situated on the northwestern edge of the eastern Snake River Plain approximately 40 miles west of Idaho Falls. Public access is limited to a few public highways that cross the Site east to west. No public highway crosses the Site north to south. Security personnel patrol public highways crossing and bordering the Site (see Figure 1).

The INEL occupies portions of five counties: Butte, Jefferson, Bonneville, Clark, and Bingham. The eastern boundary of the Site is 22 miles west of Idaho Falls. The southern boundary is 23 miles northwest of Blackfoot and 37 miles northeast of Pocatello.

2.2 Description of the INEL and Surrounding Area

The INEL lies within an area classified as a sagebrush ecosystem. This ecosystem occupies broad plains and plateaus derived from lava flows, ancient lake beds, and broad basins of alluvium. This ecosystem is characterized by shrubs, principally sagebrush, with an understory of perennial grasses and forbs. The dominant and most conspicuous plant at the INEL is large sagebrush (>3 ft tall), which covers approximately 80% of the area (460,000 acres).

The Snake River Plain is separated into three minor physical subdivisions: a central trough that extends to the northeast through the INEL and two flanking slopes that descend to the trough—one from the mountains to the north and northwest (the Lost River, Lemhi, and Bitterroot mountain ranges) and the other from a broad ridge extending from the southwest to the northeast through the Big Southern, Middle, and East Buttes on the southern portion of the INEL.

The surface of the Snake River Plain upon which the INEL is located is relatively flat. The predominant relief is manifested either by volcanic buttes jutting from the desert floor or by frequent, unevenly surfaced basalt flows, flow vents, or fissures. Elevations at the INEL range from 5,200 ft in the northeast to 4,750 ft in the southwest, with the average elevation being 5,000 ft (1,524 meters) above sea level.

INEL soils have, in general, formed as a result of alluvial, lacustrine, and eolian deposition over basalt lava flows and are derived from silicic volcanic and Paleozoic rocks from nearby mountains and buttes. Rock outcrops are common and some soils are relatively shallow. Thirteen soil series have been mapped at the INEL; 10 of the soils are classified as loams and the remaining soils are sands. Soil depth varies across the Site with deeper soils found primarily in the central and northern portions. Regardless of depth, all soils overlie fractured basalt rocks of the Snake River Plain.

Areas bordering the INEL are primarily undeveloped desert with some agriculture carried out along the northeast boundary. Approximately 95% of the INEL has been withdrawn from the public domain by DOE. However, approximately 330,000 acres of the INEL is open to controlled grazing by cattle or sheep. All grazing is prohibited within 2 miles of any nuclear facility and no dairy cows are allowed.

2.3 Hydrologic Setting

Activities conducted at the INEL potentially impact both surface and ground water quality. However, this sampling effort was directed primarily at the question of the possible presence of contaminants in surface soils in storm water retention basins associated with eight deep injection wells, and, therefore, the potential impact on ground water quality from the infrequent injection of storm water.

2.3.1 Surface Drainage

Most of the INEL is located in the Pioneer Basin, a poorly defined closed drainage basin. Surface water in the basin includes that from the Big Lost River, Little Lost River, and Birch Creek that drain mountain watersheds located to the north and northwest of the Site. The Big Lost River crosses the INEL to discharge to playas near the north-central border of the Site. Other principal drainages do not cross the INEL, but are restricted by topography to the northern areas on the Site.

Typically, surface flow onto or across the INEL occurs during regional high runoff and high flow years. These conditions have been almost nonexistent since the mid-1980s. Local rainfall and snowmelt also contribute to surface water resources, but are generally insufficient to cause significant runoff. However, rainfall and snowmelt do contribute to runoff to the storm water retention basins and contributing drainage ditches.

2.3.2 Ground Water

The Snake River Plain Aquifer underlies the INEL and supplies drinking and industrial water for the Site as well as irrigation water for agriculture in the region. The aquifer is approximately 200 miles long, 40 to 60 miles wide, and covers an area of 9,600 mi². The saturated zone occurs at a depth of approximately 450 ft below ground surface with a gradient from the northeast to the south-southwest. The aquifer is structurally complex, being composed of basalt flows and interlayered pyroclastic and sedimentary materials with permeability controlled principally by the distribution of highly fractured basalt flow tops and interflow zones.

Recharge to the aquifer occurs mostly through infiltration of irrigation water and from valley underflow from approximately 35,000 mi² of recharge area in the adjacent mountains to the north and northeast of the Snake River Plain. Direct recharge from precipitation falling on the Snake River Plain is estimated to be less than 10% of total recharge to the aquifer. Recharge to the aquifer from within the INEL occurs from river and stream flow across the Site and onto border areas, and also marginally through rainfall and snowmelt that collects in depressions in the basalt and in playa lakes. In addition, recharge occurs through effluent discharges to infiltration ponds at the INEL, and can occur through direct injection of rainfall and snowmelt through deep injection wells.

2.4 Description of Eight Deep Injection Wells at the INEL

Permit applications were submitted in 1986 to IDWR by DOE to permit eight deep injection wells used to inject excess storm water. The applications were submitted in compliance with IDWR regulations requiring that deep injection wells (injection wells 18 ft or deeper) be permitted by the State. Three deep injection wells are located in the vicinity of the Special Power Excursion Reactor

Test (SPERT) facility; one deep injection well is located at the Central Facility Area (CFA); and four deep injection wells are located at the Test Area North (TAN) facility.

2.4.1 Deep Injection Well Locations

Three deep injection wells, SPERT 34-W-3-1, SPERT 34-W-3-2, and SPERT 34-W-3-3, are located on either side of Jefferson Boulevard (see Figure 2). Storm water and snowmelt drain along a series of drainage ditches to a storm water retention basin associated with each well. The areas that drain to these wells are largely undeveloped grasslands surrounded by elevated basalt slopes. Developed areas are distant from the storm water retention basins and do not typically discharge directly to them.

The CFA deep injection well, CFA-34-W-3-4, is located on the west side of Main Street near its intersection with Montana Avenue (see Figure 3). Storm water and snowmelt discharge to a storm water retention basin through a series of drainage ditches and culverts that drain primarily developed and paved areas at CFA.

Four TAN deep injection wells, TAN 34-W-3-5, TAN 34-W-3-6, TAN 34-W-3-7, and TAN 34-W-3-8, are located in or adjacent to the TAN complex (see Figure 4). TAN 34-W-3-8 does not have a storm water retention basin associated with it. Storm water runoff drains through several ditches that discharge directly toward the TAN 34-W-3-8 well location. While collecting soil samples near this well, it was observed that work had been done on the ditch to minimize the amount of runoff that might drain toward the deep injection well enclosure inlet and that the ditch had been modified to more readily discharge past the injection well to the open desert. The other three injection wells had very large storm water retention basins associated with them.

The storm water retention basin associated with the TAN 34-W-3-5 deep injection well collects runoff from largely unpaved areas. Some runoff originates from an adjacent paved roadway and nearby parking area, as well as from developed areas at the southwest corner of the TAN facility.

The storm water retention basin associated with the TAN 34-W-3-6 deep injection well collects runoff primarily from the paved and developed areas of the TAN facility.

The storm water retention basin associated with the TAN 34-W-3-7 deep injection well collects runoff primarily from unpaved and undeveloped drainage areas northwest of the TAN facility. A paved roadway and developed rail easement extend to the west-northwest several hundred yards west of the basin. Runoff water during sufficiently wet weather drain to this structure through a complex of ditches.

Figure 2. Location of SPERT deep injection wells.

Figure 3. Location of the CFA deep injection well.

Figure 4. Location of the TAN deep injection wells.

2.4.2 Surface Completion

The surface completion of each of the deep injection wells is similar, with only minor design/construction differences. Consequently, a single description of the surface completion is applicable to each of the deep injection wells. Each deep injection well is enclosed in a concrete sump with closed top. The sumps are approximately 5–6 ft² and 3-ft deep. The TAN 34-W-3-8 deep injection well enclosure was circular with a diameter of approximately 5 ft. The floors of the sumps are concrete. Except for TAN 34-W-3-8, a piece of casing extends through one wall of each sump and protrudes outward into the retention basins. Inlets typically were greater than 5 ft above the floor of the respective retention basin. This inlet casing to TAN 34-W-3-7 was approximately 13 ft above the floor of its storm water retention basin. A removable grid used to restrict debris from entering the sumps was attached to the end of the inlet casings. TAN 34-W-3-8 has a port cut into the side of the sump through which storm water from the associated drainage ditch may enter the well enclosure if the drainage ditch is moderately full. Well casings extended 1–2 ft above the floor of each of the sumps and were capped with secondary steel grids or mesh screens to prevent debris from entering the well bore.

2.4.3 Subsurface Completion

INEL deep injection well completion data are presented in Table 1. Each of the deep injection wells contains 10- to 20-in.-diameter casing. SPERT 34-W-3-1, SPERT 34-W-3-3, TAN 34-W-3-5, TAN 34-W-3-6, and TAN 34-W-3-7 well casings extend to or nearly to total well depth. The casings have been perforated to allow or enhance water flow into the subsurface formations. Perforated intervals have not been identified for SPERT 34-W-3-1 and SPERT 34-W-3-3. The remaining three deep injection wells have shallow casings installed with open bores to depth.

2.4.4 Physical Observations

Each of the deep injection wells respond to changes in atmospheric pressures or changes in surface temperatures. This was especially evident during the two days that soil samples were collected. A strong flow of cool air was exiting each of the deep injection wells in response to lower atmospheric pressures, land surface heating, or both.

Water marks, strand lines, and vegetation indicated that none of the storm water retention basins had received significant volumes of water for some time. This observation was supported by U.S. Geological Survey (USGS) personnel who monitor and inspect the wells. Personnel working in the associated facility areas also confirmed that very little storm water had collected in the retention basins since the late 1980s. The USGS efforts to collect injected storm water also indicate that very little storm water has been injected into the subsurface through the deep injection wells for many years.

There is no storm water retention basin associated with TAN 34-W-3-8. The well is designed to receive surface flow through a near ground-level port into its enclosure. However, water would have to be approximately 2-ft deep in the drainage ditch to actually enter the well. Of the eight deep injection wells, TAN 34-W-3-8 is the most likely to have injected surface water over the last 4–5 years.

Table 1. INEL deep injection well completion data.

Well No.	Year of construction	Location	Total depth (ft)	Casing diameter (in.)	Casing depth (ft)	Depth to ground water (ft)	Drainage area (acres)
34-W-3-1	1963	SPERT	253	16-20	253	455	11,875 ^a
34-W-3-2	1963	SPERT	326	16-20	26	455	11,875 ^a
34-W-3-3	1963	SPERT	254	16	250	455	11,875 ^a
34-W-3-4	1963	CFA	68	20	10	479	2,500
34-W-3-5	1967	TAN	327.5	10	327.5 ^b	210	37
34-W-3-6	1967	TAN	252	10	252 ^c	198	62.5
34-W-3-7	1967	TAN	302	10	302 ^d	205	1,250
34-W-3-8	1967 (?)	TAN	41	24	15	210	39

- a. Injection wells 34-W-3-1, 34-W-3-2, and 34-W-3-3 have a cumulative drainage area of 11,875 acres.
- b. Injection well 34-W-3-5 casing is perforated between 84.96-84.96 ft, 205.61-215.30 ft, and 284.84-315.38 ft.
- c. Injection well 34-W-3-6 casing is perforated between 117-127 ft, 201.4-221.5 ft, and 231.5-251.6 ft.
- d. Injection well 34-W-3-7 casing is perforated between 155.6-166 ft, 246.5-266 ft, and 277.1-299.6 ft.

3. SAMPLING DESIGN

A biased sampling design was used to collect surface soil samples from storm water retention basins and one drainage ditch associated with the eight deep injection wells at the INEL. The sampling plan approach and design were presented to the staff of IDWR for review and comment prior to implementation. Prior to initiating final permitting procedures for the eight deep injection wells, IDWR requested water quality data for injected water. However, because of the extended drought and the fact that seven of the wells only infrequently inject water, injected water was unavailable for sampling. Consequently, DOE-ID and IDWR agreed that biased sampling and analysis of surface soils from associated storm water retention basins and drainage ditches would provide the best potential for detecting the presence or absence of hazardous constituents and, therefore, provide an indirect indication of injected water quality.

3.1 Sampling Objective and Scope

The objective of the project was to provide technically representative sampling and analysis of surface soils associated with several deep injection well retention basins and a drainage ditch that were repeatedly inundated by storm water runoff and snowmelt. The analytical data would then be compared to information on uncontaminated surface soils from elsewhere on the Site.

Three surface soil samples were to be collected from three borings in each of the seven storm water retention basins and along the drainage ditch that discharges past the eighth injection well, TAN 34-W-3-8. Sample intervals were 0–6 in., 6–12 in., and 12–18 in. below the surface.

The selection of sampling sites was biased toward those locations that would provide the most accurate representation of potential contaminants. It was a worse-case condition. Initial sampling locations were selected at the point of discharge to the retention basin, at the lowest point of the basin, and near the basin inlet to the well enclosures. For TAN 34-W-3-8, biased sampling locations included the two lowest points in the ditch and a point adjacent to the inlet to the well enclosure. Provisions were also made for making mutually agreed changes to the sampling plan by IDWR and INEL employees while in the field, depending on site conditions.

Factors affecting sampling site selection included topography of the storm water retention basins, evidence of repeated conditions of "standing water," and the position of inlets to the well enclosures. Factors affecting the number of samples collected included soil texture (large gravel prevented auger penetration and sample recovery) and evidence that storm water discharged to a storm water retention basin was largely confined to a small area of the basin.

3.2 Analytical Objectives and Scope

Because of the absence of storm water runoff for sampling and analysis, surface soils from each of the storm water retention basins or drainage ditch were to be analyzed to determine whether regulated contaminants were present. The presence of contaminants in the surface soils would provide an indirect indication of the possibility of contaminants entering the deep injection wells.

Soil samples were to be collected and analyzed according to the guidelines set forth in U.S. Environmental Protection Agency (EPA) SW-846 for Resource Conservation and Recovery Act (RCRA) total metals and using the toxicity characterization leaching procedure (TCLP) extraction

method 1311 followed by method 8240 for volatile organic analysis (VOA) and method 6010 for metals (method 7470 for mercury). Radiological analysis (gross alpha/beta and gamma spectrometry) was also to be performed on the collected soil samples.

Only one VOA sample was to be collected from each of the well sites. Site selection for the VOA was to be based on the worse-case situation observed at each of the well sites. This location was typically a site that appeared to be frequently inundated and located at the point of discharge to the storm water retention basins. Field analyses of soil samples using a Photovac MicroTIP photoionization detector (PID) were performed to determine the need to collect additional VOA samples.

Recovered soil samples were placed in plastic bags. The bags were sealed and the soil gases were allowed to equilibrate before analysis. The tip of the PID was inserted into the headspace of the bags to monitor the presence of volatile organics in the soil gases. A target concentration of 3 ppm was used to determine if additional VOA samples should be collected.

4. SAMPLING PROCEDURES

The sampling procedures are detailed in the *Quality Assurance Sampling and Analysis Plan for INEL Injection Well Retention Basins No. EMS-142-90* (see Appendix A). Changes to the field sampling plan were discussed with IDWR personnel who were onsite to observe the sampling effort and to examine the storm water retention basins and deep injection wells. Field notes were kept to document the sampling effort and to record the sample locations. All changes were noted in the field log notes (See Appendix B). A general summation of collection procedures and field measurements taken follows.

Soil samples were collected from each 6-in. interval from the surface to a depth of 18 in., providing site conditions did not require changes in the sampling procedure. At each sampling site, a hand auger was used to collect and extract samples of soil. The auger was advanced through each sample interval until the appropriate depth was achieved or a decision was made to withdraw from the borehole.

To ensure that representative soil samples were collected for each sampled interval, parallel auger holes approximately 6–12 in. apart were advanced at each site. Soil media from each of the 6-in. sample intervals were placed in a separate aluminum pan before being transferred to an appropriate sample container.

Each sample container was filled and sealed in the field and then logged on a chain of custody (COC). The sample containers were then surveyed for radiological contamination in preparation for offsite shipment to a commercial laboratory contracted to provide analytical services.

Several predetermined sampling sites were moved and one well interval was not collected. A summary of activities at each well site follows:

- **SPERT 34-W-3-1.** The predetermined location for samples 7, 8, and 9 was moved from an area adjacent to the injection well inlet to a low area that appeared to frequently receive "standing water." Sample 9 was not collected because large rocks and very coarse gravel were encountered that prevented advancement of the auger.
- **SPERT 34-W-3-2 and SPERT 34-W-3-3.** Soil samples were collected from the predetermined sample locations and from each of the intended sample intervals.
- **CFA 34-W-3-4.** The predetermined locations for samples 4, 5, and 6, and samples 7, 8, and 9 were moved from the center of the retention basin and near the injection well inlet, respectively. The locations were moved to sites that appeared to frequently receive "standing water" and, therefore, provide a better opportunity to detect possible contaminants. Soil samples were collected from each of the intended intervals in each of the auger holes.
- **TAN 34-W-3-5.** The predetermined location for samples 7, 8, and 9 was moved from an area adjacent to the injection well inlet to an area that appeared to frequently receive "standing water." Soil samples were collected from each of the intended sample intervals in each of the auger holes.

- **TAN 34-W-3-6.** Samples 7, 8, and 9 were not collected. Site conditions, such as the large size of the basin and lack of any evidence that water frequently collected in the area of the inlet to the deep injection well, indicated that sampling in the area of the inlet to the storm water retention basin would provide the best opportunity to detect possible contaminants. This decision was unconditionally discussed with and agreed to by personnel from IDWR. Soil samples were collected from each of the intended sample intervals at each of the two sampling sites.
- **TAN 34-W-3-7.** Samples 7, 8, and 9 were not collected. Site conditions, such as the confined area of the basin, indicated that sampling in the area of the inlet to the storm water retention basin and at the center of the basin would provide the best opportunity to detect possible contaminants. This decision was discussed with and agreed to by personnel from IDWR. Soil samples were collected from each of the intended intervals at each of the two sampling sites.
- **TAN 34-W-3-8.** Soil samples were collected from the predetermined sample locations and from the intended sample intervals.

5. SAMPLE ANALYSES

All samples were analyzed by Lockheed Environmental Systems & Technologies Co. in accordance with the sampling and analysis plan (SAP), EMS-142-90 (see Appendix A), and in accordance with appropriate EPA SW-846 methods. Sample results are summarized in the following appendices:

<u>Appendix</u>	<u>Analysis</u>	<u>Method</u>
Appendix D	Total metals	CLP 7/88 or 3/90
Appendix E	Radionuclides	Gross alpha/beta and gamma spectrometry
Appendix F	Volatile organics	CLP 7/88 or 3/90

6. QUALITY ASSURANCE

The sampling effort was conducted in accordance with a written SAP (see Appendix A). All field activities were recorded in indelible ink in a designated sample logbook. The sample logbook entries recorded field activities including sample locations, sample collection, sample numbers, and shipping preparations. Deviations from the SAP (see Appendix B) were also recorded in the sample logbook.

6.1 Activity Specific Procedures

Specific activities were conducted in accordance with written procedures to maintain quality assurance and ensure that representative soil samples were collected and analytical data would not be compromised. Written procedures used to ensure that sample media and analytical results met quality requirements and were representative are listed below:

- *Environmental Monitoring Administration Manual* (see Section 9, "References")
 - EMSP 8.1, Identification and Control of Items
 - EMSP 13.1, Handling, Storing, and Shipping Samples
 - EMSP 15.1, Evaluation and Control of Data Originating from Environmental Sampling Efforts
 - EMSP 15.2, Validation and Assessment of Data Originating from Environmental Monitoring Sampling Efforts
- *Environmental Monitoring Special Request Handbook at the Idaho National Engineering Laboratory* (see Section 9, "References")
 - SOP-EM-SR 1.12, Decontamination Procedures
 - SOP-EM-SR 1.4, Collection of Samples Using a Dipper
 - SOP-EM-SR 1.6, Collection of Samples Using a Scoop and Spoon
 - SOP-EM-SR 1.7, Collection of Samples Using a Hand Auger.

6.2 Deviations from Sampling and Analysis Plan

There were few deviations from the SAP. The primary deviation concerned the scope of the sampling objective. Not all predetermined sampling locations were sampled. The respective changes included reducing the number of sample locations in two of the storm water retention basins (TAN 34-W-3-6 and TAN 34-W-3-7), and not being able to collect soil samples from intended sample intervals (SPERT 34-W-3-1).

6.3 Validation and Data Entry

The data package was submitted to the EG&G Idaho Engineering Department's Statistics and Reliability Engineering Data Group for data validation and preparation of the data for entering into the Environmental Restoration Information System (ERIS). The data were validated to method validation Level C, which includes a check of:

- Data package for completeness
- Chain of custody forms
- Requested versus reported analyses
- Holding times.

Procedures used for the data entry and automated method validation steps that were performed are described in the EG&G Idaho Data Applications Unit written operating procedures. Following completion of validation checks, the analytical results were entered into ERIS.

7. ANALYTICAL RESULTS

The sampling and analysis effort generated data that are summarized in tabular form in Appendices D, E, and F. The analytical results include inorganic, organic, and radiological data.

7.1 Metals

All soil samples were analyzed for RCRA total metals content. The laboratory reported that all samples were analyzed within the method-specific holding times, and that method blanks were free of contamination. All Interval Quality Control were within acceptance limits, except a matrix spike recovery for cadmium, arsenic, and lead that were slightly outside of acceptance limits. However, the analytical system was determined to be operating within control limits. See Appendix D for numerical results that are reported in mg/kg. Analytes of interest were as follows:

- Arsenic
- Barium
- Cadmium
- Chromium
- Lead
- Mercury
- Selenium
- Silver.

7.2 Volatiles

One soil sample was collected from each of the deep well storm water retention basins or drainage ditch based on a worse-case condition. The determination of which location to collect soil for VOA analysis was based on visual examination of the respective basins. Sampling sites that were determined to exhibit worse-case conditions included depressions or low points at the point of discharge to the basins where there appeared to be repeated and recent evidence of "standing water" or at an intersection of drainage ditches that routed storm water to the basins and exhibited evidence of "standing water." All samples spiked with either CLP 3/90 matrix spike compounds or TCLP analytes met analyte recovery and quality control criteria. See Appendix E for numerical results, which are reported in µg/l. Target compounds included the following:

- Benzene
- Chlorobenzene
- Carbon tetrachloride
- Chloroform
- 1,2-Dichloroethane
- 1,1-Dichloroethene
- Methyl ethyl ketone (2-butanone)
- Tetrachloroethene
- Trichloroethene
- Vinyl chloride.

7.3 Radiological Results

All soil samples were analyzed for radiological characteristics. Radiological analysis included gross alpha/beta and gamma spectrometry. Quality control data were within acceptance limits for radiological analyses. (See Appendix F for numerical results that are reported in pCi/g.) Radionuclides reported included:

- Alpha emitters
 - Radium-226
 - Uranium-235
- Gamma emitters
 - Actinium-228
 - Antimony-125
 - Bismuth-212
 - Bismuth-214
 - Cesium-137
 - Cobalt-60
 - Europium-155
 - Lead-210
 - Lead-212
 - Lead-214
 - Manganese-54
 - Potassium-40
 - Ruthenium-106
 - Thallium-208
 - Thorium-234.

In the laboratory, instrument signals must exceed a critical level before the qualitative decision can be made as to whether the radionuclide or radioactivity was detected. Concentrations that equal 1.6 s meet this criterion; at 1.6 s, there is about a 95% probability that the correct decision—not detected—will be made. Given a large number of samples, as many as 5% of the samples with measured concentrations greater than or equal to 1.6 s, which were concluded as being detected, might not contain the radioactive constituent. These measurements are referred to as false positives and are errors of the first kind in hypothesis testing.

Concentrations that equal 2 s represent a measurement at the minimum detectable concentration. For true concentrations of 2 s or greater, there is a 95% or greater probability of correctly concluding that the radioactive constituent was detected in a sample.

8. SUMMARY OF RESULTS

The deep injection well associated surface soils data were compared to surface soils data from the New Production Reactor (NPR) siting study (EG&G Idaho 1992) and to surface soils data from active nonwaste management EG&G Idaho facilities collected in September 1990.

8.1 Summary of Metals Analyses

Appendix D summarizes metals analyses results for surface soils collected from the deep injection well retention basins and ditches.

The majority of the target metals in the surface soil samples collected from the deep injection well retention basins and ditches were not detected or were below detection limits. The soil concentration data for detected metals were generally in the range of trace element content for natural soils compiled by the EPA in their guidance for solid waste disposal (see Appendix G, Table G-1). For elements with concentrations outside of the range listed in EPA's general guidance (e.g., cadmium), metal concentrations in deep injection well retention basin surface soil were found to be comparable to concentrations in soils at undisturbed locations in the vicinity of the INEL, as measured in an early, INEL soil survey (see Appendix G, Table G-2). Similarly, concentrations of detected metals in injection well retention basin soils were comparable to concentrations of metals in surface soils from the NPR site (see Appendix G, Table G-3). Sample TAN34W35006 was reported to have 0.39 mg/kg mercury, which is slightly above the reported concentration of 0.01–0.03 ppm for natural soils listed in EPA's general guidance. However, the concentration of mercury is within the background range (minimum 0.04 mg/kg, maximum 0.79 mg/kg) for soils at the INEL. Mercury was undetected in all other samples, including the other two samples taken from 6-in. intervals immediately above sample TAN34W35006.

8.2 Summary of Volatile Organic Analyses

Appendix E summarizes volatile organic analyses results for the surface soils collected from the deep injection well storm water retention basins and ditches. The results of the analyses indicated that concentrations for the reported target compounds were below detection limits.

8.3 Summary of Radiological Analyses Results

Appendix E summarizes radiological analyses results for the soils collected from the deep injection well storm water retention basins and ditches. A comparison of NPR and Radiological and Environmental Sciences Laboratory (RESL) radiological soil concentration measurements is presented in Appendix G, Table G-3. The NPR survey investigated an area of the site that was undeveloped and undisturbed by past human based activities. Soil concentration data for radioactive materials at the NPR site were comparable to background measurements from Site and regional reference locations. The RESL conducts an ongoing soil sampling program with the objective of assessing the potential buildup of activity from INEL operations. To date, there has been no indication of Site-related contamination at the RESL regional soil sampling locations—the RESL's data serve as a reference regional background database.

The beta/gamma-emitting radionuclide common to the NPR study and reported from this sampling effort was cesium-137. Cesium-137 is detected in area soils up to 1–1.5 pCi/g. This is above the concentrations found in deep injection well surface soils collected and analyzed for this study. Naturally occurring radionuclides reported in the storm water retention basin surface soils exhibited concentrations comparable to the regional background measurements and to previous measurements made in the region surrounding the INEL. Nonnaturally occurring radionuclides detected in the soils (antimony-125, cobalt-60, europium-155, manganese-54, and ruthenium-106) were identified in one or two random samples. Their presence is attributed to fallout residual or possible statistical error. All of the nonnaturally occurring radionuclides are detected in area soils within the ranges reported in analyses of the soil from the storm water retention basins and ditch. The concentrations reported were compared with data for natural background radiation levels in INEL soils as reported in *The Idaho National Engineering Laboratory Site Environmental Report for the Calendar Year 1990* (Hoff et al. 1992).

9. REFERENCES

EG&G Idaho, 1990, *Preliminary Assessment of Surface Soils at Active EG&G Idaho Facilities Data Document*, EGG-ESQ-9225, Revision 0, EG&G Idaho, Inc.

EG&G Idaho, 1992, *Summary Report: Preliminary Assessment of Surface Soils at the Proposed New Production Reactor (NPR) Site at the Idaho National Engineering Laboratory*, NPRD-92-024, Revision 0, EG&G Idaho, Inc.

EG&G Idaho, (not dated), *Environmental Monitoring Administration Manual*, Environmental Monitoring Unit, EG&G Idaho, Inc.

EG&G Idaho, (not dated), *Environmental Monitoring Special Request Handbook at the Idaho National Engineering Laboratory*, EGG-ESQ-9624, Environmental Monitoring Unit, EG&G Idaho, Inc.

EPA, 1983, *Hazardous Waste Land Treatment*, SW-874, Office of Solid Waste and Emergency Response, U.S. Environmental Protection Agency, Washington, DC, p. 273.

Hoff, D. L., et al., 1991, *The Idaho National Engineering Laboratory Site Environmental Report for Calendar Year 1990*, DOE/ID-12082(90), U.S. Department of Energy Idaho Field Office, June.

Appendix A

Quality Assurance Sampling and Analysis Plan for the INEL Injection Well Retention Basins

EG&G IDAHO INC. ENVIRONMENTAL MONITORING

QUALITY ASSURANCE SAMPLING AND ANALYSIS PLAN FOR INEL INJECTION WELL RETENTION BASINS No. EMS-142-90

Prepared by

**Jay Johnson
Environmental Monitoring
CFA-615, Mail Stop 4110
526-4815**

**Project Requester: C. M. Bennett
Charge Number:
Date of Request: 10-24-90**

S&A Plan EMS-142-90
05/12/92

REVIEWS

Date

Field Team Leader:

Steve Garcia
Steve Garcia

8-13-92

Sampling Operations:

Jay Johnson
Jay Johnson

8-13-92

Internal Reviewer:

Sam Pole
Sam Pole

8-14-92

Quality Assurance:

Laurie Peterson-Wright
Laurie Peterson-Wright

8/13/92

Safety:

Steve Key
Steve Key

8/14/92

APPROVAL

Requester:

C. M. Bennett
C. M. Bennett

per telephone authorization
8-14-92

1.0 Introduction

This sampling and analysis plan is for the sampling of retention basins and one drainage ditch associated with eight injection wells on the Idaho National Engineering Laboratory (INEL). The injection wells and their associated basins are ID numbers 34-W-3-1 through 34-W-3-8. Surface sediments will be collected and submitted for laboratory analysis to determine if they contain any Resource Conservation Recovery Act (RCRA) constituents above the regulatory limits. The following analysis will be required: total metals (RCRA) and, based on field data, Volatile Organic Analysis (VOA). Toxicity Characteristic Leaching Procedure (TCLP), EPA method 1311, will be used by the laboratory prior to conducting VOA. Radiological analysis (Gross alpha/beta and gamma spectrometry) will also be performed on each sample collected.

2.0 Project Organization and Responsibility

The following is a list of key project personnel and their corresponding responsibilities:

S&A Plan Preparation:	J. A. Johnson
Project Requester:	C. M. Bennett
Sampling Operations:	J. A. Johnson
Field Team Leader:	S. Garcia
Internal Review:	L. J. Peterson-Wright
Safety:	S. Key
Laboratory:	LAL

3.0 Project Description:

3.1 Sampling/Analysis Objective and Scope: The objective of this project is to provide technically representative sampling and analysis of the retention pond surface sediments to support permitting of the injection wells by the state of Idaho. This is in response to a letter from the state dated September 12, 1990 to Mr. Gerald C. Bowman.

- 3.1 Sampling/Analysis Objective and Scope (cont.): The sampling process is designed to address criteria for obtaining representative samples and maintaining sample quality and integrity, as well as safety considerations for field personnel. Full analytical quality control (QC) practices will be required to ensure that the data obtained are of defined data quality.
- 3.2 Data Usage: Samples collected in the project will be analyzed for Toxicity Characteristic Leaching Procedure (TCLP) VOA, total metals, and radiological considerations.

4.0 Health and Safety:

In order to provide for the health and safety of the sampling personnel, the sampling will be performed in close consultation with an Industrial Hygienist (IH) and a Health Physics tech. (HP).

- 4.1 Precautions and Safety for Sampling Personnel: Sampling personnel must be trained as per 29 CFR Part 1910.120 and must wear level D protection. Level D protection is comprised of latex gloves, and safety glasses or goggles. The sampling team will be accompanied by safety representatives. A briefing will be held Monday, August 17, 1992, at the CFA conference room prior to sampling to ensure that all sampling personnel have read and understand the sampling objectives. All personnel involved in the field sampling must attend the sample briefing. If there are any questions regarding the sampling activities, they must be resolved at this time.
- 4.2 Safety Considerations: Eating, drinking, smoking or chewing will not be permitted during the sampling activities. All team members will be required to wash their hands before any of the aforementioned activities are allowed. Any contact with potentially contaminated surfaces should be avoided whenever possible. Team members should avoid sitting, leaning, or placing equipment on areas that are potentially contaminated.

- 4.2 Safety Considerations (cont.): Sample collection operations will be stopped in the event of an accident or if the Team Leader or Safety representative feels conditions are unsafe.

The sampled material and all material associated with it (used sampling tools, wipes, etc.) must be handled as hazardous until the analytical results are evaluated by Environmental Monitoring (EM). Excess sample material not retained for analysis will be returned to the bore.

- 4.3 Radiological Considerations: Any radiological concerns for these sampling events will be addressed at the time the sampling occurs and will be listed on the safe work permits.

5.0 Sampling Strategy and Procedures:

Three soil samples will be collected from each of three borings in each of the seven ponds and one drainage ditch associated with the eight deep injection wells. Samples will be discrete samples collected from boring intervals; 0 to 6 inch, 6 to 12 inch, and 12 to 18 inch depth.

The sampling sites will be biased toward those locations which should provide the most accurate representation of potential contaminants.

Sampled will be collected at the point of discharge to the ponds, at the lowest point in each pond, and at the point of discharge from the ponds to the injection wells. Samples will also be collected from the drainage ditch that conveys water to the TAN 4 injection well. The samples will be collected at the entry point to the ditch, at the low point of the ditch, and at the point of discharge from the ditch to the well.

Soil sampling sites will be subject to change depending on site conditions and in consultation with the Idaho Department of Water Resources personal (IDWR).

5.0 Sampling Strategy and Procedures (cont.):

Samples will be collected from each six inch interval from the surface to a depth of eighteen inches. Samples will be collected using a hand auger as per SOP-EM-SR-1.7, Collection of Samples Using a Hand Auger, and SOP-EM-SR-1.6, Collection of Samples Using a Scoop & Spoon. Only one VOA sample will be collected from each of the basins at the "worst" location possible and at the lowest sampling depth using the auger to retrieve the sample from the auger hole using a stainless steel spoon to transfer the material into the sample container directly from the core barrel. Field analysis using a Photovac MicroTIP PID will be collected from each sampling location. If the PID gives an indication of volatiles, a volatile sample will be collected at that point also. A target concentration of 3 ppm will be used to determine if a VOA sample will be required. The material from each 6-inch interval will be mixed in a separate aluminum pan before being transferred to an appropriate sample container. Several cores may be required in order to obtain an adequate amount of soil. There will be a total of three samples collected at each sample location; 0 to 6 inch, 6 to 12 inch, and 12 to 18 inch. The sampling tool will be cleaned as per SOP-EM-SR-1.12, Decontaminating Sampling Equipment, or a new piece of equipment will be used for each location to be sampled.

Should water be present in any of the ponds or in the TAN drainage ditch during the sampling effort, a water sample will be collected for analysis. If water is in an area from which a soil sample is to be collected, the water sample will take the place of the soil sample. Water samples will be collected using a dipper as per SOP-EM-SR-1.4, Collection of Samples Using a Dipper, and will be analyzed for the same constituents as the soil samples. Samples may be split with the IDWR personnel at their discretion during collection. All samples will be listed on a chain of custody as per EMSP 8.1, Identification and Control of Items. The samples will be surveyed by the Health Physics (HP) prior to the samples being taken from the sample site.

- 5.0 Sampling Strategy and Procedures (cont.): After the sampled materials have been released by the HP, the samples will be sent under full chain of custody to a contract laboratory for analysis according to EMSP 13.1, Handling, Storing, and Shipping. Proper custody of the samples will be maintained at all times.

Any deviations from this sampling plan must be noted in the field logbook.

- 5.1 Decontamination: To prevent cross-contamination, all sampling equipment that comes in contact with the sample must be cleaned as per Environmental Monitoring SOP-EM-SR-1.12, Decontamination Procedures.

- 5.2 Sampling Materials: The following is a list of equipment that will be needed during the sampling of each basin:

- a) (3) 40 ml glass vials for each TCLP VOA (water)
- b) (1) 125 ml glass container for each TCLP VOA (soil)
- c) (1) 500 ml glass container for each metals (soil)
- d) (1) 500 ml glass containers for each metals (water)
- e) (1) 500 ml squat jar for each gross Alpha/Beta and Gamma (soil)
- f) (1) 540 ml LDPE container for each gross Alpha/Beta and Gamma (water)
- g) Plastic wrap or bags
- h) Teriwipes or Kimwipes
- i) Parafilm and scissors

5.2 Sampling Materials (cont.):

- j) Level D Personal Protective Equipment (PPE)
- k) Cooler with blue ice
- l) Field logbook
- m) Sample labels
- n) Chain-of-Custody Forms and Seals
- o) Latex gloves
- p) Aluminum mixing pans
- q) Scoops and/or spoons (stainless steel)
- r) Stainless steel auger and bits

5.3 Prerequisites: All team members will familiarize themselves with all reference material that pertains to the sampling task before the actual field work begins.

All equipment will be prepared and will be in proper working order before proceeding to the sampling site. The sample containers will be inspected to ensure their integrity (ie. no cracks, no missing liners etc.)

6.0 Sample Analysis and Quality Control:

6.1 Analytical Procedure: All samples collected from the retention basins shall be prepared and analyzed according to the guidelines set forth in USEPA SW-846 using the TCLP extraction method 1311 followed by method 8240 for VOA, 8270 for semi VOA, and 6010 for metals (method 7470 for mercury).

- 6.1 **Analytical Procedure (cont.):** It is imperative that the designated laboratory perform the analysis using these techniques to ensure quality, precision, accuracy, and correctness of the data. If this method is not used, the laboratory must inform EG&G by telephone, then an alternate, EPA approved method, will be used.

Analytical Methods

Parameter	Prep Method	Analysis Method
Total RCRA Metals (mercury)	3050	6010
	3050	7470
TCLP VOA	1311	8240

- 6.2 **Data Completeness:** Data must be reported for all samples collected and submitted for analysis.
- 6.3 **Data Representativeness:** All sample collection, handling, and selected analytical protocols have been chosen so the results will be as representative as possible of the media and conditions being measured.
- 6.4 **Data Quality Control:** The sampling teams and laboratory's quality control programs will be set up to meet the requirements stated in SW-846. USEPA analytical level III is required.

Sensitivity and Blanks

Parameter	Sensitivity	Method Blank
Total RCRA Metals (mercury)	PQL by ICP	< PQL
	PQL by cold vapor	< PQL
TCLP VOA	PQL GC/MS	< PQL

7.0 Documentation:

- 7.1 Sample Security: All samples must be labeled and be provided handling and custody procedures as necessary to ensure the project objectives are met.
- 7.2 Field Records: All field activities must be recorded in indelible ink in the appropriate field logbook.
- 7.3 Corrective Action: Corrective actions are required whenever established control limits for an analysis are exceeded. Documentation of such corrective action is required and will be addressed in the final report.

8.0 Data Reduction and Validation:

Initial data evaluation and data quality review will be performed by the subcontract laboratory. Final data validation and evaluation will be performed by EG&G as directed in EMSP 15.1, Evaluation and Control of Data Originating From Environmental Sampling Efforts, and EMSP 15.2, Validation and Assessment of Data Originating from Environmental Monitoring Sampling Efforts.

9.0 Data Reporting:

All analytical results and QC measurements for each sample analyzed will be required within a reasonable time period after receipt of the samples by the laboratory. Data should be forwarded to EG&G for review and a letter report will be issued upon completion of the data evaluation to the requester, Mr. C. M. Bennett.

REFERENCES

1. Environmental Monitoring Administration Manual, Environmental Monitoring Unit, EG&G, Idaho, Inc.

 EMSP 8.1, Identification and Control of Items.
 EMSP 13.1, Handling, Storing, and Shipping Samples.
 EMSP 15.1, Evaluation and Control of Data Originating From Environmental Sampling Efforts.
 EMSP 15.2, Validation and Assessment of Data Originating From Environmental Monitoring Sampling Efforts.
2. Environmental Monitoring Special Request Handbook at the Idaho National Engineering Laboratory, EGG-ESQ-9624, Environmental Monitoring Unit, EG&G, Idaho, Inc.

 SOP-EM-SR 1.12, Decontamination Procedures.
 SOP-EM-SR 1.4, Collection of Samples Using a Dipper.
 SOP-EM-SR 1.6, Collection of Samples Using a Scoop & Spoon
 SOP-EM-SR 1.7, Collection of Samples Using a Hand Auger
3. EPA, 40 CFR Part 261.
4. OSHA, 29 CFR 1910.120.
5. USEPA SW-846, Test Methods for Evaluating Solid Waste, third edition, U.S. Environmental Protection Agency, November 1986.

Appendix B

Field Log Notes

DATE: 8-17-92

SAMPLERS: GARCIA, Johnson

LOCATION: INEL Retention Basins

REGISTER: SAM POLE

Site #4 - CFA BASIN - F34-W-3-4

NOT TO SCALE

Continued on Page 46

[Signature]
Signed

8-17-92

Date

Read and Understood By

[Signature]
Signed

8-17-92

Date

PROJECT _____

EMS-142-90

Continued From Page 45

Project: INSE RETENTION BASINS

Samples: LARVAE, CHYTRON

DATE: 8-17-92

(Site #4)

SAMPLE ID	TIME	ANALYSIS	CONTAINER	Lat	Depth	Preser
CFA34-W-3-4-001	0945	GROSS Alpha/BETA, GAMMA	500 ML LDPE	N/A	0-6"	N/A
CFA34-W-3-4-001	0945	TOTAL METALS (RCRA)	500 ML HDPE	211-0500	0-6"	4°C
CFA34-W-3-4-002	0955	GROSS Alpha/BETA, GAMMA	500 ML LDPE	N/A	6-12"	N/A
CFA34-W-3-4-002	0955	TOTAL METALS (RCRA)	500 ML HDPE	211-0500	6-12"	4°C
CFA34-W-3-4-003	1007	GROSS Alpha/BETA, GAMMA	500 ML LDPE	N/A	12-18"	N/A
CFA34-W-3-4-003	1007	TOTAL METALS (RCRA)	500 ML HDPE	211-0500	12-18"	4°C
CFA34-W-3-4-007	1020	GROSS Alpha/BETA, GAMMA	500 ML LDPE	N/A	0-6"	N/A
CFA34-W-3-4-007	1020	TOTAL METALS (RCRA)	500 ML HDPE	211-0500	0-6"	4°C
CFA34-W-3-4-008	1030	GROSS Alpha/BETA, GAMMA	500 ML LDPE	N/A	6-12"	N/A
CFA34-W-3-4-008	1030	TOTAL METALS (RCRA)	500 ML HDPE	211-0500	6-12"	4°C
CFA34-W-3-4-009	1040	GROSS Alpha/BETA, GAMMA	500 ML LDPE	N/A	12-18"	N/A
CFA34-W-3-4-009	1040	TOTAL METALS (RCRA)	500 ML HDPE	211-0500	12-18"	4°C
CFA34-W-3-4-009	1040	VOA	125 ML Q/MS	020720D	18"	4°C
CFA34-W-3-4-004	1055	GROSS Alpha/BETA, GAMMA	500 ML LDPE	N/A	0-6"	N/A
CFA34-W-3-4-004	1055	TOTAL METALS (RCRA)	500 ML HDPE	211-0500	0-6"	4°C
CFA34-W-3-4-005	1107	GROSS Alpha/BETA, GAMMA	500 ML LDPE	N/A	6-12"	N/A
CFA34-W-3-4-005	1107	TOTAL METALS (RCRA)	500 ML HDPE	211-0500	6-12"	4°C
CFA34-W-3-4-006	1122	GROSS Alpha/BETA, GAMMA	500 ML LDPE	N/A	12-18"	N/A
CFA34-W-3-4-006	1122	TOTAL METALS (RCRA)	500 ML HDPE	211-0500	12-18"	4°C

SAMPLES WERE COLLECTED WITH THE STAINLESS STEEL AUGER COLLECTING SAMPLES TO 0-6", 6-12", AND 12-18". SAMPLE LOCATIONS WERE SELECTED BY S. POLE. SAMPLE LOCATIONS WERE MARKED AS #1-2-3, #4-5-6, #7-8-9. EACH # REPRESENTS A DEPTH - #1-2-3 = #1(0-6") #2-(6"-12") #3-(12"-18"). SAMPLE LOCATIONS WERE MOVED FROM THE FIRST SELECTED LOCATIONS. THE VOA SAMPLE WAS TAKEN FROM LOCATION #009. ALL SAMPLES WERE COMPOSITED INTO A STAINLESS STEEL PAN PRIOR TO THE MATERIAL BEING PLACED IN THE SAMPLE CONTAINER. ALL CONTAINERS WERE LABELED AND PLACED IN A COOLER WITH BLUE ICE.

8/92

Continued on Page 47

Signed

8-17-92

Date

Signed

8-17-92

Date

PROJECT: INEL RETENTION BASINS
DATE: 8-17-92

SITE #1 - SPECT24-W-3-1

Continued on Page 48

[Signature]
Signed

8-17-92

Date

Read and Understood By

[Signature]
Signed

8-17-92

Date

Project: Inlet Retention Basin

Samples: Garcia, Johnson

DATE: 8-17-92

(Site #1)

Sample ID	TIME	ANALYSIS	Container	LOT#	Depth	Per
SPEET 34-W-3-1-001	1405	GROSS Alpha/Beta, Gamma	500 ml LDPE	N/A	0-6"	N/A
" "	1405	TOTAL Metals (PCRA)	500 ml HDPE	0100043	0-6"	4°C
SPEET 34-W-3-1-002	1415	GROSS Alpha/Beta, Gamma	500 ml LDPE	N/A	6-12"	N/A
" "	1415	TOTAL Metals (PCRA)	500 ml HDPE	0100043	6-12"	4°C
SPEET 34-W-3-1-003	1422	GROSS Alpha/Beta, Gamma	500 ml LDPE	N/A ³ 0100043	12-18"	N/A
" "	1422	TOTAL Metals (PCRA)	500 ml HDPE	0100043	12-18"	4°C
SPEET 34-W-3-1-004	1440	GROSS Alpha/Beta, Gamma	500 ml LDPE	N/A ³ 0100043	0-6"	N/A
" "	1440	TOTAL Metals (PCRA)	500 ml HDPE	0100043	0-6"	4°C
SPEET 34-W-3-1-005	1445	GROSS Alpha/Beta, Gamma	500 ml LDPE	N/A	6-12"	N/A
SPEET 34-W-3-1-005	1445	TOTAL Metals (PCRA)	500 ml HDPE	0100043	6-12"	4°C
SPEET 34-W-3-1-006	1451	GROSS Alpha/Beta, Gamma	500 ml LDPE	N/A	12-18"	N/A
" ³⁴ "	1451	TOTAL Metals (PCRA)	500 ml HDPE	0100043	12-18"	4°C
SPEET 34 -W-3-1-006	1452	VDA	125 ml glass	D2072010	18"	4°C
SPEET 34-W-3-1-007	1500	GROSS Alpha/Beta, Gamma	500 ml LDPE	N/A	0-6"	N/A
" "	1500	TOTAL Metals (PCRA)	500 ml HDPE	0100043	0-6"	4°C
SPEET 34-W-3-1-008	1510	GROSS Alpha/Beta, Gamma	500 ml LDPE	N/A	6-12"	N/A
" "	1510	TOTAL Metals (PCRA)	500 ml HDPE	0100043	6-12"	4°C
SPEET 34-W-3-1-009	1510	GROSS Alpha/Beta, Gamma	500 ml LDPE	N/A	12-18"	N/A
" "	1510	TOTAL Metals (PCRA)	500 ml HDPE	0100043	12-18"	4°C

Samples were collected using a Stainless Steel Auger. A separate head was used for each location. Samples 1-2-3 (1 = 0-6", 2 = 6-12", 3 = 12-18") was taken in the drainage ditch near the power poles. Samples 4-5-6 and 7-8-9 were taken in the low areas of the basin (See Map, Page 47). Sample #9 was not collected because of large rocks at approx. 12"-18" in the auger hole. The VDA sample was taken at 18" from Location #6. All samples were labeled and parafilm'd at the time of collection and placed into a cooler with blue ice. All sample augers were decontaminated prior to moving to a new site.

8/92

Continued on Page 49

Read and Understood By

Signed

8-17-92

Date

Signed

8-17-92

Date

Project: INEL Retention Basin

DATE: 8-17-92

Site #2 - SPERT34-W-3-2-

* Sample Location

Continued on Page 50

Signed

8-17-92

Date

Read and Understood By

Signed

8-17-92

Date

PROJECT

EMS-142-92

Continued From Page

49

PROJECT: INEL Retention Basin

Samples: Garcia, Johnson

DATE: 8-17-92

(Site #2)

SAMPLE ID	TIME	ANALYSIS	Container	Lot#	Depth
SPERT 34-W-3-2-001	1545	Gross Alpha/Beta, Gamma	500 ml LDPE	N/A	0-6" A
"	"	TOTAL Metals (RCRA)	500 ml HDPE	0100043	0-6" 4
SPERT 34-W-3-2-002	1550	Gross Alpha/Beta, Gamma	500 ml LDPE	N/A	6-12" A
"	"	TOTAL Metals (RCRA)	500 ml HDPE	0100043	6-12" 4
SPERT 34-W-3-2-003	1555	Gross Alpha/Beta, Gamma	500 ml LDPE	N/A	12"-18" N
"	"	TOTAL Metals (RCRA)	500 ml HDPE	0100043	12"-18" 4
SPERT 34-W-3-2-004	1605	Gross Alpha/Beta, Gamma	500 ml LDPE	N/A	0-6" N
"	"	TOTAL Metals (RCRA)	500 ml HDPE	0100043	0-6" 4
SPERT 34-W-3-2-003	1600	VDA	125 ml GLASS	D2072010	18" 4
SPERT 34-W-3-2-005	1610	Gross Alpha/Beta, Gamma	500 ml LDPE	NA	6-12" N
"	"	TOTAL Metals (RCRA)	500 ml HDPE	0100043	6-12" 4
SPERT 34-W-3-2-006	1615	Gross Alpha/Beta, Gamma	500 ml LDPE	NA	12"-18" A
"	"	TOTAL Metals (RCRA)	500 ml HDPE	0100043	12"-18" 4
SPERT 34-W-3-2-006	1616	VDA	125 ml GLASS	D2072010	18" 4
SPERT 34-W-3-2-007	1622	Gross Alpha/Beta, Gamma	500 ml LDPE	NA	0-6" N
"	"	TOTAL Metals (RCRA)	500 ml HDPE	0100043	0-6" 4
SPERT 34-W-3-2-008	1630	Gross Alpha/Beta, Gamma	500 ml LDPE	NA	6-12" A
"	"	TOTAL Metals (RCRA)	500 ml HDPE	0100043	6-12" 4
SPERT 34-W-3-2-009	1637	Gross Alpha/Beta, Gamma	500 ml LDPE	NA	12"-18" A
"	"	TOTAL Metals (RCRA)	500 ml HDPE	0100043	12"-18" 4

All Samples were collected as previous Basins. TWO VDA Samples were collected ONE AT 003 and ONE AT 006.

JJ
8/92

Continued on Page 51

Signed

8-17-92
Date

Read and Understood By

Signed

8-17-92
Date

Project: INEL RETENTION BASIN

Samples: Garcia, Johnson

DATE: 8-17-92

(Site #3)

SAMPLE ID	TIME	ANALYSIS	Container	LOT	Depth	PRO
IPERT34-W-3-3-001	1715	GROSS Alpha/Beta, Gamma	500 ml LDPE	NA	0-6"	NA
"	1715	TOTAL Metals (RCRA)	500 ml HDPE	0100043	0-6"	4°C
IPERT34-W-3-3-002	1717	GROSS Alpha/Beta, Gamma	500 ml LDPE	NA	6"-12"	NA
"	1717	TOTAL Metals (RCRA)	500 ml HDPE	0100043	6"-12"	4°C
IPERT34-W-3-3-003	1722	GROSS Alpha/Beta, Gamma	500 ml LDPE	NA	12"-18"	NA
"	1722	TOTAL Metals (RCRA)	500 ml HDPE	0100043	12"-18"	4°C
"	1725	VOA	125 ml glass	D2072010	18"	4°C
IPERT34-W-3-3-004	1732	GROSS Alpha/Beta, Gamma	500 ml LDPE	NA	0-6"	NA
"	1732	TOTAL Metals (RCRA)	500 ml HDPE	0100043	0-6"	4°C
IPERT34-W-3-3-005	1737	GROSS Alpha/Beta, Gamma	500 ml LDPE	NA	6"-12"	NA
"	1737	TOTAL Metals (RCRA)	500 ml HDPE	0100043	6"-12"	4°C
IPERT34-W-3-3-006	1741	GROSS Alpha/Beta, Gamma	500 ml LDPE	NA	12"-18"	NA
"	1741	TOTAL Metals (RCRA)	500 ml HDPE	0100043	12"-18"	4°C
IPERT34-W-3-3-007	1750	GROSS Alpha/Beta, Gamma	500 ml LDPE	NA	0-6"	NA
"	1750	TOTAL Metals (RCRA)	500 ml HDPE	0100043	0-6"	4°C
IPERT34-W-3-3-008	1755	GROSS Alpha/Beta, Gamma	500 ml LDPE	NA	6"-12"	NA
"	1755	TOTAL Metals (RCRA)	500 ml HDPE	0100043	6"-12"	4°C
IPERT34-W-3-3-009	1800	GROSS Alpha/Beta, Gamma	500 ml LDPE	NA	12"-18"	NA
"	1800	TOTAL Metals (RCRA)	500 ml HDPE	0100043	12"-18"	4°C

THE BASIN WAS LOCATED APPROXIMATELY 281 FEET FROM THE DAVED ROAD.
 Sample locations were selected by S. POLE. Samples were collected
 as in previous locations. The VOA was taken at #003 at 18"

JMY

8/92

Continued on Page 52

Read and Understood By

Steve Garcia

8-17-92

Signed

Date

Signed

Date

Project: INEL Retention Basins

DATE: 8-17-92

Site #3 - SPERT34-W-3-3

* SAMPLE LOCATION

Outlet (281' From Outlet to Road (Jefferson))

WELL

*
#7-8-9*
#4-5-6*
#1-2-3

NOT TO SCALE

Continued on Page 53

[Signature]
Signed

8-17-92

Date

Read and Understood By

[Signature]
Signed

8-17-92

Date

Retention
Project: INEL ~~Basins~~ Basins Samplers: Garcia, Johnson
Date: 8-18-92

(Site #5)

SAMPLE ID	TIME	Analysis	Container	Lot #	Depth	Pres.
TAN34-W-3-S-001	0925	GROSS Alpha/Beta, Gamma	500 ml LDPE	NA	0-6"	N/A
"	0925	TOTAL Metals (RCRA)	500 ml HDPE	211-0600	0-6"	4°C
TAN34-W-3-S-002	0930	GROSS Alpha/Beta, Gamma	500 ml LDPE	NA	6"-12"	NA
"	0930	TOTAL Metals (RCRA)	500 ml HDPE	0100043	6"-12"	4°C
TAN34-W-3-S-003	0940	GROSS Alpha/Beta, Gamma	500 ML LDPE	NA	12"-18"	NA
"	0940	TOTAL Metals (RCRA)	500 ML HDPE	0100043	12"-18"	4°C
TAN34-W-3-S-004	0955	GROSS Alpha/Beta, Gamma	500 ML LDPE	NA	0-6"	NA
"	0955	TOTAL METAL (RCRA)	500 ML HDPE	0100043	0-6"	4°C
TAN34-W-3-S-005	1000	GROSS Alpha/Beta, Gamma	500 ML LDPE	NA	6"-12"	NA
"	1000	TOTAL Metals (RCRA)	500 ML HDPE	0100043	6"-12"	4°C
TAN34-W-3-S-006	1005	GROSS Alpha/Beta, Gamma	500 ML LDPE	NA	12"-18"	NA
"	1005	TOTAL Metals (RCRA)	500 ML HDPE	0100043	12"-18"	4°C
TAN34-W-3-S-007	1020	GROSS Alpha/Beta, Gamma	500 ML LDPE	NA	0-6"	NA
"	1020	TOTAL METALS (RCRA)	500 ML HDPE	0100043	0-6"	4°C
TAN34-W-3-S-008	1026	GROSS Alpha/Beta, Gamma	500 ML LDPE	NA	6"-12"	NA
"	1026	TOTAL METALS (RCRA)	500 ML HDPE	0100043	6"-12"	4°C
TAN34-W-3-S-009	1035	GROSS Alpha/Beta, Gamma	500 ML LDPE	NA	12"-18"	NA
"	1035	TOTAL METALS (RCRA)	500 ML HDPE	0100043	12"-18"	4°C
TAN34-W-3-S-009	1038	VOA	125 ML GLASS	D2072010	18"	4°C

Sample locations were selected by S. POYE. Samples were again collected as in previous Basins. The VOA Sample was collected at #009

JAY

8/92

Continued on Page

54

Read and Understood By

Signed

Date

Signed

Date

Project: INEL RETENTION BASINS

DATE: 8-18-92

Site #5 - TAN34-WI-3-5

Continued on Page 55

Signed

Date

B-12

Read and Understood By

Signed

Date

Project: INEL Retention Basin

Samplers: Garcia, Johnson

DATE: 8-18-92

(SITE #8)

SAMPLE ID	TIME	ANALYSIS	CONTAINER	LOT #	Depth	Pres
N34-W-3-8-001	11:05	Gross Alpha/Beta, Gamma	500 ML HDPE	NA	0-6"	NA
"	11:05	TOTAL METALS (PCRA)	500 ML HDPE	0100043	0-6"	4%
N34-W-3-8-002	11:10	Gross Alpha/Beta, Gamma	500 ML HDPE	NA	6"-12"	NA
"	11:10	TOTAL METALS (PCRA)	500 ML HDPE	0100043	6"-12"	4%
N34-W-3-8-003	11:16	Gross Alpha/Beta, Gamma	500 ML HDPE	NA	12"-18"	NA
"	11:16	TOTAL METALS (PCRA)	500 ML HDPE	0100043	12"-18"	4%
N34-W-3-8-003	11:20	VDA	125 ML GLASS	D2072010	18"	4%
N34-W-3-8-004	11:35	Gross Alpha/Beta, Gamma	500 ML HDPE	NA	0-6"	NA
"	11:35	TOTAL METALS (PCRA)	500 ML HDPE	0100043	0-6"	4%
N34-W-3-8-005	11:42	Gross Alpha/Beta, Gamma	500 ML HDPE	NA	6"-12"	NA
"	11:42	TOTAL METALS (PCRA)	500 ML HDPE	0100043	6"-12"	4%
N34-W-3-8-006	11:50	Gross Alpha/Beta, Gamma	500 ML HDPE	NA	12"-18"	NA
"	11:50	TOTAL METALS (PCRA)	500 ML HDPE	211-0500	12"-18"	4%
N34-W-3-8-007	12:05	Gross Alpha/Beta, Gamma	500 ML HDPE	NA	0-6"	NA
"	12:05	TOTAL METALS (PCRA)	500 ML HDPE	211-0500	0-6"	4%
N34-W-3-8-008	12:12	Gross Alpha/Beta, Gamma	500 ML HDPE	NA	6"-12"	NA
"	12:12	TOTAL METALS (PCRA)	500 ML HDPE	211-0500	6"-12"	4%
N34-W-3-8-009	12:18	Gross Alpha/Beta, Gamma	500 ML HDPE	NA	12"-18"	NA
"	12:18	TOTAL METALS (PCRA)	500 ML HDPE	211-0500	12"-18"	4%

THIS LOCATION IS A DRAINAGE DITCH ONLY. THE MATERIAL FROM THIS AREA DRAINS DIRECTLY INTO THE WGH. ALL SAMPLE LOCATIONS WERE SELECTED BY S. POLE AND WERE COLLECTED USING THE SAMPLE METHODS AS THE SAMPLES COLLECTED IN THE BASINS. THE VDA WAS COLLECTED AT LOCATION # 003.

JAY

8/18/92

Continued on Page 56

Read and Understood By

[Signature]

8-18-92

Signed

Date

Signed

Date

PROJECT EMS-142-90

Project: INEL Retention Basin

DATE: 8-18-92

SITE #8 - TAN34-W-3-8

Continued on Page 57

[Signature]
Signed

8-18-92
Date

Read and Understood By
[Signature]
Signed

8-18-92
Date

Project: INEL Retention Basin

SAMPLERS: Johnson, Garcia

DATE: 8-18-92

(Site #6)

Sample ID	TIME	Analysis	Container	LPT#	Depth	Pres.
TAN34-W-3-6-001	1405	Gross Alpha/Beta, Gamma	500 ml LDPE	NA	0-6"	N/A
"	1405	TOTAL Metals (RCRA)	500 ml HDPE	0100043	0-6"	4°C
TAN34-W-3-6-002	1410	Gross Alpha/Beta, Gamma	500 ml LDPE	NA	6"-12"	N/A
"	1410	TOTAL Metals (RCRA)	500 ml HDPE	0100043	6"-12"	4°C
TAN34-W-3-6-003	1415	Gross Alpha/Beta, Gamma	500 ml LDPE	NA	12"-18"	N/A
"	1415	TOTAL Metals (RCRA)	500 ml HDPE	0100043	12"-18"	4°C
TAN34-W-3-6-003	1417	VOA	125 ml glass	D2072010	18"	4°C
TAN34-W-3-6-004	1422	Gross Alpha/Beta, Gamma	500 ml LDPE	NA	0-6"	N/A
"	1422	TOTAL Metals (RCRA)	500 ml HDPE	0100043	0-6"	4°C
TAN34-W-3-6-005	1430	Gross Alpha/Beta, Gamma	500 ml LDPE	NA	6"-12"	N/A
"	1430	TOTAL Metals (RCRA)	500 ml HDPE	0100043	6"-12"	4°C
TAN34-W-3-6-006	1435	Gross Alpha/Beta, Gamma	500 ml LDPE	NA	12"-18"	N/A
"	1435	TOTAL Metals (RCRA)	500 ml glass	E2144010	12"-18"	4°C

The location of this Basin is on the inside of the TAN (Fenced in) Area North West of the Sewer treatment plant. Sample locations were selected by S. Pole. Mr. Pole decided to collect samples at 2 locations instead of three. Samples were collected using the hand Auger as in the previous Basins. The VOA was taken at Location #3.

JAG

8/92

Continued on Page

Signed

8-18-92

Date

Read and Understood

Signed

8-18-92

Date

Project: INEL Retention Basin

DATE: 8-18-92

SITE #6 - TAN34-W-3-6

TAN
653

[Signature]

8-18-92

[Signature]
8-14-92

8/92 JJ

Project: INEL Retention Basin

DATE: 8-18-92

(Site #7)

Sample ID	TIME	ANALYSIS	Container	Lot #	Depth	Re
TAN34-W-3-7-001	1521	Gross Alpha/Beta, Gamma	500 ml LDPE	NA	0-6"	NA
" "	1521	TOTAL Metals (PCRA)	500 ml GLASS	E2144010	0-6"	4%
TAN34-W-3-7-002	1525	Gross Alpha/Beta, Gamma	500 ml LDPE	NA	6-12"	NA
" "	1525	TOTAL Metals (PCRA)	500 ml GLASS	E2144010	6-12"	4%
TAN34-W-3-7-003	1530	Gross Alpha/Beta, Gamma	500 ml LDPE	NA	12"-18"	NA
" "	1530	TOTAL Metals (PCRA)	500 ml GLASS	E2144010	12"-18"	4%
TAN34-W-3-7-003	1533	VOA	125 ml GLASS	D207010	18"	4%
TAN34-W-3-7-004	1537	Gross Alpha/Beta, Gamma	500 ml LDPE	NA	0-6"	NA
" "	1537	TOTAL Metals (PCRA)	500 ml GLASS	E2144010	0-6"	4%
TAN34-W-3-7-005	1542	Gross Alpha/Beta, Gamma	500 ml LDPE	NA	6-12"	NA
" "	1542	TOTAL Metals (PCRA)	500 ml GLASS	E2144010	6-12"	4%
TAN34-W-3-7-006	1547	Gross Alpha/Beta, Gamma	500 ml LDPE	NA	12"-18"	NA
" "	1547	TOTAL Metals (PCRA)	500 ml GLASS	E2144010	12"-18"	4%

THIS BASIN ^{W/IN} IS LOCATED Southeast of the LOFT AREA (Approx 1/4 MI).
 ACCESS to this Area is OBTAINED through a Security Gate (Gate #2).
 A Security Guard was called to open the Gate. Sample locations
 were located by S. Pole. Again only two Sample locations were selected.
 Samples were collected as in the other Basins. The VOA was taken
 from #3.

JAY

8/92

Continued on Page 61.

Signed

8-18-92

Date

Read and Understood By

Signed

8-18-92

Date

QUEST EMS-142-90

10/28/92 11

31

Continued from Page 60

Project: JMEL RETENTION BASIN

DATE: 8-18-92

Site # 7-TAN34-W-3-7

* - Sample location.

NOT TO SCALE

OFF PAVED ROAD

Continued on Page

FHP

[Signature]
Signed

8-18-92
Date

(Read and Understood By)
[Signature]
Signed

8-13-92
Date

UIC SAMPLING

CALIBRATION 55ppm ISOBUTYLENE

8/17/92 Event #232 - CALIBRATION / 2.220 / SAGE / SHARPEN PEN SOURCE CHECK

→ 233 - BOTTOM OF 6" HOLE / BAG SAMPLE = 0 ppm

CFA34-W-3-4-001 234 - 2nd hole 0-6" at 001 location

235 - @ 18" DEEP - 0 ppm from bottom of hole

CFA34-W-3-4-007 → 236 - @ 6" at 12" from hole bottom and 6" baggie sample = 0 ppm

237 - @ 18" from 007 (low spot) = 0 ppm in baggie sample

Note: Temperature inside baggie measured at 85°F

CFA34-W-3-4-004 → 238 - @ 6" from hole bottom = 0 ppm

239 @ 12" from surface in baggie = 0 ppm

240 @ 18" deep inside hole and baggie sample = 0 ppm

241 - SPERT - SOURCE CHECK ON sage brush (60 ppm) flower, then creosote on power line pole (2.0 ppm), and old macadam in baggie = 5 ppm

→ 242 - 12" deep baggie sample = 1.2 ppm

SPERT34-W-3-1-001 243 - 0 ppm in 005, 6" deep bottom of hole

005 244 - 0 ppm in 18" deep baggie sample

008 245 - 0 ppm at 12-18" CALICHE LAYER BAGGIE SAMPLE

246 - WELL OUTLET FOR SPERT34W-3-1- , OUTLET AIR TEMP = 65°F = 0 ppm

247 - WELL OUTLET FOR SPERT34W-3-2- , = 0 ppm

SPERT34-W-3-2-003 248 - 12-18" - 12' and 15" baggie readings from 1.5 to 5 ppm

249 - 18" , 0 ppm with 12" baggies sample showing on 0.5 ppm outlier.

3-2-008 250 - closest to well 0 ppm @ 12"

009 251 - 18" 0 ppm

138 ft E of
pole #12 for 003
17 ft for 003
70 ft for 003
3-2 well inlet
25

SPERT34-W-3-3-001 Event 253 - 5 ppm / 14 ppm @ 12 + 18" from intersection of ditches

002 254 0 ppm in hole @ 12", baggies = 0 ppm also for 18"

255 2.5 ppm in 18" repeat measurement on baggie

003 256 0 ppm in baggie from 12"

000 0 ppm in baggie from 18"

Event 001 POST CALIBRATION CHECK 55 ppm ISOBUTYLENE 75.0 ppm

Appendix C

Chain of Custody Forms

ENVIRONMENTAL MONITORING CHAIN OF CUSTODY FORM

2043

[illegible]

DISTRIBUTION: Original and Pink copies accompany sample shipment to laboratory. Original copy retained by customer. Pink copy retained by laboratory. Yellow copy retained by sample.

EG&G Idaho, Inc.
P.O. Box 1625 MS 4110
Idaho Falls, Idaho
(208) 526-8075 (208) 526-9535
Environmental Monitoring TeamENVIRONMENTAL MONITORING
CHAIN OF CUSTODY FORM

2048

SAMPLER: (Signature)		PROJECT NAME: EMS-142-90				PARAMETERS					
SAMPLE NO.		SAMPLING DATE	SAMPLING TIME	COMP.	GRAB	SAMPLING LOCATION	NO. OF CONTAINERS	TOTAL METALS (PRA)	TOTAL VOA (only)	GROSS ALPHA/BETA	GAMMA SPEC
FIELD	LAB										
SPRT 34-W-3-3-001		8/16/92	1716	X		SPRT	2	X	X	X	X
SPRT 34-W-3-3-002			1717	X			2	X	X	X	X
SPRT 34-W-3-3-003			1722	X			2	X	X	X	X
SPRT 34-W-3-3-003			1725		X		1	X		X	
SPRT 34-W-3-3-004			1732	X			2	X	X	X	X
SPRT 34-W-3-3-005			1737	X			2	X	X	X	X
SPRT 34-W-3-3-006			1741	X			2	X	X	X	X
SPRT 34-W-3-3-007			1750	X			2	X	X	X	X
SPRT 34-W-3-3-008			1755	X			2	X	X	X	X
SPRT 34-W-3-3-009			1800	X			2	X	X	X	X
C92-170053-014											
Relinquished by: (Signature)		Date/Time		Received by: (Signature)		Relinquished by: (Signature)		Date/Time		Received by: (Signature)	
J. W. Duncanson		8/21/92 1113									
Relinquished by: (Signature)		Date/Time		Received by: (Signature)		Relinquished by: (Signature)		Date/Time		Received by: (Signature)	
J. W. Duncanson		8/24/92 1000									

EG&G Idaho, Inc.

**P.O. Box 1625 MS 4110
Idaho Falls, Idaho
(208) 526-8075 (208) 526-9535
Environmental Monitoring Team**

ENVIRONMENTAL MONITORING CHAIN OF CUSTODY FORM

2045

SAMPLER: (Signature)		PROJECT NAME: EMS-142-92					
SAMPLE NO.		SAMPLE DATE	SAMPLING TIME	COMP.	GRAB	SAMPLING LOCATION	
FIELD	LAB						
CFA34-W-3-4-001		8/21/92	0945	X		SPEPT	
CFA34-W-3-4-002			0955	X			
CFA34-W-3-4-003			1007	X			
CFA34-W-3-4-004			1055	X			
CFA34-W-3-4-005			1107	X			
CFA34-W-3-4-006			1122	X			
CFA34-W-3-4-006	JAY 8/192						
CFA34-W-3-4-007			1020	X			
CFA34-W-3-4-008			1030	X			
CFA34-W-3-4-009			1040	X			
CFA34-W-3-4-009			1040		X		
C92-170053-014							
JAY							
8/192							
Relinquished by: (Signature)		Date/Time	Received by: (Signature)		Relinquished by: (Signature)		
Relinquished by: (Signature)		Date/Time	Received by: (Signature)		Relinquished by: (Signature)		
Airborne Express		8/24/92 1000	8/24/92 1210		8/24/92 1000		

DISTRIBUTION: Original and Pink copies accompany sample shipment to laboratory. Original copy retained by laboratory. Pink copy retained by customer. Yellow copy retained by sampler.

0824294

ENVIRONMENTAL MONITORING CHAIN OF CUSTODY FORM

2052

SAMPLER: (Signature)	PROJECT NAME: EMS-142-90													
	SAMPLE NO.	LAB	SAMPLING DATE	SAMPLING TIME	COMP.	GRAB	AQUEOUS			OTHER	NO. OF CONTAINERS	TOTAL METALS	TOTAL VOA (T)	GROSS Alpha / (TAMARA ST)
							SAMPLING LOCATION	SOLID	AQUEOUS					
TAN34-W-3-5-001			8/2/92	0925	X		TAN		X	Z	X			
TAN34-W-3-5-002				0930	X				X	Z	X			
TAN34-W-3-5-003				0940	X				X	Z	X			
TAN34-W-3-5-004				0955	X				X	Z	X			
TAN34-W-3-5-005				1000	X				X	Z	X			
TAN34-W-3-5-006				1005	X				X	Z	X			
TAN34-W-3-5-007				1020	X				X	Z	X			
TAN34-W-3-5-008				1026	X				X	Z	X			
TAN34-W-3-5-009				1035	X				X	Z	X			
TAN34-W-3-5-009				1037		X			X	I		X		
JAN														
8/92														
C92-170053-014														
Relinquished by: (Signature)	Date/Time 8/2/92 1155	Received by: (Signature)	Relinquished by: (Signature)	Received by: (Signature)	Date/Time	Relinquished by: (Signature)	Received by: (Signature)	Date/Time	Relinquished by: (Signature)	Received by: (Signature)	Date/Time	Relinquished by: (Signature)	Received by: (Signature)	Date/Time
Relinquished by: (Signature) 553 P.E.S.S.	8/2/92 1155	Received by: (Signature) M.H.P.R.	Relinquished by: (Signature)	Received by: (Signature)	8/2/92 1000	Relinquished by: (Signature)	Received by: (Signature)	8/2/92 1000	Relinquished by: (Signature)	Received by: (Signature)	8/2/92 1000	Relinquished by: (Signature)	Received by: (Signature)	8/2/92 1000

DISTRIBUTION: Original and Pink copies accompany sample shipment to laboratory. Original copy retained by laboratory. Pink copy retained by customer. Pink copy retained by laboratory. Yellow copy retained by samplers.

ENVIRONMENTAL MONITORING CHAIN OF CUSTODY FORM

EG&G Idaho, Inc.
P.O. Box 1625 MS 4110
Idaho Falls, Idaho
(208) 526-8075 (208) 526-9535
Environmental Monitoring Team

2051

SAMPLE NO.		PROJECT NAME: EMS-142-90				NO. OF CONTAINERS		PARAMETERS	
FIELD	LAB	SAMPLING DATE	SAMPLING TIME	COMP.	GRAB	SAMPLING LOCATION	AQUEOUS	SOLID	OTHER
TAN34-W-3-6-001		8/18/92	1405	X		TAN		X	2
TAN34-W-3-6-002			1410	X				X	2
TAN34-W-3-6-003			1415	X				X	2
TAN34-W-3-6-003			1417		X			X	1
TAN34-W-3-6-004			1422	X				X	2
TAN34-W-3-6-005			1430	X				X	2
TAN34-W-3-6-006			1435	X				X	2
JAY									
8/92									
C92-170053-014									
Relinquished by: (Signature)		Date/Time		Received by: (Signature)		Date/Time		Relinquished by: (Signature)	
		8/21/92 1137							
Relinquished by: (Signature)		Date/Time		Received by: (Signature)		Date/Time		Relinquished by: (Signature)	
A. L. BOUNCE		8/24/92 1100							

DISTRIBUTION: Original and Pink copies accompany sample shipment to laboratory. Original copy retained by laboratory. Pink copy retained by customer. Yellow copy retained by samplers.

11 TYPE SEALED COOLER TEMP 30°

EG&G Idaho, Inc.
P.O. Box 1625 MS 4110
Idaho Falls, Idaho
(208) 526-8075 (208) 526-9535
Environmental Monitoring Team

ENVIRONMENTAL MONITORING CHAIN OF CUSTODY FORM

2050

SAMPLER: (Signature)		PROJECT NAME: EMS-142-90				PARAMETERS									
SAMPLE NO.		SAMPLING DATE	SAMPLING TIME	COMP.	GRAB	SAMPLING LOCATION	AQUEOUS	SOLID	OTHER	NO. OF CONTAINERS	TOTAL METALS (KRA)	Gross Alpha/Beta	Gamma Spec	TOTAL VOA (GC only)	
TAN34-W-3-7-001	LAB	8/1/92	1521	X		TAN		X		1	X	X	X		
TAN34-W-3-7-002			1525	X				X		2	X	X	X		
TAN34-W-3-7-003			1530	X				X		2	X	X	X		
TAN34-W-3-7-003			1533		X			X		1					
TAN34-W-3-7-004			1537	X				X		1	X	X	X		
TAN34-W-3-7-005			1542	X				X		2	X	X	X		
TAN34-W-3-7-006			1547	X				X		2	X	X	X		
56															
8-18-92															
092-170053-014															
Relinquished by: (Signature)		Date/Time		Received by: (Signature)		Relinquished by: (Signature)		Date/Time		Received by: (Signature)		Date/Time		Received by: (Signature)	
553 258 911		8/2/92 11:45		8/2/92 11:45		553 258 911		8/2/92 10:00		553 258 911		8/2/92 10:00		553 258 911	
Airborne Express						Airborne Express									

ENVIRONMENTAL MONITORING CHAIN OF CUSTODY FORM

2053

[illegible]

Original copy retained by laboratory. Pink copy retained by customer. Yellow copy retained by samplers.

Appendix D

Summary of Inorganic Results Data

UNDERGROUND INJECTION CONTROL ASSOCIATED SURFACE SOIL SAMPLES - TOTAL METALS BY RCRA METHODS RESULTS DATA

AREA LOCATION TYPE OF LOCATION SAMPLE NUMBER MEDIA UNITS SDG NUMBER	CFA WELL # 34-W-3-4 DEEP WELL CFA34W34001 SOIL mg/kg CFA34W34001	CFA WELL # 34-W-3-4 DEEP WELL CFA34W34002 SOIL mg/kg CFA34W34001	CFA WELL # 34-W-3-4 DEEP WELL CFA34W34003 SOIL mg/kg CFA34W34001	CFA WELL # 34-W-3-4 DEEP WELL CFA34W34004 SOIL mg/kg CFA34W34001	CFA WELL # 34-W-3-4 DEEP WELL CFA34W34005 SOIL mg/kg CFA34W34001
	0-0.5	0.5-1	1-1.5	0-0.5	0.5-1
FIELD MEASUREMENTS					
Depth (ft)					
ANALYTES					
Arsenic	14.0	5.9	6.0	6.6	6.3
Barium	230	210	240	220	140
Cadmium	1.0 U	1.0 U	1.0 U	1.0 U	1.0 U
Chromium	26.0	24.0	24.0	26.0	25.0
Lead	13.0	13.0	14.0	19.0	10.0
Mercury	0.15 U	0.15 U	0.15 U	0.15 U	0.15 U
Selenium	1.0 U	1.0 U	1.0 U	1.0 U	1.0 U
Silver	2.0 U	2.0 U	2.0 U	2.0 U	2.0 U
% Solids	98.3	98.2	97.9	98.6	98.6

12-11-92

N = Matrix spike recovery exceeded acceptance limits.
U = Constituent was analyzed for but not detected (sample quantitation must be corrected for dilution and percent moisture).

UNDERGROUND INJECTION CONTROL ASSOCIATED SURFACE SOIL SAMPLES - TOTAL METALS BY RCRA METHODS RESULTS DATA (Continued) Page 2 of 13

AREA LOCATION TYPE OF LOCATION SAMPLE NUMBER MEDIA UNITS SDG NUMBER	CFA WELL # 34-W-3-4 DEEP WELL CFA34W34006 SOIL mg/kg CFA34W34001	CFA WELL # 34-W-3-4 DEEP WELL CFA34W34007 SOIL mg/kg CFA34W34001	CFA WELL # 34-W-3-4 DEEP WELL CFA34W34008 SOIL mg/kg CFA34W34008	CFA WELL # 34-W-3-4 DEEP WELL CFA34W34009 SOIL mg/kg CFA34W34008	SPERT WELL # 34-W-3-1 DEEP WELL SPERT34W31001 SOIL mg/kg SPERT34W3100
FIELD MEASUREMENTS					
Depth (ft)	1-1.5	0-0.5	0.5-1	1-1.5	0-0.5
ANALYTES					
Arsenic	5.9	7.5	7.8	7.6	11.0
Barium	100	240	170	180	220
Cadmium	1.0 U	1.1	1.0 U	1.0 U	1.0 UN
Chromium	20.0	27.0	27.0	31.0	30.0
Lead	11.0	27.0	20.0	13.0	18.0
Mercury	0.15 U	0.15 U	0.15 U	0.15 U	0.15 U
Selenium	1.0 U	1.0 U	1.0 U	1.0 U	1.0 U
Silver	2.0 U	2.0 U	2.0 U	2.0 U	2.0 U
% Solids	98.2	98.8	87.8	97.8	98.1

12-11-92

(Continued)

UNDERGROUND INJECTION CONTROL ASSOCIATED SURFACE SOIL SAMPLES - TOTAL METALS BY RCRA METHODS RESULTS DATA

AREA LOCATION TYPE OF LOCATION SAMPLE NUMBER MEDIA UNITS SDG NUMBER	SPERT WELL # 34-W-3-1 DEEP WELL SPERT34W31002 SOIL mg/kg SPERT34W3100	SPERT WELL # 34-W-3-1 DEEP WELL SPERT34W31003 SOIL mg/kg SPERT34W3100	SPERT WELL # 34-W-3-1 DEEP WELL SPERT34W31004 SOIL mg/kg SPERT34W3100	SPERT WELL # 34-W-3-1 DEEP WELL SPERT34W31005 SOIL mg/kg SPERT34W3100	SPERT WELL # 34-W-3-1 DEEP WELL SPERT34W31006 SOIL mg/kg SPERT34W3100
FIELD MEASUREMENTS					
Depth (ft)	0.5-1	1-1.5	0-0.5	0.5-1	1-1.5
ANALYTES					
Arsenic	11.0	12.0	7.9	8.0	8.6
Barium	240	240	260	370	200
Cadmium	1.0 UN	1.0 UN	1.0 UN	1.0 UN	1.0 UN
Chromium	33.0	34.0	34.0	33.0	32.0
Lead	19.0	19.0	15.0	15.0	14.0
Mercury	0.15 U	0.15 U	0.15 U	0.15 U	0.15 U
Selenium	1.0 U	1.0 U	1.0 U	1.0 U	1.0 U
Silver	2.0 U	2.0 U	2.0 U	2.0 U	2.0 U
% Solids	99.5	97.6	95.9	95.7	95.2

12-11-92

UNDERGROUND INJECTION CONTROL ASSOCIATED SURFACE SOIL SAMPLES - TOTAL METALS BY RCRA METHODS RESULTS DATA (Continued)

AREA LOCATION TYPE OF LOCATION SAMPLE NUMBER MEDIA UNITS SDG NUMBER	SPERT WELL # 34-W-3-1 DEEP WELL SPERT34W31007 SOIL mg/kg SPERT34W3100	SPERT WELL # 34-W-3-1 DEEP WELL SPERT34W31008 SOIL mg/kg SPERT34W3100	SPERT WELL # 34-W-3-2 DEEP WELL SPERT34W32001 SOIL mg/kg SPERT34W3100	SPERT WELL # 34-W-3-2 DEEP WELL SPERT34W32002 SOIL mg/kg SPERT34W3100	SPERT WELL # 34-W-3-2 DEEP WELL SPERT34W32003 SOIL mg/kg SPERT34W3100
<u>FIELD MEASUREMENTS</u>					
Depth (ft)	0-0.5	0.5-1	0-0.5	0.5-1	1-1.5
<u>ANALYTES</u>					
Arsenic	17.0	9.6	12.0	15.0	16.0
Barium	360	260	230	280	300
Cadmium	1.4	1.0 UN	1.0 UN	1.0 UN	1.0 UN
Chromium	44.0	30.0	30.0	36.0	37.0
Lead	34.0	15.0	19.0	26.0	28.0
Mercury	0.15 U	0.15 U	0.15 U	0.15 U	0.15 U
Selenium	1.0 U	1.0 U	1.0 U	1.0 U	1.0 U
Silver	2.0 U	2.0 U	2.0 U	2.0 U	2.0 U
% Solids	96.7	96.4	96.2	93.9	94.5

12-11-92

AREA LOCATION TYPE OF LOCATION SAMPLE NUMBER MEDIA UNITS SDG NUMBER	SPERT WELL # 34-U-3-2 DEEP WELL SPERT34U32004 SOIL mg/kg SPERT34U3100	SPERT WELL # 34-U-3-2 DEEP WELL SPERT34U32005 SOIL mg/kg SPERT34U3100	SPERT WELL # 34-U-3-2 DEEP WELL SPERT34U32006 SOIL mg/kg SPERT34U3100	SPERT WELL # 34-U-3-2 DEEP WELL SPERT34U32007 SOIL mg/kg SPERT34U3100	SPERT WELL # 34-U-3-2 DEEP WELL SPERT34U32008 SOIL mg/kg SPERT34U3100
<u>FIELD MEASUREMENTS</u>					
Depth (ft)	0-0.5	0.5-1	1-1.5	0-0.5	0.5-1
<u>ANALYTES</u>					
Arsenic	17.0	18.0	17.0	19.0	19.0
Barium	340	340	350	370	350
Cadmium	1.0 U	1.0	1.0	1.0 U	1.1
Chromium	39.0	38.0	41.0	45.0	43.0
Lead	34.0	31.0	31.0	34.0	33.0
Mercury	0.15 U	0.15 U	0.15 U	0.15 U	0.15 U
Selenium	1.0 U	1.0 U	1.0 U	1.0 U	1.0 U
Silver	2.0 U	2.0 U	2.0 U	2.0 U	2.0 U
% Solids	96.8	93.2	92.5	94.6	92.1

12-11-92

UNDERGROUND INJECTION CONTROL ASSOCIATED SURFACE SOIL SAMPLES - TOTAL METALS BY RCRA METHODS RESULTS DATA (Continued)

AREA LOCATION TYPE OF LOCATION SAMPLE NUMBER MEDIA UNITS SDG NUMBER	SPERT WELL # 34-W-3-2 DEEP WELL SPERT34W32009 SOIL mg/kg SPERT34W3100	SPERT WELL # 34-W-3-3 DEEP WELL SPERT34W33001 SOIL mg/kg CFA34W34001	SPERT WELL # 34-W-3-3 DEEP WELL SPERT34W33002 SOIL mg/kg CFA34W34001	SPERT WELL # 34-W-3-3 DEEP WELL SPERT34W33003 SOIL mg/kg CFA34W34001	SPERT WELL # 34-W-3-3 DEEP WELL SPERT34W33004 SOIL mg/kg CFA34W34001
	1-1.5	0-0.5	0.5-1	1-1.5	0-0.5
FIELD MEASUREMENTS Depth (ft)					
ANALYTES					
Arsenic	12.0	13.0	15.0	17.0	15.0
Barium	310	330	330	350	360
Cadmium	1.0 UN	1.0 U	1.3	1.1	1.0 U
Chromium	36.0	45.0	43.0	44.0	45.0
Lead	28.0	28.0	27.0	29.0	28.0
Mercury	0.15 U	0.15 U	0.15 U	0.15 U	0.15 U
Selenium	1.0 U	1.0 U	1.0 U	1.0 U	1.0 U
Silver	2.0 U	2.0 U	2.0 U	2.0 U	2.0 U
% Solids	93.3	98.6	95.6	95.3	97.0

12-11-92

UNDERGROUND INJECTION CONTROL ASSOCIATED SURFACE SOIL SAMPLES - TOTAL METALS BY RCRA METHODS RESULTS DATA (Continued) Page 7 of 13

AREA LOCATION TYPE OF LOCATION SAMPLE NUMBER MEDIA UNITS SDG NUMBER	SPERT WELL # 34-W-3-3 DEEP WELL SPERT34W33005 SOIL mg/kg CFA34W34001	SPERT WELL # 34-W-3-3 DEEP WELL SPERT34W33006 SOIL mg/kg CFA34W34001	SPERT WELL # 34-W-3-3 DEEP WELL SPERT34W33007 SOIL mg/kg CFA34W34001	SPERT WELL # 34-W-3-3 DEEP WELL SPERT34W33008 SOIL mg/kg CFA34W34001	SPERT WELL # 34-W-3-3 DEEP WELL SPERT34W33009 SOIL mg/kg CFA34W34001
FIELD MEASUREMENTS					
Depth (ft)	0.5-1	1-1.5	0-0.5	0.5-1	1-1.5
ANALYTES					
Arsenic	14.0	16.0	16.0	14.0	14.0
Barium	340	340	370	340	330
Cadmium	1.1	1.0 U	1.4	1.3	1.1
Chromium	47.0	43.0	46.0	45.0	45.0
Lead	26.0	26.0	34.0	25.0	24.0
Mercury	0.15 U	0.15 U	0.15 U	0.15 U	0.15 U
Selenium	1.0 U	1.0 U	1.0 U	1.0 U	1.0 U
Silver	2.0 U	2.0 U	2.0 U	2.0 U	2.0 U
% Solids	94.4	94.2	94.2	94.3	95.7

12-11-92

UNDERGROUND INJECTION CONTROL ASSOCIATED SURFACE SOIL SAMPLES - TOTAL METALS BY RCRA METHODS RESULTS DATA (Continued) Page 8 of 13

AREA LOCATION TYPE OF LOCATION SAMPLE NUMBER MEDIA UNITS SDG NUMBER	TAN WELL # 34-U-3-5 DEEP WELL TAN34U35001 SOIL mg/kg CFA34U34008	TAN WELL # 34-U-3-5 DEEP WELL TAN34U35002 SOIL mg/kg CFA34U34008	TAN WELL # 34-U-3-5 DEEP WELL TAN34U35003 SOIL mg/kg CFA34U34008	TAN WELL # 34-U-3-5 DEEP WELL TAN34U35004 SOIL mg/kg CFA34U34008	TAN WELL # 34-U-3-5 DEEP WELL TAN34U35005 SOIL mg/kg CFA34U34008
FIELD MEASUREMENTS					
Depth (ft)	0-0.5	0.5-1	1-1.5	0-0.5	0.5-1
ANALYTES					
Arsenic	10.0	10.0	11.0	10.0	11.0
Barium	170	250	230	170	230
Cadmium	1.0 U	1.1	1.0 U	1.0 U	1.0 U
Chromium	28.0	38.0	37.0	29.0	35.0
Lead	15.0	18.0	18.0	17.0	15.0
Mercury	0.15 U	0.15 U	0.15 U	0.15 U	0.15 U
Selenium	1.0 U	1.0 U	1.0 U	1.0 U	1.0 U
Silver	2.0 U	2.0 U	2.0 U	2.0 U	2.0 U
% Solids	94.9	93.4	94.2	93.9	93.5

12-11-92

UNDERGROUND INJECTION CONTROL ASSOCIATED SURFACE SOIL SAMPLES - TOTAL METALS BY RCRA METHODS RESULTS DATA (Continued) Page 9 of 13

AREA LOCATION TYPE OF LOCATION SAMPLE NUMBER MEDIA UNITS SDG NUMBER	TAN WELL # 34-U-3-5 DEEP WELL TAN34U35006 SOIL mg/kg CFA34U34008	TAN WELL # 34-U-3-5 DEEP WELL TAN34U35007 SOIL mg/kg CFA34U34008	TAN WELL # 34-U-3-5 DEEP WELL TAN34U35008 SOIL mg/kg CFA34U34008	TAN WELL # 34-U-3-5 DEEP WELL TAN34U35009 SOIL mg/kg CFA34U34008	TAN WELL # 34-U-3-6 DEEP WELL TAN34U36001 SOIL mg/kg CFA34U34008
FIELD MEASUREMENTS					
Depth (ft)	1-1.5	0-0.5	0.5-1	1-1.5	0-0.5
ANALYTES					
Arsenic	12.0	11.0	13.0	14.0	14.0
Barium	230	240	250	280	240
Cadmium	1.1	1.0 U	1.0 U	1.0 U	1.0 U
Chromium	41.0	41.0	43.0	44.0	36.0
Lead	22.0	21.0	22.0	19.0	22.0
Mercury	0.39	0.15 U	0.15 U	0.15 U	0.15 U
Selenium	1.0 U	1.0 U	1.0 U	1.0 U	1.0 U
Silver	2.0 U	2.0 U	2.0 U	2.0 U	2.0 U
% Solids	93.8	93.6	93.9	90.2	95.7
12-11-92					

UNDERGROUND INJECTION CONTROL ASSOCIATED SURFACE SOIL SAMPLES - TOTAL METALS BY RCRA METHODS RESULTS DATA (Continued) Page 10 of 13

AREA LOCATION TYPE OF LOCATION SAMPLE NUMBER MEDIA UNITS SDG NUMBER	TAN WELL # 34-W-3-6 DEEP WELL TAN34W36002 SOIL mg/kg CFA34W34008	TAN WELL # 34-W-3-6 DEEP WELL TAN34W36003 SOIL mg/kg CFA34W34008	TAN WELL # 34-W-3-6 DEEP WELL TAN34W36004 SOIL mg/kg CFA34W34008	TAN WELL # 34-W-3-6 DEEP WELL TAN34W36005 SOIL mg/kg CFA34W34008	TAN WELL # 34-W-3-6 DEEP WELL TAN34W36006 SOIL mg/kg TAN34W36006
FIELD MEASUREMENTS Depth (ft)	0.5-1	1-1.5	0-0.5	0.5-1	1-1.5
ANALYTES					
Arsenic	10.0	14.0	12.0	12.0	10.0 M
Barium	200	280	260	250	140
Cadmium	1.0 U	1.0 U	1.1	1.0 U	1.0 U
Chromium	30.0	39.0	41.0	37.0	20.0
Lead	14.0	21.0	24.0	20.0	17.0 M
Mercury	0.15 U	0.15 U	0.15 U	0.15 U	0.15 U
Selenium	1.0 U	1.0 U	1.0 U	1.0 U	1.0 U
Silver	2.0 U	2.0 U	2.0 U	2.0 U	2.0 U
% Solids	95.8	91.7	95.5	94.7	96.5
12-11-92					

UNDERGROUND INJECTION CONTROL ASSOCIATED SURFACE SOIL SAMPLES - TOTAL METALS BY RCRA METHODS RESULTS DATA (Continued) Page 11 of 13

AREA LOCATION TYPE OF LOCATION SAMPLE NUMBER MEDIA UNITS SDG NUMBER	TAN WELL # 34-U-3-7 DEEP WELL TAN34U37001 SOIL mg/kg TAN34U36006	TAN WELL # 34-U-3-7 DEEP WELL TAN34U37002 SOIL mg/kg TAN34U36006	TAN WELL # 34-U-3-7 DEEP WELL TAN34U37003 SOIL mg/kg TAN34U36006	TAN WELL # 34-U-3-7 DEEP WELL TAN34U37004 SOIL mg/kg TAN34U36006	TAN WELL # 34-U-3-7 DEEP WELL TAN34U37005 SOIL mg/kg TAN34U36006
	0-0.5	0.5-1	1-1.5	0-0.5	0.5-1
FIELD MEASUREMENTS					
Depth (ft)					
ANALYTES					
Arsenic	12.0 N	10.0 N	11.0 N	12.0 N	11.0 N
Barium	230	230	260	260	230
Cadmium	1.0 U	1.0 U	1.0 U	1.0 U	1.0 U
Chromium	25.0	27.0	26.0	31.0	28.0
Lead	14.0 N	16.0 N	19.0 N	19.0 N	13.0 N
Mercury	0.15 U	0.15 U	0.15 U	0.15 U	0.15 U
Selenium	1.0 U	1.0 U	1.0 U	1.0 U	1.0 U
Silver	2.0 U	2.0 U	2.0 U	2.0 U	2.0 U
% Solids	97.2	98.2	98.5	99.2	98.4
12-11-92					

UNDERGROUND INJECTION CONTROL ASSOCIATED SURFACE SOIL SAMPLES - TOTAL METALS BY RCRA METHODS RESULTS DATA (Continued) Page 12 of 13

AREA LOCATION TYPE OF LOCATION SAMPLE NUMBER MEDIA UNITS SDG NUMBER	TAN WELL # 34-U-3-7 DEEP WELL TAN34U37006 SOIL mg/kg TAN34U36006	TAN WELL # 34-U-3-3 DEEP WELL TAN34U38001 SOIL mg/kg TAN34U36006	TAN WELL # 34-U-3-8 DEEP WELL TAN34U38002 SOIL mg/kg TAN34U36006	TAN WELL # 34-U-3-8 DEEP WELL TAN34U38003 SOIL mg/kg TAN34U36006	TAN WELL # 34-U-3-8 DEEP WELL TAN34U38004 SOIL mg/kg TAN34U36006
FIELD MEASUREMENTS Depth (ft)	1-1.5	0-0.5	0.5-1	1-1.5	0-0.5
ANALYTES					
Arsenic	12.0 N	11.0 N	11.0 N	11.0 N	9.6 N
Barium	240	130	130	220	190
Cadmium	1.0 U	1.0 U	1.0 U	1.0 U	1.0 U
Chromium	29.0	20.0	23.0	21.0	27.0
Lead	21.0 N	17.0 N	15.0 N	17.0 N	18.0 N
Mercury	0.15 U	0.15 U	0.15 U	0.15 U	0.15 U
Selenium	1.0 U	1.0 U	1.0 U	1.0 U	1.0 U
Silver	2.0 U	2.0 U	2.0 U	2.0 U	2.0 U
% Solids	98.5	98.8	97.9	97.8	98.3

12-11-92

AREA LOCATION TYPE OF LOCATION SAMPLE NUMBER MEDIA UNITS SDG NUMBER	TAN WELL # 34-U-3-8 DEEP WELL TAN34U38005 SOIL mg/kg TAN34U36006	TAN WELL # 34-U-3-8 DEEP WELL TAN34U38006 SOIL mg/kg TAN34U36006	TAN WELL # 34-U-3-8 DEEP WELL TAN34U38007 SOIL mg/kg TAN34U36006	TAN WELL # 34-U-3-8 DEEP WELL TAN34U38008 SOIL mg/kg TAN34U36006	TAN WELL # 34-U-3-8 DEEP WELL TAN34U38009 SOIL mg/kg TAN34U36006
FIELD MEASUREMENTS Depth (ft)	0.5-1	1-1.5	0-0.5	0.5-1	1-1.5
ANALYTES					
Arsenic	12.0 N	13.0 N	8.4 N	8.2 N	7.3 N
Barium	170	150	150	110	97.0
Cadmium	1.0 U	1.0 U	1.0 U	1.0 U	1.0 U
Chromium	21.0	21.0	26.0	21.0	18.0
Lead	15.0 N	14.0 N	16.0 N	12.0 N	11.0 N
Mercury	0.15 U	0.15 U	0.15 U	0.15 U	0.15 U
Selenium	1.0 U	1.0 U	1.0 U	1.1	1.0 U
Silver	2.0 U	2.0 U	2.0 U	2.0 U	2.0 U
% Solids	97.7	97.8	98.9	99.0	99.0

12-11-92

Appendix E

Summary of TCLP Volatile Organic Results Data

UNDERGROUND INJECTION CONTROL ASSOCIATED SURFACE SOIL SAMPLES - TCLP VOLATILE ORGANIC RESULTS DATA

AREA LOCATION TYPE OF LOCATION SAMPLE NUMBER MEDIA UNITS SDG NUMBER	CFA WELL # 34-U-3-4 DEEP WELL CFA34U34009 SOIL ug/L CFA34U34009	SPERT WELL # 34-U-3-1 DEEP WELL SPERT34U31006 SOIL ug/L SPERTU31006	SPERT WELL # 34-U-3-2 DEEP WELL SPERT34U32003 SOIL ug/L SPERTU31006	SPERT WELL # 34-U-3-2 DEEP WELL SPERT34U32006 SOIL ug/L SPERTU31006	SPERT WELL # 34-U-3-3 DEEP WELL SPERT34U33003 SOIL ug/L SPERTU31006
---	---	---	---	---	---

FIELD MEASUREMENTS
Depth (ft)

TARGET COMPOUNDS
Vinyl Chloride
Methylethylketone(2-butanone)
1,1-Dichloroethene
Chloroform
1,2-Dichloroethane
Carbon Tetrachloride
Trichloroethene
Benzene
Tetrachloroethene
Chlorobenzene

Dilution Factor

12-11-92

1-1.5	1-1.5	1-1.5	1-1.5	1-1.5	1-1.5
20 U	20 U	20 U	20 U	20 U	20 U
20000 U	20000 U	20000 U	20000 U	20000 U	20000 U
70 U	70 U	70 U	70 U	70 U	70 U
600 U	600 U	600 U	600 U	600 U	600 U
50 U	50 U	50 U	50 U	50 U	50 U
50 U	50 U	50 U	50 U	50 U	50 U
50 U	50 U	50 U	50 U	50 U	50 U
70 U	70 U	70 U	70 U	70 U	70 U
10000 U	10000 U	10000 U	10000 U	10000 U	10000 U
1.000	1.000	1.000	1.000	1.000	1.000

U = Constituent was analyzed for but not detected (sample quantitation must be corrected for dilution and percent moisture).

Underground Injection Control Associated Surface Soil Samples S&A Data Document • August 1992 • Method Validation Level C

Page 2 of 2

UNDERGROUND INJECTION CONTROL ASSOCIATED SURFACE SOIL SAMPLES - TCLP VOLATILE ORGANIC RESULTS DATA (Continued)

AREA LOCATION TYPE OF LOCATION SAMPLE NUMBER MEDIA UNITS SDG NUMBER	TAN WELL # 34-W-3-5 DEEP WELL TAN34W35009 SOIL ug/L CFA34W34009	TAN WELL # 34-W-3-6 DEEP WELL TAN34W36003 SOIL ug/L CFA34W34009	TAN WELL # 34-W-3-7 DEEP WELL TAN34W37003 SOIL ug/L CFA34W34009	TAN WELL # 34-W-3-8 DEEP WELL TAN34W38003 SOIL ug/L CFA34W34009
---	---	---	---	---

FIELD MEASUREMENTS
Depth: (ft)

1-1.5

1-1.5

1-1.5

1-1.5

TARGET COMPOUNDS
Vinyl Chloride
Methyl ethyl ketone(2-butanone)
1,1-Dichloroethene
Chloroform
1,2-Dichloroethane

20 U
20000 U
70 U
600 U
50 U

20 U
20000 U
70 U
600 U
50 U

20 U
20000 U
70 U
600 U
50 U

20 U
20000 U
70 U
600 U
50 U

Carbon Tetrachloride
Trichloroethene
Benzene
Tetrachloroethene
Chlorobenzene

50 U
50 U
50 U
70 U
10000 U

50 U
50 U
50 U
70 U
10000 U

50 U
50 U
50 U
70 U
10000 U

50 U
50 U
50 U
70 U
10000 U

1.000

1.000

1.000

1.000

Dilution Factor

12-11-92

Appendix F

Summary of Analysis Results for Radionuclides

UNDERGROUND INJECTION CONTROL ASSOCIATED SURFACE SOIL SAMPLES - ANALYSIS RESULTS FOR RADIONUCLIDES

AREA LOCATION TYPE OF LOCATION SAMPLE NUMBER MEDIA UNITS	CFA WELL # 34-W-3-4 DEEP WELL CFA34W34001 SOIL pci/g	CFA WELL # 34-W-3-4 DEEP WELL CFA34W34002 SOIL pci/g	CFA WELL # 34-W-3-4 DEEP WELL CFA34W34003 SOIL pci/g	CFA WELL # 34-W-3-4 DEEP WELL CFA34W34004 SOIL pci/g	CFA WELL # 34-W-3-4 DEEP WELL CFA34W34005 SOIL pci/g
FIELD MEASUREMENTS					
Depth (ft)	0-0.5	0.5-1	1-1.5	0-0.5	0.5-1
Gross Alpha					
	1.52E+01 ± 9.0 E+00	1.16E+01 ± 6.8 E+00	9.5 E+00 ± 7.0 E+00	7.6 E+00 ± 6.9 E+00	1.39E+01 ± 8.6 E+00
Gross Beta					
	2.65E+01 ± 6.9 E+00	1.73E+01 ± 5.2 E+00	2.30E+01 ± 5.7 E+00	2.50E+01 ± 6.8 E+00	2.75E+01 ± 6.5 E+00
Alpha Emitters					
Radium - 226	1.51E+00 ± 3.40E-01	1.52E+00 ± 3.50E-01	1.02E+00 ± 3.20E-01	1.17E+00 ± 2.45E-01	1.04E+00 ± 3.50E-01
Uranium - 235	5.16E-02 ± 2.00E-01	7.98E-02 ± 2.00E-01	6.75E-02 ± 2.00E-01	6.15E-02 ± 1.50E-02	9.73E-02 ± 2.00E-01
Gamma Emitters					
Actinium - 228 (Thorium Decay)	1.30E+00 ± 9.50E-02	1.51E+00 ± 1.05E-01	1.44E+00 ± 1.25E-01	1.35E+00 ± 8.00E-02	1.45E+00 ± 1.45E-01
Antimony - 125					
Bismuth - 214 (Radium Decay)	1.18E+00 ± 8.00E-02	1.28E+00 ± 8.50E-02	1.21E+00 ± 8.00E-02	1.13E+00 ± 6.00E-02	1.18E+00 ± 7.50E-02
Bismuth - 212 (Thorium Decay)	1.81E+00 ± 3.50E-01	2.01E+00 ± 3.00E-01	1.86E+00 ± 2.70E-01	1.64E+00 ± 1.65E-01	1.70E+00 ± 2.90E-01
Cesium - 137	7.30E-02 ± 2.00E-01	1.10E-01 ± 2.00E-01		2.87E-01 ± 2.00E-01	
Cobalt - 60				2.05E-01 ± 5.50E-02	
Europium - 155					
Lead - 214 (Radium Decay)	1.26E+00 ± 8.00E-02	1.44E+00 ± 9.00E-02	1.21E+00 ± 7.50E-02	1.17E+00 ± 6.50E-02	1.38E+00 ± 8.50E-02
Lead - 212 (Thorium Decay)	1.43E+00 ± 7.50E-02	1.46E+00 ± 8.00E-02	1.45E+00 ± 7.50E-02	1.24E+00 ± 6.50E-02	1.45E+00 ± 8.00E-02
Lead - 210 (Thorium Decay)					
Manganese - 54					
Potassium - 40	2.01E+01 ± 9.90E-01	1.16E+00 ± 3.65E-01	1.17E+00 ± 3.45E-01		8.72E-01 ± 4.10E-01
Ruthenium - 106		4.87E-02 ± 2.00E-01			
Thallium - 208 (Thorium Decay)		2.07E+01 ± 1.01E+00	2.06E+01 ± 1.01E+00	2.04E+01 ± 9.10E-01	2.05E+01 ± 1.01E+00
Thorium - 234					
	4.53E-01 ± 3.50E-02	4.38E-01 ± 3.50E-02	4.67E-01 ± 3.50E-02	3.94E-01 ± 2.50E-02	4.71E-01 ± 4.00E-02
	1.53E+00 ± 3.20E-01	1.89E+00 ± 3.65E-01	1.67E+00 ± 3.45E-01		2.01E+00 ± 3.65E-01

12-11-92

UNDERGROUND INJECTION CONTROL ASSOCIATED SURFACE SOIL SAMPLES - ANALYSIS RESULTS FOR RADIONUCLIDES (Continued)

AREA LOCATION TYPE OF LOCATION SAMPLE NUMBER MEDIA UNITS	CFA WELL # 34-W-3-4 DEEP WELL CFA34W34006 SOIL pci/g	CFA WELL # 34-W-3-4 DEEP WELL CFA34W34007 SOIL pci/g	CFA WELL # 34-W-3-4 DEEP WELL CFA34W34008 SOIL pci/g	CFA WELL # 34-W-3-4 DEEP WELL CFA34W34009 SOIL pci/g	SPERT WELL # 34-W-3-1 DEEP WELL SPERT34W31001 SOIL pci/g
FIELD MEASUREMENTS					
Depth (ft)	1-1.5	0-0.5	0.5-1	1-1.5	0-0.5
Gross Alpha					
	3.1 E+01 ± 1.3 E+01	1.7 E+01 ± 1.1 E+01	1.67E+01 ± 9.1 E+00	1.99E+01 ± 9.8 E+00	1.56E+01 ± 9.3 E+00
Gross Beta					
	3.46E+01 ± 7.10E+00	3.04E+01 ± 6.7 E+00	2.70E+01 ± 6.9 E+00	3.08E+01 ± 6.9 E+00	3.36E+01 ± 7.0 E+00
Alpha Emitters					
Radium - 226	1.53E+00 ± 3.45E-01	1.27E+00 ± 3.60E-01	1.50E+00 ± 2.65E-01	1.52E+00 ± 3.70E-01	7.62E-02 ± 2.00E-02
Uranium - 235	4.72E-02 ± 2.00E-01	8.30E-02 ± 2.00E-01	5.70E-02 ± 1.50E-02	9.05E-02 ± 2.50E-02	
Gamma Emitters					
Actinium - 228 (Thorium Decay)	1.39E+00 ± 9.50E-02	1.48E+00 ± 1.35E-01	1.50E+00 ± 9.00E-02	1.52E+00 ± 1.00E-01	1.34E+00 ± 1.00E-01
Antimony - 125					
Bismuth - 214 (Radium Decay)	1.19E+00 ± 7.50E-02	1.33E+00 ± 8.50E-02	1.15E+00 ± 6.50E-02	1.46E+00 ± 8.50E-02	1.25E+00 ± 8.50E-02
Bismuth - 212 (Thorium Decay)	1.31E+00 ± 2.60E-01	1.75E+00 ± 3.20E-01	1.91E+00 ± 1.95E-01	1.44E+00 ± 3.00E-01	1.51E+00 ± 2.95E-01
Cesium - 137		1.21E+00 ± 6.50E-02	3.53E-01 ± 2.00E-01	6.67E-02 ± 1.50E-02	
Cobalt - 60					
Europium - 155					
Lead - 214 (Radium Decay)	1.25E+00 ± 7.50E-02	1.38E+00 ± 8.50E-02	1.32E+00 ± 7.50E-02	1.47E+00 ± 8.50E-02	1.35E+00 ± 8.50E-02
Lead - 212 (Thorium Decay)	1.43E+00 ± 7.50E-02	1.42E+00 ± 8.00E-02	1.34E+00 ± 7.00E-02	1.47E+00 ± 8.00E-02	1.30E+00 ± 7.50E-02
Lead - 210 (Thorium Decay)	1.11E+00 ± 3.50E-01	1.28E+00 ± 3.90E-01		1.09E+00 ± 3.45E-01	1.09E+00 ± 3.40E-01
Manganese - 54					
Potassium - 40	2.03E+01 ± 9.90E-01	1.84E+01 ± 9.35E-01	2.05E+01 ± 9.20E-01	1.80E+01 ± 9.05E-01	1.93E+01 ± 9.65E-01
Ruthenium - 106					
Thallium - 208 (Thorium Decay)	4.43E-01 ± 3.50E-02	5.15E-01 ± 3.50E-02	5.04E-01 ± 3.00E-02	4.81E-01 ± 4.00E-02	4.06E-01 ± 3.50E-02
Thorium - 234	2.11E+00 ± 3.65E-01	1.75E+00 ± 3.60E-01	1.89E+00 ± 3.15E-01	2.26E+00 ± 3.70E-01	1.39E+00 ± 3.10E-01

12-11-92

AREA LOCATION TYPE OF LOCATION SAMPLE NUMBER MEDIA UNITS	SPERT WELL # 34-W-3-1 DEEP WELL SPERT34W31002 SOIL pci/g	SPERT WELL # 34-W-3-1 DEEP WELL SPERT34W31003 SOIL pci/g	SPERT WELL # 34-W-3-1 DEEP WELL SPERT34W31004 SOIL pci/g	SPERT WELL # 34-W-3-1 DEEP WELL SPERT34W31005 SOIL pci/g	SPERT WELL # 34-W-3-1 DEEP WELL SPERT34W31006 SOIL pci/g
FIELD MEASUREMENTS					
Depth (ft)	0.5-1	1-1.5	0-0.5	0.5-1	1-1.5
Gross Alpha	1.61E+01 ± 9.6 E+00	1.74E+01 ± 9.8 E+00	1.90E+01 ± 9.6 E+00	1.18E+01 ± 7.7 E+00	1.54E+01 ± 9.6 E+00
Gross Beta	2.82E+01 ± 6.4 E+00	2.95E+01 ± 6.3 E+00	2.47E+01 ± 6.4 E+00	3.31E+01 ± 6.5 E+00	3.20E+01 ± 6.6 E+00
Alpha Emitters					
Radium - 226	1.76E+00 ± 3.50E-01	1.64E+00 ± 3.85E-01	1.14E-01 ± 2.00E-02	5.65E-02 ± 2.50E-02	1.24E-01 ± 2.50E-02
Uranium - 235	6.12E-02 ± 2.00E-02	8.54E-02 ± 2.50E-02			
Gamma Emitters					
Actinium - 228 (Thorium Decay)	1.35E+00 ± 1.05E-01	1.36E+00 ± 1.15E-01	1.35E+00 ± 1.20E-01	1.48E+00 ± 1.10E-01	1.61E+00 ± 1.10E-01
Antimony - 125					
Bismuth - 214 (Radium Decay)	1.09E+00 ± 7.50E-02	1.14E+00 ± 8.00E-02	1.04E+00 ± 8.00E-02	9.90E-01 ± 8.00E-02	1.02E+00 ± 8.00E-02
Bismuth - 212 (Thorium Decay)	2.09E+00 ± 2.70E-01	1.58E+00 ± 2.90E-01	2.01E+00 ± 3.05E-01	1.46E+00 ± 4.00E-01	1.83E+00 ± 3.10E-01
Cesium - 137	7.19E-02 ± 2.50E-02	6.44E-02 ± 2.50E-02	4.09E-02 ± 2.00E-02	9.85E-02 ± 2.50E-02	6.26E-02 ± 2.00E-02
Cobalt - 60					
Europium - 155					
Lead - 214 (Radium Decay)	1.19E+00 ± 7.50E-02	1.11E+00 ± 8.50E-02	1.03E+00 ± 7.50E-02	1.10E+00 ± 8.00E-02	1.14E+00 ± 8.00E-02
Lead - 212 (Thorium Decay)	1.39E+00 ± 7.50E-02	1.32E+00 ± 7.50E-02	1.50E+00 ± 8.50E-02	1.64E+00 ± 9.00E-02	1.58E+00 ± 8.50E-02
Lead - 210 (Thorium Decay)	1.47E+00 ± 5.60E-01	1.15E+00 ± 4.30E-01			8.24E-01 ± 4.05E-01
Manganese - 54	5.60E-02 ± 2.00E-02				
Potassium - 40	2.22E+01 ± 1.08E+00	2.10E+01 ± 1.07E+00	1.85E+01 ± 9.85E-01	2.16E+01 ± 1.11E+00	2.03E+01 ± 1.60E+00
Ruthenium - 106					
Thallium - 208 (Thorium Decay)	4.53E-01 ± 3.50E-02	4.37E-01 ± 4.00E-02	4.16E-01 ± 3.50E-02	4.93E-01 ± 4.00E-02	4.73E-01 ± 3.50E-02
Thorium - 234	1.92E+00 ± 3.60E-01	1.44E+00 ± 3.10E-01	1.57E+00 ± 3.85E-01	2.23E+00 ± 4.05E-01	

12-11-92

UNDERGROUND INJECTION CONTROL ASSOCIATED SURFACE SOIL SAMPLES - ANALYSIS RESULTS FOR RADIONUCLIDES (Continued)

AREA LOCATION TYPE OF LOCATION SAMPLE NUMBER MEDIA UNITS	SPERT WELL # 34-W-3-1 DEEP WELL SPERT34W31007 SOIL pci/g	SPERT WELL # 34-W-3-1 DEEP WELL SPERT34W31008 SOIL pci/g	SPERT WELL # 34-W-3-2 DEEP WELL SPERT34W32001 SOIL pci/g	SPERT WELL # 34-W-3-2 DEEP WELL SPERT34W32002 SOIL pci/g	SPERT WELL # 34-W-3-2 DEEP WELL SPERT34W32003 SOIL pci/g
FIELD MEASUREMENTS					
Depth (ft)	0-0.5	0.5-1	0-0.5	0.5-1	1-1.5
Gross Alpha	2.5 E+01 ± 1.2 E+01	7.8 E+00 ± 6.5 E+00	3.9 E+00 ± 4.0 E+00	1.15E+01 ± 8.0 E+00	2.3 E+01 ± 1.0 E+01
Gross Beta	3.19E+01 ± 6.6 E+00	9.9 E+00 ± 5.6 E+00	1.74E+01 ± 5.5 E+00	3.41E+01 ± 6.9 E+00	3.48E+01 ± 6.8 E+00
Alpha Emitters	2.94E+00 ± 3.40E-01	1.02E-01 ± 2.00E-02	1.28E+00 ± 3.55E-01	2.56E+00 ± 3.80E-01	1.88E+00 ± 3.60E-01
Radium - 226					
Uranium - 235					
Gamma Emitters					
Actinium - 228 (Thorium Decay)	1.71E+00 ± 1.20E-01	1.10E+00 ± 1.30E-01	1.33E+00 ± 1.00E-01	1.21E+00 ± 9.50E-02	1.45E+00 ± 1.35E-01
Antimony - 125					
Bismuth - 214 (Radium Decay)	1.34E+00 ± 8.00E-02	1.07E+00 ± 7.50E-02	1.01E+00 ± 7.50E-02	1.09E+00 ± 8.00E-02	1.11E+00 ± 8.00E-02
Bismuth - 212 (Thorium Decay)	1.54E+00 ± 2.05E-01	1.33E+00 ± 2.30E-01	1.49E+00 ± 2.90E-01	1.73E+00 ± 3.35E-01	1.64E+00 ± 3.00E-01
Cesium - 137	6.08E-01 ± 3.50E-02	1.82E-01 ± 2.50E-02	1.78E-01 ± 2.50E-02	4.51E-02 ± 2.00E-02	
Cobalt - 60					
Europium - 155					
Lead - 214 (Radium Decay)	1.50E+00 ± 9.00E-02	1.07E+00 ± 7.50E-02	1.083+00 ± 7.50E-02	1.12E+00 ± 7.00E-02	1.22E+00 ± 8.50E-02
Lead - 212 (Thorium Decay)	1.50E+00 ± 8.00E-02	1.08E+00 ± 6.50E-02	1.28E+00 ± 7.50E-02	1.26E+00 ± 7.50E-02	1.34E+00 ± 7.50E-02
Lead - 210 (Thorium Decay)		8.42E-01 ± 3.20E-01	9.56E-01 ± 3.75E-01	1.07E+00 ± 4.25E-01	
Manganese - 54	2.51E+01 ± 1.15E+00	1.40E+01 ± 7.75E-01	2.00E+01 ± 9.90E-01	2.02E+01 ± 1.03E+00	1.96E+01 ± 1.02E+00
Potassium - 40					
Ruthenium - 106					
Thallium - 208 (Thorium Decay)	5.30E-01 ± 4.00E-02	3.78E-01 ± 3.00E-02	3.86E-01 ± 3.00E-02	4.13E-01 ± 3.50E-02	4.18E-01 ± 3.50E-02
Thorium - 234		1.90E+00 ± 3.55E-01	1.78E+00 ± 3.35E-01	2.09E+00 ± 4.00E-01	1.84E+00 ± 3.80E-01

12-11-92

UNDERGROUND INJECTION CONTROL ASSOCIATED SURFACE SOIL SAMPLES - ANALYSIS RESULTS FOR RADIONUCLIDES (Continued)

Page 5 of 13

AREA LOCATION TYPE OF LOCATION SAMPLE NUMBER MEDIA UNITS	SPERT WELL # 34-W-3-2 DEEP WELL SPERT34W32004 SOIL pci/g	SPERT WELL # 34-W-3-2 DEEP WELL SPERT34W32005 SOIL pci/g	SPERT WELL # 34-W-3-2 DEEP WELL SPERT34W32006 SOIL pci/g	SPERT WELL # 34-W-3-2 DEEP WELL SPERT34W32007 SOIL pci/g	SPERT WELL # 34-W-3-2 DEEP WELL SPERT34W32008 SOIL pci/g
FIELD MEASUREMENTS					
Depth (ft)	0-0.5	0.5-1	1-1.5	0-0.5	0.5-1
Gross Alpha	1.35E+01 ± 8.5 E+00	1.39E+01 ± 9.3 E+00	2.2 E+01 ± 1.0 E+01	1.52E+01 ± 8.8 E+00	2.2 E+01 ± 1.1 E+01
Gross Beta	3.10E+01 ± 6.5 E+00	3.28E+01 ± 6.5 E+00	2.74E+01 ± 7.0 E+00	3.43E+01 ± 7.0 E+00	3.55E+01 ± 7.1 E+00
Alpha Emitters					
Radium - 226	1.51E+00 ± 4.15E-01	8.19E-01 ± 2.90E-01	8.87E-01 ± 4.10E-01	2.83E+00 ± 3.20E-01	1.40E+00 ± 3.90E-01
Uranium - 235	8.67E-02 ± 2.50E-02	8.31E-02 ± 1.50E-02	8.71E-02 ± 2.50E-02		6.27E-02 ± 2.50E-02
Gamma Emitters					
Actinium - 228 (Thorium Decay)	1.42E+00 ± 1.25E-01	1.28E+00 ± 8.50E-02	1.21E+00 ± 1.00E-01	1.49E+00 ± 1.10E-01	1.36E+00 ± 1.05E-01
Antimony - 125					
Bismuth - 214 (Radium Decay)	1.45E+00 ± 1.00E-01	1.11E+00 ± 6.00E-02	1.24E+00 ± 9.00E-02	1.15E+00 ± 7.00E-02	1.05E+00 ± 8.00E-02
Bismuth - 212 (Thorium Decay)	1.26E+00 ± 3.00E-01	1.21E+00 ± 1.95E-01	1.56E+00 ± 3.35E-01	1.95E+00 ± 3.05E-01	1.34E+00 ± 2.65E-01
Cesium - 137	3.33E-01 ± 3.00E-02	3.45E-01 ± 2.00E-02	5.74E-01 ± 4.00E-02	6.61E-01 ± 3.50E-02	7.05E-01 ± 5.00E+00
Cobalt - 60					
Europium - 155					
Lead - 214 (Radium Decay)	1.50E+00 ± 1.00E-01	1.27E+00 ± 6.50E-02	1.40E+00 ± 9.50E-02	1.30E+00 ± 8.50E-02	1.10E+00 ± 8.00E-02
Lead - 212 (Thorium Decay)	1.39E+00 ± 8.50E-02	1.22E+00 ± 5.50E-02	1.38E+00 ± 8.00E-02	1.41E+00 ± 7.50E-02	1.42E+00 ± 8.00E-02
Lead - 210 (Thorium Decay)	2.22E+00 ± 4.90E-01		1.43E+00 ± 4.30E-01		1.99E+00 ± 4.25E-01
Manganese - 54	2.05E+01 ± 1.08E+00	2.09E+01 ± 7.20E-01	1.94E+01 ± 1.04E+00	2.26E+01 ± 1.05E+00	3.65E-02 ± 1.50E-02
Potassium - 40					2.05E+01 ± 1.06E+00
Ruthenium - 106					
Thallium - 208 (Thorium Decay)	4.46E-01 ± 4.00E-02	3.94E-01 ± 3.00E-02	4.52E-01 ± 4.00E-02	5.43E-01 ± 4.00E-02	4.28E-01 ± 4.00E-02
Thorium - 234		1.67E+00 ± 3.20E-01	1.58E+00 ± 3.70E-01	2.19E+00 ± 3.95E-01	1.09E+00 ± 3.40E-01

12-11-92

UNDERGROUND INJECTION CONTROL ASSOCIATED SURFACE SOIL SAMPLES - ANALYSIS RESULTS FOR RADIONUCLIDES (Continued)

AREA LOCATION TYPE OF LOCATION SAMPLE NUMBER MEDIA UNITS	SPERT WELL # 34-W-3-2 DEEP WELL SPERT34W32009 SOIL pci/g	SPERT WELL # 34-W-3-3 DEEP WELL SPERT34W33001 SOIL pci/g	SPERT WELL # 34-W-3-3 DEEP WELL SPERT34W33002 SOIL pci/g	SPERT WELL # 34-W-3-3 DEEP WELL SPERT34W33003 SOIL pci/g	SPERT WELL # 34-W-3-3 DEEP WELL SPERT34W33004 SOIL pci/g
FIELD MEASUREMENTS					
Depth (ft)	1-1.5	0-0.5	0.5-1	1-1.5	0-0.5
Gross Alpha	2.4 E+01 ± 1.1 E+01	1.48E+01 ± 9.2 E+00	1.9 E+01 ± 1.1 E+01	1.18E+01 ± 9.5 E+00	1.15E+01 ± 7.4 E+00
Gross Beta	2.85E+01 ± 7.1 E+00	4.07E+01 ± 7.5 E+00	2.86E+01 ± 7.0 E+00	3.02E+01 ± 6.9 E+00	3.09E+01 ± 7.0 E+00
Alpha Emitters					
Radium - 226	1.39E+00 ± 4.00E-01	2.00E+00 ± 4.05E-01	2.71E+00 ± 3.15E-01	1.45E+00 ± 3.05E-01	1.39E+00 ± 4.05E-01
Uranium - 235	9.18E-02 ± 2.50E-02	6.73E-02 ± 2.50E-02			5.45E-02 ± 2.50E-02
Gamma Emitters					
Actinium - 228 (Thorium Decay)	1.32E+00 ± 1.05E-01	1.54E+00 ± 1.60E-01	1.44E+00 ± 1.00E-01	1.37E+00 ± 9.00E-02	1.41E+00 ± 1.20E-01
Antimony - 125 Bismuth - 214 (Radium Decay)	1.14E+00 ± 8.50E-02	1.34E+00 ± 9.50E-02	1.38E+00 ± 7.50E-02	1.28E+00 ± 7.50E-02	1.40E+00 ± 9.50E-02
Bismuth - 212 (Thorium Decay)	1.82E+00 ± 3.35E-01	1.76E+00 ± 3.10E-01	1.53E+00 ± 2.05E-01	1.16E+00 ± 2.00E-01	1.20E+00 ± 2.65E-01
Cesium - 137 Cobalt - 60 Europium - 155	3.25E-01 ± 3.00E-02	1.67E-01 ± 3.00E-02	1.65E-01 ± 1.50E-20		2.60E-01 ± 2.50E-02
Lead - 214 (Radium Decay)	1.18E+00 ± 7.50E-02	1.44E+00 ± 9.50E-02	1.39E+00 ± 8.50E-02	1.33E+00 ± 7.50E-02	1.54E+00 ± 1.00E-01
Lead - 212 (Thorium Decay)	1.30E+00 ± 8.00E-02	1.48E+00 ± 8.50E-02	1.37E+00 ± 7.00E-02	1.24E+00 ± 7.00E-02	1.39E+00 ± 8.00E-02
Lead - 210 (Thorium Decay)	1.80E+00 ± 4.20E-01	1.71E+00 ± 6.35E-01			1.52E+00 ± 4.60E-01
Manganese - 54 Potassium - 40 Ruthenium - 106	2.01E+01 ± 1.05E+00	2.44E+01 ± 1.20E+00	2.26E+01 ± 1.03E+00	2.20E+01 ± 1.01E+00	2.14E+01 ± 1.09E+00
Thallium - 208 (Thorium Decay)	4.10E-01 ± 4.00E-02	5.06E-01 ± 4.00E-02	4.38E-01 ± 3.00E-02	3.91E-01 ± 3.00E-02	4.85E-01 ± 4.00E-02
Thorium - 234		1.75E+00 ± 3.75E-01			2.14E+00 ± 4.05E-01

12-11-92

UNDERGROUND INJECTION CONTROL ASSOCIATED SURFACE SOIL SAMPLES - ANALYSIS RESULTS FOR RADIONUCLIDES (Continued) Page 7 of 13

AREA LOCATION TYPE OF LOCATION SAMPLE NUMBER MEDIA UNITS	SPERT WELL # 34-W-3-3 DEEP WELL SPERT34W33005 SOIL pci/g	SPERT WELL # 34-W-3-3 DEEP WELL SPERT34W33006 SOIL pci/g	SPERT WELL # 34-W-3-3 DEEP WELL SPERT34W33007 SOIL pci/g	SPERT WELL # 34-W-3-3 DEEP WELL SPERT34W33008 SOIL pci/g	SPERT WELL # 34-W-3-3 DEEP WELL SPERT34W33009 SOIL pci/g
FIELD MEASUREMENTS					
Depth (ft)	0.5-1	1-1.5	0-0.5	0.5-1	1-1.5
Gross Alpha	1.38E+01 ± 8.4 E+00	1.59E+01 ± 9.1 E+00	2.2 E+01 ± 1.0 E+01	2.0 E+01 ± 1.1 E+01	1.36E+01 ± 9.5 E+00
Gross Beta	3.02E+01 ± 7.1 E+00	3.36E+01 ± 7.3 E+00	3.39E+01 ± 7.2 E+00	2.95E+01 ± 6.9 E+00	2.86E+01 ± 6.7 E+00
Alpha Emitters					
Radium - 226	2.69E+00 ± 3.95E-01	1.93E+00 ± 2.50E-01	2.39E+00 ± 5.35E-01	2.55E+00 ± 5.10E-01	2.02E+00 ± 4.30E-01
Uranium - 235					7.04E-02 ± 2.50E-02
Gamma Emitters					
Actinium - 228 (Thorium Decay)	1.46E+00 ± 1.10E-01	1.13E+00 ± 7.50E-02	1.51E+00 ± 9.50E-02	1.48E+00 ± 1.10E-01	1.48E+00 ± 1.40E-01
Antimony - 125					2.70E-01 ± 6.00E-02
Bismuth - 214 (Radium Decay)	1.38E+00 ± 9.00E-02	1.08E+00 ± 6.00E-02	1.18E+00 ± 7.00E-02	1.23E+00 ± 7.50E-02	1.34E+00 ± 9.50E-02
Bismuth - 212 (Thorium Decay)	1.08E+00 ± 3.25E-01	1.32E+00 ± 1.70E-01	1.51E+00 ± 2.15E-01	1.30E+00 ± 2.30E-01	1.73E+00 ± 3.65E-01
Cesium - 137	2.28E-01 ± 2.50E-02		3.48E-01 ± 2.50E-02	3.38E-01 ± 2.50E-02	8.08E-02 ± 2.00E-01
Cobalt - 60					
Europium - 155					
Lead - 214 (Radium Decay)	1.43E+00 ± 9.50E-02	1.22E+00 ± 7.00E-02	1.19E+00 ± 7.50E-02	1.34E+00 ± 8.00E-02	1.45E+00 ± 9.50E-02
Lead - 212 (Thorium Decay)	1.43E+00 ± 8.50E-02	1.09E+00 ± 6.00E-02	1.44E+00 ± 8.00E-02	1.28E+00 ± 7.00E-02	1.53E+00 ± 8.50E-02
Lead - 210 (Thorium Decay)	1.00E+00 ± 3.70E-01				1.73E+00 ± 6.30E-01
Manganese - 54					
Potassium - 40	2.08E+01 ± 1.08E+00	1.77E+01 ± 8.25E-01	2.81E-02 ± 1.00E-02	3.75E-02 ± 1.50E-02	2.19E+01 ± 1.10E+00
Ruthenium - 106		3.16E-01 ± 1.20E-01	2.47E+01 ± 1.13E+00	2.24E+01 ± 1.03E+00	
Thallium - 208 (Thorium Decay)	4.86E-01 ± 4.00E-02	3.48E-01 ± 3.00E-02	5.86E-01 ± 4.00E-02	4.15E-01 ± 2.50E-02	4.81E-01 ± 4.00E-02
Thorium - 234	2.23E+00 ± 4.10E-01	1.77E+00 ± 2.90E-01	2.08E+00 ± 3.90E-01	2.19E+00 ± 4.05E-01	2.39E+00 ± 4.25E-01

12-11-92

UNDERGROUND INJECTION CONTROL ASSOCIATED SURFACE SOIL SAMPLES - ANALYSIS RESULTS FOR RADIONUCLIDES (Continued) Page 8 of 13

AREA LOCATION TYPE OF LOCATION SAMPLE NUMBER MEDIA UNITS	TAN WELL # 34-W-3-5 DEEP WELL TAN34W35001 SOIL pci/g	TAN WELL # 34-W-3-5 DEEP WELL TAN34W35002 SOIL pci/g	TAN WELL # 34-W-3-5 DEEP WELL TAN34W35003 SOIL pci/g	TAN WELL # 34-W-3-5 DEEP WELL TAN34W35004 SOIL pci/g	TAN WELL # 34-W-3-5 DEEP WELL TAN34W35005 SOIL pci/g
	0-0.5	0.5-1	1-1.5	0-0.5	0.5-1
FIELD MEASUREMENTS					
Depth (ft)					
Gross Alpha	2.6 E+01 ± 1.2 E+01	1.00E+01 ± 8.4 E+00	1.11E+01 ± 9.5 E+00	4.5 E+00 ± 7.5 E+00	1.58E+01 ± 9.4 E+00
Gross Beta	2.44E+01 ± 6.8 E+00	1.72E+01 ± 6.0 E+00	2.71E+01 ± 7.0 E+00	1.54E+01 ± 5.9 E+00	3.06E+01 ± 6.8 E+00
Alpha Emitters					
Radium - 226	2.40E+00 ± 2.80E-01	1.65E+00 ± 2.80E-01	8.84E-01 ± 4.05E-01	1.01E+00 ± 3.80E-01	2.66E+00 ± 3.40E-01
Uranium - 235			8.02E-02 ± 2.50E-02	6.74E-02 ± 2.50E-02	
Gamma Emitters					
Actinium - 228 (Thorium Decay)	7.80E-01 ± 7.00E-02	9.64E-01 ± 8.50E-02	1.19E+00 ± 1.00E-01	9.89E-01 ± 1.00E-01	1.05E+00 ± 7.50E-02
Antimony - 125					
Bismuth - 214 (Radium Decay)	9.00E-01 ± 5.00E-02	1.05E+00 ± 5.50E-02	1.16E+00 ± 8.50E-02	1.16E+00 ± 8.00E-02	1.02E+00 ± 5.50E-02
Bismuth - 212 (Thorium Decay)	8.38E-01 ± 1.70E-01	1.26E+00 ± 1.85E-01	1.47E+00 ± 3.60E-01	1.21E+00 ± 3.05E-01	1.14E+00 ± 1.95E-01
Cesium - 137				1.67E-01 ± 3.00E-02	6.70E-02 ± 1.50E-02
Cobalt - 60					
Europium - 155		1.89E-01 ± 6.00E-02			
Lead - 214 (Radium Decay)	1.12E+00 ± 6.00E-02	1.23E+00 ± 6.50E-02	1.28E+00 ± 9.00E-02	1.14E+00 ± 8.00E-02	1.15E+00 ± 6.00E-02
Lead - 212 (Thorium Decay)	8.06E-01 ± 4.50E-02	9.81E-01 ± 5.00E-02	1.11E+00 ± 6.50E-02	8.95E-01 ± 5.50E-02	1.05E+00 ± 5.00E-02
Lead - 210 (Thorium Decay)					
Manganese - 54					
Potassium - 40	1.22E+01 ± 5.10E-01	1.40E+01 ± 5.40E-01	1.57E+01 ± 7.90E-01	1.36E+01 ± 7.05E-01	1.61E+01 ± 6.05E-01
Ruthenium - 106				3.32E-01 ± 1.30E-01	
Thallium - 208 (Thorium Decay)	2.82E-01 ± 2.00E-01	3.49E-01 ± 2.00E-01	3.32E-01 ± 3.50E-02	2.79E-01 ± 3.00E-02	3.91E-01 ± 4.00E-02
Thorium - 234			1.26E+00 ± 3.35E-01		

12-11-92

UNDERGROUND INJECTION CONTROL ASSOCIATED SURFACE SOIL SAMPLES - ANALYSIS RESULTS FOR RADIONUCLIDES (Continued)

AREA LOCATION TYPE OF LOCATION SAMPLE NUMBER MEDIA UNITS	TAN WELL # 34-U-3-5 DEEP WELL TAN34U35006 SOIL pci/g	TAN WELL # 34-U-3-5 DEEP WELL TAN34U35007 SOIL pci/g	TAN WELL # 34-U-3-5 DEEP WELL TAN34U35008 SOIL pci/g	TAN WELL # 34-U-3-5 DEEP WELL TAN34U35009 SOIL pci/g	TAN WELL # 34-U-3-6 DEEP WELL TAN34U36001 SOIL pci/g
FIELD MEASUREMENTS					
Depth (ft)	1-1.5	0-0.5	0.5-1	1-1.5	0-0.5
Gross Alpha	4.5 E+01 ± 1.5 E+01	1.46E+01 ± 9.2 E+00	3.0 E+01 ± 1.2 E+01	3.3 E+01 ± 1.3 E+01	4.0 E+01 ± 1.4 E+01
Gross Beta	3.27E+01 ± 6.8 E+00	4.30E+01 ± 7.0 E+00	3.62E+01 ± 7.2 E+00	3.43E+01 ± 6.8 E+00	4.55E+01 ± 7.4 E+00
Alpha Emitters					
Radium - 226	1.40E+00 ± 3.80E-01	1.15E+00 ± 3.70E-01	1.44E+00 ± 4.00E-01	1.82E+00 ± 3.15E-01	1.02E+00 ± 4.15E-01
Uranium - 235	7.12E-02 ± 2.50E-02	6.71E-02 ± 2.00E-02	9.37E-02 ± 2.50E-02		1.13E-01 ± 2.50E-02
Gamma Emitters					
Actinium - 228 (Thorium Decay)	1.31E+00 ± 1.05E-01	1.18E+00 ± 9.50E-02	1.41E+00 ± 1.05E-01	1.32E+00 ± 1.00E-01	1.53E+00 ± 1.25E-01
Antimony - 125					
Bismuth - 214 (Radium Decay)	1.22E+00 ± 8.50E-02	1.21E+00 ± 9.00E-02	1.05E+00 ± 8.50E-02	1.11E+00 ± 5.50E-02	1.36E+00 ± 9.00E-02
Bismuth - 212 (Thorium Decay)	1.26E+00 ± 3.15E-01	1.60E+00 ± 3.35E-01	1.37E+00 ± 3.00E-01	1.41E+00 ± 2.00E-01	1.61E+00 ± 3.60E-01
Cesium - 137	4.76E-02 ± 2.00E-02	1.71E-01 ± 2.50E-02			2.11E+00 ± 1.00E-01
Cobalt - 60					
Europium - 155					
Lead - 214 (Radium Decay)	1.29E+00 ± 8.50E-02	1.23E+00 ± 8.50E-02	1.24E+00 ± 8.50E-02	1.35E+00 ± 7.00E-02	1.50E+00 ± 1.00E-01
Lead - 212 (Thorium Decay)	1.12E+00 ± 7.00E-02	1.20E+00 ± 7.50E-02	1.48E+00 ± 8.50E-02	1.33E+00 ± 6.00E-02	1.53E+00 ± 8.50E-02
Lead - 210 (Thorium Decay)			2.16E+00 ± 6.60E-01		1.88E+00 ± 4.30E-01
Manganese - 54	1.70E+01 ± 9.55E-01	1.68E+01 ± 9.20E-01	1.68E+01 ± 9.05E-01	1.98E+01 ± 7.10E-01	1.90E+01 ± 9.90E-01
Potassium - 40					
Ruthenium - 106					
Thallium - 208 (Thorium Decay)	3.56E-01 ± 4.50E-02	3.98E-01 ± 4.00E-02	4.95E-01 ± 4.00E-02	4.44E-01 ± 3.50E-02	4.62E-01 ± 4.00E-02
Thorium - 234	1.34E+00 ± 3.25E-01	1.10E+00 ± 2.85E-01	1.81E+00 ± 3.85E-01		1.92E+00 ± 3.95E-01

12-11-92

UNDERGROUND INJECTION CONTROL ASSOCIATED SURFACE SOIL SAMPLES - ANALYSIS RESULTS FOR RADIONUCLIDES (Continued)

AREA LOCATION TYPE OF LOCATION SAMPLE NUMBER MEDIA UNITS	TAN WELL # 34-U-3-6 DEEP WELL TAN34U36002 SOIL pci/g	TAN WELL # 34-U-3-6 DEEP WELL TAN34U36003 SOIL pci/g	TAN WELL # 34-U-3-6 DEEP WELL TAN34U36004 SOIL pci/g	TAN WELL # 34-U-3-6 DEEP WELL TAN34U36005 SOIL pci/g	TAN WELL # 34-U-3-6 DEEP WELL TAN34U36006 SOIL pci/g
FIELD MEASUREMENTS					
Depth (ft)	0.5-1	1-1.5	0-0.5	0.5-1	1-1.5
Gross Alpha					
Gross Beta	3.8 E+01 ± 1.4 E+01 4.10E+01 ± 7.2 E+00	2.6 E+01 ± 1.1 E+01 3.28E+01 ± 6.7 E+00	4.8 E+01 ± 1.5 E+01 4.50E+01 ± 7.6 E+00	3.9 E+01 ± 1.3 E+01 4.06E+01 ± 7.4 E+00	4.0 E+01 ± 1.3 E+01 4.35E+01 ± 7.3 E+00
Alpha Emitters					
Radium - 226	1.26E+00 ± 3.95E-01	2.93E+00 ± 3.20E-01	1.21E+00 ± 4.65E-01	1.23E-01 ± 2.50E-02	1.71E+00 ± 3.15E-01
Uranium - 235	8.08E-02 ± 2.50E-02		7.54E-02 ± 3.00E-02		4.60E-02 ± 2.00E-02
Gamma Emitters					
Actinium - 228 (Thorium Decay)	1.33E+00 ± 1.00E-01	1.36E+00 ± 9.00E-02	1.54E+00 ± 1.20E-01	1.61E+00 ± 1.20E-01	1.36E+00 ± 8.50E-02
Antimony - 125					
Bismuth - 214 (Radium Decay)	1.16E+00 ± 8.50E-02	1.19E+00 ± 6.00E-02	1.32E+00 ± 9.50E-02	1.42E+00 ± 9.50E-02	1.19E+00 ± 7.50E-02
Bismuth - 212 (Thorium Decay)	1.31E+00 ± 3.55E-01	1.73E+00 ± 2.20E-01	1.57E+00 ± 3.35E-01	1.38E+00 ± 3.30E-01	1.76E+00 ± 2.65E-01
Cesium - 137	5.21E-01 ± 4.00E-02	2.92E-01 ± 2.00E-02	4.69E+00 ± 2.00E-01	2.75E+00 ± 1.25E-01	3.05E+00 ± 1.30E-01
Cobalt - 60					4.99E-02 ± 1.50E-02
Europium - 155					
Lead - 214 (Radium Decay)	1.22E+00 ± 8.00E-02	1.24E+00 ± 6.50E-02	1.40E+00 ± 1.05E-01	1.48E+00 ± 1.00E-01	1.23E+00 ± 7.50E-02
Lead - 212 (Thorium Decay)	1.34E+00 ± 7.50E-02	1.47E+00 ± 6.50E-02	1.39E+00 ± 8.50E-02	1.52E+00 ± 9.00E-02	1.29E+00 ± 7.00E-02
Lead - 210 (Thorium Decay)			1.90E+00 ± 4.55E-01	1.46E+00 ± 4.55E-01	
Manganese - 54	1.83E+01 ± 9.80E-01	2.08E+01 ± 7.45E-01	1.96E+01 ± 1.06E+00	2.10E+01 ± 1.11E+00	1.94E+01 ± 9.25E-01
Potassium - 40					
Ruthenium - 106					
Thallium - 208 (Thorium Decay)	3.85E-01 ± 3.50E-02	4.77E-01 ± 2.50E-02	4.84E-01 ± 4.00E-02	4.86E-01 ± 4.50E-02	4.47E-01 ± 3.50E-02
Thorium - 234	1.66E+00 ± 3.55E-01	2.13E+00 ± 3.70E-01	1.71E+00 ± 4.15E-01		

12-11-92

UNDERGROUND INJECTION CONTROL ASSOCIATED SURFACE SOIL SAMPLES - ANALYSIS RESULTS FOR RADIONUCLIDES (Continued)

Page 11 of 13

AREA LOCATION TYPE OF LOCATION SAMPLE NUMBER MEDIA UNITS	TAN WELL # 34-W-3-7 DEEP WELL TAN34W37001 SOIL pCi/g	TAN WELL # 34-W-3-7 DEEP WELL TAN34W37002 SOIL pCi/g	TAN WELL # 34-W-3-7 DEEP WELL TAN34W37003 SOIL pCi/g	TAN WELL # 34-W-3-7 DEEP WELL TAN34W37004 SOIL pCi/g	TAN WELL # 34-W-3-7 DEEP WELL TAN34W37005 SOIL pCi/g
FIELD MEASUREMENTS					
Depth (ft)	0-0.5	0.5-1	1-1.5	0-0.5	0.5-1
Gross Alpha	2.4 E+01 ± 1.1 E+01	1.55E+01 ± 9.8 E+00	8.2 E+00 ± 8.2 E+00	2.7 E+01 ± 1.3 E+01	2.1 E+01 ± 1.2 E+01
Gross Beta	4.00E+01 ± 7.1 E+00	2.49E+01 ± 6.1 E+00	2.66E+01 ± 7.2 E+00	2.70E+01 ± 6.8 E+00	3.03E+01 ± 6.9 E+00
Alpha Emitters					
Radium - 226	1.26E+00 ± 3.35E-01	7.58E-01 ± 3.80E-01	1.97E+00 ± 3.00E-01	2.76E+00 ± 3.10E-01	1.92E+00 ± 4.00E-01
Uranium - 235	7.35E-02 ± 2.00E-02	1.01E-01 ± 2.50E-02			5.16E-02 ± 2.50E-02
Gamma Emitters					
Actinium - 228 (Thorium Decay)	1.20E+00 ± 8.50E-02	1.30E+00 ± 1.00E-01	1.23E+00 ± 9.50E-02	1.56E+00 ± 1.05E-01	1.20E+00 ± 1.00E-01
Antimony - 125					
Bismuth - 214 (Radium Decay)	1.12E+00 ± 7.50E-02	1.27E+00 ± 9.00E-02	1.20E+00 ± 7.00E-02	1.40E+00 ± 8.00E-02	1.39E+00 ± 9.50E-02
Bismuth - 212 (Thorium Decay)	1.16E+00 ± 3.00E-01	1.57E+00 ± 3.10E-01	1.54E+00 ± 1.95E-01	1.27E+00 ± 2.00E-01	1.74E+00 ± 2.95E-01
Cesium - 137	4.18E-02 ± 1.50E-02		5.43E-02 ± 1.50E-02	8.37E-02 ± 1.50E-02	1.13E-01 ± 2.50E-02
Cobalt - 60					
Europium - 155					
Lead - 214 (Radium Decay)	1.14E+00 ± 7.50E-02	1.42E+00 ± 9.00E-02	1.34E+00 ± 8.00E-02	1.51E+00 ± 8.50E-02	1.32E+00 ± 9.00E-02
Lead - 212 (Thorium Decay)	1.27E+00 ± 7.00E-02	1.23E+00 ± 7.50E-02	1.15E+00 ± 6.50E-02	1.40E+00 ± 7.50E-02	1.29E+00 ± 7.50E-02
Lead - 210 (Thorium Decay)	1.28E+00 ± 3.40E-01	1.14E+00 ± 4.10E-01			1.42E+00 ± 3.95E-01
Manganese - 54	1.70E+01 ± 8.75E-01	1.86E+01 ± 9.70E-01	1.81E+01 ± 8.50E-01	2.03E+01 ± 9.40E-01	1.76E+01 ± 9.30E-01
Potassium - 40					
Ruthenium - 106					
Thallium - 208 (Thorium Decay)	4.10E-01 ± 3.50E-02	4.20E-01 ± 3.50E-02	4.37E-01 ± 3.50E-02	4.63E-01 ± 3.50E-02	3.53E-01 ± 3.00E-02
Thorium - 234	1.55E+00 ± 3.20E-01	1.40E+00 ± 3.30E-01	1.90E+00 ± 3.55E-01	2.36E+00 ± 4.00E-01	1.71E+00 ± 4.00E-01

12-11-92

UNDERGROUND INJECTION CONTROL ASSOCIATED SURFACE SOIL SAMPLES - ANALYSIS RESULTS FOR RADIONUCLIDES (Continued)

AREA LOCATION TYPE OF LOCATION SAMPLE NUMBER MEDIA UNITS	TAN WELL # 34-U-3-7 DEEP WELL TAN34U37006 SOIL pci/g	TAN WELL # 34-U-3-3 DEEP WELL TAN34U38001 SOIL pci/g	TAN WELL # 34-U-3-8 DEEP WELL TAN34U38002 SOIL pci/g	TAN WELL # 34-U-3-8 DEEP WELL TAN34U38003 SOIL pci/g	TAN WELL # 34-U-3-8 DEEP WELL TAN34U38004 SOIL pci/g
FIELD MEASUREMENTS					
Depth (ft)	1-1.5	0-0.5	0.5-1	1-1.5	0-0.5
Gross Alpha					
	2.5 E+01 ± 1.2 E+01	9.6 E+00 ± 8.9 E+00	1.8 E+01 ± 1.2 E+01	2.0 E+01 ± 1.2 E+01	8.1 E+00 ± 7.5 E+00
Gross Beta					
	2.23E+01 ± 6.9 E+00	2.07E+01 ± 7.1 E+00	2.67E+01 ± 7.4 E+00	1.63E+01 ± 6.7 E+00	2.47E+01 ± 6.8 E+00
Alpha Emitters					
Radium - 226	1.04E+00 ± 3.75E-01	1.16E+00 ± 3.60E-01	1.97E+00 ± 3.10E-01	1.94E+00 ± 2.60E-01	1.55E+00 ± 3.65E-01
Uranium - 235	9.52E-02 ± 2.00E-02	5.79E-02 ± 2.00E-02			5.34E-02 ± 2.00E-02
Gamma Emitters					
Actinium - 228 (Thorium Decay)	1.60E+00 ± 1.45E-01	7.88E-01 ± 8.50E-02	1.35E+00 ± 1.20E-01	9.23E-01 ± 6.00E-02	1.09E+00 ± 1.25E-01
Antimony - 125					
Bismuth - 214 (Radium Decay)	1.20E+00 ± 8.50E-02	9.39E-01 ± 8.00E-02	1.29E+00 ± 7.50E-02	9.85E-01 ± 5.50E-02	1.11E+00 ± 8.00E-02
Bismuth - 212 (Thorium Decay)	9.75E-01 ± 2.70E-01	1.06E+00 ± 2.50E-01	1.40E+00 ± 2.30E-01	9.89E-01 ± 1.90E-01	1.46E+00 ± 2.75E-01
Cesium - 137	1.51E-01 ± 2.50E-02				
Cobalt - 60					
Europium - 155					
Lead - 214 (Radium Decay)	1.22E+00 ± 9.00E-02	1.05E+00 ± 7.50E-02	1.36E+00 ± 8.00E-02	1.10E+00 ± 6.00E-02	1.09E+00 ± 8.00E-02
Lead - 212 (Thorium Decay)	1.20E+00 ± 7.50E-02	8.54E-01 ± 6.00E-02	1.34E+00 ± 7.50E-02	9.11E-01 ± 5.00E-02	1.01E+00 ± 6.50E-02
Lead - 210 (Thorium Decay)	1.80E+00 ± 5.95E-01	6.98E-01 ± 3.05E-01			1.27E+00 ± 5.45E-01
Manganese - 54	1.69E+01 ± 9.15E-01	1.21E+01 ± 7.55E-01	2.09E+01 ± 9.70E-01	1.36E+01 ± 5.40E-01	1.62E+01 ± 8.70E-01
Potassium - 40					
Ruthenium - 106					
Thallium - 208 (Thorium Decay)	4.44E-01 ± 4.00E-02	3.04E-01 ± 3.50E-02	4.68E-01 ± 4.00E-02	3.12E-01 ± 3.50E-02	3.16E-01 ± 3.00E-02
Thorium - 234	1.49E+00 ± 4.00E-01	9.13E-01 ± 2.65E-01	1.96E+00 ± 3.65E-01	2.05E+00 ± 3.50E-01	1.24E+00 ± 3.00E-01

12-11-92

UNDERGROUND INJECTION CONTROL ASSOCIATED SURFACE SOIL SAMPLES - ANALYSIS RESULTS FOR RADIONUCLIDES (Continued)

Page 13 of 13

AREA LOCATION TYPE OF LOCATION SAMPLE NUMBER MEDIA UNITS	TAN WELL # 34-W-3-8 DEEP WELL TAN34W38005 SOIL pci/g	TAN WELL # 34-W-3-8 DEEP WELL TAN34W38006 SOIL pci/g	TAN WELL # 34-W-3-8 DEEP WELL TAN34W38007 SOIL pci/g	TAN WELL # 34-W-3-8 DEEP WELL TAN34W38008 SOIL pci/g	TAN WELL # 34-W-3-8 DEEP WELL TAN34W38009 SOIL pci/g
FIELD MEASUREMENTS					
Depth (ft)	0.5-1	1-1.5	0-0.5	0.5-1	1-1.5
Gross Alpha					
	1.03E+01 ± 8.6 E+00	1.9 E+01 ± 1.1 E+01	8.7 E+00 ± 7.8 E+00	1.3 E+00 ± 6.8 E+00	9.0 E+00 ± 9.3 E+00
Gross Beta					
	1.43E+01 ± 6.7 E+00	1.54E+01 ± 6.9 E+00	1.86E+01 ± 6.8 E+00	1.72E+01 ± 6.4 E+00	1.50E+01 ± 6.4 E+00
Alpha Emitters					
Radium - 226	1.21E+00 ± 3.75E-01		1.39E+00 ± 2.85E-01	1.24E+00 ± 3.15E-01	1.27E+00 ± 3.15E-01
Uranium - 235	6.32E-02 ± 2.00E-02	5.79E-02 ± 2.00E-02	4.12E-02 ± 1.50E-02	6.48E-02 ± 2.00E-02	
Gamma Emitters					
Actinium - 228 (Thorium Decay)	8.41E-01 ± 8.00E-02	7.92E-01 ± 9.00E-02	9.86E-01 ± 7.00E-02	8.26E-01 ± 8.00E-02	6.60E-01 ± 6.50E-02
Antimony - 125					
Bismuth - 214 (Radium Decay)	7.74E-01 ± 6.50E-02	8.79E-01 ± 7.00E-02	1.20E+00 ± 7.00E-02	1.04E+00 ± 7.00E-02	8.84E-01 ± 6.50E-02
Bismuth - 212 (Thorium Decay)	1.41E+00 ± 3.00E-01	9.41E-01 ± 2.70E-01	1.18E+00 ± 1.60E-01	7.46E-01 ± 2.05E-01	4.24E-01 ± 2.05E-01
Cesium - 137			2.43E-01 ± 2.00E-02	1.05E-01 ± 1.50E-02	6.50E-02 ± 1.50E-02
Cobalt - 60			3.62E-02 ± 1.00E-02		
Europium - 155					
Lead - 214 (Radium Decay)	8.80E-01 ± 7.00E-02	9.69E-01 ± 6.50E-02	1.29E+00 ± 7.50E-02	1.01E+00 ± 7.00E-02	9.57E-01 ± 7.00E-02
Lead - 212 (Thorium Decay)	8.57E-01 ± 6.00E-02	7.00E-01 ± 5.60E-02	9.79E-01 ± 5.50E-02	6.26E-01 ± 5.00E-02	6.63E-01 ± 5.00E-02
Lead - 210 (Thorium Decay)				7.04E-01 ± 2.60E-01	1.08E+00 ± 4.65E-01
Manganese - 54	1.15E+01 ± 7.10E-01	1.06E+01 ± 6.00E-01	1.67E+01 ± 7.90E-01	1.08E+01 ± 6.40E-01	1.05E+01 ± 6.10E-01
Potassium - 40				2.46E-01 ± 1.15E-01	
Ruthenium - 106					
Thallium - 208 (Thorium Decay)	2.77E-01 ± 3.00E-02	2.65E-01 ± 2.50E-02	3.30E-01 ± 2.00E-02	2.02E-01 ± 2.00E-02	2.15E-01 ± 2.50E-02
Thorium - 234	7.54E-01 ± 2.50E-01		1.59E+00 ± 3.45E-01	1.31E+00 ± 3.25E-01	8.98E-01 ± 2.45E-01

12-11-92

Appendix G

Summary of Soil Concentration Data for Comparison with Deep Well Retention Basin Associated Soils

Table G-1. Trace chemical element content of natural soils (EPA 1983).

Element	Common Range (ppm)	Average (ppm)	Element	Common Range (ppm)	Average (ppm)
Aluminum	10,000–300,000	71,000	Lithium	5–200	20
Antimony	2–10	—	Magnesium	600–6000	5000
Arsenic	1–50	5	Manganese	20–3000	600
Barium	100–3000	430	Mercury	0.01–0.3	.03
Beryllium	0.1–40	6	Molybdenum	0.2–5	2
Boron	2–100	10	Nickel	5–500	40
Bromine	1–10	5	Radium	8 x 10 ⁻⁵	
Cadmium	0.01–0.7	.06	Rubidium	50–500	10
Cesium	0.3–25	6	Selenium	0.1–2	.3
Chlorine	20–900	100	Silver	0.01–5	.05
Chromium	1–1000	100	Strontium	50–1000	200
Cobalt	1–40	8	Tin	2–200	10
Copper	2–100	30	Tungsten		1
Fluorine	10–4000	200	Uranium	0.9–9	1
Gallium	0.4–300	30	Vanadium	20–500	100
Gold		1	Yttrium	25–250	50
Iodine	0.1–40	5	Zinc	10–300	50
Lanthanum	1–5000	30	Zirconium	60–2000	300
Lead	2–200	10			

Table G-2. Statistics for results of metals analysis on surface soils at the Central Facilities Area (CFA), Power Burst Facility (PBF), and Test Reactor Area (TAN) at INEL (EG&G Idaho 1992).

CFA, PBF, and TRA inorganic background						
	Count	Minimum	Maximum	Median	Mean	Standard deviation
Aluminum	3	12,500.00	13,000.00	12,700.00	12,733.33	251.66
Antimony	3	0.00	0.00	0.00	0.00	0.00
Arsenic	3	0.00	75.70	44.00	39.90	38.02
Barium	3	181.00	184.00	184.00	183.00	1.73
Beryllium	3	1.20	1.40	1.30	1.30	0.10
Cadmium	3	1.90	3.00	2.80	2.57	0.59
Calcium	3	4580.00	4830.00	4590.00	4666.67	141.54
Chromium	3	15.90	16.20	15.90	16.00	0.17
Cobalt	3	0.00	6.20	5.50	3.90	3.40
Copper	3	41.00	44.40	42.60	42.67	1.70
Iron	3	16,300.00	17,200.00	16,900.00	16,800.00	458.26
Lead	3	37.00	41.80	38.20	39.00	2.50
Magnesium	3	5000.00	5520.00	5250.00	5256.67	260.06
Manganese	3	633.00	655.00	636.00	641.33	11.93
Mercury	3	0.05	0.06	0.06	0.06	0.01
Nickel	3	12.70	15.30	13.50	13.83	1.33
Potassium	3	3270.00	3420.00	3330.00	3340.00	75.50
Selenium	3	0.00	0.00	0.00	0.00	0.00
Silver	3	0.00	0.00	0.00	0.00	0.00
Sodium	3	77.60	141.00	108.00	108.87	31.71
Thallium	3	0.00	34.10	29.90	21.33	18.59
Vanadium	3	26.20	29.50	27.60	27.77	1.66
Zinc	3	64.60	67.00	65.00	65.53	1.29

Table G-3. Comparison of NPR and the DOE Radiological and Environmental Sciences (RESL) radiological soil concentration measurements.

Nuclide	NPR data ^a for the NPR site (pCi/g)	NPR data ^b for the region (pCi/g)	RESL data ^c — regional (pCi/g)
Pu-239	0.018 to 0.049 [mean=0.03]	0.026 to 0.036	0.020 (0.017 to 0.024)
Pu-238	0.0 to 0.012 [mean=0.004]	0.001 to 0.003	0.0028 (0.0023 to 0.0034)
Am-241	0.005 to 0.019 [mean=0.01]	0.008 to 0.012	0.0040 (0.003 to 0.005)
Cs-137 ^d	0.404 to 1.92 [mean=0.929]	0.672 to 2.08	0.65 (0.54 to 0.76)
U-238 ^e	1.31 to 1.790 [mean=1.478]	0.86 to 1.64	1.52 (1.48 to 1.56)
Cm-244	0.001 to 0.008 [mean=0.004]	0.002 to 0.005	--- (not reported)

a. Range of data, with the arithmetic mean in brackets.

b. Range of data.

c. Geometric mean with the range corresponding to two geometric standard deviations in parentheses.

d. Decay corrected from 1975 to 1992.

e. Data from RESL report IDO 12082 (76).

END

**DATE
FILMED**

7/9/93