NOTICE

**CERTAIN DATA
CONTAINED IN THIS
DOCUMENT MAY BE
DIFFICULT TO READ
IN MICROFICHE
PRODUCTS.**

JACOBS ENGINEERING GROUP INC.
ADVANCED SYSTEMS DIVISION, ALBUQUERQUE OPERATIONS

DELIVERABLE RECEIPT

JEGA/UMT--1288-0525

CONTRACT DE-AC04-82AL14086

DE91 005842

To: Project Integration and Control

The following deliverable was submitted to the UMTRA Project Office.

Deliverable/Title Vegetative Special Study

Task No. AH-10-15-40-06 Number Of Copies

Type

☐ Contract Deliverable ☐ Scheduled Deliverable ☒ Unscheduled Deliverable

Category

☐ Preliminary Draft ☐ Preliminary Final ☐ Published Copy
☐ Draft ☒ Final ☐ Revision

Scheduled Delivery Date N/A

Actual Delivery Date

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

Bill Glover

Task/Site Manager

JACOBS ENGINEERING GROUP INC.

ALBUQUERQUE OPERATIONS

5301 CENTRAL AVENUE N.E. — SUITE 1700, ALBUQUERQUE, NEW MEXICO 87108
TELEPHONE (505) 846-4030

Mr. W. John Arthur, III
UMTRA Project Manager
U.S. Department of Energy
Uranium Mill Tailings Project Office
5301 Central Avenue, N.E., Suite 1700
Albuquerque, New Mexico 87108

Re: Final Report for Vegetative
Cover Special Study
Contract No. DE-AC04-82AL14086

Dear John:

Submitted with this letter is the final report for the Special Study on Vegetative Covers. The objectives of the study were to evaluate the feasibility of using vegetative covers for stabilized UMTRA Project piles, to define the advantages and disadvantages of using vegetative covers, and to develop general guidelines for the design and construction of vegetative covers for the UMTRA Project. The study involved a comprehensive survey of the DOE's studies and use of vegetative covers at waste management facilities around the country, as well as observations of volunteer plant growth on existing UMTRA Project piles.

The principal finding of the report is that vegetative covers may be used to stabilize surfaces of UMTRA Project piles that have yet to be constructed. Plants will transpire precipitation back to the atmosphere rather than allowing it to percolate to the tailings, from which contaminants may be mobilized. On a properly engineered pile, the vegetation will resist erosion, adapt to climatic change, repair itself after fire or drought, and persist indefinitely with no maintenance.

Vegetative covers may be designed to protect the underlying radon barrier from penetration by roots and burrowing animals. Rock covers may be susceptible to invasion by unwanted growth of deep-rooted plants that may damage the radon barrier.

The report includes general guidelines for designing and constructing vegetative covers, with examples drawn from the covers planned for the stabilized piles for the tailings at Grand Junction and Durango, Colorado. Examples are also given of performance assessments of those covers relative to water balance and erosion resistance.

The guidelines in this report will be included in the UMTRA Project Technical Approach Document. A continuation of this special study (on a

-2-

small scale) is advised in order to keep abreast of the latest developments in research programs in progress at other DOE facilities using vegetative covers. Especially important is recent progress in the use of performance models for gully resistance and water balance, as these will facilitate compliance demonstrations for proposed UMTRA Project designs. The report also recommends that data be collected from the eight-year-old vegetative cover test plot established by Pacific Northwest Laboratories for the UMTRA Project near the Shiprock site; these data will also contribute to performance assessments for UMTRA Project piles where vegetative covers are planned.

Please contact Charles Reith, Dave Lechel, or me if you have any questions.

Very truly yours,
JACOBS ENGINEERING GROUP INC.

Donald P. Dubois, Manager
Albuquerque Operations Office

DPD/11
Enclosure

cc: BGlover
DLechel
CReith

SPECIAL STUDY ON VEGETATIVE COVERS

November 1988

U.S. Department of Energy
UMTRA Project Office
Albuquerque Operations Office
Albuquerque, New Mexico

TABLE OF CONTENTS

EXECUTIVE SUMMARY

<u>Section</u>	<u>Page</u>
1.0 INTRODUCTION	1
1.1 Purpose and scope	1
1.2 Definition of a vegetative cover	1
2.0 METHODS	4
3.0 APPLICABILITY	5
3.1 Prevention of biointrusion	5
3.1.1 Observations of volunteer plant growth on the Shiprock pile	6
3.1.2 Biointrusion hazard associated with rock-over-soil cover designs	7
3.1.3 Prevention of root penetration with a cobble biointrusion barrier	9
3.1.4 Compatibility with a vegetative cover	11
3.2 Control of water balance	13
3.3 Resistance to erosion.	18
3.3.1 Sheetwash erosion	20
3.3.2 Gully erosion	20
3.3.3 Applicability to UMTRA.	21
3.4 Summary remarks on the applicability of vegetative covers for stabilizing UMTRA Project piles.	22
4.0 IMPLEMENTATION.	24
4.1 Pile morphology.	24
4.2 Prevention of biointrusion	24
4.3 Species selection	28
4.4 Rooting medium	30
4.5 Seeding and planting	31
4.6 Rock Mulch	32
4.7 Irrigation	32
4.8 Performance monitoring	33
5.0 PERFORMANCE ASSESSMENT.	34
5.1 Methods for determination of soil loss	34
5.2 Soil loss rates at the Grand Junction and Durango sites. . .	35
5.3 Methods for assessment of water balance.	37
5.4 Results of water balance simulations and sensitivity analyses for the vegetative cover at the disposal site for the Grand Junction tailings.	41
6.0 SUMMARY AND RECOMMENDATIONS	46
6.1 Summary	46
6.2 Recommendations	50
REFERENCES	52

TABLE OF CONTENTS

APPENDIX A - A TIME-RELEASED HERBICIDAL SYSTEM FOR PREVENTING BIOINTRUSION

LIST OF FIGURES

<u>Figure</u>	<u>Page</u>
1.1 Simplified diagram of a vegetative cover.	2
3.1 Cumulative percent frequency of rooting depth and lateral extension of plants growing in adobe clay	7
3.2 Diagram of ant tunnels, pocket mice tunnels, and Russian thistle roots that were observed during the excavation of loose rock biobarrier study.	12
3.3 Factors in the evaluation of cover components for biointrusion hazard.	14
3.4 Predicted average annual hydraulic values as a function of trench cap thickness at Los Alamos.	17
4.1 Basic vegetative cover design concept with features listed for the vegetative covers planned for the stabilized piles at Grand Junction and Durango.	25
4.2 Perimeter dike removal disposal cell layout	26
4.3 Cover design concepts for prevention of gullies	27
4.4 Pile design for Gunnison, Colorado, that will protect against biointrusion on the sideslopes.	29
5.1 Results of HELP simulations for the vegetative cover at the Grand Junction site	42
5.2 Results of CREAMS simulations for the vegetative cover at the Grand Junction site	42
5.3 Sensitivity of HELP simulations to variation in the hydraulic conductivity of the soil layer.	43
5.4 Sensitivity of HELP simulations to variation in the thickness of the soil layer	43
5.5 Sensitivity of HELP simulations to the variation in leaf area index (LAI)	44
5.6 Sensitivity of CREAMS simulations in variation in leaf area index (LAI)	44
6.1 Generic cell design for relocation option	47
6.2 Generic cell design for stabilization in place.	48
6.3 Generic design for vegetative cover on topslopes.	49

LIST OF PLATES

PLATE 1	Volunteer vegetation on Shiprock pile
PLATE 2	Roots of vegetation on Shiprock pile

LIST OF TABLES

<u>Table</u>	<u>Page</u>
3.1 Environmental characteristics and biointrusion risk scores for UMTRA Project disposal sites.	8
3.2 Characteristics related to the potential for plant invasion onto a pile with a rock-over-soil cover design.	10
3.3 Characteristics related to the likelihood of biointrusion in a stabilized pile with a vegetative cover	15
3.4 Comparison of features of some infiltration models with explicit vegetative transpiration terms	19
5.1 Input Values for MUSLE calculations	36
5.2 Conditions and VM Factors Used in MUSCLE calculations for Durango and Grand Junction.	36
5.3 Soil loss calculations (inches) for two UMTRA Project sites . . .	38
5.4 Input parameter values for HELP sensitivity analyses, Grand Junction vegetated cover.	39
5.5 Input parameter values for CREAMS sensitivity analyses, Grand Junction vegetated cover.	40

EXECUTIVE SUMMARY

This report describes the findings of a special study on the use of vegetative covers to stabilize tailings piles for the Uranium Mill Tailings Remedial Action (UMTRA) Project. The principal rationale for using plants would be to establish a dynamic system for controlling water balance. Specifically, vegetation would be used to intercept and transpire precipitation to the atmosphere, rather than allowing water to drain into the tailings and mobilize contaminants. This would facilitate compliance with groundwater standards proposed for the UMTRA Project by the Environmental Protection Agency.

The goals of the study were to (1) evaluate the feasibility of using vegetative covers on UMTRA Project piles, (2) define the advantages and disadvantages of vegetative covers, and (3) develop general guidelines for their use when such use seems reasonable.

The principal method for the study was to analyze and apply to the UMTRA Project the results of research programs on vegetative covers at other U.S. Department of Energy (DOE) waste management facilities. The study also relied upon observations made of existing stabilized piles at UMTRA Project sites (Shiprock, New Mexico; Burrell, Pennsylvania; and Clive, Utah) where natural vegetation is growing on the rock-covered surfaces. Water balance and erosion models were also used to quantify the long-term performance of vegetative covers planned for the topslopes of stabilized piles at Grand Junction and Durango, Colorado, two UMTRA Project sites where the decision was made during the course of this special study to use vegetative covers. Elements in the design and construction of the vegetative covers at these two sites are discussed in the report, with explanations of the differing features that reflect differing environmental conditions.

Findings

The principal finding of the special study is that vegetative covers are appropriate for use on topslopes of stabilized UMTRA Project piles. A properly developed plant community (and associated soil layer) will maintain a long-term control of the pile's water balance, greatly restricting the amount of water that may contact the tailings and transport contaminants to underlying groundwater. The vegetative cover will adapt to climatic change, will repair itself after severe disturbance (fire and drought), and will persist indefinitely with little or no maintenance. The plants will protect topslopes against sheetwash erosion, although resistance to gullies depends more on the overall pile configuration rather than on the vegetation and soil.

Another argument in favor of using vegetative covers is that they can be designed to prevent roots from penetrating radon barriers and degrading pile integrity, whereas the current rock covers are sometimes susceptible to invasion and disruption by the unwanted volunteer growth of deep-rooted trees and shrubs.

The principal impediment to the broader use of vegetative covers on the UMTRA Project is a lack of precision in the ability to quantify performance with respect to water balance and gully formation. Efforts are proceeding rapidly throughout the scientific community to upgrade the effectiveness of hydrologic models and apply them to the design of waste impoundments. Discussions are underway with the Nuclear Regulatory Commission to clarify their expectations regarding the erosion resistance of vegetated surfaces. These activities should be the emphasis of continuing efforts to use vegetative covers on the UMTRA Project.

These concerns may be resolved in the near future by using vegetative covers in combination with other cover components that facilitate performance. For instance, Claymax^R, a bentonite clay layer sandwiched between geotextiles, may be placed under the soil as additional protection against the infiltration of water into the tailings, and erosion-resistant rock may be placed under the soil to prevent breaching of the tailings impoundment. However, the additional expense of these conservative measures may be avoided if the performance of the vegetative cover can be demonstrated to the satisfaction of reviewing agencies.

The report provides several design concepts that may be used for vegetative covers on stabilized piles. However, it is critical that certain elements in the cover (e.g., soil type, soil thickness, plant species, and surface treatments) be tailored to the environmental conditions at each site. This will assure that the vegetation community establishes itself quickly, uses the maximum amount of water, resists disturbance, and persists indefinitely (i.e., is a "climax" community). If the site-specific elements of a vegetative cover are optimized, then such a cover is highly promising as a reliable and economically feasible method for stabilizing tailings piles and protecting the underlying groundwater.

1.0 INTRODUCTION

A series of special studies was commissioned in March 1988 to investigate approaches for complying with the proposed U.S. Environmental Protection Agency (EPA) groundwater regulations on the Uranium Mill Tailings Remedial Action (UMTRA) Project. One proposed approach has been to establish vegetation on the stabilized piles. The principal rationale is to use the ability of plants to transpire water, thereby restricting the amount that may percolate into the tailings and mobilize contaminants. Secondly, plants will stabilize the soil, though not as reliably as riprap, against erosion by wind and water. Thirdly, plants may invade the covers of UMTRA Project piles naturally, making it more appropriate to accommodate rather than resist this tendency, thereby averting the need to remove deep-rooted plants as part of an active surveillance and maintenance program.

1.1 PURPOSE AND SCOPE

The purpose of the special study on vegetative covers has been (1) to evaluate the feasibility of using plants for stabilizing UMTRA Project piles, (2) to define the advantages and liabilities of a vegetative cover, and (3) to develop general guidelines for the development of a vegetative cover in those situations where such an approach seems reasonable.

Section 2.0 describes the methods used to evaluate the applicability of vegetative covers to the UMTRA Project, and to gather information relevant to the implementation and performance of such a cover.

Section 3.0 evaluates the applicability of vegetative covers in terms of the prevention of biointrusion, regulation of water balance, and stabilization against erosion. The report includes a fairly extensive discussion of biointrusion that has been observed and that may be expected on covers with rock overlying soil, because the susceptibility of riprap to invasion by plants is an important element in the decision of whether to use a vegetative cover.

Section 4.0 describes the vegetative covers that are planned for two UMTRA Project sites--Grand Junction and Durango, Colorado--with a comparison of design features that differ between the sites because of their differing environments. Section 5.0 presents the results of efforts to quantify the long-term performance of the vegetative covers at the Grand Junction and Durango sites using hydrologic and erosion models. Section 6.0 provides a summary and recommendation for future work.

1.2 DEFINITION OF A VEGETATIVE COVER

Before proceeding, it is important to define what is meant by a vegetative cover. Two components are fundamental: (1) a layer of soil that serves as a rooting medium and moisture reservoir, and (2) a plant community that is established based upon its maximal degree of adaptation to the local environment, its resistance to disturbance, and its ability

to meet performance objectives for controlling water balance and preventing erosion. Features may be applied such as rock mulches on top of the cover and cobble biobarriers beneath the soil layer to enhance durability and performance; these will be described later in this report.

Figure 1.1 illustrates the principal components of a vegetative cover as it might be used on a stabilized tailings pile.

FIGURE 1.1
SIMPLIFIED DIAGRAM OF VEGETATIVE COVER

It should be emphasized that the term "vegetative cover" does not refer to a layer of soil that is placed on top of tailings and allowed to revegetate naturally. A soil cover will eventually be populated by a climax plant community with the desired transpirational capacity (ability to control water balance) and resistance to disturbance; however, hundreds of years may pass before this happens, depending upon the quality and thickness of the soil. A vegetative cover is one in which the soil and plants have been explicitly selected for their combined ability to protect the interred waste, and the cover has been constructed in such a way as to assure the rapid establishment of a stable and self-perpetuating plant community.

2.0 METHODS

The principal method used in this study has been to review the literature related to the revegetation of mill tailings impoundments and similar waste facilities, beginning with the results of research performed on behalf of the UMTRA Project in 1980 by Pacific Northwest Laboratories. Information on the general science of land reclamation--the stabilization and revegetation of disturbed surfaces--has also been of value.

A number of personal communications and site visits have contributed to the study. Foremost were visits to Los Alamos National Laboratories and Pacific Northwest Laboratories, both of which have extensive research programs on the design and performance of vegetative cover systems. A visit was also made to the research facility of the Nuclear Regulatory Commission (NRC) in Beltsville, Maryland, for low-level waste disposal. Personal contact was especially important in understanding the results of these research programs, because many of the studies have only been underway for a few years. This means that many of the results are preliminary and as yet unpublished in the open literature.

The Durango and Grand Junction, Colorado, UMTRA Project sites were also visited as part of the development of vegetative covers, and several officials and experts were consulted in Colorado for their insights on how these covers should be implemented. The completed pile at Shiprock, New Mexico, was visited twice in mid-summer 1988, and numerous plants were carefully unearthed to observe their rooting behavior relative to the various cover components such as the rock, filter layer, and radon barrier. The stabilized piles at Burrell, Pennsylvania, and Clive, Utah (under construction), were also visited.

The study also looked at natural ecological and environmental phenomena for their potential applicability to the vegetative cover.

Finally, engineering calculations were performed and hydrologic models were employed to address the design, implementation (including cost), and performance of vegetative covers under various circumstances.

3.0 APPLICABILITY

This section is a discussion of the ability of vegetative covers to satisfy the requirements of the UMTRA Project. These requirements are stated in a series of design objectives in "Design Criteria for Stabilization of Inactive Uranium Mill Tailings Sites" (DOE, 1983). Relevant to the vegetative cover are the following:

- o Design controls to be effective for up to 1000 years, to the extent reasonably achievable, and in any case for at least 200 years.
- o Design controls that will require minimum maintenance.
- o Prevent inadvertent human intrusion and discourage plant and animal intrusion.
- o Ensure that existing or anticipated uses of ground and surface water are not adversely affected.

The protection of groundwater has recently become of primary importance as a result of new standards proposed by the EPA. The proposed groundwater standards were the impetus for a comprehensive series of special studies, of which this was a part.

The ability of a vegetative cover to satisfy the above objectives can be addressed in three elements--biointrusion, water balance, and erosion protection--each of which is addressed below.

3.1 PREVENTION OF BIOINTRUSION

Plants and burrowing animals can disrupt the integrity of a stabilized pile by creating channels through the radon barrier that would serve as conduits for radon emanation and moisture influx. Ultimately, organisms may utilize these channels to transport the tailings or their hazardous constituents to the surface, from which they may be dispersed. The various release scenarios are discussed in the "Technical Summary of the UMTRA Project Technology Development Program (1980-1984)" (DOE; 1985). The discussion of biointrusion in the technology development summary is concluded with the assertion that:

In practice...a substantial cover thickness of rock riprap on the top and sides of the pile will satisfy requirements for the control of animal burrowing and root penetration.

This assertion has not proven entirely correct. Observations of stabilized piles at the Burrell, Shiprock, and Clive sites indicate that riprap-covered surfaces may be invaded by plants. Numerous forbs (herbaceous annual plants) and several trees were growing on the Burrell and Shiprock piles during site visits in 1988, approximately two years after completion of construction. A few shrubs are growing on the Clive pile, which is still under construction.

3.1.1 Observations of volunteer plant growth on the Shiprock pile

Plate 1 is a series of photographs taken on August 9, 1988, of plants on the Shiprock pile, most of which were of three species: summercypress (Kochia spp.), russian thistle (Salsola kali), and saltcedar (Tamarix pentandra). The first two are large annual tumbleweeds that die each autumn, break free of their taproots, and disperse downwind. The latter is an aggressive phreatophyte that forms dense thickets along southwestern waterways.

Plate 2 portrays roots that were unearthed during the August 9 visit to the pile. Most of the summercypress and tumbleweeds were less than two feet tall and their root systems penetrated only to the bottom of the filter layer, at which point their progress was apparently impeded by the underlying compacted radon barrier. Some of these annual weeds were more than six feet tall and their large roots penetrated a short distance into the radon barrier.

Most significant to the issue of biointrusion were the twelve saltcedars growing on the pile, ranging between five and 12 feet tall. This growth appears to have occurred entirely within the 1988 growing season (which was an unusually wet one), because the pile was surveyed during the spring of 1988 for saltcedars and none were found, even though they would have been quite conspicuous before the annual plants began to cover the surface.

The roots of a saltcedar excavated at the Shiprock pile on August 9 indicated that significant intrusion into the radon barrier had occurred. Although the principal (tap) root was diverted horizontally approximately five inches below the upper surface of the radon barrier, at least one tributary root advanced straight down. The extent and pattern of root development after a single growing season suggests that deeper penetration of the radon barrier may occur in the future.

A follow-up visit to the Shiprock pile was made on August 30, during which a vegetation map was prepared and the roots of a second saltcedar (the largest on the pile) were excavated for observation. The rooting behavior was quite similar to that observed for the saltcedar that had been excavated on August 9. Most roots extended laterally a few inches beneath the upper surface of the radon barrier; however, at least two roots penetrated downward at least one foot into the radon barrier, beyond which it was impossible to dig without greatly enlarging the hole.

The observations at the Shiprock, Clive, and Burrell sites (root studies were not performed at the latter two sites) indicated that the surface layer of riprap at these sites may not be effective in preventing invasion by plants. Seeds had either been deposited between the interstices of the rocks, or had been present in the soil used as a filter layer or radon barrier. Once present, the seeds germinated and the plants flourished, consistent with the predictions in the technology development summary (DOE, 1985) that:

rock covers may enhance vegetation establishment and growth by providing favorable microsites for seed germination and by reducing evaporation, thus providing more water for plant growth.

The concern at these sites is that plant roots will gradually alter the radon barrier to the point that radon emanation and moisture infiltration will be greatly increased. The risk that roots will penetrate all the way to the tailings is largely dependent on the characteristics of the radon barrier. Roots tend to penetrate less deeply in clayey soils than in sandy soils, unless the clay is permeated with large cracks (Foxy et al., 1984). Figure 3.1 shows the cumulative percentage of roots reaching various depths in a natural clay soil. Penetration depths should be somewhat restricted at the Shiprock, Clive, and Burrell sites because the soils have been highly compacted, which will at least temporarily impede root advancement.

FIGURE 3.1
CUMULATIVE PERCENT FREQUENCY OF ROOTING DEPTH
AND LATERAL EXTENSION OF PLANTS
GROWING IN ADOBE CLAY (FROM FOXX ET AL., 1984)

3.1.2 Biointrusion hazard associated with rock-over-soil cover designs

Any cover design with rock over soil will have some potential for invasion and establishment of volunteer plant species. The degree of biointrusion hazard is related (1) to local environmental characteristics and (2) to anticipated pile characteristics. Table 3.1 lists environmental characteristics and provides a relative

Table 3.1 Environmental characteristics and bioinvasion risk scores for UMTPA Project disposal sites

Biotic environment	Notes	Score	FCT	LKV	CAN	LOW	BOM	SPK	RVT ^b	GUN	NAT	SRK	MAY	DUR	GRJ	RFL	SLC	GRN	AMB	SHP	TUB	HAT
Nearby deep rooted plants	(1)	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4
Nearby large trees	(2)	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4
Prairie dog colonies nearby		4	0	0	0	0	0	0	0	0	4	0	0	0	4	0	0	0	0	4	0	0
Humid to subhumid climate	(3)	3	3	0	3	3	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Long to moderate growing season	(4)	3	3	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Deep or rich top soil	(5)	3	0	0	0	0	3	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Burrowers nearby	(6)	2	2	2	2	2	2	2	2	2	0	2	2	2	0	2	2	2	2	2	2	2
Semiarid climate	(3)	2	0	2	0	0	2	2	0	2	2	2	2	2	0	2	2	0	0	0	0	0
Moderate growing season	(4)	2	0	2	2	0	0	2	2	0	2	2	2	2	2	2	2	2	2	2	2	2
Moderate to shallow topsoil	(5)	2	2 ^a	2	2	2 ^a	0	2	2	2	2	2	2	2	2	2	2	0	2	0	0	0
Predominately small shrub vegetation		2	0	2	0	0	0	2	2	2	0	0	2	0	2	0	2	2	0	2	2	2
No burrowing animals nearby		1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Arid climate	(3)	1	0	0	0	0	0	0	1	0	0	0	0	0	1	0	0	1	1	1	1	1
Short growing season	(4)	1	0	0	0	1	1	0	0	1	0	0	0	0	0	0	0	0	0	0	0	0
Poor or no top soil	(5)	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0	1	1	1
Predominately grass vegetation		1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0	0	0
Total			18	14	17	16	16	14	13	13	22	16	14	16	15	16	14	12	12	16	12	12

^a Assume site has moderate topsoil depth.

^b Riverton tailings to be moved to Gas Hills site and there is no information on weather and vegetation at Gas Hills site in EA. Ranking of this site is based on general knowledge of the area.

NOTES:

- (1) Phreatophytes (willows, saltcedar, mesquite, cottonwood) and large shrubs (four-wing salt bush, creosote, big sage).
- (2) Pine, fir, elm, pinyon, etc.
- (3) Humid climate to subhumid, 20 or more inches per year; semiarid climate, 10-20 inches per year; arid climate, less than 10 inches per year.
- (4) Long season, 7-8 months; moderate season, 5-6 months; short season, 3-4 months.
- (5) Deep topsoil or 'A'-horizon is 18 inches or more.
- (6) Rodents and rabbits.

High risk score: ≥18; MAT, FCT

Moderate risk score: 14 TO 17 CAN, LOW, BOM, SRK, DUR, RFL, SHP, GRJ, LKV, SPK, MAY, SLC

Low risk score: ≤13; RVT, GUN, GRN, AMB, TUB, HAT

score for the potential biointrusion hazard at each of the 24 UMTRA Project sites based on information in the environmental documentation and observations by Technical Assistance Contractor (TAC) personnel visiting the sites. The score for each factor is based on a subjective evaluation of the importance of that factor in contributing to the likelihood of disruption of a stabilized pile by a biological agent. A score of four was given where the hazard was high; one where the hazard was low. Sites with the highest hazards are those with relatively moist climates and nearby deep-rooting trees.

Table 3.2 describes characteristics of a rock-over-soil cover design that may be evaluated in judging the likelihood of invasion by plants onto a stabilized pile. The table suggests a number of options that may be used to resist plant invasion onto a pile with this type of cover. For instance, a lower risk may be achieved by providing a greater depth of rock on the surface, using smaller rocks, or using a soil beneath the rock that is inhospitable to the germination and growth of plants. The depth of rock required to deter plant invasion depends on rock size, climate, and properties of the underlying soil. A test plot on the Grand Junction tailings pile covered in 1980 with an 18-centimeter (cm) thick layer of two-cm diameter washed gravel (Beedlow and Hartley, 1984) was still devoid of vegetation in 1988. However, a comparable thickness of larger diameter rocks at Shiprock and Burrell did not preclude volunteer growth.

Volunteer growth will also be reduced if the soil underneath the rocks has unfavorable chemical or physical properties. Saline groundwater was used as a moisture conditioner at the Clive pile with the result that the soils of the filter layer and radon barrier are quite saline and presumably somewhat inhibitory to plant growth. As of September 15, 1988 (approximately two years after completion of the observed section of the cover), a few small shrubs were reportedly growing on the pile, although their long-term viability remains to be seen.

A short-term but highly reliable method for preventing volunteer growth on a rock-over-soil cover would be to use time-released herbicides (Burton et al., 1985). For instance, a Typar^R BiobarrierTM could be placed immediately above the radon barrier. This system consists of a Typar landscape fabric dotted with time-release pellets of the herbicide Treflan^R, which inhibits root elongation. Manufacturers claim an effectiveness of up to 100 years for this product, which is commercially available at slightly more than two dollars per square foot. Appendix A is a short description of the Typar Biobarrier provided by its manufacturer.

3.1.3 Prevention of root penetration with a cobble biointrusion barrier

A buried layer of cobbles (one or more inches in diameter) has been shown to greatly reduce root penetration and other forms of

Table 3.2 Characteristics related to the potential for plant invasion onto a pile with a rock-over-soil cover design

Element	Higher risk conditions	Lower risk conditions
1. Rock	<ul style="list-style-type: none"> o Large rock of 8 inches or greater with well-sorted sizes and large interstices o Thin layer of only 3 or fewer particles deep o Design or environment that encourages eolian deposition o Poorly drained, high water retention (too many capillary pores) 	<ul style="list-style-type: none"> o Small rock (resulting in higher temperatures and small discontinuous voids); less than 6 inches diameter o Thick layer of rock with 4 or more particles deep or at least 15 inches deep o No eolian deposition o Well drained or absent
2. Bedding underlying rock cover	<ul style="list-style-type: none"> o Absent, allowing infiltration of moisture into radon barrier 	<ul style="list-style-type: none"> o Present, encouraging rapid lateral drainage
3. Restrictive layer (e.g., Claymax)	<ul style="list-style-type: none"> o High shrinkage, limit clay content (greater cracking potential) o High optimum moisture content of Proctor design o Susceptibility to freeze/thaw weathering 	<ul style="list-style-type: none"> o Low shrinkage, limit clay content (lower cracking potential) o Low optimum moisture content of Proctor design o Protected from freeze/thaw weathering o Highly saline or sodic soil
4. Radon barrier		

biointrusion into interred waste (Hakonson, 1985; Cline et al., 1980). Figure 3.2 depicts observations reported in Cline et al. (1981) of roots and animal burrows in soil, above a simple biobarrier. The principal factors that impede root penetration are the lack of capillary pores and the presence of interstitial air spaces. This layer may be considered a capillary break. Downward extension of the roots in Figure 3.2 occurs only where soil fines have filtered into the interstices, indicating that it is important to keep soil out of the biobarrier to ensure long-term resistance to root penetration. It is also important to keep the voids free of water. Therefore, biobarrier designs for the UMTRA Project should have choked rock or a geotextile along the top surface to resist soil infiltration, and should have a high-permeability drain along the bottom to assure rapid movement of water out of the barrier. A drain layer may not be necessary if the biobarrier is on a steep enough slope that water will quickly move laterally off the surface of the underlying radon barrier.

Preliminary cover designs for proposed waste isolation cells at Los Alamos National Labs (Hakonson, 1988) and the Hanford Reservation (Waugh, 1988) incorporate cobble biobarriers of a meter or more in thickness. This thickness is greater than should be necessary for the UMTRA Project because uranium mill tailings are less hazardous and the design life is less than for the Hanford program (with a 10,000 year performance requirement). The TAC position on biointrusion is that a biobarrier thickness of greater than one foot is impractical over the large surface areas of stabilized UMTRA Project piles. Instead of producing a thick biobarrier, the approach will be to construct an efficient layer in which interstices remain free of soil and water, and any given root will be obstructed by at least two voids between the overlying soil and underlying waste. Rocks in the barrier will have a minimum diameter of one inch and a maximum diameter of less than one-half the total layer thickness. With these specifications, few if any roots will reach the tailings.

3.1.4 Compatibility with a vegetative cover

The cobble biobarrier described above has generally been used beneath a vegetative cover consisting of soil and selected plant species. An additional strategy to prevent root penetration is to provide a sufficiently large region (thickness of soil) with favorable water relations and nutrient capacity that plants will not be perpetually stressed, hence will not be as likely to extend their roots into an unfavorable medium (the biointrusion layer) for water and nutrients. The same logic applies to burrowing animals in that prairie dogs or ground squirrels will not attempt to move into a rocky, unfavorable medium if a generous layer of favorable soil is available.

The decision on whether to underlay the soil of a vegetative cover with a loose cobble biointrusion layer will depend on the

FIGURE 3.2

DIAGRAM OF ANT TUNNELS, POCKET MICE TUNNELS, AND RUSSIAN THISTLE ROOTS THAT WERE OBSERVED DURING THE EXCAVATION OF LOOSE ROCK BIOBARRIER STUDY (FROM CLINE ET AL., 1981)

local climate, the properties and thickness of the soil used as a rooting medium, and the rooting characteristics of the plant community anticipated on the cover. Table 3.3 lists factors that may be considered in judging the biointrusion hazard (specifically, the likelihood that roots will penetrate the radon barrier) of a vegetative cover with and without a biointrusion layer. In some cases, it may be possible to place a thick layer of soil with the appropriate properties to encourage the growth of shallow-rooted species. For instance, at the UMTRA Project site at Falls City, Texas, where suitable rock for a biobarrier is not locally available, a three-foot-thick layer of clay-rich soil may be applied over the radon barrier and seeded with local range grasses, which should competitively preclude the invasion of the vegetated surfaces by deep-rooted trees such as mesquite. The relatively humid climate in central Texas makes this possible by supporting a more or less uninterrupted cover of perennial grasses (on the appropriate soil). The formulation of this approach for the Falls City UMTRA Project site is still in progress and, in every case, the decision to establish a vegetative cover without an underlying biointrusion layer should only be made after a thorough investigation of the local climate, soils, and vegetation. This will insure that potential biointrusion scenarios are accounted for and that the cover may be engineered to favor the plant community that will minimize the likelihood of root penetration of the radon barrier.

Figure 3.3 is a summary comparison of factors related to biointrusion for vegetative versus rock covers.

Most of the following discussion will assume that loose cobble biobarriers will be used in combination with vegetative covers; it remains to be seen whether such a system will resist plant invasion and root penetration even when covered by additional layers of rock, rather than by soil. In any case, one of the strongest arguments in favor of the future use of vegetative covers on UMTRA Project piles is that native vegetation will eventually invade and degrade the integrity of covers with the traditional rock-over-soil stratigraphy; therefore, future pile designs should include covers that accommodate vegetation and utilize its ability to regulate water balance.

3.2 CONTROL OF WATER BALANCE

Vegetative covers have long been advocated for certain applications in waste management because of the ability of vegetation to control water balance. Specifically, the vegetation removes infiltrating precipitation by transpiring the moisture back into the atmosphere, greatly reducing the amount of water that may drain into underlying wastes and subsequently transport contaminants to groundwater. In research performed for the UMTRA Project by Pacific Northwest Laboratories, Beedlow and Hartley (1984) recommended vegetative covers over purely rock covers for most UMTRA Project piles because:

- ROCK COVER -

ROCK LAYER: the cleaner the better (for resisting biointrusion)
 ROCK LAYER: the thicker the better (for resisting biointrusion)
 ROCK SIZE: the smaller the better (down to 5 mm)
 FILTER LAYER: thickness does not matter
 FILTER PERMEABILITY: the more permeable the better
 RADON BARRIER: the thicker the better
 BARRIER TEXTURE: the more clayey the better

- VEGETATIVE COVER -

VEGETATION: the grassier the better
 ROOTING MEDIUM: the thicker the better
 ROOTING MEDIUM: the loamier the better
 BIOBARRIER: the fewer capillary pores the better
 FILTER LAYER: the more permeable the better
 RADON BARRIER: the thicker the better
 BARRIER TEXTURE: the more clayey the better

FIGURE 3.3
 FACTORS IN THE EVALUATION OF COVER COMPONENTS FOR BIOINTRUSION HAZARD

Table 3.3 Characteristics related to the likelihood of biointrusion in a stabilized pile with a vegetative cover

Element	Higher risk conditions	Lower risk conditions
Biota	<ul style="list-style-type: none"> o Large trees or deep-rooting shrubs (e.g., phreatophytes) o Long growing season o Humid to subhumid climate o Colonies of burrowing animals (prairie dogs, gophers) 	<ul style="list-style-type: none"> o Predominantly grassy vegetation in vicinity o Little or no topsoil in region o Short growing season o Arid or semiarid climate
Cover Design		
1. Topsoil	<ul style="list-style-type: none"> o Not underlain by a biointrusion barrier o Less than optimal thickness as predicted by water-balance models o Poor moisture and nutrient relations (too much sand or clay) 	<ul style="list-style-type: none"> o Underlain by biointrusion barrier o Optimal thickness for moisture retention o Favorable moisture and nutrient relations (loamy soil)
2. Biointrusion barrier (choke rock cap and poorly graded cobbles)	<ul style="list-style-type: none"> o Absent o Not properly drained by conductive and restrictive layers o Poor choke rock design o Rock size (and pore size) too small to allow adequate void air space o Layer too thin (fewer than two interstitial voids along the path of a given root) 	<ul style="list-style-type: none"> o Well drained with adequate choke rock design o Rock size of two inches or larger o High quality rock with low percentage of absorbency
3. Conductive (drain) layer (also called filter bedding)	<ul style="list-style-type: none"> o Low permeability o Too thin 	<ul style="list-style-type: none"> o High permeability
4. Restrictive layer (e.g., Claymax and/or radon barrier)	<ul style="list-style-type: none"> o High permeability o Susceptible to freeze-thaw action or cracking 	<ul style="list-style-type: none"> o Low permeability o Insulated from or resistant to freeze-thaw action or other weathering

A plant community consisting of species adapted to the environment is dynamic; it is capable of responding to changes in climate. By increasing and decreasing in response to available soil moisture, vegetation can be an efficient and reliable "pump" for removing excess soil moisture.

Whereas

Unvegetated rock covers reduce soil water loss, which could lead to accumulation and drainage from tailings piles... Rock covers can be engineered to drain laterally; these must remain functional for the design life of the impoundment. Such engineering, while certainly feasible, is complicated by the need to allow for climate change and, inevitably, vegetation growth that could change the drainage characteristics.

The ability of plants to intercept and transpire moisture has resulted in programs to develop vegetative covers for waste disposal facilities at numerous DOE installations, including the Hanford Reservation (Adams and Wing, 1987), Idaho National Engineering Laboratory (Anderson et al., 1987), Los Alamos National Laboratories (Hakonson et al., 1987), and the NRC research facility in Beltsville, Maryland (O'Donnell et al., 1987).

All of the above programs are proceeding under the assumption that drainage through the cover can be reduced to near zero. This is accomplished by optimizing the thickness and properties of the rooting medium, creating a soil layer that will store moisture that infiltrates during the dormant season until the moisture can be transpired back to the atmosphere during the growing season. The presence of a cobble biobarrier beneath the soil enhances moisture storage (thereby reducing drainage) because the absence of capillary pores in the biobarrier resists gravitational drainage unless the overlying layer becomes saturated.

Experiments with lysimeters and observations of natural systems by researchers at Hanford (Gee, 1987), Los Alamos (Hakonson et al., 1987), and the NRC research facility (O'Donnell et al., 1987) have confirmed that near-zero drainage can be achieved for short periods of time with a properly engineered vegetative cover. However, refinements in the design and long-term performance assessment of such covers are still needed and are top-priority in the research programs at these institutions.

A number of models have been used in the development and performance assessment of vegetative covers. Foremost are CREAMS, HELP, and UNSATV (Barnes and Rodgers, 1987; Gee, 1987; Hakonson, 1986, respectively). Figure 3.4 illustrates the results of a 20-year simulation with CREAMS in which evaporation runoff and seepage (percolation) are predicted as a function of increased thickness of the soil layer. Simulations using UNSATV were performed by Beedlow (1984) for hypothetical covers at the Grand Junction UMTRA Project site; Beedlow found that a vegetative cover with 40 inches of soil would have negligible drainage even in unusually wet years, whereas a rock cover would have up to 6 inches of drainage under the same climatic conditions.

FIGURE 3.4
PREDICTED AVERAGE ANNUAL HYDRAULIC VALUES AS A
FUNCTION OF COVER THICKNESS AT LOS ALAMOS.
CALCULATIONS BASED ON A CLAY LOAM COVER TOPSOIL AND
A 20-YEAR (1951-1970) PRECIPITATION RECORD AT
LOS ALAMOS, NEW MEXICO (FROM HAKONSON, 1986).

The TAC has evaluated these models for potential applicability to the UMTRA Project. Table 3.4 lists the various features of the models. The HELP and CREAMS models are based on water-balance considerations rather than more detailed soil-moisture movement theories. The UNSATV models treat soil-moisture redistribution within the soil column in a more rigorous manner, using a root-growth simulator to predict moisture extraction. None of the models currently incorporate all of the major phenomena needed to accurately simulate moisture movement through UMTRA Project covers, although they may be useful in making conservative predictions. These models are being continually upgraded, and it is recommended that the TAC continue to investigate ways to improve the utility of these models in developing and predicting the performance of cover designs.

Section 5.4 of this report illustrates the results of simulations and sensitivity analyses with HELP and CREAMS of cover performance at the Grand Junction UMTRA Project site.

Applicability of vegetative covers for controlling water balance

Vegetative covers can be an effective component for regulating water balance. The biggest question regarding the use of vegetative covers is the acceptability of the results of HELP or CREAMS modeling to reviewers at the NRC. This concern might be deferred at the Grand Junction and Durango UMTRA Project sites by the fact that the rooting medium may be underlain by Claymax[®], a layer of sodium bentonite sandwiched between two geotextiles that has a very low hydraulic conductivity. Claymax, in combination with an overlying drain/bedding layer, will presumably convert any drainage through the vegetative cover into lateral runoff, thereby protecting the tailings from moisture that could dissolve and transport contaminants. Alternatively, a geomembrane (thin layer of plastic or similar synthetic material) may be placed under the soil. This would have very low permeability, although the design life is uncertain.

If the NRC eventually accepts performance predictions using a model such as HELP or CREAMS, then Claymax or geomembranes would be unnecessary in pile designs with vegetative covers. On the other hand, considering the importance of groundwater protection and the cost of aquifer restoration, it may occasionally be advisable to include a redundant component for the control of water balance, even when the models predict that the vegetative cover will have a protectively low hydraulic conductivity over the long term. This redundancy would dispel concerns about the temporary disturbance of a vegetative cover due to fire, herbivory, or severe drought.

3.3 RESISTANCE TO EROSION

A vegetative cover is much less resistant to erosion than a rock cover and much more resistant than a cover of bare soil. Vegetation

Table 3.4 Comparison of features of some infiltration models with explicit vegetative transpiration terms

Feature	Model		
	HELP (Version 2)	CREAMS	UNSATV
Vertical unsaturated flow	Gross water balance-Darcian flow with free outflow (unit gradient), unsaturated hydraulic conductivity as function of water content (modified Brooks-Corey equation).	Gross water balance-Darcian flow analogue with approximate unsaturated hydraulic conductivity. For "breakpoint" precipitation, use Green-Ampt infiltration model.	Numerical solution of general unsaturated flow equation, with hydraulic conductivity and matrix potential as functions of water content.
Runoff	SCS Curve Method	SCS Curve Method - Green-Ampt infiltration model for "breakpoint" precipitation	None
Lateral drainage	Steady-state Boussinesq equation	None	Two dimensional: can account for lateral drainage.
Evapotranspiration	PET from modified Penman equation Soil evaporation calculated from plant interception and snow accumulation Transpiration calculated from LAI given by vegetative growth and decay model	PET from modified Penman equation Actual evapotranspiration calculated as in HELP For "breakpoint" precipitation, root extraction estimated, with root growth proportional to LAI	PET from Penman equation Drying evapotranspiration calculated by Thornthwaite-Mather method (as function of field capacity and wilting point) Vapor diffusion considered if soil surface dries out Plant roots treated as moisture sink, with root density specified by user

Note 1. Models selected from those previously applied to assessment of UMTRA Project or other DOE low-level waste disposal facilities.

Note 2. Features as described in and/or inferred from model documentation.

resists erosion by the following mechanisms (verbatim from Gray and Leiser, 1982):

Interception: foliage and plant residues absorb rainfall energy and prevent soil compaction from raindrops.

Restraint: root system physically binds or restrains soil particles while above ground residues filter sediment out of runoff.

Retardation: above-ground residues increase surface roughness and slow velocity of runoff.

Infiltration: roots and plant residues help maintain soil porosity and permeability.

Transpiration: depletion of soil moisture by plants delays onset of saturation and runoff.

3.3.1 Sheetwash erosion

The ability of vegetation to resist long-term soil removal by sheetwash or wind erosion was quantified by Beedlow (1984) in research for the UMTRA Project. Naturally vegetated landscapes around the 24 UMTRA Project sites were studied and long-term soil loss was predicted using the Universal Soil Loss Equation. Beedlow calculated that a maximum soil loss of 12.5 inches would occur over a thousand years on three percent slopes of 600 feet or less in length and that a maximum loss of 35 inches would occur on 10 percent slopes of 100 feet or less in length. Similar calculations were made by the TAC for proposed vegetative covers at the Durango and Grand Junction UMTRA Project sites; the results of these calculations, which considered episodes of vulnerability of the cover during initial plant growth and periodic disturbances, are presented in Section 5.2 of this report.

3.3.2 Gully erosion

Rock armor is the best material for stabilizing sideslopes and protecting UMTRA Project piles from gully erosion. However, Walters et al. (1986) conclude that:

Because the topslope will be relatively flat compared to the sideslope and also ringed by a parapet wall, rock riprap protection similar to that required for gullies should not be necessary....The topslope can be adequately protected by a vegetation cover or a combination of rock mulch and vegetation.

This assertion is based on the fact that the topslope would be elevated above the zone of inundation by a probable maximum flood

and that the base level for the topslope would be enforced by the parapet, meaning that no mechanism would be available for gullies to form. Because it is unlikely that gullies would form on topslopes with armored sideslopes, there has been very little research into ways of protecting against gully erosion on such surfaces or into ways of predicting the likelihood thereof.

The NRC has been working on a position paper and review plan for evaluating vegetative cover designs submitted for Title I and Title II sites. Excerpts from a preliminary draft have been provided to the TAC and Remedial Action Contractor (RAC). The NRC will accept the following technical approaches in reviewing proposed covers:

- o A detailed geomorphological study of the site and its surrounding area to establish the relationship between the watershed area, runoff rates, vegetation, slopes, and gully development.
- o A mathematical analysis to demonstrate that a gully on a given slope will not, as a result of the average annual precipitation, intrude into the tailings.
- o A mathematical calculation to determine the slope length required, for a given slope inclination, to develop a gully.
- o Calculation of the potential soil loss from vegetated and unvegetated slopes due to sheet wash erosion.
- o An empirical evaluation of the potential for the formation of deep gullies on soil sideslopes and soil perimeter dikes, with the objective of showing that even in the event of gully development the gully will not break through into the tailings.
- o Placement of rock beneath the soil to control erosion in the event of the development of a gully in the soil.
- o A rigorous cost-benefit comparison between the use of rock and soil covers in enhancing pile erosion protection.

The NRC does not demand that all of the above be done. They note that one or more of the above approaches may be needed to evaluate and confirm the anticipated performance of a particular soil cover. It is left to the judgment of the designer of the disposal cell to choose the combination of appropriate technical analytical methods to be used at a particular site.

3.3.3 Applicability to UMTRA

Given the current plan to use vegetative covers primarily on topslopes, there is generally little concern about soil loss to

sheet wash or wind erosion. Resistance of a cover to these forms of erosion can be enhanced if necessary by using a rock mulch of sufficient thickness to protect against raindrop impact, but not so thick as to retard the growth of desired plant species. In fact, such a mulch benefits plants by reducing moisture loss by evaporation and increasing moisture availability for transpiration. This increased transpirational capacity is valuable during episodes of heavy rainfall when many plants are needed to fully dewater the soil (and thereby prevent drainage.)

The perceived inability of a vegetated topslope to resist gully erosion is potentially an impediment to the use of vegetated covers on the UMTRA Project. The expense of constructing a vegetative cover is greatly increased if a gully-resistant layer of rock (larger than required for a biobarrier) must be placed beneath the soil. The TAC has proposed designs that will address this requirement without the continuous layer of erosion-resistant rock; these designs are illustrated in Section 4.1.

In any case, it is strongly recommended that further investigations be performed, and that negotiations with the NRC be continued, to explore alternatives to the use of such a rock layer, relying instead upon the pile's geomorphic configuration and upon the vegetation itself as elements to resist erosion.

3.4 SUMMARY REMARKS ON THE APPLICABILITY OF VEGETATIVE COVERS FOR STABILIZING UMTRA PROJECT PILES

The use of vegetative covers on topslopes will help fulfill the design objectives (DOE, 1984) listed at the beginning of this section.

Longevity: If locally adapted species are used in a favorable growing medium, then the vegetation will reproduce and the cover will be self-perpetuating. The plant community on the cover will renew itself after disturbance and will adapt to climatic change. If the cover is properly designed, the community thereupon will rapidly become part of the natural "climax" vegetation of the region.

Minimization of maintenance: A vegetative cover with a biointrusion layer will require less long-term maintenance than a rock cover that is perpetually being invaded by deep-rooted species, which may require removal. Some repair of rills may be necessary if severe rainfall occurs before plants are well established, and irrigation or reseeded might be required after extraordinary disturbances by fire or drought. Such scenarios are unlikely and a properly constructed vegetative cover should be maintenance-free (Rodgers et al, 1984).

Prevention of intrusion by organisms (including humans): The buried rock biobarrier will resist intrusion by plants and animals, and will be an impediment to the progress of humans digging with anything other than heavy equipment.

Protection of surface and groundwater: The primary attribute of a vegetative cover is its ability to transpire water and thereby minimize deep percolation and runoff.

In summary, vegetative covers offer great promise for widespread use on the UMTRA Project. There are no significant difficulties in constructing such covers, nor shortages of materials required therefore. The technology of selecting the correct soil, applying a favorable growing medium, preparing a seedbed, and establishing a self-perpetuating community is soundly based in the field of mine reclamation (Reith and Potter, 1986). The economics of a vegetative cover will depend in large part on the proximity of borrow sources for the required materials (soil and rock). If considerable depth of soil is needed for frost protection, then it becomes economically worthwhile to use that same soil as rooting medium. In any case, there are no elements of vegetative covers that result in greatly increased costs relative to all other design concepts proposed for the project.

As mentioned earlier, the principal impediments to the application of vegetative covers to the UMTRA Project are the lack of precision in the ability to demonstrate the performance of a cover with respect to water balance and gully erosion. Section 5.0 describes the efforts to quantify the performance of the vegetative covers planned for the Durango and Grand Junction sites. The UMTRA Project will greatly benefit from efforts to improve the modeling of water balance and prediction of gully hazard. Further, it is essential to continue negotiations with the NRC to improve their understanding of vegetative covers and clarify their expectations regarding the acceptability thereof.

4.0 IMPLEMENTATION

This chapter describes the steps involved in the development and construction of a vegetative cover. The process begins with the initial design of the pile to accommodate vegetation and resist biointrusion, and concludes with the establishment and subsequent monitoring of plants on the cover. Examples are drawn from two UMTRA Project sites, Grand Junction and Durango, where the current plans are to use vegetative covers for the topslopes of the stabilized tailings piles. These two sites have different environmental conditions that are reflected in certain characteristics of the vegetative covers planned at each site. Figure 4.1 is a sketch of the generic design for a vegetative cover, with some of the more conspicuous differences between the covers planned for Grand Junction and Durango listed below the sketch.

4.1 PILE MORPHOLOGY

The pile should be engineered so that slope angles of vegetated surfaces will be minimized to prevent runoff and sediment loss. Beedlow's (1984) calculations suggest that less than 30 cm of sediments will be removed over 1000 years from vegetated slopes of less than 10 percent. Angles of less than five percent are recommended for long slopes. Sediment loss will be at least partially compensated for by carbon fixation, the process whereby vegetation introduces solid (organic) matter to the surface litter layer and underlying soil.

The stabilized piles for both the Grand Junction and Durango tailings will have broad vegetated topslopes with steeper rock-covered sideslopes. This limits total pile area, while still providing shallow topslopes. The encompassing band of rock-covered sideslopes will partially protect the vegetated surface from fire and grazing by cattle.

Until the issue of gully erosion is resolved, it may be necessary on slopes exceeding one or two percent to underlay the soil with rock that is large enough to resist movement by gullies that might occur on the topslope or to protect the topslope against gully intrusion by some other means. Rock size (and cost) may be reduced by using alternative topslope configurations (see Figure 4.2). Alternatively, each drainage area might be contoured to concentrate flow during extraordinary precipitation events into channels that are armored with riprap. Figure 4.3 illustrates other design concepts that could be used to resist erosion of the topslope by gullying.

4.2 PREVENTION OF BIOINTRUSION

In most cases, a biobarrier of loose cobbles and choked rock should be placed under the rooting medium to protect the radon barrier from penetration by roots and burrowing animals. Section 3.1.4 describes those special cases, such as in Falls City, Texas, where it may be possible to engineer a vegetative cover that will favor only shallow-rooting species

ROOTING MEDIUM		
THICKNESS	24"	60"
SOIL TYPE	STONEY SILT LOAM	CLAY LOAM
TOPSLOPE	4%	1%
VEGETATION	SMALL SHRUBS AND GRASS	TALL GRASSES
COVERAGE	20%	80%

FIGURE 4.1
BASIC VEGETATIVE COVER DESIGN CONCEPT WITH FEATURES LISTED
FOR THE VEGETATIVE COVERS PLANNED FOR
THE STABILIZED PILES AT GRAND JUNCTION AND DURANGO

FIGURE 4.2
PERIMETER DIKE REMOVAL DISPOSAL CELL LAYOUT

- ① UPPER TOP LAYERS: FILTER, BIOINTRUSION BARRIER, SOIL, & VEGETATION
- ② LOWER TOP LAYERS: RADON & INFILTRATION BARRIER
- ③ GULLY EROSION INHIBITORS: ROCK BERMS OR DIKES
- ④ SIDESLOPE EROSION BARRIER: ROCK
- ⑤ TAILINGS & CONTAMINATED MATERIAL

- A INCLINED SLOPE: LENGTH LESS THAN CRITICAL TO INITIATE GULLY
- B FLAT SLOPE: NO GULLY DEVELOPMENT POSSIBLE

FIGURE 4.3
COVER DESIGN CONCEPTS FOR PREVENTION OF GULLIES

such as grasses and thereby preclude the need for a loose cobble biobarrier. Where a biobarrier is to be used, a minimum thickness of one foot should be adequate if the barrier is constructed as described in Section 3.1.3 of this report. Loose cobble biobarriers will be placed beneath the soil of the vegetative covers on the topslopes of both the Grand Junction and Durango piles.

No features are currently planned for the protection of sideslopes at Grand Junction and Durango against biointrusion, meaning that deep-rooting plants will have to be removed as part of surveillance and maintenance. An excellent approach to this problem is planned for the stabilized pile at Gunnison, Colorado (Figure 4.4), where steep riprap sideslopes will be underlain by random fill. Deep-rooting species are likely to invade these sideslopes, but their disruption of the pile integrity will be minimal.

4.3 SPECIES SELECTION

The goal is to establish a plant community with the highest potential productivity, hence capacity to transpire water, that the local climate and soils will support. High productivity will also result in rapid accumulation of organic matter. A high percentage of foliar cover will protect the underlying soil from the direct impact of raindrops, which may dislodge soil particles and initiate erosion.

If a vegetative cover is to be used at a site, then the various plant communities within a few miles of the site should be surveyed for that which might serve as a model for the community to be established on the stabilized tailings pile. Ideally, a community should be used that is associated with the most favorable edaphic characteristics (soil properties as related to vegetal growth); however, in some cases, this would mean that economically valuable soils (such as for agriculture) would have to be used, or that soils would have to be transported from a long distance away. Ultimately, the model community that is selected for a site will be one that can grow on the soil that is best for the project in terms of many factors, including availability, cost, and adverse impacts of removal from other possible uses.

The physiognomy (morphological structure) of the selected community will be closely emulated, and the species composition will be matched to the extent possible. In other words, if a high desert perennial grassland is judged to have the desired characteristics, then a similar community should be established on the stabilized tailings pile. However, the species may differ depending upon the availability of seed for cultivars (domesticated varieties) that have proven successful in local revegetation efforts.

Once a general community model has been selected, the species composition in the seed mix needs to be optimized relative to a variety of criteria such as drought hardiness, nutrient relations, and seasonality of water use. For instance, a blend of cool-season and warm-season grasses should be used to provide transpirational capacity over the longest time

SECTION A-A'

SECTION B-B'

FIGURE 4.4

PILE DESIGN FOR GUNNISON, COLORADO, THAT WILL PROTECT AGAINST BIOINTRUSION ON THE SIDESLOPES.

period each year. It is critical at each site that local reclamationists participate in these decisions.

A salt-desert shrub community will be used for the vegetative cover at the Cheney Reservoir disposal site for the Grand Junction tailings. This community, consisting of several shrub species and drought-tolerant perennial grasses, is dominant on the rocky soils along the gentle pediment upon which the tailings are to be placed. This community will tolerate the naturally saline soils and frequent dry years that are characteristic of the area.

A meadow-like community of robust perennial grasses will be used for the vegetative cover at the Bodo Canyon disposal site for the Durango tailings. Meadows of bluegrass, brome, galleta, and grama grass occur in pockets of relatively heavy soils (alluvial clay loams or eolian silt) throughout the region. This community will be highly productive, stabilizing against erosion and transpiring excess moisture. The grasses will temporarily resist invasion by deep-rooting species such as big sage, aspen, pine, and juniper. Ultimately, some trees and shrubs may invade the vegetative cover, although the underlying biointrusion layer will protect the radon barrier from root penetration and subsequent degradation.

4.4 ROOTING MEDIUM

The most important component of the vegetative cover is the soil, because this must support the growth and reproduction of many generations of plants. The soil provides mechanical support for plant roots, but, more importantly, it stores water and nutrients. Ideally, the soil will store all the water that falls on the cover until that water may be transpired by plants. This may be achieved by providing an adequate thickness of soil as suggested by water-balance models such as HELP, CREAMS, or UNSATV.

As mentioned in Section 4.3, the best possible soil should be used for the cover in terms of edaphic properties, although factors such as availability and cost must be considered. The most important edaphic property is texture, which affects the storage capacity for and availability of water in the soil. Specifically, the soil should have a relatively even mix of particle sizes (sand, silt, and clay), and hence should be a "loam" (Brady, 1974). Ideally, the soil will retain 30 percent or more of its weight in water at field capacity, but will release all but 10 percent to plants at wilting point. Organic matter can be added to increase water storage capacity without raising the wilting point.

It is also important to avoid soils with unfavorable chemical properties such as a lack of nutrients (particularly trace metals, which are not easily replaced in a fertilization program) or a high concentration of sodium or phytotoxic metals. Such problems are almost always evident in the plant communities growing on these soils in their natural setting.

Many of the principles for handling the soil may be adapted from the field of mine reclamation. For instance, the physical and chemical properties of the soil must be protected during collection, transport, stockpiling, and redistribution. Stockpiled soil must be well drained to prevent anaerobic chemical processes that introduce sulfides and other inhibitory agents. Ideally, many of the microscopic organisms and their spores will survive in the soil until its redistribution on the cover, as these will accelerate the early growth of plants and eventual establishment of a stable community (Whitford and Elkins, 1986).

The bulk density of soil must not be allowed to exceed 1.6 grams per cubic centimeter (g/cm^3) during redistribution, so periodic ripping may be appropriate. It is especially important to establish proper tilth in the upper six inches, because this zone will be the seedbed for germination and early growth. Fertilizer may be applied and disked into the seedbed to encourage early growth. A number of surface treatments such as mulching with straw or pea gravel may enhance plant growth, while also protecting the soil against erosion during the initial unvegetated period.

The rooting medium for the Grand Junction cover will be a stoney silt loam salvaged from the Cheney Reservoir disposal site. The soil layer will be 24 inches thick, which should prevent drainage under average conditions (see Section 5.4). The soil for the Durango cover will be a clay loam, also borrowed from the disposal site. The thickness of the soil layer, which has been determined based on freeze/thaw considerations, has been reduced to three feet. Some moisture may drain through this layer, but will be diverted laterally along the drainage layer over the underlying Claymax, which has a very low hydraulic conductivity.

4.5 SEEDING AND PLANTING

The cover should be seeded soon after soil placement in order to minimize exposure of the soil to potential erosion. Ideally, soil placement will be completed shortly before the annual rainy season, because this is the best time to seed for maximum germination and seedling survival. Seed may be applied with a range drill, which injects each seed a predetermined depth into the soil, thereby protecting against removal by birds or early desiccation.

The Durango cover will be drilled with a seed mix of perennial range grasses that are widely used for local reclamation and habitat improvement projects.

The Grand Junction cover will also be drilled with seeds of range grasses, but with seeds of several salt-desert shrubs included as well. Additionally, 1500 nursery-grown shrubs (mostly of the species shadscale) will be transplanted onto the cover. The use of containerized or bare-root stock at this site reflects the anticipated difficulty of establishing plants and the slow growth rates in the area's dry climate and less-than-ideal soils. The containerized plants will help bypass the initial period of vulnerability to erosion and will serve as "nurse plants" for the germination and early growth of other species. The

planting program at Grand Junction will greatly accelerate the process of natural succession, which leads to the establishment of a stable plant community. Such measures are not so important at Durango, where the higher precipitation and more favorable soil will support an acceptably rapid rate of natural succession and plant establishment.

4.6 ROCK MULCH

A thin layer of rocks on the surface of a vegetative cover can protect against erosion and improve water relations (Waugh, 1988; Beedlow, 1984). A rock mulch is generally appropriate for arid environments, where vegetation alone may be inadequate to stabilize the surface. The surface of the vegetative cover on the topslope of the stabilized pile at the Grand Junction disposal site will be covered with a rock mulch that is intended to emulate the desert pavement that occurs naturally on pediment where the pile is to be constructed. The observed coverage of about 25 percent rock (Reith, 1988) appears to be an important agent in stabilizing the two-to-five percent slope of the 10,000 year-old pediment against gullies and other kinds of erosion (Lindsey, 1988).

4.7 IRRIGATION

The need for supplemental water depends on both the aridity and annual variability of the local climate. In relatively moist climates such as at the Durango site, there is enough precipitation in almost any year to support the germination and early growth of plants; hence irrigation is not essential. In arid environments with annually variable precipitation, such as at the Grand Junction site, sufficient moisture for plant reproduction is available only rarely; thus, irrigation is needed to assure that plants germinate soon after soil placement, and that the cover is not vulnerable to erosion for months or even years.

The goal of the irrigation program should be to provide enough moisture to stimulate germination and prevent seedling mortality, but not so much as to encourage community dependency. Infrequent deep waterings will wet the entire soil profile, causing plants to extend their roots all the way down to the top of the biointrusion barrier. This will make plants more tolerant to drought and will assure a more complete transpirational removal of water during the cover's long-term performance. Solid set sprinkler irrigation systems have proven effective for revegetating large areas in mine reclamation.

The timing and amount of irrigation should reflect the amount of rain that falls during the first growing season. It is anticipated that about 10 inches will be adequate for the Grand Junction site. Irrigation after the first growing season is not planned, and may be applied as part of surveillance and maintenance if a severe drought destroys the cover. No irrigation is planned for the Durango site.

4.8 PERFORMANCE MONITORING

Elaborate standards have been developed for evaluating the success of revegetation relative to conditions in the surrounding environment (Fischer, 1986). To some degree, these may be applied in the form of comparisons of leaf area, biomass, and other vegetal parameters between the community on the stabilized pile and the nearby model community. However, the performance of the cover system with respect to water balance is more important. Accordingly, the rooting medium should be equipped with psychrometers or neutron-probe access ports to enable conscientious monitoring of water status throughout the soil profile (this should be done in any case to monitor and dictate irrigation practices). The vegetative cover may be considered successful if the deep layers of the rooting medium are rarely, if ever, saturated. This indicates minimal seepage of moisture to the underlying layers.

If the system is failing (allowing seepage), additional rooting medium may be added to enhance the layer's reservoir capacity, although this means that planting must start anew. The vegetal productivity cannot be upgraded beyond the maximum supportable by the local climate.

5.0 PERFORMANCE ASSESSMENT

A number of methods are available for predicting the long-term performance of a vegetative cover with respect to erosion and water balance. Predictions are essential to demonstrate compliance with the EPA standards (40 CFR 192) for longevity and groundwater protection and to gain NRC concurrence for a proposed design. However, as mentioned earlier, the lack of precision and widespread acceptance of performance-assessment methods for vegetative covers is a potential impediment to the wider use of vegetative covers in the UMTRA Project. For the moment, it is necessary to use very conservative models for calculating long-term soil loss to sheet wash and rill erosion and for predicting equilibrium water-balance conditions, and to use very conservative designs as an assurance against gully formation. However, these are areas of emphasis for ongoing efforts on the UMTRA Project and other DOE waste management programs with the result that less conservative, more realistic methods will gradually become available for use in designing and demonstrating the performance of vegetative covers.

This chapter describes the results of current efforts to assess the performance of vegetative covers proposed for the topslopes of stabilized piles for the Grand Junction and Durango tailings. These are subject to considerable refinement as the designs are finalized and compliance plans are prepared for the two sites.

5.1 METHODS FOR DETERMINATION OF SOIL LOSS

Two mathematical methods for determining soil loss are the Universal Soil Loss Equation (USLE) and the Modified Universal Soil Loss Equation (MUSLE). Both are based on regression models and are empirical formulas for predicting soil losses due to sheet or rill erosion. The major factors that control soil erosion rates, such as the type and degree of vegetal cover, rainfall and runoff, soil properties, and topography, are taken into account in both formulas. One advantage of the MUSLE over the USLE is that it can be used to evaluate average soil losses for certain types of slopes as a function of time. Another is that the topographic and erosion control factors presented for many construction conditions are not identified in the USLE. Furthermore, the USLE requires that an entire site be evaluated as one single component whereas the MUSLE can be applied to multiple components of a single site, allowing for a more accurate evaluation of a complex cover design (Abt and Ruff, 1978).

Limitations of both equations are that they do not consider the potential for gully development or intrusion, nor do they predict gully erosion, sediment yield, or snowmelt erosion. Accuracy is dependent upon how well the assumed field conditions compare to general conditions depicted in tables and figures; the factors used in the equations relate an average condition. Finally, they do not incorporate the concept of the Probable Maximum Precipitation (PMP), but rather a rainfall factor based on historical rainfall values.

The USLE developed to estimate gross soil losses due to water erosion is:

$$A = RKLSCP$$

where

A = Soil loss, tons/acre/year.

R = Rainfall erosivity factor. This factor expresses the erosion potential of the average annual rainfall in an area. It is the product of the storm's rainfall energy and the maximum 30-minute intensity.

K = Erodibility factor. It is an indication of soil erodibility based upon the soil properties that are influenced by the flow of water. These properties include general soil structure, permeability, and soil composition.

LS = Slope length and slope gradient factor (topographic factor). It expresses the overland flow of water as a function of the slope length and percent slope.

C = Cover or crop management factor. It is an indicator of how various ground covers, rates of mulching, and methods of revegetation can affect water related erosion.

P = Support practice factor. It accounts for the effect of erosion management procedures such as contouring on erosion.

Tables and figures are available in the literature for determining these factors.

In the MUSLE, the cover and erosion control factors ("C" & "P") are replaced with the VM factor. The VM factor accounts for measures implemented at the construction site to include vegetation, mulching, chemical treatments, and sprayed emulsions to impede or reduce erosion due to the overland flow of water (Nelson, et al., 1986).

5.2 SOIL LOSS RATES AT THE GRAND JUNCTION AND DURANGO SITES

Both equations were used to estimate soil losses from the proposed vegetated topslope covers of the Durango and Grand Junction embankments. Soil losses over 200-year and 1000-year periods were calculated for varying cover conditions (e.g., percentage of ground cover and percentage of time vegetation covers topslope). Some of the necessary site-specific data on soil properties were available for the calculations, such as the percent of silt and fine sand, percent of sand (grain sizes greater than 0.1 mm), general soil structure, and permeability. However, the percent of organic materials had to be assumed since this value is not normally obtained in the UMTRA Project testing program. Because the presence of organic matter helps to reduce erosion, a low value of 1.5 percent was chosen for conservatism. Also, a bulk density of 1.5 g/cm³ was used in

all calculations. This value is generally representative of common soil types (Brady, 1974). Moving soil disturbs its structure and changes the bulk density; therefore, bulk densities measured from the undisturbed soil would have been inappropriate.

Table 5.1 summarizes the LS, R, and K values used for calculating soil losses at the two sites. In using the MUSLE to obtain soil losses, time-related VM factors were based on the vegetation growth sequence shown in Table 5.2.

Table 5.1 Input values for MUSLE calculations

Site	Percent topslope	Slope length (feet)	LS	R	K
Durango	3	610	0.61	40	0.26
Grand Junction	2	660	0.35	40	0.29

Table 5.2 Conditions and VM factors used in MUSLE calculations for Durango and Grand Junction

Time	Condition	VM factor
0-42 days	bare soil	1.00
30-90 days	seedlings (fine grasses)	0.40
2-12 months	1' tall grasses	0.05
after 12 months to nth year	1 1/2 - 3' tall grasses	0.01

Erosion rates based on temporary loss of vegetation due to fires were analyzed for different frequencies of occurrence. It was assumed that the growth sequence would begin immediately after destruction, starting with bare soil conditions.

In using the USLE, a "P" value of 1.00 was assumed since erosion control practices, such as contouring, would not be done again after initial construction. The "C" factors used were based on the following two conservative assumptions:

- o There would be no appreciable canopy.
- o The cover at the surface would be mostly broadleaf herbaceous plants (such as weeds with little lateral-root network near the surface and/or decayed residue).

These assumptions were used because short brush or grasses tend to eliminate raindrop impact, reduce runoff velocities and, thus, yield smaller erosion rates. The actual vegetative covers at both sites will generally have more vigorous vegetation, with a better-developed canopy and root system, than is assumed in the calculations, meaning that actual erosion rates should be less than the predicted values.

The results of the calculations (Table 5.3) show that the degree of vegetal cover and the percentage of time during which vegetation covers the topslopes have a significant effect on the erosion rates. Soil losses are higher for the Durango site mainly because of the steeper slope gradient, since rainfall and soil erodibility factors are the same or similar. Fire frequencies shown in the table do not have a significant impact on the erosion rates for the 200- or 1000-year period, provided that plant reestablishment occurs promptly after a fire.

5.3 METHODS FOR ASSESSMENT OF WATER BALANCE

Water balance models can be used to predict evapotranspiration (ET), runoff, percolation, and other hydrologic parameters associated with a proposed vegetative cover. Models can also be used to optimize characteristics of the cover. For instance, the thickness or hydraulic conductivity of the soil can be designed to maximize water retention in the root zone, thus encouraging evapotranspiration and reducing percolation.

Section 3.2 of this report discusses three commonly used water balance models--HELP, CREAMS, and UNSATV--and their potential applicability to the UMTRA Project; features and behaviors of these models are compared in Table 3.4

Beaver (1988) conducted simulations and sensitivity analyses with the HELP and CREAMS models using data for the vegetative cover planned for the topslopes of the stabilized pile at the UMTRA Project site in Grand Junction, Colorado. Tables 5.4 and 5.5 list values for input parameters used in simulations to predict cover performance during climatic conditions such as occurred in the Grand Junction area from 1974 and through 1978. The tables also lists variations in the input values that were tested during the sensitivity analyses.

The HELP model accepts as input data the characteristics of the four principal components of the vegetative cover for the Grand Junction pile, whereas CREAMS accepts only the characteristics of the soil layer. Additional detail on the input parameters and climate simulations are in Beaver's (1988) report.

Table 5.3 Soil loss calculations (inches) for two UMTRA Project sites
MUSLE (A=RKLS "VM")

	200 years										1000 years				
	Percent of time vegetation covers topsoles					Frequency of fires					Percent of time vegetation covers topsoles				
	0	25	50	75	100 ^b	1	1/100	1/50	0	25	50	75	100 ^b	1/100	1/50
"VM" Factor	1.00	0.7470	0.4995	0.2520	0.0113	0.0125	0.0138	0.0163	1.00	0.7514	0.5039	0.2564	0.0103	0.0128	0.0153
Durango (slope = 3%)	7.4	5.5	3.7	1.9	0.1	0.1	0.1	0.1	37.0	27.8	18.7	9.5	0.4	0.5	0.6
Grand Junction (slope = 2%)	4.7	3.5	2.4	1.2	0.1	0.1	0.1	0.1	23.7	17.8	11.9	6.1	0.2	0.3	0.4

USLE (A = RKLS"CP") P=1.00

Site	200 years							1000 years						
	Percent ground cover							Percent ground cover						
	0	10	20	40	60	80	95-100	0	10	20	40	60	80	95-100
"CP" Factor	1.0	0.45	0.24	0.15	0.09	0.043	0.011	1.0	0.45	0.24	0.15	0.09	0.043	0.011
Durango (slope = 3%)	7.4	3.3	1.8	0.1	0.7	0.3	0.1	37.0	16.7	8.9	5.6	3.3	1.6	0.4
Grand Junction (slope = 2%)	4.7	2.1	1.1	0.7	0.4	0.2	0.1	23.7	10.7	5.7	3.6	2.1	1.0	0.3

^a Assuming topsoles are reseeded immediately after fire.

^b Taking into account the time involved for establishing permanent growth and assuming no fires.

Note:

bulk density = 94.4 pcf
% organic matter = 1.5

Table 5.4 Input parameter values for HELP sensitivity analyses, Grand Junction vegetated cover

Layer	Zi (in)	Por	FC	WP	o	Ki (cm/s)	Slope (%)	Drainage length (ft)
Soil (Simulation: Fig. 5.1)	16	0.32	0.25	0.10	0.12	10^{-4}	--	--
Soil (Sensitivity analyses)	variable	0.32	0.25	0.10	0.12	variable	--	--
Biointrusion Barrier	24	0.33	0.11	0.03	0.08	10	--	--
Sand Drain	12	0.34	0.16	0.03	0.10	1	0.04	600
Radon Barrier	24	0.39	0.32	0.15	0.18	10^{-7}	--	--

Sensitivity Analyses					Max LAI
Soil Layer	Ki (cm/s)	Zi (in)	E (in)	CN	
variable	24	24	24	85	1.00
10^{-4}	variable	variable	= 21	85	1.00
10^{-4}	16	16	16	variable	1.00
10^{-4}	16	16	16	85	variable

Legend

Ki = saturated hydraulic conductivity of layer i
 Zi = thickness of layer i
 E = evaporative depth
 CN = SCS AMC II curve number
 LAI = leaf area index
 Por = porosity
 FC = field capacity
 WP = wilting point
 o = initial soil moisture content

Table 5.5 Input parameter values for CREAMS sensitivity analyses, Grand Junction vegetated cover

Layer	Zi (in)	Por	FC	WP	o	Ki (in/hr)	Slope (%)	
Soil (Simulation: Fig. 5.2)	16	0.32	0.25	0.10	0.12	10^{-4}	0.04	3.3
Soil (Sensitivity analyses)	variable	0.32	0.25	0.10	0.12	variable	0.04	variable

Sensitivity Analyses					Max	
Soil Layer	Ki (in/hr)	Zi (in)	CN	LAI	X	
variable/ .15	24	variable	85	1.00	3.3	
.15	16	variable	85	1.00	3.3	
.15	16	16	variable	1.00	3.3	
.15	16	16	85	variable	3.3	
			85	1.00	variable	

Legend

Ki = saturated hydraulic conductivity of layer i
 Zi = thickness of layer i
 CN = SCS AMC II curve number
 LAI = leaf area index
 = evaporation coefficient
 Por = porosity
 FC = field capacity
 WP = wilting point
 o = initial soil moisture content

5.4 RESULTS OF WATER BALANCE SIMULATIONS AND SENSITIVITY ANALYSES FOR THE VEGETATIVE COVER AT THE DISPOSAL SITE FOR THE GRAND JUNCTION TAILINGS

Figures 5.1 and 5.2 illustrate the results of simulations using the HELP and CREAMS models with values in Tables 5.4 and 5.5 for the Grand Junction vegetative cover. The simulations used a value of 1.0 for the annual maximum leaf area index (LAI), which is the ratio of leaf area to ground area. The values for the LAI in the simulations were consistent with observations made in August 1988 (Reith, 1988) of the natural vegetation at the disposal site for the Grand Junction tailings. Climatic parameters for both simulations came from the same database; differences in the monthly precipitation inputs for winter and early spring months in Figures 5.1 and 5.2 are related to differences in the way each model treats snowfall and snowmelt (Beaver, 1988).

The simulations predict that, under average climatic conditions at the Grand Junction site, virtually no percolation would occur through a vegetative cover with a 16-inch thick layer of soil. The great majority of water would be returned to the atmosphere via evapotranspiration. The HELP model (Figure 5.1) predicted that some lateral drainage would occur in the layers beneath the soil cover during the first month of the simulated time period, and the CREAMS model (Figure 5.2), which does not handle lateral drainage, predicted that barely measurable runoff would occur during March, June, and December of each year. Simulations will be performed in the future to predict evapotranspiration, runoff, percolation, and lateral drainage during episodes of increased precipitation up to twice the annual average.

The hydraulic conductivity of the soil was the most sensitive parameter (in terms of influence on evapotranspiration, runoff, percolation, and lateral drainage) in HELP runs under average climatic conditions (Figure 5.3). As expected, low values resulted in greater runoff while high values resulted in greater percolation, which is attributable to the fact that some water is able to move down below the root zone before removal by evapotranspiration. Sensitivity analyses also indicated that a 16-inch thickness of soil was optimum for preventing percolation under average climate (Figure 5.4). Measurable percolation was predicted for soil thicknesses less than 16 inches, whereas little reduction in percolation was achieved with an increased thickness of soil. A similar result emerged from sensitivity analysis with CREAMS. Some additional thickness of soil may nonetheless be advisable to prevent percolation during episodes of increased precipitation; this is being addressed in simulations performed expressly for the Grand Junction compliance effort.

Both the HELP and CREAMS models were relatively insensitive to variation in LAI (Figures 5.5 and 5.6). This suggests that evaporation is more important than transpiration in removing moisture from the soil. One factor contributing to this unexpected result is that the models assume that both components of evapotranspiration occur equally throughout the root zone, whereas transpiration is, in reality, more important at depth (in the root zone) than evaporation, which is most important at the surface. Secondly, almost 75 percent of the soil surface at the Grand Junction disposal site is covered by either rock, plants, or plant litter

FIGURE 5.1
RESULTS OF HELP SIMULATIONS FOR THE VEGETATIVE COVER
AT THE GRAND JUNCTION SITE

FIGURE 5.2
RESULTS OF CREAMS SIMULATIONS FOR THE VEGETATIVE COVER
AT THE GRAND JUNCTION SITE

FIGURE 5.3
SENSITIVITY OF HELP SIMULATIONS TO VARIATION
IN THE HYDRAULIC CONDUCTIVITY OF THE SOIL LAYER

FIGURE 5.4
SENSITIVITY OF HELP SIMULATIONS TO VARIATION
IN THE THICKNESS OF THE SOIL LAYER

FIGURE 5.5
SENSITIVITY OF HELP SIMULATIONS TO THE VARIATION
IN LEAF AREA INDEX (LAI)

FIGURE 5.6
SENSITIVITY OF CREAMS SIMULATIONS IN VARIATION
IN LEAF AREA INDEX (LAI)

(Reith, 1988), meaning that considerable natural mulch exists to restrict evaporation. Beaver (1988) recommends increased emphasis on the issue of evaporation during future applications of water balance models to UMTRA Project cover designs.

Water balance models such as HELP, CREAMS, and UNSATV are complex and only partially applicable to the requirements of the UMTRA Project. Fortunately, the models are continually being modified for applications that more closely approximate the conditions that are encountered on the UMTRA Project. Furthermore, ongoing hydrologic research on the UMTRA Project will yield data that enhances the use of these models for predicting cover performance. In any case, it is critical that users of the models for the UMTRA Project keep in touch with their counterparts on other government projects to stay abreast of the latest developments in water balance modeling for vegetative covers.

6.0 SUMMARY AND RECOMMENDATIONS

6.1 SUMMARY

Vegetative covers are recommended for broad use on the UMTRA Project. Their use on the topslopes of stabilized piles will fulfil the Project's requirements for groundwater protection, erosion control, and prevention of biointrusion. The use of a climax vegetation community will, by definition, satisfy the longevity requirement. A proper combination of soil and vegetation can be selected for covers that will be effective at any of the UMTRA Project sites in arid, semiarid, or subhumid environments. A layer of rock mulch will be required at the most arid UMTRA Project sites to reduce moisture loss by evaporation and thereby increase availability of moisture for plants during dry periods.

Vegetative covers are being increasingly used by the industry, particularly for stabilizing the long-lived radioactive wastes generated by the DOE. The quality of methods for demonstrating the hydrologic performance and erosion resistance of vegetative covers should improve dramatically in the next few years, because these issues are of widespread interest. The most current information on plant establishment from the field of mine reclamation is readily adaptable to the design of vegetative covers for UMTRA Project piles.

Figures 6.1 and 6.2 illustrate proposed configurations for future piles and Figure 6.3 illustrates a general design for the vegetative cover that should occupy the topslopes. It is critical in every case, however, that the soil and vegetation be carefully selected for maximum performance in the environment of the disposal cell. The properties and thickness of the soil should be optimized for moisture retention and ability to support vegetation during dry periods. The vegetation community should be composed of species that are drought tolerant, that have maximum transpirational capacity, and that are fully adapted to the local environment (i.e., enabling the community to develop quickly into a stable climax community). Surface treatments such as rock mulches may be needed on a site-specific basis to improve moisture availability and hence plant survival.

Site-specific considerations must also be addressed in the development of a construction plan for the cover. The need to fertilize, irrigate, or install containerized plants (in addition to seeding) must be determined based on environmental conditions.

Even when vegetative covers are used in combination with another agent to control water balance (e.g., a geomembrane or Claymax layer), the proper soil and vegetation are important to assure rapid plant establishment, maximum resistance to drought, and quick self-renewal after severe disturbance, as all of these factors are important for protecting the soil against erosion.

- ① TOP COVER: SEE FIGURE 6.3
- ② SIDE COVER: EROSION RESISTANT ROCK
- ③ PERIMETER DIKE: COMPACTED SOIL & ROCK
- ④ DISPOSAL CELL: TAILINGS & CONTAMINATED MATERIAL
- ⑤ BASE: EXCAVATED SOIL

FIGURE 6.1
GENERIC CELL DESIGN FOR RELOCATION OPTION

- ① TOP COVER: SEE FIGURE 6.3
- ② SIDE COVER: EROSION RESISTANT ROCK
- ③ PERIMETER BERM OR DIKE: CLEAN FILL
- ④ DISPOSAL CELL: TAILINGS & CONTAMINATED MATERIAL
- ⑤ SIDE AND TOP INFILTRATION BARRIER: COMPACTED CLAY, CLAYMAX, GEOMEMBRANE, DRAIN, OR OTHER

FIGURE 6.2
GENERIC CELL DESIGN FOR STABILIZATION IN PLACE

FIGURE 6.3
GENERIC DESIGN FOR VEGETATIVE COVER ON TOPSLOPES

6.2 RECOMMENDATIONS

Vegetative covers should be considered in future designs for stabilizing the topslopes of UMTRA Project piles. The requirements for NRC concurrence on the vegetative covers at Grand Junction and Durango should be closely observed so that future submittals for vegetative covers will address the NRC's expectations. The development of the vegetative cover and the modeling of its performance at a given site must include a thorough program of site-specific data gathering. The following elements are required:

- o Selection of appropriate soil and assessment of properties.
- o Selection of a model plant community to emulate in the cover.
- o Determination of the need for irrigation or rock mulch.
- o Consultation with local reclamation specialists.

The best available climate data will also be needed to support the execution of CREAMS or a related water balance model.

An ecologist familiar with the vegetation and climate of a given site should participate at the outset in the remedial planning and design for that site. This individual can contribute to decisions regarding soil selection, biointrusion hazard, vegetation selection, and compliance planning. The multidisciplinary composition of the design team is consistent with the concept that each component in a cover contributes to the cover's overall performance. Covers may no longer be regarded as a series of independent operative components.

Investigations of the environment around a disposal site early in the design process can provide important information regarding the resistance of naturally vegetated slopes to erosion and the resistance of rock-covered surfaces (such as old check dams or bridge abutments) to biointrusion. The results of these site-specific investigations can be an important element in design decisions and subsequent compliance demonstrations.

It is also recommended that efforts continue toward an improved use of water balance models such as HELP, CREAMS, and UNSATV for designing vegetative covers and demonstrating their long-term performance. Hydrologists should learn of the latest model refinements and explore ways to enhance the models' applicability to UMTRA Project cover designs.

Efforts must also continue toward an improved understanding of gully erosion and the NRC's requirements for demonstration of a vegetative cover's resistance to gully erosion. The proposed special study for comparing Title I versus Title II requirements will satisfy this objective, as will a continued effort to quantify the risk and severity of potential gullies.

Finally, it is recommended that observations be made at a field test plot for vegetative covers established in 1980 by Pacific Northwest Laboratories expressly for the UMTRA Project. The plot was constructed at the San Juan Coal Mine, near Farmington, New Mexico, to investigate effects of various surface treatments on (1) vegetational coverage, (2) erosion resistance, and (3) water balance (Beedlow, 1984). Experiment treatments test for the effectiveness of different plant species and rock mulches in stabilizing soils and controlling infiltration. Access ports for neutron probes are still intact.

No data have been collected from this plot since 1984, and its value has greatly increased as it is now one of the oldest undisturbed demonstration plots in the nation. Quantitative studies of this "equilibrium cover" are recommended as part of a continuation of the special study on vegetative covers; hydrologic and erosional data will contribute significantly to future submittals involving vegetative covers to the NRC.

A continuing effort toward the improvement and demonstration of the vegetative-cover concept is highly worthwhile in light of the importance of this approach for future UMTRA Project pile designs.

REFERENCES

- Abt, S. R. and Ruff, J. F., 1978. "Three Procedures for Estimating Erosion From Construction Areas," from symposium on Uranium Mill Tailings Management, Fort Collins, Colorado, November 20, 21, Geotechnical Engineering Program, Civil Engineering Department, Colorado State University, Ft. Collins, CO.
- Adams, M. R., and N. R. Wing, 1987. "Protective Barrier and Warning Marker System Development Plan," RHO-RE-PL-35P, Rockwell Hanford Operations, Richland, WA.
- Anderson, et al. (J. E. Anderson, M. L. Shumar, Nancee L. Toft, and R. S. Nowak), 1987. "Control of Soil Water Balance by Sagebrush and Three Perennial Grasses in a Cold-desert Environment," in Arid Soil Research and Rehabilitation, 1:229-244.
- Beaver, D., 1988. "HELP and CREAMS Sensitivity Analyses; Grand Junction Vegetated Cover," memorandum to C. Reith and L. Coons, Jacobs Engineering Group, Albuquerque Operations Office, Albuquerque, NM, dated November 8, 1988.
- Beedlow, P. A., 1984. "Revegetation and Rock Cover for Stabilization of Inactive Uranium Mill Tailings Disposal Sites," DOE/UMT-0217, PNL-5105, UC-70, Pacific Northwest Laboratories, Richland, WA.
- Beedlow, P. A., and J. N. Hartley, 1984. "Long-term Protection of Uranium Mill Tailings," DOE/UMT-0218, PNL-4984, UC-70, Pacific Northwest Laboratories, Richland, WA.
- Brady, N. C., 1974. The Nature and Properties of Soils, 8th Edition, MacMillan Publishing Company, Inc., New York, NY.
- Burton et al. (F. G. Burton, W. E. Skiens, J. F. Cline, D. A. Cataldo, and P. Van Voris), 1986. "A Controlled Release Herbicide Device for Multiple-Year Control of Roots at Burial Sites," in Journal of Controlled Release, 3:47-54.
- Cline, et al. (J. F. Cline, D. A. Cataldo, W. E. Skiens, and F. G. Burton), 1981. "Biobarriers Used in Shallow Burial Ground Stabilization," in Nuclear Technology, 58:150-153.
- Cline, et al. (J. F. Cline, K. A. Gano, and L. E. Rogers), 1980. "Loose Rock as Biobarriers in Shallow-Land Burial," in Health Physics, 39:497-504.
- DOE (U.S. Department of Energy), 1985. "Technical Summary of the UMTRA Project Technology Development Program (1980-1984)," UMTRA-DOE/AL-200125.0000, DOE UMTRA Project Office, Albuquerque Operations Office, Albuquerque, NM.

- DOE (U.S. Department of Energy), 1983. "Design Criteria for Stabilization of Inactive Mill Tailings Sites," UMTRA-DOE/AL-050242.9949, DOE UMTRA Project Office, Albuquerque Operations Office, Albuquerque, NM.
- Fischer, N. T., 1986. "Vegetation Ecology, Sample Adequacy, and the Determination of Reclamation Success," in Principles and Methods of Reclamation Science, C. C. Reith and L. D. Potter (eds.), University of New Mexico Press, Albuquerque, NM, pages 189-214.
- Foxx, et al. (T. S. Foxx, G. D. Tierney, and J. M. Williams), 1984. "Rooting Depths of Plants Relative to Biological and Environmental Factors," LA-10254-MS/UC-70B, Los Alamos National Laboratories, Los Alamos, NM.
- Gee, G. W., 1987. "Recharge at the Hanford Site: Status Report," PNL-6403/UC-70, Pacific Northwest Laboratories, Richland, WA.
- Gray, D. H., and A. T. Leiser, 1982. Biotechnical Slope Protection and Erosion Control, Van Nostrand Reinhold Company, Inc., New York, NY.
- Hakonson, T. H., 1988. Manager of Environmental Services, Los Alamos National Laboratory, personal communication with C. C. Reith, Jacobs Engineering Group, Albuquerque Operations Office, Albuquerque, NM, dated August 1988.
- Hakonson, et al. (T. H. Hakonson, L. J. Lane, J. W. Nyhan, and G. L. DePorter), 1987. "Trench Cover System for Manipulating Water Balance on Low-level Radioactive Waste Sites," LA-UR, submitted to USGS Low-Level Radioactive Waste Workshop, Big Bear Lake, CA.
- Hakonson, T. H., 1986. "Evaluation of Geologic Materials to Limit Biological Intrusion into Low-Level Radioactive Waste Disposal Sites," LA-10286-MS/UC-70B, Los Alamos National Laboratories, Los Alamos, NM.
- Lindsey, G. 1988. "Geomorphic Stability: Topslopes," Response to NRC Technical Evaluation Report, 1988, Cheney Disposal Site, Jacobs Engineering Group, Albuquerque Operations Office, Albuquerque, NM.
- Nelson, et al. (J. D. Nelson, S. R. Abt, R. L. Volpe, and D. Van Zyl), 1986. Methodologies for Evaluating Long-Term Stabilization Designs of Uranium Mill Tailings Impoundments, prepared for Division of Waste Management, Office of Nuclear Material Safety and Safeguards, U.S. Nuclear Regulatory Commission NRCFINB0279, Ft. Collins, CO.
- O'Donnell, et al. (E. O'Donnell, R. K. Shulz, and R. W. Ridky), 1987. "Control of Water Infiltration into Near-Surface LLW Disposal Facilities," DOE Oak Ridge Model Conference, Oak Ridge, TN.
- Reith, C. C., 1988. "Field notes on observations at the Cheney Reservoir site," Jacobs Engineering Group, Albuquerque Operations Office, Albuquerque, NM, dated October 14, 1988.
- Reith, C. C., and L. D. Potter, 1986. Principles and Methods of Reclamation Science, University of New Mexico Press, Albuquerque, NM.

Rodgers, et al. (J. C. Rodgers, F. Barnes, T. Foxx, and G. Tierney), 1984. "Maintenance Free Vegetative Systems for Landfill Covers," LA-VR-84-3407, Los Alamos National Laboratories, Los Alamos, NM.

Walters, et al. (W. H. Walters, R. L. Skaggs, M. G. Foley, and P. A. Beedlow), 1986. "Erosion Protection of Uranium Tailings Impoundments," NUREG/CR-4480, PNL-5724, Pacific Northwest Laboratories, Richland, WA.

Waugh, W. J., 1988. Researcher, Pacific Northwest Laboratories, personal communication with C. C. Reith, Jacobs Engineering Group, Albuquerque Operations Office, Albuquerque, NM, dated July 1988.

Whitford, W. G., and N. Z. Elkins, 1986. "The Importance of Soil Ecology and the Ecosystem Perspective in Surface Mine Reclamation," pp. 151-182 in Principles and Methods of Reclamation Science, C. C. Reith and L. D. Potter (eds.), University of New Mexico Press, Albuquerque, NM.

PLATE 1. VOLUNTEER VEGETATION ON SHIPROCK PILE.

VIEW OF NORTH-FACING SLOPE

ANNUAL SUMMERCYPRESS AND
RUSSIAN THISTLE (ABOVE)

AND PERENNIAL SALT CEDAR (LEFT;
NOTE DAYPACK AND GLOVES FOR SCALE).

PLATE 2. ROOTS OF VEGETATION ON SHIPROCK PILE.

SUMMERCYPRESS ROOTS

SALT CEDAR ROOTS IN SITU (ABOVE)

AND UNEARTHED (RIGHT)

APPENDIX A

A TIME-RELEASED HERBICIDAL SYSTEM
FOR PREVENTING BIOINTEGRATION

1988-2088

Introducing root control
that can last until the year 2088.

Typar® Biobarrier™
is a system that blocks
roots virtually forever.

Typar Biobarrier is a root control system developed by Reemay, Inc., which combines a fabric with time-released herbicide. The system creates an in-soil herbicidal barrier that can block roots—without harming plants—for up to 100 years. That's a working life of up to 30 times greater than conventional sprays, plastic or steel barriers.

Biobarrier was originally conceived in response to the U.S. Department of Energy's search for a way to keep roots from penetrating nuclear waste sites. It was developed by Reemay, Inc. utilizing patented technology from Battelle Memorial Institute's Pacific Northwest Laboratories and the assistance of Elanco Products Company.

Biobarrier is the most effective, longest-lasting means of creating a root barrier without harming plants, trees or other vegetation or disrupting environmental soil cycles.

**A protective barrier
of controlled-release
herbicide.**

Biobarrier combines the benefits of the most modern geotextile and a proven herbicide. The carrier fabric is Typar® polypropylene geotextile which makes Biobarrier flexible and easy to install. Yet it's strong, non-degradable and porous enough to allow water and oxygen to pass through.

Permanently bonded to this rugged geotextile are pellets impregnated with the

Without Biobarrier (a), tree roots penetrate street, sidewalk and aggregate base, causing cracks and heaving.
With Biobarrier (b), a protective wall of herbicidal vapor repels roots without harming the tree.

herbicide trifluralin, manufactured by Elanco under the registered trademark Treflan.®

Instead of killing roots or plants, trifluralin works by preventing root cell division, which retards growth. Roots either stop growing or are deflected away from the treated area.

When buried underground, Biobarrier releases a herbicidal vapor into the soil at a controlled rate that can be engineered to last up to 100 years. This vapor slowly extends 2-4 inches out either side from Biobarrier before attaching to soil particles and remaining there. It's a virtual wall of herbicide that prevents root penetration.

Biobarrier is safe.

The herbicide in Biobarrier—Treflan[®]—is one of the most widely used herbicides in the United States. It has been on the market for more than 25 years and is approved for use by the Environmental Protection Agency on farm crops and many types of vegetation.

The level of trifluralin released by Biobarrier is far *below* typical levels used by farmers in single applications.

Trifluralin, Treflan's active ingredient, is safe for a variety of reasons. It's biodegradable—eventually degrading into harmless components—but cannot be absorbed into plant systems. It's non-toxic to animals and is not water-soluble. And because trifluralin attaches to soil particles, it doesn't migrate. It stays—and keeps on working—wherever Biobarrier is installed.

Applications still being discovered for Biobarrier.

Although Biobarrier was originally conceived as protection for nuclear waste burial sites, private industries and government agencies have suggested many related commercial applications. New uses are still being found.

A few of the most common uses are landfills, streets and sidewalks, septic and drain fields, and landscaping applications.

Hazardous waste landfills. Roots can eventually penetrate closure caps—even asphalt—over landfills, allowing toxic gases to escape through gaps and cracks. Chemicals can also escape after being absorbed by roots and traveling up through plant systems. However, if Biobarrier is installed horizontally between closure cap and topsoil, roots that attempt to penetrate the cap will be blocked without harm to vegetation. And Biobarrier's permeability doesn't disrupt the hydrology and soil chemistry that's critical to landfill dynamics.

Streets and sidewalks.

As trees grow, their roots can crack, lift or otherwise damage paved streets and sidewalks. But with a vertical curtain of Biobarrier buried

along the edge of the pavement, tree roots are deflected from the protected area for decades. No harm comes to the trees themselves. Biobarrier's long-lasting protection eliminates costly maintenance and prolongs the service life of streets and sidewalks, without jeopardizing valuable landscaping.

Septic and drain fields.

Biobarrier is approved for use in septic and drain fields to prevent damage and clogging caused by roots. In these applications,

Biobarrier can be literally wrapped around a drain field for full perimeter root protection or used as an underground barrier between trees and nearby pipes.

Landscaping. Biobarrier is the ideal root control system for many landscaping situations: swimming pools, gardens, indoor gardens and other areas that are

inaccessible or difficult to maintain. Installation will vary with individual conditions. In all cases, Biobarrier provides maximum root protection for minimal maintenance costs over long periods of time.

Biobarrier is a new product from Reemay, Inc.

For information about Biobarrier and recent case histories, call or write the Marketing/Communications Department of Reemay, Inc., Industrial Road, P.O. Box 511, Old Hickory, TN 37138, (800) 321-6271.

TYPAR[®]
Bio **barrier[™]**
Root Control System

Member of The Tech Group, Inc.

Industrial Road
P.O. Box 511
Old Hickory, TN 37138
(800) 321-6271

END

DATE FILMED

02 / 13 / 91