500
WB

I E8413 ①

D 1272

Prepared for DOE under contract
No. W-7405-Eng-48

About the Cover

Artist's rendering of the transport and storage of various liquefied gases, including liquefied natural gas (LNG), liquefied petroleum gas (LPG), ammonia, chlorine, etc. The storage tanks typically hold some 100 000 m³, the railroad tank cars each hold approximately 150 m³, and the trucks carry about 40 m³. These materials are transported conventionally over public highways and the nation's railroads; storage facilities are little different in appearance and location from the oil and gasoline storage facilities found throughout this country. Obviously, the transport and storage of such large, concentrated quantities of hazardous materials make it essential that we have a sound understanding of the phenomena that accompany their accidental release. To resolve the technical uncertainties surrounding spills of liquefied gaseous fuels (LGF), the Department of Energy established, in 1978, the LGF Safety and Environmental Control Assessment Program. As a major participant in the program, LLNL was asked to study the effects of large-scale LGF spills. For further information see the article beginning on p. 1.

Scientific Editor

Paul S. Brown

General Editors

Richard B. Crawford
Mary Ann Esser
Patricia L. Lien
Eleanor M. O'Neal
Palmer T. Van Dyke

About the Journal

The Lawrence Livermore National Laboratory, operated by the University of California for the United States Department of Energy, was established in 1952 to conduct nuclear weapons and controlled thermonuclear reaction research. Today, about 60% of our resources are devoted to defense programs, which include weapons and laser fusion research. Other major areas of focus are: magnetic fusion energy; laser isotope separation; chemistry, engineering, and physics research; biomedical and environmental sciences; applied energy technology; and work for other Federal agencies. The *Energy and Technology Review* is published monthly to report on accomplishments in unclassified programs. A companion journal, the *Research Monthly*, reports on weapons research and other classified programs. Titles from recent issues of the *Energy and Technology Review* are listed opposite the inside back cover.

Graphics Designer
John Schuster

Production Staff
Louisa Cardoza
Kim Osterhoff

E&TR

UCRL--52000-83-1

DE83 009213

Energy and Technology Review

Lawrence Livermore National Laboratory

January 1983

Briefs

ii

ATA Injector Meets Design Goals
Neutral-Solution Processing of Large Antireflective Surfaces for High-Power Lasers

Predicting Hazards from Large Spills of Liquefied Gases

1

We have conducted an extensive series of field experiments to study the behavior of large volumes of liquefied gases under a variety of conditions.

Laser Fusion X-Ray Measurements

13

We have developed a number of new instruments, with greatly improved energy and time resolution and a broader energy range, for measuring x-ray spectra from laser fusion experiments.

Laser-Heated Flashlamps: a Step Toward a Soft X-Ray Laser

23

Recent LLNL experiments show progress toward a technique for lasing at x-ray wavelengths.

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

NOTICE

PORTIONS OF THIS REPORT ARE UNCLASSIFIED

It has been reproduced from the best available copy to permit the broadest possible availability.

UCRL-52000-83-1

Distribution Category UC-2

January 1983

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

Briefs

ATA Injector Meets Design Goals

In early November of 1982, we began checkout of the electron gun (injector) of the Advanced Test Accelerator (ATA), the world's most advanced high-current accelerator (see *Energy and Technology Review*, UCRL-52000-81-12, December 1981, p. 1). The electron gun (Fig. 1) is designed to produce a 10-kA, 2.5-MeV electron beam, which the ATA will then accelerate (through 190 accelerator modules) to a final energy of 50 MeV. Construction of the ATA at Site 300 is being funded by the Defense Advanced Research Projects Agency (DARPA) as part of its particle-beam technology program. The primary purpose of the ATA is to provide an electron beam with enough energy and current for tests of electron-beam propagation in the atmosphere.

By testing the operation of the injector as the final stages of the ATA were being assembled, the physics and engineering team was able to verify the integrity of the ATA's electrical subsystems within the first week of testing. We then began high-voltage tests of the injector, and on the third night of high-voltage operation

attained the injector's design-specified performance: a 50-ns, 10-kA pulse of electrons at 2.5 MeV.

Because the ATA injector uses the same combination of linear induction accelerator modules and pulsed power drives as does the remainder of the accelerator, injector tests actually exercise about 10% of the entire ATA power system. The fine performance of the injector systems enhances our confidence that the entire ATA will soon be in operation at significant beam power levels.

As the final accelerator sections are being fitted into place, we are performing a series of measurements of the size and intrinsic divergence of the beam delivered by the injector. Our next step will be to attenuate the 10-kA beam current to about 1 kA and accelerate it through increasingly longer segments of the accelerator. At each stage, we will measure the characteristics of the beam to look for low-level disturbances that could disrupt the full 10-kA beam. Once we have accelerated a low-current beam through the entire ATA complement of 190 accelerator cells, we will gradually increase the current (by

Fig. 1

A schematic drawing of the 2.5-MeV electron injector for the ATA. The 2.5-MV potential difference between the anode and the cathode (provided by 10 induction accelerator units of 0.25 MV each, connected in series) extracts a 10-kA current of electrons from the large cathode. The beam starts to spread soon after it enters the anode, but focusing coils overcome the outward acceleration and shrink the beam before it enters the accelerator.

reducing the attenuation) and implement beam-quieting techniques if needed.

After the accelerator checkout is completed, we will embark upon our program of exploring the physics of how intense electron beams propagate in the atmosphere.

For further information contact William A. Barletta (415) 422-6705.

Key Words: advanced test accelerator (ATA); charged-particle beam; electron-beam propagation; electron gun; injector.

Neutral-Solution Processing of Large Antireflective Surfaces for High-Power Lasers

Large neodymium-glass lasers like LLNL's Nova laser contain many lenses and windows with antireflective surfaces that prevent costly energy losses. Antireflective surfaces are especially crucial components of high-power lasers because they typically receive the highest fluence loading of all surfaces in the laser amplifier chain and have the lowest damage threshold. The overall laser system performance, therefore, is directly related to the performance of these antireflective surfaces. We have used a new process to produce antireflective surfaces on very large (90 cm in diameter) glass lenses for the Novette and Nova lasers. The surfaces were treated by neutral-solution processing (NSP), a technique developed less than two years ago by Schott Optical Glass, Inc.¹

In NSP, a polished component made of borosilicate glass is immersed in a nearly neutral (pH 6) solution. (The exact composition of the solution is proprietary.) The solution leaches some constituents from the polished surface, leaving a porous surface layer. The porosity of the leached layer is greatest at its air interface and least at the interface between the leached layer and the solid glass substrate. Because the density of the leached layer is reduced and graded, its refractive index is graded along the surface normal and is gener-

ally less than that of the solid glass. Optimum reflectivities of less than 0.1% have been obtained with this technique. The median pore size² of 4 to 7 nm in the porous surface results in small scatter loss.

The reflectance spectrum³ of a glass surface bearing the porous layer formed by NSP is similar to that of a surface coated with a spatially homogeneous low-index layer formed by conventional vapor deposition. For a homogeneous layer of thickness d , reflectance minima occur at wavelengths λ given by $m\lambda/4 = d$, where m is an odd integer. At wavelengths corresponding to an even integer value of m , reflectance is maximum and equal to that of the uncoated substrate. A surface prepared by NSP to be antireflective at

Fig. 1

A spatial filter lens 90 cm in diameter designed for a high-power laser. The antireflective surface was formed by neutral-solution processing. In addition to producing broadband reflective properties, this readily applied technique provides high resistance to laser-induced damage.

$\lambda = 1064 \text{ nm}$ ($m = 1$) is also antireflective at $\lambda = 355 \text{ nm}$ ($m = 3$) and has a reflectance maximum at $\lambda = 532 \text{ nm}$ ($m = 2$).⁴ In this respect, the porous surface layer functions as a spatially homogeneous low-index layer. Because the refractive index is partly graded in the porous layer, however, the reflectance at the local maximum is still low. The surface is a good antireflecting film at 1064 and 355 nm; even at 532 nm, the reflectance is typically less than 30% of that of the bare untreated substrate, in contrast to a homogeneous low-index layer. Thus, the treated surface has reduced reflectivity for all wavelengths compared to the untreated surface. This makes the optimization process for several simultaneous wavelengths less critical.

The broadband antireflectivity of surfaces treated by NSP allows us several processing options in fabricating lenses and windows for 1064-nm lasers such as Novette. In 20 to 30 hours of leaching, we can produce a porous layer of a thickness that is antireflective at the second harmonic wavelength (532 nm); extending the leaching time to 40 to 60 hours produces antireflectivity at 1064 nm. By leaching for an intermediate time, we effectively center the optimum antireflecting wavelength between the two wavelengths of interest. We thus obtain nonoptimum but reasonably effective antireflecting behavior of less than 1% at both 532 nm and 1064 nm.

Although broadband reflectivity is highly desirable in itself, our use of NSP-treated optical surfaces in Novette was dictated by two additional considerations: such surfaces are resistant to laser-induced damage and are readily produced. Their threshold for laser damage by 1-ns, 1064-nm pulses is 10 to 14 J/cm², more than twice the average threshold of antireflective films deposited by electron-beam evaporation.⁴

Other techniques for producing antireflective surface are available. For example, similar resistance to laser-induced damage is exhibited by microporous antireflective surfaces etched into phase-separated glasses⁵ and by etched microporous layers that are initially

deposited from solution.⁶ Forming porous surfaces by these other techniques requires an acid-etch treatment that takes only about 1 to 15 min. With such rapid etching, however, local gradients in chemical concentration can produce non-uniform antireflective layers on large surfaces. Because NSP requires 20 to 60 hours, moderate stirring averages the effect of solution gradients and allows better control over the uniformity of the antireflection layer.

The Laboratory's NSP facility was established to treat optical components of the Novette and Nova lasers. Schott Optical Glass, Inc., has licensed LLNL to use the NSP process and has assisted us in transferring the technology. We have measured both the uniformity of antireflective layers and the laser damage thresholds of several large optical parts formed at LLNL (Fig. 1). The results indicate a successful technology transfer.

For further information contact Richard G. Wirtenson (415) 422-1332.

Key Words: antireflection surfaces; graded-index surfaces, inertial confinement fusion; lasers—neodymium-glass, solid-state; neutral-solution processing (NSP); Novette.

Notes and References

1. L. M. Cook and K. H. Mader, "Integral AR Coated Glasses for High Energy Laser Applications," in *Proc. Electro-Optics/Laser 81 Conference and Exposition*, Cahners Exposition Group, Chicago, Illinois (1981); L. M. Cook, K. H. Mader, and R. Schnabel, "Integral Antireflective Surfaces on Silicate Glass," U.S. Patent Application No. 309149, October 6, 1981.
2. H. Schroeder, "Thin Film Formation on Glass Surfaces in Chemical Coating Processes," in *Proc. Tenth Intl. Cong. on Glass*, Kyoto, 1974; J. Ceramic Soc. Japan 4, 87 (1974).
3. The optics of antireflective surfaces were discussed in the March 1982 *Energy and Technology Review* (UCRL 52000-82-3), p. 9.
4. L. M. Cook, W. H. Lowdermilk, D. Milam, and J. F. Swain, "Antireflective Surfaces for High-Energy Laser Optics Formed by Neutral-Solution Processing," *Appl. Opt.* **21**, 1484 (1982).
5. W. H. Lowdermilk and D. Milam, "Graded-Index Antireflection Surfaces for High-Power Laser Applications," *Appl. Phys. Lett.* **36**, 891 (1980).
6. S. P. Mukherjee and W. H. Lowdermilk, "Graded-Index AR Film Deposited by the Sol-Gel Process," *Appl. Opt.* **21**, 293 (1982).

Predicting Hazards from Large Spills of Liquefied Gases

contact
7381

quantities around the world. The trend to large-scale handling of such materials is seen in the liquefied gaseous fuels (LGF) industry, where economies of scale are driving upward the size of individual storage and transport containers.

An accurate and reliable set of analytical tools with which to predict the consequences of accidental releases is required to design reasonable regulations governing the storage and use of hazardous liquefied gases, to evaluate hazard-mitigation proposals and devices, and to plan prompt and appropriate responses to emergencies. We must be able to predict confidently the full range of possible consequences of an accident in a variety of circumstances. During an actual emergency, efforts to limit damage require simple, accurate information on what is likely to occur under specific conditions and the probable effect of various actions and hazard-mitigation measures on the outcome.

Quantifying the Hazards

When the temperature of a gas is reduced or its pressure increased sufficiently, it can be turned into liquid having a considerably smaller bulk than its original volume. A cryogenic ship carrying LNG, for example, holds 600 times more natural gas than it otherwise could, making it economically feasible to transport such materials over transoceanic distances. The biggest ships and land-based storage tanks now can hold more than 100 000 m³ of LNG. The storage of such large, concentrated quantities of fuel makes it important that we have a sound technical understanding of the phenomena that accompany their accidental release.

Some small-scale experiments performed before 1978 left considerable disagreement about the likely results of a large-scale LGF accident. A large spill can overwhelm factors that affect the behavior of a small spill. The dispersion of a small spill, for example, is controlled by local winds and atmospheric turbulence. In contrast, the cloud formed by the rapid release of 25 000 m³ of an LGF is large compared

to atmospheric turbulence scales. Its dispersion characteristics are thus likely to be quite different from those of small clouds, which do not disturb the atmospheric flow. Because of such phenomena, predictions extrapolated from small-scale experimental data or from standard pollution-dispersion models command little confidence.

We need to be able to predict all phenomena that occur in an accidental LGF spill. The boundary conditions of a spill are the state of the atmosphere and the conditions of the spill itself, characterized by its geometry, spill rate, volume, and velocity, and the chemical and physical properties of the spilled material. From that information, we must predict how the spilled liquid spreads and turns into a vapor and how the vapor cloud disperses. If the cloud is flammable and encounters an ignition source, we want to know the likelihood of ignition and the form of combustion—slow burn, rapid deflagration, or even detonation. Finally, we need models with which to predict the extent of damage from thermal and blast energy released by the combustion process.

To resolve the technical uncertainties surrounding LGF spills and to evaluate methods of mitigating their consequences, the Department of Energy in 1978 established the LGF Safety and Environmental Control Assessment Program. As a major participant in the program, LLNL was asked to study the effects of large-scale spills. The basic goal of the Laboratory's Spill-Effects Program is to develop a set of predictive computational tools with which to describe what can happen in any given accidental release of LGF. Because such phenomena have a complex interdependence, we have adopted an approach that integrates analysis with experimental studies. The experimental results are being used to improve and validate our computational models. In the experimental portion of the program, we recently carried out two large-scale field studies of fuel spills. The results are being used to compare the relative value of various vapor-dispersion models.

China Lake Experiments

During the summers of 1980 and 1981, we conducted two series of spill experiments, known respectively as Burro and Coyote, at the Naval Weapons Center at China Lake, California, a dry desert lake bed. In the Burro experiments, we carried out eight spills to measure the dispersion of an LNG vapor cloud under a variety of atmospheric conditions.^{2,3} Winds ranged from 1.8 to 9.1 m/s, and stability varied. The LNG was spilled at rates from 11 to 18 m³/s through a pipeline 25 cm in diameter into the center of a water spill pond 58 m in diameter and 1 m deep (LNG floats on water). Spills onto water were chosen because they produce the largest hazardous cloud for a given volume of LNG. The total spill volume ranged from 24 to 39 m³. We believe that spills at these volumes mark a threshold for observing large-cloud effects. So that the spill would not stir up the mud at the bottom of the shallow pond, we used a spill plate just below the water surface to divert the downward flow of LNG horizontally. Beyond the spill pond, the terrain rose to about 7 m above the water level at a distance of 80 m downwind and remained relatively level thereafter.

In the Burro series, we deployed a large array of gas-sensing and wind-measuring instruments upwind and downwind of the spill point (Fig. 1). One subarray consisted of 20 cup-and-vane anemometers, each at a local height of 2 m, to map the wind field. Another subarray of 25 stations tracked the gas cloud with gas-concentration sensors at 1, 3, and 8 m. Some gas sensors separated methane and higher hydrocarbons, and others sensed total hydrocarbons. An array of six stations measured gas concentration and turbulence effects using propeller bivanne anemometers at 1.4, 3.0, and 8.0 m and fast gas sensors at 1.0, 3.0, and 8.0 m. Humidity sensors, thermocouples, and heat-flux sensors collected data at various locations within the array, and infrared imagers made remote measurements. All stations were battery powered and microprocessor controlled and had some onboard memory. We

communicated with the stations from a data-recording trailer, activating them by radio telemetry and receiving data when they were polled.

The Coyote series of spill experiments, in 1981, consisted of two subseries. In one, we conducted 13 small spills to examine a phenomenon known as a rapid-phase-transition (RPT) explosion (described below). The spill materials were LNG, liquefied methane, and liquid nitrogen. These were spilled at various rates into water of different depths to determine the boundary conditions under which RPTs occur and what factors influence the size of the ensuing explosions.

In the second Coyote subseries, we spilled LNG and allowed the vapor to partly disperse under a variety of wind conditions, as in the Burro experiments. In the Coyote tests, however, the vapor cloud was then ignited by flares or by jet ignition and allowed to burn. The jet ignitor consisted of a pipe, open at one end and filled with a propane-air mixture. The gas inside the pipe was

Fig. 1

Instrumentation array for the 1980 LNG dispersion tests (Burro series) at the Naval Weapons Center, China Lake, California (shaded area is marsh). Instrument stations measured the wind velocity, gas composition and concentration, and a variety of other variables. The stations were battery powered and microprocessor controlled; they were activated by radio telemetry from a data-recording trailer, which received data when the stations were polled.

Fig. 2

Horizontal gas-concentration contours measured in the Burro 3 test, showing cloud shape at the maximum downwind extent of the lower flammability limit, the minimum gas concentration necessary for ignition. The contours are given in 2.5% increments by volume. The maximum flammable zone (shaded area), where the gas concentration is 5% or more, was about 80 m wide and extended about 255 m downwind of the spill point.

ignited at the closed end, and a flame jet emerged from the open end. Our objective was to measure the extent and violence of the burn. For the Coyote experiments, we changed the location of the Burro instrument stations to provide more measurements in the flammable region and added several instruments to measure flame velocity and the extent and radiative output of the fire. In the RPT tests, additional instruments near the spill point measured overpressure in the air and the composition, velocity, and temperature of the LNG exiting the spill pipe.

Vapor Dispersion

In studying the dispersion behavior of the gas clouds, we were interested in how the spill rate, wind speed, and atmospheric stability affected the size of the flammable zone. The gas-air mixture is no longer flammable once the concentration of methane drops below 5% by volume (defined as the lower flammability limit, or LFL).

Our vapor dispersion analyses before the experiments indicated that 40-m³ spills at rates on the order of 20 m³/min are at the threshold for observing spill-dominated dispersion effects. This prediction was confirmed by our vapor dispersion tests. Turbulent processes in the lower atmospheric boundary layer dominated the transport and dispersion of gas in all experiments but one. Figure 2 shows a horizontal contour, generated from the experimental data (1 m above the ground), of a typical cloud configuration. At its maximum size, the flammable zone was about 80 m wide and extended about 255 m downwind of the spill point. In most tests, atmospheric fluctuations caused the flammable zone to meander back and forth across the instrument array. The plume would sometimes break into pieces and then recombine into a single flow. Because of these effects, the angle and range of the downwind distance to the detected LFL fluctuated during the tests.

Table 1 Summary of Burro experiments, including ambient meteorological parameters.

Parameter	Experiment							
	Burro 2	Burro 3	Burro 4	Burro 5	Burro 6	Burro 7	Burro 8	Burro 9
Date	6/18/80	7/2/80	7/9/80	7/16/80	8/5/80	8/27/80	9/3/80	9/17/80
Spill volume, m ³	34.3	34.0	35.3	35.8	27.5	39.4	28.4	24.2
Spill rate, m ³ /min	11.9	12.2	12.1	11.3	12.8	13.6	16.0	18.4
Mean and standard deviation of windspeed at 2-m height, m/s	5.4 ± 1.8	5.4 ± 1.2	9.0 ± 1.2	7.4 ± 1.1	9.1 ± 1.1	8.4 ± 1.2	1.8 ± 0.3	5.7 ± 0.7
Richardson number at 2-m height	-0.178	-0.221	-0.054	-0.079	-0.044	-0.018	+0.121	-0.014
Wind-speed tendency	Decreasing	Fairly constant	Fairly constant	Fairly constant	Fairly constant	Nearly constant	Decreasing	Slowly decreasing
Atmospheric stability	Unstable	Unstable	Slightly unstable	Slightly unstable	Slightly unstable	Neutral to slightly unstable	Slightly stable	Neutral

To see more clearly how the mean-dering cloud mixed with the atmosphere as it propagated downwind, we plotted the maximum concentration observed at each row of instruments as a function of distance from the spill point. Figure 3 shows these data for all tests in the Burro series. Table 1 gives the values of the relevant atmospheric and spill variables. The results for tests 2 through 7 follow a similar logarithmic pattern, with a downwind distance to the LFL between 170 and 250 m. In contrast, the maximum downwind LFL in tests 8 and 9 occurred at 470 and 320 m, respectively (see Fig. 3). Significantly, Burro 8, with the largest downwind LFL, had a high spill rate, the lowest wind speed, and the most stable atmospheric conditions (as indicated by the Richardson number, a measure of the stability of the atmosphere). Burro 9, with the next largest LFL, had the highest spill rate and was close behind Burro 8 in low wind speed and atmospheric stability. More tests with variables in the range of Burro 8 and 9 would be necessary to confirm this trend and to further isolate the effects of these variables on dispersion behavior.

The shape and dynamics of the Burro 8 vapor cloud were also distinctive. The cloud was much wider, extending beyond both sides of the instrument array, and its height much less than those in other tests (Fig. 4). This cloud was also the only one to develop a distinctive bifurcated structure (Fig. 5). In addition, the cloud extended about 40 m upwind of the spill point. In contrast to other experiments, where the vapor cloud was rapidly dispersed downwind by higher wind speeds within 10 to 20 s after the spill was terminated, the Burro 8 cloud remained over the source region for nearly two minutes.

The lower wind speed in the Burro 8 test enabled the effects of gravity on the cold, dense LNG vapor cloud to dominate the effects of the surrounding atmosphere in the dispersion process. Within the cloud, spreading caused by gravity (called gravity flow) overwhelmed the effects of the atmosphere.

The ambient wind field was effectively displaced above the cloud, the wind speed in its interior dropping essentially to zero (Fig. 6). In this situation, the turbulence inside the cloud, which causes the dilution of the vapor with air, was controlled by the gravity-flow process and by heating from the ground rather than by the atmospheric processes. Although this behavior was observed in our tests only under conditions of low wind speed and in a stable atmosphere, our models indicate that it is likely to occur under a variety of ambient conditions in larger spills. Before we can verify the scaling of these processes in our models, we must

Fig. 3

Maximum gas concentrations observed at each downwind distance during the Burro series. The arrow indicates a higher concentration, which is unknown because of sensor saturation. Tests with the largest lower flammability limit (LFL) had the highest spill rates, the lowest wind speeds, and the greatest atmospheric stability.

Fig. 4

Overhead view of the Burro 8 vapor cloud. The spill facility is at the far right, with the spill pipe extending out into the cloud. Towers placed along the 57-m arc from the spill point are visible in the center of the cloud, which is moving to the left.

Fig. 5

Horizontal LNG vapor-concentration contours in the Burro 8 test at an elevation of 1 m after 200 s. The Burro 8 cloud was the only one to exhibit this bifurcated structure. The contours show volume percent and end at the edge of the instrument array. The shaded area is the maximum flammable zone where the gas concentration is 5% or greater.

conduct additional large gravity-spread experiments.

Differential Boiloff

In most of our tests, the primary constituent of the LNG was methane (about 95%), with smaller fractions of ethane, propane, and other heavier hydrocarbons. In almost every test, however, the concentration of higher hydrocarbons increased noticeably near the end of the spill (Fig. 7). In some tests, heavier hydrocarbons increased to as much as 50% of the total during the time when the fuel-air mixture was still above the flammable limit, though the original LNG contained less than 10% higher hydrocarbons. This phenomenon is caused by the large difference between the boiling point of methane and that of other hydrocarbons in LNG. After an initial flash of vapor having about the same composition as the liquid, the methane boils off first, leaving behind a mixture even richer in heavy hydrocarbons that finally vaporizes near the end of the boiling process.

It has been demonstrated that enriched fuel-air mixtures like those we observed detonate much more easily than methane-air mixtures.^{4,5} It is not known, however, whether a detonation

Fig. 6

Mean wind speed during the Burro 8 test at a station upwind of the spill pond (a) and at a station downwind of the spill pond within the gas cloud (b). The ambient wind field was effectively displaced above the cloud, the wind speed in its interior dropping essentially to zero. The shaded zone indicates the time during which the vapor cloud was passing the sensor.

in the enriched portion of the cloud will continue to propagate into the methane-air portions, which of course are much larger.

Rapid-Phase-Transition Explosions

When two liquids at very different temperatures come into contact, the hotter one—if it is above the boiling point of the colder—usually will cause the latter to boil rapidly. In certain circumstances, however, the colder liquid rather than boiling will become superheated. Should the liquid reach its superheat limit, it will instantaneously flash into vapor, creating a pressure wave. Such an event is called a rapid-phase-transition (RPT) explosion.

Small-scale experiments on RPTs in LNG-water mixtures were conducted elsewhere in the early 1970s.⁶ On the basis of the reported results, others had predicted no RPTs would occur in our experiments. Contrary to expectation, however, we observed damaging RPTs in both the Burro and Coyote series. In the Burro series, large RPT explosions occurred in two tests. In Burro 9, more than 20 explosions took place at or below the surface of the water, with the largest producing an overpressure 30 m from the spill point equivalent to that produced by 7 kg of TNT. These explosions tore the spill plate from the spill pipe and threw it 50 m, pushing back the spill pipe's half-tonne support about 1 m. As a result, we examined the RPT-explosion phenomenon more systematically in a subseries of the Coyote experiments. In these tests, we spilled LNG, liquefied methane, and liquid nitrogen onto water, varying both the depth of the spill plate and the spill rate.

Our results show that RPTs appear to arise from two different processes, one related to differential boiloff of the liquid and the other to the spill rate. Differential-boiloff-related RPTs occur late in the spill and can occur anywhere on the LNG pool floating on the water's surface. The size of the explosion is not obviously correlated with any spill parameter (larger explosions were infrequent in our tests). These

differential-boiloff-related RPTs appear to be consistent with the earlier small-scale results. In contrast, spill-rate-related RPTs occur at the spill point, often deep underwater. They begin within a few seconds of the onset of the spill and usually continue throughout the spill. In this type of RPT, the size of the explosion seems to correlate positively with spill rate (see Fig. 8),

Fig. 7

Concentration of ethane plus propane (upper plots) and of methane (lower plots) vs time in the Burro 8 test. The data were taken from infrared sensors at distances of 57 m (a) and 140 m (b) from the spill point. As in most of the tests, differential boiloff caused a noticeable increase in the fraction of higher hydrocarbons in the vapor near the end of the spill.

Fig. 8

Effect of spill rate on the yield of rapid-phase-transition explosions observed during our large LNG spills. The size of the explosion correlates positively with spill rate.⁷

Fig. 9

Results of small- and large-scale spill tests using LNG of varying composition. The Enger-Hartman RPT explosion envelope, the enclosed area outlined in color at the left, is based on data from Shell Pipeline Corp., experiments indicating that RPT explosions occur only for LNG with a composition falling within the envelope (see Ref. 6). In contrast, the LLNL explosions fall well outside the envelope. It has been suggested that the LNG in our tests may have been enriched as it left the warm spill pipe during the prespill cooldown procedure. However, the asterisk indicates an estimate of the maximum possible test-induced enrichment for the most enriched LNG used in the Coyote series, and even the first cubic metre of LNG during that spill was outside the Enger-Hartman RPT envelope.

becoming large rapidly once the spill rate is above a threshold.⁷ The explosions are fairly reproducible, the larger frequently occurring when the pond temperature is above 17°C, the water depth at the spill point is greater than a few centimetres, and the spill rate is above 16 m³/min.

It has been claimed that the composition of the LNG being spilled is a crucial parameter associated with the occurrence of RPTs. In the small-scale studies cited earlier, among the most thorough and extensive to date, the amount of LNG spilled was small (about 0.1 m³) but the number of spills large, lending credibility to the results (summarized in Fig. 9 for methane, ethane, and propane mixtures). The investigators concluded that RPT explosions occur only when the LNG composition lies within the envelope shown in Fig. 9

or is allowed to "age" (through differential boiloff) into the envelope. Our large-scale China Lake results for spill-rate-related RPTs, however (also shown in Fig. 9), are clearly well outside the envelope. The large-scale tests also show no consistent relationship between spills of LNG with a similar chemical composition and the occurrence of an RPT explosion.

The discrepancy between our results and those of the small-scale studies suggest that factors other than prespill composition dominate the occurrence of RPT explosions in large-scale spills. It has been suggested that our LNG may have been enriched on its way out of the warm spill pipe during the prespill cooldown procedure. Figure 9 shows the estimated maximum possible cooldown enrichment for the most enriched LNG used in the Coyote series. Even the first cubic metre of LNG during that spill, however, was well outside the composition envelope claimed by the prior investigation.

We cannot conclude from these results that enrichment has nothing to do with RPT explosions. Indeed, delayed RPTs must result from differential boiloff on the pond. In addition, some form of local or transient enrichment may play a role in early RPTs. Nonetheless, our results indicate that prespill composition alone does not indicate the likelihood of an RPT.

Our observations on RPT explosions and differential boiloff raise a disturbing new possibility. As noted earlier, differential boiloff can highly enrich the late portions of a vapor cloud, making it more susceptible to chemical detonation by a shock wave. Because one type of RPT explosion is also related to differential boiloff, it is most likely to produce a shock wave in a cloud just at the time it is most sensitive to detonation. We observed no spontaneous detonations in the China Lake experiments. Our current data, however, do not reveal what the maximum size of RPT explosions can be in real accidents. To resolve this issue, tests with larger spill rates and more extensive measurements of near-field, RPT-induced shock-wave structure are necessary.

Fig. 10

Combustion of the vapor cloud formed during a 40-m³ LNG spill. Note the heat-distorted image of the hills in the background. The tall flame is moving to the left past two 60-m towers.

Vapor-Cloud Combustion

When a flammable cloud is ignited, several factors determine the damage resulting from the combustion process. In our experiments, we averted cloud detonation, potentially the most damaging event, by not igniting the cloud with a strong source (a shock) in its enriched portion and by not confining it. If an ignited cloud does not detonate, the damage zone depends on how fast the flame moves, how far into the lean region it burns, and the intensity of its emitted thermal energy. In the Coyote series of five vapor burns, we examined the effects of all these variables. (Table 2 summarizes test conditions for the burns.) Figure 10 is a photograph of one burn. The fire was ignited to the right of the right-hand tower. After ignition, the flame separated and moved both upwind (to the right) and downwind (to the left) through the premixed cloud.

We measured preignition vapor-concentration contours in all tests. The clouds were ignited either by flare or by jet. We used four techniques to measure flame speed: high-speed optical cameras, side-on infrared imagery, overhead infrared imagery, and *in situ* instruments. In Coyote 6 and 7, the overhead infrared imagery enabled us to follow the flame front in both the upwind and downwind directions. The data are plotted in Fig. 11. With either ignition source, velocities were very high (about 40 m/s) near the source but fell off rapidly as the flame moved away in both directions. The flame velocity appeared symmetric to the source in relation to the wind. Other measurements of flame velocity in our experiments were consistent with these results.

Our observations are in striking contrast to those of Shell Ltd., which performed a series of smaller vapor burns at Maplin Sands in the U.K.⁸ In these experiments, no flame velocities greater than 10 m/s were observed, and most were around 5 m/s. In some of their fires, the flame front moving into the wind stagnated; in ours it never did. Our side-on infrared imagery also showed flame heights of about 60 m,

Table 2 Summary of Coyote vapor-burn series.

Test number	Methane, %	Spill rate, m ³ /min	Spill duration, min	Wind speed, m/s	Ignition source	Ignition time, min
Coyote 2	70	16	0.5	5.9	Flare	1.2
Coyote 3	79	14	1.1	5.8	Flare	1.7
Coyote 5	75	17	1.6	10	Flare	2
Coyote 6	82	17	1.4	4.8	Flare	1.9
Coyote 7	99.5	14	1.9	6	Jet	2.4

four times those measured by Shell in LNC fires.

It is too early in our analysis of the Coyote vapor burns to draw firm conclusions. We have not yet examined the radiometry data, for example, nor have we compared our burn areas to the pre-ignition concentration contours. However, preliminary data on flame velocity and height suggest that our final results will differ markedly from those of smaller-scale studies. These rather systematic discrepancies between small- and large-scale results seem to indicate that our 40-m³ experiments mark the threshold for observing the effects most likely to dominate larger spills.

Modeling Vapor-Cloud Behavior

We compared our results from the Burro experiments with predictions from three vapor-dispersion models of the release of a cold, dense gas. The

Fig. 11

Flame speed in the Coyote 6 (a) and Coyote 7 (b) tests as a function of distance in the upwind and downwind directions, taken from overhead infrared measurements. The velocities are very high near the ignition source and fall off rapidly as the flame moves away in both directions.

Germeles-Drake (GD) model, a modified Gaussian-plume model, is the simplest.⁹ The second model, SLAB, is a time-dependent, layer-averaged model with one independent spatial variable, downwind distance.¹⁰ The third model, FEM3, is based on fully three-dimensional, time-dependent conservation equations.¹¹

The tests verified our hypothesis that a large cloud behaves quite differently from a small one.

Each model takes a considerably different approach to simulating the atmospheric dispersion of a cold, dense gas. The most obvious difference is the degree to which they incorporate the basic conservation laws and three-dimensional effects. The GD model is based on the single conservation-of-species equation. In determining the dimensions of the vapor cloud at the source, it neglects momentum and energy effects after the initial gravity-spread calculations. The SLAB model, in contrast, includes the conservation equations for mass, momentum, and energy in addition to the species equation, but only in an average way. SLAB neglects variation in the crosswind plume and expresses all properties of the vapor cloud as crosswind averages that vary in the downwind direction only. Finally, the FEM3 model embodies the most comprehensive description of the conservation laws by treating them explicitly in three dimensions.

(Our calculations with FEM3 also included the effects of terrain at the China Lake site.)

Our extensive comparison of measured cloud contours with those predicted by the models indicates that of the three, the GD model performed significantly worse than the others. It always predicted a cloud narrower and taller than observed. The model also seriously underpredicted the downwind LFL in moderate and high winds and overpredicted it for the low wind speed in the Burro 8 experiment (Table 3).

The striking bifurcated plume seen only in the Burro 8 experiment provided another critical test of the models. Only the FEM3 model predicted this behavior. Figure 12 shows crosswind contour plots obtained from our data and from two FEM3 calculations, one with flat terrain and one with the real, variable terrain. Extensive comparisons of FEM3 calculations and the data indicate that the bifurcation was caused by an aerodynamic interaction between the atmosphere and the vapor cloud. Furthermore, although the bifurcation would occur even with flat terrain, it was clearly accentuated by real terrain effects at China Lake.

The relatively good performance of the FEM3 model, and its prediction of the general behavior of the Burro 8 cloud in particular, strongly encourage us to believe that it may be able to handle larger clouds. Data from larger dispersion tests will be necessary to confirm this. Conversely, we have no confidence that simple models, such as the GD model, will predict large-cloud behavior. Although the SLAB model cannot predict the bifurcated structure because of its inherent one-dimensional form, it did not do badly on the length, width, and height of the observed clouds. Because SLAB is simpler and runs much faster on a computer than the FEM3 model, we will continue to develop both. It may prove feasible to use the more sophisticated FEM3 model to establish the range of validity of the SLAB model, which can then be applied with more confidence.

We have not yet compared data with model predictions for RPT and cloud-

combustion phenomena. Our data conflict with current models that predict when RPTs will occur, although they are not conclusive enough to suggest a better approach. Some theories do suggest an upper limit to the yield of RPT explosions; testing these will require spill rates higher than $20 \text{ m}^3/\text{min}$. LLNL has two and three-dimensional combustion models that, given a burn velocity, predict fire dynamics. We intend to use these to try to reproduce the height and area of the China Lake fires as a function of time.

Summary

The results of our 40-m^3 LNG experiments have extended our understanding of the hazards posed by a large spill of LNG (or, for that matter, any other material that forms a toxic or flammable cloud). The tests verified our hypothesis that a large cloud behaves quite differently from a small one. Clouds enriched by heavier hydrocarbons resulting from differential boiloff may be more easily detonated. RPT explosions may play an important role in determining the outcome of a spill. Our analysis of the vapor burn tests is still in its early stages; the fires and flame velocities we observed were larger than those reported in small-scale experiments, but establishing scale-related effects will require further examination of the data.

Comparisons of model calculations with the data from our cloud-dispersion tests are encouraging. The sophisticated three-dimensional FEM3 model successfully accounted for cloud bifurcation and terrain effects and gave reasonably accurate values for measured downwind LFL. The simpler, crosswind-averaged SLAB model also gave reasonable LFL values, though because of inherent limitations it could not reproduce the bifurcation or terrain effects. As a result, the LNG community now has both a sophisticated and a relatively simpler model that it can use with some confidence for spills up to 40 m^3 . Our comparisons also revealed serious deficiencies in Gaussian models. These models, such as the Germeles-Drake model, should not be considered

Table 3 Maximum downwind extent of the lower flammability limit in three Burro experiments compared with model predictions.

Test number	Downwind lower flammability limit, m				
	Measured	GD model	SLAB model	FEM3 model	FEM3 with terrain
Burro 7	250	150	264	210	^a
Burro 8	470	661	418	460	400
Burro 9	320	235	315	340	325

^aNo calculation done.

conservative under all atmospheric conditions and should be abandoned.

Our results confirmed that 40-m^3 LNG experiments mark a threshold for observing large-cloud effects. Models that can reproduce the 40-m^3 results should be used next to predict the behavior of larger spills. Dispersion, vapor-burn, and RPT experiments conducted in LNG spills of 100 to 200 m^3 would provide a fair test. If the correlations between models and experiments that we obtained in the 40-m^3 spills can be validated for 200-m^3 spills, then we believe we can extrapolate these models to LNG accidents of any feasible size with reasonable confidence.

Fig. 12

Measured and calculated crosswind vapor-concentration contours (in percentages, looking toward the source) in the Burro 8 test. (a) Contour measured at 140 m after 180 s. Dashed lines indicate the outer extent of the instrument array. (b) Contour calculated with the FEM3 model, the best of the three models we employed, under the same atmospheric conditions assuming a flat terrain. (c) FEM3 calculation with a variable terrain approximating the China Lake terrain.

To carry out the additional experimental work, we will need a new facility. The U.S. Department of Energy (DOE) is encouraging industry to assume more responsibility in the type of safety study described here, and the American Gas Association has proposed that the DOE permit industrial sponsor groups to use DOE facilities at the Nevada Test Site (NTS) and at LLNL for such further research. Therefore, this year we are attempting to form sponsorship consortia consisting of industrial and governmental organizations interested in continuing field-scale spill research. Because the spill phenomena to be measured are applicable to a wide variety of chemicals that form toxic and/or combustible clouds, we have received indications of interest from more than just the LNG community; to date, 52 industrial and governmental organizations have responded positively. If the DOE gives its approval, a flexible large-scale spill facility will be assembled at the NTS and a suitable organizational structure will be established to interact with the various user consortia. Such a national center for spill safety research would be able to address many of the issues important to protecting the public while allowing sensible use of hazardous materials. □

Key Words: Burro experiments; computer model—FEM3, Germeles-Drake, SLAB; Coyote experiments; liquefied gaseous fuels (LGF); liquefied natural gas (LNG); rapid phase transition (RPT); Spill Effects Program.

Notes and References

1. G. D. Hilbert, J. H. Berkley, Jr., and F. M. Quinn, *Mississauga, Lessons in Large-Scale Evacuation, 1982 Hazardous Material Spills*

- Conference, Government Institutes, Inc., Rockville, Maryland (1982).
2. R. P. Koopman, L. M. Kampainen, W. J. Hogan, and C. D. Lind, *Burro Series Data Report: LLNL/NWC 1980 Spill Tests*, Lawrence Livermore National Laboratory, Rept. UCID-19075 (1981).
3. R. P. Koopman et al., "Analysis of Burro Series 40-m³ LNG Spill Experiments," *Dense Gas Dispersion* (special issue of *J. Hazardous Materials* 6, 1 and 2, 1982).
4. D. C. Bull, J. E. Ellsworth, and G. Hooper, "Initiation of Spherical Detonation in Hydrocarbon/Air Mixtures," presented at 6th International Colloquium on Gas Dynamics of Explosions and Reactive Systems, Stockholm, Sweden (1977).
5. C. K. Westbrook and L. C. Haselman, *Chemical Kinetics in LNG Detonations*, Lawrence Livermore National Laboratory, Rept. UCRL-82293 (1979).
6. T. Enger and D. E. Hartman, *LNG Spillage on Water. II. Final Report on Rapid Phase Transformations*, Shell Pipeline Corp., Research and Development Laboratory, Houston, Texas, Technical Progress Report No. 1-72 (1972).
7. T. McRae, *Analysis of Large-Scale LNG/Water RPT Explosions*, Lawrence Livermore National Laboratory, Rept. UCRL-88421 (1982).
8. J. A. Eyre, "Recent Large-Scale Experiments to Investigate the Combustion of Refrigerated Gas Spillage," *MIT-GRI LNG Safety and Research Workshop* March 1982, vol. 3, *LNG Fires—Combustion and Radiation*, Burlington, MA (1982).
9. A. E. Germeles and E. M. Drake, "Gravity Spreading and Atmospheric Dispersion of LNG Vapor Clouds," *Proc. 4th International Symposium on Transport of Hazardous Cargoes by Sea and Inland Waterways*, Jacksonville, Florida (1975).
10. O. Zeman, "The Dynamics and Modeling of Heavier-Than-Air Cold Gas Releases," *Atmos. Environ.* 16, 741 (1982).
11. S. T. Chan, P. M. Gresho, and D. L. Ermak, *A Three-Dimensional, Conservation Equation Model for Simulating LNG Vapor Dispersion in the Atmosphere*, Lawrence Livermore National Laboratory, Rept. UCID-19210 (1981).

Using an immense laser to implode a tiny precision-fabricated target containing deuterium and tritium is only part of the inertial-confinement fusion (ICF) research picture. A major part is measuring what happened during the implosion (diagnostics) and interpreting the data. The soft, subkilovolt x-ray spectrum emitted from a laser-produced plasma is an important indicator of the plasma temperature. Measuring this spectrum provides us with invaluable and otherwise unobtainable information about plasma conditions in an ICF experiment.

ICF implosion diagnostics are challenging because the signals from them are both weak and brief. Recently, we have developed a number of sophisticated techniques for measuring the spectral distribution of the x rays generated in these microexplosions. Application of these techniques has resulted in several new instruments of greatly improved energy and time resolution and have extended the range of our measurements to x-ray energies as high as 300 keV. Use of these new instruments with the Argus and Shiva lasers has had a major impact on our understanding of the physics of laser-produced plasmas.

The original (and still standard) instruments for measuring high- and low-energy x rays in ICF experiments are the filter fluorescer and the Dante spectrometer (so called because it looks at the Inferno and reports on conditions there).¹ Both of these instruments are based on x-ray filters, each of which transmits a different portion of the x-ray spectrum. The Dante spectrometer (useful only in the low-energy range) contains as many as ten x-ray-sensitive diodes, each covered by a different filter and each sending its signal to a different transient recorder (either an oscilloscope or a digitizer). In the filter fluorescer, the filtered x rays fall on a fluorescer and only the fluorescent x rays reach the photodiode detector.

Such measurements yield a low-resolution set of data over a moderate energy band centered at different

energy values. The time-resolution is defined by the combined response times of the diodes and the oscilloscopes. Some of the Dante channels are relatively fast (about 150 ps) but most are slow (600 ps). The filter-fluorescer channels are even slower because of the use of highly sensitive but slow detectors.

Most of our new instruments achieve high time-resolution through the use of our LLNL-developed electronic streak camera (see box on p. 16). The electronic streak camera provides a continuous record, analogous to a strip-chart recording, of how some quantity varies with time. Because it combines the detector and display into one instrument, this form of streak camera is capable of extremely fast writing speeds. Its temporal resolution is estimated at 20 ps, almost ten times better than the fastest Dante-spectrometer channels. Table 1 compares the sensitivities and resolutions of the various x-ray spectrometric techniques that are discussed here.

Multilayer-Mirror Streak Camera Spectrometer

The multilayer-mirror x-ray spectrometer, shown in Fig. 1, uses a five-segment interference mirror to select five different narrow spectral bands of the soft x rays from the laser-irradiated target, rejecting the rest.¹ Each segment of the mirror has a vacuum-deposited (sputtered) coating consisting of many alternating layers of high-Z and low-Z material. By choosing appropriate materials and carefully controlling the thickness of each layer, we can make each segment of the mirror preferentially reflect x rays of a different energy onto the slit of the streak camera [i.e., those that satisfy the condition for Bragg interference $\lambda = 2d \sin\theta$, where λ is the wavelength (inversely proportional to energy), d is the layer thickness, and θ is the angle of incidence].

The diffracted x rays, five beams at five different energies travelling side by side, next go to a segmented filter, each section of which is tuned to pass only the particular energy beam of x rays that has been reflected by the

multilayer mirror. The purpose of this filter is to remove from the beam extraneous x rays scattered or reflected from the mirrors.

Each filtered beam then falls on a different part of the streak camera's entrance slit and illuminates a different part of a photocathode. The streak camera electronically sweeps the resulting slit image across a fluorescent screen, producing a visible two-dimensional image of the x-ray intensity at five separate narrow energy bands as a function of time. The visible image is recorded on film or stored electronically in an array of CCDs (charge-coupled devices).

One of the advantages of this multilayer-mirror technique is that it records all five spectral bands simultaneously, on the same instrument. The Dante spectrometer we use for similar measurements requires a separate detector channel for each selected energy segment. Each channel is recorded on one oscilloscope or fast transient digitizer. In addition, each Dante channel is recorded on its own oscilloscope.

The inset in Fig. 1 graphically illustrates the resulting output from the multilayer-mirror spectrometer. Each plane represents the x rays recorded for a single channel, and the height represents the intensity of those x rays as a function of time. The more energetic x rays are in the foreground. By comparing the five bands of data, we find that the hard x rays appear later in time than the softer x rays, rise to lower intensities, and die away more rapidly.

Fig. 1

(a) Multilayer-mirror streaked spectrograph capable of simultaneously recording five channels of information on soft x-ray intensities in ICF experiments. (b) Three-dimensional graph of resulting output (intensity vs time as a function of energy).

High-Speed Cameras and Techniques

High-speed cameras originally were just motion picture cameras modified to run at high speed. Such framing cameras, which record motion with a series of still photographs, have advanced to the point of expanding into a viewing segment of tens of minutes events that unfolded in a very few seconds. Although the viewer perceives what looks like a smooth and continuous motion, the record is actually discontinuous, omitting the information between the frames.

Framing cameras are ideal for recording the actions of a figure skater or the reactions of dummies in a high-speed

automobile collision. For some subjects, such as an exploding system, however, what we really want is a continuous record of a change in shape or in light intensity. For such subjects, a streak camera provides the required continuous record.

A streak camera sacrifices the overall view of a subject to obtain more detail in a restricted view. A conventional (optical) streak camera focuses an image of the subject on an opaque plate with a slit in it. Another lens projects an image of the slit (and the thin slice of the subject's image

that passes through it) onto one edge of a photographic film. A spinning mirror, synchronized with the action we want to record, sweeps the slit image at high speed across the film, producing a streaked image that records variations in the dimensions and intensity of the thin slice of the subject.

The electronic streak camera carries this concept one step further (see figure). In this case, light (or x rays) enter the streak camera through a slit and impinge immediately on a photocathode, thus producing photoelectrons. The electrons are accelerated by high voltage, focused, and swept across a phosphor where they are converted to light. This light is then recorded on film or a charge-coupled device. The energy spread in the electrons at the photocathode ultimately determines the time resolution of the instrument because electrons of different energies are swept at different rates. Here, we are not using the streak camera to take pictures of an event; rather, we use each point on the streak camera's entrance slit as a separate energy information channel.

An oscilloscope also operates without moving parts, so in principle it could be made as fast as the streak camera. None are, however, partly for economic reasons but mainly because they are designed to be used with auxiliary equipment that limits their time resolution. The Dante spectrometer is slower than the streak camera, not only because its oscilloscope and detector are slow, but also because they are separate. The necessary connecting cable introduces inductance and capacitance into the circuit, lengthening the time it takes for abruptly rising signals to build up on the oscilloscope.

The electronic streak camera is free of these limitations. Since it has never been limited by the capabilities of auxiliary equipment, its sweep is three to four times faster than that of the best available oscilloscope. Furthermore, combining the detector and sweep into one instrument eliminates the x-ray to electronic converter and the connecting cable and its effects.

Reflector-Filter Streak Camera Spectrometer

The reflector-filter spectrometer² instrument differs from the multilayer-mirror instrument mainly in the use of highly polished surfaces (grazing incidence x-ray mirrors) in place of multilayers for energy discrimination (Fig. 2). Below the so-called critical energy (determined by the reflection angle and the mirror's atomic number), the mirror surface reflects x rays; higher energy x rays are absorbed. The reflected beam then goes to a filter that absorbs unwanted low-energy x rays, letting through a broad slice of the energy spectrum. The three x-ray beams so defined then go to the streak-camera slit where they are resolved in time and then recorded as a two-dimensional, intensity-modulated image.

The main spectral definition for this spectrometer is provided by the filter, with the mirrors serving primarily to cut off the higher photon energies. This instrument has broader energy resolution than the multilayer interference spectrometer (Table 1), but the x-ray streak camera provides the same excellent time resolution on both. The three energy channels shown in Fig. 2 can be expanded to six by splitting each beam and adding another set of filters.

Figure 2 also shows a streaked record from this spectrometer, using x-ray filters of carbon, vanadium, and iron, measuring the radiation from an experimental laser-irradiated target. The indicated energy ranges are from 510 to 710 eV for the iron filter, 280 to 510 eV for the vanadium filter, and 160 to 280 eV for the carbon filter. Computer processing has color-coded the intensity contours of the image to make it easier to see the intensity variations. The time variation of the x-ray intensity in the three channels is also shown graphically.

Transmission-Grating Streak-Camera Spectrometer

Our new transmission-grating spectrometer³ differs from the two instruments described above and from the

(a)

Fig. 2

(a) The three-channel reflector-filter streak-camera spectrometer for measuring soft x-rays, as mounted on Shiva. (b) Computer-enhanced color and (c) microdensitometer traces of reflector-filter spectrometer data.

Table 1 Resolution and range parameters for various x-ray detection systems.

System	Resolution		Energy range, keV	Channels
	Energy, E/ΔE	Time, ps		
Low energy				
Dante	2.0-4.5	150	0.01-2.0	10
Multilayer-mirror streak	30-100	20	0.1-1.0	5
Reflector-filter streak	3-10	20	0.2-0.7	3-6
Transmission-grating streak	4-125	20	0.1-1.5	Continuous
High energy				
Filter fluorescer	3-9	500-3000	1.5-100	10
Optical streak	about 1	10	above 25	1
Hyper filter fluorescer	1	—	150-300	4

Dante spectrometer in that it produces a continuous record of the x-ray spectrum over a broad range instead of a series of discrete moderate or narrow slices (Fig. 3). This is useful in cases involving line radiation, which may occur at some energy between those selected by the mirrors or filters and thereby be overlooked in our measurements.

The geometry for this instrument is shown in Fig. 4. A free-standing linear array of gold slats (arranged like the slats in a Venetian blind) about $0.5\text{ }\mu\text{m}$ wide and spaced $0.3\text{ }\mu\text{m}$ between centers functions like a diffraction grating in an optical spectrometer.⁴ It disperses the x-rays from the experiment into an energy spectrum along the slit of an x-ray streak camera. With this instrument, we made the first time-resolved continuous low-energy (100 eV to 1.5 keV) x-ray spectrum measurement from a laser irradiated target, as opposed to constructing the spectrum from discrete Dante measurements.

The resulting streak-camera record (Fig. 4 inset) yields direct experimental observation of prominent line radiation and absorption bands. The first bright band is made by undispersed x rays that came straight through the gold transmission grating. Next comes a broad band of high-energy (0.7- to 1.1-keV) x rays, actually unresolved line radiation from recombinations involving N-shell electrons in gold ions in the plasma. The darker band following is an artifact of the instrument, caused by

Fig. 3

A hypothetical x-ray spectrum and typical response curves for the multilayer-mirror spectrometer (red), the reflector-filter spectrometer (blue), and the grating spectrometer (black).

Fig. 4

The experimental setup for the transmission-grating soft-x-ray spectrometer. Inset: streaked continuous spectrum.

absorption of x rays in the streak-camera entrance window. The bright band after that is part of the continuous low-energy x-ray spectrum, illustrating the sharpness of the window's K-edge cutoff at 0.28 keV.

Optical Streak Camera X-Ray Spectrometer

The three spectrometers discussed above perform best in the low-energy

range (0.01 to 2 keV) and discriminate against the high-energy x rays (2 to 300 keV). These high-energy x rays are important, however, because they serve as a measure of the suprathermal (high-energy) electrons. It is one of our goals to suppress these electrons because they can preheat the fuel in a laser fusion target, stiffening it against compression and thereby interfering with the implosion.

Fig. 5

(a) Experimental setup for the optical/x-ray streak camera, showing the system for introducing a fiducial marker (the optical fiber and related components at the top of the figure).
(b) Streaked image from experiment;
(c) resulting microdensitometer trace.

Among clues to the nature of these high-energy electrons (and to possible methods of eliminating them or preventing their formation) are the shape of their energy spectrum and the time history of their appearance during the laser heating. It is also important to measure their absolute intensity. We have made major advances in techniques for measuring these quantities.

Our original instrument for measuring high-energy x rays is the filter-fluorescer spectrometer, which is effective to about 100 keV. This technique is similar in principle to the simpler x-ray filter-detector spectrometer (Dante), but it is effective in a much higher energy range. However, the time resolution for the filter-fluorescer spectrometer is limited by the time response of its detectors. The fastest of these, a fluor-microchannel plate combination, has a time resolution of 500 ps; most of the other channels record at 3000 ps.

Our new high-energy x-ray spectrometer uses an optical streak camera as a combination detector-recorder. It responds to optical light and to x rays energetic enough to penetrate its thick entrance window. Its time resolution is 10 ps. By simultaneously measuring the scattered laser light and high-energy x rays, we determine when the hot electrons were produced with respect to when the laser light was being absorbed.

We interpose a compound filter that transmits x rays only on one side (left, Fig. 5) and light only on the other (right, Fig. 5). X rays pass readily through thin aluminum foil, which is totally opaque to visible and infrared light. A layer of lead glass about 2 cm thick, however, can stop x rays and yet be transparent to infrared ($1.06\text{-}\mu\text{m}$) light from the laser.

Figure 5 outlines the experimental setup. X rays and scattered $1.06\text{-}\mu\text{m}$ light from the target pass through the filter and are measured. We also bring in $1.06\text{-}\mu\text{m}$ light by a separate channel to serve as an optical fiducial to mark the instant when the incident laser light strikes the target.

As mentioned above, the optical streak camera responds to x rays only if

they are energetic enough to pass through its entrance window. We are having a special thin-window streak camera made, using a mica window, to incorporate several lower energy channels into the same instrument.

Figure 5 also shows the streaked image from such an experiment and the resulting microdensitometer trace indicating the variations of intensity with time of incident laser light ($1.06\text{-}\mu\text{m}$ wavelength) and x rays above 25 keV. The x rays occur early in the laser light pulse and die away while the laser is still delivering energy at nearly peak intensity. These results depend on the target used, and their full significance is still under investigation.

Hyper Filter Fluorescer Spectrometer

The standard filter fluorescer technique was developed in the Nuclear Test Program for Nevada applications.⁵ It uses elemental materials in combination so that their x-ray edges define the spectral slice seen by each channel in the spectrometer (Fig. 6). The filter passes x rays of low energy and cuts off those above a certain value (different for each material). The fluorescer responds to x rays above a certain minimum energy by emitting x rays of a characteristic energy. If we choose a pair of materials such that the filter's cutoff is just above the fluorescer's threshold, the response of a detector shielded from all direct radiation and seeing only the x rays from the fluorescer will be proportional to the intensity of x rays in a narrow slice of the original x-ray spectrum.

Fig. 6

Filter-fluorescer operation. The brown area indicates the detector response, which is proportional to the product of the filter transmission (blue) and the fluorescer response (red).

This scheme suffers from a few drawbacks and limitations. Neither the filter nor the fluorescer behaves exactly according to the above description, so that the detector also sees a contribution from the small high-energy bump (due to a higher energy x-ray edge) in the response curve (Fig. 6). Various methods have been developed to suppress this bump, confining the instrument's response more nearly to the desired narrow spectral slice.

Another limitation has to do with the available materials. The K-edge cutoff of uranium, the highest of any practical filter material, is about 120 keV. Making a filter-fluorescer responsive to energies above 120 keV required a rethinking of the entire detection scheme.

What we did, in essence, was to choose a set of "incompatible" filter-fluorescer pairs. We kept the experimental geometry the same, but used a fluorescer whose threshold was above the filter's cutoff energy. This eliminated the usual spectral slice, leaving only the high-energy bump.

Stated thus, this seems like a trivial accomplishment, but the result is not. The standard scheme for measuring these x rays above the range of the normal filter fluorescer was to use a thick lead filter on a Dante-style filter-detector instrument. This effectively removed all x rays below a certain energy, but it registered all the rest, no matter how high their energy. Our new filter-fluorescer technique registers mainly those x rays within a given energy range, discriminating against those both below and above, and giving much better spectral definition to the measurements.

We used this technique at the Shiva laser facility to produce the spectrum

shown in Fig. 7; our highest energy point is well above 300 keV.

Conclusion

We have developed an array of spectrometers of various sensitivities and temporal resolutions. These advances expand the range of phenomena we can investigate, both in energy and in time. Together with our already extensive instrumentation, they give us the capability to provide timely and accurate data in the rapidly evolving fields of plasma physics and inertial confinement fusion.

We have already acquired a great deal of experience with Dante and filter fluorescer spectrometers and have been able to perform absolute calibrations that enable us to make quantitative measurements. So far, however, none of our new instruments has been calibrated absolutely, and this produces only relative measurements; we still need to supplement their output with simultaneous Dante and filter fluorescer measurements. Only when we devise absolute calibrations for these new instruments, or do enough cross comparisons, will it become possible to lessen our reliance on the Dante and filter fluorescer spectrometers. □

Key Words: Dante; diagnostics—ICF; inertial confinement fusion (ICF); laser fusion—experiments; streak camera; x-ray spectroscopy.

Notes and References

1. G. Stradling, *Multilayer X-Ray Interface Mirrors for an Improved SXRSC Spectrometer*, Lawrence Livermore National Laboratory, Rept. UCRL-50021-80 (1980).
2. R. Kauffman, G. L. Stradling, E. L. Pierce, and H. Medeck, *Quantitative Measurements Using Soft X-Ray Streak Cameras*, Lawrence Livermore National Laboratory, Rept. UCRL-85977 (1981).
3. N. M. Ceglio, R. L. Kauffman, A. M. Hawryluk, and H. Medeck, *A Time-Resolved X-Ray Transmission Grating Spectrometer for Investigation of Laser Produced Plasmas*, Lawrence Livermore National Laboratory, Rept. UCRL-87800 (1982); this instrument was used in the experiment described on p. 23 of this issue of *Energy and Technology Review*.
4. A. M. Hawryluk et al., *J. Vac. Sci. Tech.* **19**, 897 (1981).
5. The technique of x-ray spectral analysis using K-edge filters and fluorescers has been developed during the last three decades at LLNL and Los Alamos. See C. L. Wang, *Rev. Sci. Instrum.* **52** (9), 1317 (1981).

Fig. 7

Composite high-energy x-ray spectrum obtained with the filter fluorescer x-ray spectrometer (up to about 100 keV) and the hyper filter fluorescer spectrometer (out to more than 300 keV).

Laser-Heated Flashlamps: a Step Toward a Soft X-Ray Laser

Experiments conducted jointly by our
Laser and NLTE* Research Programs
with the Laboratory's Shiva laser
have explored the feasibility of
using a laser-heated flashlamp
to produce a bright, uniform
source of x radiation in the
wavelength range required
for a photoexcitation
pump for a soft
x-ray laser.

For further information contact
Dennis L. Matthews (415) 422-5360,
Peter L. Hagelstein (415) 422-7297,
or Mike Campbell (415) 422-0676.

*NLTE: Not in Local Thermodynamic Equilibrium.

Lasing at x-ray wavelengths has long been pursued both as a challenging technical achievement and as an extremely fruitful extension of the already prolific uses of the optical laser. Applications range from the holography of deoxyribonucleic acid (DNA) molecules to x-ray lithography of microcircuits. As the brightest (i.e., most energetic) available source of coherent radiation, an x-ray laser also would be adaptable to photoelectron spectroscopy and phase-contrast microscopy.

The realization of an x-ray laser poses a complex technical challenge. This is primarily due to the lack of efficient large-angle mirrors from which to form a laser cavity. This results in the

apparent need to use dipole transitions to achieve high enough gains to produce significant laser action during a single pass through the laser material. The power needed to pump such dipole transitions scales as the inverse cube of the laser wavelength.

Several investigators have proposed various soft-x-ray lasing schemes using a neodymium-glass laser as the driving source. In the most promising,¹ the driving laser light is used to heat a flashlamp foil (Fig. 1). Upon ionization to a lower state, the foil emits x rays, which are, in turn, used to strip cold neon or fluorine gas down to a helium- or hydrogen-like state of ionization. The resulting ions are resonantly photoexcited by the appropriate x-ray emission line of the flashlamp foil to create a population inversion between either the $n = 4$ and $n = 3$ states or the $n = 3$ and $n = 2$ states (Fig. 2).

In an x-ray laser based on $n = 4 \rightarrow n = 3$ transitions in neon, the x-ray spectrum of the flashlamp foil must contain an emission line near a wavelength of 1.1 nm (within ± 0.0003 nm) to resonantly photoexcite helium-like ions from their ground state to their $n = 4$ excited state. Electron-ion collisions will then primarily populate states with higher angular momentum [such as the $1s4d(^1D)$, $1s4f(^1F)$ states], which are dipole forbidden to relax to the ground state (see Fig. 2). In addition, the lower state of the x-ray laser—

Fig. 1

In a resonantly pumped x-ray laser, light from a neodymium-glass laser is used to heat a metal flashlamp foil. The foil emits x rays that both ionize and (if the x rays are of the proper wavelength) create a population inversion in a gaseous medium, which lases to produce coherent soft x radiation.

Table 1 Candidate flashlamp materials and lasing media for a resonantly pumped photoexcitation x-ray laser.

Flashlamp material	Measured flashlamp pump line (λ), nm	Required flashlamp pump line (λ), nm	Lasing medium	Energy of lasing medium, eV
$n = 3 \rightarrow n = 2$ schemes				
B-like Cr	1.4458	1.4458	He-like F	119
Be-like Mn	1.2643	1.2643	H-like F	153
$n = 4 \rightarrow n = 3$ schemes				
Be-like Cr	1.3779	1.3782	He-like F	42.3
N-like Ni	1.1000	1.100	He-like Ne	53.6
He-like Na	1.1003	1.100	He-like Ne	53.6

the $1s3p(^1P)$ or $1s3d(^1D)$ state—rapidly decays by dipole emission to the $1s2p(^1P)$ or $1s^2(^1S)$ state. The lasing scheme based on the $n = 3 \rightarrow n = 2$ transition operates similarly, the $n = 3$ state being preferentially excited with a well-chosen flashlamp emission line.

Table 1 summarizes the critical properties of candidate flashlamp materials and lasing media proposed for the photopumped x-ray laser. Except for the helium-like sodium transition, all the pumping-flashlamp foil candidates emit x rays resulting from $n = 3 \rightarrow n = 2$ transitions in ions of moderate atomic number (24 to 28). Although Table 1 is not exhaustive, it represents candidates that have received the closest scrutiny.

X-Ray Lasing Experiments at LLNL

Early in 1983, we will begin a series of experiments to study the feasibility of lasing at x-ray wavelengths. Our technique will use the Laboratory's Novette laser system (which has two arms of the ten-arm Nova laser) to irradiate two thin metal foils with 532-nm laser light. Sandwiched between the foils is a layer of neon gas that serves as the x-ray lasing medium (see Fig. 1). The foils convert the laser light to x rays that are transmitted through the foils to ionize and preferentially excite certain atomic states in the neon gas, which then lases at soft-x-ray wavelengths.

Before we can quantitatively evaluate the proposed scheme, we must know the x-ray emission characteristics of the laser-irradiated flashlamp foils. The last series of experiments performed with the Laboratory's large Shiva laser (before it was dismantled in 1982) was designed primarily to characterize the x-ray emission spectra produced by some of the candidate flashlamp materials.

Design of the Shiva Experiments

Flashlamp Targets

The flashlamp targets consisted of thin metallic foils of iron, iron-copper,

chromium, or nickel about $0.04\text{ }\mu\text{m}$ thick and 2 mm in diameter (Fig. 3). The metal was deposited on a $0.5\text{-}\mu\text{m}$ -thick parylene disk that provided mechanical strength; the targets were suspended across a thin ($25\text{-}\mu\text{m}$ -thick) Mylar hoop 3 mm in outside diameter. To facilitate centering all of Shiva's ten

Fig. 3

Typical flashlamp-foil target used in the Shiva x-ray experiments. The metal foil was deposited on a parylene disk to provide mechanical strength. The targets were suspended across a thin Mylar hoop. The ball enabled us to center all of Shiva's ten lower beams on the target.

lower beams, we mounted an alignment ball 300 μm in diameter on each target. To ensure a uniform thickness and composition of the flashlamp targets, we measured the metal foils from which they were cut. The overall uniformity over thickness of about 100 μm (determined by both light transmission and sputter erosion) was at least 20%.

Flashlamp Diagnostics

The array of diagnostic instruments used in the Shiva experiments is shown in Fig. 4. Each flashlamp target was irradiated either normal to the lower set of Shiva's beams for absorption measurements, or rotated at an angle of 30 deg to the normal to enable the diagnostics to view both sides of the target. The primary diagnostic instruments consisted of four crystal spectrographs, which measured the time- and space-integrated x-ray spectra. To obtain information on the angular variation of the x-ray spectrum of the flashlamp foils, we placed two of the spectrographs in front of the flashlamp surface and two at its rear. The rearward spectrographs were of primary importance

because they measured the spectrum that will irradiate the lasing medium.² Calibrating the response of the film used in the spectrographs to the emitted x rays was a formidable task; it represents the least certain quantity in determining the absolute intensity of the x-ray lines emitted from the flashlamp foils.

The forward spectrographs were set to measure the x-ray emission spectrum from 0.7 to 1.4 keV, the rearward spectrographs from 0.7 to 1.2 keV. To calibrate spectral energy, we placed foils with known absorption characteristics over the entrance apertures of the spectrographs. We also calibrated the spectrographs to known spectral features of the iron and chromium foils. The rearward spectrographs were calibrated to photon energy within ± 4 eV; the accuracy of their absolute intensity measurements has not yet been determined. The forward spectrographs were calibrated to energy within ± 5 eV and to absolute intensity within $\pm 50\%$.

The time history (resolved to about 20 ps) of the L-shell emission was measured using a 300-nm-period gold transmission grating, coupled to a soft-x-ray streak camera.^{3,4} The spectral resolution of $E/\Delta E = 10$ was, however, insufficient to observe individual emission lines.

We used a polar 8 $\times$ Kirkpatrick-Baez microscope to measure the uniformity of the time-integrated x-ray emission from the extremely small spot size of the irradiated foil. The microscope was fitted with a 100-nm aluminum and 3.2- μm Mylar filter to examine x-ray energies of about 1 keV. The microscope viewed the rear of the target along the laser axis. Three Dante multi-channel x-ray diode systems provided high-precision broadband intensity measurements.⁵

Target absorption was measured with an array of scattered-light pin diodes, filtered to record wavelengths of 1064 nm, and with incident and back-scattered calorimeters. For the absorption measurements, the iron and iron-copper targets were oriented at normal incidence to facilitate angular integration over the finite pin-diode array. The

Fig. 4

Configuration of diagnostic instruments used in the Shiva x-ray experiments. To measure the x-ray spectrum emitted by the flashlamp target, two time- and space-integrated crystal spectrometers viewed it from the front (the surface irradiated by the laser light) and two from the rear. For absorption measurements, the target was irradiated normal to the beam axis. To enable the instruments to view it from both sides, the target was rotated 30 deg.

total energy, pulse length, and beam balance of the Shiva laser were also carefully monitored.

Experimental Results

The laser pulse widths were measured by three streak cameras and varied from 100 to 133 ps. Shiva's ten lower beams were overlapped to give a nominal spot diameter of 1 mm. Laser energies on target ranged from 142 to 374 J. Typical peak intensities of the incident laser light were 100 to 200 TW/cm².

Target Absorption

Because of the large effective f/number ($f/1$) of Shiva's beam clusters and the laser duration used (100 to 120 ps), the dependence of target absorption on the angle of incidence of the laser light should be negligible (at least for angles less than 30 deg). (This assumption is supported by experiments with the Laboratory's Argus laser where we used an enclosing box calorimeter to measure reflected and scattered laser light.) In addition, we do not expect absorption to depend significantly on the atomic number of the target material over the modest range covered in these experiments.

Two experiments gave laser-light absorption values of $50 \pm 5\%$ for an iron foil and $39 \pm 4\%$ for an iron/copper foil. These absorption values were inferred by subtracting the backscattered light and the integrated scattered light measurements from the incident laser energy. Measurement errors due to calibration uncertainties and angular integration give an average absorption value of $45 \pm 9\%$ for these two experiments.

Source Uniformity

We measured the two-dimensional, time-integrated spatial characteristics of the x-ray emission region with the Kirkpatrick-Baez microscope. The aluminum-Mylar filter resulted in a channel response of about 0.8 to 1.2 keV. Figure 5 shows a processed spatial image of a nickel-foil experiment. The relatively soft edge of the image may result from time integration

Calibrating the response of the film used in the spectrographs was a formidable task; it represents the least certain quantity in determining the absolute intensity of the x-ray lines emitted from the flashlamp foils.

and from overlapping of Shiva's ten beams. The image shows no small-scale structure (time integration may again be responsible), although there is a relatively long-scale variation (1.5:1) in the film density over a scale length of about 500 to 700 μm . We used this image to determine the area of the source in estimating the brightness of the x-ray flashlamp. (The brightness of the source is defined as the intensity radiated per unit time per unit photon energy interval.)

X-Ray Spectra

In our detailed measurements of the x-ray emission spectra, several quantities were of particular interest: the total yield and power of the x-ray emissions from the flashlamp, the angular dependence and relative strength of the spectral lines, and the energy and brightness of x-ray lines in the vicinity of the resonance with the upper energy level of the lasing medium. Total x-ray yield is an important quantity, as the flash-

lamp x rays serve to strip down the lasing gas to its helium- or hydrogen-like ionization state. The relative spectral emission strengths of transitions from various ionization states of the flashlamp foils, and their angular dependence on opacity effects, provided a valuable check on our simulation computer codes LASNEX and XRASER. Finally, the brightness of individual flashlamp emission lines is important because it determines both the possibility of creating a population inversion in the lasing gas as well as the laser gain.

To study these quantities, we combined measurements from several different instruments. Figure 6 shows typical time-integrated spectra obtained from chromium and nickel flashlamps with the transmission grating and streak camera; the spectra display strong L-shell emission. Although the instrument does not resolve individual lines, it does show that the energy centroid of emission increases with atomic number as expected. Figure 7 shows the time history of the

Fig. 5

(a) Spatial image of 1.064- μm light incident on the flashlamp foil. The scan represents the average optical density at the target plane. (b) Two-dimensional image of x-rays emitted from flashlamp target in the energy interval from 0.8 to 1.2 keV. The spatial resolution of the x-ray microscope is about 10 μm . (c) Vertical scan through middle of the image, showing full-width half-maximum (FWHM) and full-width 0.1-maximum [FW(0.1M)] of the source intensity. (d) Horizontal scan through the middle of the image, showing FWHM and FW(0.1M).

L-shell emission from a chromium flashlamp. The 100-ps rise time is consistent with a driving-laser pulse of 100 ps [the laser pulse is Gaussian, with a full-width half-maximum (FWHM) of 100 to 120 ps] but decays more slowly, with a characteristic time of about 220 ps. The FWHM of the x-ray emission is about 190 ps, 1.5 to 2 times greater than that of the laser pulse.

Chromium Spectrum

Figure 8a shows a typical time- and space-integrated spectrum obtained for chromium flashlamp foils using the 35-deg forward spectrograph (angle measured relative to target normal). Figure 8b shows the important case of a chromium spectrum obtained with the 38-deg rearward spectrograph. All data were energy calibrated with one of the lithium-like $n = 3 \rightarrow n = 2$ transitions. The spectral linewidths measured by the 35-deg forward and 38-deg rearward spectrographs were 1.8 and 1.4 eV FWHM, respectively. In both cases, the linewidth was dominated by source size. The smaller value resulted from a different instrument design located farther from the source.

The spectrum of chromium was one of the most important measured in the Shiva experiments because it is a prime candidate for pumping fluorine to produce a 42.3-eV x-ray laser. The beryllium-like chromium emission line necessary to pump the $n = 4$ level of helium-like fluorine was theoretically predicted to be 899.78 eV; this line was measured experimentally at 899.58 eV. The chromium emission record in Fig. 8b (from a rearward spectrograph) illustrates the uncertainty surrounding spectral calibrations. A distinct group of five lines from about 0.87 to 0.91 keV should be associated with beryllium-like $3d \rightarrow 2p$ transitions. Unfortunately, the uncertainty in our energy calibration (± 4 eV) prevents any firm conclusions about whether the desired energy overlap occurs. Further measurements to improve the accuracy of these line determinations are in progress at KMS Fusion, Inc., Ann Arbor, Michigan; others will be performed at LLNL early in Novette's experimental schedule.

Line Brightness

To facilitate comparison with the kinetics calculated with the XRASER code, we have expressed the brightness of the flashlamp's pump line in terms of modal photon density (photons per mode). The modal photon density is a measure of a line's brightness at a given frequency, which can be compared to that of a blackbody radiating at a prescribed temperature. For an optically thick source in equilibrium, this

Fig. 6

X-ray spectrum produced by laser irradiation of chromium and nickel flashlamp foils. The interval ΔE (FWHM) indicates the resolution of the streaked transmission-grating spectrograph.

Fig. 7

Time history of x-ray emission at the peak intensity point in the chromium spectrum shown in Fig. 6.

Fig. 8

(a) X-ray spectrum of the $n = 3 - n = 2$ emission from a chromium flashlamp foil, showing the calibration line; data obtained with the 35-deg forward crystal spectrograph. (b) X-ray spectrum of the $n = 3 - n = 2$ emission from the same chromium foil, showing the calibration line and one of the laser pump lines (beryllium-like chromium); data obtained with the 38-deg rearward spectrograph.

modal photon density is

$$N_p = [\exp(h\nu/kT) - 1]^{-1},$$

where h is Planck's constant, ν is the emission frequency, T is the temperature, and k is Boltzmann's constant. If $h\nu/kT = 1$, $N_p = 0.58$ photons per mode; if $h\nu/kT = 2.822$ (the peak of the blackbody spectrum), $N_p = 0.063$ photons per mode, and so on. In other words, N_p scales rapidly with kT when the photon energy is fixed, emphasizing the importance of heating the flashlamp to a relatively high electron temperature.

Most laser photoexcitation schemes require flashlamp photon densities of at least 0.01 photons per mode. The quantity N_p (photons per mode) is related to parameters we actually measure by

$$N_p = (2.56 \times 10^{-24}) E_{lv}^{-3} \Delta\tau^{-1} A^{-1} \times I (\Delta E_{\text{exp}}/\Delta E_{\text{natural}}),$$

where E_{lv} is the transition energy in electron volts, $\Delta\tau$ is the duration of the transition (FWHM) in seconds, A is the emission area of the plasma in square centimetres, I is the measured x-ray intensity in units of keV/keV over 4π , and $\Delta E_{\text{exp}}/\Delta E_{\text{natural}}$ is the ratio of the experimental linewidth (FWHM) to the natural (Doppler-broadened) linewidth. In our experiments, I is uncertain to within $\pm 50\%$. We did not measure the uncertainty in $\Delta\tau$ because the duration of emission was not determined for individual lines. The ratio $\Delta E_{\text{exp}}/\Delta E_{\text{natural}}$ is known to within $\pm 50\%$. These uncertainties lead to a large uncertainty in N_p . Future experiments at KMS Fusion and LLNL (with Novette) will focus on reducing the error in each of these parameters.

Table 2 shows some of the modal photon intensities derived for the most intense lines observed in the spectrum of the chromium-hydrocarbon flashlamp foil. (We used the transmission-grating streak camera to determine $\Delta\tau$.) The brightness of the lines assumed to be candidates for pumping the x-ray laser (from the beryllium-like state) was

Table 2 Modal photon densities of the strongest lines in the flashlamp x-ray spectra for two different experiments.*

Flashlamp material	Spectral line	Line energy, eV	Photons/mode (forward 38-deg spectrograph)	Photons/mode (rearward 35-deg spectrograph)
Cr + CH	$1s^2 3d(^2D_{3/2}) - 1s^2 2p(^2P_{3/2})$	932.6	0.01	0.004
Cr + CH	$1s^3 3d(^2D_{3/2}) - 1s^2 2p(^2P_{3/2})$	932.6	0.009	0.005

*On the basis of the data from the x-ray microscope, we assumed an emission area of $6.4 \times 10^{-3} \text{ cm}^2$. We obtained a value of $\Delta\tau$ from the transmission grating and streak camera on one experiment only; in others, it was assumed to be 200 ps. The instrument source-broadened linewidth was about 1.5 eV FWHM for the forward spectrograph and about 1.8 eV for the rearward spectrograph; the natural (Doppler-broadened) linewidth was assumed to be about 0.3 eV FWHM.

about one half of the value (0.01 photons per mode) that appears necessary for photopumping the transitions of interest. Although the data embody considerable uncertainty, we will attempt to increase the value of N_p in the early phases of the Novette x-ray-laser experiments using techniques based on the wide range of irradiation conditions (a wavelength of 532 nm and higher intensities) that Novette will provide.

Summary

A popular scheme proposed for lasing at x-ray wavelengths is based on resonant photopumping of the lasing medium by x rays generated in laser-irradiated metal foils. To evaluate the quantitative feasibility of such schemes, we must first determine the x-ray emission characteristics of the foils. We used the Laboratory's Shiva laser to irradiate a number of candidate flashlamp materials. Our experiments established the feasibility of producing a bright, uniform source of x radiation in the range of wavelengths required. However, the experiments underscored uncertainties in several key parameters. To reduce the uncertainties, we will need to make more accurate determinations of the centroid energy and the width of flashlamp emission lines. We must also measure the time duration of individual emission lines with a high-resolution spectrophotograph.

Our experience in these preliminary experiments with the Shiva laser will

be applied to a much more accurate assessment of flashlamp line brightness using LLNL's Novette laser later this year. Because x-ray lasing would be marginal for some schemes at current line brightnesses, the Novette experiments will also explore techniques of increasing brightness by studying the effects of such parameters as the wavelength and intensity of the driving laser light and the thickness of the flashlamp foil. □

Key Words: LASNEX; laser—Novette, Shiva, x-ray; XRASER.

Notes and References

1. A number of x-ray lasing schemes are described in P. L. Hagelslein, *Physics of Short Wavelength Laser Design*, Lawrence Livermore National Laboratory, Rept. UCRL-53100 (1981).
2. The experimental procedure and results for these spectrographs are described in M. Boyle and L. Koppel, *Crystal Spectrograph Measurements for Laser Produced X-Ray Wavelength Identification*, Advanced Research and Applications Corporation, Sunnyvale, California, Rept. TR-139-02 (1982).
3. R. L. Kaufmann, G. L. Stradling, D. T. Attwood, and H. Medeck, *Quantitative Intensity Measurements Using a Soft X-Ray Streak Camera*, Lawrence Livermore National Laboratory, Rept. UCRL-87963 (1982).
4. N. M. Ceglie, R. L. Kauffman, A. Hawryluk, and H. Medeck, *A Time-Resolved X-Ray Transmission Grating Spectrometer for Investigation of Laser-Produced Plasmas*, Lawrence Livermore National Laboratory, Rept. UCRL-87800 (1982).
5. For a discussion of new diagnostic instruments used in laser fusion x-ray experiments, see the article beginning on p. 13 of this issue of *Energy and Technology Review*.

Past Titles

Articles published in recent issues of the *Energy and Technology Review* are grouped below mainly according to their chief sponsors, the Assistant Secretaries of the U.S. Department of Energy. Research funded by other Federal agencies is listed under Work for Others.

ENERGY RESEARCH

Understanding Tandem Mirror Devices (November 1982)

DEFENSE PROGRAMS

Inertial Fusion

The Feasibility of Inertial Confinement Fusion (December 1982)

Laser Fusion with Green and Blue Light (August 1982)

Military Application

How Old is the Universe? (December 1982)

Measuring Equations of State with the Electric Gun (December 1982)

The Regional Seismic Test Network (November 1982)

A Universal Sensor for Potentiometric Titrations (Brief—August 1982)

Electrosynthesis of N_2O_5 ; the Key to Inexpensive HMX (August 1982)

The Compuron: How Round is Round? (August 1982)

FOSSIL ENERGY

Large-Block Experiments in Underground Coal Gasification (November 1982)

LABORATORY HISTORY

Energy and Resource Programs (October 1982)

Inertial Confinement Fusion (October 1982)

The Tandem Mirror MFE Program (October 1982)

Chemistry and Materials Science in Retrospect (September 1982)

Computing at LLNL (September 1982)

Project Plowshare: A Brief History (September 1982)

The LLNL-Nevada Organization (September 1982)

LABORATORY REVIEWS

Energy and the Environment (July 1982)

LLNL 1982: Technical Horizons (July 1982)

National Defense (July 1982)

Supporting Technologies (July 1982)

The State of the Laboratory (July 1982)

NUCLEAR ENERGY

Successful Demonstration of the AVLIS Process (Brief—August 1982)

Disclaimer

This document was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor the University of California nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial products, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or the University of California. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government thereof, and shall not be used for advertising or product endorsement purposes.

Printed in the United States of America
Available from

National Technical Information Service
U.S. Department of Commerce
5285 Port Royal Road
Springfield, Virginia 22161

Price: Printed Copy \$7.00, Microfiche \$3.50