NOTICE
PORTIONS OF THIS REPORT ARE ILLEGIBLE.*

It has been reproduced from the best available copy to permit the broadest possible availability.

LA--10200-MS

DE85 002351

Compact Reversed-Field Pinch Reactors (CRFPR):

Preliminary Engineering Considerations

R. L. Hagenson*
R. A. Krakowski
C. G. Bathke
R. L. Miller
M. J. Embrechts**
N. M. Schnurr
M. E. Battat
R. J. LaBauve
J. W. Davidson

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

*Consultant at Los Alamos. Technology International, Inc., 2515 Elmwood Dr., Suite 102, Ames, IA 50010.

**Collaborator at Los Alamos. Department of Nuclear Engineering, Rensselaer Polytechnic Institute, Troy, NY 12184.

MASTER

Los Alamos Los Alamos National Laboratory
Los Alamos, New Mexico 87545

TABLE OF CONTENTS

	<u>PAGE</u>
I. EXECUTIVE SUMMARY	1
A. Introduction	1
B. Background	3
C. Scope of Study	6
D. The Reversed-Field Pinch Confinement Principle	9
E. Reactor Design Overview	16
F. Technology Assessment	22
G. Conclusions	27
II. BACKGROUND	29
A. Status of Experimental and Reactor Studies	29
B. Rationale for High-Power-Density Fusion	38
C. Simplified Reactor Model	46
D. The Reversed-Field Pinch	61
1. Confinement Principle and Application to Reactor Studies	61
2. Reactor Design-Point Update and Sensitivity	68
III. PRELIMINARY ENGINEERING DESIGN.	77
A. Design Overview	77
B. Neutronics	84
1. Calculational Procedure	84
2. Computational Results	86
a. Parametric Studies	86
b. The Canonical Blanket.	91
C. Materials	100
1. Overview	100
2. Materials Selection	103
a. First Wall	103
b. Blanket/Shield	108
c. Magnets	109
3. Radiation Effects	109
4. Summary	115

D.	In-Vacuum Components (First Wall and Limiters)	117
1.	General Thermal-Mechanical Considerations	117
2.	Thermal-Hydraulic Analysis	122
a.	First Wall	122
b.	Pumped Limiter.	130
E.	Blanket	134
1.	General Considerations.	134
2.	Thermal-Hydraulic Analysis.	138
a.	Calculation of Blanket Pumping Power	139
b.	Results	142
3.	Thermal Analysis of Shield.	146
4.	First-Wall/Blanket/Shield Integration	148
F.	Magnets	150
1.	Toroidal-Field-Coil System.	151
2.	The Poloidal-Field-Coil System	158
a.	Startup Operations.	160
b.	PFC (OHC + EFC) Conductor Locations	167
	<u>Ohmic-Heating Coil (OHC)</u>	168
	<u>Equilibrium-Field Coil (EFC)</u>	170
	<u>Combined OHC/EFC Magnetic Properties</u>	172
c.	PFC (OHC + EFC) Circuit Analysis	173
d.	Resistive PFC Numerical Circuit Analysis	179
G.	Plasma and Circuit Simulation	188
H.	Particle Control by Pumped Limiters	208
1.	Scrapeoff and Limiter Model	209
2.	Parametric Results	214
I.	Magnetic Divertor	232
J.	Vacuum and Fueling	236
K.	Current Drive	249

L.	Fusion-Power-Core Integration	261
1.	Power-Plant Energy Balance Integration	261
2.	Thermal-Hydraulic Design Integration	265
a.	Thermal-Conversion Efficiency	266
b.	Thermal-Hydraulics Design Parametrics Study	269
	<u>Limiter Analysis</u>	270
	<u>First-Wall/Second-Wall Analysis</u>	271
	<u>Shield Analysis</u>	271
	<u>Pressurized-Water Manifold/Header Design</u>	271
	<u>Blanket Analysis</u>	272
	<u>Cycle Efficiency</u>	272
c.	Thermal-Hydraulics Design Parametrics Study Results	272
3.	Mechanical Design Integration	281
IV.	ASSESSMENT	301
A.	Physics Assessment	301
B.	Technology Assessment	303
1.	Plasma Heating System	303
2.	Particle Control Systems	304
a.	Fueling	304
b.	Particle Removal	305
c.	Vacuum Pumping	306
3.	Plasma Current-Drive System	307
4.	Nuclear Systems	308
a.	In-Vacuum Components	308
b.	Blanket	310
c.	Shield	312
d.	Afterheat and Radwaste	313
5.	Magnet Systems	315
a.	Toroidal-Field Coils	315
b.	Poloidal-Field Coils	316
6.	Electrical and Mechanical Systems	316
a.	Energy Transfer and Storage (ETS)	317
b.	FPC Structural Support, Assembly, and Maintenance.	317
7.	Tritium Systems	318
8.	Balance-of-Plant Systems	318

C. Economic Assessment	320
1. Parametric Systems Model	320
2. CRFPR Cost Tradeoffs	321
D. Conclusions	332
REFERENCES	334
ACRONYMS AND NOTATION	346
ACKNOWLEDGEMENTS	348
APPENDICES	349
Appendix A. CRFPR BURN MODEL AND REACTOR DESIGN CODE	349
A.1. Computer Model for Burn Simulation	351
A.2. Fokker-Planck Slowing-Down Calculation	355
A.3. Plasma Powers and Profile Averages	357
a. Heating by Energetic Particle	358
b. Ohmic Heating	359
c. Radiation Power	359
d. Transport	361
A.4. Magnetic-Field, Density, and Temperature Profiles	363
A.5. Equilibrium and Stability	369
A.6. First-Wall Thermal-Mechanical Response	371
A.7. Reactor Energy Balance	372
Appendix B. TABLE OF CRFPR DESIGN PARAMETERS	377
Appendix C. TWO DIMENSIONAL NEUTRONICS ANALYSES	387
C.1. Introduction	387
C.2. Two-Dimensional Model	388
C.3. Neutronics Calculations	388
a. Codes	388
b. Cross Sections	393
c. Computational Specifications	393
C.4. Parametric Results	394
a. Reference (Canonical) FW/B/S Model	394
b. Modified Reference (Canonical) FW/B/S Model	400
C.5. Conclusions and Recommendations	403

COMPACT REVERSED-FIELD PINCH REACTORS (CRFPR): PRELIMINARY ENGINEERING CONSIDERATIONS

by

R. L. Hagenson, R. A. Krakowski, C. G. Bathke, R. L. Miller,
M. J. Embrechts, N. M. Schnurr, M. E. Battat, R. J. LaBauve, and J. W. Davidson

ABSTRACT

The unique confinement physics of the Reversed-Field Pinch (RFP) projects to a compact, high-power-density fusion reactor that promises a significant reduction in the cost of electricity. The compact reactor also promises a factor-of-two reduction in the fraction of total cost devoted to the reactor plant equipment [i.e., fusion power core (FPC) plus support systems]. In addition to operational and developmental benefits, these physically smaller systems can operate economically over a range of total power output. After giving an extended background and rationale for the compact fusion approaches, key FPC subsystems for the Compact RFP Reactor (CRFPR) are developed, designed, and integrated for a minimum-cost, 1000-MWe(net) system. Both the problems and promise of the compact, high-power-density fusion reactor are quantitatively evaluated on the basis of this conceptual design. The material presented in this report both forms a framework for a broader, more expanded conceptual design as well as suggests directions and emphases for related research and development.

I. EXECUTIVE SUMMARY

A. Introduction

The cost-optimized Compact Reversed-Field Pinch Reactor (CRFPR) design suggested by this study would operate with a fusion-power-core (FPC, i.e., first wall, blanket, shield, and coils) power density (MWt/m^3) and mass utilization (tonne/MWt) that are comparable to fission power plants. These two measures of FPC performance couple with appropriately modified values for plant availability and operating cost to give a cost of electricity [COE (mills/kWeh)] that is

1.6-2.0 times less than that being projected for other approaches to fusion power; a similar basis is used in evaluating these cost differences, which are significant. Furthermore, the fraction of the total plant cost required for the reactor plant equipment (i.e., FPC and support systems) can be reduced from the 50-70 % generally considered necessary for fusion to ~ 30 % for the compact systems; the influence of plasma physics in the overall cost equation for fusion is reduced, thereby diminishing the risk of development and deployment. After the background and rationale for compact fusion reactors are reviewed, preliminary designs and related technology assessments of crucial FPC engineering subsystems are presented. Physics and engineering models for the RFP are developed, many for the first time, to describe parametrically key FPC subsystems required for all aspects of plasma initiation, startup, sustenance, and plasma power conversion. Once defined, these subsystems are integrated into a cost-optimized FPC design that is used for a physics, technology, and economic assessment while simultaneously providing a basis for future, more comprehensive power-plant design studies. The material contained herein, therefore, is both summary and interim in form and is intended to provide a framework for future work.

B. Background

The development and eventual commercialization of magnetic fusion energy (MFE) is pursued in the U. S. through two co-mainline concepts, the tokamak and the tandem mirror, with a number of promising but less-developed approaches being investigated as alternative or supporting fusion concepts (AFCs). The engineering development needs for the mainline tokamak have been quantified by detailed conceptual design studies of both first-generation engineering experiments^{1,2} and commercial power reactors.³ To a lesser extent, but nevertheless at a significant level of effort and conceptual design detail, are studies of the Tandem Mirror Reactor (TMR)⁴⁻⁶ as well as nearer-term engineering devices^{7,9} based on the tandem-mirror confinement principle. Complementing and supporting both the tokamak and tandem-mirror mainline approaches are the AFCs. The status of reactor designs for tokamaks, tandem mirrors, and AFCs has been summarized quantitatively.^{9,10} A qualitative assessment of the engineering and technology needs of the major AFCs has also been presented recently.¹¹

A generic category termed "compact" or "high-power-density" approaches to fusion has been identified,¹⁰⁻¹³ into which is placed the Compact Reversed-Field Pinch Reactor (CRFPR),¹⁴⁻¹⁷ the reactor embodiment of the Ohmically-Heated Toroidal Experiment (OHE),¹⁸ high-field tokamaks,^{9,19-22} and certain subelements of the Compact Toroids (CT, i.e., spheromaks, field-reversed configurations, field-reversed mirrors, etc.).²³⁻³⁰ The word "compact" as used here describes approaches that would operate explicitly with increased engineering or system power density compared to the low power density and large physical size projected for the mainline fusion concepts. Small plant capacity [i.e., MWe(net)], although an attractive trait for first-of-a-kind systems, is not necessarily implied by "compact". While the combination of compactness and smallness in capacity is possible, economies of scale generally dictate higher unit costs (i.e., \$/kWe or mills/kWeh) for systems with lower capacity.

Concern over the dominance in mass and cost of the fusion power core [FPC, i.e., first wall/blanket/shield/coils (FW/B/S/C)] for many fusion approaches¹⁻¹⁰ has led to consideration of compact options. This concern about the large size, low power density, and physical complexity of fusion is most succinctly summarized in Fig. I.B-1, which gives on a scale of toroidal major radius cross sections of the FPCs being projected for a number of fusion reactor concepts. Although the system power densities for other fission systems are less than for the Pressurized-Water (fission) Reactor (4-5 MW/m³ for an Advanced Gas Reactor,

2-3 MW/m³ for a Liquid-Metal Fast Breeder Reactor), most fusion systems depicted on Fig. I.B-1 project power densities that are below these values. General improvements to this situation being sought through the compact, high-power-density options include a) power densities within the FPC approaching those of fission reactors (i.e., 10-30 times greater than promised by most fusion reactor conceptual designs); b) projected costs that are relatively insensitive to large changes in unit costs (\$/kg) used to estimate FPC and associated reactor plant equipment costs; c) considerably reduced size and mass of the FPC with potential for "block" (i.e., single or few-piece) installation and maintenance; and d) the potential for rapid, minimum-cost development and deployment, which generally implies rapid progress along crucial learning curves. The compact approach is not necessarily limited to a specific confinement scheme; just as the RFP has a low-power-density reactor

Fig. I.B-1. Relative sizes of mainline and alternative magnetic fusion power reactors. With the exception of the compact RFP reactor (CRFPR), all systems propose the use of large superconducting magnet coils. Thermal(net electrical) powers are indicated in Gwt(GWe) units, and FPC power densities are also shown. In presenting the (linear) MARS tandem-mirror design, its length has been reduced by 2π to generate an effective major radius for purposes of comparison only.

embodiment,³¹ it is possible to envisage compact reactor options for the tokamak,¹ the stellarator/torsatron/heliotron (S/T/H),³² and certain CT configurations.^{24, 25}

The compact option for fusion power will require the extension of existing technologies to accommodate high heat flux, higher power density, and in some instances higher magnetic fields required to operate with FPC power densities in the 5-15 MWt/m³ range rather than in the 0.3-0.5 MWt/m³ range being predicted for most other approaches (Fig. I.B-1). Ultimately, however, any comprehensive analysis of the "optimum" fusion power system must be based on the cost of electricity, COE(mills/kWeh), which accurately reflects the cost of achieving engineering feasibility (i.e., design complexity and degree of needed design conservatism), operation and maintenance costs (i.e., FPC "burnup"), costs of environment and safety restrictions, construction time, and plant availability. Hence, system power density is one important input to the equation for a competitive fusion power plant. The present study of the compact RFP reactor addresses this problem on the basis of these aforementioned broader issues.

C. Scope of Study

Although considerable insight into the engineering and economic constraints of high-power-density fusion has developed from past parametric studies,¹⁵ it nevertheless becomes necessary to perform specific conceptual engineering design studies on key FPC subsystems in order to advance the design credibility. This "framework" study develops models needed to describe all key aspects of the FPC performance for the Reversed-Field Pinch (RFP) and, then on the basis of parametric analyses using these models, develops an integrated and optimized FPC conceptual design. Of necessity, each subsystem model is simplified and will certainly be subjected to future upgrading. The FPC neutronics model and materials options couple to the unique features of the RFP confinement physics to form a starting point for this framework study. Design models and results for the following FPC subsystems are then developed, forming the central effort of this study.

- First Wall
- Blanket
- Magnets
- Plasma and Circuit Simulation
- Limiters
- Magnetic Divertors
- Vacuum and Fueling
- Current Drive

The simplified neutronics and materials models (i.e., one-dimensional, steady-state, constant properties) that serve as a basis for key design choices will require iteration and redesign as the system layout evolves, particularly with respect to blanket/shield performance (i.e., peak temperatures, stresses, two-dimensional effects on tritium-breeding ratio, coolant/manifold/header placement and size, etc.). In some cases, design iteration to a fully self-consistent integrated FPC is not within the scope of this study. This framework study concludes with an ergonomic, thermal-hydraulic, and mechanical integration of the complete FPC, the results of which are reported in this Executive Summary (Sec. I.E.). An assessment of physics, technology, and economics for this high-power-density FPC is then given (Sec. I.F.). The

results presented herein are intended to provide a data base for a comprehensive power-plant design study some time in the future.

This framework study focuses almost completely on the physics, technology, and economics of the FPC, with little consideration being given to FPC support systems or to the balance of plant (BOP). General ground rules and approach that guided this study are given below.

- When applicable and adequate, models and results emerging from mainline reactor studies are used, with a major effort being placed on specific RFP issues.
- Parameterization of key physics and technological results is stressed, with the selection of a specific or "canonical" design point being made only when choices are needed to advance or focus the design for purposes of assessment.
- Key plasma parameters are selected on the basis of economic and operational considerations while simultaneously assuring that the resulting design point can be reasonably matched with existing or developing RFP physics results (transport, beta, profiles, impurity control, current drive, field ripple constraints, field reversal conditions, current risetimes, ohmic heating, etc.).
- All reactor designs considered are based on ohmic heating by plasma currents to DT ignition using resistive copper magnets to induce currents and the RFP dynamo to generate large toroidal fields within the plasma from a relative low bias field initially introduced into the torus.
- Key FPC subsystems are designed on the basis of very long-pulse or steady-state plasma operation using current-drive and impurity-control concepts that are specific to RFPs.
- The FPC design is focused on (poloidal) pumped-limiter impurity control, but examination of (toroidal) magnetic divertors is initiated, in both cases taking advantage when possible of the advanced state of these areas for the tokamak mainline.
- The impact on cost and plant operations is considered for a range of capacities and power densities (neutron first-wall loading), but a 1000-MWe(net) power plant is selected to facilitate comparisons with the mainline reactor designs, both past and present, as well as with reactor concepts being proposed for key alternative fusion concepts.
- A neutron first-wall loading ($< 20 \text{ MW/m}^2$) is selected that minimizes COE and FPC mass while simultaneously assuring fundamental limits of heat-transfer and stress are not violated.
- As for the mainline tokamak, sputter erosion is recognized as a potentially serious lifetime determinant, but solutions are assumed to be found that will allow a high proportion of the plasma energy to be shed by radiation.

- Neutron radiation lifetimes are assumed to be in the range of 10-15 MWyr/m² (~ 10 dpa/MWyr/m²).
- In spite of marginal economic benefits accrued by increasing neutron first-wall loadings beyond ~ 10 MW/m², the minimum-COE design point at 20 MW/m² is retained by this framework study to minimize the FPC mass for purposes of utilizing single- or few-piece batch maintenance schemes.
- A commonality with the tokamak in cost data base and methodology is stressed, as well as the level of allowed physics assumption/extrapolation and technological innovation, to assure meaningful and (when possible) quantitative intercomparison and assessment of design end products.

D. The Reversed-Field Pinch Confinement Principle

The RFP is a toroidal axisymmetric device in which the primary confinement field, B_θ , is poloidal and is generated by a toroidal current, I_ϕ , flowing in the plasma.³³⁻³⁵ The RFP plasma supports a toroidal bias field, B_ϕ , to stabilize sausage ($m = 0$) and elliptical ($m = 2$) distortions. Grossly unstable MHD modes with wavelengths longer than the minor radius, r_w , of an electrically conducting shell are stabilized by the shell on a short time scale and by feedback coils for longer times. If the toroidal bias field is slightly reversed near the plasma edge, $r_p \lesssim r_w$, the resulting magnetic shear in the plasma-edge region is sufficient to stabilize local pressure-driven and current-driven instabilities. This stabilization occurs at relatively high values of the normalized plasma pressure, $\beta \equiv 2nk_B T / (B^2 / 2\mu_0)$. A sample profile for a stable RFP is illustrated in Fig. I.D-1, which also gives a comparison with a tokamak.

The existence of the RFP profiles shown in Fig. I.D-1 would seem unlikely because of the probable annihilation of opposing toroidal flux at the field reversal surface, as is illustrated graphically in the lower right quadrant of Fig. I.D-1. Experiments during the previous 25 years, however, have shown that a self-reversed field and a minimum-energy plasma are generated even if such a field is not externally imposed. Recent theories of relaxed energy states has led to a substantial increase in the fundamental appreciation of this near-minimum-energy, field-reversed state. Given any arbitrary dissipation mechanism operative within a plasma surrounded by a flux-conserving shell, that plasma will relax through resistive processes to a minimum-energy, force-free state. The key descriptive parameters in the RFP theory are the pinch parameter, θ , and the reversal parameter, F , which are defined as $\theta = B_\theta(r_w) / \langle B_\phi \rangle$ and $F = B_\phi(r_w) / \langle B_\phi \rangle$, where $\langle B_\phi \rangle = (2/r_w^2) \int_0^{r_w} B_\phi r dr$ is the average toroidal field within the conducting-shell radius, r_w ; Fig. I.D-1 illustrates graphically the meaning of F and θ . The primary attraction of the self-generating RFP as a reactor becomes obvious from Fig. I.D-1: a) high plasma current from ohmic heating; b) high fields in the plasma but low fields and currents at the magnet coils. The RFP is also an inherently high-beta configuration with the potential for a unique, low-frequency current drive for steady-state operation.

The locus of minimum-energy RFP states, as described in an F - θ phase space, is shown in Fig. I.D-2; both the analytic, $\beta = 0$ state and the experimental, finite- β states are shown. The experimental F - θ traces shown in Fig. I.D-2

Fig. 1.D-1. Sample magnetic-field and $q = (B_\phi/B_\theta)(r_p/R_T)$ minor radial profiles for the RFP and the tokamak. Shown also are graphic definitions of the RFP pinch parameter, θ , and reversal parameter, F .

illustrate the plasma drifting toward and residing within a specific region of F - θ space. This desired RFP state corresponds to $F < 0$ and $1.2 < \theta < 1.6$. Both the relaxation mechanism and associated time constants for the self-sustained toroidal-field reversal are not easily explained in terms of commonly understood plasma processes. In spite of this lack of theoretical understanding, however, strong experimental evidence exists for a plasma regeneration or "dynamo" mechanism that continually maintains the minimum-energy RFP state. Either turbulence or resistive MHD instabilities drive the plasma dynamo action, wherein toroidal plasma currents are converted to the toroidal

Fig. I.D-2. The F - θ diagram showing two experimental traces and the tendency for the plasma to seek and reside within the RFP minimum-energy state. The tokamak-like state corresponds to $(F \approx 1, \theta \approx 1/qA)$, whereas the spheromak state resides around $F \approx 0$.

flux needed for maintenance of the toroidal field reversal depicted on Fig. I.B-1 and experimentally shown on Fig. I.D-2.

The relationship between F and θ , the tokamak safety factor, $q \equiv (r_p/R_T)(B_\phi/B_\theta)$, and beta points out the essential differences between the RFP and the tokamak reactor. First, one definition of the total average beta for both RFPs and tokamaks is $\langle\beta\rangle = 2\mu_0\langle p\rangle/(B_\theta^2 + B_\phi^2)$, which in terms of the poloidal beta, β_θ , is $\langle\beta\rangle = \beta_\theta/[1 + (B_\phi/B_\theta)^2] = \beta_\theta/[1 + (F/\theta)^2]$. Proper accounting of profile effects can introduce a factor of ~ 2 into these simplified relationships between $\langle\beta\rangle$ and β_θ for both the RFP and tokamak. The tokamak-like minimum-energy state would correspond to the region on Fig. I.D-2 defined by $F \rightarrow 1$ and $\theta = F/Aq \approx 1/Aq$, where $A = R_T/r_p$ is the plasma aspect

ratio; for the tokamak, $\langle\beta\rangle = \beta_0/[1 + (qA)^2]$. The spheromak minimum-energy state corresponds to $F \rightarrow 0$ on Fig. I.D-2. For the RFP state, $|F/\theta| \approx 0.2/1.5 = 0.13$ and $\langle\beta\rangle \approx \beta_0$ (actually $\sim \beta_0/2$, accounting for profiles), whereas for the tokamak $F/\theta = qA \approx 8-10$, with $\langle\beta\rangle$ being much less than $\beta_0 \approx 1-2$. As a maximum for the tokamak, $\beta_0 \lesssim A$ to avoid the ideal kink stability and, therefore, $\langle\beta\rangle \lesssim A/[1 + (Aq)^2] \approx 1/Aq^2$.

The impact of these basic differences on the level of ohmic-heating allowed in resistive coils for systems that can operate stably with low values of $|F/\theta|$ compared to those with large $|F/\theta|$ values (i.e., the tokamak) is significant. Specifically, the ohmic losses incurred in the toroidal-field coils relative to those in the poloidal-coil system for both RFPs and tokamaks are nominally proportional to $\sim 1 + |F/\theta|$. In addition, lower ohmic losses occur in the RFP poloidal coils because of the higher aspect ratio and better inductive coupling between that coil set and plasma. The lower fields and currents in external conductors for the RFP allow the efficient use of resistive copper (or possibly aluminum) coils, significant reduction in blanket/shield thickness, and the possibility for significant reductions in FPC mass and complexity. Furthermore, the close electrical coupling between poloidal and toroidal circuits through the RFP dynamo can be used to establish a noninductive current drive for RFPs that may allow steady-state plasma operation using low-frequency and low-power rectifying technology (F- θ pumping). For these reasons as well as good experimental progress, the RFP represents an attractive candidate with which to examine the technical and economic feasibility of compact, high-power-density fusion reactors.

The present status of the RFP physics is depicted on Fig. I.D-3 in terms of a) the usual $n\tau_E$ versus T measurement of performance and; b) the ohmic scaling of $\tau_E \propto I_\phi^{\nu} r_p^2$ with plasma current, I_ϕ , and plasma minor radius, r_p . Theoretically, $\nu \approx 3/2$, whereas experimentally $\nu \approx 1$; the extension of this RFP ohmic scaling to the compact reactor is also depicted on Fig. I.D-3.

Experimentally derived poloidal betas of $\beta_0 \sim 0.1-0.15$ are typically measured on the Los Alamos ZT-40M experiment.³⁵ Neutral-beam-heated tokamak experiments have exhibited a degradation in the energy confinement time as the tokamak beta, in response to neutral-beam heating, is increased according to $\tau_E \propto 1/\beta^2$ [Appendix A.3.d.]. The poloidal beta used for the reactor is based on the experimental value of $\beta_0 \sim 0.13$, and, if the internal plasma heating (alpha-particle power) forces β_0 above 0.13, the energy confinement time is

decreased according to $\tau_E \propto 1/\beta_0^2$. The basic conclusions emerging from present-day RFP experiments are summarized below.

- Classical plasma resistivity is observed in experiment, the higher voltages required to drive current in RFPs relative to tokamaks being a result of geometric factors (i.e., higher pitch) rather than "anomalous" resistivity need to drive current against added $\vec{v} \times \vec{B}$ electric fields being generated by local, stochastic plasma motion.
- The plasma dynamo action is verified but not theoretically understood, with the dynamo dissipating little energy beyond that required by classical ohmic losses.
- Separate oscillation of poloidal and toroidal circuits result in the plasma moving predictably along the F- θ diagram, giving strong promise for F- θ pumping current drive. F- θ pumping for steady-state, ignited current drive should be efficient if the plasma dynamo action occurs with a nearly classical electrical resistivity.
- Ignition by ohmic heating is consistent with classical plasma resistivity and is a strong possibility in the RFP.
- The energy confinement time, $\tau_E(\text{OPT})$, required for an economically optimized reactor relative to an ohmic dissipation time, $\tau_E(\text{OHMIC})$, and relative to some measure of Alcator scaling, $\tau_E(\text{ALC})$, is given by $\tau_E(\text{OHMIC})/\tau_E(\text{OPT}) > 20-50$ and $\tau_E(\text{ALC})/\tau_E(\text{OPT}) > 5-10$, respectively, showing wide safety margins for ohmic ignition in RFPs.

In summary, these unique characteristics of a dynamo-sustained RFP (or spheromak) promise equally unique and attractive reactor advantages. The specific reactor implications of the $q < 1$ RFP confinement system based on the above physics indications are

- Relatively free choice of plasma aspect ratio.
- Economically high betas.
- Possibility of high values of βB^2 at the plasma and correspondingly increased plasma power density for a given field at coil.

Fig. I.D-3A. Measure of device performance in relationship to ignition and reactor goals.

- Internal plasma currents are sufficient for ohmic heating to ignition without auxiliary heating and with low-to-moderate fields and currents in the coils.
- Efficient plasma/coil electrical coupling, resulting in
 - $B_{\theta}(r_p)$ dominates and, hence, the fields and currents at the poloidal field coils are low.
 - $B_{\phi}(r_p)$ near zero, resulting in low fields and currents at toroidal-field coils.
 - Use of resistive coils is possible while maintaining efficient reactor performance.
 - Potential for efficient steady-state current drive through "F- θ pumping" with low-frequency, small-amplitude oscillations of TFCs and PFCs. The ohmic-heating-coil current can then be reduced to zero.

Fig. I.D-3B. Scaling of RFP confinement with toroidal current, I_ϕ , and plasma radius, r_p , needed to take present experimental results to reactor conditions.

E. Reactor Design Overview

The Compact Reversed-Field Pinch Reactor (CRFPR) study has focused on the FPC physics and technology needs for a nominal 1000-MWe(net) power plant. This toroidal reactor is based on a deuterium-tritium fuel cycle. Major features of this design are steady-state and ignited operation, ohmic heating to ignition, pumped-limiter impurity control, pressurized-water cooling of the high-heat-flux, copper-alloy first-wall and limiter systems, self-cooled lead-lithium ($\text{Pb}_{83}\text{Li}_{17}$, designated throughout this report as "PbLi") tritium-breeding blanket using ferritic steel (HT-9) structure, use of water-cooled copper coils positioned outside the blanket/shield system, and fully remote block maintenance of a single-piece (~ 300 tonne less ~ 800 tonne of coolant), first-wall/blanket/shield/toroidal-field-coil assembly.

Figure I.E-1 gives a cross-sectional view of the FPC, showing that this 1000-MWe(net) system is not much larger than TFTR³⁶ and requires an energy confinement time that differs little from 1-MA TFTR operation (0.25-0.30 s). An isometric sketch of one of 24 toroidal sectors is shown in Fig. I.E-2. Each of

Fig. I.E-1. Cross-sectional view of the 1000-MWe(net) CRFPR in comparison with the TFTR tokamak experiment³⁶ (poloidal-field coils not shown).

Fig. I.E-2. Isometric view of one of 24 toroidal sections for a 1000-MWe(net) CRFPR. Off-site, single-unit construction of the first-wall/blanket/shield/toroidal-field-coil torus (~ 300 tonne total without coolants) and single-piece maintenance/repair scheme is envisaged for this high-power-density design. Poloidal-field coils are not shown.

these toroidal sectors could be fabricated, assembled into the 300-tonne torus, and tested (electrically, under vacuum, and thermal-hydraulically) off site prior to shipment to and installation at the operating power-plant site. The high neutron first-wall loading of $\sim 20 \text{ MW/m}^2$ would give a one-year chronological life for a radiation lifetime of 15 MWyr/m^2 , which for the 45.2-tonne first-wall/blanket systems corresponds to a mass usage of 17.9 kg/MWtyr ($\sim 20,000 \text{ MWtd/tonne}$, somewhat less than UO_2 fissile fuel burnup in an LWR) for this 3365-MWt plant operating at a 75 % plant factor. Table I.E-I summarizes the major CRFPR design parameters.

TABLE I.E-I

MAJOR CRFPR DESIGN PARAMETERS

Net electrical power (MWe)	1000.
Gross electrical power (MWe)	1227.
Total thermal power (MWt)	3365.
Gross power-conversion efficiency (%)	36.5
Overall plant availability (%)	75.
Major radius (m)	3.8
Plasma radius (average)(m)	0.71
Plasma volume (m ³)	37.8
Neutron wall loading (MW/m ²)	19.5
Number of toroidal sectors	24.(a)
Maximum field at magnet (T)	4.5(b)
Field at plasma axis (T)	9.5
Field at plasma edge (T)	5.2
Average poloidal beta	0.23
Average total beta	0.12
Average DT ion density (10 ²⁰ /m ³)	6.6
Average DT ion temperature (keV)	10.0
Plasma burn mode	Continuous/ignited
Plasma heating method (startup)	Ohmic (246 Webers)
Plasma impurity-control method	Pumped limiter
First-wall/limiter structural materials	MZC copper alloy
Blanket/shield structural material	HT-9 ferritic steel
Tritium-breeding medium	PbLi
Primary coolant	PbLi
Thermal-conversion method	Dual-cycle, steam

(a) For off-site fabrication purposes only, single-piece or batch FPC maintenance is envisaged for this system that weighs ~ 300 tonne (first wall, blanket, shield, toroidal-field coils), to which is added a separate 800-tonne poloidal-field coil set and ~ 800 tonne of PbLi coolant.

(b) At the OHC during the burn, 9.2 T during startup.

The design parameters listed in Table I.E-I reflect the results of design guidelines (Sec. I.C.) that targeted the FPC power densities ($\sim 11.8 \text{ MW/m}^3$) and physical sizes (0.33 tonne/MWt , 285 m^3) at values at which pressurized-water fission reactors (PWRs) presently operate; the "fission power cores" (i.e., volume enclosed by primary pressure vessel) of Advanced Gas Reactors and Liquid-Metal Fast Breeder Reactors operate at engineering power densities that are 3-5 times less than for a PWR but are nevertheless much higher than values projected for most superconducting fusion reactors. Although the CRFPR power density is targeted at the PWR, considerable flexibility exists for systems of either reduced power density or reduced plant capacity (and neutron first-wall loading) while maintaining favorable projections for energy cost. The cost projections are summarized in Table I.F-I, which also gives comparisons with other fusion systems on a relatively common basis. An isometric sketch of the FPC is shown in Fig. I.E-3 which shows access being made at the outboard equatorial plane for all coolant(s), vacuum, and electrical lines. The top half of the FPC set ($\sim 400\text{-tonne}$ total) would be lifted vertically in two sections, exposing the $\sim 300\text{-tonne}$ first-wall/blanket/shield/TFC unit for removal as a single assembly during the annual maintenance period.

The costing results given on Table I.F-I for the CRFPR represents a complex tradeoff between physics ($\tau_E \propto I_\phi^\nu r_p^2$ scaling with $\nu < 3/2$ a variable), technology (neutron and heat loadings, power density, etc.), economics (plant factor, economy of scale, operating cost, etc.), and safety (afterheat, stored field energy, etc.). The operating and design margins between physics, technology, and economics have been charted on Fig. I.E-4, and a comfortable operating regime is indicated for a range of net electric output, P_E , neutron first-wall loadings, I_w , physical size as measured by plasma minor radius, r_p , and plasma confinement parameter, ν . The $I_w/P_E/\tau_E(\nu)/\text{COE}$ tradeoffs depicted on Fig. I.E-4 identify broad design margins between physics (confinement), technology (i.e., high heat/particle-flux surfaces, high-power-density blankets, batch versus patch maintenance, off-site versus on-site monolithic FPC construction, etc.), and economics (including plant availability, operating costs, recirculating power, etc.). The design point summarized on Table I.E-I is also shown on Fig. I.E-4, and the implications of decreasing both the neutron first-wall loading, net electric power, and system size (r_p , with the minimum-COE designs being relatively independent of $A = R_T/r_p$) and power density are clearly shown, as constrained by the confinement parameter ν . Although the increased COE

resulting from increased physical size and reduced FPC power density is not great for the ranges examined, the desire to maintain a single- or few-piece FPC maintenance scheme makes operating near the (shallow) COE minimum desirable. For systems with power density and first-wall loadings below those considered on Fig. I.E-4, a breakpoint occurs beyond which superconducting RFPs become more attractive; the exact position of this breakpoint remains to be determined, however.

The thrust of this framework study has been the definition of the technology and cost margins depicted in Fig. I.E-4 through conceptual design of a specific FPC design point. On the basis of these studies and conceptual designs generated, it is generally concluded that the RFP offers sufficiently broad physical, technical, and economic margins to promise a unique, realistic, robust, and "forgiving" approach to magnetic fusion energy. This framework study has also identified a number of technology problem and development areas, which are summarized in the following section.

Fig. I.E-3. Isometric view of CRFPR fusion power core.

Fig. I.E-4. Dependence of COE on r_p for a range of P_E values. Also shown are lines of constant first-wall neutron loading, I_w . The locus of points where the confinement time dictated by economics equals the RFP physics confinement time of the form $\tau_E(\text{RFP}) \propto I_w^\nu r_p^2 f(\beta_\theta)$ is also shown for a range of current exponents, ν .

F. Technology Assessment

Generic technology requirements for compact reactors have been reviewed previously.³⁷ The design approach taken for the CRFPR allowed by the unique RFP physical principles projects a unique cost advantage (Table I.F-I). More importantly, however, is the promise of fusion systems of smaller size and capacity that couple the real physics uncertainties more loosely to the overall cost equation for fusion power; a more robust and resilient design results that is capable of an early and cost-effective proof of fiscal and technical risk. This design resilience permits the recovery of an economically and technically interesting end product in the advent that less-optimistic results emerge from the physics program. This asset is particularly important for a costly

TABLE I.F-I

COST COMPARISON NORMALIZED TO TDC (1980 Dollars)

<u>ACCOUNT</u>	<u>STARFIRE</u> ³	<u>MARS</u> ⁵	<u>CRFPR</u>
20. Land and Land Rights	0.19	0.21	0.34
21. Structure and Site	20.09	10.59	26.07
22. Reactor Plant Equipment (RPE)	56.00	64.07	33.37
22.1.1. First-Wall/Blanket (FW/B)	4.77	2.33	1.54
22.1.2. Shield (S)	10.78	2.46	--
22.1.3. Coil (C)	9.90	16.06	3.20
FPC = FW/B + S + C	25.48	20.85	4.74
23. Turbine Plant Equipment	14.47	11.35	23.15
24. Electric Plant Equipment	6.77	6.78	12.62
25. Miscellaneous Plant Equipment	2.37	1.41	4.36
26. Special Materials	0.014	5.29	0.026
90. Total Direct Costs (TDC)	100.	100.	100.
99. Total Costs	185.23	174.12	173.00
Unit Direct Cost, UDC(\$/kWe)	1439.	1480. ^(a)	959.
Cost of Electricity, COE(mills/kWeh)	67.1	50 ^(a)	46.2
Net Electric Power, P _E (MWe)	1200	1202	1000

^(a) Taken from 1966 \$/kWe and 67 mills/kWeh in 1983 to 1980 using 10 % per year over 3 years to provide a common basis of comparison.

development program that remains in the early stages of progress toward commercialization.

The CRFPR design differs considerably from superconducting fusion reactors. The projected technology requirements correspondingly differ primarily because of

- Plasma Power Density: Increased plasma power density, which is proportional to $\beta^2 B^4$, where B is the confining magnetic field at the plasma surface and β is the ratio of average plasma pressure to magnetic-field pressure at the plasma surface.
- Neutron First-Wall Loading: Increased first-wall neutron current (15-20 MW/m²) and surface heat flux (4-5 MW/m², maximum, for uniform heat deposition onto the first wall).
- Blanket Power Density: Increased peak (≥ 200 MW/m³) and average (≥ 30 MW/m³) power density within a tritium-breeding blanket.
- Radiation-Hardened Resistive Coils: Increased radiation and heat fluxes at resistive magnet coils in systems designed to operate at most with only a thin heat-recovering/tritium-breeding blanket placed between the coil and the plasma.

This assessment of technological needs for the CRFPR design summarized on Table I.E-I is presented according to the three major FPC subdivisions: Plasma Engineering Systems (heating, particle control, etc.), Nuclear Systems (first wall, blanket, shield), and Magnet Systems. In addition, Tritium Systems and Electrical/Mechanical Systems represent key elements of the reactor, which at the level of this study have not received detailed attention.

Compact reactors generally would operate with somewhat increased plasma densities, which impacts certain Plasma Engineering Systems. Refueling, impurity control, and ash removal requirements, therefore, may be more demanding in that the power and mass flow rates remain essentially unchanged for the same power output, but the plasma surface area is considerably reduced. The higher plasma density may also lead to more-difficult rf current-drive requirements for steady-state operation; the potential for low-frequency "F- θ pumping" that is unique to the RFP (and spheromak) confinement, however, represents a new and potentially attractive means to drive steady-state plasma currents. Plasma heating by ohmic dissipation is unsurpassed in terms of efficiency and deliverable power density given the increased plasma current density allowed by

the RFP. Because of the higher first-wall thermal loadings, a heat-flux-concentrating limiter does not appear possible for the compact systems, and a sizeable portion ($> 40\%$) of the first wall must function as a limiter if a magnetic divertor is not used. The orientation of the RFP for poloidal limiters, however, is favorable for accommodating large limiter coverages. Generally, the in-vacuum components represent a development program that is not unlike that envisaged by the mainline tokamak high-heat-flux program. Strengthened copper alloy appears particularly suited for this first-wall (limiter) application, although control of sputter erosion for these high-heat-flux surfaces represents a crucial problem, as it does for fusion in general. Since both limiter area and energy carried from the plasma by particles are the same for the low-power-density STARFIRE and the CRFPR, the wall erosion problem should be similar. Although only beginning to be explored, the use of toroidal-field divertors for impurity control looks particularly attractive from the viewpoints of an open coil topology and the use of the minority toroidal field, both of which are mutually excluded in the tokamak.

In the sense that the increased power density within the tritium-breeding blankets all but eliminates solid breeders and helium coolant from consideration, the choices for the Nuclear Systems are appreciably narrowed. Self-cooled, liquid-metal breeders are particularly attractive for these high-power-density blankets, particularly in view of the lower fields and shortened flow paths offered by the CRFPR, thereby allowing higher cooling rates for the same MHD pump power and pressure drop. Liquid-metal-cooled first walls and limiters do not appear possible, however, because of the higher heat rating, and an appreciable fraction ($\sim 40\%$) of the fusion power is delivered from the FPC by pressurized water. The design of an efficient dual-media thermal cycle becomes important, as it is for MARS⁵, since this quantity of high-quality heat emerging in the coolant water is far too great for use only as feedwater heat. Although the resistive-coil CRFPR requires the minimum breeding-blanket thickness (~ 0.5 m), some nuclear shielding (~ 0.1 m) is required to assure $> 99\%$ energy recovery. The increased albedo provided by this shield is also important to maintain an acceptable tritium-breeding ratio; the coolant and vacuum ducting becomes a larger fraction of the blanket volume in that the FPC has been reduced in size, but the power, burn rate, DT/ash/impurity flow rate, and heat-removal requirements remain unchanged. Hence, the tendency to increase structure near the first-wall region because of current-drive and

thermal-hydraulic needs must be carefully balanced with the neutronics performance of a thin blanket/shield (reflector) system. This "real estate" issue strongly impacts assembly and blanket performance and requires considerably more study.

A potentially more difficult requirement for the DT-fueled compact systems is the need for reliable core-cooling capability because of the higher afterheat power density, particularly in the first-wall and limiter region. This enhanced afterheat power density results from the higher overall operating first-wall loading and blanket power density. It should be noted that, unlike for fission reactors, the afterheat problem is not viewed as a safety issue for fusion, but instead represents a hazard only to the FPC and the plant investment should local damage occur because of loss of cooling capability. Passive afterheat control is possible only for lower-power-density, more-expensive FPCs, and the choice between FPC efficiency versus security represents an economic rather than an environmental tradeoff. This issue is also important and deserves considerably more study.

The technology requirements for the Magnet Systems are significantly less difficult because of the absence of superconducting magnets and the low steady-state magnetic fields. The stored energy in these magnet systems is ~ 50 times less than for a superconducting system, representing a significant cost savings and potentially increased safety margin. The maintenance procedure envisaged for the compact reactor, because of the significant reductions in FPC physical size and mass, makes possible consideration of "block" maintenance, wherein the complete reactor torus is removed for maintenance and repair operations external to the reactor cavity with a more rapid replacement by a fresh pre-tested unit promising shorter downtimes and more reliable restarts. The reduced role of the toroidal-field coils (~ 0.4 T) and the efficient use of the dominant poloidal-field coils (~ 1 MA/GJ for STARFIRE compared to > 10 MA/GJ for CRFPR) allows physical decoupling of the two coil sets and the option for a unique installation and maintenance/repair scheme. The use of a toroidal divertor for impurity/ash control, however, will complicate somewhat the toroidal-field-coil set and enlarge the poloidal-field-coil set. Magnetic divertors probably will render single-piece maintenance impractical; nevertheless, the advantages of few-piece FPC maintenance and a system of considerably reduced size are expected to be retained.

A conceptual design of the F-θ pumping current-drive coils has not been made, which in all likelihood will be separate from the main confining coils and ideally would be located closer to the plasma for frequencies above ~ 50-100 Hz. A crucial tradeoff between tritium breeding and reactive power remains to be examined in that copper alloy positioned at the first wall adversely impacts the tritium-breeding ratio for this PbLi blanket. If the current-drive frequency can be reduced to a few Hz, however, it becomes feasible to oscillate the main TFC and PFC sets. At an even earlier stage of understanding is the design and impact of active feedback coils that are thought necessary to sustain electrically the conducting shell at the first-wall location; the liquid-metal blanket to a great extent should serve the function of a conducting shell for considerable times, however. Generally, the copper-alloy coils represent nearly state-of-the-art systems from the viewpoint of delivering the required fields on the required timescale, with the radiation hardening afforded by the use of inorganic (powered-MgO) insulation presenting a modest development item.

II. BACKGROUND

The general status of fusion reactor designs in relationship to present and projected near-term experiments is given in Sec. II.A. Section II.B. develops the rationale, incentives, and disincentive for high-power-density fusion options. After the RFP confinement principle is briefly summarized, the compact RFP reactor parametric design point originally suggested in Ref. 15 is further optimized and summarized in Sec. II.C. This most recent design point serves as the model used for the preliminary FPC design and integration developed in Sec. III. and assessed in Sec. IV.

A. Status of Experimental and Reactor Studies

Table II.A-I summarizes the experimental results and achievements emerging from the mainline and key alternative fusion programs. Although physics energy break-even and eventual ignition in a deuterium-tritium (DT) plasma represent major near-term and practically achievable goals, these conditions are likely to be demonstrated in devices that in terms of total plasma kinetic energy generate plasmas that are far from the requirements projected for commercial power reactors. This "stored-energy gap" between the anticipated and significant physics breakthrough and the achievement of commercial fusion is best illustrated by plotting in Fig. II.A-1 the confinement parameter, $n\tau_E$, against the total kinetic energy stored in the plasma, E_p . This plot also includes a number of engineering test and commercial reactors projected both for the mainline and key alternative confinement concepts. Given steady progress and successes in achieving adequate confinement at reactor-like plasma densities and temperatures, the stored-energy gap existing between experiments and Fusion Engineering Devices (FED), as well as between FED-like devices and commercial reactors, represents a need for significant technology development. Generally, machine costs are expected to scale directly with the stored energy and size. Bridging the stored-energy gap between FED and the commercial reactors becomes a concern in view of the already high costs projected for the former.

The key plasma, fusion-power-core (FPC), and power-plant parameters resulting from recent reactor design studies are summarized on Table II.A-II, which includes the Modular Stellarator Reactor (MSR),⁵¹ the STARFIRE commercial tokamak reactor,³ the EBT reactor (EBTR),⁵² the RFP reactor (RFPR),⁵³ and the tandem-mirror reactor (MARS).^{5,6} Given continued steady progress, improved plasma confinement to the point where plasma ignition occurs appears as an attainable goal. The extension of these desirable circumstances to the

TABLE II.A-I

SUMMARY OF KEY PARAMETERS OF SOME PRESENT MAGNETIC CONFINEMENT EXPERIMENTS

	TOKAMAK				STELLARATOR (a)		
	ALCATOR ³⁸ C	DOUBLET ³⁹ III	PLT ⁴⁰	TFTR ⁴¹	HELIOTRON ⁴² E	WENDLSTEIN ⁴³ VII-A	
Minor radius, r_p (m)	0.165	0.45	0.40	0.68	0.200	0.1	
Major radius, R (m)	0.64	1.43	1.32	2.48	2.20	2.0	
Plasma volume, V_p (m ³)	0.304	5.70	4.17	22.6	1.74	0.309	
Average density, n (10 ²⁰ /m ³)	15.0	0.8	0.6	0.25	0.3	0.5	
Average ion temperature, T_i (keV)	1.5	0.7	3.0	1.0	0.66	1.0	
Plasma energy, E_p (kJ)	330	140	360	270	17	9.5	
Energy confinement time, τ_E (ms)	50	50	40	0.2	10. (a)	10. (a)	
$n\tau_E$ (10 ¹⁶ s/m ³)	8000	400	240	500	30	500	
$\beta = 2nk_BT/(B^2/2\mu_0)$	0.015	0.035	0.02	0.003	0.01	0.008	
	REVERSED-FIELD PINCH			BUMPY TORUS	COMPACT-TOROIDS	TANDEM MIRROR	
	ZT-40M ^{44(b)}	ETA-BETA ⁴⁵ II	TPE-IRM ⁴⁶	NBT ⁴⁷	FRX-C ⁴⁸	CTX ⁴⁹	TMX ⁵⁰
Minor radius, r_p (m)	0.20	0.125	0.09	0.1	0.03	0.15-0.20	0.30
Major radius, R (m)	1.14	0.65	0.50	1.60	0.07	0.25-0.30	5.50
Plasma volume, V_p (m ³)	0.90	0.2	0.08	0.302	0.04	0.20	1.55
Average density, n (10 ²⁰ /m ³)	0.15(0.80)	1.0	0.6	0.01	50	0.8	0.027
Average ion temperature, T_i (keV)	0.30(0.35)	0.08	0.15	0.05-0.1	0.09	0.025	0.06
Plasma energy, E_p (kJ)	2.0(12.0)	0.77	0.86	0.015	8.6	0.19	0.12
Energy confinement time, τ_E (ms)	0.2(0.6)	0.1	~ 0.05	1-2	0.8	0.062	0.50
$n\tau_E$ (10 ¹⁶ s/m ³)	0.3(5.0)	1.0	0.3	0.1	40	0.5	0.14
$\beta = 2nk_BT/(B^2/2\mu_0)$	0.1(0.14)	0.1	0.1	~ 0.001	0.6-0.9	0.08-0.12	0.02

(a) Correcting for radiation gives $\tau_E = 35$ ms for W-VIIA and 40 ms for Heliotron-E.

(b) Value outside parentheses correspond to 0.2-MA operation, those within are for recent 0.4-MA discharges.

Fig. II.A-1. Achieved, projected, and reactor $n\tau_E$ values plotted versus total kinetic energy stored in the plasma, E_p . Solid squares indicate achieved parameters and open squares indicate design goals.

additional 100- to 1000-fold increase in stored plasma energy required for the commercial reactors summarized in Table II.A-II, however, will require major increases in cost, physics performance, and technology development. The smaller, and presently lower-performance, Alternative Fusion Concepts (AFCs) depicted on Fig. II.A-1 may lead directly to a competitive, less-costly commercial reactor; compact reactor embodiments that require an order-of-magnitude lower value of E_p may allow commercial fusion power to be achieved with considerably reduced development requirements.

With the exception of the CRFPR, all the reactor designs summarized on Table II.A-II would use large superconducting magnets, store large quantities of magnetic-field energy, and have system power densities (i.e., ratio of useful thermal power to FPC volume) that are 10-30 times below those for conventional fission reactors. Concurrently, these systems require large tonnages of high-

TABLE II.A-II
SUMMARY OF KEY PARAMETERS FOR A RANGE OF DT FUSION REACTOR CONCEPTS^(e)

Device	MSR ⁵¹	STARFIRE ³	EBTR ⁵²	RFPR ⁵³	MARS ^{5,6}	CRFPR ¹⁵	PWR ⁵⁴
Design date	1981	1980	1980	1979	1983	1982	1980
Plasma radius (m)	0.81	2.38	1.0	1.2	0.49	0.71	--
Major radius (m)	23.0	7.0	35.0	12.7	131 ^(a)	4.3	--
Plasma volume (m ³)	298	781	691	361	99	42.7	--
Average density (10 ²⁰ /m ³)	3.64	0.81	0.95	2.00	3.3	3.4	--
Temperature (keV)	8.0	22	29	15	28	20	--
Plasma energy (GJ)	0.21	0.67	0.91	0.81	0.44 ^(a)	0.14	--
Field energy (GJ)	109	61	131	14.7	60	1.65	--
Lawson parameter (10 ²⁰ s/m ³)	3.7	3.0	1.7	2.0	6.6	0.75	--
Average beta	0.08	0.067	0.17	0.30	0.28	0.20	--
DT plasma power density (MW/m ³)	14.8	4.5	4.1	7.0	26.3	72.4	90
Magnetic field (T)	6.56	5.8	5.0/2.25	3.3	4.7 ^(b)	5.2	--
Neutron current (MW/m ²)	1.9	3.6	1.4	2.7	4.3	19.5	--
Thermal power (MWt)	4000	4033	4028	3000	3400	3350	~ 3300
Net power (MWe)	1302	1200	1214	750	1202 ^(c)	1006	1000
System power density (MWt/m ³)	0.60	0.50	0.24	0.50	0.29	15	19.8(7.5) ^(d)
Mass utilization (tonne/MWt)	6.6	5.7	10.85	3.7	6.8	0.37	0.33
Thermal conversion efficiency	0.35	0.35	0.35	0.30	0.43	0.35	0.33
Recirculating power fraction	0.07	0.167	0.15	0.17	0.22	0.14	--
Net plant efficiency	0.33	0.30	0.30	0.25	0.33	0.30	--
Unit direct cost (\$/kWe) ^(g)	1265	1438	1737	1104	1480 ^(f)	863	900
Construction time (years)	10	6	5	10	8	5	8-10
"Then-current" (date)	1991	11986	1985	1988	1988	1986	1983
COE (mills/kWeh) ^(g)	78	67	72	66	50 ^(f)	41	40

^(a)Central cell.

^(b)Central cell, 24 T peak at mirror throat.

^(c)Based on 2800 MW of neutron power, which is multiplied in the blanket by 1.37 and an alpha-particle power of 700-MW (3500-MW fusion power), which is directly converted with an efficiency of 0.5.

^(d)Including steam-generator volume.

^(e)More detailed physics, FPC and cost comparison between the tokamak (STARFIRE and MkIIb), tandem mirror (MARS), and CRFPR can be found in Table II.C-I of Sec. II.B.

^(f)Reference 6 values are 1966 \$/kWe and 67 mills/kWeh in 1983 dollars. These values are brought to the common-base 1980 dollars using a 10 % deflation rate.

^(g)All costs based on 1980 dollars.

technology FPC mass per unit of thermal power (i.e., mass utilization in Table II.A-II). Significant reductions in FPC mass utilization, stored plasma and magnetic-field energies, and projected unit costs are major improvements promised by the compact approaches. The compact systems are nearly an order-of-magnitude closer to commercialization as measured on Fig. II.A-1 by E_p , operate with low-technology copper (nonsuperconducting) magnets, and provide a system with FPC power densities and mass utilizations that are closer to values deemed economic in contemporary fission power plants. The range of sizes projected for commercial fusion reactors, including the CRFPR and a PWR, is illustrated in Fig. II.A-2; this figure is a graphical display of the contents of Table II.A-II.

Fig. II.A-2. Relative sizes of mainline and alternative magnetic fusion power reactors. With the exception of the compact RFP reactor (CRFPR), all systems propose the use of large superconducting magnets. Thermal(net electrical) powers are indicated in GWt(GWe) units, and system power density is also shown. In presentation of the (linear) MARS tandem-mirror design, its length has been reduced by 2π to generate an effective major radius for purposes of comparison only.

In addition to the CRFPR, high-power-density versions of the tokamak (Riggitron^{9,20}) and the Ohmically-Heated Toroidal Experiment (OHTe¹⁸) have been proposed. Table II.A-III summarizes key reactor parameters for the CRFPR, OHTe, and Riggitron in comparison to the superconducting STARFIRE tokamak reactor. Intercomparisons and preliminary technology assessments for these compact systems relative to the co-mainline fusion approaches can be found in Refs. 11 and 37.

A plot of the system power density versus the mass utilization projections given on both Tables II.A-II and II.A-III results in Fig. II.A-3. Shown also are the system power densities for the Magnox,⁵⁵ Superphenix (SP) Liquid-Metal Fast-Breeder Reactor (LMFBR),⁵⁶ Advanced Gas Reactors (AGR)⁵⁷, and the aforementioned Pressurized-Water Reactor (PWR)^{54,58} with both the reactor primary pressure vessel and the steam-generator (SG) power densities for the PWR indicated. The SP system power density referred to the "hot sodium pool" is most appropriately compared to the AGR and PWR cases, since use of the full volume of reactor vessel in this case also includes the intermediate heat exchangers (IHxs) and primary coolant pumps. The system power density projected for the gas-cooled Magnox reactors is very low; these older systems are economic today simply because the original investments for these older systems have long been paid. Hence, system power densities for present fission power systems range from 2-15 MW/m³, which typically is an order of magnitude above the system power densities being projected for most fusion concepts. The compact fusion concepts are attempting to operate with system power densities that are more in line with what is deemed economic for a range of fission power systems.

It is well recognized that system power density is but one of several figures of merit useful in projecting the competitiveness of a power system. Any comprehensive analysis of an optimum power system ultimately must be based on the cost of electricity, COE(mills/kWeh). The COE should accurately reflect the cost of achieving a feasible engineering system (i.e., design complexity and degree of needed design conservatism), cost of operations and maintenance (i.e., FPC "burnup"), cost of environmental and safety restrictions (including resource utilization, afterheat and stored-magnetic-energy control, and long-term radwaste storage), construction time (on-site versus off-site fabrication), and plant availability (i.e., mean-time-to-failure versus mean-time-to-repair). Generally, the system power density, mass utilization, or neutron first-wall loading reflect one important input into the COE equations through the unit

TABLE II.A-III

SUMMARY OF KEY PARAMETERS FOR COMPACT HIGH-POWER-DENSITY
TOROIDAL FUSION REACTORS COMPARED TO STARFIRE

	STARFIRE ³	CRFPR ¹⁵	OHTe ¹⁸	RIGGATRON ^{9, 20}
Plasma radius (m)	2.38	0.71	0.67	0.32
Major radius (m)	7.0	4.3	5.91	0.80
Plasma volume (m ³)	781.	42.7	52.1	2.0
Average density (10 ²⁰ /m ³)	0.8	3.4	10.0	20-30
Average temperature (keV)	22	20(a)	5-6	12-20
Average beta	0.067	0.12	0.22	0.20
Plasma power density (MW/m ³)	4.5	72.4	64.0	500.
Plasma current (MA)	10.1	18.5	12.4	3-4
Plasma current density (MA/m ²)	0.57	11.7	8.8	7.2-9.6
Magnetic field (T)	5.8	5.2(b)	11.2(f)	10.-16.(h)
Neutron current (MW/m ²)	3.6	19.5	19.5	68.4
Thermal power ^(c) (MWt)	4033.	3350.	2740.	1325.
Net power (MWe)	1200.	1000.	904.	355.
System power density ^(d) (MWt/m ³)	0.50	15.0	3.2	5.2(i)
Mass utilization ^(e) (tonne/MWt)	5.7	0.37	1.45(g)	0.28
Thermal conversion efficiency	0.35	0.35	0.40	0.41
Recirculating power fraction	0.167	0.15	0.35	0.33
Net plant efficiency	0.30	0.30	0.24	0.27

(a) Flat temperature profile, $J_0^2(\mu r)$ density profile.

(b) Peak poloidal (confining) fields at plasma edge. Toroidal field at plasma axis is 9.5 T, toroidal field at the TFC is 0.72 T, and the maximum poloidal field is 4.5 T at the PFC. Maximum field at the back-biased OHC during startup is 9.12 T.

(c) Total useful thermal power.

(d) Based on volume enclosed by and including the coils and total thermal power.

(e) Based on total thermal power and total mass of FW/B/S/C.

(f) Peak fields at Ohmic-heating coil during initiation of discharge.

(g) Of the 5500 tonne for FW/B/S/C, this particularly heavy (PbLi) blanket weighs 3200 tonne. An unusually heavy OHC is also used to minimize losses during startup.

(h) Peak field prior to ignition, with the field subsequently being decreased during the burn.

(i) The power density within volume defined only by the Riggatron coil set is 160 MWt/m³.

Fig. II.A-3. Display of system power density versus inverse of the mass utilization for a number of fusion reactor projections and a comparison with a number of fission reactor systems.

direct cost, UDC(\$/kWe), which for a given net power output typically equals the sum of a fixed cost and a cost that varies inversely with the FPC power density or neutron first-wall loading. The system tradeoffs that enter into the determination of COE are fully incorporated into the CRFPR design-point determination and are explored more quantitatively in the following Secs. II.B. and II.C.

In summary, the present status and planned near-term progress projects confinement parameters, $n\tau_E$, that should be adequate for a self-sustained ignition in a DT plasma. This significant achievement, however, will occur in a plasma of energy content that remains many orders of magnitude below the requirements for a commercial power reactor. Generally, efficient confinement of hot and dense plasma does not appear as an insurmountable barrier to commercial fusion power; instead, the technology and cost required to contain such plasmas with reactor-relevant total energy contents and total power appear as pacing items. In this context, certain AFC concepts, although less developed at present, may offer attractive routes to commercial fusion power by allowing viable reactors with reduced total plasma energy, physical size, complexity, and associated confinement technology.

B. Rationale for High-Power-Density Fusion

On the basis of the summary of experimental status and reactor projections given in Fig. II.A-1, the compact, high-power-density approaches can reduce the stored plasma energy required for commercial fusion by an order of magnitude while simultaneously giving enhanced system power density and FPC mass utilization (Table II.A-II). Ultimately, however, the decision on an optimal system power density must be made on the basis of economics. This subsection develops further the rationale for compact systems on the basis of cost projections made for fusion.

The direct costs of building a fission or fusion reactor can be divided into two major components: the Reactor-Plant-Equipment (RPE) cost and the Balance-of-Plant (BOP) cost. The FPC consists primarily of the first wall, blanket, shield, magnets, and associated support systems, which for some concepts can represent an important contributor to the RPE cost. Other RPE items include main heat-transport systems, auxiliary heating equipment, vacuum, cryogenic, and tritium systems. The BOP consists of most subsystems outside the secondary containment, such as the secondary heat-transport system, heat exchangers and steam generators, turbines, electrical generators, auxiliary systems, and buildings.

The RPE cost for fission reactors is approximately 25 % of the plant total direct cost (TDC), the BOP accounting for the remaining 75 %. Studies of most fusion reactors project RPE costs that range from 50 to 75 % of the TDC. The BOP costs for a fission and fusion plant of the same total electrical power output are expected to be similar. Hence, TDC estimates for fusion reactors predict higher values than for fission power plants because of high RPE costs related primarily to expensive (i.e., massive, high-technology) FPCs. It is noted that fusion reactors capable of direct-energy conversion, such as the tandem mirror, attain higher overall energy conversion efficiencies and, therefore, project smaller BOP costs for the same total electrical power. In the case of the tandem mirror, however, this advantage is eroded somewhat by the higher recirculating power requirements. Furthermore, the TDC for the tandem mirror will be smaller only for sufficiently low cost of the direct-energy convertors. It is also noted that systems with unattractively high recirculating power fractions will require larger BOPs and associated costs; for such systems the RPE/BOP cost ratio will be artificially depressed, not because of low RPE, but because of abnormally high BOP costs.

A summary of RPE/TDC values based on the recent fusion reactor design studies summarized in Table II.A-II is given in Fig. II.B-1; the dominance of the RPE costs for both mainline and major alternative fusion concepts is indicated. The Unit Direct Costs ($UDC = TDC/P_E$, where P_E is the net electric power) plotted on Fig. II.B-1 as a function of the ratio RPE/TDC use nominal values of ~ 900 $\$/kWe$ and 0.25 for UDC and RPE/TDC, respectively, to normalize the fusion projections to LWR fission power. The ratio of TDC for fusion relative to fission can then be determined analytically under the assumption that the BOP costs for similar fusion and fission power plants are nominally equivalent; this "analytic" curve of $R_{DC} = (UDC)_{FUSION}/(UDC)_{FISSION}$ is also given on Fig. II.B-1. Assuming that the fusion system can expend more on capital investment by taking advantage of a nil fuel cost, this tradeoff of fuel

Fig. II.B-1. Plot of UDC versus RPE/TDC for a range of fusion reactor designs. Normalizing these costs to the LWR ($UDC \approx 900$ $\$/kWe$, $RPE/TDC \approx 0.25$), the "analytic" curve of $R_{DC} = (UDC)_{FUSION}/(UDC)_{FISSION}$ is also shown as a function of RPE/TDC under the assumption of nearly equal BOP cost for comparable fusion and fission power plants.

for capital cost becomes marginal for R_{DC} values in excess of ~ 1.3 if the fuel cost for fission nominally comprises $1/4$ - $1/3$ of the energy cost. Generally, operation in the $RPE/TDC \lesssim 0.3$, low-economic-leverage regime will require the FPC to be a less-dominant component of the TDC. For reasonable unit costs ($\$/kg$) of fabricated, high-technology components that compose the FPC and associated support systems, this criterion can be met only by decreased FPC mass utilization (tonne/MWt) or increased system power density; more-compact systems will be required.

The FPC mass per unit of generated thermal power (i.e., FPC mass utilization) for most fusion-power-plant designs is projected to lie in the range 5-10 tonne/MWt, compared to 0.3 tonne/MWt for LWRs (Table II.A-II and Fig. II.A-3). The mass utilization for the LWR is computed as the ratio of mass of the primary containment vessel (less the fuel) divided by the total thermal power generated. The mass utilization must be used carefully as a comparative measure of system performance; clearly, such comparisons imply a monotonic relationship between total mass and cost. Systems that propose FPCs composed of large masses of inexpensive and easily replaced/reused coolant (i.e., PbLi) or concrete should appropriately compensate the mass utilizations (e.g., use mass of drained blanket). It is also noted that the mass of an entire LWR fission power plant, exclusive of concrete but including all reinforcing bar, is in the range 10-15 tonne/MWt, which in some cases is approached by the FPC mass utilization alone projected for certain fusion systems. Figure II.B-2 graphically summarizes the FPC mass utilizations that have been predicted for a range of commercial fusion reactor designs; an average FPC cost of ~ 30 $\$/kg$ is indicated. The effect of doubling the unit cost of the FPC on the UDC is readily seen by doubling the slope of the dashed line on Fig. II.B-2; a ~ 60 $\$/kg$ FPC unit cost could rapidly catapult high-mass-utilizations systems out of economic contention.

The RPE for the compact RFP reactor is projected to be only $\sim 1/3$ of the TDC because the FPC and associated support equipment are smaller and less costly than the other fusion systems of similar electrical output; the FPC mass utilization is similarly closer to the comparable figure (0.3 tonne/MWt) for LWR fission power. The direct cost of the compact fusion reactor, therefore, is expected to be only slightly higher than the cost of an LWR fission reactor. More importantly, however, the total cost of systems with $RPE/TDC \lesssim 1/3$ will be less sensitive to physics and technology uncertainties associated with the

Fig. II.B-2. Correlation of the UDC projected for a number of fusion reactor designs with the FPC mass utilization. Increasing the FPC unit cost from 30 \$/kg to 60 \$/kg doubles the slope of the dashed line.

assumed plasma performance and FPC operation; both significantly effect plant performance and cost, which in turn can lead to appreciable costing uncertainty and potentially significant overruns. The criticism that absolute values of project cost should not be taken too seriously at this early stage of fusion power development has some legitimacy. Relative cost comparisons, however, are meaningful and useful. The uncertainty in predicting plasma performance and the dominance of the plasma performance in the overall cost equation for fusion represents a cause for concern. Rare are the examples where the projections of advanced technologies, be they energy or weapons systems, have proved to be either technically or economically conservative.⁵⁹

The direct capital cost represents only one component used in deriving the overall cost of electricity (COE) for a power plant. Figure II.B-3 graphically summarizes all major cost components and indicates the combination of these components to determine the COE. Also indicated on Fig. II.B-3 are elements and

Fig. II.B-3. Logic diagram illustrating the means by which the levelized generating cost of electricity (COE) is computed. Also shown at the top are key influences that may favorably or unfavorably impact the COE when considerations of compactness or high power density are taken into account.

tradeoffs that may impact favorably or unfavorably on the COE when compact versus conventional options are compared. The annual fixed charges for conventional and compact fusion reactors will be approximately proportional to the TDC because the indirect capital cost is nominally the same percentage of the TDC for both compact and conventional reactors, and the fixed charge rate will be the same unless, for example, the compact reactor requires less time to construct and is more amenable to mass production methods. Fuel expenses will be equal for the same fusion power, and operation and maintenance (O&M) costs are expected to be approximately equal for the same plant electrical capacity. The O&M costs will vary if the costs of replacing the FPC differ; both conventional and compact reactors, however, require replacement of approximately equal masses of material per unit time ($\sim 200\text{--}400$ tonne/yr) for the same FW/B lifetime (~ 15 MWyr/m²). Although FPC lifetimes of $10\text{--}15$ MWyr/m² are projected for stainless-steel first walls and blankets, transmutation-related resistivity increases in first-wall coils (i.e., for Riggatron^{9,20} and OHTE¹⁸ reactors) may reduce lifetimes to values as low as 5 MWyr/m². The annual generating cost for a compact fusion reactor in some cases, therefore, can be lower than for a superconducting fusion reactor primarily because of the lower RPE cost. The annual energy output (kWeh/yr) for fusion reactors of equal capacity may not be equal because the recirculating power fractions and the capacity factors may be different. For instance, the compact tokamak (Riggatron) and the OHTE reactors may have higher recirculating power requirements and shorter radiation lifetimes because of the first-wall coil position.

Compact fusion reactors are also expected to be higher-stress devices relative to other fusion reactors because of higher power densities, thermal loads, and neutron fluxes (and higher magnetic fields at the coil for the Riggatron). Measured in terms of power density and surface heat fluxes, however, this operating condition is similar to the standard operating conditions encountered in LWR fission systems, albeit fusion in terms of load peaking has a more-difficult cooling geometry. Furthermore, operating at the higher-stress state should not reduce the plant capacity factor if equal engineering design criteria are used for compact and conventional reactors, although a higher cost for the former is expected. Because of the significantly reduced mass utilization, the compact systems can operate with a total FPC mass that is sufficiently small (~ 1100 -tonne for CRFPR) to allow total "block" (i.e., single-piece) maintenance of the FPC, with the attendant possibility for

rapid change out, replacement, and system restart. Nevertheless, a potential exists for a lower plant factor relative to the low-power-density fusion systems, this lower plant factor possibly diminishing the promise of reduced COE anticipated as a result of reduced TDC and construction time. Design-specific reliability analyses remain to be performed on a comparative basis; an important tradeoff exists between a possible decrease in the mean-time-to-failure and mean-time-to-repair related to increased power density in smaller, more integrated systems.

Lastly, other less-quantifiable measures of technical and economic feasibility for an emerging energy technology can be formulated. The recent economic problems faced by large fission power plants⁶⁰⁻⁶² point to a potentially important lesson for fusion. Over the past decades, fission power plants have increased in size, reflecting primarily increased centralized demand, the availability of large turbine/generator units, perceived advantages of economies of scale, and the need to maintain a competitive edge over fossil energy sources. Unfortunately, the construction costs for fission power relentlessly increased, this costs insidiously tracking increases in unit size, system complexity, construction time, prices of goods and services, and licensing/regulatory constraints. The increased size and complexity for fission power prolonged the "one-of-a-kind" phase, standardization became less available, outages were longer, repair time was extended, and few repairs could be made with "off-the-shelf" inventory items. The corrective measures presently being suggested for the fission industry generally call for small, less-complex reactor systems that promise to be economic because of the eroding economies of scale. Standardization and off-site factory construction is emphasized, and flexibility in sizing is designed to track more closely the (declining) rate of market growth, the market spectrum, and changing interest rates, escalation, and minimum coverage ratios.⁶³⁻⁶⁶ This approach is said to result in a shortened and more-predictable construction schedule, with key nuclear systems being built and qualified by a small cadre of engineers and technicians at a controlled, off-site factory, with the bulk of the nonnuclear BOP construction being performed on a more rapid and less-costly schedule and location. Based on this evolving picture for fission, no reason can be identified that would cause these problems to be less severe for fusion. These problems may in fact be worse since the approaches to fusion embodied in Table II.A-II generally offer a power system that has

- 10-30 times less power density.
- 10 times more mass utilization of systems that can be immensely more complex.
- RPE dominating the cost equation, with RPE being most sensitive to yet-to-be-resolved plasma performance.
- costs tending to optimize at large total power outputs.
- complex front-line support systems that must operate in a strong radiation field.
- slow and expensive migration along crucial learning curves toward standardized reactor systems.

By focusing more onto fusion approaches that a) allow engineering tests to be performed on end-product-relevant devices, b) allow more options to be examined that are economic of time and dollars, and c) allow early demonstration of both financial and technical risk, fusion can become a serious energy option sooner. The compact, high-power-density approach offers this promise of a bolder, more-aggressive development program that can lead to an end product with enhanced potential for market penetration. The compact systems in many respects can provide a more robust, "forgiving" approach to fusion power.

C. Simplified Reactor Model

The heuristic arguments made in the last section have been guided by the results of detailed, parametric systems studies (Table II.A-III). This section uses a simplified global model to examine generic physics/engineering/economic issues related to the compact fusion systems. Of necessity the simplified physics and costing models adopted/extended for this analysis are limited and, therefore, must be applied cautiously. A more-exact analysis that is specific to the RFP is given in Sec. IV.C.

The constraints imposed by plasma and particle physics on the selection of a reactor design can generally be classified according to the following areas:

- plasma confinement
 - equilibrium
 - stability
 - particle/energy transport
- plasma heating
 - external (neutral beams, rf)
 - intrinsic (alpha particles, ohmic dissipation of plasma currents)
- initiation and sustainment of plasma currents
- plasma boundary control
 - refueling
 - impurity/ash removal
 - plasma/wall interaction.

In practice, the physics associated with each of these important areas plays a secondary role in the selection of a reactor design point.⁶⁷ Ignition is specified for a global, steady-state plasma, which together with pressure balance determines the relationship between first-wall neutron (and heat) loading and plasma minor radius, r_p ; the confinement time, τ_E , the βB^2 product evaluated at the plasma, system power density, P_{TH}/V_{FPC} , and total thermal power, P_{TH} , for a given aspect ratio, $A = R_T/r_p$, then result. Figure II.C-1 gives a schematic view of this idealized reactor model. For a blanket energy multiplication $M_N \approx 1.17(20 \text{ MeV/fusion})$, $\langle \sigma v \rangle / T^2 \approx 1.1(10)^{-24} \text{ m}^3/\text{s keV}^2$, $n\tau_E = 2(10)^{20} \text{ s/m}^2$, and $T = 15 \text{ keV}$, pressure balance, the specification of ignition, total thermal power, P_{TH} , the system power density, and a sample confinement (e.g., Alcator-like) scaling, respectively, give the following relationships:

$$I_w(\text{MW/m}^2) = 0.48 r_p (\beta B^2)^2 \quad (1)$$

$$I_w = (2.80/\tau_E^2) r_p \quad (2)$$

$$I_w = [2(P_{TH}/V_{FPC})(\Delta b + \delta)/(M_N + 1/4)] (1 + x)^2/4x \quad (3)$$

$$I_w r_p^2 = (P_{TH}/A)/[(2\pi)^2(M_N + 1/4)] \quad (4)$$

$$r_p \beta B^2 = 2.42/f_A^{1/2}, \quad (5)$$

where the blanket and shield thickness is $\Delta b = \Delta b_{BLK} + \Delta b_{SLD}$, δ is the coil thickness, and $x = r_p/(\Delta b + \delta)$. Equation (3) results from the following definition of system power density:

$$\frac{P_{TH}}{V_{FPC}} = (M_N + 1/4) I_w \frac{A_{FW}}{V_{FPC}} \quad (6A)$$

$$\frac{V_{FPC}}{A_{FW}} = \frac{r_w}{2} \left\{ 1 + \frac{\Delta b + \delta}{r_w} \right\}^2 \geq 2r_w, \quad (6B)$$

where, as shown in Fig. II.C-1, the maximum FPC power density for a given first-wall neutron loading occurs when $x = 1$; $(P_{TH}/V_{FPC})_{MAX, I_w, M_N} = I_w(M_N + 1/4)/[2(\Delta b + \delta)]$. Shown also on Fig. II.C-1 are the various reactor design points summarized on Table II.A-II. With the exception of the MARS design point, which has a considerable power flow out the open ends and minimizes the end-plug technology by minimizing the plasma radius, most of the closed systems tend to select a plasma radius based on power density and first-wall loading considerations rather than directly on the basis of plasma confinement or transport. The ratio of FPC power density, P_{TH}/V_{FPC} , to plasma fusion power density, P_F/V_P , where P_F is the neutron plus alpha-particle power and V_P is the plasma volume, is also shown on Fig. II.C-1; $(P_{TH}/V_{FPC})/(P_F/V_P) = (4/5)(M_N + 1/4)x^2/(1 + x)^2$. Depending on M_N , the plasma power density is reduced by 3-5 to give the FPC power density.

In deriving the expression for the maximum power density ($r_w \approx \Delta b + \delta$), I_w , Δb , and δ are held constant, ignoring the relatively weak interdependence between Δb , I_w , r_w , M_N , and the desire to achieve a given radiation and heating level at the coil position. The coefficients appearing in Eqs. (1) through (4) depend somewhat on assumed plasma temperature and density profiles as these quantities determine $n\tau_E$ and average fusion reactivity. The last expression

Fig. II.C-1. Radial build of a generic fusion reactor and the dependence of system power density on geometry. Shown also are the results from key reactor design studies (Table II.A-II).

[Eq. (5)] gives Alcator transport scaling for calibration purposes, where $f_A \equiv \tau_E / 5(10)^{-21} n r_p^2$; the confinement time required for a given I_w and r_p is given by Eq. (2) and must be matched by the physics scaling, be it Alcator or something else. Hence, the basic reactor characteristics are determined by a physics base that is no more profound than that required to assure a global energy and pressure balance on an idealized, average-property, steady-state, ignited plasma with the neutron first-wall loading being chosen on the basis of technology (coil fields, heat fluxes, etc.) and economics (i.e., power density, plant availability, etc.). These expressions are plotted in Fig. II.C-2, wherein

Eqs. (1) and (2) are the dot-dashed lines (respective values of βB^2 and τ_E are indicated), the long-dashed curves give the total power per unit aspect ratio, P_{TH}/A , and the solid curves give the relationship between I_w and r_p for a given system power density. In order to evaluate Eq. (3) graphically, specific values of $\Delta b + \delta$ had to be assumed. Figure II.C-2 has been generated for a typical superconducting-coil case ($\Delta b + \delta > 3$ m) and the minimum B/S case allowed for exoblanquet, resistive copper coils ($\Delta b + \delta \approx 1$ m).

Selection of a specific region of the $I_w:r_p:(P_{TH}/V_{FPC}):\beta B^2:\tau_E$ hyperspace described on Fig. II.C-2 must be made on the basis of economic and physics judgments. Economics will generally specify an optimal system power density, P_{TH}/V_{FPC} , or first-wall neutron loading, I_w ; physics will constrain the choice of τ_E and the associated scaling with the plasma system variables; and a combination of physics and engineering will determine the all-important βB^2 product. Assumptions that underlie the results depicted in Fig. II.C-2 may shift the curves and regions defined thereby, these assumptions being summarized below.

- Plasma and first-wall minor radii are taken as equal, $r_p = r_w$; the dilution of system power density by a scrapeoff region is not taken into account.
- Profile effects (i.e., peaked versus flat pressure profiles) can result in factors of two differences in fusion plasma power density for a given βB^2 ; flat profiles have been assumed.
- The field used in the product βB^2 refers to the field at the plasma surface, with the toroidal field at the coil roughly being increased to $B_c \approx B/(1 - 2/A)$ or more if finite coils and field ripple are taken into account. This constraint, of course, applies only to those systems confined primarily by toroidal field; the main confining field in an RFP is poloidal and decreases from the plasma surface to the coil.
- The blanket energy multiplication, M_N , can vary over the range 1.1 to 1.5, depending on materials selection.
- Implicit in Eq. (3) is the assumption of a fixed value of $\Delta b + \delta$. Increased shielding will be needed to protect the coils at higher first-wall neutron loadings, nominal values being selected for the purposes of Fig. II.C-2.

Fig. II.C-2. Dependence of I_w versus r_p as determined by pressure balance [Eq. (1)], ignition condition [Eq. (2)], economics [Eq. (3)], and power balance [Eq. (4)]. Expressed in terms of I_w and r_p , the Alcator scaling [Eq. (5)] becomes $I_w r_p = 2.8/f_A$, which could also be plotted as straight lines on these figures.

- The use of noncircular plasmas to achieve high-beta values obviously departs from the model used to generate Fig. II.C-2. In addition, other beta scalings (e.g., $\beta^*A = \text{constant}$) can be applied to further constrain the problem, with the $\beta^*A = \text{constant}$ condition actually giving a unique aspect ratio for maximum FPC power density.

Inclusion of these and other constraints and physics adds more realism to this simplified "systems model," with a considerable loss in transparency. In spite of these shortcomings, the present model nevertheless provides a relatively realistic description of a broad range of reactor options. Systems of low-to-moderate aspect ratio ($A = 3-5$) that are dominated by toroidal magnetic field generally cannot provide more than 5-6 T at the plasma if 10- to 12-T limits are imposed at superconducting magnets. Given beta limits in the range 0.05 to 0.10, this limits the plasma pressure parameter to $\beta B^2 \leq 2.5 \text{ T}^2$. For power plants of total thermal output $P_{TH} \leq 4000 \text{ MWt}$, most of these devices share the lower regions of Fig. II.C-2 in the narrow region defined by $P_{TH}/A = 500$ and 1500 MWt contours. These systems generally are physics (i.e., beta) and engineering (i.e., field) limited in that better economics more than likely would result for higher values of P_{TH}/V_{FPC} if this region could be obtained through higher βB^2 values.

At the other end of the spectrum are the higher-power-density systems, which attain FPC power densities in the range above 5 MWt/m^3 ; for these systems βB^2 values above $\sim 5 \text{ T}^2$ are required, with design points again generally residing within the band defined by $P_{TH}/A = 500$ and 1500 MWt. These designs, however, clustered in the upper regions of Fig. II.C-2. Generally, those confinement schemes capable of compact, high-power-density operation use a thin blanket/shield of proportions requiring normal, water-cooled copper ($\Delta b + \delta < 1 \text{ m}$) rather than superconducting ($\Delta b + \delta > 3 \text{ m}$) coils; also, unless highly stressed coils can be accommodated close to the plasma, confinement by poloidal rather than toroidal fields is preferred to achieve the increased βB^2 values ($5-6 \text{ T}^2$) required for high-power-density operation while minimizing ohmic losses in the copper coils.

The RFP allows access to both of the aforementioned reactor regimes: normal-coil, high-power-density^{15,16} or superconducting-coil lower-power-density³¹ FPCs. In the case of the RFP, the pressure balance given by Eq. (1) can be expressed in terms of the toroidal plasma current, I_ϕ , and the poloidal beta, β_θ . In this case Eq. (1) becomes

$$I_w(\text{MW/m}^2) = 7.67(10)^{-4} \frac{\beta_\theta^2 I_\phi^4}{r_p^3} \quad (7)$$

$$= 0.086 \beta_\theta^2 j_\phi^2 r_p^5 ,$$

where I_ϕ has the units of MA and $j_\phi(\text{MA/m}^2)$ is the plasma current density. This relationship can also be plotted in Fig. II.C-2 and indicates that for either standard or compact reactor embodiments, $\beta_\theta^{1/2} I_\phi$ in a narrow range about 9 MA will be required (~ 20 MA for $\beta_\theta \approx 0.2$).

Although this simplified systems model is not intended to foreclose the compact option for configurations that are dominated by large toroidal fields, certain problems become apparent when attempts are made to increase power density in systems dominated by toroidal field. Generally, increased FPC power density and reduced FPC mass utilization are obtained by increasing $I_w \approx 0.48(\beta B^2)^2 r_p$ and decreasing $\Delta b + \delta$, the latter accomplished by reduced shield thickness and the use of resistive copper coils. The increased first-wall heat load becomes comparable to that considered acceptable for the limiters of the low-power-density systems,³ with the total first-wall area for the former being comparable to the limiter area in the latter. Accompanying the increased first-wall neutron loading with reduced B/S thickness and fixed total power is an increase in blanket power density that may require flowing liquid-metal coolant/breeder. Again, if the magnetic fields within the blanket are too large, the MHD pressure drop for a flowing liquid-metal coolant, $\Delta P_{\text{MHD}} \propto \ell B^2 v$, can become prohibitive; even though the total flow path, ℓ , is reduced for a compact system, the higher blanket power density will require a high flow velocity, v , to maintain structural temperature and corrosion limits, this also contributing to increased pumping power. Hence, because of plasma power density (increased βB^2 with reduced r_p), MHD pumping power and coolant pressure, and magnet stress and ohmic losses, systems that are not dominated by toroidal field are preferred for compact, high-power-density operation. Given that these physics and engineering constraints can be met, plant and electricity costs will ultimately dictate the design region of interest on Fig. II.C-2.

Before this region in the I_w - r_p phase space where an economically attractive reactor might lie can be determined, a detailed costing tradeoff study must be made.¹⁵ A parameterized form of the costing algorithm described in Ref. 15 is used here to illustrate the essential elements of the process used for design-point selection. Again, while this simplified costing model reproduces the results from detailed designs, it must nevertheless be used cautiously when extended into regions beyond those for which "calibrations" exist. The present model also fixes the recirculating power fraction, which can be significantly influenced by MHD-pumping and ohmic-coil power requirements.

Analytically fitting the tabular costing formulae used in Ref. 15, which in turn have been adopted from the detailed STARFIRE costing data base,³ the following expression for the unit direct cost, UDC (\$/kWe), results:

$$(1 - \epsilon)UDC/1.17 = F + \frac{C}{(P_{TH}/V_{FPC})} \quad (8A)$$

$$F = \frac{460.}{P_{ET}^{0.62}} + \frac{44.3}{\eta_{TH}} + \frac{14.2}{\eta_{TH}^{0.8} P_{ET}^{0.2}} \quad (8B)$$

$$C = \frac{1000 \ c_{FPC}}{\eta_{TH}} \ , \quad (8C)$$

where ϵ is the recirculating power fraction, η_{TH} is the thermal conversion efficiency, $P_{ET}(GWe) = \eta_{TH}P_{TH}$ is the total electric power, and $c_{FPC}(M\$/m^3)$ is the volumetric cost of the FPC. The quantity F represents the fixed-cost component, whereas C relates to those costs that depend on FPC volume and, hence, system power density, P_{TH}/V_{FPC} . The factor 1.17 in Eq. (8A) accounts for 15 % contingency and 2 % spare-parts costs that are included in UDC. Equations (8) can be expressed in terms of $I_w(MW/m^2)$ given the ratio A_{FW}/V_{FPC} of first-wall area to FPC volume [Eq. (6B)]. Hence, defining a FPC cost per unit FW area, $c_{FW}(M\$/m^2) \equiv (V_{FPC}/A_{FW})c_{FPC}$, the following expression for the UDC emerges:

$$\text{UDC}(\$/\text{kWe}) = \frac{538.2}{P_E^{0.62}(1 - \epsilon)^{0.38}} + \frac{16.6}{\eta_{TH}^{0.8}(1 - \epsilon)^{0.8}P_E^{0.2}} + \left[51.8 + \frac{1170 c_{FW}}{(M_N + 1/4)I_w} \right] \frac{1}{(1 - \epsilon)\eta_{TH}} \quad (9)$$

It is noted that the FPC unit mass costs are $c'_{FPC}(\$/\text{kg}) = 10^6 c_{FPC}(\text{M}\$/\text{m}^3)/\rho_{FPC} = 10^6 c_{FW}(\text{M}\$/\text{m}^2)(A_{FW}/V_{FPC})/\rho_{FPC}$, in which $\rho_{FPC} = 2\text{--}3000 \text{ kg/m}^3$ is a typical FPC "smear" density, as is illustrated in Fig. II.A-3. The FPC unit mass costs range from 10-60 $\$/\text{kg}$, depending on the specific component, with an average value of $\sim 30 \text{ } \$/\text{kg}$ emerging from a composite of all major designs reported to date (Fig. II.B-2).

In order to convert the UDC into a COE(mills/kWeh), the annual Return On Investment (ROI) and operating costs must be specified as well as the fraction of the year, p_f , that the plant is capable of operating at full power. Hence, if the FW/B costs a fraction f_{FWB} of the total direct costs and $(I_w\tau)$ is the FW/B lifetime measured in units of MWyr/ m^2 , the COE is given by

$$\text{COE}(\text{mills/kWeh}) = \frac{\text{UDC}}{8.76} \left[f_{FWB} \frac{I_w}{(I_w\tau)} + f_{IE} \frac{(\text{ROI} + \text{O\&M})}{p_f} \right] \quad (10)$$

The quantity f_{IE} gives the factor by which the costs must be increased to account for interest and escalation during construction and other indirect costs. Using the standardized guideline given in Ref. 68, $f_{IE} = 1.73$, which for $\text{ROI} = 0.15/\text{yr}$, and for operating and maintenance costs of $\text{O\&M} = 0.02/\text{yr}$, the annual pay rate amounts to $0.29/p_f$. To this is added the annual rate at which payment is made for FW/B replacement, which is called out separately in Eq. (10).

The algorithm described in Ref. 3 for the dependence of the plant factor on I_w is used, wherein 28 days/year are given to scheduled FW/B maintenance if the first-wall chronological life, $(I_w\tau)/I_w$, exceeds one year; the annual maintenance time is increased above 28 days/year in proportion to $p_f I_w/(I_w\tau)$ if the FW/B

must be replaced more frequently than once a year. This procedure along with the FW/B replacement cost gives the major economic disincentives from high I_w values. The following expression gives the above-described dependence of p_f on I_w :

$$p_f = \begin{cases} 0.76 & \text{if } I_w/(I_w\tau) < 1.32 \text{ yr}^{-1} \\ \frac{0.835}{1 + 0.0707 I_w/(I_w\tau)} & \text{if } I_w/(I_w\tau) > 1.32 \text{ yr}^{-1} \end{cases} \quad (11)$$

Before Eqs. (9), (10), and (11) can be evaluated, typical values for the composite costs, c_{FPC} (M\$/m³), c_{FW} (M\$/m²), or c'_{FPC} (\$/kg) must be chosen. Table II.C-I gives in three parts a summary of physics, economics, and FPC parameters for the STARFIRE³ and Culham MkIIB tokamak⁶⁹, the CRFPR,¹⁵ and the tandem-mirror MARS^{5,6} reactor designs. The composite costs for each of these designs are summarized as part of Table I.C-IC.

Equations (9), (10), and (11) have been evaluated on Fig. II.C-3 using the composite FPC unit costs (37 \$/kg or 0.20 M\$/m³) listed for the CRFPR in Ref. 15 and Table II.C-IB. For all cases, the recirculating power fraction was fixed at $\epsilon = 0.15$, an assumption that must be examined by a detailed systems code.¹⁵ For the case with longer first-wall lifetimes [$(I_w\tau) = 10\text{--}15 \text{ MWyr/m}^2$], a shallow cost minimum occurs at $I_w \approx 20 \text{ MW/m}^2$, this minimum shifting to low first-wall loadings as $(I_w\tau)$ is decreased. The shape of this minimum and the shift is a result of the p_f algorithm described by Eq. (11), which discriminates against FPC replacements more frequently than once a year. The dot-dashed curve in Fig. II.C-3 shows a case similar to the STARFIRE design³ as well as the effects of increasing the unit FPC costs from the 19-\$/kg value given in Ref. 3 (Table II.C-IB) to the 37-\$/kg values used for the CRFPR (i.e., f_{FWB} increases from 0.05 to 0.10 and c_{FW} increases from 0.66 M\$/m² to 1.29 M\$/m²). It should be noted that such an increase in c'_{FPC} (M\$/kg) for STARFIRE may not be justified since the massive shield required to protect the superconducting magnets is a low-cost item, probably justifying a lower FPC unit cost compared to the CRFPR.

TABLE II.C-IA
PLASMA PHYSICS/ENGINEERING PARAMETERS

PARAMETERS	STARFIRE ³	MkIIB ⁶⁹	MARS ^{5,6}	CRFPR
Major toroidal radius, $R_T(m)$	7.0	6.7	131 ^(a)	3.8
Aspect ratio, A	3.6	3.5	NA	5.3
Plasma elongation, κ	1.6	1.75	NA	1.0
Plasma triangularity, d	0.5	0.	NA	0.
Average plasma minor radius, $r_p(m)$	2.38	2.51	0.49	0.71
Plasma volume, $V_p(m^3)$	781.	836.	98.8	37.8
Average beta, $\langle\beta\rangle$	0.067	0.092	0.28	0.12 ^(b)
Magnetic field at plasma, $B_0(T)$	5.8	4.0	4.7	0.40 ^(c)
Safety factor at limiter, q_a	5.1	2.5	NA	0.02
Plasma toroidal current, $I_\phi(MA)$	10.1	10.2	NA	18.4
Plasma current density, $I_\phi/\pi r_p^2(MA/m^2)$	0.54	0.51	NA	11.8
Average electron temperature, $T_e(keV)$	17.3	12.0	24.0	10.0
Average ion temperature, $T_i(keV)$	24.1	12.0	28.0	10.0
Average electron density, $n_e(10^{20}/m^3)$	0.81	1.50	3.3	6.55
Average fusion power, $P_f(MW)$	3510.	2992.	2600.	2732.0
Average plasma power density, P_f/V_p	4.49	3.60	26.3	72.5
Average neutron FW loading, $I_w(MW/m^2)$	3.6	3.2	4.3	19.5
Burn-time/off-time	∞	20.	∞	∞

(a) Central-cell length.

(b) Poloidal beta, $\beta_\theta = 0.23$.

(c) Toroidal field at plasma edge, toroidal field on-axis is 9.5 T, and poloidal field at plasma edge is 5.2 T.

For the FW/B design life of 15 MWyr/m^2 , lower-cost systems at higher first-wall loadings are in principle possible for STARFIRE if the engineering and physics constraints would allow the increased βB^2 while maintaining the total power constant. The difficulties in both plasma and magnet performance encountered when attempting to access high values of I_w and P_{TH}/V_{FPC} for otherwise constant-power STARFIRE-like systems are better illustrated by the following example. Since the net electrical power is given by $P_E = (2\pi)^2(M_N + 1/4)\eta_p A I_w r_w^2$ (re: typical parameters given in Table II.C-I), an increase from 3.6 MW/m^2 for STARFIRE to 20 MW/m^2 requires r_w to be decreased from 2.83 m to 1.20 m, keeping $A = R_T/r_w$ and P_E constant. Since the blanket/shield thickness cannot be decreased (actually, Δb must be increased

TABLE II.C-1B
FUSION-POWER-CORE (FPC) PERFORMANCE COMPARISONS(a)

PARAMETER	STARFIRE ³	MkIIB ⁶⁹	MARS ^{5,6}	CRFPR ^(e)
Gross thermal power, P_{TH} (MWt)	4000	3261	3400	3365
Blanket energy multiplication, M_N	1.14	1.14	1.36	1.28
Thermal conversion efficiency, η_{TH}	0.36	0.37	0.427(0.343)	0.365
Recirculating power fraction, ϵ	0.1857	0.08	0.22	0.185
Plant efficiency, $\eta_p = \eta_{TH}(1-\epsilon)$	0.30	0.34	0.33	0.30
Net electrical power, P_E (MWe)	1200.	1200.	1202.	1000.
Nominal B/S thickness, Δb (m)	2.5		0.84	0.60
Nominal coil thickness, δ (m)	1.6	{3.2	1.62	0.60
FPC volume, V_{FPC} (m ³)	8110(6630)	8000(4401)	11645.	285
First-wall area, A_{FW} (m ²)	780	716	494	112.
FPC volume/surface, V_{FPC}/A_{FW}	10.4(8.50)	11.2(6.15)	23.6	2.55
FPC cost (M\$)	440.1/363.3	719.1[473.9]	481.	45.6
• FW/B	82.4	204.5[13.50]	54.(a)	14.8
• Shield	186.1/109.3	137.2[90.3]	56.	---
• Coils	171.6	377.4[248.6]	371.	30.8
FPC unit cost, c_{FPC} (\$/kg)	19.0/22.0	41.5[27.3]	20.6	39.5
FPC volumetric cost, c_{FPC} (M\$/m ³)	0.053/0.059	0.16[0.11]	0.041	0.15
FPC area cost, c_{FW} (M\$/m ²)	0.66/0.51	1.00[0.66]	0.97	0.39
Cost figures of merit				
• RPE/TDC	0.56	0.72	0.64	0.36
• FPC/TDC	0.26/0.21	0.23	0.27	0.06
• (FW/B)/TDC	0.050	0.067	0.030	0.017
System minor radius, $r_s = [V_{FPC}/2\pi^2 R_T]^{1/2}$ (m)	7.66(6.70)	7.78(5.77)	4.2	1.95
Plasma chamber volume, V_{PC} (m ³)	1106(950)	970(836)	148.	42.
First-wall radius, r_w (m)	2.83	2.71	0.60	0.75
FW neutron loading, I_w (MW/m ²)	3.6	3.2	4.3	19.5
Power density, P_{TH}/V_{FPC} (MWt/m ³)	0.50(0.66)	0.41(0.74)	0.29	11.8
FPC mass, M_{FPC} (tonne)	23174/16496	17330	23308	1105
• FW/B	1574	4700	194(3185)(b)	45(845)(b)
• Shield	13360/6682	3650	2980(724)(d)	189
• Coils	8240	8980	8509(3496)(d)	870(c)
Specific mass, M_{FPC}/A_{FW} (tonne/m ²)	29.7/21.2	24.2	47.2	9.9
Mass utilization M_{FPC}/P_{TH} (tonne/MWt)	5.7/4.1	5.3	6.8	0.33
FPC density, M_{FPC}/V_{FPC} (tonne/m ³)	2.86/2.49	2.17(3.94)	2.0	3.9

(a) Values in () based on toroidal volume, otherwise volume of central column included. Values to right of / do not include vacuum-pumping ducts and ports. Values in [] give \$/£ conversion in 1977 followed by \$ inflation from 1977 to 1980; otherwise the conversion/inflation order is reversed.

(b) Drained (undrained).

(c) 72.8-tonne TFCs, 394-tonne OHC, 404-tonne EFC.

(d) Central cell (end plug).

(e) Cost figures based on Ref. 15 analysis.

TABLE II.C-1C

COST COMPARISON (NORMALIZED TO TDC) (1980 Dollars)

ACCOUNT	STARFIRE ³	MkIIB ⁶⁹	MARS ^{5, 6}	CRFPR
20. Land and Land Rights	0.19	--	0.21	0.34
21. Structure and Site Facilities	20.09	12.48	10.59	26.07
22. Reactor Plant Equipment (RPE)	56.00	72.04	64.07	53.37
22.1.1 First-Wall/Blanket (FW/B)	4.77	6.66	2.33	1.54
22.1.2 Shield (S)	10.78	4.47	2.46	--
22.1.3 Coil (C)	9.90	12.30	16.06	3.20
FPC = FW/B + S + C	25.46	23.43	20.85	4.74
23. Turbine Plant Equipment	14.47	10.88	11.65	23.15
24. Electric Plant Equipment	6.77	3.29	6.78	12.62
25. Miscellaneous Plant Equipment	2.37	1.27	1.41	4.36
26. Special Materials	0.014	--	5.26	0.026
90. Total Direct Costs (TDC)	100.	100.	100.	100.
99. Total Costs	185.23	200.26	174.12	173.00
Unit Direct Cost, UDC(\$/kWe)	1439	2556. [1685] ^(a)	1480. ^(b)	959.
Cost of Electricity, COE(mills/kWe)	67.1	--	50. ^(b)	46.2
Net Electric Power, P _E (MWe)	1200	1200	1202	1000

(a) Value in bracket gives \$/£ conversion in 1977 followed by \$ inflation from 1977 to 1980; otherwise the conversion/inflation order is reversed.

(b) Based on 1966 \$/kWe and 67 mills/kWeh in 1983 dollars and a 10 % per year deflation factor.

somewhat to hold the same radiation/heat flux of the superconducting magnets), the STARFIRE design moves farther from the optimum power density as $x = r_w/(\Delta b + \delta)$ decreases from 0.69 to 0.29 [$x = 1$ maximizes $(P_{TH}/V_{FPC})/I_w$ or A_{FW}/V_{FPC} for a fixed M_N , Eq. (3) and Fig. II.A-3]. Since $I_w \approx 0.48 (\beta B^2)^{1/2} r_w$ and $I_w r_w^2$ is held constant, then $\beta B^2 \propto I_w^{3/4}$. Hence, for the same on-axis field, presuming the coils are already at a peak field of 11-12 T, the $\beta \propto I_w^{3/4}$ scaling dictates that beta would have to increase by a factor of 3.62 to $\beta \approx 0.24$ compared to the design value of 0.067; for any realistic pressure profile, an average beta of > 0.24 would result in a nearly unity beta on axis. Nevertheless, given that such improved plasma performance were possible, the

Fig. II.C-3. Dependence of COE as UDC on I_w for a range of first-wall lifetimes and for various FPC costs indicated. Also shown are the plant factors used to compute COE, P_f having a major influence on COE.

system power density would be increased in proportion to $I_w x / (1 + x)^2$, which gives a factor of 3.9, leading to $P_{TH}/V_{FPC} \approx 2.0 \text{ MW/m}^3$ for STARFIRE. Although such increases are important, significant increases in system power density are achievable also by reducing $\Delta b + \delta$, pointing toward a need for confinement systems that can operate efficiently (i.e., $\epsilon < 0.15-0.20$) with normal copper magnets.

The compact, high-power-density region is technically available to RFPs even for betas far below the $\beta_0 = 0.2$ values used here. For this reason that region on Fig. II.C-2 where $I_w = 10-20 \text{ MW/m}^2$ and $r_p = 0.6-0.8 \text{ m}$ appears as most interesting from the viewpoint of economic fusion power. The physics needed to achieve plasmas in this region for the recirculating power fraction assumed for resistive-coil systems (i.e., $\Delta b + \delta \approx r_w \approx 0.7-1.0$) are largely available to the RFP configuration.

Lastly, it is noted that although little cost penalty is indicated if I_w closer to 10 MW/m^2 rather than 20 MW/m^2 is selected, if $\rho_{\text{FPC}} \approx 5 \text{ tonne/m}^3$, then $I_w \leq 20 \text{ MW/m}^3$ would be required to maintain the total FPC mass below ~ 1000 tonne; the high range of first-wall neutron loadings may be desirable from a block maintenance viewpoint, which in turn has economic implication not directly reflected by the costing models. These tradeoffs between the increased I_w , reduced mean-time-to-fail, reduced FPC mass, and reduced mean-time-to-repair remain a topic of future study. The reduction in plant factor, p_f , as I_w is increased is shown in Fig. II.C-3 for the simple algorithm previously described. Clearly, the above-mentioned tradeoffs as well as a more realistic means to model p_f deserve considerably more attention, as does the dependence of $(I_w \tau)$ on I_w . Section IV.C. describes the results of a more-comprehensive systems model designed specifically to examine these tradeoffs for the RFP.

D. The Reversed-Field Pinch

1. Confinement Principle and Application to Reactor Studies. The RFP is a toroidal axisymmetric device in which the primary confinement field, B_θ , is poloidal and is generated by a toroidal current, I_ϕ , flowing in the plasma.^{33,35} The RFP plasma supports a toroidal bias field, B_ϕ , to stabilize sausage ($m = 0$) and elliptical ($m = 2$) distortions. Grossly unstable MHD modes with wavelengths longer than the minor radius, r_w , of an electrically conducting shell are stabilized by the shell on a short time scale and by feedback coils for longer times. If the toroidal bias field is slightly reversed near the plasma edge, $r_p \lesssim r_w$, the resulting magnetic shear in the plasma-edge region is sufficient to stabilize local pressure-driven and current-driven instabilities, as specified by the Mercier criterion.³³ This stabilization occurs at relatively high values of the normalized plasma pressure, $\beta = 2nk_B T / (B^2 / 2\mu_0)$. A sample stable RFP profile is illustrated in Fig. II.D-1, which also gives a comparison with a tokamak.

The mere existence of the RFP profiles shown in Fig. II.D-1 would seem unlikely because of the probable annihilation of opposing toroidal flux at the field reversal surface. Experiments during the previous 25 years have shown,^{33,35} however, that a self-reversed field and a minimum-energy state are generated even if such a field is not externally imposed. A theory⁷⁰ of relaxed energy states has led to a substantial increase in the fundamental appreciation of this near-minimum-energy, field-reversed state. Given any arbitrary dissipation mechanism, the Taylor theory predicts that a plasma surrounded by a flux-conserving shell will relax to a minimum-energy, force-free state. The key descriptive parameters in the Taylor theory are the pinch parameter, θ , and the reversal parameter, F , which are defined as $\theta = B_\theta(r_w) / \langle B_\phi \rangle$ and $F = B_\phi(r_w) / \langle B_\phi \rangle$, where $\langle B_\phi \rangle = (2/r_w^2) \int_0^{r_w} B_\phi r dr$ is the average toroidal field within the conducting shell of radius, r_w . Appendix A gives a more detailed description of the Taylor minimum-energy state and the relationship between profiles, the parameters θ and F , and RFP burn physics.

The locus of minimum-energy states, as described in an F - θ phase space, is shown in Fig. II.D-2; both the analytic ($\beta = 0$) Taylor state and the experimental, finite- β states are shown. The experimental F - θ traces illustrated in Fig. II.D-2 show the tendency of the plasma to drift toward and reside within a specific region of F - θ space. This desired RFP state corresponds to $F < 0$ and $1.2 < \theta < 1.6$. Finite- β RFP states have been observed

Fig. II.D-1. Sample magnetic-field and $q = (B_\phi/B_\theta)(r_p/R_T)$ minor radial profiles for the RFP and the tokamak.

both experimentally^{44-46, 71-72} and numerically⁷³ for higher values of θ , although the Taylor theory predicts an ultimate relaxation to the minimum-energy states shown in Fig. II.D-2 and Appendix A. Both the relaxation mechanism and associated time constants for the self-sustained toroidal-field reversal are not well understood in terms of fundamental plasma processes in spite of the strong experimental evidence for the existence of a plasma regeneration or "dynamo" mechanism that continually maintains the minimum-energy RFP state. Generally,⁷³⁻⁷⁶ either turbulence or resistive MHD instabilities drive a plasma dynamo action, wherein toroidal plasma currents are converted to the toroidal flux needed for maintenance of the toroidal-field reversal. For the purposes of RFP reactor studies,^{15-16, 31} an efficient dynamo is enforced onto the plasma burn models both during startup and burn sustenance (Sec. III.G.) by requiring the F- θ constraint (Fig. II.D-2). Evidence for nearly classical resistivity in

Fig. II.D-2. The Taylor F - θ diagram showing two experimental traces and the tendency for the plasma to seek and reside within the RFP minimum-energy state.

RFP plasmas exists,⁷⁷ giving a strong indication of an efficient plasma dynamo action. Unlike the tokamak, the close electrical coupling between the poloidal and toroidal circuits through the RFP plasma vis a vis the F - θ diagram. This coupling also provides a means to drive toroidal current noninductively⁷⁸⁻⁸¹ at low frequency (~ 50 Hz for the reactor, Sec. III.K.), preliminary experimental evidence⁶⁹ in support of these ideas recently being obtained.

The relationship between F and θ , the tokamak safety factor, $q \equiv (r_p/R_T)(B_\phi/B_\theta)$, and beta points out the essential differences between the RFP and the tokamak reactor. First, one definition of the total average beta for both RFPs and tokamaks is $\langle \beta \rangle = 2\mu_0 \langle p \rangle / (B_\theta^2 + B_\phi^2)$, which in terms of the poloidal beta, β_θ , is $\langle \beta \rangle = \beta_\theta / [1 + (B_\phi/B_\theta)^2] = \beta_\theta / [1 + (F/\theta)^2]$. The tokamak-like minimum-energy state would correspond to the region where $F \rightarrow 1$ and $\theta = F/Aq \rightarrow 1/Aq$, where $A = R_T/r_p$ is the plasma aspect ratio; for the tokamak, $\langle \beta \rangle = \beta_\theta / [1 + (qA)^2]$. It is noted that the spheromak state corresponds to $F \rightarrow 0$

on the F - θ diagram. For the RFP state, $|F/\theta| \approx 0.2/1.5 = 0.13$ and $\langle\beta\rangle \approx \beta_\theta$, whereas for the tokamak $F/\theta = qA \approx 8-10$, with $\langle\beta\rangle$ being much less than $\beta_\theta \approx 1-2$. As a maximum for the tokamak, $\beta_\theta \leq A$ to avoid the ideal kink stability and, therefore, $\langle\beta\rangle \leq A/[1 + (Aq)^2] \approx 1/Aq^2$. The impact of these basic differences on the level of ohmic heating allowed in resistive coils for systems that can operate stably with low values of $|F/\theta|$, compared to those having large $|F/\theta|$ values (i.e., the tokamak), is shown in Ref. 15. Specifically, the ohmic losses incurred in the toroidal-field coils relative to those in the poloidal-coil system for both RFPs and tokamaks are nominally proportional to $\sim 1 + |F/\theta|$. In addition, lower ohmic losses occur in the RFP poloidal coils because of the higher aspect ratio and better inductive coupling between the coil set and plasma. Efficient use of resistive copper coils becomes much more a practical matter for the RFP compared to the tokamak.

Application of the F - θ constraint to the reactor infers the existence of a plasma dynamo; the crucial issue of enhanced plasma transport associated with the RFP dynamo remains. A transport-based confinement time scaling is not yet available for RFPs. By equating ohmic heating in the plasma, ηj^2 , to an energy loss rate of unspecified mechanism, $3nk_B T/\tau_E$, an "ohmic" scaling results, $\tau_E(\text{OHMIC}) \propto \beta_\theta T^{3/2} r_p^2 / Z_{\text{eff}}$, when the plasma resistivity, η , is assumed to be classical and pressure balance is invoked. Figure II.D-3 compares this ohmic scaling with a number of key RFP experiments. The effects of flat and $J_0(\mu r)$ temperature profile are shown, where the $\beta = 0$ Taylor theory gives $n(r)T(r) \propto J_0^2(\mu r)$ and $J_0(\mu r)$ is the tenth-order Bessel function of the first kind (Appendix A, Sec. A.4.). It is noted that the centerline plasma temperature, $T(0)$, is used in Fig. II.D-3 rather than the density-weighted average temperature, T , commonly used in the reactor burn simulations (Sec. III.G.). An expression for $\tau_E(\text{OHMIC})$ used to generate the constant- T curve is also shown. The weak dependence of the coefficient $\tau_E(\text{OHMIC})/(\beta_\theta T(0)^{3/2} r_p^2 / Z_{\text{EFF}})$ on Z_{EFF} is indicated on Fig. II.D-3, a nominal beta of $\beta_\theta \approx 0.2$ being used to show this dependence. Whatever the actual transport mechanism, that process is effectively assumed to limit the beta to a specific value. If the $T(r) \propto J_0(\mu r)$ profiles are used, the expression given in Fig. II.D-3 for $\tau_E(\text{OHMIC})$ is reduced by $\sim 17.6(1 - \beta_\theta)/(2 - \beta_\theta) \approx 7-8$. The previously reported CRFPR design points¹⁵ are also shown on Fig. II.D-3. Generally, the close agreement between experiment and "theory" is taken as an

Fig. II.D-3. Comparison of experimental confinement times from a number of RFP devices with $\tau_E(\text{OHMIC})$, the latter being obtained by equating ohmic-heating power density to transport losses, using pressure balance, and assuming stability-limited constant beta. The expression given for $\tau_E(\text{OHMIC})$ pertains to a flat temperature profile, the $J_0(\mu r)$ temperature profile case being reduced by a factor of $\sim 17.6(1 - \beta_\theta)/(2 - \beta_\theta) \approx 7-8$.

indication that the plasma dynamo action maintaining the RFP profiles requires little energy beyond that dissipated by a nearly classical plasma resistivity.

Finally, a more direct, but empirical, expression of the scaling of confinement time emerging from small, ohmically heated experiments is desired. It is recalled that the combination of pressure balance [$T \propto \beta_\theta I_\phi(I_\phi/N)$], plasma energy balance ($nT/\tau_E \propto \eta j^2$), and classical resistivity ($\eta \propto 1/T^{3/2}$) predicts that $\tau_E/r_p^2 \propto \beta_\theta^{5/2}(I_\phi/N)^{3/2}I_\phi^{3/2}$. Figure II.D-4 illustrates this scaling from present experimental results to compact RFP reactor projections. The reactor burn simulations given in Sec. III.G. utilize a scaling of this form, as

calibrated with existing experimental results using the more pessimistic $\tau_E \approx 0.05 I_\phi r_p^2 f(\beta_\theta)$ scaling curve.

In summary, the basic conclusions emerging from RFP experiment and the implications for reactor projection are given below.

- Classical plasma resistivity is observed in experiment, the higher voltages required to drive current in RFPs relative to tokamaks being a result of geometric factors (i.e., higher pitch) rather than "anomalous" resistivity need to drive current against added $\vec{v} \times \vec{B}$ electric fields being generated by local, stochastic plasma motion.
- The plasma dynamo action is verified but not theoretically understood, with the dynamo dissipating little energy beyond that required by classical ohmic losses.
- Separate oscillation of poloidal and toroidal circuits result in the plasma moving predictably along the F- θ diagram, giving strong promise for "F- θ pumping" current drive. F- θ pumping for steady-state, ignited current drive should be efficient if the plasma dynamo action occurs with a nearly classical electrical resistivity.
- Ignition by ohmic heating is consistent with classical plasma resistivity and is a strong possibility in the RFP.
- The energy confinement time, $\tau_E(\text{OPT})$, required for an economically optimized reactor relative to an ohmic dissipation time, $\tau_E(\text{OHMIC})$, and relative to some measure of Alcator scaling, $\tau_E(\text{ALC})$, is given by $\tau_E(\text{OHMIC})/\tau_E(\text{OPT}) > 20-60$ and $\tau_E(\text{ALC})/\tau_E(\text{OPT}) > 5-10$, respectively, showing wide safety margins for ohmic ignition in RFPs.

Lastly, the reactor implications of the $q < 1$ kFP confinement system are summarized below.

- Relatively free choice of plasma aspect ratio, R_T/r_p .
- Economically high betas.

Fig. II.D-4. Scaling of RFP confinement with toroidal current needed to project present experimental results to reactor conditions.

- Possibility of high values of βB^2 at the plasma and correspondingly increased plasma power density for a given field at coil.
- Internal plasma currents are sufficient for ohmic heating to ignition without auxiliary heating and with low-to-moderate fields at the coils.
- Efficient plasma/coil electrical coupling results in
 - B_θ dominates low PFC fields and currents.
 - B_ϕ near zero, low TFC fields and currents.
 - Elimination of superconducting coils in favor of resistive coils is possible, while maintaining efficient reactor performance.

- Potential for efficient steady-state current drive through modest oscillations of TFC and PFC voltages ("F- θ pumping"). With the possibility of reducing the OHC current to zero and with the inherently low TFC currents, a reactor configuration results in which external currents are flowing only in the EFCs.

2. Reactor Design-Point Update and Sensitivity. A unified parametric systems model was used to examine a fully cost-optimized RFP reactor design.¹⁵ A 1000-MWe(net) base case was selected and subjected to a parametric analysis that varied:

- plasma transport, τ_E .
- beta, β_0 .
- blanket/shield thickness, Δb .
- plasma density and temperature profiles.
- normal versus superconducting coils.
- DT versus catalyzed-DD fuel.
- net electric power, P_E (MWe).
- first-wall/blanket radiation lifetime, $I_w \tau$ (MWyr/m²).

The plasma transport scaling was varied to give a design point that minimized the cost of electricity; the resulting value of confinement time, τ_E (OPT), for a DT-fueled system amounted to $\sim 1/8$ the prediction of empirical (Alcator) tokamak transport. Table II.D-I lists parameters for both the DT and catalyzed-DD versions of the designs reported in Ref. 15. Table II.D-I also includes a "degraded" DD/CRFPR design that would operate with an average first-wall thermal flux equal to that predicted for a fully cost-optimized DT/CRFPR design. These results and associated discussions and interpretations have been presented in Ref. 15. The related assessment of engineering technology for the DT/CRFPR focused onto the following four major technological issues:

- High-heat-flux first walls ($4\text{--}5\text{ MW/m}^2$) similar to other MFE requirements, sputtering/erosion and particle control being main concern and unknown.
- High-power-density (30 MW/m^3 average, 200 MW/m^3 peak) breeding blanket similar to LWR core and may preclude solid breeders, self-cooled liquid-metal blankets appearing particularly attractive.
- High-radiation-flux resistive magnets positioned outside a thin tritium-breeding/heat-recovering blanket.
- Long-pulsed versus steady-state operation a "soft" issue from viewpoint of energy balance, technology, and cost, this issue being dominated by unresolved means for
 - impurity control (full-wall poloidal pumped limiters or a magnetic divertor)
 - steady-state current drive (F- θ pumping).

Table II.D-II summarizes in more detail³⁷ the major issues and problems envisaged for compact fusion reactors, with an emphasis being placed here on the DT/CRFPR.

The DT/CRFPR design point reported in Ref. 15 and Table II.D-I has since been modified as a result of a subsequent conceptual engineering study performed on key FPC systems. Engineering design studies that form the basis for this design-point readjustment are reported in Sec. III. Major changes include increasing the blanket and shield thickness from $\Delta b = 0.4\text{ m}$ to 0.6 m and an increase in blanket energy multiplication from the $M_N = 1.1$ value assumed in Ref. 15 to 1.3 computed for the $\Delta b = 0.5\text{-m-thick}$ PbLi blanket (Sec. III.B.). Table II.D-III gives the updated parameters for the DT-fueled CRFPR; generally, the increased losses and reduced power density accompanying an increased Δb is compensated by the increased M_N ; the revised CRFPR design, therefore, represents a small perturbation from that originally reported in Ref. 15.

The revised, fully-optimized design point reported in Table II.D-III has been subjected to further parametric sensitivity study wherein both the economy of scale and the influence of assumed FW/B lifetime was investigated. Figure II.D-5 compares this reactor cross section with that for STARFIRE and a PWR, whereas Fig. II.D-6 gives the economy of scale for the Table II.D-III design point, comparisons with the STARFIRE³ and EBTR⁵² designs also being shown. An economy-of-scale curve was determined⁵² also for EBTR and is included on Fig. II.D-6, emphasizing, however, that the neoclassical EBT transport used

in the Ref. 52 study did not admit to designs with small plant capacity at any cost.

The dependence of COE on assumed FW/B lifetime and plasma beta for the DT/CRFPR design given on Table II.D-III is depicted on Fig. II.D-7. The $I_w \tau = 15 \text{ MWyr/m}^2$ ($I_w \approx 19.5 \text{ MW/m}^2$) design point can operate with a factor of ~ 2 reduction in FW/B lifetime (and first-wall neutron loading) without large increases in COE; the degraded $I_w \approx 8\text{--}10 \text{ MW/m}^2$ system, however, requires a FPC mass that increases in mass by 1240 to ~ 2200 tonnes, which is still a considerable reduction compared to the more-conventional superconducting approaches (re: Table II.C-I). The ability to utilize "block" (single-piece) maintenance approaches, however, is compromised by the more-massive FPC designs. The effect of decreased beta from the $\beta_0 = 0.2$ design value on COE is also depicted on Fig. II.D-7, showing that decreases by over a factor of two are possible without serious increases in cost. The decreased β_0 is compensated by increased I_ϕ and β_0 , maintaining an economic value of $\beta_0 B_0^2$ at a cost of increased coil losses but not overstressing the coils.

Given credible extensions of physics and engineering needed to achieve the kind of compactness represented by the design suggested in Table II.D-III, the key question that remains is "can the system total reliability, breakdown frequency, repair/maintenance time, and operating cost (i.e., FPC mass throughput) be designed within reasonable capital cost to provide a total plant factor that gives a competitive COE?" This report begins to establish a basis for answering this important question, although significant advances in theoretical and experimental understanding will be needed to assess fully this issue. The following Sec. III. gives preliminary results of a more-detailed computational basis with which to assess the potential for extending both physics and engineering to achieve the kind of compact fusion suggested in Table II.D-III. Only better models based on actual operating experience, however, will provide a definitive answer to the last question; the material presented in Sec. III. is one step toward answering this crucial question. Modifications to the base-case parameters summarized in Table II.D-III will occur as more design realism is injected into this study; Sec. III.L. performs an energy, thermal-hydraulic, and mechanical integration of the FPC based on the models and results reported in other subsections in Sec. III. The comprehensive design table given in Appendix B reflects key power-plant parameters that have been subjected to this kind of re-evaluation and integration.

TABLE II.D-I

PARAMETER SUMMARY FOR INTERIM 1000-MWe CRFPR DESIGNS (Ref. 15)

	FULLY OPTIMIZED		DEGRADED
	DT(a)	DD(a)	DD(b)
First-wall radius, r_w (m)	0.75	0.60	0.62
Major radius, R_T (m)	4.3	4.4	14.9
Minor system radius, r_s (m)	1.6	2.1	2.32
Toroidal-coil mass (tonne)	159	403	2430
Poloidal-coil mass (tonne)	729	1960	7860
First-wall/blanket mass (tonne)	356	304	1060
Mass utilization, M/P_{TH} (tonne/MWt)	0.37	0.70	3.0
Plasma temperature, T(keV)	20.0(10.0)	35.0(28.0)	28.0
Plasma density, $n(10^{20}/m^3)$	3.4(6.7)	13.0(16.3)	7.9
Energy confinement time, τ_E (s)	0.23	1.8(1.5)	3.2
Alcator coefficient, $\tau_E/nr_p^2(10^{-21} \text{ s m})$	1.37(0.76)	4.3(2.85)	11.0
Toroidal plasma current, I_ϕ (MA)	18.5	36.8	27.4
Poloidal field at plasma, B_θ (T)	5.2	13.0	9.4
Poloidal-coil field, $B_{\theta c}$ (T)	2.6	4.4	2.9
Initial toroidal-coil field, $B_{\phi 0}$ (T)	3.3	8.3	6.0
Poloidal-coil energy, $W_{B\theta}$ (GJ)	1.11	6.2	12.0
Toroidal-coil energy, $W_{B\phi}$ (GJ)	0.54	3.0	6.4
Total thermal power, P_{TH} (MWt)	3350	3820	3820
Engineering power density, P_{TH}/V_c (MW/m ³)	15.0	10.0	2.4
Recirculating power fraction, $\epsilon = 1/Q_E$	0.147	0.25	0.25
Ohmic Q-value, $Q_T = P_{TH}/P_{OHM}$ (c)	37.1(28.8)	17.8(15.6)	15.8
Neutron wall loading, I_w (MW/m ²)	19.5	10.6	3.0
Unit total cost, UTC(\$/kWe)	1490	1810	2605
Cost of electricity, COE (mills/kWeh)	40.7	47.2	67.2

(a) $T(r) \propto \text{CONST}$ ($T(r) \propto J_o(\mu r)$).(b) Power density of DD/CRFPR was degraded until the first-wall surface heat flux was equal to the fully optimized DT/CRFPR (4.87 MW/m²).(c) P_{OHM} includes ohmic power to both plasma and TFC/PFC sets.

TABLE II.D-II
COMPACT FUSION REACTOR ISSUES/PROBLEMS

- FW heat flux and sputtering rates
 - heat fluxes similar for other fusion systems (i.e., neutral-beam grids and dumps, limiters, rf tubes)
 - integrated sputtering same as other fusion approaches
 - less tolerance for peaking factors
- FW/B burnup rate
 - replacement frequency greater
 - burnup rate similar to other approaches (200-300 tonne/yr)
- FW plasma stabilization and active feedback
 - ZT-40M conducting shell disappears on a time scale that is short compared to plasma discharge time
 - passive role of FW/B as a shell similar to tokamak
 - slow-feedback requirement similar to tokamak
 - both passive shell and active feedback requirements not well understood
- Long-pulsed versus steady-state operation
 - no energy-balance problem as long as burn time exceeds field energy replacement time (> 1 s)
 - F- θ pumping unique RFP option for steady-state current drive operating at low frequency (50-60 Hz)
 - both poloidal pumped limiters and toroidal magnetic divertors are impurity-control options
- Confinement time magnitude and scaling
 - experimental τ_E dictated by need to shed ohmic-heating power with classical resistivity at a beta limit
 - $\tau_E \propto I_p r_p^2$ takes ZT-40M results to ignition
 - Ohmic-heating scaling predicts $\tau_E \propto \beta_0 T^{3/2} r_p^2 \propto \beta_0 I^{3/2} r_p^2$
 - detailed knowledge of τ_E scaling is not necessary to predict an economic reactor with $\tau_E(\text{OPT}) \approx \tau_E(\text{ALC})/8$ and $\tau_E(\text{OPT}) \approx \tau_E(\text{OHMIC})/50$.
- Startup power, magnetic flux requirement, and startup FW heat loads
 - reactor would begin with a low-current RFP and slowly ramp current to maintain startup power $\lesssim 100$ -200 MWe
 - use dynamo action to build up B_ϕ through PFC circuit to minimize an already small TFC set
 - startup from grid may be possible (> 200 MWe)
 - FW heat load during startup will always be less than during burn period
- Disruptions and current terminations
 - present evidence indicates current termination caused by edge-plasma density starvation
 - controllable by edge refueling

Fig. II.D-5. Cross-section comparison between CRFPR, STARFIRE, and a PWR.

Fig. II.D-6. Economy of scale for CRFPR design point given in Table II.D-III, showing comparison with the STARFIRE tokamak³ and EBTR.⁵²

Fig. II.D-7. Dependence of the Table II.D-III design point in the assumed first-wall lifetime.

TABLE II.D-IIIA

KEY PHYSICS AND ENGINEERING PARAMETERS FOR THE $P_E = 1000\text{-MW}_e$,
MINIMUM-COE CASES GIVEN IN TABLE II.D-IA UPDATED FOR MORE REALISTIC ENGINEERING DESIGN

	PLASMA PARAMETERS	REF. 15 DESIGN	UPDATE ^(a)
Minor plasma radius (m)		0.71	0.71
Major plasma radius (m)		4.30	3.79
Plasma aspect ratio		6.06	5.37
Plasma current (MA)		18.5	18.4
Toroidal current density (MA/m ²)		11.7	11.8
Plasma density (10 ²⁰ /m ³)		3.37(6.74)	3.39(6.56)
Plasma temperature (keV)		20.0(10.0)	20.0(10.0)
Lawson parameter (10 ²⁰ s/m ³)		0.79(1.57)	0.79(1.51)
Energy confinement time (s)		0.23	0.23
Poloidal beta		0.20	0.20
Theta parameter		1.45	1.45
Reversal parameter		-0.20	-0.20
Plasma/first-wall radius ratio		0.95	0.95
Plasma Ohmic dissipation during burn (MW)		2.59(28.6)	2.29(25.3)
	<u>POLOIDAL-FIELD QUANTITIES</u>		
Coil thickness (m)		0.37	0.36
Average minor radius of coil (m)		1.44	1.62
Mass of coil (tonne)		729.	703.
Magnetic-field level at the coil (T)		2.58	2.28
Magnetic-field level at the plasma surface (T)		5.21	5.22
Poloidal-coil current (MA)		18.7	22.4
Poloidal-current density (MA/m ²)		5.54	6.06
Maximum energy stored in coil (MJ)		1113.	1111.
Ohmic dissipation during burn (MW)		72.0	83.0
	<u>TOROIDAL-FIELD QUANTITIES</u>		
Coil thickness (m)		0.10	0.09
Average minor radius of coil (m)		1.20	1.39
Mass of coil (tonne)		159.	149.
Initial toroidal bias field (T)		3.33	3.34
Reversed toroidal field during the burn (T)		0.68	0.68
Maximum energy stored in the coil (MJ)		539.	642.
Toroidal current density (MA/m ²)		5.54	6.06
Ohmic dissipation during burn (MW)		15.71	17.61
	<u>ENGINEERING SUMMARY</u>		
Ohmic Q-value		37.11(28.8)	32.92(27.5)
Total thermal power (MWt)		3350.(3450.)	3389.(3460.)
14.1-MeV neutron loading (MW/m ²)		19.5(20.)	19.6(20.)
14.1-MeV blanket multiplication		1.10	1.30
First-wall radius (m)		0.75	0.75
Minor radius of system (m)		1.62	1.80
Fusion-power-core mass (tonne)		1243.	1368.
System power density (MWt/m ³)		15.00	14.00
Mass utilization (tonne/MWt)		0.37	0.40
Blanket thickness (m)		0.40	0.60
Mass of first wall/blanket (tonne)		355.	516.
Average blanket power density (MWt/m ³)		51.92	36.1

(a) Based on flat plasma temperature profile, values in parentheses correspond to $J_0(\mu r)$ temperature profiles.

TABLE II.D-III B

COSTING SUMMARY FOR THE $P_E = 1000\text{-MWe}$ MINIMUM-COE CASES
GIVEN TABLE III.D-I UPDATED FOR MORE REALISTIC ENGINEERING DESIGN

ACCOUNT NUMBER	ACCOUNT TITLE	MILLION DOLLARS(1980)	
		REF.15 DESIGN	UPDATE
20.	Land and Land Rights	3.3	3.3
21.	Structures and Site Facilities	167.	250.(a)
22.	Reactor Plant Equipment	311.	320.
23.	Turbine Plant Equipment	220.	222.
24.	Electric Plant Equipment	121.	121.
25.	Miscellaneous Plant Equipment	41.8	41.8
26.	Special Materials	0.25	0.25
90.	Direct Cost	863.	959.
91.	Construction Facilities, Equipment, and Services (10%)	86.3	95.9
92.	Engineering and Construction Management Services (8%)	69.1	76.7
93.	Other Costs (5%)	43.2	48.0
94.	Interest During Construction (10%/yr)	267.	296.
95.	Escalation During Construction (5%/yr)	165.	183.
99.	Total Cost	1493.	1658.
<hr/>			
	Thermal power (MWt)	3350.	3389.
	Gross electric power (MWe)	1172.	1186.
	Net electric power (MWe)	1000.	1000.
	Engineering Q-value	6.80	6.38
	Plant factor	0.76	0.76
	Unit base cost (\$/kWe)	1062.	1180.
	Unit total cost (\$/kWe)	1493.	1658.
	Unit direct cost (\$/kWe)	863.	959.
	Capital return 15% (mills/kWeh)	33.7	37.4
	Operating 2% (mills/kWeh)	4.08	4.53
	Replacement (mills/kWeh)	2.90(b)	4.24(b)
	Power cost (mills/kWeh)	40.7	46.2
	Construction time (yr)	5.0	5.0
	Interest	0.251	0.251
	Escalation	0.155	0.155

(a) The algorithm used is Ref. 15 for the reactor building size was based on the torus size and underestimated the total reactor building size (steam generators, pumps, tritium cleanup, lay-down areas, etc.). Based on scaling from the STARFIRE design³ and LWR experience, a fixed volume of 120,000 m³ is added to the reactor hall volume as previously calculated to give the volume of the reactor building. The design is not of sufficient detail to allow a scaling of the reactor building size with total power, but the volume used conservatively applies to a 1000-MWe(net) system.

(b) Most reactor designs include replacement cost as part of the above 2 % operating cost.

III. PRELIMINARY ENGINEERING DESIGN

Although considerable insight developed from past and ongoing studies has been applied to establish realistic engineering constraints for the parametric systems analysis leading to the CRFPR design-point update given in Table II.D-III, it nevertheless becomes necessary to perform specific conceptual engineering design studies on key fusion-power-core (FPC) subsystems in order to advance the design credibility. The approach adopted for this study emphasizes FPC integration and, therefore, develops models for each FPC subsystem used to meet this goal. After presentation of a design overview in Sec. III.A., the FW/B/S/C neutronics model and results in Sec. III.B., and a materials overview in Sec. III.C., the following FPC subsystem design models and results are given:

- First Wall (Sec. III.D.)
- Blanket (Sec. III.E.)
- Magnets (Sec. III.F.)
- Plasma and Circuit Simulation (Sec. III.G.)
- Limiters (Sec. III.H.)
- Magnetic Divertors (Sec. III.I.)
- Vacuum (Sec. III.J.)
- Current Drive (Sec. III.K.)
- Fusion-Power-Core Integration (Sec. III.L.).

A. Design Overview

The Compact Reversed-Field Pinch Reactor (CRFPR) study has focused completely on the physics and technology needs of the fusion power core (FPC) for a nominal 1000-MWe(net) power plant. This toroidal reactor is based on a deuterium-tritium fuel cycle. Major features of this design are steady-state and ignited operation, heating to ignition by ohmic dissipation of intrinsic plasma currents, pumped-limiter impurity control, pressurized-water cooling of the high-heat-flux copper-alloy first-wall and limiter systems, self-cooled lead-lithium $Pb_{83}Li_{17}$ (referred to hereafter as "PbLi") blanket using ferritic steel (HT-9) structure, water-cooled copper coils positioned outside the blanket/shield system, and fully remote maintenance of a single-piece, ~ 300-tonne, first-wall/blanket/shield/toroidal-field-coil assembly.

Figure III.A-1 gives a cross-sectional view of the FPC, showing that this 1000-MWe(net) system is not much larger than Tokamak Fusion Test Reactor (TFTR)³⁶ and requires an energy confinement time that differs little from 1-MA TFTR operation (0.25 - 0.30 s). An isometric sketch of one of 24 toroidal sections is shown in Fig. III.A-2. Each of these toroidal sectors would be fabricated, assembled into the 300-tonne torus, and tested (electrically, under vacuum, and thermal-hydraulically) off-site, prior to shipment to and installation at the operating power-plant site. The high neutron first-wall loading of 20 MW/m^2 would give a one-year chronological life for a radiation lifetime of 15 MWyr/m^2 , which for the 45.2-tonne first-wall/blanket systems corresponds to a mass usage of 17.9 kg/MWtyr ($\sim 20,000 \text{ MWtd/tonne}$, somewhat less than fissile-fuel burnup in an LWR) for this 3365-MWt plant at a 75 % plant

Fig. III.A-1. Cross-sectional view of the 1000-MWe(net) CRFPR compared to TFTR³⁶ (poloidal-field coils not shown).

factor. Table III.A-I summarizes the major CRFPR design parameters, which are presented in more detail in Appendix B. These parameters reflect the results of design guidelines that targeted the CRFPR at system power densities ($\sim 11.8 \text{ MW/m}^3$) and physical sizes (0.33 tonne/MWt, 285 m^3) at which pressurized-water (fission) reactors (PWRs) presently operate; considerable flexibility exists for systems of either reduced power density or reduced plant capacity (and neutron first-wall loading) while maintaining favorable energy cost projections (Sec. IV.C.). The cost projections are summarized in Table III.A-II, which also gives comparisons with other fusion systems on a relatively common basis. The design approach taken for the CRFPR allowed by the unique RFP physics principles projects a (relative) cost advantage. More

Fig. III.A-2. Isometric view of one of 24 toroidal sections for a 1000-MWe(net) CRFPR. Off-site, single-unit construction of the first-wall/blanket/shield/toroidal-field-coil FPC (~ 300 tonne total without coolants) and single-piece maintenance/repair scheme is envisaged for this high-power-density design.

TABLE III.A-I

CRFPR MAJOR DESIGN PARAMETERS

Net electrical power (MW)	1000.
Gross electrical power (MW)	1227.
Total thermal power (MW)	3365.
Gross power-conversion efficiency (%)	36.5
Overall plant availability (%)	75.
Major radius (m)	3.8
Plasma radius (average)(m)	0.71
Plasma volume (m ³)	37.8
Number of toroidal sectors	24.
Maximum field at magnet (T) ^(a)	4.5
Field at plasma axis (T)	9.5
Field at plasma edge (T)	5.2
Average poloidal beta	0.23
Average total beta	0.12
Average DT ion density (10 ²⁰ /m ³)	6.6
Average DT ion temperature (keV)	10.0
Plasma burn mode	Continuous/ignited
Plasma heating method (startup)	Ohmic (246 Wb)
Plasma impurity-control method	Pumped limiter
First-wall/limiter structural materials	MZC copper alloy
Blanket/shield structural material	HT-9 ferritic steel
Neutron wall loading (MW/m ²)	20.
Tritium-breeding medium	PbLi
Primary coolant	PbLi
Thermal conversion method	Dual-cycle, steam

^(a)During burn, 9.2 T during startup, OHC.

importantly, however, is the promise of a smaller fusion system that couples to real physics uncertainties more loosely than to the overall cost equation for fusion power; a more robust and resilient design results that is capable of early and cost-effective proof of fiscal and technical risk.

TABLE III.A-II

COST COMPARISON (NORMALIZED TO TDC) (1980 Dollars)

<u>ACCOUNT</u>	<u>STARFIRE</u> ³	<u>MkII B</u> ^{6,9}	<u>MARS</u> ^{5,6}	<u>CRFPR</u>
20. Land and Land Rights	0.19	--	0.21	0.34
21. Structure and Site	20.09	12.48	10.59	26.07
22. Reactor Plant Equipment (RPE)	56.00	72.04	64.06	33.37
22.1.1. First-Wall/Blanket (FW/B)	4.77	6.66	2.33	1.54
22.1.2. Shield (S)	10.78	4.47	2.46	--
22.1.3. Coil (C)	9.90	12.30	16.06	3.20
FPC = FW/B + S + C	25.48	23.43	20.85	4.74
23. Turbine Plant Equipment	14.47	10.88	11.45	23.15
24. Electric Plant Equipment	6.77	3.29	6.78	12.62
25. Miscellaneous Plant Equipment	2.37	1.27	1.41	4.36
26. Special Materials	0.014	--	5.29	0.026
90. Total Direct Costs (TDC)	100.	100.	100.	100.
99. Total Costs	185.20	200.26	123.50	173.00
Unit Direct Cost, UDC(\$/kWe)	1439	2556[1685] ^(a)	1480. ^(b)	959
Cost of Electricity, COE(mills/kWeh)	67.0	--	50. ^(b)	46.2
Net Electric Power, P _E (MWe)	1200	1200	1202	1000

(a) Value in bracket gives \$/£ conversion in 1977 followed by \$ inflation from 1977 to 1980; otherwise the conversion/inflation order is reversed. Based on 1966 \$/kWe and 65 mills/kWeh in 1983 advising a 10 % per year deflation factor.

(b) Based on 1966 \$/kWe and 67 mills/kWeh in 1983 dollars and a 10 % per year deflation factor.

The CRFPR design differs considerably from superconducting fusion reactors. The projected technology requirements correspondingly differ primarily because of:

- Increased plasma power density, which is proportional to $\beta^2 B^4$, where B is the confining magnetic field at the plasma and β is the ratio of average plasma pressure to magnetic-field pressure at the plasma surface.
- Increased first-wall neutron current (15-20 MW/m²) and surface heat flux (4-5 MW/m², maximum, for uniform heat deposition onto the first wall).
- Increased peak (≥ 200 MW/m³) and average (≥ 30 MW/m³) power density within a tritium-breeding blanket.
- Increased radiation and heat fluxes at resistive magnet coils in systems designed to operate at most with only a thin heat-recovering/tritium-breeding blanket placed between the coil and the plasma.

A summary of the key technology needs for the CRFPR is given in Sec. IV. This summary is presented according to the three major FPC subdivisions: Plasma Engineering Systems (heating, particle control, etc.), Nuclear Systems (first wall, blanket, shield), and Magnet Systems. In addition, Tritium Systems and Electrical/Mechanical Systems represent key elements of the reactor, which at the level of this study have not received detailed attention. A number of the entries in the technology assessment given in Sec. IV. have been established from analyses performed in other, related studies. Compact reactors generally would operate with somewhat increased plasma densities. Refueling, impurity control, and ash removal requirements, therefore, may be more demanding. The higher plasma density may also lead to more-difficult rf current-drive requirements for steady-state operation. The potential for low-frequency "F- θ pumping"⁷⁸⁻⁸¹ that is unique to the RFP (and spheromak) confinement, however, represents a new and potentially attractive means to drive steady-state plasma currents using the RFP dynamo action to sustain this unique, minimum-energy magnetic configuration. The first-wall specific power loads for compact reactors are higher than projected for other MFE systems, which also leads to higher blanket power densities. The primary difference in magnet technology required of the CRFPR is reflected by the use of lower-field, copper-alloy coils that store considerably less total energy than the high-field superconducting coils envisaged for most other approaches.

The requirements for the Plasma Engineering Systems do not significantly differ between long-pulsed and steady-state operation except possibly for ash removal and impurity control; fueling should be similar for a 30- to 100- s burn as for a truly steady-state burn, but the latter mode may require a magnetic

divertor for ash removal and impurity control. Because of the higher first-wall thermal loadings, a heat-flux-concentrating limiter is not possible for the compact systems, and a sizable portion ($\sim 40\%$) of the first wall will have to serve the limiter function if a divertor is not used. The particle load and associated sputtering problem for these limiters do not differ from that for the lower-power-density systems, however. A potentially more-difficult safety requirement for the DT-fueled compact systems is related primarily to the need for more-reliable off-power cooling capability because of the higher afterheat power density in the FW/B, this enhanced afterheat power density resulting from the higher overall operating blanket power density. The radwaste associated with the FW/B will be generated in more concentrated form, although the total radwaste generation will be the same for all systems for the same materials and full-power exposures. Maintenance of acceptable tritium-breeding margins in the thin, high-power-density blankets presents a greater design challenge for the compact system, in that competition for this valuable "real estate" by vacuum ducts and coolant breeders/manifolds becomes more crucial. Because of the significant reductions in physical size and mass, the maintenance procedure envisaged for the compact reactor can consider "block" maintenance, wherein the complete FPC is removed for maintenance and repair operations external to the reactor cavity, with a more rapid replacement by a fresh, pretested unit promising shorter downtimes and more reliable restarts.

B. Neutronics

The starting point for the assessment of nuclear systems is the results of neutronics computations. These calculations are based on a scaled layout of the 1000-MWe(net) DT/CRFPR design and the corresponding key physics and engineering parameters reported in Ref. 15, as summarized in Sec. II.D.2. and Table II.D-III. The initial neutronics parameter studies were made using this one-dimensional reactor model to perform a preliminary assessment of materials and thermal-hydraulic needs. Specifically, the effects of varying the blanket thickness and material composition were examined. Following this parameter survey, a "canonical" neutronics model for the first wall, blanket, shield, and coils is defined. This study emphasized the minimum blanket thickness within the constraints of efficient heat recovery and tritium breeding. All shielding functions for the exoblanke coils were provided by the "blanket," although a thin, nonbreeding outer region was eventually identified as a shield operating at or near the blanket temperature.

The primary goals of this study were to examine key engineering considerations for key FPC subsystems, to generate and test models for these subsystems, to provide a preliminary integration of those subsystems, and generally to construct a framework for a future, more-comprehensive conceptual design. In a sense, this study begins and ends with the neutronics analysis. The FPC design integration has been made on the basis of one-dimensional neutronics calculations reported in this section. The multidimensional nature of the FPC design that emerged from this study will require minor design modifications and iteration. Preliminary, two-dimensional neutronics sensitivity studies are reported in Appendix C, and these suggested changes will serve as a point of departure for future work.

1. Calculational Procedure. Neutronics calculations were performed using the one-dimensional ONEDANT discrete-ordinates transport code⁸² in the S_8P_3 approximation. The XSLIBA multigroup, coupled cross-section set (30 neutron and 12 gamma-ray groups) was used. This library for 35 elements and isotopes was derived using ENDF/B-IV data.⁸³ Data for kerma factors, dpa, and H and He production were retrieved from the KERMA8 file. Activation cross sections were prepared from data contained in the GAMMON activation library.⁸⁴ An infinite cylinder model was used; all input and output quantities are normalized to a unit length of major circumference. Definitions of key quantities used in the

neutronics parametrics study are given below; the quantity P_{XX} is a linear heating rate (MW/m).

P_{FW}, P_{SW}, P_{SLD} = linear heating rate in first wall, second wall, and shield

P_{BLK} = linear heating rate in blanket

P_{TFC}, P_{PFC} = linear heating rate in toroidal-field and poloidal-field coils, $P_{FC} = P_{TFC} + P_{PFC}$

M_N = blanket energy multiplication, $(P_{FW} + P_{SW} + P_{BLK} + P_{SLD})/P_N$

P_N = fusion neutron power incident on the first wall
(91.89 MW/m for $I_w = 19.5$ MW/m²)

ϵ_B = blanket efficiency, defined as $M_N P_N / (M_N P_N + P_{FC} + P_{LOSS})$, where P_{LOSS} assumed to be zero

TBR = tritium-breeding ratio.

Figure III.B-1 displays the energy flow in the FW/B/C systems; interpretations of quantities adopted as measures of the blanket performance are also given.

Fig. III.B-1. First-wall/blanket (FW/B) energy flows and efficiency parameters. The thin outboard shield eventually added to the FW/B system is not shown.

2. Computational Results

a. Parametric Studies. The material compositions and reference geometry used for the parametric studies are shown in Fig. III.B-2. All calculations are normalized to the design first-wall loading (19.5 MW/m^2). The $\text{Pb}_{83}\text{Li}_{17}$ eutectic^{85,86} (PbLi) in the blanket consists of ^6Li enrichment at 60%.

The effect of varying blanket thickness on selected neutronics parameters was first determined. The shield thickness (Fig. III.B-2) was fixed at 5 mm; a blanket composed of 90 v/o PbLi and 10 v/o primary candidate alloy stainless steel (PCASS) was assumed. Although the neutronics results used in this study are based on PCASS, more-recent studies^{5,87} indicate corrosion in PbLi may severely limit the operating temperature, interfacial temperatures as low as 500°C being set by a $\sim 1\text{-}\mu\text{m/yr}$ limit on corrosion rate. At present HT-9 ferritic alloy may be preferred. The PCASS alloy, nevertheless, is retained for the purposes of the neutronics study.

Results are tabulated in Table III.B-I, with selected results being plotted in Fig. III.B-3. It is seen that M_N , ϵ_B , and TBR increase as the blanket thickness is increased and, as expected, P_{TFC}^N and P_{PFC}^N decrease as the blanket is thickened. The blanket efficiency is limited to about $\epsilon_B \approx 0.94$ for the configuration examined unless thicker blankets and the attendant decrease in

Fig. III.B-2. CRFPR neutronics model showing linear power flows and a more-detailed array of key regions.

TABLE III.B-I

EFFECT OF VARYING BLANKET THICKNESS ON
CRFPR NEUTRONICS PARAMETERS^(a)

Blanket thickness, $\Delta b_{BLK}(m)$	0.3	0.4	0.5	0.6
Power on first wall, $P_N(MW/m)$	91.89	91.89	91.89	91.89
Total power, $P_{BLK}(MW/m)$	130.07	127.48	125.50	124.06
Power in coils, $P_{TFC}^N + P_{PFC}^N(MW/m)$	24.37	16.19	10.68	6.97
Blanket energy multiplication, M_N	1.15	1.21	1.25	1.27
Blanket efficiency, ϵ_B	0.813	0.873	0.915	0.944
Tritium-breeding ratio, TBR	0.920	1.036	1.120	1.180
First-wall nuclear heating				
• Total, P_{FW}	20.74	20.90	20.96	20.98
• Neutron	7.60	7.64	7.66	7.66
• Gamma-ray	13.14	13.26	13.30	13.32
Toroidal-coil nuclear heating				
• Total, P_{TFC}^N	14.95	10.09	6.77	4.48
• Neutron	1.61	1.00	0.62	0.38
• Gamma-ray	13.34	9.09	6.15	4.10
Poloidal-coil nuclear heating				
• Total, P_{PFC}^N	9.42	6.10	3.91	2.48
• Neutron	0.51	0.30	0.17	0.10
• Gamma-ray	8.91	5.80	3.74	2.38
Maximum dpa/yr in copper				
• TFC	26.00	15.1	8.75	5.07
• PFC	4.96	2.73	1.51	0.84
Maximum He appm/yr in copper				
• TFC	21.10	6.83	2.24	0.73
• PFC	3.44	1.13	0.37	0.12
Maximum H appm/yr in copper				
• TFC	99.9	36.70	13.70	5.16
• PFC	15.50	5.57	2.02	0.75

(a) Blanket is 90 v/o PbLi(60% 6Li) + 10 v/o PCASS, with the shield thickness fixed at 5 mm.

Fig. III.B-3. Effect of varying PbLi blanket thickness on energy multiplication, M_N , tritium-breeding ratio, TBR, blanket efficiency, ϵ_B , coil heating, and coil radiation responses.

system power density are adopted. This tradeoff is further studied; an increased shield thickness to ~ 100 mm increases ϵ_B to 0.985.

The ONEDANT transport calculations were next made for a 0.5-m-thick blanket with shield thicknesses ranging from 5 to 125 mm; a 90/10 PbLi/PCASS mixture was again specified for the blanket. These results are plotted in Fig. III.B-4 and summarized in Table III.B-II. Also shown in Table III.B-II are the results for an 80/20 PbLi/PCASS with increased shield thicknesses. The variations of M_N , ϵ_B , and TBR are not dramatic for the range of shield thickness examined, but P_{TFC}^N and P_{PFC}^N vary within factors of 2 to 4. Comparing results for the 90/10

TABLE III.B-II

EFFECT OF VARYING SHIELD THICKNESS ON NEUTRONICS PARAMETERS
FOR A $\Delta b_{BLK} = 0.5$ -m BLANKET WITH 90/10 PbLi/PCASS.^(a)

Shield Thickness, Δb_{SLD} (mm)	5	25	50	75	125
P_{FW} (MW/m)	20.96	20.96 (21.17)	20.96	20.96 (21.16)	20.96
P_{SW} (MW/m)	4.08	4.08 (4.12)	4.08	4.08 (4.12)	4.08
P_{BLK} (MW/m)	89.56	89.51 (95.77)	89.58	89.65 (95.92)	89.73
P_{SLD} (MW/m)	0.23	1.22 (1.08)	2.57	3.97 (3.50)	6.62
P_{TFC}^N (MW/m)	6.77	6.50 (5.63)	5.82	4.98 (4.24)	3.22
P_{PFC}^N (MW/m)	3.92	3.25 (2.68)	2.53	1.93 (1.57)	1.04
M_N	1.25	1.26 (1.33)	1.28	1.29 (1.36)	1.32
ϵ_B	0.915	0.922 (0.936)	0.934	0.945 (0.955)	0.966
TBR	1.120	1.122 (1.029)	1.125	1.128 (1.034)	1.130

^(a)First-wall neutron loading $I_w = 19.5$ MW/m², results for 80/20 PbLi/PCASS blanket are shown in parentheses.

Fig. III.B-4. Effect on key measures of blanket performance on increased third-wall shield thickness for a fixed blanket thickness of $\Delta b = 0.5$ m.

and 80/20 PbLi/PCASS blankets shows that M_N and ϵ_B are higher for the 80/20 case, but the breeding ratio is $\sim 10\%$ lower.

The results reported to this point used a 5-mm-thick shield material composed of 90 v/o PCASS and 7.26 v/o water (10 v/o water at 0.726 g/cm^3). If the shield is made more absorbent of neutrons, the blanket efficiency, ϵ_B , would increase and the coil heating rates would decrease. A 0.1-m-thick third wall consisting of varying proportions of tungsten, boron carbide, PCASS, and water coolant, therefore, was considered. In addition, the 90/10 PbLi/PCASS blanket used previously was replaced by a structurally more optimal 95/5 ratio. Calculational results, assuming a homogeneous distribution of these materials, are shown in Table III.B-III. The results indicate a blanket efficiency of $\epsilon_B \approx 0.98$ for the W/B₄C and W shield cases. The breeding ratio, however, is lower than that for the 90 v/o PCASS configuration.

b. The Canonical Blanket. On the basis of parametric studies described above, a "canonical" FW/B/S/C design was adopted as a starting point for further calculations of this thin-blanket/copper-coil concept. The material and geometric specifications for this design are shown in Table III.B-IV and Fig. III.B-5. The important features of the canonical FPC neutronics design are a) a 0.5-m-thick blanket with 95/5 PbLi/PCASS and b) a 0.1-m-thick shield composed of 25-mm-thick alternating layers of B_4C and tungsten metal. Water coolant was provided for this region, although flowing PbLi coolant is also possible. Thicknesses and material compositions of the other regions are those used in the previous studies. Key results for this canonical blanket are tabulated in Table III.B-V.

Fig. III.B-5. Canonical FPC neutronics model based on an infinite cylinder geometry. Shield materials: Region A - $B_4C/SS/H_2O$; Region B - W/SS/H₂O.

Table III.B-VI lists the maximum and average volumetric heating rates and the maximum (annual) neutron fluences (> 0.1 MeV). The heating rate increases from 4.1 to 17.7 MW/m³ across the blanket/shield interface. For the shield/TFC interface, the heating rate decreases from 6.6 to 1.9 MW/m³.

Quantitative estimates were made for the transmutation of copper to nickel and zinc in the first wall and coils. The reactions of interest and the half-lives of the radioactive products are listed below and summarized in Fig. III.B-6.

Nickel-producing reactions:

Zinc-producing reactions:

Assuming a one-year irradiation time and using the appropriate production rates and decay constants, the concentration buildup of nickel and zinc in the first wall and coils can be estimated. It is convenient to express the transmutation densities as fractions of the copper atom densities in the target material. Results of these calculations are summarized in Table III.B-VII. Table III.B-VIII gives the production of ^{63}Ni and ^{60}Co from activation of FW, TFC, and PFC copper after one year of continuous irradiation for $I_w = 19.5$ MW/m².

TABLE III.B-III

EFFECT OF VARYING SHIELD MATERIALS FOR A $\Delta b_{\text{SLD}} = 100\text{-mm-THICK SHIELD}$
AND A $\Delta b_{\text{BLK}} = 0.5\text{-mm-THICK BLANKET WITH } 90 \text{ v/o PbLi and } 5 \text{ v/o PCASS.}^{(a)}$

THIRD-WALL MATERIAL	40% W + 40% B ₄ C + 10% PCASS	80% W + 10% B ₄ C	90% W	90% PCASS
P _{FW} (MW/m)	20.81	20.82	20.82	20.82
P _{SW} (MW/m)	4.07	4.07	4.08	4.08
P _{BLK} (MW/m)	86.72	87.32	87.60	89.34
P _{SLD} (MW/m)	6.21	8.25	9.31	5.78
P _{TFC} ^N (MW/m)	1.16	1.63	1.93	4.38
P _{PFC} ^N (MW/m)	0.59	0.75	0.85	1.64
P _{TOT} (MW/m)	119.56	122.84	124.59	126.04
M _N	1.282	1.311	1.326	1.306
ϵ_B	0.985	0.981	0.978	0.952
TBR	1.11	1.13	1.13	1.18
Maximum dpa/yr				
• TFC	1.180	1.450	1.620	2.890
• PFC	0.024	0.226	0.245	0.492
Maximum He appm/yr				
• TFC	0.532	0.386	0.355	0.599
• PFC	0.091	0.069	0.064	0.103
Maximum H appm/yr				
• TFC	2.61	1.900	1.760	3.540
• PFC	0.429	0.324	0.302	0.551

^(a)The shield coolant is 10 v/o water at density of 0.726 g/cm³.

Table III.B-VIII gives a finer breakdown of the first-wall transmutation rate expressed per unit 14.1-MeV neutron first-wall loading. Although Zn is formed primarily by nonthreshold (n, γ) reactions, the build-in of Ni is almost equally divided between threshold and nonthreshold reactions, with the former dominating somewhat. Hence, reductions in the Ni production rate for this 20-mm-thick copper first wall by alterations in the blanket composition and shifting to a softer neutron spectrum should not be significant. It is also noted that uncertainties are associated with the ⁶⁵Cu(n, γ) cross sections.

TABLE III.B-IV
MATERIAL COMPOSITIONS FOR THE CANONICAL BLANKET MODEL

<u>PRIMARY MATERIALS</u>	<u>DENSITY</u>	<u>COMPOSITION</u>
Cu	8.96 g/cm ³	
H ₂ O	1.00 g/cm ³	
Pb ₈₃ Li ₁₇	9.40 g/cm ³	60% enriched in ⁶ Li
PCASS	7.86 g/cm ³	66.7 w/o Fe 13.7 w/o Cr 2.0 w/o Mo 15.6 w/o Ni 2.0 w/o Mn
B ₄ C	2.5 g/cm ³	
W	19.3 g/cm ³	

MIXTURES

First wall	60 v/o Cu	29 v/o H ₂ O (40 v/o, 0.726 g/cm ³)(a)
Second wall	60 v/o PCASS	29 v/o H ₂ O (40 v/o, 0.726 g/cm ³)
Blanket	95 v/o PbLi	5 v/o PCASS
Shield (case A)	80 v/o B ₄ C 10 v/o PCASS	7.26 v/o H ₂ O (10 v/o, 0.726 g/cm ³)
Shield (case B)	80 v/o W 10 v/o PCASS	7.26 v/o H ₂ O (10 v/o, 0.726 g/cm ³)
TFC and PFC coils	10 v/o PCASS 10 v/o H ₂ O	80 v/o Cu

(a) Volume percent at temperature.

Although preliminary and approximate (i.e., homogenized, one-dimensional, parametric, interpolative), the neutronic results summarized herein are sufficient to provide a good indication of FW/B/S/C radiation responses and thermohydraulic requirements. The increases needed in both $\Delta b = \Delta b_{BLK} + \Delta b_{SLD}$ (0.4 → 0.6 m) and M_N (1.1 → 1.3) represent the major adjustments made to the preliminary design point suggested earlier in Ref. 15. and Table II.D-III. Table III.B-IX summarizes the concentration of major long-lived activation for the FW, TFC, and PFC. The results summarized in Tables III.B-V through III.B-IX represent the key neutronic parameters for the canonical blanket used in subsequent analyses leading to the PFC design integration. As will be shown,

TABLE III.B-V

SUMMARY OF PARAMETERS FOR CANONICAL BLANKET MODEL^(a)
 WITH A $\Delta b_{\text{BLK}} = 0.5\text{-m-THICK BLANKET (95/5 PbLi/PCASS)}$ AND A $\Delta b_{\text{SLD}} = 0.1\text{-m-THICK SHIELD WITH ALTERNATING LAYERS OF B}_4\text{C AND TUNGSTEN}$

$P_{\text{FW}}(\text{MW/m})$	20.80
$P_{\text{SW}}(\text{MW/m})$	4.08
$P_{\text{BLK}}(\text{MW/m})$	86.45
$P_{\text{SLD}}(\text{MW/m})$	6.02
$P_{\text{TFC}}^{\text{N}}(\text{MW/m})$	1.26
$P_{\text{PFC}}^{\text{N}}(\text{MW/m})$	0.61
$P_{\text{TOT}}(\text{MW/m})$	119.22
M_{N}	1.278
ϵ_{B}	0.985
TBR	1.11
Peak dpa/yr	
• First wall	310.
• TFC	1.220
• PFC	0.208
Peak He appm/yr	
• First wall	1750.
• TFC	0.524
• PFC	0.091
Peak H appm/yr	
• First-wall	5020.
• TFC	2.580
• PFC	0.430

(a)Based on a fusion neutron first-wall loading of $I_{\text{w}} = 19.5 \text{ MW/m}^2$.

subsequent analyses should be based on two-dimensional analyses that more accurately model the effects of pumped limiters, vacuum ducts, and coolant manifolds/headers on the key blanket performance parameters (M_{N} , ϵ_{B} , and TBR for a given Δb). Extensive two-dimensional modeling, however, was not within the scope of this study, although the results given in Appendix C give a clear direction for future work and FW/B/C design options.

TABLE III.B-VI

VOLUMETRIC HEATING RATES AND NEUTRON FLUENCES
FOR STEADY-STATE OPERATION OF THE
CANONICAL BLANKET MODEL ($I_w = 19.5 \text{ MW/m}^2$)

REGION	MAXIMUM POWER DENSITY (MW/m^3)	AVERAGE POWER DENSITY (MW/m^3)	MAXIMUM FPY ^(a) NEUTRON FLUENCE (10^{27} n/m^2)
First Wall	239.0	218.0	2.1
Second Wall	173.0	168.0	2.0
Blanket	255.0	26.9	2.0
Shield	15.0	7.24	0.17
TFC	1.94	1.41	0.024
PFC	0.80	0.16	0.004

^(a)FPY = Full-power year.

A question commonly asked is the effect of a thick copper first wall on the blanket performance. To address this issue ONEDANT calculations in cylindrical geometry were made to determine tritium-breeding ratios as a function of copper first-wall thickness. The reference case (Table III.B-V) was used: 20-mm-thick first wall consisting of 60 v/o Cu and 29 v/o H_2O ; 5-mm-thick second wall contains 60 v/o PCASS and 29 v/o H_2O . Results of the calculations are given in Fig. III.B-7. The breeding ratio decreases monotonically with increasing wall thickness; the decrease is about 15% over the range of first-wall thicknesses from 0 to 20 mm. This behavior can be explained in terms of the neutron cross sections for Cu and Pb at 14 MeV. These cross sections are as follows:

	Copper	Lead
Total(barns)	3.0	5.4
Elastic	1.4	2.9
Nonelastic	1.6	2.5
(n,2n)	0.6	2.2

The (n,2n) cross section is much higher for Pb compared to Cu. Also, the (n,2n) cross section for Pb is 88 % of the nonelastic value, so that the competition from other nonelastic processes is small. The (n,2n) and nonelastic cross sections for Cu are 0.6 and 1.6 b, respectively, and the competition from other nonelastic reactions is much greater. The lead is a better neutron multiplier

TABLE III.B-VII

NICKEL AND ZINC PRODUCTION FROM NEUTRON TRANSMUTATION
OF COPPER FW AND COILS AFTER ONE FULL-POWER YEAR ($I_w = 19.5 \text{ MW/m}^2$)

	<u>FIRST WALL</u>	<u>TFC</u>	<u>PFC</u>
Average Ni/Cu	$4.77(10)^{-2}$	$1.79(10)^{-4}$	$0.18(10)^{-4}$
Maximum Ni/Cu	$5.52(10)^{-2}$	$2.24(10)^{-4}$	$0.99(10)^{-4}$
Average Zn/Cu	$2.63(10)^{-2}$	$0.18(10)^{-4}$	$0.18(10)^{-4}$

TABLE III.B-VIII

FIRST-WALL TRANSMUTATION RATES EXPRESSED IN UNITS OF ATOMIC % PER
YEAR PER MW/m^2 OF 14.1-MeV NEUTRONS

Average Ni/Cu	0.2448
^{64}Ni from $^{63}\text{Cu}(n, \gamma)$	0.1097
^{60}Ni from $^{63}\text{Cu}(n, \alpha)$	0.0004
^{62}Ni from $^{63}\text{Cu}(n, 2n)$	0.0743
^{64}Ni from $^{65}\text{Cu}(n, 2n)$	0.0373
^{62}Ni from $^{65}\text{Cu}(n, \alpha)$	0.0025
^{63}Ni from $^{63}\text{Cu}(n, p)$	0.0206
Average Zn/Cu	0.1350
^{64}Zn from $^{63}\text{Cu}(n, \gamma)$	0.0735
^{64}Zn from $^{65}\text{Cu}(n, 2n)$	0.0246
^{65}Zn from $^{65}\text{Cu}(n, \gamma)$	0.0369
Average (Ni + Zn)/Cu	0.3798

than Cu at 14 MeV, causing the response shown in Fig. III.B-7. Several other cases were run to show that the water in the first and second walls is not responsible for the observed behavior; these cases are summarized in Table III.B-X. On the basis of these results, a clear incentive exists to operate with thinner copper first walls, particularly as breeding becomes difficult for more-realistic blanket designs (Sec. III.L.3., Appendix C.).

Fig. III.B-6. Copper activation chains (isotopes in boxes are stable).

TABLE III.B-IX
 ^{63}Ni AND ^{60}Co PRODUCTION FROM NEUTRON ACTIVATION OF COPPER (^{63}Cu)
 AFTER ON FULL-POWER YEAR ($I_w = 19.5 \text{ MW/m}^2$)

CONCENTRATION	FIRST WALL	TFC	PFC
Average $^{63}\text{Ni}/\text{Cu}$	$4.02(10)^{-3}$	$1.18(10)^{-6}$	$6.68(10)^{-8}$
Maximum $^{63}\text{Ni}/\text{Cu}$	$4.72(10)^{-3}$	$2.39(10)^{-6}$	$4.00(10)^{-7}$
Average $^{60}\text{Co}/\text{Cu}$	$1.07(10)^{-3}$	$1.96(10)^{-7}$	$1.17(10)^{-8}$
Maximum $^{60}\text{Co}/\text{Cu}$	$1.30(10)^{-3}$	$3.94(10)^{-7}$	$6.89(10)^{-8}$
Average $^{63}\text{Ni}/^{60}\text{Co}$	3.76	6.02	5.71
Maximum $^{63}\text{Ni}/^{60}\text{Co}$	3.631	6.07	5.81

Fig. III.B-7. Effect of copper first-wall thickness on tritium-breeding ratio for the canonical design summarized in Table. III.B-V. The reference first-wall thickness is 20 mm.

TABLE III.B-X

EFFECT OF COPPER FIRST-WALL THICKNESSES AND COOLANT-WATER FRACTION ON CRFPR BREEDING RATIOS

First-Wall Thickness (mm)	Case 1	Case 2	Case 3	Case 4	Case 5
0	1.308	-	-	-	-
5	1.276	-	-	-	-
10	1.299	1.238	1.231	1.238	1.269
15	1.171	-	-	-	-
20	1.108(a)	1.181	1.120	1.192	1.169

(a) Canonical blanket design

- Case 1. Canonical blanket model (Table III.B-V)
- Case 2. Water removed from first wall
- Case 3. Water removed from second wall
- Case 4. Water removed from first and second walls
- Case 5. Second wall replaced by void.

C. Materials Issues

This section summarizes the considerations used to select candidate first-wall (FW), blanket (B), shield (S), and coil (C) materials. An overview of material requirements, thermal-mechanical constraints for the FW/B materials selection, and a synopsis of anticipated radiation effects are given.

1. Overview. The interdependence between plasma physics/engineering, reactor design, and materials science/engineering needed to achieve economic, commercially attractive fusion power has been highlighted by a number of overview papers dealing with first walls,⁸⁸ blankets,⁸⁹ materials needs for specific devices,^{90,91} the world-wide materials programs addressing these needs.^{92,93} The degree to which material performance requirements are altered by the needs of compact fusion reactors has been addressed recently^{20,94} as have the material needs for copper coils operating in a strong radiation field.⁹⁵ Given acceptable plasma physics and confinement geometry, the viability of an economic compact fusion reactor will be determined by the achievable FPC engineered lifetime as measured both in terms of real time (i.e., maintenance interval and period) and radiation fluence (i.e., total amount of energy generated per mass of FPC consumed). The essential elements of this crucial question are summarized in Table III.C-I and center on a materials theme. Four major determinants of FPC lifetime are identified. By application of similar design and failure criteria to all fusion approaches and assumption of negligible rate effects of radiation in changing materials properties, the FPC lifetime determinants for compact systems can be reduced from four to two: reactor operations and component geometry (size).

The major change in reactor operating conditions for the higher-power-density options is the increased heat/particle fluxes; designing to the same failure criteria, however, should eliminate these differences, albeit potentially at a higher cost. The increased flexibility of reactor operations afforded by smaller FPCs, particularly with respect to the last point in Table III.C-I listed under component geometry, potentially can offset the added cost of designing for a more highly stressed reactor operating condition in order to assure that each unit mass of FPC delivers the economically necessary amount of energy within its lifetime. This potential for reduced mean-time-to-failure coupled with a potentially reduced mean-time-to-repair, both combining to give acceptable or even improved plant availability factors, is highly specific to system design (size, complexity, component geometry, etc.) and

TABLE III.C-I

SUMMARY OF FPC LIFETIME DETERMINANTS

- Reactor Operating Conditions
 - first-wall neutron loading
 - volumetric heating
 - damage rates (dpa/yr, He appm/yr, H appm/yr, burnup)
 - plasma energy rejection
 - particle fluxes to in-vacuum components (DT, neutrals, He, impurities)
 - heat fluxes (conduction and radiation)
 - duty cycle
 - coolant (kind and temperature/pressure)
- Material Properties
 - thermal (heat capacity, conductivity, expansivity)
 - mechanical (Young's modulus, ultimate and yield stresses, uniform elongation, total elongation, fracture toughness, creep, fatigue, crack growth, swelling)
 - electrical (conductivity)
 - nuclear (alloying constituents, transmutations, gas production, dpa, radioactivity, afterheat)
 - surfaces (sputtering, adsorption, gas recycle, electron emission)
- Component Geometry and Constraints
 - stress and temperature distributions
 - component interactions/interplay
 - size and degree precheck/shakedown allowed, quality assurance, replacement/repair time
- Design and Failure Criteria
 - elastic deformation and elastic instability
 - plastic deformation and plastic instability (incremental collapse/ratcheting)
 - brittle fracture
 - stress rupture/creep deformation
 - high-strain/low-cycle fatigue and creep/fatigue interaction
 - stress corrosion
 - swelling and differential volume change
 - undesirable changes in material properties (embrittlement, ductile-to-brittle transition temperature, electrical resistivity)

operation (pulsed nature, heat loads, etc.). Considerably more work is required to relate more quantitatively the COE and the system power density through plant availability and operating/maintenance costs. Generally, however, the key elements of the FPC lifetime issue (Table III.C-I) either may be common to all fusion approaches, or the impact of more severe reactor operation may be reduced by a reactor geometry (size) that is more amenable for rapid repair.

The key material issues and needs for fusion in general can be divided according to the following three FPC subsystems:

- In-vacuum Components (IVC)⁸⁸
 - first wall
 - limiter
 - divertor (channels, plates)
 - coils (feedback, current drive)
 - antennae
 - rf windows
- Blanket/Shield (B/S)⁸⁹
 - breeder
 - coolant
 - structure
 - multiplier
 - reflector/moderator
 - tritium barrier
 - ducts (rf, beams, fueling, vacuum, coolants)
- Magnet Coils (C)^{95, 96}
 - conductor (superconductor versus resistive)
 - insulator (organic versus inorganic)
 - structure
 - coolant [He(l) versus water]
 - kinds (TF, PF, OH, EF, active feedback, passive shell, current drive)

The majority of the materials input to this study, as applied to the above three major subsystems, has been taken from the previously cited literature in conjunction with the quantified needs of the CRFPR, as summarized below.

- high-heat-flux surfaces ($> 5 \text{ MW/m}^2$)
- high-power-density blanket ($> 200 \text{ MW/m}^3$)
- radiation-resistant, copper/inorganic-insulator coils ($> 5(10)^4 \text{ r/s}$)

Ongoing, unifying studies of the kind reported in Ref. 87 will prove invaluable in providing a supporting data base in this area.

2. Materials Selection

a. First Wall. The choice of FW/B materials used for the canonical blanket neutronics model described in Sec. III.B. (Fig. III.B-5) is dictated primarily by considerations of surface heat fluxes and volumetric power density. The selection of the cooling medium and the structural material for the first wall particularly is a critical step in the design. Many alternatives exist for withstanding high thermal and neutron fluxes and removing the associated heat.^{88,97-99} Subcooled water was chosen as the coolant, and a high-strength, high-conductivity copper alloy was selected as the structural material for the first wall and limiter. The MZC copper alloy¹⁰⁰ is a high-strength material with 0.06 % magnesium, 0.15 % zirconium, and 0.4 % chromium by weight. As a heat-transfer fluid, water is unequalled. The use of subcooled, high-pressure water provides an additional margin of safety before burnout conditions are reached. These factors, along with the design heat-transfer coefficients and erosion, are discussed in Ref. 101 and serve as a starting point for the present design.

Bulk radiation effects and interactions between the plasma and the first wall must be accommodated by design and FPC operating mode. For example, the transmutation of copper to nickel (Table III.B-VII) reduces the thermal conductivity of the first wall while simultaneously increasing the electrical resistivity. The effect of the changing alloy structure on first wall and coil performance is addressed later in this subsection. Additionally, the copper alloys have high radioactivity and afterheat at reactor shutdown. The activity of most copper alloys within one year is reduced to the point where the long-term radwaste problem is not severe.^{1,2} The afterheat at the first-wall and limiter, particularly for high wall loadings, must be accommodated by either passive or active auxiliary cooling in order to minimize the chances for structural damage immediately after a shutdown.

Although copper alloys are rarely considered as structural materials for fusion reactors, they have attracted recent attention^{97,98,102,103} for use in higher-power-density systems. The criteria for selecting first-wall materials have been summarized⁸⁸ and in order of priority include resistance to radiation damage and surface effects (sputter and chemical erosion), compatibility with coolant and with hydrogen isotopes, desirable mechanical and thermal properties (especially in the irradiated condition), and miscellaneous factors generally related to resource, availability, and cost. A commonly accepted method for

applying all of these criteria self-consistently to the selection process is not available, although several attempts along these lines have been made.^{98,99} Reactor system definition, design criteria, and materials requirements are mutually dependent and will be subject to change as the science and technology of fusion power systems evolves. High thermal conductivity is important in high-power-density systems to minimize the temperature gradients at high heat fluxes, thereby reducing thermal cyclic fatigue. High strength at operating temperature and resistance to creep deformation are also important.

It is not possible to determine the relative irradiation performance of copper alloys with respect to other candidate materials, which include stainless steel, vanadium, niobium, molybdenum, titanium, and aluminum alloys. The available data base summarized in Refs. 102-104 does not preclude copper alloy as a structural/heat-transfer material in fusion systems. The MZC copper alloy demonstrates all of the desired qualities in addition to being produced in commercial quantities, easily fabricated into the desired shapes, and relatively low cost. The latter items are favorable in light of the probable need for frequent replacement of fusion reactor first walls, no matter what the material, particularly if the irradiation life is substantially less than the 10-15 MWyr/m² presently assumed for the primary candidate alloy, stainless steel (PCASS). Copper alloys should be about as compatible with water, helium, and hydrogen as austenitic stainless steel.

A quantitative comparison between MZC copper alloy and other metals and alloys on a thermomechanical basis is useful to substantiate this material choice for the high-heat-flux CRFPR first wall. If the maximum temperature in the first wall or limiter is required not to exceed one-half the melting temperature, which is an optimistic criterion selected only for purposes of alloy comparison, then the maximum heat flux for the assumed conditions is only a function of the thickness, δ , between the plasma and the first coolant. The results of this analysis for several representative metals are shown in Fig. III.C-1. When compared on this basis, the MZC copper alloy is superior to most common engineering metals and alloys, reflecting a favorable combination of thermal conductivity and melting point. Molybdenum and titanium alloys are also superior by this measure, but these alloys are considerably more costly. Furthermore, molybdenum is difficult to fabricate if proper precautions are not taken. Titanium, like molybdenum, is subject to hydrogen embrittlement.

Fig. III.C-1. Heat flux for outer tube wall to achieve 50 % of the melting temperature as a function of tube-wall thickness.

A measure of the ability of a material to withstand thermal stress is given by the thermal stress parameter, M (W/m):

$$M = \frac{2\sigma_Y k(1 - \nu)}{\alpha E} = \frac{\sigma_Y}{\sigma_{TH}} I_{QW} \delta \quad (1)$$

In this expression, σ_Y is the yield strength, k is the thermal conductivity, ν is Poisson's ratio, α is the coefficient of thermal expansion, E is Young's modulus, σ_{TH} is the thermal stress, I_{QW} is the surface heat flux, and δ is the first-wall thickness. This parameter is applicable to thin-walled tubes. The

ratio σ_Y/σ_{TH} represents a structural safety factor. If the same safety factor and the same tube-wall thickness is used for all materials, then M is directly proportional to the maximum heat flux that the material can tolerate. Figure III.C-2 plots $M(\sigma_{TH} = \sigma_Y)$ and illustrates that the MZC copper alloy compares favorably with other commonly employed alloys. The superior tantalum-tungsten alloy is expected to have problems related to cost, fabrication, neutronics, and corrosion.

The satisfactory thermal-mechanical ranking of the MZC copper alloy, along with low cost and ease of fabrication when compared to more exotic competitors, led to its adoption as the candidate first-wall material for the CRFPR. Failure of the high-strength copper alloys to meet other design criteria leads to either

Fig. III.C-2. Stress parameter as a function of temperature for a range of alloys. This figure has been taken from Ref. 88 with the addition of the dotted curve for MZC copper alloy, based on properties reported in Ref. 100.

the choice of a more exotic alloy or a reduced first-wall thermal loading. Property changes related to radiation effects, including sputtering, and nuclear transmutation represent other crucial selection criteria remaining to be evaluated.

The response of IVC surfaces to high heat and particle fluxes is undoubtedly the primary engineering problem for both compact and other approaches to fusion. The partition of energy between particles versus photons, as well as between FW, limiter, and/or divertor, further defines this crucial uncertainty. The major materials questions for the IVCs are

- Removal of both surface ($< I_w/4 \text{ MW/m}^2$) and volumetric ($\sim 10I_w \text{ MW/m}^3$) heat loads within acceptable temperature, stress, pumping power, coolant pressures, and critical-heat-flux limits.
- Sputter erosion and redeposition rates for FW and limiter surfaces.
- Long-term (swelling, creep, embrittlement, alloy changes, etc.) and short-term (thermal conductivity changes, hydrogen permeation and recycle, etc.) radiation effects.

Although copper sputters at about triple the rate of PCASS, the active sputter-erosion rate depends on poorly understood edge-plasma and redeposition conditions. From the viewpoint of first-wall survivability, these problems are not unique to or more severe for the compact reactors. Aside from differences in basic plasma processes that may result when differences of $\sim 3-4$ in average plasma density are taken into account, the ratio of particle flux to neutron current incident onto a first wall from an ignited DT plasma should be similar for both compact and other systems, thereby decoupling somewhat the first-wall erosion problem from the issue of device compactness; the compact FPC simply achieves both neutron (dpa) and erosion (mm) lifetime "fluences" in an expected shorter chronological lifetime, but only after generating a similar total quantity of fusion energy for nominally a similar expenditure of first-wall/blanket mass and cost.

The long-term effects of radiation on copper alloy are not well understood either experimentally or theoretically. An estimate of the effects of neutron irradiation on a copper-alloy first wall, and possibly an inorganic electrical

insulation if first-wall coils or electrical breaks are required, has been summarized in Ref. 37 and more recently for the first-wall copper-coil insert proposed in MARS.¹⁰⁵

b. Blanket/Shield. The blanket and shield thickness for the compact reactor approaches is reduced to the minimum required for adequate tritium breeding and thermal energy recovery. The minimum-thickness (optimized) blanket/shield can also provide appreciably different options for FPC installation and maintenance schemes if the mass and volume are sufficiently reduced. Magnet shielding in the usual sense is not envisaged; instead a thin (0.10-m) outer region of the 0.5-m-thick blanket may contain a mixture of B_4C and a dense, high-Z material (i.e., steel, tungsten) operated at or near the blanket temperature (Table III.B-III).

For first-wall neutron loadings in the 15-20 MW/m² range, the local power density becomes comparable with that in the fuel of an LWR (> 200 MW/m³), with the average blanket power density also being compatible to that of an LWR core, (30-50 MW/m³). At these power densities ceramic tritium breeders cooled by pressurized helium gas or water become less attractive. Because of the low lithium inventory, reduced fire hazard, and unique combination of breeder/coolant/multiplier functions, the low-melting (235°C) lead-lithium compound $Pb_{83}Li_{17}$, referred to hereafter as "PbLi," has emerged as a popular choice for standard¹⁰⁶ and high-power-density⁸⁶ blankets. Use of a second fluid (H_2O , He) to cool a stagnant liquid-metal blanket requires a large number of high-pressure coolant tubes, making tritium breeding more difficult and reducing B/S reliability.

The self-cooled PbLi blankets, however, must design around the inevitable MHD pressure drop. Confinement systems with magnetic topologies that require liquid-metal coolant to flow long distances across strong magnetic fields may be forced either to coat coolant ducts with electrical insulators⁸⁶ or to reduce the MHD pressure drop simply by limiting the coolant flow velocity and thereby limit the first-wall neutron loading¹⁰⁶ and overall system performance. The MHD pressure drop manifests itself both in large pumping powers (> 1-2 % of thermal power removed) and the need for pressurized liquid-metal blankets (> 1-2 MPa), which in turn causes increased membrane stresses in an already corrosive and chemically reactive blanket. The high power density for the PbLi-cooled CRFPR blanket, as described in Sec. III.E., can be achieved with minimal pumping power without recourse to the use of electrically insulated coolant ducts

because of the unique, low-field poloidal topology; the blanket overpressure actually becomes a limiting factor for the CRFPR design.

The MHD pressure drop that accompanies the need for a flow velocity that is sufficient to achieve a given liquid-metal/structural metal interfacial temperature, as established for a given alloy by corrosion limits, may or may not be greater for the higher-power-density blankets; the higher coolant velocities, v , can be achieved with smaller total flow lengths, l , for either increased or decreased field, B , depending on plasma beta and confinement geometry (i.e., $\Delta P_{\text{MHD}} \propto l B^2 v$ for a given coolant duct configuration). The coupling of B/S power density, MHD pressure and pumping power, and corrosion (temperature) limits, therefore, is strongly dependent on design and concept. Furthermore, the basis upon which specific corrosion, and, hence, MHD pressure and pumping-power, limits are established for a given structural alloy requires further examination (i.e., duct wall thinning, alloy embrittlement, down-stream plugging, radioactivity transport, etc.). The materials problems related to corrosion (particularly for ceramic coatings), tritium recovery, and tritium barriers for the compact reactors remain similar to those for other systems using similar blankets. The acceleration of stress corrosion cracking by the addition of small amounts of water to these liquid-metal systems remains a particularly critical concern, however.

c. Magnets. Water-cooled copper coils located outside the thin, ~ 0.6 -m high-power-density blanket will be required to operate in a strong radiation field (Sec.III.B.). Radiation-resistant inorganic electrical insulation will be required. Either insulator coatings would be plasma-sprayed onto preformed copper conductors, or a powdered insulation (i.e., MgO or MgAl_2O_4) would be coextruded with conductor and coolant tube, the latter method being used in the fabrication of radiation-hardened coils for use in high-energy particle accelerators.^{107,108} The requirement for first-wall (feedback or current-drive) coils should be similar to the requirements envisaged for the MARS hybrid-magnet insert^{105,109} or for the less severe tokamak conditions anticipated at in-blanket equilibrium-field coils. The crucial issue of radiation damage to either exoblanket or FW coil is discussed in the following subsection.

3. Radiation Effects. The PbLi-cooled FPC design proposed for the CRFPR uses a 20-mm-thick copper-alloy first-wall and exoblanket coils. The results of neutronic computations given in Sec. III.B. based on this ~ 0.6 -m-thick canonical blanket/shield (Fig. III.B-5) can be used to assess systems that have

TABLE III.C-II

IMPLICATIONS OF RADIATION EFFECTS FOR
COMPACT REACTOR "MODEL" FW/B/C (FIG. III.B-5)

	VALUE ($I_w = 20 \text{ MW/m}^2$)
• FIRST WALL (Cu/H ₂ O)	
- 14.1-MeV neutron current, $J_w(\text{n/m}^2\text{s}) = 4.45(10)^{17} I_w$	$8.9(10)^{18}$
- Neutron flux, $\phi_w(\text{n/m}^2\text{s}) \approx 3.3(10)^{18} I_w$	$6.6(10)^{19}$
- Total FPY(a) fluence, $\phi_w \tau(\text{n/m}^2) = 1.05(10)^{26} I_w$	$2.1(10)^{27}$
- Radiation dose rate, R	
neutrons, $R_n(\text{rad/s}) = 8.2(10)^4 I_w$	$1.64(10)^6$
gammas, $R_\gamma(\text{rad/s}) = 1.3(10)^5 I_w$	$2.67(10)^6$
- Peak (average) dpa/yr $\approx 16 I_w$	318(282)
- Peak (average) He appm/yr $\approx 90 I_w$	1795(1480)
- Peak (average) H appm/yr $\approx 260 I_w$	5149(4370)
- Average transmutation rates	
Ni/Cu(%/yr) $= 0.25 I_w$	4.9
Zn/Cu(%/yr) $= 0.14 I_w$	2.7
- Heat flux, $I_Q(\text{MW/m}^2) < I_w/4$	5.0
- Average power density, $Q_w(\text{MW/m}^3) \approx 11 I_w$	224
• BLANKET/SHIELD ($\Delta b = 0.6 \text{ m}$, PbLi/PCASS/B ₄ C/W)	
- Peak power density, $Q_B(\text{MW/m}^3) = 13 I_w$	262(PbLi coolant)
- Average power density, $\langle Q_B \rangle(\text{MW/m}^3) = 1.4 I_w$	28
- Average PCASS dpa/yr $= 23 I_w$	47
- Average PCASS He appm/yr $= 78 I_w$	155
- Average PCASS H appm/yr $= 27 I_w$	533
• EXOBLANKET (TFC) COIL (Cu/PCASS/H ₂ O)	
- Peak neutron flux, $\phi_c(\text{n/m}^2\text{s}) = 4.0(10)^{16} I_w$	$7.9(10)^{17}$
- Radiation dose rate, R	
neutrons, $R_n(\text{rad/s}) = 1.3(10)^2 I_w$	$2.56(10)^3$
gammas, $R_\gamma(\text{rad/s}) = 1.1(10)^3 I_w$	$2.26(10)^4$
- Peak Cu dpa/yr $= 0.063 I_w$	1.25
- Peak Cu He appm/yr $= 0.027 I_w$	0.537
- Peak Cu H appm/yr $= 0.13 I_w$	2.65
- Peak PCASS dpa/yr $= 0.004 I_w$	0.801
- Peak PCASS He appm/yr $= 0.003 I_w$	0.61
- Peak PCASS H appm/yr $= 0.113 I_w$	2.25
- Average Cu transmutation rates	
Ni/Cu(%/yr) $= 9.2(10)^{-4} I_w$	0.0184
Zn/Cu(%/yr) $= 9.3(10)^{-3} I_w$	0.0019
- Peak power density, $Q_c(\text{MW/m}^3) = 0.1 I_w$	2.0(nuclear)
	0.8(ohmic)

(a) FPY = Full-power year.

either first-wall^{18,19} or exoblankeet coils. Table III.C-II summarizes the key neutronic responses per unit of first-wall neutron loading as well as responses that would be typical of a 20-MW/m² neutron loading. These results can be used

to project the FPC performance in terms of pacing materials technology issues if sufficient radiation effects information were available. Present understanding of the copper alloys and inorganic insulators, however, permits only inferences to be made. For instance, the swelling of candidate electrical insulator materials,¹¹⁰ MgO and MgAl_2O_4 , has been measured after near-room-temperature irradiation to fluences of $2.1(10)^{26}$ n/m² and neutron energies above 0.1 MeV (2.8 and 0.8 v/o, respectively). For a first-wall neutron loading of 20 MW/m² extrapolation would predict swelling of 11 v/o per year for MgAl_2O_4 at the first wall if saturation did not occur. For the same material and first-wall fluence, interposition of a 0.6-m-thick PbLi blanket would reduce the predicted insulator swelling to 0.09 v/o per year. Swelling saturation is likely, however, and would greatly decrease the high-fluence swelling while possibly increasing this value somewhat at low fluence.

The electrical conductivity of many inorganic electrical insulators under irradiation is increased by roughly an order of magnitude for every order of magnitude increase in dose rate.¹¹⁰ For the relatively low-voltage applications envisaged for the CRFPR, however, the increased leakage current and ohmic loss should be tolerable in most cases, although more-detailed coil designs are required to assess fully this potential problem. For sufficiently high voltages (> 700 V) and instantaneous radiation dose rates (> 10^4 Gy/s = 10^6 rad/s), thermal runaway through ohmic heating potentially can be destructive to electrical insulators;¹¹¹ these conditions generally apply near the first wall and for relatively high-field, actively driven coils.¹⁰⁵

Increases in the electrical resistivity of first-wall or exoblancket copper coils are anticipated from the introduction of point lattice defects (i.e., vacancies and interstitials), dislocations, voids, transmutation-induced impurities, and magnetoresistivity effects. The contribution of point defects to the enhanced electrical resistivity of copper is expected to saturate at $\sim 0.0034 \mu\Omega\text{-m}$ at 310 K.¹¹² This contribution to the increased resistivity will saturate at a considerably lower value at elevated temperatures because of the reduction in point-defect content. Since the starting resistivity is $\sim 0.02\text{--}0.04 \mu\Omega\text{-m}$, the effect of point defects on increased resistivity should be small.

A high dislocation density in the copper conductor may result from plastic deformation or from the formation of radiation-induced dislocation loops. Even for a density of 10^{16} dislocations/m², which is unlikely to be sustained at

operating first-wall temperatures, the resistivity would be increased by only a few percent.¹¹³ The resistivity contribution from this source, therefore, is expected to be insignificant. Furthermore, voids or large defect aggregates should not have an important effect on resistivity. Similarly, the resistivity contribution from magnetoresistivity for magnetic fields in the range 2-3 T and temperatures of 400-600 K is estimated to be a few percent at most and more likely will be less than one percent.

The high first-wall neutron flux will generate a significant concentration of metallic impurities through (n,p), (n, γ), and (n,2n) reactions (Sec. III.B.). Similarly, transmutation of exoblanke coil conductor will also occur but at a considerably reduced level. Both Ni and Zn impurities will be generated (Table III.B-VII). Assuming the formation of only the former element, which will have the greater effect on the electrical resistivity, the predicted resistivity increase will be slightly exaggerated. The rate of impurity formation would be ~ 5.0 % per year at the first wall and is reduced to 0.02 % per year outside a 0.6-m-thick B/S for a first-wall neutron loading of 20 MW/m². Using two sets of data for Cu-Ni alloy,¹¹⁴ the (average) resistivity increases at a first-wall or exoblanke coil would be 100-200 % per year and 0.7-1.4 % per year, respectively. Both the insulator swelling and transmutation-related resistivity increases in a first-wall copper coil will require coil changeouts more frequently than once a year (3 times a year for OHTE^{18,86} and 12 times a year for Riggatron²⁰). The dramatic decrease in radiation effects when a ~ 0.6 -m-thick B/S is interposed between the plasma and coil points to significant benefits of locating even a thin (0.10-0.15 m) neutron-absorbing/moderating region between the plasma and the coil; the OHTE reactor design¹⁸ in fact is pursuing this approach.

Since thermal conduction in copper takes place primarily by the motion of electrons, an increase in electrical resistivity will also result in a decrease in thermal conductivity. To a first approximation the changes in electrical and thermal resistivities may be assumed to be proportional¹¹⁵ (Wiedemann-Franz law). Consequently, changes in the thermal properties of a copper-alloy first wall are expected over the FW/B lifetime, perhaps leading to higher temperatures, greater thermal gradients, and increased stresses as end of life is approached. The key transmutation products are Ni and Zn, and Co to a lesser extent. The increased electrical resistivity¹¹⁴ for additions of Ni to copper amounts to $\rho/\rho_0 \approx 1 + 0.8f_{Ni}$ for $f_{Ni} < 20$ wt %. The effectiveness of Zn in

increasing ρ is 0.32 times that of Ni (i.e., $\rho/\rho_0 \approx 1 + 0.26f_{Zn}$; the Ni and Zn impurities build into pure copper at rates of 0.24 and 0.13 w/o per year, respectively, for each unit of fusion-neutron first-wall loading, (Table III.6-VIII). Although the effectiveness of Co in increasing pure-copper resistivity is 5.2 times that of Ni, Co is generated only at 4 % the Ni rate and, therefore, can be ignored as a contribution to resistivity increase. Taking the upper value for the Ni/Zn generation rate and weighting in accordance to the relative effect on resistivity increase gives the following approximate expression for ρ as a function of $I_w(\text{MW}/\text{m}^2)$ and exposure time, τ (yr):

$$\rho \approx \rho_0[1 + 0.23I_w\tau] \quad . \quad (1)$$

The Weidemann-Franz law,¹¹⁵ (i.e., $k\rho/T \approx 2.5 (11)^{-8} \text{ W ohm/K}^2$) can be used to relate the increased resistivity, to the decreased thermal conductivity. Hence,

$$k = k_0/[1 + 0.23I_w\tau] \quad . \quad (2)$$

The most immediate result of a lower value of k is a higher temperature drop through the coolant-tube wall, leading to increased thermal stresses and cyclic strain. For the base-case value of $I_w\tau = 15 \text{ MWyr}/\text{m}^2$, a decrease in k by as much as a factor of four may be possible, this value representing an upper value depending on whether the transmutation products added to the crystal matrix are incorporated at grain boundaries or form a second phase.

Electrolytic tough-pitch copper (standard electrical wire grade) contains Cu_2O . Heating of this metal in hydrogen above $\sim 775 \text{ K}$ results in internal formation of steam which causes embrittlement.¹¹⁶ Maximum first-wall temperatures envisaged for most compact systems are sufficiently low to avoid this problem by the generation of molecular hydrogen. The presence of atomic hydrogen isotopes at the first-wall surface and the generation of transmutation-induced hydrogen within the lattice (Table III.C-II), however, may result in embrittlement at the operating temperature. It may be desirable to specify oxygen-free high-conductivity copper for this application, although this would

not be fully consistent with the use of a dispersion-hardened, high-strength copper alloy.

Irradiation-induced swelling of copper occurs in the temperature range between ~ 500 and 825 K, depending on the bombarding particle, damage rate, damage level, and gas content of the metal.¹¹⁷ For "gassy" copper subjected to neutron irradiation at damage rates of $6(10)^{-7}$ dpa/s (18.8 dpa/yr), the swelling range is shifted to ~ 500 - 775 K, with a maximum occurring at 625 K. The initial neutron-induced swelling rate at 775 K corresponds to ~ 0.4 v/o per dpa.⁹⁸ A copper first wall may have a high gas content because of transmutation-induced H and He and is expected to experience a damage rate that is greater than this value. A high initial swelling rate, therefore, is indicated, but saturation may occur, and the effects of alloying on swelling are not known. Possible constraint by a stainless-steel structure backing the copper first wall may also be considered. Temperature and neutron flux differences between inner and outer first-wall surfaces, as well as throughout the steel blanket structure, will also result in spatial variations of the swelling rate through the thickness. Some variation may also result from different displacement and gas generation rates at inner and outer surfaces. These separate effects remain to be integrated into a composite estimate of first-wall life based on a detailed engineering design. Ultimately, reliable materials models of an integrated nature must be used to set the first-wall and blanket operating temperature. Little or no data are available for copper on the effect of alloying, neutron fluence (above ~ 1 dpa), and temperature except for pure copper for damage levels < 1 dpa. Irradiation tests for these alloys in a fast spectrum, however, should be available soon.

Irradiation damage often results in strengthening and embrittlement of metals as a consequence of microstructural changes. Copper is strengthened by irradiation, at least up to 411 K,¹¹⁶ and, although experimental results showing embrittlement or decreased stress-rupture lifetime for this metal are not available, these effects are likely consequences of the formation of a damage microstructure. At temperatures below approximately half the melting point and in fast-neutron fluxes greater than 10^{17} n/m² s, metals typically show an enhanced creep rate compared to that observed for the unirradiated material.¹¹⁸ This enhanced creep results from the generation of point defects during irradiation. Since a copper first wall most desirably would operate from 40% to 45% the absolute melting temperature in a high fast-neutron flux,

accelerated creep can be expected. The interaction of enhanced creep and embrittlement processes in a high-radiation-flux first wall is largely unknown, however, particularly for solution-hardened alloys. Age-hardened copper alloys such as MZC, however, may overage or the alloying element may dissolve under irradiation; generally, dispersion-hardened alloys may exhibit greater radiation stability in this respect, although the impact of atomic hydrogen within the matrix on alloy stability is not known.

4. Summary. The compact reactor approaches will require materials development that in some areas differ in emphasis from the mainline approaches. The greatest need for materials development rests with the high-heat-flux IVCs (FW, limiters, divertors). Given that IVCs can be designed and operated with 4-5 MW/m² average heat fluxes, the critical areas reduce to a) the partition of radiation versus particle flux incident upon IVC surfaces; b) the associated sputter-erosion rate; c) the redeposition processes (location and integrity); and d) the impact on the overall plasma performance of potentially large transfers of impurities around the system. The problems related to sputter erosion, however, in magnitude and kind, are not unique to compact reactors. Even if sputtering rates are increased for the compact systems, given similar plasma and edge-plasma physics, the amount of sputter per neutron fluence [mm/(MWyr/m²)] should be independent of the concept and simply becomes a matter of "fluence." Hence, the potentially unique materials problems for compact systems are related to the need to understand and control the bulk mechanical radiation damage properties of the new materials (copper or vanadium alloys) required to deal with the increased heat fluxes. Even then, such materials may be used in pumped limiters and/or divertor plates for the larger superconducting fusion systems.

The compact reactor option narrows the many B/S choices listed in Ref. 87 to a few concepts that can operate at local and average power densities considered economically necessary for other nuclear power systems. The functional integration and design simplicity of the self-cooled PbLi blanket gives a strong attraction to this B/S concept for application to compact, high-power-density fusion reactors. Extension of liquid metals for first-wall cooling, the level of MHD pressure drop and pumping power incurred within the blanket, and the impact of blanket structure corrosion limits on flow geometry and alloy selection, however, are sensitive to both design and confinement concept. The magnet development required to produce relatively small,

radiation-hardened resistive coils appears to be well advanced,^{107,108} albeit on a reduced scale. Generally, for both B/S and magnets, the materials requirements for the compact options appear no more difficult, and in many respects may be easier, than the mainline program needs. An increased emphasis, however, must be placed on understanding creep, fatigue, fatigue-creep interaction, alloy stability, and coolant-alloy interaction for the high-heat-flux materials.

D. In-Vacuum Components (First Wall and Limiters)

1. General Thermal-Mechanical Considerations. Section III.C.1. describes the first-wall materials selection criteria based primarily on generalized thermal-mechanical considerations. The feasibility of the compact RFP reactor depends on a practical first-wall and limiter design that is capable of withstanding the neutron, thermal, and particle fluxes from the high-power-density plasma. Most of the neutron flux passes through the first wall and is absorbed in a lithium-bearing blanket, but the thermal and particle fluxes are absorbed entirely by the first-wall and limiter surfaces. In addition, for every 1 MW/m^2 of fusion neutrons incident upon the first wall, typically $\sim 10 \text{ MW/m}^3$ will be deposited by neutron/gamma-ray volumetric heating within the first-wall structure; this heat also must be removed by the first-wall and limiter coolant circuits. The first-wall thermal-mechanical response was judged early in the CRFPR study as a limiting engineering constraint. The work reported in Ref. 101 was performed early in this study to provide key thermohydraulic and fatigue input to the CRFPR design-point determination. It was on the basis of cost estimates (Ref. 15 and Sec. IV.C.), supported by these early thermal-mechanical analyses, that the $I_w = 20\text{-MW/m}^2$ design point was selected.

Sections III.H. and III.I. give preliminary results of the more-serious but related problem of particle control. In addition to determining the heat load on the first wall and other in-vacuum-component (IVC) surfaces, the unresolved issue of particle control also impinges directly on the length and form of the thermonuclear burn cycle (Sec. III.G.); these factors in turn determine peak-to-average heat loads, cycle frequency and durations, and ultimately the cyclic fatigue lifetimes for the crucial first-wall/limiter system. This section describes a thermal-hydraulic analysis for a first wall subjected to the full, average heat load emanating from the plasma. The analyses presented herein are also applied to a sample limiter surface suggested by the analyses given in Sec. III.H. Because of the anticipated high first-wall coverage, the limiter surface would operate somewhat above the average first-wall heat load. Section III.H., particularly, focuses on particle-control aspects of the pumped limiter and an estimate of limiter shape for a given design heat flux. The power split between first-wall, limiter, blanket, and other systems, and the means by which these various power streams

are integrated and used to drive an efficient thermal cycle is described in Sec. III.L.

The first-wall thermal-mechanical study reported in Ref. 101 conservatively adopted the burn cycle developed for the earlier superconducting RFP reactor⁵³ design, which also used a copper-alloy first wall. This latter burn cycle was adjusted for the higher steady-state first-wall loading predicted by the earlier CRFPR parametric study.¹⁵ The first wall for this pulsed-burn case would be exposed to a time-averaged thermal flux of $I_{QW} = 4.9 \text{ MW/m}^2$ with a transient in the cycle of 8.9 MW/m^2 . The peak-to-average heat flux can be considerably reduced, although the more-severe conditions examined in Ref. 101 admitted a fatigue life for a water-cooled, copper-alloy first wall that was 10^6 cycles in one year of operation. To give some perspective to the heat-flux requirements projected CRFPR, a compilation of heat fluxes normally encountered in science and industry as well as for specific fusion applications is given in Fig. III.D-1. The average heat fluxes for this CRFPR design are somewhat higher than in typical process equipment, but these heat ratings are approximately two orders of magnitude less than the highest rates reported in the literature. For cyclic batch-burn operation, the service life based on radiation damage limits in the $I_w \approx 20\text{-MW/m}^2$ case is projected to be also on the order of one year. The CRFPR operation is presently envisaged to be longer pulsed, if not steady state, the issue of steady-state current drive being addressed in Sec. III.K.

The criteria used in Sec. III.C.2.a. for materials selection does not specify a design. To carry this design further, the selection of the principal design variables (i.e., the coolant-channel dimensions, the wall thickness, and the configuration of a heat-transfer module) must be made. A simple coolant-tube geometry is assumed. The primary (tensile) hoop stress, σ_p , in a tube subjected to internal coolant pressure, P_c , is given by

$$\frac{\sigma_p}{P_c} = \frac{\xi + 1}{\xi - 1}, \quad (1)$$

where $\xi = (1 + 2\delta/d)^2$ is the square of the ratio of outer tube diameter to inner tube diameter, d , and δ is the tube-wall thickness. The secondary thermal stress for a temperature difference ΔT_w across the tube wall is given by

Fig. III.D-1. Comparison of heat fluxes for MFE and other systems. This figure extends a previous compilation,¹¹⁹ where the magnitude of the heat flux is that transferred to the coolant. The compilation does not consider the enormous transient heat fluxes that can be generated for brief periods, for example, in shock tubes, but the heat is not transferred to a coolant.

$$\sigma_{TH} = \frac{\alpha E \Delta T_w}{2(1 - \nu)} f(\xi) \quad (2A)$$

$$f(\xi) = 2 \frac{1 - (\ln \xi)/(\xi - 1)}{\ln \xi} \quad (2B)$$

Combining the secondary (thermal) and primary (pressure) stresses for a thin-wall tube leads to the following expression for the total stress, $\sigma = \sigma_p + \sigma_{TH}$:

$$\begin{aligned} \sigma &= \frac{P_c d}{2\delta} + \frac{\alpha E I_{Qw} \delta}{2k(1 - \nu)} \\ &= \frac{P_c d}{2\delta} + \frac{\sigma_Y I_{Qw} \delta}{M} \quad , \end{aligned} \quad (3)$$

where $M = 2\sigma_Y k(1 - \nu)/\alpha E$ is the thermal stress parameter given in Fig. III.C-2, σ_Y is the yield stress, I_{Qw} is the heat flux, and $\xi \rightarrow 1$ for the approximation of a thin-walled tube.

As an example, the nominal stress in a 6-mm-diameter MZC copper-alloy tube is given as a function of δ and I_{Qw} in Fig. III.D-2 for an internal coolant pressure $P = 15.2$ MPa (2200 psia); these conditions correspond to the baseline case developed in Sec. III.L. To minimize the combined thermal and pressure stress, an optimum wall thickness of ~ 1.0 - 1.5 mm is needed. For tube walls of this thickness range, the nominal stress is 75 MPa, which is about a factor of five less than the reported¹⁰⁰ tensile strength for the MZC copper alloy at 763 K (750°F). These preliminary structural considerations do not constitute a complete failure analysis and must be refined to account for nonuniformity of heat flux, axial loading, creep, radiation effects, and (most crucially) sputter erosion.

More-detailed time/space-dependent thermal-mechanical analysis of this first-wall configuration¹⁰¹ indicates even for short-pulsed (~ 26 s) operation with peak-to-average heat-flux ratios of ~ 2 that the MZC copper is capable of 10^6 cycles, which corresponds to a design life of approximately one year with a ~ 75 - 80 % duty factor. The effects of radiation damage, power density non-uniformities, and the use of discrete limiters, however, remain to be

Fig. III.D-2. Stress in 6-mm-diameter MZC copper tube with 15.2-MPa (2200 psia) internal pressure and surface heat flux given by I_{ow} . The minima in the curves indicate an optimum design for first-wall thicknesses in the range 1.0-1.5 mm.

determined. It is noted, however, that a one-year fatigue life corresponds to a 14.1-MeV neutron fluence of 15 MWyr/m^2 for the design heat loads used in the Ref. 101 analysis.

As indicated in Sec. III.C., the thermal conductivity, k , of copper at this level of radiation may be reduced by a factor of $\sim 2-3$ over a $\sim 15\text{-MWyr/m}^2$ life. If the first-wall thickness is at the minimum stress point indicated on Fig. III.D-2 given by

$$\delta_{\text{MIN}} \approx \sqrt{\frac{P_{\text{cd}}}{2} \frac{M}{\sigma_Y I_{\text{QW}}}} \quad (4A)$$

$$\sigma_{\text{MIN}} = 2 \sqrt{\frac{P_{\text{cd}} \sigma_Y I_{\text{QW}}}{M}} \quad (4B)$$

a decrease by a factor of ~ 2 in $M \propto k$ will result in a thermal stress increase by $\sim 40\%$ to ~ 106 MPa, which is still a factor of two below the tensile strength of MZC copper alloy. The transmutations-related changes in key thermal-physical parameters for the FW advanced alloys, nevertheless, remain a concern.

2. Thermal-Hydraulic Analyses. This section describes the methodology used to estimate the first-wall and limiter coolant needs and limitations. Section III.H. gives the model used to estimate the limiter parameters. The integration of the first-wall, limiter, and blanket coolant circuits into the power cycle and consideration of related synergistic effects are addressed in Sec. III.L.

a. First Wall. A sketch of a proposed first-wall configuration is shown in Fig. III.D-3. Several other coolant-channel configurations were considered: circular tubes, rectangular channels, and embossed panels. The nominal ~ 20 -mm thickness of the FW provides an electrical shell time of ~ 10 ms, although the precise function of this shell beyond the theoretical predictions of the Taylor theory³³ is not well understood, particularly in view of the thick liquid-metal blanket that surrounds the plasma. The effects of this thick first-wall structure on the tritium-breeding ratio is shown in Fig. III.B-7. The neutronic sensitivity studies performed in Appendix C to estimate two-dimensional effects indicate the desirability to reduce this first-wall thickness to ~ 5 mm. The D-shaped coolant tube was selected based on considerations of mechanical stress and ease of fabrication. High-pressure cooling water flows through the D-shaped coolant tubes and absorbs the conductive, convective, and radiative heat flux emanating from the plasma that does not impinge on or under the limiter. In addition, nuclear heating within the first-wall material is transferred to this first-wall coolant. The coolant-channel dimensions were selected on the basis of a comprehensive parametric study (Sec. III.L.2.) that optimized on pumping-power for fixed flow conditions (i.e., subcooling, velocity, stress,

Fig. III.D-3. Proposed first-wall/second-wall (FW/SW) configuration.

etc.). This optimization is relatively independent of the actual first-wall thickness.

The direction of first-wall coolant flow can be either toroidal or poloidal. The toroidal direction was selected because of a simpler manifold design (Sec. III.L.3.). This first-wall coolant flow is in the opposite direction as that of the PbLi blanket coolant, which as shown in Sec. III.E. is primarily poloidal in order to minimize MHD pressure drops and pumping power. The first-wall cooling water flows through the first-wall cooling tubes and returns through a similar tube array in the second wall (SW, Fig. III.D-3), where nuclear heating within the second-wall and conductive heat flow from the PbLi blanket (back leakage) are absorbed. The water-cooled second wall was deemed necessary to hold temperature limits in the blanket structure set by PbLi/HT-9 corrosion limits. The toroidal FW/SW coolant flow is divided into $N \approx 24$ toroidal segments for purposes of coolant manifolding and headering.

A thermal-hydraulic analysis is performed for steady-state operation. Design variables include inside tube diameter, d , tube-wall thickness, δ , and inlet and exit coolant temperatures. Results of the neutronics calculations (Sec. III.E.) and the thermal analysis of the PbLi blanket (Sec. III.E.) are used to determine the rate of heat transfer to the FW/SW coolant water. The mass flow rate in each coolant tube is then computed for a given tube geometry and inlet/exit water temperatures. A thermal analysis is performed for both the FW and SW coolant tubes to determine the temperature and stress distribution within the material. The pressure drop over the tube length and the total pumping-power requirements are also computed for use in the integrated reactor energy balance (Sec. III.L.2.).

The total energy absorption rate for the first-wall and limiter coolant water is given by the sum of the alpha-particle and ohmic powers from the plasma, $P_\alpha + P_\Omega$, the neutron/gamma-ray energy generation within the first-wall and second-wall materials, $P_{FW} + P_{SW}$, and the convective heat transferred from the hotter PbLi blanket to the FW/SW system, P_{BL} . The plasma heat flux is obtained from a plasma transport model (Sec. III.G.), the neutron/gamma-ray energy generation rates are available from the neutronics analysis (Sec. III.B.), and the convection loss to the FW/SW from the PbLi blanket is estimated as part of the blanket thermal analysis (Sec. III.E.). The alpha-particle and ohmic-heating powers are $P_\alpha = 546.5$ MW and $P_\Omega = 25.3$ MW. From the neutronics analysis, $P_{FW} = 495.1$ MW and $P_{SW} = 97.1$ MW. The blanket thermal-hydraulic analysis gives $P_{BL} \approx 96$ MW for a total of 1260.0 MW delivered to the FW/SW water coolant, which amounts to 37.4 % of the total thermal power generated being delivered to the FW/SW (includes limiter) coolant circuit. The impact of the power split between FW/SW, limiter, blanket, and shield on the overall thermal efficiency thermal-cycle design is discussed in Sec. III.L.1.

The neutronics analysis (Sec. III.B.) is based on the assumption of a uniform (homogenized) first wall (Fig. III.B-5). In the actual design, pumped limiters may be incorporated. The limiters would be constructed of the same material and would have a similar effective thickness as the first wall. The rates of energy absorption by the first wall and limiter will also be proportional to the respective projected surface areas since the limiter design heat flux (6 MW/m^2) is approximately that of the first wall (5 MW/m^2). The analysis described in Sec. III.H. indicates that the limiters will cover approximately 38 % of the first wall.

Of the total power being lost directly from the steady-state plasma ($P_\alpha + P_\Omega = 571.8$ MW), $f_{\text{RAD}} = 0.9$ is assumed to be radiated, and the remaining 10 % is lost as convective/conduction losses. This plasma transport loss, $P_{\text{TR}} = (1 - f_{\text{RAD}})(P_\alpha + P_\Omega) = 57.2$ MW, is concentrated almost entirely on the limiter surface. The limiter also receives 38 % (limiter coverage fraction) of the neutron absorption and plasma radiative losses, which amounts to $0.38 [495.1 + 0.9(546.5 + 25.3)] = 383.6$ MW. The limiter, therefore, receives a total of 440.8 MW and the FW/SW system receives 819.1 MW. Details of this split and the integration of all power-producing systems are described in Sec. III.L.1.

A numerical analysis was used for the thermal-hydraulic design of the first and second walls. The inside diameter of the D-tubes, d , the inlet water temperature, T_{wi} , and the inlet water pressure, P_w , are treated as design variables. The stress model described in Sec. III.D.1. was used to calculate an appropriate tube-wall thickness, δ , for the specified values of d and P_w . The number of first-wall and second-wall tubes is then determined from the following expression:

$$N_T = 2N [2\pi r_w / (d + 2\delta)], \quad (5)$$

where $N \approx 24$ is the number of toroidal reactor segments and r_w is the minor radius of the first wall. The factor 2 is included in Eq. (5) because the manifold pipe supplying the FW/SW circuit in a given toroidal segment is positioned in the middle of that segment and supplies cooling tubes on both sides. The length of an average cooling tube is given by

$$L = 2\pi R_T / 2N \quad (6)$$

An additional first-wall design variable is the outlet water temperature, T_{co} . Given a value for that parameter, the mass flow rate, $\dot{m}_w$, and velocity, v , for a single tube are computed from

$$\dot{m}_w = Q_w / (N_T \Delta i), \quad (7)$$

where Q_w is the total cooling rate required for the first wall (i.e., all

surface and volumetric heating), Δi is the increase in enthalpy of the cooling water, and

$$v = 8 \dot{m}_w / (\pi d_i^2 \rho_c), \quad (8)$$

where ρ_c is the average density of the cooling water.

The inside tube-wall temperature at the exit for a first-wall tube is given by

$$T_{wi} = T_{co} + q_{wi}/h, \quad (9)$$

where q_{wi} is the heat flux at the inner surface of the tube wall and h is the local film coefficient. The heat flux q_{wi} is determined by dividing Q_w by the total effective area of the inside surface of the tubes, and h is calculated from the following expression:¹¹⁹

$$h = 0.0155 \frac{k_c}{d_H} Pr^{0.5} Re^{0.83}, \quad (10)$$

where k_c is the thermal conductivity of water, d_H is the hydraulic diameter of the tubes, Pr is the Prandtl number, and Re is the Reynolds number.

The first-wall surface absorbs radiation at a rate of $I_{Qw} = 4.59 \text{ MW/m}^2$ (i.e., f_{RAD} or 90 % of $P_\alpha + P_\Omega$ divided by A_{FW}) based on the projected wall area [$A_{FW} = (2\pi)^2 r_w R_T = 111.8 \text{ m}^2$]. The curved cylindrical surface (Fig. III.D-3) increases the effective area by a factor of $\pi/2$, giving an actual heat flux through the tube surface of $I'_{Qw} = 2.92 \text{ MW/m}^2$. The neutron/gamma-ray energy generation within the first wall is $Q_N = 218.0 \text{ MW/m}^3$ (Table III.B-VI). The temperature at the outside surface of the tubes (maximum material temperature) is calculated on the basis of one-dimensional steady-state thermal conduction, giving

$$T_{wo} = T_{wi} + Q_N(\delta/h + \delta^2/2k) + I'_{Qw}(1/h + \delta/k), \quad (11)$$

where k is the thermal conductivity of the MZC copper alloy and T_w is given by Eq. (9).

The following conditions are selected to be satisfied for an acceptable FW/SW/limiter design.

- The fluid velocity must not be large enough to cause excessive erosion. A value of 10 m/s is selected as a nominal upper limit.
- The maximum temperature at the inside surface of the tubes, T_{wi} , must be less than the saturation temperature of water by some selected amount. A difference of 10 K is selected for design purposes.
- The maximum material temperature, T_{wo} , must be less than a specified value. One-half the melting temperature is selected as the upper limit.

The second condition listed above is more conservative than the condition in a typical PWR, where the wall temperature can be above the saturation temperature in some regions, and subcooled nucleate boiling is allowed. If one or more of these conditions is not satisfied, the outlet coolant-water temperature, T_{co} , is adjusted. Lowering the outlet coolant temperature will decrease T_{wi} and T_{wo} , but v and the pumping power will increase. If adjusting the outlet coolant temperature does not yield an acceptable solution, one or more of the other design variables is adjusted. The pressure drop for the first-wall coolant tubes is given by

$$\Delta P_1 = f_F \frac{L}{d_H} \frac{\rho_c v^2}{2}, \quad (12)$$

where the Fanning friction factor is computed from the following relationship:

$$f_F = 0.184/Re^{0.2}. \quad (13)$$

The equations used to calculate thermal-hydraulic conditions for the second wall are the same as those used for the first wall except for the cooling rates and heat fluxes. The inlet coolant temperature for the second wall is the first-wall outlet temperature, and the mass flow rates and tube diameters are the same as those for the first wall since the first-wall coolant is returned through the second wall. The coolant temperatures are slightly higher in the second wall, but the heat fluxes are low and the maximum inside and outside wall temperatures are generally lower than those in the first wall.

The mechanical loading applied to the FW/SW coolant tubes arises primarily from the internal coolant pressure, with a small stress being generated by the internal temperature gradient. Calculations have been performed for a range of coolant pressures from 8.3-15.2 MPa (1200-2200 psi). The maximum tensile (hoop) stress caused by the water coolant at 15.2 MPa (2200 psi) for a tube with a 6-mm inside diameter and a 1-mm-thick wall is only 45.6 MPa (6600 psi), which is less than 20 % of the tensile strength of MZC copper at 600 K. A thermal cyclic fatigue analysis¹⁰¹ was performed for a pulsed mode of operation and indicated that the coolant tubes can easily withstand 10^6 cycles under conditions that are 2-3 times more severe than long-pulsed or steady-state operation, as measured by the peak heat flux. The present design is based on steady-state operation using "F-θ pumping" current drive.

The coolant pressure and outlet water temperature were chosen to prevent subcooled-flow boiling. The adequacy of the margin between the local peak fluid temperature and the saturation temperature is a matter of judgment that should be based on a more-refined analysis and experiments at high transient heat fluxes. The first-wall design is not sufficiently advanced to allow heat transfer in the inlet and outlet headers to be considered. Careful attention to regions where the flow turns from axial to radial will be needed to prevent localized boiling. Table III.D-I gives the thermal-hydraulic design parameters

TABLE III.D-I

FIRST-WALL THERMAL-HYDRAULIC DESIGN PARAMETERS

Heat Flux and Total Power

• Heat flux (MW/m^2)	5.0
• Volumetric heat generation (MW/m^3)	222.
• Power absorbed by first-wall coolant (MW)	819
• Percent of total thermal output	0.24

Geometry

• Number of first-wall sectors	24
• Number of channels per first-wall sector	589
• Channel length (m)	0.50
• Channel radius (mm)	3.0 ("D" shaped)
• Channel wall thickness (mm)	1.0

that have been adopted for the FW/SW system. The optimized FW/SW thermal-hydraulic parameters can be found in Table III.L-IV.

The turbulent, forced-convection correlation [Eq. (10)] predicts conservative heat-transfer coefficients for the first-wall coolant. This correlation is valid for fully developed velocity profiles and thermal boundary layers in uniformly heated tubes under steady-state conditions. Because the heat flux is nonuniform around the tube, the Nusselt number will vary circumferentially. According to an analysis that includes effects of circumferential tube-wall heat conduction,¹²⁰ the local Nusselt number at the apex of the tube may be significantly less than that used in the present design. A more-detailed analysis includes both radial and circumferential conduction¹²¹ and shows that neglect of radial conduction is not important and supports the decrease in heat transfer at the tube apex. Based on experimental results,¹²² Ref. 121 cautions that the circumferential variation in the local heat-transfer coefficient is less pronounced than theoretical analyses predict, and the decrease in heat transfer mentioned above may be too severe a penalty.

If the first-wall heat transfer should require augmentation while maintaining an acceptable pressure drop, at least two methods for improvement can be envisaged. Extended surfaces or "fins" are considered an established technology as is the use of swirl-flow devices and twisted-tape inserts. Fine spiral grooves machined on the inner tube surface achieve the benefits of both swirl and extended surfaces. Other variations are possible and are commercially available. The precise benefit in applications where the high-Reynolds-number flow is nonuniform, transient, and high flux, however, must be determined experimentally; a factor-of-two reduction in the film temperature drop does not seem unreasonable, however. Some of the highest steady-state heat fluxes to flowing water ever measured¹²³ (173 MW/m^2) were obtained with swirl flow in short smooth tubes.

Fouling of the surface at the tube/water interface will lead to reduced heat-transfer efficiency and higher copper temperatures. Many variables affect fouling, including time in service, tube surface material, temperatures of the tube surface and the water, and the water velocity. Careful control of water chemistry can greatly reduce the effects of fouling. The operating parameter range (Table III.L-IV) expected for the FW/SW system generally is in a range where fouling should be low.

At high flow velocities, the possibility of fluid erosion of the copper coolant passages must be considered. For pure water with low solids content and no cavitation, erosion should not be a problem. The flow passage geometry must carefully avoid low-pressure regions that can lead to cavitation. Corrosion of the copper wall by the water coolant in the one-year design life should be less than 0.1 mm;⁹⁹ the effects of radiation and radiolytic decomposition of the water coolant on corrosion rate, however, remains to be assessed.

Although advanced by most standards of contemporary industrial heat-transfer systems, a water-cooled, copper-alloy first wall should not present a serious development problem from the viewpoint of thermal stress and heat transfer. The stress-optimal FW thickness interposed between the coolant channel and the plasma (1.0-1.5 mm) does present a serious concern from the viewpoint of sputter-erosion life if a substantial fraction of the plasma transport incident upon the first wall appears as energetic ions or charge-exchanged neutrals. An accurate assessment of this crucial FW issue cannot be made until a better understanding of plasma-edge effects and the effectiveness of impurity-control schemes (Sec. III.H. and III.I.) is obtained.

b. Pumped Limiter. The cooling requirement for the limiter is similar to that described for the first wall in that the heat flux and energy generation rate are similar for each because of the high fraction of radiated energy ($f_{\text{RAD}} = 0.9$) and high limiter coverage fraction [$\lambda_L / (\lambda_L + \lambda_W) = 0.38$]. The MZC copper alloy is also proposed for use in the pumped limiter. The orientation of the limiter relative to the first wall is poloidal (Fig. III.E-6). The computation of the contour of the limiter surface facing the plasma is also discussed in Sec. III.H. The thickness of the limiter is made as small as possible consistent with the inclusion of coolant-water channels of sufficient size to provide adequate cooling at acceptable coolant velocities and pumping power while maximizing the limiter-slot area for purposes of particle pumping.

A thermal-hydraulic analysis similar to that used for the first-wall coolant tubes was used along with a structural analysis to determine suitable coolant-channel dimensions. The key design parameters are coolant flow rate, coolant inlet temperature, channel height and width, thickness of material between the channels and the limiter surface, and spacing between coolant channels. Optimal design requires the highest possible outlet coolant temperature that is compatible with maintaining the limiter at an acceptable operating temperature. The coolant-channel configuration proposed for the

limiter is shown in Fig. III.D-4. Cooling rates, heat fluxes, and geometric parameters for the limiters are summarized in Table III.D-II. The thermal-hydraulic analysis was made for various inlet water temperatures, pressures, and flow rates. Results of those calculations and a preliminary limiter design are given in Sec. III.L.2. (Table III.L-III).

A critical cooling problem occurs at the limiter tip. As discussed in Sec. III.H., the surface of the limiter facing the plasma receives both a radiation flux and a particle flux. This surface is shaped so that the combined energy flux incident on the limiter surface in the perpendicular direction does not exceed a design limit equal to $q_D = 6 \text{ MW/m}^2$. Equations (5) and (6) in Sec. III H.1. describe the limiter shape as determined by the solution to the edge-plasma transport equations and this q_D constraint. The point where the scrapeoff particle energy flux in the toroidal or z -direction falls below q_D determines the toroidal extent of the limiter, $z = \pm \ell_L/2$, which in turn determines the radial extent, $x = \delta'$, where the x - z coordinate system (Fig. III.D-4) is defined by the limiter leading edge (plasma radius, r_p) for $x = 0$ and the toroidal center, $z = 0$. The distance $r_w - r_p - \delta'$ determines the limiter-slot (radial) thickness available for pumping as well as the fraction, f_p , of the particles diffusing in the scrapeoff that enter the limiter slot. The resulting thickness δ' , as seen from Fig. III.D-4, is not sufficient to support cooling channels, and structure must be added to the limiter underside for this purpose. The amount of added structure, δ'' , is shown in Fig. III.D-4, which gives a view of the limiter tip as a mocked-up infinite element mesh for purposes of a thermal analysis by the computer code AYER.¹²⁴

As indicated in Fig. III.H-4, the particle energy flux, q_z , falls off nearly exponentially with distance in the scrapeoff, with an e-folding distance given approximately by $\lambda \approx 3 \text{ mm}$, where D is the scrapeoff particle diffusivity. The total heat fluxes incident onto the limiter leading edge and tip are shown in Fig. III.D-4, which is used to perform the limiter thermal analysis.

The two-dimensional finite-element AYER¹²⁴ code was used to compute the steady-state temperature distributions in the MZC copper-alloy limiter. Table III.E-I gives the thermal physical properties used, and Fig. III.D-4 gives the geometry and temperature distributions. The pressurized-water coolant flowing at the limiter tip through the 0.8- by 4.0-mm channels has a temperature of 520 K and a flow velocity of 10 m/s, which for this $Re \approx 10^5$ flow gives a local film coefficient of $94,000 \text{ W/m}^2 \text{ K}$ using Eq. (10). The temperature at the

TABLE III.D-II

PUMPED-LIMITER THERMOHYDRAULIC DESIGN PARAMETERS

Heat Flux and Total Power

• Heat flux (MW/m^2)	6.0
• Volumetric heat generation (MW/m^3)	222.
• Power absorbed by limiter coolant (MW)	396.
• Percent of total thermal output	11.8

Geometry

• Number of limiters	24.
• Number of channels for one side of a limiter	930.
• Channel length (m)	0.38
• Channel width (mm)	4.0
• Channel height (mm)	0.8

limiter tip is within limits established by creep limits for this alloy. The temperature contours at the limiter leading edge reflect the $q_D = 6 \text{ MW/m}^2$ design heat flux, while the contours reflect heat flow from the limiter tip to the bulk limiter material. These calculations include the nuclear heating within the limiter, which accounts only for $\sim 16\%$ of the total energy received by the limiter blade and 3% of the energy transferred through the leading edge to the coolant. The overall limiter power balance, including nuclear heating and coolant temperature change, is treated in Sec. III.L.2. as part of the overall FPC thermal-mechanical design integration. Although the limiter temperatures are well within an acceptable range for the configuration shown, the relatively thin sections required allow little design margin for significant net sputter erosion. Analysis of low-Z coatings on tiles and the improvements needed to better analyze these important plasma/wall interactions, including self-consistent calculation of sputtering rates, redeposition, and radiation fractions, represent an important area of future work.

Fig. III.D-4. Limiter-tip temperature and heat-flux distribution based on design developed in Sec. III.H.

E. Blanket

This section describes the thermohydraulic analysis and proposes an engineering design for the blanket. In addition to preliminary thermohydraulic analyses based on a simplified blanket model, the issues of assembly, maintenance, vacuum ducting, and coolant manifolding play an important role in this preliminary assessment. The results of this blanket scoping study are integrated with the first-wall scoping study (Sec.III.D.), the magnet design (Sec. III.F.), particle control (Sec. III.H.), and vacuum (Sec. III.J.) systems to provide an estimate of the integrated FPC (Sec. III.L.). The overall steam-power cycle and integrated system energy balance based on these scoping calculations are also described in Sec. III.L. as part of the preliminary FPC integration.

1. General Considerations. The average power density in the PbLi blanket is expected to be $\sim 30 \text{ MW/m}^3$, with the maximum occurring within the copper-alloy first wall (240 MW/m^3). The range of power densities in which other conventional and advanced engineering systems operate is shown schematically on Fig. III.E-1. Although considerably above the blanket power densities envisaged for most fusion reactor concepts, the CRFPR blanket power density does not differ greatly from other nonfusion energy sources. A survey was conducted of the various first-wall/blanket concepts that have been previously proposed for fusion reactor application.^{3,4-7,86,125-126} Those concepts were critically evaluated and various aspects of those designs have been adapted for the present design. Because of the higher local power density, liquid-lithium metal or eutectic coolants seem particularly attractive, although certain of the solid breeder materials have not been completely eliminated from consideration for operation at somewhat lower power density.

The materials used in the FW/B system provide structural, tritium-breeding, neutron-multiplying, shielding, and coolant functions. Ideally, materials selection is based on physical, thermal, neutronic, and radiation properties as well as on considerations of chemical compatibility, cost, fabricability, and resource. Ongoing work^{87,125} is quantifying and ranking the full range of FW/B concepts and materials combinations.

Generally, the blanket structural material must have good strength characteristics, good resistance to radiation damage, and acceptable compatibility with the blanket coolant. Surveys of potential structural blanket materials^{3,87} considered austenitic steels, ferritic steels, nickel, titanium,

Fig. III.E-1. Range of power densities for a number of power systems showing the relationship to the CRFPR and other fusion systems.

vanadium, and niobium alloys. A titanium-modified stainless steel was initially selected for the blanket channels and structure. This material has the same thermophysical and unirradiated mechanical properties as type 316 stainless steel but exhibits reduced swelling and embrittlement after irradiation. Considerations of increased radiation life as well as PbLi corrosion limits and

the desire to maintain high coolant temperature more recently points to the use of a ferritic steel alloy, HT-9. Table III.E-I gives selected properties for both 316 stainless steel and HT-9 ferritic alloy.

Both solid and liquid forms of lithium have been considered for the tritium breeder. A solid breeder material requires the deposited energy to be conducted to tubes or channels carrying pressurized water or helium. A liquid breeder can either be stagnant or be circulated through heat exchangers and transfer the

TABLE III.E-I

SELECTED PROPERTIES OF TYPE 316 STAINLESS STEEL, HT-9 FERRITIC STEEL,
MZC COPPER ALLOY, and PbLi COOLANT/BREEDER

PROPERTY	316 STAINLESS ³	MZC COPPER ¹⁰⁰	Pb ₈₃ Li ₁₇ ^{85,86}	HT-9 ^{3,127}
Melting temperature (°C)	1,430.	1,075.	235.	1427./1482.
Density, ρ (kg/m ³)	7,970.	8,880.	9,400.	7,750.
Poisson's ratio at 400°C, ν	0.294	~ 0.36	--	0.27
Young's modulus, E(GPa)				
• 20°C	193.	138.	--	200.
• 400°C	167.	--	--	175.
Heat capacity, c_p (J/kg K)				
• 20°C	500.	394.	--	490./452.
• 400°C	557.	418.	168.	680./618.
Thermal conductivity, k(W/m K)				
• 20°C	18.0	324.	--	29.
• 400°C	19.5	--	16.	29.
Thermal stress factor ^(a) , M(W/m)				
• 400°C	5,000.	65,000.	--	10,100.
Resistivity, η (10 ⁻⁸ ohm m)				
• 20°C	78.	2.2	--	--
• 400°C	97.	3.5	91.	90.
Viscosity (kg/m s, 300°C)	--	--	0.0029	--

(a) Figure of merit $M = 2\alpha_Y k(1 - \nu)/\alpha E$ is shown in Fig. III.C-2. Higher values imply better thermal stress characteristics. If I_{QW} (MW/m²) is the steady-state heat flux through a slab of thickness δ and the associated thermal stress is σ_{TH} , then $M = I_{QW}\delta/f_Y$, where $f_Y \equiv \sigma_{TH}/\alpha_Y$.

energy from the blanket to a steam power cycle. A thermal analysis was performed to assess the feasibility of using LiO_2 pellets surrounding tubes carrying pressurized water as a coolant at the local power density envisaged for the CRFPR. This study determined the maximum allowable coolant-tube spacing as a function of the effective (porosity-dependent) thermal conductivity of the LiO_2 and energy-generation rate within the packed bed for given values of water inlet temperature, coolant-tube size, water flow rate, and a maximum allowable LiO_2 temperature (943 K). The results of this scoping study showed that the fraction of blanket volume occupied by the coolant water and tubes could be as high as 40 % near the first wall, giving a significant reduction in the tritium-breeding ratio. In addition, the removal of energy from the blanket at temperatures less than 573 K would result in a relatively low (Rankine cycle) thermal-conversion efficiency. Hence, the use of pressurized-water-cooled, solid-breeder blankets of the kind studied in Refs. 3 and 53 does not seem feasible for the blanket power densities envisaged for the present design.

The other breeding material considered was the liquid $\text{Pb}_{83}\text{Li}_{17}$ eutectic, herein after simply referred to as "PbLi." This material can also be used as a coolant. Flowing liquid-metal coolants as used in most fusion reactor blanket concepts have problems related to potentially large pumping power and/or coolant pressures required to overcome MHD forces. The magnetic fields in the CRFPR blanket are both lower and more favorably oriented to reduce these problems. A thermal-hydraulic analysis presented later in this section shows that pumping power can be held to acceptable levels with careful design, with blanket pressurization being the primary design concern (Sec. III.L.2.).

Chemical corrosion and compatibility of PbLi with structural materials at elevated temperatures were addressed first in Ref. 85, which concluded that dissolution attack by lead is reasonably slow for stainless steel at temperatures up to 773 K, even in uninhibited lead. Although experimental data on the reactivity of PbLi and stainless steel are not sufficient for an accurate determination of a maximum operating temperature, it appears that for a blanket lifetime of about one year temperatures of PbLi in contact with stainless steel as high as 773 K may be acceptable. More-recent work¹²⁶ however, suggests coolant/structural interfacial temperatures that are ~ 50 K below the values recommended in Ref. 85. Either reduced plant efficiency or an alloy substitution (i.e., ferritic HT-9) may be required. On the other hand, corrosion-related structural temperatures are usually set by mass transport and

the potential for redeposition in cooler regions of the liquid-metal loop rather than by concerns for structural thinning and weakening. These corrosion limits, therefore, are dependent upon design choice related to flow configurations, surface areas, and whether cold-trapping or corrosion inhibitors can be used. Until these issues are resolved, maximum structural temperatures are held to $\sim 500^{\circ}\text{C}$, which for the CRFPR design requires a water-cooled "second wall" and a back leakage of higher-quality heat from the PbLi circuit to the somewhat cooler pressurized-water coolant.

The neutronics calculations given in Sec. III.B. indicate the desirability of a thin shield positioned outboard of the blanket and constructed of a material with a high neutron absorption and reflection. The materials selected are boron carbide and tungsten, both also being cooled either by flowing PbLi or pressurized water. Since this thin (0.1-m) high-temperature shield makes a major contribution to both the mass and cost of the blanket, an incentive exists to find a better composite for this location to achieve the desired blanket energy recovery efficiency ($\epsilon_B \approx 0.985$). Postdesign studies given in Appendix C also indicate the desirability to enhance the reflector rather than the shielding properties of this system and point toward the use of more steel and/or tungsten and no boron carbide. Figure III.B-5 gives the CRFPR blanket used to assess both neutronic and thermohydraulic performance. As is shown in Sec. III.L., a water-cooled shield is selected, this shield also serving an important structural function as well as defining the vacuum ducting.

2. Thermal-Hydraulic Analysis. The proposed self-cooled PbLi/steel blanket can assume a number of configurations that are best adapted to the CRFPR magnetics topology. Four configurations that have been analyzed are illustrated in Fig. III.E-2, all adopting flow in the poloidal direction. A fifth configuration, similar to configuration three with the flow in the toroidal direction, was also examined.

An MHD flow model was used to estimate the MHD pressure drop and pumping power for specified values of inlet and exit fluid temperature and for given channel dimensions. The calculational procedure is described below, which is then followed by parametric results and comparisons. Finally, a configuration is selected for the FPC integration studies (Sec. III.L.), which also served as an example for the hydraulic analysis (Table III.L-V). The blanket thermal-hydraulic studies must be made iteratively with both the magnetic (Sec. III.F.)

FIRST CONFIGURATION:
SERIES CONNECTED
CHANNELS

SECOND CONFIGURATION:
PARALLEL CHANNELS,
UNDIVIDED MANIFOLD

THIRD CONFIGURATION:
PARALLEL CHANNELS,
DIVIDED MANIFOLD

FOURTH CONFIGURATION:
SPLIT CHANNELS,
DIVIDED MANIFOLD

Fig. III.E-2. Blanket flow configurations considered for the high-power-density, flowing-PbLi/steel blanket. All cross sections indicate poloidal flow with the major axis of the torus to the left. All coolant ducting to and from the blanket is located at the low-field, accessible outboard side of the torus.

and particle-control/vacuum (Sec. III.G.) studies; the material contained herein represents a first step in that iterative design process.

a. Calculation of Blanket Pumping Power. Eddy currents are induced when an electrically conducting fluid of viscosity η and electrical conductivity σ flows between parallel plates of separation $2a$ with a velocity u perpendicular to a magnetic field. These eddy currents interact with the magnetic field, and a pressure gradient dP_M/dx results.

$$\frac{dP_M}{dx} = - \frac{\eta u}{a^2} \left[\frac{H^2 \tanh H}{H - \tanh H} + \frac{H^2 C}{1 + C} \right], \quad (1)$$

where $H = aB(\sigma/\eta)^{1/2}$ is the Hartmann number, B is the strength of the transverse magnetic-field, $C = \sigma_w t_w / \sigma a$ is the ratio of conductivity-thickness products of the flowing fluid, σa , and the channel walls, $\sigma_w t_w$. If $\dot{m}_p = P_{BLK}/c_p \Delta T$ is the mass flow rate and ΔP is the pressure drop over the entire channel length, the pumping power is given by $\dot{m}_p \Delta P / \rho$, where ρ is the fluid density and P_{BLK} is the power carried through a temperature difference ΔT by the fluid of heat capacity c_p .

The thermal power, P_{BLK} , is computed by integration of the power distribution obtained from the neutronics analysis (Sec. III.B.) over the radial width of a given coolant channel. If the inlet and exit coolant temperatures are specified, then the mass flow rate is determined. For a specific flow channel geometry, magnetic-field configuration, and fluid properties, Eq. (1) is integrated to give the MHD pressure drop ΔP_M . In order to perform this integration, the poloidal-field and toroidal-field profiles within the blanket and (outboard) coolant-ducting regions must be estimated. Referring to Fig. III.E-3, the spatial variation of the poloidal and toroidal fields within the blanket (i.e., $r_w \leq r \leq r_w + \Delta b$) and coil (i.e., $r_w + \Delta b \leq r \leq r_{c\theta} + \delta_{c\theta}/2$) regions are approximated by

$$B_\phi = \begin{cases} \frac{1.52}{R} = \frac{1.52}{R_T + r \cos \theta} & (r_w \leq r \leq r_{c\phi} + \delta_{c\phi}/2) \\ 0. & (r > r_{c\phi} + \delta_{c\phi}/2) \end{cases} \quad (2)$$

$$B_\theta = \frac{4.25}{r} - 0.8r - 0.2 \quad (r_w \leq r \leq r_{c\theta} + \delta_{c\theta}/2) \quad (3)$$

The viscous or hydraulic pressure drop, $\Delta P_H = f_F(1/8a)\rho u^2$ must be added to the magnetic pressure drop, ΔP_M , which is computed by integrating Eq. (1), using Eqs. (2) and (3). The friction factor, f_F , is computed for a fluid of density ρ and velocity u flowing through a channel of width a and length ℓ [Sec. III.D., Eq. (13)]. With the total pressure drop given by $\Delta P = \Delta P_H + \Delta P_M$, the ideal

Fig. III.E-3. Geometry used to estimate MHD pressure drop for flowing PbLi coolant in the RFP magnetic topology.

pumping power, $\dot{m}_p \Delta P / \rho$, is computed for the range of flow configurations depicted in Fig. III.E-2. The actual pumping power is the ideal value multiplied by the pump efficiency, η_{PUMP} . The calculation of the series-flow configuration (Case #1, Fig. III.E-2) proceeds with the mass flow rate computed from $\dot{m}_p = P_{\text{BLK}} / (c_p \Delta T)$. The average fluid velocity is calculated from $u = \dot{m}_p / A_{\text{CS}}$, where $A_{\text{CS}} = (2a)(2\pi R_T)$ is the average cross sectional area for the flow, $R_T = 3.8$ m is the major radius of the torus, and a is the half-width of the channel. The magnetic-field pressure drop is estimated from Eq. (1), assuming that the pressure varies linearly with distance along the channel. For flow in the poloidal direction, the toroidal field, B_ϕ is the transverse magnetic field. The half-width of the channel is $a = [\Delta b - (N - 1)t_w] / 2N$, where $\Delta b = 0.5$ m is the blanket thickness, t_w is the channel wall thickness, and N is the number of channel sections.

For flow in the radial direction, the transverse magnetic field, B_θ , varies with distance in accordance with Eq. (3). An integrated average value of B_θ is determined for use in Eq. (1). The flow length in this case is the distance from the midline of the inside channel to the outside of the blanket plus the length of the inlet or exit channel. After estimation of the hydraulic pressure drop, ΔP_H , the total pumping power is computed based on the total pressure drop $\Delta P = \Delta P_H + \Delta P_M$.

The analysis of the parallel-flow configurations (configurations #2 and #3 in Fig. III.E-2) is somewhat more complex because the thickness of the channels must be selected such that the pressure drop and temperature increase are equal for all channels. Because the governing equations are nonlinear, an iterative procedure was used. The method included the following steps:

- Select initial values of half-thickness for each channel, α_i .
- Determine the cooling rate required for each channel by multiplying the local volumetric energy-generation rate by the enclosed volume.
- Calculate the mass flow rate, $\dot{m}_{pi} = P_{BLK}/(c_p \Delta T)$, for each channel.
- Compute magnetic and hydraulic pressure drops, as discussed for the case of series flow. Add these to determine the total pressure drop for each channel, ΔP_i .
- If all ΔP_i are not equal, a new estimate of channel half-thickness is computed from $\alpha_i = \alpha_1 (\Delta P_i / \langle \Delta P \rangle)^{1/2}$, where $\langle \Delta P \rangle = (1/N) \sum \Delta P_i$.
- Repeat steps until ΔP_i is within 0.1 % of $\langle \Delta P \rangle$ for all channels.

The pumping power is then calculated for each channel and subsequently summed to determine the total pumping-power requirement.

b. Results. For all cases, the electrical conductivity ratio, $C = \sigma_w t_w / \sigma a$, was computed for an uncoated or "non-sandwiched" coolant duct; the potential for lowered pumping power and increased fabrication and compatibility problems that attends the coating or sandwiching of the coolant-channel walls with electrical insulators was not considered. The first configuration

described in Fig. III.E-2 (i.e., series flow) gave unacceptably high pumping power fractions (i.e., $> 5\%$) and, therefore, was eliminated. The fourth configuration was also set aside because of practical problems associated with design of the inlet/outlet manifolds. Results for configurations #2 and #3 are shown in Fig. III.E-4 for $N = 3$ channels. Calculations for four and five channels did not show a sufficiently decreased pumping power to justify the added design complexity and increased structure. A finer resolution of a greater number of poloidal channels at the inboard, higher-power-density regions may give a better solution of the structural temperature control, however, and represents an area of future work. Within the constraints of the present study, however, configuration #2 is preferable from the standpoint of pumping power.

The model used to estimate ΔP_M does not account for the temperature variation in the transverse direction within the PbLi coolant. This variation is of little significance for a highly turbulent flow in which mixing causes a

Fig. III.E-4. Pumping power as a function of manifold thickness (height) for the parallel-flow configurations 2 and 3 shown in Fig. III.E-2.

relatively uniform temperature profile. The presence of magnetic fields, however, greatly suppresses turbulence, and the flow is expected to be laminar for the flow rates and channel dimensions used here. The rate of energy-generation within the blanket decreases exponentially with distance into the blanket, so that the much higher energy-generation rates near the first wall will result in a highly nonuniform transverse temperature distribution. It is necessary, therefore, to ensure that PbLi temperatures in the vicinity of the structural steel do not exceed a specified (corrosion-related) limit. This limit imposes a major design constraint and was accepted for design study, although the presence of flow jets and other energy-distributing phenomena may alleviate the impact of the constraint on the thermal cycle efficiency (i.e., decrease the power delivered to the lower-temperature second-wall water coolant). Furthermore, the corrosion-rate limits used to establish structural temperatures are generally based on coolant-duct plugging rather than structural thinning constraints, the former being sensitive to the specific size (surface area) and configuration. Hence, the key driving function for this blanket design that leads to adaption of a water-cooled structural wall on the inboard side of the blanket can very well be changed by more detailed design, and a number of reasons for eliminating this complication can be cited.

The interfacial temperature was investigated with the two-dimensional, time-dependent, finite-element, heat-transfer code.¹²⁴ Laminar flow of PbLi through a channel of specified thickness was analyzed for the flow rates estimated in the previous calculations using the energy absorption rates obtained from the neutronics analysis (Sec. III.B.). Heat flow through a thermal resistance to water at 473 K was used for the boundary condition at the second wall. The results of the thermal analysis on the blanket are shown in Fig. III.E-5 for channels of thickness 0.15 and 0.25 m. The thickness of the channel nearest the first wall should be limited to approximately 0.15 m in order to maintain the structural temperature below 773 K. As noted above, a number of other means for a) maintaining this structure temperature limit or b) allowing it to increase somewhat can be envisaged. Until better design and/or data bases are available, however, the water-cooled second wall is adapted for this design (Fig. III.D-3).

Figure III.E-4 shows a decrease in pumping power with increasing manifold thickness. The channel height for the analysis shown in Fig. III.E-4 assumes the manifold covers the entire outboard circumference of the torus.

Fig. III.E-5. Transverse temperature distribution at the channel exit for the high-performance inboard coolant channel.

Interference by the toroidal-field coils (Secs. III.F. and III.L.) require that the channel width be limited to about 56 % of the circumferential distance, resulting in the channel height being increased by ~ 30 %. A value of $a \approx 0.3$ m was chosen as a satisfactory tradeoff because of the relatively low pumping power without an excessively large manifold. The thicknesses of the inside channels for configurations #2 and #3 are 0.274 and 0.167 m, respectively. Based on the limitation caused by the transverse temperature difference and structural temperature limits, configuration #3 was selected. Additional adjustments of design parameters were made to satisfy the restriction that the PbLi temperature in contact with stainless steel be less than 773 K. A summary of the resulting blanket design is given in Sec. III.L.2. (Table VI.L-V).

Stress analyses have not been performed for the blanket structure. It is anticipated that steel struts will be used to maintain proper spacing between channel walls. In anticipation of total force limits on a number of flat surfaces associated with this blanket structure, an upper limit of ~ 1.4 MPa

(200 psi) was adapted for the PbLi coolant pressure in the parametric study reported in Sec. III.L.2. and used for the final design-point selection. The FW/B mechanical design will be governed primarily by the desire to use "block" or single-piece maintenance schemes, wherein the FW/B along with the TFCs and coolant ducting would be removed as a single unit; the feasibility of such an operation rests with an ability to limit the total mass of the FPC.

3. Thermal Analysis of Shield. Initial FW/B neutronics parametrics studies selected a 0.50-m-thick PbLi blanket as adequate from the viewpoint of tritium breeding. Subsequent analyses (Sec. III.B, Fig.III.B-4) indicated the benefit of adding an additional ~ 0.10-m-thick shield outside the breeding blanket in order to enhance the efficiency of thermal-energy recovery and to reduce the thermal loading on the coils. This B_4C/W shield region could in principle be cooled by the flowing PbLi blanket coolant or by a separate pressurized-water coolant, with a somewhat reduced thermal cycle efficiency resulting from the latter approach. This section considers the thermal-hydraulic aspects of both a PbLi-cooled and a water-cooled shield options. Based on configurational design choices made as part of the FPC integration task (Sec. III.L.), a pressurized-water shield coolant is selected, the shield coolant stream being combined within the blanket envelope with the FW/limiter exit-coolant stream to produce a single exit manifold of pressurized water for use in the dual-media stream cycle.

Approximately 94.5 % of the energy generated by the plasma and multiplied in the FPC is absorbed in the first wall, limiters, and blanket. The remainder penetrates the blanket with 4.20 % deposited into the shielding provided between the blanket and the toroidal- and poloidal-field coils to maximize the recovery of thermal energy; the remaining 1.3 % is deposited into the room-temperature coils. Energy at a rate of 143 MW is absorbed in this shield. The temperature distribution within the material for a PbLi-cooled shield was computed from a one-dimensional steady-state conduction analysis using the energy-generation distribution generated by the neutronics analysis; results are summarized in Table II.E-II.

A study of the manifolding required to deliver coolant to the first wall, limiters, blanket, and shield, as well as design of the vacuum ports required for the pumped limiter, indicates that the shielding is best separated from the blanket to form both a vacuum plenum and a primary structural support. This separation makes less practical cooling the shield with PbLi blanket coolant.

In this case, pressurized water would be used as the coolant. The shield configuration would be identical to the PbLi-cooled case (Table III.E-II), except for coolant-channel widths and the addition of a third channel in contact with the inside surface. Design parameters for a water-cooled shield are given

TABLE III.E-II

SHIELD THERMAL-HYDRAULIC DESIGN PARAMETERS (PbLi COOLANT)

Geometry	
• Thickness of center channel (mm)	17.0
• Thickness of outer channel (mm)	11.0
Flow Parameters	
• Flow rate in inner channel(kg/s)	TBD
• Flow rate in center channel (kg/s)	116.7
• Flow rate in outer channel (kg/s)	50.4
• Pressure drop (MPa)	0.12
Temperatures (K)	
• PbLi inlet	573
• PbLi exit	773
• Maximum temperature in shield	998
Heat-Generation Rates (MW)	
• Segment 1 (B_4C)	75
• Segment 2 (W)	40
• Segment 3 (B_4C)	38
• Segment 4 (W)	30
Total	143

TABLE III.E-III

SHIELD THERMAL-HYDRAULIC DESIGN PARAMETERS (WATER COOLANT)

Geometry	
• Thickness of inner channel (mm)	3.5
• Thickness of middle channel (mm)	5.0
• Thickness of outer channel (mm)	3.2
Flow Parameters	
• Flow rate in inner channel (kg/s)	137
• Flow rate in center channel (kg/s)	259
• Flow rate in outer channel (kg/s)	112
• Pressure drop (MPa/psi)	0.04/5.6
Temperatures (K)	
• H_2O inlet	423
• H_2O exit	503
• Maximum temperature in third wall	728

in Table III.E-III. The water-cooled shield is adapted as the design basis for the FPC integration.

4. First-Wall/Blanket/Shield Integration. Although the full integration of key FPC subsystems is addressed in Sec. III.L., some statement of the coolant-circuit integrations seems appropriate at this point. Figure III.E-6 gives a schematic diagram of the FPC coolant flows. As indicated in Fig. III.D-3, the water-cooled first-wall D-tubes would be brazed to a segment of a toroidal surface fabricated from a ~18-mm-thick MZC copper alloy. Depending on the (passive) electrical function of the first wall as well as structural and neutronic consideration, this thickness can be reduced. These D-shaped coolant tubes are arranged to provide flow in the toroidal direction. A manifold connection would join the first-wall coolant tubes to the flow channels fabricated within the second wall, thereby providing a coolant return path. Radial headers near the outboard equatorial plane would take the water coolant to and from each of $N = 24$ toroidal sectors, these headers supplying poloidal manifolds in each sector for the limiter, first wall/second wall, and shield. The poloidal manifolds for the FW/SW system within each of 24 toroidal sectors could be located near the first-wall region and integral with the FW/SW system, or these manifolds could be located at the shield region with radial tube sheets supplying and returning coolant for each FW/SW system. To reduce the number of tubes within the B/S region, the first option was selected to demonstrate the FPC integration in Sec. III.L. This option seriously reduces the tritium-breeding ratio, requiring a thinner copper first wall, 90 % ^6Li enrichment, and a higher-albedo shield (Appendix C).

The PbLi coolant circulates through the blanket in the poloidal direction. The PbLi manifolding would also enter and exit the torus along the equatorial plane in the outboard direction. The torus may be constructed in four to eight modules if this approach is found to simplify the installation and removal of the FW/B/S/TFC assembly, compared to totally "block" or single-piece maintenance. In any case, the number of basic building blocks for off-site factory assembly would be $N = 24$. Ultimately, this choice rests with the FPC mass, which will be determined through economics by the FPC radiation lifetime.

Fig. III.E-6. Schematic diagram of pressurized-water and PbLi coolant flow in one of $N \approx 24$ toroidal sectors forming the FPC.

F. Magnets

The CRFPR design point described in Table II.D-III requires the nominal toroidal-field-coil (TFC) and poloidal-field-coil (PFC) parameters listed on Table III.F-I. The simplified magnet model used in the parametric systems model,¹⁵ from which Table III.F-I was generated, lumps the TFCs and PFCs into composite conductors with a representative conductor filling fraction ($\lambda_c \approx 0.7$) being specified to estimate ohmic losses (recirculating power), coil masses (and cost), and system power density (independent parameter). Figure III.E-3 illustrates this geometry and defines key notation. To advance the reactor design from the level of the Ref. 15 parametric study, both the TFC and PFC designs must be considered in more detail. The TFCs would be affixed to the FW/B/S system, forming a single toroidal unit that would be amenable to block maintenance. The PFCs on the other hand, would in part be moved to allow a

TABLE III.F-I

NOMINAL COIL PARAMETERS FOR CRFPR DESIGN
ESTIMATED FROM PARAMETRIC SYSTEMS CODE^(a)

PARAMETER	TFC	PFC
Coil thickness, $\delta_{c\phi, \theta}$ (m)	0.09	0.36
Current-center minor radius, $r_{c\phi, \theta}$ (m)	1.39	1.62
Total coil-set mass (tonne)	149.	703.
Magnetic field at conductor, $B_{c\phi, \theta}$ (T)	4.5 $\rightarrow$ -0.92 ^(b)	2.3
Stored energy, $W_{BC\phi, \theta}$ (MJ)	542.	1111.
Other parameters used in magnetics calculations (from Table II.D-III)		
• Major radius, R_T (m)	3.79	
• Reversed toroidal field at plasma edge, $B_{R\phi}$ (T)	-0.68 ^(b)	
• Average plasma radius, r_p (m)	0.71	
• First-wall radius, r_w (m)	0.75	
• Blanket thickness, Δb (m)	0.60	
• TFC and PFC current densities, $j_{c\phi, \theta}$ (MA/m ²)	6.06	
• Poloidal field at plasma edge, $B_{\theta}(r_p)$ (T)	5.22	

(a) Dimensions given do not reflect the added radial build that may be required for a poloidal vacuum plenum (Sec. III.L.3.).

(b) Initial (preplasma) bias field on axis could be as high as $B_{\phi 0} = 3.24$ T, although the startup procedure described in Sec. III.G.2. could limit $B_{\phi 0}$ (setup) to $B_{R\phi}$ (ignition/burn), the low-level reversed field at ignition.

vertical, en masse movement of the FW/B/S/TFC unit during the block maintenance operation (Sec. III.L.3.). This section gives the results of magnetics computations used to estimate the position, size, and support of TFCs and PFCs, which along with other key constraints (e.g., field ripple, magnetic islands, inductances, peak startup power, maximum voltages, etc.) needed to perform the FPC integration study.

1. Toroidal-Field-Coil System. The TFCs provide the initial bias field, $B_{\phi 0}$, on which the RFP is first formed, and subsequently maintains the external reversed field, $B_{R\phi}$, with a minimum ripple in toroidal field at the plasma edge. A ripple condition is used to obtain a preliminary estimate of the discretized TFC set. As summarized in Table III.F-I and illustrated in Fig. III.F-1, the parametric systems code predicts a homogeneous (i.e., toroidally continuous) TFC set of radial thickness $\delta_{c\phi} \approx 0.09$ m with a current center at $r_{c\phi} \approx 1.39$ m relative to a major coil radius of $R_T = 3.79$ m. The dimensions of the discretized TFC set are obtained by specifying $N = 24$ coils, each fitting snugly at the inboard equatorial plane around a $\Delta b = 0.6$ -m-thick blanket and shield that has a first wall positioned at $r_w = 0.75$ m. The resulting toroidal extent of each TFC, $\ell_{c\phi}$, is used in conjunction with the TFC current density, $j_{\phi c} = 6.06$ MA/m², obtained from the Ref. 15 parametric systems code, to give the radial extent, $\delta_{c\phi} = 0.15$ m, of the $N = 24$ TFCs. The current-center radius is moved from $r_{c\phi} = 1.39$ m to 1.43 m to make allowance for the discretization process. These conditions apply to the steady-state operating conditions, $B_{R\phi} = -0.68$ T. Compared to the initial on-axis bias field, $B_{\phi 0} = 3.34$ T, required to inject all toroidal flux, this field level corresponds to a TFC overrating during startup by an increase by a factor of ~ 4.9 in TFC current density (6.06 to 30.0 MA/m²) for a brief startup period should a dynamo-assisted startup prove impractical (Sec. III.F.2.). The dynamo-assisted startup, however, allows the initial toroidal bias field to equal approximately the final reversed field; the dynamo would increase the toroidal field internal to the plasma as the plasma current is increased, ignition is approached, and the minimum-energy RFP state is maintained for the appropriate $F-\theta$ values.

The discrete TFC set introduces a toroidal-field ripple with a periodicity and magnitude determined by the number of coils and their dimensions. The magnitude of this ripple is largest on the outboard side of the plasma and in the equatorial plane for a circular plasma cross section. Figure III.F-2

Fig. III.F-1. Toroidal-field-coil layout showing mod-B contours and plasma and FW/B locations, all for $N = 24$ coils and in the equatorial plane.

illustrates the toroidal-field ripple and the nomenclature used to quantify the field ripple in order to select the TFC number and dimensions.

All RFP ripple criteria are based upon dimensional limitations established by magnetic island widths. Magnetic islands result from the introduction of a spatially oscillating radial field component, B_R , which is present in any discrete TFC set, as shown in Fig. III.F-2. It is noted that magnetic islands are not peculiar to RFPs, but also represent a concern for stellarators and

Fig. III.F-2. Schematic diagram of discrete TFC set used to specify ripple constraints.

tokamaks. Magnetic islands are thought to play a role in the tokamak disruption. The island radius, Δr , is given by¹²⁸

$$\Delta r = 4 \left[\frac{r \Delta B_R}{n B_\theta (dq/dr)} \right]^{1/2}, \quad (1)$$

where r is the minor radius of the resonant surface, ΔB_R is the amplitude of the radial helical magnetic-field perturbation, n is the toroidal mode number, B_θ is the poloidal field, and $q = (B_\phi/B_\theta)/(R_T/r)$ is the safety factor. The correlation between the island width and the impact on the plasma equilibrium and transport remains to be quantified. Consequently, a universally accepted criteria for the maximum ΔB_R is not available for RFPs, tokamaks, or stellarators even though the importance of minimizing the island size is

acknowledged. One school of thought asserts that the island radius for RFPs should be smaller than the distance between the plasma radius and the reversal radius to assure field reversal occurs. Another approach argues that present-day RFP experiments obtain reversal with large field errors (i.e., $\Delta B_R/B_\theta \geq 0.01$, where ΔB_R is the peak in the radial field component along a field line, Fig. III.F-2). A reactor design criterion, therefore, should be no more stringent than an experimental design criterion. The design criterion¹²⁹ for the RFP upgrade experiment, ZT-H, is $\Delta B_R/B_\theta \leq 0.003$. Both criteria are examined for the CRFPR with the $\Delta B_R/B_\theta \leq 0.003$ constraint being used here as the design criterion.

The evaluation of Eq. (1) and the application of the first criterion requires an estimate of dq/dr . The q -profile for an RFP is typically taken to be parabolic:

$$\frac{dq}{dr} \approx \frac{q}{r/2} = \frac{2B_\phi}{RB_\theta} , \quad (2)$$

where B_ϕ is the reversed toroidal field at the plasma edge. The island radius in the vicinity of the reversal radius is then given by

$$\Delta r \approx 4 [r_p \Delta B_R R_T / 2NB_\phi]^{1/2} . \quad (3)$$

Inherent in Eq. (3) are the assumptions that the toroidal mode number, n , is given by the number of TFCs, N , and that the amplitude of the radial helical magnetic-field perturbation is given by the peak in the radial field component along a field line. The island width criterion for the CRFPR then becomes

$$\begin{aligned} \frac{\Delta r}{r_p} &\approx 4 [(\Delta B_R/B_\phi)(R_T/r_p)/2N]^{1/2} \\ &< 1 - r^*/r_w \approx 0.04 . \end{aligned} \quad (4)$$

where r^* is the radius of the reversal surface. An estimate of ΔB_R is obtained

by tracing two field lines near the plasma surface, r_p , with the three-dimensional vacuum-field magnetics code, TORSIDO,⁵¹ simulating only the TFC set. The field-line traces begin at the point $[R = R_T \pm r_p, z = 0]$ and a toroidal angle ϕ_n defining a given TFC plane for a given field period. The TORSIDO code monitors the field components along these field lines to determine the maximum of the radial field, ΔB_R .

For the ideally positioned TFC sets considered by TORSIDO, B_R produces no net radial displacement of field lines (i.e., $\langle B_R \rangle = \int B d\lambda / \int d\lambda = 0$). Modeling of the field errors inherent in coil construction and alignment that produce a net $\langle B_R \rangle$ is beyond the present level of this design; only the peak radial displacement (Fig. III.F-2) is used as a measure of ΔB_R .

All cases examined by TORSIDO require the TFC to fit snugly to the blanket/shield only on the inboard side at the equatorial plane ($R = R_T - r_p - \Delta b, z = 0$). This condition is expressed as follows:

$$\frac{\lambda_{c\phi}/2}{R_T - r_{c\phi} - \delta_{c\phi}/2} = \tan(\pi/N) , \quad (5)$$

where $r_{c\phi}$, $\lambda_{c\phi}$, and $\delta_{c\phi}$ are defined in Fig. III.F-1. The TFC conductor cross-sectional dimensions are related through the current density:

$$j_{c\phi} \lambda_{c\phi} \delta_{c\phi} = I_{c\phi} , \quad (6)$$

where $j_{c\phi}$ is the TFC current density and $I_{c\phi}$ is the TFC current per coil. Furthermore, the product $NI_{c\phi}$ is held constant in order to preserve the on-axis average toroidal field at $B_{R\phi} = -0.68$ T. Equations (5) and (6) are solved simultaneously for the coil dimensions. Parameters held fixed are listed in Table III.F-II. The results of simultaneously varying the number of TFCs, N , and the center of the TFC set, R_{TF} , are presented in Figs. III.F-3 and III.F-4 for the criteria established by $\Delta B_R/B_0 \leq 0.003$ and Eq. (3). The parameterization of R_{TF} achieves a reduction in ripple by only moving the outboard leg of the TFC outward from the blanket, thereby shifting the peak ripple from the outboard field line to the inboard field line. An accompanying increase in the coil minor radius is given by

$$r_{c\phi} = 1.43 + 2(R_{TF} - R_T) \quad (7)$$

The CRFPR design point (Table II.D-III) with $R_{TF} = R_T = 3.8$ m and $N = 24$ marginally complies with the constraint of $\Delta B_R/B_\theta < 0.003$, as seen in Fig. III.F-3. This design point requires an increase in N and/or R_{TF} to comply with the constraint of Eq. (4) shown in Fig. III.F-4. The assumptions regarding mode number ($n = N$), dq/dr [Eq. (2)], and the location of the resonant surface (at r_p) should be noted when considering the results of Fig. III.F-4. In addition, the numerical results of varying only the number of TFCs are presented in Table III.F-II for both the adjusted design point, $r_{c\phi} = 1.43$ m, and the case where a vacuum plenum of nominal radial extent (~ 0.10 m) displaces the TFCs radially outward; the need for a vacuum plenum can increase $r_{c\phi}$ to 1.53 m. The $N = 24$ case ($r_{c\phi} = 1.43$ m) has been shown in Fig. III.F-1. Figure III.F-5 gives

Fig. III.F-3. Equal-increment contours of $\Delta B_R/B_\theta$ plotted versus the number of TF coils and the location of the TFC center. Compliance with $\Delta B_R/B_\theta < 0.003$ occurs in region of thinner contour lines.

Fig. III.F-4. Equal-increment contours of Δr plotted versus the number of TFCs and the location of the TFC center. Compliance with Eq. (4) occurs in region of thinner contour lines.

the dependence of ΔB_R on toroidal and radial position for $N = 24$ and $r_{c\phi} = 1.43$ m or 1.53 m. The $N = 24$ cases serve as the basis for formulating a design to be used in the FPC integration (Sec. III.L.). A vacuum plenum of 75-mm radial thickness can be accommodated in the radial build by doubling the current density to 12.02 MA/m^2 and halving the radial thickness of the $r_{c\phi} = 1.43$ m case while maintaining the outer-bore diameter constant. The coil dimensions are then $r_{c\phi} = 1.4625$ m, $\delta_{c\phi} = 75$ mm, and $\lambda_{c\phi} = 0.60$ m. Use of the modified Bessel-function model in the burn simulation reduces the reversed toroidal field at the plasma edge from 0.68 T to 0.403 T. Consequently, both $I_{c\phi}$ and $j_{c\phi}$ can be reduced from 0.54 MA and 12.02 MA/m^2 to 0.32 MA and 7.124 MA/m^2 , respectively. The ohmic power dissipated in the TFC set, assuming copper coils with a 70 % packing fraction, is given by $P_{\text{TFC}}^{\Omega} = 1.6(10)^{-7} r_{c\phi} j_{c\phi} I_{c\phi} N$, which yields $P_{\text{TFC}}^{\Omega} = 12.6$ MW. The TFC design parameters are summarized in Table III.F-III.

TABLE III.F-II

SUMMARY OF RIPPLE AND RADIAL FIELD CALCULATIONS MADE WITH THE TORSIDO⁵¹
 CODE FOR TFC CURRENT RADII $r_{c\phi} = 1.43$ m (without vacuum plenum)
 AND $r_{c\phi} = 1.53$ m (0.10-m vacuum plenum)^(a) FOR
 TFCs CLOSELY FITTING THE B/S

PARAMETER	VALUE			
	20	24	28	32
Number of TFCs, N	20	24	28	32
Radial fluctuation of field line at outboard plasma surface δ_R (mm)	32.3(22.2)	14.6(9.3)	6.8(4.1)	3.3(1.8)
Average magnetic field along outboard field line at plasma surface (T)	0.57	0.57	0.57	0.57
Average magnetic field along inboard field line at plasma surface (T)	0.84	0.84	0.84	0.84
TFC current, I_ϕ (MA)	0.64	0.54	0.46	0.40
TFC radial thickness, $\delta_{c\phi}$ (m)	0.15	0.15	0.15	0.15
TFC toroidal length, $\ell_{c\phi}$ (m)	0.72(0.69)	0.60(0.57)	0.52(0.49)	0.45(0.43)
Distance from plasma to TFC, $r_{c\phi} - (\delta_{\phi c}/2 + r_p + \delta_R)$	0.61(0.72)	0.63(0.73)	0.64(0.74)	0.64(0.74)
Ripple constraint, $\Delta B_R/B_\theta [B_\theta = 5.22 \text{ T}]$	0.005 (0.003)	0.003 (0.002)	0.0012 (0.001)	0.001 (0.000)

(a) Values in parentheses pertain to an increase in the radial build caused by including a 0.10-m vacuum plenum; otherwise conditions remain unchanged.

2. The Poloidal-Field-Coil System. The RFP plasma is heated and confined primarily by the self-magnetic fields generated by a strong plasma current, I_ϕ , which combine with the internal toroidal field to produce the stabilizing high-shear field/pressure profiles. The PFC systems, therefore, play a major role in the reactor design. The fundamental processes involved with an RFP startup are illustrated in Fig. III.F-6. An initial toroidal bias field, $B_{\phi 0}$, is produced by the TFC system. The plasma is initiated, and a changing PFC current, $I_{c\phi}$, induces the plasma current by transformer action. The trapped initial bias

Fig. III.F-5. Radial magnetic fields for cases with and without 0.10-m-thick vacuum plenum for $R_T = 3.79$ m, $B_\phi(\text{axis}) = 0.68$ T, $r_p = 0.71$ m, and $j_{\phi c} = 6.02$ MA/m².

field is compressed by the plasma current, I_ϕ . Simultaneously, the TFC current, $I_{c\phi}$, is reduced and ultimately reversed, achieving the familiar RFP configuration depicted in the last frame in Fig. III.F-6. The bulk of the toroidal-field energy is then provided through the dominant PFC system. Once an initial, low-energy RFP state is achieved, the plasma dynamo would be used to increase further the toroidal field trapped in the plasma. The near-minimum-energy RFP state is maintained as I_ϕ is increased, turbulent plasma processes converting I_ϕ into poloidal current, I_θ , which in turn increases the toroidal field trapped within the plasma column as F and θ remain constant near the minimum-energy state (Fig. II.D-2). The toroidal field required initially within the plasma, therefore, can be made small, with a major part of the required B_ϕ being added through the PFC circuit and the dynamo effect. If the TFC system is sized to produce an initial field, $B_{\phi 0}$, that is equal and opposite to the required reversed toroidal field, $B_{R\phi}$, the RFP configuration would be

TABLE III.F-III
TFC DESIGN PARAMETERS

<u>PARAMETER</u>	<u>VALUE</u>
Major radius, $R_T(m)$	3.79
Minor radius, $r_{c\phi}(m)$	1.4625
Radial thickness, $\delta_{c\phi}(mm)$	75
Toroidal length, $l_{c\phi}(mm)$	600
Current, $I_{c\phi}(MA)$	0.32
Current density, $j_{c\phi}(MA/m^2)$	7.124
Toroidal field at plasma, $B_{\phi}(T)$	-0.403
Peak toroidal field, $B_{c\phi}(T)$	0.72
Ripple constraint, $\Delta B_r/B_{\theta}$	<0.003
Number of TFCs, N	24
Ohmic power, $P_{TFC}^{\Omega}(MW)$	12.6

established at approximately 15-20 % of the ultimate plasma current for a reversal parameter, $F = B_{\phi}(r_w)/\langle B_{\phi} \rangle$, in the range 0.1-0.2. The TFC system under these conditions requires two orders of magnitude less energy than the PFC circuit. Furthermore, the TFC set need not be designed for the startup overload, thereby allowing coils that are even less dominant of the PFC and leading to an easier maintenance scheme.

Before the PFC system can be designed to provide the steady-state (ignited) plasma requirements, as was done for the TFC system in Sec. III.F.1., both the plasma startup operations and a toroidal equilibrium must be defined. The following two sections address these important issues, with the following third section (Sec. III.G.2.c.) describing the PFC circuit analysis. This more-detailed resolution of the PFC configuration predicts a system that does not differ substantially from the more-approximate predictions of the parametric systems analysis (Table III.F-I and Ref. 15).

a. Startup Operations. The plasma current in a toroidal machine is induced by transformer action. In addition to producing the required flux change in the center of torus, the PFC system must also generate a field distribution that maintains the plasma equilibrium. Both of the current-induction and equilibrium-field functions can be provided by a single coil

Fig. III.F-6. Fundamental principle of the RFP startup sequence.

having the nearly uniform current distribution illustrated in Fig. III.F-6. This configuration greatly reduces the PFC design options, with separation of the PFC set into flux-drive (Ohmic-Heating Coil, OHC) and equilibrium (Equilibrium-Field Coils, EFC) functions being more desirable.

The OHC system provides flux change through the torus center while producing no magnetic field within the plasma minor cross section. This coil set, therefore, can be operated independently of the magnitude of the plasma current, which responds only to the change in OHC current and not the absolute current level. The stored energy and absolute field level in the OHC system is minimized through bipolar operation, wherein the OHC current is changed from $-I_{c\phi}$ to $+I_{c\phi}$.

Plasma equilibrium, on the other hand, depends on the magnitude of I_ϕ and is provided by the EFC set, which may or may not induce added flux change and plasma current. The EFC current must produce a nearly uniform vertical-field in the vicinity of the plasma (Sec. III.F.2.b.). The EFC current, I_{EF} , must closely track the plasma current, I_ϕ . Although the EFC may also contribute to the flux swing and drive the plasma current, in the extreme case when all of the ohmic-heating function is integrated into the EFC set, the entire PFC current must be operated with a less-efficient unipolar drive.

Energy can be transferred to the PFC system directly from the electrical power grid or from an intermediate energy store that initially is slowly charged from the power grid and subsequently discharged into the PFC system on a shorter time scale. The simplified circuit depicted in Fig. III.F-7, where the PFCs (i.e., OHCs + EFCs) are approximately represented by a single coil, illustrates the power transfer options. The inductances designated by L_{IN} and L_{EX} are associated with the regions or fluxes internal and external, respectively, to the PFC. An iron core ($L_{EX} \rightarrow \infty$) ideally couples the PFC current to the plasma current, giving $I_{c\phi} \approx I_\phi$ and thereby requiring a total stored energy of $E_{IN} = \frac{1}{2} L_{IN} I_\phi^2$. The amount of iron required in a reactor would be prohibitive, considerably increasing the system mass, cost, and maintenance complexity. The PFC current swing for an air-core system is given by flux conservation, $L_{EX} \Delta I_{c\phi} = (L_{EX} + L_{IN}) I_\phi$; taking $L_{EX} \sim L_{IN}$, the poloidal-current swing becomes $\Delta I_{c\phi} \approx 2 I_\phi$.

Three basic operating modes for the circuit depicted in Fig. III.F-7 are illustrated in Fig. III.F-8, and the decision options are listed in Fig. III.F-9. These three options are defined by whether an external energy

Fig. III.F-7. Simplified PFC charging/discharging circuit.

store (i.e., a capacitive rotating machine) charges the PFC system or if the PFC serves as the primary (inductive) energy store. The option that uses an inductive store can undergo a bipolar swing either through a resistive or a capacitive transfer element, thereby giving the three possible options. Using an external energy store capable of driving the PFC current from 0 to $2I_{\Phi}$ requires a total stored energy of $\frac{1}{2}L_{EX}(I_{C\Phi} - I_{\Phi})^2 + \frac{1}{2}L_{IN}I_{\Phi}^2 \approx 2E_{IN}$ for $L_{IN} \approx L_{EX}$; the stored energy required is twice that for the iron-core case because of the parasitic flux stored externally to the PFC coil. The operational mode based on an external energy store minimizes external power requirements in that the rotating machine used as the main energy store can be energized over a long period of time, and the electrical grid power, P_{GRID} , required is small.

Using the PFC as an energy-storage system significantly reduces the external energy-storage requirements. The PFC is separated into an OHC set, which produces no field within the plasma region, and an EFC set, which provides toroidal plasma equilibrium. The OHC serves as the primary energy store, this coil set being driven slowly to a current $I_{C\Phi} = -I_{\Phi}$ and storing the energy $E_{OH} = E_{IN}$ before the plasma is initiated. The energy transfer from the coil system to the plasma can be made through either resistive or capacitive elements, as is illustrated in Figs. III.F-8 and III.F-9. A capacitive transfer is highly efficient, requiring a rotating-machine energy store having a capacity

Fig. III.F-8. Decision options available for operating the PFC system, with minimum-cost choices indicated.

approximately equal to $E_{OH}/2$ and providing a complete transfer of the OHC energy to the plasma. Power from the electrical grid is needed only during the initial charging of the OHC. A capacitive transfer is required for a short-pulsed fusion burn. This efficient transfer allows the plasma current startup and rundown to occur in a short period of time, minimizing thermal cycling in the steam-to-electric thermal conversion system, and providing a means for efficient recovery of electromagnetic energy if large quantities of stored energy are

required, as in the case of the large, low-power-density superconducting approaches.⁵³ For long-pulsed or steady-state burns envisaged for the compact systems, however, these considerations are no longer important, and the resistive transfer option becomes preferred from the viewpoints of cost, operational simplicity, and use of present-day technology.

The resistive transfer option is also depicted on Fig. III.F-8. Resistively crowbarring the OHC while simultaneously initiating the plasma and connecting the EFC across the OH circuit transfers to the plasma an energy approximately equal to $E_{IN}/2$; an equivalent energy is dissipated in the transfer resistor. After the resistive transfer of the PFC current, the plasma current achieves approximately 50-70 % of the design (ignition) value; electrical grid power is then used to complete the trajectory toward full plasma current and ignition. Rapid initial current transients, limited only by the voltage allowed on the PFC system, can be achieved by the resistive transfer scheme. Since the transfer resistor has no inherent power-handling limitations, large plasma initiation powers can be generated without requiring either expensive on-site power-handling or energy-storage equipment or without demanding large transients on the electrical grid.

The CRFPR design considers long-pulsed or steady-state burns wherein energy loss, duration of the startup, and degree of reversible energy transfer would not significantly impact the overall plant efficiency. The resistive startup, therefore, is adopted as the reference design. Irrespective of the energy-transfer option, however, use of the OHC as an energy store as a minimum allows a fourfold reduction in the size of the rotating-machine energy storage if capacitive transfer is used; this element is completely eliminated if resistive transfer is used. Furthermore, substantial cost savings result from bipolar operation of the OHC system. In one limit, minimum energy requirements are achieved if an EFC is not required, while in the other limit the size of the external energy store is maximized if all the poloidal flux is driven from the EFC (i.e., no OHC is used), in which case the system must be driven in a unipolar mode; these two options delimit the OHC/EFC functional split. The overall PFC design, therefore, must seek a configuration which maximizes the role of the OHC in relation to the EFC set while satisfying the need for toroidal plasma equilibrium. This consideration is of prime importance in the placement of the EFC set and is discussed in the following section.

Fig. III.F-9. Three options considered for operating the PFC system.

b. PFC (OHC + EFC) Conductor Locations. Considerations that impact the location and current levels in the OHCs and EFCs were discussed in Sec. III.F.2.a. and are summarized in Fig. III.F-10. Determining the proper location of the EFC and OHC conductors allows the use of single-turn self-inductances and mutual inductances to describe the interaction between the OHC, EFC, and plasma. Using these parameters and enforcing plasma equilibrium allows the calculation of all necessary coil currents. The self-inductance of the plasma is calculated analytically from the following expression:

Fig. III.F-10. Major considerations that impact on the location and current levels in the OHC and EFC systems.

$$L_p = \mu_0 R_T [\ln(8R_T/r_p) - 1.25] , \quad (8)$$

which includes the internal energy stored by the magnetic fields assumed to characterize the RFP. This inductance includes the internal toroidal-field energy, which is provided by the poloidal circuit through the RFP dynamo effect. Since the final plasma configuration will be established at a low current level ($\sim 15\%$ of the final plasma current), the plasma inductance remains virtually constant over the bulk of the plasma current rise. Only variations in beta affect the profiles, and less than a 10 % change in the plasma inductance is typically exhibited by equilibrium calculations. The actual response of the plasma inductance to changes in beta has yet to be quantified experimentally, and the use of an approximate, constant inductance is deemed appropriate. For a constant inductance, both energy and magnetic helicity (Sec. III.K.) are automatically conserved. For all magnetics calculations performed for the PFC set, the plasma is simulated by imposing a surface current at the plasma radius, r_p , equal to the toroidal plasma current, I_ϕ . Calculation of the plasma self-inductance and equilibrium are based on analytic expressions, which are expected to be adequate given the uncertainty in the plasma magnetic-field profiles. The means used to position the EFC and OHC conductors are described below.

Ohmic-Heating Coil (OHC). As noted in Fig. III.F-10, use of the OHC as an energy storage requires large currents to flow in these windings before the plasma is initiated. The OHC must produce a field distribution that excludes magnetic field from the plasma region. To determine the required OHC position, the coil current distribution is represented by a Fourier series¹³⁰ and evaluated along the coil gallery with an overall location being specified as input. The Fourier coefficients are then determined by a least squares minimization of the field produced inside the plasma by the OHC. The plasma is not incorporated into this calculation. The resultant continuous-current distribution is used to determine the positions of conductors carrying equal current. The correct OHC conductor positions for the reference design are shown in Fig. III.F-11, where 20 equal-current windings are energized with each carrying 0.9 MA. The continuous-current distribution represented by a Fourier series is integrated along the conductor surface and discretized into conductors carrying equal current in order to meet the 6.1-MA/m^2 requirement projected by

FLUX(10 Wb/line): $I_{\Phi_{EFOH}} = 0.0, 11.0, 0.0$ MA

FLUX(10 Wb/line): $I_{\Phi_{EFOH}} = 0.0, 0.0, 17.9$ MA

FLUX(10 Wb/line): $I_{\Phi_{EFOH}} = 18.4, 11.0, 17.9$ MA

Fig. III.F-11. OHC and EFC conductor locations showing plasma position and lines of constant poloidal flux (volts).

the parametric systems code (Table III.F-I). Equally spaced flux surfaces produced by this coil are also shown in Fig. III.F-11, where the exclusion of magnetic field from the plasma region gives essentially a constant flux in and near the plasma region.

To provide sufficient space at the outboard equatorial plane for vacuum-pumping ducts and FW/limiter/B/S coolant manifolding, solutions for the OHC set exclude any conductor from the outer 10 % of the PFC minor circumference. This ~ 1 -m gap is apparent in Fig. III.F-11. This gap only slightly perturbs the PFC solution because of the low density of OHC current in this outboard region.

Maximizing the mutual inductance between the OHC and plasma is also accomplished by locating the inboard OHC conductors as close to the plasma as allowed by the B/S/TFC radial build.

Equilibrium-Field Coil (EFC). The EFC system provides plasma equilibrium and a portion of the flux change needed to drive the plasma current. Toroidal plasma equilibrium requires the addition of a nearly uniform vertical field, B_v . The required quasi-uniform vertical field is^{131,132} approximately given below:

$$B_v = [\mu_0 I_\phi / 4\pi R_T] [\ln(8R_T/r_p) + 2\pi\ell_1/\mu_0 + \beta_\theta - 1.5] , \quad (9)$$

where ℓ_1 is the inductance per unit length of the plasma; for the RFP with Bessel-function field profiles, $2\pi\ell_1/\mu_0 = 0.5$. As seen from Eq. (9), the vertical field must vary approximately in direct proportion to the plasma current, I_ϕ . This approximation is modified by a correction term that varies only $\lesssim 10\%$ over the entire startup cycle. Using plasma parameters describing the burn ($I_\phi = 18.4$ MA, $\beta_\theta = 0.2$, $r_p = 0.71$ m, and $R_T = 3.8$ m), a vertical field of $B_v = 1.44$ T is predicted. In principle, the magnitude and distribution of the plasma current along with β_θ must be known at each point in time, with a corresponding vertical field consistently being calculated. A feedback system will ultimately be required, although the design of such a system remains as future work. The necessary magnetic-field energies along with a first-order determination of the time-dependent currents and voltages are calculated in Sec. III.F.2.c. for a system which achieves the desired $B_v = 1.44$ T during the plasma burn.

To provide plasma equilibrium in both the horizontal and vertical directions requires a vertical field curvature that is characterized by the following decay index:¹³³

$$n = \frac{\partial \ln B_v}{\partial \ln r} = \frac{R}{r_p} \frac{B(R - r_p) - B(R + r_p)}{B(R - r_p) + B(R + r_p)} , \quad (10)$$

with $0 < n < 1.5$. Constraining the plasma to a circular cross section further specifies¹³² $0 < n \lesssim 0.65$, which is the criterion used in this design.

An infinite number of solutions exist for the EFC positions needed to produce the correct vertical-field direction, magnitude, and decay index. The possible solution set is substantially reduced when fulfilling the conditions outlined in Fig. III.F-10. Minimizing the EFC current is accomplished by placing conductors outboard of the major plasma radius, R_p . Conductors located both above and below the midplane represent a short solenoidal coil in which a quasi-uniform vertical field exists. Currents in these coils also add to the current flowing in the OHC, thereby contributing to the flux drive required to induce the plasma current. Again, to determine the necessary coil positions, the coil current distribution is represented by a Fourier series¹³⁰ and evaluated along the specified continuous EFC location. The plasma current is represented as a surface current, I_ϕ , at the plasma radius, r_p . This current produces an inherent vertical field inside the radius, r_p . The Fourier coefficients are then determined by a least square minimization of the field produced by the EFC and the plasma inside the radius, r_p . The resultant continuous-current distribution represented by a Fourier series is integrated along the conductor surface and discretized into equal-current-carrying conductors. For the reference design, the proper EFC conductor positions are also shown in Fig. III.F-11, where 12 equal-current windings are each energized with 0.9 MA. Equally spaced flux surfaces also exhibit the required concavity of the vertical field in the plasma toward the inside of the torus. A decay index of $n = 0.53$ results, assuring a circular plasma in equilibrium according to the criterion outlined in Ref. 132. An EFC current of 11.0 MA produces the required vertical field ($B_v = 1.44$ T) during the long-pulsed or steady-state burn.

The EFCs are also excluded from the outer 10 % of the coil circumference to provide space for vacuum-pumping ducts and FW/limiter/B/S coolant manifolds. Since the EFC must produce a concave field, little EFC current would normally be present in this region. The EFC currents are specified only along the outer half-plane of the torus. Allowing EFC currents in the same direction along the inner half-plane of the torus actually subtracts from the vertical field, requiring the EFC current to increase. Additional OHC function is simply being integrated into the EFC and is a condition which is to be avoided. Localizing the EFC in the outer half-plane provides sufficient area to produce a uniform current along the minor circumference. Forcing this current to be more localized at a somewhat larger radius may lower the EFC current slightly,

although the localization of current slightly causes construction difficulties and forces the conductor center away from the plasma, thereby increasing the energy-storage requirements.

Combined OHC/EFC Magnetic Properties. Several important properties of the OHC/EFC may be discerned without knowledge of the means by which the system is to be electrically driven. Single-turn, self-, and mutual inductances are

TABLE III.F-IV
OHC/EFC SINGLE-TURN PROPERTIES

<u>PARAMETER</u>	<u>VALUE</u>
Self-Inductances (μH)	
• L_p	12.0
• L_{OH}	3.45
• L_{EF}	10.6
Mutual Inductances (μH)	
• $M_{OH,p}$	3.32
• $M_{OH,EF}$	3.35
• $M_{EF,p}$	5.91
Current Levels (MA)	
• I_ϕ	18.4
• I_{EF}	11.0
• ΔI_{OH}	46.8
Magnetic Fluxes (Wb)	
• Plasma	220.
• EFC	65.0
• OHC	155.
EFC Parameters	
• Flux change (Wb/MA turns)	5.91
• Effective coil radius, $R_{EF}(\text{m})$	4.87
• B_v (T) at R_T	1.44
• Field Index, n	0.53
OHC Parameters	
• Flux change (Wb/MA turns)	3.31
• Effective coil radius, $R_{OH}(\text{m})$	2.86
• Maximum field at startup (T, $I_{OH}^- = 28.9 \text{ MA}$)	7.9
• Stray field at r_p (T, $I_{OH}^- = 28.9 \text{ MA}$)	0.01

listed in Table III.F-IV for the PFC and EFC sets shown in Fig. III.F-11. The required plasma flux of $L_p I_\phi = 220$ Wb is partially provided by the EFC, $M_{EF,P} I_{EF} = 65.0$ Wb, and dictates the flux change associated with the OHC current swing, $M_{OH,P} \Delta I_{OH} = 155$ Wb. The flux surfaces for the final energized state with $I_\phi = 18.4$ MA, $I_{EF} = +11.0$ MA, and $I_{OH} = +17.9$ are also shown in Fig. III.F-11. In this particular case the total PFC current swings symmetrically from $I_{OH} = 28.9$ MA to $I_{EF} + I_{OH} = +28.9$ MA for purposes of minimizing the required electrical grid power, as discussed in Sec. III.F.2.c.

Also given in Table III.F-IV are the effective coil radii for both OHC and EFC sets. These radii are average values to be used in subsequent calculations of inductor volume (mass) and resistive losses. As will be shown, this improved estimate of PFC requirements is close to the coarser predictions of the parametric systems code¹⁵ (Table III.F-I) upon which this particular cost-optimized CRFPR design point is based.

c. PFC (OHC + EFC) Circuit Analysis. After the OHC and EFC conductor locations and the required total currents are defined, the operational sequence and required external driving elements remain to be determined. The PFC parameters remaining to be resolved include the time-dependent coil voltages, the conductor turns ratios, and the required conductor masses.

A simplified PFC circuit is shown in Fig. III.F-12, where single-turn parameter notation is used for illustrative purposes. The operational sequence is illustrated in Fig. III.F-13. The OHC is initially charged during the period τ_c to a total current I_{OH} , requiring a maximum grid power $P_{GRID} =$

Fig. III.F-12. PFC (OHC + EFC) circuit diagram showing mutual inductions.

Fig. III.F-13. PFC(OHC + EFC) operational sequence.

$V_{GRID} I_{OH}^-$. The OHC is then connected across the EFC set, and the plasma is simultaneously initiated while a transfer resistor, R_{TR} , is connected across the combined OHC/EFC sets. The plasma current exponentially increases according to the following expression:

$$I_{\phi}(t) = \frac{I_{OH}}{\Delta I_{OH}} I_{\phi} (1 - e^{-t/\tau_{EXP}}) , \quad (11)$$

with an initial current risetime being given by

$$\left(\frac{dI_{\phi}}{dt}\right)_{t=0} = \frac{I_{OH}^-}{\Delta I_{OH}} \frac{I_{\phi}}{\tau_{EXP}} . \quad (12)$$

The time constant τ_{EXP} is determined from experiment to give a desired initial current rise, dI_{ϕ}/dt . The resistive decay continues until $V_{OH} = V_{GRID}$, when $I_{\phi}(t) = I_{\phi}(\tau_R)$, and the grid voltage is again applied to drive the PFC system. Because the system is highly inductive, the plasma current at this point varies linearly according to

$$I_{\phi}(t) = [I_{\phi} - I_{\phi}(\tau_R)] \frac{(t - \tau_R)}{\tau_L} + I_{\phi}(\tau_R) , \quad (13)$$

as P_{GRID} linearly increases to $P_{GRID} = V_{GRID} (I_{OH}^+ + I_{EF})$. Minimizing P_{GRID} then requires $I_{OH}^- = I_{OH}^+ + I_{EF}$, which defines $I_{OH}^- = 28.9$ MA and $I_{OH}^+ = 17.9$ MA. The quantity of conductor present in the OHC and EFC circuit is determined by a balance that minimizes the recirculating power fraction during the plasma burn with the conductor mass and cost.

The results from the parametric systems code¹⁵ (Table II.F-I.) predicts an optimal conductor current density of 6.06 MA/m^2 , which is applicable to I_{EF} and I_{OH}^+ during the plasma burn. The final conductor sets listed in Table III.F-V and described in Sec. III.F.2.d. have current densities of 6.06 and 6.40 MA/m^2 for the EFC and OHC systems, respectively. The total conductor volume is 13 % more than predicted by the parametric systems code,¹⁵ and the recirculated power is approximately 24 % greater. The PFC system through the RFP dynamo is used to provide virtually all the toroidal-field energy internal to the plasma, requiring approximately a 10 % increase in the required flux change and accounting for the additional recirculated power.

The tradeoff between P_{GRID} , conductor splits, and OHC current swings involves an economic optimization, as is illustrated in Fig. III.F-14. The general approach that minimizes P_{GRID} while using the optimal conductor current density during the burn as predicted by the systems economics model presents a logical path for parameter selection, although increasing $P_{GRID} (I_{OH}^+)$ in favor of a lower recirculating power may be economically attractive depending on the

Fig. III.F-14. Schematic representation of economic tradeoffs involved in the definition of PFC drive and conductor parameters.

magnitude and availability of electrical grid power; this tradeoff cannot be specified quantitatively at this stage of the study.

Determination of the system voltages and coil turns ratio requires a complete circuit analysis. A matrix representation of the circuit, as illustrated in Fig: III.F-12, is given below:

$$\begin{bmatrix} V_{OH} \\ -i_{OH}\Omega_{OH}N_{OH}^2 \\ i_{OH}\Omega_{OH}N_{OH}^2 \\ -i_{EF}\Omega_{EF}N_{EF}^2 \\ -I_{\phi}\Omega_P \end{bmatrix} = \begin{bmatrix} N_{OH}^2L_{OH} & N_{OH}N_{EF}M_{OH,EF} & -N_{OH}M_{OH,P} \\ N_{OH}(N_{EF}M_{OH,EF} & N_{EF}(N_{EF}L_{EF} & (N_{OH}M_{OH,P} \\ -N_{OH}L_{OH}) & -N_{OH}M_{OH,EF}) & -N_{EF}M_{EF,P}) \\ -N_{OH}M_{OH,P} & -N_{EF}M_{EF,P} & L_P \end{bmatrix} \cdot \begin{bmatrix} \frac{di_{OH}}{dt} \\ \frac{di_{EF}}{dt} \\ \frac{dI_{\phi}}{dt} \end{bmatrix}, \quad (14)$$

where the turns ratios N_i ($i = EF, OH$) are included explicitly. Lead currents are represented by lower-case letters, i_{OH} and i_{EF} . The above equations, including a time-dependent of the plasma resistance, Ω_P , can be solved numerically as described in the following Sec. III.F.2.d. Since an efficient reactor requires large values of L_P/Ω_P , an accurate analytic representation of the startup transient can be derived by taking Ω_P , Ω_{OH} , and Ω_{EF} to be small. The system voltage, V_{OH} , under these conditions is given by

$$V_{OH} = N_{OH} \left\{ \frac{L_{OH}}{M_{OH,P}} \left[L_P - \left(\frac{I_{EF}}{I_{\phi}} \right) M_{EF,P} \right] + M_{OH,EF} \left(\frac{I_{EF}}{I_{\phi}} \right) - M_{OH,P} \right\} \frac{dI_{\phi}}{dt}. \quad (15)$$

Enforcing the equilibrium condition defined by Eq. (9) requires the ratio I_{EF}/I_{ϕ} to be approximately constant. Using this condition directly couples V_{OH} with N_{OH} and dI_{ϕ}/dt . As seen in Fig. III.F-13, the maximum voltage, V_{MAX} , occurs at the beginning of the resistive decay. Using Eq. (11) for the plasma current transient and taking $\tau_{EXP} = 0.34$ s yields an experimentally characteristic initial plasma current rise of $dI_{\phi}/dt = 33$ MA/s for this current pulse; Eq. (15) gives $N_{OH} = 100$ if the coil voltage is to remain below 25 kV, which is an engineering constraint imposed by this study.

Requiring the EFC to be connected across the OHC during the startup transient eliminates the need for a separate power supply and forces a specific relationship between N_{EF} and N_{OH} . Again, with all resistances small, Eq. (13) gives the following relationship between N_{EF} and N_{OH} .

$$\frac{N_{EF}}{N_{OH}} = \frac{\frac{L_{OH}}{M_{OH,p}} [L_p - (\frac{I_{EF}}{I_\phi}) M_{EF,p}] + M_{OH,EF} (\frac{I_{EF}}{I_\phi}) - M_{OH,p}}{\frac{L_{OH,EF}}{M_{OH,p}} [L_p - (\frac{I_{EF}}{I_\phi}) M_{EF,p}] + L_{EF} (\frac{I_{EF}}{I_\phi}) - M_{EF,p}}, \quad (16)$$

which for a constant ratio I_{EF}/I_ϕ defines the EFC turns ratio. The maximum conductor lead current for both coil sets are then listed in Table III.F-V.

With the turns ratio N_{OH} and N_{EF} specified from Eq.(16) to be $N_{EF}/N_{OH} = 0.83$, the charging electrical-grid voltage, V_{GRID} , is determined from the maximum imposed electrical power, $P_{GRID} = V_{GRID} i_{OH}^-$, with the charge transient being described by the following expression:

$$i_{OH} = \frac{P_{GRID}}{i_{OH}^- N_{OH} \Omega_{OH}} (1 - e^{-\Omega_{OH} t / L_{OH}}). \quad (17)$$

Because of the long charging transient, this latter expression must properly include the effect of the OHC resistance, Ω_{CH} . For $P_{GRID} = 350$ MWe and $V_{GRID} = 1,200$ V, the OHC current achieves i_{OH}^- in $\tau_c = 0.49 L_{CH} / \Omega_{OH} = 10.5$ s. From Eq. (15), the resistive transient occurs from $V_{OH} = 25,000$ to $1,200$ V in $\tau_R = 3.04 \tau_{EXP} = 1.03$ s as the plasma current increases to $I_\phi(\tau_R) = 10.8$ MA. Finally, using Eq. (13), $dI_\phi/dt = [I_\phi - I_\phi(\tau_R)]/\tau_L$, and V_{GRID} in Eq. (15), the final rise of the current occurs during $\tau_L = 4.69$ s. All coil parameters are summarized in Table III.F-V and are used in Sec. III.L. in support of the FPC integration. Figure III.F-15 depicts the CRFPR coil cross sections and locations that have emerged from this equilibrium and startup analyses; a comparison with the TFTR cross section is also given.

Fig. III.F-15. CRFPR coil locations and sizes predicted by startup and equilibrium analyses.

d. Resistive PFC Numerical Circuit Analysis. Inclusion of plasma and coil resistances in the PFC circuit considerably complicates the analytic circuit modeling, requiring a numerical analysis. This analysis is rigorously accomplished by coupling the PFC circuit shown in Fig. III.F-12 to the plasma simulation model, as described in Sec. III.G. and Appendix A. Using the PFC inductance parameters listed in Table III.F-IV and the coil resistances and turns ratios given in Table III.F-V, the complete system of circuit equations listed in Eq. (14) can be evaluated. The plasma resistance, Ω_p , is computed as a function of time as the plasma temperature, density, and associated profiles vary during the startup phase (Appendix A). Because the total plasma resistive heating resulting from the poloidal, I_θ , and toroidal, I_ϕ , current is supplied by the PFC circuit through the RFP dynamo effect, the total ohmic power input defines Ω_p from the relationship $P_\Omega = I_\phi^2 \Omega_p$.

TABLE III.F-V
OHC/EFC CIRCUIT AND CONDUCTOR CHARACTERISTICS ($\Omega_p \rightarrow 0$)^(a)

<u>PARAMETER</u>	<u>VALUE</u>
Electrical Grid Requirement	
• Maximum power, $P_{\text{GRID}}(\text{MWe})^*$	350.
• Voltage, $V_{\text{GRID}}(\text{V})$	1,200.
EFC Characteristics	
• Turns, N_{EF}	83.
• Maximum lead current, $i_{\text{EF}}(\text{MA})$	0.131
• Maximum voltage, $V_{\text{MAX}}(\text{V})^*$	$2.5(10)^4$
• Average coil current density (MA/m^2)*	6.1
• Conductor filling fraction, λ_c^*	0.7
• Single-turn resistance, ^(b) ohm	$4.7(10)^{-7}$
• Dissipated power, P_{EFC}^{Ω} at $i_{\text{EF}}(\text{MWe})$	53.5
OHC Characteristics	
• Turns, N_{OH}	100
• Maximum lead current, $i_{\text{OH}}^+(\text{MA})$	0.025
• Maximum voltage, $V_{\text{MAX}}(\text{V})^*$	$2.5(10)^4$
• Average coil current density (MA/m^2)*	6.4
• Conductor filling fraction, λ_c^*	0.7
• Single-turn resistance, ^(b) ohm	$1.61(10)^{-7}$
• Dissipated power, $P_{\text{OHC}}^{\Omega}(\text{MWe})$ at i_{OH}^+	51.6
Circuit Timing	
• Charge time, $\tau_c(\text{s})$	10.5
• Experimental risetime, $\tau_{\text{EXP}}(\text{s})^*$	0.34
• Initial plasma rise, $\tau_R(\text{s})$	1.03
• Final plasma rise, $\tau_L(\text{s})$	4.69

*Input parameters.

(a) As shown in Sec. III.F.2.d., including a finite plasma resistance requires a 17 % increase in OHC current swing and a 42 % increase in OHC power consumption (73.0 MWe).

(b) Copper resistivity taken as $1.8(10)^{-8}$ ohm m.

After the electrical proper ties of the PFC circuit are defined, the reactor startup proceeds as described in Sec. III.G. To facilitate comparisons between nonresistive and resistive solutions to this simulation problem, a maximum grid power of 350 MWe and a coil voltage of 25 kV are specified, as used for the analytical solution given in Sec. III.F.2.c. Inclusion of plasma resistance requires additional poloidal flux change to achieve the desired plasma current ($I_\phi = 18.4$ MA). Since the EFC current is constrained to 11.0 MA-turns for equilibrium purposes, the additional resistive volt-seconds must be supplied from the OHC current swing.

The necessary external power supply requirements are best met if $I_{OH}^- = I_{OH}^+ + I_{EF}$; that is, the back-biased OHC current, I_{OH}^- , equals the total PFC current during the burn. For the ideal case of no plasma resistance, these currents are determined to be I_{OH}^- , I_{OH}^+ , $I_{EF} = 28.9$, 17.9, 11.0 MA-turns, respectively. Since the resistive volt-seconds are not known prior to startup, the desired symmetric current swing must be found by iteration. A representative reactor startup, including all resistances, is shown in Fig. III.F-16. The plasma, EFC, and OHC current swings are shown along with the voltage applied to the PFC circuit. A summary of key circuit parameters is given in Table III.F-VI.

The OHC is initially charged to -33.5 MA-turns in 16.3 s by the 350-MWe, 1.03-kV supply. Simultaneously paralleling the OHC and EFC while initiating the plasma, a 0.0735-ohm transfer resistor crowbars the PFC system. The peak initial coil voltage of 25 kV induces an initial plasma current rise of approximately 32 MA/s. This resistive transfer continues for a time $\tau_R = 1.2$ s until the coil voltage equals the power supply voltage (1.03 kV). Under constant voltage the external power, P_{PFC} , supplied to the PFC increases approximately linearly to a maximum of 350 MWe, as is shown in Fig. III.F-17. The slow increase in plasma current occurs over a period of $\tau_L = \sim 8$ s until the full ~ 18.4 -MA plasma current is initiated (9.2 s). Finally, a power crowbar supply of ~ 150 MWe at 436 V is used to maintain the plasma current. This power supplies the OHC and EFC resistive losses, 73.0 and 53.5 MW, respectively, and the ohmic plasma loss of 24.5 MW during the steady-state burn. The OHC current must be slowly increased to compensate for the resistive flux loss of 1.3 Wb/s unless a plasma current-drive mechanism is imposed, in which case the OHC current (and power consumption) is allowed to decay to zero.

Fig. III.F-16. Representative plasma startup transient, showing plasma, EFC and OHC currents and voltages for the baseline case simulation described in Sec. III.G.

Comparing the analytic result given in Table III.F-V to the resistive-plasma startup listed in Table III.F-VI, the additional resistive 26 Wb requires a 17 % increase in the OHC current swing. Using the same coil set in both cases, this increased current swing inflates the recirculating power requirement from 51.6 to 73.0 MWe during the burn. An external current-drive mechanism (i.e., F- θ pumping, Sec. III.K.) may allow the OHC current to be reduced slowly to zero as the burn proceeds. The OHC is used only for inducing the plasma current and serves no equilibrium function. This coil could also be swung more negatively when initially charged to minimize recirculating power during the burn, although the magnetic field at the conductor would exceed the present value of 9.15 T at 33.5 MA-turns.

The plasma current trajectory during the resistive decay phase is similar for both resistive and nonresistive solutions. The initial plasma current rise to ~12 MA requires only 1.2 s, which compares to the 1.03 s calculated

TABLE III.F-VI

OHC/EFC CIRCUIT CHARACTERISTICS WITH FINITE PLASMA RESISTANCE, Ω_p

<u>PARAMETER</u>	<u>VALUE</u>
Flux requirements (Wb)	
• Total inductive	220.
• Total resistive	26.
• EFC	65.
• OHC	181.
Current levels (MA-turns)	
• Plasma current, I_ϕ	18.4
• Equilibrium-field coil, I_{EF}	11.0
• Ohmic-heating-coil swing, ΔI_{OH}	54.8
• Initial dI_ϕ/dt (MA/s)	32.0
Electrical-grid requirements	
• Maximum power, P_{GRID} (MWe)	350.
• Voltage, V_{GRID} (kV)	1.03
• Sustainment voltage at start of burn (kV)	0.436
• Recirculating power at start of burn, P_{PFC} (MWe)	151.
- OHC	73.0
- EFC	53.5
- Plasma	24.5
Transfer resistor	
• Resistance (ohms)	0.0735
• Maximum voltage (kV)	25.
Circuit timing (s)	
• Charge time, τ_C	16.3
• Initial plasma risetime, τ_R	1.2
• Final plasma risetime, τ_L	8.0

analytically. The continued rise of the plasma current to the design value requires ~ 8 s, which is significantly longer from a volt-seconds viewpoint, than the analytic value of 4.7 s resulting from the resistive drag of the OHC, EFC, and plasma on the 350-MWe power supply.

The PFC locations, sizes, and masses, as depicted on Fig. III.F-15, are summarized on Table III.F-VII according to EFC or OHC functions. Physical details of the OHC and EFC used in the analytic and numerical startup

Fig. III.F-17. Power transient on PFC and TFC during the ohmic startup transient toward ignition.

calculations are given in Table III.F-VII. The total coil cross sections are given, although individual coil cross sections vary according to available space. This difference is particularly true for the OHC, where limited space at the inside of the torus forces the current density to peak near the interior and to be reduced a factor of ~ 2 in the outer coils, which in turn are correspondingly more important from the viewpoint of power consumption because of the factor-of-three greater circumference. The OHCs are connected electrically as five-turn coils in series to give a total of 100 turns.

The EFC is listed in Table III.F-VIIB as having 80 turns, which compares to 83 turns calculated from the analytic solution. Enforcing plasma equilibrium, the ratio of EFC current to plasma current must be $I_{EF}/I_\phi \approx 0.60$ throughout the startup transient. For a purely inductive discharge (analytic), this requirement is enforced by $N_{EF} = 83$. The tracking accuracy in the numerical simulation, however, depends upon both the plasma and EFC resistance. For $N_{EQ} = 83$, the equilibrium coil current accurately tracks the plasma current

TABLE VII.F-VII
PFC COIL PARAMETERS FOR REFERENCE DESIGN

OHC SET	R (m)	z (m)	δ_c (m)	Δz (m)	Area (m ²)	Volume (m ³)	Mass (tonne)	Resistance ($\mu\Omega$)
1	2.050	0.100	0.500	0.200	0.100	1.29	9.5	3.31
2	2.050	0.300	0.500	0.200	0.100	1.29	9.5	3.31
3	2.100	0.512	0.500	0.225	0.112	1.48	10.9	3.02
4	2.175	0.740	0.500	0.230	0.115	1.57	11.5	3.06
5	2.300	0.975	0.500	0.237	0.119	1.71	12.6	3.14
6	2.500	1.225	0.500	0.262	0.131	2.06	15.1	3.08
7	2.800	1.495	0.500	0.275	0.138	2.42	17.8	3.29
8	3.212	1.712	0.325	0.512	0.166	3.36	24.6	3.12
9	3.837	1.887	0.325	0.600	0.195	4.70	34.5	3.18
10	5.450	1.300	0.450	0.450	0.202	6.93	50.9	4.35
(11-20)		(-z)						
EFC SET								
1	4.175	1.725	0.350	0.437	0.153	4.01	29.4	4.41
2	4.512	1.625	0.325	0.450	0.146	4.15	30.4	4.98
3	4.812	1.500	0.275	0.500	0.138	4.16	30.5	5.65
4	5.087	1.325	0.275	0.500	0.138	4.39	32.3	5.98
5	5.385	0.969	0.713	0.212	0.151	5.11	37.5	5.76
6	5.511	0.744	0.695	0.237	0.165	5.70	41.9	5.41
(7-14)		(-z)						
<u>Integrated parameters</u>				<u>Value</u>				
Total current in 20 OHCs (MA)				21.1				
Total current in 12 EFCs (MA)				11.0				
Coil density, ρ_c (tonne/m ³)				7.34				
Total mass of OHCs (tonne)				394				
Total mass of EFCs (tonne)				404				

TABLE III.F-VIIA
PHYSICAL PARAMETERS OF POLOIDAL-FIELD COILS (OHC SET)

<u>PARAMETER</u>	<u>VALUE</u>
Number	20
Coil cross section (m ²)	2.8
Total coil volume (m ³)	53.9
Total coil mass (tonne)	394.
Conductor filling fraction, λ_c	0.7
Total number of turns	100
Resistance (ohms)	0.0016
Maximum applied voltage (kV)	25.
Peak back-bias values ($I_\phi = 0.0$ MA)	
• Lead current (MA)	0.335
• Average coil current density (MA/m ²)	12.0
• Dissipated power (MWe)	180.
• Maximum stored energy (MJ)	2000.
• Maximum magnet coil field (T)	9.12
• Maximum stray field at plasma (T)	0.013
Start-of-burn values ($I_\phi = 18.4$ MA)	
• Lead current (MA)	0.213
• Average coil current density (MA/m ²)	7.7
• Dissipated power (MWe)	73.0
• Maximum magnet coil field (T)	4.5

during the resistive startup phase (< 1.2 s) and drifts to $I_{EF}/I_\phi \approx 0.545$ at the end of startup (~ 10 s). Adjusting N_{EF} to 80 turns gives I_{EF}/I_ϕ ranging from 0.627 to 0.57 at the beginning and end of the startup, respectively, with the equilibrium being tracked to within $\pm 5\%$. In any case, a separate equilibrium feedback system would ultimately be required to match closely the necessary equilibrium current.

TABLE III.F-VIIB

PHYSICAL PARAMETERS OF THE POLOIDAL-FIELD COILS (EFC SET)

<u>PARAMETER</u>	<u>VALUE</u>
Number	12
Total coil cross section (m^2)	1.8
Total coil volume (m^3)	55.5
Total coil mass (tonne)	405.
Conductor filling fraction, λ_c	0.7
Total number of turns	80.0
Resistance (ohms)	0.0028
Maximum applied voltage (kV)	25.
During-the-burn values ($I_\phi = 18.4$ MA)	
• Lead current (MA)	0.135
• Average coil current density (MA/m^2)	6.05
• Dissipated power (MWe)	53.5
• Maximum magnet coil field (T)	4.5

G. Plasma and Circuit Simulation

The parametric systems evaluation given in Ref. 15, as updated and summarized in Sec. II.D.2., has provided the guidance and basis for this design study. An accurate modeling and assessment of reactor startup and operation, however, remains to be performed. Using the economically optimal design point listed in Table II.D-III as a reference, a burn simulation was performed using the CRFPR plasma simulation and systems code described in Appendix A. This time-dependent model couples the external electrical driving circuit to the plasma. A complete analysis of the PFC circuit described in Sec. III.F. is performed by the simulation code, which includes the plasma as a nonlinear circuit element.

The plasma simulation code is based on a multiparticle, time-dependent burn computation that accounts for magnetic-field and plasma profiles by performing integral averages over the plasma cross section at selected time intervals. Experimentally derived plasma profiles and transport properties are used to generate self-consistent plasma equilibrium configurations. These profiles, transport properties, and equilibrium configurations are adjusted as the DT/DD-fueled burn proceeds. The suprathermal (non-Maxwellian) plasma species (H, D, T, ^3He , and ^4He) are described by a Fokker-Planck formalism (Appendix A), with the Maxwellian component being subtracted from each slowing-down distribution and merged into a single background ion population. A complete time history of all profile-averaged plasma quantities for both DD- and DT-fueled discharges is generated. The resultant power output impinges on a two-region first-wall surface, and one-dimensional (cylindrical) temperatures and stresses are calculated as a function of time. An overall power-plant energy balance is evaluated as the reactor achieves steady-state operation.

The magnetic-field profiles are calculated from a one-dimensional plasma equilibrium that is consistent with plasma temperature, density and current-density profiles. The magnetic-field structure may be approximated analytically using a force-free model (i.e., no plasma pressure), giving $\vec{\nabla} \times \vec{B} = \mu_0 \vec{j} \equiv \mu(r) \vec{B}$. If the scalar $\mu(r) \equiv \mu_0 \vec{j} \cdot \vec{B} / B^2$ is independent of plasma minor radius, the Bessel-function model (BFM) results, where $B_\phi = A_\phi J_0(\mu r)$, $B_\theta = A_\theta J_1(\mu r)$, and A_ϕ and A_θ are constants to be determined. As derived in Appendix A, the pinch parameter, $\theta \equiv B_\theta(r_p) / \langle B_\phi \rangle$, relates μ , A_θ , and A_ϕ according to $\theta = (\mu r_p / 2)(A_\theta / A_\phi)$, where $A_\theta = A_\phi$ for the force-free, $\beta_\theta = 0$ BFM. It is noted that the plasma radius, r_p , is taken at the zero-temperature

boundary, and hence, $r_p \approx r_w$. The pinch parameter and reversal parameter, $F = B_\phi(r_p)/\langle B_\phi \rangle$, in this case, are then related as follows:

$$F = \theta \frac{J_0(2\theta)}{J_1(2\theta)}. \quad (1)$$

Equation (1) is plotted in Fig. III.G-1 and represents the near-minimum-energy, $\beta = 0$, Taylor state described in Sec. II.D.1. Presuming the magnetic fields can be approximately represented by Bessel functions when pressure is added, the relationship $\vec{\nabla}p = \vec{\nabla} \times \vec{B} \times \vec{B}$ gives $\beta_\theta = 1.0 - (A_\theta/A_\phi)^2$, and the pressure profile can be shown to be proportional to $J_0^2(\mu r)$. The minimum-energy relationship between F and θ is now modified by replacing θ with $\theta(1 - \beta_\theta)^{1/2}$ in Eq. (1). This " β -modified BFM" is plotted for $\beta_\theta = 0.25$ in Fig. III.G-1 but is only approximate because the perpendicular components of plasma current have been ignored for the assumed BFM field profiles.

The self-consistent calculation described in Appendix A integrates across the field profiles and estimates the equilibrium profiles using the Maxwell equations. The experimentally derived and extrapolated temperature and density profiles are taken as $n(r) \propto T(r) \propto J_0(\mu r)$. This parabolic-like profile yields $T_0/T = 1.6$ and $n_0/n = 2.3$, where the subscripts denote centerline values, and n and T are averaged over the plasma cross section. The spatial dependence of $\mu(r)$ is chosen to fit experimental toroidal magnetic flux and magnetic fields measured⁷⁴ at the discharge chamber wall of ZT-40M. This "Best-Fit Model" uses a constant- μ profile up to a breakpoint at $r = \alpha r_p (\alpha < 1)$, beyond which $\mu(r)$ is linearly extrapolated to zero as r approaches r_p ; the large currents at the plasma edge required by the constant- μ BFM are thereby avoided. The expressions describing this model are given in Appendix A [Eq.(A-56)]. The F - θ trajectory for $\beta_\theta = 0$ and 0.25 is also plotted in Fig. III.G-1 for the Best-Fit Model along with the numerically computed burn trajectory, the latter being bounded by the two curves for the Best-Fit Model.

Use of the aforementioned profile assumptions results in the current-density profiles plotted in Fig. III.G-2 at the operating current of $I_\phi = 18.4$ M.A. The linear extrapolation of the current density to zero is apparent for the burn case shown, which operates at $\theta = 1.55$, $F = -0.12$, and $\beta_\theta = 0.23$. These plasma current densities produce the toroidal and poloidal

Fig. III.G-1. F- θ or Taylor diagram showing the relationship between $F = B_{\phi}(r_p)/\langle B_{\phi} \rangle$ and $\theta = B_{\theta}(r_p)/\langle B_{\phi} \rangle$, the reversal and pinch parameters, respectively, for the BFM as well as for the "Best-Fit Model." The effects of finite beta are also shown.

magnetic fields plotted in Fig. III.G-3, which are similar to Bessel functions $B_{\phi} \propto J_0(\mu r)$ and $B_{\theta} \propto J_1(\mu r)$. Definition of the plasma profile characteristics allows equilibrium configurations to be generated and updated as the startup proceeds and the plasma approaches an ohmic ignition.

The reactor-operating scenario is illustrated in Fig. III.F-6, where an initially uniform, vacuum toroidal field of 0.6 T is trapped inside the plasma upon initial formation. This initial toroidal field is chosen to be similar to the final value upon reversal in order to minimize engineering demands on the TFC system. The initial, tokamak-like condition corresponds to $F = 1$ and $\theta \approx 0$ on the F- θ diagram (Fig. III.G-1). As the plasma current increases to approximately 20 % of the final value at 0.13 s, the magnetic-field structure within the plasma is assumed to achieve the final reversed-field state with $\theta = 1.55$ and $F = -0.12$ (Fig. III.G-1). Additional internal toroidal flux is assumed to be provided by the dynamo effect as the toroidal plasma current is increased to $I_{\phi} = 18.4$ MA.

Fig. III.G-2. Current-density profiles for the $I_\phi = 18.4$ -MA design-point simulation once steady-state is (Fig. III.G-1) achieved.

The reactor-operating scenario was described in Sec. III.F., where an analytic PFC circuit analysis was performed without including coil or plasma resistances. The plasma simulation and systems model incorporates the magnet-coil and plasma resistances, and the resultant voltage and current transients are given in Fig. III.F-16. An extended plot of the plasma current is given in Fig. III.G-4. The precharged OHC is resistively crowbarred while simultaneously initiating the plasma discharge and connecting the EFC across the OHC circuit. Approximately 2/3 of the initially stored energy is dissipated in the transfer resistor while the plasma current rises from zero to ~ 12 MA in 1.2 s. The rapid initial current transient of 32 MA/s is limited only by the voltage allowed on the PFC system (≤ 25 kV). The initial transient is sufficient to overcome the rapid transport losses expected for a low-temperature plasma ($\tau_E \propto I_\phi^2 r_p^2 \propto T r_p^2$). As the plasma temperature is increased, the plasma current rise can occur more slowly because of the decreased resistance and the highly inductive nature of the circuit configuration. This operational sequence minimizes the power supply requirements for startup.

Fig. III.G-3. Magnetic-field profiles for the $I_\phi = 18.4\text{-MA}$ design-point simulation, corresponding to the current densities depicted on Fig. III.G-2.

In response to the plasma current rise plotted in Fig. III.G-4, the plasma ion and electron temperatures are expected to increase to a final operating temperature near 10 keV through ohmic dissipation as the startup phase is completed. The density refueling rate and particle/energy transport are important in determining this temperature transient. Attributing the predominant energy loss to anomalous electron conduction, τ_{ce} , a fit to ZT-40M data ($\tau_{ce} \sim 0.2 \text{ ms}$, $I_\phi = 0.12 \text{ MA}$, $r_p = 0.2 \text{ m}$, $\beta_\theta = 0.1\text{-}0.15$) gives a $\tau_{ce} \propto I_\phi^\nu r_p^2$ scaling (Fig. II-13), where ν is < 1.0 , but theoretically can approach 1.5. The following scaling is adopted for this study:

$$\tau_{ce} \approx 5(10)^{-8} I_\phi r_p^2 f(\beta_\theta), \quad (2)$$

where the function $f(\beta_\theta)$ is given by

Fig. III.G-4. Expanded plot of plasma current transient.

$$f(\beta_\theta) = \begin{cases} 1.0 & , \beta_\theta < \beta_{\theta c} \\ (0.13/\beta_\theta)^2 & , \beta_\theta > \beta_{\theta c} \end{cases} \quad (3)$$

The function $f(\beta_\theta)$ is chosen to decrease τ_{ce} as a critical experimental value of $\beta_{\theta c} = 0.13$ is exceeded. As discussed in Appendix A, the beta saturation effects on τ_{ce} exhibited by tokamak neutral-beam-heated experiments³⁹ are assumed to apply also for the RFP. Also indicated by ZT-40M experiments is the particle confinement time, which is taken as $\tau_{pi} \approx 4\tau_{ce}$; the ion-conduction time is taken as $\tau_{ci} \approx \tau_{pi}$. Plotted in Fig. III.G-5 are the electron-conduction, $1/\tau_{ce}$, and ion-particle, $1/\tau_{pi}$, loss rates as well as the inverse of the total plasma energy confinement time, $1/\tau_E$, which includes both conduction and radiative losses. Also shown for comparison purposes are the classical ion-conduction time, τ_{CLASS} , and the characteristic ohmic-scaling time, τ_{OHM} , explicit expressions for both being given in Appendix A. The plasma energy and particle times increase in direct proportion to the plasma current until increases in the

poloidal beta exceeds the critical value, $\beta_{\theta c} = 0.13$, which as shown in Figs. III.G-5 and III.G-6, reduces the confinement times. The total energy confinement time during the burn is only $\tau_E \approx 0.24$ s with the electron-conduction time being $\tau_{ce} \approx 0.15$ s at $\beta_\theta = 0.23$.

The electron and ion density trajectories are given in Fig. III.G-7, where a starting density of $0.708(10)^{20} \text{ m}^{-3}$ (1-mtorr filling pressure) is increased to $6.56(10)^{20} \text{ m}^{-3}$ during the startup transient. The fueling algorithm used in this simulation attempts to maintain a constant value of j_ϕ/n or I_ϕ/N , where $N = \pi r_p^2 n$ is the plasma line density. The operating value of I_ϕ/N during the steady-state burn is $1.73(10)^{-14} \text{ A m}$, which corresponds to an electron-streaming parameter of $\xi = v/v_{TH} \approx 0.08$. The deuterium, S_D , and tritium, S_T , fueling rates are constrained to never exceed the instantaneous particle loss rate by at least 30 % according to the following function:

Fig. III.G-5. Dependence of electron-, ion-, and particle-conduction, times during the reactor startup using the scalings indicated by Eq. (III.G-2). The total confinement time includes both conduction and radiative ($Z_{eff} = 1$) losses.

Fig. III.G-6. Time dependence of poloidal beta during the plasma startup transient.

$$S_D = S_T = 1.3 \frac{N_1}{2\tau_{pi}}, \quad N_1 < 0.9737N_V \quad (3A)$$

$$S_D = S_T = \frac{N_1}{2\tau_{pi}} \exp[10(1 - N_1/N_V)] \quad N_1 > 0.9737N_V, \quad (3B)$$

where $N_V \equiv I_\phi / (I_\phi/N)_B$ and $(I_\phi/N)_B$ is the target value during the steady-state burn. The exponential factor of 10 assumes the final line density will closely adhere to the desired value, N_V , and the factor 0.9737 simply assures a

Fig. III.G-7. Time dependence of the electron and ion density during the plasma startup transient fueling algorithm given by Eqs. (III.G-3).

continuous fueling function. This fueling algorithm avoids large instantaneous and possibly unphysical fueling rates which may result when enforcing a strictly constant value of I_ϕ/N . For a major part of the startup trajectories reported here, the fueling rate is usually operating at this constraint rather than holding I_ϕ/N constant at the steady-state burn conditions. The resultant values of I_ϕ/N and streaming parameter, ξ , are plotted in Fig. III.G-8 as a function of time, with the peak occurring as the initial, rapid current rise nears $I_\phi = 12 \text{ MA}$ (Fig. III.G-4). Experimental results on ZT-40M are optimal if $I_\phi/N < (1-2)10^{-13} \text{ A m}$, above which a runaway condition may result for $T_e \approx 250\text{-eV}$ ZT-40M conditions, or the streaming parameter ξ may become too large, causing excessive resistance through streaming instabilities. The operating range of $I_\phi/N = 1.5-6(10)^{-14} \text{ A m}$ during startup is typical of ZT-40M experimental discharges.

Fig. III.G-8. Time dependence of I_ϕ/N and streaming parameter ξ during the plasma startup transient for the fueling algorithm given by Eqs. (3).

The product of particle inventory and plasma energy confinement yields a single confinement parameter, $n\tau_E$, which is plotted in Fig. III.G-9. A confinement parameter of $\sim 2(10)^{20} \text{ s/m}^3$ is required to initiate the discharge ohmically using the refueling algorithm described by Eqs. (III.G-3) for $Z_{\text{eff}} = 1.0$. The maximum value of $n\tau_E$ required during ohmic startup is affected by the fueling scheme and the associated density increase and, therefore, is considered representative of a range of startup options. The value of $n\tau_E \approx 1.6(10)^{20} \text{ s/m}^3$ at ignition/burn is also considered only as representative in that $n\tau_E$ depends on density and temperature profiles.¹⁵ It is noted that the global $n\tau_E$ for the STARFIRE tokamak reactor design is $0.64(10)^{20} \text{ s/m}^2$, where τ_E is the total plasma energy divided by total plasma heating power (alpha-particle plus rf power).

Fig. III.G-9. Time dependence of the confinement parameter, $n\tau_E$, during the plasma startup transient for the fueling algorithm given by Eq. (III.G-3).

The plasma temperature transients shown in Fig. III.G-10 exhibit an initially rapid rise in electron temperature in response to the increase in plasma current and ohmic-heating power. The damped oscillation in $n\tau_E$ and $T_{e,i}$ are a result of the primitive fueling algorithm used as well as the physics associated with alpha-particle thermalization and transport (beta) dynamics. The variation in plasma temperature is driven by the plasma powers plotted in Fig. III.G-11, which shows the total charged-particle fusion power, P_Q , as well as the conduction, P_{COND} , ohmic, P_{OHM} , bremsstrahlung, P_{BR} , and (insignificant) cyclotron, P_{CYC} , powers. The initial separation between ion and electron temperature results from the low rate of equipartition when the plasma density is low. As the density increases, this temperature difference diminishes, although dominant electron heating from both ohmic and alpha-particle deposition always maintain $T_e > T_i$. As the current and plasma density increase, the alpha-particle heating power steadily increases until $P_Q > P_{OHM}$ at 6 s into the startup transient and ignition is achieved. This initial transient toward

Fig. III.G-10. Time dependence of the average ion and electron temperatures during the plasma startup transient.

ignition occurs with a nearly constant beta, as is seen from Fig. III.G-6. The rapidly increasing alpha-particle heating power forces the beta to increase, which in turn increases the transport loss [Eq. (2)]. A highly damped plasma temperature oscillation occurs as the rapid temperature increase is overcome by the enhanced transport. A steady-state burn is achieved at 9.5 s after plasma current initiation.

The Fokker-Planck slowing-down model includes the effects of the energetic (non-Maxwellian) particles in the burn simulation. In addition to heating, the plasma energetic particles contribute to the plasma beta without producing significantly useful fusion power. The temperatures of the energetic species (T, D, ^3He , α , H) are plotted in Fig. III.G-12, with essentially no energetic deuterium assumed to be present (Appendix A). Only the energetic alpha particles are important for this DT burn, as is shown in Fig. III.G-13. During the steady-state burn, these 850-keV alpha particles are only $3(10)^{-3}$ of the total plasma ion population but contribute to 12.7 % of the total plasma

Fig. III.G-11. Time dependence of plasma powers during the plasma startup transient for the fueling algorithm given by Eqs. (3).

pressure. Maxwellian alpha particles are also present in the plasma at a concentration of 2.5 % (Fig. III.G-13) and contribute 3.7 % of the plasma pressure, including the added electrons. The percentage of the total pressure that is parasitic is 16.5 % and requires the target plasma beta to be inflated from the 0.20 design value to the plasma burn value of 0.233. An apparent advantage of operating at high plasma density is the relatively low resultant concentration of suprathreshold particles. Low-density plasma burns⁵² often have parasitic energetic-particle pressure contributions in excess of 30 %.

The primary goal of the plasma-simulation study is the verification and/or adjustment of the CRFPR operating parameters suggested by the earlier studies.¹⁵ Table III.G-I repeats Table II.D-III and includes the results from the more-detailed simulations. The parameters listed in Table III.G-I under "Burn Simulation Reference" are adopted hereafter for the FPC integration study given in Sec. III.L.

TABLE III.G-I

KEY PHYSICS AND ENGINEERING PARAMETERS FOR THE $P_E = 1000$ -MWE
 MINIMUM-COE CASES GIVEN IN TABLE II.D-III
 UPDATED USING THE TIME-DEPENDENT PLASMA/FPC SIMULATION CODE

	REF. 15		BURN
PLASMA PARAMETERS	DESIGN ^(a)	UPDATE ^(b)	SIMULATION REFERENCE
Minor plasma radius (m)	0.71	0.71	0.71
Major plasma radius (m)	4.30	3.79	3.80
Plasma aspect ratio	6.06	5.37	5.35
Plasma current (MA)	18.5	18.4	18.4
Toroidal current density (MA/m ²)	11.7	11.8	11.6
Plasma ion density (10 ²⁰ /m ³)	3.37	3.39(6.56)	6.55
Plasma ion temperature (keV)	20.0	20.0(10.0)	10.0
Lawson parameter (10 ²⁰ s/m ³)	0.79	0.79(1.51)	1.54
Energy confinement time (s)	0.23	0.23	0.23
Alcator coefficient (10 ⁻²¹ s m)	1.37	1.37(0.71)	0.70
Poloidal beta	0.20	0.20	0.23
Theta parameter	1.45	1.45	1.55
Reversal parameter	-0.20	-0.20	-0.12
Plasma/first-wall radius ratio	0.95	0.95	0.95
Plasma current/line density (10 ⁻¹⁴ A m)	3.47	3.47(1.79)	1.77
Plasma ohmic dissipation during burn (MW)	2.59	2.29(25.3)	25.3
POLOIDAL-FIELD QUANTITIES			
Coil thickness (m)	0.37	0.36	0.42 ^(c)
Average minor radius of coil (m)	1.44	1.62	1.71
Mass of coil (tonne)	729.	703.	394./404. ^(d)
Magnetic field at coil(T)	2.58	2.28	2.5/3.0 ^(e)
Magnetic field at plasma surface (T)	5.21	5.22	5.18
Poloidal-coil current (MA)	18.7	22.4	21.1/11.0 ^(e)
Poloidal-current density (MA/m ²)	5.54	6.06	7.66/6.17
Maximum energy stored in coil (MJ)	1113.	1111.	1700.
Ohmic dissipation during burn (MW)	72.0	83.0	73.0/53.5
Volumetric heating during burn (MW/m ³)	0.79	0.95	1.36/0.97

(a) Based on flat plasma temperature profile.

(b) Values in () correspond to changes resulting from the assumption of a $T(r) \propto J_0(\mu r)$ temperature profile.

(c) For comparison, discrete coils are lumped into a uniform annulus.

(d) Ohmic-heating coil (OHC)/Equilibrium-field coil (EFC) parameters given.

(e) Start-of-burn values are listed. EFC current would remain unchanged, although the OHC current would be reduced to zero as current drive is provided by other sources.

(f) The starting field is taken to be only 0.6 T with the bulk of the internal plasma flux and energy provided from the PFC circuit via the dynamo effect.

TABLE III.G-I (contd)

	REF. 15 DESIGN ^(a)	UPDATE ^(b)	BURN SIMULATION REFERENCE
<u>TOROIDAL-FIELD QUANTITIES</u>			
Coil thickness (m)	0.10	0.09	0.075
Average minor radius of coil (m)	1.20	1.39	1.4625
Mass of coil (tonne)	159.	149.	72.8
Initial toroidal bias field (T)	3.33	3.34	0.60 ^(f)
Reversed toroidal field during burn (T)	0.68	0.68	0.40
Maximum energy stored in the coil (MJ)	539.	542.	22.7 ^(d)
Toroidal current density (MA/m ²)	5.54	6.06	7.04
Ohmic dissipation during burn (MW)	15.71	17.61	12.6
Volumetric heating during burn (MW/m ³)	0.79	0.95	1.27
<u>ENGINEERING SUMMARY</u>			
Ohmic Q-value	37.11	32.92(27.5)	20.5
Total thermal power (MWt)	3350.	3389.(3460)	3365.
14.1-MeV neutron loading (MW/m ²)	19.5	19.6(20.0)	19.5
14.1-MeV blanket multiplication	1.10	1.30	1.277
First-wall radius (m)	0.75	0.75	0.75
Minor radius of system (m)	1.62	1.80	1.92
Fusion-power-core mass (tonne)	1243.	1368.	1105.
System power density (MWt/m ³)	15.00	14.00	11.8
Mass utilization (tonne/MWt)	0.37	0.40	0.33
Blanket/shield thickness (m)	0.40	0.60	0.60
Mass of first wall/blanket (tonne)	355.	516.	234.1
Average blanket power density (MWt/m ³)	51.92	36.1	33.8

(a) Based on flat plasma temperature profile.

(b) Values in () correspond to changes resulting from the assumption of a $T(r) \propto J_0(\mu r)$ temperature profile.

(c) For comparison, discrete coils are lumped into a uniform annulus.

(d) Ohmic-heating coil (OHC)/Equilibrium-field coil (EFC) parameters given.

(e) Start-of-burn values are listed. EFC current would remain unchanged, although the OHC current would be reduced to zero as current drive is provided by other sources.

(f) The starting field is taken to be only 0.6 T with the bulk of the internal plasma flux and energy provided from the PFC circuit via the dynamo effect.

Fig. III.G-12. Time dependence of suprathermal particle temperatures during the plasma startup transient.

Of primary interest when analyzing reactor startup scenarios is the first-wall thermal-mechanical transient. The plasma burn code also monitors the thermal-mechanical response of the first wall, although more-detailed engineering computations are made when completing the conceptual design. The average surface heat flux, I_{Qw} , and total DT neutron current, I_w , at the first wall are plotted on Fig. III.G-14. The neutron and first-wall heat fluxes are not separated by the factor of four that is expected simply because of the DT alpha-particle/neutron energy split. The average surface-neutron flux is plotted while the surface-heat flux is adjusted by $(2/\pi) R_T/(R_T - r_w)$, where $2/\pi$ accounts for the added surface area of a set of first-wall coolant tubes (Sec. III.D.), and the factor $R_T/(R_T - r_w)$ is a first-order approximation to consider geometric peaking in a torus. Coolant tubes near the inboard toroidal radius, $R_T - r_w$, are analyzed using the surface flux plotted in Fig. III.G-14. A volumetric neutron heating of $11.33 I_w R_T/(R_T - r_w)$, as derived from the one-dimensional neutronic calculations (Sec. III.B.), is also included in the

Fig. III.G-13. Time dependence of alpha-particle fraction during the plasma startup transient.

one-dimensional heat-transfer calculation performed as an integral part of the plasma burn simulation.

The first-wall structure suggested in Sec. III.D. is used to estimate the thermal/mechanical response during the startup transient. The water-cooled copper-alloy tubes near the inboard first-wall region have a $d/2 = 24.3$ -mm inside radius and have a $\delta = 3$ -mm tube-wall thickness. Using physical parameters characteristic of copper described in Appendix A and cooling the tubes with pressurized water at 463 K having a heat-transfer coefficient of $1.14(10)^5 \text{ W/m}^2 \text{ K}$, the thermal response of the inside and outside coolant tube surfaces is shown in Fig. III.G-15. The resulting thermal stresses are given in Fig. III.G-15B; a maximum of $\pm 82 \text{ MPa}$ (123 kpsi) is indicated. For a nominal Young's modulus of 100 GPa, this stress corresponds to a thermal strain of $< 0.1 \%$, which is expected to be far below values considered life limiting from the viewpoint of cyclic fatigue. Inclusion of more-realistic effects [i.e., peaking factors, wall thinning because of sputtering, reduced heat transfer coefficient, radiation-degraded thermal and mechanical properties, and primary-stress (coolant pressure) creep] will certainly reduce these margins and

Fig. III.G-14. Time dependence of average heat and neutron power fluxes at the first wall during the plasma startup transient.

$$I_{\phi}=18.4 \text{ MA}, R_T= 3.80 \text{ m}, r_w=0.75 \text{ m}$$

Fig. III-C-15. First-wall thermal and mechanical response to the plasma startup transient as estimated by the plasma-simulation mode. Section III.D. gives a more-detailed steady-state thermal/mechanical analysis of the first wall.

make stronger the case for minimizing the number of startup transients of the kind modeled in this section. Other factors related to external power transients (Fig. III.F-17), cyclic stresses in other FPC components (i.e., blanket, shield, manifolds/headers, structure coils), and overall energy balance combine to make a strong case for extended if not steady-state burns. The following sections on particle control, divertors, vacuum, and current drive emphasize a steady-state operation.

H. Particle Control By Pumped Limiters

The mechanisms by which heat and particles emanating from the plasma interact with the reactor structure represent the premier problem for controlled fusion; a better understanding and proper control of this interaction is essential for the life of both plasma and first-wall/limiter systems. Uniform deposition of conductive/convective/radiative plasma power to in-vacuum component (IVC, first-wall, limiter, divertor-plate) surfaces becomes even more crucial for the compact, high-power-density systems because of the higher energy and particle fluxes expected ($\geq 5 \text{ MW/m}^2$, $\geq 10^{21} \text{ particles/m}^2 \text{ s}$). The shorter acceptable design (chronological) life for a given fluence of neutrons (i.e., dpa or MWyr/m^2) or energetic particles (i.e., mm sputtering margin) must be weighted against a considerably smaller IVC system in order to evaluate the potential advantages of the compact approach.

To develop a better understanding of the plasma/first-wall interaction for the RFP configuration, tokamak models¹³⁴⁻¹³⁷ for the edge-plasma region, or regions where magnetic-field lines intersect physical structure (i.e., the scrapeoff region or simply "scrapeoff") have been appropriately modified. Specifically, the simplified scrapeoff model developed and used for the tokamak FED design¹³⁷ has been implemented with neutral-particle transport and is used to model the parameter range where pumped limiters may be applied to the CRFPR. The basis of this scrapeoff model is the one-dimensional, steady-state heat and particle equations. This set of equations is solved in the scrapeoff for an RFP magnetic topology. An algorithm that adjusts the shape and size of a limiter surface to assure a uniform design heat load is also implemented. Parametric results include variations of pumped-limiter performance with the number of poloidal limiters, the value of the design heat flux, the scrapeoff thickness, the plasma/scrapeoff interface conditions, the plasma/scrapeoff/first-wall recycle rate, and the degree of anomalous transport in the scrapeoff. The primary issue being addressed at this early development of the RFP plasma-edge model is heat transfer and limiter pumping efficiency rather than first-wall/limiter sputter erosion. An improved model for the erosion must include a better (self-consistent) model for edge-plasma impurity/radiation transport as well as the bulk plasma transport; these are topics for future work.

1. Scrapeoff and Limiter Model. The essential elements of the CRFPR scrapeoff and limiter models are depicted in Fig. III.H-1. Because of the dominance of the poloidal field at the plasma-edge radius, r_p , a toroidal array of N_L poloidal limiters is proposed. In such a configuration, the field-line connection length, L , between limiters can be made sufficiently long to allow an adequate amount of radial diffusion into the scrapeoff region (x-axis in Fig. III.H-1) as edge-plasma particles follow the high-pitch field lines between adjacent limiter surfaces. The radial diffusion is assumed to be Bohm like and must be sufficient a) to counteract the tendency to concentrate heat flux onto the leading edge of the limiter, and b) to give for the purposes of pumping an acceptably large particle flux into the channel formed by the limiter and the first wall. The poloidal limiters of toroidal extent ℓ_L are separated by a toroidal (z-axis in Fig. III.H-1) distance, ℓ_w with the total number being

$$N_L = 2\pi R_T / (\ell_L + \ell_w) \quad (1)$$

The average scrapeoff thickness, $\delta = r_w - r_p$, is determined by allowing space for vacuum pumpout.

Fig. III.H-1. Schematic (distorted) diagram of the RFP pumped-limiter model.

Although the leading edge of the limiter is assumed to be positioned at the plasma radius, r_p , image currents in fact may be established in the limiter that may cause the plasma minor radius to vary along the toroidal direction. The two-dimensional nature of the reversal layer, perturbations of the toroidally asymmetric conducting shell, and the effects of the radial field components on plasma confinement are not known and remain an important area for future work.

The total power being shed by the ignited plasma is $P_\alpha + P_\Omega$, where P_α is the alpha-particle power generated in the plasma, and $P_\Omega \ll P_\alpha$ is the ohmic dissipation in the bulk (ignited) plasma. The fraction f_{RAD} of the total energy lost from the plasma is assumed to be radiated uniformly to the limiter and first-wall surfaces. The remaining power, $(1 - f_{\text{RAD}})(P_\alpha + P_\Omega)$, enters the scrapeoff region as a conductive/convective heat flux. The fraction f_{RAD} is treated parametrically, although in actuality f_{RAD} will be determined by the bulk- and edge-plasma impurity concentration and species, which in turn must be coupled with the dynamics of plasma transport and structural sputtering. The development and/or implementation of such a model is beyond the scope of the present study.

The bulk-plasma particle loss is measured by an average particle confinement time, τ_p , which is equated to the bulk-plasma energy confinement time, $\tau_E \approx 0.21$ s, used for the cost-optimized CRFPR design point (Table II.D-III). The actual particle confinement time near the scrapeoff region, however, is expected to be decreased appreciably by edge-plasma recycling, as measured by the edge-plasma recycling coefficient, R_{Le}^* , in order to account for the rapid rate of neutral/plasma particle exchange in the edge-plasma region (i.e., the outer part of the plasma, next to the scrapeoff). Hence, the particle flux into the scrapeoff is enhanced by a factor $1/(1 - R_{\text{Le}}^*)$ above that predicted from the bulk-plasma particle loss. The recycling coefficient, R_{Le}^* , must be better defined through the appropriate multi-dimensional/multi-species transport models; for the purposes of this study, however, R_{Le}^* is treated parametrically.

The RFP scrapeoff model includes neutral-particle transport explicitly, using a modified version of the SPUDNUT¹³⁸ neutral-particle transport code. All particles colliding with the first wall are returned to the scrapeoff region as an isotropic flux of neutral particles at a specific energy. The particles colliding with the limiter are reintroduced in the scrapeoff region as isotropic volumetric sources of neutral particles at an energy level to be specified in

the code (few eV). The SPUDNUT code was modified to include volumetric sources in order to accomplish this task.

In setting up the particle and heat equations used to describe transport in the scrapeoff, an ensemble of simplifying assumptions¹³⁷ is invoked. These assumptions are

- one-dimensional (cylindrical) equations applied to the radial direction (i.e., rapid spiral flow along field lines and along the toroidal direction).
- steady state.
- equal ion and electron densities and temperatures.
- Bohm-like values for the mass diffusivity D , and $\chi = \chi_i + \chi_e = 3D$ for the heat diffusivity.
- $\gamma = \gamma_e + 1$, where $\gamma_e \approx \frac{1}{4} \ln(m_i T_e / m_e T_i)$ is used to represent the enhancement of the electron energy flux resulting from sheath potentials established between the bulk plasma and first-wall/limiter surfaces.
- nonconsistent treatment of radiation.

Under these assumptions, the scrapeoff equations become

$$-\frac{1}{r} \frac{d}{dr} \left(rD \frac{dn}{dr} \right) = -\frac{n}{\tau_{\parallel}} + S_n \quad (2)$$

$$-\frac{1}{r} \frac{d}{dr} \left(n\chi r \frac{dT}{dr} \right) - \frac{1}{r} \frac{d}{dr} \left(3TD r \frac{dn}{dr} \right) = -\frac{2\gamma nT}{\tau_{\parallel}} - Q_{CX} - Q_e^i - Q_i^i, \quad (3)$$

where S_n represents the source of ions generated by ionization of neutral particles, Q_e^i and Q_i^i are the rates at which energy is lost because of electron and ion impact ionization, and Q_{CX} is the rate at which energy is lost by ion charge exchange with neutral particles. The time $\tau_{\parallel}$ required for a plasma particle moving along a field line to impact a limiter surface is L/v_g , where L is the field-line connection length ($L = \pi R_T q$ for a two-sided toroidal limiter

in a tokamak) and v_s is the thermal ion velocity, $(k_B T/m_i)^{1/2}$. For the RFP with N_L equally spaced poloidal limiters operating with double edges, the field-line connection length is given by

$$L = \frac{\pi F}{N_L q}, \quad (4)$$

where for the RFP $q \approx (F/\theta)r^2/(r_w R_T) \approx (xF/A\theta)$, $A = R_T/r_p$, and $x = r_p/r_w$.

Both particle and energy fluxes are specified as boundary conditions at the plasma/scrapeoff interface, with R_{Le}^* being used to modify the bulk-plasma particle flux and f_{RAD} being used to adjust the partition between radiative and convection/conduction energy fluxes emanating from the bulk plasma into the edge-plasma/scrapeoff region. The plasma density and temperature are indirectly specified at the scrapeoff/first-wall interface by requiring the respective particle and energy fluxes onto the first wall to equal $\Gamma_w = \alpha_1 n v_s$ and $q_w = \alpha_2 T \Gamma_w$, where α_1 and α_2 are parameters. These latter conditions approximate an effective first-wall electrostatic sheath. Hence, both n and T are specified at the first wall to match the computed gradients at that location; an iterative procedure must be used to find the appropriate value of n and T at the first wall.

The limiter radial thickness, δ' (Fig. 11I.H-1), is determined from a constant heat-flux condition, which provides a means to determine the limiter shape.¹³⁷ The limiter surface facing the plasma must be shaped in order to accommodate the concentrated particle/heat flux that spirals along the high-pitch field lines and impacts on the poloidal limiters at a glancing angle. A constant (design) heat flux, q_D , is specified for this limiter surface, from which a limiter shape and size is iteratively determined. Figure 11I.H-2 gives the x - z coordinate system used to determine the constant heat-flux shape for the poloidal limiter. Solving the scrapeoff equations gives the diffusive, $q_\perp$, and streaming, q_z , particle heat fluxes incident onto the limiter, where q_z sums all contributions to $2nT\gamma/\tau_\parallel$ along the z -direction in the scrapeoff at constant radial position x . Specifying q_D along with the equation for the limiter shape, as given below,

$$q_D = q_z \sin\theta + q_L \cos\theta + q_{RAD} \cos\theta \quad (5)$$

$$\frac{dx}{dz} = \tan\theta \quad , \quad (6)$$

gives the desired limiter shape. The radiative component in Eq. (5), $q_{RAD} = (P_\alpha + P_\Omega)f_{RAD}$, is assumed to be distributed uniformly over the first-wall/limiter area and is added to q_D . The radial or x extent of the limiter, δ' , is determined from the point along x where $q_z = q_D$; the toroidal or z extent and cross-sectional shape then follow from solving Eqs. (5) and (6) once q_z is obtained from the solution of the scrapeoff density and temperature equations. The heat flux directed toroidally onto the limiter is taken as

$$q_z = 2\gamma T \Gamma_z \quad , \quad (7)$$

where the toroidally directed particle flux, Γ_z , is related as follows to the particle flux streaming along field lines, $\Gamma_\parallel$:

Fig. III.H-2. Limiter geometry used to compute limiter shape required for uniform heat flux.

$$\Gamma_z = \Gamma_{\parallel} \frac{B_{\phi}}{B_{\theta}[1 + (B_{\phi}/B_{\theta})^2]^{1/2}}$$

$$\approx \Gamma_{\parallel}(B_{\phi}/B_{\theta}) = \Gamma_{\parallel}(r/r_w)(F/\theta) \quad . \quad (8)$$

The local temperature, $T(r)$, in the scrapeoff is used in Eq. (7). Requiring that the number of particles incident upon the limiter in the differential volume dx , $2\pi(r_p + x)dx\Gamma_z$, equals the sum of the total volumetric streaming loss, $2\pi(r_p + x)dx(\lambda_w/2 + \lambda_L/2 - z)n(x)/\tau_{\parallel}$, along with Eq. (7) gives the following expression for $\tau_{\parallel}$:

$$\tau_{\parallel} \approx (\lambda_w/2 + \lambda_L/2 - z) \frac{n}{\Gamma_{\parallel}} \left(\frac{r_w}{r} \right) \frac{\theta}{F} \quad , \quad (9)$$

where $v_s \approx \Gamma_{\parallel}/n$. This expression for $\tau_{\parallel}$ is used in Eq. (3) together with the q_D constraint to solve iteratively for the scrapeoff temperature and density profiles that in turn are compatible with the given limiter design (i.e., N_L , q_D , δ , δ' , and leading-edge shape). It is noted that the value of δ' is a minimum in that incorporation of coolant channels into the resulting limiter structure may require the limiter to be thicker than δ' (Sec. III.D.1.b.).

2. Parametric Results. As emphasized by Howe,¹³⁷ the sensitivity of peak and design heat fluxes at limiter surfaces to variations in a simplified edge-plasma transport model renders an exact limiter design at best risky without strong direction from experiments. Hence, an emphasis is placed at this stage of the analysis on parametric sensitivity studies of limiter performance for the CRFPR design (Table II.D-III). For the $\sim 20 \text{ MW/m}^2$ surface-averaged first-wall neutron loading, an average heat flux of $\sim 5 \text{ MW/m}^2$ at the first wall is implied for divertorless plasma operation. The major goal of this limiter study, therefore, is to quantify the extent to which the design heat flux is increased above this irreducible minimum while maintaining a reasonable limiter number, shape, and performance (i.e., particles diffusing/streaming to the limiter channel).

Parameters which have been held fixed, parametrically varied, or computationally derived as part of this limiter parametrics study are summarized in Table III.H-1. A canonical base case has been defined for $N_L = 24$ (nominally one limiter per TFC), $R_{Le}^* = 0.85$, $D \approx 1 \text{ m}^2/\text{s}$ (approximately the Bohm diffusion rate), and $q_D = 6 \text{ MW/m}^2$; sensitivity studies are performed about this base case.

Density, temperature, particle flux, and energy flux profiles through the scrapeoff are shown in Fig. III.H-3 for a range of specified radiation fractions, f_{RAD} , for the base-case parameters summarized in Table III.H-1. Decreasing f_{RAD} requires a higher particle convection/conduction heat flux at the scrapeoff. Generally, increasing f_{RAD} decreases $q_{\perp}$ at the edge-plasma/scrapeoff boundary, which in turn causes the observed decrease in plasma temperature in this region, since the particle flux into the scrapeoff remains unchanged and the energy per particle, therefore, must decrease. Decreasing the edge-plasma/scrapeoff temperature causes $\tau_{\parallel} \propto 1/T^{1/2}$ to increase, which in turn decreases the streaming loss, $n/\tau_{\parallel}$, which then increases the density in this region if $\Gamma_{\perp}$ remains fixed. Figure III.H-3 displays this general behavior.

The magnitude of the energy fluxes, $q_z \approx 20\text{--}100 \text{ MW/m}^2$, indicates that the limiter shape will be nearly parallel to the first wall if the design heat flux, $q_D \approx 6 \text{ MW/m}^2$, at the limiter surface is to be maintained. Figure III.H-4 gives the toroidal energy flux incident upon the limiter as well as the limiter shapes required to meet the $q_D = 6 \text{ MW/m}^2$ constraint. As f_{RAD} decreases, the limiter coverage fraction, $\lambda_L/(\lambda_L + \lambda_w)$, increases to maintain $q_D = 6 \text{ MW/m}^2$ at all points on the limiter leading-edge surface. The high toroidal energy fluxes in the first few millimeters of the scrapeoff are a consequence of the relatively slow cross-field diffusion velocity (somewhat less than Bohm-like rates) compared to the parallel field streaming velocity, even for the high-pitch (i.e., long connection length, L) edge-plasma region of the RFP. Increasing the number of limiters combines two competing effects (i.e., less total energy per limiter versus shortened reconnection length and decreased $\tau_{\parallel}$) to relieve this problem somewhat; either D must be increased much above the Bohm-like values used here, or f_{RAD} must be increased. On the bases of the results given in Fig. III.H-4, f_{RAD} much below ~ 0.90 will give unwieldy limiter designs for the $q_D \approx 6 \text{ MW/m}^2$ limit imposed.

The dependence of limiter performance [i.e., $\lambda_L/(\lambda_L + \lambda_w)$, f_p , f_E , λ_L , δ'/δ] on N_L , q_D , and f_{RAD} is illustrated in Figs. III.H-5 and III.H-6. Typically, for $N_L \gtrsim 20\text{--}30$, the opposing effects of less energy and particles

TABLE III.H-I

FIXED, VARIED, AND DERIVED PARAMETERS USED IN
PUMPED-LIMITER PARAMETRIC STUDY

<u>FIXED PARAMETERS</u>	<u>VALUE</u> ¹⁵
Major/first-wall/plasma radii, $R_T/r_w/r_p$ (m)	4.30/0.75/0.71
Plasma volume/first-wall area, $V_p(m^3)/A_w(m^2)$	42.8/127.3
Alpha-particle power, P_α (MW)	615.6
Ohmic-heating power P_Ω (MW)	28.6
Bulk-plasma particle loss, $\langle n \rangle V_p / \tau_p (10^{23}/s)$	0.69
Average plasma density, $\langle n \rangle (10^{20}/m^3)$	3.40
Bulk-plasma energy confinement time, τ_E (s)	0.21
Reversal parameter, F	-0.2
Pinch parameter, θ	1.45
Rotational transform at first wall, $\tau(r_w) = 1/q$	41.6
Limiter radial extent, $\delta(m) = r_w - r_p$	0.04
Particle flux first-wall boundary coefficient, α_1	0.25
Energy flux first-wall boundary coefficient, α_2	6.0
<u>VARIED PARAMETERS</u>	
Fractional plasma energy lost by radiation, f_{RAD}	0.85 $\rightarrow$ 0.95
Edge-plasma recycling coefficient, R_{Le}^*	0.0 $\rightarrow$ 0.85
Particle diffusivity in scrapeoff, $D(m^2/s)$	0.5 $\rightarrow$ 10.0
Thermal diffusivity in scrapeoff, $\chi(m^2/s)$	3D
Number of limiters, $N_L = 2\pi R_T / (\lambda_L + \lambda_w)$	10 $\rightarrow$ 100
Design heat flux on first-wall/limiter, q_D (MW/m ²)	6 $\rightarrow$ 20
Particle heat flux at scrapeoff, q_1 (MW/m ²)	5.35(1 - f_{RAD})
Particle flux at scrapeoff, $\Gamma_1(10^{21}/m^2s)$	4.56/(1 - R_{Le}^*)
<u>DERIVED PARAMETERS</u>	
Edge-plasma density, $n(r_p)(10^{20}/m^3)$	1.38
Edge-plasma temperature, $T(r_p)$ (eV)	45.9
Limiter length, λ_L (m)	0.38
Limiter coverage fraction, $\lambda_L / (\lambda_L + \lambda_w)$	0.38
Limiter thickness, δ (m)	0.0115
Fraction scrapeoff particles under limiter, f_p	0.34
Fraction scrapeoff particle energy under limiter, f_E	0.12

Fig. III.H-3. Density, temperature, particle flux, and energy flux profiles in the scrapeoff for variations in the fraction, f_{RAD} , of the total plasma energy loss appearing as (edge) radiation for the base-case parameters indicated.

Fig. III.H-4. Dependence of limiter shape on f_{RAD} for the base-case parameters indicated. The limiter cross sections are indicated both on an actual scale and a scale that gives the proportion of $(l_L + l_w)/2$. The toroidal heat flux, q_z , is also shown as a function of distance into the scrapeoff.

Fig. III.H-5. Dependence of limiter performance on number of limiters, N_L , and radiation fraction, f_{RAD} , for $q_D = 6 \text{ MW/m}^2$.

Fig. III.H-6. Dependence of limiter performance on design heat flux, q_D , and radiation fraction, f_{RAD} , for $N_L = 24$ limiters.

versus reduced connection length as N_L increases is illustrated. Increasing the design heat flux beyond $q_D \approx 6 \text{ MW/m}^2$ improves the limiter performance, although the base-case value of q_D is already large.

For the base case, which now includes $f_{\text{RAD}} = 0.90$, the dependence of limiter performance on the edge recycling coefficient, R_{Le}^* , is shown on Figs. III.H-7, III.H-8, and III.H-9. The dependence of the profiles on R_{Le}^* (Fig. III.H-7) is explained as follows. Increasing R_{Le}^* leads to a decrease in the effective, edge-plasma particle confinement time, $\tau_p(1 - R_{\text{Le}}^*)$, so that both the particle flux and density at the scrapeoff/edge-plasma interface increase. Since the energy flux through this interface remains unchanged, the energy per particle decreases at this interface. The decrease in plasma temperature then leads to an increased $\tau_{\parallel}$. Since $\Gamma_{\perp} \approx nv \propto nT^{1/2}$, with $\Gamma_{\perp}$ increasing with increased R_{Le}^* , the scrapeoff/edge-plasma density increases faster than $T^{1/2}$ decreases, indicating that the streaming loss $n/\tau_{\parallel} \propto nT^{1/2}$ has a net increase; the dependence of the fluxes on R_{Le}^* depicted in Fig. III.H-7 results.

The ability to achieve an acceptable limiter performance depends primarily on a) the particle energy flux incident upon the scrapeoff (i.e., f_{RAD}), and b) the capability for rapid radial transport to spread this energy flux radially outward, away from, and under the limiter. Figures III.H-10, III.H-11, and III.H-12 show the effect on profiles and limiter performance as the particle diffusivity, D , is parametrically varied above and below the base-case value of $D = 1 \text{ m}^2/\text{s}$, with the relationship $\chi = 3D$ being maintained. The general behavior observed is explained by noting that $D(dn/dx)_{x=0} \approx \int (n/\tau_{\parallel})dx$ is nearly a constant. Hence, increases in D result in decreased density gradients. The constraint that $\chi = 3D$ makes this tendency even stronger for flat temperature gradients with $q_{\perp}$ held fixed. The dependence of limiter performance on D is summarized in Fig. III.H-12. The maximum in the fraction of particles transported into the limiter channel, f_p , as D is changed indicates that for $D < 1 \text{ m}^2/\text{s}$ the majority of the particles impinge on the limiter leading edge, whereas for $D > 1 \text{ m}^2/\text{s}$ the majority of the particles intersect the first wall and, hence, are assumed lost at the wall or ionized in the bulk plasma. The previous selection of Bohm-like $D = 1 \text{ m}^2/\text{s}$ for the base case has indeed been fortuitous from the viewpoint of optimizing the limiter pumping effectiveness.

On the basis of this scrapeoff parameter study, the varied and derived limiter parameters listed on Table III.H-II are adopted for a specific limiter point design. The limiter design parameters for the Ref. 15 case and the update

Fig. III.H-7. Density, temperature, particle flux, and energy flux profiles in the scrapeoff as a function of the edge recycling coefficient, R_{Le}^* , for the base-case parameter indicated.

Fig. III.H-8. Dependence of limiter shape on R_{Le}^* for the base-case parameters indicated. The limiter cross sections are indicated both on an actual scale and a scale that gives the proportion of $(\lambda_L + \lambda_w)/2$. The toroidal heat flux, q_z , is also shown as a function of distance into the scrapeoff.

Fig. III.H-9. Dependence of limiter performance on edge recycling coefficient, R_{Le}^* .

Fig. III.H-10. Density, temperature, particle flux, and energy flux profiles in the scrapeoff as a function of the particle diffusivity, D , for the base-case parameters indicated.

Fig. III.H-11. Dependence of limiter shape on particle diffusivity, D , for the base-case parameters indicated. The limiter cross sections are indicated both on an actual scale and a scale that gives the proportion of $(l_L + l_W)/2$. The toroidal heat flux, q_z , is also shown as a function of distance into the scrapeoff.

Fig. III.H-12. Dependence of limiter performance on particle diffusivity, D , for the base-case parameters indicated.

TABLE III.H-II
POINT-DESIGN PARAMETERS FOR A PUMPED-LIMITER SYSTEM

PARAMETER	REF. 15	UPDATE	
		<u>T(r)=CONST</u>	<u>T(r) ∝ J₀(μr)</u>
Particle confinement time, τ_p (s)	0.21	0.23	0.23
Major toroidal radius, R_T (m)	4.30	3.79	3.79
Average particle density, $\langle n \rangle (10^{20} \text{ m}^{-3})$	3.40	3.39	6.74
Alpha-particle power, P_α (MW)	615.6	546.5	546.5
Ohmic-heating power, P_Ω (MW)	28.6	2.3	25.3
Plasma energy radiation fraction, f_{RAD}	0.90	0.90	0.90
Edge-plasma recycling coefficient, R_{Le}^*	0.85	0.80	0.80
Number of limiters, $N_L = 2\pi R_T / (\lambda_L + \lambda_w)$	24	24	24
Design heat flux, q_D (MW/m ³)	6.0	6.0	6.0
Particle heat flux at scrapeoff, $q_\perp$ (MW/m ²)	0.53	0.52	0.54
Particle flux at scrapeoff, $\Gamma_\perp (10^{21}/\text{m}^2 \text{ s})$	3.83	2.62	5.21
Temperature at edge, T_e (eV)	83.2	179.3	45.9
Neutral-atom pressure at limiter slot, mtorr	12.6	11.2	18.6
Ion edge density, $n_e (10^{19}/\text{m}^3)$	6.85	2.44	13.76
Neutral edge density, $n_{ne} (10^{17}/\text{m}^3)$	1.88	3.59	2.32
Particles entering scrapeoff ($10^{23}/\text{s}$)	4.62	2.78	5.53
Particles going to limiter ($10^{24}/\text{s}$)	1.00	0.41	1.62
Particles going to wall ($10^{23}/\text{s}$)	0.66	0.12	1.29
Limiter coverage fraction, $\lambda_L / (\lambda_L + \lambda_w)$	0.37	0.34	0.38
Limiter toroidal extent, λ_L (m)	0.42	0.34	0.38
Limiter radial extent, δ' (mm)	8.4	7.6	8.4(11.4) ^(a)
Limiter thickness-to-extent ratio, δ'/δ	0.21	0.19	0.21(0.29) ^(a)
Fraction particles under limiter, f_p	0.31	0.27	0.34(0.24) ^(a)
Fraction particle energy under limiter, f_E	0.11	0.096	0.12(0.068) ^(a)
Fraction total plasma energy loss to limiter, $\sim f_{\text{RAD}} \lambda_L / (\lambda_L + \lambda_w) + (1 - f_{\text{RAD}})$	0.43	0.41	0.44
Scrapeoff recycling coefficient, R_{LS}^*	0.57	0.34	0.68
Inversion probability, κ	0.66	0.49	0.73(0.69) ^(a)

^(a)Corrected for the radial thickening of the limiter underside to allow for internal structure and coolant ducts (Sec. III.D.2.b.).

case (Table II.D-III), where the major radius is $R_T = 3.79$ m, average plasma density is $n = 6.74(10)^{20} \text{ m}^{-3}$, and particle confinement time, $\tau_E = 0.23$ s, are listed as are the scrapeoff recycling coefficient, R_{LS}^* , and the inversion probability, κ . The scrapeoff recycling coefficient is computed by the limiter code and refers to the recycling in the scrapeoff and is similar to R_{Le}^* defined for the edge-plasma region. The inversion probability gives the probability that a particle neutralized at the first wall and back of the limiter slot in the absence of pumping returns to the limiter slot (i.e., is ionized in the scrapeoff rather than in the edge or bulk-plasma region). The results from Table III.H-II indicate poloidal limiters of realistic number, size, and shape are possible for the CRFPR design point and a limiter design heat flux of $q_D < 6 \text{ MW/m}^2$. The assumptions made in developing this limiter/scrapeoff model, however, require further examination before a detailed mechanical design is warranted. In addition to the assumptions listed previously, the following limitations should be noted:

- one-dimensional neutral-atom transport model (SPUDNUT)
- approximate interface with the bulk plasma
- absence of a self-consistent treatment of impurity transport, radiation (f_{RAD}), and first-wall/limiter sputtering
- simplified (parametric) treatment of radial electrostatic sheaths at the first wall and no treatment of electrostatic effect along the toroidal direction
- sputtering, impurity transport, and redeposition, although estimated, require more accurate modeling.

The use of the SPUDNUT model to estimate the inversion probability, κ , and the inability to model properly neutral-particle interactions with the underside of the limiter generally underestimates κ and, therefore, overestimates the limiter pumping speed. A more realistic model (e.g., Monte Carlo) is needed to estimate this crucial parameter, particularly as the engineering design requires the limiter thickness, δ' , to increase in order to accommodate more support and cooling structure beyond the minimum value, δ'_{MIN} , required to assure $q_D = 6 \text{ MW/m}^2$. Figure III.H-13 gives the dependence of f_p , f_E , κ , and the average neutral-atom pressure as the limiter-slot thickness is varied for the design point suggested on Table III.H-II, these results again limited by the

assumptions listed above. The neutral-atom pressure given in Fig. III.H-13 is a radial average using the neutral-atom density profile returned by SPUDNUT and the local plasma temperature profile. This average pressure decreases nearly linearly with increasing δ' (i.e., for fixed δ , the limiter slot is diminished), nominally giving a value that is close to that used in the estimate of the vacuum requirements (Sec. III.J.).

The behavior of the particle and energy fractions, the neutral-atom pressure, and inversion factor plotted in Fig. III.H-13 as a function of the limiter thickness for the base-case designs must be explained in terms of both the model limitations as well as the physics that this model is attempting to describe. The curves of the f_p and f_E versus δ' can be explained by noting that increasing the limiter thickness will increase the number of particles striking the leading edge of the limiter, thereby decreasing f_p and f_E . As noted previously, κ is estimated using an adapted version of the SPUDNUT code (a volumetric neutral-particle source has been added at each mesh point) to model neutral-atom emissions from the limiter back surface. A transparent limiter is assumed while following trajectories and ionization events for calculating the inversion probability, κ . By assuming a transparent limiter the reflection of neutral atoms on the backside of the limiter is ignored and, hence, κ will be underestimated. The larger δ' , the thinner the limiter slot, and, therefore, κ can be expected to decrease with increasing δ' . A more realistic (two-dimensional) model must be implemented to evaluate the behavior of κ in the presence of limiter reflections. The decrease in κ as δ' is increased can be explained by simple geometric arguments and the modelistic limitations associated with the absence of limiter/neutral-atom interactions (i.e., reflections). In this case κ is a parameter indicating the ease of neutral-atom pressure build-up behind the limiter, and, therefore, a drop in neutral-atom pressure with increasing δ' is consistent with the computed κ behavior.

The Table III.H-II parameters are used to incorporate the pumped limiter into the FPC integration and to size vacuum-pumping ducts, but final design choices must await answers to the above-listed questions. It is in this spirit that the potential for magnetic divertors in RFPs has been examined as an alternative impurity-control scheme.

Fig. III.H-13. Dependence of particle and energy fractions, f_p and f_E , the inversion probability, κ , and the average neutral-atom pressure in the limiter slot as the limiter thickness (and slot width) changes for the base-case parameters listed in Table III.H-II.

I. Magnetic Divertor

Although the pumped limiter has served as the focus of the impurity control for this study (Sec. III.H.), as well as providing a means to determine the essential elements of the vacuum-system design (Sec. III.J.), preliminary consideration has been given to the use of magnetic divertors in an effort to reduce heat/particle fluxes onto surfaces having a direct view of the plasma. As for the pumped limiter, magnetic divertors in an RFP configuration have received little attention, and new development was required. The material presented herein should be considered exploratory and is the beginning of a continuing effort in an important area for RFPs.

The FPC volume required by a pumped limiter generally is substantially less in toroidal devices than the volume needed for a magnetic divertor. Because of the large premium placed on compactness and a reduced total FPC mass for the CRFPR, the pumped limiter is the natural first choice for the impurity-control scheme if both schemes are equally viable. Present experimental data on impurity-control in tokamaks,¹³⁹ however, indicate better plasma performance in devices with a magnetic divertor than in devices using a limiter because of the isolation from the plasma chamber. Although these results are not sufficiently definitive to eliminate the pumped limiter as an impurity-control scheme, the preliminary magnetic divertor design presented below, nevertheless, was performed to examine the feasibility of diverting field lines in an RFP and to gauge the impact of a magnetic divertor on the overall FPC size.

A magnetic divertor design study must begin with a selection of the field component to be nulled and ultimately diverted to an external structural surface. Most magnetic divertor designs pertain to tokamaks. These designs predominately null the minority poloidal field, and are a choice that can be supported for the following reasons. The plasma equilibrium equation, $\vec{j} \times \vec{B} = \vec{\nabla} p$, indicates that nulling a component of the magnetic field will result in a reduction in the gradient of the plasma pressure in the vicinity of the null for comparable plasma current densities. The reduction in the volume-averaged beta that inevitably results can be minimized if only the minority field is nulled. A second consideration is the effect a field null will have on particle and energy confinement. Particle confinement times generally scale in proportion to B raised to a positive exponent, for example, $\tau \propto B$ for Bohm diffusion and $B^{1.8} \rightarrow B^{2.0}$ for empirical scalings¹⁴⁰ using $\langle n_e \rangle \propto \beta B^2/T$. A reduction in confinement in the vicinity of a field null would reduce the volume-

average confinement time. Thirdly, the currents required in the divertor coils scale linearly with the magnitude of the field component to be nulled; the energy stored by and forces on the divertor coils are minimized by nulling the minority-field component. Hence, minimization of the effects on beta, confinement time, and divertor coil all indicate that the minority field is the preferred field to null. Diverting the minority poloidal field in a tokamak requires that the divertor coils be interlocked with the TFC set. A few tokamak experiments do null the majority field in an attempt to avoid the problems associated with interlocked coils.¹⁴¹ The minority field in an RFP, however, is toroidal, and the preferred minority toroidal-field component can be nulled without the engineering complexity of interlocking coils.

The simplest design of a toroidal-field divertor for an RFP merely adds TFCs of the appropriate size and current to the main TFC set. The divertor should not only isolate the region of field-line contact with structural surfaces from the plasma but also should provide a path along which the plasma exhaust can deposit energy. This goal is accomplished with divertor coils of radius sufficiently large to encase the main TFC set. The current in the coil that nulls the toroidal field must be sufficiently large to cancel the field from the TFC set. Viewing the nulling coils in each of N_D toroidal divertors as a solenoid which must cancel the field from the N toroidal-field coils, then the current in each divertor coil, I_D , is approximately related to the current in each TFC, I_{TF} , by the relationship

$$N_D I_D \approx - N I_{TF} . \quad (1)$$

A set of such divertor coils will null the toroidal field indiscriminately within the bore of TFC set. A pair of coils that flank the divertor coils are introduced with a combined current equal in magnitude but opposite in sign to that in the divertor coil in order to localize the nulling effect of the divertor coils approximately to within the distance between the divertor coil and its flanking coils. The flanking coils only afford gross control of the location of the toroidal-field null and the size of the penetration in the FPC needed to accommodate the divertor channel. A more precise method of controlling the characteristics of the field null, and in particular its toroidal extent, is necessary to reduce the degree to which the tritium-breeding

blanket is displaced by the divertor channel, the size of the gap required in the conducting first wall (i.e., may effect plasma equilibrium and stability), and the amplitude of the toroidal ripple induced, the last resulting in the formation of magnetic islands that affects both transport and field reversal (Sec. III.F.1.). Quantitative estimates of the latter two effects have not yet been made. Demonstrating a method of controlling the toroidal extent of the field null and field ripple, however, was deemed necessary for this study.

The method chosen for controlling the toroidal extent of the field perturbation introduced another divertor-flanking-coil (DFC) set with less current than the main divertor coil set but located closer to the plasma edge. Hence, the DFCs are encased by the TFC set, and a smaller gap between the divertor coil and the DFCs result. A divertor design with four toroidal divertors for the CRFPR magnetics parameters (Sec. III.F.) is shown in Fig. III.I-1, where only the TFC set, the main divertor coil set, and the DFC set have been simulated by the three-dimensional vacuum-field magnetics code, TORSIDO.⁵¹ The main divertor coil encasing the TFC set has a current of 1.6 MA, while the secondary DFCs encased within the TFC set have a current of 0.4 MA. The effect of the secondary DFC set is evident in Fig. III.I-1 from the pinching of the diverted field lines near the plasma edge. The property of localizing the divertor action to the outboard side of the plasma is characteristic of divertor designs similar to that depicted in Fig. III.I-1. A more compact divertor design is possible that yields nearly the same diversion of field lines by making the current of the diverting coils return through the DFCs rather than through the inboard side of the torus, as shown in Fig. III.I-1. Such a design remains for future work. In addition, field-line tracings are needed to include the simulation of the PFC set and the plasma currents to yield a full three-dimensional picture of the divertor as well as to reveal adequate formation of separatrix surfaces and the control of magnetic islands. This calculation also must be coupled with a transport and radiation model to determine the length of the divertor channel necessary to provide cooling of the plasma exhaust, as well as plasma stability and tritium-breeding calculations to quantify the permissible size of the toroidal gap. A code similar to ZEPHYR¹⁴² will be used for the latter purpose. Generally, work in both pumped-limiter and magnetic-divertor schemes for RFP impurity control represents an important, ongoing effort, both promising advantages relative to confinement schemes with a dominant toroidal-field component.

Fig. III.I-1. Field-line tracings in the equatorial plane for a field period of the CRFPR with four toroidal-field divertors.

J. Vacuum and Fueling

The primary function of the CRFPR vacuum system is the removal of excess impurities and helium ash generated by fusion reactions. Purging of the helium ash is accompanied by the removal of large quantities of unburned DT fuel for subsequent reprocessing and reinjection into the plasma chamber as fresh fuel (pellets). Design of the vacuum system requires a calculation that is self-consistent with the plasma-edge/limiter model (Sec. III.H.) and subject to constraints imposed to minimize neutron and gamma-ray streaming through vacuum channels, thereby maximizing blanket coverage and efficiency. The external fueling rate must balance the combined DT exhaust and burnup in steady state. The vacuum system is considered in Sec. III.J.1, and the pellet-fueling requirements are discussed in Sec. III.J.2.

1. Vacuum System. The rate of generation and, hence, removal of helium ash by the fusion reaction is given by

$$\phi_{\text{He}}(\text{He/s}) = 2\pi r_w 2\pi R_T \frac{I_w}{14.1 k_B}, \quad (1A)$$

which for $r_w = 0.75$ m, $R_T = 3.8$ m, $I_w = 19.5$ MW/m², and $k_B = 1.602(10)^{-16}$ J/eV equals $9.74(10)^{20}$ He/s and compares with $1.24(10)^{21}$ He/s for the STARFIRE tokamak design;³ the helium generation rate, of course, scales directly with fusion power. The corresponding helium gas load under standard conditions [273 K, $1.013(10)^5$ Pa] is

$$\phi_{\text{He}}^{\text{STP}}(\text{Pa m}^3/\text{s}) = 6.58(10)^{-2} r_w R_T I_w, \quad (1B)$$

corresponding to 3.66 Pa m³/s (27.8 l torr/s). At the elevated operating temperature of the limiter slot/first wall (i.e., ~ 600 K), the helium gas load becomes 8.05 Pa m³/s for the CRFPR design point.

The DT (molecular) gas load being pumped must be calculated consistently with the pumped-limiter model (Sec. III.H.) as follows:

$$\phi_{\text{DT}}^{\text{STP}}(\text{Pa m}^3/\text{s}) = 0.84(10)^{-22} \frac{\langle n \rangle V_p (1 - R_{\text{DT}})}{\tau_p (1 - R_{\text{Le}}^*)(1 - R_{\text{Le}}^*)}, \quad (2A)$$

where the average plasma density is $\langle n \rangle = 6.55(10)^{20}$ m⁻³, the plasma volume is $V_p = 37.8$ m³, $\tau_p = 0.59$ s is the core-plasma particle confinement time, R_{DT} is the limiter-slot reflection coefficient, $R_{\text{Le}}^* = 0.80$ is the edge-plasma recycling

coefficient, and $R_{LS}^* = 0.68$ is the scrapeoff recycling coefficient. For these conditions, $\phi_{DT}(DT/s) = 3.27(10)^{22}(1 - R_{DT})$ becomes

$$\phi_{DT}^{STP}(\text{Pa m}^3/\text{s}) = 55(1 - R_{DT}) . \quad (2B)$$

The limiter-slot reflection coefficient, R_{DT} , can be expressed by

$$R_{DT} = 1 - f_{DT} \epsilon_{DT} , \quad (3)$$

where $f_{DT} = 0.24$ (Table III.H-II) is the fraction of DT particles entering the limiter slot and ϵ_{DT} is the DT particle transmission probability, as defined in Ref. 3 (p. 8-111). The value of ϵ_{DT} depends on the details of the vacuum-system model, as will be shown below. Following the discussion given in Ref. 3, a mass flow balance in the limiter-slot for species i (i.e., either He or DT) requires that

$$V_{01} \frac{d(P_{0i} + P_{1i})/2}{dt} = \phi_i - F_{Ri}P_{1i} - F_{01i}(P_{1i} - P_{0i})(1 - \kappa_i) , \quad (4)$$

where P_{0i} is the gas pressure at the limiter-slot entrance, P_{1i} is the pressure of species i in the back of the slot region, V_{01} is the volume of the slot region, F_{Ri} is the effective conductance of the vacuum system beyond the slot for species i , F_{01i} is the conductance of the slot region for species i , and κ_i is the inversion probability for species i [i.e., $\kappa_{He} = 0.99$ (assumed) and $\kappa_{DT} = 0.69$ (Table III.H-II)]. The three terms on the right-hand side of Eq. (4) describe the gas load entering the limiter slot, the outflow through the vacuum system, and the backflow to the plasma chamber, respectively. Steady-state operation allows the simplification to the following expression:

$$\phi_i = F_{Ri}P_{1i}[1 + \gamma_i(1 - P_{0i}/P_{1i})(1 - \kappa_i)] , \quad (5)$$

where $\gamma_i \equiv F_{01i}/F_{Ri}$ is the ratio of the limiter-slot conductance to that of the downstream vacuum channel for species i .

The transmission probability [Eq. (3)] is given by $\epsilon_i = F_{Ri}P_{1i}/\phi_i$, which upon substitution in Eq. (5) gives

$$\epsilon_1 = \frac{1}{1 + \gamma_1(1 - P_{01}/P_{11})(1 - \kappa_1)} \quad , \quad (6)$$

and is shown on Fig. III.J-1 in the limit $P_{01}/P_{11} \ll 1$.

The schematic "unit cell" of the CRFPR vacuum system being modeled is illustrated in Fig. III.J-2, which also introduces the dimensional notation used in the vacuum conductance models. Fixed parameters are summarized on Table III.J-I and have been chosen on the basis of preliminary estimates of the overall size of the torus (Table II.D-III), blanket/shield dimensions (Fig. III.B-5.), limiter geometry (Table III.H-II), and coil sizes (Tables III.F-III and III.F-V). Figure III.J-2 represents a first level of engineering integration of the FPC and is needed to size the vacuum system. This process of FPC integration is continued in more detail in Sec. III.L.

Fig. III.J-1. Dependence of the required vacuum-system transmission probability, ϵ , on the inversion probability, κ , for various conductance ratios, γ (Ref. 3).

Fig. III.J-2. Schematic CRFPR "unit cell" vacuum-system model showing geometry and key notation.

The vacuum channel outboard of the limiter slot is sequentially composed of a) a radially divergent slot between adjacent blanket modules, b) an annular plenum extending around the outboard poloidal circumference of the torus which separates the blanket module from the shield module and provides an interruption in the neutron-streaming path from the plasma chamber to the external environment, and c) a rectangular exhaust channel on the outboard side of the torus which is constrained on either side to thickness δ_5 by a TFC and the blanket coolant ducts and above and below to height δ_6 by the blanket coolant ducts for the outboard blanket annulus. In the integrated FPC design, placement of limiter and first-wall coolant manifolds and headers may be anticipated to interface somewhat with the idealized unit-cell geometry described and used here. The channel opens into the vacuum enclosure surrounding the FPC beyond the system radius, $r_g \approx r_4$, which is taken for the purposes of these vacuum

TABLE III.J-I

FIXED PARAMETERS FOR VACUUM CALCULATION

<u>Dimensions (m):</u>	<u>Value</u>
Major toroidal radius, R_T	3.8
Minor first-wall radius, r_w	0.75
System radius, $r_4 \approx r_s$	1.69
Limiter-slot thickness, δ_1	0.0285
Radius of limiter underside, $r_1 = r_w - \delta_1$	0.7215
Exhaust-channel thickness, $\delta_5^{(a)}$	0.06
Exhaust-channel height, δ_6	0.72
Radial-gap length, $l_2 \approx \Delta_{FW/SW} + \Delta_{BLK}$	0.525
Exhaust-channel length, l_4	0.75
Shield thickness, Δ_{SLD}	0.10
TFC thickness, $\delta_{c\phi}$	0.075
TFC length, $l_{c\phi}$	0.60
TFC current-center radius, $r_{c\phi}$	1.4625
<u>Temperatures (K):</u>	
$\langle T \rangle_{01}$	600
$\langle T \rangle_{23}$	500
$\langle T \rangle_4$	350
<u>Pressures (mtorr):</u>	
Helium, P_1	5
DT, $P_1 = 2P_2 = 10P_3$	10
P_4	0.04
<u>Parameters From Pumped-Limiter Model (Table III.H-II):</u>	
Limiter-slot thickness, $\delta_1(m)$	0.0285
Limiter-slot length, $l_1(m) = l_L/2$	0.19
Reflection coefficient, R_{DT}	0.90
Inversion probability, κ_{DT}	0.69
Fraction of particles into limiter slot, f_{DT}	0.24
Transmission probability, ϵ	0.40 ^(b)

^(a) In the actual design, two such thicknesses are combined on one side of the TFC to pump each sector ($N = 24$).

^(b) A goal [Eq. (6) and Ref. 3].

calculations to have a pressure $P_4 = 0.04$ mtorr. The vacuum enclosure for the purpose of these estimates is taken to be a cylindrical chamber with 9-m radius and 5-m height giving a nominal volume (less the volume of the FPC) of $\sim 1000 \text{ m}^3$.

Vacuum conductances for these channels are calculated using a composite expression that is valid for both viscous and free-molecular flow as well as for the transition regime. Combining a viscous-flow conductance, $F_V(\text{m}^3/\text{s})$, and free-molecular-flow conductance, $F_M(\text{m}^3/\text{s})$, gives the following general relationship:

$$F = F_V + ZF_M, \quad (7)$$

where Z is given by the Knudsen expression,¹⁴³

$$Z = \frac{1 + (8/\pi)^{1/2} \frac{2\delta}{R_1 \langle v_1 \rangle} \langle P_1 \rangle}{1 + 1.235(8/\pi)^{1/2} \frac{2\delta}{\eta_1 \langle v_1 \rangle} \langle P_1 \rangle}. \quad (8)$$

The symbol δ is a characteristic duct dimension, where $\langle P_1 \rangle = (P_{IN} + P_{OUT})/2$ is the average pressure of the i^{th} species in the segment, $\langle v_1 \rangle = (8k_B \langle T \rangle / \pi m_1)^{1/2}$ is the average molecular speed of the gas in the segment, and η_1 is the gas viscosity given by

$$\eta_1 (\text{Pa s}) = 0.499 m_1 \langle v_1 \rangle / (\sqrt{2} \pi d_1^2), \quad (9)$$

where m_1 is the molecular mass (amu) and d_1 is the effective molecular diameter. Values of d_1 for He and DT are used to return the empirical values of $\eta_{\text{He}}(298 \text{ K}) = 1.99(10)^{-5} \text{ Pa s}$ and $\eta_{\text{DT}}(298 \text{ K}) = 1.41(10)^{-5} \text{ Pa s}$. For purposes of the present calculation, properties of the He/D₂/T₂/DT exhaust are computed using the average properties of the dominant (DT) effective molecular species (i.e., $m_1 = 5 \text{ amu}$).

The viscous-flow conductances, $F_V(\text{m}^3/\text{s})$, for the channels illustrated on Fig. III.J-2 are given by the following expressions:^{144, 145}

$$F_{V01} = \frac{\pi}{8\eta_1 l_1} \left[r_w^4 - r_1^4 - \frac{(r_w^2 - r_1^2)^2}{2 \ln(r_w/r_1)} \right] \langle P_{01} \rangle \quad (10A)$$

$$F_{V12} = \frac{3.287 \delta_2^3}{\eta_2 \ln(r_3/r_w)} \langle P_{12} \rangle \quad (10B)$$

$$F_{V23} = \frac{4.797(10)^{-3} Y_3 \delta_3^2 \delta_4^2}{\eta_3 \lambda_3} \langle P_{23} \rangle \quad (10C)$$

$$F_{V34} = \frac{4.797(10)^{-3} Y_4 \delta_5^2 \delta_6^2}{\eta_4 \lambda_4} \langle P_{34} \rangle , \quad (10D)$$

where the gas viscosity, η_j , is evaluated for the average local conditions, and $\langle P_{jk} \rangle \equiv (P_j + P_k)/2$. The functions Y_i are geometry-dependent corrections.¹⁴³⁻¹⁴⁵ For convenience and consistency with Eq. (4), $P_4 \approx 0.04$ mtorr. The analogous free-molecular-flow conductances, F_M (m³/s), are given by the following expressions:¹⁴³⁻¹⁴⁵

$$F_{M01} = \frac{\pi (r_w^2 - r_3^2)^2}{6 (r_w + r_3) \lambda_1} \langle v_1 \rangle \quad (11A)$$

$$F_{M12} = \frac{4\pi \delta_2^2}{3 \ln(r_3/r_w)} \langle v_2 \rangle \quad (11B)$$

$$F_{M23} = \frac{2 \delta_3^2 \delta_4^2}{3 (\delta_3 + \delta_4) \lambda_3} \langle v_3 \rangle \quad (11C)$$

$$F_{M34} = \frac{2 \delta_5^2 \delta_6^2}{3 (\delta_5 + \delta_6) \lambda_4} \langle v_4 \rangle , \quad (11D)$$

where the average molecular speeds, $\langle v_i \rangle$, are evaluated locally. In the above expressions, the Clausing factors are taken¹⁴⁵ to be $Y_3 \approx 1.2$ and $Y_4 \approx 1.5$, and orifice/aperture corrections have been neglected. The most serious approximation employed in Eqs. (10C) and (11C) is the treatment⁵² of the vacuum plenum as a rectangular duct with effective length $\lambda_3 = (2\pi r_3)/3$. A design allowance for these effects is included in the selection of the reference vacuum-system configuration. For purposes of Eq. (4), the combined conductance beyond the limiter slot is given by

$$\frac{1}{F_{R1}} = \frac{1}{F_{121}} + \frac{1}{F_{231}} + \frac{1}{F_{341}} , \quad (12)$$

for the i^{th} gas species. The appropriate viscous [Eqs.(10)] and free-molecular-flow [Eqs. (11)] expressions are combined by means of Eq. (7) to obtain the local vacuum conductances in the transition-flow regime.

The vacuum system is examined parametrically in the dimensions δ_2 and δ_3 to establish self-consistent combinations with the desired transmission probability, ϵ [Eq. (3)]. The blanket coverage factor, $f_{bc} \equiv 1 - (N\delta_2/\pi R_T)$, depends only on δ_2 for fixed N and R_T . It is desirable that f_{bc} exceed 0.95 from the viewpoints of high blanket efficiency and adequate tritium breeding. For the present, reference design $\delta_2 \leq 0.025$ m yields $f_{bc} > 0.95$. The present configuration with $r_w = 0.75$ m, $\Delta_{FW/SW} = 0.02$ m, $\Delta_{bBLK} = 0.505$ m, $\Delta_{bSLD} = 0.10$ m, and $r_{c\phi} = 1.4625$ m is consistent with $\delta_3 = 0.055$ m. These constraints are imposed on the results displayed in Fig. III.J-3, showing ϵ for the He/DT exhaust gas mixture as a function of δ_2 and δ_3 . Since $\epsilon_1 > (1 - R_1)/F_1 \approx 0.4$ is necessary to satisfy plasma impurity requirements, the region of heavier-lined contours of $\epsilon > 0.4$ on Fig. III.J-3 are of present interest. A more-sophisticated model, including the flow impedance introduced by orifices and bends or the insertion of limiter/first-wall coolant headers in the vacuum channel (Sec. III.L.3.), can be expected to degrade this initial estimate of system performance. This degradation is anticipated here by selection of a design point near the $\epsilon = 0.5$ contour rather than the $\epsilon = 0.4$ contour. Table III.J-II gives parameters for this interim vacuum-system design.

Pending a more-detailed analysis consistent with a "design to construct," geometric parameters are chosen conservatively in anticipation of unaccounted orifice and elbow impedances while simultaneously meeting the vacuum-system performance goals without seriously reducing blanket coverage. Because the vacuum calculation is coupled to the results of the edge-plasma/limiter model (Sec. III.H.), a significant change in the results of that analysis should prompt a reassessment of the vacuum system as well. Possible changes in the vacuum-system design resulting from modest changes in the limiter design can be estimated qualitatively. For example, a decrease in the limiter-slot length, l_1 , results in an increase in the limiter-slot conductance, F_{01} , and gas backflow. To maintain a given value of the transmission probability, ϵ , the downstream conductance, F_R , must increase to preserve $\gamma = F_{01}/F_R$ for a fixed value of the inversion probability, κ . The larger value of F_R is obtained by increasing δ_2 and δ_3 , all other parameters being fixed. By similar logic, an increase in the limiter-slot length results in a decrease in the required value

Fig. III.J-3. Dependence of He/DT exhaust gas transmission probability, ϵ , on blanket-segment gap thickness, $2\delta_2$, and plenum annular thickness, δ_3 , for the fixed parameters of Table III.J-1. A conservative design point at $\delta_2 \approx 0.02$ m and $\delta_3 \approx 0.05$ m is shown with blanket coverage factor $f_{bc} \approx 0.96$. Operation above (below) the dashed line at $\delta_3 = 0.05$ m requires increases (decreases) in the reference FPC radial build.

of F_R . The smaller value of F_R is obtained by decreasing δ_2 and δ_3 . If the driving pressure, P_1 , at the back of the limiter slot changes, the assumed downstream channel pressures are also changed proportionally. To maintain the reference gas load, for a given geometry (i.e., fixed δ_2 and δ_3), the transmission probability, ϵ , must increase (decrease) as P_1 decreases (increases). Finally, if the value of κ changes, the required target value of ϵ changes in the same direction. The magnitude of the change can be estimated from Fig. III.J-1. If the reference value of F_{01} changes [Eq. (3)], the target

TABLE III.J-II

CRFPR INTERIM VACUUM-SYSTEM DESIGN PARAMETERS

<u>Parameter</u>	<u>Value</u>
Unit-cell plasma chamber volume(m^3)	0.88
Gap between adjacent blanket segments, $2\delta_2(m)^{(a)}$	0.04
Blanket coverage parameter, f_{bc}	0.96
Limiter-slot thickness, $\delta_1(m)$	0.0285
Limiter-slot length, $\lambda_1(m)$	0.19 ^(b)
Radial-gap length, $\lambda_2(m) = \Delta b_{BLK} + \Delta_{FW/SW}$	0.525
Plenum annulus thickness, $\delta_3(m)$	0.05
Effective plenum length, $\delta_4(m) = \lambda_c \phi/2$	0.30
Shield thickness, $\Delta b_{SLD}(m)$	0.10
Exhaust-channel thickness, $2\delta_5(m)^{(a)}$	0.12
Exhaust-channel height, $\delta_6(m)$	0.72
Exhaust-channel length, $\lambda_4(m)$	0.75
Reflection coefficient, R_{DT}	0.90
Edge-plasma recycling coefficient, R_{Le}^*	0.80 ^(b)
Scrapeoff recycling coefficient, R_{LS}^*	0.68 ^(b)
Inversion probability, κ_{DT}	0.69 ^(b)
Fraction of particles into limiter slot, f_{DT}	0.24 ^(b)
Transmission probability, ϵ	0.49 ^(c) [0.40 ^(d)]
Conductance ratio, $\gamma = F_{O1}/F_R$	8.35
Limiter-slot conductance, $F_{O1}(m^3/s)$	16.7
Vacuum-channel conductance, $F_R(m^3/s)$	2.0
Total He gas load, $\phi_{He}^{STP}(Pa\ m^3/s)$	3.66
Total DT gas load, $\phi_{DT}^{STP}(Pa\ m^3/s)$	5.5
Total He mass flow rate (kg/s)	$6.5(10)^{-6}$
Total DT mass flow rate (kg/s)	$2.7(10)^{-4}$

^(a)The unit-cell value is doubled to give the ($N = 24$) sector value.

^(b)From Table III.H-II.

^(c)Value provided to allow for orifice and elbow effects.

^(d)Optimistic minimum requirement resulting from idealized model.

value of ϵ changes in the opposite direction to preserve the value of R_{DT} . Generally, a moderate amount of flexibility exists in the FPC vacuum and gas load design to accommodate changes in other subsystems with boundaries that define vacuum ducts and associated conductances.

2. Pellet Fueling. One approach for refueling a fusion reactor is the periodic injection of cryogenic ($\rho_0 \approx 250 \text{ kg/m}^3$) DT pellets.¹⁴⁶ As the pellets penetrate the plasma, ablation or evaporation contributes to the particle inventory. Larger initial pellet radius or higher injection speed allows deeper penetration into the plasma. It is desirable to limit the individual pellet particle inventory to a small fraction, g , of the nominal plasma particle inventory to reduce fluctuations in the density and fusion power during refueling. The time interval between pellet injection is $\tau_I(s)$.

The pellet ablation process has been considered by several authors.¹⁴⁷⁻¹⁵⁰ The basic model applied here is the so-called "neutral ablation cloud" model.¹⁴⁸ Corrections for the perturbation of the local magnetic field by the pellet lead to somewhat (up to $\sim 50\%$) reduced pellet ablation rates and longer lifetimes.¹⁴⁹ The surface ablation of a spherical pellet with initial radius $a(m)$ is represented by the following expression for the time-rate-of-change of the pellet radius:¹⁴⁸

$$\dot{a}(m/s) = \frac{-1.0(10)^{-8} n_e^{1/3} T_e^{5/3}}{a^{2/3} m^{1/3}}, \quad (13)$$

where $m(\text{amu})$ is the molecular weight of the fuel (e.g., 5 amu for DT), $n_e(m^{-3})$ is the target plasma electron density, and $T_e(\text{keV})$ is the target plasma electron temperature. Integration of Eq. (13) in the form

$$\int_0^a a^{2/3} da = \int_0^{t_p} \frac{-1.0(10)^{-8} n_e^{1/3} T_e^{5/3}}{m^{1/3}} dt, \quad (14)$$

gives the pellet lifetime, $t_p(s)$, or the time after initial injection ($t = 0$) at which the pellet completely evaporates ($a \rightarrow 0$). Assuming a constant pellet injection speed, $u(m/s)$, the maximum pellet penetration distance, $d(m)$, is given by $d = ut_p$. For radial plasma density and temperature profiles of the form

$[1 - (r/r_p)^\nu]$, where $r_p(m)$ is the plasma radius and ν is a parameter, Eq (14) can be rewritten in the following form

$$(3/5)a^{5/3} = \int_{r_p-d}^{r_p} \frac{1.0(10)^{-8} n_{eo}^{1/3} T_{eo}^{5/3}}{m_i^{1/3} u} [1 - (r/r_p)^\nu]^2 ds, \quad (15)$$

where $s = r_p - d$ is the distance along a perpendicular injection trajectory and n_{eo} and T_{eo} are the central ($r = 0$) values of plasma density and temperature, respectively. For the profile approximation used here, $n_{eo} = \langle n \rangle (\nu + 2)/\nu$ and $T_{eo} = \langle T \rangle (\nu + 2)/\nu$. Injection beyond the center of the plasma column is not of interest, so that solutions of Eq. (15) can be limited to the range $0 < d < r_p$. The solution of Eq. (15) is

$$u(m) = 1.67(10)^{-8} \frac{n_{eo}^{1/3} T_{eo}^{5/3} r_p}{m^{1/3} a^{5/3}} \left[\frac{d}{r_p} - \frac{2}{(\nu + 1)} \left(\frac{d}{r_p} \right)^\nu (\nu + 1) + \frac{1}{(2\nu + 1)} \left(\frac{d}{r_p} \right)^{2\nu + 1} \right], \quad (16)$$

which gives the required injection speed as a function of normalized penetration distance, d/r_p , for fixed plasma and pellet properties. Parabolic profiles ($\nu = 2$) for both plasma temperature and density give profiles that are close to the Bessel-function profiles assumed for the CRFPR reference design.

The time interval between pellet injections is given by $\tau_I(s) = M/\dot{M}$, where M is the pellet mass ($\rho_0 = 250 \text{ kg/m}^3$, $n_0 = 3.18(10)^{28} \text{ m}^{-3}$) and $\dot{M} = 2.78(10)^{-4} \text{ kg/s}$ is the required mass flow rate (Table III.J-II). Pellet-fueling parameters for several combinations of assumed ratios of pellet to plasma inventory, g , and normalized penetration distance, d/r_p , are summarized in Table III.J-III. Assuming advanced laser-ablation technology, the pellet injection speed is limited to $u < 100 \text{ km/s}$, requiring $g > 0.1$ and $d/r_p < 0.33$. Near-term injector technology based on pneumatic or centrifugal acceleration can attain $u \approx 2 \text{ km/s}$, which is inadequate for this application. This result is more pessimistic than earlier projections.³⁷ A model including magnetic-shielding effects would give somewhat lower estimates of the required pellet speed. Direct penetration of the pellet to the central plasma may not be

necessary if the fuel can diffuse inward. This diffusion process is assumed for the STARFIRE design,³ which is based only on edge-plasma refueling. Calculation of pellet refueling of the central cell of the MARS design⁵ using a similar model have projected $u \approx 43$ km/s for $d/r_p = 1.0$ and $u \approx 1.2$ km/s for $d/r_p = 0.2$. In both cases, $g = 0.1$ and $a \approx 4$ mm. A similar calculation for the WITAMIR design⁴ yields $u \approx 114$ km/s for $g = 0.1$ and $a \approx 3$ mm. Clearly, deep refueling by pellet injection represents a development area for magnetic fusion in general.

TABLE III.J-III

PELLET-FUELING PARAMETER VARIATIONS^(a)

Pellet Inventory/Plasma Inventory, g:	0.01	0.05	0.10
Pellet radius, a(mm)	0.98	1.67	2.11
Pellet injection time, τ_I (s)	$3.56(10)^{-3}$	$1.78(10)^{-2}$	$3.56(10)^{-2}$
Pellet mass, M(kg/pellet)	$9.89(10)^{-7}$	$4.95(10)^{-6}$	$9.89(10)^{-6}$
Pellet velocity, u(km/s)	↓	↓	↓
Penetration depth, d/r_p :			
0.25	276	113	77
0.333	356	146	99 ^(b)
0.50	487	199	136
0.75	595	243	165
1.0	614	251	171

(a) Fixed parameters: $v = 2$, $\langle n \rangle = 6.55(10)^{20} \text{ m}^{-3}$, $\langle T \rangle = 10$ keV, $r_p = 0.71$ m, $\tau_p = 0.59$ s, DT injection rate, $\dot{M} = 2.78(10)^{-4}$ kg/s.

(b) Interim reference case.

K. Current Drive

Noninductive means of steady-state current drive have been proposed for the RFP.⁷⁸⁻⁸¹ Unlike the tokamak, the toroidal and poloidal currents in the RFP are closely coupled, and it is possible in principle to create a time-average toroidal voltage within the plasma without requiring a time-varying magnetic flux to link the torus. As described in Appendix A, the minimum-energy RFP state is defined¹⁵¹⁻¹⁵² primarily by holding the toroidal flux, ϕ , and the magnetic helicity, $K = \int \vec{A} \cdot \vec{B} \, d\tau$, invariant within a conducting shell of radius r_w surrounding the plasma, where $\vec{A}$ ($\vec{\nabla} \times \vec{A} = \vec{B}$) is the magnetic vector potential and the integration is performed over the volume enclosed by the conducting shell. The magnetic helicity is simply a measure of the degree to which flux tubes within the conducting shell are interlinked. The helicity remains invariant and a global minimum energy is maintained while an external circuit parameter (e.g., voltage, V_θ , applied to a TFC) is varied to change the toroidal flux external to the plasma. Intrinsic plasma processes related to turbulence and instabilities, therefore, generate toroidal voltages and currents within the plasma in order to increase (or reduce) poloidal flux to maintain the helicity constant and the plasma in a minimum-energy state. This nonlinear coupling between plasma and magnetic fields through the F- θ diagram (Fig. II.D-2) can be used to "rectify" current oscillations created at external coils into a net steady-state current within the plasma. This "F- θ pumping" is envisaged to transform toroidal magnetic flux (poloidal currents) into toroidal currents (poloidal magnetic flux) through the plasma "dynamo" responsible for maintaining the minimum-energy RFP configuration.

Little analysis and design beyond that described in Refs. 78-81 is available to describe current-drive systems based on F- θ pumping for either experiment or the reactor. This section describes the process and develops a methodology by which future engineering evaluations of F- θ pumping current drive can proceed. In developing and evaluating these expressions along the lines described in Refs. 78 and 81, the circuit parameters, definitions, and approach summarized in Table III.K-I are used. The plasma is described in terms of K , ϕ , and W_M , and the relationship between these parameters and the circuit variables (i.e., resistances, inductances, currents, voltages) constitutes the overall current-drive model. The time dependence of K , ϕ , and W_M result⁸¹ directly from the Maxwell equations:

TABLE III.K-I

SUMMARY OF DEFINITIONS AND NOTATION USED TO MODEL
"F-θ PUMPING" CURRENT DRIVE

<u>Definition</u>	<u>Parameter</u>
Toroidal voltage on plasma	V_ϕ
Toroidal current in plasma	I_ϕ
Poloidal voltage applied to toroidal-field coil	$V_\theta = \dot{\phi}$
Poloidal current flowing in external conductor	I_θ
Plasma resistance	R_p
Magnetic helicity, where $\vec{B} = \vec{\nabla} \times \vec{A}$	$K = \frac{1}{\mu_0} \int \vec{A} \cdot \vec{B} \, dV_p$
Toroidal flux	$\phi = 2\pi \int_0^{r_w} B_\phi(r) r dr$
Total field energy within conducting shell	$W_M = \int (B^2/2\mu_0) d\tau$
Vacuum toroidal inductance	$L_0 = \mu_0 r^2/2R_T$
Inverse aspect ratio	$\epsilon = r_w/R_T$
Average toroidal field within shell	$\langle B_\phi \rangle = \phi/\pi r_w^2$
Reversal parameter (Fig. II.D-2)	$F = B_\phi(r_w)/\langle B_\phi \rangle = L_0 I_\theta/\phi$
Pinch parameter (Fig. II.D-2)	$\theta = B_\theta(r_w)/\langle B_\phi \rangle = L_0 I_\phi/\epsilon\phi$

$$\frac{dK}{dt} = 2\phi V_\phi - 2 \int \eta \vec{j} \cdot \vec{B} dV_p \quad (1)$$

$$\frac{d\phi}{dt} = + V_\theta \quad (2)$$

$$\frac{dW_M}{dt} = I_\phi V_\phi - I_\theta V_\theta - \int \eta \vec{j} \cdot \vec{j} \, dV_p \quad (3)$$

$$\vec{E} = \eta \vec{j} - \vec{v} \times \vec{B} \quad (E_\phi = \eta j_\phi - \alpha B_\phi) \quad , \quad (4)$$

where the last expression gives an Ohm's law corrected for the plasma dynamo effect. With the plasma resistance defined by

$$I_{\phi}^2 R_p = \int \eta \vec{j} \cdot \vec{j} dV_p, \quad (5)$$

the plasma helicity, flux, and energy equations become

$$\frac{dK}{dt} = 2\phi(V_{\phi} - I_{\phi} R_p) \quad (6)$$

$$\frac{d\phi}{dt} = +V_{\theta} \quad (7)$$

$$\frac{dW_M}{dt} = I_{\phi} V_{\phi} - I_{\theta} V_{\theta} - I_{\phi}^2 R, \quad (8)$$

where in Eq. (1) the helicity dissipative term, $2 \int \eta \vec{j} \cdot \vec{j} d\tau$, is given exactly by $2\phi I_{\phi} R_p$ for the Bessel-function model (BFM). It is readily seen from either Eq. (1) or (6) that if the time-average $\langle dK/dt \rangle$ is to equal zero, then $2\langle \phi V_{\phi} \rangle$ must equal the dissipation term, which means ϕ and V_{ϕ} should be nominally in phase; hence, V_{ϕ} and $V_{\theta} \approx \dot{\phi}$ should be out of phase by 90° .

A statement of W_M and $\dot{W}_M \equiv dW_M/dt$ in terms of plasma and circuit parameters is given below:

$$W_M = \frac{1}{2} L_p I_{\phi}^2 + \frac{\phi^2}{2L_c}$$

$$\dot{W}_M = V_{\phi} I_{\phi} + V_{\theta} I_{\theta} - I_{\phi}^2 R_p. \quad (9)$$

The plasma inductance, L_p , is a function of the field profiles and, for example, can be derived using the BFM or variants thereof described in Appendix A. Combining Eqs. (7), (8), and (9) using Faraday's Law ($V_{\theta} = +\dot{\phi}$) leads to the following expression for the toroidal voltage around the plasma, V_{ϕ} :

$$V_{\phi} = I_{\phi} R_p + [L_p + \frac{\theta}{2} \frac{dL_p}{d\theta}] \dot{I}_{\phi} + [\frac{1-F}{\epsilon\theta} - \frac{\epsilon\theta^2}{2L_0} \frac{dL_p}{d\theta}] V_{\theta} \quad (10)$$

Adoption of a positive Faraday's Law for the toroidal circuit is based upon a convention that orients ϕ in the same direction as I_{ϕ} . When the toroidal and poloidal circuits are coupled through the F- θ diagram a) toroidal current can be driven by an applied poloidal (TFC) voltage, V_{θ} , and b) the plasma responds as a nonlinear circuit element through the F- θ diagram. Sinusoidal variations in V_{θ} and V_{ϕ} applied to the TFC and PFC sets thereby couple nonlinearly to drive a net toroidal dc current. Equation (10) has been solved for the complete ZT-40M circuit,⁷⁸ showing the theoretical feasibility of F- θ current drive. In order to solve Eq. (10), the plasma inductance, L_p , must be expressed as a function of the pinch parameter, Λ . Using the BFM field profiles (Appendix A) and equating the total magnetic energy stored within the plasma to $\frac{1}{2} L_p I_{\phi}^2$ gives the following expression for L_p :

$$L_p = \frac{2L_0}{\epsilon^2} [1 + (2F + 1)(F - 1)/2\theta^2] \quad (11)$$

where $F = \theta J_0(2\theta)/J_1(2\theta)$ for the BFM, and included in Eq. (11) is the energy needed to compress an initially uniform toroidal flux into the $B_{\phi} \propto J_0(\mu r)$ distribution. The purely poloidal inductance for the BFM is $L_{p\theta} = 2W_{B\theta}/I_{\phi}^2 = (L_0/\epsilon^2) [1 + (F/\theta^2)(F - 1)]$. The plasma resistance, R_p , used in Eq. (10) is also dependent upon profiles through the factor g_{OHM} , with R_p given by

$$R_p = 2g_{OHM} \langle \eta \rangle / \epsilon^2 R_T \quad (12)$$

where $\langle \eta \rangle$ is the classical resistivity evaluated at the average plasma temperature. For the BFM and a flat temperature distribution, g_{OHM} is given by

$$g_{OHM} = 2(\theta^2 + F^2) - F \quad (13)$$

The profile factor, g_{OHM} , is often referred to as the resistance "anomaly"

factor, a notation that can be misleading in that as given above g_{OHM} is a measure of the extended current path resulting from the "screwing-up" of the high-pitch field lines. For the BFM model without deep reversal ($\theta < 1.6$), g_{OHM} typically is ~ 3 .

The F- θ coupled poloidal and toroidal circuit equations can be solved for I_ϕ once driver functions are selected for ϕ (i.e., $\phi = \phi_0 + \delta\phi \cos \omega t$, $V_\theta = \dot{\phi} = \delta\phi\omega \sin \omega t$) and V_ϕ (i.e., $V_\phi = \delta V_\phi \cos \omega t$). This procedure must be performed with some assurance that the time-averaged magnetic helicity is constant. The constraint that the time average of dK/dt should be zero can be used to establish limits on the magnitude of the field oscillations required to sustain a given toroidal plasma current. If the ohmic dissipation for both the induced and driven cases are similar, and if the induced case operates with ϕ_0 and $V_{\phi 0}$ for $dK/dt = 0$, then dK/dt for the driven case is given by Eq. (6) with $V_{\phi 0} \equiv I_\phi R_p$. Hence,⁸⁰

$$\frac{dK}{dt} \approx 2\phi(V_\phi - V_{\phi 0}) \quad (14)$$

Using the driver functions given below,

$$\phi = \phi_0 + \delta\phi \cos \omega t \quad (15A)$$

$$V_\phi = \delta V_\phi \cos \omega t \quad , \quad (15B)$$

the following expression for a time average of dK/dt for the driven case results:

$$- \langle dK/dt \rangle = \delta\phi\delta V_\phi + 2\phi_0 V_{\phi 0} \quad (16)$$

For $\langle dK/dt \rangle \approx 0$, the following conditions on the amplitudes of toroidal flux and voltage oscillation result:

$$\left(\frac{\delta\phi}{\phi_0}\right)\left(\frac{\delta V_\phi}{V_{\phi_0}}\right) \approx -2 \quad . \quad (17)$$

Given that toroidal flux oscillations much above $\delta\phi/\phi_0 \approx 0.2-0.3$ are expected to impact seriously the RFP configuration, the ac toroidal voltage needed to drive a dc toroidal current with $\langle dK/dt \rangle \approx 0$ can be 6-10 times greater than the voltage needed to sustain an inductively driven RFP current drive. The ac toroidal voltage probably will have to be applied at a frequency that is above $1/(\text{diffusion time})$ but lower than $1/(\text{relaxation time})$.

Many physics and engineering questions remain to be address before the viability of F- θ pumping for RFP current drive can be assessed. Of particular concern and importance are the following issues:

- Effects of $\delta I_\phi/I_\phi$ and $\delta\phi/\phi$ variations on
 - bulk-plasma transport
 - plasma-edge effects (limiter and divertor performance)
 - constancy of first-wall thermal loading, fusion yield, and blanket power density.
- Overall plant efficiency
 - magnitude of reactive power and fraction of total stored energy transferred
 - efficiency or Q-value of F- θ pumping current-drive.
- Overall FPC layout
 - use of separate versus main coils to oscillate B_ϕ and B_θ at the plasma surface, and position of driver coils if separate from main coils
 - interaction of driver coils with other FPC subsystems, particularly those related to coolant lines, divertors, magnets, and blanket neutronics performance (e.g., tritium breeding).

To assess the tradeoff between $\delta\phi/\phi_0$, $\delta V_\phi/\langle I_\phi R_p \rangle$, ω , $\delta I_\phi/\langle I_\phi \rangle$, reactive power, P_R , and the energy stored in the current-drive circuits, E_s , Eq. (10) has been solved numerically for the BFM under the constraint that $\langle \dot{I}_\phi \rangle$ and $\langle \dot{K} \rangle$ are zero. The voltage drive functions given by Eq. (15) are used, and

Table III.K-II lists the F and θ dependences of R_p and L_p , as dictated by the constant- μ BFM, as well as key plasma parameters. The dependencies of $\delta I_\phi / \langle I_\phi \rangle$, $\delta V_\phi / \langle I_\phi R_p \rangle$, P_R , and E_S on $\delta\phi/\phi_0$ and ω are shown on Fig. III.K-1 for the CRFPR operating conditions and the BFM. Selecting $\delta\phi/\phi_0 \approx 0.01$ yields a value of $\delta I_\phi / \langle I_\phi \rangle$ near the minimum of 0.003; reduced $\delta V_\phi / \langle I_\phi R_p \rangle$ relative to the value at the $\delta I_\phi / \langle I_\phi \rangle$ minimum are possible if higher I_ϕ oscillations are tolerable. Table III.K-II gives the associated parameters for this current-drive design point. For this closely coupled system the dissipative power, $P^* \approx 5.74$ MW, entirely supplies the plasma ohmic losses and gives a current-drive efficiency of $\langle I_\phi \rangle / P^* \approx 3.2$ A/W, which is expected to decrease by ~ 2 for an engineered current-drive system. The energy stored in the poloidal and toroidal current-drive circuits is 0.26 MJ. For the Modified Bessel-Function model (MBFM) and $T(r) \propto J_0(\mu r)$ the expected plasma resistive dissipation (Sec. III.G.) is 25.3 MW. If the OHC current were driven to zero ($P_{OHC}^0 = 72$ MW), once achieving steady state, a maximum of 36 MW current drive at 50 % efficiency would be available without degradation of the overall reactor power balance.

To assess the effects of using more-realistic μ profiles, the calculations depicted in Fig. III.K-1 were repeated using the MBFM (Appendix A). The magnetic fields for the MBFM are obtained by numerically integrating Eq. A-45 (Appendix A) with a μ profile that is constant in the range $0 < r < \alpha r_p$ and ramps linearly to zero for $\alpha r_p < r < r_p$, with α given by Eq. A-56. The pressure profile is held proportional to $J_0^2(\mu r)$ and normalized to correspond to the $\beta_\theta = 0.23$ design point (Table III.G-I). The resulting magnetic-field profiles are used to generate the reversal parameter, F , and the total magnetic energy, W_M , from which L_p can be derived as a function of θ . A cubic spline fit to $L_p(\theta)$ is used to generate $dL_p/d\theta$. A comparison of F , L_p , and $dL_p/d\theta$ derived from the BFM and MBFM are presented in Fig. III.K-2. The MBFM results in a reversal that is less shallow for the same θ than obtained for the BFM; a smaller inductance and a substantially smaller value of $dL_p/d\theta$ for $\theta > 1.3$ also result. A minor anomaly occurs in $dL_p/d\theta$ at $\theta \sim 1.2$ because of a discontinuity in the derivatives of L_p of all orders; this discontinuity does not affect the calculations since the region of interest is $1.4 < \theta < 1.7$.

Another consequence of the MBFM is that Eq. (6) becomes an approximation to Eq. (1) because of the varying μ profile. The conservation of helicity and energy denoted by Eqs. (6) and (8), therefore, cannot be satisfied simultaneously. A conserving set of equations can be recovered by introducing a

TABLE III.K-II

CRFPR PLASMA PARAMETERS FOR A
1000-MWe(net) MINIMUM-COE DESIGN POINT USED TO
SIMULATE F- θ PUMPING CURRENT DRIVE

<u>PLASMA PARAMETER</u>	<u>VALUE</u>
Minor plasma radius, $r_p(m)$	0.71
Major toroidal radius, $R_T(m)$	3.8
Inverse plasma aspect ratio, $\epsilon = r_p/R_T$	0.19
Average plasma temperature, $T(keV)$	20.[flat]
Average plasma density, $n(10^{20}/m^3)$	5.[$J_0^2(\mu r)$]
Toroidal plasma current, $I_{\phi 0}(MA)$	18.5
Energy confinement time, $\tau_E(s)$	0.23
F- θ model [$F = \theta J_0(2\theta)/J_1(2\theta)$]	BFM
Reversal parameter, $F = B_\phi(r_w)/\langle B_\phi \rangle$	0.0-(-0.6)
Pinch parameter, $\theta = B_\theta(r_w)/\langle B_\phi \rangle$	1.2-(-1.4)
Poloidal beta, β_θ	0.2
Streaming parameter, $I_\phi/N(10^{-14}A\ m)$	5.8
Classical plasma resistivity, $\langle \eta \rangle (10^{-10}\Omega\ m)$	3.4
<u>CIRCUIT PARAMETERS</u>	<u>VALUE</u>
Toroidal plasma inductance, $L_O(H) = \mu_0 R_T \epsilon^2 / 2$	8.3(10) ⁻⁸
Poloidal plasma inductance, $L_p(H) =$ $(L_O/\epsilon^2)[1 + (F/\theta^2)(F - 1)]$	(2.4-3.6)(10) ⁻⁶
Toroidal flux, $\phi_O(Wb) = L_O I_\phi / \epsilon \theta$	5.9-6.9
"Screw-up" factor, $g_{OHM} = 2(\theta^2 + F^2) - F$	2.9-3.0
Plasma resistance, $R_p(ohm) = 2g_{OHM}\langle \eta \rangle / \epsilon^2 R_T$	1.5(10) ⁻⁸
Plasma poloidal flux, $L_p I_\phi(Wb)$	44.-66.
Plasma ohmic voltage, $V_\phi = I_\phi R_p(V)$	0.3
Plasma decay time, $L_p/R_p(s)$	164.-234.

TABLE III.K-III

TYPICAL F-θ PUMPING CURRENT-DRIVE PARAMETERS

<u>PARAMETER</u>	<u>VALUE</u>
Fractional Flux Swing, $\delta\Phi/\langle\Phi\rangle$	0.01
Voltage Swing, $\delta V_\phi/\langle I_\phi R_p \rangle$	200.
Toroidal Voltage, $\langle I_\phi R_p \rangle$ (V)	0.31
Current Swing, $\delta I_\phi/\langle I_\phi \rangle$	0.0042
Current Swing, δI_ϕ (MA)	0.078 ^(a)
Frequency, ω (Hz)	50.
Dissipative Power, P^* (MW)	5.74
• Poloidal, P_θ^* (MW)	3.44
• Toroidal, P_ϕ^* (MW)	2.30
Efficiency Factor, $\langle I_\phi \rangle/P^*$ (A/W)	3.2 ^(b)
Stored Energy, E_s (MJ)	0.26

(a) If the $P_{OHC}^Q \approx 72$ MW were made available entirely to support current-drive inefficiencies once steady state was achieved and the OHC set was run down to zero current, a maximum level of current drive of 36 MW at 50 % efficiency (> 0.26 A/W) would be allowed without changing the overall, base-case reactor power balance. This value compares to the plasma resistive dissipation of 25.3 MW for the MBFM and $T(r) \propto J_o(\mu r)$.

(b) This amounts to $\delta I_\phi/\langle I_\phi \rangle = 0.0042$, which translates to a 1.70% power fluctuation for constant beta.

multiplicative factor into the $2\phi I_\phi R_p$ term of Eq. (6), which contains the appropriate profile weighting. This approach, however, is not warranted since the resistive dissipation described by Eq. (5) and appearing in Eq. (3) is not classical in nature but results from current fluctuations. The procedure adopted here maintains Eq. (6) intact and replaces R_p in Eqs. (8) and (10) with the product $f_A R_p$, where f_A is an effective anomaly factor. By requiring $\langle \dot{K} \rangle = \langle \dot{I}_\phi \rangle = 0$, the factor f_A is determined numerically to be ~ 0.52 for the CRFPR operating conditions (Table III.K-I) using the MBFM. The only difference in the assumed operating conditions for the two models occurs in the pinch parameter, θ , which is 1.25 for the BFM and 1.55 for the MBFM; $F = -0.122$ for both models. In addition, the value of R_p listed in Table III.K-I is used

Fig. III.K-1. Parametric evaluation of Eq. (10) for F- θ pumping current drive using Eqs. (15) as drivers and the plasma parameters listed in Table III.K-I.

independently of the value of θ , which to some extent represents an approximation.

The dependencies of $\delta I_\phi / \langle I_\phi \rangle$, $\delta V_\phi / \langle I_\phi f_{ARp} \rangle$, P_R , and E_s on $\delta\phi/\phi_0$ and ω are shown on Fig. III.K-3 for the MBFM. The minimum in $\delta I_\phi / \langle I_\phi \rangle$, P_R , and E_s for the MBFM are slightly shallower and occur at higher values of $\delta\phi/\phi_0$ compared to the BFM. Substantially larger differences in these three parameters between the two models occur at values of $\delta\phi/\phi_0 > 0.02$, where the larger-amplitude oscillations in θ can sample the corresponding greater differences in L_p and $dL_p/d\theta$ predicted by the two models (Fig. III.K-2). The MBFM results for $\delta V_\phi / \langle I_\phi f_{ARp} \rangle$ have been

Fig.III.K-2. A comparison of the BFM and the MBFM calculations of F , L_p , and $dL_p/d\theta$ for F- θ pumping current drive.

increased by $1/f_A$ over the BFM, which is directly attributable to using R_p for a resistance in Eq. (6) and $f_A R_p$ for a resistance in Eq. (10).

It remains for future work to model F- θ pumping current drive using even more realistic μ profiles in conjunction with a detailed time-dependent simulation of both plasma and circuit response (Sec. III.G.). The results of such a simulation would be needed to perform a complete circuit design and to integrate the resulting current-drive circuitry realistically into both the FPC mechanical/electrical/thermal design as well as into the CRFPR energy balance. Based on the present scoping analysis of a simplified RFP plasma, however, the

Fig. III.K-3. Parametric evaluation of Eq. (10) with a resistance of f_{AR_p} for F- θ pumping current drive using Eqs. (15) as drivers and the plasma parameters listed on Table III.K-I with S_{OHM} independent of θ .

application of F- θ pumping to drive steady-state currents in reactor-relevant RFPs using relatively low-technology power supplies appears to be promising. The key FPC issues remaining to be resolved revolve around the position and design of these low-voltage/low-current driver coils and the impact of these coils on the blanket neutronic performance if located near the first wall. If the F- θ pumping can be operated at sufficiently low frequency, oscillation of the main TFCs and PFCs become possible, thereby eliminating the impact on blanket performance.

L. Fusion-Power-Core Integration

This section integrates key FPC subsystems described individually throughout Sec. III. This FPC integration is performed at three levels: power-plant energy balance, thermal-hydraulic design, and mechanical design. Specification of a given set of design parameters at a given level of integration requires parameters to be fixed at the previous level. Each are discussed in the order given above.

1. Power-Plant Energy Balance Integration. The power distribution throughout the FPC as suggested by the neutronics analysis (Sec. III.B.) and modified by preliminary designs of first-wall (Sec. III.D.), blanket (Sec. III.E.), and pumped-limiter (Sec. III.H.) subsystems lead to the global power-plant energy balance depicted on Fig. III.L-1. Coupling these results with the more-realistic plasma and circuit simulations described in Sec. III.G. gives the baseline power balance summarized in Table III.L-I.

The power balance used to complete this FPC integration is based on

- water-cooled pumped limiter
- water-cooled first wall and second wall
- water-cooled shield (to reduce manifolding complexity)
- ohmic and nuclear heating in TFC and PFC not used by thermal-conversion cycle
- use of a steam cycle with an intermediate heat exchanger between PbLi loop and steam generator
- aside from ohmic power required by the plasma and coils, all pumping power and other auxiliary needs are held to within $f_{AU} < 0.07$ of the gross electrical power, P_{ET} .

Under these conditions 1403 MW or 41.7 % of the total recoverable thermal energy, $P_{TH} = 3365$ MW, appears in the pressurized-water coolant loop. The total unrecoverable energy deposited into the TFC/PFC set (ohmic plus nuclear heating) amounts to 5.4 % of P_{TH} , with the ratio of total ohmic dissipation, $P_{\Omega} + P_{TFC}^{\Omega} + P_{PFC}^{\Omega} = 164.4$ MW, to the fusion power, $P_N + P_{\alpha} = 2732.5$ MW, being 16.6; the plasma Q-value, $Q_p \equiv (P_N + P_{\alpha})/P_{\Omega}$, is 108. It is noted that although F- θ pumping current drive has been assumed, other than the ohmic dissipation in the plasma, the baseline power balance does not include a separate current-drive power requirement. The current-drive subsystem is not sufficiently resolved for such an assessment, and a closely coupled system has been assumed. If F- θ pumping current drive proves feasible, however, the ohmic power required by the

TABLE III.L-I
CRFPR BASELINE POWER-BALANCE SUMMARY

PARAMETER	VALUE
Major toroidal radius, $R_T(m)$	3.79
First-wall radius, $r_w(m)$	0.75
First-wall area, $A_w(m^2) = (2\pi)^2 r_w R_T$	112.1
Major circumference, $2\pi R_T(m)$	23.80
Fusion neutron first-wall loading, $I_w(MW/m^2)$	19.5
Fusion neutron power, $P_N(MW)$	2186.0
Alpha-particle power, $P_\alpha(MW)$	546.5
Plasma ohmic power, ^(a) $P_\Omega(MW)$	25.3
First-wall (and limiter) nuclear heating, ^(b) $P_{FW}(MW)$	495.1
Second-wall nuclear heating, ^(b) $P_{SW}(MW)$	97.1
Blanket nuclear heating, ^(b) $P_{BLK}(MW)$	2057.6
Shield nuclear heating, ^(b) $P_{SLD}(MW)$	143.3
Recoverable nuclear heating, $M_N P_N (MW) =$ $P_{FW} + P_{SW} + P_{BLK} + P_{SLD}$	2793.1
Energy multiplication, M_N	1.2777
Total recoverable thermal power, $P_{TH}(MW) = M_N P_N + P_\alpha + P_\Omega$	3364.9
Toroidal-field coil heating, $P_{TFC}(MW)$	42.6
• nuclear heating ^(b) $P_{TFC}^N (MW)$	30.0
• ohmic heating, ^(c) $P_{TFC}^\Omega (MW)$	12.6
Poloidal-field coil heating, $P_{PFC}(MW)$	141.0
• nuclear heating, ^(b) $P_{PFC}^N (MW)$	14.5
• ohmic heating, ^(d) $P_{PFC}^\Omega (MW)$	126.5
Fraction plasma power radiated, f_{RAD}	0.9
Fraction transport loss to limiter, f_L	~ 1.0
Fractional limiter coverage, $\lambda_L/(\lambda_L + \lambda_w)$	0.38
Limiter length ($N_L = 24$), $\lambda_L(m)$	0.38
Radiated power, $P_{RAD}(MW) = f_{RAD}(P_\alpha + P_\Omega)$	514.6
Transport power, $P_{TR}(MW) + (1 - f_{RAD})(P_\alpha + P_\Omega)$	57.1
Power to limiter, $P_L(MW) = f_L P_{TR} + (P_{RAD} + P_{FW})\lambda_L/(\lambda_L + \lambda_w)$	440.8
Total power to first wall, $P_{FW}(MW) = (1 - f_L)P_{TR} +$ $[\lambda_w/(\lambda_L + \lambda_w)](P_{RAD} + P_{FW})$	626.0

Power back-leakage from blanket to SW, ^(e) $P_{BL}(MW)$	96.0
Total power to FW/SW system, $P_{FW/SW}^{\downarrow}(MW) = P_{FW} + P_{SW} + P_{BL}$	819.1
Total power to water-cooled first-wall systems ^(f) , $P_{FW/SW} + P_L$	1259.9
Total power to magnet coolant, $P_{TFC}(MW) + P_{PFC}(MW)$	183.6
Estimated thermal-conversion efficiency, η_{TH}	0.365(g)
Gross electric power, $P_{ET}(MW) = \eta_{TH}P_{TH}$	1226.7(g)
Auxiliary power needs, $P_{AUX}(MW) = f_{AUX}P_{ET}(f_{AUX} = 0.05)$	62.6
Ohmic power to FPC, $P_C^{\Omega}(MW) = P_{TFC}^{\Omega} + P_{PFC}^{\Omega} + P_{\Omega}$	164.4
Recirculating power, $P_C(MW) = P_{AUX} + P_C^{\Omega}$	227.0(g)
Recirculating power fraction, $\epsilon = P_C/P_{ET}$	0.185(g)
Plant efficiency, $\eta_p = \eta_{TH}(1 - \epsilon)$	0.297(g)
Net electric power, $P_E(MW) = P_{ET}(1 - \epsilon)$	1000.(g)

(a) Based on peaked temperature profile, $T(r) \propto J_o(\mu r)$.

(b) Refer to Table III.B-V.

(c) For the θ and F values used in the systems code ($B_{R\phi} = -0.68$ T), a continuous TFC would generate 17.6 MW ohmic dissipation. The more-detailed plasma simulations (modified BFM, $\theta = 1.55$, $F = 0.12$, $\beta_{\theta} = 0.23$, $B_{R\phi} = 0.4$ T) and the use of discretized coils gives the value of P_{TFC}^{Ω} used in this power balance.

(d) A continuous PFC set used in the parametric systems code predicts 83.0 MW for P_{PFC}^{Ω} . The results used here are based on the magnetics computations of a discretized PFC set for $P_{EFC}^{\Omega} = 53.5$ MW and $P_{OHC}^{\Omega} = 73.0$, as described in Sec. III.F.2.d.

(e) Estimated in Sec. III.E. as penalty incurred when a structural temperature limit of $\sim 500^{\circ}C$ set by PbLi corrosion limit and amounts to 4.66 % of P_{BLK} .

(f) Amounts to 37.4 % of P_{TH} , which increases to 1403.2 MW or 41.7 % of P_{TH} if the shield, P_{SLD} , is also cooled with pressurized water.

(g) Values based on thermal-hydraulics optimization and integration study described in Sec. III.L.2.

GLOBAL POWER-PLANT BALANCE FOR CRFPR

$$\eta_{TH} = 0.365$$

$$\epsilon = 0.185$$

$$\eta_P = 0.297$$

Fig. III.L-1. Global power-plant energy balance. Refer to Table III.L-1 for definition of notation. Base-case values are shown.

OHC set (73 MWe) could be reduced to zero, with the corresponding increase in the overall plant efficiency, η_p , of approximately two percentage points. This increase amounts to 73 MWe available a) to sell to the grid and decrease the recirculating power fraction, ϵ , or b) to be applied to the current-drive system. For the latter option, current-drive inefficiencies as low as 0.26 A/W could be supplied without altering the power balance given on Table III.L-I.

The task of the thermal-hydraulic design integration given in the following subsection is to resolve the fluid and manifolding parameters for this dual-media (i.e., pressurized-water and PbLi) power conversion system. These thermal-hydraulic parameters must be defined within the constraints imposed by the need for adequate thermal-conversion and overall plant efficiency, η_{TH} and $\eta_p = (1 - \epsilon)\eta_{TH}$, respectively, and engineering limits associated with system temperature, pressure, manifolding topology, and pumping power. Once η_{TH} is specified, the baseline values listed on Table III.L-I can be applied to determine the recirculating power fraction, ϵ , and hence η_p . Figure III.L-2 depicts this tradeoff, which indicates the desirability for $\eta_{TH} > 0.36$ if η_p is to be maintained above 0.30. Since over 40 % of the thermal power appears in the pressurized-water loop, this power must be used for steam generation rather than being used solely for feedwater heating. A similar power split has been reported for the MARS design,⁶ pointing to a general need for more-careful design consideration of dual-media power cycles as applied to unique fusion needs.

2. Thermal-Hydraulic Design Integration. Sections III.D. and III.E. address general thermal-hydraulic aspects of the first wall/limiter and blanket/shield, respectively, without directly considering the means by which the pressurized-water and PbLi power streams would be combined to yield an optimal thermal-conversion efficiency, η_{TH} . In addition, the questions of coolant(s) manifolding, headering, and pumping power must be assessed from both viewpoints of FPC assembly and maintenance and gross power balance. Furthermore, these issues must be resolved at this level of study on the basis of the one-dimensional neutronic studies given in Sec. III.B.; preliminary sensitivity studies of obvious multidimensional effects resulting from more-detailed design can be found in Appendix C, although these results are not directly incorporated into the present study. On the basis of the power flow given in Sec. III.L.1., the first-wall/limiter/shield system delivers a total of 1403 MW to a pressurized-water coolant circuit, and the PbLi-cooled blanket

Fig. III.L-2. Dependence of plant efficiency, η_p , on thermal-conversion efficiency, η_{TH} , for the dual-media system depicted on Fig. III.L-1 and Table III.L-I. The maximum impact of current drive, which allows the current in the OHC to be reduced to zero, is also shown.

receives 1962 MW for a total of 3365 MWt. This section addresses the topology questions of manifold/headers and the questions of total pumping power and overall thermal-conversion efficiency from the viewpoint of a fully integrated FPC as constrained by the aforementioned neutronic (tritium-breeding) considerations.

a. Thermal-Conversion Efficiency. The high-heat-flux characteristics of the power flow depicted in Fig. III.L-1 gives the dual-media cycle with a ratio of power to PbLi/H₂O of 1.4. This ratio is not unlike a similar cycle suggested for the MARS design,^{5,6} which has a PbLi/H₂O power ratio of ~ 2.0 . Determination of an optimum cycle efficiency for such dual-media systems is an important area of future work for advanced fusion systems in general but could not be considered by this study. The approach adopted here computes an ideal cycle efficiency and then reduces this ideal efficiency by a factor shown

achievable by more-detailed steam-power-cycle studies. Typically, conversion efficiencies in excess of 75 % of the thermodynamic ideal value can be achieved³ for a single-media power conversion system. It is assumed that the dual-media cycle can also achieve 75 % of the ideal efficiency by using several stages of reheat for a cycle driven by both high-temperature PbLi and lower-temperature pressurized-water coolants. In addition, extraction from the turbine at various pressures will probably be desirable for feedwater heating. Extensive steam-power-cycle analysis and cost tradeoff studies will be needed before the compromise between increased efficiency and system complexity (i.e., reliability and cost) can be resolved.

Figure III.L-3 depicts an ideal thermodynamic conversion cycle in the form of a temperature-entropy diagram for both a single-media and a dual-media system. In computing the ideal cycle efficiency, the following assumptions are made:

Fig. III.L-3. Temperature-entropy diagrams for ideal single-media and dual-media thermal-conversion cycles, where in both cases heat is rejected to a common temperature T_E .

- the heat sources are fluids having specified supply and return temperatures, T_0 and T_1 , respectively.
- heat is transferred from the heat source fluid to an ideal heat engine in a reversible, constant-pressure steady-flow process; temperature differences and frictional losses are assumed zero for this ideal cycle.
- the heat engine rejects heat to a 300-K environment through a reversible, isothermal process.

If P_{TH} is the total thermal heat input and the fraction f_w of P_{TH} appears in the pressurized-water loop, then energy and entropy balances on the water (w) and PbLi (p) streams give the following relationships:

$$f_w P_{TH} = \dot{m}_w c_{p,w} (T_{wo} - T_{wi}) \quad (1A)$$

$$(1 - f_w) P_{TH} = \dot{m}_p c_{p,p} (T_{po} - T_{pi}) \quad (1B)$$

$$\dot{S}_w = \dot{m}_w c_{p,w} \ln(T_{wo}/T_{wi}) \quad (2A)$$

$$\dot{S}_p = \dot{m}_p c_{p,p} \ln(T_{po}/T_{pi}) \quad (2B)$$

where the inlet and outlet temperatures for both streams are depicted on Fig. III.L-3, as are the respective entropy production terms, $\dot{S}_j$. The mass flow rates are $\dot{m}_j$, and the specific heats at constant pressure for the j^{th} fluid are $c_{p,j}$. Since the useful work (electrical power) is $P_{ET}^I = P_{TH} - \dot{Q}$, where $\dot{Q} = T_E(\dot{S}_w + \dot{S}_p)$ is the heat rejection rate, then the ideal efficiency for the conversion of P_{TH} to P_{ET}^I is

$$\begin{aligned} \eta_{TH}^I &= 1 - \frac{\dot{Q}}{P_{TH}} \\ &= 1 - T_E \left[f_w \frac{\ln(T_{wo}/T_{wi})}{T_{wo} - T_{wi}} + (1 - f_w) \frac{\ln(T_{po}/T_{pi})}{T_{po} - T_{pi}} \right] \end{aligned} \quad (3)$$

The real conversion efficiency is taken as $\eta_{TH} = 0.75 \eta_{TH}^I$. As seen from Table III.L-I, $f_w = 0.417$. Since $T_E = 300$ K, the relationships between the various temperatures, flow rates, coolant duct/manifold/header parameters, and pumping powers remain to be determined before η_{TH} can be estimated. The factor 0.75 is assumed achievable at a reasonable cost in a real engineering system.

It is noted that the ideal Carnot efficiency is approached as $T_{wi} \rightarrow T_{wo} \rightarrow T_{pi} \rightarrow T_{po}$, but of course the flow rates, pressure drops, and pumping power become large if a finite amount of power (i.e., P_{TH}) is to be transported through a diminishing temperature difference. The following section examines the major tradeoffs between T_{ij} , system pressures, and pumping powers.

b. Thermal-Hydraulics Design Parametrics Study. Figure III.L-4 depicts the FPC coolant flow pattern for both the pressurized-water and PbLi loops. The simplified methodology described in Secs. III.D. and III.E. has been combined to examine the sensitivity of η_{TH} and pump power to changes in primary design

Fig. III.L-4. Schematic layout of FPC coolant loops showing the pressurized-water and PbLi loops. The relative sizes of the water-cooled limiter, first and second wall, PbLi-cooled blanket, and water-cooled shield have been distorted to illustrate the respective flow paths.

variables subject to the following fixed design parameters and specific constraints:

- Major radius, $R_T = 3.79$ m
- First-wall radius, $r_w = 0.75$ m
- Number of toroidal segments, $N = 24$
- Pump efficiencies, $\eta_{PUMP} = 0.75$
- Generator efficiency, $\eta_{GEN} = 0.98$
- Thermal-conversion efficiency, $\eta_{TH} = 0.75\eta_{TH}^I$
- First-wall, second-wall, limiter, and blanket/shield dimensions
- Limiter coolant-channel geometry (Table III.D-II)
- Cooling loads and heat fluxes of all components (Table III.L-I)

With these parameters fixed, the following limits and constraints are imposed:

- PbLi outlet temperature, $T_{po} = 773$ K
- Minimum water subcooling in first/second wall and in limiter coolant channels, $\Delta T_{SAT} = 10$ K
- Maximum water flow velocity in all channels and manifolds, $v = 10$ m/s
- Total pump power must remain less than $f_{AUX} = 0.07$ of the total electric power, P_{ET}

Upon establishing these fixed or constrained variables, the sensitivity of η_{TH} and pump power was examined as a function of the following design variables:

- cooling-water pressure
- inlet cooling-water temperature, T_{wi}
- inlet PbLi temperature, T_{pi}
- number of first- and second-wall coolant tubes allowed to operate in series
- inside diameter of first-wall coolant tubes, d_i

Using this hierarchy of fixed, constrained, and variable parameters, an optimizing procedure was used to compute individually design parameters for the limiter, the first/second wall, the shield, and the blanket. A design estimate for the pressurized-water manifold/header system, pumping power, and cycle efficiency was then obtained. Each computation is described separately below.

Limiter Analysis. An initial inlet coolant velocity is assumed for the limiter, and an energy balance is used to determine the mass flow for a fixed coolant-channel geometry (Sec. III.D.2.b.). A thermal analysis determines the

bulk water temperature and corresponding inner-wall temperature at the leading edge of the limiter; this location is viewed as the critical design point for the limiter. If the coolant temperature at this critical point is less than the saturation temperature by more than ΔT_{SAT} , the flow velocity is adjusted until this condition is satisfied. Upon convergence, the pressure drop and associated pumping power for the limiter are determined.

First-Wall/Second-Wall Analysis. By means of a thermal stress analysis and a given inside tube diameter, the tube-wall thickness and outside diameter are determined (Sec. III.D.2.a.). These dimensions combine with other fixed reactor dimensions to determine the number of first-wall tubes for each of $N = 24$ toroidal sectors. For a given value of T_{WO} , energy balance determines the mass flow rate through the tube. The minimum coolant-water subcooling is determined through a thermal analysis, and T_{WO} is iteratively adjusted until the design coolant subcooling, ΔT_{SAT} , is achieved. Upon convergence, the pressure drop and pumping power are computed along with the mass flow rate through the first-wall/second-wall system, which for the purposes of this analysis is assumed simply joined in series.

Shield Analysis. The heat fluxes and power densities for the shield are low compared to the limiter and first/second-wall systems. Generally, the shield coolant temperature is operated at the allowed subcooling, ΔT_{SAT} , and energy balance determines the required mass flow rate. Typically, the pumping power and pressure drop for this system are small.

Pressurized-Water Manifold/Header Design. These systems consist of manifold, inlet headers, and outlet headers for both the limiter and first-wall/second-wall systems. Sizing of these systems to a minimum that is consistent with pressure-drop and pumping-power constraints is important from the viewpoint of assembly and the amount of blanket and vacuum-systems "real estate" required for mutual accommodation. The previously computed mass flow rates are used along with a specified allowable flow velocity to determine inside diameters of the various manifolds and headers. Separate manifolds and headers are specified for each inlet and outlet circuit for each of $N = 24$ toroidal segments. A stress analysis is used to compute the tube-wall thicknesses and, hence, outside diameter and FPC space allocation. Pressure drops, including local losses in bends, and pumping-power requirements are estimated for each manifold/header and added to that of the system being served.

Blanket Analysis. With the PbLi inlet temperature, T_{pi} , specified, energy balance gives the mass flow rate, which in turn yields the pressure drop and pumping power using the MHD equations, field profiles, and poloidal coolant-duct configuration described in Sec. III.E.

Cycle Efficiency. The mass flow rates and water outlet temperatures from the limiter, first/second-wall, and shield systems are used to compute the total coolant-water flow rate, $\dot{m}_w$, and mixed-mean temperature, T_{wo} . Using the mass flow rate, pressure drops, pumping power, and PbLi temperatures, the ideal thermal-conversion efficiency, η_{TH}^I , is estimated and reduced by 75 % to give η_{TH} . The turbine output, P_{ET} , is the product of η_{TH} , $\eta_{GEN} = 0.98$, and P_{TH} .

c. Thermal-Hydraulics Design Parametrics Study Results. This section gives the results of sensitivity studies as the key design parameters were varied. The sensitivity of η_{TH} and $\eta_{TH}(1 - \epsilon_{pump})$ to changes in coolant-water pressure and PbLi inlet temperature, T_{pi} , is shown on Fig. III.L-5, where ϵ_{pump} is the ratio of total pumping power ($\eta_{pump} = 0.75$) to P_{ET} . The corresponding PbLi pressure drop and a direct expression of ϵ_{pump} as a function of T_{pi}

Fig. III.L-5. Effect of PbLi inlet temperature, T_{pi} , and cooling-water pressure on overall cycle efficiency, η_{TH} .

($T_{po} = 500^{\circ}\text{C}$) is shown on Fig. III.L-6. As for the pressurized-water coolant circuit, the PbLi system appears to be limited by pressure and membrane stresses rather than by pumping-power limits. The increase in cycle efficiency is small in the range $T_{pi} = 350\text{--}400^{\circ}\text{C}$, while the blanket pressure increases by 50 %. Although a detailed structural analysis of the PbLi blanket cannot be made until a more-complete design is available, it is anticipated that PbLi pressures above ~ 200 psi will cause difficult structural and fabrication problems that counteract the advantage of low pressure generally attributed to liquid-metal coolants. For these reasons, a PbLi inlet temperature of $T_{pi} = 350^{\circ}\text{C}$ (Fig. III.L-6) is selected for the canonical design.

Fig. III.L-6. Effect of PbLi inlet temperature, T_{pi} , on pumping power and PbLi pressure drop.

The overall efficiency, η_{TH} , increases with increasing cooling-water pressure but with diminishing return as the critical pressure (3206 psi) is approached. Increasing the water coolant pressure above 15.2 MPa (2200 psi) yields little additional increase in thermal-conversion efficiency. The 15.2 MPa value is close to PWR conditions and is selected for this canonical design point. Figure III.L-7 illustrates the effects of inlet coolant-water temperature, T_{wi} , and first-wall coolant-tube inside diameter, d_i , on the thermal-conversion efficiency, whereas Fig. III.L-8 gives the corresponding effects of d_i and T_{wi} on the flow velocity and pressure drop. For inlet coolant-water temperatures above $\sim 190^\circ\text{C}$, the 10-m/s flow velocity limit is exceeded; hence, $T_{wi} \approx 190^\circ\text{C}$ was selected for the canonical design. The minimum allowable coolant-tube diameter needed to assure flow velocities below ~ 10 m/s is approximately 6 mm.

The parametric results given in Figs. III.L-5 through III.L-8 are based on a single-pass FW/SW coolant circuit. No significant increase in efficiency was observed for multiply connected FW/SW tube arrays. Table III.L-II summarizes the key reactor thermal parameters for the canonical design evolved in this section. Tables III.L-III, III.L-IV, III.L-V, and III.L-VI give the key

Fig. III.L-7. Dependence of thermal-conversion efficiency on FW tube diameter and inlet water coolant temperature. The locus of 10-m/s flow velocities is also indicated.

Fig. III.L-8. Dependence of FW tube flow velocity and pressure drop on FW tube diameter and inlet water coolant temperature.

thermal-hydraulic design parameters for the key FPC subsystems as well as manifold/header sizes for use in the FPC mechanical integration.

The sensitivity of the thermal-hydraulics design point being suggested by these parametric results is best illustrated by a plot of $T_{po} - T_{pi}$ versus T_{po} that is constrained by a number of physical limitations. Figure III.L-9 shows the pinch-point limits for a 10-K minimum temperature difference between T_{po} and the steam generator outlet; two steam-generator pressures are shown. With Eq. (3) along with $\eta_{TH}^* = 0.75\eta_{GEN}\eta_{TH}(1 - \epsilon_{pump})$, $\eta_{GEN} = 0.98$, and the reference design values of $f_w = 0.417$, $T_E = 300$ K, and $T_{wo}/T_{wi} = 526.6$ K/463.0 K, lines of

TABLE III.L-II
KEY THERMAL PROPERTIES FOR THE CRFPR CANONICAL DESIGN

<u>PARAMETER</u>	<u>VALUE</u>
Total recoverable thermal power, P_{TH} (MW)	3364.9
Pressurized-water coolant	
• power, P_{THw} (MW)	1403.2
• flow rate, $\dot{m}_w$ (kg/s)	4898.8
• inlet temperature, T_{wi} (K)	463.
• outlet temperature, T_{wo} (K)	536.6
• pressure (MPa/psi)	15.2/2200
• pumping power (MW)	2.8 ^(a)
PbLi coolant	
• power, P_{THp} (MW)	1961.7
• flow rate, $\dot{m}_p$ (kg/s)	72,840.
• inlet temperature, T_{pi} (K)	623
• outlet temperature, T_{po} (K)	773
• pressure (MPa/psi)	1.1/161.
• pumping power (MW)	13.2 ^(a)
Steam-power-cycle efficiency, η_{TH}	0.372
Thermal-conversion efficiency, $\eta_{TH} = \eta_{GEN}\eta_{TH}$	0.365
Gross electric power, P_{ET} (MW)	1226.7 ^(b)
Pump power fraction, ϵ_{pump}	0.013 ^(a)
Ohmic power to coils and plasma (MWe)	164.4 ^(c)
Ohmic power fraction, ϵ_{Ω}	0.134
Auxiliary power fraction, f'_{aux} (less pump power)	0.038
Recirculating power fraction, $\epsilon = f_{aux} + \epsilon_{\Omega} + \epsilon_{pump}$	0.185
Net plant efficiency, $\eta_p = \eta_{TH}(1 - \epsilon)$	0.297
Net electrical power, P_E (MWe)	1000.

(a) Based on $\eta_{pump} = 0.75$.

(b) Based on $\eta_{TH} = 0.372$ and $\eta_{GEN} = 0.98$.

(c) Table III.L-I, $P_{\Omega} + P_{TFC}^{\Omega} + P_{PFC}^{\Omega}$.

TABLE III.L-III
PUMPED-LIMITER THERMAL-MECHANICAL DESIGN PARAMETERS

<u>PARAMETER</u>	<u>VALUE</u>
Number of limiters, N	24
Material	MZC Copper
Overall dimensions	
• toroidal extent, λ_L (m)	0.38
• maximum radial thickness, δ' (mm)	11.5
• stand-off distance from first wall, δ (mm)	40.
Coolant configuration (toroidal flow)	
• channel height (mm)	0.8
• channel width (mm)	4.0
• wall thickness to outside surface (mm)	0.8
• wall thickness between channels (mm)	1.00
• number of channels per limiter	942.
Limiter thermal rating	
• total cooling rate for all limiters, P_L (MW)	440.8
• design heat flux, q_D (MW/m ²)	6.0
• maximum limiter temperature (K)	645.
Coolant properties (pressurized water)	
• inlet temperature, T_{wi} (K)	463.
• outlet temperature, T_{wo} (K)	545.
• nominal coolant velocity, v (m/s)	10.0
• total mass flow rate, $\dot{m}_w$ (kg/s)	1311.2
• pressure drop in channel (MPa)	0.27
Manifold/header properties	
• inlet manifold (behind limiter), ID/OD(mm)	63.0/74.3
• outlet manifold (behind limiter), ID/OD(mm)	66.7/78.6
• inlet header (single radial run), ID/OD(mm)	89.1/105.0
• outlet header (single radial run), ID/OD(mm)	94.3/111.0
• total limiter circuit pressure drop (MPa)	0.55
• limiter pumping power ^(a) (MW)	0.54
• total limiter circuit pumping power ^(a) (MW)	0.94

(a) Pump efficiency is $\eta_{\text{pump}} = 0.75$.

TABLE-III.L-IV
FIRST-WALL/SECOND-WALL THERMAL-MECHANICAL DESIGN PARAMETERS

<u>PARAMETER</u>	<u>VALUE</u>
Number of segments, N	24
Material	MZC Copper/SS
Overall dimensions of segments	
• toroidal extent, $\lambda_w(m) = 2\pi R_T/N$	1.0
• minor radius, $r_w(m)$	0.75
• major toroidal radius, $R_T(m)$	3.78
Coolant configuration (toroidal flow)	
• "D-tube" ID/OD(mm)	6.0/8.0
• number of D-tubes per half-segment (inlet or outlet)	589
• tube-wall thickness, $\delta(mm)$	1.0
• FW/SW flow configuration	single-pass, series
FW/SW thermal rating	
• FW heat flux, $I_{Qw}(MW/m^2)$	5.0
• FW heat-flux power (MW)	319.1
• FW volumetric nuclear heating (peak/average, MW/m^3)	239.0/218.0
• FW nuclear-heating power (MW)	307.0
• FW total power, $P_{FW}(MW)$	626.1
• SW nuclear-heating power, $P_{SW}(MW)$	97.1
• SW back leakage from blanket, $P_{BL}(MW)$	96.0
• total power to FW/SW (MW)	819.1
• coolant inlet temperature, $T_{wi}(K)$	463.
• coolant outlet temperature, $T_{wo}(K)$	518.
• coolant mass flow rate, $\dot{m}_w(kg/s)$	3315.4
Manifold/header Properties	
• inlet manifold, ID/OD(mm)	100./118.
• outlet manifold, ID/OD(mm)	105./123.
• inlet header, ID/OD(mm)	142./167.
• outlet header, ID/OD(mm)	148./174.
• total FW/SW circuit pressure drop (MPa)	0.434
• FW/SW pumping power (MW)	0.91
• total FW/SW circuit pumping power (MW)	1.85

TABLE-III.L-V
BLANKET THERMAL-MECHANICAL DESIGN PARAMETERS

<u>PARAMETER</u>	<u>VALUE</u>
Number of segments	48.
Material	HT-9/PbLi
Overall dimensions	
• toroidal extent, $\lambda_w/2$ (m)	0.48
• radial extent, Δb (m)	0.50
• inside radius (m)	0.775
Coolant configuration (poloidal flow, Fig. III.E-2)	
• channel thicknesses with increasing radius, α_i (m)	0.148/0.136/0.206
• channel thicknesses entering manifold (m)	0.201/0.053/0.036
• channel wall thickness (mm)	5.0
Blanket thermal rating	
• total cooling rate, P_{BLK} (MW)	1961.7
• peak power density (MW/m ³)	255
• Average power density (MW/m ³)	27
• Maximum structural temperature (K)	773
Coolant properties	
• inlet temperature, T_{pi} (K)	623
• outlet temperature, T_{po} (K)	773
• nominal coolant velocity in channels, v_i (m/s)	1.25/0.50/0.23
• nominal coolant velocity in manifold (m/s)	1.29
• total mass flow rate, $\dot{m}_p$ (kg/s)	72,840.
• pressure drop in blanket/manifold (MPa)	1.11
• pumping power (MW) ^(a)	13.2
Manifold/header properties	
• radial extent beyond blanket (m)	0.47
• height(m)	0.30

(a) Pump efficiency is $\eta_{pump} = 0.75$.

TABLE III.L-VI
SHIELD THERMAL-MECHANICAL DESIGN PARAMETERS

PARAMETER	VALUE
Number of segments, N	24
Material	B ₄ C/W/SS/H ₂ O
Total power rating, P _{SLD} (MW)	143.3
Coolant mass flow rate, $\dot{m}_{SLD}$ (kg/s)	272.2
Coolant inlet temperature, T _{SLD,i} (K)	463.
Coolant outlet temperature, T _{SLD,o} (K)	597.

Fig. III.L-9. Thermal-hydraulics operating window for the PbLi-cooled blanket showing pinch-point, pressure, efficiency, and (suggestive) corrosion limits.

constant η_{TH}^* can be generated on Fig. III.L-9. Combined, these limits (e.g., < 200 psi pressure stress, $< 550^\circ\text{C}$ corrosion, η_{TH}^* thermal-conversion/pumping power, 2200 psi pinch-point limits) define a suggested operating window and related design-point sensitivities. Both more-detailed analyses and data bases are required before the engineering and materials sensitivity of the thermal-hydraulic design window illustrated on Fig. III.L-9 can be fully resolved.

3. Mechanical Design Integration. Preliminary consideration has been given to the integration of several FPC subsystems of the CRFPR at a conceptual level to define options in anticipation of more-detailed engineering designs. Constraints imposed include maintenance of the basic reference parameters¹⁵ as modified by the subsystem conceptual designs developed in this study. Summarized below are specific parameter lists used to guide this FPC mechanical design integration.

• Key plasma and FPC characteristics	Table III.G-I
• Overall power balance	Table III.L-I
• Impurity-control (poloidal pumped limiters)	
- physics and mechanical characteristics	Table III.H-II
- thermal-mechanical design	Table III.L-III
• Copper-alloy first wall	
- nuclear	Tables III.B-V, VI, VII
- thermal-mechanical	Table III.L-IV
• Self-cooled PbLi blanket	
- nuclear	Tables III.B-V, VI
- thermal-mechanical	Table III.L-V
• Hot shield	
- nuclear	Table III.B-V, VI
- thermal-mechanical	Table III.L-VI
• Magnet coils	
- nuclear	Tables III.B-V, VI, VII
- TFC	
electrical	Table III.F-III
locations	Table III.F-II
- PFC	
electrical	Table III.F-VIIA, B
locations	Table III.F-VII
• Fueling and vacuum	Table III.J-III

Appendix B gives a standard reactor design table based on the data summarized in the above-listed tables. Only the FPC mechanical integration is considered here, with the interface between the FPC and support systems (i.e., primary containment building, maintenance support equipment, primary heat-transfer circuits, etc.) being treated by future studies.

The choice of the impurity-control system has a strong influence on the FPC layout (Sec. III.H.). The goal of a block maintenance scheme and the minimum FPC weight constraint also influences the FPC layout. The number, size, location, and kind of penetrations through the FW/B/S as well as the positions of the EFCs are determined by these choices. All fluid lines are positioned at or near the outboard equatorial plane to facilitate pumping, power distribution, FPC disconnects, and vertical, single-piece FPC removal and replacement. Figure III.L-10 gives a FPC cross-sectional view, showing the space allotted in

Fig. III.L-10. Cross-sectional view of FPC showing space allotted in the EFC set to accommodate service penetrations. A cross section of the TFTR tokamak experiment³⁶ is also shown for comparison. The TFTR poloidal-field coils have been omitted.

TABLE III.L-VII

FPC MASSES BASED ON NEUTRONICS CANONICAL BLANKET (Fig. III.B-5)

Region	Thickness (m)	Volume (m ³)	Composition	Mass (tonne)
First wall	0.02	2.28	60% Cu, 40% H ₂ O	12.3
Second wall	0.005	0.579	60% PCASS, 40% H ₂ O	2.7
Blanket	0.500	76.9	5% PCASS, 95% PbLi	30.2(a)
Shield	0.10	19.88	40% B ₄ C, 40% W 10% PCASS, 10% H ₂ O	188.9
TFCs	0.075	9.92	70% Cu, 10% PCASS 10% H ₂ O, 10% MgO at 80% density	72.8
PFCs	0.42(b)	108.6		(Subtotal = 307)
• OHC	var.	53.6		
• EFC	var.	55.0		404.
				(Total = 1105)

(a) Contains ~ 720 tonnes of PbLi in blanket and ~ 80 tonnes of PbLi in manifolds to outside of PFC.

(c) Average or smeared thickness.

Fig. III.L-11. Overview of arrangement of PFC components.

Fig. III.L-12. FPC cross section showing FPC support structure, PbLi blanket, and outboard location of coolant ducts (right-hand illustration).

Fig. III.L-13. Illustration of batch maintenance removal/replacement scheme for FW/B/S/TFC torus (C), requiring removal or upper PFC shell assemblies (A and B, 146 and 253 tonne, respectively) prior to the vertical lift of the drained and decoupled FW/B/S/TFC unit (307 tonne).

the EFC set to accommodate these service penetrations. A cross section of the TFTR tokamak experiment³⁶ is also shown for comparison; the TFTR poloidal-field coils have been omitted.

Table III.L-VII summarizes the FPC component masses as modified by discretized the coil sets. The basic components of the 1105-tonne FPC are illustrated in Fig. III.L-11. The relatively tight array of PFCs allows close electrical coupling to the plasma and a minimization of coil mass and stored energy while simultaneously limiting access to the underlying TFCs (73 tonne) and FW/B/S (234 tonne, excluding the ~ 800 tonne of PbLi coolant) to only the outboard equatorial plane. A 1.25-m gap is provided between the two outermost EFCs for all FPC service penetrations. A cross-sectional view of the FPC is shown on Fig. III.L-12, illustrating the PFC support structure and the ducting for the self-cooled PbLi blanket. The FW/B/S/TFC torus (307 tonne, excluding coolants) underlying the 798-tonne PFC set would be installed and removed as a

Fig. III.L 14. Plan view of one of 24 toroidal sectors that are fabricated and assembled off site to form the FPC.

single unit after removal of the top two PFC quadrants, as is illustrated in Fig. III.L-13. The FW/B/S/TFC torus is segmented into 24 toroidal sectors, each centered on a TFC, for purposes of off-site fabrication and assembly. The ~1100-tonne PbLi-filled (720 tonne in blanket and 80 tonne in manifolds to outside of PFC) FW/B/S/TFC torus would be supported from below by a saddle or strongback arrangement extending through the lower gap in the PFC set (Fig. III.L-12).

Figure III.L-14 gives a cross-sectional cut through the equatorial plane of one of $N = 24$ toroidal sectors, illustrating typical components and nominal dimensions. The 24 poloidal limiter blades (one per sector) are arrayed in the TFC midplane. The limiter blade stand-off is 30 mm from the first-wall surface, presenting a total limiter-slot area of $\sim 6.8 \text{ m}^2$, which compares to $\sim 15 \text{ m}^2$ for the toroidal limiter suggested for the STARFIRE tokamak.³ Each of the $N = 24$ toroidal sectors contains two poloidal blanket sections separated by a radically diverging vacuum-pumping slot that connects the back of the limiter to the vacuum plenum formed by the outboard side of the blanket structure and the water-cooled shield and primary structural support. Two right-angle bends are introduced into this vacuum channel to reduce neutron streaming. The shield annulus is also segmented toroidally for purposes of initial fabrication and assembly. This shield defines the outer radial vacuum boundary as well as providing a basic structural member to each toroidal segment. The TFCs would be received by and secured to this structure in order to react overturning and centering forces, small as they may be for the RFP ($\sim 2.7 \text{ MN}$). The low-field TFCs are self-supporting (3 tonne each) against outward radial forces. Square apertures are provided in each structure/shield between TFCs at the outboard equatorial plane for vacuum ducts (to cryopumps or a vacuum tunnel), pressurized-water coolant, and PbLi coolant. Each of the 24 sectors would be welded into a single-piece torus, again with the water-cooled shield providing primary structural support both within and to the FW/B/S/TFC sector.

A crucial issue for the FPC design approach adapted by this study is the need to remove all fusion power and fuel/ash/impurity through the area defined in the vicinity of the outboard equatorial plane by the EFCs and the TFCs. As shown in Sec. III.L.2. (Fig. III.L-4), fusion power would be carried from the FPC by the coolant streams summarized in Table III.L-VIII. A manifolding/headering scheme is suggested in Fig. III.L-15 that meets the thermal-hydraulic criteria established in Sec. III.L.2. The pressurized-water

Fig. III.L-15. Manifolding and headering scheme suggested for each of $N = 24$ toroidal segments to remove heat at the levels given in Table III.L-VIII.

TABLE III.L-VIII

SUMMARY OF POWER AND MASS FLOW FROM FPC PER N = 24 SECTORS

<u>Source</u>	<u>Fluid</u>	<u>Mass Flow (kg/s)</u>	<u>Power (MW)</u>
Limiter	H ₂ O	54.6	18.4
First-wall/second-wall	H ₂ O	138.1	34.1
Shield	H ₂ O	11.3	6.0
Total for H ₂ O		204.0	58.5
Blanket	PbLi	3035.0	81.7
Vacuum	DT/He(10) ⁻⁶	0.27/0.51	- -

manifold for each pumped limiter would be positioned directly behind the poloidal limiter blade as concentric hemicylinders, with a single pair of inlet/outlet headers radially traversing the blanket/shield near the outboard equatorial plane. The limiter detail shown in Figs. III.L-15 and III.L-16 gives the coolant manifolding and flow paths. A number of options for the pressurized-water manifolding/headering scheme for the FW/SW system can be suggested. First, from the viewpoint of minimizing the number of tubes delivering coolant water to the FW/SW, it is desirable to integrate the inlet and outlet manifolds into the respective first-wall and second-wall systems, using only single pairs of inlet/outlet headers at or near the outboard equatorial plane to supply and return coolant. This approach is also illustrated on the orthographic layout given in Fig. III.L-15. Figure III.L-17 gives a detailed view of this FW/SW manifolding scheme in which the separated first-wall (copper-alloy) and second-wall (HT-9) coolant structures would be mated and joined by a return-coolant ring manifold as part of the sector assembly sequence. The adverse effects on the FW/B/S nuclear performance (tritium breeding) by displacing PbLi with presurized-water manifolds near the critical first-wall region and the means by which tritium breeding can be enhanced is discussed in Appendix C. An alternative or backup option for pressurized-water coolant manifolding/headering to correct the deleterious effects on the tritium-breeding ratio expected by the scheme depicted in Figs. III.L-15 and III.L-17 would place the manifolds at or behind the shield

Fig. III.L-16. Detailed view of pumped poloidal limiter coolant circuit.

region. In this case, which is also examined in Appendix C, radial tube sheets located at the intersector positions would deliver and return pressurized-water coolant to and from the FW/SW system. These tube sheets and associated poloidal manifolds would be located at the outer radial surfaces of each toroidal sector rather than within the sector, as was adapted for the approach depicted in Fig. III.L-15. For the purposes of completing this design integration study, however, the manifolding scheme depicted in Fig. III.L-15 is used along with the minor design changes suggested by the sensitivity studies of tritium breeding given in Appendix C. The first-wall manifolding scheme for the arrangement depicted in Fig. III.L-15 is now addressed in more detail.

As seen by the orthonormal sketch given in Fig. III.L-15 and the isometric sketch of a toroidal sector given in Fig. III.L-18, the split-flow limiter coolant would be provided by a concentric, hemicylindrical manifold serviced by $\sim 110\text{-mm-O.D.}$ headers extending radially just above and below the equatorial plane. Each side of the FW/SW within a given sector would also be serviced by independent poloidal manifolds and radial headers. A total of six 110-mm-O.D. pressurized-water headers would be brought out and around the TFCs in the

Fig. III.L-17. Detailed view of the first-wall/second-wall manifolding scheme for the minimum-tubulation option that places inlet/outlet manifolds near the first-wall region.

equatorial plane, as is shown in Fig. III.L-15. Four 40-mm-O.D. pressurized-water pipes would also service the FPC shield in the same vicinity as for the limiter and FW/SW service entries. The 1.25-m vertical gap between the outboard EFCs is acceptable from a magnetics viewpoint (Sec. III.F.2.), giving a vertical-field index of $n = 0.53$. An area of 0.095 m^2 at the TFC current center is allowed for the pressurized-water header galley, the comparable area on the other side of the TFC being dedicated to vacuum pumping. The remaining $\sim 0.39 \text{ m}^2$ (total) is used for PbLi flow to and from each blanket half within the toroidal segment; this flow area is $> 95\%$ of the design goal established in Table III.L-V. Similarly, the pressurized-water headers suggested in Fig. III.L-15 meet the design criteria established in Tables III.L-III and III.L-IV (maximum flow velocity is actually $\sim 12 \text{ m/s}$ in the exit FW/SW headers).

Fig. III.L-18. Detailed isometric view of toroidal FPC sector showing limiter and FW/SW manifolding and headering scheme and the PbLi coolant ducting.

Approximately 10 % of the FW/B/S volume is taken by the manifold/headering scheme suggested in Fig. III.L-15, which reduces the tritium-breeding ratio to below unity since the blanket volume removed is in the high-importance first-wall region. Means to recover the tritium-breeding ratio are a) decrease in first-wall thickness (Fig. III.B-7), b) modestly increase the blanket thickness, c) increase the ${}^6\text{Li}$ enrichment (now is 60%), d) increase the lithium content (i.e., stagnant, canned lithium), e) incorporate more neutron multiplication, f) adopt exoblanke manifolds and the problem of tube sheets making radial connections with the FW/SW system, or g) improve the neutron reflectivity or albedo of the thin, heat-recovering shield. The results of preliminary two-dimensional neutronics studies that explore the above-listed options are given in Appendix C. Emerging from these studies is the desire to a) thin the copper-alloy first wall from 20 mm to 5 mm, b) enrich the lithium from 60 % to 90 % ${}^6\text{Li}$, and c) improve the shield albedo by replacing the

H₂O/B₄C/W shield with H₂O/HT-9. These modifications have little practical impact on the design presented herein but should be incorporated into ongoing reactor design efforts.

Figure III.L-18 gives an isometric sketch of a CRFPR sector, showing the multiturned TFCs. Not shown are the dominant PFCs (Fig. III.L-11) or the current-drive coils. Electrical leads to the multiturn TFCs and PFCs are considerably reduced in size from the coils. In order to maximize the coupling (i.e., minimize stray inductances), the low-current poloidal current-drive coils ideally would be integral with the first-wall/limiter, along with similarly placed toroidal-field current-drive coils. As is shown in Fig. III.B-7 and Appendix C, however, placement of current-drive coils near the first-wall region will adversely effect tritium breeding, and a crucial tradeoff between current-drive and neutronic efficiency remains for future study. The main TFC and PFC sets can be used to drive current, if the drive frequency can be lower than the ~ 50 Hz assumed in this study. If F-θ pumping can be used to drive dc current in the CRFPR, the OHC set shown in Fig. III.L-10 is needed only for startup. Reduction in the size of the OHCs may result, which in turn would also allow a reduced EFC set for the same cost and recirculating power fraction.

Each of the N = 24 toroidal sectors would be fabricated, assembled, and tested at an off-site factory where the environment for quality assurance can be better controlled. Figure III.L-19 concludes this FPC mechanical integration study by depicting a sequence of assembly steps anticipated for a sector assembly. After assembling (Step #1) the TFC and structural shield (S), the left blanket half (LBH) (includes the return SW coolant manifold) is inserted (Step #2) and made captive of the assembly by subsequent welding of the return pressurized-water coolant header (#6) for the left first-wall assembly (LFW). The LFW and the associated inlet FW/SW coolant manifold/header (#1) is inserted (Step #3) and made captive of the assembly upon welding the FW/SW return coolant ring. Step #4 then inserts the limiter (L), along with the associated inlet/outlet headers (#3 and #4). The limiter is made captive of the assembly upon executing Step #5 and inserting the right first-wall (RFW) assembly and its associated inlet coolant header (#2). Step #6 makes the RFW captive of the assembly upon inserting the right blanket half (RBH), the associated SW coolant return header (#5), and the FW/SW return coolant ring. The resulting FPC sector (Fig. III.L-18), upon electrical, fluid, and vacuum testing, would be assembled into a torus (Step #7), again using the shield as the primary structure and

vacuum boundary. The assembly of the full FW/B/S/TFC torus could also be made at the factory site, with fully integrated testing being performed at either the factory, on site, or both.

The scheduled (annual) CRFPR maintenance approach envisages removal/replacement of the inner FW/B/S/TFC torus. A second FW/B/S/TFC torus would be assembled and subjected to pressure, flow, and electrical checkout prior to the substitution. As illustrated in Fig. III.L-13, access to the inner FW/B/S/TFC torus is obtained by decoupling and lifting the upper inner OHC shell (A, 146 tonne) and the upper outer EFC shell (B, 253 tonne). The FW/B/S/TFC torus, (C, 307 tonne) drained of PbLi coolant and remotely decoupled from all electrical and primary coolant lines, is then lifted as a unit vertically out of the saddle formed by the lower PFC shell/base, which remains in place. The FW/B/S/TFC torus is transferred to a hot cell for refurbishment. Attachment of vacuum pumps directly to the FPC and locating the vacuum boundary under the coil annulus, as was done for the STARFIRE tokamak³ and other fusion systems, is possible for the CRFPR. Such an approach is consistent with a stationary FPC and a "patch" maintenance approach. The FPC size reduction for a compact high-power-density device, however, allows serious consideration of batch maintenance, whereby an integrated FW/B/S/TFC torus would be removed and replaced as a single unit. To reduce the encumbrances in handling this unit, it may be preferable to locate the entire PFC in an evacuated chamber. Such a vacuum approach has been proposed for several of the conventional fusion reactors but appears even more practical for compact systems such as the CRFPR, where the total evacuated volume based on a pill-box chamber with $R \approx 9 \text{ m}$ and $h = 5 \text{ m}$ is $\sim 1000 \text{ m}^3$. Design detail of systems beyond the FPC systems is needed, however, before these options can be adequately assessed.

**STEP 1 ASSEMBLE TOROIDAL-FIELD COIL (TFC)
ONTO STRUCTURAL SHIELD(S)**

**STEP 2 INSERT LEFT BLANKET HALF (LBH) AND COOLANT
OUTLET FROM SECOND WALL (#6)**

Fig. III.L-19. Assembly sequence envisioned for each of $N = 24$ FW/B/S/TFC sectors based on a near-first-wall manifold/headering scheme.

STEP 3 INSERT LEFT FIRST WALL (LFW), ASSOCIATED SECOND - WALL COOLANT INLET (#1), AND LFW/LBH COOLANT RING (#1 INLET, #6 OUTLET)

STEP 4 INSERT POLOIDAL LIMITER AND ASSOCIATED COOLANT INLET (#3) AND OUTLET (#4)

Fig. III.L-19, continued.

STEP 5 INSERT RIGHT FIRST WALL (RFW) AND ASSOCIATED COOLANT INLET (#2)

STEP 6 INSERT RIGHT BLANKET HALF (RBH), ASSOCIATED SECOND-WALL COOLANT OUTLET (#5), AND RFW/RBH COOLANT RING (#2 INLET, #5 OUTLET)

Fig. III.L-19, continued.

STEP 7 ASSEMBLY OF FW/B/S/TFC TORUS FROM N=25 SECTORS

Fig. III.L-19, continued.

G. Conclusions

The physics and engineering characteristics of key plasma engineering systems have been broadly described, quantified, and integrated for a high-wall-loading, compact RFP reactor. The economic and operational benefits of the compact high-power-density approach can be attained by the RFP since it is one of a class of approaches that can confine high-beta plasma without excessive toroidal fields at external conductors. Hence, efficient, resistive-coil systems are possible with a FPC mass and volume reduced by factors in excess of 20 when compared with superconducting systems of similar power rating; both reduced cost and single-piece FPC maintenance of a factory-produced system become possible. Furthermore, unique and highly-efficient plasma-heating and steady-state current-drive systems that are inherent to the RFP become a possibility. Although this study stressed impurity control by high-wall-coverage (poloidal) pumped limiters, the ability to use closely-coupled resistive coils allows serious considerations of (toroidal) magnetic divertors and represents a high-priority area for future study; the practicality of magnetic divertors is greatly enhanced by the better coupling allowed in a resistive-coil system. Lastly, although this study stressed the minimum-cost, 1000-MWe(net), $\sim 20\text{-MW/m}^2$ (neutrons) design, detail parametric studies show acceptable cost penalties for lower-wall-loading systems [$5\text{-}10\text{ MW/m}^2$ (neutrons)] of nominally the same physical size but operating with reduced power density and delivering reduced total power. The RFP, therefore, presents a "robust" plasma confinement system capable of providing a range of reactor systems that are compact in both physical size and/or net power output while assuring acceptable cost and levels of engineering feasibility for a range of assumed levels of physics (beta, transport) performance. Maintenance of the regenerative RFP dynamo at higher plasma pressures while retaining the already reactor-relevant beta values with increasing current is central to achieving this ideal end product and, therefore, represents a major experimental objective of the RFP physics program.

IV. ASSESSMENT

This study concludes with an assessment of the physics (Sec. IV.A.) and technology (Sec. IV.B.) needed to achieve the reactor parameters summarized in Appendix B. Section IV.C. gives an economic assessment that indicates directions for future study and design innovation based on results showing quantitatively the tradeoffs between cost, first-wall neutron loading, net plant power, FPC size (mass, complexity, batch versus patch maintenance), and plasma confinement.

A. Physics Assessment

The cost-optimized design suggested in Sec. III.1. and summarized in Appendix B depends on the confinement of a high-pressure plasma by self-generated magnetic fields that are large within the plasma [$B_\phi(0) \approx 9.5$ T, $B_\theta(r_p) = 5.2$ T] and diminish considerably at the coils ($B_{c\phi} = 0.72$ T, $B_{c\theta} = 4.5$ T). The possibility of confining efficiently steady-state plasmas of moderate beta in a minimum-energy state using water-cooled copper-alloy coils located outside a thin high-power-density blanket offers a fusion option with considerable developmental, economic, and operational promise. The RFP is one of a class of confinement schemes with such promise. Rapid experimental and theoretical advances have occurred for the RFP in the 1980s, showing a reactor-relevant scaling [$\tau_E \propto I_\phi^\nu r_p^2 f(\beta_\theta)$, with $\nu > 1$] at reactor-relevant betas ($\beta_\theta \approx 0.1$ - 0.2) but for densities [2 - $5(10)^{19}$ m $^{-3}$] and temperatures (300-500 eV) that remain to be increased by factors of 10-20. These relatively small ($V_p = 0.8$ - 1.0 m 3), low-current ($I_\phi = 0.3$ - 0.5 MA), short-pulsed (2-30 ms) experiments must demonstrate increased confinement times by increasing primarily I_ϕ along with more moderate increases in r_p . Simultaneously, both $\beta_\theta > 0.1$ and an efficient dynamo (i.e., nearly classical resistivities) must be maintained. Progress toward these first-priority physics goals must occur in high-power-density ohmic discharges while simultaneously dealing with high heat and particle fluxes on critical components and maintaining acceptably low values of Z_{eff} and the streaming parameter, I_ϕ/N . Control of field errors, wall conditioning, and the need for active impurity-control and fueling schemes in these inherently smaller, high-current-density devices are also important physics goals. This approach towards ignition, burn, and ultimately the reactor through large increases in plasma current and low-to-moderate increases in minor plasma radius strongly couples engineering technology with plasma physics at an early stage of development. Although presenting problems from a physics

viewpoint, the early coupling of physics and technology in a small, reactor-relevant device may offer significant development advantages related to reduced cost and schedules. The central physics issues summarized above combine with the need to understand better plasma-edge effects and divertor physics in the RFP magnetics geometry. Key issues for the RFP in these latter areas include scrapeoff physics (charge exchange, radiation, transport), the magnitude and direction of electrical sheath potentials, optimal separatrix geometry, control of magnetic islands, divertor channel magnetics, and transport. Lastly and most central to the RFP is the need to resolve better the role played by the conducting first-wall shell in providing plasma stability, particularly with respect to the effects of poloidal breaks and shell penetrations (vacuum, limiter, divertor, etc.). The ability to provide plasma services while minimizing the local field errors is crucial to the control of transport and reducing local peaking of the already high first-wall energy deposition projected for the compact RFP.

B. Technology Assessment

Technology development needs for fusion can generally be assessed according to the following systems:

- Plasma-Heating Systems
 - startup
 - sustenance (ignition)
- Particle-Control Systems
 - fueling
 - particle removal
 - vacuum
- Plasma Current-Drive Systems
- Nuclear Systems
 - in-vacuum components (IVC)
 - blanket (B)
 - shield (S)
- Magnetic Systems
 - TFC
 - PFC (OHC + EFC)
 - divertor coils
 - current-drive coils
 - feedback-control coils
- Electrical and Mechanical Systems
 - energy transfer and storage (ETS)
 - FPC structural support
 - assembly and maintenance
- Tritium Systems
 - fueling and particle control
 - breeding
 - containment
- Balance-of-Plant Systems

The material developed in Sec. III. for each of these reactor systems represents the state of the knowledge for RFP reactor projections, much of this information being extracted and extended from counterpart systems being proposed for the more thoroughly examined tokamak and tandem-mirror reactors. This section summarizes the technology needs, performance requirements, design options, and related key issues that have emerged from this study for each major FPC subsystem.

1. Plasma-Heating System. Plasma heating during startup to ignition is provided by ohmic dissipation of plasma currents induced by a water-cooled copper PFC set operating at low (4-5 T) to moderate (8-9 T) fields. This ~ 25-kV, 2-GJ bipolar system should be easily developed. The means by which the PFC is powered depends on the plasma energy and magnetic flux loss incurred during startup; the RFP scaling used in this study allows the startup power to be supplied from the electrical grid at power levels of 200-300 MWe for times on the order of 8-10 s (Fig. III.G-4) and a total flux of 246 Wb. A worsened

transport, as reflected by the $\tau_E \propto I_\phi r_p^2$ scaling with the current exponent ν falling below ~ 0.8 , increases flux and power requirements, eventually necessitating an on-site energy-transfer element (i.e., a homopolar motor/generator). Even with the added cost of on-site energy storage, the relatively small amounts of stored and transferred energy (2 GJ compared to > 10 GJ for the OHC/EFC set and ~ 50 GJ for the TFC set in STARFIRE³) characterize this system as near state of the art.

Once the DT plasma is ignited, the plasma heating system (i.e., PFC system) must supply $P_\Omega = 25.3$ -MW ohmic losses to the plasma and $P_{PFC}^\Omega = 126.5$ -MW ohmic losses in the PFCs, of which $P_{OHC}^\Omega = 73.0$ MW is dissipated in the OHC set. If F- θ pumping current drive (Sec. III.K.) proves feasible, the OHC current can be reduced to zero, this power then being available to supply the current-drive power needs or for sale to the electrical grid. Generally, in terms of coil current density ($j_{c\phi} \approx 6$ -7 MA/m²), power density (1-2 MW/m³, including nuclear heating), and conductor/structural configuration, these low-voltage coils (< 250 V/turn) require a technology that differs little from that used for TFTR.³⁶ Inorganic (e.g., powdered-MgO) low-voltage insulation that most probably would be co-swaged with the conductor and water-coolant channels will be required to harden these coils for operation in a more intense radiation field, however. In principle, these coils are similar to magnets used in particle accelerators.^{107,108}

2. Particle Control Systems.

a. Fueling. The CRFPR plasma would be refueled by advanced laser-ablation pellet-acceleration techniques rather than presently available pneumatic or centrifugal pellet injectors. The pellet injectors would operate to support or augment plasma-edge refueling at a level that remains to be determined. The CRFPR plasma is 6-7 times more dense than plasmas proposed for fusion approaches like STARFIRE,³ but the factor of 3-4 reduction in plasma radius leads to pellet injector requirements that differ little from the requirements generally envisaged for fusion. Injection of a DT pellet containing ~ 10 % of the plasma inventory every ~ 0.4 s, penetrating one-third of the plasma radius (~ 50 % of plasma volume), requires an injection speed of ~ 100 km/s and advanced laser-ablation technology. Under steady-state conditions, for the same $n\tau_p$, and for similar total fusion powers, the pellet size and injection rate are independent of concept; these needs are generic to magnetic fusion.

b. Particle Removal. As for other fusion systems, considerable uncertainty surrounds the pumped-limiter particle removal scheme adopted for the CRFPR design. A purely batch burn for these more-dense plasmas would give an unacceptably short burn pulse from the viewpoint of pulse power, energy transfer/storage, and thermal-mechanical fatigue; a means of helium-ash removal and impurity control, therefore, must be postulated. The higher average neutron and thermal load at the first wall ($I_w = 19.5 \text{ MW/m}^2$ and $I_{Qw} \approx 5-6 \text{ MW/m}^2$, respectively) requires a larger fraction of the available first-wall area to serve a limiter function for a given split between radiative and convective energy loss from the plasma. Thirty-eight percent of the 112-m^2 first wall is devoted to 24 poloidal limiter, compared to $\sim 7\%$ of the 780-m^2 STARFIRE first wall being devoted to a single toroidal limiter. Both systems require a large fraction, $f_{\text{RAD}} > 0.9$, of the total plasma energy loss to be radiated uniformly over the first-wall limiter area (4.6 MW/m^2 for CRFPR, 1.0 MW/m^2 for STARFIRE) in order that manageable local heat fluxes impinge onto the limiter as particle transport. The average heat flux at the limiter associated only with particle transport is equal (1.3 MW/m^2) for both the CRFPR and STARFIRE. The pumped limiter for both the high-power-density and low-power-density systems represents an advanced heat-transfer system, complicated by potentially high particle fluxes, sputter-erosion/redeposition rates, and neutron damage rates. In terms of heat and particle fluxes, however, the limiter represents a generic issue for fusion and should not be more difficult for the compact approach. The close coupling of the pumped limiter with the first-wall/blanket structure in the CRFPR, however, requires that the limiter survive for the life of the FPC, whereas more frequent changeouts can be postulated for the larger, low-power-density systems.

The plasma for the higher-power-density systems must coexist with a potentially higher instantaneous flux of inward-moving, high-atomic-number impurities, although the total impurity influx and critical impurity fractions for a self-heated plasma are not dependent on power density. Maintenance of a given impurity fraction, however, should be easier for the higher density plasmas. For either high- or low-power-density systems, it may be necessary, therefore, a) to operate with replenishable low-atomic-number coatings (probably more feasible in a system with an order-of-magnitude less first-wall/limiter area), or b) establish a high-atomic-number radiating gas mantle surrounding a plasma that is capable of preventing high-Z impurities from entering the plasma

core. Generally, hot plasma edges are preferred in these circumstances. These ideas remain to be substantiated, and the impurity-transport and gas-recycled models advanced so far for the RFP are primitive, particularly with respect to a self-consistent treatment of edge-plasma radiation, sputtering, and impurity transport. This area deserves considerably more work to guide both existing and planned experiments as well as more-futuristic reactors.

Only preliminary estimates of impurity/ash-control schemes based on magnetic divertors have been made in this study. The ability to divert the minority toroidal field presents an option for the RFP not generally available to the tokamak, which either diverts the minority (poloidal) field and must deal with the problem of interlocked coils, or diverts the majority (toroidal) field and must address the problems of high forces, currents, and degraded (plasma pressure) confinement. Furthermore, the ability to use resistive coils located closer to the plasma leads to a magnetic divertor scheme of considerably enhanced efficiency as measured in terms of energy and space requirements. Resistive divertor coils may in fact be required even in otherwise superconducting low-power-density systems. Examination of the toroidal-field divertor for RFPs is being vigorously pursued for both the reactor and for the near-term, high-current RFP experiments. Key issues for the latter revolve around the increased energy (and cost) stored in the coil set and the effects of local perturbations in the conducting shell that surrounds the plasma.

c. Vacuum Pumping. All steady-state systems of similar total fusion power, governed by essentially the same edge-plasma physics, must deal with similar quantities of exhaust gas ($1.09 \text{ MPa m}^3/\text{s GWt}$ for the CRFPR compared to $0.79 \text{ MPa m}^3/\text{s GWt}$ for STARFIRE³). Expressed per unit first-wall area, the required pump speed for the smaller, high-power-density systems must be greater by approximately the increase in neutron first-wall loading. The increased fraction of the first-wall area that may be devoted to vacuum pumping can be reduced somewhat by a) operating with higher recycle rates, and/or b) taking advantage of the shorter radial flow path (i.e., thinner blanket/shield) to the pumps afforded by the generally smaller FPC. Once outside the FPC, the vacuum-pumping requirement becomes almost independent of concept. The smallness of the high-power-density FPC, however, may make the "vacuum building" more feasible which for the size of the FPC being considered is more aptly termed a "vacuum room" (18-m diameter $\times$ 5-m high).

Generally, the key issues for the vacuum-pumping system remain similar for all fusion concepts: maintenance of acceptable impurity levels; neutron streaming through the vacuum ducts; reduced blanket efficiency (i.e., tritium breeding, energy recovery, shielding); and choices between vacuum building versus vacuum chamber versus vacuum trenches versus individual pumps. Specific to the RFP, however, is the inadequate understanding of the role of the electrically conducting first wall, its function with respect to short-term plasma stability/equilibrium, and the degree to which this conducting first-wall shell can be divided or otherwise segmented for vacuum, impurity control, and assembly purposes. These vacuum slots can also cause field errors that in turn exacerbate the problems of high heat-flux and local peaking. The complexity of each problem and uncertainty in this area taken separately has prevented a clear analytical resolution; coupling these with the problems of locally enhanced transport, equilibrium/stability at local shell gaps, and the vacuum exhaust, therefore, presents an uncertainty that will remain unresolved for some time to come, in spite of its crucial impact on the operating space available for the CRFPR or other similar systems. Progress in this area will more likely occur on the experimental rather than the theoretical front.

3. Plasma Current-Drive System. Only preliminary analyses have been made to estimate the "F- θ pumping" current-drive parameters (Table III.K-II) for the RFP. The model used assumes ideal coupling between the current-drive coils and the plasma. Positioning of these low-frequency (50 Hz), low-voltage (20-40 times the plasma loop voltage or ~ 5 -15 V) coils near the first wall is inferred by these analyses in order to maintain both good coupling and low reactive energy ($E_s \approx 260$ kJ). Since it is desirable to minimize the associated reactive power ($\omega E_s \sim 13$ MW) and to maximize the circuit Q-value, future work in this area should focus on developing means of actively driving oscillating currents in or near each of the 24 first-wall sectors. Furthermore, if lower-frequency current drive (few Hz) is possible, the existing PFC/TFC systems can be oscillated directly. Given that the base-case OHC losses ($P_{OHC}^{\Omega} \approx 72$ MW) could be applied to drive a less-ideal current-drive circuit, considerable margin exists for supplying large current-drive inefficiencies (> 0.26 A/W) without seriously affecting the overall CRFPR power balance and recirculating power fraction. The tradeoff between current-drive efficiency and blanket neutronics performance as affected by increased near-first-wall structure and propensity

for reduced tritium breeding remains a crucial issue for future design studies of the F- θ pumping current-drive circuit.

It is noted that the 0.42 % plasma current fluctuation associated with F- θ pumping current drive translates into a 1.70 % power oscillation under constant-beta plasma operation. This level of fluctuation appears tolerable from the viewpoint of oscillations in the thermal power delivered to all coolant circuits. For the copper-alloy first-wall/limiter system, this power oscillation corresponds to a secondary (thermal) strain fluctuation of $< 10^{-5}$ applied at 50 Hz, and should present no serious fatigue problem. The effects of a ~ 0.42 % fluctuation imposed on the majority (poloidal) edge-plasma field or any minority-field (toroidal) divertor operation must be quantified by future magnetics calculations, but no serious problems are envisaged for magnetic divertor operation in this connection at this time.

Preliminary experimental evidence from ZT-40M indicates that separate oscillation of poloidal and toroid circuits, respectively, is accompanied by a plasma response that maintained an oscillating trajectory along the minimum-energy F- θ diagram. Given the continued operation of an efficient RFP dynamo to maintain the constant-helicity plasma, F- θ pumping of steady-state plasma currents should be possible. Demonstration of current drive in small, low-temperature, resistive plasmas, however, is considerably more difficult than for reactor-grade plasmas. The plasma resistance and dynamo-related anomalies represent a key issue for F- θ pumping current drive. Unlike high-frequency current drives that attempt to modify electron distribution functions to drive a net plasma current, the strong coupling of poloidal and toroidal circuits that allows the possibility for low-frequency F- θ pumping for RFPs actually becomes easier as reactor conditions are approached.

4. Nuclear Systems.

a. In-Vacuum Components. The in-vacuum components (IVCs) include the first-wall, the limiter, divertor channel walls, divertor plates, and other diagnostic surfaces in direct view of cold or hot plasma. This study and the following discussion focuses entirely on the first wall (Table III.L-IV) and limiter (Table III.L-III) issues.

The combination of high average design heat fluxes ($\sim 5 \text{ MW/m}^2$), potentially large fluxes of energetic ($< 1 \text{ keV}$) particles and high neutron fluxes, power densities, and fluences ($< 20 \text{ MW/m}^2$, $\sim 250 \text{ MW/m}^3$, $10\text{-}15 \text{ MWyr/m}^2$, respectively) couples with the major role played by these IVCs on plasma performance,

operational viability (i.e., refueling, impurity/ash control), and overall plant efficiency ($> 30\%$ thermal power received by these systems) to make this system one of the most important and difficult to resolve. The 112-m^2 first-wall area for the CRFPR is comparable to the 62-m^2 limiter area for STARFIRE,³ which has a first-wall area of 780 m^2 ; the limiter area for STARFIRE is $\sim 7\%$ of the total first-wall area, compared to $\sim 38\%$ for the CRFPR. In terms of physical heat flux, the entire first wall for the CRFPR operates under limiter-like heat fluxes, with the actual limiter surface receiving a majority of the particle flux. Both the STARFIRE and CRFPR designs assume $f_{\text{RAD}} > 0.9$ of the alpha-particle and externally applied heating power radiates uniformly over the first-wall/limiter surfaces; both systems have comparable limiter areas which receive nearly the same heat flux in the form of plasma particles (1.3 MW/m^2). Unlike the lower-power-density systems, however, the sputter fluence lifetime (mm erosion) for the CRFPR must occur when the neutron fluence lifetime (MWyr/m^2) is reached, since more-frequent changeout of the limiter alone is probably not feasible for the compact systems. As noted in Sec. IV.B.2., the impact of the erosion rates on the performance of a smaller but more-dense plasma is also an area where more theoretical insight is needed; regenerative, low-Z coatings may also be required, an approach that may be more feasible for the smaller, uniformly high-heat-flux surfaces suggested for the CRFPR.

The key issues for the IVCs envisaged for the CRFPR remain similar to those for fusion in general: the erosion at unknown but potentially serious rates of high-heat-flux surfaces and the possible need for low-Z, erodable coatings. Furthermore, the high-power-density systems are less tolerant of local heat-particle-flux peaking. Although the design of the first-wall/limiter coolant system would be eased by economically allowed reductions in neutron first-wall loading by factors of 2-3 (Sec. IV.C.), the uncertainties in erosion rates and the associated impact on both plasma and IVC design will remain large and crucial. Lastly, the combination of high-heat-flux IVCs and high-power-density blankets leads to the choice of pressurized-water-cooled IVCs and self-cooled liquid-metal breeding blankets, both driving a dual-media thermal cycle; a more complicated and potentially more costly thermal conversion system results if high overall thermal efficiencies are to be maintained (Sec. IV.B.8.).

A long list of nuclear material issues can be identified for the high-strength copper alloys being suggested for the IVCs. Alloy stability in the intensely damaging and transmuting neutron flux under simultaneously imposed thermal and coolant-pressure stresses requires considerable study. A short menu for future work in this area is given below.

- Radiation creep of a stressed, high-performance coolant system.
- Radiation swelling of both dispersion-hardened and solution-hardened copper-alloy systems.
- Effects of large transmutation rates of Cu (Ni and Zn production), causing increased hardness/strength, reduced thermal conductivity, and increased electrical resistivity, depending on final location of the transmutation products (i.e., matrix versus grain boundaries or separate inclusions).
- Fabrication, assembly, and joining methods that allow use of dissimilar metals that may share the same (H₂O) coolant system operating under high pressures (1000 - 2000 psi).
- Effects of helium and gas production within the alloy structure by nuclear reactions and the impact of these gases on mechanical properties.
- Corrosion of copper alloy and ferritic steel by an oxidizing coolant that is subjected to radiolytic decomposition.
- Development of other high-heat-flux alloys that can deal with the above-listed problems.

b. Blanket. The high nuclear power density (255 MW/m³ peak, 27 MW/m³ average) within the PbLi blanket for this $I_w = 19.5 \text{ MW/m}^2$ design point eliminates as an option solid breeders that are separately cooled by pressurized water, molten salts, or pressurized helium gas. The potential for either self-cooled or separately cooled FLIBE was not examined because of the wider thermal and breeding margins afforded by self-cooled liquid-metal blankets. Furthermore, because of reduced chemical reactivity with the pressurized-water coolants used to perform substantial cooling functions for the IVCs, and because of the neutron- and energy-multiplying advantages of lead, the 60% ⁶Li-enriched Pb₈₃Li₁₇ compound was selected initially for the CRFPR blanket. A comprehensive optimization of this high-power-density blanket from materials, thermal, neutronic, and cost viewpoints was not possible; however, the results emerging from other larger studies instead were used, and more optimal blanket designs based on self-cooled PbLi are likely. The CRFPR blanket design (Table III.L-V), however, seems to provide a reasonable choice, would operate efficiently in the

low-field RFP environment, and offers a considerably simplified overall system compared to gas- or water-cooled solid-breeder systems.

The use of a thick (~ 20 -mm) copper-alloy first wall in conjunction with a simpler first-wall/second-wall coolant manifolding scheme degrades the tritium-breeding ratio for the canonical blanket design used in this design study when examined by more realistic two-dimensional models. As shown in Appendix C, the tritium-breeding ratio can be recovered by a) reduced first-wall thickness, b) added enrichment of ${}^6\text{Li}$, c) improved albedo of the thin exoblanet shield, d) modest increases in blanket thickness, e) replacement of the H_2O coolant with D_2O , and f) shifting the water-coolant manifolds from the first-wall region to the mid-blanket region or shield region. The first three design changes (decrease first-wall thickness from 20 to 5 mm, increase ${}^6\text{Li}$ enrichment from 60 % to 90 %, replace $\text{H}_2\text{O}/\text{B}_4\text{C}/\text{W}$ shield with $\text{H}_2\text{O}/\text{HT-9}$) represent minor design changes and would be adopted by future studies. Slight increases in blanket thickness (~ 0.1 m) are also acceptable from the viewpoint of maintaining an optimal design. The use of a D_2O coolant loop is viewed as a costly complication, and the placement of the water-coolant manifolds outside the blanket requires the use of radial, intersegment flow through tube sheets, although no added pumping power would be required; these latter two options are held at lower priority as a means to improve tritium-breeding margins in these thin, high-power-density blankets.

The need to satisfy perceived corrosion limits at the inboard structural (second) wall requires water cooling at that point, the first-wall return coolant being used for that purpose. This design complication causes a somewhat reduced overall thermal efficiency and can possibly be eliminated by a more exacting design of the blanket coolant-duct structure, possibly leading to increased pump power. These kinds of trade studies should be considered in future, more-elaborate studies. A better resolution of structural corrosion limits which are based on coolant-duct plugging problems rather than structural thinning limits could also reduce the need for a separately cooled second wall and the attendant reductions in thermal efficiency, increased design complexity, and a lessened separation of water and liquid-metal coolant circuits. The key issues for this blanket as applied to the CRFPR revolve around the following issues:

- Maximum allowable structural temperature established by plugging-related corrosion limits. This issue strongly effects thermal efficiency, design complexity, safety, reliability, pumping power, and structural alloy choice (austenitics versus ferritics versus refractories).
- Tritium recovery from and inventory in the blanket and primary coolant loops.
- Structural design of blanket to support both the pumping pressures and inertial loads under high-power-density conditions for both transient (including seismic events) and steady-state conditions.
- Removal of heat from a highly nonuniform source while controlling local heating within both the coolant and the surrounding structure.
- Better resolution of the complex tradeoffs between overall nuclear performance, thermal efficiency, pumping powers, operational safety, design complexity, and cost associated with these higher-power-density blankets.

c. Shield. The CRFPR design proposes a thin ($\sim 0.10\text{-m}$) $\text{H}_2\text{O}/\text{Fe}/\text{B}_4\text{C}/\text{W}$ shield positioned outside the blanket to allow $> 99\%$ recovery of the fusion energy and to minimize the nuclear heating in the water-cooled copper coils. This shell also defines the primary vacuum plenum connecting 24 radial intersector vacuum ducts to an outboard, equatorial-plane exit vacuum duct. The primary structural support and fluid-line throughputs for the first wall, limiter, blanket, and TFCs are also provided by this system. The thermal (Table III.L-VI), mechanical, and nuclear demands on this shielding shell are minimal, although this shield forms a keystone to each of the $N = 24$ sectors and provides the assembly for the full FPC torus and the single-piece (batch) maintenance scheme. The means by which these off-site subassembly, assembly, and testing operations would be conducted are based on a highly conceptual design, more detailed studies being required to illuminate problems in a system that at present appears to be straightforward. The key issues for the shield system revolve around the transient and steady-state loads exerted on a system that must react a large and complex array of electromagnetic, high-pressure-fluid, and gravitational forces. Replacement of the tungsten in this shield by other less costly material must also be examined, since the shield comprises 62 % of the FW/B/S/TFC mass. Such redesign is advisable from the neutronics viewpoint also, in that improved albedo would enhance tritium breeding in the thin, high-power-density blanket. The reflector function rather than the shield function should be stressed by future work in this area with the use of

pressurized-water-cooled steel rather than the $H_2O/Fe/B_4C/W$ composite adopted in this study as the canonical design.

d. Afterheat and Radwaste. Only preliminary estimates of the safety and environmental issues related to the higher-power-density FPCs have been made, and the increased concern for nuclear afterheat and radwaste disposal (i.e., near-surface versus deep-geological burial) presents an important area for future study. Loss of coolant to the pumped limiter would result in its temperature increasing to $\sim 67\%$ of the melting point if the limiter radiated to an actively-cooled first wall with an emissivity of 0.4 and without any direct conduction to a heat sink through structural supports. Roughened copper at room temperature can achieve an emissivity of 0.2, and another increase of 0.2 can occur at the operating temperature. Loss of pressurized-water coolant to both limiter and first-wall/second-wall circuits would force these systems to within 79 % and 58 % of the (copper-alloy) melting point if the blanket remains actively cooled. The additional loss of PbLi coolant flow in the blanket will lead to a limiter and first-wall temperature rise that depends on the amount of natural convection allowed by the PbLi coolant circuit. Actual melting of any structural surface is unlikely for emissivities above 0.4, but the resulting thermal excursion will cause alloy changes to an extent that will probably leave overheated components unusable. For emissivities below 0.2 under conditions where all coolant flow ceases and only natural convection in the PbLi is operative, local melting of the limiter may occur. Considerably more modeling, however, is required before the extent of active emergency cooling can be assessed for these high-power-density systems and the dependence of these needs on neutron first-wall loading is resolved. Generally, the afterheat problem is viewed primarily as a problem for the plant investment rather than one of public safety per se; emergency core cooling is expected to be a plant (investment) safety system, unlike the broader role played by similar systems in fission plants.

Neutron activation of the various FPC components has been estimated only at the level described in Table III.B-IX, with an emphasis being placed on the long-term problems of ^{60}Co and ^{63}Ni generated in the copper-alloy first wall, the TFC, and the PFC. The 20-mm-thick ($\sim 2.2\text{ m}^3$) canonical first-wall model will be reduced to 5-mm thickness in future designs for the neutronics reasons described in Appendix C. The estimates of ^{60}Co and ^{63}Ni activity for the 20-mm-thick first wall are based on a one-dimensional beginning-of-life model and give

$1.03(10)^7$ and $2.05(10)^6$ Ci/m³, respectively, after one year of full-power operation at $I_w = 19.5$ MW/m². These concentrations are reduced by factors of $1.8(10)^{-4}/2.9(10)^{-4}$ and $1.1(10)^{-5}/1.7(10)^{-5}$ for $^{60}\text{Co}/^{63}\text{Ni}$ at the TFC and PFC, respectively. The Class A and Class C near-surface burial limits¹⁵³ for $^{60}\text{Co}/^{63}\text{Ni}$, respectively, are 700/35 and ~ 7000 Ci/m³; no entry for Class C burial of ^{60}Co is available.¹⁵³ Hence, in order for the first wall to qualify alone for Class C near-surface burial based on ^{63}Ni , dilution by a factor of ~ 290 would be required. If the first wall remains attached to the (drained) blanket and shield, the intrinsic system dilution factor for the copper-alloy first wall alone amounts to 70, and further dilution by a factor of ~ 4 would be required. The choices between dilution followed by Class C near-surface burial, disposal of a more-concentrated mass in deep-geological burial, or recycle of an important but active material ultimately must be made on the basis of economics and sound environmental/safety practices. Lastly, the radwaste issue for the TFCs and PFCs after one full-power year differ by factors of $2.9(10)^{-4}$ and $1.7(10)^{-5}$, respectively, for the ^{63}Ni isotope; many years of full-power operation should be possible before the Class C near-surface burial limits are exceeded in these PFC components.

The short- and long-term activation of other isotopes in the PFC (e.g., Pb, Fe, minor constituents in the HT-9 and copper alloys) can present problems for near-surface disposal, Ref. 153 listing 27 key elements of concern. More detailed radioactivity analyses remain to be performed for the design reported here or variations thereof. The concerns related to short-term maintenance and long-term radwaste disposal remain to be quantified in terms of related cost penalties and perceived licensing constraints. The tradeoffs between system economics and safety remain to be resolved; the inherently safe, "walk away" PFCs must be operated with such lower power density and high mass utilization as to raise serious questions of economic viability. Similar concerns have been cited even for counterpart approaches suggested for "second-nuclear-era" fission systems.¹⁵⁴ More detailed study is required to resolve whether the associated price is acceptable particularly when a) the afterheat issue for fusion may not be so much a public safety issue as one of protecting the plant (PFC) investment, and b) whether radwaste dilution for near-surface burial should occur by operational design (i.e., lower power density and related alloy choices), be a post-operations decision, or simply be abandoned in favor of more concentrated deep-geological burial.

5. Magnet Systems. The main confining fields are provided by induced and ultimately driven currents that in turn are generated by currents flowing in external TFCs and PFCs. In addition to the TFC and PFC sets, separate current-drive coils may be required, although a crucial tradeoff with blanket neutronics performance remains to be resolved. If very-low-frequency F- θ pumping current drive proves feasible, the primary PFC/TFC system can also be used for current drive. Lastly, feedback control of local instabilities may have to be provided by conductors dispersed outside the blanket/shield area, which like the F- θ pumping current-drive coils would operate with low current and low voltage. The current-drive and feedback circuits and associated performance goals have not been sufficiently resolved to permit an assessment other than the need to resolve better the controlling physics. In addition, little work beyond concept definition has been done for the toroidal divertor coil and associated magnetics. This section, therefore, deals only with the TFC and PFC sets required for plasma confinement.

a. Toroidal-Field Coils. As seen from Table III.F-III, in terms of size (1.46-m current radius, 75-mm radial thickness, 0.6-m toroidal extent, 3.0-tonne mass), peak field ($B_{c\phi} = 0.7$ T), engineering current density ($j_{c\phi} = 7.1$ MA/m²), and ripple constraint ($N = 24$, 0.3 % at the plasma surface), the TFC should not represent a major R&D issue. The strong radiation environment, even outside the thin blanket/shield system, however, necessitates the use of powdered inorganic electrical insulation (e.g., MgO) co-swaged with coolant channels (0.5 MW ohmic, 1.25 MW nuclear per TFC, $\sim 2(10)^4$ r/s) and conductor. The reaction of internal conductor loads, the resolution of body forces (2.7 MN), and the means by which power and coolant are delivered to these multiturn coils have been estimated and should not present a serious design problem.

A key issue for the TFC design is the degree to which current overloading is required during the initial injection of toroidal bias flux just prior to the plasma initiation. The extent to which the RFP dynamo can generate internal toroidal flux from the conversion of toroidal current will dictate the startup demands placed on the TFC system. The present design takes maximum credit for the RFP dynamo, wherein the initial bias field is equal to the final reversed field, $B_{R\phi} = -0.4$ T, and the dynamo ultimately creates the steady-state on-axis toroidal field, $B_{\phi}(0) \approx 9.5$ T, during the ~ 8 -10 s plasma current rise towards ignition. The extreme condition for TFC operation would require the plasma chamber to be filled with a toroidal flux equal to that present in the steady-

state, ignited plasma, $\phi = \langle B_\phi \rangle \pi r_p^2 \approx |B_{R\phi}| \pi r_p^2 / F \approx 5-6 \text{ Wb}$. In this case the initial toroidal bias field would be increased to 3-4 T, requiring a transient current density in the TFC of ~ 10 times the steady-state value; the advantages of increasing the toroidal field within the plasma through the RFP dynamo are apparent.

b. Poloidal-Field Coils. The PFC set dominates the drained FPC mass: 394 tonne for the OHCs, 404 tonne for the EFCs, 73 tonne for the TFCs, and 234 for the FW/B/S, with an additional ~ 800 tonne of ^7Li . The maximum field for the back-biased ($I_\phi = 0.0 \text{ MA}$) condition is 9.0 T, which decreases to 4.5 T upon achievement of the full plasma current ($I_\phi = 18.4 \text{ MA}$). Because of the good electrical coupling between the OHC and plasma, the external PFC current amounts to $I_{c\phi} = 22 \text{ MA}$, and the total stored energy is 1.7 GJ, which is a factor of ~ 6 less than for the STARFIRE³ ($I_\phi = 10.1 \text{ MA}$).

Like the TFC set, the PFCs require only state-of-the-art technology, with the exception of the need for radiation hardening and the use of inorganic (e.g., powdered-MgO) electrical insulation. The tightly integrated FPC requires the lower PFC elements to form a receiving support bed or strong back for the FW/B/S/TFC, whereas the upper PFC elements must be vertically mobile for purposes of assembly and maintenance of the FW/B/S/TFC unit. The conductor gap in the EFC set positioned about the outboard equatorial plane is needed for fluid and electrical services to the FPC and presents no serious magnetics (equilibrium) problem. Considerable mechanical and electrical design is required, however, to assure an optimal electrical lead configuration for these multiple-turn series/parallel conductors; it is expected that PFC conductor locations, sizes, and current densities will change somewhat under closer design scrutiny. The structures and force analyses also have been limited and deserve additional consideration, particularly in view of the role played by the PFCs in the overall support and maintenance scheme. Lastly, the PFC set (i.e., the OHCs, specifically) represents the primary energy storage for a grid-powered startup; the preliminary assessment of this aspect of the CRFPR is given in the following section.

6. Electrical and Mechanical Systems. This section briefly reviews and assesses what little design has been carried out on electrical and mechanical systems that directly support the FPC.

a. Energy Transfer And Storage (ETS). The primary ETS systems would deliver startup power to the PFC, and little information is available beyond the definition of the OHC/EFC circuit given in Table III.F-V. The F- θ pumping current drive and stability/equilibrium feedback control will also require an ETS system, but considerably more work is required before these systems can be defined and, therefore, subjected to a preliminary assessment.

The primary energy storage for the startup power is the OHC/EFC set, which is charged on a 15- to 20-s time scale directly from the electrical grid. With the electrical grid removed from the FPC circuit, the RFP is established and the plasma current is raised to ~ 12 MA in $\tau_R = 1.2$ s, the initial current ramp being 32 MA/s. The electrical grid is then reconnected to the FPC circuit once the required drive power drops to acceptable levels; the plasma current then ramps to the final value of $I_\phi = 18.4$ MA in $\tau_L \approx 8$ s. The peak grid power approaches 350 MWe at 1 kV. Upon ignition and achievement of a steady-state burn, ~ 246 Wb are required (26 Wb resistively consumed). The OHC, EFC, and plasma require 73.0, 53.5, and 24.5 MWe, respectively, to supply ohmic dissipation; it is also proposed to supply this 150.0-MWe load from the electrical grid. As noted in Sec. IV.B.3., the OHC currents would be driven to zero upon initiation of the plasma current drive, with the 73.0-MWe grid power requirement being used in part by the F- θ pumping circuit.

If the startup power requirement is too large, then a rotating machine (e.g., homopolar motor/generator) capable of receiving, storing, and transferring ~ 1 GJ will be required. The use of the power grid versus the use of an infrequently operated on-site ETS system represents a modest economics rather than technical feasibility issue and is influenced most strongly by unresolved physics (transport) issues.

b. FPC Structural Support, Assembly, and Maintenance. The FPC mechanical integration described in Sec. III.L.3. proposes an off-site FPC assembly from 24 identical toroidal segments that have been separately subjected to electrical, thermal-hydraulic, and vacuum testing. After similar tests of the fully assembled FW/B/S/TFC assembly, that unit would be shipped to the power-plant site and loaded into the PFC set and associated support structure. The problem of making and breaking a large number of pressurized-water and PbLi coolant-header connections can be reduced somewhat by partially including these fluid mains into the ~ 300 -tonne FW/B/S/TFC prior to lowering into the cradle formed by the PFC set, pillar supports, and associated strong back. As for any

remote maintenance operation of this kind, the joining of high-pressure coolant lines, high-current electrical leads, and vacuum ducts (if a vacuum pillbox is not used) represents a key development area.

The key engineering issue for the tightly integrated FPC depicted in Fig. III.L-16 is that of system reliability. An assessment of reliability is not possible without a more fully evolved design and (ideally) related operating experience and data base. An interesting trade exists between the mean-time-to-failure and the mean-time-to-repair and should be given high priority in assessing the relative merits of the high-power-density approach, as reflected in the annual plant factor, p_f , and ultimately in the COE. A key issue deserving further study is the relative ease and restart reliability associated with full-FPC maintenance compared to replacement of a small fraction of a considerably larger torus.

7. Tritium Systems. No work was done on tritium system requirements other than the vacuum design presented in Table III.J-I. The technical requirements of fueling and particle control, tritium breeding, and tritium containment for the CRFPR will be similar to other systems based on a self-cooled PbLi blanket. Tritium solubility in and extraction from the PbLi breeder remain as crucial unknowns, with a 1-ppm concentration giving a 0.8-kg blanket inventory; at least as much tritium is expected in the PbLi coolant external to the FPC. Tritium transport into the primary water coolant through the water-cooled second wall represents an area of concern; other water/PbLi interfaces within the FPC are at least doubly contained. For the recycle coefficients listed in Table III.J-I, the flow of tritium through the pellet-injector/plasma/limiter/vacuum loop amounts to $1.7(10)^{-4}$ kg/s, compared to 0.073 kg/s flowing in the PbLi coolant if tritium could be maintained at a 1-ppm level. The rate of tritium leakage from the primary coolant streams into the intermediate heat-exchanger loops and eventually into the environment through the steam generator and turbine cannot be assessed until a steam cycle design is available, but tritium containment in this area is viewed as a crucial issue.

8. Balance-of-Plant Systems. A Balance-of-Plant (BOP) design was not conducted, nor was a specific steam cycle suggested. The power and flow split between the pressurized-water (4900 kg/s, 1403 MW) and PbLi (72,840 kg/s, 1962 MW) coolant loops is such that considerable steam raising will be required by the water loop; the power delivered to the primary coolant water is too large for use only in feedwater heating while simultaneously expecting a good overall

plant efficiency. Hence, the design of a high-efficiency dual-media power cycle represents an important area for future work. A similar area of concern can be identified for the MARS tandem-mirror reactor.^{5,6} The efficient use of dual-media cycles may become a necessity for higher-power-density tokamak reactor designs.

A major goal of the compact, high-power-density approaches is to separate and isolate better the FPC and other nuclear support systems from an ideally nonnuclear BOP. Licensing procedures, construction costs and schedules, quality assurance, and overall plant operations would be considerably improved by a better separation and definition of nonnuclear versus nuclear systems. The level of FPC integration with the BOP provided by this study has not been sufficient to assess the advantages offered by the compact, high-power-density systems in this respect, although strong advantages are perceived on a qualitative basis. Future study should stress this important area, while simultaneously selecting BOP systems and layouts that minimize the pathways between the nuclear FPC and the nonnuclear BOP.

C. Economic Assessment

The CRFPR design originally selected for study from the Ref. 15 parametrics study (Table II.D-III) is a minimum-COE, $P_E = 1000\text{-MWe}(\text{net})$, $I_w = 19.5 \text{ MW/m}^2$ system. Although Figs. II.D-6 and II.D-7 show the effects on COE of decreasing P_E and I_w , respectively, the primary goal of the present study was to examine through a conceptual but fully integrated FPC design the problems and promise of the 1000-MWe, high-power-density reactor. Minimum-COE, 1000-MWe power plants, however, may not present an optimal system with which to demonstrate technical and economic risk for fusion. Furthermore, the choice of the high-power-density, 1000-MWe system was influenced by perceived needs based on recent utility history in the U.S., with unpredictable future markets perhaps requiring a broader spectrum of capacities. Part of that future spectrum possibly may include systems with higher COE if the total capital investment could be reduced. In addition, the technology required of the $I_w = 19.5 \text{ MW/m}^2$ base case being considered here may be too advanced for risk demonstration, and both lower first-wall neutron loading and lower net power systems may be more optimal for purposes of market penetration and confidence building. Lastly, the tradeoff between system performance, cost, and the degree of passive safety is yet to be resolved for fission power,¹⁵⁴ and relevant options should also be considered for fusion. For these reasons, the parametric systems model used originally in Ref. 15 to identify the minimum-COE system of the 1000-MWe(net) class has been used to examine the economics and operational characteristics of lower-wall-loading, lower-power-density CRFPR designs. These systems, nevertheless, remain compact and high-power-density when compared to most superconducting fusion approaches proposed to date, recognizing that the factors of 10-30 in engineering power density that presently separate these two approaches to fusion power give a broad range of options.

1. The Parametric Systems Model. The parametrics model originally reported in Ref. 15 has been generalized by allowing consideration of arbitrary confinement times in search of minimum-COE, resistive-coil RFP reactors. Figure IV.C-1 gives a logic diagram of this model, and Fig. IV.C-2 depicts both the simplified geometry and engineering energy balance used by this model. The overall physics and engineering models, systems approach, and data base are reported in Ref. 15. Table IV.C-I lists both fixed and varied parameters used to assess the cost sensitivity, as well as defining key notation. The fixed physics and engineering parameters list on Table IV.C-I are similar to the

base-case values suggested in Table II.D-III and modified by the analyses given in Sec. III. As indicated on Fig. IV.C-1, the parametrics model identifies optimal system parameters in a set of nested search loops centered on a convergence operation for the engineering Q-value, $Q_E = 1/\epsilon$, and the specified net electric power, P_E , where ϵ is the recirculating power fraction. For a given total coil thickness, δ_c , this inner iteration searches for the value of Q_E that yields the specified P_E as the split between the TFC and PFC geometry varies, subject to the constraints of equal (but unspecified) coil current densities and the matching of fixed engineering and physics parameters indicated in Fig. IV.C-1. The total coil thickness δ_c that produces a minimum-COE design for an otherwise fixed geometry, including plasma minor radius, is first determined after convergence of the set (Q_E, P_{TH}) for a given P_E . The outer-loop optimum is then determined as a function of plasma radius, r_p , which shows a higher-order (lower) COE minimum. Generally, r_p is used as a display variable, with the respective minimum-COE design corresponding to a particular value of P_E and aspect ratio. The outermost loop then varies the plasma aspect ratio, $A = R_T/r_p$, in search of an even lower minimum-COE system, although within realistic bounds, the optimum in A is fairly flat for the RFP. These fully-cost-optimized CRFPR design points are then examined as a function of P_E and the physics, engineering, and economic variables listed both on Fig. IV.C-1 and Table IV.C-I.

2. CRFPR Cost Tradeoffs. This parameter study examines primarily the effects of decreased neutron first-wall loading under conditions of fixed net electric power and under conditions of decreased net electric power. As seen from Fig. IV.C-1, I_w emerges as an output and is expressed as a function of r_p for all minimum-COE designs of constant P_E and A .

The first set of calculations varies the aspect ratio for the $P_E = 1000\text{-MWe}(\text{net})$ design point in order to demonstrate the relative insensitivity of the minimum-COE point to changes in this variable. Figure IV.C-3 shows a shallow COE minimum in A , but for all intents and purposes the COE for these cost-optimized designs is independent of A . Subsequent sensitivity studies, therefore, fix A at the base-case value of 5.35. Shown also on Fig. IV.C-3 is the dependence of the Unit Direct Cost [UDC(\$/kWe)], Q_E , and I_w on r_p , each curve giving the locus of minimum-COE designs for the indicated value of r_p .

Fig. IV.C-1. Logic diagram for the simplified parametrics systems model used to assess economic sensitivity of the CRFPR.

Fig. IV.C-2. Geometry and engineering energy balance used in the simplified parametrics systems model of CRFPR.

TABLE IV.C-I

LIST OF FIXED AND VARIED PARAMETER USED IN COST SENSITIVITY STUDY

PLASMA PARAMETERS	VALUE(BASE CASE)
Minor plasma radius, r_p (m)	Varied (0.71)
Major plasma radius, R_T (m)	Varied (3.80)
Plasma aspect ratio, $A = R_T/r_p$	Varied (5.35)
Plasma density, $n(10^{20}/m^3)$	Varied (6.55)
Plasma temperature, T (keV)	$10[T(r) \propto J_o(\mu r)]$
Profile factors, g_i	BFM(MBFM)
Ignition parameter, $n\tau_E(10^{20}s/m^2)$	1.60 (1.54)
Alcator coefficient, $\tau_E/nr_p^2(10^{-21}s \cdot m)$	5.0(a)
Pinch parameter, θ	1.45(1.55)
Reversal parameter, F	-0.2(-0.12)
Plasma/wall radius ratio, $x = r_p/r_w$	0.95
Poloidal beta, β_θ	0.20(0.23)
ENGINEERING PARAMETERS	
Thermal-conversion efficiency, η_{TH}	0.35
Blanket energy multiplication, M_N	1.30
Blanket/shield thickness, Δb (m)	0.60
Energy transfer and storage efficiency, η_{ETS}	1.0(b)
Auxiliary power fraction, f_{AUX}	0.07
Coil parameters	
• electrical resistivity, $\eta(10^{-8} \text{ ohm} \cdot m)$	1.8
• conductor filling fraction, λ_c	0.7
Net electrical power, P_E (MWe)	Varied (1000.)
ECONOMIC PARAMETERS(c)	
Return on investment (%/yr)	15
Operating cost (%/yr)	2
First-wall/blanket life, $I_w\tau$ (MWyr/ m^2)	15
Plant factor, $p_f = (365 - \tau_u - \tau_s)/365$	<0.76
• unscheduled, τ_u (days/yr)	60
• scheduled, τ_s (days/yr)	
> 1 replacement/yr	$28p_f I_w / (I_w \tau)$
< 1 replacement/yr	28
• unit costs (\$/kg, \$/m ³)	Ref.15(d)

(a)Used for comparison purposes only.

(b)Inferred long-pulsed or steady-state operation.

(c)Based primarily on the guidelines given in Ref. 68 and modified by subsequent large-reactor studies.³ All costs are referenced to 1980 dollars.

(d)Generally conservative relative to the STARFIRE cost data base³ for the FPC costing.

Fig. IV.C-3. Sensitivity of minimum-COE, $P_E = 1000$ -MWe(net) design points to changes in plasma aspect ratio, $A = R_T/r_p$. The $A = 5.35$ curve is the base-case value.

The cost and efficiency changes resulting in the dependence of COE on r_p depicted in Fig. IV.C-3 are caused by a number of competing effects. The following observations are listed to aid the interpretation of these results.

- Increased r_p for a fixed P_E requires that I_w decrease. Since P_E is approximately proportional to $I_w r_p^2 A$, increased A decreases I_w for fixed r_p , as is illustrated on Fig. IV.C-3. This argument is based simply on geometry. As I_w decreases because of increased r_p , the FPC power density decreases, resulting in an increased UDC. The resulting increase in UDC drives COE upward as r_p is increased at fixed P_E and A .
- The increase in COE with increased r_p is also caused by an increase in recirculating power delivered to the resistive coils (i.e., Q_E decreases with increased r_p , as seen from Fig. III.C-3). The Q_E decreases because of increased coil resistive losses. As r_p increases, pressure balance demands slightly increased plasma currents, which in turn will effect the coil currents. Since pressure balance dictates $I_w \propto I_\phi^4 / r_p^3$, the total power is proportional to I_ϕ^4 / r_p , which for fixed P_E and A approximately required $I_\phi \propto r_p^{1/4}$. The coil currents, however, may actually decrease because of better electrical coupling, depending on the value of A when r_p is increased. Increasing r_p for a fixed A increases R_T and hence the coil resistance, which tends to override any decrease in coil current, giving a net increase in resistive coil losses and decreases in Q_E as r_p increases.
- As r_p decreases for a fixed A , the electrical coupling between plasma and coil rapidly decreases, increased coil currents are then required to drive a given plasma current, and Q_E rapidly decreases. The COE rapidly increases as r_p is decreased.
- As r_p decreases for fixed A and P_E , the rapidly increasing $I_w \propto 1/r_p^2$ causes the plant factor, p_f , to diminish, in accordance with the algorithm given in Table IV.C-1. This decrease in p_f also contributes to the rapid increase in COE as r_p is decreased.

In summary, decreasing Q_E and p_f contributes to increasing COE with decreasing r_p , and decreasing (more slowly) Q_E along with increasing UDC causes the COE to increase as r_p increased. The COE optimum depicted in Fig. IV.C-3 results, this optimum being relatively insensitive to A , with a shallow COE minimum occurring near the base-case value of $A = 5.35$.

From the sensitivity analysis given in Fig. IV.C-3 it is clear that systems with lower values of I_w for a given A are possible for increased r_p and moderate increases in COE. Systems with lower I_w are also possible for FPCs of the same physical size as the base case by simply generating less power. The cost tradeoff associated both with off-optimum systems [$r_p > r_p(\text{OPT})$] and lower- P_E systems is displayed in Fig. IV.C-4, where $r_p(\text{OPT})$ is the plasma radius at which the COE is minimized. The general behavior of these curves follows that

described for Fig. IV.C-3. The rapid increase in the minimum-COE as P_E is decreased results from the strong (nuclear) economy of scale built into the costing procedure and data base used,⁶⁸ as depicted graphically on Fig. II.D-7. Again, the increase in COE for plasma radii below $r_p(\text{OPT})$ results from rapidly decreasing Q_E (i.e., poor electrical coupling to plasma) and p_f (i.e., increased I_w and decreased FPC chronological life), whereas the increasing COE for $r_p > r_p(\text{OPT})$ results from decreasing Q_E (i.e., increased coil resistance as R_T increases) and increasing UDC (i.e., increased FPC mass and poorer mass utilization). The values of plasma and coil currents for the parameter study described by Fig. IV.C-4 are shown on Fig. IV.C-5 as r_p varies away from $r_p(\text{OPT})$. As previously noted, operation to the left of the minimum-COE point results in poor electrical coupling, increased coil currents and ohmic losses, decreased Q_E , and rapidly increased COE. In addition, the rapid increase in I_w as r_p decreases also decreases the plant availability, again causing the COE to increase rapidly. The good coupling to the right of $r_p(\text{OPT})$ is not sufficient to overcome the increased coil resistance or the Q_E decreases, and COE increases again.

The changing plasma density and FPC mass utilization that occurs in the parametric variations are illustrated on Fig. IV.C-6. The Alcator parameter, nr_p^2 , varies by only a factor of 2.3 over the range of minimum-COE points depicted. The FPC mass utilization lies in the 0.4- to 0.6-tonne/MWt range for the minimum-COE design point and rapidly increases for lower neutron first-wall loadings, although only moderate increases in COE occur (Fig. IV.C-4) with increased r_p . These FPC mass utilizations, although increasing, remain far below those predicted for superconducting fusion approaches (a value of 5.7 tonne/MWt is predicted for STARFIRE³, Table II.C-IB). The possibility for batch, single-piece FPC maintenance is compromised, however, for the higher-COE, lower- I_w designs.

The comparison of the economic confinement time, $\tau_E(\text{OPT})$, with RFP scaling is shown on Fig. IV.C-7, which also indicates the minimum-COE design point for the range of P_E considered. Following the algorithm described on Fig. IV.C-1, $\tau_E(\text{OPT})$ is the energy confinement time required to achieve the global minimum or local minimum-COE values; no transport scaling restricts this optimization. Figure IV.C-7 demonstrates how the goal of minimum COE must be tempered with the realities of physics. The $\tau_E \propto I_\phi^2 r_p^2 f(\beta_\theta)$ RFP scaling remains to be documented fully, particularly for the current exponent and the beta function.

Fig. IV.C-4. Sensitivity of minimum-COE design points to changes in net electric power, P_E , for the $A = 5.35$ base case, showing UDC, COE, I_w , and Q_E as a function of r_p and P_E .

Fig. IV.C-5. Sensitivity of plasma (solid line) and coil (dashed line) currents as a function of r_p and P_E for the conditions depicted on Fig. IV.C-4. The solid curves give I_{ϕ} , whereas the dashed curves give $I_{\phi c}$.

Fig. IV.C-6. Sensitivity of plasma density and FPC mass utilization as a function of r_p and P_E for cost-optimized designs.

Nevertheless, the margins between physics and economics can be charted on Fig. IV.C-7, and a comfortable operating regime is indicated for $P_E > 750$ MWe and $\nu > 1$. For lower values of P_E , Fig. IV.C-7 indicates that the minimum-COE design is not attainable for the RFP scaling used (i.e., $\nu > 1$).

The $I_w/P_E/COE$ tradeoff depicted on Fig. IV.C-4 defines the margins between technology (i.e., high heat/particle-flux surfaces, high-power-density blankets, batch versus patch maintenance, off-site versus on-site monolithic FPC construction, etc.) and economics. The margins among $I_w/P_E/COE$ and physics (transport) is best seen by combining the features of the COE and I_w plots on Fig. IV.C-4 with the $\tau_E(OPT) = \tau_E(RFP)$ intersection on Fig. IV.C-8. Figure IV.C-8 graphically demonstrates this window for $\tau_E(RFP) \propto I_\phi^\nu r_p^{2f}(\beta_\theta)$ over a range of current exponents, that window opening or closing depending on whether the current exponent increases or decreases. The uniqueness of Fig. IV.C-8 rests with the comparison on a single plot of key technological

Fig. IV.C-7. Comparison of "economic" confinement time (solid line) $\tau_E(\text{OPT})$, with RFP scaling [Eq. (A-35) and Eq. (A-36), dashed curve] for the parametric sensitivity results depicted on Fig. IV.C-4.

Fig. IV.C-8. Dependence of COE on r_p for a range of P_E values. Also shown are lines of constant I_w . The condition where $\tau_E(\text{OPT}) = \tau_E(\text{RFP})$ is also shown for $\tau_E(\text{RFP}) \propto I_w^\nu r_p^2 f(\beta_\theta)$ scaling for a range of ν values.

(I_w), economic (COE, P_E), physics (ν , r_p), and institutional (P_E) variables for the RFP.

D. Conclusions

This study and the concept assessment that has emerged has dealt primarily with the definition of both the physics and technology margins that allow access to the design windows described on Fig. IV.C-8. On the basis of this model development, systems study, and conceptual design, it is generally concluded that the RFP approach can operate within broad physical, technical, and economic margins while promising a unique, realistic, and robust approach to competitive magnetic fusion energy. Many physics technology and economics issues remain to

be resolved, however, particularly with respect to the tradeoff between power density, development cost, COE, and safety and environment issues. The results of this framework study provides a basis and direction for a more comprehensive power plant study that could contribute to a better understanding of these important tradeoffs and issues for the RFP and related systems.

REFERENCES

1. C. A. Flanagan, D. Steiner, and G. E. Smith, "Fusion Engineering Device Design Description," Oak Ridge National Laboratory report ORNL/TM-7948 (December 1981).
2. "INTOR, International Tokamak Reactor, Phase I," IAEA report STI/PUB/619, Vienna, (1982).
3. C. C. Baker, M. A. Abdou, R. M. Arons, A. E. Bolon, C. D. Boley, J. N. Brooks, et al., "STARFIRE - A Commercial Tokamak Fusion Power Plant Study," Argonne National Laboratory report ANL/FPP-80-1 (September 1980).
4. B. Badger, K. Audenaerde, J. B. Beyer, D. Braun, J. D. Callen, G. A. Emmert, et al., "WITAMIR - I: A University of Wisconsin Tandem Mirror Reactor Design," University of Wisconsin report UWFDM-400 (September 1980).
5. B. G. Logan, "Mirror Advanced Reactor Study (MARS)," Nucl. Technol./Fusion 1, 563 (1983).
6. J. D. Gordon and B. G. Logan, "Magnetic Mirror Fusion Power Systems," Proc. 11th Energy Technol. Conf., Washington, D.C. (March 1984) (also TRW report TRW-FRE-009, (1984)).
7. B. Badger, F. Avenet, H. M. Attaya, K. Audenaerde, H. Avel, J. B. Beyer, et al., "TASKA: A Tandem Mirror Fusion Engineering Facility," University of Wisconsin report UWFDM-500 (March 1982).
8. T. K. Fowler and B. G. Logan, "Tandem Mirror Technology Demonstration Facility," Lawrence Livermore National Laboratory report UCID-19193 (September 1981).
9. C. C. Baker, G. A. Carlson, and R. A. Krakowski, "Trends and Developments in Magnetic Confinement Fusion Reactor Concepts," Nucl. Technol./Fusion, 1, 5-78 (January 1981).
10. Report on the Third IAEA Technical Committee Meeting and Workshop on Fusion Reactor Design-III, Tokyo, Japan, October 5-16, 1981, Nucl. Fusion 22, 671-719 (1982).
11. W. M. Stacey, Jr., C. C. Baker, R. W. Conn, R. A. Krakowski, D. Steiner, and K. I. Thomassen, "Future Technology Requirements for Magnetic Fusion - An Evaluation Based on Conceptual Design Studies," Nucl. Technol./Fusion 5, 266 (1984).
12. R. A. Krakowski and R. L. Hagenson, "Compact Fusion Reactors," Proc. 5th ANS Topical Meeting on the Technology of Fusion Energy, Knoxville, TN (April 26-28, 1983), Nucl. Technol./Fusion 4, 1265 (September 1983).
13. M. Mitchell Waldrop, "Compact Fusion: Small is Beautiful," Science 219, 154 (1983).

14. R. L. Hagenson, R. A. Krakowski, and H. Dreicer, "High-Power-Density Approaches to Magnetic Fusion Energy: Problems and Promise of Compact Reversed-Field Pinch Reactors (CRFPR)," Stockholm Symp. on New Trends in Unconventional Approaches to Magnetic Fusion (June 16-18, 1982) J. Nucl. Instr. and Methods 207, 241 (1983).
15. R. L. Hagenson and R. A. Krakowski, "Compact Reversed-Field Pinch Reactors (CRFPR): Sensitivity Study and Design-Point Determination," Los Alamos National Laboratory report LA-9389-MS (July 1982).
16. R. L. Hagenson and R. A. Krakowski, "Engineering Design of a Compact RFP Reactor (CRFPR)," Proc. 5th ANS Topical Meeting on the Technology of Fusion Energy, Knoxville, TN (April 26-28, 1983); Nucl. Technol./Fusion 4, 1284 (September 1983).
17. R. L. Hagenson, C. G. Bathke, M. E. Battat, D. J. Blevins, G. E. Cort, M. J. Embrechts, et al., "Design of A Compact Reversed-Field Pinch Reactor (CRFPR)," Proc. 10th IEEE Symposium on Fusion Engineering, Philadelphia, PA (December 5-9, 1983) IEEE Cat. No. 83CH1916-6 NPS I, 853 (1983).
18. R. F. Bourque, "OHE Reactor Concepts," Proc. 9th Symp. on Eng. Prob. of Fusion Research II, 1851, Chicago, IL, (October 26-29, 1981).
19. R. A. Jacobsen, C. E. Wagner, R. E. Covert, "Systems Studies of High-Field Tokamak Ignition Experiments," J. Nucl. Fus. 3, (4), 217 (1983).
20. S. N. Rosenwasser, R. D. Stevenson, G. Listvinsky, D. L. Vrable, J. E. McGregor, and N. Nir, "Materials and Design Aspects of the RiggatronTM Tokamak," Proc. 3rd Topical Meeting on Fusion Reactor Materials, Albuquerque, NM (September 19-22, 1983) to be published in J. Nucl. Mater. (also, International Fusion Energy Systems Company, Inc. report II-100-83 (September 1983)).
21. W. Kopendorfer, "The ZEPHYR Experiment," Fus. Technol., 1980, p. 77, Pergamon Press, NY (1981).
22. D. R. Cohn, L. Bromberg, J. E. C. Williams, H. Becker, R. LeClaire, and T. Yang, "Near-Term Tokamak Reactor Designs with High-Performance Resistive Coils," Proc. Third Tech. Comm. Meeting and Workshop on Fusion Reactor Design and Technol., Tokyo, Japan (October 15-16, 1981), IAEA-TC-392/11 I, 173 (1983).
23. H. J. Willenberg, "Definition and Conceptual Design of a Small Fusion Reactor," Mathematical Sciences Northwest report MSNW-1159 (February 1981).
24. A. E. Robson, "A Conceptual Design for an Imploding-Liner Fusion Reactor," Megagauss Physics and Technol., p. 425, Plenum Publishing Corp., NY (1980).
25. R. L. Miller and R. A. Krakowski, "Reassessment of the Slowly-Imploding Liner (LINUS) Fusion Reactor Concept," Proc. 4th Top. Mtg. Technol. of Controlled Nuclear Fusion, CONF-801011 II, 825, King of Prussia, PA (October 14-16, 1980).

26. R. E. Olson, J. G. Gilligan, E. Greenspan, and G. H. Miley, "The Spheromak Approach to High Power Density Reactors," Proc. 9th Symp. on Eng. Prob. Fusion Research II, 1898, Chicago, IL (October 26-29, 1981).
27. R. L. Hagenson and R. A. Krakowski, "A Compact-Torus Fusion Reactor Based upon the Field-Reversed Theta Pinch," Proc. 4th Top. Mtg. Technol. of Controlled Nuclear Fusion, CONF-801011 III, 1120, King of Prussia, PA (October 14-16, 1980).
28. R. L. Hagenson and R. A. Krakowski, "A Compact-Toroid Fusion Reactor Based on the Field-Reversed Theta Pinch," Los Alamos National Laboratory report LA-8758-MS (March 1981).
29. A. C. Smith, C. P. Ashworth, D. G. Abreu, D. M. Woodall, G. A. Carlson, W. S. Neef, et al., "The Prototype Moving-Ring Reactor," Proc. 9th Symp. on Eng. Prob. of Fusion Research II, 1867, Chicago, IL (October 26-29, 1981).
30. J. G. Gilligan, G. H. Miley and D. Driemeyer, "Conceptual Design of a Compact Field Reversed Mirror Reactor - SAFFIRE," Proc. 4th Top. Mtg. Technol. of Controlled Nuclear Fusion, CONF-801011 II, 840, King of Prussia, PA (October 14-17, 1980).
31. R. Hancox, R. A. Krakowski, and W. R. Spears, "The Reversed-Field Pinch Reactor (RFPR) Concept," Nucl. Eng. and Design 63, 2, 251 (1981).
32. R. L. Miller, "General Reactor Considerations for Stellarators," Los Alamos National Laboratory document LA-UR-82-2667, presented to 4th International Stellarator Workshop, Cape May, NJ (September 13-15, 1982).
33. H. A. B. Bodin and A. A. Newton, "Review Paper: Reversed-Field Pinch Research," Nucl. Fus. 20, 1255 (1980).
34. D. A. Baker and W. E. Quinn, "The Reversed-Field Pinch," Edward Teller, ed., Fusion I, Part A, 438 (Academic Press, NY) (1981).
35. "Mirror-Based and Field-Reversed Approaches to Magnetic Fusion," Course and Workshop, International School of Plasma Physics, Varenna, Italy (September 7-17, 1983).
36. Tokamak Fusion Reactor Final Design Report," Princeton Plasma Physics Laboratory report PPPL 1475 (August 1978).
37. R. A. Krakowski, J.E. Glancy, and A. E. Dabiri, "The Technology of Compact Fusion Reactor Concepts," presented at the Workshop in Compact Fusion Reactors, Washington, DC (September 31 - October 1, 1982) Nucl. Technol./Fusion 4, 342 (1983).
38. "MIT Tokamak Alcator C Exceeds Lawson Criterion," Physics Today 20 (February 1984).

39. M. Nagami and the JAERI Team, D. Overskei and the GA Team, "High- β Injection Experiments with Shaped Plasmas in Doublet-III," Proc. 9th Intern. Conf. on Plasma Physics and Controlled Nuclear Fusion Research, Baltimore, USA, paper IAEA-CN-41/A-2, I, 27 (September 1982).
40. D. Q. Hwang, M. Bitter, R. Bundy, A. Cavallo, R. Chrien, S. Cohen, et al., "High-Power ICRF and ICRF Plus Neutral-Beam Heating on PLT," ibid, IAEA-CN-41/11, II, 3.
41. P. C. Efthimion, M. Bell, W. R. Blanchard, N. Bretz, J. L. Cecchi, J. Coonrad, et al., "Initial Confinement Studies of Ohmically Heated Plasmas in the Tokamak Fusion Test Reactor," Phys. Rev. Lett. 52, 1492 (1984).
42. K. Uo, A. Iiyoshi, T. Obiki, O. Motojima, and S. Morimoto, A. Sasaki, et al., "Heliotron Studies," Proc 9th Intern. Conf. on Plasma Physics and Controlled Nuclear Research, Baltimore, USA. IAEA-CN-41/L-3, II, 209 (September 1982).
43. G. Cattanei, D. Dorst, A. Elsner, G. Grieger, H. Hacker, J. Hartfuss, et al., "Neutral-Injection Heating In the Wendelstein VII-A Stellarator," ibid, IAEA-CN-41/L-5, II, 241.
44. D. A. Baker, M. D. Bausman, C. J. Buchenauer, L. C. Burkhardt, G. Chandler, J. N. DiMarco, et al., "Performance of the ZT-40M Reversed-Field Pinch with an Inconel Liner," ibid, IAEA-CN-41/H-2-1, I, 587 (1982).
45. V. Antoni, M. Bogatin, A. Buffa, C. Bunting, S. Costa, L. Giudicotti, et al., "Studies on High Density RFP Plasmas in the Eta-Beta II Experiment," ibid, IAEA-CN-41/H-4, I, 619 (1982).
46. K. Ogawa, Y. Maejima, T. Shimada, Y. Hirano, P.G. Carolan, C. W. Gowers, et al., "Experimental and Computational Studies of Reversed Field Pinch on TPE-IR(M)," ibid, IAEA-CN-41/H-1, I, 575 (1982).
47. M. Fujiwara, T. Kamimura, M. Hosokawa, T. Shoji, H. Iguchi, et al., "Experimental and Numerical Studies on Plasma Confinement in Nagoya Bumpy Torus(NBT)," ibid, IAEA-CN-41/L-2, II, 197.
48. D. J. Rej and M. G. Tuszewski, "A Zero-Dimensional Model for Field-Reversed Configurations," Proc. 5th Symp. on Physics and Tech. of Compact Toroids in the Magnetic Fusion Program, Bellevue, WA (November 16-18, 1982).
49. C. W. Barnes, T. R. Jarboe, I. Henins, A. R. Sherwood, S. O. Knox, R. Gribble, et al., "Spheromak Formation and Operation With Background Filling Gas and A Solid Flux Conserver in CTX," Nucl. Fus. 24, 267 (1984).
50. T. C. Simonen, D. E. Baldwin, S. L. Allen, W. L. Barr, T. A. Casper, Y. J. Chen, et al., "TMX Tandem Mirror Experiments and Thermal Barrier Theoretical Studies," Proc 9th Intern. Conf. on Plasma Physics and Controlled Nuclear Fusion Research, Baltimore, USA. IAEA-CN-41/G-1, I, 519 (September 1982).

51. R. L. Miller, C. G. Bathke, R. A. Krakowski, F. M. Heck, L. Green, J. S. Karbowski, et al., "The Modular Stellarator Reactor; A Fusion Power Plant," Los Alamos National Laboratory report LA-9737-MS (July 1983).
52. C. G. Bathke, D. J. Dudziak, R. A. Krakowski, W. B. Ard, P. A. Bowers, J. W. Davis, et al., "ELMO Bumpy Torus Reactor and Power Plant Conceptual Design Study," Los Alamos National Laboratory report LA 8882-MS (August 1981).
53. R. L. Hagenson, R. A. Krakowski, and G. E. Cort, "The Reversed-Field Pinch Reactor (RFPR) Concept," Los Alamos Scientific Laboratory report LA-7973-MS (August 1979).
54. United Engineers and Constructors, Inc., "1000-MWe Central Station Power Plants Investment Cost Study," U.S. AEC report WASH-1230 (June 1972).
55. J. Hall, The Story of the Construction of Berkeley Nuclear Power Station, Leonard Hill Books, London (1963).
56. A. E. Waltar and A. B. Reynolds, Fast Breeder Reactors, Pergamon Press, NY (1982).
57. G. C. Dale (ed.) and J. M. Bowerman, "The Safety of the AGR," UK Central Electricity Generating Board and South of Scotland Electricity Board (1982).
58. UK Central Electricity Generating Board, "A Technical Outline of Sizewell 'B': The British Pressurized Water Reactor " (1983).
59. E. W. Merrow, S. W. Chapel, and C. Worthing, "A Review of Cost Estimation in New Technologies: Implications for Energy Process Plants," Rand Corporation report R-2481-DOE (July 1979).
60. L. S. Caldwell, "Utility Financing - Risk and Return," Nuclear News 27, 46 (April 1984).
61. J. Payne, "Looking for a Way Back Home," Nuclear News 26, 31 (May 1984).
62. "Nuclear Plant Involvement Affects Rates, Ratings," Nuclear News 27, 39 (May 1984).
63. C. F. McDonald and D. L. Sonn, "A New Small HTGR Power Plant Concept with Inherently Safe Features - An Engineering and Economic Challenge," Proc. American Power Conference, Chicago, IL, 45, 818 (1983).
64. "Small Reactors: Is the Nuclear Industry on the Verge of a Large Step Backward?," The Energy Daily (December 22, 1983).
65. C. E. Behrens, "Economic Potential of Smaller-Sized Nuclear Plants in Today's Economy," The Library of Congress Congressional Research Service report 83-621 ENR (January 1984).
66. R. A. George and C. K. Paulson, "A Nuclear Plant Design for the 1990s - Meeting Tomorrow's Needs," Proc. American Power Conference, Chicago, IL, 45, 799 (1983).

67. R. Carruthers, "Criteria for the Assessment of Reactor Potential," Unconventional Approaches to Fusion, B. Brunelli and G. G. Leatton (eds.), p.39-45, Plenum Press, NY (1982).
68. S. C. Schulte, W. E. Bickford, C. E. Willingham, S. K. Ghose, M. G. Walker, "Fusion Reactor Design Studies--Standard Unit Costs and Cost Scaling Rules," Pacific Northwest Laboratory report PNL-2987 (September 1979).
69. A. A. Hollis, "An Analysis of the Estimated Capital Cost of a Fusion Reactor," UKAEA Harwell report AERE-R9933 (June 1981).
70. J. B. Taylor, "Relaxation of Toroidal Discharges," 3rd Topical Conf. on Pulsed High-Beta Plasma, Culham, UK, p. 59 (1975).
71. D. A. Baker, C. J. Buchenauer, L. C. Burkhardt, J. N. DiMarco, J. N. Downing, and A. Haberstich, "Initial Reversed-Field Pinch Experiments on ZT-40M with a Metallic Vacuum Liner," 10th European Conf. on Controlled Fus. and Plasma Physics, Moscow, USSR (September 14-19, 1981) also Los Alamos National Laboratory document LA-UR-81-1413.
72. P. G. Carolan, L. Firth, C. W. Gowers, G. C. H. Heywood, I. H. Hutchinson, A. A. Newton, V. A. Piotrowicz, M. R. C. Watts, P. D. Wilcox, and H. A. B. Bodin, "Initial Results from the HBTXIA Reversed Field Pinch Experiment," 10th European Conf. on Cont. Fus. and Plasma Physics, Moscow, USSR (September 14-19, 1981).
73. A. A. Newton, Li Yin-An, J.W. Long, and B. C. Yeung, "Numerical Investigation of Reversed Field Pinches," 3rd Topical Conf. on Pulsed High-Beta Plasmas, Culham, UK, p. 323 (1975).
74. K. F. Schoenberg, R. F. Gribble, and J. A. Phillips, "Zero-Dimensional Simulations of Reversed-Field Pinch Experiments," Nucl. Fusion 22, 1433 (1982).
75. R. Gerwin and R. Keinigs, "Dynamo Theory: Can Amplification of Magnetic Field Profiles Arise from a Cross-Field Alpha Effect," Los Alamos National Laboratory report LA-9290-MS (April 1982).
76. M. J. Schaffer, "A Plasma Model with Dynamo for Sustained Reversed Field Pinches," GA Technologies report GA-A16759 (May 1982).
77. K. F. Schoenberg, R. W. Moses, Jr., and R. L. Hagenson, "Plasma Resistivity in the Progress of a Reversed-Field Dynamo," submitted to Physics of Fluid (1983), also Los Alamos National Laboratory document LA-UR-83-1739.
78. K. F. Schoenberg and R. F. Gribble, "Oscillating Field Current Drive for Reversed-Field Pinch Discharges," Proc. IEEE Mtg. on Plas. Sci., Ottawa (May 17-19, 1982).
79. K. F. Schoenberg, C. J. Buchenauer, R. J. Massey, J. G. Melton, R. W. Moses, R. A. Nebel, and J. A. Phillips, "F- θ Pumping and Field Modulation Experiments on a Reversed Field Pinch Discharge," Phys. Fluids 27, 548 (1984).

80. M. K. Bevir and J. W. Gray, "Relaxation, Flux Consumption and Quasi Steady State Pinches," Proc. RFP Theory Workshop, Los Alamos National Laboratory April 28 - May 2, 1980, Los Alamos National Laboratory report LA-8944-C, p. 176 (January 1982).
81. M. K. Bevir, C. G. Gimblett, and G. Miller, "Quasi-Steady-State Current Drive by Plasma Relaxations," Proc. IAEA Technical Meeting on Non-Inductive Current Drive in Tokamaks, Culham Laboratory (April 1983).
82. R. D. O'Dell, F. W. Brinkley, Jr., and D. R. Marr, "Users Manual for ONEDANT: A Code Package for One-Dimensional, Diffusion-Accelerated, Neutral-Particle Transport," Los Alamos National Laboratory report LA-9184-MS (February 1982).
83. D. Garber (ed.), "ENDF/B-IV Summary Documentation," Brookhaven National Laboratory report BNL-17541 (ENDF-201) (October 1975).
84. M. E. Battat, R. J. LaBauve, and D. W. Muir, "The GAMMON Activation Library," Los Alamos Scientific Laboratory report LA-8040-MS (September 1979).
85. D. K. Sze, R. Clemmer, and E. T. Cheng, "LiPb, A Novel Material for Fusion Applications," Proc. of the 4th Top. Mtg. on the Tech. of Controlled Nucl. Fus., III, 1786, King of Prussia, PA (October 14-17, 1980).
86. R. F. Bourque, "Flowing $Pb_{83}Li_{17}$ Liquid-Metal Coolant in Fusion Reactors with High-Power-Densities and Magnetic Fields," Nucl. Technol./Fusion 3, 493 (1983), also GA Technologies report GA-A16662 (June 1982).
87. M. Abdou (project manager), "Blanket Comparison and Selection Study: Interim Report," Argonne National Laboratory report ANL/FPP/TM-177 (September 1983).
88. R. W. Conn, "Tokamak Reactors and Structural Materials," J. Nucl. Mater. 85 and 86, 9 (1979).
89. D. L. Smith, "Blanket Materials for DT Fusion Reactors," ibid., p. 19.
90. R. E. Nygren, "Material Issues in the Fusion Engineering Device," ibid., p. 31.
91. M. A. Abdou, R. F. Mattas, D. L. Smith, and G. L. Kulcinski, "Important Material Considerations in INTOR," ibid., p. 41.
92. R. R. Hasiguti, "Japanese Program of Materials Research for Fusion Research," ibid., p. 51.
93. J. Nihoul, "The European Programme of Fusion Materials," ibid., p. 57.
94. R. A. Krakowski, "Materials Needs for Compact Fusion Reactors," 3rd Top. Mtg. on Fusion Reactor Materials, Albuquerque, NM (September 19-22, 1983) to be published in J. Nucl. Mater.

95. L. J. Perkins, "Material Considerations for Highly Irradiated Normal-Conducting Magnets in Fusion Reactor Applications," ibid.
96. I. N. Sviatoslavsky and W. C. Young, "Structural Design Features for Commercial Fusion Power Reactor Magnet Systems," Nucl. Eng. and Design 58, 207 (1980).
97. M. A. Hoffman, "Heat Flux Capabilities of First-Wall Tube Arrays for an Experimental Fusion Reactor," Nucl. Eng. and Design 64, 283-299 (1981).
98. G. P. Yu, "Relationship of Material Properties to the Design of a Fusion Reactor First Wall," ScD. Thesis, Dept. of Nucl Eng., MIT (May 1981).
99. C. K. Youngdal and D. L. Smith, "Stress and Lifetime Limitations of First-wall Structural Materials," J. Nucl. Mater. 85 and 86, 153 (1979).
100. P. W. Taubenblatt, W. R. Opic, and Y. T. Hsu, "A New Copper Alloy with High Strength and Conductivity," Metals Engineering Quarterly (November 1972).
101. G. E. Cort, A. L. Graham, and K. E. Christensen, "A High-Flux First-Wall Design for a Small Reversed-Field Pinch Reactor," AIAA/ASME Conf. on Fluid, Plasma, Thermophysics, and Heat Transfer, St. Louis, MO (June 8-11, 1982).
102. O. K. Harling, G. P. Yu, N. J. Grant, and J. E. Meyer, "Application of High-Strength Copper Alloys for a Fusion Reactor First Wall," Proc. 2nd - Top. Mtg. on Fus. Reactor Materials, Seattle, WA (August 9-12, 1981).
103. F. W. Wiffen, T. C. Reuther, and R. E. Gold, "Copper and Copper Alloys for Fusion Reactor Applications: Summary Report of a DOE/OFE Workshop," Proc. 3rd Topical Mtg. on Fusion Reactor Materials, Albuquerque, NM (September 19-22, 1983).
104. M. A. Hoffman and R. W. Werner, "Heat Flux Limitations on First-Wall Shields for Early Fusion Machines," Proc. 1st Topical Meeting on the Technology of Controlled Nuclear Fusion, CONF-740402-P1, 619-633 (April 16-18, 1974) (also Lawrence Livermore National Laboratory report UCRL-75622 (April 1974)).
105. L. J. Perkins and G. L. Kulcinski, "Material Considerations for Highly Irradiated Normal-Conducting Magnets in the MARS Tandem Mirror Reactor," Proc. 3rd Top. Mtg. on Fus. Reactor Materials, Albuquerque, NM (September 19-22, 1983).
106. L. J. Perkins and G. L. Kulcinski, "Economic Design Optimization of the LiPb Blanket for the Mirror Advanced Reactor (MARS)," Proc. 5th ANS Topical Meeting on the Technology of Fusion Energy, Knoxville, TN (April 26-28, 1983), Nucl. Technol./Fusion 4, 1107 (1983).
107. A. Harvey, "Radiation-Hardened Magnets Using Mineral Insulated Conductors," Los Alamos Scientific Laboratory report LA-5306-MS (June 1973).

108. R. J. Grieggs, D. J. Liska, and A. Harvey, "Radiation-Hardened Field Coils for FMIT Quadrupoles," 1983 Particle Accelerator Conf., Santa Fe, NM (March 21-23, 1983).
109. L. El-Guebaly, L. J. Perkins, and C. Maynard, "MARS Axicell Damage and Shielding Analysis," Proc. 5th ANS Top. Mtg. on the Tech. of Fus. Energy, Knoxville, TN (April 26-28, 1983), Nucl. Technol./Fusion 4, 1171 (September 1983).
110. G. F. Hurley, J. C. Kennedy, F. W. Clinard, Jr., R. A. Vangman, and W. R. McDonnell, "Structural Properties of MgO and MgAl₂O₄ after Fusion Neutron Irradiation Near Room Temperature," 2nd Top. Mtg. on Fus. Reactor Materials, Seattle, WA (August 9-12, 1981).
111. L. J. Perkins, "Dose-Rate Conductivity Enhancement in Ceramic Insulators: A New Shielding Problem?," Trans. Amer. Nucl. Soc. 44, 131 (1983).
112. J. A. Horak and T. H. Blewitt, "Fast Neutron Irradiation Induced Resistivity in Metals," Phys. Stat. Sol (A) 9, 721 (1972).
113. W. A. Harrison, "Resistivity Due to Dislocations in Copper," J. Phys. Chem. Solids 5, 44 (1958).
114. R. M. Brick, A. W. Pense, and R. B. Gordon, Structure and Properties of Engineering Materials, McGraw-Hill, NY, p. 66 (1977).
115. N. F. Mott and H. Jones, The Theory of the Properties of Metals and Alloys, 269-287, Dover, NY (1936).
116. T. H. Blewitt and T. J. Koppenal, Radiation Effects, W. F. Sheeley, ed., Gordon and Breach, NY p. 585 (1967).
117. L. D. Glowinski, J. M. Lanore, C. Foche, and Y. Adda, "Etude de la Formation des Cavites D'irradiation Dans e Cuivre IV-Etude des Mecanismes," J. Nucl. Mater. 61, 41-52 (1976).
118. W. J. Duffin and F. A. Nichols, "The Effect of Irradiation on Diffusion-Controlled Creep Processes," J. Nucl. Mater. 45, 302-316 (1972/73).
119. W. H. Rohsenow, "Boiling," Handbook of Heat Transfer, W. H. Rohsenow and J. P. Hartnett, eds. (McGraw-Hill, NY, 1973), Sec. 13, 13.34-13.63.
120. W. C. Reynolds, "Effect of Wall Heat Conduction on Convection in a Circular Tube with Arbitrary Circumferential Heat Input," Intern. Jour. of Heat and Mass Trans. 6, 925 (1963).
121. J. A. Fillo and J. R. Powell, "Coupled Conduction-Turbulent Convection in a Circular Tube," Procedures of the 6th Inter. Heat Transfer Conf. 2, 181, Toronto (1978).
122. A. L. Chan, J. W. Baughn, and M. A. Hoffman, "Nonuniform Circumferential Heat Flux Experiments in a Circular Tube," ASME Winter Annual Meeting, 75-WA/MT-52, Houston, TX (November 1975).

123. W. R. Gambill and N. D. Greene, "Boiling Burnout with Water in Vortex Flow," Chem. Eng. Progress 54, 68-76 (1958).
124. R. G. Lawton, "The AYER Heat Conduction Computer Program," Los Alamos Scientific Laboratory report LA-5613-MS (May 1974).
125. D. L. Smith, M. Abdou, P. Adler, C. Baker, D. Berwald, J. Bethin, et al., "Fusion Reactor Blanket Shield Design Study," Argonne National Laboratory report ANL/FPP-83-1 (October 1983).
126. M. Abdou, C. Baker, J. Brooks, D. DeFreece, D. Ehst, R. Mattas, et al., "A Demonstration Tokamak Power Plant Study, (DEMO)," Argonne National Laboratory report ANL/FPP/82-1 (September 1982).
127. U.S. Department of Energy, "Materials Handbook for Fusion Energy Systems." U.S. DOE report DOE/TIC - 10122 (1980).
128. R. L. Spencer, "Magnetic Islands and Stochastic Field Lines in the RFP," Proc. RFP Theory Workshop, Los Alamos, NM (April 29-May 2, 1980), Los Alamos National Laboratory report LA-8944-C, p. 129 (January 1982).
129. P. Thullen (ed.), "ZT-40U: Conceptual Design of a 2-MA Reversed-Field Pinch Experiment," Los Alamos National Laboratory document LA-UR-83-1375 (1983).
130. R. W. Moses, Jr. and J. K. Ballou, "Inductive Shielding for Pulsed Energy Storage Magnets," IEEE Trans. on Magnetics, MAG-11, 493-496 (March 1975).
131. V. D. Shafranov, Reviews of Plasma Physics, 2 (Consultants Bureau, p.103, NY) (1966).
132. J. M. Greene, J. L. Johnson, and K. E. Weimer, "Tokamak Equilibrium," Phys. Fluids 14, 671 (1971).
133. V. S. Mukhovatov and V. D. Shafranov, "Plasma Equilibrium in a Tokamak," Nucl. Fusion 11, 605 (1971).
134. M. Petravic, D. Heifetz, D. Post, W. Langer, and C. Singer, "A Model for the Performance of Poloidal Divertors," 9th Inter. Conf. on Plasma Physics and Controlled Nucl. Fus. Research, Baltimore, MD, IAEA-CN-41/D-3-2, 1, 323 (September 1-8, 1982).
135. A. K. Prinja, R. W. Conn, S. Talmadeg, D. Heifetz, and D. Post, "Physics of Particle Exhaust in Pumped Limiters," J. Nucl. Mater. 111-112, 279 (1982).
136. M. Ulrickson, "Optimum Shapes for Pumped Limiters," Princeton Plasma Physics Laboratory report PPPL-1901 (May 1982).
137. H. C. Howe, "Physics Considerations for the FED Limiter," Oak Ridge National Laboratory report ORNL/TM-703 (1982).
138. K. Audenaerde, G. A. Emmert, and M. Gordinier, "SPUDNUT: A Transport Code for Neutral Atoms in Plasma," J. Comp. Phys. 34, 268 (1980).

139. Symp. on Energy Removal and Particle Control in Toroidal Fusion Devices, Princeton, NJ (July 26-29, 1983).
140. W. Pfeiffer and R. E. Waltz, "Empirical Scaling Laws for Energy Confinement in Ohmically-Heated Tokamaks," Nucl. Fusion 19, 51 (1979).
141. K. B. Axon, J. E. Bradley, J. Burt, W. H. M. Clark, M. Dunstan, et al., "Results from DITE Experiment," Plasma Phys. and Controlled Nucl. Fusion Res. III, 201, Baltimore (September 1-8, 1982).
142. P. J. Harbour and J. G. Morgan, "Models and Codes for the Plasma Edge Region," Culham Laboratory report CLM-R234 (December 1982).
143. D. G. Worden, "Flow of Gases Through Tubes and Orifices," in S. Dushman and J. M. Lafferty, eds., Scientific Foundations of Vacuum Technique, (John Wiley & Sons, Inc., NY) (1962).
144. G. L. Weissler and R. W. Carlson, Vacuum Physics and Technology (Academic Press, NY) (1979).
145. R. Loevinger, "Fundamental Considerations in Vacuum Practice," in A. Guthrie and R. K. Wakerling, eds., Vacuum Equipment and Techniques (McGraw-Hill Book Company, Inc.) (1949).
146. S. L. Milora, "Review of Pellet Fueling," J. Fusion Energy 1, 15 (1981).
147. S. L. Gralnick, "Solid Deuterium Evaporation in a Fusion Plasma," Nucl. Fus. 13, 703-713 (1973).
148. P. B. Parks and R. J. Turnbull, "Effect of Transonic Flow in the Ablation Cloud on the Lifetime of a Solid Hydrogen Pellet in a Plasma," Phys. Fluids 21, 1735-1741 (1978).
149. R. P. Gilliard and K. Kim, "Significance of Magnetic Shielding in the Ablation of a Solid Hydrogen Pellet in a Plasma," IEEE Transaction on Plasma Science PS-8, 477-484 (December 1980).
150. W. A. Houlberg, M. A. Iskra, H. C. Howe, and S. E. Attenberger, "Pellet-A Computer Routine for Modeling Pellet Fueling in Tokamak Plasma," Oak Ridge National Laboratory report ORNL/TM-6549 (January 1979).
151. J. B. Taylor, "Relaxation of Toroidal Plasma and Generation of Reversed Magnetic Field," Phy. Letts. 33, 1139 (1974).
152. J. B. Taylor, "Relaxation of Toroidal Discharges to Stable States and Generation of Reversed Magnetic Field," Proc. 5th Inter. Conf. on Plasma Physics and Cont. Nucl. Fusion Research 1, 161, Tokyo, Japan (November 11-15, 1974).
153. F. M. Mann, "Reduced Activation Calculations for the Starfire First Wall," Hanford Engineering Development Laboratory report HEDL-TME-83-27 (October, 1983).

154. A. M. Weinberg, I. Speiwak, "Inherently Safe Reactors and a Second Nuclear Era" Science 224, 1394 (June 1984).

ACRONYMS AND ABBREVIATIONS

AFC	Alternative Fusion Concept
AGR	Advanced Gas-Cooled Reactor
B	Blanket
B/S	Blanket/Shield
BOP	Balance of Plant
BWR	Boiling-Water Reactor
C	Coil
COE	Cost of Electricity (mills/kWeh)
CRFPR	Compact Reversed-Field Pinch Reactor
DBTT	Ductile to Brittle Transition Temperature
DFC	Divertor Flanking Coil
DT	Deuterium-Tritium
D&T	Development and Technology
EBT	Elmo Bumpy Torus
EFC	Equilibrium-Field Coil
EI	Escalation/Interest
ETR	Experimental Test Reactor
FED	Fusion Engineering Device
FPC	Fusion Power Core (FW/B/S/C)
FPY	Full-Power Year
FW	First Wall
HHF	High Heat Flux
HMG	Homopolar Motor/Generator
HPD	High Power Density
IHX	Intermediate Heat Exchanger
INTOR	International Toroidal Reactor
IVC	In-Vacuum Component
LMFBR	Liquid-Metal Fast-Breeder Reactor
LWR	Light-Water Reactor
MARS	Mirror Advanced Reactor Study
M/G	Motor/Generator
MSR	Modular Stellarator Reactor
MTTF	Mean-Time-To-Failure
MTTR	Mean-Time-To-Repair

NA	Not Applicable
NBT	Nagoya Bumpy Torus
O&M	Operation and Maintenance
OHC	Ohmic-Heating Coil
OHTE	Ohmically Heated Toroidal Experiment
PFC	Poloidal-Field Coil
PWI	Plasma-Wall Interaction
PWR	Pressurized-Water Reactor
RFP	Reversed-Field Pinch
ROI	Return on Investment
RPE	Reactor Plant Equipment
SG	Steam Generator
SOL	Scrapeoff Layer
SOTA	State of the Art
SP	Superphenix
TBD	To Be Determined
TDC	Total Direct Cost
TFC	Toroidal-Field Coil
TFTR	Tokamak Fusion Test Reactor
TMR	Tandem-Mirror Reactor
UDC	Unit Direct Cost (\$/kWe)
UTC	Unit Total Cost (\$/kWe)

ACKNOWLEDGEMENTS

The authors wish to acknowledge the useful discussions with J. N. DiMarco, J. N. Downing, R. W. Moses, Jr., K. F. Schoenberg, and R. L. Spencer of Los Alamos on a wide range of physics and technical topics dealing with the extension of present RFP physics understanding to describe reactor-like conditions. The consultation and advice on materials issues by F. W. Clinard, Jr. is greatly appreciated. C. R. Mynard contributed significantly to the illustrative mechanical layout of the fusion power core; D. J. Blevins and G. E. Cort are similarly acknowledged. C. Copenhaver contributed to the limiter heat-transport assessment. During the course of this study one of the authors (RAK) made an extended visit to the Culham Laboratory and expresses his appreciation for the insights developed during that stay, particularly through conversations with R. Hancox, P. I. H. Cook, W. R. Spears, G. J. Butterworth, and D. E. T. F. Ashby. Lastly, the unflaggingly accurate and rapid typing and editing skills of Marion Clark and Olivia Moss throughout the evolution of this report are especially acknowledged.

Appendix A. CRFPR Burn Model and Reactor Design Code

The time-dependent simulation of the CRFPR couples the external electrical driving circuit to a profile-averaged zero-dimensional plasma model. A complete analysis of the poloidal-field circuit is performed, as described in Sec. III.F.2.; this analysis includes the plasma as a nonlinear circuit element. Experimentally derived plasma profiles and transport properties are used to generate self-consistent plasma equilibrium configurations that are adjusted as the DT/DD-fueled burn proceeds. The concentration and energies of species from the constituent reactions (H, ^3He , ^4He , T) are followed in time with a Fokker-Planck slowing-down formulation. Power output from the plasma impinges on a two-region first-wall surface, and one-dimensional temperature and stress distributions within the first wall are calculated as a function of time. An overall power-plant energy balance is evaluated as the reactor achieves a steady state, with an option to perform a self-consistent analysis of F- θ current drive.

The RFP systems code is based on a multiparticle, time-dependent burn computation that accounts for effects related to magnetic-field and plasma profiles by performing integral averages over the plasma cross section at selected time intervals. Magnetic field, $\vec{B}(r)$, and current density profiles, $\vec{j}(r)$, are calculated using the Maxwell equations, these profiles being computed self-consistently with input plasma density, temperature, and $\mu(r)$ profiles, where $\vec{j}_{\parallel}(r) = [\mu(r)/\mu_0]\vec{B}(r)$, $\mu_0 = 4\pi(10)^{-7}$ H/m, and $\mu(r)$ is defined by this expression for $j_{\parallel}(r)$. With these one-dimensional equilibrium relationships, profile form factors are derived numerically and used to simulate a one-dimensional calculation while maintaining the time efficiency of a zero-dimensional "point-model" code. This kind of calculation can not predict profile evolution, which instead must be provided as a function of time. This limitation, however, does not seriously compromise the burn predictions when the level of available experimental information in this area is considered. One-dimensional computer codes require spatially resolved transport coefficients, which even for the well-studied tokamak are generally unavailable. Present experiments typically provide only approximate profile information and bulk-plasma transport losses. This level of knowledge is ideally suited as input to the profile-averaging computer code described in this section; the use of multidimensional transport codes tend to create an unwarranted level of

confidence in computed results in that the predictive capabilities remain based on comparison with integral experimental results.

The CRFPR burn model provides the following specific information:

- Time history of currents, voltages, powers, and energies in the poloidal-field-coil (PFC) and toroidal-field-coil (TFC) circuits, with the PFC circuit driving the burn computation. Applying appropriate circuit switching sequences and voltages while incorporating the plasma as a nonlinear circuit element allows an accurate simulation of reactor operation.
- Self-consistent, one-dimensional (cylindrical) plasma equilibria using experimentally derived plasma density, $n(r)$, temperature, $T(r)$ and current-density [i.e., $\mu(r)$] profiles. Profile updating is performed whenever the plasma beta or boundary conditions have significantly changed over a given period of time.
- Complete time history of plasma properties is generated, including parameters that are constrained to satisfy stability requirements (particularly β_0 , θ , and F). This calculation includes profile averaging of all plasma quantities versus time for a DT- or DD-fueled burn.
- Temperature and density fractions of all energetic ionic species are determined. These non-Maxwellian suprathermal plasma species (H, D, T, ^3He , and ^4He) are described by a Fokker-Planck formalism with the Maxwellian component being subtracted from each slowing-down distribution and merged into a single background ion population.
- Complete reactor energy balance and a listing of all system energy requirements that culminate in a final expression for the engineering Q-value, Q_E , or recirculating power fraction, $\epsilon = 1/Q_E$, are computed. Results are displayed for a pulsed-plasma system, as directly simulated by the computer code and assuming the reactor performance at code termination represents a steady-state burn configuration. Details of this energy balance calculation are given in Sec. A.7.
- The option exists to model the reversed-field pinch, spheromak, tokamak, EBT, or stellarator assuming appropriate experimental temperature, density, and current profiles are available. If the plasma minor cross section is noncircular, these profiles must be mapped into a circular surface having an effective circular cross section equivalent to the actual surface being modeled.
- A simultaneous, time-dependent thermal response of the first wall during startup, burn, and plasma quench is generated. This one-dimensional heat-transfer calculation is made for a two-region first wall (i.e., coated or tiled surfaces) that can be cooled with a variety of coolant choices.

- A time-dependent mechanical/structural response of the first wall is computed simultaneously with the burn simulation, producing a one-dimensional stress history of the same structure used in the above-mentioned heat-transfer calculation.
- A file is created for interactive use with a standardized reactor costing code.¹

The modelistic details of the CRFPR systems and burn code are presented below. This description is specifically written for CRFPR simulations, although the model is easily extended to other fusion concepts. Burn simulations have been performed for tokamaks, stellarators, bumpy tori, and compact toroids by using concept-specific profile information and appropriate transport. The CRFPR code described herein is benchmarked against the DD/STARFIRE tokamak results and has shown excellent agreement.²

A.1. Computer Model for Burn Simulation.

The plasma behavior is described by a set of first-order differential equations. These time-dependent equations describe particle inventories, plasma temperatures, spatial variations, and a range of integrated plasma powers. The more general form of the calculation uses deuterium as the primary fueling source. The reaction rates, R_{ij} , of interest are summarized below:

$$R_{DDp} : D + D \rightarrow T(1.01 \text{ MeV}) + p(3.03 \text{ MeV}) \quad (\text{A-1A})$$

$$R_{DDn} : D + D \rightarrow {}^3\text{He}(0.82 \text{ MeV}) + n(2.45 \text{ MeV}) \quad (\text{A-1B})$$

$$R_{DT} : D + T \rightarrow {}^4\text{He}(3.52 \text{ MeV}) + n(14.06 \text{ MeV}) \quad (\text{A-1C})$$

$$R_{DHe} : D + {}^3\text{He} \rightarrow {}^4\text{He}(3.67 \text{ MeV}) + p(14.67 \text{ MeV}) . \quad (\text{A-1D})$$

The spatially averaged density of five ion species listed above (H, D, T, ${}^3\text{He}$, and ${}^4\text{He}$) are computed as a function of time. Rate equations used to calculate the time variation of the line density, $N_j = n_j \pi r_p^2$, are given below:

$$\dot{N}_\alpha = -N_\alpha M / \tau_{pi} + R_{DT} + R_{DHe} \quad (\text{A-2A})$$

$$\dot{N}_H = -N_H M / \tau_{pi} + R_{DHe} + R_{DDp} \quad (\text{A-2B})$$

$$\dot{N}_{He} = S_{He} - N_{HeM}/\tau_{pi} + R_{DDn} - R_{DHe} \quad (A-2C)$$

$$\dot{N}_T = S_T - N_{TM}/\tau_{pi} + R_{DDp} - R_{DT} \quad (A-2D)$$

$$\dot{N}_D = S_D - N_{DM}/\tau_{pi} - R_{DT} - 2R_{DDp} - 2R_{DDn} - R_{DHe} , \quad (A-2E)$$

where He designates ^3He , α designates ^4He , and $\dot{N}_j = dN_j/dt$. Total particle inventories, including both Maxwellian species, N_{jM} , and energetic (non-Maxwellian or superthermal) particles, are taken into account by these rate equations. This formulation separates the plasma into five energetic species, each through a Fokker-Planck model thermalizing against a homogeneous-background Maxwellian plasma of electron and ion at respective temperatures. The Maxwellian component of the energetic particle-distribution functions is continuously subtracted and merged into the thermal ion background. Particle loss is assumed to occur only from the Maxwellian plasma according to a loss time τ_{pi} . Neutral-gas fueling at a rate S_j (1/m s) is included for deuterium, tritium, and ^3He . The reaction rates for each species are evaluated from the following equations:

$$R_{DDn} = \frac{1}{2} g_{DDn} n_D^2 \langle \sigma v \rangle_{DDn} A_p \quad (A-3A)$$

$$R_{DDp} = \frac{1}{2} g_{DDp} n_D^2 \langle \sigma v \rangle_{DDp} A_p \quad (A-3B)$$

$$R_{DT} = g_{DT} n_D n_T \langle \sigma v \rangle_{DT} A_p \quad (A-3C)$$

$$R_{DHe} = g_{DHe} n_D n_{He} \langle \sigma v \rangle_{DHe} A_p , \quad (A-3D)$$

where the plasma cross-sectional area is $A_p = \pi r_p^2$, r_p is the plasma radius defined as the cold-temperature [$T(r) \rightarrow 0$] plasma boundary, and g_{ij} is a profile factor. These equations use Maxwellian-averaged cross sections^{3,4} and total particle densities (i.e., energetic plus Maxwellian densities). Because the energetic particle population is typically very small (< 1%) for the DT

densities being considered here, the non-Maxwellian contribution to the reaction rate is simply approximated by using total densities in the rate equations. A discussion of the nonthermal effects of energetic particles is given in Ref. 2. The profile-averaged weighting functions, g_{ij} , are evaluated from an expression of the following form.

$$g_{DDn} = \frac{\int_0^R P [n_D(r)]^2 \langle \sigma v \rangle_{DDn} 2\pi r dr}{n_D^2 \langle \sigma v \rangle_{DDn} |_{T_{IM}} A_P}, \quad (A-4)$$

with the other profile terms analogously derived. The radial dependence of the total ion density, $n_i(r)$, and all constituent densities (n_D , n_T , n_{He} , n_α , n_H) are taken to be identical. Integrating over the plasma radius, the average ion density is given by

$$n_i = \int_0^R P n_i(r) 2\pi r dr / A_P. \quad (A-5)$$

The density-weighted average Maxwellian temperature is given by the following expression:

$$T_{iM} = \int_0^R P T_{iM}(r) n_i(r) 2\pi r dr / N_i, \quad (A-6)$$

where $N_i = n_i A_P$.

Changes in the plasma radius introduced by adiabatic dimensional changes are taken into account by the following plasma energy balance:

$$d(3p\pi R_p^2/2)/dt = P_{SUM} - p d(\pi R_p^2)/dt, \quad (A-7)$$

where p is the total plasma pressure and P_{SUM} is the sum of all plasma powers as defined below and is expressed here on the basis of a unit toroidal length. The second term in Eq. (A-7) subtracts the direct-conversion work performed by a high-beta plasma expanding against confining magnetic fields and generally is negligible for the conditions being examined for the CRFPR. The components of P_{SUM} are defined below:

$$P_{\text{SUM}} = P_Q - P_{\text{RAD}} - P_{\text{COND}} + P_{\text{OHM}} + P_{\text{AUX}} . \quad (\text{A-8})$$

In the order listed, these powers (MW/m) are related to total charged-particle generation, radiation, thermal conduction, ohmic heating, and (optional) auxiliary heating; each power component is described in Sec. A.3. The plasma radius variation is negligible for the CRFPR, and dx/dt is equal to zero, where $x = r_p/r_w$ is the plasma radius normalized to the radius of the first material surface.

A global accounting of the plasma energy, W_p , is evaluated from Eq. (A-7), which can be rewritten as follows:

$$\dot{W}_p = -\frac{4}{3} W_p \frac{\dot{x}}{x} + P_{\text{SUM}} , \quad (\text{A-9})$$

where the first term on the right-hand side represents direct-conversion work, if applicable. The Maxwellian component of the plasma energy is defined from Eqs. (A-5) and (A-6) as

$$(W_p)_M = 3k_B(N_{iM}T_{iM} + N_eT_e) , \quad (\text{A-10})$$

and the Maxwellian electron and ion energy equations are given below:

$$\frac{d}{dt} \left(\frac{3}{2} N_{iM} k_B T_{iM} \right) = -N_{iM} k_B T_{iM} \frac{2\dot{x}}{x} - P_{Ci} , \quad (\text{A-11})$$

$$\frac{d}{dt} \left(\frac{3}{2} N_e k_B T_e \right) = -N_e k_B T_e \frac{2\dot{x}}{x} + P_{\text{OHM}} - P_{\text{RAD}} - P_{\text{Ce}} , \quad (\text{A-12})$$

where the electron/ion conduction powers, P_{Cj} ($j = i, e$), have been introduced and $k_B = 1.602(10)^{-16}$ J/keV.

Nine first-order differential equations have been introduced up to this point: five rate equations (H, D, T, ^3He , ^4He), one total energy equation, two particle energy equations (ion and electron), and one plasma-expansion (pdV

work) equation. In addition, all individual plasma powers are integrated with time, including the total charged-particle power, neutron power for both DD and DT reactions, direct-conversion work, Bremsstrahlung, cyclotron radiation into the first wall and first-wall penetrations, line radiation, ohmic heating, and electron and ion thermal conduction. Finally, the five rate equations [Eqs. (A-2)] are integrated, which in turn provide the population of energetic particles to be used as input to the Fokker-Planck model. A total of 24 equations are then integrated using a fourth-order Runge-Kutta method. This portion of the program follows the total species densities, plasma radius, total plasma energy, Maxwellian species temperature, and density variation resulting from plasma column radius changes or energy/particle losses. In addition, all plasma powers are integrated, and the production of energetic particles is computed for use by the Fokker-Planck model.

A.2. Fokker-Planck Slowing-Down Calculation.

The slowing down of energetic charged particles in the plasma is described by a Fokker-Planck model. The Fokker-Planck routine receives the incremental energetic particle additions each time step. This calculation does not modify the total species densities, plasma radius, or total plasma energy determined from the main integrating routine. Only the Maxwellian electron and ion energy equations need be modified by the Fokker-Planck equations, along with the Maxwellian number density of each ionic species. Five species are separately followed: hydrogen, $p(3.03$ and 14.67 MeV); tritium, $T(1.01$ MeV); ^3He , $\text{He}(0.82$ MeV); ^4He , $\alpha(3.52$ and 3.67 MeV); and deuterium, $D(\text{NES})$. Energetic deuterium species are produced only through nuclear-elastic-scattering (NES) events, which have been shown² to be insignificant in the density range of interest to this study. Allowances for an energetic distribution of deuterium, therefore, are not necessary, although an account for this species is retained in event neutral-beam heating studies or the examination of lower-density systems are desired.

Incremental additions of energetic particles are passed from the integration routine to the Fokker-Planck model. Energetic particles are added to the respective distribution functions as a Gaussian distribution that is centered about the "birth" energy with a velocity spread given by

$$\Delta v_s = (2k_B T_{iM}/M_{iM})^{1/2} . \quad (\text{A-13})$$

The properties of Maxwellian background species are used. A more-accurate expression would use the temperature corresponding to the peak of the cross section-velocity product, σv , for the particular reacting species,⁴ although this higher-order effect is not incorporated into this model. This spread of the Gaussian birth spectrum also includes the recoil energy of the interacting Maxwellian species. Comparing the energy content of the incremental distribution function, Δf_s , to that of the birth energy, $\Delta n_s E_s$, leads to adjustment of the background temperature that accounts for the loss of Maxwellian plasma energy resulting from the disappearance of the reacting species. Additions to the distribution function, f_s , for the energetic species are then given by

$$\Delta f_s(n/v^3) = \frac{\Delta n_s}{4\pi^{3/2}(\Delta v_s)v_s^2 e^{[(v - v_s)/\Delta v_s]^2}} , \quad (A-14)$$

where the velocity v_s corresponds to the birth energy of the energetic species. The two alpha-particle and proton species are added to their respective distribution functions, leading to a double-peaked slowing-down spectrum.⁵

At a given time step after a pulse of energetic particles is added to the respective superthermal distribution, a superthermal slowing-down calculation is then performed for all species, thereby transferring energy to the background (Maxwellian) electron and ion species. This model is also used to calculate the Maxwellian electron/ion equilibration. The Maxwellian component of each distribution function is subtracted after each time step, and these particles are added to the background ions. The background ion velocity is given by the following expression:

$$v_i = (2k_B T_{iM}/M_{iM})^{1/2} , \quad (A-15)$$

with the revised distribution function being given by

$$f' = f - \frac{\Delta n_{jM}}{\pi^{3/2}v_i^3} e^{-(v/v_i)^2} . \quad (A-16)$$

The quantity Δn_{jM} is defined so that $f'(n/v^3) > 0.0$ for each velocity mesh in the velocity range $0 < v < 4v_i$. The quantity Δn_{jM} , therefore, represents the incremental Maxwellian ion densities added to the background population for each

energetic species. The revised distribution function, f' , then consists of purely non-Maxwellian particles.

After the slowing-down calculation is performed, the Maxwellian ion/electron energy is reinitialized along with the total Maxwellian ion density and the Maxwellian density of each ion component. After redistributing the energy and densities (Maxwellian versus energetic species) within the plasma, the integrating routine proceeds to another time step. It is important to limit the Fokker-Planck calculation to redistributing energy among particles within the plasma, with the profile-integrating routine governing total particle inventories and total plasma energies.

A.3. Plasma Powers and Profile Averages.

This section summarizes the analytic expressions used to describe all plasma energy gains and losses. In all cases, the powers are evaluated locally and integrated over the plasma cross section using the time-evolving, but functionally assumed, radial profiles. A typical power may be generally represented as a function of minor plasma radius according to

$$P(r) = f[B(r), j(r), n(r), T(r)] , \quad (A-17)$$

with $P(r)$ being a function of magnetic field, $B(r)$, current density, $j(r)$, plasma density, $n(r)$, and plasma temperature, $T(r)$. The computer model reduces these powers to profile-average quantities given by

$$P = gf(B, j, n, T). \quad (A-18)$$

The weighting functions, g , are given by

$$g = \frac{\int_0^R P(r) 2\pi r dr}{PA_p} . \quad (A-19)$$

The parameters in Eq. (A-18) are defined as follows:

$$B \equiv B_{\phi 0} , \quad (A-20A)$$

$$j \equiv I_{\phi}/A_p , \quad (A-20B)$$

$$n \equiv \int_0^R n(r) 2\pi r dr / A_p , \quad (A-20C)$$

$$T \equiv \int_0^R T(r) n(r) 2\pi r dr / n A_p , \quad (A-20D)$$

where the peak toroidal field on axis, $B_{\phi 0}$, the toroidal plasma current, I_{ϕ} , and the plasma cross-sectional area, $A_p = \pi r_p^2$, are used. These predefined quantities then provide the basis from which the weighting factors are derived. The above definitions are arbitrary, with specific definitions producing a specific set of weighting functions. The following list of powers are given in units of watts per meter of toroidal length and are expressed in the form of Eq. (A-18) with the inferred calculation of weighting functions as defined by Eq. (A-19).

a. Energetic-Particle Heating. Using the four reaction rates specified by Eqs. (A-3), the energetic charged-particle (heating) powers are given by

$$P_H = [R_{DDp}(3.03) + R_{DHe}(14.67)] 10^3 k_B , \quad (A-21A)$$

$$P_T = R_{DDp}(1.01) 10^3 k_B , \quad (A-21B)$$

$$P_{He} = R_{DDn}(0.82) 10^3 k_B , \quad (A-21C)$$

$$P_{\alpha} = [R_{DT}(3.52) + R_{DHe}(3.67)] 10^3 k_B , \quad (A-21D)$$

where the hydrogen, tritium, ^3He , and ^4He rates are known. The total charged-particle power retained by the plasma is given by

$$P_Q = P_H + P_T + P_{He} + P_{\alpha} - 3k_B T_{iM}(0.8 R_{DT} + 0.75 R_{DDn}) . \quad (A-22)$$

Two Maxwellian ions are lost for each fusion reaction, with the energy being contributed to the energetic fusion products. If the reaction products are charged, this energy is retained in the plasma and no net energy loss occurs. This additional energy is added to the charged particles and is inherently taken into account by the Gaussian energy spread of the energetic particles that in turn is added to the Fokker-Planck distribution functions. That portion of P_Q

associated with the charged-particle energy loss corresponds to the energy carried away from the system by the fusion neutrons. These neutron powers are given by

$$P_{DTn} = R_{DT} [(14.1)10^3 k_B + 3k_B T_{IM}(0.80)] , \quad (A-23A)$$

$$P_{DDn} = R_{DDn} [(2.45)10^3 k_B + 3k_B T_{IM}(0.75)] , \quad (A-23B)$$

with the quantities 0.75 and 0.80 accounting for the fractions f Maxwellian-species energy given to the neutrons in each reaction.

b. Ohmic Heating. The ohmic heating power is given by

$$P_{OHM} = g_{OHM} \eta_{||} j^2 A_p , \quad (A-24)$$

where the following expression for the classical plasma resistivity^{5,6} is used:

$$\eta_{||}(\text{ohm m}) = 9.62(10)^{-10} Z_{\text{eff}}^2 \ln \Lambda / \gamma_E T_e^{3/2} . \quad (A-25)$$

The parameter Z_{eff} is the sum of $n_j Z_j^2$ divided by the sum of $n_j Z_j$ taken over all ion species j . The Coulomb logarithm is defined as follows:

$$\Lambda = 4.907(10)^{17} T_e^{3/2} / Z_{\text{eff}} n_e^{1/2} \quad (T_e < 0.0362 \text{ keV}) , \quad (A-26A)$$

$$\Lambda = \Lambda(0.0362/T_e)^{1/2} \quad (T_e > 0.0362 \text{ keV}) . \quad (A-26B)$$

The value of γ_E is approximated by the following expression:

$$\gamma_E = 0.582 + 0.418 [(Z_{\text{eff}} - 1)/Z_{\text{eff}}]^2 . \quad (A-27)$$

c. Radiation Power. The radiation power, P_{RAD} , consists of Bremsstrahlung, line, and cyclotron radiations. Impurity radiation is modeled by oxygen and uses fitted analytic functions.⁷ Any number of impurities may be added to the plasma assuming the ion species are fully stripped. The expression for line radiation, however, includes only oxygen. The average Bremsstrahlung power is⁸

$$P_{\text{BR}} = 5.35(10)^{-37} g_{\text{BR}} n_e^2 Z_{\text{eff}} T_e^{1/2} A_p . \quad (A-28)$$

The cyclotron radiation leaving a nonabsorbing plasma⁸ is given by

$$P_{CY}^T = 6.20(10)^{-17} n_e B^2 T_e (1 + T_e/204) . \quad (A-29)$$

Accounting for absorption and assuming the walls surrounding the plasma are nonreflecting,⁸ the actual fraction of cyclotron radiation leaving the plasma is given by

$$k_L = 2.1(10)^{-3} T_e^{7/2} (c B \epsilon_0 / 2 r_p n_e e)^{1/2} , \quad (A-30)$$

where $\epsilon_0 = 10^{-9}/36\pi$ F/m is the permittivity of free space, the speed of light is $c = 3(10)^8$ m/s, and the electronic charge is given by $e = 1.602(10)^{-19}$ C.

The fraction of P_{CY}^T leaving an absorbing plasma surrounded by a reflecting cylindrical wall is given as the function k_C by Krajcik.⁹ For a first-wall hole fraction f_H , therefore, the cyclotron radiation power leaving the plasma and escaping through these holes is

$$P_{CY}^H = g_{CYH} P_{CY}^T k_L f_H A_p . \quad (A-31)$$

The power leaving the plasma and absorbed by the first wall is

$$P_{CY}^W = g_{CYW} P_{CY}^T k_C (1 - f_H) A_p , \quad (A-32)$$

and the total power leaving the plasma is given by

$$P_{CY} = P_{CY}^H + P_{CY}^W . \quad (A-33)$$

d. Transport. As with most approaches to magnetically confined fusion energy, transport scaling represents a key uncertainty for any reactor projection. A transport-based confinement time scaling per se is not yet available for RFPs. By equating the ohmic heating power density, ηj^2 , to an energy loss rate, $3nk_B T/\tau_E$, of unspecified mechanism, an "ohmic" scaling results, $\tau_E(\text{OHMIC}) \propto \beta_\theta T^{3/2} r_p^2 / Z_{\text{eff}}$, where the plasma resistivity is assumed to be classical and pressure balance is invoked. The coefficient in this expression for $\tau_E(\text{OHMIC})$ depends on plasma density, temperature, and current-density [i.e., $\mu(r)$] profiles. This ohmic scaling for a flat and a $J_0(\mu r)$ temperature profile with $p(r) \propto J_0^2(\mu r)$ is compared in Fig. A-1 for a number of key RFP experiments that have reported energy confinement times while operating at a centerline temperature, $T(0)$. The weak dependence of the coefficient $\tau_E(\text{OHMIC})/(\beta_\theta T(0)^{3/2} r_p^2 / Z_{\text{eff}})$ on Z_{eff} is shown, and a nominal beta of $\beta_\theta \approx 0.2$ was used to show this dependence. Little physics other than the assumption of classical resistivity has been used, except to state that the beta

Fig. A-1. Comparison of ohmic transport scaling with a number of RFP experiments.

is limited to a specific value by the transport mechanism. If the parameter I_ϕ/N is then presumed to be relatively constant as the toroidal plasma current, I_ϕ , is increased, the relationship $I_\phi \propto T$ then results. This dependence is generally expected on the basis of pressure balance with both β_θ with I_ϕ nominally fixed. For present-day experiments $I_\phi = 0.1 - 0.2$ MA, and projected reactors have $I_\phi \approx 18$ MA, both operating with I_ϕ/N in the range $(1.5-8)10^{-14}$ A m. The ohmic scaling would then give

$$\tau_E(\text{OHMIC}) = 1.4(10)^{-10} I_\phi^{3/2} r_p^2, \quad (\text{A-34})$$

where I_ϕ has units of amperes. The coefficient has been benchmarked to the ZT-40M experiment¹⁰ at $I_\phi = 120$ kA, where $\tau_E \approx 0.2$ ms. It is emphasized, however, that the current exponent being predicted from ZT-40M is near unity.

Self-consistent experimental evidence to date generally has shown $\tau_E \propto I_\phi^\nu f(\beta_\theta)$ for a range of RFPs, where $\nu = 1.0-1.5$; the lower exponent is exhibited by ZT-40M, and the higher values are indicated by TPE-1RM.¹¹ For the present reactor simulations, the more pessimistic scaling for the electron conduction time is taken:

$$\tau_{ce} = 5(10)^{-8} I_\phi r_p^2 f(\beta_\theta), \quad (\text{A-35})$$

where I_ϕ is expressed in units of amperes, the coefficient is again benchmarked to ZT-40M experiment,¹⁰ and again emphasizing that the current exponent is near unity for ZT-40M. Beta saturation effects in neutral-beam-heated tokamaks¹²⁻¹⁴ have indicated the value of τ_{ce} is reduced by $(1/\beta_\theta)^2$ as a critical value of beta, $\beta_{\theta C}$, is exceeded. Typically, $f(\beta_\theta)$ equals unity for $\beta_\theta > \beta_{\theta C}$ and $(\beta_{\theta C}/\beta_\theta)^2$ otherwise, where $\beta_{\theta C} \approx 0.13$ is representative of present ohmically heated RFPs. The following functional forms emerge and are used for $f(\beta_\theta)$:

$$f(\beta_\theta) \begin{cases} = 1 & (\beta_\theta < 0.13) \\ = (0.13/\beta_\theta)^2 & (\beta_\theta > 0.13) \end{cases} \quad (\text{A-36})$$

Having defined the electron conduction time, preliminary experimental measurements indicate the ion-particle confinement time is given approximately by¹⁵

$$\tau_{pi} \approx 4\tau_{ce} . \quad (A-37)$$

The ion-conduction time is assumed equivalent ($\tau_{ci} \approx \tau_{pi}$).

The above equations define the transport model used in the reactor plasma simulations. Other energy confinement times are also calculated for comparison purposes. Such comparisons are particularly crucial and useful for the RFP, where an intrinsic or physics-based transport scaling is not available, economics dictate a particular value of $\tau_E = \tau_E(OPT)$, and in the process of reconciling the two with ohmic scaling it becomes useful to examine the "benchmarks" established by classical or Alcator scaling laws. The classical ion-conduction time is given below:

$$\tau_{CLASS} = \frac{19.08 T_i^{3/2} r_p^2}{(\beta_0 a_i^{1/2} \ln \Lambda)} , \quad (A-38)$$

where the atomic mass for DT is taken as $a_i = 2.5$. A Bohm-related confinement time is given by

$$\tau_{BOHM} \approx \frac{200 r_w^2 B_\theta(r_p)}{62.5 T_e} , \quad (A-39)$$

where a factor of 200 multiplies the usual Bohm time. Finally, a tokamak-related Alcator scaling of the following form is used for comparisons:

$$\tau_{ce}(ALC) \approx 4(10)^{-21} n r_p^2 . \quad (A-40)$$

A.4. Magnetic-Field, Density, and Temperature Profiles. This section specifies the magnetic-field profiles used to model reactor startup, burn, and rundown (plasma quench). A complete one-dimensional plasma equilibrium is performed at selected time intervals while imposing the experimentally derived plasma density, temperature, and current-density profiles and while satisfying pertinent edge-plasma boundary conditions. Following the formulation suggested

by Ortolani,¹⁶ the magnetic-field spatial distribution is described by specifying the current density both parallel and perpendicular to the magnetic field. This procedure separates the magnetic-field variations resulting from plasma pressure gradients from the much larger force-free parallel current component; typically, field variations from pressure gradients are usually small for $\beta_\theta < 0.2$.

From the Maxwell equations, assuming a static electric field, it follows that

$$\vec{\nabla} \times \vec{B} = \mu_0 \vec{j} = \mu_0 (\vec{j}_\parallel + \vec{j}_\perp) \quad (\text{A-41})$$

$$\vec{j} \times \vec{B} = \vec{\nabla} p. \quad (\text{A-42})$$

Performing a cross-product operation,

$$(\vec{j} \times \vec{B}) \times \vec{B} = (\vec{j} \cdot \vec{B}) \vec{B} - B^2 \vec{j} = \vec{\nabla} p \times \vec{B}. \quad (\text{A-43})$$

The parallel and perpendicular current components are given by

$$\vec{j}_\parallel = \frac{(\vec{j} \cdot \vec{B}) \vec{B}}{B^2} = \mu \vec{B} \quad (\text{A-44A})$$

$$\vec{j}_\perp = \frac{\vec{\nabla} p \times \vec{B}}{B^2}. \quad (\text{A-44B})$$

Expanding Eq. (A-43) in cylindrical coordinates where ϕ and θ are the major and minor toroidal angles, respectively, yields the following working equations used to evaluate B_θ and B_ϕ :

$$-\frac{\partial B_\phi}{\partial r} = \mu_0 j_\theta = \mu B_\theta + \mu_0 \frac{\partial p}{\partial r} \frac{B_\phi}{B^2} \quad (\text{A-45A})$$

$$\frac{1}{r} \frac{\partial}{\partial r} (r B_\theta) = \mu_0 j_\phi = \mu B_\phi - \mu_0 \frac{\partial p}{\partial r} \frac{B_\theta}{B^2}. \quad (\text{A-45B})$$

Except for special cases, these equations must be numerically integrated. Taking μ as a constant, the analytic idealized Bessel-function model (BFM) may be derived for $p(r) = 0$. In this case it follows that

$$B_{\theta}(r) = A_{\theta} J_1(\mu r) \quad (A-46A)$$

$$B_{\phi}(r) = A_{\phi} J_0(\mu r) , \quad (A-46B)$$

where $J_0(\mu r)$ and $J_1(\mu r)$ are Bessel functions of the first kind with $A_{\theta} = A_{\phi}$. Using Eq. (A-44), the plasma current densities are given by

$$j_{\phi}(r) = \frac{\mu A_{\phi} J_0(\mu r)}{\mu_0} \quad (A-47A)$$

$$j_{\theta}(r) = \frac{\mu A_{\phi} J_1(\mu r)}{\mu_0} . \quad (A-47B)$$

The toroidal plasma current, I_{ϕ} , must equal the integral of j_{ϕ} over the plasma cross section, which leads to

$$A_{\theta} = B_{\theta}(r_p)/J_1(\mu r_p), \quad (A-48)$$

where r_p is defined as the first material [$T(r_p) > 0$]. Parameters of experimental interest are defined as follows:

$$\theta = B_{\theta}(r_p)/\langle B_{\phi} \rangle \text{ (pinch parameter)} \quad (A-49)$$

$$F = B_{\phi}(r_p)/\langle B_{\phi} \rangle \text{ (reversal parameter)}, \quad (A-50)$$

where

$$\langle B_{\phi} \rangle = \frac{2}{r_p^2} \int_0^{r_p} B_{\phi} r dr . \quad (A-51)$$

The following expression is for the pinch parameter in terms of $\mu(r)$ results:

$$\theta = \frac{\mu r_p}{2} \frac{A_{\theta}}{A_{\phi}} , \quad (A-52)$$

where $A_{\theta} = A_{\phi}$ for the force-free ($\beta_{\theta} = 0$) BFM. The relationship between F and θ then becomes

$$F = \frac{\theta J_0(2\theta)}{J_1(2\theta)} . \quad (A-53)$$

A major shortcoming of the force-free BFM is the absence of plasma pressure.

From the Maxwell equation $\nabla p = \nabla \times \vec{B} \times \vec{B} / \mu_0$ and assuming the Bessel Function magnetic-field profiles are approximately maintained in the presence of plasma pressure, the following relationship between A_θ and A_ϕ results:

$$\beta_\theta = 1 - (A_\theta/A_\phi)^2, \quad (\text{A-54})$$

where the experimentally defined poloidal beta is given by

$$\beta_\theta = \frac{\langle p \rangle}{B_\theta^2(r_p)/2\mu_0}. \quad (\text{A-55})$$

For this approximate model the plasma pressure profile is described by $p(r) \propto J_0^2(\mu r)$. Observing the BFM equations, only θ and β_θ need be provided to establish the magnetic-field profile. The magnitude of the fields are then determined by I_ϕ and r_p . Even when numerically solving Eqs. (A-45), for the generalized field and current profiles, similar information is needed. The good agreement between the Bessel-function model and actual MHD stable field profiles is shown in Fig. A-2, where vacuum fields are taken beyond the radius, r_p .

Although the magnetic-field profiles for the Bessel-function model are in good agreement with the numerically computed profiles, this model has two limitations. The pressure-modified magnetic-field profiles are not described accurately by Bessel functions, and the experimental pressure profile may substantially deviate from the $p(r) \propto J_0^2(\mu r)$ functional dependence. Because $\beta_\theta \approx 0.1-0.2$, large changes in the pressure profile have little effect on the magnetic-field structure. Secondly, the current density profile given by Eqs. (A-47) in the BFM can be substantially different from the experimentally observed current density. The BFM in particular requires $\mu_0 j_\theta = \mu B_\theta$, forcing a large current density near the plasma edge where the plasma temperature is approaching zero and the plasma resistance is large. This condition is experimentally unphysical and overestimates the effective resistive heating in the plasma.

This shortcoming is resolved by direct numerical integration of Eq. (A-45). In this case the experimental density, $n(r)$, and temperature, $T(r)$, profiles are imposed along with the current density profiles using $\mu_0 j_\parallel = \mu B$, where $\mu(r)$ is a function of radius. The current density profile is forced to zero at the plasma edge by requiring $\mu(r) \rightarrow 0$ as $r \rightarrow r_p$. The numerical solution of Eq. (A-45) is straightforward if the central beta, $\beta_0 = p_0/(B_{\phi 0}^2/2\mu_0)$, and the radial

Fig. A-2. Comparison of Bessel-function model with numerically computed field profiles.

derivative of the poloidal magnetic field, $(\partial B_\theta / \partial r)_r = 0$, are known a priori. In fact, for $B_\phi \gg B_\theta$, as for a stellarator and to first order for a tokamak, this condition is indeed appropriate, assuming $n(r)$, $T(r)$, and $\mu(r)$ are known. For a reversed-field pinch and the spheromak, where $B_\theta \approx B_\phi$, and for an exact calculation of tokamak profiles, where $B_\theta \sim 0.1 B_\phi$, the centerline quantities must be derived, requiring numerical iteration of the profiles until the boundary conditions are satisfied.

Imposing $n(r)$, $T(r)$, and $\mu(r)$ profiles, solutions for $B(r)$ and $j(r)$ having the desired values of β_θ and θ are found. A given iteration requires numerical integration of Eqs. (A-45) and comparison of derived results with the desired values of β_θ and θ . The new iteration then adjusts the centerline beta and poloidal magnetic-field derivative. Simultaneous iteration on two variables uses Newton's method, and the resultant iteration converges quadratically since the number of significant places doubles on each iteration. Like the transport [Eq. (A-35)], the input profiles are referenced to the ZT-40M device.¹⁰ Operating with a toroidal plasma current of 120 kA in a 0.2-m minor radius

machine, the centerline electron temperature exceeds 300 eV at a time of 2 ms into the discharge. With power crowbar operation greater than 20-ms steady-state discharges with poloidal betas of $\beta_\theta \sim 0.1$ have been obtained. Thomson-scattering measurements of T_e at a minor radius of 0.14 m show roughly 2/3 of the central temperature, which is indicative of $T(r) \propto J_0^{1/2}(\mu r)$. Interferometric density measurements may be approximately represented by $n(r) \propto J_0^{3/2}(\mu r)$, implying a pressure profile of $p(r) \propto J_0^2(\mu r)$, which is the approximate BFM solution. At reactor-like plasma temperatures, better confinement properties are projected because of higher plasma currents, and more-gradual temperature gradients are expected. Based on these considerations, simple Bessel-function temperature and density profiles [$T(r) \propto J_0(\mu r)$, $n(r) \propto J_0(\mu r)$ where, $T(r)$ and $n(r) \rightarrow 0$ as $r \rightarrow r_p$] are taken for the reactor plasma. In this case the peak-to-average density is 2.3 and the density-weighted peak-to-average temperature is 1.6. As determined by the parametric systems code¹⁷ for a fixed pressure profile, $p(r) \propto J_0^2(\mu r)$, the specific shape of $n(r)$ and $T(r)$ has little impact on the reactor power output; as these profiles are changed, the operating temperature and density must be adjusted to maintain the same power output, and this in turn may affect other parameters such as the plasma resistive losses.

The RFP field profile is then determined when the current density profile is specified through $\mu(r)$. The spatial dependence of $\mu(r)$ is chosen to provide an accurate fit to the experimentally measured toroidal magnetic flux and to the toroidal and poloidal magnetic fields at the discharge chamber wall. A "best-fit" model uses a constant $\mu(r)$ until the breakpoint $r = \alpha r_p$ ($\alpha < 1$), where $\mu(r)$ is linearly extrapolated to zero at $r = r_p$. This breakpoint is described by a fitted function as follows:¹⁸

$$\alpha = 1.0 \quad (\theta < 1.2) \quad (\text{A-56A})$$

$$\alpha = 1.92 - f(\theta)/2.6 \quad (1.2 < \theta < 2.5) \quad , \quad (\text{A-56B})$$

where the function $f(\theta)$ is given by

$$f(\theta) = 0.04623 + 1.47121\theta + 1.21618\theta^2 - 0.83678\theta^3 + 0.13193\theta^4 \quad . \quad (\text{A-56C})$$

A.5. Equilibrium and Stability. The reversed-field force-free configuration was predicted analytically by Taylor¹⁹ as the lowest plasma energy state $\theta > 1.2$ and negligible beta for a plasma confined inside a perfectly conducting shell. From Sec. A.4. the pinch parameter, θ , and reversal parameter, F , are related according to $F = \theta J_0(2\theta)/J_1(2\theta)$, which is plotted in Fig. A-3 for the zero-beta Taylor state. Numerical calculations¹⁹ have shown the existence of high-beta stable states ($\beta_\theta = 0.3-0.4$) in the F - θ range, $\theta = 1.5-2.0$ and $F = -0.5$ to -1.0 , which is denoted as the high-beta model. A

Fig. A-3. Universal F - θ curve showing data from four RFP machines, where $F = B_\phi(r_w)/\langle B_\phi \rangle$ and $\theta = B_\theta(r_w)/\langle B_\phi \rangle$. The theoretical curve for the Bessel-function model¹⁸ is shown. The dotted curve is for the high-beta model.¹⁹

substantial body of experimental evidence has verified the Taylor theory, which is used for the reactor calculations.

The actual F- θ trajectory used in the computer analysis must be consistent with the one-dimensional plasma equilibrium which satisfies the Maxwell equations. The experimentally derived and extrapolated temperature and density profiles are taken as $n(r) \propto T(r) \propto J_0(\mu r)$. Forcing the current density to zero at the plasma edge according to the "best-fit" model [Eq. (A-56)] gives the F- θ trajectories depicted in Fig. A-4 for $\beta_\theta = 0$ and 0.25. Also given in Fig. A-4 is an approximate beta-modified analytic Bessel-function solution, where $F = \theta^* J_0(2\theta^*) / J_1(2\theta^*)$ and $\theta^* = \theta(1 - \beta_\theta)^{1/2}$.

Recent experimental data also indicate a minimization of plasma losses if the F- θ trajectory is followed during plasma startup and burn. The "best-fit" F- θ trajectory provides the relationship between the toroidal, B_ϕ , and poloidal, B_θ , fields during startup/burn at a given poloidal beta, β_θ . Experimental

Fig. A-4. Taylor diagram showing the $\beta = 0$ Taylor curve, the high-beta model, the numerical "best fit" model for $\beta_\theta = 0.0$ and 0.25, and the startup trajectory proposed for the CRFPR.

values of $\theta = 1.55$ and $F = -0.1$ to -0.15 at $\beta_0 = 0.1-0.25$ dictate the magnetic-field structure during the burn simulation.

The presence of a conducting shell provides plasma stability and equilibrium for a relatively short (~ 0.1 s) time scale. For longer times external feedback conductors must provide the image currents required to stabilize the $m = 1$ mode, as predicted by theory. Gross plasma equilibrium is also provided externally by an external vertical field for times longer than 0.1 s. An expression for the required quasi-uniform vertical field is^{20, 21}

$$B_v = (\mu_0 I_\phi / 4\pi R_T) [\ln(8R_T/r_p) + 2\pi\lambda_l/\mu_0 + \beta_0 - 1.5] , \quad (A-57)$$

where λ_l is the inductance per unit length of plasma. For the RFP with Bessel-function profiles, $2\pi\lambda_l/\mu_0 = 0.5$. To provide plasma equilibrium in both the horizontal and vertical directions requires the vertical field to have a curvature that is characterized by the following decay index:

$$n = - \frac{\partial \ln B_v}{\partial \ln r} = \left(\frac{R}{r_p} \right) \frac{B(R_T - r_p) - B(R_T + r_p)}{B(R_T - r_p) + B(R_T + r_p)} , \quad (A-58)$$

where n should lie between 0.0 and 1.5. Constraining the plasma to have a circular cross section further specifies that n be in the range of $0 < n \leq 0.65$.²²

A.6. First-Wall Thermal-Mechanical Response. A critical engineering subsystem in any fusion reactor is the first wall and the in-vacuum components (IVCs) directly exposed to the plasma. Even preliminary reactor designs must apply first-wall thermal fatigue constraints. For this reason the CRFPR computer model directly couples the thermal-mechanical analysis of the first wall and the dynamic simulation of plasma burn. This first-wall thermal-mechanical response serves only a monitoring function, the more detailed analyses of the kind described in Sec. III.D. being used for design purposes.

A one-dimensional heat-transfer calculation follows first-wall temperature variations subject to surface cooling by a specified coolant. A one-dimensional structural analysis is also directly coupled to the first-wall thermal calculation. Both thermal and structural analyses allow two material regions,

although a single water-cooled first wall is used in the burn calculations reported here.

The average surface heat flux incident on the first wall is given by

$$I'_{QW}(W/m^2) = (P_{BR} + P_{LINE} + P_{CY}^W + P_{COND})/(2\pi r_w), \quad (A-59)$$

where Bremsstrahlung, line, cyclotron (into the wall), and conduction powers per unit toroidal length are used. Volumetric heating by the energetic neutrons may also be included, this input being available from the neutronics analysis (Sec. III.B.). The volumetric heating in a 20-mm-thick copper-alloy first wall by 14.1-MeV neutrons amounts to 11.2 MW/m^3 for every MW/m^2 of 14.1-MeV neutrons incident on the first wall. Information is not available for the 2.45 MeV neutron species, which is small for the 50/50 DT fuel being used here.

The powers used for the heat-transfer calculation are given by

$$I_{QW}(W/m^2) = I'_{QW}(2/\pi)R_T/(R_T - r_w) \quad (A-60)$$

$$q_N(W/m^3) = 11.2I_w R_T/(R_T - r_w), \quad (A-61)$$

where the factor $2/\pi$ accounts for the added surface area of a first-wall tube array. The factor $R_T/(R_T - r_w)$, where R_T is the major radius, is used as a first-order consideration of toroidal power peaking.

The one-dimensional two-region thermal-mechanical subroutine uses the physical properties listed in Table A-I for copper alloy and stainless steel. The stainless-steel region is taken to be diminishingly small for the CRFPR first wall. With the copper tube dimensions, the coolant temperature, and heat-transfer coefficient as input, the thermal/mechanical characteristics can be determined.

A.7. Reactor Energy Balance. A reactor energy balance is calculated directly by the simulation code when the conditions at the time of code termination represent a steady-state condition. Figure A-5 depicts the general energy flow diagram for the CRFPR, which is an approximation to the power balance given in Fig. III.L-1. The plasma produces neutron, P_N , radiation, P_{RAD} , and conduction, P_{COND} , powers, which eventually appear as thermal power delivered to the first wall and blanket. All thermal energy delivered to the first wall and blanket coolant is converted with a thermal efficiency, η_{TH} , to

TABLE A-I
FIRST-WALL PHYSICAL PARAMETERS

PARAMETER	REGION 1	REGION 2
	316 STAINLESS STEEL	COPPER ALLOY
Density, $\rho(\text{kg/m}^3)$	7,970	8,880
Thermal conductivity, $k(\text{W/m K})$	19.5	324.
Heat capacity, $c_p(\text{J/kg})$	560.	394.
Thermal expansivity, $\alpha(1/\text{K})$	$17.7(10)^{-6}$	$19.3(10)^{-6}$
Young's Modulus, $E(\text{Pa})$	$1.67(10)^{11}$	$1.38(10)^{11}$
Poisson's ratio, ν	0.29	0.36

Fig. A-5. CRFPR power balance for a long-pulse or steady-state burn.

produce a gross (total) electric power, P_{ET} . Auxiliary power requirements P_{AUX} (pumps, plant operation, etc.) are given as a fraction f_{AUX} of P_{ET} along with power transferred to the magnet coils. The ohmic power losses in the poloidal, P_{PFC}^{Ω} , and toroidal, P_{TFC}^{Ω} , magnet coils are assumed nonrecoverable, but the plasma ohmic losses, P_{Ω} appear in the thermal-conversion cycle. Inefficiencies in supplying P_{TFC}^{Ω} , P_{PFC}^{Ω} , and P_{Ω} are represented by P_{ETS} , which is important primarily for pulsed systems. A fraction ϵ of the total electrical power, P_{ET} , must be recirculated as makeup or recirculating power, $P_C = \epsilon P_{ET}$. The net electric power is $P_E = (1 - \epsilon)P_{ET}$, and the overall plant efficiency is $\eta_p = (1 - \epsilon)\eta_{TH}$. An engineering Q-value, Q_E , is defined as a measure of system performance.

$$Q_E = \frac{P_{ET}}{P_C} = \frac{1}{\epsilon} = \frac{\eta_{TH}(P_N + P_{RAD} + P_{TR})}{P_{\Omega} + P_{TFC}^{\Omega} + P_{PFC}^{\Omega} + P_{AUX} + P_{ETS}} \quad (A-62)$$

As for the thermal-mechanical analyses described in the previous subsection, the calculation of Q_E at this level serves only a monitoring function, with more detailed and integrated calculations of the kind summarized in Sec. III.L. being used for the final design-point determination.

REFERENCES

1. S. C. Schulte, W. E. Bickford, C. E. Willingham, S. K. Ghose, M. G. Walker, "Fusion Reactor Design Studies - Standard Unit Costs and Cost Scaling Rules," Pacific Northwest Laboratory report PNL-2987 (September 1979).
2. R. L. Hagenson and R. A. Krakowski, "An Advanced-Fuel Reversed-Field Pinch Fusion Reactor (DD/RFPR): Preliminary Considerations," Los Alamos National Laboratory report LA-9139-MS (February 1982).
3. L. M. Hively, "Convenient Computational Forms for Maxwellian Reactivities," Nucl. Fus. 17, 873-876 (1977).
4. G. H. Miley, H. Towner, and N. Ivich, "Fusion Cross Sections and Reactivities," University of Illinois report COO-2218-17 (1974).
5. R. L. Miller, "Alpha-Particle Considerations Relevant to the Reversed Field Pinch Reactor (RFPR)," Proc. of the Reversed-Field Pinch Theory Workshop, Los Alamos, NM (April 29-May 2, 1980), Los Alamos National Laboratory report LA-8944-C, p. 39 (January 1982).

6. S. I. Braginskii, "Transport Processes in a Plasma," Reviews of Plasma Physics 1, M. A. Leontovich, ed., Consultants Bureau, NY (1965).
7. K. I. Thomassen (Ed.), "Ohmic Heating Systems Study for a Tokamak EPR," Los Alamos Scientific Laboratory report (CTR Division) submitted to the Division of Fusion Energy in the Department of Energy (1977).
8. D. J. Rose and M. Clark, Jr., Plasmas and Controlled Fusion, 2nd ed., The M.I.T. Press, Cambridge, Mass. (1965).
9. R. A. Krajcik, "The Effect of a Metallic Reflector Upon Cyclotron Radiation," Nucl. Fus. 13, 7 (1973).
10. D. A. Baker, M. D. Bausman, C. J. Buchenauer, L. C. Burkhardt, G. Chandler, J. N. DiMarco, "Performance of the ZT-40M Reversed-Field Pinch with an Inconel Liner," 9th International Conference on Plasma Physics and Controlled Nuclear Fusion Research, Baltimore, USA, paper IAEA CN-41/H-2-1, I, 587 (September 1982).
11. K. Ogawa, Y. Maejima, T. Shimada, Y. Hirano, P. G. Carolan, C. W. Gowers, et al., "Experimental and Computational Studies of Reversed Field Pinch on TPE-IR(M)," ibid, IAEA-CN-41/H-1, I, 575.
12. M. Nagami and the JAERI Team, D. Overskei and the GA Team, "High- β Injection Experiments with Shaped Plasmas in Doublet-III," ibid, IAEA-CN-41/A-2, I, 27.
13. D. Johnson, M. Bell, M. Bitter, K. Bol, K. Brau, T. Crowley, et al., "High Beta Experiments with Neutral Beam Injection on PDX," ibid, IAEA CN-41/A-1, I, 9.
14. M. Murakami, S. C. Bates, J. D. Bell, C. E. Bush, A. Carnevali, B. A. Carreras, et al., "Beta Scaling Experiments in ISX-B," ibid, IAEA-CN-41/A-4, I, 57.
15. D. A. Baker, L. J. Caramana, A. Haberstich, A. R. Jacobson, E. M. Little, K. F. Schoenberg, K. S. Thomas, P. G. Weber, "Preliminary Scaling of ZT-40M with Poloidal Limiters," RFP Workshop, Los Alamos National Laboratory, Los Alamos, NM (1983).
16. S. Ortolani, " μ and Pressure Model," Istituto Gas Ionizzati, Padova, Italy (1983).
17. R. L. Hagenson and R. A. Krakowski, "Compact Reversed-Field Pinch Reactors (CRFPR): Sensitivity Study and Design-Point Determination," Los Alamos National Laboratory report LA-9389-MS (July 1982).
18. J. B. Taylor, "Relaxation of Toroidal Discharges," 3rd Topical Conf. on Pulsed High-Beta Plasma, Culham, UK, p. 59 (1975).
19. A. A. Newton, Li Yin-An, J. W. Long, and B. C. Yeung, "Numerical Investigation of Reversed Field Pinches," 3rd Topical Conf. on Pulsed High-Beta Plasmas, Culham, UK, 323-328 (1975).

20. V. D. Shafranov, Reviews of Plasma Physics 2, 103 (Consultants Bureau, NY, 1966).
21. J. M. Greene, J. L. Johnson, and K. E. Weimer, "Tokamak Equilibrium," Phys. of Fluids 14, 671 (1971).
22. V. S. Mukhovatov and V. D. Shafranov, "Plasma Equilibrium in a Tokamak," Nucl. Fus. 11, 605 (1971).

APPENDIX B: Table of CRFPR Design Parameters

This table contains the comprehensive and uniform design data for the CRFPR. The format of this table follows the DOE/OFE guidelines.¹ Superscripted numbers in parentheses refer to notes found at the end of this table.

TABLE OF REACTOR DESIGN PARAMETERS

<u>Parameter</u>	<u>Unit</u>	<u>Value</u>
1. Characteristic Machine Dimensions		
1.1. Reactor envelope ^(1a)		
1.1.1. Height (coil outside diameter)	m	3.90
1.1.2. Width (coil outside diameter)	m	3.90
1.1.3. Length (major circumference)	m	23.9
1.1.4. Volume of reactor envelope	m ³	285
1.2. Plasma chamber		
1.2.1. Major toroidal radius, R_T	m	3.80
1.2.2. Minor radius	m	0.75
1.2.3. Plasma volume, V_p	m ³	37.7
1.2.4. Plasma chamber volume	m ³	42.2
1.2.5. Wall surface area	m ²	112
1.2.6. Number of sectors, $N^{(1b)}$	-	24
2. Plasma Parameters (Steady State)		
2.1. Plasma dimensions		
2.1.1. Major toroidal radius, R_T	m	3.80
2.1.2. Average minor radius, r_p	m	0.71
2.2. Average ion density, n_i	10 ²⁰ /m ³	6.55
2.3. Average alpha-particle density, n_α	10 ²⁰ /m ³	0.19
2.4. Energy confinement time, τ_E	s	0.23
2.5. Electron confinement time, τ_{pe}	s	0.15
2.6. Ion confinement time, τ_{pi}	s	0.59
2.7. Average Lawson parameter, $n_i \tau_E$	10 ²⁰ s/m ³	1.54
2.8. Average poloidal beta, ^(2a) $\langle \beta_\theta \rangle$	-	0.23
2.9. Average plasma toroidal current	MA	18.4
2.10. Average ion temperature, $\langle T_i \rangle^{(2b)}$	keV	10.
2.11. Average electron temperature, $\langle T_e \rangle^{(2b)}$	keV	10.
2.12. Average alpha-particle energy, $\langle T_\alpha \rangle^{(2c)}$	keV	805.

2.13. Effective plasma ion charge, ^(2d) Z_{eff}	-	1.06
2.14. Reactor cycle		
2.14.1. Burn pulse length	s	Steady state
2.14.2. Total pulse length	s	Steady state
2.15. Fuel cycle	-	DT/Li
2.16. Plasma-heating method	-	Ohmic (to ignition)
2.16.1. Plasma-heating power ^(2e)	MW	25.3
2.16.2. Plasma-heating frequency	GHz	NA
2.17. Plasma energy gain, ^(2f) Q_p	-	108.
3. <u>Power-Output</u>		
3.1. Plasma fusion power, $P_F = P_N + P_\alpha$	MWt	2732.5
3.1.1. 14.1-MeV neutron power, P_N	MWt	2186.0
3.1.2. 3.5-MeV alpha-particle power, P_α	MWt	546.5
3.2. Reactor thermal power	MWt	3364.9
3.2.1. Power to first wall	MWt	626.0
3.2.2. Power to limiter	MWt	440.8
3.2.3. Power from blanket ($M_N \approx 1.28$)	MWt	2057.6
3.2.4. Power to shield	MWt	143.3
3.3. Blanket power amplification factor, M_N	-	1.28
3.4. Plasma chamber power density (total cycle time average) ^(3a)	MT/m ³	64.8
3.5. Plasma power density ^(3b)	MWt/m ³	72.5
3.6. Engineering power density ^(3c)	MWt/m ³	11.8
3.7. Blanket power density ^(3d)	MWt/m ³	30.6
3.8. Total thermal power to conversion cycle, ^(3e) P_{TH}	MWt	3364.9
3.9. Plant gross electrical output, P_{ET}	MWe	1226.7
3.10. Plant net electrical output, P_E	MWe	1000.
3.11. Thermal cycle efficiency, η_{TH}	-	0.365
3.12. Net plant efficiency, $\eta_p = \eta_{TH}(1-\epsilon)$	-	0.297
3.13. Recirculating power fraction, ϵ ^(3f)	-	0.185
4. <u>Reactor Coolant System</u>		
4.1. Blanket coolant	-	Pb ₈₃ Li ₁₇
4.2. Blanket outlet temperature (hot leg)	K	773

4.3. Blanket inlet temperature (cold leg)	K	623
4.4. Blanket outlet pressure	MPa	~0.0
4.5. Blanket inlet pressure	MPa	1.1
4.6. Blanket coolant flow rate (total)	kg/s	72,840
4.7. Blanket structural material ^(4a)	-	HT-9
4.8. First-wall coolant type	-	H ₂ O
4.9. First-wall outlet temperature	K	536.6
4.10. First-wall inlet temperature	K	463.
4.11. First-wall outlet pressure	MPa	15.2
4.12. First-wall inlet pressure	MPa	15.6
4.13. First-wall coolant flow rate (total)	kg/s	4898.8
4.14. Total number of blanket coolant loops	-	TBD
4.15. Type of blanket coolant circulator	-	TBD
4.16. Power input to each circulator ^(4b)	MWe	TBD
4.17. Peak temperature in case of loss-of-coolant-flow accident		
4.17.1. First wall	K	TBD
4.17.2. Blanket multiplier	K	TBD
4.17.3. Breeder	K	TBD
4.18. Thermal energy storage ^(4b)	J	not required
5. <u>Intermediate Coolant System</u>		TBD
6. <u>Steam Generation (SG) System</u>		TBD
6.1. Steam outlet temperature	K	TBD
6.2. Steam outlet pressure	MPa	TBD
6.3. Steam flow rate (total)	kg/s	TBD
6.4. Feedwater temperature	K	TBD
6.5. Number of steam generators (SG) per loop	-	TBD
6.6. Number of reactor sectors per SG	-	TBD
6.7. SG materials, shell/tube	-	TBD
7. <u>Shield Coolant System</u>		
7.1. Total power deposited in the shield	MWt	143.3
7.2. Shield coolant type	-	H ₂ O
7.3. Shield outlet temperature	K	463
7.4. Shield inlet temperature	K	597
7.5. Coolant outlet pressure	MPa	15.2
7.6. Coolant inlet pressure	MPa	15.2

7.7. Coolant flow rate (total)	kg/s	272.2
8. <u>Reactor Auxiliary System</u>		
8.1. Vacuum pumping system		
8.1.1. Plasma chamber pressure	Pa	2.0
8.1.2. Plasma chamber volume	m ³	42.2
8.1.3. Total vacuum volume ^(8a)	m ³	60.6
8.1.4. Number of vacuum pumps ^(8b)	-	TBD
8.1.5. Regeneration interval	h	TBD
8.1.6. Helium-pumping speed (per pump)	m ³ /s	TBD
8.2. Magnet cooling system (chilled H ₂ O)		
8.2.1. TFC cooling load ^(8c)	MWt	42.6
8.2.2. PFC cooling load ^(8d)	MWt	141.0
8.3. Plasma-heating-system cooling load ^(3f,8d)	MWt	73.0
8.4. Plasma-fueling system		
8.4.1. Type ^(8e)	-	DT Pellet
8.4.2. Fuel composition	-	50% D, 50% T
8.4.3. Fueling rates	g/s(D)	0.11
	g/s(T)	0.17
8.4.4. Pellet diameter	mm	4.22
8.4.5. Pellet injection frequency	s ⁻¹	~ 28
8.5. Tritium-processing and recovery system		
8.5.1. Total tritium inventory	kg	TBD
8.5.2. Vulnerable tritium inventory	kg	TBD
8.6. Impurity control system		
	Pumped limiter	
8.6.1. Limiter coolant type	-	H ₂ O
8.6.2. Limiter outlet temperature	K	545
8.6.3. Limiter inlet temperature	K	463
8.6.4. Limiter outlet pressure	MPa	15.2
8.6.5. Limiter inlet pressure	MPa	15.4
8.6.6. Limiter coolant flow rate	kg/s	1311.2
9. <u>Reactor Components</u>		
9.1. First wall/blanket		
9.1.1. Structural material (first-wall/blanket) -		MZC-Copper/HT-9
9.1.2. Breeding material		Pb ₈₃ Li ₁₇ (60% ⁶ Li)
9.1.3. Neutron multiplier material	-	Pb
9.1.4. Breeding ratio ^(9a)	-	1.11

9.1.5.	Number of modules ^(9b)	-	1
9.1.6.	Weight of modules ^(9b)	tonnes	307
9.1.7.	Weight of largest single component	tonnes	307
9.1.8.	Dimensions of largest component ^(9c)	m	torus, 3.8-m × 1.5-m
9.1.9.	First-wall power loading		
9.1.9.1.	14.1-MeV neutron current	MW/m ²	19.5
9.1.9.2.	Energetic alpha-particle flux	MW/m ²	0.0
9.1.9.3.	Radiation, charge-exchange, and conduction power to first wall	MW/m ²	5.0
9.1.9.4.	Radiation, charge-exchange, and conduction/convection power to limiter	MW/m ²	6.0
9.1.9.5.	First-wall life	MWyr/m ²	15
9.2.	Shielding		
9.2.1.	Material		H ₂ O/W/B ₄ C/Fe
9.2.2.	Number of modules		1
9.2.3.	Weight of each module	tonnes	188.9 (included in 9.1.6.)
9.2.4.	Weight of largest single component	tonnes	188.9 (included in 9.1.6.)
9.2.5.	Dimensions of largest component	m	torus, 3.8-m × 1.43-m
9.3.	Magnets		
9.3.1.	Superconduction	-	no
9.3.2.	Conductor material (insulator)	-	Cu-alloy (MgO)
9.3.3.	Structural material	-	PCASS
9.3.4.	Operating temperature	K	300-350
9.3.5.	Coolant		H ₂ O
9.3.6.	Mean stress in coil ^(9d)	MPa	7-90
9.3.7.	Maximum force transmitted to building ^(9e)	MN	2.7
9.3.8.	Maximum field ^(9f)	T	4.5
9.3.9.	Field on plasma axis ^(9g)	T	9.5(toroidal)

9.3.10. Field at plasma surface	T	5.18(poloidal)
9.3.11. Number of magnets		
9.3.11.1. Toroidal-field coils	-	24
9.3.11.2. Equilibrium-field coils	-	12
9.3.11.3. Ohmic-heating coils	-	20
9.3.12. Mean coil radius	m	3.31
9.3.12.1. Toroidal-field coil	m	1.46
9.3.12.2. Poloidal-field coil	m	3.80
9.3.13. Total stored energy (full torus)	GJ	1.72
9.3.13.1. Toroidal-field coil	GJ	0.02
9.3.13.2. Poloidal-field coil	GJ	1.7
9.3.14. Weight of largest single component ^(9h)	tonnes	200
9.3.15. Dimension of largest single component	m	torus, 4.8-m x1.0-m
9.4. Energy transfer and storage ⁽⁹ⁱ⁾		Not required
9.5. Plasma heating		
9.5.1. Type	-	Ohmic
9.5.2. Frequency	GHz	NA
9.5.3. Power to the plasma	MW	25.3
9.5.4. Transmission method	-	Induction
9.5.5. Power reflected from plasma	MW	0.0
9.5.6. Power loss in transmission	MW	73.0
9.5.7. Power loss in amplifiers	MW	NA
9.5.8. Power loss in power supplies	MW	TBD
9.5.9. System input power	MW	~100
9.5.10. Heating time	s	8-10
9.5.11. Number of waveguide grills	-	NA
9.5.12. Number of amplifiers	-	NA
10. <u>Electrical Power Requirements</u>		
10.1. Cold-plasma start-up power from grid	MWe/s	300/8
10.2. Auxiliary power requirements ^(10a) (normal operation)	MWe	62.6
10.2.1. Electrical energy storage	MWe	none required

10.2.2.	Magnet power supply (other than ohmic losses) ^(10b)	MWe	0.0
10.2.3.	First-wall circulators ^(10c)	MWe	1.85
10.2.4.	Limiter-coolant circulators ^(10c)	MWe	0.94
10.2.5.	Blanket circulators ^(10b)	MWe	13.2
10.2.6.	Shield-coolant circulators ^(10c)	MWe	0.0
10.2.7.	Refrigeration system	MWe	NA
10.2.8.	Vacuum system (roughing)	MWe	TBD
10.2.9.	Miscellaneous reactor plant auxiliaries ^(10c)	MWe	TBD
10.2.10.	Feedwater pump system	MWe	TBD
10.2.11.	Condensing system	MWe	TBD
10.2.12.	Heat rejection system	MWe	TBD
10.2.13.	Miscellaneous BOP auxiliaries	MWe	TBD
11. <u>Buildings</u>			
11.1. Reactor Building			
11.1.1.	Characteristic dimensions	m	TBD
11.1.2.	Enclosed volume		
11.1.2.1.	Free volume ^(11a)	m ³	TBD
11.1.2.2.	Total volume	m ³	TBD
11.1.3.	Minimum wall thickness for shielding	m	TBD
11.1.4.	Internal pressure normal/accident ^(11b)	MPa	TBD
11.1.5.	Containment atmosphere	-	TBD
11.2. Turbine Building			
11.2.1.	Characteristic dimensions	m	TBD
11.2.2.	Enclosed volume	m ³	TBD
11.3. Reactor Service Building			
11.3.1.	Characteristic dimensions	m	TBD
11.3.2.	Special functions (i.e., hot cells, blanket processing equipment, etc.)	Tritium handling, radwaste, hot cells, maintenance and storage	
12. <u>Reactor Maintenance</u>			
12.1. First-wall/blanket/shield			
12.1.1.	Annual percentage	% area/yr	100

12.1.2. Area	m ² /yr	112
12.1.3. Weight ^(12a)	tonnes/yr	45.2
12.2. Radioactive material storage for life of plant (30 yr)		
12.2.1. Total long-term storage ^(12b)	m ³ /tonnes ^(12b)	270/1356(65% compression) 2400/7356(concrete fill)
12.2.2. Remaining recycled blanket storage	m ³ /tonnes	TBD
12.2.3. Total recycled reactor equipment ^(12c) (after plant decommissioning)	m ³ /tonnes	TBD
12.3. Reactor availability		TBD
12.4. Overall plant availability ^(12d)		0.75

Footnotes for Reactor Design Table

1. Characteristic Machine Dimensions

- (a) The reactor envelope encloses the poloidal-field coils and has the dimensions given with a circumference (length) of 23.9 m (at the major toroidal radius of 3.8 m).
- (b) Sectors are used only for off-site assembly of FW/B/S/C, with full torus being installed as a single unit into reactor cavity.

2. Plasma Parameters

- (a) Includes average alpha-particle pressure, total beta is 0.12.
- (b) Based on $T(r) \propto J_o(\mu r)$ profiles and BFM pressure profiles.
- (c) Thermalized Maxwellian component has been subtracted.
- (d) Based only on steady-state alpha-particle density,
 $Z_{eff} = (1 + 4f_\alpha)/(1 + 2 f_\alpha) f_\alpha = n_\alpha/n_i = 0.029$.
- (e) At steady state, 200-300-MWe grid power required during bipolar startup.
- (f) Based on ratio of fusion power to ohmic dissipation in plasma, inclusion of ohmic power dissipated in TFCs and PFCs gives a Q-value of 16.62.

3. Power Output

- (a) Based on fusion power (2732.5 MWt) divided by vacuum chamber volume (42.2 m³).
- (b) Based on fusion power (2732.5 MWt) divided by plasma volume (37.7 m³).

- (c) Based on total thermal power (3364.9 MWt) and net volume (285 m³) enclosed by and including magnets.
- (d) Based on first-wall, blanket and shield volume (110 m³) and thermal power actually delivered to primary coolant (3364.9 MWt). Peak value of blanket power density is 255 MWt/m³ and actual average for the blanket is 26.9 MWt/m³.
- (e) Does not include primary-coolant pumping power.
- (f) Includes 73 MW delivered to OHCs, which under steady-state operation could be reduced to zero.

4. Reactor Coolant System

- (a) HT-9 is a ferritic steel (85.0 Fe/11.5 Cr/1.0 Mo/0.55 Mn/0.5 Ni/0.5 W/0.4 Si/0.3 V/0.2 C).
- (b) Energy stored in the ~ 800-tonne PbLi coolant contained within the FPC amounts to 65 GJ over the temperature range from room temperature to 773 K, when ratio to the total thermal output gives ~ 20 s.

7. Shield Coolant System

- (a) Thin (0.10-m) shield operates at first-wall/shield conditions and contributes to overall reactor power cycle.

8. Reactor Auxiliary System

- (a) Vacuum volumes within the FPC include 4.5 m³ for the 24 radial slots, 10.7 m³ for the vacuum plenum, and 1.7 m³ for 24 ducts out to outer edge of FPCs.
- (b) Design choice between separate cryogenic pumps at each of 24 ducts (one per sector) or the use of a "vacuum room" remains to be made.
- (c) Of this total, 30.0 MW is nuclear heating and 12.6 is ohmic heating.
- (d) Of this total, 14.5 MW is nuclear heating, 126.5 is ohmic heating, of which 73.0 MW appears in the OHCs and 53.5 MW appears in the EFCs.
- (e) Pellet speed = 1.4 km/s with ratio of pellet inventory to plasma inventory equal to 0.05.

9. Reactor Components

- (a) Theoretical one-dimensional breeding ratio; does not include losses, decay, first-wall area reduction.
- (b) The first-wall/blanket/TFC forms a single, integral unit; weight does not include the ~ 800 tonne coolant.
- (c) When toroidal in shape, the dimensions indicate effective major and minor radii, respectively.

- (d) Lower value at PFC #12 (upper, inboard) and higher value at PFC #6 (equatorial plane, inboard); compares to 550 MPa (TFC) and 14 MPa (PFC) for STARFIRE and 127 MPa (TFC/ARE) for EBTR.
 - (e) Centering force for TFC.
 - (f) Maximum field at inboard side of PFC.
 - (g) Toroidal field at plasma edge is -0.40 T and increases to -0.72 T at the TFC.
 - (h) Total mass of PFC is 798 tonne, with EFC being 404 tonne and the OHC being 394 tonne. Each EFC and OHC set would in turn be divided into two segments for maintenance purposes.
 - (i) If a grid-assisted startup proves unfeasible, a transferred energy store of ~ 2 GJ will be required.
10. Electrical Power Requirements
- (a) Taken nominally as $f_{\text{AUX}} = 0.05$ of the gross electrical power, $P_{\text{ET}} = 1226.7$ MWe
 - (b) Refer to item 10.3.
 - (c) Based on 75 % pump efficiency.
11. Buildings
- (a) Includes volume of reactor hall and primary-coolant component room; value used to calculate overpressure in event of coolant line rupture.
 - (b) Normal operating pressure is slightly less than atmospheric, as in the present-day nuclear power plants. The accident condition is assumed to be the loss of primary coolant into the containment building.
12. Reactor Maintenance
- (a) Based on replacing entire first wall and blanket each year of operation, and recycling the shield (188.9 tonne) and TFCs (72.8 tonne).
 - (b) Includes first-wall, blanket, and limiter components.
 - (c) Includes blanket and first wall, all shielding, coils, primary structure and support, limiters, and vacuum cryopumps (if used), but excludes long-term storage in Item 12.2.1.
 - (d) Based on 60 day/year unscheduled maintenance and 28 d/FPC replacement, this algorithm being sensitive to fusion neutron wall loading and giving an optimal wall loading based on COE.

REFERENCE

1. C. R. Head, "Standard Fusion Reactor Design Study Contents," Department of Energy, Office of Fusion Energy letter RS&A:CRH:#478 (March 7, 1979).

Appendix C. Two-Dimensional Neutronics Analyses

C.1. Introduction

Estimates of the nucleonics performance of the first wall, blanket, and shield (FW/B/S) design presented in this report were based on analyses of the results of a one-dimensional neutronics model and parametrics study leading to the "canonical" model described in Sec. III.B. That parameter survey varied the thickness of the blanket and shield as well as the composition of primary materials: PCASS (structure), H_2O (FW/limiter/shield coolant), B_4C/W (shield), and $Pb_{83}Li_{17}$ (enriched to 60 % in 6Li , blanket breeder and coolant). The calculations were performed using the one-dimensional, discrete-ordinates code ONEDANT¹ and a 30-neutron/12-gamma-ray group library based on ENDF/B-IV data.²

The one-dimensional aspects of the FW/B/S design are for the most part well represented by the canonical model. Inclusion of the limiter, the vacuum ducts, and the manifolds and headers cooling the limiter, first wall, and second wall, however, give significant two-dimensional characteristics to the FW/B/S model. A two-dimensional neutronics analysis, therefore, was performed to assess the effects on the blanket performance predicted by the one-dimensional model. In addition, the effects of using ENDF/B-V cross sections³ and other changes in the FW/B/S materials (e.g., HT-9 ferritic steel was substituted for PCASS, improved shielding materials) could also be assessed.

Of particular interest to this postdesign neutronics analysis is the tritium-breeding ratio (TBR). The one-dimensional calculation for the canonical FW/B/S model predicted a value of 1.108 (Table III.B-V). Displacement of a portion of the $PbLi$ blanket by the manifold, headers, and vacuum ducts, particularly in regions near the first wall where the greatest contribution to tritium breeding occurs, however, is expected to degrade TBR seriously for the blanket design that evolved in Sec. L. In addition, a calculated TBR of ~ 1.10 is necessary to allow for calculation uncertainties in the tritium recovery efficiencies.⁴

After describing the two-dimensional neutronics model used in this postdesign assessment in Sec. C.2., the neutronics codes and cross sections are described in Sec. C.3. Section C.4 gives the parametric results for the referenced FW/B/S model and a range of design changes available to obtain adequate tritium breeding in the highly two-dimension model that has evolved through the process of integrating the FPC (Sec. L.). In the spirit of this framework study, design directions are indicated to reconcile the blanket

performance with the two-dimensional nature of this problem, only tritium breeding is computed, and more-detailed assessment of neutronic responses and design in two-dimensions must await future work.

C.2. Two-Dimensional Model

As illustrated in Fig. C-1, the CRFPR torus is composed of $N = 24$ sectors each forming a portion of the first-wall/second-wall, blanket, shield, and TFC. A half-sector, which is actually wedge shaped, was taken as the unit cell and modeled as a finite cylinder. Because this unit cell is for the most part poloidally symmetric about the plasma minor axis and toroidally symmetric about the module center plane, the origin for the coordinate system was taken at the intersection of this plane and the plasma centerline. The length of the cylindrical unit cell was taken as one-half the length of the plasma minor axis through the sector. The FW/B/S minor radii were specified at the actual design values (Fig. III.B-5). The outer radius of the calculational unit cell was taken as 1.75 m, this value being arbitrarily selected to yield a 0.25-m thickness for the region representing the PFCs. This region is approximately 40 % coil and 60 % void, and the 0.25-m thickness corresponds to a few neutron mean-free-paths, giving a reasonable cutoff for the purposes of this calculation.

The two-dimensional model is depicted in Fig. C-2. Details of the geometry for the limiter, the first wall/second wall (FW/SW), and the associated manifold region are shown in Fig. C-3. The modeling of this crucial region was simplified by homogenizing the manifold regions for both the limiter and the FW/SW into zones composed of structure (HT-9), coolant (H_2O), and void. This homogeneous modeling is also shown in Fig. C-3. The volume fractions for the various materials that compose the regions in Fig. C-2 are given in Table C-I.

C.3. Neutronics Calculations

a. Codes. The neutronics calculations were performed with a combination of computer codes: the two-dimensional, discrete-ordinates codes TRIDENT-CTR,⁵ TWODANT;⁶ the Monte Carlo code MCNP;⁷ and the one-dimensional, discrete-ordinates code ONEDANT.¹ This combination of codes was needed both to benchmark the various calculations against each other and to utilize the particular assets of each (i.e., spatial resolution versus running time).

The calculations using TRIDENT-CTR used the triangular mesh capabilities, which allowed detailed modeling of the geometry. In addition, the disk storage system used in TRIDENT-CTR allowed a much larger problem [i.e., finer mesh,

Fig. C-1. Detailed isometric view of FW/B/S/TFC torus and one of 24 sectors arranged to form the CRFPR torus. The calculation unit cell for the two-dimensional neutronics models takes one-half of this sector in cylindrical geometry. Poloidal-field coils are not shown.

Fig. C-2. Calculation unit cell for two-dimensional CRFPR FW/B/S/C model to reflect in cylindrical geometry the effects of limiter and FW/SW manifolding as well as vacuum ducting.

Fig. C-3. Detailed view of limiter, FW/SW, and associated H₂O coolant manifolds (re: Fig. III.L-17) as well as homogenized version for use in two-dimensional neutronics models (TRIDENT-CTR and MNCP).

TABLE C-I
VOLUME FRACTIONS OF MATERIALS
USED IN TWO-DIMENSION NEUTRONICS MODEL

<u>Region</u>	<u>Materials</u>	<u>Volume Fractions</u> ^(a)
Limiter	Cu	1.0
Limiter manifold	HT-9/H ₂ O	0.3564/0.5334
First wall (with coolant)	Cu/H ₂ O	0.5890/0.1654
First wall (FW)	Cu	1.0
Second wall (SW)	HT-9/H ₂ O	0.6400/0.3034
FW/SW coolant manifold	HT-9/H ₂ O	0.2364/0.5085
Blanket	PbLi	1.0
Blanket structure	HT-9	1.0
Shield Layer A	W/PCASS/H ₂ O	0.8/0.1/0.079
Shield Layer B	B ₄ C/PCASS/H ₂ O	0.8/0.1/0.079
TFC	Cu/PCASS/MgO/H ₂ O	0.7/0.1/0.1/0.0986
PFC	Cu/PCASS/MgO/H ₂ O	0.2815/0.0402/0.0402/0.0397

^(a) Adjusted for H₂O density.

higher-order scattering (P_3), and coupled neutron and gamma rays] than was possible for TWODANT. The restart capabilities of the longer-running TRIDENT-CTR also allowed the converged fluxes from one case to be used as initial values for subsequent calibrations, thereby decreasing the computing time required to converge a new problem.

Although TWODANT calculations were limited to a coarse-mesh, P_1 -scattering approximation and a number of neutron energy groups established by core storage, this code runs considerably faster than TRIDENT-CTR, allowing a larger number of two-dimensional parametric calculations to be made. Calculations were made only for an integral quantity (tritium-breeding ratio) and no attempt was made to assess the accuracy of the spatial variation in the calculated reaction rates.

The use of MCNP allowed the assessment of self-shielding effects, as well as permitting a check on the cross sections and effects of secondary energy and angular distribution. The TWODANT and TRIDENT-CTR codes used the same multigroup cross-section library, while MCNP uses a detailed pointwise library. The geometry modeled in MCNP was exactly that used in TRIDENT-CTR (i.e., the

surface segments corresponded to the triangular mesh zones specified for TRIDENT-CTR).

b. Cross Sections. The source of the multigroup cross sections used in the TRIDENT-CTR, TWODANT, and ONEDANT calculations was the MATXS6 library⁸ that was generated from ENDF/B-V data³ with the code NJOY.⁹ The MATXS6 library is an 80/24 group, coupled neutron/gamma-ray set. This library was collapsed to a 30/12 group structure for the calculations performed herein. This approach also allowed a comparison to be made with the results for the canonical FW/B/S model described in Sec. III.B. as well as an assessment of the effects of the weighting spectrum used to collapse the cross-section set. Multigroup libraries were generated using the TRANSX code⁸ in which mixing of macromaterials (e.g., H₂O), was performed. The weighting spectrum for collapsed libraries was either input, or the MATXS6 "built-in" spectrum was used.

Calculations were performed with ONEDANT for the canonical FW/B/S model with the 80/24 group library to generate various spatially averaged group fluxes for use in TRANSX as weighting functions. The 80/24 group calculation yielded a TBR value of 1.075, which compares with 1.108 reported in Sec. III.B. using the 30/12 group library based on ENDF/B-IV data. This difference most probably results from the more-recent ⁷Li evaluation in ENDF/B-V. Group weighting functions were generated as the flux average over the entire blanket, over the first 0.10 m of blanket, and over the middle 0.10 m of the 0.50-m-thick canonical blanket. Collapsed 30/12 libraries were then created using these weights as well as the built-in spectrum. Calculations with ONEDANT were then made using each of these libraries. The results for the calculated TBR are summarized in Table C-II. Little difference exists between the TBR values obtained using the first 0.10 m of blanket and the entire blanket since the flux in the first 0.10 m of blanket dominates the blanket average. Based on this analysis, subsequent calculations used a library collapsed to 30/12 neutron/gamma-ray groups using the flux spectrum averaged over the entire canonical blanket.

c. Computational Specifications. The TRIDENT-CTR mesh used in the calculations is shown in Fig. C-4, with a more detailed view of the manifold/header region behind the limiter given in Fig. C-5. A total of 1521 triangles are included in the mesh depicted on Fig. C-4. The calculations used S₈P₃ approximations and the 30/12 neutron/gamma-ray group structure described previously. An isotropic 14.1-MeV neutron source was distributed throughout the

TABLE C-II

COMPARISON OF RESULTS OF CROSS SECTION
COLLAPSING ANALYSIS USING TRITIUM-BREEDING RATIO AS A MEASURE

<u>Source</u>	<u>Collapsing Spectrum</u>	<u>Group Structure</u> (Neutron/Gamma)	<u>Calculated TBR</u>
XSLIBA ^(a)	Built-in(CLAW-IV)	30/12	1.108 ^(b)
MATXS6	-	80/24	1.074
MATXS6	Built-in	30/12	1.078
MATXS6	Total blanket average	30/12	1.071
MATXS6	First 0.10 m of blanket	30/12	1.071
MATXS6	Middle 0.10 m of blanket	30/12	1.056

^(a)Generated by G. L. Woodruff from ENDF/B-IV data.

^(b)Using canonical model and ONEDANT.

plasma volume. Initial TRIDENT-CTR calculations were converged within 10^{-4} , with later calculations being relaxed to 10^{-3} to conserve on computer time.

The 20×24 coarse-mesh boundaries used in the TWODANT calculations coincided with the region boundaries shown in Fig. C-2 with the exception of the FW/B region behind the limiter. The coarse-mesh geometry for this region is shown in Fig. C-6. Two fine-mesh intervals were specified for most coarse-mesh intervals with the exception of the broadest coarse-mesh intervals. In this case, up to five fine-mesh intervals were used. The TWODANT calculations were S_8P_1 approximations using only the 30 neutron energy groups. The neutron source was specified as in TRIDENT-CTR, and all calculations were converged to within 10^{-3} , again to conserve on computer time.

The MCNP calculations were performed in three-dimensional geometry using the identical two-dimensional model specified for TRIDENT-CTR. The tally used was a track length estimate of the flux in the regions containing PbLi multiplied by the ${}^6\text{Li}$ and ${}^7\text{Li}$ tritium-production cross sections. For this integral tally 10,000 source particles gave relative standard deviations less than 1.0 %. The ENDF/B-V cross sections were used.

C.4. Parametric Results

a. Reference (Canonical) FW/B/S Model. A base-case TRIDENT-CTR calculation for the reference model yielded a TBR of 0.785 compared to the value of 1.108 reported in Table III.B-V for the ONEDANT model and the "canonical" blanket. Subbreeding of this magnitude indicated that the blanket design or

Fig. C-4. TRIDENT-CTR finite-element mesh used to simulate two-dimensional geometry depicted on Fig. C-2.

Fig. C-5. Detail of TRIDENT-CTR finite-element mesh used to simulate the two-dimensional limiter, FW/SW, and manifold geometry depicted on Fig. C-4.

materials or both would need to be changed. The TRIDENT-CTR calculation of the Sec. III.B. canonical blanket was used as a benchmark for a TWODANT calculation which gave a TBR of 0.786. A similar MCNP calculation was performed to provide an additional benchmark and gave a value of 0.778 ± 0.006 . The fact that the discrete-ordinates and Monte Carlo results are the same, within statistics, gives credibility to the TRIDENT-CTR and TWODANT results for this system. Based on these calculations an interim reference TBR of 0.78 was selected to demonstrate the dramatic effects of more realistic two-dimensional designs on this crucial parameter. The intent of the present study is to indicate means by which TBR can be increased above unity while (ideally) maintaining the essential elements of the FPC design evolved in Sec. III.L.

The effects of various design and material changes were subsequently examined with a series of TWODANT calculations. Selected TWODANT calculations were benchmarked with a TRIDENT-CTR calculation. The time investment for the longer-running calculations was minimized by restarting the code with the specified changes using the converged fluxes for the reference model.

The effect of thickening the blanket was examined by replacing the 50-mm-thick vacuum region behind the blanket with PbLi. The ONEDANT calculations described in Sec. III.B.2.b. examined the effects of first-wall thickness on TBR and indicated that a substantial enhancement would result by thinning the copper first wall (Table III.B-X and Fig. III.B-7). Based on this assessment, TWODANT and TRIDENT-CTR calculations were performed for the reference 20-mm-thick first wall decreased to 3.0 mm (2.0-mm-thick copper and water region followed by 1.0-mm-thick copper). The effects of relocating the FW/SW coolant manifold was estimated by shifting the homogenized material representing this manifold to the rear of the blanket, locating it in the shield region. The region previously occupied by the manifold was then replaced by PbLi, while conserving the volume of the regions. The shift of these manifold regions is depicted in Fig. C-7. In addition, the effects of using D_2O as a FW/SW and limiter coolant and increasing the 6Li enrichment from 60 % to 80 % were investigated for the canonical FW/B/S (Fig. C-2). The values for the TBR calculated by TRIDENT-CTR and TWODANT for these design and material variations on the reference model are summarized in Table C-III.

With the exception of adding 50 mm of blanket, all of the design and material variations summarized on Table C-III yielded substantial improvement in the TBR. Only relocation of the FW/SW coolant manifold (Fig. C-7) or changing

Fig. C-7. Two-dimensional FW/B/S model showing the shift of the near-first-wall coolant manifold (location A) to the rear of the blanket (location B).

to D₂O coolant for the FW/SW and limiter give TBR greater than unity, however. Both of these options were considered less desirable when compared with the more simple design modifications associated with thinning the first wall and using higher ⁶Li enrichments. Specifically, use of D₂O coolant complicates the thermal cycle and is expected to add cost, whereas placement of the high-pressure FW/SW coolant manifolds in the shield region requires the use of tube sheets to deliver coolant to the FW/SW region, substantially increasing the number of individual tubes. Both design changes remain as possibilities but are ranked as less desirable relative to other choices.

In each case where the first wall was thinned, an increase of about 14 % in the TBR was calculated. It was decided, therefore, to perform a further parametric analysis for a modified reference model which included a thinner first wall.

b. Modified Reference (Canonical) FW/B/S Model. The 5-mm-thick first wall was adopted for the modified reference model; the first wall is modeled as a region of 4-mm-thick copper and water following by a region of 1-mm-thick copper. The copper and water region adjacent to the plasma is consistent with the design for this portion of the first-wall presented in Fig III.D-3, but with a thinner bulk-copper region being used. Although this wall is thicker than that considered in the previous section, the copper volume fraction in the front region is lower, and the performance for the 5-mm-thick first wall is close to that calculated previously for the 3-mm-thick first wall.

The TRIDENT-CTR calculation for the modified reference model gave a TBR of 0.899, while a value of 0.892 was calculated by TWODANT. MCNP calculations were also performed for this model and yielded a TBR 0.870 ± 0.010 which agrees with the discrete-ordinates calculations. The calculations for both reference models are summarized in Table C-IV. A new interim reference TBR of 0.88 was selected for this modified reference model as compared with 0.78 for the base reference model.

Subsequent parametric calculations were performed with TWODANT and benchmarked with MCNP for selected calculations. To assess the self-shielding effects, a cross section library with self-shielded cross sections for Cu and HT-9 was generated with TRANSX. A TWODANT calculation was performed for the reference using this library. Since the pure HT-9 and Cu cross sections are homogenized with water in the TWODANT calculation, the self-shielding was overestimated, and the TBR calculated was 0.912. This calculation did indicate

TABLE C-III

TRITIUM-BREEDING RATIOS CALCULATED FOR DESIGN
AND MATERIAL VARIATIONS ON THE REFERENCE MODEL

Coolant	^6Li Enrichment (%)	Design Variation	TBR	
			TWODANT	TRIDENT-CTR
H ₂ O	60	Reference	0.786	0.785
H ₂ O	60	Added 50 mm to PbLi blanket	0.818	-
H ₂ O	60	Relocated manifold to rear of blanket	1.033	-
H ₂ O	60	Reduce first-wall thickness from 20 mm to 3 mm	0.898	0.901
H ₂ O	80	Reference	0.842	-
H ₂ O	80	Reduce first-wall thickness from 20 mm to 3 mm	0.955	0.959
D ₂ O	60	Reference	0.989	-
D ₂ O	60	Reduce first-wall thickness from 20 mm to 3 mm	1.125	1.113

TABLE C-IV

CALCULATED TRITIUM-BREEDING RATIO
FOR BASE REFERENCE AND MODIFIED REFERENCE MODELS

	<u>BASE REFERENCE MODEL</u> (20-mm-thick copper)	<u>MODIFIED REFERENCE MODEL</u> (5-mm-thick copper)
TRIDENT-CTR	0.785	0.899
TWODANT	0.786	0.892
MCNP	0.778	0.870
Selected Interim Reference Value	0.78	0.88

that the TWODANT calculations for a specific case would probably yield slightly higher TBR values if self-shielded cross-section sets were used.

In order to assess the effects of ^6Li enrichment, TWODANT calculations were made for 80 % and 90 % ^6Li enrichments. In the case that a larger TBR margin might be required, calculations were performed with D_2O coolant as well as 60, 80, and 90 % ^6Li enrichments. The resulting TBRs are plotted in Fig. C-8. An approximate linear variation in the TBR with ^6Li enrichment for both H_2O and D_2O coolants is observed. The TBR approaches unity for H_2O coolant only for ^6Li enrichments approaching 100 %, whereas TBR values calculated for a D_2O coolant yield substantial margins. The $\text{H}_2\text{O}/90\%$ ^6Li case was also calculated with MCNP, which gave a TBR of 0.939 ± 0.005 . This latter case appeared attractive for further parametric analysis in search of further TBR improvement.

Fig. C-8. Dependence of tritium-breeding ratio on ^6Li enrichment in the modified reference FW/B/S, showing effects of replacing H_2O FW/SW and limiter coolant with D_2O .

The W/B₄C/H₂O shield positions behind the blanket in the reference FW/B/S model (Sec. III.B.) was designed to optimize the total blanket energy recovery efficiency. This 0.10-m-thick shield consists of alternating 25-mm-thick layers of 80 % tungsten and 80 % B₄C; each layer also contains 10 % PCASS structure and 7.9 % H₂O coolant. It appeared that a good reflector in this region could also enhance the TBR.

Calculations were performed with 90 % enriched ⁶Li in which all four shield layers were a) taken as the W/PCASS/H₂O mixture as described above; b) replaced with pure tungsten; or c) replaced with 90 % PCASS and 10 % H₂O. The TBRs calculated using TWODANT for these three cases are 0.979, 0.992, and 1.006, respectively. The results for the PCASS reflector prompted a MCNP calculation; a TBR value of 0.978 ± 0.009 resulted. These results indicate that even high-enrichment, well-reflected blanket designs do not provide the TBR margins required.

In order to investigate the possibility of providing a TBR margin with a slightly thicker blanket, TWODANT calculations were performed for the 90 % enriched, PCASS-reflected model with 50 mm and 100 mm of additional PbLi in the blanket region. All radii behind the blanket were correspondingly increased. These calculations yielded TBR values of 1.033 and 1.058, respectively, and are plotted in Fig. C-9. An almost linear increase in the TBR with increased blanket thickness is observed, indicating a design option for achieving the desired TBR margin. The latter case was also calculated with MCNP giving a TBR of 1.035 ± 0.008 which is consistent with previous results.

C.5. Conclusions and Recommendations.

The effects of more-detailed two-dimensional effects on the breeding potential of the canonical, one-dimensional neutronics model used throughout this framework study can be significant. A range of relatively minor FW/B/S material and design changes have been examined as means to increase the TBR above unity using fully two-dimensional models. These changes include

- increase blanket thickness
- decrease first-wall thickness
- relocate FW/SW water coolant manifold to rear of blanket
- increase ⁶Li enrichment in the self-cooled PbLi blanket
- replace H₂O with D₂O in the FW/SW and limiter coolant loops

Fig. C-9. Dependence of tritium-breeding ratio on blanket thickness for the modified reference blanket with a PCASS/H₂O shield/reflector.

- emphasize reflecting role over shield role of thin shield/reflector placed between the blanket and TFC.

It appears that for a thinner copper first wall and high ⁶Li enrichments (~ 90 %), adequate tritium-breeding ratios could be achieved with the proper selection of reflector and a small addition to the blanket thickness. These changes preserve the FPC design suggested in Sec. III.L. and are considered minor. An alternative approach would relocate the FW/SW coolant manifold to the rear of the blanket. This option should provide large TBR margins and allow ⁶Li enrichments below 90 % should this present a cost issue. If further design modifications are anticipated which would have a strong negative impact on the TBR (i.e., increased FW or limiter thickness, increased FW/SW or limiter manifold size at the first-wall location, reduced ⁶Li enrichment, etc.), changing the FW/SW and limiter coolant from H₂O to D₂O presents an option with substantial TBR margins. Finally, if a thicker copper first wall should be required, an attractive combination of the above alternatives could be selected which would yield an adequate margin for the tritium-breeding ratio.

REFERENCES

1. R. D. O'Dell, Forrest W. Brinkley, Jr., and Duane R. Marr, "User's Manual for ONEDANT: A Code Package for One-Dimensional Diffusion-Accelerated Neutral-Particle Transport," Los Alamos National Laboratory report LA-9184-M (February 1982.)
2. D. Garber (Ed.), "ENDF/B Summary Documentation," Brookhaven National Laboratory report BNL-NCS-17541 (ENDF-201), 2d Ed. (ENDF/B-IV), National Neutron Cross Section Center, Brookhaven National Laboratory, Upton, NY (October 1975).
3. R. Kinsey (Ed.), "ENDF/B Summary Documentation," Brookhaven National Laboratory report BNL-NCS-17541 (ENDF-201), 3rd Ed. (ENDF/B-V), National Nuclear Data Center, Brookhaven National Laboratory, Upton, NY (July 1979).
4. J. Jung and M. Abdou, "Assessments of Tritium Breeding Requirements and Breeding Potential for the STARFIRE/DEMO Design," Nucl. Technol./Fusion 4, 361 (1983).
5. Thomas J. Seed, "TRIDENT-CTR User's Manual," Los Alamos Scientific Laboratory report LA-7835-M (May 1979).
6. Ray E. Alcouffe, Forrest W. Brinkley, Duane R. Marr, and R. Douglas O'Dell, "User's Guide for TWODANT: A Code Package for Two-Dimensional, Diffusion-Accelerated, Neutral Particle Transport," Los Alamos National Laboratory report LA-10049-M (March 1984).
7. Los Alamos Monte Carlo Group, "MCNP - a General Monte Carlo Code for Neutron and Photon Transport," Los Alamos National Laboratory report LA-7396-M, Revised (April 1981)
8. R. J. Barrett and R. E. MacFarlane, "The MATXS-TRANSX system and the CLAW-IV Nuclear Data Library," National Bureau of Standards Special Publication 594 (September 1980).
9. R. E. MacFarlane, D. W. Muir, and R. M. Boicourt, "The NJOY Nuclear Data Processing System, Volumes I and II," Los Alamos National Laboratory report LA-9303-M, Vols. I and II (ENDF-324) (May 1982).