MASTER

RLO-2227-T22- 10

DOE/ET/90476-10

THE COMBUSTION CHARACTERISTICS OF
RED ALDER BARK

TECHNICAL PROGRESS REPORT NO. 6

DAVID C. JUNGE, PH.D.
OREGON STATE UNIVERSITY
CORVALLIS, OREGON 97331

PERIOD: SEPTEMBER 16, 1977 TO
SEPTEMBER 15, 1978

DATE OF REPORT: DECEMBER 1978

PREPARED FOR THE U.S. DEPARTMENT OF ENERGY: CONTRACT EY-76-C-06-2227
TASK AGREEMENT NO. 22

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency Thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DISCLAIMER

Portions of this document may be illegible in electronic image products. Images are produced from the best available original document.

THE COMBUSTION CHARACTERISTICS OF
RED ALDER BARK

TECHNICAL PROGRESS REPORT NO. 6

DAVID C. JUNGE, PH.D.
OREGON STATE UNIVERSITY
CORVALLIS, OREGON 97331

PERIOD: SEPTEMBER 16, 1977 TO
SEPTEMBER 15, 1978

DATE OF REPORT: DECEMBER 1978

PREPARED FOR THE U.S. DEPARTMENT OF ENERGY: CONTRACT EY-76-C-06-2227
TASK AGREEMENT NO. 22

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

DISCLAIMER

THIS REPORT WAS PREPARED AS AN ACCOUNT OF WORK SPONSORED BY THE UNITED STATES GOVERNMENT. NEITHER THE UNITED STATES NOR THE UNITED STATES DEPARTMENT OF ENERGY, NOR ANY OF THEIR EMPLOYEES, MAKES ANY WARRANTY, EXPRESS OR IMPLIED, OR ASSUMES ANY LEGAL LIABILITY OR RESPONSIBILITY FOR THE ACCURACY, COMPLETENESS OR USEFULNESS OF ANY INFORMATION, APPARATUS, PRODUCT, OR PROCESS DISCLOSED, OR REPRESENTS THAT ITS USE WOULD NOT INFRINGE PRIVATELY OWNED RIGHTS.

COPYRIGHT NOTICE

BY ACCEPTANCE OF THIS REPORT, THE PUBLISHER AND/OR RECIPIENT ACKNOWLEDGES THE U. S. GOVERNMENT'S RIGHT TO RETAIN A NONEXCLUSIVE, ROYALTY-FREE LICENSE IN AND TO ANY COPYRIGHT COVERING THIS REPORT.

TABLE OF CONTENTS

SECTION	DESCRIPTION	PAGE
1.	INTRODUCTION	1
2.	PURPOSE AND SCOPE OF THE PROJECT	2
3.	FINANCIAL SUPPORT	3
4.	PROJECT PARTICIPANTS	3
5.	TIME FRAMEWORK OF THE PROJECT	4
6.	DESCRIPTION OF THE TEST FACILITY	4
7.	DESCRIPTION OF THE INSTRUMENTATION	8
8.	DESIGN OF THE EXPERIMENTS	12
9.	DATA COLLECTED	13
10.	PROCEDURE FOR THE CONDUCT OF THE EXPERIMENTAL TESTS	14
11.	DATA ANALYSES	15
12.	EXPERIMENTAL RESULTS	17
13.	CONCLUSIONS	17
	EXPERIMENTAL DATA SUMMARY SHEETS	20
	GRAPHS OF COLLECTED DATA	38
	FUEL ANALYSIS DATA AND GRAPHS	68
	ASH ANALYSIS DATA AND GRAPHS	77
	COMBUSTIBLE CONTENT VS. SIZE OF ASH	171

LIST OF FIGURES

FIGURE NO.	DESCRIPTION	PAGE
1.	Wood Combustion Test Facility - Oregon State University	6
2.	Photograph of the Experimental Test Facility	7
3.	Schematic Illustration of the Instrumentation Used With the Combustion Test Facility	11
 <u>GRAPHS OF COLLECTED DATA</u>		
	Graphs of Carryover Rates (lbs/hr) vs. Levels of Excess Air	39
	Graphs of Carryover Rates (lbs/hr), Mean Particle Size (mm), and Percent Combustible Ash (%) vs. Lbs of Air/Lb of Fuel at the Grate	51
	Graphs of Carryover Rates (lbs/hr) vs. Lbs of Air/Lb of Fuel at the Grate for Specific Temperature Levels	52
	Graphs of Total Carryover (Lbs of Carryover/Lb of Fuel) vs. Lbs of Air/Lb of Fuel at the Grate	55
	Graphs of Combustible Carryover (Lbs of Combustible Ash/Lb of Fuel) vs. Lbs of Air/Lb of Fuel at the Grate	57
	Graphs of Carryover (Lbs of Inorganic Ash/Lb of Fuel) vs. Lbs of Air/Lb of Fuel at the Grate	61
	Graphs of Carryover Rate (Lb/hr) vs. Levels of Excess Air:	
	Comparison of Effects of Air Distribution	63
	Comparison of Effects of Inlet Air Temperature	65
 <u>GRAPHS OF FUEL ANALYSIS DATA</u>		
	Graphs of Fuel Size and Density Distributions	71
 <u>GRAPHS OF ASH ANALYSIS DATA</u>		
	Graphs of Ash Size Distribution and Density Distributions	109
 <u>GRAPHS OF COMBUSTIBLE CONTENT OF COLLECTED ASH SAMPLES</u>		
	Graphs of Combustible Content of Ash vs. Size of Ash	182

LIST OF TABLES

<u>DESCRIPTION</u>	<u>PAGE</u>
--------------------	-------------

TABLES OF COLLECTED DATA

Experimental Data Summary Sheets	21
----------------------------------	----

Computer Listing of Data For All Tests	25
--	----

FUEL ANALYSIS DATA TABLES

Calculation Tables for Fuel Combustible Content, Size and Density Analyses	69
--	----

ASH ANALYSIS DATA TABLES

Calculation Tables for Ash Combustible Content, Size, and Density Analyses	78
--	----

Calculation Tables for Ash Combustible Content vs. Size Distribution of Ash Samples	172
---	-----

ABSTRACT

Significant quantities of wood residue fuels are presently being used in industrial steam generating facilities. Recent studies indicate that substantial additional quantities of wood residue fuels are available for energy generation in the form of steam and/or electricity. A limited data base on the combustion characteristics of wood residue fuels has resulted in the installation and operation of inefficient combustion systems for these fuels.

This investigation of the combustion characteristics of wood residue fuels was undertaken to provide a data base which could be used to optimize the combustion of such fuels. Optimization of the combustion process in industrial boilers serves to improve combustion efficiency and to reduce air pollutant emissions generated in the combustion process.

This report presents data on the combustion characteristics of Red Alder bark.

The data were obtained in a pilot scale combustion test facility at Oregon State University. Other technical reports present data on the combustion characteristics of:

- Douglas Fir Bark
- Douglas Fir Planer Shavings
- Red Alder Sawdust

- Ponderosa Pine Bark
- Hemlock Bark
- Eastern White Pine Bark

An Executive Summary Report is also available which compares the combustion characteristics of the various fuel species.

SUMMARY AND CONCLUSIONS

The following conclusions are drawn based on the experiments conducted for this species of wood residue fuel used in industrial spreader-stoker boilers:

- 1) Optimum combustion conditions occur when an overall level of 50% excess air is used;
- 2) The combustion air should be distributed approximately 45% undergrate and 55% overfire to achieve minimum air pollutant emissions and maximum combustion efficiency. Care must be taken to avoid burning out the grates with this combustion mode;
- 3) The temperature of the combustion air has a significant effect on combustion efficiency and air pollutant emissions. As the temperature increases, pollutant emissions are reduced. Therefore, it is suggested that the highest possible temperature be used for combustion air to bring about most efficiency combustion and highest thermal efficiency;
- 4) The combustible content of the boiler emissions ranges from 0.65 to 51%. Under optimum combustion conditions, the average combustible content is 16.4% with a range from 4.5% to 46%. This represents roughly 1/2 of 1% of the total fuel input. The potential heat recovery from this ash is relatively small and probably does not warrant attempts to collect it. Further, the inorganic, non-combustible ash from the fuel is relatively high (3.1% of the total dry weight of the fuel under optimal firing conditions). Therefore, it is recommended that the total ash be used for landfill if at all possible. Reinjection should definitely be avoided.
- 5) The mass mean size of the ash typically ranges from 0.05 mm to 0.48 mm. Under optimum combustion conditions, the mass mean size ranges from 0.06 mm to 0.43 mm.

- 6) The mass mean density of the ash typically ranges from 0.14 to 0.53 g/cm³. Under optimum combustion conditions the mass mean density ranges from 0.14 to 0.40 g/cm³.
- 7) Careful control of combustion conditions can reduce pollutant emissions by approximately 50%.

1. INTRODUCTION

In the wood products industry, large quantities of wood residue are used for fuel, principally to generate process steam by direct combustion in boilers. In the United States there are approximately 1700 industrial wood fired boilers in operation.

With increasing fossil fuel costs there is added incentive to utilize wood residue fuels. However, present technology affecting the design and operation of wood fired boilers is limited. As a result, a large percentage of both new and older boiler facilities are experiencing difficulty in operating efficiently and in meeting the environmental restrictions.

The technology "gap" focuses on the complete combustion of the wood fuel. It is desirable to completely burn all of the combustible components of the fuel in order to maximize the combustion efficiency and minimize the fuel requirements. Complete combustion will reduce emissions of air pollutant materials and reduce requirements for "tail end" control devices to meet stringent air pollution regulations.

There are specific questions pertinent to the design and operation of wood fired boilers which have not been satisfactorily answered. For example:

- 1) What is the optimum level of excess air (air to fuel ratio) to maximize the combustion process?
- 2) What is the influence of preheating combustion air on completion of the combustion process. (The effect of preheated air on thermal efficiency is well documented, but its effect on combustion efficiency is not documented).
- 3) What is the best method of distributing air in the combustion chamber?
- 4) What is the optimum size of wood fuel required to bring about complete combustion?
- 5) What is the influence of fuel moisture on the completion of the combustion reaction? (The effect of fuel moisture on thermal efficiency can be calculated but its effect on completion of

the combustion reaction has not been documented.)

- 6) What is the relationship of fuel feed rate to the completion of the combustion reaction?
- 7) For given combustion conditions, what is the rate of carryover of unburned fuel and inorganic ash out of the boiler and into the primary collector system? This questions pertains to the design requirements of primary collector systems.
- 8) What are the physical characteristics of wood fuel fly ash in terms of size distribution, density distribution, and combustible content for specific combustion conditions? This questions also pertains to the design requirements of primary collector systems.
- 9) What are the optimum combustion parameters for reducing opacity from the wood fired boiler exhaust gases?

The answers to these questions must take into account the design of the wood burning boilers system. There are four general design categories of boiler systems:

- 1) Spreader-stokers
- 2) Dutch ovens
- 3) Suspension burning systems
- 4) Fluidized bed combustion systems

Since the early 1950's, the majority of boilers constructed in this country have been of the spreader-stoker design. It is estimated that over 50% of the currently operating boilers are spreader-stokers. Therefore, the spreader-stoker design was emphasized in the research effort reported herein.

2. PURPOSE AND SCOPE OF THE PROJECT

The purpose of this research effort is to develop a design data base for the combustion of wood residue fuels. Each of the important variables in the combustion process is taken into consideration including the following:

- 1) Species of fuel
- 2) Size of fuel
- 3) Moisture content of fuel
- 4) Feed rate of fuel
- 5) Inlet air temperature
- 6) Air to fuel ratio - level of excess air
- 7) Distribution of the combustion air above and below the grate.

When the data base is complete it will allow engineers, designers, and boiler operators to more effectively utilize wood residue fuels for energy with improved combustion efficiency and reduced air pollutant emissions.

3. FINANCIAL SUPPORT

Support for this research effort has been provided principally by the Government of the United States as noted below:

1) Phases I & II	Energy Research and Development Administration: Division of Conservation Research and Technology.	\$100,000
2) Continuation	Department of Energy: Fossil Fuels Utilization Program	\$187,000
3) Oregon State University		\$ 7,350
4) International Paper Company		\$ 2,500
5) Oregon Department of Environmental Quality		\$ 2,000

4. PROJECT PARTICIPANTS

The principal investigator for the research effort is Dr. David C. Junge, Associate Professor of Mechanical Engineering (Senior Research Scientist). Dr. R. W. Boubel, F. Kayihan, J. G. Mingle have acted as supporting investigators. Dr. Kenneth Tuttle assisted during the period when he was a candidate for the degree of Doctor of Philosophy. Several undergraduate students have participated in the project as well as two full time technicians.

5. TIME FRAMEWORK OF THE PROJECT

The initial funding of the project began on April 1, 1976. The test facility was designed and constructed during the period of April 1, 1976 to January 31, 1977. Startup and debugging took place between February 1, 1977 and April 15, 1977. Initial data were collected on Douglas fir hogged bark from April 16, 1977 to June 30, 1977. Funding for the initial phases of the project concluded June 30, 1977.

The continuation work began September 16, 1977 with funding from the Dept. of Energy. Revisions to the test facility were accomplished between September 16, 1977 and December 31, 1977. Tests on a variety of species were conducted between January 1, 1978 and July 15, 1978. Funding for the continuation work is still in progress and is expected to continue through September 15, 1979.

The results reported in this document were obtained during the period January 1, 1978 to July 15, 1978.

6. DESCRIPTION OF THE TEST FACILITY

A test facility was designed and constructed to carry out this needed research program. It is located in Corvallis, Oregon at the Fairplay Research Center, a part of Oregon State University.

As indicated in Figure 1, the test facility is a small spreader stoker boiler designed to fire wood residue fuels (hogged fuel). The system includes:

- 1) A conveyor system to control and meter the fuel flow;
- 2) A mechanical "flinger" roll to distribute fuel uniformly across the grate;
- 3) A water wall lined combustion chamber with a fixed, pin-hole grate. The area of the grate is 10 square feet. The combustion zone extends approximately 11 feet above the grate. Steam is generated at atmospheric pressure with natural recirculation in the water walls;

- 4) A fin tube, forced air cooled, jacketed duct to carry combustion exhaust gases from the combustion zone to an air preheater;
- 5) A plate type, counter flow, tripple pass air preheater designed for up to 550 °F air exit;
- 6) A cyclone separator downstream from the air preheater to remove entrained particulate matter from the exhaust gas stream;
- 7) A forced draft fan to provide combustion air to the test facility;
- 8) A system of venturi orifice flow meters to measure the amount of air distributed above and below the grate;
- 9) A system of gate valves to control the flow of air above and below the grate
- 10) Instrumentation to measure independent and dependent variables of the test facility. (Instrumentation is discussed in greater detail in Section 7.)

A photograph of the test facility is shown in Figure 2. (P. 7)

The test facility is designed to combust fuel samples with heat release rates of up to 10×10^6 BTU's per hour. Typical tests are carried out with heat release rates of 6×10^6 BTU's per hour.

Fuel species, fuel size, and fuel moisture levels are not controlled by the test facility. These characteristics are determined with the purchase of the fuel from various suppliers.

SCHEMATIC ILLUSTRATION OF WOOD COMBUSTION TEST FACILITY

Figure 1: Wood Combustion Test Facility - Oregon State University

Figure 2: Photograph of the Experimental Test Facility - Oregon State University

7. DESCRIPTION OF THE INSTRUMENTATION

The instrumentation used in conjunction with the test facility is illustrated schematically in Figure 3. Specific comments are offered concerning particular aspects of the instruments:

- 1) Fuel Size Distribution: Fuel size was determined by a screen analysis on pre-dried fuel samples. Samples were placed in a laboratory oven at 106°C until their weight reached a constant level indicating uniform, oven dry moisture levels. The samples were then screened in a series of standard (Tyler) screens to determine the mass/size distribution.
- 2) Fuel Moisture Content: Moisture content was determined by collecting random samples of the fuel from the storage pile and conducting standard gravimetric analyses. Drying was carried out at 106°C until the samples reached constant weight.
- 3) Fuel Feed Rate: Feed rates were determined by calibrating the screw feed conveyor of the fuel feed system. Calibration was in terms of cubic feet of fuel delivered per hour for each specific fuel size and fuel moisture level. Calibration checks were made at regular intervals.

Note: This method of determining fuel feed rate proved to have limitations in accuracy. The desired information on fuel feed rate was in terms of dry pounds of fuel per hour. To obtain information in this form, it was necessary to determine the volumetric flow rate of the fuel (ft^3/hr), the moisture content of the fuel ($\# \text{H}_2\text{O} / \# \text{fuel}$), and the fuel density ($\# \text{fuel} / \text{ft}^3$). Each of these measurements had inherent inaccuracies. It was found that greater accuracy in determining the fuel flow rate was possible by accurately metering the combustion air and the level of excess air in the exhaust gas. Simple calculations could then be used to determine the fuel feed rate to the combustion chamber based on the combustion air supplied to the chamber.

- 4) Fuel Density: Density of the fuel was determined by collecting samples of the fuel from a sample point mid-way in the screw feed conveyor. Known volume samples were weighed to determine their density. Caution was used to insure uniform compaction of the fuel samples.
- 5) Air Temperature Measurements: Air temperatures through the test facility were determined using standard laboratory and industrial thermometers.
- 6) Gas Flow Rates: Gas (air) flow rates were determined by the use of standard ASTM sharp edge orifices which were calibrated at various temperatures using a standard pitot tube. Pitot traverses were done according to standard methods. Each orifice is equipped with a thermometer for simultaneous temperature measurement. Orifice pressure differentials were recorded for each test condition and gas flow rates were then found by the use of an orifice flow calibration chart.

The main air flow lines to the combustion chamber were equipped with venturi orifice flow meters rather than sharp edge orifice flow meters. This was done to provide greater accuracy in measuring these two critical air flows. The calibration and pressure differential measurement were done as described above.
- 7) Temperatures in the Combustion Chamber: Exhaust gas temperatures inside the combustion chamber were determined by the use of shielded platinum-rhodium thermocouples. The data from these thermocouples is highly suspect due to re-radiation problems at elevated temperatures.
- 8) Exhaust Gas Analyses: An exhaust gas sample line was installed at the inlet to the air preheater. The sample was cooled to approximately 70 °F to condense the water vapor and remove it. Filters were placed in the sample line to remove particulate matter. Continuous oxygen, carbon monoxide, and carbon dioxide analyzers were used to evaluate the flue gas constituents. Fyrite portable analyzers were used to make spot checks on the accuracy of the continuous analyzers.

- 9) Total Ash Carryover: Ash carryover rates were determined gravimetrically using a simple laboratory scale. The ash collected at the base of the cyclone separator was weighed in a tared container and the elapsed time for the collection of the weighed sample was noted. Calculations were then made to determine the rate of ash carryover in terms of pounds/hr.
- 10) Ash Characteristics - Size, Density, Combustible Content: The characteristics of the ash were determined in the laboratory. Size distribution was obtained using standard sieve screen analyses. The density was determined by placing ash samples in graduated cylinders to determine volume, and then weighing the known volume samples to determine density in pounds/cubic foot (or g/cc). Representative samples of the collected ash were used to determine the percent of the ash which was combustible. Tared containers with known amounts of sample were placed in a muffle furnace at 600 °C for 8 hours. The remaining ash was then reweighed to determine the percent of combustible material in the sample.
- 11) Opacity Measurements: Opacity was determined visually.

DESCRIPTION OF INSTRUMENTATION

1. Fuel Species	13. Temperature @ Forced Draft Fan Exit
2. Fuel Size Distribution	14. Air Flow Rate @ Forced Draft Fan Exit
3. Fuel Moisture Content
(% by weight - "as-is" basis)	15. Gas Sample Point For Flue Gas Analyses (O_2 , CO, CO_2)
4. Fuel Feed Rate	16. Ash Sample Point
5. Fuel Density	17. Opacity Measurement Point
6. Overfire Air Temperature	
7. Underfire Air Temperature	
8. Overfire Air Flow Rate	
9. Underfire Air Flow Rate	
10. Temperature 60" Above Grate	
11. Temperature @ Air Heater Inlet	
12. Temperature @ Air Heater Exit	

Figure 3: Schematic Illustration of Instrumentation Used With the Combustion Test Facility

8. DESIGN OF THE EXPERIMENTS

The overall experimental program was designed to study the influence on the combustion of wood residue fuels of the normal combustion variables found in industrial processes. These variables include:

<u>Fuel Related Variables</u>	<u>Combustion Air Related Variables</u>
Species	Inlet Air Temperature
Size	Level of Excess Air
Moisture	Distribution of Air Above and Below The Grate
Feed Rate	

The principal dependent variable of concern in the experiments is the amount of unburned carbon and non-combustible ash carried out of the combustion chamber per unit of time. This parameter is a measure of the completeness of the combustion reaction in the test facility. High levels of combustible carbon carryover indicate poor combustion conditions. Low levels of carryover indicate better combustion conditions.

The experimental data reported in this document are for only one species: Red Alder bark. Experimental data for other species are reported in other technical reports. For experimental data in this report, the following parameters and ranges were used:

<u>Variables</u>	<u>Range of Variables</u>
No. of Experimental Test Runs:	<u>58</u>
Test Run Numbers:	<u>129</u> To <u>198</u>
Range - Fuel Size Used	<u>0.5</u> To <u>20</u> (mm)
Range - Fuel Moisture Levels Used:	<u>44.0</u> To <u>48.5</u> (%H ₂ O: "As-Is")
Range - Fuel Feed Rates Used:	<u>490</u> To <u>603</u> (Dry Pounds/Hr)
Range - Levels of Excess Air:	<u>15</u> To <u>123</u> (%)
Range - Levels of Inlet Air Temp:	<u>105</u> To <u>412</u> (°F)
Range - Levels of Air Distribution:	<u>30</u> To <u>82</u> (% Undergrate)

9. DATA COLLECTED

For each test run, data were collected for independent and dependent variables. The independent variables included the following:

- 1) Fuel Related
 - Species
 - Size Range
 - Moisture Content
 - Density
 - Feed Rate
- 2) Air Related
 - Temperatures at:
 - Forced Draft Fan Exit
 - Undergrate Air Duct
 - Overfire Air Duct
 - Air Flow Rates at:
 - Forced Draft Fan Exit
 - Undergrate Air Duct
 - Overfire Air Duct
 - Fuel Conveyor Air Duct
- 3) Weather Conditions

The dependent variables for which data were collected during each test run included the following:

- 1) Combustion Exhaust Gas Temperatures
 - 60" Above the Grate
 - At the Inlet to the Air Preheater
 - At the Exit of the Air Preheater
- 2) Ash Carryover Rate from the Discharge of the Cyclone
- 3) Ash Characteristics in Terms of Size Distribution, Combustible Content, and Density Distribution
- 4) Percent Excess Air as Determined by Oxygen Analyses
- 5) Opacity from the Exhaust Gases

For most but not all test conditions, two replications were made.

10. PROCEDURE FOR CONDUCT OF THE EXPERIMENTAL TEST RUNS

The procedure for conduct of the experimental test runs is outlined below:

- 1) Build a fire in the combustion zone and bring the test facility up to operating temperature. This generally requires 2 hours of operating time to bring the system into equilibrium.
- 2) Introduce fuel to the combustion zone where the fuel is of known and desired species, size distribution, moisture content, and fed at desired feed rates. Collect samples of the fuel to check moisture and density.
- 3) Establish the desired inlet air temperature by controlling the air flow through the air preheater and bypass lines. Establish the desired air flow rates through the overfire air lines and the underfire air duct. Check the level of excess air in the combustion zone as determined by the oxygen content of the exhaust gases. Re-adjust the overfire and underfire air flow rates to maintain desired levels of excess air and percentages of overfire and underfire air.
- 4) Begin data collection. Set the pre-tared ash collection bucket at the discharge of the cyclone collector and seal against leakage. Begin data collection from all temperature, gas flow, and pressure indicators and from the gas analysis equipment. Data points are noted at 10 minute intervals on all indicators except the flue gas analysis equipment which is continuous. Log weather conditions, opacity from the cyclone exit duct, and time of starting the test.
- 5) After sufficient running time (typically 20 to 30 minutes per test), terminate the test. Note time of finish of test run and remove the ash carryover buck from the cyclone bottom outlet. Measure the total weight of collected ash and obtain a sample of the collected ash for laboratory analyses on its characteristics.

- 6) Begin replication run of the test.
- 7) At the end of the replication run, re-adjust fuel and air flow parameters for the next test condition.

11. DATA ANALYSES

1. Fuel Size Analyses

The fuel size distribution is determined by drying a sample of the fuel at 106 °C for a minimum period of 24 hours or until the weight of the fuel sample reaches an equilibrium point. The dried samples are then screened using Tyler Standard screens indicated below:

Screen No.	(Inches)	(mm)
1	1.050	26.67
2	.742	18.85
3	.371	9.423
4	.185	4.760
5	.131	3.327
6	.079	2.000
7	.039	1.000
8	.020	.500
Pan		

The weight of each sample collected on each screen is determined and the mass-size distribution plotted on log-probability graph paper.

2. Fuel Moisture Analyses

Fuel moisture analyses were made by collecting a known weight of sample in a pre-tared container. The samples were then dried using the procedure indicated above in (1.) and re-weighed. Calculations were made to determine moisture content on a wet basis or "as-is" basis.

3. Fuel Density Analyses

Fuel density was determined by collecting a sample of the fuel as it was carried up the fuel feed conveyor (screw conveyor). The sample

was dropped from the conveyor into a container of 0.811 curic feet volume. Wehn the container was full to the top (with no mechanical compaction), the weight of the container and the fuel were determined. A simple calculation then produced the density of the fuel sample.

The density was important in determining the fuel feed rate to the combustion system in terms of pounds per hour. The feed conveyor was calibrated in terms of cubic feet of fuel delivered per hour.

4. Flue Gas Analyses

The flue gas analysis system consisted of a stainless steel gas sample line connected to the inlet side of the air preheater and to a sample gas cooling and filtration system. The cooling system allowed the entrained water in the exhaust gas to condense and be removed from the sample line. The filtration system removed entrained particulate matter to avoid plugging the gas analyzers.

Downstream from the cooling and filtration system, a sealed pump was installed to move the sample gas through the system. The exit line from the pump was connected to a sample gas header which carried the gas to the analysis instruments.

Two instruments were used to determine the flue gas constituents. An oxygen analyzer and a CO, CO₂ analyzer were used for continuous readings of the component gas percentages in the dry gas sample.

5. Ash Analyses

Laboratory analyses were conducted to determine the combustible and non-combustible content of the ash collected during the test runs. The standard ASTM test procedure was used in which the ash samples were heated to 600 °C until they reached constant weight. Initial and final weights were used to calculate the amount of combustible material in each sample. Standard screen analyses were used to determine the size distribution of the ash samples. Ash density analyses were made by determining the volume of sample collected on each of the filter screens.

6. Computer Analyses of the Data

A program was written (Fortran IV) to make the calculations pertinent to the requirements of the experimental program. The printout groups the related tests for easy comparison of test parameters and lists the independent and dependent variables.

12. EXPERIMENTAL RESULTS

The experimental test results are summarized on pages 18 and 19. The effects of the important parameters are noted on page 18 (Summary of Research Results). The characteristics of the ash are summarized on page 19 for the entire range of test parameters and for optimum combustion conditions.

The experimental data for each test condition is found in the Experimental Data Summary beginning on page 20. This section has the data in tabulated form.

Graphical representation of the data is found in the section beginning on page 38. Several forms of graphic analysis are offered to provide the reader with a greater understanding of the effects due to the combustion variables.

The raw fuel used in the experimental tests was analyzed and its analyses are indicated in tabular and graphic form beginning on page 68.

The ash analyses results are noted in both tabular and graphic form beginning on page 77. The combustible content of the ash samples as a function of their size distribution is noted in tabular and graphic form beginning on page 171.

13. CONCLUSIONS

The conclusions reached from this experimental work are summarized in the beginning of this report under Summary and Conclusions.

SUMMARY OF RESEARCH RESULTS

SUMMARY OF EFFECTS DUE TO:

1. FUEL SIZE: Not determined - only one fuel size used.
2. FUEL MOISTURE: Not determined - only one fuel moisture level used.
3. FUEL FEED RATE: Range studied (dry lbs/hr): 456 to 603

Effects statistically significant within the range studied:

Yes _____ No XXX

4. INLET AIR TEMPERATURE:

Effects statistically significant within the range studied:

Yes XXX No _____

As air temperature increases, emissions increase ____ decrease XXX

Reference: See pages 65 - 67.

5. LEVELS OF EXCESS AIR: Test results indicate an interaction effect between level of excess air and distribution of air above and below the grate: Yes _____ No XXX

Optimum level of excess air for most test conditions: 50 (%)

Reference: See pages 63, 64.

6. DISTRIBUTION OF AIR ABOVE AND BELOW THE GRATE: Lb Air/Lb Dry Fuel
Optimum rate of air flow through the grate: 3.5 - 4.5

Range of air flow rates through the grate

which were successfully tested: 2.86 to 11.04

Overall optimum air distribution:

Above the grate (overfire air): 51 (%) to 62 (%)

Below the grate (underfire air): 38 (%) to 49 (%)

Reference: See pages 51 - 62.

SUMMARY OF ASH CHARACTERISTICS

	All Tests (Range)	Optimum Combustion Conditions (Mean)	(Range)
1. Rate of Total Carryover (lbs/hr)	<u>7.2</u> to <u>33.6</u>	<u>16.3</u>	<u>12.3</u> to <u>23.1</u>
2. Concentration of Total Particulate (gr/SCF - not corrected to 12% CO ₂)	<u>1.16</u> to <u>4.24</u>	<u>1.67</u>	<u>1.30</u> to <u>1.85</u>
3. Rate of Total Carryover (lb/lb dry fuel)	<u>1.46</u> to <u>5.82</u>	<u>3.10</u>	<u>2.51</u> to <u>4.07</u>
4. Rate of Combustible Carryover (lb/lb dry fuel)	<u>0.03</u> to <u>2.82</u>	<u>0.50</u>	<u>0.14</u> to <u>1.43</u>
5. Rate of Inorganic Carryover (lb/lb dry fuel)	<u>1.55</u> to <u>4.89</u>	<u>2.62</u>	<u>1.71</u> to <u>3.89</u>
6. Mass Mean Size (mm)	<u>0.05</u> to <u>0.48</u>	<u>0.14</u>	<u>0.06</u> to <u>0.43</u>
7. Mass Mean Density (g/cm ³)	<u>0.14</u> to <u>0.53</u>	<u>0.34</u>	<u>0.14</u> to <u>0.40</u>
8. Mean Combustible Content (%)	<u>0.65</u> to <u>50.98</u>	<u>16.4</u>	<u>4.46</u> to <u>45.58</u>
9. Combustible content as a function of ash size distribution.			

See pages 182, 183.

EXPERIMENTAL DATA SUMMARY SHEETS

EXPERIMENTAL DATA SUMMARY SHEET

TEST SERIES: 129 TO 198FUEL SPECIES: ALDER BARK

----- FUEL CHARACTERISTICS -----

MASS MEAN SIZE (mm): 8.2 SIZE RANGE (mm): 0.5 TO 20MASS MEAN DENSITY (g/cm³): 0.43 DENSITY RANGE (g/cm³): 0.36 TO 0.51COMBUSTIBLE CONTENT (% OF DRY FUEL WEIGHT): 94.2

=====

|----- OPERATING PARAMETERS -----|

|----- TEST RESULTS -----|

TEST FUEL NO.	FUEL FEED RATE (LB/HR)	FUEL EXCESS H ₂ O (%)	UNDER AIR (%)	AIR GRATE TEMP. (°F)	LBS AIR / LB FUEL @ GRATE	ASH RATE (LB/HR)	COMB. ASH (%)	MASS MEAN SIZE (mm)	MASS MEAN DENS. (g/cm ³)	OPACITY (%)
---------------	------------------------	----------------------------------	---------------	----------------------	---------------------------	------------------	---------------	---------------------	--------------------------------------	-------------

129	551	44.9	33	82	370	6.79	18.6	31.45	0.143	0.34	5
130	"	"	30	82	375	6.75	20.7				"
131	"	"	53	82	343	8.56	17.4	12.97	0.065	0.36	"
132	"	"	53	82	346	8.57	16.2				"
133	584	"	80	83	380	10.05	20.4	5.13	0.058	0.48	"
134	"	"	80	83	382	10.04	21.1				"
135	"	"	100	82	380	10.88	22.4	2.34	0.055	0.53	"
136	"	"	100	82	370	11.04	21.9				"
137	492 564	" "	25 25	52 52	371 349	4.75 4.22	15.3 17.7	50.22 45.58	0.250 0.43	0.28 0.14	"
138	492	"	15	51	375	4.72	7.2				"
139	492	"	50	50	350	5.74	13.8	17.4	0.081	0.29	"
140	492	44.2	55	50	345	5.78	12.6				"
141	"	"	76	51	347	6.78	16.5				"
142	"	"	76	50	348	6.79	17.7	1.86	0.081	0.38	"
143	564	"	98	51	365	7.10	17.4	2.43	0.064	0.32	"

EXPERIMENTAL DATA SUMMARY SHEET

TEST SERIES: 129 TO 198FUEL SPECIES: ALDER BARK

----- FUEL CHARACTERISTICS -----

MASS MEAN SIZE (mm): 8.2 SIZE RANGE (mm): 0.5 TO 20.MASS MEAN DENSITY (g/cm³): 0.43 DENSITY RANGE (g/cm³): 0.36 TO 0.51COMBUSTIBLE CONTENT (% OF DRY FUEL WEIGHT): 94.2

=====

|----- OPERATING PARAMETERS -----|

|----- TEST RESULTS -----|

TEST FUEL NO.	FUEL FEED RATE (LB/HR)	EXCESS H ₂ O (%)	UNDER AIR (%)	AIR GRATE TEMP. (°F)	LBS AIR LB FUEL @ GRATE	ASH RATE (LB/HR)	COMB. ASH (%)	MASS MEAN SIZE (mm)	MASS MEAN DENS. (g/cm ³)	OPACITY (%)
------------------	------------------------------	--------------------------------	------------------	----------------------------	-------------------------------	---------------------	------------------	---------------------------	--	----------------

144	564	46.8	90	51	373	7.05	18.8				5
147	490	"	48	31	373	3.62	12.3	16.63	0.078	0.40	11
148	"	"	48	31	388	3.59	13.5				10
149	"	"	77	31	388	4.15	13.2	5.32	0.067	0.40	"
150	"	"	84	31	390	4.14	12.9				"
151	"	46.9	120	30	393	4.75	14.1	2.61	0.048	0.42	"
152	"	"	120	30	393	4.71	12.9				"
155	541	"	53	30	134	3.26	19.8	33.73	0.180	0.35	"
156	541	"	50	30	132	3.26	17.7				"
157	"	"	75	31	132	3.82	17.1	16.25	0.078	0.40	15
158	"	"	75	31	131	3.82	15.9				15
159	567	"	100	30	120	4.15	23.1	4.46	0.059	0.36	5
160	"	"	100	30	120	4.11	20.9				"
161	"	"	43	79	106	6.95	31.4	50.98	0.48	0.18	"
162	"	"	39	79	105	6.96	33.0				"

EXPERIMENTAL DATA SUMMARY SHEET

TEST SERIES: 129 TO 198FUEL SPECIES: ALDER BARK

- - - - - FUEL CHARACTERISTICS - - - - -

MASS MEAN SIZE (mm): 8.2 SIZE RANGE (mm): 0.5 TO 20.MASS MEAN DENSITY(g/cm³): 0.43 DENSITY RANGE (g/cm³): 0.36 TO 0.51COMBUSTIBLE CONTENT (% OF DRY FUEL WEIGHT): 94.2

= = = = =

| - - - - - OPERATING PARAMETERS - - - | | - - - TEST RESULTS - - - |

TEST FUEL NO.	FUEL FEED RATE (LB/HR)	FUEL EXCESS H ₂ O (%)	AIR (%)	UNDER GRADE AIR (%)	AIR TEMP. (°F)	LBS AIR LB FUEL @ GRATE	ASH RATE (LB/HR)	COMB. ASH (%)	MASS MEAN SIZE (mm)	MASS MEAN DENS. (g/cm ³)	OPACITY (%)
---------------	------------------------	----------------------------------	---------	---------------------	----------------	-------------------------	------------------	---------------	---------------------	--------------------------------------	-------------

163	567	44.0	52	82	118	8.33	30.6	41.58	0.380	0.21	5
164	"	"	60	81	118	8.06	29.4				"
165	"	"	75	81	128	9.63	26.9	21.26	0.090	0.48	10
166	"	"	75	81	127	9.64	28.5				"
167	576	"	110	80	135	10.73	22.0	2.01	0.050	0.42	"
168	"	45.7	100	80	135	10.73	23.7				"
171	524	"	68	51	130	5.72	20.2	30.5	0.150	0.34	"
172	"	"	68	51	128	5.73	19.6				"
173	550	"	88	51	135	6.28	21.3	8.08	0.071	0.37	5
174	"	"	88	51	135	6.96	19.4				"
175	"	"	123	50	143	6.28	23.4	2.94	0.064	0.44	"
176	"	"	123	50	145	6.94	20.4				"
177	472	"	70	83	412	7.82	18.6	36.55	0.23	0.29	"
178	472	"	70	83	405	7.81	19.8				"
179	498	"	110	83	410	10.40	23.1	0.65	0.049	0.42	7

WOOD SPECIES: ALDER BARK
 SIZE RANGE: 1" MINUS
 MOISTURE (%): 44.90
 DENSITY (LBS/CU. FT): 37.50

RUN NO:	129.	0.	0.	0.	0.
DATE:	4-7-78	::: :::	::: :::	::: :::	::: :::
CONVEYOR SETTING:	16.	0.	0.	0.	0.
FUEL FEED RATE:	551.	0.	0.	0.	0.
(DRY LBS/HR)					
HEAT INPUT RATE:	4961851.	0.	0.	0.	0.
(BTU/HR)					
HEAT RELEASE RATE:	496185.	0.	0.	0.	0.
(BTU/HR-SQFT)					
UNDERFIRE:	12-INCH	0-INCH	0-INCH	0-INCH	0-INCH
OVERFIRE:	6-INCH	0-INCH	0-INCH	0-INCH	0-INCH
PERCENT EX. AIR:	33.	0.	0.	0.	0.

TEMPERATURES (DEGREES F)

T2:	1288.	0.	0.	0.	0.
T3:	1120.	0.	0.	0.	0.
T4:	750.	0.	0.	0.	0.
FAN OUTLET:	62.	0.	0.	0.	0.
UNDERGRATE:	370.	0.	0.	0.	0.
OVERFIRE:	335.	0.	0.	0.	0.
AIR HEATER:	493.	0.	0.	0.	0.

PRESSURE DIFFERENTIALS (INCHES WATER)

MAIN ORIFICE:	0.0	0.0	0.0	0.0	0.0
6" VENTURI:	.4	0.0	0.0	0.0	0.0
12" VENTURI:	1.4	0.0	0.0	0.0	0.0
3" CONVEYOR:	3.0	0.0	0.0	0.0	0.0
ACROSS GRATE:	2.2	0.0	0.0	0.0	0.0

EXHAUST GAS ANALYSIS (PERCENT)

OXYGEN:	5.4	0.0	0.0	0.0	0.0
CARBON DIOXIDE:	15.6	0.0	0.0	0.0	0.0
CARBON MONOXIDE:	.14	0.00	0.00	0.00	0.00
OXIDES OF NITROGEN:	0.0	0.0	0.0	0.0	0.0

AIR FLOW RATES (ACFM)

MAIN:	0.	0.	0.	0.	0.
UNDERGRATE:	1506.	0.	0.	0.	0.
OVERFIRE:	336.	0.	0.	0.	0.

AIR FLOW RATES (SCFM)

MAIN:	0.	0.	0.	0.	0.
UNDERGRATE:	777.	0.	0.	0.	0.
OVERFIRE:	173.	0.	0.	0.	0.
UNDER + OVER:	951.	0.	0.	0.	0.
CALC. BASED ON :	940.	0.	0.	0.	0.
FUEL AND EX. AIR					
PERCENT UG:OF	82.:18.	0.: 0.	0.: 0.	0.: 0.	0.: 0.

CARRY OVER DATA

LBS/HR:	18.6	0.0	0.0	0.0	0.0
GR/SCF:	2.308	0.000	0.000	0.000	0.000
PERCENT ASH:	0.	0.	0.	0.	0.
PERCENT COMBUSTIBLE:	0.	0.	0.	0.	0.
LENGTH OF RUN(MIN):	20.	0.	0.	0.	0.
OPACITY:	5.	0.	0.	0.	0.

WEATHER: SUNNY

WOOD SPECIES: ALDER BARK
 SIZE RANGE: 1" MINUS
 MOISTURE (%): 44.90
 DENSITY (LBS/CU.FT): 37.50

RUN NO:	130-	131-	132-	133-	134-
DATE:	4-7-78	4-7-78	4-7-78	4-7-78	4-7-78
CONVEYOR SETTING:	16-	16-	16-	17-	17-
FUEL FEED RATE: (DRY LBS/HR)	551.	551.	551.	584.	584.
HEAT INPUT RATE: (BTU/HR)	4961851.	4961851.	4961851.	5254928.	5254928.
HEAT RELEASE RATE: (BTU/HR-SQFT)	496185.	496185.	496185.	525493.	525493.
UNDERFIRE:	12-INCH	12-INCH	12-INCH	12-INCH	12-INCH
OVERFIRE:	6-INCH	6-INCH	6-INCH	6-INCH	6-INCH
PERCENT EX. AIR:	30.	53.	53.	80.	80.

TEMPERATURES (DEGREES F)

T2:	1302.	1215.	1225.	1255.	1293.
T3:	1128.	1075.	1075.	1077.	1065.
T4:	755.	707.	700.	713.	720.
FAN OUTLET:	62.	63.	64.	66.	66.
UNDERGRATE:	375.	343.	346.	380.	382.
OVERFIRE:	315.	293.	289.	324.	329.
AIR HEATER:	503.	426.	423.	413.	417.

PRESSURE DIFFERENTIALS (INCHES WATER)

MAIN ORIFICE:	0.0	.2	.2	.3	.3
6" VENTURI:	.4	.7	.6	1.0	1.0
12" VENTURI:	1.4	2.2	2.2	3.6	3.6
3" CONVEYOR:	3.0	3.0	3.1	3.0	3.0
ACROSS GRATE:	2.6	2.5	2.3	2.5	2.6

EXHAUST GAS ANALYSIS (PERCENT)

OXYGEN:	5.0	7.3	7.5	9.3	9.3
CARBON DIOXIDE:	15.6	12.9	12.9	10.9	10.9
CARBON MONOXIDE:	.22	.22	.22	.25	.27
OXIDES OF NITROGEN:	0.0	0.0	0.0	0.0	0.0

AIR FLOW RATES (ACFM)

MAIN:	0-	1229.	1229.	1576.	1576.
UNDERGRATE:	1513.	1764.	1761.	2165.	2170.
OVERFIRE:	337.	394.	375.	444.	445.

AIR FLOW RATES (SCFM)

MAIN:	0-	1155.	1154.	1475.	1474.
UNDERGRATE:	773.	980.	981.	1220.	1218.
OVERFIRE:	172.	219.	209.	250.	250.
UNDER + OVER:	945.	1198.	1190.	1471.	1467.
CALC. BASED ON :	919.	1082.	1082.	1348.	1348.
FUEL AND EX- AIR					
PERCENT UG:OF	82.±18.	82.±18.	82.±18.	83.±17.	83.±17.

CARRY OVER DATA

LBS/HR:	20.7	17.4	16.2	20.4	21.1
GR/SCF:	2.627	1.876	1.747	1.766	1.830
PERCENT ASH:	0.	0.	0.	0.	0.
PERCENT COMBUSTIBLE:	0.	0.	0.	0.	0.
LENGTH OF RUN(MIN):	20.	30.	20.	20.	21.
OPACITY:	5.	5.	5.	5.	5.

WEATHER:	SUNNY	SUNNY	SUNNY	SUNNY	SUNNY
----------	-------	-------	-------	-------	-------

SRU 1.559 UNITS.

RUN COMPLETE.

WOOD SPECIES: ALDER BARK
 SIZE RANGE: 1" MINUS
 MOISTURE (%): 44.90
 DENSITY (LBS/CU.FT): 37.50

RUN NO:	135.	136.	137.	137.	138.
DATE:	4-7-78	4-7-78	4-14-78	4-11-78	4-10-78
CONVEYOR SETTING:	17.	17.	14.	17.	14.
FUEL FEED RATE:	584.	584.	492.	564.	492.
(DRY LBS/HR)					
HEAT INPUT RATE:	5254928.	5254928.	4431287.	5073724.	4431287.
(BTU/HR)					
HEAT RELEASE RATE:	525493.	525493.	443129.	507372.	443129.
(BTU/HR-SQFT)					
UNDERFIRE:	12.INCH	12.INCH	12.INCH	12.INCH	12.INCH
OVERFIRE:	6.INCH	6.INCH	6.INCH	6.INCH	6.INCH
PERCENT EX. AIR:	100.	100.	25.	25.	15.

TEMPERATURES (DEGREES F)

T2:	1300.	1310.	1348.	1347.	1342.
T3:	1040.	1022.	1103.	1097.	1133.
T4:	717.	705.	710.	678.	727.
FAN OUTLET:	64.	64.	67.	61.	67.
UNDERGRATE:	380.	370.	371.	349.	375.
OVERFIRE:	338.	335.	465.	430.	473.
AIR HEATER:	409.	401.	542.	505.	555.

PRESSURE DIFFERENTIALS (INCHES WATER)

MAIN ORIFICE:	.4	.4	0.0	0.0	0.0
6" VENTURI:	1.5	1.5	5.7	5.4	5.9
12" VENTURI:	4.3	4.4	.5	.5	.5
3" CONVEYOR:	2.9	3.0	3.0	3.0	3.0
ACROSS GRATE:	2.4	2.5	1.7	1.7	1.7

EXHAUST GAS ANALYSIS (PERCENT)

OXYGEN:	10.5	10.5	4.3	4.4	3.3
CARBON DIOXIDE:	9.5	9.2	16.4	15.1	17.8
CARBON MONOXIDE:	.38	.43	.19	.32	.34
OXIDES OF NITROGEN:	0.0	0.0	0.0	0.0	0.0

AIR FLOW RATES (ACFM)

MAIN:	1835.	1835.	0.	0.	0.
UNDERGRATE:	2333.	2345.	990.	972.	997.
OVERFIRE:	513.	512.	930.	894.	949.

AIR FLOW RATES (SCFM)

MAIN:	1722.	1723.	0.	0.	0.
UNDERGRATE:	1321.	1340.	486.	495.	483.
OVERFIRE:	290.	293.	457.	456.	460.
UNDER + OVER:	1611.	1633.	943.	951.	943.
CALC. BASED ON :	1498.	1498.	789.	904.	726.
FUEL AND EX. AIR					
PERCENT UG:OF	82.:18.	82.:18.	52.:48.	52.:48.	51.:49.

CARRY OVER DATA

LBS/HR:	22.4	21.9	15.3	17.7	7.2
GR/SCF:	1.748	1.706	2.257	2.285	1.157
PERCENT ASH:	0.	0.	0.	0.	0.
PERCENT COMBUSTIBLE:	0.	0.	0.	0.	0.
LENGTH OF RUN(MIN):	23.	20.	22.	20.	20.
OPACITY:	5.	5.	5.	5.	5.

WEATHER:	CLOUDY	CLOUDY	SUNNY	SUNNY	SUNNY
----------	--------	--------	-------	-------	-------

SRU 1.122 UNTS.

RUN COMPLETE.

WOOD SPECIES: ALDER BARK
 SIZE RANGE: 1" MINUS
 MOISTURE (%): 44.20
 DENSITY (LBS/CU.FT): 37.50

RUN NO:	139.	140.	141.	142.	143.
DATE:	4-10-78	4-10-78	4-10-78	4-10-78	4-11-78
CONVEYOR SETTING:	14.	14.	14.	14.	17.
FUEL FEED RATE:	492.	492.	492.	492.	564.
(DRY LBS/HR)					
HEAT INPUT RATE:	4431287.	4431287.	4431287.	4431287.	5073724.
(BTU/HR)					
HEAT RELEASE RATE:	443129.	443129.	443129.	443129.	507372.
(BTU/HR-SQFT)					
UNDERFIRE:	12-INCH	12-INCH	12-INCH	12-INCH	12-INCH
OVERFIRE:	6-INCH	6-INCH	6-INCH	6-INCH	6-INCH
PERCENT EX. AIR:	50.	55.	76.	76.	98.

TEMPERATURES (DEGREES F)

T2:	1390.	1370.	1370.	1373.	1432.
T3:	987.	983.	980.	980.	1030.
T4:	645.	640.	642.	645.	672.
FAN OUTLET:	76.	77.	78.	76.	63.
UNDERGRATE:	350.	345.	347.	348.	365.
OVERFIRE:	412.	407.	395.	393.	417.
AIR HEATER:	459.	448.	436.	435.	423.

PRESSURE DIFFERENTIALS (INCHES WATER)

MAIN ORIFICE:	.1	.1	.2	.2	.2
6" VENTURI:	8.8	9.0	12.5	12.7	17.3
12" VENTURI:	.7	.7	1.0	1.0	1.5
3" CONVEYOR:	3.0	3.0	3.0	3.0	3.0
ACROSS GRATE:	2.0	2.0	1.8	1.8	1.9

EXHAUST GAS ANALYSIS (PERCENT)

OXYGEN:	7.0	7.5	9.0	9.0	10.4
CARBON DIOXIDE:	13.2	12.6	11.5	12.0	10.2
CARBON MONOXIDE:	.17	.17	.15	.17	.15
OXIDES OF NITROGEN:	0.0	0.0	0.0	0.0	0.0

AIR FLOW RATES (ACFM)

MAIN:	966.	915.	1267.	1189.	1342.
UNDERGRATE:	1096.	1090.	1263.	1262.	1493.
OVERFIRE:	1075.	1080.	1237.	1245.	1416.

AIR FLOW RATES (SCFM)

MAIN:	887.	838.	1160.	1090.	1262.
UNDERGRATE:	587.	591.	693.	694.	832.
OVERFIRE:	576.	585.	679.	684.	789.
UNDER + OVER:	1163.	1176.	1372.	1378.	1621.
CALC. BASED ON :	947.	979.	1111.	1111.	1432.
FUEL AND EX. AIR					
PERCENT UG:OF	50.:50.	50.:50.	51.:49.	50.:50.	51.:49.

CARRY OVER DATA

LBS/HR:	13.8	12.6	16.5	17.7	17.4
GR/SCF:	1.703	1.502	1.732	1.858	1.420
PERCENT ASH:	0.	0.	0.	0.	0.
PERCENT COMBUSTIBLE:	0.	0.	0.	0.	0.
LENGTH OF RUN(MIN):	23.	20.	20.	20.	21.
OPACITY:	5.	5.	5.	5.	5.

WEATHER:	SUNNY	SUNNY	SUNNY	SUNNY	SUNNY
----------	-------	-------	-------	-------	-------

SRU 1.558 UNITS.

RUN COMPLETE.

WOOD SPECIES: ALDER BARK
 SIZE RANGE: 1" MINUS
 MOISTURE (%): 46.80
 DENSITY (LBS/CU.FT): 37.50

RUN NO:	144.	147.	148.	149.	150.
DATE:	4-11-78	4-12-78	4-12-78	4-12-78	4-12-78
CONVEYOR SETTING:	17.	18.	18.	18.	18.
FUEL FEED RATE:	564.	490.	490.	490.	490.
(DRY LBS/HR)					
HEAT INPUT RATE:	5073724.	4405620.	4405620.	4405620.	4405620.
(BTU/HR)					
HEAT RELEASE RATE:	507372.	440562.	440562.	440562.	440562.
(BTU/HR-SQFT)					
UNDERFIRE:	12.INCH	6.INCH	6.INCH	6.INCH	6.INCH
OVERFIRE:	6.INCH	12.INCH	12.INCH	12.INCH	12.INCH
PERCENT EX. AIR:	90.	48.	48.	77.	84.

TEMPERATURES (DEGREES F)

T2:	1437.	1512.	1532.	1540.	1550.
T3:	1028.	1013.	1040.	1040.	1028.
T4:	680.	640.	657.	677.	680.
FAN OUTLET:	63.	58.	58.	60.	61.
UNDERGRATE:	373.	373.	388.	388.	390.
OVERFIRE:	431.	390.	398.	430.	432.
AIR HEATER:	435.	453.	465.	464.	469.

PRESSURE DIFFERENTIALS (INCHES WATER)

MAIN ORIFICE:	.2	.0	.0	.1	.1
6" VENTURI:	17.3	4.3	4.3	5.8	5.8
12" VENTURI:	1.5	1.3	1.3	1.9	1.9
3" CONVEYOR:	3.0	3.0	3.0	2.9	2.9
ACROSS GRATE:	1.8	1.3	1.2	1.1	1.1

EXHAUST GAS ANALYSIS (PERCENT)

OXYGEN:	10.1	6.8	6.8	9.2	9.6
CARBON DIOXIDE:	10.1	14.1	14.1	11.7	11.3
CARBON MONOXIDE:	.15	.08	.08	.10	.08
OXIDES OF NITROGEN:	0.0	0.0	0.0	0.0	0.0

AIR FLOW RATES (ACFM)

MAIN:	1305.	521.	521.	804.	861.
UNDERGRATE:	1503.	684.	689.	794.	796.
OVERFIRE:	1424.	1537.	1547.	1799.	1804.

AIR FLOW RATES (SCFM)

MAIN:	1228.	495.	495.	761.	814.
UNDERGRATE:	326.	369.	366.	423.	422.
OVERFIRE:	783.	828.	823.	958.	955.
UNDER + OVER:	1609.	1197.	1189.	1381.	1377.
CALC. BASED ON :	1374.	929.	929.	1111.	1155.
FUEL AND EX. AIR					
PERCENT UG:OF	51.:49.	31.:69.	31.:69.	31.:69.	31.:69.

CARRY OVER DATA

LBS/HR:	18.8	12.3	13.5	13.2	12.9
GR/SCF:	1.598	1.544	1.695	1.386	1.303
PERCENT ASH:	0.	0.	0.	0.	0.
PERCENT COMBUSTIBLE:	0.	0.	0.	0.	0.
LENGTH OF RUN(MIN):	37.	20.	20.	20.	20.
OPACITY:	5.	11.	10.	10.	10.
WEATHER:	SUNNY	SUNNY	SUNNY	SUNNY	SUNNY

SRU 1.561 UNITS.

RUN COMPLETE.

WOOD SPECIES: ALDER BARK
 SIZE RANGE: 1" MINUS
 MOISTURE (%): 46.90
 DENSITY (LBS/CU.FT): 30.90

RUN NO:	151.	152.	155.	156.	157.
DATE:	4-12-78	4-12-78	4-12-78	4-12-78	4-12-78
CONVEYOR SETTING:	18.	18.	20.	20.	20.
FUEL FEED RATE:	490.	490.	541.	541.	541.
(DRY LBS/HR)					
HEAT INPUT RATE:	4405620.	4405620.	4871079.	4871079.	4871079.
(BTU/HR)					
HEAT RELEASE RATE:	440562.	440562.	487108.	487108.	487108.
(BTU/HR-SQFT)					
UNDERFIRE:	6.INCH	6.INCH	6.INCH	6.INCH	6.INCH
OVERFIRE:	12.INCH	12.INCH	12.INCH	12.INCH	12.INCH
PERCENT EX. AIR:	120.	120.	53.	50.	75.

TEMPERATURES (DEGREES F)

T2:	1490.	1513.	1437.	1440.	1530.
T3:	1003.	1015.	1118.	1132.	1095.
T4:	682.	690.	697.	715.	742.
FAN OUTLET:	62.	63.	65.	65.	66.
UNDERGRATE:	393.	393.	134.	132.	132.
OVERFIRE:	407.	408.	134.	132.	132.
AIR HEATER:	442.	443.	154.	152.	152.

PRESSURE DIFFERENTIALS (INCHES WATER)

MAIN ORIFICE:	.2	.2	.4	.4	.5
6" VENTURI:	7.5	7.4	2.8	2.8	3.9
12" VENTURI:	2.6	2.6	.8	.8	1.1
3" CONVEYOR:	2.9	3.0	3.0	3.0	2.8
ACROSS GRATE:	1.0	1.1	1.5	1.6	1.4

EXHAUST GAS ANALYSIS (PERCENT)

OXYGEN:	11.6	11.6	7.3	7.5	9.1
CARBON DIOXIDE:	9.3	9.3	13.6	13.4	11.7
CARBON MONOXIDE:	.15	.14	.14	.12	.22
OXIDES OF NITROGEN:	0.0	0.0	0.0	0.0	0.0

AIR FLOW RATES (ACFM)

MAIN:	1229.	1229.	1914.	1861.	2087.
UNDERGRATE:	886.	881.	458.	457.	535.
OVERFIRE:	2021.	2024.	1059.	1058.	1194.

AIR FLOW RATES (SCFM)

MAIN:	1157.	1156.	1794.	1744.	1952.
UNDERGRATE:	484.	480.	367.	367.	430.
OVERFIRE:	1102.	1103.	849.	850.	960.
UNDER + OVER:	1586.	1583.	1215.	1218.	1390.
CALC. BASED ON :	1381.	1381.	1062.	1041.	1215.
FUEL AND EX. AIR					
PERCENT UG:OF	30.:70.	30.:70.	30.:70.	30.:70.	31.:69.

CARRY OVER DATA

LBS/HR:	14.1	12.9	19.8	17.7	17.1
GR/SCF:	1.191	1.090	2.175	1.983	1.642
PERCENT ASH:	0.	0.	0.	0.	0.
PERCENT COMBUSTIBLE:	0.	0.	0.	0.	0.
LENGTH OF RUN(MIN):	20.	20.	20.	20.	20.
OPACITY:	10.	10.	10.	10.	15.

WEATHER:	SUNNY	SUNNY	SUNNY	SUNNY	SUNNY
----------	-------	-------	-------	-------	-------

SRU 1.501 UNITS.

RUN COMPLETE.

WOOD SPECIES: ALDER BARK
 SIZE RANGE: 1" MINUS
 MOISTURE (%): 46.90
 DENSITY (LBS/CU-FT): 30.90

RUN NO:	158.	159.	160.	161.	162.
DATE:	4-12-78	4-14-78	4-14-78	4-14-78	4-14-78
CONVEYOR SETTING:	20.	20.	20.	20.	20.
FUEL FEED RATE:	541.	567.	567.	567.	567.
(DRY LBS/HR)					
HEAT INPUT RATE:	4871079.	5103858.	5103858.	5103858.	5103858.
(BTU/HR)					
HEAT RELEASE RATE:	487108.	510386.	510386.	510386.	510386.
(BTU/HR-SQFT)					
UNDERFIRE:	6-INCH	6-INCH	6-INCH	12-INCH	12-INCH
OVERFIRE:	12-INCH	12-INCH	12-INCH	6-INCH	6-INCH
PERCENT EX. AIR:	75.	100.	100.	43.	39.

TEMPERATURES (DEGREES F)

T2:	1515.	1585.	1598.	1268.	1267.
T3:	1093.	1085.	1098.	1232.	1232.
T4:	738.	740.	745.	753.	748.
FAN OUTLET:	66.	52.	53.	55.	55.
UNDERGRATE:	131.	120.	120.	106.	105.
OVERFIRE:	131.	120.	120.	106.	105.
AIR HEATER:	151.	140.	140.	126.	125.

PRESSURE DIFFERENTIALS (INCHES WATER)

MAIN ORIFICE:	.5	.5	.5	.3	.3
6" VENTURI:	3.9	5.0	4.9	.3	.3
12" VENTURI:	1.1	1.6	1.6	.9	.9
3" CONVEYOR:	2.9	3.0	3.0	3.0	3.0
ACROSS GRATE:	1.5	1.3	1.3	2.5	2.5

EXHAUST GAS ANALYSIS (PERCENT)

OXYGEN:	8.7	10.7	10.8	6.6	6.1
CARBON DIOXIDE:	12.1	10.1	10.0	14.1	14.5
CARBON MONOXIDE:	.20	.19	.18	.34	.39
OXIDES OF NITROGEN:	0.0	0.0	0.0	0.0	0.0

AIR FLOW RATES (ACFM)

MAIN:	2087.	2291.	2291.	1637.	1695.
UNDERGRATE:	534.	596.	590.	976.	975.
OVERFIRE:	1195.	1375.	1375.	264.	264.

AIR FLOW RATES (SCFM)

MAIN:	1952.	2200.	2196.	1564.	1619.
UNDERGRATE:	430.	489.	484.	819.	820.
OVERFIRE:	962.	1128.	1128.	222.	222.
UNDER + OVER:	1392.	1617.	1618.	1041.	1042.
CALC. BASED ON :	1215.	1455.	1455.	909.	909.
FUEL AND EX. AIR					
PERCENT UG:OF	31.869.	30.170.	30.170.	79.121.	79.121.

CARRY OVER DATA

LBS/HR:	15.9	23.1	20.9	31.4	33.0
GR/SCF:	1.527	1.853	1.673	4.033	4.235
PERCENT ASH:	0.	0.	0.	0.	0.
PERCENT COMBUSTIBLE:	0.	0.	0.	0.	0.
LENGTH OF RUN(MIN):	20.	20.	21.	21.	20.
OPACITY:	15.	5.	5.	5.	5.

WEATHER:	SUNNY	RAIN	RAIN	RAIN/CLDY	CLOUDY
----------	-------	------	------	-----------	--------

SRU 1.558 UNTS.

RUN COMPLETE.

WOOD SPECIES: ALDER BARK
 SIZE RANGE: 1" MINUS
 MOISTURE (%): 44.00
 DENSITY (LBS/CU-FT): 30.70

RUN NO:	163-	164-	165-	166-	167-
DATE:	4-14-78	4-14-78	4-14-78	4-14-78	4-17-78
CONVEYOR SETTING:	20-	20-	20-	20-	21-
FUEL FEED RATE:	567-	567-	567-	567-	576-
(DRY LBS/HR)					
HEAT INPUT RATE:	5103858-	5103858-	5103858-	5103858-	5185368-
(BTU/HR)					
HEAT RELEASE RATE:	510386-	510386-	510386-	510386-	518537-
(BTU/HR-SQFT)					
UNDERFIRE:	12-INCH	12-INCH	12-INCH	12-INCH	12-INCH
OVERFIRE:	6-INCH	6-INCH	6-INCH	6-INCH	6-INCH
PERCENT EX-AIR:	52-	60-	75-	75-	110-

TEMPERATURES (DEGREES F)

T2:	1280-	1328-	1400-	1330-	1433-
T3:	1237-	1228-	1153-	1138-	1077-
T4:	787-	795-	793-	800-	753-
FAN OUTLET:	56-	57-	56-	56-	57-
UNDERGRATE:	118-	118-	128-	127-	135-
OVERFIRE:	118-	118-	128-	127-	135-
AIR HEATER:	138-	138-	148-	147-	155-

PRESSURE DIFFERENTIALS (INCHES WATER)

MAIN ORIFICE:	.4	.4	.5	.5	.6
6" VENTURI:	.3	.3	.6	.6	1.0
12" VENTURI:	1.4	1.3	2.0	2.0	2.7
3" CONVEYOR:	3.0	3.0	3.0	3.0	3.0
ACROSS GRATE:	2.8	2.8	2.8	2.9	2.4

EXHAUST GAS ANALYSIS (PERCENT)

OXYGEN:	7.3	8.0	9.1	9.0	11.4
CARBON DIOXIDE:	13.4	12.8	11.6	11.7	9.1
CARBON MONOXIDE:	.34	.22	.29	.35	.52
OXIDES OF NITROGEN:	0.0	0.0	0.0	0.0	0.0

AIR FLOW RATES (ACFM)

MAIN:	1835-	1835-	2111-	2087-	2356-
UNDERGRATE:	1193-	1155-	1403-	1401-	1605-
OVERFIRE:	266-	266-	329-	328-	390-

AIR FLOW RATES (SCFM)

MAIN:	1749-	1747-	2011-	1989-	2241-
UNDERGRATE:	981-	950-	1135-	1136-	1284-
OVERFIRE:	219-	219-	266-	266-	312-
UNDER + OVER:	1200-	1169-	1401-	1402-	1597-
CALC. BASED ON:	1091-	1091-	1273-	1273-	1478-
FUEL AND EX-AIR					
PERCENT UG:OF	82.:18.	81.:19.	81.:19.	81.:19.	80.:20.

CARRY OVER DATA

LBS/HR:	30.6	29.4	26.9	28.5	22.0
GR/SCF:	3.272	3.144	2.462	2.612	1.737
PERCENT ASH:	0-	0-	0-	0-	0-
PERCENT COMBUSTIBLE:	0-	0-	0-	0-	0-
LENGTH OF RUN(MIN):	20-	20-	21-	20-	21-
OPACITY:	5-	5-	10-	10-	10-
WEATHER:	CLOUDY	CLOUDY	RAIN	RAIN	CLOUDY

SRU 1.566 UNTS.

RUN COMPLETE.

WOOD SPECIES: ALDER BARK
 SIZE RANGE: 1" MINUS
 MOISTURE (%): 45.70
 DENSITY (LBS/CU-FT): 30.70

RUN NO:	168.	171.	172.	173.	174.
DATE:	4-17-78	4-17-78	4-17-78	4-17-78	4-17-78
CONVEYOR SETTING:	21.	19.	19.	20.	20.
FUEL FEED RATE:	576.	524.	524.	550.	550.
(DRY LBS/HR)					
HEAT INPUT RATE:	5185368.	4712471.	4712471.	4948919.	4948919.
(BTU/HR)					
HEAT RELEASE RATE:	518537.	471247.	471247.	494892.	494892.
(BTU/HR-SQFT)					
UNDERFIRE:	12-INCH	12-INCH	12-INCH	12-INCH	12-INCH
OVERFIRE:	6-INCH	6-INCH	6-INCH	6-INCH	6-INCH
PERCENT EX. AIR:	100.	68.	68.	88.	88.

TEMPERATURES (DEGREES F)

T2:	1418.	1410.	1410.	1463.	1472.
T3:	1083.	1090.	1095.	1048.	1063.
T4:	770.	680.	680.	697.	705.
FAN OUTLET:	57.	59.	58.	57.	57.
UNDERGRATE:	135.	130.	128.	135.	135.
OVERFIRE:	135.	130.	128.	135.	135.
AIR HEATER:	155.	150.	148.	155.	155.

PRESSURE DIFFERENTIALS (INCHES WATER)

MAIN ORIFICE:	.6	.4	.4	.5	.5
6" VENTURI:	1.0	5.5	5.5	8.2	8.2
12" VENTURI:	2.7	.5	.5	.7	.7
3" CONVEYOR:	3.0	3.0	3.0	3.0	3.0
ACROSS GRATE:	2.4	1.5	1.6	1.8	1.8

EXHAUST GAS ANALYSIS (PERCENT)

OXYGEN:	11.3	8.6	8.6	9.8	9.8
CARBON DIOXIDE:	9.3	12.3	12.3	11.0	11.0
CARBON MONOXIDE:	.45	.13	.13	.24	.24
OXIDES OF NITROGEN:	0.0	0.0	0.0	0.0	0.0

AIR FLOW RATES (ACFM)

MAIN:	2356.	1914.	1888.	2111.	2087.
UNDERGRATE:	1605.	773.	771.	897.	897.
OVERFIRE:	390.	739.	738.	874.	874.

AIR FLOW RATES (SCFM)

MAIN:	2242.	1815.	1793.	2010.	1987.
UNDERGRATE:	1284.	623.	624.	718.	718.
OVERFIRE:	312.	596.	597.	699.	699.
UNDER + OVER:	1597.	1219.	1221.	1416.	1416.
CALC. BASED ON :	1478.	1007.	1007.	1326.	1326.
FUEL AND EX. AIR					
PERCENT UC:OF	80.120.	51.149.	51.149.	51.149.	51.149.

CARRY OVER DATA

LBS/HR:	23.7	20.2	19.6	21.3	19.4
GR/SCF:	1.871	2.338	2.274	1.874	1.710
PERCENT ASH:	0.	0.	0.	0.	0.
PERCENT COMBUSTIBLE:	0.	0.	0.	0.	0.
LENGTH OF RUN(MIN):	20.	22.	22.	20.	21.
OPACITY:	10.	10.	10.	5.	5.

WEATHER:	CLOUDY	CLOUDY	CLDY/RAIN	RAIN	RAIN
----------	--------	--------	-----------	------	------

SRU 1.535 UNTS.

RUN COMPLETE.

WOOD SPECIES: ALDER BARK
 SIZE RANGE: 1" MINUS.
 MOISTURE (%): 45-70
 DENSITY (LBS/CU.FT): 30-70

RUN NO:	175-	176-	177-	178-	179-
DATE:	4-17-78	4-17-78	4-24-78	4-24-78	4-24-78
CONVEYOR SETTING:	20-	20-	17-	17-	18-
FUEL FEED RATE:	550-	550-	472-	472-	498-
(DRY LBS/HR)					
HEAT INPUT RATE:	4948919.	4948919.	4244532.	4244532.	4481258.
(BTU/HR)					
HEAT RELEASE RATE:	494892.	494892.	424453.	424453.	448126.
(BTU/HR-SQFT)					
UNDERFIRE:	12-INCH	12-INCH	12-INCH	12-INCH	12-INCH
OVERFIRE:	6-INCH	6-INCH	6-INCH	6-INCH	6-INCH
PERCENT EX. AIR:	123.	123.	70.	70.	110.

TEMPERATURES (DEGREES F)

T2:	1490.	1495.	1340.	1357.	1343.
T3:	1063.	1063.	1088.	1097.	1098.
T4:	730.	733.	690.	692.	750.
FAN OUTLET:	57.	56.	70.	71.	71.
UNDERGRATE:	143.	145.	412.	405.	410.
OVERFIRE:	143.	145.	303.	308.	329.
AIR HEATER:	163.	165.	518.	521.	500.

PRESSURE DIFFERENTIALS (INCHES WATER)

MAIN ORIFICE:	.5	.3	0.0	0.0	.1
6" VENTURI:	11.1	11.1	.3	.3	.9
12" VENTURI:	.9	.9	1.4	1.4	3.0
3" CONVEYOR:	3.0	3.0	3.0	3.0	3.0
ACROSS GRATE:	1.9	1.9	3.4	3.1	2.9

EXHAUST GAS ANALYSIS (PERCENT)

OXYGEN:	11.7	11.7	8.6	8.6	11.2
CARBON DIOXIDE:	9.1	9.1	12.3	12.3	9.7
CARBON MONOXIDE:	.24	.24	.13	.13	.15
OXIDES OF NITROGEN:	0.0	0.0	0.0	0.0	0.0

AIR FLOW RATES (ACFM)

MAIN:	2225.	2225.	0.	0.	966.
UNDERGRATE:	1006.	1008.	1525.	1528.	2099.
OVERFIRE:	998.	999.	309.	310.	443.

AIR FLOW RATES (SCFM)

MAIN:	2118.	2121.	0.	0.	894.
UNDERGRATE:	795.	793.	767.	766.	1076.
OVERFIRE:	788.	787.	156.	155.	227.
UNDER + OVER:	1583.	1580.	923.	921.	1303.
CALC. BASED ON:	1573.	1573.	1028.	1028.	1341.
FUEL AND EX. AIR					
PERCENT UG:OF	50.450.	50.150.	83.117.	83.117.	83.117.

CARRY OVER DATA

LBS/HR:	23.4	20.4	18.6	19.8	23.1
GR/SCF:	1.736	1.513	2.110	2.247	2.013
PERCENT ASH:	0.	0.	0.	0.	0.
PERCENT COMBUSTIBLE:	0.	0.	0.	0.	0.
LENGTH OF RUN(MIN):	20.	20.	20.	20.	21.
OPACITY:	5.	5.	5.	5.	7.

WEATHER:	RAIN	RAIN	CLOUDY	CLOUDY	CLOUDY
----------	------	------	--------	--------	--------

SRU 1.521 UNTS.

RUN COMPLETE.

WOOD SPECIES: ALDER BARK
 SIZE RANGE: 1" MINUS
 MOISTURE (%): 45.10
 DENSITY (LBS/CU.FT): 30.40

RUN NO:	180.	185.	186.	187.	188.
DATE:	4-24-78	4-26-78	4-26-78	4-26-78	4-26-78
CONVEYOR SETTING:	18.	17.	17.	16.	16.
FUEL FEED RATE: (DRY LBS/HR)	498.	483.	483.	456.	456.
HEAT INPUT RATE: (BTU/HR)	4481258.	4345422.	4345422.	4103070.	4103070.
HEAT RELEASE RATE: (BTU/HR-SQFT)	448126.	434542.	434542.	410307.	410307.
UNDERFIRE:	12-INCH	12-INCH	12-INCH	12-INCH	12-INCH
OVERFIRE:	6-INCH	6-INCH	6-INCH	6-INCH	6-INCH
PERCENT EX. AIR:	110.	56.	56.	75.	75.

TEMPERATURES (DEGREES F)

T2:	1315.	1035.	1033.	1397.	1407.
T3:	1090.	1042.	1065.	1007.	987.
T4:	753.	642.	652.	672.	652.
FAN OUTLET:	71.	61.	60.	61.	62.
UNDERGRATE:	410.	337.	345.	374.	367.
OVERFIRE:	327.	410.	420.	422.	416.
AIR HEATER:	500.	503.	515.	490.	475.

PRESSURE DIFFERENTIALS (INCHES WATER)

MAIN ORIFICE:	.1	0.0	0.0	.1	.1
6" VENTURI:	1.0	5.6	5.6	11.5	11.6
12" VENTURI:	3.0	.5	.5	1.0	1.0
3" CONVEYOR:	3.0	3.0	3.0	3.0	3.0
ACROSS GRATE:	2.7	1.7	1.9	2.0	2.0

EXHAUST GAS ANALYSIS (PERCENT)

OXYGEN:	11.2	7.7	7.7	8.9	8.9
CARBON DIOXIDE:	9.7	13.2	13.2	11.9	11.9
CARBON MONOXIDE:	.15	.14	.14	.17	.17
OXIDES OF NITROGEN:	0.0	0.0	0.0	0.0	0.0

AIR FLOW RATES (ACFM)

MAIN:	966.	0.	0.	804.	804.
UNDERGRATE:	2099.	971.	977.	1300.	1290.
OVERFIRE:	460.	907.	912.	1225.	1221.

AIR FLOW RATES (SCFM)

MAIN:	895.	0.	0.	759.	759.
UNDERGRATE:	1076.	496.	493.	673.	679.
OVERFIRE:	236.	463.	460.	634.	642.
UNDER + OVER:	1312.	959.	953.	1308.	1321.
CALC. BASED ON :	1341.	966.	966.	1023.	1023.
FUEL AND EX. AIR					
PERCENT UG:OF	82.118.	52.148.	52.148.	51.149.	51.149.

CARRY OVER DATA

LBS/HR:	25.3	20.4	21.3	18.3	17.4
GR/SCF:	2.245	2.464	2.572	2.087	1.984
PERCENT ASH:	0.	0.	0.	0.	0.
PERCENT COMBUSTIBLE:	0.	0.	0.	0.	0.
LENGTH OF RUN(MIN):	20.	20.	20.	20.	20.
OPACITY:	7.	5.	5.	5.	3.
WEATHER:	CLOUDY	CLOUDY	CLOUDY	CLOUDY	CLOUDY

SRU 1.522 UNITS.

RUN COMPLETE.

WOOD SPECIES: ALDER BARK
 SIZE RANGE: 1" MINUS
 MOISTURE (%): 43.50
 DENSITY (LBS/CU.FT): 32.40

RUN NO:	189.	190.	193.	195.	196.
DATE:	4-28-78	4-28-78	4-26-78	4-26-78	4-26-78
CONVEYOR SETTING:	22.	22.	18.	18.	18.
FUEL FEED RATE:	603.	603.	510.	510.	510.
(DRY LBS/HR)					
HEAT INPUT RATE:	5426988.	5426988.	4587774.	4587774.	4587774.
(BTU/HR)					
HEAT RELEASE RATE:	542699.	542699.	458777.	458777.	458777.
(BTU/HR-SQFT)					
UNDERFIRE:	12-INCH	12-INCH	6-INCH	6-INCH	6-INCH
OVERFIRE:	6-INCH	6-INCH	12-INCH	12-INCH	12-INCH
PERCENT EX. AIR:	77.	77.	51.	68.	68.

TEMPERATURES (DEGREES F)

T2:	1488.	1463.	1220.	1387.	1398.
T3:	1170.	1178.	1141.	1038.	1059.
T4:	820.	828.	638.	633.	667.
FAN OUTLET:	61.	63.	62.	64.	64.
UNDERGRATE:	353.	357.	366.	363.	380.
OVERFIRE:	415.	424.	375.	385.	408.
AIR HEATER:	525.	533.	470.	432.	459.

PRESSURE DIFFERENTIALS (INCHES WATER)

MAIN ORIFICE:	.1	.1	0.0	.1	.1
6" VENTURI:	12.3	12.4	2.9	5.5	5.4
12" VENTURI:	1.1	1.1	.9	1.7	1.7
3" CONVEYOR:	3.0	3.0	3.0	3.0	3.0
ACROSS GRATE:	1.4	1.5	2.5	1.6	1.6

EXHAUST GAS ANALYSIS (PERCENT)

OXYGEN:	9.1	9.1	7.2	8.4	8.4
CARBON DIOXIDE:	11.7	11.7	13.5	12.4	12.4
CARBON MONOXIDE:	.08	.08	.24	.08	.08
OXIDES OF NITROGEN:	0.0	0.0	0.0	0.0	0.0

AIR FLOW RATES (ACFM)

MAIN:	804.	804.	0.	966.	915.
UNDERGRATE:	1379.	1385.	573.	761.	765.
OVERFIRE:	1282.	1292.	1339.	1694.	1717.

AIR FLOW RATES (SCFM)

MAIN:	760.	756.	0.	907.	859.
UNDERGRATE:	689.	686.	303.	419.	410.
OVERFIRE:	640.	640.	708.	934.	919.
UNDER + OVER:	1329.	1326.	1011.	1354.	1329.
CALC. BASED ON :	1369.	1369.	987.	1098.	1098.
FUEL AND EX. AIR					
PERCENT UG:OF	52.148.	52.148.	30.170.	31.169.	31.169.

CARRY OVER DATA

LBS/HR:	33.6	34.4	16.0	17.4	15.6
GR/SCF:	8.864	2.929	2.127	1.848	1.657
PERCENT ASH:	0.	0.	0.	0.	0.
PERCENT COMBUSTIBLE:	0.	0.	0.	0.	0.
LENGTH OF RUN(MIN):	20.	22.	12.	20.	20.
OPACITY:	15.	15.	5.	5.	5.

WEATHER:	RAIN	RAIN	CLOUDY	CLOUDY	CLOUDY
----------	------	------	--------	--------	--------

SRU 1.542 UNITS.

RUN COMPLETE.

WOOD SPECIES: ALDER BARK
 SIZE RANGE: 1" MINUS
 MOISTURE (%): 46.10
 DENSITY (LBS/CU.FT): 31.70

RUN NO:	197.	198.	0.	0.	0.
DATE:	4-26-78	4-26-78			
CONVEYOR SETTING:	21.	21.	0.	0.	0.
FUEL FEED RATE:	591.	591.	0.	0.	0.
(DRY LBS/HR)					
HEAT INPUT RATE:	5314830.	5314830.	0.	0.	0.
(BTU/HR)					
HEAT RELEASE RATE:	531483.	531483.	0.	0.	0.
(BTU/HR-SQFT)					
UNDERFIRE:	6-INCH	6-INCH	0-INCH	0-INCH	0-INCH
OVERFIRE:	12-INCH	12-INCH	0-INCH	0-INCH	0-INCH
PERCENT EX. AIR:	48.	48.	0.	0.	0.

TEMPERATURES (DEGREES F)

T2:	1502.	1502.	0.	0.	0.
T3:	1140.	1148.	0.	0.	0.
T4:	710.	733.	0.	0.	0.
FAN OUTLET:	64.	64.	0.	0.	0.
UNDERGRATE:	398.	401.	0.	0.	0.
OVERFIRE:	428.	430.	0.	0.	0.
AIR HEATER:	485.	498.	0.	0.	0.

PRESSURE DIFFERENTIALS (INCHES WATER)

MAIN ORIFICE:	.1	-.1	0.0	0.0	0.0
6" VENTURI:	5.7	5.6	0.0	0.0	0.0
12" VENTURI:	1.8	1.8	0.0	0.0	0.0
3" CONVEYOR:	3.0	3.0	0.0	0.0	0.0
ACROSS GRATE:	1.5	1.5	0.0	0.0	0.0

EXHAUST GAS ANALYSIS (PERCENT)

OXYGEN:	6.8	6.8	0.0	0.0	0.0
CARBON DIOXIDE:	14.1	14.1	0.0	0.0	0.0
CARBON MONOXIDE:	.04	.04	0.00	0.00	0.00
OXIDES OF NITROGEN:	0.0	0.0	0.0	0.0	0.0

AIR FLOW RATES (ACFM)

MAIN:	966.	861.	0.	0.	0.
UNDERGRATE:	796.	795.	0.	0.	0.
OVERFIRE:	1781.	1792.	0.	0.	0.

AIR FLOW RATES (SCFM)

MAIN:	906.	809.	0.	0.	0.
UNDERGRATE:	415.	408.	0.	0.	0.
OVERFIRE:	927.	980.	0.	0.	0.
UNDER + OVER:	1342.	1329.	0.	0.	0.
CALC. BASED ON :	1121.	1121.	0.	0.	0.
FUEL AND EX. AIR					
PERCENT UG:OF	31.169.	31.169.	0.1 0.	0.1 0.	0.1 0.

CARRY OVER DATA

LBS/HR:	23.4	21.6	0.0	0.0	0.0
GR/SCF:	2.436	2.248	0.000	0.000	0.000
PERCENT ASH:	0.	0.	0.	0.	0.
PERCENT COMBUSTIBLE:	0.	0.	0.	0.	0.
LENGTH OF RUN(MIN):	20.	20.	0.	0.	0.
OPACITY:	5.	5.	0.	0.	0.

WEATHER: CLOUDY CLOUDY

SRU 1.387 UNITS.

RUN COMPLETE.

GRAPHS OF COLLECTED DATA

PLOT OF CARRYOVER RATE VS. LEVEL OF EXCESS AIR
AS MEASURED DOWNSTREAM FROM THE COMBUSTION PROCESS

TEST NOS.: 129-136
SPECIES: Alder Bark
SIZE: 1" Minus
MOISTURE: 45%

FUEL FEED RATE (DRY LBS/HR): 585
HEAT RELEASE RATE (BTU/HR): 5.2×10^5
INLET AIR TEMPERATURE (°F): 368
PERCENT UNDERGRATE AIR: 82

PLOT OF CARRYOVER RATE VS. LEVEL OF EXCESS AIR
AS MEASURED DOWNSTREAM FROM THE COMBUSTION PROCESS

TEST NOS.: 137-144
SPECIES: Alder Bark
SIZE: 1" Minus
MOISTURE: 44%

FUEL FEED RATE (DRY LBS/HR): 492
HEAT RELEASE RATE (BTU/HR): 4.4×10^5
INLET AIR TEMPERATURE (°F): 359
PERCENT UNDERGRATE AIR: 50

PLOT OF CARRYOVER RATE VS. LEVEL OF EXCESS AIR
AS MEASURED DOWNSTREAM FROM THE COMBUSTION PROCESS

TEST NOS.: 137, 143 & 144
SPECIES: Alder Bark
SIZE: 1" Minus
MOISTURE: 47%

FUEL FEED RATE (DRY LBS/HR): 564
HEAT RELEASE RATE (BTU/HR): 5.1×10^5
INLET AIR TEMPERATURE (°F): 677
PERCENT UNDERGRATE AIR: 51

PLOT OF CARRYOVER RATE VS. LEVEL OF EXCESS AIR
AS MEASURED DOWNSTREAM FROM THE COMBUSTION PROCESS

TEST NOS.: 147-152 & 193-196
SPECIES: Alder Bark
SIZE: 1" Minus
MOISTURE: 50%

FUEL FEED RATE (DRY LBS/HR): 490
HEAT RELEASE RATE (BTU/HR): 4.4×10^5
INLET AIR TEMPERATURE (°F): 388
PERCENT UNDERGRATE AIR: 30

PLOT OF CARRYOVER RATE VS. LEVEL OF EXCESS AIR
AS MEASURED DOWNSTREAM FROM THE COMBUSTION PROCESS

TEST NOS.: 155-160
SPECIES: Alder Bark
SIZE: 1" Minus
MOISTURE: 45%

FUEL FEED RATE (DRY LBS/HR): 541
HEAT RELEASE RATE (BTU/HR): 4.8×10^5
INLET AIR TEMPERATURE (°F): 128
PERCENT UNDERGRATE AIR: 30

PLOT OF CARRYOVER RATE VS. LEVEL OF EXCESS AIR
AS MEASURED DOWNSTREAM FROM THE COMBUSTION PROCESS

TEST NOS.: 161-168
SPECIES: Alder Bark
SIZE: 1" Minus
MOISTURE: 44%

FUEL FEED RATE (DRY LBS/HR): 567
HEAT RELEASE RATE (BTU/HR): 5.1×10^5
INLET AIR TEMPERATURE (°F): 121
PERCENT UNDERGRATE AIR: 80

PLOT OF CARRYOVER RATE VS. LEVEL OF EXCESS AIR
AS MEASURED DOWNSTREAM FROM THE COMBUSTION PROCESS

TEST NOS.: 171-176
SPECIES: Alder Bark
SIZE: 1" Minus
MOISTURE: 44%

FUEL FEED RATE (DRY LBS/HR): 567
HEAT RELEASE RATE (BTU/HR): 5.1×10^5
INLET AIR TEMPERATURE (°F): 136
PERCENT UNDERGRATE AIR: 50

PLOT OF CARRYOVER RATE VS. LEVEL OF EXCESS AIR
AS MEASURED DOWNSTREAM FROM THE COMBUSTION PROCESS

TEST NOS.: 177-180
SPECIES: Alder Bark
SIZE: 1" Minus
MOISTURE: 45%

FUEL FEED RATE (DRY LBS/HR): 472
HEAT RELEASE RATE (BTU/HR): 4.2×10^5
INLET AIR TEMPERATURE (°F): 409
PERCENT UNDERGRATE AIR: 82

PLOT OF CARRYOVER RATE VS. LEVEL OF EXCESS AIR
AS MEASURED DOWNSTREAM FROM THE COMBUSTION PROCESS

TEST NOS.: 185-188
SPECIES: Alder Bark
SIZE: 1" Minus
MOISTURE: 45%

FUEL FEED RATE (DRY LBS/HR): 483
HEAT RELEASE RATE (BTU/HR): 4.3×10^5
INLET AIR TEMPERATURE (°F): 356
PERCENT UNDERGRATE AIR: 52

PLOT OF CARRYOVER RATE VS. LEVEL OF EXCESS AIR
AS MEASURED DOWNSTREAM FROM THE COMBUSTION PROCESS

TEST NOS.: 189 & 190
SPECIES: Alder Bark
SIZE: 1" Minus
MOISTURE: 46%

FUEL FEED RATE (DRY LBS/HR): 603
HEAT RELEASE RATE (BTU/HR): 5.4×10^5
INLET AIR TEMPERATURE (°F): 355
PERCENT UNDERGRATE AIR: 52

PLOT OF CARRYOVER RATE VS. LEVEL OF EXCESS AIR
AS MEASURED DOWNSTREAM FROM THE COMBUSTION PROCESS

TEST NOS.: 193, 195 & 196
SPECIES: Alder Bark
SIZE: 1" Minus
MOISTURE: 46%

FUEL FEED RATE (DRY LBS/HR): 510
HEAT RELEASE RATE (BTU/HR): 4.5×10^5
INLET AIR TEMPERATURE (°F): 369
PERCENT UNDERGRATE AIR: 32

PLOT OF CARRYOVER RATE VS. LEVEL OF EXCESS AIR
AS MEASURED DOWNSTREAM FROM THE COMBUSTION PROCESS

TEST NOS.: 197 & 198
SPECIES: Alder Bark
SIZE: 1" Minus
MOISTURE: 46%

FUEL FEED RATE (DRY LBS/HR): 591
HEAT RELEASE RATE (BTU/HR): 5.3×10^5
INLET AIR TEMPERATURE (°F): 399
PERCENT UNDERGRATE AIR: 31

- ——— CARRYOVER VS. LB-AIR/LB-FUEL
- ▲ — — — MEAN PARTICLE SIZE VS. LB-AIR/LB-FUEL
- — · — % COMBUSTIBLE MATERIAL VS. LB-AIR/LB-FUEL

ALDER BARK

- CARRYOVER VS. LB-AIR/LB-FUEL
- - - MEAN PARTICLE SIZE VS. LB-AIR/LB-FUEL
- - - % COMBUSTIBLE MATERIAL VS. LB-AIR/LB-FUEL

ALDER BARK
RUNS: 129-152
AVERAGE TEMPERATURE - 369°F

———— CARRYOVER VS. LB-AIR/LB-FUEL
- - - - MEAN PARTICLE SIZE VS. LB-AIR/LB-FUEL
- . - . % COMBUSTIBLE MATERIAL VS. LB-AIR/LB-FUEL

ALDER BARK
RUNS: 155-176
AVERAGE TEMPERATURE - 128°F

—— CARRYOVER VS. LB-AIR/LB-FUEL

- - - MEAN PARTICLE SIZE VS. LB-AIR/LB-FUEL

— · — % COMBUSTIBLE MATERIAL VS. LB-AIR/LB-FUEL

ALDER BARK
RUNS: 177-198
AVERAGE TEMPERATURE - 379° F

SPECIES: ALDER BARK RUNS (129 TO 152) &
177 TO 198
 TEMPERATURE: HIGH AVERAGE MOISTURE CONTENT: 44.9%

PLOT OF THE COMPLETENESS OF THE COMBUSTION REACTION EXPRESSED AS THE LBS OF NON-COMBUSTED FUEL CARRIED OUT OF THE FURNACE/LB OF DRY FUEL ENTERING VERSUS THE AIR:FUEL RATIO AT THE GRATE

SPECIES: ALDER BARKRUNS 155 TO 176TEMPERATURE: LOWAVERAGE MOISTURE CONTENT: 44.9%

PLOT OF THE COMPLETENESS OF THE COMBUSTION REACTION EXPRESSED AS THE LBS OF NON-COMBUSTED FUEL CARRIED OUT OF THE FURNACE/LB OF DRY FUEL ENTERING VERSUS THE AIR:FUEL RATIO AT THE GRATE

SPECIES: ALDER BARK RUNS 129 TO 151

TEMPERATURE: HIGH AVERAGE MOISTURE CONTENT: 46%

PLOT OF THE COMPLETENESS OF THE COMBUSTION REACTION EXPRESSED AS THE LBS OF NON-COMBUSTED FUEL CARRIED OUT OF THE FURNACE/LB OF DRY FUEL ENTERING VERSUS THE AIR:FUEL RATIO AT THE GRATE

SPECIES: ALDER BARKRUNS 155 TO 175TEMPERATURE: LOWAVERAGE MOISTURE CONTENT: 46%

PLOT OF THE COMPLETENESS OF THE COMBUSTION REACTION EXPRESSED AS THE LBS OF NON-COMBUSTED FUEL CARRIED OUT OF THE FURNACE/LB OF DRY FUEL ENTERING VERSUS THE AIR:FUEL RATIO AT THE GRATE

SPECIES: ALDER BARKRUNS 177 TO 197TEMPERATURE: HIGHAVERAGE MOISTURE CONTENT: 46%

PLOT OF THE COMPLETENESS OF THE COMBUSTION REACTION EXPRESSED AS THE LBS OF NON-COMBUSTED FUEL CARRIED OUT OF THE FURNACE/LB OF DRY FUEL ENTERING VERSUS THE AIR:FUEL RATIO AT THE GRATE

SPECIES: ALDER BARKRUNS: 129 TO 151TEMPERATURE: HIGHAVERAGE MOISTURE CONTENT: 46% (%)

LBS OF INORGANIC ASH/LB OF DRY FUEL (EXPRESSED AS PERCENT)

PLOT OF THE PERCENT OF REMOVAL OF INORGANIC ASH VS. AIR:FUEL AT THE GRATE

SPECIES: ALDER BARKRUNS: 155 TO 175TEMPERATURE: LOWAVERAGE MOISTURE CONTENT: 46% (%)

LBS OF INORGANIC ASH/LB OF DRY FUEL (EXPRESSED AS PERCENT)

PLOT OF THE PERCENT OF REMOVAL OF INORGANIC ASH VS. AIR:FUEL AT THE GRATE

SPECIES: ALDER BARKRUNS: 177 TO 197TEMPERATURE: HIGHAVERAGE MOISTURE CONTENT: 46% (%)

LBS OF INORGANIC ASH/LB OF DRY FUEL (EXPRESSED AS PERCENT)

PLOT OF THE PERCENT OF REMOVAL OF INORGANIC ASH VS. AIR:FUEL AT THE GRATE

CARRYOVER RATE VS. EXCESS AIR
VARYING UNDERGRATE VS. OVERFIRE AIR RATIO

Alder Bark

CARRYOVER RATE VS. EXCESS AIR
VARYING UNDERGRATE VS. OVERFIRE AIR RATIO

Alder Bark

CARRYOVER RATE VS. EXCESS AIR
VARYING INLET AIR TEMPERATURES

Alder Bark

CARRYOVER RATE VS. EXCESS AIR
VARYING INLET AIR TEMPERATURES

Alder Bark

CARRYOVER RATE VS. EXCESS AIR
VARYING INLET AIR TEMPERATURES

Alder Bark

FUEL ANALYSIS DATA AND GRAPHS

DATA FORM - RAW FUEL ANALYSES

FUEL: ALDER BARK

COMBUSTIBLE CONTENT ANALYSES

	SAMPLE NO. 1	SAMPLE NO. 2	SAMPLE NO. 3
INITIAL SAMPLE + CRUCIBLE WT (gm)	<u>39.29</u>	<u>40.52</u>	<u>40.11</u>
CRUCIBLE WT (gm)	<u>26.36</u>	<u>26.46</u>	<u>26.44</u>
SAMPLE WT (gm)	<u>12.93</u>	<u>14.06</u>	<u>13.67</u>
FINAL SAMPLE + CRUCIBLE WT (gm)	<u>27.08</u>	<u>27.27</u>	<u>27.27</u>
CRUCIBLE WT (gm)	<u>26.36</u>	<u>26.46</u>	<u>26.44</u>
ASH WT (gm)	<u>0.72</u> % <u>5.57</u>	<u>0.81</u> % <u>5.76</u>	<u>0.83</u> % <u>6.07</u>
COMBUSTIBLE CARBON WT (gm)	<u>12.21</u> % <u>94.43</u>	<u>13.25</u> % <u>94.24</u>	<u>12.84</u> % <u>93.93</u>

AVERAGE % INORGANIC ASH: 5.80AVERAGE % COMBUSTIBLE CARBON: 94.20

SIZE AND DENSITY ANALYSES

SIZE (mm)	SAMPLE + PAN (gm)	PAN TARE (gm)	SAMPLE WT (gm)	CUMULATIVE WT (gm)	CUMU- LATIVE %	VOLUME (cc)	DENSITY (gm/cc)
26.67							
18.85							
9.423	44.68	17.12	27.56	320.33		75	0.367
4.760	125.92	17.12	108.80	292.77	91.40	245	0.440
3.327	53.71	17.12	36.59	183.97	57.43	90	0.407
2.000	69.14	17.12	52.02	147.38	46.01	116	0.448
1.000	77.49	17.12	60.37	95.36	29.77	130	0.464
0.500	46.18	17.12	29.06	34.99	10.92	65	0.447
PAN	23.05	17.12	5.93	5.93	1.85	16	0.371

SIZE AND DENSITY ANALYSES

ALDER BARK

SIZE (mm)	SAMPLE + PAN (gm)	PAN TARE (gm)	SAMPLE WT (gm)	CUMULATIVE WT (gm)	CUMU- LATIVE %	VOLUME (cc)	DENSITY (gm/cc)
26.67							
18.85							
9.423	76.73	17.12	59.61	291.71		140	0.426
4.760	88.92	17.12	71.80	232.10	79.57	165	0.435
3.327	49.01	17.12	31.89	160.30	54.95	78	0.409
2.000	61.32	17.12	44.20	128.41	44.02	95	0.465
1.000	72.03	17.12	54.91	84.21	28.87	113	0.486
0.500	42.76	17.12	25.64	29.30	10.04	55	0.466
PAN	20.78	17.12	3.66	3.66	1.25	9	0.407

SIZE AND DENSITY ANALYSES

ALDER BARK

SIZE (mm)	SAMPLE + PAN (gm)	PAN TARE (gm)	SAMPLE WT (gm)	CUMULATIVE WT (gm)	CUMU- LATIVE %	VOLUME (cc)	DENSITY (gm/cc)
26.67							
18.85							
9.423	95.05	17.12	77.93	334.27		170	0.458
4.760	119.71	17.12	102.59	256.34	76.69	235	0.437
3.327	53.03	17.12	35.91	153.75	46.00	85	0.422
2.000	59.28	17.12	42.16	117.84	35.25	90	0.468
1.000	65.93	17.12	48.81	75.68	22.64	95	0.514
0.500	41.01	17.12	23.89	26.87	8.04	52	0.459
PAN	20.10	17.12	2.98	2.98	0.89	7	0.428

PLOT OF PARTICLE SIZE DISTRIBUTION

ALDER BARK

RUN NUMBER: 1

PLOT OF PARTICLE DENSITY VERSUS GEOMETRIC MEAN SIZE

ALDER BARK

RUN NUMBER: J

△ = Density of material collected in pan, i.e. particles less than 0.500mm.

PLOT OF PARTICLE SIZE DISTRIBUTION

ALDER BARK

RUN NUMBER: 2

PLOT OF PARTICLE DENSITY VERSUS GEOMETRIC MEAN SIZE

ALDER BARK

RUN NUMBER: 2

▲ = Density of material collected in pan, i.e. particles less than 0.500mm.

PLOT OF PARTICLE SIZE DISTRIBUTION

ALDER BARK

RUN NUMBER: 3

PLOT OF PARTICLE DENSITY VERSUS GEOMETRIC MEAN SIZE

ALDER BARK

RUN NUMBER: 3

▲ = Density of material collected in pan, i.e. particles less than 0.500mm.

ASH ANALYSIS DATA AND GRAPHS

DATA FORM - WOOD ASH ANALYSES

RUN NO: 129

COMBUSTABLE CONTENT ANALYSES

	SAMPLE NO. 1	SAMPLE NO. 2
INITIAL SAMPLE + CRUCIBLE WT (gm)	<u>32.14</u>	<u>31.25</u>
CRUCIBLE WT (gm)	<u>27.61</u>	<u>26.91</u>
SAMPLE WT (gm)	<u>4.53</u>	<u>4.34</u>
FINAL SAMPLE + CRUCIBLE WT (gm)	<u>30.70</u>	<u>29.90</u>
CRUCIBLE WT (gm)	<u>27.61</u>	<u>26.91</u>
ASH WT (gm)	<u>3.09</u> % <u>68.21</u>	<u>2.99</u> % <u>68.89</u>
COMBUSTABLE CARBON WT (gm)	<u>1.44</u> % <u>31.79</u>	<u>1.35</u> % <u>31.11</u>

AVERAGE % INORGANIC ASH: 68.55 AVERAGE % COMBUSTABLE CARBON: 31.45

SIZE AND DENSITY ANALYSES

SIZE (mm)	SAMPLE + PAN (gm)	PAN TARE (gm)	SAMPLE WT (gm)	CUMULATIVE WT (gm)	CUMULATIVE %	VOLUME (cc)	DENSITY (gm/cc)
--------------	-------------------------	---------------------	----------------------	--------------------------	-----------------	----------------	--------------------

2.000							
1.000	32.81	17.33	15.88	137.59		1.50	0.106
.500	45.97	17.33	28.64	121.71	88.46	2.14	0.134
.250	29.36	17.28	12.08	93.07	67.64	66	0.183
.125	31.51	17.28	14.23	80.99	58.86	38	0.374
.063	36.51	17.28	19.23	66.76	48.52	50	0.385
.045	26.98	17.28	9.70	47.53	34.54	29	0.334
PAN	55.11	17.28	37.83	37.83	27.49	107	0.354

DATA FORM - WOOD ASH ANALYSES

RUN NO: 131

COMBUSTABLE CONTENT ANALYSES

	SAMPLE NO. 1	SAMPLE NO. 2
INITIAL SAMPLE + CRUCIBLE WT (gm)	<u>30.26</u>	<u>29.78</u>
CRUCIBLE WT (gm)	<u>28.59</u>	<u>28.20</u>
SAMPLE WT (gm)	<u>1.67</u>	<u>1.58</u>
FINAL SAMPLE + CRUCIBLE WT (gm)	<u>28.71</u>	<u>28.30</u>
CRUCIBLE WT (gm)	<u>28.59</u>	<u>28.20</u>
ASH WT (gm)	<u>0.12</u> % <u>7.19</u>	<u>0.10</u> % <u>6.33</u>
COMBUSTABLE CARBON WT (gm)	<u>1.55</u> % <u>92.81</u>	<u>1.48</u> % <u>93.67</u>

 AVERAGE % INORGANIC ASH: 6.76 AVERAGE % COMBUSTABLE CARBON: 93.24?

* * * * *

SIZE AND DENSITY ANALYSES

SIZE (mm)	SAMPLE + PAN (gm)	PAN TARE (gm)	SAMPLE WT (gm)	CUMULATIVE WT (gm)	CUMULATIVE % %	VOLUME (cc)	DENSITY (gm/cc)
4.000	17.78	17.19	0.59	51.20		10	0.059
2.000	37.60	17.19	20.41	50.61	98.85	286	0.071
1.000	35.29	17.19	18.10	30.20	58.98	240	0.075
.500	23.64	17.19	6.45	12.10	23.63	83	0.078
.250	18.67	17.19	1.48	5.65	11.04	13	0.114
.125	18.56	17.19	1.37	4.17	8.14	6	0.228
.063	18.48	17.19	1.29	2.80	5.47	7	0.184
.045	17.94	17.19	0.75	1.51	2.95	4	0.188
PAN	17.95	17.19	0.76	0.76	1.48	5	0.152

DATE: 4-7-78 80

ALDER BARK

DATA FORM - WOOD ASH ANALYSES

RUN NO: 131

COMBUSTABLE CONTENT ANALYSES

	SAMPLE NO. 1	SAMPLE NO. 2
INITIAL SAMPLE + CRUCIBLE WT (gm)	<u>31.72</u>	<u>31.53</u>
CRUCIBLE WT (gm)	<u>27.84</u>	<u>27.55</u>
SAMPLE WT (gm)	<u>3.88</u>	<u>3.98</u>
FINAL SAMPLE + CRUCIBLE WT (gm)	<u>31.26</u>	<u>30.97</u>
CRUCIBLE WT (gm)	<u>27.84</u>	<u>27.55</u>
ASH WT (gm)	<u>3.42</u> % <u>88.14</u>	<u>3.42</u> % <u>85.93</u>
COMBUSTABLE CARBON WT (gm)	<u>0.46</u> % <u>11.86</u>	<u>0.56</u> % <u>14.07</u>

AVERAGE % INORGANIC ASH: 87.04 AVERAGE % COMBUSTABLE CARBON: 12.97

SIZE AND DENSITY ANALYSES

SIZE (mm)	SAMPLE + PAN (gm)	PAN TARE (gm)	SAMPLE WT (gm)	CUMULATIVE WT (gm)	CUMULATIVE %	VOLUME (cc)	DENSITY (gm/cc)
--------------	-------------------------	---------------------	----------------------	--------------------------	-----------------	----------------	--------------------

2.000							
1.000	25.06	17.27	7.79	245.14		82	0.095
.500	37.81	17.27	20.54	237.35	96.82	150	0.137
.250	36.13	17.28	18.85	216.81	88.44	67	0.281
.125	53.10	17.27	35.83	197.96	80.75	65	0.551
.063	63.57	17.27	46.30	162.13	66.14	114	0.406
.045	45.75	17.27	28.48	115.83	47.25	79	0.361
PAN	104.62	17.27	87.35	87.35	35.63	194	0.450

DATE: 4-5-78 81
ALDER SAWDUST
DOUG. FIR PLANE
SHAVINGS

DATA FORM - WOOD ASH ANALYSES

RUN NO: 131

COMBUSTABLE CONTENT ANALYSES

	SAMPLE NO. 1	SAMPLE NO. 2
INITIAL SAMPLE + CRUCIBLE WT (gm)	<u>28.68</u>	<u>30.70</u>
CRUCIBLE WT (gm)	<u>26.48</u>	<u>28.53</u>
SAMPLE WT (gm)	<u>2.20</u>	<u>2.17</u>
FINAL SAMPLE + CRUCIBLE WT (gm)	<u>27.25</u>	<u>29.26</u>
CRUCIBLE WT (gm)	<u>26.48</u>	<u>28.53</u>
ASH WT (gm)	<u>0.77</u> % <u>35.0</u>	<u>0.73</u> % <u>33.64</u>
COMBUSTABLE CARBON WT (gm)	<u>1.43</u> % <u>65.0</u>	<u>1.44</u> % <u>66.36</u>

AVERAGE % INORGANIC ASH: 34.32

AVERAGE % COMBUSTABLE CARBON: 65.68

SIZE AND DENSITY ANALYSES

SIZE (mm)	SAMPLE + PAN (gm)	PAN TARE (gm)	SAMPLE WT (gm)	CUMULATIVE WT (gm)	CUMULATIVE % %	VOLUME (cc)	DENSITY (gm/cc)
--------------	-------------------------	---------------------	----------------------	--------------------------	----------------------	----------------	--------------------

2.000							
1.000	30.08	17.33	12.75	68.81		204	0.063
.500	40.89	17.33	23.56	56.06	81.47	290	0.081
.250	27.34	17.33	10.01	32.50	47.23	84	0.119
.125	25.52	17.33	8.19	22.49	32.68	32	0.256
.063	24.44	17.33	7.11	14.30	20.78	19	0.374
.045	19.12	17.33	1.79	7.19	10.45	5	0.358
PAN	22.73	17.33	5.40	5.40	7.85	14	0.386

DATA FORM - WOOD ASH ANALYSES

RUN NO: 133

COMBUSTABLE CONTENT ANALYSES

	SAMPLE NO. 1	SAMPLE NO. 2
INITIAL SAMPLE + CRUCIBLE WT (gm)	<u>35.02</u>	<u>36.85</u>
CRUCIBLE WT (gm)	<u>28.30</u>	<u>30.12</u>
SAMPLE WT (gm)	<u>6.72</u>	<u>6.73</u>
FINAL SAMPLE + CRUCIBLE WT (gm)	<u>34.69</u>	<u>36.49</u>
CRUCIBLE WT (gm)	<u>28.30</u>	<u>30.12</u>
ASH WT (gm)	<u>6.39</u> % <u>95.09</u>	<u>6.37</u> % <u>94.65</u>
COMBUSTABLE CARBON WT (gm)	<u>0.33</u> % <u>4.91</u>	<u>0.36</u> % <u>5.35</u>

AVERAGE % INORGANIC ASH: 94.87 AVERAGE % COMBUSTABLE CARBON: 5.13

SIZE AND DENSITY ANALYSES

SIZE (mm)	SAMPLE + PAN (gm)	PAN TARE (gm)	SAMPLE WT (gm)	CUMULATIVE WT (gm)	CUMULATIVE % %	VOLUME (cc)	DENSITY (gm/cc)
--------------	-------------------------	---------------------	----------------------	--------------------------	----------------------	----------------	--------------------

2.000							
1.000	22.74	17.33	5.41	200.32		48	0.113
.500	27.13	17.33	9.80	194.91	97.30	66	0.148
.250	29.80	17.33	12.47	185.11	92.41	29	0.430
.125	45.34	17.33	28.01	172.64	86.18	42	0.667
.063	57.52	17.33	40.19	144.63	72.20	83	0.484
.045	40.69	17.33	23.36	104.44	52.14	56	0.417
PAN	98.41	17.33	81.08	81.08	40.48	168	0.483

DATA FORM - WOOD ASH ANALYSES

RUN NO: 135

COMBUSTABLE CONTENT ANALYSES

	SAMPLE NO. 1	SAMPLE NO. 2
INITIAL SAMPLE + CRUCIBLE WT (gm)	<u>38.15</u>	<u>36.76</u>
CRUCIBLE WT (gm)	<u>29.60</u>	<u>28.22</u>
SAMPLE WT (gm)	<u>8.55</u>	<u>8.54</u>
FINAL SAMPLE + CRUCIBLE WT (gm)	<u>37.95</u>	<u>36.56</u>
CRUCIBLE WT (gm)	<u>29.60</u>	<u>28.22</u>
ASH WT (gm)	<u>8.35</u> % <u>97.66</u>	<u>8.34</u> % <u>97.66</u>
COMBUSTABLE CARBON WT (gm)	<u>0.20</u> % <u>2.34</u>	<u>0.20</u> % <u>2.34</u>

AVERAGE % INORGANIC ASH: 97.66 AVERAGE % COMBUSTABLE CARBON: 2.34

SIZE AND DENSITY ANALYSES

SIZE (mm)	SAMPLE + PAN (gm)	PAN TARE (gm)	SAMPLE WT (gm)	CUMULATIVE WT (gm)	CUMULATIVE %	VOLUME (cc)	DENSITY (gm/cc)
--------------	-------------------------	---------------------	----------------------	--------------------------	-----------------	----------------	--------------------

2.000							
1.000	<u>21.40</u>	<u>17.23</u>	<u>4.17</u>	<u>237.74</u>		<u>35</u>	<u>0.119</u>
.500	<u>26.86</u>	<u>17.23</u>	<u>9.63</u>	<u>233.57</u>	<u>98.25</u>	<u>56</u>	<u>0.172</u>
.250	<u>31.28</u>	<u>17.23</u>	<u>14.05</u>	<u>223.94</u>	<u>94.20</u>	<u>25</u>	<u>0.562</u>
.125	<u>49.26</u>	<u>17.23</u>	<u>32.03</u>	<u>209.89</u>	<u>88.29</u>	<u>46</u>	<u>0.696</u>
.063	<u>66.75</u>	<u>17.23</u>	<u>49.52</u>	<u>177.86</u>	<u>74.81</u>	<u>100</u>	<u>0.495</u>
.045	<u>46.00</u>	<u>17.23</u>	<u>28.77</u>	<u>128.34</u>	<u>53.98</u>	<u>65</u>	<u>0.443</u>
PAN	<u>116.80</u>	<u>17.23</u>	<u>99.57</u>	<u>99.57</u>	<u>41.88</u>	<u>230</u>	<u>0.433</u>

DATA FORM - WOOD ASH ANALYSESRUN NO: 137

COMBUSTABLE CONTENT ANALYSES

	SAMPLE NO. 1	SAMPLE NO. 2
INITIAL SAMPLE + CRUCIBLE WT (gm)	<u>33.27</u>	<u>32.98</u>
CRUCIBLE WT (gm)	<u>28.98</u>	<u>28.53</u>
SAMPLE WT (gm)	<u>4.29</u>	<u>4.45</u>
FINAL SAMPLE + CRUCIBLE WT (gm)	<u>31.15</u>	<u>30.71</u>
CRUCIBLE WT (gm)	<u>28.98</u>	<u>28.53</u>
ASH WT (gm)	<u>2.17</u> % <u>50.58</u>	<u>2.18</u> % <u>48.99</u>
COMBUSTABLE CARBON WT (gm)	<u>2.12</u> % <u>49.42</u>	<u>2.27</u> % <u>51.01</u>

AVERAGE % INORGANIC ASH: 49.79 AVERAGE % COMBUSTABLE CARBON: 50.22

SIZE AND DENSITY ANALYSES

SIZE (mm)	SAMPLE + PAN (gm)	PAN TARE (gm)	SAMPLE WT (gm)	CUMULATIVE WT (gm)	CUMULATIVE % %	VOLUME (cc)	DENSITY (gm/cc)
--------------	-------------------------	---------------------	----------------------	--------------------------	----------------------	----------------	--------------------

2.000							
1.000	29.90	17.23	12.67	127.68		123	0.103
.500	70.25	17.23	53.02	115.01	90.08	378	0.140
.250	33.31	17.23	16.08	61.99	48.55	88	0.183
.125	30.22	17.23	12.99	45.91	35.96	35	0.371
.063	29.05	17.23	11.82	32.92	25.78	30	0.394
.045	21.88	17.23	4.65	21.10	16.53	12	0.388
PAN	33.68	17.23	16.45	16.45	12.88	45	0.366

DATA FORM - WOOD ASH ANALYSES

RUN NO: 137

(Repeat)

COMBUSTABLE CONTENT ANALYSES

	SAMPLE NO. 1	SAMPLE NO. 2
INITIAL SAMPLE + CRUCIBLE WT (gm)	<u>31.33</u>	<u>30.74</u>
CRUCIBLE WT (gm)	<u>29.36</u>	<u>28.89</u>
SAMPLE WT (gm)	<u>1.97</u>	<u>1.85</u>
FINAL SAMPLE + CRUCIBLE WT (gm)	<u>30.45</u>	<u>29.08</u>
CRUCIBLE WT (gm)	<u>29.36</u>	<u>28.89</u>
ASH WT (gm)	<u>1.09</u> % <u>55.33</u>	<u>0.99</u> % <u>53.51</u>
COMBUSTABLE CARBON WT (gm)	<u>0.88</u> % <u>44.67</u>	<u>0.86</u> % <u>46.49</u>

AVERAGE % INORGANIC ASH: 54.42AVERAGE % COMBUSTABLE CARBON: 45.58

SIZE AND DENSITY ANALYSES

SIZE (mm)	SAMPLE + PAN (gm)	PAN TARE (gm)	SAMPLE WT (gm)	CUMULATIVE WT (gm)	CUMULATIVE % %	VOLUME (cc)	DENSITY (gm/cc)
--------------	-------------------------	---------------------	----------------------	--------------------------	----------------------	----------------	--------------------

2.000							
1.000	31.41	17.33	14.08	116.85		153	0.092
.500	58.89	17.33	41.56	102.77	87.95	348	0.119
.250	30.21	17.33	12.88	61.21	52.38	85	0.152
.125	28.37	17.33	11.04	48.33	41.36	35	0.315
.063	30.04	17.33	12.71	37.29	31.91	37	0.344
.045	22.48	17.33	5.15	24.58	21.04	17	0.303
PAN	36.76	17.33	19.43	19.43	16.63	59	0.329

DATA FORM - WOOD ASH ANALYSES

RUN NO: 139

COMBUSTABLE CONTENT ANALYSES

	SAMPLE NO. 1	SAMPLE NO. 2
INITIAL SAMPLE + CRUCIBLE WT (gm)	<u>30.72</u>	<u>32.80</u>
CRUCIBLE WT (gm)	<u>27.88</u>	<u>30.07</u>
SAMPLE WT (gm)	<u>2.84</u>	<u>2.73</u>
FINAL SAMPLE + CRUCIBLE WT (gm)	<u>30.20</u>	<u>32.35</u>
CRUCIBLE WT (gm)	<u>27.88</u>	<u>30.07</u>
ASH WT (gm)	<u>2.32</u> % <u>81.69</u>	<u>2.28</u> % <u>83.54</u>
COMBUSTABLE CARBON WT (gm)	<u>0.52</u> % <u>18.31</u>	<u>0.45</u> % <u>16.48</u>

AVERAGE % INORGANIC ASH: 82.61 AVERAGE % COMBUSTABLE CARBON: 17.40

SIZE AND DENSITY ANALYSES

SIZE (mm)	SAMPLE + PAN (gm)	PAN TARE (gm)	SAMPLE WT (gm)	CUMULATIVE WT (gm)	CUMULATIVE % %	VOLUME (cc)	DENSITY (gm/cc)
--------------	-------------------------	---------------------	----------------------	--------------------------	----------------------	----------------	--------------------

2.000							
1.000	24.01	17.32	6.69	163.18		96	0.070
.500	40.34	17.34	23.00	156.49	95.90	212	0.108
.250	31.04	17.34	13.70	133.49	81.81	90	0.152
.125	37.99	17.34	20.65	119.79	73.41	63	0.328
.063	48.36	17.34	31.02	99.14	60.75	102	0.304
.045	35.74	17.34	18.40	68.12	41.75	70	0.263
PAN	67.05	17.32	49.72	49.72	30.47	149	0.334

DATA FORM - WOOD ASH ANALYSES

RUN NO: 142

COMBUSTABLE CONTENT ANALYSES

	SAMPLE NO. 1	SAMPLE NO. 2
INITIAL SAMPLE + CRUCIBLE WT (gm)	<u>36.98</u>	<u>35.74</u>
CRUCIBLE WT (gm)	<u>28.30</u>	<u>27.17</u>
SAMPLE WT (gm)	<u>8.68</u>	<u>8.57</u>
FINAL SAMPLE + CRUCIBLE WT (gm)	<u>36.81</u>	<u>35.59</u>
CRUCIBLE WT (gm)	<u>28.30</u>	<u>27.17</u>
ASH WT (gm)	<u>8.51</u> % <u>98.04</u>	<u>8.42</u> % <u>98.25</u>
COMBUSTABLE CARBON WT (gm)	<u>0.17</u> % <u>1.96</u>	<u>0.15</u> % <u>1.75</u>
AVERAGE % INORGANIC ASH:	<u>98.15</u>	AVERAGE % COMBUSTABLE CARBON: <u>1.66</u>

SIZE AND DENSITY ANALYSES

SIZE (mm)	SAMPLE + PAN (gm)	PAN TARE (gm)	SAMPLE WT (gm)	CUMULATIVE WT (gm)	CUMULATIVE % %	VOLUME (cc)	DENSITY (gm/cc)
--------------	-------------------------	---------------------	----------------------	--------------------------	----------------------	----------------	--------------------

2.000							
1.000	19.79	17.33	2.46	256.72		32	0.077
.500	29.03	17.33	11.70	254.26	99.04	85	0.136
.250	40.93	17.33	23.60	242.56	94.48	65	0.363
.125	70.57	17.33	53.24	218.96	85.29	98	0.543
.063	77.33	17.33	60.00	165.72	64.55	142	0.423
.045	49.72	17.33	32.39	105.72	41.18	103	0.314
PAN	90.66	17.33	73.33	73.33	28.56	202	0.363

DATA FORM - WOOD ASH ANALYSES

RUN NO: 143

COMBUSTABLE CONTENT ANALYSES

	SAMPLE NO. 1	SAMPLE NO. 2
INITIAL SAMPLE + CRUCIBLE WT (gm)	<u>37.10</u>	<u>37.50</u>
CRUCIBLE WT (gm)	<u>27.61</u>	<u>27.55</u>
SAMPLE WT (gm)	<u>9.49</u>	<u>9.95</u>
FINAL SAMPLE + CRUCIBLE WT (gm)	<u>36.84</u>	<u>37.29</u>
CRUCIBLE WT (gm)	<u>27.61</u>	<u>27.55</u>
ASH WT (gm)	<u>9.23</u> % <u>97.26</u>	<u>9.74</u> % <u>97.89</u>
COMBUSTABLE CARBON WT (gm)	<u>0.26</u> % <u>2.74</u>	<u>0.21</u> % <u>2.11</u>

AVERAGE % INORGANIC ASH: 97.58AVERAGE % COMBUSTABLE CARBON: 2.43

SIZE AND DENSITY ANALYSES

SIZE (mm)	SAMPLE + PAN (gm)	PAN TARE (gm)	SAMPLE WT (gm)	CUMULATIVE WT (gm)	CUMULATIVE % %	VOLUME (cc)	DENSITY (gm/cc)
--------------	-------------------------	---------------------	----------------------	--------------------------	----------------------	----------------	--------------------

2.000							
1.000	20.60	17.33	3.27	285.87		34	0.096
.500	26.62	17.34	9.28	282.60	98.86	60	0.155
.250	37.44	17.34	20.10	273.32	95.61	40	0.503
.125	65.28	17.34	47.94	253.22	88.58	85	0.564
.063	81.53	17.34	64.19	205.28	71.81	174	0.369
.045	57.30	17.33	39.97	141.09	49.35	130	0.307
PAN	118.45	17.33	101.12	101.12	35.37	273	0.370

DATA FORM - WOOD ASH ANALYSES

RUN NO: 147

COMBUSTABLE CONTENT ANALYSES

	SAMPLE NO. 1	SAMPLE NO. 2
INITIAL SAMPLE + CRUCIBLE WT (gm)	<u>36.21</u>	<u>34.07</u>
CRUCIBLE WT (gm)	<u>28.46</u>	<u>26.60</u>
SAMPLE WT (gm)	<u>7.75</u>	<u>7.47</u>
FINAL SAMPLE + CRUCIBLE WT (gm)	<u>34.92</u>	<u>32.83</u>
CRUCIBLE WT (gm)	<u>28.46</u>	<u>26.60</u>
ASH WT (gm)	<u>6.46</u> % <u>83.35</u>	<u>6.23</u> % <u>83.40</u>
COMBUSTABLE CARBON WT (gm)	<u>1.29</u> % <u>16.65</u>	<u>1.24</u> % <u>16.60</u>

AVERAGE % INORGANIC ASH: 83.38 AVERAGE % COMBUSTABLE CARBON: 16.63

SIZE AND DENSITY ANALYSES

SIZE (mm)	SAMPLE + PAN (gm)	PAN TARE (gm)	SAMPLE WT (gm)	CUMULATIVE WT (gm)	CUMULATIVE % %	VOLUME (cc)	DENSITY (gm/cc)
--------------	-------------------------	---------------------	----------------------	--------------------------	----------------------	----------------	--------------------

2.000							
1.000	20.98	17.18	3.80	225.75		47	0.081
.500	42.83	17.19	25.64	221.95	98.32	185	0.139
.250	42.88	17.19	25.69	196.31	86.96	125	0.441
.125	52.02	17.19	34.83	170.62	75.58	84	0.415
.063	60.78	17.19	43.59	135.79	60.15	109	0.400
.045	40.05	17.19	22.86	92.20	40.84	62	0.369
PAN	86.53	17.19	69.34	69.34	30.75	165	0.307

DATA FORM - WOOD ASH ANALYSES

RUN NO: 149

COMBUSTABLE CONTENT ANALYSES

	SAMPLE NO. 1	SAMPLE NO. 2
INITIAL SAMPLE + CRUCIBLE WT (gm)	<u>35.65</u>	<u>36.18</u>
CRUCIBLE WT (gm)	<u>27.62</u>	<u>28.23</u>
SAMPLE WT (gm)	<u>8.03</u>	<u>7.95</u>
FINAL SAMPLE + CRUCIBLE WT (gm)	<u>35.24</u>	<u>35.74</u>
CRUCIBLE WT (gm)	<u>27.62</u>	<u>28.23</u>
ASH WT (gm)	<u>7.62</u> % <u>94.69</u>	<u>7.51</u> % <u>94.47</u>
COMBUSTABLE CARBON WT (gm)	<u>0.41</u> % <u>5.11</u>	<u>0.44</u> % <u>5.53</u>
AVERAGE % INORGANIC ASH:	<u>94.68</u>	AVERAGE % COMBUSTABLE CARBON: <u>5.32</u>

SIZE AND DENSITY ANALYSES

SIZE (mm)	SAMPLE + PAN (gm)	PAN TARE (gm)	SAMPLE WT (gm)	CUMULATIVE WT (gm)	CUMULATIVE %	VOLUME (cc)	DENSITY (gm/cc)
--------------	-------------------------	---------------------	----------------------	--------------------------	-----------------	----------------	--------------------

2.000							
1.000	<u>19.69</u>	<u>17.19</u>	<u>2.50</u>	<u>241.48</u>		<u>29</u>	<u>0.086</u>
.500	<u>27.90</u>	<u>17.19</u>	<u>10.71</u>	<u>238.98</u>	<u>98.96</u>	<u>80</u>	<u>0.134</u>
.250	<u>34.52</u>	<u>17.19</u>	<u>17.33</u>	<u>228.27</u>	<u>94.53</u>	<u>56</u>	<u>0.309</u>
.125	<u>60.65</u>	<u>17.19</u>	<u>43.46</u>	<u>210.94</u>	<u>87.08</u>	<u>78</u>	<u>0.557</u>
.063	<u>75.94</u>	<u>17.19</u>	<u>58.75</u>	<u>167.48</u>	<u>69.36</u>	<u>129</u>	<u>0.455</u>
.045	<u>48.37</u>	<u>17.19</u>	<u>31.18</u>	<u>108.73</u>	<u>45.03</u>	<u>77</u>	<u>0.405</u>
PAN	<u>94.74</u>	<u>17.19</u>	<u>77.55</u>	<u>77.55</u>	<u>32.11</u>	<u>182</u>	<u>0.426</u>

DATA FORM - WOOD ASH ANALYSES

RUN NO: 151

COMBUSTABLE CONTENT ANALYSES

	SAMPLE NO. 1	SAMPLE NO. 2
INITIAL SAMPLE + CRUCIBLE WT (gm)	<u>36.31</u>	<u>38.46</u>
CRUCIBLE WT (gm)	<u>27.62</u>	<u>29.87</u>
SAMPLE WT (gm)	<u>8.69</u>	<u>8.59</u>
FINAL SAMPLE + CRUCIBLE WT (gm)	<u>36.16</u>	<u>38.16</u>
CRUCIBLE WT (gm)	<u>27.62</u>	<u>29.87</u>
ASH WT (gm)	<u>8.54</u> % <u>98.27</u>	<u>8.29</u> % <u>96.51</u>
COMBUSTABLE CARBON WT (gm)	<u>0.15</u> % <u>1.73</u>	<u>0.30</u> % <u>3.49</u>
AVERAGE % INORGANIC ASH:	<u>97.39</u>	AVERAGE % COMBUSTABLE CARBON: <u>2.61</u>

SIZE AND DENSITY ANALYSES

SIZE (mm)	SAMPLE + PAN (gm)	PAN TARE (gm)	SAMPLE WT (gm)	CUMULATIVE WT (gm)	CUMULATIVE % %	VOLUME (cc)	DENSITY (gm/cc)
--------------	-------------------------	---------------------	----------------------	--------------------------	----------------------	----------------	--------------------

2.000							
1.000	<u>17.78</u>	<u>17.19</u>	<u>0.59</u>	<u>289.97</u>		<u>7</u>	<u>0.084</u>
.500	<u>19.22</u>	<u>17.19</u>	<u>2.03</u>	<u>289.38</u>	<u>99.80</u>	<u>15</u>	<u>0.135</u>
.250	<u>24.48</u>	<u>17.19</u>	<u>7.29</u>	<u>287.35</u>	<u>99.10</u>	<u>15</u>	<u>0.486</u>
.125	<u>52.41</u>	<u>17.19</u>	<u>35.22</u>	<u>280.06</u>	<u>96.58</u>	<u>54</u>	<u>0.652</u>
.063	<u>85.99</u>	<u>17.19</u>	<u>68.80</u>	<u>244.84</u>	<u>84.44</u>	<u>137</u>	<u>0.502</u>
.045	<u>64.97</u>	<u>17.19</u>	<u>47.78</u>	<u>176.04</u>	<u>60.71</u>	<u>109</u>	<u>0.438</u>
PAN	<u>145.45</u>	<u>17.19</u>	<u>128.26</u>	<u>128.26</u>	<u>44.23</u>	<u>314</u>	<u>0.408</u>

DATA FORM - WOOD ASH ANALYSES

RUN NO: 155

COMBUSTABLE CONTENT ANALYSES

	SAMPLE NO. 1	SAMPLE NO. 2
INITIAL SAMPLE + CRUCIBLE WT (gm)	<u>34.53</u>	<u>35.80</u>
CRUCIBLE WT (gm)	<u>29.01</u>	<u>30.11</u>
SAMPLE WT (gm)	<u>5.52</u>	<u>5.69</u>
FINAL SAMPLE + CRUCIBLE WT (gm)	<u>32.66</u>	<u>33.89</u>
CRUCIBLE WT (gm)	<u>29.01</u>	<u>30.11</u>
ASH WT (gm)	<u>3.65</u> % <u>66.12</u>	<u>3.78</u> % <u>66.43</u>
COMBUSTABLE CARBON WT (gm)	<u>1.87</u> % <u>33.88</u>	<u>1.91</u> % <u>33.57</u>

AVERAGE % INORGANIC ASH: 66.28AVERAGE % COMBUSTABLE CARBON: 33.73

SIZE AND DENSITY ANALYSES

SIZE (mm)	SAMPLE + PAN (gm)	PAN TARE (gm)	SAMPLE WT (gm)	CUMULATIVE WT (gm)	CUMULATIVE % %	VOLUME (cc)	DENSITY (gm/cc)
--------------	-------------------------	---------------------	----------------------	--------------------------	----------------------	----------------	--------------------

2.000							
1.000	24.80	17.33	7.47	169.12		83	0.090
.500	63.78	17.33	46.45	161.65	95.58	357	0.130
.250	38.07	17.33	20.74	115.20	68.12	126	0.165
.125	37.39	17.33	20.06	94.46	55.85	50	0.401
.063	39.86	17.33	22.53	74.40	43.99	58	0.388
.045	28.16	17.33	10.83	51.87	30.67	32	0.338
PAN	58.37	17.33	41.04	41.04	24.27	118	0.348

DATA FORM - WOOD ASH ANALYSES

RUN NO: 157

COMBUSTABLE CONTENT ANALYSES

	SAMPLE NO. 1	SAMPLE NO. 2
INITIAL SAMPLE + CRUCIBLE WT (gm)	<u>35.36</u>	<u>35.28</u>
CRUCIBLE WT (gm)	<u>28.47</u>	<u>28.22</u>
SAMPLE WT (gm)	<u>6.89</u>	<u>7.06</u>
FINAL SAMPLE + CRUCIBLE WT (gm)	<u>34.65</u>	<u>34.56</u>
CRUCIBLE WT (gm)	<u>28.47</u>	<u>28.22</u>
ASH WT (gm)	<u>6.18</u> % <u>89.70</u>	<u>6.34</u> % <u>89.80</u>
COMBUSTABLE CARBON WT (gm)	<u>0.71</u> % <u>10.30</u>	<u>0.72</u> % <u>10.20</u>

AVERAGE % INORGANIC ASH: 89.75 AVERAGE % COMBUSTABLE CARBON: 10.25

SIZE AND DENSITY ANALYSES

SIZE (mm)	SAMPLE + PAN (gm)	PAN TARE (gm)	SAMPLE WT (gm)	CUMULATIVE WT (gm)	CUMULATIVE % %	VOLUME (cc)	DENSITY (gm/cc)
--------------	-------------------------	---------------------	----------------------	--------------------------	----------------------	----------------	--------------------

2.000							
1.000	20.37	17.33	3.04	206.09		37	0.082
.500	36.00	17.34	18.66	203.05	98.52	64	0.292
.250	34.66	17.34	17.32	184.39	89.47	104	0.167
.125	49.93	17.34	32.59	167.07	81.07	75	0.435
.063	59.99	17.34	42.65	134.48	65.25	104	0.410
.045	39.27	17.34	21.93	91.83	44.56	71	0.309
PAN	87.24	17.34	69.90	69.90	33.92	194	0.360

DATA FORM - WOOD ASH ANALYSES

RUN NO: 159

COMBUSTABLE CONTENT ANALYSES

	SAMPLE NO. 1	SAMPLE NO. 2
INITIAL SAMPLE + CRUCIBLE WT (gm)	<u>36.16</u>	<u>36.54</u>
CRUCIBLE WT (gm)	<u>26.01</u>	<u>26.90</u>
SAMPLE WT (gm)	<u>10.15</u>	<u>9.64</u>
FINAL SAMPLE + CRUCIBLE WT (gm)	<u>35.77</u>	<u>36.05</u>
CRUCIBLE WT (gm)	<u>26.01</u>	<u>26.90</u>
ASH WT (gm)	<u>9.76</u> % <u>96.16</u>	<u>9.15</u> % <u>94.92</u>
COMBUSTABLE CARBON WT (gm)	<u>0.39</u> % <u>3.84</u>	<u>0.49</u> % <u>5.08</u>

AVERAGE % INORGANIC ASH: 95.54AVERAGE % COMBUSTABLE CARBON: 4.46

SIZE AND DENSITY ANALYSES

SIZE (mm)	SAMPLE + PAN (gm)	PAN TARE (gm)	SAMPLE WT (gm)	CUMULATIVE WT (gm)	CUMULATIVE % %	VOLUME (cc)	DENSITY (gm/cc)
--------------	-------------------------	---------------------	----------------------	--------------------------	----------------------	----------------	--------------------

2.000							
1.000	17.66	17.34	0.32	274.20		2.2	0.145
.500	20.23	17.35	2.88	273.88	99.88	18.4	0.157
.250	30.61	17.34	13.27	271.00	98.83	31.0	0.428
.125	69.83	17.34	52.49	257.73	93.99	78.0	0.673
.063	78.93	17.34	61.59	205.24	74.85	127.0	0.485
.045	49.49	17.34	32.15	143.65	52.39	90.0	0.357
PAN	128.84	17.34	111.50	111.50	40.66	294.0	0.379

DATA FORM - WOOD ASH ANALYSES

RUN NO: 161

COMBUSTABLE CONTENT ANALYSES

	SAMPLE NO. 1	SAMPLE NO. 2
INITIAL SAMPLE + CRUCIBLE WT (gm)	<u>36.50</u>	<u>33.06</u>
CRUCIBLE WT (gm)	<u>31.58</u>	<u>28.21</u>
SAMPLE WT (gm)	<u>4.92</u>	<u>4.85</u>
FINAL SAMPLE + CRUCIBLE WT (gm)	<u>33.99</u>	<u>30.59</u>
CRUCIBLE WT (gm)	<u>31.58</u>	<u>28.21</u>
ASH WT (gm)	<u>2.41</u> % <u>48.98</u>	<u>2.38</u> % <u>49.07</u>
COMBUSTABLE CARBON WT (gm)	<u>2.51</u> % <u>51.02</u>	<u>2.47</u> % <u>50.93</u>

AVERAGE % INORGANIC ASH: 49.03AVERAGE % COMBUSTABLE CARBON: 50.98

* * * * *

SIZE AND DENSITY ANALYSES

SIZE (mm)	SAMPLE + PAN (gm)	PAN TARE (gm)	SAMPLE WT (gm)	CUMULATIVE WT (gm)	CUMULATIVE % %	VOLUME (cc)	DENSITY (gm/cc)
--------------	-------------------------	---------------------	----------------------	--------------------------	----------------------	----------------	--------------------

2.000							
1.000	<u>34.75</u>	<u>17.33</u>	<u>17.42</u>	<u>148.08</u>		<u>151</u>	<u>0.115</u>
.500	<u>78.76</u>	<u>17.33</u>	<u>61.43</u>	<u>130.66</u>	<u>88.24</u>	<u>430</u>	<u>0.143</u>
.250	<u>32.93</u>	<u>17.34</u>	<u>15.59</u>	<u>69.23</u>	<u>46.75</u>	<u>82</u>	<u>0.190</u>
.125	<u>31.61</u>	<u>17.34</u>	<u>14.27</u>	<u>53.64</u>	<u>36.22</u>	<u>36</u>	<u>0.396</u>
.063	<u>29.71</u>	<u>17.34</u>	<u>12.37</u>	<u>39.37</u>	<u>26.59</u>	<u>34</u>	<u>0.364</u>
.045	<u>22.63</u>	<u>17.34</u>	<u>5.29</u>	<u>27.00</u>	<u>18.23</u>	<u>17</u>	<u>0.311</u>
PAN	<u>39.05</u>	<u>17.34</u>	<u>21.71</u>	<u>21.71</u>	<u>14.66</u>	<u>65</u>	<u>0.334</u>

DATA FORM - WOOD ASH ANALYSES

RUN NO: 163

COMBUSTABLE CONTENT ANALYSES

	SAMPLE NO. 1	SAMPLE NO. 2
INITIAL SAMPLE + CRUCIBLE WT (gm)	<u>32.35</u>	<u>35.63</u>
CRUCIBLE WT (gm)	<u>26.72</u>	<u>29.86</u>
SAMPLE WT (gm)	<u>5.63</u>	<u>5.77</u>
FINAL SAMPLE + CRUCIBLE WT (gm)	<u>30.01</u>	<u>33.23</u>
CRUCIBLE WT (gm)	<u>26.72</u>	<u>29.66</u>
ASH WT (gm)	<u>3.29</u> % <u>58.44</u>	<u>3.37</u> % <u>58.4</u>
COMBUSTABLE CARBON WT (gm)	<u>2.34</u> % <u>41.56</u>	<u>2.40</u> % <u>41.59</u>

 AVERAGE % INORGANIC ASH: 58.43 AVERAGE % COMBUSTABLE CARBON: 41.58

* * * * *

SIZE AND DENSITY ANALYSES

SIZE (mm)	SAMPLE + PAN (gm)	PAN TARE (gm)	SAMPLE WT (gm)	CUMULATIVE WT (gm)	CUMULATIVE % %	VOLUME (cc)	DENSITY (gm/cc)
--------------	-------------------------	---------------------	----------------------	--------------------------	----------------------	----------------	--------------------

2.000							
1.000	32.10	17.33	14.77	168.09		129	0.114
.500	76.24	17.33	58.91	153.32	91.21	425	0.139
.250	37.11	17.33	19.78	94.41	56.17	98	0.202
.125	37.99	17.33	20.66	74.63	44.40	44	0.470
.063	34.77	17.33	17.44	53.97	32.11	44	0.396
.045	25.34	17.34	8.00	36.53	21.73	25	0.320
PAN	45.87	17.34	28.53	28.53	16.97	84	0.340

DATA FORM - WOOD ASH ANALYSES

RUN NO: 165

COMBUSTABLE CONTENT ANALYSES

	SAMPLE NO. 1	SAMPLE NO. 2
INITIAL SAMPLE + CRUCIBLE WT (gm)	<u>33.96</u>	<u>34.68</u>
CRUCIBLE WT (gm)	<u>27.85</u>	<u>28.51</u>
SAMPLE WT (gm)	<u>6.11</u>	<u>6.17</u>
FINAL SAMPLE + CRUCIBLE WT (gm)	<u>32.66</u>	<u>33.37</u>
CRUCIBLE WT (gm)	<u>27.85</u>	<u>28.51</u>
ASH WT (gm)	<u>4.81</u> % <u>78.72</u>	<u>4.86</u> % <u>78.77</u>
COMBUSTABLE CARBON WT (gm)	<u>1.30</u> % <u>21.28</u>	<u>1.31</u> % <u>21.23</u>

AVERAGE % INORGANIC ASH: 78.75AVERAGE % COMBUSTABLE CARBON: 21.26

SIZE AND DENSITY ANALYSES

SIZE (mm)	SAMPLE + PAN (gm)	PAN TARE (gm)	SAMPLE WT (gm)	CUMULATIVE WT (gm)	CUMULATIVE % %	VOLUME (cc)	DENSITY (gm/cc)
--------------	-------------------------	---------------------	----------------------	--------------------------	----------------------	----------------	--------------------

2.000							
1.000	25.00	17.33	7.67	180.98		85	0.090
.500	49.39	17.33	32.06	173.31	95.76	249	0.129
.250	33.94	17.33	16.61	141.25	78.05	83	0.200
.125	40.43	17.33	23.10	124.64	68.87	47	0.491
.063	44.90	17.33	27.57	101.54	56.11	69	0.400
.045	32.82	17.33	15.49	73.97	40.87	52	0.298
PAN	75.81	17.33	58.48	58.48	32.31	165	0.354

DATA FORM - WOOD ASH ANALYSES

RUN NO: 167

COMBUSTABLE CONTENT ANALYSES

	SAMPLE NO. 1	SAMPLE NO. 2
INITIAL SAMPLE + CRUCIBLE WT (gm)	<u>37.92</u>	<u>37.51</u>
CRUCIBLE WT (gm)	<u>28.99</u>	<u>28.53</u>
SAMPLE WT (gm)	<u>8.93</u>	<u>8.98</u>
FINAL SAMPLE + CRUCIBLE WT (gm)	<u>37.80</u>	<u>37.27</u>
CRUCIBLE WT (gm)	<u>28.99</u>	<u>28.53</u>
ASH WT (gm)	<u>8.81</u> % <u>98.66</u>	<u>8.74</u> % <u>97.33</u>
COMBUSTABLE CARBON WT (gm)	<u>0.12</u> % <u>1.34</u>	<u>0.24</u> % <u>2.67</u>

AVERAGE % INORGANIC ASH: 98.00AVERAGE % COMBUSTABLE CARBON: 2.01

SIZE AND DENSITY ANALYSES

SIZE (mm)	SAMPLE + PAN (gm)	PAN TARE (gm)	SAMPLE WT (gm)	CUMULATIVE WT (gm)	CUMULATIVE % %	VOLUME (cc)	DENSITY (gm/cc)
--------------	-------------------------	---------------------	----------------------	--------------------------	----------------------	----------------	--------------------

2.000							
1.000	20.07	17.18	2.89	267.06		29	0.100
.500	25.41	17.18	8.23	264.17	98.92	58	0.142
.250	28.40	17.18	11.22	255.94	95.84	30	0.374
.125	50.11	17.18	32.93	244.72	91.63	50	0.659
.063	70.08	17.18	52.90	211.79	79.30	105	0.504
.045	53.37	17.18	36.19	158.89	59.50	86	0.421
PAN	139.88	17.18	122.70	122.70	45.94	265	0.463

DATA FORM - WOOD ASH ANALYSES

RUN NO: 171

COMBUSTABLE CONTENT ANALYSES

	SAMPLE NO. 1	SAMPLE NO. 2
INITIAL SAMPLE + CRUCIBLE WT (gm)	<u>33.14</u>	<u>31.33</u>
CRUCIBLE WT (gm)	<u>28.46</u>	<u>26.60</u>
SAMPLE WT (gm)	<u>4.68</u>	<u>4.73</u>
FINAL SAMPLE + CRUCIBLE WT (gm)	<u>31.72</u>	<u>29.88</u>
CRUCIBLE WT (gm)	<u>28.46</u>	<u>26.60</u>
ASH WT (gm)	<u>3.26</u> % <u>69.66</u>	<u>3.28</u> % <u>69.34</u>
COMBUSTABLE CARBON WT (gm)	<u>1.42</u> % <u>30.34</u>	<u>1.45</u> % <u>30.66</u>

AVERAGE % INORGANIC ASH: 69.50 AVERAGE % COMBUSTABLE CARBON: 30.50

SIZE AND DENSITY ANALYSES

SIZE (mm)	SAMPLE + PAN (gm)	PAN TARE (gm)	SAMPLE WT (gm)	CUMULATIVE WT (gm)	CUMULATIVE %	VOLUME (cc)	DENSITY (gm/cc)
--------------	-------------------------	---------------------	----------------------	--------------------------	-----------------	----------------	--------------------

2.000							
1.000	<u>24.17</u>	<u>17.19</u>	<u>6.98</u>	<u>139.70</u>		<u>86</u>	<u>0.081</u>
.500	<u>51.17</u>	<u>17.18</u>	<u>33.99</u>	<u>132.72</u>	<u>95.00</u>	<u>275</u>	<u>0.124</u>
.250	<u>33.30</u>	<u>17.18</u>	<u>16.12</u>	<u>98.73</u>	<u>70.67</u>	<u>101</u>	<u>0.160</u>
.125	<u>31.97</u>	<u>17.18</u>	<u>14.79</u>	<u>82.61</u>	<u>59.13</u>	<u>40</u>	<u>0.370</u>
.063	<u>37.75</u>	<u>17.18</u>	<u>20.57</u>	<u>67.82</u>	<u>48.55</u>	<u>56</u>	<u>0.367</u>
.045	<u>28.39</u>	<u>17.18</u>	<u>11.21</u>	<u>47.25</u>	<u>33.82</u>	<u>32</u>	<u>0.350</u>
PAN	<u>53.22</u>	<u>17.18</u>	<u>36.04</u>	<u>36.04</u>	<u>25.80</u>	<u>93</u>	<u>0.388</u>

DATA FORM - WOOD ASH ANALYSES

RUN NO: 173

COMBUSTABLE CONTENT ANALYSES

	SAMPLE NO. 1	SAMPLE NO. 2
INITIAL SAMPLE + CRUCIBLE WT (gm)	<u>33.13</u>	<u>33.93</u>
CRUCIBLE WT (gm)	<u>26.74</u>	<u>27.57</u>
SAMPLE WT (gm)	<u>6.39</u>	<u>6.36</u>
FINAL SAMPLE + CRUCIBLE WT (gm)	<u>32.60</u>	<u>33.43</u>
CRUCIBLE WT (gm)	<u>26.74</u>	<u>27.57</u>
ASH WT (gm)	<u>5.86</u> % <u>91.71</u>	<u>5.86</u> % <u>92.14</u>
COMBUSTABLE CARBON WT (gm)	<u>0.53</u> % <u>8.29</u>	<u>0.50</u> % <u>7.86</u>

AVERAGE % INORGANIC ASH: 91.93 AVERAGE % COMBUSTABLE CARBON: 8.08

SIZE AND DENSITY ANALYSES

SIZE (mm)	SAMPLE + PAN (gm)	PAN TARE (gm)	SAMPLE WT (gm)	CUMULATIVE WT (gm)	CUMULATIVE % %	VOLUME (cc)	DENSITY (gm/cc)
--------------	-------------------------	---------------------	----------------------	--------------------------	----------------------	----------------	--------------------

2.000							
1.000	20.36	17.18	3.18	192.95		40	0.080
.500	32.95	17.18	15.77	189.77	98.35	118	0.134
.250	34.09	17.18	16.91	174.00	90.18	70	0.242
.125	47.70	17.18	30.52	157.09	81.41	58	0.526
.063	53.45	17.18	36.27	126.57	65.60	85	0.427
.045	38.37	17.18	21.19	90.30	46.80	57	0.372
PAN	86.29	17.18	69.11	69.11	35.82	168	0.411

DATA FORM - WOOD ASH ANALYSES

RUN NO: 175

COMBUSTABLE CONTENT ANALYSES

	SAMPLE NO. 1	SAMPLE NO. 2
INITIAL SAMPLE + CRUCIBLE WT (gm)	<u>35.98</u>	<u>36.72</u>
CRUCIBLE WT (gm)	<u>26.92</u>	<u>27.62</u>
SAMPLE WT (gm)	<u>9.06</u>	<u>9.01</u>
FINAL SAMPLE + CRUCIBLE WT (gm)	<u>35.72</u>	<u>36.36</u>
CRUCIBLE WT (gm)	<u>26.92</u>	<u>27.62</u>
ASH WT (gm)	<u>8.80</u> % <u>97.13</u>	<u>8.74</u> % <u>97.00</u>
COMBUSTABLE CARBON WT (gm)	<u>0.26</u> % <u>2.87</u>	<u>0.27</u> % <u>3.00</u>

AVERAGE % INORGANIC ASH: 97.07 AVERAGE % COMBUSTABLE CARBON: 2.94

SIZE AND DENSITY ANALYSES

SIZE (mm)	SAMPLE + PAN (gm)	PAN TARE (gm)	SAMPLE WT (gm)	CUMULATIVE WT (gm)	CUMULATIVE % %	VOLUME (cc)	DENSITY (gm/cc)
--------------	-------------------------	---------------------	----------------------	--------------------------	----------------------	----------------	--------------------

2.000							
1.000	<u>19.65</u>	<u>17.22</u>	<u>2.43</u>	<u>268.96</u>		<u>31</u>	<u>0.078</u>
.500	<u>27.96</u>	<u>17.22</u>	<u>10.72</u>	<u>266.53</u>	<u>99.10</u>	<u>63.</u>	<u>0.129</u>
.250	<u>34.53</u>	<u>17.22</u>	<u>17.31</u>	<u>255.81</u>	<u>95.11</u>	<u>57</u>	<u>0.304</u>
.125	<u>63.80</u>	<u>17.22</u>	<u>46.58</u>	<u>238.50</u>	<u>88.67</u>	<u>77</u>	<u>0.605</u>
.063	<u>77.30</u>	<u>17.22</u>	<u>60.08</u>	<u>191.92</u>	<u>71.36</u>	<u>120</u>	<u>0.501</u>
.045	<u>52.70</u>	<u>17.22</u>	<u>35.48</u>	<u>131.84</u>	<u>49.02</u>	<u>80</u>	<u>0.444</u>
PAN	<u>113.58</u>	<u>17.22</u>	<u>96.36</u>	<u>96.36</u>	<u>35.83</u>	<u>220</u>	<u>0.438</u>

DATA FORM - WOOD ASH ANALYSES

RUN NO: 177

COMBUSTABLE CONTENT ANALYSES

	SAMPLE NO. 1	SAMPLE NO. 2
INITIAL SAMPLE + CRUCIBLE WT (gm)	<u>31.48</u>	<u>32.26</u>
CRUCIBLE WT (gm)	<u>26.74</u>	<u>27.56</u>
SAMPLE WT (gm)	<u>4.74</u>	<u>4.70</u>
FINAL SAMPLE + CRUCIBLE WT (gm)	<u>29.78</u>	<u>30.51</u>
CRUCIBLE WT (gm)	<u>26.74</u>	<u>27.56</u>
ASH WT (gm)	<u>3.04</u>	<u>2.95</u>
	% <u>64.14</u>	% <u>62.77</u>
COMBUSTABLE CARBON WT (gm)	<u>1.70</u>	<u>1.75</u>
	% <u>35.86</u>	% <u>37.23</u>

AVERAGE % INORGANIC ASH: 63.47 AVERAGE % COMBUSTABLE CARBON: 36.55

SIZE AND DENSITY ANALYSES

SIZE (mm)	SAMPLE + PAN (gm)	PAN TARE (gm)	SAMPLE WT (gm)	CUMULATIVE WT (gm)	CUMULATIVE % %	VOLUME (cc)	DENSITY (gm/cc)
--------------	-------------------------	---------------------	----------------------	--------------------------	----------------------	----------------	--------------------

2.000							
1.000	33.99	17.19	16.80	137.71		166	0.101
.500	54.60	17.19	37.41	120.91	87.80	292	0.128
.250	31.50	17.19	14.31	83.50	60.63	80	0.179
.125	33.37	17.19	16.18	69.19	50.24	38	0.426
.063	34.62	17.19	17.43	53.01	38.49	46	0.379
.045	26.09	17.19	8.90	35.58	25.84	27	0.330
PAN	43.87	17.19	26.68	26.68	19.37	75	0.356

DATA FORM - WOOD ASH ANALYSES

RUN NO: 179

COMBUSTABLE CONTENT ANALYSES

	SAMPLE NO. 1	SAMPLE NO. 2
INITIAL SAMPLE + CRUCIBLE WT (gm)	<u>35.48</u>	<u>33.41</u>
CRUCIBLE WT (gm)	<u>27.85</u>	<u>25.59</u>
SAMPLE WT (gm)	<u>7.63</u>	<u>7.82</u>
FINAL SAMPLE + CRUCIBLE WT (gm)	<u>35.45</u>	<u>33.34</u>
CRUCIBLE WT (gm)	<u>27.85</u>	<u>25.59</u>
ASH WT (gm)	<u>7.60</u> % <u>99.61</u>	<u>7.75</u> % <u>99.10</u>
COMBUSTABLE CARBON WT (gm)	<u>0.03</u> % <u>0.39</u>	<u>0.07</u> % <u>0.90</u>
AVERAGE % INORGANIC ASH:	<u>99.36</u>	AVERAGE % COMBUSTABLE CARBON: <u>0.65</u>

SIZE AND DENSITY ANALYSES

SIZE (mm)	SAMPLE + PAN (gm)	PAN TARE (gm)	SAMPLE WT (gm)	CUMULATIVE WT (gm)	CUMULATIVE %	VOLUME (cc)	DENSITY (gm/cc)
--------------	-------------------------	---------------------	----------------------	--------------------------	-----------------	----------------	--------------------

2.000							
1.000	20.87	17.19	3.68	230.73		33	0.112
.500	24.97	17.19	7.78	227.05	98.41	50	0.156
.250	27.20	17.19	10.01	219.27	95.03	28	0.358
.125	44.43	17.19	27.24	209.26	90.69	50	0.545
.063	65.48	17.19	48.29	182.02	78.89	103	0.469
.045	46.73	17.19	29.54	133.73	57.96	71	0.416
PAN	121.38	17.19	104.19	104.19	45.16	223	0.467

DATA FORM - WOOD ASH ANALYSES

RUN NO: 185

COMBUSTABLE CONTENT ANALYSES

	SAMPLE NO. 1		SAMPLE NO. 2
INITIAL SAMPLE + CRUCIBLE WT (gm)	<u>36.07</u>		<u>35.75</u>
CRUCIBLE WT (gm)	<u>28.99</u>		<u>28.53</u>
SAMPLE WT (gm)	<u>7.08</u>		<u>7.22</u>
FINAL SAMPLE + CRUCIBLE WT (gm)	<u>35.55</u>		<u>35.12</u>
CRUCIBLE WT (gm)	<u>28.99</u>		<u>28.53</u>
ASH WT (gm)	<u>6.56</u>	% <u>92.66</u>	<u>6.59</u> % <u>91.27</u>
COMBUSTABLE CARBON WT (gm)	<u>0.52</u>	% <u>7.34</u>	<u>0.63</u> % <u>8.73</u>

AVERAGE % INORGANIC ASH: 91.97 AVERAGE % COMBUSTABLE CARBON: 8.04

SIZE AND DENSITY ANALYSES

SIZE (mm)	SAMPLE + PAN (gm)	PAN TARE (gm)	SAMPLE WT (gm)	CUMULATIVE WT (gm)	CUMULATIVE % %	VOLUME (cc)	DENSITY (gm/cc)
--------------	-------------------------	---------------------	----------------------	--------------------------	----------------------	----------------	--------------------

2.000							
1.000	20.64	17.18	3.46	214.52		45	0.077
.500	29.62	17.18	12.44	211.06	98.39	95	0.131
.250	33.89	17.18	16.71	198.62	92.59	68	0.246
.125	48.68	17.19	31.49	181.91	84.80	70	0.450
.063	64.80	17.19	47.61	150.42	70.12	115	0.414
.045	43.59	17.18	26.41	102.81	47.93	68	0.388
PAN	93.59	17.19	76.40	76.40	35.61	175	0.437

DATA FORM - WOOD ASH ANALYSES

RUN NO: 187

COMBUSTABLE CONTENT ANALYSES

	SAMPLE NO. 1	SAMPLE NO. 2
INITIAL SAMPLE + CRUCIBLE WT (gm)	<u>31.30</u>	<u>33.16</u>
CRUCIBLE WT (gm)	<u>26.78</u>	<u>28.63</u>
SAMPLE WT (gm)	<u>4.52</u>	<u>4.53</u>
FINAL SAMPLE + CRUCIBLE WT (gm)	<u>29.03</u>	<u>30.89</u>
CRUCIBLE WT (gm)	<u>26.78</u>	<u>28.63</u>
ASH WT (gm)	<u>2.25</u> % <u>49.78</u>	<u>2.26</u> % <u>49.89</u>
COMBUSTABLE CARBON WT (gm)	<u>2.27</u> % <u>50.22</u>	<u>2.27</u> % <u>50.11</u>

AVERAGE % INORGANIC ASH: 49.84 AVERAGE % COMBUSTABLE CARBON: 50.17

SIZE AND DENSITY ANALYSES

SIZE (mm)	SAMPLE + PAN (gm)	PAN TARE (gm)	SAMPLE WT (gm)	CUMULATIVE WT (gm)	CUMULATIVE % %	VOLUME (cc)	DENSITY (gm/cc)
--------------	-------------------------	---------------------	----------------------	--------------------------	----------------------	----------------	--------------------

2.000							
1.000	31.95	17.19	14.76	136.09		128	0.115
.500	72.97	17.19	55.78	121.33	89.15	377	0.148
.250	36.09	17.19	18.90	65.55	48.17	91	0.208
.125	30.65	17.19	13.46	46.65	34.28	33	0.408
.063	27.86	17.19	10.67	33.19	24.39	28	0.381
.045	21.89	17.19	4.70	22.52	16.55	13	0.362
PAN	35.01	17.19	17.82	17.82	13.09	39	0.457

DATA FORM - WOOD ASH ANALYSES

RUN NO: 189

COMBUSTABLE CONTENT ANALYSES

	SAMPLE NO. 1	SAMPLE NO. 2
INITIAL SAMPLE + CRUCIBLE WT (gm)	<u>36.09</u>	<u>35.52</u>
CRUCIBLE WT (gm)	<u>28.58</u>	<u>28.19</u>
SAMPLE WT (gm)	<u>7.51</u>	<u>7.33</u>
FINAL SAMPLE + CRUCIBLE WT (gm)	<u>35.16</u>	<u>34.64</u>
CRUCIBLE WT (gm)	<u>28.58</u>	<u>28.19</u>
ASH WT (gm)	<u>6.58</u> % <u>87.62</u>	<u>6.45</u> % <u>87.99</u>
COMBUSTABLE CARBON WT (gm)	<u>0.93</u> % <u>12.38</u>	<u>0.88</u> % <u>12.01</u>

AVERAGE % INORGANIC ASH: 87.81 AVERAGE % COMBUSTABLE CARBON: 12.20

SIZE AND DENSITY ANALYSES

SIZE (mm)	SAMPLE + PAN (gm)	PAN TARE (gm)	SAMPLE WT (gm)	CUMULATIVE WT (gm)	CUMULATIVE % %	VOLUME (cc)	DENSITY (gm/cc)
--------------	-------------------------	---------------------	----------------------	--------------------------	----------------------	----------------	--------------------

2.000							
1.000	<u>24.28</u>	<u>17.23</u>	<u>7.05</u>	<u>221.74</u>		<u>62</u>	<u>0.114</u>
.500	<u>35.16</u>	<u>17.23</u>	<u>17.93</u>	<u>214.69</u>	<u>96.82</u>	<u>125</u>	<u>0.143</u>
.250	<u>33.83</u>	<u>17.23</u>	<u>16.60</u>	<u>196.76</u>	<u>88.73</u>	<u>69</u>	<u>0.241</u>
.125	<u>45.04</u>	<u>17.23</u>	<u>27.81</u>	<u>180.16</u>	<u>81.24</u>	<u>55</u>	<u>0.506</u>
.063	<u>58.69</u>	<u>17.23</u>	<u>41.46</u>	<u>152.35</u>	<u>68.71</u>	<u>90</u>	<u>0.461</u>
.045	<u>38.67</u>	<u>17.23</u>	<u>21.44</u>	<u>110.89</u>	<u>50.01</u>	<u>52</u>	<u>0.412</u>
PAN	<u>106.68</u>	<u>17.23</u>	<u>89.45</u>	<u>99.45</u>	<u>40.34</u>	<u>185</u>	<u>0.484</u>

DATA FORM - WOOD ASH ANALYSESRUN NO: 193

COMBUSTABLE CONTENT ANALYSES

	SAMPLE NO. 1	SAMPLE NO. 2
INITIAL SAMPLE + CRUCIBLE WT (gm)	<u>33.93</u>	<u>33.27</u>
CRUCIBLE WT (gm)	<u>28.48</u>	<u>28.23</u>
SAMPLE WT (gm)	<u>5.45</u>	<u>5.04</u>
FINAL SAMPLE + CRUCIBLE WT (gm)	<u>31.39</u>	<u>30.91</u>
CRUCIBLE WT (gm)	<u>28.48</u>	<u>28.23</u>
ASH WT (gm)	<u>2.91</u> % <u>53.39</u>	<u>2.68</u> % <u>53.17</u>
COMBUSTABLE CARBON WT (gm)	<u>2.54</u> % <u>46.61</u>	<u>2.36</u> % <u>46.83</u>

AVERAGE % INORGANIC ASH: 53.28 AVERAGE % COMBUSTABLE CARBON: 46.72

SIZE AND DENSITY ANALYSES

SIZE (mm)	SAMPLE + PAN (gm)	PAN TARE (gm)	SAMPLE WT (gm)	CUMULATIVE WT (gm)	CUMULATIVE % %	VOLUME (cc)	DENSITY (gm/cc)
--------------	-------------------------	---------------------	----------------------	--------------------------	----------------------	----------------	--------------------

2.000							
1.000	27.87	17.19	10.68	156.04		100	0.107
.500	67.09	17.18	49.91	145.36	93.16	334	0.149
.250	41.11	17.18	23.93	95.45	61.17	125	0.191
.125	36.32	17.18	19.14	71.52	45.83	55	0.348
.063	34.56	17.18	17.38	52.38	33.57	45	0.386
.045	24.95	17.18	7.77	35.00	22.43	23	0.334
PAN	44.41	17.18	27.23	27.23	77.45	64	0.425

DATA FORM - WOOD ASH ANALYSES

RUN NO: 197

COMBUSTABLE CONTENT ANALYSES

	SAMPLE NO. 1	SAMPLE NO. 2
INITIAL SAMPLE + CRUCIBLE WT (gm)	<u>34.68</u>	<u>33.00</u>
CRUCIBLE WT (gm)	<u>28.62</u>	<u>26.92</u>
SAMPLE WT (gm)	<u>6.06</u>	<u>6.08</u>
FINAL SAMPLE + CRUCIBLE WT (gm)	<u>33.04</u>	<u>31.37</u>
CRUCIBLE WT (gm)	<u>28.62</u>	<u>26.92</u>
ASH WT (gm)	<u>4.42</u> % <u>72.94</u>	<u>4.45</u> % <u>73.19</u>
COMBUSTABLE CARBON WT (gm)	<u>1.64</u> % <u>27.06</u>	<u>1.63</u> % <u>26.81</u>

AVERAGE % INORGANIC ASH: 73.07 AVERAGE % COMBUSTABLE CARBON: 26.94

SIZE AND DENSITY ANALYSES

SIZE (mm)	SAMPLE + PAN (gm)	PAN TARE (gm)	SAMPLE WT (gm)	CUMULATIVE WT (gm)	CUMULATIVE % %	VOLUME (cc)	DENSITY (gm/cc)
--------------	-------------------------	---------------------	----------------------	--------------------------	----------------------	----------------	--------------------

2.000							
1.000	26.25	17.19	9.06	182.92		95	0.095
.500	51.30	17.19	34.11	173.86	95.05	264	0.129
.250	36.23	17.19	19.04	139.75	76.40	108	0.176
.125	38.87	17.19	21.68	120.71	65.99	52	0.417
.063	46.60	17.19	29.41	99.03	54.14	68	0.433
.045	32.07	17.19	14.88	69.62	38.06	40	0.372
PAN	71.93	17.19	54.74	54.74	29.93	140	0.391

PLOT OF PARTICLE SIZE DISTRIBUTION--COLLECTED ASH

109

ALDER BARK

RUN NUMBER: 129

PLOT OF PARTICLE DENSITY VERSUS GEOMETRIC MEAN SIZE

ALDER BARK

RUN NUMBER: 129

▲ = Density of material collected in pan, i.e. particles less than 0.045 mm.

PLOT OF PARTICLE SIZE DISTRIBUTION--COLLECTED ASH

ALDER BARK

RUN NUMBER: 131

PLOT OF PARTICLE DENSITY VERSUS GEOMETRIC MEAN SIZE

ALDER BARK

RUN NUMBER: 131

▲ = Density of material collected in pan, i.e. particles less than 0.045 mm.

PLOT OF PARTICLE SIZE DISTRIBUTION--COLLECTED ASH

113

ALDER BARK

RUN NUMBER: 131

DATE: 4-7-78

PLOT OF PARTICLE DENSITY VERSUS GEOMETRIC MEAN SIZE

ALDER BARK

RUN NUMBER: 131

DATE: 4-7-78

▲ = Density of material collected in pan, i.e. particles less than 0.045mm.

PLOT OF PARTICLE SIZE DISTRIBUTION--COLLECTED ASH

ALDER SAWDUST;
DOUGLAS FIR PLANER SHAVINGS

RUN NUMBER: 131

DATE: 4-5-78

PLOT OF PARTICLE DENSITY VERSUS GEOMETRIC MEAN SIZE

ALDER SAWDUST;

DOUGLAS FIR PLANER SHAVINGS

RUN NUMBER: 131

DATE: 4-5-78

▲ = Density of material collected in pan, i.e. particles less than 0.045 mm.

PLOT OF PARTICLE SIZE DISTRIBUTION--COLLECTED ASH

117

ALDER BARK

RUN NUMBER: 133

PLOT OF PARTICLE DENSITY VERSUS GEOMETRIC MEAN SIZE

ALDER BARK

RUN NUMBER: 133

▲ = Density of material collected in pan, i.e. particles less than 0.045mm.

PLOT OF PARTICLE SIZE DISTRIBUTION--COLLECTED ASH

ALDER BARK

RUN NUMBER: 135

PLOT OF PARTICLE DENSITY VERSUS GEOMETRIC MEAN SIZE

ALDER BARK

RUN NUMBER: 135

▲ = Density of material collected in pan, i.e. particles less than 0.045mm.

PLOT OF PARTICLE SIZE DISTRIBUTION--COLLECTED ASH

ALDER BARK

RUN NUMBER: 137

PLOT OF PARTICLE DENSITY VERSUS GEOMETRIC MEAN SIZE

ALDER BARK

RUN NUMBER: 137

▲ = Density of material collected in pan, i.e. particles less than 0.045 mm.

PLOT OF PARTICLE SIZE DISTRIBUTION--COLLECTED ASH

ALDER BARK

RUN NUMBER: 137 (REPEAT)

PLOT OF PARTICLE DENSITY VERSUS GEOMETRIC MEAN SIZE

ALDER BARK

RUN NUMBER: 137 (REPEAT)

▲ = Density of material collected in pan, i.e. particles less than 0.045 mm.

PLOT OF PARTICLE SIZE DISTRIBUTION--COLLECTED ASH

125

ALDER BARK

RUN NUMBER: 139

PLOT OF PARTICLE DENSITY VERSUS GEOMETRIC MEAN SIZE

ALDER BARK

RUN NUMBER: 139

▲ = Density of material collected in pan, i.e. particles less than 0.045 mm.

PLOT OF PARTICLE SIZE DISTRIBUTION--COLLECTED ASH

ALDER BARK

RUN NUMBER: 142

PLOT OF PARTICLE DENSITY VERSUS GEOMETRIC MEAN SIZE

ALDER BARK

RUN NUMBER: 142

▲ = Density of material collected in pan, i.e. particles less than 0.045mm.

PLOT OF PARTICLE SIZE DISTRIBUTION--COLLECTED ASH

ALDER BARK

RUN NUMBER: 143

PLOT OF PARTICLE DENSITY VERSUS GEOMETRIC MEAN SIZE

ALDER BARK

RUN NUMBER: 143

▲ = Density of material collected in pan, i.e. particles less than 0.045 mm.

PLOT OF PARTICLE SIZE DISTRIBUTION--COLLECTED ASH

ALDER BARK

RUN NUMBER: 147

PLOT OF PARTICLE DENSITY VERSUS GEOMETRIC MEAN SIZE

ALDER BARK

RUN NUMBER: 147

▲ = Density of material collected in pan, i.e. particles less than 0.045mm.

PLOT OF PARTICLE SIZE DISTRIBUTION--COLLECTED ASH

ALDER BARK

RUN NUMBER: 149

PLOT OF PARTICLE DENSITY VERSUS GEOMETRIC MEAN SIZE

ALDER BARK

RUN NUMBER: 149

▲ = Density of material collected in pan, i.e. particles less than 0.045 mm.

PLOT OF PARTICLE SIZE DISTRIBUTION--COLLECTED ASH

135

ALDER BARK

RUN NUMBER: 151

PLOT OF PARTICLE DENSITY VERSUS GEOMETRIC MEAN SIZE

ALDER BARK

RUN NUMBER: 151

▲ = Density of material collected in pan, i.e. particles less than 0.043mm.

PLOT OF PARTICLE SIZE DISTRIBUTION--COLLECTED ASH

ALDER BARK

RUN NUMBER: 155

PLOT OF PARTICLE DENSITY VERSUS GEOMETRIC MEAN SIZE

ALDER BARK

RUN NUMBER: 155

▲ = Density of material collected in pan, i.e. particles less than 0.045 mm.

PLOT OF PARTICLE SIZE DISTRIBUTION--COLLECTED ASH

ALDER BARK

RUN NUMBER: 157

PLOT OF PARTICLE DENSITY VERSUS GEOMETRIC MEAN SIZE

ALDER BARK

RUN NUMBER: 157

▲ = Density of material collected in pan, i.e. particles less than 0.045mm.

PLOT OF PARTICLE SIZE DISTRIBUTION--COLLECTED ASH

ALDER BARK

RUN NUMBER: 159

PLOT OF PARTICLE DENSITY VERSUS GEOMETRIC MEAN SIZE

ALDER BARK

RUN NUMBER: 159

▲ = Density of material collected in pan, i.e. particles less than 0.045mm.

PLOT OF PARTICLE SIZE DISTRIBUTION--COLLECTED ASH

ALDER BARK

RUN NUMBER: 161

PLOT OF PARTICLE DENSITY VERSUS GEOMETRIC MEAN SIZE

ALDER BARK

RUN NUMBER: 161

▲ = Density of material collected in pan, i.e. particles less than 0.045mm.

PLOT OF PARTICLE SIZE DISTRIBUTION--COLLECTED ASH

ALDER BARK

RUN NUMBER: 163

PLOT OF PARTICLE DENSITY VERSUS GEOMETRIC MEAN SIZE

ALDER BARK

RUN NUMBER: 163

▲ = Density of material collected in pan, i.e. particles less than 0.045 mm.

PLOT OF PARTICLE SIZE DISTRIBUTION--COLLECTED ASH

ALDER BARK

RUN NUMBER: 165

PLOT OF PARTICLE DENSITY VERSUS GEOMETRIC MEAN SIZE

ALDER BARK

RUN NUMBER: 165

▲ = Density of material collected in pan, i.e. particles less than 0.045 mm.

PLOT OF PARTICLE SIZE DISTRIBUTION--COLLECTED ASH

ALDER BARK

RUN NUMBER: 167

PLOT OF PARTICLE DENSITY VERSUS GEOMETRIC MEAN SIZE

ALDER BARK

RUN NUMBER: 167

▲ = Density of material collected in pan, i.e. particles less than 0.045 mm.

PLOT OF PARTICLE SIZE DISTRIBUTION--COLLECTED ASH

151

ALDER BARK

RUN NUMBER: 171

PLOT OF PARTICLE DENSITY VERSUS GEOMETRIC MEAN SIZE

ALDER BARK

RUN NUMBER: 171

▲ = Density of material collected in pan, i.e. particles less than 0.045mm.

PLOT OF PARTICLE SIZE DISTRIBUTION--COLLECTED ASH

ALDER BARK

RUN NUMBER: 173

PLOT OF PARTICLE DENSITY VERSUS GEOMETRIC MEAN SIZE

ALDER BARK

RUN NUMBER: 173

▲ = Density of material collected in pan, i.e. particles less than 0.045 mm.

PLOT OF PARTICLE SIZE DISTRIBUTION--COLLECTED ASH

155

ALDER BARK

RUN NUMBER: 175

PLOT OF PARTICLE DENSITY VERSUS GEOMETRIC MEAN SIZE

ALDER BARK

RUN NUMBER: 175

▲ = Density of material collected in pan, i.e. particles less than 0.045 mm.

PLOT OF PARTICLE SIZE DISTRIBUTION--COLLECTED ASH

157

ALDER BARK

RUN NUMBER: 177

PLOT OF PARTICLE DENSITY VERSUS GEOMETRIC MEAN SIZE

ALDER BARK

RUN NUMBER: 177

▲ = Density of material collected in pan, i.e. particles less than 0.045 mm.

PLOT OF PARTICLE SIZE DISTRIBUTION--COLLECTED ASH

159

ALDER BARK

RUN NUMBER: 179

PLOT OF PARTICLE DENSITY VERSUS GEOMETRIC MEAN SIZE

ALDER BARK

RUN NUMBER: 179

▲ = Density of material collected in pan, i.e. particles less than 0.045 mm.

PLOT OF PARTICLE SIZE DISTRIBUTION--COLLECTED ASH

161

ALDER BARK

RUN NUMBER: 185

PLOT OF PARTICLE DENSITY VERSUS GEOMETRIC MEAN SIZE

ALDER BARK

RUN NUMBER: 185

▲ = Density of material collected in pan, i.e. particles less than 0.045 mm.

PLOT OF PARTICLE SIZE DISTRIBUTION--COLLECTED ASH

ALDER BARK

RUN NUMBER: 187

PLOT OF PARTICLE DENSITY VERSUS GEOMETRIC MEAN SIZE

ALDER BARK

RUN NUMBER: 187

▲ = Density of material collected in pan, i.e. particles less than 0.045mm.

PLOT OF PARTICLE SIZE DISTRIBUTION--COLLECTED ASH

165

ALDER BARK

RUN NUMBER: 189

PLOT OF PARTICLE DENSITY VERSUS GEOMETRIC MEAN SIZE

ALDER BARK

RUN NUMBER: 189

▲ = Density of material collected in pan, i.e. particles less than 0.045 mm.

PLOT OF PARTICLE SIZE DISTRIBUTION--COLLECTED ASH

167

ALDER BARK

RUN NUMBER: 193

PLOT OF PARTICLE DENSITY VERSUS GEOMETRIC MEAN SIZE

ALDER BARK

RUN NUMBER: 193

▲ = Density of material collected in pan, i.e. particles less than 0.045 mm.

PLOT OF PARTICLE SIZE DISTRIBUTION--COLLECTED ASH

169

ALDER BARK

RUN NUMBER: 197

PLOT OF PARTICLE DENSITY VERSUS GEOMETRIC MEAN SIZE

ALDER BARK

RUN NUMBER: 197

▲ = Density of material collected in pan, i.e. particles less than 0.045 mm.

COMBUSTIBLE CONTENT VS. SIZE OF ASH

DATA FORM - WOOD ASH ANALYSES

RUN NO: 151

COMBUSTABLE CONTENT ANALYSES

FUEL: ALDER
BARK

	SAMPLE NO. 1	SAMPLE NO. 2
INITIAL SAMPLE + CRUCIBLE WT (gm)	_____	_____
CRUCIBLE WT (gm)	_____	_____
SAMPLE WT (gm)	_____	_____
FINAL SAMPLE + CRUCIBLE WT (gm)	_____	_____
CRUCIBLE WT (gm)	_____	_____
ASH WT (gm)	_____ %	_____ %
COMBUSTABLE CARBON WT (gm)	_____ %	_____ %

AVERAGE % INORGANIC ASH: _____ AVERAGE % COMBUSTABLE CARBON: _____

* * * * *

SIZE AND DENSITY ANALYSES

SIZE (mm)	SAMPLE + PAN (gm)	PAN TARE (gm)	SAMPLE WT (gm)	CUMULATIVE WT (gm)	CUMULATIVE % %	VOLUME (cc)	DENSITY (gm/cc)
--------------	-------------------------	---------------------	----------------------	--------------------------	----------------------	----------------	--------------------

2.000							
1.000	17.61	17.12	0.49	256.80		6	0.082
.500	18.92	17.12	1.80	256.31	99.81	12	0.150
.250	23.55	17.12	6.43	254.51	99.11	13	0.495
.125	48.34	17.12	31.22	248.08	96.60	46	0.679
.063	75.73	17.12	58.61	216.86	84.45	114	0.514
.045	66.03	17.12	48.91	158.25	61.62	105	0.466
PAN	126.46	17.12	109.34	109.34	42.58	263	0.416

DATA FORM - WOOD ASH ANALYSES

RUN NO. 151COMBUSTIBLE CONTENT ANALYSESFUEL ALDER BARK

SIZE (mm) _____

SAMPLE NO. 1SAMPLE NO. 2

INITIAL SAMPLE + CRUCIBLE WT (gm)	_____	_____
CRUCIBLE WT (gm)	_____	_____
SAMPLE WT (gm)	_____	_____
FINAL SAMPLE + CRUCIBLE WT (gm)	_____	_____
CRUCIBLE WT (gm)	_____	_____
ASH WT (gm)	_____ %	_____ %
COMBUSTIBLE CARBON WT (gm)	_____ %	_____ %

AVERAGE % INORGANIC ASH _____ AVERAGE % COMBUSTIBLE CARBON _____

RUN NO. 151COMBUSTIBLE CONTENT ANALYSESFUEL ALDER BARKSIZE (mm) 1.000SAMPLE NO. 1SAMPLE NO. 2

INITIAL SAMPLE + CRUCIBLE WT (gm)	<u>25.47</u>	<u>28.56</u>
CRUCIBLE WT (gm)	<u>25.29</u>	<u>28.37</u>
SAMPLE WT (gm)	<u>0.18</u>	<u>0.19</u>
FINAL SAMPLE + CRUCIBLE WT (gm)	<u>25.33</u>	<u>28.40</u>
CRUCIBLE WT (gm)	<u>25.29</u>	<u>28.37</u>
ASH WT (gm)	<u>0.04</u> % <u>22.22</u>	<u>0.03</u> % <u>15.79</u>
COMBUSTIBLE CARBON WT (gm)	<u>0.14</u> % <u>77.78</u>	<u>0.16</u> % <u>84.21</u>

 AVERAGE % INORGANIC ASH 19.01 AVERAGE % COMBUSTIBLE CARBON 81.00

DATA FORM - WOOD ASH ANALYSES

RUN NO. 151COMBUSTIBLE CONTENT ANALYSESFUEL ALDER BARKSIZE (mm) 0.500

SAMPLE NO. 1

SAMPLE NO. 2

INITIAL SAMPLE + CRUCIBLE WT (gm)	<u>28.70</u>	<u>26.63</u>
CRUCIBLE WT (gm)	<u>27.92</u>	<u>25.86</u>
SAMPLE WT (gm)	<u>0.78</u>	<u>0.77</u>
FINAL SAMPLE + CRUCIBLE WT (gm)	<u>28.14</u>	<u>26.09</u>
CRUCIBLE WT (gm)	<u>27.92</u>	<u>25.86</u>
ASH WT (gm)	<u>0.22</u> % <u>28.21</u>	<u>0.23</u> % <u>29.87</u>
COMBUSTIBLE CARBON WT (gm)	<u>0.56</u> % <u>71.79</u>	<u>0.54</u> % <u>70.13</u>

AVERAGE % INORGANIC ASH 29.04AVERAGE % COMBUSTIBLE CARBON 70.96RUN NO. 151COMBUSTIBLE CONTENT ANALYSESFUEL ALDER BARKSIZE (mm) 0.250

SAMPLE NO. 1

SAMPLE NO. 2

INITIAL SAMPLE + CRUCIBLE WT (gm)	<u>31.85</u>	<u>30.10</u>
CRUCIBLE WT (gm)	<u>28.83</u>	<u>27.16</u>
SAMPLE WT (gm)	<u>3.02</u>	<u>2.94</u>
FINAL SAMPLE + CRUCIBLE WT (gm)	<u>31.43</u>	<u>29.69</u>
CRUCIBLE WT (gm)	<u>28.83</u>	<u>27.16</u>
ASH WT (gm)	<u>2.60</u> % <u>86.09</u>	<u>2.53</u> % <u>86.05</u>
COMBUSTIBLE CARBON WT (gm)	<u>0.42</u> % <u>13.91</u>	<u>0.41</u> % <u>13.95</u>

AVERAGE % INORGANIC ASH 86.07AVERAGE % COMBUSTIBLE CARBON 13.93

DATA FORM - WOOD ASH ANALYSES

RUN NO. 151COMBUSTIBLE CONTENT ANALYSESFUEL ALDER BARKSIZE (mm) 0.125

	<u>SAMPLE NO. 1</u>		<u>SAMPLE NO. 2</u>	
INITIAL SAMPLE + CRUCIBLE WT (gm)	<u>34.32</u>		<u>36.48</u>	
CRUCIBLE WT (gm)	<u>26.72</u>		<u>28.64</u>	
SAMPLE WT (gm)	<u>7.60</u>		<u>7.84</u>	
FINAL SAMPLE + CRUCIBLE WT (gm)	<u>34.26</u>		<u>36.42</u>	
CRUCIBLE WT (gm)	<u>26.72</u>		<u>28.64</u>	
ASH WT (gm)	<u>7.54</u>	% <u>99.21</u>	<u>7.78</u>	% <u>99.23</u>
COMBUSTIBLE CARBON WT (gm)	<u>0.06</u>	% <u>0.79</u>	<u>0.06</u>	% <u>0.77</u>
AVERAGE % INORGANIC ASH	<u>99.22</u>		AVERAGE % COMBUSTIBLE CARBON	<u>0.78</u>

RUN NO. 151COMBUSTIBLE CONTENT ANALYSESFUEL ALDER BARKSIZE (mm) 0.063

	<u>SAMPLE NO. 1</u>		<u>SAMPLE NO. 2</u>	
INITIAL SAMPLE + CRUCIBLE WT (gm)	<u>34.48</u>		<u>34.70</u>	
CRUCIBLE WT (gm)	<u>27.25</u>		<u>27.45</u>	
SAMPLE WT (gm)	<u>7.23</u>		<u>7.25</u>	
FINAL SAMPLE + CRUCIBLE WT (gm)	<u>34.42</u>		<u>34.65</u>	
CRUCIBLE WT (gm)	<u>27.25</u>		<u>27.45</u>	
ASH WT (gm)	<u>7.17</u>	% <u>99.17</u>	<u>7.20</u>	% <u>99.31</u>
COMBUSTIBLE CARBON WT (gm)	<u>0.06</u>	% <u>0.83</u>	<u>0.05</u>	% <u>0.69</u>
AVERAGE % INORGANIC ASH	<u>99.24</u>		AVERAGE % COMBUSTIBLE CARBON	<u>0.76</u>

DATA FORM - WOOD ASH ANALYSES

RUN NO. 151COMBUSTIBLE CONTENT ANALYSESFUEL ALDER BARKSIZE (mm) 0.045SAMPLE NO. 1SAMPLE NO. 2

INITIAL SAMPLE + CRUCIBLE WT (gm)	<u>31.59</u>	<u>33.70</u>
CRUCIBLE WT (gm)	<u>25.53</u>	<u>27.56</u>
SAMPLE WT (gm)	<u>6.06</u>	<u>6.14</u>
FINAL SAMPLE + CRUCIBLE WT (gm)	<u>31.59</u>	<u>33.70</u>
CRUCIBLE WT (gm)	<u>25.53</u>	<u>27.56</u>
ASH WT (gm)	<u>6.06</u> % <u>100.00</u>	<u>6.14</u> % <u>100.00</u>
COMBUSTIBLE CARBON WT (gm)	<u>0.00</u> % <u>0.00</u>	<u>0.00</u> % <u>0.00</u>
AVERAGE % INORGANIC ASH <u>100.00</u>	AVERAGE % COMBUSTIBLE CARBON <u>0.00</u>	

RUN NO. 151COMBUSTIBLE CONTENT ANALYSESFUEL ALDER BARKSIZE (mm) PANSAMPLE NO. 1SAMPLE NO. 2

INITIAL SAMPLE + CRUCIBLE WT (gm)	<u>32.30</u>	<u>33.54</u>
CRUCIBLE WT (gm)	<u>25.55</u>	<u>26.53</u>
SAMPLE WT (gm)	<u>6.75</u>	<u>7.01</u>
FINAL SAMPLE + CRUCIBLE WT (gm)	<u>32.29</u>	<u>33.39</u>
CRUCIBLE WT (gm)	<u>25.55</u>	<u>26.53</u>
ASH WT (gm)	<u>6.74</u> % <u>99.85</u>	<u>6.86</u> % <u>97.86</u>
COMBUSTIBLE CARBON WT (gm)	<u>0.01</u> % <u>0.15</u>	<u>0.15</u> % <u>2.14</u>
AVERAGE % INORGANIC ASH <u>98.86</u>	AVERAGE % COMBUSTIBLE CARBON <u>1.46</u>	

DATA FORM - WOOD ASH ANALYSESRUN NO: 175FUEL: ALDER
BARK

COMBUSTABLE CONTENT ANALYSES

	SAMPLE NO. 1	SAMPLE NO. 2
INITIAL SAMPLE + CRUCIBLE WT (gm)	_____	_____
CRUCIBLE WT (gm)	_____	_____
SAMPLE WT (gm)	_____	_____
FINAL SAMPLE + CRUCIBLE WT (gm)	_____	_____
CRUCIBLE WT (gm)	_____	_____
ASH WT (gm)	_____ %	_____ %
COMBUSTABLE CARBON WT (gm)	_____ %	_____ %

AVERAGE % INORGANIC ASH: _____ AVERAGE % COMBUSTABLE CARBON: _____

SIZE AND DENSITY ANALYSES

SIZE (mm)	SAMPLE + PAN (gm)	PAN TARE (gm)	SAMPLE WT (gm)	CUMULATIVE WT (gm)	CUMULATIVE % %	VOLUME (cc)	DENSITY (gm/cc)
--------------	-------------------------	---------------------	----------------------	--------------------------	----------------------	----------------	--------------------

2.000							
1.000	19.38	17.12	2.26	272.09		30	0.075
.500	27.95	17.12	10.83	269.83	99.17	78	0.139
.250	34.55	17.12	17.43	259.00	95.19	56	0.311
.125	64.18	17.12	47.06	241.57	88.78	75	0.627
.063	77.81	17.12	60.69	194.51	71.49	118	0.514
.045	61.68	17.12	44.56	133.82	49.18	105	0.424
PAN	106.38	17.12	89.26	89.26	32.81	237	0.377

DATA FORM - WOOD ASH ANALYSES

RUN NO. 175COMBUSTIBLE CONTENT ANALYSESFUEL ALDER BARK

SIZE (mm) _____

SAMPLE NO. 1SAMPLE NO. 2

INITIAL SAMPLE + CRUCIBLE WT (gm) _____

CRUCIBLE WT (gm) _____

SAMPLE WT (gm) _____

FINAL SAMPLE + CRUCIBLE WT (gm) _____

CRUCIBLE WT (gm) _____

ASH WT (gm) _____

COMBUSTIBLE CARBON WT (gm) _____

%

%

%

%

AVERAGE % INORGANIC ASH _____

AVERAGE % COMBUSTIBLE CARBON _____

RUN NO. 175COMBUSTIBLE CONTENT ANALYSESFUEL ALDER BARKSIZE (mm) 1.000SAMPLE NO. 1SAMPLE NO. 2INITIAL SAMPLE + CRUCIBLE WT (gm) 27.8728.46CRUCIBLE WT (gm) 26.7427.37SAMPLE WT (gm) 1.131.09FINAL SAMPLE + CRUCIBLE WT (gm) 26.9027.52CRUCIBLE WT (gm) 26.7427.37ASH WT (gm) 0.16

%

0.15

%

COMBUSTIBLE CARBON WT (gm) 0.97

%

0.94

%

AVERAGE % INORGANIC ASH 13.96AVERAGE % COMBUSTIBLE CARBON 86.04

DATA FORM - WOOD ASH ANALYSES

RUN NO. 175COMBUSTIBLE CONTENT ANALYSESFUEL ALDER BARKSIZE (mm) 0.500

	SAMPLE NO. 1	SAMPLE NO. 2
INITIAL SAMPLE + CRUCIBLE WT (gm)	<u>29.46</u>	<u>28.53</u>
CRUCIBLE WT (gm)	<u>26.77</u>	<u>25.81</u>
SAMPLE WT (gm)	<u>2.69</u>	<u>2.72</u>
FINAL SAMPLE + CRUCIBLE WT (gm)	<u>27.34</u>	<u>26.43</u>
CRUCIBLE WT (gm)	<u>26.77</u>	<u>25.81</u>
ASH WT (gm)	<u>0.57</u> % <u>21.19</u>	<u>0.62</u> % <u>22.79</u>
COMBUSTIBLE CARBON WT (gm)	<u>2.12</u> % <u>78.81</u>	<u>2.10</u> % <u>77.21</u>
AVERAGE % INORGANIC ASH	<u>21.99</u>	AVERAGE % COMBUSTIBLE CARBON <u>78.01</u>

RUN NO. 175COMBUSTIBLE CONTENT ANALYSESFUEL ALDER BARKSIZE (mm) 0.250

	SAMPLE NO. 1	SAMPLE NO. 2
INITIAL SAMPLE + CRUCIBLE WT (gm)	<u>29.86</u>	<u>30.40</u>
CRUCIBLE WT (gm)	<u>25.85</u>	<u>25.98</u>
SAMPLE WT (gm)	<u>4.01</u>	<u>4.42</u>
FINAL SAMPLE + CRUCIBLE WT (gm)	<u>28.62</u>	<u>29.05</u>
CRUCIBLE WT (gm)	<u>25.85</u>	<u>25.98</u>
ASH WT (gm)	<u>2.77</u> % <u>69.08</u>	<u>3.07</u> % <u>69.46</u>
COMBUSTIBLE CARBON WT (gm)	<u>1.24</u> % <u>30.92</u>	<u>1.35</u> % <u>30.54</u>
AVERAGE % INORGANIC ASH	<u>69.27</u>	AVERAGE % COMBUSTIBLE CARBON <u>30.73</u>

DATA FORM - WOOD ASH ANALYSES

RUN NO. 175COMBUSTIBLE CONTENT ANALYSESFUEL ALDER BARKSIZE (mm) 0.125

SAMPLE NO. 1

SAMPLE NO. 2

INITIAL SAMPLE + CRUCIBLE WT (gm)	<u>37.43</u>		<u>38.25</u>	
CRUCIBLE WT (gm)	<u>25.91</u>		<u>26.45</u>	
SAMPLE WT (gm)	<u>11.52</u>		<u>11.80</u>	
FINAL SAMPLE + CRUCIBLE WT (gm)	<u>37.13</u>		<u>37.91</u>	
CRUCIBLE WT (gm)	<u>25.91</u>		<u>26.45</u>	
ASH WT (gm)	<u>11.22</u>	% <u>97.40</u>	<u>11.46</u>	% <u>97.12</u>
COMBUSTIBLE CARBON WT (gm)	<u>0.30</u>	% <u>2.60</u>	<u>0.34</u>	% <u>2.88</u>
AVERAGE % INORGANIC ASH	<u>97.26</u>	AVERAGE % COMBUSTIBLE CARBON		<u>2.74</u>

RUN NO. 175COMBUSTIBLE CONTENT ANALYSESFUEL ALDER BARKSIZE (mm) 0.063

SAMPLE NO. 1

SAMPLE NO. 2

INITIAL SAMPLE + CRUCIBLE WT (gm)	<u>32.06</u>		<u>32.96</u>	
CRUCIBLE WT (gm)	<u>25.80</u>		<u>26.58</u>	
SAMPLE WT (gm)	<u>6.26</u>		<u>6.38</u>	
FINAL SAMPLE + CRUCIBLE WT (gm)	<u>32.06</u>		<u>32.96</u>	
CRUCIBLE WT (gm)	<u>25.80</u>		<u>26.58</u>	
ASH WT (gm)	<u>6.26</u>	% <u>100.00</u>	<u>6.38</u>	% <u>100.00</u>
COMBUSTIBLE CARBON WT (gm)	<u>0.00</u>	% <u>0.00</u>	<u>0.00</u>	% <u>0.00</u>
AVERAGE % INORGANIC ASH	<u>100.00</u>	AVERAGE % COMBUSTIBLE CARBON		<u>0.00</u>

DATA FORM - WOOD ASH ANALYSES

RUN NO. 175COMBUSTIBLE CONTENT ANALYSESFUEL ALDER BARKSIZE (mm) 0.045SAMPLE NO. 1SAMPLE NO. 2

INITIAL SAMPLE + CRUCIBLE WT (gm)	<u>31.82</u>	<u>31.46</u>
CRUCIBLE WT (gm)	<u>26.43</u>	<u>25.78</u>
SAMPLE WT (gm)	<u>5.39</u>	<u>5.68</u>
FINAL SAMPLE + CRUCIBLE WT (gm)	<u>31.82</u>	<u>31.46</u>
CRUCIBLE WT (gm)	<u>26.43</u>	<u>25.78</u>
ASH WT (gm)	<u>5.39</u> % <u>100.00</u>	<u>5.68</u> % <u>100.00</u>
COMBUSTIBLE CARBON WT (gm)	<u>0.00</u> % <u>0.00</u>	<u>0.00</u> % <u>0.00</u>

AVERAGE % INORGANIC ASH 100.00 AVERAGE % COMBUSTIBLE CARBON 0.00

RUN NO. 175COMBUSTIBLE CONTENT ANALYSESFUEL ALDER BARKSIZE (mm) 7ANSAMPLE NO. 1SAMPLE NO. 2

INITIAL SAMPLE + CRUCIBLE WT (gm)	<u>31.93</u>	<u>32.42</u>
CRUCIBLE WT (gm)	<u>26.35</u>	<u>26.88</u>
SAMPLE WT (gm)	<u>5.58</u>	<u>5.54</u>
FINAL SAMPLE + CRUCIBLE WT (gm)	<u>31.93</u>	<u>32.42</u>
CRUCIBLE WT (gm)	<u>26.35</u>	<u>26.88</u>
ASH WT (gm)	<u>5.58</u> % <u>100.00</u>	<u>5.54</u> % <u>100.00</u>
COMBUSTIBLE CARBON WT (gm)	<u>0.00</u> % <u>0.00</u>	<u>0.00</u> % <u>0.00</u>

AVERAGE % INORGANIC ASH 100.00 AVERAGE % COMBUSTIBLE CARBON 0.00

% COMBUSTIBLE MATERIAL IN CARRYOVER
VS.
PARTICLE SIZE

ALDER BARK
RUN NO. 175