Information

CONSERVATION AND RENEWABLE ENERGY INQUIRY AND REFERRAL SERVICE

Electric Vehicles

Q uiet, clean, and efficient electric vehicles (EVs) may someday become a practical mode of transportation for the general public. Electric vehicles can provide many advantages for the nation's environment and energy supply because they run on electricity, which can be produced from many sources of energy, such as coal, natural gas, uranium, and hydropower. These vehicles offer fuel versatility to the transportation sector, which depends almost solely on oil for its energy needs.

Electric vehicles are any mode of transport operated by an on-board motor that receives electricity from a battery or fuel cell. EVs come in all shapes and sizes, and may be used for different tasks. Some EVs are small and simple, such as golf carts and motor wheelchairs. Others are larger and more complex, such as school buses and vans. Some EVs can be used for long-distance travel, but most are designed for short-range, urban driving.

There are many benefits to electric vehicles. They are quiet and clean, with no tailpipe emissions. They are also efficient, using less energy than gasoline vehicles. EVs are also safe, with no risk of fire or explosion. They are also easy to maintain, with fewer moving parts than gasoline vehicles. EVs are also a good investment, with many states offering tax incentives and rebates.

photovoltaic cells (cells that convert solar energy to electricity) rather than utility-supplied electricity to recharge the batteries.

EVs: A Clean, Efficient, and Reliable Alternative

Almost all of the fuel that the transportation sector consumes is a product of petroleum. Accounting for about 66 percent of the petroleum that the nation uses, U.S. transportation consumes more oil than the residential, commercial and industrial sectors and utilities combined.

In 1988, the transportation sector consumed more petroleum than the nation produced.

Utilities, on the other hand, consumed less than 4 percent of the oil used in the nation in 1988. Many different types of power plants are on line, such as coal, nuclear, hydro, natural gas, geothermal, and oil power plants. The electric car links road transportation with a source of energy that can be delivered by many different fuels. The EV, therefore, may offer more energy security to the transportation sector.

Electric vehicles operate cleaner than cars with internal combustion engines (ICEs). Recently, concern about air pollution has grown in the United States, especially in cities with a high concentration of ICE vehicles. Fumes from ICE vehicles pollute the air with carbon monoxide and other noxious gases, causing smog in large metropolitan areas. Some officials are encouraging commuters and businesses to use electric vehicles as an alternative because these vehicles do not emit fumes. It is true that electricity is often generated from coal, natural gas, and oil power plants, which also pollute the air. Emissions from centralized power plants, however, are easier to control than emissions from 186 million vehicles. In addition, power plants that use non-polluting sources of energy, such as hydropower and geothermal plants, produce electricity in many areas, making electric vehicles even less polluting.

Most electric vehicles are reliable. Because the components of EVs are simple and few, these vehicles when fully developed will be more reliable and cost less to maintain than conventional cars. Most EVs are also more energy efficient than the average new ICE vehicle.

Electric vehicles can also help the utilities run more efficiently. EVs are usually "plugged in" at night when they are not being used. Recharging electric vehicles at night presents advantages to the electric utilities because there is less demand to produce electricity at night (This time of lower demand is called "off-peak hours.") Utilities that level peak loads operate more economically and efficiently with little capacity that remains idle.

An Old Idea with Improved Technology

Electric vehicles are not a new idea. In fact, electric cars were introduced decades before conventional, internal combustion vehicles were developed. These vehicles played a significant role in the birth of the auto industry. In the early 1900's, those who had cars often had electric vehicles. EVs, however, had problems with recharging and range. Their popularity quickly ended in the 1920's when manufacturers mass-produced more affordable gasoline-burning automobiles.

Stagnant for about 40 years, interest in electric vehicles again resurfaced in the mid-1960's in reaction to concern about air pollution. Interest became even stronger in the early 1970's during the oil crisis, as people searched for alternatives to high oil prices and long lines at the gas pumps. With improved technology for batteries, this mode of transportation can now achieve highway speeds and can be used in the commercial sector.

Electric vehicles are not expected to completely replace internal-combustion vehicles in the near future. In many cases, however, they have already become a practical alternative for some tasks. It is estimated that between 1,400 and 2,100 electric vehicles are driven in the United States. In addition, the U.S. Department of Energy (DOE) is studying about 360 electric vehicles that transport goods and provide services for the public and private sectors.

Components of the Electric Vehicle

Important components of the EV include the charger, batteries, controller, motor, and drivetrain. These components, in this order, are the path of the energy from the outlet to the wheels.

The **charger** receives electricity from the electrical outlet. This component regulates electricity and converts it from alternating current (AC) to direct current (DC) so that the electricity is compatible with the batteries. The charger then delivers electricity to the batteries.

The **batteries** store and provide electricity for the motor. Batteries will be discussed in detail further in the fact sheet.

The **controller** regulates the flow of energy from the batteries to the motor so the driver can adjust the speed. The flow of energy is usually regulated by "chopping" the direct current from the batteries to control motor power smoothly and efficiently.

The **motor** converts electrical energy to mechanical energy and transmits it to the drivetrain. Motors will also be discussed in detail further in the fact sheet.

The **drivetrain** transmits power mechanically from the motor to the wheels of the vehicle.

When inside an electric vehicle, the driver may notice that many of the displays and controls are the same as those in conventional ICE vehicles. These include the speedometer, headlights,

Figure 1. U.S. Transportation and Petroleum Use.

signals, heater, brakes, and accelerator. Other controls and displays, however, differ from those in ICE vehicles. These include the power meter, state-of-charge gauge, battery failure display, and ammeter. A particular EV may or may not have all of the controls and displays listed -- or it may have variations of these.

The **power meter** indicates the capabilities for accelerating the vehicle.

The **state-of-charge gauge** shows how much energy is in the battery. This is the equivalent of the fuel gauge in an ICE vehicle.

The **battery failure display** indicates if one or more battery cells are not working.

The **ammeter** shows the draw of electric current from the motor.

The Batteries and Motor

The batteries and electric motor are the main components that make electric vehicles different from conventional automobiles. These components pose different advantages and problems for EVs. When compared to liquid fuels, batteries are poor at storing large amounts of energy per unit weight or volume and limit the range and speed of EVs. However, current research and development of batteries is improving their limitations. Motors, on the other hand, are presently lightweight and highly efficient when compared to engines in ICE vehicles. Major advances are not required for electric motors.

The Battery Pack

The battery pack, as previously described, stores and provides electricity for the motor. Most electric cars use between eight and 40 modules in a battery pack, depending on the size and voltage of the car. A separate battery module powers the displays and controls, such as the horn, headlights, and turn signals.

A typical electric car or truck has a range of between 25 and 120 miles and a maximum speed of 50 to 70 m.p.h. Batteries may last up to 4 years (or about 800 cycles), depending on the type and assuming that the vehicle travels about 60 miles per discharge. The life of the battery, however, depends on many factors. Improper charging damages many batteries. The type of battery greatly influences how long it will last. Also, ambient temperatures above 100 degrees Fahrenheit (F) can shorten life. Moreover, the life of a battery may be shortened if

Figure 2. Components of an Electric Vehicle.

over 80 percent of the battery's storage capacity is discharged or if the vehicle is not properly maintained.

Batteries for EVs differ from those for ICE vehicles because EVs have deep-cycle batteries, while ICE vehicles have shallow-cycle batteries. Deep-cycle batteries can be drained of much of their energy without considerable harm, before being recharged. Marine and golf cart batteries are examples of deep-cycle batteries. A standard car battery, on the other hand, is a shallow-cycle battery. It is designed to give a car a short spurt of electricity to start the engine and then be fully recharged by the alternator. (If you habitually leave your car lights on by accident, you know that these batteries will allow you to let them go dead only a few times before needing replacement.)

The type of electrochemical system used in a battery system and the size and number of modules in the vehicle determine how far and how fast an electric vehicle can travel. The energy density (watt-hrs/kg) determines how much energy can be stored in a given weight of batteries. A battery pack with a high **specific energy** allows an EV to travel further on a charge than a battery pack of the same weight with a low specific energy. Specific power determines the rate that energy can be extracted from a given weight. If the battery pack of an EV has a high **specific power**, then the

EV can achieve higher speeds than an EV using a battery pack with a low specific power. A battery has yet to be developed that has both a relatively high specific energy and high specific power.

Why don't designers simply install larger battery packs (or more modules) in electric vehicles so that EVs can travel further on a charge and obtain higher speeds? After all, the more energy stored in a battery pack, the further and faster an electric vehicle can travel. Cost is one factor. Moreover, since batteries are heavy, designers are limited to the number of battery modules that can be practically used in a vehicle. Too many modules can weigh down the vehicle, causing it to expend more energy than the extra modules produce. EVs, therefore, are limited to a certain number of modules in a battery pack that supply the electricity for the motor. These limits, unfortunately, restrain the vehicles from achieving higher speeds and traveling further on a charge.

The public and private sectors are researching ways to develop lightweight batteries that can store and supply enough energy to allow EVs to achieve high speeds and long distances, while also being affordable for the general public. Currently, lightweight batteries are expensive and not widely available. Most batteries, however, share at least one of these qualities.

Present electric vehicles usually use **lead-acid** batteries. Lead-acid batteries are made from two lead electrodes and sulfuric acid as an electrolyte. The electrode and electrolyte are the primary components of the battery. Flat-plate, lead-acid batteries are the most well known type of lead-acid battery in this country. Their anode and cathode are flat plates of lead (hence the name). Owners of EVs with flat-plate, lead-acid batteries must frequently add water to the battery pack. In addition, they emit hydrogen gas when charged. (Some flat-plate lead-acid batteries are sealed, however, and do not emit hydrogen or require watering.) These batteries, however, have been used for decades. With industry in place for producing them and with an abundance of lead in the nation, they are more practical and widely available than other types. Ranging from \$72 to \$140 per kilowatt-hour (kWh) of capacity, they cost less to manufacture than others.

DOE is researching and developing more advanced types of lead-acid batteries to improve their performance and life. R&D in the Federal and private sectors has improved lead-acid batteries to increase the range and acceleration of EVs. This research is also aimed at reducing energy and water consumption of the batteries.

Two alternatives using lead-acid technology are **tubular lead-acid** batteries and **gel-cell** batteries. Tubular lead-acid batteries, which are more popular in Europe, have a tubular-shaped lead anode and cathode. More advanced types have a higher specific energy, providing a slightly longer range than flat-plate lead-acid batteries, but they do not provide as much power. They also emit less hydrogen gas. With an average life of about 4 years, tubular lead-acid batteries also last longer. Like many flat-plate lead-acid batteries, however, current batteries need to be watered.

The gel-cell batteries use gel rather than liquid sulfuric acid as an electrolyte. Gel is advantageous because it doesn't require watering and is virtually maintenance free, therefore, greatly reducing the operating costs of the vehicle. Also, because the battery is sealed and recombines the hydrogen and oxygen gases evolved during charging, it eliminates hydrogen gas buildup outside the battery. These batteries are up to 35 percent more efficient than flat-plate lead-acid batteries. Current gel-cell batteries, however, don't last as long as tubular-plate lead-acid batteries if they are

discharged deeply or for long periods.

Other types of batteries are also being researched and have been used in electric vehicles to a limited degree. The **nickel-iron** battery is one example. The nickel-iron is a durable battery that has a long life cycle and higher specific energy, allowing the vehicle to travel longer distances. A vehicle with an advanced type of this battery can travel 50 percent further than the same vehicle with a tubular lead-acid battery. Moreover, nickel-iron batteries can operate at higher temperatures and can be overcharged or discharged for a long time without damage. These batteries, however, are very expensive. Their target price is around \$125 per kWh and their current price is about \$300 per kWh. They also perform poorly at low temperatures, use lots of water, and produce excessive amounts of hydrogen gas as a by-product.

Other batteries are currently being researched such as **zinc-bromine, lithium-metal sulfide, sodium-sulfur, and iron-air** batteries. More information

about these types of batteries is available from *The Twelfth Annual Report to Congress for Fiscal Year 1988: Electric and Hybrid Vehicles Program* (see Bibliography).

Motors

Electric motors are simpler, smaller, and more efficient than internal combustion engines. Motors have only one moving part. They don't use carburetors, air filters, fuel injection systems, spark plugs, catalytic converters, or expensive exhaust systems. Since motors don't use large amounts of oil, they don't leak oil or get greasy and dirty like IC engines. (They only require oil to lubricate the bearings.) Moreover, electric motors are quiet, so they don't need mufflers.

In the past, most electric vehicles had motors that used direct current (DC) rather than alternating current (AC). To use AC, the motor needs an inverter to change the DC electricity to AC. (Batteries can only store DC power.) Previously, inverters were costly, complex

ETX-II TEST VEHICLE

INTEGRATED MOTOR/TRANSAXLE (ETX-II)

unreliable, and inefficient. New advances, however, have reduced their cost and improved their efficiency and reliability enough for practical use in EVs. Because of these advances, many new EVs use AC motors with an inverter. AC motors weigh and cost less than DC motors and don't require maintenance.

An electric motor is rated for continuous performance and can double and triple output for a short time. For example, a 15 horsepower (HP) motor can quadruple its rating for a short time, enabling it to handle occasional peak loads such as passing and climbing hills. The motor power output is controlled by varying the voltage to it.

Performance and Maintenance of Electric Vehicles

The performance and reliability of the electric vehicle depends on the quality of the components, such as the batteries and motor. Some of the vehicles using state-of-the-art, lead-acid batteries are more likely to travel further and faster than those with the same design using less advanced batteries. Performance may also vary depending on the design and purpose of the vehicle. A fork lift may be able to handle heavier loads than a sports car designed for two passengers. The sports car, however, will be faster.

Although the performance of EVs can vary greatly, the G-Van may help illustrate some of the present capabilities of the electric vehicles that use state-of-the-art technology. The G-Van was developed by VEHMA Corporation (a subsidiary of the Magna Corporation of Toronto, Canada, a major automotive supply company), with help from other groups from the private sector. This van can accelerate to 30 m.p.h. in 12 to 13 seconds, achieve speeds up to 52 m.p.h., and travel 60 miles between charges. These EVs will be produced later this year and are expected to be used as delivery and passenger vans in urban areas. The G-Van can presently hold up to 5 passengers or can be used as a cargo van, depending on the design. Future designs will hold up to 8 passengers. The vans use a tubular lead acid battery with a high specific energy, a DC motor, a state-of-the-art electronic controller, and a 1-speed transmission.

The TEVan is designed to serve a different market and should appeal to the

Figure 4. The G-Van.

personal vehicle owner. Several concept vehicles are being built and one is completed. This van was developed by the Chrysler Corporation with support from the Electric Power Research Institute (EPRI), the U.S. Department of Energy (DOE), and Southern California Edison. Using a nickel-iron battery, this van can accelerate to 30 m.p.h. in 7 seconds, travel up to 120 miles between charges, and ride at speeds of 65 m.p.h. It has the body of a popular conventional minivan, and can hold 6 passengers or 120 cubic feet of cargo. The TEVan also uses a state-of-the-art microprocessor-run battery management system, a DC motor and a 2-speed transmission. One prototype TEVan is currently being tested in Tennessee.

A new, highly advanced design for an EV is still in the early stages of development at General Motors. This bullet-shaped sports car can drive at 55 m.p.h. for 120 miles before needing to be recharged, and can go from 0 to 60 m.p.h. in 3 seconds. Unlike the other state-of-the-art EVs, this car can be completely recharged after only 3 hours of being plugged in to a standard, residential AC outlet. The EV can also achieve speeds of 100 m.p.h. The car's batteries are state-of-the-art sealed lead acid batteries, but they require more development to achieve the necessary cycle life.

Because of their simple design, most electric vehicles require few repairs. Studies conducted for DOE on the Griffon-

Van (the predecessor of the G-Van) indicate that over 50 percent of the time spent maintaining these vehicles was for scheduled items, such as battery and watering systems. Other than scheduled items, two of the three most time consuming repairs were not EV related. (These repairs were for body and glass work and brakes.)

Consumers interested in purchasing an electric vehicle should be aware that it is suited for certain applications and not for others. While long ranges, high speeds, and quick acceleration are feasible for electric vehicles, they are not possible simultaneously in the same vehicle with current technology. Many of the limits of the EV stem from limitations of batteries. For example, high speeds and quick acceleration expend energy quickly and, therefore, significantly limit range. Electric vehicles can travel further at low speeds than they can at high speeds.

Studies conducted by the Electric and Hybrid Vehicles Program of DOE indicate that EVs perform better if they are properly maintained (like any vehicle). Site operators who applied strong programs for preventative maintenance and technician training had fleets of vehicles with shorter downtime. These operators were also able to properly diagnose and repair cars when they did break down, thereby increasing the efficiency of the fleet. Programs for training drivers of electric vehicles have also been successfully implemented. Although EVs are as easy

or easier to drive than ICE vehicles, new drivers may need to familiarize themselves with the different gauges and controls and get an overall "feel" for the car. Driver training not only teaches the driver how to drive an electric vehicle, but also how to maintain EVs and recognize any problems requiring maintenance or repair.

When compared to an ICE vehicle, electric vehicles require less time and money for maintenance. EVs don't need tune-ups, lube jobs, or oil refills and changes. To maximize efficiency, however, EVs require some maintenance. The battery requires most of the maintenance. Since batteries slowly self-discharge, they need to be charged at least once every two weeks to optimize their life — even if the vehicle is not being driven. If the batteries are not charged regularly, they will eventually need to be replaced. The electrolyte level in each cell (except in the gel-cell) should be checked every two weeks. Water should be added to the batteries if the level is less than 1/2 inch above the edges of the upper plate. The specific gravity of the electrolyte in each cell should be measured. Cables from the batteries should be checked for corrosion and looseness.

Other parts of the electric vehicle also need to be maintained. Service people should annually inspect the brushes of the DC motor, which may need replacing. Brushes are usually inexpensive. Also, the cooling blower of the motor needs to be checked for loose mounting, loose connectors, and damaged duct work. Moreover, the wires, fasteners, and contacts of the controllers should be examined for looseness and corrosion.

The Cost of Electric Vehicles

Two different costs are associated with electric vehicles — the initial cost and the life-cycle cost. The initial cost is the purchased price of the vehicle. The life-cycle cost is the initial, operating, maintenance, and ancillary costs incurred over the life of the vehicle — minus the salvage value. The initial cost of electric vehicles can be relatively high, mostly because an industry is not set up to produce EVs on a large scale, however, higher demand for EVs will lower costs.

If industries produced electric vehicles by 1995, a 2-passenger EV with a sodium-sulfur battery would cost about \$12,000, while a comparable conventional car would cost about \$8,000. On

the other hand, when considering life-cycle costs, electric vehicles would be much more competitive. Hypothetically, the same 2-passenger electric car would cost the owner about \$25,000 during its life, while the conventional car would cost about \$21,000. If 1988 gasoline prices doubled, 2-passenger EVs with sodium-sulfur batteries would reach cost parity with ICE vehicles in 1995.

Like most cost comparisons of this nature, these are based on assumptions, which can significantly affect the results of the study. For example, the 2-passenger EV was assumed to last 7 years. Another example concerns assumptions made about operating costs. Off-peak electricity rates were used. It was assumed that most EVs would be charged at night. More information about life-cycle costs and assumptions pertaining to this data is discussed in *Comparison of Life Cycle Costs of Alternative Fuel Vehicles* (see Bibliography).

Challenges for Electric Vehicle Technology

Although electric vehicles offer potential as a primary mode of transportation for many people in the United States, there are still questions that pose problems for EVs on a large scale.

1. Will consumers be swayed from purchasing electric vehicles because of range or speed limitations? Although the Federal and private sector are making progress through research and development to increase range and speed, ICE vehicles still offer the most flexibility to the average consumer.
2. Although the major American automobile manufacturers, as well as Japanese companies, are currently involved in EV research and development, will industry take the initiative to commercialize electric vehicles?
3. How will the general public recharge their batteries when they are traveling (i.e., vacationing for several days)? "Fuel" stations to recharge batteries will be needed to support this type of transportation on a large scale.
4. What guidelines and policies will automobile insurance companies specify for electric vehicles?
5. What guidelines and policies will be made for electric vehicles in states

requiring annual inspection of motor vehicles?

6. Will mechanics of electric vehicles be available on a large scale?
7. How will consumers finance an electric vehicle? Will the initial cost be too high for many businesses and private residents?

The local government officials in Los Angeles, California are grappling with these questions to alleviate problems with air pollution, since levels far exceed those permitted by the Federal Clean Air Act Standards. The City Council of Los Angeles is encouraging industry to quickly produce and distribute electric vehicles. The California Energy Commission, the South Coast Air Quality Management District, the Los Angeles Department of Water and Power, and the Southern California Edison Company are providing financial support to purchasers. The City of Los Angeles and other agencies have pledged to help develop the local government and institutional market. The City will propose regulations to provide incentives to commercial users, such as allowing EVs unlimited access in congested areas, prohibiting delivery vans with IC engines to travel in congested areas during on-peak hours, and encouraging cities in the Basin to adopt similar programs.

Hybrid Vehicles

The hybrid vehicle is a variation of the electric vehicle. Many different types of hybrid vehicles have been or are being researched, using different components and different fuels. Some hybrid configurations look like 3-wheeled motorbikes, while others look and operate like conventional ICE cars.

One of the most advanced hybrid vehicles, the hybrid test vehicle (HTV), was developed by DOE. The HTV supplements an electric vehicle with a gasoline engine. This car can potentially reduce petroleum that passenger cars consume in the United States by 50 to 75 percent, depending on use patterns. While saving petroleum, the HTV still provides the mobility, performance, and passenger comfort of a conventional ICE vehicle. Like electric vehicles, these cars offer great potential to reduce air pollution in congested urban areas with high levels of stop-and-start traffic. When traveling daily under 25 miles, the HTV can achieve an average fuel economy of 75

m.p.g. The fuel economy, however, decreases as the miles driven increases. The engine, which uses gasoline, must operate more when energy in the battery runs low. After driving 75 miles, the HTV can achieve an average fuel economy of 30 m.p.g. However, the average driver of a vehicle travels about 25 miles daily. For most applications, therefore, these vehicles are highly energy efficient.

The HTV has the body of a popular, large-sized car sold in the United States and can seat five adults. It can maintain a speed of 56 m.p.h. and accelerate to that speed in less than 15 seconds. In addition, the HTV has many of the same features of an ICE vehicle currently manufactured. It has front wheel drive, independent front suspension; power rack-and-pinion steering; low-rolling resistance, steel-belted, radial tires; power brakes; an automatic, 3-speed transmission; and an air conditioner. The HTV meets all applicable Federal Motor Vehicle Safety Standards (FMVSS) of 1978, as well as, Federal emissions standards.

The HTV uses a parallel driveline arrangement. This means that both the gasoline engine and the electric motor can directly apply mechanical torque to the drive shaft to power the vehicle. Torque is the force of the rotating motion of the engine or motor. The engine does not have to feed through the battery to work. The HTV can operate on either the motor or engine or both simultaneously. A computerized microprocessor selects the appropriate arrangement of the engine and motor. The driver does not need to choose which system to use. He or she simply drives the car as if it were a conventional ICE vehicle.

The engine is a 1.7-liter, fuel-injected, gasoline engine with four cylinders and controls for emission. A special clutch was developed that stops and starts the engine in 3 seconds. The electric motor is DC-powered with regenerative braking (a way to recover energy). By braking the car, momentum is converted into electricity, which is then stored in the batteries. With ten 12-volt modules, the batteries weigh about 830 pounds. The gasoline engine may also recharge the batteries when it is running.

The battery of the HTV is usually charged at night, receiving electricity from a utility. Other independent sources that produce electricity, such as small-scale hydropower plants and photovoltaic modules (sometimes called solar cell modules) may also charge the HTV. When driven, the vehicle first uses energy

Figure 5. Hybrid test vehicle.

Figure 6. Hybrid test vehicle cutaway.

stored in the battery. If, however, the vehicle needs a supplement to increase speed or range, the microprocessor turns on the engine.

Another type of hybrid vehicle has an engine called an onboard charger unit (OCU). It is often a small engine (i.e., 8

horsepower) which essentially acts as a battery charger. The OCU is connected to the alternator. The alternator, in turn, supplies electricity to the batteries, where it is either used by the motor or stored. The other components of a hybrid vehicle operate similarly to a typical electric vehicle.

The batteries send electricity through the controller, which feeds electricity to the motor. The motor provides torque to turn the wheels. The OCU of the hybrid does not send energy directly to the wheels. The vehicle always receives its energy from batteries. This hybrid design is often used for small configurations, such as 3-wheeled vehicles or vehicles with bodies from golf-carts. Nonetheless, it is also being considered for Los Angeles vans.

Solar Powered Vehicles

Electric vehicles can be recharged with any source of energy that produces electricity. For example, an owner can buy a large photovoltaic (PV) array and plug in a conventional EV to it during the day to recharge the batteries. Researchers and developers, however, have taken this idea a step further and have designed experimental vehicles with PV cells attached to the bodies. Some of these vehicles operate solely on solar energy that has been collected from the PV cells attached to the vehicle. Attaching the PV cells to EVs allows the vehicles to travel unlimited distances without needing to recharge the battery pack, as long as the sun is shining. Still in the early stages of research and development, solar vehicles have obtained speeds of about 85 m.p.h.

Because the technology is so new, no design has been standardized for a solar-powered vehicle. Designs vary and may provide different features and capabilities. Some constants, however, do exist. For one, solar-powered vehicles operate by using PV cells, which convert energy from the sun to electricity and send it to the controller or to a battery. All solar-powered vehicles, like conventional electric vehicles, however, use electric motors. Also, because solar-powered vehicles must be efficient to operate, they usually have lightweight bodies and batteries. In most cases, lead-acid batteries are too heavy and inefficient to be used in a solar-powered vehicle. Some use expensive, state-of-the-art, lightweight batteries, such as silver-zinc batteries. PV cells for this application are usually made of crystalline silicon.

Some solar vehicles use PV cells made from gallium arsenide -- a material that produces more energy efficient PV cells. The more energy efficient the PV cells, the more electricity they will generate in a given area. Cells made from gallium arsenide are beneficial for

solar-powered vehicles because they consume less space (which is limited in these vehicles). Gallium arsenide cells, however, cost significantly more than those made of crystalline silicon.

While many conventional electric vehicles provide the space and luxuries of vehicles with IC engines, solar-powered vehicles look somewhat different and may not provide some features, such as an air conditioner and radio. With sleek, lightweight, aerodynamic bodies, many of these vehicles are not roomy. Many have only three wheels.

Solar-powered vehicles are still in the experimental stages. With further research and development, these vehicles offer potential in the market place. To demonstrate their capabilities, several worldwide races are periodically held. These include Tour de Sol, which is held annually in Switzerland; the Pentex Solar Challenge, which is held every 3 years in Australia; and the American Solar Cup, which is held in the United States.

The Solectria V is an example of a solar car in the United States using state-of-the-art technology. This car won first place in the American Solar Cup achieving 85 m.p.h. and averaging 51.9 m.p.h. Weighing 300 lbs., this aerodynamic, fiberglass car is less than 12 feet long and 6 feet wide. It uses silver-cadmium batteries and a 55 square-foot PV array

Research and Development of Electric and Hybrid Vehicles

Many groups are currently involved in researching and developing electric and hybrid vehicles. The U.S. Department of Energy (DOE), the transportation program of the Electric Power Research Institute (EPRI), as well as several automobile manufacturers and utilities, play an important role in improving and inventing new technologies to make electric and hybrid vehicles a reality for the transportation sector.

The U.S. Department of Energy, through the Electric and Hybrid Vehicles Program, is sponsoring projects to develop propulsion systems and components for electric and hybrid vehicles. Activities include the Advanced Battery Research and Development Program, the Dual Shaft Electric Propulsion (DSEP) Program, the ETX I & II Programs, the Field Test and Evaluation Project, and the Fuel Cell/Battery Powered Transit Bus Program. These activities are designed to provide research and development of electric and hybrid vehicles needed to encourage commercialization in the private sector. DOE also assists EPRI, the Electric Vehicle Development Corporation (EVDC), and other groups in their R&D projects.

Figure 7. Mana La Solar Racing Car.

EPRI helps finance projects that develop and commercialize practical EVs, such as the GM Griffon Van, the G-Van, and the Chrysler TEVan. They also finance R&D for batteries and components. Some components that have been under development include power-trains with AC motors.

While promoting and accelerating the use of EVs in the commercial sector, EVDC has managed a demonstration program for electric utilities involving the evaluation of 25 Griffon vans. Their goal is to demonstrate a market for EVs in the 1990's. EVDC is currently involved in commercializing the G-Van.

Using electric vehicles in the nation for applications such as commuting could reduce air pollution, oil imports, and oil consumption. For EVs to make an impact, however, people need to understand why these vehicles are important so that a market can be fully developed. They need to also understand that these vehicles are not "trouble free and energy free." Communicating ideas and information about electric vehicle technology is important so that the public will know that EVs are not just a technology of the past.

Bibliography

The following publications provide further information on electric vehicles. This list does not cover all the available books, reports, and articles on electric vehicles, nor is the mention of any publication to be considered a recommendation or endorsement. To obtain the publications in this bibliography, contact your local library, bookstore, or the publisher. Check the prices through your bookstore or the publisher before ordering.

Books and Reports

All About Electric and Hybrid Cars ... R. Traister; Tab Books, Inc., Blue Ridge Summit, PA 17214, 1982, 303 pp.

Building the Electric Vehicle Future: EPRI's Vehicle Development Activities ... Electric Power Research Institute, Electric Transportation Program, Electric Transportation Information Center, P.O. Box 10412, Palo Alto, CA 94303, 1987, 11 pp. Rept. No. EU-3017.11.87.

Comparison of Life Cycle Costs of Alternative Fuel Vehicles ... Booz-Allen

and Hamilton, Inc., 1988, c75 pp. Available from Electric and Hybrid Vehicles Program, U.S. Department of Energy, Washington, D.C. 20585.

Programs in Energy Conservation: Transportation Systems ... DOE, Asst. Secretary for Conservation and Renewable Energy, 1989, 13 pp. Order No. DE89000806, available from NTIS (see Source List).

The Role of Electric Vehicles in the Nation's Energy Future ... J. Asbury, J. Seay, and W. Walsh; Argonne National Laboratory, 1984, 28 pp. Rept. No. ANL/SPG-26, available from NTIS (see Source List).

Technical Brief: The Electric G-Van ... Electric Power Research Institute, Electric Transportation Information Center, P.O. Box 10412, Palo Alto, CA 94303, 1988, 2 pp. Rept. No. TB.EMU.141.6.88.

The Twelfth Annual Report to Congress for Fiscal Year 1988: Electric and Hybrid Vehicles Program ... DOE, Office of Transportation Systems, 1989, 37 pp. Rept. No. DOE/CE-0247, available from NTIS (see Source List).

Articles

An Accessible Solar Vehicle ... D. Browning and W. Becker, **PV International** 5(5):5-6, June/July 1987.

At Last, A Practical Electric Vehicle? ... M. Wald; **The New York Times** 139(48,055):D-1, D-5, November 15, 1989.

Fuel for Change: Alternative Energy Cars ... **Energy Sense** pp 11-13, Winter 1985-86.

GM Advances Model of Electricity-Run Car ... J. Mathews; **The Washington Post** 113(30):E-1, E-4, January 4, 1990.

GM's Electric Sports Car ... **Popular Science** 236 (4):32, April 1990.

The Hybrid-Configured Electric Vehicle ... M. Hackleman; **Home Power** (9):13-19, February/March 1989.

The Hybrid Electric Vehicle ... M. Hackleman; **Home Power** (8):5-11, December 1988/January 1989.

PV Racing into the Future ... **PV International** 6(5):7-8, June/July 1988.

Racing with the Sun ... D. McCosh; **Popular Science** 231(5):84-87, November 1987.

Solar Powered Transportation in America ... R. Cotter; **Northeast Sun** 7(2):10-12, May/June 1989.

Sunracer Highlights Sun Day ... **Solar Collector** 13(2):1, Spring 1988.

Papers from Proceedings

Electric Van Introduction in the United States ... G. Mader and O. Bevilacqua; Paper in **Productivity Through Energy Innovation: Proceedings from the 3rd Great P.G. & E. Energy Expo**, Oakland, CA, April 30 — May 2, 1986, pp 256-264. Entire proceedings available from Pergamon Press, Inc., Fairview Park, Elmsford, NY 10523.

Electric Vehicle Commercialization ... G. Mader; Paper in **Proceedings of the Sixteenth Energy Technology Conference**, Washington, D.C., February 28 — March 2, 1989, pp 580-592. Entire proceedings, ISBN No. 0-86587-429-8, available from Government Institutes, Inc., 966 Hungerford Dr., #24, Rockville, MD 20850.

Periodicals

Electric Vehicle Battery Technology ... Business Communications Co., Inc., 25 Van Zant St., Norwalk, CT 06855. Monthly.

Electric Vehicle Progress ... Alexander Research and Communications, Inc., 1133 Broadway, Ste. 1407, New York, NY 10010. Semimonthly.

Source List

National Technical Information Service (NTIS) 5285 Port Royal Rd. Springfield, VA 22161 (703) 287-4650

For more information:

CAREIRS
P.O. Box 8900
Silver Spring, MD 20907
(800) 523-2929

Electric Transportation Information Center
Electric Power Research Institute (EPRI)
Electric Transportation Program
P.O. Box 10412
Palo Alto, CA 94303
(800) 848-ETIC

Source of Illustrations

Figures 2 & 4 -- Courtesy of the Electric
Power Research Institute (EPRI), Palo
Alto, CA

Figure 7. Courtesy of John Paul Mitchell
Systems/Solec International, Inc.

END

DATE FILMED

02 / 13 / 91