AIM

Association for Information and Image Management

1100 Wayne Avenue, Suite 1100
Silver Spring, Maryland 20910
301/587-8202

Centimeter

Inches

MANUFACTURED TO AIM STANDARDS
BY APPLIED IMAGE, INC.

1 of 2

EPSCIL

**DOE/PC/88811-T17
(DE93014507)**

FUNDAMENTAL REACTION PATHWAYS DURING COPROCESSING

December 1992

Work Performed Under Contract No. AC22-88PC88811

**For
U.S. Department of Energy
Pittsburgh Energy Technology Center
Pittsburgh, Pennsylvania**

**By
The University of Chicago
Chicago, Illinois**

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

This report has been reproduced directly from the best available copy.

Available to DOE and DOE contractors from the Office of Scientific and Technical Information, P.O. Box 62, Oak Ridge, TN 37831; prices available from (615)576-8401.

Available to the public from the National Technical Information Service, U. S. Department of Commerce, 5285 Port Royal Rd., Springfield, VA 22161.

FUNDAMENTAL REACTION PATHWAYS DURING COPROCESSING

LEON M. STOCK AND JOHN G. GATSI, PRINCIPAL INVESTIGATORS

**KADIM CEYLAN, KUNTAL CHATTERJEE, CARLOS CHENG,
MICHAEL ETTINGER, SAO JIRALERSPONG AND AHMET METE**

RESEARCH STAFF

DECEMBER 1992

**THE UNIVERSITY OF CHICAGO
DEPARTMENT OF CHEMISTRY
5735 SOUTH ELLIS AVENUE
CHICAGO, ILLINOIS 60637**

AND

**UNIVERSAL OIL PRODUCTS
25 EAST ALGONQUIN ROAD
DES PLAINES, ILLINOIS 60017**

**PREPARED FOR THE
UNITED STATES DEPARTMENT OF ENERGY
UNDER CONTRACT NO. AG22-88PC88811**

ELEMENT	Page
TABLE OF CONTENTS	ii
LIST OF TABLES	iii
LIST OF FIGURES	v
EXECUTIVE SUMMARY	1
SECTION I. THE REACTIVITY PATTERNS OF COALS AND RESIDUA IN HYDROGEN ATOM TRANSFER, CARBON-CARBON SCISSION, AND HYDRODEMETHYLATION	
Introduction	6
Experimental	7
Results and Discussion	9
Conclusion	21
SECTION II. REACTION OF ILLINOIS NO. 6 AND WYODAK COALS WITH LLOYDMINSTER AND HONDO RESIDUA UNDER MILD CONDITIONS	
Introduction	23
Experimental	24
Results and Discussion	25
Conclusion	34
SECTION III. DIDEUTERIUM UPTAKE DURING THE COPROCESSING REACTIONS OF ILLINOIS NO. 6 AND WYODAK COALS WITH LLOYDMINSTER AND HONDO PETROLEUM RESIDUA UNDER SEVERE CONDITIONS	
Introduction	37
Experimental	38
Results and Discussion	41
Conclusion	53
SECTION IV. DIDEUTERIUM UPTAKE AND UTILIZATION DURING THE COPROCESSING REACTION OF ILLINOIS NO. 6 AND LLOYDMINSTER PETROLEUM RESIDUUM UNDER MODERATE CONDITIONS OF VARIED PRESSURE, TEMPERATURE, AND RESIDENCE TIME	
Introduction	56
Experimental	57
Results and Discussion	59
Conclusion	86

REFERENCES 88

APPENDIX

I. LIST OF PUBLICATIONS AND PRESENTATIONS..... 91

LIST OF TABLES

Table	Page
1. Analytical information for the fossil fuel materials	8
2. The measured decrease in the deuterium content of the three positions of tetralin in the exchange reactions between tetralin- d_{12} and the fossil fuel materials	10
3. The exchange reactions between tetralin- d_{12} and diphenylmethane in the presence of fossil fuel components.....	11
4. Decomposition of 1,3-diphenylpropane neat and in tetralin- d_{12}	12
5. The reactions of tetralin- d_{12} and 1,3-dimethylnaphthalene in the presence of coals and resids	12
6. Influences of coals and resids on hydrogen atom transfer from the α position of tetralin	13
7. Influence of resid constituents on hydrogen atom transfer from the α position of tetralin	13
8. Influence of coals and resids on the transfer of deuterium from tetralin- d_{12} to diphenylmethane	16
9. Analytical data for the fossil fuel materials	24
10. Coprocessing reactions of fossil fuels	25
11. Reactivity patterns in coprocessing and probe reaction systems	28
12. Solvent separated fraction yields and conversions of coprocessed products	41
13. Elemental analysis of the solvent separated starting residua and coprocessing product	42
14. Hydrogen content, deuterium content, and % deuteration of coprocessed products	44
15. Aliphatic deuterium content in solvent separated coprocessing products	45
16. Distribution of deuterated gaseous products	47

LIST OF TABLES , CONT'D.

Table	Page
17. Chemical shift ranges of hydrogen and deuterium resonances	58
18. Coprocessing reaction conditions	59
19. Coprocessing reaction yields and conversions (wt. %)	60
20. Deuterium content in coprocessed products	68

LIST OF FIGURES

Figure	Page
1. Representative infrared spectra of some starting materials and samples from the coprocessing reactions: (a) asphaltene fraction of Lloydminster residuum, (b) oil fraction of Lloydminster residuum, (c) residue from experiment 9, (d) residue from experiment 10, (e) asphaltenes from experiment 9, (f) oil from experiment 9.	31
2. Representative ¹ H NMR spectra of some samples from the coprocessing reactions: (a) asphaltene fraction of Lloydminster residuum, (b) oil fraction Lloydminster residuum, (c) asphaltene fraction from experiment 9, (d) oil fraction from experiment 9, (e) ² H NMR spectrum of asphaltene fraction from experiment 9, the intense resonance at 7.2 ppm is chloroform- <i>d</i>	32
3. Solvent separation of autoclave product	40
4. Methane-D distribution (%)	49
5. Ethane-D distribution (%)	50
6. Propane-D distribution (%)	51
7. Butane-D distribution (%)	52
8. Coal and asphaltene conversion (wt. % MAF)	62
9. Product yields (wt. %)	64
10. Reaction conditions, fraction yields, and D ₂ consumption (wt. % MAF)	66
11. Deuterium NMR spectra of solvent separated products coprocessed at 420°C for 0.5 hrs under 3000 psi D ₂ : oil (bottom), resin (middle), and asphaltene (top).	69
12. Total deuterium content (%)	70
13. Aromatic deuterium content (%)	71
14. Aliphatic deuterium content (%)	72
15. Alpha deuterium content (%)	73
16. Beta deuterium content (%)	74

LIST OF FIGURES, CONT'D.

Figure	Page
17. Gamma deuterium content (%)	75
18. Total H + D (mmol/g)	78
19. Aromatic H + D (mmol/g)	79
20. Aliphatic H + D (mmol/g)	80
21. Alpha H + D (mmol/g)	81
22. Beta H + D (mmol/g)	82
23. Gamma H + D (mmol/g)	83
24. [H + D]/C (mol/mol)	85

EXECUTIVE SUMMARY

Objectives:

The objective of this research was to investigate the fundamental reaction pathways in coal petroleum residuum coprocessing. Once the reaction pathways are defined, further efforts can be directed at improving those aspects of the chemistry of coprocessing that are responsible for the desired results such as high oil yields, low dihydrogen consumption, and mild reaction conditions.

We decided to carry out this investigation by looking at four basic aspects of coprocessing: (1) the effect of fossil fuel materials on promoting reactions essential to coprocessing such as hydrogen atom transfer, carbon-carbon bond scission, and hydrodemethylation; (2) the effect of varied mild conditions on the coprocessing reactions; (3) determination of dihydrogen uptake and utilization under severe conditions as a function of the coal or petroleum residuum employed; and (4) the effect of varied dihydrogen pressure, temperature, and residence time on the uptake and utilization of dihydrogen and on the distribution of the coprocessed products.

Accomplishments:

The new work with Illinois No. 6 coal, Wyodak coal, Lloydminster resid and Hondo resid provides new evidence to establish their influence upon hydrogen atom transfer reactions with tetralin- d_{12} and with tetralin- d_{12} and diphenylmethane, in fragmentation reactions with 1,3-diphenylpropane, and in hydrodemethylation reactions with 1,3-dimethylnaphthalene. The fossil fuel materials each individually accelerate the hydrogen atom transfer reactions of tetralin with the coals and resids and of tetralin with diphenylmethane. The degree of the hydrogen atom transfer reactions in mixtures that contain both coals and resids is essentially additive. The coals and resids also enhance the decomposition reactions of 1,3-diphenylpropane to toluene and styrene or ethylbenzene. However, the fossil fuels do not accelerate the hydrodemethylation of

1,3-dimethylnaphthalene at 400°C. The results for the three reaction probes suggest that selective hydrogen atom transfer reactions blend with initiation reactions and carbon-carbon scission reactions in subtle ways to produce novel coprocessing reactivity patterns, and imply that the addition of hydrogen atom donor solvents actually interferes with the utilization of the resid in the conversion of coal.

The experimental results from the coprocessing reactions of Illinois No. 6 and Wyodak coals with Lloydminster and Hondo residua under mild conditions strongly suggest that coprocessing proceeds via a stepwise reaction sequence in which the coal macromolecules are degraded in stages, first forming large polar asphaltenes that are subsequently converted into smaller, less polar oils. Adduction reactions of the aliphatic resid molecules to the aromatic coal molecules proceed at all stages of this chemistry. Indeed, some coal fragments appear in the oil at short reaction times. Hydrogen-transfer processes occur very rapidly among all the constituents, and dideuterium is added to the reaction products in the presence and absence of the molybdenum catalyst. The reactivity patterns for the four fossil materials suggest that their hydrogen-atom-transfer reactions have a significant influence on the course of the reaction. Our results suggest that the hydrogen donor properties of Illinois No. 6 coal may actually interfere with its conversion.

Analysis of the reactions of either Illinois No. 6 or Wyodak coal with Lloydminster or Hondo petroleum residua carried out at 420°C under 3000 psi of dideuterium has revealed in some detail how dihydrogen is essential to and utilized in the coprocessing reaction. The determination of deuterium uptake shows that, in terms of percent deuteration at the aromatic and aliphatic positions in the coal and residua molecules, the results are quite similar among the different combinations of coal and residua. However, some selectivity was observed among the solvent separated products. In three out of four reactions, percent deuteration generally decreased in the order of resin > asphaltene > oil. Clearly, the larger, more aromatic and polar constituents in the coal-residuum feedstock are more reactive in terms of deuterium uptake and exchange. This may reflect directly on the selectivity of the molybdenum based catalyst used in

this study. The evaluation of the results must also take into account that the levels of deuteration in the coprocessed products averaged approximately 25%. The $D/(H + D)$ ratio of the starting materials is 0.27 approximately. Therefore, the levels of deuteration of the coprocessed products are only moderately different than the values expected for complete equilibration of the system. All components of the system appear to be undergoing extensive hydrogen transfer and exchange chemistry.

Valuable information on the mechanistic aspects of the coprocessing reaction was provided by investigating the effects of pressure, temperature, and residence time on the dideuterium uptake and utilization, and on the distribution of coprocessing products. As pressure and then temperature were increased, trends that were not unexpected were observed in the values of the conversions and uptake and utilization of dideuterium. However, once 420°C was reached and then as residence time at this temperature was increased, important processes were observed. Coal conversion reached its maximum value after a preheat period of approximately two hours and an actual residence time at 420°C of 0.0 h, and at the same time, D-content at the alpha position reached its maximum value of approximately 36% in all the fractions after which it declined. In addition, the yield of the asphaltene fraction reached its maximum, and the reactivity of the asphaltene molecules in terms of dideuterium uptake reached its maximum level. All these observations are very closely related to the conversion of coal into toluene soluble products. The molybdenum catalyst is essential during this stage of the reaction in promoting coal conversion by capping reactive molecules and, most importantly, inhibiting non-reversible insoluble product condensation reactions. The maximization of asphaltene conversion was a function of residence time at 420°C in this series of batch autoclave reactions. As residence time at 420°C was increased, the processes upon which the conversion of asphaltene molecules to oil molecules depended became evident in terms of dideuterium uptake and utilization. Specifically, equilibration of deuterium throughout the system was being achieved. The % D-content at all the aromatic, alpha, beta, and gamma aliphatic positions is approaching the value of $D / [H + D] = 0.27$ of the initial feedstocks. The reactions which by themselves or in combination consisting of

reduction, adduction, fragmentation, and other processes that are essential to the molecular weight reducing processes that lead to oil molecules took place much less frequently than the uptake and exchange reactions that were responsible for the equilibration of deuterium. To improve the viability of the coprocessing reactions for commercial use, the two cost factors which must be addressed are the high levels of consumption of dihydrogen necessary for high levels of asphaltene conversion, and the concurrent destruction of the desired oil molecules due to their inability of the catalyst to selectively avoid them.

**SECTION I. THE REACTIVITY PATTERNS OF COALS AND RESIDS IN
HYDROGEN ATOM TRANSFER, CARBON-CARBON SCISSION, AND
HYDRODEMETHYLATION**

PREPARED BY KADIM CEYLAN AND LEON M. STOCK

INTRODUCTION

Coprocessing of coal and petroleum resid is a promising technology that has several potential technical and economic advantages (1,2), and the process is actively under study in several laboratories (3-13). In brief, coprocessing is fascinating because two substances, coal and petroleum resid, that are individually difficult to convert to a desirable product react thermally to provide a soluble, distillable product which has considerably more value as a transportation fuel than either of the starting materials. This favorable result can be realized in spite of the fact that subbituminous and bituminous coals are solids with high aromatic and heteroaromatic character and have low hydrogen to carbon ratios. The undesirable properties of coal are apparently counterbalanced by the desirable fluidity and high hydrogen to carbon ratios of the resids. Although coprocessing is a relatively mature technology, calls continue to be made that urge additional new work on the fundamental aspects of the reaction (2). In this situation, it seemed appropriate to study the chemistry of the process with the objective of achieving a greater understanding of the reactions that underlie the successful conversion of the coal macromolecules and the resid resins into soluble and distillable products.

Hydrogen transfer and carbon-carbon scission reactions in large measure dictate the outcome of direct thermal coal conversion reaction (13,14), and such process should also impact coprocessing. There is already some secure evidence for this viewpoint. Curtis and Chung found the coals and resids altered the rates of hydrogenation reactions and related processes such as hydrodenitritication and hydrodesulphurization (10). Bockrath *et al.* (13) showed that coals and resids accelerated the conversion of *cis*-decalin into *trans*-decalin and modified the product distribution in the hydromethylation of 1,3-dimethylnaphthalene.

Further, McMillen *et al.* (15) suggested that bimolecular, intermolecular hydrogen atom transfer reactions may contribute significantly to the degradation of coal macromolecular during coprocessing. Considerations of this kind implied that additional study of the influences of coals and resids on other probe reactions would be valuable to establish their influences on three important processes: hydrogen atom transfer, carbon-carbon scission, and hydrodemethylation. Specifically, the influences of four fossil materials, Illinois No. 6 and Wyodak coals and Lloydminster and Hondo resids, on the hydrogen atom transfer reactions of tetralin-*d*₁₂, on the carbon-carbon scission reaction of the relatively weak sp^3 carbon-carbon bond in 1,3-diphenylpropane, and on the carbon-carbon scission reaction of the relatively strong sp^2 carbon- sp^3 carbon bond in 1,3-dimethylnaphthalene were selected for examination on the basis of their successful use in prior investigations of coal (13,14,16,17).

EXPERIMENTAL

Equipment

The reactions were carried out in a SBL-2 fluidized sand bath reactor equipped with Techne TC-8D temperature control unit. Gas chromatographic analyses were carried out with a chromatograph interfaced with a data system and equipped with 5% OV-101 Chromosorb W. column (0.025 mm $\times$ 6.1 m). Gas chromatography mass spectroscopic analyses were performed with mass detector connected to a chromatograph with a DB 1701 (0.18 mm $\times$ 15 m) column. ^1H n.m.r. analyses were carried out with a 500 MHz spectrometer, and ^2H n.m.r. analyses were performed with a 400 MHz system. Infrared spectra were recorded on a SXB spectrophotometer. Methylene chloride and chloroform were used as solvents in the n.m.r. analyses. The infrared spectra were recorded by using potassium bromide pellets or sodium chloride discs.

Materials

Illinois No. 6 coal, Wyodak coal, Lloydminster resid and its fractions (asphaltene 16%, resin 10%, and oils 74%) and Hondo resid were supplied by Universal Oil Products, Inc.. The coal samples were 200 mesh size and were used as received. The microelemental analyses results are given in Table 1. Diphenylmethane-1,1- d_2 and triphenylmethane- d were used as internal standards in the ^2H n.m.r. analyses. These compounds were prepared by the reduction of benzophenone and triphenylmethyl alcohol, respectively as described in previous publications (18,19). Typically, benzophenone (3.65 g, 20 mmol), 10% palladium on carbon catalyst (0.36 g) and acetic acid-O- d (40 ml) were mixed in a reaction bottle to which dideuterium gas (30 psig) was added. The bottle was shaken and heated at 55-60°C. After 24 h, the pressure was released, the mixture was diluted with water, the catalyst was collected by filtration, and the products were extracted into ether. The reaction with triphenylmethane was repeated under the same conditions to achieve a high deuterium content. Evaporation of the solvent provided a crude product that was chromatographed on silica gel and *n*-hexane as the eluent. Spectroscopic analyses established that the benzylic positions of diphenylmethane-1,1- d_2 and triphenylmethane- d contained 97 and 93% deuterium, respectively.

Acetic acid-O- d was prepared from the anhydride. The other reagents and solvents were obtained commercially.

TABLE 1.
Analytical information for the fossil fuel materials

Proximate analysis (weight %)				
	Illinois No. 6		Wyodak	
Volatile matter	38.84		39.80	
Fixed carbon	45.80		36.70	
Moisture	4.08		16.42	
Ash	11.28		7.08	
Ultimate analysis (weight %, maf. basis)				
	C	H	S	N
Illinois No. 6 coal	78.8	5.51	3.43	1.59
Wyodak coal	71.0	5.50	0.98	0.92
Lloydminster resid	83.6	11.50	4.77	
Lloydminster asphaltene	82.0	7.98	7.58	1.38
Lloydminster resin	82.7	8.84	7.19	0.87
Lloydminster oil	84.1	9.95	3.91	0.65
Hondo resid	82.3	10.3	6.08	1.24

Procedure

Essentially the same procedure was used for the assessment of the reaction patterns of the fossil fuel materials in the hydrogen atom transfer reactions of tetralin and diphenylmethane, in the carbon-carbon scission reactions with 1,3-diphenylpropane, and in the hydrodemethylation of 1,3-dimethylnaphthalene. The fossil fuel materials (25 or 50 mg) and tetralin-*d*₁₂ (0.119 g, 0.819 mmol) and the other desired components were sealed in a glass capillary reactor (2.4 mm × 20 cm) under an argon atmosphere. The reactor was immersed horizontally in the sand bath that had been preheated to 400°C. After the desired reaction time, the reactor was taken out of the sand bath and cooled to ambient temperature. The contents were washed from the reactor with tetrahydrofuran and for the reactions with the coal and resids the mixture was filtered through a Soxhlet thimble. A Soxhlet extraction was carried out for 2-5 h, until the solvent in the thimble section became colorless. After the removal of tetrahydrofuran, the soluble fraction was extracted with *n*-hexane. The hexane soluble fraction was chromatographed on silica gel with *n*-hexane and tetrahydrofuran successively. The hexane eluate of the tetrahydrofuran solubles was analyzed by gas chromatographic and spectroscopic methods. The other soluble fractions were analyzed only by spectroscopic methods.

The compositions of the reaction mixtures and the reaction conditions are noted in Tables 2-5.

RESULTS AND DISCUSSION

Hydrogen atom transfer

The hydrogen-deuterium exchange reactions of the fossil fuel components with tetralin- d_{12} were studied to determine their capacity to abstract hydrogen (deuterium) from other molecules in the reaction medium.

Tetralin- d_{12} was selected for study because the selectivity of the hydrogen transfer reactions of the coal and resid can be assessed by measurement of the extent of exchange from the benzylic, α , aliphatic, β , and aromatic positions.

The results for Wyodak and Illinois No. 6 coal, Lloydminster and Hondo resid and the asphaltene, resin, and oil derived from the Lloydminster resid are summarized in Table 2.

As expected, the exchange reaction occurs selectively at the α position of tetralin. The extent of the exchange reaction at this position can be studied quite accurately by magnetic resonance spectroscopy. The incorporation of hydrogen in this position of tetralin increases with both the reaction time and with the amount of fossil material in the reaction system. The exchange reaction at the α position appears to follow first-order kinetics up to 60 min when 25 mg of the fossil material are present in the reaction. After 60 min or in the presence of larger quantities of coal, the exchange reaction slows as a consequence of the incorporation of hydrogen into tetralin and its selective abstraction from the partially labeled molecule. These observations are in agreement with the findings of previous studies (14,16,17).

TABLE 2.
The measured decrease in the deuterium content of the three positions of tetralin in the exchange reactions between tetralin- d_{12} and the fossil fuel materials^a

Reaction	Time (min)	Added fossil material	Weight ^b (mg)	Decrease in D content (%)		
				Ar, l	α	β
1	30	Illinois No. 6	25	0.3	13.2	3.4
2	60	Illinois No. 6	25	1.6	19.5	6.6
3	120	Illinois No. 6	25	1.0	22.2	5.6
4	30	Illinois No. 6	50	1.6	24.4	8.9
5	60	Illinois No. 6	50	3.6	28.0	6.8
6	30	Wyodak	25	1.3	10.4	4.2
7	60	Wyodak	25	2.6	15.6	6.4
8	120	Wyodak	25	0.3	20.2	5.6
9	30	Wyodak	50	1.5	18.6	7.4
10	60	Wyodak	50	2.6	21.9	5.6
11	30	Lloyd resid	25	1.6	7.8	1.4
12	60	Lloyd resid	25	0.5	12.6	3.1
13	120	Lloyd resid	25	1.8	16.9	6.9
14	30	Lloyd resid	50	1.3	13.7	3.0
15	60	Lloyd resid	50	1.3	21.3	1.1
16	30	Lloyd asphaltene	25	0.0	7.6	2.2
17	60	Lloyd asphaltene	25	3.4	15.4	5.9
18	30	Lloyd resin	25	0.0	8.0	1.8
19	60	Lloyd resin	25	1.4	14.4	1.9
20	30	Lloyd oil	25	0.6	7.6	2.3
21	60	Lloyd oil	25	0.9	10.7	3.0
22	30	Hondo resid	25	2.2	8.8	4.8
23	30	Hondo resid	50	1.9	17.5	9.8
24	60	Hondo resid	50	2.2	27.4	7.2
25	30	Lloyd resid and Illinois No. 6	25, 25	0.2	22.1	5.1
26	30	Lloyd resid and Wyodak	25, 25	2.9	16.4	5.3
27	30	Hondo resid and Illinois No. 6	25, 25	2.1	26.8	9.1
28	30	Hondo resid and Wyodak	25, 25	2.1	21.2	10.0

^aTetralin- d_{12} , 0.819 ± 0.002 mole, and the fossil fuel materials were sealed in glass vessels and reacted at 400°C

^bThe stated weights are accurate to $\pm 1\%$

TABLE 3.
The exchange reactions between tetralin-*d*₁₂ and diphenylmethane in the presence of fossil fuel components^a

Reaction	Time (min)	Added fossil material	Weight ^b (mg)	Change in deuterium content (%)			DPM ^c Methanol
				Aryl	T-d ₁₂ α	β	
1	30	None		0.9	8.2	3.5	19.6
2	60	None		1.0	10.7	3.1	28.2
3	120	None		0.0	15.9	5.8	38.5
4	30	Illinois No. 6	25	1.4	13.4	1.5	27.3
5	60	Illinois No. 6	25	1.4	24.9	4.4	45.4
6	120	Illinois No. 6	25	0.4	35.4	6.8	69.9
7	30	Illinois No. 6	50	1.4	28.0	7.9	22.4
8	60	Illinois No. 6	50	0.2	32.0	6.5	61.3
9	30	Wyodak	25	1.0	12.8	1.3	20.0
10	60	Wyodak	25	0.5	20.0	4.7	22.5
11	120	Wyodak	25	0.3	27.3	7.8	55.1
12	30	Wyodak	50	1.5	18.5	2.0	22.7
13	60	Wyodak	50	0.2	23.2	3.0	28.4
14	30	Lloyd resid	25	2.0	12.6	0.5	23.5
15	60	Lloyd resid	25	1.9	17.0	3.3	37.1
16	120	Lloyd resid	25	0.0	23.6	4.2	60.4
17	30	Lloyd resid	50	1.5	15.2	3.3	28.6
18	60	Lloyd resid	50	0.5	28.6	4.2	47.5
19	30	Lloyd asph	25	0.0	10.1	1.6	25.1
20	60	Lloyd asph	25	0.0	22.6	4.7	49.9
21	30	Lloyd resin	25	0.3	13.1	3.7	26.1
22	60	Lloyd resin	25	0.5	19.4	1.7	49.7
23	30	Lloyd oil	25	0.0	7.3	0.1	24.1
24	60	Lloyd oil	25	0.0	14.2	1.5	41.6
25	30	Hondo resid	25	1.1	12.7	4.6	21.8
26	30	Hondo resid	50	1.9	20.6	8.9	31.2
27	60	Hondo resid	50	2.3	33.8	9.7	61.9
28	30	Lloyd resid and Illinois No. 6	25, 25	0.5	17.7	2.9	26.2
29	30	Lloyd resid and Wyodak	25, 25	1.2	20.2	5.5	29.3
30	30	Hondo resid and Illinois No. 6	25, 25	2.4	29.5	12.3	36.6
31	30	Hondo resid and Wyodak	25, 25	1.9	24.6	9.3	27.7

^aTetralin-*d*₁₂ and diphenylmethane were equimolar at 0.819 ± 0.002 mmole, these substances and the fossil fuel materials were reacted in glass reactors at 400°C

^bSee Table 2

^cDiphenylmethane

TABLE 4.
Decomposition of 1,3-diphenylpropane neat and in tetralin-*d*₁₂

Decomposition of 1,5-diphenylpropane near and in tetralin at 170°C						
			Yield (%) ^a			
Added fossil material		Weight (mg)	DPP (% decomposed)	C ₆ H ₅ CH ₃	C ₆ H ₅ C ₂ H ₅	C ₆ H ₅ C ₂ H ₃
Neat reactions ^b						
1	None		46	85	11	14
2	Illinois No. 6	5	80	90	37	7
3	Wyodak	7	71	94	31	9
4	Lloydminster	11	66	96	28	11
5	Hondo	10	82	94	34	6
Reactions in tetralin- <i>d</i> ₁₂ ^c						
6	None		50	98	11	24
7	Illinois No. 6	51	53	93	59	4
8	Wyodak	50	44	106	63	4
9	Lloydminster	51	65	106	53	3
10	Hondo	54	71	85	37	4

^aThe yield data indicate the amounts of toluene, ethylbenzene and styrene that were detected at the end of the experiment, i.e. the fossil material-free reaction in tetralin-*d*₁₂ led to the decomposition of 50% of the diphenylpropane; 98% of the toluene that could have been formed was detected but only 35% of the two carbon atom products that should have been produced were obtained

^bThe fossil material was suspended in 0.819 mmole of 1,3-diphenylpropane in a glass vessel and heated at 100°C for 30 min ^cThe fossil material was suspended in a mixture of 0.819 mmol of 1,3-diphenylpropane and 0.819 mmol of tetralin-*d*₁₂ in a glass vessel and heated at 400°C for 30 min

TABLE 5.
The reactions of tetralin-*d*₁₂ and 1,3-dimethylnaphthalene in the presence of coals and resids^a

Reaction	Added fossil material (mg)	Time (min)	Decomposition of 1,3-DMN (%)	Product ratio 2-MN/I-MN
1	None	30	0.0	-
2	None	120	1.0	-
3	Illinois No. 6(5)	120	2.5	1.7
4	Illinois No. 6(25)	120	3.4	2.1
5	Wyodak (25)	120	4.1	3.1
6	Lloydminster(25)	120	2.7	1.5
7	Hondo(25)	120	3.2	2.2

^aTetralin-*d*₁₂, 0.819 mmole, and 1,3-dimethylnaphthalene, 25mg, 0.16 mmole, were reacted in glass capillary reactors at 400°C

TABLE 6.
Influences of coals and resids on hydrogen atom transfer from the α position of tetralin

	Illinois No. 6 coal	Wyodak coal	Hondo resid	Lloydminster resid
30 min reaction				
Weight basis (mmol α -D/mg)	0.017	0.013	0.011	0.010
Hydrogen basis (mol α -D/mol H)	0.31	0.24	0.11	0.087
60 min reaction				
Weight basis (mmol α -D/mg)	0.025	0.021	0.018	0.016
Hydrogen basis (mol α -D/mol H)	0.45	0.38	0.18	0.14

TABLE 7.
Influence of resid constituents on hydrogen atom transfer from the α position of tetralin

	Asphaltene	Resin	Oil
Weight basis (mmol α -D/mg)	0.020	0.019	0.014
Hydrogen basis (mol α -D/mol H)	0.25	0.21	0.14

The extent of exchange at the α position was used to evaluate the hydrogen atom transfer behavior of the fossil fuels. The information in Table 2 establishes the reactivity patterns that are shown in Table 6.

The observations need to be interpreted within the framework of the idea that the coals and resids decompose to produce reactive radicals that abstract deuterium atoms from surrounding solvent molecules and that the tetralyl- d_{11} radicals, in turn, abstract hydrogen atoms from the coals and resids.

Hydrogen atom transfer is a very prevalent reaction during coprocessing. The results indicate that the coals exchange 25 to 30% of their available hydrogen atoms with tetralin- d_{12} in 30 min, and that the resids exchange about 10% of their hydrogen atoms in the same interval. The differences between the coals and the resids are only moderately reduced in the 60 min experiments. Clearly, hydrogen transfer reactions are extremely rapid processes under coprocessing conditions. As discussed subsequently, all of the coals and resids can be regarded as initiators and as hydrogen atom donors. The observations for the reactions in tetralin- d_{12}

demonstrate that Illinois No. 6 coal is significantly more effective in enhancing the exchange reaction than the other fossil materials in the 30 min reactions. Its superior characteristics are evident even after 60 min. Wyodak coal also undergoes exchange more readily than the resids on a weight or hydrogen availability basis in the 30 min reaction, but this substance is clearly less reactive than Illinois No. 6 coal. Both resids have a much higher hydrogen content than the coals, and both resids are less able to exchange hydrogen atoms with tetralin- d_{12} . However, it should be stressed that the difference becomes less significant in the 60 min reactions. The possibly unexpected high reactivity of the resids may arise from their high sulphur contents. Although the structures of the organosulphur compounds in these resids are not known, it seems reasonable to postulate that these substances or, more likely, their thermal degradation products such as hydrogen sulphide may enhance the hydrogen transfer reactivity of the resid at long reaction times (20). This suggestion is in accord with the fact that hydrogen sulphide is often added to coprocessing reaction systems to accelerate the formation of desirable products (21,22).

Lloydminster resid was fractioned into three components and the influences of these substances on the hydrogen-deuterium reactions of tetralin- d_{12} were assessed. The extent of exchange from the α positions with the Lloydminster resid fractions at 50 min reaction times are shown in Table 7.

The reactivity on the basis of hydrogen availability provides a clearer representation of the reactivity pattern of these components. The hydrogen atoms in molecules that constitute the asphaltene undergo hydrogen transfer significantly more rapidly than those in the oil.

Many workers in the field have argued that synergistic interactions between the coals and the resids may be important for the achievement of high conversions to desirable products in coprocessing. Four experiments (entries 25-28 in Table 2) were carried out in an attempt to detect synergistic effects in the degree of hydrogen-deuterium exchange in the coal-resid mixtures. Comparisons of the amounts of deuterium in these reactions with the deuterium exchanged in experiments 1, 6, 11 and 22 suggest that synergistic effects are slight and that an additivity rule applies for these coal-resid mixtures. For example, a total of 21 units of deuterium exchange may be expected in reaction 25 since under the same conditions Illinois No. 6 and Lloydminster resid exchanged 13.2 units of D (reaction 1) and 7.8 units of D (reaction 11), respectively. Similarly, a total exchange of 18.2 units of D may be expected for reaction 26, since Wyodak coal exchanged 10.4 units of D in reaction 6 and Lloydminster resid exchanged 7.8 units of D in reaction 11. The experimentally determined values for reactions 25 and 26 are 22.1 and 16.4, respectively. Considering the experimental errors in the determination of the

deuterium content of tetralin, the measured and predicted values are in good accord with the concept of additivity. Indeed, only one hydrogen-deuterium exchange reaction, the reaction of Hondo resid and Illinois No. 6 coal (reaction 27) provides any evidence for a synergistic effect. However, the difference between the predicted and the determined values does not appear to be large enough to ensure that a synergistic effect has been demonstrated. The precision realized in the duplicate ^2H n.m.r. analyses showed that the errors in the deuterium content of tetralin is $\pm 2\%$. Considering this analytical uncertainty, the difference of 4.8 ($26.8 - 22.0 = 4.8$) units of deuterium between the predicted and observed values is just beyond the limits of error, and it seems unwise to infer that synergistic interactions play a major role in this aspect of the chemistry.

Another hydrogen atom transfer reaction was investigated to gain an additional perspective in the reactivity of the fossil fuel components. The hydrogen-deuterium exchange between tetralin- d_{12} and diphenylmethane was chosen for this purpose because the exchange reactions of these molecules have been extensively investigated in the presence of an array of compounds (14,15,16,23).

It should be mentioned that diphenylmethane is stable under reaction conditions. Indeed, it was found that 85-95% of the material could be readily recovered from the very complex reaction mixtures and that neither benzene nor toluene, the principal decomposition products were present. The influences of the coals and resids on the exchange reactions of diphenylmethane are presented in Table 3.

The hydrogen-deuterium exchange, which occurs selectively at the benzylic positions in tetralin- d_{12} and diphenylmethane, and increases with the reaction time, is accelerated by the coals and resids. The information can be conveniently analyzed on the basis of the degree of equilibration of the hydrogen and deuterium content of the two benzylic positions in the two molecules, but as discussed subsequently, the exchange reactions of the coals and resids complicate the interpretation of the results. In the absence of a fuel component, the deuterium content at the benzylic position of diphenylmethane is far from the equilibration value, 66.7% deuterium, even after a 120 min reaction. All of the coals and resid components accelerate the reaction. In point of fact, the equilibration value for the benzylic positions of tetralin and diphenylmethane is reached in less than 120 min with 25 mg Illinois No. 6 coal. The influences

of the other materials are more modest. The results for the 30 and 60 min experiments are assembled for convenient comparison in Table 8.

TABLE 8.
Influence of coals and resids on the transfer of deuterium from tetralin- d_{12} to diphenylmethane

	Illinois No. 6 coal	Wyodak coal	Hondo resid	Lloydminster resid	None
D in DPM (%) 30 min	27.3	20.0	21.8	23.5	19.6
D in DPM (%) 60 min	45.4	22.5		37.1	28.2
	Asphaltene	Resin	Oil		
Lloydminster resid					
D in DPM (%) 30 min	25.1	26.1	24.1		
D in DPM (%) 60 min	49.9	49.7	41.6		

The pattern of reactivity that was established in these experiments differs from the reactivity order that was deduced from the experiments with the fuels and tetralin- d_{12} along. That reaction sequence is determined by the ability of the fossil materials to initiate the reaction and to denote hydrogen atoms to tetralyl radical. The reaction sequence deduced from the data for the reactions in the presence of diphenylmethane is a better measure of the initiation events because a large amount of diphenylmethane is present and it is an effective hydrogen donor.

The occurrence of this reaction reduces the importance of the hydrogen donor properties of coal in determining the degree of exchange. The results for the short duration experiments are probably more reliable indicators of this feature of the chemistry. Illinois No. 6 coal is the most effective initiator for hydrogen atom exchange, but Lloydminster and Hondo resid are surprisingly effective. Wyodak coal is not. It is pertinent to note that Illinois No. 6 coal is simultaneously the most effective initiator and hydrogen donor. The latter property of this material was originally recognized by Collins *et al.* (24) more than 10 years ago. However, it is difficult at this stage of the study to relate the observations to one particular constituent, for example the sulphur compounds in Illinois No. 6 coal or the metallic constituents of the resids.

Although the synergistic effects of the coals and the resids were investigated (entries 28-31 in Table 3), the necessary presence of 50 mg fossil material in the reaction mixture complicates the interpretation of the results because hydrogen transfer from the coal to the tetralyl-*d*₁₁ and diphenylmethyl radicals obviates a simple analysis of the results on the basis of the role of the fossil materials as initiators. Nevertheless, it is appropriate to note that a rather novel pattern of reactivity emerges in which Illinois No. 6 coal and Hondo resid accomplish the greatest degree of hydrogen atom transfer to diphenylmethane, 36.6%, whereas Illinois No. 6 coal and Lloydminster resid accomplish the least, 26.2%.

The reactions of the coals and the resids with 1,3-diphenylpropane were studied to gain more perspective on their influence on the rate of facile sp³ carbon-sp³ carbon bond fragmentation reactions as illustrated in the equations.

The initial β-bond scission products are converted to toluene and ethylbenzene in subsequent reactions. It is also known that the 1,3-diphenyl-1-propyl radical and the benzyl radical react with the coals and resids and with styrene to form adducts. Since it is difficult to measure the yields of the diverse array of adducts, we measured the amount of 1,3-diphenylpropane that disappeared during the reaction. We also determined the toluene, styrene and ethylbenzene yields to assess the extent of adduct formation. In the first set of experiments, we examined the decomposition of 1,3-diphenylpropane, 125 to 140 mg, in the absence of another solvent, but in the present of small quantities, 5 to 10 mg, of the coals and resids at 400°C for 30 min in an argon atmosphere in a glass reaction vessel. Diphenylmethane was added to the reaction system at the end of the experiment to serve as a quantitation standard for analysis by g.c. The results for these experiments are shown in the top five entries of Table 4.

It is important that small quantities of the additives have such a large influence on rate of the reaction. 1,3-Diphenylpropane undergoes decomposition rather rapidly at 400°C. In the absence of any other substance, approximately 46% of the substance is converted to other materials. Toluene is formed in 85% yield, but the sum of the ethylbenzene and styrene yields,

25%, indicates that more than 75% of the two carbon fragmentation products are diverted into other products, presumably by adduction reactions with other intermediates derived from the starting materials as shown.

Small amounts of the fossil fuel materials (1 to 2 mg per 25 mg of 1,3-diphenylpropane) have a profound influence on the reaction. The conversion of 1,3-diphenylpropane increases by 20 to 5%, the toluene yield increase modestly, and the ethylbenzene yield increases significantly. On a weight basis, it is found that the observed enhancements occur in the order

Illinois No. 6 (6.9) > Wyodak (3.7) = Hondo (3.7) > Lloydminster (1.8)*

These results imply that the fossil fuels act as initiators of the decomposition reaction by their capacity to serve as sources of free radicals, and that only small quantities of the fossil fuels are necessary to demonstrate this effect. Illinois No. 6 coal is clearly the most effective substance, whereas Lloydminster resid is the poorest initiator. It is interesting that Lloydminster resid also produces the smallest quantity of ethylbenzene among the four substances examined in this study.

In the next series of experiments, we examined the decomposition of 1,3-diphenylpropane (158 mg, 0.819 mmole) in the presence of tetralin-*d*₁₂ (116 mg, 0.819 mmole), and a relatively large quantity of the fossil material (50 mg). The results of these experiments are presented in entries 6-10 in Table 4.

The reaction in the presence of tetralin-*d*₁₂ and the fossil material proceeds to about the same extent, 50%, as it does in the neat system, 46%. The extent of the reaction in each system depends upon the concentrations of the initiation reagents and the chain length. These cannot now be specified. It is clear, however, that the decomposition reaction of 1,3-diphenylpropane in the presence of both tetralin-*d*₁₂ and the fossil material is suppressed in three of four cases. In

* Calculated on basis of $[(\% \text{DPP conversion in presence of fossil material}) - 46.2] [\text{weight of fossil material}]^{-1}$

contrast, the conversion in the presence of Lloydminster resid remains low and unaltered. The suppression of the decomposition by tetralin-*d*₁₂ strongly suggests that this effective hydrogen donor interferes with the course of the decomposition reaction by the addition of hydrogen to the 1,3-diphenyl-1-propyl radical. The high yields of toluene that are observed also indicate the donor characteristics of the system.

Indeed, large amounts of fossil fuel initiators such as Illinois No. 6 coal cannot overcome the propensity of tetralin to donate hydrogen atoms. The influences of the fossil materials on the decomposition of 1,3-diphenylpropane in tetralin-*d*₁₂ are in the order: Hondo > Lloydminster > Illinois No. 6 > Wyodak.

It was also established that tetralin-*d*₁₂ underwent exchange to a greater degree in the reaction system with Illinois No. 6 coal (α -D content, 79%) than in the reaction system with Lloydminster resid (α -D content, 87%). Thus, the fossil substances that are the least able to participate in hydrogen atom transfer provide the greatest degree of conversion of 1,3-diphenylpropane. An important new lesson in these results is that hydrogen donation is not necessarily a desirable property for coal conversion chemistry when fragmentation reactions are necessary. Excess hydrogen donor capacity in such systems will hamper the depolymerization of coal molecules.

Appreciable amounts of low molecular weight hydrocarbons can form during the thermal conversion reactions of fossil fuels. These reactions are not desirable in direct coal liquefaction or coprocessing because they consume valuable amounts of hydrogen. Thus, the principal objective has been to convert coal to liquids or soluble products that retain as much of the original carbon and hydrogen as possible, with only the minimum necessary changes in the original molecular structure. Generally, low temperatures are preferable, but coprocessing reactions are often carried out in the temperature range between 400 and 450 C. Although thermal homolytic reactions are not rapid at these temperatures, hydrodealkylation reactions may be important. Bockrath *et al.* (13) developed a new method to study this feature of the chemistry by examining the influence of coals and other fossil materials on the extent of hydrodemethylation of 1,3-dimethylnaphthalene. They reported that the selectivity of the reaction depended upon the nature and quantity of the fossil material in the reaction system. Specifically, they observed that the formation of 2-methylnaphthalene was twice as rapid as the formation of 1-methylnaphthalene. Their approach was adopted in this study to provide

information about the extent of hydrodealkylation reactions that result from the hydrogen atoms formed from the fossil materials, or from tetralin by direct deuterium atom transfer.

The results are presented in Table 5.

The hydrodemethylation of 1,3-dimethylnaphthalene is very slow at 400°C in tetralin. This arylmethane is recovered from the reaction system quantitatively after 30 min and, after 2 h < 1% of the material is converted to monomethylnaphthalene. However, 2 to 4% decomposition was observed in the presence of coals and resids. The extent of the reaction depends upon the amount and nature of the fossil material. Although the differences are modest, the order of reactivity appears to be Wyodak > Illinois No. 6 > Hondo > Lloydminster. 2-Methylnaphthalene is produced selectively as expected on the basis of the results of Bockrath *et al.*

McMillen *et al.* (15) showed in work with model compounds that the selectivity of attack at the 1 and 2 positions of naphthalene depended upon the hydrogen atom donor responsible for the attack, and they pointed that the free radical reactivity and selectivity are inversely proportional. The reactive hydrogen atoms may be provided by dihydrogen or another donor structure. Since there was no dihydrogen in our experiments, the hydrogen atoms must have been provided by the donor solvent or the fossil materials. The experiments with tetralin-*d*₁₂, the first two entries in Table 5, indicate that hydrodemethylation by hydrogen(deuterium) atom transfer from tetralin occurs only very slowly. This reaction does not appear to contribute importantly in coprocessing under the conditions of these experiments, 400°C for 2 h. Decomposition does occur to a modest, 2-4% extent in the presence of the fossil materials when the reactions are allowed to proceed for 2 h at this temperature. The new information suggests

that the hydrogen atoms that are formed as a result of the thermal decomposition of the coals and resids hydrodemethylate 1,3-dimethylnaphthalene. Since the ratio of 2-methylnaphthalene to 1-methylnaphthalene is above 2, the reaction proceeds selectively. However, it must be emphasized that hydrodemethylation of dimethylnaphthalene is a very slow reaction relative to the many other hydrogen atom transfer reactions that occur during coprocessing.

CONCLUSION

The new work with Illinois No. 6 coal, Wyodak coal, Lloydminster resid and Hondo resid provides new evidence to establish their influence upon hydrogen atom transfer reactions with tetralin- d_{12} and with tetralin- d_{12} and diphenylmethane, in fragmentation reactions with 1,3-diphenylpropane, and in hydrodemethylation reactions with 1,3-dimethylnaphthalene. The reactions were carried out in glass reactors at 400°C. The fossil fuel materials accelerate the hydrogen atom transfer reactions of tetralin with the coals and resids and of tetralin with diphenylmethane. The degree of hydrogen atom transfer in mixtures that contain both coals and resids is essentially additive. The coals and resids also enhance the decomposition reactions of 1,3-diphenylpropane to toluene and styrene or ethylbenzene. However, the fossil fuels do not accelerate the hydrodemethylation of 1,3-dimethylnaphthalene at 400°C. The results for the three reaction probes suggest that selective hydrogen atom transfer reactions blend with initiation reactions and carbon-carbon scission reactions in subtle ways to produce novel coprocessing reactivity patterns, and imply that the addition of hydrogen atom donor solvents actually interferes with the utilization of the resid in the conversion of coal.

It is pertinent to mention that the reactions in our laboratory were carried out at relatively low conversion (about 50%) so that the threshold, limiting behavior of the coals and resids could be identified. These threshold, limiting characteristics can be overcome by conducting the reaction at very high severity with prolonged reaction times and high dihydrogen pressure at 420°C. Desirable essentially complete conversions can be realized under these conditions. However, this tactic is costly since high severity provides numerous undesirable gaseous fragmentation products. Clearly, there is a need for a practical process that operates at low severity. Any practical attempts to improve the coprocessing process so that it can be conducted at low reaction severity will need to consider the new results of our investigation in the innovative design of new favorable processing conditions.

**SECTION II. REACTION OF ILLINOIS NO. 6 AND WYODAK COALS WITH
LLOYDMINSTER AND HONDO RESIDUA UNDER MILD CONDITIONS**

PREPARED BY KADIM CEYLAN AND LEON M. STOCK

INTRODUCTION

Over the past few years a number of processes have been developed for the direct liquefaction of coal to produce distillate fuels. Typically, these processes involve thermal degradation of the macromolecular structure of coal and are followed by hydrogenation to stabilize the degraded material and increase the hydrogen to carbon ratio of the products. The conversion of coal structure is thought to occur in stages (25). In broad terms, structural elements that cross-link the coal macromolecule are thermally cleaved to produce smaller molecular fragments. The reactive fragments and other components of the macromolecule are then converted to stable substances by hydrogen atom transfer from the coal and from the solvent and the dihydrogen atmosphere. In conventional coal liquefaction technology, a hydrogenated coal derived solvent is used for the production of high-quality liquid fuels or soluble products. Coprocessing of coals with petroleum residua is being developed as an alternative route to direct liquefaction. It is generally believed that the heavy petroleum residua in coprocessing serve as slurring liquids and as sources of hydrogen atoms; in essence the residua replace the donor solvent in direct liquefaction (6,10,11,26,27).

As already mentioned in Section I, coprocessing of petroleum residua with coals is a bridge between coal liquefaction and hydrocracking that simultaneously upgrades coal and heavy petroleum residua. A review of the activity in this field suggests that special advantages may accrue from the coprocessing of coals with residua (5). But, it is well recognized that a better understanding of the chemistry of coprocessing is essential for the improvement of the technology. Therefore, coprocessing has received recent attention and new effort has been directed to elucidate the reaction pathways. Previous batch autoclave screening tests showed that the coprocessing of Illinois No. 6 coal and Wyodak coals with Lloydminster and Hondo residuum increased the liquefaction yields of these substances (22,28). Other basic studies have examined the hydrogen atom exchange, hydrogen atom transfer, and carbon-carbon bond cleavage reactions that may occur during coprocessing (13,14,17,28,29,30).

It seemed appropriate to establish the relationship between the basic work and the reaction pathways that are involved in coprocessing more securely. Accordingly, we have studied the coprocessing reactions of Illinois No. 6 and Wyodak coal with Hondo and Lloydminster residua under reaction conditions that were used to investigate the influence of these fossil materials on hydrogen atom transfer and carbon-carbon cleavage reactions in order to gather further information.

EXPERIMENTAL

Materials and Equipment

The coals, residua, residua fractions, and the reference catalyst were supplied by John G. Gatsis of the Allied Research Center. The analytical properties of coals and residua are given in Table 9.

TABLE 9
Analytical data for the fossil fuel materials^a

Fossil fuel material	ultimate analysis, wt % (maf)			
	C	H	S	N
Illinois No. 6 coal	78.8	5.51	3.43	1.59
Wyodak coal	71.0	5.50	0.98	0.92
Lloydminster residuum	83.6	11.5	4.77	b
Hondo residuum	82.3	10.3	6.08	1.24

^aThese data were provided by John Gatsis of Allied Signal Corp.

^bThe nitrogen content was not determined.

The reactions were carried out in a SBL-2 fluidized sand bath equipped with a Techne TC-8D temperature control unit. Three types of reactors were used in this study. The glass capillary reactors were 2.4 mm (i.d.) × 20 cm, the glass tubular reactors were 5 mm (i.d.) × 20 cm, and the stainless steel (SS) reactors had an internal volume of 4.5 mL. The reference catalyst was a molybdenum-based UOP proprietary catalyst. It was not pretreated before use. The other chemicals that were used in this study were available commercially, and they were purified as necessary before use.

Nuclear magnetic resonance spectroscopy for ¹H was performed with the University of Chicago 500-MHz system and ²H analysis was performed with a Varian XL-400 system. Infrared spectra were recorded with a Nicolet 20 SX spectrometer.

Procedure

The procedures for coprocessing were closely parallel to the procedures that were used in the previous study (12). The total quantity of material in the reactors was approximately 75 mg for the glass capillary reactors, 500 mg for the glass tubular reactors, and 1.2 g for the stainless steel reactors. A mixture of the fossil fuel material, in which the residuum and coal were combined in

a 2:1 ratio (maf basis), was placed into the reactor, and it was carefully sealed under an atmospheric pressure of argon or pressurized with argon or dideuterium. The starting cold argon or dideuterium gas pressure in the stainless steel reactors was approximately 500 psig. Before the reactor was pressurized with dideuterium, it was filled with argon and leak tested at 1500 psig. The reaction vessels were then immersed into the sand bath which has been preheated at 400°C. The reactor was vigorously shaken during the reaction. At an appropriate time, the reactor was removed from the sand bath and cooled immediately by immersing it in water. The glass reactors were cut and the stainless steel reactors were carefully vented to the atmosphere and then opened. The reactor contents were extracted into tetrahydrofuran and filtered and the residue was Soxhlet extracted with tetrahydrofuran. The soluble product was fractionated into asphaltenes (*n*-heptane insoluble), resins (*n*-heptane soluble, *n*-pentane insoluble), and oils (*n*-pentane soluble) by successive extractions with *n*-heptane and *n*-pentane, according to the procedure suggested by Speight and his co-workers.

RESULTS AND DISCUSSION

Coprocessing

Illinois No. 6 and Wyodak coal were coprocessed with Lloydminster and Hondo residuum in the presence and absence of dideuterium and in the presence and absence of a molybdenum catalyst at 400°C for 1 h. These fossil materials were selected for study because information about their behavior in previous autoclave screening tests was already available (22,28). The earlier coprocessing work with these materials was carried out at 420°C for 2 h with a high pressure of dihydrogen, 3000 psi. Under these conditions, Gatsis and his co-workers achieved very high conversions of the coals into tetrahydrofuran soluble products. We elected to examine the same fossil materials under much milder conditions so that the conversion of the coals would be less complete, and the influences of selected reaction parameters on the product yield and distribution could be investigated. Accordingly, the reaction temperature was decreased to 400°C, and the reaction time was decreased to 1 h. Dideuterium was used in some experiments, but at 500 psi initial pressure. The results are summarized in Table 10.

TABLE 10.
Coproprocessing reactions of fossil fuels

entry	coal and resid	reactor	gas	catl, ^b %	conv. wt%	soluble product company		
						asph	resin	oil
1	Illinois No. 6 + Lloydminster	tubular	Ar		44.2	28.7	9.7	61.6
2	Illinois No. 6 + Lloydminster	tubular	Ar		53.9	21.7	11.2	67.1 ^c
3	Illinois No. 6 + Hondo	tubular	Ar		41.5	35.1	10.1	54.8
4	Wyodak + Lloydminster	tubular	Ar		51.5	25.5	10.8	63.6
5	Wyodak + Hondo	tubular	Ar		47.1	29.1	10.5	60.4
6	Illinois No. 6 + Hondo	SS	Ar		39.8	54.5	3.1	43.0
7	Wyodak + Hondo	SS	Ar		43.2	28.0	8.3	63.6
8	Illinois No. 6 + Lloydminster	SS	D ₂		27.8	27.6	12.1	60.1 ^d
9	Illinois No. 6 + Lloydminster	SS	D ₂		51.5	33.5	3.3	63.2
10	Wyodak + Lloydminster	SS	D ₂		56.2	34.4	4.2	61.4
11	Illinois No. 6 + Lloydminster	SS	Ar	1	50.0	50.0	7.0	43.1
12	Illinois No. 6 + Hondo	SS	Ar	1	40.3	54.5	2.1	43.4
13	Wyodak + Lloydminster	SS	Ar	1	52.0	48.0	9.0	43.0
14	Wyodak + Hondo	SS	Ar	1	56.1	45.3	7.0	47.7
15	Illinois No. 6 + Lloydminster	SS	D ₂	1	53.0	33.1	7.1	59.1
16	Wyodak + Lloydminster	SS	D ₂	1	56.5	35.6	11.0	53.4
17	Illinois No. 6 + Lloydminster	capillary	Ar		40.8	22.0		78.0 ^e
18	Wyodak + Lloydminster	capillary	Ar		39.1	25.0		75.0 ^e

^aThe reactions were carried out at 400°C for 1 h. The coal conversion is based upon the quantity of insoluble residue. ^bThe weight percent catalyst concentration was calculated from 100 (molybdenum/coal(maf)). ^cThis reaction was carried out for 90 min. ^dThis reaction was carried out for 15 min. ^eThe yield of n-heptane-soluble material is reported.

Coal conversion was the principal parameter that we used to evaluate the results. The conversion values were calculated on the basis of the transformation of the insoluble coal into tetrahydrofuran-soluble materials. As expected, the conversions that are presented in Table 10 are considerably less than the conversions that were reported by Gatsis and his co-workers for the same fossil fuels under more severe conditions (22,28). These results were not unexpected inasmuch as batch autoclave studies have shown that the dihydrogen pressure and other process variables have significant effects on coal conversion (6,32).

We were concerned that the use of small reaction vessels might adversely affect the results and took special precautions to ensure that the contents of the vessels were well mixed before the reaction and to agitate the vessels vigorously during the reaction. Reaction work up also presented some problems. Reactions in glass capillary tubes, which were performed to provide products for spectroscopic studies, had material balances that ranged from 75 to 85%. The work with glass tubular reactors and stainless steel reactors gave much better results with 85-92% material balances. Replicate experiments indicate that the yields and conversions are

defined to $\pm 4\%$. We shall focus attention on the quantitative observations for the reactions that were carried out in glass tubular reactors and stainless steel vessels.

The reaction time is an important variable. An increase in the reaction times for the coprocessing of Illinois No. 6 coal and Lloydminster residuum from 60 to 90 min in an inert atmosphere increased the conversion from 44 to 54%. Similarly, an increase in the reaction time for the coprocessing of the same substances from 15 to 60 min in a dideuterium atmosphere increased the conversion from 28 to 52%. These findings are in accord with the results and conclusions of Gatsis and his co-workers who also pointed out that the incremental increase diminished after the first 60 min (22,28). The observations for Illinois No. 6 coal and Lloydminster residuum indicate that the use of dideuterium increases the conversion from 44 to 52%, the use of a catalyst increases the conversion from 44 to 50%, and the incorporation of both a catalyst and dideuterium increases the conversion to 53%. The oil yields are not impacted in the same way. The addition of the catalyst in the absence of dideuterium actually reduces the oil yield from 27 to 22%. Indeed, the highest oil yield was observed when the reaction was carried out with dideuterium but in the absence of the catalyst. The conversions of Wyodak coal and Lloydminster residuum are less dependent upon the reaction conditions. However the trends in the data for this pair of fossil materials are similar. In particular, the highest yield of oil is realized in the presence of dideuterium and the absence of the catalyst.

Lloydminster residuum is more effective than Hondo residuum for the conversion of Illinois No. 6 and Wyodak coals in the absence of a catalyst in an inert atmosphere. Our results also show that the reaction of Lloydminster residuum and Wyodak coal under these conditions provides a higher degree of conversion and more oil than the reaction of this residuum with Illinois No. 6 coal. The same situation prevails for the reactions that were carried out with dideuterium in the presence and absence of the catalyst. Although the differences are not large, they are readily perceptible.

Reactivity Patterns

We have compared the results of the coprocessing experiments with the results that were obtained in previous experiments (29) designed to probe the free-radical chemistry of the fossil materials in hydrogen atom exchange and carbon-carbon scission processes under the conditions of coprocessing. The results are presented in Table 11.

TABLE 11.
Reactivity patterns in coprocessing and probe reaction systems

		order of reactivity			
		Illinois No. 6 Lloyd- minster	Illinois No. 6 Hondo	Wyodak Lloyd- minster	Wyodak Hondo
Coprocess without Catalyst at 400 °C for 1 h					
coal conversion		3rd	4th	1st	2nd
oil yield		3rd	4th	1st	2nd
Coprocess with Catalyst at 400 °C for 1 h					
coal conversion		3rd	4th	2nd	1st
oil yield		3rd	4th	2nd	1st
Exchange of Hydrogen with Tetralin- <i>d</i> ₁₂ at 400 °C for 1 h					
benzylic exchange		2nd	1st	4th	3rd
		order of reactivity			
		Illinois No. 6	Wyodak	Hondo	Lloyd- minster
Exchange of Hydrogen with Tetralin- <i>d</i> ₁₂ at 400 °C for 1 h					
Benzylic exchange		1st	2nd	3rd	4th
Decomposition of 1,3-Diphenylpropane at 400 °C for 1 h					
conversion		1st	2nd,3rd	2nd,3rd	4th

The order of reactivity for coprocessing without a catalyst is exactly inverse to the order of reactivity of the same pairs of fossil materials in the exchange of hydrogen atoms with tetralin-*d*₁₂ under the same experimental conditions. The order of reactivity in the molybdenum-promoted coprocessing reaction is also essentially inverse to the reactivity pattern for exchange with tetralin-*d*₁₂. Previous work with 1,3-diphenylpropane suggested that Illinois No. 6 coal was the most effective initiator as well as the most effective hydrogen atom donor among the four fossil materials and that Lloydminster residuum was the least effective initiator as well as the least effective hydrogen atom donor. The complete sequences for these probe reactions are presented in Table 11. Although it is difficult to provide a comprehensive interpretation of the observations for the complex coprocessing system at this time, it is relevant to consider the chemistry of the thermolytic reactions of the coals and resids. Success in coprocessing depends upon facile initiation reactions and the occurrence of uninterrupted chain propagation sequences that redistribute hydrogen atoms, fragment the large coal and residuum molecules, and enhance the solubility through adduction. Parallel heteroatom removal reactions are also essential. This chemistry is outlined for a non-catalytic thermal process in the scheme.

Scheme. Pathways in Coprocessing^a

Initiation Reactions

coal → coal fragment radical

residuum → residuum fragment radical

Propagation Reactions

coal fragment radical + residuum hydrocarbon → coal fragment + residuum radical

coal fragment radical + coal → coal fragment + coal radical

^aMany reactions, for example, the β-scission reactions that produce hydrogen atoms, the chemistry of the adduction product radicals, the deoxygenation network, etc., are not shown in this terse illustration.

Free-radical decomposition reactions of the coal macromolecule must proceed in order to initiate the free-radical propagation reactions that are necessary to convert it and the residuum into lower molecular weight fragments and eventually into *n*-pentane-soluble products. The residua that we have examined are much less effective initiators than the coals, and Illinois No. 6 coals is a more effective initiator than Wyodak coal. Our observations also confirm that Illinois No. 6 coal is the most effective hydrogen atom donor among this group of fossil materials (14,33). We believe that this property is detrimental for the conversion of Illinois No. 6 coal because hydrogen donation terminates the essential chain reactions and simultaneously increases the aromatic character of the coal macromolecules. We noted previously that the fossil materials which are most effective hydrogen atom donors are least able to promote the decomposition of 1,3-diphenylpropane and inferred that excessive hydrogen atom donation could adversely affect coprocessing conversion (29). Thus, the observations for the coprocessing of the residua with

Illinois No. 6 coal, which is simultaneously the best initiator and best hydrogen donor, suggest that its donor properties may interfere with its successful coprocessing. Our observations also suggest that blends of coals and residua may offer enhanced degrees of conversion to oil, but more research will be necessary to verify these suggestions.

Dihydrogen addition clearly plays a major role in the liquefaction of coals (34,35). Evidence concerning the utilization of dihydrogen in coprocessing is more limited, but Curtis and Cassell have reported that the addition of hydrogen atom donors to the reaction system decreases the dihydrogen gas consumption (27). Their observations also imply that the hydrogen donor capacity of the collection of the fossil materials in the liquid phase can interfere with the desirable addition of dihydrogen to the initially highly aromatic coal molecules. Indeed, Wyodak coal consumed somewhat more dideuterium from the gas during these low conversion coprocessing experiments than Illinois No. 6 coal. This finding is in accord with the concept that enhancing the hydrogen atom donor capacity of the solvent system can diminish the utilization of the less reactive resids by decreasing the concentrations of resid radicals and, thereby, reducing the opportunities for the adduction of aliphatic resid molecules to coal molecules.

Spectroscopic work

We examined selected spectroscopic properties of the reaction products to gain further perspective on the course of the reaction. Representative infrared and nuclear magnetic resonance spectra are shown in Figures 1 and 2.

FIGURE 1.

Representative infrared spectra of some starting materials and samples from the coprocessing reactions: (1) asphaltene fraction of Lloydminster residuum, (b) oil fraction of Lloydminster residuum, (c) residue from experiment 9, (d) residue from experiment 10, (e) asphaltenes from experiment 9, (f) oil from experiment 9.

FIGURE 2

Representative ^1H NMR spectra of some samples from the coprocessing reactions: (a) asphaltene fraction of Lloydminster residuum, (b) oil fraction Lloydminster residuum, (c) asphaltene fraction from experiment 9, (d) oil fraction from experiment 9, (e) ^2H NMR spectrum of asphaltene fraction from experiment 9, the intense resonance at 7.2 ppm is chloroform-*d*.

The infrared spectra of the asphaltene, resin, and oil fractions of Lloydminster residuum are free of phenolic constituents with no absorptions near 3500 cm^{-1} . This absorption may, therefore, be used to detect the incorporation of coal molecules into the coprocessing products. Indeed, the spectra of the oil, asphaltene, and residue from the coprocessing of Illinois No. 6 coal with Lloydminster residuum in the presence of the catalyst, and dideuterium all exhibit absorptions in this region. The new ^1H NMR spectral absorptions that appear in the products also provide evidence that coal molecules are incorporated into the oil asphaltenes. Results of this kind when coupled with the mass balances provide convincing evidence that substantial amounts of coal are converted to asphaltenes and that the abundant oils also incorporate coal fragments.

In addition, the spectral studies revealed that the hydroxyl content of the residues decreased appreciably as the reaction proceeded. The decrease was greatest for the residues that were obtained from the reactions in the presence of dideuterium and greater for Wyodak coal than for Illinois No. 6 coal. We infer that increased concentrations of hydrogen atom donors, even dihydrogen, assist in the deoxygenation reactions. Although the chemistry of this reaction was not examined, it is pertinent to note that the intensity of the hydroxyl absorption in the infrared spectrum of the asphaltene fraction was rather strong at short reaction times but that the intensity of this absorption in the oil fraction was quite weak at short times. Study of the ^1H NMR spectra, however, established that the fragments were detectable in the oil after only 15 min. As the reaction time increased, the intensity of the hydroxyl absorption increased in the oil. Our results for coprocessing are compatible with the view that phenolic substances are first converted into asphaltenes and subsequently into oils.

Recently, Curtis and Chung investigated the reductive deoxygenation of phenol. They reported that the conversion of phenol into benzene and water is sharply dependent upon the reaction conditions. This aryl fragment was much more readily incorporated into the coal structure than into the residua. The observations for the pure compound suggest that the phenolic structures in coal undergo extensive hydrodeoxygenation under coprocessing conditions and that the organic constituents are fragmented or adducted to other coal molecules rather than to residua. It is also evident that phenolic constituents are incorporated essentially intact into the oil fractions during coprocessing, and Cugini and co-workers showed that the quantity of phenolic molecules in the oil depended upon the quantity of coal available for reaction during coprocessing (5). Our observations for coprocessing under mild conditions are in good accord with the previous work. Increasing the reaction time increased the phenolic content of the oils and water formation. Our observations indicate that Wyodak coal, which has a higher phenol

content than Illinois No. 6 coal, provides oils with more phenolic constituents and more water. Although the hydrodeoxygenation of phenolic compounds may not be the only source of water, this reaction appears to be the major source of water under the mild conditions that we employed. In point of fact, Hayatsu has recently shown that steroidal biomarkers can provide hydrogen atoms for the conversion of phenols into benzene derivatives (34).

Reaction Pathway

The conventionally accepted coal liquefaction mechanism emphasizes the sequential nature of the reactions in which the insoluble intractable solid is converted to smaller, but still large, soluble molecules prior to further fragmentation reactions that yield the oils. Coprocessing appears to be similar to direct liquefaction in this respect, but coprocessing also involves adduction reactions of the aliphatic resid molecules onto the more aromatic coal molecules.

Dideuterium was used to probe the role of dihydrogen in the reaction. Although the influence of the gas on the conversion and oil yields was modest, the spectroscopic data clearly establish that deuterium atoms were incorporated into the products. Weak absorptions near 2100 cm^{-1} were observed in the infrared spectra of most of the products. Our preliminary results suggest that more deuterium is incorporated in the oil than in the other fractions, and the representative ^2H NMR spectra, Figure 2, indicate that the deuterium is incorporated into aliphatic structural elements with resonances between 1 and 2 ppm. Lesser amounts of deuterium appear in benzylic and aromatic positions. We estimate that 0.1-0.2 mmol of dideuterium was incorporated per gram of the reaction mixture. The deuterium incorporation was somewhat higher in the reactions of the Wyodak coal than for the Illinois No. 6 coal. These initial results prompted the study that is discussed in Section III, because it is evident that the gas plays an important role in the chemistry with a very high degree of incorporation in the highly aliphatic constituents of the asphaltenes and the oils as noted in previous work by Skowronski and his associates (35).

CONCLUSION

The experimental results strongly suggest that coprocessing proceeds via a stepwise reactions sequence in which the coal macromolecules are degraded in stages, first forming large polar asphaltenes that are subsequently converted into smaller, less polar oils. Adduction reactions of the aliphatic resid molecules to the aromatic coal molecules proceed at all stages of this chemistry. Indeed, some coal fragments appear in the oil at short reaction times. Hydrogen-transfer processes occur very rapidly among all the constituents, and dideuterium is added to the

reaction products in the presence and absence of the molybdenum catalyst. The reactivity patterns for the four fossil materials suggest that their hydrogen-atom-transfer reactions have a significant influence on the course of the reaction. Our results suggest that the hydrogen donor properties of Illinois No. 6 coal may actually interfere with its conversion.

**SECTION III. DIDEUTERIUM UPTAKE DURING THE COPROCESSING
REACTIONS OF ILLINOIS NO. 6 AND WYODAK COALS WITH LLOYDMINSTER
AND HONDO PETROLEUM RESIDUA UNDER SEVERE CONDITIONS**

PREPARED BY MICHAEL D. ETTINGER AND LEON M. STOCK

INTRODUCTION

Direct coal liquefaction processes have been developed over the past few years towards the production of high quality distillate fuels. Typically these processes employ thermal degradation of the macromolecular coal structure followed by dihydrogen addition to stabilize the reactive fragments and to increase the hydrogen to carbon ratio of the products. Hydrogen atom transfer to produce stable liquid products occurs from the coal molecules, the solvent, and from the dihydrogen atmosphere (36). Conventional coal liquefaction reactions are carried out in expensive hydroaromatic donor solvents or in hydroaromatic rich coal derived solvents. Coprocessing of coal with petroleum residuum is being developed as an alternative route to direct liquefaction. It is generally believed that the petroleum residua in coprocessing serve as a solvent and as a hydrogen donor (37-41).

Coprocessing of petroleum residuum and coal is fast becoming a cost effective means of coal liquefaction. In addition, coprocessing is a unique route for processing coal in existing refinery infrastructures. Among the many other advantages of coprocessing are the simultaneous upgrading of two low quality feedstocks, high yields of liquid products, and the extensive heteroatom removal and demetalation. However, the reaction mechanisms responsible for producing the high quality products are not well understood and are very important to the development and improvement of the technology. Certainly, many types of reactions contribute to the conversion of coal and petroleum residua to distillate fuels such as hydrocracking, hydrogenation, hydrodesulfurization, and hydrodenitrogenation (42,43). The identification and characterization of the reaction types responsible for the conversion of the most resistant molecules to oils are essential to make the necessary improvements needed in coprocessing for successful commercialization.

The exact role of the dihydrogen atmosphere in the coprocessing reaction has not been quantitatively studied. The dihydrogen is an essential as well as an expensive component of the coprocessing reaction. It seemed appropriate to investigate and establish the relationship between dihydrogen uptake during the coprocessing reaction and the actual types of coals and residua used in the coprocessing reaction. Accordingly, we have studied the coprocessing reaction of Illinois No. 6 and Wyodak coals with Lloydminster and Hondo residua in the presence of a pressurized dideuterium atmosphere.

EXPERIMENTAL

Materials

The coals, residua, and the reference catalyst were supplied by John G. Gatsis of the Allied Research Center.

Illinois No. 6 coal was prepared by the Kentucky Center for Energy Research (KCER) and was used as received (Anal. %C, 68.60; %H, 4.51; %N, 1.39; %S, 3.04; %O, 9.65; %H₂O, 3.15; %Ash, 9.65). Wyodak Coal was obtained from the Pennsylvania State University program and was prepared by KCER, and was dried prior to use (Anal. %C, 63.01; %H, 4.50; %N, 0.90; %S, 1.08; %O, 16.73; %H₂O, 1.78; %Ash, 12.00). Lloydminster residuum (Anal. %C, 83.6; %H, 10.3; %S, 4.77; %N, 0.59; %O, 0.54) and Hondo residuum (Anal. %C, 82.17; %H, 9.57; %S, 5.50; %N, 1.37; %O, 0.74) were obtained by UOP Research Center and used as is. The catalyst was a molybdenum based UOP proprietary material. The other chemicals were available commercially and they were purified as necessary.

Procedure

Lloydminster or Hondo petroleum residuum (280 g) and Illinois No. 6 coal (165.4 g) or Wyodak coal (183 g) and the catalyst (0.2%wt Mo) were added to an 1800 ml rocking autoclave. The autoclave was sealed and was pressurized first with hydrogen sulfide and then with dideuterium to give a 10 vol% hydrogen sulfide and 90 vol% dideuterium such that at the reaction temperature of 420°C the desired dideuterium pressure of 3000 psi would be obtained. The autoclave was heated to 420°C in about 120 minutes and then kept at that temperature for a residence time of 2 hours. During the reaction, dideuterium was added automatically so that a reaction pressure of 3000 psi at 420°C was maintained. After the desired time-at-temperature, the autoclave was cooled to room temperature, and was then depressurized with the gas passing through a foam trap, caustic scrubbers, metering system, and then a sample was collected for analysis. To remove additional gas from the remaining reaction mixture, the material in the autoclave was purged with dinitrogen. This gas also was passed through the foam trap, caustic scrubber, metering system, and analyzed. Any slurry product recovered in the foam trap was recovered with toluene and added to the toluene rinse solution. The slurry product from the autoclave was decanted. The material that remained in the autoclave was removed by rinsing the vessel with toluene until the autoclave was clean. The combined slurry product was solvent separated via sonication followed by centrifugation into four fractions as shown in Figures 3: oil (pentane soluble), resin (heptane soluble/pentane insoluble), asphaltene (toluene soluble/heptane insoluble), and toluene insolubles. Solvent removal was carried out with a flash rotary

evaporator. Unfortunately, this procedure resulted in the loss of light materials from the oil fraction. All solvent separated fraction yields and conversions are adjusted for 100% ash balance.

Analysis

Deuterium spectra were obtained on a Varian XL 400 MHz spectrometer. Two hundred fifty six scans were acquired using a 90° pulse and a thirty second delay between pulses. Triphenylmethane-d₁ was used as a quantitative internal standard. Proton spectra were obtained similarly on the University of Chicago 500 MHz spectrometer and tetrakis(trimethylsilyl)silane was used as a quantitative internal standard. Elemental analysis were carried out at UOP using a Leco elemental analyzer. Gas analysis were carried out at the Institute of Gas Technology and analyzed for, among other things, deuterated methanes, ethanes, propanes, butanes, butenes, benzenes, and toluenes.

FIGURE 3

SOLVENT SEPARATION OF AUTOCLAVE PRODUCT

RESULTS AND DISCUSSION

The autoclave reactions using a combination of Illinois No. 6 or Wyodak coal with either Lloydminster or Hondo petroleum residua mixed with a molybdenum based UOP proprietary catalyst were carried out at 420°C for two hours under a deuterium atmosphere at a constant pressure of 3000 psi. The results of the solvent separation of the products are summarized in Table 12. The oil, resin, asphaltene, and insoluble yields are based upon the starting amount of MAF coal and resid. As can be seen from Table 12, approximately 23% of the starting material is unaccounted for. This portion represents the gas yield and the loss of a small amount of light material in the work-up procedure.

TABLE 12.
Solvent separated fraction yields and conversions of coprocessed products

Fraction Yields and Conversions (Wt% MAF)	Lloydminster and IL No. 6	Hondo and IL No. 6	Lloydminster and Wyodak	Hondo and Wyodak
Oil	62.32	56.07	61.21	56.62
Resin	3.91	4.00	5.13	4.92
Asphaltene	8.50	11.87	5.23	4.94
Insoluble	2.40	2.60	1.30	1.30
Coal Conversion	92.78	92.29	96.08	96.20
Asphaltene Conversion	74.08	66.58	84.56	85.60

Coal conversion was calculated as the amount of starting MAF coal minus unconverted MAF coal (insolubles) divided by the starting amount of MAF coal. Maximal levels of coal conversions over 90% were achieved in all four reactions. The conversion of the insoluble organic material in coal into molecules that are soluble in toluene is important. However, the toluene soluble asphaltene molecules are still very large and relatively useless as a direct fuel product. It is the conversion of these large molecules into smaller, hydrogen rich oil molecules that are soluble in pentane that is essential to the success of the coprocessing reaction. Therefore, we use a value similar in form to coal conversion that measures the conversion of the large asphaltenes into smaller products. This value, termed asphaltene conversion, was calculated based upon the amount of asphaltene fraction and unconverted coal (insolubles) in the autoclave

product compared to the amount of starting MAF coal and asphaltene fraction of the starting residuum. The highest asphaltene conversions of about 85% were realized when Wyodak coal was used with either Lloydminster or Hondo residua. This result is not surprising because Wyodak coal is a subbituminous coal compared to Illinois No. 6 coal which is a bituminous coal. The conversion of asphaltenes to pentane soluble products was more difficult to achieve using Illinois No. 6 coal. The combinations of Illinois No. 6 coal with Lloydminster and Hondo residua achieved lower asphaltene conversions of 74.08 and 66.58%, respectively.

The elemental analysis of the oil, resin, asphaltene, and insoluble fractions of the coprocessing products are shown in Table 13. The H/C ratios of the oil fractions rise slightly from about 0.13 in the residua to a value averaging 0.16 in the coprocessed products indicative of the production of hydrogen rich pentane soluble molecules. The H/C ratios increased despite the fact that extensive solubilization of small aromatic molecules took place which has a negative effect on the H/C ratio. Conversely, the H/C ratios in the resin and asphaltene fraction generally decreased supporting the idea that as these fractions were becoming aromatized. In all of the product fractions, the sulfur content significantly decreased even though hydrogen sulfide gas was present. The nitrogen content also decreased.

TABLE 13.
Elemental analysis of the solvent separated starting residua and coprocessing products

	Starting Lloydminster	Starting Hondo	Lloydminster and IL No. 6	Hondo and IL No. 6	Lloydminster and Wyodak	Hondo and Wyodak
<u>Oil Fractions</u>						
% Carbon	82.86	81.00	84.88	84.44	85.60	82.84
% Hydrogen	10.82	10.83	13.67	13.10	13.72	14.06
% Sulfur	4.30	5.34	1.21	1.21	1.40	1.16
% Nitrogen	1.30	0.88	0.42	0.61	0.33	0.59
<u>Resin Fractions</u>						
% Carbon	82.68	81.78	86.16	85.41	84.48	83.33
% Hydrogen	8.76	9.21	8.66	8.60	8.46	9.39
% Sulfur	7.44	7.13	1.73	1.39	2.21	1.77
% Nitrogen	1.32	1.87	2.19	1.85	1.58	1.95
<u>Asphaltene Fractions</u>						
% Carbon	82.82	81.66	87.70	85.44	83.46	85.66
% Hydrogen	8.51	8.95	7.09	8.00	7.33	7.58
% Sulfur	7.85	7.83	1.68	1.48	2.52	2.35
% Nitrogen	1.52	2.45	1.65	2.08	1.11	1.80

The deuterium incorporation into the different molecular fragments defines the paths of hydrogen transfer. In this first analysis of the results, the assignments are made according to the following chemical shift ranges. Deuterium resonances in the range of 6.3-10 ppm are assigned to aromatic deuterium atoms, while those found in the range of 4.2-0 ppm are assigned to aliphatic types. A further breakdown of the resonances in the ranges 4.2-2.0 ppm, 2.0-1.0 ppm, and 1.0-0 ppm was made by assigning resonances in those ranges to deuterium atoms alpha to aromatic rings, deuterium atoms beta to aromatic rings and in methylene and methine positions not alpha to aromatic rings, and deuterium atoms in methyl groups gamma or further from aromatic rings, respectively. Proton NMR characterization was also carried out to complement the results for deuterium. The proton NMR experiments use tetrakis(trimethylsilyl)silane as an internal standard. The NMR data from the coprocessing reaction products of Illinois No. 6 coal with Lloydminster residuum are shown in Tables 14 and 15. In addition to the actual amount of deuterium incorporated into the products, Table 14 also shows the hydrogen content in each of the products. Thus, the percent deuteration of the aromatic and aliphatic regions was determined.

Large amounts of deuterium were incorporated into the aliphatic components of the oil fractions from the different reactions. Values ranged from 24.1 mmol g⁻¹ for the reaction with Illinois No. 6 coal and Lloydminster residuum to 28.6 mmol g⁻¹ for the reaction with Wyodak coal and Hondo residuum. While the absolute amounts of deuterium uptake at the different structural positions vary from values of 2.8 mmol g⁻¹ in aromatic positions to values of 28.6 mmol g⁻¹ in aliphatic positions, the relative percentages of deuteration at the aromatic and aliphatic positions in the different fractions vary considerably less. The levels of percent deuteration average around 25%. These percentages are close to the initial deuterium to hydrogen ratio of the starting materials charged to the autoclave. Performing the calculation based upon the initial charge of dideuterium and the amount metered in during the reaction and the hydrogen content of the coal and residuum yields a value of $H / (H+D) = 0.25$. Therefore, the levels of deuteration in the coprocessed products which average 25% indicate that deuterium-hydrogen exchange occurred rapidly and that, in terms of exchange, equilibration of the system was approached. Certainly, some selectivity of the catalyst was observed. Comparing levels of deuteration between the solvent separated fractions shows that the extent of deuteration decreased in the order of resin > asphaltene > oil except for the reaction of Illinois No. 6 coal with Lloydminster residuum in which the % deuteration in the asphaltenes was higher than in the resins. Almost in all cases, aliphatic positions had higher levels of exchange.

TABLE 14.
Hydrogen content, deuterium content, and % deuteration of coprocessed products

	Hydrogen (mmol g-1)		Deuterium (mmol g-1)		Deuteration (%)	
	Aromatic (6.3-10 ppm)	Aliphatic (4.2-5 ppm)	Aromatic (6.3-10 ppm)	Aliphatic (4.2-0 ppm)	Aromatic (6.3-10 ppm)	Aliphatic (4.2-0 ppm)
<u>Lloyd + Il #6</u>						
Oil	14.7	90.8	2.9	24.1	16.5	21.0
Resin	18.0	46.6	5.3	14.6	22.7	23.9
Asphaltene	13.6	29.9	5.0	11.9	26.9	28.5
<u>Hondo + Il #6</u>						
Oil	7.7	77.7	2.8	24.9	26.7	24.3
Resin	13.1	35.9	5.9	15.5	31.1	30.2
Asphaltene	12.5	28.4	4.6	12.1	26.9	29.9
<u>Lloyd + Wyodak</u>						
Oil	10.5	85.1	3.1	27.0	22.8	24.1
Resin	14.2	40.8	5.2	15.4	26.8	27.4
Asphaltene	14.7	30.5	3.4	10.5	18.8	25.6
<u>Hondo + Wyodak</u>						
Oil	12.2	96.8	2.8	28.6	18.7	22.8
Resin	14.1	41.9	5.3	16.3	27.3	28.0
Asphaltene	15.4	30.6	3.5	11.3	18.5	27.0

TABLE 15.
Aliphatic deuterium content in solvent separated coprocessing products

Solvent Separated Fraction	Aliphatic-D 4.2-0.0 ppm (mmol g-1)	Alpha-D 4.2-2.0 ppm (mmol g-1)	Beta-D 2.0-1.0 ppm (mmol g-1)	Gamma-D 1.0-0.0 ppm (mmol g-1)
<u>Lloyd + Il #6</u>				
Oil	24.1	6.2	15.6	2.3
Resin	14.6	7.5	6.0	1.1
Asphaltene	11.9	5.9	4.8	1.2
<u>Hondo + Il #6</u>				
Oil	24.9	6.3	16.1	2.5
Resin	15.5	7.7	6.1	1.7
Asphaltene	12.1	5.5	4.7	1.9
<u>Lloyd + Wyodak</u>				
Oil	27.0	7.0	17.0	3.0
Resin	15.4	7.4	6.7	1.3
Asphaltene	10.5	4.8	4.4	1.3
<u>Hondo + Wyodak</u>				
Oil	28.6	7.0	18.5	3.1
Resin	16.3	7.8	7.2	1.3
Asphaltene	11.3	5.3	4.5	1.5

Analysis was also carried out on the gaseous products from each of the coprocessing reactions. As mentioned in the experimental section, the distribution of deuterated products was determined for methanes, ethanes, propanes, butanes, butenes, benzenes, and toluenes. Very interesting trends were observed in the levels of deuteration of these molecules. The actual quantities of deuterated butenes, benzenes, and toluenes collected for gas analysis were very small and the analytical results often had experimental errors close to 100%. Therefore, when considering the distribution of deuterated products, we will concentrate on the methanes, ethanes, propanes, and butanes. The data for these molecules are shown in Table 16 and in Figures 4-7.

As shown in Table 16, the mole percent levels of the mono- and dideuteriomethanes were very significant at levels averaging 33% and 27%, respectively. The favored product was monodeuteriomethane over even the nondeuterated species. The trideuteriomethane product was also observed at mole percent levels ranging from 10.3 to 16.6%. The weighted average level of deuteration of the methane products ranged from 32.0 to 35.7%. The ethane products exhibited a

quite different distribution. The favored product was the nondeuterated species with mole percent levels of 43.9 to 57.3%. Nondeuterated ethane was favored twofold or more over monodeuterioethane which was the next highest produced product. All the different deuterioethanes were observed, however, the weighted average level of deuteration ranged from only 13.5 to 18.8% which is much lower than the values for the methanes. The propanes and butanes have weighted average levels of deuteration averaging around 25 and 27%. These values are more in line with the levels of deuteration found in the oil, resin, and asphaltene fractions of the coprocessed products. The monodeuteriopropene is the favored product among the propanes. However, relatively large amounts of the di, tri, and tetradeuteriopropene are formed. The pentadeuteriopropene is also formed in significant levels of up to 7.4%. The butane products show a nice distribution of deuterated species with the mono- through the tetradeuteriobutanes as the favored products. Deuteration up to nonadeuteriobutane was observed with significant levels of the hexa- and heptadeuteriobutanes produced. The weighted average levels of deuteration in the different gas molecules are very interesting. It is a sensible conclusion that the levels of deuteration of the different gas molecules are directly related to the deuterium content of their source at the time of production. The deuterium content of the gas products might then indicate relative rates of production. Methane production would then seem to occur relatively slow. The lower levels of deuterium in the ethanes compared to the propanes and butanes may be due to the relative exchange reactivity of primary vs. secondary positions.

TABLE 16.
Distribution of deuterated gaseous products

	Lloydminster and IL No. 6	Hondo and IL No. 6	Lloydminster and Wyodak	Hondo and Wyodak
<u>Methanes</u>				
Total Product (mmol)	349.1	404.5	436.1	358.1
<u>Deuterated Products (mole%)</u>				
CD ₄	1.9	1.6	3.1	2.5
CH ₁ D ₃	10.9	10.3	16.6	12.6
CH ₂ D ₂	27.8	27.8	24.7	28.5
CH ₃ D ₁	34.4	34.9	30.8	32.3
CH ₄	25.1	25.4	24.7	24.1
Wt. Ave. %D	32.5	32.0	35.7	34.3
<u>Ethanes</u>				
Total Product (mmol)	126.9	180.6	211.1	132.5
<u>Deuterated Products (mole%)</u>				
C ₂ D ₆	0.1	0.1	0.1	0.2
C ₂ H ₁ D ₅	0.8	0.8	1.3	1.2
C ₂ H ₂ D ₄	2.9	3.4	4.4	4.6
C ₂ H ₃ D ₃	7.1	14.3	9.8	10.2
C ₂ H ₄ D ₂	12.3	14.6	14.5	15.4
C ₂ H ₅ D ₁	19.6	23.0	24.7	23.1
C ₂ H ₆	57.3	43.9	45.1	45.3
Wt. Ave. %D	13.5	18.8	18.0	18.4
<u>Propanes</u>				
Total Product (mmol)	126.9	180.6	211.1	132.5
<u>Deuterated Products (mole%)</u>				
C ₃ D ₈	0.0	0.0	0.0	0.1
C ₃ H ₁ D ₇	0.4	0.2	0.4	0.8
C ₃ H ₂ D ₆	1.8	1.0	1.3	3.0
C ₃ H ₃ D ₅	4.2	3.3	3.5	5.7
C ₃ H ₄ D ₄	6.8	9.3	9.4	14.3
C ₃ H ₅ D ₃	16.6	16.9	16.2	17.0
C ₃ H ₆ D ₂	20.5	21.4	20.1	16.7
C ₃ H ₇ D ₁	38.7	38.2	38.2	34.3
C ₃ H ₈	11.1	9.7	10.9	8.1
Wt. Ave. %D	23.9	24.1	24.1	28.6

TABLE 16 (continued)

Butanes

Total Product (mmol)	26.6	54.5	65.0	35.1
<u>Deuterated Products (mole%)</u>				
C ₄ D ₁₀	0.0	0.0	0.0	0.0
C ₄ H ₁ D ₉	0.1	0.1	0.1	0.1
C ₄ H ₂ D ₈	0.4	0.4	0.8	0.7
C ₄ H ₃ D ₇	1.4	1.4	2.9	2.4
C ₄ H ₄ D ₆	3.4	3.6	5.5	5.4
C ₄ H ₅ D ₅	8.6	8.9	9.6	10.3
C ₄ H ₆ D ₄	14.0	14.5	13.8	14.7
C ₄ H ₇ D ₃	19.6	19.3	17.7	18.1
C ₄ H ₈ D ₂	22.7	21.7	20.1	19.0
C ₄ H ₉ D ₁	19.4	18.2	18.7	15.5
C ₄ H ₁₀	10.3	11.9	10.8	13.8
Wt. Ave. %D	25.7	25.7	27.6	27.4

Figure 4

FIGURE 5

Ethane-D Distribution (%)

FIGURE 6

Propane-D Distribution (%)

FIGURE 7

Butane-D Distribution (%)

CONCLUSION

Analysis of the reactions of either Illinois No. 6 or Wyodak coal with Lloydminster or Hondo petroleum residua carried out at 420°C under 3000 psi of dideuterium has revealed in some detail how dihydrogen is essential to and utilized in the coprocessing reaction. The determination of deuterium uptake shows that, in terms of percent deuteration at the aromatic and aliphatic positions in the coal and residua molecules, the results are quite similar among the different combinations of coal and residua. However, some selectivity was observed among the solvent separated products. In three out of four reactions, percent deuteration generally decreased in the order of resin > asphaltene > oil. Clearly, the larger, more aromatic and polar constituents in the coal-residuum feedstock are more reactive in terms of deuterium uptake and exchange. This may reflect directly on the selectivity of the molybdenum based catalyst used in this study.

We have seen that the different combinations of coal and residua have yielded similar results. In each of the reactions, the level of deuterium content in the products averaged around 25% with some selectivity as mention above. However, the results differ slightly when looking at levels of coal and asphaltene conversion. The coal conversions differed based only upon the coal. Whether Lloydminster or Hondo residuum was used, the coal conversions were essentially the same for Wyodak coal at 96% and for Illinois No. 6 coal at 92%. Asphaltene conversion was the same at 85% for both reactions with Wyodak coal. The values differed for the reactions with Illinois No. 6 coal with asphaltene conversions at 74% for Lloydminster and 66% for Hondo residua. Pentane soluble oil yields were essentially the same at 62% for the reactions with Lloydminster residuum and at 56% for the reactions with Hondo residuum.

The evaluation of the results must also take into account that the levels of deuteration in the coprocessed products averaged approximately 25%. The $D/(H + D)$ ratio of the starting materials was approximately 0.25. Therefore, the levels of deuteration of the coprocessed products are only moderately different than the values expected for complete equilibration of the system. All components of the system appear to be undergoing extensive hydrogen transfer and exchange chemistry. The levels of deuteration of the gaseous methane, ethane, propane, and butane products which average 34, 17, 25 and 27% appear especially interesting. If it is assumed that the gaseous products once produced do not react with the catalyst, then the level of deuteration may serve as an indicator of the relative time scale of production of these gaseous hydrocarbons. However, other pathways may be responsible for these trends and warrants further investigation before any conclusions can be made.

The reaction conditions used in this study have evidently allowed for equilibration of the deuterium throughout the coprocessing system. Therefore, to gain further insight into the role of dihydrogen, a series of coprocessing reactions must be carried out under a variety of less severe conditions. More detailed analysis will then map out the pathways of dideuterium utilization as a function of reaction pressure, temperature, and residence time.

**SECTION IV. DIDEUTERIUM UPTAKE AND UTILIZATION DURING THE
COPROCESSING REACTION OF ILLINOIS NO. 6 AND LLOYDMINSTER
PETROLEUM RESIDUUM UNDER MODERATE CONDITIONS OF VARIED
PRESSURE, TEMPERATURE, AND RESIDENCE TIME**

PREPARED BY MICHAEL D. ETTINGER AND LEON M. STOCK

INTRODUCTION

Direct coal liquefaction processes have been developed over the past few years towards the production of high quality distillate fuels. Typically these processes employ thermal degradation of the macromolecular coal structure followed by dihydrogen addition to stabilize the reactive fragments and to increase the hydrogen to carbon ratio of the products. Hydrogen atom transfer to produce stable liquid products occurs from the coal molecules, the solvent, and from the dihydrogen atmosphere (36). Conventional coal liquefaction reactions are carried out in expensive hydroaromatic donor solvents or in hydroaromatic rich coal derived solvents. Coprocessing of coal with petroleum residuum is being developed as an alternative route to direct liquefaction. It is generally believed that the petroleum residua in coprocessing serve as solvent and as a hydrogen donor (37-41).

Coprocessing of petroleum residuum and coal is fast becoming a cost effective means of coal liquefaction. In addition, coprocessing is a unique route for processing coal in existing refinery infrastructures. Among the many other advantages of coprocessing are the simultaneous upgrading of two low quality feedstocks, high yields of liquid products, and the extensive heteroatom removal and demetalation. However, the reaction mechanisms responsible for producing the high quality products are not well understood and are very important to the development and improvement of the technology. Certainly, many types of reactions contribute to the conversion of coal and petroleum residua to distillate fuels such as hydrocracking, hydrogenation, hydrodesulfurization, and hydro-denitrogenation (42,43). The identification and characterization of the reaction types responsible for the conversion of the most resistant molecules to oils are essential to make the necessary improvements needed in coprocessing for successful commercialization.

The previous sections discussed the uptake and utilization of dideuterium in coprocessing reactions carried out under severe conditions. Levels of deuteration approached values consistent with hydrogen and deuterium equilibration. Little selectivity was observed as a result. Therefore, it seemed appropriate to investigate and establish the relationship between dihydrogen uptake during the coprocessing reaction as a function of reaction severity and as a function of certain characteristics of the reactions such as coal conversion, the yields of liquid products, and the level of heteroatom removal. Accordingly, we have studied the coprocessing reaction of Illinois No. 6 coal and Lloydminster residuum carried out under a dideuterium atmosphere and under various reaction conditions.

EXPERIMENTAL

Materials

Illinois No. 6 coal was prepared by the Kentucky Center for Energy Research (KCER) and used as received (Anal. %C, 66.75; %H, 4.66; %N, 1.34; %S, 2.91; %O, 8.98; %Ash, 11.28; %H₂O, 4.08). Lloydminster Resid (Anal. %C, 83.6; %H, 10.3; %S, 4.77; %N, 0.59; %O, 0.54; %Ash, 0.04) was obtained by UOP Research Center and used as received. The catalyst used was a molybdenum based UOP catalyst.

Procedure

Lloydminster petroleum residuum (280 g) and Illinois No. 6 coal (165.4 g) and the catalyst (0.2%wt Mo) were added to an 1800 ml rocking autoclave. The autoclave was sealed and was pressurized first with hydrogen sulfide and then with dideuterium to give a 10 vol% hydrogen sulfide and 90 vol% dideuterium such that at reaction temperature the desired dideuterium pressure would be obtained. The autoclave was heated to the desired temperature in about 120 minutes and then kept at that temperature for a residence time of 0.0, 0.5, or 2 hours. During the reaction, dideuterium was added automatically so that the desired reaction pressure (1770 or 3000 psi at temperature) was maintained. After the desired time-at-temperature, the autoclave was cooled to room temperature, and was then depressurized with the gas passing through a foam trap, caustic scrubbers, metering system, and then a sample was collected for analysis. To remove additional gas from the remaining reaction mixture, the material in the autoclave was purged with dinitrogen. This gas also was passed through the foam trap, caustic scrubber, metering system, and analyzed. Any slurry product recovered in the foam trap was recovered with toluene and added to the toluene rinse solution. The slurry product from the autoclave was decanted. The material that remains in the autoclave was removed by rinsing the vessel with toluene until the autoclave was clean. The combined slurry product was solvent separated via sonication followed by centrifugation into four fractions: oil (pentane soluble), resin (heptane soluble/pentane insoluble), asphaltene (toluene soluble/heptane insoluble), and toluene insolubles. Solvent removal was carried out with a flash rotary evaporator. Unfortunately, this procedure results in the loss of light materials from the oil fraction. The values of the lost light materials was added to the values for the oil fraction yields. All solvent separated fraction yields and conversions are adjusted for 100% ash balance.

Analysis

Deuterium spectra were obtained on a Varian XL 400 MHz spectrometer. Twenty-five hundred scans were acquired by using a 90° pulse and a 5 second delay between pulses. Benzaldehyde- α -d was used as a quantitative internal standard. Proton spectra were obtained similarly on the

same instrument with 256 scans by using a 90° pulse and a 20 second delay between pulses. Elemental analyses for carbon and hydrogen for each solvent separated product were obtained from Huffman Laboratories using an instrument that detected and accurately measured both hydrogen and deuterium on an atomic basis.

Quantitative Determinations

Deuterium and hydrogen concentrations were determined for a selected series of NMR chemical shift ranges as shown in Table 17. Large aromatic and aliphatic chemical shift ranges were used due to the inherent broadness of deuterium resonances fossil fuel products. Deuterium NMR spectra were taken with and without weighed amounts of an internal standard, benzaldehyde- α -d. The benzaldehyde- α -d deuterium resonance occurs at 9.6 ppm and overlaps with the aromatic region. Either one or two spectra were taken of each sample without the standard, and two spectra were taken with the internal standard. Integration was carried out by using a combination of an automatic phasing program and manual phasing. The results were very consistent yielding values within 5 % for different samples. Hydrogen NMR were taken similarly. However, the

TABLE 17
Chemical shift ranges of hydrogen and deuterium resonances

Aromatic Hydrogen Atoms	12.0 - 6.0 ppm
Aliphatic Hydrogen Atoms	5.0 - (-2.0) ppm
Hydrogen Atoms Alpha to Aromatic Rings	5.0 - 2.0 ppm
Hydrogen Atoms Beta to Aromatic Rings	2.0 - 1.0 ppm
Hydrogen Atoms Gamma to Aromatic Rings	1.0 - (-2.0) ppm

phasing and integration processes were not as consistent when analyzing for hydrogen. Consequently, NMR was combined with elemental analysis to determine the hydrogen contents. Elemental analysis for carbon and hydrogen were obtained with an instrument that measured both hydrogen and deuterium equally on an atomic basis. Thus, the %wt values for deuterium were one-half of the true value. For example, calculated D %wt values for hexadecane-d₃₄ and phenanthrene-d₁₀ are 26.3 and 10.7%, respectively. Elemental analysis yields values of 13.2 and 5.5%. The hydrogen content for the coprocessed samples was defined by using the elemental analysis and hydrogen NMR values. This approach was evaluated with several samples by careful quantitative hydrogen NMR analysis and was found to give H + D values within 4%.

RESULTS AND DISCUSSION

Coprocessing

Illinois No. 6 coal was coprocessed with Lloydminster residuum in the presence of dideuterium and a molybdenum catalyst in six batch autoclave screening experiments. These fossil materials were selected for study because information about their behavior in previous autoclave screening tests was already available (44-46). We chose to examine the coprocessing reaction of these materials under an atmosphere of dideuterium and under different reaction conditions so that the influences of pressure, temperature, and residence time on the utilization of dideuterium from the atmosphere could be investigated by using quantitative deuterium NMR techniques. The reactions were carried out under conditions as shown in Table 18. In addition, we sought to establish a relationship between dideuterium utilization in, and the yields of, the solvent separated fractions. We were also interested in the utilization of dideuterium as a function of the coal and asphaltene conversions.

As shown in Table 18, reactions 1 and 2 examined the effect of different dideuterium pressures of 1770 and 3000 psi with a final temperature of 390°C and residence time of 0 h. Reactions 2, 3, and 4 addressed the effect of different final temperatures of 390, 405, and 420°C with dideuterium pressure and residence time held constant at 3000 psi and 0 h. Reactions 4, 5, and 6 examined the effect of residence time as it was increased from 0.0 to 2.0 h with temperature and dideuterium pressure held at 420°C under 3000 psi. Throughout the series of reactions, the autoclave required two hours to reach the reaction temperature and was then held at this temperature for a residence time of either 0.0, 0.5, or 2.0 h.

TABLE 18.
Coprocessing reaction conditions

Entry	Temperature (°C)	Dideuterium Pressure (psi)	Residence Time (hr)
1	390	1770	0.0
2	390	3000	0.0
3	405	3000	0.0
4	420	3000	0.0
5	420	3000	0.5
6	420	3000	2.0

Conversions and product yields. The reaction products were solvent separated as described in the Experimental Section and the yields of oil, resin, asphaltene, and insoluble fractions were determined. The gaseous product yields were also determined. The calculation of the product yields was based upon the starting MAF analysis of the starting materials. The conversion of coal to toluene soluble products and the asphaltene conversion were calculated according to the following equations. These results are summarized in Table 19.

$$CC = 1 - \left[\frac{\text{Insolubles fraction}}{\text{Starting MAF coal}} \right]$$

$$AC = 1 - \left[\frac{(\text{Asphaltene} + \text{Insolubles})}{(\text{Starting MAF coal} + \text{Residuum Asphaltene})} \right]$$

Coal conversion is often the principal parameter that is used to evaluate the success of coal processing reactions as it measures the extent to which the coal macromolecular structure has been fragmented to form soluble and distillable, although still very large, molecules. However, the yields of the more desirable oil molecules from coal liquefaction reactions may be extremely low even with very high coal conversions. Information about the extent of oil production may be obtained from the asphaltene conversion as defined in the equation above.

TABLE 19.
Coproprocessing reaction yields and conversions (wt. %)

Reaction Conditions	Solvent Separated Fraction Yields					Conversions	
	Gas	Oil	Resin	Asph	Insol	Coal	Asph
0.0 hr at 390°C, 1770 psi D ₂	2.7	57.6	3.8	17.1	18.9	43.3	15.1
0.0 hr at 390°C, 3000 psi D ₂	1.6	58.1	3.3	17.7	19.3	42.6	13.0
0.0 hr at 405°C, 3000 psi D ₂	4.5	64.9	1.1	21.2	8.3	75.0	29.6
0.0 hr at 420°C, 3000 psi D ₂	5.6	65.4	3.6	22.8	2.7	92.1	40.1
0.5 hr at 420°C, 3000 psi D ₂	7.9	68.5	1.7	19.3	2.7	91.9	47.3
2.0 hr at 420°C, 3000 psi D ₂	7.6	77.7	3.9	8.5	2.4	92.8	74.2

Asphaltene conversion is a measure of the production of the more desirable oil molecules, and to a lesser extent, resin and gaseous molecules from the conversion of the starting MAF coal and the residuum asphaltene molecules. While the conversion of insoluble coal molecules to toluene soluble products is valuable, one goal of coprocessing is to produce a product that can be used directly as a transportation fuel or as a high grade feedstock for further refining. Therefore, the conversion of asphaltene molecules to oil molecules is the principal parameter upon which the success of coprocessing should be based.

The influence of reaction conditions on coal and asphaltene conversions is shown in Figure 8. The coal conversion remains constant at about 43% as the dihydrogen pressure at 390°C is increased from 1770 to 3000 psi. This result is not surprising in that it is generally agreed that temperature is the dominant driving force behind coal conversion in most coal liquefaction processes. As the temperature is increased from 390 to 405°C, and then to 420°C, coal conversion rises quickly to 75% and then to 92%. Maximum coal conversion of 92% is achieved early in the series after only 0.0 h at 420°C, and it remains constant at its maximum value as residence time at 420°C is increased to 2.0 h. This observation that coal conversion in this coprocessing is essentially a thermally dependent process is consistent with the idea that the first stage of coal conversion reactions is the thermal cleavage of the structural elements that cross-link the coal macromolecule to produce smaller, although still quite large, molecules. Essential to the achievement of high coal conversion is the stabilization of the initially formed reactive fragments through hydrogen atom transfer from either the coal, the residuum, or the dihydrogen atmosphere. The achievement of a coal conversion of 92% at such low severity in the series of reactions indicates that this catalytic coprocessing system is extremely effective in providing hydrogen atoms to produce stable molecules from the thermally cleaved reactive fragments.

FIGURE 8

Coal and Asphaltene Conversions (wt.%MAF)

The influence of reaction conditions on asphaltene conversion is also shown in Figure 8. It is apparent that the reactions responsible for the production of oil molecules occur at relatively slow rates. Comparison of reactions 1 and 2 show that an increase in dideuterium pressure from 1770 to 3000 psi when residence time at 390°C is 0 h has essentially no effect on asphaltene conversion which remains around 14%. As temperature increases from 390 to 405°C, and then to 420°C, asphaltene conversion rises slowly to 40%. It is only as residence time increases at 420°C that a significant level of asphaltene conversion to 74% is realized at the unfortunate expense of increased deuterium consumption, and increased production of gaseous and light-end molecules. Residence time seems to be the most important variable to the successful conversion of asphaltenes in this series of reactions.

The yields of the gas, oil, resin, asphaltene, and insoluble products are presented as a function of the reaction conditions in Figure 9. The relationship of the product yields to the reaction conditions and to the coal and asphaltene conversions are apparent. Concurrent with the achievement of maximum coal conversion, the yields of the asphaltene and insoluble fractions reach their maximum and minimum values, respectively, of 23% and 2.7% after 0.0 h at 420°C under 3000 psi of dideuterium. At the same time, production of oil molecules occurs as the oil yield increases from 57.6 to 65.4 % mirroring the moderate increase in asphaltene conversion. As residence time at 420°C increases to 2 h, coal conversion and the yield of the insoluble fraction remain constant at their maximum and minimum levels, respectively. At the same time, the asphaltene conversion increases from 40 to 75% as the oil yield increases to its maximal value of 77.8% at the expense of the asphaltene yield which falls from its maximum level of 23.0% to its minimum level of 8.5%. The resin fraction yield remains between 1 and 4 % throughout the series and has little impact on the other values.

FIGURE 9

Product Yields (wt. %)

△ Gas □ Oil ◆ Resin ◇ Asph. ★ Insol.

Unfortunately, asphaltene conversion occurs at the considerable expense of increased dideuterium consumption and increased production of very volatile and gaseous products. The quantity of dideuterium consumed is calculated from the initial and final values along with the amount metered in during the reaction to keep the pressure at 3000 psi. This value is expressed as a wt.% based on the starting coal and residuum feedstock and ranged from 0.4 to 1.1 wt.% for the first five reactions. However, as residence time at 420°C increased from 0.5 to 2.0 hrs, the deuterium consumption increased fourfold to 4.1 wt.% coincident with the largest increase in asphaltene conversion. These values are very significant especially when compared to the wt.% hydrogen in the initial coal and residuum feedstock which was 8.7%. Figure 10 shows a summary picture of the gaseous and solvent separated products that account for 100% of the starting feedstock. Also included are the values for the deuterium consumption with these values above the 100% level as these values account for a net addition to the products. The coal and asphaltene conversions are also presented. Note that the values for the oil yields consist of the actual recovered oil and the value added for the quantity of the material lost during the rotary evaporation of the solvent. This material mainly consists of C₅, C₆, C₇, and C₈ compounds. The production of materials (lost during the work-up procedure) increases from 4.0 to 15.3%, and the yields of gaseous products increase from about 2 to 8 % through the series of reaction. The production of the undesirable volatile liquids and gaseous products is clearly dependent on temperature and residence time, the majority of the volatile compounds are formed concurrently with the conversion of asphaltenes.

FIGURE 10

Deuterium Determination

The hydrogen and deuterium content of each solvent separated product of each coprocessing reaction was quantitatively determined. The deuterium content was partitioned into aromatic and aliphatic positions based upon chemical shifts of the NMR resonances. The aliphatic positions were further divided into alpha, beta, and gamma aliphatic positions. These NMR results are in Table 20. Sample spectra are shown in Figure 11.

The total aromatic, aliphatic, alpha, beta, and gamma deuterium content in the oil, resin, and asphaltene fractions as a function of reaction conditions are illustrated in Figures 12-17. The deuterium content is consistently highest in the asphaltene molecules, less in the resin, and least in the oil throughout the series and the different positions and regions. The only exception is for the asphaltene molecules under the most severe reaction conditions, and this feature will be discussed. This clearly indicates that, in the first five reactions, the asphaltenes are more reactive towards dideuterium incorporation and utilization than the resin or the oil. This is reflective of the nature of the asphaltene molecules in that they contain significant amounts of aromatic and hydroaromatic structures. Such molecules under coprocessing conditions are quite reactive towards exchange and reduction. As these molecules undergo such reactions, they are converted to less reactive oil molecules.

However, the asphaltene molecules show different behavior as reaction time at 420°C is increased from 0.0 to 2.0 hours. Asphaltene conversion is taking place and, hence, the asphaltene fraction yield decreases from its maximum value of 22.8% to its minimum value of 8.5%. At the same time, the remaining unconverted asphaltene molecules exhibit a decrease in or leveling off of the D-content as the residence time at 420°C approaches 2.0 hours. Two factors are most likely contributing to this behavior. First, the remaining asphaltene molecules are becoming relatively refractory in nature as they become more aromatic via the removal of paraffinic structural elements and possibly retrogressive condensation reactions, although production of insoluble material is not observed. Second, the level of deuterium incorporation in the asphaltene molecules is approaching 27%. This is important because the starting feedstock

TABLE 20.
deuterium content in coprocessed products

<u>Reaction Conditions (Temperature, D2 Pressure, and Residence Time)</u>						
<u>Solvent Separated Fraction</u>	<u>390°C 1770 psi 0.0 hr</u>	<u>390°C 3000 psi 0.0 hr</u>	<u>405°C 3000 psi 0.0 hr</u>	<u>420°C 3000 psi 0.0 hr</u>	<u>420°C 3000 psi 0.5 hr</u>	<u>420°C 3000 psi 2.0 hr</u>
<u>Overall D-content 12.0 - 6.0 & 5.0 - (-2.0) ppm</u>						
Oil	6.6	8.6	13.0	18.6	20.3	26.7
Resin	10.3	14.0	17.7	23.9	25.1	30.9
Asph.	14.8	17.9	24.4	27.9	26.7	27.6
<u>Aromatic D-Content 12.0 - 6.0 ppm</u>						
Oil	13.3	13.2	17.0	22.5	22.0	25.3
Resin	16.3	19.1	22.1	26.2	25.5	31.2
Asph.	20.4	22.7	27.4	29.5	26.6	26.7
<u>Aliphatic D-Content 5.0 - (-2.0) ppm</u>						
Oil	6.1	8.3	12.7	18.2	20.2	26.9
Resin	9.4	13.2	17.0	23.4	25.0	30.7
Asph.	13.6	17.0	23.7	27.5	26.7	28.0
<u>Alpha D-Content 5.0 - 2.0 ppm</u>						
Oil	19.4	25.1	29.6	36.3	35.6	34.3
Resin	21.3	29.4	31.7	35.4	34.4	35.0
Asph.	25.3	30.4	34.4	36.5	33.6	31.7
<u>Beta D-Content 2.0 - 1.0 ppm</u>						
Oil	3.8	5.4	9.7	15.8	18.7	27.4
Resin	5.1	7.5	11.3	17.5	20.3	28.6
Asph.	8.2	10.3	17.0	21.2	21.4	24.7
<u>Gamma D-Content 1.0 - (-2.0) ppm</u>						
Oil	2.5	3.3	6.9	9.9	11.6	18.7
Resin	5.3	7.5	11.6	16.3	18.0	24.2
Asph.	8.5	11.3	18.4	21.7	22.7	25.3

FIGURE 11

Deuterium NMR Spectra of Solvent Separated Products Coprocessed at 420°C for 0.5 hrs under 3000 psi D₂: Oil (bottom), Resin (middle), and Asphaltene (top).

FIGURE 12

FIGURE 13

FIGURE 14

FIGURE 15

FIGURE 16

FIGURE 17

consisting of the petroleum residuum, coal, and dideuterium gas had a deuterium to hydrogen plus deuterium ratio ($D/[H + D]$) equal to 0.27. Therefore, a statistical distribution of deuterium among the different positions in the asphaltene molecules, as well as in the oil and resin molecules, of $D/(H + D) = 0.27$ was achieved. As residence time at 420°C increases from 0.0 to 2.0 hours, the D-content decreased in the asphaltene and increased in the oil as the common value of 27% is approached.

The relative levels of the positional dideuterium uptake and utilization demonstrate that, in the lower severity reactions, the aromatic and alpha aliphatic sites react first. While overall % deuterium content ranges between 7% for the oil and 15% for the asphaltene in the lowest severity reaction, aromatic % deuterium content ranges between 13% for the oil and 21% for the asphaltene. The corresponding values for the alpha aliphatic position are higher and range from 19 to 25%. Both alpha D-content and coal conversion reach their maximal values simultaneously. The initial deuterium levels for the beta and gamma positions range from 3 to 8%. As residence time is increased, the initial selectivity towards the aromatic and alpha aliphatic positions decreases. The aromatic D-content decreases in the asphaltenes as does the alpha D-content in all the fractions as deuterium atoms are shuttled and redistributed throughout the system. Concurrently, the beta and gamma D-content make large and continuous increases. Again, as residence time at 420°C is increased, the D-content of each of the positions approach the common value of 27%.

The pattern of utilization of the dideuterium in the alpha position is consistent and supportive of the idea that molybdenum catalysts often serve to cap reactive fragments in the initial stages of coal conversion when thermal cleavage of the structural elements that cross-link coal produces an abundance of benzylic reactive sites (47). Molybdenum catalyzed hydrogenation of these sites with deuterium atoms from the atmosphere would produce a surge in the benzylic and other alpha deuterium population. This pattern is observed as coal conversion and alpha deuteration increase swiftly and both reach their maximum values simultaneously. While the natural reactivity of the benzylic positions for deuterium/hydrogen atom exchange contributed to this result, certainly, molybdenum mediated deuterium atom transfer is likely the dominant force behind the ease with which coal conversion and high levels of alpha deuteration are achieved.

Figures 18-20 show the overall, aromatic, and aliphatic (H + D) content in mmol (H + D) per gram of product. Aromatic (H + D) levels are highest in the asphaltene fractions and lowest in the oil fractions. Aromatic (H + D) levels increase as a function of reaction conditions for all

fractions. For the oil fraction, this fact is consistent with the oil fraction becoming more aromatic in nature as large asphaltene aromatic molecules are being broken down into smaller pentane soluble hydroaromatic and alkylaromatic molecules. The increasing aromatic (H + D) content in the resin and asphaltene fractions is consistent with the idea that the asphaltene and resin fractions are "aromatized" via the cleavage and removal of aliphatic structural elements that are either attached to or crosslink large aromatic clusters. These aliphatic structural elements then become oil or possibly gas molecules. As expected, the aliphatic (H + D) decreased in the resin and asphaltene fractions. The oil aliphatic (H + D) content did not rise, as previously discussed, the oil fraction is becoming more aromatic as large aromatic asphaltene molecules are being converted to smaller aromatic oil molecules. Despite this effect and the fact that hydrogen rich light molecules are being stripped from the oil fraction, and that hydrogen rich gas production is increasing, aliphatic and overall (H + D) content in the oil remains relatively constant as the oil molecules are the benefactors of the large dideuterium incorporation that takes place during coprocessing.

Figures 21-23 show the aliphatic (H + D) content broken down into the alpha, beta, and gamma (H + D) content in mmol per gram. In the resin and asphaltene fractions, the alpha (H + D) content rises slightly while the beta and gamma (H + D) content significantly decreases consistent with the cleavage of the aliphatic structural elements as discussed above. The same general trends are seen in the oil fraction as hydrogen rich gas molecules escape. Note that the beta (H + D) content in oil fraction is three times as large as the alpha or gamma (H + D) content. These values are consistent with high levels of hydroaromatic and long chain aliphatic molecules in the oil.

FIGURE 18

FIGURE 19

FIGURE 20

FIGURE 21

Alpha H + D (mmol/g)

FIGURE 22

FIGURE 23

The (H + D) content of the different positions is more powerful as an indicator of the nature of molecules present in the different fractions as a function of reaction conditions when combined with the carbon content to calculate the (H + D) / C ratio. The (H + D) / C ratios have been calculated on a molar basis for the oil, resin, and asphaltene fractions. These values have been plotted as a function of reaction conditions in Figure 24. Also shown is a weighted average of the (H + D) / C ratios of the different fractions to yield a value for the combined coprocessed product. Consistent with the previous discussion, the (H + D) / C ratios for the resin and asphaltene fractions significantly decrease as a function of reaction conditions as the unconverted molecules become more aromatic in nature as the larger, unreactive, and probably condensed ring, structures remain. The oil (H + D) / C ratio increase after the reaction temperature of 420°C is reached. As residence time is then increased to two hours, it then essentially remains constant. The (H + D) / C does not increase dramatically for the previously discussed reasons that concurrent with the addition of deuterium occurs solubilization into the oil fraction of large amounts of small aromatic molecules and production of hydrocarbon gases. The weighted average (H + D) / C ratio for the combined coprocessed product also displays the effects of the gas production. This value fluctuates around 1.40 as net increase in deuterium consumption is offset by the net increase in hydrogen rich gas production that both take place as a function of the increasing severity of the conditions.

FIGURE 24

$[H + D] / C$ (mol/mol)

■ Oil □ Resin ◆ Asph. ◇ Total

CONCLUSION

Valuable information on the mechanistic aspects of the catalyst's behavior during the coprocessing reaction is provided by this investigation. As pressure, and then temperature, are increased during the first four reactions, trends that are not unexpected are observed in the values of the conversions and uptake and utilization of dideuterium. However, once 420°C is reached and then as residence time at this temperature is increased, important processes are observed. Coal conversion reaches its maximum value after 0.0 h at 420°C, and at the same time, D-content at the alpha position reaches its maximum value of approximately 36% in all the fractions after which it declines. In addition, the yield of the asphaltene fraction has reached its maximum, and the reactivity of the asphaltene molecules in terms of dideuterium uptake has reached its maximum level. All these observations are very closely related to coal conversion into toluene soluble products (a combination of oil, resin, and asphaltene) as they all reach their maximum levels concurrently. The molybdenum catalyst is essential during this stage of the reaction in promoting coal conversion by capping reactive molecules and, most importantly, inhibiting non-reversible insoluble producing condensation reactions. At this point, coprocessing is not overly costly in terms of gas and light material production and in terms of net dideuterium uptake. Unfortunately, the maximization of asphaltene conversion, not coal conversion, is the goal of the coprocessing reaction as the production of oil molecules leads to a useful product.

The maximization of asphaltene conversion is a function of residence time at 420°C in this series of batch autoclave reactions. As residence time at 420°C is increased, the processes upon which the conversion of asphaltene molecules to oil molecules depends become evident in terms of dideuterium uptake and utilization. Specifically, equilibration of deuterium throughout the system is being achieved. The % D-content at all the aromatic, alpha, beta, and gamma aliphatic positions is approaching the value of $D / [H + D] = 0.27$ of the initial feedstocks. This is the result of all the molecules being adducted onto the catalyst numerous times. Thus, adduction of asphaltene molecules onto the catalyst must take place many, many times for the reactions to take place upon which asphaltene conversion is dependent. Such reactions which by themselves or in combination consisting of reduction, adduction, fragmentation, and other processes that are essential to the molecular weight reducing processes that lead to oil molecules take place much less frequently than the uptake and exchange reactions that are responsible for the equilibration of deuterium.

During the coprocessing reaction, all of the molecules adduct onto the catalyst at a very high rate evidence of which is the near equilibrium levels of exchange. However, the asphaltene

AIM

Association for Information and Image Management

1100 Wayne Avenue, Suite 1100
Silver Spring, Maryland 20910

301/587-8202

Centimeter

Inches

MANUFACTURED TO AIM STANDARDS
BY APPLIED IMAGE, INC.

2 of 2

25. Wallace, S., Bartle, K. D., Burke, M. P., Egia, B., Lu, S., Taylor, N., Flynn, T., Kemp, W., Steedman, W. *Fuel* **1989**, 68, 961.
26. Ohuchi, T., Steer, J., Muehlenbachs, K., Carson, D. *Coal Sci. Technol.* **1987**, 11 (Int. Conf. Coal Sci., 1987), 379.
27. Curtis, C. W., Cassell, F. N. *Energy Fuels* **1988**, 2, 1.
- 28.a Gatsis, J. G., Nelson, B. J., Lea, C. L., Nafsis, D. A., Humbach, M. J., Davis, S. P. Continuous Bench-Scale Single Stage Catalyzed Coprocessing. Presented at the Contractor's Review Meeting, Pittsburgh, October 6-8, 1987.
- 28.b McMillan, D. F., Malhotra, R., Hum, G. P., Chang, S. J. *Energy Fuels* **1987**, 1, 193.
29. Ceylan, K., Stock, L. M. *Fuel* **1990**, 69, 1386.
30. King, H. H., Stock, L. M. *Fuel* **1984**, 63, 810.
31. Speight, J. G., Long, R. B., Trowbridge, T. D. *Fuel* **1984**, 63, 616.
32. Lange, T., Kopsel, R., Kuchling, T., Klose, E. *Fuel*, **1989**, 68, 361.
33. Collins, C. J., Raaen, V. F., Benjamin, B. M., Maupin, P. H., Roark, W. H. *J. Am. Chem. Soc.* **1979**, 101, 5009.
34. Hayatsu, R., unpublished results.
35. Skowronski, R. P., Ratto, J. J., Goldberg, I. B., Heredy, L. A. *Fuel* **1984**, 63, 440.
36. Stock, L. M. Hydrogen Transfer Reactions. In *The Chemistry of Coal Conversion*; Schlosberg, R. H., Ed.; Plenum: New York, 1985; Chapter 6.
37. Curtis, C. W.; Chung, W. J. *Energy Fuels* **1989**, 3, 148.
38. Fouda, S. A.; Kelly, J. F.; Rahimi, P. M. *Energy Fuels* **1989**, 3, 154.
39. Ohuchi, T.; Steer, J.; Muehlenbachs, K.; Carson, D. *Coal Sci. Technol.* **1987**, 11 (Int. Conf. Coal Sci., 1987), 379.
40. Curtis, C. W.; Cassell, F. N. *Energy Fuels* **1988**, 2, 1.
41. Miller, R. L.; Giacomelli, G. F.; McHugh, K. J.; Baldwin, R. M. *Energy Fuels* **1989**, 3, 127.
42. Curtis, C. W.; Pellegrino, J. L. *Energy Fuels* **1989**, 3, 160.
43. Curtis, C. W.; Kim, H. *Energy Fuels* **1990**, 4, 206.
44. Stock, L. M.; Gatsis, J. G.; Ettinger, M. D.; Cheng, C.; Ceylan, K.; Jiralerspong, S.; Mete, A. "Fundamental Reaction Pathways During Coprocessing". Final Report, DOE #DE-AG22-88PC88811, 1992.
45. Gatsis, J. G.; Nelson, B. J.; Lea, C. L.; Nafsis, D. A.; Humbach, M. J.; Davis, S. P. Continuous Bench-Scale Single Stage Catalyzed Coprocessing. Presented at the Contractor's Review Meeting, Pittsburg, October 6-8, 1987.
46. Nafsis, D. A.; Humbach, M. J.; Gatsis, J. G. "Coal Liquefaction Co-Processing". Final Report, DOE / PC / 70002-T6, 1988.

47. Burgess, C. E.; Artok, L.; Schobert, H. H. Prepr. Pap. - Am. Chem. Soc., Div. Fuel Chem. 1991, 36(2), 462.

APPENDIX I.

LIST OF PUBLICATIONS AND PRESENTATIONS

K. Ceylan and L. M. Stock, Reaction Pathways During Coprocessing. The Reactivity Patterns of Coals and Resids in Hydrogen Atom Transfer, Carbon-Carbon Scission, and Hydrodemethylation, Fuel, **69**, 1386-1393 (1990).

L. M. Stock, Pittsburgh Meeting on Coprocessing (1990).

K. Ceylan and L. M. Stock, Reaction Pathways During Coprocessing. The Reaction of Illinois No. 6 and Wyodak Coals with Lloydminster and Hondo Residua under Mild Conditions. Energy and Fuels, **5**, 482-487 (1991).

K. Ceylan and L. M. Stock, Reaction Pathways During Coprocessing. The Reaction of Illinois No. 6 Coal with Lloydminster Residuum. Preprints of Papers, Am. Chem. Soc. Fuel Chem. Div., 36(2), 630-634 (1991).

M. D. Ettinger, J. G. Gatsis, and L. M. Stock, Determination of Dideuterium Uptake During Coal Petroleum Resid Coprocessing. Preprints of Papers, Am. Chem. Soc. Fuel Chem. Div., 36(2), 635-638 (1991).

L. M. Stock, Ottawa Meeting on Coprocessing (1991).

C. Cheng and L. M. Stock, Preparation of Deuterium-Labeled Petroleum Residuum and Asphaltene. Energy and Fuels, **5**, 934-935 (1991).

M. D. Ettinger, J. G. Gatsis, and L. M. Stock, Dideuterium Incorporation During the Coprocessing Reaction of Lloydminster Petroleum Resid and Illinois No. 6 Coal in D₂. Preprints of Papers, Am. Chem. Soc. Fuel Chem. Div., 37(2), 920-924 (1992).

M. D. Ettinger J. G. Gatsis, and L. M. Stock, Mechanistic Aspects of Coal-Petroleum Residua Coprocessing,. Preprints of Papers, Am. Chem. Petroleum Chem. Div. (1993).

**DATE
FILMED**

7 / 29 / 93

END