UNC.

~~CONFIDENTIAL~~

CLASSIFICATION LEVEL
(S, C, OR U)

CLASSIFICATION CHANGED TO

ATOMICS INTERNATIONAL

A Division of North American Aviation, Inc.
(Insert)

MASTER

~~UNCLASSIFIED~~
appropriate classification)

BY AUTHORITY OF

NORMAN KETZLAH (CDP)

NAA-SR-MEMO

8244

Person authorizing

Letby M.L. Nash to M. Still (9-5-68) 3210AT

Do not remove
change this classification

BY

Norman Ketzlah

(Signature of person making the change,

5-7-70

and the date thereof)

This document contains _____ pages

This is copy 4 of _____ series _____

~~RESTRICTED~~

THIS DOCUMENT CONTAINS RESTRICTED DATA AS
DEFINED IN THE ATOMIC ENERGY ACT OF 1954.
ITS TRANSMITTAL OR THE DISCLOSURE OF ITS
CONTENTS IN ANY MANNER TO AN UNAUTHORIZED
PERSON IS PROHIBITED.

RECEIVED

JAN 30 1979

CALIF. PATENT GROUP
LIVERMORE BRANCH

CLASSIFICATION TYPE

(RD OR DI)

NOTICE

This report was prepared as an account of work
sponsored by the United States Government. Neither the
United States nor the United States Department of
Energy, nor any of their employees, nor any of their
contractors, subcontractors, or their employees, makes
any warranty, express or implied, or assumes any legal
liability or responsibility for the accuracy, completeness
or usefulness of any information, apparatus, product or
process disclosed, or represents that its use would not
infringe privately owned rights.

NAA-SR-MEMOs are working papers and may be expanded,
modified, or withdrawn at any time,
and are intended for internal use only.

This report may not be published without the approval of the Patent Branch, AEC.

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

LEGAL NOTICE

This report was prepared as an account of Government sponsored work. Neither the
United States, nor the Commission, nor any person acting on behalf of the Commission:

A. Makes any warranty or representation, express or implied, with respect to the
accuracy, completeness, or usefulness of the information contained in this report, or that
the use of any information, apparatus, method, or process disclosed in this report may
not infringe privately owned rights; or

B. Assumes any liabilities with respect to the use of, or for damages resulting from
the use of information, apparatus, method, or process disclosed in this report.

As used in the above, "person acting on behalf of the Commission" includes any em-
ployee or contractor of the Commission to the extent that such employee or contractor
prepares, handles or distributes, or provides access to, any information pursuant to his
employment or contract with the Commission.

REPRODUCED FROM BEST
AVAILABLE COPY

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency Thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DISCLAIMER

Portions of this document may be illegible in electronic image products. Images are produced from the best available original document.

FOR OFFICIAL USE ONLY

ATOMICS INTERNATIONAL A Division of North American Aviation, Inc.		NAA SR Memo TOR NO 8244		APPROVALS <i>SR Fields</i>	
TECHNICAL DATA RECORD		PAGE 1 OF 21			
AUTHOR N. K. Jamison J. Lampl D. G. Oliver		DEPT & GROUP NO 727-71 723-32 727-71		DATE 3/29/63 GO NO 7611	
TITLE An Evaluation of the Techniques for End-of-Life Shutdown of Orbiting SNAP Reactors		S A NO 2063		TWR	
PROGRAM Aerospace Safety		SUBACCOUNT TITLE End-of-Life Shutdown Devices		SECURITY CLASSIFICATION (CHECK ONE BOX ONLY)	
DISTRIBUTION pg 1-21 E. Ash C. Brous J. Brunings R. Chalker D. Cockeram M. Coombs R. Courson R. Detterman R. Eggleston H. Dieckamp J. Facha S. Fields W. Flynn R. Galantine R. Gimera K. Buttrey R. Balent R. Hart M. Heisler M. Hulin C. Johnson R. Johnson L. Maki D. Mason L. Mims L. Moss W. Morgan T. Nakae J. Rohlf V. Sanders W. Scott M. Slater D. Staub O. Steele J. Stewart J. Stolz W. Sturtevant J. Susnir R. Wallerstedt E. Weisner J. Watch J. Wilde R. Wilson R. Williams A. Piccott, D. Gylfe		(CHECK ONE BOX ONLY) UNCL. ☐ AEC ☐ DOD ☐ CONF. ☒ SECRET ☐		(CHECK ONE BOX ONLY) RESTRICTED DATA ☒ DEFENSE INFO. ☐	
		AUTHORIZED CLASSIFIER SIGNATURE <i>SR Fields</i>		DATE 4/4/63	
STATEMENT OF PROBLEM <p>Evaluate the techniques for end-of-life shutdown of orbiting SNAP reactors.</p>					
ABSTRACT <p>Two techniques for the end-of-life shutdown of orbiting SNAP reactors are presented. One technique consists of two alternative methods for the destruction of the reactor core. This technique (and others) have been investigated during the past year. A second technique, uses a naturally occurring phenomena, which works on the principle of a low neutron absorbing nuclide decaying to a high neutron absorbing daughter (poison). The present design criteria for the latter technique is that only a small reduction in reactivity should occur during the mission lifetime with the slow build-up of poison eventually shutting down the reactor at some later date. Tritium, an isotope of hydrogen is presented as a parent that appears to meet all of the requirements for such an end-of-life shutdown device. The daughter, He^3 has a high neutron absorption cross section.</p> <p>The results of a preliminary study of the tritium device are presented. These results indicate that tritium is extremely promising as an end-of-life shutdown device and recommendations are made for further study. Equations governing the buildup of He^3 are presented in Appendix A. The shutdown mechanism using tritium is time dependent and is not subject to other controls (telemetry or on board intelligence). Therefore, this natural phenomenon shutdown mechanism does not solve the short orbital lifetime case.</p>					

~~CONFIDENTIAL~~

ATOMICS INTERNATIONAL

A Division of North American Aviation, Inc.

NO. NAA SR Memo 8244

DATE 3/29/63

PAGE 2 OF 21

Introduction

During the past year, efforts have been directed toward the design and demonstration of new and advanced techniques to provide positive, reliable end-of-life shutdown of orbiting SNAP reactors. Of the many techniques considered, two that showed the greatest promise were chosen for further consideration.

One technique employed methods that destruct the reactor and disperse the fuel elements. The fission products in the resulting subcritical assembly would then decay before the dispersed core re-entered the atmosphere and burned. These methods are:

1. Explosive shutdown projectile
2. Chemical reaction shutdown device.

A second very promising technique, shuts down the reactor through the gradual accumulation of a poison due to the radioactive decay of a long half life parent with a low neutron capture cross section to a stable daughter with a high neutron capture cross section. The unstable isotope of hydrogen, tritium, was chosen for further study because it best satisfied the requirements of a natural occurring shutdown device.

The purpose of these end-of-life shutdown devices is to render the reactor subcritical after the end of its useful life, so that; 1) the reactor will be subcritical when it re-enters the atmosphere; 2) the accumulated radioactive fission products can decay, with no further buildup, prior to reactor re-entry into the atmosphere. If the orbital lifetime of the reactor is sufficiently long, the fission products will have time to decay down to a very low activity level.

Description and Discussion

A. Devices to destruct the reactor assembly and disperse the fuel elements.

1. Explosive Shutdown Projectile: A destruct missile is located in the low temperature and low radiation environment of the instrument compartment. When set off by a signal, a primer cap will initiate the propellant charge, and the missile will move along a curved tube around the neutron shield into the vicinity of the reactor vessel. An explosive charge in the missile will be initiated by impact with the reactor vessel. Suitably delayed explosives will detonate, and shrapnel and explosive action will destroy the reactor vessel and disperse the fuel rods. A diagrammatic sketch of the arrangement is shown in Fig. 1.

~~CONFIDENTIAL~~

~~CONFIDENTIAL~~

ATOMICS INTERNATIONAL
A Division of North American Aviation, Inc.

NO. NAA SR Memo 8244
DATE 3/29/63
PAGE 3 OF 21

A major problem associated with a device of this type would be the development of a suitable propellant charge which could withstand the radiation and temperature environment. However, the propellant charge will be located in the low temperature, low radiation environment of the instrument compartment which would not materially effect the performance of the pyrotechnics. Thus, development would be confined to:

1. determination of the proper charge
2. the delivery system design and performance
3. the signal and system reliability

2. Chemical Reaction Shutdown Device: This device uses the pressure increase due to gas developed by chemical reaction between inorganic metals and oxidizers, to disassemble the reactor. The reactants are stored in a sealed pressure vessel adjoining the lower end of the reactor vessel. Upon initiation of the reaction by means of an EBW squib, or other suitable initiator, pressure is developed which will first break the vessel seal, then invert a flexible diaphragm at the bottom of the reactor vessel. After inversion the flexible diaphragm will cover all coolant openings in the lower grid plate of the reactor, thus forming a piston, which, upon further pressure increase, will rupture the reactor vessel to drive out and disperse the fuel rods. A diagram of this device is shown on Figure 2.

Development of this device would require the selection of appropriate elevated temperature and high radiation resistant inorganic compounds which, upon initiation, will develop adequate pressures and temperatures to destroy the reactor. A series of chemical tests have been run on approximately 58 chemical compositions of which seven appear, from a pressure build-up standpoint, to be adequate. One of the most successful combinations of pyrotechnics is $\text{Al} + \text{Sr}(\text{NO}_3)_2$ with a suitable catalyst. This mixture withstood short term thermal stability tests without any problem. Other successful combinations were $\text{Al}_4\text{C}_3 + \text{Fe}_2\text{O}_3 + \text{C}$, $\text{Al}_4\text{C}_3 + \text{SnO}_2$, $\text{Ca} + \text{CaCO}_3$, $\text{Ca} + \text{SrCO}_3 + \text{Na}_2\text{CO}_3$, $\text{Ca} + \text{SrCO}_3$, $\text{Al} + \text{PbO} + \text{C}$, $\text{Ca} + \text{PbO} + \text{C}$, but all these reactions will require thermal stability proof before any further studies may be made.

~~CONFIDENTIAL~~

~~CONFIDENTIAL~~

ATOMICS INTERNATIONAL

A Division of North American Aviation, Inc.

NO. NAA SR MEMO 8244
DATE 3/29/63
PAGE 4 OF 21

Substantial additional investigations will be required to determine the high temperature and high radiation stability of the most promising combinations to solve initiation problems, under conditions characterized by full power 1-year operation of the reactor and to furnish data on the correct loading for optimum pressure rise.

B. Natural Occurring Phenomena

1. Natural decay shutdown devices

A. Tritium

This device works on the principle of a low neutron absorbing parent decaying to a high neutron absorbing stable daughter. Tritium (parent) has a half life of 12.26 years, a negligible neutron absorption cross section and decays to He^3 (daughter) by emitting a soft low energy (0.018 Mev) β^- particle. He^3 is stable with a neutron absorption cross section of 5400 barns. Absorption of a neutron by He^3 produces tritium as a product. Thus, in a reactor, this system is regenerative.

The design criteria is that a small reduction in reactivity should occur during the mission life, with the slow build up of poison (He^3) eventually shutting down the reactor at some later date.

A preliminary investigation indicates that tritium is extremely promising as an end-of-life shutdown device. No prohibitive problem areas have been revealed by this study. Some of the major aspects of tritium considered in this study were:

1. Cost and availability: Tritium is readily available and costs approximately \$2.00 per curie or about \$5000.00 for the SNAP 10A core.

2. Acceptable poisoning during mission lifetime: There will be approximately 22% loss in reactivity due to He^3 poisoning during the first year (for the SNAP 10A reactor) requiring some compensating prepoisoning for noncontrolled operation.

3. Hazards associated with the use of tritium: The low energy (0.018 Mev) β^- emissions would be completely attenuated by almost any containment material, for example, the attenuation through the 10 mil fuel element cladding is approximately 10^{-100} . The only health hazard would probably result during the manufacturing process of incorporating the tritium in the core. Since tritium is very toxic,

~~CONFIDENTIAL~~

ATOMICS INTERNATIONAL

A Division of North American Aviation, Inc.

NO. NAA SR Memo 8244

DATE 3/29/63

PAGE 5 OF 21

when taken internally, extreme precautions would be necessary to prevent the escape of tritium to the atmosphere. These health and safety precautions would undoubtedly result in the largest expenditure of time and money in the development of this end-of-life device.

4. Build-up of He^3 poison before shutdown: The poison buildup - power decay relationship was determined for the SNAP 10A reactor and power system. A basic assumption was that all heat removal systems remained operative until shutdown. The initial reactor power level of 35 KW was assumed. The results of this analysis are plotted in Figure 4. (See Appendices A and B)

5. Amount of tritium required for shutdown: It was assumed that a negative \$3.00 in reactivity would (independent of other reactivity losses) terminate reactor operation. To provide an adequate decay of T near end-of-life, an additional potential negative reactivity is required. A negative worth of \$4.00 was assumed adequate to provide \$3.00 for shutdown.

6. Time limitations for shutdown: With the assumptions made, shutdown of the SNAP 10A reactor would occur after 25 years operation. This result is shown in Figure 4.

7. Location of tritium in the reactor: It was assumed in this study that the tritium would be placed homogeneously in the reactor core, however, the general conclusions still apply if the tritium were placed elsewhere. A primary consideration was the placement of this isotope of hydrogen in the fuel elements using the hydriding process. The hydrogen concentration in SNAP 10A is approximately 5×10^{26} atoms/core (approximately 5×10^{22} atoms/cc) whereas the estimated necessary tritium concentration would be only 5×10^{22} atoms/core (approximately 5×10^{18} atoms/cc). (See Appendix C)

B. Other parent-daughter decay chains with low energy β^- emissions.

1. The following are possible natural decay shutdown devices which could be considered:

~~CONFIDENTIAL~~

The advantage of decay chains with low energy β^- emissions is that the preoperational reactor handling operations are not complicated by any radiation hazards. This requirement essentially prohibits the use of any parent-daughter chains with other than low energy β^- emission, since attenuation of the accompanying gamma radiation would be difficult.

2. Possible Natural occurring Processes that might be Considered as End-Of-Life Shutdown Devices, or Shutdown Initiating Devices:

- a. Evaporation of a metal or non metal in the space vacuum
- b. Corrosive action of an acid-the acid might also be a poison.
- c. Permeation of gases through metal initiating an action to shutdown the reactor.
- d. Pressure buildup of He due to (n, α) reaction with boron or lithium to trigger a reaction.
- e. Decay of a parent whose daughter is more susceptible to the actions described in items a and b above.

~~CONFIDENTIAL~~

ATOMICS INTERNATIONAL

A Division of North American Aviation

NO. NAA SR MEMO 8244

DATE 3/29/63

PAGE 7 OF 21

Conclusions and Recommendations

1. Destruct Devices

A. The advantage of the destruct shutdown systems described earlier is the fact that only one destruct device is required for the entire lifetime of the reactor. The device may be initiated during and after launch, before and after achieving a successful orbit, and any time after its useful life. A command box is designed to inject a firing pin into the primer cap of the destruct missile, or to fire an EBW squib in the case of the chemical reaction destruct device.

This command box will have 5 different parallel initiating commands, any one of which will initiate the destruct action:

- (1) Telemetry signal at any time.
- (2) Voltage drop when electrical power diminishes below a certain value.
- (3) NaK outlet temperature drop below a predetermined value.
- (4) Predetermined time of one year or longer.
- (5) Loss of pressure due to melting of the extended feeler tube by reentry heat.

B. Some disadvantages of using destruct methods as end-of-life shutdown devices.

(1) The Air Force objects to having many fragments in space to track for the orbital lifetime of the reactor.

(2) The difficulties involved in attaining the required reliability of 0.99999 for such devices.

2. Tritium as an end-of-life shutdown device

A. Some of the advantages of using tritium as an end-of-life shutdown device are:

(1) It is a natural occurring phenomenon which acts as a fail-safe device.

(2) The high absorption cross section of the daughter, He^3 , reduces the amount of tritium needed to provide reactor shutdown.

(3) In a reactor, the T - He^3 system is a regenerative cycle.

(4) The long half life of tritium will result in a small negative reactivity effect (app. \$.22 for SNAP 10A) during the mission life time.

(5) The decay emissions of low energy (0.018 mev) β^- are completely attenuated by most materials.

(6) Tritium is readily available (produced in the U.S.A.) and is relatively inexpensive.

ATOMICS INTERNATIONAL

A Division of North American Aviation, Inc.

~~CONFIDENTIAL~~

NO. NAA SR MEMO 8244
DATE 3/29/63
PAGE 8 OF 21

(7) Possible use of the existing hydriding process as a means of placing tritium homogeneously in the core.

B. Some of the disadvantages of using tritium as an end-of-life shutdown device are:

(1) There is a loss of reactivity during the mission lifetime due to the poisoning by He^3 . In a controlled reactor this would not be a problem. However, in a non-controlled reactor this loss of reactivity would have to be compensated for by some means of prepoisoning. This prepoisoning may be partially accomplished by using the tritium- He^3 decay chain to build up the desired amount of He^3 poison before assembly of the reactor prior to startup. It should be noted that some He^3 prepoisoning will be unavoidable due to the time span between manufacture, assembly, and reactor startup. This can either be an advantage or disadvantage depending on the results of future studies.

(2) Tritium is very toxic when taken internally, therefore, extreme precautions must be taken in any manufacturing process. However, once properly contained, no handling hazards exist since the soft β^- are easily attenuated by most materials.

(3) The continual pressure buildup of He^3 due to the decay of tritium, if the resulting He^3 gas is confined in a non-expanding containment vessel, could possibly rupture that vessel. This is a problem that is currently being considered in relation to the containment of tritium in the fuel elements. The buildup of He^3 pressure within the fuel material could possibly damage the fuel during reactor operation, similar to the effects of fission gases on the fuel material. Important consideration in evaluating these two problems will undoubtedly be given to the binding of He^3 in the zirconium-hydride lattice.

C. Recommendations for Further Study

(1) It is recommended that future studies be made to further investigate the feasibility of using tritium as an end-of-life shutdown device. These studies should include the determination of:

a. The exact He^3 concentration-reactor power relationship considering the actual changes in reactor power.

b. Placement or location of tritium in the reactor material with supporting nuclear calculations indicating the most effective placement.

c. Effect of the power distribution within the core on He^3 burnup.

~~CONFIDENTIAL~~

~~CONFIDENTIAL~~

ATOMICS INTERNATIONAL

A Division of North American Aviation, Inc.

NO. NAA SR NEMO 8244
DATE 3/29/63
PAGE 9 OF 21

d. Effect of temperature distribution within the core on the tritium redistribution and the subsequent effect on He^3 buildup and burnup.

e. Buildup of He^3 pressure

(1) During the mission lifetime

(2) During orbital lifetime.

f. Whether the He^3 remains bound in the fuel material (assuming hydriding of the tritium) or whether it will diffuse out into the annulus between the fuel and cladding. If He^3 remains preferentially in the fuel material what are the possible deleterious effects?

g. Health and safety problems during the manufacturing process.

h. Health and safety implications to the community of a reactor containing a toxic material.

i. Reactor power level versus time until shutdown is achieved. This would yield the total integrated power and the corresponding fission product buildup and decay.

j. Prepoisoning methods to compensate for the reactivity loss during the mission lifetime.

k. Suitability of using tritium in the fuel hydriding process.

l. Movement of tritium preferentially in chemical systems as a result of:

(1) Different strengths of hydrogen and tritium bonds.

(2) Different mobilities exhibited by atoms containing hydrogen and their counterparts containing tritium.

(2) The suitability of other isotopes as shutdown devices.

(3) Continue the investigation of the more promising chemical reaction combinations to determine their thermal and irradiation stability.

(4) Complete fabrication and initiate development tests on the command device. Items (3) and (4) are necessary for short orbital life.

~~CONFIDENTIAL~~

ATOMICS INTERNATIONAL

A Division of North American Aviation, Inc.

NO. NAA SR MEMO 8244

DATE 3/29/63

PAGE 10 OF 21

~~CONFIDENTIAL~~

References

1. I.O.L. D. G. Oliver to N. K. Jamison, "Preliminary Investigations of Tritium as an End-of-Life Device," February 21, 1963.
2. W. A. Rhoades, G. A. Long, "Multigroup Reactivity Calculations for our Region Systems," NAA-SR-Memo 7515, June 26, 1962.
3. Personal communication from J. Wilde.
4. H. P. Flatt and D. C. Baller, "The AIM-6 Code", January, 1961.
5. J. Lampl, NAA SR TDR 8380, "Status Report - Reactor End-of-Life Shutdown Device Development"

~~CONFIDENTIAL~~

~~CONFIDENTIAL~~

ATOMICS INTERNATIONAL

A Division of North American Aviation, Inc.

NO. NAA SR MEMO 8244
DATE 3/29/63
PAGE 11 OF 21

APPENDIX A

Build-Up of He³ Poison with Time Estimate to Shutdown and Required T Concentrations*

* Reference 1

The governing nuclear reactions in the T-He³ system are:

The equations describing these reactions are:

$$(2) \frac{d\text{He}^3}{dt} = \lambda T - \phi(t) \sigma_a \text{He}^3$$

$$\frac{dT}{dt} = -\lambda T + \phi(t) \sigma_a \text{He}^3$$

$$T(0) = T_0$$

$$\text{He}^3(0) = \text{He}_0^3$$

where:

He_0^3 = initial He³ concentration

T_0 = initial T concentration

λ = T decay constant

σ_a = He³ absorption cross section

$\phi(t)$ = neutron flux at time t, (proportional to reactor power)

t = time

Since the reactions (1) are regenerative, without loss, then by conservation:

$$(3) T + \text{He}^3 = \text{constant} = T_0 + \text{He}_0^3$$

which may be shown by the addition of the differential equations in (2). Assuming for the moment that $\phi(t)$ is constant, then the solutions to equations (2) are:

$$(4) \text{He}^3 = \frac{1}{\phi \sigma_a + \lambda} \left[\lambda (T_0 + \text{He}_0^3) + (\text{He}_0^3 \phi \sigma_a - T_0 \lambda) e^{-(\lambda + \phi \sigma_a)t} \right]$$

~~CONFIDENTIAL~~

~~CONFIDENTIAL~~

ATOMICS INTERNATIONAL

A Division of North American Aviation, Inc.

NO. NAA SR MEMO 8244

DATE 3/29/63

PAGE 12 OF 21

$$T = \frac{1}{\phi\sigma_a + \lambda} [\phi\sigma_a (T_0 + He_0^3) - (He_0^3 \phi\sigma_a - T_0 \lambda) e^{-(\lambda + \phi\sigma_a)t}]$$

Observation of equations (4) indicates that (at constant $\phi(t)$) the He^3 , T concentrations approach non-zero asymptotic values, so that:

$$(5) \quad \frac{He_{as}^3}{T_0 + He_0^3} = \frac{\lambda / \phi\sigma_a}{1 + \lambda / \phi\sigma_a} = \frac{1}{1 + \phi\sigma_a / \lambda}$$

as t (time) $\longrightarrow \infty$. This relationship is graphed in Figure 3.

The rate that the concentrations approach equilibrium is proportional to:

$$(6) \quad e^{-(\lambda + \phi\sigma_a)t}$$

Equation (5) shows that the asymptotic He^3 concentration is inversely proportional to reactor power, ϕ , and monotonically approaches $(T_0 + He_0^3)$ as ϕ approaches 0 (end-of-life). Equation (6) shows that the time to an equilibrium value (for a given ϕ , constant) increases with decreased power and monotonically approaches $e^{-\lambda t}$ as ϕ approaches 0. Thus equations (5) and (6) tend to indicate characteristics of solutions to equations (2). In general, asymptotic concentrations are never achieved since the build-up of He^3 poison changes ϕ through reactivity feedback mechanisms.

The reduction in power results in further increased poisoning and further power reduction. These processes continue until shutdown is achieved, provided enough poisoning is available to result in shutdown. Because of these processes, the T - He^3 system will eventually shutdown the reactor, independent of initial reactor power, although the time to shutdown will increase for higher modes of power operation.

Equations (4) oversimplify the end-of-life shutdown problem by assuming $\phi(t) = \text{constant}$. To account for the power decay, the time variable can be divided into a sufficient number of intervals in which the power is assumed constant in each time interval. Equations (4) may then be expressed by:

$$(7) \quad He^3(t) = \frac{1}{\phi_i\sigma_a + \lambda} [\lambda (T_0 + He_0^3) + (He_{i-1}^3 \phi_i\sigma_a - T_{i-1} \lambda) e^{-(\lambda + \phi_i\sigma_a)(t - t_i)}]$$

~~CONFIDENTIAL~~

~~CONFIDENTIAL~~

ATOMICS INTERNATIONAL

A Division of North American Aviation, Inc.

NO. NAA SR MEMO 8244

DATE 3/29/63

PAGE 13 OF 21

$$T(t) = \frac{1}{\phi_i \sigma_a + \lambda} \left[\phi_i \sigma_a (T_o + He_o^3) - (He_i^3 \phi_i \sigma_a - T_i \lambda) e^{-(\lambda + \phi_i \sigma_a)(t-t_i)} \right]$$

where: t_i , ϕ_i , He_i^3 , and T_i are corresponding values at the beginning of time interval, i .

The neutron flux, ϕ , is a function of the radiative heat transfer from the power system and reactivity feedback mechanisms of the reactor. Mechanisms of fuel burnup, prepoisoning, active reactor control, hydrogen leakage, redistribution, etc. determined the core reactivity at any time. For a given core reactivity, criticality is achieved through the temperature coefficient feedback mechanism, thereby establishing an equilibrium reactor temperature. Mechanisms of heat transfer within the reactor system and power (neutron flux, ϕ) corresponds to the equilibrium reactor temperature. Thus:

$$(8) \phi(t) = \phi_i = f(x_1, x_2, \dots, x_j)$$

where x_j are various heat transfer and reactivity feedback mechanisms.

To determine ϕ requires establishing a mode, (or modes) of reactor operation in space and expressing the heat transfer and radiation mechanisms. The difficulty lies in that these mechanisms depend upon the mode of operation, i.e., normal operation, loss of coolant flow, loss of coolant, etc. Further complications result because the modes of operation will undoubtedly change throughout life-time as parts of the reactor system fail or are damaged by environments, i.e. loss of coolant flow, loss of coolant. Thus a general description of equation (8) is impossible.

The generalities stated above may be reduced by assuming a single mode of operation throughout life. Equation (5) indicates that the minimum He^3 concentration occurs at maximum reactor power. Thus, if one assumes a mode of operation throughout life corresponding to a maximum possible power generation, the He^3 concentration at any time will be underestimated. This results in a conservative (longer) estimate to time of shutdown, since any lower power operation would result in higher He^3 (earlier shutdown) concentrations before end-of-life. Thus, this problem reduces to one of determining the mode of maximum power operation.

~~CONFIDENTIAL~~

~~CONFIDENTIAL~~

ATOMICS INTERNATIONAL

A Division of North American Aviation, Inc.

NO. NAA SR MEMO 8244
DATE 3/29/63
PAGE 14 OF 21

The considerations discussed above were incorporated into a shutdown analysis of the SNAP 10A power system. The mode of operation assumed coolant flow and system integrity until shutdown, i.e., heat was dissipated through the radiator surfaces. With this mode of operation the reactor power core temperature relationship was assumed to be:

$$(10) \dot{P}_i = P_o \left[\frac{T_{Ri} - P_i/P_o (T_{Ro} - T_{co}) - T_s}{T_{co} - T_s} \right]^4 \quad \text{Reference 3}$$

where

- P_i = reactor power over time, i
- P_o = initial reactor power = 35 KW
- T_R = nominal reactor average temperature over time, i
- T_{Ro} = critical nominal reactor average temperature = 955°F
- T_s = nominal space temperature = 0°F
- T_{co} = initial nominal converter panel temperature = 600°F

A negative reactivity effect from He^3 of \$3.00 after startup was assumed necessary to shutdown the reactor. The various reactivity feedbacks other than He^3 poisoning were all combined into a temperature coefficient so that the critical reactivity was defined by:

$$(11) \rho_c = \rho_T (T_{Ro} - T_{Ri}) - \text{He}_i^3$$

where ρ_T = temperature coefficient $= \frac{\$3.00}{T_{Ro} - T_s} = .00314 (\$/^\circ\text{F})$.

The initial concentrations, expressed in terms of reactivity worth were assumed:

$$(12) \quad T_o = \$4.00$$

$$\text{He}_o^3 = 0$$

$\phi_o \sigma_a = .0115/\text{yr.}$ determined by averaging over SNAP 10A neutron spectrum. (Reference 2)

~~CONFIDENTIAL~~

~~CONFIDENTIAL~~

ATOMICS INTERNATIONAL

A Division of North American Aviation, Inc.

NO. NAA SR MEMO 8244

DATE 3/29/63

PAGE 15 OF 21

Equation (7) was solved for He_i^3 in time intervals, i of one year with $\phi_i \sigma_a$ given by (10) and (11). The results of He_i^3 and P_i are plotted in Figure 4. Note that shutdown occurs after 25 years. To estimate the effects of increased initial power the SNAP 10A power was increased to 700 KW, Figure 4. With increased initial power, shutdown would occur after 45 years.

Calculations utilizing the AIM-6 computer codes determined that approximately 1.1×10^{18} atoms/cc of He^3 are required for a \$1.00 change in reactivity of the SNAP 2/10A reactor. Thus \$4.00 potential reactivity would require an initial T loading of approximately $4-5 \times 10^{18}$ atoms/cc approximately 5×10^{22} atoms/core. Since the T decay level is $.49 \times 10^{19}$ curies/atom, the initial radiation level would be $.49 \times 5 \times 10^3$, approximately 2500 curies/core.

~~CONFIDENTIAL~~

~~CONFIDENTIAL~~

ATOMICS INTERNATIONAL

A Division of North American Aviation, Inc.

NO. NAA SR Memo 8244

DATE 3/29/63

PAGE 16 OF 21

APPENDIX B WHERE TO PLACE PARENT

A number of possible areas in which to place the parent in the reactor for a reactivity effect are:

- (1) fuel
- (2) cladding structure
- (3) coolant
- (4) interface between core and reflector
- (5) reflector

The most reactivity important region would be the fuel. Placing T in the fuel would have the advantages of:

- (1) T could be mixed with H during hydriding
- (2) T would be contained by the cladding, eliminating a need for additional containing structure
- (3) Cladding would attenuate the β^- radiation

Disadvantages may be:

- (1) Build-up of pressure from the formed He^3
- (2) Enhance the effect of pressure on cladding integrity and fuel element growth during reactor operation
- (3) Radiation hazards during hydriding (preventing escape of T to the atmosphere).

The area of placing the parent in the reactor may also be limited from physical reasons by the amount of poisoning needed for shutdown. Fabrication hazards may dictate where the tritium is placed.

~~CONFIDENTIAL~~

~~CONFIDENTIAL~~

ATOMICS INTERNATIONAL
A Division of North American Aviation, Inc.

NO. NAA SR MEMO 8244
DATE 3/29/63
PAGE 17 OF 21

APPENDIX C
POISON BUILD-UP BEFORE MISSION

The poison build-up between fabrication and start of mission can be a problem. Assuming, at the time of fabrication, the parent source contains no poison daughter, then equation (4) Appendix A governs the build-up of the poison daughter.

$$(1) \quad \frac{He^3(t)}{T_0} = 1 - e^{-\lambda t}$$

where: t = time measured from $He(0) = 0$

This ratio is simply a function of the T decay constant, λ . Since poison that is formed between fabrication and the end of mission is not effective as a shutdown device, the time between fabrication and end of mission must be considered when determining the required parent concentration for shutdown.

~~CONFIDENTIAL~~

EXPLOSIVE SHUTDOWN DEVICE

FIG. 1

4-9-62

7590-A0482

ATOMICS INTERNATIONAL
A Division of North American Aviation, Inc.

~~CONFIDENTIAL~~

NO. NAA SR Memo 8244
DATE 3/29/63
PAGE 18 OF 21

~~CONFIDENTIAL~~

CHEMICAL REACTION SHUTDOWN DEVICE

4-26-62

FIG. 2

7590-A0524

ATOMICS INTERNATIONAL
A Division of North American Aviation, Inc.

NO. NAA-SR-Memo 8244
DATE 3/29/63
PAGE 19 OF 21

CONFIDENTIAL

CONFIDENTIAL

Figure 3 Asymptotic He^3 Concentration In
Constant Flux Conditions

Figure 4
Negative Reactivity Buildup From
7 - He³ End-of-life Mechanism Using SNAP 10A
Heat Radiation System

~~Confidential~~

~~Confidential~~