S-CAL RESEARCH CORPORATION

RECEIVED
JUN 17 1993
OSTI

SYSTEM TO INJECT STEAM AND PRODUCE OIL FROM THE SAME WELLBORE THROUGH
DOWNHOLE VALVE SWITCHING

Contract: DE-FG01-92 CE 15553

THIRD QUARTERLY REPORT

By: Dr. Michael Gondouin

Date: 6/11/93

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DISCLAIMER

MASTER

3D
DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

SYSTEM TO INJECT STEAM AND PRODUCE OIL FROM THE SAME WELLBORE THROUGH
DOWNHOLE VALVE SWITCHING

Contract DE-FG01-92 CE 15553

THIRD QUARTERLY REPORT

ABSTRACT:

The detailed design of a sliding sleeve valve operated by wireline has been completed. This Downhole Valve is obtained by modifications of two 2 7/8 in. commercial wireline-retrievable sleeve assemblies, which will be used to connect one of the upper branches of the patented Dual Whipstock to the 2 3/8 in. steam tubing, through a thermal expansion joint. Detailed engineering drawings and materials specifications have been completed.

The design of the 30 ft-long joint comprising an H joint at the top a dual whipstock at the bottom and flow control devices for up to three drainholes equipped with 1.75 in. liners has been completed for a 7 in. cased well. This combination may be used in multi-layered reservoirs as well as in single layered reservoirs. It is also compatible with rod pump locations either above the kick-off points or near the base of the curved part of the drainhole liners. This design provides sufficient flexibility for most potential applications in the California market.

Following a cost analysis, the manufacturing process will include a combination of three welding assemblies with one 5 ft-long machined part obtained by gun-drilling of 6.25 in. bar stock. The entire assembly will be made-up by API threaded connections.

Several qualified manufacturing contractors have expressed interest in manufacturing and distributing this oil field equipment in the US and abroad, under license, following a successful Field Test in California, scheduled for 1994.

10. DETAILED DESIGN OF THE DOWNHOLE STEAM SLIDING-SLEEVE VALVE

The sliding sleeve valve, shown on the upper right branch of the H joint on the conceptual drawing of Fig. 1 (from 2nd Quarter report) will consist of two OTIS wireline-retrievable sleeve assemblies, shown on Fig. 5. The upper part of each 2 7/8 in. tubing nipple joints, with the lateral ports, will be cut-off and replaced by a doubly threaded nipple (Fig. 6) equipped with a side connection to one of the two steam feeder lines of Fig. 1. A coupling joint will be used to connect both nipple joints together. The no-go section will be removed in the upper one, and the sliding sleeves of both assemblies will be connected by a coupling tube. The fish neck of each sleeve will be fastened to the sleeve by a threaded connection. Both sleeves will thus always be operated simultaneously by the wireline tool. When the circulation sleeve is on top and pushed down, steam flows from the tubing into the upper feeder line. When the blind sleeve is on top and pushed down, steam flows into the bottom feeder line. When both connected sleeves are pulled up, the steam tubing is isolated from both feeder lines. In all three cases, the end plug closing the bottom sleeve prevents steam from flowing into the H joint cavity, whose pressure is controlled by the pump.

At the start of each new "huff and puff" cycle, the dual sleeve is pulled to the surface, thus providing access of wireline tools into the lower branches of the H joint, for transferring the retrievable plug from one drainhole to the other. The order of the two sleeves in the dual sleeve is then reversed and the dual sleeve pushed down, so that steam now goes into the other feeder line and the other drainhole. Oil pumping may continue during this wireline operation if the rod pump is located above the kick-off points, as shown on Fig.1.

In under-pressured reservoirs, however, the pump and rods are first pulled out from the producing drainhole, prior to the wireline transfer of the plug and then re-inserted through the other lower branch of the H joint, now open and set into the other drainhole, while the dual sleeve is returned downhole. To guide the rods from the production tubing into the adjacent drainhole and to reduce rod wear, the window between the two legs of the H joint is equipped with rollers at the top and bottom, as shown on Fig.7, and the rods are equipped with rollers/centralizers in their curved part.

11.DETAILED DESIGN OF THE COMBINED ELEMENT

The upper part (10 ft) of the Combined Element is the H joint. It is made by a welded assembly of four forged plates, each one bent in a half circle of $2 \frac{3}{8}$ ID, for the two J parts and $2 \frac{7}{8}$ for the two U parts, as shown on Fig.8. Each of the half circles is first welded to the J shaped profile by a longitudinal MIG weld made by first tacking the two pieces together, and then progressively extending each tacked point into adjacent bead segments, so as to reduce the heat distortion of this slender sub-assembly. The two sub-assemblies are then MIG welded to each other following a similar welding procedure, to

form a tubular assembly of 6.25 in. maximum cross-section and 10 ft length. The excess metal on the inner side of each bead is milled-out and the top and bottom connecting pieces are added using transverse welds. The two upper branches of the H joint are two 2 7/8 OD tubing threads, welded at their base by a saddle equipped with a roller. The axis of the roller is in the transverse median plane of the central elongated tube of Fig. 9. The lower two branches consist of a thick Z plate presenting two threaded female connections. These are located at a one foot interval of each other along the longitudinal axis. The middle partition of the Z plate is also equipped with a roller. After milling out of all excess metal inside the H joint, an orientation groove is cut into each of the upper inlets. These groove serve to orient and trigger the kick-over tool used to transfer plugs and mandrels from one branch to the other by wireline. This completes the H joint sub-element, which is then annealed in a furnace to relieve all welding stresses.

The next major sub-element is made by gun-drilling a 4 ft-long bar stock of 6.25 in. OD. In this bar two 2.38 in. channels are drilled-out. One of them, the right one on Fig. 10, is drilled-through straight, but the other is drilled-through along two directions making a 2 degree angle. Each end of the two channels is then cut into an API threaded connection. On the right channel, these threads axes are the same as that of the channel, but on the left channel, the threads axes are also at 2 degree angle from that of the channel. In this way, the left channel is made into an S shape.

The third major sub-element is the upper tubular whipstock, made of hardened steel (non-drillable). Because of the 2 degree kick-off angle the maximum length of this tube is about 6 ft.

The fourth major sub-element consists of a similar tubular whipstock, fitted into an inverted Y nipple joint. Its over-all length is about 15 ft. The kick-off angle on the right channel is again 2 degrees. The bottom channel may be normally plugged, and used for dumping any entrained sand production into the bottom part of the casing, below the combined element. Alternatively, it may also be used to connect the well tubings to a separate zone in the reservoir.

The fifth major sub-element consists of a thick bottom plate, with an eccentric threaded hole and welded to a side apron plate covering at least half of the 6.25 in. circumference and presenting two elliptical windows machined for a tight fit connection around each of the two inclined whipstocks. The entire apron surface around the windows is covered with a rubber pad, which will provide a seal around each window when the combined element is hung into the 7 in. (OD) well casing and pressed against its inner surface by the extended hanger slips.

These 5 sub-elements are then assembled to each other by means of 6 commercially-available landing nipple joints (OTIS Type X, 2 7/8 in. OD) terminated by two male standard API threads, one at each end (Fig. 11). The threaded connections are made-up by rotating each landing nipple using a strap-wrench. Not shown on Figure 10 are the hydraulically-set hanger slips (or buttons), located on the left lateral sides of the second and fifth sub-elements, together with their hydraulic ports. This part of the detailed design is still under review. It will make use of commercially-available parts of tubing and liner hangers. The extension of these slips is caused by hydraulic pressure in the two parallel tubings when a retrievable plug is set in each of the landing nipples above the whipstocks and the bottom plate. Small hydraulic

lines,not shown,convey this pressure to each of the hanger slips.

Conversely,two 1.25 in.diameter angled channels in the second sub-element convey the steam from the semi-circular tubes,included in the H joint sides,to entry ports located below the landing nipple joints at the top of the second sub-element.These are not shown on Fig.10,but their detailed design,including O ring seals and method of assembly is now complete.

12.CONTACTS WITH MANUFACTURING SUB-CONTRACTORS

Two qualified potential sub-contractors for the machining/assembly of these new devices have also expressed an interest in the marketing and distribution of this equipment in the Oil Field,as a supplement to their own products.One of these manufactureers has a 30 ft deep test well in which these assemblies could be tested,using various wireline tools,prior to their introduction into a real oil well.This is a crucial step in the development of any oil well equipment.It allows to quickly de-bug the equipment,at minimum cost.A successful test in the 30 ft test well will also encourage Oil Operators to make available one of their wells for a field test of this new technology when they will be invited to witness wireline operations in the 30 ft test well.

WIRELINE-RETRIEVABLE SLEEVE ASSEMBLIES - Continued

Otis Dual Flow Sleeves allow flow both through the ports and from below. They are designed primarily to protect and preserve the polished surfaces from erosion caused by flow.

Otis Circulation/Flow Sleeves feature an equalizing valve and integral plug. These sleeves are used to allow communication between the tubing annulus and the tubing inside diameter while plugging the tubing below. They incorporate a positive hold-down and equalizing feature. The sleeve with equalizing valve is set in the ported no-go landing nipple and plugs the tubing below the landing nipple flow ports. This protects the polished honed areas

of the nipple. An equalizing valve equalizes the pressure above and below the plug prior to retrieving the flow sleeve, which is run and retrieved by standard wireline procedure. The flow sleeve can be redressed on the surface and reinstalled.

Otis No-Flow Sleeves with equalizing valve and integral plug may be used to prevent flow from below or through the ports of the nipple. These are identical to the circulation/flow sleeves, except ports in the fishing neck of the lock mandrel are removed, which effectively stops all flow through the ported nipple.

FN 4176

Otis Circulation/Flow Sleeve

FN 4175

Otis No-Flow Sleeve

FIG. 7. Pump Rod in
Drain hole
(Underpressured
Reservoir)

FIG. 8. Welded Assembly of
"H" Joint Tube

PERSPECTIVE VIEW

FIG. 9. Top Saddle and Roller
(H Joint Assembly)

Scales: Vertical 1/40
Horizontal 1/4

2 7/8 in Coupling Joints

Landing Nipples And Lock Mandrels

LANDING NIPPLES AND LOCK MANDRELS SELECTIVE BY RUNNING TOOL - Continued

X[®] AND XN[®] LANDING NIPPLES AND LOCK MANDRELS

TUBING								FOR STANDARD TUBING WEIGHTS						LOCK MANDREL ID	
								X PROFILE		XN PROFILE					
								PACKING BORE		PACKING BORE		NO-GO ID			
SIZE	WEIGHT	ID		DRIFT		(IN)	(mm)	(IN)	(mm)	(IN)	(mm)	(IN)	(mm)		
(IN)	(mm)	LB/FT	(kg/m)	(IN)	(mm)	(IN)	(mm)	(IN)	(mm)	(IN)	(mm)	(IN)	(mm)		
1.050	26.67	1.20	1.79	0.824	20.93	0.730	18.54	AVAILABLE ON REQUEST							
1.315	33.40	1.80	2.68	1.049	26.64	0.955	24.26								
1.660	42.16	2.30	3.43	1.380	35.05	1.286	32.66	1.250	31.75	1.250	31.75	1.135	28.83	0.82	15.75
		2.40	3.57												
1.900	48.26	2.40	3.57	1.660	42.16	1.516	38.51	1.500	38.10	1.500	38.10	1.448	36.78	0.75	19.05
		2.78	4.11	1.810	40.89	1.516	38.51								
		2.90	4.32												
2.063	52.40	3.25	4.84	1.751	44.48	1.657	42.09	1.625	41.28	1.625	41.28	1.536	39.01	0.75	19.05
2.375	60.33	4.60	6.85	1.995	50.67	1.901	48.29	1.875	47.63	1.875	47.63	1.791	45.49	1.00	25.40
		4.70	7.00												
2.875	73.03	6.40	9.53	2.441	62.00	2.347	59.61	2.313	58.75	2.313	58.75	2.205	56.01	1.38	35.05
		6.50	9.68												
3.500	88.90	9.30	13.85	2.992	76.00	2.867	72.82	2.813	71.45	2.813	71.45	2.666	67.72	1.75	44.45
		10.30	15.34	2.922	74.22	2.797	71.04	2.750	69.85	2.750	69.85	2.635	66.93	1.75	44.45
4.000	101.60	11.00	16.38	3.478	88.29	3.351	85.12	3.313	84.15	3.313	84.15	3.135	79.63	2.12	53.85
4.500	114.30	12.75	18.99	3.958	100.53	3.833	97.36	3.813	96.85	3.813	96.85	3.725	94.62	2.62	66.55
5.000	127.00	13.00	19.36	4.494	114.15	4.369	110.97	4.313	109.55	4.313	109.55	3.987	101.27	2.82	66.55
5.500	139.70	17.00	25.32	4.892	124.26	4.767	121.08	4.582	115.87	4.582	115.87	4.455	113.16	3.12	79.25

END

**DATE
FILMED**

7 / 13 / 93