Progress Report

"Heat Transfer Studies of Waste Repository Design"
R. F. Boehm (PI), with S. Chirukuri and A. Izzeldin (student assistants)
UNLV Mechanical Engineering Department

**MAIN TASK: VISUALIZATION METHODS IN HEAT TRANSFER
THROUGH POROUS MEDIA**

Summary:

Mr. Chirukuri, the student performing this work, returned from a one-month vacation to India early in the summer. During the week of his return, he experienced a fatal burn in the laboratory. The lab, including his equipment, was locked virtually all of this past quarter while investigations were being carried out. No progress was made on this aspect of the project. In fact this incident had a very chilling effect on all related work. It is anticipated that a new person will start on this task during the next quarter.

**SUPPLEMENTAL TASK: UNSATURATED FLOW EXPERIMENT
WITH HEAT TRANSFER IN POROUS MEDIA**

Overview Introduction:

An experimental study of heat transfer in a porous medium penetrated by a liquid is to be carried out. For this work a porous medium with imbedded heat source will be used, and unsaturated water flows will be applied in a transient manner. As water flows vertically and approaches the heater, the heated area should cause vaporization of the water, forcing the vapor to flow radially (thus generally with some horizontal component). At some point in the porous medium of sufficient distance from the heater) the vapor will condense and water will flow vertically again. In this way the water should be diverted around the heated area. This general phenomenon

has been called the "heat pipe" effect. Therefore, the determination of the temperature field is to be evaluated at several points in the test sample in order to evaluate the "heat pipe" effect. Further the experiment will present a model of heat and mass transfer in an unsaturated zone of porous media, taking into account the effects of temperature gradients on the advective flux, and of the enhancement of thermal conduction. In addition, the experiment will show the effects of moisture migration around a heated element in an unsaturated porous medium flow.

Design of Experiment:

During this quarter significant effort was related to setting up the medium-scale experiment to study the heat transfer and moisture migration through an unsaturated porous medium. In our case, the porous medium is to be represented by a bed of small diameter quartz beads. In this regard the following work was done:

1. Designed and fabricated the experimental apparatus which includes an inflow system, an outflow system, and a tank to hold the glass beads, heater, instrumentation, and water.
2. Drawings of the apparatus setup and individual part components were made using Macintosh CAD drawing software.

The entire experimental apparatus consists of (see Fig. 1):

1. Plastic tank filled with quartz beads: The main part of the experimental setup which has dimensions of 1' x 3' x 2' and considered to be the test section. Included in this category is the heater and the various transducers used in the overall instrumentation.

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

2. Inflow system: The top part of the setup constitutes the inflow system which is designed to give a uniform distribution of the water to the quartz-beads-filled tank.

3. Outflow system: The bottom part of the setup constitutes the outflow system which is used to measure the water exiting the test section.

Quartz-Beads-Filled Plastic Tank:

The middle part of the experiment setup is 1 x 3 x 2 ft (0.3 x 0.9 x 0.6 m) tank fabricated from a 1/2 inch Plexiglass sheet. The tank is uniformly packed with 0.037 in (0.94 mm) diameter quartz beads. The tank is fitted with a screen arrangement at the bottom to keep the quartz beads from flowing out with exiting water. In the middle region of the tank, a 5/8 inch (16 mm) diameter electrical immersion heater that spans the tank horizontally was mounted. Locations were established for mounting thermocouples, thermistors, or capacitance elements for measuring the temperature, moisture temperature and migration speed, or moisture concentration, respectively, inside the tank.

Thermocouples are applied here in a very conventional way. Small-diameter wire thermocouples are located in specific places around the heater element, both in close proximity as well as at some distance from it.

Thermistors are to be used much less frequently in planned experiments. Approximately six units are to be placed in each experimental set up. These devices are used in ways we have developed for saturated flows. This protocol utilizes two power levels in the thermistor. One is a "low power" mode which is typical of general temperature measurement techniques with thermistors. A second, "high power" mode, is used to determine fluid speed around the thermistor. The unsaturated, two-phase situation encountered

here results in a more complicated, less deterministic situation than we have seen before.

Capacitance elements are being developed in our laboratory for mapping moisture presence throughout the apparatus. While moisture-sensing elements are available commercially, they tend to be either too bulky, too expensive, or both for application here. We also considered time domain reflectometry (TDR), but this technique indicates average moisture contents over a reasonably large-sized volume. We desire essentially point measurements. The elements we are developing are made from simple duplex wire small diameter that finds its tips on one end stripped of insulation and the two wires epoxied on each side of a small dielectric spacer. Calibration of these elements is accomplished in a quartz bead bed with various concentrations of moisture.

Inflow System:

The inflow system is designed to give a uniform distribution of water to the beads contained in the plastic tank. The system consisted of a 5 gallon head tank mounted at 7 ft high on top of the main test tank, 3/4 in plastic tubes, control valve, and set of square-patterned spray nozzles. The square nozzles are mounted on 2x4 ft plastic plate which is fitted on top of the main test tank.

Outflow System:

The outflow system is composed of 1'x3'x7" plastic tank with partitions spanning the width of the test section and spaced approximately 3" apart. The partitions work as catch chambers which are used to measure the water exiting the test tank. With the partitions, it possible to infer the one-dimensional spatial distribution of water flowing out of the test section.

Calibrations and Instrument Setups:

We are currently checking out the various aspects of the apparatus. Perhaps our primary concern is the uniformity of the water spray on top of the fill material. This needs to be quite uniform so that we can see the effects of the heater parameters on the outflow. If the inflow is nonuniform with a large degree of uncertainty, we will not know what to anticipate in the outflow, assuming even direct flow through the apparatus. Hence a series of calibration tests have been performed.

Work is beginning on the set up and calibration of the instrumentation. Of particular concern is the capacitance elements. We are both constructing and calibrating those over a period of time.

When all calibrations are completed, we will then be installing all instrumentation in the fill bed. It is important that we know the precise location of the various transducers.

Experiment Performance:

It is anticipated that most of the experimental runs will be performed during the next quarter.

Figure 1: Complete experimental apparatus system (not to scale)

DATE

FILMED

5/23/94

END