10
1-9-92 GS①

ORNL-6684

ornl

**OAK RIDGE
NATIONAL
LABORATORY**

MARTIN MARIETTA

**NAVY
MOBILITY FUELS
FORECASTING SYSTEM
REPORT:**

**NAVY FUEL
PRODUCTION
IN THE YEAR 2000**

**G. R. Hadder
R. M. Davis**

**MANAGED BY
MARTIN MARIETTA ENERGY SYSTEMS, INC.
FOR THE UNITED STATES
DEPARTMENT OF ENERGY**

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

This report has been reproduced directly from the best available copy.

Available to DOE and DOE contractors from the Office of Scientific and Technical Information, P.O. Box 62, Oak Ridge, TN 37831; prices available from (615) 576-8401, FTS 626-8401.

Available to the public from the National Technical Information Service, U.S. Department of Commerce, 5285 Port Royal Rd., Springfield, VA 22161.

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

ORNL--6684

DE92 004599

Energy Division

**NAVY MOBILITY FUELS FORECASTING SYSTEM REPORT:
NAVY FUEL PRODUCTION IN THE YEAR 2000**

Principal Investigators

**G. R. Hadder
R. M. Davis**

Published September 1991

Report Prepared for

**Navy Energy & Natural Resources Office
Office of Naval Research
Department of the Navy**

Navy Program Manager

A. Roberts

**Prepared by the
OAK RIDGE NATIONAL LABORATORY
Oak Ridge, Tennessee 37831
managed by
MARTIN MARIETTA ENERGY SYSTEMS, INC.
for the
U.S. DEPARTMENT OF ENERGY
under Contract No. DE-AC05-84OR21400**

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

TABLE OF CONTENTS

LIST OF TABLES	v
LIST OF FIGURES	vii
ACRONYMS AND ABBREVIATIONS	ix
DEFINITIONS	xi
ACKNOWLEDGEMENTS	xiii
ABSTRACT	xv
EXECUTIVE SUMMARY	S-1
1. BACKGROUND FOR ANALYSIS OF NAVY FUEL PRODUCTION IN THE YEAR 2000	1-1
1.1 THE IRAQI INVASION OF KUWAIT	1-1
1.2 THE CLEAN AIR ACT AMENDMENTS OF 1990	1-2
1.3 DEMOCRATIZATION OF EASTERN EUROPE AND THE U.S.S.R.	1-3
1.4 FUTURE PETROLEUM MARKETS	1-4
2. FORECASTING SYSTEM AND KEY ASSUMPTIONS	2-1
3. REGIONAL FUEL PRODUCTION	3-1
3.1 FUEL PRODUCTION IN U.S. BUREAU OF MINES DISTRICTS 1 AND 2	3-2
3.2 FUEL PRODUCTION IN U.S. BUREAU OF MINES DISTRICTS 7 AND 11 ...	3-4
3.3 FUEL PRODUCTION IN U.S. BUREAU OF MINES DISTRICT 8	3-5
3.4 FUEL PRODUCTION IN U.S. BUREAU OF MINES DISTRICTS 9 AND 10 ...	3-7
3.5 FUEL PRODUCTION IN U.S. BUREAU OF MINES DISTRICT 13	3-9
3.6 FUEL PRODUCTION IN THE ASIA REFINING REGION	3-11
3.7 FUEL PRODUCTION IN THE CARIBBEAN REFINING REGION	3-13
3.8 FUEL PRODUCTION IN THE JAPAN REFINING REGION	3-14
3.9 FUEL PRODUCTION IN THE MIDDLE EAST REFINING REGION	3-16
3.10 FUEL PRODUCTION IN THE NORTH EUROPE REFINING REGION	3-18
3.11 FUEL PRODUCTION IN THE PACIFIC REFINING REGION	3-18
3.12 FUEL PRODUCTION IN THE SOUTH EUROPE REFINING REGION	3-19
4. OVERVIEW OF NAVY FUEL PRODUCTION IN THE YEAR 2000	4-1
4.1 BAU 2000 COMPARED TO 1990	4-1
4.1.1 JP-5 Production	4-1
4.1.2 F-76 Production	4-1
4.2 LOW OIL PRODUCTION IN THE U.S.S.R. IN THE YEAR 2000 COMPARED TO 1990	4-1

4.2.1	JP-5 Production	4-1
4.2.2	F-76 Production	4-2
4.3	LOW OIL PRODUCTION IN THE U.S.S.R. IN THE YEAR 2000 COMPARED TO BAU 2000	4-2
4.3.1	JP-5 Production	4-2
4.3.2	F-76 Production	4-4
5.	OBSERVATIONS AND RECOMMENDATIONS	5-1
6.	REFERENCES	R-1

LIST OF TABLES

Table 1.	Assumed Navy fuel production for 1990 and 2000	3-2
Table 2.	Cost and quality changes for F-76 produced in BOMs 1 & 2	3-3
Table 3.	Aromatics content change in U.S. home heating oil	3-4
Table 4.	Cost and quality changes for JP-5 produced in BOMs 7 & 11	3-5
Table 5.	Cost and quality changes for JP-5 produced in BOM 8	3-6
Table 6.	Cost and quality changes for F-76 produced in BOM 8	3-7
Table 7.	Cost and quality changes for JP-5 produced in BOMs 9 & 10	3-8
Table 8.	Cost and quality changes for F-76 produced in BOMs 9 & 10	3-9
Table 9.	Cost and quality changes for JP-5 produced in BOM 13	3-10
Table 10.	Cost and quality changes for F-76 produced in BOM 13	3-11
Table 11.	Cost and quality changes for JP-5 produced in the Asia refining region	3-12
Table 12.	Cost and quality changes for F-76 produced in the Asia refining region	3-13
Table 13.	Cost and quality changes for F-76 produced in the Caribbean refining region ..	3-14
Table 14.	Quality changes for JP-5 produced in the Japan refining region	3-15
Table 15.	Cost and quality changes for F-76 produced in the Japan refining region	3-16
Table 16.	Quality changes for JP-5 produced in the Middle East refining region	3-17
Table 17.	Cost and quality changes for F-76 produced in the Middle East refining region	3-18
Table 18.	Cost and quality changes for F-76 produced in the Pacific refining region	3-19
Table 19.	Cost and quality changes for JP-5 produced in the South Europe refining region	3-20
Table 20.	Cost and quality changes for F-76 produced in the South Europe refining region	3-21
Table 21.	Navy fuel production cost changes: low oil production in U.S.S.R. compared to BAU 2000	4-3
Table 22.	JP-5 quality changes: low oil production in U.S.S.R. compared to BAU 2000 ...	4-3
Table 23.	F-76 quality changes: low oil production in U.S.S.R. compared to BAU 2000 ...	4-4

LIST OF FIGURES

Figure 1. Navy Mobility Fuels Forecasting System and supporting activities	2-2
Figure 2. Potential problem areas for Navy fuels in year 2000 scenarios	5-2

ACRONYMS AND ABBREVIATIONS

BAU	Business-as-usual
BOM	Bureau of Mines
CAA	Clean Air Act
Comecon	Council for Mutual Economic Assistance
DoD	Department of Defense
DOE	Department of Energy
EIA	Energy Information Administration
KNPC	Kuwait National Petroleum Company
MBD	Thousand barrels per day
ORNL	Oak Ridge National Laboratory
OTM	Oil Trade Model
OPEC	Organization of Petroleum Exporting Countries
REMS	Refinery Evaluation Modeling System
RYM	Refinery Yield Model

DEFINITIONS

For this report, blendstocks are defined as follows:

Diesels - virgin or uncracked stocks with boiling range of 550 to 690 degrees Fahrenheit.

Hydrocrackates - products of hydrocracking, with boiling range of 295 to 525 degrees Fahrenheit.

Kerosenes - virgin or uncracked stocks with boiling range of 375 to 550 degrees Fahrenheit.

Light cycle oils - products of fluid catalytic cracking, with boiling range of 430 to 630 degrees Fahrenheit.

Naphthas - virgin stocks with boiling range of 250 to 375 degrees Fahrenheit.

ACKNOWLEDGEMENTS

Throughout the development and application of the Navy Mobility Fuels Forecasting System, technical guidance and collaboration have been received from the Navy Energy & Natural Resources Office, the Naval Air Propulsion Center, and the David Taylor Naval Ship Research and Development Center. Insights on petroleum markets and refinery trends have been provided by the East-West Center Resource Systems Institute; Chevron U.S.A., Inc.; Pacific Resources, Inc.; the Amerada Hess Corporation; the Sun Company; Ashland Petroleum Company; Exxon Company, U.S.A.; Conoco, Inc.; Coastal Corporation; the National Petroleum Council; and the American Petroleum Institute. Technical support, data resources, and access to the principal forecasting models have been furnished by the Energy Information Administration, Department of Energy. ENSYS Energy & Systems, Inc., and Turner, Mason and Company have assisted in modification of the refinery models. Temple, Barker & Sloane, Inc., has provided input on petroleum logistics issues of concern to the Navy. This report was edited and typed by Jonnie Sorensen of Oak Ridge National Laboratory. The valuable contributions of these individuals and organizations are greatly appreciated.

ABSTRACT

The Refinery Yield Model of the Navy Mobility Fuels Forecasting System has been used to study the availability and quality of Navy JP-5 jet fuel and F-76 marine diesel fuel for two scenarios in the year 2000. Both scenarios account for environmental regulations for fuels produced in the U.S. and assume that Eastern Europe, the U.S.S.R., and the People's Republic of China have free market economies. One scenario is based on business-as-usual market conditions for the year 2000. The second scenario is similar to first except that U.S.S.R. crude oil production is 25 percent lower. During lower oil production in the U.S.S.R., there are no adverse effects on Navy fuel availability, but JP-5 is generally a poorer quality fuel relative to business-as-usual in the year 2000.

In comparison with 1990, there are two potential problem areas for future Navy fuel quality. The first problem is increased aromaticity of domestically produced Navy fuels. Higher percentages of aromatics could have adverse effects on storage, handling, and combustion characteristics of both JP-5 and F-76. The second, and related, problem is that highly aromatic light cycle oils are blended into F-76 at percentages which promote fuel instability. It is recommended that the Navy continue to monitor the projected trend toward increased aromaticity in JP-5 and F-76 and high percentages of light cycle oils in F-76. These potential problems should be important considerations in research and development for future Navy engines.

NAVY FUEL PRODUCTION IN THE YEAR 2000

EXECUTIVE SUMMARY

The future availability and quality of petroleum products will be affected by political and business relationships in the Middle East; by changes in government and economic systems in Eastern Europe and the U.S.S.R.; and by environmental restrictions on fuel production and fuel quality. To investigate future petroleum markets, the Department of Navy, the Department of Energy, and Oak Ridge National Laboratory defined two scenarios for the year 2000. The scenarios account for Clean Air Act and anticipated environmental regulations in the U.S. and assume that Eastern Europe, the U.S.S.R., and the People's Republic of China have free market economies.

The first scenario is based on anticipated business-as-usual market conditions in the year 2000. The second scenario is similar to the business-as-usual case, except that U.S.S.R. crude oil production continues to decline to a level sufficient to satisfy only internal demand.

The Navy Mobility Fuels Forecasting System was used to study fuel production in the year 2000 scenarios and in the reference year 1990. The main study objectives were to estimate changes in the future availability and quality of Navy JP-5 jet fuel and F-76 marine diesel fuel. Study results suggest that, for both year 2000 scenarios:

JP-5 availability will be adequate to meet peacetime requirements.

The aromatics content of JP-5 produced in the U.S. will increase, but there will be no serious quality degradations compared to 1990.

Based on increased production costs, F-76 availability could be relatively tight compared to 1990.

The aromatics content of F-76 produced in the U.S. and in the Middle East will increase. There will be a large increase in light cycle oils blended to F-76 in the Middle East. Light cycle oils have inferior stability, with tendencies to produce gums and other particulates which can cause plugging of diesel engine filters and fouling of fuel injectors.

The increased aromatics content of Navy fuels produced in the U.S. is due in part to environmental restrictions on aromatics in motor gasolines and highway diesel fuel. Aromatics are shifted from these restricted fuels to Navy fuels and to home heating oil. Pollutant emissions of home heating oils could increase because of higher percentages of aromatics.

For the scenario of low oil production in the U.S.S.R. compared to business-as-usual conditions in the year 2000:

There will be no adverse effects on the availability of Navy fuels.

There will be degradations of JP-5 smoke and freezing points in several domestic regions.

There will be no adverse effects on the quality of F-76.

The forecasting system suggests that there are two potential problem areas for future Navy fuel quality. The first problem is increased aromaticity of domestically produced Navy fuels. Higher percentages of aromatics could have adverse effects on storage, handling, and combustion characteristics of both JP-5 and F-76.

The second problem is related to the first. With few exceptions, most notably in the Caribbean, highly aromatic light cycle oils are blended into F-76 at percentages which promote fuel instability.

It is recommended that the Navy continue to monitor the projected trend toward increased aromaticity in JP-5 and F-76 and high percentages of light cycle oils in F-76. These potential problem areas should be important considerations in research and development for future Navy engines.

1. BACKGROUND FOR ANALYSIS OF NAVY FUEL PRODUCTION IN THE YEAR 2000

In recent months, several significant events have occurred which could have far-reaching impacts on domestic and world oil markets. The most notable events have been the Iraqi invasion of Kuwait, passage of the Clean Air Act Amendments of 1990 (CAA), and democratization of Eastern Europe and the U.S.S.R.

1.1 THE IRAQI INVASION OF KUWAIT

In response to the August 2, 1990, Iraqi invasion of Kuwait, the United Nations imposed an embargo on oil exports from both Iraq and Kuwait. The embargo removed about 4.5 million barrels per day of oil from the world market. Consuming-country governments and oil companies were initially concerned about the loss of crude oil supplies. However, these concerns eased as other oil exporting nations increased output to replace the lost crude oil.

The barrel-for-barrel replacement of the embargoed crude oil did not remedy the problem for several reasons. First, the replacement crude oil was heavier than the lost Iraqi and Kuwaiti crude. The effect of this substitution was to shift the world supply balance in favor of heavy products. The world lost roughly 1 million barrels per day of light products, while gaining about 1 million barrels per day of fuel oil.

Second, the invasion and embargo forced shut-down of the complex 819 thousand barrels per day (MBD) refinery system in Kuwait. Prior to the embargo, between 50 and 60 percent of Kuwait refinery production was exported to the developed world, with volumes evenly shared between Japan and Europe.

Third, the demand for jet fuel was stimulated by military activity in the Persian Gulf, which increased world jet fuel demand 5 to 7 percent. As a result, jet fuel prices climbed sharply, pulling up the prices of crudes that yield a high percentage of middle distillates.

Finally, the uncertainties associated with the problems of the Middle East caused demand for precautionary stocks to increase.¹

During the Iraqi occupation and conflict, the Kuwait National Petroleum Company (KNPC) refinery at Shuaiba was badly damaged, according to preliminary assessments. The KNPC refineries at Mina Abdulla and Mina al Ahmadi* were stripped of process control equipment and spare parts, and their tank farms were damaged.³ An estimated 550-750 Kuwaiti oil wells were sabotaged by retreating Iraqi troops. An estimated 600 wells were blowing wild at the end of the land war in February, and perhaps one fourth of those had been killed by the following June. Continuing

*The Shuaiba refinery has a crude distillation capacity of 187 MBD, with downstream units including hydrocracking capacity of 102 MBD. The Mina Abdulla refinery has a crude distillation capacity of 190 MBD, with downstream units including a 34 MBD hydrocracker. The Mina Al-Ahmadi refinery has a crude distillation capacity of 370 MBD, with downstream units including a 34 MBD hydrocracker. The Getty Oil Company refinery at Mina Al-Zour has crude distillation capacity of 72 MBD but no downstream units.²

sanctions against Iraq could keep as much as 3 million barrels per day of oil from the market as long as Saddam Hussein remains in power.⁴

1.2 THE CLEAN AIR ACT AMENDMENTS OF 1990

Whereas the Iraqi invasion focused attention on energy security, the CAA were concerned with environmental security. The environment will be the major issue for domestic refiners in the 1990s.⁵

The CAA will affect refining more than any other industry because, in addition to complying with all other CAA provisions, refiners will have to modify, design, permit, and construct new units to produce mandated clean fuels. There are programs in the CAA for oxygenated gasoline and for reformulated gasoline.

The oxygenated gasoline program requires that, beginning November 1, 1992, gasoline with a minimum oxygen content of 2.7 weight percent be sold during winter months in about 40 cities not in compliance with carbon monoxide standards.

Reformulated gasolines are required by January 1, 1995, in nine cities with extreme or severe ozone pollution problems. About 100 other cities with marginal, moderate, or serious ozone problems may "opt-in" to the reformulated gasoline program. The law specifies a gasoline formula and also an emission performance standard for reformulated gasoline. The formula includes requirements for:

- A minimum oxygen content of 2 weight percent.

- A maximum benzene content of 1 volume percent (the current benzene content of gasolines averages 1.53 volume percent).

- A maximum aromatics content of 25 volume percent (the current aromatics content of gasolines averages 32 volume percent).

- No additives with heavy metals.

- No increase in nitrogen oxide emissions compared to present gasolines.

- A 15 percent reduction in ozone-forming volatile organic compounds, compared to 1990 levels. Beginning in the year 2000, volatile organic compounds and toxic emissions are required to be at least 20 percent below 1990 levels.⁶

The CAA also limits highway diesel fuel to a maximum sulfur content of 0.05 weight percent and a minimum cetane index of 40, effective October 1, 1993.⁷

Refiners will embark on major capital spending programs (estimated at \$24 billion in the 1990s) to produce fuels mandated by the CAA. The total cost for refining and marketing industry compliance with environmental regulations in the 1990s has been estimated at \$70-\$100 billion. The budgets of even the largest companies will be strained by this level of spending.⁶

With the passage of the CAA, environmental regulations will dictate the market, define product composition and performance, influence technology, change consumer expectations of performance, and determine the feasibility of various production and supply options.⁶ In short, domestic refinery operations will be driven by environmental regulations, not by the consumer.⁵

1.3 DEMOCRATIZATION OF EASTERN EUROPE AND THE U.S.S.R.

By the late 1980s, it had become clear that Centrally Planned Economies were failing to provide a sufficient rate of growth in economic output and living standards in Eastern Europe. Consequently, the ruling regimes lost legitimacy and fell from power. Successor regimes are seeking to liberalize the process of price formation, liberalizing trade, and ending the subsidization of inefficient enterprises. Large state enterprises are being converted to joint stock companies, and the formation of small and medium-sized enterprises is being encouraged.

The economic transformation is likely to have a strongly positive impact on the rate of growth in the longer term. However, in the near term, a significant reduction in output is expected. New regimes must stabilize economies by restoring equilibrium in consumer goods markets, cope with burdensome debts, and begin to reverse damage to the infrastructure, productive base, and environment caused by mismanagement and neglect.

The economic transformation has involved dismantling of the Council for Mutual Economic Assistance (Comecon) trading system, whereby Eastern European countries primarily exported goods to the U.S.S.R. in exchange for Soviet exports of energy and other raw materials. East European exports of goods which paid for oil were grossly overpriced in Comecon trade. The real cost of Soviet oil to Eastern Europe was much lower than the free market price.

Eastern Europe is now required to pay world market prices for Soviet oil with bilateral trade to be settled in hard currency. There will be a huge shift in terms of trade in favor of the U.S.S.R., creating severe balance of payment problems for Eastern European countries.

With the near-term economic dislocations, Eastern European energy production could decline together with deliveries of Soviet energy. However, energy shortfalls could be mitigated by reductions in the quantity of energy consumed due to the economic turndown. Also, higher relative prices for energy will mean savings in direct use of energy in production processes. Higher prices will cut indirect energy consumption through reduction of excessive use of energy-intensive materials, processes, and products.

The economic transformation and related energy problems of Eastern Europe are complicated by environmental problems which stem from heavy reliance on low quality coal. Environmental concerns will force a number of Eastern European countries to seek to replace significant shares of domestically produced coal-generated energy.

With trade at world market prices, there is no strong incentive for Eastern Europe to take Soviet energy, except that the infrastructure is in place. Furthermore, Eastern Europe has experienced sharp cutbacks in Soviet energy deliveries and now view the U.S.S.R. as an unreliable supplier.⁸ Indeed, Soviet petroleum officials have warned that the U.S.S.R. may be forced to import oil within two years due to what analysts see as woeful mismanagement.⁹

During the past three years, the U.S.S.R.'s petroleum industry has experienced the most severe and broad based setbacks ever suffered by a nation not involved in a major war or crippled by deliberate government decisions to limit oil flow. Soviet oil production declined a record 6.1 percent in 1990.¹⁰ Along with oil production, refinery utilization fell to the lowest point in decades. Crude and product exports fell so steeply in 1990 that Moscow officials were predicting the largest negative trade balance in history.¹¹

As U.S.S.R. crude oil exports decline, the Organization of Petroleum Exporting Countries (OPEC) replaces them because no other producer has a significant surplus of crude oil to export.¹² Given market-driven prices and Soviet export problems, Eastern European countries are now turning to OPEC and western producers for larger volumes of crude oil and products.

1.4 FUTURE PETROLEUM MARKETS

The future availability and quality of petroleum products will be affected by relationships with and within the Middle East; changes in Eastern Europe and the U.S.S.R.; and environmental regulations. To investigate future petroleum markets, the Department of Navy, the Department of Energy, and Oak Ridge National Laboratory defined two scenarios for the year 2000. The scenarios account for CAA restrictions in the U.S. and assume that Eastern Europe, the U.S.S.R., and the People's Republic of China have free market economies.

The first scenario is based on anticipated business-as-usual market conditions in the year 2000. The second scenario is similar to the business-as-usual case, except that U.S.S.R. crude oil production continues to decline to a level sufficient to satisfy only internal demand.

Global petroleum market conditions for both scenarios are discussed in the companion report on *World Petroleum Trade Forecasts for the Year 2000*.¹³ This report describes scenario impacts on regional refining operations, with emphasis on changes in the availability and quality of Navy JP-5 jet fuel and F-76 marine diesel fuel.

2. FORECASTING SYSTEM AND KEY ASSUMPTIONS

The Navy Mobility Fuels Forecasting System has been used to study fuel production in the year 2000. The main study objectives were to estimate relative changes in the future availability and quality of JP-5 and F-76.

The forecasting system, shown conceptually in Figure 1, consists of two Department of Energy models:

The Oil Trade Model (OTM) is a personal-computer-based, static, non-linear programming model which simulates world petroleum activities. Seven types of crude oils and eight types of refined products are produced and traded among the ten geographic regions of OTM. OTM balances petroleum supply and demand by maximizing consumer and producer surpluses, as constrained by world petroleum refining and distribution capabilities.¹⁴ Crude oil supplies and the production of refined products are forecast by OTM for input to the Refinery Yield Model (RYM).

RYM is a personal-computer-based linear program^{15,16} that represents regional refining operations. RYM includes 37 refinery processes, which can be used to produce over 30 products from at least 100 crude oils. Most of the RYM petroleum products are described by detailed quality specifications.

The OTM produces an aggregated picture of regional refining for different market scenarios. Although regional refining models are embedded within the OTM, they do not explicitly represent the production of important military fuels such as JP-5 and F-76. Therefore, RYM, which contains enhanced descriptions of military fuel production, is independently executed using key results of OTM. The stand-alone RYM can be used to evaluate many variations of the refining environment. For example, RYM can produce detailed information on the effects of changing refined product prices and specifications.

The OTM was used to analyze global petroleum markets in the year 2000 for a business-as-usual scenario and for a scenario with low oil production in the U.S.S.R.

The business-as-usual scenario (the "BAU 2000" scenario) is based on Department of Energy projections of domestic and foreign supply and demand.^{17,18}

The scenario for low oil production in the U.S.S.R. is similar to BAU 2000 except that U.S.S.R. crude oil production continues to decline such that, by the year 2000, U.S.S.R. crude oil production can satisfy only internal demand. U.S.S.R. oil production is 25 percent lower compared to the BAU 2000 scenario.

In addition to the future scenarios, RYM was used to analyze refinery operations for reference conditions in 1990 (the "Year 1990" case). Subject to data availability, RYM representations of regional refinery configurations, crude input and quality, product output and quality, and economic factors matched actual values for the Year 1990.^{2,19-28}

FIGURE 1

Navy Mobility Fuels Forecasting System and supporting activities

Key assumptions for the refinery analysis of the year 2000 scenarios included the following:

All domestic motor gasoline will be reformulated, with no lead; aromatics content limited to 25 volume percent maximum; benzene content limited to 1 volume percent maximum; and oxygen content limited to 2 weight percent minimum.⁷ The Reid vapor pressure of summertime gasoline will be reduced by about 25 percent relative to gasolines of the late 1980s.

Domestic civilian highway diesel fuel will be restricted to 0.05 weight percent maximum sulfur, a minimum cetane index of 40, and a maximum aromatics content of 20 volume percent.^{7,29,33}

U.S. military forces will convert from the use of naphtha jet fuel JP-4 and ground diesel fuel to the use of kerosene jet fuel JP-8.^{34,35}

Foreign motor gasoline octanes in the year 2000 will be comparable to the octanes of current mid-grade motor gasolines in the U.S. Foreign diesel fuel specifications in the year 2000 will be comparable to current U.S. diesel fuel specifications.

3. REGIONAL FUEL PRODUCTION

Refinery Yield Model studies were performed for all regions with recent histories of Navy fuel production:

U.S. Bureau of Mines (BOM) Districts 1 and 2 (Delaware, Georgia, New Jersey, New York, North Carolina, Pennsylvania, Virginia, and West Virginia).

BOM Districts 7 and 11 (Inland Texas and New Mexico).

BOM District 8 (Texas Gulf Coast).

BOM Districts 9 and 10 (Louisiana, Mississippi, Alabama, and Arkansas).

BOM District 13 (Alaska, Arizona, California, Hawaii, Nevada, Oregon, and Washington).

Asia Refining Region (Korea, Taiwan, Philippines, and others).

Caribbean Refining Region (Puerto Rico, Virgin Islands, Bahamas, Netherlands Antilles, and Trinidad).

Japan Refining Region (Japan, including Okinawa).

Middle East Refining Region (Iran, Iraq, Kuwait, Qatar, Saudi Arabia, United Arab Emirates, Egypt, Syria, and Tunisia).

North Europe Refining Region (Norway, Sweden, Denmark, Finland, Belgium, Netherlands, Luxembourg, United Kingdom, and Ireland).

Pacific Refining Region (Australia, New Zealand, Indonesia, Singapore, Malaysia, Bahrain, and others).

South Europe Refining Region (Spain, Portugal, Italy, Greece, and Turkey).

The assumed levels of Navy fuel production, in thousand barrels per day (MBD), are shown in Table 1.^{36,37} The assumed production levels are the same for both years 1990 and 2000.

Study results for regional fuel production are presented in the following subsections. Each subsection highlights significant changes in Navy fuel attributes. The changes are tabulated and discussed for each year 2000 scenario compared to the reference year 1990. Navy fuel blendstocks are tabulated for all years.

Qualitative changes in Navy fuel attributes between the year 2000 scenarios are also discussed in these subsections. Summary tabulations of significant quantitative changes between the year 2000 scenarios are included in the overview of results in Section 4.

Readers less interested in fuel production details may prefer to skip the following subsections and proceed to the overview of results in Section 4.

Table 1. Assumed Navy fuel production for 1990 and 2000 (MBD)		
Region	JP-5	F-76
BOMs 1 & 2	0.0	0.3
BOMs 7 & 11	1.1	0.0
BOM 8	19.4	13.2
BOMs 9 & 10	4.4	2.2
BOM 13	26.9	30.5
Asia refining region	2.4	6.4
Caribbean refining region	2.5	10.1
Japan refining region	0.5	0.8
Middle East refining region	6.6	8.2
North Europe refining region	0.2	0.0
Pacific refining region	1.6	18.5
South Europe refining region	2.0	6.0
Total	67.6	96.2

3.1 FUEL PRODUCTION IN U.S. BUREAU OF MINES DISTRICTS 1 AND 2 (Delaware, Georgia, New Jersey, New York, North Carolina, Pennsylvania, Virginia, and West Virginia)

The assumed production of F-76 in BOMs 1 & 2 is 0.3 MBD. As shown in Table 2, F-76 is more costly and more aromatic in the year 2000 than in 1990.

An important component of the production cost increase between the years 1990 and 2000 is the overall 25 percent increase in the cost of crude oils. The *crude mix* selected in BOMs 1 & 2 during low oil production in the U.S.S.R. is 11 percent more costly than the 1990 crude mix.

The increase in F-76 aromatics is due in part to environmental restrictions on aromatics in motor gasolines and diesel fuel. Aromatics are shifted from these restricted fuels to F-76 and to home heating oil, as shown in Table 3.

Crude oil costs and refined product prices do not change within the year 2000 scenarios. Production cost differences within the year 2000 scenarios are influenced by changes in crude mix and quality, by refinery process utilization, and by changes in the mix and quality of refined products.

For the year 2000 scenarios in BOMs 1 & 2, F-76 cost and aromatics are higher during low oil production in the U.S.S.R. These effects are related to a 9 percent greater requirement for diesel products, with greater competition for diesel blendstocks during the U.S.S.R. scenario compared to BAU 2000.

Aggregate blendstocks for F-76 do not change between 1990 and the year 2000. Light cycle oil content is high in all cases. Light cycle oils have inferior stability, with tendencies to produce gums and other particulates which can cause plugging of diesel engine filters and fouling of fuel injectors.^{38,39}

Table 2. Cost and quality changes for F-76 produced in BOMs 1 & 2		
F-76 Attribute	Attribute Change Relative to Year 1990 (Percent)	
	BAU 2000	U.S.S.R. Low Oil Production
Production Cost	+1.4	+11.1
Aromatics Content	+8.3	+23.5

Blendstock Composition			
Stock	Volume Percent		
	Year 1990	BAU 2000	U.S.S.R. Low Oil Production
Kerosenes	20	20	20
Diesels	50	50	50
Light cycle oils	30	30	30

Table 3. Aromatics content change in U.S. home heating oil		
Region	Volume Percent Change Relative to Year 1990	
	BAU 2000	U.S.S.R. Low Oil Production
BOMs 1 & 2	+23	+30
BOMs 7 & 11	+24	+23
BOM 8	+15	+15
BOMs 9 & 10	+24	+24
BOM 13	+30	+31

3.2 FUEL PRODUCTION IN U.S. BUREAU OF MINES DISTRICTS 7 AND 11 (Inland Texas and New Mexico)

The assumed production of JP-5 in BOMs 7 & 11 is 1.1 MBD. As shown in Table 4, JP-5 is more costly and more aromatic in the year 2000 scenarios than in 1990.

For the year 2000 scenarios, the production cost of JP-5 is lower, and the aromatics content is higher during low oil production in the U.S.S.R. The decreased cost is related to a 2 percent decline in the requirement for kerosene products, with decreased competition for kerosene blendstocks during the U.S.S.R. scenario compared to BAU 2000.

As expected with increased aromatics content, smoke point falls (degrades) in the U.S.S.R. scenario, but there is an anomalous increase (improvement) of smoke point in the BAU 2000 scenario.

Aggregate blendstocks for JP-5 in the reference year 1990 contain some naphtha. Blendstocks in the year 2000 are entirely kerosenes.

The increase in JP-5 aromatics is due in part to environmental restrictions on aromatics in motor gasolines and diesel fuels. Aromatics are also shifted to home heating oil, as shown in Table 3.

Table 4. Cost and quality changes for JP-5 produced in BOMs 7 & 11		
JP-5 Attribute	Attribute Change Relative to Year 1990 (Percent)	
	BAU 2000	U.S.S.R. Low Oil Production
Production Cost	+7.0	+4.4
Aromatics Content	+5.3	+7.4
Smoke Point	+5.2	-8.0

Blendstock Composition			
Stock	Volume Percent		
	Year 1990	BAU 2000	U.S.S.R. Low Oil Production
Naphthas	2	0	0
Kerosenes	98	100	100

3.3 FUEL PRODUCTION IN U.S. BUREAU OF MINES DISTRICT 8 (Texas Gulf Coast)

The assumed production of JP-5 in BOM 8 is 19.4 MBD. As shown in Table 5, JP-5 is more costly and more aromatic in the year 2000 scenarios than in 1990.

As expected with increased aromatics content, smoke point falls in the year 2000 scenarios. Low oil production in the U.S.S.R. has a more adverse effect on smoke point.

There is an improvement in freezing point in JP-5 produced in the BAU 2000 scenario. Freezing point is expected to fall as the characterization factor of a fuel decreases (i.e., the fuel becomes more aromatic), for a constant 50 percent recovery temperature.⁴⁰

Aggregate blendstocks consist of kerosenes in all cases.

Table 5. Cost and quality changes for JP-5 produced in BOM 8		
JP-5 Attribute	Attribute Change Relative to Year 1990 (Percent)	
	BAU 2000	U.S.S.R. Low Oil Production
Production Cost	+ 4.7	+4.6
Aromatics Content	+ 4.8	+4.8
Smoke Point	- 1.2	-5.3
Freezing Point	-12.3	0

Blendstock Composition			
Stock	Volume Percent		
	Year 1990	BAU 2000	U.S.S.R. Low Oil Production
Kerosenes	100	100	100

The assumed production of F-76 in BOM 8 is 13.2 MBD. As shown in Table 6, F-76 is more costly, more aromatic, and has lower (improved) pour points in the year 2000 than in 1990. Pour point is expected to fall as a fuel becomes more aromatic.⁴⁰

F-76 production cost and quality are not greatly affected by low oil production in the U.S.S.R., compared to BAU 2000.

Aggregate blendstocks for F-76 consist of more diesels and less kerosenes in the year 2000 scenarios compared to 1990. Light cycle oil content is high, with potential instability problems for all cases.

The increase in aromatics in Navy fuels produced in BOM 8 is due in part to environmental restrictions on aromatics in motor gasolines and diesel fuels. Aromatics are also shifted to home heating oil, as shown in Table 3.

Table 6. Cost and quality changes for F-76 produced in BOM 8		
F-76 Attribute	Attribute Change Relative to Year 1990 (Percent)	
	BAU 2000	U.S.S.R. Low Oil Production
Production Cost	+19.7	+19.6
Aromatics Content	+14.4	+15.7
Pour Point	-11.3	-10.5

Blendstock Composition			
Stock	Volume Percent		
	Year 1990	BAU 2000	U.S.S.R. Low Oil Production
Kerosenes	32	22	21
Diesels	38	48	49
Light cycle oils	30	30	30

3.4 FUEL PRODUCTION IN U.S. BUREAU OF MINES DISTRICTS 9 AND 10 (Louisiana, Mississippi, Alabama, and Arkansas)

The assumed production of JP-5 in BOMs 9 & 10 is 4.4 MBD. As shown in Table 7, JP-5 is more costly and less aromatic in the year 2000 scenarios than in 1990.

The reduced JP-5 aromatics content is notable when compared to the increased aromatics content for JP-5 produced in other domestic regions. However, home heating oil displays the expected response to environmental restrictions, with increased aromatics as shown in Table 3.

Compared to BAU 2000, the production cost of JP-5 falls during low U.S.S.R. oil production. The decreased cost is related to a 10 percent decline in the requirement for kerosene products, with decreased competition for kerosene blendstocks during the U.S.S.R. scenario compared to BAU 2000.

Aggregate blendstocks for JP-5 consist of kerosenes in all cases.

Table 7. Cost and quality changes for JP-5 produced in BOMs 9 & 10		
JP-5 Attribute	Attribute Change Relative to Year 1990 (Percent)	
	BAU 2000	U.S.S.R. Low Oil Production
Production Cost	+12.0	+6.3
Aromatics Content	- 3.6	-3.6

Blendstock Composition			
Stock	Volume Percent		
	Year 1990	BAU 2000	U.S.S.R. Low Oil Production
Kerosenes	100	100	100

The assumed production of F-76 in BOMs 9 & 10 is 2.2 MBD. As shown in Table 8, F-76 is more costly and less aromatic in the year 2000 than in 1990. The reduced aromatics content is notable when compared to the increased aromatics content for F-76 produced in other domestic regions. As previously mentioned, home heating oil displays the expected response to environmental restrictions, with increased aromatics.

Compared to BAU 2000, F-76 production is less costly during low oil production in the U.S.S.R. The decreased cost is related to an 11 percent decline in the requirement for diesel products, with decreased competition for diesel blendstocks during the U.S.S.R. scenario compared to BAU 2000.

Decreased pour points of F-76 in the year 2000 are related to increased percentages of lighter kerosene blendstocks and associated reductions in the 50 percent recovery temperature. Light cycle oil content is high, with potential instability problems for all cases.

Table 8. Cost and quality changes for F-76 produced in BOMs 9 & 10		
F-76 Attribute	Attribute Change Relative to Year 1990 (Percent)	
	BAU 2000	U.S.S.R. Low Oil Production
Production Cost	+26.5	+12.6
Aromatics Content	- 6.2	- 5.9
Pour Point	- 1.6	- 8.9
50% Recovery Temperature	- 4.0	- 4.9

Blendstock Composition			
Stock	Volume Percent		
	Year 1990	BAU 2000	U.S.S.R. Low Oil Production
Kerosenes	19	32	36
Diesels	51	38	34
Light cycle oils	30	30	30

3.5 FUEL PRODUCTION IN U.S. BUREAU OF MINES DISTRICT 13 (Alaska, Arizona, California, Hawaii, Nevada, Oregon, and Washington)

The assumed production of JP-5 in BOM 13 is 26.9 MBD. As shown in Table 9, JP-5 is more costly and more aromatic in the year 2000 scenarios than in 1990.

JP-5 production cost and quality are not greatly affected by low oil production in the U.S.S.R., compared to BAU 2000.

Improvements in the freezing point of JP-5 produced in the year 2000 scenarios are consistent with increased aromatics contents.

Aggregate blendstocks for JP-5 are kerosenes in all cases.

Table 9. Cost and quality changes for JP-5 produced in BOM 13		
JP-5 Attribute	Attribute Change Relative to Year 1990 (Percent)	
	BAU 2000	U.S.S.R. Low Oil Production
Production Cost	+6.4	+6.7
Aromatics Content	+3.4	+4.4
Freezing Point	-8.7	-6.7

Blendstock Composition			
Stock	Volume Percent		
	Year 1990	BAU 2000	U.S.S.R. Low Oil Production
Kerosenes	100	100	100

The assumed production of F-76 in BOM 13 is 30.5 MBD. As shown in Table 10, F-76 is more costly and more aromatic in the year 2000 scenarios than in 1990.

Compared to BAU 2000, low oil production in the U.S.S.R. has little effect on F-76 production cost and quality.

Decreased (improved) pour points of F-76 in the year 2000 are related to increased aromatics and reductions in the 50 percent recovery temperature. Light cycle oil content is high, with potential instability problems for all cases.

The increase in aromatics in Navy fuels produced in BOM 13 is due in part to environmental restrictions on aromatics in motor gasolines and diesel fuels. Aromatics are also shifted to home heating oil, as shown in Table 3.

Table 10. Cost and quality changes for F-76 produced in BOM 13		
F-76 Attribute	Attribute Change Relative to Year 1990 (Percent)	
	BAU 2000	U.S.S.R. Low Oil Production
Production Cost	+15.2	+15.5
Aromatics Content	+ 6.6	+ 6.6
Pour Point	- 7.8	- 7.8
50% Recovery Temperature	- 1.5	- 1.5

Blendstock Composition			
Stock	Volume Percent		
	Year 1990	BAU 2000	U.S.S.R. Low Oil Production
Kerosenes	19	19	19
Diesels	51	51	51
Light cycle oils	30	30	30

3.6 FUEL PRODUCTION IN THE ASIA REFINING REGION (Korea, Taiwan, Philippines, and others)

The assumed production of JP-5 in the Asia refining region is 2.4 MBD. As shown in Table 11, JP-5 is more costly in the year 2000 scenarios compared to 1990. JP-5 also has improved luminometer numbers and smoke points in the year 2000 scenarios. Higher luminometer numbers indicate greater flame radiation and improved combustion characteristics of a fuel.

Compared to BAU 2000, the JP-5 production cost is lower during low oil production in the U.S.S.R. The decreased cost is related to a 6 percent lower requirement for gasoline in the U.S.S.R., which indirectly depresses the value of distillate blendstocks.

Aggregate blendstocks for JP-5 are kerosenes in all cases.

Table 11. Cost and quality changes for JP-5 produced in the Asia refining region		
JP-5 Attribute	Attribute Change Relative to Year 1990 (Percent)	
	BAU 2000	U.S.S.R. Low Oil Production
Production Cost	+10.3	+ 6.2
Luminometer Number	+10.2	+10.2
Smoke Point	+ 9.1	+ 9.1

Blendstock Composition			
Stock	Volume Percent		
	Year 1990	BAU 2000	U.S.S.R. Low Oil Production
Kerosenes	100	100	100

The assumed production of F-76 in the Asia refining region is 6.4 MBD. As shown in Table 12, F-76 is more costly and less aromatic in the year 2000 than in 1990.

Compared to BAU 2000, F-76 cost and aromatics content are slightly lower during low oil production in the U.S.S.R.

Decreased pour points and viscosity of F-76 in the year 2000 scenarios are consistent with reduced 50 percent recovery temperatures. Light cycle oil content is high, with potential instability problems for all cases.

Table 12. Cost and quality changes for F-76 produced in the Asia refining region		
F-76 Attribute	Attribute Change Relative to Year 1990 (Percent)	
	BAU 2000	U.S.S.R. Low Oil Production
Production Cost	+35.6	+30.2
Aromatics Content	-12.9	-16.2
Pour Point	- 1.5	- 1.8
Kinematic Viscosity	-34.3	-45.7
50% Recovery Temperature	- 6.2	- 5.9

Blendstock Composition			
Stock	Volume Percent		
	Year 1990	BAU 2000	U.S.S.R. Low Oil Production
Kerosenes	19	19	19
Diesels	51	51	51
Light cycle oils	30	30	30

3.7 FUEL PRODUCTION IN THE CARIBBEAN REFINING REGION (Puerto Rico, Virgin Islands, Bahamas, Netherlands Antilles, and Trinidad)

The assumed production of JP-5 in the Caribbean refining region is 2.5 MBD. JP-5 cost and quality do not change appreciably for year 1990 and 2000 scenarios. Except for 3 percent naphtha blended to JP-5 in the year 1990, JP-5 aggregate blendstocks consist of kerosenes.

The assumed production of F-76 in the Caribbean refining region is 10.1 MBD. As shown in Table 13, F-76 is more costly, lighter, and less aromatic in the year 2000 scenarios than in 1990.

Decreased (improved) pour points and viscosities, and decreased (degraded) flash points in the year 2000 scenarios are consistent with increased percentages of lighter kerosene blendstocks, decreased specific gravity, and reduced 50 percent recovery temperatures. Higher (improved) cetane indices for the year 2000 scenarios are expected because of the inverse relationship between cetane number and aromatics content.

Compared to the BAU 2000 scenario, F-76 produced in the U.S.S.R. low oil production scenario is more aromatic and has a lower pour point.

F-76 production is notable for the relatively low percentages of light cycle oil blended in all cases.

Table 13. Cost and quality changes for F-76 produced in the Caribbean refining region		
F-76 Attribute	Attribute Change Relative to Year 1990 (Percent)	
	BAU 2000	U.S.S.R. Low Oil Production
Production Cost	+21.5	+21.5
Specific Gravity	- 4.5	- 4.4
Aromatics Content	-41.6	-24.4
Pour Point	- 6.7	-19.0
Cetane Index	+22.4	+22.2
Flash Point	- 1.0	- 1.0
Kinematic Viscosity	-45.2	-45.2
50% Recovery Temperature	-12.5	-12.5

Blendstock Composition			
Stock	Volume Percent		
	Year 1990	BAU 2000	U.S.S.R. Low Oil Production
Kerosenes	23	90	89
Diesels	60	0	5
Light cycle oils	17	10	6

3.8 FUEL PRODUCTION IN THE JAPAN REFINING REGION (Japan, including Okinawa)

The assumed production of JP-5 in the Japan refining region is 0.5 MBD. Production costs for JP-5 are about the same for year 1990 and 2000 scenarios. As shown in Table 14, burning

characteristics (luminometer number and smoke point) of JP-5 are improved in the year 2000 compared to 1990.

Compared to the BAU 2000 scenario, JP-5 produced during low oil production in the U.S.S.R. has a higher (improved) luminometer number and smoke point.

JP-5 aggregate blendstocks in all cases are kerosenes.

Table 14. Quality changes for JP-5 produced in the Japan refining region		
JP-5 Attribute	Attribute Change Relative to Year 1990 (Percent)	
	BAU 2000	U.S.S.R. Low Oil Production
Luminometer Number	+ 6.0	+12.1
Smoke Point	+ 5.2	+10.6

Blendstock Composition			
Stock	Volume Percent		
	Year 1990	BAU 2000	U.S.S.R. Low Oil Production
Kerosenes	100	100	100

The assumed production of F-76 in the Japan refining region is 0.8 MBD. As shown in Table 15, F-76 is more costly and consists of more kerosene and less naphtha blendstocks in the year 2000 compared to 1990.

Compared to BAU 2000, low oil production in the U.S.S.R. has little effect on F-76 cost and quality.

Increased flash points in the year 2000 scenarios are consistent with the increase in kerosene blendstocks at the expense of naphtha blendstocks. Light cycle oil content is high, with potential instability problems for all cases.

Table 15. Cost and quality changes for F-76 produced in the Japan refining region		
F-76 Attribute	Attribute Change Relative to Year 1990 (Percent)	
	BAU 2000	U.S.S.R. Low Oil Production
Production Cost	+21.7	+21.7
Flash Point	+ 3.1	+ 3.1

Blendstock Composition			
Stock	Volume Percent		
	Year 1990	BAU 2000	U.S.S.R. Low Oil Production
Naphthas	13	0	0
Kerosenes	0	19	19
Diesels	57	51	51
Light cycle oils	30	30	30

3.9 FUEL PRODUCTION IN THE MIDDLE EAST REFINING REGION (Iran, Iraq, Kuwait, Qatar, Saudi Arabia, United Arab Emirates, Egypt, Syria, and Tunisia)

The assumed production of JP-5 in the Middle East refining region is 6.6 MBD. Production costs for JP-5 are about the same in all scenarios. As shown in Table 16, burning characteristics (luminometer number and smoke point) of JP-5 are improved in the year 2000 compared to 1990.

Compared to BAU 2000, low oil production in the U.S.S.R. has little effect on JP-5 production cost and quality.

Notably, the aggregate blendstocks for JP-5 include about 3 percent hydrocrackate in the reference year 1990.

Table 16. Quality changes for JP-5 produced in the Middle East refining region		
JP-5 Attribute	Attribute Change Relative to Year 1990 (Percent)	
	BAU 2000	U.S.S.R. Low Oil Production
Luminometer Number	+22.0	+22.0
Smoke Point	+19.2	+19.2

Blendstock Composition			
Stock	Volume Percent		
	Year 1990	BAU 2000	U.S.S.R. Low Oil Production
Naphthas	0.3	0	0
Kerosenes	96.4	100	100
Hydrocrackate	3.3	0	0

The assumed production of F-76 in the Middle East refining region is 8.2 MBD. As shown in Table 17, F-76 is more costly, more aromatic, and contains more cracked stocks (light cycle oils) in the year 2000 compared to the reference year 1990. The increases in aromatic cracked stocks in F-76 are related to a 31 percent increase in refinery utilization in the year 2000 scenarios.

Compared to the BAU 2000 scenario, F-76 produced during low oil production in the U.S.S.R. is slightly less aromatic and has a slightly higher pour point.

Decreased pour points in the year 2000 scenarios are consistent with increased aromatics and reduced 50 percent recovery temperatures.

In the year 2000 scenarios, light cycle oil content is high, with potential instability problems.

Table 17. Cost and quality changes for F-76 produced in the Middle East refining region		
F-76 Attribute	Attribute Change Relative to Year 1990 (Percent)	
	BAU 2000	U.S.S.R. Low Oil Production
Production Cost	+22.1	+22.1
Aromatics Content	+41.1	+38.9
Pour Point	- 2.8	- 1.1
50% Recovery Temperature	- 6.9	- 6.8

Blendstock Composition			
Stock	Volume Percent		
	Year 1990	BAU 2000	U.S.S.R. Low Oil Production
Kerosenes	27	19	19
Diesels	68	51	51
Light cycle oils	5	30	30

3.10 FUEL PRODUCTION IN THE NORTH EUROPE REFINING REGION (Norway, Sweden, Denmark, Finland, Belgium, Netherlands, Luxembourg, United Kingdom, and Ireland)

The assumed production of JP-5 in the North Europe refining region is 0.2 MBD. JP-5 cost and quality do not change appreciably for year 1990 and 2000 scenarios. Aggregate blendstocks consist of kerosenes in all cases.

North Europe does not produce F-76 in the scenarios.

3.11 FUEL PRODUCTION IN THE PACIFIC REFINING REGION (Australia, New Zealand, Indonesia, Singapore, Malaysia, Bahrain, and others)

The assumed production of JP-5 in the Pacific refining region is 1.6 MBD. JP-5 cost and quality do not change for year 1990 and 2000 scenarios. Aggregate blendstocks consist of kerosenes in all cases.

The assumed production of F-76 in the Pacific refining region is 18.5 MBD. As shown in Table 18, F-76 is more costly and slightly less aromatic in the year 2000 scenarios than in 1990.

Compared to BAU 2000, low oil production in the U.S.S.R. has little effect on F-76 production cost and quality.

Slightly increased pour points in the year 2000 scenarios are consistent with decreased aromatics. Light cycle oil content is high, with potential instability problems for all cases.

Table 18. Cost and quality changes for F-76 produced in the Pacific refining region		
F-76 Attribute	Attribute Change Relative to Year 1990 (Percent)	
	BAU 2000	U.S.S.R. Low Oil Production
Production Cost	+22.2	+22.2
Aromatics Content	- 3.2	- 3.2
Pour Point	+ 1.3	+ 1.1

Blendstock Composition			
Stock	Volume Percent		
	Year 1990	BAU 2000	U.S.S.R. Low Oil Production
Kerosenes	19	19	19
Diesels	51	51	51
Light cycle oils	30	30	30

3.12 FUEL PRODUCTION IN THE SOUTH EUROPE REFINING REGION (Spain, Portugal, Italy, Greece, and Turkey)

The assumed production of JP-5 in the South Europe refining region is 2.0 MBD. As shown in Table 19, JP-5 is less aromatic and has improved burning characteristics (luminometer number and smoke point) in the year 2000 scenarios compared to 1990.

Compared to BAU 2000, JP-5 production is less costly during low oil production in the U.S.S.R. Overall production costs are higher in the BAU 2000 scenario because of requirements for hydrogen

and residual desulfurization capacity to produce 21 percent more low sulfur residual fuel compared to the U.S.S.R. scenario.

Aggregate blendstocks consist of kerosenes in all cases.

Table 19. Cost and quality changes for JP-5 produced in the South Europe refining region		
JP-5 Attribute	Attribute Change Relative to Year 1990 (Percent)	
	BAU 2000	U.S.S.R. Low Oil Production
Production Cost	+7.1	+0.7
Aromatics Content	-3.5	-3.5
Luminometer Number	+7.4	+7.4
Smoke Point	+6.7	+6.7

Blendstock Composition			
Stock	Volume Percent		
	Year 1990	BAU 2000	U.S.S.R. Low Oil Production
Kerosenes	100	100	100

The assumed production of F-76 in the South Europe refining region is 6.0 MBD. As shown in Table 20, F-76 is more costly in the year 2000 scenarios than in 1990.

Compared to BAU 2000, F-76 production is less costly during low oil production in the U.S.S.R. As previously discussed, residual desulfurization requirements increase overall production costs in the BAU 2000 scenario.

Pour points are higher in the year 2000 scenarios than in 1990. The increased pour point of the BAU 2000 scenario could be related to lower aromatics content.

Light cycle oil content is high, with potential instability problems for all cases.

Table 20. Cost and quality changes for F-76 produced in the South Europe refining region		
F-76 Attribute	Attribute Change Relative to Year 1990 (Percent)	
	BAU 2000	U.S.S.R. Low Oil Production
Production Cost	+30.9	+23.2
Aromatics Content	- 7.4	+ 0.2
Pour Point	+ 2.1	+ 2.3
50% Recovery Temperature	- 5.1	- 0.1

Blendstock Composition			
Stock	Volume Percent		
	Year 1990	BAU 2000	U.S.S.R. Low Oil Production
Kerosenes	19	19	19
Diesels	51	51	51
Light cycle oils	30	30	30

4. OVERVIEW OF NAVY FUEL PRODUCTION IN THE YEAR 2000

Three sets of comparisons can be made for the future availability and quality of Navy fuels: BAU 2000 compared to the reference year 1990; low oil production in the U.S.S.R. in the year 2000 compared to 1990; and low oil production in the U.S.S.R. in the year 2000 compared to BAU 2000.

4.1 BAU 2000 COMPARED TO 1990

4.1.1 JP-5 Production

Compared to 1990, production costs for JP-5 increase by as much as 12 percent in the BAU 2000 scenario. These cost increases, low compared to the overall 25 percent increase in crude oil costs, suggest that JP-5 availability will not be a problem in business-as-usual markets.

In most domestic regions, the aromatics content of JP-5 increases in BAU 2000 compared to 1990. The increase in aromatics is due in part to environmental restrictions on aromatics in motor gasolines and diesel fuels. Nevertheless, there are no serious degradations in the quality of JP-5 produced in any region, domestic or foreign.

4.1.2 F-76 Production

Compared to 1990, the production costs for F-76 increase by as much as 36 percent in the BAU 2000 scenario. These cost increases are high compared to the overall increase in crude oil prices and suggest that the availability of on-specification F-76 could be tight relative to 1990.

In most domestic regions, the aromatics content of F-76 increases due to environmental restrictions on aromatics in gasolines and diesel fuels.

In the Caribbean, there is a moderate decrease (degradation) in flash point.

Pour point rises (degrades) moderately in the Pacific and South Europe.

In the Middle East, there is a large increase in the light cycle oil content and in the aromatics content of F-76. Higher light cycle oil content suggests a degradation in the stability of F-76, with increased tendency to produce gums and other particulates.

4.2 LOW OIL PRODUCTION IN THE U.S.S.R. IN THE YEAR 2000 COMPARED TO 1990

4.2.1 JP-5 Production

Compared to 1990, production costs for JP-5 increase by as much as 7 percent in the scenario for low oil production in the U.S.S.R. These cost increases, low compared to the overall 25 percent increase in crude oil costs, suggest that JP-5 availability will not be a problem.

In most domestic regions, the aromatics content of JP-5 increases compared to 1990. The increase in aromatics is due in part to environmental restrictions on aromatics in motor gasolines and

diesel fuels. As a result of increased aromatics content, there are reductions (degradations) in the smoke point of JP-5 produced in BOMs 7 & 11 and in BOM 8.

4.2.2 F-76 Production

Compared to 1990, the production costs for F-76 increase by as much as 30 percent in the scenario for low oil production in the U.S.S.R. These cost increases are high compared to the overall increase in crude oil prices and suggest that the availability of on-specification F-76 could be tight relative to 1990.

In most domestic regions, the aromatics content of F-76 increases due to environmental restrictions on aromatics in gasolines and diesel fuels.

In the Caribbean, there is a moderate decrease (degradation) in flash point.

Pour point rises (degrades) moderately in the Pacific and South Europe.

In the Middle East, there is a large increase in the light cycle oil content and in the aromatics content of F-76. Higher light cycle oil content suggests a degradation in the stability of F-76.

4.3 LOW OIL PRODUCTION IN THE U.S.S.R. IN THE YEAR 2000 COMPARED TO BAU 2000

4.3.1 JP-5 Production

Compared to BAU 2000, the average production cost for JP-5 falls about 0.6 percent during low oil production in the U.S.S.R. As shown in Table 21, the only region with a relative cost increase is BOM 13.

Table 21. Navy fuel production cost changes: low oil production in U.S.S.R. compared to BAU 2000 (percent)		
Region	JP-5	F-76
BOMs 1 & 2		+ 9.6
BOMs 7 & 11	-2.4	
BOM 8	-0.1	- 0.1
BOMs 9 & 10	-5.1	-11.0
BOM 13	+0.3	+ 0.3
Asia refining region	-3.7	- 4.0
Caribbean refining region	0.0	0.0
Japan refining region	0.0	0.0
Middle East refining region	0.0	0.0
North Europe refining region	0.0	
Pacific refining region	0.0	0.0
South Europe refining region	-6.0	- 5.9

Compared to BAU 2000, a poorer quality JP-5 is generally produced during low oil production in the U.S.S.R. Table 22 shows smoke point degradations in BOMs 7 & 11 and in BOM 8. There are freezing point degradations in BOM 8 and in BOM 13. Japan is an exception, producing JP-5 with an improved smoke point.

Table 22. JP-5 quality changes: low oil production in U.S.S.R. compared to BAU 2000 (percent)		
Region	Smoke Point	Freezing Point
BOMs 7 & 11	-12.5	0
BOM 8	- 4.2	+1.8
BOM 13	0	+2.2
Japan refining region	+ 5.1	0

4.3.2 F-76 Production

Compared to BAU 2000, the average production cost for F-76 falls about 0.8 percent during low oil production in the U.S.S.R. As shown in Table 21, the only regions with increased production costs are BOMs 1 & 2 and BOM 13.

Compared to BAU 2000, the quality of F-76 is about the same in the U.S.S.R. scenario. As shown in Table 23, there are notable reductions of pour points in BOMs 9 & 10 and in the Caribbean; and viscosity is reduced in Asia. These reductions might be considered quality improvements.

Table 23. F-76 quality changes: low oil production in U.S.S.R. compared to BAU 2000 (percent)		
Region	Pour Point	Kinematic Viscosity
BOM 8	+ 0.9	0
BOMs 9 & 10	- 7.4	0
Asia refining region	- 0.3	-17.4
Caribbean refining region	-13.2	0
Middle East refining region	+1.7	0
Pacific refining region	-0.2	0
South Europe refining region	+0.2	0

5. OBSERVATIONS AND RECOMMENDATIONS

The Refinery Yield Model of the Navy Mobility Fuels Forecasting System suggests that, for business-as-usual conditions in the year 2000, with or without low oil production in the U.S.S.R.:

JP-5 availability will be adequate to meet peacetime requirements.

The aromatics content of JP-5 produced in the U.S. will increase, but there will be no serious quality degradations compared to 1990.

Based on increased production costs, F-76 availability could be relatively tight compared to 1990.

The aromatics content of F-76 produced in the U.S. and in the Middle East will increase. There will be a large increase in light cycle oils blended to F-76 in the Middle East, with a potential degradation in fuel stability.

The increased aromatics content of Navy fuels produced in the U.S. is due in part to environmental restrictions on aromatics in motor gasolines and diesel fuels. Aromatics are shifted from these restricted fuels to Navy fuels and to home heating oil. Pollutant emissions of home heating oils could increase because of higher percentages of aromatics.

For low oil production in the U.S.S.R. compared to business-as-usual conditions in the year 2000, the forecasting system suggests that:

There will be no adverse effects on the availability of Navy fuels.

There will be degradations of JP-5 smoke and freezing points in several domestic regions.

There will be no adverse effects on the quality of F-76.

Based on forecasting system results, Figure 2 summarizes two potential problem areas for future Navy fuel quality. The first problem is increased aromaticity of domestically produced Navy fuels. Higher percentages of aromatics could have adverse effects on storage, handling, and combustion characteristics of both JP-5 and F-76.

The second problem is related to the first. With few exceptions, most notably in the Caribbean, highly aromatic light cycle oils are blended into F-76 at percentages which promote fuel instability.

It is recommended that the Navy continue to monitor the projected trend toward increased aromaticity in JP-5 and F-76 and high percentages of light cycle oils in F-76. These potential problem areas should be important considerations in research and development for future Navy engines.

Figure 2
Potential problem areas for Navy fuels in year 2000 scenarios

6. REFERENCES

1. P.K. Verleger, Jr., "Understanding the 1990 Oil Crisis," *The Energy Journal*, Vol. 11, No. 4, 1990, pp. 15-33.
2. L.A. Thrash, "Worldwide refining," *Oil & Gas Journal*, December 31, 1990, pp. 84-111.
3. "Kuwaiti oil sector damage worse than feared," *Oil & Gas Journal*, March 4, 1991, p. 22.
4. "Oil price volatility possible through 1992, depending on gulf scenarios," *Oil & Gas Journal*, June 24, 1991, pp. 21-25.
5. J. Hadder, "Report on AIChE Spring National Meeting, Petrochemical Expo'91, and Tour of Exxon Olefins Plant (Houston, April 8-11, 1991)," memorandum to Dick Davis, Oak Ridge National Laboratory, Oak Ridge, TN, April 17, 1991.
6. R.C. Scherr, G.A. Smalley, Jr., and M.E. Norman, "Clean Air Act complicates refinery planning," *Oil & Gas Journal*, May 27, 1991, pp. 68-75.
7. "Motor Fuel Requirements Under the Clean Air Act Amendments," memorandum, National Petroleum Refiners Association, Suite 1000, 1899 L. Street, NW, Washington, DC, October 31, 1990.
8. C. Movit, "East Europe's energy trade takes new shape," *Oil & Gas Journal*, June 3, 1991, pp. 57-64.
9. M. Sieff, "Soviet oilfield foul-ups could force imports," *The Washington Times*, February 20, 1991.
10. "Soviet oil industry woes may extend crisis," *Oil & Gas Journal*, June 3, 1991, pp. 65-70.
11. "Oil's woes ripple through Soviet economy," *Oil & Gas Journal*, January 7, 1991, pp. 26-27.
12. L.F. Ivanhoe, "Soviet oil production drop may be major, lasting global supply woe," *Oil & Gas Journal*, September 3, 1990, pp. 69-71.
13. S. Das, *World Petroleum Trade Forecasts for the Year 2000*, ORNL-6683, Oak Ridge National Laboratory, Oak Ridge, TN, September 1991.
14. "The Oil Trade Model (OTM)," draft documentation, Decision Analysis Corporation of Virginia, Vienna, VA, October 1989.
15. *Refinery Evaluation Modeling System (REMS) Documentation*, DOE/EIA-0460, Energy Information Administration, U.S. Department of Energy, Washington, DC, October 1984.

16. *Refinery Evaluation Modeling System (REMS) Documentation*, DOE/EIA-0461, Energy Information Administration, U.S. Department of Energy, Washington, DC, October 1984.
17. *International Energy Outlook 1990*, DOE/EIA-0484(90), Energy Information Administration, U.S. Department of Energy, Washington, DC, March 1990.
18. *National Energy Strategy: Powerful Ideas for America*, First Edition 1991/1992, U.S. Department of Energy, Washington DC, 1991.
19. L.A. Thrash, "Annual refining survey," *Oil & Gas Journal*, March 26, 1990, pp. 77-101.
20. *Petroleum Supply Annual 1990*, DOE/EIA-0340(89)/1, Energy Information Administration, U.S. Department of Energy, Washington, DC, May 1990.
21. *International Energy Annual 1988*, DOE/EIA-0219(88), Energy Information Administration, U.S. Department of Energy, Washington, DC, November 1989.
22. *U.S. Petroleum Refining*, National Petroleum Council, Committee on U.S. Petroleum Refining, draft working document, National Petroleum Council, 1625 K. Street, N.W., Washington, DC, September 26, 1986.
23. C.L. Dickson, P.W. Woodward, and P.L. Bjugstad, *Trends of Petroleum Fuels, 1987*, NIPER-309, ITT Research Institute, National Institute for Petroleum and Energy Research, Bartlesville, OK, December 1987.
24. C.L. Dickson and P.W. Woodward, *Motor Gasolines, Summer 1987*, NIPER-153 PPS, National Institute for Petroleum and Energy Research, Bartlesville, OK, March 1988.
25. C.L. Dickson and P.W. Woodward, *Motor Gasolines, Winter 1987-88*, NIPER-155 PPS, National Institute for Petroleum and Energy Research, Bartlesville, OK, June 1988.
26. C.L. Dickson and P.W. Woodward, *Heating Oils, 1988*, NIPER-156 PPS, National Institute for Petroleum and Energy Research, Bartlesville, OK, July 1988.
27. *World Wide Survey of Motor Gasoline Quality 1987*, OPP No. 4, The Associated Octel Company Limited, 20 Berkeley Square, London, England, July 1988.
28. C.L. Dickson and P.W. Woodward, *Diesel Fuel Oils, 1988*, NIPER-157 PPS, National Institute for Petroleum and Energy Research, Bartlesville, OK, October 1988.
29. Federal Register, Vol. 50, No. 51, March 15, 1985, p. 10606.
30. Federal Register, Vol. 51, No. 124, June 27, 1986, p. 23437.
31. *U.S. Refining Industry Capability to Manufacture Ultra Low Sulfur Diesel Fuels*, NPRA Survey 1986, National Petroleum Refiners Association, Suite 1000, 1899 L. Street, NW, Washington, DC 20036.

32. G.R. Hadder, S. Das, R. Lee, N. Domingo, and R.M. Davis, *Navy Mobility Fuels Forecasting System Phase V Report: Impacts of Ultra Low Sulfur Diesel Fuel Production On Navy Fuel Availability*, ORNL-6570, Oak Ridge National Laboratory, Oak Ridge, TN, September 1989.
33. "Flexible new process converts aromatics to a variety of diesel feedstocks," *Oil & Gas Journal*, July 1, 1991, p. 55.
34. G.R. Hadder, S. Das, R. Lee, N. Domingo, and R.M. Davis, *Navy Mobility Fuels Forecasting System Phase V Report: Jet Fuel Conversion by Pacific Fuel Suppliers and Impacts on Navy Fuel Availability*, ORNL-6569, Oak Ridge National Laboratory, Oak Ridge, TN, September 1989.
35. "Army tests support NATO fuel switch," *Oil & Gas Journal*, May 15, 1989, p. 26.
36. *Defense Energy Information System*, DoD 5126.46-M, Department of Defense, Office of the Assistant Secretary of Defense, Manpower, Reserve Affairs and Logistics, Washington, DC, December 1982.
37. *DFAMS Data Element Dictionary*, Defense Logistics Agency, Cameron Station, Alexandria, VA, April 18, 1985.
38. M.W. Schrepfer, R.J. Arnold, and C.A. Stansky, "Distillate stability ensured by testing, treatment," *Oil & Gas Journal*, January 16, 1984, pp. 79-84.
39. D.R. Hardy, R.N. Hazlett, and E.W. White, "Assessment of Storage Stability Additives for Naval Distillate Fuel," *Conference Proceedings, 2nd International Conference on Long-Term Storage Stabilities of Liquid Fuels*, Southwest Research Institute, San Antonio, TX, July 29 - August 1, 1986, pp. 887-901.
40. W.L. Nelson, *Petroleum Refinery Engineering*, McGraw-Hill, NY, 1958, p. 139.

INTERNAL DISTRIBUTION

1. M. S. Bronzini	10. P. Leiby
2. S. Das	11. M. MacDonald
3. R. M. Davis	12. W. R. Mixon
4. P. S. Gillis	13. D. E. Reichle
5. D. L. Greene	14. R. B. Shelton
6. G. R. Hadder	15. ORNL Patent Office
7. P. S. Hu	16. Central Research Library
8. M. A. Kuliasha	17-18. Laboratory Records
9. R. Lee	19. Laboratory Records--RC

EXTERNAL DISTRIBUTION

20. B. B. Buchanan, Professor, Computer Science Department, University of Pittsburgh, 206 Mineral Industries Building, Pittsburgh, PA 15260
21. J. J. Cuttica, Vice President, End Use Research and Development, Gas Research Institute, 8600 W. Bryn Mawr Avenue, Chicago, IL 60631
22. D. E. Morrison, Professor of Sociology, Michigan State University, 201 Berkeley Hall, East Lansing, MI 48824-1111
23. R. L. Perrine, Professor of Engineering and Applied Sciences, Engineering I, Room 2066, 405 Hilgard Avenue, University of California, Los Angeles, CA 90024-1600
24. M. Williams, Professor, Department of Economics, Northern Illinois University, DeKalb, IL 60115
- 25-34. OSTI, U.S. Department of Energy, P.O. Box 62, Oak Ridge, TN 37831
35. Office of Assistant Manager of Energy Research and Development, DOE/ORO, P.O. Box 2001, Oak Ridge, TN 37831-8600
36. D. Butler, Energy Information Administration, U.S. Department of Energy Room 5A-139, 1000 Independence Avenue, S.W., Washington, DC 20585
37. D. Dunbar, Private Consultant, 784 Columbia Avenue, Apt. 4E, New York, NY 10025
38. C. Heath, Energy Information Administration, Department of Energy, EI-42, Forrestal Building, 1000 Independence Avenue, S.W., Washington, DC 20585
39. J. Hinkle, Strategic Petroleum Reserve, Room 3G-024, 1000 Independence Avenue, S.W., Washington, DC 20585
40. C. Kilgore, Energy Information Administration, Department of Energy, Room 1H087, Forrestal Building, 1000 Independence Avenue, S.W., Washington, DC 20585
- 41-45. C. J. Nowack, Naval Air Propulsion Center, Code PE33, P.O. Box 7176, Trenton, NJ 08628
46. Office of Assistant Manager for Energy Research and Development, Department of Energy, Oak Ridge Operations Office, Oak Ridge, TN 37831
- 47-57. A. Roberts, Office of Naval Research, Navy Energy & Natural Resources Office, Code ONR-12E, 800 N. Quincy Street, Arlington, VA 22217-5000
58. A. Roehmer, U.S. Department of Energy, 1000 Independence Avenue, S.W., Room 4G-084, Washington, DC 20585
59. N. R. Sefer, Senior Research Engineer, Southwest Research Institute, Fuels and Lubricants Research Division, 6220 Culebra Road, P.O. Drawer 28510, San Antonio, TX 78284

- 60-69. R. Strucko, David Taylor Naval Ship Research and Development Center, Code 2759, Annapolis, MD 21402
- 70. M. Tallett, EnSys Energy and Systems, Inc., Rd. 7, Box 519, Flemington, NJ 08822
- 71-78. Technical Information Center, U.S. Department of Energy, P.O. Box 62, Oak Ridge TN 37831
- 79. W. Vreath, Naval Ordnance Station, Management Operations Group, Code 56C1, Indian Head, MD 20640

END

**DATE
FILMED**

01/29/92