**COAL LIQUEFACTION PROCESS STREAMS
CHARACTERIZATION AND EVALUATION**

**Quarterly Technical Progress Report
July 1 through September 30, 1991**

**R. A. Winschel, S. D. Brandes,
G. A. Robbins, F. P. Burke**

November 1991

**CONSOLIDATION COAL COMPANY
Research & Development Department
4000 Brownsville Road
Library, PA 15129**

**Prepared for the
United States Department of Energy
Under Contract No. DE-AC22-89PC89883**

**US/DOE Patent Clearance was provided by
Chicago Operations Office on 11/5/91**

MASTER
ds

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

FEB 13 1992

DEC 20 1991

NOTICE

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States nor any agency thereof, nor any of their employees, makes any warranty, expressed or implied, or assumes any legal liability or responsibility for any third party's use or the results of such use of any information, apparatus, product or process disclosed in this report, or represents that its use by such third party would not infringe privately owned rights.

**COAL LIQUEFACTION PROCESS STREAMS
CHARACTERIZATION AND EVALUATION**

**Quarterly Technical Progress Report
July 1 through September 30, 1991**

**R. A. Winschel, S. D. Brandes,
G. A. Robbins, F. P. Burke**

November 1991

**CONSOLIDATION COAL COMPANY
Research & Development Department
4000 Brownsville Road
Library, PA 15129**

**Prepared for the
United States Department of Energy
Under Contract No. DE-AC22-89PC89883**

**US/DOE Patent Clearance was provided by
Chicago Operations Office on 11/5/91**

TABLE OF CONTENTS

	<u>Page</u>
INTRODUCTION	1
Overview	1
Contract Objectives	2
Contract Activities - This Period	3
DISCUSSION	6
Hydrogenation Tests with Simulated Dowtherm A	6
Procedure	7
Results	8
Test No. 1, Simulated Dowtherm A	8
Test No. 2, Wilsonville Run 260D Distillate	8
Conclusions	9
Participants Program Status	
Summary	10
Phase I	10
Phase II	10
Discussion	10
Phase I	10
Phase II	12
Application of Standard Petroleum Refinery Tests to Coal	
Liquefaction Products - Conoco's Crude Oil Inspection Tests	
With Wilsonville Run 260D Net Product	13
Background	13
Discussion	14
EXPERIMENTAL	17
Micro-Distillation Procedure	17
Equipment	17
Procedure	18
REFERENCES	19

LIST OF FIGURES

<u>Figure</u>	<u>Page</u>
1 GC/MS Total Ion Chromatogram of Simulated Dowtherm A and Its Hydrogenation Product.	20
2 GC/MS Total Ion Chromatogram of Wilsonville Run 260D V-131B Distillate and Hydrogenation Product.	21
3 Micro-Distillation Apparatus.	22

APPENDICES

<u>Appendix</u>	<u>Page</u>
1 Modified Crude Oil Assay of Wilsonville Run 260D Net Products	23
2 Stable Carbon Isotope Analysis of Coprocessing Materials - Extended Abstract	34
3 Application of Fluorescence Microscopy to Coal-Derived Resid Characterization	35

ABSTRACT

COAL LIQUEFACTION PROCESS STREAMS CHARACTERIZATION AND EVALUATION, QUARTERLY TECHNICAL PROGRESS REPORT, JULY 1 THROUGH SEPTEMBER 30, 1991

This is the eighth Quarterly Technical Progress Report under DOE Contract DE-AC22-89PC89883. Major topics reported are:

- Hydrogenation tests were performed with the components of Dowtherm A heat transfer fluid to examine their behavior at reaction conditions simulating those used at Wilsonville. Dowtherm A is an occasional contaminant at Wilsonville.
- The status of the Participants Program is reported.
- Petroleum inspection tests were conducted on the net product of Wilsonville Run 260D by Conoco as part of the Participants Program. Conoco's report and Consol's comments are provided.
- A detailed description of the microdistillation procedure used for work under this contract is reported.
- Appendices include an extended abstract of a paper presented at the 1991 Summer National AIChE Meeting in Pittsburgh, Pennsylvania, and a preprint of a paper presented at the 202nd National Meeting of the American Chemical Society and Fourth Chemical Congress of North America, authored by and describing work done at the University of Kentucky/Center for Applied Energy Research under the Participants Program.

/ls

Section 1

INTRODUCTION

This is the Technical Progress Report for the eighth quarter of activities under DOE Contract No. DE-AC22-89PC89883. It covers the period July 1, 1991, through September 30, 1991.

OVERVIEW

Direct coal liquefaction is a complicated chemical process. Recent advances in the technology, which significantly reduced the product costs, have come about through an improved fundamental understanding of liquefaction chemistry. Further improvements are possible, and will depend on continued advances in our knowledge of process chemistry. Supplying this knowledge requires the use of a variety of the tools of analytical chemistry applied to the appropriate samples, and interpretation of the analytical data in context to process development.

The R&D Department of Consolidation Coal Company (Consol R&D) is conducting a three-year project to characterize process and product streams from direct coal liquefaction process development programs sponsored by the Department of Energy. In this project, Consol R&D will obtain samples from current process development activities in coal liquefaction and coal-oil coprocessing, and characterize them using established analytical techniques. In addition, selected samples will be characterized by other analytical techniques to evaluate their potential for aiding process development. These analyses and interpretation of the results in relation to process operations will be provided by a subcontracted project team.

In addition to samples from current process development programs, Consol R&D maintains a bank of coal liquids samples from the SRC-I, H-Coal, ITSL (Lummus and Wilsonville) and HRI-CTSL coal liquefaction programs, and the Lummus, HRI and UOP coprocessing development programs. These samples,

which represent important stages in the recent development of coal liquefaction technology, also will be used in the analytical program.

CONTRACT OBJECTIVES

Consol R&D is conducting a three-year program to characterize process and product streams from direct coal liquefaction process development projects. The program objectives are two-fold: 1) to obtain and provide appropriate samples of coal liquids for the evaluation of analytical methodology, and 2) to support ongoing DOE-sponsored coal liquefaction process development efforts. The two broad objectives have considerable overlap and together serve to provide a bridge between process development and analytical chemistry.

More specifically, the first objective is to identify, collect and disburse appropriate samples of coal liquids for analysis by techniques that hold promise, but are not fully demonstrated, for use in liquefaction process development efforts. Samples will be chosen from ongoing DOE-funded liquefaction and coprocessing projects and from Consol's collection of coal liquids produced during the past ten years. Samples will be chosen based on their relevance to process development programs, and will be well-documented in terms of feedstocks, sampling location, time and operating conditions. The samples chosen will be sufficient to judge the applicability of the analytical methods being evaluated. These process oils will be analyzed by Consol R&D in a base characterization program using techniques established in previous Consol research. Selected samples also will be provided to project team participants (as subcontractors), other researchers active in the analysis of coal liquids, who will characterize them using a range of methods beyond those used in the base program. Subcontracts to approximately 10 to 15 organizations that have specialized analytical capabilities will be a major aspect of this work. Individual analytical specialists from the subcontractors will take a major role in interpreting their own results in context to the liquefaction process, and not merely provide data. This portion of the program will evaluate the utility of promising analytical techniques for providing useful information for coal

liquefaction process development, and will apply those results to ongoing development efforts. This evaluation will be based on the usefulness of an analytical method in process monitoring, to obtain specific chemical information, and as judged by precision and accuracy.

The second objective is to support the process developers. This will include support in the form of providing results and interpretation of data obtained with the analytical techniques being assessed. However, more directly, appropriate process oils will be characterized in the base program by a variety of standard techniques that have proven relevance to development efforts. The results from these more routine analyses will aid plant operations and planning. Also, these results will provide the data needed to select appropriate samples for the non-routine techniques and provide a set of data for correlations with the results of the more exploratory techniques.

CONTRACT ACTIVITIES - THIS PERIOD

Contract activities for this quarter are listed below. The first three topics are summarized and discussed in detail under a separate heading in Section 2, Discussion. The fourth topic is fully detailed in Section 3, Experimental.

- Two autoclave catalytic hydrogenation tests were conducted to examine the behavior of Dowtherm A components (biphenyl and diphenyl ether) at reaction conditions simulating those used at Wilsonville. Dowtherm A is a heat transfer medium that on occasion contaminates various oil streams at Wilsonville.
- Progress continues to be made in the Participants Program. Phase I subcontracts are either complete or nearing completion. Preparation for Phase II was begun. A summary of activities is presented in this report.
- Also under the Participants Program, the crude oil inspection tests on the Wilsonville Run 260D net product, the second of two samples

Conoco Petroleum Products Research Division was to analyze, was completed. This completes Conoco's work under the Participants Program. Conoco's final report on this work and Consol's comments concerning the results are included here.

- At the request of Sandia National Laboratory, the procedures used by Consol for microdistillation were detailed and supplied to Sandia. Those procedures appear in the Experimental Section of this report.
- Material Safety Data Sheets (MSDSs) were created with the assistance of Du Pont Industrial Hygiene for three classes of samples which we routinely send to outside laboratories, such as those collaborating in the Participants Program. These classes of materials are the whole distillation resid, the THF-soluble distillation resid, and the THF-insoluble distillation resid of coal liquefaction oils. Copies were supplied to R. Lett of PETC, at his request.
- A paper entitled "Stable Carbon Isotope Analysis of Coprocessing Materials" by M. S. Lancet, R. A. Winschel and F. P. Burke was presented at the 1991 Summer National Meeting of the American Institute of Chemical Engineers (AIChE) in Pittsburgh in August 1991. The AIChE publishes extended abstracts, not full papers. The extended abstract appears in this report as Appendix 2.
- A paper was presented at the U.S. DOE-PETC Liquefaction Review Meeting (September 3-5, 1991) by S. D. Brandes. The title of the presentation was "The Application of Advanced Analytical Techniques to Direct Coal Liquefaction Oils". This paper was also given at the 202nd National Meeting of the American Chemical Society and Fourth Chemical Congress of North America in New York in August 1991. It can be found appended to the Quarterly Technical Progress Report for the period April 1 through June 30, 1991, of this contract.

- Work in progress, but not completed this quarter, includes: analyses of oils from Wilsonville Runs 261 and 262, preheater simulation tests, O-methylation experiments, a literature survey of analytical methods for coal liquids, reactivity tests of Black Thunder coal from Wilsonville Run 262, and characterization and caustic washing of the Wilsonville syncrude fractions.
- Work performed by one of our collaborators in the Participants Program, the University of Kentucky/Center for Applied Energy Research, was presented at the 202nd National Meeting of the American Chemical Society and the Fourth Chemical Congress of North America in New York in August 1991. The preprint "Application of Fluorescence Microscopy to Coal-Derived Resid Characterization" by R. F. Rathbone, J. C. Hower and F. J. Derbyshire appears in Appendix 3.

Section 2

DISCUSSION

HYDROGENATION TESTS WITH SIMULATED DOWTHERM A

On occasion, leaks in the heat transfer system at Wilsonville introduce the heat transfer medium Dowtherm A as a contaminant into the oil stream. Depending on the source of the contaminant, Dowtherm A contamination can spread throughout most oil streams of the plant, because it can enter the recycle streams. Dowtherm A is a mixture of 73 wt % diphenyl ether and 27 wt % biphenyl.¹

Biphenyl is a common coal-derived component of liquefaction products. Diphenyl ether is much less common (and probably absent) in uncontaminated Wilsonville coal liquefaction oils, thus its presence serves as an indicator of Dowtherm A contamination. The Dowtherm A components eventually exit the plant as net products, either in their native state or as their hydrotreated or hydrocracked products. The purge of the contaminants is not instantaneous, because a portion of the contaminants can be recycled via the V-1067 (hydrotreater flashed bottoms) stream, as apparently occurred during Wilsonville Run 260D.²

Two hydrogenation tests were performed to investigate the behavior of Dowtherm A components at reaction conditions approximating those used at Wilsonville. The first test was performed with a mixture of biphenyl and diphenyl ether that simulated Dowtherm A. The second was performed with the distillate portion of a Wilsonville recycle oil from Run 260D that contained apparent Dowtherm A contamination. Work reported earlier showed that this distillate contained 6.0 wt % of biphenyl plus diphenyl ether² in the same ratio as in Dowtherm A.¹ The feeds and products of these hydrogenation tests were analyzed by gas chromatography/mass spectrometry (GC/MS).

PROCEDURE

The reactants used were: Test No. 1) a 73/27 weight ratio of diphenyl ether/biphenyl (simulated Dowtherm A), and Test No. 2) the 850°F distillate of the V-131B oil produced on October 9, 1990, during Wilsonville Run 260D. The Wilsonville oil apparently was contaminated with Dowtherm A during its manufacture at Wilsonville.² No biphenyl or diphenyl ether was added by us. The diphenyl ether was obtained from Fisher Scientific and the biphenyl was obtained from Aldrich Chemical Co. Reactions were conducted in the 45 mL microautoclave as follows. Five grams of reactant and 2g of catalyst (HRI No. LO-4860, Shell 317 Ni/Mo/Al catalyst withdrawn after presulfiding with oil from the first reactor from CTSI Run 227-49, ground to pass a 100 mesh sieve) were loaded into the reactor, which was then pressurized with H₂ to 1500 psig at room temperature (ca. 0.3 g of H₂). The vessel was leak-tested for 5 min. The reactor was heated at 800°F for 60 min (56 min in Test No. 1) including a 2 min heat up in the fluidized sand bath, cooled with dry ice, and vented while cold. The total vent gas loss was ≤0.3 g in each case. The reactor contents were mixed and sampled for GC/MS analysis.

GC/MS analyses were performed on the feeds and products from the two autoclave reactions described above with a HP 5970 system equipped with a 30 m x 0.25 mm DB-5 column (0.25 μm film thickness). The GC conditions were: injection point 300°C; column 5 min @ 35°C, ramped to 100°C @ 35°C/min, then ramped to 320°C @40°C/min; 20 psig of He carrier gas; scan range 33 to 340 amu (samples from Test No. 1) or 45 to 340 amu (samples from Test No. 2). Samples were injected in the splitless mode in dilute tetrahydrofuran solution (ca. 0.005 wt % for Test No. 1 samples, ca. 1 wt % for Test No. 2 samples). Mass spectra were searched against the Wiley/NBS library of mass spectra.

The GC injection solvent, THF, and its impurities interfere with detection of very low-boiling components. Therefore, the hydrogenation product of the simulated Dowtherm A also was analyzed, without dilution, to identify low-boiling and low-concentration products.

RESULTS

Test No. 1. Simulated Dowtherm A

Figure 1 shows the GC/MS total ion chromatograms of the original biphenyl/diphenyl ether mixture (simulated Dowtherm A) and its hydrogenation product. In the chromatogram of the simulated Dowtherm A mixture, the biphenyl peak has 45% of the area of the diphenyl ether peak. The actual concentration by weight of biphenyl is 37% of that of diphenyl ether; i.e., a 27/73 weight ratio. In the chromatogram of the hydrogenation product, the biphenyl peak has an area 4.4 times as large as that of the diphenyl ether peak. This indicates strong selective conversion of diphenyl ether. However, the reduced intensity of the chromatogram of the reaction products also suggests conversion of biphenyl. A neat injection of the reaction product (not shown) showed the major products to be benzene, cyclohexylbenzene, phenol and bicyclohexyl and the minor products to include cyclohexane, toluene, ethylcyclohexane, ethylbenzene, xylene, propylcyclohexane, propylbenzene, butylcyclohexane, indan, cresol, butylbenzene, pentylbenzene, decalin, methyldecalin, hexylbenzene, methyltetralin, methylphenoxybenzene, methylbiphenyl isomers and phenylbicyclohexyl. It is possible that some of the minor "products" or their precursors were introduced with the catalyst, because the catalyst sample used here was presulfided in oil by HRI. The peak eluting at 26 min in Figure 1 is unidentified, but is apparently is not a component of the sample; it appears regardless of which sample is injected. On the basis of absolute peak heights in Figure 1, it appears that both biphenyl and diphenyl ether underwent substantial conversion to products. However, it is clear that diphenyl ether was converted to a substantially greater extent.

Test No. 2 - Wilsonville Run 260D Distillate

Figure 2 shows the total ion chromatograms of the Wilsonville Run 260D V-131B distillate and its hydrogenation product. In the chromatogram of the original sample, the biphenyl peak has 51% of the area of the diphenyl ether peak. This sample was shown earlier to contain biphenyl

and diphenyl ether in the weight ratio of 27/73.² The chromatogram of the hydrogenation product shows that both components are reduced in concentration relative to the main envelope of components and also that diphenyl ether is reduced to a greater extent. In the chromatogram of the product, the biphenyl peak has 3.4 times the area of the diphenyl ether peak. It is evident from Figure 2 that some of the non-Dowtherm A components of the Wilsonville oil were also hydrogenated/hydrocracked.

The conversions of the Dowtherm A components in this experiment were estimated by comparing the ratios of their peak areas to the combined peak areas of the C₂₈, C₂₉, C₃₀ and C₃₁ n-paraffin peaks in the feed and product. This approach assumes that those four n-paraffins retained the same concentration after the hydrogenation as they had before it. By this means, conversions are calculated to be 79% for biphenyl and 97% for diphenyl ether.

Conclusions

These tests show that both components of Dowtherm A, biphenyl and diphenyl ether, are readily hydrogenated/hydrocracked at reaction conditions approximating those used at Wilsonville. Diphenyl ether is substantially the more reactive of the two components. Thus, the Dowtherm A components can be purged from the Wilsonville internal oil stream either in their native state or as their hydrogenation/hydrocracking products.

PARTICIPANTS PROGRAM STATUS

SUMMARY

The following items concerning the Participants Program were accomplished this quarter.

Phase I

- Draft final reports were received from Western Research Institute and The Pennsylvania State University.
- Four additional Phase I subcontracts are drawing to a close.
- The University of Kentucky/Center for Applied Energy Research final report was given patent and technical approval by DOE.
- The Task Order Agreement between DOE and Battelle Pacific Northwest Laboratories was completed. The work will proceed as outlined in the Statement of Work prepared under Phase I of the Participants Program.
- Conoco Petroleum Products Division complete their program.

Phase II

- Proposals were received from fifteen research organizations.
- Site visits were made to four potential participants

DISCUSSION

Phase 1

Western Research Institute completed analyses on the final two samples which were sent to them last quarter. A revised final report was

received from them. This report was reviewed and revised with the author. A finished document is expected early next quarter. A request from The Pennsylvania State University (PSU) was granted for a two-month, no-cost time extension. A draft final report was subsequently received from PSU. It is being reviewed.

SRI International submitted a status report and a set of FIMS spectra. They requested additional processing information in order to aid them in interpreting the FIMS spectra. They have completed all derivatization work, and are working on their final report. Two status reports were received from Advanced Fuel Research. Contact was made with Virginia Polytechnic Institute. It was agreed that they would begin assembling the information they had on hand and would pull together a final report, although it will most likely include negative findings. National Institute for Petroleum and Energy Research reports that they had difficulty in eluting the strong acid fraction from their chromatography columns. They have successfully used an alternative experimental method in order to meet their contract obligations. They are currently writing their final report.

The University of Kentucky/Center for Applied Energy Research final report, with a Consol assessment, was given patent and technical approval by DOE for issue as a Topical Report. The report was sent for printing.

Samples were shipped to Jim Campbell at Battelle Pacific Northwest Laboratories for their effort in Phase I of the Participants Program. They will be working under a Task Order Agreement directly with U.S. DOE, utilizing the Statement of Work which we drafted. All reporting and communications will be directly between Consol and Battelle; DOE will not act as intermediary. Sample data sheets and processing information packages were sent to Battelle for the sample set.

Conoco Petroleum Products Research Division completed their portion of the Participants Program upon completion of the second set of petroleum inspection tests, this set on Wilsonville Run 260D net products. The

final report of this second set of tests is appended to this quarterly technical report. Consol's comments concerning those results appear in the next section of the body of this report.

Phase II

We received Phase II proposals from Leon Stock (University of Chicago), Kent Voorhees (Colorado School of Mines), Jerry Huffman (University of Kentucky), Ronald Pugmire (University of Utah), William McClennen (University of Utah), Dady Dadyburjor (West Virginia University), and David Wertz (University of Southern Mississippi). Four proposals were received from Iowa State University. They are authored by John Verkade, John McClelland, Robert Jacobson, and Robert Cozemius. Charles Eckert (Georgia Institute of Technology) was invited to submit a proposal for Phase II. Inclusive of the four proposal received last quarter, fifteen proposals for Phase II of the program have been received.

We visited Dr. Sanford Asher at the University of Pittsburgh to discuss with him his proposal for work in Phase II. Site visits also were made to Lehigh University (Dr. John Larsen), Massachusetts Institute of Technology (Dr. John Vander Sande), and University of Chicago (Dr. Leon Stock) to discuss proposals for Phase II. A rough outline for a statement of work was agreed upon at each site. Trip reports were written and sent for review.

APPLICATION OF STANDARD PETROLEUM REFINERY TESTS TO COAL LIQUEFACTION PRODUCTS - CONOCO'S CRUDE OIL INSPECTION TESTS WITH WILSONVILLE RUN 260D NET PRODUCT

BACKGROUND

Regardless of the specific technology used to produce transportation fuels from coal, the net product of the liquefaction process will have to undergo additional refining to make finished products. Consequently, there is a need to characterize the material leaving the liquefaction plant as net product and going to the refinery as feed.

The processor of coal liquefaction products needs to know the refining requirements of the raw liquid products which he is producing. A correlation drawn between operating variables of the finishing process and net product characteristics (in regard to specification requirements) will be extremely useful. In addition, this knowledge will provide more accurate estimations of upgrading costs to specification fuels. Standard petroleum tests, as they now are formulated, may not be directly applicable to the analysis of coal liquids. It is possible that test methods will need to be revised for use with coal liquids. Standard petroleum analyses should form the basis for the design of these tests. Although it is acknowledged that the standard petroleum feedstock tests are not tailored for the analysis of coal liquids, it is believed that they are at least a starting point for this analysis. It was recommended in the Analytical Needs Assessment³ that standard petroleum tests be performed on coal liquefaction syncrudes to assess the applicability of those tests. Therefore, in a directed attempt to meet this particular analytical need, standard petroleum refinery feed analyses are being performed on products of the Wilsonville plant.

As part of the Participants Program, Conoco Petroleum Products Research Division is performing crude oil assays on two synthetic crude oils produced by coal liquefaction. This program, including sample selection and test plan, was devised by Consol in conjunction with Dr. E. B. Klunder, Mr. R. Hickey and Mr. S. Lee of the Pittsburgh Energy Technology Center, U.S. Department of Energy, and Dr. P. Zhou and Dr. R. Rao of

Burns and Roe Services Corp. (BRSC) and Mr. R. L. Kramer of Conoco Inc. The samples selected for analysis were the net products of Wilsonville Runs 259G (Ireland Mine coal) and 260D (Black Thunder Mine coal). Conoco's final report on the Run 259G product and Consol's discussion of those results were issued earlier.⁴ A more in-depth discussion of those results also was issued,² as were results of additional analyses on the fractions.⁵ Conoco completed the tests with the Run 260D net product this quarter; the final report appears as Appendix 1 of this report. A discussion of Consol's analyses of other samples from Wilsonville Run 260D, which includes a general background of the run and a discussion of Dowtherm A contamination in Run 260D oils, appears elsewhere.²

DISCUSSION

A sample (approximately 5 gal) of the Wilsonville Run 260D syncrude was shipped directly by Southern Electric International to Conoco in a 5 gal plastic bucket.

The following summarizes Conoco's final report on the Run 260D sample, which appears in Appendix 1. Conoco performed specified tests (a modified light oil assay) on the crude and on four distillation fractions: the naphtha fraction (initial boiling point $\times$ 380°F), the jet fuel or kerosene fraction (380 $\times$ 510°F), the diesel fuel fraction (510 $\times$ 650°F) and the resid fraction (650°F+). The first distillation of 9L yielded insufficient jet fuel fraction (ca. 1.6L) to perform the specified tests. Most of the rest of the syncrude (6 or 7L) was then distilled to obtain additional quantities of the fractions. The products from the two distillations were blended prior to testing. Each distillation fraction represented 18 to 32 vol % of the syncrude. The syncrude was determined to be an aromatic, low-sulfur crude oil that is essentially free of metals, but contains high levels of nitrogen and olefins. The naphtha fraction has a high basic nitrogen content and a low API gravity relative to conventional naphthas. Relative to ASTM D-439 gasoline specifications, it has a high existent gum content, it is lacking light ends, and it failed the oxidation stability test. The jet fuel fraction would be a difficult refinery feedstock for jet fuel production because

of its high specific gravity, existent gum content, viscosity, mercaptan sulfur content, acidity, aromaticity, bromine number, olefins content, basic nitrogen content, its low smoke point and heat of combustion, and its poor color. It also appears to lack sufficient volatility. The diesel fuel fraction has a high bromine number, high viscosity and low API gravity.

In general, the product from Run 260D was of poorer quality than the product from Run 259G. The Run 260D product contained much more high-boiling material. The individual fractions had higher concentrations of nitrogen, basic nitrogen, oxygen (by difference) and phenolic oxygen. Indications are that the Run 260D product fractions are less stable. Those differences must arise from differences in the feed coal and operating conditions. Relevant differences (vs Run 259G) include the use of a high-oxygen subbituminous coal (vs bituminous), catalytic/thermal (vs catalytic/catalytic) operating mode and higher space velocity.

Conoco encountered several problems in applying the standard petroleum tests to the syncrude. First, the syncrude and its fractions had an odor reminiscent of coker products, as reported by Conoco personnel. It is possible that Dowtherm A contamination (suspected by Consol²) was one contributing element of the odor; however, since Dowtherm A has an odor very unlike coker products, it is likely that the odor is an inherent feature of the oils. The odor of the returned fractions was not particularly strong or unpleasant in the judgment of the present authors (Consol). Because of the reportedly intense odor, Conoco substituted simulated distillations for the planned ASTM D-86 true boiling point distillations on the fractions. Second, the crude and its fractions were so highly colored that certain specified tests could not be completed. These tests included: refractive index and aniline point (crude), freezing point (jet fuel fraction) and cloud point (diesel fuel fraction).

All remaining portions of the syncrude and its distillation fractions were returned to Consol for additional analyses and planned caustic

washing tests at Consol (to be reported later). This completes all currently planned work by Conoco under the Participants Program.

Section 3

EXPERIMENTAL

Experimental details are described, where appropriate, in the Discussion section of this report. Details of the other analytical techniques used in this work were reported previously.^{6,7} The micro-distillation procedures used for work under this contract appear below.

MICRO-DISTILLATION PROCEDURE

EQUIPMENT

The micro-distillation apparatus (Figure 3) consists of a six-inch Pyrex column (1/2" OD, 1/16" wall) with a side arm (3/8" OD, 1/16" wall) attached 3 1/2" from the bottom of the column. The top of the column is manufactured with a female 10/30 standard taper (ST) joint into which a glass thermocouple (T/C) well is inserted. The T/C well, which is fitted with a male 10/30 ST joint, extends to just below the point of attachment of the side arm. The bottom of the column is made with an 18/9 socket joint. The side arm is bent 60° to horizontal at 1 1/2" from the attachment to the column, and extends four inches, ending in a male 10/30 ST joint. A 50 mL long-neck receiver vessel with a female 10/30 ST joint and a glass hose connection is fitted to the side arm. A vacuum hose is attached to the glass hose connection. The column and side arm are wrapped with a resistance heater that is controlled by a variable transformer. A 50 mL or 100 mL round-bottom flask with a female 18/9 socket joint, and a side neck with a female 19/22 ST joint, is used to hold the sample. A second thermocouple well, fitted with a male 19/22 ST joint, is inserted at the side arm on the flask and extends nearly to the inside wall of the flask. The flask is heated with a spherical mantle that is controlled by a second variable transformer. A cold trap, cooled with a dry ice/acetone bath, is placed in the vacuum line to collect volatiles that do not condense in the receiver vessel.

PROCEDURE

The distillation procedure varies with sample properties and desired cut point. For samples that contain no solvent (such as tetrahydrofuran (THF)), the pot and column are gradually heated independently with a concomitant gradual reduction in pressure to a final condition of, for example, 608°F pot/ 518°F column/5 torr or 745°F pot/745°F column/1 torr. The still pot, column, receiver vessel and cold trap (including the attached thermal wells) are tared and weighed at appropriate points in the procedure in order to determine distillate yield and mass balance. A boiling chip may be added to the pot for those samples that are prone to "bumping".

Some samples, such as those that are products of microautoclave coal liquefaction tests, are charged to the round bottom flask in a THF solution. First, the majority of the THF is removed by rotovaporization at reduced pressure while the sample is contained in the distillation pot. Distillation of the remaining THF is accomplished under vacuum at 325°F pot/325°F column/5 torr or 300°F pot/300°F column/2 torr, depending on the presence of light oils. The sample then is tested for residual THF by proton nuclear magnetic resonance spectroscopy. If the sample is THF-free, the receiver vessel and cold trap are replaced, the sample is distilled, and the distillate product is collected at the desired conditions.

Section 4

REFERENCES

1. The Dow Chemical Co., Material Safety Data Sheet No. 000412, 6/18/90.
2. Robbins, G. A.; Brandes, S. D.; Winschel, R. A.; Burke, F. P. "Coal Liquefaction Process Streams Characterization and Evaluation, Quarterly Technical Progress Report, April 1 through June 30, 1991", DOE/PC 89883-29, October 1991.
3. Brandes, S. D.; Robbins, G. A.; Winschel, R. A.; Burke, F. P. "Coal Liquefaction Process Streams Characterization and Evaluation, Analytical Needs Assessment Topical Report", DOE/PC 89883-18, March 1991.
4. Brandes, S. D.; Winschel, R. A.; Robbins, G. A.; Burke, F. P., "Coal Liquefaction Process Streams Characterization and Evaluation, Quarterly Technical Progress Report, October 1 through December 31, 1990", DOE/PC 89883-24, June 1991.
5. Brandes, S. D.; Winschel, R. A.; Robbins, G. A.; Burke, F. P., "Coal Liquefaction Process Streams Characterization and Evaluation, Quarterly Technical Progress Report, January 1 through March 31, 1991", DOE/PC 89883-27, September 1991.
6. Burke, F. P.; Winschel, R. A.; Robbins, G. A. "Recycle Slurry Oil Characterization - Final Report", DOE/PC 30027-61, March 1985.
7. Winschel, R. A.; Robbins, G. A.; Burke, F. P. "Coal Liquefaction Process Solvent Characterization and Evaluation, Quarterly Technical Progress Report, July 1 through September 30, 1985", DOE/PC 70018-13, December 1985.

Figure 1. GC/MS Total Ion Chromatogram of Simulated Dowtherm A and Its Hydrogenation Product. See text for additional major peaks eluting before 10 min and minor peaks.

Figure 2. GC/MS Total Ion Chromatogram of Wilsonville Run 260D V-131B Distillate and Hydrogenation Product.
Cx alkane refers to n-paraffin of x carbon atoms.

6/10/9

Figure 3. Micro-Distillation Apparatus.

APPENDIX 1

MODIFIED CRUDE OIL ASSAY OF WILSONVILLE RUN 260D NET PRODUCTS

Performed by:

CONOCO PETROLEUM PRODUCTS RESEARCH DIVISION

**Under the Participants Program of
DOE Contract No. DE-AC22-89PC89883**

Research Report

Conoco Inc.
Research and Engineering Department
Petroleum Products Division
Ponca City, Oklahoma

No. 6210-0003-T000-1-91
To: R. A Winschel, Library
From: R. L. Kramer, Ponca City
Date: August 20, 1991
Subject: **MODIFIED LIGHT OIL, SOUTHERN CLEAN FUELS INC.-COAL LIQUEFACTION MATERIAL, SAMPLE NUMBER C90116**

Introduction

A modified light oil analysis was conducted on the Southern Clean Fuels Inc.-Coal Liquefaction sample. The sample was net product from Wilsonville Run 260D. It was produced from Black Thunder mine coal. The original sample number was 16436.

A D2892 distillation was conducted on the crude. The distillation separated the sample into four cuts: 1) Naphtha cut (IBP-380°F), 2) Jet Fuel cut (380-510°F), 3) Diesel Fuel Cut (510-650°F) and Resid (650+°F). Specified tests were conducted on the whole sample and each of the cuts. None of the samples were clay treated and no additives were added to the samples. There were safety problems concerning the noxious odor of the materials. For this reason some of the tests were not run as initially specified. To provide distillation data on the individual cuts, a gas chromatography method was used instead of a D86 distillation. Data from the tests were used to determine the suitability of the material for refinery processes. A review of the data is discussed below.

Conclusions

WHOLE CRUDE - SOUTHERN CLEAN FUELS COAL LIQUEFACTION SAMPLE is a low sulfur crude. The API gravity is 23.9°; the total sulfur is 0.05 weight percent; the vanadium and nickel contents are <1 and <0.5 ppm, respectively. Based on the analysis of the crude and the individual cuts, the nitrogen and olefins content are high which results in poor storage stability. In addition, nitrogen compounds are detrimental to the activity of catalysts in the refinery process. The coal liquefaction sample is also highly aromatic. Properties of the whole crude are reported in Table 1 and Figure 1.

STRAIGHT-RUN FRACTIONS - Yields and properties obtained by a true boiling point distillation are reported in Table 2.

Naphtha Fraction:

The Naphtha fraction distilling between IBP-380°F comprises 27.76 volume percent of the whole crude. It has an API gravity of 50.9. This is significantly lower than a more typical value of 65. The naphtha fraction has a high existent gum content (40.2 mg/100 ml washed). In addition, the higher than normal basic nitrogen content (460 ppm) could

create color stability problems. The aromatics content (7 wt. %) and octane number (87.1 by an in-house GC method) are acceptable.

Jet Fuel Fraction:

The Jet Fuel fraction distilling between 380-510°F comprises 18.63 volume percent of the whole crude. To assist in evaluating the quality of the Jet Fuel cut, a copy of the ASTM D1655 specifications for Aviation Turbine Fuels (Jet A) is attached. The Jet Fuel cut has a specific gravity of 0.9260. This is above the maximum specific gravity of 0.8400. As was the case for the naphtha fraction, the existent gum content of 90.8 mg/100ml is too high. Specifications state a maximum existent gum content of 7 mg/100ml. The high aromatics content and low smoke point are also unacceptable. In addition, the net heat of combustion of 42.0 MJ/kg is slightly below the 42.8 MJ/kg minimum.

The Jet Fuel cut would also fail due to color requirements. Jet Fuel cuts should be water white in color. The cut contains a significant quantity of olefins (3 volume percent) which has a detrimental effect on thermal stability. This is also supported by the high bromine numbers.

Olefins also create gum formation problems. From a jet fuel perspective, the coal liquefaction sample would make a very poor feed stock.

Diesel Fraction:

The Diesel cut (510-650°F) comprises 21.97 volume percent of the crude. A copy of ASTM D975 Diesel Fuel Oil Requirements has been attached to assist in the evaluation of the quality of this fraction.

The API gravity of the diesel cut (17.7°) is significantly lower than the No. 2 Diesel Fuel minimum of 30. The high olefins content, as indicated by a high bromine number (17) would most likely result in stability problems.

Resid Fraction:

The resid fraction (650+) comprises 31.83 volume percent of the crude. The API gravity for this cut was 11.9. The metals content was low for this material.

Research Report 6210-0003-T001-1-91
August 20, 1991
Page 3

Robert L. Kramer

Robert L. Kramer
Senior Engineer
Petroleum Technology and
Division Services Section
Petroleum Products R&D Division

A:RLK.105/smt

cc: FES:RAK:JAW:WWW:MHDB
DDO:WGG:LIBRARY:ASSAY FILE

TABLE 1 - CRUDE PROPERTIES

Southern Clean Fuels Inc.-Coal Liquefaction Sample, C90116

Gravity, °API 60/60°F.....	23.9
Gravity, Specific, 60/60 °F.....	0.9103
Viscosity, Kinematic, cSt	
at 60°F	5.70
at 80 °F	4.10
at 100 °F	3.10
U.O.P. Characterization Factor (a).....	10.89
Sulfur, Total, Wt.%	0.05
Carbon, Wt.%	87.4
Hydrogen, Wt.%	11.2
Nitrogen, Wt.%	0.3
Basic Nitrogen, Wt.%	0.182
Refractive Index	Too Dark
Bromine Number, g/100g	14
Carbon Residue, Conradson, Wt.%	0
Heptane Insolubles, Wt%	0.5
Ash, Wt.%	0.01
Pour Point, °F	-15
Aniline Point, °F	Too Dark
Acidity.....	0.38
Metallic Elements, ppm	
Vanadium	<1
Nickel	<0.5
Iron	23
Copper	<0.5

True Boiling Point 2892 Still Distillation

Simulated TBP Distillation by GLC

Volume % Recovery	Distillation Temp., °F
1.0	132
5.0	173
10.0	208
15.0	261
20.0	294
25.0	358
30.0	443
35.0	472
40.0	498
46.4	510
50.0	548
55.0	588
60.0	613
65.0	635
68.4	650

Volume % Recovery	Distillation Temp., °F
1	97
5	177
10	207
15	259
20	291
25	349
30	417
35	456
40	471
45	493
50	518
55	538
60	562
65	583
70	606
75	630
80	650
85	669
90	689
95	714
98	737

(a) Watson, Nelson, & Murphy Ind., Eng. Chem. Chem. 27, 1460 (1935)

TABLE 2

Yields and Properties of Straight-Run Fractions

Southern Clean Fuels Inc.-Coal Liquefaction Sample, C90116

FRACTION RANGE, °F	NAPHTHA CUT IBP-380	JET FUEL CUT 380-510	DIESEL CUT 510-650	RESID 650+
YIELD, VOLUME %	27.76	18.63	21.97	31.83
CUMULATIVE, VOLUME %	27.76	46.39	68.36	100.19
WEIGHT PERCENT	23.65	18.95	22.89	34.51
CUMULATIVE, WEIGHT %	23.65	42.60	65.49	100.00
PROPERTIES:				
GRAVITY, API	50.9	21.3	17.7	11.9
GRAVITY, SPECIFIC, 60/60°F	0.7758	0.9260	0.9484	0.9868
CARBON RESIDUE, CONRADSON, WT. %	-	-	-	0.23
SULFUR, TOTAL, WEIGHT %	0.08	0.04	0.03	0.03
MERCAPTAIN SULFUR, WEIGHT %	-	0.0085	-	-
CARBON, WEIGHT %	84.3	85.8	87.0	88.4
HYDROGEN, WEIGHT %	13.6	10.6	10.7	10.13
NITROGEN, WEIGHT %	0.1	0.3	0.3	0.4
BASIC NITROGEN, WEIGHT %	0.046	0.219	0.219	-
REFRACTIVE INDEX	1.4141	1.4852	1.5031	-
BROMINE NUMBER, g/100g	16	25	17	-
VISCOSITY, cST AT 60°F	-	-	14.0	-
VISCOSITY, cST AT 80°F	-	-	9.1	-
VISCOSITY, cST AT 100°F	-	-	6.2	-
VISCOSITY, cST AT 130°F	-	-	-	15.3
VISCOSITY, cST AT 210°F	-	-	-	4.1
VISCOSITY, cST AT 250°F	-	-	-	2.6
VISCOSITY, cST AT -20°C	-	18.94	-	-
ANILINE POINT, °F	-	63	-	-
FREEZE POINT, °C	-	Too Dark	-	-
CLOUD POINT, °F	-	-	Too Dark	-
SMOKE POINT, mm	-	9.8	-	-
VANADIUM, ppm	-	-	<1	<0.5
NICKEL, ppm	-	-	<0.5	<0.5
IRON, ppm	-	-	1	58
COPPER, ppm	-	-	<0.5	<0.5
ASH, WEIGHT %	-	-	0.00	0.02
PARAFFINS & NAPHTHENES, VOLUME %	88.0	47.0	-	-
AROMATICS, VOLUME %	7.0	50.0	-	-
OLEFINS, VOLUME %	5.0	3.0	-	-
OCTANE NO. BY GC	87.1	-	-	-
REID VAPOR PRESSURE, psi	3.1	0.0	-	-
COPPER STRIP CORROSION	1A	1A	1A	-
EXISTENT GUM TEST (WASHED), mg/100	40.2	83.0*	-	-
EXISTENT GUM TEST (UNWASHED), mg/10	56.2	90.8	-	-
OXIDATION STABILITY				
(HELD 100 PSI FOR 5 HRS. @ 212°F)	FAIL	-	-	-
ACIDITY, mg KOH/g	0.38	0.50	0.14	-
HEAT OF COMBUSTION (CALC.), MJ/kg	-	42.0	-	-
FLASH POINT, °C	-	188	255**	-
CETANE INDEX NO. (CALC. ASTM D976)	-	-	27.7	-
NAPHTHALENES, VOLUME PERCENT	-	4.94	-	-

TABLE 2 (Con't)

Yields and Properties of Straight-Run Fractions

Southern Clean Fuels Inc.-Coal Liquefaction Sample, C90116

FRACTION RANGE, °F	NAPHTHA CUT IBP-380	JET FUEL CUT 380-510	DIESEL CUT 510-650	RESID 650+
SIMULATED TBP BY GC				
WEIGHT PERCENT RECOVERY	DEGREES F	DEGREES F	DEGREES F	DEGREES F
1	78	380	459	564
5	143	401	475	600
10	176	414	492	617
20	183	434	513	638
30	187	449	528	651
40	215	457	540	662
50	240	468	553	674
60	269	476	566	685
70	283	483	577	696
80	311	491	592	711
90	340	499	610	732
95	363	509	622	750
99	392	536	643	793
FINAL BOILING POINT	399	655	654	830

* Jet Fuel specifications do not stipulate this value. Existent gum is based on "unwashed" amount.

** The flash point for the diesel cut was measured using a Pensky-Martens closed tester. The flash point for the jet fuel cut was run on a tag closed tester.

FIGURE 1
TRUE BOILING POINT DISTILLATION CURVES
SOUTHERN CLEAN FUELS INC.
SAMPLE NUMBER C90116

TABLE 1 Detailed Requirements for Diesel Fuel Oils^a

Property	ASTM Test Method ^b	Grade No. 1-D	Grade No. 2-D	Grade No. 4-D
Flash Point, °C (°F), min	D 93	38 (100)	52 (125)	55 (130)
Water and Sediment, % vol, max	D 1796	0.05	0.05	0.50
Distillation temperature, °C (°F) 90 % vol. recovered	D 86			
min.			282 (540) ^c	...
max.		288 (550)	338 (640)	...
Kinematic viscosity, mm ² /s ^d at 40°C (104°F)	D 445			
min.		1.3	1.9 ^c	5.5
max.		2.4	4.1	24.0
Residuum carbon residue on 10% distillation residue, % mass, max	D 524	0.15	0.35	...
Ash, % mass, max	D 482	0.01	0.01	0.10
Sulfur, % mass, max ^e	D 129	0.50	0.50	2.00
Copper strip corrosion rating, max. 3 h at 50°C (122°F)	D 130	No. 3	No. 3	...
Cetane number, min. ^f	D 613	40 ^g	40 ^g	30 ^g
Cloud point, °C (°F), max.	D 2500	"	"	"

^a To meet special operating conditions, modifications of individual limiting requirements may be agreed upon between purchaser, seller and manufacturer.

^b The test methods indicated are the approved referee methods. Other acceptable methods are indicated in 4.1. The values stated in SI units are to be regarded as standard. Values in parentheses are for information only.

^c When a cloud point less than -12°C (10°F) is specified, the minimum viscosity shall be 1.7 mm²/s (31.5 SUS) and the minimum 90 % recovered temperature shall be waived.

^d 1 mm²/s = 1 cSt

^e Other sulfur limits may apply in selected areas in the United States and in other countries.

^f Where cetane number by Test Method D 613 is not available, Method D 4737 may be used as an approximation.

^g Low ambient temperatures as well as engine operation at high altitudes may require the use of fuels with higher cetane ratings.

^h It is unrealistic to specify low temperature properties that will ensure satisfactory operation at all ambient conditions. However, satisfactory operation should be achieved in most cases if the cloud point (or wax appearance point) is specified at 6°C or higher above the tenth percentile minimum ambient temperature for the area in which ambient temperatures for U.S. locations are shown in Appendix X2. This guidance is general. Some equipment designs or operation may allow higher or require lower cloud point fuels. Appropriate low temperature operability properties should be agreed upon between the fuel supplier and purchaser for the intended use and expected ambient temperatures.

TABLE 2 Approximate Equivalent Viscosity Values for Diesel Fuel Oils^a

Viscosity	ASTM Test Method	Grade No. 1-D	Grade No. 2-D	Grade No. 4-D
Kinematic viscosity, min. mm ² /s ^b at 40°C (104°F) ^c	D 445			
min		1.3	1.9	5.5
max		2.4	4.1	24.0
Saybolt Universal viscosity, SUS at 38°C (100°F)				
min		-	(32.6)	(45.0)
max		(34.4)	(40.1)	(125)

^a The specification standard viscosities are listed in Table 1. Equivalent viscosities in common use are shown in Table 2 for information only. The values in parentheses are approximate and are not limiting.

^b 1 mm²/s = 1 cSt

^c Viscosity values in parentheses are for information only, may be approximate, and are not necessarily limiting.

with the same limits, provided the flash point is below 79°C (175°F) and the viscosity is below 5.5 cSt (or mm²/s)¹⁰ at

¹⁰ One centistokes (1 cSt) equals one millimetre squared per second (1 mm²/s), therefore, the two units are interchangeable.

40°C (104°F). This test method will give slightly lower values. In cases of dispute, Test Methods D 93 shall be used as the referee method.

4.1.2 *Cloud Point*—Test Method D 2500. Test Method D 3117 may also be used since the two are closely related. In case of dispute, Test Method D 2500 shall be the referee method.

4.1.3 *Water and Sediment*—Test Method D 1796.

4.1.4 *Carbon Residue*—Test Method D 524.

4.1.5 *Ash*—Test Method D 482.

4.1.6 *Distillation of No. 1-D and No. 2-D Fuel Oils*—Method D 86.

4.1.7 *Viscosity*—Test Method D 445 or by conversion in accordance with Practice D 2161.

4.1.8 *Sulfur*—Test Method D 129. Test Methods D 1552, D 2622, and D 4294 can also be used for all grades. In addition, Test Method D 1266 can be used for Grade No. 1, but only with samples having sulfur contents of 0.4 mass percent and less (down to 0.01 %). In case of dispute, Test Method D 129 is the referee sulfur test method for this specification.

4.1.9 *Corrosion*—Test Method D 130, 3 h test at 50°C.

4.1.10 *Cetane Number*—Test Method D 613.

5. Keywords

5.1 petroleum and petroleum products; fuel oil; diesel; specification

TABLE 1 Detailed Requirements of Aviation Turbine Fuels ^a

Property	Jet A or Jet A-1	Jet B	ASTM Test Method ^b
Acidity, total max, mg KOH/g	0.1		D 974 or D 3242
Aromatics, max, vol %	20 ^c	20 ^c	D 1319
Sulfur, mercaptan, ^d max, weight %	0.003	0.003	D 3227
Sulfur, total max, weight %	0.3	0.3	D 1266 or D 1552 or D 2622
Distillation temperature, °C			
10 % recovered, max, temp	205		D 86
20 % recovered, max, temp		145	
50 % recovered, max, temp	report	190	
90 % recovered, max, temp	report	245	
Final boiling point, max, temp	300		
Distillation residue, max, %	1.5	1.5	
Distillation loss, max, %	1.5	1.5	
Flash point, min, °C	38		D 56 or D 3828 ^e
Density at 15°C, kg/m ³	775 to 840	751 to 802	D 1298 or D 4052
Vapor pressure, 38°C, max, kPa		21	D 323
Freezing point, max, °C	-40 Jet A ^f -47 Jet A-1 ^f	-50 ^f	D 2386
Viscosity -20°C, max, mm ² /s ^h	8.0		D 445
Net heat of combustion, min, MJ/kg	42.8 ^a	42.8 ^a	D 4529, D 2382, D 3338, or D 4809
Combustion properties: one of the following requirements shall be met:			
(1) Luminometer number, min, or	45	45	D 1740
(2) Smoke point, min, mm, or	25	25	D 1322
(3) Smoke point, min, mm, and	20 ^f	20 ^f	D 1322
Naphthalenes, max, vol, %	3	3	D 1840
Corrosion, copper strip, 2 h at 100°C, max	No. 1	No. 1	D 130
Thermal stability: one of the following requirements shall be met:			
(1) Filter pressure drop, max, mm Hg	76 ^l	76 ^l	D 1660 ^h
Preheater deposit less than	Code 3	Code 3	
(2) Filter pressure drop, max, mm Hg	25 ^m	25 ^m	D 3241 ⁱ
Tube deposit less than	Code 3	Code 3	
Existent gum, max, mg/100 mL	7	7	D 381
Water reaction:			
Separation rating, max	(2)	(2)	D 1094
Interface rating, max	1b	1b	D 1094
Additives	See 5.2	See 5.2	
Electrical conductivity, pS/m			D 2624 or D 4308

^a The requirements herein are absolute and are not subject to correction for tolerance of the test methods. If multiple determinations are made, average results shall be used.

^b The test methods indicated in this table are referred to in Section 9.

^c Fuels with an aromatic content over 20 volume % but not exceeding 25 volume % are permitted provided the supplier (seller) notifies the purchaser of the volume, distribution and aromatic content within 90 days of date of shipment unless other reporting conditions are agreed to by both parties.

^d The mercaptan sulfur determination may be waived if the fuel is considered sweet by the doctor test described in 4.2 of Specification D 235.

^e Other freezing points may be agreed upon between supplier and purchaser.

^f Fuels having a smoke point less than 20 but not less than 18 and a maximum of 3 volume % of naphthalenes are permitted provided the supplier (seller) notifies the purchaser of the volume, distribution and smoke point and naphthalenes content within 90 days of date of shipment unless other reporting conditions are agreed to by both parties.

^g For all grades use either Eq 1 or Table 1 in Test Method D 4529 or Eq 2 in Test Method D 3338. Test Methods D 2382 or D 4809 may be used as alternatives. In case of dispute, Test Method D 2382 shall be used.

^h Thermal Stability test shall be conducted for 5 h at 149°C preheater temperature, 204.5°C filter temperature and at a flow rate of 2.7 kg/h.

ⁱ Thermal stability test (JFTOT) shall be conducted for 2.5 h at a control temperature of 260°C, but if the requirements of Table 1 are not met, the test may be conducted at 245°C. Results at both temperatures shall be reported in this case. Tube deposits shall always be reported by the Visual Method: a rating by the Tube Deposit Rating (TDR) optical density method is desirable but not mandatory.

^j A limit of 50 to 450 conductivity units (pS/m) applies only when an electrical conductivity additive is used and under the condition at point of use.

$$1 \text{ pS/m} = 1 \times 10^{-12} \Omega^{-1} \text{ m}^{-1}$$

^k Results obtained by Test Method D 3828 may be up to 2°C lower than those obtained by Test Method D 56 which is the preferred method. In case of dispute, Test Method D 56 will apply.

^l Preferred SI units are 10 kPa, max.

^m Preferred SI units are 3.3 kPa, max.

ⁿ 1 mm²/s = 1 cSt.

dures in establishing fuel quality, use the appropriate procedures in Practice D 4057.

8.2 A number of jet fuel properties including thermal stability, water separation, electrical conductivity, and others are very sensitive to trace contamination which can originate from sample containers. For recommended sample containers refer to Practice D 4306.

9. Report

9.1 The type and number of reports to ensure conformance with the requirements of this specification shall be mutually agreed upon by the seller and the purchaser of the aviation turbine fuel.

9.2 A suggested form for reporting inspection data on aviation turbine fuels is given in Appendix X3.

*abstract removed; conf
paper cycled separately*

END

**DATE
FILMED**

3 / 26 / 92