1991

STUDIES IN COMPLEX TERRA

ANL/ER/TM-1
ASCOT-91-7

**ARGONNE NATIONAL LABORATORY OPERATIONS
DURING ASCOT 1991**

R. L. Coulter and T. J. Martin

**Argonne National Laboratory
Argonne, IL 60439**

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

Argonne National Laboratory

Argonne National Laboratory, with facilities in the states of Illinois and Idaho, is owned by the United States government, and operated by the University of Chicago under the provisions of a contract with the Department of Energy.

This technical report is a product of Argonne's Environmental Research Division. For information on the division's scientific and engineering activities, contact:

Director, Environmental Research Division
Argonne National Laboratory
Argonne, Illinois 60439-4843
Telephone (708) 252-3879

Disclaimer

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

Reproduced directly from the best available copy.

Available to DOE and DOE contractors from the Office of Scientific and Technical Information, P.O. Box 62, Oak Ridge, TN 37831; prices available from (615) 576-8401, FTS 626-8401.

Available to the public from the National Technical Information Service, U.S. Department of Commerce, 5285 Port Royal Road, Springfield, VA 22161.

**ARGONNE NATIONAL LABORATORY OPERATIONS
DURING ASCOT 1991**

ANL/ER-TM--1

DE92 007510

R. L. Coulter and T. J. Martin

**Environmental Research Division
Argonne National Laboratory
Argonne, IL 60439**

**ANL/ER/TM-1
ASCOT-91-7**

December 1991

**Work supported by the U. S. Department of Energy, Office of Energy Research, Office of
Health and Environmental Research, under contract W-31-109-Eng-38**

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

MASTER

Contents

1. Background	1
2. Minisodar Data	1
3. Sites.....	1
4. Data Collection	4
5. Log of Experiments.....	5
6. Data Synopsis	11
 Appendix A: Contours of Data for Diurnal Periods at the Coal Creek Site	13
Appendix B: Contours of Data for Diurnal Periods at the Bartlett Ranch Site	25
Appendix C: Data Collected by Rover Minisodar in Visits to the Sites Indicated in Fig. 1	37
 Figure 1: Locations of Permanent and Rover Minisodar Sites.....	2
 Table 1: Site Locations and Operating Times during ASCOT 1991.....	3

ARGONNE NATIONAL LABORATORY OPERATIONS DURING ASCOT 1991

R. L. Coulter and T. J. Martin

1. Background

The Atmospheric Studies in COMplex Terrain (ASCOT) field study took place during 1991 in conjunction with a model verification exercise in and around the Rocky Flats Plant (RFP) northwest of Denver, Colorado, between January 29 and February 8. As part of this exercise, Argonne (ANL) operated a portable minisodar at several locations around RFP during each of the experimental nights. Figure 1 shows the location of this system. In addition, ANL operated "permanent" network minisodars with enhanced time resolution at Coal Creek and the Bartlett Ranch for the duration of the field study.

2. Minisodar Data

Real-time data from each minisodar are identical in format, consisting of (1) vertical profiles of horizontal wind speed along the pointing directions of each of two beams tilted from the vertical by about 17 deg, (2) vertical wind speed along a vertically pointed beam, (3) the standard deviation of the components along each of these directions, (4) the signal amplitude, and (5) the number of samples within each average that were accepted as "good." The data output to the ASCOT data center consists of wind speed, wind direction, vertical wind speed, standard deviation of wind speed along the three pointing directions, and the vertical beam signal amplitude in arbitrary units. Maximum heights of the minisodars were generally limited to 300 m; however, lower heights were occasionally used to increase the sampling rate or because of limited signal strength. During this field study, operational periods were on selected nights from 2000 hr until 0500 hr the following morning. See Table 1 for details.

3. Sites

The minisodar in Coal Creek Canyon (Linda's Ranch) is located very near the mouth of the canyon in order to delineate the drainage flow out of the canyon. The flow

from this location to the southwest of RFP is, along with the Eldorado Canyon outflow to the northwest, a very important part of the near-surface flow that intersects at RFP. This minisodar in Coal Creek Canyon was operated throughout the experimental period with typical averaging times of 1-2 min during the nighttime study periods and 5 or 10 min during daytime periods. This minisodar operated successfully throughout the period, except for a time during the morning of January 30, when high winds caused a power failure, and part of the night of January 31-February 1, when data were not successfully transferred to tape. These data, up to a height of 160 m, were recovered from a paper backup.

Figure 1 Locations of permanent (CC, BR) and rover (R) minisodar sites. Vertical lines are tower locations. Figure is not to scale.

Table 1 Site locations and operating times during ASCOT 1991. Sets of slashes denote time periods when the rover minisodar was located at the site. Thus, the Coal Creek (CC) and Bartlett Ranch (BR) systems operated at all denoted periods. They also operated between these periods and during the daytime. Positions (Universal Transverse Mercator Coordinates) and elevations (above sea level) for each site are at the right of the table.

ARGONNE NATIONAL LABORATORY MINISODAR OPERATIONS DURING ASCOT 1991																			
EXPT	I		II		III		IV	V		VI		VII		POSITION					
DATE	1/29	1/30	1/31	2/01		2/02	2/03	2/04	2/05		2/06	2/07		2/08	UTMX	UTMY	EL (m)		
TIME	1800- 1514	0900- 1600 1930- 0900	2003- 2330	0000- 0215	0300- 0530	0000- 2230- 2130 0040	0115- 0515 0130	2000- 0220- 0430	2000- 2210 0100	2245- 0100 0305	0150- 0340- 0530	2000- 2215 0340- 0530	2305- 0035	0105- 0230 0310- 0530	2000- 2135 2220- 0030	0110- 0530	488.39	4416.34	1683
SITE R1	////	////	////	////	////	////											485.70	4417.49	1784
R2				////													477.90	4420.77	1713
R3					////						////						479.68	4420.77	1820
R4						////	////				////						479.83	4412.07	1890
R5																	479.60	4414.00	1900
R6								////					////				477.08	4413.88	1968
R7									////								486.05	4411.03	1759
R8										////							485.95	4419.59	1677
R9														////			482.88	4420.45	1723
Ra																	479.35	4417.25	1851
Rb																	476.30	4413.96	1994
CC	////	////	////	////	////	////	////	////	////	////	////	////	////	////	////	////	487.20	4411.90	1670
BR	////	////	////	////	////	////	////	////	////	////	////	////	////	////	////	////			

The minisodar at the Bartlett Ranch is located southeast of RFP, to the west of Stanley Lake, in a position to monitor the near-surface flows "downstream" of RFP. This minisodar was also operated with 1- or 2-min averages during intensive nighttime studies and with 5- or 10-min averages during daytime operations. However, during several daytime periods this system was not operating because it was in the process of being installed in its network configuration.

The portable minisodar was operated during all intensive nighttime study periods, visiting sites on all sides of RFP for periods of about 2 hr by the end of the experimental period. The site locations are numbered hexadecimally in chronological order of their initial visits. Sites R5, R6, Rb, and R4 were along the extension of the western border of RFP, along Route 93 (see Fig. 1). Site R5 was south of the intersection of Routes 93 and 72; R6 and Rb were just south and north, respectively, of RFP; and R4 was north of the intersection of Routes 93 and 128, overlooking Eldorado Canyon (at a burned out restaurant, "Stonehenge"). Sites R8, R1, R2, and R9 were along the eastern boundary along Indiana Street and its extension to the north. Site R8 was at the intersection of Indiana Street and Route 72, just "above" the Bartlett Ranch; R1 was at the water treatment plant, due east of RFP; R2 was at the lidar site (intersection of Indiana Street and Route 128); and R9 was along Route 170, northeast of RFP in the Rocky Creek drainage. Site Ra was located north of RFP in the Coal Creek drainage, immediately beside the creek, about 3 km east of Route 93 and 2.5 km north of Route 128. Finally, sites R7 and R3 were just below the mouths of Coal Creek Canyon and Eldorado Canyon, respectively. Table 1 shows the times, locations in Universal Transverse Mercator coordinates, and durations of each data file.

4. Data Collection

The portable minisodar (rover) is a beam-steered, phased array contained in an enclosure small enough for transport in a station wagon along with a small gasoline generator. When a quiet location was found, the enclosure was placed about 50 m from the car, the generator was placed on the opposite side of the car from the sodar, and data collection was started with the computer in the back seat. Operation normally began about 10-15 min after arrival at each location. Several sites were visited more than once to provide some benchmarks for the data. The filtration plant to the east of RFP (site R1) was used at first as a benchmark, to coincide with airsonde launches made by Pacific Northwest

Laboratory (PNL). The site on the bluff overlooking Eldorado Canyon (site R4) was later chosen often because of the apparent importance and variability of flow from that canyon. Data were almost always taken with 1-min averaging times with the roving minisodar. The dates, times, and locations for each site can be determined by using Table 1 and Fig. 1.

All data taken by ANL and provided to the central data bank have been averaged to 10-min intervals. The maximum height was generally 300 m with range gates of 8 m, although the profiles did not always attain that height.

5. Log of Experiments

The following log gives a flavor of the conditions experienced on each night during the study. Since this description is written in the form of a diary, abbreviations and brief phrases are sometimes used. Note that the entries are from the viewpoint of the observer; i.e., no reference is necessarily made to overall conditions or to comments of other investigatory parties. The primary source for the comments is the actual data rather than log entries made during the experimental period. The log is divided into entries from each of the sites visited by the rover minisodar and from the Coal Creek and Bartlett Ranch units.

Abbreviations used in the log are the following:

<: less than

>: greater than

N, E, W, S: north, east, west, south in the meteorological sense; that is, N wind means wind from the north

Jet: wind speed profile with speeds decreasing above and below

January 29-30, 1991

Rover: Site 1. All night. Before 2300 hr, winds are light NW to NE with near-surface winds SE. At 2300 hr, strong winds (> 15 m/s) are observed aloft that reach the surface by 2330 hr. Very windy from W for remainder of night, with exception of

40-min periods near 0200 and 0600. Vertical velocities are mostly positive near the surface after midnight, becoming negative with increasing height.

Coal Creek. Very strong down-canyon winds last all night. Wind speeds often > 15 m/s very near the surface.

Bartlett Ranch. Winds are initially light and variable but become very strong after midnight (> 15 m/s), then decrease to 4 m/s by 0200 and remain relatively light and apparently rotate slowly because high winds elsewhere do not penetrate this area. Strong winds then develop again after 0600, perhaps due to greater vertical mixing. Good signal strength to heights > 250 m.

January 30-31, 1991

Rover: Site 1. All night. Five-minute averages show strong winds with approximately 2-hr oscillation in speeds.

Coal Creek. Again strong winds, though not as strong as previous night, with wind speed maximum at 100-m height or more and directions varying from SW to NW.

Bartlett Ranch. Slightly weaker (than previous night) winds from W oscillate in strength and direction with approximate 2-hr period.

January 31-February 1, 1991

Rover: Site 1. 2000-2315: High winds from W decrease 100 m above the surface. Weak negative vertical velocities are prevalent throughout profile.

Rover: Site 2. 0000-0200: Strong winds from WSW with good signal strength to 250-m height. Vertical velocities are near zero at surface, negative aloft.

Rover: Site 3. 0300-0530: Winds increase in strength with height to 15 m/s at 100 m, decrease above 250 m. Mostly positive vertical velocity, with intermittent periods of downward motion.

Coal Creek. Steady, strong winds down canyon with good signal strength to 250-m height. Approximately 3-hr oscillation in speeds; decreasing speeds coincide with near-zero or positive vertical velocity.

Bartlett Ranch. Jet from NW (7-8 m/s) descends from above 200 m to 50-100 m after 2030 hr; jet is associated with positive vertical velocity. Strong winds oscillate in time, becoming steady from W after 0240 hr. Speeds decrease rapidly after 0540 and turn to NE.

February 1-2, 1991

Rover: Site 1. 1830-2130: Light winds turn from SW to NW with maximum speed at height of 25-30 m. Vertical velocity is weak and variable.

Rover: Site 4. 2230-0030: Maximum speed of 6-7 m/s at 35-m height weakens, then reestablishes at 2330 hr. Vertical velocity is weak and undefined.

Rover: Site 5. 0115-0500: Weak winds from SE to SW prevail early, then reestablish from NW (from Coal Creek?) after 0240. Jet has maximum speed at about 25-m height. Negative vertical velocities dominate below 100-m height after 0230 hr.

Coal Creek. Down-canyon winds undercut NE winds after 1630. Jet begins at 50 m by 1700 hr, with maximum speeds increasing to 7-8 m/s. Vertical velocities are mostly negative, but intermittent positive vertical velocities occur during periods of weaker drainage. Very steady conditions occur after 2000 hr, with 10 m/s in jet at times. Layer is 175-200 m deep by 0200 hr; winds are more southerly above 150 m.

Bartlett Ranch. NW to NNW winds from surface to 50-m height, turning with height. Surface layer is 100 m deep by 2000 hr, with 4-m/s speeds in jet at 75 m. Winds turn to SW after 2240 hr, with decreasing strength. After midnight, NNE winds prevail above 20 m, SW below. After 0140 hr, SW winds dominate with increasing strength.

February 3-4, 1991

Rover: Site 4. 2000-0130: Variable wind direction before midnight, with episodes from SE to NW. After midnight, winds strengthen from W (from Eldorado Canyon, presumably), with speed maximum near 100-m height. Strong negative vertical velocities prevail from 2215 to 0030 hr, when direction is SE and S.

Rover: Site 6. 0220-0430: Well developed flow W (from Coal Creek?) has maximum speed at about 40-m height, decreasing slowly above. Weak to moderate negative vertical velocities dominate.

Coal Creek. Winds decrease at 2100 hr. (Winds had been quite high all day.) Occasional S or SE winds occur before 2200 hr. Jet begins to develop after 0000 hr (4-5 m/s); stronger jet develops after 0230 but at higher than normal elevation (100 m); jet ends at 0800 hr, up-valley flow by 0930 hr.

Bartlett Ranch. Light SW winds at 1740 hr with negative vertical velocity are evident. E winds at 2000 hr (4-8 m/s) are undercut by shallow N winds (30-m-deep layer) at 2050 hr, oscillating until 2300 hr, when winds aloft turn to S to SW along with descending stratified layer. Large negative vertical velocities develop when layer reaches surface. Winds turn to W at 0200 hr, and new surface layer develops to 150 m. Some N to NE, near-surface flow occurs from 0300 to 0340 hr, approximately when large positive vertical velocities appear above 40 m. NE flow is well established from 0430 hr onward; elevated flow from W prevails above 50 m at 0520 hr.

February 4-5, 1991

Rover: Site 6. 2000-2220: Traffic noise problems are encountered, but signal strength is good to 160-m height. Winds are approximately constant above 15 m, from WSW; negative vertical velocities dominate except for lowest level.

Rover: Site 7. 2245-0115: Jet from Coal Creek is well defined at about 50-m height; negative vertical velocities are also well defined, increasing after midnight.

Rover: Site 8. 0150-0300: Very weak winds have variable wind direction; vertical velocities are about zero.

Rover: Site 4. 0340-0530: Moderate winds are from W with some indication of a return flow above 100-m height; vertical velocities are mostly zero or negative.

Coal Creek. Transition to down-canyon flow occurs at 1600 hr. Jet becomes established at 1730 hr, < 7 m/s until 2000 hr. Surface layer is 125 m deep with jet core at 45 m and direction just S of canyon orientation below core, just N of it above core. Positive vertical velocities are evident at 0030-0130 with no obvious change in horizontal winds. Frequent jet > 7 m/s occurs in quasi-oscillatory fashion until 0600 hr; up-canyon winds take over by 0940 hr.

Bartlett Ranch. The NW flow near surface at 2000 hr becomes NE until 2120 hr, when SW direction establishes briefly to 150-m height; then flow is very shallow (< 50 m deep). At 2300 hr, surface layer is 75-100 m deep; SW to W flow develops at 0040 hr, but flow above 60 m height is NE. NNW flow descends to surface by 0200 hr in shallow layer (< 50 m). Layer deepens at 0400 hr to 100-150 m from SW, with stronger winds (4 m/s).

February 6-7, 1991

Rover: Site 4. 2000-2215: Light winds. Wind maximum is in lowest levels (about 4 m/s, 20 m height), turning from W to SW with height; negative vertical velocity.

Rover: Site 7. 2300-0030: Steady conditions with jet maximum (7-8 m/s) at 40-m height; moderate negative vertical velocity. For direct comparison with Coal Creek minisodar (to look at correlations, etc.), 30 averages are taken to 150 m.

Rover: Site 6. 0100-0230: Later time (than previous visit here) has less traffic noise. Speed maximum at 25 m (4 m/s) is from W, decreasing rapidly to light and variable by 80 m; apparently Coal Creek flow is still well defined. Negative, weak vertical velocities exist below 60 m; positive vertical velocities occur above 80 m.

Rover: Site 9. 0310-0540: Site is located in low spot NE of RFP. Winds are light, stronger at 0345-0445 hr (4 m/s). Direction is WSW, turning to NW with height, with positive vertical velocities during stronger wind periods (convergence), but negative values during lighter periods with well defined maximum in magnitude at 60 m height.

Coal Creek. Jet begins at 1920 hr, along with a descending layer from above with maximum speeds 4-5 m/s. Jet increases to 7 m/s at 2330 hr, along with some positive vertical velocities. Steady conditions prevail through rest of night, except for 2-3 min at 0325 hr. Jet strength decreases and descends at 0610 hr and is gone by 0840 hr, when up-canyon flow begins.

Bartlett Ranch. Elevated layer (100 m above surface) at 2200 hr is gone by 2300 hr; winds shift to NW and deepen to 150-m height at 0100 hr with some from E at top. At 0150 hr surface layer breaks down to nothing. Then NW to NE flow develops in elevated layer that descends to surface. At 0320 hr, NW flow with increasing winds prevails. At 0400-0600 hr winds decrease, becoming SW near surface and backing to W, then NW, at 100 m.

February 7-8, 1991

Rover: Site 4. 2000-2130: Deepening layer with S to SW flow through 70 m grows from surface with winds from WSW, while SSW winds continue aloft. Layer reaches 100-m depth by 2100 hr; vertical velocity is about zero with episodic activity.

Rover: Site a. 2220-0030: For first 10-15 min, a jet of 4 m/s at 50-m height is extant. After that winds are light, from SW during stronger episodes. Light conditions show S to SW flow up to 20-30 m, perhaps due to local drainage. Flow turns to W to NW above 20-30 m. Strong negative vertical velocity during first 15 min is replaced by a strong, brief, positive vertical velocity that marks the beginning of a light-wind period.

Rover: Site b. 0115-0530: Located halfway between Coal Creek and Eldorado Canyons along Route 93. Wind speed maximum at 75-100 m from NW prevails, with near-surface layer highly variable, sometimes coming from NE briefly. Negative vertical velocities are well defined near surface, zero to positive above.

Coal Creek. A weak jet at 1800 hr begins in earnest at 2020 hr (occasionally 7 m/s), decreasing in intensity at 2200 hr. Significant positive vertical velocities at 2320-2355 hr are followed by a strong jet (8 m/s) until 0040 hr. Oscillatory action of jet and vertical velocities continues through the night. Jet ends at 0900 hr; up-canyon flow takes over at 0940 hr.

Bartlett Ranch. Light winds. At 2300 hr an elevated layer of NE winds caps a surface NW flow; repeats at 0140 hr. Stronger flow at 0140 hr with developing NNW direction remains NW to NNW with maximum of about 7 m/s at 50 m. Lighter winds are more from W at 0440 hr and coincide with large oscillations in vertical velocities and brief E wind near surface. SW winds take over at 0530 hr through 100-m height, then back to W to NW at 0700 hr.

6. Data Synopsis

Appendixes A-C present simple contours of wind speed, wind direction, and vertical winds at the rover sites and at Coal Creek (cc). The wind speed contours are in units of cm/s, and the wind directions are in degrees relative to true north. The set of plots in Appendix A covers periods of roughly 24 hr, bracketing midnight. Each page presents data for one diurnal period. The plots in Appendix B depict contours at the Bartlett Ranch (br) during similar diurnal periods. The plots in Appendix C show the data collected by the rover. In this case each page represents a single visit to a single site. The site designations at the top of each plot are as defined in Table 1.

Appendix A

Contours of Data for Diurnal Periods at the Coal Creek Site

WIND SPEED CONTOURS ASCOT 91/01/29 site cc
500 1000 1400

WIND DIR CONTOURS ASCOT 91/01/29 site cc
225 270 315

VERT VEL CONTOURS ASCOT 91/01/29 site cc
-30 -60 -90

WIND SPEED CONTOURS ASCOT 91/01/30 site cc
200 400 700 WIND DIR CONTOURS ASCOT 91/01/30 site cc
225 270 315 VERT VEL CONTOURS ASCOT 91/01/30 site cc
0 -40 -80

WIND SPEED CONTOURS ASCOT 91/01/31 site cc

400 800 1200

WIND DIR CONTOURS ASCOT 91/01/31 site cc

225 270 315

VERT VEL CONTOURS ASCOT 91/01/31 site cc

0 -40 -80

WIND SPEED CONTOURS ASCOT 91/02/02 site cc
200 400 700

WIND DIR CONTOURS ASCOT 91/02/02 site cc
225 270 315

VERT VEL CONTOURS ASCOT 91/02/02 site cc
0 -40 -80

WIND SPEED CONTOURS ASCOT 91/02/03 site cc
200 400 700

WIND DIR CONTOURS ASCOT 91/02/03 site cc
225 270 315

VERT VEL CONTOURS ASCOT 91/02/03 site cc
0 -40 -80

WIND SPEED CONTOURS ASCOT 91/02/04 site cc
200 400 700

WIND DIR CONTOURS ASCOT 91/02/04 site cc
225 270 315

VERT VEL CONTOURS ASCOT 91/02/04 site cc
0 -40 -80

WIND SPEED CONTOURS ASCOT 91/02/06 site cc
200 400 700

WIND DIR CONTOURS ASCOT 91/02/06 site cc
225 270 315

VERT VEL CONTOURS ASCOT 91/02/06 site cc
0 40 80

Appendix B

Contours of Data for Diurnal Periods at the Bartlett Ranch Site

WIND SPEED CONTOURS ASCOT 91/01/29 site br
_____ 400 800 ----- 1200

WIND DIR CONTOURS ASCOT 91/01/29 site br
_____ 135 225 ----- 315

VERT VEL CONTOURS ASCOT 91/01/29 site br
_____ -20 0 ----- 20

WIND SPEED CONTOURS ASCOT 91/02/02 site br
—— 100 300 ----- 500

WIND DIR CONTOURS ASCOT 91/02/02 site br
—— 135 225 ----- 315

VERT VEL CONTOURS ASCOT 91/02/02 site br
—— -30 0 ----- 30

WIND SPEED CONTOURS ASCOT 91/02/03 site br
— 200 400 - - - - 600

WIND DIR CONTOURS ASCOT 91/02/03 site br
— 135 225 - - - - 315

VERT VEL CONTOURS ASCOT 91/02/03 site br
— -30 0 - - - - 30

WIND SPEED CONTOURS ASCOT 91/02/06 site br
_____100200 -----400

WIND DIR CONTOURS ASCOT 91/02/06 site br
_____135225 -----315

VERT VEL CONTOURS ASCOT 91/02/06 site br
_____ -300 -----30

WIND SPEED CONTOURS ASCOT 91/02/07 site br
—— 100 300 ----- 500

WIND DIR CONTOURS ASCOT 91/02/07 site br
—— 135 225 ----- 315

VERT VEL CONTOURS ASCOT 91/02/07 site br
—— -30 0 ----- 30

Appendix C

**Contours of Data Collected by Rover Minisodar
in Visits to the Sites Indicated in Fig. 1**

WIND SPEED CONTOURS ASCOT 91/01/29 site r1
— 100 500 - - - 900

WIND DIR CONTOURS ASCOT 91/01/29 site r1
— 225 270 - - - 315

VERT VEL CONTOURS ASCOT 91/01/29 site r1
— -20 0 - - - 20

WIND SPEED CONTOURS ASCOT 91/01/31 site r1

WIND DIR CONTOURS ASCOT 91/01/31 site r1

VERT VEL CONTOURS ASCOT 91/01/31 site r1

WIND SPEED CONTOURS ASCOT 91/02/01 site r3
—— 900 1200 ----- 1400

WIND DIR CONTOURS ASCOT 91/02/01 site r3
—— 240 270 ----- 300

VERT VEL CONTOURS ASCOT 91/02/01 site r3
—— -10 0 ----- 20

WIND SPEED CONTOURS ASCOT 91/02/01 site r4
_____ 200 400 ----- 600

WIND DIR CONTOURS ASCOT 91/02/01 site r4
_____ 225 270 ----- 315

VERT VEL CONTOURS ASCOT 91/02/01 site r4
_____ -10 0 ----- 10

WIND SPEED CONTOURS ASCOT 91/02/03 site r4
— 100 300 - - - - 500 WIND DIR CONTOURS ASCOT 91/02/03 site r4
— 225 270 - - - - 315 VERT VEL CONTOURS ASCOT 91/02/03 site r4
— -10 0 - - - - 10

WIND SPEED CONTOURS ASCOT 91/02/04 site r6
— 200 300 - - - - 400 WIND DIR CONTOURS ASCOT 91/02/04 site r6
— 225 270 - - - - 315 VERT VEL CONTOURS ASCOT 91/02/04 site r6
— -10 0 - - - - 20

WIND SPEED CONTOURS ASCOT 91/02/07 site r4
—— 200 300 ----- 400 WIND DIR CONTOURS ASCOT 91/02/07 site r4
—— 180 210 ----- 240 VERT VEL CONTOURS ASCOT 91/02/07 site r4
—— -10 0 ----- 10

WIND SPEED CONTOURS ASCOT 91/02/08 site rb
100 200 400

WIND DIR CONTOURS ASCOT 91/02/08 site rb
225 270 315

VERT VEL CONTOURS ASCOT 91/02/08 site rb
-20 0 20

END

**DATE
FILMED**

3 / 24 / 92