DOE/PC/89883--27

DE92 004518

**COAL LIQUEFACTION PROCESS STREAMS
CHARACTERIZATION AND EVALUATION**

**Quarterly Technical Progress Report
January 1 through March 31, 1991**

S. D. Brandes, R. A. Winschel,
F. P. Burke, and G. A. Robbins

September 1991

MASTER

CONSOLIDATION COAL COMPANY
Research & Development Department
4000 Brownsville Road
Library, PA 15129

Prepared for the
United States Department of Energy
Under Contract No. DE-AC22-89PC89883

US/DOE Patent Clearance was provided by
Chicago Operations Office on 8/29/91.

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

gss

NOTICE

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States nor any agency thereof, nor any of their employees, makes any warranty, expressed or implied, or assumes any legal liability or responsibility for any third party's use or the results of such use of any information, apparatus, product or process disclosed in this report, or represents that its use by such third party would not infringe privately owned rights.

TABLE OF CONTENTS

	<u>Page</u>
INTRODUCTION	1
Overview	1
Contract Objectives	2
Contract Activities - This Period	3
RESULTS AND DISCUSSION	5
HRI Delayed Coking Study (CTSL Run CC-9)	5
Summary	5
Background of HRI's Tests	6
Sample Analysis and Results	8
General Discussion	12
Conclusions	13
Solvent Quality of Maltenes	14
Summary	14
Results and Discussion	15
Experimental	17
Analyses of Wilsonville Run 259G Net Product and Product Fractions	18
Procedure	18
GC/MS Results	18
Phenolic -OH Concentrations	18
Calibration and Analysis of Standard Coal	20
Participants Program Status	22
REFERENCES	24

LIST OF TABLES

<u>Table</u>	<u>Page</u>
1 Analyses of Feed Coals, HRI Run CC-9	26
2 Run Conditions, HRI Run CC-9	27
3 Analysis of Make-Up Oils, HRI Run CC-9	28
4 Delayed Coker Feedstock (CAS Bottoms) Properties, HRI Run CC-9	29
5 Delayed Coking Test Conditions and Yields, HRI Run CC-9	30
6 Coker Overhead Product Analysis, HRI Run CC-9	31
7 Coke Analysis, HRI Run CC-9	31
8 Analyses of PFLs, Corresponding Coker Oil Products, and Hydrotreated Coker Oil Products, HRI Run CC-9	32
9 Results of Applying Correlations Between ¹ H-NMR Data and Microautoclave Solvent Quality Assays to PFLs, Coker Overhead Oils and Hydrotreated Coker Overheads, HRI Run CC-9	34
10 Solubility Fractionation of PFLs and Corresponding Coker Overhead Oil Products, HRI Run CC-9	35
11 Identification of Selected Prominent Peaks in Figure 2	36
12 Identification of Selected Prominent Peaks in Figure 3	37
13 Microautoclave Tests of PFLs, Coker Overhead Oils and Hydrotreated Coker Overheads, HRI Run CC-9	38
14 Sample Analyses, Wilsonville Run 260C, V-131B	39

LIST OF TABLES (Continued)

<u>Table</u>	<u>Page</u>
15 Microautoclave Coal Conversions, Wilsonville Run 260C, V-131B	40
16 Analysis of 1988 Batch of Old Ben No. 1 Mine, Indiana V Coal	41
17 Microautoclave Calibration Tests	42
18 Participants Program Subcontracting Status	43
19 Participants Program Sample Set for Phase I	44

LIST OF FIGURES

<u>Figure</u>	<u>Page</u>
1 HRI Ebullated-Bed Bench Unit 227 (Excludes Solvent Inventory Tank).	46
2 GC/MS Chromatograms of PFL, Coker Overhead Product and Hydrotreated Coker Overhead from Coker Test No. 1, HRI Run CC-9.	47
3 GC/MS Chromatograms of PFL, Coker Overhead Product and Hydrotreated Coker Overhead from Coker Test No. 2, HRI Run CC-9.	48
4 Total Ion Chromatogram, Naphtha Fraction, Wilsonville Run 259G Product.	49
5 Total Ion Chromatogram, Jet Fuel Fraction, Wilsonville Run 259G Product.	50
6 Total Ion Chromatogram, Diesel Fuel Fraction, Wilsonville Run 259G Product.	51
7 Total Ion Chromatogram, Crude Oil, Wilsonville Run 259G Product.	52
 Key Key to Peak Identifications (Figures 4-7)	 53

ABSTRACT

COAL LIQUEFACTION PROCESS STREAMS CHARACTERIZATION AND EVALUATION, QUARTERLY TECHNICAL PROGRESS REPORT, JANUARY 1 THROUGH MARCH 31, 1991

This is the sixth Quarterly Technical Progress Report under DOE Contract DE-AC22-89PC89883. Five major topics were reported.

- Analyses were made of four samples (two pressure filter liquids from CTSI Run CC-9 and two associated coker overhead product oils) received from Hydrocarbon Research, Inc.
- Microautoclave tests were made to assess the solvent quality of hexane-soluble oils (maltenes) isolated from a Wilsonville recycle solvent. This work was done based on a suggestion of Mr. T. Simpson, DOE, Office of Coal Conversion.
- The Wilsonville Run 259G net product and its distillation fractions returned to Consol by Conoco were analyzed by gas chromatography/mass spectrometry (GC/MS). The phenolic -OH content of these materials was determined by Fourier transform infrared (FTIR) spectroscopy.
- Microautoclave tests and chemical analyses were performed to calibrate the reactivity of the standard coal used for determining donor solvent quality of process oils in this contract.
- A brief summary of the Participants Program is presented. A listing of all samples used in Phase I of the program is included.

Section 1

INTRODUCTION

This is the Technical Progress Report for the sixth quarter of activities under DOE Contract No. DE-AC22-89PC89883. It covers the period January 1, 1991, through March 31, 1991.

OVERVIEW

Direct coal liquefaction is a complicated chemical process. Recent advances in the technology, which significantly reduced the product costs, have come about through an improved fundamental understanding of liquefaction chemistry. Further improvements are possible, and will depend on continued advances in our knowledge of process chemistry. Supplying this knowledge requires the use of a variety of the tools of analytical chemistry applied to the appropriate samples, and interpretation of the analytical data in context to process development.

The R&D Department of Consolidation Coal company (Consol R&D) is conducting a three-year project to characterize process and product streams from direct coal liquefaction process development programs sponsored by the Department of Energy. In this project, Consol R&D will obtain samples from current process development activities in coal liquefaction and coal-oil coprocessing, and characterize them using established analytical techniques. In addition, selected samples will be characterized by other analytical techniques to evaluate their potential for aiding process development. These analyses and interpretation of the results in relation to process operations will be provided by a subcontracted project team.

In addition to samples from current process development programs, Consol R&D maintains a bank of coal liquids samples from the SRC-I, H-Coal, ITSL (Lummus and Wilsonville) and HRI-CTSL coal liquefaction programs, and the HRI and UOP coprocessing development programs. These samples, which represent important stages in the recent development of coal liquefaction technology, also will be used in the analytical program.

CONTRACT OBJECTIVES

Consol R&D is conducting a three-year program to characterize process and product streams from direct coal liquefaction process development projects. The program objectives are two-fold: 1) to obtain and provide appropriate samples of coal liquids for the evaluation of analytical methodology, and 2) to support ongoing DOE-sponsored coal liquefaction process development efforts. The two broad objectives have considerable overlap and together serve to provide a bridge between process development and analytical chemistry.

More specifically, the first objective is to identify, collect and disburse appropriate samples of coal liquids for analysis by techniques that hold promise, but are not fully demonstrated, for use in liquefaction process development efforts. Samples will be chosen from ongoing DOE-funded liquefaction and coprocessing projects and from Consol's collection of coal liquids produced during the past ten years. Samples will be chosen based on their relevance to process development programs, and will be well-documented in terms of feedstocks, sampling location, time and operating conditions. The samples chosen will be sufficient to judge the applicability of the analytical methods being evaluated. These process oils will be analyzed by Consol R&D in a base characterization program using techniques established in previous Consol research. Selected samples also will be provided to project team participants (as subcontractors), other researchers active in the analysis of coal liquids, who will characterize them using a range of methods beyond those used in the base program. Subcontracts to approximately 10 to 15 organizations that have specialized analytical capabilities will be a major aspect of this work. Individual analytical specialists from the subcontractors will take a major role in interpreting their own results in context to the liquefaction process, and not merely provide data. This portion of the program will evaluate the utility of promising analytical techniques for providing useful information for coal liquefaction process development, and will apply those results to ongoing development efforts. This evaluation will be based on the usefulness of an analytical method in process monitoring,

to obtain specific chemical information, and as judged by precision and accuracy.

The second objective is to support the process developers. This will include support in the form of providing results and interpretation of data obtained with the analytical techniques being assessed. However, more directly, appropriate process oils will be characterized in the base program by a variety of standard techniques that have proven relevance to development efforts. The results from these more routine analyses will aid plant operations and planning. Also, these results will provide the data needed to select appropriate samples for the non-routine techniques and provide a set of data for correlations with the results of the more exploratory techniques.

CONTRACT ACTIVITIES - THIS PERIOD

Contract activities for this quarter are listed below. Each topic is summarized and discussed in detail under a separate heading in Section 2, Discussion. Because each topic is summarized, when appropriate, in the corresponding section of the Discussion, no overall Summary section is provided in this report.

- Analyses were made of four samples (two pressure filter liquids from CTSL Run CC-9 and two associated coker overhead product oils) received from Hydrocarbon Research, Inc. The quality of the coker overheads was determined to help evaluate the potential use of a delayed coker for solids removal in the CTSL process.
- The non-distillable, hexane-soluble oil fraction (maltene) was isolated from a Wilsonville recycle resid (V-131B, Run 260C) and microautoclave tests were made to assess its solvent quality. This work was done at the request of Mr. T. Simpson, DOE, Office of Coal Conversion.
- The Wilsonville Run 259G net product and its distillation fractions returned to Consol by Conoco were analyzed by gas chromatography/

mass spectrometry (GC/MS). The phenolic -OH content of these materials was determined by Fourier transform infrared (FTIR) spectroscopy.

- Eighteen microautoclave tests were made to calibrate the reactivity of the standard coal (Indiana V, Old Ben Mine No.1) which is used to determine donor solvent quality of the process oils tested under this contract. The coal was analyzed by chemical analyses to monitor oxidation.
- Substantial progress was made in the Participants Program this quarter. A brief summary of the Participants Program is presented. A listing of all samples used in Phase I of the program is included.
- Work in progress, but not completed this quarter, includes:
 - 1) Analysis of oils from Wilsonville Run 260
 - 2) Analysis of oils from Wilsonville Run 261
 - 3) Preheater simulation studies
 - 4) Literature search concerning analytical methods for coal liquids

Section 2

RESULTS AND DISCUSSION

HRI DELAYED COKING STUDY (CTSL Run CC-9)

SUMMARY

The objective of Hydrocarbon Research, Incorporated (HRI) Run CC-9 was to produce atmospheric-still-bottoms in the continuous Catalytic Two-Stage Liquefaction (CTSL) unit for use as feedstocks for off-line delayed coking tests. The objective of the coking tests was to study the potential use of delayed coking as a means for solids removal in the CTSL process. The solids-free liquid product from the coking operation would be used primarily as a component of the slurry oil for the CTSL process.

Four samples were received from Dr. Sudhir Panvelker of HRI for analysis. These samples included two pressure-filter liquid (PFL) samples (the filtrate of the continuous-atmospheric-still (CAS) bottoms, which were the feedstocks to the delayed coking unit), and the two corresponding overhead oil products from the coker. The coker feedstocks (CAS bottoms) were produced in Run CC-9, which was a continuation of Run CC-8. Both runs used Illinois No. 6 (Burning Star No. 2 Mine) coal as feed.¹ The feed coal had been finely pulverized by OTISCA Industries. Coking was done by Foster Wheeler Development Corporation in a four-inch diameter delayed coker.

Analyses of these samples show that the coker overhead oils have a lower boiling-point distribution, a greater percentage of hexane solubles, a slightly reduced phenolic -OH concentration, but are poorer solvents for coal conversion than the corresponding PFL's. Coker overhead oil properties are dependent on coking conditions. The combination of higher temperature and lower steam/feed ratio promoted cracking and thus increased the differences between the coker overhead oil and its corresponding PFL. The coker overhead oils contain diverse molecular types, including aromatics, hydroaromatics and paraffins. Hydrotreating the coker overhead oils lowers the heteroatom content and significantly

reduces the phenolic -OH content, lowers the condensed aromatic hydrogen content, and improves the solvent quality of the oil for coal conversion. In our tests, the solvent quality of the hydrotreated coker overhead oil remained lower than the solvent quality of the respective PFL.

BACKGROUND OF HRI'S TESTS

Run CC-9 was a continuation of Run CC-8.^{1,2} Two sets of run conditions were tested in Run CC-9. In both conditions, the feed coal was supplied by OTISCA Industries as a stable (30-35 wt %) slurry of finely pulverized coal in water. In the first condition the feed coal was mine-cleaned, and in the second condition the feed coal was cleaned by the OTISCA process. The coal was fed to the CTSL unit after on-line drying to <2 wt % water.² Analyses of the feed coals are given in Table 1.³

Run conditions are given in Table 2. The space velocity during Run CC-9 was 67 lb (MF coal)/hr/ft³ of catalyst (each stage). This is considerably higher than the space velocity (about 40 lb (MF coal)/hr/ft³, each stage) employed in most recent runs in the HRI CTSL unit. The ratio of recycle oil to fresh MF coal was 2/1, which is higher than usual. This higher recycle ratio was chosen because of operational problems encountered at lower ratios in Run CC-8. Shell 317 (Ni/Mo/Al) catalyst was used in both reactors. Make-up oil (HRI L-756, a PFL obtained from an earlier run) was used to balance the recycle oil requirements because of withdrawal of some of the continuous-atmospheric-still (CAS) bottoms for the coking study. The make-up oil requirements were changed in switching from Condition 1 (mine-cleaned coal) to Condition 2 (OTISCA-cleaned coal). The feed slurry in Condition 2 was too viscous for proper processing. At first, the CAS bottoms content of the recycle oil was reduced and then it was eliminated. The run was continued with the recycle oil consisting entirely of the light L-756 make-up oil. A second oil (Wilsonville-derived, HRI No. 5648) was substituted on the last day of the run after the supply of the L-756 oil was exhausted. The analyses of the make-up oils used in Run CC-9 are given in Table 3.

Three liquid net product streams are obtained from the CTSL unit. They are the separator overhead (SOH), the atmospheric-still-overhead (ASO), and the continuous-atmospheric-still (CAS) bottoms (Figure 1). A portion of the CAS bottoms was set aside and used as feed to the Foster Wheeler four-inch minicoker which operates in a delayed coking mode. The remaining CAS bottoms were batch pressure-filtered to produce a pressure filter liquid (PFL) and a pressure filter solid (PFS). CAS bottoms produced at both Conditions 1 and 2 were fed to the delayed coker. The product of Condition 1 was the feed for the first coker test, the product of Condition 2 was the feed for the second coker test. The analyses of these coker feedstocks are given in Table 4.

The coker was operated at a set of base conditions for the first test and at a variation of the base conditions in the second test (Table 5). Temperature and steam/feed ratio are two variables which most influence coker liquid yields. They were, therefore, selected as variables in the two runs in order to meet an objective of high liquid yields. Other parameters held constant in the two runs were pressure, throughput ratio, coking cycle time, feed rate, and steam-out period. A trial test performed at a temperature and steam rate significantly above normal commercial conditions (i.e., above 950°F) showed that the coking feedstocks were unstable at that elevated temperature. Tests 1 and 2, therefore, used temperatures in the range of 850-950°F, which are below those conventionally used for coking petroleum feeds. Coker conditions and yields are shown in Table 5. The major products of the coker are gas, overhead oil, a water-oil emulsion, and coke. The quantity of oil in the water-oil emulsion is included in the oil yields given in Table 5; however, that emulsion oil was not actually added to the main overhead oil product before analysis. Analyses of the overhead oil and coke, as provided by HRI, are given in Tables 6 and 7. In each test, 85% of the quinoline-soluble liquid content of the feed was recovered as overhead product coker oil. Approximately 32% of the 975°F⁺ organic resid was converted in each test.

SAMPLE ANALYSIS AND RESULTS

Four samples were received from HRI for evaluation. Two of these four samples (sample Nos. 5706 and 5707) are the pressure filter liquids (PFL) of the continuous atmospheric still (CAS) bottoms produced during Conditions 1 and 2, respectively, of Run CC-9. The whole CAS bottom products (not the PFLs) were used as coker feedstocks. The other two samples (sample Nos. 5708 and 5709) are the corresponding overhead oil products from the delayed coking tests which were made in the Foster Wheeler 4-inch minicoker. Consol's analyses were made to evaluate the quality of the coker liquids and coker feeds as coal liquefaction recycle oils.

The PFL samples analyzed here constitute approximately 90 wt % of the ash free CAS bottoms. The 10% toluene-insoluble material, which is filtered from the CAS bottoms, is presumed by HRI to be converted directly into coke in the delayed coking unit. It is, therefore, considered reasonable to directly compare the coker overhead oils with the PFLs, even though the PFLs are only 90% of the coker feeds (i.e., 90% of the ash-free CAS bottoms).

The elemental analyses, proton distributions, and phenolic -OH contents of all four samples, as determined by Consol, are given in Table 8. The elemental analyses of the PFLs are fairly similar to those of the corresponding coker oil products. Sample Nos. 5706 and 5708 which correspond to Condition 1 of Run CC-9 and Test 1 in the coking unit, were produced from mine-cleaned coal. Sample Nos. 5707 and 5709 were produced from the OTISCA-cleaned coal (Condition 2, Test 2). However, because the PFL contains no ash, the differences resulting from the two feed coals are minimized in these analyses. The data in Table 8 show that the coker overhead oil from Test 2 has about 50% lower sulfur and nitrogen contents than the respective PFL. The coker overhead oil from Test 1 has about 50% lower nitrogen content but a higher sulfur content than its respective PFL. Recall that the PFL constitutes only about 90% of the ash-free coker feed. A comparison of the properties of the coker overhead oils and the full coker feeds (CAS bottoms) can be made by examining the HRI data in Tables 4 and 6. Those data show a reduction

of both nitrogen and sulfur in the two coker overhead oils, relative to their feed. Interestingly, the HRI data show that the coker overhead oils have higher hydrogen contents than their respective ash-free feeds (Tables 4 and 6). The Consol data (Table 89) show that the coker overhead oils even have higher hydrogen contents than their respective PFLs.

The proton distributions (Table 8) of all four samples are fairly similar, although differences are apparent. The coker oil from Test 1 is more aromatic than its corresponding PFL (H-aromaticity = 16.4% vs 12.8%) and has a lower percentage of cyclic α and β protons (potentially donatable H). The coker oil from Test 2 has the same aromaticity as its corresponding PFL (H-aromaticity = 14.3%) but it has a lower percentage of cyclic α protons and is more paraffinic (alkyl β plus γ protons).

Correlations between ^1H -NMR data on solvent quality (as assayed by three different microautoclave tests) were developed earlier.²¹ Those correlations, which were developed from data on distillate liquefaction oils, may not be accurate predictors when applied to resid-containing oils such as PFLs or to coker oils; however, it is believed that they provide useful data for discerning trends. Those correlations were applied to the ^1H -NMR data from the PFLs, coker overhead oils and the hydrotreated coker overhead oils (the last samples will be discussed later). The correlation results appear in Table 9. The correlation indicates that the two PFLs have similar solvent quality, that the two coker overhead oils should be poorer quality solvents than their PFL counterparts and that the coker overhead oil produced in Test 1 should be a poorer solvent than that produced in Test 2.

The phenolic -OH contents of the coker overhead oils are lower than those of the respective PFLs. The separation of the four samples into solubility classes (Table 10) shows the coker overhead oil products to be reduced in asphaltenes and preasphaltenes. The coker overhead products are predominantly hexane soluble, with almost no preasphaltene content.

Gas chromatographic/mass spectrometric (GC/MS) analyses were performed on the PFLs and corresponding coker overhead oil products. Note that

GC/MS only detects volatile components; therefore, about 22% of the PFLs and about 7% of the coker overhead oils cannot be detected. Tables 11 and 12 list some of the more prominent peaks in the GC/MS chromatograms. The GC/MS spectra (Figures 2 and 3) show there to be a shift in the component distribution toward lower boiling material in the coker overhead product. This also is evident in the boiling point distributions provided by HRI (Tables 4 and 5). The shift is much more apparent in the 5706/5708 (Test 1) pair than in the 5707/5709 (Test 2) pair of samples. This is to be expected because the temperature in the coker was higher in the 5706/5708 (Test 1) case and the steam/feed ratio was lower. Both of these conditions would tend to promote more extensive cracking of the feed in the coker. The GC/MS analyses of the PFLs show preponderantly two-, three-, and four-ring condensed aromatics (mostly pyrenes) and the corresponding hydroaromatics with limited methyl substitution. The coker overhead oil produced in Test 1 (sample No. 5708) consists in part of mono- and diaromatics, substituted mono- and diaromatics, and the rearrangement and cracking products of the pyrenes (such as fluoranthene, and substituted naphthalenes). Long chain aliphatics and substituted one-, two-, three-, and four-ring compounds are detectable in the coker overhead oil produced in Test 2 (sample No. 5709). Some four-ring rearrangement products were identified. Hydroaromatic compounds were identified in both coker overhead oils. Also detectable in both samples, in relatively small quantities, are substituted phenols.

The integration of the delayed coking operation with the CTSL process was explored by HRI.³ They conclude that it is possible to utilize a delayed coker as a separation technique for the removal of solids from liquefaction bottoms. In addition, the use of a delayed coker may provide an indirect benefit to product cost, by allowing the liquefaction unit to operate at high space velocity. In their calculations, HRI assumes that the yields in the liquefaction section of the process will be unaffected by the quality of the coker overhead product. However, in an integrated system, the coker overhead oil would be recycled to the CTSL unit. The donor solvent properties of the coker overhead oils would thus become more important as their concentration in the liquefaction unit becomes

significant. In order to evaluate the solvent quality of the coker overhead oils, as compared to their respective PFLs, microautoclave solvent quality assays were done (Table 13). It was determined that the coker overhead oil products are poor donor solvents. Measured coal conversions were 14 to 20% (absolute) lower with the coker overhead products than with the respective PFLs. As anticipated from the lower hydrogen content and higher aromaticity, the coker overhead oil from Test 1 was a poorer solvent than the oil from Test 2. As noted, this appears to be related to the more severe coking conditions employed in Test 1 which resulted in a greater preponderance of cracking.

Hydrotreatment of the coker overhead products is expected to improve their donor solvent quality. Hydrotreatment of the two coker overhead oils samples was performed in a 45mL microautoclave. The microautoclave procedure⁵ used places a limit on the hydrogen available for reaction; no fresh hydrogen is added after the vessel is sealed. The result of this batch hydrotreatment is to upgrade the coker overhead oil (Table 8). There is an increase in hydrogen content, a substantial reduction in heteroatom content and a significant decrease in proton aromaticity. The ¹H-NMR correlations²¹ predict an improvement in solvent quality upon hydrotreating the coker overhead from Test 2, but the correlations give inconsistent results for the Test 1 samples (Table 9). The GC/MS analyses of these materials (Figures 2 and 3 and peak identifications in Tables 11 and 12) show substantial hydrogenation of the aromatic compounds found in the coker overhead oils. As discussed above, the coker overhead oil produced in Test 2 (sample 5709) is more like its respective PFL, apparently reflecting less cracking activity in the coker in Test 2. The hydrotreated coker overhead oil from Test 2 also exhibits a substantially higher molecular weight profile than the hydrotreated coker overhead oil from Test 1.

A test of the solvent quality of one of the hydrotreated coker overhead oils (5709-H) was made at the same conditions under which the corresponding PFL and coker oil were tested (Table 10). The resultant coal conversion using this material was intermediate between the corresponding PFL and the coker overhead oil. Considering the limited

availability of hydrogen in the microautoclave (shaker bomb) apparatus, it would appear that further hydrotreating and further improvement in oil quality would be possible under optimum conditions.

GENERAL DISCUSSION

The coker overhead products are predominantly distillable oils (~93 wt % 975°F⁻, Table 6); in fact, about 80% of the oils boil below 850°F. The coker overhead oils have a higher hydrogen content (even on an ash-free basis) and lower heteroatom content than their feedstocks. The coker overhead oils contain substantial concentrations of hydroaromatics, n-paraffins are present and there is significant alkylation of ring systems. GC/MS analysis reveals that the coker overhead oils, particularly the one from Test 2 which was conducted at thermally milder coker conditions, are not very dissimilar from the distillate portion of the respective feedstocks. Therefore, we conclude that the predominant mechanism for production of the coker overhead oils is steam-stripping/steam-distillation. Products also are made by a cracking/coking mechanism, particularly in Test 1, which was made at thermally more severe conditions; but this mechanism is clearly less dominant. In many respects, this is the same behavior observed in batch coker tests conducted by Lummus-Crest, Inc.^{6,7} (but not in the later Lummus continuous coker tests⁵). HRI's yield data support this interpretation: the feedstocks were predominantly distillates, only about 33% of the ash-free feedstocks were 975°F⁺ resid (Table 4), and only about 32% of that resid was converted in the coker. Therefore, of the total ash-free coker product (ash-free coke plus overhead oil plus gas) only about 11% of it was created by resid conversion and about 2% of that was gases.

The coker overhead oils are clearly poor donor solvents. Hydrotreating improves their solvent quality; however, their quality as donor solvents remained below those of the respective PFLs in our hydrotreating tests (Table 13). Though our hydrotreating tests were not optimized, the possibility of substantial additional improvement in solvent quality by more extensive hydrotreating is questionable in light of the low aromaticities of our hydrotreated oils (Table 8). The distillable and

aliphatic natures of the coker overhead oil (and therefore of its hydrotreated product) appear to limit solvent quality in this case.

Depending on the flows of the individual streams in an integrated CTSL-coker system, the coker overhead oils could become a substantial portion of the recycle oil stream. If that were the case, then the recycle oil would be lower boiling and could be of lower solvent quality, even after hydrotreating in the reactors, than the recycle oil used in the current CTSL system. The impact of such a change in the recycle oil on the CTSL system is unknown. Of course, any impact would be reduced as the coker overhead oil stream becomes a smaller constituent of the recycle oil.

CONCLUSIONS

It generally can be concluded that the use of delayed coking for the removal of solids from the process stream of the continuous two-stage liquefaction unit and recycle of the coker overhead oil product so produced is possible. There are, however, constraints imposed on the process by the poor solvent quality of the coker overhead oil. The coker overhead oils are amenable to upgrading by hydrogenation; tests indicate that hydrogenation can improve the solvent quality of the coker overhead oils. However, the distillable and aliphatic nature of the coker overhead oils examined here may limit the solvent quality attainable by hydrotreating.

SOLVENT QUALITY OF MALTENES

SUMMARY

Experiments were conducted to address a suggestion by Mr. Ted Simpson (U.S. DOE/HQ) concerning solvent quality of recycle solvents in coal conversion.^{8,9} The experiments entail isolation of the oils or "maltene" fraction (operationally defined as hexane solubles) of an 850°F⁺ distillation resid, and use of this material as the solvent in a microautoclave conversion test. The distillate portion (850°F⁻) of the whole oil and a mixture of the maltenes and the distillate also were used as solvent. Coal conversion was compared to that when the whole oil from which the resid was derived and the tetrahydrofuran (THF) soluble portion of the same distillation resid from which the maltenes were extracted were used as solvents.

Results indicate that, at the conditions tested, the maltene fraction is a better agent for coal conversion than the whole recycle oil, the tetrahydrofuran soluble portion of the distillation resid, or the distillate of the whole oil. A 50/50 mixture of the maltenes and the distillate was as effective as the maltenes alone.

These results are consistent with many past observations of the benefit of residual oils as liquefaction media. Work by Consol in the late 1970's with "Light SRC" generated by the Kerr-McGee CSD process produced equivalent results. In that case, it was possible to exploit the results by replacing a portion of the all-distillate SRC recycle solvent with "Light SRC", thus improving solvent quality.^{10,11} With the current ITSL process configuration, it is less clear how to make practical use of these observations, because all of the available residual product is recycled in the current process. That is, there is no place in the process to obtain more maltenes. It may be possible to produce a higher maltene content in the recycle oil by adjusting process conditions to effect greater asphaltene and preasphaltene conversion. However, it is likely that such conditions would result in higher overall resid conversion, and, in fact, reduce maltene yield. Finally, it is worth

emphasizing that the results reported here show a relative difference at conditions far removed from actual ITSL process conditions. Although these differences are real, their practical significance is not easily projected to ITSL process performance.

RESULTS AND DISCUSSION

The chemical composition and physical properties of the recycle solvent can affect the overall behavior of a coal liquefaction process. Solvent quality (SQ) is an operationally-defined term that generally refers to the influence of the solvent on the extent and rate of coal conversion. Improving solvent quality for coal conversion in a two-stage liquefaction process was addressed by Mr. T. Simpson (DOE/HQ).⁸ He surmised that the only component of the non-distillate resid that contributes to solvent quality is the hexane-soluble oils (the maltenes). In order to evaluate his hypothesis, he outlined two tests to be performed. He proposed that, following solvent extraction of the maltenes from a sample of a recycle oil resid, the maltenes be used as the solvent in a microautoclave SQ assay. The second experiment would utilize the same maltene material blended with some of the distillate from the whole oil. SQ would be compared to that of the whole oil (corrected for ash and IOM).

The maltene fraction of the 850°F⁺ distillation resid of a V-131B sample from Wilsonville Run 260C was isolated by Soxhlet extraction in hexane. In order to produce sufficient material for the intended work, maltenes were isolated from the 850°F⁺ resid of the V-131B samples taken on both 9/4/90 and 9/5/90. The maltenes from the two resid samples were blended. The maltene fraction comprised 34 wt % of the starting resid. The resid fraction (including ash and insoluble organic material) was 76.2 wt % of the whole oil; the maltenes were thus 25.9 wt % of the whole oil. Analyses of the whole oil, resid, THF soluble portion of the resid, distillate, and the maltenes are given in Table 14.

The proton distribution of the maltene fraction is similar to that of the whole oil from which it is derived. The relatively large proportion of condensed aromatic hydrogen as compared to the distillate fraction

indicates that the maltenes should have better physical solvating properties than the distillate for coal in conversion processes. Additionally, the large percentage of alkyl β protons in the distillate (which are indicative of a large paraffinic content) are predictive of lower solvent quality for the distillate. The phenolic -OH content of the maltenes is lower than that of the THF-soluble resid, but comparable to that of the 850°F⁻ distillate. The phenolics present in the 850°F⁺ resid and its maltenes fraction are higher in molecular weight than those which are found in the distillate. These residual phenolic molecules can participate in the same chemical reactions, such as alkylation reactions, as the lower molecular weight phenols found in the distillate. The larger concentration of phenols present in the total THF-soluble resid (about 1.7 times higher concentration than in the maltenes) increases the likelihood of unfavorable reactions in which the heavier phenolic compounds react to form THF insolubles, or consume hydrogen to remove oxygen.¹² It can thus be predicted, based on these comparisons, that the maltenes should be a better solvent for coal conversion than the THF soluble resid or distillate fraction of the whole oil.

Five microautoclave experiments were run. The first three experiments used the whole oil, THF soluble portion of the whole oil, and the distillate of the whole oil as solvent. The fourth and fifth microautoclave experiment used 100% maltenes and a mixture of 50 wt % maltenes and 50 wt % 850°F⁻ distillate of the same oil from which the maltenes were derived. Results of all five microautoclave experiments are given in Table 15. The non-distillable oils (maltenes) give higher coal conversion than the whole oil, distillate, or the THF soluble portion of the resid. The mixture of maltenes and distillate gave a coal conversion equivalent to that obtained with the maltenes alone.

It appears that the maltenes, as predicted, are good solvents for coal conversion. Presuming that these results apply to the general case, then increasing the concentration of these materials in the recycle oil should, all other parameters held constant, increase the solvent quality of the recycle oil.

EXPERIMENTAL

Whole recycle oil samples (V-131B) from Wilsonville Run 260 period C were distilled to produce resid and distillate in a 1" x 3' jacket-heated Vigreux column to an end-point of 320°C pot/270°C column/5 torr (850°F equivalent). Tetrahydrofuran (THF) soluble material was produced by pressure filtration with freshly distilled THF through Whatman No. 42 paper at ambient temperature. The filter cake was washed with THF until the filtrate was colorless. The THF was removed from the filtrate by distillation.

Maltenes (hexane solubles) were isolated from the 850°F⁺ resid fractions of recycle oil (V-131B) from Wilsonville Run 260C. Samples of recycle oil taken at Wilsonville on two consecutive days (9/4/90 and 9/5/90) were used. The other fractions were all produced from the 9/5/90 sample. The maltenes were isolated by Soxhlet extraction of the resid; extractions required between eight and fourteen days. The maltenes were dried of hexane by roto-evaporation and were left in a vacuum oven for a minimum of 3 hours at 110°C before use. Analyses of the maltenes, the starting oil, the 850°F⁺ resid, the THF-soluble portion of the resid, and the distillate are given in Table 14.

Microautoclave experiments were performed at the modified equilibrium conditions: 9g solvent, 6g coal, 750°F, 30 min.¹³ All experiments used Old Ben No. 1 Mine coal. Each reported result represents a single test. The reproducibility of coal conversion in this test is 1.2% absolute.¹³

ANALYSES OF WILSONVILLE RUN 259G NET PRODUCT AND PRODUCT FRACTIONS

The Wilsonville Run 259G net product oil (crude oil) and its three distillation fractions were returned to Consol by Conoco Petroleum Products Research Division in December 1990 after Conoco completed the modified light oil assay tests on them.⁹ Consol determined the phenolic -OH concentrations in the crude and its fractions by FTIR spectroscopy. Each material also was analyzed by gas chromatography/mass spectrometry (GC/MS) for further characterization.

PROCEDURE

The phenolic -OH concentrations were determined by our customary procedure.¹⁴ GC/MS analyses were performed with a HP 5970 system equipped with a 30 m x 0.25 mm DB-5 column (0.25 μ m film thickness). For the crude, jet fuel and diesel fuel fractions, the GC conditions were: injection port at 300°C; column 5 min @ 35°C then to 100°C at 35°C/min, then to 320°C @ 4°C/min; 20 psig of He carrier gas; scan from 45 to 300 amu. For the naphtha fraction, the GC conditions were 5 min @ 10°C then to 100°C @ 2°C/min, then to 320°C @ 4°C/min. Splitless injection was used. The naphtha was injected neat, the other fractions were injected as 1% solutions in tetrahydrofuran. The mass spectra were searched against the Wiley/NBS mass spectral library.

GC/MS RESULTS

The total ion chromatograms are shown in Figures 4 through 7. Identifications of prominent peaks are provided in a key immediately following Figure 7. The predominant cyclic nature (naphthenic, aromatic, hydroaromatic) of the components of these materials is apparent; virtually none of the major peaks are normal or branched paraffins.

PHENOLIC -OH CONCENTRATIONS

The phenolic -OH concentrations and the phenolic and total oxygen contents of the crude and its three fractions are listed below. The phenolic oxygen content is calculated from the determined phenolic -OH

concentration. The total oxygen content shown is a by-difference value from the Conoco analyses.⁹

Fraction	Phenolic -OH Concentration, meq/g	Oxygen Content, wt %	
		Phenolic	Total (diff.)
Naphtha	0.18	0.29	1.3
Jet Fuel	0.25	0.40	1.4
Diesel Fuel	0.13	0.21	0.9
Crude	0.18	0.29	1.4

The phenolics are concentrated in the jet fuel fraction; as was observed by other workers¹⁵ with different coal-derived syncrudes. The weighted average phenolic -OH concentration of the three fractions (calculated with Conoco's fraction yields⁹) exactly equals the phenolic -OH concentration of the crude.

CALIBRATION AND ANALYSIS OF STANDARD COAL

Routine microautoclave solvent quality assays are made with a single standard coal: Old Ben No. 1 Mine, Indiana V seam. The currently used batch of coal was received in November 1988. In April 1990, this coal batch was found to be rapidly deteriorating and it was repacked for long-term storage in air-tight, N₂-purged plastic bags in batches of 500g.¹⁶ At the time of sealing, the coal was retested. Reported here are the chemical analyses and microautoclave test results from a recently opened plastic bag (March 1991). Comparison is made to the analyses of the as-received coal (November 1988) and the analyses made upon sealing the coal in April 1990.

The degree of deterioration of the coal sample via weathering is indicated by alteration in the oxygen functional-group distribution and an increase in total and organic oxygen content.¹⁷ Pyritic sulfur is known to slowly convert to sulfate, and this often is the only perceptible change in the chemical analysis of the coal sample. The analyses given in Table 16 show that the coal, since repacking in April 1990, has oxidized only slightly, if at all. There is an approximately 0.5% increase in total oxygen, determined by difference, and a small increase in sulfate sulfur (<0.1%). There was no change in calorific value. This is in sharp contrast to the large degree of oxidation which occurred between receipt of the sample in November 1988 and retesting in April 1990.¹⁶

Generally, it has been found that oxidation results in a decrease in liquefaction yields.^{18,19} In order to determine the relative decline in performance of this coal, batch microautoclave tests have been periodically made using this coal and solvents containing varying ratios of tetralin and 1-methylnaphthalene. Three commonly used sets of test conditions were employed.¹³ The results of the most recent tests, and tests made thirteen months earlier, are given in Table 17. The coal conversions found from these tests can be used as reference points for liquefaction solvents tested with this coal. Similar data for earlier (1979 and 1981) batches of the same coal were previously reported.^{10,13,14,20}

The repeatability of the microautoclave assay was shown to have a standard deviation of 1.2% absolute.¹³ Therefore, comparison with the sample analyzed in February 1990 shows no significant change in coal conversion in the analyses performed in March 1991. There does appear to be a consistent, although small, increase in coal conversion with the March 1991 sample as compared with the February 1990 sample, in the kinetic test, at all but one solvent ratio. This could be attributed to operator bias.

Although the oxidation of the coal samples may not have completely halted, its rapidity has abated. The limited oxidation which has occurred in the last thirteen months has not affected the coal conversion yield results from microautoclave tests. Additional tests will be conducted at intervals over the duration of this contract to further monitor any change in reactivity of the coal.

PARTICIPANTS PROGRAM STATUS

Substantial progress was made in the Participants Program this quarter. All remaining proposed Phase I subcontracts were initiated with the exception of Battelle Pacific Northwest Laboratories (PNL) (see below). Table 18 is a list of all participating organizations for Phase I and the start dates for their respective subcontracts. Sample sets were assembled and shipped to all contracted organizations. A list of all samples which will be examined in Phase I of the Participants Program can be found in Table 19. Analytical data for those samples were collected and issued to the subcontractors. Processing information for each subcontractor's sample set was also assembled and sent.

DOE approval for a subcontract with Battelle PNL was not granted because Battelle is a National Laboratory and, therefore, is not eligible for funding under this contract. A field work proposal was initiated instead after tentative approval was given by DOE for such an arrangement. Consol now is awaiting initiation of the DOE/Battelle agreement to implement the Statement of Work.

The University of Kentucky/Center for Applied Energy Research (UK/CAER) completed the experimental portion of their subcontract. A draft final report was received from them. We met with F. J. Derbyshire (Director, UK/CAER) and discussed the work. We corresponded with the principal author, Robert Rathbone, and suggested some changes to the report. The final version is expected from UK/CAER early next quarter.

The second sample of synthetic crude oil from Wilsonville Run 260D was sent to Conoco Petroleum Products Research Division for analysis. The test plan was altered from that used for the first sample (Wilsonville Run 259G) in the following way: 1) the diesel fuel fraction will be cut at 650°F, 2) a number of analyses will be obtained for the 650°F+ sample, 3) acidity will be determined on the three primary product fractions, 4) the JFTOT test will be deleted, 5) Consol will caustic wash aliquots of the three primary fractions and analyze the extracts by GC/MS.

The analytical Needs Assessment was completed, received DOE technical and patent approval, and was issued as a Topical Report.

A procedure was established for issuance of the findings of each subcontractor in the Participants Program. Consol will furnish an overview for each subcontractor. These overviews will accompany the subcontractors' executive summaries and will be included in Consol's Quarterly Technical Progress Reports. In addition, the subcontractors' complete final reports will issue as Topical Reports under this contract.

Section 3

REFERENCES

1. Brandes, S. D.; Winschel, R. A.; Robbins, G. A.; Burke, F. P. "Coal Liquefaction Process Streams Characterization and Evaluation - Quarterly Technical Progress Report, July 1 through September 30, 1990", DOE/PC 89883-23, June 1991.
2. Comolli, A. G.; Johanson, E. S.; Panvelker, S. V.; Popper, G. A.; Smith, T. O. "Two-Stage, Close-Coupled Catalytic Liquefaction of Coal - Sixth Quarterly Report for the Period 1 January 1990 - 31 March 1990", DOE Contract No. DE-AC22-88PC88818, September 1990.
3. Comolli, A. G.; Johanson, E. S.; Panvelker, S. V.; Popper, G. A.; Smith, T. O. "Two-Stage, Close-Coupled Catalytic Liquefaction of Coal - Seventh Quarterly Report for the Period 1 April 1990 - 30 June 1990", DOE Contract No. DE-AC22-88PC88818, in preparation.
4. Comolli, A. G.; Johanson, E. S.; Panvelker, S. V. "CTSL Process Studies", Proceedings of the 1990 DOE Direct Liquefaction Contractors' Review Meeting, Pittsburgh, PA, September 24-26, 1990.
5. Winschel, R. A.; Burke, F. P. "Recycle Oils from Fluid Coking of Coal Liquefaction Bottoms", *Energy and Fuels* 1989, 3, 437-443.
6. Riegel, H.; Stavropoulos, N. "Batch Bench Coking Under Fluid Coking Conditions". Report to Burns and Roe Services Corp. under U.S. DOE Contract No. DE-AC22-84PC72571, August 1987.
7. Stavropoulos, N.; Riegel, H.; Suci, D. "Coking of Coal Liquefaction Bottoms, Batch Bench Coking Tests", Presented at the DOE Direct Liquefaction Contractors' Review Meeting, Pittsburgh PA, October 1987.
8. T. Simpson, Letter to R. A. Winschel, July 6, 1990.
9. Brandes, S. D.; Winschel, R. A.; Robbins, G. A.; Burke, F. P. "Coal Liquefaction Process Streams Characterization and Evaluation, Quarterly Technical Progress Report, October 1 through December 31, 1990", DOE/PC 89883-24, June 1991.
10. Kleinpeter, J. A.; Burke, F. P.; Dudt, P. J.; Jones, D. C. "Process Development for Improved SRC Options: Interim Short Residence Time Studies", Interim Report, EPRI Project 1134-1, EPRI AF-1158, August 1979.
11. Kleinpeter, J. A.; Burke, F. P.; Dudt, P. J.; Jones, D. C. "Process Development for Improved SRC Options: Short Residence Time Studies", Final Report, EPRI Project 1134-1, EPRI AP-1425, June 1980.

12. Whitehurst, D. D.; Mitchell, T. O.; Farcasiu, M. "Coal Liquefaction, the Chemistry and Technology of Thermal Processes", Academic, New York, 1980.
13. Burke, F. P.; Winschel, R. A.; Robbins, G. A. "Recycle Slurry Oil Characterization Final Report, October 1980 through March 1985", DOE Contract DE-AC22-80PC30027, March 1985.
14. Winschel, R. A.; Robbins, G. A.; Burke, F. P. "Coal Liquefaction Process Solvent Characterization and Evaluation, Technical Progress Report, July 1985 through September 1985", DOE Contract DE-AC22-84PC70018, December 1985.
15. Zhou, P.; Rao, S. N. "Assessment of Coal Liquids as Refinery Feedstocks (Interim Report)", November 1990, DE-AC22-89PC88400, in preparation.
16. Robbins, G. A.; Brandes, S.D.; Winschel, R. A.; Burke, F. P. "Coal Liquefaction Process Streams Characterization and Evaluation, Technical Progress Report, January 1 through March 31, 1990", DOE Contract DE-AC22-89PC89883, February 1991.
17. Liotta, R.; Brons, G.; Isaacs, J. "Oxidative Weathering of Illinois No. 6 Coal", *Fuel* 1983, 62, 781.
18. Chang, C. Y., Guin, J. A., Tarrer, A. R., *J. Chinese Chemical Society* 1981, 28, 155.
19. Cronauer, D. C. "The Influence of Coal Aging and Oxidation on Liquefaction" presented at the Japan/U.S. NSF Chemistry of Coal Liquefaction Meeting, 1982.
20. Winschel, R. A.; Robbins, G. A.; Burke, F. P. "Coal Liquefaction Process Solvent Characterization and Evaluation, Technical Progress Report, January 1 through March 31, 1988", DOE Contract DE-AC22-84PC70018, March 1989.
21. Winschel, R. A.; Robbins, G. A.; Burke, F. P., *Fuel* 1986, 65, 526-532.

TABLE 1
ANALYSES OF FEED COALS
HRI Run CC-9³

Condition Run Period Coal	1 16-19 Illinois No. 6	2 20-23 Illinois No. 6
Coal Type HRI No.	Mine Cleaned 5739	OTISCA Cleaned 5743
<u>Wt. %, Dry Basis</u>		
Carbon	68.78	76.05
Hydrogen	4.69	5.21
Nitrogen	1.35	1.44
Sulfur	3.37	2.68
Oxygen (diff.)	11.04	11.04
Ash	10.77	3.58
S in Ash	1.54	1.55
SO ₃ -Free Ash	10.36	3.44

/ls

TABLE 2
RUN CONDITIONS
HRI Run CC-9³

Condition Run Period	1 16-19	2 20-23
Coal Type HRI No.	Mine Cleaned 5739	OTISCA Cleaned 5743
Back Pressure, psig	2,800	2,800
Space Velocity, lb coal/hr/ft ³ Catalyst (each stage)	67	67
First Stage Temperature, °F	755	780
Second Stage Temperature, °F	805	815
Recycle Oil/MF Coal Ratio	2	2

/ls

TABLE 3
ANALYSIS OF MAKE-UP OILS
HRI Run CC-9³

Condition HRI No.	1 and 2 L-756	2 5648
°API	12.9	5.7
Carbon, wt %	87.99	90.14
Hydrogen, wt %	11.04	9.85
Nitrogen, wt %	0.33	0.37
Sulfur, wt %	0.01	0.06
Oxygen (diff.), wt %	0.63	-0.42
<u>D-1166 Distillation Temp., °F</u>		
IBP	---	735
5 vol. %	---	776
10 vol. %	519	798
20 vol. %	564	810
30 vol. %	599	830
40 vol. %	627	824
50 vol. %	656	858
60 vol. %	690	876
70 vol. %	723	888
80 vol. %	762	902
90 vol. %	854	930
95 vol. %	---	952
FBP	---	1008

/1s

TABLE 4
 DELAYED COKER FEEDSTOCK (CAS BOTTOMS) PROPERTIES
 HRI Run CC-9³

Feedstock to Coker Test No. Condition Number of Run CC-9 Run Periods	1 1 16-19	2 2 20-23
°API Gravity	-1.5	-0.5
IBP, °F	549	500
IBP x 650°F, wt %	10.00	15.00
650 x 850°F, wt %	41.51	40.09
850 x 975°F, wt %	12.40	10.74
975°F ⁺ , wt %	36.09	34.17
Carbon, wt %	84.18	85.69
Hydrogen, wt %	9.22	9.27
Nitrogen, wt %	0.49	0.55
Sulfur, wt %	0.56	0.52
Oxygen (diff.), wt %	0.68	0.86
Ash, wt %	4.87	3.11
Quinoline Insol., wt %	11.35	8.46
Toluene Insol., wt %	13.10	12.05
Pentane Insol., wt %	23.77	21.83
CCR (Liquid), wt %	8.54	7.64

/1s

TABLE 5
 DELAYED COKING TEST CONDITIONS AND YIELDS
 HRI Run CC-9^{3,4}

Coker Test No.	1	2
<u>Operating Conditions</u>		
Coke Drum Pressure, psig	Base	Base
Steam/Feed Ratio	Base	2X Base
Average Drum Temperature, °F	Base	Base -25
<u>Normalized Yields, wt %</u>		
Gas	3.65	3.07
Overhead Oil	75.53	78.56
Coke (IOM + Ash)	20.82	18.37
H ₂	0.33	0.22
H ₂ S	0.02	0.01
CO + CO ₂	0.06	0.15
C ₁ - C ₃	2.37	1.83
C ₄	0.60	0.58
C ₅	0.27	0.29
IBP x 650°F	19.86	17.38
650 x 850°F	38.81	44.12
850 x 975°F	11.66	11.40
975°F ⁺ liquids	5.19	5.66
IOM	15.95	15.26
Ash	4.87	3.11
<u>Net Yields as wt % Quin. Sol. 975°F⁺ in Feed</u>		
Net C ₄ x 975°F Yield	29.51	30.87
Net H ₂	1.33	0.87
Net H ₂ S	0.08	0.03
Net CO + CO ₂	0.23	0.57
Net C ₁ - C ₃	9.60	7.10
Net C ₄	2.44	2.26
Net C ₅	1.07	1.11
Net IBP x 650°F	39.87	9.25
Net 650 x 850°F	-10.89	15.68
Net 850 x 975°F	-2.98	2.57
<u>Process Performance</u>		
Yield of IBP x 975°F ⁺ sols. as wt % of feed	75.53	78.56
Yield of IBP x 975°F ⁺ sols. as wt % of feed coals	85.20	85.83
Conversion of 975°F ⁺ quin. sols. to coke, wt %	38.28	38.53
Conversion of 975°F ⁺ organics	32.29	32.64

71s

TABLE 6
COKER OVERHEAD PRODUCT ANALYSIS
HRI Run CC-9³

Coker Test No.	1	2
°API	9.5	10.2
IBP, °F	364	419
IBP x 650°F, wt %	26.30	22.12
650 x 850°F, wt %	51.39	56.16
850 x 975°F, wt %	15.44	14.51
975°F ⁺ , wt %	6.87	7.21
Carbon, wt %	89.00	88.95
Hydrogen, wt %	10.13	10.51
Nitrogen, wt %	0.36	0.29
Sulfur, wt %	0.39	0.11
Oxygen (diff.), wt %	0.12	0.14

/1s

TABLE 7
COKE ANALYSIS
HRI Run CC-9³

Coker Test No.	1	2
Carbon, wt %	71.15	78.26
Hydrogen, wt %	2.83	3.07
Nitrogen, wt %	1.02	1.23
Sulfur, wt %	1.86	1.89
Oxygen (diff.), wt %	2.09	0.31
Ash, wt %	21.05	15.24

/1s

TABLE 8
ANALYSES OF PFLs, CORRESPONDING COKER OIL PRODUCTS,
AND HYDROTREATED COKER OIL PRODUCTS
HRI Run CC-9

Coker Test No.	1			2		
Sample	PFL	Coker Overhead Product	Hydrotreated Coker Product (a)	PFL	Coker Overhead Product	Hydrotreated Coker Product (a)
Sample No.	5706	5708	5708-H	5707	5709	5709-H
<u>Ultimate Analysis,</u> <u>wt % as det.</u>						
C	88.03	87.50	88.93	88.06	88.09	88.68
H		9.80	10.68	9.16	10.10	10.68
N	9.52	0.24	0.09	0.38	0.19	0.09
S	0.39	0.28	<0.03	0.16	0.07	<0.03
O (by diff.)	0.12	2.18	0.27	2.24	1.55	0.52
Ash	1.94	<0.01	---	0.07	<0.01	---
	0.07					
<u>Proton Dist., %</u>						
Cond Arom.	9.6	13.1	7.2	10.6	10.8	7.2
Uncond Arom.	3.2	3.3	3.5	3.7	3.5	3.7
Cyclic Alpha	14.5	12.0	12.6	15.0	12.8	13.7
Alkyl Alpha	8.5	8.7	8.2	8.9	8.4	8.6
Cyclic Beta	21.6	19.8	22.6	20.5	20.9	23.0
Alkyl Beta	26.4	26.5	29.1	25.5	27.3	27.1
Gamma	16.2	16.5	16.8	25.8	16.3	16.7
Phenolic -OH (meq/g)	0.31	0.27	0.06	0.41	0.27	0.06

(a) Blend of products from three identical hydrotreating experiments.

/1s

TABLE 9

RESULTS OF APPLYING CORRELATIONS BETWEEN ¹H-NMR DATA
AND MICROAUTOCLAVE SOLVENT QUALITY ASSAYS TO PFLs,
COKER OVERHEAD OILS AND HYDROTREATED COKER OVERHEADS
HRI Run CC-9

Microautoclave Test	Predicted Coal Conversion, wt % MAF					
	Test 1			Test 2		
	PFL	Coker Overhead Oil	Hydrotreated Coker Overhead	PFL	Coker Overhead Oil	Hydrotreated Coker Overhead
EQ Test	71.8	67.3	65.6	73.0	67.6	71.2
KIN Test	69.5	69.0	66.0	70.6	68.1	68.7
Mod-EQ Test	82.7	78.0	81.1	82.3	80.0	83.0

Note: Correlations, from Reference 21, developed for distillate coal liquefaction oils,, not resid containing oils or coker oils. Thus, these data are only useful for discerning trends.

/ls

TABLE 10
SOLUBILITY FRACTIONATION OF PFLs
AND CORRESPONDING COKER OVERHEAD OIL PRODUCTS
HRI Run CC-9

	Solubility Fractions, wt %			
Coker Test No.	1		2	
Sample	PFL	Coker Overhead Product	PFL	Coker Overhead Product
Sample No.	5706	5708	5707	2709
Oils	67.3	92.0	69.7	93.3
Asphaltenes	13.6	7.6	16.7	5.6
Preasphaltenes	19.1	0.4	13.6	1.1

NOTE: The LCF technique used to obtain these data was devised for non-distillable samples. Therefore, these data are useful to observe trends, but may not be quantitatively accurate.

/ls

TABLE 11
IDENTIFICATION OF SELECTED PROMINENT PEAKS IN FIGURE 2

Peak No.	Identification	Peak No.	Identification
1	Hexahydropyrene	20	Methylpyrene
2	Hexahydropyrene	21	Methylpyrene
3	Dihydropyrene	22	Methylbenzophenanthrene
4	Pyrene	23	Unknown
5	Methylpyrene	24	Tetralin
6	Methylpyrene	25	Methyltetratin
7	Methylbenzophenanthrene	26	Tetrahydroacenaphthene
8	Xylene	27	Methyltetrahydroacenaphthene
9	Unknown	28	Dibenzofuran
10	Cresol	29	Octahydrophenanthrene
11	Cresol	30	Hexahydropyrene
12	Naphthalene	31	Hexahydropyrene
13	Methylnaphthalene	32	Dihydropyrene
14	Acenaphthene	33	Pyrene
15	Dibenzofuran	34	Phenylmethylnaphthalene
16	Fluorene	35	Methylpyrene
17	Phenanthrene	36	Methylbenzophenanthrene
18	Fluoranthene		
19	Pyrene		

- Peak identifications based on searches of the Wiley/NBS Database and Consol's library of coal-derived compounds.
- GC/MS Conditions: Column - 30m x 0.25mm fused silica with DB5 coating
Temperature Program - 35-100°C @ 35°/min
100-320°C @ 4°/min
Mass Spec - 45-300 amu scan, 70 eV

/ls

TABLE 12
IDENTIFICATION OF SELECTED PROMINENT PEAKS IN FIGURE 3

Peak No.	Identification	Peak No.	Identification
1	Hexahdropyrene	16	Pyrene
2	Hexahdropyrene	17	Methylpyrene
3	Dihdropyrene	18	Methylpyrene
4	Pyrene	19	Methylbenzanthracene
5	Methylpyrene	20	Tetralin
6	Methylpyrene	21	Methyltetralin
7	Methylbenzoanthracene	22	Dimethylbiphenyl
8	Cresol	23	Hexahdropyrene
9	Cresol	24	Hexahdropyrene
10	Naphthalene	25	Dihdropyrene
11	Methyltetralin	26	Pyrene
12	Methylnaphthalene	27	Unknown
13	Alkane	28	Methylpyrene
14	Methylbiphenyl	29	Methylbenzophenanthrene
15	Dimethylbiphenyl		

- Peak identifications based on searches of the Wiley/NBS Database and Consol's library of coal-derived compounds.
- GC/MS Conditions: Column - 30m x 0.25mm fused silica with DB5 coating
Temperature Program - 35-100°C @ 35°/min
100-320°C @ 4°/min
Mass Spec - 45-300 amu scan, 70 eV

/ls

TABLE 13
 MICROAUTOCLAVE TESTS OF PFLs, COKER OVERHEAD OILS
 AND HYDROTREATED COKER OVERHEADS
 HRI Run CC-9

Test	Sample	Sample No.	Coal conv., wt % to THF Solubles
1	PFL Feed	5706	84.5
	Coker Overhead Product	5708	65.1
	Hydrotreated Coker Overhead	5708H	73.9
2	PFL Feed	5707	85.8
	Coker Overhead Product	5709	71.1

Conditions: Mod-EQ test; 6g Old Ben Mine No. 1 coal, 9g solvent, 30 mL microautoclave, 30 min, 750°F

/ls

TABLE 14
SAMPLE ANALYSES
Wilsonville Run 260C, V-131B

Sample	Proton Distribution of Soluble Material, %						
	Cond Arom	Uncond Arom	Cyclic Alpha	Alkyl Alpha	Cyclic Beta	Alkyl Beta	Gamma
Whole Oil (a)	24.7	3.4	18.1	8.5	14.6	19.3	11.5
Resid (a)	31.0	3.6	20.3	8.7	14.0	14.0	8.3
THF-Soluble Resid (a)	32.6	2.8	20.2	8.7	13.8	14.2	7.6
Distillate (b)	13.3	5.0	14.3	8.2	14.7	30.9	13.3
Maltene (a)	27.4	4.4	18.4	8.5	14.4	17.3	9.5

Sample	Phenolic -OH	Yield, % of Whole Oil	Ultimate Analysis					
	Conc, meq/g	wt %	% Determined					
			C	H	N	S	O (diff)	Ash
Whole Oil	-	100.0	77.53	6.14	0.77	1.26	0.90	13.4 (c)
Resid	-	76.2						
THF-Soluble Resid	0.65	56.3	90.75	6.49	0.99	<0.03	1.74	
Distillate	0.43	21.4	89.06	9.65	0.43	<0.03	0.83	
Maltene	0.38	25.9	90.35	7.32	0.61	<0.03	1.69	

(a) NMR Solvent - C₅D₅N

(b) NMR Solvent - CDCl₃

(c) In addition to ash, this sample contains 6.5% THF-insoluble organic matter.

TABLE 15
MICROAUTOCLAVE COAL CONVERSIONS
Wilsonville Run 260C, V-131B

<u>Sample</u>	<u>Coal Conversion, wt % MAF</u>
Whole Oil	59.0 (a)
THF-Soluble Resid	61.3
Distillate	77.8
Maltene	81.2
50:50 Maltene:Distillate	82.5

(a) MAF coal basis

Conditions: Mod-EQ test

TABLE 16
ANALYSIS OF 1988 BATCH OF OLD BEN NO. 1 MINE, INDIANA V COAL

	Sample Date		
	11/88 (a)	4/90 (b)	3/91 (c)
<u>Moisture, wt % as determined</u>	8.67	8.24	7.69
<u>Proximate, wt % dry basis</u>			
Volatile Matter	41.24	41.17	41.29
Fixed Carbon	49.53	49.69	49.65
Oxidized Ash	9.23	9.14	9.06
<u>Ultimate, wt % dry basis</u>			
Carbon	71.35	71.91	71.11
Hydrogen	5.04	4.98	4.99
Nitrogen	1.43	1.49	1.38
Oxygen (diff.)	9.03	8.70	9.57
Sulfur, Total	3.87	3.78	3.85
Pyritic	1.59	1.04	1.15
Sulfate	0.10	0.57	0.66
Organic (diff.)	2.18	2.17	2.04
Chlorine	0.05	N/A	0.04
Oxidized Ash	9.23	9.14	9.06
<u>Elemental, wt % oxidized ash</u>			
Na ₂ O	0.44		0.55
K ₂ O	2.12		2.21
CaO	4.78		4.86
MgO	0.81		0.83
Fe ₂ O ₃	26.94		27.32
TiO ₂	0.89		0.92
P ₂ O ₅	0.18		0.18
SiO ₂	39.57		39.44
Al ₂ O ₃	18.82		19.17
SO ₃	3.12		3.30
Unaccounted	2.33		1.22
<u>Calorific Value, dry (HHV), Btu/lb</u>	13,154	12,799	12,788

(a) As-received sample

(b) Sample stored in plastic bucket

(c) Sample stored (from 4/90) in heat-sealed, nitrogen-purged, plastic bag.

/ls

TABLE 17
MICROAUTOCLAVE CALIBRATION TESTS

Test and Date Performed	% MAF Coal Conversion in Microautoclave with Specified Solvent Composition (% Tetralin/% 1-Methylnaphthalene)					
	0/100	5/95	10/90	25/75	50/50	100/0
KIN						
2/90	55.0	63.9	68.1	75.8	76.1	71.8
3/91	57.2	65.3	69.6	74.9	77.1	72.4
EQ						
2/90	48.9	60.7	68.4	72.5	81.1	85.9
3/91	49.6	60.3	68.0	74.2	82.3	85.7
Mod-EQ						
2/90	48.7	57.4	63.5	71.7	82.8	87.3
3/91	48.7	55.3	63.2	71.2	80.6	88.3

Conditions: KIN (Kinetic Test) - 750°F, 10 min, 12g solvent, 1.5g coal
EQ (Equilibrium Test) - 750°F, 30 min, 10g solvent, 5g coal
Mod-EQ (Modified Equilibrium Test) - 750°F, 30 min, 9g solvent, 6g coal

Coal: Old Ben No. 1 Mine, Indiana V seam, 1988 batch.

/ls

TABLE 18
PARTICIPANTS PROGRAM SUBCONTRACTING STATUS

Contractor	Start Date	Duration	Close Date
Conoco Petroleum Products Research Div.	8/90	~11 Months	~7/91
University of Kentucky/Center for Applied Energy Research	11/15/90	4 Months	3/15/91
The Pennsylvania State University	12/15/90	6 Months	6/15/91
Virginia Polytechnic Institute	1/15/91	6 Months	7/15/91
Western Research Institute	12/10/90	4 Months	4/10/91
Advanced Fuel Research	3/08/91	6 Months	9/08/91
National Institute for Petroleum and Energy Research	3/15/91	6 Months	9/08/91
SRI International	3/25/91	4 Months	7/25/91

TABLE 19
PARTICIPANTS PROGRAM SAMPLE SET FOR PHASE I

Wilsonville Pilot Plant Samples

Run	Sample Stream	Date
<u>850°F + Distillation Resid Samples</u>		
250	R-1236	Composite
	V-131B	"
	V-1067	"
251-II	R-1235	"
	V-131B	"
	V-1067	"
251-III	R-1235	"
	V-131B	"
	V-1067	"
257	R-1235	"
	V-131B	"
	V-1067	"
255B	R-1235	"
	V-131B	"
	V-1067	"
256B	R-1235	5/29/88
	V-131B	5/29/88
	R-1067	5/29/88
256E	R-1236	8/27/88
	V-131B	8/27/88
257G	R-1236	10/12/88
	V-131B	10/12/88
257F	V-131B	2/13/89
	V-131B	2/06/89
<u>Tetrahydrofuran-Insoluble Portion of 850°F + Dist. Resids</u>		
250	R-1236	Composite
	V-131B	"
251-III	R-1235	"
	V-131B	"
257	R-1235	"
	V-131B	"
259	R-1235	"
	V-131B	"
<u>Tetrahydrofuran-Soluble Portion of 850°F + Dist. Resids</u>		
250	R-1235	Composite
	V-131B	"
251-III	R-1235	"
	V-131B	"
	V-1067	"
256B	R-1235	8/27/88
	V-131B	8/27/88
256E	R-1236	10/12/88
	V-131B	10/12/88
257	R-1235	Composite
	V-131B	"
	V-1067	"
259	R-1235	"
	V-131B	"
	V-1067	"
260	V-131B	"
<u>Whole Oil Samples</u>		
251-II	V-131B	7/24/86
255	V-131B	5/29/88
257	V-131B	1/18/89
259G	R-1235	5/1/90
	V-131B	5/1/90
	V-1067	5/1/90
	V-161+V-182	5/1/90
<u>THF-Soluble Portion of Whole Oil Samples</u>		
259G	V-131B	5/1/90

TABLE 19 (Continued)
PARTICIPANTS PROGRAM SAMPLE SET FOR PHASE I

HRI Bench Unit Samples

Run	Sample Stream	Date
<u>850°F⁺ Distillation Resid Samples</u>		
I-27	Pressure Filter Liquid	5/09/87
	Pressure Filter Liquid	5/15/87
	Pressure Filter Liquid	5/24/87
	Pressure Filter Liquid	6/01/87
CC-2	1st-Stage Filter Liquid	6/27/89
	Pressure Filter Liquid	6/25/89
CC-5	1st-Stage Filter Liquid	12/04/89
	Pressure Filter Liquid	12/03/89
<u>Tetrahydrofuran-Soluble Portion of 850°F⁺ Distillation Resids</u>		
CC-2	1st-Stage Filter Liquid	6/27/89
	Pressure Filter Liquid	6/25/89
	1st-Stage Filter Liquid	12/04/89
CC-5	Pressure Filter Liquid	12/03/89
<u>Whole Oil Samples</u>		
CC-1	Pressure Filter Liquid	1/89 (day 13)
	First Stage Process Overhead	1/89 (day 14)
	Separator Process Overhead	1/89 (day 13)
	Distillate	
CC-2	Pressure Filter Liquid	6/25/89
CC-5	Pressure Filter Liquid	12/03/89

Lummus Process Development Unit

Run	Sample Stream	Date
<u>850°F⁺ Distillation Resid Samples</u>		
3LCF10	Feed to LC-Finer	1/11/84
3LCF10	Feed to LC-Finer	1/28/84
<u>Tetrahydrofuran-Soluble Portion of 850°F⁺ Distillation Resids</u>		
3LCF10	Feed to LC-Finer	1/11/84
3LCF10	Feed to LC-Finer	1/28/84

Figure 1. HRI Ebullated-Bed Bench Unit 227.
(Excludes Solvent Inventory Tank)

Figure 2. GC/MS Chromatograms of PFL, Coker Overhead Product and Hydrotreated Coker Overhead from Coker Test No. 1, HRI Run CC-9

(NOTE: See Table 11 for peak identifications)

Figure 3. GC/MS Chromatograms of PFL, Coker Overhead Product and Hydrotreated Coker Overhead from Coker Test No. 2, HRI Run CC-9

(NOTE: See Table 12 for peak identifications)

Figure 4. Total Ion Chromatogram, Naphtha Fraction, Wilsonville Run 259G Product.

Figure 5. Total Ion Chromatogram, Jet Fuel Fraction,
Wilsonville Run 259G Product.

Figure 6. Total Ion Chromatogram, Diesel Fuel Fraction, Wilsonville Run 259G Product.

Figure 7. Total Ion Chromatogram, Crude Oil,
Wilsonville Run 259G Product.

KEY TO PEAK IDENTIFICATIONS
Figures 4 through 7

Peak No.	Identification	Peak No.	Identification
1A	Butane	41A	n-Dodecane
1	C ₅ H ₁₀	41	Naphthalene
2	C ₅ H ₁₀	42	C ₂ -Indan
3A	Benzene	43	Methyltetralin
3	Cyclohexane	44	C ₂ -Indan
4	C ₇ H ₁₄	45	C ₂ -Indan
5	Methylcyclohexane	46	Methyltetralin
6	Ethylcyclopentane	47	Methyltetralin
7	Toluene	48A	n-Tridecane
9	Dimethylcyclohexane	48	Methylnaphthalene
10	Dimethylcyclohexane	49	Bicyclohexyl
11	Dimethylcyclohexane	50	Methylnaphthalene
12	Ethylcyclohexane	51	C ₂ -Tetralin
13	Trimethylcyclohexane	52	Ethyltetralin
14	Ethylbenzene	53	Tetrahydroacenaphthene
15	Xylene	54	C ₂ -Tetralin
16	Xylene	55	C ₂ -Tetralin
17	Trimethylcyclohexane	56	n-Tetradecane
18	C ₃ -Cyclohexane	57	Butyltetralin
19	C ₃ -Cyclohexane	58	C ₃ Tetralin?
20	C ₃ -Cyclohexane	59A	Acenaphthene
21	C ₃ -Cyclohexane	59	n-Pentadecane
21A	n-Nonane	60	Butyltetralin
22	Propylcyclohexane	61	Tetrahydrobenzindan
23	Propylbenzene?	62	Methylbiphenyl
24	Ethylmethylbenzene	63	Octahydroanthracene
25	Trimethylbenzene	64	C ₂ -Biphenyl
26	Perhydroindan	65	Octahydrophenanthrene
27	Trimethylbenzene	66	Tetrahydrophenanthrene
28A	n-Decane	67	Phenanthrene
28	trans-Decalin	68	n-Octadecane
29	Indan	69	C ₂ -Dibenzothiophene
30	C ₄ -Cyclohexane	70	n-Nonadecane
31	Methylindan	71	Tetrahydropyrene
32	Methylpropylbenzene	72	Hexahydropyrene
33	cis-Decalin	73	n-Eicosane
34A	n-Undecane	74	Hexahydropyrene
34	Methyldecalin	75	Dihydropyrene
35	Methyldecalin	76	Pyrene
36	Methylindan	77	n-Docosane
37	Methylindan	78	Methylpyrene
38	Tetralin	79	n-Tricosane
39	C ₂ -Phenol	80	n-Tetracosane
40	C ₂ -Phenol		

NOTES: Identifications based on search of Wiley/NBS Library of mass spectra. C_x refers to alkyl substituents of x carbon atoms. Search results may misidentify isomers, e.g., "hexahydropyrene" may refer to hexahydrofluoranthene and "C₂-biphenyl" may refer to C₂-acenaphthene.

/ls

END

**DATE
FILMED**

2 / 11 / 92