10
2-3-95 JSD

Conf-9409103-10

Polarized Electron Sources

SLAC-PUB-6702
December 1994
(N)

REVIEW OF THE SLAC AND LES HOUCHEs WORKSHOPS*

Charles Y. Prescott
Stanford Linear Accelerator Center
Stanford University, Stanford CA 94309

I. Introduction. Polarized Electron Source workshops have been held at varying intervals, beginning in 1983 when Charles Sinclair convened the first at SLAC. Since that time, three workshops were held in conjunction with the International Spin Symposia and two at other occasions. The increasing importance of polarized electron beams at accelerators has stimulated interest in these workshops. Two workshops have been held since the last International Spin Symposium in Nagoya. In 1993, a workshop was held at SLAC, and in 1994 at Les Houches, a polarized electron beam session was held as part of a polarized beam and targets workshop. This report summarizes highlights from the latter two workshops.

History of Polarized Electron Sources Workshops

Year	Place	Convenor
1983	SLAC	C. Sinclair
1988	Minneapolis	C. Sinclair
1990	Bonn	E. Reichert
1992	Nagoya	T. Nakanishi
1993	SLAC	J. Clendenin (SLAC) T. Maruyama (SLAC) D. Schultz (SLAC)
1994	Les Houches	M. Leduc (ENS Paris) E. Steffen (MPI Heidelberg)

The workshops have experienced a growing attendance. These workshops report on progress in all aspects of polarized electron beams and support the polarization progress at labs like SLAC, MIT-Bates, and Mainz, where experiments are running, and at labs such as CEBAF, NIKHEF, and KEK, where future experiments are likely to be run. Interest in polarized electrons for a future linear collider is strong. The frequency of one workshop per year should continue into the future as long as this interest in experiments with polarized electron beams remains strong.

II. The SLAC Workshop on Photocathodes for Polarized Electron Sources for Accelerators (September 8-10, 1993). This workshop was organized by J. Clendenin, T. Maruyama, and D. Schultz, and supported by SLAC. The focus of this workshop was on photocathodes for use in polarized electron sources at accelerators. The reports presented in this workshop have been combined into a proceedings consisting of copies of transparencies from each talk [1]. The workshop contributions can be divided into two categories, accelerators and cathode studies. Listed below are the laboratories and institutions represented, the speakers, and their topics. The workshop had 43 participants representing 22 institutions and laboratories

* Work supported by Department of Energy contract DE-AC03-76SF00515.

Invited talk presented at the 11th International Symposium on Spin Physics and the 8th International Symposium on Polarization Phenomena in Nuclear Physics, Bloomington, Indiana, September 15-22, 1994

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

Accelerators

Mainz
SLAC
SLAC
MIT-BATES
Los Alamos
CEBAF
KEK

Speaker

K. Aulenbacher
S. Ecklund
L. Klaisner
M. Farklende
R. Sheffield
C. Sinclair
M. Yoshioka

Subject

MAMI operating experiences
NLC and Linear Colliders
SLC experiences
Bates operating experiences
AFEL Accelerator
Emittances of GaAs sources
JLC-ATF source

Cathode Studies**Accelerators**

Bielefeld
Ferrara
Ecole Polytechnique
SLAC
St. Petersburg
SLAC
SLAC
Nagoya
Spire Corp.
Heidelberg
Novosibirsk
SLAC
Mainz
ETH Zürich
NIST
SLAC
Stanford

Speaker

G. Baum
V. Guidi
G. Lampel
R. Mair
Y. Mamaev
T. Maruyama
G. Mulhollan
T. Nakanishi
S. Vernon
S. Zwickler
A. Terekov
H. Tang
E. Reichert
H. Seigmann
D. Pierce
G. Mulhollan
W. Spicer

Subject

Strained GaAs
Timed resolved emission
Layered structures
Photoluminescence studies
InGaAs, AlGaInAs, GaAsP
Strained GaAs
Low energy test facility
Superlattice structures
MOCVD process
Energy analysis of electrons
InGaAsP on GaAs
Charge limits
Thermal studies
High pulsed laser power studies
Studies of surface magnetism
Low energy test facility
Theory

Three of the accelerator labs, Mainz, SLAC, and MIT-Bates reported on operational aspects of polarized beams. The remaining laboratory presentations reported on R&D activities aimed at possible future operations. A partial list of accelerator parameters is given below. It should be noted that parameters listed here are a snapshot given at the time of the workshop, and that they may change and can be expected to be different at future times.

Parameter	Mainz MAMI	SLAC SLC	MIT- Bates	CEBAF	KEK JLC ATF	Los Alamos AFEL
Pulsed/cw	cw	pulsed	pulsed	cw	pulsed	pulsed
Rate (Hz)		120	600		150	100
Gun type	triode	diode	diode	diode	diode	rf
Voltage (KeV)	100	120	380	100	100	10 ³
Pulse length		2 ns	15 μ s		< 1 ns	< 20 ps
Q/pulse		8 $\times 10^{10}$	2 $\times 10^{12}$		1.5 $\times 10^{10}$	6 $\times 10^{10}$
Cathode	GaAsP	strn GaAs	GaAs	GaAs	GaAs	multi-alkali
QE(%)	0.9	0.9	6.5			< 0.1
ϵ (π mm mrad)	0.32	20	0.1	0.6		3
Polarization (%)	40	80	40	—	—	0
QE lifetime (hrs)	20	100-500	200			3
Load lock?	no	yes	no	no	no	no
Laser type	dye	ti-sapp.	ti-sapp.e			

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DISCLAIMER

Portions of this document may be illegible in electronic image products. Images are produced from the best available original document.

III. The Les Houches Workshop on Polarized Beams and Targets; Sensitive Tools for the Study of Solids, Nuclei, and Particles (June 7-10, 1994). This *Scientific Network on "Polarized Beams and Targets"* workshop was organized under the auspices of the European Community "Human Capital and Mobility." The organizers were Michele Leduc (ENS Paris) and Erhard Steffens (MPI Heidelberg). Sixty three participants representing 36 institutions attended the workshop.

One day-long session was devoted to polarized electron sources and semiconductor photocathodes. Other topics at the workshop included lasers, optical pumping of gas targets, ^3He targets, and selected topics in polarized neutrons and atomic physics.

The talks covering the electron sources and semiconductor photocathodes were combined into one day and summarized in one evening session. Below are listed the presentations from those sessions relating to electron sources and photocathodes.

The talks are summarized in a collection of abstracts available from the organizers [2].

Institution	Speaker	Subject
Palaiseau	G. Lampel	The Physics of the Semiconductor Spin-Polarized Electron Source
ETH Zürich	F. Meier	Emission of Polarized Electrons from Photocathodes using Continuous and Pulsed Light Sources
SLAC	G. Mulhollan	Polarized Electron Beams at SLAC
Mainz	S. Plützer	Photoemission of Spin-Polarized Electrons from Strained $\text{In}_{1-x}\text{Ga}_x\text{As}_{1-y}\text{P}_y$ and $\text{GaAs}_{1-y}\text{P}_y$
Mainz	H. Fischer	XPS Studies of NEA-Cathode Fatigue
Palaiseau	D. M. Campbell	High Polarization and High Yield from Strained GaAs Photoelectric Sources
Orsay	S. Essabaa	Recent Developments and Latest Results of the Orsay Polarized Electron Source

IV. Summary. Gallium arsenide cathodes and layered structures of strained gallium arsenide and gallium arsenide superlattices have been shown to provide high polarization and high currents in photoemission by polarized laser beams. At accelerator facilities with running experiments, these sources have proven to operate with high reliability. Pulsed currents of up to 10 amps in 2 nanoseconds have been used at SLAC for the SLC. Polarizations up to 85% have been achieved for experiments. Mainz has operated photoemission sources with continuous currents, but in some conditions, the cathodes have shown a loss of quantum efficiency at the spot where the laser hits the photocathode when steady currents in excess of $150\ \mu\text{A}$ are drawn. Advances in laser technology, vacuum technology and cathodes materials continue to make the electron source devices better and easier to fabricate and use.

Helium afterglow sources at Rice University and Orsay offer an alternative to photoemission sources for high average currents ($\geq 100\ \mu\text{A}$) with polarization in the range of 60-80%.

1. Proceedings of the Workshop on Photocathodes for Polarized Electron Sources for Accelerators, organized by J. Clendenin et al., SLAC-432 (1993).
2. Abstracts of the Workshop on Polarized Beams and Targets; Sensitive Tools for the Study of Solids Nuclei, and Particles, organized by M. Leduc (ENS Paris) and E. Steffens (MPI Heidelberg), Les Houches (1994).