DOE/MC/27240--3139

DE93 000223

Work Plan for "Production of Mild Gasification Co-Products" Project

Topical Report

July 1992

Work Performed Under Contract No.: DE-AC21-91MC27240

For
U.S. Department of Energy
Office of Fossil Energy
Morgantown Energy Technology Center
Morgantown, West Virginia

By
SGI Fuels, Inc.
La Jolla, California

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

This report has been reproduced directly from the best available copy.

Available to DOE and DOE contractors from the Office of Scientific and Technical Information, P.O. Box 62, Oak Ridge, TN 37831; prices available from (615)576-8401, FTS 626-8401.

Available to the public from the National Technical Information Service, U.S. Department of Commerce, 5285 Port Royal Rd., Springfield, VA 22161.

**Work Plan for "Production of Mild
Gasification Co-Products" Project**

Topical Report

Work Performed Under Contract No.: DE-AC21-91MC27240

**For
U.S. Department of Energy
Office of Fossil Energy
Morgantown Energy Technology Center
P.O. Box 880
Morgantown, West Virginia 26507-0880**

**By
SGI Fuels, Inc.
La Jolla Financial Building
Suite 325
1200 Prospect
La Jolla, California 92037**

July 1992

WORK PLAN
for
CONTRACT DE-AC21-91MC27240
CONTENTS

SECTION	PAGE NO.
1.0 Description of the Process	1
2.0 Identification of Feedstock Coals and Lignites	4
3.0 Handling of Coals and Lignites	7
4.0 Processing of Coals and Lignites	9
5.0 Handling Procedures of Coproduct Sample	12
6.0 Cleanup	14
7.0 Reporting	14
8.0 Schedule Information	14

1.0 Description of Process

1.1 Facility Description

A bench scale Sample Production Unit (SPU) has been fabricated, assembled and installed in an existing development lab facility used for coal research. The SPU is to be used to evaluate the suitability of sample coals for the Liquid From Coal (LFC) process which produces high-quality, high-BTU-content, low-sulfur coal char and high-quality coal liquids typically derived from the coal reduction process.

The Development Laboratory is at 222 West Third Street, Perrysburg, Ohio, located 15 miles south of Toledo in Northwestern Ohio. It is operated for SGI International by Maumee Research and Engineering, Inc. The existing structure is situated in an area zoned for light industrial, suitable for research and testing. The present concrete block structure was erected in the mid-1960's.

The location is close to major airports, rail service and interstate highways. The site is immediately adjacent to the CSX Transportation Railroad (formerly the B&O) and is within two miles of the junction of major interstate highways, I-75 and the Ohio Turnpike, Interstates I-80 and I-90. Toledo Express Airport is 20 miles to the west and Detroit International Airport is located 65 miles to the north by interstate highway travel.

The Development Laboratory is within a leased building containing 4500 square feet of floor space. Minimum ceiling height is 16-1/2 feet above the concrete floor. A 12 feet wide by 15 feet high garage door is situated at the north end of the building. Offices, wet labs and rooms for computer controls for test equipment are located in one quadrant of the space. External to this building but constructed as part of the facility is a small structure the size of a double garage, marked "Coal Handling Area" in Figure 1.1-1. Power has been installed in the structure for lighting and the operation of the coal crushing and sizing equipment. This structure will also be used for coal storage as well as handling.

A layout of the laboratory facility is shown in Figure 1.1-1.

1.2 SPU Description

The Sample Production Unit (SPU) has been commissioned to prepare solid and liquid samples from samples of coal or lignite. The unit has been designed for portability but is set up indoors in the Development Laboratory. An equipment schematic diagram of the SPU is given in Figure 1.2-1.

Figure 1.1-1 SGI LFC LABORATORY LAYOUT

FIGURE 1.2-1 SGI LFC SAMPLE PRODUCTION UNIT - SPU

The SPU functions as follows: Heated nitrogen gas is passed through a bed of dried coal in a closed system. The hot gas heats the coal in the absence of oxygen and forces vapors from the coal. After heating, the coal is discharged as a carbon rich solid sample to be cooled in sealed containers. Vapors that are driven from the coal are piped to downstream cooling and condensing equipment. As a result of cooling the off-gas, some of the coal vapor will condense into droplets of coal liquid mist. The cooled off-gas aerosol is then passed through a voltage regulated Electrostatic Precipitator (ESP). The temperature of the ESP is maintained above the pour point of the Coal Derived Liquid (CDL). The precipitated liquid flows by gravity into a sump. The ESP including the sump is a closed system and will allow no liquid or vapor escape. The coal liquid sample, after removal from the sump, is stored in sealed containers prior to further handling. The cleaned carrier gas is passed through an afterburner control device maintained at 1600°F before being discharged from the SPU to the atmosphere.

The SPU has been designed as a versatile modular component unit. By coupling the gas heater and coal heater modules, the SPU can be used to dry the feed coal samples prior to processing the dried coal as described above. In this mode, dry nitrogen gas is heated and then used to heat the coal. It carries the moisture from the coal through the analytical section to the afterburner control device, thus by-passing the downstream oil-collecting modules during the drying process.

Procedurally, a sample of wet coal is crushed, riffled and sized. The feed coal is then dried as described above and stored in sealed metal containers. After all the coal has been dried, the SPU is preheated to operating conditions. All systems of the SPU are fully operational before the dried coal sample is processed. A computer is used to monitor and control the process variables of temperature, pressure, and flow.

Vapors released from the hot coal are carried from the reactor in the nitrogen carrier gas to the downstream ESP processing equipment where it is recovered as CDL. The processed solid sample is cooled over a period of time in a sealed metal container that is set aside from the operating SPU. After cooling, the solid samples are inerted to produce SPU processed Process Derived Fuel (PDF) but not treated by dust suppressor, MK.

The SPU processed PDF and CDL is then carefully packaged and directed to other analytical laboratories or interested clientele.

Operation of the SPU is planned for up to 10 hours in duration; however, sample processing in a batch mode is within the capability of the unit.

2.0 Identification of Feedstock Coals and Lignites

Identification of the candidate feedstock coals and lignites from which the coproduct samples of the LFC Process will be produced is underway. Much information relative to the feedstocks was given in the Statement of Work (SOW) in Contract DE-AC21-91MC27240. Table 2.0-1 summarizes the information extracted from the Contract and also reflects the changes both in name and order of the processing of the candidate coals and lignites. The changes in the Descriptions and the numerical order of the coals/lignites from the statement of work result from comments by and agreements with the Contracting Officer's Representative.

(See next Page.)

Table 2.0-1 SAMPLE FEEDSTOCK COAL/LIGNITE

<u>OPTION: Item 2</u>					
COAL	DESCRIPTION	RANK	REGION/ BASIN	LOCATION	MINE
Baseline	Buckskin	SubC	PRB	Gillette, Wyoming	Buckskin
2.	Montana Rosebud	SubB	PRB	Colstrip, Montana	Rosebud #6
3.	North Dakota Lignite	Lig	Williston Basin	North Dakota	
4.	Alaskan	SubC	Alaska		
<u>OPTION: Item 3</u>					
COAL	DESCRIPTION	RANK	REGION/ BASIN	LOCATION	MINE
5.	Texas Lignite	Lig	East Texas	Texas	
6.	W. Virginia	MVB	Appalachia Basin	West Virginia	
7.	Illinois #6	HVCB	Herrin Seam	Illinois	

2.1 Table 2.0-1, Option: Item 2

The region and/or basin from which the four feedstock coals or lignite will originate is listed. The specific mine is defined for the first or baseline coal and for the number 2 candidate coal. An agreement with those two mines will be negotiated which will specify the method of collecting the sample feedstock, and packaging and shipping the sample feedstock.

The number 3 candidate feedstock is listed as North Dakota Lignite and the number 4 candidate feedstock is identified as Alaskan SubC Coal. Communication will begin with mineowners in both those regions to identify the feedstocks for processing and negotiate sample collection terms.

The paper "Characteristics of Commonly Used U.S. Coals - Towards a Set of Standard Research Coals" by K. Lee Smith, GRA, and L. Douglas Smoot, PhD, of the Advanced Combustion Engineering Research Center, Brigham Young University, Provo, Utah, provides a suite of 11 coals as a listing of proposed standard coals for research purposes.

In the listing of the proposed standard coals is Beulah-Zap Lignite of North Dakota. It is suggested that the number 3 coal, designated as North Dakota Lignite, come from the Beulah Surface Mine.

In the listing of the 11 Proposed Standard Coals, an Alaskan coal was not included. Communication is on-going with Alaskan mine owners and candidates are being isolated.

2.2 Table 2.0-1, Option: Item 3

With reference to candidate feedstock coals number 5, number 6, and number 7 and maintaining consistency with the paper mentioned in the foregoing paragraph, the Texas Lignite that appears in the publication is Lower Wilcox Coal as the proposed standard. The proposed standard coal for West Virginia is Upper Kanawha Coal, and the standard for Illinois is Illinois #6

The mines identified have the highest probability of being the Sample Feedstock Coal/Lignite producers at this time.

3.0 Handling of Coals or Lignites

Since the coproduct samples will be characterized relative to the raw coal, it is important to obtain a run of mine (ROM) coal or lignite (referred as "coal"), so that the coproducts produced by the LFC process in the Development Center are representative of the coproducts which would be produced by a LFC plant using the same coal as feedstock.

The coal sample will be obtained according to sampling procedures outlined in ASTM D4596-86 (attached as Appendix 1-1). A specific sampling plan for the test coals will be developed by a Development Center representative and a representative of the specific mine. The plan will be consistent with paragraph 6.2 of the ASTM of Appendix 1-1. Since the sample is always small relative to the total mine resource, additional information will be obtained to enhance confidence in the economic projections from the coproduct yields.

Procedurally, six (6), 55 gallon, polyethylene drums will be supplied by SGI Fuels. To limit the exposure of the fresh coal to air, the coal sample will be quickly packed into the drums. Paragraph 7.7 of the ASTM included in Appendix 1-1 will be used as a guide for this procedure, for example. The moisture content of the fresh sample of coal will be measured using a moisture meter.

The individual drums of coal will be filled, shaken down, and topped off to exclude as much air from the drum as possible. The drums will be sealed by lids and placed on pallets for shipment. The filled, sealed, and palletized drums will be shipped to the SGI Development Center by a common carrier, routed as directly as possible, with a delivery time of not more than seven (7) days.

The information requested from the mine is listed on the standard form shown in Figure 3.0-2, Coal Sampling Form. The form will be completed to the greatest extent possible. The additional information desired in the Comments Box will include data to relate the sample to the approximate location in the resource from which the sample was taken. For example, statistical information could be available from the mine operations plan. This statistical information can be used to relate the sample to the coal resource characteristics as derived from surveys of the resource's projected coal characteristics. Statistical information may also be synthesized from proximate analyses taken from core sample data. Alternate sources of data from other surveying techniques may provide additional inputs for the projections. If this extra information can be obtained, it could improve the reliability of information derived from the sample. Making statistical or other information available will be discussed with the mine representative.

FIGURE 3.0-2 COAL SAMPLING FORM
COAL SAMPLING FORM

<u>Name of Mine</u>		<u>Location of Mine</u>		
<u>Coal Type</u>	<u>Contact Person at Mine</u>		<u>Phone No.</u>	
<u>Sampling</u>		<u>Channel Sample</u>		
<u>Date/Time</u>	<u>No. of Barrels</u>	<u>Height</u>	<u>Width</u>	<u>Depth</u>
<u>Weather conditions: i.e., overcast, raining, etc.</u>				
<u>Moisture Meter Readings (Apparent Moisture)</u>				
<u>5 minutes</u>	<u>10 minutes</u>	<u>15 minutes</u>	<u>20 minutes</u>	
<u>Coal Properties Provided by Mine (Optional)*</u>				
<u>Proximate Analysis</u>		<u>Ultimate Analysis</u>		
% Moisture		% C	<u>Btu/lb</u>	
% Volatile		% H		
% Fixed Carbon		% N	<u>Lbs SO₂/MMBTU</u>	
% Ash		% S		
		% O		
<u>Date Shipped</u>	<u>Carrier, Phone Number</u>			
<u>Comments: (*Statistical information)</u>				
				<u>Recorded by</u>

4.0 Processing of Coals and Lignites

The coal will be received at the SGI Development Center for processing in the Sample Production Unit (SPU) and an Unloading Dock Checklist initiated. (Figure 4.0-1 is a sample.) Prior to processing, the coal will be prepared by crushing and sizing, riffing, and packaging for shipment to analytical laboratories.

4.1 Crushing and Sizing

Coal will be taken from each of the storage barrels to ensure a consistent, representative mix for coal crushing/sizing. The coal will be crushed using the Development Center's crusher. Care will be taken to reduce the amount of fines produced by the crushing activity, and to limit, to the greatest extent possible, the exposure of the coal to the air. During the crushing operation the coal will be sized using the Development Center's continuous sieve. Oversized particles will be returned to the crushing operation. The crushed and sized coal will be riffled and then be stored in sealed five-gallon, polyethylene pails.

4.2 Analysis

Twenty (20) kilogram (44 pound) samples will be shipped to three government laboratories. The laboratories are:

- 1) Department of Energy/Morgantown Energy Technology Center (DOE/METC)
- 2) Oak Ridge National Laboratory (ORNL)
- 3) DOE No. 3 (to be agreed upon by METC and SGI)*

* (The "DOE No. 3" Laboratory has not been identified at this writing. After production for each feedstock coal, the samples of feedstock and coproduct samples will be packaged for delivery. If the "DOE No. 3" has not been designated by the conclusion of sample production, the Development Center will hold the sample in temporary storage for a period of six months.

At any time prior to the end of the temporary storage period, one of the following alternative courses of action may be agreed:

- 1) The requirement for delivery to "METC No. 3" may be cancelled,
- 2) The "DOE No. 3" laboratory may be designated, or
- 3) The samples may be delivered to METC for temporary or long term storage.

If none of the three courses of action are implemented, then the Development Center will use its own discretion for disposition of the "DOE No. 3" samples after the temporary storage period.)

Additionally, The Development Center will commission an independent laboratory to analyze a 20 Kg sample. This laboratory shall determine the bulk density, particle size distribution, proximate analysis, ultimate analysis (C, H, N, O, S), and heating value.

4.3 Documentation

Throughout this procedure the following items will be recorded and entered into the project data base:

1. dates and times of crushing, sizing, and storage
2. analytical results from outside and government laboratories
3. weight of the SPU-processed coal
4. amounts of SPU-processed coproducts

The information will be retrieved for the topical and final reports.

FIGURE 4.0-1 RECEIVING CHECKLIST

RECEIVING CHECKLIST

<u>Date Received</u>	<u>Name of Mine</u>	<u>Condition on Receipt</u>		
<u>Speedy Moisture Meter Check</u>				
Drum #	5 Min.	10 Min.	15 Min.	20 Min.
<u>Comments/Notes:</u>				
				<u>Received By</u>

5.0 Handling of Coproduct Samples

The coproducts will be collected and handled to limit their exposure to air. The aim is to ensure the coproducts are as close as possible to those which would be generated by an LFC Plant at the mine site.

5.1 Coproduct Collecting

5.1.1 SPU processed Process Derived Fuel (PDF)

The char will be collected in sealed, stainless steel containers. While in the containers the char will be cooled to room temperature and a small amount of water added (5% by weight) to simulate the final processing step, stabilizing the char and converting it to PDF. This SPU-processed PDF will be transferred to nitrogen filled five gallon polyethylene pails for storage and shipping.

5.1.2 Coal Derived Liquids (CDL)

During processing the CDL will be collected using a single stage, thermostatically-controlled electrostatic precipitator (ESP). The collected CDL will be trapped in a sealed collection cylinder attached directly to the ESP. The CDL will be transferred from the collection cylinder to replace nitrogen in nitrogen-filled one liter bottles for storage and shipment.

5.2 Analysis

The results of the analyses will be collected and included in the project data base to be retrieved as necessary for use in the topical and final reports.

5.2.1 SPU processed PDF

Twenty (20) Kg samples of SPU processed PDF will be sent to three government laboratories plus one outside laboratory. The government laboratories will be the same labs which received the fresh coal samples, as indicated in section 4.2, above. The outside laboratory will analyze the SPU processed PDF as was done for the coal. These tests will include the bulk density, particle size distribution, proximate analysis, ultimate analysis (C, H, N, O, S), and heating value.

5.2.2 CDL

Two-liter samples of the CDL will be sent to four government laboratories for analysis. The government laboratories will be:

- 1) Department of Energy/Morgantown Energy Technology Center (DOE/METC)
- 2) Oak Ridge National Laboratory (ORNL)
- 3) DOE No. 3 (to be agreed upon by METC and SGI Fuels) *(See footnote, Page 9)
- 4) National Institute of Occupational Safety and Health (NIOSH)

In addition, a two-liter sample of CDL will be sent to an outside laboratory for analysis. This laboratory will perform the following analyses:

- * Elemental Analysis (C ,H, O by high temperature combustion)
- * Nitrogen (ASTM D-4629)
- * Sulfur (by X-Ray, ASTM D-4294)
- * Ash content (ASTM D-482)
- * Distillation (ASTM D-86 and ASTM D-1160)
- * Simulated Distillation (by Gas Chromatography)
- * Carbon Residue, Rams bottom (ASTM D524)
- * API Gravity (ASTM D-287)
- * Flash Point (ASTM D-92)
- * Pour Point (ASTM D-97)
- * Viscosity (ASTM D-445)
- * Water Content (ASTM D-95)

6.0 Cleanup

At the conclusion of the production of SPU-produced PDF and CDL, the apparatus for production of the coproducts will be dismantled and cleaned in preparation for the next coal sample. All of the waste products and unused coal will be disposed of in accordance with State and local regulations.

7.0 Reporting

Upon receipt of the analytical data from the various government laboratories and the outside laboratory, a topical report for each coal sample will be prepared which will contain pertinent information gathered during the production process.

A final report will be prepared at the end of the project which will include selected information from the topical reports. This report will describe the result and give an overview of the project accomplishments.

8.0 Schedule Information

Schedule information is provided in Appendix 2-1 in Gantt chart format. This chart reflects information integrated from the Base Contract plus Option: Item 2.

Standard Practice for Collection of Channel Samples of Coal in the Mine¹

This standard is issued under the fixed designation D 4596; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

1. Scope

1.1 This practice describes procedures for collecting a coal sample from a channel extending from top to bottom in the face of a coal seam in a mine.

1.2 *This standard may involve hazardous materials, operations, and equipment. This standard does not purport to address all of the safety problems associated with its use. It is the responsibility of whoever uses this standard to consult and establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use. For specific precautionary information, see Note 2.*

2. Referenced Documents

2.1 ASTM Standards:

D 121 Terminology of Coal and Coke²

D 388 Classification of Coals by Rank²

D 2234 Test Methods for Collection of a Gross Sample of Coal²

D 2796 Definitions of Terms Relating to Megascopic Description of Coal and Coal Seams and Microscopical Description and Analysis of Coal²

D 4371 Test Method for Determining the Washability Characteristics of Coal²

3. Summary of Practice

3.1 At selected sites in the mine the face of the seam is cleaned of weathered coal and debris and the face is evened. A channel of uniform horizontal cross section is cut from the coal seam and the coal therefrom is collected for analysis and testing.

4. Significance and Use

4.1 Channel samples of coal are taken for subsequent chemical, physical, and petrographic testing needed for commercial evaluations, for planning of mining operations to maintain coal quality, for determining the rank of the coal in accordance with Classification D 388, and for geological studies and coal resource compilations.

NOTE 1—Sampling of the mine product for these purposes is unsatisfactory because of contamination of the product with out-of-seam material, selective mining of parts of a seam, inability to obtain samples from one or more specific locations in the mine, or other incompatibility of the purpose of sampling with the mining practice. Conversely, channel samples should not be used for evaluation of the

quality of commercial shipments of the mine product, which should be sampled in accordance with Methods D 2234.

5. Apparatus

5.1 *Steel Measuring Tape*, not less than 8 ft (2.5 m) long.

5.2 *Miner's Pick or Similar Tool*, with file for sharpening. Other devices may be used such as a pneumatically operated chain saw with tungsten carbide teeth.

5.3 *Brush or Broom*, for removing loose particles on the coal face.

5.4 *Chalk*.

5.5 *Sample Containers With Closures*—If the sample is to be used for determination of inherent moisture, the container shall be such that less than 0.05 % of the sample weight is lost between the time of sealing the container with sample and the time of opening for preparation of the sample for analysis. Steel airtight containers with polyethylene bag liners have been found to be satisfactory for this purpose. For other purposes, bags made of a strong cloth and lined with a polyethylene bag may be suitable.

5.6 *Ground Cloth*—Canvas tarpaulin or heavy-duty plastic sheet, 8 ft (2.5 m) or more square. If the purpose of sampling includes the determination of inherent moisture, the sheet shall be of low water solubility and permeability, such as polyethylene or oilcloth.

5.7 *Tags and Pen*, for sample identification and for marking.

5.8 *Shovel*.

5.9 *Notebook and Pencil*, or other means for record keeping.

6. Planning of Sampling

6.1 *Sampling Plan for Classification According to Rank:*

6.1.1 Refer to Section 7 of Classification D 388 for information on the required number and location of samples.

6.1.2 The channel size shall be at least 3 in. (8 cm) deep and 4 in. (10 cm) wide, and shall yield at least 6 lb (2.7 kg) of coal for each foot of thickness of coal seam.

6.1.3 All roof and floor rock, mineral partings more than $\frac{3}{8}$ in. (1 cm) thick, and mineralized lenses or concretions (such as sulfur balls) more than $\frac{1}{2}$ in. (1 $\frac{1}{4}$ cm) thick and 2 in. (5 cm) wide shall be excluded from the sample.

6.2 *Sampling for Other Purposes*—Variations in the purpose of sampling and in conditions encountered in the field preclude the establishment of rigid procedures covering every sampling situation. In each case, formulate a plan taking into account the mining operation, the purpose of the sampling, and the known characteristics of the coal seam. Characteristics include lateral or vertical variations in coal quality, occurrences of persistent mineral partings or concretions within the seam, and the extent of oxidation or weathering of

¹ This practice is under the jurisdiction of ASTM Committee D-5 on Coal and Coke and is the direct responsibility of Subcommittees D05.18 on Classification and D05.23 on Sampling.

Current edition approved June 27, 1986. Published August 1986.

² *Annual Book of ASTM Standards*, Vol 05.05.

coal. Take these considerations into account in planning sample site selection and whether lithotypes, partings, and layers above and below the seam should be described.^{3,4} Also establish a method of preparing the coal face, and determining the size of sample.

6.2.1 Obtain information for identification of suitable locations for sampling. Choose sites that will best satisfy the purpose of sampling.

6.2.2 A channel 3 in. (8 cm) deep (into the face of the seam) and 4 in. (10 cm) wide yields a sufficient sample for most purposes. The channel may be enlarged to minimize the effect of channel size variability when a coal characteristic of interest, such as ash content, varies greatly from layer to layer in the seam, or when the coal breaks unevenly. Also, the channel cross-section may be enlarged to obtain sufficient sample for tests requiring large amounts. The size of channel for the required amount of coal may be estimated from the density of coal—approximately 0.05 lb/in.³ (1.3 g/cm³). For information on determining washability, see Test Method D 4371 and the report by Wizzard.⁵

6.2.3 Practice with respect to weathering of the coal depends on a number of factors. Some characteristics of coal, such as total sulfur content, do not change appreciably with weathering if the coal is not leached. The forms of sulfur, the moisture-holding capacity, and oxygen content of high volatile C bituminous and lower rank coals, and the rheological properties of coking coals do change with weathering. Sampling to different depths and testing of such properties may be required to establish the depth at which unweathered coal can be obtained.

7. Sampling Procedures

7.1 At each sampling site, survey the condition of the coal face and the rock above the coal (if exposed).

NOTE 2: Warning—Beware of danger from rock falling from the roof of underground mines or from the highwall of surface mines. Take down any loose blocks as a safety precaution and to prevent extraneous material from subsequently contaminating the sample.

7.2 With a miner's pick, remove weathered coal from the face area to be sampled, to the depth (but at least 1 in. (2.5 cm)) required in the plan of sampling. True up to the face to leave a straight surface normal to the bedding and free of extraneous matter.

7.3 Describe and record observations on the character of layers in the coal seam (see Definitions D 2796) to the extent required by the sampling plan.

7.4 Mark the sides of the channel with chalk and mark any mineral partings or other parts of the seam that are to be discarded.

7.5 Clear and smooth the floor adjacent to the sample area and spread a ground cloth on the floor with one edge at the coal face.

7.6 Cut away with a miner's pick (or other tool) a channel from top to bottom (or bottom to top) of the coal seam. If a saw is used at the sides of the channel, exercise care that fines generated by the saw do not become part of the sample. Ensure that all material from the channel that is to be sampled according to the plan of sampling falls on the ground cloth and that any mineral matter to be discarded does not contaminate the coal sample. Cut the channel to a uniform width and depth in a rectangular cross section, to ensure that representative volumes of material are obtained from every part of the coal seam.

7.7 As quickly as possible, if inherent moisture will be determined, transfer the material on the ground cloth to a sample container and seal and then label the container. If surface moisture is visible on the coal, or if there is any reason to question the accuracy of inherent moisture content determined from the sample, the description of the sample shall include the warning: "Moisture content questionable."

³ Schopf, J. M., "Field Description and Sampling of Coal Beds," U.S. Geological Survey Bulletin No. 1111-B, 1960.

⁴ Field Description of Coal, ASTM STP 661, ASTM, 1978, pp 3-33, 58-68.

⁵ Wizzard, J. T., "The Reliability of Using Channel Samples to Represent Run-of-Mine Coal Washability," DOE/PETC/TR-82/3.

The American Society for Testing and Materials takes no position respecting the validity of any patent rights asserted in connection with any item mentioned in this standard. Users of this standard are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, are entirely their own responsibility.

This standard is subject to revision at any time by the responsible technical committee and must be reviewed every five years and if not revised, either reapproved or withdrawn. Your comments are invited either for revision of this standard or for additional standards and should be addressed to ASTM Headquarters. Your comments will receive careful consideration at a meeting of the responsible technical committee, which you may attend. If you feel that your comments have not received a fair hearing you should make your views known to the ASTM Committee on Standards, 1916 Race St., Philadelphia, PA 19103.

Summary
Rolled Up

Progress
Milestone

Critical
Noncritical

Project: Production of Mild Gasification
 Date: 7/2/92

Page 3

END

**DATE
FILMED**

5 / 6 / 93