DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DOE/PC/90309--8

DE93 006439

ANION-EXCHANGE RESIN-BASED DESULFURIZATION PROCESS

Annual Technical Progress Report

OCTOBER 1, 1991 - SEPTEMBER 30, 1992

Prepared by:

Atul C. Sheth
Sterling D. Strevel
Rajeev Dharmapurikar

Reviewed by OETI

JAN 23 1993

The University of Tennessee Space Institute
B.H. Goethert Parkway
Tullahoma, Tennessee 37388

DOE Grant No. DE-FG22-90PC90309

MASTER

"US/DOE Patent Clearance is not required
prior to the publication of this document."

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

Table of Contents

	<u>Page</u>
EXECUTIVE SUMMARY	vi
1.0 INTRODUCTION	1
2.0 OBJECTIVES AND PROJECT DESCRIPTION	2
3.0 PROJECT STATUS/PROGRESS TO DATE	4
3.1 Task 1.1	4
3.2 Task 1.2	4
3.2.1 Shakedown Experiments and Revisions to Fixed-Bed Setup	4
3.2.2 Equilibrium Capacity	12
3.2.3 Fixed-Bed Mathematical Model	20
3.2.4 Effect of Process Variables	29
3.2.4.1 Effect of Static CO ₂ -Pressure	29
3.2.4.2 Effect of Solution Concentration	31
3.2.4.3 Effect of Product Inhibition	33
3.2.4.4 Effect of Resin Bed Height	34
3.2.4.5 Effect of Dissolved Impurities	34
3.2.4.6 Effect of Superficial Velocity	39
3.2.4.7 Effect of Solution pH	41
3.3 Task 1.3	43
3.4 Task 1.4	44
3.4.1 Statistical Analysis of Batch Mode Results and Revised Utilities for Candidate Resins	44
3.4.1.1 Statistical Analysis	45
3.4.1.2 Multiattribute Analysis	50
3.4.2 Trade-Off Between Solution Concentration and Evaporation/Concentration Load	53
3.5 Task 1.5	57
4.0 PLANS FOR NEXT REPORTING PERIOD	62
5.0 SUMMARY	63
6.0 REFERENCES	65

List of Figures

	<u>Page</u>
Figure 1. Milestone Schedule and Status Report	5
Figure 2. Milestone Log	6
Figure 3. Fixed-Bed Schematic	8
Figure 4. Comparison of Strevel's and Modeste's Breakthrough Curves	10
Figure 5. Reproducibility Check for IRA-35 at 10 psig, 0.014 gm SO_4^{2-} / ml, 20.3 cm Bed Height, and 10.8 cc/min	11
Figure 6. Plot of Fitted Linearized Langmuir Isotherm for IRA-35	17
Figure 7. Plot of Fitted Linearized Langmuir Isotherm for IRA-68	18
Figure 8. Plot of Fitted Linearized Langmuir Isotherm for IRA-93	19
Figure 9. Langmuir Isotherms for IRA-35, IRA-68, and IRA-93 at 10 psig CO_2 -Pressure	21
Figure 10. Effect of X on C/C_o at $a_2C_o = 1.0$	22
Figure 11. Effect of a_2C_o on C/C_o at $X = 1.0$	23
Figure 12. Typical Best Fit: Run 59 (IRA-68, 10 psig, 0.004 g SO_4^{2-} / ml, 20.3 cm Bed Height, 4.96 cm^2 Column Area, and 11.0 cc/min)	24
Figure 13. Effect of Static CO_2 -Pressure on Diffusion Parameter	26
Figure 14. Effect of Solution Concentration on Diffusion Parameter	27
Figure 15. Effect of Static CO_2 -Pressure on IRA-93	30
Figure 16. Effect of Solution Concentration on IRA-93	32
Figure 17. Effect of Product Inhibition on IRA-68	35

List of Figures (Continued)

	<u>Page</u>
Figure 18. Effect of Resin Bed Height on IRA-93	36
Figure 19. Effect of Dissolved Impurities on IRA-68	38
Figure 20. Effect of Superficial Velocity on IRA-35	40
Figure 21. Effect of Solution pH on Breakthrough Curve for IRA-68	42
Figure 22. Process Schematic for Dilute Effluents	55
Figure 23. Process Schematic for Concentrated Effluents	56
Figure 24. Effect of Solution Concentration and Number of Evaporator Effects on Relative Cost of Concentration	58
Figure 25. Effect of Solution Concentration on Relative Cost of Concentration for 4-Effect Evaporator	59

List of Tables

	<u>Page</u>
Table 1. Test Conditions for IRA-68 Breakthrough Curve Comparison	12
Table 2. Effect of CO ₂ -Pressure on Equilibrium Loading	13
Table 3. $\overline{C_T}$ Values for IRA-68	15
Table 4. Calculated Langmuir Constants for IRA-68	16
Table 5. Calculated Langmuir Constants for IRA-35 and IRA-93	16
Table 6. Calculated Diffusion Parameters for IRA-35, IRA-68 and IRA-93	28
Table 7. Comparison of the Diffusion Parameters with the Literature	29
Table 8. Effect of Product Inhibition (PI) on Equilibrium Loading	33
Table 9. Effect of Dissolved Impurities on Equilibrium Loading	37
Table 12. Resin and Concentration Effects on Exhaustion Efficiency	46
Table 13. Resin and Concentration Effects on Regeneration Efficiency	46
Table 14. Resin and Cycle Effects on Exhaustion Efficiency	47
Table 15. Resin and Cycle Effects on Regeneration Efficiency	47
Table 16. Resin and Cation Effects on Exhaustion Efficiency	48
Table 17. Resin and Cation Effects on Regeneration Efficiency	48
Table 18. Resin and Seed Effect on Exhaustion Efficiency	49
Table 19. Resin and Seed Effect on Regeneration Efficiency	49
Table 20. Parameter Effects on Exhaustion and Regeneration Efficiencies	50
Table 21. Parameter Importance Ratings	51
Table 22. The Calculated Resin Utilities	53

EXECUTIVE SUMMARY

Under the DOE Grant No. DE-FG22-90PC90309, the University of Tennessee Space Institute (UTSI) has been directed to further develop an anion-exchange, resin-based desulfurization concept that has been developed and tested on a limited scope for feasibility. From environmental as well as the economic viewpoints, it is necessary that the soluble sulfates of alkali metal sorbents be desulfurized (regenerated) and recycled to make regenerative flue gas desulfurization options more attractive. In order to achieve this, a low-temperature, low-cost desulfurization process to reactivate spent alkali metal sorbents is necessary. UTSI's anion-exchange, resin-based concept uses the available technology and is believed to satisfy this requirement.

In this DOE-sponsored project, Dr. Atul C. Sheth, an Associate Professor in the Chemical Engineering Department at UTSI, with the aid of graduate research assistants, Mr. Sterling Strevel and Mr. Rajeev Dharmapurikar, will perform the following investigations:

- screening of commercially available resins
- process variables study and improving resin performance
- optimization of resin-regeneration step
- evaluation of performance enhancers
- development of Best-Process Schematic and related economics, and
- planning for proof-of-concept (POC) scale testing

The above activities have been grouped into five major tasks and the entire project is expected to take thirty-six months to complete.

During the second year (October 1, 1991 to September 30, 1992) under this grant, the following progress has been made:

- Assembled a fixed-bed set-up, carried out shakedown tests, and revised the set-up as necessary.
- Developed procedure for the fixed-bed set-up and carried out process variables study using three resins selected based on the statistical analysis of the batch mode screening experiments.
- Analyzed results from the fixed-bed process variables study and compared with the available literature. At present, there is no clear cut winner found from the three candidate resins - IRA-68, -35, and -93. Similarly, from the analyses carried out so far, the CO₂-pressure, solution concentration and superficial velocity seem to have significant effect on the equilibrium loading and/or ion-exchange kinetics.
- Demonstrated from preliminary calculations that the solution concentration scheme making use of reverse osmosis to concentrate very dilute carbonate/bicarbonate solution (i.e. < 5 wt % solution) will be more expensive than the multi-effect evaporator scheme. Also, showed that the 5-effects evaporator is economically better than a 3-effects evaporator and that the relative cost of concentration by mere evaporation would asymptotically decrease as the solution concentration increases to about 10 wt % strength.

- Attended the contractors' review meeting from June 15-17, 1992 and made presentations at this meeting as well as at the meeting with the DOE/PETC contract management staff on work done so far.

At present, the project is about six weeks behind schedule but within the budgeted costs.

1.0 INTRODUCTION

Under the current grant (# DE-FG22-90PC90309), the University of Tennessee Space Institute (UTSI) will carry out the bench scale evaluation and further development of the anion-exchange resin-based desulfurization concept to desulfurize alkali metal sulfates. This concept has been developed and patented by UTSI under U.S. Patent No. 4,917,874. The technical feasibility of this concept has been demonstrated and reported in the M.S. theses prepared by Butler⁽¹⁾ and Modeste⁽²⁾. The developmental program proposed under this DOE grant includes screening of commercially available resins to select three candidate resins for further study. These three resins will undergo a series of experiments designed to test the resins' performance under different process conditions (including the use of spent MHD seed material). The best of these resins will be used in optimizing the regeneration step and in testing the effects of performance enhancers. The process schematic developed from the results will be used to estimate the related economics.

During this reporting period, October 1, 1991 to September 30, 1992, analysis of batch mode screening experiments was completed to select three candidate resins (i.e. IRA-68, -35, and -93) for process variables study in the fixed-bed set-up. This set-up was modified and the experiments were carried out to evaluate effects of major process variables. The analysis of fixed-bed experiments is going on and we have also started simple batch mode experiments to identify desirable conditions for resin regeneration step. We have also started simple process engineering type calculations to determine the trade-off between the solution concentration and the resulting evaporation/concentration load.

2.0 OBJECTIVES AND PROJECT DESCRIPTION

Various energy conversion technologies use chemical reactions between SO₂ and alkali metal salts to comply with the sulfur oxides emission standards. Cost and availability of fresh sorbents, scarcity of landfill area, and difficulties in disposing spent sorbent material necessitate the desulfurization and recycling of these alkali metal based sorbents. The options available at present to desulfurize such spent sorbent material require complex designs or severe processing conditions. In any case the costs are extremely high. Hence, a wide-spread use of regenerable flue gas desulfurization (FGD) type systems is not possible under the current economic conditions. Therefore, there is a mandate to develop a simple, low-cost and readily acceptable regeneration system to desulfurize alkali metal based spent sorbent material.

Under the present grant from the U.S. Department of Energy's Pittsburgh Energy Technology Center (DOE/PETC), UTSI will develop a low temperature, low cost spent seed/sorbent regeneration (desulfurization) system that uses available resin-based ion-exchange technology and which can be developed in minimum time and cost. The specific objectives of the present grant are as follows:

- To further improve the UTSI concept by identifying the best available resin and to optimize the resin exhaustion, regeneration and carbonation conditions.
- To develop Best-Process Schematic and related economics.

To accomplish the above objectives, UTSI plans to use the following approach:

- Perform a screening of the commercially available candidate resins,
- Perform process variables study and improve resin performance,

- Optimize resin regeneration step,
- Evaluate effect of potential performance enhancers,
- Develop Best-Process Schematic and related economics, and
- Develop plans for proof-of-concept (POC) scale testing.

The above activities are grouped in the following five tasks for ease of monitoring the progress of the project:

Task 1.1 Literature Survey, Vendor Contacts and Screening of Resins

Task 1.2 Process Variables Study and Improving Resin Performance

Task 1.3 Optimization of Resin Regeneration Step and Evaluation of Performance Enhancers

Task 1.4 Development of Best-Process Schematic and Related Economics

Task 1.5 Project Management and Reporting

The scope of work to be accomplished under the above tasks has been discussed in detail in the first quarterly progress report (no. DOE/PC/90309-1), and the first annual technical progress report (no. DOE/PC/90309-4) submitted earlier.

3.0 PROJECT STATUS/PROGRESS TO DATE

The progress made during the period of October 1, 1991 to September 30, 1992 is shown in Figures 1 and 2. Figure 1 shows the proposed schedule and progress to date for each task. Similarly Figure 2 lists the major milestones to be accomplished under each task and their planned and actual completion dates. Activities carried out under each task are as follows:

3.1 Task 1.1

Bench scale screening tests for the candidate resins as well as preliminary selection of the three leading resins for process variables study (during task 1.2) were completed in the first year of the grant and were reported in our first annual technical progress report. To support our selection of these three resins, additional statistical analyses were carried out. These analyses as well as the resulting confirming conclusions are reported here as part of the Task 1.4 accomplishments.

3.2 Task 1.2

3.2.1 Shakedown Experiments and Revisions to Fixed-Bed Setup

Initially the fixed-bed system was to provide a semi-automatic system that could utilize individually two different sized glass columns, that could provide for regeneration, carbonation, and exhaustion of an ion-exchange material, and could be left operating alone for an extended period of time. Problems occurred, however, during the shakedown experiments that prompted a re-design of the system. These problems include unstable system flow-rates, high initial concentrations of sulfate, and unstable sampler flow-rates. The unstable system flow-rates had to be dealt with procedurally.

Milestone Schedule and Status Report

Contract Identification		ANION - EXCHANGE RESIN - BASED DESULFURIZATION PROCESS												Grant Number DE-FG22-80PC90309											
		Reporting Period October 1, 1991 - September 30, 1992																							
Contractor: Name, Address		THE UNIVERSITY OF TENNESSEE SPACE INSTITUTE TULLAHOMA, TENNESSEE 37388												Contract Completion Date August 1993											
Reporting Category - Contract Line Item or Work Breakdown Structure Element		CY 90				CY 91				CY 92				CY 93											
ID		O	N	D	J	F	M	A	M	J	J	A	S	O	N	D	J	F	M	A	M	J	J	A	
1.0		<div style="display: flex; align-items: center;"> <div style="width: 100px; height: 15px; background-color: black; margin-right: 5px;"></div> <div style="display: flex; align-items: center;"> <div style="width: 10px; height: 10px; background-color: black; margin-right: 2px;"></div> <div style="width: 10px; height: 10px; background-color: black; margin-right: 2px;"></div> </div> </div>																							
2.0		<div style="display: flex; align-items: center;"> <div style="width: 100px; height: 15px; background-color: black; margin-right: 5px;"></div> <div style="display: flex; align-items: center;"> <div style="width: 10px; height: 10px; background-color: black; margin-right: 2px;"></div> <div style="width: 10px; height: 10px; background-color: black; margin-right: 2px;"></div> </div> </div>																							
3.0		<div style="display: flex; align-items: center;"> <div style="width: 100px; height: 15px; background-color: black; margin-right: 5px;"></div> <div style="display: flex; align-items: center;"> <div style="width: 10px; height: 10px; background-color: black; margin-right: 2px;"></div> <div style="width: 10px; height: 10px; background-color: black; margin-right: 2px;"></div> </div> </div>																							
4.0		<div style="display: flex; align-items: center;"> <div style="width: 100px; height: 15px; background-color: black; margin-right: 5px;"></div> <div style="display: flex; align-items: center;"> <div style="width: 10px; height: 10px; background-color: black; margin-right: 2px;"></div> <div style="width: 10px; height: 10px; background-color: black; margin-right: 2px;"></div> </div> </div>																							
5.0		<div style="display: flex; align-items: center;"> <div style="width: 100px; height: 15px; background-color: black; margin-right: 5px;"></div> <div style="display: flex; align-items: center;"> <div style="width: 10px; height: 10px; background-color: black; margin-right: 2px;"></div> <div style="width: 10px; height: 10px; background-color: black; margin-right: 2px;"></div> </div> </div>																							
COMMENTS		<div style="display: flex; align-items: center;"> <div style="width: 100px; height: 15px; background-color: black; margin-right: 5px;"></div> <div style="display: flex; align-items: center;"> <div style="width: 10px; height: 10px; background-color: black; margin-right: 2px;"></div> <div style="width: 10px; height: 10px; background-color: black; margin-right: 2px;"></div> </div> </div>																							
Signature of Contractor's Project Manager & Date																									

MS-0038

Figure 1.

[illegible]

Figure 2

In the re-designed system, six of the manually operated valves and three of the solenoid valves were replaced with three two-way valves and a four-way valve, respectively, to reduce/remove the dead-spaces in the system, which contributed to the high initial sulfate concentrations. Due to the removal of most of the solenoids one of the timers was deleted from the system. Two isolation valves were added to the eluent and regenerant tanks to aid in the post-run system flush. The flush was also added to reduce the initial high sulfate concentrations.

In the revised system, the full flow-rate through the column could be directed to the sampler, thereby eliminating the unstable sampler flow-rates caused by the flow-splitting sampling system. The schematic of the re-designed fixed-bed system is presented in Figure 3.

After the shakedown of the original and re-designed fixed-bed systems, the experimental procedure was one of prevention and constant monitoring. The preventive measures that were necessary to provide a good run were primarily associated with the filling and flushing of the eluent and regenerant tanks. These tanks were found on-site and were modified by removing their internal baffles. The subsequent welding with a copper based welding rod caused the production of copper sulfate/hydroxide when the weld was exposed to the ammonium hydroxide (regenerant) or the potassium sulfate (eluent) solution. Therefore, these tanks could not be filled to the weld line. Another problem caused by the scavenged eluent and regenerant tanks was that of low final sulfate concentration due to a dead space in the tanks themselves. This problem could be solved by either initiating a sulfate solution rinse of the eluent tank or by using a more concentrated eluent. But due to the time required to

Figure 3. Fixed-Bed Schematic

make adjustments in sulfate solution, the former method was used. The bulk sulfate concentration of the eluent was determined by taking a few extra samples at the end of a run.

The eluent tank was flushed because of the tendency of the sulfate to precipitate out from concentrated solution when the room temperature dropped below 20°C. Therefore, the eluent tank and its associated tubing were flushed with hot tap and deionized water, respectively. The high initial sulfate concentration was thus reduced by a factor of ten (from 50 ppm to 4 ppm SO_4^{2-}).

An additional preventive measure concerned the resin's ionic form. This preventive measure consisted of performing an initial regeneration on the fresh resin sample to ensure that it was in the free base form. The 4.0 wt % ammonia solution was used in batch mode with a mixing time of approximately 24 hours.

The unstable system flow-rates persisted throughout the experimental runs. The flow-rate could only be controlled through constant monitoring. The breakthrough curves obtained from the adopted experimental procedure provide good reproducibility and compare well with the Modeste's results. Figure 4 is a comparison of a typical breakthrough curve from Modeste's work⁽²⁾ with a similar one from the present study. The test conditions for this comparison are listed in Table 1. Although the pressure, flow-rate, and bed height were slightly different, the breakthrough curve from this study compares well with the Modeste's curve. A check for the internal reproducibility was also performed. The results, in the form of breakthrough curves, are shown in Figure 5. As shown by these curves, the revised fixed-bed system and the adopted procedure provide the adequate run reproducibility.

CG-2658

Figure 4. Comparison of Strevel's and Modeste's Breakthrough Curves.

CG-2659

Figure 5. Reproducibility Check for IRA-35 at 10 psig, 0.014 gm $\text{SO}_4^{2-}/\text{ml}$, 20.3 cm Bed Height, and 10.8 cc/min.

Table 1. Test Conditions for IRA-68 Breakthrough Curve Comparison

Basis: 0.028 gm SO_4^{2-} / ml Solution

Test Conditions	Present Study	Modeste's Study ⁽²⁾
CO ₂ -Pressure (psig)	10	5
Solution Flow-rate (cm ³ /min)	11	10
Resin Bed Height (in.)	16	18

3.2.2 Equilibrium Capacity

The test conditions used in this investigation to evaluate the effect of major process variables include: CO₂-pressure (10 -120 psig), solution concentration (0.006 - 0.028 gm SO_4^{2-} / ml), product inhibition (0, 0.1, & 1.0 molar ratios of KHCO₃/K₂SO₄), resin bed height (20.3 & 40.6 cm), dissolved impurities (spent seed), and superficial velocity (0.009 & 0.037 cm/s). Effects of these variables on the equilibrium capacity of resins in general are discussed here. However, the effects of each individual variable on ion-exchange kinetics and/or equilibrium capacity are discussed in further details in the Section 3.2.4.

The equilibrium capacities for each resin are tabulated versus CO₂-pressure in Table 2. Table 2 also includes the equilibrium capacities for IRA-68 that were determined by Butler⁽¹⁾ and Modeste⁽²⁾.

Table 2. Effect of CO₂-Pressure on Equilibrium Loading

Basis: 0.028 gm SO₄²⁻ / ml solution

CO ₂ -Pressure (psig)	IRA-35 (g SO ₄ ²⁻ / ml _R)	IRA-68 (g SO ₄ ²⁻ / ml _R)	IRA-93 (g SO ₄ ²⁻ / ml _R)
0	-	0.068 ^a	-
10	0.073	0.065	0.074
20	-	0.087 ^b	-
40	0.098	0.124 ^b	0.096
80	0.130	-	0.164
120	0.126	0.136	0.168

^a Butler (1)

^b Modeste (2) with 0.039 gm SO₄²⁻ / ml solution

R is for resin

In order to use Antonson's fixed-bed model, the relationship between the Langmuir isotherm and the reversible adsorption rate must be determined. The Langmuir isotherm is defined as

$$q_{\infty} = \frac{a_1 C_o}{1 + a_2 C_o} \quad (1)$$

The kinetic rate of reversible adsorption can be written as

$$\frac{dq}{d\theta} = k_1 C_o (C_T - q) - k_2 q \quad (2)$$

where k_1 is the forward reaction (adsorption) rate constant, k_2 is the backward reaction (desorption) rate constant, and C_T is the total concentration of available adsorption sites. When the ion-exchange system is at equilibrium, equation (2) is equal to zero and q is maximum and equal to q_{∞} . Hence, by comparing equations (1) and (2), the Langmuir constants, a_1 and a_2 , can be defined in terms of the rate constants, k_1 and k_2 , and the concentration of available exchange sites, C_T as:

$$a_1 = \frac{k_1}{k_2} C_T \quad (3)$$

$$a_2 = \frac{k_1}{k_2} \quad (4)$$

From equations (3) and (4), C_T can be derived in terms of the Langmuir constants as:

$$C_T = \frac{a_1}{a_2} \quad (5)$$

In other words C_T will be a constant for a given resin and process conditions and would not change with any parameter. However the Langmuir constants, a_1 and a_2 , would change with the reaction conditions, such as the CO_2 -pressure changes investigated in this study.

Using the fitted data from Butler⁽¹⁾, Modeste⁽²⁾ and the present investigation, a maximum experimental C_T -value, (defined as $\overline{C_T}$), can be determined for IRA-68. These $\overline{C_T}$ -values and their corresponding Langmuir constants are presented in Table 3. The pre-run CO_2 -pressure is the static CO_2 -pressure applied to the system prior to the exhaustion/carbonation step. The $\overline{C_T}$ -values seem to be dependent on the static CO_2 -pressure during the pre-run and the carbonation/exhaustion step. It is believed that the higher static CO_2 -pressures would create more bicarbonate ions on the resin. Since the bicarbonate ions can be easily replaced on the resin by the sulfate ions, the maximum concentration of sulfate ions that can be removed by the resin is approached as the CO_2 -pressure is increased. The CO_2 -pressure effect on the resin sites can be represented by the following reaction:

where R is the complex cation group on the resin.

In other words the capacity of the resin for sulfate would increase with CO₂-pressure. This conjecture is supported by the results in Table 2, which shows the equilibrium loading increasing as the static CO₂-pressure is increased.

Table 3. $\overline{C}_T$ Values for IRA-68

Study	a_1 (g SO ₄ ²⁻ / ml)	a_2 (dimension less)	$\overline{C}_T$ (g SO ₄ ²⁻ / ml)	CO ₂ - Pressure (psig)	Pre-Run CO ₂ - Pressure (psig)
Butler	24.23	318.7	0.076	0	None*
Modeste	74.07	830.2	0.089	20	20 (5 min)
	42.73	322.2	0.133	40	40 (5 min)
Present	3.13	19.0	0.165	10	50 (20 min)

* Butler carbonated the resin at atmospheric pressure with a CO₂ bubbling apparatus.

From Table 2 the resin's equilibrium loading seems to level-out around 80 psig. Therefore, the $\overline{C}_T$ -values should also level-out at the same pre-run CO₂-pressure. This means that the $\overline{C}_T$ -value for IRA-68 would approach a constant value at higher CO₂-pressures. Based on this, the highest experimental $\overline{C}_T$ -value of 0.165 g SO₄²⁻/ml resin was used to calculate the Langmuir constants for IRA-68 at higher static CO₂-pressures. These calculations used the following linearized form of the Langmuir isotherm,

$$\frac{1}{a_1} = \frac{C_o}{q_\infty} - \frac{1}{\overline{C}_T} C_o, \quad (6)$$

and the experimental values of C_o and q_∞ . Calculated values of a_1 and a_2 using this procedure are presented in Table 4.

Table 4. Calculated Langmuir Constants for IRA-68

CO ₂ - Pressure (psig)	$1/\overline{C_T}$ (g SO ₄ ²⁻ /ml)	a_1 (g SO ₄ ²⁻ /ml)	a_2 (dimensionless)
10	6.070	3.13	19.00
40-80	"	4.19	25.43
120	"	30.14	182.95

The $\overline{C_T}$ -values and respective Langmuir constants for IRA-35 and IRA-93 were obtained from fitting the experimental data at 10 psig. The same Langmuir constants were used for the higher CO₂-pressures because the actual experimental data were limited and the results from equation (6) would give a negative intercept. The $\overline{C_T}$ -values and the Langmuir constant used for the IRA-35 and IRA-93 resins are presented in Table 5.

Table 5. Calculated Langmuir Constants for IRA-35 and IRA-93

Resin	CO ₂ - Pressure (psig)	$1/\overline{C_T}$ (g SO ₄ ²⁻ /ml)	a_1 (g SO ₄ ²⁻ /ml)	a_2 (dimensionless)
IRA-35	10	13.58	12.66	171.9
IRA-93	10	12.27	20.07	246.3

Equation (6) when solved for the C_o / q_∞ gives

$$\frac{C_o}{q_\infty} = \frac{1}{a_1} + \frac{1}{\overline{C_T}} C_o. \quad (7)$$

These linearized Langmuir equilibrium isotherms for IRA-35, IRA-68, and IRA-93 are provided in Figures 6-8. These plots represent the least squares fits to the concentration and equilibrium loading data at various static CO₂-pressures. The calculated

Figure 6. Plot of Fitted Linearized Langmuir Isotherm for IRA-35

Figure 7. Plot of Fitted Linearized Langmuir Isotherm for IRA-68

CG-2677

Figure 8. Plot of Fitted Linearized Langmuir Isotherm for IRA-93

values of q_{∞} at various solution concentrations for IRA-35, IRA-68, and IRA-93 at a CO_2 -pressure of 10 psig are shown in Figure 9. IRA-93 seems to have the highest equilibrium loading at a given solution concentration.

3.2.3 Fixed-Bed Mathematical Model

Antonson's model was used to analyze the fixed-bed data. This model requires two inputs. These are a_2C_0 and X , the dimensionless column length ($X=3Da_1Z/mR^2v$). With these inputs, the model will generate a breakthrough curve which can be fitted to an experimental curve. Examples of the effect of X on C/C_0 at a fixed a_2C_0 and of a_2C_0 on C/C_0 at a fixed X are shown in Figures 10 and 11, respectively. In Figure 10 the increase in dimensionless column length, X , can be interpreted as the effect of increasing diffusion parameter, D/R^2 (or rate of intraparticle diffusion), or an increase in resin bed height, z , or a decrease in linear velocity, on C/C_0 values for a given resin. The model responds by shifting the curve's origin to the right and by changing their slopes from very small to large positive values. In Figure 11 the effect of decreasing a_2C_0 on the model's C/C_0 values represents the change from a highly non-linear equilibrium to a more linear equilibrium. Correspondingly, the curve's slopes change from very large values for large a_2C_0 to small values for small a_2C_0 . An example of the typical best fit for a run is shown in Figure 12. From the best fit, the diffusion parameter can be determined using the equation for the dimensionless column length, X . The diffusion parameter is presented in this work and the literature as the intraparticle diffusion coefficient, D , divided by the square of the particle radius, R .

Figure 9. Langmuir Isotherms for IRA-35, IRA-68, and IRA-93 at 10 psig CO_2 -Pressure

Figure 10. Effect of X on C/C_0 at $a_2 C_0 = 1.0$

Figure 11. Effect of $a_2 C_0$ on C/C_0 at $X = 1.0$.

CG-2681

CG-2682

Figure 12. Typical Best Fit: Run 59 (IRA-68, 10 psig, 0.004 g SO_4/ml , 20.3 cm Bed Height, 4.96 cm^2 Column Area, and 11.0 cc/min)

The calculated diffusion parameters for IRA-35, IRA-68 and IRA-93 are given in Table 6. When dissolved impurities (as in spent seed) are present in the test solution, the diffusion parameters are roughly the same for IRA-35 and IRA-93. However IRA-68's diffusion parameter for dissolved impurities is approximately half that of the parameter for the pure K_2SO_4 solution. The probable cause for this effect could be the temporary fouling of the pores caused by the large ions or non-ionic impurities present in the spent seed extract. IRA-35 and IRA-93 have a polymer matrix that possibly prevents large ions or particles from entering the porous resin bead by reducing the size of the pores. In Table 7 the range of diffusion parameters for this investigation are compared with those found in the literature. The D/R^2 range found by Modeste⁽²⁾ for IRA-68 compares well with the values found in the present investigation.

The diffusion parameters for each resin are plotted against CO_2 -pressure and solution concentration in Figures 13 and 14, respectively. In Figure 13 the general trend of the diffusion coefficients with increasing CO_2 -pressure is downward. Above 40 psig all the resins show roughly the similar downward trend of decreasing D/R^2 values. In Figure 14, as the solution concentration increases, the diffusion parameters also increase in value. The diffusion parameters for IRA-68 at 10 psig CO_2 -pressure from this study compare well with those found by Modeste⁽²⁾ at 20 psig and 40 psig CO_2 -pressure, and in general, show a higher average value than for the other two resins. IRA-35 and IRA-93 have average diffusion parameters that are very similar. The effective diffusion parameters seems to decrease in value as the superficial velocity increases. These observations are discussed in greater detail in section 3.2.4.

Figure 13. Effect of Static CO_2 -Pressure on Diffusion Parameter

CG-2684

Figure 14. Effect of Solution Concentration on Diffusion Parameter

Table 6. Calculated Diffusion Parameters for IRA-35, IRA-68 and IRA-93

C_o (g SO_4^{2-} /ml)	a_2C_o	CO_2 - Pressure (psig)	Column no.	X (dimensionless)	D/R ² (S ⁻¹) $\times 10^{-3}$
• IRA-35					
0.005	0.930	10	I	1.0	0.017
0.013	2.188	10	I	2.5	0.043
0.026	4.411	10	I	3.0	0.054
0.024	4.210	40	I	1.5	0.026
0.027	4.567	80	I	2.0	0.034
0.026	4.548	120	I	0.9	0.016
0.021*	3.531	10	I	3.0	0.052
0.026	4.504	10	II	2.0	0.008
• IRA-68					
0.004	0.076	10	I	2.0	0.143
0.012	0.228	10	I	0.6	0.043
0.025	0.475	10	I	3.0	0.215
0.024	0.610	40	I	2.0	0.018
0.021	0.534	80	I	2.5	0.022
0.026	4.757	120	I	0.8	0.006
0.021*	0.399	10	I	1.5	0.108
0.027	0.513	10	II	2.0	0.034
• IRA-93					
0.005	1.293	10	I	2.0	0.024
0.013	3.108	10	I	2.0	0.024
0.025	6.116	10	I	4.0	0.048
0.026	6.470	40	I	5.0	0.060
0.027	6.657	80	I	3.0	0.036
0.028	6.955	120	I	4.0	0.048
0.021*	5.145	10	I	5.0	0.060
0.027	6.537	10	II	4.0	0.011

* Spent Seed extract

Table 7. Comparison of the Diffusion Parameters with the Literature

System	Reference	Temperature (°C)	D/R ² (s ⁻¹) x 10 ³
SO ₄ ²⁻ / IRA-35	Present	21	0.008-0.054
SO ₄ ²⁻ / IRA-68	(2)	20	0.050-0.183
SO ₄ ²⁻ / IRA-68	Present	21	0.006-0.215
SO ₄ ²⁻ / IRA-93	Present	21	0.011-0.060

3.2.4 Effect of Process Variables

The process variable effects that will be discussed in this section include the effects of CO₂-pressure, solution concentration, product inhibition, resin bed height, dissolved impurities, and superficial velocity. The effects of these parameters on the resin performance were determined from their breakthrough curves and equilibrium loading.

3.2.4.1 Effect of Static CO₂-Pressure

In Table 2 the effect of static CO₂-pressure on equilibrium loading was given. From that table the upward trend in equilibrium loading can be easily seen. The optimum static CO₂-pressure seems to be around 80-120 psig. IRA-93 seems to have the highest equilibrium loading at a given solution concentration.

The typical effect of CO₂-pressure on the ion-exchange kinetics can be seen in Figure 15 for IRA-93. Figure 15 shows that the increased static CO₂-pressure slightly alters the shape of the breakthrough curve. The curve's shape changes from a somewhat steep S-curve at 10 psig and 40 psig CO₂-pressure to a slightly more linear

CG-2685

Figure 15. Effect of Static CO₂ -Pressure on IRA-93

(less steep) curve at 80 and 120 psig CO₂-pressure. This change in shape is possibly due to the increased sulfate loading on the resin at higher CO₂-pressures, which would slightly decrease the diffusion parameter, causing the overall X parameter to be slightly lower (see Figure 10).

3.2.4.2 Effect of Solution Concentration

The typical effect of concentration on the equilibrium loading is shown in Figure 9. From this figure of the non-linear Langmuir isotherms for IRA-35, IRA-68, and IRA-93 at CO₂-pressure of 10 psig, IRA-93 seems to respond better as the solution concentration increases.

The solution concentration affects the ion-exchange kinetics of IRA-93 very little as shown by the breakthrough curve's shapes in Figure 16. The breakthrough curve shape and the diffusion parameters given in Figure 16 and Table 6 for IRA-93 seem to show only a slight effect of concentration. Since the breakthrough curve's shape and the diffusion parameter are related, the effect of solution concentration on the ion-exchange kinetics of IRA-35 seems also to be very slight when considering the experimental scatter. From the diffusion parameters for IRA-68 given in Table 6 and Figure 14, the effect of solution concentration on the diffusion parameters seems to be significant. The increasing diffusion parameters means an increasing X parameter, which means the effect on the breakthrough curves for IRA-68 is similar to those presented in the Figure 10. This phenomenon may also be caused by the gel-type matrix of IRA-68, because gel-type resins usually have larger pores and, therefore, possibly better (or faster) intraparticle diffusion.

CG-2686

Figure 16. Effect of Solution Concentration on IRA-93

3.2.4.3 Effect of Product Inhibition

Product inhibition (PI) is defined as the interference caused by the product, KHCO_3 , to the operation of the ion-exchange resin. By competing for or by forcing the SO_4^{2-} ions from the complex sites on the resin, the product can reduce the resin's ability to remove SO_4^{2-} ions from the bulk phase solution. The magnitude of product inhibition for the experimental runs in this investigation is determined using solutions containing initially known molar ratios of $\text{KHCO}_3/\text{K}_2\text{SO}_4$. The pH of the $\text{KHCO}_3/\text{K}_2\text{SO}_4$ solution also changes with this molar ratio. The resulting pH values of the mixtures are also given in Table 8. The effects of product inhibition on equilibrium loading for the present and Butler's⁽¹⁾ investigations are presented in Table 8. Within experimental scatter, there seems to be no effect of product inhibition on the equilibrium loading of IRA-35. However, IRA-68 and IRA-93 seem to be affected by the product inhibition. For IRA-68 Butler⁽¹⁾ saw a similar effect of increase in equilibrium loading at the 0.1 molar ratio, followed by a significant decrease at a molar ratio of 1.0 and higher. We are still exploring the reasons for such behavior.

Table 8. Effect of Product Inhibition (PI) on Equilibrium Loading

Basis: $0.028 \text{ gm SO}_4^{2-} / \text{ml}$ solution and 10 nsig CO_2 -Pressure

Molar Ratio (PI)	IRA-35 (g $\text{SO}_4^{2-}/\text{ml}_R$)	IRA-68 (g $\text{SO}_4^{2-}/\text{ml}_R$)	IRA-93 (g $\text{SO}_4^{2-}/\text{ml}_R$)	Solution pH
0.0	0.073	0.065 0.063 _B	0.074	6.5
0.1	0.068	0.095 0.087 _B	0.098	9.1
1.0	0.072	0.061 0.047 _B	0.088	8.5

B is for Butler's⁽¹⁾ runs at atmospheric pressure

R is for resin

In Figure 17 the effect of product inhibition can be seen. The ion-exchange kinetics for IRA-68 measured in terms of the breakthrough curve shape does not seem to change with the increasing ratio of product (KHCO_3) in the initial bulk solution. However, the volume of eluent needed to exhaust the resin (that means resin's capacity) increases for the 0.1 molar ratio of $\text{KHCO}_3/\text{K}_2\text{SO}_4$. Butler⁽¹⁾ also saw a similar effect of product inhibition on the IRA-68.

3.2.4.4 Effect of Resin Bed Height

Height of the resin bed should not affect the equilibrium loading of the resin measured in terms of gm SO_4^{2-} /ml of resin. Hence only the kinetic effect was evaluated. The resin bed height affects the ion-exchange kinetics only slightly, if at all, when considering experimental error. The typical breakthrough curves presented in Figure 18 for IRA-93 as the fraction of sulfate removed versus the number of bed volumes shows this result. Here, bed volume is defined as the cumulative volume of the bulk solution introduced at any time divided by the volume of resin bed. The fact that the curves for two different bed heights overlap within experimental error proves that no channeling occurred. Channeling would result in not all of the resin bed being utilized and would show a steadily rising curve rather than a typical S-shaped curve. Butler⁽¹⁾ saw a similar phenomenon in the ion-exchange kinetics for IRA-68.

3.2.4.5 Effect of Dissolved Impurities

The effect of dissolved impurities on equilibrium loading and ion-exchange kinetics was evaluated using the MHD spent seed extract. This extract used in the present study contained about 588 ppm chloride as a major impurity. In Table 9 the

CG-2687

Figure 17. Effect of Product Inhibition on IRA-68

CG-2656

Figure 18. Effect of Resin Bed Height on IRA-93

effect on the resins' equilibrium loading is shown. There seems to be a slight effect on IRA-35; however, this could be the result of experimental error. On IRA-68 and IRA-93 resin, no change in equilibrium loading values is observed suggesting that low levels of dissolved impurities possibly did not change the capacity of these two resins. However, depending upon the MHD spent seed material, the concentrations of dissolved impurities could change and subsequently could cause a significant change in the resin's capacity for the sulfate ions. For the spent seed taken from the UTSI's MHD facility, the composition of the spent seed could change from test to test as this facility tests different parameters such as K₂/S ratio and coal type, etc., and it never reaches theoretically considered steady state conditions.

Table 9. Effect of Dissolved Impurities on Equilibrium Loading

Basis: 10.0 psig CO₂ and 0.028 gm SO₄²⁻/ml

SO ₄ ²⁻ Source	IRA-35 (g SO ₄ ²⁻ /ml _R)	IRA-68 (g SO ₄ ²⁻ /ml _R)	IRA-93 (g SO ₄ ²⁻ /ml _R)
Reagent	0.073	0.065	0.074
Spent Seed	0.058	0.060	0.076

R is for resin.

The typical effect of dissolved impurities on the ion-exchange kinetics is shown in Figure 19. This figure shows the breakthrough curves for the runs using a reagent grade potassium sulfate solution and a spent seed extract. Within the experimental error, the shape of the curves are approximately the same. Therefore, no change in the ion-exchange kinetics can be detected. From the batch mode screening results discussed in earlier progress reports, the diffusion parameters given in Table 6, and

CG-2657

Figure 19. Effect of Dissolved Impurities on IRA-68

the Figure 19, there seems to be a little or no effect of dissolved impurities on the ion-exchange kinetics of the three candidate resins. Butler⁽¹⁾ also showed a similar slight to no kinetic effect due to dissolved impurities.

3.2.4.6 Effect of Superficial Velocity

Superficial velocity is not expected to affect the equilibrium loading except at very high values. These high velocities could cause the bulk solution to partially or completely by-pass the resin bed material resulting in low values for the observed equilibrium capacities. Since we did not use such a high velocity, we evaluated only the effect on the ion-exchange kinetics for the three candidate resins.

From the typical normalized curves of C/C_0 versus the grams of sulfate introduced per unit volume of resin (i.e. $\text{gm SO}_4^-/\text{ml}_{\text{resin}}$) shown in Figure 20 for IRA-35 resin and the diffusion parameters given in Table 6, there seems to be a definite effect of superficial velocity on the ion-exchange kinetics. This effect is considered to be the result of the type of mass transfer step that would be controlling the overall mass transfer. For instance, in the case of IRA-35 at the higher superficial velocity of 0.036 cm/s, the mass transfer rate may be controlled by the solid-phase (intraparticle) diffusion. Whereas at the slower superficial velocity of 0.009 cm/s the mass transfer may be controlled by the liquid-film diffusion. For the former, the model developed by Antonson⁽³⁾ and used in the present work and that of Modeste⁽²⁾ would be a more appropriate model. For the latter the Selke and Bliss' model which Butler⁽¹⁾ used would be preferable. Butler⁽¹⁾ using the Selke and Bliss' model also saw a significant effect of superficial velocity on the ion-exchange kinetics of IRA-68 which he measured

CG-2688

Figure 20. Effect of Superficial Velocity on IRA-35

in terms of the parameter $K_L S$, (that is the product of liquid-film mass transfer coefficient (K_L) and the resin's effective surface area (S)). Based on these preliminary results, it seems necessary to use a math model or models that can incorporate different mass transfer controlling steps at different superficial velocities.

3.2.4.7 Effect of Solution pH

Effect of initial solution pH on the resin performance was evaluated by carrying out the fixed-bed experiments using 50,000 ppm K_2SO_4 solution (pH=7.5), and mixture of 50,000 ppm K_2SO_4 solution with a little acetic acid solution (pH=4.25). The resulting effect for all the three resins was similar in that the breakthrough curves for pH=4.25 moved slightly to the right of the curve for pH=7.5. However, the shape of the two curves did not change significantly (see typical curve for IRA-68 in Figure 21). This can be interpreted as slightly acidic solution at the inlet either helping in maintaining the acidic to neutral conditions as required in the entire bed and thereby improving the resin capacity or helping in improving the ionic mobility of the sulfate ions. We will evaluate this effort further in task 1.3 during our planned evaluation of the effect of performance enhancers. From the similar shapes of the breakthrough curves, we can say that solution pH did not change the ion-exchange kinetics significantly, and therefore, the diffusion parameter D/R^2 .

For industrial applications, the most important attributes of an ion-exchange resin are its high equilibrium capacity, high resistance to fouling by the dissolved impurities and, of course, the high diffusion coefficients. From the process variables study completed so far, none of the three candidate resins performed significantly

Figure 21. Effect of Solution pH on Breakthrough Curve for IRA-68.

better than the other resins in view of the above attributes. Therefore, no determination as to the best resin can be made with the available data. However, the data generated so far do provide a basis for future studies/investigations in evaluating these and other resins. Cyclic operations in a slightly larger test facility and optimized resin regeneration as well as the carbonation steps would certainly help in selecting the best resin.

3.3 Task 1.3

The batch mode experiments were carried out to optimize the resin regeneration step. In these experiments, a batch size of 25 ml of resin was used and the other conditions were kept similar to the ones used in our earlier batch mode screening experiments. The major parameters to be evaluated for this optimization study included ammonia concentration, resin-to-solution (regenerant) ratio and mixing time. Out of this, the ammonia concentration effect was evaluated earlier in task 1.1 and the results were reported in our earlier progress reports. As shown in Table 10, by changing the resin-to-solution ratio from 1:1 to 1:3, the percent SO_4^{2-} retained on the three candidate resins did not change significantly. The effects of mixing time for IRA-68 and -35 are shown in Table 11. As shown in this table, the percent SO_4^{2-} retained on the resin decreased monotonically as the mixing time was increased from 5 minutes to about 30 minutes. Beyond 30 minutes, the mixing time seems to have little effect considering the experimental error.

Table 10. Effect of Resin-to-Solution Ratio on Resin Regeneration

- Basis:
- 4 wt % ammonia solution
 - mixing time of 30 minutes
 - 50,000 ppm K_2SO_4 solution (for initial exhaustion step)

Resin-to-Solution Ratio	Percent SO_4^{2-} Retained		
	IRA-68	IRA-93	IRA-35
1:1	11.4	19.0	14.0
1:2	10.8	18.6	13.5
1:3	10.2	17.8	13.3

Table 11. Effect of Mixing Time on Resin Regeneration

- Basis:
- 4 wt % of ammonia solution
 - resin-to-solution ratio of 1:2
 - 50,000 ppm K_2SO_4 solution (for initial exhaustion step)

Mixing Time (minutes)	Percent SO_4^{2-} Retained	
	IRA-68	IRA-35
5	30.0	31.6
10	21.0	29.6
20	16.0	32.0
30	10.8	19.0
40	10.9	16.5

3.4 Task 1.4

3.4.1 Statistical Analysis of Batch Mode Results and Revised Utilities for Candidate Resins

The test parameters for the batch mode evaluations included cation (different alkali metals), cycle efficiency, solution concentration and dissolved impurities (spent seed). As reported in the last annual report (no. DOE/PC/90304-4) the candidate resins were screened by a batch experimental procedure developed for the purpose. The results of that batch mode screening experiments were analyzed by the analysis of variance, two-way fixed-effects model and a multiattribute technique.

3.4.1.1 Statistical Analysis

The analysis of variance, two-way fixed-effects model was used to determine the effects of resin type, solution concentration, cyclic operations, and cations on the resin's removal and regeneration efficiencies. The values used in these calculations were the first observations taken for each resin and test condition. The batch experimental procedure was developed before the first observation was made. Therefore, there was no learning curve associated with the results, freeing the data of any bias. Due to time constraints, only one observation was taken. This weakens the statistical results and combines the interaction (C-N-R) and error terms. Therefore, no interaction effect or error can be determined from the data. The test statistic is f_0 , which is the mean square (MS) resin and/or concentration divided by the mean square interaction. This test statistic follows the F-distribution. The f_0 's are compared with the appropriate values from a F-distribution table for a 95% confidence level that the null hypothesis is true, when it is true. In this analysis the null hypothesis is that none of the above factors affect the exhaustion or regeneration efficiency. When the f_0 and the F-distribution table values are relatively close in magnitude, the conclusions drawn from the analysis are conditional⁽⁴⁾. The terms, SS and DF used in this analysis represent the sum of square and the degrees of freedom respectively. In Table 12, the comparison of the test statistic with the appropriate value from a F-distribution table shows that the resin type and solution concentration definitely affect the SO_4^{2-} removal efficiency. Based on non-linear Langmuir type of equilibrium isotherm satisfactorily fitting the fixed-bed data, increasing solution concentration should have an effect on the resin performance.

Table 12. Resin and Concentration Effects on Exhaustion Efficiency

Source	SS	DF	MS	f_0	$F_{0.05, 9, 18}$ $F_{0.05, 2, 18}$	Effect
Resin	8100.640	9	900.071	11.912	2.46	Yes
Conc.	19603.409	2	9801.704	129.717	3.55	Yes
C-N-R	1360.125	18	75.562	.000		
Error	.000	0	.000			
Total	29064.170	29				

Table 13 deals with the effect of resin type and solution concentration on the regeneration step of the batch procedure. The percent retained is 100 minus the regeneration efficiency. In Table 13, the only effect on the regeneration efficiency is found to be due to the resin type.

Table 13. Resin and Concentration Effects on Regeneration Efficiency

Source	SS	DF	MS	f_0	$F_{0.05, 9, 18}$ $F_{0.05, 2, 18}$	Effect
Resin	8953.116	9	994.791	15.237	2.46	Yes
Conc.	396.861	2	198.430	3.039	3.55	No
C-N-R	1175.173	18	65.287	.000		
Error	.000	0	.000			
Total	10525.150	29				

Tables 14 and 15 deal with the effect of resin type and cyclic operations (4 cycles) on the exhaustion and regeneration efficiency. The solution concentration used was 25K ppm K_2SO_4 . Table 14 shows that there is definitely an effect due to resin type on exhaustion efficiency. Also in Table 14 the analysis leads to the conclusion that 4 consecutive cycles of exhaustion and regeneration do not affect the exhaustion efficiency which is expected for a good commercial resin.

Table 14. Resin and Cycle Effects on Exhaustion Efficiency

Source	SS	DF	MS	t_0	$F_{0.05, 10, 30}$ $F_{0.05, 3, 30}$	Effect
Resin	20055.329	10	2005.533	82.377	2.16	Yes
Cycle	17.849	3	5.950	.244	2.92	No
C-N-R	730.371	30	24.346	.000		
Error	.000	0	.000			
Total	20803.550	43				

Table 15 deals with the effect of resin type and cyclic operation on the regeneration efficiency. Also in Table 15 the results from the fixed-effects calculations imply that both the resin type and exhaustion-regeneration cycles affect the regeneration efficiency. In some resins this means that the resin regeneration performance improves. In other cases the regeneration performance deteriorates or is erratic. Theoretically, the regeneration efficiency for 4 consecutive cycles on a relatively new resin sample should either improve or remain constant. This observed inconsistent behavior is probably due to the lack of multiple observations and few number of cycles.

Table 15. Resin and Cycle Effects on Regeneration Efficiency

Source	SS	DF	MS	t_0	$F_{0.05, 10, 30}$ $F_{0.05, 3, 30}$	Effect
Resin	5850.810	10	585.081	7.681	2.16	Yes
Cycle	3466.507	3	1155.502	15.170	2.92	Yes
C-N-R	2285.108	30	76.170	.000		
Error	.000	0	.000			
Total	11602.430	43				

Tables 16 and 17 deal with the effects of resin type and cation (sodium versus potassium sulfate) on the exhaustion and regeneration efficiency. The solutions used

were 25K ppm K_2SO_4 and 20.4K ppm Na_2SO_4 . These solutions contain the same molar concentration of sulfate ion. Table 16 shows that there is only an effect of resin type on percent removal. Similarly, the resin type definitely has an effect on the regeneration efficiency. The cations, however, have no effect on the percent removed or retained, because no cations are involved in the exhaustion and regeneration steps.

Table 16. Resin and Cation Effects on Exhaustion Efficiency

Source	SS	DF	MS	f_0	$F_{0.05, 4, 4}$ $F_{0.05, 1, 4}$	Effect
Resin	2350.054	4	587.514	255.053	6.39	Yes
Cation	16.641	1	16.641	7.224	7.71	No
C-N-R	9.214	4	2.303	.000		
Error	.000	0	.000			
Total	2375.909	9				

Table 17. Resin and Cation Effects on Regeneration Efficiency

Source	SS	DF	MS	f_0	$F_{0.05, 4, 4}$ $F_{0.05, 1, 4}$	Effect
Resin	1897.994	4	474.499	40.717	6.39	Yes
Cation	10.816	1	10.816	.928	7.71	No
C-N-R	46.614	4	11.654	.000		
Error	.000	0	.000			
Total	1955.424	9				

In Tables 18 and 19, the effect of sulfate source (i.e. pure reagent grade K_2SO_4 versus spent seed extract from the MHD Baghouse/ESP material) and resin type on the exhaustion and regeneration efficiencies are determined. In addition to potassium and sulfate, the spent seed extract also contains other dissolved impurities. Table 18

shows that there is definitely an effect due to resin type. However, there is no effect due to dissolved impurities. In Table 19, the similar analysis was performed to determine the effect on resin regeneration efficiency or the percent retained. Again, as shown in Table 19, the only parameter that affects the percent retained is the resin type, and the dissolved impurities have no effect.

Table 18. Resin and Seed Effect on Exhaustion Efficiency

Source	SS	DF	MS	t_0	$F_{0.05, 4, 4}$ $F_{0.05, 1, 4}$	Effect
Resin	2110.610	4	527.652	81.573	6.39	Yes
Seed*	2.401	1	2.401	.371	7.71	No
C-N-R	25.874	4	6.469	.000		
Error	.000	0	.000			
Total	2138.885	9				

* Seed extract from MHD spent seed

Table 19. Resin and Seed Effect on Regeneration Efficiency

Source	SS	DF	MS	t_0	$F_{0.05, 4, 4}$ $F_{0.05, 1, 4}$	Effect
Resin	2110.610	4	527.652	81.573	6.39	Yes
Seed*	2.401	1	2.401	.371	7.71	No
C-N-R	25.874	4	6.469	.000		
Error	.000	0	.000			
Total	2138.885	9				

* Seed extract from MHD spent seed

In summary, the exhaustion and regeneration efficiencies are not affected by the same parameters. The only exception to this statement is the resin type, which strongly affects both the exhaustion and regeneration efficiencies. The exhaustion efficiencies are affected by the resin type and the solution concentration. The regeneration efficiency is affected by the resin type and the cycling between the exhaustion

and regeneration steps. Table 20 summarizes the major parameters that affect the exhaustion and regeneration efficiencies.

Table 20. Parameter Effects on Exhaustion and Regeneration Efficiencies

Parameter	Efficiency	
	Exhaustion	Regeneration
Resin Type	*	*
Solution Concentration	*	-
Cyclic Operation	-	*
Cation (Na vs. K)	-	-
Dissolved impurities (Spent Seed)	-	-

* : Effect; - : No Effect

3.4.1.2 Multiattribute Analysis

Multiattribute analysis involves the use of an importance rating and a utility scheme to determine the best of several alternatives⁽⁵⁾. For the data from the batch screening experiments, the scheme developed considered the percent removal as the most important result. The importance of the resin's performance for each test condition were also established. Table 21 lists the importance ratings in two columns. The first column lists the importance of each parameter. The second column lists the importance of the attributes contained within each parameter. These ratings were arbitrarily chosen to reflect the results of the previous section, which means that the high solution concentration and cyclic operations were given the most importance. The percent removal was given slightly more importance than the percent retained.

Table 21. Parameter Importance Ratings

Parameter Rating (k_p)		Attribute Rating (k_A)	
Concentration	0.3	Removal	0.6
Cycles	0.3	Retained	0.4
Cation	0.2		
Seed	0.2		
Total	1.0		1.0

The batch screening data presented in the earlier annual report (no. DOE/PC/90309-4) were used in the weighting calculations. These calculations consisted of averaging the removal and retained percentages to reflect the resin's ability to handle concentration changes, repeated cycles of exhaustion and regeneration, and cation interference. The values associated with the spent seed extract were used as the weights corresponding to the resins tendency to be fouled by the dissolved impurities.

For each of the parameters listed in Table 21, their individual utilities were calculated using the additive utility model,

$$U_p = \sum_{A=1}^n k_A U_A. \quad (8)$$

where U_p is the utility of the parameter, k_A is the importance rating for the attributes, and U_A is the utility of the attributes. The attribute's utility function for the interval between 0 and 1 is given by:

$$U_A = 1 - \sqrt{1 - X^2} \quad (9)$$

where

$$X = \frac{X_A - X_i}{X_f - X_i}.$$

X_A is either the percent removal or retained, X_i is the beginning of the interval, and X_f is the end of the interval. For the percent removal X_i and X_f are 0 and 100, respectively. These values are reversed for the percent retained. This type of utility function gives more weight to those removal or retained percentages that are closer to their ideal values (that is 100% for removal and 0% for retained) than to those less than 10 points of their ideal value (e.g. 90% for removal and 10% for retained). The utility for each resin was then calculated using

$$U_R = \sum_{P=1}^4 k_P U_P, \quad (10)$$

where U_R is the utility of the resin and k_P is the importance rating of the parameter⁽⁵⁾. For a resin to achieve a utility of 1.0, all of the percent removal and retained values must be ideal and equal to 1.0. The calculated resin utilities are given in Table 22. The best resins from the statistical analysis were found to be IRA-35, IRA-68, and IRA-93, and therefore, were used for the process variables study discussed earlier under Task 1.2.

Table 22. The Calculated Resin Utilities

Resin	Utility (U_R)
IRA-68	0.46
IRA-35	0.43
IRA-93	0.29
A-305	0.18
UNKNOWN	0.16
IRA-94	0.12
MWA-1	0.11
WGR-2	0.11
A-7	0.10
AFP-329	0.10
A-365	0.07

3.4.2 Trade-Off Between Solution Concentration and Evaporation/Concentration Load

In order to develop the Best Process Schematic, it will be necessary to determine the trade-off between the solution concentration used during the resin exhaustion step and the subsequent evaporation/concentration load. Dilute feed solutions (concentration less than 1 wt %) gives a sulfate removal efficiency that approaches 100%. On the other hand, the resin efficiency drops to the 50-60% range for concentrated feed solutions (concentration ≥ 10 wt %). This would necessitate the use of significantly more resin than predicted by the theoretical equilibrium capacity. Thus, in general, the dilute solution would require lower resin cost than concentrated solution. Consequently, the dilute solution would require a significantly greater evaporation/concentration than the concentrated solution. For example, for a 1 wt % solution, 99 lbs of water will need to be removed by evaporation or other schemes per pound of dry salt. Compared to this, from a 10 wt % solution, one will need to remove

only 9 lbs of water per pound of dry salt. Hence, a trade-off study was necessary to determine the optimum solution concentration and the related evaporation/concentration load.

Evaporation alone cannot be economical in this case and must be used in combination with other unit operations. Reverse Osmosis (RO) can be used as an initial concentration step for dilute solution which can be further concentrated by multiple-effect evaporation. RO is considered suitable because it has proven to be economical and energy efficient for salt solutions in desalination industries and is finding more and more applications in the concentration of similar solutions in the paper and pulp industries.

To carry out this trade-off study, two alternative schemes were considered for the concentration of dilute effluents from the exhaustion step. They are:

- 1) Process schematic using Reverse Osmosis (R.O.) in combination with the subsequent evaporation in multiple-effect evaporator, (see Figure 22) and
- 2) Total concentration using evaporation in multiple-effect evaporator (see Figure 23).

In the first schematic the initial concentration was carried out by using R.O. from 1 wt % to 5 wt %. The solution was further concentrated to 47 wt % by using multiple-effect evaporation. Our preliminary results show that for this scheme, the annualized cost per 1000 lbs of potassium salt concentrated will be higher by about 12% over the evaporation alone. The higher cost can be attributed to the high cost of replacement of membranes. Development and availability of a cheaper membrane would perhaps

Figure 22. Process Schematic for Dilute Effluents

Figure 23. Process Schematic for Concentrated Effluents

make this scheme more competitive. In R.O., the best possible rejection ratio realized is around 97% to 98%. Thus, there is also a loss of 2 to 3% of incoming carbonate/bicarbonate solution. This factor would also contribute to the higher costs.

Thus, evaporation in multiple-effect evaporator still remains the most suitable scheme. The availability of low pressure steam at lower costs in the system integrated with the power plant would make it still more attractive. To develop the optimum evaporator design, calculations were also performed to find out the optimum number of effects. Addition of an effect would improve the steam economy but in turn would also add to the fixed cost of the equipment. It was found from our preliminary calculations that the relative cost of evaporation per 1000 lbs of potassium salt purified goes down from a triple effect to a five effect evaporator (see Figure 24). The analysis of the relative cost of evaporation was then extended to various inlet solution concentrations. It was found that the cost of evaporation would go down as the inlet concentration increases. (See Figure 25). Results of these preliminary calculations will be further refined when we have optimized all the processing steps and developed the "Best Process Schematic."

3.5 Task 1.5

The following activities required by the DOE contracting office were completed as a part of this task.

CG-2544

Figure 24. Effect of Solution Concentration and Number of Evaporator Effects on Relative Cost of Concentration

CG-2545

Figure 25. Effect of Solution Concentration on Relative Cost of Concentration for 4-Effect Evaporator

- The first annual technical progress report (report no. DOE/PC/90309-4) covering the performance period from August 9, 1990 - September 30, 1991, as well as three quarterly technical progress reports covering the performance periods from October 1, 1991 - June 30, 1992 were issued.
- On June 17, 1992, the program participants (Sheth and Strevel) presented the mid-way progress of the project to the technical program officer (Dr. Soung Kim) and DOE/MHD contract management personnel at the DOE/PETC office.
- Two of the program participants (Sheth and Strevel), attended the Contractors' Review Meeting organized by DOE/PETC during June 15-17, 1992 in Pittsburgh and presented the work done so far to the meeting attendees.
- Submitted for review and acceptance an abstract entitled, "Spent Seed Regeneration in Coal-Fired MHD System Using Weak-Base Anion-Exchange Resins," to the program organizers of the 5th International Conference on Processing and Utilization of High Sulfur Coals, to be held from October 24-28, 1993 at Lexington, Kentucky.
- Sterling Strevel completed his M.S. thesis based on the work done on this grant in the first two years. He has received his M.S. degree in Engineering Science and Mechanics from UT and his thesis will be available shortly for anyone's use from UT/UTSI libraries.

To date, the project is still about 6 weeks behind schedule. By readjusting the priorities and revising project scope, we plan to get back on schedule as soon as possible. However, we are still well within our budget.

4.0 PLANS FOR NEXT REPORTING PERIOD

During the next reporting period, we plan to complete the bench scale experiments to optimize the resin regeneration step, to evaluate the effect of organic acids in improving the exhaustion efficiency of candidate resins, and to carry out (in limited scope) evaluation of the resin's cycle efficiency. Analysis of these experiments will provide the basis for developing the "Best Process Schematic," and related process economics.

5.0 SUMMARY

Work performed during this reporting period is summarized as follows:

- Completed statistical and multiattribute analyses of the batch mode screening experiments. The results supported the selection of three candidate resins (IRA-68, -38, and -93) for the process variables study using fixed-bed set-up.
- Put together a fixed-bed set-up, carried out shakedown experiments and revised the set-up as necessary.
- Developed experimental procedure for the revised fixed-bed set-up and completed process variables study using three selected resins (i.e. IRA-68, -35 and -93).
- Using the model/approach used by Modeste⁽²⁾, we have analyzed the experimental results from our evaluations of the various process variables such as solution concentrations, bed height, CO₂-pressure, dissolved impurities, product inhibition and superficial velocity. From the analysis carried out so far, the CO₂-pressure, superficial velocity and solution concentration seem to have significant effect on the equilibrium loading and/or ion-exchange kinetics. Also, from the three candidate resins, no clear cut winner has been found yet. After the resin regeneration step is optimized and we are able to carry out a limited number of cyclic operations then only we may be able to select the "best" resin.

- From our preliminary calculations, the solution concentration scheme making use of reverse osmosis to concentrate very dilute carbonate/bi-carbonate solution (i.e. < 5 wt % solution) is found to be more expensive than a multi-effect evaporator scheme. Also, 5-effects evaporator is found to be better than a 3-effects evaporator and the relative cost of concentration by mere evaporation seems to asymptotically fall as the solution concentration increases to about 10 wt % strength.
- Attended the conference on projects under the University Coal Research and Historically Black Colleges and University Programs, sponsored by DOE/PETC in Pittsburgh during June 15-17, 1992 and presented the work done so far to the meeting attendees.
- Also, presented the mid-way progress of the project to the DOE/PETC technical program officer (Dr. Soung Kim) and DOE/MHD contract management personnel.

At present, the project is slightly behind schedule but well within the cost.

6.0 REFERENCES

1. Butler, W.A., "Bench Scale Evaluation of Anion-Exchange Resin-Based Seed Regeneration Concept for Coal-Fired Magnetohydrodynamics Power System," a thesis presented for M.S. degree, The University of Tennessee Space Institute, December 1986.
2. Modeste, D.C., "Evaluation of Improved Anion-Exchange Resin-Based Seed Regeneration Concept for Coal-Fired MHD Power System," a thesis presented for M.S. degree, The University of Tennessee Space Institute, December 1988.
3. Antonson, C.R., "Adsorption of Ethane in Molecular Sieve Particles," a Ph.D. Dissertation submitted to Northwestern University, Evanston, Illinois, 1968.
4. Hines, William W. and Montgomery, Douglas C., "Probability and Statistics in Engineering and Management Science," Wiley, New York, 1990.
5. Canada, John R, and Sullivan, W.C., "Economic and Multiattribute Evaluation of Advanced Manufacturing System," Prentice Hall, New Jersey, 1989.

END

**DATE
FILMED**

2 / 24 / 93