2.
WSRC-RP--92-346

DE93 002814

FORMATION RATE OF AMMONIUM NITRATE IN THE OFF-GAS LINE OF SRAT AND SME IN DWPF (U)

by L. Lee

Westinghouse Savannah River Company
Savannah River Site
Aiken, South Carolina 29808

This paper was prepared in connection with work done under Contract No. DE-AC09-89SR18035 with the U. S. Department of Energy. By acceptance of this paper, the publisher and/or recipient acknowledges the U. S. Government's right to retain a nonexclusive, royalty-free license in and to any copyright covering this paper, along with the right to reproduce and to authorize others to reproduce all or part of the copyrighted paper.

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED *Se*

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

This report has been reproduced directly from the best available copy.

Available to DOE and DOE contractors from the Office of Scientific and Technical Information, P.O. Box 62, Oak Ridge, TN 37831; prices available from (615) 576-8401, FTS 626-8401.

Available to the public from the National Technical Information Service, U.S. Department of Commerce, 5285 Port Royal Rd., Springfield, VA 22161.

Westinghouse Savannah River Company
Savannah River Laboratory

WSRC-RP-92-346

Keywords: Ammonium Nitrate
Ammonia, SRAT,
SME, Mathematical
Model

Retention Period: Permanent

CC E. W. Holtzscheiter, 773-A
C. T. Randall, 704-T
J. T. Carter, 704-1T
N. Hutson, 704-1T
J. R. Zamecnik, 704-1T
R. A. Jacobs, 704-T
C. W. Hsu, 704-1T
J. C. Marek, 704-T
PMC File, 704-T
SRL Records (4)

February 25, 1992

To: L. F. Landon, 7045-T

From: L. Lee, 704-T *Lee*

**FORMATION RATE OF AMMONIUM NITRATE IN THE OFF-GAS
LINE OF SRAT AND SME IN DWPF (U)**

I: SUMMARY:

A mathematical model for the formation rate of ammonium nitrate in the off-gas line of the Sludge Receipt and Adjustment Tank (SRAT) and the Slurry Mixed Evaporator (SME) in DWPF has been developed. The formation rate of ammonium nitrate in the off-gas line depends on pH, temperature, volume and total concentration of ammonia and ammonium ion. Based on a typical SRAT and SME cycle in DWPF, this model predicts the SRAT contributes about 50 lbs of ammonium nitrate while SME contributes about 60 lbs of ammonium nitrate to the off-gas line.

Authorized Derivative Classifier:

C. T. Randall

This report provides a preliminary ammonium nitrate formation rate expected during the melter feed preparation cycles. These data may serve as a preliminary design basis for the scrubber jumpers to be installed in the Chemical Processing Cell (CPC) to mitigate ammonium nitrate accumulation downstream of the HEME. The accuracy of this model will be tested by comparing it with data obtained from coming IDMS experiments.

II. DETAIL:

Feeds to the SRAT and SME contain ammonia and ammonium ion. Under the feed preparation conditions some of this ammonia may vaporize from the SRAT and SME and react with NO_x in the off-gas line and lead to deposition of ammonium nitrate in the vapor line. When the solution pH is below 6 most of the ammonia exists as ammonium ion, which is nonvolatile. But if the solution pH is above 9 most of the ammonium ion converts to free ammonia, which is easily vaporized under the process conditions. The volatilized ammonia reacts with NO_x in the off-gas and forms ammonium nitrate deposits. Therefore, it is obvious that the formation rate of ammonium nitrate in the off-gas line is highly pH dependent. To minimize the deposition of ammonium nitrate, it is desirable to keep the SRAT and SME at a pH as low as achievable. As an indicator of ammonia volatility, the percent free ammonia as a function of solution pH is given in Figure 1. The equations which lead to Figure 1 are summarized in Appendix I.

Figure 2 gives ammonia partial pressure, in mm Hg, as a function of solution pH and temperature. It is readily seen that the ammonia partial pressure increases with solution pH and temperature. The increase is far more pH dependent than temperature dependent. This reaffirmed the previous conclusion that to minimize ammonium nitrate deposition in the off-gas line, it is imperative to keep the solution pH at the minimum possible value.

Figure 3 gives the mass transfer coefficient of ammonia from the liquid interface into the vapor space as a function of solution temperature. The strength of natural convection increases as the solution temperature increases. Therefore, the ammonia mass transfer coefficient increases with solution temperature. The increase is much more pronounced at low temperatures than at higher temperatures as expected.

FIGURE 1: PERCENT FREE AMMONIA

FIGURE 2: NH₃ PARTIAL PRESSURE, MM Hg. AT 1000 PPM TOTAL AMMONIUM ION CONC

FIGURE 3: MASS TRANSFER COEFFICIENT FOR AMMONIA IN LB-MOLE/FT²/HR

FIGURE 4: SRAT pH AND TEMPERATURE AS FUNCTION OF TIME

Figure 4 gives detailed pH and temperature profiles for the SRAT during a typical cycle. The pH of the heel is about 8; it increases to about 12 when a new batch of sludge is mixed with the heel. The pH is then reduced to about 5 during formic acid addition and maintained at that value during PHA addition. The pH rises slowly during refluxing and boil off; this is caused by decomposition of formic acid. It reaches a value of about 8 after the cycle. The temperature and the pH share the same scale because the temperature values on the figure have been reduced by a factor of 10.

With the temperature and pH profiles given in Figure 4, with 960 ppm, 300 ppm and 1500 ppm of ammonium ion in the heel, sludge and PHA, respectively, the total ammonium nitrate deposited in the off-gas line is about 50 lbs. The final ammonium concentration in the SRAT is about 960 ppm. Figure 5 gives the total amount of ammonium nitrate deposited in the off-gas line as a function of SRAT processing time. The pH profile during the SRAT cycles are superimposed to show the sensitivity of ammonium nitrate deposition rate to the the solution pH.

Figure 6 gives the total ammonium nitrate deposition in the SME off-gas line as a function of time. To give a higher estimation of ammonium nitrate deposition rate, the pH of SME is assumed to be 9 throughout the cycle. The initial and the final ammonium nitrate deposition rates are slow because the total ammonium ion concentration is very low, only about 6 ppm. When a new batch of feed from the SRAT containing about 960 ppm of ammonium ion is added into the SME the ammonium nitrate deposition rate takes off immediately. The rate gradually tappers off as the total ammonium ion concentration is depleted. The final ammonium ion concentration in the finished SME is only about 6 ppm. The ammonium nitrate deposits in the off-gas line resulting from the SRAT and the SME cycle are about 50 and 60 lbs, respectively. Therefore, the total ammonium nitrate deposition from a complete feed preparation cycle is about 110 lbs.

The derivation of the mathematical model is given in Appendix I. BASIC programs based on the model are given in Appendix II for the SRAT and Appendix III for the SME.

FIGURE 5: SLURRY pH AND TOTAL NH_4NO_3 DEPOSITED IN THE VAPOR LINE (SRAT)

FIGURE 6: TOTAL NH_4NO_3 DEPOSITED IN THE VAPOR LINE (SME)

III. QUALITY ASSURANCE:

The computer subroutine used to solve simultaneous differential and algebraic equations has been tested with problems with known answers and the agreement are excellent. The physical properties of the system such as Henry's constant, ionization constant of ammonia are taken from Perry's Chemical Engineering Handbook and CRC Handbook, both are respectable data sources. The mass transfer coefficient for ammonia in the vapor space are calculated based on Colburn's heat and mass transfer analogy which is a well accepted practice in chemical engineering calculations. Finally, the calculated results will be compared with the upcoming IDMS data to verify the accuracy of the model.

APPENDIX I: MATHEMATICAL MODEL FOR AMMONIA VOLATILITY FROM DWPF FEED PREPARATION CYCLE

I. CHEMICAL EQUILIBRIUM OF AMMONIA IN WATER:

The chemical equilibrium of ammonia in water can be represented by Eq(1).

According to the mass action law, the equilibrium can be expressed by Eq(2).

$$[\text{NH}_4] [\text{OH}] / [\text{NH}_3] = K_b \quad (2)$$

K_b = the ionization constant for ammonia in water. Let T_o = total ammonium ion and ammonia concentration in lb-mole/ft³ and M = free ammonia concentration. Then Eq(2) can be rewritten as:

$$(T_o - M) [\text{OH}] / M = K_b \quad (3)$$

Taking logarithm of Eq(3) and substituting $(\text{pH} - 14)$ for $\text{Log} [\text{OH}]$, $\text{p}K_b$ for $-\text{Log} (K_b)$ and P_s for $\text{p}K_b + \text{pH} - 14$ Eq(3) becomes:

$$\text{Log} \{ M / (T_o - M) \} = P_s \quad (4) \text{ and}$$

$$P_s = \text{p}K_b + \text{pH} - 14 \quad (5)$$

pK_b of ammonia in water are taken from the 64th edition of CRC Handbook D-169, and can be represented by Eq(6).

$$pK_b = 5.2209 - 0.24448 * \text{Log}(T) \quad (6)$$

T = solution temperature is oF. Eq(4) can be rearranged to give Eq(5), mole fraction of free ammonia.

$$M/T_o = 10^{\wedge} P_s / (1 + 10^{\wedge} P_s) \quad (7)$$

Figure 1 gives percent of free ammonia as a function of pH, which is a graphical representation of Eq(5), Eq(6) and Eq(7).

II. PARTIAL PRESSURE OF AMMONIA:

Partial pressure of ammonia can be calculated by Henry's law, which is given in Eq(8).

$$P = H X \quad (8)$$

where, P = partial pressure of ammonia in mm Hg, H = Henry's constant also in mm Hg and X is mole fraction of free ammonia in the solution. Henry's constant for ammonia in water is taken from the 6th edition of Perry's Chemical Engineering Handbook p 3-101 and can be represented by Eq(9).

$$H = 137.84 * 10^{\wedge} (0.009622 * T) \quad (9)$$

The mole fraction of free ammonia in the solution can be obtained from Eq(7) and is given in Eq(10).

$$X = (18/62.4) * [10^{\wedge} P_s / (1 + P_s)] * T_o \quad (10)$$

Figure 2 gives the partial pressure of ammonia in mm Hg as a function of solution temperature in oF, which is a graphical representation of Eq(8), Eq(9) and Eq(10).

III. MASS TRANSFER COEFFICIENT OF AMMONIA IN THE VAPOR SPACE:

The SRAT and SME are assumed to be well-mixed so that the resistance to mass transfer is only limited by the vapor phase. The vapor phase mass transfer coefficient is estimated based on the heat and mass

transfer analogy of Colburn (see Perry's Chemical Engineering Handbook p 14-14).

$$(KG/G_m) * (U_G/P_G/D)^{(2/3)} = (h/C_p/G) * (Pr)^{(2/3)} \quad (11)$$

where, KG = mass transfer coefficient in lb-mole/ft²/hr
 G_m = molar mass velocity in lb-mole/ft²/hr
 U_G = viscosity of air in lb/ft/hr
 P_G = density of air in lb/ft³
 D = diffusivity of ammonia in air in ft²/hr/hr
 h = heat transfer coefficient in Btu/ft²/hr/oF
 C_p = heat capacity of air in Btu/lb
 G = mass velocity in lb/ft²/hr
 Pr = Prandtl number for air which is 0.69.

Substituting all known properties of the system into Eq(11), it may be simplified to Eq(12), a relationship between the heat transfer coefficient and the mass transfer coefficient.

$$KG = 0.2661 h \quad (12)$$

Therefore, if the heat transfer coefficient for natural convection is known, the mass transfer coefficient can be calculated from Eq(12). The natural convective heat transfer coefficient for the vapor phase is given by Eq(13).

$$(h * d/k) = 0.15 * (Gr * Pr)^{(1/3)} \quad (13)$$

where, d = diameter of the vessel in ft
 k = thermal conductivity of air in Btu/ft/hr/oF
 Gr = Grasof's number

Figure 3 gives the mass transfer coefficient of ammonia in the vapor space as a function of solution temperature, which is a graphical representation of Eq(12) and Eq(13).

IV. MATHEMATICAL EQUATION FOR AMMONIA VOLATILITY:

Three assumptions are made to simplify the formulation of the model, and they are:

1. Liquid phase is well-mixed.

2. For conservative estimation, the concentration of NH_3 in the bulk vapor phase is negligible.
3. There is equilibrium for NH_3 between the vapor phase and the liquid phase in the condenser, ie. condenser behaves as an equilibrium stage.

With these assumptions, the material balance for the liquid phase is given in Eq(14).

$$V \cdot (dC_1/dt) = -K_G \cdot A \cdot (P/P_t) + F \cdot C_F + E \cdot R \cdot C_2 \quad (14)$$

where,

- V= liquid volume, function of time in ft^3
- E= liquid evaporation rate, ft^3/hr
- F= liquid feed rate, ft^3/hr
- C_1 = concentration of total ammonium ion and ammonia in the liquid phase in $\text{lb-mole}/\text{ft}^3$.
- C_2 = concentration of total ammonium ion and ammonia in the condensate in $\text{lb-mole}/\text{ft}^3$.
- C_F = concentration of total ammonium ion and ammonia in the liquid feed in $\text{lb-mole}/\text{ft}^3$.
- R= is an index when the pot is boiling. $R=1$ during refluxing, $R=-1$ during boil down and $R=0$ for other conditions.
- P_t = total pressure in the vapor phase in mm Hg.
- t= time in hr.
- A= cross sectional area for the pot in ft^2 .

The partial pressure of ammonia is given by Eq(15).

$$P = H \cdot X \quad (15)$$

Mole fraction of free ammonia is given in Eq(16).

$$X = (18/62.4) \cdot \{10^5 P_s / (1 + 10^5 P_s)\} \cdot C_1 \quad (16)$$

Eq(14), Eq(15) and Eq(16) are simultaneous differential and algebraic equations which are solved by the Generalized Runge-Kutta's method. Detailed BASIC programs for this method are given in Appendix II and Appendix III. During boil down and refluxing the following equations for the condenser are required.

The material balance for the condenser during boil down or refluxing is given in Eq(17).

$$C_2 * E + F_A * (P'/P_t) = K_G * A * (P/P_t) \quad (17)$$

where, F_A = air flow rate through the condenser in lb-mole/hr.
 P' = ammonia partial pressure in the condenser, mm Hg.

The partial pressure of ammonia in the condenser is given by Eq(18), which is Henry's law.

$$C_2 / (62.4/18) * H' = P' \quad (18)$$

Henry's constant for ammonia in the condenser is given in Eq(19).

$$H' = 137.84 * 10^{(0.009622 * T')} \quad (19)$$

where, H' = Henry's constant in condenser.
 P' = partial pressure of ammonia in condenser in mm Hg.
 T' = temperature at condenser, oF.

The concentration of total ammonia and ammonium ion in the condensate C_2 may be obtained analytically from Eq(17) and Eq(18) and it is given in Eq(20).

$$C_2 = K_G * A * (P/P_t) / (E + F_A * 18/62.4 * H'/P_t) \quad (20)$$

During refluxing or boil down Eq(20) is used with Eq(14), Eq(15) and Eq(16) for ammonia volatility calculation.

APPENDIX II: BASIC PROGRAM FOR SRAT NH₃ VOLATILITY

```

10 'THIS PROGRAM CALCULATE AMMONIA VOLATILITY RATE
20 'ALL UNITS ARE BRITISH UNITS EXCEPT PRESSURE IN mmHg
30 A$=" #####^"
40 DEFINT I-P
50 N=3 'TOTAL NUMBER OF EQUATION
60 'DEFINT I-P : DEFDBL A-H,Q-Z
70 DIM
A(N,N),B(N),C(N),D(N,N),C0(N),P(N),X(N),XP(N),AK1(N),AK2(N),AK3(N),F
(N,2)
71 OPEN "O",#1,"SRATDATA"
80 'READ IN THE PROCESS VARIABLES
90 'PH; TOTAL AMMONIA,PPM; SOLUTION TEMP, °F; TANK
DIAMETER, FT; TOTAL PRESSURE, MMHG; SOLUTION VOLUME, FT^3;
COND. TEMP, °F; AIR PURGE, LB-MOLE/HR; LP
100 READ APH ,APPMT0,TEMP,DIA,APT,V,TEMPP, AIR, P
110 DATA 8,960 ,104,12,745, 240.3,104, 40.43,0
120 E=0 'EVAPORATION RATE FT^3/HR
130 FR=0 'FLOW RATE FT^3/HR
140 CF=0 'CONC OF TOTAL AMMONIUM IN THE FEED LB-MOLE/FT^3
150 'CALCULATE PROCESS PROPERTIES
160 APKB=5.2209-.24448/2.303*LOG(TEMP) ' PKB OF AMMONIA IN
THE SRAT
170 APKBP=5.2209-.24448/2.303*LOG(TEMPP) ' PKB OF AMMONIA
IN THE CONDENSER
180 AH=137.84*10^(.009622*TEMP) 'HENRY'S CONSTANT MMHG IN
THE SRAT
190 AHP=137.84*10^(.009622*TEMPP) 'HENRY'S CONSTANT IN
CONDENSER MMHG
200 G=32.2*3600*3600 'GRAVITATIONAL ACCELERATION CONSTANT
FT/HR/HR
210 BETA = 1/(460+TEMP) 'IDEAL GAS EXPANSION COEFFICIENT
220 TA=65 'AIR TEMPERATURE °F
230 ZOG=29/359*492/(TA+460)*APT/760 'AIR DENSITY LB/FT^3
240 UG=.04356*((TA+460)/(460+100))^.5 'AIR VISCOSITY 0.04356
LB/FT/HR AT 100 °F
250 APR=.69 ' AIR PRANDTL NUMBER
260 SC=.61'SCHMIDT NUMBER FOR AMMONIA IN AIR
270 CP=.24 'SPECIFIC HEAT OF AIR BTU/LB/OF
280 AK=.014*((TA+460)/(460+32))^.5 'AIR THERMOCONDUCTIVITY
BTU/HR/FT/°F
290 AREA=3.14*DIA*DIA/4 ' SOLUTION SURFACE AREA, FT^2

```

```

300 GR=G*BETA*(TEMP-TA)*DIA^3*ZOG^2/UG^2'GRASOF NUMBER
310 HC=AK/DIA*.15*(GR*.69)^(1/3) 'HEAT TRANSFER COEFFICIENT
BTU/FT/HR/oF
320 APS =APKB+APH -14
330 X(1)=APPMT0/1000000!*62.4/18 'lb-mole/ft^3 total ammonium
340 X(3)= 18/62.4 *10^APS /(1+10^APS )*X(1)'MOLE FRACTION OF
FREE AMMONIA
350 X(2)=AH *X(3)'VAPOR PRESSURE OF AMMONIA IN IN SRAT IN
MMHG
360 AKG=.2661*HC'MASS TRANSFER COEFFICIENT LB-MOLE/FT^2/HR
370 PRINT "                LBS AMMONIA    CONDENSATE PH
"

380 PRINT " TIME. HR      PPMT  EVAPORATED VAPOR LINE      "
390 'INPUT INITIAL CONDITIONS, STEP SIZE AND TIME LIMIT
400 T=0 : H = .5: RT= 92
410 'INPUT BASIC CONSTANTS FOR GSIRK
420 A1=.435867 :B2=.75 :B31=-.630172 :B32=-.24235:
R1=1.03758:R2=.83494
430 'INPUT D MATRIX
440 D(1,1)=1
450 '
460 '
470 '
480 GOTO 940 'PRINT OUT INITIAL CONDITIONS
490 'CALCULATE FIRST B MATRIX AND JACOBIAN
500 J=1
510 GOSUB 1410 'EQUATIONS TO BE SOLVED IN F(I,J)=F(X,T)
520 J=2
530 FOR I = 1 TO N
540 B(I)=F(I,1)*H 'THE FIRST B MATRIX
550 DXJ=X(I)*.0001 'X(I) INCREMENT
560 IF DXJ=0 THEN DXJ = .00001 'ALTERNATE X(I) INCREMENT
570 X(I)=X(I)+DXJ
580 GOSUB 1410 'EQUATIONS TO BE SOLVED IN F(I,J)=F(X,T)
590 FOR L = 1 TO N
600 A(L,I)=(F(L,2)-F(L,1))/DXJ*(-H*A1) 'JACOBIAN *(-H*A)
610 A(L,I)=D(L,I)+A(L,I) 'FINAL COEFFICIENT MATRIX
620 NEXT L
630 X(I)=X(I)-DXJ 'RESTORE TO ITS ORIGINAL VALUE
640 NEXT I
650 'CALCULATE AK1(I) AND NEW X(I) FOR THE SECOND MATRIX
660 GOSUB 1460 'LU DECOMPOSITION SUBROUTINE
670 FOR I = 1 TO N

```

```

680 AK1(I)=C(I) ' SOLUTIONS FOR AK1(I)
690 XP(I)=X(I) 'STORE THE ORIGINAL X(I) IN XP(I)
700 X(I)=XP(I)+B2*AK1(I) 'FOR SECOND B MATRIX CALCULATION
710 NEXT I
720 'CALCULATE THE SECOND B MATRIX
730 J=1
740 GOSUB 1410 'EQUATION SUBROUTINE, F(I,J)=F(X,T)
750 FOR I = 1 TO N
760 B(I)=F(I,1)*H 'SECOND B MATRIX
770 NEXT I
780 'CALCULATE AK2(I) AND THE THIRD B MATRIX
790 GOSUB 2080 'LATER PART OF LU DECOMPOSITION SUBROUTINE
800 FOR I = 1 TO N
810 B(I) =0 'INITIALIZE FOR THE THIRD B MATRIX
820 AK2(I)=C(I) 'SOLUTION FOR AK2(I)
830 FOR K=1 TO N
840 B(I)=B(I)+D(I,K)*(B31*AK1(K)+B32*AK2(K)) 'ALPHA MATRIX IN
THE TEXT
850 NEXT K
860 NEXT I
870 'CALCULATE AK3(I) AND NEW X(I)
880 GOSUB 2080 'LATER PART OF LU DECOMPOSITION SUBROUTINE
890 FOR I = 1 TO N
900 AK3(I)=C(I) 'SOLUTION FOR AK3(I)
910 X(I)=XP(I)+R1*AK1(I)+R2*AK2(I)+AK3(I)
920 NEXT I
930 T=T+H 'NEW TIME
940 IF T<=0 THEN TE=0 ELSE TE=TE+AKG*AREA*X(2)/APT*17*H-
E*C2*17*H 'TOTAL AMMONIA EVAPORATED INTO VAPOR LINE IN
LBS
950 APPMT=X(1)*18/62.4*1000000! 'TOTAL AMMONIUM ION IN
PPM
960 APPMF=62.4/18*X(3)*17/62.4*1000000! 'PPM OF FREE
AMMONIA
970 APHC=0 'NULL PH WHEN THERE IS NO CONDENSATE
980 IF (T>=30) AND (T<= 42) THEN E=60 : TEMP=212
990 IF (T>42) AND (T<=58) THEN E=66.75 : TEMP=212
1000 'IF (T<30) AND (T>53) THEN E=0
1010 IF T>=74 THEN V=240.3 : TEMP=104
1020 IF (T>=15) AND (T<=17) THEN V=240.3+(1041.3-240.3)/2*(T-
15) : CF=.00104
1030 IF (T>42) AND (T <58) THEN DV=-E*H ELSE DV=0
1040 IF (T>42) AND (T<58) THEN FR=66.75 :CF=.0052

```



```

1050 IF (T>=30) AND (T<=42) THEN IR=1 ELSE IR=0'IR=1 WHEN
REFLUXING
1060 IF (T>=17) AND (T<=30) THEN TEMP=203
1070 IF (T>=58) AND (T<=62) THEN TEMP=212-(212-104)/4 *(T-58)
1080 IF (T>=15) AND (T<=17) THEN APH=12 : FR=400.5
1090 IF (T>=17) AND (T<=21) THEN V=1041.3+(1068-1041.3)/4*(T-
15) : APH=12-(12-5)/4*(T-17)
1100 IF (T>=21) AND (T<=74) THEN V=1068
1110 IF (T>=21) AND (T<=30) THEN APH=5
1120 IF (T>=30) AND (T<=36) THEN APH=5+(7-5)/6 *(T-30)
1130 IF (T>=42) AND (T<=74) THEN APH=8
1140 IF T>74 THEN APH=8
1150 IF (T>17) AND (T<=42) THEN CF=0
1160 IF T>58 THEN CF=0
1170 IF (T>=17) AND (T<=42) THEN FR=0
1180 IF T>=58 THEN FR=0 :CF=0 : E=0
1190 IF (T>=36) AND (T<=42) THEN APH=7
1200 IF (T>=62) AND (T<=74) THEN TEMP= 104
1210 'IF T<=5 THEN APH=12
1220 'IF T>=5 THEN APH=APH+(5-12)/5*H
1230 'IF APH<5 THEN APH=5
1240 APKB=5.2209-.24448/2.303*LOG(TEMP) ' PKB OF AMMONIA AS
A FUNCTION OF TEMP
1250 APS =APKB+APH -14
1260 IF IR=0 AND T<=0 THEN V=V ELSE V=V+DV'VOLUME OF SRAT
AT ANY INSTANT IN FT^3
1261 APKB=5.2209-.24448/2.303*LOG(TEMP) ' PKB OF AMMONIA IN
THE SRAT
1262 AH=137.84*10^(.009622*TEMP) 'HENRY'S CONSTANT MMHG IN
THE SRAT
1263 BETA = 1/(460+TEMP) 'IDEAL GAS EXPANSION COEFFICIENT
1264 GR=G*BETA*(TEMP-TA)*DIA^3*ZOG^2/UG^2'GRASOF NUMBER
1265 HC=AK/DIA*.15*(GR*.69)^(1/3) 'HEAT TRANSFER COEFFICIENT
BTU/FT/HR/oF
1266 APS =APKB+APH -14
1267 AKG=.2661*HC'MASS TRANSFER COEFFICIENT LB-
MOLE/FT^2/HR
1270 IF ABS(212-TEMP)<1 THEN GOSUB 2370
1280 PRINT USING A$;T,APPMT,TE,APH ,V,TEMP,APHC
1281 PRINT #1,T,APPMT,TE,APH,V,TEMP,APHC
1290 'PRINT " T =";T,
1300 'FOR I = 1 TO N
1310 'PRINT "X(";I;")=";X(I),

```

```

1320 'NEXT I
1330 'PRINT OUT RESULTS
1340 'PRINT " T =";T,
1350 'FOR I = 1 TO N
1360 'PRINT "X(";I;")=";X(I),
1370 'NEXT I
1380 'PRINT
1390 IF T< RT THEN GOTO 490 'START CALCULATION FOR NEW TIME
STEP
1391 CLOSE #1
1400 END
1410 'EQUATION SUBROUTINE
1420 F(1,J)=-AKG*AREA/V*X(2)/APT+FR/ V*(CF-
X(1))+IR*E/V*C2'DIFFERENTIAL EQUATION
1430 F(2,J)=AH *X(3)-X(2)
1440 F(3,J)=18/62.4*10^APS /(1+10^APS )*X(1)-X(3)
1450 RETURN
1460 'LU-MATRICES ARE STORED AS MATRIX A
1470 P(1) = 1
1480 C0(1) = A(1,1)
1490 FOR J = 2 TO N
1500 P(J) = 0
1510 C0(J) = A(J,1)
1520 AH=137.84*10^(.009622*TEMP)      'HENRY'S CONSTANT FOR
SRAT
1530 NEXT J
1540 I = 1
1550 GOSUB 1900
1560 'COMPUTATION OF L(I,1), I = 2 TO N
1570 FOR J = 2 TO N
1580 A(J,1) = A(J,1)/A(1,1)
1590 NEXT J
1600 I = I + 1
1610 IF I = N THEN GOTO 1710
1620 'PREPARATION FOR PIVOTING
1630 FOR J = I TO N
1640 C0(J) = A(J,I)
1650 FOR L =1 TO I-1
1660 C0(J) = C0(J) - A(J,L)* A(L,I)
1670 NEXT L
1680 NEXT J
1690 GOSUB 1900
1700 'COMPUTATION OF U(I,J), J=1 TO N

```

```

1710 K=I-1
1720 FOR J=1 TO N
1730 FOR L=1 TO K
1740 A(I,J) = A(I,J) - A(I,L) *A(L,J)
1750 NEXT L
1760 IF A(I,I) <> 0 THEN GOTO 1790
1770 PRINT "SINGULAR MATRIX I =";I
1780 STOP
1790 NEXT J
1800 IF I = N THEN GOTO 2080
1810 'COMPUTATION OF L(J,I), J = i + 1 TO N
1820 FOR J = I+1 TO N
1830 FOR L = 1 TO K
1840 A(J,I) = A(J,I) - A(J,L) * A(L,I)
1850 NEXT L
1860 A(J,I) = A(J,I)/A(I,I)
1870 NEXT J
1880 GOTO 1600
1890 'SUBROUTINE FOR PARTIAL PIVOTING
1900 K = I + 1
1910 M = 0
1920 C = ABS(C0(I))
1930 FOR L = K TO N
1940 IF ABS(C0(L)) <= C THEN GOTO 1990
1950 C = ABS(C0(L))
1960 P(1) = -P(1)
1970 P(K) = L
1980 M = 1
1990 NEXT L
2000 IF M = 0 THEN RETURN
2010 L = P(K)
2020 FOR J = 1 TO N
2030 C = A(I,J)
2040 A(I,J) = A(L,J)
2050 A(L,J) = C
2060 NEXT J
2070 RETURN
2080 'ADJUSTMENT OF B(I) TO PIVOTING
2090 FOR I = 2 TO N
2100 IF P(I) = 0 THEN GOTO 2160
2110 J = P(I)
2120 K = I -1
2130 C = B(K)

```

```

2140 B(K) = B(J)
2150 B(J) = C
2160 NEXT I
2170 'SOLUTION OF THE FIRST TRIANGULAR SYSTEM
2180 'VECTOR Y IS STORED AS VECTOR B
2190 FOR I = 2 TO N
2200 K = I - 1
2210 FOR J = 1 TO K
2220 B(I) = B(I) - A(I,J) * B(J)
2230 NEXT J
2240 NEXT I
2250 'SOLUTION OF THE SECOND TRIANGULAR SYSTEM
2260 C(N) = B(N)/A(N,N)
2270 M = N - 1
2280 FOR I = M TO 1 STEP -1
2290 K = I + 1
2300 C(I) = B(I)
2310 FOR J = K TO N
2320 C(I) = C(I) - A(I,J) * C(J)
2330 NEXT J
2340 C(I) = C(I)/A(I,I)
2350 NEXT I
2360 RETURN
2370 'CALCULATE CONDENSATE WHEN THE SRAT IS BOILING
2380 C2=AKG*AREA*X(2)/APT/(E+AIR*18/62.4*AHP/APT)'TOTAL
AMMONIUM ION CONC. IN THE CONDENSATE, LB-MOLE/ft^3
2390 Y=(-10^(-APKBP)+SQR ((10^(-2*APKBP) +4*10^(-APKBP)*C2)))/2
'FREE [OH] IN LB-MOLE/FT^3
2400 YM=Y*453.6/(3.048^3) '[OH] IN MOLAR
2410 APHC=14+1/2.303*LOG(YM) 'PH OF CONDENSATE
2420 RETURN

```

APPENDIX III: BASIC PROGRAM FOR NH₃ VOLATILITY IN SME

```
10 'THIS PROGRAM CALCULATE AMMONIA VOLATILITY RATE
20 'ALL UNITS ARE BRITISH UNITS EXCEPT PRESSURE IN mmHg
30 A$="#####^"
40 DEFINT I-P
50 N=3 'TOTAL NUMBER OF EQUATION
60 'DEFINT I-P : DEFDBL A-H,Q-Z
70 DIM
A(N,N),B(N),C(N),D(N,N),C0(N),P(N),X(N),XP(N),AK1(N),AK2(N),AK3(N),F
(N,2)
71 OPEN "O", #1, "SMEDATA"
80 'READ IN THE PROCESS VARIABLES
90 'PH; TOTAL AMMONIA,PPM; SOLUTION TEMP, oF; TANK
DIAMETER, FT; TOTAL PRESSURE, MMHG; SOLUTION VOLUME, FT^3;
COND. TEMP, oF; AIR PURGE, LB-MOLE/HR; LP
100 READ APH ,APPMT0,TEMP,DIA,APT,V,TEMPP, AIR,LP
110 DATA 9, 6 ,104,12,745,1041.3,104, 10.1 ,0
120 E= 0 'EVAPORATION RATE FT^3/HR
130 FR=0 'FLOW RATE FT^3/HR
140 CF =0 'CONC OF TOTAL AMMONIUM IN THE FEED LB-MOLE/FT^3
150 'CALCULATE PROCESS PROPERTIES
160 APKB=5.2209-.24448/2.303*LOG(TEMP) ' PKB OF AMMONIA IN
THE SRAT
170 APKBP=5.2209-.24448/2.303*LOG(TEMPP) ' PKB OF AMMONIA
IN THE CONDENSER
180 AH=137.84*10^(.009622*TEMP) 'HENRY'S CONSTANT MMHG IN
THE SRAT
190 AHP=137.84*10^(.009622*TEMPP) 'HENRY'S CONSTANT IN
CONDENSER MMHG
200 G=32.2*3600*3600 'GRAVITATIONAL ACCELERATION CONSTANT
FT/HR/HR
210 BETA = 1/(460+TEMP) 'IDEAL GAS EXPANSION COEFFICIENT
220 TA=65 'AIR TEMPERATURE oF
230 ZOG=29/359*492/(TA+460)*APT/760 'AIR DENSITY LB/FT^3
240 UG=.04356*((TA+460)/(460+100))^.5 'AIR VISCOSITY 0.04356
LB/FT/HR AT 100 oF
250 APR=.69 ' AIR PRANDTL NUMBER
260 SC=.61'SCHMIDT NUMBER FOR AMMONIA IN AIR
270 CP=.24 'SPECIFIC HEAT OF AIR BTU/LB/OF
280 AK=.014*((TA+460)/(460+32))^.5 'AIR THERMOCONDUCTIVITY
BTU/HR/FT/oF
```

```

290 AREA=3.14*DIA*DIA/4 ' SOLUTION SURFACE AREA, FT^2
300 GR=G*BETA*(TEMP-TA)*DIA^3*ZOG^2/UG^2'GRASOF NUMBER
310 HC=AK/DIA*.15*(GR*.69)^(1/3) 'HEAT TRANSFER COEFFICIENT
BTU/FT/HR/oF
320 APS =APKB+APH -14
330 X(1)=APPMT0/1000000!*62.4/18 'lb-mole/ft^3 total ammonium
340 X(3)= 18/62.4 *10^APS /(1+10^APS )*X(1)'MOLE FRACTION OF
FREE AMMONIA
350 X(2)=AH *X(3)'VAPOR PRESSURE OF AMMONIA IN IN SRAT IN
MMHG
360 AKG=.2661*HC'MASS TRANSFER COEFFICIENT LB-MOLE/FT^2/HR
370 PRINT "                                LBS AMMONIA    CONDENSATE PH
"

380 PRINT " TIME. HR      PPMT  EVAPORATED VAPOR LINE      "
390 'INPUT INITIAL CONDITIONS, STEP SIZE AND TIME LIMIT
400 T=0 : H = .5: RT= 92
410 'INPUT BASIC CONSTANTS FOR GSIRK
420 A1=.435867 :B2=.75 :B31=-.630172 :B32=-.24235:
R1=1.03758:R2=.83494
430 'INPUT D MATRIX
440 D(1,1)=1
450 '
460 '
470 '
480 GOTO 940 'PRINT OUT INITIAL CONDITIONS
490 'CALCULATE FIRST B MATRIX AND JACOBIAN
500 J=1
510 GOSUB 1410 'EQUATIONS TO BE SOLVED IN F(I,J)=F(X,T)
520 J=2
530 FOR I = 1 TO N
540 B(I)=F(I,1)*H 'THE FIRST B MATRIX
550 DXJ=X(I)*.0001 'X(I) INCREMENT
560 IF DXJ=0 THEN DXJ = .00001 'ALTERNATE X(I) INCREMENT
570 X(I)=X(I)+DXJ
580 GOSUB 1410 'EQUATIONS TO BE SOLVED IN F(I,J)=F(X,T)
590 FOR L = 1 TO N
600 A(L,I)=(F(L,2)-F(L,1))/DXJ*(-H*A1) 'JACOBIAN *(-H*A)
610 A(L,I)=D(L,I)+A(L,I) 'FINAL COEFFICIENT MATRIX
620 NEXT L
630 X(I)=X(I)-DXJ 'RESTORE TO ITS ORIGINAL VALUE
640 NEXT I
650 'CALCULATE AK1(I) AND NEW X(I) FOR THE SECOND MATRIX
660 GOSUB 1460 'LU DECOMPOSITION SUBROUTINE

```

```

670 FOR I = 1 TO N
680 AK1(I)=C(I) ' SOLUTIONS FOR AK1(I)
690 XP(I)=X(I) 'STORE THE ORIGINAL X(I) IN XP(I)
700 X(I)=XP(I)+B2*AK1(I) 'FOR SECOND B MATRIX CALCULATION
710 NEXT I
720 'CALCULATE THE SECOND B MATRIX
730 J=1
740 GOSUB 1410 'EQUATION SUBROUTINE, F(I,J)=F(X,T)
750 FOR I = 1 TO N
760 B(I)=F(I,1)*H 'SECOND B MATRIX
770 NEXT I
780 'CALCULATE AK2(I) AND THE THIRD B MATRIX
790 GOSUB 2080 'LATER PART OF LU DECOMPOSITION SUBROUTINE
800 FOR I = 1 TO N
810 B(I) =0 'INITIALIZE FOR THE THIRD B MATRIX
820 AK2(I)=C(I) 'SOLUTION FOR AK2(I)
830 FOR K=1 TO N
840 B(I)=B(I)+D(I,K)*(B31*AK1(K)+B32*AK2(K)) 'ALPHA MATRIX IN
THE TEXT
850 NEXT K
860 NEXT I
870 'CALCULATE AK3(I) AND NEW X(I)
880 GOSUB 2080 'LATER PART OF LU DECOMPOSITION SUBROUTINE
890 FOR I = 1 TO N
900 AK3(I)=C(I) 'SOLUTION FOR AK3(I)
910 X(I)=XP(I)+R1*AK1(I)+R2*AK2(I)+AK3(I)
920 NEXT I
930 T=T+H 'NEW TIME
940 IF T<=0 THEN TE=0 ELSE TE=TE+AKG*AREA*X(2)/APT*17*H-
E*C2*17*H 'TOTAL AMMONIA EVAPORATED INTO VAPOR LINE IN
LBS
950 APPMT=X(1)*18/62.4*1000000! 'TOTAL AMMONIUM ION IN
PPM
960 APPMF=62.4/18*X(3)*17/62.4*1000000! 'PPM OF FREE
AMMONIA
970 APHC=0 'NULL PH WHEN THERE IS NO CONDENSATE
971 IF T=7 THEN
X(1)=(X(1)*240.3+(960/1000000!*62.4/18)*(1041.3-240.3))/1041.3
980 IF (T>=7) AND (T<= 52) THEN E=10.853 : TEMP=212
990 IF (T>7) AND (T<=52) THEN V=1041.3-(1041.3-552.93)/45*(T-7)
:IR=0
1000 IF (T>=52) THEN V=240.3 : TEMP=104 :E=0:IR=0

```

```

1240 APKB=5.2209-.24448/2.303*LOG(TEMP) ' PKB OF AMMONIA AS
A FUNCTION OF TEMP
1250 APS =APKB+APH -14
1260 IF IR=0 AND T<=0 THEN V=V ELSE V=V+DV'VOLUME OF SRAT
AT ANY INSTANT IN FT^3
1261 APKB=5.2209-.24448/2.303*LOG(TEMP) ' PKB OF AMMONIA IN
THE SRAT
1262 AH=137.84*10^(.009622*TEMP) 'HENRY'S CONSTANT MMHG IN
THE SRAT
1263 BETA = 1/(460+TEMP) 'IDEAL GAS EXPANSION COEFFICIENT
1264 GR=G*BETA*(TEMP-TA)*DIA^3*ZOG^2/UG^2'GRASOF NUMBER
1265 HC=AK/DIA*.15*(GR*.69)^(1/3) 'HEAT TRANSFER COEFFICIENT
BTU/FT/HR/oF
1266 APS =APKB+APH -14
1267 AKG=.2661*HC'MASS TRANSFER COEFFICIENT LB-
MOLE/FT^2/HR
1270 IF ABS(212-TEMP)<1 THEN GOSUB 2370
1280 PRINT USING A$;T,APPMT,TE,APH ,V,TEMP,APHC
1281 PRINT #1, T,APPMT,TE,APH,V,TEMP,APHC
1290 'PRINT " T =";T,
1300 'FOR I = 1 TO N
1310 'PRINT "X(";I;")=";X(I),
1320 'NEXT I
1330 'PRINT OUT RESULTS
1340 'PRINT " T =";T,
1350 'FOR I = 1 TO N
1360 'PRINT "X(";I;")=";X(I),
1370 'NEXT I
1380 'PRINT
1390 IF T< RT THEN GOTO 490 'START CALCULATION FOR NEW TIME
STEP
1391 CLOSE #1
1400 END
1410 'EQUATION SUBROUTINE
1420 F(1,J)=-AKG*AREA/V*X(2)/APT+FR/ V*(CF-
X(1))+IR*E/V*C2'DIFFERENTIAL EQUATION
1430 F(2,J)=AH *X(3)-X(2)
1440 F(3,J)=18/62.4*10^APS /(1+10^APS )*X(1)-X(3)
1450 RETURN
1460 'LU-MATRICES ARE STORED AS MATRIX A
1470 P(1) = 1
1480 C0(1) = A(1,1)
1490 FOR J = 2 TO N

```



```

1500 P(J) = 0
1510 C0(J) = A(J,1)
1520 AH=137.84*10^(.009622*TEMP)      'HENRY'S CONSTANT FOR
SRAT
1530 NEXT J
1540 I = 1
1550 GOSUB 1900
1560 'COMPUTATION OF L(I,1), I = 2 TO N
1570 FOR J = 2 TO N
1580 A(J,1) = A(J,1)/A(1,1)
1590 NEXT J
1600 I = I + 1
1610 IF I = N THEN GOTO 1710
1620 'PREPARATION FOR PIVOTING
1630 FOR J = I TO N
1640 C0(J) = A(J,I)
1650 FOR L = 1 TO I-1
1660 C0(J) = C0(J) - A(J,L)* A(L,I)
1670 NEXT L
1680 NEXT J
1690 GOSUB 1900
1700 'COMPUTATION OF U(I,J), J=1 TO N
1710 K=I-1
1720 FOR J=1 TO N
1730 FOR L=1 TO K
1740 A(I,J) = A(I,J) - A(I,L) *A(L,J)
1750 NEXT L
1760 IF A(I,I) <> 0 THEN GOTO 1790
1770 PRINT "SINGULAR MATRIX I =";I
1780 STOP
1790 NEXT J
1800 IF I = N THEN GOTO 2080
1810 'COMPUTATION OF L(J,I), J = i + 1 TO N
1820 FOR J = I+1 TO N
1830 FOR L = 1 TO K
1840 A(J,I) = A(J,I) - A(J,L) * A(L,I)
1850 NEXT L
1860 A(J,I) = A(J,I)/A(I,I)
1870 NEXT J
1880 GOTO 1600
1890 'SUBROUTINE FOR PARTIAL PIVOTING
1900 K = I + 1
1910 M = 0

```

```
2350 NEXT I
2360 RETURN
2370 'CALCULATE CONDENSATE WHEN THE SRAT IS BOILING
2380 C2=AKG*AREA*X(2)/APT/(E+AIR*18/62.4*AHP/APT)'TOTAL
AMMONIUM ION CONC. IN THE CONDENSATE, LB-MOLE/ft^3
2390 Y=(-10^(-APKBP)+SQR ((10^(-2*APKBP) +4*10^(-APKBP)*C2)))/2
'FREE [OH] IN LB-MOLE/FT^3
2400 YM=Y*453.6/(3.048^3) '[OH] IN MOLAR
2410 APHC=14+1/2.303*LOG(YM) 'PH OF CONDENSATE
2420 RETURN
```

```

1920 C = ABS(C0(I))
1930 FOR L = K TO N
1940 IF ABS(C0(L)) <= C THEN GOTO 1990
1950 C = ABS(C0(L))
1960 P(1) = -P(1)
1970 P(K) = L
1980 M = 1
1990 NEXT L
2000 IF M = 0 THEN RETURN
2010 L = P(K)
2020 FOR J = 1 TO N
2030 C = A(I,J)
2040 A(I,J) = A(L,J)
2050 A(L,J) = C
2060 NEXT J
2070 RETURN
2080 'ADJUSTMENT OF B(I) TO PIVOTING
2090 FOR I = 2 TO N
2100 IF P(I) = 0 THEN GOTO 2160
2110 J = P(I)
2120 K = I - 1
2130 C = B(K)
2140 B(K) = B(J)
2150 B(J) = C
2160 NEXT I
2170 'SOLUTION OF THE FIRST TRIANGULAR SYSTEM
2180 'VECTOR Y IS STORED AS VECTOR B
2190 FOR I = 2 TO N
2200 K = I - 1
2210 FOR J = 1 TO K
2220 B(I) = B(I) - A(I,J) * B(J)
2230 NEXT J
2240 NEXT I
2250 'SOLUTION OF THE SECOND TRIANGULAR SYSTEM
2260 C(N) = B(N)/A(N,N)
2270 M = N - 1
2280 FOR I = M TO 1 STEP -1
2290 K = I + 1
2300 C(I) = B(I)
2310 FOR J = K TO N
2320 C(I) = C(I) - A(I,J) * C(J)
2330 NEXT J
2340 C(I) = C(I)/A(I,I)

```

END

**DATE
FILMED**

3 / 25 / 93