DOE/MC/23174--3138

DE93 000222

**Characterization and Control of Exhaust Gas
From Diesel Engine Firing Coal-Water Mixture**

Topical Report

**Eric A. Samuel
Eli Gal
Mike Mengel
Mike Arnold**

Work Performed Under Contract No.: DE-AC21-88MC23174

**For
U.S. Department of Energy
Office of Fossil Energy
Morgantown Energy Technology Center
P.O. Box 880
Morgantown, West Virginia 26507-0880**

**By
General Electric Company
200 North Seventh Street
Lebanon, Pennsylvania 17042**

March 1990

ABSTRACT

Exhaust from the GE-TS single cylinder diesel engine, fitted with hardened metal, and diamond-tipped metal fuel injection nozzles, and firing coal-water mixture (CWM) has been characterized with respect to gas composition, particulate size distribution, and particulate filtration characteristics. The measured flue gas compositions are roughly in keeping with results from combustion calculations. The time variations of the hydrocarbon, CO, and NO_x concentrations are also understood in terms of known reaction mechanisms.

Oil fired diesel exhaust causes near-blinding of the absolute filter as shown by the rapid rise of filter pressure drop. The rate of increase of pressure drop, with CWM fuel and hardened metal fuel injection nozzles, is approximately 0.5 in. water/min, and nearly independent of filtration velocity in the range of 3 to 7 ft/min. This independence appears due to fall out from the upper part of the horizontally mounted filter. Thicker dust deposition in the bottom part of the filter and increasing fluctuation in the filter pressure drop with increasing filter cake thickness also support this self-cleaning concept. The filtration characteristics of the particulate produced in the diesel engine fitted with diamond-tipped fuel injection nozzles are quite different. Velocity effects are evident in filtration characteristics. Better combustion and higher gas temperature in the latter case produces higher NO_x and hydrocarbon concentrations, and lower CO concentration.

The particulate concentration in the CWM-exhaust is in the range of 0.25 to 0.35 gr/scf. The CWM-particulate size distribution are bi-modal comprised of an ash-like component of fixed mean size and standard deviation, and a variable incompletely burned particle component. Both components conform to the log-normal size distribution. In the case of the hardened metal nozzles, the exhaust particle size distributions show evidence of nozzle degradation with increasing engine run-time. No such degradation of the diamond-tipped nozzles has been observed after about 30 hours of engine run-time.

A 2-in. prototype cyclone showed a mass collection efficiency of about 75% at low gas flow rates, but its performance deteriorated with increasing gas flow rate. This anomalous behavior is thought to be due to small-scale fabrication effects. There is a tendency for blinding when the exhaust particulate are directly filtered through absolute filters. Precoating of metal filter elements have been shown to promote the pulse-jet cleanability of these elements. Particulate collection in granular beds are limited by the accumulation of particulate within the bed, requiring an upstream collector, such as a cyclone, to reduce the inlet loading to the granular bed.

Lime blended into the CWM fuel resulted in only about 25% SO_2 removal, and is accompanied by undesirable calcium solids buildup on the diesel engine valves. Dry injection of lime at 750F exhaust gas produced about a 40% SO_2 removal efficiency. Lime spray injection, also at the 750F gas temperature, increased the SO_2 removal to nearly 50% at the same Ca/S mole ratio of 2. None of the above methods showed any NO_x removal. A granular bed of CuO-impregnated showed better than 90% SO_2 removal at gas temperatures around 800 F. The mass transfer kinetics of SO_2 removal in the granular bed was shown to be temperature and gas velocity dependent. Also, the CuO-granular bed holds the potential for NO_x removal in the presence of NH_3 injection.

CONTENTS

	<u>PAGE NO.</u>
Abstract	iii
Figures	vii
Tables	xiv
Introduction	xvi
1.0 Emission Control Characteristics with Conventional Diesel Flue Gas.....	1
1.1 Introduction.....	1
1.2 Apparatus.....	1
1.3 Results.....	1
Pressure Transducer Calibration.....	1
Pressure Drop.....	5
2.0 Characterization of Emissions from the GE-TS CWM-Fired Single Cylinder Diesel Engine.....	18
2.1 Introduction.....	18
2.2 Apparatus.....	18
2.3 Tests with Hardened Metal Fuel Injection Nozzles...	21
2.4 Results with Hardened Metal Fuel Injection Nozzles.	21
Exhaust Gas Analyzer Calibrations.....	21
Exhaust Gas Composition.....	22
Pressure Transducer Calibrations.....	27
Sampling Apparatus Gas Temperatures.....	27
CWM Exhaust Particulae Size Distributions.....	40
Fuel Burnout.....	43

	<u>PAGE NO.</u>
2.5 Tests with Diamond-Tipped Metal Fuel Injection Nozzles.....	46
2.6 Results with Diamond-Tipped Metal Fuel Injection Nozzles.....	47
Alternate Gas Sampling Locations.....	55
Summary.....	57
3.0 Characterization of Emission Control Prototypes.....	59
3.1 Introduction.....	59
3.2 Results.....	59
SO ₂ , NO _x , HC and CO Control.....	59
Particulate Removal.....	82
Summary.....	107
4.0 Recommendations (Series 2 Test Plan).....	110
4.1 Series 3 Action Plan.....	111
Objective.....	111
Cyclone.....	112
Granular Bed.....	112
Envelope Filter.....	112
Appendix A - CWM Diesel Locomotive Conceptual Particulate Collector Costs.....	A-1
Appendix B - Analyses of Engine Deposits following Tests with Lime containing CWM.....	B-1
Appendix C - Malvern Particle Size Analyzer (Mach 2 Aerosizer).	C-1
Appendix D - Charts of Diesel Exhaust Gas Time Variations.....	D-1
Appendix E - Diesel Exhaust Particulate Size Distribution.....	E-1
Appendix F - Thimble Delta P Time Variations.....	F-1

FIGURES

<u>FIGURE</u>	<u>PAGE NO.</u>
1 Bench scale apparatus to characterize emission control prototypes using flue gas from conventional diesel engine.....	2
2 Size distribution of limestone precoat material.....	3
3 Prototype granular bed.....	3
4(a) Pressure transducer calibration for tests with filtration fabrics.....	4
4(b) Pressure transducer calibration for tests with granular bed.....	4
5 Time variation of the pressure drop across the FD2004 medium with limestone precoat for diesel exhaust flow..	7
6 Time variation of the pressure drop across the FD2004 medium without precoat for diesel exhaust flow.....	7
7 Velocity dependence of the pressure drop across the clean FD2004 filter medium for ambient air flow.....	9
8 Precoat effect on the velocity dependence of the rate of increase of filter pressure drop (DP/Dt).....	9
9(a) Dependence of the rate of increase of the filter pressure drop at 5.22 ft/min on cycle no.....	11
9(b) Dependence of the rate of increase of the filter pressure drop at 10.45 ft/min on cycle no.....	11
9(c) Dependence of the rate of increase of the filter pressure drop at 5.22 and 10.45 ft/min on cycle no.....	13
10(a) Interpretation of the granular bed DP vs. v data for ambient air in terms of Equation (3).....	13
11 Time variation of the pressure drop across the granular bed at filtration velocities of 148, 101 and 52 ft/min with diesel exhaust flow.....	14
12(a) Time variation of the pressure drop across the granular bed at the 148 ft/min filtration velocity with diesel exhaust flow, interpreted in terms of initial and steady-state rates of DP/Dt.....	14

<u>FIGURE</u>	<u>PAGE NO.</u>
12(b) Time variation of the pressure drop across the granular bed at the 101 ft/min filtration velocity with diesel exhaust flow, interpreted in terms of initial and steady-state rates of DP/Dt.....	15
12(c) Time variation of the pressure drop across the granular bed at the 52 ft/min filtration velocity with diesel exhaust flow, interpreted in terms of initial and steady-state rates of DP/Dt.....	15
13 Velocity dependence of the initial and steady-state DP/Dt values for granular bed filtration of diesel exhaust.....	16
14 Series 1 sampling probe.....	19
15 Data acquisition system used for emission control investigations at GE-TS engine laboratory.....	20
16 Time variation of Test 3 exhaust gas compositions: (a) CO and HC, (b) SO ₂ and NO _x , and (c) CO ₂ and O ₂	23
17 Time variation of Test 4 exhaust gas compositions: (a) CO and HC, (b) SO ₂ and NO _x , and (c) CO ₂ and O ₂	24
18 Time variation of Test 5 exhaust gas compositions: (a) CO and HC, (b) SO ₂ and NO _x , and (c) CO ₂ and O ₂	25
19 Calibration line for absolute pressure transmitter measuring the sampling system inlet absolute pressure..	29
20 Calibration line for absolute pressure transmitter measuring the absolute pressure at the orifice inlet...	29
21 Calibration line for differential pressure transmitter measuring the pressure drop across the thimble.....	30
22 Calibration line for differential pressure transmitter measuring the pressure drop across the orifice.....	31
23 Temperature variation in the sampling system during: (a) Test 3, (b) Test 4, and (c) Test 5.....	32
24 Test 3 observations: (a) pressure drop across thimble, and (b) thimble A/C.....	34
25 Test 4 observations: (a) pressure drop across thimble, and (b) thimble A/C.....	35

<u>FIGURE</u>	<u>PAGE NO.</u>
26 Test 5 observations: (a) pressure drop across thimble, and (b) thimble A/C.....	36
27 Time dependence of the thimble pressure drop fluctuations ($D[DP]/Dt$) during Test 5.....	36
28 Dependence on the thimble A/C of: (a) the rate of change of thimble pressure drop ($D[DP]/Dt$), and (b) the coefficient of specific resistance, K_2	38
29 Bimodal, log-normal fits for the measured fractional size distributions of the exhaust particulate collected during: (a) Test 3, (b) Test 4, and (c) Test 5 from the CWM-fired GE-TS diesel engine fitted with hardened metal fuel injection nozzles.....	39
30 Bimodal, log-normal fits for the measured fractional size distributions of the exhaust particulate collected during: (a) Test 3, (b) Test 4, and (c) Test 5 from the CWM-fired GE-TS diesel engine fitted with hardened metal fuel injection nozzles.....	41
31 Variation of the log-normal mean diameters for the bimodal distributions of Tests 3 to 5 shown in Figures 29 and 30.....	42
32 Variation of the log-normal standard deviations for the bimodal distributions of Test 3 to 5 shown in Figures 29 and 30.....	42
33 Variation of the log-normal relative mass fractions for the bimodal distributions of Tests 3 to 5 shown in Figures 29 and 30.....	42
34 Bimodal, log-normal fits for the measured fractional and cumulative (% less than) inlet size distributions of the exhaust particulate collected during Test 14 from the CWM-fired GE-TS diesel engine fitted with diamond-tipped metal fuel injection nozzles.....	48
35 Bimodal, log-normal fits for the measured fractional and cumulative (% less than) inlet size distributions of the exhaust particulate collected during Test 15 from the CWM-fired GE-TS diesel engine fitted with diamond-tipped metal fuel injection nozzles.....	49
36 Bimodal, log-normal fits for the measured fractional and cumulative (% less than) inlet size distributions of the exhaust particulate collected during Test 16 from the CWM-fired GE-TS diesel engine fitted with diamond-tipped metal fuel injection nozzles.....	50

FIGURE**PAGE NO.**

37	Bimodal, log-normal fits for the measured fractional and cumulative (% less than) inlet size distributions of the exhaust particulate collected during Test 17 from the CWM-fired GE-TS diesel engine fitted with diamond-tipped metal fuel injection nozzles.....	51
38	Bimodal, log-normal fits for the measured fractional and cumulative (% less than) inlet size distributions of the exhaust particulate collected during Test 22 from the CWM-fired GE-TS diesel engine fitted with diamond-tipped metal fuel injection nozzles.....	52
39	Series 2 equipment for evaluating emission control prototypes.....	60
40	Effect of lime-containing CWM on SO ₂ and NO _x emissions from the GE-TS engine equipped with diamond-tipped fuel injection nozzles.....	62
41	Effect of lime-containing CWM on CO emissions from GE-TS engine equipped with diamond-tipped fuel injection nozzles.....	64
42	Effect of lime-containing CWM on HC emissions from GE-TS engine equipped with diamond-tipped fuel injection nozzles.....	64
43	Effect on SO ₂ and NO _x emissions of slaked lime spray into the 550 F exhaust from the GE-TS research engine equipped with diamond-tipped fuel injection nozzles....	66
44	Effect on SO ₂ and NO _x emissions of slaked lime spray into the 750 F exhaust from the GE-TS research engine equipped with diamond-tipped fuel injection nozzles....	67
45	Effect on SO ₂ and Nox emissions of slaked lime spray into the 950 F exhaust from the GE-TS research engine equipped with diamond-tipped fuel injection nozzles....	68
46	Effect on CO ₂ and O ₂ emissions of slaked lime spray into the 550 F exhaust from GE-TS engine equipped with diamond-tipped fuel injection nozzles.....	70
47	Effect on HC and CO emissions of slaked lime spray into the 550 F exhaust from GE-TS engine equipped with diamond-tipped fuel injection nozzles.....	70
48	Effect on CO ₂ and O ₂ emissions of slaked lime spray into the 750 F exhaust from GE-TS engine equipped with diamond-tipped fuel injection nozzles.....	71
49	Effect on HC and CO emissions of slaked lime spray into the 750 F exhaust from GE-TS engine equipped with diamond-tipped fuel injection nozzles.....	71

FIGURE**PAGE NO.**

50	Effect on CO ₂ and O ₂ emissions of slaked lime spray into the 950 F exhaust from GE-TS engine equipped with diamond-tipped fuel injection nozzles.....	72
51	Effect on HC and CO emissions of slaked lime spray into the 950 F exhaust from GE-TS engine equipped with diamond-tipped fuel injection nozzles.....	72
52	SO ₂ removal when the exhaust from the CWM-fired GE-TS engine fitted with diamond-tipped fuel nozzles is passed through 2-in. and 6-in. CuO-impregnated granular beds. Figure shows the time variation of the granular bed: (a) outlet SO ₂ concentration, (b) superficial velocity, and (c) the outlet gas temperature.....	74
53	Temperature and velocity and residence time effect of the SO ₂ removal across CuO-impregnated granular beds from the exhaust of the CWM-fired GE-TS research engine fitted with diamond-tipped fuel nozzles.....	75
54	HC removal when the exhaust from the CWM-fired GE-TS engine fitted with diamond-tipped fuel nozzles is passed through 2-in. and 6-in. CuO-impregnated granular beds. Figure shows the time variation of the granular bed outlet HC concentration	76
55	Temperature and velocity and residence time effect of the HC removal across CuO-impregnated granular beds from the exhaust of the CWM-fired GE-TS research engine fitted with diamond-tipped fuel nozzles.....	77
56	CO removal when the exhaust from the CWM-fired GE-TS engine fitted with diamond-tipped fuel nozzles is passed through 2-in. and 6-in. CuO-impregnated granular beds. Figure shows the time variation of the granular bed outlet CO concentration	80
57	Temperature and velocity and residence time effect of the CO removal across CuO-impregnated granular beds from the exhaust of the CWM-fired GE-TS research engine fitted with diamond-tipped fuel nozzles.....	81
58	Cyclone mass efficiency dependence on cyclone inlet gas flow rate (GE-TS research engine with diamond-tipped nozzles).....	83
59	Measured cumulative (% less than) size distributions characteristic of cyclone operation at 2.2 acfm.....	85
60	Measured cumulative (% less than) size distributions characteristic of cyclone operation at 4.8 acfm.....	86
61	Measured cumulative (% less than) size distributions characteristic of cyclone operation at 7.4 acfm.....	87
62	Measured cumulative (% less than) size distributions characteristic of cyclone operation at 9 acfm.....	88

<u>FIGURE</u>		<u>PAGE NO.</u>
63	Cyclone inlet size distributions inferred from the size distributions shown in Figures 59 to 62 (also see Figures 34 to 38).....	89
64	Cyclone fractional (grade) efficiency curves.....	90
65	Cyclone pressure drop dependence on cyclone inlet gas flow rate.....	91
66	Time variation of: (a) the pressure drop, and (b) the A/C during filtration of CWM-derived diesel exhaust through candle filter of stainless steel Fluid Dynamics FD2003 medium without precoat.....	93
67	Time variation of: (a) the pressure drop, and (b) the A/C during filtration of CWM-derived diesel exhaust through candle filter of stainless steel Fluid Dynamics FD2605 medium without precoat.....	94
68	Time variation of: (a) the pressure drop, and (b) the A/C during filtration of CWM-derived diesel exhaust through candle filter of Inconel Bekipore medium with limestone precoat.....	95
69	Comparison of filtration characteristics of stainless steel Fluid Dynamics media without precoat and Inconel Bekipore medium. Figure shows cleaning cycle variation of the rate of change of filter pressure drop ($D[DP]/Dt$).....	96
70	Comparison of filtration characteristics of stainless steel Fluid Dynamics media without precoat and Inconel Bekipore medium. Figure shows cleaning cycle variation of the extrapolated DP(minimum).....	96
71	Time variation of: (a) the pressure drop, and (b) the A/C during filtration of CWM-derived diesel exhaust through candle filter of Inconel Fluid Dynamics medium with lime precoat.....	98
72	Time variation of: (a) the pressure drop, and (b) the A/C during filtration of CWM-derived diesel exhaust through candle filter of Inconel Bekipore medium with lime precoat	99
73	Comparison of filtration characteristics of lime precoated Inconel Fluid Dynamics and Bekipore media. Figure shows cleaning cycle variation of the rate of change of filter pressure drop ($D[DP]/Dt$).....	100
74	Comparison of filtration characteristics of lime precoated Inconel Fluid Dynamics and Bekipore media. Figure shows cleaning cycle variation of the extrapolated DP (minimum)	100

FIGURE**PAGE NO.**

75	Velocity dependence of the rate of pressure drop increase ($D[DP]/Dt$) across the CuO-containing granular bed.....	102
76	Velocity dependence of the rate of pressure drop increase ($D[DP]/Dt$) across the inert and CuO-containing granular bed.....	102
77(a)	Time dependence of the pressure drop across the 2-in. CuO-containing granular bed without upstream cyclone...	103
77(b)	Time dependence of the pressure drop across the 2-in. CuO-containing granular bed with upstream cyclone.....	104
77(c)	Time dependence of the pressure drop across the 6-in. Cu)-containing granular bed with upstream cyclone.....	105

TABLES

<u>TABLE</u>	<u>PAGE NO.</u>
1 Filtration cycles used for determining the pressure drop characteristics of particulate filters operating with diesel exhaust.....	6
2 Summary of pressure drop characteristics for FD2004 filter medium and granular bed.....	10
3 Engine operating conditions.....	21
4 Gas analyzer calibration data.....	26
5 Exhaust gas composition.....	28
6 Pressure transducer calibration data.....	33
7 Filter pressure drop characteristics.....	37
8 Log-normal characteristics of CWM exhaust particulate....	40
9 Fuel analyses of CWM fuel CWM exhaust particulate.....	44
10 Coal water mixture burnout calculation results.....	45
11 Chemical analyses of exhaust particulate ash.....	46
12 Comparison between GE-TS single cylinder engine emissions for different fuel injection nozzles.....	53
13 Log-normal characteristics of CWM exhaust particulate....	54
14 Average emissions from GE-TS single cylinder engine using sampling locations in the exhaust header and downstream of the surge tank.....	56
15 Test matrix for characterizing emission control prototypes	61
16 SO ₂ removal efficiencies and engine characteristics in the presence of lime spray injection into the exhaust gas of the GE-TS single cylinder engine.....	69
17 Effect of gas velocity and temperature on SO ₂ removal in 2-in. and 6-in. copper oxide granular bed.....	78
18 Effect of gas velocity and temperature on HC removal in 2-in. and 6-in. copper oxide granular bed.....	79
19 Effect of gas velocity and temperature on CO removal in 2-in. and 6-in. copper oxide granular bed.....	82

<u>TABLE</u>	<u>PAGE NO.</u>
20 Filtration characteristics of untreated and limestone precoated metal filter media.....	92
21 Filtration characteristics of lime precoated metal filter media.....	101
22 Rates of change of pressure drop across granular bed.....	106
23 Rates of change of pressure drop across thimble.....	108
A-1 High temperature filter budgetary cost.....	A-1
A-2 Medium temperature fabric budgetary cost.....	A-2
A-3 Conventional temperature fabric budgetary cost.....	A-3
A-4 Granular bed design parameter.....	A-3
A-5 Granular bed budgetary cost.....	A-3
A-6 Cost estimate for locomotive station located fabric filter for removal of dust from CWM diesel locomotive hoppers...	A-4
B-1 Chemical Analyses of GE-TS single cylinder.....	B-1
B-2 Calculated chemical composition of GE-TS single cylinder.	B-3

INTRODUCTION

This report discusses all of the experiments which have been conducted up to 12/31/89 toward characterizing and controlling emissions from a diesel engine firing coal-water mixture (CWM) as fuel. The report comprises four chapters. The first chapter (Chapter 1) discusses characterization of three filter media and an inert granular bed using simulated flue gas from a small diesel-fired engine. The second chapter (Chapter 2) describes the characterization of emissions from the single-cylinder research engine at GE Transportation Systems operated with coal-water mixture. The third chapter (Chapter 3) describes the characterizations of prototype emission control devices operated with flue gas from the CWM-fired research engine. Performances of the following prototype systems are discussed in this chapter:

- (i) cyclone
- (ii) filter media with and without pre-coat
- (iii) Granular bed of CuO-impregnated alumina spheres, as well as untreated alumina spheres

The final chapter (Chapter 4) discusses the implications of the previously described characterizations in the development of an emission control system suitable for application on a CWM-fired diesel locomotive. Future development plans are also summarized in this chapter. General arrangement and costs for a baseline emission control system comprising a fabric filter for particulate control and hydrated lime injection for SO₂ control are given in Appendix A. Cost variations for very high temperature (>800 F), high temperature (>500 F and <800 F), and conventional temperature (<500 F) fabric filter designs are also considered in this Appendix. Detailed test results are also included as appendices.

CHAPTER 1

EMISSION CONTROL CHARACTERISTICS WITH CONVENTIONAL DIESEL FLUE GAS

1.1 INTRODUCTION

Three filtration media were characterized with respect to particulate capture from the exhaust of a small diesel engine at CRD, using the bench-scale apparatus shown in Figure 1. The three evaluated media were:

- (i) a stainless steel sintered fiber filtration medium with a nominal 2 μ m pore diameter from Fluid Dynamics,
- (ii) the same medium as in item (i) above, but with a pre-coat of limestone with the size distribution (95% -325-mesh) shown in Figure 2, and
- (iii) a granular bed made of 20/40-mesh alumina spheres, as shown in Figure 3.

1.2 APPARATUS

The stainless steel fabric was sandwiched at the end of a 4-in stainless steel pipe by means of two flanges. The granular bed was supported on a Mott sintered metal filter in a 2-in pipe. The 6.375-in deep bed was topped with a 1-in layer of larger spheres to prevent fluidized escape of the smaller spheres. An electronic pressure transducer was used to monitor the pressure drop across a filter medium. The gas flow rate was measured with the aid of a variable-orifice flow meter, while the gas absolute pressure at the flow meter was read-out from an analog pressure gauge.

1.3 RESULTS

1.3.1 Pressure Transducer Calibration

Figure 4 show the linearity between the transducer voltage and the corresponding pressure drop measured using an oil-filled inclined manometer. The data in Figure 4(a) correspond to tests with the Fluid Dynamics medium. The transducer was adjusted to accommodate the higher pressure drops expected for the granular bed. The calibration data corresponding to the granular bed tests are shown in Figure 4(b). The linear correlations relating the transducer signal to the pressure drop allowed conversion of the transducer voltage, logged on a strip chart recorder, to be easily converted to a corresponding pressure loss.

Figure 1. Bench scale apparatus to characterize emission control prototypes using flue gas from conventional diesel engine.

Figure 2. Size distribution of limestone precoat material.

Figure 3. Prototype granular bed.

Figure 4(a). Pressure transducer calibration for tests with filtration fabrics.

Figure 4(b). Pressure transducer calibration for tests with granular bed.

1.3.2 Pressure Drop

Pressure drop (DP) characteristics of the filtration devices described above were observed in the sequence shown in Table 1.

Data from the above observations summarized in Table 1 are presented below.

1.3.2.1 Fluid Dynamics FD2004 Medium With Limestone Precoat

Figure 5 displays the time development of the pressure drop across the limestone precoat FD2004 medium during filtration of particulate from diesel exhaust during successive cycles (C), (D), and (E). Only the superficial velocity of gas flow through the filter was varied. The filter cake continued to accumulate on the filter during all three cycles. Cycles (C) and (D) determined the effect of gas velocity (or air-to-cloth ratio, A/C) on the filter pressure drop, while cycle E determined the extent to which the cycle (C) characteristics were restored at a lower A/C after soon performance at the higher A/C in cycle (D).

The observed DP vs. t traces in cycles (C), (D), and (E) are shown in Figure 5 compared with linear least-squares fits. The linear fits indicate that the filtration obeys Darcy's Law:

$$DP = K_2 W v \quad \text{-(1)-}$$

where:

- DP = Filter pressure drop, in. water (Pa)
- W = The areal dust loading on the filter, lb_m/sq.ft. (kg/m²)
- v = Average gas velocity through filter, ft/min (m/s)
- K₂ = Coefficient of specific resistance of the filter, in. water/[lb/sq.ft] / [ft/min], (1/s)

Since the filter cake is dynamically formed by the flow of the dust-laden gas through the filter, the dust areal loading may be related to the filtration time as,

$$W = c v Dt \quad \text{-(2)-}$$

where:

- c = Dust loading in the gas, lb_m/acf (kg/m³)
- Dt = Filtration time, min (s)

Equations (1) and (2) may be combined, as:

$$DP = K_2 c v^2 Dt \quad \text{-(3)-}$$

Equation (3) indicates that the slope, DP/Dt , of the pressure drop vs. time trace to be proportional to the gas particulate loading, c , and to the square of the filtration velocity, v , provided the specific coefficient of resistance, K_2 , is independent of velocity.

TABLE 1. FILTRATION CYCLES USED FOR DETERMINING THE PRESSURE DROP CHARACTERISTICS OF PARTICULATE FILTERS OPERATING WITH DIESEL EXHAUST.

CYCLE	FILTRATION MEDIUM	LIMESTONE PRECOAT?	OBSERVED DP CHARACTERISTIC	
			DP vs. v	DP vs. t
(A)	FD2004 (New)	No	Ambient Air	
(B)	FD2004	Yes	Ambient Air (Forming Precoat)	
(C)	FD2004	Yes	Flue Gas (10% Flow)	
(D)	FD2004	Yes	Flue Gas (20% Flow)	
(E)	FD2004	Yes	Flue Gas (10% Flow)	
(F)	FD2004 (Clean)	No	Ambient Air	
(G)	FD2004	No	Flue Gas (10% Flow)	
(H)	FD2004	No	Flue Gas (20% Flow)	
(I)	Granular Bed (Clean)	No	Ambient Air	
(J)	Granular Bed	No	Flue Gas (75% Flow)	
(K)	Granular Bed	No	Flue Gas (50% Flow)	
(L)	Granular Bed	No	Flue Gas (50% Flow)

Figure 5. Time variation of the pressure drop across the FD2004 medium with limestone precoat for diesel exhaust flow.

Figure 6. Time variation of the pressure drop across the FD2004 medium without precoat for diesel exhaust flow.

The results for the FD2004 filter, shown in Table 2 for both with and without precoat, indicate that DP/Dt increases with respect to filtration velocity at a rate faster than that expected by the square of the velocity. For example, at the end of cycle (C), $DP=4.03$.

According to Equation (1), the DP value at the beginning of cycle (D) should be 2×4.03 or 8.06, since no additional filter cake is formed when the velocity is doubled for cycle (D). The actual value of 9.45 in. water for the initial DP for cycle (D) is greater than expected value of 8.06, and indicates a velocity dependent K_2 , probably through compaction of both the precoat and the filter cake at the higher velocity. The cycle (D) slope of 0.486 in. water/min is also greater than the value of 0.256 in. water/min ($4 \times$ cycle (C) slope of 0.064 in. water/min) expected on the basis of Equation (2) by a large margin. A similar comparison holds between cycles (D) and (E). The DP at the beginning of cycle (E) of 7.28 in. water is significantly lower than half the DP value at the end of cycle (D) of 17.26 in. water. Once again, the slope of cycle (E) (0.085 in. water/min) is significantly lower than half of the cycle (D) slope of 0.486 in. water/min.

1.3.2.2 Fluid Dynamics FD2004 Medium Without Limestone Precoat

Similar conclusions may be drawn for the FD2004 filter without limestone precoat from the pressure drop vs. time data presented in Figure 6. For example, the time 0, cycle (H) DP of 10.74 in. water is more than the expected value of double the DP value of 4.4 in. water obtained at the end of filtration in cycle (G). Furthermore, the slope of cycle (H) of 0.478 in. water/min is greater than four times that of cycle (G) (0.111 in. water/min). However, the scaling of the filter pressure drop without precoat appears to be closer to that expected on the basis of Equations (1) and (2) than that with precoat, suggesting that the precoat material itself introduces the velocity dependent K_2 .

1.3.2.3 Comparison of Data from Precoated FD2004 with Data from FD2004 without Precoat

Figure 7 compare the performance of the new substrate (cycle (A)) with the substrate (cycle (F)) cleaned at the end of cycle (E). The new medium has a slightly lower DP/Dv value than the exposed substrate after cleaning, indicating good cleanability of the FD2004 medium with precoat. The cleanability of the medium after filtration without precoat was not investigated.

Figure 8 compares the effect of precoat on the velocity dependence of the DP/Dt slope. No significant effect attributable to precoat is noticeable, leading to the conclusion that the filtration characteristics of the filter medium with and without precoat are nearly the same.

The spread in the DP/Dt data shown in Figure 8 is replotted in Figure 9 as a function of the no. of filtration cycles at a given

Figure 7. Velocity dependence of the pressure drop across the clean FD2004 filter medium for ambient air flow.

Figure 8. Precoat effect on the velocity dependence of the rate of increase of filter pressure drop (DP/Dt).

TABLE 2. SUMMARY OF PRESSURE DROP CHARACTERISTICS FOR
FD2004 FILTER MEDIUM AND GRANULAR BED.

CYCLE	A/C	LIMESTONE PRECOAT?	FILTRATION TIME, t_0 , min	DP AT TIME:		DP/Dt	DP/Dv
	ft/ min			$t-t_0$ in. water	in. water	/min	in. water /min
(A)	-	No	-	-	-	-	0.0997
(F)	-	No	-	-	-	-	0.1226
(C)	5.2	Yes	30	2.11	4.03	0.064	-
(D)	10.5	Yes	16	9.45	17.26	0.486	-
(E)	5.2	Yes	32	7.28		0.085	-
(G)	5.2	No	30	1.08		0.111	-
(H)	10.4	No	28	10.74		0.478	-
(I)	-	No	-	-	-	-	$DP = .1525v$ $+ .00105v^2$
(J)	148	No	18			.3947 1.393	-
(K)	101	No	22			1.197 1.197	-
(L)	52	No	32			1.7537 .8353	-

filtration velocity. While Figure 9(a) shows a steady increase of the DP/Dt value with cycle # at the lower velocity, Figure 9(b) shows nearly constant DP/Dt at the higher velocity. In Figure 9(a), the increase in DP/Dt between cycles 1 and 2 (with precoat) is nearly the same as the increase in DP/Dt between cycle 3 (without precoat) and cycle 2 (with precoat). Hence the increase in DP/Dt with filtration cycle at the 5.4 ft/min velocity cannot be attributed to precoat effects. The DP/Dt changes at the 10.5 ft/min velocity appear to be insignificant.

1.3.2.4 Granular Bed

The granular bed investigated comprised a 6.375-in high column of 20/40-mesh (0.438-0.835 mm diameter) alumina sphere supported on a Mott sintered metal filter in a 2-in-diameter stainless steel pipe. The granular bed was topped with a 1-in bed of larger alumina sphere to prevent loss of the smaller spheres through fluidization.

Figure 9(a). Dependence of the rate of increase of the filter pressure drop at 5.22 ft/min on cycle no.

Figure 9(b). Dependence of the rate of increase of the filter pressure drop at 10.45 ft/min on cycle no.

Figure 10 shows the variation of the pressure drop (DP) across the granular bed as a function of the filtration velocity. Three different fits were attempted in order to reduce the data to scalable form. Figure 10(a) shows the interpretation in terms of the equation:

$$DP = A v^B \quad \text{-(3)-}$$

where A and B are constants. For capillary flow, the constant B=1, while for orifice flow, B=2. The fitted value of B=1.253 indicates flow in both regimes. Figure 10(b) is based on this notion of flow having two components:

$$DP = A v + B v^2 \quad \text{-(4)-}$$

where A and B are constants. The values of A=0.1525 in. water/(ft/min), and B=0.00105 in. water/(ft/min)² derived from a least-squares analysis of the data shows predominantly capillary flow at low velocities, with increasing contribution from the orifice-type flow with increasing velocity. The Ergun Correlation (1) was used to obtain a third fit for the data. The Ergun Correlation is similar to Equation (4), but specific to granular beds:

$$DP = 150u(1-e)^2v/[d^2e^3] + 1.75o(1-e)v^2/[de^3] \quad \text{-(5)-}$$

where:

u = gas viscosity

o = gas density

d = diameter of spheres comprising granular bed

e = effective porosity of granular bed

Least-squares analysis of the DP vs. v data for the granular bed assuming an average diameter of 0.0625 mm for the bed material yielded an effective porosity of 0.3666 (see Figure 10(c)). This last analysis is useful because it validates the Ergun Correlation as a means of scaling up granular bed pressure drop data.

The time development of the pressure drop across the granular bed for different filtration velocities of diesel exhaust gas is shown in Figure 11. The tests were run in the order of decreasing velocity with no cleaning of the bed between tests. The DP vs. t data for the granular bed are in general characterized by two slopes, an initial slope at the beginning of filtration and a final slope steady state slope. The data at the highest (148 ft/min) and the lowest (52 ft/min) show the two slopes, while the data at the intermediate velocity of 101 ft/min shows a steady linear trend all through the filtration cycle. Figures 12(a), 12(b), and 12(c) show the Dp vs. time data interpreted in terms of the initial and steady-state slopes. The slopes themselves are plotted in Figure 13 showing the trend for the steady-state slope to increase with velocity and the trend for the initial slope to decrease with filtration velocity.

Figure 9(c). Dependence of the rate of increase of the filter pressure drop at 5.22 and 10.45 ft/min on cycle no.

Figure 10(a). Interpretation of the granular bed DP vs. v data for ambient air in terms of Equation (3).

Figure 11. Time variation of the pressure drop across the granular bed at filtration velocities of 148, 101 and 52 ft/min with diesel exhaust flow.

Figure 12(a). Time variation of the pressure drop across the granular bed at the 148 ft/min filtration velocity with diesel exhaust flow, interpreted in terms of initial and steady-state rates of DP/Dt.

Figure 12(b). Time variation of the pressure drop across the granular bed at the 101 ft/min filtration velocity with diesel exhaust flow, interpreted in terms of initial and steady-state rates of DP/Dt .

Figure 12(c). Time variation of the pressure drop across the granular bed at the 52 ft/min filtration velocity with diesel exhaust flow, interpreted in terms of initial and steady-state rates of DP/Dt .

Figure 13. Velocity dependence of the initial and steady-state DP/Dt values for granular bed filtration of diesel exhaust.

Since there was no cleaning in-between tests at different velocities, the effective porosity of the granular bed was not constant during the tests due to the capture particulate from the diesel exhaust. As a result, the decrease of the initial slope with increasing velocity is difficult to interpret. However, the increase of the steady state slope with respect to velocity is understandable from Equation (1). The variation of the steady-state slope does not fit a linear trend. This may also be due to the varying effective porosity of the granular bed during tests.

CHAPTER 2

CHARACTERIZATION OF EMISSIONS FROM THE GE-TS CWM-FIRED SINGLE CYLINDER DIESEL ENGINE

2.1 INTRODUCTION

The characterization of emissions from the single cylinder research engine at GE Transportation Systems (GE-TS) was performed in two stages representing the evolution of the engine fuel injection nozzles tests. The first stage fuel injection nozzles were of the best available hardened metal. Intolerance of these metal nozzles to abrasion damage by the CWM fuel led to the design of diamond-tipped metal nozzles. These stage II nozzles have to date performed satisfactorily in the research engine, and hold promise for commercialization in the CWM-fired diesel locomotive. Four tests were performed to characterize the emissions with the hardened metal fuel injection nozzles for both diesel and coal-water mixture (CWM) fuels. A larger number of tests (22) were conducted with the diamond-tipped nozzles. While these larger number of tests were primarily performed to characterize the performance of prototype emission control devices using CWM-derived flue gas, the emission measurements from these tests are discussed in this chapter.

This chapter presents the results and data analyses from the CWM exhaust characterization tests that were performed with the GE-TS engine.

2.2 APPARATUS

All the emission measurements were performed using the Series 1 sampling system shown in Figure 14. The Series 1 sampling system uses a slipstream of about 3% of the total flow extracted from the surge tank downstream of the engine. The hot slipstream gas initially flows through an absolute filter, rated at 1 micrometer, in which particulate matter is removed. The particulate-free gas then flows through a metering orifice and then through a series of gas analyzers which continuously measure its composition (SO_2 , NO_x , CO , CO_2 , HC , and O_2). Analyses for the chemical composition, size distribution, and shape of the particulate collected in the absolute filter were performed off-line. Periodic acquisitions of the gas flow rate, gas composition, and pressure drop across the absolute filter and other operational data were performed with the aid of an AT-compatible computer and a analog-to-digital datalogger interface, and stored on disk for later analyses (see Figure 15).

FIG 1; PHASE I SAMPLE TRAIN

Figure 14. Series 1 sampling probe.

PROPOSED
DATA ACQUISITION SYSTEM
FOR
COAL-WATER SLURRY-FIRED DIESEL LOCOMOTIVE PROJECT

Figure 15. Data acquisition system used for emission control investigations at GE-TS engine laboratory.

2.3 TESTS WITH HARDENED METAL FUEL INJECTION NOZZLES

The GE-TS engine was operated with diesel oil fuel during Test 01. This test was used as a practice run to determine potential operational problems with the Series 1 equipment and the gas analyses instrumentation provided by GE-TS. The remaining three tests were performed with the engine fired with coal-water mixture (CWM). The diesel engine operating conditions under CWM operation during the three emission tests (Tests 03, 04, and 05) are as follows (see Table 3). The burnout values shown in Table 3 are nominal. Accurate calculations for the burnout using emission measurements will be discussed below.

TABLE 3. ENGINE OPERATING CONDITIONS

	TEST 03	TEST 04	TEST 05
HP	222	215	238
BURNOUT, %	93.1	90.1	90.5
Pmax, psia	2,285	2,076	2,435
EXCESS AIR	2.16	2.16	1.93

2.4 RESULTS WITH HARDENED METAL FUEL INJECTION NOZZLES

2.4.1 Exhaust Gas Analyzer Calibrations

The CWM exhaust gas was analyzed for SO_2 , NO_x , O_2 , CO_2 , CO, and Hydrocarbons (HC). The on-line gas analyzers used continuously monitoring the diesel exhaust gas were calibrated using calibration gas. The analyzer signal vs. calibration gas concentrations obtained from this procedure are shown in Table 2. The SO_2 , O_2 , and HC analyzers were found to have linear responses over their respective design measurement ranges. Each of these analyzers required only a single constant to convert its signal voltage to a concentration unit. As evident from Table 2, the analyzers for measuring NO , CO_2 , and CO showed non-linear signal output with respect to gas concentration. The conversion of the signals voltages from these analyzers to concentration units was accomplished through look-up tables entered into the data-logger, which allowed linear interpolations between calibration data.

2.4.2 Exhaust Gas Composition

Figures 16, 17, and 18 show the exhaust gas compositions during Tests 3, 4, and 5. Span adjustments and calibrations were performed during part of Test 3. Meaningful gas concentration data were obtained during this test after about 85 minutes into the test (see Figure 16). In Test 4, gas sampling from the engine was initiated after about 30 minutes into the test (see Figure 4). All of the data presented in Figure 5 showing gas concentrations during Test 5 are meaningful. Table 5 summarizes the mean exhaust gas concentrations measured during Tests 3, 4, and 5. The measured CWM flue gas composition are roughly in keeping with results from combustion calculations. Instrumentation baseline drifts are an issue, and can be overcome in the future by automatic baseline reset procedures. The periodic fluctuation in the NO_x and CO concentrations appear to be due to corresponding periodic shifts in thermal equilibria. A decreasing HC (hydrocarbon) concentration and an increasing CO concentration was observed in all three emission tests performed on the CWM-fired engine.

GE-TS CWM DIESEL(222HP,93.1%,2285psi,2.6X)
CEESI EMISSION TEST NO. 3 - 4/17/89

Figure 16. Time variation of Test 3 exhaust gas compositions:
 (a) CO and HC, (b) SO₂ and NO_x, and (c) CO₂ and O₂.

GE-TS CWM DIESEL(215HP,90.1%,2176psi,2.2X)
GEESI EMISSION TEST NO. 4 - 4/18/89

Figure 17. Time variation of Test 4 exhaust gas compositions:
 (a) CO and HC, (b) SO₂ and NO_x, and (c) CO₂ and O₂.

GE-TS CWM DIESEL(238HP,90.5%,2435psi,1.9X)
GEESI EMISSION TEST NO. 5 - 4/19/89

Figure 18. Time variation of Test 5 exhaust gas compositions:
 (a) CO and HC, (b) SO₂ and NO_x, and (c) CO₂ and O₂.

TABLE 4. GAS ANALYZER CALIBRATION DATA

GAS	CONCENTRATION	ANALYZER SIGNAL,V	SENSITIVITY, ppm/V OR %/V
SO ₂	0 ppmvw	1.000	
	253 ppmvw	2.012	250 ppmvw/V
NO _x	0 ppmvw	0	
	1002 ppmvw	0.4280	2341 ppmvw/V
	1025 ppmvw	0.4378	2341 ppmvw/V
	1563 ppmvw	0.6274	2838 ppmvw/V
O ₂	0 %vw	0	
	20.9 %vw	1.8856	11.08 %vw/V
CO ₂	0 %vw	0	
	3.999 %vw	0.661	6.05 %vw/V
	4.77 %vw	0.719	6.634 %vw/V
CO	0 ppmvw	0	
	276 ppmvw	0.1257	2196 ppmvw/V
	697 ppmvw	0.2743	2833 ppmvw/V
HC	0 ppmvw	0	
	500 ppmvw	1.000	500 ppmvw/V

The particulate concentration in the CWM exhaust was measured by weighing the particulate catch in the absolute filter, and by measuring the total volume of exhaust gas depositing this particulate, and is in the range of 0.25 to 0.35 gr/acf. Particulate samples are being analyzed for chemical composition.

2.4.3 Pressure Transducer Calibrations

The gas flow rate and temperature were monitored throughout Tests 3, 4, and 5. While the thermocouple used to monitor temperature are absolute sensors and required no calibrations, the pressure transducers used to monitor gas flow did require calibrations. The gas flow at the inlet of the absolute filter was measured through monitoring of the absolute pressure at the absolute filter inlet, the absolute pressure at the inlet of the square edged-orifice and the pressure drop across the orifice. The pressure transducers were calibrated by imposing varying pressures on the transducer by means of an external pressure source (sealed bellows), measuring these externally induced pressures (or pressure differences) by means of a precision water manometer, and monitoring the corresponding signals from the transducers through the data acquisition system. The orifice itself was calibrated using a separate calibration apparatus in the laboratory using ambient air.

The pressure transducer calibration data are shown in Table 6, and in Figures 19, 20, 21, and 22. Because of slight non-linearities between transducer response and pressure, the calibration data were entered into the data acquisition system through look-up tables which ensures linear interpolations only between successive calibration data points spanning given transducer outputs being converted to pressure units.

2.4.4 Sampling Apparatus Gas Temperatures

Figure 23(a), 23(b), and 23(c) shows the temperature variation of the gas in the sampling apparatus during Test 3, 4, and 5. The data in these Figures show the effectiveness of the heat tracing and insulation in maintaining uniform temperature within the apparatus. The temperature variations during Test 5 is larger than those for Tests 3 and 4. This is because of the higher exhaust gas flow rate during Test 5. The cylindrical absolute filter elements used in Tests 3 and 4 had dimensions

TABLE 5. EXHAUST GAS COMPOSITION

	TEST NO.3	TEST NO.4	TEST NO.5
CO, ppmvw	454	400-600	695-836
HC, ppmvw	120	89-131	96-172
NOx, ppmvw	532	433	574
SO ₂ , ppmvw	259	233	293
CO ₂ , % molar	6.19	6.11	6.39
O ₂ , % molar	13.74	13.74	12.95
PARTICULATE CONC, gr/ft ³	0.25	0.34	0.27
HP	222	215	238
BURNOUT, %	93.1	90.1	90.5
P _{max} , psia	2,285	2,076	2,435
EXCESS AIR	2.16	2.16	1.93

of 1.25 in. diameter X 5 5/32 in. length corresponding to a surface area of 0.162 sq.ft.. The element used in Test 5 had the same diameter as in Tests 3 and 4 but a 20 in. length. The larger surface area of the Test 5 filter element allowed the capability of a higher flow rate during Test 5. The temperature within the sampling apparatus could be maintained within only 50 F with the higher sampling gas flow rate.

2.4.5 Absolute Filter Pressure Drop Characteristics

The pressure drop across the absolute filter cake was monitored during all three tests. The time variation of the pressure drop and the average

DOE CWM DIESEL LOCOMOTIVE PROJECT

SYSTEM INLET PRESSURE CELL CALIBRATION

Figure 19. Calibration line for absolute pressure transmitter measuring the sampling system inlet absolute pressure.

ORIFICE PRESSURE CELL CALIBRATION

Figure 20. Calibration line for absolute pressure transmitter measuring the absolute pressure at the orifice inlet

DOE CWM DIESEL LOCOMOTIVE PROJECT

GAS THIMBLE DP CELL CALIBRATION #1

GAS THIMBLE DP CELL CALIBRATION #2

Figure 21. Calibration line for differential pressure transmitter measuring the pressure drop across the thimble.

DOE CWM DIESEL LOCOMOTIVE PROJECT

ORIFICE DP CELL CALIBRATION

Figure 22. Calibration line for differential pressure transmitter measuring the pressure drop across the orifice.

GE-TS CWM DIESEL(222HP,93.1%,2285psi,2.6X)

GEESI EMISSION TEST NO. 8 - 4/17/88

GE-TS CWM DIESEL(215HP,90.1%,2176psi,2.2X)

GEESI EMISSION TEST NO. 4 - 4/18/88

GE-TS CWM DIESEL(238HP,90.5%,2435psi,1.9X)

TEST NO. 5 - 34" THIMBLE

Figure 23. Temperature variation in the sampling system during: (a) Test 3, (b) Test 4, and (c) Test 5.

TABLE 6. PRESSURE TRANSDUCER CALIBRATION DATA

TRANSDUCER	PRESSURE, in. water	SIGNAL, V	CALIBRATION LINE
System Inlet	0	1.0708	
Gauge Pressure	25	1.1071	
(Figure 19)	40	1.1310	663.6 V - 710.5
Orifice Inlet	0	1.0284	
Gauge Pressure	5	2.0832	
(Figure 20)	10	3.0638	
	15	3.9617	
	20	4.7850	
	25	5.5282	5.5329 V - 6.3583
Absolute Filter	0	0.9975	
Pressure Drop	10	1.9776	
Calibration #1	20	2.9509	
(Figure 21(a))	30	3.9271	
	40	4.9007	10.250 V - 10.246
Absolute Filter	0	0.7120	
Pressure Drop	10	1.0801	
Calibration #2	20	1.6150	
(Figure 21(b))	30	2.1480	
	40	2.6810	19.890 V - 12.763
Orifice Pressure	0	1.0209	
Drop (Figure 22)	5	1.8701	
	10	2.6857	
	15	3.4532	
	20	4.1738	
	25	4.8321	6.5321 V - 7.1355

air-to-cloth ratio in the absolute filter measured during Tests 3, 4, and 5 are shown in Figures 24, 25, and 26. In both Tests 3 and 4 (Figures 24 and 25), the CWM fuel was introduced into the engine at about time $t=40$ min. In Test 5, sampling of the CWM exhaust was initiated at time $t=35$ min. Soon after changeover from diesel oil to CWM fuel, the absolute filter pressure first decreased for a period of about 15 min. before settling to a trend of linearly increasing pressure drop with time. In both Tests 4 and 5, the pressure across the filter always showed an overall trend of increasing pressure drop with respect to time. In Test 5, the pressure drop displayed fluctuations, the extent of which appeared to increase with increasing time (or filter cake thickness). This fact is shown more clearly in Figure 27 which plots the time variation in the number of DP/Dt slope reversals. Figure 27 shows an increasing number of slope reversals with increasing filtration time.

Figure 24. Test 3 observations: (a) pressure drop across thimble, and (b) thimble A/C.

GE-TS CWM DIESEL(215HP,90.1%,2176psi,2.2X)
 GEESI EMISSION TEST NO. 4 - 4/18/89

Figure 25. Test 4 observations: (a) pressure drop across thimble, and (b) thimble A/C.

GE-TS CWM DIESEL(238HP,90.5%,2435psi,1.9X)
GEESI EMISSION TEST NO. 5 - 4/18/88

Figure 26. Test 5 observations: (a) pressure drop across thimble, and (b) thimble A/C

Figure 27. Time dependence of the thimble pressure drop fluctuations ($D[DP]/Dt$) during Test 5.

The rate of increase of pressure drop with CWM-fired diesel exhaust is approximately 0.5 in. water/min, and nearly independent of A/C in the range of 3 to 7 ft/min. This independence appears to be related to filter cake fallout from the upper part of the horizontal filter. Thicker dust deposition observed in the bottom part of the filter and the increasing intensity of fluctuation of the absolute pressure drop discussed above also support this self-cleaning concept.

The variation of the rate of change of the pressure drop across the filter, and the coefficient of specific resistance, K_2 , defined from D'arcy's Law (see Equation (1) in Chapter 1) are shown in Figure 28 and 29. The average value of K_2 appears to be around 500.

Operation of the absolute filter with exhaust from diesel fuel (Figures 25 and 26) is characterized by rapid increase in the filter pressure drop. This near blinding of the filter with diesel exhaust appears due to fineness of the diesel exhaust particulate.

TABLE 7. FILTER PRESSURE DROP CHARACTERISTICS

	TEST NO.3	TEST NO.4	TEST NO.5
PERIOD 1:			
A/C	5.24	6.21	3.07
D(DP)/Dt	-1.06	1.66	0.46
K ₂	884	1,269	
PERIOD 2:			
A/C	5.34		4.53
D(DP)/Dt	.51		0.40
K ₂	497		507
PERIOD 3:			
A/C			5.47
D(DP)/Dt			0.52
K ₂			454

In conclusion, fabric filter cleanup of CWM exhaust with hardened metal fuel injection nozzles shows promise, although similar cleanup of diesel oil exhaust appeared to be difficult.

DOE CWM DIESEL LOCOMOTIVE PROJECT
PHASE 1 EMISSION TESTS ON GE-TS CWM ENGINE

PHASE 1 EMISSION TESTS ON GE-TS CWM ENGINE

Figure 28. (a) Dependence on the thimble A/C of: (a) the rate of change of thimble pressure drop ($D[DP]/Dt$), and (b) the coefficient of specific resistance, K_2 .

DOE CWM DIESEL PROJECT
CWM DIESEL EXHAUST SIZE DISTRIBUTION

Figure 29. Bimodal, log-normal fits for the measured fractional size distributions of the exhaust particulate collected during: (a) Test 3, (b) Test 4, and (c) Test 5 from the CWM-fired GE-TS diesel engine fitted with hardened metal fuel injection nozzles.

2.4.6 CWM Exhaust Particulate Size Distributions

Figures 29 and 30 summarize the size distributions of the particulate matter collected in the absolute filter during Tests 3, 4, and 5. The size distributions were measured with a Shimadzu Size Analyzer operating on light scattering principles. The observed size distributions are bi-modal. Figures 29 and 30 also show the result of fitting the bimodal size distributions to log-normal distributions defined by:

$$f(D) = K/D \exp -\{[\ln(D/D_0)]/[2^{0.5} \ln s]\}^2$$

where $K = (2 \pi)^{0.5} \ln s$. In the above distribution, D_0 is the mean size and s the standard deviation.

Figure 29 shows the fractional mass distributions while Figure 30 shows the cumulative mass distributions. Table 8 summarizes the variation of the log-normal characteristics of the observed size distributions. Figures 31, 32, and 33 show the variation of the fitted log-normal distribution parameters with Test No. The distribution having the smaller mean size appears to be fixed with Test No. or nozzle wear, and is identifiable with the ash cores containing little or no carbon resulting from fully combusted CWM particles. The second distribution appears to be attributable to incompletely burned carbon particles. This size distribution varies in both mean size and the standard deviation with each test.

TABLE 8. LOG-NORMAL CHARACTERISTICS OF CWM EXHAUST PARTICULATE (HARDENED METAL FUEL INJECTION NOZZLES)

TEST NO.	DISTRIBUTION 1			DISTRIBUTION 2		
	$D_0, \mu m$	s	MASS FRACTION	$D_0, \mu m$	s	MASS FRACTION
3	3.40	1.394	0.652	10.5	1.300	0.348
4	3.20	1.332	0.470	12.0	1.394	0.530
5	3.30	1.332	0.425	13.8	1.455	0.575

Figure 30. Bimodal, log-normal fits for the measured fractional size distributions of the exhaust particulate collected during: (a) Test 3, (b) Test 4, and (c) Test 5 from the CWM-fired GE-TS diesel engine fitted with hardened metal fuel injection nozzles.

DOE CWM DIESEL PROJECT
CWM EXHAUST PARTICULATE CHARACTERISTICS

Figure 31. Variation of the log-normal mean diameters for the bimodal distributions of Tests 3 to 5 shown in Figures 29 and 30.

Figure 32. Variation of the log-normal standard deviations for the bimodal distributions of Tests 3 to 5 shown in Figures 29 and 30.

Figure 33. Variation of the log-normal relative mass fractions for the bimodal distributions of Tests 3 to 5 shown in Figures 29 and 30.

2.4.7 Fuel Burnout

The fuel burnout values presented by GE-TS are based on a thermal energy balance. In this analysis, the CWM heating value is compared with the thermal energy of the exhaust gas and engine heat losses. The difference between the CWM heating value input and the heat dissipated in the engine and the exhaust gas is interpreted in terms of a fuel burnout fraction. In Table 10, this thermal value for the fuel burnout is shown as the observed value for the burnout fraction.

Characterization of the exhaust from the CWM-fired diesel engine allows two additional determinations of the fuel burnout. The first method is based on fuel analyses of the CWM-fuel and the exhaust particulate (treated as fuel for the purpose of performing fuel analyses). In this determination, the burnout fraction is given by:

$$f_E = f_F / [f_F + (1-f_F)(1-B)], \text{ where}$$

f_E = mass fraction of ash in exhaust particulate
(dry basis)

f_F = mass fraction of ash in fuel (dry basis)

B = fuel burnout fraction

The fuel burnout, B , can be obtained from the above equation, as:

$$B = 1 - f_F(1-f_E) / [f_E(1-f_F)]$$

The first of the calculated values for the burnout presented in Table 10 relates to the above method. The fuel analyses for the CWM-fuel and exhaust particulate from Tests 3, 4, and 5 used in the fuel analyses-based burnout evaluation are shown in Table 11.

Table 11 also compares the relative mass fraction of particles belonging to the fully burned coal particles, as deduced from the size distributions of the exhaust particulate with the mass ratio of Ash/(Ash + Fixed Carbon) using the results of the chemical analyses. Both these ratios show the similar trends with engine run time, and add credence to the previous assumption that one component in the bimodal exhaust particulate is attributable to nearly completely burned ash.

An alternative expression for fuel burnout, B , may be obtained by combining a combustion calculation for predicting the CWM-derived exhaust gas composition, and the measured exhaust gas composition and particulate concentration. In this calculation, the Excess Air Factor, defined as:

$$\text{Excess Air Factor} = \frac{[\text{Moles Actual } O_2 / \text{Unit Mass CWM}]}{[\text{Moles Stoichiometric } O_2 / \text{Unit Mass CWM}]}$$

is varied until the predicted CO_2 concentration is in agreement with the corresponding measured value. At the same time, the burnout fraction is varied until the calculated particulate concentration, comprising the ash from the CWM coal and the unburned carbon, is in agreement with its corresponding experimental value. The second of the calculated burnout values shown in Table 10 relates to the combustion-based calculation.

TABLE 9. FUEL ANALYSES OF CWM FUEL CWM-EXHAUST PARTICULATE

TEST #	3	4	5	CWM
<i>Analysis</i>				
Total Moist	8.23	7.42	6.09	0.0
Volatile	27.7	35.5	23.7	39.4
Fixed C	20.6	26.3	43.4	59.8
Ash	43.4	30.8	26.8	0.8
Sulfur	2.50	1.70	1.44	0.81
Carbon	41.4	54.5	58.5	82.59
Hydrogen	<0.1	<0.1	<0.1	5.34
Nitrogen	0.74	0.96	1.05	2.08
Oxygen	4.14	4.95	6.32	8.15
Btu/Lb	5,670	7,500	7,940	14,892
Ash/(Fixed C+Ash)	0.68	0.54	0.38	
Dist 1 /(Dist 1+Dist 2) (From Table 6)	0.65	0.47	0.43	

There are inherent errors in each of the three methods of determining fuel burnout. In the thermodynamic method, estimates of heat losses by the engine have large uncertainties. The method based on the fuel analyses assumes that all of the non-ash material of the exhaust particulate resides on the particulate. This assumption ignores the presence of volatiles in the exhaust particulate (see Table 11). The burnout determination based on the combustion calculation too ignores the presence of volatile matter on the exhaust particulate.

The burnout values determined from the fuel analyses and combustion calculations appear to be closer together than the burnout values obtained from the method based on thermodynamics.

Table 11 summarizes the chemical analyses of the ash component of the exhaust particulate (after oxidation of all organic material). The variation in the ash composition with engine run time appears to be due to statistical fluctuations in the CWM composition as well as to the uncertainty in the results due to the small sample masses being used in the analyses.

TABLE 10. COAL-WATER MIXTURE BURNOUT CALCULATION RESULTS

	TEST 03		TEST 04		TEST 05	
	CALC	OBS	CALC	OBS	CALC	OBS
Excess Air,%	2.675	2.16	2.705	2.16	2.585	1.93
Burnout,% (Fuel Analyses)	97.00	93.10	95.60	90.10	96.90	90.50
Burnout,% (Combustion Calculation)	99.07	93.10	97.98	90.10	97.47	90.50
EXHAUST GAS CONC.						
CO ₂ , vol%	6.19	6.19	6.11	6.11	6.39	6.39
H ₂ O, vol%	6.67		6.67		6.86	
N ₂ , vol%	75.03		75.03		74.90	
HCl, ppmvw	47.0		47.1		48.6	
SO ₂ , ppmvw	246	259	247	233	255	293
O ₂ , vol%	12.08	13.74	12.16	13.74	11.81	12.95
Part,gr/acf	0.25	0.25	0.34	0.34	0.27	0.27

TABLE 11. CHEMICAL ANALYSES OF EXHAUST PARTICULATE ASH

COMPONENT MASS %	TEST 3	TEST 4	TEST 5
SiO_2	17.5	17.7	16.7
Al_2O_3	21.3	20.1	18.8
Fe_2O_3	29.1	30.4	32.2
TiO_2	3.20	6.39	3.51
CaO	7.44	7.54	4.14
MgO	2.35	2.44	1.08
Na_2O	4.80	4.46	3.92
K_2O	1.15	1.14	1.13
Li_2O	0.02	0.02	0.02
P_2O_5	0.25	0.31	0.25
Specific Gravity	1.52	1.81	1.34

2.5 TESTS WITH DIAMOND-TIPPED METAL FUEL INJECTION NOZZLES

Most of the 24 tests performed with the new fuel injection nozzles corresponded to a 250 HP power output from the engine. On some SO_2 removal tests, the fuel injection timing and excess air flow rate were varied to obtain specific exhaust gas temperatures at the engine manifold at the expense of the engine power output. These non-standard test conditions are clearly stated in the discussions on SO_2 removal to follow in the next chapter.

2.6 RESULTS WITH DIAMOND-TIPPED METAL FUEL INJECTION NOZZLES

Table 12 compares the emissions from the GE-TS engine fitted with the diamond-tipped nozzles with those when the nozzles were of hardened metal. Differences in the SO_2 , CO_2 , and O_2 concentrations are primarily due to variations in the excess air used for combustion. On the other hand, there are significant differences in the NO_x , HC, and CO concentrations attributable to differences in the fuel injection nozzles. With the diamond nozzle, the NO_x concentration is 30 to 60% higher, the HC concentration is 20 to 100% higher, while the CO concentration is 50 to 75% lower than in the metal nozzle. The above differences are understandable on the basis of the assumption that fuel atomization is superior in the diamond-tipped nozzle. Consequently, coal combustion occurs more rapidly in the engine with the diamond nozzles resulting in hotter flame temperatures in the engine. The higher NO_x and HC concentrations observed for the diamond nozzle are a direct consequence of the higher engine cylinder gas temperature. Oxidation of the CO in the engine exhaust continues in the exhaust duct. A higher exhaust gas temperature will be expected to result in a higher fraction of CO being converted to CO_2 , as observed in the case of the engine fitted with diamond-tipped nozzles.

Earlier sections discussed the bi-modal size distributions for the diesel exhaust particulate (see Figures 29 and 30, and Table 8). The log-normal parameters corresponding to the inlet particulate size distributions obtained with the diamond nozzles are presented in Table 13 and in Figures 34 to 38. Table 13 shows the parameters of the distributions of particulate collected in the cyclone hopper, absolute filter, and the particulate captured in the granular bed. These distributions will be discussed relative to the performances of the prototype cyclone and granular bed in later sections. The interest in this section is to compare differences in the diesel exhaust particulate distributions attributable to differences in the fuel injection nozzles. The inlet size distributions plotted in Figures 34 to 38 and summarized in Table 13 were inferred from the distributions of cyclone hopper and absolute filter (thimble) catches during tests to characterize the performance of the prototype cyclone. The distributions obtained for the engine running with the hardened metal nozzles showed a decreasing mass fraction of the ash-like component (and consequently an increasing mass fraction of the carbonaceous component) with increasing engine run-time indicating combustion degradation probably due to nozzle degradation. The size distributions in Table 13 show no evidence of such a degradation of the diamond tipped nozzle with increasing engine run-time. In fact, the last test for which the size distribution was measured (Test 22) shows the

Figure 34. Bimodal, log-normal fits for the measured fractional and cumulative (% less than) inlet size distributions of the exhaust particulate collected during Test 14 from the CWM-fired GE-TS diesel engine fitted with diamond-tipped metal fuel injection nozzles.

Figure 35. Bimodal, log-normal fits for the measured fractional and cumulative (% less than) inlet size distributions of the exhaust particulate collected during Test 15 from the CWM-fired GE-TS diesel engine fitted with diamond-tipped metal fuel injection nozzles.

Figure 36. Bimodal, log-normal fits for the measured fractional and cumulative (% less than) inlet size distributions of the exhaust particulate collected during Test 16 from the CWM-fired GE-TS diesel engine fitted with diamond-tipped metal fuel injection nozzles.

Figure 37. Bimodal, log-normal fits for the measured fractional and cumulative (% less than) inlet size distributions of the exhaust particulate collected during Test 17 from the CWM-fired GE-TS diesel engine fitted with diamond-tipped metal fuel injection nozzles.

Figure 38. Bimodal, log-normal fits for the measured fractional and cumulative (% less than) inlet size distributions of the exhaust particulate collected during Test 22 from the CWM-fired GE-TS diesel engine fitted with diamond-tipped metal fuel injection nozzles.

TABLE 12. COMPARISON BETWEEN GE-TS SINGLE CYLINDER
ENGINE EMISSIONS FOR DIFFERENT FUEL
INJECTION NOZZLES

<u>EMISSION COMPONENT</u>	<u>HARDENED METAL NOZZLE</u>	<u>DIAMOND TIPPED NOZZLE</u>
SO ₂ , ppmvw	230-290	270-308
NO _x , ppmvw	430-575	680-747
HC, ppmvw	95-170	190-206
CO, ppmvw	400-840	208-214
CO ₂ , %(vol)	6.2-6.4	6.0-7.8
O ₂ , %(vol)	13.0-13.7	11.8-14.0
FUEL BURNOUT:	90-95%	95-99%

TABLE 13. LOG-NORMAL CHARACTERISTICS OF CWM EXHAUST PARTICULATE
(DIAMOND-TIPPED METAL FUEL INJECTION NOZZLES)

TEST NO.	DISTRIBUTION 1			DISTRIBUTION 2		
	$D_o, \mu m$	s	MASS FRACTION	$D_o, \mu m$	s	MASS FRACTION
8(CYCLONE)	3.20	1.30	0.76	10.0	1.25	0.24
12(CYCLONE)	2.20	1.25	0.55	7.5	1.40	0.45
14(CYCLONE)	3.50	1.30	0.35	15.0	1.40	0.65
15(CYCLONE)	3.50	1.25	0.60	10.0	1.25	0.40
16(CYCLONE)	3.30	1.25	0.73	11.0	1.25	0.27
17(CYCLONE)	3.50	1.23	0.45	12.5	1.30	0.55
18(CYCLONE)	3.30	1.25	0.50	10.0	1.30	0.50
12(THIMBLE)	3.50	1.30	0.85	10.5	1.23	0.15
14(THIMBLE)	3.00	1.35	1.00	N/A	N/A	0.00
15(THIMBLE)	2.40	1.40	0.95	7.0	1.20	0.05
16(THIMBLE)	3.20	1.40	1.00	N/A	N/A	0.00
17(THIMBLE)	3.30	1.40	1.00	N/A	N/A	0.00
8(GRAN.BED)	3.30	1.35	0.76	12.0	1.40	0.24
18(GRAN.BED)	3.00	1.40	0.45	19.5	1.40	0.55
14(INLET)	3.20	1.37	0.50	14.7	1.42	0.50
15(INLET)	3.00	1.40	0.73	10.6	1.30	0.27
16(INLET)	3.20	1.30	0.85	11.0	1.30	0.15
17(INLET)	3.30	1.23	0.57	12.6	1.34	0.43
22(INLET)	3.15	1.35	1.00	N/A	N/A	0.00

ash-like component to predominate with little evidence for the presence of the carbonaceous component. This is an indication of the improved combustion characteristics obtainable in the diesel engine fitted with the diamond-tipped fuel injection nozzles, and the absence of nozzle degradation with increasing engine run-time up to about 30 hours.

Earlier tests (Tests 14 to 17) show varying relative mass fractions of the ash-like and carbonaceous components probably resulting from variations in engine parameters (such as fuel injection timing). Table 13 shows that increasing mass fraction of the ash-like component (or increasing fuel burn-out efficiency) is accompanied by a decreasing mean size of the carbonaceous component. This relationship is expected, and indicates that the unburned fuel resides in the carbonaceous component. Improved fuel combustion results in a finer exhaust particle size distribution due to the absence of the larger-sized carbonaceous component. Consequently, improved combustion places a greater burden on the particulate collector downstream of the engine. This difficulty will be discussed in greater detail in later sections of this report.

The detailed size distributions summarized in Table 13 are assembled in Appendix D.

2.6 Alternate Gas Sampling Locations

A comparison of emission measurements using single engine exhaust gas samples drawn from two separate sampling locations was performed (Test 22). The two sampling locations were Port No. 3 in the exhaust header and Port No. 1 downstream of the surge tank. Gas from each location was alternately sampled for a 20 to 30 minute period and delivered to a common gas analyzer instrumentation rack equipped for the measurement of SO_2 , NO_x ($\text{NO} + \text{NO}_2$), O_2 , CO_2 , CO , and hydrocarbons (HC). Coal water mixture made from nominally 2.5 μm Otisca Penna Mariana coal was used in the current engine test. Table 14 below summarizes the average emissions recorded by the gas analyzers for each sample location. Since oxidation of the hydrocarbons to CO and CO_2 appear to take place during transit of the exhaust gas, no meaningful correlations can be made between the emission measurements of both HC and CO from the two sampling locations. The differences in the SO_2 , NO_x , O_2 , and CO_2 gas concentrations measured for the two sample locations may be understood by noting that the sample location downstream of the surge tank yields a spatially well mixed gas sample, while the gas sample drawn from the exhaust manifold is subject to pulsations resulting from the openings and closings of the engine intake and exhaust valves. During the period that the exhaust valve is opened, high pressure and high temperature exhaust gas rushes past the exhaust header sampling location. This is followed by a period when both exhaust and intake valves are simultaneously open. During this scavenging period, combustion air travels at a slower rate past the sampling location due to its lower pressure and temperature. Since the exhaust gas flows faster than the combustion air in the exhaust header, the gas sampled from the exhaust header can be expected to consist of a continuous stream of a short pulse of exhaust gas followed by a longer stream of combustion air. Gas Analyzers having long response times when measuring such a pulsed sample, will emphasize the concentration of the gas in the longer pulse (i.e. the combustion air). Thus, the gas analyzers cannot provide a good time average because of pulsations in the gas sample delivered to them. On the other hand, the surge tank provides ample volume and gas residence time to obtain a well-mixed, and representative sample.

TABLE 14. AVERAGE EMISSIONS FROM GE-TS SINGLE CYLINDER ENGINE USING SAMPLING LOCATIONS IN THE EXHAUST HEADER AND DOWNSTREAM OF THE SURGE TANK.

MEASUREMENT	UNITS	EXHAUST HEADER	SURGE TANK
SO ₂	ppmvw	134	191
NO _x	ppmvw	373	740
O ₂	%(vol)	16.7	12.8
CO ₂	%(vol)	3.43	6.99
HC	ppmvw	288	201
CO	ppmvw	157	193
MASS MEAN DIAMETER	um	2.99	2.91
LOI	%(mass)	46.5	40.6
FUEL BURNOUT	%(mass)	98.5*	98.8*

* Assuming 1.7% ash in coal

Table 14 also compares the mean particle size and the loss on ignition (LOI) of the samples captured from the two sampling locations. The size distributions of the particulate matter from the two sampling locations appear to be the same. The sample obtained from the surge tank location appears to be slightly finer than that from the exhaust header location, indicating slight combustion of particulate char even after exhaust from the engine. The higher LOI for the exhaust sample also confirms this post-engine combustion.

Previous exhaust particulate matter were seen to be bimodal with peaks at approximately 3 and 10 μm . The particulate matter from the current test appear to comprise only the smaller particles, possibly indicating finer CWM atomization or finer CWM coal particulate than in previous engine tests.

The detailed size distributions discussed above are compiled in Appendix E.

2.6 SUMMARY

Exhaust from the GE-TS single cylinder diesel engine fitted with fuel injection nozzles of hardened, and diamond-tipped metal nozzles, and firing CWM has been characterized with respect to gas composition, particulate size distribution, and particulate filtration characteristics. The measured flue gas compositions are roughly in keeping with results from combustion calculations. Periodic fluctuations in the measured NO_x and CO concentrations appear due to temperature dependent shifts in^x chemical equilibria. Observed trends of decreasing HC (hydrocarbon) concentration and increasing CO concentration with the GE-TS engine appear to be due to oxidation of the HC in the exhaust duct. The diamond-tipped nozzles appear to result in higher gas temperatures within the engine cylinders through better atomization, and consequently better coal combustion. Higher NO_x and HC concentrations result in comparison with the hardened metal nozzles. More CO is oxidized in the exhaust duct in the case of the diamond-tipped nozzles, again as a result of the higher exhaust gas temperatures.

Oil fired diesel exhaust causes near-blinding of the absolute filter as shown by the rapid rise of filter pressure drop. The rate of increase of pressure drop with CWM-fired exhaust is approximately 0.5 in.w.c./min, and nearly independent of filtration velocity in the range of 3 to 7 ft/min. This independence appears due to fall out from the upper part of the horizontally mounted filter. Thicker dust deposition in the bottom part of the filter and increasing fluctuation in the filter pressure drop with increasing filter cake thickness also support this self-cleaning concept. Thus, filtration of CWM-exhaust appears feasible, although filtration of diesel oil exhaust appears difficult.

The particulate concentration in the CWM-exhaust is in the range of 0.25 to 0.35 gr/acf. The CWM-particulate size distributions are bi-modal and comprised of a ash component of fixed mean size and standard deviation, and a variable, incompletely burned particle component whose mean size and standard deviation increase with increasing engine run time. When the fuel injection nozzles are of hardened metal, the fraction of the ash component decreases with increasing engine run time, while the fraction of the incompletely burned coal particles increases. Both components conform to a log-normal size distribution.

No degradation of fuel atomization is evident from the size distributions of the exhaust particulate when the GE-TS research engine is fitted with diamond-tipped fuel injection nozzles. The diamond tipped nozzles also lead to improved fuel combustion even to the extent of nearly completely burning out the carbonaceous component in the exhaust particulate. Collection of the finer exhaust particulate resulting from good fuel combustion in this case will be more difficult. The better combustion, and consequently hotter flame temperatures, obtained in the diesel engine with the aid of the diamond-tipped nozzles is also accompanied by higher NO_x and hydrocarbon production. On the other hand, the CO concentration is lower probably due to post-combustion oxidation.

CHAPTER 3 - CHARACTERIZATION OF EMISSION CONTROL PROTOTYPES

3.1 INTRODUCTION

24 tests to characterize bench-scale emission control devices included in the Series 2 equipment, shown in Figure 39, were completed. The 24 tests spanned the following emission control methods:

(i) Control of SO_2

- (a) lime-impregnated coal-water mixture (CWM)
- (b) lime dry injection into CWM exhaust gas
- (c) lime spray injection into CWM exhaust gas
- (d) copper oxide granular bed

(ii) Particulate Control

- (a) cyclone
- (b) metal filters
- (c) copper oxide granular bed
- (d) inert granular bed

The arrangements of the control devices during these tests are shown in Table 15. The characteristics of each emission control technique learned from these tests are summarized below.

3.2 RESULTS

3.2.1 SO_2 , NO_x , HC and CO Control

3.2.1.1 Lime-impregnated CWM

A homogeneous mixture of lime in CWM was obtained by slowly adding hydrated lime (calcium hydroxide) to a continuously mixed CWM slurry. The lime content in the resulting lime/CWM composition corresponded to a lime to sulfur mole ratio of 2. Two commercially available hydrated limes were evaluated. These limes are known by their commercial names: 'Lynwood' (L), and 'Marble Head' (M). The latter composition is modified through the addition of a surfactant known as 'Lignosol'. Figure 40 compares the baseline (B) SO_2 concentration corresponding to untreated CWM with those corresponding to CWM treated with 'Lynwood' (L) and 'Marble Head' (M) limes. The SO_2 concentrations corresponding to both limes are approximately the same² (after times > 10 min in

Figure 39. Series 2 equipment for evaluating emission control prototypes.

TABLE 15. TEST MATRIX FOR CHARACTERIZING EMISSION CONTROL PROTOTYPES

CONTROL METHOD/ EQUIPMENT	TEST NO.	CYCLONE	CANDLE FILTER	GRANULAR BED	ABSOLUTE FILTER
Cyclone	1	X			X
Cyclone	2	X			X
Cyclone	3	X			X
Cyclone	4	X			X
Cyclone	14	X			X
Cyclone	15	X			X
Cyclone	16	X			X
Cyclone	17	X			X
Candle Filter	6		FD2003		X
Candle Filter	7	X	FD2605		X
Candle Filter	13		Bekipore		X
Candle Filter	23		FD(Incl)		X
Candle Filter	24		Bekipore		X
CWM/Lime	1	X			X
CWM/Lime	2	X			X
CWM/Lime	3	X			X
CWM/Lime	4	X			X
CWM/Lime	9	X			X
CWM/Lime	10	X			X
CWM/Lime	11	X			X
Lime Spray	19				X
Lime Spray	20				X
Lime Spray	21				X
CuO GB	5			X(2")	X
CuO GB	8	X		X(2")	X
CuO GB	12	X		X(6")	X
Inert GB	18	X		X(6")	X
Emissions	22				X

Figure 40), indicating the lime source to be insignificant. The SO_2 removal efficiency with both limes is in the range of 20 to 25%. The low SO_2 removal efficiency for this process can be due to the following limitations:

- (i) low gas residence time in the exhaust duct
- (ii) good initial reaction rate poisoned by CaO sintering due to the high exhaust gas temperature

Figure 40. Effect of lime-containing CWM on SO₂ and NO_x emissions from the GE-TS engine equipped with diamond-tipped fuel injection nozzles.

- (iii) decomposition of the CaSO_3 or CaSO_4 due to the high exhaust gas temperature.
- (iv) lime and ash are combined in the combustion process to produce sintered fly ash particles in which the lime is not easily available for the desulfurization reaction.

The above mechanisms provide fundamental limitations for SO_2 removal by lime-containing CWM which do not appear to be easily overcome.

Figure 41 and 42 show the time variations of the CO and HC concentrations during the tests with the untreated CWM and the CWM treated with lime. There appear to be no variations attributable to lime addition in the HC concentrations. The slight variations in the CO concentrations may be due to slight differences in combustion conditions.

3.2.1.2 Lime Dry Injection

Experiments to investigate the potential for capturing SO_2 with hydrated lime (having a mean size of about 2 μm) dry injected into the diesel exhaust were conducted in a drop-tube furnace. This system simulates the diesel exhaust gas composition and gas temperature, and is equipped with a dry sorbent transport and injection system. The reactor is 3m high and has an inside diameter of 15 cm., and is lined with refractory material in order to maintain isothermal conditions within the reactor. A natural gas-fired burner attached to the reactor bottom supplies the hot combustion products. Suction pyrometers and thermocouples were used to continuously monitor gas temperature. SO_2 was metered into the natural gas flowing to the burner. The lime sorbent was injected into the combustion products with the aid of a 'K-tron' twin screw feeder and a venturi eductor located at the bottom of the reactor. The sorbent was metered through monitoring of the feeder weight loss, and pneumatically transported to the eductor where it is dispersed into the combustion gas. The furnace exhaust was continuously monitored for CO_2 , CO, O_2 , and SO_2 . When the gas temperature is stable, and the baseline gas concentrations are measured, the lime sorbent is injected at a rate corresponding to a dry stoichiometric ratio (moles lime per mole inlet SO_2) of 2. SO_2 removal at different gas residence times was accomplished by sampling the gas delivered to the gas analyzers from different points along the reactor.

Because the diesel engine exhaust operates at an absolute gas pressure of 2.2 atmospheres, the SO_2 concentration in the reactor (which operates at atmospheric pressure) was adjusted to properly simulate the diffusional driving forces present in the engine exhaust. In addition, the potential for CO_2 in the simulated gas stream to compete with SO_2 for the lime was considered. Previous investigation described in the literature (1) no appreciable calcium carbonate formation under the present conditions despite the CO_2 concentration being two orders of magnitude higher than that of the SO_2 . These previous investigations indicate that hydrated lime reacts preferentially with SO_2 to form the sulfite even in the presence of CO_2 .

Figure 41. Effect of lime-containing CWM on CO emissions from GE-TS engine equipped with diamond-tipped fuel injection nozzles.

Figure 42. Effect of lime-containing CWM on HC emissions from GE-TS engine equipped with diamond-tipped fuel injection nozzles.

At a gas residence time of 925 F, the SO_2 capture efficiency was about 40%, and is comparable to the SO_2 removal observed with slaked lime spray injection into the exhaust gas at the same temperature (see below). The gas residence time in the current GE-TS diesel engine exhaust manifold is expected to be about 20 ms. However, this residence time could be increased to 60 ms by modifying the engine exhaust manifold.

SO_2 removal by dry injection appears to be limited by the following processes:

- (a) pore closings within the sorbent by reaction products, and
- (b) pore closings within the sorbent particles by sintering.

Combined SO_2 and NO_x removal by dry injection of alternative sorbents, such as CuO -impregnated alumina, will be investigated in the future.

3.2.1.3 Lime Spray Injection

Table 16 and Figures 43, 44, and 45 summarize the SO_2 removal efficiencies observed in the presence of lime slurry injection into the exhaust gas from the GE-TS single cylinder engine. The lime slurry was injected by means of a two fluid nozzle producing droplets with the mean size 40 micrometer located on the exhaust duct and downstream of the surge tank. Most of the reaction between the CWM exhaust and the lime slurry droplets is expected to take place in the surge tank. The temperature of the exhaust gas leaving the engine was varied by varying the power output of the engine (or the fuel delivery rate together with controlling engine combustion characteristics, such as fuel injection timing). The results in Table 16 and Figures 43, 44, and 45 indicate a peak SO_2 removal efficiency of 48.5% at a exhaust gas temperature of 750 F. Increasing the exhaust gas temperature to 950 F results in a decrease of the SO_2 removal efficiency to 40.6%. The SO_2 removal efficiency at 550 F is the lowest at 26.2%. Table 16 also shows a consistent NO_x removal of about 3% in all three tests. Although this removal is marginally detectable, it may provide useful clues to the NO_x removal process.

The exhaust gas NO_x , CO (carbon monoxide), and HC (hydrocarbons) concentrations (see Figures 46 to 51) show interesting trends with respect to the exhaust gas exit temperature (or engine power output). The NO_x concentration decreases with increasing temperature. The decrease in NO_x concentration when the exhaust gas increases from 550 F to 750 F is small (about 5% change), but the corresponding decrease when the exit temperature increases from 750 to 950 F is sharp (about 40%). At the 950 F exit temperature, the NO_x concentration is 367 ppmvw compared with 646 ppmvw at the 550 F temperature. The lowering of the NO_x appears to be due to the lowering of the peak cycle temperature resulting from fuel injection timing delay. It appears that significant NO_x control could be achieved through control of engine parameters relating to fuel combustion. The HC concentration

Figure 43. Effect on SO_2 and NO_x emissions of slaked lime spray into the 550 F exhaust from the GE-TS research engine equipped with diamond-tipped fuel injection nozzles.

Figure 44. Effect on SO_2 and NO_x emissions of slaked lime spray into the 750 F exhaust from the GE-TS research engine equipped with diamond-tipped fuel injection nozzles.

Figure 45. Effect on SO₂ and NO_x emissions of slaked lime spray into the 950 F exhaust from the GE-TS research engine equipped with diamond-tipped fuel injection nozzles.

TABLE 16. SO₂ REMOVAL EFFICIENCIES AND ENGINE CHARACTERISTICS IN THE PRESENCE OF LIME SPRAY INJECTION INTO THE EXHAUST GAS OF THE GE-TS SINGLE CYLINDER ENGINE

TEST NO:	19	20	21
<u>Engine Parameters:</u>			
Exhaust Gas Exit Temp, F	550	750	950
CWM Feed Rate, lb/min	2.2302	3.4588	4.1382
Pilot Fuel Feed Rate, lb/min	0.1294	0.1150	0.1222
DP across Combustion Air Venturi, in. water	19.76	19.79	19.72
<u>Exhaust Gas Composition:</u>			
Inlet SO ₂ , ppmvw	158	222	197
Outlet SO ₂ , ppmvw	117	114	117
Inlet NO _x , ppmvw	668	634	377
Outlet NO _x , ppmvw	646	617	367
HC, ppmvw	232	152	17
CO, ppmvw	114	231	598
CO ₂ , %(vol)	4.98	7.37	8.56
O ₂ , %(vol)	14.91	12.20	10.71
<u>Emission Control Parameters:</u>			
SO ₂ Removal Efficiency, %	26.2	48.5	40.6
NO _x Removal Efficiency, %	3.3	2.8	2.6
Temperature Range in Sampling Equipment, F	707 to 438	704 to 436	722 to 451

Figure 46. Effect on CO₂ & O₂ emissions of slaked lime spray into the 550 F exhaust from GE-TS engine equipped with diamond-tipped fuel injection nozzles.

Figure 47. Effect on HC & CO emissions of slaked lime spray into the 550 F exhaust from GE-TS engine equipped with diamond-tipped fuel injection nozzles.

Figure 48. Effect on CO₂ & O₂ emissions of slaked lime spray into the 750 F exhaust from GE-TS engine equipped with diamond-tipped fuel injection nozzles.

Figure 49. Effect on HC & CO emissions of slaked lime spray into the 750 F exhaust from GE-TS engine equipped with diamond-tipped fuel injection nozzles.

Figure 50. Effect on CO₂ & O₂ emissions of slaked lime spray into the 950 F exhaust from GE-TS engine equipped with diamond-tipped fuel injection nozzles.

Figure 51. Effect on HC & CO emissions of slaked lime spray into the 950 F exhaust from GE-TS engine equipped with diamond-tipped fuel injection nozzles.

displays a trend similar to that shown by the NO_x concentration. At the 950 F exit temperature, the HC concentration^x is virtually reduced to zero (17 ppmvw) as compared with its 232 ppmvw value at the 550 F temperature, and 152 ppmvw value at the 750 F temperature. On the other hand, the CO concentration increases with increasing exhaust gas exit temperature probably due to partial oxidation of the hydrocarbons and carbonaceous particulate in the exhaust gas. The CO concentration increases by a factor of about 500% as the exhaust gas exit temperature is increased from 550 F to 750 F.

3.2.1.3 Copper Oxide Granular Bed

SO_2 removal in 2-in. and a 6-in. granular beds of commercial grade copper oxide supported on alumina spheres was investigated. The alumina spheres, 100 μm in diameter, were dipped in a 20 to 25% solution of copper nitrate and then baked in an oven at 650 F. At this temperature, the copper nitrate decomposes to the oxide with high surface area.

SO_2 removal efficiency in the copper oxide granular bed was found to be dependent on both gas velocity (or gas residence time in the bed) and temperature. The gas temperature variation during the course of a 60 to 90-minute test run was due to heat exchange between the inlet gas and the granular bed.

The effects of gas velocity and gas temperature on the reactivity of SO_2 in a 2-in. and a 6-in. granular bed are summarized in Table 17 and Figures 52 and 53. In the 6-in. bed at the 40 ft/min gas velocity the SO_2 removal efficiency increased only slightly (from 96 to 98%) despite variation of the gas temperature over the 840 to 920 F range. This fact suggests that in the 6-in bed, at a 30 to 40 ft/min gas velocity, the bed depth (or gas residence) time compensates for temperature induced decreased copper oxide reactivity. Table 17 shows that at nearly the same gas temperatures the SO_2 removal efficiencies with the 2-in. bed are almost in par with those of the 6-in. bed despite a three-fold difference in the gas residence time. This fact suggests that gas temperature determines the reactivity of the copper oxide granular bed to a greater extent than gas residence time in the bed. Better than 90% removal was observed in the 6-in. bed over the 800 to 920 F gas temperature range. A gas temperature of about 780 F gave reasonable removals in both beds.

Table 18 and Figures 54 & 55 summarize the effects of gas temperature and gas velocity on the removal of hydrocarbons by the copper oxide granular bed. The hydrocarbon (HC) removal efficiency is only a weak function of the temperature in the case of the 6-in. bed. This is probably because the bed height (or gas residence time in the bed) compensates for the reduced reactivity at the lower temperatures. Therefore, temperature effects on granular bed are more evident in the 2-in. bed. Lower temperature results in lower HC removal effectiveness. However, the results summarized in Table 17 indicate that lower HC removal at lower temperature can be compensated by increased gas residence time in the bed effected either by increasing the bed height or by decreasing the gas velocity.

Figure 52. SO₂ removal when the exhaust from the CWM-fired GE-TS engine fitted with diamond-tipped fuel nozzles is passed through 2-in. and 6-in. CuO-impregnated granular beds. Figure shows the time variation of the granular bed: (a) outlet SO₂ concentration, (b) superficial velocity, and (c) the outlet gas temperature.

Figure 53. Temperature and velocity and residence time effect of the SO_2 removal across CuO -impregnated granular beds from the exhaust of the CHM-fitted GE-TS research engine fitted with diamond-tipped fuel nozzles.

Figure 54. HC removal when the exhaust from the CHM-fired GE-TS engine fitted with diamond-tipped fuel nozzles is passed through 2-in. and 6-in. CuO-impregnated granular beds. Figure shows the time variation of the granular bed outlet HC concentration.

CuO GRANULAR BED HC REMOVAL

Figure 55. Temperature and velocity and residence time effect of the HC removal across CuO-impregnated granular beds from the exhaust of the CWM-fired GE-TS research engine fitted with diamond-tipped fuel nozzles.

TABLE 17. EFFECT OF GAS VELOCITY AND TEMPERATURE ON SO₂ REMOVAL
IN 2-in. AND 6-in. COPPER OXIDE GRANULAR BED²

BED HEIGHT	GAS VELOCITY	GAS RESIDENCE	GAS TEMP	SO ₂ CONC. AT GB OUTLET	SO ₂ REMOVAL EFFICIENCY
in.	ft/min	msec	F	ppmv	%
2	58	172	880	25	91
	58	172	775	50	83
	77	130	775	95	67
	77	130	730	110	62
	116	86	730	150	48
	116	86	710	160	45
6	40	750	920	5	98
	40	750	840	10	97
	63	476	840	10	97
	63	476	780	30	90
	120	250	780	85	71
	120	250	770	105	64
	35	857	770	10	97
	35	857	795	10	97

TABLE 18. EFFECT OF GAS VELOCITY AND TEMPERATURE ON HC REMOVAL IN 2-in. AND 6-in. COPPER OXIDE GRANULAR BED

BED HEIGHT EFFICIENCY in.	GAS VELOCITY ft/min	GAS RESIDENCE msec	GAS TEMP F	HC CONC. AT GB OUTLET ppmvw	HC REMOVAL %
2	58	172	880	22	89
	58	172	775	44	77
	77	130	775	61	69
	77	130	730	71	63
	116	86	730	94	52
	116	86	710	100	49
6	40	750	920	12	94
	40	750	840	11	94
	63	476	840	11	94
	63	476	780	16	92
	120	250	780	19	90
	120	250	770	19	90
	35	857	770	16	92
	35	857	795	16	92

It is likely that removal of HC in the copper oxide granular bed is also accompanied by CO and CO₂ formation. Thus HC removal may be expected to increase the CO concentration of the gas passing through the granular bed. Oxidation of the carbonaceous particles deposited in the inlet layers of the granular bed is likely to be a another source of CO production in the granular bed. The CO concentration in the gas leaving the granular bed is determined by the kinetics of competing effects of CO production by HC and collected carbonaceous matter, and CO reduction by the granular bed. Initially, in a clean granular bed, the CO removal appears to be substantial in both the 2-in., and the 6-in. beds (see Table 19). However as particles are deposited in the granular bed, the overall CO removal progressively decreases. The CO production reactions appear to dominate at the lower gas temperatures. In the 6-in. bed, at a gas velocity of 60 ft/min and gas temperatures below 800 F, the CO concentration at the granular bed outlet was more than at the inlet (see Figures 56 & 57).

Figure 56. CO removal when the exhaust from the CHM-fired GE-TS engine fitted with diamond-tipped fuel nozzles is passed through 2-in. and 6-in. CuO -impregnated granular beds. Figure shows the time variation of the granular bed outlet CO concentration.

Figure 57. Temperature and velocity and residence time effect of the CO removal across CuO-impregnated granular beds from the exhaust of the CWM-fired GE-TS research engine fitted with diamond-tipped fuel nozzles.

Thus CO production in the granular bed is a concern, which in principle could be alleviated by operating a high efficiency cyclone upstream of the granular bed to reduce the particulate loading to the granular bed.

Future evaluations of the copper oxide process will include comparison of measurements with existing reactivity models and characterizations of the effect of regeneration on copper oxide reactivity. Experiments to characterize simultaneous SO₂ and NO removal in the presence of NH₃ injection will also be investigated.

TABLE 19. EFFECT OF GAS VELOCITY AND TEMPERATURE ON CO REMOVAL IN 2-in. AND 6-in. COPPER OXIDE GRANULAR BED

BED HEIGHT	GAS VELOCITY	GAS RESIDENCE	GAS TEMP	CO CONC. AT GB OUTLET	SO ₂ REMOVAL EFFICIENCY
in.	ft/min	msec	F	ppmvw	%
2	58	172	880	57	73
	58	172	775	134	36
	77	130	775	134	36
	77	130	730	198	5
	116	86	730	198	5
	116	86	710	201	4
6	40	750	920	28	87
	40	750	840	56	74
	63	476	840	83	60
	63	476	795	175	16

3.2.2 Particulate Removal

3.2.2.1 Cyclone

A 2-in. diameter cyclone when operated at an inlet gas flow rate of 2 acfm showed a particulate collection efficiency (by mass) of 75% which was consistent with design expectations. Increasing the cyclone inlet flow in the range from 2 to as high as 9 acfm showed a trend of decreasing mass efficiency with respect to increasing inlet gas flow rate (see Figure 58), and is opposite to the trend expected on the basis of the GE design experience.

GE-TS SINGLE CYLINDER ENGINE TESTS

Figure 58. Cyclone mass efficiency dependence on cyclone inlet gas flow rate (GE-TS research engine with diamond-tipped nozzles).

As noted previously the CWM exhaust particulate distribution comprises two log-normal components attributable to a nearly completely burned ash component, and an incompletely burned carbonaceous component. In the case of the particulate formed with the new diamond-tipped fuel injection nozzles, the former distribution is centered approximately at 3 micrometer while the latter distribution is centered at around 11 micrometer. The log-normal standard deviations of both distributions are about 1.3. The inlet size distribution shown in Figure 59 for the 2 acfm-Test was inferred from the measured mass loading and size distributions of the cyclone hopper and cyclone exhaust (absolute filter catch) particulate. In the 2 acfm test (showing 75% mass efficiency), none of the particulate at the outlet of the cyclone was above 5 micrometer (see Figure 59). The cyclone was thus an effective collector of the incompletely burned particulate component in the CWM engine exhaust. The size distributions characterizing cyclone performance at the higher gas flow rates are summarized in Figures 60, 61, and 62. The inlet size distributions for all the test runs are plotted together in Figure 63. The same figures, fitted to log-normal distributions, were presented in earlier in Figures 34 to 38). The relative mass fractions of the ash and carbonaceous components appear to vary from test to test indicating variations in combustion conditions. Figure 64 shows the fractional cyclone efficiencies for different cyclone inlet gas flow rates. Increasing cyclone inlet gas flow rate appears to result in increasing cut-off diameter (the diameter at which the cyclone efficiency is 50%) rather than the expected trend of decreasing cut-off diameter with increasing gas flow rate. This observed trend for the cyclone cut-off diameters is also consistent with the observed trend of decreasing cyclone efficiency with increasing gas flow rate. It is likely that small-scale fabrication effects and excessive particulate reentrainment are responsible for the anomalous variation of efficiency and cut-off diameter with respect to inlet gas flow rate. The above observations point to the need for cyclone evaluations on larger prototypes for obtaining meaningful cyclone scale-up data.

The pressure drop across the cyclone varied as the square of the inlet gas flow rate (see Figure 65). This observed trend is consistent with observations on large cyclones but does not guarantee high particulate removal efficiency.

3.2.2.2 Candle Filter

Three filter media made by sintering metal fibers in metal scrims were evaluated. Two of the filter media, one of stainless steel and the other of Inconel were obtained from Fluid Dynamics. The third filter, also of Inconel, was obtained from Bekipor. These filter elements are practically absolute filters showing no detectable particulate penetration at air-to-cloth ratios (A/C) of 3, 5, and 10 ft/min. Two tests (Test Nos. 6 and 13) were initially performed. In Test No.6, the Fluid Dynamics stainless steel medium (FD2003 rated at 1 μ m pore size) in the form of a 2-in. diameter X 24-in. long candle filter, and without any precoat treatment, was exposed to varying flow rates of the exhaust gas from the CWM-fired single

GE-TS SINGLE CYLINDER CWM ENGINE TESTS

Figure 59. Measured cumulative (% less than) size distributions characteristic of cyclone operation at 2.2 acfm.

GE-TS SINGLE CYLINDER CWM ENGINE TESTS

Figure 60. Measured cumulative (% less than) size distributions characteristic of cyclone operation at 4.8 acfm.

GE-TS SINGLE CYLINDER CWM ENGINE TESTS

Figure 61. Measured cumulative (% less than) size distributions characteristic of cyclone operation at 7.4 acfm.

GE-TS SINGLE CYLINDER CWM ENGINE TESTS

Figure 62. Measured cumulative (% less than) size distributions characteristic of cyclone operation at 9 acfm.

GE-TS SINGLE CYLINDER CWM ENGINE TESTS

Figure 63. Cyclone inlet size distributions inferred from the size distributions shown in Figures 59 to 62 (also see Figures 34 to 38).

GE-TS SINGLE CYLINDER CWM ENGINE TESTS

Figure 64. Cyclone fractional (grade) efficiency curves.

Figure 65. Cyclone pressure drop dependence on cyclone inlet gas flow rate.

cylinder research engine. This element showed rates of change of filter pressure drop with respect to time ($d[DP]/dt$) of 0.55, 1.22, and 2.57 in. water per min at A/C ratios of 2.6, 4.5, and 9.3 ft/min (also see Table 20 and Figure 66). The rate of increase of the filter pressure drop with respect to time is sufficiently high at the higher A/C range to require frequent cleaning. The Fluid Dynamics filter was subject to three, off-line, reverse pulse jets following cleaning periods at the 9.3 ft/min A/C. As seen in Figure 66, none of these pulses resulted in a reduction of the filter pressure-drop. Figure 67 and Table 20 summarize similar data obtained with a different stainless steel medium from Fluid Dynamics (FD2605). The filter from this material too was subject to multiple, off-line, pulse-jet cleanings, which as in the case of the previous Fluid Dynamics material, did not result in appreciable recovery in the pressure drop across the filter. This non-cleanability, as measured by the impact of the pulse-jet on the DP vs. time development (Figures 66 and 67) and by the increasing $D[DP]/Dt$ and DP(minimum) with cycle number (Figures 69 and 70), may be ascribed to blinding of the stainless steel medium either from chemical attack by the SO_2 containing exhaust gas, or to the lack of a precoat material. Both these concerns were alleviated in a subsequent test (Test No.13) with

TABLE 20. FILTRATION CHARACTERISTICS OF UNTREATED AND LIMESTONE PRECOATED METAL FILTER MEDIA

MEDIUM	A/C ft/min	CYCLE #	$D[DP]/Dt$ in/min	DPmin in.H ₂ O
Fluid Dynamics	2.63		0.34	
FD2003	4.54		0.89	
(stainless steel,	9.33	1	3.63	79.8
without precoat)	9.33	2	3.04	95.5
TEST NO. 6	9.33	3	3.29	112.1
	9.33	4	4.15	119.9
Fluid Dynamics	3.46		0.56	
FD2605	6.13	1	1.19	19.1
(stainless steel,	6.16	2	1.69	28.9
without precoat)	6.16	3	2.14	19.3
TEST NO. 7	12.86		2.91	

a candle filter of the Bekipor medium. This medium, of Inconel and rated to be impervious to chemical attack, and was precoatd with limestone prior to testing. The time development of the pressure drop across the Bekipore filter is shown in Figure 68. The rates of increase of pressure drop across the Bekipore candle filter, $D[DP]/Dt$, are shown in Table 20 and plotted in Figures 69 and 70. Off-line, high pressure pulse-jet blow back was found to be effective in removing the filter cake from the Bekipore medium. The $D[DP]/Dt$ slopes for the Bekipore filter were lower than for the Fluid Dynamics media possibly indicating the lower extent of blinding in the Bekipore filter. It is likely that this lower blinding extent for

Figure 66. Time variation of: (a) the pressure drop, and (b) the A/C during filtration of CWM-derived diesel exhaust through candle filter of stainless steel Fluid Dynamics FD2003 medium without precoat.

Figure 67. Time variation of: (a) the pressure drop, and (b) the A/C during filtration of CWM-derived diesel exhaust through candle filter of stainless steel Fluid Dynamics FD2605 medium without precoat.

Figure 68. Time variation of: (a) the pressure drop, and (b) the A/C during filtration of CWM-derived diesel exhaust through candle filter of Inconel[®] Bekipore medium with limestone precoat.

Figure 69. Comparison of filtration characteristics of stainless steel Fluid Dynamics media without precoat and Inconel^R Bekipore medium. Figure shows cleaning cycle variation of the rate of change of filter pressure drop ($D[DP]/Dt$).

Figure 70. Comparison of filtration characteristics of stainless steel Fluid Dynamics media without precoat and Inconel^R Bekipore medium. Figure shows cleaning cycle variation of the extrapolated DP(minimum).

the Bekipore filter resulted from the use of precoat. The cleanability of the Bekipore medium is significant since it demonstrates the applicability of a pulse-jet-cleaned filter for particulate control of CWM exhaust.

Filtration of CWM exhaust particulate with precoated metal candle filters was investigated in two additional tests (Test Nos. 23 and 24). Lime was used as a precoat material in order to assess any additional benefits from SO_2 and NO_x removal. Again, candle filters of sintered metal felts from Fluid Dynamics and Bekipore were evaluated. In these two tests both filter elements were of Inconel. Figures 71 and 72 show the time developments of the pressure drops across the filters, while Table 21 and Figures 73 and 74 show the variations of the slopes, $D[DP]/Dt$ and the extrapolated minimum value of DP with cleaning cycle. The slopes of $D[DP]/Dt$ for the Bekipore material are higher than for the Fluid Dynamics material. Also, while the slope increases with every cleaning cycle for the Bekipore filter, it appears to stabilize after about 5 cycles in the Fluid Dynamics material. The slope for the first cycle is the lowest for both filter media. However, in the case of the FD material, the slopes for three subsequent cycles (cycles 2, 3, and 4) remain the same. In the case of the Bekipore material, the slopes continue to increase with every cycle. The increasing slope in the case of the Bekipore material is probably indicative of slow and continuous blinding of this filter material even with the lime precoat. It appears that the lime precoat on the Bekipore material is easily removed, and is effective only during the first cycle. Earlier tests, described above, indicated stable $D[DP]/Dt$ values for the Bekipore with the limestone precoat. It appears that the limestone precoat is not as easily removed as the lime precoat on the Bekipore filter. In comparison, the lime precoated Fluid Dynamics candle filter appears to demonstrate stable operation. Inspection of this candle filter indicated the presence of an easily removable cake on the filter at the end of the 9 cycles. This observation indicates that the off-line reverse pulse-jet cleaning (at 60 psia in 30 psia gas) was not completely effective in cleaning the filter. The lower $d[DP]/dt$ slopes and higher baseline (minimum) pressure for this filter material are consistent with this conclusion. Fluid Dynamics engineers have recommended pulsing at a higher pressure. Higher pressure pulse-jet cleaning will be applied in future tests.

3.2.2.3 Granular Bed

Particulate collection in the previously-described copper oxide-containing granular bed media as well as an inert granular bed, were also studied. The inert bed comprised 1.5 in. alumina spheres with diameters in the range 20 to 40 mm followed by 3 layers of # 16, #10, and #8 ball bearings, each of height 1.5 in. The granular beds were found to be effective particulate collectors downstream of the cyclone. The particulate collection efficiency in the 6-in. bed was found to be higher than 90%. The effectiveness of the granular bed as a downstream device for a cyclone also relates to the rate of increase of pressure drop. Typically, the granular bed pressure drop increase is one-tenth of that across a fabric filter at design flow

Figure 71. Time variation of: (a) the pressure drop, and (b) the A/C during filtration of CWM-derived diesel exhaust through candle filter of Inconel[®] Fluid Dynamics medium with lime precoat.

Figure 72. Time variation of: (a) the pressure drop, and (b) the A/C during filtration of CWM-derived diesel exhaust through candle filter of Incone^l Bekipore medium with lime precoat.

Figure 73. Comparison of filtration characteristics of lime precoated Inconel[®] Fluid Dynamics and Bekipore media. Figure shows cleaning cycle variation of the rate of change of filter pressure drop ($D[DP]/Dt$).

Figure 74. Comparison of filtration characteristics of lime precoated Inconel[®] Fluid Dynamics and Bekipore media. Figure shows cleaning cycle variation of the extrapolated $DP(\text{minimum})$.

TABLE 21. FILTRATION CHARACTERISTICS OF LIME PRECOATED METAL FILTER MEDIA

MEDIUM	A/C ft/min	CYCLE #	D[DP]/Dt in/min	DPmin in.H2O
Fluid Dynamics	7.11	1	0.66	14.8
FD2003	8.30	2	1.38	6.5
(Inconel,	8.30	3	1.27	12.0
lime precoat)	8.30	4	1.41	18.9
TEST NO. 23	8.30	5	1.60	23.5
	8.30	6	2.11	24.8
	7.11	7	1.22	23.2
	7.11	8	2.03	21.2
	7.11	9	1.46	23.4
Bekipore	7.07	1	1.10	0.0
(Inconel,	8.04	2	1.98	1.3
lime precoat)	8.04	3	2.93	2.4
TEST NO. 24	8.04	4	2.65	12.5
	8.88	5	3.34	15.5
	8.88	6	3.73	15.2
	7.77	7	4.15	14.6

rates. This advantage is offset by the non-cleanability of the granular bed and the increasing $D[DP]/Dt$ values with increasing collection time in the fixed bed granular bed due to particulate accumulation. The rate of increase of granular bed pressure drop will decrease with increasing cyclone efficiency. On the other hand, fabric filters are not recommended for use as a downstream device for a high efficiency cyclone. The effect of particulate accumulation on the granular bed pressure drop may be reconciled in practice only if the upstream cyclone has a better than 90% mass efficiency, and allows a low particulate loading at the granular bed inlet. Table 22 summarizes the $D[DP]/Dt$ rates for the 4 granular beds tested. Figures 75 and 76 displays the nearly linear relationship between $D[DP]/Dt$ and the average gas velocity through the granular bed (Figure 75 presents the $D[DP]/Dt$ data for the CuO granular bed, while Figure 76 displays the rate of pressure drop increase data for all the granular beds. The rate at which $D[DP]/Dt$ increases with increasing velocity (i.e. the slope of $D[DP]/Dt$ vs velocity) is higher for the case when there is no upstream cyclone (see Figures 77(a), 77(b), and 77(c)). As discussed above, this is to be expected from the higher particulate concentration at the granular bed inlet in the absence of the cyclone. The variation of $D[DP]/Dt$ with velocity for the 2 in. and 6 in. CuO-containing granular beds appear to be nearly the same. The 6-in. bed with more void volume would be expected to accommodate more particulate matter within in it and hence have a lower rate of pressure drop increase in time. The nearly equal pressure variations for the 2 in. and 6 in. beds indicates that the particulate capture occurs at least within the first 2 in. of the granular beds. The inert bed shows a higher $D[DP]/Dt$ vs. velocity slope than the 3 granular beds contain CuO.

Figure 75. Velocity dependence of the rate of pressure drop increase ($D[DP]/Dt$) across the CuO -containing granular bed.

Figure 76 Velocity dependence of the rate of pressure drop increase ($D[DP]/Dt$) across the inert and CuO -containing granular bed.

GRANULAR BED DP, in. water

AVG. GRANULAR BED VELOCITY, ft/min

Figure 77(a). Time dependence of the pressure drop across the 2-in. CuO-containing granular bed without upstream cyclone.

Figure 77(b). Time dependence of the pressure drop across the 2-in. CuO-containing granular bed with upstream cyclone.

Figure 77(c). Time dependence of the pressure drop across the 6-in. CuO-containing granular bed with upstream cyclone.

This anomalously high pressure drop variation is due to the high particulate loading resulting from limestone being blended into the CWM used in this test.

Future studies will focus on characterizing particulate collection in a granular bed when used downstream of a high efficiency cyclone.

TABLE 22. RATE OF CHANGE OF PRESSURE DROP ACROSS GRANULAR BEDS

TEST NO	TEST DESCRIPTION	VELOCITY ft/min	D[DP]/Dt in./min
5	2 in. CuO GB + THIMBLE	54	0.075
		66	0.220
		95	0.460
8	Cyclone + 2 in. CuO GB + Thimble	57	0.040
		76	0.155
		118	0.347
12	Cyclone + 6 in. CuO GB + Thimble	42	-0.041
		64	0.118
		120	0.394
		38	0.122
18	Cyclone + 6 in. inert GB + Thimble	34	0.616
		60	0.466
		134	1.967

3.2.2.4 Thimble

The pressure drop across the absolute filter in the Series 2 equipment is useful for assessing the extent of particulate penetration through the collection devices being evaluated, as well as for assessing the effect of fine particulate on filtration characteristics. Table 23 show that near blinding of the absolute filter results when the diesel exhaust is passed directly through the absolute filter without flow through a particulate precollector (Tests 9, 10 & 11). For these tests, the pressure drop across the absolute filter (thimble) is greater than 10 in./min, indicative of filter surface area limitation through blinding. The blinding extent in Test 11 is the worst observed, showing a pressure increase rate higher than 115 in./min. Even in the presence of lime spray injection (Tests 19, 20, and 21), the D[DP]/Dt values are in the range of 0.9 to 2 in./min at an A/C around 4.5 ft/min. The rate of pressure drop increase in Test 22, corresponding to no precollector and no lime spray injection) is more consistent with those in Tests 19 to 21 rather than with those in Tests 9 to 11. It is likely that the smaller extent of blinding in this test, as compared with Tests 9 to 11, is due to a lower fraction of fines generated in the engine during this test. When a the cyclone is included as a precollector (Tests 1 to 2 and 14 to 17), the 2 in./min D[DP]/DT value is reached at higher A/C values in the range of 6

to 8 ft/min. Using the granular bed as the precollector leads to even smaller $D[DP]/Dt$ values for the thimble indicating even higher particulate collection efficiencies in the granular bed. In this case, the 2 in./min $D[DP]/Dt$ value is reached at A/C values in the range of 8 to 16 ft/min. As expected, the metal filter media yield the best particulate collection efficiencies, and consequently the lowest thimble pressure drop increases. The Fluid Dynamics elements gave the highest observed particulate collection efficiencies. When candle filters of these elements are used as precollectors, the thimble pressure drop increase is less than 0.06 in./min at A/C of 14 ft/min. The collection efficiency of the Bekipore medium, known to have a more open pore structure than the Fluid Dynamics media, is lower, and slightly better than that of the granular bed. The lower $D[DP]/Dt$ values observed for the Bekipore material is consistent with the penetration of fines through this medium.

Charts showing the time variation of the thimble pressure drop and A/C during all the tests are assembled in Appendix D.

Summary -

The main points of the characterizations of prototype devices for the control of particulate and gaseous emissions are as follows:

1. The copper oxide, fixed granular bed is a viable device for both SO_2 control and for particulate control if used downstream of a high efficiency cyclone. In the presence of NH_3 injection, this granular bed may also potentially control NO_x emissions.
2. Lime containing CWM was not effective (20-25% removal) in removing SO_2 when directly injected in the diesel engine.
3. Injection of dry hydrated lime into the diesel exhaust showed a maximum SO_2 removal efficiency of about 40% at exhaust temperatures in the neighborhood of $750^\circ C$ and at a lime dry stoichiometric ratio (moles lime to moles SO_2 in the exhaust gas) of 2.
4. Injection of a lime spray (with the aid of a two-fluid nozzle) into the diesel exhaust showed a maximum SO_2 removal efficiency of about 50% at exhaust temperatures in the neighborhood of $750^\circ C$ and also at a lime dry stoichiometric ratio of 2.

TABLE 23. RATES OF CHANGE OF PRESSURE DROP ACROSS THIMBLE

TEST NO	TEST DESCRIPTION	A/C ft/min	D[DP]/Dt "H2O/min
1	CYCLONE + TH (BASELINE)	6.19	1.828
2	CYCLONE + TH (CWM/LIME)	8.29	2.314
14	CYCLONE + TH	3.53	0.531
15	CYCLONE + TH	14.58	11.812
16	CYCLONE + TH	7.70	2.366
17	CYCLONE + TH	11.83	11.830
5	2" CuO GB + THIMBLE	7.65 9.48 13.66	1.747 1.011 0.460
8	CYC + 2" CuO + TH	6.92 10.01 16.16	1.915 2.547 2.119
12	CYC + 6" CuO + TH	4.98 8.42 16.73 5.10	0.539 1.359 2.530 -0.029
18	INERT GB + CYC + TH	4.81 8.37 18.80	0.442 0.281 0.498
7	FD2605 CF + TH	3.87 6.83 14.31	0.022 0.000 0.055
13	BEKIPORE CF + TH	4.05 7.90 11.48 11.52 11.67	0.121 0.370 1.263 0.698 0.743
23	FD CF (LIME PRECOAT) + THIMBLE	6.30 7.40 6.50	0.000 0.015 0.008
24	BEKIPORE CF(LIME PRECOAT) + THIMBLE	7.90 8.40 8.40 8.40 9.60 9.60 10.80	1.406 0.381 0.445 1.095 1.140 1.040 0.904

TABLE 23. RATES OF CHANGE OF PRESSURE DROP ACROSS THIMBLE (CONTINUED...)

TEST NO	TEST DESCRIPTION	A/C ft/min	D[DP]/Dt "H ₂ O/min
9	THIMBLE ONLY (BASELINE)	4.47	11.228
10	TH ONLY (CWM/LIME-L)	4.51	30.752
11	TH ONLY (CWM/LIME-M)	2.18	116.460
19	TH ONLY (LIME SPRAY/550F)	4.43 4.52	1.356 0.891
20	TH ONLY (LIME SPRAY/750F)	4.42 4.51	1.227 1.426
21	TH ONLY (LIME SPRAY/950F)	4.57 4.62	2.010 1.680
22	TH ONLY (DUAL GAS SAMPLE)	4.04	1.325

5. A pulse-jet cleaned particulate filter of sintered Inconel fibers is a viable particulate control device. However, exposure of filters of these media directly to the exhaust gas may lead to media blinding. Filter cleanability and degradation due to blinding are ensured when a limestone precoat is used. Filtration characterization in the presence of continuous or periodic precoat injection needs to be evaluated. The effectiveness of different precoat materials also need to be established. SO₂ control at the 50% level can be effected with this² device by upstream lime spray injection. SO₂ control at the 90% level appears to be achievable with this device by upstream injection of CuO or CuO-containing alumina powder.
6. The cyclone appears to be a viable upstream particulate control device for use with a fixed granular bed. However, high efficiency, large-scale cyclone designs need to be tested.

CHAPTER 4 - RECOMMENDATIONS

4.0 SERIES 2 TEST PLAN

Single candle filter elements of the following 9 filter media shall be characterized with respect to cleanability and coefficient of specific resistance, with and without pre-coat:

- 1. Woven ceramic fabric from 3M (with limestone precoat - TEST 1)*
- 2. Felt of sintered stainless steel fibers from Fluid Dynamics (with limestone precoat - TEST 2)*
- 3. Felt of Inconel fibers from Fluid Dynamics (without precoat - TEST 3, and with copper oxide precoat - TEST 4)*
- 4. Felt of sintered stainless steel fibers (Type 1) from Michigan Dynamics (with zinc oxide precoat - TEST 5)*
- 5. Felt of sintered stainless steel fibers (Type 2) from Michigan Dynamics (with limestone precoat - TEST 6)*
- 6. Felt of sintered stainless steel fibers from Bekipor (with limestone precoat - TEST 7)*
- 7. Felt of Inconel fibers from Bekipor (with copper oxide precoat - TEST 8)*
- 8. Woven Inconel fabric from Bekipor (with zinc ferrite precoat - TEST 9)*
- 9. Sintered metal medium from Mott (with magnesium oxide precoat - TEST 10)*
- 10. Oven Inconel fabric from Bekipor (with zinc ferrite precoat - TEST 9)*

Each of the above filter media shall be characterized for the following conditions:

- 1. Pre-coat material: powdered limestone, copper oxide, zinc oxide, magnesium oxide and zinc ferrite (nominally 90% -325 Mesh)*

2. The pre-coat material shall be applied off-line prior to exposing the media to CWM exhaust. For each pre-coat condition (no pre-coat, and pre-coat of limestone or copper oxide), the A/C shall be first maintained at 4 ft/min until a pressure drop of 15 in. water across the filter is reached. At this point, the filter shall be subject to an off-line, reverse pulse-jet. Following the cleaning, the gas flow through the filter will be resumed at 4 ft/min for a sufficiently long period to allow recording of the filter pressure drop following cleaning. Soon after this short period, the A/C shall be increased to 7 ft/min, and the procedure of collection and cleaning observed at 4 ft/min, repeated. Following cleaning of the filter cake collected at 7 ft/min, the collection and cleaning procedure shall be repeated for a 10 ft/min A/C.

The following are GEESI action items to support Series 2 testing:

1. Procure 2 Inconel candle filters from Fluid Dynamics
2. Procure copper oxide powder for use as filter pre-coat material
3. Modify the Series 2 system to operate at ambient pressure,
4. Install and test pre-coating system, and
5. Install Malvern Particle Size Analyzer in GE-TS Engine Laboratory.

4.1 SERIES 3 ACTION PLAN

4.1.1 Objective

Series 3 objective is to demonstrate emission control on a scale which treats a substantial portion (about 50%) of the CWM exhaust gas released from the GE-TS single cylinder research engine.

The maximum exhaust gas flow rate expected from this engine upstream of the turbo-charger (corresponding to a notch setting of 8) is 742.5 acfm at an absolute pressure of 35.9 psia (21.2 psig) and a temperature of 880 F. Downstream of the turbocharger, the expected gas flow rate is 1748 acfm at atmospheric pressure (14.7 psia) and a temperature of 700-800 F. The overall plan to achieve the Series 3 objective is to first test cold-flow models of promising emission control designs, and select those designs showing the best projected (scaled-up) results under CWM engine downstream turbocharger conditions for implementation on the GE-TS research engine. The design flow rate for the cold-flow model has been chosen as 500 acfm to be compatible with an existing pulse-jet fabric filter. Since velocity is a primary scale-up criterion for emission control equipment, the 500

cfm design flow rate is also expected to translate to a 500 cfm design flow rate under the atmospheric pressure and high temperature conditions in the CWM exhaust downstream of the turbocharger. Scaling rules may then be used to correct the cold-flow design guidelines for application at turbocharger outlet conditions (14.7 psig and 700-800 F temperature).

4.1.2 Cyclone

The two emission control alternatives shown to be viable by Series 2 testing shall be cold-flow tested. These are : (i) the cyclone-copper oxide granular bed combination, and (ii) fabric filter with upstream reagent injection. Several promising cyclone designs offered by the GEESI Cyclone Group will be subject to qualification under cold-flow conditions. Design work on these cold-flow model cyclones has already begun. Since only sheet metal fabrication of these cold flow model cyclones is necessary, local sheet metal shops will be contacted through Purchasing to initiate cold-flow model cyclone procurement, as soon as the designs are available from the Cyclone Group. The cold-flow model testing of the cyclones will determine the particulate collection efficiencies of each cyclone at 3 different gas flow rates (design, minimum, and maximum).

4.1.3 Granular Bed

Nearly full-scale, sheet metal or plastic, cold-flow models of the granular bed and envelope filter shall also be tested for determining flow distributions, pressure drop characteristics, and in the case of the filter, filter cake cleanability.

Figure 78 shows a sketch of the granular bed design to be cold-flow tested. It consists of two parallel 6-in. deep beds each having its own outlet channel but connected to a common inlet channel. Each granular bed channel will have a 2 ft X 2 ft face inlet area, and will have a design gas velocity of 60 ft/min. The 6-in. bed depth was determined in the Series 2 studies to remove SO₂ with an efficiency higher than 90%. The cold-flow model testing will determine:

- (i) Time variation of the pressure drop across the granular bed
- (ii) Particulate collection efficiency using test particulate resembling CWM exhaust particulate (such as copier toner)
- (iii) Inlet gas flow velocity distribution

at three flows (design flow, minimum flow, and maximum flow).

4.1.4 Envelope Filter

Figure 79 shows a sketch of the envelope filter to be cold-flow modeled. This filter has 8 parallel 2 ft X 2 ft filtration surfaces configured so that alternate channels serve as inlet and outlet manifolds. The 64 ft²

area of the arrangement at a design A/C of 8 ft/min will allow a design gas flow rate of 500 cfm. The cold-flow model testing of the envelope filter will determine:

- (i) Time variation of the pressure drop across the filter
- (ii) Particulate collection efficiency using test particulate resembling CWM exhaust particulate (such as copier toner)
- (iii) Inlet gas flow velocity distribution
- (iv) cleanability of filter cake as measure by the rate of change of the filter pressure drop following cleaning.

At three flows (design flow, minimum flow, and maximum flow).

The cyclone, granular bed, and envelope filter cold-flow modeling, and the designing of these devices for application in the GE-TS single cylinder engine will proceed concurrently. Design improvements suggested by the cold-flow modeling effort will be incorporated on the final design of the devices for the GE-TS single cylinder engine.

APPENDIX A

CWM DIESEL LOCOMOTIVE CONCEPTUAL PARTICULATE COLLECTOR COSTS

Budgetary costs associated with conceptual design of particulate collectors for a full-scale CWM-fired diesel locomotive have been prepared. The following designs were considered: (i) high temperature, low pressure fabric filter, (ii) medium temperature, low pressure fabric filter (iii) conventional low pressure fabric filter, (iv) granular bed without SO₂/NO_x control, (v) granular bed with SO₂/NO_x control, and (vi) conventional fabric filter for use in cleaning locomotive ash hoppers during locomotive stops in railway stations. Two bag sizes were considered for the fabric filters. The bag layout and conceptual baghouse design are shown in Figure A-1

The budgetary costs are summarized below:

TABLE A-1. HIGH TEMPERATURE FILTER BUDGETARY COST

ITEM	QUANTITY	UNIT \$	TOTAL \$
1..Instrumentation & Controls	1	2,214.00	2,214.00
2. Louvres	4	1,600.00	6,400.00
3. Woven SS-316 Bags, 6"X6.5'	160	307.40	49,184.00
4. Cages, 20SWG with Venturi	160	15.00	2,400.00
5. SS Casing with Access Doors	1	36,028.00	36,028.00
6. Insulation & Lagging	1	11,010.00	11,010.00
7. Freight	1	2,744.00	2,744.00
8. Engineering & In-House Hours	50	42.00	2,100.00
GRAND TOTAL			112,080.00

TABLE A-2. MEDIUM-TEMPERATURE FABRIC FILTER BUDGETARY COST

ITEM	QUANTITY	UNIT \$	TOTAL \$
1. Instrumentation & Controls	1	2,214.00	2,214.00
2. Louvres	4	800.00	3,200.00
3. Woven SS-316 Bags, 6"X6.5'	160	248.00	39,680.00
4. Cages, 20SWG with Venturi	160	15.00	2,400.00
5. MS Casing with Access Doors	1	18,014.00	18,014.00
6. Insulation & Lagging	1	5,505.00	5,505.00
7. Freight	1	2,744.00	2,744.00
8. Engineering & In-House Hours	50	42.00	2,100.00
GRAND TOTAL			75,857.00

TABLE A-3. CONVENTIONAL FABRIC FILTER BUDGETARY COST

ITEM	QUANTITY	UNIT \$	TOTAL \$
1. Instrumentation & Controls	1	2,214.00	2,214.00
2. Louvres	4	800.00	3,200.00
3. Woven SS-316 Bags, 4"X6.5'	308	50.20	15,461.60
4. Cages, 20SWG with Venturi	308	15.00	4,620.00
5. MS Casing with Access Doors	1	18,612.00	18,612.00
6. Insulation & Lagging	1	5,505.00	5,505.00
7. Freight	1	2,744.00	2,744.00
8. Engineering & In-House Hours	50	42.00	2,100.00
GRAND TOTAL			54,456.60

TABLE A-4. GRANULAR BED DESIGN PARAMETERS

VARIABLE	UNIT	VALUE
1. Gas Flow Rate	acfm	21,600
2. Gas Velocity Through Bed	ft/s	1.50
3. Insulation Surface	sq ft	528
4. Vessel Weight	lb	6,452
5. Granular Material Weight	lb	16,518

TABLE A-5. GRANULAR BED BUDGETARY COST

ITEM	QUANTITY	COST \$
1. Vessel	1	22,875.53
2. Internals (Louvers, Perf. Plates)	1 Lot	8,894.12
3. Insulation	1 Lot	7,038.62
4. Granular Bed Media, @0.50/lb	16,518 lb	8,258.82
SUB-TOTAL.		47,067.10
5. Contingency (20%)		9,413.42
TOTAL.		56,480.51

OPTION for SO₂ Adsorbent for Granular bed Material:

Add:

6. Bed Material @ \$1.50/lb Added Cost	24,776.47
7. Additional Contingency (20% of Item 6)	4,955.29
TOTAL ADDITIONAL COST FOR SO ₂ REMOVAL OPTION.....	29,731.76
GRAND TOTAL WITH SO ₂ REMOVAL OPTION	86,212.28

The above costs are scaled-up for a gas flow rate of 21,600 cfm from Eli Gal's 4/11/88 cost projection for a 17,000 cfm system.

TABLE A-6. COST ESTIMATE FOR LOCOMOTIVE STATION-LOCATED FABRIC FILTER
FOR REMOVAL OF DUST FROM CWM DIESEL LOCOMOTIVE HOPPERS

=====		
ITEM	QUANTITY	UNIT \$

Fabric Filter for Removal of 1000 lb ash in 60 min at an average gas flow rate of 6000 cfm, and dust concentration of 19 gr/acf, and having a power rating of 40HP. Filter equipped with variable frequency motor & drive, on-line pulse jet, and truck loading stand. Nominal fabric filter size = 12' X 9'.	1	32,604.00
Cost estimate based on list price of standard fabric filter product from: Kreamer Tools 75 Devon Rd., Brampton, Ontario CANADA L6T 5A4.		
Telephone: (416)-458-0400		
=====		

APPENDIX B

ANALYSES OF ENGINE DEPOSITS FOLLOWING TESTS WITH LIME CONTAINING CWM

Between 6/16/89 and 7/19/89 a series of 18 tests was performed to characterize cyclone, fabric filter, and copper oxide granular bed prototypes with respect to particulate and SO₂ control. Five of these tests sought to measure the SO₂ removal effectiveness of Ca-based reagents mixed into the CWM (Coal-Water²Mixture) fuel. The results from these 18 tests have been reported in previous Monthly Reports.

At the end of these 18 tests, the GE-TS single-cylinder research engine was dismantled for maintenance. Table 29 reports the chemical analyses of the large deposits of yellowish particulate matter was found around the engine valves. These deposits appear to originate from the calcium-containing reagents added to the CWM fuel during the previous emission control tests. As these deposits are continuously exposed to the exhaust gas at temperatures exceeding 1000 F, it is likely that the lime deposits are partly converted to calcium sulfate and calcium carbonate by

TABLE B-1. CHEMICAL ANALYSES OF GE-TS SINGLE CYLINDER
RESEARCH ENGINE DEPOSITS (7/89)

SAMPLE DESCRIPTION	QTY. SAMPLE RECEIVED g	Ca ⁺⁺ (%)	LOSS ON IGNITION (%)	ACID INSOL- UBLE (%)	CaSO ₄ .2H ₂ O (%)
TR4731 (PISTON CROWN)	0.8562	7.4	71.95	N/A	N/A
TR4731 (L)INLET VALVE FACE	8.2870	36.7	22.69	0.76	37.34
TR4731 (R)INLET VALVE FACE	1.6362	37.1	27.36	1.62	29.28
TR4731 (L)EXH.VALVE STEM	4.0823	42.7	30.87	0.19	12.63
TR4731 (R)EXH.VALVE STEM	2.2587	42.0	32.62	0.20	9.58
TR4731 (L)EXH.VALVE	4.3331	35.0	22.63	4.00	42.72
TR4731 (R)EXH. VALVE	8.0034	35.0	23.28	3.67	35.75

reaction with the exhaust gas CO_2 and SO_2 . Some calcium oxide may also be expected from the calcination (decomposition) of the carbonate. The results shown in Table B-1 may be further analyzed to obtain the ash, calcium carbonate, and calcium sulfate, and calcium oxide components as follows:

- (a) assume that the AI (acid insoluble) component only includes carbon (C)
- (b) assume that the LOI (loss on ignition at 800 C) component includes loss of carbon, loss of CO_2 from CaCO_3 , and loss of $2 \text{ H}_2\text{O}$ from $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$. This assumption yields the carbonate percentage, as:

$$\text{CaCO}_3(\%) =$$

$$[\text{LOI}(\%) - \text{C}(\%) - (36/172)\text{CaSO}_4 \cdot 2\text{H}_2\text{O}(\%)] / [44/100]$$

- (c) obtain CaO percentage by equating Ca^{++} contributions from CaO, CaCO_3 and $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$, as:

$$\text{CaO} =$$

$$[\text{Ca}^{++}(\%) - (40/100)\text{CaCO}_3(\%) - (40/172)\text{CaSO}_4 \cdot 2\text{H}_2\text{O}]/[40/56]$$

- (d) obtain fly ash percentage from knowledge of the carbon, sulfate, carbonate, and oxide fractions so that the sum of all components is 100% .

Table B-2 summarizes the composition of the engine deposits derived using the above-described procedure. Even lime additive is expected to lead to both sulfate ($\text{CaSO}_4 \cdot (2\text{H}_2\text{O})$) and carbonate through reaction with the SO_2 and CO_2 in the exhaust gas. The valve stem deposits appear to be predominantly calcium carbonate. On the other hand the valve face deposits appear to contain more or less equal mass percentages of the sulfate and the carbonate. These differences in the compositions of valve face and stem deposits may be due to the valve faces being exposed to the exhaust gas and the lower temperatures of the valve stems as compared with those of the valve faces. The carbonaceous matter appears to be small in these deposits due to continuous oxidation in the exhaust gas stream.

TABLE B-2. CALCULATED CHEMICAL COMPOSITIONS OF GE-TS SINGLE
CYLINDER RESEARCH ENGINE DEPOSITS (7/89)

SAMPLE DESCRIPTION	CaO (%)	CaCO ₃ (%)	CaSO ₄ · 2H ₂ O (%)	C (%)	FLY ASH (%)
TR4731 (PISTON CROWN)	N/A	N/A	N/A	N/A	N/A
TR4731 (L)INLET VALVE FACE	21.3	32.1	37.3	0.76	8.6
TR4731 (R)INLET VALVE FACE	17.5	44.6	29.3	1.62	7.1
TR4731 (L)EXH. VALVE STEM	12.2	63.7	12.6	0.19	11.3
TR4731 (R)EXH. VALVE STEM	17.0	69.1	9.6	0.20	4.1
TR4731 (L)EXH. VALVE	22.8	22.0	42.7	4.00	8.5
TR4731 (R)EXH. VALVE	21.9	27.6	35.8	3.67	11.1

APPENDIX C

MALVERN PARTICLE SIZE ANALYZER (MACH 2 AEROSIZER)

The particle size data from the Malvern Analyzer was compared with those reported by the "Micromeritics Sedigraph" instrument, after a factory maintenance check-out of the Malvern analyzer. The comparison, performed with samples of fractionated limestone, is summarized in Figure C-1. The shapes of the corresponding cumulative mass fraction curves reported by both instruments for each sample are seen to be similar. For a given sample, the size distribution curves from the two instruments may be made to overlap closely through a small translation of the size axis for one instrument's curve relative to the other's. Slight differences between the particle size reported by the two instruments is not unexpected, since the particle size depends on the measurement technique. The Micromeritics instrument infers particle size from measurement of liquid sedimentation rate, while the Malvern instrument infers it from measurement of the particle time of flight in a sub-sonic jet. The former yields a hydrodynamic diameter, while the latter yields an aerodynamic diameter. Systematic differences between these two diameters are to be expected.

The close agreement between the Malvern and Micromeritics measurements for limestone samples qualifies the Malvern instrument's hardware and software functions. Further qualifications for particulate resembling the ash material in CWM engine exhaust are ongoing. Results from these further tests with the Malvern Analyzer will be reported in forthcoming reports.

MALVERN & SEDIGRAPH COMPARISON FRACTIONATED THOMASVILLE LIMESTONE

APPENDIX D

CHARTS OF DIESEL EXHAUST GAS TIME VARIATIONS

GE-TS SINGLE CYLINDER CWM ENGINE TESTS

SO₂ AND NO_x CONCENTRATIONS TEST TS01

GE-TS SINGLE CYLINDER CWM ENGINE TESTS

HC AND CO CONCENTRATIONS TEST TS01

GE-TS SINGLE CYLINDER CWM ENGINE TESTS

CO₂ AND O₂ CONCENTRATIONS TEST TS01

GE-TS SINGLE CYLINDER CWM ENGINE TESTS

SO₂ AND NO_x CONCENTRATIONS TEST TS02

GE-TS SINGLE CYLINDER CWM ENGINE TESTS

HC AND CO CONCENTRATIONS TEST TS02

GE-TS SINGLE CYLINDER CWM ENGINE TESTS

CO2 AND O2 CONCENTRATIONS TEST TS02

GE-TS SINGLE CYLINDER CWM ENGINE TESTS

SO₂ AND NO_x CONCENTRATIONS TEST TS03

GE-TS SINGLE CYLINDER CWM ENGINE TESTS

HC AND CO CONCENTRATIONS TEST TS03

GE-TS SINGLE CYLINDER CWM ENGINE TESTS

CO2 AND O2 CONCENTRATIONS TEST TS03

GE-TS SINGLE CYLINDER CWM ENGINE TESTS

SO₂ AND NO_x CONCENTRATIONS TEST TS04

GE-TS SINGLE CYLINDER CWM ENGINE TESTS

HC AND CO CONCENTRATIONS TEST TS04

GE-TS SINGLE CYLINDER CWM ENGINE TESTS

CO2 AND O2 CONCENTRATIONS TEST TS04

GE-TS SINGLE CYLINDER CWM ENGINE TESTS

SO₂ AND NO_x CONCENTRATIONS TEST TS05

GE-TS SINGLE CYLINDER CWM ENGINE TESTS

HC AND CO CONCENTRATIONS TEST TS05

GE-TS SINGLE CYLINDER CWM ENGINE TESTS

CO2 AND O2 CONCENTRATIONS TEST TS05

GE-TS SINGLE CYLINDER CWM ENGINE TESTS

SO₂ AND NO_x CONCENTRATIONS TEST TS 06

GE-TS SINGLE CYLINDER CWM ENGINE TESTS

HC AND CO CONCENTRATIONS TEST TS 06

GE-TS SINGLE CYLINDER CWM ENGINE TESTS

CO2 AND O2 CONCENTRATIONS TEST TS 06

GE-TS SINGLE CYLINDER CWM ENGINE TESTS

SO₂ AND NO_x CONCENTRATIONS TEST TS07

GE-TS SINGLE CYLINDER CWM ENGINE TESTS

HC AND CO CONCENTRATIONS TEST TS07

GE-TS SINGLE CYLINDER CWM ENGINE TESTS

CO2 AND O2 CONCENTRATIONS TEST TS07

GE-TS SINGLE CYLINDER CWM ENGINE TESTS

SO₂ AND NO_x CONCENTRATIONS TEST TS08

GE-TS SINGLE CYLINDER CWM ENGINE TESTS

HC AND CO CONCENTRATIONS TEST TS08

GE-TS SINGLE CYLINDER CWM ENGINE TESTS

CO2 AND O2 CONCENTRATIONS TEST TS08

GE-TS SINGLE CYLINDER CWM ENGINE TESTS

SO₂ AND NO_x CONCENTRATIONS TEST TS09

GE-TS SINGLE CYLINDER CWM ENGINE TESTS

HC AND CO CONCENTRATIONS TEST TS09

GE-TS SINGLE CYLINDER CWM ENGINE TESTS

CO2 AND O2 CONCENTRATIONS TEST TS09

GE-TS SINGLE CYLINDER CWM ENGINE TESTS

SO₂ AND NO_x CONCENTRATIONS TEST TS10

GE-TS SINGLE CYLINDER CWM ENGINE TESTS

HC AND CO CONCENTRATIONS TEST TS10

GE-TS SINGLE CYLINDER CWM ENGINE TESTS

CO₂ AND O₂ CONCENTRATIONS TEST TS10

GE-TS SINGLE CYLINDER CWM ENGINE TESTS

SO₂ AND NO_x CONCENTRATIONS TEST TS11

GE-TS SINGLE CYLINDER CWM ENGINE TESTS

HC AND CO CONCENTRATIONS TEST TS11

GE-TS SINGLE CYLINDER CWM ENGINE TESTS

CO2 AND O2 CONCENTRATIONS TEST TS11

GE-TS SINGLE CYLINDER CWM ENGINE TESTS

SO₂ AND NO_x CONCENTRATIONS TEST TS12

GE-TS SINGLE CYLINDER CWM ENGINE TESTS

HC AND CO CONCENTRATIONS TEST TS12

GE-TS SINGLE CYLINDER CWM ENGINE TESTS

CO2 AND O2 CONCENTRATIONS TEST TS12

GE-TS SINGLE CYLINDER CWM ENGINE TESTS

SO₂ AND NO_x CONCENTRATIONS TEST TS13

GE-TS SINGLE CYLINDER CWM ENGINE TESTS

HC AND CO CONCENTRATIONS TEST TS13

GE-TS SINGLE CYLINDER CWM ENGINE TESTS

CO₂ AND O₂ CONCENTRATIONS TEST TS13

GE-TS SINGLE CYLINDER CWM ENGINE TESTS

SO₂ AND NO_x CONCENTRATIONS TEST TS14

GE-TS SINGLE CYLINDER CWM ENGINE TESTS

HC AND CO CONCENTRATIONS TEST TS14

GE-TS SINGLE CYLINDER CWM ENGINE TESTS

CO₂ AND O₂ CONCENTRATIONS TEST TS14

GE-TS SINGLE CYLINDER CWM ENGINE TESTS

SO₂ AND NO_x CONCENTRATIONS TEST TS15

GE-TS SINGLE CYLINDER CWM ENGINE TESTS

HC AND CO CONCENTRATIONS TEST TS15

GE-TS SINGLE CYLINDER CWM ENGINE TESTS

CO₂ AND O₂ CONCENTRATIONS TEST TS15

GE-TS SINGLE CYLINDER CWM ENGINE TESTS

CO2 AND O2 CONCENTRATIONS TEST TS16

GE-TS SINGLE CYLINDER CWM ENGINE TESTS

SO₂ AND NO_x CONCENTRATIONS TEST TS17

GE-TS SINGLE CYLINDER CWM ENGINE TESTS

HC AND CO CONCENTRATIONS TEST TS17

GE-TS SINGLE CYLINDER CWM ENGINE TESTS

CO₂ AND O₂ CONCENTRATIONS TEST TS17

GE-TS SINGLE CYLINDER CWM ENGINE TESTS

SO₂ AND NO_x CONCENTRATIONS TEST TS18

GE-TS SINGLE CYLINDER CWM ENGINE TESTS

HC AND CO CONCENTRATIONS TEST TS18

GE-TS SINGLE CYLINDER CWM ENGINE TESTS

CO₂ AND O₂ CONCENTRATIONS TEST TS18

APPENDIX E

DIESEL EXHAUST PARTICULATE SIZE DISTRIBUTION

The size distributions were measured by means of a Shimadzu analyzer operating on the principles of laser light scattering. The log-normal fits were performed on the cumulative (fraction less than) in an electronic spread sheet program (SuperCalc 4).

GE-TS SINGLE CYLINDER CWM ENGINE TESTS

FRACTIONAL SIZE DISTRIBUTION (TS-08CYC)

CUMULATIVE SIZE DISTRIBUTION (TS-08CYC)

GE-TS SINGLE CYLINDER CWM ENGINE TESTS

FRACTIONAL SIZE DISTRIBUTION (TS-08) ^{GB}

CUMULATIVE SIZE DISTRIBUTION (TS-08)

GE-TS SINGLE CYLINDER CWM ENGINE TESTS

FRACTIONAL SIZE DISTRIBUTION (TS-08GB)

CUMULATIVE SIZE DISTRIBUTION (TS-08GB)

GE-TS SINGLE CYLINDER CWM ENGINE TESTS

FRACTIONAL SIZE DISTRIBUTION (TS-12CYC)

CUMULATIVE SIZE DISTRIBUTION (TS-12CYC)

GE-TS SINGLE CYLINDER CWM ENGINE TESTS

FRACTIONAL SIZE DISTRIBUTION (TS-12THM)

CUMULATIVE SIZE DISTRIBUTION (TS-12THM)

GE-TS SINGLE CYLINDER CWM ENGINE TESTS

FRACTIONAL SIZE DISTRIBUTION (TS-14CYC)

CUMULATIVE SIZE DISTRIBUTION (TS-14CYC)

GE-TS SINGLE CYLINDER CWM ENGINE TESTS

FRACTIONAL SIZE DISTRIBUTION (TS-14THM)

CUMULATIVE SIZE DISTRIBUTION (TS-14THM)

GE-TS SINGLE CYLINDER CWM ENGINE TESTS

FRACTIONAL SIZE DISTRIBUTION (TS-15CYC)

CUMULATIVE SIZE DISTRIBUTION (TS-15CYC)

GE-TS SINGLE CYLINDER CWM ENGINE TESTS

FRACTIONAL SIZE DISTRIBUTION (TS-15THM)

CUMULATIVE SIZE DISTRIBUTION (TS-15THM)

GE-TS SINGLE CYLINDER CWM ENGINE TESTS

FRACTIONAL SIZE DISTRIBUTION (TS-16CYC)

CUMULATIVE SIZE DISTRIBUTION (TS-16CYC)

GE-TS SINGLE CYLINDER CWM ENGINE TESTS

FRACTIONAL SIZE DISTRIBUTION (TS-16THM)

CUMULATIVE SIZE DISTRIBUTION (TS-16THM)

GE-TS SINGLE CYLINDER CWM ENGINE TESTS

FRACTIONAL SIZE DISTRIBUTION (TS-17CYC)

CUMULATIVE SIZE DISTRIBUTION (TS-17CYC)

GE-TS SINGLE CYLINDER CWM ENGINE TESTS

FRACTIONAL SIZE DISTRIBUTION (TS-17THM)

CUMULATIVE SIZE DISTRIBUTION (TS-17THM)

GE-TS SINGLE CYLINDER CWM ENGINE TESTS

FRACTIONAL SIZE DISTRIBUTION (TS-18CYC)

CUMULATIVE SIZE DISTRIBUTION (TS-18CYC)

GE-TS SINGLE CYLINDER CWM ENGINE TESTS

FRACTIONAL SIZE DISTRIBUTION (TS-18GB)

CUMULATIVE SIZE DISTRIBUTION (TS-18GB)

APPENDIX F

THIMBLE DELTA P TIME VARIATIONS

THIMBLE DP, gm-water

THIMBLE A/C, ft^2/min

END

**DATE
FILMED**

3 / 5 / 93