006133

1 OF 1

DOE/PC/89768--T9

TECHNICAL PROGRESS REPORT NUMBER SEVEN

DOE/PC/89768--T9

FOR THE PERIOD
March 1 - May 31, 1991

DE93 006133

DOE Contract Number DE-FG22-89PC89768

PULSED ELECTRON BEAM PRECHARGER

Submitted by

Aerosol Physics Group
Department of Physics
The Florida State University
Tallahassee, FL 32306-3016

Principal Investigator

Dr. W. Neil Shelton
Professor of Physics
(904) 644-6552

Report Editor

Wright C. Finney
Associate in Research
(904) 644-1598

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

MASTER

EP

"US/DOE Patent Clearance is not required prior to the publication of this document."

PULSED ELECTRON BEAM PRECHARGER
Technical Progress Report Number Seven
March 1 - May 31, 1991

Table of Contents

	<u>Page</u>
I. INTRODUCTION AND CURRENT STATUS OF THE PROJECT	1
II. CONTRACT PROGRESS DURING QUARTER SEVEN	10
A. Electron Beam Precipitator Wind Tunnel	10
1. Review of EBP Components and Subsystems	10
2. Particle Charge vs. Radius Apparatus	22
3. Absolute Filter Holder Aerosol Sampler	27
B. Particle Charge vs. Radius Ratio (Q/A) Investigation	32
1. General Experimental Procedures	32
2. Properties and Concentration of Test Aerosol	34
3. Operation of Q/A Measurement Device	36
4. Computation of Saturation and Predicted Charge	37
5. Charge vs. Radius Ratios - Measured Values	40
III. PUBLICATIONS, PRESENTATIONS, AND PARTICIPATIONS	46
A. Department of Chemical Engineering Colloquium, Florida State University	46
IV. PERSONNEL	47

I. INTRODUCTION AND CURRENT STATUS OF THE PROJECT

During the previous reporting period (Quarter Six), the charging and removal of a fine, high resistivity aerosol using the advanced technology of electron beam precipitation was successfully accomplished. Precharging a dust stream circulating through the EBP wind tunnel produced collection efficiency figures of up to 40 times greater than with corona charging and collection alone (Table 1). The increased system collection efficiency attributed to electron beam precharging was determined to be the result of increased particle charge. It was found that as precharger electric field was raised, collection efficiency became greater. In sequence, saturation particle charge varies with the precharger electric field strength, particle migration velocity varies with the precharger and collector electric field, and collection efficiency varies with the migration velocity. Maximizing the system collection efficiency requires both a high charging electric field (provided by the E-beam precharger), and a high collecting electric field (provided by the collector wires and plates).

Because increased particle collection efficiency is directly attributable to higher particle charge, the focus of research during Quarter Seven was shifted to learning more about the actual charge magnitude on the aerosol particles. Charge determinations in precipitators have traditionally been made on bulk dust samples collected from the flue gas stream, which gives an overall charge vs. mass (Q/M) ratio measurement. More recently, techniques have been developed which allow the measurement of the charge on individual particles in a rapid and repeatable fashion. One such advanced technique has been developed at FSU for use in characterizing the electron beam precharger.

Table 1.

High Particle Loading Collection Efficiency Runs -
Mk. III-B E-Beam Precharger using 1.0 μm Hydral

Experimental Conditions - Run # 450

Test Aerosol	:	Hydral, 1.0 μm diameter
Particle Count Period	:	84 sec.
Climet Dilution Ratio	:	50:1
Precharger Gas Velocity	:	3.2 ft.sec
Collector Electric Field	:	4.0 kV/cm
Collector Ion Current	:	100 μA
Electron Beam Energy	:	90 keV
Electron Beam Current	:	2.0 μA
Precharger Voltage	:	66, 70 kV
Precharger Electric Field	:	4.7, 5.0 kV/cm
Precharger Ion Current	:	41, 43 μA

	Particle Count	Penetration %	Efficiency %	α -Value	Electric Field
<u>Run #305</u>					
Particles Only	80,575,000				
Particles, Coll.	11,250,000	14.0	86.0		
Part., Coll., Prech.	1,070,000	1.33	98.7	10.5	4.7 kV/cm
Part., Coll., Prech.	279,250	0.35	99.7	40.2	5.0 kV/cm

The FSU particle charge vs. radius (Q/A) apparatus is based in principal on the old Millikan oil drop physics experiment in which the charge of an electron is found using fine particles suspended in an electric field. This unique device has the advantage of being able to directly measure the charge on many individual particles in a short period of time. The Q/A apparatus was frequently operated in conjunction with the particle collection efficiency experiments, and the particle charge data was compared with theoretical values in order to assess the charging effectiveness of the electron beam precharger. A summary of this work covering a period of approximately six months is presented in the following sections.

Section II-A contains a review of the layout and operation of the entire FSU Electron Beam Precipitator (EBP) test system. In addition, a description of many recent important upgrades and modifications to the wind tunnel and subsystems can be found in this section. The EBP is basically an instrumented wind tunnel in the form of a closed circuit loop of ductwork. Various functional modules are interspersed along the length of the wind tunnel, including specialized sections for aerosol generation, electron beam particle precharging, electrostatic dust collection, and gas and particle monitoring. Monodisperse ($1.0\text{ }\mu\text{m}$ mean diameter) hydrated alumina "Hydral" dust or polydisperse fly ash aerosols are circulated in the wind tunnel using a high capacity blower; the particles are completely filtered out of the gas stream after passing through a large absolute filter.

Electron beam precipitation is a two-stage procedure, and, as such, different operational requirements are necessary for the precharging and collecting sections. The Mk. III electron beam precharger is located downstream from the aerosol entrainment

module. It is composed of a length of non-conducting ductwork bounded on either side by a set of electrodes. A 100 keV electron accelerator produces a plasma region of bipolar ionization within an annex adjacent to the precharger proper. DC or pulsed electric fields can be applied to the precharger electrodes, extracting a monopolar charge fraction from the ionization zone. Aerosols passing through the precharger are charged to very high levels, and then are transported downstream to the collector. The collecting section just downstream from the precharger is configured like a conventional electrostatic precipitator in order to test electron beam precharging in a "retrofit" situation. Together, the intense charging capability of the precharger and the high efficiency of the collector constitute an effective two-stage particle removal system.

A rotating spark gap power supply is currently being developed for the pulsed electron beam precharging experiments which will be started later in the contract period. During early tests of this pulser, it was found that a large amount of electromagnetic noise was produced by the rotating spark gap. Despite numerous attempts to totally eliminate the emitted noise, only partial success in this endeavor was achieved. A search was begun in order to locate a particle monitoring system which would not be affected by the operation of the pulsed power supply.

The Climet optical particle counter was used in some of the earlier tests using dc-only energization of the precharger electrodes (see Technical Progress Report 6). For the present experimental runs focusing on the determination of particle charge vs. radius, and for the future runs using pulsed power, however, the optical particle counter was abandoned in favor of a non-electronic, bulk dust filtering system for use in determining the wind tunnel particle concentration under high loading conditions. Shakedown runs with this filter holder proved its effectiveness in sampling the particle-laden gas passing through the E-beam precharger and collector.

One of the most important tasks of the present contract is to measure in-situ the charge and mass of individual particles exiting the electron beam precharger. Although this capability has been demonstrated during earlier experiments, there were recurring problems with the procedure which included the inability to remotely focus the microscope objective lens while running an experiment. Operation of the FSU-developed charge vs. radius (Q/A) apparatus was greatly improved with the addition of a synchronous motor and gear train which now allows very fine control of the particle image on the video screen.

Additional modifications and upgrades to the EBP subsystems included installing a heated pressurization system for the AccuRate screw feeder which aided the dust feeding and deagglomeration process. Particle counting and sizing using the Climet multichannel analyzer and sensing unit (for certain dc-only runs) was improved by a long overdue overhaul. Data acquisition was made more reliable through the repair and recalibration of the MicroMac A/D signal converter and the aging but functional microcomputer which links all of the electronic monitors.

Section II-B details the sequence of Quarter Seven experiments leading to the determination of charge vs. radius ratios for particles charged by the electron beam precharger. This portion of the Technical Progress Report contains subsections on general experimental methods, chemical and physical properties of the test aerosol, the Q/A ratio measurement device, calculation of several comparative parameters, and an analysis of particle precharging and collection. In an effort to produce results which can be used as a basis for comparison to both previous dc electron beam precharging experiments and the upcoming pulsed precharging experiments, great care was taken to insure the constancy and compatibility of all of the run parameters.

Experimental runs to determine particle charge and collection efficiency were performed as a five-step procedure leading to the determination of particle concentration using a) aerosol-only, b) aerosol treated by the collector, and c) aerosol treated by both the collector and the precharger. Comparison of the collector-only condition with the precharger-collector condition can be made using a computed collection efficiency improvement factor denoted as " α ". A series of these multi-step procedures was used to examine a number of precharger and collector parameters which were varied

through an appropriate range. Values of aerosol penetration, particle collection efficiency, and the calculated α -value provided a quantitative indication of how well the system was performing at the optimum level of each tested parameter. For most of these runs, a concurrent measurement was made of the charge on individual particles sampled downstream from the electron beam precharger.

Hydral (hydrated alumina) powder was chosen as the test dust to be resuspended in the wind tunnel because of its highly desirable properties for these experiments. It is monodisperse, having a mean diameter of $1.0 \mu\text{m}$, and, most importantly, it exhibits very high resistivity at ambient wind tunnel temperature. Hydral is fed into the EBP aerosol entrainment module ductwork at a concentration of approximately 0.01 gr/ft^3 . This dust concentration is lower than that found in conventional electrostatic precipitators primarily because of the limitations of the fluidized bed portion of the dust feeder apparatus. As earlier described, for these experiments an absolute filter holder replaced the Climet as the primary particle monitoring device, allowing higher than previous concentrations of aerosol to be tested.

As has already been stated, the magnitude of the electric field determines the theoretical saturation limit of the charge on a particle. However, the maximum potential charge limit on a particle depends upon, among other variables, the radius of the particle and the residence time of the particle in the charging electric field region. Therefore, the calculated predicted particle charge level for a particular residence time will be lower than the theoretical saturation limit unless the residence time of the particle in question is infinite. Theoretical saturation and predicted particle charge levels were calculated for a number of

parametric conditions corresponding to many of the experiments run both previously and specifically for this study during Quarter Seven.

In addition to the computed charge values, the charge on individual particles was directly measured using the FSU-developed charge vs. radius ratio (Q/A) measurement system. This device samples particles from the EBP wind tunnel just downstream from the precharger and introduces them into a laser-illuminated chamber bounded by an oscillating electric field. Particle charge is derived from the magnitude of oscillation while radius and mass are determined by the falling velocity of the particle in the enclosed chamber.

Experimental and theoretical particle charge values were determined for precharger gas velocities of zero (infinite residence time) and 4.0 ft/s (250 ms residence time) at various precharger anode voltages. The predicted charge at 4.0 ft/s is approximately 95% of the saturation charge limit, meaning that at realistic duct gas velocities, particles passing through the precharger should have the potential to closely approach the maximum possible charge. Saturation and predicted charge levels for the experimental conditions examined this term ranged from 2.55 to 3.73×10^{-17} C, or 159 to 232 electronic charges. Individual particle charge as measured by the Q/A device at the same conditions was only about 80% of the predicted charge for a particular particle radius. This may be due to imperfect gas flow through the precharger or to the presence of spurious positive ions in the charging zone (which normally should be completely negatively monopolar).

Section III of this TPR reports on a presentation by one member of our group (Finney) who accepted an invitation to give the departmental colloquium in the Department of Chemical Engineering, FAMU/FSU College of Engineering, in October of 1990. The purpose of the talk was to apprise new and returning engineering faculty members and students of the work being carried out by the Aerosol Physics Group on electron beam precipitation, pulsed streamer corona treatment of gas-phase sulfur and nitrogen dioxide, and free electron charging of aerosol particles. Lastly, Section IV lists the personnel currently affiliated with the project.

II. CONTRACT PROGRESS DURING QUARTER SIX

A. Electron Beam Precipitator Wind Tunnel

1. Review of EBP Components and Subsystems

Electron beam particle precharging experiments using a dc charging electric field were conducted using the FSU Electron Beam Precipitator wind tunnel, the Mk. III E-beam precharger, and a moderately high concentration of high resistivity Hydral test dust. Although the wind tunnel and associated subsystems have been described elsewhere in detail, a review of the experimental apparatus, the mechanics of precharging, and the data acquisition and analysis procedures will be presented here.

Figure 1 shows the Electron Beam Precipitator (EBP) test system, a facility which is unique in the U.S. by virtue of combining the technologies of electron beam treatment, pulsed power energization, and electrostatic precipitation in a single unit. The closed-circuit or "racetrack" wind tunnel is composed of a continuous loop of square, stainless steel ductwork interspersed with a number of specialized modules. Some approximate dimensions of the system are: length - 19 ft, width - 7 ft, height - 3.5 ft, total path length - 45 ft, duct size - 1 ft x 1 ft. Opening module tops and sides as well as a number of sampling ports allow ready access to the interior of the wind tunnel.

A large squirrel cage blower controlled by an outlet damper circulates room temperature air at gas velocities and volumes of up to 33 ft and 2000 ACFM, respectively. Just upstream from the fan is a large H.E.P.A. high capacity filter capable of removing 99.97% of all particles larger than 0.3 μm diameter. A humidity

F.S.U. ELECTRON BEAM PRECIPITATOR TEST SYSTEM

Figure 1. The Two-Stage, Laboratory Scale FSU Electron Beam Precipitator Wind Tunnel, showing the Aerosol Injection, E-Beam Precharger, and Collector Modules.

control and monitoring device is located downstream from the fan. Relative humidity levels during the tests ranged from 30 - 50% but were generally very close to 40% RH. Dry air from a compressed air source can also be added to control humidity.

The test aerosol was composed of monodisperse, 1.0 μm median diameter hydrated alumina (Hydral) dust having a resistivity at room temperature of $> 10^{12} \Omega\text{-cm}$. A highly concentrated dust suspension was generated using the fluidized bed/screw feeder aerosol generator (Figure 2), and then it was dispersed into the circulating gas stream at the particle injection module. Two 50% open area baffle screens downstream from the injection point insure that a completely distributed aerosol will be delivered to the precharger.

Since electron beam precipitation is a two-stage concept, particle charging and collecting occur as two separate functions. Particle charging is accomplished in the electron beam precharger upstream from the collecting section. Figure 3 shows the precharging module and the associated electron beam source and vacuum station. The outer precharging module has the same cross sectional area (1 ft x 1 ft) as the wind tunnel ductwork, although the actual precharger sub-duct is only one-quarter the size (6 in x 6 in). The smaller duct is suspended concentrically within the outer module and is constructed of an insulating material. Within the precharger bounding the vertical walls are two parallel sets of metal plane electrodes across which the charging electric field is applied. The flow of test aerosol passes between these electrodes which delineate the charging zone.

Ions and electrons which drive the particle charging process are provided by an electron beam source (Figure 4). The source

Figure 2. Schematic Diagram of the Fluidized Bed / Screw Feeder Aerosol Generation System, which Deagglomerates and Resuspends Hydral and Fly Ash.

—Top View—
Electron Beam Precharger
100 keV Accelerator, and
Vacuum Station

Figure 3. Top View of the BG/CP-2C Vacuum Station, The 100 keV Electron Beam Accelerator (MINACC), and the E-Beam Particle Precharging Module.

Figure 4. Side View Schematic Diagram of the 100 keV Electron Beam Accelerator (MINACC), showing the Accelerator Column, the thin Window, and the Dropping Resistors.

itself is a 100 keV maximum energy electron accelerator constructed at FSU, dubbed the MINACC. Within an evacuated, insulating PVC tube are a hot filament cathode and a series of internal accelerating rings at successively lower electric potentials. The electron beam passes down the tube through the center of the rings and then exits through a thin plastic film "window" out into atmospheric pressure within the precharger, where the ionization process occurs.

Maintaining the MINACC at a pressure level of approximately 5×10^{-6} torr is a dedicated vacuum station, the BG-2 (Figure 3). Control over the pumping process is exercised by a CVC vacuum gauge controller and a series of solenoid-actuated valves. Protection for the diffusion pump is built into the station circuitry in case of an accelerator window blowout or other major vacuum leak.

The mechanics of electron beam particle precharging have been described elsewhere in detail, but the process will be briefly outlined again. As the high energy electron beam passes from vacuum into air through the "window" on the end of the MINACC, the ionization process commences (Figure 5). Positive and negative ions and secondary electrons are created by high energy electrons colliding with oxygen molecules. The rate of ion and secondary electron production is dependent primarily upon the initial electron beam energy and current. This zone of ionization is contained within a recessed area out of the flow of aerosol in the precharger.

Figure 6 shows the present internal electrode configuration of the Mk. III E-beam precharger. Along both side walls of the inner precharging module are a set of plate which define the boundary of the charging zone. When an electric field is applied

Figure 5. Representation of the process of Electron Beam Ionization of Air Molecules, showing the formation of Secondary Electrons by the Primary Beam, and the Separation of Charge using an intense dc Electric Field.

Figure 6. Top View of the Mk. III Electron Beam Precharging Module showing the E-Beam Accelerator, the Cathode and Anode Electrodes, and the Ionization and Charging Regions.

between the anode and cathode electrodes, the charge density is separated into two monopolar fractions. The negative fraction composed of (-) ions and free electrons is drawn out into and maintained in the charging zone, through which particle-laden gas is flowing. High levels of particle charge and fast charging rates result from, respectively, the large electric fields and dense ion currents in the precharger.

Highly charged particles pass out of the precharger, into an expansion section, and then into the collector. Baffle screens insure an even flow into and out of the collection module. The electrostatic collector (Figure 7) is of a standard wire-plate precipitator design with two channels, one of which can be blocked off with a baffle plate, thereby converting the collector to a higher velocity, lower SCA (specific collection area) device. Each field is composed of two 2.5 ft wide by 4 ft high collecting plates separated by 6 in. Five 0.125 in thick wires spaced at 5 in hang between each set of plates. The gas velocity in the collector can be varied between 0.6 ft/s and 2.35 ft/s, changing the SCA from 833 to 1667 using only one collector channel. Voltage was generally set at either 26.7 kV (3.5 kV/cm) or 30.5 kV (4.0 kV/cm). Table 2 shows the dimensional relationships between the precharging module, the racetrack ductwork, and the one and two channel collector configurations.

Several monitoring locations are spaced throughout the wind tunnel, with the three main ones being 1) just upstream from the precharger, 2) midway between the precharging and collecting modules, and 3) immediately downstream from the collector. The latter monitoring station was used for these experiments. It contains a Climet optical particle counter which measures particle size and number, from which the system collection efficiency can

COLLECTING MODULE (Top)

Figure 7. Top View of the Collecting Module within the EBP Wind Tunnel, showing detail of the Six Electric Field Regions composed of Parallel Collection Plates and Central Corona Wires.

Table 2.

DIMENSIONAL RELATIONSHIPS OF THE EBP WIND TUNNEL (EBP)

FSU ELECTRON BEAM PRECIPITATOR

DUCT -- Stainless Steel, Closed Loop, 1 ft² Cross Sectional Area,
40 ft. Path Length

PRECHARGER -- Mk. III Version, Charging Zone
Length = 15 cm (0.5 ft)
Width = 14 cm (0.45 ft)

ELECTRICAL PARAMETERS -- Voltage = 0 - 77 kV dc
E - Field = 5.5 kV/cm
Ion Current = 0 - 40 μA_2
Current Density = 1.25 mA/m²

ELECTRON BEAM -- Energy = 90 keV
Current = 2 μA

COLLECTING SECTION -- Plate Area = 60 ft²
Width = 6 in
Wires = 0.109 in (15)

AEROSOLS AND GENERATORS -- PSL (Collision Nebulizer)
Hydrated Alumina, Fly Ash
(Fluidized Bed/Screw Feeder)

PARTICLE MONITORS -- Optical Particle Counter
Absolute Filter Holder

be determined. The absolute filter holder bulk dust sampling device is also located here. A Kurz electronic air velocity probe and a General Eastern relative humidity and temperature sensor completed the array of aerosol monitors.

Figure 8 shows a schematic diagram of the EBP microcomputer-based data acquisition system which ties the above mentioned monitors to a small computer. In addition to the inputs from the Climet multichannel analyzer and the air velocity and humidity probes, a Micromac data acquisition device measures the precharger and collector voltages and currents and sends the digital data to the computer. A remote controlled, closed circuit TV system is used to visually monitor analog meters measuring the MINACC accelerator vacuum, the electron beam current, and the precharger and collector ion current levels.

2. Particle Charge vs. Radius Apparatus

The charge vs. radius (Q/A) measurement apparatus (Figure 9) was described in detail in Technical Progress Report No. 2. It is based on a highly modified Millikan Oil Drop apparatus used to measure particle size and charge in an airborne medium. In operation, a precharged aerosol sample is drawn from the wind tunnel using a nozzle and then introduced into the Q/A device. Particle charge and radius measurements are made possible by making video recordings of the laser-illuminated particles as they are passed into an airtight cell. The cell chamber contains a set of parallel plates which generate an ac electric field, causing particles in the field to oscillate in a known and calculable manner. Using the magnitude of particle oscillation and the rate of fall of the particles in a series of computer spreadsheet and graphing programs, a Q/A ratio can be obtained. Thus, for each

Figure 8. The Microprocessor-based Data Acquisition and Analysis System serving the Electron Beam Precipitator Monitors.

F.S.U. Charge / Radius Measurement System

Figure 9. The FSU Particle Charge vs. Radius (Q/A) Monitoring Apparatus, showing the Laser Beam, the Video Recording System, and the Particle Charge Measurement Cell.

experimental run, the particle charge provided by electron beam precharging can be compared with the particle collection efficiency of the system in order to establish a cause and effect relationship.

The main goal of the project this quarter concerning the improvement of the charge vs. radius ratio apparatus was to complete the upgrade of the focusing system. As parts for the upgrade began to arrive from orders placed earlier, a completely dimensioned draft sketch was made of the exact system design. A synchronous ac stepping motor and an adjustable gear train assembly was developed in order to provide for finer control of the optical components and to allow the focusing speeds to be changed as desired.

The first task of constructing the focus system frame proved to be a labor-intensive job due to the fact that many of the pieces necessary for assembly had to be machined by hand. Another step consisted of wiring the motor control switching circuitry into a grounded metal box with standard AC input line. Additional time was allocated for rewiring the external focus control system to be compatible with the new motor and, in addition, replacing the control pushbuttons with a single toggle switch.

The final Q/A focusing system design consisted of a V-shaped apparatus with slots milled in either side. These slots were used to secure the motor and gear train, and allowed the assembly to be moved to accommodate different gear ratios. Changing gear ratios adjusts focusing speed and torque of the apparatus to accommodate for various experimental conditions. The gear train consists of four gears, three of which are fixed ratio gears, and a removable fourth gear which determines the output speed. Any gear out of a

set of variable sized gears (the current set includes three) can act as the fourth gear, thereby changing the gear train ratio and speed. Input to output ratios range from 1:24 to 1:12 to 1:8, giving output speeds of 3, 6, and 9 RPM (as reduced from the fixed motor speed of 72 RPM). This fourth gear is attached to a shaft which runs to the focus control knob; this knob moves the lens focus carriage located on the structural beam in forward or in reverse.

A set of safety microswitches was installed on the carriage and wired to the motor control lines. The microswitches prevent the focus control from overshooting the carriage stops by turning off the motor when the carriage reaches a certain point. Without this safety failure, the gears could possibly "strip" if the focusing system locked up.

Operation and setup of the new camera focusing system is similar to the previous system. The motor control circuitry is connected to a long control line which runs inside the accelerator vault to an external panel switch in the control room. The motor is then easily controlled from outside the vault. Moving the switch up or down moves the focus lens in or out; when the switch is placed in the middle position, the motor is almost instantaneously stopped with no noticeable backlash which was a major problem in the previous setup.

In final testing of the completed focus system, it was concluded that the new design was more versatile and was extremely effective in solving the problems inherent in the earlier design. The motor control started and stopped with almost no delay while being fully reversible, and the new system was also easily removable from the Q/A bench as well. An added feature of speed

control over the system was also an important benefit, which may prove to be very useful in experiments to come.

3. Absolute Filter Holder Aerosol Sampler

A new method to sample and count aerosol particles was commissioned this term because of the inability of the Climet optical counter (Figure 10) to function in concert with the pulsed power supply, or to count very high particle numbers. When an oscilloscope was connected to the communication cable of the Climet, it was found that a voltage with a peak value of as high as 50 volts was induced on the cable by the pulsed power supply (Figure 11). This noise resulted in a distortion of the data transmitted from the sensing unit to the multichannel analyzer, usually causing the entire network to "lock up".

The revised particle monitoring protocol involved attaching an "absolute filter holder" (Figure 12) onto the side of the monitoring module downstream from the collecting section. Monodisperse aerosol was withdrawn using a sampling nozzle inserted into the wind tunnel; the nozzle was attached to the body of the filter holder which was, in turn, connected to a vacuum pump. The vacuum pump was calibrated to sample the air isokinetically (gas velocity in the nozzle = gas velocity in the wind tunnel duct). This isokinetic rate was found to be 3.75 SCFH. Contained within the filter holder was a paper filter which removed 99.9% of all particles of $0.1 \mu\text{m}$ diameter or greater. The number of individual monodisperse Hydral particles could then be calculated by weighing the filter paper before and after the sampling period.

A number of test samples of fifteen minutes duration were taken to determine the constancy of this method. The filter paper

CI-225

FEATURES:

- ☐ 0.3 MICRON SENSITIVITY
- ☐ LONG DISTANCE DATA TRANSMISSION
- ☐ COMPACT DESIGN WITHOUT SACRIFICING VERSATILITY OR PERFORMANCE
- ☐ ELLIPTICAL MIRROR OPTICS

MODEL CI-225 OPTICAL SYSTEM:

The patented elliptical mirror light collection system is recognized as the finest in the world, gathering the greatest amount of scattered light for any given particle.

SPECIFICATIONS:

Power: 115/230 volt, 60/50 Hz.

Signals: (1) Digital Output, BNC Connector (J3)
(2) Analog Output for Particle Size Analysis, BNC Connector (J4)

Standard Particle Size Range: .3 to 10 microns and above

Flow Rate: .25 cubic feet per minute

Weight: 40 lbs.

Size: 9½" H, 11½" W, 19¾" L

CI-210 MULTI-CHANNEL ANALYZER

The Climet CI-210 Multi-Channel Analyzer is a micro-processor-controlled multiple pulse discriminator which receives pulses representing particle sizes from one to forty Climet Particle Sensors simultaneously. Pulses are continuously discriminated, accumulated, displayed, and recorded in the CI-210 according to the unit's ten internally stored programs. Most any number of sensors x size ranges per sensor combination $\leq$ forty can be specified. Alarms, data summaries, and computer interfaces are optional and available upon request.

Figure 10. The Climet Optical Particle Size/Number Measurement System, showing the CI-225 Counting Unit and the CI-210 Multichannel Analyzer.

1 - High Voltage Rectifier	7 - D.C. Isolation Capacitor
2 - Faraday Cage	8 - Corona Ball
3 - Capacitor Bank	9 - Current Limiting Resistor
4 - Mechanical Spark Gap	10 - D.C. Ammeter
5 - Strobe Lamp	11 - Precharger Electrodes
6 - Tail Resistor	12 - Current Limiting Resistor

FINNEY 003 MP

Figure 11. Top View of the High Voltage Pulsed Power Supply, showing the Rectifier Network, the Capacitor Bank, the Rotating Spark Gap, and other components.

Figure 12. The Absolute Filter Holder Aerosol Sampler, used for determining bulk particle mass in E-Beam experiments having high concentrations of Hydral Dust.

was weighed before and after an electron beam precharging run, and a change in weight was determined. The change in the filter paper weight was small, within the range of 0.3 mg. This, however, represents a difference of approximately 12,500 particles when using 1.0 μm diameter hydrated alumina dust as the test aerosol. From early indications, the absolute filter holder method of monitoring particle concentration, while not "real time", represents the best available technique which is also immune to noise emitted from the pulsed power supply.

B. Particle Charge vs. Radius Ratio (Q/A) Investigation

1. General Experimental Procedures

The experimental methods used in the previous high aerosol concentration electron beam precharging runs described in Technical Progress Report 6 were repeated for the particle charge vs. radius experiments. Air at room temperature and 40% relative humidity was circulated in the FSU Electron Beam Precipitator (EBP) wind tunnel (Figure 1) at a gas volume of 1.0 ft³/s (velocity = 4.0 ft/s). A particle-free source of test gas was insured by a high capacity absolute filter located upstream from the aerosol entrainment module. The screw feeder/fluidized bed aerosol generator produced a moderately high concentration of resuspended dust which was then injected into the circulating gas stream. Four porous baffle screens along the flow path separating the aerosol entrainment module and the E-beam precharger mixed the dust laden gas thoroughly.

Charging of the particles in the test aerosol takes place in the Mk. III-B electron beam precharger (Figure 6), approximately 12 feet downstream from the point of dust injection. Layout and function of the precharger, the 100 keV MINACC E-beam accelerator, and the dedicated BG-2 vacuum station have already been described in Section II.A. The sampling nozzle for the particle charge vs. radius apparatus is located immediately downstream from the precharger outlet. After precharging, the airborne particles are removed from the gas stream in the collecting section. A monitoring section just downstream from the collector houses a gas temperature and velocity sensor and two sampling tubes, one leading to the Climet optical particle counter and dilution system, and the other to the bulk dust absolute filter holder. Electronic signals

from all of the monitoring devices were subsequently sent to a microcomputer-based data acquisition system for on-line analysis and eventual storage.

Procedures for making a complete experimental run are as follows. Normally one parameter was varied while the others were held constant. Each experiment consisted of several steps which compared the EBP system collection efficiency with just the collector operating to the collection efficiency with both the precharger and collector operating. Each sampling period using the absolute filter holder and pumping train lasted 900 seconds (15 minutes). Particle mass information was recorded for the five-step process: 1) aerosol alone, 2) aerosol treated by collector only, 3) aerosol treated by precharger and collector, 4) repeat Step 2, and 5) repeat Step 1. Data from Steps 1 and 5 and also Steps 2 and 4 were averaged in order to offset any small changes in aerosol concentration over time.

Runs were performed using Hydral test dust at moderately high concentrations with a dc electric field only (no pulsed power) applied to the precharger electrodes, while the electron beam itself was also operated in the dc continuous mode. In addition to the particle count data, charge vs. radius (Q/A) measurements were made during most of the experiments to correlate particle charge with particle collection efficiency. Theoretical saturation charge and predicted charge calculations were also performed to compare to the experimental particle charge data.

General run conditions were as follows:

1. Gas Composition : Air
2. Gas Temperature & Humidity: 25°C, 40% RH
3. Prech. Volume & Velocity : 1.0 ft³/s, 4.0 ft/s
4. Test Dust Type and Size : Hydral, 1.0 μ m mean diameter
5. Fluidized Bed Flow : 0.12 ft³/s
6. Screw Feeder Setting : 100
7. Filter Sampler Flow : 3.75 SCFH = isokinetic
8. Sample Time : 15 minutes (900 seconds) .

2. Properties and Concentration of the Test Aerosol

As called for in the contract Statement of Work, electron beam particle precharging was tested initially using hydrated alumina, or Hydral (Table 3). This Alcoa Aluminas product has the chemical formula $\text{Al}_2\text{O}_3 \cdot 3\text{H}_2\text{O}$ and its properties resemble common alumina in many respects. Hydral is composed of monodisperse particles of $1.0 \pm 0.5 \mu\text{m}$ diameter having a dielectric constant of 8.7. It has the physical form of a white, crystalline substance with a specific gravity of 2.40 g/cm³ and a bulk density of 8-14 lb/ft³, depending on packing. Hydral does not react chemically when exposed to air, water, heat, or strong oxidizers. Possibly most important in the present application is the fact that hydrated alumina exhibits high ($> 10^{12} \Omega\text{-cm}$) resistivity at room temperature, the temperature at which the EBP wind tunnel is currently operated.

Conventional electrostatic precipitators typically operate with duct dust concentrations of between 2.7 and 13.5×10^{10} particles/ft³. In the measurement units more commonly used in electrostatic precipitator terminology, this particle loading

Table 3.

Chemical, Physical, and Size Distribution Properties of "Hydral"Typical Chemical Analysis

<u>Chemical</u>	<u>Formula</u>	<u>Percent (%)</u>
Aluminum Oxide	Al_2O_3	64.7
Silica	SiO_2	0.04
Ferric Oxide	Fe_2O_3	0.01
Sodium Oxide	Na_2O	0.45
Sodium Oxide (soluble)	Na_2O	less than 0.25
Moisture	H_2O	less than 1

Typical Physical Properties

Specific Gravity, g/cm ³	2.40
Tapped Density, lbs/cu ft.	26 - 34
Loose Density, lbs/cu ft.	8 - 14
Lbs./Solid Gallon	19.99
One Lb. Bulks, Gallons	0.0500
Passage Through 325 mesh, %	99.85
Dielectric Constant	~8.7

Typical Particle Size Distribution

<u>Microns</u>	<u>% less than</u>
2	100
1	85
0.5	28

corresponds to a concentration on the order of 1 to 5 grains/ft³. The maximum dust loading that can be realistically tested in the EBP wind tunnel is on the order of 0.1 grain/ft³. For the experiments presented in this report, the highest particle concentration that was generated was approximately 0.05 grain/ft³. The original target goal of 1 grain/ft³ was unattainable in the present experiments due to particle generator and monitor limitations. However, the dust concentration resuspended into the wind tunnel for the experiments presented here is almost five times higher than the dust concentration in any previous experiment.

3. Operation of Charge vs. Radius Ratio Measurement Device

Particle collection efficiency measurements are one way to assess the effectiveness of E-beam precharging on overall system performance. Another way is through the direct measurement of the charge on individual particles exiting the precharger; more highly charged particles should be collected with greater efficiency. Particle charge vs. radius (Q/A) measurements were made using the unique laser-oscillating field Q/A apparatus which was developed at FSU and is shown in Figure 9. The principles of design and operation of this device are described in Section II.A.3 of this report.

A probe was inserted into the wind tunnel duct immediately downstream from the precharger in order to sample the highly charged particles as close to the source as possible. The charge vs. radius unit was positioned adjacent to the wind tunnel to minimize tubing length. During an experiment, a number of aerosol samples were introduced into the Q/A cell and then individual particles were tested for charge and mass. Approximately five repeat cell samples were measured at each different parametric

condition. The data was analyzed and is presented as a series of particles having varying radii and charge levels.

4. Computation of Saturation and Predicted Particle Charge

Calculations of the theoretical charge on 1.0 μm diameter Hydral particles for several electron beam precharger electric field values is shown in Table 4. The parameters employed in the theoretical calculations corresponded to conditions used in actual experimental runs. During preliminary runs, parameter values were chosen which were found to be optimal for efficient particle charging.

Precharger anode voltage was varied in 11 kV steps from 55 to 77 kV, corresponding to electric field values of from 3.93 to 5.50 kV/cm. Particle charge determinations were made using a computer program which calculated the theoretical field charge limit on Hydral particles having a dielectric constant of 8.7. Two charge values were generated for each voltage setting: one for infinite residence time (precharger gas velocity = 0), and one for a residence time of the aerosol in the charging zone of 250 ms (precharger gas velocity = 4.0 ft/s).

From Table 4, the theoretical saturation field charge on particles increased as the precharger electric field was raised from 3.93 to 5.5 kV/cm. The fact that the charge saturation limit varies with electric field is given by the well known Pauthenier ionic field charging equation:

$$q(\infty) = \frac{12 \pi \epsilon_0 \epsilon_s a^2 E}{(\epsilon_s + 2)}$$

Table 4.

Theoretical Particle Charge for Several
Precharger Electric Field Values

Run Conditions

Particle Type : Hydrated Alumina, "Hydral"
 Particle Diameter : 1.0 μm monodisperse
 Dielectric Constant : 8.7
 Anode Ion Current : 40 μA
 Average Current Density : 1.25 mA/m^2
 Precharging Path Length : 30.5 cm (1.0 ft)
 Electrode Separation : 14 cm. (0.46 ft)

Anode Voltage (kV)	Electric Field (kV/cm)	Precharger Gas Velocity (ft/sec)	Residence Time (msec)	Particle Charge ($\times 10^{-17}$ C)	Electronic Charge (#e ⁻)
55	3.93	0	∞	2.67	166e
"	"	4.0	250	2.55	159e
66	4.71	0	∞	3.20	199e
"	"	4.0	250	3.04	189e
77	5.50	0	∞	3.73	232e
"	"	4.0	250	3.51	219e

where:

- $q(\infty)$ = saturation field charge of particle
- ϵ_0 = permittivity of free space
- ϵ_s = specific dielectric permittivity
- a = radius of particle
- E = charging electric field

and by more recent improvements to the theory. From these calculations, saturation particle charge for an infinite residence time ranges from 2.67×10^{-17} C (166 electronic charges) to 3.73×10^{-17} C (232 e) for precharger anode voltages of from 55 to 77 kV.

Nearing or achieving saturation charge assumes that a particle will have a sufficiently long residence time in the precharger. If the precharger gas velocity is zero, residence time is infinite and the charge on a particle will eventually reach the saturation limit. When the precharger gas velocity is increased above zero, less time is available for a particle to be charged to the maximum level. The relation of saturation charge and time is governed by the charging time constant equation:

$$q(t) = q(\infty) \frac{t/\tau}{1 + t/\tau}$$

where:

- $q(t)$ = particle charge at time t
- $q(\infty)$ = saturation particle charge
- t = residence time in the charging zone
- τ = charging time constant.

According to the above relation, as residence time approaches infinity, particle charge will asymptotically approach the saturation limit.

For the present example, a gas velocity of 4.0 ft/s corresponded to a particle residence time in the precharger of 250 ms. The predicted charge on a particle passing through the charging zone for this time interval was calculated and compared to the saturation charge at infinite residence time. The average ion current density (J) was held constant at 1.25 mA/m². Predicted particle charge varied from 2.55×10^{-17} C (159 electronic charges) to 3.51×10^{-17} C (219 e) as the electric field was increased from 3.93 kV/cm to 5.50 kV/cm. These charge values are close to the theoretical saturation charge levels for infinite residence time, ranging from 95.5 % of the saturation charge limit at 55 kV anode voltage, to 94.4 % of the limit at 77 kV voltage.

From earlier studies using low concentrations of 1.0 μ m diameter polystyrene latex spheres, charging particles to within 5 % of the saturation charge limit for a given current density results in very high particle collection efficiencies. However, if the precharger gas velocity is increased and the residence time is thereby reduced, other calculations show that the predicted particle charge falls off dramatically. The result would then be a significantly degraded system particle collection efficiency.

5. Charge vs. Radius Ratios - Measured Values

To compare actual particle charge levels with calculated theoretical saturation charge levels, a series of experimental runs measuring the charge vs. radius ratio of particles exiting the precharger was performed. An aerosol composed of 1.0 μ m mean

diameter Hydral dust was generated and re-dispersed at moderately high density into the EBP wind tunnel. Gas velocity was 1.0 ft/s in the wind tunnel duct and 4.0 ft/s in the precharging module. The MINACC electron beam source was operated at a beam energy and current of 90 keV and 2 μ A, respectively. Two successively higher electric potentials (66 kV and 77 kV) were applied across the 14 cm wide charging zone gap in the Mk. III-B electron beam precharger. Average ion current and current density produced under these conditions was measured at 40 μ A, or 1.25 mA/m².

Figures 13 and 14 illustrate the results of the particle charge vs. radius measurement experiment. Plots of particle charge (in number of electronic charges) vs. particle diameter (in micrometers) was fit by a straight line using a least-squares simple regression. An equation of the straight line is included at the lower right corner of each of the two figures along with the correlation coefficient "R". Second degree polynomial fits of the theoretical maximum saturation charge and the predicted charge level of a particle with 250 ms residence time in the precharger are also plotted on the figures.

Since Hydral dust is nominally monodisperse (1.0 μ m diameter, $\pm$ approximately 0.5 μ m), most of the data should fall near the 1.0 μ m diameter point on the abscissa. However, due to incomplete de-agglomeration of the bulk Hydral by the fluidized bed, clumping of two or more particles is apparently occurring. The test aerosol being generated and circulated through the precharging module is not perfectly monodisperse. This causes measured "particles" of up to almost 2 μ m diameter to show up in the experimental data. Each individual particle represented by a data point, regardless of size, is measured separately to determine the charge and mass.

Charge vs. Diameter: Hydral Run #17, 66 kV, S=14 cm

Figure 13. Graph of Particle Charge in Number of Electronic Charges vs. Particle Diameter in Micrometers for Hydral Aerosol at a Precharger Voltage of 66 kV.

Charge vs. Diameter: Hydral Run #17, 77kV, S=14 cm

Figure 14. Graph of Particle Charge in Number of Electronic Charges vs. Particle Diameter in Micrometers for Hydral Aerosol at a Precharger Voltage of 77 kV.

Therefore, the data accurately represent the results of E-beam precharging even though particle clumping may be occurring.

At 66 kV precharger voltage, or 4.71 kV/cm electric field (Figure 13), plotted lines representing a) the theoretical maximum saturation particle charge for infinite residence time, and b) the predicted saturation particle charge at 250 ms residence time, fall very close to each other. As calculated earlier, the predicted charge line falls just slightly below the maximum saturation charge line because, under ideal conditions, 250 ms is sufficient time for a particle of 1.0 μm nominal diameter (+ 0.5 μm - 0.25 μm) to achieve about 95% of the infinite residence time charge. The experimental data and fitted line for 66 kV precharger voltage fell somewhat lower than the 250 ms predicted charge line. Nevertheless, at 66 kV voltage, the precharger demonstrates its charging effectiveness by yielding data which approach the predicted charge line which, of course, represents ideal charging performance for the particular conditions.

Particle charging efficiency deteriorated when the precharger voltage was raised to 77 kV (5.5 kV/cm electric field). Figure 14 shows that particle charge remains approximately the same regardless of particle size. The nearly horizontal line fit of the data diverges substantially from the calculated particle charge lines at infinite residence time and at 250 ms residence time. These results exhibit behavior which suggest that at 77 kV anode voltage, reduced monopolar particle charging is occurring in the precharger. The 16 % increase in precharger anode voltage from 66 kV to 77 kV dramatically decreases electron beam particle precharging.

Several reasons for the disparity in the predicted and actual particle charge levels at 77 kV can be postulated. The first concerns the fact that at excessive precharger electric fields, free electrons in the charging zone may become accelerated to an energy level high enough to produce bipolar secondary ionization. Secondly, very high anode voltage levels may attract the leading edge of the primary electron beam out into the charging zone, producing another source of unwanted bipolar ionization. A third source of ions opposite in sign to the negative working ions may result from the emission of positive corona from the anode electrode when operated at high precharger electric fields.

Each of the above phenomena introduce positive ions into the charging zone, effectively negating the proper monopolar operation of the precharger. Even a small amount of positive charge overcomes and degrades the dense negative ion and electron flux which normally predominates throughout the charging zone. For a particular precharger geometry (dimensions, electrode arrangement, E-beam placement), care must be taken not to exceed a precharger anode voltage which will initiate any of the aforementioned undesirable conditions. A more in-depth analysis of the mechanics of electron beam energy/precharger geometry/anode voltage matching will be presented in a future Technical Progress Report.

III. PUBLICATIONS, PRESENTATIONS, AND PARTICIPATIONS

A. Department of Chemical Engineering Colloquium, Florida State University -- "Air Pollution Control Technology using Energetic Electrons for Coal Fired Power Plants".

Earlier during the period covered by this contract, one of the investigators was invited to give the departmental colloquium to the Department of Chemical Engineering, Florida A & M University / Florida State University College of Engineering, Tallahassee, FL. Professors Bruce R. Locke and Pedro Z. Arce hosted W. C. Finney of the FSU Aerosol Physics Group who presented a talk entitled "Air Pollution Control Technology using Energetic Electrons for Coal Fired Power Plants" on Wednesday, October 17, 1990, in the Central Engineering Building at the Innovation Park Campus of FSU.

Topics which were discussed in depth during the colloquium included: two-stage electron beam precipitation of aerosols; dc and pulsed E-beam particle precharging, advanced collector designs; monitoring systems, free electron charging of aerosol particles; high energy electron beam irradiation of SO_x and NO_x gas-phase pollutants; and pulsed streamer corona (PEER) treatment of SO_2 , NO_x , and (RO_x) (fly ash). Recent experimental results from the Pulsed Electron Beam Precharger project were especially emphasized.

The colloquium presentation and subsequent meetings have led to the establishment of an ongoing, mutually beneficial working relationship between personnel from the Aerosol Physics Group and the Chemical Engineering department. Many research subjects of common interest in the fields of air pollution control technology will be pursued jointly by these two groups.

V. PERSONNEL

A. Scientific Investigators

1. Dr. W. Neil Shelton Principal Investigator
2. Mr. Wright C. Finney Associate in Research

B. Graduate Student Assistants

1. TBA

C. Undergraduate Student Assistants

1. Chris Oswald
2. Misho Sarwar
3. John Blair

D. Part Time Secretaries

1. Nancy Lochner
2. Amy Maxey
3. Natalie Duguid

**DATE
FILMED**

2 / 8 / 93