WSRC-TR-92-458

TECHNICAL BASES FOR PRECIPITATE HYDROLYSIS PROCESS (U)

by C. J. Bannochie

Westinghouse Savannah River Company
Savannah River Site
Aiken, South Carolina 29808

Other Authors:

This paper was prepared in connection with work done under Contract No. DE-AC09-89SR18035 with the U. S. Department of Energy. By acceptance of this paper, the publisher and/or recipient acknowledges the U. S. Government's right to retain a nonexclusive, royalty-free license in and to any copyright covering this paper, along with the right to reproduce and to authorize others to reproduce all or part of the copyrighted paper.

MASTER

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

This report has been reproduced directly from the best available copy.

Available to DOE and DOE contractors from the Office of Scientific and Technical Information, P.O. Box 62, Oak Ridge, TN 37831; prices available from (615) 576-8401, FTS 626-8401.

Available to the public from the National Technical Information Service, U.S. Department of Commerce, 5285 Port Royal Rd., Springfield, VA 22161.

October 5, 1992

TO: E. W. Holtzscheiter, 773-A

FROM: C. J. Bannochie, 305-A *Bannochie*
D. P. Lambert, 704-1T *D. P. Lambert*

Derivative Classifier *[Signature]*

TECHNICAL BASES FOR PRECIPITATE HYDROLYSIS PROCESS OPERATING PARAMETERS (U)

Summary

This report provides the experimental data and rationale in support of the operating parameters for precipitate hydrolysis specified in WSRC-RP-92-737¹. The report is divided into two sections, the first dealing with lab-scale precipitate hydrolysis experimentation while the second part addresses large-scale runs conducted to demonstrate the revised operating parameters in the Precipitate Hydrolysis Experimental Facility (PHEF).

Introduction

In order to address issues concerning high-boiling organic by-products of precipitate hydrolysis and the concerns about hydroxylamine nitrate (HAN) proposed as a nitrite ion scavenger, an experimental program was initiated in conjunction with the Nitrite Task Team recommendation to reduce the level of nitrite ion in the incoming DWPF feed. The aim of this program was both to demonstrate the acceptability of conducting the hydrolysis at low nitrite ion levels (0.01 M) and to define process operating parameters for a late-wash flowsheet for the salt-processing cell in DWPF. This was achieved by looking more closely at the chemistry involved in the hydrolysis of insoluble tetraphenylborate precipitates. In the course of this work a greater understanding of several factors affecting the rate of hydrolysis of phenylboronic acid, the final and rate-limiting step in the hydrolysis of tetraphenylborate, were identified. These factors include the ratio of copper(II) catalyst to formic acid, the presence of nitrite ion, and reactions of diphenylmercury. The material on these ratios is provided for informational value only and will not be used to run the process.

The goal for the defined process operating parameters was a single process for application during cold chemical runs, both with and without mercury, as well as for radioactive operations. Parameters capable of meeting three criteria were desired. First they must achieve the process requirements of <53 ppm phenylboronic acid in the precipitate hydrolysis aqueous (PHA)² and

<260 ppm diphenylmercury in the organic product³. Secondly, they must consider DWPF equipment constraints. And as a final constraint, the parameters must be robust enough to withstand a degree of uncertainty in feed character and properties.

QA Controls

The experimentation conducted in bench-scale precipitate reactor studies was a scoping activity and was performed in accordance with procedure DWP&HT 2-3, WSRC 1Q43, "Control of Research and Development Activities." Records are kept in laboratory notebooks WSRC-NB-92-66 and WSRC-NB-92-117. All PHEF process run data are stored in the Vantage data collection system running on the VAX computer located in 679-T. A registered data notebook, WSRC-NB-90-178 was used to record data related to Runs 60-63. A run notebook containing the approved run plan, all procedures pertaining to the run, the sample schedule, and run preparation calculations and parameters is retained for each run.

The accuracy of analytical results were controlled by bracketing the analytical results with check standards which were controlled to within 5% (except liquid chromatography results) of their nominal values. The liquid chromatography results were controlled via check standards that were controlled to within 10% of their nominal values. The analytical results are stored in the Laboratory Information Management Software stored on the VAX in 679-T.

SECTION I

Tank 48/49 Product Simulants

Two types of non-radioactive precipitate slurries were studied: 1) an unirradiated precipitate slurry that simulates the projected composition of the plant's radioactive precipitate after two years storage in Tank 49 and 2) an irradiated precipitate slurry that was prepared to simulate freshly prepared slurry in Tank 48 and was subsequently exposed to gamma radiation from a cobalt-60 source. The irradiated slurries were given an absorbed dose of $1.9\text{E}+08$ rads by exposing them to a gamma dose rate of $3.5\text{E}+06$ rads/hr for 55 hours in order to simulate a two year storage at the average activity level of 24 Ci/gal cesium-137 anticipated for the first five years of high-level waste processed.

Both types of precipitate slurries were prepared by adding the vendor supplied solution of sodium tetraphenylborate to a solution of potassium and cesium salts containing the monosodium titanate and sodium nitrite (and diphenylmercury, when appropriate). The unirradiated precipitate simulant was prepared and sampled for analysis of composition prior to each experiment. The salts were added based on the average blend of salts from the material balance for SRS salt waste⁴, modified to reflect radiolytic generation of carbonate. The salt composition, shown in Table I, was such as to provide for an excess of potassium and carbonate ions to simulate radioactive degradation and storage of the precipitate slurry in Tank 49. Table II shows the composition of the unirradiated precipitate simulant as well as the composition of the irradiated

simulant prior to irradiation. The slurry for irradiation contained diphenylmercury at three times the nominal flowsheet level and initially, about 0.25M nitrite. The irradiated slurry, after removal from the cobalt well, was analyzed for organics and inorganics. It was then adjusted to 0.08M nitrite and washed in a continuous washing operation to reduce the nitrite ion concentration to 0.01M.⁵ The washing was performed by pumping the irradiated slurry through a sintered-metal crossflow filter and adding wash water to the agitated slurry at the same rate at which permeate was withdrawn. No secondary precipitation of soluble potassium/cesium salts was performed on these simulants - this modification to accomodate a late wash facility was made later in the experimental program.

In order to examine the effects of the copper:acid ratio and nitrite ion the unirradiated simulant feed was employed. The desired level of nitrite ion was added and a corresponding change in the amount of water made. This precipitate slurry simulated certain features of the radiolyzed slurry (sodium, carbonate, phenol) but many of the radiolysis products (benzene, biphenyl, phenylboronic acid, phenylphenols, terphenyls formate, oxalate) were left out of the basic recipe to determine whether these materials are produced by the hydrolysis reactions. Initial work on diphenylmercury effects was also done with this unirradiated simulant by adding in solid diphenylmercury. Later this work was continued with the irradiated materials where it was found that the hydrolysis kinetics could be followed more consistently.

Precipitate Hydrolysis

Hydrolysis experiments were performed in a 2 L cylindrical glass vessel with a tapered flat bottom fitted with a temperature probe, stainless steel dual 4 blade mechanical stirrer, stainless steel feed tube, glass sampling tube, and insulated glass vapor line connected to a condenser followed by a glass decanter. Aqueous was returned from the decanter to the reactor vessel. Experiments were also conducted in a 1 L Hastelloy C-276 vessel to simulate the plant reactor vessel (no difference was noted in the PBA kinetics from that observed with the glass reactor vessel).

The general process sequence employed is as follows. Precipitate slurry was fed to the reactor vessel below the heel level over a two hour period. The amount of deionized water used to rinse the feed lines was approximately equivalent to the decanter aqueous holdup and was accounted for in the calculations. Temperature was maintained with an electronic temperature controller during the feed and post-feed periods. Following the feed period samples were withdrawn every hour, but occasionally more frequently as required to monitor the PBA, copper, and diphenylmercury (when present) levels. Following the reaction period, the temperature was increased to begin aqueous stripping of any high-boiling organic by-products of the hydrolysis. In the decanter the condensed aqueous phase dropped through the benzene organic phase, which collected during the feed and reaction cycle, transferring the dissolved organic by-products such as biphenyl and diphenylamine. During the entire reaction period the system is kept under a carbon dioxide purge at a flow rate of 2.8 std. cm³/min.

The reaction heel is scaled to duplicate the one necessary to cover the steam and cooling coils in the pilot-scale facility. The heel contains formic acid, copper formate, and deionized water. It is charged to the reactor vessel and brought to the reaction temperature prior to the addition of the precipitate slurry.

Processing Parameters

The stated process operating parameters and the rationale for each of them based on experimental findings are provided below. The effects of nitrite ion will be discussed where appropriate.

PHA Target Acid - 0.25M (acceptable range 0.20 - 0.30M)

Copper(II) Catalyst Target Conc. - 950 ppm (acceptable range 850 - 1050 ppm total Cu)

Timing of Catalyst Addition - in pre-reaction heel

Precipitate Reactor Temperature During Feed Cycle - $90^{\circ}\pm 5^{\circ}\text{C}$

Post-Feed Reaction Period Prior to Aqueous Boil - 5 hours @ $90^{\circ}\pm 5^{\circ}\text{C}$

Aqueous Boiling Period - 5 hours minimum

Total Aqueous Boilup - 10,000 lbs minimum (DWPF)

Copper(II) Catalyst Concentration and Target Acidity in PHA

In a series of experiments unirradiated simulant was hydrolyzed at predetermined total acid levels at each of three copper(II) formate catalyst amounts: 475, 950, and 1425 ppm. Total acid was determined by addition of an amount consumed by the base equivalents from hydroxide, carbonate, TPB^- , and nitrite (when present), plus an additional amount to reach the desired level of acid. In each of these experiments only the amount of initial formic acid in the pre-reaction heel was varied. The level of phenylboronic acid (PBA) was followed by HPLC in samples taken at one hour intervals throughout a five hour reaction period at 90°C and aqueous boil period at 102°C (slightly positive CO_2 pressure). When necessary additional samples were drawn during the first hour of aqueous boil when necessitated by the rate of loss of PBA. Since loss of the final phenyl ring is rate-determining in the hydrolysis of tetraphenylborate, the PBA levels allowed us to judge the degree of reaction completion. A plot of the natural logarithm of [PBA] versus time gave a straight line consistent with a first order loss of PBA. The slope of this line is reported here as an observed, or apparent, first order rate constant. Figure I shows an example of the type of correlations observed in the data. At 475 ppm Cu(II) it was not possible to eliminate the PBA during the reaction period at any of the acid levels examined in the absence of nitrite ion. Figure (II) shows the levels of PBA remaining in the reaction solution at the end

of the five hour reaction period at 90°C. The selection of this reaction temperature will be discussed below. In fact, in the case of 475 ppm Cu(II) it was not possible to eliminate the PBA even after five hours at 102°C. When the level of Cu(II) was increased to 950 ppm there was a significant increase in the rate of PBA hydrolysis and the levels after five hours of reaction at 90°C ranged from 300 - 500 ppm with complete hydrolysis achieved by completion of the aqueous stripping period. At 1425 ppm Cu(II) the levels were reduced even further, to between 125 - 400 ppm, during the initial five hours at 90°C.

Perhaps the most striking observation concerned the relationship between the copper(II) formate catalyst and the amount of total acid necessary to maximize the rate of hydrolysis of PBA. At each successive catalyst level additional formic acid was necessary to maximize the rate of hydrolysis. Even more striking was the fact that there was a parabolic relationship between the Cu(II) and the total titratable acid in the system. Figure (III) shows this relationship for systems both with and without nitrite ion. With either too little or too much acid, there was a decrease in the observed rate constant for hydrolysis of PBA. It was also noted that there was a correlation between the maximum observed rate constants for each Cu(II) level.

The effect of 0.01M nitrite ion under the conditions identified to give the maximum rate of PBA hydrolysis for each Cu(II) level were examined. Again there was a correlation between the observed rate constants for the three levels of catalyst examined. When various levels of formic acid were utilized to affect a change in the total acid level of the 950 ppm Cu(II) system, it was noted that there was more flexibility in the ratio of acid in the presence of 0.01M nitrite ion. The acid level could be reduced from 0.6M to 0.3M and maintain essentially the same observed rate of hydrolysis of PBA. However, below 0.3M total acid there is a decrease in the observed rate constant. See Figure III.

As anticipated the changes in the rate constant were directly proportional to the nitrite ion level in the feed. See Figure IV. Nitrite ion may be involved in a catalytic cycle of the copper catalyst, possibly serving to oxidize Cu(I) back to Cu(II) in much the same manner that occurs in the conversion of nitrous acid to nitric oxide by Fe(II)⁶. Nitrous acid with a pK_a of 3.0 (25°C, $I=1.0$)⁷ is readily formed in this buffered system, pH 3.5 - 4.0.

Equation (2) has an even more positive standard cell potential ($E^\circ = 0.83\text{V}$) than (1) $E^\circ = 0.23\text{V}$ and thus would also be expected to occur spontaneously. It has been shown that PBA when refluxed with cupric chloride produces cuprous chloride⁸. Hence the level of soluble copper in the PR can be expected to vary depending on the particular redox environment and insoluble copper species will likely occur.

ties to the levels of some organic by-products such as diphenylamine. There was a direct relationship between the starting nitrite ion level in the feed and the residual amount of diphenylamine remaining in the PHA. See Figure V. Since the small scale decanter performance may be a factor here, these values should be viewed in light of this fact.

The specified acidity target and range were selected after looking at the processing of irradiated feeds containing diphenylmercury (Ph_2Hg). With the irradiated feed the target acidity was achieved by addition of sufficient acid to bring the material to pH 5.5, account for the base equivalents of TPB⁻, and supply the desired level of excess acidity (0.2-0.3M PHA). Diphenylmercury increases the rate of hydrolysis of phenylboronic acid but hydrolysis of Ph_2Hg does not appear significant until after the complete hydrolysis of PBA. This can be seen in Figure VI. The level of Ph_2Hg remains constant until after the level of PBA drops to near zero. The rationale for completing hydrolysis of Ph_2Hg during the reaction period prior to the onset of aqueous stripping will be elaborated upon in a later section.

Timing of Catalyst Addition

The catalyst is added to the pre-reaction heel in order to begin the hydrolysis reaction as rapidly as possible at the onset of feed addition. This eliminates foaming due to a build up of unhydrolyzed solids which can trap gases. Additionally, since the reaction is believed to proceed by a free radical mechanism⁹, the more rapidly that the benzene is distilled from the reacting solution the lower the statistical probability that phenyl radicals produced during the hydrolysis of TPB will combine with benzene to produce biphenyl as a reaction by-product rather than reaction of phenyl radicals with water to produce benzene. This can be seen in the following equations.

Post-Feed Reaction Period and Temperature

Several factors are involved in the length and temperature of the post-feed reaction period including the time necessary to complete hydrolysis of PBA and Ph_2Hg as well as the vapor pressure of Ph_2Hg . The five hour reaction time at 90°C was brought about initially by an examination of the effect of Ph_2Hg on precipitate hydrolysis. When precipitate slurry was fed

to the reactor vessel over the standard two hour period at 90°C and followed immediately by aqueous stripping at 102°C, Ph₂Hg levels in the decanter organic product were in the range 1000-1500 ppm. The current disposal limit on Ph₂Hg in the organic product is 260 ppm³. In an attempt to hydrolyze the Ph₂Hg more rapidly to Hg(II), which is rapidly reduced to Hg(0) by the formic acid and does not collect in the organic phase, 98°C feeding was initiated. Unfortunately, the Ph₂Hg levels in the organic product increased to 2000-3000 ppm. In the absence of data on the vapor pressure behavior of Ph₂Hg an estimation was necessary. Figure VII presents a semilogarithmic plot of the vapor pressure (P) versus 1/T for various mercuric halides. Assuming that the slope for the ln(P) versus 1/T for Ph₂Hg is similar to these compounds, an estimate can be made for the vapor pressure of Ph₂Hg using the data¹⁰ for HgI₂.

$$\ln(P)_{\text{Ph}_2\text{Hg}} \approx \ln(P)_{\text{HgI}_2} = 23.38 - 1.007\text{E}4 / T$$

The estimate indicates an increase by a factor of two on going from 90°C to 98°C. So in order to hydrolyze the Ph₂Hg and prevent it from steam stripping into the organic product, the Ph₂Hg levels were examined in the organic product after 90°C reaction periods of two, four, and five hours. At five hours, three times the nominal (1000 ppm) anticipated feed level of Ph₂Hg was hydrolyzed successfully resulting in no Ph₂Hg in the organic product.

Since the vapor pressure of Ph₂Hg increases with temperature it is best to keep the precipitate reactor (PR) temperature close to the 90°C target. If the temperature is on the low end of the range (85-95°C) it will only decrease the hydrolysis kinetics and possibly necessitate an additional hour of reaction while an increased reaction temperature may result in the collection of Ph₂Hg in the organic product where it will need to be hydrolyzed, if it exceeds the 260 ppm limit, during the organic evaporator (OE) cycle or returned to the PR.

Total Aqueous Boilup and Boiling Period

Five hours of aqueous stripping at a rate of 60g/hr (equivalent to a boilup of one-third of the feed mass) was demonstrated throughout our development work for a late-washed flowsheet for precipitate hydrolysis to provide sufficient time for stripping of key organic by-products such as biphenyl and diphenylamine produced during precipitate hydrolysis under optimized conditions. See Tables III and IV. Since the decanter efficiency in bench-scale precipitate hydrolysis may not be directly comparable to that in PHEF, confirmation of the adequacy of the boilup rate was left to PHEF process simulations.

Conclusions

The process operating parameters for precipitate hydrolysis for a late-wash flowsheet at 0.01M nitrite ion are capable of achieving the process requirements of <53 ppm phenylboronic acid in the PHA and <260 ppm diphenylmercury in the organic product. The organic by-products formed (eg. biphenyl, terphenyls, and diphenylamine) can be removed from the PHA during aqueous stripping due to the reduced production with the lower nitrite ion feed levels.

SECTION II

PHEF Demonstration of the Late-Washing Flowsheet

The Precipitate Hydrolysis Experimental Facility (PHEF) process demonstration of the late wash flowsheet occurred between June and August 1992. Four runs (PHEF Runs 60-63) were completed to demonstrate the feasibility of the late wash flowsheet in the 1/5th DWPF engineering scale facility. Five areas will be briefly discussed: 1) Feed composition, 2) PHA quality, 3) Hydrolysis reaction kinetics, 4) Temperature control, and 5) Organic removal.

Feed Composition

Typical feed composition for runs 60-63 is listed in Table V. The feed used for all four runs was purchased from Optima Chemicals to simulate the late wash radioactive slurry which will be processed by DWPF. The slurry specifications were developed to simulate a 4x washing without late precipitation. The slurry is purchased as a separate salt solution which is combined with a sodium tetraphenyl borate solution in the TNX W-1 Slurry Storage Tank. Nitrite, biphenyl, foam retardants, and water are added to the slurry after it is transferred to the Precipitate Hold Tank to meet the run specifications.

PHA Quality

The late wash PHA was low in high boiling organics and ammonium relative to the HAN process. The organic analytical results are summarized in tables VI-IX. The PHA product high boiling organic concentration was 8.4% of the high boiling organic concentration in typical HAN flowsheet runs¹⁰. The PHA had a low diphenylamine concentration because of the low diphenylamine production. The PHEF PHA contained no detectable ammonium versus the approximately 1000 ppm measured in the HAN process. There was no production of ammonia in the late wash runs because of the removal of hydroxylamine nitrate (HAN) from the flowsheet which was the source of the ammonia production.

Hydrolysis Reaction Kinetics

The DWPF Process Requirement that the PBA concentration is below 53 mg/L was met for all four runs. The five hour reaction period was specified using data gathered in the laboratory scale experiments to complete the hydrolysis of phenylboronic acid (PBA) to benzene. The Precipitate Reactor was sampled at 30 minute intervals during the five hour reaction period. A graph of PBA versus time is summarized in Figure 8 for Runs 60-63 (the first 90 minutes of Run 62 data is not included because representative samples were not pulled). In each of these runs, the PBA concentration dropped below 53 mg/L before the five hour reaction period was complete. Three of the four runs had PBA concentrations less than 53 mg/L within the first four hours of the reaction period.

Late Wash Feed and Reaction Temperature Control

The liquid temperature was controlled within the late wash flowsheet temperature limits (85-95°C) throughout the two critical periods for temperature control. The liquid temperature was controlled during the feed period at 90°C ($\pm 2.5^\circ\text{C}$). The liquid temperature was controlled during the five hour reaction period at 90°C ($\pm 1^\circ\text{C}$)¹¹.

Decanter Organic Removal Performance

Long term decanter performance in the late wash process will be good because of the low production of high boiling organics. The new decanter had higher extraction efficiency during stripping and was better at self cleaning than the existing decanter. The higher extraction efficiency of the new decanter should lead to a 50% lower high boiling organic content for strippable organics (diphenylamine and biphenyl) in the PHA. This should lead to less operational problems and cleaning downtime in DWPF¹².

Conclusions

The PHEF late wash runs demonstrated that precipitate product could be produced that is lower in ammonium and high boiling organics while meeting the specification for reaction completion of phenylboronic acid hydrolysis. Temperature control and decanter organic removal performance were both excellent in the late wash process.

References

1. Landon, L. F., *DWPF Integrated Cold Runs Revised Technical Bases for Precipitate Hydrolysis (U)*, WSRC-RP-92-737, May 27, 1992.
2. Jacobs, R. A., *SRAT and PRBT Vapor Flammability - SRL Recommendations to the Defense Waste Processing Facility (U)*, WSRC-RP-90-0793, June 21, 1991.
3. Eibling, R. E. and Jacobs, R. A. (prepared by), *Process Requirements for Precipitate Hydrolysis*, DWPF-PR-S03(rev. 1), January 27, 1992.
4. Choi, A. S., *Material Balance Tables for the DWPF Basic Data Report (DPSP-80-1033)rev.138 Appendix G., Table 90-1*, WSRC-TR-90-93, February 28, 1990.
5. Morrissey, M. F., *Late Washing Efficiency (U)*, WSRC-RP-92-1030, August 31, 1992.
6. Cotton, F. A. and Wilkinson, G., *Advanced Inorganic Chemistry*, 5th ed. New York: John Wiley & Sons, 1988: 327.

7. Smith, R. M. and Martell, A. E., *Critical Stability Constants, Vol 4.* New York: Plenum, 1976: 47.
8. Ainley, A. D. and Challenger, F., *J. Chem. Soc.* **1930**, 2174-2180.
9. Smiley, R. A., *Salt Processing Cell Flowsheet: Preliminary Analysis and Recommendations*, WSRC Subcontract AA89066S, July 1992.
10. Hodgeman, C. D., Ed. *CRC Handbook of Chemistry and Physics*, 36th ed. Cleveland: Chemical Rubber Publishing, 1954.
11. Lambert, D. P., Young, S. R., *Organic Accumulation in the DWPF CPC Vessel Vent System (U)*, SRTC-LSE-92-0033, October 3, 1992 (DRAFT)
12. Lambert, D. P., Edwards, R. E., Shah, H. B., and Young, S. R., *Run 60 Preliminary Report, Precipitate Hydrolysis Experimental Facility (U)*, WSRC-RP-92-943, July 28, 1992.
13. Lambert, D. P., *Effectiveness of Decanter Modifications on Organic Removal (U)*, WSRC-RP-92-996, August 20, 1992.

Contributors

M. A. Baich
J. T. Carter
R. E. Edwards
R. E. Eibling
L. F. Landon
J. C. Marek
H. B. Shah
S. R. Young

Distribution

L. F. Landon, 704-T
J. T. Carter, 704-1T
R. A. Jacobs, 704-T
J. C. Marek, 704-T
R. E. Eibling, 704-T
M. A. Baich, 704-T
H. B. Shah, 704-1T
S. R. Young, 704-1T
R. E. Edwards, 704-1T
H. E. Shook, 704-1T
A. L. Blancett, 773-A
F. R. Graham, 773-A
T. S. Rudisill, 773-A
SRTC Records, 773-A (4)

Table I. Salt composition used in the preparation of the unirradiated precipitate feed.

Component	Amount(wt%)
H ₂ O	0.948
K ₂ CO ₃	0.0337
Na ₂ CO ₃	0.0132
CsNO ₃	0.000953
B(OH) ₃	0.000967
KCl	0.0000676
KF	0.0000204
Na ₂ SO ₄	0.000398
K ₂ CrO ₄	0.0000130
Na ₂ SiO ₃ ·9H ₂ O	0.0000217
K ₂ MoO ₄	0.00000199
C ₆ H ₅ OH	0.00296
C ₆ H ₅ B(OH) ₂	0
NaNO ₂	0

Table II. Composition of unirradiated Tank 49 simulant and irradiated Tank 48 simulant prior to irradiation.

Component	Unirradiated(wt.%)	Irradiated (wt.%)
H ₂ O	89.2	87.8
KBPh ₄	8.10	8.86
CsBPh ₄	0.113	0.111
NaBPh ₄	0	0.537
NaNO ₃	0.0212	0.171
NaNO ₂	*	1.56
Na ₂ SO ₄	0.0203	0.0205
Na ₂ CO ₃	1.87	0.0189
NaOH	0.15	0.363
Na ₂ SiO ₃	0.000474	0.000481
NaCl	0.00270	0.00135
NaF	0.000756	0.000646
Na ₂ CrO ₄	0.000543	0.000552
K ₂ CO ₃	0.164	0
CsOH	0	1.55 x 10 ⁻¹⁰
Na ₂ B ₄ O ₇	0.0402	0.0224
C ₆ H ₅ ONa	0.151	0.000459
Hg(C ₆ H ₅) ₂	0	0.315
NaTi ₂ O ₅ H	0.200	0.200

* Added into simulant at various levels, see text.

Table III. Composition of PHA under various conditions specified by "total acid (M)/NO₂⁻ (M)/Ph₂Hg (mg/L)" for an initial target copper(II) concentration of 950 ppm. PHA from conditions specifying Ph₂Hg were from an irradiated feed. Units are mg/L unless specified otherwise.

Component	0.32/0/0	0.65/0/0	Cold Chemical Runs w/o Hg		Cold Chemical Runs w/ Hg	
			0.19/0.01/0	0.31/0.01/0	0.22/0.01/650	0.31/0.01/650
PBA	<1	<1	<1	<1	<1	<1
N-Phenylformamide	<1	<1	377	278	184	197
Aniline	<1	<1	107	97	102	107
Phenol	843	902	1569	1325	1060	1008
Nitrobenzene	<1	<1	<1	<1	<1	<1
Nitrosobenzene	<1	<1	<1	4	<1	<1
4-Phenylphenol	<1	<1	<1	<1	66	67
2-Phenylphenol	<1	<1	<1	<1	10	12
Diphenylamine	<1	2	<1	86	35	12
Biphenyl	<1	44	7	<1	14	<1
<i>o</i> -Terphenyl	<1	<1	<1	<1	2	2
<i>m</i> -Terphenyl	<1	<1	<1	<1	32	47
<i>p</i> -Terphenyl	<1	<1	<1	<1	7	10
Total Mercury	-	-	-	-	32 ppm	20 ppm

Table IV. Composition of organic product under various conditions specified by "total acid (M)/NO₂⁻ (M)/Ph₂Hg (mg/L)" for an initial target copper(II) concentration of 950 ppm. PHA from conditions specifying Ph₂Hg were from an irradiated feed. Units are mg/L.

Component	0.32/0/0	0.65/0/0	Cold Chemical Runs w/o Hg		Cold Chemical Runs w/ Hg	
			0.19/0.01/0	0.31/0.01/0	0.22/0.01/650	0.31/0.01/650
PBA	155	<1	<1	<1	<1	<1
N-Phenylformamide	<1	<1	<1	<1	<1	<1
Aniline	<1	<1	67	16	14	7
Phenol	4329	3988	6411	6626	1666	1453
Nitrobenzene	<1	<1	<1	<1	34	32
Nitrosobenzene	<1	<1	<1	<1	23	19
4-Phenylphenol	<1	<1	9	8	34	18
2-Phenylphenol	<1	68	<1	<1	152	103
Diphenylamine	185	242	2784	1835	1151	1012
Biphenyl	2810	2464	6094	5865	12986	9726
<i>o</i> -Terphenyl	<1	<1	9	19	178	106
<i>m</i> -Terphenyl	<1	<1	9	10	236	68
<i>p</i> -Terphenyl	<1	<1	54	46	66	32
Diphenylmercury	-	-	-	-	<10	<10

Table V. Typical precipitate slurry used for PHEF runs 60-63. Runs 60 and 61 precipitate slurry added no biphenyl. Runs 62 and 63 precipitate slurry contained 2000 ppm biphenyl simulating radiolysis of the TPB in the storage tank. The feed is representative of 4x late wash slurry without late precipitation. The feed was specified using data prepared by S. R. Young dated May 5, 1992.

Component	Value	Units
Volume Fed	720	Gallons
Nitrite	0.008 - 0.012	M
Tetraphenyl Borate	6.7 - 8.1	weight %
Titanate,	1800 - 2200	ppm
Biphenyl	*	mg/L
Cesium	0.03	weight %
Insoluble solids	7.80	weight %
Total Base (slurry)	0.15	M
* Added 2000 ppm biphenyl to precipitate slurry during runs 62 and 63		

Table VI. Run 60 Precipitate Hydrolysis Aqueous Product Organic Composition.

Sample Number	P6122A	P6122B	AVERAGE	Standard Deviation
Component	mg/L	mg/L	mg/L	mg/L
Phenylboronic Acid	9.0	7.0	8.0	1.7
N-Phenylformamide	262.3	210.0	236.2	41.0
Aniline	157.7	113.7	135.7	28.8
Phenol	1,755.3	1,496.0	1,625.7	241.6
Nitrobenzene	ND	ND	-	-
Nitrosobenzene	ND	ND	-	-
4-Phenylphenol	3.3	4.3	3.8	1.7
2-Phenylphenol	1.0	1.7	-	-
Diphenylamine	13.0	17.0	15.0	3.2
Biphenyl	2.3	3.0	-	-
O-Terphenyl	1.0	2.0	-	-
M-Terphenyl	ND	1.3	-	-
P-Terphenyl	1.0	2.0	-	-
Total High Boiling Organics	17.3	25.3	21.3	-

The "Total High Boiling Organics" category is a sum of the detectable Diphenylamine, Biphenyl, and Terphenyls in the PHA product. Three analyses were completed for each sample. The averages listed below for each sample are the averages of the detectable component. The average and standard deviation is calculated only for samples where all analyses are above the detectable limits.

Table VII. Run 61 Precipitate Hydrolysis Aqueous Product Organic Composition.

Sample Number	P6272A	P6272B	P6272C	AVERAGE	Standard Deviation	
	Units	mg/L	mg/L	mg/L	mg/L	
Component						
Phenylboronic Acid		7.7	8.3	9.3	8.4	1.4
N-Phenylformamide		250.7	256.3	248.3	251.8	3.8
Aniline		118.7	118.0	115.3	117.3	2.3
Phenol		1,616.0	1,744.3	1,717.0	1,692.4	59.3
Nitrobenzene		2.0	ND	12.0	-	-
Nitrosobenzene		ND	ND	ND	-	-
4-Phenylphenol		ND	8.7	13.3	-	-
2-Phenylphenol		1.0	1.5	3.5	-	-
Diphenylamine		9.3	11.3	15.3	12.0	5.7
Biphenyl		1.0	2.0	11.0	-	-
O-Terphenyl		ND	1.0	7.0	-	-
M-Terphenyl		ND	ND	ND	-	-
P-Terphenyl		ND	ND	10.0	-	-
Total High Boiling Organics		10.3	14.3	43.3	22.7	-

The "Total High Boiling Organics" category is a sum of the detectable Diphenylamine, Biphenyl, and Terphenyls in the PHA product. Three analyses were completed for each sample. The averages listed below for each sample are the averages of the detectable component. The average and standard deviation is calculated only for samples where all analyses are above the detectable limits.

Table VIII. Run 62 Precipitate Hydrolysis Aqueous Product Organic Composition after 5 hours of aqueous boil.

Sample Number	P6472A	P6472B	P6472C	AVERAGE	Standard Dev
Units	mg/L	mg/L	mg/L	mg/L	mg/L
Component					
Phenylboronic Acid	10.3	11.0	10.7	10.7	1.5
N-Phenylformamide	184.3	186.3	185.7	185.4	1.9
Aniline	117.7	110.7	116.0	114.8	3.4
Phenol	2,033.7	2,038.3	2,048.3	2,040.1	7.8
Nitrobenzene	ND	ND	ND	-	-
Nitrosobenzene	8.3	4.0	5.3	6.1	4.9
4-Phenylphenol	3.7	1.7	3.0	2.8	1.6
2-Phenylphenol	3.5	1.5	1.0	-	-
Diphenylamine	44.7	38.3	40.3	41.1	5.9
Biphenyl	13.3	2.0	5.3	-	-
O-Terphenyl	4.0	ND	1.0	-	-
M-Terphenyl	6.7	ND	3.0	-	-
P-Terphenyl	5.3	1.3	2.3	3.0	3.4
Total High Boiling Organics	74.0	41.7	52.0	55.9	-

Run 62 Precipitate Hydrolysis Aqueous Product Organic Composition after 10 hours of aqueous boil.

Sample Number	P6561A	P6561B	P6561C	AVERAGE	Standard Dev
Units	mg/L	mg/L	mg/L	mg/L	mg/L
Component					
Phenylboronic Acid	9.0	8.3	8.0	8.4	0.5
N-Phenylformamide	192.0	192.7	192.7	192.4	0.9
Aniline	124.7	124.7	124.0	124.4	0.9
Phenol	1,800.7	1,819.3	1,825.3	1,815.1	16.1
Nitrobenzene	ND	ND	ND	-	-
Nitrosobenzene	2.0	1.0	2.0	-	-
4-Phenylphenol	1.5	1.3	3.0	-	-
2-Phenylphenol	ND	1.0	4.5	-	-
Diphenylamine	7.7	7.0	4.3	6.3	2.2
Biphenyl	5.0	1.0	2.0	-	-
O-Terphenyl	3.7	3.3	3.0	-	-
M-Terphenyl	ND	ND	ND	-	-
P-Terphenyl	2.0	1.0	ND	-	-
Total High Boiling Organics	18.3	12.3	9.3	13.3	-

The "Total High Boiling Organics" category is a sum of the detectable Diphenylamine, Biphenyl, and Terphenyls in the PHA product. Three analyses were completed for each sample. The averages listed below for each sample are the averages of the detectable component. The average and standard deviation is calculated only for samples where all analyses are above the detectable limits.

Table IX. Run 63 Precipitate Hydrolysis Aqueous Product Organic Composition.

Sample Number	P6709A	P6709B	P6709C	AVERAGE	Standard Deviation
Component	Units	mg/L	mg/L	mg/L	mg/L
Phenylboronic Acid		9.7	17.0	10.5	12.6
N-Phenylformamide		174.7	177.7	194.7	182.3
Aniline		128.3	127.7	126.7	127.6
Phenol		2,162.3	2,152.3	2,161.7	2,158.8
Nitrobenzene		9.0	11.0	14.7	-
Nitrosobenzene		22.7	9.0	9.7	13.8
4-Phenylphenol		11.0	2.0	10.3	-
2-Phenylphenol		5.5	4.7	3.0	-
Diphenylamine		23.7	21.3	23.3	22.8
Biphenyl		2.5	2.0	1.0	-
O-Terphenyl		1.0	1.0	ND	-
M-Terphenyl		ND	1.5	ND	-
P-Terphenyl		ND	1.0	ND	-
Total High Boiling Organics		27.2	26.8	24.3	26.1

The "Total High Boiling Organics" category is a sum of the detectable Diphenylamine, Biphenyl, and Terphenyls in the PHA product. Three analyses were completed for each sample. The averages listed below for each sample are the averages of the detectable component. The average and standard deviation is calculated only for samples where all analyses are above the detectable limits.

Figure I. Plot of the $\ln[\text{PBA}]$ versus time (hrs) for an unirradiated, tetraphenylborate precipitate slurry without nitrite ion with 950 ppm Cu(II) and 0.3M total acid at 90°C followed by five additional hours at 102°C.

Figure II. Phenylboronic acid levels (mg/L) after five hours of hydrolysis of an unirradiated, tetraphenylborate precipitate without nitrite ion at various levels of Cu(II) as a function of total acid (M) at 90°C.

Figure III. Observed rate constant (hrs^{-1}) for hydrolysis of phenylboronic acid versus total acid (M) for varying levels of Cu(II) at 90°C both with (0.01M) and without nitrite ion in an unirradiated, tetraphenylborate precipitate.

Figure IV. Variation in the observed rate constant (hrs^{-1}) for hydrolysis of phenylboronic acid as a function of the initial sodium nitrite level (M) in an unirradiated, tetraphenylborate precipitate.

Figure V. Variation in the level of diphenylamine remaining in the aqueous product from an unirradiated, tetraphenylborate precipitate after five hours of aqueous stripping at 102°C, but without an initial five hour reaction period, as a function of initial sodium nitrite level (M).

Figure VI. Effect of diphenylmercury (Ph_2Hg) the phenylboronic acid (PBA) hydrolysis kinetics at 90°C with 950 ppm $\text{Cu}(\text{II})$, 0.3M total acid, and 0.01M sodium nitrite. The change in Ph_2Hg concentration is shown by the unconnected solid circles.

Figure VII. Variation in the vapor pressure, $\ln(P)$ (mmHg), of various mercuric halides as a function of temperature, $1/T$ (1/K). Also shown is the single datum point for diphenylmercury [10.5 mmHg at 204°C].

Figure VIII. PBA Hydrolysis Kinetics: PHEF Runs 60, 61, 62, and 63.

**DATE
FILMED**

4 / 28 / 93