BNL--47959

DE93 005541

Determining Temperature Distributions Inside a Nuclear Reactor

E. Schmidt, S. F. Mughabghab and O. W. Lazareth

August 1992

**Reactor Systems Division
Department of Nuclear Energy**

**Brookhaven National Laboratory
Associated Universities, Inc.
Upton, NY 11973**

Under Contract No. DE-AC02-76CH00016 with the

UNITED STATES DEPARTMENT OF ENERGY

MASTER

REPRODUCTION OF THIS DOCUMENT IS UNLIMITED ED

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, not any any of their contractors, subcontractors, or their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency, contractor, or subcontractor thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency, contractor or subcontractor thereof.

Printed in the United States of America
Available from
National Technical Information Service
U.S. Department of Commerce
5285 Port Royal Road
Springfield, VA 22161

NTIS price codes:
Printed Copy: A06; Microfiche Copy: A01

Table of Contents

	<u>Page</u>
I. Introduction.....	1
A. Description of the System.....	1
B. Dimensionality and Constraints.....	1
C. Summary.....	1
II. Method.....	2
A. Mathematical Description and Solution.....	2
B. Computer Model and Temperature Calculations.....	3
III. Test Cases.....	3
A. Circle.....	3
1. Description.....	3
2. Analytical Solution.....	3
3. ANSYS Solution.....	5
B. 'Shape'.....	5
1. The Area of Material.....	6
IV. The Actual Case.....	7
A. Description.....	7
B. Results.....	7
References.....	11
Appendix A.....	12

List of Tables

	<u>Page</u>
Table 1.....	8
Table 2.....	9
Table 3.....	10

List of Figures

	<u>Page</u>
Figure 1.....	15
Figure 2.....	16
Figure 3.....	17

I. Introduction

A. Description of the System

In a nuclear reactor, energetic particles are generated in the fuel region during the fission process. As these particles are slowed down and absorbed by material in the reactor, this material is heated. The material is cooled by convection of hydrogen flowing through coolant channels.

The primary contributions to this heating process are neutrons and gamma rays. The neutrons have a short mean free-path. They travel a relatively short distance between collisions with nuclei of surrounding material and most end up being absorbed within the fuel region which is about 1 cm thick. Gamma rays, on the other hand, travel a comparatively longer distance between collisions and they travel tens of centimeters from their point of creation. We are interested in the temperature distribution of moderating material, therefore, the primary source of heating will be gamma rays.

B. Dimensionality and Constraints

Modeling the entire reactor for computer simulation would be rather expensive and time consuming (both personnel time and machine time). Consequently, we decided on using a two dimensional description of the 'worst case.' The 'worst case' is one in which the heating rate is highest and the cooling rate is lowest.

C. Summary

The computer simulation is, therefore, a two dimensional model which is heated by radiation and cooled by convection.

II. Method

A. Mathematical Description and Solution

The steady state temperature distribution due to distributed heat sources is Poisson's equation:

$$\nabla^2 T = - \frac{Q}{K} \text{ (Hildebrand, P415, with a change in notation)}$$

where T is the temperature, Q is the heat source, and K is the thermal conductivity.

In matrix notation, this equation is:

$$[K] \{T\} = \{Q\} \text{ (ANSYS, p. 2-2)}$$

where $[K]$ is the thermal conductivity matrix, $\{T\}$ is the temperature vector, and $\{Q\}$ is the heat source rate vector.

The computer program ANSYS (ANSYS, p. 2-2) uses the finite element method to solve this matrix equation. The method is described in Rao (Rao, p 425) and in an ANSYS manual (ANSYS-B, Chapter 2).

B. Computer Model and Temperature Calculations

ANSYS uses the concept of "keypoints," which are user-defined locations which are important to the model being generated. For the problem at hand, keypoints are defined at the vertices and centers of circles of the structure being modeled. Using these keypoints, lines and circles are generated. Take for example, in the model shown below. A complete set of instructions is included in Appendix 1.

In general, seven keypoints are generated (K1 through K7). A circle is generated about K4. This process produces both the keypoints K8 and K10 and also the circular line segments connecting K8, K9, K10, and also the circular line segments connecting K8, K9, K10, and K11. Lines are also produced by connecting keypoints with straight lines. Areas are then defined in terms of both straight and curved lines at the boundaries. Materials are assigned to areas. Sources are then added. Convection cooling boundary conditions complete the picture. The model is then meshed with model points and ANSYS then calculates the temperatures at all node points.

III. Test Cases

A. 'Circle'

1. Description

We have a two dimensional case in which a circle is heated by radiation on its surface and is convectively cooled (see Figure 1 and Table 1) at its perimeter by a surrounding liquid.

2. Analytical Solution

First, find the temperature at the edge of the circle.

For convection cooling,

$$\dot{Q} dV = H(T_1 - T_2) \quad (A)$$

$$\dot{Q} \pi r^2 = H(2\pi r) (T_{edge} - T_{bulk})$$

$$Q = 10^7 \text{ W/M}^3$$

$$H = 10^4 \text{ W} \cdot \text{m}^{-1} \cdot \text{K}^{-1}$$

$$T_{bulk} = 100 \text{ K}$$

$$T_{edge} = T_{bulk} + \frac{\dot{Q} \pi r^2}{H(2\pi) r} = 100 + \frac{10^7 (\pi) (10^{-2})}{10^4 (2\pi) (10^{-1})} = 100 + 50 = 150$$

Next, knowing the temperature at the edge of the circle, find the temperature at the center of the circle. In 'circular' coords, we have

$$\frac{1}{r} \frac{\partial}{\partial r} \left(r \frac{\partial \theta}{\partial r} \right) = \frac{-Q}{k}$$

or

$$\frac{\partial}{\partial r} \left(r \frac{\partial \theta}{\partial r} \right) = \frac{-Qr}{k}$$

Integrating, we find

$$r \frac{\partial \theta}{\partial r} = \frac{-Qr^2}{2k}$$

Dividing by r, we get

$$\frac{\partial \theta}{\partial r} = \frac{-Qr}{2k}$$

Integrating a second time yields,

$$\theta_{edge} - \theta_{center} = \frac{-Qr^2}{4k} \bigg|_{r=0}^{r=R} = \frac{-QR^2}{4k}$$

or

$$\theta_{center} = \theta_{edge} + \frac{QR^2}{4k}$$

The constants are:

$$R = .1 \text{ m}$$

$$k = 300 \text{ W. m}^{-1} \cdot \text{K}^{-1}$$

$$Q = 10 \times 10^6 \text{ W/m}^3$$

$$\theta_{edge} = 150 \text{ K}$$

Substituting, we find:

$$\theta_{center} = 150 + \frac{(10^7)(10^{-2})}{4(300)} = 150 + \frac{10^3}{12} = 150 + 83.33 = 233.33$$

3. ANSYS Solution

$$\theta_{edge} = 149.8 \text{ K}$$

$$\theta_{center} = 233.3 \text{ K}$$

B. 'Shape' (Case TA10)

This case consists of a solid hexagon with circular holes (Figure 2 is a 30 degree section and Table 2 lists the dimensions). The material is a perfect conductor (infinite conductivity) and the holes are channels through which coolant flows.

1. The Area of Material

The area of the hexagon with no holes is

$$A_{Hex} = [6] [\frac{1}{2}(\text{base})(\text{height})]$$

for the 6 triangles which make up the hexagon.

The area of the hexagon also can be expressed as:

$$A_{Hex} = \frac{\sqrt{3}}{2} p^2$$

where p is the pitch. For our case, $p = .08791 \text{ m}$

$$A_{Hex} = \frac{\sqrt{3}}{2} (.08791)^2 = 66.93 \times 10^{-4} \text{ m}^2$$

Now we calculate the area of the holes. The large central hole has a radius of 3.00 cm and the other 42 holes have a radius of .17 cm

$$A_{Holes} = \pi [(.0300)^2 + 42(.0017)^2] = 32.09 \times 10^{-4} \text{ m}^2$$

The energy balance is $E_{in} = E_{out}$, or

$$(Q) (A_{rad}) = \sum_{i=1}^{NMAT} (H) (L_{conv}) (T_{Bulk} - T_{surf})$$

where:

Q is the radiation energy density

A_{rad} is the area subjected to the radiation

Index (i) is over all solid materials

T_{bulk} is the bulk temperature of the coolant

T_{surf} is the surface temperature of the solid material

The temperature throughout the solid material is the same as the surface temperature. For simplicity, we set the conductivity to infinity. (Therefore, all the material will be at the same temperature.) The parameters for this test case are listed in Table 2. Evaluation of this equation yields:

$$\left(7 \times 10^8 \frac{W}{m^2}\right) [(66.93 - 32.09)^2 \times 10^{-4} m^2] = \\ [(4.78910^4)] \cdot [(2\pi) (.03000)] [-120 + T_{surf}] + \\ 42 [(5.275E4) (2\pi) (.0017)] [-75 + T_{surf}]$$

which yields $T_{surf} = 162.03K$. The ANSYS result is 161.993. With the results of the two test cases, we conclude that we are using ANSYS correctly and are getting accurate results (local file name TA10).

Also, the size of the mesh was varied from two to 12 line segments per element for the Test Case No. 1 (element type #35) but the final temperatures varied by less than one degree. So we conclude that the mesh density is not significant for temperature calculations for our type of model.

IV. The Actual Case

A. Description

We are concerned with a reactor which will power a rocket on a mission to Mars. The particular study at hand is the temperature distribution of the moderator of that reactor. The design of that moderator is in a state of flux (the pun is intended). Nevertheless, we have chosen one particular design with specific materials and dimensions. The moderator is in the shape of a hexagonal solid with a co-axial cylinder in which the fuel element will be placed. The analysis was performed in two dimensions on a "slice" of the moderator. The "slice" is made perpendicular to the axis of the moderator and, therefore, is a hexagon with a circle at its center. A 30-degree section is shown in Figure 3. The material of the moderator is the element Be with some 7LiH imbedded within it. Both these materials moderate and reflect the neutrons emanating from the fissionable fuel. The moderator is convectively cooled with hydrogen flowing through the coolant channels. The large circle located at the center of the hexagon is the outside of a cylindrical shell (or in two dimensions, a circular ring) of hydrogen flowing between the enclosed circular fuel element and the circular inside surface of the moderator. The other (smaller) circles represent the channels through which other streams of hydrogen flow (at a different temperature) to cool the moderator. The materials and dimensions used are listed in Table 3.

B. Results

The temperatures calculated with the ANSYS program are displayed graphically in Figure 4 including temperature contours. The range is from 134 to 426 K and the materials can withstand these calculated temperatures (Local file name TA3F).

Table 1

Case	'Circle'
(Local File Name)	('CIRCLE')
Material	Beryllium (Be)
Radius	.1 m (=10 cm)
Be Thermal Conductivity	300 W·m ⁻¹ ·K ⁻¹
Radiation Heat Deposition	1 x 10 ⁷ W·m ⁻³
Peripheral Coolant Channel	-
Film Coef.	1 x 10 ⁴ W·m ⁻² ·K ⁻¹
Bulk Temperature	100 K

Table 2

Case	'Shape'
(Local File Name)	'TA10'
Predominant Material	Fictitious
Inner Radius	.03000 m
Outer Pitch	.08791 m
Thermal Conductivity	$1 \times 10^{10} \text{ W}\cdot\text{m}^{-1}\cdot\text{K}^{-1}$
Radiation Heat Deposition	$7.0 \times 10^8 \text{ W/m}^3$
Coolant Channel No. 1 (Larger; Central)	
Radius	.03000 m
Film Coef.	$4.789 \times 10^4 \text{ W}\cdot\text{m}^{-2}\cdot\text{K}^{-1}$
Bulk Temperature	120 K
Coolant Channels No. 2 Through No. 6 (Smaller)	
Radii (Of All)	.00170 m
Film Coef. (Of All)	$5.275 \times 10^4 \text{ W}\cdot\text{m}^{-2}\cdot\text{K}^{-1}$
Bulk Temperature (Of All)	75 K
No. 2 Center (R; θ)	.03846 m; 0 deg
No. 3 Center (R; θ)	.04805 m; 0 deg
No. 4 Center (R; θ)	.03370 m; 17 deg
No. 5 Center (R; θ)	.04141 m; 17 deg
No. 6 Center (R; θ)	.04026 m; 30 deg

Table 3

Case	Actual Case
(Local File Name)	'TA3F'
Materials	Mostly Be, some ⁷ LiH
Thermal Conductivity (Be)	450 W·m ⁻¹ ·K ⁻¹
Thermal Conductivity (⁷ LiH)	11.0 W·m ⁻¹ ·K ⁻¹
Inner Radius	.0300 m
Outer Pitch	.0879 m
Radiation Heat Deposition	7.4 x 10 ⁸ W/m ³
Coolant Channel No. 1 (Larger)	
Radius	.0300 m
Film Coef.	4.789 x 10 ⁴ W·m ⁻² ·K ⁻¹
Bulk Temperature	120 K
Coolant Channels No. 2 Through No. 6	
Radii (Of All)	.00170 m
Film Coef (Of All)	5.275 x 10 ⁴ W·m ⁻² ·K ⁻¹
Bulk Temperature (Of All)	75K
No. 2 Center (R;θ)	.03846 m; 0 deg
No. 3 Center	.04805 m; 0 deg
No. 4 Center	.03370 m; 17 deg
No. 5 Center	.04141 m; 17 deg
No. 6 Center	.04026 m; 30 deg
No. 1 ⁷ LiH, Center (R;θ)	.03846 m; 0 deg
No. 1 ⁷ LiH, Inner and Outer Radius of Ring	.0017 and .00689 m
No. 2 ⁷ LiH, Center (R;θ)	.0075 m; 23 deg
No. 2 ⁷ LiH, Radius of Circle	.00172 m

REFERENCES

1. Hildebrand, F. B., Advanced Calculus For Engineers, Prentice-Hall, Inc., Englewood Cliffs, NJ, 1949.
2. ANSYS, ANSYS Primer For Thermal Analysis For Revision 4.4, Swanson Analysis Systems, Inc., June 21, 1991.
3. ANSYS-B, ANSYS Primer For Stress Analysis For Revision 4.4, Swanson Analysis Systems, Inc., June 21, 1991.
4. Rao, S. S., The Finite Element Method In Engineering, Pergamon Press, Elmsford, NY, 1982.

APPENDIX A


```

/title,ta3d(si)
/show,340
/plot
/plot,kpoi,1
/plot,line,1
/plot,area,1
c**constants
pi=3.1415927
dtr=pi/180.
c**user constants. start.
p= .01*8.791
r0=.01*3.00
r1=.01*.689
r2=.01*.172
r3=.01*.17
d1=.01*.157
d2=.01*.1
d3=.01*.1
d4=.01*.2
d5=.01*.2
d6=.01*.45
d7=.01*.2
s=p/sqrt(3.)
deg1=17.
deg2=23.
deg3=30.
c** user constants. end
c** calculated parameters. start.
c** level zero. (base level) #####
k,1,0.,0.,
temp=r0
k,2,temp
temp=temp+d1+r1
k,3,temp
temp=temp+r1+d2+r3
k,4,temp
temp=temp+r3+d3
c**note. at this point, 'temp' .se. 's' (side)
k,5,temp
f10=temp
f13=f10*cos(deg3*dtr)
f12=f13/cos((deg3-deg2)*dtr)
f11=f13/cos((deg3-deg1)*dtr)
csys,1
c** level i. (at deg1; first level above base) #####

```

```
temp=r0
k,6,temp,deg1
temp=temp+d4+r3
k,7,temp,deg1
temp=f11-r3-d5
k,8,temp,deg1
temp=f11
k,9,temp,deg1
c*** level 2. (at deg2; 2nd level above base) #####
temp=r0
k,10,temp,deg2
temp=temp+d6+r2
k,11,temp,deg2
temp=f12
k,12,temp,deg2
```

```

c** level 3. (at deg3; 3rd level above base) #####
temp=r0
k,13,temp,deg3
temp=f13-r3-d7
k,14,temp,deg3
temp=f13
k,15,temp,deg3
circle,3,r3
circle,3,r1
circle,4,r3
circle,7,r3,,1
circle,8,r3,,1
circle,11,r2,,1
circle,14,r3,,1
csys,0
/menu,main
kplot

```

FIGURE 1

FIGURE 2

FIGURE 3

END

**DATE
FILMED**

3 / 26 / 93