NOTICE

**CERTAIN DATA
CONTAINED IN THIS
DOCUMENT MAY BE
DIFFICULT TO READ
IN MICROFICHE
PRODUCTS.**

BEAM TRACKING OF SXLS WITH REALISTIC MAGNETIC FIELD

Yun-Xiang Huang

September 1991

NATIONAL SYNCHROTRON LIGHT SOURCE

**BROOKHAVEN NATIONAL LABORATORY
ASSOCIATED UNIVERSITIES, INC.**

Under Contract No. DE-AC02-76CH00016 with the

UNITED STATES DEPARTMENT OF ENERGY

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, nor any of their contractors, subcontractors, or their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency, contractor or subcontractor thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency, contractor or subcontractor thereof.

BEAM TRACKING OF SXLS WITH REALISTIC MAGNETIC FIELD

Yun-Xiang Huang*
University of Houston
Houston, Texas

September 1991

*Visited NSLS July 1991

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

BEAM TRACKING OF SXLS WITH REALISTIC MAGNETIC FIELD

Introduction

In early 1977, while working for NSLS at Brookhaven National Lab., Dr. Ohnuma noticed that tunes of NSLS calculated with code SYNCH were significantly different from those obtained with code PATRICIA^[1]. This problem surfaced again in 1991 when people at BNL discovered discrepancies in their compact ring SXLS chromaticities calculated with different codes, as shown in Table 1.

One potential source of the ambiguities is the different treatment of the edge field and the combined function field of dipole magnet. Fig. 1 shows the outline of the SXLS lattice structure(not to scale). There are two dipoles each of which with the bending angle of 180° instead of at most a few degrees which is common in high energy synchrotrons. The calculation of a three-dimensional field using TOSCA indicates that the fringe field extends to cover the whole region between the dipole and the quadrupole, having a vertical field strength of 250 gauss at the edge of the quadrupole. In this case, the fringe multiple field will undoubtedly play a nontrivial role in determining basic machine parameters. Therefore, the classical treatment for simulating particle motion in synchrotron, which uses the isomagnetic approximation plus thin lens kicks, no longer accurately models the closed orbit of the machine. In order to correctly calculate tunes, chromaticities as well as the dynamic aperture in such kind of machine with a large magnetic bending angle, it is necessary to integrate the exact equations of motion in a realistic representation of the magnetic field.

The Integration Code--COMSYN

For a long-term tracking calculation, a canonical integration technique is desirable in order to preserve the canonical character of equations of motion.

But this is presently limited to the motion where the magnetic field can be described by only one component of the vector potential. Otherwise it might be difficult to obtain an explicit symplectic map^[2].

We developed a computer code COMSYN, which employs an improved 4th order Runge-Kutta procedure to integrate the exact equations of motion. The magnetic field is either measured directly or computed by running a three dimensional code. It is not symplectic, but the tolerance of the truncation error has been selected so as not to accumulate the error to affect the results. The computational accuracy of this code was tested by tracking the reference particle in SXLS for over 10^4 turns. The departure of the particle from the ideal orbit is within 10^{-8} meter and 10^{-12} rad(see: attached Table 2). This code was also tested by comparing its calculation results of lattice parameters with those from the codes MAD and DIMAD in an isomagnetic approximation. All of them are in a good agreement. Fig.2-9 and Table 3-4 give the computational results calculated by COMSYN and Table 5 gives some of the linear lattice parameters computed by other code. In those calculations, the deviation of the matrix determinant from unity is less than 10^{-8} for horizontal motion and 10^{-12} for vertical motion. It turns out the distortion of this code from the exact symplecticity is negligible.

The choice of rectangular frame and time as the independent variable makes the equations take the following form:

$$\ddot{x} = \frac{e}{m}(B_z \dot{y} - B_y \dot{z})$$

$$\ddot{y} = \frac{e}{m}(B_x \dot{z} - B_z \dot{x})$$

$$\ddot{z} = \frac{e}{m}(B_y \dot{x} - B_x \dot{y}).$$

Due to the simplified form of these equations, the CPU time is significantly

reduced. With 600 integration step in each superperiod, it takes about 10 minutes to track a particle over 1000 turns in the realistic 3-D field on a CRAY.

Beam Tracking of SXLS in Realistic Field

A 3-D code TOSCA is used to calculate the magnetic field along the particle orbit including the magnetic fringe area. Then five particles with different initial condition are tracked over one superperiod. Using Courant-Snyder parameter matrix, all lattice functions are derived which are shown in Table 6. The corresponding results computed by Roy Blumberg using similar method are also shown in Table 6. It can be seen that two columns are in very good agreement.

However, a major obstacle in the calculation of beam dynamics aperture has been the extensive CPU time required by TOSCA. To make such a study possible a spline procedure has been employed to create a magnetic field fit based on the TOSCA generated mesh field. Table. 7 shows the expression of three field components used to fit the dipole field up to 14th order. The accuracy of the fitting procedure was checked which is shown in Table 6. As the result, the CPU time has been greatly reduced, from 12 minutes per turn to 8 second/turn.

With the fitted magnetic field the dynamic aperture of SXLS has been calculated, as shown in Figs.10. The rectangle in Fig.10 represents the size of beam pipe. It can be seen that the aperture is even smaller than the beam pipe at some part. Fig.11 shows the corresponding result of the dynamic aperture calculated by KRACKPOT, an integration code which uses two-dimensional isomagnetic field, plus thin kick approximation for higher order terms. It indicates that the size of the dynamic aperture obtained by code COMSYN is only one third of that by KRACKPOT. If the longitudinal field component is removed from the TOSCA field in our calculation using COMSYN, the aperture can be increased by 30%. If the fringe field is removed and the same combined function field is used inside the dipole, then an aperture with the same size as

that by KRACKPOT can be obtained from our calculations. Therefore, the significant difference in aperture size should be caused from effects of the fringe field and the longitudinal field component both of which have been omitted by KRACKPOT.

A further study has also been carried out by tracking three particles (particle 1, 2, 3 denoted in fig. 10) with the different initial amplitude over one thousand turns. The fast Fourier transform method is then used to find their tunes. The result is shown in Fig. 12. In the tune diagram, P_0 is the originally designed operating point, but the practical operating point using the TOSCA-generated field is located at P_1 . The points P_2 and P_3 represent the operating points for particles 2 and 3 in Fig. 10, respectively. It can be seen that as the amplitude of particle increases its tunes shift to smaller values, and eventually fall within the area of dense resonance lines. This is probably one reason for the poor beam dynamic aperture of SXLS. One cure of this problem is to move the designed operating point along an opposite direction to the shift of tunes so as to provide a larger space for the change with particles of big amplitude. An example is given in Fig. 10, where the operating point has been moved to $\nu_h = 1.28$ and $\nu_v = 0.48$ and the resultant aperture is increased by as much as to 30%. Figs.13 and 14 give the vertical tune spectrum analysed by FFT method for a particle with the same amplitude and the different operating point. A larger tune split can be observed with the particle at the operating point P_1 ($\nu_h = 1.415$, $\nu_v = 0.405$). Figs.15 and 16 show the phase space in the horizontal and vertical motions. A large smear can be seen in the vertical space. This is consistent with the FFT analysis described above. A more detailed study will be performed based on the new current setting for the dipole and TOSCA-generated field.

Acknowledgements

We should like to thank Steven Kramer, Roy Blumberg and Jim Murphy of

Brookhaven National Synchrotron Lab for useful discussion and especially for providing field data.

References

- [1] S. Ohnuma, Fermilab internal report (1983).
- [2] Ronald D. Ruth, A Canonical Integration Technique , IEEE Trans on NS, Vol. NS-30, No. 4, Aug 1983.

Work performed under the auspices of the U.S. Department of Energy,
under Contract No. DE-AC02-76CH00016.

2.7. Chromaticity Correction

The calculation of the 'correct' chromaticity of a small storage ring with a combined function dipole magnet ($n \neq 0$) is to some degree an open question. Table 2.11 indicates the differences in the chromaticities for the SXLS as calculated by several of the standard lattice codes.

Code	ξ_x	ξ_y
Beta	-.46895	+.1625
Dimad	-.46895	-1.28953
Leda	-.49	-1.32
Mad	-.46896	-1.28953
Marylie	-.376	-1.97
Patricia	+.3479	-.4981
Synch	-.469	-1.29

∴ SXLS Chromaticity

Table 1. SXLS Chromaticity computed by
several standard codes

Fig. 1

SXLS

Ring-Centered Cylindrical Coordinate System
Not To Scale
Dimensions In Meters

June 17, 1991, a test of the computational accuracy by tracking
the reference particle in a uniform magnetic field.

*****

Input Data

*****

#QSUB -1M 7MW

#QSUB -1T 01:00:00

#QSUB -eo

ja

cd huang

procstat -R rawfile bnltest2<<EOF

H

B

DA

O

1

0 10000 1 2

500

Stop no. each half superperiod

1.D-13 10.

Error requirement fitting magnet boundary

5 0.0525D0 0.126D0 0.2035 0.281D0 1.1775D0 Boundary No. and position

2.291994537277119D0 1.314863714D0

Initial Betax and Betay

696.D0 0.D0 1.D-03 Designed energy and Momentum dispersion

-3.85D0 0.4433062359D0 4.7058143D0 0.D0 43.099480D0

0.D0 0.D0 0.D0 0.D0 0.D0

EX

EOF

ja -cst

*****

No.	X(meter)	X' (rad)	Turns

*****

1, 2*0., 1

1, -7.176481631177E-13, -1.4327544258063E-12, 2

1, 1.2258993820069E-10, -3.8458970097187E-13, 200

1, 8.7165901163644E-9, 6.0127681845102E-12, 1000

1, 1.8981904048587E-8, 4.0033748907087E-12, 2000

1, 2.6625709637074E-8, 5.1503072555563E-12, 3000

1, 1.8759418907166E-8, -5.2509147941445E-12, 4000

1, 9.1321723516558E-9, -7.0055918064421E-12, 5000

1, -1.9314363441936E-9, -7.1472024287898E-12, 6000

1, -1.1992852932963E-8, -6.5251149680806E-12, 7000

1, -2.2391628107243E-8, -7.7275165970469E-12, 8000

1, -3.1123057908644E-8, -7.0109618320894E-12, 9000

1, -4.1784083748553E-8, -7.7406018672398E-12, 10000

1, -5.1517648813615E-8, -3.4992120155855E-12, 11000

1, -4.3388997283955E-8, 5.0992006095656E-12, 12000

1, -4.0610821372411E-8, 4.7282234214615E-12, 13000

1, -3.0691762020751E-8, 5.8184931750379E-12, 14000

1, -2.009940658354E-8, 3.3483614630163E-12, 15000

1, -9.9030081912588E-9, 7.8174461665252E-12, 16000

1, -4.766672390133E-9, 5.5558559455749E-12, 17000

1, 4.8056563173304E-9, 5.5816779954484E-12, 18000

1, 8.1139077678927E-9, 6.9218095065671E-12, 19000

1, 1.7350924252924E-8, 6.4406978698799E-12, 20000

*****

CPU with CRAY:1216.362s

damping 7×10^4 turns

Table 2. Deviation of the Reference particle from the
Ideal Orbit as Function of Turn Number

Fig. 2

Fig. 3

Lattice Functions With Hard Edge

Fig. 4

Lattice Functions With Hard Edge

Fig. 4


```

=====
*****Tune Calculation with Iso-Mag. Field*****
                        June 18, 1991
=====
-----
x0,y0 (mm)  x0',y0' (mrad)  tuneX      tuneY      |detx-1|  |dety-1|
-----
MATRIX by tracking 4 particles for half superperiod

1.D-01      1.D-01      1.41520025    0.414614544  4.7d-05  3.6d-07
1.d-02      1.d-02      1.41508197    0.414614408  2.3d-06  3.6d-09
1.d-03      1.d-03      1.41507175    0.414614407  1.5d-06  7.5d-13
1.d-04      1.d-04      1.41509099    0.414614407  1.3d-06  6.2d-12
#####

FFT  by tracking a particle for 8192 turns

1.d-03      1.d-03      1.41505788    0.41462031

```

Table. 3. Calculated tune value as a function of the initial departure δ of the chosen 4 particle from the reference orbit. Also shown in the table is the departure of matrix determinant from unit. It turns out that the distortion of the tracking calculation to symplecticity is negligible.

Tune Computation by FFT (8192 turns) with I_{omag} -field

Tune Y (y0=1. d=03mm)

Fig. 5

Tune X

Fig. 6

Phase Space Calculation with Isomag. Field

Fig. 7

Vertical phase Space with Isomagnetic Field

Fig.8 $Y (X_0 = 18 \text{ mm}, Y_0 = 7 \text{ mm}) \text{ [mm]}$

```

=====
*****Synchrotron radiation integrals*****
=====
I1= 2.7494728342385 I2= 10.411982599195 I3= 17.253888966319
I4= 5.1124504188900 I5= 5.5336284015466

Emittance= 7.4227324175395d-07 ENERGY SPREAD= 6.8767651743784d-04

Damping Time of Stored Beam
Tx= 2.2643687347601 Ty= 1.1527818979363 Te= 0.46277578363523

Damping partition function
JX= 0.50098396437062 JE= 2.4910160356294

```

```

=====
*****Matrix for one superperiod*****
=====

(DR, PHI) (mm, deg.) =, #6 0.31454133887743 -8.9299559222181d-10

      BH11      BH12      BH21      BH22
-0.26289109 -2.21048107 0.42110696 -0.26289109
      BV11      BV12      BV21      BV22
0.26340188 1.55069808 -0.60012936 0.26340188

```

```

=====
*****Output of Lattice Functions*****
=====

DDETBH= -3.9308732322663d-05 DDETBV= 6.9386829615325d-11
TUNEX= 1.4153240092474 TUNEY= 0.41515547705636
BETAX0= 2.2911293077595 BETAXF= 0.37059143207709
BETAY0= 1.6074637441828 BETAYF= 6.7788477344613
ETA0= 1.26073280 ETAF= 0.31454133887743

```

Table 4. Lattice Parameters calculated by
COMSYN

Dynamic Aperture with Isomagnetic Field

Fig 9

Machine Phase	Phase I	Phase II
Energy, E [MeV]	200	696
Dipole Magnet Type	EM	SC
Dipole Field, B_0 [T]	1.1	3.85
Bending Radius, ρ [m]	.6037	
Field Index, n	.1759	
Lattice Structure	FODO-like	
Superperiods, N_s	2	
Circumference, C [m]	8.503	
Critical Wavelength, λ_c [Å]	423	10
Number of Superperiods	2	
Horizontal Betatron Tune, ν_x	1.415	
Vertical Betatron Tune, ν_y	.415	
Energy Loss Per Turn, U_0 [KeV]	.234	34.4
Natural Energy Spread, σ_{E0}	2.0×10^{-4}	6.9×10^{-4}
Damping Partition Numbers, J_x, J_y, J_e	.53, 1., 2.47	
Damping Times, τ_x, τ_y, τ_e [ms]	91, 48, 20	2.16, 1.15, .46
Uncorrected Chromaticity, ξ_x, ξ_y	-.49, -1.32	
Momentum Compaction, α	.32	
Natural Emittance, ϵ [m-rad]	5.92×10^{-8}	7.17×10^{-7}

SXLS Storage Ring Parameters

Table 5. Lattice parameters calculated by
Standard code

July 4, 1991, Parameters for SXLS results using TOSCA and 14th order
fit coefficients generated from TOSCA data.

*****

	ROY (TOSCA)	<u>YX (TOSCA)</u>	<u>YX (FIT)</u>	ERR (YX)	ERR (ROY)
=====	=====	=====	=====	=====	=====
E (MeV)	699.29114	698.7801394	698.780467	3.3d-04	
TuneH	1.415	1.41502944	1.41503188	2.4d-06	
TuneV	0.406217	0.40616711	0.4058189	3.5d-04	5.2d-04
BtaH0	2.478477	2.47880619	2.478453	3.5d-04	5.1d-04
BtaHf	0.43633064	0.43621742	0.43612726	9.0d-05	1.0d-04
BtaV0	1.570694	1.57095103	1.57287098	1.8d-03	2.8d-03
BtaVf	7.310962	7.3114391	7.31409022	2.6d-03	5.3d-03
Eta0	1.40917	1.4125244	1.412322	2.0d-04	
Etaf	0.267549	0.266212102			
KsiH	-1.16815	-1.165224			
KsiV	1.34504	1.3150214			

Table. 6. A Comparison of Lattice Parameters
Using TOSCA - Generated Field and Fitting Field.

```

bz0=c(1,1)+c(1,2)*x1+c(1,3)*x2+c(1,4)*x3+c(1,5)*x4+c(1,6)*x5
+      +c(1,7)*x6+c(1,8)*x7+c(1,9)*x8+c(1,10)*x9+c(1,11)*x10
+      +c(1,12)*x11+c(1,13)*x12+c(1,14)*x13+c(1,15)*x14
+      +z2*(c(3,1)+c(3,2)*x1+c(3,3)*x2+c(3,4)*x3+c(3,5)*x4
+          +c(3,6)*x5+c(3,7)*x6+c(3,8)*x7+c(3,9)*x8+c(3,10)*x9
+          +c(3,11)*x10+c(3,12)*x11+c(3,13)*x12)
+      +z4*(c(5,1)+c(5,2)*x1+c(5,3)*x2+c(5,4)*x3+c(5,5)*x4
+          +c(5,6)*x5+c(5,7)*x6+c(5,8)*x7+c(5,9)*x8
+          +c(5,10)*x9+c(5,11)*x10)
+      +z6*(c(7,1)+c(7,2)*x1+c(7,3)*x2+c(7,4)*x3+c(7,5)*x4
+          +c(7,6)*x5+c(7,7)*x6+c(7,8)*x7+c(7,9)*x8)
+      +z8*(c(9,1)+c(9,2)*x1+c(9,3)*x2+c(9,4)*x3+c(9,5)*x4
+          +c(9,6)*x5+c(9,7)*x6)
+      +z10*(c(11,1)+c(11,2)*x1+c(11,3)*x2 +c(11,4)*x3
+            +c(11,5)*x4)
+      +z12*(c(13,1)+c(13,2)*x1+c(13,3)*x2)
+      +z14*c(15,1)

```

```

b*x0=z1*(c(1,2)+2*c(1,3)*x1+3*c(1,4)*x2+4*c(1,5)*x3+5*c(1,6)*x4
+
+6*c(1,7)*x5+7*c(1,8)*x6+8*c(1,9)*x7+9*c(1,10)*x8
+
+10*c(1,11)*x9+11*c(1,12)*x10+12*c(1,13)*x11
+
+13*c(1,14)*x12+14*c(1,15)*x13)
+
+z3/3*(c(3,2)+2*c(3,3)*x1+3*c(3,4)*x2+4*c(3,5)*x3+5*c(3,6)*x4
+
+6*c(3,7)*x5+7*c(3,8)*x6+8*c(3,9)*x7+9*c(3,10)*x8
+
+10*c(3,11)*x9+11*c(3,12)*x10+12*c(3,13)*x11)
+
+z5/5*(c(5,2)+2*c(5,3)*x1+3*c(5,4)*x2+4*c(5,5)*x3+5*c(5,6)*x4
+
+6*c(5,7)*x5+7*c(5,8)*x6+8*c(5,9)*x7+9*c(5,10)*x8
+
+10*c(5,11)*x9)
+
+z7/7*(c(7,2)+2*c(7,3)*x1+3*c(7,4)*x2+4*c(7,5)*x3+5*c(7,6)*x4
+
+6*c(7,7)*x5+7*c(7,8)*x6+8*c(7,9)*x7)
+
+z9/9*(c(9,2)+2*c(9,3)*x1+3*c(9,4)*x2+4*c(9,5)*x3+5*c(9,6)*x4
+
+6*c(9,7)*x5)
+
+z11/11*(c(11,2)+2*c(11,3)*x1+3*c(11,4)*x2+4*c(11,5)*x3
+
+5*c(11,6)*x4)
+
+z13/13*(c(13,2)+2*c(13,3)*x1)

```

```

bs=(z1*(d(1,1)+d(1,2)*x1+d(1,3)*x2+d(1,4)*x3+d(1,5)*x4+d(1,6)*x5
+
+d(1,7)*x6+d(1,8)*x7+d(1,9)*x8+d(1,10)*x9+d(1,11)*x10
+
+d(1,12)*x11+d(1,13)*x12+d(1,14)*x13)
+
+z3/3*(d(3,1)+d(3,2)*x1+d(3,3)*x2+d(3,4)*x3+d(3,5)*x4
+
+d(3,6)*x5+d(3,7)*x6+d(3,8)*x7+d(3,9)*x8+d(3,10)*x9
+
+d(3,11)*x10+d(3,12)*x11)
+
+z5/5*(d(5,1)+d(5,2)*x1+d(5,3)*x2+d(5,4)*x3+d(5,5)*x4
+
+d(5,6)*x5+d(5,7)*x6+d(5,8)*x7+d(5,9)*x8+d(5,10)*x9)
+
+z7/7*(d(7,1)+d(7,2)*x1+d(7,3)*x2+d(7,4)*x3+d(7,5)*x4
+
+d(7,6)*x5+d(7,7)*x6+d(7,8)*x7)
+
+z9/9*(d(9,1)+d(9,2)*x1+d(9,3)*x2+d(9,4)*x3+d(9,5)*x4
+
+d(9,6)*x5)
+
+z11/11*(d(11,1)+d(11,2)*x1+d(11,3)*x2+d(11,4)*x3)
+
+z13/13*(d(13,1)+d(13,2)*x1))/(1.d0+h*x1)

```

Table. 7. Expression of 3-D magnetic field components used to fit the dipole field up to 14th order.

DA with Fitted Mag. Field at SF Center

Fig 10

KRACKPOT Tracking: 1000 turns

Fig. 11 Dynamic Aperture Calculated by KRACKDOT

NONLINEAR RESONANCES IN SXLS ν_H - ν_V PLANE NEAR OPERATING POINT $\nu_H=1.415$ $\nu_V=0.415$

--- 3rd ORDER (SEXTUPOLE)
..... 4th ORDER (OCTUPOLE)
-.-.- 5th ORDER (DECAPOLE)

FROM SXLS CDR
MURPHY & VIGNOLA

—...— 6th ORDER (DUODECAPOLE)

Fig. 12

Fig.13 Tune Spectrum by FFT with operation point P1

Tune γ ($x_0 = 25 \text{ mm}$, $y_0 = 10 \text{ mm}$) $\begin{cases} v_x = 1.28 \\ v_y = 0.48 \end{cases}$
 Fig. 14. Tune Spectrum by FFT with operation point

Tune Calculation with Fitted Mag. Field(1024 turns)

Horizontal Phase Space with Fitted Mag. Field

Fig. 15

Vertical Phase Space with Fitted Mag. Field

Fig 16

END

**DATE
FILMED**

2 / 18 / 92