PROGRESS REPORT TO THE DEPARTMENT OF ENERGY

Title of Project: Computer Aided Surface Representation

Grant Number: DE- FG02-87ER25041

Duration of grant: June 1, 1988 - May 31, 1991

Period covered by Progress Report: ~~June 1, 1988 - May 31, 1989~~

Principal Investigator: Robert E. Barnhill
Department of Computer Science
Arizona State University
Tempe, Arizona 85287

Date: February 9, 1989

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

MASTER*EB*

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

TABLE OF CONTENTS

INTRODUCTION: RESEARCH PLAN.....	1
RESEARCH AREAS.....	1
1. Surfaces defined on surfaces.....	1
2. Multivariate visualization.....	1
3. Geometry processing.....	1
4. Invariant metric.....	2
RESEARCH PRESENTATIONS.....	2
FACULTY SUMMARIES:.....	3
R. Barnhill	3
G. Farin	7
T. Foley	10
G. Nielson	15
Research papers and theses supported by DoE grant	26
Research Plans for the Coming Year	28
Appendix:	
Research Plan: Summary of Proposed Research	30
Table of Contents of original proposal.....	31
1988-89 Graduate students and topics	32

Introduction: Research Plan

The central research problem of this project is the effective representation and display of surfaces, interpolating to given information, in three or more dimensions. In a typical problem, we wish to create a surface from some discrete information. If this information is itself on another surface, the problem is to determine a "surface defined on a surface", which is discussed below. Often, properties of an already constructed surface are desired: such "geometry processing" is described below.

The Summary of Proposed Research from our original proposal describes the aims of this research project. This Summary and the Table of Contents from the original proposal are enclosed as an Appendix to this Progress Report.

The broad sweep from constructive mathematics through algorithms and computer graphics displays is utilized in this research. The wide range of activity, directed to both theory and applications, makes this project unique.

Last month the first Ardent Titan delivered in the State of Arizona came to our group, funded by the DoE and Arizona State University. Although the Titan is a commercial product, its newness requires our close collaboration with Ardent to maximize results.

During the past year, four faculty members and several graduate research assistants have worked on this DoE project. The gaining of new professionals is an important aspect of this project. A listing of the students and their topics is given in the Appendix.

The most significant publication during the past year is the book, Curves and Surfaces for Computer Aided Geometric Design, by Dr. Gerald Farin. This 300 page volume helps fill a considerable gap in the subject and includes many new results on Bernstein-Bezier curves and surfaces.

Research Areas

Research progress was made in several areas. Additional detail is given in the faculty summaries in the next section. Some of the most significant research is summarized below:

1. Surfaces defined on surfaces

R. E. Barnhill and S. Ou have developed a new method (using triangular patches) of interpolating on convex regions and are comparing it with earlier work by Bruce Piper (using Dirichlet ules) on the DoE project at Utah. T. Foley has modified a method (Hardy's multiquadric) for interpolation over the sphere. T. Foley, G. Nielson and D. Lane have developed techniques for interpolating data on nonconvex closed surface domains.

2. Multivariate visualization

The computer graphics display of trivariate surfaces is being pursued by B. Hamann, R. Heiland and D. Lane under the direction of T. Foley and G. Nielson. This requires intrinsic use of our interactive computer graphics equipment, the Silicon Graphics 3130, 4D70GT and the Ardent Titan.

3. Geometry Processing

Geometry processing is the extraction of geometric features from an already constructed surface. We have made progress on several topics, including curvature analysis, surface-surface intersection and numerical integration. Curvature analysis has been used as a surface interrogation tool and to determine best twists for bicubic patches. Surface-surface intersections have been extended from rectangular to triangular patches and, in addition, two general algorithms are being compared. The adaptive numerical integration scheme developed earlier has been used to determine additional surface properties and has also been extended to trivariate surfaces.

4. Invariant metric

Many surface algorithms implicitly depend upon the units of measurement. Nielson has developed a metric that is invariant in the sense that it is independent of the units of measurement. Nielson and Foley have been applying this new affine invariant metric to a variety of methods and techniques used for the representation and design of curves and surfaces; including scattered data interpolation, knot spacing problems for spline interpolation, and triangulations and tessellations.

Research Presentations

Presentations during the past year include the following: Dr. Robert Barnhill spoke at the Mathematical Sciences Chair meeting in Washington, D. C. in November, 1988, on the Computer Aided Geometric Design Group's research. He also gave an invited talk, on adaptive cubatures, at the Mathematics of Surfaces III conference in Oxford in September and the keynote lecture for "CAGD Day" at the Texas Approximation Theory Conference in January, 1989. Two other members of our Group spoke at the Texas conference: Dr. Tom Foley on Surface Interpolation with Shape Controls and Mr. Steve Watson on Adaptive Numerical Multiple Integration Methods. The four CAGD faculty, Drs. Barnhill, Farin, Foley and Nielson all spoke at the Mathematical Methods in CAGD conference in Oslo, Norway in June. In June, Drs. Barnhill and Farin participated in the CAGD conference in Jerusalem and spoke on triangulation methods and B-splines, respectively. Foley spoke on interpolation of scattered data over a spherical domain at the Conference on Algorithms for Approximation '88 at the Royal Military College of Science, England. The four CAGD faculty also gave a six hour tutorial at SIGGRAPH in Atlanta and included multidimensional methods and geometry processing therein. G. Farin presented curvature analysis methods at the 1988 MIT Sea grant symposium and chaired the "surfaces" sessions of the 1988 IFIP workshop on Geometric Modeling.

Future significant meetings include "Surfaces in CAGD" at the Mathematics Institute, Oberwolfach, F. R. Germany in which the CAGD faculty will present their research and the SIAM meeting on Geometric Design, to be held in Tempe, Arizona, in November, 1989. This continuation of the SIAM series of meetings on Applied Geometry held at RPI is chaired by Dr. Barnhill with Drs. Farin, Foley and Nielson organizing various sessions at the meeting. The SIAM meeting, with probably some 500 participants, will include a visit to the CAGD Lab.

Drs. Barnhill, Foley and Nielson visited Sandia National Labs to initiate a collaboration there. We are developing some demonstration software for Ardent, which will publicize our multidimensional methods. Drs. Foley and Nielson are collaborating with DoE researchers at the Lawrence Livermore Labs.

Faculty Summary for DoE Grant Robert E. Barnhill

My principal research areas during the past year have been Surfaces on Surfaces and Geometry Processing.

Surfaces Defined on Surfaces

I invented the phrase "surfaces defined on surfaces" several years ago to describe the construction of (higher dimensional) surfaces defined on physical objects. My students and I, at the University of Utah, developed several methods for interpolating to data given on a surface. (Barnhill, Piper, and Stead, '85), (Barnhill, Makatura, and Stead '87), (Barnhill, Piper, and Rescorla, '87). By the time of my move to Arizona State University in late 1986, I wanted both to develop new methods for this problem and to compare existing methods. Thus I selected S. Ou to work on this problem. We have developed a new method for interpolating on convex regions, which involves triangular patches and geodesic distances. Simultaneously we are comparing this method with Piper's method (Barnhill, Piper, and Rescorla, '87) which utilizes a generalized Shepard's Formula with Dirichlet tessellated domains of data dependence and geodesic distances. Our introduction of the new method and comparison with the old will be presented at the Surfaces on CAGD symposium at the Mathematics Institute, Oberwolfach, in April, 1989. It will also comprise Ou's Master's thesis at Arizona State University. After Ou graduates, this research will be continued by D. Wang who has just come from the New York Institute of Technology to join the CAGD group.

The topic of Surfaces on Surfaces is so important that we have two groups working on it. (See Foley's summary.) A future plan is to catalog comparisons of the various methods.

Contours of four dimensional surfaces

Multidimensional surfaces and in particular four dimensional surfaces can only be displayed indirectly. Our best idea at Utah was to look at contours of trivariate surfaces, which are themselves three dimensional surfaces. This project is continuing and B. Bloomquist is enhancing the algorithm to use the Clough-Tocher trivariate interpolant announced by A. Worsey.

Geometry Processing

G. Farin and I invented the term "geometry processing" to describe the calculation of geometric properties of already constructed curves and surfaces. Several new developments in geometry processing can be reported.

Curvature Analysis

For curves, Farin and others at Utah developed curve smoothing algorithms utilizing curvature plots. The corresponding surface idea is to examine the curvatures of a surface. The traditional curvature studied has been Gaussian curvature, perhaps because of its ease of computation. Fayard's thesis (Fayard, '88) considers two other curvatures, mean and absolute, along with Gaussian curvature. The three curvatures together provide a good interrogation tool. The most used surface type is a network of bicubic patches. Bicubic patches have always been awkward because of the presence of (1,1) derivatives ("twists"). Curvatures correspond to second derivatives. Therefore we used Fayard's curvature analysis to study effective methods of determining twists. (Barnhill, Farin, Fayard, and Hagen, '88).

Surface-surface Intersections

The calculation of Surface-Surface Intersections has many applications, including tolerance checking and computer graphics displays. At Utah we developed a surface-surface intersection algorithm for general rectangular patches (Barnhill, Farin, Jordan, and Piper, '87). There is only one comparably general surface-surface intersection algorithm (Houghton, Emnett, Factor, and Sabharwal, 85). Under my supervision, S. Kersey is making a critical comparison of the two algorithms (Barnhill and Kersey, '89). In addition, Kersey has generalized the algorithm to the case of triangular patches.

Offset Surfaces

Offset surfaces are useful for ensuring that objects have clearance to pass one another, among many applications. The key problem with all published offset surface algorithms is the lack of a robust self-intersection detection for the offset surface. By using our surface-surface intersection on the offset surface, we provide a solution to this problem. I am supervising T. Frost's work on developing a general offset surface algorithm. The interactive computer graphics display of the offset surface is crucial to understanding it.

Numerical Multiple Integration

My 1964 Ph.D. thesis was on numerical integration and the topic has arisen throughout my career. Frank Little and I developed a robust adaptive cubature for bivariate integrals at Utah (Barnhill and Little, '84). Steve Watson and I have extended this algorithm to calculate many surfaces properties such as volumes and moments (Barnhill and Watson, '89). We are currently investigating trivariate cubatures so that we can calculate physical or mass properties of surfaces on surfaces. Watson's forthcoming Master's thesis will contain some of this research.

Triangulations

The problem of triangulating given data sites, perhaps including a nonconvex boundary including holes, in two or more dimensions, has many applications such as finite element analysis and computer graphics rendering models. D. Hansford and C. House have worked on various aspects of this problem (See Farin's description of Hansford's work), particularly the construction of "optimal" triangles. The key idea is a useful definition of "optimal". Currently we are developing data dependent optimal triangulations, which will form the basis for House's Master's thesis.

References:

1. Barnhill, R. E. and G. M. Nielson (1984), Adaptive triangular cubatures, Surfaces, Special issue of Rocky Mountain Journal of Mathematics, editors, January, vol. 14, pp. 53-76.
2. Barnhill, R. E., B. Piper and S. E. Stead (1985), Surface representation for the graphical display of structure data, The Visual Computer, 1, pp. 108-111.
3. Barnhill, R. E. (1987), Geometry processing, American Institute of Astronautics and Astrophysics, proceedings of St. Louis meeting.
4. Barnhill, R. E., G. Farin, L. Fayard and H. Hagen (1987), Twists, curvatures and surface interrogation, Computer Aided Design, pp. 341-346.
5. Barnhill, R. E., G. Farin, M. Jordan and B. R. Piper (1987), Surface/surface intersection, Computer Aided Geometric Design, 4, pp. 3-16.
6. Barnhill, R. E., G. T. Makatura and S. E. Stead (1987), A new look at higher dimensional surfaces through computer graphics, Geometric Modeling, G. Farin, editor, Society for Industrial and Applied Mathematics, pp. 123-129.
7. Barnhill, R. E., B. R. Piper and K. L. Rescorla (1987), Interpolation to arbitrary data on a surface, Geometric Modeling, G. Farin, editor, Society for Industrial and Applied Mathematics, pp. 281-289.
8. Barnhill, R. E. (1988), Geometry Processing: Curvature analysis and surface/surface intersection, Proceedings of "Mathematical Methods in CAGD", Oslo, Norway, Academic Press.
9. Barnhill, R. E. and S. Watson (1988), Geometry processing: Numerical multiple integration, Mathematics of Surfaces III, Oxford University Press, to appear.
10. Houghton, E. G., R. F. Emmett, J. D. Factor, and C. L. Sabharwal (1985), Implementation of a divide-and-conquer method for intersection of parametric surfaces, in: Barnhill, R. E. and Boehm, W., eds., Surfaces in Computer Geometric Design '84, North-Holland, Amsterdam.

Figure 1. Surface-surface intersection of a torus and a triangular patch. The respective domain paths are illustrated beneath the range illustration. (Barnhill and Kersey).

Figure 2. The self-intersection of a rectangular (bicubic) patch, using the surface-surface intersection algorithm of Barnhill and Kersey.

Figure 3. Surface on surface method of Barnhill and Ou applied to a trigonometric function defined on a "torpedo-shaped" domain. Constant contour shading is used to display the results.

Faculty Summary for DoE Grant Gerald Farin

My research during the second half of 1988 focused on the investigation of rational Bézier and B-spline schemes. These are of interest for the DOE since they offer a unified framework for all curve and surface schemes presently employed by DOE labs, in addition to being able to solve several concrete problems.

Three students worked under my direction: P. Rastogi implemented a package for rational Bézier curves and for conic splines, intended as a collection of subroutines to facilitate my own research. P. Chang is completing his Master's thesis on the subject of interpolation by rational B-spline curves. P. Kashyap is implementing my ideas of offsets of conic splines.

L. Fayard completed a M.S. thesis on the use of curvature analyses for surface interrogation - an instance of geometry processing. His research generalized the standard - and - deficient method of considering Gaussian curvature as the analysis tool. An illustration is given on page 8.

D. Hansford has submitted a paper on the neutral case of the min-max triangulation. Since this triangulation has certain numerical advantages, this research is of importance per se; moreover, it may lead to the discovery of an efficient algorithm for computing the min-max triangulation.

Relevant publications from the time period under consideration include:

- The paper [1] gives an overview of existing methods in the field of rational curves and surfaces. It addresses several problem areas, and tries to point out possible solutions.
- The paper [2] addresses two very special problems, namely that of finding the offset of a conic spline and that of smoothing conic splines (i.e., to make a G^1 conic spline into a G^2 conic spline.) The first topic is a standard problem, for instance in the context of ignition of solid fuel rockets (see [5]). The second one is of interest to industrial applications involving design with conic splines, as is typical for the aircraft industry.
- The article with A. Worsey [4] concentrates on the problem of nonunique shape representation in the rational Bézier Form. This problem needs to be solved in order for algorithms to be able to flag two different shape descriptions as actually equivalent. More research is under way concerning the same problem for rational B-splines.
- An article nearing completion is the one with A. Worsey on contouring quadric surfaces [3]. This is a preliminary study that should lead to an efficient algorithm to contour trivariate quadratics, as they arise in multivariate interpolation problems. The contours are represented as rational Bézier quadratics.
- Research is under way (with a preliminary report scheduled for the CAGD symposium in Oberwolfach) concerning a new type of scattered data interpolant. It involves a piecewise rational quadratic parametrization of the plane (according to work by Sibson [6], [7]), combined with the concept of Bézier tetrahedra (see Farin [8] and de Boor [9]). This interpolant works in any dimension and should be easy to contour.
- Another project under consideration (together with D. Hansford) is an algorithm to find the piecewise Bézier representation of Wilson-Fowler splines (a DOE standard) directly. Such an algorithm should be superior to the presently employed techniques that still rely on the original work by Wilson and Fowler [10] (see also Fritsch [11]).

Figure 1: Curvature plots of seemingly flat surface

Figure 2: Curvature plots reveal differences in twist estimation schemes

References

- [1] G. Farin. Curvature continuity and offsets for piecewise conics. *ACM Transactions on Graphics*, 1989, to appear.
- [2] G. Farin. Rational curves and surfaces. In L. Schumaker, editor, *Mathematical Aspects of CAGD*, Academic Press, 1989.

- [3] G. Farin and A. Worsey. Contouring quadratic surfaces, 1989, in preparation.
- [4] G. Farin and A. Worsey. Reparametrization and degree elevation of Bezier curves, 1988. submitted for publication.
- [5] W. Tiller and E. Hanson. Offsets of two-dimensional profiles. *IEEE Computer Graphics and Applications*, 4:36-46, 1984.
- [6] R. Sibson. A vector identity for the Dirichlet tessellation. *Math Proc of the Cambridge Philosophical Society*, 87:151-155, 1980.
- [7] R. Sibson. *A brief description of the natural neighbour interpolant*. Technical Report, Math department, Univ. of Bath, 1980.
- [8] G. Farin. Triangular Bernstein-Bezier patches. *Computer Aided Geometric Design*, 3(2):83-128, 1986.
- [9] C. de Boor, B-form basics. In G. Farin, editor, *Geometric Modeling: Algorithms and New Trends*, pages 131-148, SIAM, Philadelphia, 1987.
- [10] A. Fowler and C. Wilson. *Cubic spline, a curve fitting routine*. Technical Report, Union Carbide, Oak Ridge, 1963. Report Y-1400.
- [11] F. Fritsch. Energy comparison of Wilson-Fowler splines with other interpolating splines. In G. Farin, editor, *Geometric Modeling: Algorithms and New Trends*, pages 185-202, SIAM, Philadelphia, 1987.
- [12] R. Barnhill, G. Farin, L. Fayard, and H. Hagen. Twists, curvatures, and surface interrogation. *Computer Aided Design*, 20(6):341-346, 1988.

Faculty Summary for DoE Grant Tom Foley

My research in 1988-89 focused on "surface on surface" interpolation; shape preserving interpolation, applications of an affine invariant metric, and the visualization of multivariate functions. Much of my work has been joint research with G. Nielson, thus I will discuss the first two areas, and my research in the other two areas is covered in G. Nielson's section.

Surfaces on Surfaces

Given N arbitrary points p_i on a closed surface D and associated real values f_i , we address the problem of constructing a smooth function $F(p)$ defined over all of D which satisfies $F(p_i) = f_i$ for $i = 1, \dots, N$. Applications include modeling other closed surfaces in CAGD and representing functions which estimate temperature or pressure over all of the surface D , based on the given discrete samples. Since the domain of F is a surface and the graph of F can also be considered as a surface, we generally refer to this problem as a "surface on surface" problem.

Researchers: Foley, Nielson, Lane

For the case where the domain D is a sphere, a C^2 interpolant based on geodesic distance was developed by [Foley '89]. The method is a modification of the reciprocal multiquadric approach which applies to 3D data defined on a planar domain. Figure 1 is a rendering of this spherical domain interpolant applied to $N=90$ data points. The transparent surface is the interpolating function projected out radially from the sphere, and the data points are denoted by the radially projected "sticks". Figure 2 represents the same interpolant with color blended contours on the earth's domain surface. The computer graphics research involved with the rendering of surfaces on surfaces was done by Foley, Nielson, and Lane, and it extends the work of [Nielson and Ramaraj '87]. The graphics research has just been completed and we plan to write up the results and publish them this year. The research on the spherical domain interpolant was presented by T. Foley at the Conference on Algorithms for Approximation '88 at the Royal Military College of Science, Shrivenham, England. Another approach for interpolation and approximation of data on a sphere involving a compact support basis similar to B-splines is currently being investigated by Foley and Lane.

Researchers: Foley, Nielson, Lane, Franke, Hagen

T. A. Foley, D. Lane and G. M. Nielson of Arizona State University, in collaboration with R. Franke (Naval Postgraduate School, Monterey, CA), and H. Hagen (Univ. of Kaiserslautern, Kaiserslautern, West Germany), obtained a solution to the surface on surface problem on more general domains. The approach makes use of an effective interpolant over a spherical domain, such as [Nielson and Ramaraj '87], or [Foley '89]. It is assumed that the surface domain D is topologically equivalent to a sphere (genus zero) and that it is defined in one of the following three ways: D is defined by parametric equations over a rectangular or spherical domain; D is defined as a radially projected function over a sphere; or D is described by a discrete set of 3D points which have the star-like property with respect to some center point. In each of these three cases, the general technique conceptually involves mapping the domain D to a unit sphere, solving a corresponding interpolation problem on the spherical domain, and finally mapping the results back to the surface domain D . Using the C^2 spherical interpolant in [Foley '89], we have implemented and tested this technique on a variety of data sets. The method was effective and graphical results from the Silicon Graphics Iris 4D/70 are shown in Figures 3 and 4. The programs have been also implemented on the Ardent Titan, where larger test cases are being generated. We intend to write up the results in the next month and submit the paper for publication.

Figure 1. This is a rendering of the spherical domain interpolant in [Foley '89] applied to $N=90$ data points. The transparent surface is the interpolating function projected out radially from the sphere, and the data points are denoted by the radially projected "sticks".

Figure 2. This is another way to visualize the same interpolant in Figure 1 with color blended contours on the earth's domain surface.

Figure 3. This is a plot of a surface domain D defined by parametric equations representing a surface of revolution. The small rectangles on the surface are the $N=90$ points P_i where function values are sampled.

Figure 4. This is a color blended contour map of the interpolant to the $N=90$ data points generated by evaluating a known test function at the 90 points shown in Figure 3. The interpolant is visually indistinguishable from the known test function.

Shape Preserving Interpolation

Researcher: Foley

A shape preserving interpolant is a function which passes through some given data and retains the intrinsic shape implied by the given data. More precisely, the interpolating function is increasing, decreasing or convex in the regions where the data is increasing, decreasing or convex. An optimization approach to solving this problem was completed and published in [Foley '88]. This approach differs from other methods in that locally monotone data are considered and shape control parameters can be used to modify the function. Figure 5 is an example of this method to data which consists of increasing, decreasing and constant data. A portion of this research was done at Lawrence Livermore National Lab in the summer of 1987, and it was completed at Arizona State University in 1988.

Researchers: Foley, Goodman, Unsworth

In the Fall of 1987, K. Unsworth (Dundee University, Dundee, Scotland) visited Arizona State University under D.O.E. support. In collaboration with T. A. Foley, they worked on a shape preserving method that applies to parametric vector valued data. Together with T. Goodman (Dundee University), this approach has been accepted for publication [Foley, Goodman and Unsworth '89]. This research was presented by K. Unsworth at the Conference on Mathematical Methods in CAGD, Oslo, Norway.

Researchers: Foley, Ely, Hamann, Neuser

D. Neuser completed his M.S. thesis in Computer Science at Arizona State University in 1988 on the related problem of curve and surface interpolation with interactive shape control parameters. This generalization of [Foley '87] uses piecewise quintic polynomials to represent a function which optimizes a norm on the first, second and third derivatives. This technique was presented by T. Foley at the Sixth Texas Symposium on Approximation Theory, and a paper is currently being written that will be submitted for publication in the proceedings. A related paper [Foley and Ely '88], initially written in 1987, was revised and it has been accepted for publication. T. Foley and B. Hamann have begun work on a method which involves interpolation with piecewise quartic curves and surfaces. This technique optimizes a measure of the function's second derivative, and preliminary results appear promising.

References:

1. Foley, T. A. (1987), Interpolation with interval and point tension controls using cubic weighted v-splines, ACM Transactions on Mathematical Software, vol. 13, pp. 68-96.
2. Foley, T. A. (1988), A shape preserving interpolant with tension controls, Computer Aided Geometric Design, vol. 5, pp. 105-118.
3. Foley, T. A. (1989), Interpolation of scattered data on a spherical domain, in Algorithms for Approximation '88, Oxford University Press, to appear.
4. Foley, T. A. and Ely, H. S. (1989), Surface interpolation with tension controls using cardinal bases, Computer Aided Geometric Design, to appear.
5. Foley, T. A., Goodman T. N. and Unsworth, K. (1989), An algorithm for shape preserving parametric interpolating curves with G^2 continuity, in Mathematical Methods in CAGD, Academic Press, to appear.
6. Nielson, G. M. and Ramaraj, R. (1987), Interpolation over a sphere, Computer Aided Geometric Design, vol. 4, pp. 41-57.

Figure 5. a) is the conventional cubic spline interpolant, and b) is the interpolation method of [Foley '88], which preserves local monotonicity and convexity.

Progress Report for DOE Grant Gregory M. Nielson

Since the beginning of last summer, I have been involved in a variety of research projects. On most of these projects, I have collaborated with other faculty and students. Tom Foley and I have worked together on a number of projects. While we interact quite often with most of the students affiliated with the CAGD group, the students that we most often work with are Bernd Hamann, Randy Heiland and David Lane. For the most part, the research I have done falls into the subject areas of Affine Invariant Metric, Multivariate and Volume Visualization, Animation of Rigid Bodies using Splines on Spheres, Terrain Simulation, and Surfaces on Surfaces. The first four of these topics are discussed here and the last is discussed in Foley's section.

Affine Invariant Metric

Researchers: Greg Nielson and Tom Foley

Many of the well known and widely used methods of CAGD are not invariant with respect to affine transformations of the input data. In some cases, this means that if the data is rotated the results of the method do not reflect this rotation in the proper way. In other cases, this means that the choice of the units of measurement used for the input data will have an effect on the results of the method. If inches and seconds are used, the results could be different than if meters and minutes were used. In [Nielson '87], a new way of measuring distance was introduced which allows many (but not all) of the techniques of CAGD to be adjusted so this problem is eliminated. More recently, we have incorporated this new metric along with some ideas and techniques of Tom Foley to yield an effective method of selecting the knots for spline interpolation. These new results were reported by Tom Foley at an international conference on CAGD held in Norway this past summer. A paper [Foley and Nielson, '89] based on this presentation will be included in the proceedings of this conference. Also at this same conference, I presented a survey of the uses of this new affine invariant metric. This paper [Nielson and Foley, '89] will be included in the invited speaker section of the these same proceedings.

Triangulating and tessellating data sets is often an important step in many of the techniques of CAGD. Optimal triangulations are very often desired. Optimal triangulations are often based upon angles which are not invariant with respect to affine transformations of the data. By exploiting the duality between a certain optimal triangulation (cf. Figure 2) and the Dirichlet tessellation (cf. Figure 1) and using our new affine invariant metric we have arrived at a characterization of a new affine invariant, optimal triangulation. I have recently written a paper on this topic and submitted it for publication [Nielson '88].

References:

- Nielson, G. M. (1987), Coordinate free scattered data interpolation, in *Topics in Multivariate Approximation*, L. L. Schumaker, C. Chui and F. Utreras (eds.), Academic Press, New York, 1987, 175-184.
- Nielson, G. M. (1988), Affine invariant triangulations and tessellations, Technical Report TR-88-023, Computer Science Department, Arizona State University.
- Nielson, G. M. and Foley, T. A. (1989), A survey of applications of an affine invariant norm, in *Mathematical Methods in CAGD*, Academic Press, to appear.
- Foley, T. A. and Nielson, G. M. (1989), Knot selection for parametric spline interpolation, in *Mathematical Methods in CAGD*, Tom Lyche and Larry Schumaker, eds. Academic Press, to appear.

Figure 1. The Dirichlet tessellation of a set of points

Figure 2. An optimal triangulation of a set of data points

Multivariate & Volume Visualization

Researchers: Greg Nielson, Tom Foley, Bernd Hamann and David Lane

Since the representation of multivariate surfaces is one of the major thrusts of our group's research, we have been active in developing new techniques for the graphical rendering of multivariate data. Some of these techniques not only apply to multivariate surfaces, they also apply to medical CAT and MR data. Since there is no apparent single method that allows us to fully understand a multidimensional object, we have implemented a suite of methods, many of which we have developed ourselves. We are continuing this research and will eventually publish our results. A sampling of the methods we have developed now follows:

Contouring: For trivariate functions of the form $w = F(x,y,z)$, we have continued the research initiated by Barnhill, Makatura and Stead [Barnhill, et al '87] on visualizing the graph by using contour surfaces. Each 3D surface represents the set of (x,y,z) points that satisfy $F(x,y,z) = w_i$ for some constants w_i . This technique is a generalization of the contouring methods which yield 2D contour curves for a 3D surface. A typical example of some of our current implementations of this type of method is shown in Figure 1.

Cube-method: For this method, a user specified number of "voxels" are displayed in a regular cubical grid (cf. Figure 2). The colors of the vertices of the little cubes represent the value of the trivariate function at this point. Gouraud shading is used for the display of the voxels. It should be pointed out that a static view does not yield much information. The implementation we have allows for the interactive rotation of the total volume domain and this process allows one to effectively assess the behavior of a trivariate function.

Vanishing Cube: This method utilizes transparency in order to allow one to see the graph of a trivariate function. The alpha-buffer on the Silicon Graphics is used. As the walls of the cells become more and more transparent, one can look inside and observe the behavior of the function at interior points. The impact of this method must be observed on the graphics terminal and can not be detected by a static image as shown in Figure 3.

Trace methods: If one variable of a trivariate function is held constant, then standard techniques for displaying bivariate surfaces can be used to view this trace. By simultaneously displaying all three traces (x fixed, y fixed and z fixed), it is possible to assess some aspects of the behavior of the function. If we display these three surfaces in an organized layout and allow the user to interactively select the fixed value for each of the three independent variables, we obtain a rather effective method for viewing trivariate functions. Selecting the three fixed values is equivalent to selecting a point in a cube. We use the triad mouse [Nielson and Olsen, '87] as a 3D input technique to allow the user to select these fixed values. Figures 4, 5 and 6 show examples of this type of method. In Figures 4 and 5, the trace surfaces are displayed and in Figure 6, the trace contours are shown.

References:

Barnhill, R. E., Makatura, G. T., and Stead, S. E. (1987), A new look at higher dimensional surfaces through computer graphics, in *Geometric Modeling: Algorithms and New Trends*, Gerald E. Farin (ed.), SIAM, Philadelphia, pp. 123- 130.

Nielson, G. M. and Olsen, D. R. (1987), Direct manipulation Techniques for 3D Objects using 2D locator devices, in *Interactive 3D Graphics*, Frank Crow and Stephen M. Pizer (eds.), pp. 175-182.

Figure 1. Contour method

Figure 2. Cube-Method

Figure 3. Vanishing-cube Method

Figure 4. Trace Method, Surface, View A

Figure 5. Trace Methods, Surface, View B

Figure 6. Trace Methods, Contour

Animation of Rigid Bodies using Splines on Spheres

Researchers: Greg Nielson and Randy Heiland

This research is concerned with the development of new methods for the animation of rotations. Given a sequence of orientations of an object as shown in Figure 1, the problem is to produce intermediate positions which represent a smooth transition from one to the next as is shown in Figure 2. The method we have recently developed [Nielson and Heiland '88a] utilizes the quaternion representation of a rotation matrix and a new curve interpolation scheme for points on a four dimensional sphere. The spline interpolation for the 4D sphere is a generalization of a new method we have developed for interpolating points on a 3D sphere which is described in [Nielson '89]. It is based upon control points on the surface of a sphere and produces a C^2 curve which remains on the sphere. The construction of this new curve is analogous to cubic B-splines where the individual cubic segments are represented as Bernstein/Bézier curves. The spherical analogs of the Bernstein/Bézier curves are defined by means of a spherical version of the de Casteljau algorithm (see Figure 3) based upon geodesic interpolation on the sphere rather than conventional linear interpolation. The method has been implemented and tested on the SGI 4D70. A typical screen image of this interactive program is shown in Figure 4. We have made a video [Nielson and Heiland '89] which demonstrates the results of this interactive program.

References:

Nielson, G. M. and R. W. Heiland, Interpolation of Rotation Matrices using Quaternions and Splines on a 4D Sphere, submitted

Nielson, G. M. and R. W. Heiland, Splines on a sphere for animated rotations, Video (VHS, 7 minutes), Arizona State University, Tempe, Arizona, 1988.

Nielson, G. M., Bernstein/Bézier curves and splines on spheres based upon a spherical de Casteljau algorithm, Arizona State University Technical Report TR-88-028, 1988

Figure 1. A Sequence of Orientations

Figure 2. Some interpolated orientations

Figure 3. Spherical de Casteljau Algorithm

Figure 4. Typical screen image of interactive program for animated rotations and splines on spheres

Terrain Simulation

Researchers: Greg Nielson, Alex D. Kelley and Michael C. Malin

This research was done in conjunction with Mike Malin of the Geology Department at ASU and a student, Alex Kelley, who worked for Dr. Malin during the time of this research. This is a good example of joint and interdisciplinary research. We were very fortunate to have this research accepted for presentation at the 1988 SIGGRAPH meeting and later published in the proceedings of this conference [Kelley, Malin and Nielson '88]. This research is based on the observation that the major process affecting the configuration and evolution of terrain is erosion by flowing water. Landscapes thus reflect the branching patterns of river and stream networks. The network patterns contain information that is characteristic of the landscape's topographic features. Stream networks are first modelled by using stochastic methods utilizing a small number of initial parameters. The stochastic models are designed to maintain several physical principles known for drainage networks. The eroded surface is represented as a surface under tension [Nielson and Franke '84], using the tension parameters to shape the profiles of valleys created by the stream networks. The model can be used to generate terrain databases for flight simulation and computer animation applications

References:

Kelley, A. D. (1988), Three-Dimensional Digital Simulation of Drainage Basin Development, M. S. Thesis in Computer Science, Arizona State University.

Kelley, A. D., M. C. Malin and G. M. Nielson (1988), Terrain Simulation Using a Model of Stream Erosion, Computer Graphics, Vol. 22.

Nielson, G. M. and R. F. Franke (1984), A method for the construction of surface under tension, Rocky Mountain Journal of Mathematics 14, pp. 203-221.

Figure 1. Drainage Network using Surface in Tension

Figure 2. Typical results of this method

Research Papers and Theses Supported by DoE Grant

1. Barnhill, R. E. (1989), Geometry Processing: Curvature Analysis and Surface-Surface Intersections, Mathematical Methods in CAGD, Tom Lyche and Larry Schumaker, editors, Academic Press.
2. Barnhill, R. E. (1989), A survey of Computer Aided Geometric Design, in Approximation Theory VI, C. Chui, L. L. Schumaker and J. Ward eds., Academic Press, NY, to appear.
3. Barnhill, R. E., Farin, G., Fayard, L., (1988), and Hagen, H., Twists, curvatures and surface interrogation, Computer Aided Design 20, 341-346.
4. Barnhill, R. E. and Kersey, S. N. (1989), Two general methods for surface-surface intersection, preprint.
5. Barnhill, R. E. and Watson, S. H. (1989), Geometry processing: numerical multiple integration, in Mathematics of Surfaces III, Oxford University Press, to appear.
6. Barnhill, R. E. and Ou, S. (1989), Surfaces on surfaces, preprint.
7. Farin, G. (1989), Curvature continuity and offsets for piecewise conics. ACM Transactions on Graphics, to appear.
8. Farin, G. (1989), Rational curves and surfaces. In L. Schumaker, editor, Mathematical Aspects of CAGD, Academic Press.
9. Farin, G. and Hagen, H. (1989), Local twist estimation, submitted for publication.
10. Farin, G. and Worsey, A. (1989), Contouring quadratic surfaces, in preparation.
11. Farin, G. and Worsey, A. (1989), Reparametrization and degree elevation of Bezier curves, submitted for publication.
12. Farin, G. (1988), Geometry in design: the Bezier method. In J. Rice, editor, Mathematical Aspects of Scientific Software, Springer-Verlag.
13. Farin, G. (1988), The use of triangular patches in CAD. In M. Wozny, H. McLaughlin, and J. Encarnacao, editors, Geometric Modeling for CAD Applications, pages 191-194, North-Holland.
14. Farin, G. Hansford, D. and Worsey, A. (1988), Results on the singular cases for interpolating gamma-splines. Manuscript.
15. Fayard, L. (1988), Surface interrogation using curvature plots, M.S. Thesis, Computer Science Department, Arizona State University.
16. Foley, T. A. (1988), A shape preserving interpolant with tension controls, Computer Aided Geometric Design, vol. 5, pp. 105-118.
17. Foley, T. A. (1989), Interpolation of scattered data on a spherical domain, in Algorithms for Approximation '88, Oxford University Press, to appear.
18. Foley, T. A. and Ely, H. S. (1989), Surface interpolation with tension controls using cardinal bases, Computer Aided Geometric Design, to appear.
19. Foley, T. A., Goodman T. N. and Unsworth, K. (1989), An algorithm for shape preserving parametric interpolating curves with G^2 continuity, in Mathematical Methods in CAGD, Academic Press, to appear.

20. Foley, T. A. and Nielson, G. M. (1989), Knot selection for parametric spline interpolation, in Mathematical Methods in CAGD, Academic Press, to appear.
21. Hansford, D. (1988), Geometric continuity via differential geometry and gamma-spline interpolation, M.S. Thesis, Computer Science Department, Arizona State University.
22. Hansford, D. (1989), The neutral case for the min-max triangulation, submitted for publication.
23. Kelley, A. D. (1988), Three-Dimensional digital simulation of drainage basin development, M.S. Thesis, Computer Science Department, Arizona State University.
24. Kelley, A. D., Malin, M. C. and Nielson, G. M. (1988), Terrain simulation using a model of stream erosion, *Computer Graphics*, vol. 22, no. 4, pp. 263-268.
25. Kersey, S. N. (1988), Triparametric volumes for flow modeling and visualization, M.S. Thesis, Computer Science Department, Arizona State University.
26. Neuser, D. A. (1988), Curve and surface interpolation using quintic weighted tau-splines, M. S. Thesis, Computer Science Department, Arizona State University.
27. Nielson, G. M. (1988a), Affine invariant triangulations and tessellations, Technical Report TR-88-023, Computer Science Department, Arizona State University.
28. Nielson, G. M. (1988b), Bernstein/Bezier curves and splines on spheres based upon a spherical de Casteljau algorithm, Technical Report TR-88-028, Computer Science Department, Arizona State University.
29. Nielson, G. M. (1988c), Interactive surface design using triangular network splines, in *Proceedings of Engineering Graphics and Descriptive Geometry*, S. M. Slaby and H. Stachel, eds., Vienna, Austria, vol. 2, pp. 70-77.
30. Nielson, G. M. and Heiland, R. W. (1988), Interpolation of rotation matrices using quaternions on a 4D sphere, submitted.
31. Nielson, G. M. and Foley, T. A. (1989), A survey of applications of an affine invariant norm, in Mathematical Methods in CAGD, Tom Lyche and Larry Schumaker, editors, Academic Press, to appear.
32. Ong, L. L. (1988), Near real-time display of dynamic objects, M.S. Thesis, Computer Science Department, Arizona State University.

Research Plans for the Coming Year

The scope and objectives of the project will continue as originally proposed.

An immediate plan is to learn and utilize the capabilities of the Ardent Titan, particularly its multiprocessing capabilities. In addition, our interactive computer graphics equipment will be linked with Arizona State University's Cray.

We shall continue to solicit data from actual physical problems, such as those at Sandia Labs and Lawrence Livermore Labs.

The occasion of the SIAM meeting on Geometric Design in Tempe will be used to compare our methods with others, through minisymposia, discussions and demonstrations.

Specific plans for research topics include the following.

Multidimensional interpolation

Comparison of the different surface on surface interpolants will continue, using interactive graphics equipment to display the results. Additional investigation of display methods will be carried out. The contouring of trivariate surfaces will be approached using the trivariate Clough-Tocher interpolant. Additional visualization techniques will be investigated and compared with those in this report.

Multivariate Visualization

The research group will continue developing new techniques and comparing them with existing methods. We plan to publish results that have recently been completed. During the past week, Foley, Nielson and Lane developed a technique that should significantly speed up the multivariate visualization problem when expensive ray tracing techniques are used. For moderately complex scenes, a ray tracing algorithm may require 1000 or more computations for each pixel plotted. Since a full sized image has roughly a million pixels, the computation of a single image is very costly. Using surface on surface methods to interpolate 20 different views of the object, we can obtain an approximate view of the object at roughly 40 operations per pixel. In addition, all million of the pixels could be computed simultaneously in a multiprocessor environment. Initial results appear promising, thus we will investigate these concepts further.

Geometry Processing

The comparison of the two surface-surface intersection algorithms will be completed. The application of them to finding self-intersections for offset surfaces will also be completed. The bivariate adaptive numerical integration schemes have been generalized to trivariate problems; the robustness of these trivariate methods will be investigated.

Shape Preserving Interpolation

We will continue with work that is already in progress which involves optimizing a measure of the second derivative. In addition, we will address the problem of computing surfaces which preserve local monotonicity. Currently, there are no known effective solutions to this problem. Completed research will be submitted for publication and some of the curve techniques will be extended to surfaces.

APPENDIX

Department of Energy Proposal - November 1, 1987

RESEARCH PLAN: SUMMARY OF PROPOSED RESEARCH

The Research plan of this proposal includes the Representation of three-dimensional surfaces and multidimensional surfaces.

A. Three-Dimensional Surfaces

1. Piecewise polynomial triangular interpolants.
 - develop triangular polynomial patches for 3D scattered data problems.
2. Geometry processing.
 - a. Curvature analysis.
 - study a variety of curvatures as surface interrogation tools.
 - b. Surface/surface intersection.
 - develop a surface/surface intersection algorithm for triangular patches.
 - c. Contouring.
 - improve bivariate contouring methods and develop and test trivariate methods for four-dimensional surfaces.
 - d. Generalized contouring.
 - develop methods and code for the generalized contouring problem.
 - e. Numerical integration.
 - enhance the Barnhill, Little, Watson algorithm to find additional properties of three-dimensional surfaces and develop an adaptive numerical integration algorithm for four-dimensional surfaces.
3. Monotonicity and convexity preserving surface interpolation.
 - develop bivariate interpolation methods which preserve local monotonicity and/or convexity.
4. Contour interpolation.
 - develop a bivariate interpolant to data along contours.

B. Multi-dimensional Surfaces.

1. Surfaces defined on surfaces.
 - develop general methods for creating and displaying a surface defined on a three-dimensional surface.
2. Contouring of multivariate interpolants.
 - use contouring for the interactive viewing of multidimensional surfaces.
3. Data reduction
 - utilize multidimensional interpolants as a data reduction tool.

C. Wilson-Fowler splines

- Enhance Wilson-Fowler splines by use of the Bezier representations.

D. Multiprocessing

- investigate computational improvements of surface methods in a multiprocessing environment

Department of Energy Proposal - November 1, 1987

TABLE OF CONTENTS

	Page
PROJECT SUMMARY	1
INTRODUCTION	1
Significance and Application	1
History: Surfaces in Computer Aided Geometric Design	1
RESEARCH ENVIRONMENT	3
Faculty Research	3
Training of New Professionals	3
Research Collaborations	5
Research Symposia, Books and Journal	5
Dissemination of research	6
CURRENT RESEARCH AND PROPOSED RESEARCH	7
Three-Dimensional Surfaces	7
Piecewise Polynomial Triangular Interpolants	7
Monotonicity and Convexity Preserving Interpolants	8
Geometry Processing	8
Curvature Analysis	8
Surface/Surface Intersections	9
Contouring	9
Generalized Contouring	9
Numerical Integration	10
Contour Interpolation	10
Multi-Dimensional Surfaces	10
Surfaces Defined on Surfaces	10
Contouring of Multivariate Interpolants	11
Data Reduction	11
The Wilson-Fowler Spline	12
Multiprocessing	12
Figures	13
RESEARCH PLAN; SUMMARY OF PROPOSED RESEARCH	18
RESEARCH BIBLIOGRAPHY	19
EQUIPMENT AVAILABLE TO THIS RESEARCH PROJECT	24
BUDGET	
Summary Proposal Budget: Years 1-3	
Budget Explanation Page	
Current and Pending Support	
FIGURES	
VITAS OF PRINCIPAL INVESTIGATOR AND THREE CO-PRINCIPAL INVESTIGATORS	
APPENDICES	

1988-89 Graduate Students, With Their Topics, Currently Supported On DoE Project

NAME	TOPIC
Brett Bloomquist	Contours of trivariate surfaces
Larry Fayard	Curvature analysis for surface interrogation
Todd Frost	Offset surfaces
Bernd Hamann	Display of trivariate interpolants
Dianne Hansford	Gamma spline curves, nearest neighbor interpolants
Randy Heiland	Splines on spheres
Chris House	Optimal triangulations
Scott Kersey	Surface-surface intersection
David Lane	Interpolation on the sphere
Sui-sheng Ou	Surfaces defined on surfaces
Parag Rastogi	Rational Bezier and B-spline curves and surfaces
Steve Watson	Mass properties of surfaces utilizing adaptive numerical integration.

END

**DATE
FILMED**

2 / 27 / 92