OPTICAL SCIENCES CENTER
(602) 621-5854

ME/ER/12102--1

DE93 005048

COMBUSTIVE MANAGEMENT OF OIL SPILLS

FINAL REPORT

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DOE GRANT #DE FGO 2-90-ER-12102

MASTER

da
DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

Frontispiece
(see section 3.4, page 55)

IN-SITU BURNING
500 gal/hour

IN-SITU INCINERATION
2500 gal/hour

Acknowledgements

We are grateful to Dr. Ryszard Gajewski, Director of the Advanced Energy Projects Division, Department of Energy, who initiated the funding of this unusual program. The sustained encouragement and advice of his successor, Dr. Walter Polanski, were extremely helpful to us, and our continued association with Dr. Duane Barney, also of the Advanced Energy Projects Office, has been most appreciated.

We were very fortunate in having Ms. Kathryn McSwain as our Administrative Assistant during the rather complex experimental phases of our work.

We wish to thank the staff of the University of Arizona Agricultural Experiment Station for allowing us to use their facilities and for providing outstanding logistic support.

We all thank our spouses who consistently provided assistance with forbearance to us on those frequent occasions when we returned from experiments bearing less than attractive signatures of crude oil in our clothing and on our persons.

Dr. Peter Franken, Principal Investigator

Mr. Dale Perry, Project Engineer

Mr. Ray Randt, Program Manager

Dr. Russell Petersen, Prof. of Aerospace and Mechanical Engineering

Ms. Cindy Thorpe, Administrative Assistant

Tucson, April 15, 1992

Contents

Acknowledgements	i
Introduction	iii
Executive Summary	v
Chapter 1: Theoretical Considerations	1
Section 1.1: Numerical Items	1
Section 1.2: Fire Whirl	2
Section 1.3: Chimney Effect	12
Section 1.4: Adiabatic Flame Temperature	17
Chapter 2: Experimental Program	32
Section 2.1: Liquid Oxygen (LOX) Assisted Ignition	32
2.1a: Properties of LOX	32
2.1b: Combustion of Mousse, Floating Oils, and Debris ..	33
2.1c: Modifications of Helitorch	34
Section 2.2: In Situ Incineration	35
2.2a: Passive Ducting Experimenting	35
2.2b: Augmented Ducting Experiments	36
2.2c: Incinerators	39
Chapter 3: Operational Considerations	47
Section 3.1: In Situ Incineration	48
Section 3.2: Incinerator Storage & Maintenance	50
Section 3.3: Operations	52
Section 3.4: Comparison of Incineration with In Situ Burning	55
Conclusions and Recommendations	59
Appendix A: Test Data	A-1
Appendix C: Color Section	CS-1

Introduction

The effective catalyst for funding this research program was, undoubtedly, the Exxon Valdez disaster in the Spring of 1989. The almost nightly televised spectacle of thousands of men and women, often on their hands and knees, moping up bits of the oil soused shores of Prince William Sound underscored the frequent pathetic futility of conventional oil spill mitigation.

During the past 10 years or so the techniques of "free burning", usually called "in situ burning", or "in situ combustion" have been developed and received some very limited experimental validation. In this technique floating oil is corralled in to a boom, more or less near the disaster site, and ignited. This approach exhibits two major drawbacks:

- 1) Safety considerations, requirements for relatively benign weather and sea conditions, and the inability to burn significantly weathered or emulsified oils are factors which severely limit the scenarios in which this technique can be deployed.
- 2) The production of dense soot clouds, always characteristic of free burning oil, presents an almost insurmountable barrier to obtaining the prompt permits necessary for an effective burn in virtually any U.S. coastal area.

The primary objective of the present program was to develop a technique we call "in situ incineration" in which the spilled oil is not burned in a boomed structure but, rather, pumped into a floating incinerator which operates continuously. It was anticipated that the elevated temperatures of this enclosed and control combustion would dramatically reduce the production of soot clouds and, accordingly, present a more environmentally acceptable mitigation technique. Furthermore, and most importantly perhaps, is the fact that in situ incineration can be deployed in far more varied and extensive conditions than can the method of in situ burning.

It was a further objective of this program to explore the use of liquid oxygen (LOX) for the initiation of high temperature combustion of oil soaked debris and, also, effective total conflagrations of foundered tankers.

It was an additional charge of the original program to explore any promising combustive techniques not embraced by these two stipulated tasks.

Executive Summary

Extensive experiments with in situ incineration were performed on a desert site at the University of Arizona with very striking results. The largest incinerator, 6 feet in diameter with a 30 foot chimney, developed combustion temperatures of 3000° F, and attendant soot production approximately 1000 times less than that produced by conventional in situ burning. This soot production, in fact, is approximately 30 times less than current allowable EPA standards for incinerators and internal combustion engines.

Furthermore, as a consequence of the high temperature combustion, the burn rate was established at a very high 3400 gallons per hour for this particular 6 foot diameter structure. The rudimentary design studies we have carried out relative to a seagoing 8 foot diameter incinerator have predicted that a continuous burn rate of 7000 gallons per hour is realistic. This structure was taken as a basis for operational design because it is compatible with C-130 flyability, and will be inexpensive enough (\$120,000 per copy) to be stored at those seaside depots throughout the U.S. coast line in which the requisite ancillary equipments (booms, service tugs, etc.) are already deployed.

The LOX experiments verified our expectations with respect to combustion of debris and various highly weathered or emulsified oils. We have concluded, however, that the use of liquid oxygen in actual beach clean up is not promising because the very high temperatures associated with this combustion are almost certain to produce environmentally deleterious effects on the beach surface and its immediately sublying structures. However, the use of liquid oxygen augmentation for shore based and flyable incinerators may still play an important role in handling the problem of accumulated debris.

Our experiments with liquid oxygen have indicated that an important modification can and should be made to the currently deployed "Helitorch" which is a helicopter born device for dropping burning globules of jellied gasoline to ignite floating oil, or arctic entrained oil slicks.

An assessment of LOX assisted incineration of Foundered tankers was not undertaken in the present program, but the repeated experimental observations of LOX assisted combustion of small quantities of material strongly suggest the desirability of exploring a modest scale evaluation.

CHAPTER 1 - THEORETICAL CONSIDERATIONS

Introduction

In this chapter we discuss the theoretical underpinnings of the material described in Chapter 2 (Experimental Program) and Chapter 3 (Operational Considerations).

Section 1.1 is merely a listing of certain numbers which are useful to calculations and estimates.

Section 1.2 - The Fire Whirl. This phenomenon relates to the passive ducting discussed in Chapter 2.

Section 1.3 - The Chimney Effect. We show in a semi-quantitative manner, the advantages of using a "stack", or chimney, in controlled combustion.

Section 1.4 - The Adiabatic Flame Temperature. Pertinent theory and calculations are presented for estimation of this temperature which is a good approximation to the maximum temperature that can be developed in a continuously operating flame.

Section 1.1 - Numerical Items

In this section we gather data and conversion factors that are useful for the development of engineering and operational estimates.

PRIMARY PHYSICAL DATA:

Density of water = 1.0 g/ml = 10^3 kg/m³ = 8.34 lb/gal = 62.4 lb/ft³

Average density of crude oil = 0.9 g/ml = 7.5 lb/gal = 56.2 lb/ft³

SLICK CHARACTERISTICS:

The amount of oil in a 1 mm thick oil slick is:

$$0.02458 \text{ gal/ft}^2 = 900 \text{ metric tons/km}^2 = 2.7 \times 10^5 \text{ gal/km}^2 = 4.3 \times 10^5 \text{ gal/mi}^2.$$

For a burn rate of 1 gal/ft²/minute the rate at which the surface disappears is 29 mm/minute.

This is often called the "slick rate".

THERMAL AND CHEMICAL DATA:

We assume the "average" hydrocarbon in crude oil is $C_n H_{2n}$, where n is an integer which does not effect the ultimate stoichiometric values. We use 19,000 BTU per lb = 2.0×10^7 joules/lb = the heat developed in complete combustion. (The range of combustion data for all the oil fractions is within about 10 percent of this figure.)

The complete combustion of 1 gal of crude oil requires 285 ft³ of pure oxygen (NTP) which, in turn, requires 1360 ft³ of air (NTP).

The volume of one gallon is $231 \text{ in}^3 = 0.134 \text{ ft}^3 = 3.79 \times 10^{-3} \text{ m}^3$

Section 1.2 - The Fire Whirl

A buoyant column of heated rising air or hot combustion gases tends to have a swirl component. In discussions of tornados, cyclones, etc., it is common to model the phenomenon as a finite diameter vortex core in so-called "solid body" rotation, surrounded by a "potential vortex" wherein the fluid, although it moves around the common center, has no vorticity.

The terms *velocity potential* and *stream function* are often used. Not all situations may be treated as potential flows (e.g. boundary layers). For a velocity potential to *exist* the flow must be irrotational (curl-free) i.e. : $\nabla \times \mathbf{v} = 0$. The velocity potential, ϕ , is a mathematical scalar function the components of whose gradient are the velocity components. Thus $\vec{v} = \nabla \phi$, where $\phi = \phi(x, y, z)$ in cartesian coordinates or $\phi = \phi(r, \theta, z)$ in cylindrical polar

coordinates. The stream function Ψ is a mathematical scalar function such that lines of constant Ψ are streamlines. A *streamline* is a line in space such that the direction of the velocity vector at a point in space coincides with the direction of the tangent to the streamline at that point. Streamlines exist in all flows but it is only when the flow is *steady* (velocity components are time-independent) that the streamline pattern is steady and hence useful. If the flow is steady and laminar (non-turbulent), streamlines are identical with particle path lines. When dissipative effects (due to shearing action on the viscous fluid) are negligible, it is reasonable to treat the flow as irrotational (curl-free) and hence potential. If the flow is steady, plane-two-dimensional, and potential, it is possible to write an expression for the so-called *complex potential*, $W(z)$, where z is the complex variable $x + iy$ in cartesian coordinates or $re^{i\theta}$ in polar coordinates. The complex potential W is the sum of a real part, ϕ (the velocity potential), and an imaginary part, Ψ (the stream function). Thus $W = \phi + i\Psi$.

It is well-known that the complex potential for an origin-centered, plane-two-dimensional point vortex is

$$W = \frac{-iA}{2\pi} \cdot \ln z. \quad (1)$$

Letting $z = re^{i\theta}$ we note that

$$W = \frac{-iA}{2\pi} [\ln r + i\theta]. \quad (2)$$

thus the real part

$$\phi = \frac{A\theta}{2\pi} \quad (3)$$

is the velocity potential, and the imaginary part is

$$\Psi = \frac{-A}{2\pi} \ln r. \quad (4)$$

It follows from computing $\nabla\phi$ that the radial-component of velocity is given by

$$v_r = \frac{\partial\phi}{\partial r} = 0 \quad (5)$$

and the tangential component is

$$v_\theta = \frac{1}{r} \times \frac{\partial \phi}{\partial \theta} = \frac{A}{2\pi r} \quad (6)$$

The circulation, $\Gamma = \oint \vec{v} \cdot d\vec{r}$, is the integral around *any* closed path embracing the singularity.

If we take the closed path as an origin-centered circle of radius r we may write

$$\Gamma = \int_0^{2\pi} v_\theta r d\theta = \frac{A}{2\pi r} \cdot 2\pi r = A, \quad (7)$$

and hence the constant A is identical with Γ , the circulation of the vortex (sometimes called the *vortex strength*). We may thus write

$$W = \frac{-i\Gamma}{2\pi} \ln z \quad (8)$$

where W is the complex potential for a flow rotating about the origin in a counter-clockwise sense. It is to be noted that this flow is everywhere irrotational (vorticity-free) *except* at the origin, which is a mathematical singularity of the function.

As was implied in the first paragraph of this article, the flow at and near the center of whirling gas flows can *not* be described by the above "potential vortex" (since the origin is a singular point) and, rather, it is assumed that in the core region the flow is more or less in so-called "solid body" motion. In the core the flow is *not* irrotational (i.e., *not* curl-free) and hence a velocity potential does not exist. If the flow were truly "solid body" there would be only a tangential component of velocity:

$$\vec{v} = r \Omega \hat{e}_\theta, \quad (9)$$

where r is the radial coordinate, Ω is the angular velocity of the fluid, and $\hat{e}_\theta$ is the unit vector in the tangential direction. Recalling that the vorticity vector is the curl of the velocity vector ($\nabla \times \vec{v}$) in cylindrical polar coordinates (r, θ, z) there is only a component of vorticity in the z -direction

$$\omega_z = \frac{\partial v_\theta}{\partial r} + \frac{1}{r} \left(v_\theta - r \frac{\partial v_r}{\partial \theta} \right). \quad (10)$$

For the solid body vortex core the radial velocity component is given by

$$v_r = 0 , \quad (11)$$

and the tangential component is,

$$v_\theta = r\Omega \quad (12)$$

Thus

$$\omega_z = \Omega + \frac{1}{r} r \Omega = 2\Omega. \quad (13)$$

The above discussion is meant only to suggest some of the characteristics of the fire whirl. There is nothing in the potential vortex and the "solid body" rotational vortex core that deals with other aspects of the fire whirl, such as the energy released in the combustion process, the axial (vertical) component of velocity, the radial inflow near the ground plane (at the base of the fire whirl), the entrainment of surrounding vorticity-bearing air by the rising column of hot combustion products, etc.

There have been a number of papers in the last 25 years which deal with these aspects: among the most notable is the PhD thesis of Ying (Harvard, 1965) which was later published in the 11th Symposium on Combustion (1967) by Emmons and Ying. In addition there are references (2), (3) ... (6) and (7).

- References -

1. (a) Emmons, H.W. and S.J. Ying, "The Fire Whirl", 11th Symposium on Combustion, Combustion Institute, Pitt., PA. (1967)
 (b) Ying, S.J., "Fire Whirl", "PhD Thesis, Harvard, (1965).
2. (a) Mayle, Robert E., "The Fire Whirl: Theory and Experiment", Technical Report No.5, Harvard University Engineering Sciences Lab., Feb. 1973, N.S.F. Grant GK-10314.
 (b) Mayle, Robert E., "Aerodynamics of the Fire Whirl", PhD Thesis, Harvard, (1970).

3. Muraszew, A., and Fedele, J.B., "Trajectory of Firebrands In and Out of Fire Whirls", Combustion and Flame 30, 321-324 (1977). Discusses effects of prevailing winds. I didn't find it particularly useful.
4. Emori, R.I. and Saito, K., "Model Experiment of Hazardous Forest Fire Whirl", Fire Technology vol.18, no.4, 319-329, Nov. 1982. Attempts to derive scaling laws of forest fires. They came up with Froude number (relative importance of inertial forces to buoyancy forces) and two other numbers, designated as Π_{12} and Π_{13} , where $\Pi_{12} = C_p \rho \Theta u / q$, (Θ is temp.), the relative importance of stored heat in the combustion gases (accompanied with temperature rise) to the heat generated from the fire, and $\Pi_{13} = \rho l g u / J q$, (ρ is density, l is characteristic length, g is gravitational accel., u is characteristic velocity, J is mechanical equivalent of heat, and q is heat generated per unit surface and unit time.) Π_{13} assesses the relative importance of "work" done by buoyancy forces to the generated heat from the fire. No mention is made of the significance of the Rossby number (which involves the circulation (vortex strength)).
5. Soma, S. and Saito, K., "Fire Whirl... A Scale Modeling Approach", Combustion Institute/Eastern states Section, 1988 Technical Meeting, Dec. 5-7, 1988, 67/1-4.
6. Inamura, T., Saito, K. and Taghavi, K., "A Model to Predict Transient Combustion Behavior of Liquid Pool Fires", Combustion Institute/Eastern States Section, 1989 Technical Meeting, Oct.30 - Nov.1, 1989, 53/1-4.
7. Lee, S.L. and Otto, F.W., "Gross Vortex Activities In a Simple Simulated Urban Fire", Fire and Explosion Research, 15th International Symposium on Comb., The Combustion Institute, pgs. 157-162, 1974.

In their fire whirl paper Emmons and Ying¹ attempted an analysis entitled the "Plume Theory." Taking a cylindrical coordinate system (x, r, θ) with corresponding velocity components u (axial), v (radial) and w (tangential) with the x axis (many people use z as the

symbol for the axial coordinate) along the vertical fire whirl axis of symmetry with the origin set above the fuel surface by the thickness of the ground boundary layer, they write the appropriate general equations which are reproduced here to give the reader an idea of the complexity of the general problem.

Continuity (of mass)

$$\frac{\partial}{\partial r}(\rho r v) + \frac{\partial}{\partial x}(\rho r u) = 0, \quad (14)$$

x momentum (axial)

$$\frac{\partial}{\partial r}(\rho r v u) + \frac{\partial}{\partial x}(\rho r u^2) = -r \left(\frac{\partial p}{\partial x} \right) - r(\rho g) + \frac{\partial}{\partial r}(r \tau_{rx}), \quad (15)$$

r momentum (radial)

$$\frac{\partial}{\partial r}(\rho r v^2) + \frac{\partial}{\partial x}(\rho r u v) - \rho w^2 = -r \left(\frac{\partial p}{\partial r} \right) + \frac{\partial}{\partial x}(r \tau_{rx}), \quad (16)$$

θ momentum (tangential)

$$\frac{\partial}{\partial r}(\rho r^2 v w) + \frac{\partial}{\partial x}(\rho r^2 u w) = \frac{\partial}{\partial r}(r^2 \tau_{r\theta}) + \frac{\partial}{\partial x}(r^2 \tau_{x\theta}), \quad (17)$$

There is no pressure variation with θ because of axial symmetry.

Energy (global)

$$\begin{aligned} & \frac{\partial}{\partial r}(\rho r v c_p T) + \frac{\partial}{\partial x}(\rho r u c_p T) + \frac{\partial}{\partial r}(r q_r) + \frac{\partial}{\partial x}(r q_x) \\ & \text{enthalpy convection} \quad \text{heat flux by conduction} \\ & \quad \text{terms} \quad \text{and turbulence transport} \\ & - \frac{\partial}{\partial r} \left[r \sum_s \rho c_{p,s} T D_s \left(\frac{\partial Y_s}{\partial r} \right) \right] - \frac{\partial}{\partial x} \left[r \sum_s \rho c_{p,s} T D_s \left(\frac{\partial Y_s}{\partial x} \right) \right] \\ & \quad \text{enthalpy transport by diffusion} \\ & = r H K Y_{O_2} Y_F \\ & \quad \text{energy source term (by chemical reaction)} \end{aligned} \quad (18)$$

continuity (of chemical species)

$$\frac{\partial}{\partial r}(\rho r v Y_F) + \frac{\partial}{\partial x}(\rho r u Y_F) - \frac{\partial}{\partial r} \left[\rho r D_F \left(\frac{\partial Y_F}{\partial r} \right) \right] - \frac{\partial}{\partial x} \left[\rho r D_F \left(\frac{\partial Y_F}{\partial x} \right) \right] = -r K Y_{O_2} Y_F, \quad (19)$$

where the symbols have the customary meaning for a steady mean turbulent flow.

The terms τ_{ij} are the components of the stress tensor, the i^{th} component of the stress on a surface whose normal is in the j^{th} direction (where i and j can be r , θ , or x).

q_i = heat flux by conduction and turbulence in the i^{th} direction.

D_s = diffusion coefficient of species s .

Y_s = mass fraction of species s .

H = heat of combustion per unit mass of the fuel (less any heat loss by radiation from the core).

K = mass consumption rate (mass of fuel per unit volume and time consumed in the chemical combustion reactions).

The symbols p , ρ , and T stand for static pressure, mass density, and absolute temperature respectively. Since the fire whirl is a *diffusion flame* whose rate is controlled by the mixing rate of fuel and air (i.e., the characteristic chemical kinetic time is much, much shorter than the characteristic mechanical mixing time), K is *not* a chemical kinetic rate but rather is a measure of the local mean mixing rate inside of the fire whirl at the location of active combustion. Emmons and Ying suggested that K would be related to the Taylor turbulent mixing coefficient α which appears subsequently in Eqs. (22) and (23).

The above general equations are obviously intractable to mathematical analysis. To simplify them, the equations were integrated in r between zero and infinity and only the largest terms in each equation were kept.

Defining certain mean quantities such as

$$\bar{u} \equiv \int_0^{\infty} \rho u^2 r dr / \int_0^{\infty} \rho u r dr , \quad (20)$$

$$\bar{b}^2 \equiv \int_0^{\infty} \rho u r dr / \rho_0 \bar{u} , \quad (21)$$

where $\bar{b}$ is a sort of averaged plume radius (a function of x),

Taylor turbulent mixing coefficient

$$\alpha \equiv -\lim_{r \rightarrow \infty} (rv) / \bar{b} \bar{u} , \quad (22)$$

the continuity Eq. (14) becomes

$$\frac{d}{dx} (\bar{u} \bar{b}^2) = \alpha \bar{b} \bar{u} , \quad (23)$$

the radial momentum Eq. (16) becomes

$$p = p_0(\infty, 0) - \rho_0 g x - \int_r^{\infty} \left(\frac{\rho \omega^2}{r} \right) dr , \quad (24)$$

(where the shear stress term and the integrals of v^2 and uv are neglected relative to w^2).

The tangential (θ) momentum equation (17) becomes

$$\frac{d}{dx} (\bar{u} \bar{w} \bar{b}^3) = \alpha L \bar{b} \bar{u} , \quad (25)$$

where the mean tangential velocity

$$\bar{w} \equiv \int_0^{\infty} \rho r^2 u v dr / (\rho_0 \bar{u} \bar{b}^3) , \quad (26)$$

and the circulation (vortex strength)

$$L \equiv \lim_{r \rightarrow \infty} (rw) = \frac{\Gamma}{2\pi} , \quad (27)$$

The axial (x) momentum equation (15) becomes

$$\frac{d}{dx} \left[\bar{u}^2 \bar{b}^2 - k \bar{w}^2 \bar{b}^2 + \frac{1}{2} L^2 \ell n \bar{b} \right] = \frac{\langle \Delta \gamma \rangle \bar{b}^2}{\rho_0} \quad (28)$$

with the definition

$$\langle \Delta \gamma \rangle \equiv \frac{1}{\bar{b}^2} \int_0^\infty (\rho_o - \rho) g r dr, \quad (29)$$

where $\rho_o \equiv \lim_{r \rightarrow \infty} \rho$ (independent of x).

The energy equation (18) becomes

$$\frac{d}{dx} [\bar{u} \langle \Delta \gamma \rangle \bar{b}^2] = \frac{gH}{c_p T_o} \bar{K} \bar{b}^2 \bar{Y}_{O_2} \bar{Y}_F, \quad (30)$$

with definitions

$$\bar{Y}_s \equiv \int_0^\infty \rho Y_s u r dr / \rho_o \bar{b}^2 \bar{u}. \quad (31)$$

and

$$\bar{K} \equiv \int_0^\infty K Y_{O_2} Y_F r dr / \bar{b}^2 \bar{Y}_{O_2} \bar{Y}_F. \quad (32)$$

The species continuity equation (19) becomes

$$\frac{d}{dx} [\bar{u} \bar{b}^2 \bar{Y}_F] = -\bar{K} \bar{b}^2 \bar{Y}_{O_2} \bar{Y}_F / \rho_o \quad (33)$$

The value of the constant k in the axial momentum equation (28) must be experimentally determined, but if the forces arising from centrifugal acceleration in the core may be neglected relative to those in the annular free vortex region, k may be set equal to zero. Doing this decouples Eq. (25) for the core whirl $\bar{w}$ from the other equations. The set of six equations (23), (24), (25), (28), (30) and (33) can be further reduced by elimination of the source terms from Eqs. (30) and (33). This is done by re-writing Eq. (30) as

$$\frac{c_p T_o}{gH} \frac{d}{dx} (\bar{u} \bar{b}^2 \langle \Delta \gamma \rangle) = \bar{K} \bar{b}^2 \bar{Y}_{O_2} \bar{Y}_F \quad (31')$$

and adding to Eq. (33). When this is done the fuel composition may be expressed as

$$\bar{Y}_F = (\bar{u}_o \bar{b}_o^2 \bar{u} \bar{b}^2) \bar{Y}_{F_o} - (c_p T_o / H) \left(\frac{\langle \Delta \gamma \rangle}{\bar{\gamma}_o} \right), \quad (34)$$

where $\bar{\gamma}_o \equiv g \rho_o$.

Hence, there remain only three equations (for $\bar{u}$, $\bar{b}$, and $\langle \Delta \gamma \rangle$). The variables are made

dimensionless in terms of values at $x = 0$, i.e.,

$$u^* \equiv \bar{u}/\bar{u}_0, \quad b^* \equiv \bar{b}/\bar{b}_0, \quad x^* \equiv x/\bar{b}_0, \quad \gamma^* \equiv \frac{\langle \Delta \gamma \rangle}{g \rho_0},$$

$$L^* \equiv \frac{L}{\bar{u}_0 \bar{b}_0} = \frac{1}{R_0} \quad (R_0 \text{ is the Rossby number}).$$

In the final form the continuity equation is

$$\frac{d}{dx^*} (u^* b^{*2}) = \alpha u^* b^*, \quad (35)$$

the x-momentum equation is

$$\frac{d}{dx^*} \left[u^{*2} b^{*2} + \frac{1}{2} L^{*2} \ell n b^* \right] = \gamma^* b^{*2} / F_0, \quad (36)$$

and the energy equation is

$$\frac{d}{dx^*} [u^* \gamma^* b^{*2}] = S \left[\frac{Da_2}{u^* b^{*2}} - \gamma^* \right]. \quad (37)$$

In the above, $F_0 \equiv \bar{u}_0^2 / g \bar{b}_0$ is the Froude number, $Da_2 = HYF_0 / C_p T_0$ is the second Damköhler number and $S \equiv \bar{K} \bar{Y}_{O_2} \bar{b}_0 / \rho_0 \bar{u}_0$ is the reaction rate number (assumed constant). Equations (35), (36), and (37) are tractable and were solved by Emmons and Ying with the aid of a computer but the "theoretical" results did not agree very well with the experimentally observed results. There was too much uncertainty in the assumed values of various parameters. As Professor Emmons pointed out at the time of writing (1967) "The theory is in such a preliminary state ... that we were seeking *hints* for what may be happening rather than a *data correlation*" At the present time (1991) the theory does not seem to have advanced much further. The main stumbling block appears to be the lack of an adequate theory of turbulence, although certainly there is also a shortage of chemical kinetic information. Nevertheless, it is a truism that *some* theory is better than none at all. Francis Fendell said that "analytic surrender will accomplish nothing" (Ref. (1a) - comments).

What is well established experimentally is that the velocity distribution outside of the core is that of a potential vortex. In the experiments of Emmons and Ying the presence of

rotation decreased the Taylor turbulent plume mixing coefficient α by an order of magnitude.

The fire whirl theory requires an additional parameter to the usual convection plume theory (e.g., dust devils, tornadoes, etc.); namely the Rossby number $R_o = 1/L^* = 2\pi\bar{u}_0\bar{b}_0/\Gamma$. In addition, Emmons and Ying point out that the Froude number $F_o \equiv \bar{u}_0^2/g\bar{b}_0$ is also important. It is not surprising that the chemical reactions in fire whirls are of the *diffusion flame* type, wherein the reaction rate is controlled by turbulent mixing rather than chemical factors. As suggested above, "... the pertinent mixing rate is the turbulence level in the vicinity of the combustion zone inside of the whirl ..." It has not yet been possible to relate this turbulence level to the jet mixing rate α .

Section 1.3 - The Chimney Effect

As will be discussed in Chapter 2, our largest incinerator had a chimney height of 30 feet and a diameter of 6 feet. The purpose of the chimney (also called "stack") is to create an induced draft (a pressure difference below that of the surrounding atmosphere). Since the pressure of the column of hot gases emerging from the stack is atmospheric, the pressure at the stack entrance is below atmospheric, thus causing the flow of combustion-feeding air and hot gases to be increased.¹

The degree of the naturally-induced draft depends largely upon the stack height, although the diameter also plays a role. Diameter and height are not independent variables in arriving at the net draft created by the chimney. Height primarily affects the theoretical draft (see figure 1.1), whereas diameter primarily affects the velocity (see figure 1.2) and the resultant friction loss (see figure 1.3) within the chimney itself. It is fairly obvious that the higher the ambient air temperature the lower the stack effect (this is also indicated in figure 1.3).

¹ Combustion Engineering (Combustion Engineering Company, 1948), Draft, Fans and Chimneys, Chapter 26.

Needless to say, although the greater the stack height, along with a correspondingly larger diameter, the greater the chimney effect, the *realistic* stack dimensions depend upon other factors such as cost, construction matters, and stability in cross-winds (and, in the future, sea states).

Figure 26-7. Chart of theoretical draft per foot of height resulting from temperature difference inside and outside of chimney.

Figure 1.1

Figure 26-6. Chart of capacity and economic velocity as compared with chimney diameter.

Figure 1.2

Figures 26-6, 7 & 8 are from Chapter 26 of the afore-mentioned book Combustion Engineering.

Figure 26-8. Chart for determining friction loss in chimney.

Figure 1.3

A chimney operates to produce a draft because it contains a column of heated gas and is connected at its base (sometimes called breeching) to the cooler outside air. To produce the flow of hot combustion gases, the acceleration loss of the flow and the friction losses in the chimney must be overcome by the theoretical differential static head (pressure difference) between the hot and cold column, which in turn depends on the height of the hot column and the density of the the combustion gases.

Presented below is a simple analysis relating the various factors involved in the creation of chimney drafts.

Nomenclature:

$\gamma \equiv \rho g$ specific weight

$\rho \equiv$ density

$g =$ local acceleration of gravity

$z =$ elevation

$k =$ loss factor (dimension-less)

where subscripts 1 & 2 stand for ambient

air and the exit plane of the stack, respectively.

$\gamma_1 =$ air

$\gamma_2 =$ oil

$\gamma_3 =$ water

$\gamma_4 =$ hot gases

$h = z_1 - z_2$

The energy equation (expressed in terms of "head") is:

$$\frac{V_1^2}{2g} + \frac{p_1}{\gamma_1} + Z_1 = \frac{V_2^2}{2g} + \frac{p_2}{\gamma_4} + Z_2 + K \frac{V_2^2}{2g}. \quad (38)$$

The first term on the left is negligible, the last term on the right is a loss term.

Since $p_2 = p_1 - \Delta p$, $h = z_2 - z_1$, and $\gamma_4 = \gamma_1 - \Delta \gamma$, we may rewrite this as

$$\frac{p_1}{\gamma_1} - \frac{(p_1 - \Delta p)}{\gamma_1 - \Delta \gamma} = h + \frac{V_2^2}{2g} (1 + K). \quad (38^I)$$

Clearing fractions and simplifying,

$$\frac{p_1(\gamma_1 - \Delta \gamma) - p_1\gamma_1 + \Delta p\gamma_1}{\gamma_1(\gamma_1 - \Delta \gamma)} = h + \frac{V_2^2}{2g} (1 + K), \quad (38^{II})$$

$$\gamma_1(\gamma_1 - \Delta\gamma) \approx \gamma_1^2, \quad (39)$$

$$\frac{-p_1\Delta\gamma + \Delta p\gamma_1}{\gamma_1^2} \approx h + \frac{V_2^2}{2g} (1 + K), \quad (40)$$

$$\gamma_1\Delta p \approx p_1\Delta\gamma + \gamma_1^2h + \frac{V_2^2}{2g} (1 + K) \gamma_1^2. \quad (41)$$

Thus, the "draft",

$$\Delta p \approx p_1 \frac{\Delta\gamma}{\gamma_1} + \gamma_1 h + \gamma_1 \frac{V_2^2}{2g} (1 + K). \quad (42)$$

This equation shows the dependence of the draft, Δp , upon the specific weight difference, $\Delta\gamma$; ambient pressure, p_1 ; stack height, h ; mean speed of the hot gases in the stack, V_2 ; and the "loss factor", K , of the chimney.

Section 1.4 The Adiabatic Flame Temperature

In this section we calculate the "Adiabatic Flame Temperature" which approximates the *maximum* temperature that can be developed in a continuously operating incinerator.

The temperature of a flame which is not in too close proximity to a cooler surface (ie. when there is no "quenching" effect) is known as the adiabatic flame temperature. The term adiabatic (no heat transfer) may appear strange to the un-initiated, but if one considers a small control volume located 2 or 3 flame zone thicknesses² downstream of the flame zone

²The flame-zone thickness is usually defined as the distance $x_b - x_a$ in Fig. 1.5 where a and b are the points of intersection of the tangent to the T vs x curve (drawn through the point of inflection) with the lines corresponding to T_{unburned} and T_{burned} respectively. A typical value of the flame-zone thickness is of the order of 1 mm (0.040 inches) for combustion at standard atmospheric pressure.

as is shown in the sketch Fig. 1.4, the meaning of the term will become clear.

Fig. 1.4

Since the temperature of the hot gases entering the control volume at surface A in the sketch is no different from that of the gases leaving the control volume at surface B, there is no heat transfer by thermal conduction to or from the control volume. Further, if one can neglect heat transfer by radiation from any of the six surfaces of the control volume (which is not always the case for a "rich" flame wherein the hot gases may contain unburned carbon particles), then the control volume is truly adiabatic.

A plot of the temperature (temperature profile) for a typical flame is shown in Fig. 1.5.

Fig. 1.5

Note that the temperature profile typically exhibits a slight overshoot before settling back to what is called the adiabatic flame temperature (T_{burned}). This is due to the finite time it takes to establish an equilibrium between the kinetic and internal temperatures. Also note that the "final" temperature remains virtually constant for many flame zone thicknesses downstream, owing to the fact that the thermal conductivity of the combustion gases is extremely small.

Another thing to note about the adiabatic flame temperature is that it is a strong function of the strength of the unburned mixture of fuel and oxidizer (the oxidizer in our case is air, of course). The mixture strength (whether it be fuel "rich" or fuel "lean") is frequently specified by ϕ , the equivalence ratio, which is defined as follows:

$$\phi \equiv \frac{A/F_{(\text{molar})}}{A/F_{(\text{molar})} \text{ stoichiometric}} \frac{\text{actual}}{\text{stoichiometric}} \quad (43)$$

The term $A/F_{(\text{molar})} \text{ stoichiometric}$ is the molar ratio of air to fuel if the fuel is to be oxidized to only carbon dioxide (CO_2) and water vapor (H_2O). As an example, consider methane, $\text{CH}_4 + 2 (\text{O}_2 + 3.76 \text{ N}_2) \rightarrow \text{CO}_2 + 2 \text{ H}_2\text{O} + 7.52 \text{ N}_2$. In this case $A/F_{(\text{molar})} \text{ stoichiometric}$ is $2 \times (1 + 3.76) = 9.52$. Note that, for combustion calculations, "air" is assumed to consist of nitrogen and oxygen in molar proportions of 3.76 to 1.0. (This is called "engineering air"!)

If ϕ is greater than one, the combustion is said to be fuel-lean or just "lean".

With the above in mind the variation of $T_{\text{adiabatic}}$ with ϕ would appear as shown in Fig. 1.6.

Fig. 1.6

The adiabatic flame temperature is a rather weak function of the initial temperature, T_1 and a very weak function of the pressure, p .

If the chemical formula of a fuel is known precisely (which is certainly not the case for fuel oil) and the equivalence ratio ϕ , the pressure, p and the initial temperature T_1 , are all known, the adiabatic flame temperature may be precisely calculated. This calculation procedure is given below.

The most general chemical equation for hydrocarbon combustion in standard air is:

Hence, the requisite moles of air, A , is given by:

$$2A = 2n + m/2 \rightarrow A = n + m/4 \quad (45)$$

thus $A/F_{\text{actual}} = 4.76 A \phi$

Knowing A we may then write:

$$A/F_{\text{stoichiometric}} = 4.76 A, \quad (46).$$

For a given value of ϕ , our chemical equation (44) (molar basis) becomes:

In the above there are, *á priori*, 6 unknowns: a,b,...,f. In addition, for a given initial temperature T_1 , the "final" (adiabatic) flame temperature, T_2 , is unknown. In order to determine T_2 and the (a,b,...,f), we must know T_1 , the pressure P, the equivalence ratio ϕ , and the values for n and m (ie, the chemical formula for the fuel oil). Reasonable values of m/n are 2.3 for "fresh" oil and 1.6 for "weathered" oil. Further, it is plausible to choose n = 10, absent further information. Let us choose m = 21 (fairly "fresh" oil); A then becomes $10 + 21/4 = 15.25$. Let us further choose $\phi = 1.0$ (stoichiometric); for ϕ to be greater than 1.0 ("lean") would probably require a means for producing "forced" air.

Our chemical equation then becomes:

In this equation the limits are:

$0 < a < 10$, $0 < b < 10$, $0 < c < 10.5$, $0 < d < 15.25$, $0 < e < 10.5$, $0 < f < 21$. To solve this problem, which has 7 unknowns (T_2 and the 6 unknown a,b,...,f), we will need an energy equation, three atom balance equations (for C,H and O), and three equilibrium constant equations which account for dissociation.

If $T_{adiabatic}$ were calculated neglecting dissociation, the result would be larger than the actual temperature. Dissociation of chemical compounds ("species") occurs to a significant degree if the temperature is high enough. For example, if one mole of carbon dioxide is heated at atmospheric pressure to $1920^\circ K$, the dissociation is 0.93% (i.e. the equilibrium composition at $1920^\circ K$ would be: 0.9907 moles of CO_2 , 0.0093 moles of carbon monoxide, CO, and 0.00465 moles of oxygen, O_2). The relevant (equilibrium) equation describing this is:

The equilibrium constant for this situation is defined as:

$$K_p(T) \equiv P_{CO_2}/P_{CO} P_{O_2}^{1/2}, \quad (50)$$

In equation (50) P_{CO_2} is the partial pressure of CO_2 , etc. The "total pressure" is, by Dalton's Law, the sum of the partial pressures of the various species co-existing in equilibrium).

$K_p(T)$ (the equilibrium constant based on partial pressures) is a function of the absolute

When this is expressed on a molar basis the time rate of change (decrease) of molar concentration of CO_2 may be written as:

$$\left. \frac{d [\text{CO}_2]}{d t} \right|_f = -k_f [\text{CO}_2] [\text{CO}_2] = -k_f [\text{CO}_2]^2, \quad (52)$$

where the subscript f stands for "forward" direction and k_f is the so-called forward rate constant (a strong function of temperature).

The reverse effect can occur - i.e. two molecules of CO can collide with one molecule of O_2 to form two molecules of CO_2

Here the time rate of change (increase) of molar concentration of CO_2 may be written as:

$$\left. \frac{d [\text{CO}_2]}{d t} \right|_b = -k_b [\text{CO}] [\text{CO}] [\text{O}_2] = -k_b [\text{CO}]^2 [\text{O}_2] \quad (54)$$

where subscript b stands for "backward". At thermochemical equilibrium the rate of decrease plus the rate of increase equals zero, i.e.

$$-k_f [\text{CO}_2]_e^2 + k_b [\text{CO}]_e^2 [\text{O}_2]_e = 0 \quad (55)$$

where the subscript e stands for "equilibrium". This may be re-arranged as:

where the subscript e stands for "equilibrium". This may be re-arranged as:

$$\frac{[CO_2]_e^2}{[CO]_e^2 [O_2]_e} = \frac{k_b}{k_f} \equiv K_c (T), \quad (56)$$

where $K_c (T)$ is the equilibrium constant based on concentration and is a strong function of temperature.

We may write the perfect gas equation as:

$$P_{CO_2} V = N_{CO_2} R_o T, \quad (57),$$

where P_{CO_2} is the partial pressure of CO_2 , V is the total volume, N_{CO_2} is the number of moles of CO_2 , R_o is the universal gas constant, and T is the temperature. This may be re-arranged as:

$$N_{CO_2} / V = [CO_2] = P_{CO_2} / R_o T. \quad (58a).$$

In a similar fashion we may write:

$$[CO] = P_{CO} / R_o T, \quad (58b),$$

$$\text{and } [O_2] = P_{O_2} / R_o T. \quad (58c)$$

Dropping the subscript e in equation (56) and substituting equations (58 a, b and c) we may write:

$$\frac{(P_{CO_2} / R_o T)^2}{(P_{CO} / R_o T)^2 (P_{O_2} / R_o T)} = K_c (T), \quad (59a)$$

Re-arranging this we may write:

The equilibrium constant based on partial pressures, $K_p (T)$, is thus related to $K_c (T)$ by the

$$\frac{(p_{CO_2})^2}{(p_{CO})^2 p_{O_2}} = \frac{(R_o T)^3}{(R_o T)^2} K_c(T) = (R_o T) K_c(T) = K_p(T), \quad (59b)$$

factor of $(R_o T)$ for the equilibrium situation:

$$K_p(T) = P_{CO_2} / P_{CO} P_{O_2}^{1/2} \text{ which is equation (50).}$$

Three equilibrium constant equations are needed. We can write:

$$Kp_1(T) \equiv P_{CO_2} / P_{CO} P_{O_2}^{1/2}; \quad (60)$$

$$Kp_2(T) \equiv P_{H_2O} / P_{H_2} P_{O_2}^{1/2}; \quad (61)$$

$$Kp_3(T) \equiv P_{OH} / P_{H_2}^{1/2} P_{O_2}^{1/2}. \quad (62)$$

Let n be the total number of moles coexisting in equilibrium: $n = a + b + c + d + e + f + 57.34$. Note the strong effect of the presence of nitrogen, which acts as an energy absorber, thus limiting $T_{\text{adiabatic}}$. The partial pressure of CO_2 , expressed in atmospheres, is: $P_{CO_2} = (p)(a/n)$ which, for combustion at atmospheric pressure, becomes a/n , (the mole fraction of the CO_2 co-existing in equilibrium at T_2 with the other species).

The atom balance equations (63), (64), and (65) are very simple. Thus

$$C: 10 = a + b \quad (63)$$

$$H: 21 = 2c + 2e + f, \quad (64)$$

$$O: 30.5 = 2a + b + c + 2d + f, \quad (65).$$

The "black-box" schematic, shown in (Fig. 1.7(a)) below is a convenient aid for deriving the appropriate energy equation.

Fig. 1.7 (a)

To understand Fig. 1.7(a) one must first understand the term heat of formation. The heat of formation of a compound (chemical species) at a given temperature is the amount of heat that must be either added (endothermic) or extracted (exothermic) when that compound is formed at that temperature from its "elements". The term "elements" in this context means the basic "building blocks" in their natural state: e.g. H_2 (gas), C (graphite), O_2 (gas), etc. The heats of formation of all of the "elements" are, by definition, zero at all temperatures. In Fig. 1.7(a) the 45 kcal is the reverse (or negative) of the heat of formation of $C_{10}H_{21}$ since

the mole of $C_{10}H_{21}$ is shown being decomposed into its elements C and H_2 . The 45 kcal figure used here is the negative of the average of the heats of formation of the olefin 1-decane ($C_{10}H_{20}$) (-29.67 kcal) and the normal paraffin n-decane ($C_{10}H_{22}$) (-59.67 kcal). The symbol ΔH_f° is commonly used for the heat of formation, the superscript o implying perfect gases which is a good assumption for standard pressure.

The "formation chambers" FC_1 , FC_2 , FC_3 and FC_4 are for formation of CO_2 , CO, H_2O , and hydroxyl OH at the temperature T_1 . If $T_1 = 300^\circ K$ ($27^\circ C$), the heats of formation are -94.055 kcal, -26.414 kcal, -57.803 kcal and +9.432 kcal. They are all exothermic except for OH (the hydroxyl).

The CO_2 , CO, H_2O (vapor), O_2 , H_2 , OH and N_2 (all at temp. $T_1 = 300^\circ K$) are now ready to move into "heat exchangers" HX_1 , HX_2 , HX_3 , HX_4 , HX_5 , HX_6 and HX_7 ; these gases enter at T_1 and emerge at T_2 (the adiabatic flame temperature which is to be determined). This is shown in Fig. 1.7(b) below.

Fig. 1.7(b)

In Fig. 1.7(b) the symbol $\hat{h}_{\text{CO}} @T_1$ stands for the molar enthalpy of CO_2 at the temperature $T_1 = 300 \text{ K}$, etc. Molar enthalpies are tabulated in the JANAF tables. (JANAF stands for Joint Army Navy Air Force Committee, a multi-service group which serves as a clearing-house and disseminating agency for thermochemical data.)

Finally, the energy equation is obtained by imposing the adiabatic requirement that the sum of the energy out must equal the sum of the energy in. The sum of the energy out is: $94.055 a + 26.414 b + 57.803 c$ (units of kilo-calories). The sum of the energy in is:

$$45 + a (\hat{h}_{CO_2} @T_2 - \hat{h}_{CO_2} @T_1) + b (\hat{h}_{CO} @T_2 - \hat{h}_{CO} @T_1) + c (\hat{h}_{H_2O} @T_2 - \hat{h}_{H_2O} @T_1) + d (\hat{h}_{O_2} - \hat{h}_{O_2} @T_1) + e (\hat{h}_{H_2} @T_2 - \hat{h}_{H_2} @T_1) + f (\hat{h}_{OH} @T_2 - \hat{h}_{OH} @T_1) + 57.34 (\hat{h}_{N_2} @T_2 - \hat{h}_{N_2} @T_1) + 9.43 f \text{ (units of k-cal.)}$$

When these two energies are equated it becomes the energy equation:

$$94.055a + 26.414b + 57.803c = 45 + a \frac{\Delta \hat{h}_{CO_2}}{T_1 \rightarrow T_2} + b \frac{\Delta \hat{h}_{CO}}{T_1 \rightarrow T_2} + c \frac{\Delta \hat{h}_{H_2O}}{T_1 \rightarrow T_2} + d \frac{\Delta \hat{h}_{O_2}}{T_1 \rightarrow T_2} + e \frac{\Delta \hat{h}_{H_2}}{T_1 \rightarrow T_2} + f \frac{\Delta \hat{h}_{OH_2}}{T_1 \rightarrow T_2} + 57.34 \Delta \hat{h}_{N_2} + 9.432f, \text{ (units of k-cal.)} \quad (66)$$

It is to be noted, as stated previously, that the unknowns are 7-fold: T_2 , a , b , c , d , e , and f . The task now becomes one of solving equations (60) through (66) simultaneously. While extremely tedious, this can be done "by hand" with the aid of a pocket calculator. There are however, computer programs available to do this rapidly and efficiently. One such program, which uses the principle of the minimization of the Gibb's free energy, is called the Gordon-McBride program (Sanford Gordon and Bonnie McBride of N.A.S.A. Lewis, Cleveland).

Since there is no information for our fictitious compound $C_{10}H_{21}$ (which we have taken to represent crude oil), the Gordon-McBride program was applied twice, once for the Olefin 1-decane ($C_{10}H_{20}$) and once for the normal paraffin n-decane ($C_{10}H_{22}$), the initial temperature T_1 being $300^\circ K$ and at standard atmospheric pressure. The results are:

$$T_2 = 2333.3^\circ K \text{ (for } C_{10}H_{20}\text{)}$$

$$= 2060.3^\circ C$$

$$\text{and } T_2 = 2332.9^\circ K \text{ (for n-} C_{10}H_{22}\text{)}$$

$$= 2059.9^\circ C.$$

It is interesting to note that the maximum temperatures observed in our experimental

program (chapter 2) are just a few hundred degrees below this theoretical upper limit.

Tables 1 (a) and 1 (b) are summaries of the results for $C_{10}H_{20}$ and $C_{10}H_{22}$. It is to be further noted that many more species than (a) through (f) plus N_2 were considered in the Gordon-McBride program and that the only oxide of nitrogen to exist in any significant degree was NO which had a mole fraction of 0.00274.

This example establishes the important fact that the adiabatic flame temperature is insensitive to the exact composition of the constituent hydrocarbons.

Thanks are due to Mr. Mario Rascon for running the Gordon-McBride program and furnishing the results.

THERMODYNAMIC EQUILIBRIUM COMBUSTION PROPERTIES AT ASSIGNED
PRESSURES

CHEMICAL FORMULA				MT FRACTION	ENERGY	STATE	TEMP
FUEL	C	1.00000	H 2.00000	(SEE NOTE)	CAL/MOL		DEG K
OXIDANT	N	1.56176	O 0.41959	1.000000	-296.700	L	298.15
			AR 0.00932	1.000000	-28.200	G	298.15
			C 0.00300				

O/F= 14.7100 PERCENT FUEL= 6.3654 EQUIVALENCE RATIO= 1.0191 PHI= 1.0194

THERMODYNAMIC PROPERTIES

P, ATM 1.0000
T, DEG K 2333.3
RHO, G/CC 1.5033-4
H, CAL/G -2.2570
U, CAL/G -163.35
G, CAL/G -5308.30
S, CAL/(G)(K) 2.2741
M, MOL WT 28.782
(DLV/DLP)T -1.00399
(DLV/DLP)P 1.1146
CP, CAL/(G)(K) 0.5757
GAHMA (S) 1.1696
SON VEL, M/SEC 887.9

TABLE 1(a)

MOLE FRACTIONS

CO 0.02043
CO2 0.11298
H 0.00072
H2 0.00398
H2O 0.12434
NO 0.00274
N2 0.72439
O 0.00047
OH 0.00387
O2 0.00608

ADDITIONAL PRODUCTS WHICH WERE CONSIDERED BUT WHOSE MOLE FRACTIONS WERE LESS THAN 0.50000E-05 FOR ALL ASSIGNED CONDITIONS

C	CH	CH2	FORMALDEHYDE	FORMIC ACID	CH3	HYDROXYMETHYLENE
METHYLOXIDE	CH4	METHANOL	CM	NCN RAD	CNN RAD	C2
C2H RAD	ACETYLENE	KETENE	C2H3 RAD	METHYL CYANIDE	CH3CO RAD	CH2CHO RAD
ETHYLENE	ACETALDEHYDE	ACETIC ACID	(FORMIC ACID)2	ETHYL RAD	ETHYL OXIDE RAD	ETHANE
AZOMETHANE	ETHANOL	DIMETHYL ETHER	CNC RAD	CYANOGEN	CCO RAD	C3
C3H3 RAD	CYCLOPROPENE	PROPYLENE	ALLENE	C3H5 RAD	CYCLOPROPANE	PROPYLENE
PROPYLENE OXIDE	I-PROPYL RAD	N-PROPYL RAD	PROPANE	1-PROPANOL	CARBON SUBOXIDE	C4
BUTADIENE	BUTAN-1EN-3YN	CYCLOBUTADIENE	2-BUTYNE	1,3-BUTADIENE	2-BUTENE TRANS	2-BUTENE CIS
ISOBUTENE	1-BUTENE	(ACETIC ACID)2	S-BUTYL RAD	N-BUTYL RAD	1-BUTYL RAD	ISOBUTANE
N-BUTANE	CARBON SUBMITR:O	CS	CYCLOPENTADIENE	CYCLOPENTANE	1-PENTENE	N-PENTYL RAD
T-PENTYL RAD	CH3C:CH3)2CH3	PENTANE	ISOPENTANE	HEXATRIYNE	PHENYL RAD	PHENOXY RAD
BENZENE	PHENOL	CYCLOHEXENE	N-HEXYL RAD	BENZALDEHYDE	TOLUENE	C7ESOL
1-HEPTENE	N-HEPTYL RAD	N-HEPTANE	1-OCTENE	N-OCTYL RAD	OCTANE	ISO-OCTANE
N-NONYL RAD	NAPHTHLENE	AZULENE	N-DECYL RAD	O-BIPHENYL RAD	BIPHENYL	JET-A(G)
SIBENZYL	HCH	HCO RAD	NHCO	HNO	HNO2	HNH3
HG2	H2N2	H2O2	N	HCO	NH	NH2

N-3	NH2CH	N02	N03	N2H2	NH2NO2	N2H4
H2O	N2O3	N2O4	N2O5	N3	N3H	O3
C:GR)	BENZENE(L)	TOLUENE(L)	OCTANE(L)	JET-A(L)	H2O(S)	H2O(L)

NOTE. WEIGHT FRACTION OF FUEL IN TOTAL FUELS AND OF OXIDANT IN TOTAL OXIDANTS

THERMODYNAMIC EQUILIBRIUM COMBUSTION PROPERTIES AT ASSIGNED
PRESSURES

FUEL C 1.00000 H 2.20000 OXIDANT N 1.56176 O 0.41959 AR 0.00932 C 0.00300	WT FRACTION (SEE NOTE) 1.000000 1.000000	ENERGY CAL/MOL -596.700 -28.200	STATE L G	TEMP DEG K 298.15 298.15
--	---	--	-----------------	-----------------------------------

O/F= 14.9800 PERCENT FUEL= 6.2578 EQUIVALENCE RATIO= 1.0194 PHI= 1.0197

THERMODYNAMIC PROPERTIES

P, ATM	1.0000
T, DEG K	2332.9
RHO, G/CC	1.49554
H, CAL/G	-3.5360
U, CAL/G	-165.47
G, CAL/G	-5336.51
S, CAL/(G)(K)	2.2851
M, MOL WT	28.629
(DLV/DLP)T	-1.00396
(DLV/DLP)P	1.1137
CP, CAL/(G)(K)	0.5769
GAMMA (S)	1.1700
SON VEL, M/SEC	890.3

TABLE 1(b)

MOLE FRACTIONS

CO	0.01989
CO2	0.10880
H	0.00074
H2	0.00427
H2O	0.13188
NO	0.00270
N2	0.72137
O	0.00046
OH	0.00396
O2	0.00592

ADDITIONAL PRODUCTS WHICH WERE CONSIDERED BUT WHOSE MOLE FRACTIONS WERE LESS THAN 0.50000E-05 FOR ALL ASSIGNED CONDITIONS

C METHYLOXIDE C2H RAD ETHYLENE AZOMETHANE C3H3 RAD PROPYLENE OXIDE BUTADIENE ISOBUTENE N-BUTANE T-PENTYL RAD BENZENE 1-HEPTENE N-NONYL RAD B1BENZYL HO2	CH CH4 ACETYLENE ACETALDEHYDE ETHANOL CYCLOPROPENE I-PROPYL RAD BUTAN-1EN-3YN 1-3UTENE CARBON SUBNITRID CH3C/CH3/2CH3 PHEMOL N-HEPTYL RAD NAPHTHLENE HCH H2N2	CH2 METHANOL KETENE ACETIC ACID DIMETHYL ETHER PROPYNE N-PROPYL RAD CYCLOBUTADIENE (ACETIC ACID)2 CS PENTANE CYCLOHEXENE N-HEPTANE AZULENE HCO RAD H2O2	FORMALDEHYDE CH C2H3 RAD (FORMIC ACID)2 CNC RAD ALLENE PROPANE 2-BUTYNE S-BUTYL RAD CYCLOPENTADIENE ISOPENTANE N-HEXYL RAD 1-OCTENE N-DECYL RAD HMO N	FORMIC ACID NCN RAD METHYL CYANIDE ETHYL RAD CYANOGEN C3H5 RAD 1-PROPANOL 1,3-BUTADIENE N-BUTYL RAD CYCLOPENTANE HEXATRIYNE BENZALDEHYDE N-OCTYL RAD O-3IPHENYL RAD HNO NCO	CH3 CNN RAD CH3CO RAD ETHYL OXIDE RAD CCO RAD CYCLOPROPANE CARBON SUBOXIDE 2-BUTENE TRANS 1-BUTYL RAD 1-PENTENE PHENYL RAD TOLUENE OCTANE BIPHENYL HNO2 NH	HYDROXYMETHYLENE C2 CH2CHO RAD ETHANE C3 PROPYLENE C4 2-BUTENE CIS ISOBUTANE N-PENTYL RAD PHENOXY RAD CRESOL ISO-OCTANE JET-A(G) HNO3 NH2
--	--	--	--	--	---	--

NH3	NH2OH	NO2	NO3	N2H2	NH2NO2	N2H4
N2O	N2O3	N2O4	N2O5	N3	N3H	O3
C(GR)	BENZENE(L)	TOLUENE(L)	OCTANE(L)	JET-A(L)	H2O(S)	H2O(L)

NOTE: WEIGHT FRACTION OF FUEL IN TOTAL FUELS AND OF OXIDANT IN TOTAL OXIDANTS

CHAPTER 2 - EXPERIMENTAL PROGRAM

All of the experiments at the North Campbell Farm site of the University of Arizona were conducted between April 17, 1990 and March 29, 1991. These primary data were recorded in real time on video tapes which provide the archival record. A description of the salient features of each experiment is provided in Appendix A-1, and this record will be used as a reference in the summary of results discussed in this chapter.

Section 2.1. - Liquid Oxygen (LOX) Assisted Ignition.

Section 2.1.a. - Properties of LOX. The basic material data pertinent to liquid oxygen are as follows:

Spec. gravity (rel. to water) = 1.14

Boiling point = -182.96°C

Density of oxygen in LOX / Density of oxygen in air (ntp) = 952.3

Liquid oxygen, ferocious oxidant and dangerous material as it seems is, in fact, a common material which is inexpensive to manufacture and for which the distribution and storage systems are well in place. LOX is currently the primary source of gaseous oxygen for supplemental breathing. It is routinely stored in residential bedrooms in standard vacuum walled containers (Dewars) which exhibit storage containment times measured in months. The oxygen is evaporated from the liquid and is used as a breathing supplement in a large variety of chronic and acute disease processes which can be managed effectively in a home environment. Liquid oxygen is transported to these sites by container trucks, and handled by relatively ordinary staff. Liquid oxygen is also the source for all of the gaseous oxygen carried by military aircraft simply because this storage is far less "weighty" (and less dangerous!) than the alternative of iron cylinders containing compressed gaseous oxygen.

The typical "manufacturing" cost of LOX is in the neighborhood of \$.08 per pound = \$0.17

per liter = \$0.64 per gallon, and it is readily transported by air or by tank truck, at a cost comparable to that for the shipment of ordinary flammable or hazardous liquids.

Section 2.1.b. - Combustion of Mousse, Floating Oils and Debris. Experiments performed early in 1990 at the laboratories of the Optical Sciences Center established that emulsified mixtures of oil and water (mousse) could be effectively burned with the direct addition of liquid and gaseous oxygen mixtures which were conveyed to the incineration by styrofoam cups or conventional cryogenic piping.

We undertook a series of experiments at the Farm site of the University (pages A-1 through A-20) in which we explored the use of LOX assisted ignition and combustion of mousse, in various configurations and altered concentrations. The effectiveness of these combustions, in general, increased with scale. I.e., it took significantly less LOX (per pound of mousse) to consume 5 pounds than it did to consume 5 ounces. This is due, in part, to the "roll off" of LOX when it is applied to very small samples as well as to the fact that the heat of combustion in large samples can be effectively utilized to continue the separation of the oil and water, and the initial evaporation of the hydrocarbons themselves. In the largest experiments we burned 3 or 4 pounds of mousse in a shallow pit, and also some 5 pounds of the material poured over a small rock pile. (Page A-8)

The elevated temperatures of these combustions, we believe, make the usefulness of this technique for beach cleanup very limited. Rocks appear to crack under the heat, and there would certainly be extensive sterilization of the sublying beach structures. However, we conclude that the use of liquid oxygen for combustion of mousse in a contained environment on shore is very likely a practical consideration if the alternative is to transport over large distances with subsequent disposal elsewhere. It is evident from the video tapes of the work that the high temperature incineration in LOX assisted combustion greatly reduces soot production, in contrast to the conventional fuel rich combustion of this material.

In the period from May 2, 1990 through May 15, 1990 (pages A-30 through A-33) we experimented at the North Campbell Farm site with small ponds in which we floated various

oil and water combinations. Combustion of these hydrocarbons was augmented by the application of liquid oxygen, in a variety of methods. We found it particularly efficacious to allow small amounts of liquid oxygen to flow down a chute onto the surface of the oil in which were floating small amounts of burning punk or paper. (Page A-20)

We were able to sustain combustion in heavy spent crankcase oils, weathered oils, and Prudhoe Bay crude slicks less than a millimeter thick. In short, we verified that it was possible to burn virtually any hydrocarbon that floated. In this work the combustion temperatures were high (judged primarily by color), and the productions of black smoke were significantly reduced.

In these experiments we included a successful attempt to burn an 8-inch lawn tractor rubber tire. The combustion was extremely hot and complete, with little to no residue. (Page A-15) One of the important lessons that had to be learned, and relearned several times, was that a great deal of caution needs to be exercised when LOX is applied in situations where combustible vapors are present. It is often possible to suddenly generate the requirements for a fuel-air detonation, upon the application of the LOX, and the resulting explosion can range in intensity from merely startling to downright unfriendly. (Page A-11)

Section 2.1.c. - Modification of Helitorch. During the course of these experiments with LOX it was firmly established that this material vastly increased the ignitability of hydrocarbons exhibiting a low vapor pressure. These included tars, chilled oils, heavily weathered oils, and many varieties of mousse.

This result leads to the important notion of modifying the conventional "Helitorch" which is used to ignite oil slicks, as well as oil spilled on ice and, on occasion, in remote land sites. If these oils are either very cold or sufficiently weathered to have lost most of their volatile components, then the deployment of Helitorch is simply not effective. [This device releases "globs" of burning jellied gasoline as kind of a non-projecting flamethrower; it was developed for the Forest Service to satisfy their requirement for setting backfires in remote locations.]

It does not present profound engineering challenges to reconfigure a Helitorch to drop styrofoam "balls" each containing about a cup of LOX and equipped with simple contact fuses. We have shown in our very early experiments that dropping this quantity of LOX in a styrofoam container onto some surface and immediately thereafter providing a small flame always succeeds in starting a combustion if there is combustible material around. Furthermore, the styrofoam itself participates in and assists the burning process.

Although the requisite engineering needs to be careful and disciplined, of course, the introduction of such a device into the equipment currently used for Helitorch operations does not appear to present significant difficulty. The usefulness of this device is manifest in Arctic spills and situations where, for one reason or another, the surface combustible volatiles are not sufficient to support ignition by a conventional Helitorch.

Section 2.2. - In Situ Incineration.

Section 2.2.a. - Passive Ducting Experiments. In 1964 Russell Petersen of the University of Arizona demonstrated the principles of "passive ducting" in which vanes are deployed about a burning substance in order to guide the in-flowing air into a cyclonic pattern. (Departmental Records) In the case of Petersen's early work with alcohol flames, the primary effect of the passive ducting was to increase the burn-rate up to fivefold. We decided to explore techniques of passive ducting both to enhance the burn-rate of crude oils as well as to increase the combustion temperature of the burn itself.

Our first experiment, on May 17, 1990, was accomplished on the roof of the Optical Sciences Center and was essentially a reproduction of Professor Petersen's earlier work. (Page A-28) Shortly thereafter we commenced our work with iron ponds, surrounded with large sheet iron vanes, in which we burned various floating oils.

The first experiment was accomplished with eight vanes consisting of 4 ft x 4 ft iron sheets, circumscribing a four foot pond containing four gallons of used crankcase oil. (Page A-24)

The overall effect was that the use of these vanes increased the intensity of the burns by about twofold.

At this stage we decided it was important to explore techniques of "augmenting" the passive ducting effects in order to force more air into the burn with the hope of increasing both the burn rate as well as the temperature of combustion.

Section 2.2.b. - Augmented Ducting Experiments. In the period May through September 17, 1990 we explored numerous methods for augmenting the ducting effects. These included:

- 1) Using large squirrel cage blowers to force low velocity air in between the vanes.
- 2) Injecting small amounts (less than 300 cfm) of high velocity (greater than 100 feet per second) air into the center of the burn and directed straight upwards.
- 3) The same as just above but with several air jets canted off center in such a way as to stimulate a cyclonic whirl within the structure.
- 4) A variety of techniques for "agitating" or "bubbling" the oil-water surface during the burn.

1. We used standard evaporative air conditioning blowers with rated capacities of 5,500 cfm, exit throats of 16"x 22", and exit air velocities of 41 feet per second (28 mph). We found an approximately threefold increase in burn rate by placing each blower about 3 feet away from the openings between vanes, with a total of 8 or 10 blowers depending upon the available spaces. Concomitant with this greater consumption was also a notable increase in flame temperatures, as judged primarily by visual inspection. Thermocouple measurements of temperature indicated an increase from about 1800°F to 2200°F, but our instrumentation was rather crude at this time. This instrumental insufficiency was corrected by the time the very high temperature combustions were realized.

It is instructive to estimate some of the air flow rates. We determined the burn rate in one of the eight foot pond experiments to be approximately 0.5 gallons per minute per square foot of oil surface. (This is about seven times more than the "free burning rate".) The total burn rate for this experiment was approximately 25 gallons per minute which, therefore, consumed the oxygen present in about 37,000 cubic feet of air a minute. The total rated output of the eight blowers was 44,000 cfm; without the blowers the ordinary ducted burning rate was about 8 gallons per minute which, in turn, is only about double the absolute free burning rate.

We concluded from these studies that this simple form of adding low velocity air between the vanes was not going to yield a practical large scale approach unless we could devise some means of "leveraging" the supplied air with additional drafting effects. In other words, we do not believe it would be effective in practice to supply all the air needed for combustion; it will be important to have other processes kick in, which provide a "natural" augmentation of the combustion itself.

2. We rented a conventional construction site air compressor rated at 285 cubic feet per/minute (CFM). Typical outputs at the hose end exhibited an exit velocity of some 400 feet per second (270 mph), with a beam diameter of about 3/4 of an inch. (It was very difficult but not impossible to hold one's hand about one foot in front of this jet.) The general result of a large number of different experiments was that one or two 100 cfm high velocity air streams like these, oriented more or less straight up along the axis of the incinerator and located a few inches to a few feet above the burning liquid, accomplished a dramatic increase in burn rate and consequent combustion temperatures. Indeed, our conclusion is that the addition of a few hundred cfm of compressed air is more utilitarian than the addition of more than 50,000 cfm of low velocity streams. We believe that this dramatic and not entirely expected effect arises, in large part, because of the "entrainment" and "whorl" effects associated with a high velocity air stream as well as the local increase of combustion temperature associated with substantially greater aeration. An example of this augmentation is shown in the color photograph C-12.

We have routinely achieved "leverage ratios" of 100 or more. This ratio is the measure of the number of additional cubic feet of air consumed in the burn per 1 cfm of high velocity air supplied by the pipe, and is given by:

$$\text{Leverage Ratio (LR)} = r \times 1450 \times (1/p),$$

where r is the burn rate in gallons per minute and p is the compressed air measured in cubic feet per minute (cfm) supplied by the external compressor. (Note: 1450 is the number of cubic feet of air (stp) required to completely burn one gallon of oil.)

3. We experimented with several jets, rather than just one, and discovered that the most effective arrangement of four outputs (300 cfm in toto) was to have one straight up the axis of the furnace, about 3 feet above the liquid surface, and the remaining three each placed about 2 feet from the central axis, a few feet above the liquid, and canted by some 30°. These jets produced a "cyclonic" or "whirling" action within the incinerator in the same rotational sense as produced by the external vanes. We did not have the resources of time or funds to construct experiments that would permit us to optimize the compressor exit port configurations within the incinerator. This clearly needs to be done in the development phase of this project.

4. Throughout the later part of our experimental program we tried to augment the "roiling" effects that occur at the oil water interface of intense burns. We used small amounts of high velocity compressed air projected from small nozzles to throw up mixtures of oil and water from the burning surface, and in a variety of configurations.

We found it was possible to actually decrease the burn rate and combustion temperature if we projected too much oil and water above the surface. We concluded that this effect comes about primarily because of a reduction in flame temperatures produced, probably, by an excess of water droplets in the burning region.

The most effective configuration of the "roiling" nozzle seems to be one in which the jet points down towards the liquid from a position approximately one foot above it. If a flame

is not present, this configuration of air jet produces a noticeable spattering of relatively fine droplets from the surface as well as a locally intense agitation. When this jet is made operational during the burn there is a dramatic increase in both the combustion temperature as well as the burn rate itself. We believe this is due primarily to the conventional effect of "atomization" which is utilized in one form or another in most contemporary furnace designs.

Section 2.2.c. - Incinerators. Many of our experiments during the summer of 1990 convinced us that the "open vane" structures with which we were working will not have a direct application for in-situ burns; the risk of combustion spilling out of the vaned structure and spreading into the surrounding oil surface is unacceptable. Not only is there a severe operational hazard presented by such a spread, but also if there is some combustion of the surrounding oil surface, the air being blown into the structure by the blowers would now be oxygen poor because it will have been air that has been used, to some extent, for combustion itself. We would end up, in effect, with a rather standard form of free-burning oil slick in the middle of which a lot of expensive equipment would be beating the devil out of nothing and burning up in the process.

Accordingly, in October, 1990 we turned our attention to the design of incinerator structures which would incorporate as much of the augmented ducting phenomena as we could but would provide an essentially total isolation of the combustion process from the surrounding space. For illustrative purposes we show drawings and a photograph of our largest incinerator, completed in November 1990, which has a chimney height of 30 feet and a diameter of 6 feet. (Figure 2.1) The incinerator illustrated in these figures is as close to a prototype of what we propose operating at sea as we were able to accomplish with the present program resources.

Shielded Platinum-Iridium thermocouples capable of temperature determinations in excess of 3,000°F were placed at 5 uniformly spaced positions within the chimney, starting at the burn level and proceeding to the top of the incinerator. When full bore "candle" combustion

Figure 2.1a Overall

Figure 2.1b Exploded view

Figure 2.1 6 Feet diameter incinerator

Figure 2.1c Assembly operations

was achieved most of the thermocouple measurements ranged from 2900°F to 3050°F; the very hottest point was usually about 15 feet above the surface of the burning liquid. During these burns it was possible to see the interior through various small (less than 1 inch) holes in the chimney which had been used for previous instrumentation ports. The incandescence, considering that it was viewed in typically bright Arizona midday sunshine, was most impressive.

The 1½ inch thick ceramic thermal blanket³ lined the interior of this large chimney plays, we believe, a crucial role in the effectiveness of the combustion. First and foremost, it permits steady state internal combustion temperatures of 3000°F and greater while the outside galvanized iron structure remains at less than 500°F. We believe a second and important role is carried out by providing a very large and extremely hot surface area to engage the oil and water droplets subsequent to their being "bubbled" by the compressed air. There may also be a significant "wicking" action that augments the vaporization of the oils themselves.

It is very important to recognize that the striking burn rates (in excess of 3000 gallons per hour) are consistent with combustion temperatures in the 3000°F range. (For perspective, combustion temperatures common to "free burning" are typically less than 2000°F.)

Temperature profiles were obtained with the Thermocouple installed as described. (Page A-73) We call the reader's attention to figure 2.2 and the thermal data displayed therein from the experiment in which 185 gallons of unweathered crude oil were placed into the incinerator, providing an approximately 7 inch thick "slick" over 10 inches of water in the base of the chamber. We allowed this burn to develop naturally for the first 1.5 minutes because experience had taught us that premature augmentation would sometimes simply extinguish the combustion itself. At 1.5 minutes into the burn we activated the compressed

³"Durablanket" (8 lb/ft³) manufactured by Sohio Materials Company, Refractories Division, Keasbey, NJ 08832.

Temperature VS. Time for the
Experiment of March 11, 1991

FIG. 2.2

air jets and at 2 minutes into the burn the "bubbler jets". The combustion then went to the elevated temperatures which were achieved between 3 minutes and 7.5 minutes. At $t=7.5$ minutes the fire had gone out and the subsequent portion of the temperature curve exhibits conventional exponential thermal relaxation. A color photograph of this burn is shown in the Frontispiece.

The thermal measurements at the other ports were almost identical to the one shown in figure 2.2. These temperature data's permit us to refine our estimates of burn rates. The average rate, of course, is simply calculated from the fact that the fire lasted for 7.5 minutes. Hence, the average burn rate is $185/7.5 = 25$ gallons per minute. However, we believe that the burn rate rises extremely rapidly as a function of internal temperature so that we estimate 85% of the oil was consumed between $t = 5.0$ minutes and 7.5 minutes. This yields a peak burn rate of 74 gallons per minute which we have used as the basis for our systems studies. These studies predict a burn rate of 7000 gph for our seagoing incinerator design.

This postulated burn rate of 7000 gph will release 10^9 BTU's per hour. (This result is readily derived from the data of chapter 1.1). In contrast, the largest combustion rate of hazardous wastes (The Red Rock facility in Arkansas) is 0.15×10^9 BTU per hour, and this unit has a construction and installation cost in excess of one hundred million dollars.

The basic reason for our huge burn rate and our thousand fold less construction cost derives from the important fact that we have designed a single purpose incinerator. To wit, the consumption of vast quantities of oil with negligible production of soot. The commercial incinerators, by contrast, are designed for many different feeds (chopped up tires, paper products, hazardous materials, as well as combustible fluids). And, furthermore, these commercial incinerators must meet strict EPA standards for continuous operation. To this end they must be equipped with "scrubbers", second stage combustion, and other very carefully stipulated effluent managements. Incorporating all of these equipments, and procedures, into a unit designed for many tens of thousands of hours of continuous operation is responsible for the very high commercial incinerator costs.

An inspection of the Frontispiece makes it immediately apparent that the soot or smoke production from in situ incineration is enormously less than that developed by in situ burning. The reasons for this dramatic reduction are twofold: we achieve virtually stoichiometric fuel-air mixtures (in comparison with the very fuel rich mixtures of in situ burning) and we burn at three thousand degrees F (vs. eighteen hundred degrees, typically). Indeed, our particulate production is several to many times less (per pound burned) than is currently allowed by the EPA standards for commercial incineration!

The data and analysis of our soot production will now be reviewed. The particulate production in our incinerations is so low that conventional measurement methods (grain collection and CO₂ determinations) are not practical. These could be modified of course, but when particulate densities as low as we observe are to be measured, it is then more suitable and effective to utilize optical methodology.

Simple visual observation of the sun's image extinguished by a free burning soot cloud yields some very important quantitative information. An example of the transparent side of extinction is shown on Page CS-5, where four photographs were taken of the sun in a fairly fuel rich burn produced at our site. The striking feature of these photographs is that the solar image does not "red out" but maintains its blue-white color throughout extinction. This simple observation establishes that there is no appreciable Rayleigh scattering contribution to the extinction. For a Rayleigh case, where the optical wavelength is large compared to particulate size, the effect would definitely be a "red out" exactly as we see with the setting sun in a very dusty atmosphere, or with street lights during many conditions of haze or fog. Our observed "neutral density" effect establishes that we are dealing with particulate size several to many times larger than a wavelength; i.e, particles of ten or more micrometers in diameter. It is interesting to note that this easily established fact about particulate size is entirely consonant with a large number of physical measurements in which particles have actually been collected and measured.*

*David Evans, National Institute of Standards and Technology, private communication.

The significance of this datum for our calculation of actual soot densities is that the amount of material (per square foot of cloud and for a fixed optical attenuation) has a very soft dependence on the particulate dimensions. For purposes of calculation, if we assume a cloud of spherical particles all of radius r , then it is straightforward to show that the mass of these particles, per square foot of cloud and for a given optical attenuation, is proportional to r . However, in the Rayleigh regime, where the optical cross section is proportional to r^6 , we have a mass per unit area dependence in the cloud going as r^{-3} . Thus, with Rayleigh scattering clouds the requisite mass per unit area is a very sensitive function of the particle radii whereas in the geometric scattering case that we consider here this dependence is only linear and thus very "soft" in the regime studied in our experiments. By illustration, if the average particle size in the soot cloud is fifty microns or one hundred microns it is not going to make more than a factor of two difference in the determination of the total mass per unit area. However, for the situation of Rayleigh scattering (in which the optical wavelength is much larger than the particle size) the difference of a factor of two in radius size produces a factor of eight in the final result.

We will now assume that the average particle size in the in situ smoke clouds is the same as that in our high temperature incineration plumes. Note that, in reality, the incineration particulate size is very likely to be less than in the black burning clouds because of evaporative and combustive processing. If we took this effect into account it would only reduce the estimates of particulate mass per cubic foot, which we now derive.

We have repeatedly verified that the solar image is actually totally extinguished for the clouds produced by in situ burning. This tells us immediately that the total optical attenuation is at least eighty db (i.e., 10^8). This conclusion is established by the fact that in a clear sky the direct solar image is 60 db brighter than the adjacent clear sky, and actual extinction of the image requires an attenuation of at least 20 db below the brightness of that adjacent sky.

We will now introduce the conventional notion of an optical depth which is defined as that penetration length into a cloud which provides an attenuation of $1/e = 0.37$. Since we have established that the in situ burn cloud attenuates by at least a factor of 10^8 then we conclude: $e^{-n} = 10^{-8}$, where n = the number of optical depths in this cloud. Therefore, $n = 18$. In conventional optical terms we would describe this cloud as comprising at least 18 optical depths.

We now examine the obscuration produced by our "incineration cloud" and assert, by observation, that it is less than 0.05. This assertion is simply equivalent to the fact that in order for a cloud to be "visible" the scattering or attenuation would need to be in the range of 0.05 in order to exhibit sufficient contrast for an unambiguous observation. This value of 0.05, of course, represents an upper limit. Since our incineration clouds range between barely detectable and genuinely invisible we take the attenuation figure to be 0.05, and so we are lead directly to the equation $e^{-m} = 0.95$, where m = the number of optical depths to these clouds. This equation yields $m = 0.05$.

If we now assume that the distribution of particle sizes in both the in situ burn cloud as well as the incineration cloud are the same we can conclude:

$$\frac{n}{m} = \frac{18}{0.05} = 360 \quad (67)$$

which equals the ratio of particulate matter densities under the assumptions listed to this point. To summarize: the fact that the incineration cloud is transparent and the in situ burn cloud is totally opaque (to visible solar radiation) establishes that the ratio of particulate matter in these two clouds is at least a factor of 360.

The fact that the particulate size distribution in the incineration cloud is definitely less than in the in situ burn cloud means that the actual particulate mass density ratio will, actually be in excess of 360.

Examining the frontispiece again, we note that the fuel consumption was approximately 5

times greater for the incinerator burn than for the in situ combustion. Accordingly, the mass particulate matter in the clouds, per unit of fuel consumed, would then be $5 \times 360 = 1800$.

This result assumes, of course, comparable cross sectional areas of the two clouds when, in fact, the cross sectional area of the in situ burn (see frontispiece) is significantly larger than for the incineration cloud. This factor, in turn, serves to increase the estimate of the particulate ratios.

The final factor for consideration is that the upward velocity of the incineration cloud is significantly greater than that of the in situ burn, both because more fuel is being consumed per hour and the effluent volume (per unit of consumed fuel) is greater because the combustion has been stoichiometric. This factor serves to decrease the estimated particulate ratio.

Approximate evaluations of all of the above factors yield a best estimate of the particulate ratio of 1000, with an estimated error limit of a factor of 3. What we mean by this, specifically, is that we think it highly unlikely that the actual particulate ratio would be greater than 3,000 or less than 350, and that 1,000 is the value which we think is most likely.

It is interesting to note that with a ratio as small as 350 (and the reader is once again referred to the Frontispiece!) the particulate production would still be below that permitted by the EPA standards for commercially operated incinerators.

CHAPTER 3 - OPERATIONAL CONSIDERATIONS

Introduction. We now want to discuss some of the operational aspects of the construction and deployment of in situ incinerators. It is important for the reader to bear in mind that no formal marine or operational engineering studies have been undertaken in the present program; these efforts are the subject of the development

proposal to be submitted. Nevertheless, the basic deployment concepts can be described with some accuracy and several of the important parameters of actual spill scenarios can be established.

Section 3.1. - The In Situ Incinerator. A drawing of a proposed version of the incinerator is shown in figure 3.1. The essential functional aspects are:

1. The incineration chamber and chimney are modeled after the structures that we have tested to date. Entrance ports, structural reinforcement, and other crucial engineering details are not shown in this sketch.
2. The submersible structure is designed only to contain the oil, water and debris pumped into the structure. It has an open bottom and, perhaps, a keel structure for stability, and it has a mechanical integrity sufficient to permit towing at speeds up to 15 knots. (Because this part of the structure is entirely submerged the engineering constraints are actually less severe than these presented to the designer of a conventional seaworthy barge.)
3. Heat pipes, or equivalent thermal transfer equipment, are to be installed so that some fraction of the enormous heat energy developed in the incineration can be transferred to the fluids trapped in the submersible. The object is to maintain a steady temperature regime of 150-180°F. Our experiments indicate that the separation of mousse is strikingly enhanced by maintaining it at these elevated temperatures.
4. Air compressors, monitoring and control equipments, and operational personnel are to be stationed on an adjacent service vessel not shown.

The overall size of this incinerator is designed to be compatible with C-130 (Hercules) flyability. (The Hercules open cargo bay is 8x10x40 feet and acceptable

Fig. 3.1 Sketch of Seagoing Incinerator

cargo weights are approximately 30,000 pounds.) The proposed incinerator will be broken down into 2 loads, and the requisite compressors and control equipment can also be carried by the two aircraft.

The estimate of 7,000 gallons per hour combustion rate is based on an extrapolation from the data developed in our desert tests, and assumes that this rate scales as the cross sectional area of the chimney. This plausible but by no means fundamental scaling law has been tested by us in chimney structures ranging from 2 feet to 5'8" inner diameter and found to be in good approximation to the data.

It is important to note that the only structures above the water line are the catamaran elements, the chimney, collar, and ports. Furthermore, the chimney is insulated so that external surface temperatures will not exceed 400°F. (Temperatures in the combustion chamber interior will exceed 3,000°F.)

We estimate the construction cost of each incinerator at \$120,000, assuming a "production" of approximately 100 units. This analysis is based on the "per pound" data summarized in table 3.1. The closest approximation to our incinerator manufacture is probably that of the naval barges, since they comprise both materials and construction techniques that are very similar to those we anticipate with the incinerators. We doubled the estimated cost (per pound) for the incinerator, compared to barges, because the wiring, control systems, and test requirements are likely to be more extensive.

Section 3.2 - Incinerator storage and maintenance. We anticipate the storage of incinerators at sites where other oil spill mediation equipment is deployed. We propose that these incinerators be hung dry at dockside and lowered to the water for deployment or testing. This dry storage vastly decreases the maintenance costs, compared to those that would be developed by storage in water. The ancillary equipment such as air compressors can be periodically tested without need for floating the system.

COST DATA

<u>ITEM</u>	<u>WEIGHT/LBS</u>	<u>COST</u>	<u>COST/LB</u>
Barges for U.S. Navy (from Ship Design Group, NAV SEA Systems Com.):	-----	-----	\$1.50
Insulated container trailer, without refig:	5,000	\$25,000	\$1.67
Fully appointed furniture van:	16,000	\$35,000	\$2.19
18-gauge welded steel storage cabinet:	404	\$ 618	\$1.53
Bayliner center console fishing boat (20 ft, LOA):	3,074	\$11,780	\$3.83
Ford Tempo:	2,980	\$10,490	\$3.52
Maytag washer:	211	\$ 479	\$2.27

INCINERATOR COST, AT \$3.00/LB, WILL BE: \$120,000

Table 3.1

In our rudimentary systems analysis we have estimated the storage and annual maintenance costs at \$10,000 per incinerator, inclusive of labor and materials. This is far less than the storage and maintenance costs of the service vessels that must also be available at these sites. We have not tried to refine these storage and maintenance costs simply because they are a manifestly minute part of the total systems costs and, accordingly, we do not think they merit more precise evaluation at this time.

Section 3.3 - Operations. In most oil spill situations we anticipate one or more of these incinerators will be towed by conventional (and small) surface service vessels at the spill site, and deployed as shown in figure 3.2a. The reader should take this particular deployment as an example for the discussion which follows.

The basic concept is to pump oil (as well as water and floating debris) into the submersible skirt of each incinerator. In the present design this skirt has a capacity of 34,000 gallons; it is evident that this capacity could be increased to 100,000 gallons or more without adding significantly to the capital cost or to storage and maintenance operations.

We anticipate that the incinerator will be burning oil continuously during the cleanup operation, at a rate of approximately 7,000 gallons per hour. The heat generated by this combustion will be approximately 10^9 btu's per hour which, if all of it were to be deployed to heating, would be sufficient to raise the temperature of one million gallons of sea water (per hour) by 100°F . In our present rough analysis we anticipate there will be a need to

Figure 3.2a

3M FIRE BOOM

Figure 3.2b

heat no more than 50,000 gallons of water per hour; this is assuming, basically, that at least 15% of the total fluid pumped into the incinerator will be combustible.

These estimates lead us to conclude that if only 5% of the heat power generated in the combustion is returned to the submersible chamber, sufficient heat will be available in that chamber to maintain the requisite 150°F in the enclosed fluid. The elevated temperature, in turn, provides a tremendous acceleration of the process of separating the combustible oil from partially or even excessively emulsified compounds of oil and sea water. The elevated temperatures also, of course, accelerate the separation of small items of combustible debris and cause them to float to the burn surface at the throat of the incinerator.

It is useful to contrast our proposed deployment scenario (Figure 3.2a) with that currently being advanced for in situ burning. The operational concept is indicated in figure 3.2b, which is taken directly from the 3M Corporation literature. In this "free burning" approach it is clear that the oil snared by the boom immediately adjacent to the oil spill source cannot be burned; the hazards are simply too great. It is anticipated that when the oil contained in the fireboom, shown in the upper part of figure 3.2b, is totally consumed then that boom will be towed into the spilled oil area and the now filled boom shown in the lower part of figure 3.2b will be towed out away from the ships and will be set afire as shown.

It is hard to overemphasize the operational risks associated with this exchanging process. These booms cannot be towed faster than one knot without losing entrained oil by cavitation and other turbulent phenomena. In addition, these towing operations are seriously compromised by adverse weather conditions.

In the following section we summarize a comparison of our proposed in situ incineration technique with the 3M proposal for in situ burning.

Section 3.4 - Comparison of Incineration with In Situ Burning.

We append below a summary of this comparison, which will be followed by discussion of each component.

Feature	In Situ Burning	In Situ Incineration
Particulate (soot) production	15% by weight	0.015% by weight
Incremental Capital Costs per site.	2.4 million dollars	1.7 million dollars
Incremental labor cost per operational.	12 man hours/per hour	9 man hours/per hour
Operational considerations A	Firebooms are easily brought to site with service vessel, or helicopter crane.	Incinerator can be readily brought to site by service vessel or helicopter crane.
B	Boomed oil must be towed away from vessels prior to burning, a hazardous operation which will also produce several hours of "dead time".	Incineration is continuous, takes place adjacent to the boomed oil, and no towing of boomed oil is required.
C	Oil that is weathered, significantly emulsified, or less than 1mm thick cannot be burned.	All the oil components with specific gravity less than 1.15 will be incinerated, irrespective of weathering or emulsification. There is no minimum thickness.

(CONTINUED ON NEXT PAGE)

D	The factors immediately above predict floating residues.	There is <u>no</u> floating residue after incineration.
Weather parameters A	Towing of the booms can't be accomplished in sea states of greater than 1 foot "chop".	Towing of the booms is not a factor in incineration.
B	Burning can't be sustained in winds exceeding 15 knots, and may be dangerous (depending upon direction) at wind speeds that are significantly less.	Wind speed has no deleterious effect on the incineration, short of winds so violent as to produce a hazard to the physical integrity of the incinerator itself, or to its attending service vessel, or to personnel directly.

Particulate (soot) production. From the social-political perspective it is hard to overemphasize the importance of the enormous reduction in particulate production afforded by incineration. To put this in a somewhat wry perspective, imagine the effects of an in situ incineration of 100,000 gallons of spilled oil in the Los Angeles Harbor area. This would require two of our incinerators operating for about 7 hours. This operation, of course, would be very intriguing to observers. Each incinerator would provide an extraordinarily white hot flame region above their chimneys, but basically no visible smoke.

The actual particulate thrown into the atmosphere during the hypothecated burn would be approximately 100 pounds. Let us contrast this figure with the additional particulate thrown into the atmosphere on this day by the additional automobile exhaust in Los Angeles County due to "sightseers" for the event. It would seem conservative to estimate that 100,000 vehicles would consume one gallon of gasoline, that day, beyond whatever their normal consumption might be. Accordingly, the additional gasoline consumption would amount to 100,000 gallons which would, in turn, project over 3,000 pounds of particulate into the

atmosphere! In other words, the environmental impact of a plausible number of gawkers would be about two orders of magnitude greater than that of the incineration process itself, at least as far as particulate contamination is concerned.

Let us now contrast the effects of straight in situ burning if that were ever permitted. In this case about 100,000 pounds of particulate would be thrown into the atmosphere in the form of very visible black clouds of soot. The deleterious social and political ramifications of this conflagration in the Los Angeles Harbor area would be simply enormous.

Incremental capital costs per site. For this estimate we have postulated two 3M fire booms and 4 service vessels required for the in situ burning, contrasted with one standard boom, three service vessels, and an incinerator. (See figure 3.2b)

Incremental labor costs per operation. For this comparison we are assigning three man hours/per hour for each service vessel. In fact, the difference of three man hours per hour in the postulated operations would become even greater owing to the additional support staff required to carry out the delicate operation of moving four vessels and two towed booms containing oil in essentially continuous exchange.

operational considerations A. The weight of each 3M fire boom is 15,000 pounds in contrast to the estimated 40,000 pounds of each incinerator. In addition, the "packaging" problems presented by the firebooms are somewhat less than that of the incinerator, simply because these booms can be transported with significantly greater density than can the relatively large volume incinerator. However, we believe that the transportability of the two systems are comparable.

Operational considerations B. This comparison springs from essential considerations of operational safety.

Operational considerations C. The inability to burn weathered or emulsified oil, or thin slicks, has been abundantly verified in both our experiments as well as in the limited body of literature on the free burning operations. In contrast, with incineration techniques the combustion is virtually complete, irrespective of weathering or emulsification. The reader is reminded that an important part of the incinerator process is the separation of oil from sea water that is accomplished virtually automatically by maintaining the fluids at about 150°F.

Operational considerations D. The statement that "there is negligible floating residue after incineration" merely reflects the fact that in every one of our intense incinerator burns the only floating residue has been a "sheen" which, because of the evident coloration, comprised a "slick" of oil approximately 1 micrometer thick.

Weather parameters A. We acknowledge the fact that some people may dispute, and with conviction, that firebooms can be towed in sea states exhibiting more than one foot of chop. The important fact here is that towing is not required in incineration.

Weather parameters B. The fact that in situ burning can't be sustained in the referenced winds derives from experimental observations reported extensively in the literature and in private communications. We recognize that quantifying the susceptibility to weather conditions is arguable but we do claim it is obvious that a well designed wood burning stove can be operated in weather conditions far less friendly than can a campfire.

Conclusions and recommendations.

This experimental program has demonstrated the practicality of small incinerators capable of burning very large quantities of oil without significant production of soot clouds. This accomplishment has been based on combustion at very high temperatures (3000° F) and a thermal-mechanical design that continuously assists the separation and consequent burning of hydrocarbons that have become weathered, emulsified, and deficient in volatile components. Our initial systems analysis strongly suggests that this technology can be successfully incorporated into combustive management techniques for oil spills which will present strong operational and sociopolitical advantages over current methods of "free" burning.

We strongly recommend the initiation of a development phase of this program in which a floatable incinerator will be built and tested for seaworthiness as well as combustive performance. It will not be necessary to simulate an actual oil spill; the incinerator's performance can be evaluated by using various oils, including weathered and heavily emulsified materials, together with debris and other materials that can be expected at sea.

Elements of the final phase of this program will depend, of course, on the specific results of the proposed development effort.

APPENDIX A

Test Data

Tape 2

Video ID No. 0000-6937

Date of Experiment:	April 17, 1990
Location of Experiment:	North Campbell Farm
Purpose of Experiment:	Incineration of mousse
Outline of fixture:	12"x 12"x 1/4" Insulating pressed composition board

We poured 4 ounces of our mousse mixture onto the 12"x12"x1/4" insulated platform. We then embedded several small pieces of charcoal, previously soaked in lighter fluid, into the body of our mousse sample. The purpose of the charcoal is to act as an ignition source. Following ignition of these pieces, we attempted to enhance the burning of the mousse with a stream of liquid oxygen/gaseous oxygen emitted from a 165 liter flask of liquid oxygen. The gaseous pressure emitted from the liquid oxygen wand was excess and blew the mousse and charcoal off the platform. We achieved no useable results.

Tape 2
Video ID No. 0938-1842

Date of Experiment:	April 17, 1990
Location of Experiment:	North Campbell Farm
Purpose of Experiment:	Incineration of mousse
Outline of fixture:	12"x 12"x 1/4" insulated platform 165 liter dewar Flame thrower

The purpose of the first part of this experiment was to test the "micro" flame thrower. We started out with a solution of 14 grams of gelling agent per liter of gasoline and the device worked very well. We could successfully project a narrow stream of fire 25 feet. In the second part of this experiment we used the flame thrower and liquid oxygen simultaneously in an attempt to burn mousse. Once again the liquid oxygen wand blew the charcoal off the platform as well as the mousse. The flame thrower performed sufficiently but refinement will be necessary if we are to continue with this device. We were unable to burn the mousse successfully.

For Color version of this photo see page CS-1, Photo C-1.

Tape 2
Video ID No. 0938-1842

Date of Experiment:	April 17, 1990
Location of Experiment:	North Campbell Farm
Purpose of Experiment:	Incineration of mousse
Outline of fixture:	12"x 12"x 1/4" insulated platform 165 liter dewar Flame thrower

The purpose of the first part of this experiment was to test the "micro" flame thrower. We started out with a solution of 14 grams of gelling agent per liter of gasoline and the device worked very well. We could successfully project a narrow stream of fire 25 feet. In the second part of this experiment we used the flame thrower and liquid oxygen simultaneously in an attempt to burn mousse. Once again the liquid oxygen wand blew the charcoal off the platform as well as the mousse. The flame thrower performed sufficiently but refinement will be necessary if we are to continue with this device. We were unable to burn the mousse successfully.

Tape 2
Video ID No. 2188-2511

Date of Experiment:	April 19, 1990
Location of Experiment:	North Campbell Farm
Purpose of Experiment:	Incineration of mousse
Outline of Fixture:	12"x 12"x 1/4" insulated platform 165 liter dewar of liquid oxygen

For this experiment we used approximately 11 ounces of mousse left over from our last experiment. Into this somewhat tainted sample of mousse we embedded several small pieces of charcoal that had been saturated with lighter fluid. Following this we set fire to the embedded charcoal and began to apply the liquid oxygen directly from the dewar line. In doing this we eliminated the dispensing wand in an attempt to reduce the accompanying gaseous pressure normally transferred through the line with the liquid oxygen. Using this technique we were able to burn the mousse completely; however, it required several liter's of liquid oxygen and a considerable amount of time. The smoke generated during this experiment was substantially less than in any of the previous experiments wherein jellied gasoline had been used as a combustive element.

Tape 2
Video ID No. 2511-3275

Date of Experiment:	April 19, 1990
Location of Experiment:	North Campbell Farm
Purpose of Experiment:	Incineration of mousse
Outline of Fixture:	12"x 12"x 1/4" insulated platform 165 liter dewar of liquid oxygen

We placed approximately 20 ounces of mousse on the insulated platform along with several small saturated pieces of charcoal. We lit the charcoal with a napkin and then assisted the combustive process by dribbling liquid oxygen down onto the mousse. The absence of the high velocity jet of gaseous oxygen definitely created a more effective situation for the combustion. The mousse was completely consumed but it took a long time and required several liters of liquid oxygen.

Tape 2
Video ID No. 3276-3547

Date of Experiment:	April 19, 1990
Location of Experiment:	North Campbell Farm
Purpose of Experiment:	Incineration of mousse
Outline of Fixture:	None

In an attempt to create conditions more similar to actual beach situations, we placed 3 ounces of the mousse directly on the sandy soil. In this sample we embedded saturated charcoal. We set fire to the charcoal and proceeded to spray liquid oxygen directly onto the mousse. Most of the mousse burned; however, a small portion of it froze and formed a lump consisting of mousse mixed with gravel, sand and ice.

Tape 2

Video ID No. 4082-4531

Date of Experiment:	April 19, 1990
Location of Experiment:	North Campbell Farm
Purpose of Experiment:	Incineration of mousse

Once again, in order to approximate the conditions of an actual beach more closely, we created a small crater in the sand approximately 18 " in diameter and 6" deep. In this crater we installed a 4 mil mylar film to protect the surrounding soil from contamination. We sprinkled sand and gravel over the film to create our beach and poured 3½ pounds of mousse into the pit. We placed saturated charcoal around the edges of the mousse and lit this with a napkin. Immediately following this we sprayed liquid oxygen directly onto the mixture. The mousse appeared to be completely burned. For our mousse mixture we used 80% water. The remaining 20% was a 50/50 solution of asphalt #20 grade and Prudhoe Bay Crude oil.

Tape 2
Video ID No. 4532-4876

Date of Experiment:	April 23, 1990
Location of Experiment:	North Campbell Farm
Outline of Fixture:	Assembled several large rocks in a stacked configuration.

We formed a rock pile and poured 5½ pounds of mousse on top of the rocks. We allowed the mousse to flow down through and saturate the surface of the rocks. Following this we used the flame thrower in conjunction with the application of liquid oxygen to burn the mousse off the rock pile. The rocks were severely burned. Most of the rocks cracked from the heat and all the rocks were covered with carbon. The mousse for the most part was completely burned off the rocks. If we are to continue to use the flame thrower it will require refinement in the way of safety and control mechanisms. One other consideration is the moisture content of the rocks. [After this experiment was conducted we spoke to a Coast Guard representative, Commander Doug Manning, while we were in Alaska. He indicated that they had several injuries caused by rocks exploding when exposed to sharp rises in temperature.] For this reason it may not be feasible or safe to burn mousse directly on rocky beaches.

For color version of this photo see page CS-1, Photo C-2.

Tape 3
Video ID No. 0000-0227

Date of Experiment:	April 24, 1990
Location of Experiment:	North Campbell Farm
Outline of Fixture:	12" x 12" insulated platform

The object of this experiment was to test the burn rate and efficiency of burning charcoal with the assistance of liquid oxygen/gaseous oxygen. We saturated a dozen small pieces of ordinary charcoal in lighter fluid. Following this, we lit the sample with a match and applied liquid oxygen/gaseous oxygen from directly overhead. The charcoal burned very hot and glowed as the concentrations of liquid oxygen/gaseous oxygen were applied. The gaseous oxygen seemed to have more impact on the burn rate in that its flow could be readily directed and/or controlled.

Tape 3
Video ID No. 0228-0502

Date of Experiment:	April 24, 1990
Location of Experiment:	North Campbell Farm
Outline of Fixture:	12"x 12" insulated platform

This experiment was designed to accelerate the consumption rate of mousse. To do this we added powdered magnesium to our sample. We started out with 3 ounces of mousse, into which we mixed approximately 20 grams of powdered magnesium. For our ignitor we used 2 small pieces of saturated charcoal placed directly into our sample. To this we applied a stream of liquid oxygen/gaseous oxygen from directly overhead down onto the sample. The addition of powdered magnesium seemed to have little or no visible impact on the consumption rate of our sample.

Tape 4
Video ID No. 0000-0756

Date of Experiment:	May 2, 1990
Location of Experiment:	North Campbell Farm
Outline of Fixture	Sheet metal pond 2 ft in dia and 4" in depth with a sheet metal liquid oxygen delivery chute

This experiment was designed to evaluate the impact of adding liquid oxygen directly onto a burning oil slick. We constructed a metal pond approximately 2 feet in diameter with a wall height of 4 inches. Into this pond we poured 5 gallons of fresh water, which gave us an approximate water depth of 3½ inches. To this we added 1 liter of Prudhoe Bay crude oil. The oil floated on top of the water and formed an oil slick approximately 3 millimeters in thickness. Using a napkin as an ignitor/wick we set fire to the oil. One minute into the burn, remote controls were used to dispense 1.5 liters of liquid oxygen directly onto the surface of the burning oil. The intensity of the fire increased substantially and 2 explosions occurred almost immediately. Approximately 2.5 gallons of water were thrown from the pond. Consequently we were unable to determine how much oil burned vs. how much was thrown out of the pond from the explosions. Most of the oil was removed from the pond. At this point we are not sure of the source and/or the exact chemical interaction which caused the 2 explosions. It is evident by the liquid oxygen still floating on the water's surface at the completion of this experiment that we may have used an excessive amount of liquid oxygen in this test.

For color version of this photo see page CS-1, Photo C-3.

Tape 4
Video ID No. 0757-1260

Date of Experiment:	May 2, 1990
Location of Experiment:	North Campbell Farm
Outline of Fixture	Sheet metal pond 2 ft in dia and 4" in depth

This experiment was conducted to establish a baseline burn on the 2 foot fixture. We floated 1 liter of Prudhoe Bay crude oil atop 5 gallons of fresh water. We lit the oil and allowed it to free-burn. As the fire progressed, some 2 minutes into the burn, the combustion started to intensify. A loud crackling noise began to come from the surface of the pond. The water's surface began to boil, throwing small droplets of water and oil into the air. The intensity of the fire during this period was substantial. The entire burn lasted approximately 3 minutes. One half liter of oil was consumed, leaving the heavier fractions of oil on the water surface. This seems to be consistent with the published articles we have been able to locate to date.

Tape 4
Video ID No. 1261-1485

Date of Experiment:	May 2, 1990
Location of Experiment:	North Campbell Farm
Outline of Fixture:	Sheet metal pond 2 ft in diameter and 4" in depth

In our previous experiment we floated 1 liter of crude oil on 5 gallons of fresh water. In a non-assisted free burn we were able to burn off approximately 50% of the crude oil. Examination of the remaining sample indicates that what was burned represented most or all of the lighter fractions of the 1 liter sample. In this experiment we attempted to burn off the remaining 50% or $\frac{1}{2}$ liter left from our last experiment. To accomplish this we augmented the burn with 1 liter of liquid oxygen. The $\frac{1}{2}$ liter sample burned off leaving approximately 1/20th of the original sample still floating on the water's surface. Having previously burned off the lighter fractions from the sample we did not experience any explosions due to the addition of liquid oxygen. This supports the theory we have in reference to the lighter fractions of crude oil being responsible for the formation of highly explosive vapor mixtures when liquid oxygen is applied.

Tape 4
Video ID No. 1486-1559

Date of Experiment:	May 2, 1990
Location of Experiment:	North Campbell Farm
Outline of Fixture:	Sheet metal pond 2 ft in diameter and 4" in depth

We weathered 5 gallons of crude oil in an open container for approximately 1 week, in an attempt to eliminate the lighter fractions. Following this we drew a 1 liter sample of the weathered oil and floated it on water in the 2 foot fixture. First, we unsuccessfully tried to free burn the sample using our standard ignition device. Next, we placed a lit napkin on the oil's surface. While the napkin was burning, 1 liter of liquid oxygen was poured directly onto the surface of the oil. The following combustion consumed 95% of the 1 liter sample. Once again, with the lighter fractions of the crude not present, we were able to conduct this experiment without an explosion.

Tape 4
Video ID No. 1560-2240

Date of Experiment:	May 2, 1990
Location of Experiment:	North Campbell Farm
Outline of Fixture:	Experiment took place on the ground

The burning of rubber tires usually produces huge amounts of black smoke and soot. In this experiment we ignited an 8 inch lawn tractor tire, allowed it to burn black, and then assisted the remainder of the burn with liquid oxygen. The tire burned intensely and completely with less soot and smoke than a non-assisted burn.

For color version of this photo see page CS-1, Photo C-4.

Tape 4
Video ID No. 2241-2516

Date of Experiment:	May 7, 1990
Location of Experiment:	North Campbell Farm
Outline of Fixture:	Sheet metal pond 2 ft in diameter 4" in depth with a 1/4" copper supply tube coupled to a 30 cu ft gaseous oxygen cylinder.

On the 2 foot fixture we floated 1 liter of fresh Prudhoe Bay crude oil. On the bottom of this pond we fabricated a device designed to release gaseous oxygen from below the surface. This device was coupled to a 30 cu ft gaseous oxygen cylinder. Our plan was to light the oil, allow the fire to develop and then turn on the oxygen in an attempt to increase the combustion rate and reduce the residual left on the water's surface after the burn. The gaseous oxygen cylinder ran out before we finished this experiment; consequently we were not able to ascertain definite results. We will reschedule this experiment. Fifty percent of our oil sample was still left on the surface of the water.

Tape 4
Video ID No. 2517-2934

Date of Experiment:	May 7, 1990
Location of Experiment:	North Campbell Farm
Outline of Fixture:	Sheet metal pond 2' in diameter and 4" in depth with a 1/4" copper supply line coupled to a gaseous oxygen cylinder.

In this experiment we started out with the residual $\frac{1}{2}$ liter of oil left from our previous experiment. Our goal was to ignite the oil, allow it to burn very close to its completion, and then supply oxygen to see if we could extend the burn beyond its normal free burn cycle. Unable to ignite the original sample, we added $\frac{1}{2}$ liter of fresh Prudhoe Bay crude. We were successful in extending the consumption of the oil, beyond the free burn cycle, by approximately 30%.

Tape 4
Video ID No. 2935-3576

Date of Experiment:	May 14, 1990
Location of Experiment:	North Campbell Farm
Outline of fixture:	Sheet metal pond 8 ft in diameter and 4" in depth with a 4 ft diameter containment structure within

For this experiment we constructed a metal pond 8 feet in diameter with a wall height of 4 inches. In this fixture we poured approximately 90 gallons of fresh water, to a depth of almost 3 inches. A 4 foot diameter pond made of 18 gauge steel band was placed inside the 8 foot diameter pond. A delivery chute made out of 18 gauge steel will be used to deliver liquid oxygen directly onto the surface of the pond. Two gallons of used crankcase oil was poured into the 4 foot pond. A styrofoam container filled with 2 liters of liquid oxygen was placed at the top of the delivery chute. Two standard office pencils were poked through the bottom of one side on the styrofoam container. The removal of these pencils allowed the liquid oxygen to escape from the styrofoam container and travel down the chute onto the surface of the 4 foot pond. Our first attempt was to try to set fire to the used crankcase oil floating on the pond. It would not burn. Next, a 2x4 piece of wood was placed into the pond, napkins were placed on top of wood and were lit. When we allowed liquid oxygen to travel down the chute to the surface of the 4 foot pond, an intense fire developed. Several small explosions occurred and 75% of the 2 gallon sample was consumed. Following this experiment, we added 1 gallon of used crankcase oil to the $\frac{1}{2}$ gallons still floating on the 4 foot pond. We filled the styrofoam container with 2 liters of liquid oxygen, placed the lit napkins into the pond, and allowed them to burn for approximately 10 seconds. We then allowed liquid oxygen to travel down the chute onto the surface of the 4 foot pond. When the liquid oxygen reached the burning napkins a fire developed. In this experiment we note that only 1 port was open through which liquid oxygen could dispense. The resulting fire was less dramatic and went out before the 2 liters of liquid oxygen were dispensed. Fifty percent of the sample was consumed in the fire.

Tape 4
Video ID No. 2935-3576

Date of Experiment:	May 14, 1990
Location of Experiment:	North Campbell Farm
Outline of fixture:	Sheet metal pond 8 ft in diameter and 4" in depth with a 4 ft diameter containment structure within

Tape 4
Video ID No. 3577-3800

Date of Experiment:	May 15, 1990
Location of Experiment:	North Campbell Farm
Outline of Fixture:	Sheet metal pond 8 ft in diameter

For this experiment we removed the 4 foot diameter band from the 8 foot diameter sheet metal pond. Into the 8 foot pond we poured 8 gallons of used crankcase oil. We placed a styrofoam container atop our sheet metal liquid oxygen delivery chute. Following this we lit a napkin, floated it on the surface of the oil and allowed it to burn for approximately 10 seconds. At this time we removed the pencils from the liquid oxygen container and allowed the liquid oxygen to travel down the chute to the surface of the oil. The resulting fire was very intense; the oil consumed in this blaze amounted to about 6 of the original 8 gallons. The burn lasted 2 minutes and 45 seconds and very little black smoke was visible. The extreme temperatures warped the sheet metal delivery chute and also vaporized the liquid oxygen containment fixture towards the end of the experiment.

For color version of this photo see page CS-1, Photo C-5.

Tape 4
Video ID No. 3801-4118

Date of Experiment:	May 17, 1990
Location of Experiment:	Roof of the Optical Sciences Center
Outline of Fixture:	8" pie pan and eight 6" tall by 2 ft long sheet metal fins

For this experiment we devised an apparatus out of a standard pie pan. We filled the pie pan with alcohol. Around this pie pan we placed 8 metal fins approximately 6 inches tall by 2 foot long. The object of the fins is to control the air flow supporting the burning alcohol. The fins were placed tangentially to the pie pan in an effort to create a vortical air flow pattern. Previous research conducted by Dr. Petersen suggested that the induced vortical drafting would entrain the surrounding air and thereby increase aeration at the center of the combustion. We lit the alcohol with a napkin and observed the flame patterns. Consistent with Dr. Petersen's suggestions, the flame assumed a vortical column and a noticeable increase in flame height was apparent.

Tape 4
Video ID No. 4119-4370

Date of Experiment:	May 22, 1990
Location of Experiment:	North Campbell Farm
Outline of Fixture:	Sheet metal pond 2 ft in diameter and 4" in depth Eight curved sheet metal vanes

For this experiment we floated 1 liter of Prudhoe Bay crude oil in the 2 foot pond. Around the pond we placed 8 sheet iron vanes, bent in a semi-circle configuration. When we set fire to the oil and, as in our previous "pie pan" experiments, the flame formed a vortical column. The addition of vanes in this base line burn increased the flame height by 200% and produced 50% less smoke than the base line burn without vanes. Next we floated 1 liter of Prudhoe Bay crude oil in our 2 foot pond, removed the 8 semi-circle fins and replaced them with comparable straight fins. The results were comparable. It was determined that the vanes definitely helped augment our combustion by supplying additional aeration to the center of the blaze, but the configuration or shape of the vanes seemed to have little impact on the combustion rate. It is to be noted that the burn lasted approximately 1.5 minutes with the vanes and approximately 2 minutes without.

Tape 4
Video ID No. 4371 to the end

Date of Experiment:	May 22, 1990
Location of Experiment:	North Campbell Farm
Outline of Fixture:	Sheet metal pond 2 ft in diameter and 4" in depth

We poured 1 liter of Prudhoe Bay crude oil into the 2 foot pond and ignited it. The object of this experiment was to re-establish our base line data on the 2 foot pond. The burn lasted approximately 2 minutes.

Tape 5
Video ID No. 0000-1907

Date of Experiment:	May 31, 1990
Location of Experiment:	North Campbell Farm
Outline of Fixture:	Sheet metal pond 4 ft in diameter and 4" in depth with eight 4 ft x 4 ft sheet metal vanes

Considering the success of previous experiments, in which we placed sheet metal vanes around a burn fixture, we decided to evaluate those experiments on a larger scale. We placed the 4 ft diameter band back into the center of the 8 ft pond, which allowed us to experiment at the 4 ft level. In this "corral" we floated 2 gallons of used crankcase oil. We placed 8 - 4 ft x 4 ft sheet metal vanes tangentially around the 4 foot pond. At first we were unable to light the oil. We then tried a combination of liquid oxygen and a napkin, and this also did not work. Finally we soaked a handful of paper towels in fuel oil, lit them, and placed them on the surface of the pond. Within 45 seconds a fire developed and the flames formed a well-defined vortical column. Seventy percent of the oil was consumed in this fire.

Next, in an attempt to burn off the remaining 30%, we peppered the surface with hardwood sawdust (approximately 3 pounds). It was hoped that the sawdust would absorb some of the oil and that the oil would be consumed when the sawdust burned. Once again our standard napkin failed to start the oil on fire. To this we added 8 ounces of liquid oxygen and were able to sustain a burn for 30 seconds. The sawdust had no appreciable impact on the experiment.

For color version of this photo see page CS-1, Photo C-6.

Tape 5
Video ID No. 1908-3057

Date of Experiment:	June 1, 1990
Location of Experiment:	North Campbell Farm
Outline of Fixture:	Sheet metal pond 8 ft in diameter and 4" in depth and eight 4 ft x 4 ft sheet metal vanes

In this experiment we decided to increase the scale and burn on the 8 foot pond. We placed 8 - 4 feet by 4 feet sheet metal vanes tangentially around the 8 foot pond. Next we floated 4 gallons of used crankcase oil and 1 liter of fuel oil. We used our standard ignition device and failed to light the oil. Next we poured 8 ounces of liquid oxygen on the surface of the pond and a substantial explosion occurred. No fire developed following the explosion. We placed another ignitor on the pond, followed by a liter of fuel oil and then added 8 ounces of liquid oxygen. At this point the fire started and burned for approximately 1.5 minutes. Approximately 70% of the oil was consumed in this fire.

Next, we moved the sheet metal vanes so that a portion of each vane protruded in from the edge of the pond toward the center for about 18 inches. The fins were still in a tangential configuration. We poured an additional 5 gallons of used crankcase oil onto the pond. We then lit napkins which had been soaked in fuel oil and floated them onto the pond. Following this we added 8 ounces of liquid oxygen. The fire that followed was very intense with flame heights reaching approximately 18 feet. The vanes did a good job controlling the air flow, achieving a vortical flame column.

Tape 5
Video ID No. 3058-3535

Date of Experiment:	June 4, 1990
Location of Experiment:	North Campbell Farm
Outline of Fixture:	8 ft sheet metal pond

Our intention was to do a base line burn on the 8 foot pond. We placed 5 gallons of used crankcase oil on the surface of the pond; and to this added one liter of jellied gasoline for the ignition. Next we set fire to the pond and let it burn almost to completion. As the fire started to go out, we dispensed 8 ounces of liquid oxygen into the fire. This helped rekindle the flame for about 20 seconds, after which we dispensed a 2nd and a 3rd 8 ounce container of liquid oxygen. The addition of liquid oxygen at the end of the fire helped prolong the blaze but not for long. When compared to a similar burn on the same fixture where vanes were used, the smoke emitted from this burn was 200% greater. Only 50% of the oil was consumed in this blaze.

Tape 5
Video ID No. 3536-4389

Date of Experiment:	June 11, 1990
Location of Experiment:	North Campbell Farm
Outline of Fixture:	12"x 12" insulated platform

Dr. Franken attended an Arctic Oil Conference in Edmundton, Canada, in May, and he brought back a yellow powdery substance designed to absorb oil but not water. It was hoped that large concentrations of oil could be collected in this powder and then incinerated. The following experiments were conducted:

1. First we mixed 2 cups of Prudhoe Bay crude oil into 1 package of powder. To this we mixed in 300 cc of fresh water. Next we poured the entire contents of the mixture onto the insulated platform. The water began to run off immediately. Using a napkin we set fire to the sample. The oil seemed to burn off first, followed by the powder. It took about 45 minutes for the oil to completely burn off. As the burn came to an end we poured 8 ounces of liquid oxygen onto the platform. All of the powder and oil burned off but it took a long time.
2. Next we placed approximately 3 ounces of powder on our insulated platform and set it on fire. As the flames consumed the powder it started to reduce or melt. At this point we poured liquid oxygen down over the powder, and it burned rapidly.
3. We placed a package of the powder in the center of a 4 ft x 4 ft sheet of metal. We set fire to the package and poured liquid oxygen directly onto it. The powder that came in contact with the liquid oxygen burned immediately; however the powder is so light it blows away when not contained.

Tape 5
Video ID No. 4390-4578

Date of Experiment:	June 12, 1990
Location of Experiment:	AME Lab
Outline of Fixture:	8" pie pan Eight 6" tall by 2 ft long sheet metal vanes

We conducted a base line burn of alcohol in a standard round pie pan. The idea behind using the lab for this experiment was to be able to conduct the experiment without the prevailing winds we have been experiencing out at the farm. We filled a standard round pie pan with alcohol and set fire to it with a match. The flame fluctuated and seemed to have no consistent or constant direction. Next we placed 8 - 6" x 2 ft long sheet metal vanes around the perimeter of the pie pan in a tangential configuration. The resulting vortical flame configuration was well defined and the flame height increased by approximately 200%. For color version of this photo see page CS-2, Photo C-7 & C-8.

Tape 5
Video ID No. 4579-4710

Date of Experiment:	June 12, 1990
Location of Experiment:	North Campbell Farm
Outline of Fixture:	8 ft sheet metal pond Eight 4 ft x 4 ft sheet metal vanes 350 cfm sidewalk blower

For this experiment we poured 3 gallons of used crankcase oil on the 8 foot pond. We installed 8 - 4 ft x 4 ft sheet metal vanes tangentially around the periphery of the pond to control and increase the air supply. Next we ran a 3" pipe to the center of the pond to which we coupled a 350 cfm conventional sidewalk blower. Utilizing the sidewalk blower in conjunction with the vanes we were able to create a more intense fire, produce less smoke and consume approximately 75% of the oil.

Tape 5
Video ID No. 4711-4765

Date of Experiment:	June 12, 1990
Location of Experiment:	North Campbell Farm
Outline of Fixture:	On the ground/sand

We poured approximately $\frac{1}{2}$ gallon of water on a small portion of sand in an effort to assimilate shoreline conditions. Next we poured approximately 4 ounces of Prudhoe Bay crude oil over the water-saturated sand. We allowed the oil to penetrate the water-saturated sand as much as possible and then poured liquid oxygen directly onto the water/oil solution. Our intention was to freeze the sample with a limited amount of cryogenic fluid in the hope that it could be removed in chunks. The sample did not freeze after adding approximately 8 to 10 ounces of liquid oxygen. It was our conclusion that the amount of cryogenic fluid needed to change the state of the oil would not be economically practical.

Tape 6
Video ID No. 0000-0607

Date of Experiment:	May 29, 1990
Location of Experiment:	North Campbell Farm
Outline of Fixture:	2 ft sheet metal pond 4" in depth Remote liquid oxygen dispenser

In this experiment we fabricated a device designed to dispense liquid oxygen and simultaneously ignite the oil. Our experiment was conducted on the 2 foot fixture, where we floated 1 liter of fresh Prudhoe Bay crude oil. In setting up our remote-controlled ignitor/dispenser we armed it with 8 ounces of liquid oxygen. Upon pressing the start button a solid fuel ignitor fired; this dispensed the liquid oxygen onto the oil surface. A major explosion immediately occurred. The contents of the pond were blown as far as 70 feet. Once again we have confirmed that the combination of fresh crude oil and liquid oxygen create an explosive situation.

Tape 6
Video ID No. 0608-1353

Date of Experiment:	June 2, 1990
Location of Experiment:	North Campbell Farm
Outline of Fixture:	2 ft sheet metal pond 4" in depth

We duplicated our 2 foot burn, however this time using 1 liter of oil which had been weathered for 2 days. The sample would not light using our standard ignitor. We added 8 ounces of fresh Prudhoe Bay crude oil and the sample ignited. Next we used a fire extinguisher to try and put the fire out. It went out very quickly with a single blast from the 5 pound extinguisher. Our goal here was to make sure that we could put out a fire in weathered oil.

Tape 6
Video ID No. 1354-2485

Date of Experiment: June 3, 1990
Location of Experiment: North Campbell Farm

We constructed a 16 foot diameter sheet metal fire pond. Directly in the center of the pond we installed an 8 inch sheet metal air duct which ran under ground for the purpose of supplying air or liquid oxygen to the forthcoming fires. On our 16 ft pond we floated 50 gallons of fresh crude oil. We let this oil float on the water for approximately 2 days prior to the burn. Around the periphery of the 16 foot fire pond we placed 10 - 8 ft x 10 ft sheet metal vanes in a tangential configuration. In addition to the 10 vanes we installed 10 - 5,500 cfm squirrel cage blowers to supply additional aeration to the base of our fire. The ignition was achieved using the remote solid fuel device developed earlier, coupled to approximately 2 gallons of liquid oxygen. Upon ignition we experienced a large explosion, followed by a violent fire. The smoke generated from this fire was much more than we had originally expected, but considerably less than that of an open, free burn. The burn lasted 3 minutes; a free burn at 1/10th of a gallon per square foot per minute would have lasted 6 minutes.

Tape 7
Video ID No. 0000-0178

Date of Experiment:	June 4, 1990
Location of Experiment:	North Campbell Farm

This was a damage assessment of the 16 ft fixture after our last burn, which occurred on June 3, 1990. Most of the water had leaked from the pond. This was due to a separation between the pond and our 8 inch stand or supply pipe. It is surmised that the explosion we experienced in our last experiment caused this rupture. Our mirror was floating in the water, the rubber seal that held the mirror in place melted. The mirror is in surprisingly good condition considering the intensity of the blaze. The sheet metal vanes are warped, some more than others but all are still in useable condition. We have decided to cut elliptical holes in each of the 10 vanes, so we can reposition the 5,500 cfm blowers to achieve a more radial air flow.

Tape 7
Video ID No. 0179-0734

Date of Experiment: June 4, 1990
Location of Experiment: North Campbell Farm

All the necessary repairs have been made to our 16 ft fire pond. We refilled the pond with water. Next we floated 50 gallons of fresh crude oil on the surface. On this experiment we relocated the squirrel cage blowers in a more radial configuration in an attempt to provide additional air to the center of the burn. We also installed 3 -5,500 cfm floor fans around the periphery of the pond for additional air supply. Instead of using liquid oxygen to ignite this fire we simply lit a fuel soaked rag and placed it on the surface of the pond by hand. The ignition for this experiment took approximately one minute longer than using the liquid oxygen. The burn was black and lasted a long time. By rearranging the blowers in a radial position we forced the floating oil to swirl to the outside edge of the pond. Most of the air supply was directed towards the center of the fire and thus the periphery burned very fuel-rich. Damage to the structure was extensive--4 of the 10 vanes were beyond repair. The remaining 6 were warped but will last for approximately one more experiment. Eighty-five percent of the oil was burned in this experiment. It took approximately 6 minutes and was very fuel rich.

Tape 8
Video ID No. 0000-1096

Date of Experiment: July 27, 1990
Location of Experiment: North Campbell Farm

In this experiment we used the 8 foot pond. We placed 8 - 4 ft tall by 6 ft wide sheet metal vanes in a tangential configuration around the pond's periphery. Beneath the surface of the water we placed a copper coil made of one inch copper tubing. On the bottom surface of this coil we drilled 1/8th inch diameter holes approximately one inch apart. We pumped air through the coil using a 185 cfm compressor. Our intention was to provide additional air to the surface of the pond and observe the effect of the agitation provided by the bubbles floating to the surface. We ignited the oil and allowed it to burn for approximately 1 minute; next we turned on the air supply and allowed the fire to burn for about 5 minutes. At this point, it was obvious that the fire was not going to develop much intensity. We turned the compressed air supply off and the fire began to progress rapidly. It was determined that the disruption of the surface by the air bubbles created a cooling effect on the oil and never allowed the fire to pick up momentum. Burn time was 7 minutes and 45 seconds in which we burned 5 gallons of fresh crude oil. The smoke emitted from this burn was substantially less than that of a free burn.

Tape 8
Video ID No. 1340-1737

Date of Experiment: July 27, 1990
Location of Experiment: North Campbell Farm

This is a duplication of our last experiment where we floated 5 gallons of crude oil on the 8 foot pond, placed the copper coil with the 1/8th inch diameter holes facing up approximately 2 inches above the ponds surface. We removed 1 of the 8 sheet metal vanes so that Dr. Franken could video the experiment from a better vantage point. The results were comparable to the prior experiment--the burn lasted approximately 2½ minutes, was smoke free for about 1½ minutes and then became fuel-rich.

For color version of this photo see page CS-2, Photo C-10.

Tape 8
Video ID No. 1097-1339

Date of Experiment:	July 27, 1990
Location of Experiment:	North Campbell Farm

For this experiment we used the 8 ft pond surrounded by 8 - 4 ft wide by 6 ft tall sheet metal vanes with the copper coil in place. Instead of placing the coil with holes facing down we placed the holes facing up. We also elevated the coil to approximately 2 inches above the oil's surface. Our goal here was to allow the surface of the pond to boil while providing additional air directly above the flame. We floated 5 gallons of fresh crude oil; lit the oil and the fire developed immediately. Following this we turned on the 185 cfm air compressor. The fire was much more intense, the vortical column was well-defined and reasonably smoke-free for the first 1 minute and 30 seconds. The fire lasted 2½ minutes and consumed 5 gallons of fresh crude oil. The oil left on the water surface after the burn was minimal, perhaps less than one pint.

Tape 8
Video ID No. 1738-1590

Date of Experiment:	July 30, 1990
Location of Experiment:	North Campbell Farm

In previous experiments we had utilized a copper coil with 1/8" diameter holes drilled approximately 1 foot apart. This coil was then coupled to a 185 cfm air compressor. The intention was to provide additional air just above the surface of the pond during combustion. This apparatus worked out very well; however, we found several segregated patches of oil burning in different areas of the pond's surface. To address this problem we devised a radial surface concentrator. This device will direct the oil floating on the surface to the center of the pond. For this experiment, we changed the vane configuration from a 4 ft tall by 6 ft wide to a 4 ft wide by 6 ft tall. We made this change to find out if the height of the vanes would have an impact on the overall height of the flames and the consumption rate. We also placed 8 - 5,500 cfm squirrel cage blowers around the periphery of the pond to help provide additional aeration. We floated 5 gallons of fresh crude oil, lit the oil and waited for 30 seconds--at which time we turned on the compressed air. The compressed air coil was compromised immediately and had to be turned off. Following this, we turned on the 8 - 5,500 cfm squirrel cage blowers. The fire lasted approximately 4 minutes, 98⁺ percent of the oil was consumed, and the smoke turned white shortly after the blowers came on. The vortical flame column consequent to the 5,500 cfm squirrel cage blowers being turned on was very impressive.

Tape 8
Video ID No. 1600-2413

Date of Experiment: July 30, 1990
Location of Experiment: North Campbell Farm

This experiment took place on the 8 ft pond. We utilized 8 - 4 ft wide by 6 ft tall sheet metal vanes, 8 - 5,500 cfm squirrel cage blowers and a single compressed air jet placed facing up directly in the center of the pond. We floated 5 gallons of fresh crude oil on the pond and set fire to the oil. Approximately 30 seconds into the burn, we turned on the blowers and a large column of black smoke rose from the pond. Approximately 1 minute and 30 seconds into the burn, we turned on the compressed air jet. The flames immediately rose from the surface and covered most of the area above the pond. At this point, the black smoke turned white. The compressed air line was compromised 1½ minutes into the burn by the intense heat emitted from the flame. The black column of smoke returned and was present for the duration of this experiment.

Tape 8

Video ID No. 2414-2790

Date of Experiment:

August 4, 1990

Location of Experiment:

North Campbell Farm

Utilizing the 8 foot pond, we installed 8 sheet metal vanes 4 ft wide by 10 ft tall. To this we reinstalled the 1 inch copper coil and suspended it 2 inches above the oil's surface with the 1/8" diameter holes facing up. Originally on this copper coil we had one end of the coil capped off and the other end of the coil attached to a 185 cfm air compressor. For this experiment, both ends of the copper coil were attached to 185 cfm air compressors. Eight 5,500 cfm squirrel cage blowers were placed around the periphery of the 8 foot pond. They were located between each one of the sheet metal vanes. In addition to this, we installed a 3 inch air supply pipe coupled to a 350 cfm sidewalk blower. The piping for this blower led directly to the center of the pond and discharged at 90° from the surface directly in the center of the pond. For this experiment, we floated 5 gallons of fresh crude oil. We set fire to the oil and 30 seconds into the burn turned on the 5,500 cfm squirrel cage blowers. Next the sidewalk blowers were turned on, then the compressed air. Initially the smoke was thick and black. Thirty seconds after the compressed air was turned on the smoke began to turn grayish white. 90+ percent of the oil was burned. We found that the coil had been compromised at some point during our experiment and were unable to determine exactly when this happened. The experiment lasted approximately 2 minutes and 55 seconds.

For color version of these photo's see page CS-3, Photo's C-11 & C-12.

Tape 8
Video ID No. 2791-3127

Date of Experiment:	August 4, 1990
Location of Experiment:	North Campbell Farm

This experiment took place on the 8 ft pond. We utilized the 4 ft wide x 10 ft tall sheet metal vanes, 8 - 5,500 cfm squirrel cage blowers, a single compressed air jet placed directly in the center of the pond pointed up, and the 350 cfm sidewalk blower piped into the corner of the pond with the emerging jet facing up. We floated 5 gallons of fresh crude oil and lit this sample. Thirty seconds into the burn we turned on the 5,500 cfm squirrel cage blowers; this created a strong vortical flame column. We then turned on the 350 cfm sidewalk blower; the flame's intensity increased and the smoke went from black to gray. Next we turned on the 185 cfm compressed air jet and the smoke disappeared immediately. Following this we turned the 185 cfm compressor off and the black/gray smoke returned. We restarted the 185 cfm air compressor and the smoke disappeared in a matter of seconds. In this experiment we burned 90+ percent of the oil and were able to effectively control the smoke generated from the fire.

Tape 8
Video ID No. 3128-3372

Date of Experiment: August 11, 1990
Location of Experiment: North Campbell Farm

On the 2 foot pond we floated 1 liter of Prudhoe Bay crude oil and we used a street flare to try and ignite the oil. The velocity of the flame emitted from the flare blew the oil away from the flame. Eventually, however, we were able to light the oil. We allowed the oil to burn for approximately 30 seconds until the generated smoke was black. Next we used an airless type sprayer and showered the surface of the burning oil with a mist of water vapor. This was an attempt to alter the flame temperature and observe the impact on the fuel air ratio. The mist appeared to have little or no visible impact on the smoke emissions.

Tape 8
Video ID No. 3373-3862

Date of Experiment: August 22, 1990
Location of Experiment: North Campbell Farm

For this experiment we assembled an 8 ft pond inside the 16 ft pond. In this 8 foot pond we installed 4 - 7/8" compressed air lines attached to 2 - 185 cfm air compressors. We installed 8 - 3-inch steel air supply pipes; each of these were coupled to a 350 cfm sidewalk blower. We also installed a radial surface concentrator designed to direct the burning oil to the center of the pond. We placed 8 - 4 ft wide by 10 ft tall sheet metal vanes tangentially around the 8 ft pond but inside the 16 ft pond. We placed 8 - 5,500 cfm squirrel cage blowers around the periphery of the 16 ft pond directed tangentially inward between each of the 8 sheet metal vanes. We put 10 inches of water in the 16 ft pond and 10 inches of water in the 8 ft pond. Located directly in the center of the 8 ft pond was an 8" stand pipe. This pipe was subterranean and ran from the center of the 8 ft pond underground some 40 feet. Attached to this 8-inch pipe was a 165 liter dewar of liquid oxygen. Then we floated 15 gallons of fresh crude oil on the 8 ft pond and set it on fire. Approximately 45 seconds into the burn we turned on the 5,500 cfm squirrel cage blowers. The blowers prevented the flame from developing so 2 minutes into the burn we turned off the 5,500 cfm squirrel cage blowers. Following this the fire started to develop and we opened the compressed air lines. The smoke disappeared and the fire took on the shape of a blow torch. Next we kicked the 5,500 cfm squirrel cage blowers back in and the torch took on the shape of a vortical fire column and from this point reduced in height from 12 ft to 6 ft. Note: There was no smoke visible. Next we turned on the 8 - 350 cfm sidewalk blowers and opened the valve on the 165 liter liquid oxygen dewar. The flame turned white from the liquid oxygen. The fire started to go out so we turned off the compressed air, the 350 cfm sidewalk blowers and the liquid oxygen. At this point, the fire rekindled and we turned the compressors and the 5,500 cfm squirrel cage blowers back on. Our total burn time was approximately 7 minutes and 45 seconds. At one point we were too lean and had to cut back on the augmentation air to keep the fire burning.

A-44a

Tape 8
Video ID No. 3863-4273

Date of Experiment: August 22, 1990
Location of Experiment: North Campbell Farm

For this experiment we floated 10 gallons of fresh crude oil with the equipment and experimental conditions being exactly the same as described on page A-44. We lit the oil and 1 minute into the burn we turned on the 350 cfm sidewalk blowers, 4 compressed air lines, and opened the valve on the 165 liter liquid oxygen dewar. The flames again resembled a blow torch. Very little black smoke was emitted, flame heights reached approximately 18 ft and the burn lasted for approximately 4 minutes and 51 seconds.

Tape 8
Video ID No. 4273-4642

Date of Experiment: August 23, 1990
Location of Experiment: North Campbell Farm

The equipment and experimental conditions were exactly the same as the previous day (described on page A-44) except that the 5,500 cfm squirrel cage blowers were relocated, being placed approximately 6 feet away from the periphery of the 16 ft pond, directed between the sheet metal vanes. We loaded 15 gallons of fresh crude oil onto the surface of the 8 foot pond. We lit the oil and approximately 1 minute into the burn we turned on the 5,500 cfm squirrel cage blowers and the 350 cfm sidewalk blowers immediately followed by the 185 cfm compressed air lines. The fire was very intense with very little to no black smoke. In our previous experiment it was felt that the 5,500 cfm squirrel cage blowers were disrupting the surface of the oil during the burn and moving them back 6 feet seemed to have a positive effect. The burn lasted approximately 2 minutes.

Tape 8
Video ID No. 4643-4979

Date of Experiment:	August 23, 1990
Location of Experiment:	North Campbell Farm

The equipment and experimental conditions were exactly as described on the previous pages (pages A-44 & A-48). For this burn we floated 15 gallons of crude oil on the 8 foot pond. We lit the oil and 1 minute into the burn we turned on the 5,500 cfm squirrel cage blowers. Next we turned on the first compressor immediately followed by the second compressor. At this point the smoke turned gray. One minute later we turned on the 350 cfm sidewalk blowers. The smoke was still gray but took on more of a whitish color. The fire lasted for approximately 4 minutes and 90⁺ percent of the oil was consumed in the blaze.

Tape 8
Video ID No. 4980-5175

Date of Experiment: August 23, 1990
Location of Experiment: North Campbell Farm

The equipment and experimental conditions were exactly the same as described on page A-47 except that for this experiment we moved the 5,500 cfm squirrel cage blowers back in directly to the edge of the 16 ft pond. We directed them slightly upward so they would not disrupt the surface of the oil. We floated 15 gallons of crude oil on the 8 foot pond. One minute into the burn we turned on the 5,500 cfm squirrel cage blowers followed by the compressed air jets and then the 350 cfm sidewalk blowers. The flames were approximately 15 ft tall and very little black smoke was generated. The fire lasted 2 minutes and 40 seconds. Moving the blowers in is effective as long as they are not directed down onto the oil's surface.

Tape 9
Video ID No. 0000-0575

Date of Experiment:	August 29, 1990
Location of Experiment:	North Campbell Farm

The equipment was identical to that of the previous experiment. In this experiment, we explored techniques to extinguish the fire. We floated 15 gallons of fresh crude oil on the 8 ft pond. We lit the oil and approximately 45 seconds into the burn we turned on the 5,500 cfm squirrel cage blowers and the 350 cfm sidewalk blowers. Thirty seconds later we turned on the compressor. One minute and 30 seconds into the burn we turned off all support to the fire. Mr. Perry walked up to the fixture and tried to put the fire out using a CO₂ fire extinguisher. The attempt was futile, the nozzle on the extinguisher melted and the fire continued to burn as if no attempt had been made.

Tape 9
Video ID No. 0576-1280

Date of Experiment: August 29, 1990
Location of Experiment: North Campbell Farm

The equipment and experimental conditions were as described on page A-44 except that we placed 11" of water in the 16 ft pond and 11" of water in the 8 ft pond. This is significant in that we now had a single surface between the ponds, with no barriers (as in all of the experiments previous to this). This experiment was designed to see if we could contain the fire within the 8 ft pond surface and/or inside the sheet metal vanes. We floated 50 gallons of fresh crude oil, lit this oil, and 30 seconds into the burn we turned on the 5,500 cfm squirrel cage blowers. One minute into the burn we turned on the 10 - 350 cfm sidewalk blowers. One minute and 15 seconds later we turned on the 4 compressed air lines and the fire all but went out. Next we turned off the compressed air to allow the fire to rekindle. Two minutes into the burn we turned off the 5,500 cfm squirrel cage blowers and turned on only the compressed air. At this point the fire developed rather fast, and within a matter of 15 seconds the fire had spread from the 8 ft pond onto the 16 ft pond. Upon this development we turned on the 5,500 cfm squirrel cage blowers and the 350 cfm sidewalk blowers in an attempt to drive the fire back onto the 8 ft pond. The fire continued to expand and spread to the entire 16 ft fixture. The fire was being sucked into the inlet port of the 5,500 cfm squirrel cage blowers. This experiment destroyed 5 of the 5,500 cfm squirrel cage blowers, warped most of the vanes and generated considerable amounts of thick black smoke. This experiment was "successful" in that we learned the consequences of containing the fire, or the lack thereof. We also were able to see the impact that each of the augmenting devices have on the fire. The burn lasted approximately 5 minutes and 30 seconds.

Tape 9
Video ID No. 1281 to 2169

Date of Experiment:	September 17, 1990
Location of Experiment:	North Campbell Farm

We fabricated a 55 gallon barrel with 12 - 2½" by 12" louvers installed around the upper portion of the barrel. On the top of the barrel we fabricated a vane structure having 8 sheet metal vanes approximately 2 feet tall by 16 inches wide arranged in a tangential configuration over the top of the barrel. In the lower segment of the barrel we installed 4 compressed air supply pipes facing up and protruding just above the fluid surface. In this experiment we coupled one of the compressed air lines to a bucket of water. This was designed to inject a mist of water vapor into the flame. During the burn we tried combinations of compressed air and external blowers to achieve the optimum burn. As it turned out, we placed too much oil in the fixture and, upon boiling, oil and water spilled out of the fixture and ran out onto the ground. From here we decided to go back to the drawing board.

Tape 9
Video ID No. 2170-5023

Date of Experiment: October 3, 1990
Location of Experiment: North Campbell Farm

Experiment 1. For this experiment we utilized our 55 gallon barrel fixture. We changed the 4 compressed air supply pipes so that 3 of them were directed back down onto the surface of the oil. This was an attempt to achieve more of an atomization effect on the oil's surface. The fourth pipe was directed straight up the center of the vane fixture. We floated 4 gallons of fresh crude oil. Three minutes into the burn we turned on the compressed air and the fire increased somewhat in intensity. The smoke (what little we had initially) disappeared. The 4 gallons took 15 minutes to burn, which is a very slow burn rate compared to that described on page A-49. In this sense, the results of this experiment were negative. Atomization of the surface seemed to have a substantial negative impact on the burn.

Experiment 2. Next we added 3 gallons of fresh crude oil to the existing mixture in the barrel. Thirty seconds after lighting the oil we turned on the 4 - 5,500 cfm squirrel cage blowers; the fire developed and, approximately 2 minutes and 30 seconds into the burn, we turned on the compressed air supply. The fire expanded and started to come out of the 12 upper louvers. This situation continued for about 1 minute at which point the fire started to diminish. It was determined that the 12 louvers were not positively affecting the burning process. The burn lasted approximately 11 minutes.

Tape 9
Video ID No. 2170-5023

Experiment 3. Next we removed the top 8 vanes and installed a 20" diameter sheet metal stack 6 feet tall. We added 3 gallons of fresh crude oil to the undetermined residual remaining from our previous burns. We lit the oil and the smoke generated was very thick and black. This burn lasted for approximately 9 minutes.

Experiment 4. Next we removed the 20" by 6 ft sheet metal stack and replaced it with an 18 inch by 6 foot sheet metal stack. This was done to increase the air flow down around the stack into the center of the fire. We added 3 gallons of fresh crude oil and lit the mixture. Three minutes into the fire our support members for the stack melted and the stack collapsed. At this point we extinguished the fire, and replaced the support members. Following this we relit the oil still floating on the water's surface. Having burned off most of the lighter factions of this oil sample, the fire was slow to develop. Once we achieved an adequate flame, the temperatures were sufficient to melt the support members once again.

Tape 9
Video ID No. 5023-5526

Date of Experiment: October 13, 1990
Location of Experiment: North Campbell Farm

For this experiment we utilized the 55 gallon fixture. We removed the 18" stack and replaced it with a 17" outer diameter heavy sheet metal stack. The overall height of the 17" stack was 8 feet. Next we floated 5 gallons of crude oil, lit the oil, and 1 minute and 48 seconds into the burn we turned on the compressed air. The black smoke disappeared immediately and the radiant heat increased. After 5 minutes we shut off the compressed air and allowed the fire to rekindle. At 7 minutes we turned on the 5,500 cfm squirrel cage blowers and the flame started to emerge from the stack. Following this we turned on the compressed air and the flames took on the shape of an intense torch. Thirty seconds later a large fire ball belched out of the top of the stack. This burn lasted 12 minutes and 20 seconds.

Tape 9
Video ID No. 5527-5874

Date of Experiment:	October 16, 1990
Location of Experiment:	North Campbell Farm

Utilizing our 55 gallon fixture we maintained the 17" outer diameter by 8 ft tall stack. We floated 5 gallons of fresh crude oil and allowed it to weather for approximately 3 days prior to this experiment. Next we floated an additional 5 gallons of fresh crude oil and set fire to our mixture. Two minutes into the burn we turned on the 5,500 cfm squirrel cage blowers. Some 5 minutes later we developed large amounts of black smoke. At this point we kicked in the compressed air and were able to clean up the smoke and maintain a large plume of fire for the remainder of our burn. This burn was very informative in that we were able to regulate the flame emerging from the top of the stack.

Tape 10
Video ID No. 0000-1064

Date of Experiment:	October 18, 1990
Location of Experiment:	North Campbell Farm

Using our 55-gallon fixture we sealed the 12 louver ports around the top edge, installed a baffle atop of the 17" outer diameter by 8 ft tall stack and eliminated the 4 external 5,500 cfm squirrel cage blowers. Internally we had a single air jet directed straight up through the stack. This jet protruding approximately 8 inches above the fluid surface in the containment fixture. In addition to this central air jet we had 3 compressed air lines, approximately 6 inches above the total fluid surface, directed back down onto the oil. These 3 compressed air lines were to serve as atomizers and were designed to splash the oil up into the combustion area. Both the atomizers and the central air jet were hooked to a single 185 cfm compressor. Into this fixture we floated approximately 10 gallons of fresh crude oil. We ignited the crude oil and approximately 30 seconds into the burn we opened the dampers. The fire intensified, the smoke emitted from the stack turned very black, and at approximately 1 minute and 10 seconds into the burn we turned on the bubblers. At this time the smoke changed from black to brownish-gray, a large plume of fire protruded from the stack and remained there for the duration of this experiment. We noted that when the bubblers were turned on large drops of unburned oil were thrown out the top of the stack. This burn lasted for approximately 6 minutes.

Tape 10
Video ID No. 2745-3520

Date of Experiment:	November 9, 1990
Location of Experiment:	North Campbell Farm

We are conducted this experiment in the 55 gallon fixture to test the thermocouple devices. We placed 3 Type K (Chromel-Alumel, 1148° C max. operating range) thermocouples in the wall of the 8 foot stack and connected them to a Fluke Hydra Data Logger. Dave Clarkson from the John Fluke Manufacturing Co. was on hand to insure the proper equipment performance. We placed 10 gallons of crude oil in the fixture and ignited it. Three minutes into the burn we realized the bubbler was not attached. By several minutes into the burn we had it connected, this burn ended up lasting 12 minutes and was very hot. At this point we returned the Hydra Data Logger to the office and uploaded the information into the computer. The thermocouples were damaged at 1200°C.

Tape 10
Video ID No. 1065-2289

Date of Experiment: October 24, 1990
Location of Experiment: North Campbell Farm

For this experiment we fabricated a new containment fixture made out of 1/8" thick steel. This fixture measures 47" in diameter and has a vertical wall height of 36 inches. Into this fixture we have installed 1 central air jet pointing straight up, protruding approximately 12 inches above the fluid surface. Next we installed 4 atomizer heads. The purpose of these heads was to atomize the oil and force it into the combustion chamber. To this containment fixture we attached a square stack which measures 33" x 33" x 12 ft tall. The stack also is constructed of 1/8" sheet steel. Into the containment fixture we placed 63 gallons of fresh water and 10 gallons of fresh crude oil. We set fire to the oil and approximately 3 minutes into the burn we turned on the central air jet. At this point, the smoke started to clear up and approximately 30 seconds later we turned on the atomizer. The fire immediately started to protrude from the top of our stack. The smoke generated in this experiment was low but was more than had been expected. At approximately 5-6 minutes into the burn the fixture started to turn red hot. The 4 legs supporting the stack became weak from the high temperatures and started to collapse.

For color version of this photo see page CS-3, Photo C-13.

Tape 10
Video ID No. 3521-3937

Date of Experiment:	December 28, 1990
Location of Experiment:	North Campbell Farm

Into our existing 47" diameter containment fixture we installed a culvert stack 30" in diameter by 20 ft tall, lined with a 2" ceramic thermal blanket. To this 30" diameter stack we attached 4 Type K thermocouples connected to our Hydra Data Logger. The central air jet, as well as the atomizer, was still in the same configuration. Onto this fixture we floated 10 gallons of fresh crude oil and ignited it. One minute into the burn we turned on the central air jet and then the atomizer approximately 1 minute later. Large drops of oil were thrown out the top of the stack. The burn was very clean and could be regulated by simply adjusting the atomizer air jet flow, but again the thermocouples were damaged. It had become obvious that we needed thermocouples that could withstand higher temperatures. The maximum operating temperature for Type K thermocouples is 1250° C.

Tape 10
Video ID No. 3938-4423

Date of Experiment: April 28, 1990
Location of Experiment: North Campbell Farm

Using the 47" diameter containment fixture we floated 10 gallons of fresh crude oil. Thirty seconds after ignition we turned on the central air jet and the atomizer. Two minutes and 30 seconds into the burn we cut the central air and regulated the atomizer in an attempt to correlate their effect on the consumption rate. Black smoke was generated once the central air jet was turned off. The Type K thermocouples were all damaged. The burn lasted approximately 13 minutes.

Tape 10
Video ID No. 4424-4855

Date of Experiment:	January 2, 1991
Location of Experiment:	North Campbell Farm

We conducted this experiment in our 47" diameter containment fixture. In an attempt to shield the Type K thermocouples we placed them inside quartz tubing. We floated 19 gallons of fresh crude oil and ignited it. One minute and 30 seconds into the burn we turned on the atomizer and the central air jet. For the next several minutes we varied the air flow to the jet and to the atomizer. We learned that the atomizer controls the consumption rate and may be used to control the fuel air mixtures. The jet controls the smoke issuing from the stack. The central air jet plays a major role in the entrainment of fresh air to the base of the stack. The burn lasted approximately 7 minutes. About 15 gallons of oil was consumed in the blaze, about 3 gallons of oil was thrown out of the top, and a gallon or less was left on the water surface.

For color version of this photo see pag CS-3, Photo C-14.

Tape 10
Video ID No. 4856-5744

Date of Experiment: January 3, 1991
Location of Experiment: North Campbell Farm

This experiment was conducted on the 47" containment fixture. In our previous experiment several gallons of water had evaporated from the containment fixture so we added about 20 gallons of fresh water. This created an imbalance in the water level. We started with 15 gallons of weathered crude. Shortly after ignition we turned on the atomizer, which put the fire out immediately. It was surmised that the lack of fresh volatiles and/or the elevated water level were responsible for the lack of combustion. Following this we added 4 gallons of fresh crude and the fire started to develop very slowly. Ten minutes into the burn we added in 7.5 gallons of fresh crude oil. Finally the fire started to develop. One minute later we kicked in the central air jet and the smoke began to dissipate. At this point we started to speculate about the installation of baffles to control the drafting around the base of the stack. Next we placed a baffle over the top of our stack while the burn was in progress. This allowed the fire to develop but as soon as the atomizers were turned on the fire all but went out. The water level appears to have a direct and immediate impact on the combustion. As it turned out, the water level was above our atomizers and each time we turned on the atomizers they threw water up into the fire and extinguished the blaze. Fifteen to 18 gallons of oil were still present on the surface of the fixture.

Tape 10
Video ID No. 5750-5835

Date of Experiment:	January 4, 1991
Location of Experiment:	North Campbell Farm

For this experiment we used our 47" containment fixture. We started out with 15-17 gallons of unburned oil left from our previous experiment. To this we added 18 gallons of fresh crude oil. We have made adjustments in the atomizer to create less agitation of the fluid surface. We also installed an additional control valve on the atomizer.

Tape 10
Video ID No. 5836-6000

Date of Experiment: January 7, 1991
Location of Experiment: Davis-Monthan Firing Range

This experiment was designed to provide information on the results of firing tracer bullets into containers filled with liquid oxygen. We filled an 8-ounce styrofoam coffee cup with 8-ounces of liquid oxygen. Next we placed this cup in the center of a 9" x 14" pie pan. The pie pan contained a ½" layer of #10 asphalt. Next we fired a 30-06 tracer bullet into the center of the cup from approximately 50 yards away. The cup disintegrated on impact and no combustion was evident. Following this we repeated several variations of the first experiment but none of these encouraged the thought of using tracers as a possible ignition device.

Tape 11
Video ID No. 0000-0755

Date of Experiment:	January 11, 1991
Location of Experiment:	North Campbell Farm

In our 47" diameter containment fixture we have installed a feed pump, designed to add water or oil from below the fluid surface. We have installed baffles around the top edge of the containment fixture designed to control the air supply and/or drafting to the base of the fire. We have also replaced the Type K thermocouples with platinum rhodium Type R. Type R and Type S thermocouples are both platinum-platinum/rhodium. Type R is 6% rhodium and Type S is 30% rhodium. The maximum useful operating temperature is 1450°C for both Types R and S. It is hoped that these will survive the extreme temperatures we are experiencing. Next we floated 19 gallons of fresh crude oil on the pond's surface. One minute and 30 seconds into the burn we opened the central air jet. This increased the intensity of the fire and cut the smoke production substantially. At 2 minutes and 30 seconds into the burn we started to regulate the atomizer and the lower baffles. Five minutes into the burn it was necessary to turn on the feed pump because we had lost approximately 2 inches of water. The burn lasted 7 minutes and consumed 18 gallons of crude oil. We were able to more effectively control the fire with the use of the baffle; however, we are still throwing oil out the top of the 20 foot stack.

Tape 11
Video ID No. 0756-2136

Date of Experiment:	January 11, 1991
Location of Experiment:	North Campbell Farm

We floated 19 gallons of fresh crude oil on the 47" containment fixture and lit the oil with the baffles closed. The fire started to develop very rapidly with very black smoke. Next, we turned on the central air jet and the smoke developed a brownish color. Following this we opened the lower baffles and the fire cleaned up in a matter of seconds. In this experiment we were able to produce a very clean candle shaped flame which protruded 8 ft from the top of our 20 ft stack. Note that in this burn we did not use our atomizer. The burn lasted approximately 19 minutes and consumed 85 to 90% of the oil.

Tape 11
Video ID No. 2137-2745
Page 3

Date of Experiment:	January 11, 1991
Location of Experiment:	North Campbell Farm

In our 47" containment fixture we floated 19 gallons of crude oil. We lit the oil and 1 minute and 30 seconds into the burn we partially opened the lower baffles and started to vary the atomizer. For this experiment we wanted to establish what would happen if we used the baffles and the atomizer but not the central air jet. The results were not very impressive. The fire never developed enough to increase the consumption rate to a significant degree. The burn lasted approximately 9 minutes and we burned approximately 9 gallons of the oil.

Tape 11
Video ID No. 2746-4105
Page 4

Date of Experiment: January 24, 1991
Location of Experiment: North Campbell Farm

To our 47" containment fixture we installed a baffle on top of the stack. This baffle is intended to restrict the oil droplets from being thrown out the top of the stack. We floated 19 gallons of fresh crude oil along with the 9 gallons of oil remaining from our last experiment. Next we lit the oil and 30 seconds into the burn we turned down the central air jet. The smoke started to disappear. One minute into the burn we turned on the atomizer and the fire started to reduce. Regulation of the atomizer was necessary to maintain a constant combustion rate in the fixture. It was speculated that the water level may have been too high in relation to the atomizer. The baffle survived the burn but not without substantial deterioration. The upper baffle was effective in preventing the oil from being thrown out of the stack but the consumption rate was reduced significantly. It does not look like this is a device we can use. The burn lasted approximately 18 minutes.

Tape 11
Video ID No. 4106-4505
Page 5

Date of Experiment:	January 3, 1991
Location of Experiment:	North Campbell Farm

This was not an experiment but merely a demo burn for Duane Barney from the Department of Energy on the 47" fixture.

Tape 11
Video ID No. 4506-5294
Page 6

Date of Experiment: February 17, 1991
Location of Experiment: North Campbell Farm

Once again this was a demo burn. A reporter and a photographer from the Tucson Citizen (Tucson's afternoon newspaper) were present. The 47" diameter containment fixture was once again used with 18 gallons of oil be supplied. The burn took place at night, was very spectacular, and created a strong impression on the news people.

Tape 11
Video ID No. 5720-6000

Date of Experiment:	February 17, 1991
Location of Experiment:	North Campbell Farm

On our 47" containment fixture we floated 30 gallons of crude oil. We reduced the water level so that the atomizer was projecting approximately 1" above the water level and into the oil. We had approximately 5" of oil floating on the water. The flame was very rich.

Tape 11
Video ID No. 5295-5719

Date of Experiment: February 17, 1991
Location of Experiment: North Campbell Farm

To our 47" containment fixture we installed a 10 ft extension on top of the existing 20 ft stack. We floated 30 gallons of fresh crude oil and 1 minute into the burn we turned on the central air jet. The smoke immediately began to clean up. At 1 minute and 45 seconds into the burn we kicked in the atomizer. The flames projected 30 ft above the stack and appeared to be slightly fuel rich but not smokey. The droplets of oil thrown from the top of the stack were drastically reduced (almost nonexistent). The burn lasted approximately 14 minutes.

For color version of this photo see page CS-4, Photo C-15.

Tape 12
Video ID No. 0000-1175

Date of Experiment:	March 8, 1991
Location of Experiment:	North Campbell Farm

For this experiment we fabricated a structure 8 ft in diameter with 4 ft high wall. (See Fig. 2.1) This fixture is constructed on top of a 4 ft tall platform to allow access from the bottom during operation. We installed nine 12 3/4" x 15" tall air supply ports to allow air to enter the chamber from beneath the platform. Four of the 9 ports were equipped with baffles to regulate air flow, another 4 of the ports were equipped with 5,500 cfm squirrel cage blowers. These blowers were directed straight up through the center of the stack. The remaining portal has a single compressed air jet directed straight up through the combustion chamber. Six atomizer heads were installed approximately 6" above the floor of the structure. The central air jet and the atomizer were coupled to two 185 cfm compressors. We placed a 6 ft diameter x 30 ft tall stack directly in the center of the fixture. The stack was lined with a blanket of ceramic fiber insulation 1½" thick. On top of the 4 ft high containment walls we installed 4 baffle assemblies, designed to regulate air flow over the rim. A feed pump was installed to replenish the water loss during operation. This pump is regulated by a temperature censor located inside the fixture. To monitor the internal stack temperature reading we installed 4 Type R thermocouples attached to a Fluke Hydra Data Logger. We floated 37 gallons of fresh crude oil onto 6" of water. The oil was ignited and 2 minutes and 15 seconds into the burn we partially opened the top baffles and opened the lower baffles all the way. At approximately 2 minutes and 30 seconds into the burn we turned on the atomizer and then opened all of the baffles. The fire projecting from the top of the 30 foot stack was incredibly hot and seemed to burn on the rich side for most of the experiment; however it did burn clean for a small time towards the end of the experiment. The feed pump also kicked in as the fire went out. For color photos of this type of burn, see Fig.'s C-16, C-17 and C-18 on page CS-4.

Tape 12

Video ID No. 4251-5289

Date of Experiment:

March 29, 1991

Location of Experiment:

North Campbell Farm

We floated approximately 315 gallons of fresh crude oil. Approximately 2 minutes and 10 seconds into the burn we turned on the central air jet. At 4 minutes into the burn we opened slightly the valve on the first pair of atomizers. At this point a plume of black smoke and fire began to pour out of the stack. Five minutes into the burn we opened the valve completely on the first pair of atomizers. The smoke at this point was substantial. At 5 minutes and 30 seconds into the burn we opened the second and third pair of atomizers. The flames were protruding approximately 70 ft above the top of our 30 ft stack and were accompanied by a considerable amount of thick black smoke. This burn lasted approximately 21 minutes and consumed 315 gallons of fresh crude oil.

For color version of this photo see page CS-4, Photo C-18.

Tape 12
Video ID No. 1859 to 2877

Date of Experiment: March 14, 1991
Location of Experiment: North Campbell Farm

We manufactured approximately 80 gallons of mousse. Our formula was 64 gallons of fresh water, 16 pounds of mineralized salt and 16 gallons of fresh crude oil. To this solution we provided a constant bubbling of air for approximately 4 days. In our 47" containment fixture we poured 24 gallons of fresh crude oil. We lit the oil and manipulated our augmentation devices to achieve the optimum flame. At this point we poured 15 gallons of mousse into the burning containment fixture. The fire went out within seconds of adding the mousse. Following this we reprimed the fixture with an additional 10 gallons of fresh crude oil. We were able to light the fire but as soon as the atomizer was turned on the fire was doused. Using this technique we were not able to burn mousse.

For color version of this photo see page CS-4, Photo C-15.

Tape 12
Video ID No. 2878-3730

Date of Experiment:	March 20, 1991
Location of Experiment:	North Campbell Farm

We devised a dispensing system designed to enable us to burn 300 gallons of fresh crude oil. Our goal here was to conduct a longer burn to achieve a steady state over a longer period of time. Two minutes into the burn we opened the upper air baffles. At 2 minutes and 30 seconds we kicked in the central air jet and the atomizer. The smoke generated by this burn was considerable. On this burn we photographed the smoke against the sun to calibrate the opacity of the plume. This burn lasted for approximately 15 minutes. For color photos see page CS5-5, which show four photo's.

Tape 12
Video ID No. 3731-4250

Date of Experiment:	March 28, 1991
Location of Experiment:	North Campbell Farm

This experiment was conducted at night during total darkness. We floated 50 gallons of fresh crude oil on the 8 ft fixture. In this experiment we wanted to light the oil and allow it to free burn. At 1 minute into the burn we opened the upper dampers. At 2 minutes into the burn we opened the lower dampers. Our goal was to see if the burn would clean up or remain smokey. However, it was so dark we were not able to determine whether indeed the smoke did clean up. The burn lasted for approximately 11 minutes.

Tape 12
Video ID No. 1176-1858

Date of Experiment: March 9, 1991
Location of Experiment: North Campbell Farm

In our 8 foot fixture as described on page A-73 we floated 200 gallons of fresh crude oil. We set fire to the oil and 1 minute and 45 seconds into the burn we opened the lower baffles. At 2 minutes we kicked in the central air jet and atomizer. Immediately following this we had a fire develop underneath the platform. The following fire was black and very fuel rich. All of the 5,500 cfm squirrel cage blowers were melted down. The central air jet supply hose melted and all electrical support to the fire was compromised. In spite of all this, the experiment was useful in that we learned much about the safety precautions required for this scale of experiment. The burn lasted approximately 7 minutes and burned 28 gallons of crude oil.

For color version of this photo see page CS-4, Photo C-17.

APPENDIX C

Color Section

C-1 Incineration of Mousse with LOX assist and flame thrower (A-2).

C-2 Incineration of Mousse on large rocks with LOX assist and flame thrower (A-8).

C-3 2 ft. dia. pond with explosive combustion (A-11).

C-4 Burning of rubber tire with LOX assist (A-15).

C-5 8 ft. dia. pond with LOX delivery chute (A-20).

C-6 Fire pond with 8. 4 ft. x 4 ft. sheet metal vanes (A-24).

C-7 Pie pan alcohol fire for base line (A-28).

C-8 Same pie pan with vanes (A-28).

C-9 Elevated view of 8 ft. pond with vanes, showing vortex (A-25)

C-10 8 ft. pond with parted vane showing air delivery coil (A-37).

C-11 Commencement of burn in 8 ft. pond with vanes (A-41).

C-12 Progression of burn from C-11 (A-41).

C-13 47 inch fixture, 12 ft. stack, air jet and 4 atomizers (A-58).

C-14 47 inch fixture, 20 ft. stack, with 4 type K thermocouples (A-61).

C-15 47 inch fixture with a 30 ft. stack (A-72).

C-16 8 ft. fixture, 30 ft. stack and 4 blowers (A-74).

C-17 8 ft. fixture, 30 ft. stack and 4 blowers (A-75).

C-18 8 ft. fixture, 30 ft. stack, central jet and atomizer (A-79).

Solar images through relatively "thin" soot cloud.
Arrows point to location of sun.

END

**DATE
FILMED**

1 / 19 / 93