DEC 18 1992

DOE/PC/89883--60

DE93 007565

Coal Liquefaction Process Streams Characterization and Evaluation

**Quarterly Technical Progress Report
July 1 Through September 30, 1992**

By: S. D. Brandes, R. A. Winschel, and F. P. Burke

November 1992

CONSOL Inc.
Research & Development
4000 Brownsville Road
Library, PA 15129

Prepared for the:

United States Department of Energy
Contract No. DE-AC22-89PC89883

U.S. DOE Patent Clearance was provided by
Chicago Operations Office on November 12, 1992.

MASTER

A handwritten signature or set of initials, possibly "FB", located at the bottom right of the page.

NOTICE

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States nor any agency thereof, nor any of their employees, makes any warranty, expressed or implied, or assumes any legal liability or responsibility for any third party's use or the results of such use of any information, apparatus, product or process disclosed in this report, or represents that its use by such third party would not infringe privately owned rights.

Coal Liquefaction Process Streams Characterization and Evaluation

**Quarterly Technical Progress Report
July 1 Through September 30, 1992**

By: S. D. Brandes, R. A. Winschel, and F. P. Burke

November 1992

CONSOL Inc.
Research & Development
4000 Brownsville Road
Library, PA 15129

Prepared for the:

United States Department of Energy
Contract No. DE-AC22-89PC89883

U.S. DOE Patent Clearance was provided by
Chicago Operations Office on November 12, 1992.

TABLE OF CONTENTS

	<u>Page</u>
INTRODUCTION	1
Overview	1
Contract Objectives	2
Contract Activities - This Period	3
RESULTS AND DISCUSSION	4
Participants Program Status	4
Summary	4
Phase I	4
Phase II	4
Discussion	4
Phase II	4
CONSOL Evaluation and Executive Summary of Final Report From Lehigh University	5
Introduction	5
Summary	5
Program Description	6
Participant's Methodology	7
Participant's Major Findings	7
CONSOL Evaluation	8
Further Development	9
Participant's Statement of Work	9
References	10
Lehigh Executive Summary	11
CONSOL Evaluation and Executive Summary of Final Report From West Virginia University	11
Introduction	11
Summary	12
Program Description	12
Participant's Methodology	13
Participant's Major Findings	13
CONSOL Evaluation	14
Further Development	15
Participant's Statement of Work	16
References	17
West Virginia University Executive Summary	17
CONSOL Evaluation and Executive Summary of Final Report From Vander Sande Associates	18
Introduction	18
Summary	18
Program Description	19
Participant's Methodology	19
Participant's Major Findings	20
CONSOL Evaluation	21
Further Development	22
Participant's Statement of Work	22
Vander Sande Associates Executive Summary	23
EXPERIMENTAL	25
REFERENCES	26

APPENDICES

<u>Appendix</u>		<u>Page</u>
1	Analytical Data	27
2	The Chemical Nature of Coal Liquid Resids and the Implications for Process Development	49

ABSTRACT

COAL LIQUEFACTION PROCESS STREAMS CHARACTERIZATION AND EVALUATION, QUARTERLY TECHNICAL PROGRESS REPORT, JULY 1 THROUGH SEPTEMBER 30, 1992

This is the twelfth Quarterly Technical Progress Report under DOE Contract DE-AC22-89PC89883. Major topics reported are:

- A summary of the status of the Participants Program is given.
- Summaries of the final reports produced by Lehigh University, West Virginia University, and Vander Sande Associates under the Participants Program are presented.
- Analytical data produced by CONSOL are provided in Appendix 1 for all samples employed in the Participants Program and issued with the samples to research groups in the Participants Program.
- A paper was presented at the 1992 U.S. Department of Energy Pittsburgh Energy Technology Center Liquefaction Contractors' Review Conference, held in Pittsburgh September 23-24, 1992, entitled "The Chemical Nature of Coal Liquid Resids and the Implications for Process Development". It appears as Appendix 2 in this report.

Section 1 INTRODUCTION

This is the Technical Progress Report for the twelfth quarter of activities under DOE Contract No. DE-AC22-89PC89883. It covers the period July 1 through September 30, 1992.

OVERVIEW

Direct coal liquefaction is a complicated chemical process. Recent advances in the technology, which significantly reduced the product costs, have come about through an improved fundamental understanding of liquefaction chemistry. Further improvements are possible, and will depend on continued advances in our knowledge of process chemistry. Supplying this knowledge requires the use of a variety of the tools of analytical chemistry applied to the appropriate samples, and interpretation of the analytical data in context to process development.

The Research and Development Department of CONSOL Inc. (CONSOL) is conducting a three-year project to characterize process and product streams from direct coal liquefaction process development programs sponsored by the Department of Energy. In this project, CONSOL obtains samples from current process development activities in coal liquefaction and coal-oil coprocessing, and characterizes them using established analytical techniques. In addition, selected samples are characterized by other analytical techniques to evaluate their potential for aiding process development. These analyses and interpretation of the results in relation to process operations are provided by a subcontracted project team.

In addition to samples from current process development programs, CONSOL maintains a bank of coal liquids samples from the SRC-I, H-Coal, ITSL (Lummus and Wilsonville) and HRI-CTSL coal liquefaction programs, and the Lummus, HRI and UOP coprocessing development programs. These samples, which represent important stages in the recent development of coal liquefaction technology, are also used in the analytical program.

CONTRACT OBJECTIVES

CONSOL is conducting a three-year program to characterize process and product streams from direct coal liquefaction process development projects. The program objectives are two-fold: 1) to obtain and provide appropriate samples of coal liquids for the evaluation of analytical methodology, and 2) to support ongoing DOE-sponsored coal liquefaction process development efforts. The two broad objectives have considerable overlap and together serve to provide a bridge between process development and analytical chemistry.

More specifically, the first objective is to identify, collect, and disburse appropriate samples of coal liquids for analysis by techniques that hold promise, but are not fully demonstrated, for use in liquefaction process development efforts. Samples are chosen from ongoing DOE-funded liquefaction and coprocessing projects and from CONSOL's collection of coal liquids produced during the past ten years. Samples are chosen based on their relevance to process development programs, and are well-documented in terms of feedstocks, sampling location, time and operating conditions. The samples chosen are sufficient to judge the applicability of the analytical methods being evaluated. These process oils are analyzed by CONSOL in a base characterization program using techniques established in previous CONSOL research. Selected samples also are provided to project team participants (as subcontractors), other researchers active in the analysis of coal liquids, who characterize them using a range of methods beyond those used in the base program. Subcontracts to approximately 16 organizations that have specialized analytical capabilities are a major aspect of this work. Individual analytical specialists from the subcontractors take a major role in interpreting their own results in context to the liquefaction process, and not merely provide data. This portion of the program includes an evaluation of the utility of promising analytical techniques for providing useful information for coal liquefaction process development; those results will be applied to ongoing development efforts. This evaluation will be based on the usefulness of an analytical method in process monitoring, to obtain specific chemical information, and as judged by precision and accuracy.

The second objective is to support the process developers. This includes support in the form of providing results and interpretation of data obtained with the analytical techniques being assessed. However, more directly, appropriate

process oils are being characterized in the base program by a variety of standard techniques that have proven relevance to development efforts. The results from these more routine analyses aid plant operations and planning. Also, these results provide the data needed to select appropriate samples for the non-routine techniques and provide a set of data for correlations with the results of the more exploratory techniques.

CONTRACT ACTIVITIES - THIS PERIOD

Contract activities for this quarter are listed below. Each activity is summarized and discussed under a separate heading in Section 2 of this report. Consequently, there is no overall Summary section provided in this report.

- Substantial progress was made in the Participants Program this quarter. A summary of activities in the Participants Program is presented. Revised final reports were received from all Phase II participants, with the exception of the University of Pittsburgh. Evaluations were written for three of the seven reports received. The CONSOL evaluations and the executive summaries excerpted from those three reports are found in this report.
- Analytical data produced by CONSOL for each sample issued in both Phase I and Phase II of the Participants program are assembled in tabular form in Appendix 1 of this report.
- A paper was presented at the U.S. DOE-PETC Liquefaction Contractors' Review Conference (September 23-24, 1992) by S. D. Brandes. The title of the presentation was "The Chemical Nature of Coal Liquid Resids and the Implications for Process Development". It appears as Appendix 2 in this report.
- Work in progress, but not yet completed this quarter, includes:
 1. Analysis of oils from Wilsonville Run 263.
 2. Literature search concerning analytical methods for coal liquids.
 3. Analysis of twelve oil and coal samples received from HRI PDU Run 260-03.

Section 2

RESULTS AND DISCUSSION

PARTICIPANTS PROGRAM STATUS

SUMMARY

The following items were accomplished in the twelfth quarter of this contract.

All analytical data produced by CONSOL of samples issued to researchers in the Participants Program were compiled and appear in tabulated form as Appendix 1 of this report.

Phase I

Phase I of the program is concluded.

Phase II

The final reports from Lehigh University, West Virginia University, Vander Sande Associates, the University of Chicago, the University of Utah, the University of Kentucky, and Iowa State University were received. A preliminary draft final report was received from the University of Pittsburgh.

CONSOL evaluations were written for subcontracts with Lehigh University, West Virginia University, and Vander Sande Associates. They appear elsewhere in this report, along with the respective executive summaries from the subcontractors' final reports.

One additional sample was requested by and sent to Iowa State University for follow-up of work performed in their subcontract.

DISCUSSION

Phase II

Draft final reports were received from eight of the nine subcontractors in Phase II of the Participants Program. The project with Battelle, Pacific Northwest Laboratory was completed last quarter. Each draft report was reviewed with its authors. Subsequent to review, the final reports for seven of the nine subcontracts were revised by the authors. The final reports from Lehigh University, West Virginia University, Vander Sande Associates, the University of Chicago, the

University of Utah, the University of Kentucky, and Iowa State University were received. CONSOL wrote evaluations for subcontracts with Lehigh University, West Virginia University, and Vander Sande Associates. They appear elsewhere in this report, along with the executive summaries from the subcontractors' final reports.

A preliminary draft final report was received from the University of Pittsburgh. It was reviewed and discussed with the University of Pittsburgh. It was agreed by Pitt that the statement of work had not been satisfied and that additional work would be required before the final report could be accepted. A no-cost time extension was granted to Pitt to complete all contracted work. The final report is expected in October 1992.

CONSOL EVALUATION AND EXECUTIVE SUMMARY OF FINAL REPORT FROM LEHIGH UNIVERSITY

Introduction

Under subcontract from CONSOL Inc. (U.S. DOE Contract No. DE-AC22-89PC89883), Lehigh University studied the use of californium plasma desorption mass spectrometry (^{252}Cf -PDMS), gel permeation chromatography (GPC), and medium pressure liquid chromatography (MPLC) for analysis of tetrahydrofuran-soluble coal derived resids. The following assessment briefly highlights the major findings of the project, and evaluates the potential of the methods for application to coal derived materials. These results will be incorporated by CONSOL into a general overview of the application of novel analytical techniques to coal derived materials at the conclusion of this contract.

Summary

This study demonstrated the feasibility of using ^{252}Cf -PDMS, GPC, and MPLC for the examination of the tetrahydrofuran (THF)-soluble portion of distillation resid materials derived from direct coal liquefaction. The ^{252}Cf -PDMS technique was used to determine molecular weight distributions of twenty-five THF-soluble resids. In order to determine if ^{252}Cf -PDMS responds differently to different chemical classes of compounds, Lehigh separated five of the samples into chemically distinct fractions by MPLC, then analyzed the parent samples, their fractions, and the re-mixed fractions by ^{252}Cf -PDMS and GPC. Irreversible alteration of the samples upon separation was noted by Lehigh. This was confirmed by use of gas chromatographic (GC) analyses. The noted irreversible

alterations prevented a direct comparison of the remixed materials and the original samples. Thus, the selective response of ^{252}Cf -PDMS to different chemical classes of compounds could not be confirmed or ruled out. The number average molecular weights (M_n) obtained by ^{252}Cf -PDMS and GPC agreed well. However, the weight average molecular weights (M_w) obtained by GPC are always higher than the corresponding ^{252}Cf -PDMS results. Number average molecular weights and weight average molecular weights obtained with ^{252}Cf -PDMS and GPC were compared with those obtained by field ionization mass spectrometry (FIMS), previously reported by SRI International¹ for the parent resid samples from which the Lehigh THF-soluble samples were derived. Both GPC and ^{252}Cf -PDMS gave higher weight average molecular weights (M_w) than FIMS, but all three methods gave similar number average molecular weights (M_n). Vapor phase osmometry (VPO) and ebulliometry (two additional methods for determination of average molecular weights) were considered for use on these samples, but not attempted due to lack of time. Further development of the ^{252}Cf -PDMS and GPC methods as process development tools appears to be justified based on the results of this study.

Program Description

This report describes the work performed at Lehigh University under a subcontract from CONSOL Inc., Research and Development. CONSOL's prime contract to the U.S. Department of Energy (Contract No. DE-AC22-89PC89883, "Coal Liquefaction Process Streams Characterization and Evaluation") established a program for the analysis of direct coal liquefaction derived materials. The program involves a number of participating organizations whose analytical expertise is being applied to these materials. This Participants Program has two main objectives. The broad objective is to improve our understanding of fundamental coal liquefaction chemistry to facilitate process improvement and new process development. The specific approach to achieving this objective is to provide a bridge between direct coal liquefaction process development and analytical chemistry by demonstrating the application of various advanced analytical methods to coal liquefaction materials. The methodologies (or techniques) of interest are those which are novel in their application for the support of coal liquefaction and those which have not been fully demonstrated in this application. CONSOL is providing well-documented samples from different direct coal liquefaction production facilities to the program participants. The participants are required to interpret their analytical data in context to the processing conditions under

which the samples were generated. The methodology employed is then evaluated for its usefulness in analyzing direct coal liquefaction derived materials.

Participant's Methodology

Lehigh used ^{252}Cf -PDMS, GPC, MPLC, and GC to analyze the THF-soluble portion of 850°F+ distillation resids. These materials are solids at room temperature. All of the samples were produced at the Wilsonville pilot plant. Two major processing parameters were varied among the Wilsonville runs. These were feed coal and reactor configuration (thermal/catalytic (T/C) or catalytic/catalytic (C/C), and high/low (H/L) or low/high (L/H) reactor temperature). Samples were taken from three locations: between the reactors, after the second-stage reactor, and at the recycle oil tank. These samples are expected to represent different extents of coal liquefaction. Twelve of the samples were composites of samples taken over long periods of single runs. Two interstage samples were obtained from single run periods and were chosen to represent H/L and L/H reactor temperature sequences. Six samples were chosen from two different run periods within a single run to test the effects of T/C, H/L operation as compared to C/T, L/H operation. Two recycle samples were obtained from different run periods within a single run in which the major operating variable was the use of different catalysts.

Participant's Major Findings

The following principal observations for the application of ^{252}Cf -PDMS, GPC, and MPLC to coal liquefaction materials were reported by Lehigh.

The number average molecular weights of the samples determined by GPC were of the same order of magnitude as those obtained by ^{252}Cf -PDMS. The weight average molecular weights determined by GPC were consistently higher, by a factor of about 1.5, than those obtained by ^{252}Cf -PDMS. The authors suggest three possible reasons for the observed differences: 1) The increased sensitivity of the GPC method at high molecular weight causes this region to be more heavily weighted in the weight average molecular weight. 2) The recycle oils are fragmenting in the PDMS. 3) The less polar polymeric materials in the resids give very low, or no, PDMS response. Therefore, PDMS may not be detecting all of the sample.

In comparison to FIMS data¹, ²⁵²Cf-PDMS mass spectra show similarities in the 100 - 1200 m/z range. Below 100 m/z, incomplete subtraction of ²⁵²Cf-PDMS peaks, which arise from the Mylar disc on which the sample is supported, confound the spectra. At m/z greater than 1200, the ²⁵²Cf-PDMS spectra exhibit an envelope of material. The FIMS technique was limited by volatility of the samples and the FIMS results were reported only up to m/e = 1400, where resolution of the spectrum was good.² The additional material detected by ²⁵²Cf-PDMS (m/e >1400) increases the determined weight average molecular weights of the samples to twice the FIMS values. However, the number average molecular weights are identical (within experimental error, ± 10 Da).

To determine if the ²⁵²Cf-PDMS technique discriminates by chemical class in the ionization process, MPLC was used to separate five samples into distinct chemical classes (oils, asphaltenes, and preasphaltenes). The parent samples, the MPLC fractions, and the remixed fractions were analyzed by GPC and ²⁵²Cf-PDMS. Remixed samples had a consistently lower M_n than the original THF-soluble resid sample. No clear pattern was apparent for M_w ; however, the polydispersity (ratio of M_w/M_n) obtained from either method was consistently higher for all remixed samples. Gas chromatography was used to examine the original and remixed materials to examine possible causes for the differences. It was determined that the remixed materials were significantly different from the original samples. It was, therefore, not possible to determine whether or not discrimination by chemical class occurs in the ionization process of the ²⁵²Cf-PDMS experiment. Examination of the ²⁵²Cf-PDMS profiles of the separated fractions showed individual mass ions in the oils and asphaltene fractions and remixed fractions. These were not apparent in the original THF-soluble resid sample or in the preasphaltene fraction.

CONSOL Evaluation

The ²⁵²Cf-PDMS and GPC techniques were shown to be capable of determining molecular weight distributions and average molecular weight values of direct coal liquefaction resid samples. The question of discrimination by chemical class by the ionization process of the ²⁵²Cf-PDMS technique is yet unanswered. It is possible with the ²⁵²Cf-PDMS method to detect materials with molecular weights on the order of 30,000 Da. The THF-soluble coal-derived resids examined in this study exhibited molecular weight envelopes which extended to approximately 3000

Da. It may be possible that some of the higher molecular weight material (m/e >1400, which is the upper limit reported by the FIMS method) is the result of recombination reactions occurring post ionization². Although the FIMS technique is limited by volatility, the number average molecular weights obtained by the ²⁵²Cf-PDMS technique on THF-soluble portions of the resids agree well with the FIMS results.

Samples obtained from different runs with different processing parameters could not be distinguished by comparison of the number or weight average molecular weights obtained by the ²⁵²Cf-PDMS or GPC techniques. A more detailed examination of the ²⁵²Cf-PDMS profiles may prove to be of some utility in discerning differences in the process-derived resid samples.

The ²⁵²Cf-PDMS equipment used in this study was a Bio-ion Model 20 spectrometer; it costs about \$220,000. It requires approximately one-half hour to prepare a solvent-soluble sample and approximately fifteen minutes to acquire data.

Further Development

There are a number of avenues for further development of the ²⁵²Cf-PDMS and GPC techniques for coal liquefaction derived resids. Lehigh suggested a more extensive study of the application of the ²⁵²Cf-PDMS and GPC techniques to a larger selection of resid samples, and other coal-derived samples, of high molecular weight. It is recommended by CONSOL that the molecular weight profiles obtained from ²⁵²Cf-PDMS be carefully examined to detect any systematic variations which can be attributed to changes in processing conditions. The appearance of individual low-mass ions in the oils and asphaltene fractions which are not apparent in the whole original THF-soluble resid spectrum should be further investigated in light of the corresponding appearance of these same mass ions in the FIMS spectra¹ and field desorption mass spectrometry (FDMS) spectra³. It also is recommended that a further study be made to determine if chemical class discrimination affects the results from ²⁵²Cf-PDMS.

Participant's Statement of Work

The analysis of coal products by ²⁵²Cf-Plasma Desorption Mass Spectrometry (²⁵²Cf-PDMS) has been only briefly explored. ²⁵²Cf-PDMS is a technique which has been used for a variety of applications in the biochemical field and has shown some

utility in the examination of petroleum heavy oils and bottoms. It has not, however, been fully demonstrated in its application to the chemistry of coal conversion. As such, it fits well within the scope of the participants program.

The application of ^{252}Cf -PDMS to a reasonably large sample set (25 samples) will allow a demonstration of the value of this technique. These samples have been selected so that the utility of ^{252}Cf -PDMS for addressing the issue of resid reactivity can be evaluated. The twenty-five samples will be supplied to Lehigh with the following information: elemental analyses, ash content, ash elemental analysis, phenolic -OH concentration, calorific value, hydrogen classes by ^1H -NMR, and the full history of the sample (plant, process conditions, age, and storage conditions). Additionally, spectra obtained by other mass spectrometric techniques, such as field ionization mass spectrometry (FIMS) and field desorption mass spectrometry (FDMS), will be supplied for samples, as available. All samples are the tetrahydrofuran-soluble portion of non-distillable residual materials. Sample size will be approximately 1g. Most samples will be brittle pitch-like materials that will be supplied as approximately minus 60 mesh powder.

The question of whether or not discrimination is inherent in the ionization process in ^{252}Cf -PDMS will be addressed by preliminary separation of five of the samples into aliphatic rich and aromatic rich fractions. These samples will be separated into chemical classes using liquid chromatographic techniques on a silica gel support. Material retained on the column will be recovered by dissolution of the silica gel in NaOH solution. Each fraction obtained will then be examined by ^{252}Cf -PDMS. The sample fractions will then be remixed and spectra obtained. Each of the five samples and their fractions will be examined by gel permeation chromatography, vapor phase osmometry, and, if possible, by ebulliometry to obtain comparative molecular weight data.

Repeat analyses will be performed as necessary to determine reproducibility.

References

1. Malhotra, R.; McMillen, D. F. "Coal Liquefaction Process Streams Characterization and Evaluation; Characterization of Coal Liquids by Field Ionization Mass Spectrometry and Iodotrimethylsilane Derivatization, Topical Report," DOE/PC 89883-39, January 1992.
2. Personal communication with R. Malhotra, SRI International.

3. Campbell, J. A.; Linehan, J. C.; Robins, W. H. "Coal Liquefaction Process Streams Characterization and Evaluation; Characterization of Coal Derived Materials by Field Desorption Mass Spectrometry, Two-Dimensional Nuclear Magnetic Resonance, Supercritical Fluid Extraction, and Supercritical Fluid Chromatography/Mass Spectrometry, Topical Report," DOE/PC 89883-51, July 1992.

Lehigh Executive Summary

Californium Plasma Desorption Mass Spectrometry (PDMS) has been used to analyze heavy distillation residues obtained from direct coal liquefaction processes. The characteristics of the ^{252}Cf -PDMS technique for the analysis of these non-polar materials were determined, especially the efficiency with which molecules of different chemical type are ionized and detected. The molecular weight distributions of several THF-soluble portions of non-distillable residual materials (850°F⁺ "resids") obtained from the Wilsonville pilot plant were determined. These data are compared to results obtained by Field Ionization Mass Spectrometry (FIMS) and Gel Permeation Chromatography (GPC). In general, number average molecular weights for all three techniques agreed well. Both GPC and PDMS gave higher weight average molecular weights than FIMS and agreed with each other for samples having weight averages below 2000 amu. The molecular weight distributions for these resids produced under a range of conditions are quite similar. The separation of the resids into chemical classes by Medium Pressure Column Chromatography (MPLC) on silica gel is irreversible. PDMS is a rapid effective method for obtaining molecular weight distributions for direct liquefaction resids.

CONSOL EVALUATION AND EXECUTIVE SUMMARY OF FINAL REPORT FROM WEST VIRGINIA UNIVERSITY

Introduction

Under subcontract from CONSOL Inc. (DOE Contract No. DE-AC22-89PC89883), West Virginia University studied the use of temperature-programmed electron spin resonance (ESR) and thermogravimetric analysis (TGA) to analyze coal derived materials. The following assessment briefly highlights the major findings of the project, and evaluates the potential of the method for application to coal derived materials. These results will be incorporated by CONSOL into a general overview of the application of novel analytical techniques to coal derived materials at the conclusion of this contract.

Summary

This study demonstrated the feasibility of using temperature-programmed ESR and TGA for the examination of tetrahydrofuran (THF)-soluble distillation resid materials derived from direct coal liquefaction. TGA is used to quantitate volatile losses in a temperature-programmed experiment. The TGA data are used to correct the free radical densities obtained by ESR as volatile material is evolved from the samples in the temperature-programmed ESR experiment. The techniques, when employed in tandem, can be used to determine the content and nature of the free radicals in the samples at temperatures approximating those used in the liquefaction process.

TGA and ESR experiments were performed in flowing nitrogen and hydrogen, at ambient pressure. No significant difference was observed in the ESR spectra in the different atmospheres, except in the case of low-rank coal-derived resids. The TGA results, however, were systematically different; mass loss in an H₂ atmosphere is consistently higher than that observed in an N₂ atmosphere. It was shown that temperature-programmed ESR, which can pinpoint conditions at which the free radical content is the highest, has potential to be a guide for the appropriate choice of conditions for optimum resid upgrading. Further development of these combined analytical methods as process development tools appears justified based on these results.

Program Description

This report describes the work performed at West Virginia University under a subcontract from CONSOL Inc., Research and Development. CONSOL's prime contract to the U.S. Department of Energy (Contract No. DE-AC22-89PC89883, "Coal Liquefaction Process Streams Characterization and Evaluation") established a program for the analysis of direct coal liquefaction derived materials. The program involves a number of participating organizations whose analytical expertise is being applied to these materials. This Participants Program has two main objectives. The broad objective is to improve our understanding of fundamental coal liquefaction chemistry to facilitate process improvement and new process development. The specific approach to achieving this objective is to provide a bridge between direct coal liquefaction process development and analytical chemistry by demonstrating the application of various advanced analytical methods to coal liquefaction materials. The methodologies (or

techniques) of interest are those which are novel in their application for the support of coal liquefaction and those which have not been fully demonstrated in this application. CONSOL is providing well-documented samples from different direct coal liquefaction process development facilities to the program participants. The participants are required to interpret their analytical data in context to the processing conditions under which the samples were generated. The methodology employed is then evaluated for its usefulness in analyzing direct coal liquefaction derived materials.

Participant's Methodology

West Virginia used ESR and TGA as associated techniques to analyze the THF-soluble portion of 850°F distillation resid. The ten samples were produced at the Wilsonville pilot plant. Two major processing parameters were varied among the Wilsonville runs: feed coal and reactor configuration (thermal/catalytic vs catalytic/catalytic). Samples from Wilsonville were taken from three locations: between the reactors, after the second-stage reactor, and at the recycle oil tank. These samples are expected to represent different extents of coal liquefaction. Six of the ten Wilsonville samples were composites of samples taken over long periods of single runs. Four samples were obtained from single run periods and were chosen to represent thermal/catalytic vs catalytic/thermal processing.

Participant's Major Findings

The following principal observations for the application of TGA and ESR to coal liquefaction materials were reported by West Virginia University.

Most of the observed weight loss in the TGA experiments for all samples occurred between 300 and 500°C and was greater in a flowing H₂ atmosphere than in N₂. This, it was speculated, may be the result of the suppression of retrograde reactions in the presence of H₂. The amount of material remaining (char) correlates with the aromaticity of the samples. A similar observation was noted previously by another program participant for a number of the THF-soluble samples, including six of the identical samples that were in the WVU sample set.¹ For all samples, weight loss began at a lower temperature in H₂ than in N₂.

An inverse relationship between the ESR free radical densities (N) and the H/C ratios of the samples was found. This was interpreted as indicating that the lower the free radical content is, the more hydrogenated the resid; thus, resids with low N values are more upgraded than resids with higher N values. Increases of an order of magnitude in N were observed for all resid samples at low temperatures (100 to 200°C), although there was no accompanying mass loss. This behavior, which is not found in coal samples, is apparently due to cleavage of weak bonds not accompanied by the evolution of volatile materials. At temperatures above 300°C, there is a fifty-fold increase in N corresponding to the evolution of volatile species that is associated with the rupture of bonds in the sample (thermal cracking).

N values for resids are smaller than those of the parent (bituminous) coals by more than an order of magnitude. The samples in the set derived from Illinois No. 6 coal produced the greatest yield of volatile materials. They also have the highest H/C ratio of the samples studied and a slightly higher free radical density when measured in H₂ than in N₂. In contrast, the samples derived from a subbituminous coal (Wyodak and Anderson seam) which have the lowest H/C values among the samples studied and yield lower N values in H₂ than in N₂, are believed to be hydrogenated under the conditions of the ESR experiment.

Measured linewidths (ΔH) for all samples show a variation with temperature, but they are unaffected by atmosphere (H₂ or N₂). Linewidths for the resid samples increase from about 8 Gauss at room temperature to about 12 Gauss at about 200°C, corresponding to the ten-fold increase in free radical density (N), and then decrease to about 2 Gauss by 500°C. The decrease is associated with the fluid state of the samples at the elevated temperatures. The g-values of the samples fell within the range of 2.0015 and 2.0025 (± 0.0005). There was no influence of atmosphere on g-value. There was a slight decrease in the value with increasing temperature. This behavior is similar to that observed for neutral oxygen-containing species.

CONSOL Evaluation

The TGA and temperature-programmed ESR techniques were shown in this study to have potential for the analysis of direct coal liquefaction resid samples and for providing direction for process development. The free radical density (N) may

prove to be a good indicator of resid reactivity. The lower the N value, the more hydrogenated and perhaps, therefore, more reactive the resid. This inference concerning reactivity is supported by the TGA data, which showed that samples with lower N values were more volatile.

The N values of the resids were observed to increase ten-fold at low temperature (100 to 200°C) with no corresponding volatilization. This behavior, which is not observed in the ESR of the parent coals, indicates that resid chemistry occurs at quite low temperatures. Thus, it may be possible to hydrogenate resids in this low temperature range if an appropriate catalyst can be found.

Definite identification of the free radicals could not be obtained, although their ESR behavior is most similar to the neutral oxygen-containing species.

Because there was almost no difference in the ESR spectra under H₂ and N₂ at ambient pressure, indicating that there was little or no interaction of the H₂ with the resid, it was not possible to determine a hydrogen donor ability (HDA) index for these samples. However, it may be possible to obtain an HDA index at elevated pressure.

The Mettler TA3000 TGA apparatus used in this work costs approximately \$40,000. The 9.4 GHz Varian ESR with the hot probe accessory costs about \$250,000. ESR experiments, including raw data conversion, require approximately two days per sample. TGA experiments require approximately four hours per sample. Data interpretation is not trivial and requires a professional trained in ESR methods. Expendable supplies (ESR tubes, TGA sample holders, and purge gases) for the analysis of the ten samples cost approximately \$1000.

Further Development

There are a number of avenues for further development of the ESR and TGA techniques for coal liquefaction derived resids. Suggested by the West Virginia University researchers is an expanded use of the TGA as a combined tool with proton nuclear magnetic resonance spectroscopy or Fourier transform infrared spectroscopy for analysis of the evolved volatile materials from the resids. Some utility of this latter combined technique has been previously demonstrated in this program.¹ It also was suggested, that in the temperature range in which

the ESR indicates that there is an increase in free radical content with minimal weight loss, studies should be made of the usefulness of different hydrogenation catalysts. Also, expanding the experimental program to include high-pressure ESR experiments with and without catalysts would provide more insight into the behavior of the resids under direct coal liquefaction processing conditions. Another suggestion for further development of the technique includes establishment of a better correlation between feed coal and resid properties by use of the ESR technique.

Participant's Statement of Work

Electron spin resonance (ESR) spectroscopy has been used for the investigation of coal. It has not, however, been fully demonstrated for the characterization of coal liquefaction resids nor for its ability to support coal liquefaction process development. As such, it fits well within the scope of the participants program.

The application of ESR to a sample set of 10 samples will allow a demonstration of the value of this technique for the characterization of coal liquefaction-derived resids. These samples have been selected so that the utility of ESR for addressing the issue of resid reactivity can be evaluated. Each sample will be subjected to a temperature-programmed ESR experiment in both a flowing hydrogen atmosphere and a flowing nitrogen atmosphere. Each ESR experiment will be accompanied by a corresponding thermogravimetric analysis (TGA). The conditions of the TGA experiment will mimic those of the corresponding ESR experiment. Both the ESR and TGA experiments will be run at atmospheric pressure. The maximum temperature used in the temperature programs of the ESR and TGA experiments will be at least as high as the highest processing temperature achieved when the samples were produced. ESR spectra will be collected at intervals during the temperature program. The data collected by the ESR experiment will include intensity, g-value, and line shape and their evolution with temperature. Based on the maxima of free radical density, as a function of temperature, the hydrogen donor ability (HA) of each sample will be evaluated. The samples will be supplied to WVU with the following information, as available: elemental analyses, ash content, ash elemental analysis, phenolic -OH concentration, calorific value, hydrogen classes by ^1H -NMR, and the full history of the sample (plant, process conditions including maximum processing temperature, age, and storage

conditions). The samples are the tetrahydrofuran-soluble portion of non-distillable residual materials. Sample size will be at least 1g. The ten soluble resid samples will be solid materials that will be supplied as approximately minus 60 mesh powders.

References

1. Serio, M. A.; Hsisheng, T.; Bassilakis, R.; Solomon, P. R. "Coal Liquefaction Process Streams Characterization and Evaluation; FT-IR Methods for Characterization of Coal Liquefaction Products, Topical Report", DOE/PC 89883-45, April 1992.

West Virginia University Executive Summary

In this report, results on the characterization of ten resid samples using thermogravimetric analysis (TGA) and electron spin resonance (ESR) spectroscopy are presented. The resid samples are THF-soluble fractions of solid coal liquefaction material (850°F- resids) obtained from the liquefaction of three coals. TGA measurements of weight loss and reaction rate were carried out from room temperature (RT) to 500°C in flowing N₂ and H₂ gases. In ESR spectroscopy, where only a single line is observed, the free radical density N as well as the g-values and linewidths ΔH are reported from RT to 500°C, again in flowing N₂ and H₂ gases.

TGA measurements show that most of the weight loss occurs between 300 and 500°C, more weight is lost in H₂ than in N₂ and that weight loss begins to occur at lower temperatures in H₂ than in N₂. A strong correlation is observed between the remaining weight in H₂ at 500°C and the aromaticity of the resids.

The ESR results show that the RT free radical density N for resids is smaller by over an order of magnitude than N for bituminous coals. This is due to hydrogenation in liquefaction which lowers N by capping the free radicals. The variation of the RT N among resids bears an approximate proportionality to the atomic C/H ratio of resids. On heating the samples in N₂ and H₂, nearly an order of magnitude increase in N is observed between 100 and 200°C in all samples without significant weight loss, suggesting that this increase in N is due to thermolysis of the weaker bonds in resids. From 300°C to 500°C, another increase in N by a factor of about 50 is observed. Since this region coincides with the massive evolution of volatiles in TGA, this increase in N is due to severe

thermal cracking. The changes in g-values with temperature are not significant, whereas the linewidth ΔH first increases reaching peak values of about 12 Gauss near 200°C and then decreases monotonically with increasing temperatures, reaching values of about 2 Gauss near 500°C. A tentative interpretation for this behavior is advanced.

Based on the above results, two suggestions for applications to coal liquefaction processes are immediately apparent: (i) weight loss in H₂ flow in TGA experiments, when combined with ¹H-NMR and possibly FTIR is likely to provide an excellent tool for characterizing resids; (ii) considerable thermal bond cleavage observed in ESR experiments in the 100°C to 200°C range without weight loss suggests that a suitable catalyst may promote hydrogenation of the resids at these temperatures.

CONSOL EVALUATION AND EXECUTIVE SUMMARY OF FINAL REPORT FROM VANDER SANDE ASSOCIATES

Introduction

Under subcontract from CONSOL Inc. (U.S. DOE Contract No. DE-AC22-89PC89883), Vander Sande Associates studied the use of transmission electron microscopy (TEM), scanning transmission electron microscopy (STEM) and energy dispersive X-ray (EDX) spectroscopy for analysis of dispersed catalysts in the insoluble portion of coal-derived materials. Dr. John B. Vander Sande, the principal investigator of this work, is vice president of Vander Sande Associates and professor of Materials Science and Engineering at Massachusetts Institute of Technology. The following assessment briefly highlights the major findings of the project, and evaluates the potential of the method for application to coal derived materials. These results will be incorporated by CONSOL into a general overview of the application of novel analytical techniques to coal derived materials at the conclusion of this contract.

Summary

This study demonstrated the feasibility of using scanning transmission electron microscopy (STEM) accompanied by energy dispersive X-ray (EDX) spectroscopy for the examination of the tetrahydrofuran (THF)-insoluble portion of distillation resid materials derived from direct coal liquefaction. The technique was able to determine the distribution, morphology, and elemental composition of dispersed

catalyst components in the insoluble portion of the distillation resids. An attempt was made to use transmission electron microscopy (TEM) on these samples; however, detailed compositional information could not be obtained. Further development of STEM and EDX as aids to process development apparently are justified based on these results.

Program Description

This report describes the work performed by Vander Sande Associates under a subcontract from CONSOL Inc., Research and Development. CONSOL's prime contract to the U.S. Department of Energy (Contract No. DE-AC22-89PC89883, "Coal Liquefaction Process Streams Characterization and Evaluation") established a program for the analysis of direct coal liquefaction derived materials. The program involves a number of participating organizations whose analytical expertise is being applied to these materials. This Participants Program has two main objectives. The broad objective is to improve our understanding of fundamental coal liquefaction chemistry to facilitate process improvement and new process development. The specific approach to achieving this objective is to provide a bridge between direct coal liquefaction process development and analytical chemistry by demonstrating the application of various advanced analytical methods to coal liquefaction materials. The methodologies (or techniques) of interest are those which are novel in their application for the support of coal liquefaction and those which have not been fully demonstrated in this application. CONSOL is providing well-documented samples from different direct coal liquefaction production facilities to the program participants. The participants are required to interpret their analytical data in context to the processing conditions under which the samples were generated. The methodology employed is then evaluated for its usefulness in analyzing direct coal liquefaction derived materials.

Participant's Methodology

Vander Sande Associates used STEM and EDX to analyze the THF-insoluble portion of distillation resids (850°F+) that were known to contain a molybdenum-based dispersed catalyst used in the liquefaction process. The insoluble portion of the resid is a solid at room temperature and contains organic material and mineral matter native to the coal as well as the added catalyst. The original samples were produced at the Wilsonville pilot plant. The major processing

parameter which was considered in the choice of these samples was the concentration of the added catalyst. Samples were obtained from two processing runs which used the same feed coal. In one run, slurry-phase (dispersed) molybdenum catalyst was fed to the first reactor. In the other run, slurry catalyst was fed to the first reactor in the two-stage process and supported catalyst was used in the second reactor. Samples from Wilsonville were taken from three locations: between the reactors, after the second-stage reactor, and at the recycle oil vessel. These samples are expected to represent different extents of coal liquefaction and perhaps different catalyst morphology, composition, and activity. The samples were composites of a number of samples taken during a single run day in a single operating run period. All experimental work reported here was performed at the Materials Science and Engineering Department of the Massachusetts Institute of Technology.

Participant's Major Findings

The following principal observations for the application of STEM and EDX to coal liquefaction materials were reported by Vander Sande Associates. Preliminary examination of the samples using transmission scanning microscopy (TEM) provided insufficient compositional information; therefore, all work was accomplished with the STEM.

The STEM technique has a spatial resolution for imaging of about 0.5 nm and for compositional analysis of about 2.0 nm. Using both "bright-field" and "dark-field" modes, compositional analysis of the features detected was accomplished. Molybdenum, introduced into the two processing runs as Molyvan L, a catalyst precursor, was detected in all of the samples of the processing run in which the Molyvan L was introduced at the 500 ppm MF coal level (Run 262), and only in the recycle sample from the run in which Molyvan L was introduced at the 100 ppm MF coal level (Run 263). The largest localized concentrations of Mo were detected in the recycle sample in Run 263. The Mo was rarely seen as a particle in the THF-insoluble portion of the resids; rather, it was typically seen in a diffuse state in which any existent particles are smaller than observable at the resolution of the instrument (<2nm). Sulfur was often found to be associated with the Mo. Iron was observed in all samples and it was always found in association with sulfur. The FeS were determined to be particulate (about 0.1-2.0 μm) in nature.

CONSOL Evaluation

The STEM and EDX technique were shown to be useful for the analysis of the THF-insoluble portion of the direct coal liquefaction resid samples. It was shown that localized distributions of the different elements and compounds in the sample could be determined. The morphology of the detected elements and compounds was discernable. However, little difference was observed in the concentration or morphology of the Fe or Mo among the samples in which Fe and Mo were detected. It is, therefore, not possible, based on these six samples, to comment on the effect of processing conditions on the nature of the Mo catalyst.

The concentration of the highly dispersed Mo was below the detection limits of the STEM and EDX methods for two of the samples. In two of the three samples obtained from a processing run in which only 100 ppm (MF coal basis) of fresh Mo was introduced, the method was not able to detect the molybdenum that was present, even though the dispersed Mo catalyst was concentrated (~1300 ppm) in the THF-insoluble portion of the resid before examination.

There was an apparent discrepancy in the concentrations of Mo detected via the STEM and EDX techniques and conventional bulk methods. The STEM and EDX techniques indicate that the highest Mo concentration is in the recycle samples, but the bulk analysis indicates that those samples have low to medium Mo concentrations. This apparent discrepancy can be resolved if consideration is given to the fact that the STEM method, by experimental design, is reporting only on the Mo-enriched regions of the sample.

The STEM and EDX techniques appear to be powerful diagnostic tools for the analysis of these materials. The techniques are well-suited to the task of following the fate of dispersed catalysts through the liquefaction process.

Sample preparation was minimal; the dry powdered sample was distributed on a carbon film, which was supported by a Cu mesh grid, and placed directly into the microscope. The STEM instrument used to accomplish the work described in this report costs approximately \$650,000. The time required to run one sample is about one day. The operation of the equipment and the interpretation of the data are most commonly performed by highly trained professional personnel.

Further Development

Further development of the STEM technique for analysis of catalytic materials in coal liquefaction derived resid appears to be warranted. It is suggested that many additional samples containing iron and molybdenum based catalysts be examined to determine if processing trends affect the morphology of the materials. It is also suggested by Vander Sande Associates that electron energy loss spectroscopy (EELS) be tested with process derived samples to learn more about the local chemical environment of the Mo.

Participant's Statement of Work

Transmission Electron Microscopy (TEM) and Scanning Transmission Electron Microscopy (STEM) are techniques which have been used for the investigation of ceramic materials, coal and coal ash. It has not, however, been demonstrated for its ability to answer questions pertaining to the chemistry of coal conversion. As such, it fits well within the scope of the participants program.

The application of TEM and STEM to a specified sample set (6 samples) will allow a demonstration of the value of this technique for the examination of the dispersed catalyst in coal liquefaction-derived resid. The samples are known to contain molybdenum, originally introduced as a catalyst precursor (Molyvan L), and dispersed iron. These samples have been selected so that the utility of TEM and STEM for addressing the issue of catalyst activity can be evaluated by obtaining information on the size, morphology, occurrence, and chemical nature of the molybdenum and the iron in the different samples. Examination of the samples will be done in two steps. First, the samples will be globally scanned by STEM to map the molybdenum and iron concentrations. Then the Mo- and Fe-rich areas will be examined in a point-by-point analysis at high magnification by TEM. The point-by-point examination will include microdiffraction analysis and either energy dispersive X-ray spectroscopy (EDX) or electron energy loss spectrometry (EELS). Examination of the samples by other techniques such as Auger electron spectroscopy and secondary ion mass spectroscopy (SIMS) also will be employed to provide additional information for each sample. The samples will be supplied to MIT with the following information, as available: elemental analyses, ash content, ash elemental analysis, phenolic -OH concentration, calorific value, hydrogen classes by ¹H-NMR, and the full history of the sample (plant, process conditions, age, and storage conditions). The samples are the

tetrahydrofuran-insoluble portion of non-distillable residual materials. They contain THF-insoluble organic material and ash. Sample size will be at least 1g. The six insoluble resid samples will be solid materials that will be supplied as approximately minus 60 mesh powders. All experimental work will be performed at the Massachusetts Institute of Technology, Department of Materials Science and Engineering, Cambridge, Massachusetts.

Vander Sande Associates Executive Summary

Scanning transmission electron microscopy (STEM) was accomplished on six tetrahydrofuran (THF) insoluble portions of solid 850°F* materials (resids) from two Wilsonville direct coal liquefaction processing runs. Three samples are from a run employing a fresh molybdenum concentration of 500 ppm MF coal while the second set of three samples are from a run employing a fresh molybdenum concentration of 100 ppm MF coal. In each case, Molyvan L was used as the slurry catalyst. In each of the two sample sets, one sample is from the "interstage" sampling point (between the first and second reactors), the second sample from the "recycle" sampling point (at the solvent surge tank) and the third sample from the "second stage product" sampling point (from a vessel after the second reactor).

Samples were prepared for electron microscopy by distributing the dry powders on a thin carbon film which itself is supported on a Cu mesh grid. The observations presented in this report were obtained using a Vacuum Generators HB-5 STEM operating at 100 kV. This instrument has a spatial resolution for imaging of ~0.5 nm and a spatial resolution for compositional analysis of ~2.0 nm.

Imaging of samples was done in both bright-field and dark-field modes. Compositional analysis of features seen was accomplished by using a windowless energy dispersive X-ray detector and associated analyzer. This analytical approach is based on the incident electron probe interacting with the thin, solid sample generating characteristic X-rays from the volume of the sample under electron irradiation. The X-rays produced are collected by the X-ray detector, sorted in terms of their (characteristic) energy, and presented in a plot of X-ray intensity vs energy. The X-ray intensity in a given peak can also be used to "drive" the CRT to produce an X-ray map of the sample as the electron beam scans the object.

Mo was detected in all of the samples from the 500 ppm MF coal Mo concentration samples, but only from the "recycle" 100 ppm MF coal Mo concentration sample. The Mo concentration was locally the highest in the "recycle" 500 ppm MF coal sample. The Mo is rarely seen as a particle, but rather appears as a diffuse, organic-like mass suggesting that Mo is in a "molecular" state rather than a particulate state. The FeS has a particle size of 0.1-2.0 microns.

It is concluded that STEM is an extremely useful technique for analyzing the fine details of morphology and composition in coal liquefaction resid. As this analysis requires detailed information on local composition, transmission electron microscopy was determined to be a less useful technique compared to STEM.

Section 3

EXPERIMENTAL

Experimental details are described, where appropriate, in the Discussion section of this report. Details of the other analytical techniques used in this work were reported previously.^{1,2}

Section 4

REFERENCES

1. Burke, F. P.; Winschel, R. A.; Robbins, G. A. "Recycle Slurry Oil Characterization Final Report, October 1980 through March 1985", DOE/PC 30027-61, March 1985.
2. Winschel, R. A.; Robbins, G. A.; Burke, F. P. "Coal Liquefaction Process Solvent Characterization and Evaluation, Technical Progress report, July 1 through September 30, 1985", DOE/PC 70018-13, December 1985.

APPENDIX 1

This appendix includes analytical data produced by CONSOL for each distinct sample issued in the Participants Program. The data are arranged primarily by production facility and secondarily by sample type. The different sample types are 850°F⁺ resids, the tetrahydrofuran (THF)-soluble 850°F⁺ resids, the tetrahydrofuran (THF)-insoluble 850°F⁺ resids, pyridine-soluble 850°F⁺ resids, whole process streams, distillates, filter liquids, and coals. Experimental methods used to acquire these data are given in References 1 and 2.

WILSONVILLE 850°F⁺ RESIDS

Run Number	250	250	250	251-II	251-II	251-II
Balance Period	Composite	Composite	Composite	Composite	Composite	Composite
Sampling Point	V131B	R1236	V1067	R1258	V131B	V1067
Feed Coal Seam	Illinois No.6	Illinois No.6	Illinois No.6	Wyodak	Wyodak	Wyodak
Feed Coal Mine	Burning Star #2	Burning Star #2	Burning Star #2	Clovis Point	Clovis Point	Clovis Point
Ultimate:						
Ash wt % as det.	0.2	6.13	10.2			26.98
C, wt % MAF	89.73	89.65	89.9	88.27	87.81	88.03
H, wt % MAF	7.43	6.33	7.16	6.07	6.85	6.68
N, wt % MAF	1	1.27	1.1	1.23	0.97	1.05
S, wt % MAF	0.28	1.02	1.11	1.85	2.32	2
O (diff), wt % MAF	1.56	1.73	0.73	2.58	2.06	2.23
Ash Elementals (%):						
Na ₂ O	0.48	0.26	0.29			1.37
K ₂ O	1.98	1.84	1.52			0.46
CaO	8.96	5.45	10.17			19.43
MgO	1.56	0.91	0.8			3.7
Fe ₂ O ₃	17.7	17.78	18.56			11.71
TiO ₂	1.85	0.9	0.72			0.78
P ₂ O ₅	0.87	0.35	0.3			0.61
SiO ₂	46.51	47.45	42.76			30.57
Al ₂ O ₃	18.81	18.79	16.14			15.57
SO ₃		4.57	7.57			13.32
Unaccounted	1.29	1.7	1.18			2.48
Proton Distribution of THF Sols, %						
Condensed Aromatics	20.2	29.3	21.1	26.8	22.2	25.6
Uncondensed Aromatics	5.9	5.2	5.2	6.4	4.6	5.4
Cyclic Alpha	19.1	20.8	19.9	20.2	19.7	21.2
Alkyl Alpha	9.6	9.5	9.7	8.9	8.7	9.5
Cyclic Beta	16.6	13.9	17.8	13.1	15.4	14.2
Alkyl Beta	18.2	13.6	16.4	16.5	20	16.2
Gamma	10.4	7.8	10	8	9.4	8
Phenolic -OH Concentration of THF Sols, meq/g	0.74	1.07	0.71	1.1		
Phenolic Peak Location, cm⁻¹	3299	3292	3298	3294	3298	3297
Insoluble Org. Matter, wt %, as det.	0.2	4.6	5.2	16	13.4	16.5

WILSONVILLE 850°F⁺ RESIDS

Run Number	251-III	251-III	251-III	255	255
Balance Period	Composite	Composite	Composite	Composite	Composite
Sampling Point	V131B	V1258	V1067	V131B	R1235
Feed Coal Seam	Wyodak	Wyodak	Wyodak	Texas Lignite/ Ohio 6	Texas Lignite/ Ohio 6
Feed Coal Mine	Clovis Point	Clovis Point	Clovis Point		
Ultimate:					
Ash wt % as det.	28.64	27.9	30.33	26.77	27.69
C, wt % MAF	87.42	87.96	87.4	90.76	89.05
H, wt % MAF	6.78	6.66	6.89	6.96	6.33
N, wt % MAF	0.91	1	0.82	1.22	1.38
S, wt % MAF	2.56	2.58	2.78	2.43	2.95
O (diff), wt % MAF	2.33	1.8	2.11	-1.37	0.29
Ash Elementals (%):					
Na ₂ O			1.37		
K ₂ O			0.31		
CaO			22.38		
MgO			4.1		
Fe ₂ O ₃			14.94		
TiO ₂			0.65		
P ₂ O ₅			0.57		
SiO ₂			26.77		
Al ₂ O ₃			12.31		
SO ₃			14.55		
Unaccounted			2.05		
Proton Distribution of THF Sols, %					
Condensed Aromatics	23.2	30	17.1	23.9	29.2
Uncondensed Aromatics	3.5	3.5	3.8	3.8	3.1
Cyclic Alpha	21.6	21	20.1	22	22.8
Alkyl Alpha	9	8.8	8.7	8.9	9.2
Cyclic Beta	16.4	13.8	18.3	16.4	15.4
Alkyl Beta	17	16.4	22.3	17.3	14.4
Gamma	9.4	6.5	9.7	7.8	5.8
Phenolic -OH Concentration of THF Sols, meq/g	0.52	0.85	0.57	0.65	0.55
Phenolic Peak Location, cm ⁻¹	3303	3294	3303	3299	3294
Insoluble Org. Matter, wt %, as det.	16.1	20.4	19.3	16.7	18.4

WILSONVILLE 850°F⁺ RESIDS

Run Number	255	256	256	256	256
Balance Period	Composite	B	B	E	E
Sampling Point	V1067	V131B	R1236	V131B	R1236
Feed Coal Seam	Texas Lignite/ Ohio 6	Ohio 6	Ohio 6	Ohio 6	Ohio 6
Feed Coal Mine		Holmes	Holmes	Crooksville	Crooksville
Ultimate:					
Ash wt % as det.	29.37	7.19	7.67	9.85	10.36
C, wt % MAF	90.32	81.81	80.65	79.86	78.97
H, wt % MAF	6.63	5.88	5.74	6.48	6.33
N, wt % MAF	1.27	1.5	1.49	0.82	0.94
S, wt % MAF	3.02	1.61	1.79	1.04	1.14
O (diff), wt % MAF	-1.24	1.96	2.61	1.9	2.22
Ash Elementals (%):					
Na ₂ O	1.16				
K ₂ O	0.45				
CaO	14.42				
MgO	3.45				
Fe ₂ O ₃	16.93				
TiO ₂	1.06				
P ₂ O ₅	0.16				
SiO ₂	32.92				
Al ₂ O ₃	12.85				
SO ₃	14.64				
Unaccounted	1.96				
Proton Distribution of THF Sols, %					
Condensed Aromatics	22.8	21.3	28.2	22.8	24.3
Uncondensed Aromatics	4.1	11.2	5.8	5.1	3.7
Cyclic Alpha	21.5	17.9	21.7	19.7	21.7
Alkyl Alpha	9	10.5	10.4	9.3	9.8
Cyclic Beta	16.9	12.2	12.7	16.2	16.1
Alkyl Beta	17.4	17.2	14.2	17	15.6
Gamma	8.3	9.7	7	9.9	8.7
Phenolic -OH Concentration of THF Sols, meq/g	0.68	1.2	1.25	0.66	0.83
Phenolic Peak Location, cm ⁻¹	3300	3295	3294	3298	3298
Insoluble Org. Matter, wt %, as det.	18.2		7.8	4	4.7

WILSONVILLE 850°F⁺ RESIDS

Run Number	257	257	257	257	257
Balance Period	Composite	Composite	Composite	F	G
Sampling Point	R1235	V131B	V1067	R1236	R1235
Feed Coal Seam	Illinois No.6	Illinois No.6	Illinois No.6	Illinois No.6	Illinois No.6
Feed Coal Mine	Burning Star #2	Burning Star #2	Burning Star #2	Burning Star #2	Burning Star #2
Ultimate:					
Ash wt % as det.	12.52	9.28	13.49	13.31	12.33
C, wt % MAF	88.05	88.64	87.99	76.5	76.26
H, wt % MAF	7.7	8.08	7.87	6.73	6.48
N, wt % MAF	0.86	0.78	0.77	0.69	0.83
S, wt % MAF	1.34	0.79	1.2	1.24	1.36
O (diff), wt % MAF	2.05	1.71	2.16	1.53	2.74
Ash Elementals (%):					
Na ₂ O			0.41		
K ₂ O			1.88		
CaO			6.55		
MgO			0.91		
Fe ₂ O ₃			17.12		
TiO ₂			0.76		
P ₂ O ₅			0.15		
SiO ₂			46.77		
Al ₂ O ₃			17.74		
SO ₃			6.15		
Unaccounted			1.56		
Proton Distribution of THF Sols, %					
Condensed Aromatics	18.1	16.8	16.9	15.9	15.7
Uncondensed Aromatics	3.7	3.1	3.4	2.8	3.8
Cyclic Alpha	19.6	19.1	19.4	19.7	19
Alkyl Alpha	9.2	8.9	9.2	9.1	8.8
Cyclic Beta	19.2	20.7	19.8	20.3	19.2
Alkyl Beta	19.9	20.7	20.7	21	20.5
Gamma	10.4	10.6	10.7	11.3	12.9
Phenolic -OH Concentration of THF Sols, meq/g	0.68	0.5	0.57	0.62	0.83
Phenolic Peak Location, cm ⁻¹	3300	3302	3302	3299	3298
Insoluble Org. Matter, wt %, as det.	21.3	14.8	21.3	7.6	11.2

WILSONVILLE 850°F RESIDS

Run Number	258	258	259	259	259
Balance Period	Composite	Composite	Composite	Composite	Composite
Sampling Point	V131B	R-1235	R1235	V131B	V1067
Feed Coal Seam	Wyodak and Anderson	Wyodak and Anderson	Pittsburgh	Pittsburgh	Pittsburgh
Feed Coal Mine	Black Thunder	Black Thunder	Ireland	Ireland	Ireland
Ultimate:					
Ash wt % as det.	16.62	17.21	8.74	8.51	10.21
C, wt % MAF	91.24	90.9	90.12	91.01	90.24
H, wt % MAF	6.04	5.86	6.19	6.5	6.39
N, wt % MAF	1.18	1.21	1.15	1.04	1.05
S, wt % MAF	1.95	2.1	1.5	1.25	1.49
O (diff), wt % MAF	-0.41	-0.06	1.04	0.2	0.83
Ash Elementals (%):					
Na ₂ O			0.52	0.52	0.51
K ₂ O			1.63	1.65	1.6
CaO			2.62	2.97	2.72
MgO			0.84	0.87	0.84
Fe ₂ O ₃			20.67	20.76	21.83
TiO ₂			0.91	0.93	0.91
P ₂ O ₅			0.15	0.15	0.15
SiO ₂			44.3	44.01	43.89
Al ₂ O ₃			24.77	25.29	24.3
SO ₃			1.46	1.09	1.37
Unaccounted			2.13	1.76	1.88
Proton Distribution of THF Sols, %					
Condensed Aromatics	34	39.5	30.7	26.1	27.8
Uncondensed Aromatics	5.8	6.9	2.6	5.4	3.8
Cyclic Alpha	20.2	20.1	20.9	18.9	21.2
Alkyl Alpha	9	9.4	10.2	9.4	9.6
Cyclic Beta	12.6	10.6	13.8	14.8	15.5
Alkyl Beta	12	11.2	13.4	14.6	13.4
Gamma	6.3	5.8	8.4	10.8	8.7
Phenolic -OH Concentration of THF Sols, meq/g	0.85	1.09	0.92	0.69	0.7
Phenolic Peak Location, cm ⁻¹		3294	3295	3296	3296
Insoluble Org. Matter, wt %, as det.	12.8	15.3			

WILSONVILLE THF-SOLUBLE 850°F⁺ RESIDS

Run Number	250	250	250	251-II	251-II	251-II
Balance Period	Composite	Composite	Composite	Composite	Composite	Composite
Sampling Point	R1236	V131B	V-1067	V-1067	V-131B	R-1258
Feed Coal Seam	Illinois No.6	Illinois No.6	Illinois No.6	Wyodak	Wyodak	Wyodak
Feed Coal Mine	Burning Star No.2	Burning Star No. 2	Burning Star No.2	Clovis Point	Clovis Point	Clovis Point
Ultimate:						
C, wt % MAF	89.38	89.18	89.91	89.88	89.72	89.38
H, wt % MAF	6.51	7.39	7.14	6.75	7.08	6.13
N, wt % MAF	1.16	0.89	1.02	1.22	1.04	1.33
S, wt % MAF	0.5	0.25	0.27	0.05	0.06	0.15
O (diff), wt % MAF	2.45	2.29	1.6 [*]	2.1	2.1	3.01
Proton Distribution of THF Solis, %						
Condensed Aromatics	30.8	20.9	20.4	26.5	23.4	31.9
Uncondensed Aromatics	5.2	4.4	5.6	3.5	3.6	5.1
Cyclic Alpha	19	18.6	18.7	21.3	19.9	18.1
Alkyl Alpha	10.3	9.8	9.8	9.6	8.7	9.4
Cyclic Beta	13	16.8	17.2	15.1	15.9	12.6
Alkyl Beta	12.9	17.6	17.2	16.3	19	14.3
Gamma	8.8	11.8	11.2	7.7	9.5	8.6
Phenolic -OH Concentration, meq/g	1.07	0.74	0.55	0.81	0.75	1.17
Phenolic Peak Location, cm ⁻¹	3292	3299	3297	3298	3297	3292

WILSONVILLE THF-SOLUBLE 850°F⁺ RESIDS

Run Number	251-III	251-III	251-III	255	255	255	255
Balance Period					B	B	B
Sampling Point	V131B	R1258	V1067	R-1236	V-1067	V-131B	R-1235
Feed Coal Seam	Wyodak	Wyodak	Wyodak	Texas Lignite	Texas Lignite	Texas Lignite	Texas Lignite
Feed Coal Mine	Clovis Point	Clovis Point	Clovis Point	Martin Lake	Martin Lake	Martin Lake	Martin Lake
Ultimate:							
C, wt % MAF	89.43	89.38	88.75	89.27	89.4	89.39	89.06
H, wt % MAF	7.92	7.26	8.02	6.64	7	7.12	6.7
N, wt % MAF	0.74	0.88	0.7	1.3	1.28	1.23	1.37
S, wt % MAF	0.03	0.06	0.32	0.18	0.13	0.09	0.19
O (diff), wt % MAF	1.88	2.42	2.21	2.61	2.19	2.17	2.68
Proton Distribution of THF Sols, %							
Condensed Aromatics	19.1	24.4	18.6	29.2	23.1	22.4	26.7
Uncondensed Aromatics	3.3	4.1	3.2	3.1	3.7	4.3	5.4
Cyclic Alpha	18.6	17.6	19.3	22.8	20.8	19.2	19.1
Alkyl Alpha	9.2	8.9	9.2	9.2	9.5	9.5	9.7
Cyclic Beta	17.1	14.2	16.2	15.4	16.2	15.9	13.8
Alkyl Beta	22	20.5	22.7	14.4	17.9	18.5	16.4
Gamma	10.6	10.3	10.7	5.8	8.7	10.3	8.8
Phenolic -OH Concentration, meq/g	0.52	0.85	0.42	1.04	0.77	0.71	1.03
Phenolic Peak Location, cm⁻¹	3303	3294	3308	3294	3298	3298	3295

WILSONVILLE THF-SOLUBLE 850°F⁺ RESIDS

Run Number	256	256	256	256	257	257
Balance Period	B	B	E	E	Composite	Composite
Sampling Point	V131B	R1236	V131B	R1236	V131B	R1235
Feed Coal Seam	Ohio No.6	Ohio No.6	Ohio No. 6	Ohio No. 6	Illinois No. 6	Illinois No. 6
Feed Coal Mine	Holmes	Holmes	Crooksville	Crooksville	Burning Star No.2	Burning Star No.2
Ultimate:						
C, wt % MAF	88.54	88.19	90.07	89.88	88.75	88.41
H, wt % MAF	6.37	6.42	7.25	7.21	8.15	8.04
N, wt % MAF	1.61	1.61	0.95	1.03	0.66	0.86
S, wt % MAF	0.65	0.74	0.05	0.12	0.14	0.26
O (diff), wt % MAF	2.83	3.78	1.63	1.76	2.3	2.43
Proton Distribution of THF Sols, %						
Condensed Aromatics	21.3	27.5	23	24.3	16.7	17.8
Uncondensed Aromatics	11.2	6	5.6	4.1	4.4	4.9
Cyclic Alpha	17.9	20.5	18.3	21.5	17.9	18.6
Alkyl Alpha	10.5	10.4	9.5	9.7	9.4	9.2
Cyclic Beta	12.2	12.5	15.7	15.7	16.6	18.1
Alkyl Beta	17.2	14.4	16.8	15.6	20.4	19.7
Gamma	6.7	8.6	11.2	9.1	12.5	11.7
Phenolic -OH Concentration, meq/g	1.2	1.25	0.66	0.83	0.5	0.68
Phenolic Peak Location, cm ⁻¹	3295	3294	3298	3298	3302	3300

WILSONVILLE THF-SOLUBLE 850°F⁺ RESIDS

Run Number	257	257	257	258	258	259
Balance Period	Composite	F	G	Composite	Composite	Composite
Sampling Point	V1067	R1235	R-1235	V-131B	R-1235	V131B
Feed Coal Seam	Illinois No. 6	Illinois No. 6	Illinois No. 6	Wyodak and Anderson	Wyodak and Anderson	Pittsburgh
Feed Coal Mine	Burning Star No. 2	Burning Star No. 2	Burning Star No. 2	Spring Creek/ Black Thunder	Spring Creek/ Black Thunder	Ireland
Ultimate:						
C, wt % MAF	88.32	89.45	88.11	90.6	90.11	90.54
H, wt % MAF	8.16	7.96	7.76	6.2	6.1	6.74
N, wt % MAF	0.65	0.77	0.87	1.12	1.21	0.91
S, wt % MAF	0.15	0.23	0.45	0.04	0.1	0.39
O (diff), wt % MAF	2.72	1.59	2.81	2.04	2.48	1.42
Proton Distribution of THF Sol, %						
Condensed Aromatics	17.7	16.4	15.4	32	33.7	26.1
Uncondensed Aromatics	3	3.2	4.5	6.7	6.7	5.4
Cyclic Alpha	18.9	18.4	17.7	18.7	18.3	18.9
Alkyl Alpha	9.3	8.9	9.8	9.8	9.9	9.4
Cyclic Beta	19.5	20.5	18.9	12.3	11.3	14.8
Alkyl Beta	19.6	20.8	21.9	12.3	12	14.6
Gamma	11.9	11.7	11.8	8.2	8	10.8
Phenolic -OH Concentration, meq/g	0.57	0.59	0.81	0.85	1.09	0.69
Phenolic Peak Location, cm⁻¹	3301	3296	3295	3295	3292	3296

WILSONVILLE THF-SOLUBLE 850°F⁺ RESIDS

Run Number	259	259	260	260	260	260
Balance Period	Composite	Composite	ABC	ABC	ABC	C
Sampling Point	R1235	V1067	V131B	V-1067	R-1235	V-1067
Feed Coal Seam	Pittsburgh	Pittsburgh	Wyodak and Anderson	Wyodak and Anderson	Wyodak and Anderson	Wyodak and Anderson
Feed Coal Mine	Ireland	Ireland	Black Thunder	Black Thunder	Black Thunder	Black Thunder
Ultimate:						
C, wt % MAF	89.79	89.8	89.56	91.22	90.72	89.74
H, wt % MAF	6.49	6.8	6.51	6.44	6.31	6.46
N, wt % MAF	1.06	1	1.09	1.14	1.17	1.12
S, wt % MAF	0.63	0.41	0.04	0.03	0.05	0.04
O (diff), wt % MAF	2.03	1.99	1.8	1.17	1.75	2.64
Proton Distribution of THF Sols, %						
Condensed Aromatics	30.7	28.6	33.8	32.4	33.4	30.5
Uncondensed Aromatics	2.6	3.6	2.4	5.1	3.7	4.7
Cyclic Alpha	20.9	21.7	18.4	20.3	19.9	20.8
Alkyl Alpha	10.2	9.1	9.1	8.6	9.3	9.4
Cyclic Beta	13.8	14.8	13.2	12.9	12.6	13.8
Alkyl Beta	13.4	13.5	14.7	13.3	14.3	13
Gamma	8.4	8.7	8.4	7.4	6.8	7.8
Phenolic -OH Concentration, meq/g	0.92	0.7	0.71	0.7	0.97	0.61
Phenolic Peak Location, cm ⁻¹	3295	3296	3296	3296	3295	3294

WILSONVILLE THF-SOLUBLE 850°F⁺ RESIDS

Run Number	260	260	260	260	260	260
Balance Period	C	C	D	D	DEF	E
Sampling Point	V-131B	R-1235	V-1067	R1235	R-1235	V-1067
Feed Coal Seam	Wyodak and Anderson	Wyodak and Anderson	Wyodak and Anderson	Wyodak and Anderson	Wyodak and Anderson	Wyodak and Anderson
Feed Coal Mine	Black Thunder	Black Thunder	Black Thunder	Black Thunder	Black Thunder	Black Thunder
Ultimate:						
C, wt % MAF	90.9	90.41	89.1	89.2	88.72	89.24
H, wt % MAF	6.32	6.25	6.95	7.13	7.11	6.92
N, wt % MAF	1.11	1.14	1.33	1.08	0.98	1.19
S, wt % MAF	0.03	0.04	0.03	0.03	0.09	0.07
O (diff), wt % MAF	1.64	2.16	2.59	2.56	3.1	2.58
Proton Distribution of THF Sols, %						
Condensed Aromatics	32.2	32.8	24.7	23.2	20.3	24.8
Uncondensed Aromatics	5.1	4.6	3.8	4.4	4.3	4.8
Cyclic Alpha	18.1	20	19.3	18.6	17.2	18
Alkyl Alpha	9.2	9.4	9.3	8.7	9.4	9.1
Cyclic Beta	13.6	12.7	15.8	15.7	15.3	14.4
Alkyl Beta	13.9	14.5	18.8	19.9	21.2	19.5
Gamma	7.8	6	8.2	9.5	12.3	9.5
Phenolic -OH Concentration, meq/g	0.67	0.97	0.88	0.82	0.95	0.93
Phenolic Peak Location, cm ⁻¹	3296	3295	3298	3299	3294	3296

WILSONVILLE THF-SOLUBLE 850°F⁺ RESIDS

Run Number	260	260	261	261	261	262
Balance Period	E	E	ABCD	D	E	Composite
Sampling Point	V-131B	R-1235	R-1235	V-131B	V-131B	R-1235
Feed Coal Seam	Wyodak and Anderson	Wyodak and Anderson	Illinois No. 6	Illinois No. 6	Illinois No. 6	Wyodak and Anderson
Feed Coal Mine	Black Thunder	Black Thunder	Burning Star No. 2	Burning Star No. 2	Burning Star No. 2	Black Thunder
Ultimate:						
C, wt % MAF	89.46	89.54	89.41	90.19	90.52	88.59
H, wt % MAF	6.69	6.96	6.95	5.93	5.22	7.37
N, wt % MAF	1.13	1.13	1.25	1.61	1.25	0.89
S, wt % MAF	0.05	0.05	0.47	0.23	0.28	0.11
O (diff), wt % MAF	2.67	2.32	1.92	2.04	2.73	3.04
Proton Distribution of THF Sols, %						
Condensed Aromatics	22.5	23.3	24.4	25.3	33.1	30.9
Uncondensed Aromatics	5.1	4	5.5	4.1	4.6	1.4
Cyclic Alpha	16.8	18.2	21.4	18.3	19.4	18.8
Alkyl Alpha	9.3	9.1	9.2	9.2	9.5	9.7
Cyclic Beta	14.4	15.2	15.7	16.1	13.3	13.6
Alkyl Beta	21.2	20.4	14.6	17.1	12.5	15.9
Gamma	10.8	9.8	9.2	9.9	7.7	9.7
Phenolic -OH Concentration, meq/g	0.89	0.96	1.01	0.77	0.83	1.14
Phenolic Peak Location, cm⁻¹	3297	3296	3296	3297	3296	3297

WILSONVILLE PYRIDINE-SOLUBLE 850°F⁺ RESIDS

Run Number	250	257	257	258	259	259
Balance Period	Composite	Composite	Composite	Composite	Composite	Composite
Sampling Point	R1235	V-131B	R-1235	R-1235	V-131B	R-1235
Feed Coal Seam	Illinois No. 6	Illinois No. 6	Illinois No. 6	Wyodak and Anderson	Pittsburgh	Pittsburgh
Feed Coal Mine	Burning Star #2	Burning Star #2	Burning Star #2	Black Thunder	Ireland	Ireland
Ultimate:						
C, wt % MAF	88.18	87.52	87.72	89.19	89.83	89.27
H, wt % MAF	6.04	7.38	7.32	5.59	5.38	6.07
N, wt % MAF	1.60	0.9	0.97	1.57	1.19	1.31
S, wt % MAF	0.49	0.15	0.28	0.06	0.38	0.62
O (diff), wt % MAF	3.69	4.05	3.71	3.59	2.22	2.73
Proton Distribution of THF Sols, %						
Condensed Aromatics	27.8	16.1	17.3	29.2	23.5	26.2
Uncondensed Aromatics	6.0	4.8	6.3	7.3	6	8.3
Cyclic Alpha	17.7	15.6	15.8	17.4	17.8	17.1
Alkyl Alpha	9.4	9.2	8.7	9	9.2	8.9
Cyclic Beta	14.6	19.3	18.6	12.1	14.6	14
Alkyl Beta	13.8	21.6	19.8	14.2	16.8	15
Gamma	10.7	13.3	13.3	10.8	12.1	10.5
Phenolic -OH Concentration of THF Sols, meq/g	1.07	0.5	0.68	1.09	0.69	0.92
Phenolic Peak Location, cm ⁻¹	3292	3302	3300	3294	3296	3295
Pyridine Soluble, % of Parent Resid	91.09	86.49	80.21	71.45	84.51	83.63

WILSONVILLE THF-INSOLUBLE 850°F⁺ RESIDS

Run Number	262	262	262	263	263	263
Balance Period	B	B	B	E	E	E
Sampling Point	V1067	R1235	V131B	V131B	R1235	V1067
Feed Coal Seam	Wyodak and Anderson	Wyodak and Anderson	Wyodak and Anderson	Wyodak and Anderson	Wyodak and Anderson	Wyodak and Anderson
Feed Coal Mine	Black Thunder	Black Thunder	Black Thunder	Black Thunder	Black Thunder	Black Thunder
Ultimate:						
Ash wt % dry	52.01	49.05	47.79	65.37	62.37	65.79
C, wt % dry	42.5	44.54	45.56	34.36	35.93	33.73
H, wt % dry	2.55	2.67	2.77	1.84	1.97	1.8
N, wt % dry	0.77	0.76	0.82	0.51	0.52	0.52
S, wt % dry	4.94	4.61	4.52	6.31	5.99	6.2
O (diff), wt % dry	-2.77	-1.63	-1.46	-8.39	-6.78	-8.04
Ash Elementals (%):						
Na ₂ O	0.39	0.41	0.4	0.22	0.22	0.22
K ₂ O	0.26	0.25	0.24	0.35	0.35	0.35
CaO	16.3	16.2	16.28	16.35	16.76	16.31
MgO	3.53	3.48	3.5	3.26	3.29	3.26
Fe ₂ O ₃	22.2	22.17	22.49	22.76	22.75	22.49
TiO ₂	0.86	0.86	0.87	0.84	0.85	0.85
P ₂ O ₅	1.96	1.92	1.74	1.3	1.31	1.29
SiO ₂	21.7	22.16	21.5	21.67	21.35	22.38
Al ₂ O ₃	11.55	11.43	11.49	13.1	13.07	13.18
SO ₃						
Unaccounted						
Mo, ppm of dry sample	3133	2852	2411	1312.5	1265.5	1315.5

WILSONVILLE WHOLE PROCESS OILS

Run Number	251-II	255	257	259
Balance Period	A	B	E	G
Sampling Point	V131B	V131B	V131B	R1235
Feed Coal Seam	Wyodak	Texas Lignite/ Ohio No. 6	Illinois No. 6	Pittsburgh
Feed Coal Mine	Clovis Point		Burning Star #2	Ireland
Ultimate:				
Ash wt % as det	14.40	9.34	6.81	8.62
C, wt % MAF	88.24	89.81	88.31	89.32
H, wt % MAF	8.15	8.75	8.42	7.42
N, wt % MAF	0.89	0.94	0.75	0.31
S, wt % MAF	0.71	0.78	0.65	1.07
O (diff), wt % MAF	2.00	-0.28	1.86	1.87
Proton Distribution of THF Sols, %				
Condensed Aromatics	16.5	13.6	12.7	21.6
Uncondensed Aromatics	5.0	3.7	4.8	4.0
Cyclic Alpha	15.8	15.7	15.1	19.7
Alkyl Alpha	9.7	9.1	8.8	9.0
Cyclic Beta	15.4	18.0	19.9	15.4
Alkyl Beta	25.4	25.1	23.1	18.4
Gamma	12.5	14.8	15.6	11.9
Phenolic -OH Concentration				
of THF Sols, meq/g	0.41	0.33	0.26	0.60
Phenolic Peak Location, cm ⁻¹	3309	3307	3307	3297
Insoluble Organic Matter,				
wt %, as det.	9.4	6.4	4.4	
THF Soluble 850°F⁺ Resid,				
wt %, as det.	34.5	31.7	71.4	
850°F Distillate, wt % as det.	40.1	48.7	16.6	

WILSONVILLE WHOLE PROCESS OILS

Run Number	259	259	259	259
Balance Period	G	G	G	G
Sampling Point	V1067	V131B	V161+V182	V164
Feed Coal Seam	Pittsburgh	Pittsburgh	Pittsburgh	Pittsburgh
Feed Coal Mine	Ireland	Ireland	Ireland	Ireland
Ultimate:				
Ash wt % as det	7.42	6.36	0.44	0.005
C, wt % MAF	90.83	90.63	86.41	86.66
H, wt % MAF	7.97	7.73	13.01	11.91
N, wt % MAF	0.22	0.18	0.09	0.17
S, wt % MAF	0.97	0.81	0.05	0.14
O (diff), wt % MAF	0.0	0.64	0.44	1.11
Proton Distribution of THF Sols, %				
Condensed Aromatics	19.6	21.7	2.2	5.2
Uncondensed Aromatics	4.2	4.1	6.3	4.9
Cyclic Alpha	16.7	17.8	4.8	8.7
Alkyl Alpha	9.0	8.4	7.6	7.6
Cyclic Beta	16.4	16.6	18.8	23.9
Alkyl Beta	19.9	20.3	30.1	29.3
Gamma	14.3	11.1	30.3	20.4
Phenolic -OH Concentration of THF Sols, meq/g	0.42	0.34	0.18	0.27
Phenolic Peak Location, cm	3299	3300	3323	3317
Insoluble Organic Matter, wt %, as det.		5.8		
THF Soluble 850°F ⁺ Resid, wt %, as det.		53.2		
850°F Distillate, wt % as det.		33.8		

WILSONVILLE - FEED COALS

Coal Seam	Illinois No. 6	Wyodak and Anderson	Wyodak	Pittsburgh
Feed Coal Mine	Burning Star #2	Black Thunder	Clovis Point	Ireland
Proximate, wt % Dry:				
Ash	10.92	6.35	8.34	4.68
Volatile Matter	38.74	45.01	48.25	43.82
Fixed Carbon	50.34	48.64	43.41	51.50
Sulfur Total	3.39	0.48	1.09	3.13
Moisture, wt % as det.	7.61	0.07	19.89	0.85
Ultimate, wt % Dry:				
Ash	10.92	6.35	8.34	4.68
C	71.49	70.30	65.62	77.44
H	4.78	5.03	4.65	5.69
N	1.36	0.96	0.87	1.31
Cl	0.048	0.073	0.053	0.062
S (total)	3.39	0.48	1.09	3.13
O (diff)	8.01	16.81	19.38	7.69
Sulfur Forms, wt % Dry				
Pyritic	1.71	0.08	0.11	0.68
Sulfate	0.06	0.03	0.25	<0.01
Organic	1.62	0.37	0.73	2.45
Ash Elementals, %:				
Na ₂ O	0.28	1.00		0.35
K ₂ O	1.85	0.33		1.48
CaO	5.85	20.52		2.69
MgO	0.92	4.43		0.79
Fe ₂ O ₃	18.26	4.53		26.08
TiO ₂	0.88	1.19		0.95
P ₂ O ₅	0.03	0.91		0.12
SiO ₂	47.81	32.39		40.24
Al ₂ O ₃	18.42	15.56		22.70
SO ₃	4.37	18.50		3.10
Unaccounted	1.33	0.64		1.50
Calorific Value, Btu/lb, dry	12720	12085	11004	14114
MAF Basis	14279	12904	12005	14807

HRI 850°F⁺ RESIDS AND WHOLE PROCESS OILS

Run Number	CC-1	CC-1	CC-1	CC-2*	CC-2
Balance Period	14A	13	13	14A/B/C	14
Sampling Point	1st Stage FL	SO/PD	PFL	PFL	PFL
Feed Coal Seam	Illinois No. 6	Illinois No. 6	Illinois No. 6	Wyodak and Anderson	Wyodak and Anderson
Feed Coal Mine	Burning Star #2	Burning Star #2	Burning Star #2	Black Thunder	Black Thunder
Ultimate:					
C, wt % MAF	89.03	85.82	88.65	90.12	90.15
H, wt % MAF	9.75	12.63	9.18	8.14	9.64
N, wt % MAF	0.19	0.05	0.26	0.41	0.3
S, wt % MAF	0.02	0	0.01	0.03	0.03
O (diff), wt % MAF	1.01	1.5	1.9	1.30	-0.12
Proton Distribution of THF Sols, %					
Condensed Aromatics	10.7	2.9	11.6	20.3	11.8
Uncondensed Aromatics	3.9	3.9	4.3	3.1	3.2
Cyclic Alpha	13.4	7.1	13.6	16.6	13.1
Alkyl Alpha	8.2	6.4	8.5	8.3	7.9
Cyclic Beta	19.6	24.8	18.5	17.1	19.1
Alkyl Beta	28.6	31.9	28.1	23.1	29.2
Gamma	15.6	23.1	15.3	11.5	15.7
Phenolic -OH Concentration of THF Sols, meq/g	0.46	0.04	0.22	0.24	0.13
Phenolic Peak Location, cm ⁻¹	3299	3353	3299	3299	3309

*Resid

HRI 850°F⁺ RESIDS AND WHOLE PROCESS OILS

Run Number	CC-2	CC-2	CC-2	CC-5	CC-5	CC-5
Balance Period	15A	14 A/B/C	15A	15A/B/C	16A	15
Sampling Point	1st Stage FL	PFL	1st Stage FL	PFL	FL	PFL
Feed Coal Seam	Wyodak and Anderson	Wyodak and Anderson	Wyodak and Anderson	Wyodak and Anderson	Wyodak and Anderson	Wyodak and Anderson
Feed Coal Mine	Black Thunder	Black Thunder	Black Thunder	Black Thunder	Black Thunder	Black Thunder
Ultimate:						
C, wt % as det.	88.68	89.94	89.47	90.67	89.39	88.46
H, wt % MAF	8.83	8.16	8.88	7.56	8.45	8.95
N, wt % MAF	0.34	0.43	0.41	0.56	0.51	0.39
S, wt % MAF	0.03	<0.03	<0.03	0.03	0.03	0.03
O (diff), wt % MAF	2.12	1.47	1.22	1.18	1.62	2.19
Proton Distribution of THF Sols, %						
Condensed Aromatics	14.5	20.3	14.5	24.7	17.1	15.9
Uncondensed Aromatics	3.2	3.1	3.2	2.9	2.5	3.7
Cyclic Alpha	16.1	16.6	16.1	17.5	18.6	15
Alkyl Alpha	8	8.3	8	8.7	9	8.4
Cyclic Beta	18.5	17.1	18.5	16.3	18.5	17.8
Alkyl Beta	25.7	23.1	25.7	20	23	25.8
Gamma	14.1	11.5	14.1	10	11.3	13.4
Phenolic -OH Concentration of THF Sols, meq/g	0.25	0.24	0.25	0.38	0.49	0.18
Phenolic Peak Location, cm ⁻¹	3306	3301	3306	3296	3303	3306

HRI 850°F* RESIDS AND WHOLE PROCESS OILS

Run Number	CC-5*	CC-5*	I-27	I-27	I-27	I-27
Balance Period	16A	15A/B/C	18	2	25	8
Sampling Point	1st Stage FL	PFL	PFL	PFL	PFL	PFL
Feed Coal Seam	Wyodak and Anderson	Wyodak and Anderson	Illinois No. 6	Illinois No. 6	Illinois No. 6	Illinois No. 6
Feed Coal Mine	Black Thunder	Black Thunder	Burning Star #2	Burning Star #2	Burning Star #2	Burning Star #2
Ultimate:						
C, wt % as det.	80.65	90.47	89.58	88.06	90.31	88.25
H, wt % MAF	6.88	7.59	7.12	9.14	6.5	8.18
N, wt % MAF	0.76	0.56	0.9	0.48	1.09	0.59
S, wt % MAF	0.22	<0.03	0.15	0.03	0.16	0.06
O (diff), wt % MAF	5.16	1.38	2.25	2.29	1.94	2.92
Proton Distribution of THF Sols, %						
Condensed Aromatics	17.1	24.7	25.3	12	33.5	17.8
Uncondensed Aromatics	2.5	2.9	3.9	2.5	4.8	2.9
Cyclic Alpha	18.6	17.5	20.8	18.9	19.7	19.6
Alkyl Alpha	9	8.7	9.4	9.2	9.1	8.7
Cyclic Beta	18.5	16.3	16.5	23.9	13.9	20
Alkyl Beta	23	20	15.2	22.5	11.8	19.8
Gamma	11.3	10	8.8	10.9	7.1	11.2
Phenolic -OH Concentration of THF Sols, meq/g	0.49	0.38	0.66	0.25	0.71	0.41
Phenolic Peak Location, cm ⁻¹	3303	3296	3297	3305	3296	3301

*Resid

LUMMUS 850°F⁺ RESIDS AND WHOLE PROCESS OILS

Run Number	3LCF10	3LCF10
Balance Period	0111	0128
Sampling Point	Feed	Feed
Feed Coal Seam	Wyodak/ Illinois No. 6	Wyodak/ Illinois No. 6
Feed Coal Mine		
Ultimate:		
Ash, wt % as det.	0.79	9.97
C, wt % MAF	87.75	78.53
H, wt % MAF	6.09	4.80
N, wt % MAF	0.79	0.99
S, wt % MAF	0.29	0.56
O (diff), wt % MAF	4.27	5.11
Proton Distribution of THF Sols, %		
Condensed Aromatics	31.6	35.1
Uncondensed Aromatics	10.8	7.6
Cyclic Alpha	13.8	16.5
Alkyl Alpha	8.4	8.5
Cyclic Beta	11.0	12.9
Alkyl Beta	14.0	12.2
Gamma	9.5	7.2
Phenolic -OH Concentration of THF Sols, meq/g	0.96	1.19
Phenolic Peak Location, cm⁻¹	3290	3289

APPENDIX 2

**THE CHEMICAL NATURE OF COAL LIQUID RESIDS
AND THE IMPLICATIONS FOR PROCESS DEVELOPMENT**

S. D. Brandes
R. A. Winschel
G. A. Robbins
F. P. Burke

CONSOL Inc.
Research & Development
4000 Brownsville Road
Library, PA 15129

Prepared for Presentation at the
1992 DOE Liquefaction Contractors' Review Conference
Pittsburgh, PA

September 22-24, 1992

THE CHEMICAL NATURE OF COAL LIQUID RESIDS AND THE IMPLICATIONS FOR PROCESS DEVELOPMENT

S. D. Brandes, R. A. Winschel, G. A. Robbins, F. P. Burke
CONSOL Inc.

Research & Development
4000 Brownsville Road
Library, PA 15129

Key words: coal liquids, resid

INTRODUCTION

The informational needs for the advancement of direct coal liquefaction process development include the knowledge to choose the appropriate analytical tools. CONSOL Inc. is working with a number of research groups to evaluate various methods for analyzing direct coal liquefaction process-derived samples.¹ Each individual method was applied to process-derived samples and the advantages (and some drawbacks) for each have come to light.²⁻⁸ The large database accumulated in the study may be useful in choosing analytical methods for process development and design of facilities. This paper will give a brief overview of the program and the samples studied. It will also explore the usefulness of the data collected in the program by examining a few specific examples. The impact of the analytical methods explored in the program on process design costs also will be addressed.

Close-coupled integrated two-stage direct coal liquefaction, on a pilot plant scale, is a continuous, multi-step operation. The process steps include mixing feed coal with recycled coal liquid to form a slurry; thermal and/or catalytic liquefaction of the coal in the slurry; stripping of the light, high-value products; and recycling of the heavy residues to near extinction. The coal concentration in the feed slurry is typically 30 wt %. The slurry oil consists mostly of relatively high molecular weight material (resids) and some light distillable materials. Each process stream, with the exception of the distillation column overheads, also is comprised of 50% or more of non-distillable (850°F⁺) resid. Because of the preponderance of the resid in the system, and its influence on the overall properties of the process streams, the program described above was directed to the study of these materials.

PROGRAM STRUCTURE

The program organized by CONSOL to coordinate the distribution of well-documented direct coal liquefaction samples to evaluate potentially useful analytical techniques is structured in two phases. In Phase I, nine organizations were chosen to participate in the program (Table 1). Eighteen different analytical methods were incorporated into the program for Phase I. These methods are, for the most part, well established analytical techniques which are uncommon in their application to coal-derived materials. Each researcher was responsible for the interpretation of the results of the tests in light of the processing information provided by CONSOL with each sample. In order to provide the maximum information on any one sample, Phase I of the program was structured to use techniques which both complemented and supplemented each other. Phase II of the program expanded the Phase I tests with eight additional research groups and eleven methods (Table 2) that also appear to be promising, and which had not been considered in Phase I. A concerted effort was made to tie together the methods which were chosen in Phase I to Phase II methods by choice of samples.

PROGRAM SAMPLES

A key to the success of the program is the proper selection of samples. Evaluation of the analytical methodologies were based in part on the ability of the method to identify differences in the samples which can be attributed to differences in the conditions under which the samples were produced. This may include such diverse variables as feed coal rank, reactor temperature, catalyst type, age, or use in one or both reactors (in a two-stage system), sampling point in the direct coal liquefaction plant, and whether or not the feed coal was in some way treated before liquefaction. It is necessary to provide a diverse set of samples to the analytical researcher for testing. In both Phase I and Phase II of the program, sample sets for each method were chosen with large differences in production variables. Analytical methods that could distinguish among the samples and provide information useful for predictive purposes were considered successful techniques.

All samples in the program were obtained from CONSOL's sample bank, which includes materials from the Wilsonville, Lummus, HRI, H-Coal Pilot Plant liquefaction programs and the UOP and HRI coprocessing programs. In addition, CONSOL continues to obtain and analyze samples from active DOE-sponsored process development programs. All samples distributed in the program were analyzed by CONSOL. Such analyses include (when appropriate): elemental analysis, ash content, ash elemental analysis, solubility fractionation, phenolic -OH concentration, calorific value, and hydrogen classes by ¹H-NMR. In addition, CONSOL documented the full history of the samples (plant, process conditions, age, storage conditions, hydrogen consumption, and yield data for the associated run). Kinetic parameters were calculated for a number of the coal liquefaction runs from which samples were selected for the program. All information was supplied to the program participants to aid in the evaluation of the analytical methods.

The sample sets for the entire program were integrated so that the maximum information content could be obtained by judicious choice of samples for analysis by any one method, and by the application of as many of the methods as appropriate to a single sample.

RESULTS AND DISCUSSION

The results of the analyses of six 850°F⁺ distillation resid samples, obtained from two process runs (Run 257⁹ and Run 259¹⁰) conducted at the Wilsonville Advanced Two-Stage Direct Coal Liquefaction facility, will be used to demonstrate the potential usefulness of these data for process development. Each of the samples are composites of many daily samples obtained over the length of the liquefaction test. These tests lasted for a number of months and included numerous changes in operating conditions. The feed to Wilsonville Run 257 was Illinois No. 6 coal from Burning Star No. 2 Mine and the feed to Run 259 was Pittsburgh seam coal from Ireland Mine. The resid from Run 259 was notably more difficult to convert to distillate products, based on Wilsonville operating results. Both runs were carried out with catalyst in both reactors. Both runs operated, for the most part, with the first of the two reactors at a higher temperature than the second reactor. Samples were obtained from three locations in the plant (Figure 1): between the two reactors (Interstage), after the second reactor but before the deasher (2nd Stage Product), and at the vessel used to accumulate different process flows to form the slurry solvent that is recycled back through the system (Recycle). Samples obtained from these different locations during a single run are expected to represent different degrees of coal conversion in the direct liquefaction process. The samples analyzed were the 850°F⁺ distillation resids of these three process streams, and, in some cases, the tetrahydrofuran-soluble portion of the resids.

The analyses performed by CONSOL on the samples include elemental analyses, proton NMR (and classification of the proton signal into defined groups), and determination of phenolic -OH by Fourier transform infrared spectroscopy (FTIR). Pyrolysis and subsequent detection and analysis of the pyrolysate by thermogravimetric (TG)-FTIR, fluorescence microscopy, reflectance microscopy, field ionization mass spectrometry (FIMS), and various separation techniques, including liquid chromatography were performed by Advanced Fuel Research,⁷ University of Kentucky,⁴ The Pennsylvania State University,³ SRI International,⁵ and Virginia Polytechnic and State University,² respectively.

Table 3 presents the elemental analyses of the six composite resid samples and the parent coals. It is readily apparent that the hydrogen content is increased and the heteroatom content is decreased in the resid as the coal slurry proceeds through the liquefaction process. Also given in Table 3 are the phenolic -OH contents of the tetrahydrofuran (THF)-soluble portion of each resid. Figure 2 shows that the phenolic -OH contents, determined by FTIR, correlate relatively well with the yield of the most polar liquid chromatography fraction of the THF-soluble portion of resids.² The data presented in Figure 2 were obtained from a number of resids obtained from different liquefaction runs made at different facilities, including Runs 257 and 259 made at Wilsonville.

The TG-FTIR results, presented in Table 2, show a reduction in gas make in the pyrolysis of the resids with a corresponding increase in tar yield as the coal is converted in the liquefaction system. The remaining ~2 to ~10% of the resid, not accounted for in these analyses, is converted to additional gases (NH₃, COS) and light hydrocarbons, such as C₂H₄ and benzene. It is notable that the resids produced in the Illinois No. 6 coal run generate a much larger proportion of these volatile materials and more tar than the resids produced from the Pittsburgh seam coal resid. The char yields from the distillation resids correlate with the phenolic -OH content of the THF-soluble portion of the resid, which, as discussed above, correlates to the very polar material found in the resid.

The proton NMR data for the THF-soluble portions of the resids (Table 3) are divided into five spectral regions corresponding to five proton types. These types are condensed aromatics, uncondensed aromatics, alpha protons, beta protons, and gamma protons. The condensed aromatic component of the Run 257 resids decreases from interstage to second-stage product samples and is relatively unchanged in the recycle stream by partial deashing. The increase in aromaticity from recycle to interstage samples comes about from the addition of fresh feed coal to the slurry which is then liquefied in the first reactor. The conversion of the 850°F⁺ resid in each stage of the liquefaction process is not the same; it was approximately two times greater in the first stage than in the second stage for Run 257, and about 1.5 times greater in the first stage than the second stage in Run 259. Nonetheless, it is concluded that for Run 257, the aromatic coal structure is broken down in the first stage of the liquefaction system with little additional change of aromaticity in the second reactor. The liquefaction process conditions in Run 259 were more severe than in Run 257 (higher temperature, lower space velocity) and the rejection of resid in the deasher was lower. This accounts for the total aromaticity being higher in the Run 259 samples. However, within Run 259, an interesting trend is seen. The percent of condensed aromatic protons decreases and that of the uncondensed aromatic materials increases sequentially from the interstage to second stage product to recycle resid. This indicates that the process stream (which is mostly resid) is being converted to less-condensed aromatic moieties, but the unconverted resid is not being saturated. This is supported by a number of other analyses. For example, total volatile material of the resids (100% char) determined from the TG-FTIR experiment is essentially the same as the percentage of uncondensed aromatic protons for each sample from Run 257. However, for the Run 259 samples, there is

a large increase observed for total volatiles and uncondensed aromatic protons in the recycle sample.

Microscopy proved to be a useful technique in the examination of the resids, which are solid at room temperature. It was possible to distinguish different petrographic components in the samples that are related to the extent that the coal slurry had reacted. Point counts and mean random reflectance measurement were made of three components: the high-reflecting vitroplast, the partially reacted vitrinite, and the low-reflecting vitroplast. Values for the interstage and recycle materials in this example data set are given in Table 4. The concentration of low-reflecting vitroplast is higher for the interstage samples than the recycle samples in both Runs 257 and 259. However, for the recycle samples, its concentration is considerably lower in Run 259 than in Run 257. This indicates that across the second stage reactor and deasher, the Pittsburgh coal resid is less upgraded than the Illinois coal-derived materials, and may, in fact, be undergoing retrogressive reactions. This supports the NMR results described above.

Fluorescence microscopy^{6,11} provides a great deal of qualitative information and some quantifiable values including the wavelength of maximum fluorescence (L_{max}) and the fluorescence intensity at L_{max} . It is possible to relate the intensity and the wavelength at L_{max} to the relative degree of aromaticity, and thus to the relative reactivity of the material; the lower the intensity and the longer the wavelength, the higher the aromatic concentration and therefore the lower the reactivity. Resids from Run 257 were found to contain two distinct populations; values of L_{max} and intensity are given in Table 5 for both. Comparison of samples from Run 257 (either population) and Run 259 (Table 5) shows the intensity of the Run 259 interstage sample is relatively low and the L_{max} is high (approaching 700nm). This suggests that the interstage resid from Run 259 is comprised of a more-condensed aromatic structure than the Illinois No. 6 interstage resid and it is thus inferred to be less reactive. The recycle resid samples follow the same trend; the Run 259 sample is also more aromatic and is inferred to be less reactive. Another quantifiable value is the quotient of the fluorescence intensities measured at 700nm (red) and 525nm (green). These red:green quotients (Q) can be used to assess the variability of the fluorescence properties within a heterogeneous sample. A shift to longer wavelengths (red) indicates a more extended pi-bond conjugation or a larger proportion of condensed aromatics. The red:green quotients usually are reported as histograms. Figure 3 shows the histograms for the Runs 257 and 259 interstage and recycle resid samples. The Run 259 samples exhibit much higher proportion of the material at higher Q values than the Run 257 samples. This is consistent with the ¹H-NMR data where ~20% of all protons are aromatic in the Run 257 recycle sample and ~32% are aromatic in the Run 259 recycle sample. Across the second-stage reactor (and including the part of the process stream that has been deashed), there is a considerable shift of the fluorescence of the material to the green (or shorter wavelength, lower aromaticity) in Run 257, but not in Run 259. This may help explain the greater propensity of the Run 259 resids to form char in the TG-FTIR experiments.

FIMS data and their interpretation for these samples have been presented elsewhere.¹² Because of a distinct bimodality, the FIMS profiles of the distillation resids were deconvoluted into two overlapping components, A and B. Component A represents a molecular weight (m/e) range centered at approximately 350 Da, component B is centered around 600 Da. The relative weight fractions of A and B were used to compare the resid samples. Table 6 presents the weight percent of component A for each of the six samples obtained from both the even- and odd-mass FIMS profiles. In agreement with the data discussed above, the concentration of component A in the Run 257 resid almost doubles as the coal slurry passes through the first-stage reactor indicating that the molecular weight of the resid was

reduced in the first-stage reactor. As discussed above, conversion of the resid in the first-stage reactor was approximately twice that of the second-stage reactor for Run 257, and correspondingly the concentration of component A in the second-stage product sample increases from the interstage sample, but is only about 1.5 times that of the interstage sample. In comparison, Run 259 interstage and second-stage samples are less enriched with lower molecular weight material. The concentration of low molecular weight material decreases across both the first-stage and second-stage reactors. It increases in the recycle sample only after part of the second-stage product stream passes through the deasher where high molecular weight materials are rejected along with the ash.

SUMMARY AND CONCLUSION

To briefly summarize the information presented above; relative to the Illinois No. 6 coal resids, the Pittsburgh seam coal resids are less hydrogenated, higher molecular weight, less fluorescent and they produce fewer volatiles upon pyrolysis. In addition, the Pittsburgh seam coal resids are more phenolic, more aromatic and contain more nitrogen. These characteristics are consistent with the lower observed reactivity of the Pittsburgh seam coal resids, which must have arisen from a combination of the coal and operating conditions. The NMR, FIMS and TG-FTIR data indicate that in Run 257, the upgrading of Illinois No. 6 coal to lower molecular weight, more volatile, less aromatic materials was primarily achieved in the first stage of the two-stage system. Additionally, reflectance microscopy data show that the resid derived from the Illinois No. 6 coal in the first-stage reactor is more upgraded in passing through the second-stage reactor and deasher than the Pittsburgh seam coal first-stage resid. Phenolic -OH determinations made on the THF-soluble portion of the distillation resids correlate with the amount of very polar fraction isolated from the resids by liquid chromatography and also with the char yield from the TG experiments. Fluorescence microscopic examination of the resids leads to inferences of resid reactivity. These inferences are supported by the other data.

PROGRAM IMPLICATIONS FOR PROCESS DEVELOPMENT

It is apparent that a number of analytical methods are required to fully describe process derived resids; however, the trends observed by any one method are generally consistent with the response of the other methods. The implication for process development is that the choice of methodology for analytical use, among these methods which were tested, can be determined by the requirements of the process developer based on such factors as cost, time, or frequency of measurement. Another result of this extensive program is that it is now apparent that a wide variety of analytical techniques are applicable to the analysis of the process-derived resid samples and can be used to both improve our understanding of the fundamental chemistry of these materials and to aid in the advancement of process development.

The analytical methods evaluated in this program have potential to help reduce the costs of coal liquids when used as part of a process development program. Figure 4 shows a condensed summary of the twenty-nine different analytical methods evaluated in the program and highlights the process cost factors on which each has the greatest potential impact. The program was directed at resid characterization methods. Because this resid comprises over 50% of the process streams, and because its conversion is often the kinetically limiting reaction in liquefaction, information on this material will most greatly impact reactor costs by influencing secondary factors such as space velocity, temperature, necessary reactor volume, catalyst loading, etc. In contrast, methods used to investigate the resids can have only minimal impact on product quality costs. Although, by understanding better the reactivity of the resid, we may have a better control on the costs of improving product quality.

FUTURE DIRECTIONS

Possible future directions for the program include a more detailed evaluation of the techniques identified in Phases I and II as being most promising for reducing process development costs and providing useful information on the fundamental chemistry of the resids. Another avenue of future work is the exploration of the issue of resid reactivity to establish an independent scale whereby coal-derived resids could be compared on an equivalent basis. A third direction for work could entail the use of the large data base accumulated in Phases I and II and any subsequent phases of this program as a learning set for modern computational techniques, such as neural networks or chemometrics. This would provide both a comprehensive analysis of these data as well as an established system which could be used predictively to forecast outcomes from new input data. A fourth direction for the program could include the evaluation of new methods not evaluated previously in the program.

ACKNOWLEDGEMENT

This work was funded by the U.S. Department of Energy under contract No. DE-AC22-89PC89883.

REFERENCES

1. Brandes, S. D.; Winschel, R. A.; Burke, F. P. "The Application of Advanced Analytical Techniques to Direct Coal Liquefaction," Am. Chem. Soc., Div. Fuel Chem. Preprints, 1991, 36(3), 1172.
2. Taylor, L. T.; Hellgeth, J. W.; Sequeira, A. "Coal Liquefaction Process Streams Characterization and Evaluation; Analysis of Coal Liquefaction Process Streams by Chromatographic and Spectroscopic Techniques, Topical Report," DOE/PC 89883-41, January 1992.
3. Mitchell, G.; Davis, A. "Coal Liquefaction Process Streams Characterization and Evaluation; Gold Tube Carbonization and Reflectance Microscopy, Topical Report," DOE/PC 89883-37, December 1991.
4. Rathbone, R. F.; Hower, J. C.; Derbyshire, F. J. "Coal Liquefaction Process Streams Characterization and Evaluation; Novel Analytical Techniques for Coal Liquefaction: Fluorescence Microscopy, Topical Report," DOE/PC 89883-30, October 1991.
5. Malhotra, R.; McMillen, D. F. "Coal Liquefaction Process Streams Characterization and Evaluation; Characterization of Coal Liquids by Field Ionization Mass Spectrometry and Iodotrimethylsilane Derivatization, Topical Report," DOE/PC 89883-39, January 1992.
6. Miknis, F. P. "Coal Liquefaction Process Streams Characterization and Evaluation; Solid-State NMR Characterization of Coal Liquefaction Products, Topical Report," DOE/PC 89883-36, November 1991.
7. Serio, M. A.; Hsisheng, T.; Bassilakis, R.; Solomon, P. R. "Coal Liquefaction Process Streams Characterization and Evaluation; FT-IR Methods for Characterization of Coal Liquefaction Products, Topical Report," DOE/PC 89883-45, April 1992.
8. Green, J. B.; Pearson, C. D.; Young, L. L.; Green, J. A. "Coal Liquefaction Process Streams Characterization and Evaluation; Application of Liquid Chromatographic Separation Methods to THF-Soluble Portions of Integrated Two-Stage Coal Liquefaction Resids, Topical Report," DOE/PC89883-47, May 1992.
9. Winschel, R. A.; Robbins, G. A.; Burke, F. P. "Coal Liquefaction Process Solvent Characterization and Evaluation, Technical Progress Report July 1 through Sept. 30, 1988," DOE/PC 70018-68, July 1989.

10. Winschel, R. A.; Robbins, G. A.; Burke, F. P. "Coal Liquefaction Process Solvent Characterization and Evaluation, Technical Progress Report April 1 through June 30, 1990," DOE/PC 89883-22, July 1991.
11. Rathbone, R. F.; Hower, J. C.; Derbyshire, F. J. "Application of Fluorescence Microscopy to Coal-Derived Resid Characterization," Am. Chem. Soc., Div. Fuel Chem. Preprints, 1991, 36(3), 1164.
12. Malhotra, R.; McMillen, D. F., Huestis, D. L. "Characterization of Coal Liquefaction Resids by Field Ionization Mass Spectrometry: Correlation Spectral Features with Processing Parameters," Am. Chem. Soc., Div. Fuel Chem. Preprints, 1992, 37 (2), 908.

TABLE 1
PARTICIPANTS PROGRAM - PHASE I

<u>Participating Organization</u>	<u>Methods</u>	<u>Principal Investigators</u>
University of Kentucky/Center for Applied Research	Fluorescence Microscopy	F. Derbyshire R. Rathbone
Virginia Polytechnic Institute and State University	SFE SFC Liquid Chromatography-FTIR	L. Taylor
Western Research Institute	Solid State $^1\text{H}/^{13}\text{C}$ -NMR	F. Miknis D. Netzel
The Pennsylvania State University	Reflectance Microscopy Gold Tube Carbonization - Microscopy	A. Davis G. Mitchell
SRI International	FIMS Oxygen Speciation by Derivatization	R. Malhotra D. McMillen
Advanced Fuel Research	FTIR TG-FTIR	M. Serio
National Institute for Petroleum and Energy Research	Acid/Base/Neutral Separation	R. Anderson J. Green
Battelle, Pacific Northwest Laboratories	FDMS 2-D NMR ^{13}C -NMR HPLC	J. Campbell
Conoco Inc., Petroleum Products Research Division	ASTM Petroleum Inspection Tests	R. Kramer

TABLE 2
PARTICIPANTS PROGRAM - PHASE II

Participating Organization	Methods	Principal Investigators
Lehigh University	^{252}Cf -PDMS	J. Larsen
University of Pittsburgh	UV Resonance Raman Spectroscopy	S. Asher
University of Kentucky	XANES (S speciation)	G. Huffman
University of Chicago	Oxygen Derivatization/ ^{13}C -NMR	L. Stock
University of Utah	^{13}C -NMR/Structural Description	R. Pugmire M. Solum
Vander Sande Associates	Scanning Transmission Electron Microscopy/EDX Spectroscopy	J. Vander Sande
Iowa State University	Phospholane Derivatization/ ^{31}P -NMR	J. Verkade
West Virginia University	ESR/TGA	M. Seehra M. Ibrahim

TABLE 3
ELEMENTAL ANALYSES AND PHENOLIC -OH CONTENTS OF 850°F⁺
DISTILLATION RESIDS AND PARENT COALS^{9,10}

	Run 257				Run 259			
	Feed Coal	Inter-stage Resid	2nd Stage Resid	Recycle Resid	Feed Coal	Inter-stage Resid	2nd Stage Resid	Recycle Resid
wt % of 850°F ⁺ Resid in Process Stream	-	81.9	77.5	79.8	-	72.3	67.9	73.1
Ash, wt % as det.	11.76	12.52	13.49	9.28	4.68	8.74	10.21	8.51
C, wt % MAF	79.52	88.05	87.99	88.64	81.24	90.12	90.24	91.01
H, wt % MAF	5.51	7.70	7.87	8.08	5.97	6.19	6.39	6.50
N, wt % MAF	1.53	0.86	0.77	0.78	1.37	1.15	1.05	1.04
S, wt % MAF	3.68	1.34	1.20	0.79	3.28	1.50	1.49	1.25
O, wt % (by diff) MAF	9.58	2.05	2.16	1.71	8.07	1.04	0.83	0.20
Phenolic -OH, meq/g ^(a)	-	0.68	0.57	0.50	-	0.92	0.70	0.69

(a) determined on the THF-soluble portion of the resid

TABLE 4
TG-FTIR ANALYSES OF 850°F⁺ DISTILLATION RESIDS⁷

TG Yield, wt % daf	Run 257			Run 259		
	Interstage	2nd Stage	Recycle	Interstage	2nd Stage	Recycle
Tar	70.48	69.90	73.49	65.00	65.56	67.07
Gas ^(a)	4.85	4.32	3.71	5.59	3.89	3.61
Char	17.50	15.88	14.15	27.80	28.39	22.88
Unaccounted	7.17	9.90	8.65	1.61	2.16	6.44

(a) Gas = CH₄+CO+CO₂+SO₂

TABLE 5
PROTON NMR ANALYSES OF THF-SOLUBLE PORTION OF 850°F⁺ RESIDS^{9,10}

Proton Type (wt %)	Run 257			Run 259		
	Interstage	2nd Stage	Recycle	Interstage	2nd Stage	Recycle
Condensed Aromatic	18.1	16.9	16.8	30.7	27.8	26.1
Uncondensed Aromatic	3.7	3.4	3.1	2.6	3.8	5.4
Alpha	28.8	28.6	28.0	31.1	30.8	28.3
Beta	39.1	40.5	41.4	27.2	28.9	30.4
Gamma	10.4	10.7	10.6	8.4	8.7	10.8

TABLE 6
NORMALIZED CONCENTRATIONS OF PETROGRAPHIC COMPONENTS^(a)
OF 850°F⁺ DISTILLATION RESIDS³

Component, %	Run 257		Run 259	
	Interstage	Recycle	Interstage	Recycle
Low-Reflecting Vitroplast	78.0	73.5	79.0	63.5
Partially Reacted Vitrinite ^(b)	0.5	0.0	0.5	0.5
High-Reflecting Vitroplast	21.5	26.5	20.0	36.0

(a) 200 reflectance measurements made on each sample

(b) unreacted coal

TABLE 7
WAVELENGTH AND INTENSITY OF MAXIMUM FLUORESCENCE
OF 850°F⁺ DISTILLATION RESIDS⁴

	Run 257		Run 259	
	Interstage	Recycle	Interstage	Recycle
Fluorescence Spectrum Maximum, L_{max} , nm	646 ^(a) /604 ^(b)	633 ^(a) /585 ^(b)	696	696
Intensity at L_{max} , counts	6714/12666	9284/32108	6658	8497

(a) Population 1

(b) Population 2

TABLE 8
wt % COMPONENT A OF 850°F⁺ RESIDS
FROM EVEN- AND ODD-MASS FIMS PROFILES⁵

Weight %	Run 257			Run 259		
	Interstage	2nd Stage	Recycle	Interstage	2nd Stage	Recycle
A Even	22.4	32.0	13.1	13.7	9.2	18.5
A Odd	7.9	12.9	4.3	4.0	2.2	6.3

Figure 1. Simplified Flow Scheme Integrated Two-Stage
Direct Coal Liquefaction.

Figure 2. Phenolic -OH Concentration vs Yield of Liquid Chromatography Polar Fraction (F4).²

Figure 3. Red:Green Quotient Histograms for Wilsonville Runs 257 and 259 Resids.⁴

Figure 4. Potential Impacts of Phase I and II Analytical Methods on Direct Liquefaction Cost Factors.

END

**DATE
FILMED**

3 / 17 / 93