WSRC-RP-92-1030

LATE WASHING EFFICIENCY (U)

WSRC-RP--92-1030

DE93 006568

by M. F. Morrissey

Westinghouse Savannah River Company
Savannah River Site
Aiken, South Carolina 29808

Other Authors:

This paper was prepared in connection with work done under Contract No. DE-AC09-89SR18035 with the U. S. Department of Energy. By acceptance of this paper, the publisher and/or recipient acknowledges the U. S. Government's right to retain a nonexclusive, royalty-free license in and to any copyright covering this paper, along with the right to reproduce and to authorize others to reproduce all or part of the copyrighted paper.

MASTER

ch-2
DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

This report has been reproduced directly from the best available copy.

Available to DOE and DOE contractors from the Office of Scientific and Technical Information, P.O. Box 62, Oak Ridge, TN 37831; prices available from (615) 576-8401, FTS 626-8401.

Available to the public from the National Technical Information Service, U.S. Department of Commerce, 5285 Port Royal Rd., Springfield, VA 22161.

Westinghouse Savannah River Company
Savannah River Technology Center

WSRC-RP-92-1030

Keywords: Filters, Cross Flow, Late Washing

Retention: Lifetime

Page 1 of 5

CC: W. L. Tamosaitis, 773-A
E. W. Holtzscheiter, 773-A
M. D. Boersma, 704-T
L. F. Landon, 704-T
J. C. Marek, 704-T
L. M. Nelson, 773-43A
L. O. Dworyanyn, 779-2A
D. J. McCabe, 676-T
M. L. Meyer, 676-1T
D. N. Burns, 676-T
W. J. Vetsch, 704-S
SRL Records

To: D. L. Fish, 773-A

August 31st, 1992

From: M. F. Morrissey, 676-T *M. F. Morrissey*

Late Washing Efficiency (U)

1.0 Abstract

Interim Waste Technology has demonstrated the Late Washing concept on the Experimental Laboratory Filter (ELF) at TNX. In two tests, washing reduced the $[\text{NO}_2^-]$ from 0.08 M to approximately 0.01 M on slurries with 2 year equivalent radiation exposures and 9.5 wt. % solids. For both washes, the $[\text{NO}_2^-]$ decreased at rates near theoretical for a constant volume stirred vessel, indicating approximately 100 % washing efficiency. Permeate flux was greater than 0.05 gpm/ft² for both washes at a transmembrane pressure of 50 psi and flow velocity of 9 ft/sec.

2.0 Introduction

The In-Tank Precipitation (ITP) Process decontaminates radioactive waste in Tank 48 by precipitating Cs^{137} with tetraphenylborate and adsorbing Sr^{90} with sodium titanate. Concentrated potassium tetraphenylborate/sodium titanate slurry is then transferred to Tank 49 for storage. Waste Management will eventually transfer the slurry to the Defense Waste Processing Facility (DWPF) for vitrification, but while waste remains in Tank 49, the $[\text{NO}_2^-]$ must remain high to inhibit corrosion. Waste with high $[\text{NO}_2^-]$ complicates DWPF processes. To avoid complications, the $[\text{NO}_2^-]$ must be reduced to 0.01M.

The Late Washing Process has been proposed to reduce the $[\text{NO}_2^-]$ to ≤ 0.01 M. In Late Washing, the KTPB slurry will be washed to reduce the $[\text{NO}_2^-]$. Fresh wash water dilutes the nitrite and cross flow filtration removes the wash water after it has reached ambient $[\text{NO}_2^-]$.

Interim Waste Technology has demonstrated the Late Washing Process with the ELF, a bench scale

filtration system (See Attachment 1). Flux tests have been conducted with irradiated slurries to evaluate filter performance at various operating conditions. This report examines the washing efficiency by evaluating permeate flux and water usage.

3.0 Experimental

3.1 Equipment

The ELF contains a single sintered stainless steel filter. Late Washing is being designed to use an ITP type Filter. The ITP filter compares with the ELF filter in the following ways:

1. ELF filter internal diameter = 3/8 "	ITP filter internal diameter = 5/8 "
2. ELF filter length = 16 7/8 "	ITP filter Length = 10 '
3. The ELF has 1 element/housing	The ITP filter has 144 elements/housing
4. The ELF permeate/backpulse line is in the center of the housing.
The ITP permeate/backpulse line is near the filter exhaust.	
5. ELF filter surface area = 0.138 ft ²	ITP filter surface area = 230 ft ²
6. Both ELF & ITP filters are 0.5 μ Mott HyPulse filters.	
7 The ELF uses a Wilden M2 double diaphragm pump with Blacoh surge suppressor.
ITP and probably Late Washing will use low shear centrifugal pumps.	

Based on surface area the ELF is a 1/1700 model of the ITP filter.

3.2 Cleaning

Performing experiments reproducibly required starting with a clean filter. Recirculating 1.0 wt. % oxalic acid and 1.0 wt. % caustic successfully cleaned the filter to original conditions. Testing deionized water flux prior to every experiment verified cleanliness. A graph demonstrating the clean water fluxes for Experiments A - D appears in Attachment 2.

3.3 Simulant

DWPT prepared irradiated and non irradiated slurries. The composition is shown in Attachment 3. Non irradiated slurries contained 500 ppm SURFYNOL®, because non irradiated KTPB slurries foam when recirculated in the ELF. Furthermore non irradiated slurries stratify after sufficient agitation. After precipitation, the slurry will appear white, opaque and uniform, but after pumping or agitating the slurry stratifies. KTPB foam forms on top, sodium titanate falls to the bottom and a clear salt solution remains in the center. Stratified slurry proves more filterable if the pump draws from the clear solution and less filterable if the pump draws from the bottom or top where the solids loading is high. Adding SURFYNOL® to non irradiated slurries decreases foaming and stratification.

To irradiate slurries, DWPT exposed them to 3×10^8 rad in a ⁶⁰Co well. This exposure is equivalent to 2 years self irradiation during storage of slurry containing 36 Ci ¹³⁷Cs/gallon. Slurries with 2 year exposure and no reprecipitation did not require SURFYNOL®.

3.4 Flux Tests

The filter's potential for separating spent wash water from irradiated slurry was evaluated by

filtering non irradiated and irradiated slurries. The data on non irradiated slurries provided a baseline, while the irradiated slurries represented Late Wash feed. Repeating experiments determined reproducibility.

Transmembrane pressure, flow velocity and slurry composition affect filter performance. To evaluate these parameters several experiments were conducted (Experiments A, B, C, D & E). Experiments A & E utilized non irradiated slurries and Experiments B, C & D utilized irradiated slurries. Each experiment's design was a center point with eight points located around the center of an ellipse (Attachment 4). One hour tests were conducted at each point, manually backpulsing for approximately one second every fifteen minutes with 90 psi air. The design sequence appears in Attachment 5. Each experiment began at the center point, 6 fps & 30 psi, then tested four points on the ellipse followed by a repetition of the center point. The next four tests occurred at the remaining points on the ellipse and the final test occurred at the center point. All experiments used the same test sequence.

The first eleven tests examined clean filter performance. Previous studies with freshly precipitated KTPB slurry have shown that allowing KTPB slurry to remain static for as little as 1 hour decreases filter performance¹. IWT refers to this phenomenon as "static membrane formation". The potential for static membrane formation in irradiated slurries was evaluated by allowing slurry to remain static in the ELF for two hours and then repeating the eleven tests. A change in flux would indicate static membrane formation. After the second eleven tests, IWT allowed the slurry to remain static for an additional twenty four hours and then ran another eleven tests.

The flux tests were operated in total recycle, so all concentrations remained constant. Pumping the slurry exposes it to shear and backpulsing with air contributes to foaming, each of which decreases permeate flux.

3.5 Slurry Washing

For a perfectly mixed constant volume washing the water volume required to reduce $[\text{NO}_2^-]$ to 0.01 M is given by the following equation:

$$V_{\text{wash water}} = V_{\text{aqueous}} \cdot \ln([\text{NO}_2^-]_{\text{initial}} / 0.01 \text{ M})$$

$$V_{\text{aqueous}} = \text{slurry's aqueous volume}$$

V_{aqueous} and $[\text{NO}_2^-]_{\text{initial}}$ were measured and $V_{\text{wash water}}$ was calculated. Slurry was washed by connecting the permeate line to the spent wash water vessel and then adding wash water to the process vessel at the rate the filter generated spent wash water. The process vessel was agitated during the first washing, but not the second. Maintaining a constant liquid level in the process vessel verified that the spent wash water left at the rate fresh wash water entered.

Before beginning each wash the $[\text{NO}_2^-]$ was increased to approximately 0.08 M. The wash water volumes required to decrease $[\text{NO}_2^-]$ from 0.08 M to 0.01 M (in 0.01 M increments) were calculated. The permeate was analyzed after adding these volumes to evaluate the washing efficiency.

3.6 Results and Conclusions

The Late Washing Demonstration results appear in the Late Washing Demonstration Datasheet and on the Experiment C Graph (Attachments 6 & 7). The Washing efficiency was close to theoretical. Washing occurred at room temperature, approximately 50 psi transmembrane pressure and

approximately 9 fps flow velocity. After Experiment C recirculating 1.0 wt. % oxalic acid and 1 wt. % caustic were used to clean the filter back to original condition.

The second washing (Experiment D) did not use an agitator. Turnover in the Process Vessel was greater than 2 vessel volumes/minute and researchers predicted this rapid turnover would provide sufficient agitation. The slurry did not separate into phases during the wash. The second wash was begun by adding nitrite to increase the $[\text{NO}_2^-]$ to 0.08 M. The analytical results showed only 0.06 M, this is probably because not all the nitrite had dissolved when the sample was pulled. The Experiment D Graph (Attachment 8) demonstrates $[\text{NO}_2^-]$ was less than theoretical during the first three samples, probably because nitrite was not dissolved at this time. At the end of the wash the $[\text{NO}_2^-]$ was approximately theoretical. Experiment D indicates the importance of thorough agitation.

Flux tests were designed to investigate the potential for static membrane formation. The irradiated slurries used in experiments C and D did not display significant static membrane formation during the flux tests.

3.7 Error Margins

The ELF uses a Wilden M2 diaphragm pump, which causes pressures and flows to fluctuate. The surge suppressor suppresses, but does not eliminate fluctuation. Fluctuating pressure and flow make reading pressure and flow gauges difficult. Readings will have the following error margins:

<u>Measurement</u>	<u>Measuring Device</u>	<u>Typical Value</u>	<u>Margin of Error</u>
Concentrate Flow	Flow Meter 1	1.0 - 10.0 gpm	± 0.1 gpm
Permeate Flow (High Flow)	Flow Meter 2	0.1 - 3.0 gpm	± 0.1 gpm
Permeate Flow (Low Flow)	Flow Meter 3	10 - 250 ml/min	± 5 ml/min
Feed Pressure	Pressure Gauge 2	15 - 100 psi	± 4 psi
Concentrate Pressure	Pressure Gauge 3	15 - 100 psi	± 3 psi
Permeate Pressure	Pressure Gauge 5	0 - 75 psi	± 2 psi
Backpulse Duration	Stop watch	1 - 4 seconds	± 0.5 seconds
Backpulse Frequency	Stop watch	5 - 20 minutes	± 0.5 seconds

4.0 Attachments

- 4.0.1 Attachment 1 - Experimental Laboratory Filter Sketch
- 4.0.2 Attachment 2 - Water Flux Tests A - D Graph
- 4.0.3 Attachment 3 - Slurry Formula
- 4.0.4 Attachment 4 - Late Washing Flux Test Design
- 4.0.5 Attachment 5 - Late Washing Flux Test Design Datasheet
- 4.0.6 Attachment 6 - Late Washing Demonstration Datasheet
- 4.0.7 Attachment 7 - Late Washing Demonstration - Experiment C Graph
- 4.0.8 Attachment 8 - Late Washing Demonstration - Experiment D Graph

5.0 References

5.0.1 Reference 1 - M. F. Morrissey, ITP Filter Performance, IWT-LWT-91-107, 10/7/92.

Experimental Laboratory Filter
Interim Waste Technology
Savannah River Technology Center

Attachment 1

Water Fluxes C & D *Attachment 2*

Attachment 3

DWPT first blended the salt solution presented below.

Salt Solution					
Compound	Mass Added	Molecular Weight	Moles	Molarity	Concentration
H ₂ O	6,178.35 grams	18.00 g/mol	343.2417 moles	53.9784 M	952,560 ppm
K ₂ CO ₃	3.45 grams	138.20 g/mol	0.0250 moles	0.0039 M	532 ppm
KNO ₂	268.95 grams	85.10 g/mol	3.1605 moles	0.4970 M	41,466 ppm
CsNO ₃	6.72 grams	194.91 g/mol	0.0345 moles	0.0054 M	1,036 ppm
KNO ₃	25.02 grams	101.10 g/mol	0.2475 moles	0.0389 M	3,858 ppm
KCl	0.24 grams	74.55 g/mol	0.0032 moles	0.0005 M	37 ppm
KF	0.13 grams	58.10 g/mol	0.0022 moles	0.0004 M	20 ppm
Na ₂ SO ₄	2.87 grams	141.98 g/mol	0.0202 moles	0.0032 M	442 ppm
K ₂ CrO ₄	0.09 grams	194.19 g/mol	0.0005 moles	0.0001 M	14 ppm
Na ₂ SiO ₃ ·9H ₂ O	0.16 grams	284.07 g/mol	0.0006 moles	0.0001 M	25 ppm
K ₂ MnO ₄	0.01 grams	197.13 g/mol	0.0001 moles	0.0000 M	2 ppm
C ₂ H ₅ B(OH) ₂	0.06 grams	94.00 g/mol	0.0006 moles	0.0001 M	9 ppm

Total Mass 6,486.05 grams

Total Volume 6.359 liters

DWPT then added salt solution to NaTPB solution, sodium titante slurry & diphenyl mercury.

Slurry					
Compound	Mass Added	Molecular Weight	Moles	Molarity	Concentration
Salt Solution	3,243.03 grams	N/A	N/A	N/A	N/A
NaTPB Solution	3,534.90 grams	341.79 g/mol	1.7375 moles	0.2532 M	504,986 ppm
NaTi ₂ O ₅ H Slurry	152.50 grams	453.73 g/mol	0.0309 moles	0.0045 M	21,786 ppm
(C ₆ H ₅) ₂ Hg	22.07 grams	478.18 g/mol	0.0462 moles	0.0067 M	3,153 ppm
H ₂ O	47.50 grams	18.00 g/mol	2,6389 moles	0.3845 M	6,786 ppm

Total Mass 7,000.00 grams

Total Volume 6.863 liters

Final Slurry Composition

Compound	Mass Added	Molecular Weight	Moles	Molarity	Concentration
H ₂ O	6,216.22 grams	18.00 g/mol	345.3454 moles	50.3218 M	888,031 ppm
Na	41.13 grams	22.99 g/mol	1.7891 moles	0.2607 M	5,876 ppm
K	66.75 grams	39.10 g/mol	1.7072 moles	0.2488 M	9,536 ppm
CO ₃	0.75 grams	60.00 g/mol	0.0125 moles	0.0018 M	107 ppm
NO ₂	47.41 grams	30.00 g/mol	1.5802 moles	0.2303 M	6,772 ppm
NO ₃	6.48 grams	46.00 g/mol	0.1410 moles	0.0205 M	926 ppm
Cl	0.06 grams	35.45 g/mol	0.0016 moles	0.0002 M	8 ppm
F	0.02 grams	20.00 g/mol	0.0011 moles	0.0002 M	3 ppm
SO ₄	0.97 grams	96.06 g/mol	0.0101 moles	0.0015 M	139 ppm
CrO ₄	0.03 grams	116.00 g/mol	0.0002 moles	0.0000 M	4 ppm
SiO ₃	0.02 grams	76.09 g/mol	0.0003 moles	0.0000 M	3 ppm
MnO ₄	0.00 grams	118.94 g/mol	0.0000 moles	0.0000 M	0 ppm
C ₂ H ₅ B(OH) ₂	0.03 grams	94.00 g/mol	0.0003 moles	0.0000 M	4 ppm
TPB	593.86 grams	341.79 g/mol	1.7375 moles	0.2532 M	84,838 ppm
Ti ₂ O ₅ H	5.46 grams	176.80 g/mol	0.0028 moles	0.0004 M	779 ppm
(C ₆ H ₅) ₂ Hg	22.07 grams	478.18 g/mol	0.0462 moles	0.0067 M	3,153 ppm

Total Mass 7,000.00 grams

Total Volume 6.863 liters

Flux Test Design *Attachment 4*

Attachment 5

Late Washing Flux Test Design Datasheet

Test	F conc	V flow	P feed	T	P conc	F perm	P perm	P trans	P flux
1	2.06 gpm	6 fps	30 psi						
2	2.75 gpm	8 fps	40 psi						
3	0.69 gpm	2 fps	30 psi						
4	2.06 gpm	6 fps	15 psi						
5	2.75 gpm	8 fps	20 psi						
6	2.06 gpm	6 fps	30 psi						
7	1.38 gpm	4 fps	40 psi						
8	2.06 gpm	6 fps	45 psi						
9	3.44 gpm	10 fps	30 psi						
10	1.38 gpm	4 fps	20 psi						
11	2.06 gpm	6 fps	30 psi						

2 Hour Static Interval

Test	F conc	V flow	P feed	T	P conc	F perm	P perm	P trans	P flux
12	2.06 gpm	6 fps	30 psi						
13	2.75 gpm	8 fps	40 psi						
14	0.69 gpm	2 fps	30 psi						
15	2.06 gpm	6 fps	15 psi						
16	2.75 gpm	8 fps	20 psi						
17	2.06 gpm	6 fps	30 psi						
18	1.38 gpm	4 fps	40 psi						
19	2.06 gpm	6 fps	45 psi						
20	3.44 gpm	10 fps	30 psi						
21	1.38 gpm	4 fps	20 psi						
22	2.06 gpm	6 fps	30 psi						

24 Hour Static Interval

Test	F conc	V flow	P feed	T	P conc	F perm	P perm	P trans	P flux
23	2.06 gpm	6 fps	30 psi						
24	2.75 gpm	8 fps	40 psi						
25	0.69 gpm	2 fps	30 psi						
26	2.06 gpm	6 fps	15 psi						
27	2.75 gpm	8 fps	20 psi						
28	2.06 gpm	6 fps	30 psi						
29	1.38 gpm	4 fps	40 psi						
30	2.06 gpm	6 fps	45 psi						
31	3.44 gpm	10 fps	30 psi						
32	1.38 gpm	4 fps	20 psi						
33	2.06 gpm	6 fps	30 psi						

Late Washing Demonstration Datasheet

Test: Washing Experiment C Slurry				Filter: C	Date: 4/16/92		BP Frequency = 15 minutes		BP Duration = 1 second	
M. vessel	M. v. & s.	M. slurry	M. eq.	Y. sd.	INO2Is	M. NaNO2	Solids/Slurry	INO2II	P. trans	Flux perm
951.3 g	7833.0 g	6871.7 g	6209.3 g	6.209 l	0.0830 M	32.65 g	0.0964	0.0068 M	48.1 psi	0.0528 gpm/11.2
Sample	V. Wash. Water	Time	P. feed	Temperature	P. perm	F. perm	P. conc	F. conc	INO2-I ppm	INO2-I Ms
PI	0.000 l	12:33	53 psi	75 °F	0 psi	11.0 ml/min	45 psi	3.96 gpm	3818 ppm	0.0830 M
SWW(0.07)	1.058 l	12:38	58 psi	76 °F	0 psi	10.0 ml/min	50 psi	3.53 gpm	3216 ppm	0.0699 M
SWW(0.06)	0.957 l	12:55	58 psi	77 °F	0 psi	7.0 ml/min	50 psi	3.15 gpm	2410 ppm	0.0611 M
SWW(0.05)	1.132 l	13:25	58 psi	77 °F	0 psi	11.0 ml/min	50 psi	3.75 gpm	2316 ppm	0.0503 M
SWW(0.04)	1.386 l	14:07	58 psi	79 °F	0 psi	7.5 ml/min	50 psi	3.66 gpm	1852 ppm	0.0403 M
SWW(0.03)	1.786 l	14:44	58 psi	79 °F	0 psi	7.0 ml/min	50 psi	3.50 gpm	1502 ppm	0.0327 M
SWW(0.02)	2.518 l	16:06	58 psi	80 °F	0 psi	7.0 ml/min	50 psi	3.45 gpm	1037 ppm	0.0225 M
SWW(0.01)	4.304 l	19:26	58 psi	79 °F	0 psi	5.0 ml/min	50 psi	2.75 gpm	509 ppm	0.0111 M
SWW(0.01B)	0.600 l	21:15	58 psi	79 °F	0 psi	5.0 ml/min	50 psi	2.60 gpm	451 ppm	0.0098 M
Total WW		Total Time	P. feed	Temperature	P. perm	F. perm	P. conc	F. conc	Y. flow	Actual Perm
13.740 l		517 min	51.7 psi	70.1 °F	0 psi	7.1 ml/min	44.5 psi	3.04 gpm	8.87 fps	27.6 ml/min

BP Duration = 1 second

M. vessel	M. v. #	M. slurry	M. eq	Y. eq	INO21s	M. NaNO2	Solids/slurry	INO21	P. trans	Flux perm
961.3 g	7413.0 g	6451.7 g	5829.8 g	5.830 l	0.0600 M	19.87 g	0.0964	0.0106 M	55.4 psi	0.0635 gpm/ft ²

Sample	V. Wash	Water	Time	P. feed	Temperature	P. perm	F. perm	P. conc	F. conc	INO2-1	INO2-1
FI	0.000 l		0:00	47 psi	81 °F	0 psi	13.0 ml/min	40 psi	2.43 gpm	2760 ppm	0.0600 M
SWW(0.05)	1.063 l		0:29	47 psi	81 °F	0 psi	13.0 ml/min	40 psi	2.43 gpm	2714 ppm	0.0590 M
SWW(0.04)	1.301 l		1:07	50 psi	80 °F	0 psi	8.0 ml/min	43 psi	2.45 gpm	2254 ppm	0.0490 M
SWW(0.03)	1.677 l		2:00	54 psi	79 °F	0 psi	10.0 ml/min	48 psi	1.65 gpm	1794 ppm	0.0390 M
SWW(0.02)	2.364 l		3:20	55 psi	77 °F	0 psi	12.0 ml/min	48 psi	1.62 gpm	1228 ppm	0.0267 M
SWW(0.01)	4.041 l		6:05	55 psi	77 °F	0 psi	5.0 ml/min	45 psi	2.40 gpm	690 ppm	0.0150 M
SWW(0.01B)	0.600 l		6:30	55 psi	76 °F	0 psi	7.0 ml/min	45 psi	1.76 gpm	644 ppm	0.0140 M
SWW(0.01C)	0.600 l		6:55	55 psi	75 °F	0 psi	8.0 ml/min	48 psi	1.92 gpm	552 ppm	0.0120 M
Total WW			Total Time	P. feed	Temperature	P. perm	F. perm	P. conc	F. conc	P. flow	Actual Perm
11.646 l			415 min	50.7 psi	80.4 °F	0 psi	10.0 ml/min	51.0 psi	2.38 gpm	5.05 fpm	33.1 ml/min

Late Washing Demonstration - Experiment C

Late Washing Demonstration - Experiment D

END

DATE
FILMED

4 129193